

# The listingsutf8 package

Heiko Oberdiek  
<heiko.oberdiek at gmail.com>

2011/11/10 v1.2

## Abstract

Package listings does not support files with multi-byte encodings such as UTF-8. In case of `\lstinputlisting` a simple workaround is possible if an one-byte encoding exists that the file can be converted to. Also  $\epsilon$ -TeX and pdfTeX regardless of its mode are required.

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	User interface . . . . .	2
1.2	Future . . . . .	2
<b>2</b>	<b>Implementation</b>	<b>2</b>
2.1	Catcodes and identification . . . . .	2
2.2	Package options . . . . .	3
2.3	Check prerequisites . . . . .	4
2.4	Add support for UTF-8 . . . . .	4
2.4.1	Conversion . . . . .	4
2.4.2	Convert CR/LF pairs to LF . . . . .	5
2.4.3	Patch <code>\lst@InputListing</code> . . . . .	5
<b>3</b>	<b>Test</b>	<b>5</b>
3.1	Catcode checks for loading . . . . .	5
3.2	Test example for latin1 . . . . .	6
<b>4</b>	<b>Installation</b>	<b>7</b>
4.1	Download . . . . .	7
4.2	Bundle installation . . . . .	7
4.3	Package installation . . . . .	7
4.4	Refresh file name databases . . . . .	8
4.5	Some details for the interested . . . . .	8
<b>5</b>	<b>Catalogue</b>	<b>9</b>
<b>6</b>	<b>References</b>	<b>9</b>
<b>7</b>	<b>History</b>	<b>9</b>
	[2007/10/22 v1.0] . . . . .	9
	[2007/11/11 v1.1] . . . . .	9
	[2011/11/10 v1.2] . . . . .	10
<b>8</b>	<b>Index</b>	<b>10</b>

# 1 Documentation

## 1.1 User interface

Load this package after or instead of package listings [2]. The package does not define own options and passes given options to package listings.

The syntax of package listings' key `inputencoding` is extended:

```
inputencoding=utf8/⟨one-byte-encoding⟩  
Example: inputencoding=utf8/latin1
```

That means the file is encoded in UTF-8 and can be converted to the given `⟨one-byte-encoding⟩`. The available encodings for `⟨one-byte-encoding⟩` are listed in section “1.2 Supported encodings” of package `stringenc`'s documentation [3]. Of course, the encoding must encode its characters with one byte exactly. This excludes the unicode encodings (`utf8`, `utf16`, ...).

Only `\lstinputlisting` is supported by the syntax extension of key `inputencoding`.

Internally package `listingsutf8` reads the file as binary file via primitives of pdfTeX (`\pdffiledump`). Then the file contents is converted as string using package `stringenc` and finally the string is read as virtual file by  $\varepsilon$ -TeX's `\scantokens`.

## 1.2 Future

Workarounds are not provided for

- `\lstinline`
- Environment `lstlisting`.
- Environments defined by `\lstnewenvironment`.

Perhaps someone will find time to extend package listings with full native support for UTF-8. Then this package would become obsolete.

# 2 Implementation

```
1 ⟨*package⟩
```

## 2.1 Catcodes and identification

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%  
3 \catcode13=5 % ^M  
4 \endlinechar=13 %  
5 \catcode123=1 % {  
6 \catcode125=2 % }  
7 \catcode64=11 % @  
8 \def\x{\endgroup  
9 \expandafter\edef\csname lstU@AtEnd\endcsname{%  
10 \endlinechar=\the\endlinechar\relax  
11 \catcode13=\the\catcode13\relax  
12 \catcode32=\the\catcode32\relax  
13 \catcode35=\the\catcode35\relax  
14 \catcode61=\the\catcode61\relax  
15 \catcode64=\the\catcode64\relax  
16 \catcode123=\the\catcode123\relax  
17 \catcode125=\the\catcode125\relax  
18 }%
```

```

19 }%
20 \x\catcode61\catcode48\catcode32=10\relax%
21 \catcode13=5 % ^^M
22 \endlinechar=13 %
23 \catcode35=6 % #
24 \catcode64=11 % @
25 \catcode123=1 % {
26 \catcode125=2 % }
27 \def\TMP@EnsureCode#1#2{%
28   \edef\lstU@AtEnd{%
29     \lstU@AtEnd
30     \catcode#1=\the\catcode#1\relax
31   }%
32   \catcode#1=#2\relax
33 }
34 \TMP@EnsureCode{10}{12}% ^^J
35 \TMP@EnsureCode{33}{12}% !
36 \TMP@EnsureCode{36}{3}% $
37 \TMP@EnsureCode{38}{4}% &
38 \TMP@EnsureCode{39}{12}% '
39 \TMP@EnsureCode{40}{12}% (
40 \TMP@EnsureCode{41}{12}% )
41 \TMP@EnsureCode{42}{12}% *
42 \TMP@EnsureCode{43}{12}% +
43 \TMP@EnsureCode{44}{12}% ,
44 \TMP@EnsureCode{45}{12}% -
45 \TMP@EnsureCode{46}{12}% .
46 \TMP@EnsureCode{47}{12}% /
47 \TMP@EnsureCode{58}{12}% :
48 \TMP@EnsureCode{60}{12}% <
49 \TMP@EnsureCode{62}{12}% >
50 \TMP@EnsureCode{91}{12}% [
51 \TMP@EnsureCode{93}{12}% ]
52 \TMP@EnsureCode{94}{7}% ^ (superscript)
53 \TMP@EnsureCode{95}{8}% _ (subscript)
54 \TMP@EnsureCode{96}{12}% `
55 \TMP@EnsureCode{124}{12}% |
56 \TMP@EnsureCode{126}{13}% ~ (active)
57 \edef\lstU@AtEnd{\lstU@AtEnd\noexpand\endinput}

```

Package identification.

```

58 \NeedsTeXFormat{LaTeX2e}
59 \ProvidesPackage{listingsutf8}%
60 [2011/11/10 v1.2 Allow UTF-8 in listings input (HO)]

```

## 2.2 Package options

Just pass options to package listings.

```

61 \DeclareOption*{%
62   \PassOptionsToPackage\CurrentOption{listings}%
63 }
64 \ProcessOptions*

```

Key inputencoding was introduced in version 2002/04/01 v1.0 of package listings.

```

65 \RequirePackage{listings}[2002/04/01]

```

Ensure that `\inputencoding` is provided.

```

66 \AtBeginDocument{%
67   \@ifundefined{inputencoding}{%
68     \RequirePackage{inputenc}%

```

```
69 }{}%
70 }
```

## 2.3 Check prerequisites

```
71 \RequirePackage{pdftexcmds}[2011/04/22]
72 \def\lstU@temp#1#2{%
73   \begingroup\expandafter\expandafter\expandafter\endgroup
74   \expandafter\ifx\csname #1\endcsname\relax
75     \PackageWarningNoLine{listingsutf8}{%
76       Package loading is aborted because of missing %
77       \@backslashchar#1.\MessageBreak
78       #2%
79     }%
80   \expandafter\lstU@AtEnd
81   \fi
82 }
83 \lstU@temp{scantokens}{It is provided by e-TeX}%
84 \lstU@temp{pdf@unescapehex}{It is provided by pdfTeX >= 1.30}%
85 \lstU@temp{pdf@filedump}{It is provided by pdfTeX >= 1.30}%
86 \lstU@temp{pdf@filesize}{It is provided by pdfTeX >= 1.30}%
87 \RequirePackage{stringenc}[2010/03/01]
```

## 2.4 Add support for UTF-8

```
\iflstU@utfviii
```

```
88 \newif\iflstU@utfviii
```

```
\lstU@inputenc
```

```
89 \def\lstU@inputenc#1{%
90   \expandafter\lstU@@inputenc#1utf8/utf8/\@nil
91 }
```

```
\lstU@@inputenc
```

```
92 \lst@Key{inputencoding}\relax{%
93   \def\lst@inputenc{#1}%
94   \lstU@inputenc{#1}%
95 }
```

### 2.4.1 Conversion

```
\lstU@input
```

```
96 \def\lstU@input#1{%
97   \iflstU@utfviii
98     \edef\lstU@text{%
99       \pdf@unescapehex{%
100        \pdf@filedump{0}{\pdf@filesize{#1}}{#1}%
101       }%
102     }%
103     \lstU@CRLFtoLF\lstU@text
104     \StringEncodingConvert\lstU@text\lstU@text{utf8}\lst@inputenc
105     \def\lstU@temp{%
106       \scantokens\expandafter{\lstU@text}%
107     }%
108   \else
109     \def\lstU@temp{%
```

```

110     \input{#1}%
111   }%
112   \fi
113   \lstU@temp
114 }

```

## 2.4.2 Convert CR/LF pairs to LF

\lstU@CRLFtoLF

```

115 \begingroup
116   \endlinechar=-1 %
117   \@makeother^^J %
118   \@makeother^^M %
119   \gdef\lstU@CRLFtoLF#1{%
120     \edef#1{%
121       \expandafter\lstU@CRLFtoLF@aux#1^^M^^J\@nil
122     }%
123   }%
124   \gdef\lstU@CRLFtoLF@aux#1^^M^^J#2\@nil{%
125     #1%
126     \ifx\relax#2\relax
127       \@car
128     \fi
129     ^^J%
130     \lstU@CRLFtoLF@aux#2\@nil
131   }%
132 \endgroup %

```

## 2.4.3 Patch \lst@InputListing

```

133 \def\lstU@temp#1\def\lst@next#2#3\@nil{%
134   \def\lst@InputListing##1{%
135     #1%
136     \def\lst@next{\lstU@input{##1}}%
137     #3%
138   }%
139 }
140 \expandafter\lstU@temp\lst@InputListing{#1}\@nil
141 \lstU@AtEnd%
142 </package>

```

# 3 Test

## 3.1 Catcode checks for loading

```

143 (*test1)
144 \NeedsTeXFormat{LaTeX2e}
145 \documentclass{minimal}
146 \makeatletter
147 \def\RestoreCatcodes{}
148 \count@=0 %
149 \loop
150   \edef\RestoreCatcodes{%
151     \RestoreCatcodes
152     \catcode\the\count@=\the\catcode\count@\relax
153   }%
154 \ifnum\count@<255 %

```

```

155 \advance\count@\@ne
156 \repeat
157
158 \def\RangeCatcodeInvalid#1#2{%
159 \count@=#1\relax
160 \loop
161 \catcode\count@=15 %
162 \ifnum\count@<#2\relax
163 \advance\count@\@ne
164 \repeat
165 }
166 \def\Test{%
167 \RangeCatcodeInvalid{0}{47}%
168 \RangeCatcodeInvalid{58}{64}%
169 \RangeCatcodeInvalid{91}{96}%
170 \RangeCatcodeInvalid{123}{127}%
171 \catcode'\@=12 %
172 \catcode'\@=0 %
173 \catcode'\{=1 %
174 \catcode'\}=2 %
175 \catcode'\#=6 %
176 \catcode'\[=12 %
177 \catcode'\]=12 %
178 \catcode'\%=14 %
179 \catcode'\ =10 %
180 \catcode13=5 %
181 \RequirePackage{listingsutf8}[2011/11/10]\relax
182 \RestoreCatcodes
183 }
184 \Test
185 \csname @@end\endcsname
186 \end
187 </test1>

```

### 3.2 Test example for latin1

```

188 (*test2)
189 \NeedsTeXFormat{LaTeX2e}
190 \documentclass{minimal}
191 \usepackage{filecontents}
192 \def\do#1{%
193 \ifx#1\~%
194 \else
195 \noexpand\do\noexpand#1%
196 \fi
197 }
198 \expandafter\let\expandafter\dospecials\expandafter\empty
199 \expandafter\edef\expandafter\dospecials\expandafter{\dospecials}
200 \begin{filecontents*}{ExampleUTF8.java}
201 public class ExampleUTF8 {
202     public static String testString =
203         "Umlauts: " +
204         "\u00c3\u0084\u00c3\u0096\u00c3\u009c\u00c3\u00a4\u00c3\u00b6\u00c3\u00bc\u00c3\u009f";
205     public static void main(String[] args) {
206         System.out.println(testString);
207     }
208 }
209 \end{filecontents*}

```

```

210 \usepackage{listingsutf8}[2011/11/10]
211 \def\Text{%
212   Umlauts: %
213   ^^c3^^84^^c3^^96^^c3^^9c^^c3^^a4^^c3^^b6^^c3^^bc^^c3^^9f%
214 }
215 \begin{document}
216 \lstinputlisting[%
217   language=Java,%
218   inputencoding=utf8/latin1,%
219 ]{ExampleUTF8.java}
220 \end{document}
221 </test2>

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/listingsutf8.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/listingsutf8.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for  $\TeX$  Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain  $\TeX$ :

```
tex listingsutf8.dtx
```

---

<sup>1</sup>[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
listingsutf8.sty      → tex/latex/oberdiek/listingsutf8.sty
listingsutf8.pdf     → doc/latex/oberdiek/listingsutf8.pdf
test/listingsutf8-test1.tex → doc/latex/oberdiek/test/listingsutf8-test1.tex
test/listingsutf8-test2.tex → doc/latex/oberdiek/test/listingsutf8-test2.tex
test/listingsutf8-test3.tex → doc/latex/oberdiek/test/listingsutf8-test3.tex
test/listingsutf8-test4.tex → doc/latex/oberdiek/test/listingsutf8-test4.tex
test/listingsutf8-test5.tex → doc/latex/oberdiek/test/listingsutf8-test5.tex
listingsutf8.dtx     → source/latex/oberdiek/listingsutf8.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 4.4 Refresh file name databases

If your  $\text{T}_{\text{E}}\text{X}$  distribution (`te $\text{T}_{\text{E}}\text{X}$` , `mik $\text{T}_{\text{E}}\text{X}$` , ...) relies on file name databases, you must refresh these. For example, `te $\text{T}_{\text{E}}\text{X}$`  users run `texhash` or `mktextlsr`.

## 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk listingsutf8.pdf unpack_files output .
```

**Unpacking with  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ .** The `.dtx` chooses its action depending on the format:

**plain  $\text{T}_{\text{E}}\text{X}$ :** Run `docstrip` and extract the files.

**$\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ :** Generate the documentation.

If you insist on using  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$  for `docstrip` (really, `docstrip` does not need  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{listingsutf8.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$` :

```
pdflatex listingsutf8.dtx
makeindex -s gind.ist listingsutf8.idx
pdflatex listingsutf8.dtx
makeindex -s gind.ist listingsutf8.idx
pdflatex listingsutf8.dtx
```

## 5 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `listingsutf8.xml`.

```
222 (*catalogue)
223 <?xml version='1.0' encoding='us-ascii'?>
224 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
225 <entry datestamp='$Date$' modifier='$Author$' id='listingsutf8'>
226   <name>listingsutf8</name>
227   <caption>Allow UTF-8 in listings input.</caption>
228   <authorref id='auth:oberdiek' />
229   <copyright owner='Heiko Oberdiek' year='2007,2011' />
230   <license type='lppl1.3' />
231   <version number='1.2' />
232   <description>
233     Package <xref refid='listings'>listings</xref> does not support files
234     with multi-byte encodings such as UTF-8. In the case of
235     <tt>\lstinputlisting</tt>, a simple workaround is possible if a
236     one-byte encoding exists that the file can be converted to. The
237     package requires the e-TeX extensions under pdfTeX (in either PDF
238     or DVI output mode).
239     <p/>
240     The package is part of the <xref refid='oberdiek'>oberdiek</xref> bundle.
241   </description>
242   <documentation details='Package documentation'
243     href='ctan:/macros/latex/contrib/oberdiek/listingsutf8.pdf' />
244   <ctan file='true' path='/macros/latex/contrib/oberdiek/listingsutf8.dtx' />
245   <miktex location='oberdiek' />
246   <texlive location='oberdiek' />
247   <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
248 </entry>
249 </catalogue>
```

## 6 References

- [1] Alan Jeffrey, Frank Mittelbach, *inputenc.sty*, 2006/05/05 v1.1b. [CTAN:macros/latex/base/inputenc.dtx](#)
- [2] Carsten Heinz, Brooks Moses: *The listings package*; 2007/02/22; [CTAN:macros/latex/contrib/listings/](#).
- [3] Heiko Oberdiek: *The stringenc package*; 2007/10/22; [CTAN:macros/latex/contrib/oberdiek/stringenc.pdf](#).

## 7 History

[2007/10/22 v1.0]

- First version.

[2007/11/11 v1.1]

- Use of package `pdftexcmds`.

[2011/11/10 v1.2]

- DOS line ends CR/LF normalized to LF to avoid empty lines (Bug report of Thomas Benkert in de.comp.text.tex).

## 8 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\#</code> .....	175
<code>\%</code> .....	178
<code>\@</code> .....	171
<code>\@backslashchar</code> .....	77
<code>\@car</code> .....	127
<code>\@ifundefined</code> .....	67
<code>\@makeother</code> .....	117, 118
<code>\@ne</code> .....	155, 163
<code>\@nil</code> .....	90, 121, 124, 130, 133, 140
<code>\[</code> .....	176
<code>\]</code> .....	172
<code>\{</code> .....	173
<code>\}</code> .....	174
<code>\]</code> .....	177
<code>\^</code> .....	117, 118, 193
<code>\_</code> .....	179
<b>A</b>	
<code>\advance</code> .....	155, 163
<code>\AtBeginDocument</code> .....	66
<b>B</b>	
<code>\begin</code> .....	200, 215
<b>C</b>	
<code>\catcode</code> 2, 3, 5, 6, 7, 11, 12, 13, 14, 15, 16, 17, 20, 21, 23, 24, 25, 26, 30, 32, 152, 161, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180	
<code>\count@</code> .....	148, 152, 154, 155, 159, 161, 162, 163
<code>\csname</code> .....	9, 74, 185
<code>\CurrentOption</code> .....	62
<b>D</b>	
<code>\DeclareOption</code> .....	61
<code>\do</code> .....	192, 195
<code>\documentclass</code> .....	145, 190
<code>\dospecials</code> .....	198, 199
<b>E</b>	
<code>\empty</code> .....	198
<code>\end</code> .....	186, 209, 220
<code>\endcsname</code> .....	9, 74, 185
<code>\endinput</code> .....	57
<code>\endlinechar</code> .....	4, 10, 22, 116
<b>G</b>	
<code>\gdef</code> .....	119, 124
<b>I</b>	
<code>\iflstU@utfviii</code> .....	88, 97
<code>\ifnum</code> .....	154, 162
<code>\ifx</code> .....	74, 126, 193
<code>\input</code> .....	110
<b>L</b>	
<code>\loop</code> .....	149, 160
<code>\lst@inputenc</code> .....	93, 104
<code>\lst@InputListing</code> .....	134, 140
<code>\lst@Key</code> .....	92
<code>\lst@next</code> .....	133, 136
<code>\lstinputlisting</code> .....	216, 235
<code>\lstU@@inputenc</code> .....	90, 92
<code>\lstU@AtEnd</code> .....	28, 29, 57, 80, 141
<code>\lstU@CRLFtoLF</code> .....	103, 115
<code>\lstU@CRLFtoLF@aux</code> ....	121, 124, 130
<code>\lstU@input</code> .....	96, 136
<code>\lstU@inputenc</code> .....	89, 94
<code>\lstU@temp</code> .....	72, 83, 84, 85, 86, 105, 109, 113, 133, 140
<code>\lstU@text</code> .....	98, 103, 104, 106
<b>M</b>	
<code>\makeatletter</code> .....	146
<code>\MessageBreak</code> .....	77
<b>N</b>	
<code>\NeedsTeXFormat</code> .....	58, 144, 189
<code>\newif</code> .....	88
<b>P</b>	
<code>\PackageWarningNoLine</code> .....	75
<code>\PassOptionsToPackage</code> .....	62
<code>\pdf@filedump</code> .....	100
<code>\pdf@filesize</code> .....	100
<code>\pdf@unescapehex</code> .....	99
<code>\ProcessOptions</code> .....	64
<code>\ProvidesPackage</code> .....	59

<b>R</b>		<b>\Text</b> . . . . .	211
\RangeCatcodeInvalid . . . . .		\the 10, 11, 12, 13, 14, 15, 16, 17, 30, 152	
. . . . .	158, 167, 168, 169, 170	\TMP@EnsureCode 27, 34, 35, 36, 37,	
\repeat . . . . .	156, 164	38, 39, 40, 41, 42, 43, 44, 45, 46,	
\RequirePackage . . . . .	65, 68, 71, 87, 181	47, 48, 49, 50, 51, 52, 53, 54, 55, 56	
\RestoreCatcodes . . . . .	147, 150, 151, 182		
<b>S</b>		<b>U</b>	
\scantokens . . . . .	106	\usepackage . . . . .	191, 210
\StringEncodingConvert . . . . .	104		
<b>T</b>		<b>X</b>	
\Test . . . . .	166, 184	\x . . . . .	8, 20