

The ltxcmds package

Heiko Oberdiek
<oberdiek@uni-freiburg.de>

2009/12/12 v1.1

Abstract

The package ltxcmds exports some utility macros from the L^AT_EX kernel into a separate namespace and also provides them for other formats such as plain-T_EX.

Contents

1	Documentation	2
1.1	Introduction	2
1.2	Argument killers	2
1.3	Argument grabbers	2
1.4	List helpers	2
1.5	Tail recursion	2
1.6	Empty macro	2
1.7	Characters	2
1.8	Command definitions	3
2	Implementation	3
2.1	Identification	3
2.2	Argument killers	4
2.3	Argument grabbers	5
2.4	List helpers	5
2.5	Tail recursion	5
2.6	Empty macro	5
2.7	Characters	5
2.8	Command definitions	6
3	Test	7
3.1	Catcode checks for loading	7
4	Installation	8
4.1	Download	8
4.2	Bundle installation	8
4.3	Package installation	8
4.4	Refresh file name databases	9
4.5	Some details for the interested	9
5	History	9
	[2009/08/05 v1.0]	9
	[2009/12/12 v1.1]	9
6	Index	10

1 Documentation

1.1 Introduction

Many of my packages also support other formats such as plain- \TeX . Because I am rather familiar with the utility macros from \LaTeX 's kernel (e.g. \@gobble , \@firstoftwo), I found myself rewriting them again and again, because they are lacking in plain- \TeX .

Therefore this package provides often used macros and similar ones with the name prefix \ltx@ . This avoids also faulty redefinitions. I remember an example where a package redefined \@firstoftwo with forgetting \long .

1.2 Argument killers

$\text{\ltx@gobble} \{\langle 1 \rangle\}$	\rightarrow
$\text{\ltx@gobbletwo} \{\langle 1 \rangle\} \{\langle 2 \rangle\}$	\rightarrow
$\text{\ltx@gobblethree} \{\langle 1 \rangle\} \{\langle 2 \rangle\} \{\langle 3 \rangle\}$	\rightarrow
$\text{\ltx@gobblefour} \{\langle 1 \rangle\} \{\langle 2 \rangle\} \{\langle 3 \rangle\} \{\langle 4 \rangle\}$	\rightarrow

1.3 Argument grabbers

$\text{\ltx@firstofone} \{\langle 1 \rangle\}$	\rightarrow	$\langle 1 \rangle$
$\text{\ltx@firstoftwo} \{\langle 1 \rangle\} \{\langle 2 \rangle\}$	\rightarrow	$\langle 1 \rangle$
$\text{\ltx@secondoftwo} \{\langle 1 \rangle\} \{\langle 2 \rangle\}$	\rightarrow	$\langle 2 \rangle$

1.4 List helpers

$\text{\ltx@car} \{\langle 1 \rangle\} \dots \text{\@nil}$	\rightarrow	$\langle 1 \rangle$
$\text{\ltx@cdr} \{\langle 1 \rangle\} \dots \text{\@nil}$	\rightarrow	\dots

1.5 Tail recursion

$\text{\ltx@ReturnAfterFi} \{\langle 1 \rangle\} \text{\fi}$	\rightarrow	$\text{\fi} \langle 1 \rangle$
$\text{\ltx@ReturnAfterElseFi} \{\langle 1 \rangle\} \text{\else} \{\langle 2 \rangle\} \text{\fi}$	\rightarrow	$\text{\fi} \langle 1 \rangle$

1.6 Empty macro

\ltx@empty	\rightarrow
---------------------	---------------

1.7 Characters

\ltx@space
\ltx@percentchar
$\text{\ltx@backslashchar}$

1.8 Command definitions

`\ltx@ifundefined {<cmd>} {<yes>} {<no>}`

If ε -TeX is available, `\ifcsname` is used that does not have the side effect of defining undefined commands with meaning of `\relax`. This command is always expandable. Change in version 1.1: Also the meaning `\relax` is always considered “undefined”.

`\ltx@ifundefined {<cmd>} {<yes>} {<no>}`

If ε -TeX is available, `\ifcsname` is used that does not have the side effect of defining undefined commands with meaning of `\relax`. Also it always checks for the meaning of `\relax` and considers this as undefined. This macro is not expandable without ε -TeX.

`\ltx@LocalExpandAfter`

It expands the token after the next token but in a local context. That is the difference to `\expandafter`. The local context discards the side effect of `\csname` and let the command undefined after the expansion step.

2 Implementation

2.1 Identification

```
1 <*package>
```

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \catcode123 1 % {
9   \catcode125 2 % }
10  \expandafter\let\expandafter\x\csname ver@ltxcmds.sty\endcsname
11  \ifx\x\relax % plain-TeX, first loading
12  \else
13    \def\empty{}%
14    \ifx\x\empty % LaTeX, first loading,
15    % variable is initialized, but \ProvidesPackage not yet seen
16    \else
17      \catcode35 6 % #
18      \expandafter\ifx\csname PackageInfo\endcsname\relax
19      \def\x#1#2{%
20        \immediate\write-1{Package #1 Info: #2.}%
21      }%
22    \else
23      \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24    \fi
25    \x{ltxcmds}{The package is already loaded}%
26    \aftergroup\endinput
27  \fi
28 \fi
29 \endgroup
```

Package identification:

```
30 \begingroup
```

```

31 \catcode35 6 % #
32 \catcode40 12 % (
33 \catcode41 12 % )
34 \catcode44 12 % ,
35 \catcode45 12 % -
36 \catcode46 12 % .
37 \catcode47 12 % /
38 \catcode58 12 % :
39 \catcode64 11 % @
40 \catcode91 12 % [
41 \catcode93 12 % ]
42 \catcode123 1 % {
43 \catcode125 2 % }
44 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
45   \def\x#1#2#3[#4]{\endgroup
46     \immediate\write-1{Package: #3 #4}%
47     \xdef#1{#4}%
48   }%
49 \else
50   \def\x#1#2[#3]{\endgroup
51     #2[#3]}%
52   \ifx#1\@undefined
53     \xdef#1{#3}%
54   \fi
55   \ifx#1\relax
56     \xdef#1{#3}%
57   \fi
58 }%
59 \fi
60 \expandafter\x\csname ver@ltxcmds.sty\endcsname
61 \ProvidesPackage{ltxcmds}%
62 [2009/12/12 v1.1 LaTeX kernel commands for general use (H0)]
63 \begingroup
64 \catcode123 1 % {
65 \catcode125 2 % }
66 \def\x{\endgroup
67   \expandafter\edef\csname ltx@AtEnd\endcsname{%
68     \catcode35 \the\catcode35\relax
69     \catcode64 \the\catcode64\relax
70     \catcode123 \the\catcode123\relax
71     \catcode125 \the\catcode125\relax
72   }%
73 }%
74 \x
75 \catcode35 6 % #
76 \catcode64 11 % @
77 \catcode123 1 % {
78 \catcode125 2 % }
79 \def\TMP@EnsureCode#1#2{%
80   \edef\ltx@AtEnd{%
81     \ltx@AtEnd
82     \catcode#1 \the\catcode#1\relax
83   }%
84   \catcode#1 #2\relax
85 }
86 \TMP@EnsureCode{61}{12}% =
87 \TMP@EnsureCode{96}{12}% ‘

```

2.2 Argument killers

\ltx@gobble

```
88 \long\def\ltx@gobble#1{}
```

```

\ltx@gobbletwo
89 \long\def\ltx@gobbletwo#1#2{}

\ltx@gobblethree
90 \long\def\ltx@gobblethree#1#2#3{}

\ltx@gobblefour
91 \long\def\ltx@gobblefour#1#2#3#4{}

```

2.3 Argument grabbers

```

\ltx@firstofone
92 \long\def\ltx@firstofone#1{#1}

\ltx@firstoftwo
93 \long\def\ltx@firstoftwo#1#2{#1}

\ltx@secondoftwo
94 \long\def\ltx@secondoftwo#1#2{#2}

```

2.4 List helpers

```

\ltx@car
95 \long\def\ltx@car#1#2\@nil{#1}

\ltx@cdr
96 \long\def\ltx@cdr#1#2\@nil{#2}

```

2.5 Tail recursion

```

\ltx@ReturnAfterFi
97 \long\def\ltx@ReturnAfterFi#1\fi{#1}

\ltx@ReturnAfterElseFi
98 \long\def\ltx@ReturnAfterFi#1\else#2\fi{#1}

```

2.6 Empty macro

```

\ltx@empty
99 \def\ltx@empty{}

```

2.7 Characters

```

\ltx@space
100 \def\ltx@space{ }

\ltx@percentchar
101 \begingroup
102 \lccode'0='%\relax
103 \lowercase{\endgroup
104 \def\ltx@percentchar{0}%
105 }

\ltx@backslashchar
106 \begingroup
107 \lccode'0='\\relax
108 \lowercase{\endgroup
109 \def\ltx@backslashchar{0}%
110 }

```

2.8 Command definitions

```

\ltx@LocalExpandAfter

111 \def\ltx@LocalExpandAfter{%
112   \begingroup
113   \expandafter\expandafter\expandafter
114   \endgroup
115   \expandafter
116 }

117 \ltx@LocalExpandAfter
118 \ifx\csname ifcsname\endcsname\relax

\ltx@ifundefined

119   \def\ltx@ifundefined#1{%
120     \expandafter\ifx\csname #1\endcsname\relax
121       \expandafter\ltx@firstoftwo
122     \else
123       \expandafter\ltx@secondoftwo
124     \fi
125   }%

\ltx@ifUndefined

126   \def\ltx@ifUndefined#1{%
127     \begingroup\expandafter\expandafter\expandafter\endgroup
128     \expandafter\ifx\csname #1\endcsname\relax
129       \expandafter\ltx@firstoftwo
130     \else
131       \expandafter\ltx@secondoftwo
132     \fi
133   }%

134   \expandafter\ltx@gobble
135 \else
136   \expandafter\ltx@firstofone
137 \fi
138 {%

\ltx@ifundefined

139   \def\ltx@ifundefined#1{%
140     \ifcsname #1\endcsname
141       \expandafter\ifx\csname #1\endcsname\relax
142         \expandafter\expandafter\expandafter\ltx@firstoftwo
143       \else
144         \expandafter\expandafter\expandafter\ltx@secondoftwo
145       \fi
146     \else
147       \expandafter\ltx@firstoftwo
148     \fi
149   }%

\ltx@ifUndefined

150   \let\ltx@ifUndefined\ltx@ifundefined

151 }

152 \ltx@AtEnd
153 \endpackage

```

3 Test

3.1 Catcode checks for loading

```
154 (*test1)
155 \catcode'\{=1 %
156 \catcode'\}=2 %
157 \catcode'\#=6 %
158 \catcode'\@=11 %
159 \expandafter\ifx\csname count@\endcsname\relax
160   \countdef\count@=255 %
161 \fi
162 \expandafter\ifx\csname @gobble\endcsname\relax
163   \long\def\@gobble#1{}%
164 \fi
165 \expandafter\ifx\csname @firstofone\endcsname\relax
166   \long\def\@firstofone#1{#1}%
167 \fi
168 \expandafter\ifx\csname loop\endcsname\relax
169   \expandafter\@firstofone
170 \else
171   \expandafter\@gobble
172 \fi
173 {%
174   \def\loop#1\repeat{%
175     \def\body{#1}%
176     \iterate
177   }%
178   \def\iterate{%
179     \body
180     \let\next\iterate
181   \else
182     \let\next\relax
183   \fi
184   \next
185 }%
186 \let\repeat=\fi
187 }%
188 \def\RestoreCatcodes{}
189 \count@=0 %
190 \loop
191   \edef\RestoreCatcodes{%
192     \RestoreCatcodes
193     \catcode\the\count@=\the\catcode\count@\relax
194   }%
195 \ifnum\count@<255 %
196   \advance\count@ 1 %
197 \repeat
198
199 \def\RangeCatcodeInvalid#1#2{%
200   \count@=#1\relax
201   \loop
202     \catcode\count@=15 %
203   \ifnum\count@<#2\relax
204     \advance\count@ 1 %
205   \repeat
206 }
207 \expandafter\ifx\csname LoadCommand\endcsname\relax
208   \def\LoadCommand{\input ltxcmds.sty\relax}%
209 \fi
210 \def\Test{%
211   \RangeCatcodeInvalid{0}{47}%
```

```

212 \RangeCatcodeInvalid{58}{64}%
213 \RangeCatcodeInvalid{91}{96}%
214 \RangeCatcodeInvalid{123}{255}%
215 \catcode'\@=12 %
216 \catcode'\=0 %
217 \catcode'\{=1 %
218 \catcode'\}=2 %
219 \catcode'\#=6 %
220 \catcode'\[=12 %
221 \catcode'\]=12 %
222 \catcode'\%=14 %
223 \catcode'\ =10 %
224 \catcode13=5 %
225 \LoadCommand
226 \RestoreCatcodes
227 }
228 \Test
229 \csname @@end\endcsname
230 \end
231 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/ltxcmds.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/ltxcmds.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex ltxcmds.dtx
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
ltxcmds.sty      → tex/generic/oberdiek/ltxcmds.sty
ltxcmds.pdf      → doc/latex/oberdiek/ltxcmds.pdf
test/ltxcmds-test1.tex → doc/latex/oberdiek/test/ltxcmds-test1.tex
ltxcmds.dtx      → source/latex/oberdiek/ltxcmds.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk ltxcmds.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain- \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{ltxcmds.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf \LaTeX` :

```
pdflatex ltxcmds.dtx
makeindex -s gind.ist ltxcmds.idx
pdflatex ltxcmds.dtx
makeindex -s gind.ist ltxcmds.idx
pdflatex ltxcmds.dtx
```

5 History

[2009/08/05 v1.0]

- First version.

[2009/12/12 v1.1]

- Short title shortened.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
<code>\#</code>	157, 219	<code>\input</code> 208
<code>\%</code>	102, 222	<code>\iterate</code> 176, 178, 180
<code>\@</code>	158, 215	
<code>\@firstofone</code>	166, 169	L
<code>\@gobble</code>	163, 171	<code>\lccode</code> 102, 107
<code>\@nil</code>	95, 96	<code>\LoadCommand</code> 208, 225
<code>\@undefined</code>	52	<code>\loop</code> 174, 190, 201
<code>\[</code>	220	<code>\lowercase</code> 103, 108
<code>\]</code>	107, 216	<code>\ltx@AtEnd</code> 80, 81, 152
<code>\{</code>	155, 217	<code>\ltx@backslashchar</code> 106
<code>\}</code>	156, 218	<code>\ltx@car</code> 2, 95
<code>\]</code>	221	<code>\ltx@cdr</code> 96
		<code>\ltx@empty</code> 2, 99
<code>_</code>	223	<code>\ltx@firstofone</code> 2, 92, 136
		<code>\ltx@firstoftwo</code> 93, 121, 129, 142, 147
A		<code>\ltx@gobble</code> 2, 88, 134
<code>\advance</code>	196, 204	<code>\ltx@gobblefour</code> 91
<code>\aftergroup</code>	26	<code>\ltx@gobblethree</code> 90
		<code>\ltx@gobbletwo</code> 89
B		<code>\ltx@ifundefined</code> 3, 126, 150
<code>\body</code>	175, 179	<code>\ltx@ifundefined</code> 3, 119, 139, 150
		<code>\ltx@LocalExpandAfter</code> 3, 111, 117
C		<code>\ltx@percentchar</code> 101
<code>\catcode</code>	3, 4, 5, 6, 7, 8, 9, 17, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 64, 65, 68, 69, 70, 71, 75, 76, 77, 78, 82, 84, 155, 156, 157, 158, 193, 202, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224	<code>\ltx@ReturnAfterElseFi</code> 98
<code>\count@</code>	160, 189, 193, 195, 196, 200, 202, 203, 204	<code>\ltx@ReturnAfterFi</code> 2, 97, 98
<code>\countdef</code>	160	<code>\ltx@secondoftwo</code> 94, 123, 131, 144
<code>\csname</code>	10, 18, 44, 60, 67, 118, 120, 128, 141, 159, 162, 165, 168, 207, 229	<code>\ltx@space</code> 2, 100
E		N
<code>\empty</code>	13, 14	<code>\next</code> 180, 182, 184
<code>\end</code>	230	
<code>\endcsname</code>	10, 18, 44, 60, 67, 118, 120, 128, 140, 141, 159, 162, 165, 168, 207, 229	P
<code>\endinput</code>	26	<code>\PackageInfo</code> 23
		<code>\ProvidesPackage</code> 15, 61
I		
<code>\ifcsname</code>	140	R
<code>\ifnum</code>	195, 203	<code>\RangeCatcodeInvalid</code> 199, 211, 212, 213, 214
<code>\ifx</code>	11, 14, 18, 44, 52, 55, 118, 120, 128, 141, 159, 162, 165, 168, 207	<code>\repeat</code> 174, 186, 197, 205
<code>\immediate</code>	20, 46	<code>\RestoreCatcodes</code> 188, 191, 192, 226
		T
		<code>\Test</code> 210, 228
		<code>\the</code> 68, 69, 70, 71, 82, 193
		<code>\TMP@EnsureCode</code> 79, 86, 87
		W
		<code>\write</code> 20, 46
		X
		<code>\x</code> 10, 11, 14, 19, 23, 25, 45, 50, 60, 66, 74