

The luatex package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2009/04/10 v0.2

Abstract

This package manages the new and extended features and resources that LUATEX provides. Examples are attributes and catcode tables.

Contents

1 Documentation	2
1.1 Introduction	2
1.1.1 L ^A T _E X	2
1.1.2 plain-T _E X	2
1.2 Register allocation	3
1.2.1 Register with 16 bit	3
1.2.2 Insertions	3
1.3 Lua states	3
1.4 Attributes	3
1.5 Catcode tables	4
1.5.1 Interface proposal	4
1.6 Lua module loading	5
1.6.1 Package luatex-loader	6
2 Implementation	6
2.1 Reload check and package identification	6
2.2 Catcodes	7
2.3 Check for LUATEX	8
2.4 Inherit support for ε-T _E X	8
2.5 Adaption of ε-T _E X's register allocation	8
2.6 plain-T _E X compatibility	9
2.7 Lua states	11
2.8 Attributes	11
2.8.1 Allocation	11
2.8.2 Interface	11
2.9 Catcode tables	12
2.9.1 Allocation	12
2.9.2 \SetCatcodeRange	12
2.9.3 Predefined catcode tables	13
2.9.4 Number stack	13
2.9.5 Catcode regime macros	14
2.10 Lua module loader	14
2.11 Lua script	16

3	Test	16
3.1	Catcode checks for loading	17
3.2	Catcode tables	18
3.2.1	Predefined catcode tables	18
3.2.2	Catcode table number stack	19
3.2.3	Catcode table stack	19
3.2.4	Catcode regime macros	20
3.3	Attribute allocation	20
3.4	Lua states	20
3.5	Short test for plain-T _{EX}	21
4	Installation	21
4.1	Download	21
4.2	Bundle installation	21
4.3	Package installation	21
4.4	Refresh file name databases	22
4.5	Some details for the interested	22
5	History	22
[2007/12/12 v0.1]	22
[2009/04/10 v0.2]	23
6	Index	23

1 Documentation

1.1 Introduction

T_{EX} provides global resources such as registers. But it does not provide an interface for managing these resources. For example, two packages want to use a counter register. If they take the same register number, then the use of both packages will conflict and they cannot be used together. Therefore formats such as plain-T_{EX} or L^AT_{EX} implement an allocation scheme for registers. A package reserves with \newcount an unused register number for its own exclusive use.

Nowadays T_{EX} is not alone anymore: ε-T_{EX}, pdfT_{EX} and other compilers for T_{EX} are developed that extend and add new features and resources.

Now LUAT_{EX} has reached beta state. It inherits most of pdfT_{EX}'s features including ε-T_{EX}. Also it implements new concepts such as attributes or catcode tables.

1.1.1 L^AT_{EX}

L^AT_{EX} 2_ε is frozen and therefore refuses to even notice the new T_{EX} variants. Not even the old ε-T_{EX} is supported by its kernel. At least there is a third party package `etex` that manages the new ε-T_{EX} resources.

This package tries to do the same for LUAT_{EX} and starts to support at least a few of the new features.

1.1.2 plain-T_{EX}

L^AT_{EX} has inherited its resource handling from plain-T_{EX}. The interface is basically the same: \newcount, ... Therefore this package tries to follow this tradition by providing compatibility to plain-T_{EX}. It can be loaded with plain-T_{EX} and defines at least some of the features that this packages provides for L^AT_{EX}.

1.2 Register allocation

1.2.1 Register with 16 bit

Because LUATEX is a super set of ε -TEX regarding registers, the register allocation scheme should not conflict with package etex. Therefore this package is loaded to inherit its allocation scheme. The only change is currently that the limit is increased to 65536 registers for the following register classes:

- count
- dimen
- skip
- muskip
- marks
- toks
- box

This affects the number of global and local registers. Because it is done in a package and not in the kernel, it is possible that someone loads package etex before uses the local allocation variants. This will prevent the extension for this register class. If more registers are needed, just load package luatex earlier.

1.2.2 Insertions

Insertions need four registers \count, \dimen, \skip, and \box with the same number. Usually they are allocated downwards from 254, 253, ... Also \newcount, \newdimen, ... fill up these register numbers from below before switching to higher register numbers by package etex. When this occurs, no insertions can be allocated anymore.

Therefore \newcount, \newdimen, \newskip, and \newbox are replaced by their global variants (\globcount, ...) that use the higher numbers immediately, leaving the room for insertions. There should not be an efficiency penalty because LUATEX stores the registers of a class in the same Lua table unlike ε -TEX, where registers below 256 are stored in an array and higher numbers are put in a tree structure.

1.3 Lua states

```
\newluastate {\langle cmd \rangle}
```

Macro \newluastate reserves a new Lua state and stores the number in \cmd.

1.4 Attributes

Nodes can have custom attributes in LUATEX. These attributes are organized by a new register class. As the other registers up to 2^{16} attributes are supported. An attribute value can be negative that means the attribute is not set. Otherwise TEX's range of non-negative integers up to 2^{31} are available.

```
\newattribute {\langle cmd \rangle}
```

Macro \newattribute defines command \langle cmd \rangle using \attributedef using an new attribute number. The new attribute is initially unset.

```
\setattribute {\langle cmd \rangle} {\langle value \rangle}
```

Macro \setattribute locally sets attribute command \langle cmd \rangle to the number \langle value \rangle. Valid values range from -1 until 2^{31} (the upper limit is the same as for other TEX integer numbers).

```
\unsetattribute {\langle cmd\rangle}
```

Macro `\unsetattribute` clears the attribute command $\langle cmd \rangle$.

1.5 Catcode tables

LUATEX introduces catcode tables as new feature, see documentation. There is need for discussion, how to deal best:

- `\initcatcodetable` and `\setcatcodetable` act globally.
- `\catcodetable` causes an error if used with an uninitialized catcode table.
- Large catcode table numbers should be avoided because of performance breakdown.
- Use case LATEX package: The package must not be surprised by changed catcodes and must not surprise by changing catcodes accidentally. Catcode tables could offer a solution. At the begin a catcode regime with standard catcodes is established and the old one is restored afterwards.
- Use case: LUATEX's `tex.print` might be used with a catcode table number, for example a table where all entries have catcode "other".
- Readonly catcode tables.
- Is there is a need for local allocations? (Package etex's `\loc` variants are not used in TeX Live 2007.)

1.5.1 Interface proposal

The idea: `\newcatcodetable` allocates odd numbered catcode tables. Even numbered tables are managed as stack. Also some catcode tables are defined. These must not be changed.

```
\newcatcodetable {\langle cmd\rangle}
```

Macro `\newcatcodetable` reserves a new catcode table and remembers its number in $\langle cmd \rangle$. The catcode table is initialized with ini-TEX's catcodes.

```
\CatcodeTableIniTeX  
\CatcodeTableString  
\CatcodeTableOther  
\CatcodeTableLaTeX
```

These are catcode tables and must not be changed. `\CatcodeTableIniTeX` contains the catcode settings of ini-TEX. `\CatcodeTableString` follows TEX's convention of `\string`, `\meaning` and friends. The space gets catcode 10 (space), the other characters have catcode 12 (other). In `\CatcodeTableOther` all entries have catcode 12 (other). `\CatcodeTableLaTeX` contains the setting of a pure LATEX format ('at' is other).

```
\CatcodeTableStack  
\IncCatcodeTableStack  
\DecCatcodeTableStack
```

`\CatcodeTableStack` is the stack pointer. Initially it is catcode table zero. `\IncCatcodeTableStack` and `\DecCatcodeTableStack` increments and decrements the stack pointer. Currently `\IncCatcodeTableStack` does not initialize a

new catcode table. Both increment and decrement operations do not set a catcode table.

```
\PushCatcodeTableNumStack
\PopCatcodeTableNumStack
```

It can be handy to have a global stack for catcode table numbers to deal with the global assignment property of `\initcatcodetable` and `\savecatcodetable`. `\PushCatcodeTableNumStack` pushes the current catcode table on the stack. `\PopCatcodeTableNumStack` pops the topmost number off the number stack to set the current catcode table. Catcode table zero is used in case of an empty stack.

```
\BeginCatcodeRegime {\langle catcodetable \rangle}
\EndCatcodeRegime
```

`\BeginCatcodeRegime` remembers the current catcode table number. Then it creates and uses a fresh catcode table on the stack that is initialized by `\langle catcodetable \rangle`:

```
\PushCatcodeTableNumStack
\catcodetable{\langle catcodetable \rangle} \IncCatcodeTableStack
\savecatcodetable\CatcodeTableStack
\catcodetable\CatcodeTableStack
```

`\EndCatcodeRegime` drops the catcode table, created by `\BeginCatcodeRegime` and sets the catcode table that was active before:

```
\DecCatcodeTableStack
\PopCatcodeTableNumStack
```

These macros solve the use case, described earlier for a L^AT_EX package:

```
% package foobar.sty
\BeginCatcodeRegime\CatcodeTableLaTeX
\makeatletter
% ... package contents ...
\EndCatcodeRegime
% end of package
```

If the package wants to change catcodes after its loading, `\AtBeginDocument` or `\AtEndOfPackage` can be used.

```
\SetCatcodeRange {\langle from \rangle} {\langle to \rangle} {\langle catcode \rangle}
```

The catcodes of characters in range from `\langle from \rangle` to inclusive `\langle to \rangle` are set to `\langle catcode \rangle`.

1.6 Lua module loading

Currently LU^AT_EX (version 0.20) does not support Lua script files inside TDS:`scripts//`, because Lua's mechanism for module loading does not use the `kpathsea` library. Therefore this packages appends a `kpse` loader to the list of Lua's module loaders. It finds the module `\langle module \rangle` by

```
kpse.find_file("\langle module \rangle.lua", "texmfscripts")
```

Unhappily `kpathsea` does not support directory components in a file name. Therefore the Lua convention is not followed to replace dots in the module name by the directory separator.

Example: A Lua script of a package `foobar` wants the following modules:

```

require("foobar.hello.world")
require("org.somewhere.xyz")

```

Then they can be find in:

```

TDS:scripts/foobar/foobar.hello.world.lua
TDS:scripts/foobar/org.somewhere.xyz.lua

```

I would have preferred the following locations, following lua conventions, e.g.:

```

TDS:scripts/foobar/hello/world.lua
TDS:scripts/foobar/org/somewhere/xyz.lua

```

But I do not know, how to achieve this in a reliable way using `kpathsea`.

1.6.1 Package luatex-loader

If someone do not need or want package `luatex` but it's extension for module loading, then he can use package `luatex-loader`. Both plain-`\TeX` and `\LaTeX` are supported.

2 Implementation

1 `(*package)`

2.1 Reload check and package identification

Reload check, especially if the package is not used with `\LaTeX`.

```

2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \expandafter\let\expandafter\x\csname ver@luatex.sty\endcsname
9   \ifcase 0%
10     \ifx\x\relax % plain
11     \else
12       \ifx\x\empty % LaTeX
13       \else
14         1%
15       \fi
16     \fi
17   \else
18     \catcode35 6 % #
19     \catcode123 1 % {
20     \catcode125 2 % }
21     \expandafter\ifx\csname PackageInfo\endcsname\relax
22       \def\x#1#2{%
23         \immediate\write-1{Package #1 Info: #2.}%
24       }%
25     \else
26       \def\x#1#2{\PackageInfo{#1}{#2, stopped}%
27     \fi
28     \x{luatex}{The package is already loaded}%
29     \endgroup
30     \expandafter\endinput
31   \fi
32 \endgroup

```

Package identification:

```

33 \begingroup
34   \catcode35 6 % #

```

```

35  \catcode40 12 % (
36  \catcode41 12 % )
37  \catcode44 12 % ,
38  \catcode45 12 % -
39  \catcode46 12 % .
40  \catcode47 12 % /
41  \catcode58 12 % :
42  \catcode64 11 % @
43  \catcode123 1 % {
44  \catcode125 2 % }
45 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
46   \def\x#1#2#3[#4]{\endgroup
47     \immediate\write-1{Package: #3 #4}%
48     \xdef#1[#4]%
49   }%
50 \else
51   \def\x#1#2[#3]{\endgroup
52     #2[#3]%
53     \ifx#1\undefined
54       \xdef#1{\#3}%
55     \fi
56     \ifx#1\relax
57       \xdef#1{\#3}%
58     \fi
59   }%
60 \fi
61 \expandafter\x\csname ver@luatex.sty\endcsname
62 \ProvidesPackage{luatex}%
63 [2009/04/10 v0.2 LuaTeX basic definition package (HO)]

```

2.2 Catcodes

```

64 \begingroup
65  \catcode123 1 % {
66  \catcode125 2 % }
67  \def\x{\endgroup
68  \expandafter\edef\csname LuT@AtEnd\endcsname{%
69    \catcode35 \the\catcode35\relax
70    \catcode64 \the\catcode64\relax
71    \catcode123 \the\catcode123\relax
72    \catcode125 \the\catcode125\relax
73  }%
74 }%
75 \x
76 \catcode35 6 % #
77 \catcode64 11 % @
78 \catcode123 1 % {
79 \catcode125 2 % }
80 \def\TMP@EnsureCode#1#2{%
81   \edef\LuT@AtEnd{%
82     \LuT@AtEnd
83     \catcode#1 \the\catcode#1\relax
84   }%
85   \catcode#1 #2\relax
86 }
87 \TMP@EnsureCode{10}{12}% ^~J
88 \TMP@EnsureCode{34}{12}% "
89 \TMP@EnsureCode{36}{3}% $
90 \TMP@EnsureCode{39}{12}% ,
91 \TMP@EnsureCode{40}{12}% (
92 \TMP@EnsureCode{41}{12}% )
93 \TMP@EnsureCode{42}{12}% *

```

```

94 \TMP@EnsureCode{43}{12}%
95 \TMP@EnsureCode{44}{12}%
96 \TMP@EnsureCode{45}{12}%
97 \TMP@EnsureCode{46}{12}%
98 \TMP@EnsureCode{47}{12}%
99 \TMP@EnsureCode{60}{12}%
100 \TMP@EnsureCode{61}{12}%
101 \TMP@EnsureCode{62}{12}%
102 \TMP@EnsureCode{95}{12}%
103 \TMP@EnsureCode{96}{12}%

```

2.3 Check for LuATEX

Without LUATEX there is no point in using this package.

```

104 \begingroup\expandafter\expandafter\expandafter\endgroup
105 \expandafter\ifx\csname RequirePackage\endcsname\relax
106   \input infwarerr.sty\relax
107   \input ifluatex.sty\relax
108 \else
109   \RequirePackage{infwarerr}[2007/09/09]%
110   \RequirePackage{ifluatex}[2009/04/10]%
111 \fi
112 \ifluatex
113 \else
114   \PackageError{luatex}{%
115     This package may only be run using LuATeX%
116   }{\@ehc
117   \LuT@AtEnd
118   \expandafter\endinput
119 \fi

```

2.4 Inherit support for ε -TEX

Package `etex` is not compatible for plain-TEX. But it could be present if a format is used that is based on `etex.src`. Therefore we only load the package in case of IATEX and tests its presence independently of the format by looking for `\et@xins`.

```

120 \begingroup\expandafter\expandafter\expandafter\endgroup
121 \expandafter\ifx\csname RequirePackage\endcsname\relax
122 \else
123   \RequirePackage{etex}[1998/03/26]%
124 \fi

```

2.5 Adaption of ε -TEX's register allocation

ε -TEX has increased the number of TEX registers from 2^8 (256) to 2^{15} (32768) for a register class. LUATEX extends the limit further to 2^{16} (65536). The allocation scheme of package `etex` is not changed. But this can be subject for discussion.

If a register class hasn't registered any local registers yet, then the limit can safely be pushed to 65536.

```

125 \begingroup\expandafter\expandafter\expandafter\endgroup
126 \expandafter\ifx\csname et@xins\endcsname\relax
127   \PackageWarningNoLine{luatex}{%
128     Support for eTeX is not loaded (etex.src)%
129   }%
130 \else
131   \def\LuT@temp#1{%
132     \ifnum\count27#1=32768 %
133       \count27#1=65536 %
134     \fi
135   }%
136   \LuT@temp0%

```

```

137  \LuT@temp1%
138  \LuT@temp2%
139  \LuT@temp3%
140  \LuT@temp4%
141  \LuT@temp5%
142  \LuT@temp6%

```

ε - \TeX uses an array for the first 256 registers and then a tree structure. LUATEX stores all registers of a class in one Lua table. There shouldn't be large performance differences. This allows starting immediately in the extended area, leaving room for insertions.

```

143  \let\newcount\globcount
144  \let\newdimen\globdimen
145  \let\newskip\globskip
146  \let\newbox\globbox
147 \fi

```

2.6 plain- \TeX compatibility

```

\@empty
148 \expandafter\ifx\csname \@empty\endcsname\relax
149   \def\@empty{}%
150 \fi

\@gobble
151 \expandafter\ifx\csname \@gobble\endcsname\relax
152   \long\def\@gobble#1{}%
153 \fi

\@firstofone
154 \expandafter\ifx\csname \@firstofone\endcsname\relax
155   \long\def\@firstofone#1{#1}%
156 \fi

\@firstoftwo
157 \expandafter\ifx\csname \@firstoftwo\endcsname\relax
158   \long\def\@firstoftwo#1#2{#1}%
159 \fi

\@car
160 \expandafter\ifx\csname \@car\endcsname\relax
161   \def\@car#1#2\@nil{#1}%
162 \fi

\@cdr
163 \expandafter\ifx\csname \@cdr\endcsname\relax
164   \def\@cdr#1#2\@nil{#2}%
165 \fi

\@ifstar
166 \expandafter\ifx\csname \@ifstar\endcsname\relax
167   \def\@ifstar#1{%
168     \@ifnextchar*{\@firstoftwo{#1}}{}%
169   }%

```

```

\@ifnextchar
170   \long\def\@ifnextchar#1#2#3{%
171     \let\reserved@d=#1%
172     \def\reserved@a{#2}%
173     \def\reserved@b{#3}%
174     \futurelet\@let@token\@ifnch
175   }%

```

```

\@ifnch
176  \def\@ifnch{%
177    \ifx\@let@token\@sptoken
178      \let\reserved@c\@xifnch
179    \else
180      \ifx\@let@token\reserved@d
181        \let\reserved@c\reserved@a
182      \else
183        \let\reserved@c\reserved@b
184      \fi
185    \fi
186    \reserved@c
187  }%
188
\@sptoken
188  \let\LuT@temp\:%
189  \def\:{\let\@sptoken= }%
190  \: % explicit space
191
\@xifnch
191  \def\:{\@xifnch}%
192  \expandafter\def\:\f%
193    \futurelet\@let@token\@ifnch
194  }%
195  \let\:\LuT@temp
196 \fi
197
\@tempcnta
197 \expandafter\ifx\csname @tempcnta\endcsname\relax
198   \csname newcount\endcsname\@tempcnta
199 \fi
200
\@tempcntb
200 \expandafter\ifx\csname @tempcntb\endcsname\relax
201   \csname newcount\endcsname\@tempcntb
202 \fi
203
\LuT@newcommand
203 \begingroup\expandafter\expandafter\expandafter\expandafter\endgroup
204 \expandafter\ifx\csname newcommand\endcsname\relax
205   \def\LuT@newcommand#1[#2]#3{%
206     \ifx#1\@undefined
207       \let#1\relax
208     \else
209       \ifx#1\relax
210     \else
211       \PackageError{luatex}{%
212         \string#1 is already defined.\MessageBreak
213         Redefinition is skipped%
214       }{\ehc
215     \fi
216   \fi
217   \ifx#1\relax
218     \ifcase#2 %
219       \def#1{#3}%
220     \or
221       \def#1##1{#3}%
222     \or
223       \def#1##1##2{#3}%
224     \or
225       \def#1##1##2##3{#3}%

```

```

226      \or
227      \cINTERNAL@ERROR
228      \fi
229      \fi
230  }%
231 \else
232   \def\LuT@newcommand{\newcommand*}%
233 \fi

```

2.7 Lua states

```

\LuT@AllocLuaState
234 \newcount\LuT@AllocLuaState
235 \LuT@AllocLuaState=\z@

\newluastate
236 \LuT@newcommand\newluastate[1]{%
237   \ifnum\LuT@AllocLuaState<65535 %
238     \global\advance\LuT@AllocLuaState\@ne
239     \allocationnumber\LuT@AllocLuaState
240     \global\chardef#1=\allocationnumber
241     \wlog{\string#1=\string\luastate\the\allocationnumber}%
242   \else
243     \errmessage{No room for a new \string\luastate}%
244   \fi
245 }

```

2.8 Attributes

2.8.1 Allocation

```

\LuT@AllocAttribute
246 \newcount\LuT@AllocAttribute
247 \LuT@AllocAttribute=\m@ne

\newattribute
248 \LuT@newcommand\newattribute[1]{%
249   \ifnum\LuT@AllocAttribute<65535 %
250     \global\advance\LuT@AllocAttribute\@ne
251     \allocationnumber\LuT@AllocAttribute
252     \global\attributedef#1=\allocationnumber
253     \unsetattribute{#1}%
254     \wlog{\string#1=\string\attribute\the\allocationnumber}%
255   \else
256     \errmessage{No room for a new \string\attribute}%
257   \fi
258 }

```

2.8.2 Interface

```

\setattribute
259 \LuT@newcommand\setattribute[2]{%
260   #1=\numexpr#2\relax
261 }

\unsetattribute
262 \LuT@newcommand\unsetattribute[1]{%
263   #1=\m@ne
264 }

```

2.9 Catcode tables

2.9.1 Allocation

```
\LuT@AllocCatcodeTable
265 \newcount\LuT@AllocCatcodeTable
266 \LuT@AllocCatcodeTable=\m@ne
267 \newcount\CatcodeTableStack
268 \CatcodeTableStack=\z@

\newcatcodetable
269 \LuT@newcommand\newcatcodetable[1]{%
270   \ifnum\LuT@AllocCatcodeTable<1114110 % 0x10FFFF is maximal \chardef
271     % or < 268435455 % 2^28 - 1
272     \global\advance\LuT@AllocCatcodeTable by\tw@
273     \allocationnumber=\LuT@AllocCatcodeTable
274     \global\chardef#1=\allocationnumber
275     \wlog{%
276       \string#1=\string\catcodetable\the\allocationnumber
277     }%
278   \else
279     \errmessage{No room for a new \string\catcodetable}%
280   \fi
281 }%

\IncCatcodeTableStack
282 \LuT@newcommand\IncCatcodeTableStack[0]{%
283   \ifnum\CatcodeTableStack<268435454 %
284     \global\advance\CatcodeTableStack by\tw@
285   \else
286     \PackageError{luatex}{%
287       Catcode table stack overflow%
288     }\@ehd
289   \fi
290 }

\DecCatcodeTableStack
291 \LuT@newcommand\DecCatcodeTableStack[0]{%
292   \ifnum\CatcodeTableStack>\z@
293     \global\advance\CatcodeTableStack by-2 %
294   \else
295     \PackageError{luatex}{%
296       Catcode table stack is empty%
297     }\@ehd
298   \fi
299 }
```

2.9.2 \SetCatcodeRange

```
\SetCatcodeRange
300 \LuT@newcommand\SetCatcodeRange[3]{%
301   \edef\LuT@temp{%
302     \noexpand\@tempcpta=\the\@tempcpta
303     \noexpand\@tempcntb=\the\@tempcntb
304     \noexpand\count@=\the\count@
305     \relax
306   }%
307   \tempcpta=\numexpr#1\relax
308   \tempcntb=\numexpr#2\relax
309   \count@=\numexpr#3\relax
310   \loop
311     \unless\ifnum\@tempcpta>\@tempcntb
```

```

312      \catcode`\@tempcnta=\count@
313      \advance\@tempcnta by \one
314      \repeat
315      \LuT@temp
316 }

317 \newcatcodetable{CatcodeTableIniTeX}
318 \newcatcodetable{CatcodeTableString}
319 \newcatcodetable{CatcodeTableOther}
320 \newcatcodetable{CatcodeTableLaTeX}

321 \initcatcodetable{CatcodeTableIniTeX}
322 \begingroup
323   \def\@makeother#1{\catcode#1=12\relax}%
324   \iffirstofone{%
325     \catcodetable{CatcodeTableIniTeX}
326     \begingroup
327       \SetCatcodeRange{0}{8}{15}%
328       \catcode9=10 % tab
329       \catcode11=15 %
330       \catcode12=13 % form feed
331       \SetCatcodeRange{14}{31}{15}%
332       \catcode35=6 % hash
333       \catcode36=3 % dollar
334       \catcode38=4 % ampersand
335       \catcode94=7 % circumflex
336       \catcode95=8 % underscore
337       \catcode123=1 % brace left
338       \catcode125=2 % brace right
339       \catcode126=13 % tilde
340       \catcode127=15 %
341       \savecatcodetable{CatcodeTableLaTeX}
342     \endgroup
343     \@makeother{0}%
344     \@makeother{13}%
345     \@makeother{37}%
346     \@makeother{92}%
347     \@makeother{127}%
348     \SetCatcodeRange{65}{90}{12}%
349     \SetCatcodeRange{97}{122}{12}%
350     \savecatcodetable{CatcodeTableString}
351     \@makeother{32}%
352     \savecatcodetable{CatcodeTableOther}
353   \endgroup
354 }%

```

2.9.4 Number stack

```

\LuT@NumStackEmpty A special empty stack value because of \cdr's brace removal.
355 \def\LuT@NumStackEmpty{0}

\LuT@NumStack
356 \let\LuT@NumStack\LuT@NumStackEmpty

\PushCatcodeTableNumStack
357 \LuT@newcommand{PushCatcodeTableNumStack}[0]{%
358   \xdef\LuT@NumStack{%
359     {\the\catcodetable}\LuT@NumStack
360   }%
361 }

```

```

\PopCatcodeTableNumStack
362 \LuT@newcommand\PopCatcodeTableNumStack[0]{%
363   \ifx\LuT@NumStack\LuT@NumStackEmpty
364     \PackageWarning{luatex}{Empty catcode table number stack}%
365     \catcodetable\z@
366   \else
367     \catcodetable=\expandafter\@car\LuT@NumStack\@nil\relax
368     \xdef\LuT@NumStack{%
369       \expandafter\@cdr\LuT@NumStack\@nil
370     }%
371   \fi
372 }

```

2.9.5 Catcode regime macros

```

\BeginCatcodeRegime
373 \LuT@newcommand\BeginCatcodeRegime[1]{%
374   \PushCatcodeTableNumStack
375   \catcodetable=\numexpr#1\relax
376   \IncCatcodeTableStack
377   \savecatcodetable\CatcodeTableStack
378   \catcodetable\CatcodeTableStack
379 }

\EndCatcodeRegime
380 \LuT@newcommand\EndCatcodeRegime[0]{%
381   \DecCatcodeTableStack
382   \PopCatcodeTableNumStack
383 }

```

2.10 Lua module loader

```

384 \begingroup\expandafter\expandafter\expandafter\endgroup
385 \expandafter\ifx\csname RequirePackage\endcsname\relax
386   \input luatex-loader.sty\relax
387 \else
388   \RequirePackage{luatex-loader}[2009/04/10]%
389 \fi
390 \LuT@AtEnd
391 </package>
392 <*loader>

      Reload check, especially if the package is not used with LATEX.
393 \begingroup
394   \catcode44 12 % ,
395   \catcode45 12 % -
396   \catcode46 12 % .
397   \catcode58 12 % :
398   \catcode64 11 % @
399   \expandafter\let\expandafter\x\csname ver@luatex-loader.sty\endcsname
400   \ifcase 0%
401     \ifx\x\relax % plain
402   \else
403     \ifx\x\empty % LaTeX
404   \else
405     1%
406   \fi
407   \fi
408 \else
409   \catcode35 6 % #
410   \catcode123 1 % {

```

```

411      \catcode125 2 % }
412      \expandafter\ifx\csname PackageInfo\endcsname\relax
413          \def\x#1#2{%
414              \immediate\write-1{Package #1 Info: #2.}%
415          }%
416      \else
417          \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
418      \fi
419      \x{luatex-loader}{The package is already loaded}%
420      \endgroup
421      \expandafter\endinput
422  \fi
423 \endgroup

Package identification:
424 \begingroup
425   \catcode35 6 % #
426   \catcode40 12 % (
427   \catcode41 12 % )
428   \catcode44 12 % ,
429   \catcode45 12 % -
430   \catcode46 12 % .
431   \catcode47 12 % /
432   \catcode58 12 % :
433   \catcode64 11 % @
434   \catcode123 1 % {
435   \catcode125 2 % }
436   \expandafter\ifx\csname ProvidesPackage\endcsname\relax
437       \def\x#1#2#3[#4]{\endgroup
438           \immediate\write-1{Package: #3 #4}%
439           \xdef#1{#4}%
440       }%
441   \else
442       \def\x#1#2[#3]{\endgroup
443           #2[{#3}]%
444           \ifx#1\undefined
445               \xdef#1{#3}%
446           \fi
447           \ifx#1\relax
448               \xdef#1{#3}%
449           \fi
450       }%
451   \fi
452 \expandafter\x\csname ver@luatex-loader.sty\endcsname
453 \ProvidesPackage{luatex-loader}%
454 [2009/04/10 v0.2 Lua module loader (HO)]
```

455 \begingroup

456 \catcode10 12 % ^^J

457 \catcode34 12 % "

458 \catcode39 12 % '

459 \catcode40 12 % (

460 \catcode41 12 %)

461 \catcode44 12 % ,

462 \catcode46 12 % .

463 \catcode60 12 % <

464 \catcode61 12 % =

465 \catcode95 12 % _ (other!)

466 \catcode96 12 % '

467 \endlinechar=10 %

468 \ifnum\luatexversion<36 %
469 \directlua0%
470 \else %
471 \expandafter\directlua %

```

472 \fi %
473 {%
474   do
475     local script = "oberdiek.luatex.lua"
476     local file = kpse.find_file(script, "texmfscripts")
477     if file then
478       texio.write_nl("(" .. file .. ")")
479       dofile(file)
480     else
481       error("File '" .. script .. "' not found")
482     end
483   end
484 }
485 \endgroup%
486 
```

2.11 Lua script

Currently LUATEX does not use KPSE when searching for module files. The following Lua script implements a workaround. It extends `package.loader` by another search method. Modules are found by the module name with extension `.lua` similar to

```
kpsewhich --format=texmfscripts <module>.lua
```

Unhappily `kpsewhich` does not support directory components in the file name. Therefore a module `a.b.c` cannot be installed as `a/b/c.lua`. The script must be named `a.b.c.lua`.

```

487 <*lua>
488 module("oberdiek.luatex", package.seeall)
489 function kpse_module_loader(module)
490   local script = module .. ".lua"
491   local file = kpse.find_file(script, "texmfscripts")
492   if file then
493     local loader, error = loadfile(file)
494     if loader then
495       texio.write_nl("(" .. file .. ")")
496       return loader
497     end
498     return "\n\t[oberdiek.luatex.kpse_module_loader] Loading error:\n\t"
499     .. error
500   end
501   return "\n\t[oberdiek.luatex.kpse_module_loader] Search failed"
502 end
503 table.insert(package.loaders, kpse_module_loader)
504 
```

3 Test

```

505 <*test2>
506 \documentclass{article}
507 \def\LoadCommand{%
508   \RequirePackage{luatex}[2009/04/10]%
509 }
510 
```

- 511 <*test3>
- 512 \documentclass{article}
- 513 \def\LoadCommand{%
- 514 \RequirePackage{luatex-loader}[2009/04/10]%
- 515 }

```

516 </test3>

```

3.1 Catcode checks for loading

```

517 <*test1>
518 \catcode`#=1 %
519 \catcode`#=2 %
520 \catcode`#=6 %
521 \catcode`@=11 %
522 \expandafter\ifx\csname count@\endcsname\relax
523   \countdef{count}@=255 %
524 \fi
525 \expandafter\ifx\csname @firstofone\endcsname\relax
526   \long\def{@firstofone#1}%
527 \fi
528 \expandafter\ifx\csname @firstofone\endcsname\relax
529   \long\def{@firstofone#1{#1}}%
530 \fi
531 \expandafter\ifx\csname loop\endcsname\relax
532   \expandafter\@firstofone
533 \else
534   \expandafter\@gobble
535 \fi
536 {%
537   \def{loop#1\repeat}{%
538     \def{body{#1}}%
539     \iterate
540   }%
541   \def{\iterate}{%
542     \body
543     \let{\next}{\iterate}
544   \else
545     \let{\next}{\relax}
546   \fi
547   \next
548 }%
549   \let{\repeat}{\fi
550 }%
551 \def{\RestoreCatcodes}{}
552 \count@=0 %
553 \loop
554   \edef{\RestoreCatcodes}{%
555     \RestoreCatcodes
556     \catcode{\the\count@=\the\catcode}\count@\relax
557   }%
558 \ifnum{\count@<255}%
559   \advance{\count@ 1}%
560 \repeat
561
562 \def{\RangeCatcodeInvalid#1#2}{%
563   \count@=#1\relax
564   \loop
565     \catcode{\count@=15}%
566   \ifnum{\count@<#2}\relax
567     \advance{\count@ 1}%
568   \repeat
569 }
570 \expandafter\ifx\csname LoadCommand\endcsname\relax
571   \def{\LoadCommand}{\input luatex.sty\relax}%
572 \fi
573 \def{\Test}{%
574   \RangeCatcodeInvalid{0}{47}%
575   \RangeCatcodeInvalid{58}{64}%

```

```

576  \RangeCatcodeInvalid{91}{96}%
577  \RangeCatcodeInvalid{123}{255}%
578  \catcode`\@=12 %
579  \catcode`\|=0 %
580  \catcode`\{=1 %
581  \catcode`\}=2 %
582  \catcode`\#=6 %
583  \catcode`\[=12 %
584  \catcode`\]=12 %
585  \catcode`\%=14 %
586  \catcode`\ =10 %
587  \catcode`13=5 %
588  \LoadCommand
589  \RestoreCatcodes
590 }
591 \Test
592 \csname @@end\endcsname
593 \end
594 
```

3.2 Catcode tables

3.2.1 Predefined catcode tables

```

595 <*test4>
596 \NeedsTeXFormat{LaTeX2e}

Remember LATEX's initial catcodes in count registers starting at \TestLaTeX.
597 \count0=0 %
598 \chardef\TestLaTeX=1000 %
599 \chardef\TestMax=300 %
600 \loop
601   \count\numexpr\TestLaTeX+\count0\relax=\catcode\count0 %
602 \ifnum\count0<\TestMax
603   \advance\count0 by 1 %
604 \repeat
605 \documentclass{minimal}
606 \usepackage{luatex}[2009/04/10]
607 \usepackage{qstest}
608 \IncludeTests{*}
609 \LogTests{log}{*}{*}
610 \makeatletter
611 \def\Check#1{%
612   \Expect{\the\count0=\the\catcode\count0}%
613   *{\the\count0=#1}%
614 }
615 \newcount\scratch
616 \def\Test#1#2{%
617   \begin{qstest}{CatcodeTable#1}{CatcodeTable#1}%
618     \catcodetable\csname CatcodeTable#1\endcsname
619     \count0=\z@
620     \loop
621       \scratch=#2\relax
622       \Expect{\the\count0=\the\catcode\count0}%
623       *{\the\count0=\the\scratch}%
624     \ifnum\count0<\TestMax
625       \advance\count0\@ne
626     \repeat
627   \end{qstest}%
628 }
629 \Test{LaTeX}{\the\count\numexpr\TestLaTeX+\count0}%
630 \Test{String}{\ifnum\count0=32 10\else 12\fi}%
631 \Test{Other}{12}%
632 \initcatcodetable99 %

```

```

633 \Test{IniTeX}{%
634   0\relax
635   \begingroup
636     \catcodetable99 %
637     \global\scratch=\the\catcode\count@
638   \endgroup
639 }

```

3.2.2 Catcode table number stack

```

640 \begin{qstest}{CatcodeTableNumStack}{CatcodeTableNumStack}
641   \def\TestStack#1{%
642     \Expect*\{\LuT@NumStack\}{#1}%
643   }%
644   \TestStack{0}%
645   \PushCatcodeTableNumStack
646   \TestStack{{0}0}%
647   \@firstofone{%
648     \begingroup
649       \initcatcodetable12 %
650       \catcodetable12 %
651       \PushCatcodeTableNumStack
652       \TestStack{{12}{0}0}%
653       \PopCatcodeTableNumStack
654       \TestStack{{0}0}%
655       \PopCatcodeTableNumStack
656       \TestStack{0}%
657       \def\TestWarning{Missing empty stack warning}%
658       \def\@PackageWarning#1#2{\def\TestWarning{empty stack}}%
659       \PopCatcodeTableNumStack
660       \TestStack{0}%
661       \Expect*\{\TestWarning\}{empty stack}%
662     \endgroup
663   }%
664 \end{qstest}

```

3.2.3 Catcode table stack

```

665 \begin{qstest}{CatcodeTableStack}{CatcodeTableStack}
666   \def\TestStack#1{%
667     \Expect*\{\the\CatcodeTableStack\}{#1}%
668   }%
669   \TestStack{0}%
670   \IncCatcodeTableStack
671   \TestStack{2}%
672   \IncCatcodeTableStack
673   \TestStack{4}%
674   \begingroup
675     \IncCatcodeTableStack
676     \TestStack{6}%
677   \endgroup
678   \TestStack{6}%
679   \begingroup
680     \DecCatcodeTableStack
681     \TestStack{4}%
682   \endgroup
683   \TestStack{4}%
684   \DecCatcodeTableStack
685   \TestStack{2}%
686   \DecCatcodeTableStack
687   \TestStack{0}%
688   \begingroup
689     \def\TestError{Missing error}%
690     \def\@PackageError#1#2#3{%
691       \def\TestError{Empty stack}%

```

```

692      }%
693      \DecCatcodeTableStack
694      \TestStack{0}%
695      \Expect*\{\TestError\}{Empty stack}%
696  \endgroup
697 \end{qstest}

```

3.2.4 Catcode regime macros

```

698 \begin{qstest}{CatcodeRegime}{CatcodeRegime}
699   \def\TestStacks#1#2#3{%
700     \Expect*\{\the\catcodetable\}{#1}%
701     \Expect*\{\the\CatcodeTableStack\}{#2}%
702     \Expect*\{\LuT@NumStack\}{#3}%
703   }%
704   \TestStacks{0}{0}{0}%
705   \catcode`|=7 %
706   \BeginCatcodeRegime\CatcodeTableLaTeX
707   \TestStacks{2}{2}{0}%
708   \Expect*\{\the\catcode`|}{12}%
709   \EndCatcodeRegime
710   \TestStacks{0}{0}{0}%
711   \Expect*\{\the\catcode`|}{7}%
712 \end{qstest}

```

3.3 Attribute allocation

```

713 \begin{qstest}{Attributes}{Attributes}
714   \newattribute\TestAttr
715   \Expect*\{\meaning\TestAttr\}%
716   *{\string\attribute\number\allocationnumber}%
717   \Expect*\{\the\allocationnumber}{0}%
718   \begingroup
719     \newattribute\TestAttr
720     \Expect*\{\the\allocationnumber}{1}%
721   \endgroup
722   \Expect*\{\the\allocationnumber}{0}%
723   \Expect*\{\meaning\TestAttr}*{\string\attribute1}%
724   \Expect*\{\the\TestAttr}{-1}%
725   \def\Test#1{%
726     \setattribute\TestAttr{#1}%
727     \Expect*\{\the\TestAttr}{#1}%
728   }%
729   \Test{0}%
730   \Test{1}%
731   \Test{-1}%
732   \Test{123}%
733   \unsetattribute\TestAttr
734   \Expect*\{\the\TestAttr}{-1}%
735   \begingroup
736     \Expect*\{\the\TestAttr}{-1}%
737     \Test{1234}%
738   \endgroup
739   \Expect*\{\the\TestAttr}{-1}%
740 \end{qstest}

```

3.4 Lua states

```

741 \begin{qstest}{LuaState}{LuaState}
742   \newluastate\TestLuaState
743   \Expect*\{\number\TestLuaState}{1}%
744   \newluastate\TestLuaState
745   \Expect*\{\number\TestLuaState}{2}%
746 \end{qstest}
747 \@@end

```

```

748 </test4>
3.5 Short test for plain-TEX
749 <*test5>
750 \input luatex.sty\relax
751 \newluastate\TestLuaState
752 \newattribute\TestAttr
753 \setattribute\TestAttr{10}
754 \unsetattribute\TestAttr
755 \newcatcodetable\TestCTa
756 \begingroup
757   \SetCatcodeRange{'A}{`Z}{12}%
758 \endgroup
759 \BeginCatcodeRegime\CatcodeTableLaTeX
760 \EndCatcodeRegime
761 \end
762 </test5>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/luatex.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/luatex.pdf Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:install/macros/latex/contrib/oberdiek.tds.zip

TDS refers to the standard “A Directory Structure for T_EX Files” (CTAN:tds/tds.pdf). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex luatex.dtx
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
luatex.sty           → tex/generic/oberdiek/luatex.sty
luatex-loader.sty   → tex/generic/oberdiek/luatex-loader.sty
oberdiek.luatex.lua → scripts/oberdiek/oberdiek.luatex.lua
luatex.pdf          → doc/latex/oberdiek/luatex.pdf
test/luatex-test1.tex → doc/latex/oberdiek/test/luatex-test1.tex
test/luatex-test2.tex → doc/latex/oberdiek/test/luatex-test2.tex
test/luatex-test3.tex → doc/latex/oberdiek/test/luatex-test3.tex
test/luatex-test4.tex → doc/latex/oberdiek/test/luatex-test4.tex
test/luatex-test5.tex → doc/latex/oberdiek/test/luatex-test5.tex
luatex.dtx          → source/latex/oberdiek/luatex.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk luatex.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{luatex.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex luatex.dtx
makeindex -s gind.ist luatex.idx
pdflatex luatex.dtx
makeindex -s gind.ist luatex.idx
pdflatex luatex.dtx
```

5 History

[2007/12/12 v0.1]

- First public version.

- Requires package `ifluatex` in version 2.0 to ensure `\luatexversion`.
- Updates the call of `\directlua`, the syntax has changed in LUATEX 0.36.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	B
<code>\#</code>	520, 582
<code>\%</code>	585
<code>\:</code>	188, 189, 190, 191, 192, 195
<code>\@</code>	521, 578
<code>\@@end</code>	747
<code>\@INTERNAL@ERROR</code>	227
<code>\@PackageError</code>	114, 211, 286, 295, 690
<code>\@PackageWarning</code>	364, 658
<code>\@PackageWarningNoLine</code>	127
<code>\@car</code>	160, 367
<code>\@cdr</code>	163, 369
<code>\@ehc</code>	116, 214
<code>\@ehd</code>	288, 297
<code>\@empty</code>	148
<code>\@firstofone</code> . . .	<u>154</u> , 324, 529, 532, 647
<code>\@firstoftwo</code>	<u>157</u> , 168
<code>\@gobble</code>	<u>151</u> , 526, 534
<code>\@ifnch</code>	174, <u>176</u> , 193
<code>\@ifnextchar</code>	168, <u>170</u>
<code>\@ifstar</code>	<u>166</u>
<code>\@let@token</code>	174, 177, 180, 193
<code>\@makeother</code>	323, 343, 344, 345, 346, 347, 351
<code>\@ne</code>	238, 250, 313, 625
<code>\@nil</code>	161, 164, 367, 369
<code>\@spoken</code>	177, 188
<code>\@tempcnta</code> . . .	<u>197</u> , 302, 307, 311, 312, 313
<code>\@tempcntb</code>	<u>200</u> , 303, 308, 311
<code>\@undefined</code>	53, 206, 444
<code>\@xifnch</code>	178, <u>191</u>
<code>\[</code>	583
<code>\\"</code>	579
<code>\{</code>	518, 580
<code>\}</code>	519, 581
<code>\]</code>	584
<code>\ </code>	705, 708, 711
<code>\u</code>	586
A	D
<code>\advance</code>	238, 250, 272,
.	<u>284</u> , 293, 313, 559, 567, 603, 625
<code>\allocationnumber</code>	
.	239, 240, 241, 251, 252, 254,
.	<u>273</u> , 274, 276, 716, 717, 720, 722
<code>\attribute</code>	254, 256, 716, 723
<code>\attributedef</code>	252
E	E
	<code>\empty</code>
	12, 403

\end	593, 627, 664, 697, 712, 740, 746, 761	
\EndCatcodeRegime	380, 709, 760
\endcsname	8, 21, 45, 61, 68, 105, 121, 126, 148, 151, 154, 157, 160, 163, 166, 197, 198, 200, 201, 204, 385, 399, 412, 436, 452, 522, 525, 528, 531, 570, 592, 618	
\endinput	30, 118, 421
\endlinechar	467
\errmessage	243, 256, 279
\Expect	612, 622, 642, 661, 667, 695, 700, 701, 702, 708, 711, 715, 717, 720, 722, 723, 724, 727, 734, 736, 739, 743, 745
	F	
\futurelet	174, 193
	G	
\globbox	146
\globcount	143
\globdimen	144
\globskip	145
	I	
\ifcase	9, 218, 400
\ifluatex	112
\ifnum	. 132, 237, 249, 270, 283, 292, 311, 468, 558, 566, 602, 624, 630	
\ifx	10, 12, 21, 45, 53, 56, 105, 121, 126, 148, 151, 154, 157, 160, 163, 166, 177, 180, 197, 200, 204, 206, 209, 217, 363, 385, 401, 403, 412, 436, 444, 447, 522, 525, 528, 531, 570
\immediate	23, 47, 414, 438
\IncCatcodeTableStack	282, 376, 670, 672, 675
\IncludeTests	608
\initcatcodetable	321, 632, 649
\input	106, 107, 386, 571, 750
\iterate	539, 541, 543
	L	
\LoadCommand	507, 513, 571, 588
\LogTests	609
\loop	310, 537, 553, 564, 600, 620
\luastate	241, 243
\luatexversion	468
\LuT@AllocAttribute	246, 249, 250, 251	
\LuT@AllocCatcodeTable	265, 270, 272, 273
\LuT@AllocLuaState	234, 237, 238, 239	
\LuT@AtEnd	81, 82, 117, 390
\LuT@newcommand	203, 236, 248, 259, 262, 269, 282, 291, 300, 357, 362, 373, 380
\LuT@NumStack	356, 358, 359, 363, 367, 368, 369, 642, 702
\LuT@NumStackEmpty	355, 356, 363
\LuT@temp	. 131, 136, 137, 138, 139, 140, 141, 142, 188, 195, 301, 315	
	M	
\m@ne	247, 263, 266
\makeatletter	610
\meaning	715, 723
\MessageBreak	212
	N	
\n	498, 501
\NeedsTeXFormat	596
\newattribute	3, 248, 714, 719, 752	
\newbox	146
\newcatcodetable	4, 269, 317, 318, 319, 320, 755
\newcommand	232
\newcount	. 143, 234, 246, 265, 267, 615	
\newdimen	144
\newluastate	3, 236, 742, 744, 751	
\newskip	145
\next	543, 545, 547
\number	716, 743, 745
\numexpr	260, 307, 308, 309, 375, 601, 629	
	P	
\PackageInfo	26, 417
\PopCatcodeTableNumStack	362, 382, 653, 655, 659
\ProvidesPackage	62, 453
\PushCatcodeTableNumStack	5, 357, 374, 645, 651
	R	
\RangeCatcodeInvalid	562, 574, 575, 576, 577
\repeat	314, 537, 549, 560, 568, 604, 626	
\RequirePackage	109, 110, 123, 388, 508, 514
\reserved@a	172, 181
\reserved@b	173, 183
\reserved@c	178, 181, 183, 186
\reserved@d	171, 180
\RestoreCatcodes	551, 554, 555, 589
	S	
\savecatcodetable	341, 350, 352, 377
\scratch	615, 621, 623, 637
\setattribute	3, 259, 726, 753	
\SetCatcodeRange	5, 300, 327, 331, 348, 349, 757
	T	
\t	498, 501
\Test	. 573, 591, 616, 629, 630, 631, 633, 725, 729, 730, 731, 732, 737	
\TestAttr	714, 715, 719, 723, 724, 726, 727, 733, 734, 736, 739, 752, 753, 754
\TestCTa	755
\TestError	689, 691, 695
\TestLaTeX	598, 601, 629
\TestLuaState	. 742, 743, 744, 745, 751	
\TestMax	599, 602, 624
\TestStack	641, 644, 646, 652, 654, 656, 660, 666, 669, 671, 673, 676, 678, 681, 683, 685, 687, 694	

\TestStacks	699, 704, 707, 710	\unsetattribute	4, 253, 262, 733, 754
\TestWarning	657, 658, 661	\usepackage	606, 607
\the	69, 70, 71, 72, 83, 241, 254, 276, 302, 303, 304, 359, 556, 612, 613, 622, 623, 629, 637, 667, 700, 701, 708, 711, 717, 720, 722, 724, 727, 734, 736, 739		W
\TMP@EnsureCode	80, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103	\wlog	241, 254, 275
\tw@	272, 284	\write	23, 47, 414, 438
			X
		\x	8, 10, 12, 22, 26, 28, 46, 51, 61, 67, 75, 399, 401, 403, 413, 417, 419, 437, 442, 452
			Z
U		\z@	235, 268, 292, 365, 619
\unless	311		