

# The makerobust package

Heiko Oberdiek  
<oberdiek@uni-freiburg.de>

2006/03/18 v1.0

## Abstract

Package makerobust provides `\MakeRobustCommand` that converts an existing macro to a robust one.

## Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>User interface</b>                     | <b>1</b> |
| 1.1      | Example . . . . .                         | 2        |
| <b>2</b> | <b>Implementation</b>                     | <b>2</b> |
| <b>3</b> | <b>Installation</b>                       | <b>3</b> |
| 3.1      | Download . . . . .                        | 3        |
| 3.2      | Bundle installation . . . . .             | 3        |
| 3.3      | Package installation . . . . .            | 3        |
| 3.4      | Refresh file name databases . . . . .     | 4        |
| 3.5      | Some details for the interested . . . . . | 4        |
| <b>4</b> | <b>History</b>                            | <b>4</b> |
|          | [2006/03/18 v1.0] . . . . .               | 4        |
| <b>5</b> | <b>Index</b>                              | <b>5</b> |

## 1 User interface

L<sup>A</sup>T<sub>E</sub>X offers `\DeclareRobustCommand` to define a robust macro that does not break if it is used in moving arguments. Sometimes a macro is already defined, but not robust. For example, `\(` and `\)` are not robust, inside `\section` the user must use `\protect` explicitly. This could be avoided by making `\(` and `\)` robust.

`\MakeRobustCommand{⟨cmd⟩}`

`\MakeRobustCommand` redefines the macro `⟨cmd⟩` by using `\DeclareRobustCommand` and the existing definition of the macro `⟨cmd⟩`.

- It is an error if `⟨cmd⟩` is undefined. If you want to define a robust command, then you can use `\DeclareRobustCommand` directly.
- If the macro has previously been defined by `\DeclareRobustCommand` then the redefinition of `\MakeRobustCommand` is omitted, because the macro is already robust. Only an information entry is written to the `.log` file. Thus you do not get a warning or an error if the macro is already robust because of an updated L<sup>A</sup>T<sub>E</sub>X or package that defines the macro.

- Two macros are defined for a macro, defined by `\DeclareRobustCommand`. Example:

```
\DeclareRobustCommand{\foobar}{definition text}
```

Then the macro “`\foobar`” contains the protection code and, depending on the protection mode, calls the internal macro “`\foobar` ”. Notice the space at the end of the macro name. This internal macro “`\foobar` ” now contains the definition “`definition text`”, given in `\DeclareRobustCommand`.

Sometimes it can happen, that the internal macro already exists. This can be caused by a previous `\DeclareRobustCommand` followed by `\renewcommand`. Then the redefinition by `\MakeRobustCommand` would be safe.

However, it can also be possible that the macro is already robust, using the internal macro, but with a different protection code. The redefinition by `\MakeRobustCommand` would then generate an infinite loop.

Therefore `\MakeRobustCommand` raises an error message, if the internal macro (with space at the end) already exists.

## 1.1 Example

```
1 \example
2 \documentclass{article}
3 \usepackage{makerobust}
4 \MakeRobustCommand{(
5 \MakeRobustCommand\)
6 \pagestyle{headings}
7 \begin{document}
8 \tableofcontents
9 \section{Einstein:  $E=mc^2$ }
10 \newpage
11 Second page.
12 \end{document}
13 \example
```

## 2 Implementation

```
14 \package
15 \NeedsTeXFormat{LaTeX2e}
16 \ProvidesPackage{makerobust}%
17 [2006/03/18 v1.0 Making a macro robust (HO)]%
18 \def\MakeRobustCommand#1{%
19   \begingroup
20   \ifundefined{\expandafter\@gobble\string#1}{%
21     \endgroup
22     \PackageError{makerobust}{%
23       Macro \string'\string#1\string' is not defined%
24     }\@ehc
25   }{%
26     \global\let\MR@temp#1%
27     \let#1\@undefined
28     \expandafter\let\expandafter\MR@temp
29       \csname\expandafter\@gobble\string#1\endcsname
30     \DeclareRobustCommand#1{%
31       \ifx#1\MR@temp
32         \endgroup
33         \PackageInfo{makerobust}{%
34           \string'\string#1\string' is already robust%
35         }%
36     \else
37       \ifundefined{MR@temp}{%

```

```

38      \global\let\MR@gtemp#1%
39      \endgroup
40      \expandafter\let\csname\expandafter\@gobble\string#1 \endcsname#1%
41      \let#1\MR@gtemp
42  }{%
43      \endgroup
44      \PackageError{makerobust}{%
45          Internal macro \string'\string#1 \string' already exists%
46      }\@ehc
47  }%
48  \fi
49  }%
50  }
51 \</package>

```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/makerobust.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/makerobust.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain-T<sub>E</sub>X:

```
tex makerobust.dtx
```

---

<sup>1</sup><http://ftp.ctan.org/tex-archive/>

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
makerobust.sty      → tex/latex/oberdiek/makerobust.sty
makerobust.pdf       → doc/latex/oberdiek/makerobust.pdf
makerobust-example.tex → doc/latex/oberdiek/makerobust-example.tex
makerobust.dtx       → source/latex/oberdiek/makerobust.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 3.4 Refresh file name databases

If your  $\text{T}_{\text{E}}\text{X}$  distribution (`te $\text{T}_{\text{E}}\text{X}$` , `mik $\text{T}_{\text{E}}\text{X}$` , ...) relies on file name databases, you must refresh these. For example, `te $\text{T}_{\text{E}}\text{X}$`  users run `texhash` or `mktextlsr`.

### 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk makerobust.pdf unpack_files output .
```

**Unpacking with  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ .** The `.dtx` chooses its action depending on the format:

**plain- $\text{T}_{\text{E}}\text{X}$ :** Run `docstrip` and extract the files.

**$\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ :** Generate the documentation.

If you insist on using  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$  for `docstrip` (really, `docstrip` does not need  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{makerobust.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdf $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$` :

```
pdflatex makerobust.dtx
makeindex -s gind.ist makerobust.idx
pdflatex makerobust.dtx
makeindex -s gind.ist makerobust.idx
pdflatex makerobust.dtx
```

## 4 History

[2006/03/18 v1.0]

- First version.

## 5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols               |            | M                  |                |
|-----------------------|------------|--------------------|----------------|
| \(                    | 4, 9       | \MakeRobustCommand | 1, 4, 5, 18    |
| \)                    | 5, 9       | \MR@gtemp          | 26, 31, 38, 41 |
| \@ehc                 | 24, 46     | \MR@temp           | 28             |
| \@gobble              | 20, 29, 40 | N                  |                |
| \@ifundefined         | 20, 37     | \NeedsTeXFormat    | 15             |
| \@undefined           | 27         | \newpage           | 10             |
| B                     |            | P                  |                |
| \begin                | 7          | \PackageError      | 22, 44         |
| C                     |            | \PackageInfo       | 33             |
| \csname               | 29, 40     | \pagestyle         | 6              |
| D                     |            | \ProvidesPackage   | 16             |
| \DeclareRobustCommand | 30         | S                  |                |
| \documentclass        | 2          | \section           | 9              |
| E                     |            | T                  |                |
| \end                  | 12         | \tableofcontents   | 8              |
| \endcsname            | 29, 40     | U                  |                |
| I                     |            | \usepackage        | 3              |
| \ifx                  | 31         |                    |                |