

The pdfcol package

Heiko Oberdiek*

<heiko.oberdiek at gmail.com>

2016/05/16 v1.3

Abstract

Since version 1.40 pdfTeX supports color stacks. The driver file `pdftex.def` for package `color` defines and uses a main color stack since version v0.04b. Package `pdfcol` is intended for package writers. It defines macros for setting and maintaining new color stacks.

Contents

| | | |
|----------|--|-----------|
| 1 | Documentation | 2 |
| 1.1 | Requirements | 2 |
| 1.2 | Interface | 2 |
| 2 | Implementation | 3 |
| 2.1 | Reload check and package identification | 3 |
| 2.2 | Catcodes | 4 |
| 2.3 | Check requirements | 5 |
| 2.3.1 | Check package <code>luacolor</code> | 5 |
| 2.3.2 | Check PDF mode | 6 |
| 2.3.3 | Check version of pdfTeX | 6 |
| 2.3.4 | Check <code>pdftex.def</code> | 6 |
| 2.4 | Enabled interface macros | 7 |
| 2.5 | Disabled interface macros | 8 |
| 3 | Test | 9 |
| 3.1 | Catcode checks for loading | 9 |
| 3.2 | Very simple test | 11 |
| 3.3 | Detection of package <code>luacolor</code> | 12 |
| 4 | Installation | 12 |
| 4.1 | Download | 12 |
| 4.2 | Bundle installation | 12 |
| 4.3 | Package installation | 13 |
| 4.4 | Refresh file name databases | 13 |
| 4.5 | Some details for the interested | 13 |
| 5 | Catalogue | 14 |

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

| | |
|-------------------|-----------|
| 6 History | 14 |
| [2007/09/09 v1.0] | 14 |
| [2007/12/09 v1.1] | 15 |
| [2007/12/12 v1.2] | 15 |
| [2016/05/16 v1.3] | 15 |
| 7 Index | 15 |

1 Documentation

Version 1.40 of pdfTeX adds new primitives `\pdfcolorstackinit` and `\pdfcolorstack`. Now color stacks can be defined and used. A main color stack is maintained by the driver file `pdftex.def` similar to dvips or dvi_{pdfm}. However the number of color stacks is not limited to one in pdfTeX. Thus further color problems can now be solved, such as footnotes across pages or text that is set in parallel columns (e.g. packages `parallel` or `parcolumn`). Unlike the main color stack, the support by additional color stacks cannot be done in a transparent manner.

This package `pdfcol` provides an easier interface to additional color stacks without the need to use the low level primitives.

1.1 Requirements

- pdfTeX 1.40 or greater.
- pdfTeX in PDF mode. (I don't know a DVI driver that support several color stacks.)
- `pdftex.def` 2007/01/02 v0.04b.

Package `pdfcol` checks the requirements and sets switch `\ifpdfcolAvailable` accordingly.

1.2 Interface

`\ifpdfcolAvailable`

If the requirements of section 1.1 are met the switch `\ifpdfcolAvailable` behaves as `\iftrue`. Otherwise the other interface macros in this section will be disabled with a message. Also the first use of such a macro will print a message. The messages are print to the `.log` file only if pdfTeX is not used in PDF mode.

`\pdfcolErrorNoStacks`

The first call of `\pdfcolErrorNoStacks` prints an error message, if color stacks are not available.

`\pdfcolInitStack {name}`

A new color stack is initialized by `\pdfcolInitStack`. The `name` is used for indentifying the stack. It usually consists of letters and digits. (The name must survive a `\csname`.)

The intension of the macro is the definition of an additional color stack. Thus the stack is not page bounded like the main color stack. Black (0 g 0 G) is used

as initial color value. And colors are written with modifier `direct` that means without setting the current transfer matrix and changing the current point (see documentation of pdfTeX for `\pdfliteral direct{...}`).

`\pdfcolIfStackExists {<name>} {<then>} {<else>}`

Macro `\pdfcolIfStackExists` checks whether color stack `<name>` exists. In case of success argument `<then>` is executed and `<else>` otherwise.

`\pdfcolSwitchStack {<name>}`

Macro `\pdfcolSwitchStack` switches the color stack. The color macros of package `color` (or `xcolor`) now uses the new color stack with name `<name>`.

`\pdfcolSetCurrentColor`

Macro `\pdfcolSetCurrentColor` replaces the topmost entry of the stack by the current color (`\current@color`).

`\pdfcolSetCurrent {<name>}`

Macro `\pdfcolSetCurrent` sets the color that is read in the top-most entry of color stack `<name>`. If `<name>` is empty, the default color stack is used.

2 Implementation

1 `(*package)`

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```

2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^~M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@pdfcol.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17 \def\empty{}%
18 \ifx\x\empty % LaTeX, first loading,
19 % variable is initialized, but \ProvidesPackage not yet seen
20 \else
21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
```

```

25     \else
26       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27     \fi
28     \x{pdfcol}{The package is already loaded}%
29     \aftergroup\endinput
30   \fi
31 \fi
32 \endgroup%
Package identification:
33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34   \catcode13=5 % ^~M
35   \endlinechar=13 %
36   \catcode35=6 % #
37   \catcode39=12 % '
38   \catcode40=12 % (
39   \catcode41=12 % )
40   \catcode44=12 % ,
41   \catcode45=12 % -
42   \catcode46=12 % .
43   \catcode47=12 % /
44   \catcode58=12 % :
45   \catcode64=11 % @
46   \catcode91=12 % [
47   \catcode93=12 % ]
48   \catcode123=1 % {
49   \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51   \def\x#1#2#3[#4]{\endgroup
52     \immediate\write-1{Package: #3 #4}%
53     \xdef#1{#4}%
54   }%
55 \else
56   \def\x#1#2[#3]{\endgroup
57     #2[#{#3}]%
58     \ifx#1\@undefined
59       \xdef#1{#3}%
60     \fi
61     \ifx#1\relax
62       \xdef#1{#3}%
63     \fi
64   }%
65 \fi
66 \expandafter\x\csname ver@pdfcol.sty\endcsname
67 \ProvidesPackage{pdfcol}%
68 [2016/05/16 v1.3 Handle new color stacks for pdfTeX (HO)]%

```

2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%
70   \catcode13=5 % ^~M
71   \endlinechar=13 %
72   \catcode123=1 % {
73   \catcode125=2 % }
74   \catcode64=11 % @
75   \def\x{\endgroup
76     \expandafter\edef\csname PDFCOL@AtEnd\endcsname{%
77       \endlinechar=\the\endlinechar\relax
78       \catcode13=\the\catcode13\relax

```

```

79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\PDFCOL@AtEnd{%
96     \PDFCOL@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{39}{12}% '
102 \TMP@EnsureCode{40}{12}% (
103 \TMP@EnsureCode{41}{12}% )
104 \TMP@EnsureCode{43}{12}% +
105 \TMP@EnsureCode{44}{12}% ,
106 \TMP@EnsureCode{46}{12}% .
107 \TMP@EnsureCode{47}{12}% /
108 \TMP@EnsureCode{91}{12}% [
109 \TMP@EnsureCode{93}{12}% ]
110 \TMP@EnsureCode{96}{12}% '
111 \edef\PDFCOL@AtEnd{\PDFCOL@AtEnd\noexpand\endinput}

```

2.3 Check requirements

\PDFCOL@RequirePackage

```

112 \begingroup\expandafter\expandafter\expandafter\endgroup
113 \expandafter\ifx\csname RequirePackage\endcsname\relax
114   \def\PDFCOL@RequirePackage#1[#2]{\input #1.sty\relax}%
115 \else
116   \def\PDFCOL@RequirePackage#1[#2]{%
117     \RequirePackage{#1}[#2]}%
118   }%
119 \fi

120 \PDFCOL@RequirePackage{ltxcmds}[2010/03/01]

```

ifpdfcolAvailable

```

121 \ltx@newif\ifpdfcolAvailable
122 \pdfcolAvailabletrue

```

2.3.1 Check package luacolor

```

123 \ltx@newif\ifPDFCOL@luacolor
124 \begingroup\expandafter\expandafter\expandafter\endgroup
125 \expandafter\ifx\csname ver@luacolor.sty\endcsname\relax
126   \PDFCOL@luacolorfalse
127 \else

```

```

128 \PDFCOL@luacolortrue
129 \fi

```

2.3.2 Check PDF mode

```

130 \PDFCOL@RequirePackage{infwarerr}[2007/09/09]
131 \PDFCOL@RequirePackage{ifpdf}[2007/09/09]
132 \ifcase\ifpdf\ifPDFCOL@luacolor 1\fi\else 1\fi0 %
133 \def\PDFCOL@Message{%
134   \@PackageWarningNoLine{pdfcol}%
135 }%
136 \else
137 \pdfcolAvailablefalse
138 \def\PDFCOL@Message{%
139   \@PackageInfoNoLine{pdfcol}%
140 }%
141 \PDFCOL@Message{%
142   Interface disabled because of %
143   \ifPDFCOL@luacolor
144     package 'luacolor'%
145   \else
146     missing PDF mode of pdfTeX%
147   \fi
148 }%
149 \fi

```

2.3.3 Check version of pdfTeX

```

150 \ifpdfcolAvailable
151 \begingroup\expandafter\expandafter\expandafter\endgroup
152 \expandafter\ifx\csname pdfcolorstack\endcsname\relax
153 \pdfcolAvailablefalse
154 \PDFCOL@Message{%
155   Interface disabled because of too old pdfTeX.\MessageBreak
156   Required is version 1.40+ for \string\pdfcolorstack
157 }%
158 \fi
159 \fi
160 \ifpdfcolAvailable
161 \begingroup\expandafter\expandafter\expandafter\endgroup
162 \expandafter\ifx\csname pdfcolorstack\endcsname\relax
163 \pdfcolAvailablefalse
164 \PDFCOL@Message{%
165   Interface disabled because of too old pdfTeX.\MessageBreak
166   Required is version 1.40+ for \string\pdfcolorstackinit
167 }%
168 \fi
169 \fi

```

2.3.4 Check pdftex.def

```

170 \ifpdfcolAvailable
171 \begingroup\expandafter\expandafter\expandafter\endgroup
172 \expandafter\ifx\csname @pdfcolorstack\endcsname\relax

```

Try to load package color if it is not yet loaded (L^AT_EX case).

```

173 \begingroup\expandafter\expandafter\expandafter\endgroup
174 \expandafter\ifx\csname ver@color.sty\endcsname\relax
175 \begingroup\expandafter\expandafter\expandafter\endgroup
176 \expandafter\ifx\csname documentclass\endcsname\relax
177 \else
178 \RequirePackage[pdftex]{color}\relax

```

```

179     \fi
180   \fi
181   \begingroup\expandafter\expandafter\expandafter\endgroup
182   \expandafter\ifx\csname @pdfcolorstack\endcsname\relax
183     \pdfcolAvailablefalse
184     \PDFCOL@Message{%
185       Interface disabled because 'pdftex.def'\MessageBreak
186       is not loaded or it is too old.\MessageBreak
187       Required is version 0.04b or greater%
188     }%
189   \fi
190 \fi
191 \fi
192 \let\pdfcolAvailabletrue\relax
193 \let\pdfcolAvailablefalse\relax

```

2.4 Enabled interface macros

```

194 \ifpdfcolAvailable

\pdfcolErrorNoStacks
195   \let\pdfcolErrorNoStacks\relax

\pdfcol@Value
196   \expandafter\ifx\csname pdfcol@Value\endcsname\relax
197   \def\pdfcol@Value{0 g 0 G}%
198   \fi

\pdfcol@LiteralModifier
199   \expandafter\ifx\csname pdfcol@LiteralModifier\endcsname\relax
200   \def\pdfcol@LiteralModifier{direct}%
201   \fi

\pdfcolInitStack
202   \def\pdfcolInitStack#1{%
203     \expandafter\ifx\csname pdfcol@Stack@#1\endcsname\relax
204       \global\expandafter\chardef\csname pdfcol@Stack@#1\endcsname=%
205       \pdfcolorstackinit\pdfcol@LiteralModifier{\pdfcol@Value}%
206       \relax
207       \@PackageInfo{pdfcol}{%
208         New color stack '#1' = \number\csname pdfcol@Stack@#1\endcsname
209       }%
210     \else
211       \@PackageError{pdfcol}{%
212         Stack '#1' is already defined%
213       }\@ehc
214     \fi
215   }%

\pdfcolIfStackExists
216   \def\pdfcolIfStackExists#1{%
217     \expandafter\ifx\csname pdfcol@Stack@#1\endcsname\relax
218     \expandafter\@secondoftwo
219   \else
220     \expandafter\@firstoftwo
221   \fi
222   }%

```

```

\@firstoftwo
223 \expandafter\ifx\csname @firstoftwo\endcsname\relax
224 \long\def\@firstoftwo#1#2{#1}%
225 \fi

\@secondoftwo
226 \expandafter\ifx\csname @secondoftwo\endcsname\relax
227 \long\def\@secondoftwo#1#2{#2}%
228 \fi

\pdfcolSwitchStack
229 \def\pdfcolSwitchStack#1{%
230 \pdfcolIfStackExists{#1}{%
231 \expandafter\let\expandafter\@pdfcolorstack
232 \csname pdfcol@Stack@#1\endcsname
233 }{%
234 \pdfcol@ErrorNoStack{#1}%
235 }%
236 }%

\pdfcolSetCurrentColor
237 \def\pdfcolSetCurrentColor{%
238 \pdfcolorstack\@pdfcolorstack set{\current@color}%
239 }%

\pdfcolSetCurrent
240 \def\pdfcolSetCurrent#1{%
241 \ifx\#1\%
242 \pdfcolorstack\@pdfcolorstack current\relax
243 \else
244 \pdfcolIfStackExists{#1}{%
245 \pdfcolorstack\csname pdfcol@Stack@#1\endcsname current\relax
246 }{%
247 \pdfcol@ErrorNoStack{#1}%
248 }%
249 \fi
250 }%

\pdfcol@ErrorNoStack
251 \def\pdfcol@ErrorNoStack#1{%
252 \@PackageError{pdfcol}{Stack '#1' does not exists}\@ehc
253 }%

```

2.5 Disabled interface macros

```

254 \else

\pdfcolErrorNoStacks
255 \def\pdfcolErrorNoStacks{%
256 \@PackageError{pdfcol}{%
257 Color stacks are not available%
258 }{%
259 Update pdfTeX (1.40) and 'pdftex.def' (0.04b) %
260 if necessary.\MessageBreak
261 Ensure that 'pdftex.def' is loaded %
262 (package 'color' or 'xcolor').\MessageBreak
263 Further messages can be found in TeX's %

```

```

264         protocol file '\jobname.log'.\MessageBreak
265     \MessageBreak
266     \@ehc
267 }%
268 \global\let\pdfcolErrorNoStacks\relax
269 }%

\PDFCOL@Disabled
270 \def\PDFCOL@Disabled{%
271     \PDFCOL@Message{%
272         pdfTeX's color stacks are not available%
273     }%
274     \global\let\PDFCOL@Disabled\relax
275 }%

\pdfcolInitStack
276 \def\pdfcolInitStack#1{%
277     \PDFCOL@Disabled
278 }%

\pdfcolIfStackExists
279 \long\def\pdfcolIfStackExists#1#2#3{#3}%

\pdfcolSwitchStack
280 \def\pdfcolSwitchStack#1{%
281     \PDFCOL@Disabled
282 }%

\pdfcolSetCurrentColor
283 \def\pdfcolSetCurrentColor{%
284     \PDFCOL@Disabled
285 }%

\pdfcolSetCurrent
286 \def\pdfcolSetCurrent#1{%
287     \PDFCOL@Disabled
288 }%

289 \fi
290 \PDFCOL@AtEnd%
291 \</package>

```

3 Test

3.1 Catcode checks for loading

```

292 \<test1>
293 \catcode'\{=1 %
294 \catcode'\}=2 %
295 \catcode'\#=6 %
296 \catcode'\@=11 %
297 \expandafter\ifx\csname count@\endcsname\relax
298     \countdef\count@=255 %
299 \fi
300 \expandafter\ifx\csname @gobble\endcsname\relax
301     \long\def\@gobble#1{}%

```

```

302 \fi
303 \expandafter\ifx\csname @firstofone\endcsname\relax
304 \long\def\@firstofone#1{#1}%
305 \fi
306 \expandafter\ifx\csname loop\endcsname\relax
307 \expandafter\@firstofone
308 \else
309 \expandafter\@gobble
310 \fi
311 {%
312 \def\loop#1\repeat{%
313 \def\body{#1}%
314 \iterate
315 }%
316 \def\iterate{%
317 \body
318 \let\next\iterate
319 \else
320 \let\next\relax
321 \fi
322 \next
323 }%
324 \let\repeat=\fi
325 }%
326 \def\RestoreCatcodes{}
327 \count@=0 %
328 \loop
329 \edef\RestoreCatcodes{%
330 \RestoreCatcodes
331 \catcode\the\count@=\the\catcode\count@\relax
332 }%
333 \ifnum\count@<255 %
334 \advance\count@ 1 %
335 \repeat
336
337 \def\RangeCatcodeInvalid#1#2{%
338 \count@=#1\relax
339 \loop
340 \catcode\count@=15 %
341 \ifnum\count@<#2\relax
342 \advance\count@ 1 %
343 \repeat
344 }
345 \def\RangeCatcodeCheck#1#2#3{%
346 \count@=#1\relax
347 \loop
348 \ifnum#3=\catcode\count@
349 \else
350 \errmessage{%
351 Character \the\count@\space
352 with wrong catcode \the\catcode\count@\space
353 instead of \number#3%
354 }%
355 \fi
356 \ifnum\count@<#2\relax
357 \advance\count@ 1 %
358 \repeat
359 }

```

```

360 \def\space{ }
361 \expandafter\ifx\csname LoadCommand\endcsname\relax
362 \def\LoadCommand{\input pdfcol.sty\relax}%
363 \fi
364 \def\Test{%
365 \RangeCatcodeInvalid{0}{47}%
366 \RangeCatcodeInvalid{58}{64}%
367 \RangeCatcodeInvalid{91}{96}%
368 \RangeCatcodeInvalid{123}{255}%
369 \catcode'\@=12 %
370 \catcode'\=0 %
371 \catcode'\%=14 %
372 \LoadCommand
373 \RangeCatcodeCheck{0}{36}{15}%
374 \RangeCatcodeCheck{37}{37}{14}%
375 \RangeCatcodeCheck{38}{47}{15}%
376 \RangeCatcodeCheck{48}{57}{12}%
377 \RangeCatcodeCheck{58}{63}{15}%
378 \RangeCatcodeCheck{64}{64}{12}%
379 \RangeCatcodeCheck{65}{90}{11}%
380 \RangeCatcodeCheck{91}{91}{15}%
381 \RangeCatcodeCheck{92}{92}{0}%
382 \RangeCatcodeCheck{93}{96}{15}%
383 \RangeCatcodeCheck{97}{122}{11}%
384 \RangeCatcodeCheck{123}{255}{15}%
385 \RestoreCatcodes
386 }
387 \Test
388 \csname @@end\endcsname
389 \end
390 </test1>

```

3.2 Very simple test

```

391 <*test2 | test3>
392 \NeedsTeXFormat{LaTeX2e}
393 \nofiles
394 \documentclass{article}
395 \usepackage{pdfcol}[2016/05/16]
396 \usepackage{qstest}
397 \IncludeTests{*}
398 \LogTests{log}{*}{*}
399 \begin{document}
400 \begin{qstest}{pdfcol}{}%
401 \makeatletter
402 <*test2>
403 \Expect*{\ifpdfcolAvailable true\else false\fi}{false}%
404 </test2>
405 <*test3>
406 \Expect*{\ifpdfcolAvailable true\else false\fi}{true}%
407 \Expect*{\number\pdfcolorstack}{0}%
408 </test3>
409 \setbox0=\hbox{%
410 \pdfcolInitStack{test}%
411 <*test3>
412 \Expect*{\number\pdfcol@Stack@test}{1}%
413 \Expect*{\number\pdfcolorstack}{0}%
414 </test3>
415 \pdfcolSwitchStack{test}%

```

```

416 ⟨*test3⟩
417   \Expect*{\number\@pdfcolorstack}{1}%
418 ⟨/test3⟩
419   \pdfcolSetCurrent{test}%
420   \pdfcolSetCurrent{}%
421   }%
422   \Expect*{\the\wd0}{0.0pt}%
423 ⟨*test3⟩
424   \Expect*{\number\@pdfcolorstack}{0}%
425   \Expect*{\number\pdfcol@Stack@test}{1}%
426   \Expect*{\pdfcolIfStackExists{test}{true}{false}}{true}%
427 ⟨/test3⟩
428   \Expect*{\pdfcolIfStackExists{dummy}{true}{false}}{false}%
429   \end{qstest}%
430 \end{document}
431 ⟨/test2 | test3⟩

```

3.3 Detection of package luacolor

```

432 ⟨*test4⟩
433 \NeedsTeXFormat{LaTeX2e}
434 \documentclass{article}
435 \usepackage{luacolor}
436 \usepackage{pdfcol}
437 \makeatletter
438 \ifpdfcolAvailable
439   \@latex@error{Detection of package luacolor failed}%
440 \fi
441 \csname @@end\endcsname
442 ⟨/test4⟩

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/pdfcol.dtx](http://ctan.org/pkg/pdfcol) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcol.pdf](http://ctan.org/pkg/pdfcol) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](http://ctan.org/pkg/oberdiek)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](http://ctan.org/pkg/tds)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹<http://ctan.org/pkg/pdfcol>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex pdfcol.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfcol.sty          → tex/generic/oberdiek/pdfcol.sty
pdfcol.pdf          → doc/latex/oberdiek/pdfcol.pdf
test/pdfcol-test1.tex → doc/latex/oberdiek/test/pdfcol-test1.tex
test/pdfcol-test2.tex → doc/latex/oberdiek/test/pdfcol-test2.tex
test/pdfcol-test3.tex → doc/latex/oberdiek/test/pdfcol-test3.tex
test/pdfcol-test4.tex → doc/latex/oberdiek/test/pdfcol-test4.tex
pdfcol.dtx          → source/latex/oberdiek/pdfcol.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (`te \TeX` , `mik \TeX` , ...) relies on file name databases, you must refresh these. For example, `te \TeX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk pdfcol.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcol.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex pdfcol.dtx
makeindex -s gind.ist pdfcol.idx
pdflatex pdfcol.dtx
makeindex -s gind.ist pdfcol.idx
pdflatex pdfcol.dtx
```

5 Catalogue

The following XML file can be used as source for the [T_EX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `pdfcol.xml`.

```
443 (*catalogue)
444 <?xml version='1.0' encoding='us-ascii'?>
445 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
446 <entry datestamp='$Date$' modifier='$Author$' id='pdfcol'>
447   <name>pdfcol</name>
448   <caption>Defines macros fpr maintaining color stacks under pdfTeX.</caption>
449   <authorref id='auth:oberdiek' />
450   <copyright owner='Heiko Oberdiek' year='2007' />
451   <license type='lppl1.3' />
452   <version number='1.3' />
453   <description>
454     Since version 1.40 pdfTeX supports color stacks.
455     The driver file <tt>pdftex.def</tt> for package
456     <xref refid='color'>color</xref> defines and uses a main color
457     stack since version v0.04b.
458     <p/>
459     This package is intended for package writers.
460     It defines macros for setting and maintaining new color stacks.
461     <p/>
462     The package is part of the <xref refid='oberdiek'>oberdiek</xref>
463     bundle.
464   </description>
465   <documentation details='Package documentation'
466     href='ctan:/macros/latex/contrib/oberdiek/pdfcol.pdf' />
467   <ctan file='true' path='/macros/latex/contrib/oberdiek/pdfcol.dtx' />
468   <miktex location='oberdiek' />
469   <texlive location='oberdiek' />
470   <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
471 </entry>
472 </catalogue>
```

6 History

[2007/09/09 v1.0]

- First version.

[2007/12/09 v1.1]

- `\pdfcolSetCurrentColor` added.

[2007/12/12 v1.2]

- Detection for package `luacolor` added.

[2016/05/16 v1.3]

- Documentation updates.

7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

| Symbols | |
|---|--|
| <code>\#</code> | 295 |
| <code>\%</code> | 371 |
| <code>\@</code> | 296, 369 |
| <code>\@PackageError</code> | 211, 252, 256 |
| <code>\@PackageInfo</code> | 207 |
| <code>\@PackageInfoNoLine</code> | 139 |
| <code>\@PackageWarningNoLine</code> | 134 |
| <code>\@ehc</code> | 213, 252, 266 |
| <code>\@firstofone</code> | 304, 307 |
| <code>\@firstoftwo</code> | 220, <u>223</u> |
| <code>\@gobble</code> | 301, 309 |
| <code>\@latex@error</code> | 439 |
| <code>\@pdfcolorstack</code> | 231, 238, 242, 407, 413, 417, 424 |
| <code>\@secondoftwo</code> | 218, <u>226</u> |
| <code>\@undefined</code> | 58 |
| <code>\@</code> | 241, 370 |
| <code>\{</code> | 293 |
| <code>\}</code> | 294 |
| A | |
| <code>\advance</code> | 334, 342, 357 |
| <code>\aftergroup</code> | 29 |
| B | |
| <code>\begin</code> | 399, 400 |
| <code>\body</code> | 313, 317 |
| C | |
| <code>\catcode</code> | 2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 293, 294, 295, 296, 331, 340, 348, 352, 369, 370, 371 |
| <code>\chardef</code> | 204 |
| <code>\count@</code> | 298, 327, 331, 333, 334, 338, 340, 341, 342, 346, 348, 351, 352, 356, 357 |
| <code>\countdef</code> | 298 |
| <code>\csname</code> | 14, 21, 50, 66, 76, 113, 125, 152, 162, 172, 174, 176, 182, 196, 199, 203, 204, 208, 217, 223, 226, 232, 245, 297, 300, 303, 306, 361, 388, 441 |
| <code>\current@color</code> | 238 |
| D | |
| <code>\documentclass</code> | 394, 434 |
| E | |
| <code>\empty</code> | 17, 18 |
| <code>\end</code> | 389, 429, 430 |
| <code>\endcsname</code> | 14, 21, 50, 66, 76, 113, 125, 152, 162, 172, 174, 176, 182, 196, 199, 203, 204, 208, 217, 223, 226, 232, 245, 297, 300, 303, 306, 361, 388, 441 |
| <code>\endinput</code> | 29, 111 |
| <code>\endlinechar</code> | 4, 35, 71, 77, 89 |
| <code>\errmessage</code> | 350 |
| <code>\Expect</code> | 403, 406, 407, 412, 413, 417, 422, 424, 425, 426, 428 |
| H | |
| <code>\hbox</code> | 409 |
| I | |
| <code>\ifcase</code> | 132 |
| <code>\ifnum</code> | 333, 341, 348, 356 |
| <code>\ifpdf</code> | 132 |
| <code>\ifPDFCOL@luacolor</code> | 123, 132, 143 |
| <code>\ifpdfcolAvailable</code> ... | 2, <u>121</u> , 121, 150, 160, 170, 194, 403, 406, 438 |
| <code>\ifx</code> | 15, 18, 21, 50, 58, 61, 113, 125, 152, 162, 172, 174, 176, |

182, 196, 199, 203, 217, 223,
 226, 241, 297, 300, 303, 306, 361
 \immediate 23, 52
 \IncludeTests 397
 \input 114, 362
 \iterate 314, 316, 318

J

\jobname 264

L

\LoadCommand 362, 372
 \LogTests 398
 \loop 312, 328, 339, 347
 \ltx@newif 121, 123

M

\makeatletter 401, 437
 \MessageBreak 155,
 165, 185, 186, 260, 262, 264, 265

N

\NeedsTeXFormat 392, 433
 \next 318, 320, 322
 \nofiles 393
 \number 208,
 353, 407, 412, 413, 417, 424, 425

P

\PackageInfo 26
 \PDFCOL@AtEnd 95, 96, 111, 290
 \PDFCOL@Disabled 270, 277, 281, 284, 287
 \pdfcol@ErrorNoStack .. 234, 247, 251
 \pdfcol@LiteralModifier ... 199, 205
 \PDFCOL@luacolorfalse 126
 \PDFCOL@luacolortrue 128
 \PDFCOL@Message
 . 133, 138, 141, 154, 164, 184, 271
 \PDFCOL@RequirePackage
 112, 120, 130, 131
 \pdfcol@Stack@test 412, 425
 \pdfcol@Value 196, 205
 \pdfcol@Availablefalse
 137, 153, 163, 183, 193

\pdfcol@Availabletrue 122, 192
 \pdfcol@ErrorNoStacks 2, 195, 255
 \pdfcol@IfStackExists
 ... 3, 216, 230, 244, 279, 426, 428
 \pdfcol@InitStack 2, 202, 276, 410
 \pdfcolorstack 156, 238, 242, 245
 \pdfcolorstackinit 166, 205
 \pdfcol@SetCurrent 3, 240, 286, 419, 420
 \pdfcol@SetCurrentColor .. 3, 237, 283
 \pdfcol@SwitchStack ... 3, 229, 280, 415
 \ProvidesPackage 19, 67

R

\RangeCatcodeCheck
 . 345, 373, 374, 375, 376, 377,
 378, 379, 380, 381, 382, 383, 384
 \RangeCatcodeInvalid
 337, 365, 366, 367, 368
 \repeat 312, 324, 335, 343, 358
 \RequirePackage 117, 178
 \RestoreCatcodes .. 326, 329, 330, 385

S

\setbox 409
 \space 351, 352, 360

T

\Test 364, 387
 \the 77, 78, 79, 80,
 81, 82, 83, 84, 97, 331, 351, 352, 422
 \TMP@EnsureCode . 94, 101, 102, 103,
 104, 105, 106, 107, 108, 109, 110

U

\usepackage 395, 396, 435, 436

W

\wd 422
 \write 23, 52

X

\x 14, 15, 18, 22, 26, 28, 51, 56, 66, 75, 87