

The pdfcolmk package

Heiko Oberdiek*

<heiko.oberdiek at gmail.com>

2016/05/16 v1.3

Abstract

This package tries a solution for the missing color stack of pdfTeX.

Contents

1	Documentation	2
1.1	Introduction	2
1.2	Background	2
1.3	Limitations	2
1.4	Recommendation	2
1.5	Usage	2
1.6	Compatibility	2
2	Implementation	3
2.1	\marginpar fix	4
2.1.1	latex/base/latex.ltx	4
2.1.2	memoir.cls	5
2.1.3	poemscol/marn.sty, poemscol/newmarn.sty	6
2.1.4	refman/refart.cls, refnam/refrep.cls	7
2.2	Color fix	9
3	Installation	10
3.1	Download	10
3.2	Bundle installation	10
3.3	Package installation	11
3.4	Refresh file name databases	11
3.5	Some details for the interested	11
4	Catalogue	12
5	History	12
	[2000/08/27 v0.1]	12
	[2000/09/02 v0.2]	12
	[2000/09/02 v0.3]	12
	[2000/09/06 v0.4]	12
	[2000/09/06 v0.5]	13
	[2005/06/15 v0.6]	13
	[2005/07/09 v0.7]	13
	[2006/02/20 v0.8]	13
	[2007/01/01 v1.0]	13
	[2007/04/11 v1.1]	13
	[2008/08/11 v1.2]	13
	[2016/05/16 v1.3]	13

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Documentation

1.1 Introduction

This package uses a mark register in order to solve the problem of a missing color stack of pdfTeX prior 1.40.0. Since this version of pdfTeX a color stack is available and supported by pdfTeX.def 2007/01/01 v0.04a. In this case this package is obsolete and the package stops its loading.

1.2 Background

After the Dante meeting (Clausthal 2000) I have started to experiment with the eTeX method of a *colour* mark. One of the major problems is the understanding of the output routine and the need to rewrite it because of missing hooks. Currently I have made some tests in onecolumn and twocolumn mode, but the state is experimental.

1.3 Limitations

- Mark limitations: page breaks in math.
- L^AT_EX's output routine is redefined.
 - Changes in the output routine of newer versions of LaTeX are not detected.
 - Packages that change the output routine are not supported.
- It does not support several independent text streams like footnotes.
- Limitations in float and marginpar support.

1.4 Recommendation

ϵ -T_EX (for additional mark register) Without ϵ -T_EX L^AT_EX's mark commands are redefined to store an additional color value.

1.5 Usage

Load after package color:

```
\usepackage[pdftex]{color}  
\usepackage{pdfcolmk}
```

1.6 Compatibility

- Load the following packages after pdfcolmk:

```
mparhack.sty
```

- Load the following packages before pdfcolmk:

```
marn.sty  
newmarn.sty
```

- Supported \@addmarginpar patch:

```
latex/base/latex.ltx  
memoir.cls  
poemscol/marn.sty, poemscol/newmarn.sty  
mparhack.sty
```

- Unsupported \@addmarginpar patch:

lineno.sty
sttools/marginal.sty
revtex4.cls

2 Implementation

```

1 (*package)
Package identification.
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{pdfcolmk}%
4 [2016/05/16 v1.3 Color support for pdfTeX via marks (HO)]
5 \ifundefined{ver@pdftex.def}{%
6   \PackageWarningNoLine{pdfcolmk}{%
7     Nothing to fix, because \string`pdftex.def\string' not loaded%
8   }%
9   \endinput
10 }{}
11 \ifpackageloaded{color}{%}%
12   \PackageWarningNoLine{pdfcolmk}{%
13     Nothing to fix, because \string`color.sty\string' not loaded%
14   }%
15   \endinput
16 }
17 \begingroup\expandafter\expandafter\expandafter\endgroup
18 \expandafter\ifx\csname main@pdfcolorstack\endcsname\relax
19 \else
20   % pdftex.def >= 2007/01/01 0.04a and pdfTeX >= 1.40.0
21   \begingroup
22     \let\on@line\@empty
23     \PackageInfo{pdfcolmk}{%
24       The color stack of pdfTeX \string>\string= 1.40 is used. %
25       Therefore\MessageBreak
26       this package is not necessary and not loaded%
27     }%
28   \endgroup
29   \expandafter\endinput
30 \fi
31
32 \PackageInfo{pdfcolmk}{%
33   This package tries to simulate dvips's color stack\MessageBreak
34   for pdfTeX based on a mark register of e-TeX.\MessageBreak
35   It redefines LaTeX's output routine. Therefore\MessageBreak
36   use with care, no warranties%
37 }
38
39 \ifx\marks\@undefined
40
41   \let\pec@mark\mark
42   \let\pec@value\empty
43   \long\def\mark#1{%
44     \protected@xdef\pec@value{#1}%
45     \pec@setmark
46   }%
47   \def\pec@setmark{%
48     \begingroup
49       \@temptokena\expandafter{\pec@value}%
50       \pec@mark{{\current@color}\the\@temptokena}%
51     \endgroup
52   }%
53   \def\pec@getmark{%
54     \xdef\pec@botcolor{%

```

```

55     \expandafter\@firstofthree\botmark\@empty\@empty\@empty
56   }%
57 }%
58 \long\def\@firstofthree#1#2#3{#1}%
59 \CheckCommand{\@leftmark}[2]{#1}%
60 \CheckCommand{\@rightmark}[2]{#2}%
61 \CheckCommand*{\leftmark}{%
62   \expandafter\@leftmark\botmark\@empty\@empty
63 }%
64 \CheckCommand*{\rightmark}{%
65   \expandafter\@rightmark\firstmark\@empty\@empty
66 }%
67 \long\def\@leftmark#1#2#3{#2}%
68 \long\def\@rightmark#1#2#3{#3}%
69 \g@addto@macro\leftmark\@empty
70 \g@addto@macro\rightmark\@empty
71
72 \else
73
74   \RequirePackage{etex}[1998/03/26]%
75   \newmarks\pec@marks
76   \def\pec@setmark{\marks\pec@marks{\current@color}}%
77   \def\pec@getmark{\xdef\pec@botcolor{\botmarks\pec@marks}}%
78
79 \fi

```

2.1 \marginpar fix

```

80 \chardef\pec@result\z@
81 \def\pec@temp#1{%
82   \chardef\pec@result\@ne
83   \begingroup
84     \let\on@line\@empty
85     \PackageInfo{pdfcolmk}{%
86       Patch for \string\@addmarginpar\space applied (#1)%
87     }%
88   \endgroup
89 }

```

2.1.1 latex/base/latex.ltx

```

90 \def\pec@addmarginpar{%
91   \@next\@marbox\@currlist{%
92     \@cons\@freelist\@marbox
93     \@cons\@freelist\@currbox
94   }\@latexbug
95   \@tempcnta\@ne
96   \if@twocolumn
97     \if@firstcolumn
98       \@tempcnta\m@ne
99     \fi
100  \else
101    \if@mparswitch
102      \ifodd\c@page
103        \else
104          \@tempcnta\m@ne
105        \fi
106      \fi
107    \if@reversemargin \@tempcnta -\@tempcnta \fi
108  \fi
109  \ifnum\@tempcnta <\z@ \global\setbox\@marbox\box\@currbox \fi
110  \@tempdima\@mparbottom
111  \advance\@tempdima -\@pageht
112  \advance\@tempdima\ht\@marbox

```

```

113 \ifdim\@tempdima >\z@
114 \latex@warning@no@line{Marginpar on page \thepage\space moved}%
115 \else
116 \@tempdima\z@
117 \fi
118 \global\@mparbottom\@pageht
119 \global\advance\@mparbottom\@tempdima
120 \global\advance\@mparbottom\dp\@marbox
121 \global\advance\@mparbottom\marginparpush
122 \advance\@tempdima -\ht\@marbox
123 \global\setbox\@marbox\vbox{%
124 \vskip \@tempdima
125 \box \@marbox
126 }%
127 \global \ht\@marbox \z@
128 \global \dp\@marbox \z@
129 \kern -\@pagedp
130 \nointerlineskip
131 \hb@xt@\columnwidth{%
132 \ifnum \@tempcnta >\z@
133 \hskip\columnwidth
134 \hskip\marginparsep
135 \else
136 \hskip -\marginparsep
137 \hskip -\marginparwidth
138 \fi
139 \box\@marbox \hss
140 }%
141 \nointerlineskip
142 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}%
143 }
144 \ifx\pec@addmarginpar\@addmarginpar
145 \pec@temp{latex/base}%
146 \fi

```

2.1.2 memoir.cls

```

147 \def\pec@addmarginpar{%
148 \checkoddpage
149 \@next\@marbox\@currlist{%
150 \@cons\@freelist\@marbox
151 \@cons\@freelist\@currbox
152 }\@latexbug
153 \@tempcnta\@ne
154 \if@twocolumn
155 \if@firstcolumn
156 \@tempcnta\m@ne
157 \fi
158 \else
159 \if@mparswitch
160 \ifoddpage
161 \else
162 \@tempcnta\m@ne
163 \fi
164 \fi
165 \if@reversemargin
166 \@tempcnta -\@tempcnta
167 \fi
168 \fi
169 \ifnum\@tempcnta <\z@
170 \global\setbox\@marbox\box\@currbox
171 \fi
172 \@tempdima\@mparbottom
173 \advance\@tempdima -\@pageht

```

```

174 \advance\@tempdima\ht\@marbox
175 \ifdim\@tempdima >\z@
176 \latex@warning@no@line{%
177   Marginpar on page \thepage\space moved by \the\@tempdima
178 }%
179 \else
180 \@tempdima\z@
181 \fi
182 \global\@mparbottom\@pageht
183 \global\advance\@mparbottom\@tempdima
184 \global\advance\@mparbottom\dp\@marbox
185 \global\advance\@mparbottom\marginparpush
186 \advance\@tempdima -\ht\@marbox
187 \global\setbox\@marbox\vbox{%
188   \vskip \@tempdima
189   \box \@marbox
190 }%
191 \global \ht\@marbox \z@
192 \global \dp\@marbox \z@
193 \kern -\@pagedp
194 \nointerlineskip
195 \hb@xt@\columnwidth{%
196   \ifnum \@tempcnta >\z@
197     \hskip\columnwidth
198     \hskip\marginparsep
199   \else
200     \hskip -\marginparsep
201     \hskip -\marginparwidth
202   \fi
203   \box\@marbox
204   \hss
205 }%
206 \nointerlineskip
207 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}%
208 }%
209 \ifx\pec@addmarginpar\@addmarginpar
210 \pec@temp{memoir.cls}%
211 \fi

```

2.1.3 poemscol/marn.sty, poemscol/newmarn.sty

```

212 \def\pec@addmarginpar{%
213   \@next \@marbox\@currlist{%
214     \@cons\@freelist\@marbox
215     \@cons\@freelist\@currbox
216   }\@latexbug
217   \global\advance\@mpar@count\m@ne
218   \@ifundefined{\@marn@\the\@mpar@count @}{% was location logged last time?
219     \@tempcnta\@ne % NO: use original LaTeX logic
220     \if@twocolumn
221       \if@firstcolumn
222         \@tempcnta\m@ne
223       \fi
224     \else
225       \if@mparswitch
226         \ifodd\c@page
227           \else
228             \@tempcnta\m@ne
229           \fi
230         \fi
231       \if@reversemargin
232         \@tempcnta -\@tempcnta
233       \fi
234     \fi

```

```

235 }{%
236 \@tempcnta % YES: use record from last time to decide side.
237 \@nameuse{@marn@the\@mpar@count @}%
238 \if@reversemargin -\fi \@ne
239 }%
240 \ifnum \@tempcnta <\z@
241 \global\setbox\@marbox\box\@currbox
242 \global\let\@marnbottom\@mparbottoml
243 \else
244 \global\let\@marnbottom\@mparbottom
245 \fi
246 \@tempdima\@marnbottom \advance\@tempdima -\@pageht
247 \advance\@tempdima\ht\@marbox
248 \ifdim \@tempdima >\z@
249 \@@warning{Marginpar on page \thepage\space moved}%
250 \else
251 \@tempdima\z@
252 \fi
253 \global\@marnbottom\@pageht
254 \global\advance\@marnbottom\@tempdima
255 \global\advance\@marnbottom\dp\@marbox
256 \global\advance\@marnbottom\marginparpush
257 \advance\@tempdima -\ht\@marbox
258 \global\ht\@marbox\z@
259 \global\dp\@marbox\z@
260 \vskip -\@pagedp
261 \vskip\@tempdima\nointerlineskip
262 \hbox to\columnwidth{%
263 \ifnum \@tempcnta >\z@
264 \hskip\columnwidth
265 \hskip\marginparsep
266 \else
267 \hskip -\marginparsep
268 \hskip -\marginparwidth
269 \fi
270 \if@filesw % record where this is for use next time:
271 \@marn@log\@mpar@count
272 \fi
273 \box\@marbox
274 \hss
275 }%
276 \nobreak %% RmS 91/06/21 \nobreak added
277 \vskip -\@tempdima
278 \nointerlineskip
279 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}%
280 }
281 \ifx\pec@addmarginpar\@addmarginpar
282 \pec@temp{poemscol/(new)marn.sty}%
283 \fi

```

2.1.4 refman/refart.cls, refnam/refrep.cls

```

284 \def\pec@addmarginpar{%
285 \@next\@marbox\@currlist{%
286 \@cons\@freelist\@marbox
287 \@cons\@freelist\@currbox
288 }\@latexbug
289 \@tempcnta\@ne
290 \if@twocolumn
291 \if@firstcolumn
292 \@tempcnta\m@ne
293 \fi
294 \else
295 \@tempcnta\m@ne

```

```

296 \fi
297 \ifnum \@tempcnta < \z@
298   \global\setbox \@marbox \box \@currbox
299 \fi
300 \@tempdima \@mparbottom
301 \advance \@tempdima - \@pageht
302 \advance \@tempdima \ht \@marbox
303 \ifdim \@tempdima > \z@
304   \@@warning{Marginpar on page \thepage\space moved}%
305 \else
306   \@tempdima \z@
307 \fi
308 \global \@mparbottom \@pageht
309 \global\advance \@mparbottom \@tempdima
310 \global\advance \@mparbottom \dp \@marbox
311 \global\advance \@mparbottom \marginparpush
312 \advance \@tempdima - \ht \@marbox
313 \global\setbox \@marbox \vbox{%
314   \vskip \@tempdima \box \@marbox
315 }%
316 \global \ht \@marbox \z@
317 \global \dp \@marbox \z@
318 \kern -\@pagedp
319 \nointerlineskip
320 \hb@xt@\columnwidth{%
321   \ifnum \@tempcnta > \z@
322     \hskip \columnwidth
323     \hskip \marginparsep
324   \else
325     \hskip -\marginparsep
326     \hskip -\marginparwidth
327   \fi
328   \box \@marbox
329   \hss
330 }%
331 \nointerlineskip
332 \hbox{\vrule \@height \z@ \@width \z@ \@depth \@pagedp}%
333 }
334 \ifx \pec@addmarginpar \@addmarginpar
335   \pec@temp{ref{art|rep}.cls}%
336 \fi
337
338 \ifcase \pec@result
339   \PackageInfo{pdfcolmk}{%
340     Fix for \string \@addmarginpar\space is omitted, %
341     because this variant\MessageBreak
342     of \string \@addmarginpar\space
343     is not recognized%
344   }%
345 \else
346   % apply patch for \@addmarginpar
347   \def \pec@PatchAddMarginpar#1\columnwidth#2#3\@nil{%
348     \pec@PatchAddMarginparI#2\@nil{#1}{#3}%
349   }%
350   \def \pec@PatchAddMarginparI#1\box \@marbox \hss#2\@nil#3#4{%
351     \def \@addmarginpar{%
352       #3%
353       \columnwidth{%
354         #1%
355         \pdfliteral{q}%
356         \rlap{%
357           \box \@marbox

```



```

358     }%
359     \pdfliteral{Q}%
360     \hss
361     #2%
362     }%
363     #4%
364     }%
365     }%
366     \expandafter\pec@PatchAddMarginpar\@addmarginpar\@nil
367 \fi

```

2.2 Color fix

```

368 \def\set@color{%
369   \pdfliteral{\current@color}%
370   \ifinner
371   \else
372     \pec@setmark
373   \fi
374   \aftergroup\reset@color
375 }
376 \def\reset@color{%
377   \pdfliteral{\current@color}%
378   \ifinner
379   \else
380     \pec@setmark
381   \fi
382 }
383
384 \let\pec@botcolor\current@color
385
386 \def\pec@PatchVBoxCCLV{%
387   \ifx\pec@botcolor\@empty
388   \else
389     \setbox\@cclv\vbox{%
390       \pdfliteral{\pec@botcolor}%
391       \unvbox\@cclv
392     }%
393   \fi
394   \pec@getmark
395 }
396
397 \def\pec@PatchAlreadyInBox{%
398   \ifx\pec@botcolor\@empty
399   \else
400     \pdfliteral{\pec@botcolor}%
401   \fi
402   \pec@getmark
403 }
404
405 \@ifclassloaded{memoir}{%
406   \expandafter\def\expandafter\mem@makecol\expandafter{%
407     \expandafter\pec@PatchVBoxCCLV
408     \mem@makecol
409   }%
410   \endinput
411 }{}
412
413 \@ifclassloaded{seminar}{%
414   \newcommand\pec@org@makeslide{}%
415   \let\pec@org@makeslide\@makeslide
416   \def\@makeslide{%
417     \pec@PatchVBoxCCLV

```

```

418 \pec@org@makeslide
419 }%
420 \endinput
421 }{}
422
423 \long\def\pec@output#1\@specialoutput\else#2\pec@end{%
424 \begingroup
425 \def\x{#2}%
426 \expandafter\endgroup
427 \ifx\x\@empty
428 \PackageWarningNoLine{pdfcolmk}{%
429 Unexpected \string\output\space routine detected,%
430 \MessageBreak
431 loading of package stopped%
432 }%
433 \expandafter\endinput
434 \fi
435 }
436 \expandafter\expandafter\expandafter\pec@output
437 \expandafter\@firstofone\the\output\@specialoutput\else\pec@end
438
439 \long\def\pec@output#1\@specialoutput\else#2\pec@end{%
440 \output{%
441 #1\@specialoutput\else
442 \pec@PatchVBoxCCLV
443 #2%
444 }%
445 }
446 \expandafter\expandafter\expandafter\pec@output
447 \expandafter\@firstofone\the\output\pec@end
448 \endpackage

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/pdfcolmk.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcolmk.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

¹<http://ctan.org/pkg/pdfcolmk>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain \TeX :

```
tex pdfcolmk.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfcolmk.sty → tex/latex/oberdiek/pdfcolmk.sty
pdfcolmk.pdf → doc/latex/oberdiek/pdfcolmk.pdf
pdfcolmk.dtx → source/latex/oberdiek/pdfcolmk.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your \TeX distribution (te \TeX , mi \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktextlsr`.

3.5 Some details for the interested

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcolmk.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdf \LaTeX :

```
pdflatex pdfcolmk.dtx
makeindex -s gind.ist pdfcolmk.idx
pdflatex pdfcolmk.dtx
makeindex -s gind.ist pdfcolmk.idx
pdflatex pdfcolmk.dtx
```

4 Catalogue

The following XML file can be used as source for the [T_EX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `pdfcolmk.xml`.

```
449 (*catalogue)
450 <?xml version='1.0' encoding='us-ascii'?>
451 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
452 <entry datestamp='$Date$' modifier='$Author$' id='pdfcolmk'>
453   <name>pdfcolmk</name>
454   <caption>Improving colour support under pdftex.</caption>
455   <authorref id='auth:oberdiek'>
456   <copyright owner='Heiko Oberdiek' year='2000,2005-2008'>/>
457   <license type='lppl1.3'>/>
458   <version number='1.3'>/>
459   <description>
460     The package provides macros that emulate the &#x2018;colour stack&#x2019;
461     functionality of dvips. The colour stack deals with colour
462     manipulations when asynchronous events (like page-breaking) occur;
463     pdftex does not (yet) have such a stack, but dvips does, and the
464     <xref refid='color'>color</xref> package makes extensive use of
465     it.
466     <p/>
467     This package is an experimental solution to the problem, and works
468     best with pdf-e-tex.
469     <p/>
470     The package is part of the <xref refid='oberdiek'>oberdiek</xref> bundle.
471   </description>
472   <documentation details='Package documentation'
473     href='ctan:/macros/latex/contrib/oberdiek/pdfcolmk.pdf'>/>
474   <ctan file='true' path='/macros/latex/contrib/oberdiek/pdfcolmk.dtx'>/>
475   <miktex location='oberdiek'>/>
476   <texlive location='oberdiek'>/>
477   <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'>/>
478 </entry>
479 </catalogue>
```

5 History

[2000/08/27 v0.1]

- First published version in newsgroup [comp.text.tex](#):
“[pdftex: bug with colors?](#)”²

[2000/09/02 v0.2]

- Next try.

[2000/09/02 v0.3]

- Solution without ε -T_EX added.

[2000/09/06 v0.4]

- Patch commands added.
- Patch for seminar.cls added.

²Url: <http://groups.google.com/group/comp.text.tex/msg/6f088e69e4085d2c>

[2000/09/06 v0.5]

- Bug fix: initialization of `\pec@value` added.

[2005/06/15 v0.6]

- Support for `\marginpar` added. See thread in [comp.text.tex](#):
“Using `\textcolor` and `\marginpar` together”³

[2005/07/09 v0.7]

- Output support added for memoir, provided by Lars Madsen.

[2006/02/20 v0.8]

- Code is not changed.
- DTX framework.

[2007/01/01 v1.0]

- If `pdftex.def` \geq 2007/01/01 v0.04a is used with `pdfTeX` \geq 1.40.0, then package `pdfcolmk` is obsolete.

[2007/04/11 v1.1]

- Line ends sanitized.

[2008/08/11 v1.2]

- Code is not changed.
- URLs updated.

[2016/05/16 v1.3]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@@warning</code>	249, 304
<code>\@addmarginpar</code>	86, 144, 209, 281, 334, 340, 342, 346, 351, 366
<code>\@cclv</code>	389, 391
<code>\@cons</code> 92, 93, 150, 151, 214, 215, 286, 287	
<code>\@currbox</code>	93, 109, 151, 170, 215, 241, 287, 298
<code>\@currlist</code>	91, 149, 213, 285
<code>\@depth</code>	142, 207, 279, 332
<code>\@empty</code>	22, 55, 62, 65, 69, 70, 84, 387, 398, 427
<code>\@firstofone</code>	437, 447
<code>\@firstofthree</code>	55, 58
<code>\@freelist</code>	92, 93, 150, 151, 214, 215, 286, 287
<code>\@height</code>	142, 207, 279, 332
<code>\@ifclassloaded</code>	405, 413
<code>\@ifpackageloaded</code>	11
<code>\@ifundefined</code>	5, 218
<code>\@latex@warning@no@line</code>	114, 176
<code>\@latexbug</code>	94, 152, 216, 288
<code>\@leftmark</code>	59, 62, 67
<code>\@makeslide</code>	415, 416
<code>\@marbox</code>	91, 92, 109, 112, 120, 122, 123, 125, 127, 128, 139, 149, 150, 170, 174, 184, 186, 187, 189, 191, 192, 203, 213, 214, 241,

³URL: <http://groups.google.com/group/comp.text.tex/msg/38ed58f8845a2a4f>

247, 255, 257, 258, 259, 273, 285, 286, 298, 302, 310, 312, 313, 314, 316, 317, 328, 350, 357	\endcsname 18
\@marn@log 271	\endinginput 9, 15, 29, 410, 420, 433
\@marnbottom 242, 244, 246, 253, 254, 255, 256	F
\@mpar@count 217, 218, 237, 271	\firstmark 65
\@mparbottom 110, 118, 119, 120, 121, 172, 182, 183, 184, 185, 244, 300, 308, 309, 310, 311	G
\@mparbottoml 242	\g@addto@macro 69, 70
\@nameuse 237	H
\@ne 82, 95, 153, 219, 238, 289	\hb@xt@ 131, 195, 320
\@next 91, 149, 213, 285	\hbox 142, 207, 262, 279, 332
\@nil 347, 348, 350, 366	\hskip 133, 134, 136, 137, 197, 198, 200, 201, 264, 265, 267, 268, 322, 323, 325, 326
\@pagedp 129, 142, 193, 207, 260, 279, 318, 332	\hss 139, 204, 274, 329, 350, 360
\@pageht 111, 118, 173, 182, 246, 253, 301, 308	\ht 112, 122, 127, 174, 186, 191, 247, 257, 258, 302, 312, 316
\@rightmark 60, 65, 68	I
\@specialoutput 423, 437, 439, 441	\if@filesw 270
\@tempcnta 95, 98, 104, 107, 109, 132, 153, 156, 162, 166, 169, 196, 219, 222, 228, 232, 236, 240, 263, 289, 292, 295, 297, 321	\if@firstcolumn 97, 155, 221, 291
\@tempdima 110, 111, 112, 113, 116, 119, 122, 124, 172, 173, 174, 175, 177, 180, 183, 186, 188, 246, 247, 248, 251, 254, 257, 261, 277, 300, 301, 302, 303, 306, 309, 312, 314	\if@mparswitch 101, 159, 225
\@temptokena 49, 50	\if@reversemargin 107, 165, 231, 238
\@undefined 39	\if@twocolumn 96, 154, 220, 290
\@width 142, 207, 279, 332	\ifcase 338
A	\ifdim 113, 175, 248, 303
\advance 111, 112, 119, 120, 121, 122, 173, 174, 183, 184, 185, 186, 217, 246, 247, 254, 255, 256, 257, 301, 302, 309, 310, 311, 312	\ifinner 370, 378
\aftergroup 374	\ifnum 109, 132, 169, 196, 240, 263, 297, 321
B	\ifodd 102, 226
\botmark 55, 62	\ifoddpage 160
\botmarks 77	\ifx 18, 39, 144, 209, 281, 334, 387, 398, 427
\box 109, 125, 139, 170, 189, 203, 241, 273, 298, 314, 328, 350, 357	K
C	\kern 129, 193, 318
\c@page 102, 226	L
\chardef 80, 82	\leftmark 61, 69
\CheckCommand 59, 60, 61, 64	M
\checkoddpage 148	\m@ne 98, 104, 156, 162, 217, 222, 228, 292, 295
\columnwidth 131, 133, 195, 197, 262, 264, 320, 322, 347, 353	\marginparpush 121, 185, 256, 311
\csname 18	\marginparsep 134, 136, 198, 200, 265, 267, 323, 325
\current@color 50, 76, 369, 377, 384	\marginparwidth 137, 201, 268, 326
D	\mark 41, 43
\dp 120, 128, 184, 192, 255, 259, 310, 317	\marks 39, 76
E	\mem@makecol 406, 408
\empty 42	\MessageBreak 25, 33, 34, 35, 341, 430
	N
	\NeedsTeXFormat 2
	\newcommand 414
	\newmarks 75
	\nobreak 276
	\nointerlineskip 130, 141, 194, 206, 261, 278, 319, 331
	O
	\on@line 22, 84
	\output 429, 437, 440, 447

P	
\PackageInfo	23, 32, 85, 339
\PackageWarningNoLine	6, 12, 428
\pdfliteral	355, 359, 369, 377, 390, 400
\pec@addmarginpar	90, 144, 147, 209, 212, 281, 284, 334
\pec@botcolor	54, 77, 384, 387, 390, 398, 400
\pec@end	423, 437, 439, 447
\pec@getmark	53, 77, 394, 402
\pec@mark	41, 50
\pec@marks	75, 76, 77
\pec@org@makeslide	414, 415, 418
\pec@output	423, 436, 439, 446
\pec@PatchAddMarginpar	347, 366
\pec@PatchAddMarginparI	348, 350
\pec@PatchAlreadyInBox	397
\pec@PatchVBoxCCLV	386, 407, 417, 442
\pec@result	80, 82, 338
\pec@setmark	45, 47, 76, 372, 380
\pec@temp	81, 145, 210, 282, 335
\pec@value	42, 44, 49
\protected@xdef	44
\ProvidesPackage	3
R	
\RequirePackage	74
\reset@color	374, 376
\rightmark	64, 70
\rlap	356
S	
\set@color	368
\setbox	109, 123, 170, 187, 241, 298, 313, 389
\space	86, 114, 177, 249, 304, 340, 342, 429
T	
\the	50, 177, 218, 237, 437, 447
\thepage	114, 177, 249, 304
U	
\unvbox	391
V	
\vbox	123, 187, 313, 389
\vrule	142, 207, 279, 332
\vskip	124, 188, 260, 261, 277, 314
X	
\x	425, 427
Z	
\z@	80, 109, 113, 116, 127, 128, 132, 142, 169, 175, 180, 191, 192, 196, 207, 240, 248, 251, 258, 259, 263, 279, 297, 303, 306, 316, 317, 321, 332