

# The pdfcolmk package

Heiko Oberdiek\*

<heiko.oberdiek at gmail.com>

2016/05/16 v1.3

## Abstract

This package tries a solution for the missing color stack of pdfTeX.

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	Introduction	2
1.2	Background	2
1.3	Limitations	2
1.4	Recommendation	2
1.5	Usage	2
1.6	Compatibility	2
<b>2</b>	<b>Implementation</b>	<b>3</b>
2.1	\marginpar fix	4
2.1.1	latex/base/latex.ltx	4
2.1.2	memoir.cls	5
2.1.3	poemscol/marn.sty, poemscol/newmarn.sty	6
2.1.4	refman/refart.cls, refnam/refrep.cls	7
2.2	Color fix	9
<b>3</b>	<b>Installation</b>	<b>10</b>
3.1	Download	10
3.2	Bundle installation	10
3.3	Package installation	11
3.4	Refresh file name databases	11
3.5	Some details for the interested	11
<b>4</b>	<b>Catalogue</b>	<b>12</b>
<b>5</b>	<b>History</b>	<b>12</b>
	[2000/08/27 v0.1]	12
	[2000/09/02 v0.2]	12
	[2000/09/02 v0.3]	12
	[2000/09/06 v0.4]	12
	[2000/09/06 v0.5]	13
	[2005/06/15 v0.6]	13
	[2005/07/09 v0.7]	13
	[2006/02/20 v0.8]	13
	[2007/01/01 v1.0]	13
	[2007/04/11 v1.1]	13
	[2008/08/11 v1.2]	13
	[2016/05/16 v1.3]	13

---

\*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

## 1 Documentation

### 1.1 Introduction

This package uses a mark register in order to solve the problem of a missing color stack of pdfTeX prior 1.40.0. Since this version of pdfTeX a color stack is available and supported by `pdftex.def` 2007/01/01 v0.04a. In this case this package is obsolete and the package stops its loading.

### 1.2 Background

After the Dante meeting (Clausthal 2000) I have started to experiment with the eTeX method of a *colour* mark. One of the major problems is the understanding of the output routine and the need to rewrite it because of missing hooks. Currently I have made some tests in in onecolumn and twocolumn mode, but the state is experimental.

### 1.3 Limitations

- Mark limitations: page breaks in math.
- L<sup>A</sup>T<sub>E</sub>X's output routine is redefined.
  - Changes in the output routine of newer versions of LaTeX are not detected.
  - Packages that change the output routine are not supported.
- It does not support several independent text streams like footnotes.
- Limitations in float and marginpar support.

### 1.4 Recommendation

$\varepsilon$ -T<sub>E</sub>X (for additional mark register) Without  $\varepsilon$ -T<sub>E</sub>X L<sup>A</sup>T<sub>E</sub>X's mark commands are redefined to store an additional color value.

### 1.5 Usage

Load after package color:

```
\usepackage[pdftex]{color}
\usepackage{pdfcolmk}
```

### 1.6 Compatibility

- Load the following packages after pdfcolmk:
 

```
mparhack.sty
```
- Load the following packages before pdfcolmk:
 

```
marn.sty
newmarn.sty
```
- Supported \@addmarginpar patch:
 

```
latex/base/latex.ltx
memoir.cls
poemscol/marn.sty, poemscol/newmarn.sty
mparhack.sty
```

- Unsupported \@addmarginpar patch:

```
lineno.sty
sttools/marginal.sty
revtex4.cls
```

## 2 Implementation

```
1 (*package)
Package identification.
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{pdfcolmk}%
4 [2016/05/16 v1.3 Color support for pdfTeX via marks (HO)]
5 \@ifundefined{ver@pdftex.def}{%
6   \PackageWarningNoLine{pdfcolmk}{%
7     Nothing to fix, because \string`pdftex.def\string' not loaded%
8   }%
9   \endinput
10 }{}
11 \@ifpackageloaded{color}{%{}%
12   \PackageWarningNoLine{pdfcolmk}{%
13     Nothing to fix, because \string`color.sty\string' not loaded%
14   }%
15   \endinput
16 }
17 \begingroup\expandafter\expandafter\expandafter\endgroup
18 \expandafter\ifx\csname main@pdfcolorstack\endcsname\relax
19 \else
20   % pdftex.def >= 2007/01/01 0.04a and pdfTeX >= 1.40.0
21   \begingroup
22     \let\on@line\@empty
23     \PackageInfo{pdfcolmk}{%
24       The color stack of pdfTeX \string>\string= 1.40 is used. %
25       Therefore\MessageBreak
26       this package is not necessary and not loaded%
27     }%
28   \endgroup
29   \expandafter\endinput
30 \fi
31
32 \PackageInfo{pdfcolmk}{%
33   This package tries to simulate dvips's color stack\MessageBreak
34   for pdfTeX based on a mark register of e-TeX.\MessageBreak
35   It redefines LaTeX's output routine. Therefore\MessageBreak
36   use with care, no warranties%
37 }
38
39 \ifx\marks\@undefined
40
41   \let\pec@mark\mark
42   \let\pec@value\empty
43   \long\def\mark#1{%
44     \protected@xdef\pec@value{#1}%
45     \pec@setmark
46   }%
47   \def\pec@setmark{%
48     \begingroup
49     \@temptokena\expandafter{\pec@value}%
50     \pec@mark{{\current@color}\the\@temptokena}%
51   \endgroup
52 }%
```

```

53 \def\pec@getmark{%
54   \xdef\pec@botcolor{%
55     \expandafter\@firstofthree\botmark\@empty\@empty\@empty
56   }%
57 }%
58 \long\def\@firstofthree#1#2#3{#1}%
59 \CheckCommand{\@leftmark}[2]{#1}%
60 \CheckCommand{\@rightmark}[2]{#2}%
61 \CheckCommand*{\leftmark}{%
62   \expandafter\@leftmark\botmark\@empty\@empty
63 }%
64 \CheckCommand*{\rightmark}{%
65   \expandafter\@rightmark\firstmark\@empty\@empty
66 }%
67 \long\def\@leftmark#1#2#3{#2}%
68 \long\def\@rightmark#1#2#3{#3}%
69 \g@addto@macro\leftmark\@empty
70 \g@addto@macro\rightmark\@empty
71
72 \else
73
74 \RequirePackage{etex}[1998/03/26]%
75 \newmarks\pec@marks
76 \def\pec@setmark{\marks\pec@marks{\current@color}}%
77 \def\pec@getmark{\xdef\pec@botcolor{\botmarks\pec@marks}}%
78
79 \fi

```

## 2.1 \marginpar fix

```

80 \chardef\pec@result\z@
81 \def\pec@temp#1{%
82   \chardef\pec@result\@ne
83   \begingroup
84     \let\on@line\@empty
85     \PackageInfo{pdfcolmk}{%
86       Patch for \string\@addmarginpar\space applied (#1)%
87     }%
88   \endgroup
89 }

```

### 2.1.1 latex/base/latex.ltx

```

90 \def\pec@addmarginpar{%
91   \@next\@marbox\@currlist{%
92     \@cons\@freelist\@marbox
93     \@cons\@freelist\@currbox
94   }\@latexbug
95   \@tempcnta\@ne
96   \if@twocolumn
97     \if@firstcolumn
98       \@tempcnta\m@ne
99     \fi
100   \else
101     \if@mparswitch
102       \ifodd\c@page
103         \else
104           \@tempcnta\m@ne
105         \fi
106       \fi
107     \if@reversemargin \@tempcnta -\@tempcnta \fi
108   \fi
109   \ifnum\@tempcnta <\z@ \global\setbox\@marbox\box\@currbox \fi
110   \@tempdima\@mparbottom

```

```

111 \advance\@tempdima -\@pageht
112 \advance\@tempdima\ht\@marbox
113 \ifdim\@tempdima >\z@
114 \latexwarning@no@line{Marginpar on page \thepage\space moved}%
115 \else
116 \@tempdima\z@
117 \fi
118 \global\@mparbottom\@pageht
119 \global\advance\@mparbottom\@tempdima
120 \global\advance\@mparbottom\dp\@marbox
121 \global\advance\@mparbottom\marginparpush
122 \advance\@tempdima -\ht\@marbox
123 \global\setbox\@marbox\vbox{%
124 \vskip \@tempdima
125 \box \@marbox
126 }%
127 \global\ht\@marbox\z@
128 \global\dp\@marbox\z@
129 \kern -\@pagedp
130 \nointerlineskip
131 \hb@xt@\columnwidth{%
132 \ifnum \@tempcnta >\z@
133 \hskip\columnwidth
134 \hskip\marginparsep
135 \else
136 \hskip -\marginparsep
137 \hskip -\marginparwidth
138 \fi
139 \box\@marbox\hss
140 }%
141 \nointerlineskip
142 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}%
143 }
144 \ifx\pec@addmarginpar\@addmarginpar
145 \pec@temp{latex/base}%
146 \fi

```

### 2.1.2 memoir.cls

```

147 \def\pec@addmarginpar{%
148 \checkoddpage
149 \@next\@marbox\@currlist{%
150 \@cons\@freelist\@marbox
151 \@cons\@freelist\@currbox
152 }\latexbug
153 \@tempcnta\@ne
154 \if@twocolumn
155 \if@firstcolumn
156 \@tempcnta\m@ne
157 \fi
158 \else
159 \if@mparswitch
160 \ifoddpage
161 \else
162 \@tempcnta\m@ne
163 \fi
164 \fi
165 \if@reversemargin
166 \@tempcnta -\@tempcnta
167 \fi
168 \fi
169 \ifnum\@tempcnta <\z@
170 \global\setbox\@marbox\box\@currbox
171 \fi

```

```

172 \@tempdima\@mparbottom
173 \advance\@tempdima -\@pageht
174 \advance\@tempdima\ht\@marbox
175 \ifdim\@tempdima >\z@
176 \latexwarning@no@line{%
177   Marginpar on page \thepage\space moved by \the\@tempdima
178 }%
179 \else
180 \@tempdima\z@
181 \fi
182 \global\@mparbottom\@pageht
183 \global\advance\@mparbottom\@tempdima
184 \global\advance\@mparbottom\dp\@marbox
185 \global\advance\@mparbottom\marginparpush
186 \advance\@tempdima -\ht\@marbox
187 \global\setbox\@marbox\vbox{%
188   \vskip \@tempdima
189   \box \@marbox
190 }%
191 \global \ht\@marbox \z@
192 \global \dp\@marbox \z@
193 \kern -\@pagedp
194 \nointerlineskip
195 \hb@xt@\columnwidth{%
196   \ifnum \@tempcnta >\z@
197     \hskip\columnwidth
198     \hskip\marginparsep
199   \else
200     \hskip -\marginparsep
201     \hskip -\marginparwidth
202   \fi
203   \box\@marbox
204   \hss
205 }%
206 \nointerlineskip
207 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}%
208 }%
209 \ifx\pec@addmarginpar\@addmarginpar
210 \pec@temp{memoir.cls}%
211 \fi

```

### 2.1.3 poemscol/marn.sty, poemscol/newmarn.sty

```

212 \def\pec@addmarginpar{%
213   \@next \@marbox\@currlist{%
214     \@cons\@freelist\@marbox
215     \@cons\@freelist\@currbox
216   }\@latexbug
217   \global\advance\@mpar@count\m@ne
218   \ifundefined{\marn@the\@mpar@count @}{% was location logged last time?
219     \@tempcnta\@ne % NO: use original LaTeX logic
220     \if@twocolumn
221       \if@firstcolumn
222         \@tempcnta\m@ne
223       \fi
224     \else
225       \if@mparswitch
226         \ifodd\c@page
227         \else
228           \@tempcnta\m@ne
229         \fi
230       \fi
231       \if@reversemargin
232         \@tempcnta -\@tempcnta

```

```

233 \fi
234 \fi
235 }{ %
236 \@tempcnta % YES: use record from last time to decide side.
237 \@nameuse{@marn@the\@mpar@count @}%
238 \if@reversemargin -\fi \@ne
239 } %
240 \ifnum \@tempcnta < \z@
241 \global\setbox\@marbox\box\@currbox
242 \global\let\@marnbottom\@mparbottoml
243 \else
244 \global\let\@marnbottom\@mparbottom
245 \fi
246 \@tempdima\@marnbottom \advance\@tempdima -\@pageht
247 \advance\@tempdima\ht\@marbox
248 \ifdim\@tempdima > \z@
249 \@@warning{Marginpar on page \thepage\space moved}%
250 \else
251 \@tempdima\z@
252 \fi
253 \global\@marnbottom\@pageht
254 \global\advance\@marnbottom\@tempdima
255 \global\advance\@marnbottom\dp\@marbox
256 \global\advance\@marnbottom\marginparpush
257 \advance\@tempdima -\ht\@marbox
258 \global\ht\@marbox\z@
259 \global\dp\@marbox\z@
260 \vskip -\@pagedp
261 \vskip\@tempdima\nointerlineskip
262 \hbox to\columnwidth{%
263 \ifnum \@tempcnta > \z@
264 \hskip\columnwidth
265 \hskip\marginparsep
266 \else
267 \hskip -\marginparsep
268 \hskip -\marginparwidth
269 \fi
270 \if@filesw % record where this is for use next time:
271 \@marn@log\@mpar@count
272 \fi
273 \box\@marbox
274 \hss
275 } %
276 \nobreak %% RmS 91/06/21 \nobreak added
277 \vskip -\@tempdima
278 \nointerlineskip
279 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}%
280 }
281 \ifx\pec@addmarginpar\@addmarginpar
282 \pec@temp{poemscol/(new)marn.sty}%
283 \fi

```

#### 2.1.4 refman/refart.cls, refnam/refrep.cls

```

284 \def\pec@addmarginpar{%
285 \next\@marbox\@currlist{%
286 \cons\@freelist\@marbox
287 \cons\@freelist\@currbox
288 }\@latexbug
289 \@tempcnta\@ne
290 \if@twocolumn
291 \if@firstcolumn
292 \@tempcnta\m@ne
293 \fi

```

```

294 \else
295   \@tempcnta\m@ne
296 \fi
297 \ifnum\@tempcnta <\z@
298   \global\setbox\@marbox\box\@currbox
299 \fi
300 \@tempdima\@mparbottom
301 \advance\@tempdima -\@pageht
302 \advance\@tempdima\ht\@marbox
303 \ifdim\@tempdima >\z@
304   \@@warning{Marginpar on page \thepage\space moved}%
305 \else
306   \@tempdima\z@
307 \fi
308 \global\@mparbottom\@pageht
309 \global\advance\@mparbottom\@tempdima
310 \global\advance\@mparbottom\dp\@marbox
311 \global\advance\@mparbottom\marginparpush
312 \advance\@tempdima -\ht\@marbox
313 \global\setbox\@marbox\vbox{%
314   \vskip \@tempdima \box \@marbox
315 }%
316 \global \ht\@marbox \z@
317 \global \dp\@marbox \z@
318 \kern -\@pagedp
319 \nointerlineskip
320 \hb@xt@\columnwidth{%
321   \ifnum \@tempcnta >\z@
322     \hskip\columnwidth
323     \hskip\marginparsep
324   \else
325     \hskip -\marginparsep
326     \hskip -\marginparwidth
327   \fi
328   \box\@marbox
329   \hss
330 }%
331 \nointerlineskip
332 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}%
333 }
334 \ifx\pec@addmarginpar\@addmarginpar
335   \pec@temp{ref{art|rep}.cls}%
336 \fi
337
338 \ifcase\pec@result
339   \PackageInfo{pdfcolmk}{%
340     Fix for \string\@addmarginpar\space is omitted, %
341     because this variant\MessageBreak
342     of \string\@addmarginpar\space
343     is not recognized%
344   }%
345 \else
346   % apply patch for \@addmarginpar
347   \def\pec@PatchAddMarginpar#1\columnwidth#2#3\@nil{%
348     \pec@PatchAddMarginparI#2\@nil{#1}{#3}%
349   }%
350   \def\pec@PatchAddMarginparI#1\box\@marbox\hss#2\@nil#3#4{%
351     \def\@addmarginpar{%
352       #3%
353       \columnwidth{%
354         #1%
355         \pdfliteral{q}%

```



```

356      \rlap{%
357      \box\@marbox
358      }%
359      \pdfliteral{Q}%
360      \hss
361      #2%
362      }%
363      #4%
364      }%
365      }%
366      \expandafter\pec@PatchAddMarginpar\@addmarginpar\@nil
367 \fi

```

## 2.2 Color fix

```

368 \def\set@color{%
369   \pdfliteral{\current@color}%
370   \ifinner
371   \else
372     \pec@setmark
373   \fi
374   \aftergroup\reset@color
375 }
376 \def\reset@color{%
377   \pdfliteral{\current@color}%
378   \ifinner
379   \else
380     \pec@setmark
381   \fi
382 }
383
384 \let\pec@botcolor\current@color
385
386 \def\pec@PatchVBoxCCLV{%
387   \ifx\pec@botcolor\@empty
388   \else
389     \setbox\@cclv\vbox{%
390       \pdfliteral{\pec@botcolor}%
391       \unvbox\@cclv
392     }%
393   \fi
394   \pec@getmark
395 }
396
397 \def\pec@PatchAlreadyInBox{%
398   \ifx\pec@botcolor\@empty
399   \else
400     \pdfliteral{\pec@botcolor}%
401   \fi
402   \pec@getmark
403 }
404
405 \@ifclassloaded{memoir}{%
406   \expandafter\def\expandafter\mem@makecol\expandafter{%
407     \expandafter\pec@PatchVBoxCCLV
408     \mem@makecol
409   }%
410   \endinput
411 }{}
412
413 \@ifclassloaded{seminar}{%
414   \newcommand\pec@org@makeslide{}%
415   \let\pec@org@makeslide\@makeslide

```

```

416 \def\@makeslide{%
417   \pec@PatchVBoxCCLV
418   \pec@org@makeslide
419 }%
420 \endinput
421 }{}
422
423 \long\def\pec@output#1\@specialoutput\else#2\pec@end{%
424   \begingroup
425   \def\x{#2}%
426   \expandafter\endgroup
427   \ifx\x\@empty
428     \PackageWarningNoLine{pdfcolmk}{%
429       Unexpected \string\output\space routine detected,%
430       \MessageBreak
431       loading of package stopped%
432     }%
433   \expandafter\endinput
434   \fi
435 }
436 \expandafter\expandafter\expandafter\pec@output
437 \expandafter\@firstofone\the\output\@specialoutput\else\pec@end
438
439 \long\def\pec@output#1\@specialoutput\else#2\pec@end{%
440   \output{%
441     #1\@specialoutput\else
442     \pec@PatchVBoxCCLV
443     #2%
444   }%
445 }
446 \expandafter\expandafter\expandafter\pec@output
447 \expandafter\@firstofone\the\output\pec@end
448 \endpackage

```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/pdfcolmk.dtx](http://ctan.org/macros/latex/contrib/oberdiek/pdfcolmk.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcolmk.pdf](http://ctan.org/macros/latex/contrib/oberdiek/pdfcolmk.pdf) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](http://ctan.org/install/macros/latex/contrib/oberdiek.tds.zip)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](http://ctan.org/tds/tds.pdf)). Directories with `texmf` in their name are usually organized this way.

### 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

---

<sup>1</sup><http://ctan.org/pkg/pdfcolmk>

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain  $\text{\TeX}$ :

```
tex pdfcolmk.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfcolmk.sty → tex/latex/oberdiek/pdfcolmk.sty
pdfcolmk.pdf → doc/latex/oberdiek/pdfcolmk.pdf
pdfcolmk.dtx → source/latex/oberdiek/pdfcolmk.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 3.4 Refresh file name databases

If your  $\text{\TeX}$  distribution (te $\text{\TeX}$ , mi $\text{\TeX}$ , ...) relies on file name databases, you must refresh these. For example, te $\text{\TeX}$  users run `texhash` or `mktextlsr`.

### 3.5 Some details for the interested

**Unpacking with  $\text{\LaTeX}$ .** The `.dtx` chooses its action depending on the format:

**plain  $\text{\TeX}$ :** Run `docstrip` and extract the files.

**$\text{\LaTeX}$ :** Generate the documentation.

If you insist on using  $\text{\LaTeX}$  for `docstrip` (really, `docstrip` does not need  $\text{\LaTeX}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcolmk.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdf $\text{\LaTeX}$ :

```
pdflatex pdfcolmk.dtx
makeindex -s gind.ist pdfcolmk.idx
pdflatex pdfcolmk.dtx
makeindex -s gind.ist pdfcolmk.idx
pdflatex pdfcolmk.dtx
```

## 4 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `pdfcolmk.xml`.

```
449 (*catalogue)
450 <?xml version='1.0' encoding='us-ascii'?>
451 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
452 <entry datestamp='$Date$' modifier='$Author$' id='pdfcolmk'>
453   <name>pdfcolmk</name>
454   <caption>Improving colour support under pdftex.</caption>
455   <authorref id='auth:oberdiek'>
456   <copyright owner='Heiko Oberdiek' year='2000,2005-2008'>/>
457   <license type='lppl1.3'>/>
458   <version number='1.3'>/>
459   <description>
460     The package provides macros that emulate the &#x2018;colour stack&#x2019;
461     functionality of dvips. The colour stack deals with colour
462     manipulations when asynchronous events (like page-breaking) occur;
463     pdftex does not (yet) have such a stack, but dvips does, and the
464     <xref refid='color'>color</xref> package makes extensive use of
465     it.
466     <p/>
467     This package is an experimental solution to the problem, and works
468     best with pdf-e-tex.
469     <p/>
470     The package is part of the <xref refid='oberdiek'>oberdiek</xref> bundle.
471   </description>
472   <documentation details='Package documentation'
473     href='ctan:/macros/latex/contrib/oberdiek/pdfcolmk.pdf'>/>
474   <ctan file='true' path='/macros/latex/contrib/oberdiek/pdfcolmk.dtx'>/>
475   <miktex location='oberdiek'>/>
476   <texlive location='oberdiek'>/>
477   <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'>/>
478 </entry>
479 </catalogue>
```

## 5 History

[2000/08/27 v0.1]

- First published version in newsgroup [comp.text.tex](#):  
“[pdftex: bug with colors?](#)”<sup>2</sup>

[2000/09/02 v0.2]

- Next try.

[2000/09/02 v0.3]

- Solution without  $\varepsilon$ -T<sub>E</sub>X added.

[2000/09/06 v0.4]

- Patch commands added.
- Patch for seminar.cls added.

---

<sup>2</sup>Url: <http://groups.google.com/group/comp.text.tex/msg/6f088e69e4085d2c>

[2000/09/06 v0.5]

- Bug fix: initialization of `\pec@value` added.

[2005/06/15 v0.6]

- Support for `\marginpar` added. See thread in [comp.text.tex](#):  
“Using `\textcolor` and `\marginpar` together”<sup>3</sup>

[2005/07/09 v0.7]

- Output support added for memoir, provided by Lars Madsen.

[2006/02/20 v0.8]

- Code is not changed.
- DTX framework.

[2007/01/01 v1.0]

- If `pdftex.def`  $\geq$  2007/01/01 v0.04a is used with `pdfTeX`  $\geq$  1.40.0, then package `pdfcolmk` is obsolete.

[2007/04/11 v1.1]

- Line ends sanitized.

[2008/08/11 v1.2]

- Code is not changed.
- URLs updated.

[2016/05/16 v1.3]

- Documentation updates.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@@warning</code> . . . . .	249, 304
<code>\@addmarginpar</code> . . . . .	86, 144, 209, 281, 334, 340, 342, 346, 351, 366
<code>\@cclv</code> . . . . .	389, 391
<code>\@cons</code> 92, 93, 150, 151, 214, 215, 286, 287	
<code>\@currbox</code> . . . . .	93, 109, 151, 170, 215, 241, 287, 298
<code>\@currlist</code> . . . . .	91, 149, 213, 285
<code>\@depth</code> . . . . .	142, 207, 279, 332
<code>\@empty</code> . . . . .	22, 55, 62, 65, 69, 70, 84, 387, 398, 427
<code>\@firstofone</code> . . . . .	437, 447
<code>\@firstofthree</code> . . . . .	55, 58
<code>\@freelist</code> . . . . .	92, 93, 150, 151, 214, 215, 286, 287
<code>\@height</code> . . . . .	142, 207, 279, 332
<code>\@ifclassloaded</code> . . . . .	405, 413
<code>\@ifpackageloaded</code> . . . . .	11
<code>\@ifundefined</code> . . . . .	5, 218
<code>\@latex@warning@no@line</code> . . . .	114, 176
<code>\@latexbug</code> . . . . .	94, 152, 216, 288
<code>\@leftmark</code> . . . . .	59, 62, 67
<code>\@makeslide</code> . . . . .	415, 416
<code>\@marbox</code> . . . . .	91, 92, 109, 112, 120, 122, 123, 125, 127, 128, 139, 149, 150, 170, 174, 184, 186, 187, 189, 191, 192, 203, 213, 214, 241,

<sup>3</sup>URL: <http://groups.google.com/group/comp.text.tex/msg/38ed58f8845a2a4f>

247, 255, 257, 258, 259, 273, 285, 286, 298, 302, 310, 312, 313, 314, 316, 317, 328, 350, 357	\endcsname . . . . . 18
\@marn@log . . . . . 271	\endinginput . . . . . 9, 15, 29, 410, 420, 433
\@marnbottom . . . . . . 242, 244, 246, 253, 254, 255, 256	<b>F</b>
\@mpar@count . . . . . 217, 218, 237, 271	\firstmark . . . . . 65
\@mparbottom . . . . . 110, 118, 119, 120, 121, 172, 182, 183, 184, 185, 244, 300, 308, 309, 310, 311	<b>G</b>
\@mparbottoml . . . . . 242	\g@addto@macro . . . . . 69, 70
\@nameuse . . . . . 237	<b>H</b>
\@ne . . . . . 82, 95, 153, 219, 238, 289	\hb@xt@ . . . . . 131, 195, 320
\@next . . . . . 91, 149, 213, 285	\hbox . . . . . 142, 207, 262, 279, 332
\@nil . . . . . 347, 348, 350, 366	\hskip . . . . . 133, 134, 136, 137, 197, 198, 200, 201, 264, 265, 267, 268, 322, 323, 325, 326
\@pagedp . . . . . 129, 142, 193, 207, 260, 279, 318, 332	\hss . . . . . 139, 204, 274, 329, 350, 360
\@pageht . . . . . 111, 118, 173, 182, 246, 253, 301, 308	\ht . . . . . 112, 122, 127, 174, 186, 191, 247, 257, 258, 302, 312, 316
\@rightmark . . . . . 60, 65, 68	<b>I</b>
\@specialoutput . . . . . 423, 437, 439, 441	\if@filesw . . . . . 270
\@tempcnta . . . . . 95, 98, 104, 107, 109, 132, 153, 156, 162, 166, 169, 196, 219, 222, 228, 232, 236, 240, 263, 289, 292, 295, 297, 321	\if@firstcolumn . . . . . 97, 155, 221, 291
\@tempdima . . . . . 110, 111, 112, 113, 116, 119, 122, 124, 172, 173, 174, 175, 177, 180, 183, 186, 188, 246, 247, 248, 251, 254, 257, 261, 277, 300, 301, 302, 303, 306, 309, 312, 314	\if@mparswitch . . . . . 101, 159, 225
\@temptokena . . . . . 49, 50	\if@reversemargin . . . . . 107, 165, 231, 238
\@undefined . . . . . 39	\if@twocolumn . . . . . 96, 154, 220, 290
\@width . . . . . 142, 207, 279, 332	\ifcase . . . . . 338
<b>A</b>	\ifdim . . . . . 113, 175, 248, 303
\advance 111, 112, 119, 120, 121, 122, 173, 174, 183, 184, 185, 186, 217, 246, 247, 254, 255, 256, 257, 301, 302, 309, 310, 311, 312	\ifinner . . . . . 370, 378
\aftergroup . . . . . 374	\ifnum . . . . . 109, 132, 169, 196, 240, 263, 297, 321
<b>B</b>	\ifodd . . . . . 102, 226
\botmark . . . . . 55, 62	\ifoddpage . . . . . 160
\botmarks . . . . . 77	\ifx . . . . . 18, 39, 144, 209, 281, 334, 387, 398, 427
\box . . . . . 109, 125, 139, 170, 189, 203, 241, 273, 298, 314, 328, 350, 357	<b>K</b>
<b>C</b>	\kern . . . . . 129, 193, 318
\c@page . . . . . 102, 226	<b>L</b>
\chardef . . . . . 80, 82	\leftmark . . . . . 61, 69
\CheckCommand . . . . . 59, 60, 61, 64	<b>M</b>
\checkoddpage . . . . . 148	\m@ne . . . . . 98, 104, 156, 162, 217, 222, 228, 292, 295
\columnwidth . . . . . 131, 133, 195, 197, 262, 264, 320, 322, 347, 353	\marginparpush . . . . . 121, 185, 256, 311
\csname . . . . . 18	\marginparsep . . . . . 134, 136, 198, 200, 265, 267, 323, 325
\current@color . . . . . 50, 76, 369, 377, 384	\marginparwidth . . . . . 137, 201, 268, 326
<b>D</b>	\mark . . . . . 41, 43
\dp 120, 128, 184, 192, 255, 259, 310, 317	\marks . . . . . 39, 76
<b>E</b>	\mem@makecol . . . . . 406, 408
\empty . . . . . 42	\MessageBreak . . . . . 25, 33, 34, 35, 341, 430
	<b>N</b>
	\NeedsTeXFormat . . . . . 2
	\newcommand . . . . . 414
	\newmarks . . . . . 75
	\nobreak . . . . . 276
	\nointerlineskip . . . . . 130, 141, 194, 206, 261, 278, 319, 331
	<b>O</b>
	\on@line . . . . . 22, 84
	\output . . . . . 429, 437, 440, 447

<b>P</b>	
\PackageInfo	23, 32, 85, 339
\PackageWarningNoLine	6, 12, 428
\pdfliteral	355, 359, 369, 377, 390, 400
\pec@addmarginpar	90, 144, 147, 209, 212, 281, 284, 334
\pec@botcolor	54, 77, 384, 387, 390, 398, 400
\pec@end	423, 437, 439, 447
\pec@getmark	53, 77, 394, 402
\pec@mark	41, 50
\pec@marks	75, 76, 77
\pec@org@makeslide	414, 415, 418
\pec@output	423, 436, 439, 446
\pec@PatchAddMarginpar	347, 366
\pec@PatchAddMarginparI	348, 350
\pec@PatchAlreadyInBox	397
\pec@PatchVBoxCCLV	386, 407, 417, 442
\pec@result	80, 82, 338
\pec@setmark	45, 47, 76, 372, 380
\pec@temp	81, 145, 210, 282, 335
\pec@value	42, 44, 49
\protected@xdef	44
\ProvidesPackage	3
<b>R</b>	
\RequirePackage	74
\reset@color	374, 376
\rightmark	64, 70
\rlap	356
<b>S</b>	
\set@color	368
\setbox	109, 123, 170, 187, 241, 298, 313, 389
\space	86, 114, 177, 249, 304, 340, 342, 429
<b>T</b>	
\the	50, 177, 218, 237, 437, 447
\thepage	114, 177, 249, 304
<b>U</b>	
\unvbox	391
<b>V</b>	
\vbox	123, 187, 313, 389
\vrule	142, 207, 279, 332
\vskip	124, 188, 260, 261, 277, 314
<b>X</b>	
\x	425, 427
<b>Z</b>	
\z@	80, 109, 113, 116, 127, 128, 132, 142, 169, 175, 180, 191, 192, 196, 207, 240, 248, 251, 258, 259, 263, 279, 297, 303, 306, 316, 317, 321, 332