

# The pdfcolparcolumns package

Heiko Oberdiek  
<oberdiek@uni-freiburg.de>

2010/01/11 v1.3

## Abstract

Since version 1.40 pdfTeX supports several color stacks. This package uses them to fix color problems in package parcolumns.

## Contents

|          |   |          |
|----------|---|----------|
| <b>1</b> | <b>Usage</b>                              | <b>2</b> |
| 1.1      | Option rulebetweenecolor . . . . .        | 2        |
| 1.2      | Future . . . . .                          | 2        |
| <b>2</b> | <b>Implementation</b>                     | <b>2</b> |
| 2.1      | Identification . . . . .                  | 2        |
| 2.2      | Load packages . . . . .                   | 2        |
| 2.2.1    | Package parcolumns . . . . .              | 2        |
| 2.2.2    | Package pdfcol . . . . .                  | 3        |
| 2.2.3    | Package infwarerr . . . . .               | 3        |
| 2.3      | Color stack macros . . . . .              | 3        |
| 2.4      | Patches . . . . .                         | 3        |
| 2.4.1    | Init stacks . . . . .                     | 3        |
| 2.4.2    | Switch stack . . . . .                    | 4        |
| 2.4.3    | Set current stack color . . . . .         | 4        |
| <b>3</b> | <b>Test</b>                               | <b>6</b> |
| <b>4</b> | <b>Installation</b>                       | <b>7</b> |
| 4.1      | Download . . . . .                        | 7        |
| 4.2      | Bundle installation . . . . .             | 7        |
| 4.3      | Package installation . . . . .            | 7        |
| 4.4      | Refresh file name databases . . . . .     | 7        |
| 4.5      | Some details for the interested . . . . . | 8        |
| <b>5</b> | <b>References</b>                         | <b>8</b> |
| <b>6</b> | <b>History</b>                            | <b>8</b> |
|          | [2007/07/26 v1.0] . . . . .               | 8        |
|          | [2007/09/09 v1.1] . . . . .               | 8        |
|          | [2008/08/11 v1.2] . . . . .               | 9        |
|          | [2010/01/11 v1.3] . . . . .               | 9        |
| <b>7</b> | <b>Index</b>                              | <b>9</b> |

# 1 Usage

```
\usepackage{pdfcolparcolumns}
```

The package `pdfcolparcolumns` loads package `parcolumns` [1]. If color stacks are available then the macros of `parcolumns` are patched to add support for color stacks.

## 1.1 Option `rulebetweencolor`

Package `pdfcolparcolumns` also fixes the color for the rule between columns (if `rulebetween` is set). Default color is `\normalcolor`. But this can be changed by using option `rulebetweencolor`. It takes a color specification as value. If the value is empty, then the default (`\normalcolor`) is used. Examples:

```
rulebetweencolor=blue,
rulebetweencolor={red},
rulebetweencolor={}, % \normalcolor is used
rulebetweencolor=[rgb]{1,0,.5} % see below
```

If used inside the optional argument of environment `parcolumns` and the value contains an optional argument, then whole value must be put in curly braces:

```
\begin{parcolumns}[
  rulebetween,
  rulebetweencolor=[rgb]{1,0,.5},
]{2}
...
\end{parcolumns}
```

This option `rulebetweencolor` can also be set using `\setkeys`:

```
\setkeys{parcolumns}{rulebetweencolor=green}
```

## 1.2 Future

Currently package `parcolumns` does not seem to be maintained. Nevertheless if there will be a new version that adds support for color stacks, then this package may become obsolete.

# 2 Implementation

## 2.1 Identification

```
1 <*package>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{pdfcolparcolumns}%
4 [2010/01/11 v1.3 Color stacks support for parcolumns (HO)]%
```

## 2.2 Load packages

### 2.2.1 Package `parcolumns`

Currently package `parcolumns` does not define options. Thus it is just a precaution that the options of package `pdfcolparcolumns` are passed to package `parcolumns`.

```
5 \DeclareOption*{%
6   \PassOptionsToPackage{\CurrentOption}{parcolumns}%
7 }
8 \ProcessOptions\relax
9 \RequirePackage{parcolumns}[2004/11/25]
```

## 2.2.2 Package pdfcol

```
10 \RequirePackage{pdfcol}[2007/09/09]
11 \ifpdfcolAvailable
12 \else
13   \PackageInfo{pdfcolparcolumns}{%
14     Loading aborted, because color stacks are not available%
15   }%
16   \expandafter\endinput
17 \fi
```

## 2.2.3 Package infwarerr

```
18 \RequirePackage{infwarerr}[2007/09/09]
```

## 2.3 Color stack macros

`\pcpc@MaxStack` Macro `\pcpc@MaxStack` holds the highest number of allocated stacks.

```
19 \global\chardef\pcpc@MaxStack=\z@
```

`\pcpc@InitStacks` Macro `\pcpc@InitStacks` takes the number of columns as argument and ensures that there are enough color stacks for all columns.

```
20 \def\pcpc@InitStacks#1{%
21   \ifnum#1>\pcpc@MaxStack
22     \begingroup
23       \count@\pcpc@MaxStack
24       \loop
25         \advance\count@\@ne
26         \pdfcolInitStack{pcpc@\the\count@}%
27       \ifnum#1>\count@
28         \repeat
29       \global\chardef\pcpc@MaxStack=\count@
30     \endgroup
31   \fi
32 }
```

`\pcpc@SwitchStack`

```
33 \def\pcpc@SwitchStack#1{%
34   \pdfcolSwitchStack{pcpc@\number#1}%
35 }
```

`\pcpc@SetCurrent`

```
36 \def\pcpc@SetCurrent#1{%
37   \pdfcolSetCurrent{pcpc@\number#1}%
38 }
```

## 2.4 Patches

Now the color stack macros are patched into the macros of package `parcolumns`.

### 2.4.1 Init stacks

`\pcpc@InitStacks` should go into the definition of environment `parcolumns`. `\pc@allococolumns` is executed there and nowhere else, thus we hook into it.

```
39 \g@addto@macro\pc@allococolumns{%
40   \pcpc@InitStacks\pc@columncount
41 }
```

### 2.4.2 Switch stack

`\pcpc@SwitchStack` should be called by marco `\colchunk@`. However it is easier to patch `\pc@setcolumnwidth` that is executed in `\colchunk@` only.

```
42 \g@addto@macro\pc@setcolumnwidth{%  
43   \pcpc@SwitchStack\pc@columnctr  
44 }
```

### 2.4.3 Set current stack color

`\pcpc@SetCurrent` is set at the begin of each line. It must be inserted into `\pc@placeboxes`. Unhappily there is no easy way. Therefore we check and redefine `\pc@placeboxes`.

```
45 \begingroup  
46   \def\x{%  
47     \global\let\@tempa\relax  
48     \count@\z@  
49     \hb@xt@\linewidth{%  
50       \vfuzz30ex %  
51       \vbadness\@M  
52       \splittopskip\z@skip  
53       \loop  
54       \ifnum\count@<\pc@columncount  
55         \advance\count@\@ne  
56         \expandafter\ifvoid\csname pc@column@\number\count@\endcsname  
57           \hskip\csname pc@column@width@\number\count@\endcsname  
58         \else  
59           \expandafter\setbox\expandafter\@tempboxa\expandafter  
60             \vsplit\csname pc@column@\number\count@\endcsname  
61             to \dp\strutbox  
62             \vbox{%  
63               \unvbox\@tempboxa  
64             }%  
65         \fi  
66         \expandafter\ifvoid\csname pc@column@\number\count@\endcsname  
67         \else  
68           \global\let\@tempa\pc@placeboxes  
69         \fi  
70         \ifnum\count@<\pc@columncount  
71           \strut  
72           \hfill  
73           \ifpc@rulebetween  
74             \vrule  
75             \hfill  
76           \fi  
77         \fi  
78       \repeat  
79     }%  
80     \@tempa  
81   }%  
82   \ifx\x\pc@placeboxes  
83   \else  
84     \@PackageWarningNoLine{pdfcolparcolumns}{%  
85       Command \string\pc@placeboxes\space has changed.\MessageBreak  
86       Supported versions of package ‘parcolumns’:\MessageBreak  
87       \space\space 2004/08/05.\MessageBreak  
88       The redefinition of \string\pc@placeboxes\space may not%  
89       \MessageBreak  
90       behave correctly depending on the changes%  
91     }%  
92   \fi  
93 \endgroup
```

\pc@placeboxes

```

94 \renewcommand*{\pc@placeboxes}{%
95   \global\let\@tempa\relax
96   \count@\z@
97   \hb@xt@\linewidth{%
98     \vfuzz30ex %
99     \vbadness\@M
100    \splittopskip\z@skip
101    \loop
102    \ifnum\count@<\pc@columncount
103      \advance\count@\@ne
104      \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
105      \hskip\csname pc@column@width@\number\count@\endcsname
106      \else
107        \expandafter\setbox\expandafter\@tempboxa\expandafter
108        \vsplit\csname pc@column@\number\count@\endcsname
109        to \dp\strutbox
110        \vbox{%
111          \pcpc@SetCurrent\count@
112          \unvbox\@tempboxa
113        }%
114      \fi
115      \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
116      \else
117        \global\let\@tempa\pc@placeboxes
118      \fi
119      \ifnum\count@<\pc@columncount
120        \strut
121        \hfill
122        \ifpc@rulebetween
123          \begingroup
124            \pcpc@RuleBetweenColor
125            \vrule
126          \endgroup
127          \hfill
128        \fi
129      \fi
130    \repeat
131  }%
132  \@tempa
133 }
```

\pcpc@RuleBetweenColorDefault

```

134 \def\pcpc@RuleBetweenColorDefault{%
135   \normalcolor
136 }
```

\pcpc@RuleBetweenColor

```

137 \let\pcpc@RuleBetweenColor\pcpc@RuleBetweenColorDefault

138 \define@key{parcolumns}{rulebetweencolor}{%
139   \edef\pcpc@temp{#1}%
140   \ifx\pcpc@temp\@empty
141     \let\pcpc@RuleBetweenColor\pcpc@RuleBetweenColorDefault
142   \else
143     \edef\pcpc@temp{%
144       \noexpand\@ifnextchar [{%
145         \def\noexpand\pcpc@RuleBetweenColor{%
146           \noexpand\color\pcpc@temp
147         }%
148         \noexpand\pcpc@GobbleNil
149       }{%

```

```

150      \def\noexpand\pcpc@RuleBetweenColor{%
151      \noexpand\color{\pcpc@temp}%
152      }%
153      \noexpand\pcpc@GobbleNil
154      }%
155      \pcpc@temp\noexpand\@nil
156      }%
157      \pcpc@temp
158      \fi
159 }

```

\pcpc@GobbleNil

```

160 \long\def\pcpc@GobbleNil#1\@nil{}
161 </package>

```

### 3 Test

The test file is a modified version of the file that Donald Goodman has posted in [comp.text.tex](#): “Re: xcolor glitches”<sup>1</sup>

```

162 <test1>
163 \NeedsTeXFormat{LaTeX2e}
164 \AtEndDocument{%
165   \typeout{%
166     \typeout{*****}%
167     \typeout{*** \space Check the PDF file manually! \space ***}%
168     \typeout{*****}%
169     \typeout{%
170   }
171 \documentclass{article}
172 \usepackage{xcolor}
173 \usepackage{pdfcolparcolumns}
174
175 \newcommand{\instruct}[1]{%
176   \noindent
177   \footnotesize
178   \textcolor{red}{#1}%
179 }
180
181 \begin{document}
182   \begin{parcolumns}[colwidths={1=2.3in,2=2.3in},sloppy]{2}%
183     \colchunk[1]{%
184       \instruct{Et non dicitur versus} %
185       Fidelium anim\ae\ %
186       \instruct{%
187         sed immediate subiungitur antiphona finalis %
188         beat\ae\ Mari\ae\ Virginis%
189       } %
190       100.%
191     }%
192     \colchunk[2]{%
193       \instruct{%
194         And the verse %
195         \textcolor{black}{May the souls of the faithful} %
196         is not said, but the final antiphon of the %
197         Blessed Virgin Mary, %
198         \textcolor{black}{100,} %
199         is immediately joined.%
200       }%
201     }%

```

<sup>1</sup>Url: <http://groups.google.com/group/comp.text.tex/msg/8eda74ed292012bb>

```

202 \end{parcolumns}%
203 \end{document}
204 </test1>

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>2</sup>:

[CTAN:macros/latex/contrib/oberdiek/pdfcolparcolumns.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcolparcolumns.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```

chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/

```

### 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain-T<sub>E</sub>X:

```
tex pdfcolparcolumns.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```

pdfcolparcolumns.sty      → tex/latex/oberdiek/pdfcolparcolumns.sty
pdfcolparcolumns.pdf      → doc/latex/oberdiek/pdfcolparcolumns.pdf
test/pdfcolparcolumns-test1.tex → doc/latex/oberdiek/test/pdfcolparcolumns-test1.tex
pdfcolparcolumns.dtx      → source/latex/oberdiek/pdfcolparcolumns.dtx

```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

### 4.4 Refresh file name databases

If your T<sub>E</sub>X distribution (teT<sub>E</sub>X, mikT<sub>E</sub>X, ...) relies on file name databases, you must refresh these. For example, teT<sub>E</sub>X users run `texhash` or `mktextlsr`.

<sup>2</sup>[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

## 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk pdfcolparcolumns.pdf unpack_files output .
```

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain-T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for `docstrip` (really, `docstrip` does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcolparcolumns.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex pdfcolparcolumns.dtx
makeindex -s gind.ist pdfcolparcolumns.idx
pdflatex pdfcolparcolumns.dtx
makeindex -s gind.ist pdfcolparcolumns.idx
pdflatex pdfcolparcolumns.dtx
```

## 5 References

- [1] Jonathan Sauer: *The parcolumns package*; 2004/11/25;  
[CTAN:macros/latex/contrib/sauerj/parcolumns.pdf](http://www.ctan.org/ctan/macros/latex/contrib/sauerj/parcolumns.pdf).
- [2] Heiko Oberdiek: *The pdfcol package*; 2007/09/09;  
[CTAN:macros/latex/contrib/oberdiek/pdfcol.pdf](http://www.ctan.org/ctan/macros/latex/contrib/oberdiek/pdfcol.pdf).

## 6 History

[2007/07/26 v1.0]

- First version, published in the newsgroup [comp.text.tex](http://groups.google.com/group/comp.text.tex) with the name `parcolumns-colorstacks`: “[Re: xcolor glitches](http://groups.google.com/group/comp.text.tex/msg/56bd897b11bca414)”<sup>3</sup>

[2007/09/09 v1.1]

- CTAN version, package name renamed to `pdfcolparcolumns`.
- Uses package `pdfcol`.
- Documentation added.
- Test file added.

---

<sup>3</sup>Url: <http://groups.google.com/group/comp.text.tex/msg/56bd897b11bca414>



[2008/08/11 v1.2]

- Code is not changed.
- URLs updated.

[2010/01/11 v1.3]

- Fix for rule color.
- New option `rulebetweencolor` for environment `parcolumns`.

## 7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols                             |  | G  |   |
|-------------------------------------|--|--|---|
| <code>\@M</code>                    | 51, 99   | <code>\g@addto@macro</code>                | 39, 42  |
| <code>\@PackageWarningNoLine</code> | 84   | H  |   |
| <code>\@empty</code>                | 140  | <code>\hb@xt@</code>                       | 49, 97  |
| <code>\@ifnextchar</code>           | 144  | <code>\hfill</code>                        | 72, 75, 121, 127                              |
| <code>\@ne</code>                   | 25, 55, 103  | <code>\hskip</code>                        | 57, 105                                       |
| <code>\@nil</code>                  | 155, 160   | I  |   |
| <code>\@tempa</code>                | 47, 68, 80, 95, 117, 132   | <code>\ifnum</code>                        | 21, 27, 54, 70, 102, 119                      |
| <code>\@tempboxa</code>             | 59, 63, 107, 112   | <code>\ifpc@rulebetween</code>             | 73, 122                                       |
|                                     |  | <code>\ifpdfcolAvailable</code>            | 11  |
| <code>\_</code>                     | 185, 188   | <code>\ifvoid</code>                       | 56, 66, 104, 115                              |
| A                                   |  | <code>\ifx</code>                          | 82, 140                                       |
| <code>\advance</code>               | 25, 55, 103  | <code>\instruct</code>                     | 175, 184, 186, 193                            |
| <code>\ae</code>                    | 185, 188   | L  |   |
| <code>\AtEndDocument</code>         | 164  | <code>\linewidth</code>                    | 49, 97  |
| B                                   |  | <code>\loop</code>                         | 24, 53, 101                                   |
| <code>\begin</code>                 | 181, 182   | M  |   |
| C                                   |  | <code>\MessageBreak</code>                 | 85, 86, 87, 89                                |
| <code>\chardef</code>               | 19, 29   | N  |   |
| <code>\colchunk</code>              | 183, 192   | <code>\NeedsTeXFormat</code>               | 2, 163  |
| <code>\color</code>                 | 146, 151   | <code>\newcommand</code>                   | 175   |
| <code>\count@</code>                | 23, 25, 26, 27, 29, 48, 54,<br>55, 56, 57, 60, 66, 70, 96, 102,<br>103, 104, 105, 108, 111, 115, 119 | <code>\noindent</code>                     | 176   |
| <code>\csname</code>                | 56, 57, 60, 66, 104, 105, 108, 115   | <code>\normalcolor</code>                  | 135   |
| <code>\CurrentOption</code>         | 6  | <code>\number</code>                       | 34,<br>37, 56, 57, 60, 66, 104, 105, 108, 115 |
| D                                   |  | P  |   |
| <code>\DeclareOption</code>         | 5  | <code>\PackageInfo</code>                  | 13  |
| <code>\define@key</code>            | 138  | <code>\PassoptionsToPackage</code>         | 6   |
| <code>\documentclass</code>         | 171  | <code>\pc@alloccolumns</code>              | 39  |
| <code>\dp</code>                    | 61, 109  | <code>\pc@columncount</code>               | 40, 54, 70, 102, 119                          |
| E                                   |  | <code>\pc@columnctr</code>                 | 43  |
| <code>\end</code>                   | 202, 203   | <code>\pc@placeboxes</code>                | 68, 82, 85, 88, 94                            |
| <code>\endcsname</code>             | 56, 57, 60, 66, 104, 105, 108, 115   | <code>\pc@setcolumnwidth</code>            | 42  |
| <code>\endinput</code>              | 16   | <code>\pcpc@GobbleNil</code>               | 148, 153, 160                                 |
| F                                   |  | <code>\pcpc@InitStacks</code>              | 20, 40  |
| <code>\footnotesize</code>          | 177  | <code>\pcpc@MaxStack</code>                | 19, 21, 23, 29                                |
|                                     |  | <code>\pcpc@RuleBetweenColor</code>        | 124, 137, 141, 145, 150                       |
|                                     |  | <code>\pcpc@RuleBetweenColorDefault</code> | 134, 137, 141                                 |

|                    |                                   |             |                         |
|--------------------|-----------------------------------|-------------|-------------------------|
| \pcpc@SetCurrent   | 36, 111                           |             |                         |
| \pcpc@SwitchStack  | 33, 43                            |             |                         |
| \pcpc@temp         | 139, 140, 143, 146, 151, 155, 157 |             |                         |
| \pdfcolInitStack   | 26                                |             |                         |
| \pdfcolSetCurrent  | 37                                |             |                         |
| \pdfcolSwitchStack | 34                                |             |                         |
| \ProcessOptions    | 8                                 |             |                         |
| \ProvidesPackage   | 3                                 |             |                         |
| <b>R</b>           |                                   |             |                         |
| \renewcommand      | 94                                |             |                         |
| \repeat            | 28, 78, 130                       |             |                         |
| \RequirePackage    | 9, 10, 18                         |             |                         |
| <b>S</b>           |                                   |             |                         |
| \setbox            | 59, 107                           |             |                         |
| \space             | 85, 87, 88, 167                   |             |                         |
| \splittopskip      | 52, 100                           |             |                         |
| \strut             | 71, 120                           |             |                         |
| \strutbox          | 61, 109                           |             |                         |
|                    |                                   | <b>T</b>    |                         |
|                    |                                   | \textcolor  | 178, 195, 198           |
|                    |                                   | \the        | 26                      |
|                    |                                   | \typeout    | 165, 166, 167, 168, 169 |
|                    |                                   | <b>U</b>    |                         |
|                    |                                   | \unvbox     | 63, 112                 |
|                    |                                   | \usepackage | 172, 173                |
|                    |                                   | <b>V</b>    |                         |
|                    |                                   | \vbadness   | 51, 99                  |
|                    |                                   | \vbox       | 62, 110                 |
|                    |                                   | \vfuzz      | 50, 98                  |
|                    |                                   | \vrule      | 74, 125                 |
|                    |                                   | \vsplit     | 60, 108                 |
|                    |                                   | <b>X</b>    |                         |
|                    |                                   | \x          | 46, 82                  |
|                    |                                   | <b>Z</b>    |                         |
|                    |                                   | \z@         | 19, 48, 96              |
|                    |                                   | \z@skip     | 52, 100                 |