

# The pdfcrypt package

Heiko Oberdiek

<heiko.oberdiek at gmail.com>

2007/04/26 v1.0

## Abstract

This package supports the setting of pdf encryption options for VTeX and some older versions of pdfTeX.

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	Alternatives	2
1.2	Usage	2
1.2.1	Special characters	3
1.2.2	\nopdfcrypt	3
1.2.3	Configuration file	3
1.2.4	Support for plain T <sub>E</sub> X	3
1.3	Hints for pdfT <sub>E</sub> X	3
<b>2</b>	<b>Implementation</b>	<b>4</b>
2.1	Help macros for plain T <sub>E</sub> X	4
2.2	Package Identification and checks	5
2.3	Driver detection	6
2.4	Load package keyval	6
2.5	Define options	7
2.6	support of configuration file	12
2.7	Package options	12
<b>3</b>	<b>Installation</b>	<b>12</b>
3.1	Download	12
3.2	Bundle installation	13
3.3	Package installation	13
3.4	Refresh file name databases	13
3.5	Some details for the interested	13
<b>4</b>	<b>Catalogue</b>	<b>14</b>
<b>5</b>	<b>History</b>	<b>15</b>
	[2001/04/02 v0.1]	15
	[2001/07/19 v0.2]	15
	[2001/07/19 v0.3]	15
	[2001/07/19 v0.4]	15
	[2001/08/05 v0.5]	15
	[2001/08/09 v0.6]	15
	[2001/10/28 v0.7]	15

[2006/02/20 v0.8]	15
[2007/04/11 v0.9]	16
[2007/04/26 v1.0]	16
<b>6 Index</b>	<b>16</b>

## 1 Documentation

This package allows the setting of pdf encryption options for

- V<sub>T</sub>E<sub>X</sub>, since version 7.35, <http://www.micropress-inc.com/>.
- pdf<sub>T</sub>E<sub>X</sub>, patched by Ricardo Sanchez Carmenes<sup>1</sup>.  
Some supported versions are:

pdf<sub>T</sub>E<sub>X</sub>-1.00a,  
pdf<sub>T</sub>E<sub>X</sub>-0.14h-pdfcrypt-20010310,  
pdfcrypt-20010331

**Note:** Since pdf<sub>T</sub>E<sub>X</sub>-1.10a (2003-01-16) encryption support was dropped! Thus the package is now obsolete for recent pdf<sub>T</sub>E<sub>X</sub> versions.

### 1.1 Alternatives

There are free alternatives, programs that can be used for postprocessing the pdf file:

- pdftk  
<http://www.accesspdf.com/pdftk/>
- Multivalent  
<http://multivalent.sourceforge.net/>
- PDFBox  
<http://www.pdfbox.org/>
- PDFTrans  
<http://maddingue.free.fr/software/pdftrans.html>
- ...

### 1.2 Usage

The options can be set as package options or with the command `\pdfcryptsetup`:

```
owner=<owner password>
user=<user password>
print, copy, edit, annotate=true, false
all, none
debug
```

The encryption is set at `\begin{document}` by default, but this can be forced for an earlier time using the option `set`. Example:

```
\usepackage[owner=Donald,user=Knuth,print=false]{pdfcrypt}
...
\begin{document}
```

---

<sup>1</sup>Ricardo Sanchez Carmenes's email address: [carmenes@bioquimica.uniovi.es](mailto:carmenes@bioquimica.uniovi.es)

or

```
\usepackage{pdfcrypt}
\pdfcryptsetup{owner=Donald,user=Knut}
\pdfcryptsetup{print=false,set}
...
\begin{document}
```

### 1.2.1 Special characters

The characters ‘{’, ‘}’, and ‘\’ have to be escaped with ‘\’. Then the string should not be specified as package option but with the macro `\pdfcryptsetup`, eg:

```
\pdfcryptsetup{user={\{\}\Hello\}},print=false}
```

The password here is “`{\Hello}`”. Active characters can be used and are not expanded. Macros except for `\{`, `\}`, and `\%` should not be used and are not expanded.

### 1.2.2 `\nopdfcrypt`

Often the whole process of pdf generation includes several  $\text{\TeX}$  compilations and perhaps other postprocessing steps. Therefore a feature would be useful to disable the encryption stuff in order to speed up the first compilations. Therefore package `pdfcrypt` will look for the macro `\nopdfcrypt`. If it has the meaning of the letter ‘Y’, the package will be disabled. Example:

```
pdflatex '\let\nopdfcrypt=Y\input myfile'
thumbpdf myfile
pdfelatex myfile
```

### 1.2.3 Configuration file

If the file `pdfcrypt.cfg` exists it is loaded and can be used for common settings.

### 1.2.4 Support for plain $\text{\TeX}$

The package can also be used with plain  $\text{\TeX}$ . It defines the missing  $\text{\LaTeX}$  macros and loads package `keyval`. The configuration file is not supported and automatically loaded.

## 1.3 Hints for pdf $\text{\TeX}$

This section is out of date, because the encryption support was removed from pdf $\text{\TeX}$ . Therefore this hints are of historical interest only.

\* There are packages such as `thumbpdf` that ship out some stuff (`\immediate\pdfobj{...}`). In these cases `\pdfcrypt` will be ignored without warning or error message. Therefore the package `pdfcrypt` should be loaded before and option “set” should be used in order to force the call of `\pdfcrypt`, for example:

```
\usepackage{pdfcrypt}
\pdfcryptsetup{..., set}
...
\usepackage{thumbpdf}
```

```

* Compiling pdfTeX (eg. version 1.00a-pretest-20010804):
pdfTeX versions are available at
  ftp://ftp.cstug.cz/pub/tex/local/cstug/thanh/pdftex/snapshots/
Unpack the latest .tgz file:
  > tar xzf pdftex-20010804.tgz
Enable encryption support:
  src> cd src/teXk/web2c/pdftexdir
  src/teXk/web2c/pdftexdir> ln -fs pdfcrypt-full.c pdfcrypt.c
Compile:
  src/teXk/web2c/pdftexdir> cd ../../..
  src> ./configure
  src> cd teXk/web2c
  src/teXk/web2c> make pdftexbin
At last install the binary and pool files.

```

## 2 Implementation

```
1 \*package)
```

### 2.1 Help macros for plain T<sub>E</sub>X

```

2 \expandafter\edef\csname pc@endinput\endcsname{%
3   \catcode'\noexpand\@=\the\catcode'\@ \relax
4   \noexpand\endinput
5 }
6 \catcode'\@=11 %
7
8 \expandafter\ifx\csname @firstoftwo\endcsname \relax
9   \long\def\@firstoftwo#1#2{#1}%
10 \fi
11
12 \expandafter\ifx\csname @secondoftwo\endcsname \relax
13   \long\def\@secondoftwo#1#2{#2}%
14 \fi
15
16 \expandafter\ifx\csname @ifundefined\endcsname \relax
17   \def\@ifundefined#1{%
18     \expandafter\ifx\csname #1\endcsname \relax
19       \expandafter\@firstoftwo
20     \else
21       \expandafter\@secondoftwo
22     \fi
23   }%
24 \fi
25
26 \@ifundefined{ifnextchar}{%
27   \long\def\@ifnextchar#1#2#3{%
28     \let\reserved@d=#1%
29     \def\reserved@a{#2}%
30     \def\reserved@b{#3}%
31     \futurelet\@let@token\@ifnch
32   }%
33   \def\@ifnch{%
34     \ifx\@let@token\@sptoken
35       \let\reserved@c\@xifnch
36     \else
37       \ifx\@let@token\reserved@d
38         \let\reserved@c\reserved@a

```

```

39     \else
40     \let\reserved@c\reserved@b
41     \fi
42     \fi
43     \reserved@c
44 }%
45 \begingroup
46 \def\:\global\let\@sptoken=}%
47 \:}%
48 \def\:\@xifnch}%
49 \expandafter\gdef\:\{\futurelet\@let@token\@ifnch}%
50 \endgroup
51 }{}
52
53 \@ifundefined{ProvidesPackage}{%
54   \def\ProvidesPackage#1{%
55     \ifnextchar[\pc@ProvidesPackage{#1}}%
56     {\pc@ProvidesPackage{#1}[]}%
57   }%
58   \def\pc@ProvidesPackage#1[#2]{%
59     \immediate\write-1{Package: #1 #2}%
60   }%
61 }{}
62
63 \begingroup\expandafter\expandafter\expandafter\endgroup
64 \expandafter\ifx\csname RequirePackage\endcsname\relax
65   \input infwarerr.sty\relax
66 \else
67   \RequirePackage{infwarerr}%
68 \fi
69
70 \@ifundefined{@gobble}{%
71   \long\def@gobble#1{}%
72 }{}
73
74 \@ifundefined{@empty}{%
75   \def@empty{}%
76 }{}

```

## 2.2 Package Identification and checks

```

77 \ProvidesPackage{pdfcrypt}%
78 [2007/04/26 v1.0 Allows the setting of PDF encryption (H0)]%
79 \@ifundefined{pdfcryptsetup}{%
80   \let\pdfcryptsetup@gobble
81 }{}%
82 \@PackageWarningNoLine{pdfcrypt}{Package pdfcrypt is already loaded}%
83 \pc@endinput
84 }

```

Support for \nopdfcrypt.

```

85 \newif\ifpc@nopdfcrypt
86 \ifx Y\nopdfcrypt
87   \@PackageWarningNoLine{pdfcrypt}{%
88     Encryption disabled by \string \nopdfcrypt\space request%
89   }%
90   \global\pc@nopdfcrypttrue
91 \fi

```

## 2.3 Driver detection

```
92 \let\pc@driver\@empty
93 \begingroup
94 % pdfTeX detection
95 \@ifundefined{pdfoutput}{%
96 }{%
97   \ifcase\pdfoutput
98   \else
99     \@ifundefined{pdfcrypt}{%
100       \@PackageError{pdfcrypt}{%
101         PDF encryption is not supported with this pdfTeX%
102       }{%
103         Encryption support was added in 0.14h (2001/03/10)\MessageBreak
104         and removed in 1.10a (2003/01/16).%
105       }%
106     \endgroup
107     \pc@endinput
108   }{%
109     \gdef\pc@driver{pdftex}%
110   }%
111 \fi
112 }%
113 % VTeX detection
114 \@ifundefined{OpMode}{%
115 }{%
116   \ifnum\OpMode=1 %
117     \ifnum\@ifundefined{VTeXversion}0\VTeXversion<735 %
118       \@PackageError{pdfcrypt}{%
119         PDF encryption is not supported with this VTeX%
120       }{%
121         You need VTeX 7.35 or higher.%
122       }%
123     \endgroup
124     \pc@endinput
125   \else
126     \gdef\pc@driver{vtex}%
127   \fi
128 \fi
129 }%
130 \endgroup
```

## 2.4 Load package keyval

```
131 \@ifundefined{@makeother}{%
132   \def\@makeother#1{\catcode'#1=12\relax}%
133 }{}
134
135 \@ifundefined{g@addto@macro}{%
136   \long\def\g@addto@macro#1#2{%
137     \begingroup
138     \toks@\expandafter{#1#2}%
139     \xdef#1{\the\toks@}%
140   \endgroup
141   }%
142 }{}
143
144 \@ifundefined{@namedef}{%
145   \def\@namedef#1{\expandafter\def\csname#1\endcsname}%
146 }
```

```

146 }{}
147
148 \@ifundefined{@nameuse}{%
149   \def\@nameuse#1{\csname #1\endcsname}%
150 }{}
151
152 \def\pc@KeyvalRestore{%
153   \let\pc@KeyvalRestore\@undefined
154 }
155
156 \let\pcOrg@NeedsTeXFormat\NeedsTeXFormat
157 \@ifundefined{NeedsTeXFormat}{%
158   \def\NeedsTeXFormat#1{%
159     \g@addto@macro\pc@KeyvalRestore{%
160       \let\NeedsTeXFormat\pcOrg@NeedsTeXFormat
161     }%
162 }{}
163
164 \let\pcOrg@DeclareOption\DeclareOption
165 \@ifundefined{DeclareOption}{%
166   \def\DeclareOption#1#2{#2}%
167   \g@addto@macro\pc@KeyvalRestore{%
168     \let\DeclareOption\pcOrg@DeclareOption
169   }%
170 }{}
171
172 \let\pcOrg@ExecuteOptions\ExecuteOptions
173 \@ifundefined{ExecuteOptions}{%
174   \def\ExecuteOptions#1{%
175     \g@addto@macro\pc@KeyvalRestore{%
176       \let\ExecuteOptions\pcOrg@ExecuteOptions
177     }%
178 }{}
179
180 \let\pcOrg@ProcessOptions\ProcessOptions
181 \@ifundefined{ProcessOptions}{%
182   \def\ProcessOptions{%
183     \g@addto@macro\pc@KeyvalRestore{%
184       \let\ProcessOptions\pcOrg@ProcessOptions
185     }%
186 }{}%
187
188 \begingroup\expandafter\expandafter\expandafter\endgroup
189 \expandafter\ifx\csname RequirePackage\endcsname\relax
190   \input keyval.sty\relax
191 \else
192   \RequirePackage{keyval}%
193 \fi
194 \pc@KeyvalRestore

```

## 2.5 Define options

```

195 \@ifundefined{@dblarg}{%
196   \long\def\@dblarg#1{\@ifnextchar[{\#1}{\@xdblarg{\#1}}}%
197   \long\def\@xdblarg#1#2{#1[#2]#2}%
198 }{}
199
200 \newif\ifpc@set
201 \newif\ifpc@print

```

```

202 \newif\ifpc@copy
203 \newif\ifpc@edit
204 \newif\ifpc@annotate
205 \newif\ifpc@debug
206 \let\pc@owner\@empty
207 \let\pc@user\@empty
208
209 % default: allow all
210 \pc@printtrue
211 \pc@copytrue
212 \pc@edittrue
213 \pc@annotatetrue
214
215 \edef\pc@temp{\catcode'\noexpand\"=\the\catcode'\relax}
216 \makeoother\"
217 \def\pc@set{%
218   \@PackageInfo{pdfcrypt}{%
219     \ifpc@debug
220       \ifx\pc@owner\@empty
221         No owner password%
222       \else
223         Owner password: '\pc@owner'%
224       \fi
225       \MessageBreak
226       \ifx\pc@user\@empty
227         No user password%
228       \else
229         User password: '\pc@user'%
230       \fi
231       \MessageBreak
232       Flags: %
233       \ifpc@print   \else no\fi print, %
234       \ifpc@copy    \else no\fi copy, %
235       \ifpc@edit    \else no\fi edit, %
236       \ifpc@annotate\else no\fi annotate%
237       \MessageBreak
238     \fi
239     \ifpc@nopdfcrypt
240       Encryption is disabled by '\string\nopdfcrypt'%
241     \else
242       Encryption is set for '\pc@driver'%
243     \fi
244   }%
245   \ifpc@nopdfcrypt
246   \else
247     \@ifundefined{pc@set@\pc@driver}{%
248       \ifx\pc@driver\@empty
249         \@PackageError{pdfcrypt}{No driver for encryption %
250           support found}\@ehc
251       \else
252         \@PackageError{pdfcrypt}{Cannot set encryption for %
253           unknown driver '\pc@driver'}\@ehc
254       \fi
255     }{%
256       \@nameuse{pc@set@\pc@driver}%
257     }%
258   \fi
259 }

```



```

260 \def\pc@set@pdftex{%
261   \ifnum\pdftexversion<100 %
262     \pc@set@pdftexold
263   \else
264     \pc@set@pdftexnew
265   \fi
266 }
267 \def\pc@set@pdftexold{%
268   \pdfcrypt{%
269     owner "\pc@owner" %
270     user "\pc@user" %
271     \ifpc@print   \else no\fi print %
272     \ifpc@copy    \else no\fi copy %
273     \ifpc@edit    \else no\fi edit %
274     \ifpc@annotate\else no\fi annotate%
275   }%
276 }
277 \def\pc@set@pdftexnew{%
278   \pdfcrypt
279   owner{\pc@owner}%
280   user{\pc@user}%
281   \ifpc@print   \else no\fi print %
282   \ifpc@copy    \else no\fi copy %
283   \ifpc@edit    \else no\fi edit %
284   \ifpc@annotate\else no\fi annotate%
285   \relax
286 }
287 \def\pc@set@vtex{%
288   \immediate\special{!security %
289     O=\pc@MakeVTeXString\pc@owner,%
290     U=\pc@MakeVTeXString\pc@user,%
291     P\ifpc@print +\else -\fi,%
292     C\ifpc@copy +\else -\fi,%
293     M\ifpc@edit +\else -\fi,%
294     A\ifpc@annotate +\else -\fi
295   }%
296 }
297 \def\pc@MakeVTeXString#1{%
298   "\expandafter\pc@@MakeVTeXString#1"@nil"
299 }
300 \def\pc@@MakeVTeXString#1"#2@nil{%
301   #1%
302   \ifx\#2\%
303     \else
304       "%
305       \@ReturnAfterFi{%
306         \pc@@MakeVTeXString#2@nil
307       }%
308     \fi
309 }
310 \long\def\@ReturnAfterFi#1\fi{\fi#1}
311 \pc@temp
312
313 \begingroup
314   \catcode'\ =12 \gdef\pc@spaceother{ }\catcode'\ =10\relax
315   \catcode'\|=0 %
316   \catcode'\|=12 %
317   \gdef\pc@DefString#1#2{%

```

```

318 |def#1{#2}%
319 |edef#1{|expandafter|strip@prefix|meaning#1}%
320 |edef#1{|expandafter|pc@SpaceToOther#1 |@nil}%
321 |edef#1{|expandafter|pc@EscapeRemove#1|@empty|@empty|@nil}%
322 }%
323 |gdef|pc@EscapeRemove#1\#2#3|@nil{%
324 #1#2%
325 |ifx|\#3|\%%
326 |else
327 |@ReturnAfterFi{%
328 |pc@EscapeRemove#3|@nil
329 }%
330 |fi
331 }%
332 |endgroup
333 \def\pc@SpaceToOther#1 #2\@nil{%
334 #1%
335 \ifx\#2\%
336 \else
337 \pc@spaceother
338 \@ReturnAfterFi{%
339 \pc@SpaceToOther#2\@nil
340 }%
341 \fi
342 }
343
344 \def\pc@boolkey{\@dblarg\pc@@boolkey}
345 \def\pc@@boolkey[#1]#2#3{%
346 \lowercase{\def\pc@temp{#3}}%
347 \ifx\pc@temp\@empty
348 \let\pc@temp\pc@true
349 \fi
350 \ifx\pc@temp\pc@true
351 \else
352 \ifx\pc@temp\pc@false
353 \else
354 \let\pc@temp\relax
355 \fi
356 \fi
357 \ifx\pc@temp\relax
358 \@PackageWarning{pdfcrypt}{%
359 Unexpected value \string'#3\string' of %
360 option \string'#2\string'\MessageBreak
361 instead of %
362 \string'true\string' or \string'false\string'%
363 }%
364 \else
365 \csname pc@#2\pc@temp\endcsname
366 \fi
367 }
368 \def\pc@true{true}
369 \def\pc@false{false}
370
371 \define@key{pc}{set}[true]{%
372 \pc@boolkey{set}{#1}%
373 }
374 \define@key{pc}{pdftex}[]{%
375 \def\pc@driver{pdftex}%

```

```

376 }
377 \define@key{pc}{vtex}[] {%
378   \def\pc@driver{vtex}%
379 }
380 \define@key{pc}{print}[true] {%
381   \pc@boolkey{print}{#1}%
382 }
383 \define@key{pc}{copy}[true] {%
384   \pc@boolkey{copy}{#1}%
385 }
386 \define@key{pc}{edit}[true] {%
387   \pc@boolkey{edit}{#1}%
388 }
389 \define@key{pc}{annotate}[true] {%
390   \pc@boolkey{annotate}{#1}%
391 }
392 \define@key{pc}{all}[] {%
393   \pc@boolkey{print}{true}%
394   \pc@boolkey{copy}{true}%
395   \pc@boolkey{edit}{true}%
396   \pc@boolkey{annotate}{true}%
397 }
398 \define@key{pc}{none}[] {%
399   \pc@boolkey{print}{false}%
400   \pc@boolkey{copy}{false}%
401   \pc@boolkey{edit}{false}%
402   \pc@boolkey{annotate}{false}%
403 }
404
405 \define@key{pc}{owner} {%
406   \pc@DefString\pc@owner{#1}%
407 }
408 \define@key{pc}{user} {%
409   \pc@DefString\pc@user{#1}%
410 }
411 \define@key{pc}{debug}[true] {%
412   \pc@boolkey{debug}{#1}%
413 }
414
415 \def\pdfcryptsetup#1 {%
416   \setkeys{pc}{#1}%
417   \ifpc@set
418     \pc@set
419     \global\let\pc@set\relax
420     \gdef\pdfcryptsetup##1 {%
421       \@PackageWarning{pdfcrypt} {%
422         Encryption options are already set\MessageBreak
423         new values are ignored%
424       }%
425     }%
426   \fi
427 }
428 \begingroup\expandafter\expandafter\expandafter\endgroup
429 \expandafter\ifx\csname @onlypreamble\endcsname\relax
430 \else
431   \@onlypreamble\pdfcryptsetup
432 \fi

```

## 2.6 support of configuration file

```
433 \begingroup\expandafter\expandafter\expandafter\endgroup
434 \expandafter\ifx\csname InputIfFileExists\endcsname\relax
435   \@PackageInfo{pdfcrypt}{%
436     Configuration file pdfcrypt.cfg not supported.%
437   }%
438 \else
439   \let\pc@ExecuteOptions\ExecuteOptions
440   \InputIfFileExists{pdfcrypt.cfg}{-}{-}%
441   \let\ExecuteOptions\pc@ExecuteOptions
442 \fi
```

## 2.7 Package options

Plain format does not know package options.

```
443 \begingroup\expandafter\expandafter\expandafter\endgroup
444 \expandafter\ifx\csname @classoptionslist\endcsname\relax
445   \expandafter\pc@endinput
446 \fi
```

Process global and local options.

```
447 \def\pc@ProcessOptionsWithKV{%
448   \let\pc@temp\@empty
449   \@for\CurrentOption:=\@classoptionslist\do{%
450     \ifundefined{KV\pc@\CurrentOption}{-}{%
451       \edef\pc@temp{\pc@temp,\CurrentOption,%
452         \@expandtwoargs\@removeelement\CurrentOption
453         \@unusedoptionlist\@unusedoptionlist
454       }%
455     }%
456     \edef\pc@temp{%
457       \noexpand\pdfcryptsetup{%
458         \pc@temp\@optionlist{\@currname.\@current}%
459       }%
460     }%
461     \pc@temp
462 }
463 \pc@ProcessOptionsWithKV
464 \AtEndOfPackage{\let\@unprocessedoptions\relax}
465 \AtBeginDocument{\pc@set}
466
467 \pc@endinput
468 \</package>
```

# 3 Installation

## 3.1 Download

**Package.** This package is available on CTAN<sup>2</sup>:

[CTAN:macros/latex/contrib/oberdiek/pdfcrypt.dtx](http://ctan.org/ctan/ctan/macros/latex/contrib/oberdiek/pdfcrypt.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcrypt.pdf](http://ctan.org/ctan/ctan/macros/latex/contrib/oberdiek/pdfcrypt.pdf) Documentation.

---

<sup>2</sup>[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for  $\TeX$  Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

## 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

## 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain  $\TeX$ :

```
tex pdfcrypt.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfcrypt.sty → tex/generic/oberdiek/pdfcrypt.sty
pdfcrypt.pdf → doc/latex/oberdiek/pdfcrypt.pdf
pdfcrypt.dtx → source/latex/oberdiek/pdfcrypt.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 3.4 Refresh file name databases

If your  $\TeX$  distribution (`te $\TeX$` , `mik $\TeX$` , ...) relies on file name databases, you must refresh these. For example, `te $\TeX$`  users run `texhash` or `mktextlsr`.

## 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk pdfcrypt.pdf unpack_files output .
```

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The .dtx chooses its action depending on the format:

**plain T<sub>E</sub>X:** Run docstrip and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for docstrip (really, docstrip does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcrypt.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex pdfcrypt.dtx
makeindex -s gind.ist pdfcrypt.idx
pdflatex pdfcrypt.dtx
makeindex -s gind.ist pdfcrypt.idx
pdflatex pdfcrypt.dtx
```

## 4 Catalogue

The following XML file can be used as source for the [T<sub>E</sub>X Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `pdfcrypt.xml`.

```
469 (*catalogue)
470 <?xml version='1.0' encoding='us-ascii'?>
471 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
472 <entry datestamp='$Date$' modifier='$Author$' id='pdfcrypt'>
473   <name>pdfcrypt</name>
474   <caption>Allows the setting of pdf encryption.</caption>
475   <authorref id='auth:oberdiek'>/>
476   <copyright owner='Heiko Oberdiek' year='2001,2006,2007'>/>
477   <license type='lppl1.3'>/>
478   <version number='1.0'>/>
479   <description>
480     Allows the setting of pdf encryption options for VTeX and some
481     older versions of pdfTeX. The options can be set as package
482     options or in the command <tt>\pdfcryptsetup</tt>. Options
483     include <tt>owner=OwnerPassword</tt>, <tt>user=UserPassword,
484     print</tt>, <tt>copy</tt>, <tt>edit</tt>, <tt>annotate=true,
485     false all, none</tt>. The encryption is set at
486     <tt>\begin{document}</tt> by default, but this can be forced for
487     an earlier time by option &#x2018;set&#x2019;.
488   <p/>
489   Example:
490   <tt>\usepackage[owner=Donald,user=Knuth,print=false]{pdfcrypt}</tt>
491   <p/>
492   The package is part of the <xref refid='oberdiek'>oberdiek</xref> bundle.
493 </description>
```

```

494 <documentation details='Package documentation'
495     href='ctan:/macros/latex/contrib/oberdiek/pdfcrypt.pdf'/>
496 <ctan file='true' path='/macros/latex/contrib/oberdiek/pdfcrypt.dtx'/>
497 <miktex location='oberdiek'/>
498 <texlive location='oberdiek'/>
499 <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'/>
500 </entry>
501 </catalogue>

```

## 5 History

### [2001/04/02 v0.1]

- First public version, published in the pdftex mailing list for testing with pdfcrypt-20010331

### [2001/07/19 v0.2]

- Default: all allowed.
- Support for V<sub>T</sub>E<sub>X</sub> added.

### [2001/07/19 v0.3]

- Bug fix: V<sub>T</sub>E<sub>X</sub> letter for edit is M (modify).

### [2001/07/19 v0.4]

- Bug fix: `\VTeXversion` is correct after regenerating the format file.

### [2001/08/05 v0.5]

- Syntax change in pdf<sub>T</sub>E<sub>X</sub> 1.00a.

### [2001/08/09 v0.6]

- Support of special characters:  
input: `\{, \}, \` for `{, }, \`  
output: " in V<sub>T</sub>E<sub>X</sub>
- Option debug added.

### [2001/10/28 v0.7]

- Plain compatibility.
- `\nopdfcrypt` added.
- Typos corrected.

### [2006/02/20 v0.8]

- Obsolete remarks for pdf<sub>T</sub>E<sub>X</sub>.
- DTX framework.
- LPPL 1.3

[2007/04/11 v0.9]

- Line ends sanitized.

[2007/04/26 v1.0]

- Use of package infwarerr.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\"</code> .....	215, 216
<code>\#</code> .....	323, 325
<code>\%</code> .....	325
<code>\:</code> .....	46, 47, 48, 49
<code>\@</code> .....	3, 6
<code>\@PackageError</code> ....	100, 118, 249, 252
<code>\@PackageInfo</code> .....	218, 435
<code>\@PackageWarning</code> .....	358, 421
<code>\@PackageWarningNoLine</code> .....	82, 87
<code>\@ReturnAfterFi</code> .....	305, 310, 338
<code>\@classoptionslist</code> .....	449
<code>\@currentx</code> .....	458
<code>\@currname</code> .....	458
<code>\@dblarg</code> .....	196, 344
<code>\@ehc</code> .....	250, 253
<code>\@empty</code> .....	75, 92, 206, 207, 220, 226, 248, 347, 448
<code>\@expandtwoargs</code> .....	452
<code>\@firstoftwo</code> .....	9, 19
<code>\@for</code> .....	449
<code>\@gobble</code> .....	71, 80
<code>\@ifnch</code> .....	31, 33, 49
<code>\@ifnextchar</code> .....	27, 55, 196
<code>\@ifundefined</code> .....	17, 26, 53, 70, 74, 79, 95, 99, 114, 117, 131, 135, 144, 148, 157, 165, 173, 181, 195, 247, 450
<code>\@let@token</code> .....	31, 34, 37, 49
<code>\@makeoother</code> .....	132, 216
<code>\@namedef</code> .....	145
<code>\@nameuse</code> .....	149, 256
<code>\@nil</code> .....	298, 300, 306, 333, 339
<code>\@onlypreamble</code> .....	431
<code>\@optionlist</code> .....	458
<code>\@removeelement</code> .....	452
<code>\@secondoftwo</code> .....	13, 21
<code>\@sptoken</code> .....	34, 46
<code>\@undefined</code> .....	153
<code>\@unprocessedoptions</code> .....	464
<code>\@unusedoptionlist</code> .....	453
<code>\@xdblarg</code> .....	196, 197
<code>\@xifnch</code> .....	35, 48
<code>\\</code> .....	302, 316, 335
<code>\\</code> .....	315, 321
<code>\_</code> .....	314
A	
<code>\AtBeginDocument</code> .....	465
<code>\AtEndOfPackage</code> .....	464
B	
<code>\begin</code> .....	486
C	
<code>\catcode</code> ..	3, 6, 132, 215, 314, 315, 316
<code>\csname</code> .....	2, 8, 12, 16, 18, 64, 145, 149, 189, 365, 429, 434, 444
<code>\CurrentOption</code> ....	449, 450, 451, 452
D	
<code>\DeclareOption</code> .....	164, 166, 168
<code>\define@key</code> .....	371, 374, 377, 380, 383, 386, 389, 392, 398, 405, 408, 411
<code>\do</code> .....	449
E	
<code>\endcsname</code> .....	2, 8, 12, 16, 18, 64, 145, 149, 189, 365, 429, 434, 444
<code>\endinput</code> .....	4
<code>\ExecuteOptions</code> .....	172, 174, 176, 439, 441
F	
<code>\futurelet</code> .....	31, 49
G	
<code>\g@addto@macro</code> .....	136, 159, 167, 175, 183
<code>\gdef</code> .....	49, 109, 126, 314, 420
I	
<code>\ifcase</code> .....	97
<code>\ifnum</code> .....	116, 117, 261
<code>\ifpc@annotate</code> .....	204, 236, 274, 284, 294
<code>\ifpc@copy</code> ...	202, 234, 272, 282, 292
<code>\ifpc@debug</code> .....	205, 219



<code>\ifpc@edit</code> . . .	203, 235, 273, 283, 293	<code>\pc@ProvidesPackage</code> . . . . .	55, 56, 58
<code>\ifpc@nopdfcrypt</code> . . . . .	85, 239, 245	<code>\pc@set</code> . . . . .	217, 418, 419, 465
<code>\ifpc@print</code> . . .	201, 233, 271, 281, 291	<code>\pc@set@pdftex</code> . . . . .	260
<code>\ifpc@set</code> . . . . .	200, 417	<code>\pc@set@pdftexnew</code> . . . . .	264, 277
<code>\ifx</code> . . . . .	8, 12, 16, 18, 34, 37, 64, 86, 189, 220, 226, 248, 302, 335, 347, 350, 352, 357, 429, 434, 444	<code>\pc@set@pdftexold</code> . . . . .	262, 267
<code>\immediate</code> . . . . .	59, 288	<code>\pc@set@vtex</code> . . . . .	287
<code>\input</code> . . . . .	65, 190	<code>\pc@spaceother</code> . . . . .	314, 337
<code>\InputIfFileExists</code> . . . . .	440	<code>\pc@SpaceToOther</code> . . . . .	333, 339
<b>L</b>		<code>\pc@temp</code> . . . . .	215, 311, 346, 347, 348, 350, 352, 354, 357, 365, 448, 451, 456, 458, 461
<code>\lowercase</code> . . . . .	346	<code>\pc@true</code> . . . . .	348, 350, 368
<b>M</b>		<code>\pc@user</code> 207, 226, 229, 270, 280, 290, 409	
<code>\MessageBreak</code> . . . . .		<code>\pc@Org@DeclareOption</code> . . . . .	164, 168
. . . . .	103, 225, 231, 237, 360, 422	<code>\pc@Org@ExecuteOptions</code> . . . . .	172, 176
<b>N</b>		<code>\pc@Org@NeedsTeXFormat</code> . . . . .	156, 160
<code>\NeedsTeXFormat</code> . . . . .	156, 158, 160	<code>\pc@Org@ProcessOptions</code> . . . . .	180, 184
<code>\newif</code> .	85, 200, 201, 202, 203, 204, 205	<code>\pdfcrypt</code> . . . . .	268, 278
<code>\nopdfcrypt</code> . . . . .	86, 88, 240	<code>\pdfcryptsetup</code> . . . . .	
<b>O</b>		. . . . .	80, 415, 420, 431, 457, 482
<code>\OpMode</code> . . . . .	116	<code>\pdfoutput</code> . . . . .	97
<b>P</b>		<code>\pdftexversion</code> . . . . .	261
<code>\pc@@boolkey</code> . . . . .	344, 345	<code>\ProcessOptions</code> . . . . .	180, 182, 184
<code>\pc@@MakeVTeXString</code> . . .	298, 300, 306	<code>\ProvidesPackage</code> . . . . .	54, 77
<code>\pc@annotatetrue</code> . . . . .	213	<b>R</b>	
<code>\pc@boolkey</code> . . . . .	344, 372, 381, 384, 387, 390, 393, 394, 395, 396, 399, 400, 401, 402, 412	<code>\RequirePackage</code> . . . . .	67, 192
<code>\pc@copytrue</code> . . . . .	211	<code>\reserved@a</code> . . . . .	29, 38
<code>\pc@DefString</code> . . . . .	406, 409	<code>\reserved@b</code> . . . . .	30, 40
<code>\pc@driver</code> . . . . .	92, 109, 126, 242, 247, 248, 253, 256, 375, 378	<code>\reserved@c</code> . . . . .	35, 38, 40, 43
<code>\pc@edittrue</code> . . . . .	212	<code>\reserved@d</code> . . . . .	28, 37
<code>\pc@endinput</code> . . .	83, 107, 124, 445, 467	<b>S</b>	
<code>\pc@ExecuteOptions</code> . . . . .	439, 441	<code>\setkeys</code> . . . . .	416
<code>\pc@false</code> . . . . .	352, 369	<code>\space</code> . . . . .	88
<code>\pc@KeyvalRestore</code> . . . . .		<code>\special</code> . . . . .	288
. . . . .	152, 153, 159, 167, 175, 183, 194	<b>T</b>	
<code>\pc@MakeVTeXString</code> . . . .	289, 290, 297	<code>\the</code> . . . . .	3, 139, 215
<code>\pc@nopdfcrypttrue</code> . . . . .	90	<code>\toks@</code> . . . . .	138, 139
<code>\pc@owner</code> . . . . .		<b>U</b>	
. . . . .	206, 220, 223, 269, 279, 289, 406	<code>\usepackage</code> . . . . .	490
<code>\pc@printtrue</code> . . . . .	210	<b>V</b>	
<code>\pc@ProcessOptionsWithKV</code> . . .	447, 463	<code>\VTeXversion</code> . . . . .	117
		<b>W</b>	
		<code>\write</code> . . . . .	59