

The `pdfescape` package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2007/09/09 v1.6

Abstract

This package implements pdfTEX's escape features (`\pdfescapehex`, `\pdfunescapehex`, `\pdfescapename`, `\pdfescapestring`) using TeX or ε -TeX.

Contents

1 Documentation	2
1.1 Additional unescape macros	2
1.2 Sanitizing macro	2
2 Implementation	3
2.1 Reload check and package identification	3
2.2 Catcodes	4
2.3 Sanitizing	4
2.3.1 Space characters	5
2.3.2 Space normalization	5
2.4 \EdefUnescapeName	5
2.5 \EdefUnescapeString	7
2.6 User macros (pdfTEX analogues)	10
2.7 Help macros	11
2.7.1 Characters	11
2.7.2 Switch for ε -TeX	11
2.8 Conversions	11
2.8.1 Conversion to hex string	11
2.8.2 Character code to octal number	12
2.8.3 Unpack hex string	13
2.8.4 Conversion to PDF name	14
2.8.5 Conversion to PDF string	15
3 Test	15
3.1 Catcode checks for loading	15
3.2 Macro tests	16
3.3 Test with \pdfescape... commands	16
3.4 Test without \pdfescape..., with ε -TeX	16
3.5 Test without \pdfescape... and ε -TeX	16
3.6 Check/ensure test preconditions	17
3.6.1 Check \pdfescape...	17
3.6.2 Check ε -TeX	17
3.7 Common part	17
4 Installation	23
4.1 Download	23
4.2 Bundle installation	23
4.3 Package installation	24
4.4 Refresh file name databases	24
4.5 Some details for the interested	24

5 History	25
[2007/02/21 v1.0]	25
[2007/02/25 v1.1]	25
[2007/03/20 v1.2]	25
[2007/04/11 v1.3]	25
[2007/04/21 v1.4]	25
[2007/08/27 v1.5]	25
[2007/09/09 v1.6]	25
6 Index	25

1 Documentation

```
\EdefEscapeHex {\⟨cmd⟩} {\⟨string⟩}
\EdefUnescapeHex {\⟨cmd⟩} {\⟨string⟩}
\EdefEscapeName {\⟨cmd⟩} {\⟨string⟩}
\EdefEscapeString {\⟨cmd⟩} {\⟨string⟩}
```

These commands converts *⟨string⟩* and stores the result in macro *⟨cmd⟩*. The conversion result is the same as the conversion of the corresponding pdftEX’s primitives. Note that the argument *⟨string⟩* is expanded before the conversion.

For example, if pdftEX >= 1.30 is present, then \EdefEscapeHex becomes to:

```
\def\EdefEscapeHex#1#2{%
  \edef#1{\pdfescapehex{#2}}%
}
```

The package provides implementations for the case that pdftEX is not present (or too old). Even ε-TEx can be missing, however it is used if it is detected.

Babel. The input strings may contain shorthand characters of package babel.

1.1 Additional unescape macros

```
\EdefUnescapeName {\⟨cmd⟩} {\⟨string⟩}
```

Sequences of a hash sign with two hexadecimal digits are converted to the corresponding character (PDF-1.2). A hash sign that is not followed by two hexadecimal digits is left unchanged. The catcodes in the result string follow TeX’s conventions. The space has catcode 10 (space) and the other characters have catcode 12 (other).

```
\EdefUnescapeString {\⟨cmd⟩} {\⟨string⟩}
```

Macro *⟨cmd⟩* stores the unescaped string in *⟨string⟩*. All the rules for literal strings are implemented, see PDF specification. The catcodes in the result string follow TeX’s conventions.

1.2 Sanitizing macro

```
\EdefSanitize {\⟨cmd⟩} {\⟨string⟩}
```

Argument *⟨string⟩* is expanded, converted to a string of tokens with catcode 12 (other) and space tokens, and stored in macro *⟨cmd⟩*.

2 Implementation

1 `<*package>`

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3   \catcode44 12 % ,
4   \catcode45 12 % -
5   \catcode46 12 % .
6   \catcode58 12 % :
7   \catcode64 11 % @
8   \expandafter\let\expandafter\x\csname ver@pdfescape.sty\endcsname
9   \ifcase 0%
10     \ifx\x\relax % plain
11     \else
12       \ifx\x\empty % LaTeX
13       \else
14         %
15       \fi
16     \fi
17   \else
18     \expandafter\ifx\x\csname PackageInfo\endcsname\relax
19       \def\x#1#2{%
20         \immediate\write-1{Package #1 Info: #2.}%
21       }%
22     \else
23       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24     \fi
25     \x{pdfescape}{The package is already loaded}%
26   \endgroup
27   \expandafter\endinput
28 \fi
29 \endgroup
```

Package identification:

```
30 \begingroup
31   \catcode40 12 % (
32   \catcode41 12 % )
33   \catcode44 12 % ,
34   \catcode45 12 % -
35   \catcode46 12 % .
36   \catcode47 12 % /
37   \catcode58 12 % :
38   \catcode64 11 % @
39   \expandafter\ifx\x\csname ProvidesPackage\endcsname\relax
40     \def\x#1#2#3[#4]{\endgroup
41       \immediate\write-1{Package: #3 #4}%
42       \xdef#1[#4]%
43     }%
44   \else
45     \def\x#1#2[#3]{\endgroup
46       #2[#3]%
47       \ifx#1\relax
48         \xdef#1[#3]%
49       \fi
50     }%
51   \fi
52 \expandafter\x\csname ver@pdfescape.sty\endcsname
53 \ProvidesPackage{pdfescape}%
54 [2007/09/09 v1.6 Provides hex, PDF name and string conversions (HO)]
```

2.2 Catcodes

```
55 \expandafter\edef\csname PE@AtEnd\endcsname{%
56   \catcode64 \the\catcode64\relax
57 }
58 \catcode64 11 % @
59 \def\TMP@EnsureCode#1#2#3{%
60   \edef\PE@AtEnd{%
61     \PE@AtEnd
62     #1#2 \the#1#2\relax
63   }%
64   #1#2 #3\relax
65 }
66 \TMP@EnsureCode\catcode{0}{12}%
67 \TMP@EnsureCode\catcode{34}{12}%
68 \TMP@EnsureCode\catcode{39}{12}%
69 \TMP@EnsureCode\catcode{42}{12}%
70 \TMP@EnsureCode\catcode{45}{12}%
71 \TMP@EnsureCode\catcode{46}{12}%
72 \TMP@EnsureCode\catcode{60}{12}%
73 \TMP@EnsureCode\catcode{61}{12}%
74 \TMP@EnsureCode\catcode{62}{12}%
75 \TMP@EnsureCode\catcode{94}{7}%
76 \TMP@EnsureCode\catcode{96}{12}%
77 \TMP@EnsureCode\uccode{34}{0}%
78 \TMP@EnsureCode\uccode{48}{0}%
79 \TMP@EnsureCode\uccode{61}{0}%
=
```

2.3 Sanitizing

- \EdefSanitize Macro \EdefSanitize takes #2, entirely converts it to token with catcode 12 (other) and stores the result in macro #1.

```
80 \begingroup\expandafter\expandafter\expandafter\endgroup
81 \expandafter\ifx\csname detokenize\endcsname\relax
82   \long\def\EdefSanitize#1#2{%
83     \begingroup
84       \csname @safe@activestrue\endcsname
85       \edef#1{\#2}%
86       \PE@onelevel@sanitize#1%
87     \expandafter\endgroup
88     \expandafter\def\expandafter#1\expandafter{\#1}%
89   }%
90 \begingroup\expandafter\expandafter\expandafter\endgroup
91 \expandafter\ifx\csname @onelevel@sanitize\endcsname\relax
92   \def\PE@onelevel@sanitize#1{%
93     \edef#1{\expandafter\PE@strip@prefix\meaning#1}%
94   }%
95   \def\PE@strip@prefix#1{}%
96 \else
97   \let\PE@onelevel@sanitize\@onelevel@sanitize
98 \fi
99 \else
100 \long\def\EdefSanitize#1#2{%
101   \begingroup
102     \csname @safe@activestrue\endcsname
103     \edef#1{\#2}%
104     \PE@onelevel@sanitize#1%
105   \expandafter\endgroup
106   \expandafter\def\expandafter#1\expandafter{\#1}%
107 }%
108 \def\PE@onelevel@sanitize#1{%
109   \edef#1{\detokenize\expandafter{\#1}}%
110 }%
```

```

111 \fi

\PE@sanitize Macro \PE@sanitize is only defined for compatibility with version 1.4. Its use is
112 \let\PE@sanitize\EdefSanitize

```

2.3.1 Space characters

```

\PE@space@other
113 \begingroup
114   \catcode`\ =12\relax%
115 \def\x{\endgroup\def\PE@space@other{ }}\x\relax

\PE@space@space
116 \def\PE@space@space{ }

```

2.3.2 Space normalization

```

\PE@SanitizeSpaceOther
117 \def\PE@SanitizeSpaceOther#1{%
118   \edef#1{\expandafter\PE@SpaceToOther#1 \relax}%
119 }

\PE@SpaceToOther
120 \def\PE@SpaceToOther#1 #2\relax{%
121   #1%
122   \ifx\\#2\\%
123   \else
124     \PE@space@other
125     \c@ReturnAfterFi{%
126       \PE@SpaceToOther#2\relax
127     }%
128   \fi
129 }

\c@ReturnAfterFi
130 \long\def\c@ReturnAfterFi#1\fi{\fi#1}

```

2.4 \EdefUnescapeName

```

\EdefUnescapeName
131 \def\EdefUnescapeName#1#2{%
132   \EdefSanitize#1{#2}%
133   \PE@SanitizeSpaceOther#1%
134   \PE@UnescapeName#1%
135   \PE@onelvel@sanitize#1%
136 }

\PE@UnescapeName
137 \begingroup
138   \catcode`\$=6 % hash
139   \catcode`\#=12 % other
140   \gdef\PE@UnescapeName$1{%
141     \begingroup
142       \PE@InitUccodeHexDigit
143       \def\PE@result{}%
144       \expandafter\PE@DeName$1#\relax\relax
145     \expandafter\endgroup
146     \expandafter\def\expandafter$1\expandafter{\PE@result}%
147   }%

```

```

148 \gdef\PE@DeName$1##2$3{%
149   \ifx\relax$2%
150     \edef\PE@result{\PE@result$1}%
151     \let\PE@next\relax
152   \else
153     \ifx\relax$3%
154       % wrong escape sequence in input
155       \edef\PE@result{\PE@result$1}%
156       \let\PE@next\relax
157   \else
158     \uppercase{%
159       \def\PE@testA{$2}%
160       \def\PE@testB{$3}%
161     }%
162     \ifcase\ifcase\expandafter\PE@TestUcHexDigit\PE@testA
163       \ifcase\expandafter\PE@TestUcHexDigit\PE@testB
164         \z@
165       \else
166         \cne
167       \fi
168     \else
169       \one
170     \fi
171     \uccode\z@=\PE@testA\PE@testB\relax
172     \uppercase{%
173       \def\PE@temp{``@}%
174     }%
175     \uccode\z@=\z@
176     \edef\PE@result{\PE@result$1\PE@temp}%
177     \let\PE@next\PE@DeName
178   \else
179     % wrong escape sequence in input
180     \edef\PE@result{\PE@result$1}%
181     \def\PE@next{\PE@DeName$2$3}%
182   \fi
183   \fi
184 \fi
185 \PE@next
186 }%
187 \endgroup

\P@InitUccodeHexDigit
188 \def\PE@InitUccodeHexDigit{%
189   \uccode'a='A\relax
190   \uccode'b='B\relax
191   \uccode'c='C\relax
192   \uccode'd='D\relax
193   \uccode'e='E\relax
194   \uccode'f='F\relax
195   \uccode'A=\z@
196   \uccode'B=\z@
197   \uccode'C=\z@
198   \uccode'D=\z@
199   \uccode'E=\z@
200   \uccode'F=\z@
201   \uccode'0=\z@
202   \uccode'1=\z@
203   \uccode'2=\z@
204   \uccode'3=\z@
205   \uccode'4=\z@
206   \uccode'5=\z@
207   \uccode'6=\z@
208   \uccode'7=\z@

```

```

209  \uccode`8=\z@%
210  \uccode`9=\z@%
211 }

\PETestUcHexDigit
212 \def\PETestUcHexDigit#1{%
213   \ifnum`#1<48 % 0
214     \cne
215   \else
216     \ifnum`#1>70 % F
217       \cne
218     \else
219       \ifnum`#1>57 % 9
220         \ifnum`#1<65 % A
221           \cne
222         \else
223           \z@
224         \fi
225       \else
226         \z@
227       \fi
228     \fi
229   \fi
230 }

```

2.5 \EdefUnescapeString

```

\EdefUnescapeString
231 \def\EdefUnescapeString#1#2{%
232   \EdefSanitize#1{#2}%
233   \PESanitizeSpaceOther#1%
234   \PENormalizeLineEnd#1%
235   \PEUnescapeString#1%
236   \PEonelinelevel@sanitize#1%
237 }

238 \begingroup
239   \uccode`\8=10 % lf
240   \uccode`\9=13 % cr
241 \def\x#1#2{\endgroup

\PENormalizeLineEnd
242 \def\PENormalizeLineEnd##1{%
243   \def\PE@result{}%
244   \expandafter\PE@NormalizeLineEnd##1#2\relax
245   \let##1\PE@result
246 }%

\PE@NormalizeLineEnd
247 \def\PE@NormalizeLineEnd##1##2##2{%
248   \ifx\relax##2%
249     \edef\PE@result{\PE@result##1}%
250     \let\PE@next\relax
251   \else
252     \edef\PE@result{\PE@result##1}%
253     \ifx##1##2% lf
254       \let\PE@next\PE@NormalizeLineEnd
255     \else
256       \def\PE@next{\PE@NormalizeLineEnd##2}%
257     \fi
258   \fi
259   \PE@next

```

```

260   }%
261 }%
262 \uppercase{%
263   \x 89%
264 }

265 \begingroup
266   \catcode`|=0 %
267   \catcode`\|=12 %

\PE@UnescapeString

268 |gdef|PE@UnescapeString#1{%
269   |begingroup
270     |def|PE@result{}%
271     |expandafter|PE@DeString#1\|relax
272   |expandafter|endgroup
273   |expandafter|def|expandafter#1|expandafter{|PE@result}%
274 }%

\PE@DeString

275 |gdef|PE@DeString#1\#2{%
276   |ifx|relax#2%
277     |edef|PE@result{|PE@result#1}%
278     |let|PE@next|relax
279   |else
280     |if n#2%
281       |uccode|z@=10 %
282     |else|if r#2%
283       |uccode|z@=13 %
284     |else|if t#2%
285       |uccode|z@=9 %
286     |else|if b#2%
287       |uccode|z@=8 %
288     |else|if f#2%
289       |uccode|z@=12 %
290   |else
291     |uccode|z@=|z@
292   |fi|fi|fi|fi
293   |ifnum|uccode|z@>|z@
294     |uppercase{%
295       |edef|PE@temp{^^@}%
296     }%
297     |edef|PE@result{|PE@result#1|PE@temp}%
298     |let|PE@next|PE@DeString
299   |else
300     |if\#2% backslash
301       |edef|PE@result{|PE@result#1}%
302       |let|PE@next|PE@CheckEndBackslash
303     |else
304       |ifnum`#2=10 % linefeed
305         |edef|PE@result{|PE@result#1}%
306         |let|PE@next|PE@DeString
307     |else
308       |ifcase|PE@TestOctDigit#2%
309         |edef|PE@result{|PE@result#1}%
310         |def|PE@next{|PE@OctI#2}%
311       |else
312         |edef|PE@result{|PE@result#1#2}%
313         |let|PE@next|PE@DeString
314       |fi
315       |fi
316       |fi

```

```

317      |fi
318      |fi
319      |PE@next
320  }%
321
\PE@CheckEndBackslash
321  |gdef|PE@CheckEndBackslash#1{%
322    |ifx|relax#1%
323    |else
324      |edef|PE@result{|PE@result\}%
325      |expandafter|PE@DeString|expandafter#1%
326    |fi
327  }%
328 |endgroup
329
\PE@TestOctDigit
329 \def\PE@TestOctDigit#1{%
330   \ifnum`#1<48 % 0
331     \@ne
332   \else
333     \ifnum`#1>55 % 7
334       \@ne
335     \else
336       \z@
337     \fi
338   \fi
339 }
340
\PE@OctI
340 \def\PE@OctI#1#2{%
341   \ifcase\PE@TestOctDigit#2%
342     \def\PE@next{\PE@OctII{#1#2}}%
343   \else
344     \def\PE@next{\PE@OctAll#1#2}%
345   \fi
346   \PE@next
347 }
348
\PE@OctII
348 \def\PE@OctII#1#2{%
349   \ifcase\PE@TestOctDigit#2%
350     \def\PE@next{\PE@OctAll{#1#2}}%
351   \else
352     \def\PE@next{\PE@OctAll{#1}#2}%
353   \fi
354   \PE@next
355 }
356
\PE@OctAll
356 \def\PE@OctAll#1{%
357   \uccode`\z@='#1\relax
358   \uppercase{%
359     \edef\PE@result{\PE@result^{^{\z@}}\}%
360   }%
361   \PE@DeString
362 }

```

2.6 User macros (pdfTeX analogues)

```
363 \begingroup\expandafter\expandafter\expandafter\endgroup
364 \expandafter\ifx\csname pdfescapehex\endcsname\relax

\edefEscapeHex
365 \long\def\EdefEscapeHex#1#2{%
366   \EdefSanitize#1{#2}%
367   \PE@SanitizeSpaceOther#1%
368   \PE@EscapeHex#1%
369 }%

\edefUnescapeHex
370 \def\EdefUnescapeHex#1#2{%
371   \EdefSanitize#1{#2}%
372   \PE@UnescapeHex#1%
373 }%

\edefEscapeName
374 \long\def\EdefEscapeName#1#2{%
375   \EdefSanitize#1{#2}%
376   \PE@SanitizeSpaceOther#1%
377   \PE@EscapeName#1%
378 }%

\edefEscapeString
379 \long\def\EdefEscapeString#1#2{%
380   \EdefSanitize#1{#2}%
381   \PE@SanitizeSpaceOther#1%
382   \PE@EscapeString#1%
383 }%

384 \else
\PE@edefbabel Help macro that adds support for babel's shorthand characters.
385 \long\def\PE@edefbabel#1#2#3{%
386   \begin{group}
387     \csname @save@activestru\endcsname
388     \edef#1{#2{#3}}%
389   \expandafter\endgroup
390   \expandafter\def\expandafter#1\expandafter{\#1}%
391 }%

\edefEscapeHex
392 \long\def\EdefEscapeHex#1#2{%
393   \PE@edefbabel#1\pdfescapehex{#2}%
394 }%

\edefUnescapeHex
395 \def\EdefUnescapeHex#1#2{%
396   \PE@edefbabel#1\pdfunescapehex{#2}%
397 }%

\edefEscapeName
398 \long\def\EdefEscapeName#1#2{%
399   \PE@edefbabel#1\pdfescapename{#2}%
400 }%

\edefEscapeString
401 \long\def\EdefEscapeString#1#2{%
402   \PE@edefbabel#1\pdfescapestring{#2}%
403 }%
```

```

404   \PE@AtEnd
405   \expandafter\endinput
406 \fi

```

2.7 Help macros

2.7.1 Characters

Special characters with catcode 12 (other) are created and stored in macros.

```
\PE@hash
407 \edef\PE@hash{\string#}
```

```
\PE@backslash
```

```

408 \begingroup
409   \escapechar=-1 %
410 \edef\x{\endgroup
411   \def\noexpand\PE@backslash{\string\\}%
412 }
413 \x

```

2.7.2 Switch for ε -**TEX**

```

414 \newif\ifPE@etex
415 \begingroup\expandafter\expandafter\expandafter\endgroup
416 \expandafter\ifx\csname numexpr\endcsname\relax
417 \else
418   \PE@etexttrue
419 \fi

```

2.8 Conversions

2.8.1 Conversion to hex string

```
\PE@EscapeHex
```

```

420 \ifPE@etex
421   \def\PE@EscapeHex#1{%
422     \edef#1{\expandafter\PE@ToHex#1\relax}%
423   }%
424 \else
425   \def\PE@EscapeHex#1{%
426     \def\PE@result{}%
427     \expandafter\PE@ToHex#1\relax
428     \let#1\PE@result
429   }%
430 \fi

```

```
\PE@ToHex
```

```

431 \def\PE@ToHex#1{%
432   \ifx\relax#1%
433   \else
434     \PE@HexChar{#1}%
435     \expandafter\PE@ToHex
436   \fi
437 }%

```

```
\PE@HexChar
```

```

438 \ifPE@etex
439   \def\PE@HexChar#1{%
440     \PE@HexDigit{\numexpr\dimexpr.0625\dimexpr`#1sp\relax\relax\relax}%
441     \PE@HexDigit{%
442       \numexpr`#1-16*\dimexpr.0625\dimexpr`#1sp\relax\relax\relax

```

```

443      }%
444  }%
445 \else
446   \def\PE@HexChar#1{%
447     \dimen0='#1sp%
448     \dimen2=.0625\dimen0 %
449     \advance\dimen0-16\dimen2 %
450     \edef\PE@result{%
451       \PE@result
452       \PE@HexDigit{\dimen2 }%
453       \PE@HexDigit{\dimen0 }%
454     }%
455   }%
456 \fi

\PE@HexDigit

457 \def\PE@HexDigit#1{%
458   \expandafter\string
459   \ifcase#1%
460     0\or 1\or 2\or 3\or 4\or 5\or 6\or 7\or 8\or 9\or
461     A\or B\or C\or D\or E\or F%
462   \fi
463 }

```

2.8.2 Character code to octal number

```

\PE@OctChar

464 \ifPE@etex
465   \def\PE@OctChar#1{%
466     \expandafter\PE@@OctChar
467     \the\numexpr\dimexpr.015625\dimexpr`#1sp\relax\relax
468     \expandafter\relax
469     \expandafter\relax
470     \the\numexpr\dimexpr.125\dimexpr`#1sp\relax\relax\relax
471     \relax
472     #1%
473   }%
474   \def\PE@@OctChar#1\relax#2\relax#3{%
475     \PE@backslash
476     #1%
477     \the\numexpr#2-8*#1\relax
478     \the\numexpr\dimexpr`#3sp\relax-8*#2\relax
479   }%
480 \else
481   \def\PE@OctChar#1{%
482     \dimen0='#1sp%
483     \dimen2=.125\dimen0 %
484     \dimen4=.125\dimen2 %
485     \advance\dimen0-8\dimen2 %
486     \advance\dimen2-8\dimen4 %
487     \edef\PE@result{%
488       \PE@result
489       \PE@backslash
490       \number\dimen4 %
491       \number\dimen2 %
492       \number\dimen0 %
493     }%
494   }%
495 \fi

```

2.8.3 Unpack hex string

```

\PE@UnescapeHex
496 \def\PE@UnescapeHex#1{%
497   \begingroup
498     \PE@InitUccodeHexDigit
499     \def\PE@result{}%
500     \expandafter\PE@DeHex#1\relax\relax
501   \expandafter\endgroup
502   \expandafter\def\expandafter#1\expandafter{\PE@result}%
503 }

\PE@DeHex
504 \def\PE@DeHex#1#2{%
505   \ifx#2\relax
506     \ifx#1\relax
507       \let\PE@next\relax
508     \else
509       \uppercase{%
510         \def\PE@testA{#1}%
511       }%
512       \ifcase\expandafter\PE@TestUcHexDigit\PE@testA
513         \def\PE@next{%
514           \PE@DeHex#10\relax\relax
515         }%
516       \else
517         \let\PE@next\relax
518       \fi
519     \fi
520   \else
521     \uppercase{%
522       \def\PE@testA{#1}%
523       \def\PE@testB{#2}%
524     }%
525     \ifcase\expandafter\PE@TestUcHexDigit\PE@testA
526       \ifcase\expandafter\PE@TestUcHexDigit\PE@testB
527         \uccode`z@="\PE@testA\PE@testB\relax
528         \ifnum\uccode`z@=32 %
529           \let\PE@temp\PE@space@space
530         \else
531           \uppercase{%
532             \def\PE@temp{^^0}%
533           }%
534         \fi
535         \edef\PE@result{\PE@result\PE@temp}%
536         \let\PE@next\PE@DeHex
537       \else
538         % invalid input sequence
539         \def\PE@next{%
540           \PE@DeHex#1%
541         }%
542       \fi
543     \else
544       % invalid input sequence
545       \def\PE@next{\PE@DeHex#2}%
546     \fi
547   \fi
548   \PE@next
549 }

```

2.8.4 Conversion to PDF name

```

\PE@EscapeName
 550 \ifPE@etex
 551   \def\PE@EscapeName#1{%
 552     \edef#1{\expandafter\PE@EscapeNameTokens#1\relax}%
 553   }%
 554 \else
 555   \def\PE@EscapeName#1{%
 556     \def\PE@result{}%
 557     \expandafter\PE@EscapeNameTokens#1\relax
 558     \let#1\PE@result
 559   }%
 560 \fi

\PE@EscapeNameTokens
 561 \def\PE@EscapeNameTokens#1{%
 562   \ifx\relax#1%
 563   \else
 564     \ifnum`#1<33 %
 565       \ifcase`#1 %
 566         % drop illegal zero
 567       \else
 568         \PE@EscapeNameAdd\PE@hash
 569         \PE@HexChar#1%
 570       \fi
 571     \else
 572       \ifnum`#1>126 %
 573         \PE@EscapeNameAdd\PE@hash
 574         \PE@HexChar#1%
 575       \else \ifnum`#1=35 \PE@EscapeNameHashChar 23% #
 576         \else\ifnum`#1=37 \PE@EscapeNameHashChar 25% %
 577         \else\ifnum`#1=40 \PE@EscapeNameHashChar 28% (
 578         \else\ifnum`#1=41 \PE@EscapeNameHashChar 29% )
 579         \else\ifnum`#1=47 \PE@EscapeNameHashChar 2F% /
 580         \else\ifnum`#1=60 \PE@EscapeNameHashChar 3C% <
 581         \else\ifnum`#1=62 \PE@EscapeNameHashChar 3E% >
 582         \else\ifnum`#1=91 \PE@EscapeNameHashChar 5B% [
 583         \else\ifnum`#1=93 \PE@EscapeNameHashChar 5D% ]
 584         \else\ifnum`#1=123 \PE@EscapeNameHashChar 7B% {
 585         \else\ifnum`#1=125 \PE@EscapeNameHashChar 7D% }
 586       \else
 587         \PE@EscapeNameAdd{#1}%
 588       \fi\fi\fi\fi\fi\fi\fi\fi
 589     \fi
 590   \fi
 591   \expandafter\PE@EscapeNameTokens
 592 \fi
 593 }%
 594 \def\PE@EscapeNameHashChar#1#2{%
 595   \PE@EscapeNameAdd{\PE@hash\string#1\string#2}%
 596 }%

\PE@EscapeNameAdd
 597 \ifPE@etex
 598   \def\PE@EscapeNameAdd#1{#1}%
 599 \else
 600   \def\PE@EscapeNameAdd#1{%
 601     \edef\PE@result{%
 602       \PE@result
 603       #1%
 604     }%

```

```

605  }%
606 \fi

607 \ifPE@etex
608   \def\PE@EscapeString#1{%
609     \edef#1{\expandafter\PE@EscapeStringTokens#1\relax}%
610   }%
611 \else
612   \def\PE@EscapeString#1{%
613     \begingroup
614       \def\PE@result{}%
615       \expandafter\PE@EscapeStringTokens#1\relax
616     \expandafter\endgroup
617     \expandafter\def\expandafter#1\expandafter{\PE@result}%
618   }%
619 \fi

```

```

\PE@EscapeStringTokens
620 \def\PE@EscapeStringTokens#1{%
621   \ifx\relax#1%
622   \else
623     \ifnum`#1<33 %
624       \PE@OctChar#1%
625     \else
626       \ifnum`#1>126 %
627         \PE@OctChar#1%
628       \else \ifnum`#1=40 \PE@EscapeStringAdd{\string\()%
629         \else\ifnum`#1=41 \PE@EscapeStringAdd{\string())}%
630         \else\ifnum`#1=92 \PE@EscapeStringAdd{\string\\}%
631         \else
632           \PE@EscapeStringAdd{#1}%
633         \fi\fi\fi
634       \fi
635     \fi
636     \expandafter\PE@EscapeStringTokens
637   \fi
638 }%

```

```

\PE@EscapeStringAdd
639 \ifPE@etex
640   \def\PE@EscapeStringAdd#1{#1}%
641 \else
642   \def\PE@EscapeStringAdd#1{%
643     \edef\PE@result{%
644       \PE@result
645       #1%
646     }%
647   }%
648 \fi

649 \PE@AtEnd
650 
```

3 Test

3.1 Catcode checks for loading

```

651 <*test1>

```

```

652 \catcode`\@=11 %
653 \def\RestoreCatcodes{}
654 \count@=0 %
655 \loop
656   \edef\RestoreCatcodes{%
657     \RestoreCatcodes
658     \catcode\the\count@=\the\catcode\count@\relax
659   }%
660 \ifnum\count@<255 %
661   \advance\count@\@ne
662 \repeat
663
664 \def\RangeCatcodeInvalid#1#2{%
665   \count@=#1\relax
666   \loop
667     \catcode\count@=15 %
668   \ifnum\count@<#2\relax
669     \advance\count@\@ne
670   \repeat
671 }
672 \def\Test{%
673   \RangeCatcodeInvalid{0}{47}%
674   \RangeCatcodeInvalid{58}{64}%
675   \RangeCatcodeInvalid{91}{96}%
676   \RangeCatcodeInvalid{123}{255}%
677   \catcode`\@=12 %
678   \catcode`\\=0 %
679   \catcode`\{=1 %
680   \catcode`\}=2 %
681   \catcode`\#=6 %
682   \catcode`\[=12 %
683   \catcode`\]=12 %
684   \catcode`\%=14 %
685   \catcode`\ =10 %
686   \catcode13=5 %
687   \input pdfescape.sty\relax
688   \RestoreCatcodes
689 }
690 \Test
691 \csname @@end\endcsname
692 \end
693 </test1>

```

3.2 Macro tests

```

694 <*test2 | test3 | test4>
695 \NeedsTeXFormat{LaTeX2e}
696 \makeatletter

```

3.3 Test with \pdfescape... commands

```

697 <*test2>
698 \ProvidesFile{pdfescape-test1.tex}%
699   [2007/09/09 v1.6 Test with \string\pdfescape... commands]%
700 </test2>

```

3.4 Test without \pdfescape..., with ε - \TeX

```

701 <*test3>
702 \ProvidesFile{pdfescape-test2.tex}%
703   [2007/09/09 v1.6 Test without \string\pdfescape..., with  $\varepsilon$ - $\text{\TeX}$ ]%
704 </test3>

```

3.5 Test without \pdfescape... and ε - \TeX

```

705 <*test4>
706 \ProvidesFile{pdfescape-test3.tex}%
707   [2007/09/09 v1.6 Test without \string\pdfescape... and e-TeX]%
708 </test4>

```

3.6 Check/ensure test preconditions

3.6.1 Check \pdfescape...

```

709 <*test2>
710 \@ifundefined{pdfescapehex}{%
711   \PackageError{pdfescape-test1}{%
712     Missing \string\pdfescape... commands%
713   }{Test aborted.}%
714   \stop
715 }{%
716 </test2>
717 <*test3 | test4>
718 \let\pdfescapehex\@undefined
719 \let\pdfunescapehex\@undefined
720 \let\pdfescapename\@undefined
721 \let\pdfescapestring\@undefined
722 </test3 | test4>

```

3.6.2 Check ε -TeX

```

723 <*test3>
724 \@ifundefined{numexpr}{%
725   \PackageError{pdfescape-test2}{%
726     Missing \eTeX
727   }{Test aborted.}%
728   \stop
729 }{%
730 </test3>

```

Package `qstest` uses ε -TeX, thus ε -TeX's features can only be disabled later during loading of package `pdfescape`.

3.7 Common part

The files for testing uses the framework, provided by the new package `qstest` of David Kastrup.

```

731 \RequirePackage{qstest}
732 \IncludeTests{*}
733 \LogTests{log}{*}{*}
734
735 \newcommand*\ExpectVar}[2]{%
736   \ifx#1#2%
737   \else
738     \begingroup
739       \onelevel@sanitize#1%
740       \onelevel@sanitize#2%
741       \typeout{[#1] <> [#2]}% hash-ok
742     \endgroup
743   \fi
744   \Expect*{\ifx#1#2true\else false\fi}{true}%
745 }
746
747 \makeatletter
748 \begingroup
749   \gdef\AllBytes{}%
750   \count@=0 %
751   \catcode0=12 %
752   \whilenum\count@<256 \do{%
753     \lccode0=\count@

```

```

754     \ifnum\count@=32 %
755         \xdef\AllBytes{\AllBytes\space}%
756     \else
757         \lowercase{%
758             \xdef\AllBytes{\AllBytes^{^{\count@}}}%}
759         }%
760     \fi
761     \advance\count@ by 1 %
762 }
763 \endgroup
764 \newcommand*{\AllBytesHex}{%
765     000102030405060708090A0B0C0D0E0F%
766     101112131415161718191A1B1C1D1E1F%
767     202122232425262728292A2B2C2D2E2F%
768     303132333435363738393A3B3C3D3E3F%
769     404142434445464748494A4B4C4D4E4F%
770     505152535455565758595A5B5C5D5E5F%
771     606162636465666768696A6B6C6D6E6F%
772     707172737475767778797A7B7C7D7E7F%
773     808182838485868788898A8B8C8D8E8F%
774     909192939495969798999A9B9C9D9E9F%
775     A0A1A2A3A4A5A6A7A8A9AAABACADAEAF%
776     B0B1B2B3B4B5B6B7B8B9BABBBCBDBEBF%
777     C0C1C2C3C4C5C6C7C8C9CACBCCCDCCECF%
778     D0D1D2D3D4D5D6D7D8D9DADBDCCDDDEF%
779     E0E1E2E3E4E5E6E7E8E9EAEBCEDEEEF%
780     F0F1F2F3F4F5F6F7F8F9FAFBFCFDFF%
781 }
782 \onelevel@sanitize\AllBytesHex
783 \expandafter\lowercase\expandafter{%
784     \expandafter\newcommand\expandafter*\expandafter\expandafter\AllBytesHexLC
785         \expandafter{\AllBytesHex}%
786 }
787 \newcommand*{\AllBytesName}{}
788 \begingroup
789     \catcode`\#=12 %
790     \xdef\AllBytesName{%
791         #01#02#03#04#05#06#07#08#09#0A#0B#0C#0D#0E#0F%
792         #10#11#12#13#14#15#16#17#18#19#1A#1B#1C#1D#1E#1F%
793         #20!"#23$#25&'#28#29**,-.#2F%
794         0123456789:;#3C=#3E?%
795         @ABCDEFGHIJKLMNO%
796         PQRSTUVWXYZ#5B\@backslashchar#5D^_%
797         'abcdefghijklmn%`%
798         pqrstuvwxyz#7B|#7D\string~#7F%
799         #80#81#82#83#84#85#86#87#88#89#8A#8B#8C#8D#8E#8F%
800         #90#91#92#93#94#95#96#97#98#99#9A#9B#9C#9D#9E#9F%
801         #A0#A1#A2#A3#A4#A5#A6#A7#A8#A9#AA#AB#AC#AD#AE#AF%
802         #B0#B1#B2#B3#B4#B5#B6#B7#B8#B9#BA#BB#BC#BD#BE#BF%
803         #C0#C1#C2#C3#C4#C5#C6#C7#C8#C9#CA#CB#CC#CD#CE#CF%
804         #D0#D1#D2#D3#D4#D5#D6#D7#D8#D9#DA#DB#DC#DD#DE#DF%
805         #E0#E1#E2#E3#E4#E5#E6#E7#E8#E9#EA#EB#EC#ED#EE#EF%
806         #F0#F1#F2#F3#F4#F5#F6#F7#F8#F9#FA#FB#FC#FD#FE#FF%
807     }%
808 \endgroup
809 \onelevel@sanitize\AllBytesName
810
811 \newcommand*{\AllBytesString}{}
812 \begingroup
813     \def\\{|}%
814     \edef\%{\@percentchar}%
815     \catcode`\|=0 %

```

```

816  \catcode`\#=12 %
817  \catcode`\~=12 %
818  \catcode`\|=12 %
819  \xdef\AllBytesString{%
820    \000\001\002\003\004\005\006\007\010\011\012\013\014\015\016\017%
821    \020\021\022\023\024\025\026\027\030\031\032\033\034\035\036\037%
822    \040!"#$!%&`(\()**+,-./%
823    0123456789:;=>?%
824    @ABCDEFGHIJKLMNO%
825    PQRSTUVWXYZ[\ ]^_%
826    'abcdefghijklmn%
827    pqrstuvwxyz{|}~\177%
828    \200\201\202\203\204\205\206\207\210\211\212\213\214\215\216\217%
829    \220\221\222\223\224\225\226\227\230\231\232\233\234\235\236\237%
830    \240\241\242\243\244\245\246\247\250\251\252\253\254\255\256\257%
831    \260\261\262\263\264\265\266\267\270\271\272\273\274\275\276\277%
832    \300\301\302\303\304\305\306\307\310\311\312\313\314\315\316\317%
833    \320\321\322\323\324\325\326\327\330\331\332\333\334\335\336\337%
834    \340\341\342\343\344\345\346\347\350\351\352\353\354\355\356\357%
835    \360\361\362\363\364\365\366\367\370\371\372\373\374\375\376\377%
836  }%
837 }%
838 \onelevel@sanitize\AllBytesString
839
840 {*test4}
841 \let\org@detokenize\detokenize
842 \let\detokenize@\undefined
843 \let\org@numexpr\numexpr
844 \let\numexpr@\undefined
845 
846 \RequirePackage{pdfescape}
847 {*test4}
848 \let\detokenize\org@detokenize
849 \let\numexpr\org@numexpr
850 
851
852 \begin{qstest}{all-hex}{\AllBytes, escapehex}
853   \EdefEscapeHex\x{\AllBytes}%
854   \Expect*\{x\}*\{\AllBytesHex}%
855   \ExpectVar\x\AllBytesHex
856 \end{qstest}
857
858 \begin{qstest}{all-unhex}{\AllBytesHex, unescapehex}
859   \EdefUnescapeHex\x{\AllBytesHex}%
860   \Expect*\{x\}*\{\AllBytes\}%
861   \ExpectVar\x\AllBytes
862 \end{qstest}
863
864 \begin{qstest}{all-unhex-lc}{\AllBytesHexLC, unescapehex, lowercase}
865   \EdefUnescapeHex\x{\AllBytesHexLC}%
866   \Expect*\{x\}*\{\AllBytes\}%
867   \ExpectVar\x\AllBytes
868 \end{qstest}
869
870 \begin{qstest}{unhex-incomplete}{unescapehex, incomplete}
871   \EdefUnescapeHex\x{4}%
872   \Expect*\{x\}{@}%
873 \end{qstest}
874
875 \begin{qstest}{unhex-space}{unescapehex, space}
876   \EdefUnescapeHex\x{20}%
877   \Expect*\{x\}{ }%

```

```

878  \ExpectVar\x\space
879 \end{qstest}
880
881 \begin{qstest}{unhex-spaces}{unescapehex, spaces}
882  \EdefUnescapeHex\x{204020204120}%
883  \def\y#1{%
884    \edef\z{\#1\string @#1#1\string A#1}%
885  }\y{ }%
886 \Expect*\{\x\}*\{\z\}%
887 \ExpectVar\x\z
888 \end{qstest}
889
890 \begin{qstest}{unhex-hash}{unescapehex, hash}
891  \catcode`\#=12 %
892  \EdefUnescapeHex\x{\#20}%
893  \ExpectVar\x\space
894 \end{qstest}
895
896 \begin{qstest}{unhex-invalid}{unescapehex, invalid}
897  \def\test#1#2{%
898    \EdefUnescapeHex\x{\#1}%
899    \edef\y{\#2}%
900    \onelevel@sanitize\y
901    \ExpectVar\x\y
902  }%
903 <*test2>
904  \edef\x{\pdfunescapehex{4X}}%
905  \edef\y{\string 0}%
906  \ifx\x\y
907  \else
908    \def~{\space}%
909    \typeout{*****}%
910    \typeout{* Your pdfTeX contains bug 777. ~~~*}%
911    \typeout{* This test is redefined as dummy, *}%
912    \typeout{* because it triggers the bug. ~~~*}%
913    \typeout{*****}%
914  \def\test#1#2{j}%
915  \fi
916 </test2>
917  \test{X}{}%
918  \test{XY}{}%
919  \test{XYZ}{}%
920  \test{A}{^a0}%
921  \test{AX}{^a0}%
922  \test{XA}{^a0}%
923  \test{XXAXX}{^a0}%
924 \end{qstest}
925
926 \begin{qstest}{all-name}{\AllBytes, escapename}
927  \EdefEscapeName\x{\AllBytes}%
928  \Expect*\{\x\}*\{\AllBytesName\}%
929  \ExpectVar\x\AllBytesName
930 \end{qstest}
931
932 \begin{qstest}{all-string}{\AllBytes, escapestring}
933  \EdefEscapeString\x{\AllBytes}%
934  \Expect*\{\x\}*\{\AllBytesString\}%
935  \ExpectVar\x\AllBytesString
936 \end{qstest}
937
938 \begin{qstest}{uchexdigit}{unescape, uppercase hex digit}
939  \catcode`\@=11 %

```

```

940 \catcode0=12 %
941 \def\test#1#2{%
942     \uccode0=#1\relax
943     \uppercase{%
944         \def\x{^~@}%
945     }%
946     \Expect*{%
947         \ifcase\expandafter\PE@TestUcHexDigit\x
948             true%
949         \else
950             false%
951         \fi
952     }{#2}%
953 }%
954 \def\range#1#2#3{%
955     \count0=#1\relax
956     \loop
957         \ifnum\count0<#2\relax
958             \test{\count0}{#3}%
959             \advance\count0 by 1 %
960         \repeat
961 }%
962 \range{0}{47}{false}%
963 \range{48}{57}{true}%
964 \range{58}{64}{false}%
965 \range{65}{70}{true}%
966 \range{71}{255}{false}%
967 \end{qstest}
968
969 \begin{qstest}{unescapename}{unescapename}
970 \def\test#1#2{%
971     \EdefUnescapeName\x{#1}%
972     \edef\y{#2}%
973     \Onelevel@sanitize\y
974     \ExpectVar\x\y
975 }%
976 \catcode`#=12 %
977 \catcode0=12 %
978 \test{}{ }%
979 \test{x}{x}%
980 \test{xy}{xy}%
981 \test{#}{#}%
982 \test{##}{##}%
983 \test{###}{###}%
984 \test{####}{####}%
985 \test{#x}{#x}%
986 \test{#xy}{#xy}%
987 \test{#1}{#1}%
988 \test{#40}{@}%
989 \test{#400}{@0}%
990 \test{#4x0}{#4x0}%
991 \test{#ab}{^~ab}%
992 \test{#00}{^~@}%
993 \test{x#40y#40z}{x@y@z}%
994 \test{#40#40#40#40}{@cccc}%
995 \test{a#x}{a#x}%
996 \test{a#xy}{a#xy}%
997 \test{a#1}{a#1}%
998 \test{a#40}{a@}%
999 \test{a#400}{a@0}%
1000 \test{#20}{ }%
1001 \test{a#20}{a }%

```

```

1002  \test{a#20b}{a b}%
1003  \test{a#20#20b}{a \space\space b}%
1004 \end{qstest}
1005
1006 \begin{qstest}{unescapestring}{unescapestring}
1007  \def\test#1#2{%
1008    \EdefUnescapeString\x{\#1}%
1009    \edef\y{\#2}%
1010    \onelevel@sanitize\y
1011    \ExpectVar\x\y
1012  }%
1013  \catcode0=12 %
1014  \def\DefChar#1#2{%
1015    \begingroup
1016      \uccode0=#2\relax
1017      \uppercase{\endgroup
1018        \def#1{^\@}%
1019      }%
1020  }%
1021  \DefChar\nul{0}%
1022  \DefChar\one{1}%
1023  \DefChar\bel{8}%
1024  \DefChar\tab{9}%
1025  \DefChar\lf{10}%
1026  \DefChar\ff{12}%
1027  \DefChar\cr{13}%
1028  \DefChar\\{92}%
1029  \test{}{ }%
1030  \test{a}{a}%
1031  \test{{}}{{}}%
1032  \test{{}}{{}}%
1033  \test{{y}}{{y}}%
1034  \test{{000}}{{nul}}%
1035  \test{{b}}{{bel}}%
1036  \test{{t}}{{tab}}%
1037  \test{{n}}{{lf}}%
1038  \test{{f}}{{ff}}%
1039  \test{{r}}{{cr}}%
1040  \test{{()}}{{}}%
1041  \test{{()}}{{}}%
1042  \test{{040}}{{ }}%
1043  \test{{100}}{{@}}%
1044  \test{{40}}{{ }}%
1045  \test{{1}}{{one}}%
1046  \test{{01}}{{one}}%
1047  \test{{001}}{{one}}%
1048  \test{{18}}{{one8}}%
1049  \test{{018}}{{one8}}%
1050  \test{{0018}}{{one8}}%
1051  \test{x{{x}}}%
1052  \test{x{{}}}{x}%
1053  \test{x{{}}}{x{{y}}}%
1054  \test{x{{000}}}{x{nul}}%
1055  \test{x{{b}}}{x{bel}}%
1056  \test{x{{t}}}{x{tab}}%
1057  \test{x{{n}}}{x{lf}}%
1058  \test{x{{f}}}{x{ff}}%
1059  \test{x{{r}}}{x{cr}}%
1060  \test{x{{()}}}{x{{()}}}%
1061  \test{x{{()}}}{x{{()}}}%
1062  \test{x{{040}}}{x{{ }}}%
1063  \test{x{{100}}}{x{{@}}}%

```

```

1064  \test{x\\40}{x }%
1065  \test{x\\1}{x\one}%
1066  \test{x\\01}{x\one}%
1067  \test{x\\001}{x\one}%
1068  \test{x\\18}{x\one8}%
1069  \test{x\\018}{x\one8}%
1070  \test{x\\0018}{x\one8}%
1071  \test{\b\t\n\f\r\\(\\\\000\\040}{%
1072    \bel\tab\lf\ff\cr()\nul\space
1073 }%
1074  \test{\lf}{}
1075  \test{x\\lf}{x}%
1076  \test{cr}{lf}%
1077  \test{cr\lf}{lf}%
1078  \test{lf}{lf}%
1079  \test{lf\cr}{lf\lf}%
1080  \test{x\cr}{x\lf}%
1081  \test{x\cr\lf}{x\lf}%
1082  \test{x\lf}{x\lf}%
1083  \test{x\lf\cr}{x\lf\lf}%
1084  \test{x\\cr\lf y\cr}{xy\lf}%
1085 \end{qstest}
1086 \stop
1087 </test2 | test3 | test4>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/pdfescape.dtx The source file.

CTAN:macros/latex/contrib/oberdiek/pdfescape.pdf Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip

TDS refers to the standard “A Directory Structure for TeX Files” (CTAN:tds.tds.pdf). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek-tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-`TeX`:

```
tex pdfescape.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
pdfescape.sty      → tex/generic/oberdiek/pdfescape.sty  
pdfescape.pdf     → doc/latex/oberdiek/pdfescape.pdf  
pdfescape-test1.tex → doc/latex/oberdiek/pdfescape-test1.tex  
pdfescape-test2.tex → doc/latex/oberdiek/pdfescape-test2.tex  
pdfescape-test3.tex → doc/latex/oberdiek/pdfescape-test3.tex  
pdfescape-test4.tex → doc/latex/oberdiek/pdfescape-test4.tex  
pdfescape.dtx      → source/latex/oberdiek/pdfescape.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TeX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk pdfescape.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-`TeX`: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=\input{pdfescape.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex pdfescape.dtx  
makeindex -s gind.ist pdfescape.idx  
pdflatex pdfescape.dtx  
makeindex -s gind.ist pdfescape.idx  
pdflatex pdfescape.dtx
```

5 History

[2007/02/21 v1.0]

- First version.

[2007/02/25 v1.1]

- Test files added.
- `\EdefUnescapeHex` supports lowercase letters.
- Fix: `\EdefEscapeName{^^@}`
- Fix: `\EdefEscapeName{\string#}`
- Fix for `\EdefUnescapeHex` in case of incomplete hex string.
- Fix: `\EdefUnescapeHex` generates space tokens with catcode 10 (space) in all cases.
- Fix: `\EdefEscapeHex` and `\EdefEscapeName` now generate tokens with catcode 12 (other) only.

[2007/03/20 v1.2]

- Fix: Wrong year in `\ProvidesPackage`.

[2007/04/11 v1.3]

- Line ends sanitized.

[2007/04/21 v1.4]

- `\EdefUnescapeName` and `\EdefUnescapeString` added.

[2007/08/27 v1.5]

- `\EdefSanitize` added (replaces `\PE@sanitize`).

[2007/09/09 v1.6]

- Fix in catcode setup.

6 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\#</code>	139, 275, 300, 681, 789, 816, 891, 976
<code>\\$</code> 138
<code>\%</code>	684, 814
<code>\(</code>	628, 822
<code>\)</code>	629, 822
<code>\@</code>	652, 677, 939
<code>\@ReturnAfterFi</code>	125, <u>130</u>
<code>\@backslashchar</code>	796
<code>\@undefined</code>	710, 724
<code>\@ne</code>	166, 169,
	214, 217, 221, 331, 334, 661, 669
	<code>\@onelevel@sanitize</code> 97, 739,
	740, 782, 809, 838, 900, 973, 1010
	<code>\@percentchar</code> 814
	<code>\@undefined</code> 718, 719, 720, 721, 842, 844
	<code>\@whilenum</code> 752
	<code>\[</code> 682
	<code>\\\</code> 122, 267, 411, 630, 678, 818, 825,
	1028, 1031, 1032, 1033, 1034,
	1035, 1036, 1037, 1038, 1039,
	1040, 1041, 1042, 1043, 1044,

	E
\EdefEscapeHex	2, 365, 392, 853
\EdefEscapeName	374, 398, 927
\EdefEscapeString	379, 401, 933
\EdefSanitize	2, 80, 112, 132, 232, 366, 371, 375, 380
\EdefUnescapeHex	370, 395, 859, 865, 871, 876, 882, 892, 898
\EdefUnescapeName	2, 131, 971
\EdefUnescapeString	2, 231, 1008
\empty	12
\end	692, 856, 862, 868, 873, 879, 888, 894, 924, 930, 936, 967, 1004, 1085
\endcsname	8, 18, 39, 52, 55, 81, 84, 91, 102, 364, 387, 416, 691
\endinput	27, 405
\escapechar	409
\eTeX	726
\Expect	744, 854, 860, 866, 872, 877, 886, 928, 934, 946
\ExpectVar	735, 855, 861, 867, 878, 887, 893, 901, 929, 935, 974, 1011
	F
\ff	1026, 1038, 1058, 1072
	G
\gdef	140, 148, 749
	I
\ifcase	9, 162, 163, 341, 349, 459, 512, 525, 526, 565, 947
\ifnum	213, 216, 219, 220, 330, 333, 528, 564, 572, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 623, 626, 628, 629, 630, 660, 668, 754, 957
\ifPE@etex	414, 420, 438, 464, 550, 597, 607, 639
\ifx	10, 12, 18, 39, 47, 81, 91, 122, 149, 153, 248, 253, 364, 416, 432, 505, 506, 562, 621, 736, 744, 906
\immediate	20, 41
\IncludeTests	732
\input	687
	L
\lccode	753
\lf	1025, 1037, 1057, 1072, 1074, 1075, 1076, 1077, 1078, 1079, 1080, 1081, 1082, 1083, 1084
\LogTests	733
\loop	655, 666, 956
\lowercase	757, 783
	M
\makeatletter	696, 747
\meaning	93
	N
\NeedsTeXFormat	695
\newcommand	735, 764, 784, 787, 811
\newif	414
\nul	1021, 1034, 1054, 1072

\number 490, 491, 492
 \numexpr 440, 442,
 467, 470, 477, 478, 843, 844, 849

O

\one 1022, 1045,
 1046, 1047, 1048, 1049, 1050,
 1065, 1066, 1067, 1068, 1069, 1070
 \org@detokenize 841, 848
 \org@numexpr 843, 849

P

\PackageError 711, 725
 \PackageInfo 23
 \pdfescape 699, 703, 707, 712
 \pdfescapehex 393, 718
 \pdfescapename 399, 720
 \pdfescapestring 402, 721
 \pdfunescapehex 396, 719, 904
 \PE@@NormalizeLineEnd 244, 247
 \PE@@OctChar 466, 474
 \PE@AtEnd 60, 61, 404, 649
 \PE@backslash 408, 475, 489
 \PE@CheckEndBackslash 321
 \PE@DeHex 500, 504
 \PE@DeName 144, 148, 177, 181
 \PE@DeString 275, 361
 \PE@edefbabel . 385, 393, 396, 399, 402
 \PE@EscapeHex 368, 420
 \PE@EscapeName 377, 550
 \PE@EscapeNameAdd
 568, 573, 587, 595, 597
 \PE@EscapeNameHashChar
 575, 576, 577, 578, 579,
 580, 581, 582, 583, 584, 585, 594
 \PE@EscapeNameTokens .. 552, 557, 561
 \PE@EscapeString 382, 607
 \PE@EscapeStringAdd
 628, 629, 630, 632, 639
 \PE@EscapeStringTokens 609, 615, 620
 \PE@etexttrue 418
 \PE@hash 407, 568, 573, 595
 \PE@HexChar 434, 438, 569, 574
 \PE@HexDigit .. 440, 441, 452, 453, 457
 \PE@InitUccodeHexDigit 142, 188, 498
 \PE@next 151, 156, 177,
 181, 185, 250, 254, 256, 259,
 342, 344, 346, 350, 352, 354,
 507, 513, 517, 536, 539, 545, 548
 \PE@NormalizeLineEnd 234, 242
 \PE@OctAll 344, 350, 352, 356
 \PE@OctChar 464, 624, 627
 \PE@OctI 340
 \PE@OctII 342, 348
 \PE@onelinelevel@sanitize
 86, 92, 97, 104, 108, 135, 236
 \PE@result 143, 146, 150,
 155, 176, 180, 243, 245, 249,
 252, 359, 426, 428, 450, 451,
 487, 488, 499, 502, 535, 556,
 558, 601, 602, 614, 617, 643, 644
 \PE@sanitize 112

\PE@SanitizeSpaceOther
 117, 133, 233, 367, 376, 381
 \PE@space@other 113, 124
 \PE@space@space 116, 529
 \PE@SpaceToOther 118, 120
 \PE@strip@prefix 93, 95
 \PE@temp 173, 176, 529, 532, 535
 \PE@testA 159,
 162, 171, 510, 512, 522, 525, 527
 \PE@testB . 160, 163, 171, 523, 526, 527
 \PE@TestOctDigit 329, 341, 349
 \PE@TestUcHexDigit
 162, 163, 212, 512, 525, 526, 947

\PE@ToHex 422, 427, 431
 \PE@UnescapeHex 372, 496
 \PE@UnescapeName 134, 137
 \PE@UnescapeString 235, 268
 \ProvidesFile 698, 702, 706
 \ProvidesPackage 53

R

\range 954, 962, 963, 964, 965, 966
 \RangeCatcodeInvalid
 664, 673, 674, 675, 676

\repeat 662, 670, 960
 \RequirePackage 731, 846
 \RestoreCatcodes .. 653, 656, 657, 688

S

\space .. 755, 878, 893, 908, 1003, 1072
 \stop 714, 728, 1086

T

\tab 1024, 1036, 1056, 1072
 \Test 672, 690
 \test 897, 914, 917, 918, 919, 920, 921,
 922, 923, 941, 958, 970, 978,
 979, 980, 981, 982, 983, 984,
 985, 986, 987, 988, 989, 990,
 991, 992, 993, 994, 995, 996,
 997, 998, 999, 1000, 1001, 1002,
 1003, 1007, 1029, 1030, 1031,
 1032, 1033, 1034, 1035, 1036,
 1037, 1038, 1039, 1040, 1041,
 1042, 1043, 1044, 1045, 1046,
 1047, 1048, 1049, 1050, 1051,
 1052, 1053, 1054, 1055, 1056,
 1057, 1058, 1059, 1060, 1061,
 1062, 1063, 1064, 1065, 1066,
 1067, 1068, 1069, 1070, 1071,
 1074, 1075, 1076, 1077, 1078,
 1079, 1080, 1081, 1082, 1083, 1084

\the 56, 62, 467, 470, 477, 478, 658
 \TMP@EnsureCode 59, 66, 67, 68, 69,
 70, 71, 72, 73, 74, 75, 76, 77, 78, 79
 \typeout .. 741, 909, 910, 911, 912, 913

U

\uccode 77, 78,
 79, 171, 175, 189, 190, 191, 192,
 193, 194, 195, 196, 197, 198,
 199, 200, 201, 202, 203, 204,

		Y
		887, 892, 893, 898, 901, 904,
		906, 927, 928, 929, 933, 934,
		935, 944, 947, 971, 974, 1008, 1011
	W	
\write 20, 41	\y
		883, 885, 899, 900, 901, 905,
		906, 972, 973, 974, 1009, 1010, 1011
	X	Z
\x 8, 10, 12, 19, 23, 25, 40, 45, 52, 115, 241, 263, 410, 413, 853, 854, 855, 859, 860, 861, 865, 866, 867, 871, 872, 876, 877, 878, 882, 886,	\z
		884, 886, 887
		\z@ ... 164, 171, 175, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 223, 226, 336, 357, 527, 528