

# The `settobox` package

Heiko Oberdiek  
<oberdiek@uni-freiburg.de>

2007/04/11 v1.3

## Abstract

Commands are defined for getting box sizes similar to L<sup>A</sup>T<sub>E</sub>X's `\settowidth` commands.

## Contents

|                   |                                        |          |
|-------------------|----------------------------------------|----------|
| <b>1</b>          | <b>Usage</b>                           | <b>1</b> |
| 1.1               | Get box dimensions                     | 1        |
| 1.2               | Set box dimensions                     | 2        |
| 1.3               | Move box                               | 2        |
| 1.4               | Example                                | 2        |
| 1.4.1             | Short example                          | 2        |
| 1.4.2             | Test file that shows box manipulations | 2        |
| <b>2</b>          | <b>Implementation</b>                  | <b>4</b> |
| <b>3</b>          | <b>Installation</b>                    | <b>6</b> |
| 3.1               | Download                               | 6        |
| 3.2               | Bundle installation                    | 6        |
| 3.3               | Package installation                   | 6        |
| 3.4               | Refresh file name databases            | 7        |
| 3.5               | Some details for the interested        | 7        |
| <b>4</b>          | <b>History</b>                         | <b>7</b> |
| [2000/02/11 v1.0] |                                        | 7        |
| [2000/09/07 v1.1] |                                        | 7        |
| [2006/02/20 v1.2] |                                        | 7        |
| [2007/04/11 v1.3] |                                        | 8        |
| <b>5</b>          | <b>Index</b>                           | <b>8</b> |

## 1 Usage

### 1.1 Get box dimensions

|                                                                                                                       |
|-----------------------------------------------------------------------------------------------------------------------|
| <code>\settoboxwidth{&lt;L<sup>A</sup>T<sub>E</sub>X length&gt;}{&lt;L<sup>A</sup>T<sub>E</sub>X box&gt;}</code>      |
| <code>\settoboxheight{&lt;L<sup>A</sup>T<sub>E</sub>X length&gt;}{&lt;L<sup>A</sup>T<sub>E</sub>X box&gt;}</code>     |
| <code>\settoboxdepth{&lt;L<sup>A</sup>T<sub>E</sub>X length&gt;}{&lt;L<sup>A</sup>T<sub>E</sub>X box&gt;}</code>      |
| <code>\settobxtotalheight{&lt;L<sup>A</sup>T<sub>E</sub>X length&gt;}{&lt;L<sup>A</sup>T<sub>E</sub>X box&gt;}</code> |

A `<LATEX box>` is allocated by `\newsavebox`. It can be filled by `\sbox` or the environment `lrbox`. The commands above extract then the desired lengths.

## 1.2 Set box dimensions

```
\setboxwidth{\langle LATEX box\rangle}{\langle LATEX length expression\rangle}  
\setboxheight{\langle LATEX box\rangle}{\langle LATEX length expression\rangle}  
\setboxdepth{\langle LATEX box\rangle}{\langle LATEX length expression\rangle}
```

These commands allow the manipulation of the box. Package `calc` is supported in the  $\langle L^A T_E X \text{ length expression} \rangle$ . Also the following length are available in this expression:

|                           |                        |
|---------------------------|------------------------|
| <code>\width</code>       | width of the box       |
| <code>\height</code>      | height of the box      |
| <code>\depth</code>       | depth of the box       |
| <code>\totalheight</code> | totalheight of the box |

Note, the base point (point at the left margin of the baseline) always remain constant.

## 1.3 Move box

```
\setboxmoveleft{\langle LATEX box\rangle}{\langle LATEX length expression\rangle}  
\setboxmoveright{\langle LATEX box\rangle}{\langle LATEX length expression\rangle}  
\setboxlower{\langle LATEX box\rangle}{\langle LATEX length expression\rangle}  
\setboxright{\langle LATEX box\rangle}{\langle LATEX length expression\rangle}
```

Note, the box is shifted relative to the base point. The base point is always inside the box, however the width and height of the box change along with the movement.

## 1.4 Example

### 1.4.1 Short example

```
\newsavebox{\mybox}  
\newlength{\mylength}  
\sbox{\mybox}{Hello World}  
\settoboxwidth{\mylength}{\mybox}
```

### 1.4.2 Test file that shows box manipulations

```
1 \example  
2 %<<END  
3 \documentclass{article}  
4  
5 \usepackage{settobox}  
6 \usepackage{calc}  
7  
8 \newsavebox{\mybox}  
9  
10 \setlength{\fboxsep}{0pt}  
11 \setlength{\parindent}{20pt}  
12 \setlength{\parskip}{10pt}  
13 \pagestyle{empty}  
14  
15 % \test{#1}  
16 % The macro is called with commands in #1 that manipulates  
17 % the box \mybox. These commands along with the result of  
18 % the manipulation is shown. Thus the essence of the  
19 % macro is:  
20 %  
21 % a) \sbox{\mybox}{The cracy fox.}
```

```

22 %   b) #1 % manipulates \mybox
23 %   c) Print #1 commands.
24 %   d) Print box with frame
25 %
26 % The implemenation looks more weird:
27 \makeatletter
28 \newcommand*{\test}[1]{%
29   \par
30   \begin{group}
31     \raggedright
32     \edef\x{\detokenize{#1}}%
33     \let\do\@makeoother
34     \dospecials
35     \catcode'\~\active
36     \catcode'\ =10\relax
37     \def~{\}%
38     \noindent
39     \texttt{\scantokens\expandafter{\x}}%
40     \par
41   \end{group}
42   \begin{group}
43     \let~\relax
44     \sbox{\mybox}{The cracy fox.}%
45     #1%
46     A---\fbox{\usebox{\mybox}}---B%
47   \end{group}
48   \par
49 }
50 \makeatother
51
52 \begin{document}
53
54 \test{\setboxwidth{\mybox}{1.25\width}}
55 \test{\setboxheight{\mybox}{0pt}}
56 \test{\setboxheight{\mybox}{2\height}}
57 \test{\setboxdepth{\mybox}{\height}}
58 \test{\setboxmoveleft{\mybox}{5pt}}
59 \test{%
60   \setboxmoveleft{\mybox}{5pt}~%
61   \setboxwidth{\mybox}{\width + 5pt}%
62 }
63 \test{\setboxmoveright{\mybox}{0.5\width}}
64 \test{\setboxlower{\mybox}{\height}}
65 \test{\setboxraise{\mybox}{\depth}}
66 \test{%
67   \setboxmoveright{\mybox}{5pt}~%
68   \setboxwidth{\mybox}{\width + 5pt}~%
69   \setboxheight{\mybox}{\height + 5pt}~%
70   \setboxdepth{\mybox}{\depth + 5pt}%
71 }
72
73 \end{document}
74 %END
75 \end{example}

```

The result:

---

`\setboxwidth {\mybox }{1.25\width }`

A—The cracy fox.—B

`\setboxheight {\mybox }{0pt}`

A—The cracy fox.—B

```
\setboxheight {\mybox }{2\height }
```

A—The cracy fox.—B

```
\setboxdepth {\mybox }{\height }
```

A—The cracy fox.—B

```
\setboxmoveleft {\mybox }{5pt}
```

A—The cracy fox.—B

```
\setboxmoveleft {\mybox }{5pt}
\setboxwidth {\mybox }{\width + 5pt}
```

A—The cracy fox.—B

```
\setboxmoveright {\mybox }{0.5\width }
```

A—The cracy fox.—B

```
\setboxlower {\mybox }{\height }
```

A—The cracy fox.—B

```
\setboxraise {\mybox }{\depth }
```

A—The cracy fox.—B

```
\setboxmoveright {\mybox }{5pt}
\setboxwidth {\mybox }{\width + 5pt}
\setboxheight {\mybox }{\height + 5pt}
\setboxdepth {\mybox }{\depth + 5pt}
```

A—The cracy fox.—B

---

## 2 Implementation

```
76 (*package)
Package identification.
77 \NeedsTeXFormat{LaTeX2e}
78 \ProvidesPackage{settoebox}%
79 [2007/04/11 v1.3 Getting box sizes (HO)]
80 \newcommand*{\settoboxwidth}[2]{\setlength{#1}{\wd#2}}
81 \newcommand*{\settoboxheight}[2]{\setlength{#1}{\ht#2}}
82 \newcommand*{\settoboxdepth}[2]{\setlength{#1}{\dp#2}}
83 \newcommand*{\settoboxtotalheight}[2]{%
84   \setlength{#1}{\ht#2}%
85   \addtolength{#1}{\dp#2}%
86 }

\setboxwidth

87 \newcommand*{\setboxwidth}[2]{%
88   \settobox@length\wd{#1}{#2}%
89 }

\setboxheight
```

```

90 \newcommand*\setboxheight}[2]{%
91   \settobox@length\ht{#1}{#2}%
92 }

\setboxheight

93 \newcommand*\setboxdepth}[2]{%
94   \settobox@length\dp{#1}{#2}%
95 }

\setboxmoveleft

96 \newcommand*\setboxmoveleft}[2]{%
97   \settobox@horiz{-}{#1}{#2}%
98 }

\setboxmoveright

99 \newcommand*\setboxmoveright}[2]{%
100   \settobox@horiz{}{#1}{#2}%
101 }

\setboxlower

102 \newcommand*\setboxlower}[2]{%
103   \settobox@vert\lower{#1}{#2}%
104 }

\setboxraise

105 \newcommand*\setboxraise}[2]{%
106   \settobox@vert\raise{#1}{#2}%
107 }

\settobox@length The work for the \setbox... commands is done by \settobox@length. Inside
the length expression \width, \height, \depth, \totalheight are set to the
dimensions of the box.
#1: the property of the box that is to be changed (\wd, \ht, \dp)
#2: the box
#3: length expression

108 \def\settobox@length#1#2#3{%
109   \settobox@calc{#2}{#3}{#1#2=##1sp\relax}%
110 }

\settobox@horiz

111 \def\settobox@horiz#1#2#3{%
112   \settobox@calc{#2}{#3}{\setbox#2=\hbox{\kern#1##1sp\copy#2}}%
113 }

\settobox@vert

114 \def\settobox@vert#1#2#3{%
115   \settobox@calc{#2}{#3}{\setbox#2=\hbox{#1##1sp\copy#2}}%
116 }

\settobox@calc

117 \def\settobox@calc#1#2#3{%
118   \begingroup
119     \def\width{\wd#1}%
120     \def\height{\ht#1}%
121     \def\depth{\dp#1}%
122     \dimen@ \ht#1\relax
123     \advance\dimen@ \dp#1\relax
124     \def\totalheight{\dimen@}%
125     \setlength{\dimen@}{#2}%
126     \count@ \dimen@

```

```

127     \def\x##1{\endgroup
128         #3%
129     }%
130     \expandafter\x\expandafter{\the\count0}%
131 }

132 </package>

```

## 3 Installation

### 3.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/settobox.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/settobox.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

### 3.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

### 3.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T<sub>E</sub>X:

```
tex settobox.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```

settobox.sty      → tex/latex/oberdiek/settobox.sty
settobox.pdf      → doc/latex/oberdiek/settobox.pdf
settobox-example.tex → doc/latex/oberdiek/settobox-example.tex
settobox.dtx      → source/latex/oberdiek/settobox.dtx

```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

---

<sup>1</sup><http://ftp.ctan.org/tex-archive/>

### 3.4 Refresh file name databases

If your  $\text{\TeX}$  distribution ( $\text{te}\text{\TeX}$ ,  $\text{mik}\text{\TeX}$ , ...) relies on file name databases, you must refresh these. For example,  $\text{te}\text{\TeX}$  users run `texhash` or `mktextlsr`.

### 3.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk settobox.pdf unpack_files output .
```

**Unpacking with  $\text{\LaTeX}$ .** The `.dtx` chooses its action depending on the format:

**plain- $\text{\TeX}$ :** Run `docstrip` and extract the files.

**$\text{\LaTeX}$ :** Generate the documentation.

If you insist on using  $\text{\LaTeX}$  for `docstrip` (really, `docstrip` does not need  $\text{\LaTeX}$ ), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{settobox.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with  $\text{pdf}\text{\LaTeX}$ :

```
pdflatex settobox.dtx
makeindex -s gind.ist settobox.idx
pdflatex settobox.dtx
makeindex -s gind.ist settobox.idx
pdflatex settobox.dtx
```

## 4 History

[2000/02/11 v1.0]

- First public release, written as answer in the newsgroup `de.comp.text.tex` in the thread *Die Hoehe von Minipages und Bild*, date: 2000/02/11.

[2000/09/07 v1.1]

- Documentation added.
- CTAN release.

[2006/02/20 v1.2]

- `\setboxwidth`, `\setboxheight`, `\setboxdepth` added.
- Box move commands added.
- DTX framework.
- LPPL 1.3

- Line ends sanitized.

## 5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

| Symbols                            |                                                                                     |                                                         |                                                     |
|------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|-----------------------------------------------------|
| <code>\@makeoother</code> .....    | 33                                                                                  | <code>\newcommand</code> .....                          | 28, 80, 81,<br>82, 83, 87, 90, 93, 96, 99, 102, 105 |
| <code>\\</code> .....              | 37                                                                                  | <code>\newsavebox</code> .....                          | 8                                                   |
| <code>\~</code> .....              | 35                                                                                  | <code>\noindent</code> .....                            | 38                                                  |
| A                                  |                                                                                     | P                                                       |                                                     |
| <code>\_</code> .....              | 36                                                                                  | <code>\pagestyle</code> .....                           | 13                                                  |
| <code>\active</code> .....         | 35                                                                                  | <code>\par</code> .....                                 | 29, 40, 48                                          |
| <code>\addtolength</code> .....    | 85                                                                                  | <code>\parindent</code> .....                           | 11                                                  |
| <code>\advance</code> .....        | 123                                                                                 | <code>\parskip</code> .....                             | 12                                                  |
| B                                  |                                                                                     | <code>\ProvidesPackage</code> .....                     | 78                                                  |
| <code>\begin</code> .....          | 52                                                                                  | R                                                       |                                                     |
| C                                  |                                                                                     | <code>\raggedright</code> .....                         | 31                                                  |
| <code>\catcode</code> .....        | 35, 36                                                                              | <code>\raise</code> .....                               | 106                                                 |
| <code>\copy</code> .....           | 112, 115                                                                            | S                                                       |                                                     |
| <code>\count@</code> .....         | 126, 130                                                                            | <code>\sbox</code> .....                                | 21, 44                                              |
| D                                  |                                                                                     | <code>\scantokens</code> .....                          | 39                                                  |
| <code>\depth</code> .....          | 65, 70, 121                                                                         | <code>\setbox</code> .....                              | 112, 115                                            |
| <code>\detokenize</code> .....     | 32                                                                                  | <code>\setboxdepth</code> .....                         | 2, 57, 70, 93                                       |
| <code>\dimen@</code> .....         | 122, 123, 124, 125, 126                                                             | <code>\setboxheight</code> .....                        | 2, 55, 56, 69, 90, 93                               |
| <code>\do</code> .....             | 33                                                                                  | <code>\setboxlower</code> .....                         | 2, 64, 102                                          |
| <code>\documentclass</code> .....  | 3                                                                                   | <code>\setboxmoveleft</code> .....                      | 2, 58, 60, 96                                       |
| <code>\dospecials</code> .....     | 34                                                                                  | <code>\setboxmoveright</code> .....                     | 2, 63, 67, 99                                       |
| <code>\dp</code> .....             | 82, 85, 94, 121, 123                                                                | <code>\setboxraise</code> .....                         | 65, 105                                             |
| E                                  |                                                                                     | <code>\setboxright</code> .....                         | 2                                                   |
| <code>\end</code> .....            | 73                                                                                  | <code>\setboxwidth</code> .....                         | 2, 54, 61, 68, 87                                   |
| F                                  |                                                                                     | <code>\setlength</code> 10, 11, 12, 80, 81, 82, 84, 125 |                                                     |
| <code>\fbox</code> .....           | 46                                                                                  | <code>\settobox@calc</code> ....                        | 109, 112, 115, 117                                  |
| <code>\fboxsep</code> .....        | 10                                                                                  | <code>\settobox@horiz</code> .....                      | 97, 100, 111                                        |
| H                                  |                                                                                     | <code>\settobox@length</code> ....                      | 88, 91, 94, 108                                     |
| <code>\hbox</code> .....           | 112, 115                                                                            | <code>\settobox@vert</code> .....                       | 103, 106, 114                                       |
| <code>\height</code> .....         | 56, 57, 64, 69, 120                                                                 | <code>\settoboxdepth</code> .....                       | 1, 82                                               |
| <code>\ht</code> .....             | 81, 84, 91, 120, 122                                                                | <code>\settoboxheight</code> .....                      | 1, 81                                               |
| K                                  |                                                                                     | <code>\settoboxtotalheight</code> .....                 | 1, 83                                               |
| <code>\kern</code> .....           | 112                                                                                 | <code>\settoboxwidth</code> .....                       | 1, 80                                               |
| L                                  |                                                                                     | T                                                       |                                                     |
| <code>\lower</code> .....          | 103                                                                                 | <code>\test</code> .....                                | 15, 28,<br>54, 55, 56, 57, 58, 59, 63, 64, 65, 66   |
| M                                  |                                                                                     | <code>\texttt</code> .....                              | 39                                                  |
| <code>\makeatletter</code> .....   | 27                                                                                  | <code>\the</code> .....                                 | 130                                                 |
| <code>\makeatother</code> .....    | 50                                                                                  | <code>\totalheight</code> .....                         | 124                                                 |
| <code>\mybox</code> .....          | 8,<br>17, 21, 22, 44, 46, 54, 55, 56, 57,<br>58, 60, 61, 63, 64, 65, 67, 68, 69, 70 | U                                                       |                                                     |
| N                                  |                                                                                     | <code>\usebox</code> .....                              | 46                                                  |
| <code>\NeedsTeXFormat</code> ..... | 77                                                                                  | <code>\usepackage</code> .....                          | 5, 6                                                |
|                                    |                                                                                     | W                                                       |                                                     |
|                                    |                                                                                     | <code>\wd</code> .....                                  | 80, 88, 119                                         |
|                                    |                                                                                     | <code>\width</code> .....                               | 54, 61, 63, 68, 119                                 |
|                                    |                                                                                     | X                                                       |                                                     |
|                                    |                                                                                     | <code>\x</code> .....                                   | 32, 39, 127, 130                                    |