

The soulutf8 package

Heiko Oberdiek
<oberdiek@uni-freiburg.de>

2007/09/09 v1.0

Abstract

This package extends package `soul` and adds some support for UTF-8. Namely the input encodings `utf8.def` from package `inputenc` and package `ucs`'s `utf8x.def` are supported.

Contents

1	Documentation	2
1.1	Patch	2
1.2	Future	2
2	Implementation	2
2.1	Reload check and package identification	2
2.2	Catcodes	3
2.3	Loading packages	4
2.3.1	plain- \TeX	4
2.3.2	\LaTeX	5
2.3.3	ϵ - \TeX	5
2.4	Macro for redefinitions	5
2.5	Redefinition of <code>\SOUL@eval</code>	6
2.6	UTF-8 analysis	9
2.6.1	Help strings	9
2.6.2	Support for <code>utf8.def</code>	9
2.6.3	Support for <code>utf8x.def</code>	10
2.7	Actions for UTF-8 sequences	10
2.7.1	Redefinition of <code>\SOUL@splittoken</code>	11
2.8	Patches	12
3	Test	14
3.1	Catcode checks for loading	14
3.2	\LaTeX tests	16
3.2.1	Driver definitions	17
3.2.2	Test macros	18
3.2.3	Testing	21
4	Installation	22
4.1	Download	22
4.2	Bundle installation	22
4.3	Package installation	22
4.4	Refresh file name databases	23
4.5	Some details for the interested	23
5	References	24

6 History	24
[2007/09/09 v1.0]	24
7 Index	24

1 Documentation

This package `soulutf8` does not have own options and does not define new user commands. Any option is passed to package `soul` [1] that is loaded first. Then some internal macros of `soul` are redefined to add support for UTF-8. The following input encodings are supported:

```
utf8      LATEX base    TDS:tex/latex/base/utf8.def [3]
utf8x     Package ucs   TDS:tex/latex/ucs/utf8x.def [2]
```

UTF-8 byte sequences are added as token group to a word, even if these UTF-8 characters are some kind of hyphen or space. As exception the following three Unicode characters are handled specially:

Slot	Name	Action
U+00A0	NO-BREAK SPACE	like ~
U+2013	EN DASH	--
U+2014	EM DASH	---

1.1 Patch

Also package `soulutf8` tries to patch package `soul` to improve its behaviour:

- A problem with additional levels of curly braces is fixed. As advantage more implicate kernings are detected. However, the result may be incompatible with the original behaviour of package `soul` because of these respected implicate kernings.
- ε -T_EX, especially `\unexpanded` is supported. This allows a better protection of token groups (`\mbox{...}`, `math, ...`).

1.2 Future

Currently package `soul` does not seem to be maintained. Nevertheless if there will be a new version that adds support for UTF-8, then this package may become obsolete.

2 Implementation

```
1 <*package>
```

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup
3 \catcode44 12 % ,
4 \catcode45 12 % -
5 \catcode46 12 % .
6 \catcode58 12 % :
7 \catcode64 11 % @
8 \catcode123 1 % {
9 \catcode125 2 % }
10 \expandafter\let\expandafter\x\csname ver@soulutf8.sty\endcsname
11 \ifx\x\relax % plain-TEX, first loading
```

```

12 \else
13   \def\empty{}%
14   \ifx\x\empty % LaTeX, first loading,
15     % variable is initialized, but \ProvidesPackage not yet seen
16   \else
17     \catcode35 6 % #
18     \expandafter\ifx\csname PackageInfo\endcsname\relax
19     \def\x#1#2{%
20       \immediate\write-1{Package #1 Info: #2.}%
21     }%
22   \else
23     \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
24   \fi
25   \x{soulutf8}{The package is already loaded}%
26   \aftergroup\endinput
27 \fi
28 \fi
29 \endgroup

```

Package identification:

```

30 \begingroup
31 \catcode35 6 % #
32 \catcode40 12 % (
33 \catcode41 12 % )
34 \catcode44 12 % ,
35 \catcode45 12 % -
36 \catcode46 12 % .
37 \catcode47 12 % /
38 \catcode58 12 % :
39 \catcode64 11 % @
40 \catcode91 12 % [
41 \catcode93 12 % ]
42 \catcode123 1 % {
43 \catcode125 2 % }
44 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
45   \def\x#1#2#3[#4]{\endgroup
46     \immediate\write-1{Package: #3 #4}%
47     \xdef#1{#4}%
48   }%
49 \else
50   \def\x#1#2[#3]{\endgroup
51     #2[#3]}%
52   \ifx#1\@undefined
53     \xdef#1{#3}%
54   \fi
55   \ifx#1\relax
56     \xdef#1{#3}%
57   \fi
58 }%
59 \fi
60 \expandafter\x\csname ver@soulutf8.sty\endcsname
61 \ProvidesPackage{soulutf8}%
62 [2007/09/09 v1.0 Adding support for UTF-8 to soul (HO)]

```

2.2 Catcodes

```

63 \begingroup
64 \catcode123 1 % {
65 \catcode125 2 % }
66 \def\x{\endgroup
67   \expandafter\edef\csname SOuL@AtEnd\endcsname{%
68     \catcode35 \the\catcode35\relax
69     \catcode64 \the\catcode64\relax

```

```

70      \catcode123 \the\catcode123\relax
71      \catcode125 \the\catcode125\relax
72    }%
73  }%
74 \x
75 \catcode35 6 % #
76 \catcode64 11 % @
77 \catcode123 1 % {
78 \catcode125 2 % }
79 \def\TMP@EnsureCode#1#2{%
80   \edef\Soul@AtEnd{%
81     \Soul@AtEnd
82     \catcode#1 \the\catcode#1\relax
83   }%
84   \catcode#1 #2\relax
85 }
86 \TMP@EnsureCode{10}{12}% ^^J
87 \TMP@EnsureCode{33}{12}% !
88 \TMP@EnsureCode{34}{12}% "
89 \TMP@EnsureCode{36}{3}% $
90 \TMP@EnsureCode{39}{12}% '
91 \TMP@EnsureCode{40}{12}% (
92 \TMP@EnsureCode{41}{12}% )
93 \TMP@EnsureCode{42}{12}% *
94 \TMP@EnsureCode{43}{12}% +
95 \TMP@EnsureCode{44}{12}% ,
96 \TMP@EnsureCode{45}{12}% -
97 \TMP@EnsureCode{46}{12}% .
98 \TMP@EnsureCode{47}{12}% /
99 \TMP@EnsureCode{58}{12}% :
100 \TMP@EnsureCode{60}{12}% <
101 \TMP@EnsureCode{61}{12}% =
102 \TMP@EnsureCode{62}{12}% >
103 \TMP@EnsureCode{94}{7}% ^
104 \TMP@EnsureCode{96}{12}% '
105 \TMP@EnsureCode{126}\active % ~
106 \TMP@EnsureCode{128}{12}% ^^80
107 \TMP@EnsureCode{147}{12}% ^^93
108 \TMP@EnsureCode{148}{12}% ^^94
109 \TMP@EnsureCode{160}{12}% ^^a0
110 \TMP@EnsureCode{194}{12}% ^^c2
111 \TMP@EnsureCode{226}{12}% ^^e2

```

2.3 Loading packages

Package soul uses `\documentclass` to detect L^AT_EX.

```
112 \ifx\documentclass\@undefined
```

2.3.1 plain-T_EX

First we check, whether package soul is already loaded.

```
113 \expandafter\ifx\csname SOUL@\endcsname\relax
```

In case of plain-T_EX package soul defines some macros in a simple manner that will break the definitions of `miniltx.tex`, for example. Therefore these macros are first saved and restored afterwards.

```

114   \let\Soul@orgDeclareRobustCommand\DeclareRobustCommand
115   \let\Soul@orgnewcommand           \newcommand
116   \let\Soul@orgDeclareOption       \DeclareOption
117   \let\Soul@orgPackageError        \PackageError
118   \def\Soul@restorelatexcmds{%
119     \let\DeclareRobustCommand\Soul@orgDeclareRobustCommand
120     \let\newcommand           \Soul@orgnewcommand

```

```

121     \let\DeclareOption      \SOuL@orgDeclareOption
122     \let\PackageError      \SOuL@orgPackageError
123   }%
124   \input soul.sty\relax
125   \SOuL@restorelatexcmds
126 \fi

```

`\SOUL@error` Package soul's use of `\PackageError` is replaced by `\@PackageError` of package `infwarerr`.

```

127 \input infwarerr.sty\relax
128 \let\SOuL@orgSOUL@error\SOUL@error
129 \def\SOUL@error{%
130   \begingroup
131     \let\PackageError\@PackageError
132     \SOuL@orgSOUL@error
133   \endgroup
134 }%
135 \input etexcmds.sty\relax

```

`\@onelevel@sanitize` Define L^AT_EX's `\@onelevel@sanitize` if not already available.

```

136 \expandafter\ifx\csname @onelevel@sanitize\endcsname\relax
137   \def\@onelevel@sanitize#1{%
138     \edef#1{%
139       \expandafter\strip@prefix\meaning#1%
140     }%
141   }%

```

`\strip@prefix`

```

142   \def\strip@prefix#1>{ }%
143 \fi
144 \else

```

2.3.2 L^AT_EX

```

145 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{soul}}%
146 \ProcessOptions\relax
147 \RequirePackage{soul}[2003/11/17]%
148 \RequirePackage{infwarerr}[2007/09/09]%
149 \RequirePackage{etexcmds}[2007/09/09]%
150 \fi

```

2.3.3 ε -T_EX

In plain-T_EX command `\+` is an *outer* macro. Therefore numbers are used to avoid problems.

```

151 \ifetex@unexpanded
152   \catcode33=14 % '!': comment
153   \catcode43=9  % '+': ignore
154 \else
155   \catcode33=9  % '!': ignore
156   \catcode43=14 % '+': comment
157 \fi

```

2.4 Macro for redefinitions

`\SOuL@redefine`

```

158 \def\SOuL@redefine#1{%
159   \begingroup
160     \def\SOuL@cmd{#1}%
161     \afterassignment\SOuL@cmdcheck
162     \def\SOuL@temp
163 }

```

\SOUL@cmdcheck

```
164 \def\SOUL@cmdcheck{%
165   \expandafter\ifx\SOUL@cmd\SOUL@temp
166   \else
167     \edef\SOUL@temp*{\expandafter\string\SOUL@cmd}%
168     \@PackageWarningNoLine{soulutf8}{%
169       Command \SOUL@temp* has changed.\MessageBreak
170       Supported versions of package 'soul': 2003/11/17.\MessageBreak
171       Depending on the unknown changes the redefinition\MessageBreak
172       of \SOUL@temp* may not behave correctly%
173     }%
174   \fi
175 \expandafter\endgroup
176 \expandafter\def\SOUL@cmd
177 }
```

2.5 Redefinition of \SOUL@eval

\SOUL@eval Macro \SOUL@eval is redefined to add detection of the first byte of a UTF-8 sequence. Because \SOUL@eval is overwritten, a warning is issued, if the contents of \SOUL@eval is not as expected.

```
178 \SOUL@redefine\SOUL@eval{%
```

First the expected definition.

```
179 \def\SOUL@n*##1{\SOUL@scan}%
180 \if\noexpand\SOUL@@\SOUL@spc
181 \else
182   \SOUL@ignorespacesfalse
183 \fi
184 \ifnum\SOUL@minus=\thr@@
185   \SOUL@flushminus
186 \else\ifnum\SOUL@comma=\tw@
187   \SOUL@flushcomma
188 \else\ifnum\SOUL@apo=\tw@
189   \SOUL@flushapo
190 \else\ifnum\SOUL@grave=\tw@
191   \SOUL@flushgrave
192 \fi\fi\fi\fi
193 \ifx\SOUL@@-\else\SOUL@flushminus\fi
194 \ifx\SOUL@,@\else\SOUL@flushcomma\fi
195 \ifx\SOUL@@'\else\SOUL@flushapo\fi
196 \ifx\SOUL@@'\else\SOUL@flushgrave\fi
197 \ifx\SOUL@@-%
198   \advance\SOUL@minus\@ne
199 \else\ifx\SOUL@@,%
200   \advance\SOUL@comma\@ne
201 \else\ifx\SOUL@@'%
202   \advance\SOUL@apo\@ne
203 \else\ifx\SOUL@@'\%
204   \advance\SOUL@grave\@ne
205 \else
206   \SOUL@flushminus
207   \SOUL@flushcomma
208   \SOUL@flushapo
209   \SOUL@flushgrave
210   \ifx\SOUL@@\SOUL@stop
211     \def\SOUL@n*{%
212       \SOUL@doword
213       \SOUL@eventuallyexhyphen\null
214     }%
215   \else\ifx\SOUL@@\par
216     \def\SOUL@n*\par{\par\leavevmode\SOUL@scan}%

```



```

278 \ifx\SOUL@@-\else\SOUL@flushminus\fi
279 \ifx\SOUL@,@\else\SOUL@flushcomma\fi
280 \ifx\SOUL@@'\else\SOUL@flushapo\fi
281 \ifx\SOUL@@'\else\SOUL@flushgrave\fi
282 \ifx\SOUL@@-%
283   \advance\SOUL@minus\@ne
284 \else\ifx\SOUL@,@,%
285   \advance\SOUL@comma\@ne
286 \else\ifx\SOUL@@'\%
287   \advance\SOUL@apo\@ne
288 \else\ifx\SOUL@@'\%
289   \advance\SOUL@grave\@ne
290 \else
291   \SOUL@flushminus
292   \SOUL@flushcomma
293   \SOUL@flushapo
294   \SOUL@flushgrave
295   \ifx\SOUL@@\SOUL@stop
296     \def\SOUL@n*{%
297       \SOUL@doword
298       \SOUL@eventuallyexhyphen\null
299     }%
300   \else\ifx\SOUL@@\par
301     \def\SOUL@n*\par{\par\leavevmode\SOUL@scan}%
302   \else\if\noexpand\SOUL@@\SOUL@spc
303     \SOUL@doword
304     \SOUL@eventuallyexhyphen\null
305     \ifSOUL@ignorespaces
306     \else
307       \SOUL@everyspace{}%
308     \fi
309     \def\SOUL@n* {\SOUL@scan}%
310   \else\ifx\SOUL@@\%
311     \SOUL@doword
312     \SOUL@eventuallyexhyphen\null
313     \SOUL@everyspace{\unskip\nobreak\hfil\break}%
314     \SOUL@ignorepacestrue
315   \else\ifx\SOUL@@~%
316     \SOUL@doword
317     \SOUL@eventuallyexhyphen\null
318     \SOUL@everyspace{\nobreak}%
319   \else\ifx\SOUL@@\slash
320     \SOUL@doword
321     \SOUL@eventuallyexhyphen{/}%
322     \SOUL@exhyphen{/}%
323   \else\ifx\SOUL@@\mbox
324     \def\SOUL@n*{\SOUL@addprotect}%
325   \else\ifx\SOUL@@\hbox
326     \def\SOUL@n*{\SOUL@addprotect}%
327   \else\ifx\SOUL@@\soulomit
328     \def\SOUL@n*\soulomit##1{%
329       \SOUL@doword
330       {\spaceskip\SOUL@spaceskip##1}%
331       \SOUL@scan
332     }%
333   \else\ifx\SOUL@@\break
334     \SOUL@doword
335     \break
336   \else\ifx\SOUL@@\linebreak
337     \SOUL@doword
338     \SOUL@everyspace{\linebreak}%
339   \else\ifcat\bgroup\noexpand\SOUL@@

```



```

393 \def\Soul@temp{#2}%
394 \chardef\Soul@octets=%
395 \ifx\Soul@temp\Soul@stringtwo
396 \tw@
397 \else\ifx\Soul@temp\Soul@stringthree
398 \thr@@
399 \else\ifx\Soul@temp\Soul@stringfour
400 4 %
401 \else
402 \z@
403 \fi\fi\fi
404 }

```

2.6.3 Support for utf8x.def

\Soul@analyzeutfviiiix

```

405 \begingroup
406 \edef\x{\endgroup
407 \def\noexpand\Soul@analyzeutfviiiix{%
408 \noexpand\expandafter\noexpand\Soul@checkutfviiiix
409 \noexpand\meaning\noexpand\Soul@@
410 \Soul@stringmacrocolon\Soul@charhash1{}-{}-{}-{}%
411 \Soul@stringcsnameu\Soul@stringundeferr
412 \noexpand\@nil
413 }%

```

\Soul@checkutfviiiix

```

414 \def\noexpand\Soul@checkutfviiiix
415 ##1\Soul@stringmacrocolon\Soul@charhash1##2##3##4##5##6%
416 \Soul@stringcsnameu##7\Soul@stringundeferr##8\noexpand\@nil
417 }%
418 \x{%
419 \def\Soul@temp{#7}%
420 \ifx\Soul@temp\Soul@empty
421 \chardef\Soul@octets=\z@
422 \else
423 \def\Soul@temp{#5}%
424 \ifx\Soul@temp\Soul@charthree
425 \chardef\Soul@octets=4 %
426 \else
427 \def\Soul@temp{#3}%
428 \ifx\Soul@temp\Soul@chartwo
429 \chardef\Soul@octets=\thr@@
430 \else
431 \chardef\Soul@octets=\tw@
432 \fi
433 \fi
434 \fi
435 }

```

2.7 Actions for UTF-8 sequences

\Soul@addtwooctets

```

436 \def\Soul@addtwooctets#1#2{%
437 \def\Soul@temp{#1#2}%
438 \@onelevel@sanitize\Soul@temp
439 \ifx\Soul@temp\Soul@stringnobreakspace
440 \Soul@doword
441 \Soul@eventuallyexhyphen\null
442 \Soul@everySPACE{\nobreak}%
443 \let\Soul@next\Soul@scan

```

```

444 \else
445   \def\Soul@next{%
446 !     \Soul@addtoken{\noexpand#1\noexpand#2}}%
447 +     \Soul@addtoken{\etex@unexpanded{#1#2}}}%
448   }%
449 \fi
450 \Soul@next
451 }

```

\Soul@addthreeoctets

```

452 \def\Soul@addthreeoctets#1#2#3{%
453   \def\Soul@temp{#1#2#3}%
454   \@onelevel@sanitize\Soul@temp
455   \ifx\Soul@temp\Soul@stringendash
456     \Soul@doword
457     \Soul@eventuallyexhyphen{-}%
458     \Soul@exhyphen{--}%
459     \let\Soul@next\Soul@scan
460   \else
461     \ifx\Soul@temp\Soul@stringemdash
462       \Soul@doword
463       \Soul@eventuallyexhyphen{-}%
464       \Soul@exhyphen{---}%
465       \let\Soul@next\Soul@scan
466     \else
467       \def\Soul@next{%
468 !         \Soul@addtoken{\noexpand#1\noexpand#2\noexpand#3}}%
469 +         \Soul@addtoken{\etex@unexpanded{#1#2#3}}}%
470       }%
471     \fi
472   \fi
473   \Soul@next
474 }

```

\Soul@addfouroctets

```

475 \def\Soul@addfouroctets#1#2#3#4{%
476 ! \Soul@addtoken{\noexpand#1\noexpand#2\noexpand#3\noexpand#4}}%
477 + \Soul@addtoken{\etex@unexpanded{#1#2#3#4}}}%
478 }

```

2.7.1 Redefinition of \Soul@splittoken

\Soul@splittoken Macro **\Soul@splittoken** separates the first token or token group from a word and redefines the word to contain the remaining tokens. However if the remaining tokens are a token group, then the curly braces will be removed and the token group is splitted by the next call of **\Soul@splittoken**. The redefinition avoids the removal of curly braces around the remaining tokens.

```

479 \Soul@redefine\Soul@splittoken#1#2\Soul@stop{%
480   \global\Soul@token={#1}%
481   \global\Soul@word={#2}%
482 }#1{%
483   \global\Soul@token={#1}%
484   \Soul@remainingtoken\relax
485 }

```

\Soul@remainingtoken

```

486 \def\Soul@remainingtoken#1\Soul@stop{%
487   \global\Soul@word=\expandafter{\@gobble#1}%
488 }

```

2.8 Patches

The fixed `\SOUL@splittoken` allows to remove the double sets of curly braces in other macros of package `soul`. The benefit is that implicate kernings are more often detected and fixes a bug in package `soul`. The disadvantage is incompatibility. The width of the resulting strings may change.

`\SOUL@flushcomma`

```
489 \SOUL@redefine\SOUL@flushcomma{%
490   \ifcase\SOUL@comma
491   \or
492     \edef\x{\SOUL@word={\the\SOUL@word,}}\x
493   \or
494     \edef\x{\SOUL@word={\the\SOUL@word{, ,}}}\x
495   \fi
496   \SOUL@comma\z@
497 }{%
498   \ifcase\SOUL@comma
499   \or
500     \edef\x{\SOUL@word={\the\SOUL@word,}}\x
501   \or
502     \edef\x{\SOUL@word={\the\SOUL@word{, ,}}}\x
503   \fi
504   \SOUL@comma\z@
505 }
```

`\SOUL@flushapo`

```
506 \SOUL@redefine\SOUL@flushapo{%
507   \ifcase\SOUL@apo
508   \or
509     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
510   \or
511     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
512   \fi
513   \SOUL@apo\z@
514 }{%
515   \ifcase\SOUL@apo
516   \or
517     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
518   \or
519     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
520   \fi
521   \SOUL@apo\z@
522 }
```

`\SOUL@flushgrave`

```
523 \SOUL@redefine\SOUL@flushgrave{%
524   \ifcase\SOUL@grave
525   \or
526     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
527   \or
528     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
529   \fi
530   \SOUL@grave\z@
531 }{%
532   \ifcase\SOUL@grave
533   \or
534     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
535   \or
536     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
537   \fi
538   \SOUL@grave\z@
539 }
```

\SOUL@addgroup

```

540 \SOuL@redefine\SOUL@addgroup#1#2{%
541   {%
542     \let\protect\noexpand
543     \edef\x{%
544       \global\SOUL@word={%
545         \the\SOUL@word
546         {{\noexpand#1#2}}}%
547     }%
548   }%
549   \x
550 }%
551 \SOUL@scan
552 }#1#2{%
553   \begingroup
554     \let\protect\noexpand
555     \edef\x{\endgroup
556       \SOUL@word={%
557         \the\SOUL@word
558         !      {\noexpand#1{#2}}}%
559 +      {\etex@unexpanded{#1{#2}}}}%
560     }%
561   }%
562   \x
563   \SOUL@scan
564 }

```

\SOUL@addmath

```

565 \SOuL@redefine\SOUL@addmath$#1${%
566   {%
567     \let\protect\noexpand
568     \edef\x{%
569       \global\SOUL@word={%
570         \the\SOUL@word
571         {{\hbox{ $#1$ }}}}%
572     }%
573   }%
574   \x
575 }%
576 \SOUL@scan
577 }$#1${%
578   \begingroup
579     \let\protect\noexpand
580     \edef\x{\endgroup
581       \SOUL@word={%
582         \the\SOUL@word
583         !      {\hbox{ $#1$ }}}}%
584 +      {\etex@unexpanded{\hbox{ $#1$ }}}}%
585     }%
586   }%
587   \x
588   \SOUL@scan
589 }

```

\SOUL@addprotect

```

590 \SOuL@redefine\SOUL@addprotect#1#2{%
591   {%
592     \let\protect\noexpand
593     \edef\x{%
594       \global\SOUL@word={%
595         \the\SOUL@word
596         {{\hbox{ #2}}}}%

```

```

597     }%
598   }%
599   \x
600 }%
601 \SOUL@scan
602 }#1#2{%
603 \begingroup
604   \let\protect\noexpand
605   \edef\x{\endgroup
606     \SOUL@word={%
607       \the\SOUL@word
608 !     {\hbox{#2}}}%
609 +     {\etex@unexpanded{\hbox{#2}}}%
610   }%
611 }%
612 \x
613 \SOUL@scan
614 }

```

\SOUL@addtoken

```

615 + \SOUL@redefine\SOUL@addtoken#1{%
616 +   \edef\x{%
617 +     \SOUL@word={%
618 +       \the\SOUL@word
619 +       \noexpand#1%
620 +     }%
621 +   }%
622 +   \x
623 +   \SOUL@scan
624 + }#1{%
625 +   \edef\x{%
626 +     \SOUL@word={%
627 +       \the\SOUL@word
628 +       \etex@unexpanded{#1}%
629 +     }%
630 +   }%
631 +   \x
632 +   \SOUL@scan
633 + }%

634 \SOUL@AtEnd
635 </package>

```

3 Test

3.1 Catcode checks for loading

```

636 <*test1>
637 \catcode'\{=1 %
638 \catcode'\}=2 %
639 \catcode'\#=6 %
640 \catcode'\@=11 %
641 \expandafter\ifx\csname count@\endcsname\relax
642 \countdef\count@=255 %
643 \fi
644 \expandafter\ifx\csname @gobble\endcsname\relax
645 \long\def@gobble#1{%
646 \fi
647 \expandafter\ifx\csname @firstofone\endcsname\relax
648 \long\def@firstofone#1{#1}%
649 \fi

```

```

650 \expandafter\ifx\csname loop\endcsname\relax
651 \expandafter\@firstofone
652 \else
653 \expandafter\@gobble
654 \fi
655 {%
656 \def\loop#1\repeat{%
657 \def\body{#1}%
658 \iterate
659 }%
660 \def\iterate{%
661 \body
662 \let\next\iterate
663 \else
664 \let\next\relax
665 \fi
666 \next
667 }%
668 \let\repeat=\fi
669 }%
670 \def\RestoreCatcodes{}
671 \count@=0 %
672 \loop
673 \edef\RestoreCatcodes{%
674 \RestoreCatcodes
675 \catcode\the\count@=\the\catcode\count@\relax
676 }%
677 \ifnum\count@<255 %
678 \advance\count@ 1 %
679 \repeat
680
681 \def\RangeCatcodeInvalid#1#2{%
682 \count@=#1\relax
683 \loop
684 \catcode\count@=15 %
685 \ifnum\count@<#2\relax
686 \advance\count@ 1 %
687 \repeat
688 }
689 \expandafter\ifx\csname LoadCommand\endcsname\relax
690 \def\LoadCommand{\input soulutf8.sty\relax}%
691 \fi
692 \def\Test{%
693 \RangeCatcodeInvalid{0}{47}%
694 \RangeCatcodeInvalid{58}{64}%
695 \RangeCatcodeInvalid{91}{96}%
696 \RangeCatcodeInvalid{123}{255}%
697 \catcode'\@=12 %
698 \catcode'\=0 %
699 \catcode'\{=1 %
700 \catcode'\}=2 %
701 \catcode'\#=6 %
702 \catcode'\[=12 %
703 \catcode'\]=12 %
704 \catcode'\%=14 %
705 \catcode'\ =10 %
706 \catcode13=5 %
707 \LoadCommand
708 \RestoreCatcodes
709 }
710 \Test
711 \csname @@end\endcsname

```

```

712 \end
713 </test1>

```

3.2 L^AT_EX tests

```

714 <*test2 | test3 | test4 | test5>
715 <noetex> \let \SavedUnexpanded \unexpanded
716 <noetex> \let \unexpanded \UNDEFINED
717 \NeedsTeXFormat{LaTeX2e}
718 \documentclass{article}
719 \usepackage[T1]{fontenc}
720 \usepackage{lmodern}
721 \usepackage{textcomp}
722 \usepackage[ngerman]{babel}
723 \expandafter\def\csname ver@hypdestopt.sty\endcsname{}
724 \usepackage[unicode]{hyperref}
725 \usepackage{bookmark}
726 \usepackage{color}
727 \usepackage{soul}[2003/11/17]
728 \makeatletter
729 \newcommand*{\@ifDefined}[1]{%
730   \@ifundefined{#1}{%
731     \latex@error{%
732       \expandafter\noexpand\csname#1\endcsname undefined%
733     }\@ehc
734   }%
735 }
736 \newcommand*{\SaveOrg}[1]{%
737   \@ifdefinable{ORG@SOUL@#1}{%
738     \@ifDefined{SOUL@#1}{%
739       \expandafter\let\csname ORG@SOUL@#1\expandafter\endcsname
740         \csname SOUL@#1\endcsname
741     }%
742   }%
743 }
744 \newcommand*{\RestoreOrg}[1]{%
745   \@ifDefined{ORG@SOUL@#1}{%
746     \@ifDefined{SOUL@#1}{%
747       \expandafter\let\csname SOUL@#1\expandafter\endcsname
748         \csname ORG@SOUL@#1\endcsname
749     }%
750   }%
751 }
752 \makeatother
753 \SaveOrg{eval}
754 \SaveOrg{splittoken}
755 \SaveOrg{flushcomma}
756 \SaveOrg{flushapo}
757 \SaveOrg{grave}
758 \SaveOrg{addgroup}
759 \SaveOrg{addmath}
760 \SaveOrg{addprotect}
761 \SaveOrg{addtoken}
762 \usepackage{soulutf8}[2007/09/09]
763 <noetex> \let \unexpanded \SavedUnexpanded

```

Input encoding utf8.

```

764 <*utf8>
765 \usepackage[utf8]{inputenc}
766 \DeclareUnicodeCharacter{00A0}{\nobreakspace}
767 </utf8>

```

Input encoding utf8x. Package ucs has a nasty bug, that it redefines \show.

```

768 <*utf8x>
769 \let\origshow\show
770 \usepackage[utf8x]{inputenc}
771 \AtBeginDocument{%
772   \let\show\origshow
773 }
774 </utf8x>

```

3.2.1 Driver definitions

```
775 \makeatletter
```

\an The definition for \an is taken from the documentation of package soul.

```

776 \DeclareRobustCommand*\an{%
777   \def\SOUL@preamble{$^{^P}$}%
778   \def\SOUL@everySPACE##1{##1\texttt{\char'\ }\linebreak[2]}%
779   \def\SOUL@postamble{$^{^E}$}%
780   \def\SOUL@everyhyphen{$^{^-}$}\linebreak[1]}%
781   \def\SOUL@everyexhyphen##1{##1$^{^=}$}%
782   \def\SOUL@everysyllable{$^{^S}$}%
783   \def\SOUL@everytoken{\the\SOUL@token$^{^T}$}%
784   \def\SOUL@everylowerthan{$^{^L}$}%
785   \SOUL@
786 }

```

\sy The definition for \sy is taken from the documentation of package soul.

```

787 \DeclareRobustCommand*\sy{%
788   \SOUL@setup
789   \def\SOUL@preamble{%
790     \lefthyphenmin=\z@
791     \righthyphenmin=\z@
792   }%
793   \def\SOUL@everySPACE##1{##1\space}%
794   \def\SOUL@everysyllable{\the\SOUL@syllable}%
795   \def\SOUL@everyhyphen{%
796     \discretionary{%
797       \SOUL@setkern\SOUL@hyphkern
798       \SOUL@sethyphenchar
799     }{}{%
800       \hbox{\kern1pt$\cdot$}%
801     }%
802   }%
803   \def\SOUL@everyexhyphen##1{%
804     \SOUL@setkern\SOUL@hyphkern
805     \hbox{##1}%
806     \discretionary{}{}{%
807       \SOUL@setkern\SOUL@charkern
808     }%
809   }%
810   \SOUL@
811 }

```

\soulH

```

812 \DeclareRobustCommand*\soulH{%
813   \def\SOUL@preamble{%
814     \gdef\SOULH{}%
815     \soulHadd{ }%
816   }%
817   \def\SOUL@everySPACE##1{%
818     \soulHadd{Sp}%
819   }%
820   \def\SOUL@postamble{%
821     \soulHadd{ ]}%

```

```

822 }%
823 \def\SOUL@everyhyphen{%
824   \soulHadd{Hy}%
825 }%
826 \def\SOUL@everyexhyphen##1{%
827   \soulHadd{Exhy}%
828 }%
829 \def\SOUL@everysyllable{%
830   \soulHadd{Sy}%
831 }%
832 \def\SOUL@everytoken{%
833   \soulHadd{T}%
834 }%
835 \def\SOUL@everylowerthan{%
836   \soulHadd{<}%
837 }%
838 \SOUL@
839 }
840 \newcommand*{\soulHadd}[1]{%
841   #1%
842   \expandafter\gdef\expandafter\soulHstring\expandafter{%
843     \soulHstring
844     #1%
845   }%
846 }

```

3.2.2 Test macros

```

847 \usepackage{qstest}
848 \IncludeTests{*}
849 \LogTests{log}{*}{*}

850 \newsavebox\boxA
851 \newsavebox\boxB
852 \newsavebox\boxC

\TestDriver

853 \newcommand*{\TestDriver}[4]{%
854   \subsection{Driver #1}%
855   \@PackageInfo{soulutf8-test}{* Driver #1}%
856   \expandafter\let\expandafter\testdriver\csname #1\endcsname
857   \def\teststringA{#3}%
858   \def\teststringB{#4}%
859   \begin{qstest}{string-#2-driver-#1}{string,#2,driver,#1}%
860     \@PackageInfo{soulutf8-test}{* Version: soulutf8}%
861     \global\let\soulHstring\@empty
862     \setbox0=\hbox{\expandafter\testdriver\expandafter{\teststringA}}%
863     \let\HstringA\soulHstring
864     \SetTestVBox{\boxA}{\teststringA}%
865     %
866     \@PackageInfo{soulutf8-test}{* Version: soul + patch}%
867     \global\let\soulHstring\@empty
868     \RestoreOrg{eval}%
869     \setbox2=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
870     \let\HstringB\soulHstring
871     \SetTestVBox{\boxB}{\teststringB}%
872     %
873     \@PackageInfo{soulutf8-test}{* Version: original soul}%
874     \global\let\soulHstring\@empty
875     \RestoreOrg{splittoken}%
876     \RestoreOrg{flushcomma}%
877     \RestoreOrg{flushapo}%
878     \RestoreOrg{grave}%

```

```

879 \RestoreOrg{addgroup}%
880 \RestoreOrg{addmath}%
881 \RestoreOrg{addprotect}%
882 \RestoreOrg{addtoken}%
883 \setbox4=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
884 \let\HstringC\soulHstring
885 \SetTestVBox{\boxC}{\teststringB}%
886 %
887 \TestInfo{0}{soulutf8}%
888 \TestInfo{2}{soul + patch}%
889 \TestInfo{4}{original soul}%
890 \TestInfoVBox
891 \showboxdepth=\maxdimen
892 \showboxbreadth=\maxdimen
893 \tracingonline=@ne
894 \Expect*{\HstringA}*{\HstringB}%
895 \Expect*{\HstringA}*{\HstringC}%
896 \Expect*{\the\wd0}*{\the\wd2}%
897 \ifdim\wd0=\wd2 %
898 \else
899 \showbox0 %
900 \showbox2 %
901 \fi
902 \Expect*{\the\ht0}*{\the\ht2}%
903 \Expect*{\the\dp0}*{\the\dp2}%
904 \Expect*{\the\wd\boxB}*{\the\wd\boxA}%
905 \Expect*{\the\wd\boxC}*{\the\wd\boxA}%
906 \Expect*{\the\ht\boxB}*{\the\ht\boxA}%
907 \ifdim\ht\boxB=\ht\boxA
908 \else
909 \showbox\boxA
910 \showbox\boxB
911 \fi
912 \Expect*{\the\ht\boxC}*{\the\ht\boxA}%
913 \Expect*{\the\dp\boxB}*{\the\dp\boxA}%
914 \Expect*{\the\dp\boxC}*{\the\dp\boxA}%
915 \end{qstest}%
916 }

```

\SetTestVBox

```

917 \newcommand*{\SetTestVBox}[2]{%
918 \setbox#1=\vbox{%
919 \hsize=0pt\relax
920 \hfuzz=100mm\relax
921 \expandafter\testdriver\expandafter{#2}%
922 }%
923 }

```

\TestInfo

```

924 \newcommand*{\TestInfo}[2]{%
925 \par
926 \noindent
927 \copy#1\relax
928 \hfill
929 \begin{group}
930 \small
931 \ifdim\wd0=\wd2\relax
932 \ifdim\wd0=\wd4\relax
933 \else
934 \ifnum#1=2 %
935 \raisebox{.5\baselineskip}[Opt][Opt]{%
936 \llap{$\}$ }%

```

```

937         \rlap{width = \the\wd#1\relax\space$\{$}%
938         \phantom{width = 999.99999pt}}%
939         \qqquad
940     }%
941     \else
942         \ifnum#1=4 %
943             \rlap{width = \the\wd#1}%
944             \phantom{width = 999.99999pt}}%
945             \qqquad
946         \fi
947     \fi
948 \fi
949 \else
950     \begingroup
951         \bfseries
952         \rlap{width = \the\wd#1}%
953         \phantom{width = 999.99999pt}}%
954     \endgroup
955     \qqquad
956 \fi
957 \rlap{(#2)}%
958 \phantom{(original soul)}}%
959 \endgroup
960 \par
961 }

```

\TestInfoVBox

```

962 \newcommand*{\TestInfoVBox}{%
963     \par
964     \noindent
965     \mbox{\vrule\relax\space\copy\boxA}%
966     \ifdim\ht\boxA=\ht\boxB
967     \else
968         \hfill
969         \begingroup
970             \small
971             \rlap{(soulutf8)}%
972             \phantom{(soulutf8)}}%
973         \endgroup
974     \par
975     \noindent
976     \mbox{\vrule\relax\space\copy\boxB}%
977     \hfill
978     \begingroup
979         \small
980         \rlap{(soul)}%
981         \phantom{(soulutf8)}}%
982     \endgroup
983 \fi
984 \par
985 }

```

\Test

```

986 \makeatletter
987 \newcommand*{\Test}[3]{%
988     \clearpage
989     \begingroup
990         \def\linebreak{\textbackslash linebreak }%
991         \def\{\{\textbackslash\textbackslash}%
992         \def\soulomit##1{%
993             \textbackslash soulomit\textbraceleft##1\textbraceright
994         }%

```

```

995 \def\mbox##1{%
996 \textbackslash mbox\textbraceleft##1\textbraceright
997 }%
998 \def\abc{\textbackslash abc }%
999 \def\texttt##1{%
1000 \textbackslash texttt\textbraceleft##1\textbraceright
1001 }%
1002 \def\c##1{%
1003 \textbackslash c\textbraceleft##1\textbraceright
1004 }%
1005 <utf8x>
1006 \count@=128 %
1007 \loop
1008 \ifnum\count@<256 %
1009 \lccode'\~=\count@
1010 \lowercase{%
1011 \def~{\noexpand~}%
1012 }%
1013 \advance\count@\@ne
1014 \repeat
1015 </utf8x>
1016 \csname protected@edef\endcsname\x\endgroup
1017 \noexpand\section{String #1: #2}%
1018 }%
1019 \x
1020 \TestDriver{so}{#1}{#2}{#3}%
1021 \TestDriver{caps}{#1}{#2}{#3}%
1022 \TestDriver{ul}{#1}{#2}{#3}%
1023 \TestDriver{st}{#1}{#2}{#3}%
1024 \TestDriver{hl}{#1}{#2}{#3}%
1025 \TestDriver{an}{#1}{#2}{#3}%
1026 \TestDriver{sy}{#1}{#2}{#3}%
1027 \TestDriver{soulH}{#1}{#2}{#3}%
1028 }
1029 \makeatother

```

3.2.3 Testing

```

1030 \begin{document}
1031 \Test A{}{}%
1032 \Test B{Hello World}{Hello World}%
1033 \Test C{%
1034 Umlauts: ^c3^84^c3^96^c3^9c^c3^a4^c3^b6^c3^bc^c3^9f%
1035 }%
1036 Umlauts: \"A\"O\"U\"a\"o\"u\"ss
1037 }%
1038 \Test D{Euro: ^e2^82^ac}{Euro: \texteuro}%
1039 \Test E{Stra^c3^9fe}{Stra\ss e}%
1040 \Test F{R^c3^b6mer}{R\"omer}%
1041 \Test G{A^e2^80^93B^e2^80^94C}{A--B---C}%
1042 \Test H{X^c2^a0Y}{X~Y}%
1043 \Test I{A^c5^a4}{A\v T}%
1044 \Test J{A,B,,C,,,D,,,E}{A,B,,C,,,D,,,E}%
1045 \Test K{A'B''C''D''''E}{A'B''C''D''''E}%
1046 \Test L{A'B'C''D''''E}{A'B'C''D''''E}%
1047 \Test M{A$x$B}{A$x$B}%
1048 \Test N{A\mbox{abc}B}{A\mbox{abc}B}%
1049 \Test O{,TA''}{,TA''}%
1050 \Test P{{'!}'Hola{''}}{{'!}'Hola{''}}%
1051 \Test Q{re-sent\slash x}{re-sent\slash x}%
1052 \Test R{new\\line}{new\\line}%
1053 \Test S{foo\linebreak bar}{foo\linebreak bar}%
1054 \Test T{Virchow{sche}}{Virchow{sche}}%

```

```

1055 \Test U{A\soulomit{foo}B}{A\soulomit{foo}B}%
1056 \Test V{A\texttt{xyz}B}{A\texttt{xyz}B}%
1057 \Test W{ffi}{ffi}%
1058 \Test X{f{}f{}i}{f{}f{}i}%
1059 \Test Y{f\mbox{}f\mbox{}i}{f\mbox{}f\mbox{}i}%
1060 \Test Z{c{"a}}{c{"a}}%
1061 <*test2 | test3>
1062 \let\abcx\UNDEFINED
1063 \def\abc{%
1064     \begingroup
1065     \def\abcx{x}%
1066     \abcx
1067     \endgroup
1068 }%
1069 \Test{AA}{[{x\abc x}]}[{xxx}]}%
1070 </test2 | test3>
1071 \end{document}
1072 </test2 | test3 | test4 | test5>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/soulutf8.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/soulutf8.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting docstrip archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex soulutf8.dtx
```

¹<http://ftp.ctan.org/tex-archive/>

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
soulutf8.sty      → tex/generic/oberdiek/soulutf8.sty
soulutf8.pdf      → doc/latex/oberdiek/soulutf8.pdf
test/soulutf8-test1.tex → doc/latex/oberdiek/test/soulutf8-test1.tex
test/soulutf8-test2.tex → doc/latex/oberdiek/test/soulutf8-test2.tex
test/soulutf8-test3.tex → doc/latex/oberdiek/test/soulutf8-test3.tex
test/soulutf8-test4.tex → doc/latex/oberdiek/test/soulutf8-test4.tex
test/soulutf8-test5.tex → doc/latex/oberdiek/test/soulutf8-test5.tex
soulutf8.dtx      → source/latex/oberdiek/soulutf8.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your \TeX distribution (te \TeX , mik \TeX , ...) relies on file name databases, you must refresh these. For example, te \TeX users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk soulutf8.pdf unpack_files output .
```

Unpacking with \LaTeX . The `.dtx` chooses its action depending on the format:

plain- \TeX : Run `docstrip` and extract the files.

\LaTeX : Generate the documentation.

If you insist on using \LaTeX for `docstrip` (really, `docstrip` does not need \LaTeX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{soulutf8.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdf \LaTeX :

```
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
```

5 References

- [1] Melchior Franz: *The soul package*; 2003/11/17;
CTAN:macros/latex/contrib/soul/.
- [2] Dominique P. G. Unruh: *ucs.sty – Unicode Support*; 2004/10/17;
CTAN:macros/latex/contrib/unicode/.
- [3] Frank Mittelbach, Chris Rowley: *Providing some UTF-8 support via inputenc*;
2006/03/30;
CTAN:macros/latex/base/utf8ienc.dtx.

6 History

[2007/09/09 v1.0]

- First version.

7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	
\"	1036, 1040, 1060
\#	639, 701
\%	704
\@	640, 697
\@PackageError	131
\@PackageInfo	855, 860, 866, 873
\@PackageWarningNoLine	168
\@ehc	733
\@empty	861, 867, 874
\@firstofone	648, 651
\@gobble	487, 645, 653
\@ifDefined	729, 738, 745, 746
\@ifdefinable	737
\@ifundefined	730
\@latex@error	731
\@ne	198, 200, 202, 204, 283, 285, 287, 289, 893, 1013
\@nil	387, 390, 412, 416
\@onelevel@sanitize	136, 364, 438, 454
\@undefined	52, 112
\[702
\]	225, 310, 698, 991, 1052
\{	637, 699, 937
\}	638, 700, 936
\]	703
\~	1009
_	705, 778
A	
\abc	998, 1063, 1069
\abcx	1062, 1065, 1066
\active	105
\advance	198, 200, 202, 204, 283, 285, 287, 289, 678, 686, 1013
B	
\afterassignment	161
\aftergroup	26
\an	776
\AtBeginDocument	771
\baselineskip	935
\begin	859, 1030
\bfseries	951
\body	657, 661
\boxA	850, 864, 904, 905, 906, 907, 909, 912, 913, 914, 965, 966
\boxB	851, 871, 904, 906, 907, 910, 913, 966, 976
\boxC	852, 885, 905, 912, 914
\break	228, 248, 250, 313, 333, 335
C	
\c	1002, 1060
\catcode	3, 4, 5, 6, 7, 8, 9, 17, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 64, 65, 68, 69, 70, 71, 75, 76, 77, 78, 82, 84, 152, 153, 155, 156, 637, 638, 639, 640, 675, 684, 697, 698, 699, 700, 701, 702, 703, 704, 705, 706
\cdot	800
\char	778
\chardef	394, 421, 425, 429, 431
\clearpage	988
\copy	927, 965, 976
\count@	642, 671, 675, 677, 678, 682, 684, 685, 686, 1006, 1008, 1009, 1013
\countdef	642
\csname	10, 18, 44, 60, 67, 113, 136, 363, 364, 641,

644, 647, 650, 689, 711, 723, 732, 739, 740, 747, 748, 856, 1016	\input 124, 127, 135, 690
\CurrentOption 145	\iterate 658, 660, 662
D	K
\DeclareOption 116, 121, 145	\kern 800
\DeclareRobustCommand 114, 119, 776, 787, 812	L
\DeclareUnicodeCharacter 766	\lccode 1009
\discretionary 796, 806	\leavevmode 216, 301
\documentclass 112, 718	\lefthyphenmin 790
\dp 903, 913, 914	\linebreak 251, 253, 336, 338, 778, 780, 990, 1053
E	\llap 936
\empty 13, 14	\LoadCommand 690, 707
\end 712, 915, 1071	\LogTests 849
\endscname 10, 18, 44, 60, 67, 113, 136, 363, 364, 641, 644, 647, 650, 689, 711, 723, 732, 739, 740, 747, 748, 856, 1016	\loop 656, 672, 683, 1007
\endinginput 26	\lowercase 1010
\etex@unexpanded 447, 469, 477, 559, 584, 609, 628	M
\Expect 894, 895, 896, 902, 903, 904, 905, 906, 912, 913, 914	\makeatletter 728, 775, 986
G	\makeatother 752, 1029
\gdef 814, 842	\maxdimen 891, 892
H	\mbox 238, 323, 965, 976, 995, 1048, 1059
\hbox .. 240, 325, 571, 583, 584, 596, 608, 609, 800, 805, 862, 869, 883	\meaning 139, 385, 409
\hfil 228, 313	\MessageBreak 169, 170, 171
\hfill 928, 968, 977	N
\hfuzz 920	\NeedsTeXFormat 717
\hsize 919	\newcommand 115, 120, 729, 736, 744, 840, 853, 917, 924, 962, 987
\HstringA 863, 894, 895	\newsavebox 850, 851, 852
\HstringB 870, 894	\next 662, 664, 666
\HstringC 884, 895	\nobreak 228, 233, 313, 318, 442
\ht 902, 906, 907, 912, 966	\nobreakspace 766
I	\noindent 926, 964, 975
\if 180, 217, 265, 302	\null 213, 219, 227, 232, 298, 304, 312, 317, 441
\ifcase 345, 348, 490, 498, 507, 515, 524, 532	O
\ifcat 254, 256, 339, 341	\origshow 769, 772
\ifdim 897, 907, 931, 932, 966	P
\ifetex@unexpanded 151	\PackageError 117, 122, 131
\ifnum . 184, 186, 188, 190, 269, 271, 273, 275, 677, 685, 934, 942, 1008	\PackageInfo 23
\ifSOUL@ignorespaces 220, 305	\par 215, 216, 300, 301, 925, 960, 963, 974, 984
\ifx 11, 14, 18, 44, 52, 55, 112, 113, 136, 165, 193, 194, 195, 196, 197, 199, 201, 203, 210, 215, 225, 230, 234, 238, 240, 242, 248, 251, 278, 279, 280, 281, 282, 284, 286, 288, 295, 300, 310, 315, 319, 323, 325, 327, 333, 336, 395, 397, 399, 420, 424, 428, 439, 455, 461, 641, 644, 647, 650, 689	\PassOptionsToPackage 145
\immediate 20, 46	\phantom .. 938, 944, 953, 958, 972, 981
\IncludeTests 848	\ProcessOptions 146
	\protect .. 542, 554, 567, 579, 592, 604
	\ProvidesPackage 15, 61
	Q
	\qqquad 939, 945, 955
	R
	\raisebox 935
	\RangeCatcodeInvalid 681, 693, 694, 695, 696
	\repeat 656, 668, 679, 687, 1014
	\RequirePackage 147, 148, 149
	\RestoreCatcodes .. 670, 673, 674, 708
	\RestoreOrg 744, 868, 875, 876, 877, 878, 879, 880, 881, 882

\righthyphenmin	791	\SOUL@everylowerthan	784, 835
\rlap	937, 943, 952, 957, 971, 980	\SOUL@everyospace	222, 228, 233, 253, 307, 313, 318, 338, 442, 778, 793, 817
S			
\SavedUnexpanded	715, 763	\SOUL@everyosyllable	782, 794, 829
\SaveOrg	736, 753, 754, 755, 756, 757, 758, 759, 760, 761	\SOUL@everytoken	783, 832
\section	1017	\SOUL@exhyphen	237, 322, 458, 464
\setbox	862, 869, 883, 918	\SOUL@flushapo	189, 195, 208, 274, 280, 293, 506
\SetTestVBox	864, 871, 885, 917	\SOUL@flushcomma	187, 194, 207, 272, 279, 292, 489
\show	769, 772	\SOUL@flushgrave	191, 196, 209, 276, 281, 294, 523
\showbox	899, 900, 909, 910	\SOUL@flushminus	185, 193, 206, 270, 278, 291
\showboxbreadth	892	\SOUL@grave	190, 204, 275, 289, 524, 530, 532, 538
\showboxdepth	891	\SOUL@hyphkern	797, 804
\slash	234, 319, 1051	\SOUL@ignorespacesfalse	182, 267
\small	930, 970, 979	\SOUL@ignorespacestrue	229, 314
\SOUL@	785, 810, 838	\SOUL@minus	184, 198, 269, 283
\SOUL@@	180, 193, 194, 195, 196, 197, 199, 201, 203, 210, 215, 217, 225, 230, 234, 238, 240, 242, 248, 251, 254, 256, 265, 278, 279, 280, 281, 282, 284, 286, 288, 295, 300, 302, 310, 315, 319, 323, 325, 327, 333, 336, 339, 341, 385, 409	\SOUL@n	179, 211, 216, 224, 239, 241, 243, 255, 257, 259, 262, 264, 296, 301, 309, 324, 326, 328, 340, 342, 349, 352, 354, 356, 360
\SOuL@addfouroctets	356, 475	\SOuL@next	443, 445, 450, 459, 465, 467, 473
\SOUL@addgroup	255, 340, 540	\SOuL@octets	345, 348, 394, 421, 425, 429, 431
\SOUL@addmath	257, 342, 565	\SOuL@orgDeclareOption	116, 121
\SOUL@addprotect	239, 241, 324, 326, 590	\SOuL@orgDeclareRobustCommand	114, 119
\SOuL@addthreooctets	354, 452	\SOuL@orgnewcommand	115, 120
\SOUL@addtoken	446, 447, 468, 469, 476, 477, 615	\SOuL@orgPackageError	117, 122
\SOuL@addtwooctets	352, 436	\SOuL@orgSOUL@error	128, 132
\SOuL@analyzeutfviii	344, 381	\SOUL@postamble	779, 820
\SOuL@analyzeutfviiix	346, 405	\SOUL@preamble	777, 789, 813
\SOUL@apo	188, 202, 273, 287, 507, 513, 515, 521	\SOuL@redefine	158, 178, 479, 489, 506, 523, 540, 565, 590, 615
\SOuL@AtEnd	80, 81, 634	\SOuL@remainingtoken	484, 486
\SOuL@charhash	377, 410, 415	\SOuL@restorelatexcmds	118, 125
\SOUL@charkern	807	\SOUL@scan	179, 216, 224, 246, 264, 301, 309, 331, 443, 459, 465, 551, 563, 576, 588, 601, 613, 623, 632
\SOuL@charthree	379, 424	\SOUL@sethyphenchar	798
\SOuL@chartwo	378, 428	\SOUL@setkern	797, 804, 807
\SOuL@checkutfviii	384, 389	\SOUL@setup	788
\SOuL@checkutfviiix	408, 414	\SOUL@spaceskip	245, 330
\SOuL@cmd	160, 165, 167, 176	\SOUL@spc	180, 217, 265, 302
\SOuL@cmdcheck	161, 164	\SOUL@splittoken	479
\SOUL@comma	186, 200, 271, 285, 490, 496, 498, 504	\SOUL@stop	210, 295, 479, 486
\SOuL@defsanitizedstring	362, 366, 367, 368, 369, 370, 371, 372, 373	\SOuL@stringcsnameu	411, 416
\SOUL@dotoken	259, 349	\SOuL@stringemdash	375, 461
\SOUL@doword	212, 218, 226, 231, 235, 244, 249, 252, 297, 303, 311, 316, 320, 329, 334, 337, 440, 456, 462	\SOuL@stringendash	374, 455
\SOuL@empty	380, 420	\SOuL@stringfour	399
\SOUL@error	127	\SOuL@stringmacrocolon	410, 415
\SOUL@eval	178	\SOuL@stringnobreakspace	376, 439
\SOUL@eventuallyexhyphen	213, 219, 227, 232, 236, 298, 304, 312, 317, 321, 441, 457, 463	\SOuL@stringoctets	386, 390
\SOUL@everyexhyphen	781, 803, 826	\SOuL@stringthree	397
\SOUL@everyhyphen	780, 795, 823	\SOuL@stringtwo	395
		\SOuL@stringundeferr	411, 416

\SOUL@stringUTFviii	386, 390
\SOUL@syllable	794
\SOUL@temp	162, 165, 167, 169, 172, 393, 395, 397, 399, 419, 420, 423, 424, 427, 428, 437, 438, 439, 453, 454, 455, 461
\SOUL@token	480, 483, 783
\SOUL@word	481, 487, 492, 494, 500, 502, 509, 511, 517, 519, 526, 528, 534, 536, 544, 545, 556, 557, 569, 570, 581, 582, 594, 595, 606, 607, 617, 618, 626, 627
\SOULH	814
\soulH	<u>812</u>
\soulHadd	815, 818, 821, 824, 827, 830, 833, 836, 840
\soulHstring	842, 843, 861, 863, 867, 870, 874, 884
\soulomit	242, 243, 327, 328, 992, 1055
\space	793, 937, 965, 976
\spaceskip	245, 330
\ss	1036, 1039
\strip@prefix	139, <u>142</u>
\subsection	<u>854</u>
\sy	<u>787</u>
T		
\Test	692, 710, <u>986</u> , 1031, 1032, 1033, 1038, 1039, 1040, 1041, 1042, 1043, 1044, 1045, 1046, 1047, 1048, 1049, 1050, 1051, 1052, 1053, 1054, 1055, 1056, 1057, 1058, 1059, 1060, 1069
\TestDriver	<u>853</u> , 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027
\testdriver	856, 862, 869, 883, 921
\TestInfo	887, 888, 889, <u>924</u>
\TestInfoVBox	890, <u>962</u>
\teststringA	857, 862, 864
\teststringB	858, 869, 871, 883, 885
\textbackslashash 990, 991, 993, 996, 998, 1000, 1003
\textbraceleft	993, 996, 1000, 1003
\textbraceright	993, 996, 1000, 1003
\teuro	1038
\textrm{ttt}	778, 999, 1056
\the	68, 69, 70, 71, 82, 492, 494, 500, 502, 509, 511, 517, 519, 526, 528, 534, 536, 545, 557, 570, 582, 595, 607, 618, 627, 675, 783, 794, 896, 902, 903, 904, 905, 906, 912, 913, 914, 937, 943, 952
\thr@@	184, 269, 398, 429
\TMP@EnsureCode	79, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111
\tracingonline	893
\tw@	186, 188, 190, 271, 273, 275, 396, 431
U		
\UNDEFINED	716, 1062
\unexpanded	715, 716, 763
\unskip	228, 313
\usepackage	719, 720, 721, 722, 724, 725, 726, 727, 762, 765, 770, 847
V		
\v	1043
\ vbox	918
\vrule	965, 976
W		
\wd	896, 897, 904, 905, 931, 932, 937, 943, 952
\write	20, 46
X		
\x	10, 11, 14, 19, 23, 25, 45, 50, 60, 66, 74, 382, 392, 406, 418, 492, 494, 500, 502, 509, 511, 517, 519, 526, 528, 534, 536, 543, 549, 555, 562, 568, 574, 580, 587, 593, 599, 605, 612, 616, 622, 625, 631, 1016, 1019
Z		
\z@	402, 421, 496, 504, 513, 521, 530, 538, 790, 791