

The soulutf8 package

Heiko Oberdiek
<heiko.oberdiek at gmail.com>

2007/09/09 v1.0

Abstract

This package extends package `soul` and adds some support for UTF-8. Namely the input encodings `utf8.def` from package `inputenc` and package `ucs`'s `utf8x.def` are supported.

Contents

1	Documentation	2
1.1	Patch	2
1.2	Future	2
2	Implementation	2
2.1	Reload check and package identification	2
2.2	Catcodes	3
2.3	Loading packages	4
2.3.1	plain \TeX	5
2.3.2	\LaTeX	5
2.3.3	$\epsilon\text{-TeX}$	5
2.4	Macro for redefinitions	6
2.5	Redefinition of <code>\SOUL@eval</code>	6
2.6	UTF-8 analysis	9
2.6.1	Help strings	9
2.6.2	Support for <code>utf8.def</code>	10
2.6.3	Support for <code>utf8x.def</code>	10
2.7	Actions for UTF-8 sequences	11
2.7.1	Redefinition of <code>\SOUL@splittoken</code>	11
2.8	Patches	12
3	Test	15
3.1	Catcode checks for loading	15
3.2	\LaTeX tests	16
3.2.1	Driver definitions	17
3.2.2	Test macros	19
3.2.3	Testing	22
4	Installation	22
4.1	Download	22
4.2	Bundle installation	23
4.3	Package installation	23
4.4	Refresh file name databases	23
4.5	Some details for the interested	23
5	References	24

6 History	24
[2007/09/09 v1.0]	24
7 Index	24

1 Documentation

This package `soulutf8` does not have own options and does not define new user commands. Any option is passed to package `soul` [1] that is loaded first. Then some internal macros of `soul` are redefined to add support for UTF-8. The following input encodings are supported:

```
utf8      LATEX base    TDS:tex/latex/base/utf8.def [3]
utf8x     Package ucs   TDS:tex/latex/ucs/utf8x.def [2]
```

UTF-8 byte sequences are added as token group to a word, even if these UTF-8 characters are some kind of hyphen or space. As exception the following three Unicode characters are handled specially:

Slot	Name	Action
U+00A0	NO-BREAK SPACE	like ~
U+2013	EN DASH	--
U+2014	EM DASH	---

1.1 Patch

Also package `soulutf8` tries to patch package `soul` to improve its behaviour:

- A problem with additional levels of curly braces is fixed. As advantage more implicate kernings are detected. However, the result may be incompatible with the original behaviour of package `soul` because of these respected implicate kernings.
- ε -T_EX, especially `\unexpanded` is supported. This allows a better protection of token groups (`\mbox{...}`, `math, ...`).

1.2 Future

Currently package `soul` does not seem to be maintained. Nevertheless if there will be a new version that adds support for UTF-8, then this package may become obsolete.

2 Implementation

```
1 <*package>
```

2.1 Reload check and package identification

Reload check, especially if the package is not used with L^AT_EX.

```
2 \begingroup\catcode61\catcode48\catcode32=10\relax%
3 \catcode13=5 % ^^M
4 \endlinechar=13 %
5 \catcode35=6 % #
6 \catcode39=12 % '
7 \catcode44=12 % ,
8 \catcode45=12 % -
9 \catcode46=12 % .
10 \catcode58=12 % :
11 \catcode64=11 % @
```

```

12 \catcode123=1 % {
13 \catcode125=2 % }
14 \expandafter\let\expandafter\x\csname ver@soulutf8.sty\endcsname
15 \ifx\x\relax % plain-TeX, first loading
16 \else
17   \def\empty{}%
18   \ifx\x\empty % LaTeX, first loading,
19     % variable is initialized, but \ProvidesPackage not yet seen
20   \else
21     \expandafter\ifx\csname PackageInfo\endcsname\relax
22       \def\x#1#2{%
23         \immediate\write-1{Package #1 Info: #2.}%
24       }%
25     \else
26       \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27     \fi
28     \x{soulutf8}{The package is already loaded}%
29     \aftergroup\endinput
30   \fi
31 \fi
32 \endgroup%

```

Package identification:

```

33 \begingroup\catcode61\catcode48\catcode32=10\relax%
34 \catcode13=5 % ^^M
35 \endlinechar=13 %
36 \catcode35=6 % #
37 \catcode39=12 % '
38 \catcode40=12 % (
39 \catcode41=12 % )
40 \catcode44=12 % ,
41 \catcode45=12 % -
42 \catcode46=12 % .
43 \catcode47=12 % /
44 \catcode58=12 % :
45 \catcode64=11 % @
46 \catcode91=12 % [
47 \catcode93=12 % ]
48 \catcode123=1 % {
49 \catcode125=2 % }
50 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
51   \def\x#1#2#3[#4]{\endgroup
52     \immediate\write-1{Package: #3 #4}%
53     \xdef#1{#4}%
54   }%
55 \else
56   \def\x#1#2[#3]{\endgroup
57     #2[#{#3}]%
58     \ifx#1\@undefined
59       \xdef#1{#3}%
60     \fi
61     \ifx#1\relax
62       \xdef#1{#3}%
63     \fi
64   }%
65 \fi
66 \expandafter\x\csname ver@soulutf8.sty\endcsname
67 \ProvidesPackage{soulutf8}%
68 [2007/09/09 v1.0 Adding support for UTF-8 to soul (H0)]%

```

2.2 Catcodes

```

69 \begingroup\catcode61\catcode48\catcode32=10\relax%

```

```

70 \catcode13=5 % ^^M
71 \endlinechar=13 %
72 \catcode123=1 % {
73 \catcode125=2 % }
74 \catcode64=11 % @
75 \def\x{\endgroup
76   \expandafter\edef\csname SOuL@AtEnd\endcsname{%
77     \endlinechar=\the\endlinechar\relax
78     \catcode13=\the\catcode13\relax
79     \catcode32=\the\catcode32\relax
80     \catcode35=\the\catcode35\relax
81     \catcode61=\the\catcode61\relax
82     \catcode64=\the\catcode64\relax
83     \catcode123=\the\catcode123\relax
84     \catcode125=\the\catcode125\relax
85   }%
86 }%
87 \x\catcode61\catcode48\catcode32=10\relax%
88 \catcode13=5 % ^^M
89 \endlinechar=13 %
90 \catcode35=6 % #
91 \catcode64=11 % @
92 \catcode123=1 % {
93 \catcode125=2 % }
94 \def\TMP@EnsureCode#1#2{%
95   \edef\SOuL@AtEnd{%
96     \SOuL@AtEnd
97     \catcode#1=\the\catcode#1\relax
98   }%
99   \catcode#1=#2\relax
100 }
101 \TMP@EnsureCode{10}{12}% ^^J
102 \TMP@EnsureCode{33}{12}% !
103 \TMP@EnsureCode{34}{12}% "
104 \TMP@EnsureCode{36}{3}% $
105 \TMP@EnsureCode{39}{12}% '
106 \TMP@EnsureCode{40}{12}% (
107 \TMP@EnsureCode{41}{12}% )
108 \TMP@EnsureCode{42}{12}% *
109 \TMP@EnsureCode{43}{12}% +
110 \TMP@EnsureCode{44}{12}% ,
111 \TMP@EnsureCode{45}{12}% -
112 \TMP@EnsureCode{46}{12}% .
113 \TMP@EnsureCode{47}{12}% /
114 \TMP@EnsureCode{58}{12}% :
115 \TMP@EnsureCode{60}{12}% <
116 \TMP@EnsureCode{62}{12}% >
117 \TMP@EnsureCode{91}{12}% [
118 \TMP@EnsureCode{93}{12}% ]
119 \TMP@EnsureCode{94}{7}% ^
120 \TMP@EnsureCode{96}{12}% ‘
121 \TMP@EnsureCode{126}\active % ~
122 \TMP@EnsureCode{128}{12}% ^^80
123 \TMP@EnsureCode{147}{12}% ^^93
124 \TMP@EnsureCode{148}{12}% ^^94
125 \TMP@EnsureCode{160}{12}% ^^a0
126 \TMP@EnsureCode{194}{12}% ^^c2
127 \TMP@EnsureCode{226}{12}% ^^e2
128 \edef\SOuL@AtEnd{\SOuL@AtEnd\noexpand\endinput}

```

2.3 Loading packages

Package soul uses `\documentclass` to detect L^AT_EX.

129 \ifx\documentclass\@undefined

2.3.1 plain T_EX

First we check, whether package soul is already loaded.

130 \expandafter\ifx\csname SOUL@\endcsname\relax

In case of plain T_EX package soul defines some macros in a simple manner that will break the definitions of miniltx.tex, for example. Therefore these macros are first saved and restored afterwards.

```

131 \let\Soul@orgDeclareRobustCommand\DeclareRobustCommand
132 \let\Soul@orgnewcommand\newcommand
133 \let\Soul@orgDeclareOption\DeclareOption
134 \let\Soul@orgPackageError\PackageError
135 \def\Soul@restorelatexcmds{%
136 \let\DeclareRobustCommand\Soul@orgDeclareRobustCommand
137 \let\newcommand\Soul@orgnewcommand
138 \let\DeclareOption\Soul@orgDeclareOption
139 \let\PackageError\Soul@orgPackageError
140 }%
141 \input soul.sty\relax
142 \Soul@restorelatexcmds
143 \fi

```

\SOUL@error Package soul's use of \PackageError is replaced by \@PackageError of package infwarerr.

```

144 \input infwarerr.sty\relax
145 \let\Soul@orgSOUL@error\SOUL@error
146 \def\SOUL@error{%
147 \begingroup
148 \let\PackageError\@PackageError
149 \Soul@orgSOUL@error
150 \endgroup
151 }%
152 \input etexcmds.sty\relax

```

\@onelevel@sanitize Define I^AT_EX's \@onelevel@sanitize if not already available.

```

153 \expandafter\ifx\csname @onelevel@sanitize\endcsname\relax
154 \def\@onelevel@sanitize#1{%
155 \edef#1{%
156 \expandafter\strip@prefix\meaning#1%
157 }%
158 }%

```

\strip@prefix

```

159 \def\strip@prefix#1>{}%
160 \fi
161 \else

```

2.3.2 I^AT_EX

```

162 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{soul}}%
163 \ProcessOptions\relax
164 \RequirePackage{soul}[2003/11/17]%
165 \RequirePackage{infwarerr}[2007/09/09]%
166 \RequirePackage{etexcmds}[2007/09/09]%
167 \fi

```

2.3.3 ε-T_EX

In plain T_EX command \+ is an *outer* macro. Therefore numbers are used to avoid problems.

```

168 \ifetex@unexpanded
169 \catcode33=14 % '!': comment
170 \catcode43=9 % '+': ignore
171 \else
172 \catcode33=9 % '!': ignore
173 \catcode43=14 % '+': comment
174 \fi

```

2.4 Macro for redefinitions

`\SOuL@redefine`

```

175 \def\SOuL@redefine#1{%
176 \begingroup
177 \def\SOuL@cmd{#1}%
178 \afterassignment\SOuL@cmdcheck
179 \def\SOuL@temp
180 }

```

`\SOuL@cmdcheck`

```

181 \def\SOuL@cmdcheck{%
182 \expandafter\ifx\SOuL@cmd\SOuL@temp
183 \else
184 \edef\SOuL@temp*{\expandafter\string\SOuL@cmd}%
185 \@PackageWarningNoLine{soulutf8}{%
186 Command \SOuL@temp* has changed.\MessageBreak
187 Supported versions of package 'soul': 2003/11/17.\MessageBreak
188 Depending on the unknown changes the redefinition\MessageBreak
189 of \SOuL@temp* may not behave correctly%
190 }%
191 \fi
192 \expandafter\endgroup
193 \expandafter\def\SOuL@cmd
194 }

```

2.5 Redefinition of `\SOUL@eval`

`\SOUL@eval` Macro `\SOUL@eval` is redefined to add detection of the first byte of a UTF-8 sequence. Because `\SOUL@eval` is overwritten, a warning is issued, if the contents of `\SOUL@eval` is not as expected.

```

195 \SOuL@redefine\SOUL@eval{%

```

First the expected definition.

```

196 \def\SOUL@n*##1{\SOUL@scan}%
197 \if\noexpand\SOUL@@\SOUL@spc
198 \else
199 \SOUL@ignorespacesfalse
200 \fi
201 \ifnum\SOUL@minus=\thr@@
202 \SOUL@flushminus
203 \else\ifnum\SOUL@comma=\tw@
204 \SOUL@flushcomma
205 \else\ifnum\SOUL@apo=\tw@
206 \SOUL@flushapo
207 \else\ifnum\SOUL@grave=\tw@
208 \SOUL@flushgrave
209 \fi\fi\fi\fi
210 \ifx\SOUL@@-\else\SOUL@flushminus\fi
211 \ifx\SOUL@,@\else\SOUL@flushcomma\fi
212 \ifx\SOUL@@'\else\SOUL@flushapo\fi
213 \ifx\SOUL@@'\else\SOUL@flushgrave\fi
214 \ifx\SOUL@@-%
215 \advance\SOUL@minus\@ne

```

```

216 \else\ifx\SOUL@@,%
217   \advance\SOUL@comma\@ne
218 \else\ifx\SOUL@' %
219   \advance\SOUL@apo\@ne
220 \else\ifx\SOUL@@"%
221   \advance\SOUL@grave\@ne
222 \else
223   \SOUL@flushminus
224   \SOUL@flushcomma
225   \SOUL@flushapo
226   \SOUL@flushgrave
227   \ifx\SOUL@@\SOUL@stop
228     \def\SOUL@n*{%
229       \SOUL@doword
230       \SOUL@eventuallyexhyphen\null
231     }%
232 \else\ifx\SOUL@@\par
233   \def\SOUL@n*\par{\par\leavevmode\SOUL@scan}%
234 \elseifnoexpand\SOUL@@\SOUL@spc
235   \SOUL@doword
236   \SOUL@eventuallyexhyphen\null
237   \ifSOUL@ignorespaces
238     \else
239       \SOUL@everyspace{}%
240     \fi
241     \def\SOUL@n* {\SOUL@scan}%
242 \else\ifx\SOUL@@\%%
243   \SOUL@doword
244   \SOUL@eventuallyexhyphen\null
245   \SOUL@everySPACE{unskip\nobreak\hfil\break}%
246   \SOUL@ignoreSPACEtrue
247 \else\ifx\SOUL@@~%
248   \SOUL@doword
249   \SOUL@eventuallyexhyphen\null
250   \SOUL@everySPACE{nobreak}%
251 \else\ifx\SOUL@@\/%
252   \SOUL@doword
253   \SOUL@eventuallyexhyphen{/}%
254   \SOUL@exhyphen{/}%
255 \else\ifx\SOUL@@\mbox
256   \def\SOUL@n*{\SOUL@addprotect}%
257 \else\ifx\SOUL@@\hbox
258   \def\SOUL@n*{\SOUL@addprotect}%
259 \else\ifx\SOUL@@\soulomit
260   \def\SOUL@n*\soulomit##1{%
261     \SOUL@doword
262     {spaceskip\SOUL@spaceskip##1}%
263     \SOUL@scan
264   }%
265 \else\ifx\SOUL@@\break
266   \SOUL@doword
267   \break
268 \else\ifx\SOUL@@\linebreak
269   \SOUL@doword
270   \SOUL@everySPACE{linebreak}%
271 \else\ifcat\bgroupnoexpand\SOUL@@
272   \def\SOUL@n*{\SOUL@addgroup{}}%
273 \else\ifcat$\noexpand\SOUL@@
274   \def\SOUL@n*{\SOUL@addmath}%
275 \else
276   \def\SOUL@n*{\SOUL@dotoken}%
277 \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi

```

```

278 \fi\fi\fi\fi
279 \SOUL@n*%
280 }{%
```

Now the redefined version follows.

```

281 \def\SOUL@n*##1{\SOUL@scan}%
282 \if\noexpand\SOUL@@\SOUL@spc
283 \else
284 \SOUL@ignorespacesfalse
285 \fi
286 \ifnum\SOUL@minus=\thr@@
287 \SOUL@flushminus
288 \else\ifnum\SOUL@comma=\tw@
289 \SOUL@flushcomma
290 \else\ifnum\SOUL@apo=\tw@
291 \SOUL@flushapo
292 \else\ifnum\SOUL@grave=\tw@
293 \SOUL@flushgrave
294 \fi\fi\fi\fi
295 \ifx\SOUL@@-\else\SOUL@flushminus\fi
296 \ifx\SOUL@,@\else\SOUL@flushcomma\fi
297 \ifx\SOUL@@'\else\SOUL@flushapo\fi
298 \ifx\SOUL@@'\else\SOUL@flushgrave\fi
299 \ifx\SOUL@@-%
300 \advance\SOUL@minus\@ne
301 \else\ifx\SOUL@@,%
302 \advance\SOUL@comma\@ne
303 \else\ifx\SOUL@@'%
304 \advance\SOUL@apo\@ne
305 \else\ifx\SOUL@@'\%
306 \advance\SOUL@grave\@ne
307 \else
308 \SOUL@flushminus
309 \SOUL@flushcomma
310 \SOUL@flushapo
311 \SOUL@flushgrave
312 \ifx\SOUL@@\SOUL@stop
313 \def\SOUL@n*{%
314 \SOUL@doword
315 \SOUL@eventuallyexhyphen\null
316 }%
317 \else\ifx\SOUL@@\par
318 \def\SOUL@n*\par{\par\leavevmode\SOUL@scan}%
319 \else\if\noexpand\SOUL@@\SOUL@spc
320 \SOUL@doword
321 \SOUL@eventuallyexhyphen\null
322 \ifSOUL@ignorespaces
323 \else
324 \SOUL@everySPACE{}%
325 \fi
326 \def\SOUL@n* {\SOUL@scan}%
327 \else\ifx\SOUL@@\%
328 \SOUL@doword
329 \SOUL@eventuallyexhyphen\null
330 \SOUL@everySPACE{\unskip\nobreak\hfil\break}%
331 \SOUL@ignorespacestrue
332 \else\ifx\SOUL@@~%
333 \SOUL@doword
334 \SOUL@eventuallyexhyphen\null
335 \SOUL@everySPACE{\nobreak}%
336 \else\ifx\SOUL@@\slash
337 \SOUL@doword
338 \SOUL@eventuallyexhyphen{/}%
```



```

395 \edef\S0uL@chartwo{\string 2}
396 \edef\S0uL@charthree{\string 3}
397 \def\S0uL@empty{}

```

2.6.2 Support for utf8.def

\S0uL@analyzeutfviii

```

398 \begingroup
399 \edef\x{\endgroup
400   \def\noexpand\S0uL@analyzeutfviii{%
401     \noexpand\expandafter\noexpand\S0uL@checkutfviii
402     \noexpand\meaning\noexpand\S0uL@@
403     \S0uL@stringUTFviii\S0uL@stringoctets
404     \noexpand\@nil
405   }%
406   \def\noexpand\S0uL@checkutfviii
407     ##1\S0uL@stringUTFviii##2\S0uL@stringoctets##3\noexpand\@nil
408   }%
409 \x{%
410   \def\S0uL@temp{#2}%
411   \chardef\S0uL@octets=%
412     \ifx\S0uL@temp\S0uL@stringtwo
413       \tw@
414     \else\ifx\S0uL@temp\S0uL@stringthree
415       \thr@@
416     \else\ifx\S0uL@temp\S0uL@stringfour
417       4 %
418     \else
419       \z@
420     \fi\fi\fi
421 }

```

2.6.3 Support for utf8x.def

\S0uL@analyzeutfviiix

```

422 \begingroup
423 \edef\x{\endgroup
424   \def\noexpand\S0uL@analyzeutfviiix{%
425     \noexpand\expandafter\noexpand\S0uL@checkutfviiix
426     \noexpand\meaning\noexpand\S0uL@@
427     \S0uL@stringmacrocolon\S0uL@charhash1{-}{-}{-}{-}%
428     \S0uL@stringcsnameu\S0uL@stringundeferr
429     \noexpand\@nil
430   }%

```

\S0uL@checkutfviiix

```

431   \def\noexpand\S0uL@checkutfviiix
432     ##1\S0uL@stringmacrocolon\S0uL@charhash1##2##3##4##5##6%
433     \S0uL@stringcsnameu##7\S0uL@stringundeferr##8\noexpand\@nil
434   }%
435 \x{%
436   \def\S0uL@temp{#7}%
437   \ifx\S0uL@temp\S0uL@empty
438     \chardef\S0uL@octets=\z@
439   \else
440     \def\S0uL@temp{#5}%
441     \ifx\S0uL@temp\S0uL@charthree
442       \chardef\S0uL@octets=4 %
443     \else
444       \def\S0uL@temp{#3}%
445       \ifx\S0uL@temp\S0uL@chartwo
446         \chardef\S0uL@octets=\thr@@

```

```

447     \else
448     \chardef\Soul@octets=\tw@
449     \fi
450 \fi
451 \fi
452 }

```

2.7 Actions for UTF-8 sequences

`\Soul@addtwooctets`

```

453 \def\Soul@addtwooctets#1#2{%
454   \def\Soul@temp{#1#2}%
455   \@onelevel@sanitize\Soul@temp
456   \ifx\Soul@temp\Soul@stringnobreakspace
457     \SOUL@doword
458     \SOUL@eventuallyexhyphen\null
459     \SOUL@everySPACE{\nobreak}%
460     \let\Soul@next\Soul@scan
461   \else
462     \def\Soul@next{%
463       ! \SOUL@addtoken{\noexpand#1\noexpand#2}}%
464     + \SOUL@addtoken{\etex@unexpanded{#1#2}}}%
465     }%
466   \fi
467   \Soul@next
468 }

```

`\Soul@addthreeoctets`

```

469 \def\Soul@addthreeoctets#1#2#3{%
470   \def\Soul@temp{#1#2#3}%
471   \@onelevel@sanitize\Soul@temp
472   \ifx\Soul@temp\Soul@stringendash
473     \SOUL@doword
474     \SOUL@eventuallyexhyphen{-}%
475     \SOUL@exhyphen{--}%
476     \let\Soul@next\Soul@scan
477   \else
478     \ifx\Soul@temp\Soul@stringemdash
479       \SOUL@doword
480       \SOUL@eventuallyexhyphen{-}%
481       \SOUL@exhyphen{---}%
482       \let\Soul@next\Soul@scan
483     \else
484       \def\Soul@next{%
485         ! \SOUL@addtoken{\noexpand#1\noexpand#2\noexpand#3}}%
486       + \SOUL@addtoken{\etex@unexpanded{#1#2#3}}}%
487       }%
488     \fi
489   \fi
490   \Soul@next
491 }

```

`\Soul@addfouroctets`

```

492 \def\Soul@addfouroctets#1#2#3#4{%
493   ! \SOUL@addtoken{\noexpand#1\noexpand#2\noexpand#3\noexpand#4}}%
494   + \SOUL@addtoken{\etex@unexpanded{#1#2#3#4}}}%
495 }

```

2.7.1 Redefinition of `\SOUL@splittoken`

`\SOUL@splittoken` Macro `\SOUL@splittoken` separates the first token or token group from a word and redefines the word to contain the remaining tokens. However if the remaining

tokens are a token group, then the curly braces will be removed and the token group is splitted by the next call of `\SOUL@splittoken`. The redefinition avoids the removal of curly braces around the remaining tokens.

```

496 \SOUL@redefine\SOUL@splittoken#1#2\SOUL@stop{%
497   \global\SOUL@token={#1}%
498   \global\SOUL@word={#2}%
499 }#1{%
500   \global\SOUL@token={#1}%
501   \SOUL@remainingtoken\relax
502 }
```

`\SOUL@remainingtoken`

```

503 \def\SOUL@remainingtoken#1\SOUL@stop{%
504   \global\SOUL@word=\expandafter{\@gobble#1}%
505 }
```

2.8 Patches

The fixed `\SOUL@splittoken` allows to remove the double sets of curly braces in other macros of package `soul`. The benefit is that implicate kernings are more often detected and fixes a bug in package `soul`. The disadvantage is incompatibility. The width of the resulting strings may change.

`\SOUL@flushcomma`

```

506 \SOUL@redefine\SOUL@flushcomma{%
507   \ifcase\SOUL@comma
508   \or
509     \edef\x{\SOUL@word={\the\SOUL@word,}}\x
510   \or
511     \edef\x{\SOUL@word={\the\SOUL@word{, ,}}}\x
512   \fi
513   \SOUL@comma\z@
514 }{%
515   \ifcase\SOUL@comma
516   \or
517     \edef\x{\SOUL@word={\the\SOUL@word,}}\x
518   \or
519     \edef\x{\SOUL@word={\the\SOUL@word{, ,}}}\x
520   \fi
521   \SOUL@comma\z@
522 }
```

`\SOUL@flushapo`

```

523 \SOUL@redefine\SOUL@flushapo{%
524   \ifcase\SOUL@apo
525   \or
526     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
527   \or
528     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
529   \fi
530   \SOUL@apo\z@
531 }{%
532   \ifcase\SOUL@apo
533   \or
534     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
535   \or
536     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
537   \fi
538   \SOUL@apo\z@
539 }
```

\SOUL@flushgrave

```

540 \SOuL@redefine\SOUL@flushgrave{%
541   \ifcase\SOUL@grave
542   \or
543     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
544   \or
545     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
546   \fi
547   \SOUL@grave\z@
548 }{%
549   \ifcase\SOUL@grave
550   \or
551     \edef\x{\SOUL@word={\the\SOUL@word'}}\x
552   \or
553     \edef\x{\SOUL@word={\the\SOUL@word{' '}}}\x
554   \fi
555   \SOUL@grave\z@
556 }

```

\SOUL@addgroup

```

557 \SOuL@redefine\SOUL@addgroup#1#2{%
558   {%
559     \let\protect\noexpand
560     \edef\x{%
561       \global\SOUL@word={%
562         \the\SOUL@word
563         {\noexpand#1#2}}%
564     }%
565   }%
566   \x
567 }%
568 \SOUL@scan
569 }#1#2{%
570   \begingroup
571   \let\protect\noexpand
572   \edef\x{\endgroup
573     \SOUL@word={%
574       \the\SOUL@word
575       {\noexpand#1#2}}%
576   +   {\etex@unexpanded{#1#2}}}%
577   }%
578 }%
579 \x
580 \SOUL@scan
581 }

```

\SOUL@addmath

```

582 \SOuL@redefine\SOUL@addmath$#1${%
583   {%
584     \let\protect\noexpand
585     \edef\x{%
586       \global\SOUL@word={%
587         \the\SOUL@word
588         {\hbox{ $#1$ }}%
589     }%
590   }%
591   \x
592 }%
593 \SOUL@scan
594 }$#1${%
595   \begingroup
596   \let\protect\noexpand

```

```

597 \edef\x{\endgroup
598 \SOUL@word={%
599 \the\SOUL@word
600 ! {\hbox{ $#1$}}}%
601 + {\etex@unexpanded{\hbox{ $#1$}}}%
602 }%
603 }%
604 \x
605 \SOUL@scan
606 }

```

\SOUL@addprotect

```

607 \SOUL@redefine\SOUL@addprotect#1#2{%
608 {%
609 \let\protect\noexpand
610 \edef\x{%
611 \global\SOUL@word={%
612 \the\SOUL@word
613 {\hbox{ #2}}}%
614 }%
615 }%
616 \x
617 }%
618 \SOUL@scan
619 }#1#2{%
620 \begingroup
621 \let\protect\noexpand
622 \edef\x{\endgroup
623 \SOUL@word={%
624 \the\SOUL@word
625 ! {\hbox{ #2}}}%
626 + {\etex@unexpanded{\hbox{ #2}}}%
627 }%
628 }%
629 \x
630 \SOUL@scan
631 }

```

\SOUL@addtoken

```

632 + \SOUL@redefine\SOUL@addtoken#1{%
633 + \edef\x{%
634 + \SOUL@word={%
635 + \the\SOUL@word
636 + \noexpand#1%
637 + }%
638 + }%
639 + \x
640 + \SOUL@scan
641 + }#1{%
642 + \edef\x{%
643 + \SOUL@word={%
644 + \the\SOUL@word
645 + \etex@unexpanded{#1}%
646 + }%
647 + }%
648 + \x
649 + \SOUL@scan
650 + }%

```

651 \SOUL@AtEnd%

652 </package>

3 Test

3.1 Catcode checks for loading

```
653 <*test1>
654 \catcode'\{=1 %
655 \catcode'\}=2 %
656 \catcode'\#=6 %
657 \catcode'\@=11 %
658 \expandafter\ifx\csname count@\endcsname\relax
659 \countdef\count@=255 %
660 \fi
661 \expandafter\ifx\csname @gobble\endcsname\relax
662 \long\def\@gobble#1{}%
663 \fi
664 \expandafter\ifx\csname @firstofone\endcsname\relax
665 \long\def\@firstofone#1{#1}%
666 \fi
667 \expandafter\ifx\csname loop\endcsname\relax
668 \expandafter\@firstofone
669 \else
670 \expandafter\@gobble
671 \fi
672 {%
673 \def\loop#1\repeat{%
674 \def\body{#1}%
675 \iterate
676 }%
677 \def\iterate{%
678 \body
679 \let\next\iterate
680 \else
681 \let\next\relax
682 \fi
683 \next
684 }%
685 \let\repeat=\fi
686 }%
687 \def\RestoreCatcodes{}
688 \count@=0 %
689 \loop
690 \edef\RestoreCatcodes{%
691 \RestoreCatcodes
692 \catcode\the\count@=\the\catcode\count@\relax
693 }%
694 \ifnum\count@<255 %
695 \advance\count@ 1 %
696 \repeat
697
698 \def\RangeCatcodeInvalid#1#2{%
699 \count@=#1\relax
700 \loop
701 \catcode\count@=15 %
702 \ifnum\count@<#2\relax
703 \advance\count@ 1 %
704 \repeat
705 }
706 \def\RangeCatcodeCheck#1#2#3{%
707 \count@=#1\relax
708 \loop
709 \ifnum#3=\catcode\count@
710 \else
```

```

711     \errmessage{%
712         Character \the\count@\space
713         with wrong catcode \the\catcode\count@\space
714         instead of \number#3%
715     }%
716     \fi
717     \ifnum\count@<#2\relax
718         \advance\count@ 1 %
719     \repeat
720 }
721 \def\space{ }
722 \expandafter\ifx\csname LoadCommand\endcsname\relax
723     \def\LoadCommand{\input soulutf8.sty\relax}%
724 \fi
725 \def\Test{%
726     \RangeCatcodeInvalid{0}{47}%
727     \RangeCatcodeInvalid{58}{64}%
728     \RangeCatcodeInvalid{91}{96}%
729     \RangeCatcodeInvalid{123}{255}%
730     \catcode'\@=12 %
731     \catcode'\=0 %
732     \catcode'\%=14 %
733     \LoadCommand
734     \RangeCatcodeCheck{0}{36}{15}%
735     \RangeCatcodeCheck{37}{37}{14}%
736     \RangeCatcodeCheck{38}{47}{15}%
737     \RangeCatcodeCheck{48}{57}{12}%
738     \RangeCatcodeCheck{58}{63}{15}%
739     \RangeCatcodeCheck{64}{64}{12}%
740     \RangeCatcodeCheck{65}{90}{11}%
741     \RangeCatcodeCheck{91}{91}{15}%
742     \RangeCatcodeCheck{92}{92}{0}%
743     \RangeCatcodeCheck{93}{96}{15}%
744     \RangeCatcodeCheck{97}{122}{11}%
745     \RangeCatcodeCheck{123}{255}{15}%
746     \RestoreCatcodes
747 }
748 \Test
749 \csname @@end\endcsname
750 \end
751 \</test1>

```

3.2 L^AT_EX tests

```

752 <*test2 | test3 | test4 | test5>
753 <noetex> \let \SavedUnexpanded\unexpanded
754 <noetex> \let \unexpanded\UNDEFINED
755 \NeedsTeXFormat{LaTeX2e}
756 \documentclass{article}
757 \usepackage[T1]{fontenc}
758 \usepackage{lmodern}
759 \usepackage{textcomp}
760 \usepackage[ngerman]{babel}
761 \expandafter\def\csname ver@hypdestopt.sty\endcsname{}
762 \usepackage[unicode]{hyperref}
763 \usepackage{bookmark}
764 \usepackage{color}
765 \usepackage{soul}[2003/11/17]
766 \makeatletter
767 \newcommand*{\@ifDefined}[1]{%
768     \@ifundefined{#1}{%
769         \@latex@error{%
770             \expandafter\noexpand\csname#1\endcsname undefined%

```



```

771   }\@ehc
772 }%
773 }
774 \newcommand*{\SaveOrg}[1]{%
775   \@ifdefinable{ORG@SOUL@#1}{%
776     \@ifDefined{SOUL@#1}{%
777       \expandafter\let\csname ORG@SOUL@#1\expandafter\endcsname
778         \csname SOUL@#1\endcsname
779     }%
780 }%
781 }
782 \newcommand*{\RestoreOrg}[1]{%
783   \@ifDefined{ORG@SOUL@#1}{%
784     \@ifDefined{SOUL@#1}{%
785       \expandafter\let\csname SOUL@#1\expandafter\endcsname
786         \csname ORG@SOUL@#1\endcsname
787     }%
788 }%
789 }
790 \makeatother
791 \SaveOrg{eval}
792 \SaveOrg{splittoken}
793 \SaveOrg{flushcomma}
794 \SaveOrg{flushapo}
795 \SaveOrg{grave}
796 \SaveOrg{addgroup}
797 \SaveOrg{addmath}
798 \SaveOrg{addprotect}
799 \SaveOrg{addtoken}
800 \usepackage{soulutf8}[2007/09/09]
801 \noetex\let\unexpanded\SavedUnexpanded

```

Input encoding utf8.

```

802 \*utf8)
803 \usepackage[utf8]{inputenc}
804 \DeclareUnicodeCharacter{00A0}{\nobreakspace}
805 \</utf8)

```

Input encoding utf8x. Package ucs has a nasty bug, that it redefines \show.

```

806 \*utf8x)
807 \let\origshow\show
808 \usepackage[utf8x]{inputenc}
809 \AtBeginDocument{%
810   \let\show\origshow
811 }
812 \</utf8x)

```

3.2.1 Driver definitions

```

813 \makeatletter

```

\an The definition for \an is taken from the documentation of package soul.

```

814 \DeclareRobustCommand*\an){%
815   \def\SOUL@preamble{${\^P}$}%
816   \def\SOUL@everyspace##1{##1\texttt{\char'\ }\linebreak[2]}%
817   \def\SOUL@postamble{${\^E}$}%
818   \def\SOUL@everyhyphen{${\^~}$\linebreak[1]}%
819   \def\SOUL@everyexhyphen##1{##1${\^=}$}%
820   \def\SOUL@everysyllable{${\^S}$}%
821   \def\SOUL@everytoken{\the\SOUL@token${\^T}$}%
822   \def\SOUL@everylowerthan{${\^L}$}%
823   \SOUL@
824 }

```

\sy The definition for \sy is taken from the documentation of package soul.

```

825 \DeclareRobustCommand*{\sy}{%
826   \SOUL@setup
827   \def\SOUL@preamble{%
828     \lefthyphenmin=\z@
829     \righthyphenmin=\z@
830   }%
831   \def\SOUL@everySPACE##1{##1\space}%
832   \def\SOUL@everySYLLABLE{\the\SOUL@SYLLABLE}%
833   \def\SOUL@everyHYPHEN{%
834     \discretionary{%
835       \SOUL@setkern\SOUL@hyphkern
836       \SOUL@sethyphenchar
837     }{}{%
838       \hbox{\kern1pt$\cdot$}%
839     }%
840   }%
841   \def\SOUL@everyEXHYPHEN##1{%
842     \SOUL@setkern\SOUL@hyphkern
843     \hbox{##1}%
844     \discretionary{}{}{%
845       \SOUL@setkern\SOUL@charkern
846     }%
847   }%
848   \SOUL@
849 }

```

\soulH

```

850 \DeclareRobustCommand*{\soulH}{%
851   \def\SOUL@preamble{%
852     \gdef\SOULH{}%
853     \soulHadd{}%
854   }%
855   \def\SOUL@everySPACE##1{%
856     \soulHadd{Sp}%
857   }%
858   \def\SOUL@postamble{%
859     \soulHadd{]}%
860   }%
861   \def\SOUL@everyHYPHEN{%
862     \soulHadd{Hy}%
863   }%
864   \def\SOUL@everyEXHYPHEN##1{%
865     \soulHadd{Exhy}%
866   }%
867   \def\SOUL@everySYLLABLE{%
868     \soulHadd{Sy}%
869   }%
870   \def\SOUL@everyTOKEN{%
871     \soulHadd{T}%
872   }%
873   \def\SOUL@everyLOWERTHAN{%
874     \soulHadd{<}%
875   }%
876   \SOUL@
877 }
878 \newcommand*{\soulHadd}[1]{%
879   #1%
880   \expandafter\gdef\expandafter\soulHstring\expandafter{%
881     \soulHstring
882     #1%
883   }%
884 }

```

3.2.2 Test macros

```

885 \usepackage{qstest}
886 \IncludeTests{*}
887 \LogTests{log}{*}{*}

888 \newsavebox\boxA
889 \newsavebox\boxB
890 \newsavebox\boxC

\TestDriver

891 \newcommand*{\TestDriver}[4]{%
892   \subsection{Driver #1}%
893   \@PackageInfo{soulutf8-test}{* Driver #1}%
894   \expandafter\let\expandafter\testdriver\csname #1\endcsname
895   \def\teststringA{#3}%
896   \def\teststringB{#4}%
897   \begin{qstest}{string-#2-driver-#1}{string,#2,driver,#1}%
898     \@PackageInfo{soulutf8-test}{* Version: soulutf8}%
899     \global\let\soulHstring\empty
900     \setbox0=\hbox{\expandafter\testdriver\expandafter{\teststringA}}%
901     \let\HstringA\soulHstring
902     \SetTestVBox{\boxA}{\teststringA}%
903     %
904     \@PackageInfo{soulutf8-test}{* Version: soul + patch}%
905     \global\let\soulHstring\empty
906     \RestoreOrg{eval}%
907     \setbox2=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
908     \let\HstringB\soulHstring
909     \SetTestVBox{\boxB}{\teststringB}%
910     %
911     \@PackageInfo{soulutf8-test}{* Version: original soul}%
912     \global\let\soulHstring\empty
913     \RestoreOrg{splittoken}%
914     \RestoreOrg{flushcomma}%
915     \RestoreOrg{flushapo}%
916     \RestoreOrg{grave}%
917     \RestoreOrg{addgroup}%
918     \RestoreOrg{addmath}%
919     \RestoreOrg{addprotect}%
920     \RestoreOrg{addtoken}%
921     \setbox4=\hbox{\expandafter\testdriver\expandafter{\teststringB}}%
922     \let\HstringC\soulHstring
923     \SetTestVBox{\boxC}{\teststringB}%
924     %
925     \TestInfo{0}{soulutf8}%
926     \TestInfo{2}{soul + patch}%
927     \TestInfo{4}{original soul}%
928     \TestInfoVBox
929     \showboxdepth=\maxdimen
930     \showboxbreadth=\maxdimen
931     \tracingonline=\@ne
932     \Expect*{\HstringA}*{\HstringB}%
933     \Expect*{\HstringA}*{\HstringC}%
934     \Expect*{\the\wd0}*{\the\wd2}%
935     \ifdim\wd0=\wd2 %
936       \else
937         \showbox0 %
938         \showbox2 %
939       \fi
940     \Expect*{\the\ht0}*{\the\ht2}%
941     \Expect*{\the\dp0}*{\the\dp2}%
942     \Expect*{\the\wd\boxB}*{\the\wd\boxA}%
943     \Expect*{\the\wd\boxC}*{\the\wd\boxA}%

```

```

944 \Expect*{\the\ht\boxB}*{\the\ht\boxA}%
945 \ifdim\ht\boxB=\ht\boxA
946 \else
947 \showbox\boxA
948 \showbox\boxB
949 \fi
950 \Expect*{\the\ht\boxC}*{\the\ht\boxA}%
951 \Expect*{\the\dp\boxB}*{\the\dp\boxA}%
952 \Expect*{\the\dp\boxC}*{\the\dp\boxA}%
953 \end{qstest}%
954 }

\SetTestVBox

955 \newcommand*{\SetTestVBox}[2]{%
956 \setbox#1=\vbox{%
957 \hsize=0pt\relax
958 \hfuzz=100mm\relax
959 \expandafter\testdriver\expandafter{#2}%
960 }%
961 }

\TestInfo

962 \newcommand*{\TestInfo}[2]{%
963 \par
964 \noindent
965 \copy#1\relax
966 \hfill
967 \begin{group}
968 \small
969 \ifdim\wd0=\wd2\relax
970 \ifdim\wd0=\wd4\relax
971 \else
972 \ifnum#1=2 %
973 \raisebox{.5\baselineskip}[0pt][0pt]{%
974 \llap{$\}$ }%
975 \rlap{width = \the\wd#1\relax\space$\{\}$}%
976 \phantom{width = 999.99999pt}%
977 \quad
978 }%
979 \else
980 \ifnum#1=4 %
981 \rlap{width = \the\wd#1}%
982 \phantom{width = 999.99999pt}%
983 \quad
984 \fi
985 \fi
986 \fi
987 \else
988 \begin{group}
989 \bfseries
990 \rlap{width = \the\wd#1}%
991 \phantom{width = 999.99999pt}%
992 \end{group}
993 \quad
994 \fi
995 \rlap{(#2)}%
996 \phantom{(original soul)}%
997 \end{group}
998 \par
999 }

\TestInfoVBox

```

```

1000 \newcommand*{\TestInfoVBox}{%
1001   \par
1002   \noindent
1003   \mbox{\vrule\relax\space\copy\boxA}%
1004   \ifdim\ht\boxA=\ht\boxB
1005   \else
1006     \hfill
1007     \begin{group}
1008       \small
1009       \rlap{(soulutf8)}%
1010       \phantom{(soulutf8)}%
1011     \end{group}
1012   \par
1013   \noindent
1014   \mbox{\vrule\relax\space\copy\boxB}%
1015   \hfill
1016   \begin{group}
1017     \small
1018     \rlap{(soul)}%
1019     \phantom{(soulutf8)}%
1020   \end{group}
1021 \fi
1022 \par
1023 }

```

\Test

```

1024 \makeatletter
1025 \newcommand*{\Test}[3]{%
1026   \clearpage
1027   \begin{group}
1028     \def\linebreak{\textbackslash linebreak }%
1029     \def\{\{\textbackslash\textbackslash}%
1030     \def\soulomit##1{%
1031       \textbackslash soulomit\textbraceleft##1\textbraceright
1032     }%
1033     \def\mbox##1{%
1034       \textbackslash mbox\textbraceleft##1\textbraceright
1035     }%
1036     \def\abc{\textbackslash abc }%
1037     \def\texttt##1{%
1038       \textbackslash texttt\textbraceleft##1\textbraceright
1039     }%
1040     \def\c##1{%
1041       \textbackslash c\textbraceleft##1\textbraceright
1042     }%
1043 \<utf8x>
1044   \count@=128 %
1045   \loop
1046     \ifnum\count@<256 %
1047       \lccode'\~=\count@
1048       \lowercase{%
1049         \def~{\noexpand~}%
1050       }%
1051       \advance\count@\@ne
1052     \repeat
1053 \</utf8x>
1054   \csname protected@edef\endcsname\x\endgroup
1055   \noexpand\section{String #1: #2}%
1056   }%
1057 \x
1058 \TestDriver{so}{#1}{#2}{#3}%
1059 \TestDriver{caps}{#1}{#2}{#3}%
1060 \TestDriver{ul}{#1}{#2}{#3}%

```

```

1061 \TestDriver{st}{#1}{#2}{#3}%
1062 \TestDriver{hl}{#1}{#2}{#3}%
1063 \TestDriver{an}{#1}{#2}{#3}%
1064 \TestDriver{sy}{#1}{#2}{#3}%
1065 \TestDriver{soulH}{#1}{#2}{#3}%
1066 }
1067 \makeatother

```

3.2.3 Testing

```

1068 \begin{document}
1069 \Test A{}{}%
1070 \Test B{Hello World}{Hello World}%
1071 \Test C{%
1072   Umlauts: ^^c3^^84^^c3^^96^^c3^^9c^^c3^^a4^^c3^^b6^^c3^^bc^^c3^^9f%
1073 }{%
1074   Umlauts: \"A\"O\"U\"a\"o\"u\\ss
1075 }%
1076 \Test D{Euro: ^^e2^^82^^ac}{Euro: \texteuro}%
1077 \Test E{Stra^^c3^^9fe}{Stra\\ss e}%
1078 \Test F{R^^c3^^b6mer}{R\"omer}%
1079 \Test G{A^^e2^^80^^93B^^e2^^80^^94C}{A--B---C}%
1080 \Test H{X^^c2^^a0Y}{X~Y}%
1081 \Test I{A^^c5^^a4}{A\v T}%
1082 \Test J{A,B,,C,,,D,,,E}{A,B,,C,,,D,,,E}%
1083 \Test K{A'B''C''D''E}{A'B''C''D''E}%
1084 \Test L{A'B'C'D'E}{A'B'C'D'E}%
1085 \Test M{A$x$B}{A$x$B}%
1086 \Test N{A\mbox{abc}B}{A\mbox{abc}B}%
1087 \Test O{,TA''}{,TA''}%
1088 \Test P{{!'}Hola{?}}{!'}Hola{?}}%
1089 \Test Q{re-sent\slash x}{re-sent\slash x}%
1090 \Test R{new\\line}{new\\line}%
1091 \Test S{foo\\linebreak bar}{foo\\linebreak bar}%
1092 \Test T{Virchow{sche}}{Virchow{sche}}%
1093 \Test U{A\soulomit{foo}B}{A\soulomit{foo}B}%
1094 \Test V{A\texttt{xyz}B}{A\texttt{xyz}B}%
1095 \Test W{ffi}{ffi}%
1096 \Test X{f{}f{}i}{f{}f{}i}%
1097 \Test Y{f\mbox{}}f\mbox{}i}{f\mbox{}f\mbox{}i}%
1098 \Test Z{\c{"a}}{\c{"a}}%
1099 <*test2 | test3>
1100 \let\abcx\UNDEFINED
1101 \def\abc{%
1102   \begingroup
1103     \def\abcx{x}%
1104     \abcx
1105   \endgroup
1106 }%
1107 \Test{AA}{[{x\abc x}]}{[{xxx}]}%
1108 </test2 | test3>
1109 \end{document}
1110 </test2 | test3 | test4 | test5>

```

4 Installation

4.1 Download

Package. This package is available on CTAN¹:

CTAN:macros/latex/contrib/oberdiek/soulutf8.dtx The source file.

¹<http://ftp.ctan.org/tex-archive/>

[CTAN:macros/latex/contrib/oberdiek/soulutf8.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex soulutf8.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
soulutf8.sty      → tex/generic/oberdiek/soulutf8.sty
soulutf8.pdf      → doc/latex/oberdiek/soulutf8.pdf
test/soulutf8-test1.tex → doc/latex/oberdiek/test/soulutf8-test1.tex
test/soulutf8-test2.tex → doc/latex/oberdiek/test/soulutf8-test2.tex
test/soulutf8-test3.tex → doc/latex/oberdiek/test/soulutf8-test3.tex
test/soulutf8-test4.tex → doc/latex/oberdiek/test/soulutf8-test4.tex
test/soulutf8-test5.tex → doc/latex/oberdiek/test/soulutf8-test5.tex
soulutf8.dtx      → source/latex/oberdiek/soulutf8.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your T_EX distribution (teT_EX, mikT_EX, ...) relies on file name databases, you must refresh these. For example, teT_EX users run `texhash` or `mktextlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk soulutf8.pdf unpack_files output .
```

Unpacking with L^AT_EX. The .dtx chooses its action depending on the format:

plain T_EX: Run docstrip and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for docstrip (really, docstrip does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{soulutf8.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file ltxdoc.cfg. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
makeindex -s gind.ist soulutf8.idx
pdflatex soulutf8.dtx
```

5 References

- [1] Melchior Franz: *The soul package*; 2003/11/17;
[CTAN:macros/latex/contrib/soul/](#).
- [2] Dominique P. G. Unruh: *ucs.sty – Unicode Support*; 2004/10/17;
[CTAN:macros/latex/contrib/unicode/](#).
- [3] Frank Mittelbach, Chris Rowley: *Providing some UTF-8 support via inputenc*; 2006/03/30;
[CTAN:macros/latex/base/utf8ienc.dtx](#).

6 History

[2007/09/09 v1.0]

- First version.

7 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
\@ehc	771
\@empty	899, 905, 912
\@firstofone	665, 668
\@gobble	504, 662, 670
\@ifDefined	767, 776, 783, 784
\@ifdefinable	775
\@ifundefined	768
\@latex@error	769
\@PackageError	148
\@PackageInfo	893, 898, 904, 911
\@PackageWarningNoLine	185
\@	657, 730
\%	732
\#	656
\"	1074, 1078, 1098

<code>\@ne</code>	215, 217, 219, 221, 300, 302, 304, 306, 931, 1051	<code>\DeclareRobustCommand</code>	131, 136, 814, 825, 850
<code>\@nil</code>	404, 407, 429, 433	<code>\DeclareUnicodeCharacter</code>	804
<code>\@onelevel@sanitize</code>	153, 381, 455, 471	<code>\discretionary</code>	834, 844
<code>\@undefined</code>	58, 129	<code>\documentclass</code>	129, 756
<code>\@</code>	242, 327, 731, 1029, 1090	<code>\dp</code>	941, 951, 952
<code>\{</code>	654, 975	E	
<code>\}</code>	655, 974	<code>\empty</code>	17, 18
<code>\~</code>	1047	<code>\end</code>	750, 953, 1109
 		<code>\endcsname</code>	14, 21, 50, 66, 76, 130, 153, 380, 381, 658, 661, 664, 667, 722, 749, 761, 770, 777, 778, 785, 786, 894, 1054
A		<code>\endinput</code>	29, 128
<code>\abc</code>	1036, 1101, 1107	<code>\endlinechar</code>	4, 35, 71, 77, 89
<code>\abcx</code>	1100, 1103, 1104	<code>\errmessage</code>	711
<code>\active</code>	121	<code>\etex@unexpanded</code>	464, 486, 494, 576, 601, 626, 645
<code>\advance</code> ..	215, 217, 219, 221, 300, 302, 304, 306, 695, 703, 718, 1051	<code>\Expect</code>	932, 933, 934, 940, 941, 942, 943, 944, 950, 951, 952
<code>\afterassignment</code>	178	G	
<code>\aftergroup</code>	29	<code>\gdef</code>	852, 880
<code>\an</code>	814	H	
<code>\AtBeginDocument</code>	809	<code>\hbox</code> ..	257, 342, 588, 600, 601, 613, 625, 626, 838, 843, 900, 907, 921
B		<code>\hfil</code>	245, 330
<code>\baselineskip</code>	973	<code>\hfill</code>	966, 1006, 1015
<code>\begin</code>	897, 1068	<code>\hfuzz</code>	958
<code>\bfseries</code>	989	<code>\hsize</code>	957
<code>\body</code>	674, 678	<code>\HstringA</code>	901, 932, 933
<code>\boxA</code>	888, 902, 942, 943, 944, 945, 947, 950, 951, 952, 1003, 1004	<code>\HstringB</code>	908, 932
<code>\boxB</code>	889, 909, 942, 944, 945, 948, 951, 1004, 1014	<code>\HstringC</code>	922, 933
<code>\boxC</code>	890, 923, 943, 950, 952	<code>\ht</code>	940, 944, 945, 950, 1004
<code>\break</code>	245, 265, 267, 330, 350, 352	I	
C		<code>\if</code>	197, 234, 282, 319
<code>\c</code>	1040, 1098	<code>\ifcase</code>	362, 365, 507, 515, 524, 532, 541, 549
<code>\catcode</code>	2, 3, 5, 6, 7, 8, 9, 10, 11, 12, 13, 33, 34, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 69, 70, 72, 73, 74, 78, 79, 80, 81, 82, 83, 84, 87, 88, 90, 91, 92, 93, 97, 99, 169, 170, 172, 173, 654, 655, 656, 657, 692, 701, 709, 713, 730, 731, 732	<code>\ifcat</code>	271, 273, 356, 358
<code>\cdot</code>	838	<code>\ifdim</code>	935, 945, 969, 970, 1004
<code>\char</code>	816	<code>\ifetex@unexpanded</code>	168
<code>\chardef</code>	411, 438, 442, 446, 448	<code>\ifnum</code>	201, 203, 205, 207, 286, 288, 290, 292, 694, 702, 709, 717, 972, 980, 1046
<code>\clearpage</code>	1026	<code>\ifSOUL@ignorespaces</code>	237, 322
<code>\copy</code>	965, 1003, 1014	<code>\ifx</code>	15, 18, 21, 50, 58, 61, 129, 130, 153, 182, 210, 211, 212, 213, 214, 216, 218, 220, 227, 232, 242, 247, 251, 255, 257, 259, 265, 268, 295, 296, 297, 298, 299, 301, 303, 305, 312, 317, 327, 332, 336, 340, 342, 344, 350, 353, 412, 414, 416, 437, 441, 445, 456, 472, 478, 658, 661, 664, 667, 722
<code>\count@</code>	659, 688, 692, 694, 695, 699, 701, 702, 703, 707, 709, 712, 713, 717, 718, 1044, 1046, 1047, 1051	<code>\immediate</code>	23, 52
<code>\countdef</code>	659	<code>\IncludeTests</code>	886
<code>\csname</code>	14, 21, 50, 66, 76, 130, 153, 380, 381, 658, 661, 664, 667, 722, 749, 761, 770, 777, 778, 785, 786, 894, 1054	<code>\input</code>	141, 144, 152, 723
<code>\CurrentOption</code>	162	<code>\iterate</code>	675, 677, 679
D			
<code>\DeclareOption</code>	133, 138, 162		

K	
<code>\kern</code>	838
L	
<code>\lccode</code>	1047
<code>\leavevmode</code>	233, 318
<code>\lefthyphenmin</code>	828
<code>\linebreak</code>	268,
	270, 353, 355, 816, 818, 1028, 1091
<code>\llap</code>	974
<code>\LoadCommand</code>	723, 733
<code>\LogTests</code>	887
<code>\loop</code>	673, 689, 700, 708, 1045
<code>\lowercase</code>	1048
M	
<code>\makeatletter</code>	766, 813, 1024
<code>\makeatother</code>	790, 1067
<code>\maxdimen</code>	929, 930
<code>\mbox</code>	255,
	340, 1003, 1014, 1033, 1086, 1097
<code>\meaning</code>	156, 402, 426
<code>\MessageBreak</code>	186, 187, 188
N	
<code>\NeedsTeXFormat</code>	755
<code>\newcommand</code>	132, 137, 767, 774,
	782, 878, 891, 955, 962, 1000, 1025
<code>\newsavebox</code>	888, 889, 890
<code>\next</code>	679, 681, 683
<code>\nobreak</code>	245, 250, 330, 335, 459
<code>\nobreakspace</code>	804
<code>\noindent</code>	964, 1002, 1013
<code>\null</code>	230, 236,
	244, 249, 315, 321, 329, 334, 458
<code>\number</code>	714
O	
<code>\origshow</code>	807, 810
P	
<code>\PackageError</code>	134, 139, 148
<code>\PackageInfo</code>	26
<code>\par</code>	232, 233,
	317, 318, 963, 998, 1001, 1012, 1022
<code>\PassOptionsToPackage</code>	162
<code>\phantom</code>	976, 982, 991, 996, 1010, 1019
<code>\ProcessOptions</code>	163
<code>\protect</code> ..	559, 571, 584, 596, 609, 621
<code>\ProvidesPackage</code>	19, 67
Q	
<code>\qqquad</code>	977, 983, 993
R	
<code>\raisebox</code>	973
<code>\RangeCatcodeCheck</code>	
	706, 734, 735, 736, 737, 738,
	739, 740, 741, 742, 743, 744, 745
<code>\RangeCatcodeInvalid</code>	
	698, 726, 727, 728, 729
<code>\repeat</code> ..	673, 685, 696, 704, 719, 1052
<code>\RequirePackage</code>	164, 165, 166
<code>\RestoreCatcodes</code> ..	687, 690, 691, 746
<code>\RestoreOrg</code>	782, 906, 913,
	914, 915, 916, 917, 918, 919, 920
<code>\righthyphenmin</code>	829
<code>\rlap</code> ...	975, 981, 990, 995, 1009, 1018
S	
<code>\SavedUnexpanded</code>	753, 801
<code>\SaveOrg</code>	774, 791, 792,
	793, 794, 795, 796, 797, 798, 799
<code>\section</code>	1055
<code>\setbox</code>	900, 907, 921, 956
<code>\SetTestVBox</code>	902, 909, 923, <u>955</u>
<code>\show</code>	807, 810
<code>\showbox</code>	937, 938, 947, 948
<code>\showboxbreadth</code>	930
<code>\showboxdepth</code>	929
<code>\slash</code>	251, 336, 1089
<code>\small</code>	968, 1008, 1017
<code>\SOUL@</code>	823, 848, 876
<code>\SOUL@@</code>	197, 210, 211,
	212, 213, 214, 216, 218, 220,
	227, 232, 234, 242, 247, 251,
	255, 257, 259, 265, 268, 271,
	273, 282, 295, 296, 297, 298,
	299, 301, 303, 305, 312, 317,
	319, 327, 332, 336, 340, 342,
	344, 350, 353, 356, 358, 402, 426
<code>\SOuL@addfouroctets</code>	373, <u>492</u>
<code>\SOUL@addgroup</code>	272, 357, <u>557</u>
<code>\SOUL@addmath</code>	274, 359, <u>582</u>
<code>\SOUL@addprotect</code> ..	256, 258, 341, 343, <u>607</u>
<code>\SOuL@addthreetoctets</code>	371, <u>469</u>
<code>\SOUL@addtoken</code>	
	463, 464, 485, 486, 493, 494, <u>632</u>
<code>\SOuL@addtwooctets</code>	369, <u>453</u>
<code>\SOuL@analyzeutfviii</code>	361, <u>398</u>
<code>\SOuL@analyzeutfviiix</code>	363, <u>422</u>
<code>\SOUL@apo</code>	205,
	219, 290, 304, 524, 530, 532, 538
<code>\SOuL@AtEnd</code>	95, 96, 128, 651
<code>\SOuL@charhash</code>	394, 427, 432
<code>\SOUL@charkern</code>	845
<code>\SOuL@charthree</code>	396, 441
<code>\SOuL@chartwo</code>	395, 445
<code>\SOuL@checkutfviii</code>	401, 406
<code>\SOuL@checkutfviiix</code>	425, <u>431</u>
<code>\SOuL@cmd</code>	177, 182, 184, 193
<code>\SOuL@cmdcheck</code>	178, <u>181</u>
<code>\SOUL@comma</code>	203,
	217, 288, 302, 507, 513, 515, 521
<code>\SOuL@defsanitizedstring</code> ..	379, 383,
	384, 385, 386, 387, 388, 389, 390
<code>\SOUL@dotoken</code>	276, 366
<code>\SOUL@doword</code>	
	229, 235, 243, 248, 252, 261,
	266, 269, 314, 320, 328, 333,
	337, 346, 351, 354, 457, 473, 479
<code>\SOuL@empty</code>	397, 437
<code>\SOUL@error</code>	<u>144</u>
<code>\SOUL@eval</code>	<u>195</u>

<code>\SOUL@eventuallyexhyphen</code>	<code>\SOuL@stringnobreakspace</code>
. 230, 236, 244, 249, 253, 315,	393, 456
321, 329, 334, 338, 458, 474, 480	<code>\SOuL@stringoctets</code>
<code>\SOUL@everyexhyphen</code>	403, 407
819, 841, 864	<code>\SOuL@stringthree</code>
<code>\SOUL@everyhyphen</code>	414
818, 833, 861	<code>\SOuL@stringtwo</code>
<code>\SOUL@everylowerthan</code>	412
822, 873	<code>\SOuL@stringundeferr</code>
<code>\SOUL@everyspace</code>	428, 433
. 239, 245, 250, 270, 324,	<code>\SOuL@stringUTFviii</code>
330, 335, 355, 459, 816, 831, 855	403, 407
<code>\SOUL@everysyllable</code>	<code>\SOUL@syllable</code>
820, 832, 867	832
<code>\SOUL@everytoken</code>	<code>\SOuL@temp</code>
821, 870	179, 182, 184,
<code>\SOUL@exhyphen</code>	186, 189, 410, 412, 414, 416,
254, 339, 475, 481	436, 437, 440, 441, 444, 445,
<code>\SOUL@flushapo</code>	454, 455, 456, 470, 471, 472, 478
. 206, 212, 225, 291, 297, 310, 523	<code>\SOUL@token</code>
<code>\SOUL@flushcomma</code>	497, 500, 821
. 204, 211, 224, 289, 296, 309, 506	<code>\SOUL@word</code>
<code>\SOUL@flushgrave</code>	498, 504, 509, 511, 517,
. 208, 213, 226, 293, 298, 311, 540	519, 526, 528, 534, 536, 543,
<code>\SOUL@flushminus</code>	545, 551, 553, 561, 562, 573,
. 202, 210, 223, 287, 295, 308	574, 586, 587, 598, 599, 611,
<code>\SOUL@grave</code>	612, 623, 624, 634, 635, 643, 644
207,	<code>\SOULH</code>
221, 292, 306, 541, 547, 549, 555	852
<code>\SOUL@hyphkern</code>	<code>\soulH</code>
835, 842	850
<code>\SOUL@ignorespacesfalse</code>	<code>\soulHadd</code>
199, 284	853, 856,
<code>\SOUL@ignorespacestrue</code>	859, 862, 865, 868, 871, 874, 878
246, 331	<code>\soulHstring</code>
<code>\SOUL@minus</code>	880,
201, 215, 286, 300	881, 899, 901, 905, 908, 912, 922
<code>\SOUL@n</code> 196, 228, 233, 241, 256, 258,	<code>\soulomit</code> 259, 260, 344, 345, 1030, 1093
260, 272, 274, 276, 279, 281,	<code>\space</code> 712, 713, 721, 831, 975, 1003, 1014
313, 318, 326, 341, 343, 345,	<code>\spaceskip</code>
357, 359, 366, 369, 371, 373, 377	262, 347
<code>\SOuL@next</code>	<code>\ss</code>
. 460, 462, 467, 476, 482, 484, 490	1074, 1077
<code>\SOuL@octets</code>	<code>\strip@prefix</code>
. 362, 365, 411, 438, 442, 446, 448	156, 159
<code>\SOuL@orgDeclareOption</code>	<code>\subsection</code>
133, 138	892
<code>\SOuL@orgDeclareRobustCommand</code>	<code>\sy</code>
131, 136	825
<code>\SOuL@orgnewcommand</code>	
132, 137	
<code>\SOuL@orgPackageError</code>	
134, 139	
<code>\SOuL@orgSOUL@error</code>	
145, 149	
<code>\SOUL@postamble</code>	
817, 858	
<code>\SOUL@preamble</code>	
815, 827, 851	
<code>\SOuL@redefine</code>	
175, 195, 496,	
506, 523, 540, 557, 582, 607, 632	
<code>\SOuL@remainingtoken</code>	
501, 503	
<code>\SOuL@restorelatexcmds</code>	
135, 142	
<code>\SOUL@scan</code>	
. 196, 233, 241, 263, 281, 318,	
326, 348, 460, 476, 482, 568,	
580, 593, 605, 618, 630, 640, 649	
<code>\SOUL@sethyphenchar</code>	
836	
<code>\SOUL@setkern</code>	
835, 842, 845	
<code>\SOUL@setup</code>	
826	
<code>\SOUL@spaceskip</code>	
262, 347	
<code>\SOUL@spc</code>	
197, 234, 282, 319	
<code>\SOUL@splittoken</code>	
496	
<code>\SOUL@stop</code>	
227, 312, 496, 503	
<code>\SOuL@stringcsnameu</code>	
428, 433	
<code>\SOuL@stringemdash</code>	
392, 478	
<code>\SOuL@stringendash</code>	
391, 472	
<code>\SOuL@stringfour</code>	
416	
<code>\SOuL@stringmacrocolon</code>	
427, 432	

T

<code>\Test</code>	725, 748, 1024, 1069,
1070, 1071, 1076, 1077, 1078,	
1079, 1080, 1081, 1082, 1083,	
1084, 1085, 1086, 1087, 1088,	
1089, 1090, 1091, 1092, 1093,	
1094, 1095, 1096, 1097, 1098, 1107	
<code>\TestDriver</code>	891, 1058, 1059,
1060, 1061, 1062, 1063, 1064, 1065	
<code>\testdriver</code>	894, 900, 907, 921, 959
<code>\TestInfo</code>	925, 926, 927, 962
<code>\TestInfoVBox</code>	928, 1000
<code>\teststringA</code>	895, 900, 902
<code>\teststringB</code>	896, 907, 909, 921, 923
<code>\textbackslash</code>	1028,
1029, 1031, 1034, 1036, 1038, 1041	
<code>\textbraceleft</code>	1031, 1034, 1038, 1041
<code>\textbraceright</code>	1031, 1034, 1038, 1041
<code>\texteuro</code>	1076
<code>\texttt</code>	816, 1037, 1094
<code>\the</code>	77, 78, 79, 80, 81, 82, 83, 84,
97, 509, 511, 517, 519, 526, 528,	
534, 536, 543, 545, 551, 553,	
562, 574, 587, 599, 612, 624,	
635, 644, 692, 712, 713, 821,	
832, 934, 940, 941, 942, 943,	
944, 950, 951, 952, 975, 981, 990	
<code>\thr@@</code>	201, 286, 415, 446
<code>\TMP@EnsureCode</code>	94, 101, 102,
103, 104, 105, 106, 107, 108,	
109, 110, 111, 112, 113, 114,	

