

The **tabularht** package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2007/04/11 v2.5

Abstract

This package defines some environments that adds a height specification to tabular and array.

Contents

1	Usage	1
1.1	Option <code>vlines</code>	2
1.2	Limitations	3
1.3	Compatibility	3
1.4	Examples	3
1.4.1	Example 1	3
1.4.2	Example 2	3
2	Implementation	4
2.1	Environments	4
2.2	Options	6
2.3	Option <code>vlines</code> , driver independent stuff	7
2.4	Driver pdftex	7
2.5	DVI drivers	11
3	Installation	13
3.1	Download	13
3.2	Bundle installation	13
3.3	Package installation	14
3.4	Refresh file name databases	14
3.5	Some details for the interested	14
4	History	15
[2005/09/22 v1.0]		15
[2005/10/16 v2.0]		15
[2005/10/18 v2.1]		15
[2006/02/20 v2.2]		15
[2006/12/22 v2.3]		15
[2007/03/21 v2.4]		15
[2007/04/11 v2.5]		15
5	Index	15

1 Usage

```
\usepackage{tabularht}
```

The package provides the following environments that extend the tabular/array environment by a height specification as first argument:

- `tabularht`, `tabularht*`
- `arrayht`
- `tabularhtx` (if package `tabularx` is loaded)

The `height` argument allows a length specification, package `calc` is supported if used. This means, the tabular will have the specified height. You can also use the prefixes `to=` and `spread=`. `to=` is the default, `spread=` means, the natural height of the tabular box is changed by the length after `spread=`.

Examples:

```
\begin{tabularht}{1in}           → height is 1in
\begin{tabularht}{to=1in}        → height is 1in
\begin{tabularht}{spread=0pt} → natural height, same as \begin{tabular}
\begin{tabularht}{spread=1in} → natural height increased by 1in
```

Hint: See also package `tabularkv`, it provides an interface, where most parameters for the environments can be given by key-value pairs.

`\interrowspace{...}`

Adds space between table rows. It is essentially the same as `\noalign{\vspace{...}}`.

`\interrowfill`

Short for `\interrowspace{\fill}`

`\interrowstart ... \interrowstop`

Marker commands, useful for option `vlines`.

1.1 Option `vlines`

Warning: This stuff is experimental.

Vertical lines are interrupted, if space is inserted in `\noalign`, `\interrowspace`, `\addlinespace` (`booktabs`), between double `\hlines`. This option tries to detect and add the vertical lines. The lines in a tabular with `tabularht` support (environments of this package) are numbered from left to right. The gap that is controlled by `\interrowspace` or inbetween `\interrowstart` and `\interrowstop` is then filled with the detected vertical lines.

If only a limited selection of the lines should be drawn, the commands know an optional argument with a list of line numbers, e.g.

```
\begin{tabularht}{50mm}{|1|1|}
  Hello & World\\
  \interrowfill[1,3]
  Foo & Bar
\end{tabularht}
```

There are three lines, but the middle line is not drawn in the gap between the first and second row. Zero can be used to suppress all lines:

```
\interrowspace[0]{10mm}
```

The syntax of the commands with the optional argument with the line number list `<list>`. `<list>` is a comma separated list of numbers, `<height>` means the height specification described above with the optional prefixes `to=` or `spread=`.

```
\interrowspace [<list>] {<height>}
\interrowfill [<list>]
\interrowstart [<list>] ... \interrowstop
```

Option `vlines` is driver dependent and uses ε -TeX features.

pdftex: pdftEX in PDF mode. Here the positions of the lines are written with the help of the `\pdfsavepos` feature into the `.aux` file(s). Therefore you need two LaTeX runs to get the lines.

dvips: Here, PostScript's currentpoint is used to get the line positions. The lines are then drawn at the end of the page. Thus one L^AT_EX/dvips run is sufficient for this option.

Other drivers:

PostScript drivers: probably possible, an end of page hook would be nice.

VTeX: with GeX (PostScript interpreter) probably possible.

dvipdfm: no idea. The big problem is, how to get the current position?

1.2 Limitations

- Vertical lines are interrupted by `\noalign{\vfill}`.

1.3 Compatibility

- `array`, `delarray`, `tabularx` are supported.
- There can be problems with packages that redefine `\@array` (or `\@@array`, `\@tabarray`) and `\@arrayrule` (for option `vlines`).
- `colortbl`: it should at least work, but there isn't support for filling the gaps with color, neither the rules nor the backgrounds.

1.4 Examples

1.4.1 Example 1

```
1 <*example1>
2 \documentclass{article}
3 \usepackage{tabularht}
4
5 \begin{document}
6 \fbox{%
7   \begin{tabularht}{1in}{4in}{10{\extracolsep{\fill}}r}%
8     upper left corner & upper right corner\\%
9     \noalign{\vfill}\%\\%
10    \multicolumn{2}{c}{\multicolumn{2}{c}{bounding box}}\\%
11    \noalign{\vfill}\%\\%
12    lower left corner & lower right corner\\%
13  \end{tabularht}%
14 }
15 \end{document}
16 </example1>
```

1.4.2 Example 2

```
17 <*example2>
18 \documentclass{article}
19 \usepackage{booktabs}
20 \usepackage[dvips,vlines]{tabularht}
21
22 \begin{document}
```

```

23
24 \begin{tabularht}{spread=0pt}{|l|l|}
25   \hline
26   First&Line\\%
27   \hline
28 \interrowstart
29   \addlinespace[10mm]%
30 \interrowstop
31   \hline
32   Second&Line\\%
33 \interrowstart
34   \hline
35   \hline
36 \interrowstop
37   Third&Line\\%
38   \hline
39 \interrowspace{10mm}
40   \hline
41   Fourth&Line\\%
42   \hline
43 \end{tabularht}
44
45 \end{document}
46 </example2>

```

2 Implementation

47 <*package>

Package identification.

```

48 \NeedsTeXFormat{LaTeX2e}
49 \ProvidesPackage{tabularht}%
50 [2007/04/11 v2.5 Tabular with height specification (HO)]

```

2.1 Environments

```

51 \let\@toarrayheight\@empty
52 \let\tabH@array@init\@empty
53
54 \toks@=%
55   \begingroup
56     \long\def\x{\vcenter\fi\fi\bgroup#2\sharp#3#4@nil}%
57     \endgroup
58     \gdef\@array[##1]##2{%
59       \tabH@array@init
60       #1%
61       \vcenter\fi\fi
62       \@toarrayheight
63       \bgroup
64       \let\@toarrayheight\@empty
65       #2\sharp##3#4%
66     }%
67   }%
68   \expandafter\x\@array[#1]{#2}\@nil % hash-ok
69 }
70 \edef\tabH@patch@array{\the\toks@}
71 \def\tabH@patch@array{%
72   \ifx\@array\@array
73     \def\reserved@a{\let\@array\@array}%
74   \else
75     \let\reserved@a\relax
76   \fi
77   \tabH@patch@array
78   \reserved@a

```

```

79 }
80 \tabH@patch@@array
81
82 \@ifpackageloaded{array}{}{%
83   \AtBeginDocument{%
84     \@ifpackageloaded{array}{}{%
85       \tabH@patch@@array
86     }{}%
87   }%
88 }
89
90 \def\tabH@setheight#1{%
91   \tracingmacros=1
92   \tabH@setheight#1=\@nil
93 }
94 \def\tabH@setheight#1=#2=#3\@nil{%
95   \ifx\#2\#\%
96     \setlength{\dimen@}{#1}%
97     \edef\@toarrayheight{to\the\dimen@}%
98   \else
99     \edef\tabH@temp{\zap@space#1 \empty}%
100    \ifx\tabH@temp\tabH@to
101      \else
102        \ifx\tabH@temp\tabH@spread
103          \else
104            \PackageError{tabularht}{%
105              Unknown height specifier %
106              '\expandafter\strip@prefix\meaning\tabH@temp'%
107            }{%
108              The height dimension for tabular height can be prefixed%
109              \MessageBreak
110              with 'to=' or 'spread=', default is 'to='.%%
111            }%
112            \let\tabH@temp\tabH@to
113          \fi
114        \fi
115        \setlength{\dimen@}{#2}%
116        \edef\@toarrayheight{\tabH@temp\the\dimen@}%
117      \fi
118 }
119 \def\tabH@to{to}
120 \def\tabH@spread{spread}

```

First argument is the height of the table, then the original arguments for tabular follow.

```

121 \newenvironment{tabularht}[1]{%
122   \tabH@setheight{#1}%
123   \tabular
124 }{%
125   \endtabular
126 }
127
128 \newenvironment{tabularht*}[1]{%
129   \tabH@setheight{#1}%
130   \nameuse{tabular*}%
131 }{%
132   \nameuse{endtabular*}%
133 }
134
135 \newenvironment{tabularhtx}[1]{%
136   \tabH@setheight{#1}%
137   \tabularx
138 }{%

```

```

139  \endtabularx
140 }
141
142 \newenvironment{arrayht}[1]{%
143   \tabH@setheight{#1}%
144   \array
145 }{%
146   \endarray
147 }
148
149 \def\interrowspace{%
150   \noalign\bgroup
151   \tabH@interrowspace
152 }
153 \newcommand*\tabH@interrowspace[2][]{%
154   \tabH@vspace{#1}{#2}%
155   \egroup
156 }
157 \def\interrowfill{%
158   \noalign\bgroup
159   \tabH@interrowfill
160 }
161 \newcommand*\tabH@interrowfill[1][]{%
162   \tabH@vspace{#1}{\fill}%
163   \egroup
164 }
165 \def\tabH@vspace#1#2{%
166   \tabH@vspace@start{#1}%
167   \vspace{#2}%
168   \tabH@vspace@stop
169 }
170 \let\tabH@vspace@start\gobble
171 \let\tabH@vspace@stop\empty
172
173 \newcommand*\interrowstart{%
174   \noalign\bgroup
175   \tabH@interrowstart
176 }
177 \newcommand*\tabH@interrowstart[1][]{%
178   \tabH@vspace@start{#1}%
179   \egroup
180 }
181 \newcommand*\interrowstop{%
182   \noalign{\tabH@vspace@stop}%
183 }

```

2.2 Options

```

184 \providemode*{\tabH@driver}{}
185
186 \DeclareOption{vlines}{%
187   \let\tabH@temp\relax
188 }
189 \DeclareOption{pdftex}{}
190 \DeclareOption{dvips}{%
191   \def\tabH@driver{dvips}%
192 }
193 \ProcessOptions*\relax
194
195 \ifx\tabH@temp\relax
196 \else
197   \expandafter\endinput
198 \fi

```

```

199
200 \begingroup
201   \@ifundefined{eTeXversion}{%
202     \PackageError{tabularht}{%
203       Option 'vlines' requires eTeX%
204     }{%
205       Use of eTeX is recommended for LaTeX, see ltnews16.%%
206     }%
207   \endgroup
208   \endinput
209 }{%
210 \endgroup

```

2.3 Option vlines, driver independent stuff

```

211 \begingroup
212   \let\@addtoreset\gobbletwo
213   \newcounter{tabH@unique}%
214 \endgroup
215 \let\tabH@currenttab\empty
216
217 \def\tabH@array@init{%
218   \ifx\@toarrayheight\empty
219     % ignore vertical lines of nested tabular environments
220     \let\tabH@currenttab\empty
221   \else
222     \stepcounter{tabH@unique}%
223     \edef\tabH@currenttab{\the\c@tabH@unique}%
224   \fi
225 }
226
227 \renewcommand*\{@arrayrule}{%
228   \@addtopreamble{%
229     \hskip -.5\arrayrulewidth
230     \ifx\tabH@currenttab\empty
231     \else
232       \tabH@vrule{\tabH@currenttab}%
233     \fi
234     \begingroup
235       \expandafter\ifx\csname CT@arc@\endcsname\relax
236       \else
237         \expandafter\CT@arc@
238       \fi
239       \vline
240     \endgroup
241     \hskip -.5\arrayrulewidth
242   }%
243 }
244 \let\tabH@arrayrule\arrayrule
245 \AtBeginDocument{%
246   \@ifpackageloaded{colortbl}{%
247     \let\@arrayrule\tabH@arrayrule
248   }{%
249 }
250
251 \let\tabH@vrule\gobble

```

2.4 Driver pdftex

```

252 \RequirePackage{ifpdf}
253 \ifpdf
254   \begingroup
255     \@ifundefined{pdfsavepos}{%
256       \PackageError{tabularht}{%

```

```

257      Your pdfTeX is too old%
258  }{%
259      \string\pdfsavepos\space is missing.%
260  }%
261  \endgroup
262  \csname fi\endcsname
263  \endinput
264 }{%
265
266 \let\on@line\@empty
267 \PackageInfo{tabularht}{%
268   Using driver 'pdftex' because of pdfTeX in PDF mode%
269 }%
270 \endgroup
271
272 \protected\def\tabH@vrule#1{%
273   \if@filesw
274     \pdfsavepos
275     \protected@write\@auxout{%
276       \let\tabH@lastxpos\relax
277     }{%
278       \tabH@aux@vrule{#1}{\tabH@lastxpos}%
279     }%
280   \fi
281 }%
282
283 \def\tabH@lastxpos{\the\pdflastxpos}%
284 \def\tabH@lastypos{\the\pdflastypos}%
285
286 % The .aux file contains three commands:
287 % \tabH@aux@vrule{tabular id}{x position}
288 % \tabH@aux@vstart{tabular id}{row id}{x position}{y position}
289 % \tabH@aux@vstop{y position}
290 %
291 \AtBeginDocument{%
292   % The .aux files are read the first time before
293   % \AtBeginDocument and later at \end{document}.
294   % \tabH@aux@done is a marker to distinguish
295   % between these two readings. Only in the first
296   % case we need the \tabH@aux@... commands.
297   \let\tabH@aux@done\@empty
298   \if@filesw
299     \immediate\write\@mainaux{%
300       \percentchar\percentchar BeginProlog: tabularht%
301     }%
302     % items in the aux file are executed,
303     % if tabularht is loaded
304     % and during the aux file read at \begin{document} only
305     \immediate\write\@mainaux{%
306       \detokenize{%
307         % the \tabH@aux@... commands are needed only if
308         % tabularht is loaded with driver pdftex.
309         \@ifundefined{tabH@aux@vrule}\@secondoftwo\@firstofone
310       }%
311         % disable commands except for the first .aux files reading
312         \@ifundefined{tabH@aux@done}\@gobble\@firstofone
313       }%
314     }%
315     \let\tabH@aux@vrule\@gobbletwo
316     \let\tabH@aux@vstart\@gobblefour
317     \let\tabH@aux@vstop\@gobble
318   }%

```

```

319      }%
320      }%
321      \immediate\write\@mainaux{%
322          \percentchar\percentchar EndProlog: tabularht%
323      }%
324      \fi
325  }%
326
327  % the x positions of vrules are stored in
328  % \tabH@<tabcount>list with distinct values
329  \protected\def\tabH@aux@vrule#1#2{%
330      \@ifundefined{tabH@#1list}{%
331          \expandafter\xdef\csname tabH@#1list\endcsname{%
332              \noexpand\do{#2}%
333          }%
334      }{%
335          \begin{group}
336              \def\x{#2}%
337              \let\y\undefined
338              \let\do\tabH@do@add
339              \expandafter\xdef\csname tabH@#1list\endcsname{%
340                  \csname tabH@#1list\endcsname\empty
341                  \ifx\y\undefined
342                      \noexpand\do{\x}%
343                  \fi
344              }%
345          \endgroup
346      }%
347  }%
348  \def\tabH@do@add#1{%
349      \ifx\y\undefined
350          \ifnum#1<\x\space
351          \else
352              \expandafter\ifx\csname y\endcsname\relax\fi
353              \ifnum#1>\x\space
354                  \noexpand\do{\x}%
355              \fi
356          \fi
357      \fi
358      \noexpand\do{#1}%
359  }%
360
361  \def\tabH@vspace@start#1{%
362      \if@filesw
363          \stepcounter{tabH@unique}%
364          \edef\tabH@currentrow{\the\c@tabH@unique}%
365          \pdfsavepos
366          \protected\write\auxout{%
367              \let\tabH@lastxpos\relax
368              \let\tabH@lastypos\relax
369          }{%
370              \tabH@aux@vstart{\tabH@currenttab}{\tabH@currentrow}%
371                  {\tabH@lastxpos}{\tabH@lastypos}%
372          }%
373      \fi
374      \begin{group}
375          \edef\@{tabH@\tabH@currenttab row\tabH@currentrow}%
376          \expandafter\let\expandafter\x\csname\@ x\endcsname
377          \ifx\x\relax
378          \else
379              \expandafter\let\expandafter\y\csname\@ y\endcsname
380              \expandafter\let\expandafter\l

```

```

381     \csname tabH@\tabH@currenttab list\endcsname
382     \ifx\l\relax
383     \else
384         \def\f{\#1}%
385         \ifx\f\empty
386             \let\do\tabH@do@set
387         \else
388             \count@=\z@
389             \let\do\tabH@do@filter
390         \fi
391         \setbox\z@=\hbox{\l}%
392         \wd\z@=\z@
393         \dp\z@=\z@
394         \copy\z@
395     \fi
396 \fi
397 \endgroup
398 }%
399 \def\tabH@vspace@stop{%
400     \if@filesw
401         \pdfsavepos
402         \protected@write\auxout{%
403             \let\tabH@lastpos\relax
404         }{%
405             \tabH@aux@vstop{\tabH@lastpos}%
406         }%
407     \fi
408 }%
409 \def\tabH@do@set#1{%
410     \hbox to \z@{%
411         \hskip \dimexpr #1sp - \x sp\relax
412         \vrule \width\arrayrulewidth
413             \depth\dimexpr \y sp\relax
414         \hss
415     }%
416 }%
417 \def\tabH@do@filter{%
418     \tempswafalse
419     \advance\count@\@ne
420     \for\:=\f\do{%
421         \ifnum\:=\count@
422             \tempswatrue
423         \fi
424     }%
425     \if@tempswa
426         \expandafter\tabH@do@set
427     \else
428         \expandafter@gobble
429     \fi
430 }%
431
432 \protected\def\tabH@aux@vstart#1#2#3#4{%
433     \def\tabH@current@vstart{{#1}{#2}{#3}{#4}}%
434 }%
435 \protected\def\tabH@aux@vstop{%
436     \expandafter\tabH@aux@v\tabH@current@vstart
437 }%
438 \def\tabH@aux@v#1#2#3#4#5{%
439     \expandafter\gdef\csname tabH@#1row#2x\endcsname{#3}%
440     \expandafter\xdef\csname tabH@#1row#2y\endcsname{%
441         \the\numexpr #4 - #5\relax
442     }%

```

```

443  }%
444
445  \csname fi\endcsname
446  \endinput
447
448 \fi

```

2.5 DVI drivers

```

449 \ifx\tabH@driver\@empty
450   \PackageError{tabularht}{%
451     Missing DVI driver, option `vlines' disabled%
452   }{%
453     Supported DVI drivers: dvips.%%
454   }%
455   \expandafter\endinput
456 \fi
457
458 \def\tabH@driver@dvips{%
459   \def\tabH@literalsps##1{\special{ps:SDict begin ##1 end}}{%
460   \def\tabH@headerps##1{\special{! ##1}}{%
461   }%
462
463 \onelevel@sanitize\tabH@driver
464 \ifundefined{tabH@driver@\tabH@driver}{%
465   \PackageError{tabularht}{%
466     Unsupported driver '\tabH@driver'%
467   }{%
468     Supported DVI drivers: dvips.%%
469   }%
470   \endinput
471 }{%
472
473 \begingroup
474   \let\on@line\@empty
475   \PackageInfo{tabularht}{%
476     Using driver '\tabH@driver'%
477   }%
478 \endgroup
479 \csname tabH@driver@tabH@driver\endcsname
480
481 \protected\def\tabH@vrule#1#2\vrule#3\arrayrulewidth{%
482   #2% \fi or empty
483   % hack to get rid of maxdrift rounding of dvips,
484   % thus simulate a large motion
485   \kern1in\relax
486   \tabH@literalsps{%
487     #1 tabH.vrule %
488     Resolution neg 0 translate%
489   }%
490   \vrule#3\arrayrulewidth
491   \tabH@literalsps{Resolution 0 translate}%
492   \kern-1in\relax
493 }%
494
495 \def\tabH@vspace@start#1{%
496   \begingroup
497   \let\y\@empty
498   \for\x:=#1\do{%
499     \ifx\y\@empty
500       \edef\y{\x}%
501     \else
502       \edef\y{\y\space\x}%

```

```

503      \fi
504      }%
505      \tabH@literalps{\tabH@currenttab[\y]currentpoint exch pop}%
506 \endgroup
507 }
508 \def\tabH@vspace@stop{%
509   \tabH@literalps{%
510     currentpoint exch pop %
511     \number\dimexpr\arrayrulewidth\relax\space
512     tabH.vspace%
513   }%
514 }
515
516 \tabH@headerps{%
517   userdict begin%
518   /tabH.list 10 dict def%
519   /tabH.job [] def %
520   end%
521   /tabH.vrule{%
522     10 string cvs cvn dup tabH.list exch known{%
523       tabH.list exch dup [ exch tabH.list exch get %
524       currentpoint pop round exch true exch{%
525         % tabH.list key [ ... x true i
526         % tabH.list key [ ... false i
527         exch{%
528           % ... [ ... x i
529           2 copy lt{false}{%
530             2 copy eq{pop false}{exch true}ifelse%
531           }ifelse%
532           }{false}ifelse%
533         }forall %
534         pop%
535         lput%
536       }{%
537         tabH.list exch[currentpoint pop round]put%
538       }ifelse%
539     }bind def%
540   % <tab num> <cols array> <ytop> <ybottom> <rulewidth[sp]>
541   /tabH.vspace{%
542     userdict begin %
543     10 dict dup begin %
544       exch 65536 div Resolution mul 72.27 div %
545       % dvips uses a poor man's ceil function
546       % see dopage.c before "drawrule": (int)(... + 0.9999999)
547       0.9999999 add truncate%
548       /rulewidth exch def %
549       exch/ybottom exch def %
550       exch/ytop exch def %
551       exch/cols exch def %
552       exch/tabkey exch 10 string cvs cvn def %
553     end%
554     /tabH.job exch[exch userdict/tabH.job get aload pop]def %
555   end%
556 }bind def %
557 % Now we do the work at the end of the page.
558 % Unhappily "eop-hook" cannot be used, because "eop"
559 % executes "restore" before, so that all data are lost.
560 TeXDict begin%
561   /eop%
562   [%
563   {%
564     tabH.job{%

```

```

565      begin%
566          /colarray %
567              tabH.list tabkey known{tabH.list tabkey get}{[]}ifelse %
568          def %
569              cols length 0 eq not{%
570                  /colarray[%]
571                      cols{1 sub %
572                          dup 0 lt{pop}{%
573                              dup colarray length ge{pop}{%
574                                  colarray exch get%
575                              }ifelse%
576                          }ifelse%
577                      }forall%
578                  ]def%
579              }if %
580          colarray{%
581              % (rulewidth) == rulewidth == % debug
582              Resolution sub %
583                  ytop rulewidth ytop ybottom sub v%
584              }forall %
585          end%
586      }forall%
587      % tabH.list{== ==}forall % debug
588  }bind aload pop %
589  TeXDict /eop get aload pop%
590  ]cvx def %
591 end%
592 }
593 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/tabularht.dtx](http://ctan.org/macros/latex/contrib/oberdiek/tabularht.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/tabularht.pdf](http://ctan.org/macros/latex/contrib/oberdiek/tabularht.pdf) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:macros/latex/contrib/oberdiek/oberdiek-tds.zip](http://ctan.org/macros/latex/contrib/oberdiek/oberdiek-tds.zip)

3.2 Bundle installation

Unpacking. Unpack the `oberdiek-tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek-tds.zip -d ~/texmf
```

Script installation. Check the directory `TDSScripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

¹[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-**TEX**:

```
tex tabularht.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>tabularht.sty</code>	→ <code>tex/latex/oberdiek/tabularht.sty</code>
<code>tabularht.pdf</code>	→ <code>doc/latex/oberdiek/tabularht.pdf</code>
<code>tabularht-example1.tex</code>	→ <code>doc/latex/oberdiek/tabularht-example1.tex</code>
<code>tabularht-example2.tex</code>	→ <code>doc/latex/oberdiek/tabularht-example2.tex</code>
<code>tabularht.dtx</code>	→ <code>source/latex/oberdiek/tabularht.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your **TEX** distribution (`teTEX`, `mikTEX`, ...) relies on file name databases, you must refresh these. For example, `teTEX` users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk tabularht.pdf unpack_files output .
```

Unpacking with LATEX. The `.dtx` chooses its action depending on the format:

plain-TEX: Run `docstrip` and extract the files.

LATEX: Generate the documentation.

If you insist on using LATEX for `docstrip` (really, `docstrip` does not need LATEX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{tabularht.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdfLATEX`:

```
pdflatex tabularht.dtx
makeindex -s gind.ist tabularht.idx
pdflatex tabularht.dtx
makeindex -s gind.ist tabularht.idx
pdflatex tabularht.dtx
```

4 History

[2005/09/22 v1.0]

- First public version.

[2005/10/16 v2.0]

- Height specification allows `to=...` or `spread=...`, default is `to=`.
- Option `vlines` added, drivers `pdftex` and `dvi`.
- `\interrowspace`, `\interrowfil`, and `\interrowstart...\\interrowstop` added.

[2005/10/18 v2.1]

- Fix for package `colortbl`, but the colors of `colortbl` remain unsupported.

[2006/02/20 v2.2]

- Code is not changed.
- DTX framework.

[2006/12/22 v2.3]

- Documentation fix.
- Fix in code of option `vlines`.

[2007/03/21 v2.4]

- Fix: Counter `tabh@unique` must not be changed by `\include`.

[2007/04/11 v2.5]

- Line ends sanitized.

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\@array</code>	<i>72, 73</i> \ifpackage{loaded} <i>82, 84, 246</i>
<code>\@addtopreamble</code>	<i>228</i> \ifundefined <i>201, 255, 309, 312, 330, 464</i>
<code>\@addtoreset</code>	<i>212</i> \mainaux <i>299, 305, 321</i>
<code>\@array</code>	<i>58, 68, 72, 73</i> \nameuse <i>130, 132</i>
<code>\@arrayrule</code>	<i>227, 244, 247</i> \ne <i>419</i>
<code>\@auxout</code>	<i>275, 366, 402</i> \nil <i>56, 68, 92, 94</i>
<code>\@depth</code>	<i>413</i> \onelevel@sanitize <i>463</i>
<code>\@empty</code>	<i>51, 52, 64,</i> \percentchar <i>300, 322</i>
	<i>99, 171, 215, 218, 220, 230, 266,</i> \secondoftwo <i>309</i>
	<i>297, 340, 385, 449, 474, 497, 499</i> \sharp <i>56, 65</i>
<code>\@firstofone</code>	<i>309, 312</i> \tempswafalse <i>418</i>
<code>\@for</code>	<i>420, 498</i> \tempswatrue <i>422</i>
<code>\@gobble</code>	<i>170, 251, 312, 317, 428</i> \toarrayheight <i>51, 62, 64, 97, 116, 218</i>
<code>\@gobblefour</code>	<i>316</i> \undefined <i>337, 341, 349</i>
<code>\@gobbletwo</code>	<i>212, 315</i> \width <i>412</i>

\`	8, 10, 12, 26, 32, 37, 41, 95	\ifx	72, 95, 100, 102, 195, 218, 230, 235, 341, 349, 352, 377, 382, 385, 449, 499
A			
\a	375, 376, 379	\immediate	299, 305, 321
\addlinespace	29	\interrowfill	2, 157
\advance	419	\interrowspace	2, 39, 149
\array	144	\interrowstart	2, 28, 33, 173
\arrayrulewidth	229, 241, 412, 481, 490, 511	\interrowstop	30, 36, 181
\AtBeginDocument	83, 245, 291, 293	K	
B			
\begin	5, 7, 22, 24, 304	\kern	485, 492
C			
\c@tabH@unique	223, 364	L	
\copy	394	\l	380, 382, 391
\count@	388, 419, 421	M	
\csname	235, 262, 331, 339, 340, 352, 376, 379, 381, 439, 440, 445, 479	\meaning	106
\CT@arc@	237	\MessageBreak	109
D			
\DeclareOption	186, 189, 190	\multicolumn	10
\detokenize	306	N	
\dimen@	96, 97, 115, 116	\NeedsTeXFormat	48
\dimexpr	411, 413, 511	\newcommand	153, 161, 173, 177, 181
\do	332, 338, 342, 354, 358, 386, 389, 420, 498	\newcounter	213
\documentclass	2, 18	\newenvironment	121, 128, 135, 142
\dp	393	\noalign	9, 11, 150, 158, 174, 182
E			
\e	420, 421	\number	511
\end	13, 15, 43, 45, 293	\numexpr	441
\endarray	146	O	
\endcsname	235, 262, 331, 339, 340, 352, 376, 379, 381, 439, 440, 445, 479	\on@line	266, 474
\endinput	197, 208, 263, 446, 455, 470	P	
\endtabular	125	\PackageError	104, 202, 256, 450, 465
\endtabularx	139	\PackageInfo	267, 475
\extracolsep	7	\pdflastxpos	283
F			
\f	384, 385, 420	\pdflastypos	284
\fbox	6	\pdfsavepos	259, 274, 365, 401
\fill	7, 162	\ProcessOptions	193
G			
\gdef	58, 439	\protected	272, 329, 432, 435, 481
H			
\hbox	391, 410	\protected@write	275, 366, 402
\hline	25, 27, 31, 34, 35, 38, 40, 42	\providecommand	184
\hskip	229, 241, 411	\ProvidesPackage	49
\hss	414	R	
I			
\if@files w	273, 298, 362, 400	\renewcommand	227
\if@tempswa	425	\RequirePackage	252
\ifnum	350, 353, 421	\reserved@a	73, 75, 78
\ifpdf	253	S	
T			
\tabH@	328	\setbox	391
\tabH@setheight	92, 94	\setlength	96, 115
\tabH@array@init	52, 59, 217	\space	259, 350, 353, 502, 511
\tabH@arrayrule	244, 247	\special	459, 460
\tabH@aux@	296, 307	\stepcounter	222, 363
\tabH@aux@done	294, 297	\strip@prefix	106

```

\tabH@aux@v ..... 436, 438 \tabH@vspace@stop ..... 168, 171, 182, 399, 508
\tabH@aux@vrule .... 278, 287, 315, 329 ..... 123
\tabH@aux@vstart ... 288, 316, 370, 432 \tabular ..... 123
\tabH@aux@vstop ... 289, 317, 405, 435 \tabularx ..... 137
\tabH@current@vstart .... 433, 436 \the . 70, 97, 116, 223, 283, 284, 364, 441
\tabH@currentrow .... 364, 370, 375 \toks@ ..... 54, 70
\tabH@currenttab .... 215, 220, 223, 230, 232, 370, 375, 381, 505
\tabH@do@add ..... 338, 348 \tracingmacros ..... 91
\tabH@do@filter ..... 389, 417
\tabH@do@set ..... 386, 409, 426
\tabH@driver ..... 184, 191, 449, 463, 464, 466, 476, 479
\tabH@driver@dviips ..... 458 \vcenter ..... 56, 61
\tabH@headerps ..... 460, 516 \vfill ..... 9, 11
\tabH@interrowfill .... 159, 161 \vline ..... 239
\tabH@interrowspace .... 151, 153 \vrule ..... 412, 481, 490
\tabH@interrowstart .... 175, 177 \vspace ..... 167
\tabH@lastxpos ... 276, 278, 283, 367, 371
\tabH@lastypos ... 284, 368, 371, 403, 405
\tabH@literalps ... 459, 486, 491, 505, 509
\tabH@patch@array ..... 71, 80, 85
\tabH@patch@array ..... 70, 77
\tabH@setheight ... 90, 122, 129, 136, 143
\tabH@spread ..... 102, 120
\tabH@temp ..... 99, 100, 102, 106, 112, 116, 187, 195
\tabH@to ..... 100, 112, 119
\tabH@vrule ..... 232, 251, 272, 481
\tabH@vspace ..... 154, 162, 165
\tabH@vspace@start ..... 166, 170, 178, 361, 495

```

U

```

\usepackage ..... 3, 19, 20

```

V

```

\vcenter ..... 56, 61
\vfill ..... 9, 11
\vline ..... 239
\vrule ..... 412, 481, 490
\vspace ..... 167

```

W

```

\wd ..... 392
\write ..... 299, 305, 321

```

X

```

\x ..... 56, 68, 336, 342, 350, 353, 354, 376, 377, 411, 498, 500, 502, 505

```

Y

```

\y ..... 337, 341, 349, 379, 413, 497, 499, 500, 502, 505

```

Z

```

\z@ ..... 388, 391, 392, 393, 394, 410
\zap@space ..... 99

```