

The **tabularkv** package

Heiko Oberdiek

<oberdiek@uni-freiburg.de>

2006/02/20 v1.1

Abstract

This package adds a key value interface for tabular by the new environment **tabularkv**. Thus the T_EX source code looks better by named parameters, especially if package **tabularht** is used.

Contents

1 Usage	1
1.1 Example	2
2 Implementation	2
3 Installation	3
3.1 Some details for the interested	3
4 History	4
[2005/09/22 v1.0]	4
[2006/02/20 v1.1]	4
5 Index	4

1 Usage

```
\usepackage{tabularkv}
```

The package provides the environment **tabularkv** that takes an optional argument with tabular parameters:

width: width specification, "tabular*" is used.

x: width specification, **tabularx** is used, package **tabularx** must be loaded.

height: height specification, see package **tabularht**.

valign: vertical positioning, this option is optional;
values: top, bottom, center.

Parameter **valign** optional, the following are equivalent:

```
\begin{tabularkv}{...}, valign=top]{l}...\end{tabularkv}  
\begin{tabularkv}{...}[t]{l}...\end{tabularkv}
```

1.1 Example

```
1 <example>
2 \documentclass{article}
3 \usepackage{tabularkv}
4
5 \begin{document}
6 \fbox{%
7   \begin{tabularkv}[
8     width=4in,
9     height=1in,
10    valign=center
11   ]{@{}l@{\extracolsep{\fill}}r@{}}
12   upper left corner & upper right corner\\%
13   \noalign{\vfill}%
14   \multicolumn{2}{c}{\bounding box}\\%
15   \noalign{\vfill}%
16   lower left corner & lower right corner\\%
17 \end{tabularkv}%
18 }
19 \end{document}
20 </example>
```

2 Implementation

```
21 <package>
22 Package identification.
23 \NeedsTeXFormat{LaTeX2e}
24 \ProvidesPackage{tabularkv}%
25 [2006/02/20 v1.1 Key value interface for tabular parameters (HO)]
26 \RequirePackage{keyval}
27 \RequirePackage{tabularht}
28 \let\tabKV@star@x\empty
29 \let\tabKV@width\empty
30 \let\tabKV@valign\empty
31
32 \define@key{tabKV}{height}{%
33   \setlength{\dimen@}{#1}%
34   \edef\@toarrayheight{to\the\dimen@}%
35 }
36 \define@key{tabKV}{width}{%
37   \def\tabKV@width{#1}%
38   \def\tabKV@star@x{*}%
39 }
40 \define@key{tabKV}{x}{%
41   \def\tabKV@width{#1}%
42   \def\tabKV@star@x{x}%
43 }
44 \define@key{tabKV}{valign}{%
45   \edef\tabKV@valign{[\@car #1\@nil]}%
46 }
47 \newenvironment{tabularkv}[1][]{%
48   \setkeys{tabKV}{#1}%
49   \nameuse{%
50     tabular\expandafter\expandafter\expandafter
51   }{%
52     \expandafter\expandafter\expandafter\expandafter\expandafter\expandafter
53   }{%
54     \nameuse{endtabular\expandafter\expandafter\expandafter\expandafter\expandafter}%
55 }
```

3 Installation

CTAN. This package is available on CTAN¹:

`CTAN:macros/latex/contrib/oberdiek/tabularkv.dtx` The source file.

`CTAN:macros/latex/contrib/oberdiek/tabularkv.pdf` Documentation.

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T_EX:

```
tex tabularkv.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>tabularkv.sty</code>	→	<code>tex/latex/oberdiek/tabularkv.sty</code>
<code>tabularkv.pdf</code>	→	<code>doc/latex/oberdiek/tabularkv.pdf</code>
<code>tabularkv-example.tex</code>	→	<code>doc/latex/oberdiek/tabularkv-example.tex</code>
<code>tabularkv.dtx</code>	→	<code>source/latex/oberdiek/tabularkv.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

Refresh file databases. If your T_EX distribution (teT_EX, mikT_EX, ...) rely on file databases, you must refresh these. For example, teT_EX users run `texhash` or `mktexlsr`.

3.1 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk tabularkv.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain-T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intension:

```
latex \install=y\input{tabularkv.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex tabularkv.dtx
makeindex -s gind.ist tabularkv.idx
pdflatex tabularkv.dtx
makeindex -s gind.ist tabularkv.idx
pdflatex tabularkv.dtx
```

¹<http://ftp.ctan.org/tex-archive/>

4 History

[2005/09/22 v1.0]

- First public version.

[2006/02/20 v1.1]

- DTX framework.
- Code is not changed.

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	N
\@car	45
\@empty	28, 29, 30
\@nameuse	49, 54
\@nil	45
\@toarrayheight	34
\\"	12, 14, 16
B	P
\begin	5, 7
D	R
\define@key	32, 36, 40, 44
\dimen@	33, 34
\documentclass	2
E	S
\end	17, 19
\extracolsep	11
F	T
\fbox	6
\fill	11
M	U
\multicolumn	14
V	
\vfill	13, 15