

# The **telprint** package

Heiko Oberdiek  
<oberdiek@uni-freiburg.de>

2008/08/11 v1.10

## Abstract

Package **telprint** provides `\telprint` for formatting German phone numbers.

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	Introduction . . . . .	2
1.2	Short overview in English . . . . .	2
1.2.1	Configuration . . . . .	2
1.3	Documentation in German . . . . .	2
<b>2</b>	<b>Implementation</b>	<b>3</b>
2.1	Reload check and package identification . . . . .	3
2.2	Catcodes . . . . .	4
2.3	Package macros . . . . .	5
<b>3</b>	<b>Test</b>	<b>7</b>
3.1	Catcode checks for loading . . . . .	7
<b>4</b>	<b>Installation</b>	<b>8</b>
4.1	Download . . . . .	8
4.2	Bundle installation . . . . .	9
4.3	Package installation . . . . .	9
4.4	Refresh file name databases . . . . .	9
4.5	Some details for the interested . . . . .	9
<b>5</b>	<b>History</b>	<b>10</b>
	[1996/11/28 v1.0] . . . . .	10
	[1997/09/16 v1.1] . . . . .	10
	[1997/10/16 v1.2] . . . . .	10
	[1997/12/09 v1.3] . . . . .	10
	[2004/11/02 v1.4] . . . . .	10
	[2005/09/30 v1.5] . . . . .	10
	[2006/02/12 v1.6] . . . . .	10
	[2006/08/26 v1.7] . . . . .	11
	[2007/04/11 v1.8] . . . . .	11
	[2007/09/09 v1.9] . . . . .	11
	[2008/08/11 v1.10] . . . . .	11
<b>6</b>	<b>Index</b>	<b>11</b>

# 1 Documentation

## 1.1 Introduction

This is a very old package that I have written to format phone numbers. It follows German conventions and the documentation is mainly in German.

## 1.2 Short overview in English

L<sup>A</sup>T<sub>E</sub>X:

```
\usepackage{telprint}
\telprint{123/456-789}
```

plain-T<sub>E</sub>X:

```
\input telprint.sty
\telprint{123/456-789}
```

**\telprint**      **\telprint{...}** formats the explicitly given number. Digits, spaces and some special characters ('+', '/', '-', '(', ')', '~', ' ') are supported. Numbers are divided into groups of two digits from the right. Examples:

```
\telprint{0761/12345}      ==> 07\,61/1\,23\,45
\telprint{01234/567-89}    ==> 0\,12\,34/5\,67\leavevmode\hbox{-}89
\telprint{+49 (6221) 297}  ==> +49~(62\,21)~2\,97
```

### 1.2.1 Configuration

The output of the symbols can be configured by **\telhyphen**, **\telslash**, **\telleftparen**, **\telrightparen**, **\telplus**, **\teltilde**. Example:

```
\telslash{\,/\,}\telprint{12/34} ==> 12\,/\/,34
```

**\telspace**      **\telspace** configures the space between digit groups.

**\telnumber**    **\telnumber** only formats a number in digit groups; special characters are not recognized.

## 1.3 Documentation in German

**\telprint**      • **telprint#1**  
Der eigentliche Anwenderbefehl zur formatierten Ausgabe von Telefonnummern. Diese dürfen dabei nur als Zahlen angegeben werden (da sie tokenweise analysiert werden). Als Trenn- oder Sonderzeichen werden unterstützt: '+', '/', '-', '(', ')', '~', ' '. Einfache Leerzeichen werden erkannt und durch Tilden ersetzt, um Trennungen in der Telefonnummer zu verhindern. (Man beachte aus gleichem Grunde die **\hbox** bei '-'). Beispiele:

```
\telprint{0761/12345}      ==> 07\,61/1\,23\,45
\telprint{01234/567-89}    ==> 0\,12\,34/5\,67\leavevmode\hbox{-}89
\telprint{+49 (6221) 297}  ==> +49~(62\,21)~2\,97
```

Der Rest enthält eher Technisches:

**\telspace**      • **\telspace#1**  
Mit diesem Befehl wird der Abstand zwischen den Zifferngruppen angegeben (Default: \,). (Durch **\telspace{}** kann dieser zusätzliche Abstand abgestellt werden.)

<code>\telhyphen</code>	<ul style="list-style-type: none"> <li>• <code>\telhyphen#1</code> Dieser Befehl gibt die Art des Bindestriches, wie er ausgegeben werden soll. In der Eingabe darf jedoch nur der einfache Bindestrich stehen: <code>\telprint{123-45}</code>, jedoch NIE <code>\telprint{123--45}</code>! Kopka-Bindestrich-Fans geben an: <code>\telhyphen{\leavevmode\hbox{--}}</code></li> </ul>
<code>\telslash</code>	<ul style="list-style-type: none"> <li>• <code>\telslash#1, \telleftparen#1, \telrightparen#1, \telplus#1, \teltilde</code> Diese Befehle konfigurieren die Zeichen <code>'/'</code>, <code>'('</code>, <code>')'</code>, <code>'+'</code> und <code>'~'</code>. Sie funktionieren analog zu <code>\telhyphen</code>.</li> <li>• <code>\telnumber#1</code> Richtung interner Befehl: Er dient dazu, eine Zifferngruppe in Zweiergruppen auszugeben. Die einzelnen Zahlen werden im Tokenregister <code>\TELtoks</code> gespeichert. Abwechselnd werden dabei zwischen zwei Token (Zahlen) <code>\TELx</code> bzw. <code>\TELy</code> eingefügt, abhängig von dem wechselnden Wert von <code>\TELswitch</code>. Zum Schluss kann dann einfach festgestellt werden ob die Nummer nun eine geradzahlige oder ungeradzahlige Zahl von Ziffern aufwies. Dem entsprechend wird <code>\TELx</code> mit dem Zusatzabstand belegt und <code>\TELy</code> leer definiert oder umgekehrt. )</li> <li>• <code>\TEL...</code> interne Befehle, Technisches: <code>\TELsplit</code> dient zur Aufteilung einer zusammengesetzten Telefonnummer (Vorwahl, Hauptnummer, Nebenstelle). In dieser Implementation werden als Trennzeichen nur <code>'/'</code> und <code>'-'</code> erkannt. Die einzelnen Bestandteile wie Vorwahl werden dann dem Befehl <code>\telnumber</code> zur Formatierung uebergeben.</li> <li>• Die Erkennung von einfachen Leerzeichen ist um einiges schwieriger: Die Tokenentrennung ueber Parameter <code>#1#2</code> funktioniert nicht für einfache Leerzeichen, da TeX sie <i>niemals</i> als eigenständige Argumente behandelt! (The TeXbook, Chapter 20, p. 201)  (Anmerkung am Rande: Deshalb funktionieren die entsprechenden Tokenmakros auf S. 149 des Buches „Einführung in TeX“ von N. Schwarz (3. Aufl.) nicht, wenn im Tokenregister als erstes ein einfaches Leerzeichen steht!)</li> </ul>
<code>\telleftparen</code>	
<code>\telrightparen</code>	
<code>\telplus</code>	
<code>\teltilde</code>	
<code>\telnumber</code>	

## 2 Implementation

```
1 (*package)
```

### 2.1 Reload check and package identification

Reload check, especially if the package is not used with L<sup>A</sup>T<sub>E</sub>X.

```
2 \begingroup
3 \catcode44 12 % ,
4 \catcode45 12 % -
5 \catcode46 12 % .
6 \catcode58 12 % :
7 \catcode64 11 % @
8 \expandafter\let\expandafter\x\csname ver@telprint.sty\endcsname
9 \ifcase 0%
10 \ifx\x\relax % plain
11 \else
12 \ifx\x\empty % LaTeX
13 \else
14 1%
15 \fi
16 \fi
17 \else
18 \catcode35 6 % #
19 \catcode123 1 % {
20 \catcode125 2 % }
```

```

21 \expandafter\ifx\csname PackageInfo\endcsname\relax
22 \def\x#1#2{%
23 \immediate\write-1{Package #1 Info: #2.}%
24 }%
25 \else
26 \def\x#1#2{\PackageInfo{#1}{#2, stopped}}%
27 \fi
28 \x{telprint}{The package is already loaded}%
29 \endgroup
30 \expandafter\endinput
31 \fi
32 \endgroup

```

Package identification:

```

33 \begingroup
34 \catcode35 6 % #
35 \catcode40 12 % (
36 \catcode41 12 % )
37 \catcode44 12 % ,
38 \catcode45 12 % -
39 \catcode46 12 % .
40 \catcode47 12 % /
41 \catcode58 12 % :
42 \catcode64 11 % @
43 \catcode123 1 % {
44 \catcode125 2 % }
45 \expandafter\ifx\csname ProvidesPackage\endcsname\relax
46 \def\x#1#2#3[#4]{\endgroup
47 \immediate\write-1{Package: #3 #4}%
48 \xdef#1{#4}%
49 }%
50 \else
51 \def\x#1#2[#3]{\endgroup
52 #2[#{#3}]%
53 \ifx#1@undefined
54 \xdef#1{#3}%
55 \fi
56 \ifx#1\relax
57 \xdef#1{#3}%
58 \fi
59 }%
60 \fi
61 \expandafter\x\csname ver@telprint.sty\endcsname
62 \ProvidesPackage{telprint}%
63 [2008/08/11 v1.10 Formatting of German phone numbers (HO)]

```

## 2.2 Catcodes

```

64 \begingroup
65 \catcode123 1 % {
66 \catcode125 2 % }
67 \def\x{\endgroup
68 \expandafter\edef\csname TELAtEnd\endcsname{%
69 \catcode35 \the\catcode35\relax
70 \catcode64 \the\catcode64\relax
71 \catcode123 \the\catcode123\relax
72 \catcode125 \the\catcode125\relax
73 }%
74 }%
75 \x
76 \catcode35 6 % #
77 \catcode64 11 % @
78 \catcode123 1 % {

```

```

79 \catcode125 2 % }
80 \def\TMP@EnsureCode#1#2{%
81   \edef\TELAtEnd{%
82     \TELAtEnd
83     \catcode#1 \the\catcode#1\relax
84   }%
85   \catcode#1 #2\relax
86 }
87 \TMP@EnsureCode{33}{12}% !
88 \TMP@EnsureCode{36}{3}% $
89 \TMP@EnsureCode{40}{12}% (
90 \TMP@EnsureCode{41}{12}% )
91 \TMP@EnsureCode{42}{12}% *
92 \TMP@EnsureCode{43}{12}% +
93 \TMP@EnsureCode{44}{12}% ,
94 \TMP@EnsureCode{45}{12}% -
95 \TMP@EnsureCode{46}{12}% .
96 \TMP@EnsureCode{47}{12}% /
97 \TMP@EnsureCode{61}{12}% =
98 \TMP@EnsureCode{126}{13}% ~ (active)

```

## 2.3 Package macros

```

99 \ifx\DeclareRobustCommand\UnDeFiNeD
100   \def\DeclareRobustCommand*#1[1]{\def#1##1}%
101   \def\TELreset{\let\DeclareRobustCommand=\UnDeFiNeD}%
102   \input infwarerr.sty\relax
103   \@PackageInfo{telprint}{%
104     Macros are not robust!%
105   }%
106 \else
107   \let\TELreset=\relax
108 \fi

\telspace

109 \DeclareRobustCommand*\telspace[1]{\def\TELspace{#1}}
110 \telspace{ }$ , $ { }

\telhyphen

111 \DeclareRobustCommand*\telhyphen[1]{\def\TELhyphen{#1}}
112 \telhyphen{\leavevmode\hbox{-}}% \hbox zur Verhinderung der Trennung

\telslash

113 \DeclareRobustCommand*\telslash[1]{\def\TELslash{#1}}
114 \telslash{/}%

\telleftparen

115 \DeclareRobustCommand*\telleftparen[1]{\def\TELleftparen{#1}}
116 \telleftparen{(}%

\telrightparen

117 \DeclareRobustCommand*\telrightparen[1]{\def\TELrightparen{#1}}
118 \telrightparen{)}%

\telplus

119 \DeclareRobustCommand*\telplus[1]{\def\TELplus{#1}}
120 \telplus{+}%

\teltilde

121 \DeclareRobustCommand*\teltilde[1]{\def\TELtilde{#1}}
122 \teltilde{~}%

```

```

\TELtoks
123 \newtoks\TELtoks

\TELnumber
124 \def\TELnumber#1#2\TELnumberEND{%
125   \begingroup
126   \def\0{#2}%
127   \expandafter\endgroup
128   \ifx\0\empty
129     \TELtoks=\expandafter{\the\TELtoks#1}%
130     \ifnum\TELswitch=0 %
131       \def\TELx{\TELspace}\def\TELy{}%
132     \else
133       \def\TELx{}\def\TELy{\TELspace}%
134     \fi
135     \the\TELtoks
136   \else
137     \ifnum\TELswitch=0 %
138       \TELtoks=\expandafter{\the\TELtoks#1\TELx}%
139       \def\TELswitch{1}%
140     \else
141       \TELtoks=\expandafter{\the\TELtoks#1\TELy}%
142       \def\TELswitch{0}%
143     \fi
144   \TELnumber#2\TELnumberEND
145 \fi
146 }

\telnumber
147 \DeclareRobustCommand*\telnumber*[1]{%
148   \TELtoks={}%
149   \def\TELswitch{0}%
150   \TELnumber#1\TELnumberEND
151 }

\TELsplit
152 \def\TELsplit{\futurelet\TELfuture\TELDosplit}

\TELDosplit
153 \def\TELDosplit#1#2\TELsplitEND
154 {%
155   \def\TELsp{ }%
156   \expandafter\ifx\TELsp\TELfuture
157     \let\TELfuture=\relax
158     \expandafter\telnumber\expandafter{\the\TELtoks}~%
159     \telprint{#1#2}% Das Leerzeichen kann nicht #1 sein!
160   \else
161     \def\TELfirst{#1}%
162     \ifx\TELfirst\empty
163       \expandafter\telnumber\expandafter{\the\TELtoks}%
164       \TELtoks={}%
165     \else\if-\TELfirst
166       \expandafter\telnumber\expandafter{\the\TELtoks}\TELhyphen
167       \telprint{#2}%
168     \else\if/\TELfirst
169       \expandafter\telnumber\expandafter{\the\TELtoks}\TELslash
170       \telprint{#2}%
171     \else\if(\TELfirst
172       \expandafter\telnumber\expandafter{\the\TELtoks}\TELleftparen
173       \telprint{#2}%
174     \else\if)\TELfirst

```

```

175     \expandafter\telnumber\expandafter{\the\TELtoks}\TELrightparen
176     \telprint{#2}%
177   \else\if+\TELfirst
178     \expandafter\telnumber\expandafter{\the\TELtoks}\TELplus
179     \telprint{#2}%
180   \else\def\TELtemp{~}\ifx\TELtemp\TELfirst
181     \expandafter\telnumber\expandafter{\the\TELtoks}\TELtilde
182     \telprint{#2}%
183   \else
184     \TELtoks=\expandafter{\the\TELtoks#1}%
185     \TELsplit#2{}\TELsplitEND
186     \fi\fi\fi\fi\fi\fi\fi
187   \fi
188 }

```

\telprint

```

189 \DeclareRobustCommand*{\telprint}[1]{%
190   \TELtoks={}%
191   \TELsplit#1{}\TELsplitEND
192 }

193 \TELreset\let\TELreset=\UnDeFiNeD
194 \TELAtEnd
195 </package>

```

## 3 Test

### 3.1 Catcode checks for loading

```

196 <*test1>

197 \catcode'\{=1 %
198 \catcode'\}=2 %
199 \catcode'\#=6 %
200 \catcode'\@=11 %
201 \expandafter\ifx\csname count@\endcsname\relax
202   \countdef\count@=255 %
203 \fi
204 \expandafter\ifx\csname @gobble\endcsname\relax
205   \long\def\@gobble#1{}%
206 \fi
207 \expandafter\ifx\csname @firstofone\endcsname\relax
208   \long\def\@firstofone#1{#1}%
209 \fi
210 \expandafter\ifx\csname loop\endcsname\relax
211   \expandafter\@firstofone
212 \else
213   \expandafter\@gobble
214 \fi
215 {%
216   \def\loop#1\repeat{%
217     \def\body{#1}%
218     \iterate
219   }%
220   \def\iterate{%
221     \body
222     \let\next\iterate
223   \else
224     \let\next\relax
225   \fi
226   \next
227 }%

```

```

228 \let\repeat=\fi
229 }%
230 \def\RestoreCatcodes{}
231 \count@=0 %
232 \loop
233 \edef\RestoreCatcodes{%
234 \RestoreCatcodes
235 \catcode\the\count@=\the\catcode\count@\relax
236 }%
237 \ifnum\count@<255 %
238 \advance\count@ 1 %
239 \repeat
240
241 \def\RangeCatcodeInvalid#1#2{%
242 \count@=#1\relax
243 \loop
244 \catcode\count@=15 %
245 \ifnum\count@<#2\relax
246 \advance\count@ 1 %
247 \repeat
248 }
249 \expandafter\ifx\csname LoadCommand\endcsname\relax
250 \def\LoadCommand{\input telprint.sty\relax}%
251 \fi
252 \def\Test{%
253 \RangeCatcodeInvalid{0}{47}%
254 \RangeCatcodeInvalid{58}{64}%
255 \RangeCatcodeInvalid{91}{96}%
256 \RangeCatcodeInvalid{123}{255}%
257 \catcode'\@=12 %
258 \catcode'\=0 %
259 \catcode'\{=1 %
260 \catcode'\}=2 %
261 \catcode'\#=6 %
262 \catcode'\[=12 %
263 \catcode'\]=12 %
264 \catcode'\%=14 %
265 \catcode'\ =10 %
266 \catcode13=5 %
267 \LoadCommand
268 \RestoreCatcodes
269 }
270 \Test
271 \csname @@end\endcsname
272 \end
273 </test1>

```

## 4 Installation

### 4.1 Download

**Package.** This package is available on CTAN<sup>1</sup>:

[CTAN:macros/latex/contrib/oberdiek/telprint.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/telprint.pdf](#) Documentation.

**Bundle.** All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

---

<sup>1</sup>[ftp://ftp.ctan.org/tex-archive/](http://ftp.ctan.org/tex-archive/)



[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

*TDS* refers to the standard “A Directory Structure for T<sub>E</sub>X Files” ([CTAN:tds/tds.pdf](#)). Directories with `texmf` in their name are usually organized this way.

## 4.2 Bundle installation

**Unpacking.** Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

**Script installation.** Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

## 4.3 Package installation

**Unpacking.** The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain-T<sub>E</sub>X:

```
tex telprint.dtx
```

**TDS.** Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>telprint.sty</code>	→ <code>tex/generic/oberdiek/telprint.sty</code>
<code>telprint.pdf</code>	→ <code>doc/latex/oberdiek/telprint.pdf</code>
<code>test/telprint-test1.tex</code>	→ <code>doc/latex/oberdiek/test/telprint-test1.tex</code>
<code>telprint.dtx</code>	→ <code>source/latex/oberdiek/telprint.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`’s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

## 4.4 Refresh file name databases

If your T<sub>E</sub>X distribution (teT<sub>E</sub>X, mikT<sub>E</sub>X, ...) relies on file name databases, you must refresh these. For example, teT<sub>E</sub>X users run `texhash` or `mktextlsr`.

## 4.5 Some details for the interested

**Attached source.** The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk telprint.pdf unpack_files output .
```

**Unpacking with L<sup>A</sup>T<sub>E</sub>X.** The `.dtx` chooses its action depending on the format:

**plain-T<sub>E</sub>X:** Run `docstrip` and extract the files.

**L<sup>A</sup>T<sub>E</sub>X:** Generate the documentation.

If you insist on using L<sup>A</sup>T<sub>E</sub>X for `docstrip` (really, `docstrip` does not need L<sup>A</sup>T<sub>E</sub>X), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{telprint.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

**Generating the documentation.** You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL<sup>A</sup>T<sub>E</sub>X:

```
pdflatex telprint.dtx
makeindex -s gind.ist telprint.idx
pdflatex telprint.dtx
makeindex -s gind.ist telprint.idx
pdflatex telprint.dtx
```

## 5 History

### [1996/11/28 v1.0]

- Erste lauffähige Version.
- Nur `'-'` und `'/'` als zulässige Sonderzeichen.

### [1997/09/16 v1.1]

- Dokumentation und Kommentare (Posting in `de.comp.text.tex`).
- Erweiterung um Sonderzeichen `'(, ')`, `'+'`, `'~'` und `' '`.
- Trennungsverhinderung am `'hyphen'`.

### [1997/10/16 v1.2]

- Schutz vor wiederholtem Einlesen.
- Unter L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> Nutzung des `\DeclareRobustCommand`-Features.

### [1997/12/09 v1.3]

- Temporäre Variable eingespart.
- Posted in newsgroup `de.comp.text.tex`:  
“**Re: Generisches Markup für Telefonnummern?**”<sup>2</sup>

### [2004/11/02 v1.4]

- Fehler in der Dokumentation korrigiert.

### [2005/09/30 v1.5]

- Konfigurierbare Symbole: `'/'`, `'(, ')`, `'+'` und `'~'`.

### [2006/02/12 v1.6]

- LPPL 1.3.
- Kurze Übersicht in Englisch.
- CTAN.

---

<sup>2</sup>Url: <http://groups.google.com/group/de.comp.text.tex/msg/86b3a86140007309>

[2006/08/26 v1.7]

- New DTX framework.

[2007/04/11 v1.8]

- Line ends sanitized.

[2007/09/09 v1.9]

- Catcode section added.
- Missing docstrip tag added.

[2008/08/11 v1.10]

- Code is not changed.
- URLs updated.

## 6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\#</code> .....	199, 261
<code>\%</code> .....	264
<code>\,</code> .....	110
<code>\@</code> .....	200, 257
<code>\@PackageInfo</code> .....	103
<code>\@firstofone</code> .....	208, 211
<code>\@gobble</code> .....	205, 213
<code>\@undefined</code> .....	53
<code>\[</code> .....	262
<code>\]</code> .....	258
<code>\{</code> .....	197, 259
<code>\}</code> .....	198, 260
<code>\]</code> .....	263
<code>\countdef</code> .....	202
<code>\csname</code> .....	8, 21, 45, 61, 68, 201, 204, 207, 210, 249, 271
D	
<code>\DeclareRobustCommand</code> .....	99, 100, 101, 109, 111, 113, 115, 117, 119, 121, 147, 189
E	
<code>\empty</code> .....	12, 128, 162
<code>\end</code> .....	272
<code>\endcsname</code> .....	8, 21, 45, 61, 68, 201, 204, 207, 210, 249, 271
<code>\endinput</code> .....	30
F	
<code>\futurelet</code> .....	152
H	
<code>\hbox</code> .....	112
A	
<code>\advance</code> .....	238, 246
B	
<code>\body</code> .....	217, 221
C	
<code>\catcode</code> ...	3, 4, 5, 6, 7, 18, 19, 20, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 65, 66, 69, 70, 71, 72, 76, 77, 78, 79, 83, 85, 197, 198, 199, 200, 235, 244, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266
<code>\count@</code> .....	202, 231, 235, 237, 238, 242, 244, 245, 246
I	
<code>\if</code> .....	165, 168, 171, 174, 177
<code>\ifcase</code> .....	9
<code>\ifnum</code> .....	130, 137, 237, 245
<code>\ifx</code> .....	10, 12, 21, 45, 53, 56, 99, 128, 156, 162, 180, 201, 204, 207, 210, 249
<code>\immediate</code> .....	23, 47
<code>\input</code> .....	102, 250
<code>\iterate</code> .....	218, 220, 222
L	
<code>\leavevmode</code> .....	112
<code>\LoadCommand</code> .....	250, 267
<code>\loop</code> .....	216, 232, 243

<b>N</b>			
\newtoks	123	\TELrightparen	117, 175
\next	222, 224, 226	\telrightparen	3, <u>117</u>
<b>P</b>		\TELslash	113, 169
\PackageInfo	26	\telslash	3, <u>113</u>
\ProvidesPackage	62	\TELsp	155, 156
<b>R</b>		\TELspace	109, 131, 133
\RangeCatcodeInvalid		\telspace	2, 2, <u>109</u>
	241, 253, 254, 255, 256	\TELsplit	<u>152</u> , 185, 191
\repeat	216, 228, 239, 247	\TELsplitEND	153, 185, 191
\RestoreCatcodes	230, 233, 234, 268	\TELswitch	130, 137, 139, 142, 149
<b>T</b>		\TELtemp	180
\TELatEnd	81, 82, 194	\TELtilde	121, 181
\TELdosplit	152, <u>153</u>	\teltilde	3, <u>121</u>
\TELfirst	161,	\TELtoks	<u>123</u> , 129, 135, 138,
	162, 165, 168, 171, 174, 177, 180		141, 148, 158, 163, 164, 166,
\TELfuture	152, 156, 157		169, 172, 175, 178, 181, 184, 190
\TELhyphen	111, 166	\TELx	131, 133, 138
\telhyphen	3, <u>111</u>	\TELy	131, 133, 141
\TELleftparen	115, 172	\Test	252, 270
\telleftparen	3, <u>115</u>	\the	69, 70, 71, 72, 83, 129,
\TELnumber	<u>124</u> , 150		135, 138, 141, 158, 163, 166,
\telnumber	2, 3, <u>147</u> , 158,	\TMP@EnsureCode	80, 87, 88,
	163, 166, 169, 172, 175, 178, 181		89, 90, 91, 92, 93, 94, 95, 96, 97, 98
\TELnumberEND	124, 144, 150	<b>U</b>	
\TELplus	119, 178	\UnDeFiNeD	99, 101, 193
\telplus	3, <u>119</u>	<b>W</b>	
\telprint	2, 2, 159,	\write	23, 47
	167, 170, 173, 176, 179, 182, <u>189</u>	<b>X</b>	
\TELreset	101, 107, 193	\x	8, 10, 12, 22, 26, 28, 46, 51, 61, 67, 75