

The `twoopt` package

Heiko Oberdiek*

<heiko.oberdiek at gmail.com>

2016/05/16 v1.6

Abstract

This package provides commands to define macros with two optional arguments.

Contents

1 Usage	1
2 Implementation	2
3 Installation	3
3.1 Download	3
3.2 Bundle installation	4
3.3 Package installation	4
3.4 Refresh file name databases	4
3.5 Some details for the interested	4
4 Catalogue	5
5 History	5
[1998/10/30 v1.0]	5
[1998/10/30 v1.1]	5
[1998/11/04 v1.2]	6
[1999/04/12 v1.3]	6
[2006/02/20 v1.4]	6
[2008/08/11 v1.5]	6
[2016/05/16 v1.6]	6
6 Index	6

1 Usage

`\newcommandtwoopt` Similar to `\newcommand`, `\renewcommand` and `\providecommand` this package provides commands to define macros with two optional arguments. The names of the commands are built by appending the package name to the L^AT_EX-pendants:

```
\newcommandtwoopt  {\langle cmd \rangle} [\langle num \rangle] [\langle default1 \rangle][\langle default2 \rangle] {\langle def. \rangle}
\renewcommandtwoopt {\langle cmd \rangle} [\langle num \rangle] [\langle default1 \rangle][\langle default2 \rangle] {\langle def. \rangle}
\providecommandtwoopt {\langle cmd \rangle} [\langle num \rangle] [\langle default1 \rangle][\langle default2 \rangle] {\langle def. \rangle}
```

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

Also the `*`-forms are supported. Indeed it is better to use this ones, unless it is intended to hold whole paragraphs in some of the arguments. If the macro is defined with the `*`-form, missing braces can be detected earlier.

Example:

```
\newcommandtwoopt{\bsp}[3][AA][BB]{%
  \typeout{\string\bsp: #1,#2,#3}%
}
\bsp[aa][bb]{cc} → \bsp: aa,bb,cc
\bsp[aa]{cc}      → \bsp: aa,BB,cc
\bsp{cc}          → \bsp: AA,BB,cc
```

2 Implementation

```
1 \<package>
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{twoopt}
4 [2016/05/16 v1.6 Definitions with two optional arguments (HO)]%

\newcommandtwoopt

5 \newcommand{\newcommandtwoopt}{%
6   \ifstar{\@newcommandtwoopt*}{\@newcommandtwoopt}}%
7 }

\@newcommandtwoopt <#1>: star
                   <#2>: macro name to be defined
8 \newcommand{\@newcommandtwoopt}{%
9   \long\def\@newcommandtwoopt#1#2{%
10    \expandafter\@@newcommandtwoopt
11    \csname2\string#2\endcsname{#1}{#2}%
12 }

\@@newcommandtwoopt <#1>: help command to be defined (\2\<name>)
                   <#2>: star
                   <#3>: macro name to be defined
                   <#4>: number of total arguments
                   <#5>: default for optional argument one
                   <#6>: default for optional argument two
13 \newcommand{\@@newcommandtwoopt}{%
14   \long\def\@@newcommandtwoopt#1#2#3[#4][#5][#6]{%
15     \newcommand#2#3[1][#5]{%
16       \to@ScanSecondOptArg#1{##1}{#6}%
17     }%
18     \newcommand#2#1[#4]{%
19 }

\renewcommandtwoopt

20 \newcommand{\renewcommandtwoopt}{%
21   \ifstar{\@renewcommandtwoopt*}{\@renewcommandtwoopt}}%
22 }

\@renewcommandtwoopt <#1>: star
                   <#2>: command name to be defined
23 \newcommand{\@renewcommandtwoopt}{%
24   \long\def\@renewcommandtwoopt#1#2{%
25     \begingroup
26     \escapechar\m@ne
27     \xdef\@gtempa{\string#2}%
28   \endgroup
29   \expandafter\@ifundefined\@gtempa{%
30     \@latex@error{\noexpand#2undefined}\@ehc
```

```

31 }{}%
32 \let#2\@undefined
33 \expandafter\let\csname2\string#2\endcsname\@undefined
34 \expandafter\@newcommandtwoopt
35 \csname2\string#2\endcsname{#1}{#2}%
36 }

\providecommandtwoopt
37 \newcommand{\providecommandtwoopt}{}%
38 \@ifstar{\@providecommandtwoopt*}{\@providecommandtwoopt{}}%
39 }

\@providecommandtwoopt <#1>: star
<#2>: command name to be defined
40 \newcommand{\@providecommandtwoopt}{}
41 \long\def\@providecommandtwoopt#1#2{%
42 \begingroup
43 \escapechar\m@ne
44 \xdef\@gtempa{\string#2}%
45 \endgroup
46 \expandafter\@ifundefined\@gtempa{%
47 \expandafter\@newcommandtwoopt
48 \csname2\string#2\endcsname{#1}{#2}%
49 }{}%
50 \let\to@dummysA\@undefined
51 \let\to@dummysB\@undefined
52 \@newcommandtwoopt\to@dummysA{#1}\to@dummysB
53 }%
54 }

\to@ScanSecondOptArg <#1>: help command to be defined (\2<name>)
<#2>: first arg of command to be defined
<#3>: default for second opt. arg.
55 \newcommand{\to@ScanSecondOptArg}[3]{%
56 \ifnextchar{%
57 \expandafter#1\to@ArgOptToArgArg{#2}%
58 }{}%
59 #1{#2}{#3}%
60 }%
61 }

\to@ArgOptToArgArg
62 \newcommand{\to@ArgOptToArgArg}{}
63 \long\def\to@ArgOptToArgArg#1[#2]{\{#1\}{#2}}

64 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/twoopt.dtx](http://ctan.org/macros/latex/contrib/oberdiek/twoopt.dtx) The source file.

[CTAN:macros/latex/contrib/oberdiek/twoopt.pdf](http://ctan.org/macros/latex/contrib/oberdiek/twoopt.pdf) Documentation.

¹<http://ctan.org/pkg/twoopt>

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](#)). Directories with **texmf** in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as **texmf** tree) of your choice. Example (linux):

```
unzip oberdiek.tds.zip -d ~/texmf
```

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as **pdfatfi**. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting **docstrip** archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex twoopt.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as **texmf** tree):

```
twoopt.sty → tex/latex/oberdiek/twoopt.sty
twoopt.pdf → doc/latex/oberdiek/twoopt.pdf
twoopt.dtx → source/latex/oberdiek/twoopt.dtx
```

If you have a `docstrip.cfg` that configures and enables **docstrip**’s TDS installing feature, then some files can already be in the right place, see the documentation of **docstrip**.

3.4 Refresh file name databases

If your T_EX distribution (teT_EX, mikT_EX, ...) relies on file name databases, you must refresh these. For example, teT_EX users run **texhash** or **mktextlsr**.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run **docstrip** and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for **docstrip** (really, **docstrip** does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{twoopt.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex twoopt.dtx
makeindex -s gind.ist twoopt.idx
pdflatex twoopt.dtx
makeindex -s gind.ist twoopt.idx
pdflatex twoopt.dtx
```

4 Catalogue

The following XML file can be used as source for the [T_EX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `twoopt.xml`.

```
65 (*catalogue)
66 <?xml version='1.0' encoding='us-ascii'?>
67 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
68 <entry datestamp='$Date$' modifier='$Author$' id='twoopt'>
69   <name>twoopt</name>
70   <caption>Definitions with two optional arguments.</caption>
71   <authorref id='auth:oberdiek'>
72     <copyright owner='Heiko Oberdiek' year='1999,2006,2008'>
73       <license type='lppl1.3'>
74         <version number='1.6'>
75           <description>
76             Variants of <tt>\newcommand</tt>, <tt>\renewcommand</tt> and
77             <tt>\providecommand</tt> are provided.
78           <p/>
79             The package is part of the <xref refid='oberdiek'>oberdiek</xref>
80             bundle.
81           </description>
82           <documentation details='Package documentation'
83             href='ctan:/macros/latex/contrib/oberdiek/twoopt.pdf'>
84             <ctan file='true' path='/macros/latex/contrib/oberdiek/twoopt.dtx'>
85             <miktex location='oberdiek'>
86             <texlive location='oberdiek'>
87             <install path='/macros/latex/contrib/oberdiek/oberdiek.tds.zip'>
88           </entry>
89 </catalogue>
```

5 History

[1998/10/30 v1.0]

- The first version was built as a response to a question of Rebecca and Rowland², published in the newsgroup [comp.text.tex](#):
“Re: [Q] LaTeX command with two optional arguments?”³

[1998/10/30 v1.1]

- Improvements added in response to Stefan Ulrich⁴ in the same thread:

²Rebecca and Rowland’s email address: rebecca@astrid.u-net.com

³Url: <http://groups.google.com/group/comp.text.tex/msg/0ab1afde7b172d37>

⁴Stefan Ulrich’s email address: ulrich@cis.uni-muenchen.de

“Re: [Q] LaTeX command with two optional arguments?”⁵

[1998/11/04 v1.2]

- Fixes for LaTeX bugs 2896, 2901, 2902 added.

[1999/04/12 v1.3]

- Fixes removed because of LaTeX [1998/12/01].
- Documentation in dtx format.
- Copyright: LPPL ([CTAN:macros/latex/base/lppl.txt](#))
- First CTAN release.

[2006/02/20 v1.4]

- Code is not changed.
- New DTX framework.
- LPPL 1.3

[2008/08/11 v1.5]

- Code is not changed.
- URLs updated from [www.dejanews.com](#) to [groups.google.com](#).

[2016/05/16 v1.6]

- Documentation updates.

6 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols		N	
<code>\@@newcommandtwoopt</code>		<code>\NeedsTeXFormat</code>	2
	10 , 13 , 34 , 47 , 52	<code>\newcommand</code>	5 , 8 , 13 , 15 , 18 , 20 , 23 , 37 , 40 , 55 , 62 , 76
<code>\@ehc</code>	30	<code>\newcommandtwoopt</code>	1 , 5
<code>\@gtempa</code>	27 , 29 , 44 , 46		
<code>\@ifnextchar</code>	56	P	
<code>\@ifstar</code>	6 , 21 , 38	<code>\providecommand</code>	77
<code>\@ifundefined</code>	29 , 46	<code>\providecommandtwoopt</code>	1 , 37
<code>\@latex@error</code>	30	<code>\ProvidesPackage</code>	3
<code>\@newcommandtwoopt</code>	6 , 8		
<code>\@providecommandtwoopt</code>	38 , 40	R	
<code>\@renewcommandtwoopt</code>	21 , 23	<code>\renewcommand</code>	76
<code>\@undefined</code>	32 , 33 , 50 , 51	<code>\renewcommandtwoopt</code>	1 , 20
C			
<code>\csname</code>	11 , 33 , 35 , 48	T	
E		<code>\to@ArgOptToArgArg</code>	57 , 62
<code>\endcsname</code>	11 , 33 , 35 , 48	<code>\to@dummaryA</code>	50 , 52
<code>\escapechar</code>	26 , 43	<code>\to@dummaryB</code>	51 , 52
M		<code>\to@ScanSecondOptArg</code>	16 , 55
<code>\m@ne</code>	26 , 43		

⁵Url: <http://groups.google.com/group/comp.text.tex/msg/b8d84d4336f302c4>