

# The `overarrows` package\*

Julien Labb   
Julien.Labbe@univ-grenoble-alpes.fr

January 19, 2023

## Abstract

A LATEX package to create custom arrows over math expressions, mainly for vectors (but arrows can as well be drawn below). Arrows stretch with content, scale with math styles, and have a correct kerning when a subscript follows.

Short example:

```
\NewOverArrowCommand{\overrightharpoon}{%
  end=\rightharpoonup
}

\begin{align*}
&\&\overrightharpoon{v} \ &&\overrightharpoon{v}_{\text{subscript}} \\ 
&\&\overrightharpoon{ABCD} \ &&\overrightharpoon{*v}_{\text{subscript}}
\end{align*}
```

$$\begin{array}{c} \overrightarrow{v} \\ \overrightarrow{ABCD} \end{array} \qquad \begin{array}{c} \overrightarrow{v}_{\text{subscript}} \\ \overrightarrow{v}_{\text{subscript}} \end{array}$$

Predefined commands are also provided:

- to typeset vectors:

$$\overrightarrow{v} \quad \overrightarrow{AB},$$

- to draw arrows of various shapes above math expressions:

$$\overrightarrow{AB} \quad \overleftarrow{AB} \quad \overleftrightarrow{AB} \quad \overrightarrow{AB} \quad \overleftarrow{AB} \quad \overrightarrow{AB} \quad \overleftarrow{AB} \quad \overrightarrow{AB},$$

- to draw arrows of various shapes under math expressions:

$$\overunderline{AB} \quad \overleftarrow{AB} \quad \overleftrightarrow{AB} \quad \overline{AB} \quad \overunderline{AB} \quad \overline{AB} \quad \overleftarrow{AB} \quad \overline{AB}.$$

---

\*This document corresponds to `overarrows` v1.0.1, dated 2023/01/19.

# Contents

<b>1 Presentation of the package</b>	<b>3</b>
<b>2 Introduction</b>	<b>3</b>
2.1 Vector arrows . . . . .	3
2.2 Stack and arrow macros . . . . .	4
2.3 Extensible arrows . . . . .	4
<b>3 Quick start</b>	<b>5</b>
3.1 Loading the package <code>overarrows</code> . . . . .	5
3.2 Commands creation . . . . .	5
3.3 Start and end of the arrow . . . . .	5
3.4 Size and position of the arrow . . . . .	7
3.5 Symbols assemblage . . . . .	8
3.6 Drawing the arrow with TikZ . . . . .	10
3.7 Drawing the arrow with L <sup>A</sup> T <sub>E</sub> X picture environment . . . . .	11
<b>4 User interface</b>	<b>11</b>
4.1 Package options . . . . .	11
4.1.1 <code>esvect</code> configuration . . . . .	11
4.1.2 Predefined commands . . . . .	13
4.1.3 Other options . . . . .	14
4.2 Commands . . . . .	15
4.2.1 Macro for commands creation . . . . .	15
4.2.2 Useful macros for symbols assemblage . . . . .	16
4.2.3 Useful lengths for TikZ or <code>picture</code> environment . . . . .	17
4.2.4 Vectors macros . . . . .	18
4.2.5 Predefined commands . . . . .	18
4.3 Keys . . . . .	20
4.3.1 Arrow position and length settings . . . . .	20
4.3.2 Subscripts detection setting . . . . .	22
4.3.3 Symbols assemblage settings . . . . .	22
4.3.4 TikZ settings . . . . .	24
4.3.5 Picture environment settings . . . . .	25
4.4 Advanced commands and keys . . . . .	26
4.4.1 Advanced commands . . . . .	26
4.4.2 Advanced keys . . . . .	27
<b>5 Complements</b>	<b>28</b>
5.1 Math font issue . . . . .	28
5.2 Package dependencies . . . . .	28
5.3 Alternatives . . . . .	28
5.4 Changelog . . . . .	28
<b>6 Implementation</b>	<b>29</b>
<b>Index</b>	<b>45</b>

# 1 Presentation of the package

The `overarrows` package allows to create commands for drawing arrows over math expressions. These arrows:

- are fully customisable, at command definition, through a key-value interface;
- stretch with the content and can cover many characters, like in  $\overrightarrow{AB}$ ;
- scale with math styles<sup>1</sup>, like in  $\overrightarrow{v}_{\overline{u}\overline{w}}$ .

Commands created with the `overarrows` package are provided with a starred variant, that removes the extra end space generated by the arrow. This is particularly useful when the command is followed by a subscript. For example, the velocity of the center of mass can be written with exactly the same kerning when scalar  $v_{\text{cm}}$  or vector  $\overrightarrow{v}_{\text{cm}}$  (no extra space before the subscript, unlike the output of the unstarred variant:  $\overrightarrow{v}_{\text{cm}}$ ).

The `overarrows` package was primitively written for vectors, but in a highly customisable way. It can be used to define a large variety of arrows, using math symbols, or PGF/TikZ commands. It's also possible to create commands that draw the arrows under. Some predefined commands are provided, giving<sup>2</sup>, for arrow over:

$$\overrightarrow{\alpha + \beta} \quad \overleftarrow{\alpha + \beta} \quad \overleftrightarrow{\alpha + \beta} \quad \overrightarrow{\alpha + \beta} \quad \overleftarrow{\alpha + \beta} \quad \overbrace{\alpha + \beta} \quad \overline{\alpha + \beta} \quad \overline{\alpha + \beta}$$

and for arrow under :

$$\overleftarrow{\alpha + \beta} \quad \overleftarrow{\alpha + \beta}$$

## 2 Introduction

### 2.1 Vector arrows

Vectors are commonly typeset in bold face, or with an arrow above<sup>3</sup>. For this second convention, `TEX/LATEX` provides the command `\vec`, which accents its content (using the `\mathaccnt` command) with the character ↗ (`\mathchar"017E` in Computer Modern font). But ↗ isn't extensible, and gives:  $\vec{v}$ ,  $\vec{AB}$  or  $\vec{\text{grad}}$  (there's no command `\widevec` analogous to `\widehat`).

An extensible alternative is given by the command `\overrightarrow`, available in `TEX/LATEX`, and which is redefined by the commonly used `amsmath` package. But its arrow, built with the `\rightarrow` symbol →, is too large with the default *Computer Modern* font:  $\overrightarrow{AB}$ . Another alternative is the `esvect` package, which provides the `\vv` command and a set of custom arrows:  $\overrightarrow{AB}$ ,  $\overrightarrow{AB}$ ,  $\overrightarrow{AB}$ ,  $\overrightarrow{AB}$ ,  $\overrightarrow{AB}$ ,  $\overrightarrow{AB}$ ,  $\overrightarrow{AB}$ .

<sup>1</sup> `\displaystyle`, `\textstyle`, `\scriptstyle` and `\scriptscriptstyle`.

<sup>2</sup> Displayed here with the `old-arrows`<sup>P.14</sup> option.

<sup>3</sup> See, for example: International Organization for Standardization. (2019). *Quantities and units – Part 2: Mathematics* (ISO Standard No. 80000-2:2019). <https://www.iso.org/standard/64973.html>.

## 2.2 Stack and arrow macros

It worth looking at the definition of `\overrightarrow` command:

```
\long macro:->\mathpalette {\overarrow@ \rightarrowfill@ }
```

Three macros are used here:

`\mathpalette` adapts the output to the current math style;

`\overarrow@` is the *stack macro*, that puts the arrow above the content;

`\rightarrowfill@` is the *arrow macro*, that holds the content of the arrow.

The command `\vv` from `esvec` is defined with a very similar way, using its own stack macro (`\overvect@`) and arrow macro (`\vectfill@`).

The `overarrows` package uses the same mechanism. Arrow and stack macros are set, at command creation, through a key-value interface provided by the `pgfkeys` package (after creation, however, the command definition is static and the key-value interface is not used).

## 2.3 Extensible arrows

Arrows drawn by the commands `\overrightarrow` or `\vv` are built by joining math symbols, and made extensible by repetition of the central symbol<sup>4</sup>. Thus, the line of the macro `\overrightarrow` is made by repetition of command `\relbar` — (which simply corresponds to the minus sign), while `\vv` use its own command `\relbareda` -.

This method may generate some undesirable spacing issues, when symbols badly overlap. See, for example, the output of `\overrightarrow` (left) and `esvect` `\vv` (right) in `\scriptscriptstyle` math style (scaled by a factor 4):

While the arrow on the left lets guess where the symbols — overlap, the arrow on the right present unwanted spaces and show clearly its composition as association of the symbols -, - and →.

By default, the `overarrows` package uses the same mechanism to extend arrows according to their contents. Settings and tools are provided to perform fine tuning and avoid spacing issues. As example, see below the `\overrightarrow` and `\vv` commands, as redefined by `overarrows` (in `\scriptscriptstyle` and scaled by a factor 4):

The `overarrows` package also provides an alternative mechanism. When used, the length `\overarrowlength` is set, according to the arrow command content, and can be employed, for example, to draw arrows using PGF/TikZ or the L<sup>A</sup>T<sub>E</sub>X picture environment.

---

<sup>4</sup>Using the T<sub>E</sub>X `\cleaders` command.

## 3 Quick start

### 3.1 Loading the package `overarrows`

To load the `overarrows`, simply add in preamble, before the “`\begin{document}`”:

```
\usepackage{overarrows}
```

Options can be given, in a comma-separated list. For example, to use the predefined commands shown in the section 1, page 3, write:

```
\usepackage[allcommands, old-arrows]{overarrows}
```

This define the commands (described in section 4.2.5, page 18):

- `\overrightarrow`<sup>P. 18</sup>
- `\overleftarrow`<sup>P. 19</sup>
- `\overleftrightarrow`<sup>P. 19</sup>
- `\overrightharpoonup`<sup>P. 19</sup>
- `\overrightharpoondown`<sup>P. 19</sup>
- `\overleftharpoonup`<sup>P. 19</sup>
- `\overleftharpoondown`<sup>P. 19</sup>
- `\overbar`<sup>P. 19</sup>
- `\underrightarrow`<sup>P. 19</sup>
- `\underleftarrow`<sup>P. 19</sup>
- `\underleftrightarrow`<sup>P. 19</sup>
- `\underrightharpoonup`<sup>P. 19</sup>
- `\underrightharpoondown`<sup>P. 20</sup>
- `\underleftharpoonup`<sup>P. 20</sup>
- `\underleftharpoondown`<sup>P. 20</sup>
- `\underbar`<sup>P. 20</sup>

Note that the `old-arrows`<sup>P. 14</sup> option may give bad results, if math fonts have been changed. Simply remove the option in this case.

Many other options are available. See the complete list, page 11.

### 3.2 Commands creation

Commands are created with `\NewOverArrowCommand`<sup>P. 15</sup>. This macro take two mandatory arguments : the name of the command (without backslash), and the arrow configuration as comma-separated list of key-values. By default, a right arrow is set:

```
\NewOverArrowCommand{myovercmd}{  
$\\myovercmd{test}$}
```

$\overrightarrow{test}$

Commands are defined with a starred variant, designed to handle subscripts:

```
$ v_{\sub} \qqquad \myovercmd{v}_{\sub} \qqquad \myovercmd*{v}_{\sub} $  
v_{\sub} \overrightarrow{v}_{\sub} \overrightarrow{v}_{\sub}
```

### 3.3 Start and end of the arrow

Extremities of the arrow are set by the keys `start`<sup>P. 22</sup> and `end`<sup>P. 22</sup>. For example, an arrow starting with a hook (symbol `\lhook`) and ending with two heads (symbol `\twoheadrightarrow`) is defined by:

```
\NewOverArrowCommand{\overhooktwoheadrightarrow}{%
  start=\lhook, end=\twoheadrightarrow,
}
```

Note that `\twoheadrightarrow` must be defined, as it is not in L<sup>A</sup>T<sub>E</sub>X. This can be done with the package `amssymb`, by adding in preamble:

```
\usepackage{amssymb}
```

With the previous definition, the result of the command `\overhooktwoheadrightarrow` is faulty:

```
$ \overhooktwoheadrightarrow{v} \qquad \overhooktwoheadrightarrow{AB} $
```

The problem comes from symbols junction and the trimming used to obtain their overlap. It can be solved with the keys `trim start`<sup>P. 23</sup> and `trim end`<sup>P. 23</sup>, which are numbers and set the corresponding trimming in math units (typically 1/18 em). Appropriate values gives better results:

```
\NewOverArrowCommand{\overhooktwoheadrightarrow}{%
  start=\lhook, end=\twoheadrightarrow,
  trim start=1.5, trim end=2,
}
$ \overhooktwoheadrightarrow{v} \qquad \overhooktwoheadrightarrow{AB} $
```

If the math font differs from the default *Computer Modern*, the central part of the arrow may have inappropriate position or line width. This is because the default symbol used for the arrow line is `\relbar` - from the `esvect` package. If needed, try to set the `middle`<sup>P. 22</sup> key with the symbol `\relbar` —. The trimming should also be adapted:

```
\NewOverArrowCommand{\overhooktwoheadrightarrow}{%
  start=\lhook, end=\twoheadrightarrow, middle=\relbar, %
  trim start=0, trim end=3, trim middle=5,
}
$ \overhooktwoheadrightarrow{v} \qquad \overhooktwoheadrightarrow{AB} $
```

Finding the correct values for `trim start`<sup>P. 23</sup>, `trim end`<sup>P. 23</sup> and `trim middle`<sup>P. 23</sup> may need many trials. For this purpose, the macro `\TestOverArrow`<sup>P. 16</sup> displays the result of a command for different lengths and math styles:

```
\TestOverArrow{\overhooktwoheadrightarrow}
```

\displaystyle	\textstyle	\scriptstyle	\scriptscriptstyle
$\overleftrightarrow{v}$	$\overleftrightarrow{v}$	$\overleftrightarrow{v}$	$\overleftrightarrow{v}$
$\overleftrightarrow{AB}$	$\overleftrightarrow{AB}$	$\overleftrightarrow{AB}$	$\overleftrightarrow{AB}$
$\overleftrightarrow{\text{grad}}$	$\overleftrightarrow{\text{grad}}$	$\overleftrightarrow{\text{grad}}$	$\overleftrightarrow{\text{grad}}$
$\overleftrightarrow{\text{my long vector}}$	$\overleftrightarrow{\text{my long vector}}$	$\overleftrightarrow{\text{my long vector}}$	$\overleftrightarrow{\text{my long vector}}$

### 3.4 Size and position of the arrow

A command `\OverRightarrow`, built with the symbols `\Relbar` = and `\Rightarrow` ⇒, gives:

```
\NewOverArrowCommand{\OverRightarrow}{%
  start=\Relbar,
  middle=\Relbar,
  end=\Rightarrow,
  trim=4,
}
$ \OverRightarrow{v} \qquad \OverRightarrow{AB} $
```

$\overrightarrow{v}$      $\overrightarrow{AB}$

The key `trim` → P. 23 sets `trim start` → P. 23, `trim middle` → P. 23 and `trim end` → P. 23 with the same value.

The previous arrow is visually too big. The macro `\smallermathstyle` → P. 17 allows to obtain a better result:

```
\NewOverArrowCommand{\OverRightarrow}{%
  start={\smallermathstyle\Relbar},
  middle={\smallermathstyle\Relbar},
  end=\Rightarrow,
  trim=4,
}
$ \OverRightarrow{v} \qquad \OverRightarrow{AB} $
```

$\overrightarrow{v}$      $\overrightarrow{AB}$

Note that `\smallermathstyle` → P. 17 should not be used for `end` → P. 22, because this last is formatted with the same math style as `start` → P. 22.

It would be better to add an extra space between the arrow and the content of the command. This can be done with the key `space after arrow` → P. 22:

```
\NewOverArrowCommand{\OverRightarrow}{%
  start={\smallermathstyle\Relbar},
  middle={\smallermathstyle\Relbar},
  end=\Rightarrow,
  trim=4,
  space after arrow=0.25ex,
}
$ \OverRightarrow{v} \qquad \OverRightarrow{AB} $
```

$\overrightarrow{v}$      $\overrightarrow{AB}$

Default arrows are slightly shifted to the right. For a left arrow, this should be reversed, using the keys `shift left` → P. 21 and `shift right` → P. 21. These keys set the corresponding shifts, in math units. Example:

```
\NewOverArrowCommand{\OverLeftarrow}{%
  start={\smallermathstyle\Leftarrow},
  middle={\smallermathstyle\Relbar},
  end=\Relbar,
  trim=4,
  space after arrow=0.25ex,
  shift left=0, shift right=2,
}
$ \OverLeftarrow{v} \qquad \OverLeftarrow{AB} $
```

$$\overleftarrow{v} \qquad \overleftarrow{AB}$$

Finally, the key `arrow under`<sup>P.20</sup> places the arrow below the content, instead of above (and `space before arrow`<sup>P.22</sup> sets the space upon it):

```
\NewOverArrowCommand{\OverLeftRightarrow}{%
  start={\smallermathstyle\Leftarrow},
  middle={\smallermathstyle\Relbar},
  end=\Rightarrow,
  trim=4,
  arrow under,
  space before arrow=0.5ex,
  shift left=0, shift right=0,
}
$ \OverLeftRightarrow{v} \qquad \OverLeftRightarrow{AB} $
```

$$v \qquad \overleftarrow{AB}$$

### 3.5 Symbols assemblage

Many L<sup>A</sup>T<sub>E</sub>X math symbols are built by assemblage, using the macro `\joinrel`<sup>5</sup> which remove 3 math units of horizontal space. The `overarrows` package provides a flexible version of `\joinrel`, called `\xjoinrel`<sup>P.16</sup>, which remove an arbitrary number of math units, given as optional argument.

Symbols association is then simple. As example, one can define a triple tail macro `\tttail` from the symbol `\succ` :

```
\newcommand*{\tttail}{\succ\xjoinrel[10]\succ\xjoinrel[10]\succ}
$ \tttail $
```

$$\succ\!\succ\!\succ$$

Thus defined, the macro `\tttail` can be used in arrow definition:

<sup>5</sup>For example, the symbol `\models` = is defined as `\mathrel{|}\joinrel\Relbar` and corresponds to the assemblage of a vertical line | and the symbol `\Relbar` =. The command `\mathrel` modifies the spacing according to the math relation class ; `\Relbar` corresponds to the equal sign (it's definition is `\mathrel{=}`).

```
\NewOverArrowCommand{\overrightarrowtail}{%
  start={\tttail},
  end={\rightarrow},
  trim start=12,
  shift left=0, shift right=0,
  space after arrow=.2ex,
  min length=24,
}
$ \overrightarrowtail{v} \qquad \overrightarrowtail{AB} $
```



Here the `min length`<sup>P.20</sup> key was added to ensure a minimum length (in math units) when the content of the command is small (as for a single character).

The previous arrow would be better with a smaller tail, and this can be done with the macro `\smallermathstyle`<sup>P.17</sup>. But a small tail and a normal sized head are not aligned; as `{\smallermathstyle\ttail}\xjoinrel[8]\rightarrow` gives:



The solution comes from the command `\vcenter` which centers materials on math axis. The tail must then be wrapped in a `\hbox`:

```
\NewOverArrowCommand{\overrightarrowtail}{%
  start={\vcenter{\hbox{\smallermathstyle\ttail}}},
  end={\rightarrow},
  trim start=12,
  shift left=0, shift right=0,
  space after arrow=.2ex,
  min length=24,
}
$ \overrightarrowtail{v} \qquad \overrightarrowtail{AB} $
```



Text symbols, namely symbols that are not defined in math mode, can also be used. They should yet be enclosed in the `\text` macro, from the `amsmath` package, to be correctly displayed and correctly scaled according to math style. With, for example, the arrow heads given by the symbols 40 and 41 of the *lasy* font:

```
\newcommand*{\leftarrowhead}{\usefont{U}{lasy}{m}{n}\symbol{40}}
\newcommand*{\rightarrowhead}{\usefont{U}{lasy}{m}{n}\symbol{41}}
\NewOverArrowCommand{\overleftarrowtail}{%
  start=\text{\rightarrowhead},
  end=\text{\leftarrowhead},
  trim start=0.7, trim end=0.7,
  min length=20,
  shift leftright=-2,
}
$ \overleftarrowtail{AB} \qquad \overleftarrowtail{AB} $
```



### 3.6 Drawing the arrow with TikZ

In addition to the default method presented previously (assemblage of symbols, as described in section 2.3, page 4), the `overarrows` package has an alternative method to draw the arrow. This one allows the use of graphic languages such as PGF/TikZ.

Drawing arrows with TikZ requires to load the `tikz` package and its library `arrows.meta`. This can be simply done by passing the `tikzP.15` option to the `overarrows` package<sup>6</sup>:

```
\usepackage[tikz]{overarrows}
```

To use PGF/TikZ language, the optional argument `tikz` must be passed to `\NewOverArrowCommandP.15`. TikZ picture are not extensible. That's why the `overarrows` package provides three lengths that can be used in TikZ commands:

- `\overarrowlengthP.17` for the arrow length,
- `\overarrowthicknessP.17` and `\overarrowssmallerthicknessP.18` for the arrow thickness.

These lengths are computed at each utilisation of a command created with the `tikz` optional argument.

Without any other configuration, a right arrow is drawn:

```
\NewOverArrowCommand[tikz]{\overrightarrow}{}
$ \overrightarrow{v} \qquad \overrightarrow{AB} $
```



Keys to use Tikz are described in section 4.3.4, page 24. Main keys are: `tikz optionsP.24`, `path optionsP.25` and `pathP.25`. It's also possible to append settings with `add tikz optionsP.25` and `add path optionsP.25`. The full TikZ command used to draw the arrow can as well be entirely redefined with the key `tikz commandP.25`.

Here is an example of an arrow drawn with TikZ<sup>7</sup>:

```
\NewOverArrowCommand[tikz]{\overarchedleftarrow}{%
  add tikz options={y=\overarrowlength},
  add tikz options={line width=\overarrowssmallerthickness},
  path options={arrows={<[scale=0.5]->[scale=0.5]}},
  path={(0,0) arc (-250:70:0.5 and 0.1)},
  center arrow,
  min length=25,
  space after arrow=0.4ex,
}
$ \overarchedleftarrow{v} \qquad \overarchedleftarrow{ABCD} $
```



<sup>6</sup>Note that the `tikzP.15` option isn't mandatory to use TikZ commands in `overarrows`. The `tikz` package and its library `arrows.meta` can be loaded independently.

<sup>7</sup>TikZ arrows are very powerfull, but much slower to draw than the default method using assemblage of math symbols.

### 3.7 Drawing the arrow with L<sup>A</sup>T<sub>E</sub>X picture environment

As well as TikZ, the L<sup>A</sup>T<sub>E</sub>X `picture` environment can be used to draw the arrow. For this, the optional argument `picture` must be passed to `\NewOverArrowCommand`<sup>P. 15</sup>. Like for TikZ, the three lengths `\overarrowlength`<sup>P. 17</sup>, `\overarrowthickness`<sup>P. 17</sup> and `\overarrowsmallerthickness`<sup>P. 18</sup> can be used in `picture` commands. By default, a right vector is drawn:

```
\NewOverArrowCommand[picture]{overpictarrow}{}  
$ \overpictarrow{v} \qquad \overpictarrow{AB} $
```



If `overarrows` is loaded with the option `pstarrow`<sup>P. 15</sup>, the package `pict2e` is used and a PSTricks style vector arrows is set. This gives:

```
\NewOverArrowCommand[picture]{overpictarrow}{}  
$ \overpictarrow{v} \qquad \overpictarrow{AB} $
```



Keys to use L<sup>A</sup>T<sub>E</sub>X `picture` environment are described in section 4.3.5, page 25. The main keys are `picture command`<sup>P. 26</sup>, `geometry`<sup>P. 26</sup> an `line thickness`<sup>P. 26</sup>. Here is an example:

```
\NewOverArrowCommand[picture]{overbandedarrow}{  
    picture command={%  
        \qbezier  
        (0.0\overarrowlength,0)  
        (0.5\overarrowlength,0)  
        (0.9\overarrowlength,0.2\overarrowlength)  
        \put(0.9\overarrowlength,0.2\overarrowlength){  
            \vector(2,1){0.2\overarrowlength}}  
    },  
    geometry={(0.0\overarrowlength,0.4\overarrowlength)(0,0)},  
    line thickness={\overarrowsmallerthickness},  
    center arrow,  
    space after arrow=0.4ex,  
}  
$ \overbandedarrow{v} \qquad \overbandedarrow{AB} $
```



## 4 User interface

### 4.1 Package options

The `overarrows` package accepts many options, given as a comma-separated list `<options>` at package loading: `\usepackage[<options>]{overarrows}`.

The option `esvect` is set by default. This can be overridden with `noesvect`.

#### 4.1.1 esvect configuration

`esvect`

Loads the `esvect` package and redefines its vector commands  $\vec{v}$ <sup>P.18</sup> through the `overarrows` mechanism. Original `esvect`  $\vec{v}$  macro is still available with  $\text{\esvect}\vec{v}$ <sup>P.18</sup>.

The `esvect` package provides the symbol  $\relbar$  which is smaller and often more flexible than the classic one  $\relbar$ .  $\relbar$  fits with the standard *Computer Modern* math font, but can be unsuitable with other fonts.

The `esvect` package also provides the right arrow command  $\f1dr$ . The shape of the arrow depends on the option passed to the `esvect` package:  $\rightarrow$  (option `a`),  $\rightarrow$  (option `b`),  $\rightarrow$  (option `c`),  $\rightarrow$  (option `d`),  $\rightarrow$  (option `e`),  $\rightarrow$  (option `f`),  $\rightarrow$  (option `g`) or  $\rightarrow$  (option `h`). Note that by default `overarrows` loads the `esvect` package with the option `f` (while `esvect` default is `d`). This can be changed with one of the eight options described below: `esvecta`, `esvectb`, `esvectc`, `esvectd`, `esvecte`, `esvectf`, `esvectg` and `esvecth`.

This option is set by default and can be unset with `noesvect`.

#### **noesvect**

Prevents the loading of the `esvect` package and the definition of the command  $\vec{v}$ <sup>P.18</sup>.

#### **esvecta**

Loads the `esvect` package with the `a` option.

$\f1dr$  corresponds to the symbol  $\rightarrow$ .  $\vec{v}$  command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

#### **esvectb**

Loads the `esvect` package with the `b` option.

$\f1dr$  corresponds to the symbol  $\rightarrow$ .  $\vec{v}$  command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

#### **esvectc**

Loads the `esvect` package with the `c` option.

$\f1dr$  corresponds to the symbol  $\rightarrow$ .  $\vec{v}$  command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

#### **esvectd**

Loads the `esvect` package with the `d` option.

$\f1dr$  corresponds to the symbol  $\rightarrow$ .  $\vec{v}$  command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

#### **esvecte**

Loads the `esvect` package with the `e` option.

$\f1dr$  corresponds to the symbol  $\rightarrow$ .  $\vec{v}$  command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

#### **esvectf**

Loads the `esvect` package with the `f` option.

$\f1dr$  corresponds to the symbol  $\rightarrow$ .  $\vec{v}$  command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

#### **esvectg**

Loads the `esvect` package with the `g` option.

$\f1dr$  corresponds to the symbol  $\rightarrow$ .  $\vec{v}$  command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

### **esvecth**

Loads the esvect package with the h option.

\fldr corresponds to the symbol . \vv command gives :  $\vec{v}$   $\overrightarrow{AB}$   $\overrightarrow{\text{grad}}$ .

#### **4.1.2 Predefined commands**

The overarrows package provides sixteen predefined commands, eight with the arrow over, and eight with the arrow under. By default, these commands are not defined, and must be activated by the corresponding option. Beware that commands are created without checking if already defined by another package (\overleftarrow, \overrightarrow, \overleftrightarrow, \underleftarrow, \underrightarrow and \underleftrightarrow are, for example, part of the amsmath package).

Three options are also available to define set of commands.

#### **Set of commands**

##### **allcommands**

Defines all sixteen predefined commands.

##### **overcommands**

Defines all eight predefined commands with arrow over.

##### **undercommands**

Defines all eight predefined commands with arrow under.

#### **Over arrows**

##### **overrightarrow**

Defines the \overrightarrow<sup>P. 18</sup> command:  $\vec{v}$ ,  $\overrightarrow{AB}$ ,  $\overrightarrow{\text{grad}}$ .

##### **overleftarrow**

Defines the \overleftarrow<sup>P. 19</sup> command:  $\overleftarrow{v}$ ,  $\overleftarrow{AB}$ ,  $\overleftarrow{\text{grad}}$ .

##### **overleftrightarrow**

Defines the \overleftrightarrow<sup>P. 19</sup> command:  $\overleftrightarrow{v}$ ,  $\overleftrightarrow{AB}$ ,  $\overleftrightarrow{\text{grad}}$ .

##### **overrightharpoonup**

Defines the \overrightharpoonup<sup>P. 19</sup> command:  $\vec{v}$ ,  $\overrightarrow{AB}$ ,  $\overrightarrow{\text{grad}}$ .

##### **overrightharpoondown**

Defines the \overrightharpoondown<sup>P. 19</sup> command:  $\overleftarrow{v}$ ,  $\overleftarrow{AB}$ ,  $\overleftarrow{\text{grad}}$ .

##### **overleftharpoonup**

Defines the \overleftharpoonup<sup>P. 19</sup> command:  $\overleftarrow{v}$ ,  $\overleftarrow{AB}$ ,  $\overleftarrow{\text{grad}}$ .

### **overleftharpoondown**

Defines the  $\overleftharpoondown^{\rightarrow P.19}$  command:  $\overline{v}$ ,  $\overline{AB}$ ,  $\overline{\text{grad}}$ .

### **overbar**

Defines the  $\overbar^{\rightarrow P.19}$  command:  $\overline{v}$ ,  $\overline{AB}$ ,  $\overline{\text{grad}}$ .

## **Under arrows**

### **underrightarrow**

Defines the  $\underrightarrow^{\rightarrow P.19}$  command:  $\underline{v}$ ,  $\underline{AB}$ ,  $\underline{\text{grad}}$ .

### **underleftarrow**

Defines the  $\underleftarrow^{\rightarrow P.19}$  command:  $\underline{\underline{v}}$ ,  $\underline{\underline{AB}}$ ,  $\underline{\underline{\text{grad}}}$ .

### **underleftrightarrow**

Defines the  $\underleftrightarrow^{\rightarrow P.19}$  command:  $\underline{\leftrightarrow}v$ ,  $\underline{\leftrightarrow}AB$ ,  $\underline{\leftrightarrow}\text{grad}$ .

### **underrightharpoonup**

Defines the  $\underrightharpoonup^{\rightarrow P.19}$  command:  $\underline{v}$ ,  $\underline{AB}$ ,  $\underline{\text{grad}}$ .

### **underrightharpoondown**

Defines the  $\underrightharpoondown^{\rightarrow P.20}$  command:  $\underline{\overline{v}}$ ,  $\underline{\overline{AB}}$ ,  $\underline{\overline{\text{grad}}}$ .

### **underleftharpoonup**

Defines the  $\underleftharpoonup^{\rightarrow P.20}$  command:  $\underline{\underline{v}}$ ,  $\underline{\underline{AB}}$ ,  $\underline{\underline{\text{grad}}}$ .

### **underleftharpoondown**

Defines the  $\underleftharpoondown^{\rightarrow P.20}$  command:  $\underline{\underline{\overline{v}}}$ ,  $\underline{\underline{\overline{AB}}}$ ,  $\underline{\underline{\overline{\text{grad}}}}$ .

### **underbar**

Defines the  $\underbar^{\rightarrow P.20}$  command:  $\underline{v}$ ,  $\underline{AB}$ ,  $\underline{\text{grad}}$ .

### **4.1.3 Other options**

#### **old-arrows**

Loads the `old-arrows` package with its option `old`. This provides the symbols  $\varleftarrow$   $\leftarrow$  and  $\varrightarrow$   $\rightarrow$ , used then by default for predefined command.

When the `old-arrows` option is set, the commands  $\overrightrightarrow^{\rightarrow P.18}$ ,  $\overleftarrow^{\rightarrow P.19}$ ,  $\overleftarrow{}^{\rightarrow P.19}$ ,  $\overrightarrow{}^{\rightarrow P.19}$ ,  $\underrightarrow{}^{\rightarrow P.19}$ ,  $\underleftarrow{}^{\rightarrow P.19}$  and  $\underrightarrow{}^{\rightarrow P.19}$  give respectively :  $\overrightarrow{AB}$ ,  $\overleftarrow{AB}$ ,  $\overleftrightarrow{AB}$ ,  $\underline{AB}$ ,  $\underline{\overline{AB}}$  and  $\underline{\overleftrightarrow{AB}}$

## **tikz**

Loads the package `tikz` with its library `arrows.meta`.

Note that TikZ arrows, drawn with the `tikz` method, are always available, even if this option is not set, provided the `tikz` package and its library are loaded independently.

## **pstarrows**

Loads the `pict2e` package, with its option `pstarrows`. Vectors using `LATEX picture` environment gives then  $\overrightarrow{AB}$  instead of  $\vec{AB}$ .

Note that this affect all vectors drawn in `LATEX picture` environments, and that this setting can be changed on the fly with the commands `\pstarrows` and `\ltxarrows` from the `pict2e` package.

## **subscripts**

Sets the default value of the key `detect subscripts`<sup>P.22</sup> to `true`.

This option also impacts the command `\vv`<sup>P.18</sup> and all predefined commands, so that they automatically use their starred variant when a subscript follows.

## **debug**

Writes the meaning of defined commands in `LATEX log`.

## 4.2 Commands

### 4.2.1 Macro for commands creation

```
\NewOverArrowCommand[⟨method⟩]{⟨name⟩}{⟨keys⟩}
\RenewOverArrowCommand[⟨method⟩]{⟨name⟩}{⟨keys⟩}
\ProvideOverArrowCommand[⟨method⟩]{⟨name⟩}{⟨keys⟩}
\DeclareOverArrowCommand[⟨method⟩]{⟨name⟩}{⟨keys⟩}
```

Creates the command `\⟨name⟩` and its starred variant `\⟨name⟩*`. The starred variant `\⟨name⟩*` removes the extra end space generated by the arrow, which is suitable, as example, when a subscript follows.

`\NewOverArrowCommand` raises an error if `\⟨name⟩` is already defined.

`\RenewOverArrowCommand` raises an error if `\⟨name⟩` is undefined.

`\ProvideOverArrowCommand` sets `\⟨name⟩` if the command is undefined and does nothing if it is already defined, without raising any error.

`\DeclareOverArrowCommand` sets `\⟨name⟩`, whether the command is already defined or not, without raising any error.

The `⟨method⟩` used to draw the arrow must be:

`symb` to draw the arrow by symbols assemblage (default);

`tikz` to draw the arrow with PGF/TikZ;

`picture` to draw the arrow with the `LATEX picture` environment.

With no  $\langle method \rangle$  argument, the `symb` method is chosen.

$\langle keys \rangle$  is a comma-separated list of keys-values. Available keys depends of the  $\langle method \rangle$  chosen and are described in section 4.3, page 20.

```
\NewOverArrowCommand[tikz]{myoverarrow}{arrows={Bar-Bar}, center arrow}
$ \myoverarrow{v} \qquad \myoverarrow{ABCD} $
```

```
\TestOverArrow[⟨pattern⟩]{⟨name⟩}
\TestOverArrow*[⟨pattern⟩]{⟨name⟩}
```

Displays the result of the command  $\langle name \rangle$  for patterns of various lengths and for the four math styles. A custom  $\langle pattern \rangle$  can be added to the predefined ones.

The starred variant `\TestOverArrow*` displays a full report, including kerning tests of the commands `\langle name \rangle` and `\langle name \rangle*`.

```
\TestOverArrow*[my~pattern]{vv}
```

### Test of `\vv` and `\vv*` macros

#### `\vv` for different math styles

<code>\displaystyle</code>	<code>\textstyle</code>	<code>\scriptstyle</code>	<code>\scriptscriptstyle</code>
$\vec{v}$	$\vec{v}$	$\vec{v}$	$\vec{v}$
$\overrightarrow{AB}$	$\overrightarrow{AB}$	$\overrightarrow{AB}$	$\overrightarrow{AB}$
$\overrightarrow{\text{grad}}$	$\overrightarrow{\text{grad}}$	$\overrightarrow{\text{grad}}$	$\overrightarrow{\text{grad}}$
$\overrightarrow{\text{my long vector}}$	$\overrightarrow{\text{my long vector}}$	$\overrightarrow{\text{my long vector}}$	$\overrightarrow{\text{my long vector}}$
$\overrightarrow{\text{my pattern}}$	$\overrightarrow{\text{my pattern}}$	$\overrightarrow{\text{my pattern}}$	$\overrightarrow{\text{my pattern}}$

#### `\vv` kerning

$$\vec{t}_{\vec{u}\vec{v}} \quad \vec{i}_0 \quad \vec{v} = \vec{v}_x + \vec{v}_y + \vec{v}_z = v_x \vec{i} + v_y \vec{j} + v_z \vec{k}$$

#### `\vv*` kerning

$$\vec{t}_{\vec{u}\vec{v}} \quad \vec{i}_0 \quad \vec{v} = \vec{v}_x + \vec{v}_y + \vec{v}_z = v_x \vec{i} + v_y \vec{j} + v_z \vec{k}$$


## 4.2.2 Useful macros for symbols assemblage

Math symbols assemblage is the default method used to draw arrows. The macros `\xjoinrel` and `\smallermathstyle` are designed to help combine and format math symbols.

`\xjoinrel[⟨number⟩]`

Removes an horizontal space of  $\langle number \rangle$  math units (3.5 mu by default). Must be used in math mode. Useful to assemble math symbols and create new ones.

```
\newcommand*{\triplebar}{\Relbar\xjoinrel[14]\relbar}
\newcommand*{\triplebararrow}{\Relbar\xjoinrel[15]\rightarrow}
\scalebox{2}{$ \triplebar \quad \triplebararrow $}\par
\scalebox{2}{$ \triplebar\xjoinrel\triplebararrow $}
```



### \smallermathstyle

Applies the next math style, smaller than the current. That is:

- sets `\scriptstyle` if the current math style is `\displaystyle` or `\textstyle`;
- sets `\scriptscriptstyle` if the current math style is `\scriptstyle`;
- does nothing if the current math style is `\scriptscriptstyle`.

```
$ \displaystyle AB \quad \textstyle AB
 \quad \scriptstyle AB \quad \scriptscriptstyle AB \$\par
 \$ \displaystyle AB \quad \smallermathstyle AB
 \quad \smallermathstyle AB \quad \smallermathstyle AB $
```

$$\begin{array}{llll} AB & AB & AB & AB \\ AB & AB & AB & AB \end{array}$$

### 4.2.3 Useful lengths for TikZ or picture environment

Arrows drawn with graphic languages, like PGF/TikZ or the `\picture` environment, are not extensible. The three lengths `\overarrowlength`, `\overarrowthickness` and `\overarrowsmallerthickness` are computed at each utilisation of a command set with the `tikz` or `picture` method, so they can be used in drawing commands.

```
\NewOverArrowCommand[tikz]{overparabola}{%
  path options={x=\overarrowlength, line width=\overarrowsmallerthickness},
  path={(0,0) parabola [parabola height=0.2\overarrowlength] (1,0)},
  arrows={-}, center arrow, min length=30,
}
\$ \displaystyle \overparabola{v} \quad \overparabola{ABCD} \$\par
\$ \scriptstyle \overparabola{v} \quad \overparabola{ABCD} \$\par
```



### \overarrowlength

Is set to the width of the arrow command content, or, if larger, to the minimal arrow length set through the key `min length`<sup>P.20</sup>.

### \overarrowthickness

Is set to the default rule thickness of the current math style. That is:

- `\fontdimen 8 \textfont 3` in `\displaystyle` or `\textstyle`;
- `\fontdimen 8 \scriptfont 3` in `\scriptstyle`;
- `\fontdimen 8 \scriptscriptfont 3` in `\scriptscriptstyle`.

### \overarrowallerthickness

Is set to the default rule thickness of the next smaller math style. That is:

- `\fontdimen 8 \scriptfont 3` in `\displaystyle` or `\textstyle`;
- `\fontdimen 8 \scriptscriptfont 3` in `\scriptstyle` or `\scriptscriptstyle`.

#### 4.2.4 Vectors macros

The macro `\vv`, dedicated to vectors, is automatically defined when the option `esvectP.11` is set (which is the default). It is a clone of the `\vv` command provided by the `esvect` package, but its starred variant has a correct kerning when followed by a subscript.

`\vv{<content>}`  
`\vv*{<content>}`

Draws a vector arrow upon math `<content>`. The shape of the arrow depends on the corresponding options described in section 4.1.1, page 11 : `esvectaP.12`, `esvectbP.12`, `esvectcP.12`, `esvectdP.12`, `esvecteP.12`, `esvectfP.12`, `esvectgP.12`, `esvecthP.13`.

The starred variant `\vv*` suppresses the end space created by the arrow.

```
$ \vv{\imath_0} \quad \vv{e_r} \quad \vv{L}_\Delta $ \par
$ \vv*{\imath_0} \quad \vv*{e_r} \quad \vv*{L}_\Delta $
```

$$\begin{array}{ccc} \vec{\imath}_0 & \vec{e}_r & \vec{L}_\Delta \\ \overrightarrow{\imath}_0 & \overrightarrow{e}_r & \overrightarrow{L}_\Delta \end{array}$$

### \esvectvv

Is simply the backup of the original `esvect \vv` command.

```
$ \esvectvv{\imath_0} \quad \esvectvv{e_r} \quad \esvectvv{L}_\Delta $ \par
$ \esvectvv*{\imath_0} \quad \esvectvv*{e_r} \quad \esvectvv*{L}_\Delta $
```

$$\begin{array}{ccc} \vec{\imath}_0 & \vec{e}_r & \vec{L}_\Delta \\ \overrightarrow{\imath}_0 & \overrightarrow{e}_r & \overrightarrow{L}_\Delta \end{array}$$

#### 4.2.5 Predefined commands

Predefined commands are defined if the corresponding option is set (see section 4.1.2, page 13). The commands `\overrightarrow`, `\overleftarrow`, `\overleftrightarrow`, `\underrightarrow`, `\underleftarrow` and `\underleftrightarrow` are affected by the option `old-arrowsP.14`.

##### Over arrows

### \overrightarrow

$$\overrightarrow{v} \quad \overrightarrow{AB} \quad \overrightarrow{\text{grad}}$$

The shape of the arrow is smaller if the option `old-arrowsP.14` is set.

`\overleftarrow`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

The shape of the arrow is smaller if the option `old-arrows`<sup>P. 14</sup> is set.

`\overleftrightarrow`

$$\overleftrightarrow{v} \quad \overleftrightarrow{AB} \quad \overleftrightarrow{\text{grad}}$$

The shape of the arrows is smaller if the option `old-arrows`<sup>P. 14</sup> is set.

`\overrightharpoonup`

$$\overrightarrow{v} \quad \overrightarrow{AB} \quad \overrightarrow{\text{grad}}$$

`\overrightharpoondown`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

`\overleftharpoonup`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

`\overleftharpoondown`

$$\overrightarrow{v} \quad \overrightarrow{AB} \quad \overrightarrow{\text{grad}}$$

`\overbar`

$$\overline{v} \quad \overline{AB} \quad \overline{\text{grad}}$$

## Under arrows

`\underrightarrow`

$$\overrightarrow{v} \quad \overrightarrow{AB} \quad \overrightarrow{\text{grad}}$$

The shape of the arrow is smaller if the option `old-arrows`<sup>P. 14</sup> is set.

`\underleftarrow`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

The shape of the arrow is smaller if the option `old-arrows`<sup>P. 14</sup> is set.

`\underleftrightarrow`

$$\overleftrightarrow{v} \quad \overleftrightarrow{AB} \quad \overleftrightarrow{\text{grad}}$$

The shape of the arrows is smaller if the option `old-arrows`<sup>P. 14</sup> is set.

`\underrightrightarrow`

$$\overleftarrow{v} \quad \overleftarrow{AB} \quad \overleftarrow{\text{grad}}$$

`\underrightharpoondown`

$\overrightarrow{v}$      $\overrightarrow{AB}$      $\overrightarrow{\text{grad}}$

`\underleftharpoonup`

$\underline{v}$      $\underline{AB}$      $\underline{\text{grad}}$

`\underleftharpoondown`

$\overleftarrow{v}$      $\overleftarrow{AB}$      $\overleftarrow{\text{grad}}$

`\underbar`

$\underline{v}$      $\underline{AB}$      $\underline{\text{grad}}$

### 4.3 Keys

The customisation of arrows is done at command creation through a key-value interface provided by the `pgfkeys` package (with `/overarrows/` as key path).

#### 4.3.1 Arrow position and length settings

These keys are available whatever the method chosen at command creation (see section 4.2.1, page 15 for the documentation of commands creation).

##### Length

`min length={<number>}`

(no default, see below for the initial value)

Sets the minimal arrow length to  $\langle number \rangle$  math units. The arrow length is set from content width, or, if larger, to this value.

The initial value of `min length` depends on the  $\langle method \rangle$  chosen at command creation (see section 4.2.1, page 15 for the documentation of commands creation):

- $\langle number \rangle = 0$  for the `symb` method (default);
- $\langle number \rangle = 12$  for the `tikz` method;
- $\langle number \rangle = 18$  for the `picture` method.

```
\NewOverArrowCommand{overlongarrow}{min length=50}
$ \overlongarrow{v} \qquad \overlongarrow{ABCDEF} $
```

$\overrightarrow{v}$      $\overbrace{ABCDEF}$

##### Placement

`arrow under`

(default `autoconfig`, initially unset)

`arrow under=autoconfig|noconfig`

Places the arrow under, instead of over.

`arrow under` or `arrow under=autoconfig` also configures suitably the key `detect subscripts`<sup>→ P.22</sup> to `false` and the key `before arrow`<sup>→ P.22</sup> to get an additional space over the arrow.

`arrow under=noconfig` does not do any additional configuration.

```
\NewOverArrowCommand{underhooks}{%
  start={\lhook}, end={\rhook}, trim=1,
  arrow under, shift leftright=-4,
}
$ \underhooks{v} \qquad \underhooks{AB} $
```



### Horizontal shifts

`shift left={⟨number⟩}` (no default, initially 2)

Shifts the left side of the arrow by `⟨number⟩` math units (positive number means a shift to the right).

`shift right={⟨number⟩}` (no default, see below for the initial value)

Shifts the right side of the arrow by `⟨number⟩` math units (positive number means a shift to the left).

The initial value of `shift right` depends on the `⟨method⟩` chosen at command creation (see section 4.2.1, page 15 for the documentation of commands creation):

- `⟨number⟩ = 0` for the `symb` method (default);
- `⟨number⟩ = -2` for the `tikz` and `picture` methods.

```
\NewOverArrowCommand{lookback}{%
  start={\leftarrow}, end={\rightarrow},
  shift left=-50, shift right=-10,
}
$ \lookback{\text{look back}} $
```



`shift leftright=[⟨number⟩]` (no default)

Sets `shift left` and `shift right` to the same `⟨number⟩` value.

`center arrow`

Sets `shift left` and `shift right` to zero.

`left arrow` (default 2)

Sets `shift left` to zero and `shift right` to `⟨number⟩`.

`right arrow` (default 2)

Sets `shift right` to zero and `shift left` to `⟨number⟩`.

### Vertical adjunct

<b>before arrow</b> ={<vertical material>}	(initially empty)
<b>after arrow</b> ={<vertical material>}	(initially empty)

Adds the <vertical material> before or after the arrow.

Over and under arrow commands are typeset through the  $\text{\TeX}$  `\ialign` command, which aligns contents, like a tabular. The <vertical material> is inserted between the rows, with  $\text{\TeX}$  `\noalign` command.

These keys are essentially used to add some extra space between the arrow and the content of the command. They can be set in a handier way with the keys `space before arrow` and `space after arrow`.

<b>space before arrow</b> ={<length>}	(no default)
---------------------------------------	--------------

Adds a space of <length> before the arrow. This sets the keys `before arrow`.

<b>space after arrow</b> ={<length>}	(no default)
--------------------------------------	--------------

Adds a space of <length> after the arrow. This sets the keys `after arrow`.

```
\NewOverArrowCommand{overharpoonsdown}{%
  start=\leftharpoondown, end=rightharpoondown, center arrow,
  space before arrow=-0.2ex, space after arrow=0.3ex,
}
$ \dot{\overharpoonsdown{v}} \qquad \ddot{\overharpoonsdown{AB}}$
```



### 4.3.2 Subscripts detection setting

This key is available whatever the method chosen at command creation (see section 4.2.1, page 15 for the documentation of commands creation).

<b>detect subscripts</b> =true false	(default true, see below for the initial value)
--------------------------------------	---

Removes automatically the extra end space created by the arrow, if a subscript immediately follows the command.

By default, the initial value of `detect subscripts` is `false`. When the option `subscriptsP.15` is set, the initial value of `detect subscripts` is `true`.

```
\NewOverArrowCommand{autosub}{detect subscripts}
$ \imath_0 \qquad \imath_0 \qquad \imath_0 \qquad \imath_0 $
```



### 4.3.3 Symbols assemblage settings

The following keys are available for arrows drawn with the default `symb` method (see section 4.2.1, page 15 for the documentation of commands creation).

<b>start</b> ={<command>}	(no default, initially <code>\relbar</code> )
<b>middle</b> ={<command>}	(no default, initially set by <code>middle config=auto</code> )
<b>end</b> ={<command>}	(no default, see below for the initial value)

Sets the <command> used to draw the start (left), middle (center) or end (right) part of the arrow. The `middle` one is repeated, if necessary, to extend

the arrow. It is set, initially by `middle config=auto`. By default, the `end` symbols is initially `\rightarrow`. When the option `old-arrowsP.14` is set, the initial value of `end` is `\varrightarrow`.

`start` and `end` symbols are typeset in the same group. `middle` is typeset alone. This means that, if a command, like `\smallermathstyleP.17`, is used to alter the symbols, it should be applied both to `start` and `middle` (but not to `end`).

```
\NewOverArrowCommand{smalleroverrightarrow}{%
  start={\smallermathstyle\relbar},
  middle={\smallermathstyle\relbareda},
  end={\rightarrow},
  space after arrow={0.2ex},
}
$ \smalleroverrightarrow{v} \qquad \smalleroverrightarrow{AB} $
```

$\vec{v}$        $\overrightarrow{AB}$

**trim start={⟨number⟩}** (no default, initially 7)

Trims ⟨number⟩ math units from the right side of the `startP.22` symbol.

**trim middle={⟨number⟩}** (no default, initially set by `middle config=auto`)

Trims ⟨number⟩ math units from both left and right sides of the `middleP.22` symbol.

**trim end={⟨number⟩}** (no default, initially 7)

Trims ⟨number⟩ math units from the left side of the `endP.22` symbol.

**trim={⟨number⟩}** (no default)

Sets `trim start`, `trim middle` and `trim end` to the same ⟨number⟩ value.

**no trimming**

Clears `trim start`, `trim middle` and `trim end`.

**middle config=auto|relbar|relbareda** (no default)

Sets a suitable configuration for the keys `middleP.22` and `trim middle`:

**For middle config = relbar**, `middleP.22` is set to `\relbar` — and `trim middle` to 2.5.

**For middle config = relbareda**, `middleP.22` is set to `\relbareda` - and `trim middle` to 1.

**For middle config = auto**, `middleP.22` is set with `middle config = relabareda` if the option `esvectP.11` is set (which is the default) and `middle config = relabar` if not.

**amsmath** (default `mimic`)  
**amsmath=mimic|strict**

Loads a configuration coherent with `amsmath \overrightarrow` command.

`amsmath` or `amsmath=mimic` sets the corresponding keys suitably:

```

start={\relbar}      middle={\relbar}      end={\rightarrow}
trim start=7       trim middle=2        trim end=7
shift leftright=0   after arrow={}      before arrow={}

```

**amsmath=strict** makes, in addition, the command uses the internal macros of amsmath \overrightarrow (no trimming, fill macro=\arrowfill@, stack macro=\overarrow@). Note that many configuration keys becomes ineffective.

```

esvect                                     (default mimic)
esvect=mimic|strict

```

Loads a configuration coherent with **amsmath \vv** command.

**esvect or esvect=mimic** sets the corresponding keys suitably:

```

start={\relbaredd}      middle={\relbareda}      end={\fldr}
trim start=1.5         trim middle=0          trim end=1.5
space before arrow=-.7pt space after arrow=-.3pt right arrow=2

```

**esvect=strict** makes, in addition, the command uses the internal macros of **esvect \vv** (no trimming, fill macro=\traitfill@, stack macro=\overvect@). Note that many configuration keys becomes ineffective.

#### 4.3.4 TikZ settings

If, at command creation (see section 4.2.1, page 15 for the documentation of commands creation), the **tikz** method is chosen, then the arrow is drawn by the command:

```
\tikz[tikz options]{tikz command}
```

where **tikz options** and **tikz command**<sup>P. 25</sup> are two keys described below. When **tikz command** is let unset, the drawing command turns into:

```
\tikz[tikz options]{\draw[path options] path;}
```

The best way to customise **tikz** arrows is then to set the keys **tikz options**, **path options**<sup>P. 25</sup> and **path**<sup>P. 25</sup>, preferably through the handy alternatives: **add tikz options**<sup>P. 25</sup>, **add path options**<sup>P. 25</sup>, **arrows**<sup>P. 25</sup>, **line thickness**<sup>P. 25</sup> or **thinner**<sup>P. 25</sup>.

```

\NewOverArrowCommand[tikz]{overdotteddoublearrow}{%
  add tikz options={blue}, add path options={densely dotted},
  arrows={->[scale=0.5]>[scale=0.5]}, thinner,
  min length=20, space after arrow={0.3ex},
}
$ \overdotteddoublearrow{v} \qquad \overdotteddoublearrow{AB} $

```



The following keys are available when the **tikz** method is chosen.

```

tikz options={\langle TikZ options\rangle}
  (no default, initially x=\overarrowlength, line width=\overarrowthickness)

Sets TikZ options to \langle TikZ options\rangle.

```

```

path options={\langle path options\rangle}          (no default, initially arrows=-Classical TikZ Rightarrow, cap=round)
    Sets TikZ path options to \langle path options\rangle.

path={\langle path specification\rangle}           (no default, initially (0,0)--(1,0))
    Sets TikZ path specification to \langle path\rangle (the ending semicolon is automatically appended).

add tikz options={\langle TikZ options\rangle}        (no default)
    Appends the options \langle TikZ options\rangle to the key tikz optionsP.24.

add path options={\langle path options\rangle}        (no default)
    Appends the options \langle path options\rangle to the key path options.

arrows={\langle arrow specification\rangle}          (no default)
    Appends the option arrows=\langle arrow specification\rangle to the key path options.

line thickness={\langle length\rangle}                 (no default)
    Appends the option line width=\langle length\rangle to the key path options.

thinner
    Sets the keys line thickness with \overarrow{smallderthickness}.

tikz command={\langle TikZ command\rangle}            (initially unset)
    Sets the \langle TikZ command\rangle used to draw the arrow. If left unset, the value \draw[path options] path; is used.

```

#### 4.3.5 Picture environment settings

If, at command creation (see section 4.2.1, page 15 for the documentation of commands creation), the **picture** method is chosen, then the arrow is drawn with by:


```

\begin{picture}{geometry}
  \linethickness{\line thickness}
  picture command
\end{picture}

```

where **geometry**<sup>P.26</sup>, **line thickness**<sup>P.26</sup> and **picture command** are three keys described below.

```
% ^^A \arc and \roundcap commands are from the pict2e package
% ^^A this example needs \usepackage{pict2e} in the preamble
\NewOverArrowCommand[picture]{overarc}{%
  picture command={%
    \roundcap
    \put(0.5\overarrowlength,0){\arc[180,0]{0.6\overarrowlength}}
  },
  geometry={%
    (1.2\overarrowlength,0.5\overarrowlength)(-0.1\overarrowlength,0.2ex)
  },
  thinner, center arrow,
}
$ \overarc{v} \qquad \overarc{AB} $
```



The following keys are available when the `picture` method is chosen.

`picture command={⟨picture command⟩}`  
(no default, initially `\put(0,0){\vector(1,0){\overarrowlength}}`)  
Sets picture command to `⟨picture command⟩`.

`geometry={⟨picture geometry specification⟩}`  
(no default, initially `(\overarrowlength,1ex)(0,-0.5ex)`)  
Sets picture geometry to `⟨picture geometry specification⟩`.

`line thickness={⟨length⟩}`  
(no default)  
Sets the picture line thickness to `⟨length⟩`.

`thinner`  
(no default)  
Sets the keys `line thickness` with `\overarrowsmallerthickness`.

## 4.4 Advanced commands and keys

The following commands and keys are used in the implementation of the `overarrows` package. They can also be employed for an advanced configuration of the commands created, although unnecessary in the vast majority of cases.

### 4.4.1 Advanced commands

```
\SetOverArrowsMethod[⟨stack mechanism⟩]{⟨name⟩}[⟨pre code⟩]{⟨keys def⟩}
\SetOverArrowsMethod*{⟨name⟩}[⟨pre code⟩]{⟨keys def⟩}
```

Defines the method `⟨name⟩`, to be used in commands `\NewOverArrowCommand`<sup>P.15</sup>, `\RenewOverArrowCommand`<sup>P.15</sup>, `\ProvideOverArrowCommand`<sup>P.15</sup> or `\DeclareOverArrowCommand`<sup>P.15</sup>. When the `⟨name⟩` method is chosen, corresponding keys are defined by `⟨keys def⟩`. This must set, in particular, the keys `no stack macro hook`<sup>P.27</sup> and `no arrow macro hook`<sup>P.27</sup>. Optional code `⟨pre code⟩` is evaluated before the keys definition.

The unstarred variant automatically defines the key `no stack macro hook`<sup>P.27</sup>, according to the value of the optional `⟨stack mechanism⟩`. This one must be:

**fill** if arrow macro<sup>→ P. 27</sup> creates extensible arrows (typically with \cleaders).

In this case, the arrow macro (defined by no arrow macro hook<sup>→ P. 27</sup>) is called with the math style, passed as argument (it can be, for example, the macro \rightarrowfill@ used by amsmath \overrightarrow). fill is the mechanism used by the symb method.

**lens** if arrow macro creates fixed-length arrows, and needs the computation of lengths \overarrowlength<sup>→ P. 17</sup>, \overarrowthickness<sup>→ P. 17</sup> and \overarrowsmallerthickness<sup>→ P. 18</sup>. In this case, the arrow macro (defined by no arrow macro hook) is called without argument. lens is the mechanism used by the tikz and picture methods.

Without optional *stack mechanism*, fill is used. The starred variant does not set the key no stack macro hook.

#### 4.4.2 Advanced keys

**stack macro**={⟨stack definition⟩} (no default, initially unset)

Defines the stack macro to be ⟨stack definition⟩. Stack macro is a command which takes three arguments: the arrow macro set by arrow macro, the math style, and the command content (under or over the arrow). ⟨stack definition⟩ can be, for example, the macro \overarrow@ used by amsmath \overrightarrow.

**arrow macro**={⟨arrow definition⟩} (no default, initially unset)

Defines the arrow macro (used in the stack macro) by to be ⟨arrow definition⟩.

**no stack macro hook**={⟨code⟩} (no default)

Sets the ⟨code⟩ executed if stack macro is left unset, after user evaluation of ⟨keys⟩ in \NewOverArrowCommand<sup>→ P. 15</sup>, \RenewOverArrowCommand<sup>→ P. 15</sup>, \ProvideOverArrowCommand<sup>→ P. 15</sup> or \DeclareOverArrowCommand<sup>→ P. 15</sup>.

⟨code⟩ must configure stack macro accordingly to the user keys setting.

**no arrow macro hook**={⟨code⟩} (no default)

Sets the ⟨code⟩ executed if arrow macro is left unset, after user evaluation of ⟨keys⟩ in \NewOverArrowCommand<sup>→ P. 15</sup>, \RenewOverArrowCommand<sup>→ P. 15</sup>, \ProvideOverArrowCommand<sup>→ P. 15</sup> or \DeclareOverArrowCommand<sup>→ P. 15</sup>.

⟨code⟩ must configure arrow macro accordingly to the user keys setting.

**fill macro**={⟨definition⟩} (no default, initially unset)

Defines the fill macro to be ⟨definition⟩. The fill macro is used by arrows created with the symb method, to set arrow macro in no arrow macro hook. It is called with fours arguments: start, middle and end symbols used to draw the arrow, and the math style. ⟨definition⟩ can be, for example, the macro \arrowfill@ used by amsmath \overrightarrow.

## 5 Complements

### 5.1 Math font issue

If the math font differs from the default *Computer Modern*, arrow drawn with the `symb` method may have a central part of the arrow with inappropriate position or line width. This is because the default symbol used for the arrow line is `\relbar` from the `esvect` package. This can be fixed with the `noesvectP. 12` option.

### 5.2 Package dependencies

The following packages are used by `overarrows`:

- `amsmath`
- `etoolbox`
- `pgfkeys`
- `esvect` (unless the option `noesvectP. 12` is used)
- `old-arrows` (when the option `old-arrowsP. 14` is used)
- `tikz` (when the `tikz` method or the option `tikzP. 15` is used)
- `pict2e` (when the option `pstarrowsP. 15` is used)

`LATEX` distributions prior to 2020/10/01 must load the `xparse` package before `overarrows`.

### 5.3 Alternatives

**esvect** package (<https://www.ctan.org/pkg/esvect>), by Eddie Saudrais, provides the fine vector macro `\vv`. This package is loaded by default by `overarrows`.

**letterswitharrows** package (<https://www.ctan.org/pkg/letterswitharrows>), by Max Teegen, provides left and right over arrows commands, which can extend to multiple characters.

**overrightarrow** package (<https://www.ctan.org/pkg/overrightarrow>), by Robin Fairbairns, provides the `\Overrightarrow` which is an amalgam of `\overrightarrow` and `\Rightarrow`.

**harpoon** package (<https://ctan.org/pkg/harpoon>), by Tobias Kuipers, provides over- and under-harpoon symbol commands.

### 5.4 Changelog

**v1.0.1** Bug fix for under\* options.

**v1.0** Initial version.

## 6 Implementation

### Management of options

#### Declaration of conditionals

```
1 \newif\ifovar@option@oldarrows@
2 \newif\ifovar@option@esvect@ \ovar@option@esvect@true \PassOptionsToPackage{f}{esvect}
3 \newif\ifovar@option@tikz@
4 \newif\ifovar@option@pstarrows@
5 \newif\ifovar@detectsubscripts@
6 \newif\ifovar@option@debug@
```

Following conditionals are for predefined commands.

```
7 \newif\ifovar@option@overrightarrow@
8 \newif\ifovar@option@underrightarrow@
9 \newif\ifovar@option@overleftarrow@
10 \newif\ifovar@option@underleftarrow@
11 \newif\ifovar@option@overleftrightarrow@
12 \newif\ifovar@option@underleftrightarrow@
13 \newif\ifovar@option@overrightharpoonup@
14 \newif\ifovar@option@underrightharpoonup@
15 \newif\ifovar@option@overrightharpoondown@
16 \newif\ifovar@option@underrightharpoondown@
17 \newif\ifovar@option@overleftharpoonup@
18 \newif\ifovar@option@underleftharpoonup@
19 \newif\ifovar@option@overleftharpoondown@
20 \newif\ifovar@option@underleftharpoondown@
21 \newif\ifovar@option@overbar@
22 \newif\ifovar@option@underbar@
```

#### Declaration of options

```
23 \DeclareOption{esvect}{\ovar@option@esvect@true}
24 \DeclareOption{noesvect}{\ovar@option@esvect@false}
25 \DeclareOption{esvecta}{\ovar@option@esvect@true\PassOptionsToPackage{a}{esvect}}
26 \DeclareOption{esvectb}{\ovar@option@esvect@true\PassOptionsToPackage{b}{esvect}}
27 \DeclareOption{esvectc}{\ovar@option@esvect@true\PassOptionsToPackage{c}{esvect}}
28 \DeclareOption{esvectd}{\ovar@option@esvect@true\PassOptionsToPackage{d}{esvect}}
29 \DeclareOption{esvecte}{\ovar@option@esvect@true\PassOptionsToPackage{e}{esvect}}
30 \DeclareOption{esvectf}{\ovar@option@esvect@true\PassOptionsToPackage{f}{esvect}}
31 \DeclareOption{esvectg}{\ovar@option@esvect@true\PassOptionsToPackage{g}{esvect}}
32 \DeclareOption{esvecth}{\ovar@option@esvect@true\PassOptionsToPackage{h}{esvect}}
33 \DeclareOption{old-arrows}{\ovar@option@oldarrows@true}
34 \DeclareOption{tikz}{\ovar@option@tikz@true}
35 \DeclareOption{pstarrows}{\ovar@option@pstarrows@true}
36 \DeclareOption{subscripts}{\ovar@detectsubscripts@true}
37 \DeclareOption{debug}{\ovar@option@debug@true}
```

Following options are for predefined commands.

```
38 \DeclareOption{overrightarrow}{\ovar@option@overrightarrow@true}
39 \DeclareOption{underrightarrow}{\ovar@option@underrightarrow@true}
40 \DeclareOption{overleftarrow}{\ovar@option@overleftarrow@true}
41 \DeclareOption{underleftarrow}{\ovar@option@underleftarrow@true}
42 \DeclareOption{overleftrightarrow}{\ovar@option@overleftrightarrow@true}
43 \DeclareOption{underleftrightarrow}{\ovar@option@underleftrightarrow@true}
44 \DeclareOption{overrightharpoonup}{\ovar@option@overrightharpoonup@true}
45 \DeclareOption{underrightharpoonup}{\ovar@option@underrightharpoonup@true}
46 \DeclareOption{overrightharpoondown}{\ovar@option@overrightharpoondown@true}
47 \DeclareOption{underrightharpoondown}{\ovar@option@underrightharpoondown@true}
48 \DeclareOption{overleftharpoonup}{\ovar@option@overleftharpoonup@true}
```

```

49 \DeclareOption{underleftharpoonup}{\ovar@option@underleftharpoonup@true}
50 \DeclareOption{overleftharpoondown}{\ovar@option@overleftharpoondown@true}
51 \DeclareOption{underleftharpoondown}{\ovar@option@underleftharpoondown@true}
52 \DeclareOption{overbar}{\ovar@option@overbar@true}
53 \DeclareOption{underbar}{\ovar@option@underbar@true}

```

Following options are for sets of predefined commands.

```

54 \DeclareOption{overcommands}{%
55   \ovar@option@overrightarrow@true
56   \ovar@option@overleftarrow@true
57   \ovar@option@overleftrightarrow@true
58   \ovar@option@overrightharpoonup@true
59   \ovar@option@overrightharpoondown@true
60   \ovar@option@overleftharpoonup@true
61   \ovar@option@overleftharpoondown@true
62   \ovar@option@overbar@true
63 }
64 \DeclareOption{undercommands}{%
65   \ovar@option@underrightarrow@true
66   \ovar@option@underleftarrow@true
67   \ovar@option@underleftrightarrow@true
68   \ovar@option@underrightharpoonup@true
69   \ovar@option@underrightharpoondown@true
70   \ovar@option@underleftharpoonup@true
71   \ovar@option@underleftharpoondown@true
72   \ovar@option@underbar@true
73 }
74 \DeclareOption{allcommands}{%
75   \ovar@option@overrightarrow@true
76   \ovar@option@underrightarrow@true
77   \ovar@option@overleftarrow@true
78   \ovar@option@underleftarrow@true
79   \ovar@option@overleftrightarrow@true
80   \ovar@option@underleftrightarrow@true
81   \ovar@option@overrightharpoonup@true
82   \ovar@option@underrightharpoonup@true
83   \ovar@option@overrightharpoondown@true
84   \ovar@option@underrightharpoondown@true
85   \ovar@option@overleftharpoonup@true
86   \ovar@option@underleftharpoonup@true
87   \ovar@option@overleftharpoondown@true
88   \ovar@option@underleftharpoondown@true
89   \ovar@option@overbar@true
90   \ovar@option@underbar@true
91 }

```

## Options processing

```

92 \DeclareOption*{\PackageWarning{overarrows}{Unknown option: '\CurrentOption'}}
93 \ProcessOptions\relax

```

## Package dependencies

L<sup>A</sup>T<sub>E</sub>X distributions prior to 2020/10/01 must add the `xparse` package.

```

94 \RequirePackage{amsmath}
95 \RequirePackage{etoolbox}

```

Option `old-arrows`<sup>→ P.<sup>14</sup>. Configuration of arrows used for predefined commands.</sup>

```

96 \let\ovar@rightarrow\rightarrow
97 \let\ovar@leftarrow\leftarrow
98 \ifovar@option@oldarrows@

```

```

99  \RequirePackage[old]{old-arrows}
100 \let\ovar@rightarrow\varrightarrow
101 \let\ovar@leftarrow\varleftarrow
102 \fi

```

Option `esvect`<sup>→ P. 11</sup>.

```

103 \ifovar@option@esvect@
104   \RequirePackage{esvect}
105 \fi

```

Option `tikz`<sup>→ P. 15</sup>.

```

106 \ifovar@option@tikz@
107   \RequirePackage{tikz}
108   \usetikzlibrary{arrows.meta}
109 \fi

```

Option `pstarrows`<sup>→ P. 15</sup>.

```

110 \ifovar@option@pstarrows@
111   \RequirePackage[pstarrows]{pict2e}
112 \fi

```

## Management of keys

### Family declaration and setters

```

113 \RequirePackage{pgfkeys}
114 \pgfkeys{overarrows/.is family}
115 \newcommand{\ovar@set}[1]{\pgfqkeys{/overarrows}{#1}}
\SetOverArrowsMethod
116 \NewDocumentCommand{\SetOverArrowsMethod}{ s O{fill} m O{} m }{%
117   \IfBooleanTF{#1}{%
118     \csgdef{\ovar@set@#3}{#4\ovar@set{#5}}%
119   }{%
120     \csgdef{\ovar@set@#3}{#4\ovar@set{%
121       no stack macro hook/.code={%
122         \ovar@set{stack macro/.expanded={%
123           \expandafter\expandonce\csname ovar@stack@#2\endcsname\%
124           {\expandonce\ovar@length@min}\%
125           {\expandonce\ovar@before@arrow}{\expandonce\ovar@after@arrow}\%
126         }}%
127       },#5}}%
128   }%
129 }

```

### Common keys

```

130 \SetOverArrowsMethod*[common]{\undef{\ovar@macro@stack}\undef{\ovar@macro@arrow}}{%
131   detect subscripts/.is if=ovar@detectsubscripts@,
stack macro→ P. 27 and arrow macro→ P. 27.
132   stack macro/.store in=\ovar@macro@stack,
133   arrow macro/.store in=\ovar@macro@arrow,
134   stack macro/.value required,
135   arrow macro/.value required,

```

no stack macro hook<sup>→ P. 27</sup>, no arrow macro hook<sup>→ P. 27</sup>. These two keys must be redefined by the command `\ovar@set@⟨method⟩`.

```

136   no stack macro hook/.code={%
137     \PackageError{overarrows}{Undefined stack macro}%
138     {The requested method is perhaps misspelled}

```

```

139 },
140 no arrow macro hook/.code={%
141   \PackageError{overarrows}{Undefined arrow macro}
142   {The requested method is perhaps misspelled}
143 },
144 min length→ P.20.
145   min length/.store in=\ovar@length@min,
146   min length/.value required,
147   min length=0,
148 before arrow→ P.22, after arrow→ P.22, space before arrow→ P.22, space after
149 arrow→ P.22.
150   before arrow/.store in=\ovar@before@arrow,
151   after arrow/.store in=\ovar@after@arrow,
152   before arrow/.value required,
153   after arrow/.value required,
154   before arrow=\empty,
155   after arrow=\empty,
156   space before arrow/.code=\pgfkeysalso{before arrow={\kern ##1}},
157   space after arrow/.code=\pgfkeysalso{after arrow={\kern ##1}},
158 shift left→ P.21, shift right→ P.21, shift leftright→ P.21, center arrow→ P.21,
159 left arrow→ P.21, right arrow→ P.21.
160   shift left/.store in=\ovar@shift@left,
161   shift right/.store in=\ovar@shift@right,
162   shift left/.value required,
163   shift right/.value required,
164   shift leftright/.code=\pgfkeysalso{%
165     shift left=##1, shift right=##1,
166   },
167   center arrow/.code=\pgfkeysalso{shift leftright=0},
168   shift leftright/.value required,
169   center arrow/.value forbidden,
170   left arrow/.code=\pgfkeysalso{%
171     shift left=0, shift right=##1,
172   },
173   right arrow/.code=\pgfkeysalso{%
174     shift left=##1, shift right=0,
175   },
176   left arrow/.default=2,
177   right arrow/.default=2,
178   right arrow,
179 arrow under→ P.20.
180   arrow under/.is choice,
181   arrow under/noconfig/.code={%
182     \def\ovar@stack@fill{\ovar@stackunder@fill}
183     \def\ovar@stack@lens{\ovar@stackunder@lens}
184   },
185   arrow under/autoconfig/.code={%
186     \pgfkeysalso{%
187       arrow under=noconfig,
188       detect subscripts=false,
189       before arrow={\kern 1.3\ex@\relax},% like underarrow@ from amsmath
190     }
191   },
192   arrow under/.default=autoconfig,
193 }

```

### Keys for the symb method

```
188 \SetOverArrowsMethod{symb}{\undef{\ovar@macro@arrowfill}}{%
```

Fill macro.

```
189 fill macro/.store in=\ovar@macro@arrowfill,  
190 fill macro/.value required,
```

Arrow macro.

```
191 no arrow macro hook/.code={%  
192 \ifdef{\ovar@macro@arrowfill}{}{  
193 \ovar@set{  
194   fill macro/.expanded={%  
195     \noexpand\ovar@arrow@fill%  
196     {\expandonce\ovar@shift@left}{\expandonce\ovar@shift@right}%  
197   }  
198 }  
199 }  
200 \ovar@set{  
201   arrow macro/.expanded={%  
202     \expandonce{\ovar@macro@arrowfill}%  
203     {\expandonce{\ovar@arrow@start}\expandonce{\ovar@trim@start}}%  
204     {\expandonce{\ovar@trim@middle}\expandonce{\ovar@arrow@middle}}%  
205     {\expandonce{\ovar@trim@middle}}%  
206     {\expandonce{\ovar@trim@end}\expandonce{\ovar@arrow@end}}%  
207   }  
208 }  
209 },
```

start $\rightarrow$ P.22, middle $\rightarrow$ P.22, end $\rightarrow$ P.22.

```
210 start/.store in=\ovar@arrow@start,  
211 middle/.store in=\ovar@arrow@middle,  
212 end/.store in=\ovar@arrow@end,  
213 start/.value required,  
214 middle/.value required,  
215 end/.value required,
```

trim start $\rightarrow$ P.23, trim middle $\rightarrow$ P.23, trim end $\rightarrow$ P.23, trim $\rightarrow$ P.23, no trimming $\rightarrow$ P.23.

```
216 trim start/.code={\def\ovar@trim@start{\xjoinrel[\#1]}},  
217 trim middle/.code={\def\ovar@trim@middle{\xjoinrel[\#1]}},  
218 trim end/.code={\def\ovar@trim@end{\xjoinrel[\#1]}},  
219 trim start/.value required,  
220 trim middle/.value required,  
221 trim end/.value required,  
222 trim/.code={\pgfkeysalso{trim start=\#1, trim middle=\#1, trim end=\#1}},  
223 trim/.value required,  
224 no trimming/.code={%  
225   \let\ovar@trim@start\empty  
226   \let\ovar@trim@middle\empty  
227   \let\ovar@trim@end\empty  
228 },  
229 no trimming/.value forbidden,
```

middle config $\rightarrow$ P.23.

```
230 middle config/.is choice,  
231 middle config/.value required,  
232 middle config/relbar/.code=\pgfkeysalso{  
233   middle=\relbar,  
234   trim middle=2.5,  
235 },  
236 middle config/relbareda/.code={%  
237   \ifundef{\relbareda}{%  
238     \PackageWarning{overarrows}{Key 'middle config=relbareda' used,
```

```

239   \MessageBreak%
240   but \protect\relbareda\space is undefined; ignored.
241   \MessageBreak%
242   Load 'esvect' package, or use 'esvect' option \MessageBreak%
243   to remove this warning}
244 }{%
245   \pgfkeysalso{%
246     middle={\relbareda},
247     trim middle={1},
248   }
249 }
250 },
251 middle config/.code={%
252   \ifovar@option@esvect@
253   \pgfkeysalso{middle config=relbareda}
254   \else
255   \pgfkeysalso{middle config=relbar}
256   \fi
257 },

```

amsmath<sup>→ P. 23.</sup>

```

258 amsmath/.is choice,%
259 amsmath/mimic/.code=\pgfkeysalso{%
260   start={\relbar}, middle={\relbar}, end={\rightarrowarrow},
261   trim start=7,
262   trim middle=2,
263   trim end=7,
264   shift leftright=0,
265   after arrow={}, before arrow={},
266 },
267 amsmath/strict/.code=\pgfkeysalso{%
268   amsmath=mimic,
269   no trimming,
270   fill macro={\arrowfill@}, stack macro={\overarrow@},
271 },
272 amsmath/.default=mimic,

```

esvect<sup>→ P. 24.</sup>

```

273 esvect/.is choice,%
274 esvect/mimic/.code=\pgfkeysalso{%
275   start={\relbaredd}, middle={\relbareda}, end={\fldr},
276   trim start=1.5,
277   trim end=1.5,
278   trim middle=0,
279   right arrow=2,
280   space before arrow=-.7pt,
281   space after arrow=-.3pt,
282 },
283 esvect/strict/.code=\pgfkeysalso{%
284   esvect=mimic,
285   no trimming,
286   fill macro={\traitfill@}, stack macro={\overvect@},
287 },
288 esvect/.default=mimic,

```

Initial configuration.

```

289 amsmath, middle config=auto, end=\ovar@rightarrow, right arrow,
290 }
```

### Keys for the tikz method

```

291 \SetOverArrowsMethod[lens]{tikz}{\undef{\ovar@tikz@command}}{%
```

Arrow macro.

```

292 no arrow macro hook/.code={%
293   \ifdef{\ovar@tikz@command}{}{%
294     \pgfkeysgetvalue{/overarrows/path options}{\ovar@tikz@pathoptions}
295     \ovar@set{%
296       tikz command/.expanded={%
297         \noexpand\draw[\expandonce{\ovar@tikz@pathoptions}]\expandonce{\ovar@tikz@path};
298       }
299     }
300   }
301   \pgfkeysgetvalue{/overarrows/tikz options}{\ovar@tikz@options}
302   \ovar@set{%
303     arrow macro/.expanded={%
304       $\noexpand\mkern \expandonce{\ovar@shift@left} mu\noexpand\relax$%
305       \noexpand\tikz[\expandonce{\ovar@tikz@options}]{\expandonce{\ovar@tikz@command}}%
306       $\noexpand\mkern \expandonce{\ovar@shift@right} mu\noexpand\relax$%
307     }
308   }
309 },

```

TikZ parts: `tikz command` $\rightarrow$ P. 25, `tikz options` $\rightarrow$ P. 24, `path options` $\rightarrow$ P. 25, `path` $\rightarrow$ P. 25.

```

310 tikz command/.store in=\ovar@tikz@command,
311 tikz options/.initial={x=\overarrowlength, line width=\overarrowthickness},
312 path options/.initial={arrows=-Classical TikZ Rightarrow, cap=round},
313 path/.store in=\ovar@tikz@path,
314 path={(0,0)--(1,0)},
315 tikz command/.value required,
316 tikz options/.value required,
317 path options/.value required,
318 path/.value required,

```

TikZ handy keys: `add path options` $\rightarrow$ P. 25, `add tikz options` $\rightarrow$ P. 25, `arrows` $\rightarrow$ P. 25, `line thickness` $\rightarrow$ P. 25, `thinner` $\rightarrow$ P. 25.

```

319 add path options/.code=\pgfkeysalso{%
320   path options/.append={, ##1},%
321   add tikz options/.code=\pgfkeysalso{%
322     tikz options/.append={, ##1},%
323     arrows/.code=\pgfkeysalso{add path options={arrows={##1}}},%
324     line thickness/.code=\pgfkeysalso{add path options={line width=##1}},%
325     thinner/.code=\pgfkeysalso{line thickness={\overarrowsmallerthickness}},%
326     add path options/.value required,%
327     add tikz options/.value required,%
328     arrows/.value required,%
329     line thickness/.value required,%
330     thinner/.value forbidden,%

```

Initial configuration.

```

331 shift right=-2,
332 min length=12,
333 }

```

### Keys for the picture method

```

334 \SetOverArrowsMethod[lens]{picture}{%

```

Arrow macro.

```

335 no arrow macro hook/.code={%
336   \ovar@set{%
337     arrow macro/.expanded={%
338       $\noexpand\mkern \expandonce{\ovar@shift@left} mu\noexpand\relax$%

```

```

339   \noexpand\begin{picture}\expandonce{\ovar@picture@geometry}%
340     \noexpand\linethickness{\expandonce{\ovar@picture@linethickness}}%
341     \expandonce{\ovar@picture@command}%
342     \noexpand\end{picture}%
343   \$\noexpand\mkern \expandonce{\ovar@shift@right} mu\noexpand\relax$%
344 }
345 }
346 },

```

Picture parts: picture command $\rightarrow$ P. 26, geometry $\rightarrow$ P. 26, line thickness $\rightarrow$ P. 26.

```

347 picture command/.store in=\ovar@picture@command,
348 geometry/.store in=\ovar@picture@geometry,
349 line thickness/.store in=\ovar@picture@linethickness,
350 picture command/.value required,
351 geometry/.value required,
352 line thickness/.value required,

```

Picture handy key: thinner $\rightarrow$ P. 26.

```

353 thinner/.code=\pgfkeysalso{line thickness={\overarrowsmallerthickness}},

```

Initial configuration.

```

354 shift right=-2,
355 min length=18,
356 geometry={(\overarrowlength,1ex)(0,-0.5ex)},%
357 line thickness={\overarrowthickness},%
358 picture command={\put(0,0){\vector(1,0){\overarrowlength}}},%
359 }

```

## Commands

### Macros for symbols assemblage

```

\xjoinrel 360 \ifdef{\xjoinrel}{%
361   \PackageWarning{overarrows}{Command \protect\xjoinrel already defined.%
362   \MessageBreak%
363   Previous definition will be overridden}%
364 }{}%

```

Use a default value of 3.5 mu, as recommended by egreg (see <https://tex.stackexchange.com/a/471736>). \joinrel uses a value of 3 mu.

```

365 \DeclareRobustCommand{\xjoinrel}[1][3.5]{\mathrel{\mkern-#1mu}}
366 \newcommand*{\smallermathstyle}[1]{%
367   \mathchoice{\scriptstyle}{\scriptstyle}{\scriptstyle}{\scriptstyle}%
368 }

```

\ovar@arrow@fill Macro used for default fill macro $\rightarrow$ P. 27.

- #1: left shift
- #2: right shift
- #3: arrow start
- #4: arrow middle
- #5: arrow end
- #6: math style

```

369 \def\ovar@arrow@fill#1#2#3#4#5#6{%
370   \$\mathrel{\thickmuskip0mu\medmuskip\thickmuskip\thinmuskip\thickmuskip\relax}%
371   \mkern #1 mu\relax#6#3\%
372   \cleaders\hbox{\$#6#4\$}\hfill\%
373   #5\mkern #2 mu\relax\$%
374 }

```

## Macros for fixed length arrows

Lengths declaration.

```

375 \newlength{\overarrowlength}
376 \newlength{\overarrowthickness}
377 \newlength{\overarrowsmallerthickness}
378 \newlength{\ovar@extralength}
379 \newlength{\ovar@tempdim}

\ovar@set@arrowlength
      Sets \overarrowlength→ P. 17.
      #1: min length, in math units
      #2: math style
      #3: content

380 \def\ovar@set@arrowlength#1#2#3{%
381   \settowidth{\ovar@tempdim}{$\mathbf{m@th}#2\mskip #1 mu\relax$}%
382   \settowidth{\overarrowlength}{$\mathbf{m@th}#2#3$}%
383   \ifdim \overarrowlength < \ovar@tempdim \overarrowlength=\ovar@tempdim\fi%
384 }

```

\ovar@set@arrowthickness
 Sets \overarrowthickness<sup>→ P. 17</sup> and \overarrowsmallerthickness<sup>→ P. 18.</sup>

#1: arrow length  
#2: math style

```

385 \def\ovar@set@arrowthickness#1{%
386   \ifx#1\displaystyle%
387     \overarrowthickness = \fontdimen 8 \textfont 3%
388     \overarrowsmallerthickness = \fontdimen 8 \scriptfont 3%
389   \else\ifx#1\textstyle%
390     \overarrowthickness = \fontdimen 8 \textfont 3%
391     \overarrowsmallerthickness = \fontdimen 8 \scriptfont 3%
392   \else\ifx#1\scriptstyle%
393     \overarrowthickness = \fontdimen 8 \scriptfont 3%
394     \overarrowsmallerthickness = \fontdimen 8 \scriptscriptfont 3%
395   \else%
396     \overarrowthickness = \fontdimen 8 \scriptscriptfont 3%
397     \overarrowsmallerthickness = \overarrowthickness%
398   \fi\fi\fi%
399 }

```

## Stack macros

\ovar@stackover@@

Bases of all stack macros.

#1: min length, in math units  
#2: vertical mode material before arrow  
#3: vertical mode material after arrow  
#4: arrow  
#5: math style  
#6: content

```

400 \def\ovar@stackover@@#1#2#3#4#5#6{\vbox{\ialign{##\cr\cr%
401   $#5\mskip #1 mu\relax$\cr\cr%
402   \noalign{\#2\nointerlineskip}\#4\cr\cr%
403   \noalign{\#3\nointerlineskip}%
404   $\mathbf{m@th}\hfil#5#6\hfil$\cr\cr%
405   }%
406   }%
407 }
408 \def\ovar@stackunder@@#1#2#3#4#5#6{\vtop{\ialign{##\cr\cr%
409   $\mathbf{m@th}\hfil#5#6\hfil$\cr\cr%

```

```

410      \noalign{#2\nointerlineskip}\#4\crcr%
411      \noalign{#3\nointerlineskip}%
412      $#5\mskip #1 mu\relax$\crcr%
413      }%
414      }%
415 }

\ovar@stackover@          % Stack macros without min arrow length.
\ovar@stackunder@          % #1: vertical mode material before arrow
                           % #2: vertical mode material after arrow
                           % #3: arrow macro
                           % #4: math style
                           % #5: content
416 \def\ovar@stackover@#1#2#3#4#5{\ovar@stackover@@{#1}{#2}{#3}{#4}{#5}}
417 \def\ovar@stackunder@#1#2#3#4#5{\ovar@stackunder@@{#1}{#2}{#3}{#4}{#5}}
\ovar@stackover@fill        % Stack macros for extensible arrows.
\ovar@stackunder@fill       % #1: min length, in math units
                           % #2: vertical mode material before arrow
                           % #3: vertical mode material after arrow
                           % #4: arrow filler macro
                           % #5: math style
                           % #6: content
418 \def\ovar@stackover@fill#1#2#3#4#5#6{\ovar@stackover@@{#1}{#2}{#3}{#4#5}{#5}{#6}}
419 \def\ovar@stackunder@fill#1#2#3#4#5#6{\ovar@stackunder@@{#1}{#2}{#3}{#4#5}{#5}{#6}}
\ovar@stack@fill            % \ovar@stack@fill matches the macro \ovar@stackover@fill by default, or
                           % \ovar@stackunder@fill with arrow underP. 20.
420 \def\ovar@stack@fill{\ovar@stackover@fill}

\ovar@stackover@lens        % Stack macros for fixed-length arrows (these call \ovar@set@arrowlength and
                           % \ovar@set@arrowthickness).
\ovar@stackunder@lens
\ovar@stack@lens             % #1: min length, in math units
                           % #2: vertical mode material before arrow
                           % #3: vertical mode material after arrow
                           % #4: arrow content macro
                           % #5: math style
                           % #6: content
421 \def\ovar@stackover@lens#1#2#3#4#5#6{%
422   \ovar@set@arrowlength{#1}{#5}{#6}%
423   \ovar@set@arrowthickness{#5}%
424   \ovar@stackover@{#2}{#3}{#4}{#5}{#6}%
425 }
426 \def\ovar@stackunder@lens#1#2#3#4#5#6{%
427   \ovar@set@arrowlength{#1}{#5}{#6}%
428   \ovar@set@arrowthickness{#5}%
429   \ovar@stackunder@{#2}{#3}{#4}{#5}{#6}%
430 }

\ovar@stack@lens            % \ovar@stack@lens matches the macro \ovar@stackover@lens by default, or
                           % \ovar@stackunder@lens with arrow underP. 20.
431 \def\ovar@stack@lens{\ovar@stackover@lens}

```

## Macro for commands creation

```
\DeclareOverArrowCommand
```

```

432 \NewDocumentCommand{\DeclareOverArrowCommand}{ O{symb} m m }{%
433   \begingroup
434   \ovar@set@common
435   \ifcsdef{\ovar@set@#1}{%
436     \csuse{\ovar@set@#1}
437   }{%
438     \PackageError{overarrows}{Unknown method #1}
439     {Try with 'symb', 'tikz' or 'picture'}
440   }
441   \ovar@set{#3}
442   \ifdef{\ovar@macro@arrow}{%
443     \ovar@set{no arrow macro hook}
444   }
445   \ifdef{\ovar@macro@stack}{%
446     \ovar@set{no stack macro hook}
447   }
448   \csxdef{\ovar@#2@normal}{%
449     \noexpand\mathpalette{%
450       \expandonce{\ovar@macro@stack}\{\expandonce{\ovar@macro@arrow}\}%
451     }
452   }
453   \csxdef{\ovar@#2@starred}{%
454     \noexpand\mathpalette{%
455       \noexpand\ovar@starversion{%
456         \expandonce{\ovar@macro@stack}\{\expandonce{\ovar@macro@arrow}\}%
457       }
458     }
459   }
460   \ifovar@detectsubscripts@%
461   \csgdef{\ovar@#2@auto}##1{%
462     \@ifnextchar_{%
463       \csuse{\ovar@#2@starred}{##1}%
464     }{%
465       \csuse{\ovar@#2@normal}{##1}%
466     }%
467   }
468   \csgdef{\#2}{%
469     \@ifstar{\csuse{\ovar@#2@starred}}{\csuse{\ovar@#2@auto}}%
470   }
471   \else
472   \csgdef{\#2}{%
473     \@ifstar{\csuse{\ovar@#2@starred}}{\csuse{\ovar@#2@normal}}%
474   }
475   \fi
476   \ifovar@option@debug@
477   \PackageInfo{overarrows}{%
478     Meaning of \protect\ovar@#2@normal\MessageBreak
479     used for @backslashchar#2:\MessageBreak%
480     \expandafter\meaning\csname ovvar@#2@normal\endcsname
481   \fi
482   \endgroup
483 }
484 \ProvideOverArrowCommand
485 \NewDocumentCommand{\ProvideOverArrowCommand}{ O{symb} m m }{%
486   \ifcsdef{\#2}{}{%
487     \DeclareOverArrowCommand[#1]{\#2}{\#3}
488   }
489 \NewOverArrowCommand
490 \NewDocumentCommand{\NewOverArrowCommand}{ O{symb} m m }{%
491   \ifcsdef{\#2}{%
492     \PackageError{overarrows}{Command \csname \#2\endcsname already defined}%
493     {You have used \protect\NewOverArrowCommand\space with a command that
494      already has a definition. \MessageBreak%

```

```

494     Choose another name, or use instead \protect\DeclareOverArrowCommand.}
495 }{%
496   \DeclareOverArrowCommand[#1]{#2}{#3}
497 }
498 }

\ReneWOverArrowCommand
499 \NewDocumentCommand{\RenewOverArrowCommand}{ O{symb} m m }{%
500   \ifcsundef{#2}{%
501     \PackageError{overarrows}{Command \csname #2\endcsname undefined}{%
502       You have used \protect\RenewOverArrowCommand\space with a command that was
503       never defined. \MessageBreak%
504       Check the requested name, or use instead \protect\NewOverArrowCommand.}
505   }{%
506     \DeclareOverArrowCommand[#1]{#2}{#3}
507   }
508 }

```

### Starred variant

\ovar@starversion

```

#1: definition (stack macro + arrow macro)
#2: math style
#3: content

509 \def\ovar@starversion#1#2#3{%
510   #1#2{#3}%
511   \settowidth{\ovar@extralength}{$\m@th#1#2{#3}$}
512   \settowidth{\ovar@tempdim}{$\m@th#2{#3}$}
513   \deflength{\ovar@extralength}{0.5\ovar@extralength-0.5\ovar@tempdim}%
514   \kern-\ovar@extralength%
515 }

```

### \vv vector command

\vv

```

Backup and redefinition of esvect \vvP.18 vector command.

\esvectvv
516 \ifovar@option@esvect@
517   \let\esvectvv\vv
518   \undef\vv
519   \NewOverArrowCommand{\vv}{esvect, middle config=auto}
520 \fi

```

### Predefined commands

\overrightarrow

```

521 \ifovar@option@overrightarrow@
522   \DeclareOverArrowCommand{\overrightarrow}{%
523     amsmath, middle config=relbar,
524     end=\ovar@rightarrow,
525     right arrow,
526   }
527 \fi

\underrightarrow
528 \ifovar@option@underrightarrow@
529   \DeclareOverArrowCommand{\underrightarrow}{%
530     amsmath, middle config=relbar,
531     end=\ovar@rightarrow,
532     right arrow,
533     arrow under,
534   }
535 \fi

\overleftarrow

```

```

536 \ifovar@option@overleftarrow@
537   \DeclareOverArrowCommand{overleftarrow}{%
538     amsmath, middle config=relbar,
539     start=\ovar@leftarrow,
540     end=\relbar,
541     left arrow,
542   }
543 \fi
\underleftarrow
544 \ifovar@option@underleftarrow@
545   \DeclareOverArrowCommand{underleftarrow}{%
546     amsmath, middle config=relbar,
547     start=\ovar@leftarrow,
548     end=\relbar,
549     left arrow,
550     arrow under,
551   }
552 \fi
\overleftrightarrow
553 \ifovar@option@overleftrightarrow@
554   \DeclareOverArrowCommand{overleftrightarrow}{%
555     amsmath, middle config=relbar,
556     start=\ovar@leftarrow,
557     end=\ovar@rightarrow,
558     center arrow,
559   }
560 \fi
\underleftrightarrow
561 \ifovar@option@underleftrightarrow@
562   \DeclareOverArrowCommand{underleftrightarrow}{%
563     amsmath, middle config=relbar,
564     start=\ovar@leftarrow,
565     end=\ovar@rightarrow,
566     center arrow,
567     arrow under,
568   }
569 \fi
\overrightharpoonup
570 \ifovar@option@overrightharpoonup@
571   \DeclareOverArrowCommand{overrightharpoonup}{%
572     amsmath, middle config=relbar,
573     end=\rightharpoonup,
574     right arrow,
575   }
576 \fi
\underrightharpoonup
577 \ifovar@option@underrightharpoonup@
578   \DeclareOverArrowCommand{underrightharpoonup}{%
579     amsmath, middle config=relbar,
580     end=\rightharpoonup,
581     right arrow,
582     arrow under,
583   }
584 \fi
\overrightharpoondown
585 \ifovar@option@overrightharpoondown@
586   \DeclareOverArrowCommand{overrightharpoondown}{%
587     amsmath, middle config=relbar,
588     end=\rightharpoondown,
589     right arrow,
590   }
591 \fi
\underrightharpoondown
592 \ifovar@option@underrightharpoondown@
593   \DeclareOverArrowCommand{underrightharpoondown}{%

```

```

594     amsmath, middle config=relbar,
595     end=\rightharpoondown,
596     right arrow,
597     arrow under,
598   }
599 \fi
\overleftharpoonup
600 \ifovar@option@overleftharpoonup@
601   \DeclareOverArrowCommand{overleftharpoonup}{%
602     amsmath, middle config=relbar,
603     start=\leftharpoonup,
604     end=\relbar,
605     left arrow,
606   }
607 \fi
\underleftharpoonup
608 \ifovar@option@underleftharpoonup@
609   \DeclareOverArrowCommand{underleftharpoonup}{%
610     amsmath, middle config=relbar,
611     start=\leftharpoonup,
612     end=\relbar,
613     left arrow,
614     arrow under,
615   }
616 \fi
\overleftharpoondown
617 \ifovar@option@overleftharpoondown@
618   \DeclareOverArrowCommand{overleftharpoondown}{%
619     amsmath, middle config=relbar,
620     start=\leftharpoondown,
621     end=\relbar,
622     left arrow,
623   }
624 \fi
\underleftharpoondown
625 \ifovar@option@underleftharpoondown@
626   \DeclareOverArrowCommand{underleftharpoondown}{%
627     amsmath, middle config=relbar,
628     start=\leftharpoondown,
629     end=\relbar,
630     left arrow,
631     arrow under,
632   }
633 \fi
\overbar
634 \ifovar@option@overbar@
635   \DeclareOverArrowCommand{overbar}{%
636     amsmath, middle config=relbar,
637     start={\std@minus}, end={\std@minus},% \relbar is defined with \mathsm@sh
638     shift leftright=0,
639     space after arrow=-0.3ex,
640   }
641 \fi
\underbar
642 \ifovar@option@underbar@
643   \DeclareOverArrowCommand{underbar}{%
644     amsmath, middle config=relbar,
645     start={\std@minus}, end={\std@minus},% \relbar is defined with \mathsm@sh
646     shift leftright=0,
647     arrow under,
648     space before arrow=-0.3ex,
649   }
650 \fi

```

## Test macros

```
\ovar@testmathstyles
```

Tabular containing the output of a command for the four math styles and different patterns.

```

651 \newcommand{\ovar@testmathstyles}[2][]{%
652   \begingroup
653   \newcommand*{\ovar@row@teststyle}[1]{%
654     $ \displaystyle \##1$%
655     & $ \textstyle \##1$%
656     & $ \scriptstyle \##1$%
657     & $ \scriptscriptstyle \##1$%
658   \\%
659 }
660 \renewcommand*{\arraystretch}{1.5}
661 \begin{tabular}{0.95\linewidth}{@{\extracolsep{\fill}} cccc}
662   \hline
663   \footnotesize\textrt{\textrt{\textbackslash displaystyle}}
664   & \footnotesize\textrt{\textrt{\textbackslash textstyle}}
665   & \footnotesize\textrt{\textrt{\textbackslash scriptstyle}}
666   & \footnotesize\textrt{\textrt{\textbackslash scriptscriptstyle}}
667   \\
668   \hline
669   \ovar@row@teststyle{\csuse{#2}{v}}
670   \ovar@row@teststyle{\csuse{#2}{AB}}
671   \ovar@row@teststyle{\csuse{#2}{\mathrm{grad}}}
672   \ovar@row@teststyle{\csuse{#2}{my-long-vector}}
673   \IfValueT{#1}{\ovar@row@teststyle{\csuse{#2}{#1}}}
674   \hline
675 \end{tabular}
676 \endgroup
677 }
```

```
\TestOverArrow
```

```

678 \NewDocumentCommand{\TestOverArrow}{ s o m }{%
679   \ifcsdef{#3}{}{%
680     \PackageWarning{overarrows}{Unknown name '#3' passed to
681       \protect\TestOverArrow}
682   }
683   \IfBooleanTF{#1}{%
684     \noindent\fbox{%
685       \begin{minipage}{0.95\linewidth}
686         \centering
687         \noindent\textrt{\textbf{\large Test of \textbackslash textrt{\textbackslash textbackslash\#3} and \textbackslash textrt{\textbackslash textbackslash\#3*} macros}}
688         \bigskip\par
689         \textrt{\textbf{\textbackslash textrt{\textbackslash textbackslash\#3} for different math styles}}
690         \smallskip\par
691         \ovar@testmathstyles[#2]{#3}%
692         \bigskip\par
693         \textrt{\textbf{\textbackslash textrt{\textbackslash textbackslash\#3} kerning}}
694         \begin{displaymath}
695           \csuse{#3}{t}_{\csuse{#3}{u}_{\csuse{#3}{v}}}
696           \quad
697           \qquad
698           \csuse{#3}{\imath}_0
699           \qquad
700           \csuse{#3}{v}
701           = \csuse{#3}{v}_x + \csuse{#3}{v}_y + \csuse{#3}{v}_z
702           = v_x \csuse{#3}{\imath} + v_y \csuse{#3}{\jmath} + v_z \csuse{#3}{k}
703         \end{displaymath}
704         \textrt{\textbf{\textbackslash textrt{\textbackslash textbackslash\#3*} kerning}}
705         \begin{displaymath}
706           \csuse{#3}{t}_{\csuse{#3}{u}_{\csuse{#3}{v}}}
707           \quad
708           \qquad
709         \end{displaymath}
710       \end{minipage}
711     }
712   }
713 }
```

```

708     \csuse{#3}{\imath}_0
709     \quad
710     \csuse{#3}{\v}
711     = \csuse{#3}{\v}_x + \csuse{#3}{\v}_y + \csuse{#3}{\v}_z
712     = \v_x \csuse{#3}{\imath} + \v_y \csuse{#3}{\jmath} + \v_z \csuse{#3}{\k}
713     \end{displaymath}
714     \end{minipage}%
715     }\\
716     \bigskip\par
717     }%\\
718     \ovar@testmathstyles[#2]{#3}%
719   }

```

# Index

Entries listed in the categories “commands”, “lengths”, and “internal macros” also include references to package implementation.

Package options	Commands
<code>allcommands</code> , 13	<code>\DeclareOverArrowCommand</code> , 15, 39–42
<code>debug</code> , 15	<code>\esvectvv</code> , 18, 40
<code>esvect</code> , 11	<code>\NewOverArrowCommand</code> , 15, 39, 40
<code>esvecta</code> , 12	<code>\overbar</code> , 19, 30, 42
<code>esvectb</code> , 12	<code>\overleftarrow</code> , 19, 29, 41
<code>esvectc</code> , 12	<code>\overleftharpoondown</code> , 19, 30, 42
<code>esvectd</code> , 12	<code>\overleftharpoonup</code> , 19, 29, 42
<code>esvecte</code> , 12	<code>\overleftrightarrow</code> , 19, 29, 41
<code>esvectf</code> , 12	<code>\overrightarrow</code> , 18, 29, 40
<code>esvectg</code> , 12	<code>\overrightharpoondown</code> , 19, 29, 41
<code>esvecth</code> , 13	<code>\overrightharpoonup</code> , 19, 29, 41
<code>noesvect</code> , 12	<code>\ProvideOverArrowCommand</code> , 15, 39
<code>old-arrows</code> , 14	<code>\RenewOverArrowCommand</code> , 15, 40
<code>overbar</code> , 14	<code>\SetOverArrowsMethod</code> , 26, 31, 33–35
<code>overcommands</code> , 13	<code>\SetOverArrowsMethod*</code> , 26
<code>overleftarrow</code> , 13	<code>\smallermathstyle</code> , 17, 36
<code>overleftharpoondown</code> , 14	<code>\TestOverArrow</code> , 16, 43
<code>overleftharpoonup</code> , 13	<code>\TestOverArrow*</code> , 16
<code>overleftrightarrow</code> , 13	<code>\underbar</code> , 20, 30, 42
<code>overrightarrow</code> , 13	<code>\underleftarrow</code> , 19, 29, 41
<code>overrightharpoondown</code> , 13	<code>\underleftharpoondown</code> , 20, 30, 42
<code>overrightharpoonup</code> , 13	<code>\underleftharpoonup</code> , 20, 30, 42
<code>pstarrows</code> , 15	<code>\underleftrightarrow</code> , 19, 29, 41
<code>subscripts</code> , 15	<code>\underrightarrow</code> , 19, 29, 40
<code>tikz</code> , 15	<code>\underrightharpoondown</code> , 20, 29, 41
<code>underbar</code> , 14	<code>\underrightharpoonup</code> , 19, 29, 41
<code>undercommands</code> , 13	<code>\vv</code> , 18, 40
<code>underleftarrow</code> , 14	<code>\vv*</code> , 18
<code>underleftharpoondown</code> , 14	<code>\xjoinrel</code> , 16, 33, 36
<code>underleftharpoonup</code> , 14	
<code>underleftrightarrow</code> , 14	
<code>underrightarrow</code> , 14	
<code>underrightharpoondown</code> , 14	
<code>underrightharpoonup</code> , 14	
<code>add path options</code> key, 25	<code>debug</code> package option, 15
<code>add tikz options</code> key, 25	<code>\DeclareOverArrowCommand</code> , 15
<code>after arrow</code> key, 22	<code>detect subscripts</code> key, 22
<code>allcommands</code> package option, 13	
<code>amsmath</code> key, 23	<code>end</code> key, 22
<code>arrow macro</code> key, 27	<code>esvect</code> key, 24
<code>arrow under</code> key, 20	<code>esvect</code> package option, 11
<code>arrows</code> key, 25	<code>esvecta</code> package option, 12
<code>before arrow</code> key, 22	<code>esvectb</code> package option, 12
<code>center arrow</code> key, 21	<code>esvectc</code> package option, 12
	<code>esvectd</code> package option, 12
	<code>esvecte</code> package option, 12

```

esvectf package option, 12
esvectg package option, 12
esvecth package option, 13
\esvectvv, 18

fill macro key, 27

geometry key, 26

Internal macros
  \ifovar@detectsubscripts@, 29,
    39
  \ifovar@option@debug@, 29, 39
  \ifovar@option@esvect@, 29, 31,
    34, 40
  \ifovar@option@oldarrows@, 29,
    30
  \ifovar@option@overbar@, 29, 42
  \ifovar@option@overleftarrow@,
    29, 41
  \ifovar@option@overleftharpoondown@,
    29, 42
  \ifovar@option@overleftharpoonup@,
    29, 42
  \ifovar@option@overleftrightarrow@,
    29, 41
  \ifovar@option@overrightarrow@,
    29, 40
  \ifovar@option@overrightharpoondown@,
    29, 41
  \ifovar@option@overrightharpoonup@,
    29, 41
  \ifovar@option@pstarrows@, 29,
    31
  \ifovar@option@tikz@, 29, 31
  \ifovar@option@underbar@, 29, 42
  \ifovar@option@underleftarrow@,
    29, 41
  \ifovar@option@underleftharpoondown@,
    29, 42
  \ifovar@option@underleftharpoonup@,
    29, 42
  \ifovar@option@underleftrightarrow@, Keys
    29, 41
  \ifovar@option@underrightarrow@,
    29, 40
  \ifovar@option@underrightharpoondown@,
    29, 41
  \ifovar@option@underrightharpoonup@,
    29, 41
  \ovar@after@arrow, 31, 32
  \ovar@arrow@end, 33
  \ovar@arrow@fill, 33, 36
  \ovar@arrow@middle, 33
  \ovar@arrow@start, 33
  \ovar@before@arrow, 31, 32
  \ovar@extralength, 37, 40
  \ovar@leftarrow, 30, 31, 41
  \ovar@length@min, 31, 32
  \ovar@macro@arrow, 31, 39
  \ovar@macro@arrowfill, 33
  \ovar@macro@stack, 31, 39
  \ovar@picture@command, 36
  \ovar@picture@geometry, 36
  \ovar@picture@linethickness, 36
  \ovar@rightarrow, 30, 31, 34, 40,
    41
  \ovar@row@teststyle, 43
  \ovar@set, 31, 33, 35, 39
  \ovar@set@, 31, 39
  \ovar@set@arrowlength, 37, 38
  \ovar@set@arrowthickness, 37, 38
  \ovar@set@common, 39
  \ovar@shift@left, 32, 33, 35
  \ovar@shift@right, 32, 33, 35, 36
  \ovar@stack@fill, 32, 38
  \ovar@stack@lens, 32, 38
  \ovar@stackover@, 38
  \ovar@stackover@@, 37, 38
  \ovar@stackover@fill, 38
  \ovar@stackover@lens, 38
  \ovar@stackunder@, 38
  \ovar@stackunder@@, 37, 38
  \ovar@stackunder@fill, 32, 38
  \ovar@stackunder@lens, 32, 38
  \ovar@starversion, 39, 40
  \ovar@tempdim, 37, 40
  \ovar@testmathstyles, 43, 44
  \ovar@tikz@command, 34, 35
  \ovar@tikz@options, 35
  \ovar@tikz@path, 35
  \ovar@tikz@pathoptions, 35
  \ovar@trim@end, 33
  \ovar@trim@middle, 33
  \ovar@trim@start, 33
  add path options, 25
  add tikz options, 25
  after arrow, 22
  amsmath, 23
  arrow macro, 27
  arrow under, 20
  arrows, 25
  before arrow, 22
  center arrow, 21
  detect subscripts, 22
  end, 22

```

```

esvect, 24
fill macro, 27
geometry, 26
left arrow, 21
line thickness, 25, 26
middle, 22
middle config, 23
min length, 20
no arrow macro hook, 27
no stack macro hook, 27
no trimming, 23
path, 25
path options, 25
picture command, 26
right arrow, 21
shift left, 21
shift leftright, 21
shift right, 21
space after arrow, 22
space before arrow, 22
stack macro, 27
start, 22
thinner, 25, 26
tikz command, 25
tikz options, 24
trim, 23
trim end, 23
trim middle, 23
trim start, 23

left arrow key, 21
Lengths
  \overarrowlength, 17, 35–37
  \overarrowsmallerthickness, 18,
    35–37
  \overarrowthickness, 17, 35–37
line thickness key, 25, 26

middle key, 22
middle config key, 23
min length key, 20
  \NewOverArrowCommand, 15
no arrow macro hook key, 27
no stack macro hook key, 27
no trimming key, 23
noesvect package option, 12

old-arrows package option, 14
\overarrowlength length, 17
\overarrowsmallerthickness length,
  18
\overarrowthickness length, 17
\overbar, 19
overbar package option, 14

overcommands package option, 13
\overleftarrow, 19
overleftarrow package option, 13
\overleftharpoondown, 19
overleftharpoondown package option,
  14
\overleftharpoonup, 19
overleftharpoonup package option, 13
\overleftrightarrow, 19
overleftrightarrow package option, 13
\overrightarrow, 18
overrightarrow package option, 13
\overrightharpoondown, 19
overrightharpoondown package option,
  13
\overrightharpoonup, 19
overrightharpoonup package option, 13

path key, 25
path options key, 25
picture command key, 26
\ProvideOverArrowCommand, 15
pstarrows package option, 15

\RenewOverArrowCommand, 15
right arrow key, 21

\SetOverArrowsMethod, 26
\SetOverArrowsMethod*, 26
shift left key, 21
shift leftright key, 21
shift right key, 21
\smallermathstyle, 17
space after arrow key, 22
space before arrow key, 22
stack macro key, 27
start key, 22
subscripts package option, 15

\TestOverArrow, 16
\TestOverArrow*, 16
thinner key, 25, 26
tikz package option, 15
tikz command key, 25
tikz options key, 24
trim key, 23
trim end key, 23
trim middle key, 23
trim start key, 23

underbar, 20
underbar package option, 14
undercommands package option, 13
\underleftarrow, 19
underleftarrow package option, 14

```

\underleftharpoondown, 20  
**underleftharpoon** package option,  
14  
\underleftharpoonup, 20  
**underleftharpoon** package option, 14  
\underleftarrow, 19  
**underleftarrow** package option,  
14  
\underrightarrow, 19  
**underrightarrow** package option, 14  
\underrightharpoondown, 20  
**underrightharpoon** package  
option, 14  
\underrightharpoonup, 19  
**underrightharpoon** package option,  
14  
\vv, 18  
\vv\*, 18  
\xjoinrel, 16

## Change History

v1.0	v1.0.1
General: Initial version . . . . .	1
General: Bug fix for under* options	29