

# The Ornaments package <sup>1</sup>

Alain Matthes

March 10, 2016

<sup>1</sup> Inspired by P.Fradin (psvectorian)

☞ ((Version 0.21))

This document describes the L<sup>A</sup>T<sub>E</sub>X package *pgfornament* and presents the syntax and parameters of the macro "pgfornament". It also provides examples and comments on the package's use. Firstly, I would like to thank Till TANTAU for the beautiful L<sup>A</sup>T<sub>E</sub>X package, namely **TikZ**. I am grateful to Vincent LE MOIGN for allowing us to distribute the ornaments <sup>2</sup> in the format Pstricks and **PGF/TikZ**. I would like to thank also Enrico GREGORIO for some great ideas used in this package. You will find at the end of this document the 196 symbols provided with the package. Next to the document you are reading, you will find documentation on the package *tikzrput*.

<sup>2</sup> <http://www.vectorian.net/> (free sample)



## Contents

<i>How to install the package</i>	5
<i>How to use the package</i>	5
<i>The main macro</i>	6
<i>Number argument</i>	6
<i>Argument and options</i>	6
<i>Examples of the use of options</i>	7
<i>Examples of symmetry</i>	8
<i>Option ydelta</i>	8
<i>Option color</i>	9
<i>Style pgfornamentstyle</i>	9
<i>Advanced options from TikZ</i>	9
<i>What is a (pgf)ornament?</i>	10
<i>Placing a vector ornament on a page</i>	11
<i>On each page with the package eso-pic</i>	11
<i>On one page with the picture environment</i>	11
<i>With TikZ, the options remember picture and overlay</i>	12
<i>Placing a vector ornament in the flow</i>	12
 <i>Directly</i>	12
<i>In the flow with TikZ</i>	12



<i>Ornament inside a node</i>	14
<i>One ornament between two nodes</i>	15
<i>How to use <b>to</b> [ornament= ...]</i>	15
<i>How to use the option <b>ornament/at</b></i>	16
<i>How to use the option <b>options</b></i>	16
<i>Ornaments : Vector Symbols</i>	17
<i>Symbols part 1</i>	17
<i>Symbols part 2</i>	18
<i>Ornaments : Vector Corners</i>	19
<i>Ornaments : Vector Lines</i>	20
<i>Ornaments : Animals part 1</i>	21
<i>Ornaments : Animals part 2</i>	22
<i>Ornaments : Hands</i>	23
<i>Ornaments : Humans</i>	23
<i>Ornaments : Objects part 1</i>	24
<i>Ornaments : Objects part 2</i>	25
<i>Application : Creating a frame</i>	27
<i>Application : Frame around a text</i>	28
<i>Application : text inside a frame</i>	29
<i>Application : other way to get a pentagon</i>	30
<i>Package <b>tikzrput</b></i>	30
<i>Example with <b>\rput</b></i>	30
<i>Ornament with <b>\rput</b></i>	30
<i>Examples from <b>psvectorian</b></i>	31
<i>Large Title – e01</i>	31
<i>Cover with frame – e02</i>	31
<i>Little Title – e03</i>	32
<i>Advanced usage</i>	32
<i>Look at the code</i>	32
<i>How to use the code differently</i>	33
<i>Define a symbol with Inksape</i>	34
<i>From .eps or .mps file</i>	35
<i>Problem</i>	35



*List of Figures*

1	Minimal code for vectorian ornaments	5
2	Result of the minimal code	5
3	Vectorian ornament n° 1	6
4	Vectorian ornament n° 2	6
5	am ornament n° 1	6
6	Vertical symmetry	8
7	Horizontal symmetry	8
8	Central symmetry	8
9	How to use tkznameydelta	8
10	How to use tkznamecolor	9
11	How to use the style <code>pgfornamentstyle</code>	9
12	How to add <b>TikZ</b> ' styles	9
13	Minimal code to get an ornament	10
14	Assembling of ornaments version 2	13
15	Assembling of ornaments version 1	13
16	Style with node	14
17	Node in the flow	14
18	One ornament between two nodes	15
19	Two ornaments between two nodes	15
20	A pentagon	15
21	at	16
22	How options	16
23	Creating a frame	27
24	A poem	28
25	Text inside a frame with a tikzpicture's environment	29
26	A pentagon	30
27	Example with <code>\rput</code>	30
28	Placement with <code>rput</code>	31
29	...	31
30	Example named e01 in <code>psvectorian</code>	31
31	Example named e03	32
32	Usage of another family	34
33	Symbol from <code>Inskape</code>	35
34	Symbol from <code>.eps</code> file	35

  
*List of Tables*

1	List of options for the pgfornament macro.	6
2	List of symbols (part 1).	17
3	A list of symbols (part 2).	18
4	A list of corners	19
5	A list of lines.	20
6	A list of Animals.	21
7	A list of Animals.	22
8	A list of hands .	23
9	A list of humans .	23
10	A list of objects .	24
11	A list of objects .	25



### *How to install the package*

With TeXLive, if you need to install it by yourself, a TDS compliant zip archive is provided (pgfornament.zip). Just download that file, and unpack it in your TDS directory ( /texmf for Unix-like systems).

- pgfornament must to be in /texmf/tex/latex
- pgflibraryvectorian.code.tex must to be in /texmf/tex/latex
- pgflibraryam.code.tex must to be in /texmf/tex/latex
- the folder vectorian must to be in /texmf/tex/generic
- the folder am must to be in /texmf/tex/generic

With MiKTeX, copy folder pgfornament into C:\texmf\tex\latex, then run MiKTeX Options . In the File name database section, click on Refresh now.

### *How to use the package*

You only need to add

```
\usepackage{ornament}
```

or

```
\usepackage[object=vectorian]{ornament}
```

in your preamble. The pgfornament package loads TikZ.

Without any options, ornament package uses the vectorian symbols. If you want to use other symbols, you give the name of the list of symbols like this :

```
\usepackage[object=am]{ornament}.
```

I create am to show you how to create new symbols and how to use it (see the section 7). You can see below, the minimum code to get a vector ornament.

```
\documentclass{scrartcl}
\usepackage{pgfornament}
\begin{document}
\pgfornament[width = 2cm,
             color = red]{1}
\end{document}
```

Figure 1: Minimal code for vectorian ornaments



Figure 2: Result of the minimal code

### The main macro

The macro `\pgfornament` draws the object linked to the given number, with the vectorian family this number is between 1 and now 196. This macro can be used alone, or inside a picture. It's defined by an environment `tikzpicture` placed at the current point.

The objects displayed depend of the option used when `\pgfornament` is called. The specifications of the `\pgfornament` command is:

```
\pgfornament[⟨options⟩]{number}
```

The result is a picture defined by a `tikzpicture` environment.

### Number argument

The number designs an object of a list by a rank. With you get the figure 3

```
\usepackage{ornament}
...
\pgfornament[width=2cm]{1}
```

with

```
\usepackage{ornament}
...
\pgfornament[width=2cm]{2}
```

and with

```
\usepackage[object=am]{ornament}
...
\pgfornament[width=4cm]{1}
```

### Argument and options

The macro has six options. You have four possibilities for the last option `symmetry`. The next table describes these options.

name	default	definition
<code>scale</code>	1	ratio of height to width is unchanged
<code>width</code>	{}	set the width, ratio unchanged
<code>height</code>	{}	set the height, ratio unchanged
<code>color</code>	black	color of the ornament
<code>opacity</code>	1	nb inf 1, opacity of the ornament
<code>ydelta</code>	0 pt	value to adjust vertically the ornament
<code>symmetry=v</code>	none	vertical symmetry
<code>symmetry=h</code>	none	horizontal symmetry
<code>symmetry=c</code>	none	central symmetry
<code>symmetry=none</code>	none	no symmetry by default

you get the figure



Figure 3: Vectorian ornament n° 1

you get



Figure 4: Vectorian ornament n° 2

you get the figure

Figure 5: am ornament n° 1

Table 1: List of options for the `pgfornament` macro.

*Examples of the use of options*

## 1. Option scale

```
\pgfornament[scale=0.25]{77}
```



## 2. Option width

```
\pgfornament[width=5cm]{77}
```



## 3. Option height

```
\pgfornament[height=1cm]{77}
```



## 4. Option color

```
\pgfornament[height=1cm,color=green!20!black]{77}
```



## 5. Option opacity

```
\pgfornament[height=1cm,color=green!20!black,opacity=0.2]{77}
```



## 6. Option symmetry=h

```
\pgfornament[height=1cm,symmetry=h]{77}
```



## 7. Option symmetry=v

```
\pgfornament[height=1cm,symmetry=v]{77}
```




## 8. Option symmetry=c




```
\pgfornament[height=1cm,symmetry=c]{77}
```

### Examples of symmetry

#### 1. Symmetry vertical axis



#### 2. Symmetry horizontal axis



#### 3. Symmetry with respect to the origin





Figure 6: Vertical symmetry

Figure 7: Horizontal symmetry

Figure 8: Central symmetry

### Option *ydelta*

```
\pgfornament[color=MidnightBlue,width=2cm,ydelta=-10pt]{25}%  
\pgfornament[color=PineGreen,width=2cm]{25}%  
\pgfornament[color=Periwinkle,width=2cm,ydelta=+10pt]{25}%
```




Figure 9: How to use tkznameydelta

*Option color*

```
\pgfornament[color=MidnightBlue,width=2cm]{24}%
```

*Style pgfornamentstyle*

This style can modify some options like the color and also how to fill the symbol when it's possible.

```
\begin{tikzpicture}
\tikzset{pgfornamentstyle/.style={
  fill=SpringGreen,
  fill opacity=.5,
  line width=1pt}}%
\pgfornament[color=OliveGreen,scale=2,anchor=south]{24}%
\end{tikzpicture}
```

*Advanced options from TikZ*

```
\begin{tikzpicture}
\tikzset{pgfornamentstyle/.style={draw=Periwinkle,
  fill=SpringGreen}}%
\node[draw=Periwinkle,circle,anchor=center,
  inner sep=0pt,fill=GreenYellow] at (0,0){%
\pgfornament[anchor=center,scale=2]{24}};
\end{tikzpicture}
```




Figure 10: How to use tkznamecolor




Figure 11: How to use the style pgfornamentstyle

Figure 12: How to add TikZ' styles

## What is a (pgf)ornament?


When you write in your document `\pgfornament{1}`, you get the first ornament of a family (by default `vectorian`'s family). This ornament is a vector object defined by an environment `tikzpicture`.

```
\begin{tikzpicture}[%
  baseline=({[yshift=\pgfornamentydelta]%
    current bounding box.\pgfornamentanchor}),
  pgfornamentstyle]
  \pgftransformscale{\pgfornamentscale}%
  \pgf@ornament{#2}%
\end{tikzpicture}%
```

You can modify the aspect of the picture if you change `\pgfornamentscale`, or `pgfornamentstyle`. With `\pgfornamentydelta`, or `\pgfornamentanchor` you can move the picture but this depends on the different environments. The next code gives the picture 13. I chose this method so that the use is as simple as possible.

```
\documentclass{scrartcl}
\usepackage{pgfornament}
\begin{document}
\pgfornament{1}
\end{document}
```

The ornament is placed in a rectangle<sup>3</sup>.



On the last figure, I represent all the anchors that you can use. Now you will see how to place this picture on a page, in the flow of text or inside a complex picture.




Figure 13: Minimal code to get an ornament

<sup>3</sup> You can find the dimensions of this shape in the file `pgflibraryvectorian.code.tex`. The name of this file depends of the name of the vector family. By default actually it's `vectorian`.

*Placing a vector ornament on a page**On each page with the package `eso-pic`*

You may have noticed the existence of an ornament placed at each corner of the pages. The next code explains how to do this. The only part of the code linked to `pgfornament` is to use the macro `\pgfornament`. To put the object at the right place on the page, we need to consider its width.

Perhaps you saw the ornaments in each corner of each page I used the package `eso-pic` and the next code. The macro `\put` places the ornament at a point but you need to change correctly the anchor.

```
\usepackage{eso-pic}
\makeatletter
\AddToShipoutPicture{%
\begingroup
\setlength{\@tempdima}{2mm}%
\setlength{\@tempdimb}{\paperwidth-\@tempdima-2cm}%
\setlength{\@tempdimc}{\paperheight-\@tempdima}%
\put(\LenToUnit{\@tempdima},\LenToUnit{\@tempdimc}){%
\pgfornament[anchor=north west,width=2cm]{63}}
\put(\LenToUnit{\@tempdima},\LenToUnit{\@tempdima}){%
\pgfornament[anchor=south west,width=2cm,symmetry=h]{63}}
\put(\LenToUnit{\@tempdimb},\LenToUnit{\@tempdimc}){%
\pgfornament[anchor=north east,width=2cm,symmetry=v]{63}}
\put(\LenToUnit{\@tempdimb},\LenToUnit{\@tempdima}){%
\pgfornament[anchor=south east,width=2cm,symmetry=c]{63}}
\endgroup
}
\makeatother
```

*On one page with the `picture` environment*

The next code is used to delimit the text area on the page defined by the `tufte` class.<sup>4</sup>

<sup>4</sup> `\strippt` is defined by `\let\strippt\strip@pt`

```
\newcommand{\eachpageornament}{%
\unitlength=1pt
\begin{picture}(0,0)%
\put(0,0){\pgfornament[width=1cm]{41}};%
\put(\strippt\textwidth,0){%
\pgfornament[width=1cm,symmetry=v]{41}};%
\put(0,-\strippt\textheight){%
\pgfornament[width=1cm,symmetry=h]{41}};%
\put(\strippt\textwidth,-\strippt\textheight){%
\pgfornament[width=1cm,symmetry=c]{41}};%
\end{picture}}%
\eachpageornament
```

With `TikZ`, the options `remember picture` and `overlay`

You can without `eso-pic` but with `TikZ` get the same result on one page with the next macro. `remember picture` is obligatory, this option tells `TikZ` that it should attempt to remember the position of the current picture on the page, you need to compile twice if you use such code. The option `overlay` switches the computation of the bounding box so the pictures are not in the flow of the text and they don't modify the layout.

```
\newcommand{\eachpageornament}{%
\begin{tikzpicture}[remember picture, overlay]
  \node[anchor=north west] at (current page.north west){%
    \pgfornament[width=2cm]{63}};
  \node[anchor=north east] at (current page.north east){%
    \pgfornament[width=2cm,symmetry=v]{63}};
  \node[anchor=south west] at (current page.south west){%
    \pgfornament[width=2cm,symmetry=h]{63}};
  \node[anchor=south east] at (current page.south east){%
    \pgfornament[width=2cm,symmetry=c]{63}};
\end{tikzpicture}
}
```

*Placing a vector ornament in the flow*



*Directly*



The next code show you the effect of different choice of anchor.



```
{ \color{black}baseline \pgfsetfillopacity{0.2}%
\fbx{\pgfornament[anchor=south,width=2cm]{69}}%
\fbx{\pgfornament[width=2cm]{69}}%
\fbx{\pgfornament[anchor=north,width=2cm]{69}}%
\pgfsetfillopacity{1} baseline }
```

Perhaps you are interesting by the code to modify the subsection?

```
\subsection{\protect\pgfornament[anchor=south,width=1cm]{78}\
  Directly \
\protect\pgfornament[anchor=south,width=1cm,symmetry=v]{78}}
```

*In the flow with `TikZ`*

Generally, the best way is to place the ornament inside a node and the node inside an environment `tikzpicture`. You can need to specify

the position of the node inside the *tikzpicture* and you can add an anchor to place exactly the ornament like you want.

```
\begin{tikzpicture}
  \foreach \a in {0,45,...,315}
    \node[anchor=west,rotate=\a,inner sep=0pt,xshift=12pt] {%
      \pgfornament[width=1cm]{88}};
\end{tikzpicture}
```

```
\begin{tikzpicture}
  \foreach \a in {0,45,...,315}
    \node[anchor=west,rotate=\a,inner sep=0pt] {%
      \pgfornament[width=1cm]{88}};
\end{tikzpicture}
```

*Remark : It's difficult to get the same result with `\put` and `\rotatebox` but it's easy with the rotating package.*

```
\foreach \a in {0,45,...,315}{%
  \turnbox{\a}{\pgfornament[width=1cm]{88}}}%
```




Figure 14: Assembling of ornaments version 2





Figure 15: Assembling of ornaments version 1



### Ornament inside a node

This method is very useful and flexible because it's possible to use the options and styles with the command `\node`. You can modify the style `pgfornamentstyle`<sup>5</sup>.

```
\tikzset{pgfornamentstyle/.style={%
  draw=green!20!black,inner sep=0pt,fill=orange,
  fill opacity=.5,scale=2,ultra thick}}%
\tikz\node {\fbox{\pgfornament{3}}};
```




Figure 16: Style with node

☞ If we use a `tikzpicture` inside the flow then it's very useful to know how to place the picture. The important part of the code is :

```
\tikz[baseline=(current bounding box.south)]
```

☞ Don't forget to use `inner sep =0pt` because you can get undesirable space around the object.

```
baseline\tikz[baseline]
\node[inner sep=0pt]{\fbox{\pgfornament[width=2cm]{3}}};
baseline
\tikz[baseline=(current bounding box.south)]
\node[inner sep=0pt]{\fbox{\pgfornament[width=2cm]{3}}};
baseline
\tikz[baseline=(current bounding box.north)]
\node[inner sep=0pt]{\fbox{\pgfornament[width=2cm]{3}}};
baseline
```



Figure 17: Node in the flow

### One ornament between two nodes

I created an option for the `to` command. You only need to call an ornament with `ornament=number`.

```
\draw (A) to [object = <number>] (B) ;
```

#### How to use `to [ornament= ...]`

This code shows how to place an ornament between two nodes. The width of the ornament is automatically calculate.

```
\begin{tikzpicture}
\node (A) at (0,0) {};
\node (B) at (5,2) {};
\draw [help lines,color=Maroon!60] (0,0) grid (5,2);
\draw [fill=Maroon!30] (A) circle (2pt) (B) circle (2pt);
\draw [orange] (A) to [ornament=88] (B);
\end{tikzpicture}
```




Figure 18: One ornament between two nodes

The next code shows how to place two ornaments between two nodes.

```
\begin{tikzpicture}
\node (A) at (0,0) {};
\node (B) at (5,2) {};
\draw [help lines,color=Maroon!60] (0,0) grid (5,2);
\draw [fill=Maroon!30] (A) circle (2pt) (B) circle (2pt);
\path (A)-(B) coordinate[pos=.5] (c1);
\draw [orange] (A) to [ornament=84]
(c1) to [ornament=84] (B);
\end{tikzpicture}
```



Figure 19: Two ornaments between two nodes

#### Example with a pentagon

```
\begin{tikzpicture}[every node={anchor=center,
inner sep=0pt}]
\node[regular polygon, regular polygon sides=5,
rotate=36,minimum size=6cm,inner sep=0pt](s) {};
\path (s.side 1) to [ornament=83] (s.side 2)
to [ornament=83] (s.side 3)
to [ornament=83] (s.side 4)
to [ornament=83] (s.side 5)
to [ornament=83] (s.side 1);
\end{tikzpicture}
```




Figure 20: A pentagon

### How to use the option `ornament/at`

It's possible to move the ornament on the line AB. You only need to write `at = number` where number is a percent like `pos`.

```
\begin{tikzpicture}
\node (A) at (0,0) {};
\node (B) at (4,0) {};
\draw [help lines,color=Maroon!60] (0,-1) grid (4,1);
\path (A.center) to [ornament=84,ornament/at=0] (B.center);
\path (A.center) to [ornament=84,ornament/at=1] (B.center);
\end{tikzpicture}
```




Figure 21: `at`

### How to use the option `options`

If an ornament is misplaced we can move it up or down. Look at the code to see how to use `options`.

```
\begin{tikzpicture}
\node (A) at (0,0) {};
\node (B) at (5,2) {};
\draw [help lines,color=Maroon!40] (0,0) grid (5,2);
\draw [fill=Maroon!20] (A) circle (2pt) (B) circle (2pt);
\path (A.center) to [ornament=84,
options/.append style={yshift=1pt}] (B.center);
\end{tikzpicture}
```




Figure 22: How `options`

*Ornaments : Vector Symbols*

Here a list of the first thirty elements

*Symbols part 1*

1)		2)	
3)		4)	
5)		6)	
7)		8)	
9)		10)	
11)		12)	
13)		14)	
15)		16)	
17)		18)	
19)		20)	
21)		22)	
23)		24)	
25)		26)	
27)		28)	
29)		30)	

Table 2: List of symbols (part 1).

*Symbols part 2*

The next list is about symbols of decoration. The design is more sophisticated. Be careful indices range from sixty-five to seventy-nine.

65)		66)	
67)		68)	
69)		70)	
71)			
		72)	
73)		74)	
75)		76)	
77)		78)	
79)			

Table 3: A list of symbols (part 2).

*Ornaments : Vector Corners*

The next list of ornaments concerns objects to place in the corners of a figure. Half of them is not useful because it is obtained by symmetry of the other.

31)		32)	
33)		34)	
35)		36)	
37)		38)	
39)		40)	
41)		42)	
61)		62)	
63)		64)	
97)		98)	
131)		132)	
194)		195)	
140)		141)	

Table 4: A list of corners

*Ornaments : Vector Lines*

The next list concerns symbols used to make a line.


Table 5: A list of lines.



*Ornaments : Animals part 1*

The next list concerns symbols with animals.

Table 6: A list of Animals.

90)		91)	
100)			
102)		104)	
106)		107)	
108)		109)	
110)		111)	
112)		113)	
158)		159)	

*Ornaments : Animals part 2*

The nex list concerns symbols with animals.

Table 7: A list of Animals.

100)		
122)		123) 
124)		161) 
133)		134) 
135)		136) 
156)		157) 
158)		159) 
190)		193) 
137)		

*Ornaments : Hands*

The next list concerns symbols used to make a line.



Table 8: A list of hands .

Remark : Ornaments 154 and 155 are identic but their sizes are smaller.

*Ornaments : Humans*

The next list concerns symbols used to make a line.




Table 9: A list of humans .

Remark : Ornaments 143, 144 and 145, 146 are identic but their sizes are different.

*Ornaments : Objects part 1*

The next list concerns symbols used to make a line.

Table 10: A list of objects .


114)		115)	
116)		117)	
118)		119)	
120)		121)	
126)		127)	
128)		129)	
130)		131)	
147)		148)	

*Ornaments : Objects part 2*

The next list concerns symbols used to make a line.

Table 11: A list of objects .

162)		163)	
164)		165)	
166)		167)	
168)		169)	
170)		171)	
172)		173)	
174)		175)	
176)		177)	
178)		179)	
180)		181)	
182)		183)	



*Application : Creating a frame*

Remark : Corners are the same dimensions ( width = height )




Figure 23: Creating a frame

```

\begin{tikzpicture}[color=Maroon,
                    every node/.style={inner sep=0pt}]
\draw[help lines] (-6,-6) grid (6,6);
\node[minimum size=12cm] (vecbox){};
\node[anchor=north west] at (vecbox.north west)
    {\pgfornament[width=5cm]{61}};
\node[anchor=north east] at (vecbox.north east)
    {\pgfornament[width=5cm,symmetry=v]{61}};
\node[anchor=south west] at (vecbox.south west)
    {\pgfornament[width=5cm,symmetry=h]{61}};
\node[anchor=south east] at (vecbox.south east)
    {\pgfornament[width=5cm,symmetry=c]{61}};
\end{tikzpicture}

```

*Application : Frame around a text*

I chose a poem to illustrate this theme.




Figure 24: A poem

The poem is placed in a node named `Text`. Then we can place the corners relatively to four anchors of the node `Text`. Finally with the macros `\gformenthline` and `\gformentvline` it's possible to finish the frame.

```

\begin{tikzpicture}[every node/.style={inner sep=0pt}]
\node[text width=8cm,align=center](Text){%
  In visions of the dark night ... } ;
\node[shift={(-1cm,1cm)},anchor=north west](CNW)
at (Text.north west) {\pgforment[width=1.75cm]{61}};
\node[shift={(1cm,1cm)},anchor=north east](CNE)
at (Text.north east) {\pgforment[width=1.75cm,symmetry=v]{61}};
\node[shift={(-1cm,-1cm)},anchor=south west](CSW)
at (Text.south west) {\pgforment[width=1.75cm,symmetry=h]{61}};
\node[shift={(1cm,-1cm)},anchor=south east](CSE)
at (Text.south east) {\pgforment[width=1.75cm,symmetry=c]{61}};
\pgformenthline{CNW}{CNE}{north}{87}
\pgformenthline{CSW}{CSE}{south}{87}
\pgformentvline{CNW}{CSW}{west}{87}
\pgformentvline{CNE}{CSE}{east}{87}
\end{tikzpicture}

```

*Application : text inside a frame*

Firstly we build the frame with the help of nodes and then we place the text in a node relatively to others nodes.




Figure 25: Text inside a frame with a tikzpicture's environment

```

\newcommand{\framesize}{8 cm}
\begin{tikzpicture}[color=Maroon,
                  transform shape,
                  every node/.style={inner sep=0pt}]
\node[minimum size=\framesize,fill=Beige!10](vecbox){};
\node[anchor=north west] at (vecbox.north west){%
  \pgfornament[width=0.2*\framesize]{63}};
\node[anchor=north east] at (vecbox.north east){%
  \pgfornament[width=0.2*\framesize,symmetry=v]{63}};
\node[anchor=south west] at (vecbox.south west){%
  \pgfornament[width=0.2*\framesize,symmetry=h]{63}};
\node[anchor=south east] at (vecbox.south east){%
  \pgfornament[width=0.2*\framesize,symmetry=c]{63}};
\node[anchor=north] at (vecbox.north){%
  \pgfornament[width=0.6*\framesize,symmetry=h]{46}};
\node[anchor=south] at (vecbox.south){%
  \pgfornament[width=0.6*\framesize]{46}};
\node[anchor=north,rotate=90] at (vecbox.west){%
  \pgfornament[width=0.6*\framesize,symmetry=h]{46}};
\node[anchor=north,rotate=-90] at (vecbox.east){%
  \pgfornament[width=0.6*\framesize,symmetry=h]{46}};
\node[inner sep=6pt] (text) at (vecbox.center){\Huge Ornaments};
\node[anchor=north] at (text.south){%
  \pgfornament[width=0.5*\framesize]{75}};
\node[anchor=south] at (text.north){%
  \pgfornament[width=0.5*\framesize,symmetry=h]{75}};
\end{tikzpicture}

```

### Application : other way to get a pentagon

We can place ornaments manually but the last method can also be used .<sup>6</sup>

```
\begin{tikzpicture}[every node={anchor=center,inner sep=0pt}]
  \node[regular polygon,
    regular polygon sides=5,
    minimum size=5cm,
    inner sep=0pt](s) {};
  \getornamentlength{s}{corner 1}{s}{corner 2}
  \node[rotate=216] at (s.side 1)
    {\pgfornament[width=\ornamentlen]{88}};
  \node[rotate=288] at (s.side 2)
    {\pgfornament[width=\ornamentlen]{88}};
  \node[rotate=0] at (s.side 3)
    {\pgfornament[width=\ornamentlen]{88}};
  \node[rotate=72] at (s.side 4)
    {\pgfornament[width=\ornamentlen]{88}};
  \node[rotate=144] at (s.side 5)
    {\pgfornament[width=\ornamentlen]{88}};
\end{tikzpicture}
```

<sup>6</sup> `\getornamentlength` is ...




Figure 26: A pentagon

### Package `tikzrput`

Pstricks Users are accustomed to placing objects with `\rput`, so I created a package `tikzrput` with only one macro `\rput`. This macro is used as that of Pstricks with the same argument and options. Next to the document you are reading, you will find documentation on this package. The display of an object at the point  $(x,y)$  is realized with `\rput` of *pstricks* like this :

```
\rput[⟨refpoint⟩]{⟨angle⟩}(x,y){\pgfornament[⟨options⟩]{⟨number⟩}}
```

### Example with `\rput`

```
\foreach \a in {0,4,...,356}{%
  \rput(\a;2){$\bullet$}%
}
\rput[B](0;0){Circle}%
```




Figure 27: Example with `\rput`

### Ornament with `\rput`

```
\begin{picture}(5,4)
  \rput(2,1){\pgfornament[width=2cm]{1}}
  \rput(4,2){\pgfornament[width=2cm]{2}}
\end{picture}
```

Pour rappel,

```
\begin{tikzpicture}
  \draw[help lines] (0,0) grid (6,4);
  \draw[use as bounding box] (0,0) rectangle (6,4);
  \node[inner sep=0pt,] at (2,1){%
    \pgfornament[width=2cm,color=CadetBlue]{3}};
  \node[anchor=south,inner sep=0pt] at (4,2){%
    \pgfornament[color=CadetBlue,width=2cm]{3}};
\end{tikzpicture}
\caption{Placement with nodes}
```

### Examples from psvectorian

#### Large Title – e01

This example is given here :

<http://melusine.eu.org/syracuse/pstricks/vectorian/e01.tex> . I use the macro `rput` from my package `tikzrput` to get the figure with the same code. I only replace `\psvectorian` by `\pgfornament`.



```
\rput[r](-3pt,3pt){\pgfornament[scale=.35]{72}}
\large{Motifs d'ornements}%
\rput[l](3pt,3pt){\pgfornament[scale=.35]{73}}\
\rput(0,0){\pgfornament[scale=.5]{85}}
```

#### Cover with frame – e02

This example is given here

<http://melusine.eu.org/syracuse/pstricks/vectorian/e02.tex>  
I need `tikzpicture` and `\draw` to replace `pspicture` and `\psframe`.

```
\begin{tikzpicture}[color=blue]
  \draw[use as bounding box,thin] (-5,-5) rectangle (5,5);
  \node {\rput[tl](-3,5){\pgfornament[width=6cm]{71}}
  \rput[bl](-3,-5){\pgfornament[width=6cm,,symmetry=h]{71}}
  %coins
  \rput[tl](-5,5){\pgfornament[width=2cm]{63}}
  \rput[tr](5,5){\pgfornament[width=2cm,,symmetry=v]{63}}
  \rput[bl](-5,-5){\pgfornament[width=2cm,,symmetry=h]{63}}
```




Figure 28: Placement with `rput`




Figure 29: ...

Figure 30: Example named `e01` in `psvectorian`

```

\put[br](5,-5){\pgfornament[width=2cm,symmetry=c]{63}}
% côtés
\put[b1]{-90}(-5,3){\pgfornament[width=6cm]{46}}
\put[b1]{90}(5,-3){\pgfornament[width=6cm]{46}}
%texte+soulignement+chapeau
\put(0,0){\Huge Ornaments}
\put[t](0,-0.5){\pgfornament[width=5cm]{75}}
\put[b](0,0.5){\pgfornament[width=5cm]{69}}
% oiseaux
\put[tr]{-30}(-1,2.5){\pgfornament[width=2cm]{57}}
\put[t1]{30}(1,2.5){\pgfornament[width=2cm,symmetry=v]{57}}};
\end{tikzpicture}

```

### Little Title – e03

This example is given here

<http://melusine.eu.org/syracuse/pstricks/vectorian/e03.tex>

I corrected a little problem with blank space around the text.

```

\begin{center}
\put[r]{-2pt,6pt}{\pgfornament[,height=1cm]{21}}
{\Large Texte}%
\put[l]{2pt,6pt}{\pgfornament[height=1cm]{23}}
\end{center}

```



Figure 31: Example named e03

### Advanced usage

#### Look at the code

The package first define the name of the family of ornament `\vectorian` by default it's `vectorian`.

```

\begin{tikzpicture}[%
  baseline={([yshift=\pgfornamentydelta]%
  current bounding box.\pgfornamentanchor)},pgfornamentstyle]
  \pgftransformscale{\pgfornamentscale}%
  \pgf@ornament{#2}%
\end{tikzpicture}%

```

Options for placement are `yshift=\pgfornamentydelta` and `\pgfornamentanchor`. Options for aspect are `pgfornamentstyle` and `\pgfornamentscale`. The object is called by `\pgf@ornament`. This macro define locally other macros used for creating the symbols and it loads the symbol with `\@@input \OrnamentsFamily#1.pgf..` The symbol with the rank `#1` in the family `\OrnamentsFamily` is loaded.

```

\def\pgf@ornament#1{%
\beginpgfgroup
\def\i{\pgfusepath{clip}}%
\let\o\pgfpathclose
\let\s\pgfusepathqfillstroke
\def\p ##1##2{\pgfpoint{##1bp}{##2bp}}%
\def\m ##1 ##2 {\pgfpathmoveto{\p{##1}{##2}}}%
\def\l ##1 ##2 {\pgfpathlineto{\p{##1}{##2}}}%
\def\r ##1 ##2 ##3 ##4 {\pgfpathrectangle{\p{##1}{##2}}{\p{##3}{##4}}}%
\def\c ##1 ##2 ##3 ##4 ##5 ##6 {%
\pgfpathcurveto{\p{##1}{##2}}{\p{##3}{##4}}{\p{##5}{##6}}}%
\@input \OrnamentsFamily#1.pgf%
\endpgfgroup}%

```

A symbol : the next code is used to define the first object of the family **am**. For example I created two very simple vector ornaments `am1.pgf`<sup>7</sup> and `am2.pgf`. Actually the family **am** is only composed by two elements.

The real definition of an object uses a lot of bytes, with the mechanism<sup>8</sup> described above, I can save the object like this :

```

\m 0 0
\c 50 0 150 0 200 16
\c 250 0 350 0 400 0
\l 400 1
\c 350 0 250 0 200 22
\c 150 0 50 0 0 1
\l 0 0
\s
\endinput

```

<sup>7</sup> The next code defines this ornament

<sup>8</sup> I received an useful help from *Enrico Gregorio*

### *How to use the code differently*

For example you can create a new macro to call an object of another family and you can modify the object.

```

\makeatletter
\newcommand{\callornament}[1]{%
\beginpgfgroup
\def\i{\pgfusepath{clip}}%
\let\o\pgfpathclose
\let\s\pgfusepathqfillstroke
\def\p ##1##2{\pgfpoint{##1bp}{##2bp}}%
\def\m ##1 ##2 {\pgfpathmoveto{\p{##1}{##2}}}%
\def\l ##1 ##2 {\pgfpathlineto{\p{##1}{##2}}}%
\def\r ##1 ##2 ##3 ##4 {\pgfpathrectangle{\p{##1}{##2}}{\p{##3}{##4}}}%
\def\c ##1 ##2 ##3 ##4 ##5 ##6 {%
\pgfpathcurveto{\p{##1}{##2}}{\p{##3}{##4}}{\p{##5}{##6}}}%

```

```
\@input #1\relax
\m 0 0 \l 400 0 \o\s
\endgroup}
\makeatother
```

```
\tikz[scale=.5] \callornament{am1.pgf} ;
```

---

Figure 32: Usage of another family

### Define a symbol with Inksape

You can create a symbol with **Inksape**, then you save the symbol with the format **LaTeX with Pstricks**.

```
%LaTeX with PStricks extensions
%%Creator: inkscape 0.48.2
%%Please note this file requires PStricks extensions
\psset{xunit=.5pt,yunit=.5pt,runit=.5pt}
\begin{pspicture}(744.09448242,1052.36218262)
{
\newrgbcolor{curcolor}{0 0 0}
\pscustom[linewidth=1,linicolor=curcolor]
{
\newpath
\moveto(231.428,665.714)
\curveto(235.869,658.981)(224.543,656.406)(220.238,658.333)
\curveto(208.570,663.555)(209.816,679.616)(216.666,688.095)
\curveto(228.919,703.261)(252.107,700.575)(265.000,687.857)
\curveto(283.919,669.192)(279.643,638.050)(260.952,620.952)
\curveto(236.039,598.163)(196.704,604.097)(175.476,628.809)
\curveto(148.762,659.906)(156.386,707.535)(187.142,732.857)
\curveto(224.393,763.525)(280.367,754.197)(309.761,717.380)
\curveto(344.402,673.993)(333.361,609.645)(290.476,576.190)
\curveto(240.963,537.565)(168.220,550.325)(130.714,599.285)
\curveto(88.097,654.917)(102.579,736.068)(157.619,777.619)
\curveto(219.364,824.233)(308.932,808.026)(354.523,746.904)
\curveto(405.139,679.048)(387.205,581.057)(319.999,531.428)
\curveto(294.222,512.3928)(262.917,501.397)(230.928,499.848)
}
}
\end{pspicture}
```

You modify the code like this : <sup>9</sup>

```
\begin{group}
\def\i{\pgfusepath{clip}}%
\def\k{\pgfusepath{stroke}}%
\let\o\pgfpathclose
\let\s\pgfusepathqfillstroke
\def\p #1#2{\pgfqqpoint{#1bp}{#2bp}}%
\def\m #1 #2 {\pgfpathmoveto{\p{#1}{#2}}}%
\def\r #1 #2 #3 #4 {\pgfpathrectangle{\p{#1}{#2}}{%
\p{#3}{#4}}}%
\def\l #1 #2 {\pgfpathlineto{\p{#1}{#2}}}%
\def\c #1 #2 #3 #4 #5 #6 {%
\pgfpathcurveto{\p{#1}{#2}}{\p{#3}{#4}}{\p{#5}{#6}}}%
\begin{tikzpicture}
\pgftransformscale{.4}
```

<sup>9</sup> You can also modify all the coordinates if you don't want to use `\pgftransformscale`

```

\m 231.428 665.714
\c 235.869 658.981 224.543 656.406 220.238 658.333
\c 208.570 663.555 209.816 679.616 216.666 688.095
\c 228.919 703.261 252.107 700.575 265.000 687.857
\c 283.919 669.192 279.643 638.050 260.952 620.952
\c 236.039 598.163 196.704 604.097 175.476 628.809
\c 148.762 659.906 156.386 707.535 187.142 732.857
\c 224.393 763.525 280.367 754.197 309.761 717.380
\c 344.402 673.993 333.361 609.645 290.476 576.190
\c 240.963 537.565 168.220 550.325 130.714 599.285
\c 88.097 654.917 102.579 736.068 157.619 777.619
\c 219.364 824.233 308.932 808.026 354.523 746.904
\c 405.139 679.048 387.205 581.057 319.999 531.428
\c 294.222 512.392 262.917 501.397 230.928 499.848
\k
\end{tikzpicture}
\endgroup

```




Figure 33: Symbol from Inskape

From *.eps* or *.mps* file


Another symbol : <sup>10</sup>.

```

\begin{tikzpicture}
\pgftransformscale{.4}
\m 71.43 238.86
\l 310.29 238.86
\l 310.29 332.57
\l 428.57 214.29
\l 310.29 96.00
\l 310.29 189.71
\l 71.43 189.71
\l 71.43 238.86
\s
\m 453.14 381.71
\l 500.00 381.71
\l 500.00 46.86
\l 453.14 46.86
\l 453.14 381.71
\s
\end{tikzpicture}

```

<sup>10</sup> You can create a new family name **symp** and you save the new code in a file **symp1.pgf**. It's the first vector object of the new family

Figure 34: Symbol from *.eps* file

### Problem

If you got an error like "Package tikz Error: + or - expected.", perhaps there is a conflict with the babel package. It's possible to resolve this type of conflict with `\shorthandoff{!}` just before your tikzpicture. You can also write in your preamble

```

\tikzset{every picture/.prefix style={%
  execute at begin picture=\shorthandoff{!}}

```

and finally you can use `\usetikzlibrary{babel}` only with pgf 3.0 In french, you can get an error with `! :`, and `;`. Babel makes these characters activ

If you got a problem with the option `at` replace `at` by `ornament/at`.

*Index*

- TikZ package, 9, 12
- `\AddToShipoutPicture`, 11
- am family, 5
- anchor, 27
- `\anchor`, 11
- anchors, 10
- baseline, 14
- color, 29
- color option, 6, 7, 9
- current bounding box, 14
- current page, 12
- distributions
  - MiKTeX, 5
  - TeXLive, 5
- `\draw`, 31
- environments
  - pspicture, 31
  - tikzpicture, 6, 10, 13, 31
- eso-pic package, 11, 12
- every node , 29
- families
  - am, 5
  - vectorian, 5, 10
- `\foreach`, 30
- `\gformenthline`, 28
- `\gformentvline`, 28
- height option, 6, 7
- help lines, 31
- inner sep, 14
- Inskape, 34
- `\LenToUnit`, 11
- MiKTeX distribution, 5
- minimum size, 27
- `\node`, 14
- opacity option, 6, 7
- options, 16
- options(pgforment)
  - color, 6, 7, 9
  - height, 6, 7
  - opacity, 6, 7
  - pgformentstyle, 14
  - scale, 6, 7
  - symmetry=c, 6, 7
  - symmetry=h, 6, 7
  - symmetry=none, 6
  - symmetry=v, 6, 7
  - width, 6, 7
  - ydelta, 6, 8
- ornament
  - Animals part 1, 21
  - Animals part 2, 22
  - hands , 23
  - Humans , 23
  - lines, 19, 20
  - objects1 , 24
  - objects2 , 25
  - symbols1, 17
  - symbols2, 18
- ornament/at, 16
- `\OrnamentsFamily`, 32
- overlay, 12
- packages
  - TikZ, 9, 12
  - eso-pic, 11, 12
  - pgforment, 1, 5, 11
  - Pstricks, 34
  - rotating, 13
  - tikzrput, 1, 30
- pgforment
  - options, 6
- `\pgforment`, 6, 11, 31
- pgforment package, 1, 5, 11
- `\pgforment [(options)] {number}`, 6, 30
- `\pgformentanchor`, 10, 32
- `\pgformentscale`, 10, 32
- pgformentstyle option, 14
- pgformentstyle style(TikZ), 9, 10, 32
- `\pgformentydelta`, 10, 32
- `\pgfpathclose`, 34
- `\pgfpathcurveto`, 34
- `\pgfpathlineto`, 34
- `\pgfpathmoveto`, 34
- `\pgfpoint`, 34
- `\pgfusepath`, 34
- `\psframe`, 31
- pspicture environment, 31
- Pstricks package, 34
- `\psvectorian`, 31
- `\put`, 11, 13
- regular polygon, 30
- `\resetpgformentstyle`, 14
- rotate, 30
- `\rotatebox`, 13

rotating package, 13  
rput, 30  
`\rput`, 30  
`\rput`, 31  
  
scale option, 6, 7  
shorthandoff, 35  
south, 31  
`\stript`, 11  
styles(`TikZ`)  
    `pgfornamentstyle`, 9, 10, 32  
symmetry=c option, 6, 7  
symmetry=h option, 6, 7  
symmetry=none option, 6  
symmetry=v option, 6, 7  
  
TeXLive distribution, 5  
tikzpicture environment, 6, 10, 13,  
    31  
tikzrput package, 1, 30  
to, 15  
transform shape, 29  
  
`\use as bounding box`, 31  
  
vectorian family, 5, 10  
  
width option, 6, 7  
  
ydelta option, 6, 8