

The `pst-pdf` package^{*}

Rolf Niepraschk[†] Hubert Gäßlein

2008/09/16

1 Introduction

The package `pst-pdf` simplifies the use of graphics from PSTricks and other PostScript code in PDF documents. As in building a bibliography with `BIBTEX` additional external programmes are being invoked. In this case they are used to create a PDF file (`\PDFcontainer`) that will contain all this graphics material. In the final document this contents will be inserted instead of the original PostScript code.

2 Usage

2.1 Package options

active Activates the extraction mode (DVI output). An explicit declaration usually is not necessary (default in `LATEX` mode).

inactive No special actions; only the packages `pstricks` and `graphicx` are loaded (default in `VTEX`). Can be used to just convert the document with `LATEX` into a DVI file while avoiding the automatic extraction mode.

pstricks The package `pstricks` is loaded (default).

nopstricks The package `pstricks` does not get loaded. Once it is detected that `pstricks` was loaded however in some other way, the `pspicture` environment is treated as if the option “`pstricks`” was given.

draft From the `\PDFcontainer` file included graphics is displayed as frame in `pdfLATEX` mode.

final From the `\PDFcontainer` file included graphics is correctly displayed in `pdfLATEX` mode (default).

tightpage The graphics’ dimensions in the `\PDFcontainer` file match exactly those of the corresponding `TEX` boxes (default).

notightpage The dimensions of the `TEX` box corresponding to its graphics is not always correct, since a PostScript statement can draw outside its box. The option “`notightpage`” makes the graphics in the `\PDFcontainer` file to be at

^{*}This document corresponds to `pst-pdf` v1.1u, dated 2008/09/16. Thanks to Peter Dyballa for the translation.

[†]Rolf.Niepraschk@gmx.de

least the size of the whole page. To be able to make use of the graphics' in a later pdfL^AT_EX run, the \PDFcontainer file needs to be finished in a way that each graphics gets reduced in size to its visible part. For this an external programme like **pdfcrop**¹ can be useful. Its use can save declaring the option "trim" (see also section 2.4).

displaymath In PDF mode the mathematical environments **displaymath**, **eqnarray**, and **\$\$** get also extracted and included as graphics. This way additional PStricks extensions can easily be added to the contents of these environments. (Question: how do AMSL^AT_EX environments behave?)

<other> All other options are passed to **pstricks** package.

2.2 Program calls

The following table shows the course necessary to create a PDF document containing PostScript graphics². As comparison the analogous course for a bibliography is shown.

PostScript graphics	bibliography
pdflatex document.tex	pdflatex document.tex
<i>auxiliary calls</i>	
latex document.tex	
dvips -o document-pics.ps document.dvi	
ps2pdf document-pics.ps	bibtex document.aux
pdflatex document.tex	pdflatex document.tex

While creating the output only code from inside a **pspicture** or **postscript** environment is considered. PostScript graphics files, which are passed as parameter of an **\includegraphics** statement, too are included into the \PDFcontainer file. This file's name is by default **\jobname**-pics.pdf. It can be changed by re-defining the macro \PDFcontainer.

2.3 User commands

pspicture `\begin{pspicture}[(keys)] ((x0,x1))((y0,y1)) ... \end{pspicture}`
The **pspicture** environment is not available when the option "nopstricks" was given. It is to be used the same way as if in PStricks. In pdfL^AT_EX mode this environment's contents is only displayed when the \PDFcontainer file was created before.

postscript `\begin{postscript}[(keys)] ... \end{postscript}`
The **postscript** environment can contain any code except floats. In pdfL^AT_EX mode its contents is take too off the \PDFcontainer file. Other as in the **pspicture** environment the necessary space is not always preserved when the \PDFcontainer file does not exist yet.

\includegraphics `\includegraphics[(keys)]{(filename)}`

¹CTAN: support/pdfcrop/

²The TeX distribution "teTeX" contains a UNIX shell script ps4pdf which executes all the necessary steps. See: CTAN: macros/latex/contrib/ps4pdf/

To be used as in `graphics/graphicx` defined. In pdfL^AT_EX mode it is now additionally feasable to pass the name of an EPS file. Its visible contents too is taken from the `\PDFcontainer` file.

```
\includegraphicx      \includegraphicx[<keys>]{<pxfadd>}<>{<ovpfd>}[<ovpbgd>]{<filename>}
Wie im Paket psfragx definiert zu verwenden.

\savepicture        \savepicture{<name>}
The last output graphics (result of the pspicture or postscript environments or the \includegraphics statement with an PostScript file as argument) is being saved in a file under the name as given by the parameter.

\usepicture         \usepicture[<keys>]{<name>}
Die zuvor mit \savepicture gespeicherte Grafik wird ausgegeben. Der optionale Parameter entpricht dem bei der Anweisung \includegraphics möglichen.

pst-pdf-defs        \begin{pst-pdf-defs} ... \end{pst-pdf-defs}
Sollen eigene Makros oder Umgebungen definiert werden, die das Zeichen & (andere?) im Ersetzungstext enthalten, so müssen diese Definitionen von der Umgebung pst-pdf-defs umschlossen werden.
```

2.4 Command options

The behaviour of the `\includegraphics` and `\usepicture` statements and the `postscript` environment can be modified with any of the following parameters (key value syntax):

frame=<true|false> As with the `\fbox` statement a frame is drawn around the graphics. Any change of size due to rotation is taken into account. Drawing happens in pdfL^AT_EX mode; before, in creating the `\PDFcontainer` file, it is ignored. Default: false.

innerframe=<true|false> As in “frame”, but the frame is drawn around the graphics, not its box.

ignore=<true|false> If “true” no graphics is output. With `\savepicture{<name>}` the graphics can be used later in a different place via `\usepicture`. Default: false.

showname=<true|false> A caption of minimal font size records the used file’s name. Default: false.

namefont= Controls the font used when “showname=true” is set. Default: `\ttfamily\tiny`

All parameters can be set globally as in `\setkeys{Gin}{<key=>value}`.

3 Implementation

¹ `(*package)`

3.1 Package options

² `\newcommand*\ppf@TeX@mode{-1}`

```

3 \newcommand*\ppf@draft{false}
4 \newif\if@ppf@PST@used\@ppf@PST@usedtrue
5 \newif\if@ppf@tightpage \@ppf@tightpagetrue
6 \DeclareOption{active}{\OptionNotUsed}
7 \DeclareOption{inactive}{\def\ppf@TeX@mode{9}}
8 \DeclareOption{ignore}{\def\ppf@TeX@mode{999}}
9 \DeclareOption{pstricks}{\@ppf@PST@usedtrue}
10 \DeclareOption{nopstricks}{\@ppf@PST@usedfalse}
11 \DeclareOption{displaymath}{%
12   \PassOptionsToPackage{\CurrentOption{preview}}}
13 \DeclareOption{draft}{\def\ppf@draft{true}}
14 \DeclareOption{final}{\def\ppf@draft{false}}%
15   \PassOptionsToPackage{\CurrentOption{graphicx}}}

16 \DeclareOption{notightpage}{\@ppf@tightpagefalse}%
17 \DeclareOption{tightpage}{\@ppf@tightpagetrue}%
18 \DeclareOption*{%
19   \PassOptionsToPackage{\CurrentOption{pstricks}}}
20 \ProcessOptions\relax
21 \ifnum\ppf@TeX@mode=999\relax\expandafter\endinput\fi

```

3.2 Compiler tests

It is tested which TeX compiler in which mode of operation is actually used (see ‘`graphics.cfg`’ in teTeX/TeX Live). Accordingly the environments `pspicture` and `postscript` gain each a different range of functions. This test is only executed when the options `active` or `inactive` were not given.

```

22 \ifnum\ppf@TeX@mode=-1\relax
23   \begingroup
Default (TeX with a dvi-to-ps converter)
24   \chardef\x=0 %
Check pdfTeX
25   \@ifundefined{pdfoutput}{}{%
26     \ifcase\pdfoutput\else
27       \chardef\x=1 %
28     \fi
29   }%
Check VTeX
30   \@ifundefined{OpMode}{}{\chardef\x=2 }%
31 \expandafter\endgroup
32 \ifcase\x
  ⇒ DVI mode
33   \def\ppf@TeX@mode{0}%
34 \or
  ⇒ pdfTeX is running in PDF mode
35   \def\ppf@TeX@mode{1}%
36 \else
  ⇒ VTeX is running
37   \def\ppf@TeX@mode{9}%
38 \fi
39 \fi

```

```

40 \newcommand*\PDFcontainer{}
41 \edef\PDFcontainer{\jobname-pics.pdf}
42 \newcounter{pspicture}
43 \newcommand*\ppf@other@extensions[1]{}
44 \newcommand*\usepicture[2][]{}
45 \newcommand*\savepicture[1]{}

pst-pdf-defs
46 \newenvironment*{pst-pdf-defs}{%
47   \endgroup
48 %   ??? \currenvline
49 }{%
50   \begingroup
51   \def\currenvir{pst-pdf-defs}%
52 }

53 \RequirePackage{graphicx}%
54 \let\ppf@Ginclude@graphics\Ginclude@graphics
55 \let\ppf@Gin@extensions\Gin@extensions
56 \let\ppf@Gin@ii\Gin@ii
57 \newif\if@ppf@pdftex@graphic
58 \newif\if@Gin@frame\Gin@framefalse
59 \newif\if@Gin@innerframe\Gin@innerframefalse
60 \newif\if@Gin@showname\Gin@shownamefalse
61 \newif\if@Gin@ignore\Gin@ignorefalse

\ifpr@outer in fact is defined in package preview. We have to do it here too since
otherwise TeX could “stumble and fall” while parsing the \ifcase structure.
62 \newif\ifpr@outer

\ppf@is@pdfTeX@graphic Parameter #1 is the name of a graphics file with or without extension, parameter
#2 contains the valid extensions in PDF mode, parameter #3 contains the valid
extensions in DVI mode. If it works to process the graphics in PDF mode, then
the statements in #4 are executed, otherwise those in #5.
63 \newcommand*\ppf@is@pdfTeX@graphic[5]{%
64   \if@ppf@pdftex@graphicfalse%
65   \begingroup
66     \edef\pdfTeXext{#2}%

Instead of loading the found graphics, only a test on file name extension.
67   \def\Gin@setfile##1##2##3{%
68     \edef\@tempb{##2}%
69     \cfor\@tempa:=\pdfTeXext\do{%
70       \ifx\@tempa\@tempb\global\@ppf@pdftex@graphictrue\fi}%
71     \edef\Gin@extensions{##2,##3}%
72     \pr@outerfalse\ppf@Ginclude@graphics{##1}%
73   \endgroup
74   \if@ppf@pdftex@graphic#4\else#5\fi
75 }

76 \ifcase\ppf@TeX@mode\relax

```

3.3 Extraction mode (DVI output)

The `pspicture` environment retains any definition from `pstricks.tex`. Only the code from the environments `pspicture` and `postscript` as well as `\includegraphics` with PostScript files leads to records into the DVI file. The remainder of the document's code is ignored for output. After conversion of the DVI file via PostScript ("dvips") into PDF (`\PDFcontainer` file) each graphics takes exactly one page in the `\PDFcontainer` file. The `TeX` compiler with DVI output and the package option "active" both force this mode.

```
77  \PackageInfo{pst-pdf}{%
78    MODE: \ppf@TeX@mode\space (dvi -- extraction mode)}
79  \nofiles
80  \let\makeindex\empty \let\maketitle\empty
81  \AtBeginDocument{\overfullrule=1z@}%
82  \if@ppf@PST@used\RequirePackage{pstricks}\fi
83  \RequirePackage[active,dvips,tightpage]{preview}[2005/01/29]%
84  \newcommand*\ppf@PreviewBbAdjust{}%
85  \newcommand*\ppf@RestoreBbAdjust{}%
86  \let\PreviewBbAdjust\ppf@PreviewBbAdjust}%
```

The pdfL^AT_EX mode compliant graphics file formats are needed too.

```
87  \begingroup
88  \let\AtBeginDocument\gobble \let\PackageWarningNoLine\gobbletwo
89  \chardef\pdftexversion=121 %
90  \chardef\pdfoutput=1 %
91  \input{pdftex.def}%
92  \edef\x{\endgroup\def\noexpand\ppf@other@extensions{\Gin@extensions}}
93  }%
94  \x
```

In PDF mode no rules must be defined for its compliant (PNG, JPEG, PDF) graphics file formats (because of for example 'dvips' extensions). The universal EPS rule is used to at least find these files.

```
95  \AtBeginDocument{%
96    \ifpackageloaded[keyval]{%
97      \def\KV@errx#1{\PackageInfo{keyval}{#1}}%
98    }{}%
99    \ifpackageloaded[xkeyval]{%
100      \def\XKV@err#1{\PackageInfo{xkeyval}{#1}}%
101    }{}%
```

In this mode undefined keys should not be an error.

```
102  \for@tempa:=\ppf@other@extensions\dof%
103    \expandafter\let\csname Gin@rule@\@tempa\endcsname\relax}%
104  \DeclareGraphicsRule{*}{eps}{*}{}%
```

No function in this mode.

```
105  \define@key{Gin}{innerframe}[true]{}%
106  \define@key{Gin}{frame}[true]{}%
107  \define@key{Gin}{ignore}[true]{}%
108  \define@key{Gin}{showname}[true]{}%
109  \define@key{Gin}{namefont}{}%
110  \ifundefined{GPT@page}{\define@key{Gin}{page}{}{}}{}%
111  \if@ppf@tightpage\else
```

```

112      \def\PreviewBbAdjust{%
113          -600pt -600pt 600pt 600pt}%
114      \AtEndDocument{%
115          \PackageWarningNoLine{pst-pdf}{Picture container needs cropping.}}}%
116      \fi

postscript The postscript environment utilises the trim option in the same manner as does
\includegraphics (any specification without dimension is interpreted as if given
in bp).
117  \newenvironment{postscript}[1] []{%
118      \global\let\ppf@PreviewBbAdjust\PreviewBbAdjust
119      \if@ppf@tightpage
120          \begingroup
121              \setkeys{Gin}{#1}%
122              \xdef\PreviewBbAdjust{%
123                  -\Gin@vllx bp -\Gin@vly bp \Gin@vurx bp \Gin@vury bp}%
124          \endgroup
125      \fi
126      \ignorespaces
127  }%
128  {\aftergroup\ppf@RestoreBbAdjust}%

129  \PreviewEnvironment{postscript}%
130  \AtBeginDocument{%
131      \@ifundefined{PSTricksLoaded}{}%
132  }%
133  \%
}

pspicture Announce preview original definition.
134      \PreviewEnvironment{pspicture}%

psmatrix Announce preview original definition.
135      \ifundefined{psmatrix}{}%
136      \%
137      \PreviewEnvironment{psmatrix}%
138      \newcommand*\ppf@set@mode{}%
139      \newcommand*\ppf@test@mmode{}%
140      \ifmmode
141          \ifinner
142              \let\ppf@set@mode=$%
143          \else
144              \def\ppf@set@mode{$$}%
145          \fi
146      \else
147          \let\ppf@set@mode=\empty
148      \fi
149  }%
150  \let\ppf@psmatrix=psmatrix
151  \expandafter\let\expandafter\ppf@pr@psmatrix%
152      \expandafter\csname pr@\string\psmatrix\endcsname
153  \let\ppf@endpsmatrix=endpsmatrix
154  \def\psmatrix{\ppf@test@mmode\ppf@psmatrix}
155  \expandafter\def\csname pr@\string\psmatrix\endcsname{%
156      \ppf@set@mode\ppf@pr@psmatrix}%

```

```

157      \def\endpsmatrix{\ppf@endpsmatrix\ppf@set@mode}%
158      }%

```

Announce internal macro `\pst@object` to enable the use of some PSTricks code outside of `pspicture` environments. At the moment invocations of the following kind are feasible:

```

\pst@object {[<m>][*<o>][<o>]{<o>}(<o>)(<o>)(<o>)}
  (<m> = necessary, *<o> = optional, o = optional)

```

More than three optional arguments at the call's end, as in `\psline` possible, do not work yet.

```

159      \PreviewMacro[{}]*[]%
160      ?\bgroup{\#1}{\#1}}){}%
161      ?\bgroup{\#1}{\#1}}){}%
162      ?(\#1){(\#1)}}){}%
163      ?(\#1){(\#1)}}){}%
164      ?(\#1){(\#1)}}){}%
165      }]{\pst@object}}

```

Prevent multiple test-wise setting of table contents by “`tabularx`”.

```

166      \@ifundefined{tabularx}{}{%
167          \newcolumntype{X}{c}%
168          \expandafter\let\expandafter\tabularx\csname tabular*\endcsname
169          \expandafter\let\expandafter\endtabularx\csname endtabular*\endcsname
170      }%

```

Support of `\includegraphicx` from the package `psfragx`.

```

171      \ifundefined{pfx@includegraphicx}{}{%
172          \PreviewMacro[{}]{\pfx@includegraphicx}%
173      }%

```

`\Gscale@@box` Disable scaling.

```

174  \def\Gscale@@box#1#2#3{%
175      \toks@{\mbox}%
176  }

```

`\Ginclude@graphics` All graphics content of well known format (for instance EPS files) is treated in a regular way, which in this mode denotes that it is subject to `preview` functions. Other graphics content (for instance PDF files) is ignored.

```

177  \def\Ginclude@graphics#1{%
178      \ifpr@outer

```

Generally pdfTeX supported graphics formats are intended to be preferred (inclusion in final pdfTeX run). If it's a PostScript type graphics, then the original definition is in function again and registration for the `preview` package is necessary in order to convert this PostScript type graphics into PDF.

```

179      \ppf@is@pdfTeX@graphic{\#1}{\ppf@other@extensions}{\Gin@extensions}%

```

Dummy box to prevent a division by zero while scaling or rotating. Otherwise ignored.

```

180      {\rule{10pt}{10pt}}%
181      {\ppf@Ginclude@graphics{\#1}}%
182      \else

```

Inside a PostScript environment (`\pspicture` etc.) `\includegraphics` has to behave as in its original definition (only DVIPS supported graphics formats are allowed).

```

183      \ppf@Ginclude@graphics{#1}%
184      \fi
185  }%
186  \PreviewMacro[{{}}]{\ppf@Ginclude@graphics}%
187  \let\pdfliteral\gobble%
188 \or

```

3.4 pdf^LA_TE_X mode (PDF output)

When the `\PDFcontainer` file (default: `\jobname-pics.pdf`) exists, the contents of the environments `\pspicture` and `\postscript` is ignored. Instead the corresponding graphics from the `\PDFcontainer` file is used.

```

189  \PackageInfo{pst-pdf}{MODE: \ppf@TeX@mode\space (pdfTeX mode)}%
Prevent pdfTeX's message Non-PDF special ignored!.
190  \if@ppf@PST@used
191    \let\ppf@temp\AtBeginDvi\let\AtBeginDvi\gobble
192    \RequirePackage{pstricks}\let\AtBeginDvi\ppf@temp
193  \fi
194  \@temptokena{%
195    \let\Gin@PS@file@header\gobble\let\Gin@PS@literal@header\gobble
196    \let\Gin@PS@raw\gobble\let\Gin@PS@restored\gobble
197    \@ifundefined{PSTricksLoaded}{}{%
Necessary if PSTRicks < 2.0.
198    \PSTRicksOff
199    \@ifundefined{c@lor@to@ps}{\def\c@lor@to@ps#1 #2@@{}{}}{}}%
PostScript output is now inhibited and later once again.
200  \the\@temptokena
201  \expandafter\AtBeginDocument\expandafter
202  {\the\@temptokena\@temptokena{}}
203  \@ifundefined{PSTricksLoaded}{}{%

```

To parse the arguments of PSTRicks' `\pst@object` we load `preview` in active mode, but restore the default definitions of `\output` and `\shipout`. `\pr@startbox` and `\pr@endbox` serve here only to disable `\pst@object` and to load the corresponding graphics from the `\PDFcontainer` file. At present a maximum of three optional parameters in round braces (parenthesis) at the end of `\pst@object` is supported, which is sufficient, but not always enough.

```

204  \newtoks\ppf@output
205  \ppf@output\expandafter{\the\output}%
206  \let\ppf@nofiles=\nofiles \let\nofiles=\relax
207  \let\ppf@shipout=\shipout
208  \RequirePackage[active]{preview}[2005/01/29]%
209  \let\shipout=\ppf@shipout \let\ppf@shipout=\relax
210  \let\nofiles=\ppf@nofiles \let\ppf@nofiles=\relax
211  \output\expandafter{\the\ppf@output} \ppf@output{}%
\pr@startbox, \pr@endbox: simpler over original definitions.
212  \long\def\pr@startbox#1#2{%

```

```

213   \ifpr@outer
214     \toks@{\#2}%
215     \edef\pr@cleanup{\the\toks@}%
216     \setbox\@tempboxa\vbox\bgroup
217     \everydisplay{}%
218     \pr@outerfalse%
219     \expandafter\@firstofone
220   \else
221     \expandafter\@gobble
222     \fi{\#1}}%
223   \def\pr@endbox{%
224     \egroup
225     \setbox\@tempboxa\box\voidb@x
226     \ppf@@getpicture
227     \pr@cleanup}%

```

(See also the identical definition in DVI mode.)

```

228   \AtBeginDocument{%
229     \@ifundefined{pst@object}{}%
230   {%
231     \PreviewMacro[{{}*[]}{%
232       ?\bgroup{\#{\#1}{\{#1\}}}{\{#1\}}{%
233       ?\bgroup{\#{\#1}{\{#1\}}}{\{#1\}}{%
234       ?(\#{\{#1\}}{\{(\#1)\}}){\{#1\}}{%
235       ?(\#{\{#1\}}{\{(\#1)\}}){\{#1\}}{%
236       ?(\#{\{#1\}}{\{(\#1)\}}){\{#1\}}{%
237       }]{\pst@object}}{%
238     }%
239   }%

```

Too the supported file name extensions from DVI mode are needed.

```

240   \begingroup
241     \input{dvips.def}%
242     \edef\x{\endgroup\def\noexpand\ppf@other@extensions{\Gin@extensions}}%
243   \x

```

Dummy definition for in DVI mode supported file formats.

```

244   \DeclareGraphicsRule{*}{eps}{*}{}
245   \define@key{Gin}{innerframe}[true]{%
246     \lowercase{\Gin@boolkey{\#1}{innerframe}}%
247   \define@key{Gin}{frame}[true]{%
248     \lowercase{\Gin@boolkey{\#1}{frame}}%
249   \define@key{Gin}{ignore}[true]{%
250     \lowercase{\Gin@boolkey{\#1}{ignore}}%
251   \define@key{Gin}{frame@@}{%

```

(For internal use only!)

```

252   \edef\@tempa{\toks@{\noexpand\frame{\the\toks@}}}%
253   \ifcase#1\relax
254     \ifGin@innerframe\else\let\@tempa\relax\fi
255   \or
256     \ifGin@frame\else\let\@tempa\relax\fi
257   \fi
258   \@tempa
259 }%

```

```

260  \define@key{Gin}{showname}[true]{%
261    \lowercase{\Gin@boolkey{#1}{showname}}%
262  \define@key{Gin}{namefont}{%
263    \begingroup
264      \temptokena\expandafter{\ppf@namefont#1}%
265      \edef\x{\endgroup\def\noexpand\ppf@namefont{\the\temptokena}}%
266      \x
267  }%
268  \newcommand*\ppf@filename{}%
269  \newcommand*\ppf@namefont{\tiny\ttfamily}%
270  \newcommand*\ppf@Gin@keys{}%
271  \let\ppf@Gin@setfile\Gin@setfile

\Gin@setfile Save real file name and, if applicable, page number for later use.
272  \def\Gin@setfile#1#2#3{\ppf@Gin@setfile{#1}{#2}{#3}%
273    \xdef\ppf@filename{%
274      #3\ifx\GPT@page\empty\else(\GPT@page)\fi}%

\Gin@ii Examine the options “frame”, “ignore”, etc. as soon as other special cases.
275  \def\Gin@ii[#1]{%
276    \begingroup
      The value of \ifGin@innerframe has to be known before the inner frame is drawn.
      The values for \ifGin@showname and \ppf@namefont need to be available after
      rendering the graphics too. Thus beforehand and protected inside a group examine
      the options.
277    \setkeys{Gin}{#1}%
278    \temptokena{#1}\def\tempb{#2}%
      Finds empty file name when calling \usepicture.
279    \ifx\tempb\empty\else
280      \ppf@is@pdfTeX@graphic{#2}{\Gin@extensions}{\ppf@other@extensions}%

      Graphics out of \PDFcontainer are complete – scaled, rotated, etc. Don’t apply
      these things again and therefore ignore the optional parameters.
281    {%
282      \ifx\tempb\PDFcontainer
283        \temptokena{page=\GPT@page}%
284      \fi
285    }%
286    {%
287      \refstepcounter{pspicture}%
288      \temptokena{page=\the\c@pspicture}\def\tempb{\PDFcontainer}%
289    }%
290    \fi
291    \ifGin@ignore\else
      “frame@=0” = inner frame, “frame@=1” = outer frame.
292      \edef\tempa{\noexpand\ppf@Gin@ii[frame@=0,\the\temptokena,
293        frame@=1]{\tempb}}%
294      \tempa
295      \ifGin@showname
296        \ppf@namefont
297        \raisebox{-\ht\strutbox}[0pt][0pt]{\llap{\ppf@filename}}%
298        \gdef\ppf@filename{}%

```

```

299      \fi
300      \fi
301      \endgroup
302  }%
303 \IfFileExists{\PDFcontainer}{%
304 {%
\ppf@container@max The number of pages as contained in \PDFcontainer file.
305     \pdfximage{\PDFcontainer}%
306     \edef\ppf@container@max{\the\pdflastximagepages}%
307     \AtEndDocument{%
308         \ifnum\c@pspicture>\z@
A warning only makes sense when a graphics is needed at all.
309         \ifnum\c@pspicture=\ppf@container@max\else
310             \PackageWarningNoLine{pst-pdf}{%
311                 '\PDFcontainer' contains \ppf@container@max space pages
312                 \MessageBreak but \the\c@pspicture space pages are requested:
313                 \MessageBreak File '\PDFcontainer' is no more valid!
314                 \MessageBreak Recreate it
315             }%
316         \fi
317     \fi
318 }%
319 }%
320 {%
321     \def\ppf@container@max{0}%
322     \AtEndDocument{%
323         \ifnum\c@pspicture>\z@
324             \filename@parse{\PDFcontainer}%
325             \PackageWarningNoLine{pst-pdf}{%
326                 File '\PDFcontainer' not found.\MessageBreak
327                 Use the following commands to create it:\MessageBreak
328                 -----
329                 \MessageBreak
330                 latex \jobname.tex\MessageBreak
331                 dvips -o \filename@base.ps \jobname.dvi\MessageBreak
332                 ps2pdf \filename@base.ps\MessageBreak
333                 -----
334             }%
335         \fi
336     }%
337 }%
\ppf@isnum If parameter #1 is numeric, the instructions in #2, otherwise those in #3 are executed (see bibtopic.sty).
338     \newcommand\ppf@isnum[1]{%
339         \if!\ifnum#1<1\else_\fi\expandafter\@firstoftwo
340         \else\expandafter\@secondoftwo\fi}%
psmatrix Both environments ignore their contents and load instead the corresponding graphics out of the \PDFcontainer file. The value of the herein used pspicture counter's value can be used in \label/\ref.
pspicture

```

```

postscript
341   \newcommand*\ppf@set@mode{}%
342   \newcommand*\ppf@test@mmode{}%
343   \ifmmode
344     \ifinner
345       \let\ppf@set@mode=$%
346     \else
347       \def\ppf@set@mode{$$}%
348     \fi
349   \else
350     \let\ppf@set@mode=\empty
351   \fi
352 }

353 \RequirePackage{environ}%
354 \newenvironment{postscript}[1][]{}%
355   \def\@tempa{postscript}%
356   \ifx\@tempa\@currenvir
357     \def\ppf@Gin@keys{\#1}%
358   \else
359     \def\ppf@Gin@keys{}%
360   \fi
361   \ppf@@getpicture
362   \Collect@Body\@gobble}{}%
363 \AtBeginDocument{%
364   \@ifundefined{PSTricksLoaded}{}{%
365     \def\pst@@@picture[#1](#2,#3)(#4,#5){\postscript}%
366     \def\endpspicture{\endpostscript\endgroup}%
367   \@ifundefined{psmatrix}{}{%
368     \let\psmatrix=\postscript
369     \let\endpsmatrix=\endpostscript}%
370 }%
371 \@ifundefined{pfx@includegraphicx}{}{%

```

The useless redefinition of `\includegraphics` in pdf_TE_X mode (package `psfragx`) is leading to double insertion of the result. We go back to the original meaning.

```

372   \let\includegraphics=\pfx@includegraphics
373   \def\pfx@includegraphicx#1#2{\ppf@@getpicture}%
374 }%
375 }%

```

`\savepicture` Saves the recent graphics' number in a macro named `\ppf@@@#1`.

```

376 \def\savepicture#1{%
377   \expandafter\xdef\csname ppf@@@#1\endcsname{\the\pdflastximage}}%

```

`\usepicture` Inserts graphics with symbolic name #2. This name has to be declared beforehand in `\savepicture{<name>}`. Instead of a name a number can be used too, which directly addresses a graphics in the `\PDFcontainer` file. The optional parameter #1 corresponds to the one in `\includegraphics`.

```

378 \renewcommand*\usepicture[2][]{%
379   \@ifundefined{ppf@@@#2}%
380   {%
381     \ppf@isnum{#2}%
382     {\ppf@getpicture{#1}{#2}}%

```

```

383     {\@latex@error{picture '#2' undefined}\@ehc}%
384   }%
385   {%
386     \begingroup
387       \def\Ginclude@graphics##1{%
388         \xdef\ppf@filename{#2}%
389         \setbox\z@\hbox{\pdfrefximage\@nameuse{ppf@@#2}}%
390         \Gin@nat@height\ht\z@ \Gin@nat@width\wd\z@
391         \def\Gin@llx{0} \let\Gin@lly\Gin@llx
392         \Gin@defaultbp\Gin@curx{\Gin@nat@width}%
393         \Gin@defaultbp\Gin@cury{\Gin@nat@height}%
394         \Gin@bboxtrue\Gin@viewport@code
395         \Gin@nat@height\Gin@ury bp%
396         \advance\Gin@nat@height-\Gin@lly bp%
397         \Gin@nat@width\Gin@curx bp%
398         \advance\Gin@nat@width-\Gin@llx bp%
399         \Gin@req@sizes
400         \ht\z@\Gin@req@height \wd\z@\Gin@req@width
401         \leavevmode\box\z@}%
402       \define@key{Gin}{type}{}{%
403         \includegraphics[scale=1,#1]{}%
404       \endgroup
405     }%

```

\ppf@getpicture Inserts the page (graphics) with number #2 from the \PDFcontainer file. Parameter #1: any option as in \includegraphics.

```

406   \newcommand*\ppf@getpicture[2]{%
407     \tempcnta=#2\relax%
408     \ifnum\tempcnta>\ppf@container@max
409       \PackageWarningNoLine{pst-pdf}{%
410         pspicture No. \the\tempcnta space undefined}%
411     \else
412       \includegraphics[draft=\ppf@draft,#1,page=\the\tempcnta]{%
413         \PDFcontainer}%
414     \fi
415     \gdef\ppf@Gin@keys{}%

```

\ppf@@getpicture Inserts next page (graphics) from the \PDFcontainer file.

```

416   \newcommand*\ppf@@getpicture{%
417     \ifpr@outer
418       \refstepcounter{pspicture}%
419       \expandafter\ppf@getpicture\expandafter{\ppf@Gin@keys}%
420       {\the\c@pspicture}%
421     \fi}%

```

pst-pdf-defs Environment without grouping. The character & has the catcode “other”. Useful for user-defined macro definitions with e.g. psmatrix inside.

```

422   \renewenvironment*pst-pdf-defs}%
423   {%
424     \endgroup
425   %   ??? \currenvline
426   \chardef\ppf@temp=\catcode`\&%
427   \makeother\&%
428 }%

```

```

429     \catcode`\&=\ppf@temp
430     \begingroup
431     \def\@currenvir{pst-pdf-defs}%
432   }
433 \else

```

3.5 Inactive Mode

Only the packages `pstricks` and `graphicx` are loaded – no further exertion of influence. The package option “`inactive`” as soon as the VTEXcompiler force this mode.

```

434 \PackageInfo{pst-pdf}{MODE: \ppf@TeX@mode\space (inactive mode)}%
435 \newenvironment{postscript}[1][]{\ignorespaces}{}
436 \let\ppf@is@pdfTeX@graphic\relax
437 \fi
438 \InputIfFileExists{pst-pdf.cfg}{%
439   \PackageInfo{pst-pdf}{Local config file pst-pdf.cfg used}}{}%
440 </package>

```

Change History

v1.0a		v1.0g	
General: Initial version.	General: Definition of <code>\PDFcontainer</code> now with <code>\edef</code> . (RN)
v1.0b		<code>\usepicture</code> : Now <code>\usepspicture</code> does accept a numerical parameter. (RN)
General: Some code and documentation cleaning. (RN)
v1.0c		v1.0h	
General: New options “ <code>pstricks</code> ”, “ <code>nopstricks</code> ”, “ <code>draft</code> ” and “ <code>final</code> ”. (RN)	<code>\psmatrix</code> : Based no more on the comment environment from the verbatim package. (RN)
v1.0d		v1.0i	
General: Redefinition of <code>\includegraphics</code> in modes 0 and 1. Now using of eps graphics directly in pdf <small>L</small> A <small>T</small> E <small>X</small> is possible. (RN)	<code>\ppf@is@pdfTeX@graphic</code> : No more errors for given files without extensions. (RN)
v1.0e		v1.0j	
<code>postscript</code> : “ <code>trim</code> ” option added. (RN)	General: Check <code>AtBeginDocument</code> for package ‘ <code>pstricks</code> ’ even if “ <code>nopstricks</code> ” is given. (RN)
v1.0f		v1.0k	
General: Config file loading added. (RN)	<code>\Gin@setfile</code> : Show also the page number if exists. (RN)
<code>\savepicture</code> : New macro <code>\savepspicture</code> . (RN)	<code>\Gin@include@graphics</code> : Prevent division by zero. (RN)
<code>\usepicture</code> : New macro <code>\usepspicture</code> . Useful for putting a PSTricks graphic in a box or something else. (RN)	13	v1.0l	
		General: Options “ <code>framesep</code> ”, “ <code>framerule</code> ”, “ <code>linewidth</code> ” removed, “ <code>fname</code> ” and “ <code>inner-frame</code> ” added. (RN)

v1.0m	
General: New package option “notightpage” added. (RN)	1
v1.0n	
General: Changed macro names (<code>\savepicture</code> and <code>\usepicture</code>). (RN)	1
Some code cleaning. (RN)	1
v1.0o	
General: New code for “notightpage”. (RN)	6
Option “fname” renamed to “showname”. (RN)	1
v1.0p	
General: Some code and documentation cleaning. (RN)	1
v1.0q	
<code>\usepspicture</code> : Now <code>\usepspicture</code> works for all kind of graphics. (RN)	13
v1.0r	
<code>\ppf@is@pdfTeX@graphic</code> : Changed <code>\ppf@is@known@graphic</code> to <code>\ppf@is@pdfTeX@graphic</code> . Now pdfTeX graphics are preferred. (RN)	5
v1.0s	
General: Scaling e.g. of PostScript pictures now only in extraction mode. Some code cleaning. (RN)	1
<code>\Gin@ii</code> : Rewritten. (RN)	11
v1.1a	
General: Support for the internal PSTricks macro <code>\pst@object</code> . (HjG/RN)	8
v1.1b	
General: Ignore the call of <code>\nofiles</code> inside of <code>preview</code> . (RN)	9
Some code and documentation cleaning. (RN)	1
v1.1c	
General: New package option “tightpage” added. (RN)	1
Special support for “tabularx”. (RN)	8
Suppress handling of pdfTeX graphic formats in DVI mode. (RN)	6
v1.1d	
<code>\postscript</code> : Support for PSTricks environment “psmatrix”. (RN)	13
v1.1e	
General: New option “displaymath” (see preview package). (HjG/RN)	3
v1.1f	
General: Package option “ignore” reimplemented. Now the compilation of the dtx file in L ^A T _E X mode is possible. (RN)	3
v1.1g	
<code>\postscript</code> : “psmatrix” environment (preserve math mode). (RN/HjG)	13
<code>\pspicture</code> : <code>\pspicture</code> environment must still parse its arguments. (RN/HjG)	12
v1.1h	
<code>\Ginclude@graphics</code> : Check if inside of a PS-related environment (correct graphic inclusion). (RN)	8
v1.1i	
General: <code>\ifpr@outer</code> must be predefined. (HjG/RN)	5
Package option “final” also for “graphicx”. (RN)	4
<code>\Ginclude@graphics</code> : Correction of the inside check. (RN/HjG)	8
v1.1k	
General: New environment <code>pst-pdf-defs</code> : Support for PSTricks environment “psmatrix” inside user definitions. (RN,HjG)	1
v1.1l	
General: Support for the package “psfrags”. (RN)	8
v1.1m	
General: Merge english and german version of the documentation. (RN)	1
v1.1n	
General: <code>\nofiles</code> added (suggestion of Torsten Bronger).	6
v1.1o	
<code>\Gscale@@box</code> : Disable scaling. (RN)	8
v1.1p	
General: <code>\nofiles</code> makes <code>\makeindex</code> and <code>\maketoc</code> to <code>\relax</code> . <code>\empty</code> is better because of later <code>\renewcommand</code> 's.	6
v1.1p1	
General: <code>\let\output\gobble</code> before loading of “preview” added.	

	(RN)	9	page key in DVI mode.	6
v1.1q	General: Problem with “tabularx” and “threeparttable” solved. (RN)	8	v1.1t	General: Remove the line “\let\output\@gobble” be- cause of bad side effects. (RN) . . 9
v1.1r	General: Fixed values for \PreviewBbAdjust because \paperwidth is not allways defined (suggested by Will Robertson).	6	v1.1u	postscript: Using environ the en- vironment postscript is now sim- ple and more robust. (RN) . . 13
v1.1s	General: Dummy definition of the			General: \pdfoutput must be set when loading “pdftex.def” in DVI mode. (RN)
				6

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	pst-pdf-defs . . .	I
\&	426, 427, 429	\if@ppf@pdftex@graphic
\@currenvir	51, 356, 431	57, 74
\@currenvline	48, 425	\if@ppf@PST@used
\@ehc	383	4, 82, 190
\@firstofone	219	\if@ppf@tightpage
\@ifpackageloaded	96, 99	5, 111, 120
\@latex@error	383	\ifGin@frame
\@makeother	427	58, 256
\@ppf@PST@usedfalse	10	\ifGin@ignore
\@ppf@PST@usedtrue	4, 9	61, 291
\@ppf@pdftex@graphicfalse	64	\ifGin@innerframe
\@ppf@pdftex@graphicttrue	70	59, 254
\@ppf@tightpagefalse	16	\ifGin@showname
\@ppf@tightpagetrue	5, 17	60, 295
A		
\AtBeginDvi	191, 192	\ifinner
C		
\c@lor@to@ps	199	\ifmmode
\c@pspicture	288, 308,	\ifpr@outer
	309, 312, 323, 420	62, 178, 213, 417
\catcode	426, 429	\includegraphics
\Collect@Body	362	2, 372, 403, 412
\CurrentOption	12, 15, 19	\includegraphicx
D		
\DeclareGraphicsRule	104, 244	J
\define@key	105–110,	\jobname
	245, 247, 249,	41, 330, 331
	251, 260, 262, 402	K
E		
\endpostscript	366, 369	\KV@errx
\endpsmatrix	153, 157, 369	97
\endpspicture	366	L
\endtabularx	169	\leavevmode
environments:		401
postscript	2, 117, 341	\long
psmatrix	135, 341	212
pspicture	2, 134, 341	M
		\makeglossary
		80
		\makeindex
		80
		\mbox
		175
N		
\newcolumntype	167	O
\nofiles	79, 206, 210	\OptionNotUsed
P		
\PassOptionsToPackage	12, 15, 19	\output
\PDFcontainer	40, 41, 282, 288,	\overfullrule
		81

\pdf@lastximage	377	\ppf@is@pdfTeX@graphic	63, 179, 280, 436	\PreviewMacro	159, 172, 186, 231
\pdf@lastximagepages	306	\ppf@isnum	338, 381	\psmatrix	150, 152, 154, 155, 368
\pdfliteral	187	\ppf@namefont	264, 265, 269, 296	psmatrix	(environment) ... 135, 341
\pdfoutput	26, 90	\ppf@nofiles	206, 210	pspicture	(environment) . 2, 134, 341
\pdfrefximage	389	\ppf@other@extensions	43, 92, 102, 179, 242, 280	pst-pdf-defs	(environment) .. 3, 46, 422
\pdfTeXtext	66, 69	\ppf@output	204, 205, 211	\pst@@@picture	... 365
\pdfTeXversion	89	\ppf@pr@psmatrix	151, 156	\pst@object	165, 237
\pdfximage	305	\ppf@PreviewBbAdjust	84, 86, 119	\PSTricksOff	198
\pfx@includegraphics	372	\ppf@psmatrix	150, 154	R	
\pfx@includegraphicx	172, 373	\ppf@RestoreBbAdjust	85, 129	\raisebox	297
\postscript	365, 368	\ppf@set@mode	138, 142, 144, 147, 156, 157, 341, 345, 347, 350	\refstepcounter	287, 418
postscript	(environment) . 2, 117, 341	\ppf@test@emode	139, 154, 342	\rule	180
\ppf@getpicture	226, 361, 373, 416	\ppf@TeX@mode	2, 7, 8, 21, 22, 33, 35, 37, 76, 78, 189, 434	S	
\ppf@container@max	305, 309, 311, 321, 408	\ppf@shipout	207, 209	\savepicture	3, 45, 376
\ppf@draft	3, 13, 14, 412	\ppf@temp	191, 192, 426, 429	\setkeys	122, 277
\ppf@endpsmatrix	153, 157	\ppf@test@emode	139, 154, 342	\shipout	207, 209
\ppf@filename	268, 273, 297, 298, 388	\ppf@TeX@mode	2, 7, 8, 21, 22, 33, 35, 37, 76, 78, 189, 434	\string	152, 155
\ppf@getpicture	382, 406, 419	\pr@cleanup	215, 227	\strutbox	297
\ppf@Gin@extensions	55	\pr@endbox	223	T	
\ppf@Gin@ii	56, 292	\pr@outerfalse	72, 218	\tabularx	168
\ppf@Gin@keys	270, 357, 359, 415, 419	\pr@startbox	212	U	
\ppf@Gin@setfile	271, 272	\PreviewBbAdjust	.. 86, 112, 119, 123	\usepicture	3, 44, 378
\ppf@Gin@include@graphics	54, 72, 181, 183, 186	\PreviewEnvironment	... 130, 134, 137	V	
				\voidb@x	225
				X	
				\XKV@err	100