

The realboxes package

Martin Scharrer
martin@scharrer-online.de

<http://www.ctan.org/pkg/realboxes>

v0.2 from 2011/08/08

Abstract

Provides variants of common “box”-macros which reads their content as real box and not as macro argument.

1 Introduction

The \LaTeX core and several packages like `graphics/x` provide some `\<xxx>box` macros which modify their content by first placing it into a box. However, these macros still read their content as a macro argument and therefore do not support verbatim content. This package provides variants of these macros which use the authors other package `collectbox` to collect the content as real box before it is modified (framed, raised, scaled, rotated, etc.). This allows for verbatim and other special content.

The provided macros simply have the same names as the original versions but start with an upper-case letter instead. However, these macros do not support the special `picture` syntax as the original macros. The “long-form” macros, like `\Makebox`, can also be used as environments, but not the “short-form” macros, like `\Mbox`. However, normally the long form uses the short form anyway when no optional arguments are used.

Length values

Some of the macros await length values to specify a dimension of the content. For all macros the lengths `\width`, `\height`, `\depth` and `\totalheight` (= height + depth) can be used to refer to the original dimensions of the content. Also the `adjcalc` package from the `adjustbox` bundle is used to allow for mathematical expressions for these values. By default the $\epsilon\text{-}\text{\TeX}$ primitive `\dimexpr` is used which allows for `+, -, *` and `/` as well as grouping using `()`. If either $\epsilon\text{-}\text{\TeX}$ or the `adjcalc` package is not available, than the `calc` package is used by default. It is also possible to use the `pgfmath` framework of the `pgf` bundle. To select a different math back-end simply load the `adjcalc` package with one of the options ‘`etex`’, ‘`calc`’, ‘`pgfmath`’ or ‘`none`’ before the `realboxes` package. See the `adjustbox` manual for more information about `adjcalc`.

2 Usage

The following macros are provided dependent on the used package options. The options state other packages which are loaded and variants of their box macros are provided. See the package manual for more details about these macros. If loaded without any options the **core** macros are loaded as well as all variant of macros for all already loaded packages (“auto-detection mode”).

2.1 L^AT_EX code macros (option core)

`\Mbox{\langle content\rangle}`

This variant of `\mbox` is the only macro which doesn’t use `\collectbox` because of the simplicity of the original macro. `\Mbox` will use `\hbox` directly to process the `\langle content\rangle` (and will expand it to search for the opening brace). The special case when `\langle content\rangle` is a single token is handled by using `\mbox` instead.

`\Makebox[\langle width\rangle] [\langle position\rangle] {\langle content\rangle}`

Places the `\langle content\rangle` in a box of width `\langle width\rangle` (by default the native width) and horizontally aligns it accordantly to `\langle position\rangle`. Valid values are l for left, r for right and c for center alignment (default). If no optional arguments are used this macro equals to `\Mbox`.

`\Fbox{\langle content\rangle}`

Draws a frame around `\langle content\rangle` with a line width of `\fboxrule` and a separation of `\fboxsep`. The baseline of the content is not affected.

`\Framebox[\langle width\rangle] [\langle position\rangle] {\langle content\rangle}`

Like `\Makebox` but draws a frame like `\Fbox`. If no optional arguments are used this macro equals to `\Fbox`.

`\Frame{\langle content\rangle}`

Similar to `\Fbox` but does draw the frame tightly around its content with no separation. The resulting box will also have no depth, i.e. might be moved up. Note that the original `\frame` macro is indented for use inside a `picture` environment but can also be used in normal text. The line width is the current `picture` line width (`\@wholewidth`) which can be (globally) set using `\linethickness{\langle length\rangle}` (also in normal text mode).

`\Raisebox{\langle length\rangle} [\langle height\rangle] [\langle depth\rangle] {\langle content\rangle}`

Raises the `\langle content\rangle` by `\langle length\rangle`. Negative values lower the content. In addition to this the official height and depth can be set. This does not scale the content, but only make TeX reserve less vertical space.

`\Centerline{\langle content \rangle}`

Places `\langle content \rangle` into a box of width `\ linewidth` and centers it inside this box (even if the content is wider). This is similar to `\Makebox[\ linewidth] [c]{\langle content \rangle}`.

`\Leftline{\langle content \rangle}`

Places `\langle content \rangle` into a box of width `\ linewidth` and left aligns it inside this box. If the content is wider it will stick out on the right site. This is similar to `\Makebox[\ linewidth] [l]{\langle content \rangle}`.

`\Rightline{\langle content \rangle}`

Places `\langle content \rangle` into a box of width `\ linewidth` and right aligns it inside this box. If the content is wider it will stick out on the left site. This is similar to `\Makebox[\ linewidth] [r]{\langle content \rangle}`.

`\Rlap{\langle content \rangle}`

Places `\langle content \rangle` into a box of zero width so that it laps over to the right site. The following material to the right will be printed on top of it. This is similar to `\Makebox[0pt] [1]{\langle content \rangle}`.

`\Llap{\langle content \rangle}`

Places `\langle content \rangle` into a box of zero width so that it laps over to the left site. The content will be printed on top of the previous material on the left. This is similar to `\Makebox[0pt] [1]{\langle content \rangle}`.

`\Parbox[\langle pos \rangle] [\langle height \rangle] [\langle inner-pos \rangle] {\langle width \rangle} {\langle content \rangle}`

Places the `\langle content \rangle` into a paragraph box of the given `\width`. The optional `\pos` argument can be used to select the vertical alignment of the box towards the surrounding: ‘t’ align box to the top baseline, ‘b’ align to the bottom baseline or ‘c’ vertically center the content. In addition to this the `\height` and the `\inner-pos`ition can be set as further optional arguments. Valid values for `\inner-pos` are: ‘t’ flush content to the top, ‘b’ flush content to the bottom, ‘c’ center the content inside the box or ‘s’ to stretch the material vertically across the box. This only works if the content contains something vertically stretchable.

This macro uses also `collectbox` but redefines an internal macro to collect a vertical box instead of the usual horizontal one.

`\Sbox{\langle boxregister \rangle}{\langle content \rangle}`

This saves the `\langle content \rangle` into the given `\boxregister`, which must be first allocated using `\newsavebox{\boxregister}`.

```
\Savebox{\boxregister}[\width][\position]{\content}
```

Sets the *(content)* in a box of the given width and alignment like `\Makebox` and stores it in `\boxregister`. If no optional arguments are used this macro equals to `\Sbox`.

2.2 Color macros (option **color** or **xcolor**)

```
\Colorbox[\color model]{\color}{\content}
```

Sets the *(content)* into a box with the given background *(color)*. If required the *(color model)* can be specified.

```
\Fcolorbox[\fc model]{\frame color}[\bg model]{\background color}{\content}
```

Sets the *(content)* into a box with the given *(background color)* and draws a frame around it like `\Fbox` but with a given *(frame color)*. If required the color *(model)* can be specified. If only the frame color model is specified it will also be used for the background color.

2.3 Graphic macros (option **graphics** or **graphicx**)

```
\Rotatebox[\options]{\angle}{\content}
```

Rotates the *(content)* by *(angle)* which is be default in degrees anti-clockwise (360 = full circle). As *(options)* the following keys can be used:

*x=**(dimen)*

*y=**(dimen)* Allows to specify the X and Y coordinate of the coordinate of the center of rotation relative to the reference point of the box.

*origin=**(label)* Allows to specify the center of the rotation using the following letters which can be combined: ‘l’ left side, ‘r’ right side, ‘c’ center of the box, ‘t’ top of the box, ‘b’ bottom of the box and ‘B’ for the base line. For example ‘tr’ rotates about the top right corner.

*units=**(number)* allows to change the default units of degrees anti-clockwise (360) to any *(number)* of units in one full anti-clockwise rotation. For example -360 specifies degrees clockwise and 6.283185 specifies radians.

```
\Scalebox{\h-scale}[\v-scale]{\content}
```

Scales the *(content)* by the given *(scale)* factor. The vertical scaling can be specified independently using the optional argument.

```
\Reflectbox{\content}
```

This reflects the *(content)* and is equal to `\Scalebox{-1}{1}{\content}`.

```
\Resizebox{\width}{\height}{\content}
```

Resizes the `\content` to the given `\width` and/or `\height`. The special value ‘!’ can be used for one of the two values to scale it accordantly to the other value. `\Resizebox{!}{!}{\content}` will not change the size of the content. If both values are used the aspect ratio might be changed. This can be avoided (for the local `\TeX` group) using `\setkeys{Gin}{keepaspectratio}`. Then the content is scaled to the smaller of the two values.

```
\Resizebox*{\width}{\totalheight}{\content}
```

Like `\Resizebox` but scales the total height (= height + depth) instead of the height.

2.4 Macros of the `dashbox` package (option `dashbox`)

```
\Dbox{\content}
```

Like `\Fbox` but uses a dashed line instead.

```
\Dashbox[\width][\position]{\content}
```

Like `\Framebox` but uses a dashed line instead.

```
\Lbox[\layers]{\content}
```

Draws some solid background layers to the lower right of the content which produces a shadow effect. The `\content` is supposed to also use `\Dbox` or `\Fbox` to draw the foreground dash or frame box. By default two layers are drawn but this can be changed by the optional argument.

```
\Dlbox[\layers]{\content}
```

Like `\Lbox` but draws the layers with dashed lines instead.

2.5 Compatibility with the `fancybox` package (option `fancybox`)

The `fancybox` package defines its macros already in a verbatim compatible way. However, if this option is used the `\Sbox` macro provided by the `core` option is defined in a way to not collide with the `Sbox` environment of this package.

3 Implementation

3.1 Package Header and Options

```
1  \NeedsTeXFormat{LaTeX2e}[1999/12/01]
2  \ProvidesPackage{realboxes}[2011/08/08 v0.2 Change ↵
   box commands to read there content as real boxes]
3  \newif\ifrealboxes@core
4  \newif\ifrealboxes@xcolor
5  \newif\ifrealboxes@color
6  \newif\ifrealboxes@graphicx
7  \newif\ifrealboxes@graphics
8  \newif\ifrealboxes@dashbox
9  \newif\ifrealboxes@fancybox
10 \DeclareOption{all}{%
11   \realboxes@coretrue
12   \realboxes@xcolortrue
13   \realboxes@colortrue
14   \realboxes@graphicxtrue
15   \realboxes@graphicstrue
16   \realboxes@dashboxtrue
17   \realboxes@fancyboxtrue
18 }
19 \DeclareOption*{%
20   \begingroup
21   \expandafter\ifx\csname realboxes@\CurrentOption\relax
22     true\endcsname\relax
23   \endgroup
24   \unknownoptionerror
25   \else
26     \endgroup
27     \csname realboxes@\CurrentOption true\relax
28   \endcsname
29   \fi
30 }
31 \ProcessOptions\relax

32 \edef\@tempa{\@optionlist{\@currname.\@currext}}
33 \ifx\@tempa\empty
34   \realboxes@coretrue
35   \@ifpackageloaded{dashbox}{\realboxes@dashboxtrue,}
36   \ifx\@tempa\empty
37   \realboxes@colortrue
38   \realboxes@xcolortrue
39   \realboxes@graphicstrue
40   \realboxes@graphicxtrue
41 }
```

```

38      \@ifpackageloaded{fancybox}{\/
39          realboxes@fancyboxtrue}{}
40      \fi
41      \ifrealboxes@fancybox
42          \realboxes@coretrue
43      \fi
44      \RequirePackage{collectbox}
45      \IfFileExists{adjcalc.sty}{%
46          \RequirePackage{adjcalc}
47      }{%
48          \RequirePackage{calc}
49          \def\adjsetlength{\setlength}
50      }

```

3.2 L^AT_EX core

```

50      \ifrealboxes@core

```

\Makebox

```

51      \newcommand*{\Makebox}[%
52          \collectboxcheckenv{Makebox}%
53          \@ifnextchar[%
54              \OMakebox
55              \mbox
56          ]

```

\@Makebox

```

57      \def\@Makebox[#1]{%
58          \ifnextchar[%
59              {\@iMakebox{#1}}%
60              {\@iMakebox{#1}[c]}%
61      }

```

\@iMakebox

```

62      \def\@iMakebox#1[#2]{%
63          \collectbox{%
64              \let\@tempboxa\collectedbox
65              \adjsetlength\@tempdima{#1}%
66              \hb@xt@\@tempdima{\csname bm@#2\endcsname}%
67          }%
68      }

```

\Fbox

```
69 \newcommand*\Fbox{%
70   \collectbox{\kern\fboxsep}{\let\@tempboxa\%
71     collectedbox\@frameb@x\relax}{\kern\fboxsep}%
72 }
```

\Frame

```
72 \newcommand*\Frame{%
73   \collectbox{\frame\BOXCONTENT}%
74 }
```

\Mbox

```
75 \newcommand*\Mbox{%
76   \leavevmode
77   \@ifnextchar\bgroup
78     \hbox
79     \mbox
80 }
```

\Raisebox

```
81 \newcommand*\Raisebox[1]{%
82   \leavevmode
83   \collectboxcheckenv{Raisebox}%
84   \ifnextchar[%
85     {\@Rsbox{#1}}%
86     {\@collectbox{\@iRsbox{#1}{}}}%
87 }
```

\@Rsbox

```
88 \def\@Rsbox[#1][#2]{%
89   \ifnextchar[%
90     {\@iRsbox{#1}{#2}}%
91     {\@collectbox{\@iRsbox{#1}{#2}}}%
92 }
```

```
\@iRsbox
```

```
93  \def\@iRsbox#1#2{%
94      \adjsetlength\@tempdima{#1}%
95      \ifx \\#2\\ \else
96          \adjsetlength\@tempdimb{#2}%
97      \fi
98      \setbox\collectedbox\hbox{\raise\@tempdima\box\,
99          collectedbox}%
100     \ifx \\#2\\ \else
101         \ht\collectedbox\@tempdimb
102     \fi
103     \box\collectedbox
104 }
```

```
\@iiRsbox
```

```
104 \def\@iiRsbox#1#2[#3]{%
105     \@collectbox{\@iiiRsbox{#1}{#2}{#3}}%
106 }
```

```
\@iiiRsbox
```

```
107 \def\@iiiRsbox#1#2#3{%
108     \adjsetlength\@tempdima{#1}%
109     \adjsetlength\@tempdimb{#2}%
110     \adjsetlength\dimen@{#3}%
111     \setbox\collectedbox\hbox{\raise\@tempdima\box\,
112         collectedbox}%
113     \ht\collectedbox\@tempdimb
114     \dp\collectedbox\dimen@
115     \box\collectedbox
116 }
```

```
\Leftline
```

```
116 \newcommand*\Leftline{\nocollectbox@to\linewidth{}{}\hss}
```

```
\Rightline
```

```
117 \newcommand*\Rightline{\nocollectbox@to\linewidth\hss\{}{}\}}
```

```
\Centerline
```

```
118 \newcommand*\Centerline{\nocollectbox@to\linewidth\hss{}\\hss}
```

```
\Rlap
```

```
119 \newcommand*\Rlap{\nocollectbox@to\z@\{}{}\hss}
```

```
\Llap
```

```
120 \newcommand*\Llap{\nocollectbox@to\z@\hss\{}{}\}
```

```
\Framebox
```

```
121 \newcommand*\Framebox{%
122     \collectboxcheckenv{Framebox}%
123     \@ifnextchar[%%
124         \@Framebox%
125         \Fbox%
126     }%
```

```
\@Framebox
```

```
127 \def\@Framebox [#1]{%
128     \ifnextchar[%%
129         {\@iFramebox{#1}}%
130         {\@iFramebox{#1}[c]}%
131     }
```

```
\@iFramebox
```

```
132 \def\@iFramebox #1[#2]{%
133     \collectbox{\@iFramebox{#1}{#2}}%
134 }
```

```
\@iiFramebox
```

```
135 \def \@iiFramebox #1#2{%
136     \let\@tempboxa\collectedbox
137     \adjsetlength\@tempdima{#1}%
138     \setbox\@tempboxa\hb@xt@\@tempdima
139         {\kern\fboxsep\csname bm@\#2\endcsname\kern\-
140         \fboxsep}%
141     \framebox{\kern-\fboxrule}%
141 }
```

```
\Parbox
```

```
142 \newcommand\Parbox{%
143     \collectboxcheckenv{Parbox}%
144     \@ifnextchar[%
145         \@iParbox
146         {\@iiiParbox \relax[s]}%
147 }
```

```
\@iParbox
```

```
148 \def \@iParbox [#1]{%
149     \ifnextchar[%
150         {\@iiiParbox{#1}}%
151         {\@iiiParbox{#1}\relax[s]}%
152 }
```

```
\@iiParbox
```

```
153 \def \@iiParbox #1[#2]{%
154     \ifnextchar[%
155         {\@iiiParbox{#1}{#2}}%
156         {\@iiiParbox{#1}{#2}[#1]}%
157 }
```

```
\@iiiParbox
```

```
158 \def \@iiiParbox #1#2[#3]#4{%
159     \leavevmode
160     \begingroup
161     \pboxswfalse
```

```

162 \adjsetlength\@tempdima{#4}%
163 \let\collect@box\vbox
164 \let\@tempboxa\collectedbox
165 \collectbox@\hsize\@tempdima\@parboxrestore}{\v
166   @vParbox{#1}{#2}{#3}{\@par}%
167 }
```

\@vParbox

```

167 \def\@vParbox#1#2#3{%
168   \ifx\relax#2\else
169     \adjsetlength\@tempdimb{#2}%
170     \edef\@parboxto{\the\@tempdimb}%
171   \fi
172   \if#1b\vbox
173     \else\if #1B\vbox
174     \else\if #1t\vtop
175     \else\if #1T\vtop
176     \else\ifmmode\vcenter
177     \else\@pboxswtrue \$\vcenter
178     \fi\fi\fi
179     \fi\fi\fi
180     \@parboxto{\let\hss\vss\let\unhbox\unvbox
181       \csname bm@#3\endcsname}%
182     \if@pboxsw \m@th\$ \fi
183   \endgroup
184 }
```

\Sbox@

```

185 \newcommand*\Sbox@[1]{\@collectboxto{#1}{}}
```

\Savebox

```

186 \def\Savebox#1{%
187   \@ifnextchar[%
188     {\@Savebox#1}%
189     {\Sbox@#1}%
190 }
```

3.2.1 fancybox Compatibility

```

191 \ifrealboxes\fancybox
192 \RequirePackage{fancybox}
193 \let\orig\fancy\Sbox\Sbox
```

\Sbox

```
194 \def\Sbox{%
195   \begingroup
196   \def\@tempa{\Sbox}%
197   \expandafter\endgroup
198   \ifx\@currenvir\@tempa
199     \orig@fancy@Sbox
200     \edef\@currenvir{\@currenvir\space}%
201   \else
202     \expandafter\Sbox@
203   \fi
204 }
205 \else
206 \let\Sbox\Sbox@
207 \AtBeginDocument{\@ifpackageloaded{fancybox}{%
208   \PackageWarning{realboxes}{Package 'fancybox' got%
209   loaded. This requires 'realboxes' to be%
210   loaded with the 'fancybox' option!}%
211 }{}}
212 \fi
```

\@Savebox

```
211 \def@\Savebox#1[#2]{%
212   \@ifnextchar [%
213     {\@iSavebox#1[#2]}%
214     {\@iSavebox#1[#2][c]}%
215 }
```

\@iSavebox

```
216 \def@\iSavebox#1#2[#3]{%
217   \@collectboxto#1{\@iiSavebox{#1}{#2}{#3}}%
218 }
```

\@iiSavebox

```
219 \def@\iiSavebox#1#2#3{%
220   \sbox#1{%
221     \let\@tempboxa#1%
222     \adjsetlength\@tempdima{#2}%
223     \hb@xt@\@tempdima{\csname bm@\#3\endcsname}%
224   }%
225 }
```

```
226 \fi
```

3.3 color and xcolor Packages

```
227 \ifrealboxes@xcolor
228     \RequirePackage{xcolor}
229     \realboxes@colortrue
230 \else
231     \ifrealboxes@color
232     \RequirePackage{color}
233     \fi
234 \fi
235 \ifrealboxes@color
```

```
\Colorbox
```

```
236 \newcommand*\Colorbox{}%
```

```
\Colorbox
```

```
237 \def\Colorbox#1#2{%
238     \collectboxcheckenv{Colorbox}%
239     \Color@box{#1}%
240 }
```

```
\Color@box
```

```
241 \def\Color@box#1#2{%
242     \collectbox{\color@box{#1}{#2}\BOXCONTENT}%
243 }
```

```
\Fcolorbox
```

```
244 \newcommand*\Fcolorbox{}
```

```
\Fcolorbox
```

```
245 \def\Fcolorbox#1#2{%
246     \collectboxcheckenv{Fcolorbox}%
247     \Color@fbox{#1}%
248 }
```

```
\Color@fbox
```

```
249 \def\Color@fbox#1#2#3{%
250   \Color@@fbox{#1}{#2}{#3}%
251 }
```

```
\Color@@fbox
```

```
252 \def\Color@@fbox#1#2#3#4{%
253   \protect\@collectbox{\protect\color@fb@x%
254     {#1}{#2}{#3}{#4}\BOXCONTENT}%
255 }
```

```
\fi
```

3.4 color and xcolor Packages

```
256 \ifrealboxes@graphicx
257   \RequirePackage{graphicx}
258   \realboxes@graphicxtrue
259 \else
260   \ifrealboxes@graphics
261     \RequirePackage{graphics}
262   \fi
263 \fi
264 \ifrealboxes@graphics
```

```
\Rotatebox
```

```
265 \newcommand*\Rotatebox{%
266   \collectboxcheckenv{Rotatebox}%
267   \@ifnextchar[%
268     \Rotatebox@kv
269     \Rotatebox@std
270 }
```

```
\Rotatebox@kv
```

```
271 \def\Rotatebox@kv [#1]#2{%
272   \@collectbox{\Grot@box@kv [#1]{#2}\BOXCONTENT}%
273 }
```

\Rotatebox@std

```
274 \def\Rotatebox@std#1{%
275   \collectbox{\Grot@box@std{#1}\BOXCONTENT}%
276 }
```

\Scalebox

```
277 \newcommand*\Scalebox[1]{%
278   \collectboxcheckenv{Scalebox}%
279   \ifnextchar[%
280     {\Scale@box{#1}}%
281     {\Scale@box{#1}[#1]}%
282 }
```

\Scale@box

```
283 \def\Scale@box[#2]{%
284   \collectbox{\Gscale@box{#1}[#2]\BOXCONTENT}%
285 }
```

\Reflectbox

```
286 \newcommand*\Reflectbox{%
287   \collectboxcheckenv{Reflectbox}%
288   \Scale@box{-1}[1]%
289 }
```

\Resizebox

```
290 \newcommand*\Resizebox{%
291   \collectboxcheckenv{Resizebox}%
292   \ifstar
293     {\@Resizebox\totalheight}%
294     {\@Resizebox\height}%
295 }
```

\Resizebox

```
296 \namedef{Resizebox*}{%
297   \collectboxisenv{Resizebox*}%
298   \@Resizebox\totalheight
299 }
```

```
\@Resizebox
```

```
300 \def\@Resizebox#1#2#3{%
301     \@collectbox{\let\setlength\adjsetlength\%
302         Gscale@@box{#1}{#2}{#3}\BOXCONTENT}%
303     }
304 \fi
```

3.5 dashbox Package

```
304 \ifrealboxes@dashbox
305 \RequirePackage{dashbox}
```

```
\Dbox
```

```
306 \newcommand*\Dbox{%
307     \@collectbox{\dbox{\BOXCONTENT}}%
308 }
```

```
\Dashbox
```

```
309 \newcommand*\Dashbox{%
310     \@ifnextchar[%
311         \@Dashbox
312         \Dbox
313 }
```

```
\@Dashbox
```

```
314 \def\@Dashbox[#1]{%
315     \@ifnextchar[%
316         {\@iDashbox{#1}}%
317         {\@iDashbox{#1}[c]}%
318 }
```

```
\@iDashbox
```

```
319 \def\@iDashbox[#1][#2]{%
320     \@collectbox{\dashbox[#1][#2]{\BOXCONTENT}}%
321 }
```

```
\Lbox
```

```
322 \newcommand*\Lbox{%
323     \@ifnextchar[%
324         \@Lbox
325         {\@collectbox{\lbox{\BOXCONTENT}}}}%
326 }
```

```
\@Lbox
```

```
327 \def\@Lbox [#1]{%
328     \@collectbox{\lbox [#1]{\BOXCONTENT}}%
329 }
```

```
\Dlbox
```

```
330 \newcommand*\Dlbox{%
331     \@ifnextchar[%
332         \@Dlbox
333         {\@collectbox*\dlbox}}%
334 }
```

```
\@Dlbox
```

```
335 \def\@Dlbox [#1]{%
336     \@collectbox{\dlbox [#1]{\BOXCONTENT}}%
337 }
```

```
338 \fi
```