

# Tabulars with reledmac

February 10, 2017

## Abstract

This file provides example of using tabular environments with *reledmac*.  
We use `edtabularl`, `edtabularc` and `edtabularr`, with marginal,  
critical and familiar notes. We also use optional arguments of `\pstart`.

## 1 Left align

1	linea prima	linea prima	sidenote l, sidenote
2	linea secunda	linea secunda <sup>1</sup>	l
3	linea tertia	linea tertia	
4	linea quarta	linea quarta	
5	linea quinta	linea quinta <sup>1</sup>	
6	linea sexta	linea sexta	

## 2 Center align

7	linea prima	linea prima	sidenote c, sidenote
8	linea secunda	linea secunda <sup>2</sup>	c, sidenote c
9	linea tertia	linea tertia	
10	linea quarta	linea quarta	
11	linea quinta	linea quinta <sup>2</sup>	
12	linea sexta	linea sexta	

---

<sup>1</sup>familiar footnote A.  
<sup>2</sup>familiar footnote A.

---

<sup>1</sup>familiar footnote B.  
<sup>2</sup>familiar footnote B.

---

3 tertia ] critical note A  
9 tertia ] critical note A

---

4 quarta ] critical note B  
10 quarta ] critical note B

3 Right align

sidenote r, sidenote	linea prima	linea prima
r, sidenote	linea secunda	linea secunda <sup>3</sup>
15	linea tertia	linea tertia
16	linea quarta	linea quarta
17	linea quinta	linea quinta <sup>3</sup>
18	linea sexta	linea sexta

---

<sup>3</sup>familiar footnote A.

---

<sup>3</sup>familiar footnote B.

---

15 tertia ] critical note A

---

16 quarta ] critical note B