

Tabulars with reledmac

November 29, 2015

Abstract

This file provides example of using tabular environments with *reledmac*.
We use `edtabularl`, `edtabularc` and `edtabularr`, with marginal,
critical and familiar notes. We also use optional arguments of `\pstart`.

1 Left align

| | | | |
|---|---------------|----------------------------|------------|
| 1 | linea prima | linea prima | sidenote l |
| 2 | linea secunda | linea secunda ¹ | |
| 3 | linea tertia | linea tertia | |
| 4 | linea quarta | linea quarta | |
| 5 | linea quinta | linea quinta ¹ | |
| 6 | linea sexta | linea sexta | |

2 Center align

| | | | |
|----|---------------|----------------------------|------------|
| 7 | linea prima | linea prima | sidenote c |
| 8 | linea secunda | linea secunda ² | |
| 9 | linea tertia | linea tertia | |
| 10 | linea quarta | linea quarta | |
| 11 | linea quinta | linea quinta ² | |
| 12 | linea sexta | linea sexta | |

3 Right align

| | | | |
|-------|-----------------------------------|-----------------|------------|
| 13 | linea prima | linea prima | sidenote r |
| <hr/> | | | |
| | ¹ familiar footnote A. | | |
| | ² familiar footnote A. | | |
| <hr/> | | | |
| | ¹ familiar footnote B. | | |
| | ² familiar footnote B. | | |
| <hr/> | | | |
| 3 | tertia] | critical note A | |
| 9 | tertia] | critical note A | |
| <hr/> | | | |
| 4 | quarta] | critical note B | |
| 10 | quarta] | critical note B | |

| | | |
|----|---------------|----------------------------|
| 14 | linea secunda | linea secunda ³ |
| 15 | linea tertia | linea tertia |
| 16 | linea quarta | linea quarta |
| 17 | linea quinta | linea quinta ³ |
| 18 | linea sexta | linea sexta |

³familiar footnote A.

³familiar footnote B.

15 tertia] critical note A

16 quarta] critical note B