

reledmac

Typeset scholarly editions with L^AT_EX*

Maïeul Rouquette[†]

based on the original ledmac by
Peter Wilson
Herries Press

which was based on the original edmac, tabmac and edstanza by
John Lavagnino, Dominik Wujastyk, Herbert Breger and Wayne Sullivan.

Abstract

The **reledmac** provides many tools in order to typeset scholarly editions. It is based on the **eledmac** package, which was based on the **ledmac** package, which was based on the **edmac** TeX package.

It can be used in combination with **reledpar** in order to typeset two texts in parallel, like an original text and its translation in a modern language.

reledmac provides many tools and options. Normally, they are all documented in this file. Also provided is a help folder, “examples”. The folder contains additional examples (although not for every possible case). Examples starting with “1-” are for basic uses, those starting with “2-” are for advanced uses.

To report bugs or request a new feature, please go to ledmac GitHub page and click on “New Issue”: <https://github.com/maieul/ledmac/issues/>. You must create an account on github.com to access my page (maieul/ledmac). GitHub accounts are free for open-source users. You can post messages in English or in French (preferred).

You can subscribe to the **reledmac** mail list at:
<http://geekographie.maieul.net/146>

Contents

1 Introduction	12
1.1 Aim of the package	12
1.2 History	13
1.2.1 edmac	13
1.2.2 ledmac	14
1.2.3 elledmac	14

*This file (**reledmac.dtx**) has version number v2.31.2, last revised 2019/04/03.

[†]maieul at maieul dot net

1.2.4 <code>reledmac</code>	14
1.3 Bibliography	15
2 How the package works – the problem of the number of L^AT_EX runs	15
3 Compatibility warning	15
4 Options	15
4.1 Specific features	16
4.2 Optimizing package performance	16
5 Text lines and paragraphs numbering	17
5.1 Text lines numbering	17
5.2 Paragraphs	17
5.2.1 Basics	17
5.2.2 Automatically producing <code>\pstart</code> ... <code>\pend</code>	18
5.2.3 Content before specific <code>\pstart</code> and after specific <code>\pend</code>	19
5.2.4 Content before every <code>\pstart</code> and after every <code>\pend</code>	19
5.2.5 Numbering paragraphs (<code>\pstart</code>)	19
5.2.6 Languages written in Right to Left	20
5.2.7 Memory limits	20
5.3 Lineation commands	21
5.3.1 Disabling lineation	21
5.3.2 Setting lineation start and step	21
5.3.3 Setting lineation reset	22
5.3.4 Setting line number margin	22
5.3.5 Other settings	22
5.4 Changing the line numbers	22
5.4.1 Sublineation	23
5.4.2 Locking lineation	23
5.4.3 Setting and changing line number	23
5.4.4 Line number style	24
5.4.5 Skipping and hiding number	24
5.5 Adding annotations to line numbers	24
5.5.1 Modifying annotation associated with a specific note	26
5.5.2 Changing the position of the annotation	26
5.5.3 Changing the macro in which annotations are wrapped	26
5.5.4 Not printing the second identical annotations	27
5.5.5 Separator between annotations	27
5.6 Executing code at each line	27
5.7 Executing code at a specific line	27
6 Apparatus commands	28
6.1 Terminology	28
6.2 Critical notes	28
6.2.1 The lemma	28

6.2.2 Footnotes	29
6.2.3 Endnotes	30
6.2.4 Paragraph in critical apparatus	31
6.2.5 Change lemma and line number	31
6.2.6 Changing the names of commands for critical apparatus	32
6.3 Disambiguation of identical words in the apparatus	33
6.3.1 Basic use	33
6.3.2 Case setting	33
6.3.3 Notes about input encoding with UTF-8 processor	33
6.3.4 Use with \lemma command	34
6.3.5 Sameword for a group of words	36
6.3.6 Customizing	36
6.3.7 Problems with some macros	37
6.3.8 Automatic sameword annotation	37
6.4 Apparatus of manuscripts	38
6.4.1 Marking sections of text	38
6.4.2 Layout of the apparatus of manuscripts	38
6.4.3 Settings	39
6.5 Familiar notes	39
6.5.1 Basic use	39
6.5.2 Customizing mark	39
6.5.3 Separator for multiple footnotes	40
6.6 Printing the footnote mark without printing the footnote text	40
6.7 Changing series	40
6.7.1 Create a new series	40
6.7.2 Delete series	40
6.7.3 Series order	41
6.8 Position of critical and familiar footnotes	41
7 Apparatus customization	42
7.1 Notes arrangement in a series	42
7.2 Control line number printing	43
7.2.1 Print line number only at first time	43
7.2.2 Print page number only at first time	43
7.2.3 Arbitrary text before line number	44
7.2.4 Separator for line range	44
7.2.5 Abbreviate line range	44
7.2.6 Disable line number	45
7.2.7 Printing pstart number	45
7.2.8 Printing stanza number	46
7.2.9 Separator between line and subline numbers	46
7.2.10 Separator between page and line numbers	46
7.2.11 Space around number	46
7.2.12 Space around line symbol	46
7.2.13 Space in place of number	47
7.2.14 Boxing line number and line symbol	47

7.3 Arbitrary code around line number	48
7.4 Separator between the lemma and the note	48
7.4.1 For footnotes	48
7.4.2 For endnotes	48
7.5 Font style	49
7.5.1 For line number	49
7.5.2 For the lemma	49
7.5.3 For all notes	49
7.6 Wrapping notes	50
7.6.1 Wrapping lemmas	50
7.6.2 Wrapping contents	50
7.7 Indent of notes content	50
7.8 Arbitrary code at the beginning of notes	50
7.9 Arbitrary code before inserting note	51
7.10 Options for footnotes in columns	51
7.10.1 Alignment	51
7.10.2 Size of the columns	51
7.11 Options for paragraphed footnotes and notes grouped by line	52
7.11.1 Mark separation of notes	52
7.11.2 Ragged text	52
7.12 Options for block of notes	52
7.12.1 Grouping notes by line	52
7.12.2 Text before notes	53
7.12.3 Code before notes	53
7.12.4 Spacing	53
7.12.5 Rule	53
7.12.6 Maximum height	54
7.12.7 Width	54
7.13 Footnotes and the <code>reledpar</code> columns	54
7.14 Line number annotation	54
7.15 Endnotes in one paragraph	55
8 Fonts	55
9 Verse	55
9.1 Basic	55
9.2 Define stanza indents	56
9.3 Repeating stanza indents	56
9.4 Manual stanza indent	57
9.5 Stanza breaking	57
9.6 Hanging symbol	57
9.7 Long verse and page break	58
9.8 Content before/after verses	58
9.9 Numbering stanza	59
9.10 Various tools	59
9.11 Notes on empty lines	59

<i>Contents</i>	5
10 Grouping	60
11 Cross referencing	60
11.1 Basic use	60
11.2 Cross-referencing to a critical note	61
11.3 Cross-referencing which return a number in any case	61
11.3.1 Cross-referencing in order to define line number of a critical note .	62
11.4 Not automatic cross-referencing	62
11.5 Normal L ^A T _E X cross-referencing	62
11.6 References to start and end lines	62
11.6.1 Reference to main text lines	62
11.6.2 References to lines that are commented on in the apparatus	63
11.6.3 Settings	63
11.6.4 Combining multiple references	65
11.7 Compatibility with <code>xr</code> package	65
12 Sidenotes	66
12.1 Basics	66
12.2 Setting	66
12.2.1 Width	66
12.2.2 Vertical position	66
12.2.3 Distance to the main text	66
12.2.4 Font	66
12.2.5 Separator between notes	67
13 Indexing	67
13.1 Basics	67
13.2 Use with <code>imakeidx</code> or <code>indextools</code>	67
13.3 Referring to critical notes	67
13.4 Separator between page and line numbers	68
13.5 Using <code>xindy</code>	68
13.6 Advanced setting	69
14 Glossary	69
14.1 Preamble setting	69
14.2 Commands	69
15 Tabular material	70
16 Sectioning commands	73
16.1 Sectioning commands without line numbers or critical notes	73
16.2 Sectioning commands with line numbering and critical notes	73
16.3 Optimization	74
17 Quotation environments	74

18 Page breaks	74
18.1 Control page breaking	74
18.2 Prevent page break in a long verses	75
19 Miscellaneous	75
19.1 Known and suspected limitations	76
19.1.1 Non-standard geometry	76
19.1.2 <code>f1oatrow</code> package compatibility	76
19.1.3 ‘No room for a new’	76
19.1.4 Marginal notes	76
19.1.5 Paragraph shape	77
19.1.6 Paragraphed footnotes	77
19.1.7 Use with other packages	77
19.2 Parallel typesetting	78
I Implementation overview	79
II Preliminaries	79
II.1 Links with original <code>edmac</code>	79
II.2 Package declaration	79
II.3 Package options	80
II.3.1 Options of <code>reledpar</code>	80
II.3.2 Options of <code>reledmac</code>	80
II.4 Loading packages	82
II.5 Compatibility with LuaTeX	83
II.6 Boolean flags	83
II.7 Messages	84
II.8 Gobbling	90
II.9 Wrapping content	90
II.10 Miscellaneous commands	91
II.11 Prepare <code>reledpar</code>	91
II.12 Booleans provided by other optional packages which are required in any case	92
III Sectioning commands	92
IV List macros	98
V Line counting	99
V.1 Choosing the system of lineation	99
V.2 Line number margin	101
V.3 Line number initialization and increment	102
V.4 Line number locking	103
V.5 Line number style	104
V.6 Line number printing	104
V.7 Line number counters and lists	106
V.8 Line number locking counter	107

V.9 Line number associated to lemma	107
V.10 Reading the line-list file	110
V.11 Commands within the line-list file	113
V.12 Writing to the line-list file	126
VI Marking text for notes	134
VI.1 \edtext itself	135
VI.2 Substitute lemma	142
VI.3 Substitute line numbers	143
VI.4 Lemma disambiguation	144
VII Paragraph decomposition and reassembly	151
VII.1 Boxes, counters, \pstart and \pend	152
VII.2 Processing one line	158
VII.2.1 General process	158
VII.2.2 Process for “normal” line	159
VII.2.3 Process for line containing \eledsection command	161
VII.2.4 Hooks	162
VII.2.5 Sidenotes and marginal line number initialization	163
VIII Line and page number computation	164
VIII.1 Continuous line numbering between parallel typesetting and normal typesetting	167
IX Line number annotation	168
X Line number printing	170
XI Pstart number printing inside	174
XII Restoring footnotes and penalties	176
XII.1 Add insertions to the vertical list	176
XII.2 Penalties	178
XII.3 Printing leftover notes	179
XII.4 Text before notes	180
XIII Critical footnotes	181
XIII.1 Fonts	182
XIII.2 Individual note options	182
XIII.3 Notes language	182
XIII.4 General survey of the way we manage notes	184
XIII.5 General setup	184
XIII.6 Footnotes arrangement	185
XIII.6.1 User level macro	185
XIII.6.2 Normal footnote	185
XIII.6.3 Paragraphed footnotes	190
XIII.6.4 Columnar footnotes	197

XIII.7 Footnote hanging indent	204
XIII.8 Critical notes presentation	205
XIII.8.1 Font tools	205
XIII.8.2 Pstart number in footnote	206
XIII.8.3 Lemma printing	206
XIII.8.4 Line number printing	207
XIII.8.5 Footnote grouped by line	217
XIV Familiar footnotes	219
XIV.1 Adjacent footnotes	219
XIV.2 Regular footnotes for numbered texts	220
XIV.3 Footnote formats	222
XIV.4 Footnote arrangement	223
XIV.4.1 User level macro	223
XIV.4.2 Normal footnotes	223
XIV.4.3 Two columns footnotes	229
XIV.4.4 Three columns footnotes	232
XIV.4.5 Paragraphed footnotes	234
XIV.5 Wrapping footnote marks in hyperlink	238
XV Code common to both critical and familiar footnote in normal arrangement	239
XVI Footnotes' width for two columns	239
XVII Footnotes' order	241
XVIII Footnotes' rule	241
XIX Specific skip for first series of footnotes	242
XIX.1 Overview	242
XIX.2 User level command	242
XIX.3 Internal commands	243
XX Endnotes	244
XX.1 Internal commands	244
XX.2 User level commands	248
XX.2.1 Inserting contents to endnotes	248
XX.2.2 Printing endnotes	249
XXI Generate series of notes	257
XXI.1 Test if series is still existing	257
XXI.2 Init specific to <code>reledpar</code>	257
XXI.3 For critical footnotes	257
XXI.3.1 Options	258
XXI.3.2 Create inserts, needed to add notes in foot	259

XXI.3.3 Create commands for critical apparatus, \Afootnote, \Bfootnote etc.	259
XXI.3.4 Set standard display	262
XXI.4 For familiar footnotes	262
XXI.4.1 Options	262
XXI.4.2 Create tools for familiar footnotes (\footnoteX)	263
XXI.5 The endnotes	265
XXI.5.1 The auxiliary file	266
XXI.5.2 The main macro	266
XXI.5.3 Tools	267
XXI.5.4 Internal commands	267
XXI.5.5 The options	267
XXI.6 Init standards series (A,B,C,D,E)	269
XXII Setting series display	269
XXII.1 Change series order	269
XXII.2 Test series order	270
XXII.2.1 Get the first series	270
XXII.3 Series setting	270
XXII.3.1 General way of working	270
XXII.3.2 Tools to set options	271
XXII.3.3 Tools to generate options commands	272
XXII.3.4 Options for critical notes	273
XXII.3.5 Options for familiar notes	275
XXII.3.6 Options for endnotes	276
XXII.4 Hooks for a particular footnote	278
XXII.5 Alias	280
XXIII Output routine	280
XXIII.1 Extra footnotes output	280
XXIII.2 Patching standard output's commands	283
XXIV Page numbering in parallel typesetting	286
XXV Cross referencing	288
XXV.1 Compatibility with xref	304
XXVI Sidenotes	305
XXVII Minipages and such	312
XXVIII Indexing	317
XXVIII.1 Looking on package order	318
XXVIII.2 Auxiliary macros for \edindex	318
XXVIII.3 Code specific to \edindex in critical footnotes	319
XXVIII.4 Analysis of command in indexed text	320
XXVIII.5 Code for the formatted index	321

XXVIII.6 Main code	321
XXVIII.7 Hyperlink	323
XXVIII.8 ‘innote’ and ‘notenumber’ option of <code>indextools</code> package	326
XXIX Glossaries	326
XXX Verse	328
XXX.1 Hanging symbol management	329
XXX.2 Using & character	329
XXX.3 Code category setting	329
XXX.4 Stanza count and indent	330
XXX.5 Numbering stanza	331
XXX.6 Stanza number in note	332
XXX.7 Main work	333
XXX.8 Restore catcode and penalties	336
XXXI Apparatus of Manuscripts	336
XXXI.1 User level macro	336
XXXI.2 Setting macro	337
XXXI.3 Counters and lists	338
XXXI.4 Auxiliary file macros	339
XXXI.5 Action macro	339
XXXI.6 Inserting footnote	345
XXXI.7 Other	345
XXXII Arrays and tables	345
XXXII.1 Preamble: macro as environment	345
XXXII.2 Tabular environments	349
XXXII.2.1 Disabling and restoring commands	349
XXXII.2.2 Counters, boxes and lengths	353
XXXII.2.3 Tabular typesetting	357
XXXII.2.4 Environments	368
XXXIII Quotation’s commands	368
XXXIV Section’s title commands	369
XXXIV.1 Commands to disable some feature	369
XXXIV.2 General overview	370
XXXIV.3 <code>\beforeeledchapter</code> command	370
XXXIV.4 Auxiliary commands	371
XXXIV.5 Patching standard commands	372
XXXIV.6 Main code of <code>\eledxxx</code> commands	377
XXXIV.7 Macros written in the auxiliary file	379
XXXV Page breaking or no page breaking depending of specific lines	382
XXXVI Long verse: prevents being separated by a page break	383

<i>Contents</i>	11
XXXVII Tools for hyperref package	384
XXXVIII Compatibility with eleedmac	385
Appendix A Things to do when changing versions	387
A.1 Migrating from edmac to ledmac	387
A.2 Migration from ledmac to eleedmac	388
A.3 Migration to eleedmac 1.5.1	389
A.4 Migration to eleedmac 1.12.0	389
A.5 Migration to eleedmac 17.1	390
A.6 Migration to eleedmac 1.21.0	390
A.6.1 \Xledsetnormalparstuff and \ledsetnormalparstuffX	390
A.6.2 Endnotes	390
A.7 Migration to eleedmac 1.22.0	390
A.8 Migration to eleedmac 1.23.0	390
A.9 Migration from eleedmac to reledmac	391
A.9.1 Risk of ‘no room for a new’	391
A.9.2 Multiple indices with memoir	391
A.9.3 Deprecated commands and options	391
A.9.4 \renewcommand replaced by command	392
A.9.5 Commands the names of which have been changed	392
A.9.6 Endnotes	394
A.9.7 Z Series	394
A.9.8 Internal commands	394
A.10 Migration to reledmac 2.1.0	394
A.11 Migration to reledmac 2.1.3	394
A.12 Migration to reledmac 2.3.0	394
A.13 Migration to reledmac 2.4.0	395
A.14 Migration to reledmac 2.5.0	395
A.15 Migration to reledmac 2.7.0	395
A.16 Migration to reledmac 2.7.2	395
A.17 Migration to reledmac 2.8.0	395
A.18 Migration to reledmac 2.13.1	395
A.19 Migration to reledmac 2.18.0	396
A.20 Migration to reledmac 2.21.0	396
A.21 Migration to reledmac 2.24.0	396
A.22 Migration to reledmac 2.26.0	396
A.23 Migration to reledmac 2.27.1	396
A.24 Migration to reledmac 2.30.0	396
A.25 Migration to reledmac 2.31.1	397
Appendix B Auxiliary softwares	397
B.1 <i>samewords</i>	397
B.2 critical-keys for <i>Emacs</i>	397
B.3 Import from TEI	397

References	398
Index	398
Change History	449

1 Introduction

1.1 Aim of the package

The `reledmac` package, together with `LATEX`, provides several important facilities for formatting critical editions of texts in a traditional manner. Major features include:

- automatic stepped line numbering, by page, section or paragraph;
- sub-lineation within the main series of line numbers;
- variant readings automatically keyed to line numbers;
- caters to both prose and verse;
- multiple series of footnotes and endnotes;
- block or columnar formatting of the footnotes;
- simple tabular material may be line numbered;
- indexing keyed to page and line numbers.

`reledmac` allows the scholar engaged in preparing a critical edition to focus attention wholly on the task of creating the critical text and evaluating the variant readings, text-critical notes and testimonia. `LATEX` and `reledmac` will take care of the formatting and visual correlation of all the disparate types of information.

Apart from `reledmac` there are other `LATEX` packages for typesetting critical editions. However, the aim of `reledmac` is to provide an “all in one” and flexible tool in the field of critical editions.

Any suggestions for new features are welcome.

This manual contains a general description of how to use `reledmac`, followed by the complete source code and its extensive documentation (in sections I and following, enumerated with Roman numerals). It ends with a list of actions to do when migrating from one version to other, a change history and an index to the source code.

You do not need to read the source code for this package in order to use it; we provide this code primarily for reference, and many of our comments on it repeat material that is also found in earlier sections. But no documentation, however thorough, can cover every question that comes up and many can be answered quickly by consulting the code. On a first reading, we suggest that you read only the general documentation in sections 2, unless you are particularly interested in the innards of `reledmac`.

1.2 History

1.2.1 edmac

The original version of `edmac` was `TEXTED.TEX`, written by John Lavagnino in late 1987 and early 1988 for formatting critical editions of English plays.

John passed these macros on to Dominik Wujastyk who, in September–October 1988, added the footnote paragraphing mechanism, margin swapping and other changes to suit his own purposes, making the style more like that traditionally used for classical texts in Latin and Greek (e.g., the Oxford Classical Texts series). He also wrote some extra documentation and sent the files out to several people. This version of the macros was the first to be called `edmac`.

The present version was developed in the summer of 1990, with the intent of adding necessary features, streamlining and documenting the code, and further generalizing it to make it easily adaptable to the needs of editors in different disciplines. John did most of the general reworking and documentation, with the financial assistance of the Division of the Humanities and Social Sciences, California Institute of Technology. Dominik adapted the code to the conventions of Frank Mittelbach’s `doc` option, and added some documentation, multiple-column footnotes, cross-references, and crop marks.¹ A description by John and Dominik of this version of `edmac` was published as ‘An overview of `edmac`: a PLAIN \TeX format for critical editions’, *TUGboat* 11 (1990), pp. 623–643.

From 1991 through 1994, the macros continued to evolve, and were tested at a number of sites. We are very grateful to all the members of the (now defunct) `edmac@mailbase.ac.uk` discussion group who helped us with smoothing out the bugs and infelicities in the macros. Ron Whitney and our anonymous reviewer at the TUG were both of great help in ironing out last-minute wrinkles, while Ron made some important suggestions which may help to make future versions of `edmac` even more efficient. Wayne Sullivan, in particular, provided several important fixes and contributions, including adapting the Mittelbach/Schöpf ‘New Font Selection Scheme’ for use with PLAIN \TeX and `edmac`. Another project Wayne has worked on is a DVI post-processor which works with an `edmac` that has been slightly modified to output `\specials`. This combination enables you to recover to some extent the text of each line as ASCII code, facilitating the creation of concordances, an *index verborum*, etc.

As of 1994, we were pleased to be able to say that `edmac` was being used for the real-life book production of several interesting editions, such as the Latin texts of Euclid’s *Elements*,² an edition of the letters of Nicolaus Copernicus,³ Simon Bredon’s *Arithmetica*,⁴ a Latin translation by Plato of Tivoli of an Arabic astrolabe text,⁵ a Latin translation of part II of the Arabic *Algebra* by Abū Kāmil Shujā’ b. Aslam,⁶ the Latin *Rithmacha* of Werinher

¹This version of the macros was used to format the Sanskrit text in volume I of *Metarules of Pāṇinian Grammar* by Dominik Wujastyk (Groningen: Forsten, 1993).

²Gerhard Brey used `edmac` in the production of Hubert L. L. Busard and Menso Folkerts, *Robert of Chester’s (?) Redaction of Euclid’s Elements, the so-called Adelard II Version*, 2 vols., (Basel, Boston, Berlin: Birkhäuser, 1992).

³Being prepared at the German Copernicus Research Institute, Munich.

⁴Being prepared by Menso Folkerts *et al.*, at the Institut für Geschichte der Naturwissenschaften in Munich.

⁵Richard Lorch, Gerhard Brey *et al.*, at the same Institute.

⁶Richard Lorch, ‘Abū Kāmil on the Pentagon and Decagon’ in *Vestigia Mathematica*, ed. M. Folkerts and J. P. Hogendijk (Amsterdam, Atlanta: Rodopi, 1993).

von Tegernsee,⁷ a middle-Dutch romance epic on the Crusades,⁸ a seventeenth-century Hungarian politico-philosophical tract,⁹ an anonymous Latin compilation from Hungary entitled *Sermones Compilati in Studio Gererali Quinqueecclesiensi in Regno Ungarie*,¹⁰ the collected letters and papers of Leibniz,¹¹ Theodosius's *Spherics*, the German *Algorismus* of Sacrobosco, the Sanskrit text of the *Kāśikāvṛtti* of Vāmana and Jayāditya,¹² and the English texts of Thomas Middleton's collected works.

1.2.2 ledmac

Version 1.0 of `tabmac` was released by Herbert Breger in October 1996. This added the capability for typesetting tabular material.

Version 0.01 of `edstanza` was released by Wayne Sullivan in June 1992, to help a colleague with typesetting Irish verse.

In March 2003 Peter Wilson started an attempt to port `edmac` from TeX to LaTeX. The starting point was `edmac` version 3.16 as documented on 19 July 1994 (available from CTAN). In August 2003 the `tabmac` functions were added; the starting point for these being version 1.0 of October 1996. The `edstanza` (v0.01) functions were added in February 2004. Sidenotes and regular footnotes in numbered text were added in April 2004. This port was called `ledmac` (LaTeX `edmac`).

Since July 2011, `ledmac` is maintained by Maïeul Rouquette. It is increasingly powerful and flexible, but it also has become increasingly divergent from the original TeX macro.

1.2.3 eledmac

Important changes were put in version 1.0, to make `ledmac` more easily extensible (see 7 p. 42). These changes can trigger small problems with the old customization. That is why a new name was selected: `eledmac` (extended `ledmac`).

To migrate from `ledmac` to `eledmac`, please read A.2 p. 388.

1.2.4 reledmac

`eledmac` has facilitated the creation of customized critical editions. However, the changes made to allow such customization were made in a non-systematic way. Many deprecated commands were kept and many technical 'debts' were accumulated, hindering the future evolution of the package.

For these reasons, Maïeul Rouquette decided on a spring cleaning of the code. As some commands name were changed, the resulting compatibility was broken (a little).

⁷Menso Folkerts, 'Die Rithmachia des Werinher von Tegernsee', ibid.

⁸Geert H. M. Claassens, *De Middelnederlandse Kruisvaartromans*, (Amsterdam: Schiphower en Brinkman, 1993).

⁹Emil Hargittay, *Csáky István: Politica philosophiae Okoskodás-szerint való rendes életnek példája (1664–1674)* (Budapest: Argumentum Kiadó, 1992).

¹⁰Being produced, as was the previous book, by Gyula Mayer in Budapest.

¹¹Leibniz, *Sämtliche Schriften und Briefe*, series I, III, VII, being edited by Dr. H. Breger, Dr. N. Gädeke and others at the Leibniz-Archiv, Niedersächsische Landesbibliothek, Hannover. (see <http://www.nlb-hannover.de/Leibniz>)

¹²Being prepared at Poona and Lausanne Universities.

A new name was selected: `reledmac` (extended renewed `eledmac`). To migrate from `eledmac` to `reledmac`, please read A.9 p. 391.

1.3 Bibliography

A collaborative list of works edited with (r)(e)ledmac is available at https://www.zotero.org/groups/209265/critical_editions_typeset_with_edmac_ledmac_eledmac_and_reledmac/. Please add your own edition made with (r)(e)ledmac.

If you write a book or an article about (r)(e)ledmac, please add it on the collaborative bibliography on <https://www.zotero.org/groups/1024519/>.

2 How the package works – the problem of the number of L^AT_EX runs

The `reledmac` package is a three-pass package like L^AT_EX itself. Although your textual apparatus and line numbers will be printed on the first run, it takes two more compilations by L^AT_EX to be sure that everything is correctly placed, and one more if you typeset right-to-left text with X_EL^AT_EX. If you make any subsequent changes altering the number of lines or notes, the input file may similarly require three passes to get everything to the right place. `reledmac` will tell you that you need to make more runs when it detects changes, but it does not expend the labor to check this thoroughly. If you have problems with a line or two misnumbered at the top of a page, try running L^AT_EX once or twice more.

However, the best way to be sure that one has made the right number of runs is to use some of L^AT_EX's run scripts like *latexmk*.

3 Compatibility warning

If you use other classes than `\article` or `\book`, or modify the layout with `geometry`, some settings should be made to have correct height for the blocks of notes.

Please read 7.12.6 p. 54.

A file may mix *numbered* and *unnumbered* text.

Numbered text is printed with marginal line numbers and can include footnotes and endnotes that are referenced to those line numbers: this is how you will want to print the text that you are editing.

Unnumbered text is not printed with line numbers, and you can't use `reledmac`'s note commands with it: this is appropriate for introductions and other material added by the editor around the edited text.

4 Options

The package can be loaded with a number of global options which are listed here. There are two types of options: 1) options which provide specific features, and, 2) options which optimize the package's performance. It is advisable for you to read the relevant

parts of the handbook, before reading about the first type of option (specific features), but you can look at the second type (package optimization) in your first reading of the manual.

4.1 Specific features

draft underlines lemmas in the main text.

auxdir `reledmac` generates auxiliary files. It could be useful to store them in a specific directory. You can set it using `auxdir=<folder>` option. Note the two following point:

1. `TEX` is not able to create folder. You should create it yourself.
2. The option does not change the default `LATEX` auxiliary files (`.aux`, `.toc`, ...).

eledmac-compat help to migrate from `eledmac` to `reledmac` (see A.9.5 p. 392).

nopenalties must be called in some cases when using paragraphed endnotes (?? p. ??

nopbinverse prevents page break within verse environment.

noquotation by default, the quotation environment is redefined within numbered text. You can disable this redefinition with `noquotation` (see 17 p. 74).

noresetlinenumannotation Does not reset the annotations to line number at each line. See 5.5 p. 24.

parapparatus by default, the apparatus cannot contain paragraph breaks; this option enables paragraphing inside the apparatus.

swcaseinsensitive make `\sameword` command case insensitive.

widthliketwocolumns set the width of the text printed in a single column to be the same as the width of the text printed in two parallel columns with `reledpar`. This is useful when alternating between normal and parallel typesetting.

xindy and `xindy+hyperref` select `xindy` as the index processor (13.5 p. 68).

4.2 Optimizing package performance

nocritical disables tools for critical footnotes (`\Afootnote`, `\Bfootnote` etc.). If you do not need critical footnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.

noeledsec disables tools for `\eledsection` and related commands (16.2 p. 73).

noend disables tools for endnotes (`\Aendnote`, `\Bendnote` etc.). If you do not need endnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.

nofamiliar disables tools for familiar footnotes (\footnoteA, \footnoteB etc.). If you do not need familiar footnotes, this option lets **reledmac** run faster. It will also preserve room for other packages.

noledgroup **reledmac** allows use of a series of critical notes and a new series of normal notes inside minipage and ledgroup environments (see 10 p. 60). However, such features use up computer memory, at the expense of other processing needs. So if you do not need this feature, use **noledgroup** option. This should make **reledmac** faster.

series **reledmac** defines five levels of notes: A, B, C, D, E. Using all these levels consumes memory space and processing speed. This is why, if your work does not require the entire A–E series, you can narrow down the available number of series. For example, if you only need A and B series, call the package with **series={A,B}** option.

5 Text lines and paragraphs numbering

5.1 Text lines numbering

\beginnumbering **\endnumbering** Each section of numbered text must be preceded by **\beginnumbering** and followed by **\endnumbering**, as in the following example.

```
\beginnumbering
Text
\endnumbering
```

The **\beginnumbering** macro resets the line number to zero, reads an auxiliary file called *<jobname>.nn* (where *<jobname>* is the name of the main input file for this job, and nn is 1 for the first numbered section, 2 for the second section, and so on), and then creates a new version of this auxiliary file to collect information during this run. The first instance of **\beginnumbering** also opens a file called *<jobname>.<series>end* to receive the text of the endnotes. **\endnumbering** closes the *<jobname>.nn* file.

If the line numbering of a text is to be continuous from start to end, then the whole text will be typed between one pair of **\beginnumbering** and **\endnumbering** commands. But your text will most often contain chapter or other divisions marking sections that should be independently numbered, and these will be appropriate places to begin new numbered sections.

reledmac has to read and store in memory a certain amount of information about the entire section when it encounters a **\beginnumbering** command, so it speeds up the processing and reduces memory use when a text is divided into a larger number of sections (at the expense of multiplying the number of external files that are generated).

5.2 Paragraphs

5.2.1 Basics

\pstart Within a numbered section, each paragraph of numbered text must be marked using the **\pend**

\pstart and \pend commands like this:

```
\pstart
Paragraph of text.
\pend
```

Text that appears within a numbered section but is not marked with \pstart and \pend will not be numbered.

The following example shows the proper section and paragraph markup and the kind of output that would typically be generated:

```
\beginnumbering
\pstart
This is a sample paragraph, with
lines numbered automatically.
\pend
```

```
\pstart
This paragraph too has its
lines automatically numbered.
\pend
```

The lines of this paragraph are
not numbered.

```
\pstart
And here the numbering begins
again.
\pend
\endnumbering
```

5.2.2 Automatically producing \pstart ... \pend

\autopar You can use \autopar to avoid the nuisance of this paragraph markup and still have every paragraph automatically numbered. The \autopar command needs to be called inside a \beginnumbering...\\endnumbering structure, as follows:

```
\beginnumbering
\autopar
```

A paragraph of numbered text.

Another paragraph of numbered
text.

```
\endnumbering
```

\autopar fails, however, on paragraphs that start with a { or with any other command that starts a new group before it generates any text. Such paragraphs need to be started explicitly, before the new group is opened, using \indent, \noindent, or

\leavevmode, or using \pstart itself.¹³

5.2.3 Content before specific \pstart and after specific \pend

Both \pstart and \pend can take an optional argument in brackets. Its content will be printed before the beginning of \pstart / after the end of \pend instead of the argument of \AtEveryPstart / \AtEveryPend.

Note that a \noindent will be automatically added before this argument, and, consequently, a \parskip will be inserted. You can use a second optional argument in brackets to avoid that \noindent.

```
\pstart[foo] % A \noindent will be inserted before foo.  
\pstart[] [foo] % No \noindent before foo.
```

The second optional argument of \pstart / \pend replaces the argument of \AtEveryPstart* / \AtEveryPend*.

If you need to start a \pstart with brackets, or to add brackets after a \pend, just add a \relax between \pstart ... \pend and the brackets.

This feature is also useful when typesetting verses (see 9 p. 55) or reledpar (see 19.2 p. 78).

A \noindent is automatically added before this argument.

5.2.4 Content before every \pstart and after every \pend

\AtEveryPstart
\AtEveryPend

You can use both \AtEveryPstart and \AtEveryPend. Their arguments will be printed before every \pstart begins / after every \pend ends.

Note that a \noindent will be inserted before the argument, and, consequently, a \parskip. You can use the starred version of \AtEveryPstart and \AtEveryPend to avoid the \noindent.

The argument of \AtStartEveryPstart / \AtEndEveryPend will be inserted at the beginning / the end of every \pstart / \pend in the same paragraph. For example, if you want each \pstart to start with a star, you can use:

```
\AtStartEveryPstart{*}
```

Instead of manually doing

```
\pstart * Real pstart content.\pend
```

5.2.5 Numbering paragraphs (\pstart)

It is possible to insert a number at every \pstart command; you must use the \numberpstarttrue command to have it. You can stop the numbering with \numberpstartfalse. You can redefine the command \thepstart to change style. You can change the value

¹³For a detailed study of the reasons for this restriction, see Barbara Beeton, 'Initiation rites', *TUGboat* 12 (1991), pp. 257–258.

of the pstart number by using *after* \begin{numbering}:

```
\setcounter{pstart}{value}
```

On each \begin{numbering} the numbering restarts.

With the \sidepstartnumtrue command, the number of \pstart will be printed at the sides of the text. In this case, the line number will be not printed.

With the \labelpstarttrue command, a \label added just after a \pstart will refer to the number of this pstart.

5.2.6 Languages written in Right to Left

If you use languages written right to left with Lua^LT_EX or X^LT_EX, you must switch text direction *before* the \pstart command.

5.2.7 Memory limits

This paragraph is kept for history, but the problems described below should not appear with the most recent version of L^AT_EX.

```
\pausenumbering  
\resumenumbering
```

reledmac stores a lot of information about line numbers and footnotes in memory as it goes through a numbered section. But at the end of such a section, it empties its memory out, so to speak. If your text has a very long numbered section it is possible that your L^AT_EX may reach its memory limit. There are two solutions to this.

The first solution is to get a larger L^AT_EX with increased memory.

The second solution is to split your long section into several smaller ones. The trouble with this is that your line numbering will start again at zero with each new section. To avoid this problem, we provide \pausenumbering and \resumenumbering which are just like \endnumbering ... \begin{numbering}, except that they arrange for your line numbering to continue across the break. Use \pausenumbering only between numbered paragraphs:

```
\begin{numbering}  
\pstart  
Paragraph of text.  
\pend  
\pausenumbering  
  
\resumenumbering  
\pstart  
Another paragraph.  
\pend  
\endnumbering
```

We have defined these commands as two macros, in case you find it necessary to insert text between numbered sections without disturbing the line numbering. But if you are really just using these macros to save memory, you might as well type,

```
\newcommand{\memorybreak}{\pausenumbering\resumenumbers}
```

and type `\memorybreak` between the relevant `\pend` and `\pstart`.

5.3 Lineation commands

5.3.1 Disabling lineation

`\numberlinefalse` `\numberlinetrue` Line numbering can be disabled with `\numberlinefalse`. It can be enabled again with `\numberlinetrue`.

This feature must be used with caution.

- It should not be used if you have critical footnotes after `\numberlinefalse`.
- It could be used in the following cases:
 - You want only familiar footnotes, not critical footnotes;
 - You want only parallel typesetting (using `reledpar`) but no critical footnotes.
 - You disable, for a portion of text, line numbering
- It must not be used if:
 - You just not want to have the line number in the margins, but want to use critical footnote. In this case, set to a big value, such as 100,000 (5.3.2 p. 21).
 - You want to freeze the line numbering for some line, but still keep critical footnotes. In this case, use `\startlock` (5.4.2 p. 23).

A successor to `reledmac` may disable this feature.

5.3.2 Setting lineation start and step

`\firstlinenum` `\linenumincrement` By default, `reledmac` numbers every 5th line. There are two counters that control this behaviour: `firstlinenum` and `linenumincrement`. They can be changed using `\firstlinenum{<num>}` and `\linenumincrement{<num>}`. `\firstlinenum` specifies the first line that will have a printed number, and `\linenumincrement` is the difference between successive numbered lines. For example, to start printing numbers at the first line and to have every other line numbered:

`\firstlinenum{1} \linenumincrement{2}`

There are similar commands, `\firstsublinenum{<num>}` and `\sublinenumincrement{<num>}` for controlling sub-line numbering.

You can define `\linenumberlist` to specify a non-uniform distribution of printed line numbers. For example:

`\gdef\linenumberlist{1,2,3,5,7,11,13,17,19,23,29}`

to have numbers printed on prime-numbered lines only. There must be no spaces within the definition which consists of comma-separated integer numbers. The numbers can be

in any order but it is easier to read if you put them in numerical order. Either omitting the definition of `\linenumberlist` or following the empty definition

```
\gdef\linenumberlist{}
```

the standard numbering sequence is applied. The standard sequence is that specified by the combination of the `firstlinenum`, `linenumincrement`, `firstsublinenum` and `linenumincrement` counter values.

5.3.3 Setting lineation reset

`\lineation`

Lines can be numbered either by page, by pstart or by section; you specify this using the `\lineation{<arg>}` macro, where `<arg>` is either page, pstart or section.

You may only use this command at places where numbering is not in effect; you can't change the lineation system within a section. You can change it between sections: they don't all have to use the same lineation system. The package's standard setting is `\lineation{section}`. If the lineation is by pstart, the pstart number will be printed before the line number in the notes.

5.3.4 Setting line number margin

`\linenummargin`

The command `\linenummargin{<location>}` specifies the margin where the line (or pstart) numbers will be printed. The permissible values for `<location>` are `left`, `right`, `inner`, or `outer`: for example, `\linenummargin{inner}`. The package's default setting is

```
\linenummargin{left}
```

to typeset the numbers in the left hand margin. You can change this whenever you're not in the middle of making a paragraph.

More precisely, the value of `\linenummargin` used is the value in effect at the `\pend` of a numbered paragraph. Apart from an initial setting for `\linenummargin`, only change `\linenummargin` after a `\pend`, whereupon it will apply to all following numbered paragraphs, until changed again (changing it between a `\pstart` and `\pend` pair will apply the change to all of the current paragraph).

5.3.5 Other settings

`\leftlinenum`
`\rightlinenum`
`\linenumsep`

When a marginal line number is to be printed, there are many ways to display it. You can redefine `\leftlinenum` and `\rightlinenum` to change the way marginal line numbers are printed in the left and right margins respectively; the initial versions print the number in font `\numlabfont` (described below) at a distance `\linenumsep` (initially set to one pica) from the text.

5.4 Changing the line numbers

Normally, line numbering starts at 1 for the first line of a section and increments by one for each line thereafter. There are various common modifications of this system and the commands described here allow you to put such modifications into effect.

5.4.1 Sublineation

`\startsub` You insert the `\startsub` and `\endsub` commands in your text to turn sub-lineation on and off. For example, stage directions in plays are often numbered with sub-line numbers: as line 10.1, 10.2, 10.3, rather than as 11, 12, and 13. Titles and headings are sometimes numbered with sub-line numbers as well.

When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it doesn't take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if it changes in the middle.

`Xsublinesep` You can change the separator between the line number and the subline number either by using `\Xsublinesep` without any optional argument (7.2.9 p. 46) or by using `\Xsublinesepside`. In the second case, it will change the separator only for line numbers in the margins, not in the footnotes.

5.4.2 Locking lineation

`\startlock` The `\startlock` command, used in running text, locks the line number at its current value, until you insert `\endlock`. It can tell for itself whether you are in a patch of line or sub-line numbering. One use for line-number locking is in printing poetry: there the line numbers should be those of verse lines rather than of printed lines, even when a verse line requires several printed lines. But in this case you may use the `\stanza` mechanism, see 9 p. 55.

`\lockdisp` When line-number locking is used, several printed lines may have the same line number, and you have to specify whether you want the number attached to the first printed line or the last, or whether you just want the number printed by them all, assuming that the settings of the previous parameters requires the display of a line number for this line. You specify your preference using `\lockdisp{<arg>}`; its argument is a word, either `first`, `last`, or `all`. The package initially sets this as `\lockdisp{first}`.

5.4.3 Setting and changing line number

`\setline` In some cases you may want to modify the line numbers that are automatically calculated: if you are printing only fragments of a work but want to print line numbers appropriate to a complete version, for example. The `\setline{<num>}` and `\advanceline{<num>}` commands may be used to change the current line's number (or the sub-line number, if sub-lineation is currently on). They change both the marginal line numbers and the line numbers passed to the notes. `\setline` takes one argument, the value to which you want the line number set; it must be 0 or greater. `\advanceline` takes one argument, an amount that should be added to the current line number; it may be positive or negative.

`\setlinenum` The `\setline` and `\advanceline` macros should only be used within a `\pstart... \pend` group. The `\setlinenum{<num>}` command can be used outside such a group, for example, between a `\pend` and a `\pstart`. It sets the line number to `<num>`. It has no effect if used within a `\pstart... \pend` group.

5.4.4 Line number style

`\linenumberstyle{<style>}`
`\sublinenumberstyle{<style>}`

Alph Uppercase letters (A ... Z).

alph Lowercase letters (a ... z).

arabic Arabic numerals (1, 2, ...)

Roman Uppercase Roman numerals (I, II, ...)

roman Lowercase Roman numerals (i, ii, ...)

Note that with the **Alph** or **alph** styles, ‘numbers’ must be between 1 and 26 inclusive.

Similarly `\sublinenumberstyle{<style>}` can be used to change the numbering style of sub-line numbers, which is normally arabic numerals.

5.4.5 Skipping and hidding number

`\skipnumbering`

When inserted into a numbered line the macro `\skipnumbering` causes the numbering of that particular line to be skipped; that is, the line number is unchanged and no line number will be printed. Note that if you use it in `\stanza`, you must call it at the beginning of the verse.

`\hidenumbering`

When inserted into a numbered line, the macro `\hidenumbering` causes the number for that particular line to be hidden; namely, no line number will print. Note that if you use it in `\stanza`, you must call it at the beginning of the verse.

`\hidenumberingonleftpage`

`\hidenumberingonleftpage` is like `hidenumbering`, but is applied only on left page. `\hidenumberingonrightpage` is applied on right page. They can be useful if the position of the line number is depending of the position of the page, but the position of marginal note is fixed.

5.5 Adding annotations to line numbers

You may want to have two or more numbers associated with a line of text. Consider, for example, the following cases:

- You want to split a line of verse into two parts depending upon some stylistic / rhythmic / linguistic convention.
- You want to add the line number used by a previous edition of the work.
- You want to typeset biblical text, and use division in verse.

In such instances, you must add the second number manually, as `reledmac` can’t determine a general pattern for such numbering, which depends too heavily upon the edited text.¹⁴

To resolve this issue, `reledmac` allows you to annotate line numbers using the fol-

¹⁴However, you may create your own commands dealing with such patterns which will in turn call `reledmac` commands.

lowing command:

```
\linenumannotation{<annotation>}
```

The annotation can contain any textual value (whether number, text, or other) such as the line number from the older edition. Here are some characteristics of line number annotation:

- An annotation is associated with a line of text. It is reset with each new line of text, unless you use the `noresetlinenumannotation` option of `reledmac`.
- It is printed alongside the line number in the margin.
- It is printed following the line number in critical footnotes and endnotes.
- And of particular interest: the annotation is printed in the critical note *only* when the `\edtext` is issued after the `\linenumannotation`.
- If two or more annotations are called before an `\edtext`, the last one is used in associated notes.
- If an annotation is called within an `\edtext`, it is printed as an annotation for the end of the lemma.

Here is an example, supposing we are on line 1:

```
\edtext{first lemma}
\linenumannotation{A}
\edtext{second lemma}{...}
\edtext{third%}
    \linenumannotation{B}
    lemma}{...}
\edtext{fourth lemma}&
```

In the critical notes, the line number will be followed

- by nothing in the first lemma, as there is no annotation for this line;
- by “A” for the second lemma;
- by “A-B” for the third lemma, as it starts while annotation A is still in effect and it finishes after annotation B has already taken effect;
- by “B” for the fourth lemma.

5.5.1 Modifying annotation associated with a specific note

`\lineannot` The `\linenum` (6.2.5 p. 32) macro changes the line number passed to a note. The `\lineannot` macro does the same for the annotations. It takes one argument, containing the beginning and ending annotations separated by a pipe (|). As with `\linenum`, if one wishes to change some specific part of the annotation, one can use

```
\lineannot{|b}|% to change the ending annotation
\lineannot{|a}|% to change the beginning annotation
\lineannot{|a|b}|% to change both
\lineannot{\empty}|% to delete the beginning annotation
```

5.5.2 Changing the position of the annotation

By default, annotations are placed after line numbers in both margin and footnote.

To change this behaviour, one can use one of the following commands:

- `\Xlinenumannotationposition[⟨s⟩]{⟨v⟩}` changes the position in critical footnotes with ⟨s⟩ for the series of footnotes to which it applies, where ⟨s⟩ may be a comma-separated list of series. When ⟨s⟩ is empty, the change applies also to annotations at the sides of the page, alongside the line number.
- `\Xlinenumannotationpositionside{⟨v⟩}` changes the position at the sides of the page, alongside the line numbers.
- `\Xendlinenumannotationposition[⟨s⟩]{⟨v⟩}` changes the position in critical endnotes, ⟨s⟩ for the series of endnotes to which it applies, where ⟨s⟩ may once again be a comma-separated list of series.

In each of these three commands, ⟨v⟩ can be `after` or `before` to indicate position with regards to the line number.

5.5.3 Changing the macro in which annotations are wrapped

By default, annotations are wrapped in the `\textsuperscript` macro. You can modify this using one of the following:

- `\Xwraplinenumannotation[⟨s⟩]{⟨cmd⟩}` for critical footnotes; ⟨s⟩ indicates the series of notes to which it applies and may be a comma-separated list of series. When ⟨s⟩ is empty, the change applies to the annotations in the margins also—around the line number—as well as to the annotations referenced using the `\annotationref` command of the crossref mechanism (11 p. 60).
 - `\Xwraplinenumannotationside{⟨cmd⟩}` for annotations in the margins only.
- Note that `\Xwraplinenumannotation` without any optional argument will override this setting.

- `\Xwraplinenumannotationref{<cmd>}` for annotations referenced using the `\annotationref` command of the crossref mechanism (11 p. 60).

Note that `\Xwraplinenumannotation` without any optional argument will override this setting.

- `\Xendwraplinenumannotation[<s>]{<cmd>}` for critical endnotes, where `<s>` indicates the series of notes to which it applies, which may be a comma-separated list.

`<cmd>` is a command which can take one argument; the backslash is required though.

For example, if you do not wish to have annotations in the margins, but do want to have them in bold in the critical footnotes and endnotes, you say:¹⁵

```
\makeatletter
\Xwraplinenumannotation{\textbf}
\Xendwraplinenumannotation{\textbf}
\Xwraplinenumannotationside{\@gobble}
\makeatother
```

5.5.4 Not printing the second identical annotations

If you print only line number annotation, you may get in critical notes something like 6-6, because the starting and ending annotations are the same. You can avoid that using `\Xnoidenticallinenumannotation[<s>]`, for critical footnotes or `\Xendnoidenticallinenumannotation[<s>]`

5.5.5 Separator between annotations

If there are more than one annotation in the same line, there are separated by a comma. If you want to change the separator, you can use `\setlinenumannotationsep{<sep>}`

5.6 Executing code at each line

`\dolinehook` provides an advanced feature for users. The argument passed to `\dolinehook{<arg>}` will be executed before slicing a new line in the paragraph. The argument passed to `\doinsidelinehook{<arg>}` will be executed before printing a new line, when the line number has already been fixed. In many cases, the latter is more useful than the former. The file examples/2-line_numbers_in_header.tex provides an example for printing the first and last line numbers of a page in the header.

5.7 Executing code at a specific line

Sometime, you want to execute a code at a precise point in the flow of your text. For example, if the current header of the page corresponds to the position inside the text,

¹⁵The `\@gobble` command takes one argument, and returns nothing.

you may want to use `\markboth` (or similar) command. The main problem is that you need to execute `\markboth` when `reledmac` typesets the text, and not when it reads it, because that could create damage with vertical spacing.

`\doinsidethislinehook`

The `\doinsidethislinehook{<code>}` macro allows `<code>` to be executed when the text is typeset. The `<code>` will be executed in the line equivalent to the position of `\doinsidethislinehook` in the flow of the text.

For example, with the following code:

```
\beginnumbering
\pstart
...
1.\doinsidelinehook{\markboth{1}{1}} a
\pend
```

`\markboth{1}{1}` will be executed at the line the 1. will be typeset. The `<code>` of `\doinsidethislinehook` will be executed only at the second run of `LATEX`.

See the file `examples/2-subdivision-number-in-header.tex` for an example. Especially, the use of this command with `LATEX` counters is quite complex, but the example show you how to deal with this problem.

6 Apparatus commands

6.1 Terminology

We call “critical notes” notes which refer to both a lemma, that is a part of text, and a line number. Critical notes are subdivided in critical footnotes and critical endnotes.

We call “familiar notes” notes which refer to a footnote mark in the main text.

`reledmac` manages many series of notes of each category. A series of notes is identified by an uppercase letter. When the series letter is at the *beginning* of a command name, it refers to a critical footnote. When the series letter is at the *end* of a command name, it refers to a familiar footnote.

So :

- `\Afootnote` is a critical footnote of the series A.
- `\Bendnote` is a critical endnote of the series B.
- `\footnoteC` is a familiar footnote of the series C.

6.2 Critical notes

6.2.1 The lemma

`\edtext` Within numbered paragraphs, all footnotes and endnotes are generated by the `\edtext` macro:

```
\edtext{<lemma>}{<commands>}
```

The *<lemma>* argument is the lemma in the main text: \edtext both prints this as part of the text, and makes it available to the *<commands>* you specify to generate notes.

For example:

```
I am happy:  
I saw my friend \edtext{Smith}{  
  \Afootnote{Jones C, D.}  
  on Tuesday.  
} 1 I am happy: I saw my friend Smith on  
  2 Tuesday.  
_____  
1 Smith ] Jones C, D.
```

The lemma Smith is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, Jones C, D. The footnote macro is supplied with the line number at which the lemma appears in the main text.

The *<lemma>* may contain further \edtext commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

```
I am happy : \edtext{I saw my friend 1 I am happy : I saw my friend Smith on  
  \edtext{Smith}{\Afootnote{Jones 2 Tuesday.  
  C, D.}} on Tuesday.}{  
  \Bfootnote{The date was  
  July 16, 1954.}  
} 1 Smith ] Jones C, D.  
_____  
1-2 I saw my friend Smith on Tuesday.] The  
date was July 16, 1954.
```

However, \edtext cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; an \edtext that starts in the *<lemma>* argument of another \edtext must end there, too. (The \lemma and \linenum commands may be used to generate overlapping notes if necessary.)

6.2.2 Footnotes

The second argument of the \edtext macro, *<commands>*, may contain a series of subsidiary commands that generate various kinds of notes.

\Afootnote Five separate series of footnotes are maintained; each macro takes one argument like \Afootnote{<text>}. When all of the five are used, the A notes appear in a layer just below the main text, followed by the rest in turn, down to the E notes at the bottom.
 \Bfootnote These are the main macros that you will use to construct the critical apparatus of your text.
 \Cfootnote
 \Dfootnote
 \Efootnote

If you need more series of critical notes, please look at 6.7.1 p. 40.

An optional argument can be added before the text of the footnote. Its value is a comma-separated list of options. The available options are:

- **fulllines** to disable \Xtwolines and \Xmorethanwolines features for this note (cf. 7.2.5 p. 44).
- **nonum** disables line numbering for this note. A horizontal blank space is added instead. You can use \Xinplaceofnumber to set it (7.2.13 p. 47).
- **nosep** to disable the lemma separator for this note. A horizontal blank space is added instead. You can use \Xinplaceoffemmaseparator to set it (7.4.1 p. 48).

- `linerangesep=⟨c⟩` to change to `⟨c⟩` the separator between start line and end line for this particular note.

Example: `\Afootnote[nonum]{⟨text⟩}`.

6.2.3 Endnotes

`\Aendnote`

`\Bendnote`

`\Cendnote`

`\Dendnote`

`\Eendnote`

Inserting endnotes The package also maintains five separate series of endnotes.

If you do not need the endnotes facility, you should use `noend` option when loading `reledmac`.

The mechanism is similar to the one for footnotes: each macro takes one or more optional arguments and one single argument, like:

`\Aendnote[⟨option⟩]{⟨text⟩}`.

`⟨option⟩` can contain a comma-separated list of values. Allowed values are:

- `fulllines` to disable `\Xendtwolines` and `\Xendmorethanwolines` features for this particular note (cf. 7.2.5 p. 44).
- `nonum` to disable line number for this particular note.
- `nosep` to disable the lemma separator for this particular note. A horizontal blank space is added instead. You can use `\Xendinplaceoflemmaseparator` to set it (7.4.2 p. 49).
- `linerangesep=⟨c⟩` to change to `⟨c⟩` the separator between start line and end line for this particular note.

`\doendnotes`

Printing endnotes Normally, endnotes are not printed: you must use the `\doendnotes{⟨s⟩}`, where `⟨s⟩` is the letter of the series to be printed. Put this command where you want the corresponding set of endnotes printed. In this case, all the endnotes of the `⟨s⟩` series are printed, for all numbered sections.

`\doendnotesbysection`

However, you may want to print the endnotes of one given series covering the first numbered section, then the endnotes of another given series covering the first numbered section, then the endnotes of the first given series covering the second numbered section, then the endnotes of the second given series covering the second numbered section, and so forth. In this case, use `\doendnotesbysection{⟨s⟩}`. For each value of `⟨s⟩`, the first call of the command will print the notes for the first series, the second call will print the notes for the second series etc. For example, do:

```
\section{Endnotes}
\subsection{First text}
\doendnotesbysection{A}
\doendnotesbysection{B}
\subsection{Second text}
\doendnotesbysection{A}
\doendnotesbysection{B}
```

Note that by default inside endnotes no separator is used between the lemma and the content. However you can use the `\Xendlemmaseparator` macro to define one (7.4.2 p. 48).

As endnotes may be printed at any point in the document they always start with the page number where they are called.

toendnotes Xtoendnotes **Code between endnotes** Sometimes, it is useful to insert content between endnotes of the same series: for example to separate endnotes of different sections of the same text. In this case, you could use *inside numbered text* the command:
`\toendnotes[⟨series⟩]{⟨content⟩}` where *⟨series⟩* is a comma-separated list of the series of endnotes where *⟨content⟩* must be inserted. If *⟨series⟩* is empty, then *⟨content⟩* is inserted to all the series.

For example:

```
\toendnotes{\section{Section's title}}
```

Alternatively, you can use `\Xtoendnotes{⟨content⟩}`, where “X” must be replaced by a series letter.

Remember that the endnotes are temporarily stored in an auxiliary file. That means in general you want to write the *⟨content⟩* in the auxiliary file *without expanding it*, that is without interpreting *TEX* content.

However, in some cases, you may want to write a once-expanded¹⁶ version of the *⟨content⟩*, that is the version where the commands are expanded on the first level. This can be, for example, to get a counter value. Use the starred version in this case. For example:

```
\Atoendnotes*{\string\section{Letter 1 (chap. \thechapter)}}
```

6.2.4 Paragraph in critical apparatus

By default, no paragraph can be made in the notes of the critical apparatus. You can allow it by adding the options `parapparatus` when loading the package :

```
\usepackage[parapparatus]{eledmac}
```

Note that you *cannot* use paragraphs (e.g. blank lines or `\par`) inside of notes, when they are set to *paragraph* arrangement!

6.2.5 Change lemma and line number

\lemma If you want to change the lemma that gets passed to the notes, you can do this by using `\lemma{⟨alternative⟩}` within the second argument to `\edtext` and before the note commands. The most common use of this command is to abbreviate the lemma that’s printed in the notes. For example:

¹⁶The expansion mechanism of *TEX* is a quite complex problem, but fundamental. We have no place to explain it fully here. Read introduction to *TEX* to understand well.

```
I am happy :
\edtext{I saw my friend
  \edtext{Smith}{\Afootnote{Jones
    C, D.}} on Tuesday.}
  {\lemma{I \dots} Tuesday.}
  \Bfootnote{The date was
    July 16, 1954.}
}

1 I am happy : I saw my friend Smith on
2 Tuesday.
_____
1 Smith ] Jones C, D.
_____
1-2 I ... Tuesday.] The date was July 16, 1954.
```

\linenum

You can use `\linenum{<arg>}` to change the line numbers passed to the notes. `<arg>` actually consist of seven parameters: the page, line, and sub-line number for the start of the lemma; the same three numbers for the end of the lemma; and the font specifier for the lemma. As the argument to `\linenum`, you specify those seven parameters in that order, separated by vertical bars (the `|` character). I.e.

`\linenum{<start page>}|<s. line>|<s. sub-l>|<end p>|<e. l>|<e. sub-l>||}`
 However, you can retain the value computed by `reledmac` for any number by simply omitting it; and you can omit a sequence of vertical bars at the end of the argument. For example, `\linenum{|||23}` changes only the ending page number of the current lemma.

This command does not change the marginal line numbers in any way; it just changes the numbers passed to the notes. Its use comes in situations that `\edtext` has trouble dealing with for whatever reason. If you need notes for overlapping passages that aren't nested, for instance, you can use `\lemma` and `\linenum` to generate such notes despite the limitations of `\edtext`. If the `<lemma>` argument to `\edtext` is extremely long, you may run out of memory; here again you can specify a note with an abbreviated lemma using `\lemma` and `\linenum`. The numbers used in `\linenum` need not be entered manually; you can use the ‘`x-`’ symbolic cross-referencing commands below (11 p. 60) to compute them automatically.

Similarly, being able to manually change the lemma's font specifier in the notes might be important if you were using multiple scripts or languages. The form of the font specifier is three separate codes separated by `/` characters, giving the family, series, and shape codes as defined within NFSS.

6.2.6 Changing the names of commands for critical apparatus

The commands for generating the apparatus have been given rather bland names, because editors in different fields have widely divergent notions of what sort of notes are required, where they should be printed, and what they should be called. But this does not mean you have to type `\Afootnote` when you would rather type something you find more meaningful, like `\variant`.

We recommend that you create a series of such aliases and use them instead of the names chosen here; all you have to do is put commands of this form at the start of your file:¹⁷

```
\newcommandx{\variant}[2][1,usedefault]{\Afootnote[#1]{#2}}
```

¹⁷We use `\newcommand` and `\newcommandx` instead of classical `\let` command because the `edtable` environments have to modify the notes definition, and we need to use the newest definition of notes. Read the handbook of `xargs` to know more about `\newcommandx`.

```
\newcommandx{\explanatory}[2][1,usedefault]{\Bfootnote[#1]{#2}}
\newcommand{\trivial}[1]{\Aendnote{#1}}
\newcommandx{\testimonia}[2][1,usedefault]{\Cfootnote[#1]{#2}}
```

6.3 Disambiguation of identical words in the apparatus

Sometimes, the same word occurs twice (or more) in the same line. `reledmac` provides tools to disambiguate references in the critical notes. The lemma will be followed by a reference number if a given word occurs more than once in the same line.

6.3.1 Basic use

`\sameword` To use this tool, you have to mark every occurrence of the potentially ambiguous term with the `\sameword` command:

```
Lupus \sameword{aut} canis \edtext{\sameword{aut}}{\Afootnote{et}} felix
```

In this example, `aut` will be followed, in the critical note, by the exponent 2 if it is printed in the same line as the first `aut`, but it will not if it is printed in a different line. The number is printed only after the second run.

6.3.2 Case setting

By default, `\sameword` is sensitive to the case. E.g. “foo” is considered as a different word to “Foo”.

You can use the `swcaseinsensitive` when loading the package to make `\sameword` insensitive to the case, i.e. to consider “foo” as identical “Foo”.

6.3.3 Notes about input encoding with UTF-8 processor

If you use UTF-8 processor, like Xe^T_EX or Lua^T_EX, there should not be any glitches. However, pay attention to how characters are encoded. Similar-looking characters may be represented differently in unicode numbering.

For instance, in Greek, “ φ ” has two possible unicode numbers:

- GREEK SMALL LETTER ALPHA (U+03B1) + COMBINING GREEK YPOGEGRAMMENI (U+0345)
- GREEK SMALL LETTER ALPHA WITH YPOGEGRAMMENI (U+1FB3)

Which unicode number you use depends, many times, on your keyboard configuration (the computer-input system).

Inside `reledmac`, the `\sameword` command considers these two unicodes (code positions) as different characters. If you use only one unicode number consistently, the distinction will probably make no difference to how your text looks, but `\sameword` will process the text inaccurately, based on the unicode numbers. To prevent this, do the following:

- If you use Xe^TE_X, add this line in your preamble: \XeTeXinputnormalization 1.
- If you use Lua^TE_X, use the `uninormalize` package of Michal Hoftich¹⁸ with the `buffer` option set to true.

With these tools, Xe^TE_X / Lua^TE_X will dynamically normalize unicode input when reading the file. Consequently, you will have no problems with the `\sameword` command.

6.3.4 Use with `\lemma` command

If you use the `\lemma` command, `reledmac` cannot know to which occurrence of `\sameword` in the first argument of `\edtext` a word marked with `\sameword` in `\lemma` should refer.

For example, in the following example:

```
some thing
\edtext{\sameword{sw}}
    and other \sameword{sw}
    and again \sameword{sw}
    it is all}%
{\lemma{\sameword{sw} \ldots all}\Afootnote{critical note}}.%
```

`reledmac` cannot know if the “sw” in `\lemma` refers to the word after “thing”, after “other”, or after “again”.

Consequently, you must tell `reledmac` to which instance of `\sameword` you are referring in the first argument of `\edtext`:

- In the content of `\lemma`, use `\sameword` with no optional argument.
- In the first argument of `\edtext`, use `\sameword` with the optional argument `[\langle X \rangle]`. $\langle X \rangle$ is the depth of the `\edtext` where the `\lemma` is used. So if the `\lemma` is called in a `\edtext` inside another `\edtext`, $\langle X \rangle$ is equal to 2. If the `\lemma` is called in a `\edtext` “of first level”, $\langle X \rangle$ is equal to 1. If the lemma is called in both 1 and 2 `\edtext` depth, $\langle X \rangle$ is 1, 2. If that word is referenced in the lemma of every `\edtext` depth, $\langle X \rangle$ can also be set to `inlemma`.

Note that only words that are actually referenced in a `\lemma` need the optional argument. Therefore, the first `\sameword` in the example above should have “1” as its optional argument, to be referenced correctly in the lemma.


Note also that the $\langle X \rangle$ does not refer to the level where the `\sameword` occurs, but to the level of the `\lemma` that refers to that `\sameword`. For example:

```
\edtext{some \edtext{\sameword[1]{word}}{\Afootnote{om. M}}}
    and other \sameword{word}
    and again a \sameword{word}
    it is all}%
{\lemma{some \sameword{word} \ldots all}\Afootnote{critical note}}.%
```

¹⁸<https://github.com/michal-h21/uninormalize>.

Here the `\sameword` occurs in an `\edtext` of level 2, but since it is referenced by `\lemma` on level 1, it has “1” in the optional argument.

In the following example figure, each framed box represents an `\edtext` level. Each number is an occurrence of `\sameword`. After a framed box, the text in superscript represents the content of `\lemma` for that `\edtext` level. The text in subscript at the right of a number represents the content of the optional argument of `\sameword`.



The `\sameword` number 3 is called in a `\lemma` related to an `\edtext` of level 2. It must be marked by “2”.

The `\sameword` number 5 is called in a `\lemma` related to `\edtext` of level 1. It must be marked by “1”.

The `\sameword` number 1 is called in two `\lemmas`: one related to a `\edtext` of level 1, the other related to `\edtext` of level 2. It must be marked by “1,2”. However, as `\lemma` is called only in level 1 and 2, “1,2” could be replaced by “inlemma”.

The `\sameword` number 2 is in the first argument of a `\edtext` of level 3, but it has no `\lemma-command`, so there is no need to mark it.

Here, the corresponding code:

```
\edtext{%
  \edtext{%
    \sameword[inlemma]{A} (1)
    \edtext{%
      \sameword{A} (2)
    }%
  }%
  \footnote{level~3}%
}%
\sameword[2]{A} (3)
}%
\lemma{%
  \sameword{A}%
  \ldots%
  \sameword{A}%
}%
\footnote{level~2}%
\sameword{A} (4)
\sameword[1]{A} (5)
}%
\lemma{\sameword{A}\ldots\sameword{A}}%
\footnote{level~1}%
}
```

1	A (1) A (2) A (3) A (4) A (5)	
		1 A ^{1...A⁵}] level 1
		1 A ^{1...A³}] level 2
		1 A ² (2)] level 3

6.3.5 Sameword for a group of words

Sometimes a group of words and not only a single word, occurs multiple times. In this case, you have two possibilities.

First, you can consider only the individual words, and not groups of word. For example:

```
\sameword{per} \sameword{causam}
tamen scire
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
est
\edtext{\sameword{per} \sameword{causam}}{\Bfootnote{causam rei B}}
cognoscere
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
```

1 per causam tamen scire causam est per causam cognoscere causam

1 causam²] fnote
 1 per² causam³] causam rei B
 1 causam⁴] fnote

In this case it is clear which “per causam” is meant.

However, in the case that “per causam” is the lemma of the second note, there should be only one number for that whole lemma. In this case we can mark all “per causam” groups. But as “causam” is also called as lemma in note 1 and 3, we need to use nested \sameword commands. Consequently, we need to use \lemma for the \edtext linked to “per causam”, as we don’t want to number each individual word.

```
\sameword{per \sameword{causam}} tamen scire
\edtext{\sameword{causam}}{\Bfootnote{fnote}} est
\edtext{\sameword[1]{per \sameword{causam}}}{\lemma{\sameword{per causam}}\Bfootnote{causam}}
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
```

1 per causam tamen scire causam est per causam cognoscere causam

1 causam²] fnote
 1 per causam²] causam rei B
 1 causam⁴] fnote

6.3.6 Customizing

`\showwordrank` You can redefine the `\showwordrank` macro to change the way the number is printed. The default value is

```
\newcommand{\showwordrank}[2]{%
  #1\textsuperscript{#2}%
}
```

6.3.7 Problems with some macros

- `\swnoexpands` Macros inside `\sameword` that are not fully expandable, mainly macros which manipulate font features, write on full or have optional argument, may cause problems during compilation. Custom commands inside `\sameword` may therefore result in errors saying that “Use of `sameword` doesn’t match its definition.” To solve this, include a redefinition of your custom commands in the `\swnoexpands` macro. In order to not include any content of a macro during comparison, identify the command with `\@gobble`. For example:

```
\makeatletter
\appto{\swnoexpands}{%
  \let\somemacro\@gobble%
}
\makeatother
```

This will drop the content of `\somemacro` during comparison.

To include the content of the first and only one argument of a custom command in `sameword` comparison, use the `\@firstofone` command. For example, this is how `\emph` is handled:

```
\makeatletter
\appto{\swnoexpands}{%
  \let\emph\@firstofone%
}
\makeatother
```

To include command which can take optional argument, use `\RenewExpandableDocumentCommand` of `\xparse`. For example, this is how `\edindex` is handled:

```
\makeatletter
\appto{\swnoexpands}{%
  \RenewExpandableDocumentCommand{\edindex}{om}{}%
}
\makeatother
```

6.3.8 Automatic `sameword` annotation

All potentially ambiguous apparatus entries must be annotated manually. That annotation process is laborious and includes a risk of errors. *Samewords* is a Python script that can automate this step of the process. It can be installed via the *Python Package Index*, but see <https://github.com/stenskjaer/samewords> for more info and documentation. The script is still at a beta stage, so comments and questions as well as error reports are very welcome at <https://github.com/stenskjaer/samewords/issues>.

Please note that the maintainer of this script is not identical with the maintainer of `reledmac`.

6.4 Apparatus of manuscripts

The critical notes mostly refer to textual variants between manuscripts which contain the text to be edited. It may so happen that the manuscripts only contain parts of the text. Depending on one's wishes, `reledmac` can generate lists of relevant manuscripts for any delimited portion of text. Such lists are referred to as "apparatuses of manuscripts".

To produce an apparatus of manuscripts with `reledmac`, you have to insert specific commands that are used to mark the sections for which only part of the manuscripts are relevant. These commands will be processed, and **after the second TeX run**, corresponding apparatuses of manuscripts will be inserted in the first (viz. 'A' series) level of footnotes.

As the insertion of this apparatus can change the page breaks, you may have to run TeX two or more times. We strongly recommend to use tools like *latexmk* to do that.

6.4.1 Marking sections of text

`\msdata{\text{}}` must be inserted at the point where a section for which only part of the manuscripts are relevant starts. `\text{}` can be any arbitrary text, viz. a list of the manuscripts that are used for the section that starts. The command must be attached right at the point where the section starts, with no space, like so:

```
\msdata{ABC}Lorem ipsum
```

Which means that the section of text starting by "Lorem ipsum" is witnessed by manuscripts A, B and C.

`\stopmsdata` must be inserted at the point where the section of text previously marked by `\msdata` ends. The command must be attached right to the end of the section, with no space. As `\stopmsdata` is a *TeX* argumentless macro, it will gobble the following space. To keep that space, you have to either append a backslash followed by a space or `{}` to `\stopmsdata`, like so:

```
\msdata{ABC}Lorem ipsum dolor  
[...]  
amet\stopmsdata{} \msdata{ABCD}sic transit [...]
```

Which means that the part of text containing "Lorem ipsum dolor [...] amet" is witnessed by manuscripts A, B and C, while the part of text starting by "sic transit" is witnessed by manuscripts A, B, C and D.

`\stopmsdata` is also automatically inserted by `\msdata`.

Note that in most cases, any `\stopmsdata` is followed by `\msdata`. However, as these two command are usually separated by a space, it may happen that a line break be automatically inserted between them. This is why it is advised to always insert `\stopmsdata`, even if `\msdata` inserts it in case it is forgotten.

6.4.2 Layout of the apparatus of manuscripts

On every page, the apparatus of manuscripts marks the corresponding section with starting and ending line numbers. However, the following rules will be applied:

- If the section does not start on the current page, the starting line number will be the line number of the first line on the page.
- If the section does not stop on the current page, the ending line number will be the line number of the last line on the page.
- If the section neither starts nor ends on the current page, no line number will be printed. The same is true in case both `\msdata` is called at the very beginning of the page and `\endmsdata` is called at the very end of the page.

6.4.3 Settings

As the apparatus of manuscripts technically consists of first-level critical notes ('A' series), any setting available for critical notes can be applied (7 p. 42). However, the following *additional* commands are available.

`\setmsdataseries`

The series used by default for the apparatus of manuscripts is series A. However, you can change it with `\setmsdataseries{<series>}`.

`\setmsdatalabel`

As the apparatus of manuscripts consists of regular critical footnotes, a lemma is associated to them. By default, it is "Ms.". You can change it using `\setmsdatalabel{<txt>}`.

`\setmsdataposition`

If you want the manuscript apparatus to be on the same level of critical footnotes as the other apparatuses, for each line, reledmac will first insert the manuscript apparatus, then the other footnotes. You can change it using:

`\msdataposition{regular-msdata}`

And restore the default behaviour using `\msdataposition{msdata-regular}`

6.5 Familiar notes

6.5.1 Basic use

`\footnoteA` As well as the standard L^AT_EX footnotes generated via `\footnote`, the package also provides five series of additional footnotes called `\footnoteA` through `\footnoteE`. These have the familiar marker in the text, and the marked text at the foot of the page can be formatted using any of the styles described for the critical footnotes. Note that the 'regular' footnotes have the series letter at the end of the macro name whereas the critical footnotes have the series letter at the start of the name.

The footnote can take a first optional argument to manually define the footnote number or footnote symbol. For example:

```
\footnoteA[22]{This footnote will be numbered 22}
```

6.5.2 Customizing mark

`\thefootnoteA` Each series uses a set of macros for styling the marks. The mark numbering scheme of series A is defined by the `\thefootnoteA` macro; the default is:

`\renewcommand*{\thefootnoteA}{\arabic{footnoteA}}`

The appearance of the mark in the text is controlled by `\bodyfootmarkA` which is defined as:

```
\newcommand*{\bodyfootmarkA}{%
  \hbox{\textsuperscript{\normalfont\@nameuse{@thefnmarkA}}}}
```

The command `\footfootmarkA` controls the appearance of the mark at the start of the footnote text. It is defined as:

```
\newcommand*{\footfootmarkA}{\textsuperscript{\@nameuse{@thefnmarkA}}}
```

There are similar command triples for the other series.

6.5.3 Separator for multiple footnotes

The `footmisc` package [Fai03] by Robin Fairbairns has an option whereby sequential footnote marks in the text can be separated by commas^{3,4} like so. As a convenience `reledmac` provides this automatically.

`\multfootsep`

`\multfootsep` is used as the separator between footnote markers. Its default definition is:

```
\providecommand*{\multfootsep}{\textsuperscript{\normalfont,}}
```

and can be changed if necessary.

6.6 Printing the footnote mark without printing the footnote text

`\footnoteXmark`
`\footnoteXtext`

In certain cases, you can't directly use `\footnote{X}`; for example, when using `\uline` command of the `ulem` package. You need to print the footnote mark first, then call the footnote text to be inserted.

For all $\langle X \rangle$ command, `reledmac` provides a `\footnote{X}mark` command and a `\footnote{X}text` command, equivalent to standard L^AT_EX's command `\footnotemark` and `\footnotetext`. For example, to use with `\uline`, do:

```
This is \uline{a test containing\mbox{\footnoteAmark}}\footnoteAtext{A simple footnote.}\uline{ a simple footnote.}
```

If you use `reledpar`, you can't use these two commands to print the footnote mark on one side and the footnote text on the other side.

You must use `\footnote{X}nomk` and `\footnote{X}mk`, defined in `reledpar` (?? p. ??)

6.7 Changing series

6.7.1 Create a new series

If you need more than five series of critical footnotes, you can create extra series, using `\newseries` command. For example, to create F and G series `\newseries{G,H}`.

6.7.2 Delete series

As the number of series which are defined increases, `reledmac` gets slower. If you do not need all of the six standard series (A–E), you can load the package with the `series` option. For example, if you need only series A and B, use:

```
\usepackage[series={A,B}]{eledmac}
```

6.7.3 Series order

The default series order is the one called with the `series` option of the package, or, if this option is not used, A, B, C, D, E. Series order determines footnotes order.

`\seriesatbegin` `\seriesatend` However in some specific cases, you need to change the series order at some point inside the document. You can use `\seriesatbegin{⟨s⟩}` to pull up a given series `⟨s⟩` to the beginning, or `\seriesatend{⟨s⟩}` to push it down to the end.

6.8 Position of critical and familiar footnotes

`\fnpos` There is a historical incoherence in (r)(e)ledmac. The familiar footnotes are before the critical footnotes in a normal page, but after in a minipage or in a ledgroup. However, it is possible to change the relative position of both types of footnotes. If you want to have familiar footnotes after critical footnotes in a normal page, use:

```
\fnpos{critical-familiar}
```

Or, if you want a minipage or ledgroup to have critical footnotes after familiar footnotes, use:

```
\mpfnpos{familiar-critical}
```

You can also decide to alternate familiar and critical footnotes with your own order. In this case, the second argument of `\fnpos` or `\mpfnpos` is a comma-separated list of values. Each value has the following form:

`⟨series⟩⟨type⟩`

`⟨series⟩` is a series letter (A,B,C etc.), while `⟨type⟩` must be either “critical” or “familiar”.

For example, suppose you want to first print the familiar footnotes of the “A” series, then all the series of critical footnotes, and finally all the series of familiar footnotes, except the “A” series. In this case, use the following command:

```
\fnpos{%
  {A}{familiar},
  {A}{critical},%
  {B}{critical},%
  {C}{critical},%
  {D}{critical},%
  {E}{critical},%
  {B}{familiar},%
  {C}{familiar},%
  {D}{familiar},%
  {E}{familiar}%
}
```

Note that you must define the position of all the series of footnotes you use. If you don't, you will have infinite runs of L^AT_EX.

7 Apparatus customization

Some commands can be used to change the display of the footnotes. All can have an optional argument [$\langle s \rangle$], which is the letter of the series — or a list of letters separated by comma — depending on which option is applied. If the optional argument is omitted or empty, the setting will apply to the entire series.

When a length, noted $\langle l \rangle$, is used, it can be stretchable: `a plus b minus c`. The final length m is calculated by L^AT_EX to have: $a - c \leq m \leq a + b$. If you use some relative unit¹⁹, it will be relative to font size of the footnote, except for commands concerning the place kept by the notes — including blank space.

Some commands are boolean, indicating when an option is enabled. If you want to disable the option after enabling it, you must use `[false]` as the second optional argument. For example:

- `\XX[A] [false]` to disable the 'XX' option for the series A.
- `\XX[] [false]` to disable it for all series.

There is also name convention:

- Names prefixed by `X` are for setting of critical footnotes.
- Names prefixed by `Xend` are for setting of critical endnotes.
- Names suffixed by `X` are for setting of familiar footnotes.

7.1 Notes arrangement in a series

`\Xarrangement`
`\arrangementX`

By default, all footnotes are formatted as a series of separate paragraphs in one column. Three other formats are also available for notes.

Use `\Xarrangement[⟨s⟩]{⟨a⟩}` to change the arrangement of the ⟨s⟩ series of critical footnotes and `\arrangementX[⟨s⟩]{⟨a⟩}` to change the arrangement of the ⟨s⟩ series of familiar footnotes.

The value of ⟨a⟩ can be one of the following

- `paragraph` formats all of the footnotes of a series as a single paragraph; if you use this arrangement, you are strongly encouraged to read 19.1.6 p. 77.
- `twocol` formats them as separate paragraphs, but in two columns;
- `threecol`, in three columns.
- `normal`, restore normal arrangement.

¹⁹Like `em` which is the width of an 'm' in a given font.

You should set up the page layout parameters, and in particular the `\baselineskip` of the footnotes, before you call this macro because its action depends on these; too much or too little space will be allotted for the notes on the page if these macros use the wrong values.

Note that you *cannot* use paragraphs (e.g. blank lines or `\par`) or line breaks (`\break` or `\linebreak` or `\newline` etc.) inside of notes, when they are set to paragraph arrangement!

The notes arrangement must be called after having defined the document geometry setting. If you must change geometry setting inside your document, do not forget to call note arrangement again.

`\hsize` has been set for the pages that use this series of notes; otherwise TeX will try to put too many or too few of these notes on each page. If you need to change the `\hsize` within the document, call the arrangement macro again afterwards to take account of the new value.

7.2 Control line number printing

7.2.1 Print line number only at first time

By default, the line number is printed in every note. If you want to print it only the first time for a given line number (i.e., once for line 1, once for line 2, etc.), you can use `\Xnumberonlyfirstinline[⟨s⟩]`.

Suppose you have a lemma on line 2 and a lemma between line 2 and line 3. With `\Xnumberonlyfirstinline`, the second lemma is considered to be on the same line as the first lemma. But if you use both `\Xnumberonlyfirstinline[⟨s⟩]` and `\Xnumberonlyfirstintwo[⟨s⟩]`, a distinction is made.

For setting a particular symbol in place of the line number, you can use `\Xsymlinenum[⟨s⟩]{⟨symbol⟩}` in combination with `\Xnumberonlyfirstinline[⟨s⟩]`. From the second lemma of the same line, the symbol will be used instead of the line number. Note that any command called in `⟨symbol⟩` must be robust. Use `\robustify` to robustify a non-robust command.

For endnotes, `\Xendnumberonlyfirstinline`; `\Xendnumberonlyfirstintwo[⟨s⟩]` and `\Xendsymlinenum` are the equivalents of `\Xnumberonlyfirstinline[⟨s⟩]`; `\Xnumberonlyfirstintwo[⟨s⟩]` and `\Xsymlinenum`.

7.2.2 Print page number only at first time

For endnotes, `reledmac` provides a mechanism for printing the page number only the first time it is seen. However, when a lemma spans over two pages, the line numbers are normally printed in the following pattern: starting page number - starting line number - ending page number - ending line number. It follows that what corresponds to the actual ‘page number’ may not be self-evident. So: `\Xendpagenumberonlyfirst[⟨s⟩]` can be called to ensure that the starting page number of a lemma be not printed if it is the same as the ending page number of the preceding lemma. You can use *additionally* one (and only one) of the following commands:

- `\Xendpagenumberonlyfirstifsingle[⟨s⟩]`: the first page number of the lemma will not be printed only if the following conditions are true:

1. The starting page number of the lemma is the same as the ending page number of the preceding lemma.
2. The ending page number of the lemma is the same as the starting page number of the lemma.

In this case the ending page number will always be printed if it is different from the starting page number.

- `\Xendpagenumberonlyfirstintwo[⟨s⟩]`: both the starting page number and the ending page number of a lemma are not printed if they are both the same as the starting page number and the ending page number of the preceding lemma respectively.

In any case, you can use:

`\Xendsympagenum`

- `\Xendsympagenum[⟨series⟩]{⟨c⟩}` to print `⟨c⟩` when the page number is not printed.

`\Xendinplaceofpagenumber`

- `\Xendinplaceofpagenumber[⟨series⟩]{⟨l⟩}` to print a `⟨l⟩` length horizontal space in case no symbol is printed instead of the page number.

7.2.3 Arbitrary text before line number

`\Xbeforenumber`

`\Xbeforenumber[⟨s⟩]{⟨txt⟩}` allows the insertion of `⟨txt⟩` before the line number only when the line number is printed, so taking into account `\Xnumberonlyfirstinline` and the like.

`\Xendbeforepagenumber`

For endnotes `\Xendbeforepagenumber[⟨s⟩]{⟨text⟩}` defines the text before the page number in endnotes. Default value is p. (“p” followed by a dot).

`\Xendafterpagenumber`
`\Xendlineprefixsingle`

`\Xendafterpagenumber[⟨s⟩]{⟨text⟩}` defines the text after the page number in endnotes. Default value is) (open parenthesis followed by a single space). `\Xendlineprefixsingle[⟨s⟩]` defines the text before the line number in endnotes when there is only one line. Default value is empty. `\Xendlineprefixmore[⟨s⟩]{⟨text⟩}` defines the text before the line number in endnotes when there is more than one line. Default value is empty. If you don’t define it, it will use the value defined by `\Xendlineprefixsingle`.

`\Xendlineprefixmore`

7.2.4 Separator for line range

`\Xlinerangeseparator`
`\Xendlinerangeseparator`

By default, the separator between the begin line and the end line in a lines’ range is an en-dash in a normal font (`\textnormal{--}`). You can change it for critical footnotes with `\Xlinerangeseparator[⟨s⟩]{⟨text⟩}`, and with `\Xendlinerangeseparator[⟨s⟩]{⟨text⟩}` for critical endnotes.

`\Xtwolines`
`\Xmorethantwolines`

If a lemma is printed on two subsequent lines, `reledmac` will print the first and the last line numbers. Instead of this, it is also possible to print an abbreviation which stands for “line 1 and subsequent line(s)”.

To achieve this, use `\Xtwolines[⟨s⟩]{⟨text⟩}` and `\Xmorethanwolines[⟨s⟩]{⟨text⟩}`. The `⟨text⟩` argument of `\Xtwolines` will be printed if the lemma is on two lines, and the `⟨text⟩` argument of `\Xmorethanwolines` will be printed if the lemma is on three or more lines. For example:

```
\Xtwolines{sq.}
\Xmorethanwolines{sqq.}
```

will print “1sq.” for a lemma which falls on lines 1–2 and “1sqq.” for a lemma which falls on lines 1–4.

If you use `\Xtwolines` without setting `\Xmorethanwolines`, the `⟨text⟩` argument of `\Xtwolines` will be used for lemmas which fall on three or more lines.

However, if you want to use a short form (when the lemma overlaps two lines, but not more than two), use `\Xtwolinesbutnotmore[⟨series⟩]`.

When you use lineation by page, the final page number, if different from the initial page number, will not be printed, because the final page number is included in the `\Xendtwolines` symbol.

However, you can force print the final page number with
`\Xtwolinesonlyinsamepage[⟨series⟩]`.

You can disable `\Xtwolines` and related for a specific note by using the ‘[fulllines]’ argument in the note macro cf. 6.2.2 p. 29.

For endnotes, use these macros: `\Xendtwolines;` `\Xendmorethanwolines;`
`\Xendtwolinesbutnotmore;`
`\Xendtwolinesonlyinsamepage` instead of `\Xtwolines;` `\Xmorethanwolines;`
`\Xtwolinesbutnotmore;` `\Xtwolinesonlyinsamepage`.

7.2.6 Disable line number

`\Xnonumber` You can use `\Xnonumber[⟨s⟩]` if you do not want to have the line number in a footnote.
`\Xendnonumber` `\Xendnonumber[⟨s⟩]` is the same for endnote.

7.2.7 Printing pstart number

`\Xpstart` You can use `\Xpstart[⟨s⟩]` if you want to print the pstart number in the footnote, before the line and subline number. Note that when you change the lineation system, the option is automatically switched :

- If you use lineation by pstart, the option is enabled.
- If you use lineation by section or by page, the option is disabled.

`\Xstarteverytime` By default, the pstart number is printed only in the part of text where you have called `\numberpstarttrue`. We don’t know why you would like to print the pstart number in the notes and not in the main text. However, if you want to do it, you can call `\Xstarteverytime[⟨s⟩]`. In this case, the pstart number will be printed every time in footnote.

`\Xonlypstart` In combination with `\Xpstart`, you can use `\Xonlypstart[⟨s⟩]` if you want to print only the pstart number in the footnote, and not the line and subline number.

7.2.8 Printing stanza number

`\Xstanza` You can use `\Xstanza[⟨s⟩]` if you want to print the stanza number in the footnote, before the line and subline number.

Of course the stanza number is printed only when you use `\numberstanza`

`\Xstanzaseparator` When using `\Xstanza`, you can use `\Xstanzaseparator[⟨s⟩]{⟨text⟩}` to print `⟨text⟩` after the stanza number. Default value is empty.

7.2.9 Separator between line and subline numbers

`\Xsublinesep` `\Xsublinesep[⟨s⟩]{⟨txt⟩}` changes the separator between line and subline in footnotes.

Employed without optional argument, it also changes the separator in side numbering.

`\Xendsublinesep[⟨s⟩]{⟨txt⟩}` does the same thing for endnotes.

However, it does not change anything for the separator in side numbering. Use `\Xsublinesep` without optional argument or `\Xsublinesepside{⟨txt⟩}` to do it.

The default value is `\textnormal{.}`.

7.2.10 Separator between page and line numbers

`\Xpagelinesep` `\Xpagelinesep[⟨s⟩]{⟨txt⟩}` changes the separator between the page and line number in footnotes.

By default, the value defined for `\Xsublinesep` is used.

7.2.11 Space around number

`\Xbeforenumber` With `\Xbeforenumber[⟨s⟩]{⟨l⟩}`, you can add some space before the line number in a footnote. If the line number is not printed, the space is not either. The default value is 0 pt.

`\Xafternumber` With `\Xafternumber[⟨s⟩]{⟨l⟩}` you can add some space after the line number in a footnote. If the line number is not printed, neither is the space. The default value is 0.5 em.

`\Xendbeforenumber` and `\Xendafternumber` are the equivalents of `\Xbeforenumber` and `\Xafternumber` for endnotes.

By default, the space defined by `\Xafternumber` is breakable. With `\Xnonbreakableafternumber[⟨s⟩]` it becomes nonbreakable.

7.2.12 Space around line symbol

`\Xbeforesymlinenum` With `\Xbeforesymlinenum[⟨s⟩]{⟨l⟩}` you can add some space before the line symbol in a footnote. The default value is value set by `\Xbeforenumber`.

`\Xaftersymlinenum` With `\Xaftersymlinenum[⟨s⟩]{⟨l⟩}` you can add some space after the line symbol in a footnote. The default value is value set by `\Xafternumber`.

`\Xendbeforesymlinenum` and `\Xendaftersymlinenum` are the equivalents of

`\Xnonbreakableafternumber` and `\Xnonbreakablebeforenumber` for endnotes.

\Xbeforesymlinenum and \Xaftersymlinenum for the endnotes.

7.2.13 Space in place of number

\Xinplaceofnumber If no number or symbolic line number is printed, you can add a space, with \Xinplaceofnumber[⟨s⟩]{⟨l⟩}. The default value is 1 em.
\Xendinplaceofnumber \Xendinplaceofnumber[⟨s⟩]{⟨l⟩} is the same, for critical endnotes.

7.2.14 Boxing line number and line symbol

\Xboxlinenum It could be useful to put the line number inside a fixed box: the content of the note will be printed after this box. You can use \Xboxlinenum[⟨s⟩]{⟨l⟩} to do that. To subsequently disable this feature, use \Xboxlinenum with length equal to 0 pt. One use of this feature is to print line number in a column, and the note in an other column:

```
\Xhangindent{1em}
\Xafternumber{0em}
\Xboxlinenum{1em}
```

\Xboxsymlinenum \Xboxsymlinenum[⟨s⟩]{⟨l⟩} is the same as \Xboxlinenum but for the line number symbol.
\Xendboxsymlinenum \Xendboxsymlinenum[⟨s⟩]{⟨l⟩} is the same as \Xboxsymlinenum but for endnotes.

\Xboxlinenumalign If you put line number in box, it will be aligned left inside the box. However, you can change it using \Xboxlinenumalign[⟨s⟩]{⟨text⟩} where ⟨text⟩ can be the following:

L to align left (default value);

R to align right;

C to center.

When using \Xboxlinenum, reledmac put all the line number description in the same box. That is, the same box will contain: the start line number, the dash, and either the end line number or the range symbol (like ff.). However, it is possible to box them in two different boxes.

- \Xboxstartlinenum[⟨s⟩]{⟨l⟩} will box the start line number in a box of length ⟨l⟩. The content will be put at the right of the box.
- \Xboxendlinenum[⟨s⟩]{⟨l⟩} will box the dash plus the end line number or the range symbol in a box of length ⟨l⟩. The content will be put at the left of the box.

With these two commands, it is possible to horizontally align the dash of line number when using critical notes, to obtain something like:

```
1
12-23
24ff.
```

\Xendboxlinenum
 \Xendboxlinenumalign
 \Xendboxstartlinenumalign
 \Xendboxendlinenumalign

\Xendboxlinenum[$\langle s \rangle$]{ $\langle l \rangle$ }, \Xendboxlinenumalign[$\langle s \rangle$]{ $\langle text \rangle$ }, \Xendboxstartlinenum[$\langle s \rangle$]{ $\langle l \rangle$ } and \Xendboxendlinenum[$\langle s \rangle$]{ $\langle l \rangle$ } are the same as, respectively, \Xboxlinenum and \Xboxlinenumalign, \Xboxstartlinenum, \Xboxendlinenum except in endnotes.

7.3 Arbitrary code around line number

\Xendbhooklinenumber
 \Xendahooklinenumber
 \Xendbhookinplaceofnumber
 \Xendahookinplaceofnumber

\Xendbhooklinenumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code before line numbers in endnotes. The code is executed before the \Xendbeforelinenumber space and before the \Xendnotenumfont font setting.

\Xendahooklinenumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code after line number in endnotes. The code is executed after the \Xendafternumber space.

\Xendbhookinplaceofnumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code before space or symbol which replace line number in endnotes. The code is executed before the \Xendbeforesymlinenum space and before the \Xendnotenumfont font setting.

\Xendahookinplaceofnumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code after space or symbol which replace line number in endnotes. The code is executed after the \Xendaftersymlinenum space.

7.4 Separator between the lemma and the note

7.4.1 For footnotes

\Xlemmaseparator
 \Xbeforelemmaseparator
 \Xafterlemmaseparator
 \Xnolemmaseparator
 \Xinplaceoflemmaseparator

By default, in a footnote, the separator between the lemma and the note is a right bracket (\rbracket)²⁰. You can use \Xlemmaseparator[$\langle s \rangle$]{ $\langle Xlemmaseparator \rangle$ } to change it. The optional argument can be used to specify the series in which it is used. Note that there is a non-breakable space between the lemma and the separator, but a **breakable** space between the separator and the following text.

Using \Xbeforelemmaseparator[$\langle s \rangle$]{ $\langle l \rangle$ } you can add some space between lemma and separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

Using \Xafterlemmaseparator[$\langle s \rangle$]{ $\langle l \rangle$ } you can add some space between separator and note. If your lemma separator is empty, this space will not be printed. The default value is 0.5 em.

You can suppress the lemma separator, using \Xnolemmaseparator[$\langle s \rangle$], which is simply a alias of \Xlemmaseparator[$\langle s \rangle$]{ $\langle \rangle$ }.

With \Xinplaceoflemmaseparator[$\langle s \rangle$]{ $\langle l \rangle$ } you can add a space if no lemma separator is printed. The default value is 1 em.

7.4.2 For endnotes

\Xendlemmaseparator

By default, there is no separator inside endnotes between the lemma and the content of the note. You can use \Xendlemmaseparator[$\langle s \rangle$]{ $\langle Xendlemmaseparator \rangle$ } to change this. The optional argument can be used to specify the series in which it is used. A common value of $\langle Xendlemmaseparator \rangle$ is \lbracket.

²⁰For *polyglossia*, when the lemma is RTL, the bracket automatically switches to a left bracket.

Note that there is a non-breakable space between the lemma and the separator, but a **breakable** space between the separator and the following text.

Using `\Xendbeforelemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between the lemma and the separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

Using `\Xendafterlemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between the separator and the content of the note. If your lemma separator is empty, this space won't be printed. The default value is 0.5 em.

With `\Xendinplaceoflemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space if you choose to remove the lemma separator. The default value is 0.5 em.

7.5 Font style

7.5.1 For line number

`\Xnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes ; `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\Xendnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\notenumfontX[⟨s⟩]{⟨command⟩}` is used to change the font style for note numbers in familiar footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

7.5.2 For the lemma

By default, font of the lemma in footnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The `\Xlemmadisablefontselection[⟨s⟩]` command allows to disable it for a specific series.

By default, font of the lemma in endnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The command allows `\Xendlemmadisablefontselection[⟨s⟩]` to disable it for a specific series.

Use `\Xlemmafont[⟨s⟩]{⟨cmd⟩}` to apply a TeX font command to the lemma. For example, to have boldface lemma:

```
\Xlemmafont{\bfseries}
```

`\Xendlemmafont[⟨s⟩]{⟨cmd⟩}` is the same for endnotes.

7.5.3 For all notes

`\Xnotefontsize[⟨s⟩]{⟨command⟩}` is used to define the font size of critical footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard L^ET_EX size, like `\small`.

\notefontsizeX[⟨s⟩]{⟨command⟩} is used to define the font size of familiar footnotes of the series. The default value is \footnotesize. The ⟨command⟩ must not be a size in pt, but a standard L^AT_EX size, like \small.
 \Xendnotefontsize

\Xendnotefontsize[⟨s⟩]{⟨l⟩} is used to define the font size of end critical footnotes of the series. The default value is \footnotesize. The ⟨command⟩ must not be a size in pt, but a standard L^AT_EX size, like \small.

7.6 Wrapping notes

7.6.1 Wrapping lemmas

\Xwraplemma[⟨s⟩]{⟨cmd⟩} is used to wrap, in the footnote, the lemma in a L^AT_EX command. For example, with the bidi package, to ensure having a lemma written right to left, use \Xwraplemma{\RL}.

\Xendwraplemma[⟨s⟩]{⟨cmd⟩} is the same for endnotes.

7.6.2 Wrapping contents

\Xwrapcontent[⟨s⟩]{⟨cmd⟩} is used to wrap the footnote contents — excluding the lemma — in a L^AT_EX command.

For example, if the language of your note is not the same as the language of the lemma, use \Xwrapcontent{\foreignlanguage{⟨language⟩}} (with babel) or \Xwrapcontent{\text{⟨language⟩}} (for babel).

\Xendwrapcontent[⟨s⟩]{⟨cmd⟩} is the same for endnotes.
 \wrapcontentX[⟨s⟩]{⟨cmd⟩} is the same for familiar footnotes.

7.7 Indent of notes content

\Xparindent By default, reledmac does not add indentation before the paragraphs inside critical footnotes. Use \Xparindent[⟨s⟩] to enable indentation.

\parindentX By default, reledmac does not add indentation before the paragraphs inside familiar footnotes. Use \parindentX[⟨s⟩] to enable indentation.

\Xhangindent For critical notes NOT paragraphed you can define an indent with \Xhangindent[⟨s⟩]{⟨l⟩}, which will be applied in the second line of notes. It can help to make distinction between a new note and a break in a note. The default value is 0 pt.

\hangindentX For familiar notes NOT paragraphed you can define an indentation with \hangindentX[⟨s⟩]{⟨l⟩}, which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.

\Xendhangindent For critical endnotes NOT paragraphed you can define an indentation with \Xendhangindent[⟨s⟩]{⟨l⟩}, which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.

7.8 Arbitrary code at the beginning of notes

The three next commands add arbitrary code at the beginning of notes. As the name's space is local to the notes, you can use it to redefine some style inside the notes. For

example, if you don't want the pstart number to be in bold, use :

```
\Xbhooknote{\renewcommand{\thepstart}{\arabic{pstart}.}}
```

`\Xbhooknote` `\Xbhooknote[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each critical footnote.
`\bhooknoteX` `\bhooknoteX[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each familiar footnote.
`\Xendbhooknote` `\Xendbhooknote[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each endnote.

7.9 Arbitrary code before inserting note

`\Xbeforeinserting` `\Xbeforeinserting[⟨s⟩]{⟨code⟩}` and `\beforeinsertingX` `\beforeinsertingX[⟨s⟩]{⟨code⟩}` are very technical commands.

They allow one to add any arbitrary code just before the footnotes are added in the list of footnotes. The main use is to insert text direction code. For example, if you edit right-to-left text with `bidi`, but want your critical footnote be left-to-right, use `\Xbeforeinserting\LTR`. You should also use `\Xwraplemma` to ensure your lemmas are right-to-left in a left-to-right paragraph (7.6.1 p. 50)).

Note that the changes are local to the footnote.

7.10 Options for footnotes in columns

7.10.1 Alignment

`\Xcolalign` `\colalignX` By default, text in footnotes of two or three columns are flush left and without hyphenation. However, you can change this with `\Xcolalign[⟨s⟩]{⟨code⟩}` for critical footnotes, and `\colalignX[⟨s⟩]{⟨code⟩}` for familiar footnotes.

`<code>` must be one of the following command:

`\justifying` to have text justified, as usual with L^AT_EX. You can also let `<code>` empty.

`\raggedright` to have text left aligned, but *without hyphenation*. That is the default `reledmac` setting.

`\RaggedRight` to have text left aligned *with hyphenation* (requires `ragged2e`).

`\raggedleft` to have text right aligned, but *without hyphenation*.

`\RaggedLeft` to have text right aligned *with hyphenation* (requires `ragged2e`).

`\centering` to have text centered, but *without hyphenation*.

`\Centering` to have text centered *with hyphenation* (requires `ragged2e`).

7.10.2 Size of the columns

For the following four macros, be careful that the columns are made from right to left.

`\Xhsizetwocol` `\hsizetwocol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical notes are displaying in two columns. Default value is `.45 \hspace`.

`\Xhsizethreecol` `\hsizethreecol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical

notes are displaying in three columns. Default value is `.3 \hsize`.

`\hsizetwocolX`

`\hsizetwocolX[\langle s\rangle]{\langle l\rangle}` is used to change width of a column when familiar notes are displaying in two columns. Default value is `.45 \hsize`.

`\hsizethreecolX`

`\hsizethreecolX[\langle s\rangle]{\langle l\rangle}` is used to change width of a column when familiar notes are displaying in three columns. Default value is `.3 \hsize`.

7.11 Options for paragraphed footnotes and notes grouped by line

7.11.1 Mark separation of notes

`\Xafternote
\afternoteX`

You can add some horizontal space after a note by using `\Xafternote[\langle s\rangle]{\langle l\rangle}` (for critical footnotes) or `\afternoteX[\langle s\rangle]{\langle l\rangle}` (for familiar footnotes). The default value is `1em plus .4em minus .4em`.

`\Xparafootsep
\parafootsepX`

For paragraphed footnotes (see below), you can choose the separator between each note by using `\Xparafootsep[\langle s\rangle]{\langle text\rangle}` for critical notes and `\parafootsepX` for familiar notes. A common separator is the double pipe (`||`), which you can set by using `\Xparafootsep{\parallel}`.

Note that if the symbol defined by `\Xsymlinenum` must be used at the beginning of a note, the `\Xparafootsep / \parafootsepX` is not used before this note.

7.11.2 Ragged text

`\Xragged`

Text in paragraphed critical notes is justified, but you can use `\Xragged[\langle s\rangle]{L}` if you want it to be ragged left (i.e., right justified), or `\Xragged[\langle s\rangle]{R}` if you want it to be ragged right (i.e., left justified).

`\raggedX`

Text in paragraphed footnotes is justified, but you can use `\raggedX[\langle s\rangle]{L}` if you want it to be ragged left, or `\raggedX[\langle s\rangle]{R}` if you want it to be ragged right.

7.12 Options for block of notes

7.12.1 Grouping notes by line

`\Xgroupbyline`

If you do not use `\Xarrangement{paragraph}`, you may want to group all the critical footnotes related to the same line in the same paragraph. In this case, use `\Xgroupbyline[\langle series\rangle]`.

In many cases, you might like to use it in combination with `\Xnumberonlyfirstinline` (7.2.1 p. 43).

`\Xgroupbylineseparatwolines`

Note that the `\Xafternote` and `\Xparafootsep` settings are used to determine space and content between footnotes (7.11 p. 52). Suppose you have two notes on line 1 which overlap lines 1 and 2. This last note will be printed, if you use `\Xgroupbyline` in the same group as the previous one. In the case you want that note to be distinct, you must use both `\Xgroupbyline` and `\Xgroupbylineseparatwolines[\langle s\rangle]`.

In many cases, you might like to use it in combination with `\Xnumberonlyfirstintwolines` (7.2.1 p. 43)

7.12.2 Text before notes

- \Xtxtbeforenotes
 \txtbeforenotesX
 \Xendtxtbeforenotes
- \Xtxtbeforenotesonlyonce
 \txtbeforenotesonlyonceX
- You can add text before critical footnotes with \Xtxtbeforenotes[*s*]{*text*}.
 You can add text before familiar footnotes with \txtbeforenotesX[*s*]{*text*}.
 You can add text before endnotes with \Xendtxtbeforenotes[*s*]{*text*}. The text will be typeset only if there are endnotes.
 By default, such texts are inserted at the beginning of the groups of notes on each page. You can add \Xtxtbeforenotesonlyonce (for critical footnotes) and \txtbeforenotesonlyonceX (for familiar footnotes) to insert them only the first time notes are typeset.

7.12.3 Code before notes

- \Xbhookgroup
 \bhookgroupX
- While \Xtxtbeforenotes is for typesetting text before notes, \Xbhookgroup[*s*]{*code*} and \bhookgroupX[*s*]{*code*} (for critical and familiar respectively) are for executing code before a group of notes, between the rules and the printing of the notes.

7.12.4 Spacing

- \Xbeforenotes
 \beforenotesX
- \Xprenotes
 \prenotesX
- You can change the vertical space before the rule of the critical notes with \Xbeforenotes[*s*]{*l*}. The default value is 1.2em plus .6em minus .6em.
Be careful, the standard L^AT_EX footnote rule used by reledmac decreases by 3pt. This 3pt decrease is not changed by this command.
 You can change the vertical space printed before the rule of the familiar notes with \beforenotesX[*s*]{*l*}. The default value is 1.2em plus .6em minus .6em.
Be careful, the standard L^AT_EX footnote rule, which is used by reledmac, decreases 3pt. These 3pt are not changed by this command.
 You can set the space before the first series of critical notes printed on each page and set a different amount of space for each subsequent series on the page. You can do it with \Xprenotes{*l*}. The default value is 0pt. You can disable this feature by setting the length to 0pt.
 You can set the space before the first printed (in a page) series of familiar notes to be different from the space before other series. The default value is 0pt. You can do this with \prenotesX{*l*}. You can disable this feature by setting the length to 0pt.

7.12.5 Rule

- \Xafterrule
 \afterruleX
- You can change the vertical space printed after the rule of the critical notes with \Xafterrule[*s*]{*l*}. The default value is 0pt.
Be careful, the standard L^AT_EX footnote rule, which is used by reledmac, adds 2.6pt. These 2.6pt are not changed by this command.
 You can change the vertical space printed after the rule of the familiar notes with \afterruleX[*s*]{*l*}. The default value is 0pt.
Be careful, the standard L^AT_EX footnote rule, which is used by reledmac, adds 2.6pt. These 2.6pt are not changed by this command.

7.12.6 Maximum height

`\Xmaxhnotes` By default, one series of critical notes can take up to 80% of `\vsize`, before being broken to the next page. If you want to change the size use `\Xmaxhnotes[⟨s⟩]{⟨l⟩}`. Be careful : the length can't be flexible, and is relative to the current font. For example, if you want the note to take, at most, 33% of the text height, do `\Xmaxhnotes{.33\textheight}`.

`\maxhnotesX` `\maxhnotesX[⟨s⟩]{⟨l⟩}` is the same as previous, but for familiar footnotes.

Note that in many cases, you should call these commands in the begin of the document, because the `\vsize` in the preamble is not the same as `\vsize` after the preamble. That why we recommend to you to add in your preamble

```
\AtBeginDocument{
    \maxhnotesX{0.8\textheight}
    \Xmaxhnotes{0.8\textheight}
}
```

Be careful with the two previous commands. Actually, for technical purposes, one paragraphed note is considered as one block. Consequently, it cannot be broken between two pages, even if you used these commands. The debug is in the todolist.

7.12.7 Width

`\Xwidth` `\Xwidth[⟨s⟩]{⟨l⟩}` sets the total width of critical footnotes. `\widthX[⟨s⟩]{⟨l⟩}` does the same for familiar footnotes.

`⟨l⟩` can be a length expression, parsable with `\dimexpr`. For example:

```
\Xwidth{\columnwidth+\marginparsep+\ledrsnotewidth}
\widthX{\columnwidth+\marginparsep+\ledrsnotewidth}
```

Note that changes the width of the block of notes. If you want to change the width of each column when typesetting notes in columns, use `\Xsizetwocol`, `\Xsizethreecol`, `\hsizetwocolX`, `\hsizethreecolX`, see 7.10.2 p. 51.

7.13 Footnotes and the `reledpar` columns

`\Xnoteswidthliketwocolumns`
`\noteswidthliketwocolumnsX`

If you use `reledpar` `\columns` macro, you can call :

- `\Xnoteswidthliketwocolumns[⟨s⟩]` to create critical notes with a two-column size width.
- `\noteswidthliketwocolumnsX[⟨s⟩]` to create familiar notes with a two-column size width.

7.14 Line number annotation

The way line number annotations are typeset can be changed using hooks as described in 5.5.2 p. 26 and 5.5.3 p. 26.

7.15 Endnotes in one paragraph

- `\Xendparagraph` By default, any new endnote starts a new paragraph. Use `\Xendparagraph[⟨s⟩]` to have all end notes of one given series set in one paragraph.
- `\Xendafternote` You can add some space after a endnote series by using `\Xendafternote[⟨s⟩]{⟨l⟩}`. The default value is `1em plus .4em minus .4em`.
- `\Xendsep` You can choose the separator between each note by `\Xendsep[⟨s⟩]{⟨text⟩}`. A common separator is the double pipe (||), which you can set by using `\Xendsep{\parallel}`.

8 Fonts

One of the most important features of the appearance of the notes, and indeed of your whole document, will be the fonts used. We will first describe the commands that give you control over the use of fonts in the different structural elements of the document, especially within the notes, and then in subsequent sections specify how these commands are used.

- `\numlabfont` Line numbers for the main text are usually printed in a smaller font in the margin. The `\numlabfont` macro is provided as a standard name for that font: it is initially defined as
`\newcommand{\numlabfont}{\normalfont\scriptsize}`
 You might wish to use a different font if, for example, you preferred to have these line numbers printed using old-style numerals.
- `\select@lemmafont` We will briefly discuss `\select@lemmafont` here because it is important to know about it now, although it is not one of the macros you would expect to change in the course of a simple job. Hence it is ‘protected’ by having the @-sign in its name.

When you use the `\edtext` macro to mark a word in your text as a lemma, that word will normally be printed again in your apparatus. If the word in the text happens to be in a font such as italic or bold you would probably expect it to appear in the apparatus in the same font. This becomes an absolute necessity if the font is actually a different script, such as Arabic or Cyrillic. `\select@lemmafont` does the work of decoding `reledmac`’s data about the fonts used to print the lemma in the main text and calling up those fonts for printing the lemma in the note.

`\select@lemmafont` is a macro that takes one long argument—the cluster of line numbers passed to the note commands. This cluster ends with a code indicating what fonts were in use at the start of the lemma. `\select@lemmafont` selects the appropriate font for the note using that font specifier.

`reledmac` uses `\select@lemmafont` in a standard footnote format macro called `\normalfootfmt`. The footnote formats for each of the layers A to E are `\let` equal to `\normalfootfmt`. So all the layers of the footnotes are formatted in the same way.

9 Verse

9.1 Basic

- `\stanza` Use `\stanza` at the start of a stanza. Each line in a stanza is ended by an ampersand (&),
`\&`

and the stanza itself is ended by putting `\&` at the end of the last line.

If you need to add brackets directly after `\stanza`, `&` or `\&`, add `\norelax`. Otherwise, the brackets will be interpreted as delimitation of an optional argument (cf. 9.8 p. 58)

9.2 Define stanza indents

`\stanzaindentbase` Lines within a stanza may be indented. The indents are integer multiples of the length `\stanzaindentbase`, whose default value is 20pt.

`\setstanzaindents` In order to use the stanza macros, **one must set the indentation values**. First the value of `\stanzaindentbase` should be set, unless the default value 20pt is desired. Every stanza line indentation is a multiple of this.

To specify these multiples one invokes, for example
`\setstanzaindents{3,1,2,1,2}.`

The numerical entries must be whole numbers, 0 or greater, separated by commas without embedded spaces. The first entry gives the hanging indentation to be used if the stanza line requires more than one print line.

If it is known that each stanza line will fit in one print line, then this first entry should be 0; TeX does less work in this case, but no harm ensues if the hanging indentation is not 0 but is never used.

If you want the hanging verse to be flush right, you can use `\sethanginsymbol`: see p. 9.6 p. 58.

Enumeration is by stanza lines, not by print lines. In the above example the lines are indented one unit, two units, one unit, two units, with 3 units of hanging indentation in case a stanza line is too long to fit on one print line.

9.3 Repeating stanza indents

Since version 0.13, if the indentation is repeated every n verses of the stanza, you can define only the n first indentations, and indicate that they are repeated, defining the value of the `stanzaindentsrepetition` counter at n . For example:

```
\setstanzaindents{5,1,0}
\setcounter{stanzaindentsrepetition}{2}
```

is like

```
\setstanzaindents{5,1,0,1,0,1,0,1,0,1,0}
```

Be careful: the feature is changed in elemac 1.5.1. See A.3 p. 389.

If you don't use the `stanzaindentsrepetition` counter, make sure you have at least one more numerical entry in `\setstanzavalue`s than the number of lines in the stanza.

If you want to disable this feature again, just put the counter to 0:

```
\setcounter{stanzaindent}{0}
```

The macros make no restriction on the number of lines in a stanza. Stanza indentation values (and penalty values) obey T_EX's grouping conventions, so if one stanza among several has a different structure, its indentations (penalties) may be set within a group; the prior values will be restored when the group ends.

9.4 Manual stanza indent

`\stanzaindent` You can set the indent of some specific verse by calling `\stanzaindent{<value>}` at the beginning of the verse, before any other character. In this case, the indent defined by `\setstanzaindent` for this verse is skipped, and `{<value>}` is used instead.

If you use the mechanism of indent repetition, the next verse will be printed as it should be even if the current verse would have its normal indent value. In other words, using `\stanzaindent` in a verse does not shift the indent repetition.

However, if you want to shift the indent repetition, so the next verse has the indent normally used for the current verse, use `\stanzaindent*` instead of `\stanzaindent`.

9.5 Stanza breaking

`\setstanzapenalties` When the stanzas run over several pages, it is often desirable that page breaks should arise between certain lines in the stanza, so a facility for including penalties after stanza lines is provided. If you are satisfied with the page breaks, you need not set the penalty values.

The command
`\setstanzapenalties{1,5000,10100,5000,0}`
 results in a penalty of 5000 being placed after the first and third lines of the stanza, and a penalty of -100 after the second.

The first entry “1” is a control value. If it is zero, then no penalties are passed on to T_EX, which is the default. Values between 0 and 10000 are penalty values; values between 10001 and 20000 have 10000 subtracted and the result is given as a negative penalty. The mechanism used for indentations and penalties requires unsigned values less than 32768. No penalty is placed after the last line, so the final ,0 in the example above could be omitted. A penalty of 10000 will prevent a page break; such a penalty is included automatically where there is stanza hanging indentation. A penalty of -10000 (corresponding to the entry value 20000 in this context) forces a page break. Values in between act as suggestions as to the desirability of a page break at a given line. There is a subtle interaction between penalties and *glue*, so it may take some adjustment of skips and penalties to achieve the best results.

9.6 Hanging symbol

It is possible to insert a symbol in each line of hanging verse, as in French typography; for example, the opening bracket ‘[’. To insert it in `reledmac`, use macro `\sethangingsymbol{<h>}` with this code. In the example of French typography, do

```
\sethangingsymbol{[\,]}
```

You can also use it to force hanging verse to be flush right:

```
\sethangingsymbol{\protect\hfill}
```

9.7 Long verse and page break

If you want to prevent page breaks inside long verses, use the option `nopbinverse` when loading package, or use `\lednopbinversetrue`. Read 18.2 p. 75 for further details.

9.8 Content before/after verses

It is possible to add content, like a subtitle or a spacing, before or after verse:

- The `\stanza` command can take an optional argument (in brackets). Its content will be printed before the stanza. A `\noindent` is inserted before the content of first optional argument. If you don't want this `\noindent`, you can use the second optional argument (also in brackets):

```
\stanza[foo] % \noindent is inserted before foo.  
\stanza[] [foo] % There is no \noindent inserted before foo.
```

`\AtEveryStanza`

- Use `\AtEveryStanza{\langle arg\rangle}` to automatically add content before stanzas (not in the same paragraph).

Note that a `\noindent` will be inserted before the argument, and, consequently, a `\parskip`. You can use the starred version of `\AtEveryStanza` to avoid this `\noindent`.

`\AtStartEveryStanza`

- Use `\AtStartEveryStanza` to automatically add content at the beginning of stanzas (in the same paragraph).

- `\&` can be replaced by `\newverse` with two optional arguments (in brackets). The first will be printed after the current verse, the second before the next verse.

A `\noindent` is automatically inserted before the contents of these optional arguments.

Use a third and fourth optional argument to not add these `\noindents` (to add content respectively after the current verse / before the next verse).

- Use `\AtEveryPend{\langle arg\rangle}` to automatically add content after verses (including the final one) and `\AtEveryPstart{\langle arg\rangle}` to automatically add content before verses (including the first one).

- `\&` can take an optional argument (in brackets). Its content will be printed after the stanza.

\AtEveryStopStanza

- Use \AtEveryStopStanza to automatically add content after the end of stanzas (not in the same paragraph).

Note that a \noindent will be inserted before the argument, and, consequently, a \parskip. You can use the starred version of \AtEveryStopStanza to avoid this \noindent.

\BeforeEveryStopStanza

- Use \BeforeEveryStopStanza to automatically add content at the end of stanzas (in the same paragraph).

9.9 Numbering stanza

\numberstanzatrue
\numberstanzafalse

If you want to automatically number stanzas, use \numberstanzatrue. In this case, the line number will restart at each \stanza.

If you want to disable this feature again, use \numberstanzafalse.

You can use this feature in combination with \Xstanza (7.2.8 p. 46).

\thestanza

You can redefine \thestanza to change the aspect of stanza number. Default value is:

```
\renewcommand{\thestanza}{%
  \textbf{\arabic{stanza}}%
```

You can change the value of the stanza counter with the usual commands of L^AT_EX.

\stanzanumwrapper

You can redefine \stanzanumwrapper in order to modify the way the stanza number is inserted in the flow of text. Default value is:

```
\newcommand{\stanzanumwrapper}[1]{%
  \flagstanza{#1}}}
```

9.10 Various tools

\ampersand

If you need to print an & symbol in a stanza, use the \ampersand macro, not \& as this will end the stanza.

\flagstanza

Putting \flagstanza[<len>]{<text>} at the start of a line in a stanza (or elsewhere) will typeset <text> at a distance <len> before the line. The default <len> is \stanzaindentbase.

9.11 Notes on empty lines

Since v2.3.0 of reledmac, empty lines when typesetting verses no longer produce new paragraphs, and consequently, do not insert vertical spaces. Use optional argument of \stanza or \newverse to insert vertical space (9.8 p. 58).

10 Grouping

In a `minipage` environment L^AT_EX changes `\footnote` numbering from arabic to alphabetic and puts the footnotes at the end of the minipage.

`minipage`

You can put numbered text with critical footnotes in a minipage and the footnotes are set at the end of the minipage.

You can also put familiar footnotes (see section 6.5) in a minipage but unlike with `\footnote` the numbering scheme is unaltered.

`ledgroup`

Minipages, of course, are not broken across pages. Footnotes in a `ledgroup` environment are typeset at the end of the environment, as with minipages, but the environment includes normal page breaks. The environment makes no change to the `textwidth` so it appears as normal text; it just might be that footnotes appear in the middle of a page, with text above and below.

`ledgroupsized`

The `ledgroupsized` environment is similar to `ledgroup` except that you must specify a width for the environment, as with a `minipage`.

`\begin{ledgroupsized}[\langle pos \rangle]{\langle width \rangle}`.

The required `\langle width \rangle` argument is the text width for the environment. The optional `\langle pos \rangle` argument is for positioning numbered text within the normal `textwidth`. It may be one of the characters:

`l` (left) numbered text is flush left with respect to the normal `textwidth`. This is the default.

`c` (center) numbered text is in the center of the `textwidth`.

`r` (right) numbered text is flush right with respect to the normal `textwidth`.

Note that normal text, footnotes, and so forth are all flush left.

`\begin{ledgroupsized}{\textwidth}` is effectively the same as `\begin{ledgroup}`

11 Cross referencing

The package provides a simple cross-referencing facility that allows you to mark places in the text with labels, and generate page and line number references to those places elsewhere using those labels.

11.1 Basic use

`\edlabel`

First you place a label in the text using the command `\edlabel{\langle lab \rangle}`. `\langle lab \rangle` can be almost anything you like, including letters, numbers, punctuation, or a combination—anything but spaces; you might type `\edlabel{toves-3}`, for example.²¹

`\edpageref`

`\edlineref`

`\sublineref`

`\pstartref`

`\annotationref`

Elsewhere in the text, either before or after the `\edlabel`, you can refer to its location with `\edpageref{\langle lab \rangle}`, `\edlineref{\langle lab \rangle}`, `\edsublineref{\langle lab \rangle}`, `\pstartref{\langle lab \rangle}` or `\annotationref{\langle lab \rangle}`, that will produce, respectively, the page, line, sub-line, pstart, the annotation, on which the `\edlabel{\langle lab \rangle}` command occurred.

²¹More precisely, you should stick to characters in the TeX categories of “letter” and “other”.

Note that the `\edlineref` command insert the side flag after the line number.

An `\edlabel` command may appear in the main text, or in the first argument of `\edtext`, but not in the apparatus itself. But `\edpageref`, `\edlineref`, `\sublineref`, `\pstartref` commands can also be used in the apparatus to refer to `\edlabels` in the text.

The `\edlabel` command works by writing macros to `LATEX.aux` file. You will need to process your document through `LATEX` twice in order for the references to be resolved.

You will be warned if you use `\edlabel{foo}` and `foo` has been used as a label before. The `ref` commands will return references to the last place in the file marked with this label. You will also be warned if a reference is made to an undefined label. (This will also happen the first time you process a document after adding a new `\edlabel` command: the auxiliary file will not have been updated yet.)

11.2 Cross-referencing to a critical note

If you want to refer to a word which is a lemma word, the `\edlabel` command should be in the first argument of `\edtext` command.

If you want to refer to the content of a `\Xfootnote`, the line and subline number printed will be the start line.

If you want to refer to starting and ending lines, you should use `\appref` and related tools (11.6.2 p. 63).

11.3 Cross-referencing which return a number in any case

```
\xpageref
\xlineref
\xsublineref
\xpstartref
\xannotationref
```

However, there are situations in which you will want `reledmac` to return a number without displaying any warning messages about undefined labels or the like: if you want to use the reference in a context where `LATEX` is looking for a number, such a warning will lead to a complaint that the number is missing. This is the case for references used within the argument to `\linenum`, for example (see 6.2.5 p. 32).

For this situation, `reledmac` supplies variants of the reference commands, with the `x` prefix: `\xpageref`, `\xlineref`, `\xsublineref`, `\xpstartref` and `\xannotationref`. They have the following limitations:

- They will not tell you if the label is undefined.
- They must be preceded in the file by at least one of the four other cross-reference commands—e.g., a `\edlabel{foo}` command, even if you never refer to that label—since those commands can all do the necessary processing of the `.aux` file, and the `\x...` ones cannot.
- When `hyperref` is loaded, the hyperref link will not be added. (Indeed, it is not a limitation, but a feature.)
- With `reledpar`, the `\xlineref` does not insert the right side flag, in order to obtain a line number. Use `\xflagref` to obtain the side flag, depending of your flag.

11.3.1 Cross-referencing in order to define line number of a critical note

\xxref

The `\xxref{\langle lab1\rangle}{\langle lab2\rangle}` command generates a reference to a sequence of lines, for use in the second argument of `\edtext`. It takes two arguments, both of which are labels: e.g., `\xxref{mouse}{elephant}`.

It automatically calls `\linenum` (6.2.5 p. 32) and `\lineannot` (5.5.1 p. 26) and sets the beginning page, line, subline numbers and line annotations to those of the place where `\edlabel{mouse}` was placed, and the ending ones to those where `\edlabel{elephant}` occurs.

For example, one might use the following:

```
\beginnumbering

\pstart
\edlabel{Queritur}Queritur utrum metaphysica sit scientia una.
\pend

\pstart
\edtext{Et videtur quod non\edlabel{non}.}{\xxref{Queritur}{non}\lemma{queritur \dots{} non}}
\pend

\endnumbering
```

11.4 Not automatic cross-referencing

\edmakelabel

Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired—for example, if you want to refer to a page and line number in another volume of your edition. In such cases, you can use the `\edmakelabel{\langle lab\rangle}{\langle numbers\rangle}` macro so that you can ‘roll your own’ label.

For example, if you type ‘`\edmakelabel{elephant}{10|25|0}`’ you will create a new label, and a later call to `\edpageref{elephant}` would print ‘10’ and `\lineref{elephant}` would print ‘25’. The sub-line number here is zero. It is usually best to collect your `\edmakelabel` statements near the top of your document, so that you can see them at a glance.

11.5 Normal L^AT_EX cross-referencing

\label

The normal `\label`, `\ref` and `\pageref` macros may be used within numbered text, and operate in the familiar fashion.

\pageref

11.6 References to start and end lines

11.6.1 Reference to main text lines

Many times, you may want to make a cross-reference to a passage that is defined by a start line and an end line. `reledmac` provides specific tools for this scenario.

\edlabelS	Use \edlabelS{\langle label\rangle} to mark the start line of the passage.
\edlabelE	Use \edlabelE{\langle label\rangle} to mark the end the end line of the passage. These two commands just create two labels which are named \langle label\rangle :start and \langle label\rangle :end.
\edlabelSE	Use \edlabelSE{\langle label\rangle} to mark just one location in the text. Contrary to a classical \edlabel, the \langle label\rangle could be use with \SEref and \SErefwithpage.
\SEref	The main utility is to use them with three other commands. \SEref{\langle label\rangle} will make a cross-reference printed as a reference in critical footnotes.
\SErefwithpage	\SErefwithpage will make a cross-reference printed as a reference in critical endnotes.
\SErefonlypage	\SErefonlypage will make a cross-reference printed only with page number.

11.6.2 References to lines that are commented on in the apparatus

You may want to make a cross-reference to a passage that is referred to by \edtext, reledmac provides specific tools for this scenario.

\applabel	If you use \applabel{\langle label\rangle} inside the second argument of a \edtext, reledmac will add a \edlabel at the beginning and end of the marked passage. The label at the beginning of the passage will have the title \langle label\rangle :start, while the label at the end will have the title \langle label\rangle :end.
\appref	If you use \linenum (6.2.5 p. 32) to refer to these labels, reledmac will use your line settings to refer to the passage.
\apprefwithpage	You can also use \appref{\langle label\rangle} and \apprefwithpage{\langle label\rangle} to refer to these lines. The first one will print the lines as they are printed in the critical footnotes, while the second will print the lines as they are printed in endnotes.

11.6.3 Settings

\setapprefprefixsingle	Specific to these tools	If you use \setapprefprefixsingle{\langle prefix\rangle}, \langle prefix\rangle will be printed before the line numbers of a \appref-reference. If you use \setapprefprefixmore{\langle prefix\rangle}, \langle prefix\rangle will be printed before the line numbers, if you refer to more than one line.
\setapprefprefixmore		For example, you may use:

```
\setapprefprefixsingle{line~}
\setapprefprefixmore{lines~}
```

Note that if you do not use \setapprefprefixmore, the argument of \setapprefprefixsingle will be used in any case.

\setSErefprefixsingle and \setSErefprefixmore are similar for \SEref command.

Use \setSErefonlypageprefixsingle{\langle prefix\rangle} to set the page prefix for \SErefonlypage when there is only one page. Use \setSErefonlypageprefixmore{\langle prefix\rangle} to set it when there is more than one page. For example:

```
\setSErefonlypageprefixsingle{p.~}
\setSErefonlypageprefixmore{pp.~}
```

```
\setSErefprefixsingle
\setSErefprefixmore
SErefonlypageprefixsingle
SErefonlypageprefixmore
```

Note that if you do not use `\setSErefonlypageprefixmore`, the value of `\setSErefonlypageprefixsingle` is used instead.

Also note that `\setSErefonlypageprefixsingle` is only a shortcut for `\Xendbeforepagenumber` (see 11.6.3 p. 64). So if you use `\Xendbeforepagenumber` without any optional argument, it will override this setting.

Linked to setting of critical footnotes and endnotes Some commands which set the appearance of line numbers in critical footnotes also set the appearance of line numbers in `\appref` and `\SEref` if called *without the optional series argument*.

These commands are the following:

- `\Xlineflag` (for `reledpar`), enabled by default.
- `\Xlinerangeseparator`
- `\Xmorethanwolines`
- `\Xsublinesep`
- `\Xtwolines`
- `\Xtwolinesbutnotmore`
- `\Xtwolinesonlyinsamepage`
- `\Xlinenumannotationposition`
- `\Xwraplinenumannotation`
- `\Xnoidenticallinenumannotation`

If you want to make settings specific to `\appref` or `\SEref`, just call them with an optional argument containing a comma-separated list of command names (for example `appref,SEref`) or with a suffix equal to the command name (for example `appref`).

The same principle is available for `\apprefwithpage`, `\SErefwithpage` and `\SErefonlypage` with the following commands:

- `\Xendafterpagenumber` (not for `\SErefonlypage`)
- `\Xendbeforepagenumber`
- `\Xendlineflag` (for `reledpar`), enabled by default.
- `\Xendlineprefixmore`
- `\Xendlineprefixsingle`
- `\Xendlinerangeseparator`
- `\Xendmorethanwolines`
- `\Xendsublinesep`

- \Xendtwo-lines
- \Xendtwo-lines-but-not-more
- \Xendtwo-lines-only-in-same-page
- \Xendline-num-annotation-position
- \Xendwrap-line-num-annotation
- \Xendnoidentical-line-num-annotation

For one specific command When calling \appref and \SEref, you can use as a first optional argument, in brackets ([]), any optional argument which can be used for critical footnotes (6.2.2 p. 29).

When calling \appref-with-page, \SEref-with-page or \SEref-only-page you can use as a first optional argument, in brackets ([]), any optional argument which can be used for critical endnotes (6.2.3 p. 30).

11.6.4 Combining multiple references

When combining multiple cross references into a list, it is possible to prevent prefixes reappearing by adding an optional argument to \appref and \SEref. The available options are:

- *noprefix* to remove any prefix set by \setappref-prefix-single or the equivalent for a single reference;
- *prefixmore* to force the plural version of a prefix.

For example, a reference to ‘lines 65–66, 72, and 75’ might use \SEref [prefixmore]{ref1}, \SEref [noprefix]{ref2} to achieve this result.

11.7 Compatibility with *xr* package

The \externaldocument command of the \xr package allows making cross-references from an external document, with the standard L^AT_EX commands \label and \ref (and related).

To use it with the *reledmac* cross-reference commands (i.e. \edlabel and related), you must do the following:

1. Load the *xr* package.
2. Load the *reledmac* package.
3. Use the \externaldocument document command.

12 Sidenotes

12.1 Basics

The `\marginpar` command does not work in numbered text. Instead, the package provides for non-floating sidenotes in either margin.

```
\ledinnernote
\ledouternote
\ledleftnote
\ledrightnote
\ledsidenote
\sidenotemargin
```

`\ledinnernote{<text>}` will put `<text>` into the inner margin level with where the command was issued. Similarly, `\ledouternote{<text>}` puts `<text>` in the outer margin.

`\ledsidenote{<text>}` will put `<text>` into the margin specified by the current setting of `\sidenotemargin{<location>}`. The permissible value for `<location>` is one out of the list `left`, `right`, `inner`, or `outer`, for example `\sidenotemargin{outer}`. The package's default setting is

`\sidenotemargin{right}`

to typeset `\ledsidenotes` in the right hand margin. This is the opposite of the default margin for line numbers. The style for a `\ledsidenote` follows that for a `\ledleftnote` or a `\ledrightnote` depending on the margin it is put in.

If two note commands for the same side are called in the same line, they will be appended and separated by a comma.

The notes will appear only after the second L^AT_EX run. If the note positions change in your .tex file, you need two runs to get the correction position in the output file. You are strongly encouraged to use tools like *latexmk*, to be sure to get the correct number of runs.

12.2 Setting

12.2.1 Width

`\ledlsnotewidth` The left sidenote text is put into a box of width `\ledlsnotewidth` and the right text into a box of width `\ledrsnotewidth`. These are initially set to the value of `\marginparwidth`.

12.2.2 Vertical position

`\rightnoteupfalse` By default, sidenotes are placed to align with the last line of the note to which it refers.
`\leftnoteupfalse` If you want they to be placed to align with the first line of the note to which it refers, use `\leftnoteupfalse` (for left note) and/or `\rightnoteupfalse` (for right note).

12.2.3 Distance to the main text

`\ledlsnotesep` The texts are put a distance `\ledlsnotesep` (or `\ledrsnotesep`) into the left (or right) margin. These lengths are initially set to the value of `\linenumsep`.

12.2.4 Font

These macros specify how the sidenote texts are to be typeset. The initial definitions are:

```
\newcommand*{\ledlsnotefontsetup}{\raggedleft\footnotesize}%
\newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}%
```

```
\ledlsnotefontsetup
\ledrsnotefontsetup
```

```
\newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}%
\right
```

These can of course be changed to suit.

12.2.5 Separator between notes

`\setsidenotessep` If you have two or more sidenotes for the same line, they are separated by a comma. But if you want to change this separator, you can use `\setsidenotessep{<sep>}`.

13 Indexing

13.1 Basics

`\edindex` L^AT_EX provides the `\index{<item>}` command for specifying that `<item>` and the current page number should be added to the raw index (`.idx`) file. The `\edindex{<item>}` macro can be used in numbered text to specify that `<item>` and the current page & linenumber should be added to the raw index file.

Note that the file `.idx` will contain the right reference only after the third run, because of the internal indexing mechanism of `reledmac`. That means you must first run (Xe/Lua)L^AT_EX three times, then run `makeindex`, and then finally run (Xe/Lua)L^AT_EX again, in order to get an index with the right page numbers.

Also note that using `\edtext` in familiar footnotes refers to the line where the footnotes are called

13.2 Use with `imakeidx` or `indextools`

If the `imakeidx` or `indextools` package is used then the macro takes an optional argument, which is the name of a raw index file. For example `\edindex[line]{item}` will use `line.idx` as the raw file instead of `\jobname.idx`.

The minimal version of `imakeidx` package to be used is the version 1.3a uploaded on CTAN on 2013/07/11.

Be careful with the order of package loading and index declaration. You must use this order:

1. Load `imakeidx` or `indextools`.
2. Load `reledmac`.
3. Declare the index with the macro `\makeindex` of `imakeidx` and `indextools`.

13.3 Referring to critical notes

If you want to refer to a word inside an `\edtext{<lemma>}{<app>}` command, `\edindex` should be defined inside the first argument, e.g.,

```
The \edtext{creature\edindex{elephant}} was quite
unafraid}{\Afootnote{Of the mouse, that is.}}
```

If you add `\edindex` inside some `\Xfootnote` command, it will refer to that note, and a suffix *n* will be appended to the reference. You can redefine this suffix by redefining the command `\ledinnotemark`. Its actual definition is:

```
\newcommand{\ledinnotemark}[1]{\#1\emph{n}}
```

Where #1 stands for the reference.

13.4 Separator between page and line numbers

`\pagelinesep`

The page & linenumber combination is written as `page\pagelinesep line`, where the default definition is `\newcommand{\pagelinesep}{-}` so that an item on page 3, line 5 will be noted as being at 3-5. You can renew `\pagelinesep` to get a different separator.

- is the default separator used by the `MAKEINDEX` program.

You can reconfigure it, this example defines a colon as separator:

```
\renewcommand{\pagelinesep}{:}
```

However, you also have to configure your `.ist` index style file. For example, if you use : as separator²².

```
page_compositor ":"
```

Read the `MAKEINDEX` program's handbook about the `.ist` file.

13.5 Using xindy

Should you decide to use `xindy` instead of `makeindex` to transform your `.idx` files into `.ind` files, you must use some specific configuration file (`.xdy`) so that `xindy` can understand `eledmac` reference syntax of which the scheme is:
`pagenumber-linenumber`

An example of such a file is provided in the “examples” folder. Read the `xindy` handbook to learn how to use it.²³

This file also provides, with an explanation, the settings that are needed to put `reledmac` lines numbers in parenthesis, in order to make a better distinction between line numbers and page ranges.

In any case, you must load `reledmac` with the `xindy` option, in order to generate a `.xdy` file which is specific to your document. This file is needed by the `.xdy` example file which is in the “examples” folder. Its default name is `reledmac-markup-attr.xdy`, but you can change it by using your own as an argument of the `xindy+hyperref` option.

If you choose to use both `xindy` and the `hyperref` package, you must do three more things:

²²For further detail, you can read <http://tex.stackexchange.com/a/32783/7712>.

²³Or, for people who read French, read <http://geekographie.maieul.net/174>.

1. Use `xindy+hyperref` option when loading the `reledmac` package. When you run (Xe/Lua)TeX with this option, a `.xdy` configuration file will be generated with all the settings needed to allow internal hyperlinking in each index entry which is created by `\edindex`.
2. Use `hyperindex=false` option when loading `hyperref`.
3. Uncomment – by removing the semicolons at the beginning of the relevant lines – some lines in the `<code>.xdy</code>` file provided in the “examples” folder in order to restore internal links in the index to be used by the standard `index` command.²⁴.

13.6 Advanced setting

`\edindexlab` The `\edindex` process uses a `\label` and `\ref` mechanism to get the correct line number. It automatically generates labels of the form `\label{\edindexlab N}`, where `N` is a number, and the default definition of `\edindexlab` is:
`\newcommand*\{\edindexlab\}{\$&}`
in the hopes that this will not be used by any other labels (`\edindex`’s labels are like `\label{\$&27}`). You can change `\edindexlab` to something else if you need to.

14 Glossary

`reledmac` provides mechanism to make glossaries with the `glossaries` package, referring not to the page, but to the page and line.

14.1 Preamble setting

The standard compositor between page and line number in `reledmac` is a dash, while `glossaries` uses, by default, a dot. Consequently, you must:

- Or set `.glossaries`:
`\glsSetCompositor{-}`
- Or set `reledmac`:
`\renewcommand{\pagelinesep}{-}`
In this case, the above will have consequences for your use of `\edindex` and you should set your `.ist` file (13.4 p. 68).

14.2 Commands

The `\gls`, `\Gls`, and related commands of `glossaries` packages have a prefixed version with `ed`, which refers to the page line. The argument are the same as for the standard commands. So for example:

`\edgls[<options>]{<label>}[<insert>]`

²⁴These are the recommended lines to provide the best possible compatibility between `hyperref` and `xindy`, even without using `reledmac`.

15 Tabular material

\TeX 's normal `tabular` and `array` environments cannot be used where line numbering is being done; more precisely, they can be used but with odd results, so don't use them. However, `reledmac` provides some simple tabulation environments that can be line numbered. The environments can also be used in normal unnumbered text.

`edarrayl`
`edarrayc`
`edarrayr`
`edtabularl`
`edtabularc`
`edtabularr`

There are six environments; the `edarray*` environments are for math and `edtabular*` for text entries. The final `l`, `c`, or `r` in the environment names indicate that the entries will be flushleft (`l`), centered (`c`) or flushright (`r`). There is no means of specifying different formats for each column, nor for specifying a fixed width for a column. The environments are centered with respect to the surrounding text.

```
\begin{edtabularc}
1 & 2 & 3 \\
a & bb & ccc \\
AAA & BB & C
\end{edtabularc}
```

1	2	3
a	bb	ccc
AAA	BB	C

Entries in the environments are the same as for the normal `array` and `tabular` environments but there must be no ending `\\"` at the end of the last row. *There must be the same number of column designators (the &) in each row.* There is no equivalent to any line drawing commands (such as `\hline`). However, unlike the normal environments, the `ed...` environments can cross page breaks.

Macros like `\edtext` can be used as part of an entry.

For example:

```
\begin{numbering}
\pstart
\begin{edtabularl}
\textbf{\Large I} & wish I was a little bug\edindex{bug} &
\textbf{\Large I} & eat my peas with honey\edindex{honey} \\
& With whiskers \edtext{round}{\footnote{around}} my tummy &
& I've done it all my life. \\
& I'd climb into a honey\edindex{honey} pot &
& It makes the peas taste funny \\
& And get my tummy gummy.\edindex{gummy} &
& But it keeps them on the knife.
\end{edtabularl}
\pend
\end{numbering}
```

produces the following parallel pair of verses.

1	I wish I was a little bug	I eat my peas with honey
2	With whiskers round my tummy	I've done it all my life.
3	I'd climb into a honey pot	It makes the peas taste funny
4	And get my tummy gummy.	But it keeps them on the knife.

`\edtabcolsep` The distance between the columns is controlled by the length `\edtabcolsep`.

```
\spreadmath \spreadmath{ $\langle math \rangle$ } typesets { $\langle math \rangle$ } but the { $\langle math \rangle$ } has no effect on the
\spreadtext \spreadtext{ $\langle text \rangle$ } is the analogous command for use
in edtabular environments.
\begin{edarrayl}
1 & 2 & 3 & 4 \\
& \spreadmath{F+G+C} & & \\
a & bb & ccc & dddd
\end{edarrayl}
```

1	2	3	4
$F + G + C$			
a	bb	ccc	ddd

\edrowfill The macro $\edrowfill{\langle start \rangle}{\langle end \rangle}{\langle fill \rangle}$ fills columns number $\langle start \rangle$ to $\langle end \rangle$ inclusive with $\langle fill \rangle$. The $\langle fill \rangle$ argument can be any horizontal ‘fill’. For example, \hrulefill or \upbracefill .

Note that every row must have the same number of columns, even if some would not appear to be necessary.

The \edrowfill macro can be used in both tabular and array environments. The typeset appearance of the following code is shown below.

```
\begin{edtabularr}
1 & 2 & 3 & 4 & 5 \\
Q & & fd & h & qwertziohg \\
v & wptz & x & y & vb \\
g & nnn & \edrowfill{1}{3}{\downbracefill} & \upbracefill{5}{\edrowfill{3}{5}{\upbracefill}} & \\
\edrowfill{1}{3}{\downbracefill} & & & & \\
k & & 1 & co & ghweropjklmnbcxys \\
1 & 2 & 3 & \edrowfill{4}{5}{\hrulefill} &
\end{edtabularr}
```

1	2	3	4	5
Q		fd	h	qwertziohg
v	wptz	x	y	vb
g	nnn	$\overbrace{\hspace{1cm}}$		
k		1	pq	dgh
1	2	3	$\overbrace{\hspace{1cm}}$	

You can also define your own ‘fill’. For example:

```
\newcommand*{\upbracketfill}{%
\vrule height 4pt depth 0pt\hrulefill\vrule height 4pt depth 0pt}
```

is a fill like \upbracefill except it has the appearance of a (horizontal) bracket instead of a brace. It can be used like this:

```
\begin{edarrayc}
1 & 2 & 3 & 4 \\
a & \edrowfill{2}{3}{\upbracketfill} & & \\
A & B & & C & D
\end{edarrayc}
```

$$\begin{array}{cccc} 1 & 2 & 3 & 4 \\ a & \sqcap & & d \\ A & B & C & D \end{array}$$

`\edatleft` `\edatleft[<math>]{<symbol>}{<halfheight>}` typesets the math `<symbol>` as `\left{<symbol>` with the optional `<math>` centered before it. The `<symbol>` is twice `<halfheight>` tall. The `\edatright` macro is similar and it typesets `\right{<symbol>}` with `<math>` centered after it.

```
\begin{edarrayc}
& 1 & 2 & 3 & \\
& 4 & 5 & 6 & \\
\edatleft[left =]{\{}{1.5\baselineskip}
& 7 & 8 & 9 & \\
\edatright[= right\}]{\} }{1.5\baselineskip}
\end{edarrayc}
```

$$left = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} = right$$

`\edbeforetab` `\edbeforetab{<text>}{<entry>}`, where `<entry>` is an entry in the leftmost column, typesets `<text>` left justified before the `<entry>`. Similarly `\edaftertab{<entry>}{<text>}`, where `<entry>` is an entry in the rightmost column, typesets `<text>` right justified after the `<entry>`.

For example:

```
\begin{edarrayl}
A & 1 & 2 & 3 \\
\edbeforetab{Before}{B} & 1 & 3 & 6 \\
C & 1 & 4 & \edaftertab{8}{After} \\
D & 1 & 5 & 0
\end{edarrayl}
```

Before	$A \quad 1 \quad 2 \quad 3$ $B \quad 1 \quad 3 \quad 6$ $C \quad 1 \quad 4 \quad 8$ $D \quad 1 \quad 5 \quad 0$	After
--------	--	-------

`\edvertline` The macro `\edvertline{<height>}` draws a vertical line `<height>` high (contrast this with `\edatright` where the size argument is half the desired height).

```
\begin{edarrayr}
a & b & C & d & \\
v & w & x & y &
\end{edarrayr}
```

```
m & n & o & p   & \\
k &   & L & cvb & \edvertline{4pc}
\end{edarrayr}
```

<i>a</i>	<i>b</i>	<i>C</i>	<i>d</i>
<i>v</i>	<i>w</i>	<i>x</i>	<i>y</i>
<i>m</i>	<i>n</i>	<i>o</i>	<i>p</i>
<i>k</i>		<i>L</i>	<i>cvb</i>

The `\edvertdots` macro is similar to `\edvertline` except that it produces a vertical dotted instead of a solid line.

16 Sectioning commands

16.1 Sectioning commands without line numbers or critical notes

The standard sectioning commands (`\chapter`, `\section` etc.) can be used inside numbered text. In this case, you must call them as an optional argument of `\pstart` (5.2.3 p. 19):

```
\pstart[\section{section}]
Pstart content.
\pend
```

The line which contains them will not be numbered, and you cannot add critical notes inside.

16.2 Sectioning commands with line numbering and critical notes

You have to use the following commands:

- `\eledchapter[<text>]{<critical text>},`
- `\eledchapter*,`
- `\eledsection[<text>]{<critical text>},`
- `\eledsection*,`
- `\eledsubsection[<text>]{<critical text>},`
- `\eledsubsection*,`
- `\eledsubsubsection[<text>]{<critical text>},`
- `\eledsubsubsection*.`

These are equivalent to the L^AT_EX commands. Each individual command must be called alone in a `\pstart ... \pend`:

```
\pstart
\eledsection*{xxxx\ledsidenote{section}}
\pend
\pstart
\eledsubsection*{xxxx\ledsidenote{sub}}
\pend
\pstart
normal text
\pend
```

After the first run, you will see only the text. This is normal. After the second run, you will see the formatting. Finally, with the third run, you will see the table of contents.

For technical reasons, the page break before `\elechapter` cannot be added automatically. You have to insert it manually via `\beforeeledchapter`, which must be called outside of a numbered section.

16.3 Optimization

`\noeledsec` If you are not going to have any `\eledxxx` commands, then load `reledmac` with `\noeledsec` option. That will suppress the generation of unneeded `.eledsec` files, save memory, and make `reledmac` run faster.

17 Quotation environments

The quotation and quote environments can be used so that the same definition/note appears both inside and outside a numbered section. The typographical consequences will resemble the outside numbered sections, based on the styles of the *book* class. However, if you use a package that redefines these environments, these redefinitions won't be available inside the numbered section. You must open any quotation environments inside a `\pstart ... \pend` block, not outside. A quotation environment MUST NOT be opened immediately after a `\pstart` and MUST NOT be closed immediately before a `\pend`.

In some cases, you do not want these environments to be redefined in numbered sections. You can load the package with the option `noquotation` to prevent this redefinition.

18 Page breaks

18.1 Control page breaking

`reledmac` and `reledpar` break pages automatically. However, you may sometimes want to either force page breaks, or prevent them. The packages provide two macros:

```
\ledpb
\lednbp
```

- \ledpb adds a page break.
- \lednomp prevents a page break, by adding one line to the current page if needed.

These commands have effect only at the second run.

These two commands take effect at the beginning of line in which they are called. For example, if you call \ledpb at l. 444, then l. 443 will be at p. n , and l. 444 at p. $n + 1$. However, you can change the behavior and decide they will have effect after the end of the line, adding \ledpbsetting{after} at the beginning of your file (better: in your preamble). With the previous example, l. 444 will be on p. n and l. 445 will be on p. $n + 1$.

If you are using reledpar to typeset parallel pages, you must use \lednomp on both sides in the two corresponding lines. This is especially important when you are using stanzas; otherwise, the pages will be out of sync.

18.2 Prevent page break in a long verses

\lednompinversetrue

You can also decide to prevent page breaks between two lines of a long verse. To do this, use nopbinverse when loading package, or add \lednompinversetrue in the beginning of your file (better: in your preamble).

This feature works only with verse of 2 lines and no more. It works on the third run, or on the fourth run if using reledpar. By default, when a long verse runs between two pages, a page break will be placed at the beginning of the verse. However, if you have added \ledpbsetting{after}, the page break will be placed at the end of the long verse and the page containing the long verse will have one extra line.

19 Miscellaneous

\extensionchars

When the package assembles the name of the auxiliary file for a section, it prefixes \extensionchars to the section number. This is initially defined to be empty, but you can add some characters to help distinguish these files if you like; what you use is likely to be system-dependent. If, for example, you said \renewcommand{\extensionchars}{!}, then you would get temporary files called jobname . !1, jobname . !2, etc.

\ifledfinal

The package can take options. The option ‘final’, which is the default is for final typesetting; this sets \ifledfinal to TRUE. The other option, ‘draft’, may be useful during earlier stages and sets \ifledfinal to FALSE.

\showlemma

The lemma within the text is printed via \showlemma{lemma}. Normally, or with the ‘final’ option, the definition of \showlemma is:

```
\newcommand*{\showlemma}[1]{#1}
```

so it just produces its argument. With the ‘draft’ option it is defined as

```
\newcommand*{\showlemma}[1]{\textit{#1}}
```

so that its argument is typeset in an italic font, which may make it easier to check that all lemmas have been treated.

If you would prefer some other style, you could put something like this in the preamble:

```
\ifledfinal \else
```

```
\renewcommand{\showlemma}[1]{\textbf{#1}}% or simply ...[1]{#1}
\fi
```

19.1 Known and suspected limitations

19.1.1 Non-standard geometry

If you use classes other than `article` or `book`, or if you use the `geometry` package, you should use `maxhnotesX` and/or `\Xmaxhnotes` as explained in 7.12.6 p. 54 in order to prevent footnotes from overlapping the bottom margin.

19.1.2 floatrow package compatibility

The `floatrow` package must be loaded before the `reledmac`.

19.1.3 ‘No room for a new’

Sometimes, especially when using `reledmac` with other packages, you could obtain warning messages such ‘no room for a new count’ or ‘no room for a new write’.

In order to prevent such problems, the first thing is to use the options to optimize `reledmac`. For example, if you need only two series of notes, use the `series={A,B}` option. Read 16.3 p. 74 in order to know which are the available options.

However, if with these options you still have such messages, here are some tricks.

‘no room for a new count’ is often caused by `biblatex` being used at the same time.
Load `reledmac` (and `reledpar`) *before* `biblatex`.

‘no room for a new write’ can be caused by multiple indexes. In this case, use `indextools` of `imakeidx` with the `splitindex` option, in order to obtain only one `.idx` file. If that does not solve your problem, you can use `morewrites` package. That should solve the problem, but `LATEX` will be slower.

If after reading and applying these advices you have still problem, contact us with a minimal working example.

19.1.4 Marginal notes

In general, `reledmac`’s system for adding marginal line numbers breaks anything that makes direct use of the `LATEX` insert system, which includes `marginpars`, `footnotes` and `floats`.

However, you can use both `\footnote` and the familiar footnote series notes in numbered text. A `\marginpar` in numbered text will throw away its contents and send a warning message to the terminal and log file, but will do no harm.

19.1.5 Paragraph shape

\parshape cannot be used within numbered text, except in a very restricted way.

\ballast L^AT_EX is a three-pass system, but even after a document has been processed three times, there are some tricky situations in which the page breaks decided by T_EX never settle down. At each successive run, reledmac may oscillate between two different sets of page decisions. To stop this happening, should it arise, Wayne Sullivan suggested the inclusion of the quantity \ballast. The amount of \ballast will be subtracted from the penalties which apply to the page breaks calculated on the *previous* run through T_EX, thus reinforcing these breaks. So if you find your page breaks oscillating, insert
\setcounter{ballast}{100}
or some such figure, and with any luck the page breaks will settle down. Luckily, this problem does not crop up at all often.

19.1.6 Paragraphed footnotes

The restriction on explicit line-breaking in paragraphed footnotes, mentioned on 7.1 p. 43, and described in more detail on XIII.6.3 p. 193, really is a nuisance if that is something you need to do. There are some possible solutions, described by Michael Downes, but this area remains unsatisfactory.

If you use more than one series of paragraphed notes, it may happen, in some particular cases, that only the footnote rule, with no accompanying footnotes, be printed. In this case use reledmac package option nopenalties which should solve the problem, but also may produce widow or orphan lines. For the time being, we have no solution of this problem.

\footfudgefiddle For paragraphed footnotes T_EX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. \footfudgefiddle can be increased from its default 64 (say, to 68) to increase the estimate. You have to use \renewcommand for this, like:

\renewcommand{\footfudgefiddle}{68}

Note that you must call it *before* \Xarrangement{paragraph} or \arrangementX{paragraph}.

Any settings to ‘geometry’ must be made before \Xarrangement / \arrangementX.

Finally, in many cases you should use \Xmaxhnotes and / or \maxhnotesX (7.12.6 p. 54), in order to define the maximum height relative to \textheight and not to \vsize, because the \vsize value is not the same inside and outside of the preamble.

19.1.7 Use with other packages

Because of reledmac’s complexity, it may not play well with other packages. In particular reledmac is sensitive to commands in the arguments to the \edtext and *footnote macros (this is discussed in more detail in section VI, and in particular the discussion about \no@expands and \morenoexpands). You will have to see what works or doesn’t work in your particular case.

\morenoexpands You can define the macro \morenoexpands to modify macros that you call within \edtext. Because of the way reledmac numbers the lines the arguments to \edtext can be processed more than once and in some cases a macro should only be processed

once. One example is the `\colorbox` macro from the `color` package, which you might use like this:

```
... \edtext{\colorbox{mycolor}{lemma}}{\Afootnote{... \colorbox{...}}}
```

If you actually try this²⁵ you will find L^AT_EX whining ‘Missing { inserted’, and then things start to fall apart. The trick in this case is to specify either:

```
\newcommand{\morenoexpands}{\let\colorbox=0}
```

or

```
\makeatletter
\newcommand{\morenoexpands}{\let\colorbox\@secondoftwo}
\makeatother
```

(`\@secondoftwo` is an internal L^AT_EX macro that takes two arguments and throws away the first one.) The first incantation lets color show in both the main text and footnotes whereas the second one shows color in the main text but kills it in the lemma and footnotes. On the other hand if you use `\textcolor` instead, like

```
... \edtext{\textcolor{mycolor}{lemma}}{\Afootnote{... \textcolor{...}}}
```

there is no need to fiddle with `\morenoexpands` as the color will naturally be displayed in both the text and footnotes. To kill the color in the lemma and footnotes, though, you can do:

```
\makeatletter
\newcommand{\morenoexpands}{\let\textcolor\@secondoftwo}
\makeatother
```

It took Peter Wilson a little while to discover all this. If you run into this sort of problem you may have to spend some time experimenting before hitting on a solution.

If you want to use the option *bottom* of the `footmisc` package, you must load this package *before* the `reledmac` package.

19.2 Parallel typesetting

Peter Wilson has developed the `ledpar` package as an extension to `ledmac` specifically for parallel typesetting of critical texts. This also cooperates with the `babel` / `polyglossia` packages for typesetting in multiple languages. `reledpar` is the successor of the primitive `ledpar` package.

Peter Wilson also developed the `ledarab` package for handling parallel Arabic text in critical editions. However, this package is not maintained by Maïeul Rouquette. You should use the capabilities of a modern TeX processor, like Xe(La)TeX

²⁵Reported by Dirk-Jan Dekker in the CTT thread ‘Incompatibility of “color” package’ on 2003/08/28.

I Implementation overview

We present the `reledmac` code in roughly the order in which it is used during a run of `TEX`. The order is *exactly* that in which it is read when you load the `reledmac` package, because the same file is used to generate this manual and to generate the `LATEX` package file.

Most of what follows consists of macro definitions, but there are some commands that are executed immediately—especially at the start of the code. The documentation generally describes the code from the point of view of what happens when the macros are executed, though. As each macro is introduced, its name is printed in the margin.

After package options, we begin with the commands you use to start and stop line numbering in a section of text (Section II). Next comes the machinery for writing and reading the auxiliary file for each section that helps us count lines, and for creating list macros encoding the information from that file (Section V); this auxiliary file will be read at the start of each section, to create those list macros, and a new version of the file will be started to collect information from the body of the section.

Next are commands for marking sections of the text for footnotes (Section VI), followed by the macros that take each paragraph apart, attach the line numbers and insertions, and send the result to the vertical list (Section VII). The footnote commands (Section XIII) and output routine (Section XXIII) finish the main part of the processing; cross-referencing (Section XXV) and endnotes (Section XX) complete the story.

In what follows, macros with an @ in their name are more internal to the workings of `reledmac` than those made up just of ordinary letters, just as in PLAIN `TEX` (see *The TeXbook*, p. 344). You are meant to be able to make free with ordinary macros, but the '@' ones should be treated with more respect, and changed only if you are pretty sure of what you are doing.

II Preliminaries

II.1 Links with original `edmac`

Generally, these are the modifications to the original `edmac` code:

- Replace as many `\def`'s by `\newcommand`'s as possible to avoid overwriting `LATEX` macros.
- Replace user-level `TEX` counts by `LATEX` counters.
- Use the `LATEX` font handling mechanisms.
- Use `LATEX` messaging and file facilities.

II.2 Package declaration

Announce the name and version of the package, which is targetted for `LaTeX2e`.

```

1  %<*code>
2  \NeedsTeXFormat{LaTeX2e}
3  \ProvidesPackage{reledmac}[2019/04/03 v2.31.2 typesetting critical editions
4  ]%

```

II.3 Package options

Use this to remember which option is used, set and execute the options with final as the default. We use `xkeyval` in order to manage options with argument.

```

\ifparledgroup
\ifsameparallelpagenumber
\ifprevpgnotnumbered
  \ifledfinal
  \ifnocritical@
  \ife@noeled@sec
    \ifnoend@
  \ifnofamiliar@
  \ifnoledgroup@
\ifparapparatus@
\ifnoquotation@
\iflednopbinverse
\ifwidthliketwocolumns
  \ifxindy@
\ifxindyhyperref@
\ifeledmaccompat@
\ifnoresetlinenumannotation@

```

II.3.1 Options of `reledpar`

Here, we define some booleans specific to `reledpar` options, but which have consequences on `reledmac` internal commands.

```

11 \DeclareOptionX{series}[A,B,C,D,E]{\xdef\default@series{\#1}}
12 \ExecuteOptionsX{series}%
13 
14 \newif\if@noeled@sec%
15 \DeclareOptionX{noeledsec}{\@noeled@sectrue}%
16 
17 \newif\ifnocritical@
18 \DeclareOptionX{nocrical}{\nocritical@true}%
19 
20 \newif\ifnofamiliar@
21 \DeclareOptionX{nofamiliar}{\nofamiliar@true}%
22 
23 \newif\ifnoledgroup@
24 \DeclareOptionX{noledgroup}{\noledgroup@true}%
25 
26 \newif\ifnoend@
27 \DeclareOptionX{noend}{%
28   \let\l@dend@open\@gobble%
29   \let\l@dend@close\relax%
30   \global\let\l@dend@stuff=\relax%
31   \noend@true%
32 }%

```

```

33
34 \newif\ifnoquotation@
35 \DeclareOptionX{noquotation}{\noquotation@true}
36
37 \newif\ifledfinal
38 \DeclareOptionX{final}{\ledfinaltrue}
39 \DeclareOptionX{draft}{\ledfinalfalse}
40 \ExecuteOptionsX{final}
41
42 \newif\ifparapparatus@
43 \DeclareOptionX{parapparatus}{\parapparatus@true}
44
45 \newif\iflednopbinverse
46 \DeclareOptionX{nopbinverse}{\lednopbinversetrue}
47
48 \newif\ifwidthliketwocolumns%
49 \DeclareOptionX{widthliketwocolumns}{\widthliketwocolumnstrue}%
50
51 \newif\ifcontinuousnumberingwithcolumns
52 \DeclareOptionX{continuousnumberingwithcolumns}{\continuousnumberingwithcolumnstrue}%
53
54 \newif\ifxindy@
55 \DeclareOptionX{xindy}[eledmac-markup-attr.xdy]{%
56   \AtBeginDocument{\immediate\openout\eledmac@xindy@out=\#1}%
57   \newwrite\eledmac@xindy@out%
58   \xindy@true%
59   \gdef\eledmacmarkuprefdepth{:depth 1}%
60   \AtEndDocument{\immediate\closeout\eledmac@xindy@out}%
61 }%
62
63 \newif\ifxindyhyperref@
64 \DeclareOptionX{xindy+hyperref}{%
65   \xindyhyperref@true%
66 }%
67
68 \newif\ifeledmaccompat@
69 \DeclareOptionX{eledmac-compat}{%
70   \eledmaccompat@true%
71 }%
72 \DeclareOptionX{nopenalties}{%
73   \AtBeginDocument{\let\add@penalties\relax}%
74 }
75 \def\l@auxdir{}%
76 \DeclareOptionX{auxdir}{%
77   \xdef\l@auxdir{\#1}%
78 }%
79
80 \newif\ifsw@caseinsensitive%
81 \DeclareOptionX{swcaseinsensitive}{%

```

```

82   \sw@caseinsensitivetrue%
83 }%
84 \newif\ifnoresetlinenumannotation@
85 \DeclareOptionX[noresetlinenumannotation]{%
86   \noresetlinenumannotation@true%
87 }%
88 %

```

We use the starred form of `\ProcessOptionsX` which executes options in the order listed in the source file: class options, then listed package options, so a package option can override a class option with the same name. This was suggested by Dan Luecking in the ctt thread *Class/package option processing*, on 27 February 2004.

```

89 \ProcessOptionsX*\relax
90 %
91 %

```

II.4 Loading packages

Loading package `xargs` to declare commands with optional arguments. Loading package `xparse` to declare fully expandable commands with optional argument. Ideally, we should use only `xparse` and not `xargs`. For historical reasons, we use both. `Etoolbox` is also used to make code clearer - for example, in dynamic command names (which can replace `\csname` etc.). Use `suffix` to declare commands with a starred version, `xstring` to work with strings, `ifluatex` and `ifxetex` to test if `LuaTeX` or `XETEX` is running, and `ragged2e` to manage ragged justification for paragraphed notes.

```

92 \RequirePackage{xargs}
93 \RequirePackage{xparse}[2017/03/07]%
94 \RequirePackage{etoolbox}
95 \@ifl@t@r\fmtversion{2015/10/01}
96 { \ifboolexpr{not test{\@ifl@t@r\fmtversion{2016/03/31}} or (test{\%
97 ifdefstring{\fmtversion}{2016/03/31}} and test {\ifnumless{\patch@level
98 }{3}})}\%
99   {\PackageWarning{reledmac}{You are using a LaTeX version older than
100  2016/03/31 patch 3.}%
101   \MessageBreak You are strongly encouraged to use a newer version.}\}%
102   {}%
103 }%
104 \RequirePackage{suffix}
105 \RequirePackage{xstring}
106 \RequirePackage{ifluatex}
107 \RequirePackage{ragged2e}
108 \RequirePackage{ifxetex}%
109 %

```

II.5 Compatibility with *LuaTeX*

Here, we enable some primitives for *LuaTeX*.

```

110 \ifx\directlua\undefined\else%
111   \directlua{tex.enableprimitives("", {"textdir", "pardir", "bodydir"})}
112 \fi
113 %

```

II.6 Boolean flags

`\ifl@dmemoir` Define a flag for if the `memoir` class has been used.

```

114 \newif\ifl@dmemoir
115 \@ifclassloaded{memoir}{\l@dmemoirtrue}{\l@dmemoirfalse}
116 %
117 %

```

`\if@ledgroup` Flag set to true inside a `ledgroup` environment.

```

118 \newif\if@ledgroup%
119 %

```

`\ifl@imakeidx` Define a flag for if the `imakeidx` package has been used.

```

120 \newif\ifl@imakeidx
121 \@ifpackageloaded{imakeidx}{\l@imakeidxtrue}{%False is the default value
122 %

```

`\ifl@indextools` Define a flag for if the `indextools` package has been used.

```

123 \newif\ifl@indextools%
124 \@ifpackageloaded{indextools}{%
125   \l@indextoolstrue%
126   \l@imakeidxtrue%
127   \let\imki@wrindexentry\indtl@wrindexentry%
128 }{%
129 %

```

False is the default value. We consider `indextools` as a variant of `imakeidx`. That is why we set `\ifl@imakeidx` to true. We also let `\imki@wrindexentry` to `\indtl@wrindexentry`.

`\ifl@footmisc` Define a flag if the `footmisc` package has been loaded.

```

130 \newif\ifl@footmisc
131 \@ifpackageloaded{footmisc}{\l@footmisctrue}{%False is the default value
132 %

```

`\if@RTL` The `\if@RTL` is defined by the `bidi` package, which is sometimes loaded by *polyglossia*. But we define it as well if the `bidi` package is not loaded.

```

133 \ifdef{\if@RTL}{}{\newif\if@RTL}
134 %

```

\if@firstlineofpage *\if@firstlineofpage* is set to TRUE at the first line of every page. *\if@firstlineofpageR* is for the right side.

```

135 \newif\if@firstlineofpage%
136 \newif\if@firstlineofpageR%
137 %

```

II.7 Messages

All the messages are grouped here as macros. This saves TEX's memory when the same message is repeated and also lets them be edited easily.

\reledmac@warning Write a warning message.

```

138 \newcommand{\reledmac@warning}[1]{\PackageWarning{reledmac}{#1}}
139 %

```

\reledmac@error Write an error message.

```

140 \newcommand{\reledmac@error}[2]{\PackageError{reledmac}{#1}{#2}}
141 %

```

```

\led@err@NumberingStarted42 \newcommand*{\led@err@NumberingStarted}{%
\led@err@NumberingNotStarted43   \reledmac@error{Numbering has already been started}{\@ehc}}
\led@err@NumberingShouldHaveStarted44 \newcommand*{\led@err@NumberingNotStarted}{%
45   \reledmac@error{Numbering was not started}{\@ehc}}
46 \newcommand*{\led@err@NumberingShouldHaveStarted}{%
47   \reledmac@error{Numbering should already have been started}{\@ehc}}
48 %

```

```

\led@err@edtextoutsidepstart49 \newcommand*{\led@err@edtextoutsidepstart}{%
\led@err@PstartInEdtext50   \reledmac@error{\string\edtext\space outside numbered paragraph (\pstart\%
\led@err@PendInEdtext   space ... \space\pend)}{\@ehc}}%
51
52 \newcommand{\led@err@PstartInEdtext}[1]{%
53   \reledmac@error{\string\pstart\space in \string\edtext\space #1 argument
54 }{\@ehc}}%
55
56 \newcommand{\led@err@PendInEdtext}[1]{%
57   \reledmac@error{\string\pend\space in \string\edtext\space #1 argument}{\%
58 }%
59 %

```

```

\led@mess@NotesChanged60 \newcommand*{\led@mess@NotesChanged}{%
  161   \typeout{reledmac reminder: }%
  162   \typeout{ The number of the footnotes in this section}
  163   has changed since the last run.}%
  164   \typeout{ You will need to run LaTeX two more times}
  165   before the footnote placement}%
  166   \typeout{ and line numbering in this section are}
  167   correct.}%
  168 %

led@mess@SectionContinued69 \newcommand*{\led@mess@SectionContinued}[1]{%
  170   \message{Section #1 (continuing the previous section)}}
  171 %

d@err@LineationInNumbered72 \newcommand*{\led@err@LineationInNumbered}{%
  173   \reledmac@error{You can't use \string\lineation\space within}
  174   a numbered section}\{@ehc}%
  175 %

\led@warn@BadLineation76 \newcommand*{\led@warn@BadLineation}{%
  176 @BadLineation\space argument}}
\led@warn@BadLinenummargin77 \reledmac@warning{Bad \string\linenummargin}
\led@warn@BadLockdisp78 \newcommand*{\led@warn@BadLockdisp}{%
  177   \reledmac@warning{Bad \string\lockdisp\space argument}}
\led@warn@BadSublockdisp79 \newcommand*{\led@warn@BadSublockdisp}{%
  178   \reledmac@warning{Bad \string\sublockdisp\space argument}}
  179   \reledmac@warning{Bad \string\lockdisp\space argument}}
  180   \reledmac@warning{Bad \string\sublockdisp\space argument}}
  181   \reledmac@warning{Bad \string\lockdisp\space argument}}
  182   \reledmac@warning{Bad \string\sublockdisp\space argument}}
  183   \reledmac@warning{Bad \string\lockdisp\space argument}}
  184 %

\led@warn@NoFile85 \newcommand*{\led@warn@NoFile}[1]{%
  185   \reledmac@warning{File '#1' not found}}
  186 %
  187 %

led@warn@LineFileObsolete88 \newcommand*{\led@warn@Obsolete}[1]{%
  188   \reledmac@warning{Line-list file #1 was obsolete. We have not read it.
  189   Please run LaTeX again.}}
  190 %

\arn@BadAdvancelineSubline91 \newcommand*{\arn@BadAdvancelineSubline}{%
  191   \reledmac@warning{\string\advanceline\space produced a sub-line
  192   number less than zero.}}
\arn@BadAdvancelineLine92 \newcommand*{\arn@BadAdvancelineLine}{%
  193   \reledmac@warning{\string\advanceline\space produced a line
  194   number less than zero.}}
  195   \reledmac@warning{\string\advanceline\space produced a line
  196   number less than zero.}%
  197 %

```

```

\led@warn@BadSetline98 \newcommand*{\led@warn@BadSetline}{%
\led@warn@BadSetlinenum99   \reledmac@warning{Bad \string\setline\space argument}%
200 \newcommand*{\led@warn@BadSetlinenum}{%
201   \reledmac@warning{Bad \string\setlinenum\space argument}%
202 %

\led@err@PstartNotNumbered203 \newcommand*{\led@err@PstartNotNumbered}{%
\led@err@PstartInPstart204   \reledmac@error{\string\pstart\space must be used within a
\led@err@PendNotNumbered205       numbered section \%}
\led@err@PendNoPstart206       (\string\beginnumbering\space ... \string\endnumbering)%
}{\@ehc}%
\led@err@AutoparNotNumbered207 \newcommand*{\led@err@PstartInPstart}{%
\led@err@NumberingWithoutPstart208   \reledmac@error{\string\pstart\space encountered while another
209       \string\pstart\space was in effect}{\@ehc}%
210 \newcommand*{\led@err@PendNotNumbered}{%
211   \reledmac@error{\string\pend\space must be used within a
212       numbered section}{\@ehc}%
213 \newcommand*{\led@err@PendNoPstart}{%
214   \reledmac@error{\string\pend\space must follow a \string\pstart}{\@ehc}%
215 \newcommand*{\led@err@AutoparNotNumbered}{%
216   \reledmac@error{\string\autopar\space must be used within a
217       numbered section}{\@ehc}%
218 \newcommand*{\led@err@NumberingWithoutPstart}{%
219   \reledmac@error{\string\beginnumbering... \string\endnumbering\space
220       without \string\pstart}{\@ehc}%
}

\led@warn@BadAction221 \newcommand*{\led@warn@BadAction}{%
222   \reledmac@warning{Bad action code, value \next@action.}%
223 %

\led@warn@DuplicateLabel224 \newcommand*{\led@warn@DuplicateLabel}[1]{%
\led@warn@AppLabelOutSecondArgEdtext225   \reledmac@warning{Duplicate definition of label `#1' \@gobble}%
\led@warn@RefUndefined226   \@latex@warning@no@line{Label `#1' multiply defined}%
\led@warn@RefUndefined227 }%
\newcommand*{\led@warn@AppLabelOutSecondArgEdtext}[1]{%
228   \reledmac@warning{\string\applabel\space outside of the second argument
229       of an \string\edtext\space `#1' on page \thepage.}%
\newcommand*{\led@warn@RefUndefined}[1]{%
230   \G@refundefinedtrue%
231   \reledmac@warning{Reference `#1' on page \thepage\space undefined.%
232       Using `000'.}%
233   \@latex@warning{Reference `#1' undefined\on@line}%
234 }%
\newcommand*{\led@warn@pairRefUndefined}[1]{%
235   \G@refundefinedtrue%
236 }
```

```

238     \reledmac@warning{Reference `#1:start' and/or `#1:end' on page \thepage\
space undefined.
239         Using `??'.}%
240     \@latex@warning{Reference `#1:start' and/or `#1:end' undefined\on@line}%
241 }
242 %

```

```

\led@warn@NoMarginpars43 \newcommand*{\led@warn@NoMarginpars}{%
244     \reledmac@warning{You can't use \string\marginpar\space in numbered text
245 }%
246 %

```

```

ed@warn@BadSidenotemargin46 \newcommand*{\led@warn@BadSidenotemargin}{%
247     \reledmac@warning{Bad \string\sidenotemmargin\space argument}%
248 %

```

```

\led@warn@NoIndexFile49 \newcommand*{\led@warn@NoIndexFile}[1]{%
250     \reledmac@warning{Undefined index file #1}%
251 %

```

```

led@warn@SeriesStillExist52 \newcommand{\led@warn@SeriesStillExist}[1]{%
253     \reledmac@warning{Series #1 is still existing !}%
254 }%
255 %

```

```

\led@err@BadAction56 \newcommand*{\led@err@StanzaIndentNotDefined}{%
257     \reledmac@error{You have not defined the indentation for the line \number
\stanza@count}{\@ehc}}%
258 %

```

```

\led@err@ManySidenotes59 \newcommand{\led@err@ManySidenotes}{%
\led@err@ManyLeftnotes60 \ifledRcol@%
\led@err@ManyRightnotes61     \reledmac@warning{\itemcount@\space sidenotes on line \the\line@numR\
space p. \the\page@numR}%
262     \else%
263         \reledmac@warning{\itemcount@\space sidenotes on line \the\line@numR\
space p. \the\page@numR}%
264     \fi%
265 }%
266 \newcommand{\led@err@ManyLeftnotes}{%
267     \ifledRcol@%
268         \reledmac@warning{\itemcount@\space leftnotes on line \the\line@numR\
space p. \the\page@numR}%

```

```

269 \else%
270   \reledmac@warning{\itemcount@ \space leftnotes on line \the\line@num \
271   space p. \the\page@num}%
272 \fi%
273 }%
274 \newcommand{\led@err@ManyRightnotes}{%
275   \ifledRcol@%
276     \reledmac@warning{\itemcount@ \space rightnotes on line \the\line@numR \
277     space p. \the\page@numR}%
278   \else%
279     \reledmac@warning{\itemcount@ \space rightnotes on line \the\line@num \
280     space p. \the\page@num}%
281   \fi%
282 }%
283 %

\led@err@TooManyColumns81 \newcommand*{\led@err@TooManyColumns}{%
\led@err@UnequalColumns82   \reledmac@error{Too many columns}{\@ehc}%
\led@err@LowStartColumn83 \newcommand*{\led@err@UnequalColumns}{%
\led@err@HighEndColumn84   \reledmac@error{Number of columns is not equal to the number
\led@err@ReverseColumns85       in the previous row (or \protect\\ \space forgotten?)}{\@ehc}%
                                \reledmac@error{Start column is too low}{\@ehc}%
                                \reledmac@error{End column is too high}{\@ehc}%
\newcommand*{\led@err@ReverseColumns}{%
\led@err@toendnotes@outsidenumbering93   \reledmac@error{Start column is greater than end column}{\@ehc}%
                                %
                                \newcommand{\led@err@toendnotes@outsidenumbering}{%
294     \reledmac@error{\string\toendnotes\space and related commands must be
295     called inside a numbered texte (\string\beginnumbering\space ... \space\string
296     \endnumbering)}{\@ehc}%
297   }%
298   %
299 }

\led@err@EdtextWithoutFootnote97 \newcommand{\led@err@EdtextWithoutFootnote}{%
298   \reledmac@error{edtext without Xfootnote. Check syntax}{\@ehc}%
299 }%
300 %

\led@err@FootnoteNotInSecondArgEdtext01 \newcommand{\led@err@FootnoteNotInSecondArgEdtext}[1]{%
302   \reledmac@error{#1 footnote outside of the second argument of an edtext.
303   Check syntax}{\@ehc}%
304 }%
305 %

```

```

error@PackageAfterEledmac05 \newcommand{\led@error@PackageAfterEledmac}[1]{%
 306   \reledmac@error{#1 must be loaded before reledmac}{\@ehc}%
 307 }%
 308 %

```

```

error@fail@patch@@makecol09 \newcommand{\led@error@fail@patch@@makecol}{%
 310   \reledmac@error{Fail to patch \string\@makecol\space command}{\@ehc}%
 311 }%
 312 %

```

```

ror@fail@patch@@reinserts13 \newcommand{\led@error@fail@patch@@reinserts}{%
 314   \reledmac@error{Fail to patch \string\@reinserts\space command}{\@ehc}%
 315 }%
 316 %

```

```

r@fail@patch@@doclearpage17 \newcommand{\led@error@fail@patch@@doclearpage}{%
 318   \reledmac@error{Fail to patch \string\@doclearpage\space command}{\@ehc}%
 319 }%
 320 %

```

```

r@fail@patch@@iiiminipage21 \newcommand{\led@error@fail@patch@@iiiminipage}{%
 322   \reledmac@error{Fail to patch \string\@iiiminipage\space command}{\@ehc}%
 323 }%
 324 %

```

```

or@fail@patch@endminipage25 \newcommand{\led@error@fail@patch@endminipage}{%
 326   \reledmac@error{Failed to patch the \string\endminipage\space command}{\@ehc}%
 327 }%
 328 %

```

```

or@fail@patch@endminipage29 \newcommand{\led@error@fail@patch@makeindex}{%
 330   \reledmac@error{Failed to patch the \string\makeindex\space command}{\@ehc}%
 331 }%
 332 %

```

```

n@edinde@outsidenumbering33 \newcommand{\led@warn@edinde@outsidenumbering}{%
 334   \reledmac@warning{\string\edindex\space called outside of \string\beginnumbering\space ... \space \string\endnumbering. \MessageBreak
 335   Automatically switched to \string\index.}%
 336 }%

```

```
\led@warning@hsizex@deprecated37 \newcommand{\led@warning@hsizex@deprecated}{%
 338   \reledmac@warning{\string\hsizex\space command deprecated, use \string\
 339   widthx\space instead.}%
 340 }%
 341 %
```

```
\led@warning@xhsizex@deprecated41 \newcommand{\led@warning@xhsizex@deprecated}{%
 342   \reledmac@warning{\string\xhsizex\space command deprecated, use \string\
 343   Xwidth\space instead.}%
 344 }%
 345 %
```

```
\led@warning@msdatawithoutstop45 \newcommand{\led@warning@msdatawithoutstop}{%
 346   \reledmac@warning{\string\msdata\space without corresponding \string\
 347   stopmsdata}%
 348 }%
 349 %
```

```
\led@warning@prexnotes@deprecated49 \newcommand{\led@warning@prexnotes@deprecated}{%
 350   \reledmac@warning@prexnotes@deprecated%
 351 }%
 352 %
```

II.8 Gobbling

Here, we define some commands which gobble their arguments.

```
\@gobblethree53 \providecommand*\{@gobblethree}[3]{}
\@gobblefour54 \providecommand*\{@gobblefour}[4]{}
\@gobbleseven55 \providecommand*\{@gobbleseven}[7]{}
 356 %
```

II.9 Wrapping content

`\l@wrap@ifnotemptybox` `\l@wrapcs@ifnotemptybox`

The `\l@wrap@ifnotemptybox` macro wraps its second argument in the command passed as the first argument, but only if the second argument does not produce an empty box. That is useful for example when we need to wrap something on a `\textsuperscript`.

Indeed `a\textsuperscript{}`b does not produce the same typographical result as ab.²⁶ The `\l@wrapcs@ifnotemptybox` does the same, but take as argument a control sequence name, so without backslash.

²⁶Compare the distance between letters in the first case (ab) and in the second one (ab).

```

357 \newcommand{\l@wrap@ifnotemptybox}[2]{%
358   \setbox0=\hbox{#2}%
359   \ifdim\wd0=\z@\else%
360     #1{#2}%
361   \fi%
362 }%
363 \newcommand{\l@wrapcs@ifnotemptybox}[2]{%
364   \l@wrap@ifnotemptybox{\csname #1\endcsname}{#2}%
365 }%
366 %

```

II.10 Miscellaneous commands

`\showlemma` `\showlemma{<lemma>}` typesets the lemma text in the body. It depends on the option.

```

367 \ifledfinal
368   \newcommand*{\showlemma}[1]{#1}
369 \else
370   \newcommand*{\showlemma}[1]{\underline{#1}}
371 \fi
372 %
373 %

```

`\linenumberlist` The code for the `\linenumberlist` mechanism was given to Peter Wilson by Wayne Sullivan on 2004/02/11.

Initialize it as `\empty`.

```

374 \let\linenumberlist=\empty
375 %
376 %

```

`\@l@dtmpcnta` In imitation of `\TeX`, we create a couple of scratch counters.

`\@l@dtmpcntb` `\TeX` already defines `\@tempcnta` and `\@tempcntb` but Peter Wilson found in the past that it can be dangerous to use these (for example one of the AMS packages did something nasty to the `ccaption` package's use of one of these).

```

377 \newcount\@l@dtmpcnta \newcount\@l@dtmpcntb
378 %

```

II.11 Prepare reledpar

`\ifl@dpairing` In preparation for the `reledpar` package, these are related to the ‘right’ text of parallel texts (when `\ifl@dpairing` is TRUE). They are explained in the `reledpar` manual.

```

\ifl@dprintingpages
\ifl@dprintingcolumns
  \newif\ifl@dpairing
  \ifpst@rtedL
    \newif\ifl@dpaging%
  \l@dnumpstartsL
    \newif\ifl@dprintingpages%

```

```

382 \newif\ifl@dprintingcolumns%
383 \newif\ifpst@rtedL
384 \newcount\l@dnumpstartsL
385 %

```

\ifledRcol `\ifledRcol` is set to true in the `Rightside` environnement. It must be not confused with `\ifledRcol@` which is set to true when a right line is processed, in `\Pages` or `\Columns`.

```

386 \newif\ifledRcol
387 \newif\ifledRcol@
388 %

```

\ifnumberingR The `\ifnumberingR` flag is set to true if we're within a right text numbered section.

```

389 \newif\ifnumberingR
390 %

```

\ifafterendnumberingR The `\ifafterendnumberingR` boolean is set to TRUE at `\endnumberingR` and to FALSE at next `\beginnumberingR` or real `\beginnumbering` (not `\resumenumbers`). It is mainly used for the `continuousnumberingwithcolumns`, to avoid incrementing right column line counters after a `\endnumberingR`.

```

391 \newif\ifafterendnumberingR%
392 %

```

The `\ifXnote@` macro is set to true when we are typesetting a critical footnote.

```

393 \newif\ifXnote@%
394 %

```

II.12 Booleans provided by other optional packages which are required in any case

\ifindtl@innote The `\ifindtl@innote` and `\ifindtl@notenumber` are required even if `indextools` is not used.

```

395 \providebool{indtl@innote}%
396 \providebool{indtl@notenumber}%
397 %

```

III Sectioning commands

\section@num You use `\beginnumbering` and `\endnumbering` to begin and end a line-numbered section of the text; the pair of commands may be used as many times as you like within one document to start and end multiple, separately line-numbered sections. L^AT_EX will maintain and display a ‘section number’ as a count named `\section@num` that counts how many `\beginnumbering` and `\resumenumbers` commands have appeared; it need not be related to the logical divisions of your text.

\extensionchars Each section will read and write an associated ‘line-list file’, containing information used to do the numbering; the file will be called *<jobname>.nn*, where nn is the section number. However, you may direct that an extra string be added before the nn in that filename, in order to distinguish these temporary files from others: that string is called **\extensionchars**. Initially it’s empty, since different operating systems have greatly varying ideas about what characters are permitted in file names. So `\renewcommand{\extensionchars}{-}` gives temporary files called *jobname.-1*, *jobname.-2*, etc.

```
398 \newcount\section@num
399 \section@num=0
400 \let\extensionchars=\empty
401 %
```

\ifnumbering The **\ifnumbering** flag is set to true if we are within a numbered section (that is, between **\beginnumbering** and **\endnumbering**). You can use **\ifnumbering** in your own code to check whether you are in a numbered section, but do not change the flag’s value.

```
402 \newif\ifnumbering
403 %
```

\beginnumbering **\initnumbering@reg** **\beginnumbering** begins a section of numbered text. When it is executed we increment the section number, initialize our counters, send a message to your terminal, and call macros to start the lineation machinery and endnote files.

The initializations here are trickier than they look. **\line@list@stuff** will use all of the counters that are zeroed here when it assembles the line-list and other lists of information about the lineation. But it will do all of this locally and within a group, and when it is done the lists will remain but the counters will return to zero. Those same counters will then be used as we process the text of this section, but the assignments will be made globally. These initializations actually apply to both uses, though in all other respects there should be no direct interaction between the use of these counters and variables in the two processing steps. For parallel processing :

- zero **\l@dnum@startsL** – the number of chunks to be processed.
- set **\ifpst@rtedL** to FALSE.

```
404 \newcommand*{\beginnumbering}{%
405   \ifnumbering
406     \led@err@NumberingStarted
407     \endnumbering
408   \fi
409   \global\numberingtrue
410   \global\afterendnumberingRfalse%
411   \global\advance\section@num \@ne
412   \initnumbering@reg
413   \message{Section \the\section@num }%
```

```

414 \line@list@stuff{\jobname.\extensionchars\the\section@num}%
415 \ifcontinuousnumberingwithcolumns%
416   \unless\ifafterendnumberingR%
417     \unless\ifl@dpairing%
418       \ledRcoltrue%
419       \global\advance\section@numR \cne%
420       \message{Section \the\section@numR R (continuousnumbering)}%
421       \line@list@stuffR{\jobname.\extensionchars\the\section@numR R}%
422       \ledRcolfalse%
423     \fi%
424   \fi%
425 \fi%
426 \l@dend@stuff
427 \setcounter{pstart}{1}
428 \ifl@dpairing
429   \global\l@dnumpstartsL \z@%
430   \global\pst@rtedLfalse
431 %

```

The tools for section's title commands are called:

- Define an empty list of pstart number where sectioning commands are called.
- Input auxiliary file with the description of section titles.
- Open the same auxiliary file to write in.

```

432 \else
433   \begingroup
434     \global\@afterindenttrue%In order to reestablish normal feature if the \
435     begingroup was not here
436     \initnumbering@quote
437     \ifwidthliketwocolumns%
438       \setwidthliketwocolumns%
439       \csuse{setpositionliketwocolumns@\columns@position}%
440     \fi%
441   \fi
442   \gdef\eled@sections@@{}%
443   \if@noeled@sec\else%
444     \makeatletter%
445     \InputIfFileExists%
446       {\l@auxdir\jobname.eledsec\the\section@num}%
447       {}%
448       {\led@warn@NoFile{\l@auxdir\jobname.eledsec\the\section@num}}%
449     \makeatother%
450     \immediate\openout\eled@sectioning@out=\l@auxdir\jobname.eledsec\the\
451     section@num\relax%
452   \fi%
453 }
454 \newcommand*{\initnumbering@reg}{%
455   \global\pst@rtedLfalse

```

```

454 \global\l@dnumpstartsL \z@
455 \global\absline@num \z@
456 \gdef\normal@page@break{}
457 \gdef\l@prev@pb={}
458 \gdef\l@prev@nopb={}
459 \global\line@num \z@
460 \global\subline@num \z@
461 \global\@clock \z@
462 \global\sub@lock \z@
463 \global\sublines@false
464 \global\let\next@page@num=\relax
465 \global\let\this@section@next@page@num=\relax%
466 \global\let\sub@change=\relax
467 \global\last@page@num=-10000%
468 \ifdefined\line@numR%
469   \line@numR=\z@%
470   \last@page@numR=\z@%
471 \fi%
472 \resetprevline@
473 \resetprevpage@num
474 \global\stopmsdata@inserted@true%
475 \global\let\@msdata@list\relax%
476 \global\csundef{\@msdata@\add@msd@c @data}%
477 }
478 %
479 %

```

\endnumbering `\endnumbering` must follow the last text for a numbered section. It takes care of notifying you when changes have been noted in the input that require running the file through again to move everything to the right place. We define it using `\def` and not `\newcommand` because L^AT_EX does not allow defining command whose name starts by “end” except if we are currently creating an environment, which is not the case here.

```

480 \def\endnumbering{%
481   \ifnumbering
482     \global\numberingfalse
483     \normal@pars
484     \ifnum\l@dnumpstartsL=0%
485       \led@err@NumberingWithoutPstart%
486     \fi%
487 %

```

For the `continuousnumberingwithcolumn` options, we need to store a global value for the next `\endnumbering`. We don’t modify this counter globally, because that creates problem for nested `\edtext`.

```

488   \global\page@num=\this@section@page@num%
489   \global\last@page@num=\this@section@last@page@num%
490   \global\let\next@page@num\this@section@next@page@num%
491   \ifl@dpairing

```

```

492   \global\pst@rteLfalse
493   \else
494     \ifx\insertlines@list\empty\else
495       \global\noteschanged@true
496     \fi
497     \ifx\line@list\empty\else
498       \global\noteschanged@true
499     \fi
500   \fi
501   \ifnoteschanged@
502     \led@mess@NotesChanged
503   \fi
504 \else
505   \led@err@NumberingNotStarted
506 \fi
507 \autoparfalse
508 \if@noeled@sec\else%
509   \immediate\closeout\eled@sectioning@out%
510 \fi%
511 \ifl@dpairing\else
512   \global\l@dnumpstartsL=\z@%
513   \endgroup
514 \fi
515 }
516 %

```

\pausenumbering
 \resumenumbering
 \ifresumenumbering@start
 \pausenumbering@page@num

The \pausenumbering macro is just the same as \endnumbering, but with the \ifnumbering flag set to true, to show that numbering continues across the gap.²⁷ The \pausenumbering@page@num counter stores the \this@section@next@page@num when the \pause@numbering is called.

```

517 \newcount\pausenumbering@page@num%
518 \newcommand{\pausenumbering}{%
519   \ifx\this@section@next@page@num\relax%
520     \global\pausenumbering@page@num=0%
521   \else%
522     \global\pausenumbering@page@num=\this@section@next@page@num%
523   \fi%
524   \ifautopar\global\autopar@pausetrue\fi%
525   \endnumbering\global\numberingtrue}
526 %

```

The \resumenumbering macro is a bit more involved, but not much. It does most of the same things as \beginnumbering, but without resetting the various counters. Note that no check is made by \resumenumbering to ensure that \pausenumbering was actually invoked. The boolean \ifresumenumbering@start is set to true. That allows us to avoid resetting the line number at the first line of \resumenumbering if the lineation is by page. This boolean is set to false after the first action.

²⁷Peter Wilson's thanks to Wayne Sullivan, who suggested the idea behind these macros.

```

527 \newif\ifresumenumbering@start%
528 \newcommand*{\resumenumbering}{%
529   \ifnumbering
530     \ifaftopar@pause\autopar\fi
531     \global\pst@rteLtrue
532     \global\advance\section@num \@ne
533     \global\resumenumbering@starttrue%
534     \led@mess@SectionContinued{\the\section@num}%
535     \set@continuousnumberingforL%
536     \line@list@stuff{\jobname.\extensionchars\the\section@num}%
537     \ifcontinuousnumberingwithcolumns%
538       \unless\ifafterendnumberingR%
539         \unless\ifl@dpairing%
540           \ledRcoltrue%
541           \global\advance\section@numR \@ne%
542           \message{Section \the\section@numR R (continuousnumbering)}%
543           \line@list@stuffR{\jobname.\extensionchars\the\section@numR R}%
544           \ledRcolfalse%
545         \fi%
546       \fi%
547     \fi%
548     \l@end@stuff
549     \ifl@dpairing\else%
550       \begingroup%
551       \initnumbering@quote%
552       \ifwidthliketwocolumns%
553         \setwidthliketwocolumns%
554         \csuse{setpositionliketwocolumns@\columns@position}%
555       \fi%
556     \fi%
557   \else
558     \led@err@NumberingShouldHaveStarted
559     \endnumbering
560     \beginnumbering
561   \fi}
562
563
564 %

```

`t@continuousnumberingforL` `\set@continuousnumberingforL` sets pstart counters at a `\beginnumbering` or a `\resumenumbering` in order to have continuous numbering with single column text.

```

565 \newcommand{\set@continuousnumberingforL}{%
566   \ifcontinuousnumberingwithcolumns%
567     \ifl@dpairing%
568       \unless\ifl@dpaging%
569         \global\c@pstartL=\c@pstart%
570       \fi%
571     \fi%
572   \fi%

```

```
573 }%
574 %
```

IV List macros

We will make heavy use of lists of information, which will be built up and taken apart by the following macros; they are adapted from *The TeXbook*, pp. 378–379, which discusses their use in more detail.

These macros consume a large amount of the run-time of this code. We intend to replace them in a future version, and in anticipation of doing so have defined their interface in such a way that it is not sensitive to details of the underlying code.

The historical list tools of `ledmac` are kept, because in many cases there are more useful than `etoolbox`'s lists. They allow to get and delete the first element of a list in one operation. They also expands the items added to the list.

However, `etoolbox`'s lists are more useful to loop on them. Consequently, depending on what we need, we use one or either.

It could be nice to unify them to the L^AT_EX3 list, however such migration would take quite some time with some risk of error, for a gain which will be minor.

\list@create The `\list@create` macro creates a new list. This macro does not do anything beyond initializing an empty list macro.

```
575 \newcommand*{\list@create}[1]{%
576   \global\let#1=\empty%
577 }%
578 %
```

\list@clear The `\list@clear` macro just initializes a list to the empty list; it is no different from `\list@create` in its effect, but it is in its semantic.

```
579 \newcommand*{\list@clear}[1]{%
580   \global\let#1=\empty%
581 }
582 %
```

\xright@appenditem `\xright@appenditem` expands an item and appends it to the right end of a list macro. We want the expansion because we will often be using this to store the current value of a counter. `\xright@appenditem` creates global control sequences, like `\xdef`, and uses two temporary token-list registers, `\@toksa` and `\@toksb`.

```
583 \newtoks\led@toksa \newtoks\led@toksb
584 \global\let\led@toksa={\\}
585 \long\def\xright@appenditem#1\to#2{%
586   \global\let\led@toksb=\expandafter{#2}%
587   \xdef#2{\the\led@toksb\the\led@toksa\expandafter{#1}}%
588   \global\let\led@toksb={}%
589 }%
```

`\xleft@appenditem` `\xleft@appenditem` expands an item and appends it to the left end of a list macro; it is otherwise identical to `\xright@appenditem`.

```

590 \long\def\xleft@appenditem#1\to#2{%
591   \global\led@toksb=\expandafter{\#2}%
592   \xdef#2{\the\led@toksa\expandafter{\#1}\the\led@toksb}%
593   \global\led@toksb={}
594 %

```

`\gl@p` The `\gl@p` macro removes the leftmost item from a list and places it in a control sequence. You type `\gl@p\l\to\z` (where `\l` is the list macro, and `\z` receives the left item). `\l` is assumed nonempty:use `\ifx\l\empty` to test for an empty `\l`. The control sequences created by `\gl@p` are all global.

```

595 \def\gl@p#1\to#2{\expandafter\gl@poff#1\gl@poff#1#2}
596 \long\def\gl@poff\#1#2\gl@poff#3#4{\gdef#4{\#1}\gdef#3{\#2}}
597 %
598 %

```

V Line counting

V.1 Choosing the system of lineation

Line number can be reset at each section (default) ; at each page ; at each pstart. Here we define internal codes for these systems and the macros.

`\ifbypstart@` The `\ifbypage@` and `\ifbypstart@` flag specifie the current lineation system:
`\bypstart@true` • line-of-page: `bypstart@ = false` and `bypage@ = true`.
`\bypstart@false`
`\ifbypage@` • line-of-pstart: `bypstart@ = true` and `bypage@ = false`.
`\bypage@true`
`\bypage@false` `reledmac` will use the line-of-section system unless instructed otherwise.

```

599 \newif\ifbypage@
600 \newif\ifbypstart@
601 %

```

The `\ifbypage@R` and `\ifbypstart@R` flag specifie the current lineation for right side in case of using `reledpar`. They are now defined because they are used in some specific code. `reledpar` will use the line-of-section system unless instructed otherwise.

```

\ifbypage@R02 \newif\ifbypage@R
\ifbypstart@R03 \newif\ifbypstart@R
604 %

```

`\lineation` `\lineation{<word>}` is the macro you use to select the lineation system. Its argument is a string: either page, section or pstart.

```

605 \newcommand*{\lineation}[1]{{%
606 %

```

We can't change the lineation system inside numbering section.

```

607 \ifnumbering
608   \led@err@LineationInNumbered
609 \else
610 %

```

If the argument is page.

```

611 \def\@tempa{\#1}\def\@tempb{page}%
612 \ifx\@tempa\@tempb
613   \global\bypage@true
614   \global\bypstart@false
615   \unless\ifnocritical@%
616     \Xpstart[] [false]%
617   \fi%
618 %

```

If the argument is pstart.

```

619 \else
620   \def\@tempb{pstart}%
621   \ifx\@tempa\@tempb
622     \global\bypage@false
623     \global\bypstart@true
624     \unless\ifnocritical@%
625       \Xpstart%
626     \fi%
627 %

```

And finally, if the argument is section (default).

```

628 \else
629   \def\@tempb{section}%
630   \ifx\@tempa\@tempb
631     \global\bypage@false
632     \global\bypstart@false
633     \unless\ifnocritical@%
634       \Xpstart[] [false]%
635     \fi%
636 %

```

In other case, it is an error.

```

637 \else
638   \led@warn@BadLineation
639 \fi
640 \fi
641 \fi
642 \fi}%
643 %

```

V.2 Line number margin

\linenummargin \linenummargin{*word*} specify which margin line numbers are in; it takes one argument, a string, which value can be `left`; `right`; `inner` or `outer`.
\l@dge@line@margin The selection is recorded in the count \line@margin: 0 for left, 1 for right, 2 for outer, and 3 for inner.

```

644 \newcount\line@margin%
645 \newcount\line@margin@columns%Only for parallel typesetting
646 \line@margin@columns=\m@ne%
647
648 \newcommand*{\linenummargin}[1]{%
649   \l@dge@line@margin{#1}%
650   \ifnum\@l@dge@tempcntb>\m@ne
651     \ifledRcol
652       \global\line@marginR=\@l@dge@tempcntb
653       \led@warn@setting@in@rightside{\linenummargin}%
654     \else
655       \global\line@margin=\@l@dge@tempcntb
656     \fi
657   \fi}%
658
659 \newcommand*{\l@dge@line@margin}[1]{%
660   \def\@tempa{#1}\def\@tempb{left}%
661   \ifx\@tempa\@tempb
662     \@l@dge@tempcntb \z@
663   \else
664     \def\@tempb{right}%
665     \ifx\@tempa\@tempb
666       \@l@dge@tempcntb \cne
667     \else
668       \def\@tempb{outer}%
669       \ifx\@tempa\@tempb
670         \@l@dge@tempcntb \tw@
671       \else
672         \def\@tempb{inner}%
673         \ifx\@tempa\@tempb
674           \@l@dge@tempcntb \thr@@
675         \else
676           \led@warn@BadLinenummargin
677           \@l@dge@tempcntb \m@ne
678         \fi
679       \fi
680     \fi
681   \fi}%
682 %
683 %

```

V.3 Line number initialization and increment

\c@firstlinenum

\c@linenumincrement

The following counters tell reledmac which lines should be printed with line numbers. `firstlinenum` is the number of the first line in each section that gets a number; `linenumincrement` is the difference between successive numbered lines. The initial values of these counters produce labels on lines 5, 10, 15, etc. `linenumincrement` must be at least 1.

```
684 \newcounter{firstlinenum}
685   \setcounter{firstlinenum}{5}
686 \newcounter{linenumincrement}
687   \setcounter{linenumincrement}{5}
688 %
```

\c@firstsublinenum
\c@sublinenumincrement

The following parameters are just like `firstlinenum` and `linenumincrement`, but for sub-line numbers. `sublinenumincrement` must be at least 1.

```
689 \newcounter{firstsublinenum}
690   \setcounter{firstsublinenum}{5}
691 \newcounter{sublinenumincrement}
692   \setcounter{sublinenumincrement}{5}
693 %
694 %
```

\firstlinenum

\linenumincrement

\firstsublinenum⁶⁹⁵

\sublinenumincrement⁶⁹⁶

These macros can be used to set the corresponding counters.

```
697 \newcommand*{\firstlinenum}[1]{%
698   \ifledRcol%
699     \setcounter{firstlinenumR}{#1}%
700     \led@warn@setting@in@rightside{\firstlinenum}%
701   \else%
702     \setcounter{firstlinenum}{#1}%
703   \fi%
704 }
705 \newcommand*{\linenumincrement}[1]{%
706   \ifledRcol%
707     \setcounter{linenumincrementR}{#1}%
708     \led@warn@setting@in@rightside{\linenumincrement}%
709   \else%
710     \setcounter{linenumincrement}{#1}%
711   \fi%
712 }
713 \newcommand*{\firstsublinenum}[1]{%
714   \ifledRcol%
715     \setcounter{firstsublinenumR}{#1}%
716     \led@warn@setting@in@rightside{\firstsublinenum}%
717   \else%
718     \setcounter{firstsublinenum}{#1}%
719   \fi%
```

```

719 }
720 \newcommand*{\sublinenumincrement}[1]{%
721   \ifledRcol{%
722     \setcounter{sublinenumincrementR}{\#1}%
723     \led@warn@setting@in@rightside{\sublinenumincrement}%
724   }{\else{%
725     \setcounter{sublinenumincrement}{\#1}%
726   }}\fi%
727 }
728 %
729 %

```

V.4 Line number locking

`\lockdisp` When line locking is being used, the `\lockdisp{<word>}` macro specifies whether a line number—if one is due to appear—should be printed on the first printed line or on the last, or by all of them. Its argument is a word, either `first`, `last`, or `all`. Initially, it is set to `first`.

`\lock@disp` encodes the selection: 0 for `first`, 1 for `last`, 2 for `all`.

```

730 \newcount\lock@disp
731 \newcommand{\lockdisp}[1]{{%
732   \l@dge@lock@disp{\#1}%
733   \ifnum\l@dge@tempcntb>\m@ne
734     \global\lock@disp=\l@dge@tempcntb
735   \else
736     \led@warn@BadLockdisp
737   \fi}%
738 \newcommand*{\l@dge@lock@disp}[1]{%
739   \def\@tempa{\#1}\def\@tempb{first}%
740   \ifx\@tempa\@tempb
741     \l@dge@tempcntb \z@
742   \else
743     \def\@tempb{last}%
744     \ifx\@tempa\@tempb
745       \l@dge@tempcntb \cne
746     \else
747       \def\@tempb{all}%
748       \ifx\@tempa\@tempb
749         \l@dge@tempcntb \tw@
750       \else
751         \l@dge@tempcntb \m@ne
752       \fi
753     \fi
754   \fi%
755 %
756 %

```

`\subblockdisp` The same questions about where to print the line number apply to sub-lines, and these are the analogous macros for dealing with the problem.

```

757 \newcount\subblock@disp
758 \newcommand{\subblockdisp}[1]{{%
759   \l@dge@lock@disp{#1}%
760   \ifnum\@l@dtmpcntb>\m@ne
761     \global\subblock@disp=\@l@dtmpcntb
762   \else
763     \l@e@warn@BadSubblockdisp
764   \fi}%
765 %
766 %

```

V.5 Line number style

`\linenumberstyle` We provide a mechanism for using different representations of the line numbers, not just the normal arabic.

`\linenumrep` NOTE: In v0.7 `\linenumrep` and `\sublinenumrep` replaced the internal `\linenumr@p` and `\sublinenumr@p`.
`\sublinenumberstyle` `\linenumberstyle` and `\sublinenumberstyle` are user level macros for setting the number representation (`\linenumrep` and `\sublinenumrep`) for line and sub-line numbers.

```

767 \newcommand*{\linenumberstyle}[1]{%
768   \def\linenumrep##1{\@nameuse{@##1}{##1}}%
769 \newcommand*{\sublinenumberstyle}[1]{%
770   \def\sublinenumrep##1{\@nameuse{@##1}{##1}}%
771 %

```

Initialise the number styles to arabic.

```

772 \linenumberstyle{arabic}
773   \let\linenumr@p\linenumrep
774 \sublinenumberstyle{arabic}
775   \let\sublinenumr@p\sublinenumrep
776 %
777 %

```

V.6 Line number printing

`\leftlinenum` `\leftlinenum` and `\rightlinenum` are the macros that are called to print marginal line numbers on a page, for left- and right-hand margins respectively. They are made easy to access and change, since you may want to change the styling in some way. These standard versions illustrate the general sort of thing that will be needed; they are based on the `\leftheadline` macro in *The TeXbook*, p. 416.

Whatever these macros output gets printed in a box that will be put into the appropriate margin without any space between it and the line of text. You will generally want a kern between a line number and the text, and `\linenumsep` is provided as a

standard way of storing its size. Line numbers are usually printed in a smaller font, and `\numlabfont` is provided as a standard name for that font. When called, these macros will be executed within a group, so font changes and the like will remain local.

`\ledlinenum` typesets the line (and subline) number.

The original `\numlabfont` specification is equivalent to the L^AT_EX `\scriptsize` for a 10pt document.

```

778 \newlength{\linenumsep}
779   \setlength{\linenumsep}{1pc}
780 \newcommand*{\numlabfont}{\normalfont\scriptsize}
781 \newcommand*{\ledlinenum}{%
782   \bgroup%
783   \ifluatex%
784     \textdir TLT%
785   \fi%
786   \numlabfont%
787   \ifdefstring{\Xlinenumannotationposition@side}{before}{%
788     \l@wrap@ifnotemptybox{\Xwraplinenumannotation@side}{%
789       \csuse{annot@\the\absline@num @\the\section@num}%
790     }%
791   }{}%
792   \linenumrep{\line@num}%
793   \ifsublines@%
794     \ifnum\subline@num>0\relax%
795       \unskip%
796       \Xsublinesep@side%
797       \sublinenumrep{\subline@num}%
798     \fi%
799   \fi%
800   \ifdefstring{\Xlinenumannotationposition@side}{after}{%
801     \l@wrap@ifnotemptybox{\Xwraplinenumannotation@side}{%
802       \csuse{annot@\the\absline@num @\the\section@num}%
803     }%
804   }{}%
805   \egroup%
806 }%
807 %
808 \newcommand*{\leftlinenum}{%
809   \ledlinenum
810   \kern\linenumsep}
811 \newcommand*{\rightlinenum}{%
812   \kern\linenumsep
813   \ledlinenum}
814 %
815 %

```

V.7 Line number counters and lists

Footnote references using line numbers rather than symbols can't be generated in one pass, because we do not know the line numbers till we ship out the pages. It would be possible if footnotes were never keyed to more than one line; but some footnotes gloss passages that may run for several lines, and they must be tied to the first line of the passage glossed. And even one-line passages require two passes if we want line-per-page numbering rather than line-per-section numbering.

So we run \LaTeX over the text several times, and each time save information about page and line numbers in a ‘line-list file’ to be used during the next pass. At the start of each section—whenever `\begin{numbering}` is executed—the line-list file for that section is read, and the information from it is encoded into a few list macros.

We need first to define the different line numbers that are involved in these macros, and the associated counters.

`\line@num` The count `\line@num` stores the line number that is used in marginal line numbering and in notes: counting either by section, page or pstart, depending on your choice for this section. This may be qualified by `\subline@num`.

```
816 \newcount\line@num
817 %
```

`\subline@num` The count `\subline@num` stores a sub-line number that qualifies `\line@num`. For example, line 10 might have sub-line numbers 1, 2 and 3, which might be printed as lines 10.1, 10.2, 10.3.

```
818 \newcount\subline@num
819 %
```

`\ifsblines@` We maintain an associated flag, `\ifsblines@`, to tell us whether we're within a sub-line range or not.

`\sblines@true` You may wonder why we do not just use the value of `\subline@num` to determine this—treating anything greater than 0 as an indication that sub-lineation is on. We need a separate flag because sub-lineation can be used together with line-number locking in odd ways: several pieces of a logical line might be interrupted by pieces of sub-lineated text, and those sub-line numbers should not return to zero until the next change in the major line number. This is common in the typesetting of English Renaissance verse drama, in which stage directions are given sub-line numbers: a single line of verse may be interrupted by several stage directions.

```
820 \newif\ifsblines@
821 %
```

`\absline@num` The count `\absline@num` stores the absolute number of lines since the start of the section: that is, the number we have actually printed, no matter what numbers we attached to them. This value is never printed on an output page, though `\line@num` will often be equal to it. It is used internally to keep track of where notes are to appear and where new pages start: using this value rather than `\line@num` is a lot simpler, because it does not depend on the lineation system in use.

```

822 \newcount\absline@num
823 %

```

We will call `\absline@num` numbers “absolute” numbers, and `\line@num` and `\subline@num` numbers “visible” numbers.

V.8 Line number locking counter

`\@lock` The counts `\@lock` and `\sub@lock` tell us the state of line-number and sub-line-number locking. 0 means we are not within a locked set of lines; 1 means we are at the first line in the set; 2, at some intermediate line; and 3, at the last line.

```

824 \newcount\@lock
825 \newcount\sub@lock
826 %

```

V.9 Line number associated to lemma

`\line@list` Now we can define the list of macros which will be created from the line-list file. We
`\insertlines@list` will maintain the following lists:
`\actionlines@list`

`\actions@list`
`\annot@list`

- `\line@list`: the page and line numbers for every lemma marked by `\edtext`. There are seven pieces of information, separated by vertical bars:
 1. the starting page,
 2. line, and
 3. sub-line numbers, followed by the
 4. ending page,
 5. line, and
 6. sub-line numbers, and then the
 7. font specifier for the lemma.

These line numbers are all visible numbers. The font specifier is a set of four codes for font encoding, family, series, and shape, separated by / characters. Thus a lemma that started on page 23, line 35 and went on until page 24, line 3 (with no sub-line numbering), and was typeset in a normal roman font would have a line list entry like this:

23|35|0|24|3|0|OT1/cmr/m/n.

There is one item in this list for every lemma marked by `\edtext`, even if there are several notes to that lemma, or no notes at all. `\edtext` reads the data in this list, making it available for use in the text of notes.

- `\insertlines@list`: the line numbers of lines that have footnotes or other insertions. These are the absolute numbers where the corresponding lemmas begin. This list contains one entry for every footnote in the section; one lemma may contribute no footnotes or many footnotes. This list is used by `\add@inserts` within `\do@line`, to tell it where to insert notes.

- `\actionlines@list`: a list of absolute line numbers at which we are to perform special actions; these actions are specified by the `\actions@list` list defined below.
- `\actions@list`: action codes corresponding to the line numbers in `\actionlines@list`. These codes tell `reledmac` what action it is supposed to take at each of these lines. One action, the page-start action, is generated behind the scenes by `reledmac` itself; the others, for specifying sub-lineation, line-number locking, and line-number alteration, are generated only by explicit commands in your input file. The page-start and line-number-alteration actions require arguments, to specify the new values for the page or line numbers; instead of storing those arguments in another list, we have chosen the action-code values so that they can encode both the action and the argument in these cases. Action codes greater than -1000 are page-start actions, and the code value is the page number; action codes less than -5000 specify line numbers, and the code value is a transformed version of the line number; action codes between these two values specify other actions which require no argument.

Here is the full list of action codes and their meanings:

Any number greater than -1000 is a page-start action: the line number associated with it is the first line on a page, and the action number is the page number. (The cutoff of -1000 is chosen because negative page-number values are used by some macro packages; we assume that page-number values less than -1000 are not common.) Page-start action codes are added to the list by the `\page@action` macro, which is (indirectly) triggered by the workings of the `\page@start` macro; that macro should always be called in the output routine, just before the page contents are assembled. `Eledmac` calls it in `\pagecontents`.

The action code -1001 specifies the start of sub-lineation: meaning that, starting with the next line, we should be advancing `\subline@num` at each start-of-line command, rather than `\line@num`.

The action code -1002 specifies the end of sub-lineation. At the next start-of-line, we should clear the sub-line counter and start advancing the line number. The action codes for starting and ending sub-lineation are added to the list by the `\sub@action` macro, as called to implement the `\startsub` and `\endsub` macros.

The action code -1003 specifies the start of line number locking. After the number for the current line is computed, it will remain at that value through the next line that has an action code to end locking.

The action code -1004 specifies the end of line number locking.

The action code -1005 specifies the start of sub-line number locking. After the number for the current sub-line is computed, it will remain at that value through the next sub-line that has an action code to end locking.

The action code -1006 specifies the end of sub-line number locking.

The four action codes for line and sub-line number locking are added to the list by the `\do@lockon` and `\do@lockoff` macros, as called to implement the

\startlock and \endlock macros.

An action code of -5000 or less sets the current visible line number (either the line number or the sub-line number, whichever is currently being advanced) to a specific positive value. The value of the code is $-(5000 + n)$, where n is the value (always ≥ 0) assigned to the current line number. Action codes of this type are added to the list by the \set@line@action macro, as called to implement the \advanceline and \setline macros: this action only occurs when the user has specified some change to the line numbers using those macros. Normally `reledmac` computes the visible line numbers from the absolute line numbers with reference to the other action codes and the settings they invoke; it does not require an entry in the action-code list for every line.

- \annot@list stores line number annotations for the start and the end lines of each \edtext, as \line@list does for line numbers. We don't store that in the same list as line numbers as \Xprintlines already have height arguments, and a `TEX` macro can take at most nine arguments.

Here are the commands to create these lists:

```

827 \list@create{\line@list}
828 \list@create{\insertlines@list}
829 \list@create{\actionlines@list}
830 \list@create{\actions@list}
831 \list@create{\annot@list}%
832 %

```

\page@num We will need some counts while we read the line-list, for the page number and the ending page, line, and sub-line numbers. Some of these will be used again later on, when we

\endpage@num are acting on the data in our list macros.

```

\endsubline@num
833 \newcount\page@num
834 \newcount\endpage@num
835 \newcount\endline@num
836 \newcount\endsubline@num
837 %

```

\this@section@page@num The \this@section@page@num stores the page number on which a numbering section ends.

```

838 \newcount\this@section@page@num%
839 %

```

\ifnoteschanged@ If the number of the footnotes in a section is different from what it was during the last run, or if this is the very first time you've run `LATEX`, on this file, the information from the line-list used to place the notes will be wrong, and some notes will probably be misplaced. When this happens, we prefer to give a single error message for the whole section rather than messages at every point where we notice the problem, because we do not really know where in the section notes were added or removed, and the solution in any case is simply to run `LATEX` two more times; there is no fix needed to the document.

The `\ifnoteschanged@` flag is set if such a change in the number of notes is discovered at any point.

```
840 \newif\ifnoteschanged@
841 %
```

`\resetprevline@` Inside the apparatus, at each note, the line number is stored in a macro called `\prevlineX`, where X is the letter of the current series. This macro is called when using `\Xnumberonlyfirstinline`. This macro must be reset at the same time as the line number. The `\resetprevline@` does this resetting for every series.

```
\resetprevline@42 \newcommand*{\resetprevline@}{%
 843   \def\do##1{\global\csundef{prevline##1}}%
 844   \dolistloop{\@series}%
 845 }
 846 %
```

`\resetprevpage@num` Inside the apparatus, at each note, the page number is stored in a macro called `\prevpageX@num`, where X is the letter of the current series. This macro is called when using `\Xparafootsep` or `\parafootsepX`. This macro must be reset at the beginning of each numbered section. The `\resetprevpage@` command resets this macro for every series.

```
\resetprevpage@47 \newcommand*{\resetprevpage@num}{%
 848   \def\do##1{%
 849     \ifcsdef{prevpage##1@num}{%
 850       \global\csname prevpage##1@num\endcsname=\z@%
 851       \global\csname prevpage##1@numR\endcsname=\z@%
 852     }%
 853     {}%
 854     \ifcsdef{##1prevpage@num}{%
 855       \global\csname ##1prevpage@num\endcsname=\z@%
 856       \global\csname ##1prevpage@numR\endcsname=\z@%
 857     }%
 858     {}%
 859   }%
 860   \dolistloop{\@series}%
 861 }
 862 %
```

V.10 Reading the line-list file

`\read@linelist` `\read@linelist{<file>}` is the control sequence that is called by `\beginnumbering` (via `\line@list@stuff`) to open and process a line-list file; its argument is the name of the file. . First, it clear all previous line's list.

```
863 \newread\@inputcheck
864 \newcommand*{\read@linelist}[1]{%
```

```

865   \ifledRcol%
866     \list@clearing@regR%
867   \else%
868     \list@clearing@reg%
869   \fi%
870 %

```

When using `reledpar`, make sure that the `\maxlinesinpar@list` is empty (otherwise things will be thrown out of kilter if there is any old stuff still hanging in there).

```

871   \list@clear{\maxlinesinpar@list}
872 %

```

Now get the file and interpret it. When the file is there we start a new group and make some special definitions we will need to process it. It is a sequence of TeX commands, but they require a few special settings. We make [and] become grouping characters: they are used that way in the line-list file, because we need to write them out one at a time rather than in balanced pairs, and it is easier to just use something other than real braces. @ must become a letter, since this is run in the ordinary L^AT_EX context. We ignore carriage returns, since if we are in horizontal mode they can get interpreted as spaces to be printed.

Our line, page, and line-locking counters were already zeroed by `\line@list@stuff` if this is being called from within `\beginnumbering`; sub-lineation will be turned off as well in that case. On the other hand, if this is being called from `\resumenumbering`, those things should still have the values they had when `\pausenumbering` was executed.

If the file is not there, we print an informative message.

Now, after these preliminaries, we start interpreting the file.

```

873 \get@linelistfile{#1}%
874 \@stopmsd%Security if last \endms{} is forgotten
875 \unless\ifledRcol%Get the last line of the last page
876   \csnumgdef{@lastabsline@forpage@\the\page@num}{\the\absline@num}%
877   \csnumgdef{@lastline@forpage@\the\page@num}{\the\line@num}%
878 \else%
879   \csnumgdef{@lastabsline@forpageR@\the\page@numR}{\the\absline@numR}%
880   \csnumgdef{@lastline@forpageR@\the\page@numR}{\the\line@numR}%
881 \fi%
882 \endgroup
883 %

```

When the reading is done, we are all through with the line-list file. All the information we needed from it will now be encoded in our list macros.

Finally, we initialize the `\next@actionline` and `\next@action` macros, which specify where and what the next action to be taken is.

```

884 \ifledRcol
885   \global\page@numR=\m@ne
886   \ifx\actionlines@listR\empty
887     \gdef\next@actionlineR{1000000}%
888   \else

```

```

889     \gl@p\actionlines@listR\to\next@actionlineR
890     \gl@p\actions@listR\to\next@actionR
891   \fi
892 \else
893   \global\page@num=\m@ne
894   \ifx\actionlines@list\empty
895     \gdef\next@actionline{1000000}%
896   \else
897     \gl@p\actionlines@list\to\next@actionline
898     \gl@p\actions@list\to\next@action
899   \fi
900 \fi
901 }
902 %

```

`\list@clearing@reg` Clears the lists for `\read@linelist`

```

903 \newcommand*{\list@clearing@reg}{%
904   \list@clear{\line@list}%
905   \list@clear{\insertlines@list}%
906   \list@clear{\actionlines@list}%
907   \list@clear{\actions@list}%
908   \list@clear{\linesinpar@listL}%
909   \list@clear{\linesonpage@listL}%
910 }%
911 %

```

`\get@linelistfile` reledmac can take advantage of the L^AT_EX ‘safe file input’ macros to get the line-list file.

```

912 \newcommand*{\get@linelistfile}[1]{%
913   \InputIfFileExists{\l@auxdir#1}{%
914     \global\noteschanged@false
915     \begingroup
916       \catcode`\[=1 \catcode`\]=2
917       \makeatletter \catcode`\^=9}%
918     \led@warn@NoFile{\l@auxdir#1}%
919     \global\noteschanged@true
920   \begingroup}%
921 }
922 %
923 %

```

This version of `\read@linelist` creates list macros containing data for the entire section, so they could get rather large. It would be no more difficult to read the line-list file incrementally rather than all at once: we could read, at the start of each paragraph, only the commands relating to that paragraph. But this would require that we have two line-lists open at once, one for reading, one for writing, and on systems without version numbers we would have to do some file renaming outside of L^AT_EX for that to

work. We have retained this slower approach to avoid that sort of hacking about, but have provided the `\pausenumbering` and `\resumenumbering` macros to help you if you run into macro memory limitations (see 5.2.7 p. 20 above).

V.11 Commands within the line-list file

This section defines the commands that can appear within a line-list file. They all have very short names because we are likely to be writing very large numbers of them out. One macro, `\@nl`, is especially short, since it will be written to the line-list file once for every line of text in a numbered section. (Another of these commands, `\@lab`, will be introduced in a later section, among the cross-referencing commands it is associated with.)

When these commands modify the various page and line counters, they deliberately do not use `\global`. This is because we want them to affect only the counter values within the current group when nested calls of `\@ref` occur. (The code assumes throughout that the value of `\globaldefs` is zero.)

The macros with `action` in their names contain all the code that modifies the action-code list: again, this is so that they can be turned off easily for nested calls of `\@ref`.

`\line@list@version` The `\line@list@version` check if the line-list file does not refers to the older commands of `reledmac`. In this case, we stop reading the line-list file. Consequently, `\line@list@version` must be the first line of a line-number file.

```

924 \newcommand{\line@list@version}[1]{%
925   \IfStrEq{#1}{\this@line@list@version}%
926   {}%
927   {\ifledRcol%
928     \led@warn@Obsolete{\jobname.\extensionchars\the\section@num}%
929   \else%
930     \led@warn@Obsolete{\jobname.\extensionchars\the\section@num}%
931   \fi%
932   \endinput%
933 }%
934 }%
935 %

```

`\@nl` `\@nl` does everything related to the start of a new line of numbered text.

`\@nl@reg` In order to get the `\setlinenum` to work Peter Wilson had to slip in some new code at the start of the macro, to get the timing of the actions correct. The problem was that his original naive implementation of `\setlinenum` had a unfortunate tendency to change the number of the last line of the *preceding* paragraph. The new code is sort of based on the page number handling and `\setline`. It seems that a lot of fiddling with the line number internals is required.

In November 2004 in order to accurately determine page numbers Peter Wilson added these to the macro. It is now:

`\@nl{\<page counter number>}{\<printed page number>}`

We do not (yet) use the printed number (i.e., the `\thepage`) but it may come in handy later. The macro `\@page` checks if a new page has started.

Exactly what `\@nl` does depends on whether right text is being processed. That's why many code is defined in `\@nl@reg` or `\nl@regR`.

```

936
937 \newcommand*{\@nl}[2]{%
938   \atpage{#1}%
939   \ifledRcol%
940     \@nl@regR%
941   \else%
942     \@nl@reg%
943   \fi%
944 }
945 \newcommand*{\@nl@reg}{%
946   \ifx\l@dchset@num\relax \else
947     \advance\absline@num \@ne
948     \csgdef{l@dchset@num@\the\absline@num}{}%To remember this line have
949     been marked by a \setlinenum
950     \set@line@action
951     \let\l@dchset@num=\relax
952     \advance\absline@num \m@ne
953     \advance\line@num \m@ne
954   \fi
955 }
```

First increment the absolute line-number, and perform deferred actions relating to page starts and sub-lines.

```

955 \reset@current@annot%
956 \advance\absline@num \@ne
957   \ifx\next@page@num\relax \else
958     \page@action
959     \let\next@page@num=\relax
960   \fi
961   \ifx\sub@change\relax \else
962     \ifnum\sub@change>\z@
963       \sublines@true
964     \else
965       \sublines@false
966     \fi
967     \sub@action
968     \let\sub@change=\relax
969   \fi
970 }
```

Fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

971   \ifcase\@lock
972     \or
973       \@clock \tw@
974     \or \or
975       \@clock \z@
```

```

976      \fi
977      \ifcase\sub@lock
978          \or
979              \sub@lock \tw@
980          \or \or
981              \sub@lock \z@
982      \fi
983 %

```

Now advance the visible line number, unless it has been locked.

```

984      \ifsublines@
985          \ifnum\sub@lock<\tw@
986              \advance\subline@num \cne
987          \fi
988      \else
989          \ifnum\@clock<\tw@
990              \advance\line@num \cne \subline@num \z@
991          \fi
992      \fi}
993 %
994 %

```

```

\last@page@num  \cpage determines whether or not a new page has been started, based on the page
his@section@last@page@num  values held by \cnl.

\cpage
995 \newcount\last@page@num
996   \last@page@num=-10000
997
998 \newcount>this@section@last@page@num%
999   \this@section@last@page@num=-10000%
1000
1001 \newcommand*\cpage}[1]{%
1002     \ifledRcol
1003         \ifnum #1=\last@page@numR
1004     \else
1005         \csnumgdef{\lastabsline@forpageR@\the\page@numR}{\the\absline@numR}%
1006         \csnumgdef{\lastline@forpageR@\the\page@numR}{\the\line@numR}%
1007         \ifbypage@R
1008             \ifx\l@dchset@num\relax%Not resetting if preceded by a \setlinenum
1009                 \ifboolexpr{%
1010                     bool{resumenumeratingR@start}%
1011                     and test {\ifnumequal{\last@page@numR}{-10000}}%
1012                 }%
1013                 {}%
1014                 {}%
1015                 \line@numR \z@%
1016                 \subline@numR \z@%
1017                 \global\csdef{reset@lineR\the\numexpr\absline@numR+1\relax @\%
1018 the\section@numR}{}%
1019             }%

```

```

1019   \fi%
1020   \fi
1021   \page@numR=#1%
1022   \this@section@page@numR=#1%
1023   \last@page@numR=#1%
1024   \this@section@last@page@numR=#1%
1025   \def\next@page@numR{#1}%
1026   \gdef\this@section@next@page@numR{#1}%
1027   \fi
1028 \else
1029   \ifnum #1=\last@page@num
1030   \else
1031     \csnumgdef{\lastabsline@forpage@{\the\page@num}{\the\absline@num}%
1032     \csnumgdef{\lastline@forpage@{\the\page@num}{\the\line@num}%
1033     \ifbypage@
1034       \ifx\l@dchset@num\relax%Not resetting if preceded by a \setlinenum
1035         \line@num \z@%
1036         \subline@num \z@%
1037         \global\csdef{reset@line{\the\numexpr\absline@num+1\relax @\the\
1038           section@num}{}}
1039       \fi%
1040     \fi
1041     \page@num=#1%
1042     \global\this@section@page@num=#1%
1043     \global\this@section@last@page@num=#1%
1044     \def\next@page@num{#1}%
1045 %

```

And we set a flag that tells `\@nl` that a new page number is to be set, because other associated actions shouldn't occur until the next line-start occurs.

```

1046   \gdef\this@section@next@page@num{#1}%
1047   \listxadd{\normal@page@break}{\the\absline@num}
1048   \fi
1049 \fi}
1050 %

```

`\@pend` These do not do anything at this point, but will have been added to the auxiliary file(s)
`\@pendR` if the `reledpar` package has been used. They are just here to stop `reledmac` from
`\@lopL` moaning if the `reledpar` is used for one run and then not for the following one.

```

1051 \newcommand*{\@pend}[1]{}
1052 \newcommand*{\@pendR}[1]{}
1053 \newcommand*{\@lopL}[1]{}
1054 \newcommand*{\@lopR}[1]{}
1055 %

```

`\sub@on` The `\sub@on` and `\sub@off` macros turn sub-lineation on and off: but not directly, since
`\sub@off`

such changes do not really take effect until the next line of text. Instead they set a flag that notifies `\@nl` of the necessary action.

```

1057 \newcommand*{\sub@on}{\ifsublines@
1058   \let\sub@change=\relax
1059   \else
1060     \def\sub@change{1}%
1061   \fi}
1062 \newcommand*{\sub@off}{\ifsublines@
1063   \def\sub@change{-1}%
1064   \else
1065     \let\sub@change=\relax
1066   \fi}
1067 %
1068 %

```

\@adv The `\@adv{\langle num\rangle}` macro advances the current visible line number by the amount specified as its argument. This is used to implement `\advanceline`.

```

1069
1070 \newcommand*{\@adv}[1]{%
1071   \ifsublines@
1072   \ifledRcol
1073     \advance\subline@numR by #1\relax
1074     \ifnum\subline@numR<\z@
1075       \led@warn@BadAdvancelineSubline
1076       \subline@numR \z@
1077     \fi
1078   \else
1079     \advance\subline@num by #1\relax
1080     \ifnum\subline@num<\z@
1081       \led@warn@BadAdvancelineSubline
1082       \subline@num \z@
1083     \fi
1084   \fi
1085 \else
1086   \ifledRcol
1087     \advance\line@numR by #1\relax
1088     \ifnum\line@numR<\z@
1089       \led@warn@BadAdvancelineLine
1090       \line@numR \z@
1091     \fi
1092   \else
1093     \advance\line@num by #1\relax
1094     \ifnum\line@num<\z@
1095       \led@warn@BadAdvancelineLine
1096       \line@num \z@
1097     \fi
1098   \fi
1099 \fi

```

```

1100 \set@line@action}
1101 %
1102 %

```

\@set The `\@set{<num>}` macro sets the current visible line number to the value specified as its argument. This is used to implement `\setline`.

```

1103
1104 \newcommand*{\@set}[1]{%
1105   \ifledRcol
1106     \ifsblines@
1107       \subline@numR=#1\relax
1108     \else
1109       \line@numR=#1\relax
1110     \fi
1111     \set@line@action
1112   \else
1113     \ifsblines@
1114       \subline@num=#1\relax
1115     \else
1116       \line@num=#1\relax
1117     \fi
1118     \set@line@action
1119   \fi}
1120 %
1121 %

```

\l@d@set The `\l@d@set{<num>}` macro sets the line number for the next `\pstart` to the value specified as its argument. This is used to implement `\setlinenum`.

`\l@dchset@num` is a flag to the `\onl?` macro. If it is not `\relax` then a linenumber change is to be done.

```

1122
1123 \newcommand*{\l@d@set}[1]{%
1124   \ifledRcol
1125     \line@numR=#1\relax
1126     \advance\line@numR \one
1127     \def\l@dchset@num{#1}
1128   \else
1129     \line@num=#1\relax
1130     \advance\line@num \one
1131     \def\l@dchset@num{#1}
1132   \fi}
1133 \let\l@dchset@num\relax
1134 %
1135 %

```

\page@action `\page@action` adds an entry to the action-code list to change the page number.

```

1136
1137 \newcommand*{\page@action}{%
1138   \ifledRcol
1139     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1140     \xright@appenditem{\next@page@numR}\to\actions@listR
1141   \else
1142     \xright@appenditem{\the\absline@num}\to\actionlines@list
1143     \xright@appenditem{\next@page@num}\to\actions@list
1144   \fi
1145 %

```

\set@line@action \set@line@action adds an entry to the action-code list to change the visible line number.

```

1146
1147 \newcommand*{\set@line@action}{%
1148   \ifledRcol
1149     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1150     \ifsblines@
1151       @l@dtempcnta=\subline@numR
1152     \else
1153       @l@dtempcnta=\line@numR
1154     \fi
1155     \advance@l@dtempcnta by -5000\relax
1156     \xright@appenditem{\the@l@dtempcnta}\to\actions@listR
1157   \else
1158     \xright@appenditem{\the\absline@num}\to\actionlines@list
1159     \ifsblines@
1160       @l@dtempcnta=\subline@num
1161     \else
1162       @l@dtempcnta=\line@num
1163     \fi
1164     \advance@l@dtempcnta by -5000\relax
1165     \xright@appenditem{\the@l@dtempcnta}\to\actions@list
1166   \fi
1167 %

```

\sub@action \sub@action adds an entry to the action-code list to turn sub-lineation on or off, according to the current value of the \ifsblines@ flag.

```

1168
1169 \newcommand*{\sub@action}{%
1170   \ifledRcol
1171     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1172     \ifsblines@
1173       \xright@appenditem{-1001}\to\actions@listR
1174     \else
1175       \xright@appenditem{-1002}\to\actions@listR
1176     \fi
1177   \else

```

```

1178   \xright@appenditem{\the\absline@num}\to\actionlines@list
1179   \ifsublines@
1180     \xright@appenditem{-1001}\to\actions@list
1181   \else
1182     \xright@appenditem{-1002}\to\actions@list
1183   \fi
1184 \fi}
1185 %

```

`\lock@on` `\lock@on` adds an entry to the action-code list to turn line number locking on. The `\do@lockon` current setting of the sub-lineation flag tells us whether this applies to line numbers or `\do@lockonL` sub-line numbers.

Adding commands to the action list is slow, and it is very often the case that a lock-on command is immediately followed by a lock-off command in the line-list file, and therefore really does nothing. We use a look-ahead scheme here to detect such pairs, and add nothing to the line-list in those cases.

```

1186 \newcommand*{\lock@on}{\futurelet\next\do@clockon}
1187
1188 \newcommand*{\do@lockon}{%
1189   \ifx\next\lock@off
1190     \global\let\lock@off=\skip@lockoff
1191   \else
1192     \ifledRcol
1193       \do@lockonR
1194     \else
1195       \do@lockonL
1196     \fi
1197   \fi}
1198
1199 \newcommand*{\do@lockonL}{%
1200   \xright@appenditem{\the\absline@num}\to\actionlines@list
1201   \ifsublines@
1202     \xright@appenditem{-1005}\to\actions@list
1203     \ifnum\sub@clock=\z@
1204       \sub@lock \@ne
1205     \else
1206       \ifnum\sub@clock=\thr@@
1207         \sub@lock \@ne
1208       \fi
1209     \fi
1210   \fi
1211   \else
1212     \xright@appenditem{-1003}\to\actions@list
1213     \ifnum@\clock=\z@
1214       \@clock \@ne
1215     \else
1216       \ifnum@\clock=\thr@@
1217         \@clock \@ne

```

```

1218      \fi
1219      \fi
1220      \fi}
1221
1222 %

```

```

\lock@off  \lock@off adds an entry to the action-code list to turn line number locking off.
\do@clockoff
\do@lockoffL1223 \newcommand*{\do@lockoffL}{%
\do@lockoff1224 \xright@appenditem{\the\absline@num}\to\actionlines@list
\skip@clockoff1225 \ifsublines@
    \xright@appenditem{-1006}\to\actions@list
    \ifnum\sub@clock=\tw@%
        \sub@clock \thr@@
    \else
        \sub@clock \z@%
    \fi
\else
    \xright@appenditem{-1004}\to\actions@list
    \ifnum@\clock=\tw@%
        @clock \thr@@
    \else
        @clock \z@%
    \fi
\fi}
1239 \fi}

1240 \newcommand*{\do@lockoff}{%
1241     \reset@current@annot%
1242     \ifledRcol
1243         \do@lockoffR
1244     \else
1245         \do@lockoffL
1246     \fi}
1248 \newcommand*{\skip@clockoff}{\global\let\lock@off=\do@lockoff}
1249 \global\let\lock@off=\do@lockoff
1250
1251 %

```

\n@num These macros implement the \skipnumbering command. They use action code 1007.

```

1252 \newcommand*{\n@num}{%
1253     \ifledRcol%
1254         \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1255         \xright@appenditem{-1007}\to\actions@listR
1256     \else%
1257         \xright@appenditem{\the\absline@num}\to\actionlines@list%
1258         \xright@appenditem{-1007}\to\actions@list%
1259     \fi%
1260 }%

```

```
1261 %
1262 %
```

\n@num@stanza This macro implements the \skipnumbering for stanza command. It uses action code 1008.

```
1263 \newcommand*{\n@num@stanza}{%
1264   \ifledRcol%
1265     \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1266     \xright@appenditem{-1008}\to\actions@listR%
1267   \else%
1268     \xright@appenditem{\the\absline@num}\to\actionlines@list%
1269     \xright@appenditem{-1008}\to\actions@list%
1270   \fi%
1271 }
1272 %
```

\ifl@dhidenumber \hidenumbering hides number in margin. It uses action code 1009. \hidenumberingonleftpage and \hidenumberingonrightpage are variant, using action code only conditionnaly

```
\hidenumberingonleftpage
\hidenumberingonrightpage73 \newif\ifl@dhidenumber
1274 \newcommand*{\hidenumbering}{%
1275   \ifledRcol%
1276     \write\linenum@outR{\string\hide@num}%
1277   \else%
1278     \write\linenum@out{\string\hide@num}%
1279   \fi%
1280 }%
1281 \newcommand*{\hide@num}{%
1282   \ifledRcol%
1283     \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1284     \xright@appenditem{-1009}\to\actions@listR%
1285   \else%
1286     \xright@appenditem{\the\absline@num}\to\actionlines@list%
1287     \xright@appenditem{-1009}\to\actions@list%
1288   \fi%
1289 }
1290 \newcommand*{\hidenumberingonleftpage}{%
1291   \ifledRcol%
1292     \write\linenum@outR{\string\hide@num@left}%
1293   \else%
1294     \write\linenum@out{\string\hide@num@left}%
1295   \fi%
1296 }%
1297 \newcommand*{\hide@num@left}{%
1298   \ifledRcol%
1299     \ifodd\page@numR\else%
1300       \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
```

```

1302     \xright@appenditem{-1009}\to\actions@listR%
1303     \fi%
1304 \else%
1305     \ifodd\page@num\else%
1306         \xright@appenditem{\the\absline@num}\to\actionlines@list%%
1307         \xright@appenditem{-1009}\to\actions@list%
1308     \fi%
1309 \fi%
1310 }%
1311
1312 \newcommand*{\hidenumberingonrightpage}{%
1313     \ifledRcol%
1314         \write\linenum@outR{\string\hide@num@right}%
1315     \else%
1316         \write\linenum@out{\string\hide@num@right}%
1317     \fi%
1318 }%
1319
1320 \newcommand*{\hide@num@right}{%
1321     \ifledRcol%
1322         \ifodd\page@numR%
1323             \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1324             \xright@appenditem{-1009}\to\actions@listR%
1325         \fi%
1326     \else%
1327         \ifodd\page@num%
1328             \xright@appenditem{\the\absline@num}\to\actionlines@list%%
1329             \xright@appenditem{-1009}\to\actions@list%
1330         \fi%
1331     \fi%
1332 }%
1333 %
1334 %

```

\@ref \@ref marks the start of a passage, for creation of a footnote reference. It takes two arguments:

- #1, the number of entries to add to \insertlines@list for this reference. This value, here and within \edtext, which computes it and writes it to the line-list file, will be stored in the count \insert@count.

```

1335 \newcount\insert@count
1336 %

```

- #2, a sequence of other line-list-file commands, executed to determine the ending line-number. (This may also include other \@ref commands, corresponding to uses of \edtext within the first argument of another instance of \edtext.)

\dummy@ref When nesting of \@ref commands does occur, it is necessary to temporarily redefine \@ref within \@ref, so that we are only doing one of these at a time.

```

1337 \newcommand*{\dummy@ref}[2]{#2}
1338 %

```

\@ref@reg The first thing \@ref (i.e. \@ref@reg) itself does is to add the specified number of items to the \insertlines@list list.

```

1339 \newcommand*{\@ref}[2]{%
1340   \ifldRcol%
1341     \@ref@regR{#1}{#2}%
1342   \else%
1343     \@ref@reg{#1}{#2}%
1344   \fi%
1345 }%
1346 \newcommand*{\@ref@reg}[2]{%
1347   \global\insert@count=#1\relax
1348   \global\advance\@edtext@level by 1%
1349   \loop\ifnum\insert@count>\z@
1350     \xright@appenditem{\the\absline@num}\to\insertlines@list
1351     \global\advance\insert@count \m@ne
1352   \repeat
1353 %

```

Next, process the second argument to determine the page and line numbers for the end of this lemma. We temporarily equate \@ref to a different macro that just executes its argument, so that nested \@ref commands are just skipped this time. Some other macros need to be temporarily redefined to suppress their action.

```

1354 \begin{group}
1355   \let\@ref=\dummy@ref
1356   \let\@lopL@gobble
1357   \let\page@action=\relax
1358   \let\sub@action=\relax
1359   \let\set@line@action=\relax
1360   \let\@lab=\relax
1361   \let\@lemma=\relax%
1362   \let\@sw\@gobblethree%
1363   \let\store@annot@to@absline\@gobble%
1364   #2
1365   \global\endpage@num=\page@num
1366   \global\endline@num=\line@num
1367   \global\endsubline@num=\subline@num
1368   \global\let\endcurrent@annot=\current@annot%
1369 \endgroup
1370 %

```

Now store all the information about the location of the lemma's start and end in \line@list.

```

1371 \xright@appenditem%
1372   {(\the\page@num|\the\line@num|%
1373    \ifsublines@ \the\subline@num \else 0\fi|%

```

```

1374     \the\endpage@num|\the\endline@num|%
1375     \ifsublines@ \the\endsubline@num \else 0\fi}\to\line@list
1376     \xright@appenditem%
1377     {\current@annot|\endcurrent@annot}\to\annot@list%
1378 %

```

And now, call `\@ref@reg@parsearg`, which can be also called by `\@ref@later`

```

1379     \@ref@reg@parse{#2}%
1380 %

```

Decrease edtext level counter.

```

1381     \global\advance\@edtext@level by -1%
1382 }
1383 %

```

`\@ref@reg@parse` The `\@ref@reg@parsearg` command parses the second argument of a `\@ref` or the unique argument of `\@ref@later` written in the auxiliary fill.

First, create a list which stores every second argument of each `\@sw` in this lemma, at this level. Also set the boolean about the use of lemma in this edtext level to false.

```

1384 \newcommand{\@ref@reg@parse}[1]{%
1385   \expandafter\list@create\expandafter{\csname sw@list@edtext@tmp@\the\
1386   @edtext@level\endcsname}%
1387   \providebool{lemmacommand@\the\@edtext@level}%
1388   \boolfalse{lemmacommand@\the\@edtext@level}%
1389 %

```

Execute the second argument of `\@ref` again, to perform for real all the commands within it.

```

1389   #1%
1390 %

```

Now, we store the list of `\@sw` of this current `\@edtext` as an element of the global list of list of `\@sw` for a `\@edtext` depth.

```

1391   \ifnum\@edtext@level>0%
1392     \def\create@this@edtext@level{\expandafter\list@create\expandafter{\
1393       \csname sw@list@edtext@\the\@edtext@level\endcsname}%
1394     \ifcsundef{sw@list@edtext@\the\@edtext@level}{\create@this@edtext@level
1395     }{%
1396       \letcs{\@tmp}{sw@list@edtext@\the\@edtext@level}%
1397       \letcs{\@tmpp}{sw@list@edtext@tmp@\the\@edtext@level}%
1398       \xright@appenditem{\expandonce{\@tmpp}}{\@tmp}%
1399       \global\cslet{sw@list@edtext@\the\@edtext@level}{\@tmp}%
1400     }%
1401 %

```

\ref@reg@later This macro is stored in the auxiliary file when using \edtextlater. It is used only to get the correct value for the \sameword tools.

```

1403 \newcommand{\@ref@later}[1]{%
1404   \global\advance\edtext@level by \one%
1405   \ifledRcol%
1406     \gref@reg@parseR{#1}%
1407   \else%
1408     \gref@reg@parse{#1}%
1409   \fi%
1410   \global\advance\edtext@level by -\one%
1411 }%
1412 %

```

V.12 Writing to the line-list file

We have now defined all the counters, lists, and commands involved in reading the line-list file at the start of a section. Now we will cover the commands that reledmac uses within the text of a section to write commands out to the line-list.

\linenum@out The file will be opened on output stream \linenum@out.

```

1413 \newwrite\linenum@out
1414 %

```

\iffirst@linenum@out@ \first@linenum@out@true \first@linenum@out@false Once any file is opened on this stream, we keep it open forever, or else switch to another file that we keep open. The reason is that we want the output routine to write the page number for every page to this file; otherwise we would have to write it at the start of every line. But it is not very easy for the output routine to tell whether an output stream is open or not. There is no way to test the status of a particular output stream directly, and the asynchronous nature of output routines makes the status hard to determine by other means.

We can manage pretty well by means of the \iffirst@linenum@out@ flag; its inelegant name suggests the nature of the problem that made its creation necessary. It is set to be true before any \linenum@out file is opened. When such a file is opened for the first time, it is done using \immediate, so that it will at once be safe for the output routine to write to it; we then set this flag to false.

```

1415 \newif\iffirst@linenum@out@
1416   \first@linenum@out@true
1417 %

```

\this@line@list@version The commands allowed in the line-list file and their arguments can change between two version of reledmac. The \this@line@list@version command is upgraded when it happens. It is written in the file list. If we process a line-list file which used a older version, that means the commands used inside are deprecated, and we can't use them.

```

1418 \newcommand{\this@line@list@version}{7}%
1419 %

```

`\line@list@stuff` The `\line@list@stuff{<file>}` macro, which is called by `\beginnumbering`, performs all the line-list operations needed at the start of a section. Its argument is the name of the line-list file.

```
1420 \let\next@line@list@stuff\relax%
1421 \newcommand*\line@list@stuff[1]{%
1422 %
```

First, define a toggle set to true when we are not in the first run.

```
1423 \global\newtoggle{notfirstrun@#1}%
1424 \IfFileExists{\l@auxdir#1}{%
1425   \global\toggletrue{notfirstrun@#1}%
1426   \global\togglefalse{notfirstrun@#1}%
1427 %
```

A internal hook (not used yet).

```
1428 \next@line@list@stuff%
1429 \global\let\next@line@list@stuff\relax%
1430 %
```

Use the commands of the previous section to interpret the line-list file from the last run.

```
1431 \read@linelist{#1}%
1432 %
```

Now close the current output line-list file, if any, and open a new one. The first time we open a line-list file for output, we do it using `\immediate`, and clear the `\iffirst@linenum@out@` flag. `reledmac` and `reledpar` can fill the `\next@line@list@stuff` hook between a `\endnumbering` (associated with numbered file n) and a `\beginnumbering` (associated with numbered file $n + 1$). It allows adding content to the numbered file $n + 1$ and not n .

```
1433 \iffirst@linenum@out@
1434   \global\first@linenum@out@false%
1435   \immediate\openout\linenum@out=\l@auxdir#1\relax%
1436   \immediate\write\linenum@out{\string\line@list@version{\%
1437     this@line@list@version}}%
1438   \ifl@dpaging%
1439     \immediate\write\linenum@out{\string\@par@sync@option{\%
1440       @par@this@sync@option}}%
1441   \fi%
1442 \else
1443 %
```

If we get here, then this is not the first line-list we have seen, so we do not open or close the files immediately.

```
1442 \if@minipage%
1443   \leavevmode%
1444   \fi%
1445   \closeout\linenum@out%
1446   \openout\linenum@out=\l@auxdir#1\relax%
```

```
1447 \write\linenum@out{\string\line@list@version{\this@line@list@version}}
%
1448 \ifl@dpaging%
1449   \write\linenum@out{\string\@par@sync@option{\@par@this@sync@option}}
%
1450   \fi%
1451 \fi%
1452 }%
1453 %
1454 %
```

`\new@line` The `\new@line` macro sends the `\@nl` command to the line-list file, to mark the start of
`\l@the@cc@page` a new text line, and its page number. It writes the two forms of the page number:

- Raw form (`\the\c@page`, which can be used for numeric tests).
 - Formatted form (for example, in Roman).

Actually, only the first form is used by `\onl`. If we use the `\sameparallelpagenumber` option of `reledpar`, we must write not the real page number (i.e. page counter, defined in standard L^AT_EX) but the printed page number (i.e. `par@page` counter, defined only on `reledmac`).

- For the raw form, we use `\the\c@page` macro, because the `\par@page` counter is increased for each page.
 - For the formatted version, `\thepage` is patched through `\par@patch@thepage`. So we have nothing to change.

```

1455 \newcommand*{\new@line}{%
1456   \ifnumberline%
1457     \IfStrEq{\led@pb@setting}{after}%
1458       {\xifinlist{\the\absline@num}{\l@prev@nopb}%
1459        {\xifinlist{\the\absline@num}{\normal@page@break}%
1460          {\numgdef{\next@page}{\c@par@page+\@ne}%
1461            \write\linenum@out{\string\@nl[\next@page] [\next@page]}%
1462          }%
1463          {\write\linenum@out{\string\@nl[\the\c@par@page] [\thepage]}%
1464        }%
1465        {\write\linenum@out{\string\@nl[\the\c@par@page] [\thepage]}}}}%
1466   }%
1467   \IfStrEq{\led@pb@setting}{before}%
1468     {\numdef{\next@absline}{\the\absline@num+\@ne}%
1469      \xifinlist{\next@absline}{\l@prev@nopb}%
1470        {\xifinlist{\the\absline@num}{\normal@page@break}%
1471          {\numgdef{\nc@page}{\c@par@page+\@ne}%
1472            \write\linenum@out{\string\@nl[\nc@page] [\nc@page]}%
1473          }%
1474          {\write\linenum@out{\string\@nl[\the\c@par@page] [\thepage]}}}}%
1475   }%

```

```

1476      {\write\linenum@out{\string\nl[\the\c@par@page] [\thepage]}}%
1477  }%
1478  {}%
1479  \IfStrEqCase{\led@pb@setting}%
1480  {%
1481    {before}{\relax}%
1482    {after}{\relax}%
1483  }{%
1484    \write\linenum@out{\string\nl[\the\c@par@page] [\thepage]}}%
1485  }%
1486  \fi%
1487 }
1488
1489 \newcommand{\l@the@c@page}{%
1490   \ifboolexpr{%
1491     bool{sameparallelpagenumber}%
1492     or bool{prevpgnotnumbered}%
1493   }{%
1494     {\the\c@par@page}%
1495     {\the\c@page}%
1496   }%
1497 }
1498 %

```

\if@noneed@Footnote \if@noneed@Footnote is a boolean to check if we have to print a error message when a \edtext is called without any critical notes.

\flag@start We enclose a lemma marked by \edtext in \flag@start and \flag@end: these send
\flag@end the \ref command to the line-list file. \edtext is responsible for setting the value of
\insert@count appropriately; it actually gets done by the various footnote macros.

```

1498 \newif\if@noneed@Footnote%
1499
1500 \newcommand*\flag@start}{%
1501   \ifledRcol{%
1502     \edef\next{\write\linenum@outR{%
1503       \string\@ref[\the\insert@countR] []}}%
1504     \next%
1505     \ifnum\insert@countR<1%
1506       \if@noneed@Footnote\else%
1507         \led@err@EdtextWithoutFootnote%
1508       \fi%
1509     \fi%
1510   \else%
1511     \edef\next{\write\linenum@out{%
1512       \string\@ref[\the\insert@count] []}}%
1513     \next%
1514     \ifnum\insert@count<1%
1515       \if@noneed@Footnote\else%
1516         \led@err@EdtextWithoutFootnote%
1517       \fi%

```

```

1518   \fi%
1519 \fi}%
1520
1521 \newcommand*{\flag@end}{%
1522   \ifledRcol%
1523     \write\linenum@outR[]}%
1524   \else%
1525     \write\linenum@out[]}%
1526   \fi}%
1527
1528 %
1529 %

```

\flag@start@RTL With X_ET_EX, there is a problem when using RTL: the writing of a command in the numbered auxiliary files (.1, .2 etc) is reversed when the first argument of \edtext is typeset in one line, but it is **not** reversed when this first argument is typeset in two lines or more.²⁸

To solve this problem, we use a crossref mechanism. At the first run, we put a label, but we do not write any \cref command. When the value of the label can be tested, that is after three runs, we're doing:

- If the first argument of \edtext is typeset on only one line, we first call \flag@end, at the point we normally call \flag@start, at the beginning of the content of the first argument, and we call \flag@end at the point we normally call \flag@start, at the end of the content of the first argument.
- If the first argument of \edtext is typeset on only two lines, we use the normal order.

This system is a workaround for the problem of order when writing in auxiliary files.

The \flag@start@RTL and \flag@end@RTL macro put the label, do the test and call the right commands.

```

1530 \newcommand{\flag@start@RTL}{%
1531   \edlabel{\edtext:start:\csuse{thisedtext@\the\@edtext@level}}%
1532   \IfStrEq{\xabslineref{\edtext:start:\csuse{thisedtext@\the\@edtext@level}}}{%
1533     {000}}%
1534     {}%
1535     {}%
1536   \ifnumequal{%
1537     {\xabslineref{\edtext:start:\csuse{thisedtext@\the\@edtext@level}}}}{%
1538     {\xabslineref{\edtext:end:\csuse{thisedtext@\the\@edtext@level}}}}{%
1539     {\flag@end}}%
1540     {\flag@start}}%

```

²⁸This problem is caused by the way X_ET_EX manages right-to-left typesetting. David Carlisle explains it on <http://tex.stackexchange.com/a/333373/7712> and provides a potential solution, using \vadjust. However in some cases this adds spurious vertical spaces in reledmac. That is why we are using the solution explained below.

```

1541      }%
1542  }%
1543
1544 \newcommand{\flag@end@RTL}{%
1545   \edlabel{edtext:end:\csuse{thisedtext@\the\@edtext@level}}%
1546   \IfStrEq{\xabslineref{edtext:start}:\csuse{thisedtext@\the\@edtext@level}
1547   }{}}%
1548   {000}%
1549   {}%
1550   {}%
1551   \ifnumequal{%
1552     \xabslineref{edtext:start:\csuse{thisedtext@\the\@edtext@level}}}{%
1553     \xabslineref{edtext:end:\csuse{thisedtext@\the\@edtext@level}}}{%
1554     {\flag@start}%
1555     {\flag@end}%
1556   }%
1557 }%
1558 %

```

\flag@start@later \flag@start@later and \flag@end@later: these send the \ref@later to the line-list file command to the line-list file

```

1558 \newcommand*{\flag@start@later}{%
1559   \ifledRcol%
1560     \write\linenum@outR{\string\@ref@later[]}%
1561   \else%
1562     \write\linenum@out{\string\@ref@later[]}%
1563   \fi%
1564 }%
1565 \newcommand{\flag@end@later}{%
1566   \ifledRcol%
1567     \write\linenum@outR{}%
1568   \else%
1569     \write\linenum@out{}%
1570   \fi%
1571 }
1572 %

```

\startsub \startsub and \endsub turn sub-lineation on and off, by writing appropriate instructions to the line-list file. When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it does not take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if that changes in the middle.

We tinker with \lastskip because a command of either sort really needs to be attached to the last word preceding the change, not the first word that follows the change. This is because sub-lineation will often turn on and off in mid-line—stage directions, for example, often are mixed with dialogue in that way—and when a line is mixed we want

to label it using the system that was in effect at its start. But when sub-lineation begins at the very start of a line we have a problem, if we don't put in this code.

```

1573
1574
1575 \newcommand*{\startsub}{\dimen0\lastskip
1576   \ifdim\dimen0>0pt \unskip \fi
1577   \ifledRcol \write\linenum@outR{\string\sub@on}%
1578   \else      \write\linenum@out{\string\sub@on}%
1579   \fi
1580   \ifdim\dimen0>0pt \hskip\dimen0 \fi}
1581 \def\endsub{\dimen0\lastskip
1582   \ifdim\dimen0>0pt \unskip \fi
1583   \ifledRcol \write\linenum@outR{\string\sub@off}%
1584   \else      \write\linenum@out{\string\sub@off}%
1585   \fi
1586   \ifdim\dimen0>0pt \hskip\dimen0 \fi}
1587
1588 %

```

\advanceline You can use `\advanceline{<num>}` in running text to advance the current visible line-number by a specified value, positive or negative.

```

1589 \newcommand*{\advanceline}[1]{\leavevmode%
1590   \ifledRcol \write\linenum@outR{\string@\adv[#1]}%
1591   \else      \write\linenum@out{\string@\adv[#1]}%
1592   \fi%
1593 }
1594 %

```

\setline You can use `\setline{<num>}` in running text (i.e., within `\pstart...\\pend`) to set the current visible line-number to a specified positive value.

```

1595
1596 \newcommand*{\setline}[1]{%
1597   \leavevmode%
1598   \ifnum#1<\z@%
1599     \led@warn@BadSetline%
1600   \else%
1601     \ifledRcol%
1602       \write\linenum@outR{\string@\set[#1]}%
1603     \else%
1604       \write\linenum@out{\string@\set[#1]}%
1605     \fi%
1606   \fi%
1607 }%
1608
1609 %

```

\setlinenum You can use `\setlinenum{<num>}` before a `\pstart` to set the visible line-number to a specified positive value. It writes a `\l@d@set` command to the line-list file.

```

1610
1611 \newcommand*{\setlinenum}[1]{%
1612   \ifnum#1<\z@
1613     \led@warn@BadSetlinenum
1614   \else
1615     \ifledRcol \write\linenum@outR{\string\l@d@set[#1]}
1616     \else      \write\linenum@out{\string\l@d@set[#1]} \fi
1617   \fi}
1618
1619 %

```

\startlock You can use `\startlock` or `\endlock` in running text to start or end line number locking at the current line. They decide whether line numbers or sub-line numbers are affected, depending on the current state of the sub-lineation flags.

```

1620
1621 \newcommand*{\startlock}{%
1622   \ifledRcol \write\linenum@outR{\string\lock@on}%
1623   \else      \write\linenum@out{\string\lock@on}%
1624   \fi}
1625 \def\endlock{%
1626   \ifledRcol \write\linenum@outR{\string\lock@off}%
1627   \else      \write\linenum@out{\string\lock@off}%
1628   \fi}
1629 %

```

\ifl@dskipnumber In numbered text `\skipnumbering` will suspend the numbering for that particular line.
\ifl@dskipversenumber

```

1630 \newif\ifl@dskipnumber
1631 \newif\ifl@dskipversenumber%
1632 \skipnumbering \newcommand*{\skipnumbering}{%
1633   \leavevemode%
1634   \ifledRcol%
1635     \ifinstanza%
1636       \write\linenum@outR{\string\n@num@stanza}%
1637     \else%
1638       \write\linenum@outR{\string\n@num}%
1639     \fi%
1640     \advanceline{-1}%
1641   \else%
1642     \ifinstanza%
1643       \write\linenum@out{\string\n@num@stanza}%
1644     \else%
1645       \write\linenum@out{\string\n@num}%
1646     \fi%
1647     \advanceline{-1}%
1648   \fi%
1649 }%
1650

```

VI **Marking text for notes**

The `\edtext` macro is used to create all footnotes and endnotes, as well as to print the portion of the main text to which a given note or notes is keyed. The idea is to have that lemma appear only once in the `.tex` file: all instances of it in the main text and in the notes are copied from that one appearance.

The `\edtext` macro takes two arguments.

```
\edtext{#1}{#2}
```

- #1 is the piece of the main text being glossed; it gets added to the main text, and is also used as a lemma for notes to it.
- #2 is a series of subsidiary macros that generate various kinds of notes.

The `\edtext` macro may be used (somewhat) recursively; that is, `\edtext` may be used within its own first argument. The code would be much simpler without this feature, but nested notes will commonly be necessary: it is quite likely that we will have an explanatory note for a long passage and notes on variants for individual words within that passage. The situation we can't handle is overlapping notes that are not nested: for example, one note covering lines 10–15, and another covering 12–18. You can handle such cases by using the `\lemma` and `\linenum` macros within #2: they alter the copy of the lemma and the line numbers that are passed to the notes, and hence allow you to overcome any limitations of this system, albeit with extra effort.

The recursive operation of `\edtext` will fail if you try to use a copy that is called something other than `\edtext`. In order to handle recursion, `\edtext` needs to redefine its own definition temporarily at one point, and that does not work if the macro you are calling is not actually named `\edtext`. There is no problem as long as `\edtext` is not invoked in the first argument. If you want to call `\edtext` something else, it is best to create instead a macro that expands to an invocation of `\edtext`, rather than copying `\edtext` and giving it a new name; otherwise you will need to add an appropriate definition for your new macro to `\morenoexpands`.

Side-effects of our line-numbering code make it impossible to use the usual footnote macros directly within a paragraph whose lines are numbered (see comments to `\do@line`, VII.2.1 p. 158). Instead, the appropriate note-generating command is appended to the list macro `\inserts@list`, and when `\pend` completes the paragraph it inserts all the notes at the proper places.

Note that we do not provide previous-note information, although it is often wanted; your own macros must handle that. We can not do it correctly without keeping track of what kind of notes have gone past: it is not just a matter of remembering the line numbers associated with the previous invocation of `\edtext`, because that might have been for a different kind of note. It is preferable for your footnote macros to store and recall this kind of information if they need it.

VI.1 \edtext itself

The various note-generating macros might want to request that commands be executed not at once, but in close connection with the start or end of the lemma. For example, footnote numbers in the text should be connected to the end of the lemma; or, instead of a single macro to create a note listing variants, you might want to use several macros in series to create individual variants, which would each add information to a private macro or token register, which in turn would be formatted and output when all of #2 for the lemma has been read.

\end@lemmas To accomodate this, we provide a list macro to which macros may add commands that should subsequently be executed at the end of the lemma when that lemma is added to the text of the paragraph. A macro should add its contribution to `\end@lemmas` by using `\xleft@appenditem`. (Anything that needs to be done at the *start* of the lemma may be handled using `\aftergroup`, since the commands specified within `\edtext`'s second argument are executed within a group that ends just before the lemma is added to the main text.)

`\end@lemmas` is intended for the few things that need to be associated with the end of the lemma, like footnote numbers. Such numbers are not implemented in the current version, and indeed no use is currently made of `\end@lemmas` or of the `\aftergroup` trick. The general approach would be to define a macro to be used within the second argument of `\edtext` that would add the appropriate command to `\end@lemmas`.

Commands that are added to this list should always take care not to do anything that adds possible line-breaks to the output; otherwise line numbering could be thrown off.

```
1652 \list@create{\end@lemmas}
1653 %
```

\dummy@edtext We now need to define a number of macros that allow us to weed out nested instances of `\edtext`, and other problematic macros, from our lemma. This is similar to what we did in reading the line-list file using `\dummy@ref` and various redefinitions—and that is because nested `\edtexts` macros create nested `\ref` entries in the line-list file.

```
1654 \newcommand{\dummy@edtext}[2]{#1}
1655 %
```

\dummy@edtext@showlemma Some time, we want to obtain only the first argument of `\edtext`, while also wrapping it in `\showlemma`. For example, when printing a `\eledsection`.

```
1656 \newcommand{\dummy@edtext@showlemma}[2]{\showlemma{#1}}%
1657 %
```

We are going to need another macro that takes one argument and ignores it entirely. This is supplied by the L^AT_EX `\@gobble{\langle arg\rangle}`.

\no@expands We need to turn off macro expansion for certain sorts of macros we are likely to see
\morenoexpands within the lemma and within the notes.

The first class is font-changing macros. We suppress expansion for them by letting them become equal to zero.²⁹ This is done because we want to pass into our notes the generic commands to change to roman or whatever, and not their expansions that will ask for a particular style at a specified size. The notes may well be in a smaller font, so the command should be expanded later, when the note's environment is in effect.

A second sort to turn off includes a few of the accent macros. Most are not a problem: an accent that is expanded to an \accent command may be harder to read but it works just the same. The ones that cause problems are: those that use alignments— \TeX seems to get confused about the difference between alignment parameters and macro parameters; those that use temporary control sequences; and those that look carefully at what the current font is.

(The \copyright macro defined in PLAIN \TeX has this sort of problem as well, but is not used enough to bother with. That macro, and any other that causes trouble, will get by all right if you put a \protect in front of it in your file.)

We also need to eliminate all `reledmac` macros like `\edlabel` and `\setline` that write things to auxiliary files: that writing should be done only once. And we make `\edtext` itself, if it appears within its own argument, do nothing but copy its first argument.

Finally, we execute `\morenoexpands`. The version of `\morenoexpands` defined here does nothing; but you may define a version of your own when you need to add more expansion suppressions as needed with your macros. That makes it possible to make such additions without needing to copy or modify the standard `reledmac` code. If you define your own `\morenoexpands`, you must be very careful about spaces: if the macro adds any spaces to the text when it runs, extra space will appear in the main text when `\edtext` is used.

The `\new@series` command also adds `\let\footnote{X}\@gobble` to the end of the `\no@expands` macro for the series `{X}`.

(A related problem, not addressed by these two macros, is that of characters whose category code are changed by any of the macros used in the arguments to `\edtext`. Since the category codes are set when the arguments are scanned, macros that depend on changing them will not work. We have most often encountered this with characters that are made ‘active’ within text in some, but not all, of the languages used within the document. One way around the problem, if it takes this form, is to ensure that those characters are *always* active. Within languages that make no special use of them, their associated control sequences should simply return the proper character. A simpler solution is to avoid active characters, using `LuaTeX` or `XeTeX`.)

```

1658 \newcommand*{\no@expands}{%
1659   \let\select@Olemmafont=0%
1660   \let\startsub=\relax \let\endsub=\relax
1661   \let\startlock=\relax \let\endlock=\relax
1662   \let\edlabel=\@gobble
1663   \let\setline=\@gobble \let\advanceline=\@gobble
1664   \let\sameword\sameword@inedtext%
1665   \let\edtext=\dummy@edtext

```

²⁹Since ‘control sequences equivalent to characters are not expandable’—*The TeXbook*, answer to Exercise 20.14.

```

1666   \let\edindex\dummy@edindex%
1667   \l@dtabnoexpands
1668   \let\linenumannotation=\@gobble%
1669   \morenoexpands}
1670 \let\morenoexpands=\relax
1671 %
1672 %

```

\@tag Now, we define an empty \@tag command. It will be redefine by \edtext: its value is the first argument. It will be used by the \Xfootnote commands.

```

1673 \newcommand{\@tag}{}
1674 %

```

\@edtext@level This counter is increased by 1 at each level of \edtext.

```

1675 \newcount\@edtext@level%
1676 \@edtext@level=0%
1677 %

```

\if@edtext@secondarg@ This boolean is set to TRUE before reading the second argument of a \edtext. It is tested on some macro which must be executed only inside a second argument.

```

1678 \newif\if@edtext@secondarg@
1679 %

```

\theedtext The edtext counter is increased at each \edtext command. It is used to insert hyperlinks between a notes and the lemma.

```

1680 \newcounter{edtext}
1681 \renewcommand{\theedtext}{\edtxt@\arabic{edtext}}%
1682 %

```

\edtext When executed, \edtext first ensures that we are in horizontal mode.

```

1683 \newcommand{\edtext}[2]{\leavevmode%
1684 %

```

Then, check if we are in a numbered paragraph (\pstart... \pend)..

```

1685 \ifnumberedpar@%
1686 %

```

Check the content of the arguments, to be certain there is no forbidden command inside.

```

1687 \@check@edtext@args{\#1}{\#2}%
1688 %

```

We increment the \@edtext@level \TeX counter to know in which level of \edtext we are.

```

1689 \global\advance\@edtext@level by 1%
1690 %

```

We also increase the `\edtext` L^AT_EX counter to insert a hypertarget if the `hyperref` package is loaded, and also works with `\edtext` on right-to-left typesetting with X_L^AT_EX.

We store the value for the current level in a global macro. So we have one macro by level of `\edtext`. That is required, because `\edtext` can contain `\edtext`.

```

1691 \stepcounter{\edtext}%
1692 \csxdef{thisedtext@\the\@edtext@level}{\theedtext}%
1693 %

```

By default, we do not use `\lemma`

```

1694 \global\@lemmacommand@false%
1695 %

```

```

1696 \begingroup%
1697 %

```

We get the next series of samewords data in the list of samewords data for the current `\edtext` level. We push them inside `\sw@inthisedtext`.

```

1698 \ifledRcol%
1699 \ifcscvoid{sw@list@edtextR@\the\@edtext@level}%
1700   {\global\let\sw@inthisedtext\empty}%
1701   {\expandafter\gl@p\csname sw@list@edtextR@\the\@edtext@level\endcsname\to\sw@inthisedtext}%
1702 \else%
1703   \ifcscvoid{sw@list@edtext@\the\@edtext@level}%
1704     {\global\let\sw@inthisedtext\empty}%
1705     {\expandafter\gl@p\csname sw@list@edtext@\the\@edtext@level\endcsname\to\sw@inthisedtext}%
1706   \fi%
1707 %

```

\@tag Our normal lemma is just argument #1; but that argument could have further invocations of `\edtext` within it. We get a copy of the lemma without any `\edtext` macros within it by temporarily redefining `\edtext` to just copy its first argument and ignore the other, and then expand #1 into `\@tag`, our lemma.

This is done within a group that starts here, in order to get the original `\edtext` restored; within this group we have also turned off the expansion of those control sequences commonly found within text that can cause trouble for us.

```

1708 \global\renewcommand{\@tag}{%
1709   \noexpand\expands #1}%
1710 }%
1711 %

```

\l@d@nums Prepare more data for the benefit of note-generating macros: the line references and font specifier for this lemma go to `\l@d@nums`.

```
1712     \set@line%
1713     %
```

\insert@count will be altered by the note-generating macros: it counts the number of deferred footnotes or other insertions generated by this instance of \edtext. If we are in a right column (`reledpar`), we use \insert@countR instead of \insert@count.

```
1714     \ifledRcol \global\insert@countR \z@%
1715     \else      \global\insert@count \z@ \fi%
1716     %
```

Now process the note-generating macros in argument #2 (i.e., \Afootnote, \lemma, etc.). \ignorespaces is here to skip over any spaces that might appear at the start of #2; otherwise they wind up in the main text. Footnote and other macros that are used within #2 should all end with \ignorespaces as well, to skip any spaces between macros when several are used in series.

```
1717     \cedtext@secondarg@true%
1718     \ignorespaces #2\relax%
1719     \cedtext@secondarg@false%
1720     %
```

With X_ET_EX, you must track whether the language reads left to right (English) or right to left (Arabic). `reledmac` defines an \if@RTL boolean test is not already defined.

```
1721     \if@RTL%
1722     \flag@start@RTL%
1723     \else%
1724     \flag@start%
1725     \fi%
1726     %
```

We write in the numbered file wether the current \edtext has a \lemma in the the second argument.

```
1727     \if@lemmacommand@%
1728     \ifledRcol%
1729     \write\linenum@outR{\string\@lemma}%
1730     \else%
1731     \write\linenum@out{\string\@lemma}%
1732     \fi%
1733     \fi%
1734     %
```

Finally, we are ready to admit the first argument into the current paragraph.

It is important that we generate and output all the notes for this chunk of text *before* putting the text into the paragraph: notes that are referenced by line number should generally be tied to the start of the passage they gloss, not the end. That should all be done within the expansion of #2 above, or in \aftergroup commands within that expansion.

```

1735 \endgroup%
1736 \ifdef{\hypertarget}{%
1737   {%
1738     \Hy@raisedlink@left{\hypertarget{\csuse{thisedtext@\the\@edtext@level}:start}{}}%
1739     \showlemma{\#1}%
1740     \Hy@raisedlink{\hypertarget{\csuse{thisedtext@\the\@edtext@level}:end}{}}%
1741   }%
1742   {%
1743     \showlemma{\#1}%
1744   }%
1745 %

```

Finally, we add any insertions that are associated with the *end* of the lemma. Footnotes that are identified by symbols rather than by where the lemma begins in the main text need to be done here, and not above.

```

1746 \ifx\end@lemmas\empty \else%
1747   \gl@p\end@lemmas\to\x@lemma%
1748   \x@lemma%
1749   \global\let\x@lemma=\relax%
1750 \fi%
1751 \if@RTL%
1752   \flag@end@RTL%
1753 \else%
1754   \flag@end%
1755 \fi%
1756 %

```

We switch some flags to false.

- The one that checks having footnotes inside a `\edtext`.
- The one that says we are inside a `\edtext`. In fact, it is not a flag, but a counter which is increased to 1 in each level of `\edtext`.
- The one that says we are inside a `\@lemma`.

```

1757 \global\@noneed@Footnotefalse%
1758 \global\advance\@edtext@level by -1%
1759 \global\@lemma@command@false%
1760 %

```

We also reset `\@beforeinsertofthisedtext`

```

1761 \global\let\@beforeinsertofthisedtext\relax%
1762 %

```

If we are outside of a numbered paragraph, we send an error message and print the first argument.

```

1763     \else%
1764     \showlemma{\#1} {(\textbf{\textsf{Edtext outside numbered paragraph}})}\%
1765     \led@err@edtextoutsidepstart%
1766   }%
1767
1768 %
1769 %

```

\@check@edtext@args A macro which just checks the arguments of the \edtext and let know if there is some probleme, like, for example, \pstart inside.

```

1770 \newcommand{\@check@edtext@args}[2]{%
1771   \begingroup%
1772   \noexpandarg%
1773   \IfSubStr{\#1}{\pstart}{\led@err@PstartInEdtext{first}}{}%
1774   \IfSubStr{\#1}{\pend}{\led@err@PendInEdtext{first}}{}%
1775   \IfSubStr{\#2}{\pstart}{\led@err@PstartInEdtext{second}}{}%
1776   \IfSubStr{\#2}{\pend}{\led@err@PendInEdtext{second}}{}%
1777   \endgroup%
1778 }%
1779 %
1780 %

```

@beforeinsertofthisedtext \@beforeinsertofthisedtext is an internal macro. `reledmac` or `reledpar` can add in this macro any content required to be executed before doing any \insert related to a \edtext. Its content is \let equal to \relax at the end of every \edtext.

```

1781 \let\@beforeinsertofthisedtext\relax
1782 %

```

\ifnumberline The \ifnumberline option can be set to FALSE to disable line numbering.

```

1783 \newif\ifnumberline
1784 \numberlinetrue
1785 %

```

\set@line The \set@line macro is called by \edtext to put the line-reference field and font specifier for the current block of text into \l@d@nums.

One instance of \edtext may generate several notes, or it may generate none – it is legitimate for argument #2 to \edtext to be empty. But \flag@start and \flag@end induce the generation of a single entry in \line@list during the next run, and it is vital to also remove one and only one \line@list entry here.

If no more lines are listed in \line@list, something is wrong – probably just some change in the input. We set all the numbers to zeros, following an old publishing convention for numerical references that have not yet been resolved.

```

1786 \newcommand*{\set@line}{%
1787   \ifledRcol

```

```

1788 \ifx\line@listR\empty
1789   \global\noteschanged@true
1790   \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
1791 \else
1792   \gl@p\line@listR\to\@tempb
1793   \xdef\l@d@nums{\@tempb|\edfont@info}%
1794   \global\let\@tempb=\undefined
1795 \fi
1796 \ifx\annot@listR\empty%
1797   \xdef\l@current@annotR{|}%
1798 \else%
1799   \gl@p\annot@listR\to\@tempb%
1800   \xdef\l@current@annotR{\@tempb}%
1801   \global\let\@tempb=\undefined%
1802 \fi%
1803 \else
1804   \ifx\line@list\empty
1805     \global\noteschanged@true
1806     \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
1807 \else
1808   \gl@p\line@list\to\@tempb
1809   \xdef\l@d@nums{\@tempb|\edfont@info}%
1810   \global\let\@tempb=\undefined
1811 \fi
1812 \ifx\annot@list\empty%
1813   \xdef\l@current@annot{|}%
1814 \else%
1815   \gl@p\annot@list\to\@tempb%
1816   \xdef\l@current@annot{\@tempb}%
1817   \global\let\@tempb=\undefined%
1818 \fi%
1819 \fi}
1820
1821 %

```

\edfont@info The macro `\edfont@info` returns coded information about the current font.

```

1822 \newcommand*{\edfont@info}{\f@encoding/\f@family/\f@series/\f@shape}
1823
1824 %

```

VI.2 Substitute lemma

\lemma The `\lemma{<text>}` macro allows you to change the lemma that is passed on to the notes. Read about `\@tag` in normal `\edtext` macro for more details about `\sw@list@inedtext` and `\no@expands` (VI.1 p. 138).

```

1825 \newcommand*{\lemma}[1]{%
1826   \global\@lemmacommand@true%

```

```

1827   \global\renewcommand{\@tag}{%
1828     \noexpand\#1%
1829   }%
1830   \ignorespaces%
1831 }%
1832 %

```

\@lemma The `\@lemma` is written in the numbered file to set which `\edtext` has an `\lemma` as second argument.

```

1833 \newcommand{\@lemma}{%
1834   \booltrue{lemmacommand@\the\edtext@level}%
1835 }%
1836 %

```

\if@lemmacommand@ This boolean is set to TRUE inside a `\edtext` (or `\critext`) when a `\lemma` command is called. That is useful for some commands which can have a different behavior if the lemma in the note is different from the lemma in the main text.

```

1837 \newif\if@lemmacommand@
1838 %

```

VI.3 Substitute line numbers

\linenum The `\linenum` macro can change any or all of the page and line numbers that are passed on to the notes.

As argument `\linenum` takes a set of seven parameters separated by vertical bars, in the format used internally for `\l@d@nums` (see V.9 p. 107): the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma. However, you can omit any parameters you do not want to change, and you can omit a string of vertical bars at the end of the argument. Hence `\linenum{18|4|0|18|7|1|0}` is an invocation that changes all the parameters, but `\linenum{|3|}` only changes the starting line number, and leaves the rest unaltered.

We use `\`` as an internal separator for the macro parameters.

```

1839 \newcommand*{\linenum}[1]{%
1840   \xdef\@tempa{\#1|||||\noexpand\\l@d@nums}%
1841   \global\let\l@d@nums=\empty
1842   \expandafter\line@set\@tempa\\\ignorespaces}
1843 %

```

\line@set `\linenum` calls `\line@set` to do the actual work; it looks at the first number in the argument to `\linenum`, sets the corresponding value in `\l@d@nums`, and then calls itself to process the next number in the `\linenum` argument, if there are more numbers in `\l@d@nums` to process.

```

1844 \def\line@set#1#2#3#4\\{%
1845   \gdef\@tempb{\#1}%

```

```

1846 \ifx\@tempb\empty
1847   \l@d@add{#3}%
1848 \else
1849   \l@d@add{#1}%
1850 \fi
1851 \gdef\@tempb{#4}%
1852 \ifx\@tempb\empty\else
1853   \l@d@add{}|\line@set#2\\#4\\%
1854 \fi}
1855 %

```

\l@d@add \line@set uses \l@d@add to tack numbers or vertical bars onto the right hand end of \l@d@nums.

```

1856 \newcommand{\l@d@add}[1]{\xdef\l@d@nums{\l@d@nums#1}}
1857 %
1858 %

```

\lineannot \lineannot@set Last but not least, \lineannot allows us to substitute line number annotation. It is different from \linenum for backward compatibility with older versions of `reledmac`. It calls \lineannot@set to determine whether we must change only one annotation or two, or none.

```

1859 \newcommand*{\lineannot}[1]{%
1860   \lineannot@set#1%
1861 }%
1862 \def\lineannot@set#1#2{%
1863   \expandafter\parse@annot#1#2%
1864   \IfStrEq{#1}{}
1865   {\let\@tempa\annot@start}%
1866   {\def\@tempa{#1}}%
1867   \IfStrEq{#2}{}
1868   {\let\@tempb\annot@start}%
1869   {\def\@tempb{#2}}%
1870   \xdef\l@current@annot{\@tempa|\@tempb}%
1871 }%
1872 %

```

VI.4 Lemma disambiguation

The mechanism which counts the occurrence of a same word in a same line is quite complex, because, when `TEX` reads a command between a \pstart and a \pend, it does not know yet which are the line numbers.

The general mechanism is the following:

- **At the first run**, each \sameword command increments an etoolbox counter the name of which contains the argument of the \sameword commands.

- Then this counter, associated with the argument of `\sameword` is stored with the `\@sw` command in the auxiliary file of the current `reledmac` section (the `.1, .2...` file).
- **When this auxiliary file is read at the second run**, different operations are achieved:

1. Get the rank of each `\sameword` in a line (relative rank) from the rank of each `\sameword` in all the numbered section (absolute rank):

- For each paired `\sameword` argument and absolute line number, a counter is defined. Its value corresponds to the number of times `\sameword{<argument>}` is called from the beginning of the lineation to the end of the current line. We also store the same data for the preceding absolute line number, if it does not have `\sameword{<argument>}`.
- For each `\sameword` having the same argument, we subtract from its absolute rank the number stored for the paired `\sameword` argument and previous absolute line number. Consequently, we obtain the relative rank.
- See the following example which explains how, for same `\sameword`, absolute ranks are transformed to relative ranks.

```

At line 1:
absolute rank 1 becomes relative rank 1-0 = 1
1 is stored for this \sameword and line 1
At line 2:
absolute rank 2 becomes relative rank 2-1 = 1
absolute rank 3 becomes relative rank 3-1 = 2
3 is stored for this \sameword and line 2
At line 3:
no \sameword for this line.
3 is stored for this \sameword and line 3
At line 4:
absolute rank 4 becomes relative rank 4-3 = 1
4 is stored for this \sameword and line 4

```

2. Create lists of lists of `\sameword` by depth of `\edtext`. That is: create a list for `\edtexts` of level 1, a list for `\edtexts` of level 2, a list for `\edtexts` of level 3 etc. For each `\edtext` in these lists, we store all of the relative ranks of `\sameword` which are called as lemma information. That is: 1) either called in the first argument of `\sameword`, or, 2) called in the `\lemma` macro of the second argument of `\sameword` AND marked by the optional argument of `\sameword` in first argument of `\edtext`.

For example, suppose a line with nested `\edtexts` which contains some word marked by `\sameword` and having the following relative rank:

bar ¹	<code>foo¹ foo² bar² foo³</code>	(A)(B) <code>foo⁴ bar³</code>	(C)	<code>foo⁵</code>	(D) <code>bar⁴</code>	(E)
------------------	--	---	-----	------------------------------	----------------------------------	-----

In this example, all lemma information for \edtext is framed. The text in parenthesis is the content of critical notes associated to the preceding frame. As you can see, we have two levels of \edtext.

The list for \edtexts of level 1 is $\{\{1, 2, 2, 3, 4, 3\}, \{5, 4\}\}$.

The list for \edtexts of level 2 is $\{\{1, 2, 2, 3\}, \{5\}\}$.

As you can see, the mandatory argument of \sameword does not matter: we store the rank informations for every word potentially ambiguous.

- At the second run, when a critical notes is called, we associate it to the next item of the list associated to its \edtext level. So, in the previous example:
 - Critical notes (A) and (B) are associated with $\{1, 2, 2, 3\}$.
 - Critical note (C) is associated with $\{1, 2, 2, 3, 4, 3\}$.
 - Critical note (D) is associated with $\{5\}$.
 - Critical note (E) is associated with $\{5, 4\}$.
- At the second run, when a critical note is printed:
 - The \sameword command is let \sameword@inedtext.
 - At each call of this \sameword@inedtext, we step to the next element of the list associated to the note. Let it be r .
 - For the word marked by \sameword, we calculate how many time it is called in its line. To do it:
 - * We get the absolute line number of the current \sameword. This absolute line number was stored with a list of relative ranks for the current \edtext. That means, in the previous example, that if the absolute line number of \edtext was 1, that critical notes (A) and (B) were not associated with $\{1, 2, 2, 3\}$ but with $\{(1, 1), (2, 1), (2, 1), (3, 1)\}$. Such a method of knowing the absolute line number associated to a \sameword is required because a \edtext can overlap many lines, but \sameword can't get it.
 - * When reading the auxiliary file, we get the value associated to the pair composed by the current marked word and the current absolute line number. To this value, we subtract the value associated to the pair composed by the current marked word and the previous absolute line number. Let the result be n .
 - If $n > 1$, that means the current word appears more than once in its line. In this case, we call \showwordrank with the word as the first argument and r as the second argument. If the word is called only once, we just print it.

After theory, implementation.

`\get@sw@txt` As the argument of \sameword can contain an active character if we use `inputenc` with `utf8` option instead of native UTF-8 engine, we store its detokenized content in a macro in order to allow the dynamic name of macro with \csname.³⁰

³⁰See <http://tex.stackexchange.com/q/244538/7712>.

Because there is a bug with `\detokenize` and X_ET_EX when using non BMP characters³¹, we detokenize only for non-X_ET_EXengines. In any case, in X_ET_EXa `\csname` construction can contain UTF-8 characters without a problem, as UTF-8 characters are not managed with category codes, but instead read directly as UTF-8 characters.

```
1873 \newcommand{\get@sw@txt}[1]{%
1874   \begingroup%
1875   \swnoexpands%
1876 }.
```

Using case sensibility option.

```
1877 \ifsw@caseinsensitive%
1878   \def\@tmpa##1{\lowercase{##1}}%
1879 \else%
1880   \def\@tmpa##1{##1}%
1881 \fi%
1882 %
```

And now, define `\sw@txt`.

```
1883 \ifxetex%
1884   \@tmpa{\xdef\sw@txt{#1}}%
1885 \else%
1886   \@tmpa{\expandafter\xdef\expandafter\sw@txt\expandafter{\detokenize
1887 {#1}}}%
1888 \fi%
1889 \endgroup%
1890 }
```

Allow some macros inside `\sameword`. We use `\RenewExpandableDocumentCommand` to get expandable command with optional argument. Cf. <https://tex.stackexchange.com/a/384783/7712>.

```
\sw@noexpand91 \newcommand{\swnoexpands}{%
1892   \let\sameword\l@secondmandarg% Allow to have nested \sameword
1893   \let\emph\@firstofone%
1894   \let\textit\@firstofone%
1895   \let\textbf\@firstofone%
1896   \let\textsc\@firstofone%
1897   \let\framebox\@firstofone%
1898   \let\edtext\dummy@edtext%
1899   \RenewExpandableDocumentCommand{\edindex}{om}{}%
1900   \ifdefinable\index{%
1901     \RenewExpandableDocumentCommand{\index}{om}{}%
1902   }%
1903   \let\selectlanguage\@gobble%
1904   \let\foreignlanguage\@secondoftwo%
```

³¹<http://sourceforge.net/p/xetex/bugs/108/>

```

1905 \ifdefinable\xpg@loaded%
1906   \renewcommand\do[1]{%
1907     \expandafter\RenewExpandableDocumentCommand\expandafter{\csname
1908       text##1\endcsname}{\om}{\####2}%
1909     }%
1910     \expandafter\docslist\expandafter{\xpg@loaded}%
1911   \fi%
1912 }%
1913 %

```

\sameword The hight level macro `\sameword`, used by the editor.

```

1913 \newcommandx{\sameword}[2][1,usedefault]{%
1914   \leavevmode%
1915   \get@sw@txt{#2}%
1916 }

```

Now, the real code. First, increment the counter corresponding to the argument.

```

1917 \unless\ifledRcol%
1918   \csnumgdef{\sw@\sw@txt}{\csuse{\sw@\sw@txt}+\@ne}%
1919 %

```

Then, write its value to the numbered file.

```

1920 \protected@write\linenum@out{}{\string\@sw{\sw@txt}{\csuse{\sw@\sw@txt}
1921 }}{#1}%
1922 %

```

Do the same thing if we are in the right column.

```

1922 \else%
1923   \csnumgdef{\sw@\sw@txt}{\csuse{\sw@\sw@txt}+\@ne}%
1924   \protected@write\linenum@outR{}{\string\@sw{\sw@txt}{\csuse{\sw@\sw@txt}
1925 }}{#1}%
1926 \fi%
1927 %

```

And print the word.

```

1927 #2%
1928 }%
1929 %

```

A flag set to true if a `\@sw` relative rank must be added to the list of ranks for a specific `\edtext`.

```

\if@addsw30 \newif\if@addsw%
1931 %

```

\@sw The command printed in the auxiliary files.

```

1932 \newcommand{\@sw}[3]{%
1933   \get@sw@txt{#1}%
1934   \unless\ifledRcol%
1935 %

```

First, define a counter which store the second argument as value for a each paired absolute line number/first argument

```

1936 \csxdef{sw@\sw@txt}{\the\absline@num}{\the\section@num}{#2}%
1937 %

```

If such argument was not defined for the preceding line, define it.

```

1938 \numdef{\prev@line}{\absline@num-1}%
1939 \ifcsundef{sw@\sw@txt}{\prev@line}{\the\section@num}{%}
1940   \csnumgdef{sw@\sw@txt}{\prev@line}{\the\section@num}{#2-1}%
1941 }{%
1942 %

```

Then, calculate the position of the word in the line.

```

1943 \numdef{\the@sw}{#2-\csuse{sw@\sw@txt}{\prev@line}{\the\section@num}}%
1944 %

```

And do the same thing for the right side.

```

1945 \else%
1946   \csxdef{sw@\sw@txt}{\absline@numR}{\the\section@numR}{#2}%
1947   \numdef{\prev@line}{\absline@numR-1}%
1948   \ifcsundef{sw@\sw@txt}{\prev@line}{\the\section@numR}{%}
1949     \csnumgdef{sw@\sw@txt}{\prev@line}{\the\section@numR}{#2-1}%
1950   }{%
1951   \numdef{\the@sw}{#2-\csuse{sw@\sw@txt}{\prev@line}{\the\section@numR}{#2}}%
1952 }%
1953 %

```

And now, add it to the list of \@sw for the current edtext, in all depth.

```

1954 \@tempcpta=\@edtext@level
1955 \@whilenum{\@tempcpta>0}\do{%
1956   \ifcsdef{sw@list@edtext@tmp}{\the\@tempcpta}{%
1957     }{%
1958       \addswfalse%
1959       \notbool{lemmacommand}{\the\@tempcpta}{%
1960         \addswtrue%
1961         \IfStrEq{#3}{inlemma}{%
1962           \addswtrue%
1963           \def\do##1{%
1964             \def\do##1{%
1965               \ifnumequal{##1}{\the\@tempcpta}{%
1966                 \addswtrue\listbreak}%
1967               }%
1968             }%

```

```

1969          \docsVlist{#3}%
1970      }%
1971  }%
1972 \if@addsw%
1973   \letcs{\@tmp}{\sw@list@edtext@tmp@\the\@tempcnta}%
1974   \ifledRcol%
1975     \xright@appenditem{{\the\sw}{\the\absline@numR}}\to\@tmp%
1976   \else%
1977     \xright@appenditem{{\the\sw}{\the\absline@num}}\to\@tmp%
1978   \fi%
1979   \cslet{\sw@list@edtext@tmp@\the\@tempcnta}{\@tmp}%
1980   \fi%
1981 }%
1982 {%
1983 \advance\@tempcnta by -1%
1984 }%
1985 }%
1986 %

```

`\sameword@inedtext` The command called when `\sameword` is called in a `\edtext`.

```

1987 \newcommandx{\sameword@inedtext}[2][1,usedefault]{%
1988   \get@sw@txt{#2}%
1989   \unless\ifledRcol@%
1990   %

```

Just a precaution.

```

1991   \ifx\sw@list@inedtext\empty%
1992     \def\the\sw{999}%
1993     \def\this@absline{-99}%
1994   \else%
1995   %

```

But in many cases, at this step, we should have some content in the list `\sw@list@inedtext`, which contains the reference for `\edtext`.

```

1996   \gl@p\sw@list@inedtext\to\@tmp%
1997   \edef\the\sw{\expandafter\@firstoftwo\@tmp}%
1998   \edef\this@absline{\expandafter\@secondoftwo\@tmp}%
1999   \fi%
2000 %

```

First, calculate the number of occurrences of the word in the current line

```

2001   \ifcsdef{\sw@\sw@txt}{\this@absline}{\the\section@num}{%
2002     \numdef{\prev@line}{\this@absline-1}%
2003     \numdef{\sw@atthisline}{\csuse{\sw@\sw@txt}{\this@absline}{\the\section@num}-\csuse{\sw@\sw@txt}{\prev@line}{\the\section@num}}%
2004   }%
2005   {\numdef{\sw@atthisline}{0}}%
2006 %

```

Finally, print the rank, but only if there is more than one occurrence of the word in the current line.

```

2007     \ifnumgreater{\sw@atthisline}{1}%
2008         {\showwordrank{#2}{\the@sw}}%
2009         {#2}%
2010     %

```

And the same for right side.

```

2011     \else%
2012         \ifx\sw@list@inedtext\empty%
2013             \def\the@sw{999}%
2014             \def\this@absline{-99}%
2015         \else%
2016             \gl@p\sw@list@inedtext\to\@tmp%
2017             \edef\the@sw{\expandafter\@firstoftwo\@tmp}%
2018             \edef\this@absline{\expandafter\@secondoftwo\@tmp}%
2019         \fi%
2020         \ifcsdef{sw@\sw@txt}{\this@absline}{\the\section@numR@R}%
2021             \numdef{\prev@line}{\this@absline-1}%
2022             \numdef{\sw@atthisline}{\csuse{sw@\sw@txt}{\this@absline}{\the\section@numR@R}-\csuse{sw@\sw@txt}{\prev@line}{\the\section@numR@R}}%
2023             }%
2024             \numdef{\sw@atthisline}{0}%
2025             \ifnumgreater{\sw@atthisline}{1}%
2026                 {\showwordrank{#2}{\the@sw}}%
2027                 {#2}%
2028             \fi%
2029         }%
2030     %

```

`\showwordrank` Finally, the way the rank will be printed.

```

2031 \newcommand{\showwordrank}[2]{%
2032     #1\textsuperscript{#2}%
2033 }%
2034 %

```

VII Paragraph decomposition and reassembly

In order to be able to count the lines of text and affix line numbers, we add an extra stage of processing for each paragraph. We send the paragraph into a box register, rather than straight onto the vertical list, and when the paragraph ends we slice the paragraph into its component lines; to each line we add any notes or line numbers, add a command to write to the line-list, and then at last send the line to the vertical list. This section contains all the code for this processing.

VII.1 Boxes, counters, \pstart and \pend

```
\raw@text
\ifnumberedpar@
\numberedpar@true
\numberedpar@false
  \num@lines
  \one@line
  \par@line
```

Here are numbers and flags that are used internally in the course of the paragraph decomposition.

When we first form the paragraph, it goes into a box register, `\raw@text`, instead of onto the current vertical list. The `\ifnumberedpar@` flag will be true while a paragraph is being processed in that way. `\num@lines` will store the number of lines in the paragraph when it is complete. When we chop it up into lines, each line in turn goes into the `\one@line` register, and `\par@line` will be the number of that line within the paragraph.

```
2035 \newbox\raw@text
2036 \newif\ifnumberedpar@
2037 \newcount\num@lines
2038 \newbox\one@line
2039 \newcount\par@line
2040 %
```

```
\pstarts@typeset@L
\pstarts@read@L
```

The `\pstarts@typeset@L` counts the number of LEFT `\pstart` typeset. A left `\pstart` can be a `\pstart` typeset in normal mode, or `\pstart` typeset in left column or page in parallel mode (`withreledpar`). In the first case, its value is increased at every `\pstart` command. In the second case, its value is increased in `\Columns` or `\Pages` when we prepare to typeset a left `\pstart`. The `\pstarts@read@L` counts the number of LEFT `\pstart` read. A left `\pstart` can be a `\pstart` typeset in normal mode, or `\pstart` typeset in left column or page in parallel mode (`withreledpar`). In the first case, its value is increased at every `\pstart` command. In the second case, its value is increased at every `\pstar@L`.

```
2041 \newcount\pstarts@typeset@L%
2042 \newcount\pstarts@read@L%
2043 %
```

```
\pstart
\AtEveryPstart
\AtStartEveryPstart
  \numberpstarttrue
  \numberpstartfalse
    \labelpstarttrue
    \labelpstartfalse
      \thepstart
\ifat@every@pstart@star@
```

`\pstart` starts the paragraph by clearing the `\inserts@list` list and other relevant variables, and then arranges for the subsequent text to go into the `\raw@text` box. `\pstart` needs to appear at the start of every paragraph that is to be numbered; the `\autopar` command below may be used to insert these commands automatically.

Beware: everything that occurs between `\pstart` and `\pend` is happening within a group; definitions must be global if you want them to survive past the end of the paragraph.

```
2044 \newcommand{\AtStartEveryPstart}[1]{%
2045   \ifstrempty{#1}{%
2046     {\gdef\@at@start@every@pstart{}%}
2047     {\gdef\@at@start@every@pstart{#1}}%}
2048   }%
2049   \def\@at@start@every@pstart{}%
2050 }
2051 \newif\ifat@every@pstart@star@%
```

```

2053 \newcommand{\AtEveryPstart}[1]{%
2054   \ifstrempty{#1}%
2055     {\gdef\at@every@pstart{}%}
2056     {\gdef\at@every@pstart{\noindent#1}}%
2057   \global\at@every@pstart@star@false%
2058 }%
2059 \WithSuffix\newcommand\AtEveryPstart*[1]{%
2060   \ifstrempty{#1}%
2061     {\gdef\at@every@pstart{}%}
2062     {\gdef\at@every@pstart{#1}}%
2063   \global\at@every@pstart@star@true%
2064 }%
2065 \def\at@every@pstart{}%
2066
2067 \newcounter{pstart}
2068 \renewcommand{\thepstart}{\bfseries@arabic{c@pstart}. }
2069 \newif\ifnumberpstart
2070 \numberpstartfalse
2071 \newif\iflabelpstart
2072 \labelpstartfalse
2073 \newcommandx*\pstart}[2][1,2,usedefault]{%
2074   \normal@pars%
2075   \ifboolexpr{%
2076     test {\ifstrempty{#1}}%
2077     and test {\ifstrempty{#2}}%
2078   }%
2079   {\at@every@pstart}%
2080   {%
2081     \ifstrempty{#1}{}{\noindent#1}%
2082     \ifstrempty{#2}{}{#2}%
2083   }%
2084   \ifaupar%
2085     \autpar%
2086   \fi%
2087   \ifluatex%
2088     \edef\l@luatextextdir{\the\textdir}%
2089   \fi%
2090   \nobreaktrue%
2091   \ifnumbering \else%
2092     \led@err@PstartNotNumbered%
2093     \beginnumbering%
2094   \fi%
2095   \ifnumberedpar@%
2096     \led@err@PstartInPstart%
2097     \pend%
2098   \fi%
2099   \list@clear{inserts@list}%
2100   \global\let\next@insert=\empty%
2101   \begingroup\normal@pars%
2102   \global\advance \l@dnumpstartsL@ne

```

```

2103 \global\advance \pstarts@typeset@L\@ne%
2104 \global\advance \pstarts@read@L\@ne%
2105 \global\setbox\raw@text=\vbox\bgroup%
2106 \if@nobreak%
2107   \if@afterindent\else%
2108     \noindent%
2109     \global\@afterindenttrue%
2110   \fi%
2111 \fi%
2112 \ifboolexpr{%
2113   bool{autopar}%
2114   and bool{by@autopar}%
2115 }%
2116 {}%
2117 {}%
2118 \ifnumberpstart%
2119   \ifinstanza\else%
2120     \ifsidepstartnum\else%
2121       \thepstart%
2122     \fi%
2123   \fi%
2124 \fi%
2125 }%
2126 \numberedpar@true%
2127 \iflabelpstart%
2128   \protected@edef\@currentlabel{\p@pstart\thepstart}%
2129 \fi%
2130 \l@dzopenalties%
2131 \at@start@every@pstart%
2132 \global\by@autofalse%
2133 \ignorespaces%because not automatically ignored if an optional argument
is used (classical TeX behavior for space after commands)
2134 }
2135 %

```

\pend \pend must be used to end a numbered paragraph.

```

2136 \newcommandx*{\pend}[2][1,2]{\usedefault}{\ifnumbering \else%
2137   \led@err@PendNotNumbered%
2138 \fi%
2139 \global\l@dskipversenumberfalse%
2140 \ifnumberedpar@ \else%
2141   \led@err@PendNoPstart%
2142 \fi%
2143 %

```

We set all the usual interline penalties to zero and then immediately call \endgraf to end the paragraph; this ensures that there will be no large interline penalties to prevent us from slicing the paragraph into pieces. These penalties revert to the values that you set when the group for the \vbox ends. Then we call \do@line to slice a line off the top

of the paragraph, add a line number and footnotes, and restore it to the page; we keep doing this until there are not any more lines left.

```

2144   \l@dzeropenalties%
2145   \cat@end@every@pend%
2146   \endgraf\global\num@lines=\prevgraf\egroup%
2147   \global\par@line=0%
2148 %

```

We check if lineation is by pstart: in this case, we reset the line number, but only in the second line of the pstart. We can't reset line number at the beginning of \pstart, as \setline is parsed at the end of previous \pend, and so, we must do it at the end of first line of pstart.

```

2149   \csnumdef{\pstartline}{0}%
2150   \loop\ifvbox\raw@text%
2151     \csnumdef{\pstartline}{\pstartline+\@ne}%
2152     \do@line%
2153     \ifbypstart@%
2154       \ifnumequal{\pstartline}{1}{%
2155         \bgroup%
2156         \let\leavevmode\relax%
2157         \setline{1}%
2158         \egroup%
2159         \resetprevline@{}%
2160       }{%
2161         \fi%
2162         \repeat%
2163 %

```

Deal with any leftover notes, and then end the group that was begun in the \pstart.

```

2163   \flush@notes%
2164   \endgroup%
2165   \ignorespaces%
2166 %

```

Increase pstart counter.

```

2167   \ifnumberpstart%
2168     \global\pstartnumtrue%
2169   \fi%
2170   \addtocounter{\pstart}{1}%
2171   \ifcontinuousnumberingwithcolumns%
2172     \addtocounter{\pstartL}{1}%
2173     \addtocounter{\pstartR}{1}%
2174   \fi%
2175 %

```

Print the optional arguments of \pend or the content printed after every \pend

```

2176   \normal@pars%
2177   \ifboolexpr{%
2178     test {\ifstrempy{#1}}%

```

```

2179     and test {\ifstrempty{#2}}%
2180   }%
2181   {\at@every@pend}%
2182   {%
2183   \ifstrempty{#1}{}{\noindent#1}%
2184   \ifstrempty{#2}{}{#2}%
2185   }%
2186 %

```

Restore standard “nobreak” and “autopar” settings. Normally, `\if@nobreak` is true only immediately after a sectioning command (see `latex.ltx` file). As a `\pstart ... \pend` structure can’t contain any sectioning command, we set `\if@nobreak` to false.

```

2187   \nobreakfalse%
2188   \ifautopar%
2189     \autopar%
2190   \fi%
2191 }
2192 %

```

Here, two macros to insert content after every `\pend`, between numbered line. `\AtEveryPend` is the user macro, `\at@every@pend` is macro set by it.

```

\AtEveryPend93
\at@every@pend94
\ifat@every@pend@star@95 \newif\ifat@every@pend@star@%
2196 \newcommand{\AtEveryPend}[1]{%
2197   \ifstrempty{#1}%
2198     {\gdef\at@every@pend{}%}
2199     {\gdef\at@every@pend{\noindent#1}%
2200     \global\at@every@pend@star@false%}
2201   }%
2202 \WithSuffix\newcommand\AtEveryPend*[1]{%
2203   \ifstrempty{#1}%
2204     {\gdef\at@every@pend{}%}
2205     {\gdef\at@every@pend{#1}%
2206     \global\at@every@pend@star@true%}
2207   }%
2208 \xdef\at@every@pend{}%
2209 %
2210 %

```

`\AtEndEveryPend` Here a macro to insert automatically any content at the end of `\pend`, in numbered lines.

```

2211 \newcommand{\AtEndEveryPend}[1]{%
2212   \ifstrempty{#1}%
2213     {\xdef\cat@end@every@pend{}%}
2214     {\gdef\cat@end@every@pend{#1}%
2215   }%
2216 \def\cat@end@every@pend{}%
2217 %

```

\l@dzeropenalties A macro to zero penalties for \pend or \pstart.

```

2218 \newcommand*{\l@dzeropenalties}{%
2219   \brokenpenalty \z@ \clubpenalty \z@
2220   \displaywidowpenalty \z@ \interlinepenalty \z@ \predisplaypenalty \z@
2221   \postdisplaypenalty \z@ \widowpenalty \z@}
2222 %
2223 %

```

\autopar In most cases it is only an annoyance to have to label the paragraphs to be numbered with \pstart and \pend. \autopar will do that automatically, allowing you to start a paragraph with its first word and no other preliminaries, and to end it with a blank line or a \par command. The command should be issued within a group, after \beginnumbering has been used to start the numbering; all paragraphs within the group will be affected.

A few situations can cause problems. One is a paragraph that begins with a begin-group character or command: \pstart will not get invoked until after such a group beginning is processed; as a result the character that ends the group will be mistaken for the end of the \vbox that \pstart creates, and the rest of the paragraph will not be numbered. Such paragraphs need to be started explicitly using \indent, \noindent, or \leavevmode — or \pstart, since you can still include your own \pstart and \pend commands even with \autopar on.

Prematurely ending the group within which \autopar is in effect will cause a similar problem. You must either leave a blank line or use \par to end the last paragraph before you end the group.

The functioning of this macro is more tricky than the usual \everypar: we do not want anything to go onto the vertical list at all, so we have to end the paragraph, erase any evidence that it ever existed, and start it again using \pstart. We remove the paragraph-indentation box using \lastbox and save the width, and then skip backwards over the \parskip that has been added for this paragraph. Then we start again with \pstart, restoring the indentation that we saved, and locally change \par so that it will do our \pend for us.

The boolean \ifautopar is set to TRUE while \autopar is enabled, and the \ifby@autopar is set to TRUE at each \pstart automatically called by the \autopar feature. A manual \pstart will have a \ifby@autopar set to FALSE.

```

2224 \newif\ifautopar
2225 \newif\ifby@autopar%
2226 \newcommand*{\autopar}{%
2227   \ifledRcol
2228     \ifnumberingR \else
2229       \led@err@AutoparNotNumbered
2230     \beginnumberingR
2231     \fi
2232   \else
2233     \ifnumbering \else
2234       \led@err@AutoparNotNumbered
2235     \beginnumbering

```

```

2236   \fi
2237   \fi
2238   \autopartrue
2239   \everypar{\setbox0=\lastbox
2240     \endgraf \vskip-\parskip
2241     \global\by@\autopartrue%
2242     \pstart \noindent \kern\wd0%
2243     \ifnumberpstart%
2244       \ifinstanza\else%
2245         \thepstart%
2246       \fi%
2247     \fi%
2248     \let\par=\pend}%
2249   \ignorespaces}
2250 %

```

\normal@pars We also define a macro which we can rely on to turn off the \autopar definitions at various important places, if they are in force. We will want to do this within a footnotes, for example.

```

2251 \newcommand*{\normal@pars}{\everypar{}{\let\par\endgraf}}
2252 %
2253 %

```

\ifautopar@pause We define a boolean test switched to true at the beginning of the \pausenumbering command if the autopar is enabled. This boolean will be tested at the beginning of \resumenumbering to continue the autopar if needed.

```

2254 \newif\ifautopar@pause
2255 %

```

VII.2 Processing one line

VII.2.1 General process

\do@line The \do@line macro is called by \pend to do all the processing for a single line of text. The \l@dunhbox@line macro only \unhboxes one line, but packages like \microtype can override it as required.

```

2256 \newcommand*{\l@dunhbox@line}[1]{\unhbox #1}
2257 \newcommand*{\do@line}{%
2258   {\vbadness=10000
2259   \splittopskip=\z@
2260   \do@linehook
2261   \l@demptyd@ta
2262   \global\setbox\one@line=\vsplit\raw@text to\baselineskip}%
2263   \unvbox\one@line \global\setbox\one@line=\lastbox
2264   \getline@num
2265   \IfStrEq{\led@pb@setting}{before}{\led@check@pb\led@check@nopb}{}}

```

```

2266   \ifnum@\clock>\@ne
2267     \inserthangingsymboltrue
2268   \else
2269     \inserthangingsymbolfalse
2270   \fi
2271   \check@pb@in@verse
2272   \ifl@dhidenumber%
2273     \global\l@dhidenumberfalse%
2274     \f@x@l@cks%
2275   \else%
2276     \affixline@num%
2277   \fi%
2278 %

```

Depending whether a sectioning command is called at this pstart or not we print sectioning command or normal line,

```

2279   \xifinlist{\the\pstarts@typeset@L}{\eled@sections@@}%
2280     {\print@eledsection}%
2281     {\print@line}%
2282   \IfStrEq{\led@pb@setting}{after}{\led@check@pb\led@check@nopb}{}
2283 }%
2284 %

```

VII.2.2 Process for “normal” line

`\print@line` `\print@line` is for normal line, i. e line without sectioning command.

```

2285 \def\print@line{
2286 %

```

Insert the pstart number inside, if we are in the first line of a pstart.

```

2287   \affixpstart@num%
2288 %

```

The line will be boxed, to have the good width.

```

2289   \hb@xt@ \linewidth{%
2290   %

```

User hooks.

```

2291   \do@insidelinehook%
2292   \csuse{insidethis@\the\absline@num @\the\section@num}%
2293   \global\csundef{insidethis@\the\absline@num @\the\section@num}%
2294 %

```

Left line number

```

2295   \l@dld@ta%
2296 %

```

Prepare text to be inserted before notes.

```

2297 \if@firstlineofpage%
2298   \set@Xtxtbeforenotes%
2299   \set@txtbeforenotesX%
2300   \global\@firstlineofpagefalse%
2301 \fi%
2302 %

```

Insert footnotes made of manuscripts data and critical footnotes.

```

2303   \ifdefstring{\ms@data@position}{msdata-regular}{%
2304     \insert@msdata%
2305     \add@inserts%
2306     \add@Xgroupbyline%
2307   }{%
2308     \add@inserts%
2309     \add@Xgroupbyline%
2310     \insert@msdata%
2311   }%
2312 %

```

Insert marginal notes.

```

2313   \affixside@note%
2314 %

```

Print left notes.

```

2315   \l@dlsn@te
2316 %

```

Boxes the line, writes information about new line in the numbered file.

```

2317   {\ledllfill\hb@xt@ \wd\one@line{%
2318     \new@line%
2319   }%

```

If we use the `continuousnumberingwithcolumns`, we increase right line number.

```

2320   \continuousnumberingwithcolumns@sync@linenumber@singletext%
2321 %

```

If we use `LuaTeX` then restore the direction.

```

2322   \ifluatex%
2323     \textdir\l@luatextextdir@L%
2324   \fi%
2325 %

```

Insert, if needed, the hanging symbol.

```

2326   \inserthangingsymbol%
2327 %

```

And so, print the line.

```

2328   \l@dunhbox@line{\one@line}%
2329 %

```

Right line number

```
2330 \ledrlfill\l@drd@ta%
2331 %
```

Print right notes.

```
2332 \l@drsn@te%
2333 }%
2334 %
```

And reinsert penalties (for page breaking)...

```
2335 \add@penalties%
2336 }
2337 %
```

VII.2.3 Process for line containing \eledsection command

\print@eledsection \print@eledsection to print sectioning command with line number. It sets the correct spacing, depending whether a sectioning command was called at previous \pstart, calls the sectioning command, prints the normal line outside of the paper, to be able to have critical footnotes. Because of how this prints, a vertical spacing correction is added.

```
2338 \def\print@eledsection{%
2339   \if@firstlineofpage%
2340     \set@Xtxtbeforenotes%
2341     \set@txtbeforenotesX%
2342     \global\@firstlineofpagefalse%
2343   \fi%
2344   \ifdefstring{\ms@data@position}{msdata-regular}{%
2345     \insert@msdata%
2346     \add@inserts%
2347     \add@Xgroupbyline%
2348   }%
2349   \add@inserts%
2350   \add@Xgroupbyline%
2351   \insert@msdata%
2352 }%
2353 \affixside@note%
2354 \numdef{\temp@}{\pstarts@typeset@L-1}%
2355 \xifinlist{\temp@}{\eled@sections@@}{\nobreaktrue}{\nobreakfalse}%
2356 \eled@sectioningtrue%
2357 \csuse{\eled@sectioning@\the\pstarts@typeset@L}%
2358 \eled@sectioningfalse%
2359 \global\csundef{\eled@sectioning@\the\pstarts@typeset@L}%
2360 \if@RTL%
2361   \hspace{-3\paperwidth}%
2362   {\hbox{\l@dunhbox@line{\one@line}} \new@line}%
2363 \else%
2364   \hspace{3\paperwidth}%
2365   {\new@line \hbox{\l@dunhbox@line{\one@line}}}%
2366 }
```

```

2366   \fi%
2367   \vskip-\baselineskip%
2368   \continuousnumberingwithcolumns@sync@linenumber@singletext%
2369 }
2370 %

```

VII.2.4 Hooks

`\do@linehook` Two hooks into `\do@line`. The first is called at the beginning of `\do@line`, the second is called in the line box. The second can, for example, have a `\markboth` command inside, the first can not.

```

2371 \newcommand*{\do@linehook}={}
2372 \newcommand*{\do@insidelinehook}={}
2373 %

```

`\dolinehook` These high level commands just redefine the low level commands. They have to be used
`\doinsidelinehook` be user, without `\makeatletter`.

```

2374 \newcommand*{\dolinehook}[1]{\gdef\do@linehook{#1}}%
2375 \newcommand*{\doinsidelinehook}[1]{\gdef\do@insidelinehook{#1}}%
2376 %
2377 %

```

`\doinsidethislinehook` The `\doinsidethislinehook` can be called directly in the main flood of a text. It will
`@insidethisline` define a hook executed at a specific line, determined by the position of the command in
the flood of the text.

```

2378 \newcommand{\doinsidethislinehook}[1]{%
2379   \leavevmode% In case it begins with a \pstart, ensure the @insidethisline
   is written after \onl
2380   \ifledRcol%
2381     \write\linenum@outR{\string\@insidethisline[\unexpanded{#1}]}%
2382   \else%
2383     \write\linenum@out{\string\@insidethisline[\unexpanded{#1}]}%
2384   \fi%
2385 }%
2386 %

```

The auxiliary file command just store the information to be executed when typesetting
the specific line.

```

2387 \newcommand{\@insidethisline}[1]{%
2388   \ifledRcol%
2389     \csgappto{insidethisR@\the\absline@numR @\the\section@numR}{#1}%
2390   \else%
2391     \csgappto{insidethis@\the\absline@num @\the\section@num}{#1}%
2392   \fi%
2393 }%
2394 %

```

VII.2.5 Sidenotes and marginal line number initialization

\l@emptyd@ta Nulls the \dots d@ta, which may later hold line numbers. Similarly for \l@dcsnotetext, \\l@dld@ta \\l@dcsnotetext@l, \\l@dcsnotetext@r for the texts of the sidenotes, left and right notes.

```

\l@dcsnotetext2395 \newcommand*\l@emptyd@ta{%
\l@dcsnotetext@l2396   \gdef\l@dld@ta{}%
\l@dcsnotetext@r2397   \gdef\l@drd@ta{}%
2398   \gdef\l@dcsnotetext@l{}%
2399   \gdef\l@dcsnotetext@r{}%
2400   \gdef\l@dcsnotetext{}}

2401 %
2402 %

```

\l@dlsn@te Zero width boxes of the left and right sidenotes, together with their kerns, and, eventually, with additional space if we are in parallel columns typesetting.

```

\l@dlsn@te2403 \newcommand{\l@dlsn@te}{%
2404   \ifboolexpr{%
2405     bool {l@printingcolumns}%
2406     and bool {ledRcol@}%
2407   }{%
2408     \tempdima=\morespace@leftnote@rightcolumn%
2409   }{%
2410     \tempdima=z@%
2411   }%
2412   \hb@xt@ \z@{\hss\box\l@dlp@rbox\kern\ledlsnotesep\hskip\tempdima}%
2413 }%
2414 \newcommand{\l@drsn@te}{%
2415   \ifboolexpr{%
2416     bool {l@printingcolumns}%
2417     and not bool {ledRcol@}%
2418   }{%
2419     \tempdima=\morespace@rightnote@leftcolumn%
2420   }{%
2421     \tempdima=z@%
2422   }%
2423   \hb@xt@ \z@{\hskip\tempdima\kern\ledrsnotesep\box\l@drp@rbox\hss}%
2424 }%
2425 %
2426 %

```

\ledllfill These macros are called at the left (\ledllfill) and the right (\ledllfill) of each numbered line. The initial definitions correspond to the original code for \do@line.

```

\ledllfill2427 \newcommand*\ledllfill{\hfil}
\ledrlfill2428 \newcommand*\ledrlfill{}}

2429 %
2430 %

```

VIII Line and page number computation

`\getline@num` The `\getline@num` macro determines the page and line numbers for the line we are about to send to the vertical list.

```

2431 \newcommand*{\getline@num}{%
2432   \global\advance\absline@num \cne%
2433   \do@actions
2434   \do@ballast
2435   \ifnumberline
2436     \ifsblines@
2437       \ifnum\sub@lock<\tw@
2438         \global\advance\spline@num \cne
2439       \fi
2440     \else
2441       \ifnum\clock<\tw@
2442         \global\advance\line@num \cne
2443         \global\spline@num \z@
2444       \fi
2445     \fi
2446   \fi
2447 }
2448 %

```

`\do@ballast` The real work in the macro above is done in `\do@actions`, but before we plunge into that, let's get `\do@ballast` out of the way. This macro looks to see if there is an action to be performed on the *next* line, and if it is going to be a page break action, `\do@ballast` decreases the count `\ballast@count` counter by the amount of `ballast`. This means, in practice, that when `\add@penalties` assigns penalties at this point, TeX will be given extra encouragement to break the page here (see XII.2 p. 178).

`\ballast@count` First we set up the required counters; they are initially set to zero, and will remain so unless you type `\setcounter{ballast}{<some figure>}` in your document.

```

2449 \newcount\ballast@count
2450 \newcounter{ballast}
2451   \setcounter{ballast}{0}
2452 %

```

And here is `\do@ballast` itself. It advances `\absline@num` within the protection of a group to make its check for what happens on the next line.

```

2453 \newcommand*{\do@ballast}{\global\ballast@count \z@
2454   \begingroup
2455     \advance\absline@num \cne
2456     \ifnum\next@actionline=\absline@num
2457       \ifnum\next@action>-1001\relax
2458         \global\advance\ballast@count by -\c@ballast
2459       \fi
2460     \fi

```

```
2461     \endgroup}
2462 %
```

\do@actions The `\do@actions` macro looks at the list of actions to take at particular absolute line numbers, and does everything that is specified for the current line.

It may call itself recursively, and to do this efficiently (using TeX's optimization for tail recursion), we define a control-sequence called `\do@actions@next` that is always the last thing that `\do@actions` does. If there could be more actions to process for this line, `\do@actions@next` is set equal to `\do@actions`; otherwise it is just `\relax`.

```
2463 \newcommand*{\do@actions}{%
2464   \global\let\do@actions@next=\relax
2465   \ifnum\absline@num<\next@actionline\else
2466 %
```

First, page number changes, which will generally be the most common actions. If we are restarting lineation on each page, this is where it happens.

```
2467   \ifnum\next@action>-1001
2468     \global\page@num=\next@action
2469     \ifresumenumbering@start%
2470       \setbox0=\hbox{}%Required to get the correct page number, when the
2471       \resumenumbering is just after a \newpage
2472       \ifnum\pausenumbering@page@num<\page@num%
2473         \global\resumenumbering@startfalse%
2474       \fi%
2475     \fi%
2476     \ifboolexpr{%
2477       bool{resumenumbering@start}%
2478       and test {\ifdimgreater{\pagedepth}{\z@}}%
2479     }%
2480     {}%
2481     {\global\@firstlineofpagetrue}%
2482     \ifcsdef{reset@line}{\absline@num \the\section@num}%
2483     {}%
2484     \global\line@num=\z@%
2485     \global\subline@num=\z@%
2486     \resetprevline@%
2487     {}%
2488     {}%
2489     \global\resumenumbering@startfalse%
2490     \add@msdata@firstlineofpage%
2491 %
```

Next, we handle commands that change the line-number values. (We subtract 5001 rather than 5000 here because the line number is going to be incremented automatically in `\getline@num`.)

```
2491 \else
2492   \ifnum\next@action<-4999
2493     \cldtempcnta=-\next@action
```

```

2494     \advance\@l@dtempcpta by -5001
2495     \ifsublines@
2496         \global\subline@num=\@l@dtempcpta
2497     \else
2498         \global\line@num=\@l@dtempcpta
2499     \fi
2500 %

```

We rescale the value in `\@l@dtempcpta` so that we can use a case statement.

```

2501     \else
2502         \@l@dtempcpta=-\next@action
2503         \advance\@l@dtempcpta by -1000
2504         \do@actions@fixedcode
2505     \fi
2506 \fi
2507 %

```

Now we get information about the next action off the list, and then set `\do@actions@next` so that we will call ourselves recursively: the next action might also be for this line.

There is no warning if we find `\actionlines@list` empty, since that will always happen near the end of the section.

```

2508     \ifx\actionlines@list\empty
2509         \gdef\next@actionline{1000000}%
2510     \else
2511         \gl@p\actionlines@list\to\next@actionline
2512         \gl@p\actions@list\to\next@action
2513         \global\let\do@actions@next=\do@actions
2514     \fi
2515 \fi
2516 %

```

Make the recursive call, if necessary.

```

2517 \do@actions@next
2518
2519 %

```

`\do@actions@fixedcode` This macro handles the fixed codes for `\do@actions`. It is one big case statement.

```

2520 \newcommand*{\do@actions@fixedcode}{%
2521     \ifcase\@l@dtempcpta
2522         \or%                                % 1001 = starting sublineation
2523             \global\sublines@true
2524         \or%                                % 1002 = ending sublineation
2525             \global\sublines@false
2526         \or%                                % 1003 = starting locking number
2527             \global\@clock=\@ne
2528         \or%                                % 1004 = ending locking number
2529             \ifnum\@clock=\tw@
2530                 \global\@clock=\thr@@

```

```

2531     \else
2532         \global\@clock=\z@
2533     \fi
2534     \or%                                % 1005 = starting locking subnumber
2535         \global\sub@clock=\@ne
2536     \or%                                % 1006 = ending locking subnumber
2537         \ifnum\sub@clock=\tw@
2538             \global\sub@clock=\thr@@
2539         \else
2540             \global\sub@clock=\z@
2541         \fi
2542     \or%                                % 1007 = skipping numbering
2543         \l@dskipnumbertrue
2544     \or%                                % 1008 = skipping numbering in stanza
2545         \l@dskipversenumbertrue%
2546     \or%                                % 1009 = hiding number
2547         \l@dhidenumbertrue
2548     \or%                                % 1010 = inserting msdata
2549         \add@msdata%
2550     \else
2551         \led@warn@BadAction
2552     \fi}
2553
2554 %

```

VIII.1 Continuous line numbering between parallel typesetting and normal typesetting

`\sync@linenumber@singletext` The `continuousnumberingwithcolumns` option allows to alternate between single text and two parallel texts, keeping the same line numbers when switching from one layout to the other. The lines counter for the text in a single column and for the text in the left column in parallel typesetting is the same. But the lines counter for the text in the same column is the not the same.

When typesetting single column text, if the option is enabled, we need to “simulate” typesetting right line, in order to keep the two counters synchronized. That is the aim of the

`\continuousnumberingwithcolumns@\sync@linenumber@singletext` macro.

```

2556 \newcommand{\continuousnumberingwithcolumns@\sync@linenumber@singletext}{%
2557     \ifcontinuousnumberingwithcolumns%
2558         \unless\ifafterendnumberingR%
2559             \new@lineR%
2560             \xappto\next@line@list@stuffR{%
2561                 \unexpanded{\global\line@numR=\}\the\line@num%
2562             }%
2563     \fi%

```

```

2564   \fi%
2565 }%
2566 %

```

IX Line number annotation

The `\linenumannotation` allows users to add manual annotations to line numbers, for example to refer to line numbers from an older edition.

That implies that annotations be added

- in marginal line numbers. This feature is implemented by associating annotations with the absolute line numbers when reading the auxiliary numbered files (.1, .2 etc.).
- in critical footnotes. This feature is implemented by associating start / end line number annotations with each `\edtext` when reading the auxiliary numbered files.
- to crossref commands which refer to line numbers (to be completed when I will have resolved this issue).

`\linenumannotation` First, the user-level command, which only writes commands to the numbered files, storing the annotation.

```

2567 \newcommand{\linenumannotation}[1]{%
2568   \leavevmode%In case it begins with a \pstart, ensure the \cannot is
   written after \onl
2569   \ifledRcol%
2570     \write\linenum@outR{\string\cannot[\#1]}%
2571   \else%
2572     \write\linenum@out{\string\cannot[\#1]}%
2573   \fi%
2574 }%
2575 %

```

`\Xlinenumannotationposition@side` The `\Xlinenumannotationposition@side` macro, to determine the position of line number annotations in lines printed in the side, relative to the line number position. The default value is “after”, but it can be changed to “before”, using the `\Xlinenumannotationposition` macro.

```

2576 \def\Xlinenumannotationposition@side{after}%
2577 %

```

`\Xwraplinenumannotation@ref` The `\Xwraplinenumannotation@ref` macro is applied to line annotations in crossref.

`\Xwraplinenumannotation@side` The `\Xwraplinenumannotation@side` macro is applied to line annotation in sides. They must be modified by users using `\Xwraplinenumannotation`. By default, they call `\textsuperscript`.

We also define toggle `Xnoidenticallinenumannotation@ref` and `Xnoidenticallinenumannotation@side`.

```

2578 \def\Xwraplinenumannotation@ref{\textsuperscript}%
2579 \def\Xwraplinenumannotation@side{\textsuperscript}%
2580 \newtoggle{Xnoidenticallinenumannotation@ref}%
2581 \newtoggle{Xnoidenticallinenumannotation@side}%
2582 %

```

\@cannot Then, the numbered files command **\@cannot**, which

\store@annot@to@absline

- associates the annotation to the absolute lines number.
- stores the current annotation in a macro to be used by the **\@ref@reg** macro, which manages all things related to **\edtext** in numbered files. As we don't want to store it multiple times in the event of nested **\edtext**, we use an auxiliary macro, **\store@annot@to@absline**, which is set to **\gobble** when we parse nested **\edtext** in numbered auxiliary files.

```

2583 \newcommand{\@cannot}[1]{%
2584   \store@annot@to@absline{\#1}%
2585   \def\current@annot{\#1}%
2586 }%
2587 \newcommand{\store@annot@to@absline}[1]{%
2588   \ifledRcol{%
2589     \ifcsdef{annotR@\the\absline@numR \the\section@numR}{%
2590       \csgappto{annotR@\the\absline@numR \the\section@numR}{\%
2591         @linenumannotationsep\#1}%
2592       }{%
2593         \csgdef{annotR@\the\absline@numR \the\section@numR}{\#1}%
2594       }%
2595     \else{%
2596       \ifcsdef{annot@\the\absline@num \the\section@num}{%
2597         \csgappto{annot@\the\absline@num \the\section@num}{\%
2598           @linenumannotationsep\#1}%
2599         }{%
2600           \csgdef{annot@\the\absline@num \the\section@num}{\#1}%
2601         }%
2602       }%
2603     }%
2604   }%

```

\current@annot By default, there is no annotation to a line number, so we store an empty **\current@annot**

```

2603 \let\current@annot=\empty%
2604 %

```

\reset@current@annot **\reset@current@annot** is called at each **\@nl** in numbered auxiliary files. It resets the annotation of line numbers at each line.

```

2605 \newcommand{\reset@current@annot}{%
2606   \unless\ifnoresetlinenumannotation@

```

```

2607   \let\current@annot\empty%
2608   \fi
2609 }%
2610 %

```

- `\parse@annot` In the `\annot@list` list, each individual `\edtext` is associated with a starting and an ending line number annotation, which is stored this way: `start annotation|end annotation`. The `\parse@annot` reads the format and defines two global macros.

```

2611 \def\parse@annot#1|#2|{
2612   \gdef\annot@start{#1}%
2613   \gdef\annot@end{#2}%
2614 }%
2615 %

```

- `\setlinenumannotationsep` The separator between the annotations and the way to redefine it.

```

\@linenumannotationsep
2616 \newcommand{\setlinenumannotationsep}[1]{\gdef\@linenumannotationsep{#1}}%
2617 \def\@linenumannotationsep{, }%
2618 %

```

X Line number printing

- `\affixline@num` `\affixline@num` just puts a left line number into `\l@dld@ta` or a right line number into `\l@drd@ta` as required.

To determine whether we need to affix a line number to this line, we compute the following:

$$\begin{aligned} n &= \text{int}((\text{linenum} - \text{firstlinenum}) / \text{linenumincrement}) \\ m &= \text{firstlinenum} + (n \times \text{linenumincrement}) \end{aligned}$$

(where `int` truncates a real number to an integer). `m` will be equal to `linenum` only if we are to paste a number on here. However, the formula breaks down for the first line to number (and any before that), so we check that case separately: if `\line@num ≤ \firstlinenum`, we compare the two directly instead of making these calculations.

We compute, in the scratch counter `\@l@dtmpcnta`, the number of the next line that should be printed with a number (`m` in the above discussion), and move the current line number into the counter `\@l@dtmpcntb` for comparison.

First, the case when we are within a sub-line range.

```

2619 \newcommand*{\affixline@num}{%
2620   %

```

No number is attached if `\ifl@dskipnumber` is TRUE (and then it is set to its normal FALSE value). No number is attached if `\ifnumberline` is FALSE (the normal value is TRUE).

```

2621 \ifledgroupnotesL@{\else
2622   \ifnumberline
2623     \ifl@dskipnumber
2624       \global\l@dskipnumberfalse
2625     \else
2626       \ifsblines@%
2627         \l@l@dtmpcntb=\subline@num
2628         \ifnum\subline@num>\c@firstsublinenum
2629           \l@l@dtmpcnta=\subline@num
2630           \advance\l@l@dtmpcnta by-\c@firstsublinenum
2631           \divide\l@l@dtmpcnta by\c@sublinenumincrement
2632           \multiply\l@l@dtmpcnta by\c@sublinenumincrement
2633           \advance\l@l@dtmpcnta by\c@firstsublinenum
2634         \else
2635           \l@l@dtmpcnta=\c@firstsublinenum
2636         \fi
2637 %

```

That takes care of computing the values for comparison, but if line number locking is in effect we have to make a further check. If this check fails, then we disable the line-number display by setting the counters to arbitrary but unequal values.

```

2638 \ch@cksub@l@ck
2639 %

```

Now the line number case, which works the same way.

```

2640 \else
2641   \l@l@dtmpcntb=\line@num
2642 %

```

Check on the `\linenumberlist` If it is `\empty` use the standard algorithm.

```

2643 \ifx\linenumberlist\empty
2644   \ifnum\line@num>\c@firstlinenum
2645     \l@l@dtmpcnta=\line@num
2646     \advance\l@l@dtmpcnta by-\c@firstlinenum
2647     \divide\l@l@dtmpcnta by\c@linenumincrement
2648     \multiply\l@l@dtmpcnta by\c@linenumincrement
2649     \advance\l@l@dtmpcnta by\c@firstlinenum
2650   \else
2651     \l@l@dtmpcnta=\c@firstlinenum
2652   \fi
2653 \else
2654 %

```

The `\linenumberlist` was not `\empty`, so here is Wayne's numbering mechanism. This takes place in TeX's mouth.

```

2655 \l@l@dtmpcnta=\line@num
2656 \edef\rem@nder{,\linenumberlist,\number\line@num,}%
2657 \edef\sc@n@list{\def\noexpand\sc@n@list

```

```

2658     #####1,\number\@l@dtempcpta,#####2|{\def\noexpand\rem@cinder
2659     {####2}}}%
2660     \sc@n@list\expandafter\sc@n@list\rem@cinder|%
2661     \ifx\rem@cinder\empty%
2662     \advance\@l@dtempcpta\@ne
2663     \fi
2664 %

```

A locking check for lines, just like the version for sub-line numbers above.

```

2665     \ch@ck@l@ck
2666     \fi
2667 %

```

The following tests are true if we need to print a line number.

```

2668 \ifnum\@l@dtempcpta=\@l@dtempcntb
2669   \ifl@dskipversenumber\else
2670 %

```

If we got here, we are going to print a line number; so now we need to calculate a number that will tell us which side of the page will get the line number. We start from `\line@margin`, which asks for one side always if it is less than 2; and then if the side does depend on the page number, we simply add the page number to this side code—because the values of `\line@margin` have been devised so that this produces a number that is even for left-margin numbers and odd for right-margin numbers.

For L^AT_EX we have to consider two column documents as well. In this case Peter Wilson thought we need to put the numbers at the outside of the column—the left of the first column and the right of the second. Do the `twocolumn` stuff before going on with the original code.

`\l@dld@ta` A left line number is stored in `\l@dld@ta` and a right one in `\l@drd@ta`.

```

\l@drd@ta
2671   \if@twocolumn
2672     \if@firstcolumn
2673       \gdef\l@dld@ta{\llap{\leftlinenum}}%
2674     \else
2675       \gdef\l@drd@ta{\rlap{\rightlinenum}}%
2676     \fi
2677   \else
2678     \ifboolexpr{bool {\l@dpriintingcolumns} and test {\i
2679     fnumgreater{\line@margin@columns}{\m@ne}}}{%
2680       {\@l@dtempcntb=\line@margin@columns}%
2681       {\@l@dtempcntb=\line@margin}%
2682       \ifnum\@l@dtempcntb>\@ne
2683         \advance\@l@dtempcntb \page@num
2684       \fi
2685     \ifboolexpr{%
2686       bool {\l@dpriintingcolumns}%
2687       and (\%

```

```

2687      (test {\ifdefstring{\linenum@OnlyPages@ForColumns}{left
2688          }%
2689          and test {\ifnumodd{\page@num}{%
2690              }%
2691              or%
2692              (test {\ifdefstring{\linenum@OnlyPages@ForColumns}{right
2693                  }%
2694                  and not test {\ifnumodd{\page@num}{%
2695                      }%
2696                      }%
2697                      }%
2698                      \ifodd@\l@dtmpcntb%
2699                          \gdef\l@drd@ta{\rlap{{\rightlinenum}}}%
2700                          \else%
2701                              \gdef\l@dld@ta{\llap{{\leftlinenum}}}%
2702                          \fi%
2703                      }%
2704                      \fi
2705                      \fi
2706                      \fi
2707  %

```

Now fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

2708      \f@x@l@cks
2709      \fi
2710      \fi
2711      \fi
2712  }
2713 %
2714 %

```

\ch@cksub@l@ck These macros handle line number locking for `\affixline@num`. **\ch@cksub@l@ck** checks subline locking. If it fails, then we disable the line-number display by setting the counters to arbitrary but unequal values.

```

2715 \newcommand*{\ch@cksub@l@ck}{%
2716     \ifcase\sub@lock
2717         \or
2718             \ifnum\sublock@disp=\@ne
2719                 \l@dtmpcntb=\z@ \l@dtmpcpta=\@ne
2720             \fi
2721         \or
2722             \ifnum\sublock@disp=\tw@ \else
2723                 \l@dtmpcntb=\z@ \l@dtmpcpta=\@ne
2724             \fi
2725         \or

```

```

2726     \ifnum\sublock@disp=\z@%
2727         \cldtempcntb=\z@ \cldtempcnta=\@ne
2728     \fi
2729 \fi}
2730 %

```

Similarly for line numbers.

```

2731 \newcommand*{\ch@ck@l@ck}{%
2732     \ifcase\@clock
2733     \or
2734         \ifnum\lock@disp=\@ne
2735             \cldtempcntb=\z@ \cldtempcnta=\@ne
2736         \fi
2737     \or
2738         \ifnum\lock@disp=\tw@
2739             \else
2740                 \cldtempcntb=\z@ \cldtempcnta=\@ne
2741             \fi
2742     \or
2743         \ifnum\lock@disp=\z@%
2744             \cldtempcntb=\z@ \cldtempcnta=\@ne
2745         \fi
2746 \fi}
2747 %

```

Fix the lock counters. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

2747 \newcommand*{\fx@l@cks}{%
2748     \ifcase\@lock
2749     \or
2750         \global\@lock=\tw@
2751     \or \or
2752         \global\@lock=\z@%
2753     \fi
2754     \ifcase\sub@lock
2755     \or
2756         \global\sub@lock=\tw@
2757     \or \or
2758         \global\sub@lock=\z@%
2759     \fi
2760 %
2761 %

```

XI Pstart number printing inside

Inside, the printing of the pstart number runs like the printing of the line number. There are only a few differences:

```
\affixpstart@num
  \pstartnum
```

- The pstarts counter is upgraded in the \pend command. Consequently, the \affixpstart@num command has not to upgrade it, unlike the \affixline@num which upgrades the lines counter.
- To print the pstart number only at the beginning of a pstart, and not in every line, a boolean test is made. The \pstartnum boolean is set to TRUE at every \pend. It is tried in the \leftpstartnum and \rightstartnum commands. After the try, it is set to FALSE.

```
\leftpstartnum62
\rightstartnum63 \newif\ifsidepstartnum
\ifsidepstartnum64 \newcommand*{\affixpstart@num}{%
  2765   \ifsidepstartnum
  2766     \if@twocolumn
  2767       \if@firstcolumn
  2768         \gdef\l@dld@ta{\llap{{\leftpstartnum}}}%
  2769       \else
  2770         \gdef\l@drd@ta{\rlap{{\rightpstartnum}}}%
  2771       \fi
  2772     \else
  2773       \l@dtmpcntb=\line@margin%
  2774       \ifnum\l@dtmpcntb>\@ne
  2775         \advance\l@dtmpcntb \page@num
  2776       \fi
  2777       \ifodd\l@dtmpcntb
  2778         \gdef\l@drd@ta{\rlap{{\rightpstartnum}}}%
  2779       \else
  2780         \gdef\l@dld@ta{\llap{{\leftpstartnum}}}%
  2781       \fi
  2782     \fi
  2783   \fi
  2784 }
  2785 %
  2786
  2787 \newif\ifpstartnum
  2788 \pstartnumtrue
  2789 \newcommand*{\leftpstartnum}{%
  2790   \ifpstartnum\the pstart
  2791   \kern\linenumsep\fi
  2792   \global\pstartnumfalse
  2793 }
  2794 \newcommand*{\rightpstartnum}{%
  2795   \ifpstartnum
  2796     \kern\linenumsep
  2797     \the pstart
  2798   \fi
  2799   \global\pstartnumfalse
  2800 }
  2801 }
```

2802 %

XII Restoring footnotes and penalties

Because of the paragraph decomposition process in order to number line, `reledmac` must hack the standard way `TEX` works in order to manage insertion of footnotes, both critical and familiar.

We need to call the `\insert` commands not when the content of `\pstart...\pend` is read by `TEX` by when each individual line is typeset.

Consequently, when reading the content of `\pstart...\pend`, we store the insertion (footnotes) in an specific `reledmac`'s list, and we restore them to the vertical list when printing each individual line.

XII.1 Add insertions to the vertical list

`\inserts@list` `\inserts@list` is the list macro that contains the inserts that we save up for one paragraph.

2803 `\list@create{\inserts@list}`
2804 %

`\add@inserts` `\add@inserts` is the penultimate macro used by `\do@line`; it takes insertions saved in a list macro and sends them onto the vertical list.

It may call itself recursively, and to do this efficiently (using `TEX`'s optimization for tail recursion), we define a control-sequence called `\add@inserts@next` that is always the last thing that `\add@inserts` does. If there could be more inserts to process for this line, `\add@inserts@next` is set equal to `\add@inserts`; otherwise it is just `\relax`.

2805 `\newcommand*{\add@inserts}{%`
2806 `\global\let\add@inserts@next=\relax`
2807 %

If `\inserts@list` is empty, there are not any more notes or insertions for this paragraph, and we need not waste our time.

2808 `\ifx\inserts@list\empty \else`
2809 %

The `\next@insert` macro records the number of the line that receives the next footnote or other insert; it is empty when we start out, and just after we have affixed a note or insert.

2810 `\ifx\next@insert\empty`
2811 `\ifx\insertlines@list\empty`
2812 `\global\noteschanged@true`
2813 `\gdef\next@insert{100000}%`
2814 `\else`
2815 `\gl@p\insertlines@list\to\next@insert`
2816 `\fi`

```
2817     \fi
2818 %
```

If the next insert's for this line, tack it on (and then erase the contents of the insert macro, as it could be quite large). In that case, we also set `\add@inserts@next` so that we will call ourselves recursively: there might be another insert for this same line.

```
2819 \ifnum\next@insert=\absline@num
2820   \gl@p\inserts@list\to@\insert
2821   \@insert
2822   \global\let\@insert=\undefined
2823   \global\let\next@insert=\empty
2824   \global\let\add@inserts@next=\add@inserts
2825   \fi
2826 \fi
2827 %
```

Make the recursive call, if necessary.

```
2828 \add@inserts@next}
2829 %
2830 %
```

`\add@Xgroupbyline` If you use `\Xgroupbyline`, the insertion of the critical footnotes are not made immediately in `\add@inserts`, but the content to be inserted is stored, in order to be inserted later in one block. This insertion in one block is made by `\add@Xgroupbyline`.

```
2831 \newcommand{\add@Xgroupbyline}{%
2832   \unless\ifnocritical@%
2833   \def\do##1{%
2834     \let\olddo\do%Save the old \do macro, that is this macro itself!
2835     \def\do####1{%
2836       \ifcsdef{##1@forinserting}{}{%
2837         \X@beforeinsertion{##1}%
2838         \if@ledgroup%
2839           \global\setbox\@nameuse{mp##1footins}=\vbox{%
2840             \insert\csname ##1footins\endcsname%
2841           }%
2842         \else%
2843           \insert\csname ##1footins\endcsname%
2844         \fi%
2845       }%
2846       \notoggle{Xparindent@##1}{\parindent=\z@{}}%
2847       \ifcsdef{Xysize\csuse{series@display##1}@@##1}{}{%
2848         \hspace{\csuse{Xysize\csuse{series@display##1}@@##1}}%
2849       }%
2850       \if@ledgroup%
2851         \unvbox\@nameuse{mp##1footins}%
2852       \fi%
2853       \X@atbegininsertion{##1}%
2854       \ifcsstring{series@display##1}{}{%
2855         \Xledsetnormalparstuff{##1}%
2856       }%
2857     }%
2858   }%
```

```

2855           \rule{z}{\splittopskip}%
2856       }%
2857   {}%
2858   \csuse{##1@forinserting@####1}%
2859     \strut\par%
2860   }%
2861   \global\csundef{##1@forinserting@####1}%
2862   }%
2863   {}%
2864   }%
2865   \ifcsdef{##1@forinserting}{}{%
2866     \dolistcsloop{##1@forinserting}%
2867   }{%
2868     \global\csundef{##1@forinserting}%
2869     \let\do\olddo%Restore old do
2870   }%
2871   \dolistloop{\@series}%
2872 \fi%
2873 }%
2874
2875
2876 %

```

XII.2 Penalties

`\add@penalties` `\add@penalties` is the last macro used by `\do@line`. It adds up the club, widow, and interline penalties, and puts a single penalty of the appropriate size back into the paragraph; these penalties get removed by the `\vsplit` operation. `\displaywidowpenalty` and `\brokenpenalty` are not restored, since we have no easy way to find out where we should insert them.

In this code, `\num@lines` is the number of lines in the whole paragraph, and `\par@line` is the line we are working on at the moment. The count `\@l@dtmpcpta` is used to calculate and accumulate the penalty; it is initially set to the value of `\ballast@count`, which has been worked out in `\do@ballast` above (VIII p. 164). Finally, the penalty is checked to see that it does not go below -10000 .

```

2877 \newcommand*{\add@penalties}{\@l@dtmpcpta=\ballast@count
2878   \ifnum\num@lines>\@ne
2879     \global\advance\par@line \@ne
2880   \ifnum\par@line=\@ne
2881     \advance\@l@dtmpcpta \clubpenalty
2882   \fi
2883   \@l@dtmpcntb=\par@line \advance\@l@dtmpcntb \@ne
2884   \ifnum\@l@dtmpcntb=\num@lines
2885     \advance\@l@dtmpcpta \widowpenalty
2886   \fi
2887   \ifnum\par@line<\num@lines
2888     \advance\@l@dtmpcpta \interlinepenalty
2889   \fi

```

```

2890     \fi
2891     \ifnum\@l@dtempcnta=\z@
2892         \relax
2893     \else
2894         \ifnum\@l@dtempcnta>-10000
2895             \penalty\@l@dtempcnta
2896         \else
2897             \penalty -10000
2898         \fi
2899     \fi}
2900
2901 %

```

XII.3 Printing leftover notes

\flush@notes The `\flush@notes` macro is called after the entire paragraph has been sliced up and sent on to the vertical list. If the number of notes to this paragraph has increased since the previous run of TeX, then there can be leftover notes that have not yet been printed. An appropriate error message will be printed elsewhere; but it is best to go ahead and print these notes somewhere, even if it is not in quite the right place. What we do is dump them all out here, so that they should be printed on the same page as the last line of the paragraph. We can hope that is not too far from the proper location, to which they will move on the next run. For the first run, we do not flush the notes, as that means all the notes will be added at the end of numbered section, and so, very far of the expected position

```

2902 \newcommand*{\flush@notes}{%
2903   \iftoggle{notfirstrun@\jobname.\extensionchars\the\section@num}{%
2904     \@xloop%
2905     \ifx\inserts@list\empty \else%
2906       \gl@p\inserts@list\to\@insert%
2907       \@insert%
2908       \global\let\@insert=\undefined%
2909     \repeat%
2910   }{}%
2911 }%
2912
2913
2914 %

```

\@xloop `\@xloop` is a variant of the Plain TeX `\loop` macro, useful when it's hard to construct a positive test using the TeX `\if` commands—as in `\flush@notes` above. One types `\@xloop ... \if ... \else ... \repeat`, and the action following `\else` is repeated as long as the `\if` test fails. (This macro will work wherever the Plain TeX `\loop` is used, too, so we could just call it `\loop`; but it seems preferable not to change the definitions of any of the standard macros.)

This variant of `\loop` was introduced by Alois Kabelschacht in *TUGboat* 8 (1987), pp. 184–5.

```

2915 \def\@xloop#1\repeat{%
2916   \def\body{\#1\expandafter\body\fi}%
2917   \body}
2918 %
2919 %

```

XII.4 Text before notes

\set@Xtxtbeforenotes The **\set@Xtxtbeforenotes** macro resets the **Xtxtbeforesnotes@<series>** @typeset boolean to false. Just before the first note of the **<series>** in a page, the **\Xtextbeforenotes** will be inserted.

```

2920 \newcommand{\set@Xtxtbeforenotes}{%
2921   \unless\ifnocrITICAL@%
2922   \def\do##1{%
2923     \nottoggle{Xtxtbeforesnotesonlyonce@##1}{%
2924       \global\togglefalse{Xtxtbeforesnotes@##1@typeset}%
2925     }{}%
2926   }%
2927   \dolistloop{\@series}%
2928 \fi%
2929 }%
2930 %

```

\set@txtbeforenotesX The **\set@txtbeforenotesX** does the same for the **\textbeforenotesX**.

```

2931 \newcommand{\set@txtbeforenotesX}{%
2932   \unless\ifnofamiliar@%
2933   \def\do##1{%
2934     \nottoggle{txtbeforesnotesonlyonceX@##1}{%
2935       \global\togglefalse{txtbeforesnotesX##1@typeset}%
2936     }{}%
2937   }%
2938   \dolistloop{\@series}%
2939 \fi%
2940 }%
2941 %

```

\insert@Xtxtbeforenotes **\insert@Xtxtbeforenotes{<series>}**, called when inserting a familiar footnote, will insert the text before the note if it is not already inserted. For paragraphed footnotes, it will insert it as a component of the first footnote. For other types of footnotes, it will insert it as a regular footnote.

\insert@txtbeforenotesX is the same for familiar footnotes.

```

2942 \newcommand{\insert@Xtxtbeforenotes}[1]{%
2943   \nottoggle{Xtxtbeforesnotes##1@typeset}{%
2944     \global\toggletrue{Xtxtbeforesnotes##1@typeset}%
2945     \ifcsvoid{Xtxtbeforesnotes##1}{}{%
2946       \ifcsstring{series@display##1}{paragraph}%

```

```

2947 {\noindent\csuse{Xtxtbeforenotes@#1}}%
2948 {\expandafter\insert\csname#1footins\endcsname%
2949 \bgroup%
2950 \noindent%
2951 \ifcsdef{\csuse{series@display#1}@begin@insert}{%
2952   \csuse{\csuse{series@display#1}@begin@insert}{#1}%
2953 }{}%
2954 \strut\csuse{Xnotefontsize@#1}%
2955 \csuse{Xtxtbeforenotes@#1}%
2956 \egroup%
2957 }%
2958 }%
2959 }%
2960 {}%
2961 }%
2962
2963
2964 \newcommand{\insert@txtbeforenotesX}[1]{%
2965   \notoggle{txtbeforenotesX@#1@typeset}{%
2966     \global\toggletrue{txtbeforenotesX@#1@typeset}%
2967     \ifcvoid{txtbeforenotesX@#1}{}{%
2968       \ifcsstring{series@displayX#1}{paragraph}%
2969         {\noindent\csuse{txtbeforenotesX@#1}}%
2970         {\expandafter\insert\csname footins#1\endcsname%
2971           \bgroup%
2972           \noindent%
2973           \ifcsdef{\csuse{series@displayX#1}@begin@insert}{%
2974             \csuse{\csuse{series@displayX#1}@begin@insert}{#1}%
2975           }{}%
2976           \strut\csuse{notefontsizeX@#1}\csuse{txtbeforenotesX@#1}%
2977           \egroup%
2978         }%
2979       }%
2980     }%
2981   }%
2982 }%
2983
2984
2985 %

```

XIII Critical footnotes

The footnote macros are adapted from those in PLAIN \TeX , but they differ in these respects: the outer-level commands must add other commands to a list macro rather than doing insertions immediately; there are many separate levels of the footnotes, not just one; and there are options to reformat footnotes into paragraphs or into multiple columns.

XIII.1 Fonts

Before getting into the details of formatting the notes, we set up some font macros. It is the notes that present the greatest challenge for our font-handling mechanism, because we need to be able to take fragments of our main text and print them in different forms: it is common to reduce the size, for example, without otherwise changing the fonts used.

`\select@lemmafont` `\select@lemmafont` `\select@lemmafont` `\select@lemmafont` is provided to set the right font for the lemma in a note. This macro extracts the font specifier from the line and page number cluster, and issues the associated font-changing command, so that the lemma is printed in its original font.

```

2986 \def\select@lemmafont#1#2#3#4#5#6#7{\select@lemmafont#7}
2987 \def\select@lemmafont#1#2#3#4{%
2988   {\fontencoding{#1}\fontfamily{#2}\fontseries{#3}\fontshape{#4}}%
2989   \selectfont}
2990 %
2991 %

```

XIII.2 Individual note options

`\footnoteoptions@` The `\footnoteoption@[<side>]{<options>}[<value>]` changes the value of on options of Xfootnote, to switch between true and false.

```

2992 \newcommand*{\footnoteoptions@}[3]{%
2993   \def\do##1{%
2994     \ifstreq{\#1}{L}{% On the left side
2995       \xright@appenditem{\noexpand\setkeys[mac]{#3footnoteoption}{%
2996         unexpanded{##1}}}\to\inserts@list%
2997       \global\advance\insert@count \z@% Increment the left insert
2998       counter.%
2999     }%
3000     \xright@appenditem{\noexpand\setkeys[mac]{#3footnoteoption}{%
3001       unexpanded{##1}}}\to\inserts@listR%
3002       \global\advance\insert@countR \z@% Increment the right insert
3003       counter insert.%
3004     }%
3005   }%
3006   \notblank{#2}{\docs@list{#2}}% Parsing all options
3007 }
3008 %

```

XIII.3 Notes language

`\footnotelang@lua` `\footnotelang@lua` is called to remember the information about the direction of a lemma when Lua \TeX is used.

```

3006 \newcommandx*{\footnotelang@lua}[1][1=L,usedefault]{%
3007   \ifstreq{\#1}{L}{%

```

```

3008     \xright@appenditem{{\csxdef{footnote@luatextextdir}{\the\textdir}}}\to\
3009     inserts@list%Know the dir of lemma
3010     \global\advance\insert@count \@ne%
3011     \xright@appenditem{{\csxdef{footnote@luatexpardir}{\the\pardir}}}\to\
3012     inserts@list%Know the dir of lemma
3013     \global\advance\insert@count \@ne%
3014     }%
3015     {%
3016     \xright@appenditem{{\csxdef{footnote@luatextextdir}{\the\textdir}}}\to\
3017     inserts@listR%Know the dir of lemma
3018     \global\advance\insert@countR \@ne%
3019     }%
3020   %

```

\footnotelang@poly \footnotelang@poly is called to remember the information about the language of a lemma when `polyglossia` is used.

```

3021 \newcommandx*\footnotelang@poly[1][1=L,usedefault]{%
3022   \ifstrequal{\#1}{L}{%
3023     \if@RTL%
3024       \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\
3025     inserts@list%Know the language used in the lemma
3026     \global\advance\insert@count \@ne%
3027   \else%
3028     \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\
3029     inserts@list%Know the language of lemma
3030     \global\advance\insert@count \@ne%
3031   \fi%
3032   \xright@appenditem{{\csxdef{footnote@lang}{\expandonce\languagename}}}\to\
3033   inserts@list%Know the language of lemma
3034   \global\advance\insert@count \@ne%
3035   }%
3036   {%
3037     \if@RTL%
3038       \xright@appenditem{{\csxdef{footnote@dir}{@RTLtrue}}}\to\
3039     inserts@listR%Know the language of lemma
3040     \global\advance\insert@countR \@ne%
3041   \else%
3042     \xright@appenditem{{\csxdef{footnote@dir}{@RTLfalse}}}\to\
3043     inserts@listR%Know the language of lemma
3044     \global\advance\insert@countR \@ne%
3045   }%

```

```
3044 }
3045 %
```

XIII.4 General survey of the way we manage notes

The processing of each note is done by four principal macros: the `\vfootnote` macro takes the text of the footnote and does the `\insert`; it calls on the `\footfmt` macro to select the right fonts, print the line number and lemma, and do any other formatting needed for that individual note. Within the output routine, the two other macros, `\footstart` and `\footgroup`, are called; the first prints extra vertical space and a footnote rule, if desired; the second does any reformatting of the whole set of the footnotes in this series for this page—such as paragraphing or division into columns—and then sends them to the page.

These four macros, and the other macros and parameters shown here, are distinguished by the ‘series letter’ that indicates which set of the footnotes we are dealing with—A, B, C, D, or E. The series letter always precedes the string `foot` in macro and parameter names. Hence, for the A series, the four macros are called `\vAfootnote`, `\Afootfmt`, `\Afootstart`, and `\Afootgroup`.

These macros are changed depending of the footnotes arrangement: “normal”, “paragraphed”, “two columns” or “three columns”.

XIII.5 General setup

`\footsplitskips` Some setup code that is common for a variety of the footnotes. The setup is for:

- `\interlinepenalty`.
- `\splittopskip` (skip before last part of notes that flow from one page to another).
- `\splitmaxdepth`.
- `\floatingpenalty`, that is penalty values being added when a long note flows from one page to another. Here, we let it to 0 when we are processing parallel pages in `eledpar`, in order to allow notes to flow from left to right pages and *vice-versa*. Otherwise, we let it to `\@MM`, which is the standard L^AT_EX `\floatingpenalty`.

```
3046 \newcommand*{\footsplitskips}{%
3047   \interlinepenalty=\interfootnotelinepenalty
3048   \unless\ifl@dprintingpages%
3049     \floatingpenalty=\@MM%
3050   \fi%
3051   \splittopskip=\ht\strutbox \splitmaxdepth=\dp\strutbox
3052   \leftskip=\z@skip \rightskip=\z@skip}
3053 %
3054 %
```

`\normalfootnoterule` `\normalfootnoterule` is a standard footnote-rule macro, for use by a `footstart` macro: just the same as the Plain TeX footnote rule.

```
3055 \let\normalfootnoterule=\footnoterule
3056 %
```

XIII.6 Footnotes arrangement

XIII.6.1 User level macro

`\Xarrangement` `\Xarrangement[⟨s⟩]{⟨arrangement⟩}` The command calls, for each series, a specific command which set many counters and commands in order to define specific arrangement.

```
3057 \newcommandx{\Xarrangement}[2][1,usedefault]{%
3058   \def\do##1{%
3059     \csname Xarrangement@##2\endcsname{##1}%
3060   }%
3061   \ifstrempty{##1}%
3062     {%
3063       \dolistloop{\@series}%
3064     }%
3065   {%
3066     \docs{vlist}{##1}%
3067   }%
3068 }%
3069 %
```

XIII.6.2 Normal footnote

`\Xarrangement@normal` We can now define all the parameters for the series of footnotes; initially they use the “normal” footnote formatting.

What we want to do here is to insert something like the following for each footnote series. (This is an example, not part of the actual `reledmac` code.)

```
\skip\Afootins=12pt plus5pt minus5pt
\count\Afootins=1000
\dimen\Afootins=0.8\vsiz
\let\vAfootnote=\normalvfootnote \let\Afootfmt=\normalfootfmt
\let\Afootstart=\normalfootstart \let\Afootgroup=\normalfootgroup
\let\Afootnoterule=\normalfootnoterule
```

(Read *The TeXbook* in order to understand what are the counter, skip and dimen associated to an insertion.)

Instead of repeating ourselves, we define a `\Xarrangement@normal` macro that makes all these assignments for us, for any given series letter. This command is called when people use `\Xarrangement[⟨series⟩]{normal}`.

Now we set up the `\Xarrangement@normal` macro itself. It takes one argument: the footnote series letter.

```

3070 \newcommand*{\Xarrangement@normal}[1]{%
3071   \csgdef{series@display#1}{normal}
3072   \expandafter\let\csname #1footstart\endcsname=\normalfootstart
3073   \expandafter\let\csname v#1footnote\endcsname=\normalvfootnote
3074   \expandafter\let\csname #1footfmt\endcsname=\normalfootfmt
3075   \expandafter\let\csname #1footgroup\endcsname=\normalfootgroup
3076   \expandafter\let\csname #1footnoterule\endcsname=%
3077     \normalfootnoterule
3078   \count\csname #1footins\endcsname=1000
3079   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}
3080   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3081   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3082 %

```

The `reledpar` provides tools in order to confine notes to one side. The mechanism is explained in the `reledpar`'s handbook. For now, just retain we need to store default value of the counter associated to the notes \TeX 's inserts.

```

3083 \csxdef{default@#1footins}{1000}%Use this to confine the notes to one
3084   side only
3085 %

```

Now do the setup for minipage footnotes. We use as much as possible of the normal setup as we can (so the notes will have a similar layout).

```

3085 \ifnoledgroup@{\else%
3086   \expandafter\let\csname mpv#1footnote\endcsname=\mpnnormalvfootnote
3087   \expandafter\let\csname mp#1footgroup\endcsname=\mpnnormalfootgroup
3088   \count\csname mp#1footins\endcsname=1000
3089   \dimen\csname mp#1footins\endcsname=\csuse{Xmaxhnotes@#1}
3090   \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3091   \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3092 \fi
3093 }
3094 %
3095 %

```

\normalvfootnote We now begin a series of commands that do ‘normal’ footnote formatting: a format much like that implemented in `PLAIN \TeX` , in which each footnote is a separate paragraph.

`\normalvfootnote` takes the series letter as #1 and the entire text of the footnote is #2. It does the `\insert` for this note, calling on the `\footfmt` macro for this note series to format the text of the note.

```

3096 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalvfootnote}[2]{%
3097   \iftoggle{Xgroupbyline@#1}{%In the case we use \Xgroupbyline, the
3098     insertion is done later, in \add@Xgroupbyline.
3099     \prepare@Xgroupbyline{#1}{#2}{\normalvfootnote@inserted}%
3100   }{%In the case we don't use \Xgroupbyline, the insertion is made directly
3101     \X@beforeinsertion{#1}%
3102     \insert\csname #1footins\endcsname{%
3103       \X@atbegininsertion{#1}%

```

```

3103      \normalvfootnote@inserted{#1}{#2}%
3104      }%
3105      }%
3106      }%
3107      %

```

\normalvfootnote@inserted The \normalvfootnote@inserted macro is expanded to the content to be added to a \insert for normal critical footnote.

```

3108 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalvfootnote@inserted}[2]{%
3109   \nottoggle{Xgroupbyline@#1}{\noindent}{\csuse{Xhooknote@#1}%
3110   \csuse{Xnotefontsize@#1}%
3111   \iftoggle{Xgroupbyline@#1}{\strut}{%
3112     \footsplitskips
3113     \ifl@dpairing\ifl@dpaging\else%
3114       \setXnoteswidthliketwocolumns@{#1}%
3115     \fi\fi%
3116     \setXnotespositionliketwocolumns@{#1}%
3117     \spaceskip=\z@skip \xspaceskip=\z@skip%
3118     \csname #1footfmt\endcsname #2{#1}%
3119   }%
3120   %
}

```

```

\X@beforeinsertion21 \newcommand{\X@beforeinsertion}[1]{%
3122   \if@ledgroup\else%
3123     \insert@Xtxtbeforenotes{#1}%
3124   \fi%
3125   \csuse{Xbeforeinserting@#1}%
3126 }%
3127 %

```

```

\beforeinsertion@X28 \newcommand{\beforeinsertion@X}[1]{%
3129   \if@ledgroup\else%
3130     \insert@txtbeforenotesX{#1}%
3131   \fi%
3132   \csuse{beforeinsertingX@#1}%
3133 }%
3134 %

```

```

\X@atbegininsertion35 \newcommand{\X@atbegininsertion}[1]{%
3136   \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3137 }%
3138 %

```

And somewhat different versions of \normalvfootnote and \normalvfootnote@inserted for minipages.

```
\mpnormalvfootnote39 \notbool{parapparatus@}{\newcommand*{\newcommand}{\mpnormalvfootnote}[2]{%
 3140   \iftoggle{Xgroupbyline@#1}{%
 3141     \prepare@Xgroupbyline{#1}{#2}{\mpnormalvfootnote@inserted}%
 3142   }%
 3143   {%
 3144     \global\setbox\@nameuse{mp#1footins}%
 3145     \vbox{%
 3146       \unvbox\@nameuse{mp#1footins}%
 3147       \mpnormalvfootnote@inserted{#1}{#2}%
 3148     }%
 3149   }%
 3150 }%
 3151 }%
 3152 %
```

```
\mpnormalvfootnote@inserted53 \newcommand{\mpnormalvfootnote@inserted}[2]{%
 3154   \noindent\csuse{Xhooknote@#1}%
 3155   \csuse{Xnotefontsize@#1}%
 3156   \hsize\columnwidth%
 3157   \parboxrestore%
 3158   \color@begingroup%
 3159   \csname #1footfmt\endcsname \#2{#1}\color@endgroup%
 3160 }%
 3161 %
```

\normalfootfmt `\normalfootfmt` is a ‘normal’ macro to take the footnote line and page number information (see V.9 p. 107), and the desired text, and output what’s to be printed. Argument #1 contains the line and page number information and lemma font specifier; #2 is the lemma; #3 is the note’s text; #4 is the note’s series. This version is very rudimentary—it uses `\printlines` to print just the range of line numbers, followed by a square bracket, the lemma, and the note text.

```
3162 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalfootfmt}[4]{%
 3163   \Xstorelineinfo{#1}{#4}%
 3164   \nottoggle{Xgroupbyline@#4}{\Xledsetnormalparstuff{#4}}{}%
 3165   \Xsethangindent{#4}%
 3166   \nottoggle{Xgroupbyline@#4}{\rule{z@\splittopskip}{}{}}%
 3167   {\printlinefootnote{#1}{#4}}%
 3168   \print@lemma{#1}{#2}{#4}%
 3169   \csuse{Xwrapcontent@#4}{#3}%
 3170   \nottoggle{Xgroupbyline@#4}{\strut\par}{}%
 3171 }%
 3172 %
```

\normalfootstart `\normalfootstart` is a standard footnote-starting macro, called in the output routine whenever there are footnotes of this series to be printed: it skips a bit and then draws a rule.

Any `\footstart` macro must put onto the page something that takes up space exactly equal to the `\skip\Xfootins` value for the associated series of notes. TeX makes page computations based on that `\skip` value, and the output pages will suffer from spacing problems if what you add takes up a different amount of space.

But if the skip `\Xprenotes@` is greater than 0 pt, it is used instead of `\skip\footins` for the first printed series in one page.

The `\leftskip` and `\rightskip` values are both zeroed here. Similarly, these skips are cancelled in the `\vfootnote` macros for the various types of notes. Strictly speaking, this is necessary only if you are using paragraphed footnotes, but we have put it here and in the other `\vfootnote` macros too so that the behavior of `reledmac` in this respect is general across all footnote types. What this means is that any `\leftskip` and `\rightskip` you specify applies to the main text, but not the footnotes. The footnotes continue to be of width `\hsize`.

```
3173 \newcommand*{\normalfootstart}[1]{%
3174   %
```

The first series of notes printed in a page can have a specific skip before it. In order to insert this specific skip without overlap the bottom margin of the page, Maëul Rouquette have defined an algorithm explained in XIX p. 242. Here is part of this algorithm, when the block of notes are ready to be printed.

```
3175 \ifdim\equal{0pt}{\Xprenotes@}{%
3176   %
3177   \iftoggle{\Xprenotes@}{%
3178     \togglefalse{\Xprenotes@}%
3179     \skip\csname #1footins\endcsname=%
3180     \glueexpr\csuse{\Xprenotes@}+\csuse{\Xafterrule@#1}\relax%
3181   }%
3182 }%
3183 }%
3184 \vskip\skip\csname #1footins\endcsname%
3185 %
```

And now, the problem of left and right skip for notes. Especially when using one feature of `reledpar` which allows to have the footnotes horizontal size as the size of columns printed by `\Columns`. Read XVI p. 239 for the general description of the problem.

```
3186 \leftskip0pt \rightskip0pt
3187 \ifl@dpairing\else%
3188   \hsize=\old@hsize%
3189 \fi%
3190 \setXnoteswidthliketwocolumns@{#1}%
3191 \setXnotespositionliketwocolumns@{#1}%
3192 %
```

And now, print the footnote's rule to finish the footnote's introduction.

```
3193 \print@Xfootnoterule{#1}%
3194 }%
3195 %
```

\normalfootgroup \normalfootgroup is a standard footnote-grouping macro: it sends the contents of the footnote-insert box to the output page without alteration.

```

3196 \newcommand*{\normalfootgroup}[1]{%
3197   \csuse{Xbhookgroup@#1}%
3198   \unvbox\csname #1footins\endcsname%
3199   \hsize=\old@hsize%
3200 }%
3201 %
3202 %

```

\mpnormalfootgroup A somewhat different version for minipages. Note that, in this case, we do not make distinctions between the \Xfootgroup and \Xfootstarts macros.

```

3203 \unless\ifnoledgroup@
3204 \newcommand*{\mpnormalfootgroup}[1]{{%
3205   \vskip\skip\@nameuse{mp#1footins}%
3206   \ifl@dpairing\ifparledgroup%
3207     \leavevmode\marks\parledgroup@{begin}%
3208     \marks\parledgroup@series{#1}%
3209     \marks\parledgroup@type{Xfootnote}%
3210   \fi\fi\normalcolor%
3211   \ifparledgroup%
3212     \ifl@dpairing%
3213     \else%
3214       \setXnoteswidthliketwocolumns@{#1}%
3215       \setXnotespositionliketwocolumns@{#1}%
3216       \print@Xfootnoterule{#1}%
3217     \fi%
3218   \else%
3219     \setXnoteswidthliketwocolumns@{#1}%
3220     \setXnotespositionliketwocolumns@{#1}%
3221     \print@Xfootnoterule{#1}%
3222   \fi%
3223   \setlength{\parindent}{0pt}%
3224   \csuse{Xbhookgroup@#1}%
3225   \unvbox\csname mp#1footins\endcsname}%
3226 \fi%
3227 %

```

XIII.6.3 Paragraphed footnotes

The paragraphed-footnote option reformats all the footnotes of one series for a page into a single paragraph; this is especially appropriate when the notes are numerous and brief. The code is based on *The TeXbook*, pp. 398–400, with alterations for our environment. This algorithm uses a considerable amount of save-stack space: a \TeX of ordinary size may not be able to handle more than about 100 notes of this kind on a page.

\Xarrangement@paragraph The \Xarrangement@paragraph macro sets up everything for one series of the footnotes so that they will be paragraphed; it takes the series letter as argument. We include

the setting of `\count\footins` to 1000 for the footnote series just in case user is switching to paragraphed footnotes after having columnar ones, since they change this value (see below).

The argument of `\Xarrangement@footparagraph` is the letter denoting the series of notes to be paragraphed.

```

3228 \newcommand*{\Xarrangement@paragraph}[1]{%
3229   \csgdef{series@display#1}{paragraph}
3230   \expandafter\let\csname #1footstart\endcsname=\parafootstart
3231   \expandafter\let\csname v#1footnote\endcsname=\paravfootnote
3232   \expandafter\let\csname #1footfmt\endcsname=\parafootfmt
3233   \expandafter\let\csname #1footgroup\endcsname=\parafootgroup
3234   \count\csname #1footins\endcsname=1000
3235   \csxdef{default@#1footins}{1000}%Use this to confine the notes to one
3236   side only
3237   \dimen\csname #1footins\endcsname=\csuse{Xmaxnotes@#1}
3238   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3239   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3240   \para@footsetup{#1}
3241 %

```

And the extra setup for minipages.

```

3241 \ifnoledgroup@{\else
3242   \expandafter\let\csname mpv#1footnote\endcsname=\mpparavfootnote
3243   \expandafter\let\csname mp#1footgroup\endcsname=\mpparafootgroup
3244   \count\csname mp#1footins\endcsname=1000
3245   \dimen\csname mp#1footins\endcsname=\csuse{Xmaxnotes@#1}
3246   \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3247   \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3248 \fi
3249 }
3250 %

```

\footfudgefiddle For paragraphed footnotes TeX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. `\footfudgefiddle` can be increased from its default 64 (say, to 70) to increase the estimate.

```

3251 \providecommand{\footfudgefiddle}{64}
3252 %

```

\para@footsetup `\footparagraph` calls the `\para@footsetup` macro to calculate a special fudge factor, which is the ratio of the `\baselineskip` to the `\hsize`. We assume that the proper value of `\baselineskip` for the footnotes (normally 9 pt) has been set already. The argument of the macro is again the note series letter.

Peter Wilson thinks that `\columnwidth` should be used here for L^AT_EX not `\hsize`. Peter Wilson have also included `\footfudgefiddle`.

```

3253 \newcommand*{\para@footsetup}[1]{\csuse{Xbhookgroup@#1}\csuse{%
3254   Knotefontsize@#1}}

```

```

3254 \setXnoteswidthliketwocolumns@{\#1}%
3255 \ifcsempty{Xwidth@{\#1}}%
3256   {}%
3257   {\columnwidth=\expandafter\dimexpr\csuse{Xwidth@{\#1}}\relax}%
3258 \dimen0=\baselineskip
3259 \multiply\dimen0 by 1024
3260 \divide \dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\
3261   \csxdef{#1footfudgefactor}{%
3262     \expandafter\strip@pt\dimen0 }}}
3263 %
3264 %

```

\strip@pt strip the characters pt from a dimen value.

\parafootstart \parafootstart is the same as \normalfootstart, but we give it again to ensure that \rightskip and \leftskip are zeroed (this needs to be done before \para@footgroup in the output routine). The size of paragraphed notes is calculated using a fudge factor which in turn is based on \hsize. So the paragraph of notes needs to be that wide.

The argument of the macro is again the note series letter.

```

3265 \newcommand*{\parafootstart}[1]{%
3266   \rightskip=0pt \leftskip=0pt%
3267   \notoggle{Xparindent@{\#1}}{\parindent=\z@}{}
3268   \ifdimequal{0pt}{\Xprenotes@}{}
3269   {}%
3270   \iftoggle{Xprenotes@}{%
3271     \togglefalse{Xprenotes@}%
3272     \skip\csname #1footins\endcsname=%
3273     \glueexpr\csuse{Xprenotes@}+\csuse{Xafterrule@{\#1}}\relax%
3274   }%
3275   {}%
3276 }%
3277 \vskip\skip\csname #1footins\endcsname%
3278 \setXnoteswidthliketwocolumns@{\#1}%
3279 \setXnotespositionliketwocolumns@{\#1}%
3280 \print@Xfootnoterule{\#1}%
3281 \let\bidi@RTL@everypar\empty%
3282 \noindent\leavevmode}
3283 %

```

\paravfootnote \paravfootnote is a version of the \vfootnote command that is used for paragraphed notes. It gets appended to the \inserts@list list by an outer-level footnote command like \Afootnote. The first argument is the note series letter; the second is the full text of the printed note itself, including line numbers, lemmata, and footnote text.

The initial model for this insertion is, of course, the \insert\footins definition in *The TeXbook*, p. 398. There, the footnotes are first collected up in hboxes, and these hboxes are later unpacked and stuck together into a paragraph.

However, Michael Downes has pointed out that because text in hboxes gets typeset in restricted horizontal mode, there are some undesirable side-effects if you later want to break such text across lines. In restricted horizontal mode, where TeX does not expect to have to break lines, it does not insert certain items like `\discretionary`s. If you later unbox these hboxes and stick them together, as the *TeXbook* macros do to make these footnotes, you lose the ability to hyphenate after an explicit hyphen. This can lead to overfull hboxes when you would not expect to find them, and to the uninitiated it might be very hard to see why the problem had arisen.³²

Wayne Sullivan pointed out to us another subtle problem that arises from the same cause: TeX also leaves the `\language` whatsit nodes out of the horizontal list.³³ So changes from one language to another will not invoke the proper hyphenation rules in such footnotes. Since critical editions often do deal with several languages, especially in a footnotes, we really ought to get this bit of code right.

To get around these problems, Wayne suggested emendations to the *TeXbook* versions of these macros which are broadly the same as those described by Michael: the central idea (also suggested by Donald Knuth in a letter to Michael) is to avoid collecting the text in an `\hbox` in the first place, but instead to collect it in a `\vbox` whose width is (virtually) infinite. The text is therefore typeset in unrestricted horizontal mode, as a paragraph consisting of a single long line. Later, there is an extra level of unboxing to be done: we have to unpack the `\vbox`, as well as the hboxes inside it, but that is not too hard. For details, we refer you to Michael's article, where the issues are clearly explained.³⁴ Michael's unboxing macro is called `\Xunvxh`: unbox, extract the last line, and `unhbox` it.

Doing things this way has an important consequence: as Michael pointed out, you really can't put an explicit line-break into a note built in a `\vbox` the way we are doing.³⁵ In other words, be very careful not to use `\break`, or `\penalty-10000`, or any equivalent inside your para-footnote. If you do, most of the note will probably disappear. You *are* allowed to make strong suggestions; in fact `\penalty-9999` will be quite okay. Just do not make the break mandatory. We have not applied any of Michael's solutions here, since we feel that the problem is exiguous, and `reledmac` is quite baroque enough already. If you think you are having this problem, look up Michael's solutions.

One more thing: we set `\leftskip` and `\rightskip` to zero. This has the effect of neutralizing any such skips which may apply to the main text (cf. XIII.6.2 p. 189 above). We need to do this, since `\footfudgefactor` is calculated on the assumption that the notes are `\hsize` wide.

So, finally, here is the modified foot-paragraph code, which sets the footnote in vertical mode so that language and discretionary nodes are included.

```

3284 \newcommand*{\paravfootnote}[2]{%
3285   \csuse{Xbeforeinserting@\#1}%
3286   \insert\csname #1footins\endcsname
3287   \bgroup

```

³² Michael Downes, 'Line Breaking in \unboxed Text', *TUGboat* 11 (1990), pp. 605–612.

³³ See *The TeXbook*, p. 455 (editions after January 1990).

³⁴ Wayne supplied his own macros to do this, but since they were almost identical to Michael's, Peter Wilson have used the latter's `\Xunvxh` macro since it is publicly documented.

³⁵ 'Line Breaking', p. 610.

```

3288 \csuse{Xnotefontsize@#1}
3289 \footfoldsplitskips
3290 \setbox0=\vbox{\hsize=\maxdimen%
3291   \let\bidi@RTL@everypar\empty%
3292   \insert@Xtxtbeforenotes{#1}%
3293   \noindent\csuse{Xbhooknote@#1}%
3294   \csname #1footfmt\endcsname #2{#1}%
3295 \setbox0=\hbox{\Xunvxh{0}{#1}}%
3296 \dp0=0pt
3297 \ht0=\csname #1footfudgefactor\endcsname\wd0
3298 %

```

Here we produce the contents of the footnote from box 0, and add a penalty of 0 between boxes in this insert.

```

3299 \if@RTL\noindent \leavevmode\fi\box0%
3300 \penalty0
3301 \egroup}
3302 %

```

The final penalty of 0 was added here at Wayne's suggestion to avoid a weird page-breaking problem, which occurs on those occasions when TeX attempts to split foot paragraphs. After trying out such a split (see *The TeXbook*, p. 124), TeX inserts a penalty of -10000 here, which nearly always forces the break at the end of the whole footnote paragraph (since individual notes can't be split) even when this leads to an overfull vbox. The change above results in a penalty of 0 instead which allows, but does not force, such breaks. This penalty of 0 is later removed, after page breaks have been decided, by the \unpenalty macro in \makehboxofhboxes. So it does not affect how the footnote paragraphs are typeset (the notes still have a penalty of -10 between them, which is added by \parafootfmt).

\mpparavfootnote This version is for minipages.

```

3304 \newcommand*{\mpparavfootnote}[2]{%
3305   \global\setbox\@nameuse{mp#1footins}\vbox{%
3306     \unvbox\@nameuse{mp#1footins}%
3307     \csuse{Xnotefontsize@#1}%
3308     \footfoldsplitskips
3309     \setbox0=\vbox{\hsize=\maxdimen%
3310       \let\bidi@RTL@everypar\empty%
3311       \insert@Xtxtbeforenotes{#1}%
3312       \noindent\color@begingroup%
3313       \csuse{Xbhooknote@#1}%
3314       \csname #1footfmt\endcsname #2{#1}\color@endgroup}%
3315     \setbox0=\hbox{\Xunvxh{0}{#1}}%
3316     \dp0=\z@
3317     \ht0=\csname #1footfudgefactor\endcsname\wd0
3318     \box0
3319     \penalty0
3320   }%

```

```
3321 %
3322 %
```

\Xunvxh Here is (modified) Michael's definition of \unvxh, used above. Michael's macro also takes care to remove some unwanted penalties and glue that TeX automatically attaches to the end of paragraphs. When TeX finishes a paragraph, it throws away any remaining glue, and then tacks on the following items: a \penalty of 10000, a \parfillskip and a \rightskip (*The TeXbook*, pp. 99–100). \unvxh cancels these unwanted paragraph-final items using \unskip and \unpenalty.

```
3323 \newcommand*{\Xunvxh}[2]{%
3324   \setbox0=\vbox{\unvbox#1%
3325     \global\setbox1=\lastbox}%
3326   \unhbox1
3327   \unskip          % remove \rightskip,
3328   \unskip          % remove \parfillskip,
3329   \unpenalty       % remove \penalty of 10000,
3330   \hskip\csuse{Xafternote@#2}\relax}% add the glue to go between the notes
3331 %
3332 %
```

\parafootfmt \parafootfmt is \normalfootfmt adapted to do the special stuff needed for paragraphed notes – leaving out the \endgraf at the end, sticking in special penalties and kern and leaving out the \footstrut. The first argument is the line and page number information, the second is the lemma, the third is the text of the footnote, and the fourth is the series (optional, for backward compatibility).

```
3333 \newcommand*{\parafootfmt}[4]{%
3334   \Xstorelineinfo{#1}{#4}%
3335   \Xinsertparafootsep{#4}%
3336   \ledsetnormalparstuff@common%
3337   \printlinefootnote{#1}{#4}%
3338   \print@lemma{#1}{#2}{#4}%
3339   \csuse{Xwrapcontent@#4}{#3}%
3340   \penalty-10 }
3341 %
```

Note that in the above definition, the penalty of -10 encourages a line break between notes, so that notes have a slight tendency to begin on new lines. The \Xinsertparafootsep command is used to insert the \Xparafootsep@series between each note in the *same* page.

\parafootgroup This footgroup code is modelled on the macros in *The TeXbook*, p. 399. The only difference is the \unpenalty in \makehboxofhboxes, which is there to remove the penalty of 0 which was added to the end of each footnote by \paravfootnote.

The call to \Xnotefontsize@ $\langle s \rangle$ is to ensure that the correct \baselineskip for the footnotes is used. The argument is the note series letter.

```
3342 \newcommand*{\parafootgroup}[1]{%
3343   \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
```

```

3344 \unvbox\csname #1footins\endcsname
3345 \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
3346 \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
3347 \makehboxofhboxes
3348 \setbox0=\hbox{\unhbox0 \removehboxes}%
3349 \csuse{Xhookgroup@#1}%
3350 \csuse{Xnotefontsize@#1}%
3351 \unhbox0\par%
3352 \global\hsize=\old@hsize%
3353 }%
3354 %
3355 %

```

\mpparafootgroup The minipage version.

```

3356 \newcommand*{\mpparafootgroup}[1]{%
3357   \setXnoteswidthliketwocolumns@{#1}%
3358   \vskip\skip@\nameuse{mp#1footins}%
3359   \ifl@dpairing\ifparledgroup%
3360     \leavevmode\marks\parledgroup@{begin}%
3361     \marks\parledgroup@series{#1}%
3362     \marks\parledgroup@type{Xfootnote}%
3363   \fi\fi\normalcolor
3364   \ifparledgroup%
3365     \ifl@dpairing%
3366     \else%
3367       \setXnoteswidthliketwocolumns@{#1}%
3368       \setXnotespositionliketwocolumns@{#1}%
3369       \print@Xfootnoterule{#1}%
3370   \fi%
3371   \else%
3372     \setXnoteswidthliketwocolumns@{#1}%
3373     \setXnotespositionliketwocolumns@{#1}%
3374     \print@Xfootnoterule{#1}%
3375   \fi%
3376   \unvbox\csname mp#1footins\endcsname
3377   \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
3378   \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
3379   \makehboxofhboxes
3380   \setbox0=\hbox{\unhbox0 \removehboxes}%
3381   \csuse{Xhookgroup@#1}%
3382   \csuse{Xnotefontsize@#1}%
3383   \nottoggle{Xparindent@#1}{\parindent=\z@}{}%
3384   \unhbox0\par}%
3385 %
3386 %

```

And finally, the two macros which are required to transform the long horizontal box stored in the insert' box to a printable text.

```
\makehboxofhboxes87 \newcommand*{\makehboxofhboxes}{\setbox0=\hbox{}%
\removehboxes88 \loop
  \unpenalty
  \setbox2=\lastbox
  \ifhbox2
    \setbox0=\hbox{\box2\unhbox0}%
  \repeat}
\newcommand*{\removehboxes}{\setbox0=\lastbox
\ifhbox0{\removehboxes}\unhbox0 \fi}
%
```

Insertion of the footnotes separator The command `\Xinsertparafootsep{<series>}` must be called at the beginning of `\parafootfm`.

```
\prevpage@num99 \newcommand{\Xinsertparafootsep}[1]{%
\Xinsertparafootsep00 \ifldRcol0%
  \ifnumequal{\csuse{#1prevpage@numR}}{\page@numR}%
    \ifcsdef{prevline#1}{ Be sur \prevline#1 exists.
      \ifcsequall{prevline#1}{lineinfo@}%
        \ifcsempty{Xsymlinenum@#1}{\csuse{Xparafootsep@#1}{}%}
          {\csuse{Xparafootsep@#1}}%
        }%
      {\csuse{Xparafootsep@#1}}%
    }%
  {}%
  \global\csname #1prevpage@numR\endcsname=\page@numR%
\else%
  \ifnumequal{\csuse{#1prevpage@num}}{\page@num}%
    \ifcsdef{prevline#1}{ Be sur \prevline#1 exists.
      \ifcsequall{prevline#1}{lineinfo@}%
        \ifcsempty{Xsymlinenum@#1}{\csuse{Xparafootsep@#1}{}%}
          {\csuse{Xparafootsep@#1}}%
        }%
      {\csuse{Xparafootsep@#1}}%
    }%
  {}%
  \global\csname #1prevpage@num\endcsname=\page@num%
\fi%
}
```

XIII.6.4 Columnar footnotes

Common tools

`\rigidbalance` We will now define macros for three-column notes and two-column notes. Both sets of macros will use `\rigidbalance`, which splits a box (#1) into into a number (#2) of
`\rigidbalanceX`

```
\rigidbalance
\splitoff
\dosplits
\@h
\@k
```

columns, each with a space (#3) between the top baseline and the top of the \vbox. The \rigidbalance macro is taken from *The TeXbook*, p. 397, with a slight change to the syntax of the arguments so that they do not depend on white space. Note also the extra unboxing in \splitoff, which allows the new \vbox to have its natural height as it goes into the alignment.

The L^AT_EX \line macro has no relationship to the TeX \line. The L^AT_EX equivalent is \@@line.

We do not call directly \rigidbalance, but we call \Xrigidbalance for critical notes and \rigidbalanceX for familiar notes. Both of them call \rigidbalance.

```

3425 \newcount\@k \newdimen\@h
3426 \newcommand*\Xrigidbalance[3]{%
3427   \hsize=\expandafter\dimexpr\csuse{Xwidth@\@currentseries}\relax%
3428   \rigidbalance{\#1}{\#2}{\#3}%
3429 }%
3430
3431 \newcommand*\rigidbalanceX[3]{%
3432   \hsize=\expandafter\dimexpr\csuse{widthX@\@currentseries}\relax%
3433   \rigidbalance{\#1}{\#2}{\#3}%
3434 }%
3435
3436 \newcommand*\rigidbalance[3]{%
3437   \setbox0=\box\@k \@k=\#2 \@h=\#3%
3438   \@@line{\splittopskip=\@h \vbadness=\@M \hfilneg
3439   \valign{\#\vfil\cr\dosplits}}}
3440
3441 \newcommand*\dosplits{\ifnum\@k>0 \noalign{\hfil}\splitoff
3442   \global\advance\@k-1\cr\dosplits\fi}
3443
3444 \newcommand*\splitoff{\dimen0=\ht0
3445   \divide\dimen0 by\@k \advance\dimen0 by\@h
3446   \setbox2\vsplit0 to \dimen0
3447   \unvbox2 }
3448 %
3449 %

```

Three columns

```

\Xarrangement@threecol\newcommand*\Xarrangement@threecol[1]{%
3450   \csgdef{series@display#1}{threecol}
3451   \expandafter\let\csname v#1footnote\endcsname=\threecolvfootnote
3452   \expandafter\let\csname #1footfmt\endcsname=\threecolfootfmt
3453   \expandafter\let\csname #1footgroup\endcsname=\threecolfootgroup
3454   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}%
3455   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3456   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3457   \threecolfootsetup{\#1}
3458 %
3459 %

```

The additional setup for minipages.

```

3460   \ifnoledgroup@{\else
3461     \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
3462     \expandafter\let\csname mp#1footgroup\endcsname=\mpthreecolfootgroup
3463     \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3464     \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3465     \mpthreecolfootsetup{#1}
3466   \fi
3467 }
3468 %
3469 %

```

The `\footstart` and `\footnoterule` macros for these notes assume the normal values (XIII.6.2 p. 188 above).

\threecolfootsetup The `\threecolfootsetup` macro calculates and sets some numbers for three-column footnotes.

We set the `\count` of the foot insert to 333. Each footnote can be thought of as contributing only one third of its height to the page, since the footnote insertion has been made as a long narrow column, which then gets trisectioned by the `\rigidbalance` routine (inside `\threecolfootgroup`). These new, shorter columns are saved in a box, and then that box is *put back* into the footnote insert, replacing the original collection of the footnotes. This new box is, therefore, only about a third of the height of the original one.

The `\dimen` value for this note series has to change in the inverse way: it needs to be three times the actual limit on the amount of space these notes are allowed to fill on the page, because when TeX is accumulating material for the page and checking that limit, it does not apply the `\count` scaling.

```

3470 \newcommand*{\threecolfootsetup}[1]{%
3471   \count\csname #1footins\endcsname 333
3472   \csxdef{default@#1footins}{333}%Use this to confine the notes to one
3473   side only
3474   \multiply\dimen\csname #1footins\endcsname \thr@@%
3475 %

```

\mpthreecolfootsetup The setup for minipages.

```

3475 \newcommand*{\mpthreecolfootsetup}[1]{%
3476   \count\csname mp#1footins\endcsname 333
3477   \multiply\dimen\csname mp#1footins\endcsname \thr@@%
3478 %
3479 %

```

\threecolvfootnote `\threecolvfootnote` This is the `\vfootnote` command for three-column notes. However, most of the code is deported on `\threecolvfootnote@` inserted. The call to `\Xnotefontsize@{s}` ensures that the `\splittopskip` and `\splitmaxdepth` take their values from the right `\strutbox`: the one used in a footnotes. Note especially

the importance of temporarily reducing the `\hsize` to 0.3 of its normal value. This determines the widths of the individual columns. So if the normal `\hsize` is (say) 10 cm, then each column will be $0.3 \times 10 = 3$ cm wide, leaving a gap of 1 cm spread equally between columns (i.e., .5 cm between each).

The arguments are #1 the note series letter and #1 the full text of the note (including numbers, lemma and text).

```

3480 \notbool{parapparatus@}{\newcommand*{\newcommand}{\threecolvfootnote}[2]{%
3481   \iftoggle{Xgroupbyline@#1}{%
3482     \prepare@Xgroupbyline[#1]{#2}{\threecolvfootnote@inserted}%
3483   }%
3484   {%
3485     \X@beforeinsertion{#1}%
3486     \insert\csname #1footins\endcsname{%
3487       \threecolvfootnote@inserted[#1]{#2}%
3488     }%
3489   }%
3490 }%
3491 %

```

```

\threecolvfootnote@inserted_92 \notbool{parapparatus@}{\newcommand*{\newcommand}{\threecolvfootnote@inserted}[2]{%
3493   \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3494   \noindent\csuse{Xhooknote@#1}%
3495   \csuse{Xnotefontsize@#1}%
3496   \footsplitskips%
3497   \csname #1footfmt\endcsname #2{#1}%
3498 }%
3499 %

```

`\threecolfootfmt` `\threecolfootfmt` is the command that formats one note. The arguments are #1 the line numbers, #2 the lemma and #4 the text of the `-footnote` command #4 optional (for backward compatibility): the series.

```

3500 \notbool{parapparatus@}{\newcommand*{\newcommand}{\threecolfootfmt}[4]{%
3501   \Xstorelineinfo{#1}{#4}%
3502   \threecol@begin@insert{#4}%
3503   \hspace{\parindent}%
3504   \printlinefootnote{#1}{#4}%
3505   \print@lemma{#1}{#2}{#4}%
3506   \csuse{Xwrapcontent@#4}{#3}%
3507   \nottoggle{Xgroupbyline@#4}{%
3508     {\strut\par\allowbreak}%
3509   }%
3510 }%
3511 %

```

`\threecol@begin@insert` The `\threecol@begin@insert` contains code used at the beginning of any `\insert` for critical footnotes in three columns. It is used both by `\threecolfootfmt` and by `\insert@Xtxtbeforenotes`.

```

3512 \newcommand{\threecol@begin@insert}[1]{%
3513   \normal@pars%
3514   \nottoggle{Xgroupbyline@#1}{%
3515     {\hsize \csuse{Xhsizethreecol@#1}}%
3516     {}%
3517     \nottoggle{Xparindent@#1}{\parindent=\z@}{%
3518       \tolerance=5000%
3519       \Xsethangindent{#1}%
3520       \tempdima=\parindent%
3521       \csuse{Xcolalign@#1}%
3522       \parindent=\tempdima%
3523       \strut%
3524     }%
3525   }%
3526 %

```

\threecolfootgroup And here is the `footgroup` macro that is called within the output routine to regroup the notes into three columns. Once again, the call to `\Xnotefontsize@<s>` is there to ensure that it is the right `\splittopskip`—the one used in footnotes—which is used to provide the third argument for `\rigidbalance`. This third argument (`\@h`) is the topskip for the box containing the text of the footnotes, and does the job of making sure the top lines of the columns line up horizontally. In *The TeXbook*, p. 398, Donald Knuth suggests retrieving the ouput of `\rigidbalance`, putting it back into the insertion box, and then printing the box. Here, we just print the `\line` which comes out of `\rigidbalance` directly, without any re-boxing.

```

3526 \newcommand*{\threecolfootgroup}[1]{%
3527   \begingroup%
3528   \csuse{Xbhookgroup@#1}%
3529   \csuse{Xnotefontsize@#1}%
3530   \par%
3531   \splittopskip=\ht\strutbox%
3532   \expandafter%
3533   \Xrigidbalance\csname #1footins\endcsname \thr@@ \splittopskip%
3534   \endgroup%
3535 }%
3536 %

```

\mpthreecolfootgroup The setup for minipages.

```

3537 \newcommand*{\mpthreecolfootgroup}[1]{{%
3538   \vskip\skip\nameuse{mp#1footins}%
3539   \ifl@dpairing\ifparledgroup%
3540     \leavevmode\marks\parledgroup@{begin}%
3541     \marks\parledgroup@series{#1}%
3542     \marks\parledgroup@type{Xfootnote}%
3543   \fi\fi\normalcolor%
3544   \ifparledgroup%
3545     \ifl@dpairing%
3546   \else%

```

```

3547   \setXnoteswidthliketwocolumns@{\#1}%
3548   \setXnotespositionliketwocolumns@{\#1}%
3549   \print@Xfootnoterule{\#1}%
3550   \fi%
3551 \else%
3552   \setXnoteswidthliketwocolumns@{\#1}%
3553   \setXnotespositionliketwocolumns@{\#1}%
3554   \print@Xfootnoterule{\#1}%
3555   \fi%
3556   \csuse{Xhookgroup@\#1}\par%
3557   \splittopskip=\ht\strutbox
3558   \expandafter
3559   \Xrigidbalance\csname mp\#1footins\endcsname \thr@@ \splittopskip}}%
3560 %
3561 %

```

Two columns

```

\Xarrangement@twocol \newcommand*{\Xarrangement@twocol}[1]{%
3562   \csgdef{series@display#1}{twocol}
3563   \expandafter\let\csname v\#1footnote\endcsname=\twocolvfootnote
3564   \expandafter\let\csname #1footfmt\endcsname=\twocolfootfmt
3565   \expandafter\let\csname #1footgroup\endcsname=\twocolfootgroup
3566   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@\#1}%
3567   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@\#1}%
3568   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@\#1}%
3569   \twocolfootsetup{\#1}
3570 %
3571 %

```

The additional setup for minipages.

```

3572 \ifnoledgroup@ \else
3573   \expandafter\let\csname mpv\#1footnote\endcsname=\mpnormalvfootnote
3574   \expandafter\let\csname mp\#1footgroup\endcsname=\mptwocolfootgroup
3575   \skip\csname mp\#1footins\endcsname=\csuse{Xbeforenotes@\#1}%
3576   \advance\skip\csname mp\#1footins\endcsname by\csuse{Xafterrule@\#1}%
3577   \mptwocolfootsetup{\#1}
3578 \fi
3579 }
3580 %
3581 %

```

\twocolfootsetup Here is a series of macros which are very similar to their three-column counterparts. In
 \twocolvfootnote this case, each note is assumed to contribute only a half a line of text. And the notes are
 \twocolvfootnote@inserted set in columns giving a gap between them of one tenth of the \hsize.
 \twocolfootfmt
 \twocolfootgroup
 \twocolfootgroup@ \newcommand*{\twocolfootsetup}[1]{%
 3582 \count\csname #1footins\endcsname 500
 3583 \csxdef{default@\#1footins}{500}%
 3584 }

```

3585   \multiply\dimen\csname #1footins\endcsname \tw@%
3586 %

3587 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolvfootnote}[2]{%
3588   \iftoggle{Xgroupbyline@#1}{%
3589     \prepare@Xgroupbyline{#1}{#2}{\twocolvfootnote@inserted}%
3590   }{%
3591     \X@beforeinsertion{#1}%
3592     \insert\csname #1footins\endcsname{%
3593       \twocolvfootnote@inserted{#1}{#2}%
3594     }%
3595   }%
3596 }%
3597 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolvfootnote@inserted}[2]{%
3598   \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3599   \noindent\csuse{Xbhooknote@#1}%
3600   \csuse{Xnotefontsize@#1}%
3601   \footskip%
3602   \csname #1footfmt\endcsname #2{#1}%
3603 }%
3604 %

3605 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolfootfmt}[4]{% 4th
3606   arg is optional, for backward compatibility
3607   \Xstorelineinfo{#1}{#4}%
3608   \twocol@begin@insert{#4}%
3609   \hspace{\parindent}%
3610   \printlinefootnote{#1}{#4}%
3611   \print@lemma{#1}{#2}{#4}%
3612   \csuse{Xwrapcontent@#4}{#3}%
3613   \nottoggle{Xgroupbyline@#4}{%
3614     {\strut\par\allowbreak}%
3615   }%
3616 }%
3617 %

3618 \newcommand{\twocol@begin@insert}[1]{%
3619   \normal@pars%
3620   \hsize \csuse{Xhsize@#1}%
3621   \nottoggle{Xparindent@#1}{\parindent=\z@}{%
3622     \tolerance=5000%
3623     \Xsethangindent{#1}%
3624     \tempdima=\parindent%
3625     \csuse{Xcolalign@#1}%
3626     \parindent=\tempdima%
3627     \strut%
3628   }%
3629 \newcommand*{\twocolfootgroup}[1]{%

```

```

3630 \begingroup%
3631   \csuse{Xbhookgroup@#1}%
3632   \csuse{Xnotefontsize@#1}%
3633   \par%
3634   \splittopskip=\ht\strutbox%
3635   \expandafter%
3636   \Xrigidbalance\csname #1footins\endcsname \tw@ \splittopskip%
3637 \endgroup%
3638 }%
3639 %
3640 %

```

\mptwocolfootsetup The versions for minipages.

\mptwocolfootgroup

```

3641 \newcommand*{\mptwocolfootsetup}[1]{%
3642   \count\csname mp#1footins\endcsname 500
3643   \multiply\dimen\csname mp#1footins\endcsname \tw@}
3644 %

```

```

3645 \newcommand*{\mptwocolfootgroup}[1]{{%
3646   \vskip\skip\@nameuse{mp#1footins}
3647   \ifl@dpairing\ifparledgroup%
3648     \leavevmode\marks\parledgroup@{begin}%
3649     \marks\parledgroup@series{#1}%
3650     \marks\parledgroup@type{Xfootnote}%
3651   \fi\fi\normalcolor
3652   \ifparledgroup%
3653     \ifl@dpairing%
3654     \else%
3655       \setXnoteswidthliketwocolumns@{#1}%
3656       \setXnotespositionliketwocolumns@{#1}%
3657       \print@Xfootnoterule{#1}%
3658     \fi%
3659   \else%
3660     \setXnoteswidthliketwocolumns@{#1}%
3661     \setXnotespositionliketwocolumns@{#1}%
3662     \print@Xfootnoterule{#1}%
3663   \fi%
3664   \csuse{Xbhookgroup@#1}\par%
3665   \splittopskip=\ht\strutbox%
3666   \expandafter%
3667   \Xrigidbalance\csname mp#1footins\endcsname \tw@ \splittopskip}%
3668 %
3669 %

```

XIII.7 Footnote hanging indent

\Xsethangindent \Xsethangindent sets the hangindent for a critical footnote, while \sethangindentX does it for a familiar footnote.

```

3670 \newcommand{\Xsethangindent}[1]{%
3671   \if@RTL%
3672     \hangindent=-\csuse{Xhangindent@#1}%
3673     \everypar{\hangindent=-\csuse{Xhangindent@#1}}%
3674   \else%
3675     \hangindent=\csuse{Xhangindent@#1}%
3676     \everypar{\hangindent=\csuse{Xhangindent@#1}}%
3677   \fi%
3678 }%
3679 \newcommand{\sethangindentX}[1]{%
3680   \if@RTL%
3681     \hangindent=-\csuse{hangindentX@#1}%
3682     \everypar{\hangindent=-\csuse{hangindentX@#1}}%
3683   \else%
3684     \hangindent=\csuse{hangindentX@#1}%
3685     \everypar{\hangindent=\csuse{hangindentX@#1}}%
3686   \fi%
3687 }%
3688 %

```

XIII.8 Critical notes presentation

Here, we define some commons macro which are used in order to print a critical notes, that is a note with 1) line number 2) lemma 3) lemma separator 4) text associated to the lemma.

XIII.8.1 Font tools

\endashchar The fonts that are used for printing notes might not have the character mapping we expect: for example, the Computer Modern font that contains old-style numerals does not contain an en-dash or square brackets, and its period and comma are in odd locations. To allow use of the standard footnote macros with such fonts, we use the following macros for certain characters.

The `\endashchar` macro is simply an en-dash from the normal font and is immune to changes in the surrounding font. The same goes for the full stop. These two are used in `\printlines`. The right bracket macro is the same again; it crops up in `\normalfootfmt` and the other footnote macros for controlling the format of the footnotes.

Note that these commands are not directly called by `reledmac`, but are enclosed as default value of specific hooks. Consequently, people should not redefine them, but use instead the `\Xlinerangeseparator`, `\Xendlinerangeseparator`, `\Xsublinesep`, `\Xendsublinesep` and `\Xlemmaseparator` macros.

With `polyglossia`, each critical note has a `\footnote@lang` which shows the language of the lemma, and which can be used to switch the bracket from right to left.

```

3689 \def\endashchar{\textnormal{--}}
3690
3691 \newcommand*\fullstop{\textnormal{.}}

```

```

3692 \def\Xsublinesep@side{\fullstop}
3693
3694 \newcommand*{\rbracket}{\textnormal{%
3695   \csuse{text}\csuse{footnote@lang}{%
3696     \ifluatex%
3697       \ifdefstring{\footnote@luatextextdir}{TRT}{\thinspace[]}{\thinspace
3698     }%
3699     \else%
3700       \thinspace]%
3701     \fi}%
3702   }%
3703 }
3704 %

```

XIII.8.2 Pstart number in footnote

`\printpstart` The `\printpstart` macro prints the pstart number for a note.

```

3705 \newcommand{\printpstart}[0]{%
3706   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
3707     l@dprintingcolumns}}{%
3708     \ifledRcol%
3709       \theppstartR%
3710     \else%
3711       \theppstartL%
3712     \fi%
3713   }{%
3714     \theppstart%
3715   }%
3716 %

```

XIII.8.3 Lemma printing

`\print@lemma` `\print@lemma` is called inside critical footnotes to print the lemma and the lemma separator (#1: line number and font information, #2: lemma, #3: series).

```

3717 %
3718 \newcommand{\print@lemma}[3]{%
3719   \bgroup%
3720   \notoggle{Xlemmadisablefontselection@#3}%
3721   {\select@lemmafont#1}%
3722   {}%
3723   \bgroup%
3724   \csuse{Xlemmafont@#3}%Deprecated
3725   \csuse{Xwraplemma@#3}{#2}%
3726   \egroup%
3727   \egroup%

```

```

3728 \iftoggle{nosep@}{%
3729   \hskip\csuse{Xinplaceoflemmaseparator@#3}%
3730   \relax%
3731 }%
3732 {\ifcsempty{Xlemmaseparator@#3}%
3733   {%
3734     \hskip\csuse{Xinplaceoflemmaseparator@#3}%
3735     \relax%
3736   }%
3737   {%
3738     \nobreak%
3739     \hskip\csuse{Xbeforelemmaseparator@#3}%
3740     \csuse{Xlemmaseparator@#3}%
3741     \hskip\csuse{Xafterlemmaseparator@#3}%
3742     \relax%
3743   }%
3744 }%
3745 }%
3746 %

```

XIII.8.4 Line number printing

\Xstorelineinfo The `\Xstorelineinfo` macro is used to store some data about line number of the current critical footnote, data which will be reused later for the `\Xnumberonlyfirstinline` and related setting.

#1 footnote specification for the current footnote; #2 footnote series.

```

3747 \newcommand{\Xstorelineinfo}[2]{%
3748   \l@dp@rsefootspec#1|%
3749   \iftoggle{Xnumberonlyfirstintwolines@#2}{%
3750     \xdef\lineinfo@{\l@dparsedstartline - \l@dparsedstartsub - \
3751     \l@dparsedendline - \l@dparsedendsub}%
3752   }%
3753   \xdef\lineinfo@{\l@dparsedstartline - \l@dparsedstartsub}%
3754 }%
3755 }%
3756 %

```

\printlinefootnote The `\printlinefootnote` macro is called in each `\<type>footfmt` command. It controls whether the line number is printed or not, according to the series options. Its first argument is the information about lines; its second is the series of the footnote. The printing of the line number is shared in `\printlinefootnotenumbers`.

```

3757 \newcommand{\printlinefootnote}[2]{%
3758   \iftoggle{nonum@}{% Try if the line number must printed for this specific
3759   not (by default, yes)
3760     \hspace{\csuse{Xinplaceofnumber@#2}}%
3761   }%
3762 %

```

```

3761   {%
3762     {%
3763       \iftoggle{Xnonumber@#2}{% Try if the line number must printed (by
3764         default, yes)
3765           {%
3766             \hspace{\csuse{Xinplaceofnumber@#2}}%
3767           }%
3768           {%
3769             {\iftoggle{Xnumberonlyfirstinline@#2}{% If for this series the
3770               line number must be printed only in the first time.
3771                 {%
3772                   \ifcsdef{prevline#2}{%
3773                     {%
3774                       {\%Be sure the \prevline exists.
3775                         \ifcsequal{prevline#2}{\lineinfo@}{% Try it
3776                           {%
3777                             \ifcsempty{Xsymlinenum@#2}{%
3778                               {%
3779                                 \hspace{\csuse{Xinplaceofnumber@#2}}%
3780                               }%
3781                               {%
3782                                 {\printlinefootnotearea{#2}}%
3783                               }%
3784                               {%
3785                                 \printlinefootnotearea{#1}{#2}%
3786                               }%
3787                               }%
3788                               {%
3789                                 \printlinefootnotearea{#1}{#2}%
3790                               }%
3791                               {\csxdef{prevline#2}{\lineinfo@}%
3792                               }%
3793                               }%
3794                               }%
3795                           }%
3796                         }%
3797                         }%
3798           }%
3799         }%
3800       \csuse{Xnotenumfont@#1}%
3801       \ifdimequal{\csuse{Xboxsymlinenum@#1}}{\z@}{%
3802         {\csuse{Xsymlinenum@#1}}%
3803         {\hbox to \csuse{Xboxsymlinenum@#1}{%
3804           {\csuse{Xsymlinenum@#1}\hfill}}%

```

\printsymlinefootnotearea This macro prints the space before the line symbol, changes the font, when prints the line symbol and the space after it.

```

3798 \newcommand{\printsymlinefootnotearea}[1]{%
3799   \hspace{\csuse{Xbeforesymlinenum@#1}}%
3800   \csuse{Xnotenumfont@#1}%
3801   \ifdimequal{\csuse{Xboxsymlinenum@#1}}{\z@}{%
3802     {\csuse{Xsymlinenum@#1}}%
3803     {\hbox to \csuse{Xboxsymlinenum@#1}{%
3804       {\csuse{Xsymlinenum@#1}\hfill}}%

```

```

3805      }%
3806      \hspace{\csuse{Xaftersymlinenum@#1}}%
3807  }%
3808 %

```

\printlinefootnotearea This macro prints the space before the line number, changes the font, then prints the line number and the space after it. It is called by `\printlinefootnote` depending of the options about repeating line numbers. The first argument is line information, the second is the notes series (A, B, C, etc.)

```

3809 \newcommand{\printlinefootnotearea}[2]{%
3810   \printXbeforenumber{#2}%
3811   \csuse{Xnotenumfont@#2}%
3812   \boxfootnotenumbers{#1}{#2}%
3813   \printXafternumber{#2}%
3814 }%
3815 %

```

\boxfootnotenumbers Depending on the user settings, this macro will box line numbers (or not). The first argument is line information, the second is the notes series (A, B, C, etc.) The previous `\printlinefootnotearea` calls it.

```

3816 \newcommand{\boxfootnotenumbers}[2]{%
3817   \ifdim\equal{\csuse{Xboxlinenum@#2}}{0pt}{%
3818     \printlinefootnotenumbers{#1}{#2}%
3819   }%
3820   \{%
3821     \hbox to \csuse{Xboxlinenum@#2}{%
3822       \{%
3823         \IfSubStr{RC}{\csuse{Xboxlinenumalign@#2}}{\hfill}{}%
3824         \printlinefootnotenumbers{#1}{#2}%
3825         \IfSubStr{LC}{\csuse{Xboxlinenumalign@#2}}{\hfill}{}%
3826       }%
3827     }%
3828   }%
3829 %

```

\printlinefootnotenumbers This macro prints, if needed, the pstart number and the line number. The first argument is line information, the second is the notes series (A, B, C, etc.) The previous `\boxlinefootnote` calls it.

```

3830 \newcommand{\printlinefootnotenumbers}[2]{%
3831   \xdef\@currentseries{#2}%
3832   \ifboolexpr{%
3833     (togl{Xpstart@#2} and bool{numberpstart})%
3834     or togg{Xpstarteverytime@#2}}{%
3835     {\printpstart}{}%
3836     \iftoggle{Xstanza@#2}{%
3837       \ifnumberstanza{%

```

```

3838     \printstanza%
3839     \csuse{Xstanzaseparator@#2}%
3840     \fi%
3841   }{}%
3842   \iftoggle{Xonlypstart@#2}{}{%
3843     \csuse{Xtxtbeforenumber@#2}%
3844     \printlines#1|\ifledRcol@\ORlineflag\fi|}%
3845   }%
3846 %

```

`\printXbeforenumber` This macro prints a space (before the line number) in footnote. It is called by `\printlinefootnotearea`. Its only argument is the note series (A, B, C, etc.)

```

3847 \newcommand{\printXbeforenumber}[1]{%
3848   \hspace{\csuse{Xbeforenumber@#1}}%
3849 }%
3850 %

```

`\printXafternumber` This macro prints the space, adding eventually a `\nobreak`, after the line number, in footnote. It is called by `\printlinefootnotearea`. Its only argument is the series

```

3851 \newcommand{\printXafternumber}[1]{%
3852   \iftoggle{Xnonbreakableafternumber@#1}{\nobreak}{}
3853   \hspace{\csuse{Xafternumber@#1}}%
3854 }%
3855 %

```

If we have decided to print the line number in a specific notes, the `\printlines` macro prints the line numbers for a note—which, in the general case, is a rather complicated task. The seven parameters of the argument are the line numbers as stored in `\l@d@nums`, in the form described on V.9 p. 107: the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma.

`edmac`' creator have defined six boolean in order to know which component of line number description we have to print:

- `\ifl@d@pnum` for page numbers;
- `\ifl@d@ssub` for starting sub-line;
- `\ifl@d@elin` for ending line;
- `\ifl@d@esl` for ending sub-line; and
- `\ifl@d@dash` for the dash between the starting and ending groups.

There is no boolean for the line number because it is always printed.

Maïeul Rouquette has added `\ifl@d@Xtwolines` and `\ifl@d@Xmorethantwolines` to print a symbol which stands for “and subsequent” when there are two, three or more lines. Is also defines `\cannot@start@print` and `\cannot@end@print` which define annotations associated with the starting and ending line numbers in critical footnotes.

```

\ifl@d@pnum56 \newif\ifl@d@pnum
\ifl@d@ssub57 \newif\ifl@d@ssub
\ifl@d@elin58 \newif\ifl@d@elin
\ifl@d@esl59 \newif\ifl@d@esl
\ifl@d@dash60 \newif\ifl@d@dash
\ifl@d@Xtwolines3861 \newif\ifl@d@Xtwolines%
\ifl@d@Xmorethantwolines3862 \newif\ifl@d@Xmorethantwolines%
\let\@cannot@start@print\relax3863
\let\@cannot@end@print\relax3864
\@cannot@end@print3865
%
```

\l@dparsefootspec \l@dparsefootspec{\langle spec\rangle}{\langle lemma\rangle}{\langle text\rangle} parses a footnote specification. \langle lemma\rangle and \langle text\rangle are the lemma and text respectively. \langle spec\rangle is the line and page number and lemma font specifier in \l@d@nums style format. The real work is done by \l@dp@rsefootspec which defines macros holding the numeric values. In many cases, \l@dparsedstartpage \l@dparsedstartline \l@dparsedstartsub \l@dparseendpage \l@dparseendline \l@dparseendsub this last command is called directly. Just a reminder of the arguments:

```

\printlines #1 | #2 | #3 | #4 | #5 | #6 | #7
\printlines start-page | line | subline | end-page | line | subline | fontflag
\newcommand*\l@dparsefootspec[3]{\l@dp@rsefootspec#1|}
\def\l@dp@rsefootspec#1|#2|#3|#4|#5|#6|#7|{%
  \gdef\l@dparsedstartpage{#1}%
  \gdef\l@dparsedstartline{#2}%
  \gdef\l@dparsedstartsub{#3}%
  \gdef\l@dparseendpage{#4}%
  \gdef\l@dparseendline{#5}%
  \gdef\l@dparseendsub{#6}%
}
%
```

Initialise the several number value macros.

```

\def\l@dparsedstartpage{0}%
\def\l@dparsedstartline{0}%
\def\l@dparsedstartsub{0}%
\def\l@dparseendpage{0}%
\def\l@dparseendline{0}%
\def\l@dparseendsub{0}%
%
```

\setprintlines The macro \setprintlines does the work of deciding what numbers should be printed. Its arguments are the same as the first 6 of \printlines.

```

\newcommand*\setprintlines[6]{%
  \let\@cannot@start@print\relax%
  \let\@cannot@end@print\relax%
  \l@d@pnumfalse%
  \l@d@dashfalse%
  \l@d@elinfalse%
}
%
```

We print the page numbers only if: 1) we are doing the lineation by page, and 2) the ending page number is different from the starting page number.a

```

3891 \ifbypage@
3892   \ifnum#4=#1 \else
3893     \l@d@pnumtrue
3894     \l@d@dashtrue
3895   \fi
3896 \fi
3897 %

```

We print the ending line number if: (1) we are printing the ending page number, or (2) the ending line number is different from the starting line number. If either of these conditions is true, we also print the annotation linked to the ending line number annotations.

```

3698 \ifboolexpr{%
3699   bool{\l@d@pnum}%
3700   or not test{\ifnumequal{#2}{#5}}%
3701 }{%
3702   \l@d@elintrue%
3703   \l@d@dashtrue%
3704   \unless\ifx\relax\annot@end%
3705   \def\@annot@end@print{%
3706     \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{%
3707       \annot@end}%
3708     }%
3709   }{%
3710 %

```

We define the starting line number annotation as a merge of the starting annotation and ending annotation if we don't print the ending line number. Otherwise, it is only the starting annotation.

```

3911 \ifl@d@elin{%
3912   \def\@annot@start@print{%
3913     \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{%
3914       \annot@start}%
3915     }%
3916   \else%
3917     \ifx\annot@start\annot@end%
3918     \unless\ifx\annot@start\relax%
3919     \def\@annot@start@print{%
3920       \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{%
3921         \annot@start}%
3922       }%
3923     \fi%
3924   \else%
3925     \ifx\@annot@end@print\relax%
3926     \def\@annot@start@print{%
3927       \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{%

```

```

3926      \ifx\annot@start\empty\else%
3927          \annot@start%
3928          \ifdefined\linerangesep@\%
3929              \linerangesep@\%
3930          \else%
3931              \csuse{Xlinerangeseparator@\currentseries}%
3932          \fi%
3933          \fi%
3934          \annot@end%
3935      }%
3936  }%
3937  \else%
3938      \let\cannot@start@print\cannot@end@print%
3939      \let\cannot@end@print\relax%
3940      \fi%
3941      \fi%
3942      \fi%
3943  %

```

We print the starting sub-line if it is nonzero.

```

3944  \l@d@ssubfalse
3945  \ifnum#3=0 \else
3946      \l@d@ssubtrue
3947  \fi
3948 %

```

We print the ending sub-line if it is nonzero and: (1) it is different from the starting sub-line number, or (2) the ending line number is being printed.

```

3949  \l@d@eslfalse
3950  \ifnum#6=0 \else
3951      \ifnum#6=#3
3952          \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
3953      \else
3954          \l@d@esltrue
3955          \l@d@dashtrue
3956      \fi
3957  \fi%
3958 %

```

However, if the `\Xtwolines` is set for the current series, we do not print the last line number.

```

3959  \ifl@d@dash%
3960      \ifboolexpr{togl{fulllines@} or test{\ifcsempty{Xtwolines@\%
3961 @currentseries}}}{%
3962          {}%
3963          {}%
3964          \setistwo{followinglines}{#1}{#2}{#4}{#5}%
3965          \ifboolexpr{%
3966              {}%

```

```

3966      togl {Xtwolinesbutnotmore@{@currentseries}%
3967      and not%
3968      (%
3969      bool {istwofollowinglines@}%
3970      )%
3971      )%
3972      or%
3973      (%
3974      (not test{\ifnumequal{#1}{#4}})%
3975      and togl{Xtwolinesonlyinsamepage@{@currentseries}%
3976      }%
3977      }%
3978      {}%
3979      {}%
3980      \l@d@dashfalse%
3981      \l@d@Xtwolinestrue%
3982      \l@d@elinfalse%
3983      \l@d@eslfalse%
3984      \ifcsempy{Xmorethan twolines@{@currentseries}%
3985      {}%
3986      {\ifistwofollowinglines@{\else}%
3987      \l@d@Xmorethan twolinestrue%
3988      \fi%
3989      }%
3990      }%
3991      }%
3992      \fi%
3993  %

```

If the `\Xnoidenticalinenumannotation` is set for this series, we check if the ending annotation is identical to the starting. If true, we don't print the ending annotation

```

3994  \iftoggle{Xnoidenticalinenumannotation@{@currentseries}%
3995  \ifx\annot@start\annot@end%
3996  \let\@annot@end@print\relax%
3997  \ifx\linenumrep\@gobble%Don't print the dash if we're not printing
the line number
3998  \l@d@dashfalse%
3999  \fi%
4000  \fi%
4001  }{}%
4002 %

```

End of `\setprintlines`.

```

4003 }%
4004 %

```

\setistwofollowinglines The `\ifistwofollowinglines` boolean, used by the `\Xtwolines` and related setting, is set to true by `\setistwofollowinglines`. This command takes the following arguments:

- #1 First page number.
- #2 First line number.
- #3 Last page number.
- #4 Last line number.

If $\#3 - \#2 = 1$, then that means the two lines are subsequent, and consequently `\ifistwofollowinglines` is set to true. However, if we use lineation by page, two given lines can be subsequent if:

- The first line number is equal to the last line number of the first page.
- The last line number is equal to 1.
- $\#3 - \#1$ is equal to 1.

```

4005 \newif\ifistwofollowinglines%
4006 \newcommand{\setistwofollowinglines}[4]{%
4007   \ifcsdef{lastlinenumberon@\#1}%
4008     {\numdef{\tmp}{\csuse{lastlinenumberon@\#1}}}%
4009     {\numdef{\tmp}{0}}%
4010   \istwofollowinglines@false%
4011   \ifnumequal{\#4-\#2}{1}%
4012     {\istwofollowinglines@true}%
4013     {\ifbypage@%
4014       \ifnumequal{\#3-\#1}{1}%
4015       {%
4016         \ifnumequal{\#2}{\tmp}%
4017           {\ifnumequal{\#4}{1}{\istwofollowinglines@true}{}}
4018           {}%
4019       }%
4020       {}%
4021     \fi%
4022   }%
4023 }%
4024 %

```

`\printlines` So, we have decided which part of line number sets will be printed depending of these value. Now we are ready to print them. If the lineation is by pstart, we print the pstart. Arguments are 1) start page number 2) start line number 3) start subline number 4) end page number 5) end line number 6) end subline number 7) font specification 8) side flag

```

4025 \def\printlines#1|#2|#3|#4|#5|#6|#7|#8|{%
4026   \begingroup%
4027 %

```

If we use `LuaTeX`, ensure we use good text's direction.

```

4028 \ifluatex%
4029   \edef\@tmp{\the\textrm{dir}}%
4030   \ifdefstring{\@tmp}{TLT}{}{\textrm{dir} TLT}%Test in order to prevent
      spurious space (bug #397)
4031   \fi%
4032 %

```

Decide which part of line number components we will print.

```

4033 \setprintlines{#1}{#2}{#3}{#4}{#5}{#6}%
4034 %

```

One subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could come after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period). So, first, print the start line number.

```

4035 \ifdim\currentseries=0pt%
4036   {\bgroup}%
4037   {\leavevmode\hbox to \currentseries\bgrouphfill}%
4038   \ifcsstring{Xlinenumannotationposition@\currentseries}{before}%
4039     {\cannotstart}%
4040     {}%
4041   \ifld@pnum%
4042     \wrap@edcrossref{@this@crossref@start}{#1}%
4043     \csuse{Xpagelinesep@\currentseries}%
4044   \fi%
4045   \wrap@edcrossref{@this@crossref@start}{%
4046     \linenumrep{#2}%
4047     \iftoggle{Xlineflag@\currentseries}{#8}{%}
4048   }%
4049   \ifld@ssub%
4050     \csuse{Xsublinesep@\currentseries}%
4051     \wrap@edcrossref{@this@crossref@start}{\sublinenumrep{#3}}%
4052   \fi
4053   \ifcsstring{Xlinenumannotationposition@\currentseries}{after}%
4054     {\cannotstart}%
4055     {}%
4056   \egroup%
4057 %

```

Then print the dash + end line number, or the range symbol.

```

4058 \ifdim\currentseries=0pt%
4059   {\bgroup}%
4060   {\hbox to \currentseries\bgrouphfill}%
4061   \ifld@Xtwolines%
4062     \ifld@Xmorethanwolines%
4063       \csuse{Xmorethanwolines@\currentseries}%
4064     \else%
4065       \csuse{Xtwolines@\currentseries}%

```

```

4066      \fi%
4067      \else%
4068      \ifl@d@dash%
4069      \ifdefineline@sep@%
4070      \line@sep@%
4071      \else%
4072      \csuse{Xlinerangeseparator@\@currentseries}%
4073      \fi%
4074      \fi%
4075      \ifcsstring{Xlinenumannotationposition@\@currentseries}{before}%
4076      {\@cannot@end@print}%
4077      {}%
4078      \ifl@d@pnum%
4079      \wrap@edcrossref{\@this@crossref@end}{#4}%
4080      \csuse{Xpagelinesep@\@currentseries}%
4081      \fi%
4082      \ifl@d@elin%
4083      \wrap@edcrossref{\@this@crossref@end}{%
4084      \linenumrep{#5}%
4085      \iftoggle{Xlineflag@\@currentseries}{#8}{}%
4086      }%
4087      \fi%
4088      \ifl@d@esl%
4089      \ifl@d@elin%
4090      \csuse{Xsublinesep@\@currentseries}%
4091      \fi%
4092      \wrap@edcrossref{\@this@crossref@end}{\sublinenumrep{#6}}%
4093      \fi%
4094      \ifcsstring{Xlinenumannotationposition@\@currentseries}{after}%
4095      {\@cannot@end@print}%
4096      {}%
4097      \fi%
4098      \ifdim\equal{\csuse{Xboxendlinenum@\@currentseries}}{0pt}%
4099      {}%
4100      {\hfill}\% Prevent underfull hbox
4101      \egroup%
4102      \endgroup%
4103  }%
4104 %

```

XIII.8.5 Footnote grouped by line

\prepare@Xgroupbyline \prepare@Xgroupbyline is a macro called on the \meta{XXXvfootnote} if \Xgroupbyline is set to true, instead of calling \insert directly.

- #1 The series
- #2 The content of the footnote, which is also the line number indication
- #3 This macro, which prepares the contents of the insertion

```

4105 \newcommand{\prepare@Xgroupbyline}[3]{%

```

```

4106   \iftoggle{Xgroupbylinesseparatetwo{#1}{%
4107     \l@dparsesfootspec#2%
4108     \ifcsdef{#1@forinserting@}{\l@dparsedendpage-\l@dparsedendline-\%
4109       \l@dparsedendsub}{%
4110         {%
4111           \csgappto{#1@forinserting@}{\l@dparsedendpage-\l@dparsedendline-\%
4112             \l@dparsedendsub}{%
4113               \hskip\csuse{Xafternote@#1}\relax%
4114             }%
4115           }%
4116         }%
4117         \add@hooktoggle@specific@to@cs{#1@forinserting@}{\l@dparsedendpage-\%
4118           \l@dparsedendline-\l@dparsedendsub}{%
4119             \add@hookarg@specific@to@cs{#1@forinserting@}{\l@dparsedendpage-\%
4120               \l@dparsedendline-\l@dparsedendsub}{%
4121                 \csgappto{%
4122                   {#1@forinserting@}{\l@dparsedendpage-\l@dparsedendline-\l@dparsedendsub}%
4123                 }%
4124                 \keep@this@crossref@forinserting%
4125                 \unexpanded{%
4126                   \ifcsempty{Xsymlinenum@#1}{%
4127                     {\csuse{Xparafootsep@#1}}%
4128                     {}%
4129                     #3{#1}{#2}%
4130                   }%
4131                 }%
4132                 \listcsxadd{#1@forinserting}{\l@dparsedendpage-\l@dparsedendline-\%
4133                   \l@dparsedendsub}{%
4134                 }{%
4135                   \ifcsdef{#1@forinserting@all}{%
4136                     \csgappto{%
4137                       {#1@forinserting@all}%
4138                       {\hskip\csuse{Xafternote@#1}\relax}%
4139                     }{%
4140                       \add@hooktoggle@specific@to@cs{#1@forinserting@all}{%
4141                         \add@hookarg@specific@to@cs{#1@forinserting@all}{%
4142                           \csgappto{%
4143                             {#1@forinserting@all}%
4144                             \keep@this@crossref@forinserting%
4145                             \unexpanded{%
4146                               \ifcsempty{Xsymlinenum@#1}{%
4147                                 {\csuse{Xparafootsep@#1}}%
4148                                 {}%
4149                                 #3{#1}{#2}%
4150                               }%
4151                             }%
4152                           }{%
4153                             \listcsgadd{#1@forinserting}{all}{%
4154                               }%
4155                             }%
4156                           }%
4157                         }%
4158                       }%
4159                     }%
4160                   }%
4161                 }%
4162               }%
4163             }%
4164           }%
4165         }%
4166       }%
4167     }%
4168   }%
4169 }
```

```
4150 }%
4151 %
```

`his@crossref@forinserting` \keep@this@crossref@forinserting is called by \prepare@Xgroupbyline. It just ensures that \atthis@crossref@start and \this@crossref@end value are kept in memory.

```
4152 \newcommand{\keep@this@crossref@forinserting}{%
4153   \unexpanded{\gdef\atthis@crossref@start}{\atthis@crossref@start}%
4154   \unexpanded{\gdef\this@crossref@end}{\atthis@crossref@end}%
4155 }%
4156 %
```

XIV Familiar footnotes

XIV.1 Adjacent footnotes

The original edmac provided users with five series of critical footnotes (\Afootnote \Bfootnote \Cfootnote \Dfootnote \Efootnote), and L^AT_EX provides a single numbered footnote. The reledmac package uses the edmac mechanism to provide six series of numbered footnotes.

First, though, the footmisc package has an option whereby two or more consecutive \footnotes have their marks separated by commas. This seemed to Peter Wilson such a useful ability that it was provided automatically by eledmac.

Maïeul Rouquette has maintained this feature in reledmac, despite he thought that is not directly in relationship with the aim of reledmac.

`\multiplefootnotemarker` These macros may have been defined by the memoir class, are provided by the footmisc package and perhaps by other footnote packages. That is why we use \providecommand and not \newcommand.

```
4157 \providecommand*\multiplefootnotemarker{3sp}
4158 \providecommand*\multfootsep{\textsuperscript{\normalfont,}}
4159 %
4160 %
```

`\m@mmf@prepare` A pair of self-cancelling kerns. This may have been defined in the memoir class.

```
4161 \providecommand*\m@mmf@prepare{%
4162   \kern-\multiplefootnotemarker
4163   \kern\multiplefootnotemarker\relax}
4164 %
```

`\m@mmf@check` This may have been defined in the memoir class. If it recognises the last kern as \multiplefootnotemarker it typesets \multfootsep.

```

4165 \providecommand*\m@mmf@check}{%
4166   \ifdim\lastkern=\multiplefootnotemarker\relax
4167     \edef\x@sf{\the\spacefactor}%
4168     \unkern
4169     \multfootsep
4170     \spacefactor\x@sf\relax
4171   \fi}
4172 %
4173 %

```

We have to modify `\@footnotetext` and `\@footnotemark`. However, if `memoir` is used the modifications have already been made.

```

4174 \@ifclassloaded{memoir}{}{%
4175 %

```

`\@footnotetext` Add `\m@mmf@prepare` at the end of `\@footnotetext`.

```

4176 \apptocmd{\@footnotetext}{\m@mmf@prepare}{}{%
4177 %

```

`\@footnotemark` Modify `\@footnotemark` to cater for adjacent `\footnotes`.

```

4178 %
4179 \patchcmd{\@footnotemark}
4180   {\nobreak}
4181   {\m@mmf@check
4182   \nobreak
4183   }
4184   {}{%
4185 \patchcmd{\@footnotemark}
4186   {\@makefnmark}
4187   {\@makefnmark
4188   \m@mmf@prepare
4189   }
4190   {}{%
4191 %

```

Finished the modifications for the non-memoir case.

```

4192 }
4193 %
4194 %

```

XIV.2 Regular footnotes for numbered texts

`\l@dold@footnotetext` In order to enable the regular `\footnotes` in numbered text we have to play around with its `\@footnotetext`, using different forms for when in numbered or regular text.

```
4195 \pretocmd{\@footnotetext}{%
4196   \ifnumberedpar@
4197     \edtext{}{(\l@dbfnote{\#1})}%
4198   \else
4199     \{}{}\}
4200 \apptocmd{\@footnotetext}{\fi}{}{%
4201 }
```

```

\l@dbfnote \l@dbfnote adds the footnote to the insert list, and \vl@dbfnote calls the original
\vl@dbfnote \@footnotetext. We also patch \footnote in order to get the correct footnote
\vl@dbfnote numbers when typesetting parallel texts. This is moved into a \get@fnmark command.

\footnote
\get@fnmark
\get@thisfootnote
 4202 \patchcmd%
 4203   {\footnote}%
 4204   {\stepcounter{\mpfn}}%
 4205   {%
 4206     \ifboolexpr{bool{\l@dpairing} or bool{\l@dprintingpages} or bool{%
 4207       \l@dprintingcolumns}}{%
 4208       \global\advance\footnote@reading by \one%
 4209       \get@thisfootnote%
 4210       \get@fnmark{\thisc@footnote}%
 4211       \ifcsdef{footnotereading}{\the\footnote@reading}{\typeset}%
 4212         {\setcounter{\mpfn}{\csuse{footnotereading}{\the\footnote@reading=}}%
 4213         {\setcounter{\mpfn}{\footnote@reading}}%
 4214       }{%
 4215         \stepcounter{\mpfn}%
 4216       }%
 4217     }%
 4218     {}%
 4219   }%
 4220 
 4221 \newcommand{\get@thisfootnote}{%
 4222   \ifboolexpr{bool{\l@dpairing} or bool{\l@dprintingpages} or bool{%
 4223     \l@dprintingcolumns}}{%
 4224       \protected@xdef{\thisc@footnote}{\the\footnote@reading}%
 4225     }{%
 4226       \protected@xdef{\thisc@footnote}{\the\c@footnote}%
 4227     }%
 4228   }%
 4229 \newcommand{\l@dbfnote}[1]{%
 4230   \get@thisfootnote%
 4231   \gdef\@tag{\#1\relax}%
 4232   \ifledRcol%
 4233     \xright@appenditem{%
 4234       \ifdefined\Hy@footnote@currentHref%

```

```

4235          \noexpand\def\noexpand\Hy@footnote@currentHref{\
4236              Hy@footnote@currentHref}%
4237              \fi%
4238          \noexpand\vl@dbfnote{{\expandonce\@tag}}{{\thisc@footnote}}%
4239          }%
4240          \to\inserts@listR
4241          \global\advance\insert@countR \zne%
4242      \else%
4243          \xright@appenditem{%
4244              \ifdefined\Hy@footnote@currentHref%
4245                  \noexpand\def\noexpand\Hy@footnote@currentHref{\
4246                      Hy@footnote@currentHref}%
4247                  \fi%
4248                  \noexpand\vl@dbfnote{{\expandonce\@tag}}{{\thisc@footnote}}%
4249                  }%
4250                  \to\inserts@list
4251                  \global\advance\insert@count \zne%
4252          \fi
4253          \ignorespaces%
4254      }%
4255      \newcommand{\get@fnmark}[1]{%
4256          \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{%
4257              l@dprintingcolumns}}%
4258          {%
4259              \stepcounter{footnote@typeset}%
4260              \setcounter{footnote}{\c@footnote@typeset}%
4261              \immediate\write\z@\mainaux{%
4262                  \csgdef{footnotereading#1=typeset}{\the\c@footnote@typeset}%
4263                  }%
4264              \def\@thefnmark{\thefootnote}%
4265          }%
4266          \setcounter{footnote}{#1}%
4267          \def\@thefnmark{\thefootnote}%
4268      }%
4269      \newcommand{\vl@dbfnote}[2]{%
4270          \get@fnmark{#2}%
4271          \c@footnotetext{#1}%
4272      }%
4273      %

```

XIV.3 Footnote formats

Some of the code for the various formats is remarkably similar to that in section ??.
The following macros generally set things up for the ‘standard’ footnote format.

`\prebodyfootmark` Two convenience macros for use by `\...@footnotemark...` macros.

```

\postbodyfootmark
4275 \newcommand*\prebodyfootmark{%
4276   \leavevmode
4277   \ifhmode
4278     \edef\x@sf{\the\spacefactor}%
4279     \m@mmf@check
4280     \nobreak
4281   \fi}
4282 \newcommand*\postbodyfootmark{%
4283   \m@mmf@prepare
4284   \ifhmode\spacefactor\x@sf\fi\relax}
4285 %
4286 %

```

XIV.4 Footnote arrangement

XIV.4.1 User level macro

`\arrangementX` `\arrangementX[⟨s⟩]{⟨arrangement⟩}` command calls, for each series, a specific command which set many counters and commands in order to define specific arrangement.

```

4287 \newcommandx{\arrangementX}[2][1,usedefault]{%
4288   \def\do##1{%
4289     \csname arrangementX@##2\endcsname{##1}%
4290   }%
4291   \ifstrempty{##1}{%
4292     {%
4293       \dolistloop{\@series}%
4294     }%
4295     {%
4296       \docslist{##1}%
4297     }%
4298   }%
4299 }

```

XIV.4.2 Normal footnotes

`\normal@footnotemarkX` `\normal@footnotemarkX{⟨series⟩}` sets up the typesetting of the marker at the point where the footnote is called for.

```

4300 \newcommand*\normal@footnotemarkX[1]{%
4301   \prebodyfootmark
4302   \wrapped@bodyfootmarkX{#1}%
4303   \postbodyfootmark}
4304 %
4305 %

```

`\normalbodyfootmarkX` The `\normalbodyfootmarkX{⟨series⟩}` *really* typesets the in-text marker. The style is the normal superscript.

```

4306 \newcommand*{\normalbodyfootmarkX}[1]{%
4307   \hbox{\textsuperscript{\normalfont\@nameuse{@thefnmark#1}}}}
4308 %

```

\normalvfootnoteX \normalvfootnoteX{\series}{\text} does the \insert for the \series and calls the series' \footfmt... to format the \text.

```

4309 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalvfootnoteX}[2]{%
4310   \beforeinsertion@X{#1}%
4311   \insert{\@nameuse{footins#1}\bgroup
4312     \fontseries{\seriesdefault}%
4313     \fontshape{\shapedefault}%
4314     \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4315     \noindent\csuse{bhooknoteX@#1}%
4316     \csuse{notefontsizeX@#1}%
4317     \footskip
4318     \ifl@dpairing\ifl@dpage\else%
4319       \setnoteswidthliketwocolumnsX@{#1}%
4320     \fi\fi%
4321     \setnotesXpositionliketwocolumns@{#1}%
4322     \spaceskip=\z@skip \xspaceskip=\z@skip
4323     \csuse{\csuse{footnote@dir}}\@nameuse{footfmt#1}{#1}{#2}\egroup}
4324 %
4325 %

```

\mpnormalvfootnoteX The minipage version.

```

4326 \newcommand*{\mpnormalvfootnoteX}[3]{%
4327   \get@thisfootnoteX{#1}%
4328   \get@fnmarkX{#1}{\thisc@footnote}{#3}%
4329   \ifstrempty{#3}{%
4330     \edef\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
4331   }{%
4332     \edef\this@footnoteX@reading{\#\#3}%
4333   }%
4334   \global\setbox\@nameuse{mpfootins#1}\vbox{%
4335     \unvbox\@nameuse{mpfootins#1}%
4336     \noindent\csuse{bhooknoteX@#1}%
4337     \csuse{notefontsizeX@#1}%
4338     \hsize\columnwidth
4339     \parboxrestore
4340     \color@begingroup
4341     \@nameuse{footfmt#1}{#1}{#2}\color@endgroup}%
4342 %
4343 %

```

\normalfootfmtX \normalfootfmtX{\series}{\text} typesets the footnote text, prepended by the marker.

```

4344 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalfootfmtX}[2]{%
4345   \ifluatex%

```

```

4346   \textdir\footnote@luatexttextdir%
4347   \pardir\footnote@luatexpardir%
4348   \par%
4349 \fi%
4350   \protected@edef\@currentlabel{%
4351     \nameuse{@thefnmark#1}%
4352   }%
4353 \ledsetnormalparstuffX{#1}%
4354 \sethangindentX{#1}%
4355 \rule{z@}{\splittopskip}%
4356 {{\csuse{notenumfontX@#1}\wrapped@footfootmarkX{#1}}%
4357   \csuse{wrapcontentX@#1}{#2}%
4358 \strut\par}%
4359 %
4360 %

```

`\normalfootfootmarkX` `\normalfootfootmarkX{\langle series\rangle}` is called by `\normalfootfmtX` to typeset the footnote marker in the footer before the footnote text.

```

4361 \newcommand*{\normalfootfootmarkX}[1]{%
4362   \textsuperscript{\nameuse{@thefnmark#1}}}
4363 %
4364 %

```

`\normalfootstartX` `\normalfootstartX{\langle series\rangle}` is the `\langle series\rangle` footnote starting macro used in the output routine.

```

4365 \newcommand*{\normalfootstartX}[1]{%
4366   \ifdim\equal{Opt}{\prenotesX@}{}
4367   {%
4368     \iftoggle{prenotesX@}{%
4369       \togglefalse{prenotesX@}%
4370       \skip\csname footins#1\endcsname=%
4371       \glueexpr\csuse{prenotesX@}+\csuse{afterruleX@#1}\relax%
4372     }%
4373   {}%
4374   }%
4375   \vskip\skip\csname footins#1\endcsname%
4376   \leftskip=\z@%
4377   \rightskip=\z@%
4378   \ifl@dpairing\else%
4379     \hsize=\oldhsize%
4380   \fi%
4381   \setnoteswidthliketwocolumnsX@{#1}%
4382   \setnotesXpositionliketwocolumns@{#1}%
4383   \print@footnoteXrule{#1}%
4384 }%
4385 %
4386 %

```

\normalfootnoteruleX The rule drawn before the footnote series group.

```
4387 \let\normalfootnoteruleX=\footnoterule
4388 %
4389 %
```

\normalfootgroupX `\normalfootgroupX{<series>}` sends the contents of the `<series>` insert box to the output page without alteration.

```
4390 \newcommand*{\normalfootgroupX}[1]{%
4391   \csuse{bhookgroupX@#1}%
4392   \unvbox\@nameuse{footins#1}%
4393   \hsize=\old@hsize%
4394 }%
4395 %
4396 %
```

\mpnormalfootgroupX The minipage version.

```
4397 \newcommand*{\mpnormalfootgroupX}[1]{%
4398   \vskip\skip\@nameuse{mpfootins#1}
4399   \ifl@dpairing\ifparledgroup%
4400     \leavevmode\marks\parledgroup@\begin}%
4401     \marks\parledgroup@series{#1}%
4402     \marks\parledgroup@type{footnoteX}%
4403   \fi\fi\normalcolor
4404   \ifparledgroup%
4405     \ifl@dpairing%
4406     \else%
4407       \setnoteswidthliketwocolumnsX@{#1}%
4408       \setnotesXpositionliketwocolumns@{#1}%
4409       \print@footnoteXrule{#1}%
4410     \fi%
4411   \else%
4412     \setnoteswidthliketwocolumnsX@{#1}%
4413     \setnotesXpositionliketwocolumns@{#1}%
4414     \print@footnoteXrule{#1}%
4415   \fi%
4416   \csuse{bhookgroupX@#1}%
4417   \unvbox\@nameuse{mpfootins#1}%
4418 %
4419 %
```

\normalbfnoteX #1 = footnote series, #2 = footnote content, #3 manual footnote number

```
4420
4421 \newcommand{\normalbfnoteX}[3]{%
4422   \get@thisfootnoteX{#1}%
4423   \ifledRcol%
4424     \ifluatex
```

```

4425   \footnotelang@lua[R]%
4426   \fi
4427   \@ifundefined{xpg@main@language}{\if polyglossia
4428     {}%
4429     {\footnotelang@poly[R]}%
4430   \xright@appenditem{%
4431     \noexpand\led@set@index@fornote{#1}%
4432     \noexpand\prepare@edindex@fornote{\l@d@nums}%
4433     \unexpanded{\def\this@footnoteX@reading}{\the\csname footnote#1
4434       @reading\endcsname}%
4435     \noexpand\vbfnoteX{#1}{#2}{\thisc@footnote}{#3}%
4436     \noexpand\led@reinit@index@fornote%
4437     \unexpanded{\advance\@edindex@fornote@m@ne}%
4438   }%
4439   \to\inserts@listR
4440   \global\advance\insert@countR \cne%
4441 \else%
4442   \ifluatex
4443     \footnotelang@lua%
4444   \fi
4445   \@ifundefined{xpg@main@language}{\if polyglossia
4446     {}%
4447     {\footnotelang@poly}%
4448   \xright@appenditem{%
4449     \noexpand\led@set@index@fornote{#1}%
4450     \noexpand\prepare@edindex@fornote{\l@d@nums}%
4451     \unexpanded{\def\this@footnoteX@reading}{\the\csname footnote#1
4452       @reading\endcsname}%
4453     \noexpand\vbfnoteX{#1}{#2}{\thisc@footnote}{#3}%
4454     \noexpand\led@reinit@index@fornote%
4455     \unexpanded{\advance\@edindex@fornote@m@ne}%
4456   }%
4457   \to\inserts@list
4458   \global\advance\insert@count \cne%
4459 \fi
4460 \ignorespaces}
4461 %

```

`\get@thisfootnoteX` The macro `\get@thisfootnote` command just saves the footnote number in the `\thisfootnote` macro, depending on the use of pairing environments.

```

4461 \newcommand{\get@thisfootnoteX}[1]{%
4462   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
4463     l@dprintingcolumns}}{%
4464     \protected@xdef\thisc@footnote{\the\csname footnote#1@reading\
4465       endcsname}%
4466   }{%
4467     \protected@xdef\thisc@footnote{\the\csname c@footnote#1\endcsname}%
4468   }%

```

```
4467 }%
4468 %
```

\vbfnoteX This command calls the correct footnote-inserting commands. #1 footnote series, #2 footnote content, #3 footnote counter, #4 manual footnote mark

```
4469 \newcommand{\vbfnoteX}[4]{%
4470   \get@fnmarkX{#1}{#3}{#4}\relax%
4471   \nameuse{regvfootnote#1}{#1}{#2}%
4472 }%
4473 %
```

\get@fnmarkX This command gets the correct footnote number when typesetting parallel texts. #1 footnote series, #2 footnote counter, #3 manual footnote number

```
4474 \newcommand{\get@fnmarkX}[3]{%
4475   \ifstrempy{#3}{%
4476     \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{%
4477       l@dprintingcolumns}}{%
4478       \stepcounter{footnote#1@typeset}%
4479       \setcounter{footnote#1}{\value{footnote#1@typeset}}%
4480       \namedef{@thefnmark#1}{\csuse{thefootnote#1}}%
4481       \immediate\write\mainaux{%
4482         \csgdef{footnote#1reading#2=typeset}{\the\csname c@footnote#1%
4483         @typeset\endcsname}%
4484       }%
4485     }%
4486     \setcounter{footnote#1}{#2}%
4487     \namedef{@thefnmark#1}{\csuse{thefootnote#1}}%
4488   }%
4489 }%
4490 {%
4491   \csdef{@thefnmark#1}{#3}%
4492 }%
4493 }%
4494 %
4495 %
```

\vnumfootnoteX #1 footnote series, #2 footnote content, #3 manual footnote mark

```
4496
4497 \newcommand{\vnumfootnoteX}[3]{%
4498   \ifnumberedpar@
4499     \edtext{}{\normalbfnoteX{#1}{#2}{#3}}%
4500   \else
4501     \def\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
4502     \get@thisfootnoteX{#1}%
4503     \get@fnmarkX{#1}{\expandonce\thisc@footnote}{#3}%
4504 }
```

```

4504     \nameuse{regvfootnote#1}{#1}{#2}%
4505     \fi}
4506 %

```

`arrangementX@normal \arrangementX@normal{\langle series\rangle}` initialises the settings for the `\langle series\rangle` footnotes. This should always be called for each series.

```

4507 \newcommand*{\arrangementX@normal}[1]{%
4508   \csgdef{series@displayX#1}{normal}
4509   \expandafter\let\csname footstart#1\endcsname=\normalfootstartX
4510   \namedef{@footnotemark#1}{\normalfootnotemarkX{#1}}
4511   \namedef{bodyfootmark#1}{\normalbodyfootmarkX{#1}}
4512   \expandafter\let\csname regvfootnote#1\endcsname=\normalvfootnoteX
4513   \expandafter\let\csname vfootnote#1\endcsname=\vnumfootnoteX
4514   \expandafter\let\csname footfmt#1\endcsname=\normalfootfmtX
4515   \namedef{footfootmark#1}{\normalfootfootmarkX{#1}}
4516   \expandafter\let\csname footgroup#1\endcsname=\normalfootgroupX
4517   \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
4518   \count\csname footins#1\endcsname=1000
4519   \csxdef{default@footins#1}{1000}\%Use to have note only for one side
4520   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
4521   \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}\%
4522   \advance\skip\csname footins#1\endcsname by\csuse{afterruleX@#1}\%
4523 %

```

Additions for minipages.

```

4524 \ifnoledgroup@\else%
4525   \expandafter\let\csname mpvfootnote#1\endcsname=\mpnnormalvfootnoteX
4526   \expandafter\let\csname mpfootgroup#1\endcsname=\mpnnormalfootgroupX
4527   \count\csname mpfootins#1\endcsname=1000
4528   \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
4529   \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}\%
4530   \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}\%
4531 \fi
4532 }
4533 %
4534 %

```

XIV.4.3 Two columns footnotes

The following macros set footnotes in two columns. It is assumed that the length of each footnote is less than the column width.

```

\arrangementX@twocol \newcommand*{\arrangementX@twocol}[1]{%
4535   \csgdef{series@displayX#1}{twocol}
4536   \expandafter\let\csname regvfootnote#1\endcsname=\twocolvfootnoteX
4537   \expandafter\let\csname footfmt#1\endcsname=\twocolfootfmtX
4538   \expandafter\let\csname footgroup#1\endcsname=\twocolfootgroupX
4539   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}\%
4540 %

```

```

4541 \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
4542 \advance\skip\csname footins#1\endcsname by \csuse{afterruleX@#1}\relax%
4543 \twocolfootsetupX{#1}
4544 \ifnoledgroup@{\else%
4545   \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
4546   \expandafter\let\csname mpfootgroup#1\endcsname=\mptwocolfootgroupX
4547   \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
4548   \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}
4549   \mptwocolfootsetupX{#1}
4550 } \fi%
4551 }
4552 %
4553 %

\twocolfootsetupX \twocolfootsetupX{\langle series\rangle}
\mptwocolfootsetupX
4554 \newcommand*{\twocolfootsetupX}[1]{%
4555   \count\csname footins#1\endcsname 500
4556   \csxdef{default@footins#1}{500}%Use this to confine the notes to one
4557   side only
4558   \multiply\dimen\csname footins#1\endcsname by \tw@}
4559 \newcommand*{\mptwocolfootsetupX}[1]{%
4560   \count\csname mpfootins#1\endcsname 500
4561   \multiply\dimen\csname mpfootins#1\endcsname by \tw@}
4562 %

\twocolvfootnoteX \twocolvfootnoteX{\langle series\rangle}
4563 \notbool{parapparatus@}{\newcommand*{\newcommand}{\newcommand}{\twocolvfootnoteX}[2]{%
4564   \beforeinsertion@X{#1}%
4565   \insert\csname footins#1\endcsname\bgroup%
4566   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4567   \noindent\csuse{bhooknoteX@#1}%
4568   \csuse{notefontsizeX@#1}%
4569   \footfolds skips%
4570   \spaceskip=\z@skip \xspaceskip=\z@skip%
4571   \nameuse{footfmt#1}{#1}{#2}\egroup}
4572 %
4573 %

\twocolfootfmtX \twocolfootfmtX{\langle series\rangle}
4574 \notbool{parapparatus@}{\newcommand*{\newcommand}{\newcommand}{\twocolfootfmtX}[2]{%
4575   \protected@edef\@currentlabel{%
4576     \nameuse{@thefnmark}{#1}%
4577   }%
4578   \normal@pars%
4579   \sethangindentX{#1}%
4580   \hsize \csuse{hsizetwocolX@#1}%

```

```

4581 \notoggle{parindentX@#1}{\parindent=\z@}{}
4582   \tolerance=5000\relax%
4583   \par%
4584   \tempdima=\parindent%
4585   \csuse{colalignX@#1}%
4586   \parindent=\tempdima%
4587   {\hspace{\parindent}%
4588     \csuse{notenumfontX@#1}\wrapped@footfootmarkX{#1}\strut%
4589     \csuse{wrapcontentX@#1}{#2}%
4590     \strut\par}%
4591   \allowbreak%
4592 }%
4593 %
4594 %

```

```

\twocolfootgroupX \twocolfootgroupX{\series}
\mptwocolfootgroupX
4595 \newcommand*{\twocolfootgroupX}[1]{{\csuse{bhookgroupX@#1}\csuse{%
  note fontsize X@#1}%
4596   \splittopskip=\ht\strutbox%
4597   \expandafter%
4598   \rigidbalanceX\csname footins#1\endcsname \tw@ \splittopskip}%
4599 %
4600 \newcommand*{\mptwocolfootgroupX}[1]{%
4601   \vskip\skip\@nameuse{mpfootins#1}%
4602   \ifl@dpairing\ifparledgroup%
4603     \leavevmode\marks\parledgroup@{begin}%
4604     \marks\parledgroup@series{#1}%
4605     \marks\parledgroup@type{footnoteX}%
4606   \fi\fi\normalcolor%
4607   \ifparledgroup%
4608     \ifl@dpairing%
4609     \else%
4610       \setnoteswidth liketwocolumnsX@{#1}%
4611       \setnotesXposition liketwocolumns@{#1}%
4612       \print@footnoteXrule{#1}%
4613     \fi%
4614   \else%
4615     \setnoteswidth liketwocolumnsX@{#1}%
4616     \setnotesXposition liketwocolumns@{#1}%
4617     \print@footnoteXrule{#1}%
4618   \fi%
4619   \csuse{bhookgroupX@#1}%
4620   \splittopskip=\ht\strutbox%
4621   \expandafter%
4622   \rigidbalanceX\csname mpfootins#1\endcsname \tw@ \splittopskip}%
4623 %
4624 %

```

XIV.4.4 Three columns footnotes

The following macros set footnotes in three columns. It is assumed that the length of each footnote is less than the column width.

```

\arrangementX@threecol425 \newcommand*{\arrangementX@threecol}[1]{%
  426   \csgdef{series@displayX#1}{threecol}
  427   \expandafter\let\csname regvfootnote#1\endcsname=\threecolvfootnoteX
  428   \expandafter\let\csname footfmt#1\endcsname=\threecolfootfmtX
  429   \expandafter\let\csname footgroup#1\endcsname=\threecolfootgroupX
  430   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}%
  431   \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
  432   \advance\skip\csname footins#1\endcsname by \csuse{afterruleX@#1}\relax%
  433   \threecolfootsetupX{#1}
  434   \ifnolegroup@\else%
  435     \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
  436     \expandafter\let\csname mpfootgroup#1\endcsname=\mpthreecolfootgroupX
  437     \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
  438     \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}%
  439     \mpthreecolfootsetupX{#1}
  440   \fi%
  441 }
  442 %
  443 %

\threecolfootsetupX \threecolfootsetupX{\langle series\rangle}
\mpthreecolfootsetupX444 \newcommand*{\threecolfootsetupX}[1]{%
  445   \count\csname footins#1\endcsname 333
  446   \csxdef{default@footins#1}{333}%Use this to confine the notes to one
  447   side only
  448   \multiply\dimen\csname footins#1\endcsname by \thr@@
  449   \newcommand*{\mpthreecolfootsetupX}[1]{%
  450     \count\csname mpfootins#1\endcsname 333
  451     \multiply\dimen\csname mpfootins#1\endcsname by \thr@@
  452   %
}

\threecolvfootnoteX \threecolvfootnoteX{\langle series\rangle}{\langle text\rangle}
  453 \notbool{parapparatus@}{\newcommand*{\newcommand}{\newcommand}{\threecolvfootnoteX}[2]{%
  454   %
  455   \beforeinsertionX{#1}%
  456   \insert\csname footins#1\endcsname\bgroup%
  457   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
  458   \noindent\csuse{bhooknoteX@#1}%
  459   \csuse{notefontsizeX@#1}%
  460   \footsplitskips%
  461   \egroup\nameuse{footfmt#1}{#1}{#2}\egroup}
  462 %
  463 
```

```

4662 %
4663 \threecolfootfmtX \threecolfootfmtX{\langle series\rangle}
4664 \notbool{parapparatus@}{\newcommand*{\newcommand}{\threecolfootfmtX}[2]{%
4665   \protected@edef{\currentlabel}{%
4666     \nameuse{@thefnmark#1}%
4667   }%
4668   \sethangindentX{\#1}%
4669   \normal@pars%
4670   \hsize \csuse{hsizethreecolX@#1}%
4671   \nottoggle{parindentX@#1}{\parindent=\z@}{%
4672     \tolerance=5000\relax%
4673     \tempdima=\parindent%
4674     \csuse{colalignX@#1}%
4675     \parindent=\tempdima%
4676     {\hskip\parindent}%
4677     \csuse{notenumfontX@#1}\wrapped@footfootmarkX{\#1}\strut%
4678     \csuse{wrapcontentX@#1}{\#2}%
4679     \strut\par}\allowbreak}
4680 %

\threecolfootgroupX \threecolfootgroupX{\langle series\rangle}
\mpthreecolfootgroupX
4681 \newcommand*{\threecolfootgroupX}[1]{\csuse{bhookgroupX@#1}\csuse{%
4682   note fontsize X@#1}%
4683   \splittopskip=\ht\strutbox%
4684   \expandafter\rigidbalanceX\csname footins#1\endcsname \thr@@ \splittopskip}}
4685
4686 \newcommand*{\mpthreecolfootgroupX}[1]{%
4687   \vskip\skip\nameuse{mpfootins#1}%
4688   \ifl@dpairing\ifparledgroup%
4689     \leavevmode\marks\parledgroup@{begin}%
4690     \marks\parledgroup@series{\#1}%
4691     \marks\parledgroup@type{footnoteX}%
4692     \fi\fi\normalcolor%
4693   \ifparledgroup%
4694     \ifl@dpairing%
4695     \else%
4696       \setnoteswidthliketwocolumnsX{\#1}%
4697       \setnotesXpositionliketwocolumns{\#1}%
4698       \print@footnoteXrule{\#1}%
4699     \fi%
4700   \else%
4701     \setnoteswidthliketwocolumnsX{\#1}%
4702     \setnotesXpositionliketwocolumns{\#1}%
4703     \print@footnoteXrule{\#1}%
4704   \fi%

```

```

4705 \csuse{bhookgroupX@#1}%
4706 \splittopskip=\ht\strutbox
4707 \expandafter
4708 \rigidbalanceX\csname mpfootins#1\endcsname \thr@@ \splittopskip}}%
4709 %
4710 %

```

XIV.4.5 Paragraphed footnotes

The following macros set footnotes as one paragraph.

\arrangementX@paragraph \footparagraphX{\langle series\rangle}

```

4711 \newcommand*{\arrangementX@paragraph}[1]{%
4712   \csgdef{series@displayX#1}{paragraph}%
4713   \expandafter\let\csname footstart#1\endcsname=\parafootstartX
4714   \expandafter\let\csname regvfootnote#1\endcsname=\para@vfootnoteX
4715   \expandafter\let\csname footfmt#1\endcsname=\parafootfmtX
4716   \expandafter\let\csname footgroup#1\endcsname=\para@footgroupX
4717   \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
4718   \count\csname footins#1\endcsname=1000
4719   \csxdef{default@footins#1}{1000}%Use this to confine the notes to one
4720   side only
4721   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
4722   \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
4723   \advance\skip\csname footins#1\endcsname by\csuse{afterruleX@#1}%
4724   \para@footsetupX{#1}
4725   \ifnolegroup@\else
4726     \expandafter\let\csname mpvfootnote#1\endcsname=\mppara@vfootnoteX
4727     \expandafter\let\csname mpfootgroup#1\endcsname=\mppara@footgroupX
4728     \count\csname mpfootins#1\endcsname=1000
4729     \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
4730     \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
4731     \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}%
4732   \fi
4733 }
4734 %

```

\para@footsetupX \para@footsetupX{\langle series\rangle}

```

4735 \newcommand*{\para@footsetupX}[1]{\{\csuse{bhookgroupX@#1}\}\csuse{%
4736   note fontsizeX@#1}%
4737   \setnoteswidth like two columns X@{#1}%
4738   \ifcsempty{widthX@#1}%
4739     {}%
4740     {\columnwidth=\expandafter\dimexpr\csuse{widthX@#1}\relax}%
4741   \dimen0=\baselineskip
4742   \multiply\dimen0 by 1024

```

```

4742   \divide\dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\relax%
4743   %
4744   \expandafter
4745   \xdef\csname footfudgefactor#1\endcsname{%
4746     \expandafter\strip@pt\dimen0 }}}
4747 %

```

```

\parafootstartX \parafootstartX{\langle series\rangle}

4748 \newcommand*{\parafootstartX}[1]{%
4749   \ifdim\dimen0=\z@{%
4750     {%
4751       \iftoggle{\prenotesX}{%
4752         \togglegfalse{\prenotesX}%
4753         \skip\csname footins#1\endcsname=%
4754           \glueexpr\csuse{\prenotesX}+\csuse{afterruleX#1}\relax%
4755         }%
4756       {}%
4757     }%
4758     \leftskip=\z@%
4759     \rightskip=\z@%
4760     \notoggle{\parindentX}{\parindent=\z@}{}%
4761     \vskip\skip\@nameuse{footins#1}%
4762     \setnoteswidthliketwocolumnsX{\#1}%
4763     \setnotesXpositionliketwocolumns{\#1}%
4764     \print@footnoteXrule{\#1}%
4765   }%
4766 %
4767 %

```

```

\para@vfootnoteX \para@vfootnoteX{\langle series\rangle}{\langle text\rangle}
\mp para@vfootnoteX
4768 \newcommand*{\para@vfootnoteX}[2]{%
4769   \csuse{beforeinsertingX#1}%
4770   \insert\csname footins#1\endcsname{%
4771     \bgroup
4772       \csuse{notefontsizeX#1}%
4773       \footsplitkips
4774       \setbox0=\vbox{\hsize=\maxdimen%
4775         \let\bidi@RTL@everypar\empty%
4776         \insert\textbeforenotesX{\#1}%
4777         \noindent\csuse{bhooknoteX#1}%
4778         \nameuse{footfmt{\#1}{\#1}{\#2}}%
4779       \setbox0=\hbox{\unvvhX{\#0}{\#1}}%
4780       \dp0=\z@%
4781       \ht0=\csname footfudgefactor#1\endcsname\wd0
4782       \box0
4783       \penalty0
4784     \egroup}%

```

```

4785 \newcommand*{\mppara@vfootnoteX}[3]{%
4786   \get@thisfootnoteX{#1}%
4787   \get@fnmarkX{#1}{\thisc@footnote}{#3}%
4788   \edef\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
4789   \global\setbox\@nameuse{mpfootins#1}\vbox{%
4790     \unvbox\@nameuse{mpfootins#1}%
4791     \csuse{notefontsizeX@#1}%
4792     \footsplitskips%
4793     \setbox0=\vbox{\hsize=\maxdimen}%
4794     \let\bidi@RTL@everypar\empty%
4795     \noindent\color@begingroup%
4796     \csuse{bhooknoteX@#1}%
4797     \color@endgroup}%
4798     \setbox0=\hbox{\unvxhX{0}{#1}}%
4799     \dp0=\z@%
4800     \ht0=\csname footfudgefactor#1\endcsname\wd0%
4801     \box0%
4802     \penalty0}%
4803 %
4804 %

```

```

\unvxhX \newcommand*{\unvxhX}[2]{% 2th is optional for retro-compatibility
4806   \setbox0=\vbox{\unvbox#1}%
4807   \global\setbox1=\lastbox}%
4808 \unhbox1%
4809 \unskip % remove \rightskip,
4810 \unskip % remove \parfillskip,
4811 \unpenalty % remove \penalty of 10000,
4812 \hskip\csuse{afternoteX@#2}%
4813 \relax}%
4814 but add the glue to go between the notes
4815 %

```

\parafootfmtX \parafootfmtX{\langle series\rangle}

```

4816 \newcommand*{\parafootfmtX}[2]{%
4817   \protected\edef\@currentlabel{%
4818     \@nameuse{@thefnmark#1}%
4819   }%
4820   \insertparafootsepX{#1}%
4821   \ledsetnormalparstuff@common%
4822   {\csuse{notenumfontX@#1}%
4823   \csuse{notenumfontX@#1}%
4824   \wrapped@footfootmarkX{#1}%
4825   \strut%
4826   \csuse{wrapcontentX@#1}{#2}%
4827   \penalty-10}%
4828 %
4829 %

```

```

\para@footgroupX \para@footgroupX{\series}
\mppara@footgroupX
4830 \newcommand*\para@footgroupX[1]{%
4831   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4832   \unvbox\csname footins#1\endcsname
4833   \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
4834   \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
4835   \makehboxofhboxes
4836   \setbox0=\hbox{\unhbox0 \removehboxes}%
4837   \csuse{bhookgroupX@#1}%
4838   \csuse{notefontsizeX@#1}%
4839   \unhbox0\par}
4840
4841 \newcommand*\mppara@footgroupX[1]{%
4842   \setnoteswidthliketwocolumnsX@{#1}%
4843   \vskip\skip\@nameuse{mpfootins#1}
4844   \ifl@dpairing\ifparledgroup
4845     \leavevmode%
4846     \leavevmode\marks\parledgroup@{begin}%
4847     \marks\parledgroup@series{#1}%
4848     \marks\parledgroup@type{footnoteX}%
4849   \fi\fi\normalcolor
4850   \ifparledgroup%
4851     \ifl@dpairing%
4852     \else%
4853       \setnoteswidthliketwocolumnsX@{#1}%
4854       \setnotesXpositionliketwocolumns@{#1}%
4855       \print@footnoteXrule{#1}%
4856     \fi%
4857   \else%
4858     \setnoteswidthliketwocolumnsX@{#1}%
4859     \setnotesXpositionliketwocolumns@{#1}%
4860     \print@footnoteXrule{#1}%
4861   \fi%
4862   \unvbox\csname mpfootins#1\endcsname
4863   \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
4864   \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
4865   \makehboxofhboxes
4866   \setbox0=\hbox{\unhbox0 \removehboxes}%
4867   \csuse{bhookgroupX@#1}%
4868   \csuse{notefontsizeX@#1}%
4869   \notoggle{parindentX@#1}{\parindent=\z@}{}%
4870   \unhbox0\par}
4871 %
4872 %

```

Insertion of the footnotes separator The command `\insertparafootsepX{\series}` must be called at the beginning of `\parafootftmX`.

```
\insertparafootsepX73 \newcommand{\insertparafootsepX}[1]{%
 4874   \ifldRcol@%
 4875     \ifnumequal{\csuse{prevpage#1@numR}}{\page@numR}{%
 4876       {\csuse{Xparafootsep@#1}}%
 4877       {}%
 4878     \global\csname prevpage#1@numR\endcsname=\page@numR%
 4879   \else%
 4880     \ifnumequal{\csuse{prevpage#1@num}}{\page@num}{%
 4881       {\csuse{Xparafootsep@#1}}%
 4882       {}%
 4883     \global\csname prevpage#1@num\endcsname=\page@num%
 4884   \fi%
 4885 }
 4886 %
```

XIV.5 Wrapping footnote marks in hyperlink

\wrapped@footfootmarkX \wrapped@footfootmarkX prints the footnote mark of the footpage, wrapped in `hyperref` package's commands, if needed.

```
4887 \newcommand{\wrapped@footfootmarkX}[1]{%
4888   \ifdef\hypertarget{%
4889     \hyperlink{%
4890       {@bodyfootmark#1@\this@footnoteX@reading}%
4891       {\@nameuse{footfootmark#1}}%
4892     \Hy@raisedlink{%
4893       \hypertarget{%
4894         {@footnotemark#1@\this@footnoteX@reading}%
4895       {}%
4896     }%
4897   \else%
4898     \@nameuse{footfootmark#1}%
4899   \fi%
4900 }
4901 %
```

\wrapped@bodyfootmarkX \wrapped@bodyfootmarkX prints the footnote mark of the text body, wrapped in `hyperref` package's commands, if needed.

```
4902 \newcommand{\wrapped@bodyfootmarkX}[1]{%
4903   \ifdef\hypertarget{%
4904     \hyperlink{%
4905       {@footnotemark#1@\expandafter\the\csname footnote#1@reading\endcsname}%
4906       {\@nameuse{bodyfootmark#1}}%
4907     \Hy@raisedlink{%
4908       \hypertarget{%
4909         {@bodyfootmark#1@\expandafter\the\csname footnote#1@reading\endcsname}%
4910       {}%
4911     }%
4912   \else%
4913     \@nameuse{bodyfootmark#1}%
4914   \fi%
4915 }
```

```

4910      {}%
4911      }%
4912      \else%
4913      \nameuse{bodyfootmark#1}%
4914      \fi%
4915  }%
4916 %

```

XV Code common to both critical and familiar footnote in normal arrangement

\par should always be redefined to \endgraf within the format macro (this is what \normal@pars does), to override tricky material in the main text to get the lines numbered automatically (as set up by \autopar, for example).

In the case of footnote arranged in a “normal” way, we also must set some setting for paragraph indent and text direction when using LuaTEX.

That why we have defined \ledsetnormalparstuff@common in order to make this setting for both familiar and critical notes. This command is called by command to make specific setting to critical or familiar footnote.

```

dsetnormalparstuff@common17 \newcommand*{\ledsetnormalparstuff@common}{%
\Xledsetnormalparstuff18 \ifluatex%
\Xledsetnormalparstuff19 \ifdefstring{\footnote@luatextextdir}{TLT}{%
4920   {\textdir\footnote@luatextextdir}%
4921   \pardir\footnote@luatexpardir%
4922   \fi%
4923   \csuse{\csuse{footnote@dir}}%
4924   \normal@pars%
4925   \parfillskip \z@\oplus 1fil}%
4926 %
4927 \newcommand*{\Xledsetnormalparstuff}[1]{%
4928   \ledsetnormalparstuff@common%
4929   \notoggle{Xparindent@#1}{\parindent=\z@\hspace{\parindent}}%
4930 }%
4931 %
4932 \newcommand*{\ledsetnormalparstuffX}[1]{%
4933   \ledsetnormalparstuff@common%
4934   \notoggle{parindentX@#1}{\parindent=\z@\hspace{\parindent}}%
4935 }%
4936 %

```

XVI Footnotes’ width for two columns

We define here some commands which make sense only with reledpar, but must be called when defining notes parameters. These commands change the width of block notes to allow them to have the same size than two parallel columns.

`\old@hsize` These two commands are called at the beginning of critical or familiar notes groups.
`\setXnoteswidthliketwocolumns@` They set, if the option is enabled, the `\hsize`. They are also called at the on the setup
`\setnoteswidthliketwocolumnsX@` for paragraphed notes.

```

4937 \newdimen\old@hsize%
4938 \AtBeginDocument{\old@hsize=\hsize}%
4939
4940
4941 \newcommand{\setXnoteswidthliketwocolumns@}[1]{%
4942   \global\let\hsize@fornote=\hsize%
4943   \global\old@hsize=\hsize%
4944   \let\old@columnwidth=\columnwidth%
4945   \iftoggle{Xnoteswidthliketwocolumns@#1}{%
4946     {%
4947       \setwidthliketwocolumns%
4948       \global\let\hsize@fornote=\hsize%
4949     }%
4950   }%
4951   \let\hsize=\hsize@fornote%
4952   \let\columnwidth=\old@columnwidth%
4953 }%
4954
4955 \newcommand{\setnoteswidthliketwocolumnsX@}[1]{%
4956   \global\let\hsize@fornote=\hsize%
4957   \global\old@hsize=\hsize%
4958   \let\old@columnwidth=\columnwidth%
4959   \iftoggle{noteswidthliketwocolumnsX@#1}{%
4960     {%
4961       \setwidthliketwocolumns%
4962       \global\let\hsize@fornote=\hsize%
4963     }%
4964   }%
4965   \let\hsize=\hsize@fornote%
4966   \let\columnwidth=\old@columnwidth%
4967 }%
4968
4969 %

```

`\setXnotespositionliketwocolumns@` These two commands set the position of the critical / familiar footnotes, depending on
`\setnotesXpositionliketwocolumns@` the hooks `Xnoteswidthliketwocolumns` and `noteswidthliketwocolumnsX`. They
call commands which are defined only in `reledpar`, because this feature has no sens
without `reledpar`.

```

4970 \newcommand{\setXnotespositionliketwocolumns@}[1]{%
4971   \iftoggle{Xnoteswidthliketwocolumns@#1}{%
4972     \csuse{setnotespositionliketwocolumns@\columns@position}%
4973   }%
4974 }%
4975
4976 \newcommand{\setnotesXpositionliketwocolumns@}[1]{%

```

```

4977     \iftoggle{noteswidthliketwocolumnsX@#1}{%
4978         \csuse{setnotespositionliketwocolumns@\columns@position}%
4979     }{}%
4980 }%
4981 %
4982 %

```

XVII Footnotes' order

`\fnpos` The `\fnpos` and `\mpfnpos` simply place their arguments in `\@fnpos` and `\@mpfnpos`, which will be used later in the output routine.

```

\@fnpos 4983 \def\@fnpos{familiar-critical}
\@mpfnpos 4984 \def\@mpfnpos{critical-familiar}
4985 \newcommand{\fnpos}[1]{\xdef\@fnpos{#1}}
4986 \newcommand{\mpfnpos}[1]{\xdef\@mpfnpos{#1}}
4987 %

```

XVIII Footnotes' rule

Because the footnotes' rules can be shifted to the right when footnotes are set like two columns, we do not print them directly, but we put them in a `\vbox`.

```

\print@Xfootnoterule88 \newcommand{\print@Xfootnoterule}[1]{%
\print@footnoteXrule89   \vskip-\csuse{Xafterrule@#1}%Because count in \dimen\csuse{#1footins}
4990   \nointerlineskip%
4991   \moveleft-\leftskip\vbox{\csuse{#1footnoterule}}%
4992   \nointerlineskip%
4993   \vskip\csuse{Xafterrule@#1}%
4994 }%
4995 %
4996 \newcommand{\print@footnoteXrule}[1]{%
4997   \vskip-\csuse{afterruleX@#1}%Because count in \dimen\csuse{footins#1}
4998   \nointerlineskip%
4999   \moveleft-\leftskip\vbox{\csuse{footnoterule#1}}%
5000   \nointerlineskip%
5001   \vskip\csuse{afterruleX@#1}%
5002 }%
5003 %
5004 %

```

XIX Specific skip for first series of footnotes

XIX.1 Overview

\Xbeforenotes inserts a specific skip for the first series of notes in a page. As we can't know in advance which series will be the first, we call \prepare@Xprenotes before inserting any critical notes in order to prevent page number overlapping.

1. If it is the first note of the current page, it changes the footnote skip for the series to the value specified to \Xbeforenotes. It also keeps the series of the note as the first one of the current page.
2. If it is not the first note of the current page:
 - If the current series is printed after the series kept as the first of the current page, then nothing happens.
 - If the current series is printed before the series kept as the first of the current page, then it changes the footnote skip of the current series to the value normally used by the series which was marked as the first of the page. It also keeps the current series as the new first one of the current page.

For example, suppose the series order is A,B. We call first a \Bfootnote and a \Afootnote. The only skips used are, finally, the skip specific to the first series of the page, and the skip for the B series. If we have not called \Afootnote, the only skip used is the skip specific to the first series of the page.

That is perfect.

The series skip and the first series of the current page are reset before the footnotes are printed. Then, the footstart macros manage the problem of the first series of the page.

After the rule, the space which is defined by \Xafterrule does not depend on whether the series is the first one of the page or not. So we use its normal value for each series.

And now, implementation !

XIX.2 User level command

\Xprenotes@ If user redefines \Xprenotes@, via \Xprenotes to a value greater than 0 pt, this skip will be added before first series notes instead of the notes skip.

```

5005 \newtoggle{Xprenotes@}%
5006 \togglettrue{Xprenotes@}%
5007 \newcommand{\Xprenotes@}{0pt}%
5008 \newcommand*{\Xprenotes}[1]{\renewcommand{\Xprenotes@}{#1}}%
5009 \newcommand{\preXnotes}[1]{\led@warning@preXnotes@deprecated\Xprenotes{#1}}%
%For compatibility
5010 %

```

The same, but for familiar footnotes.

```

\Xprenotes11 \newtoggle{prenotesX@}
\Xprenotes@12 \toggletrue{prenotesX@}
5013 \newcommand{\prenotesX@}{Opt}
5014 \newcommand*{\prenotesX}[1]{\renewcommand{\prenotesX@}{#1}}
5015 %

```

XIX.3 Internal commands

```

firstXseries@16 \gdef\firstXseries@{}
prepare@Xprenotes17 \newcommand{\prepare@Xprenotes}[1]{%
5018 \ifdimequal{Opt}{\Xprenotes@}%
5019 {}%
5020 {}%
5021 \IfStrEq{\firstXseries@}{}{%
5022 \global\skip\csuse{#1footins}=\Xprenotes@%
5023 \global\advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@}
5024 #1}%
5025 \gdef\firstXseries@{#1}%
5026 }%
5027 {}%
5028 \ifseriesbefore{#1}{\firstXseries@}%
5029 {}%
5030 \global\skip\csuse{#1footins}=\csuse{Xbeforenotes@\firstXseries@}%
5031 \global\advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@}
5032 #1}%
5033 \gdef\firstXseries@{#1}%
5034 }%
5035 {}%
5036 }%
5037 %

```

The same thing is required for familiar notes and \prenotesX.

```

firstseriesX@38 \gdef\firstseriesX@{}
prepare@prenotesX39 \newcommand{\prepare@prenotesX}[1]{%
5040 \ifdimequal{Opt}{\prenotesX@}%
5041 {}%
5042 {}%
5043 \IfStrEq{\firstseriesX@}{}{%
5044 \global\skip\csuse{footins#1}=\prenotesX@%
5045 \global\advance\skip\csname footins#1\endcsname by\csuse{afterruleX@}
5046 #1}%
5047 \gdef\firstseriesX@{#1}%
5048 }%
5049 \ifseriesbefore{#1}{\firstseriesX@}%

```

```

5050   {%
5051   \global\skip\csuse{footins#1}=\csuse{beforenotesX@\firstseriesX@}%
5052   \global\advance\skip\csname footins#1\endcsname by\csuse{afterruleX@%
#1}%
5053   \gdef\firstXseries@{\#1}%
5054   }%
5055   {}%
5056   }%
5057   }%
5058 }
5059 %

```

XX Endnotes

First, check the noend option.

```

5060 \ifbool{noend@}{\relax}{%Used instead of \ifnoend@ to prevent expansion problem
5061 %

```

XX.1 Internal commands

`\l@dend@open` `\l@dend@close` `\l@dend@open` and `\l@dend@close` are the macros that are used to open and close the endnote file. Note that all our writing to this file is `\immediate`: all page and line numbers for the endnotes are generated by the same mechanism we use for the footnotes, so that there is no need to defer any writing to catch information from the output routine. The argument of these two command is the series letter.

```

5062 \newcommand{\l@dend@open}[1]{%
5063   \global\booltrue{l@dend@#1}%
5064   \expandafter\immediate%
5065   \expandafter\openout%
5066   \csname l@d@#1end\endcsname%
5067   =\l@auxdir\jobname.#1end\relax%
5068 }%
5069 \newcommand{\l@dend@close}[1]{%
5070   \global\boolfalse{l@dend@#1}%
5071   \expandafter\immediate%
5072   \expandafter\closeout\csname l@d@#1end\endcsname%
5073 }%
5074 %
5075 %

```

`\l@dend@stuff` `\l@dend@stuff` is used by `\beginnumbering` to do everything that is necessary for the endnotes at the start of each section: it opens the `\l@d@nd` file, if necessary, and writes the section number to the endnote file.

```

5076 \newcommand{\l@dend@stuff}{%
5077   \def\do##1{%

```

```

5078   \ifbool{l@dend@##1}{%
5079     {\l@dend@open{##1}}%
5080     \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname{\
5081       string\l@d@section{\the\section@num}\@percentchar}%
5082     }%
5083   \dolistloop{\@series}%
5084 }%
5085 %

```

\endprint The `\endprint` here is nearly identical in its functioning to `\normalfootfmt`.

\l@d@section The endnote file also contains `\l@d@section` commands, which supply the section numbers from the main text; standard reledmac does nothing with this information, but it is there if you want to write custom macros to do something with it. Arguments are:

- #1 Line numbers and font selection.
- #2 Lemma.
- #3 Note content.
- #4 Series.
- #5 Optional argument of `\Xendnote`.
- #6 Side (L or R).
- #7 Label for cross-referencing.

```

5086 \global\notbool{parapparatus@}{\long}\def\endprint#1#2#3#4#5#6#7{%
5087   \iftoggle{Xendfirstnote@#4}{%
5088     \global\togglefalse{Xendfirstnote@#4}%
5089     \csuse{Xendtxtbeforenotes@#4}%
5090   }%
5091   \csuse{Xendbhooknote@#4}%
5092   \csuse{Xendnotefontsize@#4}%
5093   \hangindent=\csuse{Xendhangindent@#4}%
5094   \ifXendinsertsep@%
5095     \hskip\csuse{Xendafternote@#4}\relax%
5096     \csuse{Xendsep@#4}%
5097   \else%
5098     \iftoggle{Xendparagraph@#4}{%
5099       {\global\Xendinsertsep@true}%
5100     }%
5101   \fi%
5102   \xdef@\currentseries{#4}%
5103   \def\do##1{%
5104     \setkeys[mac]{truefootnoteoption}{##1}%
5105   }%

```

```

5106 \notblank{#5}{\docslist{#5}}{%
5107 \IfStrEq{#6}{R}{\ledRcol@true}{%
5108 \def\@this@crossref@start{#7:start}%
5109 \def\@this@crossref@end{#7:end}%
5110 \printlineendnote{#1}{#4}%
5111 \IfStrEq{#6}{R}{\ledRcol@false}{%
5112 \nottoggle{Xendlemmadisablefontselection@#4}{%
5113 {\select@lemmafont#1}%
5114 }%
5115 \bgroup%
5116 \csuse{Xendlemmafont@#4}%
5117 \csuse{Xendwraplemma@#4}{#2}%
5118 \egroup%
5119 \ifboolexpr{%
5120 togl {nosep@}%
5121 or test{\ifcsempy{Xendlemmaseparator@#4}}%
5122 }%
5123 {\hskip\csuse{Xendinplaceoflemmaseparator@#4}\relax}%
5124 {\nobreak%
5125 \hskip\csuse{Xendbeforelemmaseparator@#4}%
5126 \csuse{Xendlemmaseparator@#4}%
5127 \hskip\csuse{Xendafterlemmaseparator@#4}%
5128 \relax%
5129 }%
5130 \csuse{Xendwrapcontent@#4}{#3}%
5131 \nottoggle{Xendparagraph@#4}{\par}{%
5132 \def\do##1{%
5133 \setkeys[mac]{falsefootnoteoption}{##1}%
5134 }%
5135 \notblank{#5}{\docslist{#5}}{%
5136 }%
5137 \let\l@d@section=\gobble
5138 %
5139 %
5140 %

```

\printlineendnote This macro controls, in endnote, whether the line number is printed or not, according to the series options. Its first argument is the information about lines; its second is the series of the footnote.

```

5141 \newcommand{\printlineendnote}[2]{%
5142 \l@dp@rsefotpspec#1}%
5143 \iftoggle{Xendnumberonlyfirstintwolines@#2}{%
5144 \xdef\lineinfo@{\l@dparsedstartpage - \l@dparsedstartline - \
5145 \l@dparsedstartsub - \l@dparsedendpage - \l@dparsedendline - \
5146 \l@dparsedendsub}%
5147 }%
5148 \xdef\lineinfo@{\l@dparsedstartpage - \l@dparsedstartline - \
5149 \l@dparsedstartsub}%

```

```

5148      }%
5149      \ifboolexpr{%
5150          togl {nonum@}%
5151          or togl {Xendnonumber@#2}%
5152      }%
5153      {\hspace{\csuse{Xendinplaceofnumber@#2}}}%
5154      {%
5155          \iftoggle{Xendnumberonlyfirstinline@#2}{%
5156              \ifcsdef{prevendline@#2}{%
5157                  \ifcsequal{prevendline@#2}{lineinfo@}{%
5158                      {%
5159                          \csuse{Xendbhookinplaceofnumber@#2}%
5160                          \ifcsempy{Xendsymlinenum@#2}{%
5161                              {\hspace{\csuse{Xendinplaceofnumber@#2}}}{%
5162                                  {\printsymlineendnotearea{#2}}{%
5163                                      \csuse{Xendahookinplaceofnumber@2}{%
5164                                          }{%
5165                                              {\printlineendnotearea{#1}{#2}}{%
5166                                              {\printlineendnotearea{#1}{#2}}{%
5167                                              }{%
5168                                              {\printlineendnotearea{#1}{#2}}%We keep every time line
5169                                              \csxdef{prevendline@#2}{\lineinfo@}{%
5170                                              }{%
5171 }{%
5172 %

```

```

\printsymlineendnotearea73 \newcommand{\printsymlineendnotearea}[1]{%
5174     \hspace{\csuse{Xendbefore symlinenum@#1}}{%
5175     \csuse{Xendnotenumfont@#1}{%
5176     \ifdimequal{\csuse{Xendboxsymlinenum@#1}}{\z@}{%
5177         {\csuse{Xendsymlinenum@#1}}{%
5178         {\hbox to \csuse{Xendboxsymlinenum@#1}{%
5179             {\csuse{Xendsymlinenum@#1}\hfill}}{%
5180         }{%
5181         \hspace{\csuse{Xendaftersymlinenum@#1}}{%
5182     }{%
5183 %

```

\printlineendnotearea This macro prints the space before the line number, changes the font, then prints the line number and the space after it. It is called by \endprint depending of the options about repeating line numbers. The first argument is line information, the second is the notes series (A, B, C, etc.)

```

5184 \newcommand{\printlineendnotearea}[2]{%
5185     \csuse{Xendbhooklinenumber@#2}{%
5186     \hspace{\csuse{Xendbefore number@#2}}{%
5187     \bgroup{%
5188         \csuse{Xendnotenumfont@#2}{%
5189         \ifdimequal{\csuse{Xendboxlinenum@#2}}{0pt}{%

```

```

5190   {\printendlines#1||\ifledRcol@{\Rlineflag\fi}%
5191   {\leavevmode%
5192   \hbox to \csuse{Xendboxlinenum@\#2}%
5193   {%
5194   \IfSubStr{RC}{\csuse{Xendboxlinenumalign@\#2}}{\hfill}{}%
5195   \printendlines#1||\ifledRcol@{\Rlineflag\fi}%
5196   \IfSubStr{LC}{\csuse{Xendboxlinenumalign@\#2}}{\hfill}{}%
5197   }%
5198   \egroup%
5199   \hspace{\csuse{Xendafternumber@\#2}}%
5200   \csuse{Xendahooklinenumber@\#2}%
5201 }%
5202 %

```

XX.2 User level commands

XX.2.1 Inserting contents to endnotes

The \Xendnotes commands are defined above, when defining apparatus commands by series. Here, we define only \toendnotes command not specific to a series, in order to insert arbitrary code. The regular version writes an unexpanded argument, while the regular version writes a once-expanded argument.

```

\toendnotes03 \newcommandx{\toendnotes}[2][1,usedefault]{%
\toendnotes04 \ifboolexpr{bool{numbering} or bool{numberingR}}{%
5205   \def\do##1{%
5206   \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname{%
5207   {\unexpanded{##2}\@percentchar}}%
5208   }%
5209   \ifstrempty{##1}{%
5210     {\dolistloop{\@series}}%
5211     {\docslist{##1}}%
5212   }{\led@err@toendnotes@outsidenumbering}%
5213 }%
5214 \WithSuffix\newcommandx\toendnotes*[2][1,usedefault]{%
5215 \ifboolexpr{bool{numbering} or bool{numberingR}}{%
5216   \def\do##1{%
5217   \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname{%
5218   {##2\@percentchar}}%
5219   }%
5220   \ifstrempty{##1}{%
5221     {\dolistloop{\@series}}%
5222     {\docslist{##1}}%
5223   }{\led@err@toendnotes@outsidenumbering}%
5224 }%
5225 %

```

XX.2.2 Printing endnotes

`\doendnotes` `\doendnotes` is the command you use to print one series of endnotes; it takes one argument: the series letter of the note series you want to print. `\Xendinsertsep@` is set to true at the first note of the series, and to false at the last one.

```

5226 \newif\ifXendinsertsep@
5227 \newcommand*{\doendnotes}[1]{%
5228   \l@dend@close{#1}%
5229   \begingroup
5230     \csxdef{prevpagenum@#1}{}%
5231     \csxdef{prevpagerange@#1}{}%
5232     \global\toggletrue{Xendfirstnote@#1}%
5233     \makeatletter
5234     \expandafter\let\csname #1end\endcsname=\endprint
5235     \input{l@auxdir\jobname.#1end}%
5236     \global\Xendinsertsep@false%
5237   \endgroup
5238 %

```

`\doendnotesbysection` `\doendnotesbysection` is a variant of the previous macro. While `\doendnotes` print endnotes for all of numbered sections `\doendnotesbysection` print the endnotes for the first numbered section at its first call for a series, then for the second section at its second call for the same series, then for the third section at its third call for the same series, and so on.

```

5239 \newcommand*{\doendnotesbysection}[1]{%
5240   \l@dend@close{#1}%
5241   \csxdef{prevpagenum@#1}{}%
5242   \csxdef{prevpagerange@#1}{}%
5243   \global\expandafter\advance\csname #1end@bysection\endcsname by 1%
5244   \begingroup%
5245     \makeatletter%
5246     \def\l@d@section##1{%
5247       \global\toggletrue{Xendfirstnote@#1}%
5248       \ifnumequal{##1}{\csname #1end@bysection\endcsname}%
5249         {\cslet{#1end}{\endprint}}%
5250         {\cslet{#1end}{\gobbleseven}}%
5251     }%
5252     \input{l@auxdir\jobname.#1end}%
5253     \global\Xendinsertsep@false%
5254   \endgroup%
5255 }%
5256 %

```

We close now the conditional period, which depends on `\ifnoend@`, because the following commands can be used by other commands than those specific to endnotes.

```

5257 }%
5258 %

```

`\setprintendlines` The `\printendlines` macro is similar to `\printlines` but is for printing endnotes rather than footnotes.

The principal difference between foot- and endnotes is that footnotes are printed on the page where they are specified but endnotes are printed at a different point in the document. We need an indication of the source of an endnote; `\setprintendlines` provides this by always printing the page number. The coding is slightly simpler than `\setprintlines`.

from the starting page number.

```
5259 \newcommand*{\setprintendlines}[6]{%
5260   \let\@cannot@start@print\relax%
5261   \let\@cannot@end@print\relax%
5262   \l@d@pnumfalse%
5263   \l@d@dashfalse%
5264   \l@d@elinfalse%
5265 }
```

First of all, we print the second page number only if the ending page number is different

```
5266 \ifnum#4=#1 \else
5267   \l@d@pnumtrue
5268   \l@d@dashtrue
5269 \fi
5270 %
```

We print the ending line number if: (1) we are printing the ending page number, or (2) the ending line is different from the starting line number.

```
5271 \ifboolexpr{%
5272   bool{\l@d@pnum}%
5273   or not test{\ifnumequal{#2}{#5}}%
5274 }{%
5275   \l@d@elintrue%
5276   \l@d@dashtrue%
5277   \l@d@elintrue
5278   \l@d@dashtrue
5279   \unless\ifx\relax\annot@end%
5280   \def\@cannot@end@print{%
5281     \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries
5282   }{\annot@end}%
5283   }%
5284 }%
5285 {}%
5286 %
```

We define the starting line number annotation as a merge of the starting annotation and ending annotation if we don't print the ending line number. Otherwise, it is only the starting annotation.

```
5287 \ifl@d@elin%
5288 \def\@cannot@start@print{%
```

```

5289      \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries}{\
5290          annot@start}%
5291      }%
5292      \else%
5293          \ifx\annot@start\annot@end%
5294              \unless\ifx\@annot@start\relax%
5295                  \def\@annot@start@print{%
5296                      \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries}\
5297                      {\annot@start}%
5298                  }%
5299                  \fi%
5300              \else%
5301                  \ifx\@annot@end@print\relax%
5302                      \def\@annot@start@print{%
5303                          \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries}\
5304                          \{}%
5305                          \ifx\annot@start\empty\else%
5306                              \annot@start%
5307                              \ifdefinelinearangesep@%
5308                                  \linearangesep@%
5309                              \else%
5310                                  \csuse{Xendlinerangeseparator@\@currentseries}%
5311                              \fi%
5312                          \fi%
5313                      \else%
5314                          \let\@annot@start@print\@annot@end@print%
5315                          \let\@annot@end@print\relax%
5316                      \fi%
5317                  \fi%
5318              \fi%
5319  %

```

We print the starting sub-line if it is nonzero.

```

5320      \l@d@ssubfalse
5321      \ifnum#3=0 \else
5322          \l@d@ssubtrue
5323      \fi
5324  %

```

We print the ending sub-line if it is nonzero and: (1) it is different from the starting sub-line number, or (2) the ending line number is being printed.

```

5325      \l@d@eslfalse
5326      \ifnum#6=0 \else
5327          \ifnum#6=#3
5328              \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
5329          \else
5330              \l@d@esltrue

```

```

5331      \l@d@dashtrue
5332      \fi
5333      \fi%
5334 %
5335      \ifl@d@dash%
5336      \ifboolexpr{togl{fulllines@} or test{\ifcsempy{Xendtwolines@\
5337      @currentseries}}}{%
5338      {}%
5339      {}%
5340      \setistwofollowinglines{#1}{#2}{#4}{#5}%
5341      \ifboolexpr{%
5342          {}%
5343          togl {Xendtwolinesbutnotmore@{@currentseries}}%
5344          and not%
5345          {}%
5346          bool {istwofollowinglines@}%
5347          {}%
5348          or%
5349          {}%
5350          (not test{\ifnumequal{#1}{#4}})%
5351          and togl{Xendtwolinesonlyinsamepage@{@currentseries}}%
5352          {}%
5353          {}%
5354          {}%
5355          {}%
5356          \l@d@dashfalse%
5357          \l@d@Xtwolinestruue%
5358          \l@d@elinfalse%
5359          \l@d@eslfase%
5360          \ifcsempy{Xendmorethantwolines@{@currentseries}}{%
5361              {}%
5362              {\ifistwofollowinglines@{\else{%
5363                  \l@d@Xmorethantwolinestrue%
5364                  \fi}%
5365                  {}%
5366                  {}%
5367              }%
5368          \fi}%
5369      }%

```

If the `\Xendnoidenticallinenumannotation` is set for this series, we check if the ending annotation is identical to the starting. If true, we don't print the ending annotation

```

5370      \iftoggle{Xendnoidenticallinenumannotation@{@currentseries}}{%
5371          \ifx\annot@start\annot@end%
5372          \let\@annot@end@print\relax%
5373          \ifx\linenumrep\gobble%Don't print the dash if we're not printing
the line number

```

```

5374     \l@d@dashfalse%
5375     \fi%
5376     \fi%
5377   }{}}%
5378 %

```

End of `\setprintendlines`.

```

5379 }%
5380 %

```

`\printendlines` Now we are ready to print it all.

```

5381 \def\printendlines#1|#2|#3|#4|#5|#6|#7|#8|{%
5382   \begingroup
5383   \setprintendlines{#1}{#2}{#3}{#4}{#5}{#6}%
5384 %

```

The only subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could be coming after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period).

So, first, start the starting line box, if needed.

```

5385 \ifdim\equal{\csuse{Xendboxstartlinenum@\currentseries}}{0pt}%
5386   {\bgroup%
5387   {\leavevmode\hbox to \csuse{Xendboxstartlinenum@\currentseries}\bgroup%
5388   \hfill}%
5389 %

```

Then, print the starting page number-

```

5389 \ifboolexpr{%
5390   ()%
5391   test{\ifcsstring{prevpagenum@\currentseries}{#1}}%
5392   and not%
5393   (t gl{Xendpagenumberonlyfirstifsingl e@\currentseries} and bool{%
5394     1@d@pnum})%
5395   )%
5396   or%
5397   ()%
5398   test {\ifcsstring{prevpagerange@\currentseries}{#1-#4}}%
5399   )%
5400   }%
5401   \ifcse mpty{Xendsympagenum@\currentseries}%
5402   {\hspace{\csuse{Xendinplaceofpagenumber@\currentseries}}}%
5403   {\csuse{Xendsympagenum@\currentseries}}%
5404   }%
5405   t%
5406   \wrap@edcrossref{@this@crossref@start}{\printnpnum{#1}}%
5407   }%
5408 %

```

Then, determine what must be printed before the start line.

```

5409   \ifl@d@dash%
5410     \ifl@d@pnum%
5411       \csuse{Xendlineprefixsingle@\@currentseries}%
5412     \else%
5413       \ifcsempy{Xendlineprefixmore@\@currentseries}%
5414         {\csuse{Xendlineprefixsingle@\@currentseries}}%
5415         {\csuse{Xendlineprefixmore@\@currentseries}}%
5416       \fi%
5417     \else%
5418       \csuse{Xendlineprefixsingle@\@currentseries}%
5419     \fi%
5420 %

```

Then print the starting line, followed, if needed, by the side flag and the starting sub line number, then the line number annotation.

```

5421   \ifcsstring{Xendlinenumannotationposition@\@currentseries}{before}%
5422     {\@cannot@start@print}%
5423     {}%
5424   \wrap@edcrossref{\@this@crossref@start}{%
5425     \ifledRcol@%
5426       \linenumrepR{#2}%
5427     \else%
5428       \linenumrep{#2}%
5429     \fi%
5430   }%
5431   \iftoggle{Xendlineflag@\@currentseries}{\ifledRcol@{\Rlineflag}\fi}{}%
5432   \ifl@d@ssub%
5433     \csuse{Xendsublinesep@\@currentseries}%
5434     \wrap@edcrossref{\@this@crossref@start}{%
5435       \ifledRcol@%
5436         \sublinenumrepR{#3}%
5437       \else%
5438         \sublinenumrep{#3}%
5439       \fi%
5440     }%
5441   \fi%
5442   \ifcsstring{Xendlinenumannotationposition@\@currentseries}{after}%
5443     {\@cannot@start@print}%
5444     {}%
5445 %

```

Close the box.

```

5446   \egroup%
5447 %

```

Open the box for the ending line number.

```

5448   \ifdimequal{\csuse{Xendboxendlinenum@\@currentseries}}{0pt}%
5449     {\bgroup}%

```

```

5450      {\hbox to \csuse{Xendboxendlinenum@\@currentseries}\bgroup}%
5451 %

```

Print the dash + the ending line number, or the line number range symbol.

```

5452  \ifl@d@Xtwolines%
5453    \ifl@d@XmorethanTwolines%
5454      \csuse{XendmorethanTwolines@\@currentseries}%
5455    \else%
5456      \csuse{Xendtwolines@\@currentseries}%
5457    \fi%
5458  \else%
5459    \ifl@d@dash%
5460      \ifdefined\linerangesep@%
5461        \linerangesep@%
5462      \else%
5463        \csuse{Xendlinerangeseparator@\@currentseries}%
5464      \fi%
5465    \fi%
5466 %

```

Print the ending page number.

```

5467  \ifl@d@pnum%
5468    \ifcstrcmp{prevpagerange@\@currentseries}{#1-#4}%
5469    {%
5470      \ifcsempy{Xendsympagenum@\@currentseries}%
5471        {\hspace{\csuse{Xendifplaceofpagenumber@\@currentseries}}}%
5472        {\csuse{Xendsympagenum@\@currentseries}}%
5473    }%
5474    {%
5475      \wrap@edcrossref{@this@crossref@end}\printnpnum{#4}%
5476    }%
5477  \fi%
5478 %

```

Print the ending line number, with, if needed, the line prefix, and followed by the side flag, the subline number, and line number annotation.

```

5479  \ifcstrcmp{Xendlinenumannotationposition@\@currentseries}{before}%
5480    {@cannot@end@print}%
5481    {}%
5482  \ifl@d@elin%
5483    \ifl@d@pnum\csuse{Xendlineprefixsingle@\@currentseries}\fi%
5484    \wrap@edcrossref{@this@crossref@end}{%
5485      \ifledRcol@%
5486        \linenumrep{#5}%
5487      \else%
5488        \linenumrep{#5}%
5489      \fi%
5490    }%
5491  \iftoggle{Xendlineflag@\@currentseries}{\ifledRcol@\Rlineflag\fi}{}%

```

```

5492 \fi%
5493 \ifl@d@esl%
5494   \ifl@d@elin%
5495     \csuse{Xendsublinesep@\@currentseries}%
5496   \fi%
5497   \wrap@edcrossref{\@this@crossref@end}{%
5498     \ifledRcol@%
5499       \sublinenumrep{\#6}%
5500     \else%
5501       \sublinenumrep{\#6}%
5502     \fi%
5503   }%
5504 \fi%
5505 \ifcsstring{Xendlinenumannotationposition@\@currentseries}{after}%
5506   {\@annot@end@print}%
5507   {}%
5508 \fi%
5509 %

```

Close the ending line box.

```

5510 \ifdimequal{\csuse{Xendboxendlinenum@\@currentseries}}{0pt}%
5511   {}%
5512   {\hfill}\% Prevent underfull hbox
5513 \egroup%
5514 %

```

And, finally, save, if needed, the current page number for the Xendpagenumberonlyfirst hooks.

```

5515 \iftoggle{Xendpagenumberonlyfirst@\@currentseries}%
5516   {\iftoggle{Xendpagenumberonlyfirstintwo@\@currentseries}%
5517     {\csxdef{prevpagerange@\@currentseries}{\#1-\#4}}%
5518     {\csxdef{prevpagenum@\@currentseries}{\#4}}%
5519   }%
5520   {}%
5521 %

```

Now, the end of \printendlines macro.

```

5522 \endgroup%
5523 }%
5524 %
5525 %

```

\printnpnum A macro to print a page number in an endnote. Should not be override anymore

```

5526 \newcommand*{\printnpnum}[1]{\csuse{Xendbeforepagenumber@\@currentseries}%
5527   \#1\csuse{Xendafterpagenumber@\@currentseries}%
5528 %

```

XXI Generate series of notes

In this section, X means the name of the series (A, B etc.)

\series \series\series creates one more new series. It is a public command, which just loops on the private command \newseries@.

```
5529 \newcommand{\newseries}[1]{%
5530     \def\do##1{\newseries@{##1}}%
5531     \doCSVlist{#1}
5532 }
5533 %
```

\@series The \series@ macro is an etoolbox list, which contains the name of all series.

```
5534 \newcommand{\@series}{}
5535 %
```

The command \newseries@\series creates a new series of the footnote.

```
\newseries@36 \newcommand{\newseries@}[1]{%
5537 %
```

XXI.1 Test if series is still existing

```
5538     \xifinlist{#1}{\@series}{\led@warn@SeriesStillExist{#1}}%
5539     \f%
5540 %
```

XXI.2 Init specific to reledpar

When calling \newseries@ after having loaded reledpar, we need to load specific setting.

```
5541     \ifdef{\newseries@par}{%
5542         \newseries@par{#1}}%
5543     \fi%
5544 %
```

XXI.3 For critical footnotes

Critical footnotes are those which start with letters. We look for the \nocritical option of reledmac.

```
5545     \unless{\ifnocritical}{%
5546 %}
```

XXI.3.1 Options

```

5547   \newtoggle{Xlineflag@#1}
5548   \newtoggle{Xparindent@#1}
5549   \newtoggle{Xlemmadisablefontselection@#1}
5550   \csgdef{Xwrapcontent@#1}{}%
5551   \csgdef{Xbeforeinserting@#1}{}%
5552   \csgdef{Xhangindent@#1}{0pt}%
5553   \csgdef{Xragged@#1}{}%
5554   \csgdef{Xhsizetwocol@#1}{0.45 \hsize}%
5555   \csgdef{Xhsizethreecol@#1}{.3 \hsize}%
5556   \csgdef{Xcolalign@#1}{\raggedright}%
5557   \csgdef{Xnotenumfont@#1}{\normalfont}%
5558   \csgdef{Xnotefontsize@#1}{\footnotesize}%
5559   \csgdef{Xbhooknote@#1}{}%
5560   \csgdef{Xbhookgroup@#1}{}%
5561
5562   \csgdef{Xboxlinenum@#1}{0pt}%
5563   \csgdef{Xboxlinenumalign@#1}{L}%
5564
5565   \csgdef{Xboxstartlinenum@#1}{0pt}%
5566   \csgdef{Xboxendlinenum@#1}{0pt}%
5567
5568   \csgdef{Xboxsymlinenum@#1}{0pt}%
5569   \newtoggle{Xnumberonlyfirstinline@#1}%
5570   \newtoggle{Xgroupbyline@#1}%
5571   \newtoggle{Xgroupbylineseparetwolines@#1}%
5572   \newtoggle{Xnumberonlyfirstintwolines@#1}%
5573   \csgdef{Xtwolines@#1}{}%
5574   \csgdef{Xmorethantwolines@#1}{}%
5575   \csgdef{Xsublinesep@#1}{\fullstop}%
5576   \csgdef{Xpagelinesep@#1}{\csname Xsublinesep@#1\endcsname}%
for
backward compatibility, call Xsublinesep@#1
5577   \newtoggle{Xtwolinesbutnotmore@#1}%
5578   \newtoggle{Xtwolinesonlyinsamepage@#1}%
5579   \newtoggle{Xonlypstart@#1}%
5580   \newtoggle{Xpstarteverytime@#1}%
5581   \newtoggle{Xpstart@#1}%
5582   \newtoggle{Xstanzao@#1}%
5583   \csgdef{Xstanzaseparator@#1}{}%
5584   \csgdef{Xsymlinenum@#1}{}%
5585   \newtoggle{Xnonumber@#1}%
5586   \csgdef{Xbeforenumber@#1}{0pt}%
5587   \csgdef{Xtxtbeforenumber@#1}{}%
5588   \csgdef{Xafternumber@#1}{0.5em}%
5589   \newtoggle{Xnonbreakableafternumber@#1}%
5590   \csgdef{Xbeforesymlinenum@#1}{\csuse{Xbeforenumber@#1}}%
5591   \csgdef{Xaftersymlinenum@#1}{\csuse{Xafternumber@#1}}%
5592   \csgdef{Xinplaceofnumber@#1}{1em}%
5593   \global\cslet{Xlemmaseparator@#1}{\rbracket}%

```

```

5594 \csgdef{Xbeforelemmaseparator@#1}{0em}%
5595 \csgdef{Xafterlemmaseparator@#1}{0.5em}%
5596 \csgdef{Xinplaceoflemmaseparator@#1}{1em}%
5597 \csgdef{Xbeforenotes@#1}{1.2em \oplus .6em \ominus .6em}
5598 \csgdef{Xafterrule@#1}{0pt}

5599
5600 \csgdef{Xtxtbeforenotes@#1}{}
5601 \newtoggle{Xtxtbeforenotes@#1@typeset}%Not directly used by user,
but internal
5602 \newtoggle{Xtxtbeforenotesonlyonce@#1}%

5603
5604 \csgdef{Xmaxhnotes@#1}{0.8\vsizex}
5605 \newtoggle{Xnoteswidthliketwocolumns@#1}%
5606 \csgdef{Xparafootsep@#1}{}
5607 \csgdef{Xafternote@#1}{1em plus .4em minus .4em}
5608 \csgdef{Xlinerangeseparator@#1}{\endashchar}%

5609
5610 \csgdef{Xlemmafont@#1}{}
5611 \csgdef{Xwraplemma@#1}{}
5612 \csgdef{Xwidth@#1}{\hsize}
5613 \csgdef{Xwraplinenumannotation@#1}{\textsuperscript}%
5614 \csgdef{Xlinenumannotationposition@#1}{after}%
5615 \newtoggle{Xnoidenticallinenumannotation@#1}%
5616 %

```

XXI.3.2 Create inserts, needed to add notes in foot

As regards inserts, see chapter 15 of *The TeXbook* by D. Knuth.

```

5617 \expandafter\newinsert\csname #1footins\endcsname%
5618 \unless\ifnoledgroup@%
5619 \expandafter\newinsert\csname mp#1footins\endcsname%
5620 \fi%
5621 %

```

XXI.3.3 Create commands for critical apparatus, \Afootnote, \Bfootnote etc.

Note the double # in command: it is because command it is made inside another command.

```

5622 \global\notbool{parapparatus@}{\expandafter\newcommand\expandafter
*}{\expandafter\newcommand}\csname #1footnote\endcsname[2] [] {%
5623 \if@edtext@secondarg@%
5624 \ifledRcol%
5625 \ifcsstring{Xonlyside@#1}{L}{\%
5626 led@error@note@called@onrightside{#1footnote}}{}%
5627 \else%
5628 \ifcsstring{Xonlyside@#1}{R}{\%
5629 led@error@note@called@onleftside{#1footnote}}{}%
5628 \fi%
5629 \begingroup%

```

```

5630   \newcommand{\content}{##2}%
5631   \ifnumberedpar@%
5632     \ifledRcol%
5633       \ifluatex%
5634         \footnotelang@lua[R]%
5635       \fi%
5636     \@ifundefined{xp@main@language}%
5637       {}%
5638     \else%
5639       \footnotelang@poly[R]%
5640     \fi%
5641     \footnoteoptions@{R}{##1}{true}%
5642     \xright@appenditem{%
5643       \ifbool{indt@innote}%
5644         {\unexpanded{\let\index\nindex}}%
5645       \ifbool{indt@notenumber}%
5646         {\unexpanded{\let\index\nindex}}%There is no note
5647         {}%
5648       \noexpand\xnote@true%
5649       \noexpand\prepare@Xprenotes{#1}%
5650       \noexpand\prepare@edindex@fornote{\l@d@nums}%
5651       \unexpanded{\def\sw@list@inedtext}{\expandafter\
5652         unexpanded\expandafter{\sw@inthisedtext}}%The value of the \sw@inthisedtext
5653         of current \edtext will be pushed to \sw@list@inedtext when the notes are
5654         expanded.
5655       \noexpand\setcounter{stanzaR}{\the\c@stanzaR}%Save
5656         stanzaR counter for footnote
5657       \unexpanded{\def@this@crossref@start}{\theedtext:
5658         start}%
5659       \unexpanded{\def@this@crossref@end}{\theedtext:end}%
5660       \expandonce{\@beforeinsertofthisedtext}% Internal for
5661         now, no reason to make it public
5662       \noexpand\parse@annot{\l@current@annotR}%
5663       \noexpand\csuse{v#1footnote}{#1}%
5664       {\l@d@nums}{\expandonce{\@tag}{\expandonce\content}}%
5665     %
5666     \noexpand\xnote@false%
5667     \unexpanded{\advance\@edindex@fornote@\m@ne}%
5668     \ifbool{indt@innote}%
5669       {\unexpanded{\let\index\orig@@index}}%
5670     \ifbool{indt@notenumber}%
5671       {\unexpanded{\let\index\orig@@index}}%
5672     \} \to \inserts@listR
5673     \footnoteoptions@{R}{##1}{false}%
5674     \global\advance\insert@countR \m@ne%
5675   \else%
5676     \ifluatex%
5677       \footnotelang@lua%

```

```

5672          \fi%
5673  \@ifundefined{xpg@main@language}{%if polyglossia
5674      {}%
5675      {\footnotelang@poly}%
5676      \footnoteoptions@{L}{##1}{true}%
5677      \xright@appenditem{%
5678          \ifbool{indtl@innote}{%
5679              {\unexpanded{\let\index\nindex}}%
5680              {}%
5681          \ifbool{indtl@notenumber}{%
5682              {\unexpanded{\let\index\nindex}}%There is no note
5683              ...number so
5684              {}%
5685              \noexpand\Xnote@true%
5686              \noexpand\prepare@Xprenotes{#1}%
5687              \noexpand\prepare@edindex@fornote{\l@d@nums}%
5688              \unexpanded{\def\sw@list@inedtext}{\expandafter\
5689              unexpanded\expandafter{\sw@inthisedtext}}%The value of the \sw@inthisedtext
5690              of current edtext will be pushed to \sw@list@inedtext when the notes are
5691              expanded.
5692              \ifl@dpairing%
5693                  \noexpand\setcounter{stanzaL}{\the\c@stanzaL}%Save
5694                  stanzaR counter for footnote
5695                  \fi%
5696                  \unexpanded{\def\@this@crossref@start}{\theedtext:
5697                  start}%
5698                  \unexpanded{\def\@this@crossref@end}{\theedtext:end}%
5699                  \expandonce{\@beforeinsertofthisedtext}%Internal for
5700                  now, no reason to make it public
5701                  \noexpand\parse@annot\l@current@annot|%
5702                  \noexpand\csuse{v#1footnote}%
5703                  {#1}%
5704                  {{\l@d@nums}{\expandonce{@tag}{\expandonce\content
5705                  }}}%
5706                  \noexpand\Xnote@false%
5707                  \unexpanded{\advance@\edindex@fornote@\m@ne}%
5708                  \ifbool{indtl@innote}{%
5709                      {\unexpanded{\let\index\orig@@index}}%
5710                      {}%
5711                      \ifbool{indtl@notenumber}{%
5712                          {\unexpanded{\let\index\orig@@index}}%
5713                          {}%
5714                          }{\to\inserts@list
5715                          \global\advance\insert@count \c@ne%
5716                          \footnoteoptions@{L}{##1}{false}%
5717                          \fi
5718                      \else
5719                          \csuse{v#1footnote}{#1}{{0|0|0|0|0|0|0}{}{##1}}%
5720                      \fi%
5721                  \endgroup%

```

```

5714     \else%
5715         \led@err@FootnoteNotInSecondArgEdtext{#1}%
5716     \fi%
5717     \ignorespaces%
5718 }
5719 %

```

Create counter used to determine on which page the previous note was called.

```

5720     \expandafter\newcount\csname #1prevpage@num\endcsname%
5721     \expandafter\newcount\csname #1prevpage@numR\endcsname%
5722 %

```

We need to be able to modify `reledmac`'s footnote macros and restore their

```

5723     \global\csletcs{\#1@footnote}{\#1footnote}
5724 %

```

XXI.3.4 Set standard display

```

5725     \Xarrangement@normal{#1}%
5726 %

```

End of for critical footnotes.

```

5727     \fi
5728 %

```

XXI.4 For familiar footnotes

Familiar footnotes are those which end with letters. We look for the `nofamiliar` option of `reledmac`.

```

5729     \unless\ifnofamiliar@
5730 %

```

XXI.4.1 Options

```

5731     \newtoggle{parindentX@#1}
5732     \csgdef{wrapcontentX@#1}{}%
5733     \csgdef{hangindentX@#1}{0pt}%
5734     \csgdef{beforeinsertingX@#1}{}%
5735     \csgdef{raggedX@#1}{}%
5736     \csgdef{hsizetwocolX@#1}{0.45 \hsize}%
5737     \csgdef{hsizethreecolX@#1}{.3 \hsize}%
5738     \csgdef{colalignX@#1}{\raggedright}%
5739     \csgdef{notenumfontX@#1}{\normalfont}%
5740     \csgdef{notefontsizeX@#1}{\footnotesize}%
5741     \csgdef{bhooknoteX@#1}{}%
5742     \csgdef{bhookgroupX@#1}{}%
5743     \csgdef{afterruleX@#1}{0pt}

```

```

5744 \csgdef{beforeenotesX@#1}{1.2em \oplus .6em \ominus .6em}
5745 \csgdef{maxhnotesX@#1}{0.8\vsizex}%
5746 \newtoggle{noteswidthliketwocolumnsX@#1}%
5747 \csgdef{parafootsepX@#1}{\%}
5748 \csgdef{afternoteX@#1}{1em plus .4em minus .4em}
5749 \csgdef{widthX@#1}{\hsize}%
5750 \csgdef{txtbeforenotesX@#1}{\%}
5751 \newtoggle{txtbeforesnotesX@#1@typeset}\%Not directly used by user,
but internal
5752 \newtoggle{txtbeforenotesonlyonceX@#1}%
5753 % End of for familiar footnotes.
5754 % \subsubsection{Create inserts, needed to add notes in foot}
5755 % As regards inserts, see chapter 15 of the TeXBook by D. Knuth.
5756 % \begin{macrocode}
5757 \expandafter\newinsert\csname footins#1\endcsname%
5758 \unless\ifnoleadgroup@\%
5759 \expandafter\newinsert\csname mpfootins#1\endcsname%
5760 \fi%
5761 %

```

XXI.4.2 Create tools for familiar footnotes (\footnoteX)

First, create the \footnoteX command. Note the double # in command: it is because a command is called inside another command.

```

5762 \global\expandafter\newcommand\csname footnote#1\endcsname[2][]{%
5763 \begingroup%
5764 \prepare@prenotesX{\#1}%
5765 \newcommand{\content}{##2}%
5766 %
5767 %

```

If we are using the \csquotes package, we reset the quotation level.

```

5768 \ifdefinable\csq@qlevel{%
5769 \csq@qlevel=0\relax%
5770 \fi%
5771 %

```

If we are preparing parallel typesetting, we cannot just increase the footnote counter. Read *reledpar*'s handbook about that (V.1.2 p. 53). If we have a manual footnote mark, use it.

```

5772 \global\expandafter\advance\csname footnote#1@reading\
5773 endcsname by \one%
5774 \ifstrempty{##1}{%
5775 \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or
5776 bool{l@dprintingcolumns}}{%
5777 \ifcsdef{footnote#1reading}{\the\csname footnote#1@reading
5778 \endcsname=typeset}%
5779 {\setcounter{footnote#1}{\csuse{footnote#1reading}{\the\csname
5780 footnote#1@reading\endcsname=typeset}}}%

```

```

5777      {\setcounter{footnote#1}{\the\csname footnote#1@reading\
5778      endcsname}}%
5779      }{%
5780      \stepcounter{footnote#1}%
5781      }%
5782 %

```

We also have to check consistency with `\onlysideX` setting.

```

5783      \ifledRcol%
5784          \ifcsstring{\onlysideX@#1}{L}{%
5785              \led@error@note@called@onrightside{footnote#1}}{}%
5786          \else%
5787              \ifcsstring{\onlysideX@#1}{R}{%
5788                  \led@error@note@called@onleftside{footnote#1}}{}%
5789          \fi%
5790 %

```

And now, the feature not depending of wether we are preparing parallel typesetting

```

5791      \ifstrempy{##1}{%
5792          {\protected@csxdef{@thefnmark#1}{\csuse{thefootnote#1}}}%
5793          {\protected@csxdef{@thefnmark#1}{##1}}%
5794          \notoggle{nomk@}{Nomk is set to true when using \
5795          footnoteXnomk with \parpackage
5796          {\csuse{@footnotemark#1}}%
5797          {}%
5798          \ifluatex%
5799              \xdef\footnote@luatextextdir{\the\textdir}%
5800              \xdef\footnote@luatexpardir{\the\pardir}%
5801          \fi%
5802          \if@ledgroup%
5803              \led@set@index@fornote{#1}%
5804          \fi%
5805          \csuse{vfootnote#1}{##1}{\expandonce\content}{##1}\
5806          m@mmf@prepare%
5807          \ifbool{indtl@innote}%
5808              {\let\index\orig@@index}%
5809              {}%
5810              \ifbool{indtl@notenumber}%
5811                  {\let\index\orig@@index}%
5812                  {}%
5813          \endgroup%
5814      }
5815 %

```

Then define the counters. The `\TeX` counter `footnoteX` is the only one manipulated by the user. This is the one which is printed. The `\TeX` counter `\footnoteX@reading` is increased at each footnote. It is used for hyperlinks, for using `hyperlink` package, and for getting the correct footnote number when using parallel typesetting (V.1.2 p. 53).

```

5812     \newcounter{footnote#1}
5813         \global\expandafter\renewcommand\csname thefootnote#1\endcsname{\
5814             arabic{footnote#1}}
5815             \expandafter\newcount\csname footnote#1@reading\endcsname%
5816             %

```

Create counter used to determine on which page the previous note was called.

```

5816     \expandafter\newcount\csname prevpage#1@num\endcsname%
5817     \expandafter\newcount\csname prevpage#1@numR\endcsname%
5818     %

```

Add `\let\footnoteX\@gobble` to `\no@expands`.

```

5819     \expandafter\gappto\expandafter\no@expands\expandafter{\expandafter\
5820         let\csname footnote#1\endcsname\@gobble}%
5821         %

```

And now, define `\footnoteXmark` and `\footnoteXtext`, equivalent to classical `\footnotemark` and `\footnotetext`.

```

5821     \expandafter\newcommand\csname footnote#1mark\endcsname{%
5822         \begingroup%
5823             \prepare@prenotesX{#1}%
5824             \stepcounter{footnote#1}%
5825             \protected@csxdef{@thefnmark#1}{\csuse{thefootnote#1}}%
5826             \csuse{@footnotemark#1}%
5827             \m@mmf@prepare%
5828             \endgroup%
5829         }%
5830         \expandafter\newcommand\csname footnote#1text\endcsname[1]{%
5831             \begingroup%
5832                 \csuse{vfootnote#1}{#1}{\expandonce{##1}}%
5833             \endgroup%
5834         }%
5835         %

```

Do not forget to initialize the series.

```

5836     \arrangementX@normal{#1}%
5837     \fi
5838     %

```

XXI.5 The endnotes

Endnotes are commands like `\Xendnote`, where X is a series letter. First, we check for the `noend` options.

```

5839     \unless\ifnoend@
5840     %

```

XXI.5.1 The auxiliary file

```
\l@d@Xend
\ifl@dend@X
\l@dend@Xtrue Endnotes of all varieties are saved up in a file, one by series, typically named <jobname>.Xend.
\l@dend is the output stream number for this file, and \ifl@dend@X is a flag that is
true when the file is open.

\l@dend@Xfalse
5841      \expandafter\newwrite\csname l@d@#1end\endcsname%
5842      \expandafter\newif\csname ifl@dend@#1\endcsname%
5843  %
```

XXI.5.2 The main macro

The \Xendnote macro functions to write one endnote to the .Xend file. We change \newlinechar so that in the file every space becomes the start of a new line; this generally ensures that a long note does not exceed restrictions on the length of lines in files.

```
5844
5845      \global\expandafter\newcommandx\csname #1endnote\endcsname[2][1,
5846      usedefault]{%
5847          \bgroup%
5848          \newlinechar='40%
5849          \global\@noneed@Footnotetrue%
5850          \newcommand{\content}{##2}%
5851          \stepcounter{labidx}%
5852          \expandafter\immediate\expandafter\write\csname l@d@#1end\
5853          endcsname{%
5854              \unexpanded{\def\sw@list@inedtext}%
5855              {\expandafter\unexpanded\expandafter{\sw@inthisedtext}}%
5856              \percentchar\space%Explicit space, to add a linebreak in the
5857              output file
5858              \noexpand\parse@annot\l@current@annot|\percentchar\space%
5859              \expandafter\string\csname #1end\endcsname%
5860              {\ifnumberedpar@\l@d@nums\fi}%
5861              {\ifnumberedpar@\expandonce\@tag\fi}%
5862              {\expandonce\content}%
5863              {##1}%
5864              {\unexpanded{##1}}%
5865              {\ifledRcol R\else L\fi}%
5866              {\theedtext}%
5867              \percentchar%
5868          }%
5869  %
```

XXI.5.3 Tools

The `\Xtoendnotes` command inserts any arbitrary content into the endnote file. It is an alias of the more generalist `\addtoendnotes`

```

5870
5871      \global\expandafter\newcommand\csname #1toendnotes\endcsname[1]{%
5872          \toendnotes[#1]{##1}%
5873      }%
5874
5875      \expandafter\WithSuffix\expandafter\newcommand\csname #1toendnotes\endcsname*[1]{%
5876          \toendnotes*[#1]{##1}%
5877      }%
5878
5879 %

```

XXI.5.4 Internal commands

`\Xendnote` commands called `\Xend` commands on to the endnote file; these are analogous to the various `footfmt` commands above, and they take the same arguments. When we process this file, we want to pick out the notes of one series and ignore all the rest. To do that, we equate the `end` command for the series we want to `\endprint`, and leave the rest equated to `\@gobbleseven`, which just skips over its seven arguments.

```

5880
5881      \global\cslet{\#1end}{\@gobbleseven}
5882 %

```

We need to store the number of times `\doendnotesbysection` is called for one series.

```

5883      \global\expandafter\newcount\csname #1end@bysection\endcsname%
5884 %

```

XXI.5.5 The options

```

5885      \csgdef{Xendwraplemma@#1}{}%
5886      \csgdef{Xendwrapcontent@#1}{}%
5887      \csgdef{Xendtwolines@#1}{}%
5888      \csgdef{Xendmorethan twolines@#1}{}%
5889      \newtoggle{Xendtwolinesbutnotmore@#1}{}%
5890      \newtoggle{Xendtwolinesonlyinsamepage@#1}{}%
5891      \newtoggle{Xendlemmadisablefontselection@#1}%
5892      \csgdef{Xendnotenumfont@#1}{\normalfont}%
5893      \csgdef{Xendnotefontsize@#1}{\footnotesize}%
5894      \csgdef{Xendbhooknote@#1}{}%
5895
5896      \csgdef{Xendsublinesep@#1}{\fullstop}%
5897
5898      \csgdef{Xendbeforenumber@#1}{0pt}

```

```

5899 \csgdef{Xendafternumber@#1}{0.5em}
5900
5901 \csgdef{Xendboxlinenum@#1}{0pt}%
5902 \csgdef{Xendboxlinenumalign@#1}{L}%
5903
5904 \csgdef{Xendboxstartlinenum@#1}{0pt}%
5905 \csgdef{Xendboxendlinenum@#1}{0pt}%
5906
5907 \csgdef{Xendlemmaseparator@#1}{ }%
5908 \csgdef{Xendbeforelemmaseparator@#1}{0em}%
5909 \csgdef{Xendafterlemmaseparator@#1}{0.5em}%
5910 \csgdef{Xendinplaceoflemmaseparator@#1}{0.5em}%
5911
5912 \newtoggle{Xendparagraph@#1}%
5913 \csgdef{Xendafternote@#1}{1em plus .4em minus .4em}%
5914 \csgdef{Xendsep@#1}{ }%
5915
5916 \csgdef{Xendinplaceofnumber@#1}{0pt}%
5917 \newtoggle{Xendnonumber@#1}%
5918
5919 \csgdef{Xendhangindent@#1}{0pt}%
5920 \newtoggle{Xendnumberonlyfirstinline@#1}%
5921 \newtoggle{Xendnumberonlyfirstintwo-lines@#1}%
5922
5923 \csgdef{Xendbeforesymlinenum@#1}{\csuse{Xendbeforenumber@#1}}%
5924 \csgdef{Xendaftersymlinenum@#1}{\csuse{Xendafternumber@#1}}%
5925 \csgdef{Xendsymlinenum@#1}{ }%
5926 \csgdef{Xendboxsymlinenum@#1}{0pt}%
5927
5928 \csgdef{Xendbhooklinenum@#1}{ }%
5929 \csgdef{Xendehooklinenum@#1}{ }%
5930 \csgdef{Xendbhookinplaceofnumber@#1}{ }%
5931 \csgdef{Xendehookinplaceofnumber@#1}{ }%
5932
5933 \csgdef{Xendlinerangeseparator@#1}{\endashchar}%
5934
5935 \csgdef{Xendbeforepagenumber@#1}{p. }%
5936 \csgdef{Xendafterpagenumber@#1}{ } }%
5937 \csgdef{Xendlineprefixsingle@#1}{ }%
5938 \csgdef{Xendlineprefixmore@#1}{ }%
5939
5940 \newtoggle{Xendlineflag@#1}
5941
5942 \csgdef{Xendlemmafont@#1}{ }%
5943
5944 \csgdef{Xendlinenumannotationposition@#1}{after}%
5945 \csgdef{Xendwraplinenumannotation@#1}{\textsuperscript}%
5946 \newtoggle{Xendnoidenticallinenumannotation@#1}%
5947
5948 \newtoggle{Xendpagenumberonlyfirst@#1}%

```

```

5949 \newtoggle{Xendpagenumberonlyfirstifsingle@#1}%
5950 \newtoggle{Xendpagenumberonlyfirstintwo@#1}%
5951 \csgdef{Xendsympagenum@#1}{}%
5952 \csgdef{Xendinplaceofpagenumber@#1}{Opt}%
5953
5954 \csgdef{Xendtxtbeforenotes@#1}{}%
5955 \newtoggle{Xendifrstnote@#1}%Not a hook, but used to apply
  Xendtxtbeforenotes
5956 %
5957 %

```

End of endnotes declaration

```

5958 \fi%
5959 %

```

Dump series in \@series

```

5960 \listxadd{\@series}{#1}
5961 }
5962 }% End of \newseries
5963 %

```

XXI.6 Init standards series (A,B,C,D,E)

```

5964 \expandafter\newseries\expandafter{\default@series}%
5965 %

```

XXII Setting series display

XXII.1 Change series order

`\seriesatbegin` `\seriesatbegin{⟨s⟩}` changes the order of series, to put the series `⟨s⟩` at the beginning of the list. The series can be the result of a command.

```

5966 \newcommand{\seriesatbegin}[1]{%
5967   \StrDel{\@series}{#1}[\@series]%
5968   \edef\@new{}%
5969   \listead{\@new}{#1}%
5970   \listead{\@new}{\@series}%
5971   \xdef\@series{\@new}%
5972 }
5973 %

```

`\seriesatend` And `\seriesatend` moves the series to the end of the list.

```

5974 \newcommand{\seriesatend}[1]{%
5975   \StrDel{\@series}{#1}[\@series]%
5976   \edef\@new{}%
5977   \listead{\@new}{\@series}%
5978   \listead{\@new}{#1}%

```

```

5979     \xdef\@series{\@new}%
5980 }
5981 %

```

XXII.2 Test series order

`\ifseriesbefore` `\ifseriesbefore{<seriesA>}{<seriesB>}{{<true>}}{{<false>}}` expands to `<true>` if `<seriesA>` is printed before `<seriesB>`, or to `<false>` otherwise.

```

5982 \newcommand{\ifseriesbefore}[4]{%
5983   \StrPosition{\@series}{#1}[\@first]%
5984   \StrPosition{\@series}{#2}[\@second]%
5985   \ifnumgreater{\@second}{\@first}{#3}{#4}%
5986 }
5987 %

```

XXII.2.1 Get the first series

In some specific case, we need to know the first series of the list of series.

```

\@getfirstseries88 \newcommand{\@getfirstseries}{%
5989   \ifdefempty{\@series}{%
5990     {\xdef\@firstseries{}%
5991      {\StrChar{\@series}{1}[\@firstseries]}%
5992    }%
5993 %

```

XXII.3 Series setting

XXII.3.1 General way of working

The setting's command (like `\numberonlyfirstinline`), also called “hooks” can be divided in two categories: those which require a string values and those which require a boolean value. The first category includes those which require a length value, because we store the length's expression send by user and we evaluate it only in the commands which requires to know the setting. The second category require boolean value only when it is set to FALSE. Otherwise, we understand the insinuated value is TRUE.

For each “hook” command, we store the value in commands (first category) or a etoolbox's toggle (second category) which names are in the form `\<hook>@<series>`. For example, when calling `\twolines{<sq.>}`, we store `sq.` in commands `\twolines@A`, `\twolines@B`, `\twolines@C...` for each series defined for use with `reledmac`, or, if the `[<series>]` optional argument was send, for each series of this argument.

These values are tested in some specific places, scattered in all the code, depending of their effects. The default values are defined by the `\newsseries@` command.

In order to prevent code duplication, we have created some generic commands. Some of them change the value of any hook send as argument. Some other, getting a hook name, generate the user level commands.

XXII.3.2 Tools to set options

`\settoggle@series` `\settoggle@series{<series>}{<toggle>}{<value>}` is a generic command to switch toggles for some series. The arguments are:

- #1 (mandatory): the series for which the hooks should be set. If empty, all the series will be affected.
- #2 (mandatory): the name of the hook.
- #3 (mandatory): the new value of toggle (true or false).
- #4 (optional): if equal to `reload`, reload the footnote setting (call again `\Xarrangement` or `\arrangementX` or ... depending of the footnote display).
- #5 (optional): if not empty, and if #1 is empty, change the hook setting for pseudo-series, as `appref`.

```

5994 \newcommandx{\settoggle@series}[5][4,5,usedefault]{%
5995   \def\do##1{%
5996     \global\settoggle{#2##1}{#3}%
5997     \ifstreq{#4}{critical}{%
5998       \csuse{Xarrangement@\csuse{series@display##1}}{##1}%
5999     }{}%
6000     \ifstreq{#4}{familiar}{%
6001       \csuse{arrangementX@\csuse{series@displayX##1}}{##1}%
6002     }{}%
6003   }%
6004   \ifstrempty{#1}{%
6005     \dolistloop{\@series}%
6006     \ifstrempty{#5}{%
6007       \doCSVlist{#5}%
6008     }{%
6009     }%
6010     {%
6011       \doCSVlist{#1}%
6012     }%
6013   }%
6014 %

```

`\setcommand@series` `\setcommand@series{<series>}{<command>}{<value>}` is a generic command to store a hook's value into commands specific to some series. The arguments are:

- #1 (mandatory): the series for which the hooks should be set. If empty, all the series will be affected.
- #2 (mandatory): the name of the hook.
- #3 (mandatory): the new value of the hook/command.

- #4 (optional): if equal to `reload`, reload the footnote setting (call `\footnormal` or `\footparagraph` or ... depending of the footnote display).
- #5 (optional): if not empty, and if #1 is empty, change the hook setting for pseudo-series, as `appref`.

```

6015 \newcommandx{\setcommand@series}[5][4,5,usedefault]{%
6016   \def\do##1{%
6017     \csgdef{#2##1}{##3}%
6018     \ifstreq{#4}{critical}{%
6019       \csuse{Xarrangement@}\csuse{series@display##1}{##1}%
6020     }{}%
6021     \ifstreq{#4}{familiar}{%
6022       \csuse{arrangementX@\csuse{series@displayX##1}}{##1}%
6023     }{}%
6024   }%
6025   \ifstrempty{#1}{%
6026     \dolistloop{\@series}%
6027     \ifstrempty{#5}{%
6028       \docslist{#5}%
6029     }{%
6030     }%
6031   }{%
6032     \docslist{#1}%
6033   }%
6034 }%
6035 %

```

XXII.3.3 Tools to generate options commands

`\newhookcommand@series` `\newhookcommand@series\command` names is a generic command to add new commands for hooks, like `\Xhsizetwocol`. The first argument is the name of the hook, the second a comma-separated list of pseudo-series where the hook can be used, like `appref` in the case of `\Xtwolines`. The second argument is also used to create commands named `\<hookname>\<pseudoseries>`, like `\Xtwolinesappref`.

```

6036 \newcommandx{\newhookcommand@series}[2][2,usedefault]{%
6037   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][]{%
6038     \setcommand@series{##1}{##1}{##2}[]##2}%
6039   }%
6040   \ifstrempty{#2}{%
6041     \def\do##1{%
6042       \global\expandafter\newcommand\expandafter*\csname #1##1\endcsname
6043       [1]{%
6044         \csuse{##1}##1####1}%
6045       }%
6046     \docslist{#2}%
6047   }%

```

```
6048 }
6049 %
```

\newhooktoggle@series \newhooktoggle@series\command names is a generic command to add new commands for a new toggle hook, like \Xnumberonlyfirstinline. The second argument is also used to create commands named \<hookname>\<pseudoseries>, like \Xtwolinesbutnotmoreappref.

```
6050 \newcommandx{\newhooktoggle@series}[2][2,usedefault]{%
6051   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={%
6052     \settoggle@series{##1}{#1}{##2}[] [#2]%
6053   }%
6054   \ifstrempty{#2}{}{%
6055     \def\do##1{%
6056       \global\expandafter\newcommand\expandafter*\csname #1##1\endcsname{%
6057         \csuse{##1}##1}%
6058     }%
6059   }%
6060   \do{csvlist}{#2}%
6061 }%
6062 }%
6063 %
```

\hooktoggle@series@reload \newhookcommand@toggle@reload does the same thing as \newhooktoggle@series but the commands created by this macro also reload the series arrangement, depending of type os notes

```
6064 \newcommand{\newhooktoggle@series@reload}[2]{%
6065   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={%
6066     \settoggle@series{##1}{#1}{##2}[#2]%
6067   }%
6068 }%
6069 %
```

\hookcommand@series@reload \newhookcommand@series@reload does the same thing as \newhookcommand@series but the commands created by this macro also reload the series' arrangement.

```
6070 \newcommand{\newhookcommand@series@reload}[2]{%
6071   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][] {%
6072     \setcommand@series{##1}{#1}{##2}[#2]%
6073   }%
6074 }%
6075 %
```

XXII.3.4 Options for critical notes

Before generating the commands that are used to set the critical notes, such as \Xnumberonlyfirstinline, \Xlemmaseparator and the like, we check the nocritical

option.

```

6076 \unless\ifnocritical@
6077   \newhookcommand@series{Xwrapcontent}%
6078   \newhookcommand@series{Xbeforeinserting}%
6079   \newhookcommand@series{Xlemmafont}%
6080   \newhookcommand@series{Xwraplemma}%
6081   \newhooktoggle@series{Xparindent}
6082   \newhookcommand@series{Xhangindent}
6083   \newhookcommand@series{Xragged}
6084   \newhookcommand@series{Xsizetwocol}
6085   \newhookcommand@series{Xsizethreecol}
6086   \newhookcommand@series{Xcolalign}%
6087   \newhookcommand@series{Xnotenumfont}
6088   \newhookcommand@series{Xbhooknote}
6089   \newhookcommand@series@reload{Xbhookgroup}{critical}
6090   \newhookcommand@series{Xboxsymlinenum}%
6091   \newhookcommand@series{Xsymlinenum}
6092   \newhookcommand@series{Xbeforenumber}
6093   \newhookcommand@series{Txtbeforenumber}
6094   \newhookcommand@series{Xafternumber}
6095   \newhookcommand@series{Xbeforesymlinenum}
6096   \newhookcommand@series{Xaftersymlinenum}
6097   \newhookcommand@series{Xinplaceofnumber}
6098   \newhookcommand@series{Xlemmaseparator}
6099   \newhookcommand@series{Xbeforelemmaseparator}
6100   \newhookcommand@series{Xafterlemmaseparator}
6101   \newhookcommand@series{Xinplaceoflemmaseparator}
6102   \newhookcommand@series{Txtbeforennotes}
6103   \newhooktoggle@series{Txtbeforennotesonlyonce}%
6104   \newhookcommand@series@reload{Xafterrule}{critical}
6105   \newhooktoggle@series{Xnumberonlyfirstinline}
6106   \newhooktoggle@series{Xnumberonlyfirstintwo-lines}
6107   \newhooktoggle@series{Xgroupbyline}%
6108   \newhooktoggle@series{Xgroupbylinesparetwo-lines}%
6109   \newhooktoggle@series{Xnonumber}
6110   \newhooktoggle@series{Xpstart}
6111   \newhooktoggle@series{Xpstarteverytime}%

6112
6113   \newhooktoggle@series{Xstanza}%
6114   \newhookcommand@series{Xstanzaseparator}%

6115
6116   \newhooktoggle@series{Xonlypstart}
6117   \newhooktoggle@series{Xnonbreakableafternumber}
6118   \newhooktoggle@series{Xlemmadisablefontselection}
6119   \newhookcommand@series@reload{Xmaxhnotes}{critical}
6120   \newhookcommand@series@reload{Xbeforennotes}{critical}
6121   \newhooktoggle@series@reload{Xnoteswidthliketwo-columns}{critical}%
6122   \newhookcommand@series@reload{Xnotefontsize}{critical}
6123

```

```

6124 \newhookcommand@series{Xboxlinenum}%
6125 \newhookcommand@series{Xboxlinenumalign}%
6126
6127 \newhookcommand@series{Xboxstartlinenum}%
6128 \newhookcommand@series{Xboxendlinenum}%
6129
6130 \newhookcommand@series{Xafternote}%
6131 \newhookcommand@series{Xparafootsep}%
6132 \newhookcommand@series@reload[Xwidth]{critical}%
6133
6134 \ifundef{\Xhsiz}%
6135   \f%
6136     \newcommandx{\Xhsiz}[2][1,usedefault]{%
6137       \led@warning@Xhsiz@deprecated%
6138       \Xwidth[#1]{#2}%
6139     }%
6140   \}%
6141 \}%
6142 \fi
6143 %

```

Now, hooks for critical notes which also apply to crossreferencing and line numbering at the sides of the page.

```

6144 \newhooktoggleg@series{Xlineflag}[appref,SEref]
6145 \newhookcommand@series{Xtwolines}[appref,SEref]
6146 \newhookcommand@series{Xmorethantwolines}[appref,SEref]
6147 \newhookcommand@series{Xsublinesep}[appref,SEref,side]%
6148 \newhookcommand@series{Xpagelinesep}[appref,SEref,side]%
6149 \newhooktoggleg@series{Xtwolinesbutnotmore}[appref,SEref]
6150 \newhooktoggleg@series{Xtwolinesonlyinsamepage}[appref,SEref]
6151 \newhookcommand@series{Xlinerangeseparator}[appref,SEref]
6152 \newhookcommand@series{Xlinenumannotationposition}[side,appref,SEref]%
6153 \newhookcommand@series{Xwraplinenumannotation}[side,ref,appref,SEref]%
6154 \newhooktoggleg@series{Xnoidenticallinenumannotation}[side,ref,appref,SEref]
6155 %

```

XXII.3.5 Options for familiar notes

Before generating the optional commands for familiar notes, we check the `\nofamiliar` option.

```

6156 \unless\ifnofamiliar@
6157   \newhookcommand@series{wrapcontentX}%
6158   \newhookcommand@series{beforeinsertingX}%
6159   \newhooktoggleg@series{parindentX}
6160   \newhookcommand@series{hangindentX}
6161   \newhookcommand@series{raggedX}
6162   \newhookcommand@series{hsizetwocolX}

```

```

6163 \newhookcommand@series{hsizethreecolX}
6164 \newhookcommand@series{colalignX}%
6165 \newhookcommand@series{notenumfontX}
6166 \newhookcommand@series{bhooknoteX}
6167 \newhookcommand@series@reload{bhookgroupX}{familiar}
6168 \newhookcommand@series@reload{beforenotesX}{familiar}
6169 \newhookcommand@series@reload{maxhnotesX}{familiar}
6170 \newhooktoggle@series@reload{noteswidthliketwocolumnsX}{familiar}%
6171 \newhookcommand@series@reload{afterruleX}{familiar}
6172 \newhookcommand@series@reload{notefontsizeX}{familiar}
6173 \newhookcommand@series{afternoteX}
6174 \newhookcommand@series{parafootsepX}
6175 \newhookcommand@series{txtbeforenotesX}%
6176 \newhooktoggle@series{txtbeforenotesonlyonceX}%
6177 \newhookcommand@series@reload{widthX}{familiar}%
6178 \ifundef{\hsizeX}%
6179 {%
6180   \newcommandx{\hsizeX}[2][1,usedefault]{%
6181     \led@warning@hsizeX@deprecated%
6182     \widthX[#1]{#2}%
6183   }%
6184 }%
6185 {}%
6186 \fi
6187 %

```

XXII.3.6 Options for endnotes

Before generating the commands that are used to set the endnotes, such as `\Xnumberonlyfirstinline`, `\Xlemmaseparator+` and the like, we check the `noend` option.

```

6188 \unless\ifnoend@
6189   \newhookcommand@series{Xendwraplemma}
6190   \newhookcommand@series{Xendwrapcontent}
6191   \newhookcommand@series{Xendnotenumfont}
6192   \newhookcommand@series{Xendlemmapfont}%
6193   \newhookcommand@series{Xendbhooknote}

6194
6195   \newhookcommand@series{Xendboxlinenum}%
6196   \newhookcommand@series{Xendboxlinenumalign}%

6197
6198   \newhookcommand@series{Xendboxstartlinenum}%
6199   \newhookcommand@series{Xendboxendlinenum}%

6200
6201   \newhookcommand@series{Xendnotefontsize}
6202   \newhooktoggle@series{Xendlemmadisablefontselection}
6203   \newhookcommand@series{Xendlemmaseparator}
6204   \newhookcommand@series{Xendbeforelemmaseparator}
6205   \newhookcommand@series{Xendafterlemmaseparator}
6206   \newhookcommand@series{Xendinplaceoflemmaseparator}

```

```

6207
6208   \newhookcommand@series{Xendbeforenumber}%
6209   \newhookcommand@series{Xendafternumber}%
6210
6211   \newhooktoggle@series{Xendparagraph}
6212   \newhookcommand@series{Xendafternote}
6213   \newhookcommand@series{Xendsep}
6214
6215   \newhookcommand@series{Xendinplaceofnumber}%
6216   \newhooktoggle@series{Xendnonumber}%
6217
6218   \newhooktoggle@series{Xendnumberonlyfirstinline}%
6219   \newhooktoggle@series{Xendnumberonlyfirstintwolines}%
6220
6221   \newhookcommand@series{Xendsymlinenum}%
6222   \newhookcommand@series{Xendbeforesymlinenum}%
6223   \newhookcommand@series{Xendaftersymlinenum}%
6224   \newhookcommand@series{Xendboxsymlinenum}%
6225
6226   \newhookcommand@series{Xendbhooklinenumber}%
6227   \newhookcommand@series{Xendahooklinenumber}%
6228   \newhookcommand@series{Xendbhookinplaceofnumber}%
6229   \newhookcommand@series{Xendahookinplaceofnumber}%
6230
6231   \newhookcommand@series{Xendhangindent}%
6232
6233   \newhooktoggle@series{Xendpagenumberonlyfirst}%
6234   \newhooktoggle@series{Xendpagenumberonlyfirstifsingle}%
6235   \newhooktoggle@series{Xendpagenumberonlyfirstintwo}%
6236   \newhookcommand@series{Xendsympagenum}%
6237   \newhookcommand@series{Xendinplaceofpagenumber}%
6238
6239   \newhookcommand@series{Xendtxtbeforenotes}%
6240
6241 \fi
6242   \newhooktoggle@series{Xendlineflag} [apprefwithpage,SErefwithpage]
6243   \newhookcommand@series{Xendtwolines} [apprefwithpage,SErefwithpage]
6244   \newhookcommand@series{Xendmorethan twolines} [apprefwithpage,SErefwithpage]
6245   \newhooktoggle@series{Xendtwolinesbutnotmore} [apprefwithpage,SErefwithpage]
6246   \newhooktoggle@series{Xendtwolinesonlyinsamepage} [apprefwithpage,
6247     SErefwithpage]
6248   \newhookcommand@series{Xendlinerangeseparator} [apprefwithpage,SErefwithpage
6249     ]
6250   \newhookcommand@series{Xendbeforepagenumber} [apprefwithpage,SErefwithpage,
6251     SErefonlypage]
6252   \newhookcommand@series{Xendafterpagenumber} [apprefwithpage,SErefwithpage]
6253   \newhookcommand@series{Xendlineprefixsingle} [apprefwithpage,SErefwithpage]
6254   \newhookcommand@series{Xendlineprefixmore} [apprefwithpage,SErefwithpage]
6255   \newhookcommand@series{Xendsublinesep} [apprefwithpage,SErefwithpage]

```

```

6254 \newhookcommand@series{Xendlinenumannotationposition}[apprefwithpage,
6255 Serefwithpage]%
6255 \newhookcommand@series{Xendwraplinenumannotation}[apprefwithpage,
6256 Serefwithpage]%
6256 \newhooktoggle@series{Xendnoidenticallinenumannotation}[apprefwithpage,
6257 Serefwithpage]%
6257 %

```

XXII.4 Hooks for a particular footnote

`\newhooktoggle@specific` `\newhooktoggle@specific` is a generic command to create boolean hook specific to a note.

```

6258 \newcommand{\newhooktoggle@specific}[1]{%
6259   \newtoggle{#1}%
6260   \listgadd{\hooktoggle@specific}{#1}%
6261   \define@key[mac]{truefootnoteoption}{#1}[]{\global\settoggle{#1@}{true}}%
When enabling footnote option
6262   \define@key[mac]{falsefootnoteoption}{#1}[]{\global\settoggle{#1@}{false}}
6263 }
6264 %

```

`\newhookarg@specific` `\newhookarg@specific` is a generic command to create argument hook specific to a note.

```

6265 \newcommand{\newhookarg@specific}[1]{%
6266   \listgadd{\hookarg@specific}{#1}%
6267   \define@key[mac]{truefootnoteoption}{#1}{\csgdef{#1@}{##1}}%
When enabling
footnote option
6268   \define@key[mac]{falsefootnoteoption}{#1}{\global\csundef{#1@}}%
When
disabling footnote option
6269 }
6270 %

```

`\hooktoggle@specific` `\add@hooktoggle@specific@to@cs` The `\add@hooktoggle@specific@to@cs` macro stores to a macro all the current values of hook toggle specific to a command. It is useful for the `\Xgroupbyline` option, which does not immediately add notes to the inserts list. It uses the `\hooktoggle@specific` list.

```

6271 \def\hooktoggle@specific{}%
6272 \newcommand{\add@hooktoggle@specific@to@cs}[1]{%
6273   \def\do##1{%
6274     \iftoggle{##1@}{%
6275       \ifcsdef{##1}{%
6276         \csgappto{##1}{\togglettrue{##1@}}%
6277       }{%
6278         \csgdef{##1}{\togglettrue{##1@}}%
6279       }%

```

```

6280 }{%
6281   \ifcsdef{#1}{%
6282     \csgappto{#1}{\togglefalse{##1@}}%
6283   }{%
6284     \csgdef{#1}{\togglefalse{##1@}}%
6285   }%
6286 }{%
6287 }{%
6288 \dolistloop{\hooktogglegeneric}%
6289 }%
6290 %

```

`\hookarg@specific` The same, but for optional argument of critical footnotes with assigned value.

```

dd@hookarg@specific@to@cs
6291 \def\hookarg@specific{}%
6292 \newcommand{\add@hookarg@specific@to@cs}[1]{%
6293   \def\do##1{%
6294     \ifcsoption{##1@}{}{%
6295       \ifcsdef{#1}{%
6296         \csexpando{#1}{%
6297           \noexpand\csdef%
6298             {##1@}{\csname##1@\endcsname}}%
6299       }{%
6300         \csexpando{#1}{%
6301           \noexpand\csdef%
6302             {##1@}{\csname##1@\endcsname}}%
6303       }%
6304     }%
6305   }%
6306 }{%
6307 }{%
6308 \dolistloop{\hookarg@specific}%
6309 }%
6310 %

```

And now, we define some hooks specific to a note.

```

6311 \newhooktogglegeneric{fulllines}%
6312 \newhooktogglegeneric{nonum}%
6313 \newhooktogglegeneric{nosep}%
6314 \newhooktogglegeneric{noprefix}%
6315 \newhooktogglegeneric{prefixmore}%
6316 \newhookarg@specific{linerangesep}%
6317 %

```

`linerangesep@` `\linerangesep@` is defined by the option `linerangesep` of critical notes to change temporarily the line range separator for a specific line. As we have to define it before typesetting the line and undefine it after, we use the family of `xkeyval` package's key.

```

6318 %

```

\nomk@ \nomk@ toggle is used by `reledpar` to remove the footnote mark in the text when using `\footnoteXmk`. Read `reledpar` handbook.

```
6319 \newtoggle{nomk@}%
6320 %
```

XXII.5 Alias

\Xnolemmaseparator \Xnolemmaseparator[⟨series⟩] is just an alias for \Xlemmaseparator[⟨series⟩]{}

```
6321 \newcommandx*{\Xnolemmaseparator}[1][1]{\Xlemmaseparator[#1]{}}
6322 %
```

XXIII Output routine

Now we begin the output routine and associated things.

XXIII.1 Extra footnotes output

With luck we might only have to change \makecol and \reinserts of L^AT_EX's kernel. Since `reledmac`, we use `etoolbox`'s patching commands instead of overriding. It should provides better compatibility with other package which modify these commands

\l@ddoxtrafeet \l@ddoxtrafeet is the code extending \makecol to cater for the extra `reledmac` feet. We have two categories of extra footnotes. By default, we order the footnote inserts so that the regular footnotes of L^AT_EX are first, then familiar familiar footnotes and finally the critical footnotes.

```
6323 \newcommand*{\l@ddoxtrafeet}{%
6324   \IfStrEq{familiar-critical}{\fnpos}%
6325     {\do@feetX\do@Xfeet}%
6326     {%
6327       \IfStrEq{critical-familiar}{\fnpos}%
6328         {\do@Xfeet\do@feetX}%
6329         {%
6330           \setbox\outputbox \vbox{%
6331             \unvbox\outputbox%
6332               \do@feet@custom@order{}{\fnpos}%
6333             }%
6334           }%
6335         }%
6336     }%
6337   }%
6338 %
```

\do@feet@custom@order \do@feet@custom@order is called when \fnpos is neither 'familiar-critical', nor 'critical-familiar', that is, when the order is more complex. In this case, people must define the order for all footnote series. If they don't, L^AT_EX could perform an infinite run.

```

6339 \newcommand{\do@feet@custom@order}[2]{%
640     \def\do##1{%
641         \edef\@@notesseries{\@firstoftwo##1}%
642         \edef\@@notetype{\@secondoftwo##1}%
643         \ifdefstring{\@@notetype}{critical}%
644             {\csuse{\#1append@Xnotes}{\@@notesseries}}%
645             {\ifdefstring{\@@notetype}{familiar}%
646                 {\csuse{\#1append@notesX}{\@@notesseries}}%
647                 {}%}
648             }%
649     }%
650     \expandafter\docslist\expandafter{#2}%
651 }%
652 %

```

\do@feet \do@feet is the code extending \makecol to cater to the extra critical feet.

```

6353 \newcommand*{\do@feet}{%
6354     \setbox\@outputbox \vbox{%
6355         \unvbox\@outputbox
6356         \op@feet}%
6357 %

```

\op@feet The extra critical feet to be added to the output. . . A macro which appends critical notes to the output's routine, also adding vertical space before notes

```

\append@Xnotes
6358 \newcommand{\append@Xnotes}[1]{%
6359     \ifvoid\csuse{\#1footins}\else%
6360         \global\skip\csuse{\#1footins}=\csuse{Xbeforenotes@#1}%
6361         \global\advance\skip\csuse{\#1footins} by\csuse{Xafterrule@#1}%
6362         \print@Xnotes{#1}%
6363     \fi%
6364 }%
6365 %

```

The normal way to add one series, \print@Xnotes, is replaced by `reledpar` when using \Pages.

```

6366 \newcommand\print@Xnotes[1]{%
6367     \xdef\@currentseries{\#1}%
6368     \csuse{\#1footstart}{\#1}%
6369     \csuse{\#1footgroup}{\#1}%
6370 }%
6371 %

```

We print all series of notes by looping on them. We check before printing them that they are not voided.

```

6372 \newcommand*{\op@feet}{%
6373     \unless\ifnocritical%
6374         \gdef\firstXseries{}%

```

```

6375   \def\do##1{%
6376     \append@Xnotes{##1}%
6377     }%
6378   \dolistloop{\@series}%
6379   \fi%
6380 }%
6381 %

```

\l@ddodoreinxtrafeet **\l@ddodoreinxtrafeet** is the code catering for the extra footnotes within **\@reinserts**. We use the same category and ordering as in **\l@ddoxtrafeet**.

```

6382 \newcommand*{\l@ddodoreinxtrafeet}{%
6383   \IfStrEq{familiar-critical}{\@fnpos}%
6384     {\@doreinfeetX\X@doreinfeet}%
6385     {%
6386       \IfStrEq{critical-familiar}{\@fnpos}%
6387         {\X@doreinfeet\@doreinfeetX}%
6388         {\@doreinfeetX\X@doreinfeet}%
6389     }%
6390 }
6391 %
6392 %

```

\X@doreinfeet **\X@doreinfeet** is the code for catering for the extra critical footnotes within **\@reinserts**.

```

6393 \newcommand*{\X@doreinfeet}{%
6394   \unless\ifnocritical@%
6395     \def\do##1{%
6396       \ifvoid\csuse{##1footins}\else%
6397         \insert\csuse{##1footins}{\unvbox\csuse{##1footins}}%
6398       \fi}%
6399     \dolistloop{\@series}%
6400     \fi%
6401 }
6402 %
6403 %

```

\print@notesX We have to add all the new kinds of familiar footnotes to the output routine. A macro
\append@notesX which appends the familiar footnotes of one series onto the output routine, also adding vertical skip before notes.

```

6404 \newcommand{\append@notesX}[1]{%
6405   \ifvoid\csuse{footins#1}\else%
6406     \global\skip\csuse{footins#1}=\csuse{beforenotesX@#1}%
6407     \global\advance\skip\csuse{footins#1} by\csuse{afterruleX@#1}%
6408     \print@notesX{#1}%
6409   \fi%
6410 }%
6411 %

```

The normal way to print one series of notes. `\print@Xnotes` is replaced by `reledpar` when using `\Pages`.

```

6412 \newcommand{\print@notesX}[1]{%
6413   \xdef\@currentseries{#1}%
6414   \csuse{footstart#1}{#1}%
6415   \csuse{footgroup#1}{#1}%
6416 }%
6417 %

```

We print all the series of notes by looping over them. We check before printing them that they are not voided.

```

6418 \newcommand*{\do@feetX}{%
6419   \unless\ifnofamiliar@%
6420     \gdef\firstseriesX{}%
6421     \setbox\@outputbox \vbox{%
6422       \unvbox\@outputbox%
6423       \def\do##1{%
6424         \append@notesX{##1}%
6425       }%
6426       \dolistloop{\@series}%
6427     \fi%
6428   }%
6429 %
6430 \newcommand{\@doreinfeetX}{%
6431   \unless\ifnofamiliar@%
6432     \def\do##1{%
6433       \ifvoid\csuse{footins##1}\else
6434         \insert%
6435           \csuse{footins##1}%
6436           {\unvbox\csuse{footins##1}}%
6437       \fi%
6438     }%
6439     \dolistloop{\@series}%
6440   \fi%
6441 }%
6442 %
6443 %

```

XXIII.2 Patching standard output's commands

The `memoir` class does not use the ‘standard’ versions of `\@makecol` and `\@reinserts`, due to its sidebar insert. We had better add that code if `memoir` is used. (It can be awkward dealing with `\if` code within `\if` code, so don’t use `\ifl@dmemoir` here.)

```

6444 \@ifclassloaded{memoir}{%
6445 %

```

`memoir` is loaded so we use `memoir`'s built in hooks.

```

6446   \g@addto@macro{\m@mddoextrafeet}{\l@ddoxtrafeet}%
6447   \g@addto@macro{\m@mdodoreinextrafeet}{\l@ddodoreinxtrafeet}%
6448 }{%
6449 %

```

`memoir` has not been loaded, so patch `\@makecol` and `\@reinserts`. If the `fancyhdr` package < version 3.8 has been loaded, we patch the `\@makecol` command, because this package redefines the standard `\@makecol` in the preamble to call `\@makecol`, which has been `\let` to `\@makecol`. If this package is not loaded, we directly patch `\@makecol`. If the `fancyhdr` package \geq version 3.8, we also directly patch `\@makecol`, because `fancyhdr` does its own patch `\AtBeginDocument`.

```

6450 \ifboolexpr{%
6451   test{\@ifpackageloaded{fancyhdr}}%
6452   and test {\ifdef{\@makecol}}%
6453 }{%
6454   \patchcmd{%
6455     {\@makecol}%
6456     {\xdef\@freelist{\@freelist\@midlist}}%
6457     {\xdef\@freelist{\@freelist\@midlist}\l@ddoxtrafeet}%
6458     {}%
6459     {\@error@fail@patch{\@makecol}}%
6460   }{%
6461     \patchcmd{%
6462       {\@makecol}%
6463       {\xdef\@freelist{\@freelist\@midlist}}%
6464       {\xdef\@freelist{\@freelist\@midlist}\l@ddoxtrafeet}%
6465       {}%
6466       {\@error@fail@patch{\@makecol}}%
6467     }{%
6468       \patchcmd{%
6469         {\@reinserts}%
6470         {\@ifvbox}%
6471         {\l@ddodoreinxtrafeet\@ifvbox}%
6472         {}%
6473         {\@error@fail@patch{\@reinserts}}%
6474       }{%
6475     }%
6476   }%
6477 }

```

It turns out that `\@doclearpage` also needs modifying.

`\if@led@nofoot` We have to check if there are any leftover feet.

```

6478 \newif\if@led@nofoot
6479 %
6480 %

```

```

6481 \@ifclassloaded{memoir}{%
6482 %

```

If the `memoir` class is loaded, we hook into its modified `\@doclearpage`.

```
\@mem@extranofeet83 \g@addto@macro{\@mem@extranofeet}{%
 6484   \def\do#1{%
 6485     \unless\ifnocritical%
 6486       \ifvoid\csuse{\#1footins}\else\@mem@nofootfalse\fi%
 6487       \fi%
 6488       \unless\ifnofamiliar%
 6489         \ifvoid\csuse{footins#1}\else\@mem@nofootfalse\fi%
 6490         \fi%
 6491       }
 6492   \dolistloop{\@series}%
 6493 }%
 6494 }{%
 6495 }
```

As `memoir` is not loaded we have patch `\@doclearpage`.

```
\@led@testifnofoot96 \newcommand*{\@led@testifnofoot}{%
 6498   \@led@nofoottrue%
 6499   \ifvoid\footins\else%
 6500     \@led@nofootfalse%
 6501   \fi%
 6502   \def\do##1{%
 6503     \unless\ifnocritical%
 6504       \ifvoid\csuse{\##1footins}\else%
 6505         \@led@nofootfalse%
 6506       \fi%
 6507       \unless\ifnofamiliar%
 6508         \ifvoid\csuse{footins##1}\else%
 6509           \@led@nofootfalse%
 6510         \fi%
 6511       \fi%
 6512     }%
 6513   \dolistloop{\@series}%
 6514 }%
 6515 \pretocmd%
 6516 { \@doclearpage }%
 6517 { \@led@testifnofoot }%
 6518 { }%
 6519 { }%
 6520 { \led@error@fail@patch@\@doclearpage }%
 6521 \patchcmd%
 6522 { \@doclearpage }%
 6523 { \ifvoid\footins }%
 6524 { \if@led@nofoot }%
 6525 { }%
```

```

6527 {\led@error@fail@patch@@doclearpage}%
6528 }
6529 }
6530 %
6531 %

```

XXIV Page numbering in parallel typesetting

The `reledpar` package has two options which change the way page numbering works. We need to implement these options on `reledmac` and not on `reledpar` because they have some consequences for the `reledmac` auxiliary files (numbered file; see V.12 p. 128). The `sameparallelpagenumber` option allows the same page number on both left and right side. The `prevpgnotnumbered` option allows an empty (not numbered) right-side page before `\Pages`.

We cannot implement these two options by changing the value of the page counter, since its value is used by many L^AT_EX features to determine whether a page is left (even numbered) or right (odd numbered). Consequently, we have to do it by patching `\thepage`, in order to use the value of the `par@page` counter instead of the value of the page counter.

This counter will be increased in a patched version of L^AT_EX's `\@outputpage` macro, as is the page counter in this macro. However, this increase will take account of the options.

<code>\par@patch@thepage</code> <code>\par@patch@pagenumbering</code>	<code>\par@patch@thepage</code> patches <code>\thepage</code> in order to use the value of <code>par@page</code> counter and not the value of <code>page</code> . It must be called after any redefinition of <code>\thepage</code> . That is why we insert it at the end of the L ^A T _E X macro <code>\pagenumbering</code> , which is called by some <code>\xxxmatter</code> commands. In cases when we are using the <code>memoir</code> class, we insert it at the end of <code>\@memnum</code> . When using <code>\pagenumbering</code> , we also need to reset the <code>par@page</code> counter. Consequently, we put <code>\par@patch@thepage</code> and counter reset in <code>\par@patch@pagenumbering</code> . We also call <code>\par@patch@thepage</code> at the beginning of the document.
--	--

```

6532
6533 \newcommand{\par@patch@thepage}{%
6534   \ifboolexpr{%
6535     bool{sameparallelpagenumber}%
6536     or bool{prevpgnotnumbered}%
6537   }{%
6538     \patchcmd{\thepage}{%
6539       {page}{par@page}%
6540       {}{%
6541         {\led@error@fail@patch@thepage}%
6542       }{%
6543     }{%
6544   }{%
6545 \newcommand{\par@patch@pagenumbering}{%

```

```

6547     \setcounter{par@page}{1}%
6548     \par@patch@thepage%
6549 }%
6550
6551 \ifl@dmemoir%
6552     \apptocmd{\@memnum}{%
6553         {\par@patch@pagenumbering}%
6554     }%
6555     {\led@error@fail@patch@memnum}%
6556
6557 \else%
6558     \apptocmd{\pagenumbering}{%
6559         {\par@patch@pagenumbering}%
6560     }%
6561     {\led@error@fail@patch@pagenumbering}%
6562 \fi%
6563
6564 \AtBeginDocument{\par@patch@thepage}%
6565 %

```

\@outputpage As its name says, `\@outputpage` is a L^AT_EX macro called in the output routine. It is this macro which increases the page counter. We patch it in order to increase, conditionally, the `par@page` counter.

```

6566 \AtBeginDocument{%
6567     \apptocmd{\@outputpage}{%
6568         \ifsameparallelpagenumber{%
6569             \ifl@dprintingpages{%
6570                 \ifodd\c@page\else{%
6571                     \stepcounter{par@page}%
6572                 }\fi%
6573             }\else{%
6574                 \stepcounter{par@page}%
6575             }\fi%
6576         }\else{%
6577             \stepcounter{par@page}%
6578         }\fi%
6579     }%
6580     {\led@error@fail@patch@outputpage}%
6581 }%
6582 %
6583 %

```

\thepar@page The `par@page` counter.

```

6584 \newcounter{par@page}%
6585 \setcounter{par@page}{1}%
6586 %

```

XXV Cross referencing

You can mark a place in the text using a command of the form `\edlabel{<foo>}`, and later refer to it using the label `<foo>` by typing `\edpageref{<foo>}`, or `\lineref{<foo>}` or `\sublineref{<foo>}` or `\pstartref`. These reference commands will produce, respectively, the page, line sub-line and pstart on which the `\edlabel{<foo>}` command occurred.

The reference macros warn you if a reference is made to an undefined label. If `{<foo>}` has been used as a label before, the `\edlabel{<foo>}` command will issue a complaint; subsequent `\edpageref` and `\edlineref` commands will refer to the latest occurrence of `\edlabel{<foo>}`.

`\labelref@list` Set up a new list, `\labelref@list`, to hold the page, line and sub-line numbers for each label.

```
6587 \list@create{\labelref@list}
6588 %
```

`\zz@000` Two convenience macros to zero three / four labeling counters in one go.

```
\zz@0000
6589 \newcommand*{\zz@000}{000|000|000}%
6590 \newcommand*{\zz@0000}{000|000|000|000}%
6591 %
6592 %
```

`\edlabel` The `\edlabel` command first writes a `\@lab` macro to the `\linenum@out` file. It then checks to see that the `\labelref@list` actually has something in it (if not, it creates a dummy entry), and pops the next value for the current label, storing it in `\label@refs`. Finally it defines the label to be `\empty` so that any future check will turn up the fact that it has been used.³⁶

This version of the original edmac `\label` uses `\@bsphack` and `\@esphack` to eliminate extra space problems and also use the L^AT_EX write methods for the `.aux` file.

Jesse Billett³⁷ found that the original code could be off by several pages. This version, hopefully cures that, and also allows for non-arabic page numbering.

```
6593 \newcommand*{\edlabel}[1]{%
6594   \leavevmode%
6595   \@bsphack%
6596   \ifboolexpr{bool{ledRcol} \or bool{ledRcol@}}{%
6597     \ifXnote@%
6598       \protected@write\@auxout{}{%
6599         {\string\l@dmake@labelsR\space\the\page|\l@dparsedstartline|\
6600           \l@dparsedstartsub||\annot@start|\the\c@pstartR|\#1}}%
6601       \ifdef{\hypertarget}{%
6602         \Hy@raisedlink{\hypertarget{\#1}{}}%
6603       }%
6604     }%
6605   }%
```

³⁶The remaining macros in this section were kindly revised by Wayne Sullivan, who substantially improved their efficiency and flexibility.

³⁷(jdb43@cam.ac.uk) via the ctt thread ‘ledmac cross referencing’, 25 August 2003.

```

6603 \else%
6604   \write\linenum@outR{\string\@lab}%
6605   \ifx\labelref@listR\empty%
6606     \xdef\label@refs{\zz@000}%
6607   \else%
6608     \gl@p\labelref@listR\to\label@refs%
6609   \fi%
6610   \ifvmode%
6611     \advancelabel@refs%
6612   \fi%
6613 %

```

Use code from the kernel \label command to write the correct page number. Also define an hypertarget if hyperref package is loaded.

```

6614   \protected@write\@auxout{}%
6615     {\string\l@dmake@labelsR\space\thepage|\label@refs|\the\c@pstartR
6616     |{\#1}}%
6617     \ifdef{\hypertarget}%
6618       {\Hy@raisedlink{\hypertarget{\#1}{}}}%
6619       {}%
6620     \fi%
6621   }{%
6622     \ifXnote@%
6623       \ifl@dpairing%pstart or pstartL?
6624         \protected@write\@auxout{}%
6625           {\string\l@dmake@labels\space\thepage|\l@dparsedstartline|\
6626           l@dparsedstartsub||\annot@start|\the\c@pstartL|{\#1}}%
6627           \ifdef{\hypertarget}%
6628             {\Hy@raisedlink{\hypertarget{\#1}{}}}%
6629             {}%
6630           \else%
6631             \protected@write\@auxout{}%
6632               {\string\l@dmake@labels\space\thepage|\l@dparsedstartline|\
6633               l@dparsedstartsub||\annot@start|\the\c@pstart|{\#1}}%
6634               \ifdef{\hypertarget}%
6635                 {\Hy@raisedlink{\hypertarget{\#1}{}}}%
6636                 {}%
6637               \fi%
6638             \else%
6639               \write\linenum@out{\string\@lab}%
6640               \ifx\labelref@list\empty%
6641                 \xdef\label@refs{\zz@000}%
6642               \else%
6643                 \gl@p\labelref@list\to\label@refs%
6644               \fi%
6645               \ifvmode%
6646                 \advancelabel@refs%
6647               \fi%
6648             \ifl@dpairing%Pstart or PstartL?
6649               \protected@write\@auxout{}%

```

```

6647      {\string\l@dmake@labels\space\thepage|\label@refs|\the\c@pstartL
|{#1}}%
6648      \ifdef{\hypertarget}%
6649          {\Hy@raisedlink{\hypertarget{#1}{}}}%
6650          {}%
6651      \else%
6652          \protected@write\@auxout{}%
6653          {\string\l@dmake@labels\space\thepage|\label@refs|\the\c@pstart
|{#1}}%
6654          \ifdef{\hypertarget}%
6655              {\Hy@raisedlink{\hypertarget{#1}{}}}%
6656              {}%
6657          \fi%
6658      \fi%
6659  }%
6660  \esphack%
6661 %
6662 %

```

`\advancelabel@refs` In cases where `\edlabel` is the first element in a paragraph, we have a problem with line counts, because line counts change only at the first horizontal box of the paragraph. Hence, we need to test `\edlabel` if it occurs at the start of a paragraph. To do so, we use `\ifvmode`. If the test is true, we must advance by one unit the amount of text we write into the .aux file. We do so with the `\advancelabel@refs` command.

```

6663 \newcounter{line}%
6664 \newcounter{subline}%
6665 \newcounter{absline}%
6666 \newcommand{\advancelabel@refs}{%
6667     \setcounter{line}{\expandafter\labelrefsparseline\label@refs}%
6668     \stepcounter{line}%
6669     \setcounter{absline}{\expandafter\labelrefsparseabsline\label@refs}%
6670     \stepcounter{absline}%
6671     \ifsublines@%
6672         \setcounter{subline}{\expandafter\labelrefsparseline\label@refs}%
6673         \stepcounter{subline}{1}%
6674         \def\label@refs{\theline|\thesubline|\theabsline}%
6675     \else%
6676         \def\label@refs{\theline|0|\theabsline}%
6677     \fi%
6678 }
6679 \def\labelrefsparseline#1|#2|#3{#1}%
6680 \def\labelrefsparseline#1|#2|#3{#2}%
6681 \def\labelrefsparseabsline#1|#2|#3{#3}%
6682 %

```

`\l@dmake@labels` The `\l@dmake@labels` macro gets executed when the labels file is read. For each label it defines a macro, whose name is made up partly from the label you supplied, that

contains the page, line and sub-line numbers. But first it checks to see whether the label has already been used (and complains if it has).

The initial use of `\newcommand` is to catch if `\l@dmake@labels` has been previously defined (by a class or package).

#1 page number, #2 line number, #3 sub-line number, #4 absolute line number, #5 line number annotation, #6 pstart number, #7 label.

```

6683 \newcommand*\l@dmake@labels(){}
6684 \def\l@dmake@labels#1|#2|#3|#4|#5|#6|#7{%
6685   \expandafter\ifx\csname the@label\endcsname\relax%
6686   \else%
6687     \led@warn@DuplicateLabel{\csname\relax}
6688   \fi
6689   \global\providetoggle{label@#7@ledRcol}%
6690   this toggle, which tells us whether a label is linked to the right or left
6691   side
6692   \csgdef{the@label\csname\relax}{#1|#2|#3|#4|#5|#6|\relax}%
6693   \ignorespaces
6694 %

```

\LaTeX reads the aux file at both the beginning and end of the document, so we have to switch off duplicate label checking after the first time the file is read.

```

6695 \AtBeginDocument{%
6696   \def\l@dmake@labels#1|#2|#3|#4|#5|#6|#7{}%
6697 }
6698 %
6699 %

```

\@lab The `\@lab` command, which appears in the `\linenum@out` file, appends the current value of page, line, sub-line, and absolute line to the `\labelref@list`. These values are defined by the earlier `\@page`, `\@nl`, and the `\sub@on` and `\sub@off` commands appearing in the `\linenum@out` file.

\LaTeX uses the page counter for page numbers. However, it appears that this is not the right place to grab the page number. That task is now done in the `\edlabel` macro. This version of `\@lab` appends just the current line and sub-line numbers to `\labelref@list`.

```

6700 \newcommand*\@lab{%
6701   \ifledRcol
6702     \xright@appenditem{\linenumr@p{\line@numR}|%
6703       \xright@appenditem{\linenumr@p{\line@numR}|%
6704         \ifsblines@ \sublinenumr@p{\subline@numR}\else 0\fi|%
6705         \the\absline@numR|%
6706         \current@annot|%
6707       }%
6708     \to\labelref@listR

```

```

6709 \else
6710   \xright@appenditem{%
6711     \linenumr@p{\line@num}|%
6712     \ifsblines@ \sublinenumr@p{\subline@num}\else 0\fi|%
6713     \the\absline@num|%
6714     \current@annot%
6715   }%
6716   \to\labelref@list
6717 \fi}
6718 %

```

\applabel \applabel, if called in \edtext will insert automatically both a starting and an ending label for the current edtext lines.

```

6719 \newcommand*{\applabel}[1]{%
6720   \if@edtext@secondarg@%
6721   %

```

Label should not be already defined.

```

6722 \ifcsundef{\the@label#1}{%
6723   \csdef{\the@label#1}{applabel}%
6724 }%
6725 {%
6726   \led@warn@DuplicateLabel{#1 (applabel)}%
6727 }%
6728 %

```

Parse the \edtext line numbers and annotations.

```

6729 \expandafter\l@dp@rsefootspec\l@d@nums|%
6730 \expandafter\parse@annot\l@current@annot|%
6731 %

```

Use the L^AT_EX standard hack for label.

```

6732 \@bsphack%
6733 %

```

And now, write the data in the auxiliary file.

```

6734 \ifldRcol%
6735   \protected@write\@auxout{}{%
6736     {\string\l@dmake@labelsR\space\l@dparsedstartpage|\%
6737     \l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstartR{#1:#
6738     start}}%
6739   \ifdef{\hypertarget}{%
6740     {\Hy@raisedlink{\hypertarget{#1:start}{}{}}%}
6741   \else%
6742     \protected@write\@auxout{}{%
6743       {\string\l@dmake@labelsR\space\l@dparsedendpage|\l@dparsedendline%
6744       ||\l@dparsedendsub||\annot@end|\the\c@pstartR{#1:end}}%}
6745   \else%

```

```

6743 \ifl@dpairing%pstart or pstartL?
6744   \protected@write\@auxout{()}%
6745     {\string\l@dmake@labels\space\l@dparsedstartpage|\
6746      l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstartL|{\#1:-
6747      start}}%
6748   \ifdef{\hypertarget}{%
6749     {\Hy@raisedlink{\hypertarget{\#1:start}{}{}}{}}%
6750   }%
6751   \protected@write\@auxout{()}%
6752     {\string\l@dmake@labels\space\l@dparsedendpage|\
6753      l@dparsedendline|\l@dparsedendsub||\annot@end|\the\c@pstartL|{\#1:end}}%
6754   \else%
6755     \protected@write\@auxout{()}%
6756       {\string\l@dmake@labels\space\l@dparsedstartpage|\
6757      l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstart|{\#1:start}}%
6758   \ifdef{\hypertarget}{%
6759     {\Hy@raisedlink{\hypertarget{\#1:start}{}{}}{}}%
6760   }%
6761   \protected@write\@auxout{()}%
6762     {\string\l@dmake@labels\space\l@dparsedendpage|\
6763      l@dparsedendline|\l@dparsedendsub||\annot@end|\the\c@pstart|{\#1:end}}%
6764   \fi%
6765   \fi%
6766 %

```

Use the L^AT_EX standard hack for label.

```

6762 \@esphack%
6763 %

```

Warning if \applabel is called outside of \edtext.

```

6764 \else%
6765   \led@warn@AppLabel0utSecondArgEdtext{\#1}%
6766 \fi%
6767 %

```

End of \applabel

```

6768 }%
6769 %

```

\edlabelS \edlabelS and \edlabelE are just used to mark the beginning and the end of a passage.
\edlabelE
\edlabelSE

```

6770 \newcommand{\edlabelS}[1]{%
6771   \edlabel{\#1:start}%
6772 }
6773 \newcommand{\edlabelE}[1]{%
6774   \edlabel{\#1:end}%
6775 }
6776 \newcommand{\edlabelSE}[1]{%

```

```

6777 \edlabelS{#1}%
6778 \edlabelE{#1}%
6779 }
6780 %

```

\wrap@edcrossref *\wrap@edcrossref* is called around all *reledmac* crossref commands, except those which start with x. It adds the hyperlink.

```

6781 \newrobustcmd{\wrap@edcrossref}[2]{%
6782   \ifdef{\hyperlink}{%
6783     {\hyperlink{#1}{#2}}{%
6784       {#2}}{%
6785     }%
6786   }%

```

\edpageref If the specified label exists, *\edpageref* gives its page number.

\xpageref For this reference command, as for the other two, a special version with prefix x is provided for use in places where the command is to be scanned as a number, as in *\linenum*. These special versions have two limitations: they do not print error messages if the reference is unknown, and they can't appear as the first label or reference command in the file; you must ensure that a *\edlabel* or a normal reference command appears first, or these x-commands will always return zeros.

ET_EX already defines a *\pageref*, so changing the name to *\edpageref*.

```

6787 \newcommand*{\edpageref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{1}{#1}}}
6788 \newcommand*{\xpageref}[1]{\l@dgetref@num{1}{#1}}
6789 %
6790 %

```

\edlineref If the specified label exists, *\lineref* gives its line number.

\xlineref

```

6791 \newcommand*{\edlineref}[1]{%
6792   \l@dref@undefined{#1}%
6793   \wrap@edcrossref{#1}{%
6794     \providetoggle{label@#1@ledRcol}% Required for the first run, when the
6795     label has not yet been parsed on the .aux file
6796     \iftoggle{label@#1@ledRcol}{%
6797       {\linenumrepR{\l@dgetref@num{2}{#1}}}{%
6798       {\linenumrep{\l@dgetref@num{2}{#1}}}{%
6799         \xflagref{#1}}{%
6800       }% }%
6801 \newcommand*{\xlineref}[1]{\l@dgetref@num{2}{#1}}%
6802 %
6803 %

```

\sublineref If the specified label exists, *\sublineref* gives its sub-line number.

\xsublineref

```

6804 \newcommand*{\sublineref}[1]{%
6805   \l@dref@undefined{#1}%
6806   \wrap@edcrossref{#1}{%
6807     \providetoggle{label@#1@ledRcol}%Required for the first run, when the
       label has not yet been parsed on the .aux file
6808   \iftoggle{label@#1@ledRcol}{%
6809     {\sublinenumrep{\l@dgetref@num{3}{#1}}}{%
6810     {\sublinenumrep{\l@dgetref@num{3}{#1}}}{%
6811   }%
6812 }%
6813 \newcommand*{\xsublineref}[1]{\l@dgetref@num{3}{#1}}
6814 %
6815 %

```

\xabslineref If the specified label exists, **\xabslineref** gives its absolute line number. This is generally used only by **reledmac** internal macros.

```

6816 \newcommand*{\xabslineref}[1]{\l@dgetref@num{4}{#1}}%
6817 %

```

\annotationref If the specified label exists, **\edannotationref** gives the line number annotation with
\xannotationref which it is associated.

```

6818 \newcommand*{\annotationref}[1]{%
6819   \l@dref@undefined{#1}%
6820   \wrap@edcrossref{#1}{%
6821     \l@wrap@ifemptybox{\Xwraplinenumannotation@ref}{%
6822       \l@dgetref@num{5}{#1}%
6823     }%
6824   }%
6825 }%
6826 \newcommand*{\xannotationref}[1]{%
6827   \l@dgetref@num{5}{#1}%
6828 }%
6829 %

```

\pstarteref If the specified label exists, **\pstartref** gives its pstart number.

```

\xpstartref
6830 \newcommand*{\pstartref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{6}{#1}}}{%
6831 \newcommand*{\xpstartref}[1]{\l@dgetref@num{6}{#1}}%
6832 %
6833 %

```

\xflagref **\xflagref** finds the side flag of any ref defined with **\edlabel**.

```

6834 \newcommand*{\xflagref}[1]{\l@dgetref@num{7}{#1}}%
6835 %

```

The next three macros are used by the referencing commands above, and do the job of extracting the right numbers from the label macro that contains the page, line, and sub-line number.

- \l@eref@undefined** The `\l@eref@undefined` macro is called when you refer to a label with the normal referencing macros. Its argument is a label, and it just checks that the label has been defined.

```

6836 \newcommand*{\l@eref@undefined}[1]{%
6837   \expandafter\ifx\csname the@label#1\endcsname\relax
6838     \l@warn@RefUndefined{#1}%
6839   \fi}
6840 %
6841 %

```

- \l@dgetref@num** Next, `\l@dgetref@num` fetches the number we want. It has two arguments: the first is simply a digit, specifying whether to fetch a page (1), line (2), sub-line (3), (4) pstart number or (5) side flag. (This switching is done by calling `\l@dlabel@parse`.) The second argument is the label-macro, which because of the `\@lab` macro above is defined to be a string of the type 123|456|789.

```

6842 \newcommand*{\l@dgetref@num}[2]{%
6843   \expandafter
6844   \ifx\csname the@label#2\endcsname \relax
6845     000%
6846   \else
6847     \expandafter\expandafter\expandafter
6848     \l@dlabel@parse\csname the@label#2\endcsname|#1%
6849   \fi}
6850 %
6851 %

```

- \l@dlabel@parse** Notice that we slipped another | delimiter into the penultimate line of `\l@dgetref@num`, to keep the ‘switch-number’ separate from the reference numbers. This | is used as another parameter delimiter by `\l@dlabel@parse`, which extracts the appropriate number from its first argument. The |-delimited arguments consist of the expanded label-macro (three reference numbers), followed by the switch-number (1, 2, 3, 4, 5, 6) which defines which of the former seven numbers to extract. (It was given earlier as the first argument of `\l@dgetref@num`.)

```

6852 \newcommand*{\l@dlabel@parse}{}%
6853 \def\l@dlabel@parse#1|#2|#3|#4|#5|#6|#7|#8{%
6854   \ifcase #8%
6855     \or #1%
6856     \or #2%
6857     \or #3%
6858     \or #4%
6859     \or #5%
6860     \or #6%

```

```

6861     \or #7%
6862     \fi}
6863 %

```

\xxref The `\xxref` command takes two arguments, both of which are labels, e.g., `\xxref{mouse}{elephant}`. It first does some checking to make sure that the labels do exist (if one does not, those numbers are set to zero). Then it calls `\linenum` and sets the beginning page, line, and sub-line numbers to those of the place where `\label{mouse}` was placed, and the ending numbers to those at `{elephant}`. The point of this is to be able to manufacture footnote line references to passages which cannot be specified in the normal way as the first argument to `\edtext` for one reason or another. Using `\xxref` in the second argument of `\edtext` lets you set things up at least semi-automatically.

```

6864 \newcommand*{\xxref}[2]{%
6865   {%
6866     \expandafter\ifx\csname the@label#1\endcsname\relax%
6867       \let\@tempa\zz@@@%
6868       \def\@tempc{}%
6869     \else%
6870       \def\@tempa{%
6871         \l@dgetref@num{1}{#1}%
6872         \l@dgetref@num{2}{#1}%
6873         \l@dgetref@num{3}{#1}%
6874       }%
6875       \edef\@tempc{%
6876         \l@dgetref@num{5}{#1}%
6877       }%
6878     \fi%
6879     \expandafter\ifx\csname the@label#2\endcsname\relax%
6880       \let\@tempb\zz@@@%
6881       \def\@tempd{}%
6882     \else%
6883       \def\@tempb{%
6884         \l@dgetref@num{1}{#2}%
6885         \l@dgetref@num{2}{#2}%
6886         \l@dgetref@num{3}{#2}%
6887       }%
6888       \edef\@tempd{%
6889         \l@dgetref@num{5}{#2}%
6890       }%
6891     \fi%
6892     \global\appto{@beforeinsertofthisedtext{%
6893       \def\@this@crossref@start{#1}%
6894     }%
6895     \global\appto{@beforeinsertofthisedtext{%
6896       \def\@this@crossref@end{#2}%
6897     }%
6898     \linenum{\@tempa|\@tempb}%
6899     \edef\@tempc{\@tempc|\@tempd}%

```

```

6900   \expandafter\lineannot\expandafter{\@tempe}%
6901   }%
6902 }%
6903
6904
6905 %

```

\appref \appref, \SEref, \apprefwithpage, \SErefwithpage and \SEonlypage print cross-ref to some start / end lines defined by specific commands. It prints the lines as they should be printed in the apparatus (critical notes for not suffixed versions, endnotes for suffixed versions).

\SErefwithpage Here we define hooks similar to some those related to critical footnotes or endnotes.

So, first declare the default value of the hooks for the pseudo-series. Also declare the internal toggle which are switch by `reledmac`.

```

6906 \def\Xtwolines@appref{}%
6907 \def\Xtwolines@SEref{}%
6908
6909 \def\Xmorethantwolines@appref{}%
6910 \def\Xmorethantwolines@SEref{}%
6911
6912 \def\Xlinerangeseparator@appref{\endashchar}%
6913 \def\Xlinerangeseparator@SEref{\endashchar}%
6914
6915 \def\Xsublinesep@appref{\fullstop}%
6916 \def\Xsublinesep@SEref{\fullstop}%
6917
6918 \def\Xpagelinesep@appref{\fullstop}%
6919 \def\Xpagelinesep@SEref{\fullstop}%
6920
6921
6922 \newtoggle{Xtwolinesbutnotmore@appref}%
6923 \newtoggle{Xtwolinesbutnotmore@SEref}%
6924
6925 \newtoggle{Xtwolinesonlyinsamepage@appref}%
6926
6927 \newtoggle{Xtwolinesonlyinsamepage@SEref}%
6928
6929 \newtoggle{Xlineflag@appref}%
6930 \togglettrue{Xlineflag@appref}%%Here exception
6931 \newtoggle{Xlineflag@SEref}%
6932 \togglettrue{Xlineflag@SEref}%%Here exception
6933
6934 \def\Xlinenumannotationposition@appref{after}%
6935 \def\Xlinenumannotationposition@SEref{after}%
6936
6937 \def\Xwraplinenumannotation@appref{\textsuperscript}%
6938 \def\Xwraplinenumannotation@SEref{\textsuperscript}%
6939 \newtoggle{Xnoidenticallinenumannotation@appref}%

```

```

6940 \newtoggle{Xnoidenticallinenumannotation@SEref}%
6941
6942 \def\Xendtwolines@apprefwithpage{}%
6943 \def\Xendtwolines@SErefwithpage{}%
6944
6945 \def\Xendmorethan twolines@apprefwithpage{}%
6946 \def\Xendmorethan twolines@SErefwithpage{}%
6947
6948 \def\Xendlinerangeseparator@apprefwithpage{\endashchar}%
6949 \def\Xendlinerangeseparator@SErefwithpage{\endashchar}%
6950 \def\Xendlinerangeseparator@SErefonlypage{\endashchar}%
6951
6952 \def\Xendbeforepagenumber@apprefwithpage{p.}%
6953 \def\Xendbeforepagenumber@SErefwithpage{p.}%
6954 \def\Xendbeforepagenumber@SEonlypage{p.}%
6955
6956 \def\Xendafterpagenumber@apprefwithpage{} }%
6957 \def\Xendafterpagenumber@SErefwithpage{} }%
6958
6959
6960 \def\Xendlineprefixsingle@apprefwithpage{}%
6961 \def\Xendlineprefixsingle@SErefwithpage{}%
6962
6963 \def\Xendlineprefixmore@apprefwithpage{}%
6964 \def\Xendlineprefixmore@SErefwithpage{}%
6965
6966 \newtoggle{Xendtwolinesbutnotmore@apprefwithpage}%
6967 \newtoggle{Xendtwolinesbutnotmore@SErefwithpage}%
6968
6969 \def\Xendsublinesep@apprefwithpage{\fullstop}%
6970 \def\Xendsublinesep@SErefwithpage{\fullstop}%
6971
6972 \newtoggle{Xendtwolinesonlyinsamepage@apprefwithpage}%
6973 \newtoggle{Xendtwolinesonlyinsamepage@SErefwithpage}%
6974
6975 \newtoggle{Xendlineflag@apprefwithpage}%
6976 \togglettrue{Xendlineflag@apprefwithpage}%Here, exception
6977 \newtoggle{Xendlineflag@SErefwithpage}%
6978 \togglettrue{Xendlineflag@SErefwithpage}%Here, exception
6979
6980 \def\Xendlinenumannotationposition@apprefwithpage{after}%
6981 \def\Xendlinenumannotationposition@apprefwithpage@SErefwithpage{after}%
6982
6983 \def\Xendwraplinenumannotation@apprefwithpage{\textsuperscript}%
6984 \def\Xendwraplinenumannotation@SErefwithpage{\textsuperscript}%
6985
6986 \newtoggle{Xendnoidenticallinenumannotation@apprefwithpage}%
6987 \newtoggle{Xendnoidenticallinenumannotation@SErefwithpage}%
6988 %

```

Note that some of these hooks are declared but no user command can change their values. Such hooks are not pertinent for `appref` and `apprefwithpage` pseudo-series, but their values are nonetheless tested in some macros.

```

6989 \gdef\Xboxstartlinenum@appref{0pt}
6990 \gdef\Xboxstartlinenum@Seref{0pt}
6991
6992 \gdef\Xboxendlinenum@appref{0pt}
6993 \gdef\Xboxendlinenum@Seref{0pt}
6994
6995 \gdef\Xendboxstartlinenum@apprefwithpage{0pt}
6996 \gdef\Xendboxstartlinenum@Serefwithpage{0pt}
6997
6998 \gdef\Xendboxendlinenum@apprefwithpage{0pt}
6999 \gdef\Xendboxendlinenum@Serefwithpage{0pt}
7000
7001 \newtoggle{Xendpagenumberonlyfirst@apprefwithpage}
7002 \newtoggle{Xendpagenumberonlyfirst@Serefwithpage}
7003
7004 \newtoggle{Xendpagenumberonlyfirstifsingle@apprefwithpage}
7005 \newtoggle{Xendpagenumberonlyfirstifsingle@Serefwithpage}
7006
7007 \newtoggle{Xendpagenumberonlyfirstintwo@apprefwithpage}
7008 \newtoggle{Xendpagenumberonlyfirstintwo@Serefwithpage}
7009
7010 \gdef\Xendsympagenum@apprefwithpage{}
7011 \gdef\Xendsympagenum@Serefwithpage{}
7012
7013 \gdef\Xendinplaceofpagenumber@apprefwithpage{}
7014 \gdef\Xendinplaceofpagenumber@Serefwithpage{}
7015
7016 %
7017 %

```

Now, declare the default values of `\@apprefprefixsingle` and `\@apprefprefixmore`, `\@Serefprefix`, `\@Serefprefixmore` and the commands which defines them.

```

7018 \newcommand{\@apprefprefixsingle}{}
7019 \newcommand{\@Serefprefixsingle}{}
7020
7021 \newcommand{\@apprefprefixmore}{}
7022 \newcommand{\@Serefprefixmore}{}
7023
7024 \newcommand{\setapprefprefixsingle}[1]{%
7025   \gdef\@apprefprefixsingle{#1}%
7026 }
7027 \newcommand{\setSerefprefixsingle}[1]{%
7028   \gdef\@Serefprefixsingle{#1}%
7029 }
7030
7031 \newcommand{\setapprefprefixmore}[1]{%

```

```
7032 \gdef\@apprefprefixmore{\#1}%
7033 }
7034 \newcommand{\setSerefprefixmore}[1]{%
7035 \gdef\@Serefprefixmore{\#1}%
7036 }
7037
7038 %
```

And not \setSErefonlypageprefixsingle and \setSErefonlypageprefixmore.

```
7039 \newcommand{\setSerefonlypageprefixsingle}[1]{%
7040   \gdef\SErefonlypage@prefixsingle{#1}%
7041 }%
7042 \newcommand{\setSerefonlypageprefixmore}[1]{%
7043   \gdef\SErefonlypage@prefixmore{#1}%
7044 }%
7045 %
```

And now, the main commands: \appref, \apprefwithpage, \SEref and \SErefwithpage

These commands call \refformatted@ and \refformattedwithpage, which calls \printlines and \printendlines . That is why we have previously declared all hooks values tested inside these last commands.

```
7046
7047 \newcommandx{\appref}[2][1,usedefault]{\reformatted@{#1}{#2}{appref}}
7048 \newcommandx{\SEref}[2][1,usedefault]{\reformatted@{#1}{#2}{SEref}}
7049
7050 \newcommandx{\apprefwithpage}[2][1,usedefault]{\reformattedwithpage@{#1}{#2}{appref}}
7051 \newcommandx{\SErefwithpage}[2][1,usedefault]{\reformattedwithpage@{#1}{#2}{SEref}}
7052 \newcommandx{\SErefonlypage}[2][1,usedefault]{\reformatdonlypage@{#1}{#2}{SEref}}
7053
7054
7055 \newcommand{\reformatted@}[3]{%
7056   \def\do##1{%
7057     \setkeys[mac]{truefootnoteoption}{##1}%
7058   }%
7059   \notblank{#1}{\docslist{#1}}{}%
7060   \xdef\@currentseries{#3}%
7061   \iftoggle{noprefix@}{}{%
7062     {%
7063       \ifcsempty{@#3prefixmore}{%
7064         {\@apprefprefixsingle}{%
7065           {%
7066             \IfEq{\xlineref{#2:start}}{\xlineref{#2:end}}{%
7067               \iftoggle{prefixmore@}{%
7068                 {\csuse{@#3prefixmore}}{%
7069                   {\csuse{@#3prefixsingle}}{%
7070                     }{%
7071                   }{%
7072                 }{%
7073               }{%
7074             }{%
7075           }{%
7076         }{%
7077       }{%
7078     }{%
7079   }{%
7080 }
```

```

7071   {\csuse{@#3prefixmore}}%
7072   }%
7073 }%
7074 \ifboolexpr{%
7075   test{\ifcsundef{the@label#2:start}}%
7076   or test{\ifcsundef{the@label#2:end}}%
7077 }%
7078 {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}%
7079 }%
7080   \def\@this@crossref@start{#2:start}%
7081   \def\@this@crossref@end{#2:end}%
7082   \xdef\annot@start{\xannotationref{#2:start}}%
7083   \xdef\annot@end{\xannotationref{#2:end}}%
7084   \printlines\xpageref{#2:start}|\xlineref{#2:start}|\xsublineref{#2:
7085 start}|\xpageref{#2:end}|\xlineref{#2:end}|\xsublineref{#2:end}|\relax\
7086 xflagref{#2:start}|%
7087 }%
7088 \def\do##1{%
7089   \setkeys[mac]{falsefootnoteoption}{##1}%
7090 }%
7091 \newcommand{\reformattedwithpage@}[3]{%
7092   \def\do##1{%
7093     \setkeys[mac]{truefootnoteoption}{##1}%
7094   }%
7095   \notblank{#1}{\docslist{#1}}{}%
7096   \xdef\@currentseries{#3withpage}%
7097   \ifboolexpr{%
7098     test{\ifcsundef{the@label#2:start}}%
7099     or test{\ifcsundef{the@label#2:end}}%
7100   }%
7101   {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}%
7102   }%
7103   \def\@this@crossref@start{#2:start}%
7104   \def\@this@crossref@end{#2:end}%
7105   \printendlines\xpageref{#2:start}|\xlineref{#2:start}|\xsublineref{#2:
7106 start}|\xpageref{#2:end}|\xlineref{#2:end}|\xsublineref{#2:end}|\relax\
7107 xflagref{#2:start}|%
7108 }%
7109 \def\do##1{%
7110   \setkeys[mac]{falsefootnoteoption}{##1}%
7111 }%
7112 \notblank{#1}{\docslist{#1}}{}%
7113 \newcommand{\reformattedonlypage@}[3]{%
7114   \def\do##1{%
7115     \setkeys[mac]{truefootnoteoption}{##1}%
7116 }
```

```

7117     }%
7118 \notblank{\#1}{\docslist{\#1}{}{}}%
7119 \xdef\@currentseries{\#3onlypage}%
7120 \ifboolexpr{%
7121   test{\ifcsundef{the@label#2:start}}{}}%
7122   or test{\ifcsundef{the@label#2:end}}{}}%
7123 }%
7124 {\led@warn@pairRefUndefined{\#2}\nfss@text{\reset@font\bfseries ??}}{}}%
7125 {\ifnumequal{\xpageref{\#2:end}}{\xpageref{\#2:start}}}{}}%
7126 {%
7127   \ifcsvvoid{\#3onlypage@prefixsingle}{}}%
7128   {}}%
7129   {\csletcs{\Xendbeforepagenumber@{\#3onlypage}}{\#3onlypage@prefixsingle}}%
7130 }%
7131 \printnpnum{%
7132   \wrap@edcrossref{\#2:start}{\xpageref{\#2:start}}{}}%
7133 {}}%
7134 {%
7135   \ifcsvvoid{\#3onlypage@prefixmore}{}}%
7136   {}}%
7137   {\csletcs{\Xendbeforepagenumber@{\#3onlypage}}{\#3onlypage@prefixmore}}{}}%
7138 \ifdef{\linerangesep}{%
7139   \printnpnum{%
7140     \wrap@edcrossref{\#2:start}{\xpageref{\#2:start}}{}}%
7141     \linerangesep{}}%
7142     \wrap@edcrossref{\#2:end}{\xpageref{\#2:end}}{}}%
7143   {}}%
7144 \else{%
7145   \printnpnum{%
7146     \wrap@edcrossref{\#2:start}{\xpageref{\#2:start}}{}}%
7147     \csuse{\Xendlinerangeseparator@\@currentseries}{}}%
7148     \wrap@edcrossref{\#2:end}{\xpageref{\#2:end}}{}}%
7149   {}}%
7150 \fi{}}%
7151 }%
7152 }%
7153 \def\do##1{%
7154   \setkeys[mac]{falsefootnoteoption}{##1}}%
7155 }%
7156 \notblank{\#1}{\docslist{\#1}{}{}}%
7157 {}}%
7158 %

```

\edmakelabel Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired; you can use the `\edmakelabel` macro make your own label. For example, if you insert `\edmakelabel{elephant}{10|25|0}` you will have created a new label, and a later call to `\edpageref{elephant}` would print ‘10’ and `\lineref{elephant}` would print ‘25’. The sub-line number here is zero. `\edmakelabel` takes a label, fol-

lowed by a page and a line number(s) as arguments. L^AT_EX defines a \makelabel macro which is used in lists. Peter Wilson has changed the name to \edmakelabel.

```
7159 \newcommand*{\edmakelabel}[2]{\expandafter\xdef\csname the@label#1\
7160   endcsname{#2}}
7160 %
7161 %
```

(If you are only going to refer to such a label using \xxref, then you can omit entries in the same way as with \linenum (see VI.3 p. 143 and V.9 p. 107), since \xxref makes a call to \linenum in order to do its work.)

XXV.1 Compatibility with xref

Here, we provide compatibility with the xref to enable reledmac's cross-referencing to external documents. We assume that the user loads xref *before* reledmac, but uses \externaldocument *after* loading reledmac.

\XR@test First, we patch the xr macro \XR@test, which is called on every line of the external .aux file, in order to also call macros specific to reledmac.

```
7162 \preto{\XR@test}{%
7163   {\XR@test@mac###1#2#3#4###}%
7164   {}%
7165   {}%
7166 %}
```

\XR@test@mac The \XR@test@mac takes the full content of a line of the external .aux files, with the three final dots added by xr.

```
7167 \long\def{\XR@test@mac###1###{\XR@test@mac@test#1}%
7168 %}
```

\XR@test@mac@test And finally, \XR@test@mac@test does the job. This code is based on the \XR@test macro of the xr package. However, note that the \XR@prefix is not called here, but it is integrated directly in \l@dmake@labels and \l@dmake@labelsR.

```
7169 \long\def{\XR@test@mac@test#1#2...{%
7170   %The triple dots (NOT \ldots) are because
7171   %of the line 22 of xr.sty v5.02 1994/05/28
7172   \ifx#1\l@dmake@labels%
7173     \l@dmake@labels#2%
7174   \else
7175     \ifx#1\l@dmake@labelsR%
7176       \l@dmake@labelsR #2%
7177     \fi%
7178   \fi%
7179 }%
7180 %}
```

XXVI Sidenotes

Regular \marginpars do not work inside numbered text – they do not produce any note but do put an extra unnumbered blank line into the text.

\@xympar Changing \@xympar a little at least ensures that \marginpars in numbered text do not disturb the flow.

```

7179 \preto{cmd}{\@xympar}%
7180   {\ifnumbered{par}%
7181     \led@warn@NoMarginpars
7182     \esphack
7183   \else}%
7184   {}%
7185   {}%
7186
7187 \appto{cmd}{\@xympar}%
7188   {\fi}%
7189   {}
7190   {}
7191
7192 %

```

We provide sidenotes as replacement for \marginpar in numbered text.

\sidenote@margin These are the sidenote equivalents to \line@margin and \linenummargin for specifying which margin. The default is the right margin (opposite to the default for line numbers). \l@dgtsidenote@margin returns the number associated to sidenote margin:

left: 0

right: 1

outer: 2

inner: 3

```

7193 \newcount\sidenote@margin
7194 \newcommand*\sidenotemargin[1]{{%
7195   \l@dgtsidenote@margin{#1}%
7196   \ifnum\@l@dtmpcntb>\m@ne
7197     \ifledRcol
7198       \global\sidenote@marginR=\@l@dtmpcntb
7199     \else
7200       \global\sidenote@margin=\@l@dtmpcntb
7201     \fi
7202   \fi}%
7203 \newcommand*\l@dgtsidenote@margin[1]{%
7204   \def\@tempa{#1}\def\@tempb{\left}%

```

```

7205   \ifx\@tempa\@tempb
7206     \@l@dtmcntb \z@
7207   \else
7208     \def\@tempb{right}%
7209     \ifx\@tempa\@tempb
7210       \@l@dtmcntb \@ne
7211     \else
7212       \def\@tempb{outer}%
7213       \ifx\@tempa\@tempb
7214         \@l@dtmcntb \tw@
7215       \else
7216         \def\@tempb{inner}%
7217         \ifx\@tempa\@tempb
7218           \@l@dtmcntb \thr@@
7219         \else
7220           \led@warn@BadSidenotemargin
7221           \@l@dtmcntb \m@ne
7222         \fi
7223       \fi
7224     \fi
7225   \fi}
7226 \sidenotemargin{right}
7227 %

```

\l@dlp@rbox We need two boxes to store sidenote texts.

```

\l@drp@rbox
7229 \newbox\l@dlp@rbox
7230 \newbox\l@drp@rbox
7231 %
7232 %

```

\ledlsnotewidth \ledrsnotewidth These specify the width of the left/right boxes (initialised to \marginparwidth), their distance from the text (initialised to \linenumsep), and the fonts used.

```

\ledlsnotesep
7233 \newdimen\ledlsnotewidth \ledlsnotewidth=\marginparwidth
\ledrsnotesep
7234 \newdimen\ledrsnotewidth \ledrsnotewidth=\marginparwidth
\ledlsnotefontsetup
7235 \newdimen\ledlsnotesep \ledlsnotesep=\linenumsep
\ledrsnotefontsetup
7236 \newdimen\ledrsnotesep \ledrsnotesep=\linenumsep
7237 \newcommand*\{\ledlsnotefontsetup}{\raggedleft\footnotesize}
7238 \newcommand*\{\ledrsnotefontsetup}{\raggedright\footnotesize}
7239 %
7240 %

```

\ledleftnote \ledleftnote, \ledrightnote, \ledinernote, \ledouternote are the user commands for left, right, inner and outer sidenotes. The two last one are just alias for the \ledinernote two first one, depending of the page number. \ledsidenote{\text} is the command for a moveable sidenote.

\ledsidenote

```

7241 \newcommand*{\ledleftnote}[1]{\edtext{}{\l@dlsnote{#1}}}
7242 \newcommand*{\ledrightnote}[1]{\edtext{}{\l@drsnote{#1}}}
7243 \newcommand*{\ledsidenote}[1]{\edtext{}{\l@dcsnote{#1}}}%
7244 \newcommand*{\leddinnernote}[1]{\edtext{}{\l@disnote{#1}}}%
7245 \newcommand*{\leddouternote}[1]{\edtext{}{\l@dosnote{#1}}}%
7246 %

```

\l@dlsnote . The ‘footnotes’ for left, right, and moveable sidenotes. The whole scheme is reminiscent
 \l@drsnote of the critical footnotes code.

```

\l@dcsnote
7247 \newif\ifrightnoteup
\l@desnote
7248   \rightnoteuptrue
\l@disnote
7249
7250 \newcommand*{\l@dlsnote}[1]{%
7251   \begingroup%
7252   \newcommand{\content}{#1}%
7253   \ifnumberedpar@
7254     \ifledRcol%
7255       \xright@appenditem{\noexpand\v{l@dlsnote}{\expandonce\content}}%
7256         \to\inserts@listR
7257       \global\advance\insert@countR \z@ne%
7258     \else%
7259       \xright@appenditem{\noexpand\v{l@dlsnote}{\expandonce\content}}%
7260         \to\inserts@list
7261       \global\advance\insert@count \z@ne%
7262     \fi
7263   \fi%
7264   \ignorespaces%
7265   \endgroup%
7266 }%
7267
7268 \newcommand*{\l@drsnote}[1]{%
7269   \begingroup%
7270   \newcommand{\content}{#1}%
7271   \ifnumberedpar@
7272     \ifledRcol%
7273       \xright@appenditem{\noexpand\v{l@drsnote}{\expandonce\content}}%
7274         \to\inserts@listR
7275       \global\advance\insert@countR \z@ne%
7276     \else%
7277       \xright@appenditem{\noexpand\v{l@drsnote}{\expandonce\content}}%
7278         \to\inserts@list
7279       \global\advance\insert@count \z@ne%
7280     \fi
7281   \fi\ignorespaces%
7282   \endgroup%
7283 }%
7284
7285 \newcommand*{\l@dcsnote}[1]{%
7286   \begingroup%

```

```

7287 \newcommand{\content}{\#1}%
7288 \ifnumberedpar@
7289   \ifledRcol%
7290     \xright@appenditem{\noexpand\vl@dcsnote{\expandonce\content}}%
7291       \to\inserts@listR
7292     \global\advance\insert@countR \cne%
7293   \else%
7294     \xright@appenditem{\noexpand\vl@dcsnote{\expandonce\content}}%
7295       \to\inserts@list
7296     \global\advance\insert@count \cne%
7297   \fi
7298 \fi\ignorespaces%
7299 \endgroup%
7300 }%
7301
7302 \newcommand*{\l@disnote}[1]{%
7303   \begingroup%
7304   \newcommand{\content}{\#1}%
7305   \ifnumberedpar@
7306     \ifledRcol%
7307       \xright@appenditem{\noexpand\vl@disnote{\expandonce\content}}%
7308         \to\inserts@listR%
7309       \global\advance\insert@countR \cne%
7310     \else%
7311       \xright@appenditem{\noexpand\vl@disnote{\expandonce\content}}%
7312         \to\inserts@list%
7313       \global\advance\insert@count \cne%
7314     \fi%
7315   \fi\ignorespaces%
7316   \endgroup%
7317 }%
7318
7319 \newcommand*{\l@dosnote}[1]{%
7320   \begingroup%
7321   \newcommand{\content}{\#1}%
7322   \ifnumberedpar@
7323     \ifledRcol%
7324       \xright@appenditem{\noexpand\vl@dosnote{\expandonce\content}}%
7325         \to\inserts@listR%
7326       \global\advance\insert@countR \cne%
7327     \else%
7328       \xright@appenditem{\noexpand\vl@dosnote{\expandonce\content}}%
7329         \to\inserts@list%
7330       \global\advance\insert@count \cne%
7331     \fi%
7332   \fi\ignorespaces%
7333   \endgroup%
7334 }%
7335 %

```

\vl@dlsnote Put the left/right text into boxes, but just save the moveable text. \l@dcsnotetext, \vl@drsnote \l@dcsnotetext@l and \l@dcsnotetext@r are etoolbox's lists which will store the \vl@dcsnote content of sidenotes. We store the content in lists, because we need to loop later on \vl@disnote them, in case many sidenote co-exist for the same line. That is there some special test \vl@dosnote to do, in order to:

- Store the content of \ledsidenote to \l@dcsnotetext in any cases.
- Store the content of \rightsidenote to:
 - \l@dcsnotetext if \ledsidenote is to be put on right.
 - \l@dcsnotetext@r if \ledsidenote is to be put on left.
- Store the content of \leftsidenote to:
 - \l@dcsnotetext if \ledsidenote is to be put on left.
 - \l@dcsnotetext@l if \ledsidenote is to be put on right.

\vl@disnote and \vl@dosnote just call \vl@dlsnote or \vl@drsnote, depending of the page.

```

7337 \newcommand*{\vl@dlsnote}[1]{%
7338   \ifledRcol@%
7339     \l@dtempcntb=\sidenote@marginR%
7340     \ifnum\l@dtempcntb>\@ne%
7341       \advance\l@dtempcntb by\page@numR%
7342     \fi%
7343   \else%
7344     \l@dtempcntb=\sidenote@margin%
7345     \ifnum\l@dtempcntb>\@ne%
7346       \advance\l@dtempcntb by\page@num%
7347     \fi%
7348   \fi%
7349   \ifodd\l@dtempcntb%
7350     \listgadd{\l@dcsnotetext@l}{#1}%
7351   \else%
7352     \listgadd{\l@dcsnotetext}{#1}%
7353   \fi
7354 }
7355 \newcommand*{\vl@drsnote}[1]{%
7356   \ifledRcol@%
7357     \l@dtempcntb=\sidenote@marginR%
7358     \ifnum\l@dtempcntb>\@ne%
7359       \advance\l@dtempcntb by\page@numR%
7360     \fi%
7361   \else%
7362     \l@dtempcntb=\sidenote@margin%
7363     \ifnum\l@dtempcntb>\@ne%
7364       \advance\l@dtempcntb by\page@num%
7365     \fi%

```

```

7366   \fi%
7367   \ifodd\@l@dtempcntb%
7368     \listgadd{\l@dcsnotetext}{#1}%
7369   \else%
7370     \listgadd{\l@dcsnotetext@r}{#1}%
7371   \fi%
7372 }
7373 \newcommand*{\vl@dcsnote}[1]{\listgadd{\l@dcsnotetext}{#1}}
7374
7375 \newcommand{\vl@disnote}[1]{%
7376   \ifledRcol@%
7377     \tempcnta=\page@numR%
7378   \else%
7379     \tempcnta=\page@num%
7380   \fi%
7381   \ifodd\tempcnta% ODD => right page => inner side = left side
7382     \vl@dlsnote{#1}%
7383   \else%
7384     \vl@drsnote{#1}%
7385   \fi%
7386 }%
7387
7388 \newcommand{\vl@dosnote}[1]{%
7389   \ifledRcol@%
7390     \tempcnta=\page@numR%
7391   \else%
7392     \tempcnta=\page@num%
7393   \fi%
7394   \ifodd\tempcnta% ODD => right page => outer side = right side
7395     \vl@drsnote{#1}%
7396   \else%
7397     \vl@dlsnote{#1}%
7398   \fi%
7399 }%
7400
7401 %

```

`\setl@dlp@rbox` `\setl@dlprbox{\langle lednums \rangle}{\langle tag \rangle}{\langle text \rangle}` puts `\langle text \rangle` into the `\l@dlp@rbox` box.
`\setl@drpr@box` And similarly for the right side box. It is these boxes that finally get displayed in the margins.

```

7402 \newcommand*{\setl@dlp@rbox}[1]{%
7403   \begingroup%
7404     \parindent\z@\hspace=\ledlsnotewidth%
7405     \ledlsnotefontsetup%We kept it outside of the vbox, because can affect
    the ragging
      \global\setbox\l@dlp@rbox%
7406     \ifleftnoteup%
7407       =\vbox to\z@{\{\ledlsnotefontsetup\vss #1\}}%We put \
7408     ledlsnotefontsetup inside footnote because required for color command. Note

```

```

the {} to keep setting local.
7409   \else%
7410     =\vbox to 0.70\baselineskip{{\ledrsnotefontsetup\strut#1\vss}}%
7411   \fi%
7412 \endgroup%
7413 }

7414 \newcommand*{\setl@drp@rbox}[1]{%
7415   \begingroup%
7416     \parindent\z@\hsize=\ledrsnotewidth%
7417     \ledrsnotefontsetup%We kept it outside of the vbox, because can affect
the ragging
7418     \global\setbox\l@drp@rbox%
7419     \ifrightnoteup%
7420       =\vbox to\z@{{\ledrsnotefontsetup\vss#1}}%We put \ledrsnotefontsetup
inside footnote because required for color command. Note the {} to keep
setting local.
7421     \else%
7422       =\vbox to0.7\baselineskip{{\ledrsnotefontsetup\strut#1\vss}}%
7423     \fi%
7424   \endgroup%
7425 }%
7426 \newif\ifleftnoteup
7427   \leftnoteuptrue
7428 %
7429 %

```

\@sidenotesep This macro is used to separate sidenotes of the same line.

```

7430 \newcommand{\setsidenotesep}[1]{\gdef\@sidenotesep{#1}}
7431 \newcommand{\@sidenotesep}{, }
7432 %

```

\affixside@note This macro puts any moveable sidenote text into the left or right sidenote box, depending on which margin it is meant to go in. It's a very much stripped down version of **\affixline@num**.

Before do it, we concatenate all moveable sidenotes of the line, using **\@sidenotesep** as separator. It is the result that we put on the sidenote.

```

7433 \newcommand*{\affixside@note}{%
7434   \prepare@edindex@fornote{\the\page@num|\the\line@num|\the\subline@num|\
the\page@num|\the\line@num|\the\subline@num|}%
7435   \def\sidenotecontent@{}%
7436   \numgdef{\itemcount@}{0}%
7437   \def\do##1{%
7438     \ifnumequal{\itemcount@}{0}%
7439       {%
7440         \appto\sidenotecontent@{\#\#1}}% Not print not separator before
the 1st note
7441       {\appto\sidenotecontent@{\@sidenotesep ##1}}%
7442     }%

```

```

7443     \numgdef{\itemcount}{\itemcount+\@ne}%
7444   }%
7445   \dolistloop{\l@dcsnotetext}%
7446   \ifnumgreater{\itemcount}{1}{\led@err@ManySidenotes}{}%
7447 %

```

And we do the same for left and right notes (not movable).

```

7448 \gdef{@temp1@d}{}
7449 \gdef{@temp1@n}{\l@dcsnotetext\l@dcsnotetext\l@dcsnotetext@r}%
7450 \ifx{@temp1@d}{\temp1@n} \else%
7451   \if@twocolumn%
7452     \if@firstcolumn%
7453       \setl@dlp@rbox{##1}{\sidenotecontent}%
7454     \else%
7455       \setl@drp@rbox{\sidenotecontent}%
7456     \fi%
7457   \else%
7458     \l@dtmpcntb=\sidenote@margin%
7459     \ifnum\l@dtmpcntb>\@ne%
7460       \advance\l@dtmpcntb by\page@num%
7461     \fi%
7462     \ifodd\l@dtmpcntb%
7463       \setl@drp@rbox{\sidenotecontent}%
7464     \gdef\sidenotecontent{}%
7465     \numgdef{\itemcount}{0}%
7466     \dolistloop{\l@dcsnotetext@l}%
7467     \ifnumgreater{\itemcount}{1}{\led@err@ManyLeftnotes}{}%
7468     \setl@dlp@rbox{\sidenotecontent}%
7469   \else%
7470     \setl@dlp@rbox{\sidenotecontent}%
7471     \gdef\sidenotecontent{}%
7472     \numgdef{\itemcount}{0}%
7473     \dolistloop{\l@dcsnotetext@r}%
7474     \ifnumgreater{\itemcount}{1}{\led@err@ManyRightnotes}{}%
7475     \setl@drp@rbox{\sidenotecontent}%
7476     \fi%
7477   \fi%
7478 \fi%
7479 \advance\@edindex@fornote@\m@ne%
7480 }
7481 %

```

XXVII Minipages and such

We can put footnotes into minipages. The preparatory code has been set up earlier, all that remains is to ensure that it is available inside a minipage box. This requires some alteration to the kernel code, specifically the `\@iiiminipage` and `\endminipage` macros. We will arrange this so that additional series can be easily added.

\l@dfbeginmini These will be the hooks in \iiminpage and \endminipage.

\l@dfetendmini They can be extended to handle other things if necessary.

```

7482 \ifnoledgroup@\else%
7483 \newcommand*{\l@dfbeginmini}{\@ledgrouptrue\l@dedbeginmini\
7484 \l@dfbeginmini}
7485 \newcommand*{\l@dfetendmini}{%
7486     \IfStrEq{critical-familiar}{\@mpfnpos}%
7487     {\l@dedendmini\l@dfamendmini}%
7488     {%
7489         \IfStrEq{familiar-critical}{\@mpfnpos}%
7490         {\l@dfamendmini\l@dedendmini}%
7491         {\do@feet@custom@order{mp@}{\@mpfnpos}}%
7492     }%
7493 }%
7494 %

```

\l@dedbeginmini These handle the initiation and closure of critical footnotes in a minipage environment.

```

\l@dedendmini
\newcommand*{\l@dedbeginmini}{%
7494 \unless\ifnocritical%
7495     \def\do##1{%
7496         \csletcs{v##1footnote}{mpv##1footnote}%
7497     }%
7498     \dolistloop{\@series}%
7499     \fi%
7500 }
7501 %
7502 \newcommand*{\l@dedendmini}{%
7503 \unless\ifnocritical%
7504     \ifl@dpairing%
7505         \ifledRcol%
7506             \flush@notesR%
7507         \else%
7508             \flush@notes%
7509         \fi%
7510     \fi
7511     \def\do##1{%
7512         \mp@append@Xnotes{##1}%
7513     }%
7514     \dolistloop{\@series}%
7515     \fi%
7516 }%
7517 \newcommand{\mp@append@Xnotes}[1]{%
7518 \ifvoid\csuse{mp#1footins}\else%
7519     \ifl@dpairing%
7520         \ifparledgroup%
7521             \ifledRcol%
7522                 \dimgdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+\skip
7523 @nameuse{mp#1footins}}%
7524             \else%

```

```

7524     \dimgdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+\
7525     skip\@nameuse{mp#1footins}}%
7526     \fi%
7527     \fi%
7528     \ifcsstring{series@display#1}{paragraph}{}{%
7529         \setbox\@nameuse{mp#1footins}=\vbox{%
7530             \csuse{Xnotefontsize@#1}%
7531             \ifcsdef{Xhsize}\csuse{series@display#1}@#1}{%
7532                 \hsize\csuse{Xhsize}\csuse{series@display#1}#1}%
7533             }{}%
7534             \noindent\csuse{Txtbeforenotes@#1}%
7535             \unvbox\@nameuse{mp#1footins}%
7536             \parboxrestore%
7537         }%
7538     }%
7539     \csuse{mp#1footgroup}##1}%
7540     \fi%
7541 }%
7542 %

```

\l@dfambeginmini These handle the initiation and closure of familiar footnotes in a minipage environment.

\l@dfamendmini

\mp@append@notesX

```

7543 \newcommand*\l@dfambeginmini}{%
7544 \unless\ifnofamiliar@%
7545     \def\do##1{\csletcs{vfootnote##1}{mpvfootnote##1}}%
7546     \dolistloop{\@series}%
7547     \fi%
7548 }%
7549
7550 \newcommand*\l@dfamendmini}{%
7551 \unless\ifnofamiliar@%
7552     \def\do##1{%
7553         \mp@append@notesX##1}%
7554     }%
7555     \dolistloop{\@series}%
7556     \fi%
7557 }%
7558 \newcommand{\mp@append@notesX}[1]{%
7559     \ifvoid\csuse{mpfootins#1}\else{%
7560         \ifcsstring{series@displayX#1}{paragraph}{}{%
7561             \setbox\@nameuse{mpfootins#1}=\vbox{%
7562                 \csuse{notefontsizeX@#1}%
7563                 \ifcsdef{hsize}\csuse{series@display#1}X@#1}{%
7564                     \hsize\csuse{hsize}\csuse{series@display#1}X#1}%
7565                 }{}%
7566                 \noindent\csuse{txtbeforenotesX@#1}%
7567                 \unvbox\@nameuse{mpfootins#1}%
7568                 \parboxrestore%
7569             }%

```

```

7570      }%
7571      \csuse{mpfootgroup#1}{#1}%
7572      \fi%
7573  }%
7574 %

```

\@iiiminipage This is our extended form of the kernel \@iiiminipage defined in `ltboxes.dtx`.

```

7575 \patchcmd{%
7576   {\@iiiminipage}%
7577   {\let\@footnotetext\@mpfootnotetext}%
7578   {\let\@footnotetext\@mpfootnotetext\l@dfreetbeginmini}%
7579   {}%
7580   {\@led@error@fail@patch@\@iiiminipage}%
7581 }%

```

\endminipage This is our extended form of the kernel \endminipage defined in `ltboxes.dtx`.

```

7582 \patchcmd{%
7583   {\endminipage}%
7584   {\footnoterule}%
7585   {\footnoterule\l@advance@parledgroup@beforenormalnotes}%
7586   {}%
7587   {\@led@error@fail@patch@\endminipage}%
7588 }%
7589 \patchcmd{%
7590   {\endminipage}%
7591   {\@minipagetrue}%
7592   {\l@dfreetendmini\@minipagetrue}%
7593   {}%
7594   {\@led@error@fail@patch@\endminipage}%
7595 }%
7596 %

```

\l@dunboxmpfoot @\l@dunboxmpfoot insert normal footnotes for ledgroup.

```

edgroup@beforenormalnotes
7597 \newcommand*{\l@dunboxmpfoot}{%
7598   \vskip\skip\@mpfootins
7599   \normalcolor
7600   \footnoterule
7601   \l@advance@parledgroup@beforenormalnotes
7602   \unvbox\@mpfootins%
7603 }
7604 %

```

When using parallel ledgroup, we need to store the vertical space added before footnote, in order to compensate them between left and right pages.

```

7605 \newcommand{\l@advance@parledgroup@beforenormalnotes}{%
7606   \ifparledgroup
7607     \ifl@dpairing

```

```

7608     \ifledRcol
7609         \dimdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+\
7610             skip\@mpfootins}
7611         \else
7612             \dimdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+\
7613                 skip\@mpfootins}
7614             \fi
7615         \fi
7616     }
7617 %

```

`ledgroup` This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, fixed width minipage.

```

7617 \newenvironment{ledgroup}{%
7618     \resetprevpage@num%
7619     \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
7620     \let\@footnotetext\@mpfootnotetext
7621     \l@dfreetbeginmini%
7622 }{%
7623     \par
7624     \unskip
7625     \ifvoid\@mpfootins\else
7626         \l@unboxmpfoot
7627         \fi
7628     \l@dfreetendmini%
7629     \c@ledgroupfalse%
7630 }
7631
7632
7633
7634 %

```

`ledgroupsized` `\begin{ledgroupsized}[\langle pos \rangle]{\width}`

This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, variable `\width` minipage. The optional `\langle pos \rangle` controls the sideways position of numbered text.

```

7635 \newenvironment{ledgroupsized}[2][1]{%
7636 %

```

Set the various text measures.

```

7637     \hsize #2\relax
7638 %

```

Initialize fills for centering.

```

7639     \let\ledllfill\hfil
7640     \let\ledrlfill\hfil

```

```

7641     \def\@tempa{\#1}\def\@tempb{1}%
7642 %

```

Left adjusted numbered lines

```

7643     \ifx\@tempa\@tempb
7644         \let\ledllfill\relax
7645     \else
7646         \def\@tempb{r}%
7647         \ifx\@tempa\@tempb
7648 %

```

Right adjusted numbered lines

```

7649     \let\ledrlfill\relax
7650     \fi
7651     \fi
7652 %

```

Set up the footnoting.

```

7653     \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
7654     \let\@footnotetext\@mpfootnotetext
7655     \l@dfetbeginmini%
7656 }{%
7657     \par
7658     \unskip
7659     \ifvoid\@mpfootins\else
7660         \l@unboxmpfoot
7661     \fi
7662     \l@dfetendmini%
7663 }
7664 %
7665 %

```

Close the \ifnoledgroup@ \else.

```

7666 \fi%
7667 %

```

\ifledgroupnotesL@ These boolean tests check if we are in the notes of a ledgroup. If we are, we do not
\ifledgroupnotesR@ number the lines. It could be useful for parallel ledgroup of `reledpar`.

```

7668 \newif\ifledgroupnotesL@
7669 \newif\ifledgroupnotesR@
7670 %

```

XXVIII Indexing

Here is some code for indexing using page and line numbers.

XXVIII.1 Looking on package order

First, ensure that `imakeidx` or `indextools` is loaded *before* `eledmac`.

```

7671 \AtBeginDocument{%
7672   \unless\ifl@imakeidx%
7673     \c@ifpackageloaded{imakeidx}{\led@error@PackageAfterEledmac{imakeidx}}{}%
7674   \fi%
7675   \unless\ifl@indextools%
7676     \c@ifpackageloaded{indextools}{\led@error@PackageAfterEledmac{indextools}}{}%
7677   \fi%
7678   \unless\ifl@footmisc%
7679     \c@ifpackageloaded{footmisc}{\led@error@PackageAfterEledmac{footmisc}}{}%
7680   \fi%
7681 }
7682 %

```

XXVIII.2 Auxiliary macros for \edindex

`\pagelinesep` In order to get a correct line number we have to use the label/ref mechanism. These
`\edindexlab` macros are for that.

```

\c@labidx
7683 \newcommand{\pagelinesep}{-}
7684 \newcommand{\edindexlab}{$&}
7685 \newcounter{labidx}
7686 \setcounter{labidx}{0}
7687 %
7688 %

```

`\doedindexlabel` This macro sets an `\edlabel`.

```

7689 \newcommand{\doedindexlabel}{%
7690   \stepcounter{labidx}%
7691   \edlabel{\edindexlab\thelabidx}%
7692 }
7693 %
7694 %

```

`\thepageline` This macro makes up the page/line number combo from the label/ref. The associated counter is never directly used, but it is required in order to not have any error message with `\edgls`.

```

7695 \newcounter{pageline}%
7696 \renewcommand{\thepageline}{%
7697   \thepage%
7698   \pagelinesep%
7699   \xlineref{\edindexlab\thelabidx}%

```

```
7700 }
7701 %
```

\thestrartpageline These macros make up the page/line start/end number when the `\edindex` command
\theendpageline is called in critical notes.

```
7702 \newcommand{\thestrartpageline}{%
7703   \l@dparsedstartpage%
7704   \pagelinesep%
7705   \l@dparsedstartline%
7706 }
7707 \newcommand{\theendpageline}{%
7708   \l@dparsedendpage%
7709   \pagelinesep%
7710   \l@dparsedendline%
7711 }
7712 %
```

XXVIII.3 Code specific to `\edindex` in critical footnotes

\@edindex@fornote@ This counter is incremented at the beginning of each note (either a footnote or a side-note), and decremented at the end of each note. If its value is greater than 0, that means we are inside a note.

```
7713 \newcount\@edindex@fornote@
7714 %
```

\prepare@edindex@fornote This macro is called at the beginning of each critical note. It switches some parameters, to allow index referring to this note, with reference to page and line number. It also defines `\@ledinnote@command` which will be printed as an encapsulating command after the `|`.

```
7715 \newcommand{\prepare@edindex@fornote}[1]{%
7716   \l@dp@rsefootspec#1%
7717   \advance\@edindex@fornote@\@ne%
7718 }
7719 %
```

`\edindex@ledinnote@command` The `\get@edindex@ledinnote@command` macro defines a `\@ledinnote@command` command which is added as an attribute (text inserted after `|`) of the next index entry.

Consequently, we write the definition of the location reference attribute in the `.xdy` file.

```
7720 \newcommand{\get@edindex@ledinnote@command}{%
7721   \ifxindy@%
7722     \gdef\@ledinnote@command{%
7723       ledinnote\thelabidx%
7724     }%
7725     \ifxindyhyperref@%
```

```

7726   \immediate\write\eledmac@xindy@out{%
7727     (define-attributes ("ledinnote\thelabidx"))^^J
7728     \space\space(markup-locref^^J
7729       \eledmacmarkuplocrefdepth^^J
7730       :open "\string\ledinnote[\edindexlab\thelabidx]{\@index@command
7731       }{"^^J
7732       :close "}"^^J
7733       :attr "ledinnote\thelabidx"^^J
7734     )
7735   }%
7736 \else%
7737   \immediate\write\eledmac@xindy@out{%
7738     (define-attributes ("ledinnote\thelabidx"))^^J
7739     \space\space(markup-locref^^J
7740       \eledmacmarkuplocrefdepth^^J
7741       :open "\string\ledinnote{\@index@command}{\@index@command}"^^J
7742       :close "}"^^J
7743       :attr "ledinnote\thelabidx"^^J
7744     )
7745   }%
7746 \fi%
7747 %

```

If we do not use `xindy` option, `\@ledinnote@command` will produce something like `ledinnote{formattingcommand}`.

```

7747 \else%
7748   \gdef\@ledinnote@command{%
7749     ledinnote[\edindexlab\thelabidx]{\@index@command}%
7750   }%
7751 \fi%
7752 }
7753 %

```

XXVIII.4 Analysis of command in indexed text

`\get@index@command` This macro is used to analyze if a text to be indexed has a command after a `|`.

```

7754 \def\get@index@command#1|#2+{%
7755   \gdef\@index@txt{\#1}%
7756   \gdef\@index@command{\#2}%
7757   \xdef\@index@parenthesis{}%
7758   \IfBeginWith{\@index@command}{()}{%
7759     \StrGobbleLeft{\@index@command}{1}[\@index@command@]%
7760     \global\let\@index@command\@index@command@%
7761     \xdef\@index@parenthesis{}%
7762   }{%
7763   \IfBeginWith{\@index@command}{}{%
7764     \StrGobbleLeft{\@index@command}{1}[\@index@command@]%
7765     \global\let\@index@command\@index@command@%

```

```

7766      \xdef\@index@parenthesis{}%
7767      }{}}%
7768  }%
7769  %

```

XXVIII.5 Code for the formatted index

`\ledinnote` These macros are used to specify that an index reference points to a note. Arguments of `\ledinnote` are: #1 (optional): the label for the hyperlink, #2: command applied to the number, #3: the number itself.

```

7770 \newcommandx{\ledinnote}[3][1,usedefault]{%
7771   \ifboolexpr{%
7772     test{\ifdefeq{\iftrue}{\ifHy@hyperindex}}{%
7773       or{%
7774         bool {xindyhyperref@}}%
7775       }%
7776     }{%
7777       \csuse{#2}{\hyperlink{#1}{\ledinnotemark{#3}}}}%
7778     }%
7779   }{%
7780     \csuse{#2}{\ledinnotemark{#3}}%
7781   }%
7782 }%
7783 \newcommand{\ledinnotehyperpage}[2]{\csuse{#1}{\ledinnotemark{\hyperpage{#2}}}}%
7784 \newcommand{\ledinnotemark}[1]{#1\emph{n}}%
7785 %

```

XXVIII.6 Main code

Eledmac and ledmac were using the specific indexing tools of the `memoir` in order to allow multiple index. However, eledmac used `imakeidx` or `indextools` tools when one these two package was loaded. This system forced to maintained a double code, which was not very useful. Since reledmac, we use only the `imakeidx` or `indextools` tools.

The `memoir` class provides more flexible indexing than the standard classes. We need different code if the `memoir` class is being used, except if `imakeidx` or `indextools` is used.

`\ledindex` Write the index information to the `idx` file.

`\@wredindex`

`\dummy@edindex`

```

7786 \newcommandx{\@wredindex}[2][1=\expandonce\jobname,usedefault]{%#1 = the
7787   index name, #2 = the text
7788   \begingroup%
7789     \let\emph\@firstofone%
7790     \let\textbf\@firstofone%
7791     \let\textit\@firstofone%
7792     \let\textmd\@firstofone%

```

```

7792   \let\textnormal\@firstofone%
7793   \let\textrm\@firstofone%
7794   \let\textsc\@firstofone%
7795   \let\textsf\@firstofone%
7796   \let\textsl\@firstofone%
7797   \let\texttt\@firstofone%
7798   \let\textup\@firstofone%
7799   \xdef\@tmp{\#2}%To be used in IfSubStr instead of #2 directly. Avoid
some expansion bugs (for example with \edindex{textsc{something}})
7800   \endgroup%
7801   \ifl@imakeidx%
7802     \ifnum\@edindex@fornote@>\z@%
7803       \IfSubStr[1]{\@tmp}{|}{\get@index@command#2+}{\get@index@command#2|+}
%
7804       \get@edindex@ledinnote@command%
7805       \expandafter\imki@wrindexentry{\#1}{\@index@txt|(\@ledinnote@command
}{\thestartpageline}%
7806       \expandafter\imki@wrindexentry{\#1}{\@index@txt})\@ledinnote@command
}{\theendpageline}%
7807     \else%
7808       \get@edindex@hyperref{\#2}%
7809       \imki@wrindexentry{\#1}{\@index@txt\@edindex@hyperref}{\thepageline}%
7810     \fi%
7811   \else%
7812     \ifnum\@edindex@fornote@>\z@%
7813       \IfSubStr[1]{\@tmp}{|}{\get@index@command#2+}{\get@index@command#2|+}
%
7814       \get@edindex@ledinnote@command%
7815       \expandafter\protected@write\@indexfile{ }%
7816       {\string\indexentry{\@index@txt|(\@ledinnote@command}{\thestartpageline}
}%
7817       \expandafter\protected@write\@indexfile{ }%
7818       {\string\indexentry{\@index@txt}\@ledinnote@command}{\theendpageline}
}%
7819     \else%
7820       \protected@write\@indexfile{ }%
7821       {\string\indexentry{\#2}{\thepageline}}
}%
7822     \fi%
7823   \fi%
7824   \endgroup%
7825   \esphack%
7826 }
7827 %
7828 }
```

Need to add the definition of \edindex to \makeindex, and initialise \edindex to do nothing.

```

7831 \pretocmd{\makeindex}{%
7832   \def\edindex{%
7833     \ifboolexpr{bool{numbering} or bool{numberingR} or bool{
```

```

7834   l@dprintingpages} or bool{l@dprintingcolumns}{%
7835     \@bsphack%
7836     \doedindexlabel%
7837     \begingroup%
7838     \@sanitize%
7839     \@wredindex%
7840   }%
7841   \led@warn@edinde@outsidenumbering%
7842   \index%
7843 }%
7844 }%
7845 }%
7846 {}%
7847 {\led@error@fail@patch@makeindex}%
7848 \newcommand{\edindex}[1]{\@bsphack\@esphack}
7849 \newcommandx{\dummy@edindex}[2][1=\expandonce\jobname,usedefault]{}%
7850 %

```

XXVIII.7 Hyperlink

\hyperlinkformat \hyperlinkformat command is to be used to have both a internal hyperlink and a format, when indexing.

```

7851 \newcommand{\hyperlinkformat}[3]{%
7852   \ifstrempty{#1}%
7853     {\hyperlink{#2}{#3}}%
7854     {\csuse{#1}{\hyperlink{#2}{#3}}}%
7855   }%
7856 %

```

\hyperlinkR \hyperlinkR command is to be used to create a internal hyperlink and \ledRflag, when indexing.

```

7857 \newcommand{\hyperlinkR}[2]{%
7858   \hyperlink{#1}{\#2\@Rlineflag}%
7859 }%
7860 %
7861 %

```

\hyperlinkformatR \hyperlinkformatR command is to be used to create a internal hyperlink, a format and a \@Rlineflag, when indexing.

```

7862 \newcommand{\hyperlinkformatR}[3]{%
7863   \hyperlinkformat{#1}{#2}{#3\@Rlineflag}%
7864 }%
7865 %
7866 %

```

\get@edindex@hyperref \get@edindex@hyperref is to be used to define the \@edindex@hyperref macro, which, in index, links to the point where the index was called (with hyperref).

```
7867 \newcommand{\get@edindex@hyperref}[1]{%
7868 %
```

We have to disable temporary spaces to work through a xstring bug (or feature?)

```
7869 \edef\temp@{%
7870 \catcode` =9 %space need for catcode
7871 \detokenize{\#1} %For active character in unicode
7872 \catcode` =10 % space need for catcode
7873 }%
7874 %
```

Now, we define \@edindex@hyperref if the hyperindex of hyperref is enabled.

```
7875 \ifdefeq{\iftrue}{\ifHy@hyperindex}{%
7876 \IfSubStr{\temp@}{|}{%
7877 {\get@index@command#1+%
7878 \ifledRcol%
7879 \gdef\@edindex@hyperref{| \index@parenthesis %space kept
7880 hyperlinkformatR{\index@command}%
7881 {\edindexlab\thelabidx}}%
7882 \else%
7883 \gdef\@edindex@hyperref{| \index@parenthesis %space kept
7884 hyperlinkformat{\index@command}%
7885 {\edindexlab\thelabidx}}%
7886 \fi%
7887 }%
7888 {\get@index@command#1|+%
7889 \ifledRcol%
7890 \gdef\@edindex@hyperref{| hyperlinkR{\edindexlab\thelabidx}}%
7891 \else%
7892 \gdef\@edindex@hyperref{| hyperlink{\edindexlab\thelabidx}}%
7893 \fi%
7894 }%
7895 }%
7896 %
```

```
7897 % If we use both xindy and hyperref, first get the \protect\cs{%
7898 index@command} command.
7899 % Then define \protect\cs{@edindex@hyperref} in the form \verb+eledmacXXX+
7900 % \begin{macrocode}
7901 {\ifxindyhyperref@%
7902 \IfSubStr{\temp@}{|}{%
7903 {\get@index@command#1+}%
7904 {\get@index@command#1|+}%
7905 \gdef\@edindex@hyperref{| eledmac\thelabidx}%
7906 }%
```

If we start a reference range by a opening parenthesis, store the \thelabidx for the current \edindex, then define \@edindex@hyperref in the form |(eledmac\thelabidx).

```

7906   \IfStrEq{\@index@parenthesis}{()}{%
7907     {%
7908       \csxdef{xindy@{index@txt}}{\thelabidx}{%
7909         \gdef\@edindex@hyperref{|(eledmac\thelabidx){%
7910           }{%
7911           }{%
7912         }%
7913       }%
7914     }%
7915   }%
7916 }
```

This `\thelabidx` will be called back at the closing parenthesis, to have the same number in `\@edindex@hyperref` command that we had at the opening parenthesis. `\@edindex@hyperref` start by a closing parenthesis, then followed by `eledmacXXX` where XXX is the `\thelabidx` of the opening `\@edindex`.

```

7913   \IfStrEq{\@index@parenthesis}{()}{%
7914     {%
7915       \xdef\@edindex@hyperref{|)eledmac\csuse{xindy@{index@txt}}{%
7916         \global\csundef{xindy@{index@txt}}{%
7917           }{%
7918         }%
7919       }%
7920     }%
7921   }%
7922 }
```

Write in the .xdy file the attributes of the location.

```

7919   {%
7920     \immediate\write\eledmac\xindy@out{%
7921       (define-attributes ("eledmac\thelabidx"))^^J
7922       \space\space(markup-locref^^J
7923         \eledmacmarkuplocrefdepth^^J
7924         :open "\string\hyperlink%
7925           \ifledRcol R\fi%
7926           {\@edindexlab\thelabidx}%
7927           {\ifdefempty{\@index@command}%
7928             {}%
7929             {\@backslashchar\@index@command}%
7930             {"^^J
7931           :close "}"})"^^J
7932           :attr "eledmac\thelabidx"^^J
7933         )
7934       }%
7935     }%
7936   }%
7937 }
```

And now, in any other case.

```

7937   \else%
7938     \gdef\@index@txt{\#1}{%
7939       \gdef\@edindex@hyperref{}{%
7940         \fi%
7941       }%
7942     }%
7943   }%
```

XXVIII.8 ‘innote’ and ‘notenumber’ option of `indextools` package

`\led@set@index@fornote` The `\led@set@index@fornote` is called when a familiar footnote is inserted — and not when it is read — and changes the `\index` command depending of the option of the `indextools` package. Its only argument is the note series.

```

7944 \newcommand{\led@set@index@fornote}[1]{%
7945   \ifbooleq{\indtl@innote}{%
7946     {\let\index\nindex}%
7947     {}%
7948   \ifbooleq{\indtl@notenumber}{%
7949     {}%
7950     \renewcommand{\index}[2][\indtl@jobname]{%
7951       \orig@@index[\#1]{%
7952         \##2|innotenumber{\this@footnoteX@reading}%
7953       }%
7954     }%
7955   }%
7956   {}%
7957 }%
7958 %

```

`\led@reinit@index@fornote` The `\led@reinit@index@fornote` just reset the default value of `\index`.

```

7959 \newcommand{\led@reinit@index@fornote}{%
7960   \ifbooleq{\indtl@innote}{%
7961     {\let\index\orig@@index}%
7962     {}%
7963   \ifbooleq{\indtl@notenumber}{%
7964     {\let\index\orig@@index}%
7965     {}%
7966   }%
7967 %

```

XXIX Glossaries

Here, we define the `\gls`-like commands prefixed by `ed`, only if the package `glossaries` is loaded.

```

7968 \AtBeginDocument{%
7969   \@ifpackageloaded{glossaries}{%
7970   %

```

First those which arguments are $[(options)]\{label\}[(insert)]$.

```

7971   \renewcommand{\do}[1]{%
7972     \expandafter\DeclareRobustCommand\x\csname ed#1\endcsname[3][1,3,
7973     usedefault]{%
7974       \doedindexlabel%

```

```

7974     \csname#1\endcsname [counter=pageline,##1]{##2}[##3]%
7975   }%
7976   \expandafter\WithSuffix\expandafter\DeclareRobustCommandx\csname ed
#1\endcsname*[3][1,3,usedefault]{%
7977     \doedindexlabel%
7978     \csname#1\endcsname*[counter=pageline,##1]{##2}[##3]%
7979   }%
7980 }%
7981 \docslist{%
7982   gls,%
7983   Gls,%
7984   GLS,%
7985   glspl,%
7986   Glspl,%
7987   GLSpl,%
7988   glstext,%
7989   Glstext,%
7990   GLStext,%
7991   Glsfir,%
7992   GLSfir,%
7993   glsplur,%
7994   Glsplur,%
7995   GLSplur,%
7996   glsfirplur,%
7997   Glsfirplur,%
7998   GLSfirplur,%
7999   glsname,%
8000   Glsname,%
8001   GLSname,%
8002   glssymbol,%
8003   Glssymbol,%
8004   GLSsymbol,%
8005   glsdesc,%
8006   Glsdesc,%
8007   GLSdesc,%
8008   glsuseri,%
8009   Glsuseri,%
8010   GLSuseri,%
8011   glsuserii,%
8012   Glsuserii,%
8013   GLSuserii,%
8014   glsuseriii,%
8015   Glsuseriii,%
8016   GLSuseriii,%
8017   glsuseriv,%
8018   Glsuseriv,%
8019   GLSuseriv,%
8020   glsuserv,%
8021   Glsuserv,%
8022   GLSuserv,%

```

```

8023     glsuservi,%
8024     Glsuservi,%
8025     GLSuservi%
8026     }%
8027 %

```

Then those which arguments are [$\langle options \rangle$] { $\langle label \rangle$ } { $\langle link text \rangle$ }.

```

8028     \renewcommand{\do}[1]{%
8029         \expandafter\DeclareRobustCommandx\csname ed#1\endcsname[3][1,
8030         usedefault]{%
8031             \doedindexlabel%
8032             \csname#1\endcsname[counter=pageline,##1]{##2}{##3}%
8033             }%
8034             \expandafter\WithSuffix\expandafter\DeclareRobustCommandx\csname ed
8035             #1\endcsname*[3][1,usedefault]{%
8036                 \doedindexlabel%
8037                 \csname#1\endcsname*[counter=pageline,##1]{##2}{##3}%
8038                 }%
8039 %

```

Then those which arguments are [$\langle options \rangle$] { $\langle label \rangle$ }.

```

8040     \renewcommand{\do}[1]{%
8041         \expandafter\DeclareRobustCommandx\csname ed#1\endcsname[2][1,
8042         usedefault]{%
8043             \doedindexlabel%
8044             \csname#1\endcsname[counter=pageline,##1]{##2}%
8045             }%
8046             \expandafter\WithSuffix\expandafter\DeclareRobustCommandx\csname ed
8047             #1\endcsname*[2][1,usedefault]{%
8048                 \doedindexlabel%
8049                 \csname#1\endcsname*[counter=pageline,##1]{##2}%
8050                 }%
8051                 \docsvlist{glsadd}%
8052             }{%
8053 %

```

XXX Verse

The original code is principally Wayne Sullivan's code from `edstanza`. However, the code has been many time modified by Maïeul Rouquette in order to obtain new features and improved compatibility with `reledpar`.

XXX.1 Hanging symbol management

\@hangingsymbol
\sethangingsymbol The macro \@hangingsymbol is used to insert a symbol on each hanging of verses. It is set by user level macro \sethangingsymbol.

\ifinstanza For example, in French typography, the symbol is '['. We obtain it by means of the following code:

```
\sethangingsymbol{[\,]}
```

The \ifinstanza boolean is used to ensure that we are in a stanza part.

```
8054 \def\@hangingsymbol{}  
8055 \newcommand*\sethangingsymbol[1]{%  
8056   \gdef\@hangingsymbol{\#1}%  
8057 }%  
8058 \newif\ifinstanza  
8059 %
```

\inserthangingsymbol The boolean \inserthangingsymbol is set to TRUE when \clock is greater than 1,
\ifinserthangingsymbol i.e. when we are not in the first line of a verse. The switch of \inserthangingsymbol is made in \do@line before the printing of line but after the line number calculation.

```
8060 \newif\inserthangingsymbol  
8061 \newcommand{\inserthangingsymbol}{%  
8062 \ifinserthangingsymbol%  
8063   \ifinstanza%  
8064     \@hangingsymbol%  
8065   \fi%  
8066 \fi%  
8067 }  
8068 %
```

XXX.2 Using & character

\ampersand Within a stanza the \& macro is going to be usurped. We need an alias in case an & needs to be typeset in a stanza. Define it rather than letting it in case some other package has already defined it.

```
8069 \newcommand*\ampersand{\char`\&}  
8070 %  
8071 %
```

XXX.3 Code category setting

\stanza@count Before we can define the main macros we need to save and reset some category codes.
\stanzaindentbase To save the current values we use \next and \body from the \loop macro.

```

8072 \chardef\body=\catcode`@`@=11
8073 \chardef\next=\catcode`&`@&=\active
8074
8075
8076 %
8077 %

```

XXX.4 Stanza count and indent

A count register is allocated for counting lines in a stanza; also allocated is a dimension register which is used to specify the base value for line indentation; all stanza indentations are multiples of this value. The default value of `\stanzaindentbase` is 20pt.

```

8078 \newcount\stanza@count
8079 \newlength{\stanzaindentbase}
8080 \setlength{\stanzaindentbase}{20pt}
8081
8082 %

```

`\strip@szacnt` The indentations of stanza lines are non-negative integer multiples of the unit called `\stanzaindentbase`. To make it easier for the user to specify these numbers, some list macros are defined. These take numerical values in a list separated by commas and assign the values to special control sequences using `\mathchardef`. Though this does limit the range from 0 to 32767, it should suffice for most applications, including *penalties*, which will be discussed below.

```

8083 \def\strip@szacnt#1,#2{`\def@tempb{#1}\def@tempa{#2`}}
8084 \newcommand*{\setstanzavalues}[2]{`\def@tempa{#2,,`%
8085     \stanza@count\z@
8086     \def\next{\expandafter\strip@szacnt@\tempa
8087         `ifx@\tempb\empty\let\next\relax\else
8088             \expandafter\mathchardef\csname #1@\number\stanza@count
8089             @\endcsname@\tempb\relax
8090             \advance\stanza@count\@ne\fi\next`%
8091     \next`}
8092
8093 %

```

`\setstanzaindents` In the original edmac, `\setstanzavalues{sza}{...}` had to be called to set the indents, and similarly `\setstanzavalues{szp}{...}` to set the penalties. `\setstanzaindents` and `\setstanzapenalties` macros are a convenience to give the user one less thing to worry about (misspelling the first argument).

```

8094 \newcommand*{\setstanzaindents}[1]{\setstanzavalues{sza}{#1}}
8095 \newcommand*{\setstanzapenalties}[1]{\setstanzavalues{szp}{#1}}
8096 %
8097 %

```

\managestanza@modulo Since version 0.13, the `stanzaindent$repetition` counter can be used when the indentation is repeated every n verses. The `\managestanza@modulo` is a command which modifies the counter `stanza@modulo`. The command adds 1 to `stanza@modulo`, but if `stanza@modulo` is equal to the `stanzaindent$repetition` counter, the command restarts it.

```

8098 \newcounter{stanzaindent$repetition}
8099 \newcount\stanza@modulo
8100
8101 \newcommand*\managestanza@modulo[0]{%
8102     \advance\stanza@modulo\@ne%
8103     \ifnum\stanza@modulo>\value{stanzaindent$repetition}%
8104         \stanza@modulo\@ne%
8105     \fi%
8106 }
8107 %

```

\stanzaindent The macro `\stanzaindent`, when called at the beginning of a verse, changes the indentation normally defined for this verse by `\setstanzaindent`. The starred version skips the current verse for the repetition of stanza indent.

```

8108 \newcommand{\stanzaindent}[1]{%
8109     \hspace{\dimexpr#1\stanzaindentbase-\parindent\relax}%
8110     \ignorespaces%
8111 }%
8112 \WithSuffix\newcommand\stanzaindent*[1]{%
8113     \stanzaindent{#1}%
8114     \global\advance\stanza@modulo-\@ne%
8115     \ifnum\stanza@modulo=0%
8116         \global\stanza@modulo=\value{stanzaindent$repetition}%
8117     \fi%
8118     \ignorespaces%
8119 }%
8120 %

```

XXX.5 Numbering stanza

Here, macro for numbering stanza. First, the stanza counter.

```

\thestanza21 \newcounter{stanza}
8122 \renewcommand{\thestanza}{%
8123     \textbf{\arabic{stanza}}%
8124 }
8125 %

```

\ifnumberstanza Then, macro to activate automatically numbering of stanza.

```

8126 \newif\ifnumberstanza%
8127 %

```

\@insertstanzonenumber Now, macro called at the first line of of verse of a stanza.

```

8128 \newcommand{\@insertstanzonenumber}[0]{%
8129   \ifnumberstanza%
8130     \ifl@dpairing%
8131       \ifledRcol%
8132         \stanzanumwrapper{\thestanzaR}%
8133       \else%
8134         \stanzanumwrapper{\thestanzaL}%
8135       \fi%
8136     \else%
8137       \stanzanumwrapper{\thestanza}%
8138     \fi%
8139     \setline{1}%
8140   \fi%
8141 }%
8142 %

```

\@advancestanzanumber Also a command to advance the counter of stanza.

```

8143 \newcommand{\@advancestanzanumber}[0]{%
8144   \ifnumberstanza%
8145     \ifl@dpairing%
8146       \ifledRcol%
8147         \addtocounter{stanzaR}{1}%
8148       \else%
8149         \addtocounter{stanzaL}{1}%
8150       \fi%
8151     \else%
8152       \addtocounter{stanza}{1}%
8153     \fi%
8154   \fi%
8155 }%
8156 %

```

\stanzanumwrapper And finally, the wrapper for stanza number

```

8157 \newcommand{\stanzanumwrapper}[1]{%
8158   \flagstanza{\#1}%
8159 }%
8160 %

```

XXX.6 Stanza number in note

Here, the command called when printing stanza number in notes.

```

8161 \newcommand{\printstanza}[0]{%
8162   \ifboolexpr{bool{l@dpairing} or bool{l@printingpages} or bool{%
8163     l@printingcolumns}}{%
8164       \ifledRcol@%

```

```

8164          \thestanzaR%
8165      \else%
8166          \thestanzaL%
8167      \fi%
8168  }%
8169      \thestanza%
8170  }%
8171 }
8172 %

```

XXX.7 Main work

`\stanza@line` Now we arrive at the main works. `\stanza@line` sets the indentation for the line and `\stanza@hang` starts a numbered paragraph—each line is treated as a paragraph. `\stanza@hang` sets the hanging indentation to be used if the stanza line requires more than one print line. `\sza@penalty`

If it is known that each stanza line will fit on one print line, it is advisable to set the hanging indentation to zero. `\sza@penalty` places the specified penalty following each stanza line. By default, this facility is turned off so that no penalty is included. However, the user may initiate these penalties to indicate good and bad places in the stanza for page breaking.

```

8173 \newcommandx{\stanza@line}[2][1,2]{\usedefault}{%
8174     \ifnum\value{stanzaindentrepetition}=0
8175         \ifcsdef{sza@\number\stanza@count }{%
8176             {%
8177                 \parindent=\csname sza@\number\stanza@count @\endcsname\
8178                 stanzaindentbase%
8179             }{%
8180                 \led@err@StanzaIndentNotDefined%
8181             }%
8182         \else
8183             \ifcsdef{sza@\number\stanza@modulo }{%
8184                 \parindent=\csname sza@\number\stanza@modulo @\endcsname\
8185                 stanzaindentbase%
8186                 \managesstanza@modulo%
8187             }{%
8188                 \led@err@StanzaIndentNotDefined%
8189             }%
8190             \fi
8191             \pstart[#1] [#2]\stanza@hang\ignorespaces%
8192         }%
8193         \xdef\stanza@hang{\noexpand\leavevmode\noexpand\startlock
8194             \hangindent\expandafter
8195             \noexpand\csname sza@\number\endcsname\stanzaindentbase
8196             \hangafter\@ne}
8197         \def\sza@penalty{\count@{\csname szp@\number\stanza@count @\endcsname
8198             \ifnum\count@>@\M\advance\count@-\@M\penalty-\else
8199             \penalty\fi\count@}}

```

8199 %

\@startstanza
 \stanza
 \@stopstanza
 \AtEveryStopStanza
 \AtEveryStanza
 \AtStartEveryStanza
 \BeforeEveryStopStanza
 \newverse

Now we have the components of the \stanza macro, which appears at the start of a group of lines. This macro initializes the count and checks to see if hanging indentation and penalties are to be included. Hanging indentation suspends the line count, so that the enumeration is by verse line rather than by print line. If the print line count is desired, invoke \let\startlock\relax and do the same for \endlock. Here and above we have used \xdef to make the stored macros take up a bit less space, but it also makes them more obscure to the reader. Lines of the stanza are delimited by ampersands &. The last line of the stanza must end with \&.

```

8200 \xdef\@startstanza[#1] [#2]{%
8201   \noexpand\instanzatrue\expandafter
8202   \begin{group}%
8203   \catcode`\noexpand\&\active%
8204   \global\stanza@count\@ne\stanza@modulo\@ne
8205   \noexpand\ifnum\expandafter\noexpand
8206   \csname sza@\@ne\endcsname=\z@\let\noexpand\stanza@hang\relax
8207   \let\noexpand\endlock\relax\noexpand\else\interlinepenalty
8208   \OMrightskip\z@ plus 1fil\relax\noexpand\fi\noexpand\ifnum
8209   \expandafter\noexpand\csname szp@\@ne\endcsname=\z@
8210   \let\noexpand\sza@penalty\relax\noexpand\fi%
8211   \def\noexpand&{%
8212     \noexpand\newverse[] []}%
8213   \def\noexpand\&{\noexpand\@stopstanza}%
8214   \noexpand\@advancestanzanumber}%
8215   \noexpand\stanza@line[#1] [#2]%
8216   \noexpand\@insertstanzanumber}%
8217   \let\par\relax\ignorespaces%No paragraph in verses
8218 }

8219 \newcommandx{\stanza}[2][1,2,usedefault]{%
8220   \ifboolexpr{%
8221     not test{\ifdefvoid{\at@every@stanza}}%
8222     and test{\ifstrempty{#1}}%
8223     and test{\ifstrempty{#2}}}%
8224   {\@startstanza[] [\at@every@stanza]\at@start@every@stanza}%
8225   {\@startstanza[#1] [#2]\at@start@every@stanza}%
8226 }%
8227 }%

8228 \newcommandx{\@stopstanza}[2][1,2,usedefault]{%
8229   \unskip%
8230   \endlock%
8231   \ifboolexpr{%
8232     not test{\ifdefvoid{\at@every@stop@stanza}}%
8233     and test{\ifstrempty{#1}}%
8234     and test{\ifstrempty{#2}}}%
8235   {\before@every@stop@stanza\pend[] [\at@every@stop@stanza]}%
8236   {\before@every@stop@stanza\pend[#1] [#2]}%
8237 }
```

```

8238     \endgroup%
8239     \instanzafalse%
8240 }
8241
8242 \newcommand{\AtEveryStopStanza}[1]{%
8243     \ifstrempty{#1}%
8244         {\gdef\at@every@stop@stanza{}%}
8245         {\gdef\at@every@stop@stanza{\noindent#1}}%
8246 }%
8247 \WithSuffix\newcommand\AtEveryStopStanza*[1]{%
8248     \ifstrempty{#1}%
8249         {\gdef\at@every@stop@stanza{}%}
8250         {\gdef\at@every@stop@stanza{#1}}%
8251 }%
8252 \def\at@every@stop@stanza{}%
8253
8254 \newcommand{\AtEveryStanza}[1]{%
8255     \ifstrempty{#1}%
8256         {\gdef\at@every@stanza{}%}
8257         {\gdef\at@every@stanza{\noindent#1}}%
8258 }%
8259 \WithSuffix\newcommand\AtEveryStanza*[1]{%
8260     \ifstrempty{#1}%
8261         {\gdef\at@every@stanza{}%}
8262         {\gdef\at@every@stanza{#1}}%
8263 }%
8264
8265
8266 \newcommand{\AtStartEveryStanza}[1]{%
8267     \ifstrempty{#1}%
8268         {\gdef\at@start@every@stanza{}%}
8269         {\gdef\at@start@every@stanza{#1}}%
8270 }%
8271 \def\at@start@every@stanza{}%
8272
8273 \newcommand{\BeforeEveryStopStanza}[1]{%
8274     \ifstrempty{#1}%
8275         {\gdef\before@every@stop@stanza{}%}
8276         {\gdef\before@every@stop@stanza{#1}}%
8277 }%
8278 \def\before@every@stop@stanza{}%
8279
8280 \newcommandx*{\newverse}[4][1,2,3,4,usedefault]{%
8281     \unskip%
8282     \endlock\pend[#1][#3]\sza@penalty\global%
8283     \advance\stanza@count\one\stanza@line[#2][#4]%
8284 }
8285
8286 %
8287 %

```

\flagstanza Use `\flagstanza[len]{text}` at the start of a line to put `text` a distance `len` before the start of the line. The default for `len` is `\stanzaindentbase`.

```
8288 \newcommand*{\flagstanza}[2][\stanzaindentbase]{%
8289   \hskip -#1\llap{#2}\hskip #1\ignorespaces}
8290 %
8291 %
```

XXX.8 Restore catcode and penalties

The ampersand & is used to mark the end of each stanza line, except the last, which is marked with \&. This means that `\halign` may not be used directly within a stanza line. This does not affect macros involving alignments defined outside `\stanza \&`. Since these macros usurp the control sequence \&, the replacement `\ampersand` is defined to be used if this symbol is needed in a stanza. Also we reset the modified category codes and initialize the penalty default.

```
8292 \catcode`\&=\next
8293 \catcode`\@=\body
8294 \setstanzavalues{szp}{0}
8295 %
8296 %
```

XXXI Apparatus of Manuscripts

XXXI.1 User level macro

\msdata The user level `\msdata` command only writes the manuscripts data in a numbered auxiliary file. There are two associated etoolbox counters.

```
\msdata@cR
8297 \def\msdata@c{%
8298 \def\msdata@cR{%
8299 \newcommand{\msdata}[1]{%
8300   \leavevmode%
8301   \unless\ifstopmsdata@inserted@%
8302     \stopmsdata%
8303     \led@warning@msdata@withoutstop%
8304   \fi%
8305   \global\stopmsdata@inserted@false%
8306   \unless\ifledRcol%
8307     \numgdef{\msdata@c}{\msdata@c+1}%
8308     \ifdef{\hypertarget}{%
8309       \edlabel{\msdata@c:start:msdata}%
8310     }{%
8311       \protected@write\linenum@out{}{%
8312         \string\@msd{\#1}%
8313     }%
8314   \else%
```

```

8315     \numgdef{\msdata@cR}{\msdata@cR+1}%
8316     \ifdef{\hypertarget}{%
8317         \edlabel{\msdata@cR:start:msdata}%
8318     }{%
8319     \protected@write\linenum@outR{}{%
8320         \string\@msd{\#1}%
8321     }%
8322     \fi%
8323 }%
8324 %

```

\stopmsdata The user level \stopmsdata command only writes information about the end of manuscripts data in numbered auxiliary file.

```

8325 \newcommand{\stopmsdata}[0]{%
8326     \leavevmode%
8327     \unless\ifledRcol%
8328         \protected@write\linenum@out{}{%
8329             \string\@stopmsd}%
8330     }%
8331     \ifdef{\hypertarget}{%
8332         \edlabel{\msdata@c:end:msdata}%
8333     }{%
8334     \else%
8335         \protected@write\linenum@outR{}{%
8336             \string\@stopmsd}%
8337     }%
8338     \ifdef{\hypertarget}{%
8339         \edlabel{\msdata@cR:end:msdata}%
8340     }{%
8341     \fi%
8342     \global\stopmsdata@inserted@true%
8343 }%
8344 %

```

\ifstopmsdata@inserted@ The \ifstopmsdata@inserted@ boolean is set to TRUE at every \stopmsdata and reset to FALSE at all \msdata. It also set to TRUE at every \beginnumbering. It is used to automatically insert \stopmsdata if forgotten before \msdata

```

8345 \newif\ifstopmsdata@inserted@
8346 %

```

XXXI.2 Setting macro

Setting macros for the manuscripts apparatus tools is very easy: they just save their argument in an internal macro.

\setmsdataseries In which series of notes will be printed the apparatus of manuscripts?

```

8347 \newcommand{\setmsdataseries}[1]{%
8348   \gdef\@msdata@series{#1}%
8349 }%
8350 \def\@msdata@series{A}%
8351 %

```

`\setmsdataposition` The label for the manuscripts data.

```

8352 \def\ms@data@position{msdata-regular}%
8353 \newcommand{\setmsdataposition}[1]{%
8354   \gdef\ms@data@position{#1}%
8355 }%
8356 %

```

`\setmsdatalabel` The label for the manuscripts data.

```

8357 \def\ms@data@label{Ms.}%
8358 \newcommand{\setmsdatalabel}[1]{%
8359   \gdef\ms@data@label{#1}%
8360 }%
8361 %

```

XXXI.3 Counters and lists

`\@msd@c` `\@msd@c` is a counter incremented at each `\@msd` read in auxiliary file.

```

8362 \numdef{\@msd@c}{0}
8363 \numdef{\@msd@cR}{0}
8364 %

```

`\add@msd@` `\add@msd@` is a counter incremented at each `\add@msddata`, that is at each time we prepare the insertion of manuscripts data footnote.

```

8365 \numdef{\add@msd@c}{0}%
8366 \numdef{\add@msd@cR}{0}%
8367 %

```

`\@msdata@list` The `\@msdata@list` will contain, for each line, the lists of command to be executed to insert the manuscripts apparatus. It will be filled on `\add@msdata` and looped on `\insert@msdata`, then emptied.

```

8368 \def\@msdata@list{}%
8369 %

```

XXXI.4 Auxiliary file macros

\@msd The \@msd macro is written in the auxiliary file. It just defines three macros by \msdata macro, which allow us to know the manuscripts data, the line number and the absolute line number where it was called

It also stores the action code 1010 in the list of actions by line.

```

8370 \newcommand{\@msd}[1]{%
8371   \unless\ifledRcol%
8372     \global\numdef{\@msd@c}{\@msd@c+\@ne}%
8373     \csgdef{\msdata@\@msd@c \data}{\#1}%
8374     \csxdef{\msdata@\@msd@c \linenumber}{\the\line@num}%
8375     \csxdef{\msdata@\@msd@c \abslinenumber}{\the\absline@num}%
8376     \xright@appenditem{\the\absline@num}\to\actionlines@list%
8377     \xright@appenditem{-1010}\to\actions@list%
8378   \else%
8379     \global\numdef{\@msd@cR}{\@msd@cR+\@ne}%
8380     \csgdef{\msdata@\@msd@cR \dataR}{\#1}%
8381     \csxdef{\msdata@\@msd@cR \linenumberR}{\the\line@numR}%
8382     \csxdef{\msdata@\@msd@cR \abslinenumberR}{\the\absline@numR}%
8383     \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
8384     \xright@appenditem{-1010}\to\actions@listR%
8385   \fi%
8386 }%
8387 %

```

\@stopmsd Inserted in the auxiliary file by \stopmsd, the \@stopmsd macro will store in two commands the line number and the absolute line number on which it is called.

```

8388 \newcommand{\@stopmsd}[0]{%
8389   \unless\ifledRcol%
8390     \ifcsundef{\msdata@\@msd@c \stoplinenumber}{%
8391       \csxdef{\msdata@\@msd@c \stopabslinenumber}{\the\absline@num}%
8392       \csxdef{\msdata@\@msd@c \stoplinenumber}{\the\line@num}%
8393     }%
8394   \else%
8395     \ifcsundef{\msdata@\@msd@cR \stoplinenumberR}{%
8396       \csxdef{\msdata@\@msd@cR \stopabslinenumberR}{\the\absline@numR}%
8397       \csxdef{\msdata@\@msd@cR \stoplinenumberR}{\the\line@numR}%
8398     }%
8399   }%
8400 \fi%
8401 }%
8402 %

```

XXXI.5 Action macro

\add@msdata \add@msdata is executed on each line when action code 1010 is seen. It will not insert immediately the manuscript data footnote, as action code are executed before the

line be typeset, and, consequently, could be on the previous page. So it just stores the manuscript data footnote to `\@msdata@list`.

```

8403 \newcommand{\add@msdata}{%
8404   \bgroup%
8405   \normalfont%
8406   \unless\ifledRcol@%
8407     \numgdef{\add@msd@c}{\add@msd@c+\@ne}%
8408     \ifcsdef{@msdata@}{\add@msd@c @data}{%
8409       \letcs{@data}{@msdata@\add@msd@c @data}%
8410       \edef\l@d@nums{%
8411         000% Start page = we don't print it
8412         \csuse{@msdata@\add@msd@c @linenumber}|% Start line number
8413         000% Start subline number, for now, not used
8414         000% End page number, we don't print it
8415         \ifnumless{\csuse{@msdata@\add@msd@c @stopabslinenumber}}{\csuse{%
8416           @lastabsline@forpage@\the\page@num}}%
8417             {\csuse{@msdata@\add@msd@c @stoplinenumber}}%End line number if
8418             in the same page
8419               {\csuse{@lastline@forpage@\the\page@num}}%Otherwise, last
8420             number of the page
8421             |%
8422             000% End sub line number, for now, not used
8423             \edfont@info%Font
8424             }%
8425             \@msd@options@fullpagefalse%
8426             \if@firstlineofpage%Try if the data are for the full page. If yes
8427             , will add options to the list.
8428             \unless\if@msdata@insertedfrompreviouspage%
8429               \ifnumless{\csuse{@lastabsline@forpage@\the\page@num}}{\csuse{%
8430                 @msdata@\add@msd@c @stopabslinenumber}+\@ne}%
8431               {%
8432                 \numdef{\@tmp}{\add@msd@c+\@ne}%
8433                 \ifcsdef{@msdata@}{@tmp @abslinenumber}{%
8434                   \ifnumequal{\csuse{@msdata@}{@tmp @abslinenumber}}{\csuse{%
8435                     @lastabsline@forpage@\the\page@num}}%
8436                     {}%
8437                     {\@msd@options@fullpagetrue}%
8438                     }%
8439                     {\@msd@options@fullpagetrue}%
8440                     }%
8441                     {}%
8442                     \fi%
8443                   \fi%
8444                   \listxadd{@msdata@list}{%
8445                     \@msd@options@iffullpage%
8446                     \ifluatex%
8447                       \csxdef{footnote@luatextextdir}{\the\textdir}%
8448                       \csxdef{footnote@luatexpardir}{\the\pardir}%
8449                     \fi%

```

```

8444 \csdef{@this@crossref@start}{\add@msd@c:start:msdata}%
8445   \csdef{@this@crossref@end}{\add@msd@c:end:msdata}%
8446   \unexpanded{%
8447     \def\annot@start{}%
8448     \def\annot@end{}%
8449   }%
8450   \noexpand\csuse{v\@msdata@series footnote}{\@msdata@series}{\{%
8451     \expandonce{l@d@nums}{\msdata@label}\{\expandonce{@data}\}}%
8452     \reset@msd@options@iffullpage}%
8453   }%
8454   {}%
8455 \else%
8456   \numgdef{\add@msd@cR}{\add@msd@cR+\@ne}%
8457   \ifcsdef{@msdata@\add@msd@cR @dataR}{%
8458     \letcs{@data}{@msdata@\add@msd@cR @dataR}%
8459     \edef\l@d@nums{%
8460       000% Start page = we don't print it
8461       \csuse{@msdata@\add@msd@cR @linenumberR}|% Start line number
8462       000% Start subline number, for now, not used
8463       000% End page number, we don't print it
8464       \ifnumless{\csuse{@msdata@\add@msd@cR @stopabslinenumberR}}{%
8465         \csuse{@lastline@forpageR@\the\page@numR}}%
8466         \csuse{@msdata@\add@msd@cR @stoplinenumberR}}%End line number
8467       if in the same page
8468         \csuse{@lastline@forpageR@\the\page@numR}}%Otherwise, last
8469       number of the page
8470     }%
8471     000% End sub line number, for now, not used
8472     \edfont@info%Font
8473   }%
8474   \@msd@options@fullpagefalse%
8475   \if@firstlineofpageR%
8476     \unless\if@msdata@insertedfrompreviouspage%
8477       \ifnumless{\csuse{@lastabsline@forpageR@\the\page@numR}}{%
8478         \csuse{@msdata@\add@msd@c @stopabslinenumberR}+\@ne}%
8479       }%
8480       \numdef{\@tmp}{\add@msd@cR+\@ne}%
8481       \ifcsdef{@msdata@\@tmp @abslinenumberR}{%
8482         \ifnumequal{\csuse{@msdata@\@tmp @abslinenumberR}}{\csuse{%
8483           @lastabsline@forpageR@\the\page@numR}}{%
8484             }%
8485             \csd@options@fullpagetrue}%
8486           }%
8487           \csd@options@fullpagetrue}%
8488         }%
8489         \fi%
8490       \fi%
8491     \listxadd{@msdata@list}{%

```

```

8488     \@msd@options@iffullpage%
8489     \ifluatex%
8490         \csxdef{footnote@luatextextdir}{\the\textdir}%
8491         \csxdef{footnote@luatexpardir}{\the\pardir}%
8492     \fi%
8493     \csdef{@this@crossref@start}{\add@msd@cR:start:msdata}%
8494     \csdef{@this@crossref@end}{\add@msd@cR:end:msdata}%
8495     \unexpanded{%
8496         \def\annot@start{}%
8497         \def\annot@end{}%
8498     }%
8499     \noexpand\csuse{v\@msdata@series footnote}{\@msdata@series}{\{%
8500         \expandonce\l@d@nums}{\ms@data@label}{\expandonce\@data}}%
8501     \reset@msd@options@iffullpage%
8502 }%
8503 {}%
8504 \fi%
8505 \egroup%
8506 }%
8507 %

```

`\if@msdata@insertedfrompreviouspage` The `\if@msdata@insertedfrompreviouspage` boolean is set to TRUE if `reledmac` automatically inserts data from previous page in the first line of a page.

```

8508 \newif\if@msdata@insertedfrompreviouspage%
8509 %

```

`\add@msdata@firstlineofpage` `\add@msdata@firstlineofpage` is called at the first line of every page. It inserts manuscript data which start on one of the previous pages and continue on this page.

```

8510 \newcommand{\add@msdata@firstlineofpage}{%
8511     \bgroup%
8512     \normalfont%
8513     \unless\ifledRcol@%
8514         \ifcsdef{@msdata@\add@msd@c @data}{}%
8515         \ifnumless{\the\absline@num-\@ne}{\csuse{@msdata@\add@msd@c
8516             @stopabslinenumber}}{%
8517             {%
8518                 \global{@msdata@insertedfrompreviouspagetrue}%
8519                 \letcs{\@data}{@msdata@\add@msd@c @data}%
8520                 \edef\l@d@nums{%
8521                     000}% Start page = we don't print it
8522                     \numexpr\the\line@num+\@ne\relax}% Start line number = first line
8523                     of the page. As \add@msdata@firstlineofpage is called before line number
8524                     has been incremented, we increment it for printing
8525                     000}% Start subline number, for now, not used
8526                     000}% End page number, we don't print it
8527                     \ifnumless{\csuse{@msdata@\add@msd@c @stopabslinenumber}}{\csuse{
8528                         @lastabsline@forpage@\the\page@num}}{%

```

```

8525          {\csuse{@msdata@\add@msd@c @stoplinenumber}}%End line number if
8526          in the same page
8526          {\csuse{@lastline@forpage@\the\page@num}}%Otherwise, last
8527          number of the page
8527          |%
8528          000!% End sub line number, for now, not used
8529          \edfont@info%Font
8530          }%
8531          \@msd@options@fullpagefalse%
8532          \ifnumless{\csuse{@lastabsline@forpage@\the\page@num}}{\csuse{
8532          @msdata@\add@msd@c @stopabslinenumber}+\@ne}%We will test if the ms data is
8533          for the full page
8533          {%
8534          \numdef{\@tmp}{\add@msd@c+\@ne}%
8535          \ifcsdef{@msdata@\@tmp @abslinenumber}%
8536          {\ifnumequal{\csuse{@msdata@\@tmp @abslinenumber}}{\csuse{
8536          @lastabsline@forpage@\the\page@num}}{%
8537          }%
8538          {\@msd@options@fullpagetrue}%
8539          }%
8540          {\@msd@options@fullpagetrue}%
8541          }%
8542          {}%
8543          \listxadd{@msdata@list}{%
8544          \@msd@options@iffullpage%
8545          \ifluatex%
8546          \csxdef{footnote@luatextextdir}{\the\textrm}%
8547          \csxdef{footnote@luatexpardir}{\the\pardir}%
8548          \fi%
8549          \csdef{@this@crossref@start}{\add@msd@c:start:msdata}%
8550          \csdef{@this@crossref@end}{\add@msd@c:end:msdata}%
8551          \unexpanded{%
8552          \def\annot@start{}%
8553          \def\annot@end{}%
8554          }%
8555          \noexpand\csuse{v@\msdata@series footnote}{\msdata@series}{\expandonce{l@d@nums}{\msdata@label}\expandonce{\@data}{}}
8556          \reset@msd@options@iffullpage%
8557          }%
8558          }%
8559          {\global\@msdata@insertedfrompreviouspagefalse}%
8560          }{%
8561          \else%
8562          \ifcsdef{@msdata@\add@msd@cR @dataR}{%
8563          \ifnumless{\the\absline@numR-\@ne}{\csuse{@msdata@\add@msd@cR
8563          @stopabslinenumberR}}{%
8564          }%
8565          \global\@msdata@insertedfrompreviouspagetrue%
8566          \letcs{\@data}{\msdata@\add@msd@cR @dataR}%
8567          \edef{l@d@nums}{%

```

```

8568      000|% Start page = we don't print it
8569      \numexpr\the\line@numR+\@ne\relax|% Start line number = first
8570      line of the page. As \add@msdata@firstlineofpage is called before line
8571      number has been incremented, we increment it for printing
8572      000|% Start subline number, for now, not used
8573      000|% End page number, we don't print it
8574      \ifnumless{\csuse{@msdata@add@msd@cR @stopabslinenumberR}}{\csuse{@lastline@forpageR@\the\page@numR}}%
8575          {\csuse{@msdata@add@msd@cR @stoplinenumberR}}%End line number
8576      if in the same page
8577          {\csuse{@lastline@forpageR@\the\page@numR}}%Otherwise, last
8578      number of the page
8579          |%
8580          000|% End sub line number, for now, not used
8581          \edfont@info%Font
8582          }%
8583          \@msd@options@fullpagefalse%
8584          \ifnumless{\csuse{@lastabsline@forpageR@\the\page@numR}}{\csuse{
8585              @msdata@add@msd@cR @stopabslinenumberR}+\@ne}%
8586              |%
8587              \numdef{\@tmp}{\add@msd@cR+\@ne}%
8588              \ifcsdef{@msdata@\@tmp @abslinenumberR}%
8589                  {\ifnumequal{\csuse{@msdata@\@tmp @abslinenumberR}}{\csuse{
8590                      @lastabsline@forpageR@\the\page@numR}}%
8591                      |%
8592                      {\@msd@options@fullpagetrue}%
8593                      }%
8594                      {\@msd@options@fullpagetrue}%
8595                      }%
8596                      |%
8597                      |%
8598                      \listxadd{@msdata@list}{%
8599                          \@msd@options@iffullpage%
8600                          \ifluatex%
8601                              \csxdef{footnote@luatextextdir}{\the\textdir}%
8602                              \csxdef{footnote@luatexpardir}{\the\pardir}%
8603                              \fi%
8604                              \csdef{@this@crossref@start}{\add@msd@cR:start:msdata}%
8605                              \csdef{@this@crossref@end}{\add@msd@cR:end:msdata}%
8606                              \unexpanded{%
8607                                  \def\annot@start{}%
8608                                  \def\annot@end{}%
8609                                  }%
8610                                  \noexpand\csuse{v@\msdata@series footnote}{\msdata@series}{{}
8611                                  \expandonce{\@d@nums}{\msdata@label}{\expandonce{\data}{}}
8612                                  \reset@msd@options@iffullpage%
8613                                  }%
8614                                  }%
8615                                  |%
8616                                  {\global\msdata@insertedfrompreviouspagefalse}%
8617                                  }-{}%
8618                                  \fi%

```

```

8610     \egroup%
8611 }%
8612 %

```

XXXI.6 Inserting footnote

Just before inserting standard insert (familiar and critical footnotes, sidenotes), we call `\insert@msdata` to insert manuscripts data's footnotes.

```

\insert@msdata13 \newcommand{\insert@msdata}{%
8614     \def\do##1{##1}%
8615     \dolistloop{\@msdata@list}%
8616     \global\let\@msdata@list\relax%
8617 }%
8618 %

```

XXXI.7 Other

`\@msd@options@iffullpage` sets some options if the manuscripts data are for all the page. `\reset@msd@options@iffullpage` resets them after the footnote. `\if@msd@options@fullpage` is switch to true in `add@msdata@firstlineofpage` if these option must be inserted.

```

8619 \newif\if@msd@options@fullpage%
8620 \newcommand{\@msd@options@iffullpage}[0]{%
8621     \if@msd@options@fullpage%
8622         \noexpand\toggletrue{nonum@}%
8623         \ifdefvoid{\msd@data@label}{%
8624             {\noexpand\toggletrue{nosep@}}%
8625             {}%
8626         \fi%
8627     }%
8628 \newcommand{\reset@msd@options@iffullpage}[0]{%
8629     \noexpand\togglefalse{nonum@}%
8630     \noexpand\togglefalse{nosep@}%
8631 }%
8632 %

```

XXXII Arrays and tables

XXXII.1 Preamble: macro as environment

The following is borrowed, and renamed, from the `amsmath` package. See also the CTT thread ‘`eeq` and `amstex`’, 1995/08/31, started by Keith Reckdahl and ended definitively by David M. Jones.

Several of the [math] macros scan their body twice. This means we must collect all text in the body of an environment form before calling the macro.

\@emptytoks This is actually defined in the `amsgen` package.

```
8633 \newtoks\@emptytoks
8634 %
8635 %
```

The rest is from `amsmath`.

\l@denvbody A token register to contain the body.

```
8636 \newtoks\l@denvbody
8637 %
8638 %
```

\addtol@denvbody `\addtol@denvbody{arg}` adds `arg` to the token register `\l@denvbody`.

```
8639 \newcommand{\addtol@denvbody}[1]{%
8640   \global\l@denvbody\expandafter{\the\l@denvbody#1}}
8641 %
8642 %
```

\l@dcollect@body The macro `\l@dcollect@body` starts the scan for the `\end{\langle env\rangle}` command of the current environment. It takes a macro name as argument. This macro is supposed to take the whole body of the environment as its argument. For example, given `cenv#1{...}` as a macro that processes #1, then the environment form, `\begin{cenv}` would call `\l@dcollect@body\cenv`.

```
8643 \newcommand{\l@dcollect@body}[1]{%
8644   \l@denvbody{\expandafter#1\expandafter{\the\l@denvbody}}%
8645   \edef\processl@denvbody{\the\l@denvbody\noexpand\end{\@currenvir}}%
8646   \l@denvbody\@emptytoks \def\l@dbegin@stack{b}%
8647   \begingroup
8648     \expandafter\let\csname@currenvir\endcsname\l@dcollect@@body
8649     \edef\processl@denvbody{\expandafter\noexpand\csname@currenvir\
8650       endcsname}%
8651     \processl@denvbody%
8652   }%
8653 %
```

\l@dpush@begins When adding a piece of the current environment's contents to `\l@denvbody`, we scan it to check for additional `\begin` tokens, and add a 'b' to the stack for any that we find.

```
8654 \def\l@dpush@begins#1\begin#2{%
8655   \ifx\end#2\else b\expandafter\l@dpush@begins\fi}
8656 %
8657 %
```

\l@dcollect@@body \l@dcollect@@body takes two arguments: the first will consist of all text up to the next \end command, and the second will be the \end command's argument. If there are any extra \begin commands in the body text, a marker is pushed onto a stack by the \l@dpush@begins function. Empty state for this stack means we have reached the \end that matches our original \begin. Otherwise we need to include the \end and its argument in the material we are adding to the environment body accumulator.

```

8658 \def\l@dcollect@@body#1\end#2{%
8659   \edef\l@dbegin@stack{\l@dpush@begins#1\begin\end
8660   \expandafter\gobble\l@dbegin@stack}%
8661   \ifx\empty\l@dbegin@stack
8662     \endgroup
8663     \checkend{#2}%
8664     \addtol@denvbody{#1}%
8665   \else
8666     \addtol@denvbody{#1\end{#2}}%
8667   \fi
8668   \processl@denvbody % A little tricky! Note the grouping
8669 }
8670 %
8671 %

```

There was a question on CTT about how to use \collect@body for a macro taking an argument. The following is part of that thread.

From: Heiko Oberdiek <oberdiek@uni-freiburg.de>
 Newsgroups: comp.text.tex
 Subject: Re: Using \collect@body with commands that take >1 argument
 Date: Fri, 08 Aug 2003 09:03:20 +0200

eed132@psu.edu (Evan) wrote:
 > I'm trying to make a new Latex environment that acts like the>
 \colorbox command that is part of the color package. I looked through
 > the FAQ and ran across this bit about using the \collect@body command
 > that is part of AMSLaTeX:
 > http://www.tex.ac.uk/cgi-bin/texfaq2html?label=cmdasenv
 >
 > It almost works. If I do something like the following:
 > \newcommand{\redbox}[1]{\colorbox{red}{#1}}
 >
 > \makeatletter
 > \newenvironment{redbox}{\collect@body \redbox}{}

You will get an error message: Command \redbox already defined.
 Thus you must rename either the command \redbox or the environment name.

> \begin{coloredbox}{blue}
 > Yadda yadda yadda... this is on a blue background...
 > \end{coloredbox}

> and can't figure out how to make the \collect@body take this.

```
> \collect@body \colorbox{red}
> \collect@body {\colorbox{red}}
```

The argument of \collect@body has to be one token exactly.

```
\documentclass{article}
\usepackage{color}
\usepackage{amsmath}

\newcommand{\redbox}[1]{\colorbox{red}{#1}}
\makeatletter
\newenvironment{coloredbox}[1]{%
  \def\next@{\colorbox{#1}}%
  \collect@body\next@
}{}{}

% ignore spaces at begin and end of environment
\newenvironment{coloredboxII}[1]{%
  \def\next@{\mycoloredbox{#1}}%
  \collect@body\next@
}{}{}

\newcommand{\mycoloredbox}[2]{%
  \colorbox{#1}{\ignorespaces#2\unskip}%
}

% support of optional color model argument
\newcommand\coloredboxIII\endcsname{%
\def\coloredboxIII#1{%
  \coloredboxIII{#1}%
}
\def\coloredboxIII#1#2{%
  \def\next@{\mycoloredboxIII{#1}{#2}}%
  \collect@body\next@
}
\newcommand{\mycoloredboxIII}[3]{%
  \colorbox{#1}{#2}\ignorespaces#3\unskip}%
}

\makeatother

\begin{document}
Black text before
\begin{coloredbox}{blue}
Hello World
\end{coloredbox}
Black text after

Black text before
```

```

\begin{coloredboxII}{blue}
Hello World
\end{coloredboxII}
Black text after

Black text before
\begin{coloredboxIII}[rgb]{0,0,1}
Hello World
\end{coloredboxIII}
Black text after

\end{document}

Yours sincerely
Heiko <oberdiek@uni-freiburg.de>

```

XXXII.2 Tabular environments

This is based on the work by Herbert Breger in developing `tabmac.tex`.

The original `tabmac.tex` file was void of comments or any explanatory text other than the above notice. The algorithm is Breger's. Peter Wilson have made some cosmetic changes to the original code and reimplemented some things so they are more LaTeX-like. All the commentary are from Peter Wilson, as are any mistake or errors.

However, Maïeul Rouquette has modified code in order to add new features of `eledmac` and `reledmac`.

XXXII.2.1 Disabling and restoring commands

`\l@dtabnoexpands` More no expansion for critical and familiar footnotes in tabular environment.

```

8672 \newcommand*\l@dtabnoexpands{%
8673   \let\rtab=0%
8674   \let\ctab=0%
8675   \let\ltab=0%
8676   \let\rtabtext=0%
8677   \let\ltabtext=0%
8678   \let\ctabtext=0%
8679   \let\edbforetab=0%
8680   \let\edaftertab=0%
8681   \let\edatleft=0%
8682   \let\edatright=0%
8683   \let\edvertline=0%
8684   \let\edvertdots=0%
8685   \let\edrowfill=0%
8686 }
8687 %
8688 %

```

\disable@familiarnotes Macros to disable and restore familiar notes, to prevent them from printing multiple times in edtabularx and edarrayx environments.

```

8689 \newcommand{\disable@familiarnotes}{%
8690   \unless\ifnofamiliar@%
8691     \def\do##1{%
8692       \csletcs{footnote@@##1}{footnote##1}%
8693       \expandafter\renewcommand \csname footnote##1\endcsname[1]{%
8694         \protected@csxdef{@thefnmark##1}{\csuse{thefootnote##1}}%
8695         \csuse{@footnotemark##1}%
8696       }%
8697     }%
8698     \dolistloop{\@series}%
8699   \fi%
8700 }%
8701 \newcommand{\restore@familiarnotes}{%
8702   \unless\ifnofamiliar@%
8703     \def\do##1{%
8704       \csletcs{footnote##1}{footnote@@##1}%
8705     }%
8706     \dolistloop{\@series}%
8707   \fi%
8708 }%
8709 %
8710 %

```

\disable@sidenotes The same for sidenotes.

```

8711 \newcommand{\disable@sidenotes}{%
8712   \let\@ledrightnote\ledrightnote%
8713   \let\@ledleftnote\ledleftnote%
8714   \let\@ledsidenote\ledsidenote%
8715   \let\ledrightnote@gobble%
8716   \let\ledleftnote@gobble%
8717   \let\ledsidenote@gobble%
8718 }%
8719 \newcommand{\restore@sidenotes}{%
8720   \let\ledrightnote\@ledrightnote%
8721   \let\ledleftnote\@ledleftnote%
8722   \let\ledsidenote\@ledsidenote%
8723 }%
8724 %

```

\disable@endnotes The same for endnotes.

```

8725 \newcommand{\disable@endnotes}{%
8726   \unless\ifnoend@%
8727     \def\do##1{%
8728       \csletcs{##1@endnote}{##1endnote}%
8729       \expandafter\renewcommand \csname ##1endnote\endcsname[1]{}%

```

```

8730      }%
8731      \dolistloop{\@series}%
8732      \fi%
8733  }%
8734  \newcommand{\restore@endnotes}{%
8735  \unless\ifnofamiliar@%
8736  \def\do##1{%
8737  \csletcs{##1endnote}{##1@endnote}%
8738  }%
8739  \dolistloop{\@series}%
8740  \fi%
8741 }%
8742 %

```

\disable@notes Disable/restore side, familiar and end notes.

```

\restore@notes \newcommand{\restore@notes}{%
8743  \newcommand{\disable@sidenotes}{%
8744  \disable@sidenotes%
8745  \disable@familiarnotes%
8746  \disable@endnotes%
8747 }%
8748 \newcommand{\restore@notes}{%
8749  \restore@sidenotes%
8750  \restore@familiarnotes%
8751  \restore@endnotes%
8752 }%
8753 %

```

\EDTEXT We need to be able to modify the \edtext macros and also restore their original definitions.

```

8754 \let\EDTEXT=\edtext
8755 \newcommand{\xedtext}[2]{\EDTEXT{#1}{#2}}
8756 %

```

\EDLABEL We need to be able to modify and restore the \edlabel macro.

```

\xedlabel \let\EDLABEL=\edlabel
8757 \newcommand*{\xedlabel}[1]{\EDLABEL{#1}}
8758 %
8759 %

```

\xedindex Macros supporting modification and restoration of \edindex.

```

\nulledindex \AtBeginDocument{\let\xedindex\edindex}%
8760 \newcommand{\nulledindex}[2][\jobname]{\@bsphack\@esphack}%
8761 %
8762 %
8763 %

```

\@line@@num Macro supporting restoration of \linenum.

```
8764 \let\@line@@num=\linenum
8765 %
```

\l@dgobbleoptarg \l@dgobbleoptarg[⟨arg⟩]{⟨arg⟩} replaces these two arguments (first is optional) by \relax.

```
8766 \newcommand*{\l@dgobbleoptarg}[2][]{\relax}%
8767 %
8768 %
```

\l@secondmandarg \l@secondoptarg[⟨arg⟩]{⟨arg⟩} gobble the first (optional) argument, and expand to the second (mandatory) argument.

```
8769 \NewExpandableDocumentCommand{\l@secondmandarg}{om}{#2}%
8770 %
```

```
\Relax71 \let\Relax=\relax
\next72 \let\next=\next
8773 %
8774 %
```

\l@dmodforedtext Modify and restore various macros for when \edtext is used.

```
\l@restoreforedtext
8775 \newcommand{\l@dmodforedtext}{%
8776   \let\edtext\relax
8777   \def\do##1{\global\csletcs{##1footnote}{\l@dgobbleoptarg}}%
8778   \dolistloop{\@series}%
8779   \let\edindex\nulledindex
8780   \let\linenum@gobble}%
8781 \newcommand{\l@restoreforedtext}{%
8782   \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}%
8783   \dolistloop{\@series}%
8784   \let\edindex\xedindex}
8785 %
```

\l@dnnullfills Nullify and restore some column fillers, etc.

```
\l@restorefills
8786 \newcommand{\l@dnnullfills}{%
8787   \def\edlabel##1{}%
8788   \def\edrowfill##1##2##3{}%
8789 }
8790 \newcommand{\l@restorefills}{%
8791   \def\edrowfill##1##2##3{\@EDROWFILL{##1}{##2}{##3}}%
8792 }
8793 %
8794 %
```

\letsforverteilen Gathers some lets and other code that is common to the *verteilen* macros.

```

8795 \newcommand{\letsforverteilen}{%
8796   \let\edtext\xedtext
8797   \let\ediindex\xídiindex
8798   \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}
8799   \dolistloop{\@series}%
8800   \let\linenum\@line@@num
8801   \hilfsskip=\l@dcollwidth%
8802   \advance\hilfsskip by -\wd\hilfsbox
8803   \def\edlabel##1{\xídilabel{##1}}}

8804 %
8805 %

```

`\disablel@tabfeet` Declarations for using or using `\edtext` inside tabulars. The default at this point is for
`\enablel@tabfeet` `\edtext`.

```

8806 \newcommand\disablel@tabfeet{\l@modforedtext}%
8807 \newcommand\enablel@tabfeet{\l@restoreforedtext}%
8808 %

```

XXXII.2.2 Counters, boxes and lengths

`\l@dampcount` `\l@dampcount` is a counter for the & column dividers and `\l@dcollcount` is a counter
`\l@dcollcount` for the columns.

```

8809 \newcount\l@dampcount
8810   \l@dampcount=1\relax
8811 \newcount\l@dcollcount
8812   \l@dcollcount=0\relax
8813 %
8814 %

```

`\hilfsbox` Some (temporary) helper items.

```

8815 \newbox\hilfsbox
8816 \newskip\hilfsskip
\hilfscount
8817 \newbox\Hilfsbox
8818 \newcount\hilfscount
8819 %
8820 %

```

30 columns should be adequate (compared to the original 60). These are the column widths. (Originally these were German spelled numbers e.g., `\eins`, `\zwei`, etc).

```

8821 \newdimen\dcoli
8822 \newdimen\dcolii
8823 \newdimen\dcoliii
8824 \newdimen\dcoliv
8825 \newdimen\dcolv
8826 \newdimen\dcolvi
8827 \newdimen\dcolvii

```

```

8828 \newdimen\dcollviii
8829 \newdimen\dcoliix
8830 \newdimen\dcolx
8831 \newdimen\dcolxi
8832 \newdimen\dcolxii
8833 \newdimen\dcolxiii
8834 \newdimen\dcolxiv
8835 \newdimen\dcolxv
8836 \newdimen\dcolxvi
8837 \newdimen\dcolxvii
8838 \newdimen\dcolxviii
8839 \newdimen\dcolxix
8840 \newdimen\dcolxx
8841 \newdimen\dcolxxi
8842 \newdimen\dcolxxii
8843 \newdimen\dcolxxiii
8844 \newdimen\dcolxxiv
8845 \newdimen\dcolxxv
8846 \newdimen\dcolxxvi
8847 \newdimen\dcolxxvii
8848 \newdimen\dcolxxviii
8849 \newdimen\dcolxxix
8850 \newdimen\dcolxxx
8851 \newdimen\dcollerr % added for error handling
8852 %
8853 %

```

\l@dcollwidth This is a cunning way of storing the columnwidths indexed by the column number **\l@dcollcount**, like an array. (was \Dimenzuordnung)

```

8854 \newcommand{\l@dcollwidth}{\ifcase \the\l@dcollcount \dcoli %??
8855   \or \dcoli \or \dcollii \or \dcolliii
8856   \or \dcolliv \or \dcollv \or \dcollvi
8857   \or \dcollvii \or \dcollviii \or \dcoliix \or \dcollx
8858   \or \dcollxi \or \dcollxii \or \dcollxiii
8859   \or \dcollxiv \or \dcollxv \or \dcollxvi
8860   \or \dcollxvii \or \dcollxviii \or \dcollxix \or \dcollxx
8861   \or \dcollxxi \or \dcollxxii \or \dcollxxiii
8862   \or \dcollxxiv \or \dcollxxv \or \dcollxxvi
8863   \or \dcollxxvii \or \dcollxxviii \or \dcollxxix \or \dcollxxx
8864   \else \dcollerr \fi}
8865 %
8866 %

```

\step\l@dcollcount This increments the column counter, and issues an error message if it is too large.

```

8867 \newcommand*{\step\l@dcollcount}{\advance\l@dcollcount\@ne
8868   \ifnum\l@dcollcount>30\relax
8869     \led@err@TooManyColumns
8870   \fi}

```

```
8871 %
8872 %
```

\l@dsetmaxcolwidth Sets the column width to the maximum value seen so far.

```
8873 \newcommand{\l@dsetmaxcolwidth}{%
8874   \ifdim\l@dcolwidth < \wd\hilfsbox
8875     \l@dcolwidth = \wd\hilfsbox
8876   \else \relax \fi}
8877 %
8878 %
```

\measuremcell Measure (recursively) the width required for a math cell.

```
8879 \def\measuremcell #1&{%
8880   \ifx #1\relax \ifnum\l@dcolcount=0\let\NEXT\relax%
8881     \else\l@dcheckcols%
8882       \l@dcolcount=0%
8883       \let\NEXT\measuremcell%
8884     \fi%
8885   \else\setbox\hilfsbox=\hbox{\$#1\$}%
8886   \step\l@dcolcount%
8887   \l@dsetmaxcolwidth%
8888   \let\NEXT\measuremcell%
8889   \fi\NEXT}
8890 %
8891 %
```

\measuretcell Measure (recursively) the width required for a text cell.

```
8892 \def\measuretcell #1&{%
8893   \ifx #1\relax \ifnum\l@dcolcount=0\let\NEXT\relax%
8894     \else\l@dcheckcols%
8895       \l@dcolcount=0%
8896       \let\NEXT\measuretcell%
8897     \fi%
8898   \else\setbox\hilfsbox=\hbox{#1}%
8899   \step\l@dcolcount%
8900   \l@dsetmaxcolwidth%
8901   \let\NEXT\measuretcell%
8902   \fi\NEXT}
8903 %
8904 %
```

\measuremrow Measure (recursively) the width required for a math row.

```
8905 \def\measuremrow #1\\{%
8906   \ifx #1\relax \let\NEXT\relax%
8907   \else\measuremcell #1&\&\&%
8908   \let\NEXT\measuremrow%
```

```

8909     \fi\NEXT}
8910 %

```

\measuretrow Measure (recursively) the width required for a text row.

```

8911 \def\measuretrow #1\\{%
8912   \ifx #1&\let\NEXT\relax%
8913   \else\measuretrcell #1&\&\&%
8914     \let\NEXT\measuretrrow%
8915   \fi\NEXT}
8916 %
8917 %

```

\edtabcolsep The length **\edtabcolsep** controls the distance between columns.

```

8918 \newskip\edtabcolsep
8919 \global\edtabcolsep=10pt
8920 %
8921 %

```

```

\variab22 \newcommand{\variab}{\relax}
8923 %
8924 %

```

\l@dcheckcols Check that the number of columns is consistent.

```

8925 \newcommand*\l@dcheckcols{%
8926   \ifnum\l@dcolcount=1\relax
8927   \else
8928     \ifnum\l@dampcount=1\relax
8929     \else
8930       \ifnum\l@dcolcount=\l@dampcount\relax
8931       \else
8932         \l@d@err@UnequalColumns
8933       \fi
8934     \fi
8935     \l@dampcount=\l@dcolcount
8936   \fi}
8937 %
8938 %

```

\edfillldimen A length.

```

8939 \newdimen\edfillldimen
8940 \edfillldimen=0pt
8941 %
8942 %

```

`\c@addcolcount` A counter to hold the number of a column. We use a roman number so that we can grab the column dimension from `\dcol`. We do not use the `\romannumeral` L^AT_EX command, because some packages, like `babel` can override it in some specific cases (Greek, for example).

```
8943 \newcounter{addcolcount}
8944   \renewcommand{\theaddcolcount}{\romannumeral \c@addcolcount}
8945 %
```

XXXII.2.3 Tabular typesetting

`\setmcellright` Typeset (recursively) cells of display math right justified.

```
8946 \def\setmcellright #1&{\def\edlabel##1{}%
8947   \let\edindex\nulledindex
8948   \ifx #1\relax\ifnum\l@dcolcount=0%\removelastskip
8949     \let\Next\relax%
8950   \else\l@dcolcount=0%
8951     \let\Next=\setmcellright%
8952   \fi%
8953 \else%
8954   \disablel@tabfeet%
8955   \stepl@dcolcount%
8956   \disable@notes%
8957   \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
8958   \restore@notes%
8959   \letsforverteilen%
8960   \hskip\hilfsskip$\displaystyle{#1}$%
8961   \hskip\edtabcolsep%
8962   \let\Next=\setmcellright%
8963 \fi\Next}
8964 %
8965 %
```

`\settcellright` Typeset (recursively) cells of text right justified.

```
8966 \def\settcellright #1&{\def\edlabel##1{}%
8967   \let\edindex\nulledindex
8968   \ifx #1\relax\ifnum\l@dcolcount=0%\removelastskip
8969     \let\Next\relax%
8970   \else\l@dcolcount=0%
8971     \let\Next=\settcellright%
8972   \fi%
8973 \else%
8974   \disablel@tabfeet%
8975   \stepl@dcolcount%
8976   \disable@notes%
8977   \setbox\hilfsbox=\hbox{#1}%
8978   \restore@notes%
8979   \letsforverteilen%
8980   \hskip\hilfsskip#1%
```

```

8981     \hskip\edtabcolsep%
8982     \let\Next=\settcellright%
8983   \fi\Next}
8984 %

```

\setmcellleft Typeset (recursively) cells of display math left justified.

```

8985 \def\setmcellleft #1{\def\edlabel##1{}%
8986   \let\edindex\nulledindex
8987   \ifx #1\ \
8988     \ifnum\l@dcolcount=0 \let\Next\relax%
8989     \else\l@dcolcount=0%
8990       \let\Next=\setmcellleft%
8991     \fi%
8992   \else \disablel@dtabfeet%
8993     \stepl@dcolcount%
8994     \disable@notes%
8995     \setbox\hilfsbox=\hbox{\$#1\$}%
8996     \restore@notes%
8997     \letsforverteilen%
8998     \$#1\$ \hskip\hilfsskip\hskip\edtabcolsep%
8999     \let\Next=\setmcellleft%
9000   \fi\Next}
9001 %

```

\settcellleft Typeset (recursively) cells of text left justified.

```

9002 \def\settcellleft #1{\def\edlabel##1{}%
9003   \let\edindex\nulledindex
9004   \ifx #1\ \
9005     \ifnum\l@dcolcount=0 \let\Next\relax%
9006     \else\l@dcolcount=0%
9007       \let\Next=\settcellleft%
9008     \fi%
9009   \else \disablel@dtabfeet%
9010     \stepl@dcolcount%
9011     \disable@notes%
9012     \setbox\hilfsbox=\hbox{#1}%
9013     \restore@notes%
9014     \letsforverteilen%
9015     #1\hskip\hilfsskip\hskip\edtabcolsep%
9016     \let\Next=\settcellleft%
9017 \fi\Next}
9018 %

```

\setmcellcenter Typeset (recursively) cells of display math centered.

```

9018 \def\setmcellcenter #1{\def\edlabel##1{}%
9019   \let\edindex\nulledindex
9020   \ifx #1\ \
9021     \ifnum\l@dcolcount=0\let\Next\relax%

```

```

9022          \let\Next=\setmcellcenter%
9023          \fi%
9024      \else \disabled@dtabfeet%
9025          \stepl@dcolcount%
9026          \disabled@notes%
9027          \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
9028          \restore@notes%
9029          \letsforverteilen%
9030          \hskip 0.5\hifskip$\displaystyle{#1}\$ \hskip 0.5\hifskip%
9031          \hskip\edtabcolsep%
9032          \let\Next=\setmcellcenter%
9033          \fi\Next}
9034 %
9035 %

```

\settcellcenter Typeset (recursively) cells of text centered.

```

9036 \def\settcellcenter #1{\def\edlabel##1{}%
9037     \let\edindex\nulledindex
9038     \ifx #1\` \ifnum\l@dcolcount=0 \let\Next\relax%
9039     \else\l@dcolcount=0%
9040         \let\Next=\settcellcenter%
9041         \fi%
9042     \else \disabled@dtabfeet%
9043         \stepl@dcolcount%
9044         \disabled@notes%
9045         \setbox\hilfsbox=\hbox{#1}%
9046         \restore@notes%
9047         \letsforverteilen%
9048         \hskip 0.5\hifskip #1\hskip 0.5\hifskip%
9049         \hskip\edtabcolsep%
9050         \let\Next=\settcellcenter%
9051         \fi\Next}
9052 %
9053 %

```

```
\NEXT54 \let\NEXT=\relax
```

```

9055 %
9056 %

```

\setmrowright Typeset (recursively) rows of right justified math.

```

9057 \def\setmrowright #1\`{%
9058     \ifx #1& \let\NEXT\relax
9059     \else \centerline{\setmcellright #1&\&\&\\&}
9060     \let\NEXT=\setmrowright
9061     \fi\NEXT}
9062 %

```

\settowright Typeset (recursively) rows of right justified text.

```

9063 \def\settowright #1\\{%
9064   \ifx #1& \let\next\relax
9065   \else \centerline{\setcellright #1&\&\&\\}
9066     \let\next=\settowright
9067   \fi\next}
9068 %
9069 %

```

\setmrowleft Typeset (recursively) rows of left justified math.

```

9070 \def\setmrowleft #1\\{%
9071   \ifx #1& \let\next\relax
9072   \else \centerline{\setmcellleft #1&\&\&\\}
9073     \let\next=\setmrowleft
9074   \fi\next}
9075 %

```

\settowleft Typeset (recursively) rows of left justified text.

```

9076 \def\settowleft #1\\{%
9077   \ifx #1& \let\next\relax
9078   \else \centerline{\setcellleft #1&\&\&\\}
9079     \let\next=\settowleft
9080   \fi\next}
9081 %
9082 %

```

\setmrowcenter Typeset (recursively) rows of centered math.

```

9083 \def\setmrowcenter #1\\{%
9084   \ifx #1& \let\next\relax%
9085   \else \centerline{\setmcellcenter #1&\&\&\\}
9086     \let\next=\setmrowcenter
9087   \fi\next}
9088 %

```

\settowcenter Typeset (recursively) rows of centered text.

```

9089 \def\settowcenter #1\\{%
9090   \ifx #1& \let\next\relax
9091   \else \centerline{\setcellcenter #1&\&\&\\}
9092     \let\next=\settowcenter
9093   \fi\next}
9094 %
9095 %

```

```

\nullsetzen906 \newcommand{\nullsetzen}{%
907     \step1@dcolcount%
908     \l@dcolwidth=0pt%
909     \ifnum\l@dcolcount=30\let\NEXT\relax%
910         \l@dcolcount=0\relax
911     \else\let\NEXT\nullsetzen%
912     \fi\NEXT}
913
914 %

```

\edatleft \edatleft[$\langle math \rangle$] { $\langle symbol \rangle$ } { $\langle len \rangle$ }. Left $\langle symbol \rangle$, 2 $\langle len \rangle$ high with prepended $\langle math \rangle$ vertically centered.

```

9105 \newcommand{\edatleft}[3][\@empty]{%
9106     \ifx#1\@empty
9107         \vbox to 10pt{\vss\hbox{$\left.\rule{0pt}{#3} width0pt height #3
9108             depth 0pt \right. \$\hss}\vfil}
9109     \else
9110         \vbox to 4pt{\vss\hbox{$\left.\rule{#1pt}{#3} width0pt height #3
9111             depth 0pt \right. \$}\vfil}
9112     \fi}
9113 %

```

\edatright \edatright[$\langle math \rangle$] { $\langle symbol \rangle$ } { $\langle len \rangle$ }. Right $\langle symbol \rangle$, 2 $\langle len \rangle$ high with appended $\langle math \rangle$ vertically centered.

```

9114 \newcommand{\edatright}[3][\@empty]{%
9115     \ifx#1\@empty
9116         \vbox to 10pt{\vss\hbox{$\left.\rule{0pt}{#3} width0pt height #3
9117             depth 0pt \right. \$\hss}\vfil}
9118     \else
9119         \vbox to 4pt{\vss\hbox{$\left.\rule{#1pt}{#3} width0pt height #3
9120             depth 0pt \right. \$1}\vfil}
9121     \fi}
9122
9123 %

```

\edvertline \edvertline{ $\langle len \rangle$ } vertical line $\langle len \rangle$ high.

```

9124 \newcommand{\edvertline}[1]{\vbox to 8pt{\vss\hbox{\vrule height #1}\vfil}}
9125
9126 %

```

\edvertdots \edvertdots{ $\langle len \rangle$ } vertical dotted line $\langle len \rangle$ high.

```

9127 \newcommand{\edvertdots}[1]{\vbox to 1pt{\vss\vbox to #1%
9128     {\cleaders\hbox{$\m@th\hbox{.}\vbox to 0.5em{ }$}\vfil}}}
9129
9130 %

```

`\l@dtabaddcols \l@dtabaddcols{\langle startcol \rangle}{\langle endcol \rangle}` adds the widths of the columns $\langle startcol \rangle$ through $\langle endcol \rangle$ to `\edfilldimen`. It is a L^AT_EX style reimplementation of the original `\@add@`.

```

9131 \newcommand{\l@dtabaddcols}[2]{%
9132   \l@dcheckstartend{#1}{#2}%
9133   \ifl@dstartendok
9134     \setcounter{addcolcount}{#1}%
9135     \@whilenum {\value{addcolcount}<#2}\relax \do
9136       \advance\edfilldimen by \the\csname dcol\theaddcolcount\endcsname
9137       \advance\edfilldimen by \edtabcolsep
9138       \stepcounter{addcolcount}%
9139     \advance\edfilldimen by \the\csname dcol\theaddcolcount\endcsname
9140   \fi
9141 }
9142
9143 %

```

`\ifl@dstartendok \l@dcheckstartend{\langle startcol \rangle}{\langle endcol \rangle}` checks that the values of $\langle startcol \rangle$ and $\langle endcol \rangle$ are sensible. If they are then `\ifl@dstartendok` is set TRUE, otherwise it is set FALSE.

```

9144 \newif\ifl@dstartendok
9145 \newcommand{\l@dcheckstartend}[2]{%
9146   \l@dstartendoktrue
9147   \ifnum #1<\@ne
9148     \l@dstartendokfalse
9149     \led@err@LowStartColumn
9150   \fi
9151   \ifnum #2>30\relax
9152     \l@dstartendokfalse
9153     \led@err@HighEndColumn
9154   \fi
9155   \ifnum #1>#2\relax
9156     \l@dstartendokfalse
9157     \led@err@ReverseColumns
9158   \fi
9159 }
9160
9161 %

```

`\edrowfill \edrowfill{\langle startcol \rangle}{\langle endcol \rangle}fill` fills columns $\langle startcol \rangle$ to $\langle endcol \rangle$ inclusive with `\@edrowfill@ {fill}` (e.g. `\hrulefill`, `\upbracefill`). This is a L^AT_EX style reimplementation and generalization of the original `\waklam`, `\Waklam`, `\waklamec`, `\wastricht` and `\wapunktel` macros.

```

9162 \newcommand*{\edrowfill}[3]{%
9163   \l@dtabaddcols{#1}{#2}%
9164   \hb@xt@ \the\l@dcolwidth{\hb@xt@ \the\edfilldimen{#3}\hss}%
9165   \let\@edrowfill@\edrowfill
9166   \def\@EDROWFILL@#1#2#3{\@edrowfill@{#1}{#2}{#3}}%

```

```
9167 %
9168 %
```

\edbeforetab The macro `\edbeforetab{text}{{math}}` puts *text* at the left margin before array cell entry *math*. Conversely, the macro `\edaftertab{math}{{text}}` puts *text* at the right margin after array cell entry *math*. `\edbeforetab` should be in the first column and `\edaftertab` in the last column. The following macros support these.

\leftltab `\leftltab{text}` for `\edbeforetab` in `\ltab`.

```
9169 \newcommand{\leftltab}[1]{%
9170   \hb@xt@z@{\vbox{\edtabindent%
9171     \moveleft\Hilfsskip\hbox{\#1}\hss}}%
9172 %
9173 %
```

\leftrrtab `\leftrrtab{text}{{math}}` for `\edbeforetab` in `\rtab`.

```
9174 \newcommand{\leftrrtab}[2]{%
9175   #2\hb@xt@z@{\vbox{\edtabindent%
9176     \advance\Hilfsskip by\dcoli%
9177     \moveleft\Hilfsskip\hbox{\#1}\hss}}%
9178 %
9179 %
```

\leftctab `\leftctab{text}{{math}}` for `\edbeforetab` in `\ctab`.

```
9180 \newcommand{\leftctab}[2]{%
9181   \hb@xt@z@{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
9182     \advance\Hilfsskip by 0.5\dcoli%
9183     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9184       \disablel@tabfeet$\displaystyle{##2}$%
9185       \advance\Hilfsskip by -0.5\wd\hilfsbox%
9186       \moveleft\Hilfsskip\hbox{\#1}\hss}%
9187     #2}%
9188 %
9189 %
```

\rightctab `\rightctab{{math}}{text}` for `\edaftertab` in `\ctab`.

```
9190 \newcommand{\rightctab}[2]{%
9191   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9192     \disablel@tabfeet#2\l@dampcount=\l@dcolcount%
9193     #1\hb@xt@z@{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
9194       \advance\Hilfsskip by 0.5\l@dcolwidth%
9195       \advance\Hilfsskip by -\wd\hilfsbox%
9196       \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9197         \disablel@tabfeet$\displaystyle{##1}$%
9198         \advance\Hilfsskip by -0.5\wd\hilfsbox%
```

```

9199   \advance\Hilfsskip by \edtabcolsep%
9200   \moveright\Hilfsskip\hbox{ #2}\hss}%
9201 }
9202
9203 %

```

\rightltab \rightltab{\langle math\rangle}{\langle text\rangle} for \edaftertab in \ltab.

```

9204 \newcommand{\rightltab}[2]{%
9205   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9206   \disablel@dtabfeet#2}\l@dampcount=\l@dcollcount%
9207   #1\hb@xt@z@\vbox{\edtabindent\l@dcollcount=\l@dampcount%
9208   \advance\Hilfsskip by\l@dcollwidth%
9209   \advance\Hilfsskip by-\wd\hilfsbox%
9210   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9211   \disablel@dtabfeet$\displaystyle{#1}$}%
9212   \advance\Hilfsskip by-\wd\hilfsbox%
9213   \advance\Hilfsskip by\edtabcolsep%
9214   \moveright\Hilfsskip\hbox{ #2}\hss}%
9215 }
9216
9217 %

```

\rightrtab \rightrtab{\langle math\rangle}{\langle text\rangle} for \edaftertab in \rtab.

```

9218 \newcommand{\rightrtab}[2]{%
9219   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
9220   \disablel@dtabfeet#2}%
9221   #1\hb@xt@z@\vbox{\edtabindent%
9222   \advance\Hilfsskip by-\wd\hilfsbox%
9223   \advance\Hilfsskip by\edtabcolsep%
9224   \moveright\Hilfsskip\hbox{ #2}\hss}%
9225 }
9226
9227 %

```

\rtab \rtab{\langle body\rangle} typesets *body* as an array with the entries right justified.

\edbforetab The process is first to measure the *body* to get the column widths, and then in a
\edaftertab second pass to typeset the body.

```

9228 \newcommand{\rtab}[1]{%
9229   \l@dnnullfills
9230   \def\edbforetab##1##2{\leftrtab{##1}{##2}%
9231   \def\edaftertab##1##2{\rightrtab{##1}{##2}%
9232   \measurebody{#1}%
9233   \l@drestorefills
9234   \variab
9235   \setmrowright #1\&\\%
9236   \enablel@dtabfeet}
9237
9238 %

```

\measurembody `\measurembody{\langle body \rangle}` measures the array `\langle body \rangle`.

```

9239  \newcommand{\measurembody}[1]{%
9240    \disable@dtabfeet%
9241    \l@dcollcount=0%
9242    \nullsetzen%
9243    \l@dcollcount=0%
9244    \measuremrow #1\\&\\%
9245    \global\l@dampcount=1}
9246
9247 %

```

\ratabtext `\ratabtext{\langle body \rangle}` typesets `\langle body \rangle` as a tabular with the entries right justified.

```

9248  \newcommand{\ratabtext}[1]{%
9249    \l@dnnullfills
9250    \measuretbody{#1}%
9251    \l@drestorefills
9252    \variab
9253    \settowright #1\\&\\%
9254    \enable@dtabfeet}
9255
9256 %

```

\measuretbody `\measuretbody{\langle body \rangle}` measures the tabular `\langle body \rangle`.

```

9257  \newcommand{\measuretbody}[1]{%
9258    \disable@notes%
9259    \disable@dtabfeet%
9260    \l@dcollcount=0%
9261    \nullsetzen%
9262    \l@dcollcount=0%
9263    \measuretrow #1\\&\\%
9264    \restore@notes%
9265    \global\l@dampcount=1}
9266
9267 %

```

\ltab Array with entries left justified.

```

\edbeforetab 9268 \newcommand{\ltab}[1]{%
\edaftertab 9269 \l@dnnullfills
9270    \def\edbeforetab##1##2{\leftltab{##1}{##2}}%
9271    \def\edaftertab##1##2{\rightltab{##1}{##2}}%
9272    \measurebody{#1}%
9273    \l@drestorefills
9274    \variab
9275    \setmrowleft #1\\&\\%
9276    \enable@dtabfeet}
9277
9278 %

```

\latabtext Tabular with entries left justified.

```

9279 \newcommand{\latabtext}[1]{%
9280   \l@dnnullfills
9281   \measuretbody{#1}%
9282   \l@drestorefills
9283   \variab
9284   \setrowleft #1\\&\\%
9285   \enablel@dtabfeet}
9286 %
9287 %

```

\ctab Array with centered entries.

```

\edbeforetab 9288 \newcommand{\ctab}[1]{%
\edaftertab 9289   \l@dnnullfills
9290   \def\edbeforetab##1##2{\leftctab{##1}{##2}}%
9291   \def\edaftertab##1##2{\rightctab{##1}{##2}}%
9292   \measurebody{#1}%
9293   \l@drestorefills
9294   \variab
9295   \setmrowcenter #1\\&\\%
9296   \enablel@dtabfeet}
9297 %
9298 %

```

\ctabtext Tabular with entries centered.

```

9299 \newcommand{\ctabtext}[1]{%
9300   \l@dnnullfills
9301   \measuretbody{#1}%
9302   \l@drestorefills
9303   \variab
9304   \setrowcenter #1\\&\\%
9305   \enablel@dtabfeet}
9306 %
9307 %

```

```

\spreadtext 908 \newcommand{\spreadtext}[1]{%\l@dcollcount=\l@dampcount%
9309   \hb@xt@ \the\l@dcollwidth{\hbox{#1}\hss}}
9310 %

```

```

\spreadmath 911 \newcommand{\spreadmath}[1]{%
9312   \hb@xt@ \the\l@dcollwidth{\hbox{$\displaystyle{#1}$}\hss}}
9313 %
9314 %

```

\HILFSskip More helpers.
\Hilfsskip

```

9315 \newskip\HILFSskip
9316 \newskip\Hilfsskip
9317 %
9318 %

```

```

\EDTABINDENT19 \newcommand{\EDTABINDENT}{%
9320   \ifnum\l@dcollcount=30\let\NEXT\relax\l@dcollcount=0%
9321   \else\step\l@dcollcount%
9322     \advance\Hilfsskip by\l@dcollwidth%
9323     \ifdim\l@dcollwidth=0pt\advance\hilfscount\@ne
9324     \else\advance\Hilfsskip by \the\hilfscount\edtabcolsep%
9325     \hilfscount=1\fi%
9326     \let\NEXT=\EDTABINDENT%
9327   \fi\NEXT}%
9328 %

```

\edtabindent (was \tabindent)

```

9329 \newcommand{\edtabindent}{%
9330   \l@dcollcount=0\relax
9331   \Hilfsskip=0pt%
9332   \hilfscount=1\relax
9333   \EDTABINDENT%
9334   \hilfsskip=\hspace{%
9335   \advance\hilfsskip -\Hilfsskip%
9336   \Hilfsskip=0.5\hilfsskip%
9337 }%
9338 %
9339 %

```

\EDTAB (was \TAB)

```

9340 \def\EDTAB #1|#2|{%
9341   \setbox\tabhilfbox=\hbox{$\displaystyle{#1}$}%
9342   \setbox\tabHilfbox=\hbox{$\displaystyle{#2}$}%
9343   \advance\tabelskip -\wd\tabhilfbox%
9344   \advance\tabelskip -\wd\tabHilfbox%
9345   \unhbox\tabhilfbox\hskip\tabelskip%
9346   \unhbox\tabHilfbox}%
9347 %
9348 %

```

\EDTABtext (was \TABtext)

```

9349 \def\EDTABtext #1|#2|{%
9350   \setbox\tabhilfbox=\hbox{\#1}%
9351   \setbox\tabHilfbox=\hbox{\#2}%
9352   \advance\tabelskip -\wd\tabhilfbox%
9353   \advance\tabelskip -\wd\tabHilfbox%

```

```

9354   \unhbox\tabhilfbox\hskip\tabelskip%
9355   \unhbox\tabHilfbox}%
9356 %

```

\tabhilfbox Further helpers.

```

\tabHilfbox
9357 \newbox\tabhilfbox
9358 \newbox\tabHilfbox
9359 %
9360 %

```

XXXII.2.4 Environments

edarrayl edarrayc edarrayr The ‘environment’ forms for \ltab, \ctab and \rtab.

```

9361 \newenvironment{edarrayl}{\l@ddcollect@body\ltab}{}
9362 \newenvironment{edarrayc}{\l@ddcollect@body\ctab}{}
9363 \newenvironment{edarrayr}{\l@ddcollect@body\rtab}{}
9364 %
9365 %

```

edtabularl edtabularc edtabularr The ‘environment’ forms for \ltabtext, \ctabtext and \rtabtext.

```

9366 \newenvironment{edtabularl}{\l@ddcollect@body\ltabtext}{}
9367 \newenvironment{edtabularc}{\l@ddcollect@body\ctabtext}{}
9368 \newenvironment{edtabularr}{\l@ddcollect@body\rtabtext}{}
9369 %
9370 %

```

XXXIII Quotation's commands

\initnumbering@quote This macro, called at the beginning of any numbered section, locally redefines the quotation and quote environments, in order to allow their use inside of numbered sections.

```

\quotation \initnumbering@quote defines quotation environment.
\endquotation
\quote
\endquote
9371 \newcommand{\initnumbering@quote}{
9372   \ifnoquotation@\else
9373     \renewcommand{\quotation}{\par\leavevmode%
9374       \parindent=1.5em%
9375       \skipnumbering%
9376       \ifautopar%
9377         \vskip-\parskip%
9378       \else%
9379         \vskip\topsep%
9380       \fi%
9381     \global\leftskip=\leftmargin%

```

```

9382           \global\rightskip=\leftmargin%
9383       }
9384   \renewcommand{\endquotation}{\par%
9385     \global\leftskip=0pt%
9386     \global\rightskip=0pt%
9387     \leavevmode%
9388     \skipnumbering%
9389     \ifautopar%
9390       \vskip-\parskip%
9391     \else%
9392       \vskip\topsep%
9393     \fi%
9394   }
9395   \renewcommand{\quote}{\par\leavevmode%
9396     \parindent=0pt%
9397     \skipnumbering%
9398     \ifautopar%
9399       \vskip-\parskip%
9400     \else%
9401       \vskip\topsep%
9402     \fi%
9403     \global\leftskip=\leftmargin%
9404     \global\rightskip=\leftmargin%
9405   }
9406   \renewcommand{\endquote}{\par%
9407     \global\leftskip=0pt%
9408     \global\rightskip=0pt%
9409     \leavevmode%
9410     \skipnumbering%
9411     \ifautopar%
9412       \vskip-\parskip%
9413     \else%
9414       \vskip\topsep%
9415     \fi%
9416   }
9417   \fi
9418 }
9419 %

```

XXXIV Section's title commands

XXXIV.1 Commands to disable some feature

`\ledsectnotoc` The `\ledsectnotoc` only disables the `\addcontentsline` macro.

```

9420 \newcommand{\ledsectnotoc}{\let\addcontentsline\@gobblethree}
9421 %

```

`\ledsectnomark` The `\ledsectnomark` only disables the `\chaptermark`, `\sectionmark` and `\subsectionmark` macros.

```

9422 \newcommand{\ledsectnomark}{%
9423   \let\chaptermark\@gobble%
9424   \let\sectionmark\@gobble%
9425   \let\subsectionmark\@gobble%
9426 }
9427 %

```

XXXIV.2 General overview

The system of `\eledxxxx` commands to section text work like this:

1. When one of these commands is called, `reledmac` writes to an auxiliary files:
 - The section level.
 - The section title.
 - The side (when `reledpar` is used).
 - The pstart where the command is called.
 - If we have starred version or not.
2. `reledmac` adds the title of the section to pstart, as normal content. This is to enable critical notes.
3. When `TeX` is run a other time, this file is read. That:
 - Adds the pstart number to a list of pstarts where a sectioning command is used.
 - Defines a command, the name of which contains the pstart number, and which calls the normal `TeX` sectioning command.
4. This last command is called when the pstart is effectively printed.

XXXIV.3 `\beforeeledchapter` command

We do not define commands for `\eledsection` and related if the `noeledsec` option is loaded. We use `etoolbox` tests and not the `\ifxxx... \else... \fi` structure to prevent problem of expansions with command after the `\ifxxx` which contains `\fi`. As we patch command inside this test, we need to change the category code of `#` character *before* `\notbool` statement, because the second argument is read with the standard catcode (read *The TeXbook* to understand when the catcode's change has effect).

```

9428 \catcode`\#=12
9429 \notbool{@noeled@sec}{%
9430 %

```

\beforeeledchapter For technical reasons, not yet solved, page-breaking before chapters can't be made automatically by eledmac. Users have to use **\beforeeledchapter**.

```

9431 \ifl@dmemoir
9432   \newcommand\beforeeledchapter{%
9433   \clearforchapter%
9434 }
9435 \else
9436   \newcommand\beforeeledchapter{%
9437   \if@openright%
9438   \cleardoublepage%
9439 \else%
9440   \clearpage%
9441 \fi%
9442 }
9443 \fi
9444 %

```

XXXIV.4 Auxiliary commands

nt@leftmargin@eledsection **t@rightmargin@eledsection** **\print@leftmargin@eledsection** and **\print@rightmargin@eledsection** are added by reledmac inside the code of sectioning command, in order to affix lines numbers. They include tests for RTL languages.

```

9445 \def\print@rightmargin@eledsection{%
9446   \if@eled@sectioning%
9447   \begingroup%
9448   \if@RTL%
9449     \let\llap\rlap%
9450     \let\leftlinenum\rightlinenum%
9451     \let\leftlinenumR\rightlinenumR%
9452     \let\l@drd@ta\l@dld@ta%
9453     \let\l@drsn@te\l@dlsn@te%
9454   \fi%
9455   \hfill\l@drd@ta \csuse{LR}{\l@drsn@te}%
9456   \endgroup%
9457   \fi%
9458 }%
9459
9460 \def\print@leftmargin@eledsection{%
9461   \if@eled@sectioning%
9462   \leavevmode%
9463   \begingroup%
9464   \if@RTL%
9465     \let\rlap\llap%
9466     \let\rightlinenum\leftlinenum%
9467     \let\rightlinenumR\leftlinenumR%
9468     \let\l@dld@ta\l@drd@ta%
9469     \let\l@dlsn@te\l@drsn@te%
9470   \fi%

```

```

9471   \l@ldld@ta\csuse{LR}{\l@ldsn@te}%
9472   \endgroup%
9473   \fi%
9474 }%
9475 %
9476 %

```

XXXIV.5 Patching standard commands

We have to patch L^AT_EX, book and memoir sectioning commands in order to:

- Disable \edtext inside.
- Disable page breaking (for \chapter).
- Add line numbers and sidenotes.

\@sect

Unfortunately, Maïeul Rouquette was not able to try if `memoir` is loaded. That is why `eledmac` tries to define for both standard class and `memoir` class.

```

9477 \AtBeginDocument{%
9478
9479
9480 \pretocmd{\M@sect}{%
9481   {\let\old@edtext=\edtext%
9482   \let\edtext=\dummy@edtext@showlemma%
9483   }
9484   {}
9485   {}}
9486
9487 \apptocmd{\M@sect}{%
9488   {\let\edtext=\old@edtext}
9489   {}
9490   {}}
9491
9492 \patchcmd{\M@sect}{%
9493   { #9}
9494   { #9%
9495   \print@rightmargin@eledsection%
9496   }
9497   {}
9498   {}}
9499
9500 \patchcmd{\M@sect}{%
9501   {\hskip #3\relax}
9502   {\hskip #3\relax%
9503   \print@leftmargin@eledsection%
9504   }
9505   {}
9506   {}}

```

```

9507
9508 \patchcmd{\@mem@old@ssect}
9509   {#5}
9510   {#5%
9511   \print@leftmargin@eledsection%
9512   }
9513   {}
9514   {}
9515
9516 \patchcmd{\@mem@old@ssect}
9517   {\hskip #1}
9518   {\hskip #1%
9519   \print@rightmargin@eledsection%
9520   }
9521   {}
9522   {}
9523
9524
9525
9526 \patchcmd{\scr@startchapter}{\if@openright\cleardoublepage\else\clearpage\
9527 fi}{%
9528   \if@eled@sectioning\else%
9529   \ifl@printingpages\else%
9530   \if@openright\cleardoublepage\else\clearpage\fi%No clearpage inside a
9531   \Pages: will keep critical notes from printing on the title page. Here for
9532   \scrbook.
9533   \fi%
9534   \fi%
9535   }
9536 \patchcmd{\@makechapterhead}
9537   {#1}
9538   {\print@leftmargin@eledsection%
9539   #1%
9540   \print@rightmargin@eledsection%
9541   }
9542   {}
9543   {}
9544
9545 \patchcmd{\@makechapterhead}{% For BIDI
9546   {\if@RTL\raggedleft\else\raggedright\fi}%
9547   {\if@eled@sectioning\else%
9548   \if@RTL\raggedleft\else\raggedright\fi%
9549   \fi%
9550   }%
9551   {}%
9552   {}%
9553

```

```

9554 \patchcmd{\@makeschapterhead}
9555   {#1}
9556   {\print@leftmargin@eledsection%
9557     #1%
9558     \print@rightmargin@eledsection%
9559   }
9560   {}
9561   {}
9562
9563 \preto{\@sect}{%
9564   {\let\old@edtext=\edtext
9565   \let\edtext=\dummy@edtext@showlemma%
9566   }
9567   {}
9568   {}
9569
9570 \appto{\@sect}{%
9571   {\let\edtext=\old@edtext}
9572   {}
9573   {}
9574
9575 \preto{\@ssect}{%
9576   {\let\old@edtext=\edtext%
9577   \let\edtext=\dummy@edtext@showlemma%
9578   }
9579   {}
9580   {}
9581
9582 \appto{\@ssect}{%
9583   {\let\edtext=\old@edtext}
9584   {}
9585   {}
9586
9587 %

```

`hyperref` also redefines `\@sect`. That is why, when manipulating arguments, we patch `\@sect` and the same only if `hyperref` is not used. If it is, we patch the `\NR` commands.

```

9588 \@ifpackageloaded{nameref}{%
9589
9590   \patchcmd{\NR@sect}{%
9591     {#8}
9592     {#8%
9593     \print@rightmargin@eledsection%
9594   }
9595   {}
9596   {}
9597
9598   \patchcmd{\NR@sect}{%
9599     {\hskip #3\relax}
9600     {\hskip #3\relax%
```

```
9601     \print@leftmargin@eledsection%
9602     }
9603     {}
9604     {}

9605     \patchcmd{\NR@ssect}
9606       {#5}
9607       {#5%
9608       \print@rightmargin@eledsection%
9609       }
9610       {}
9611       {}
9612       {}

9613     \patchcmd{\NR@ssect}
9614       {\hskip #1}
9615       {\hskip #1%
9616       \print@leftmargin@eledsection%
9617       }
9618       {}
9619       {}
9620       {}

9621   }%
9622   {
9623     \patchcmd{\@sect}
9624       {#8}
9625       {#8%
9626       \print@rightmargin@eledsection%
9627       }
9628       {}
9629       {}

9630     \patchcmd{\@sect}
9631       {\hskip #3\relax}
9632       {\hskip #3\relax%
9633       \print@leftmargin@eledsection%
9634       }
9635       {}
9636       {}
9637       {}

9638     \patchcmd{\@ssect}
9639       {#5}
9640       {#5%
9641       \print@rightmargin@eledsection%
9642       }
9643       {}
9644       {}
9645       {}

9646     \patchcmd{\@ssect}
9647       {\hskip #1}
9648       {\hskip #1%
9649       \print@leftmargin@eledsection%
```

```

9651   }
9652   {}
9653   {}
9654   }%
9655 }%
9656 %

```

Close the `\notbool{@noeled@sec}` statement. Also, we have finished patching the commands, using # with a catcode equal to 12, so we are restoring the normal catcode for #.

```

9657 {}}%
9658 \protect\catcode`\#=6 %Space NEEDS by \catcode
9659 %

```

\chapter We patch the `\chapter` command even if the `noeledsec` option is called, because we can use `\chapter` in the optional argument of a `\pstart` in parallel typesetting.

```

9660 \AtBeginDocument{%
9661 \patchcmd{\chapter}{\clearforchapter}{%
9662 \if@eled@sectioning\else%
9663 \ifl@dprintingpages\else%
9664 \clearforchapter%
9665 \fi%
9666 \fi%
9667 }%
9668 {}%
9669 {}%
9670
9671 \patchcmd{\chapter}{\if@openright\cleardoublepage\else\clearpage\fi}{%
9672 \if@eled@sectioning\else%
9673 \ifl@dprintingpages%
9674 \endgraf%
9675 \else%
9676 \if@openright\cleardoublepage\else\clearpage\fi%No clearpage inside a
9677 \Pages: will keep critical notes from printing on the title page. Here for
9678 classical classes
9679 \fi%
9680 \fi%
9681 {}%
9682 }%
9683 %

```

\if@eled@sectioning The boolean `\if@eled@sectioning` is set to true when a sectioning command is called by a `\eledxxx` command, and set to false after. It is used to enable/disable line number printing.

```

9684 \newif\if@eled@sectioning%
9685 %

```

We reopen a new `\notbool{@noeled@sec}` statement, as we will define the `\eleselection` commands.

```
9686 \notbool{@noeled@sec}{%
9687 %
```

XXXIV.6 Main code of \eledxxx commands

`\eled@sectioning@out` `\eled@sectioning@out` is the output file, to dump the pstarts where a sectioning command is used.

```
9688 \newwrite\eled@sectioning@out
9689 %
```

`\eledchapter` And now, the user sectioning commands, which write to the file, and also add content
`\eledsection` as a “normal” line.

```
\eledsubsection
9690 \newcommand{\eledchapter}[2][]{%
9691   \disable@familiarnotes%
9692   \#2%
9693   \restore@familiarnotes%
9694   \ifledRcol%
9695     \immediate\write\eled@sectioning@out{%
9696       \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{}{R}%
9697     }%
9698   \else%
9699     \immediate\write\eled@sectioning@out{%
9700       \string\eled@chapter{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{}{R}%
9701     }%
9702   \fi%
9703 }
9704
9705 \newcommand{\eledsection}[2][]{%
9706   \disable@familiarnotes%
9707   \#2%
9708   \restore@familiarnotes%
9709   \ifledRcol%
9710     \immediate\write\eled@sectioning@out{%
9711       \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpstartsR}{}{R}%
9712     }%
9713   \else%
9714     \immediate\write\eled@sectioning@out{%
9715       \string\eled@section{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{}{R}%
9716     }%
9717   \fi%
9718 }
9719
9720 \newcommand{\eledsubsection}[2][]{%
9721   \disable@familiarnotes%
9722   \#2%
```

```

9723   \restore@familiarnotes%
9724   \ifledRcol%
9725     \immediate\write\eled@sectioningR@out{%
9726       \string\eled@subsection{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsR}{\#R}
9727     }
9728   }%
9729   \else%
9730     \immediate\write\eled@sectioningR@out{%
9731       \string\eled@subsection{\#1}{\unexpanded{\#2}}{\the\pstarts@read@L}{\#P}
9732     }%
9733   \fi%
9734 } \newcommand{\eledsubsubsection}[2] [] {%
9735   \disable@familiarnotes%
9736   \#2%
9737   \restore@familiarnotes%
9738   \ifledRcol%
9739     \immediate\write\eled@sectioningR@out{%
9740       \string\eled@subsubsection{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsR}
9741     }%
9742   \else%
9743     \immediate\write\eled@sectioningR@out{%
9744       \string\eled@subsubsection{\#1}{\unexpanded{\#2}}{\the\pstarts@read@L}
9745     }%
9746   \fi%
9747 }
9748
9749 \WithSuffix\newcommand\eledchapter*[2] [] {%
9750   \disable@familiarnotes%
9751   \#2%
9752   \restore@familiarnotes%
9753   \ifledRcol%
9754     \immediate\write\eled@sectioningR@out{%
9755       \string\eled@chapter{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsR}{\#R}
9756     }%
9757   \else%
9758     \immediate\write\eled@sectioningR@out{%
9759       \string\eled@chapter{\#1}{\unexpanded{\#2}}{\the\pstarts@read@L}{\#P}
9760     }%
9761   \fi%
9762 }
9763 \WithSuffix\newcommand\eledsection*[2] [] {%
9764   \disable@familiarnotes%
9765   \#2%
9766   \restore@familiarnotes%

```

```

9769   \ifledRcol%
9770     \immediate\write\eled@sectioningR@out{%
9771       \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpstsr}{*}{R}%
9772     }%
9773   \else%
9774     \immediate\write\eled@sectioning@out{%
9775       \string\eled@section{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{*}{}
9776     }%
9777   \fi%
9778 }
9779
9780 \WithSuffix\newcommand\eledsubsection*[2] [] {%
9781   \disable@familiarnotes%
9782   #2%
9783   \restore@familiarnotes%
9784   \ifledRcol%
9785     \immediate\write\eled@sectioningR@out{%
9786       \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dnumpstsr}{*}{R}%
9787     }%
9788   \else%
9789     \immediate\write\eled@sectioning@out{%
9790       \string\eled@subsection{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{*}{}
9791     }%
9792   \fi%
9793 }
9794
9795 \WithSuffix\newcommand\eledsubsubsection*[2] [] {%
9796   \disable@familiarnotes%
9797   #2%
9798   \restore@familiarnotes%
9799   \ifledRcol%
9800     \immediate\write\eled@sectioningR@out{%
9801       \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dnumpstsr}{*}{R}%
9802     }%
9803   \else%
9804     \immediate\write\eled@sectioning@out{%
9805       \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\pstarts@read@L}{*}{}
9806     }%
9807   \fi%
9808 }
9809 %

```

XXXIV.7 Macros written in the auxiliary file

\eled@chapter The sectioning macros, called in the auxiliary file. They have five arguments:

\eled@section

\eled@subsection

\eled@subsubsection

1. Optional arguments of L^AT_EX sectioning command.
2. Mandatory arguments of L^AT_EX sectioning command.
3. Pstart number.
4. Side: R if right, nothing if left.
5. Starred or not.

```

9810 \def\eled@chapter#1#2#3#4#5{%
9811   \ifstrempty{#4}%
9812     {%
9813       \ifstrempty{#1}%
9814         {%
9815           \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\%
9816             chapter[#2]}%
9817             \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{} \chattermark\%
9818               [#2]}%
9819             }%Need for \pairs, because of using parbox.
9820             \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\%
9821               chapter[#1] [#2]}%
9822             \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{} \chattermark\%
9823               [#2]}%Need for \pairs, because of using parbox.
9824             }%
9825             \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\%
9826               chapter*{#2}}%
9827             \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\%
9828               chapter*[#1] [#2]}%Bug in LaTeX!
9829             }%
9830   \listcsgadd{eled@sections#5@0}{#3}%
9831 }
9832 \def\eled@section#1#2#3#4#5{%
9833   \ifstrempty{#4}%
9834     {\ifstrempty{#1}%
9835       {%
9836         \csgdef{eled@sectioning@#3#5}{\section{#2}}%
9837         \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{} \sectionmark\%
9838           [#2]}%Need for \pairs, because of using parbox.
9839         }%
9840         \csgdef{eled@sectioning@#3#5}{\section[#1] [#2]}%
9841         \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{} \sectionmark\%
9842           [#1]}%Need for \pairs, because of using parbox.
9843         }%
9844       }%
9845     }%
9846   }%
9847 }
```

```

9842 {\ifstrempty{#1}%
9843   {\csgdef{eled@sectioning@#3#5}{\section*{[#2]}}%
9844   {\csgdef{eled@sectioning@#3#5}{\section*[#1]{#2}}}}%Bug in LaTeX!
9845 }
9846 \listcsgadd{eled@sections#5@0}{#3}%
9847 }
9848 \def\eled@subsection#1#2#3#4#5{%
9849   \ifstrempty{#4}%
9850     {\ifstrempty{#1}%
9851       {%
9852         {\csgdef{eled@sectioning@#3#5}{\subsection{[#2]}}%
9853         {\csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext}\csuse{%
9854           subsectionmark}{#2}}}}%Need for \pairs, because of using parbox. \csuse in
9855           case of \subsectionmark is not defined (book)
9856       }%
9857       {%
9858         {\csgdef{eled@sectioning@#3#5}{\subsection*[#1]{#2}}}}%
9859         {\csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext}\csuse{%
9860           subsectionmark}{#1}}}}%Need for \pairs, because of using parbox. \csuse in
9861           case of \subsectionmark is not defined (book)
9862       }%
9863     }%
9864   \listcsgadd{eled@sections#5@0}{#3}%
9865 }
9866 \def\eled@subsubsection#1#2#3#4#5{%
9867   \ifstrempty{#4}%
9868     {\ifstrempty{#1}%
9869       {%
9870         {\csgdef{eled@sectioning@#3#5}{\subsubsection{[#2]}}%
9871         {\csgdef{eled@sectioning@#3#5}{\subsubsection*[#1]{#2}}}}}}%Bug in LaTeX!
9872     }%
9873   \listcsgadd{eled@sections#5@0}{#3}%
9874 }
9875 }
9876 \listcsgadd{eled@sections#5@0}{#3}%
9877 }
9878 %

```

End of the conditional test about `noeledsec` option.

```

9880 }{}%
9881 %

```

XXXV Page breaking or no page breaking depending of specific lines

By default, page breaks are automatic. However, the user can define lines which will force page breaks, or prevent page breaks around one specific line. On the first run, the line-list file records the line number of where the page break is being changed (either forced, or prevented). On the next run, page breaks occur either before or after this line, depending on how the user sets the command. The default setting is after the line.

`\normal@page@break` `\normal@page@break` is an etoolbox list which contains the absolute line number of the last line, for each page.

```
9882 \def\normal@page@break{}  
9883 %
```

`\prev@pb` The `\l@prev@pb` macro is a etoolbox list, which contains the lines in which page breaks occur (before or after). The `\l@prev@nopb` macro is a etoolbox list, which contains the lines with NO page break before or after.

```
9884 \def\l@prev@pb{}  
9885 \def\l@prev@nopb{}  
9886 %
```

`\ledpb` The `\ledpb` macro writes the call to `\led@pb` in line-list file. The `\ledpbnum` macro writes the call to `\led@pbnum` in line-list file. The `\lednompb` macro writes the call to `\led@nompb` in line-list file. The `\lednopbnum` macro writes the call to `\led@nopbnum` in line-list file.

```
9887 \newcommand{\ledpb}{\write\linenum@out{\string\led@pb}}  
9888 \newcommand{\ledpbnum}[1]{\write\linenum@out{\string\led@pbnum{#1}}}  
9889 \newcommand{\lednompb}{\write\linenum@out{\string\led@nompb}}  
9890 \newcommand{\lednopbnum}[1]{\write\linenum@out{\string\led@nopbnum{#1}}}  
9891 %
```

`\led@pb` The `\led@pb` adds the absolute line number in the `\prev@pb` list. The `\led@pbnum` adds the argument in the `\prev@pb` list. The `\led@nompb` adds the absolute line number in the `\prev@nopb` list. The `\led@nopbnum` adds the argument in the `\prev@nopb` list.

```
9892 \newcommand{\led@pb}{\listxadd{\l@prev@pb}{\the\absline@num}}  
9893 \newcommand{\led@pbnum}[1]{\listxadd{\l@prev@pb}{#1}}  
9894 \newcommand{\led@nompb}{\listxadd{\l@prev@nompb}{\the\absline@num}}  
9895 \newcommand{\led@nopbnum}[1]{\listxadd{\l@prev@nompb}{#1}}  
9896 %
```

`\ledpbsetting` The `\ledpbsetting` macro only changes the value of `\led@pb@macro`, for which the default value is before.

```
9897 \def\led@pb@setting{before}  
9898 \newcommand{\ledpbsetting}[1]{\gdef\led@pb@setting{#1}}  
9899 %
```

\led@check@pb The \led@check@pb and \led@check@nopb are called before or after each line. They check if a page break must occur, depending on the current line and on the content of \l@pb.

```

9900 \newcommand{\led@check@pb}{\xifinlist{\the\absline@num}{\l@prev@pb}{\
9901   pagebreak[4]}{}}
9902 \newcommand{\led@check@nopb}{%
9903   \IfStrEq{\led@pb@setting}{before}{%
9904     \xifinlist{\the\absline@num}{\l@prev@nopb}{%
9905       {\numdef{\abs@prevline}{\the\absline@num-1}}%
9906       \xifinlist{\abs@prevline}{\normal@page@break}{%
9907         {\nopagebreak[4]\enlargethispage{\baselineskip}}% 
9908         {}}% 
9909       {}% 
9910     }%
9911   \IfStrEq{\led@pb@setting}{after}{%
9912     \xifinlist{\the\absline@num}{\l@prev@nopb}{%
9913       \xifinlist{\the\absline@num}{\normal@page@break}{%
9914         {\nopagebreak[4]\enlargethispage{\baselineskip}}% 
9915         {}% 
9916     }%
9917     {}% 
9918   }%
9919 }%
9920 }
9921 %

```

XXXVI Long verse: prevents being separated by a page break

\iflednopbinverse The \lednopbinverse boolean is set to false by default. If set to true, reledmac will automatically prevent page breaks inside verse. The declaration is made at the beginning of the file, because it is used as a package option.

\check@pb@in@verse The \check@pb@in@verse checks if a verse is broken in two page. If true, it adds:

- The absolute line number of the first line of the verse -1 in the \led@pb list, if the page break must occur before the verse.
- The absolute line number of the first line of the verse -1 in the \led@nopb list, if the page break must occur after the verse.

```

9922 \newcommand{\check@pb@in@verse}{%
9923   \ifinstanza\iflednopbinverse\ifinserthangingsymbol% Using stanzas and
9924   enabling page breaks in verse control, while on a hanging verse.
9925   \ifnum\page@num=\last@page@num\else%If we have change page
9926     \IfStrEq{\led@pb@setting}{before}{%

```

```

9926      \numgdef{\abs@line@verse}{\the\absline@num-1}%
9927      \ledpbnum{\abs@line@verse}%
9928      }{}%
9929      \IfStrEq{\led@pb@setting}{after}{%
9930          \numgdef{\abs@line@verse}{\the\absline@num-1}%
9931          \lednopbnum{\abs@line@verse}%
9932          }{}%
9933          \fi%
9934          \fi\fi\fi%
9935      }
9936 %

```

XXXVII Tools for hyperref package

\Hy@raisedlink@left The hyperref package provides a \Hy@raisedlink command, to be used to add an anchor to the top of a line and not to the bottom of it.³⁸

However, this command disrupts the line breaking mechanism when it is called before any word. This is why reledmac defines \Hy@raisedlink@left that is called to the left of words, at the beginning of \edtext or inside the \edlabel commands.³⁹

```

9937 \def\Hy@raisedlink@left#1{%
9938     \ifvmode
9939         #1%
9940     \else
9941         \Hy@SaveSpaceFactor
9942         \llap{\smash{%
9943             \begingroup
9944                 \let\HyperRaiseLinkLength\@tempdima
9945                 \setlength\HyperRaiseLinkLength\HyperRaiseLinkDefault
9946                 \HyperRaiseLinkHook
9947             \expandafter\endgroup
9948             \expandafter\raise\the\HyperRaiseLinkLength\hbox{%
9949                 \Hy@RestoreSpaceFactor
9950                 #1%
9951                 \Hy@SaveSpaceFactor
9952             }%
9953         }%
9954         \Hy@RestoreSpaceFactor
9955         \penalty\@M\hskip\z@\relax
9956     \fi
9957 }
9958 %

```

³⁸<http://tex.stackexchange.com/a/17138/7712>.

³⁹The code is inspired by an answer given by @unbonpetit. Thanks to him. <http://texnique.fr:80/osqa/questions/781/hyraisedlink-perturbe-la-maniere-dont-se-fait-la-coupure-de-ligne/801>.

XXXVIII Compatibility with eleedmac

Here, we define some commands for the eleedmac-compat option.

```

9959 \ifeledmaccompat@%
9960
9961 \newcommand{\footnormalX}[1]{\arrangementX[#1]{normal}}%
9962 \newcommand{\footparagraphX}[1]{\arrangementX[#1]{paragraph}}%
9963 \newcommand{\foottwocolX}[1]{\arrangementX[#1]{twocol}}%
9964 \newcommand{\footthreecolX}[1]{\XarrangementX[#1]{threecol}}%
9965
9966 \unless\ifnocritical@
9967   \newcommand{\footnormal}[1]{\Xarrangement[#1]{normal}}%
9968   \newcommand{\footparagraph}[1]{\Xarrangement[#1]{paragraph}}%
9969   \newcommand{\foottwocol}[1]{\Xarrangement[#1]{twocol}}%
9970   \newcommand{\footthreecol}[1]{\Xarrangement[#1]{threecol}}%
9971   \let\hsizetwocol\Xhsizetwocol
9972   \let\hsizethreecol\Xhsizethreecol
9973   \let\bhookXnote\Xbhooknote
9974   \let\boxsymlinenum\Xboxsymlinenum
9975   \let\symlinenum\Xsymlinenum
9976   \let\beforenumberinfofootnote\Xbeforenumber
9977   \let\afternumberinfofootnote\Xafternumber
9978   \let\beforeXsymlinenum\Xbeforesymlinenum
9979   \let\afterXsymlinenum\Xaftersymlinenum
9980   \let\inplaceofnumber\Xinplaceofnumber
9981   \let\Xlemmaseparator\lemmaseparator
9982   \let\afterlemmaseparator\Xafterlemmaseparator
9983   \let\beforelemmaseparator\Xbeforelemmaseparator
9984   \let\inplaceoflemmaseparator\Xinplaceoflemmaseparator
9985   \let\txtbeforeXnotes\Txtbeforenotes
9986   \let\afterXrule\Xafterrule
9987   \let\numberonlyfirstinline\Xnumberonlyfirstinline
9988   \let\numberonlyfirstintwo\Xnumberonlyfirstintwo
9989   \let\nonumberinfofootnote\Xnonumberinfofootnote
9990   \let\pstartinfofootnote\Xpstart
9991   \let\pstartinfofootnoteeverytime\Xpstarteverytime
9992   \let\onlyXpstart\Xonlypstart
9993   \let\Xnonumberinfofootnote\Xnonumber
9994   \let\nonbreakableafternumber\Xnonbreakableafternumber
9995   \let\maxhXnotes\Xmaxhnotes
9996   \let\beforeXnotes\Xbeforenotes
9997   \let\boxlinenum\Xboxlinenum
9998   \let\boxlinenumalign\Xboxlinenumalign
9999   \let\boxstartlinenum\Xboxstartlinenum
10000  \let\boxendlinenum\Xboxendlinenum
10001  \let\twolines\Xtwolines
10002  \let\morethan twolines\Xmorethan twolines
10003  \let\twolinesbutnotmore\Xtwolinesbutnotmore
10004  \let\twolinesonlyinsamepage\Xtwolinesonlyinsamepage

```

```

10005 \fi
10006
10007 \unless\ifnofamiliar@
10008   \let\notesXwidthliketwocolumns\noteswidthliketwocolumnsX
10009 \fi
10010 \newcommandx{\parafootsep}[2][1,usedefault]{%
10011   \Xparafootsep[#1]{#2}%
10012   \parafootsepX[#1]{#2}%
10013 }%
10014
10015 \newcommandx{\afternote}[2][1,usedefault]{%
10016   \Xafternote[#1]{#2}%
10017   \afternoteX[#1]{#2}%
10018 }%
10019
10020 \unless\ifnoend@
10021   \let\XendXtwolines\Xendtwolines
10022   \let\XendXmorethanTwolines\XendmorethanTwolines
10023   \let\bhookXendnote\Xendbhooknote
10024   \let\boxXendlinenum\Xendboxlinenum%
10025   \let\boxXendlinenumalign\Xendboxlinenumalign%
10026   \let\boxXendstartlinenum\Xendboxstartlinenum%
10027   \let\boxXendendlinenum\Xendboxendlinenum%
10028   \let\XendXlemmaseparator\Xendlemmaseparator
10029   \let\XendXbeforelemmaseparator\Xendbeforelemmaseparator
10030   \let\XendXafterlemmaseparator\Xendafterlemmaseparator
10031   \let\XendXinplaceoflemmaseparator\Xendinplaceoflemmaseparator
10032 \fi
10033
10034 \AtBeginDocument{%
10035   \ifdef\lineref{}{\let\lineref\edlineref}%
10036 }%
10037
10038 \fi%
10039 %
10040 %

```

</code>

Appendix A Things to do when changing versions

A.1 Migrating from `edmac` to `ledmac`

If you have never used `edmac`, ignore this section. If you have used `edmac` and are starting on a completely new document, ignore this section. Only read this section if you are converting an original `edmac` document to use `ledmac`.

The package still provides the original `\text` command, but it is (a) deprecated, and (b) its name has been changed⁴⁰ to `\critext`; use the `\edtext` macro instead. However, if you do use `\critext` (the new name for `\text`), the following is a reminder.

`\critext` Within numbered paragraphs, footnotes and endnotes are generated by forms of the `\critext` macro:

```
\critext{\langle lemma\rangle}{\langle commands\rangle}/
```

The `\langle lemma\rangle` argument is the lemma in the main text: `\critext` both prints this as part of the text, and makes it available to the `\langle commands\rangle` you specify to generate notes. The `/` at the end terminates the command; it is part of the macro's definition so that spaces after the macro will be treated as significant.

For example:

I saw my friend <code>\critext{Smith}</code>	1 I saw my friend
<code>\Afootnote{Jones C, D.}/</code>	2 Smith on Tuesday.
on Tuesday.	<u>2 Smith] Jones C, D.</u>

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D.` The footnote macro is supplied with the line number at which the lemma appears in the main text.

The `\langle lemma\rangle` may contain further `\critext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

<code>\critext{I saw my friend</code>	1 I saw my friend
<code>\critext{Smith}{\Afootnote{Jones</code>	2 Smith on Tuesday.
<code>C, D.}/ on Tuesday.}</code>	<u>2 Smith] Jones C, D.</u>
<code>\Bfootnote{The date was</code>	<u>1-2 I saw my friend</u>
<code>July 16, 1954.}</code>	Smith on Tuesday.] The
<code>/</code>	date was July 16, 1954.

However, `\critext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; a `\critext` that starts in the `\langle lemma\rangle` argument of another `\critext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

The second argument of the `\critext` macro, `\langle commands\rangle`, is the same as the second argument to the `\edtext` macro.

It is possible to define aliases for `\critext`, which can be easier to type. You can make a single character substitute for `\critext` by saying this:

```
\catcode`\<=\active
```

⁴⁰A name like `\text` is likely to be defined by other `TeX` packages (it certainly is by the AMS packages) and it seems sensible to try and avoid clashes with other definitions.

```
\let<=\critext
```

Then you might say `<{Smith}\variant{Jones}/`. This of course destroys the ability to use `<` in any new macro definitions, so long as it remains in effect; hence it should be used with care.

Changing the character at the end of the command requires more work:

```
\catcode`<=\active
\def\xtext{\#1\#2}{\critext{\#1}{\#2}/}
\let<=\xtext
```

This allows you to say `<{Smith}\Afootnote{Jones}`.

Aliases for `\critext` of the first kind shown here also can't be nested—that is, you can't use the alias in the text that forms the first argument to `\critext`. (See VI p. 134 to find out why.) Aliases of the second kind may be nested without any problem.

If you really have to use `\critext` in any of the tabular or array environments, then `\edtext` must not be used in the same environment. If you use `\critext` in one of these environments then you have to issue the declaration `\usingcritext` beforehand. The declaration `\usingedtext` must be issued to revert to the default assumption that `\edtext` will be used.

A.2 Migration from ledmac to elemac

In `elemac`, some changes were made in the code to allow easy customization. This may cause problems for people who have already made their own. The next sections explain how to handle this.

If you have created your own series using `\addfootins` and `\addfootinsX`, you must use instead the `\newseries` command (see 6.7.1 p. 40), and remove any `\Xfootnote` command.

If you have customized the `\XXXXXXfmt` command, please check whether you can achieve the same by the commands documented for display options (7 p. 42) or `\Xfootnote` options (6.2.2 p. 29). Otherwise please add a new ticket on Github to request a new function for doing this.⁴¹

If for some reason you do not want to make the modifications to use the new functions of `elemac`, you can continue using your own `\XXXXXXfmt` command, but you must replace:

```
\renewcommand*{\XXXXXXfmt}[3]
```

with

```
\renewcommandx*{\XXXXXXfmt}[4][4=Z]
```

⁴¹<https://github.com/maieul/ledmac/issues>

If you do not make that, you will get a spurious [X], where X is series letter.

If you used a \protect command inside a \footnote command inside a numbered section, you must change the \protect to \noexpand. Otherwise the command after the \protect will be discarded.

A.3 Migration to elemac 1.5.1

The version 1.5.1 corrects a bug in `stanzaindent repetition` (cf. 9.3 p. 56). This bug had two consequences:

1. `stanzaindent repetition` did not work when its value was greater than 2.
2. `stanzaindent repetition` worked wrong when its value was equal to 2.

So, if you used `stanzaindent repetition` with a value equal to 2, you had to change your `\setstanzaindent`. Explanation:

```
\setcounter{stanzaindent repetition}{2}
\setstanzaindent{5,1,0}
```

This code, in versions prior to 1.5.1, made the first line have an indentation of 0, the second line of 1, the third verse of 0, the fourth verse of 1 and so forth.

But this code should have instead achieved quite the contrary: the first line would have an indentation of 1, the second line of 0, the third line of 1, the fourth line of 0 and so forth.

So version 1.5.1 corrected this bug. If you want to keep the former presentation, you must change:

```
\setcounter{stanzaindent repetition}{2}
\setstanzaindent{5,1,0}
```

to:

```
\setcounter{stanzaindent repetition}{2}
\setstanzaindent{5,0,1}
```

A.4 Migration to elemac 1.12.0

The migration to elemac 1.12.0 is easy:

- You must first delete all the auxiliary files, then compile your document three times as usual.
- If you have modified `\1@reg`, which is not advisable, you must rename it to `\@nl@reg`.

There is an additional problem. If you have put text into brackets just after `\pstart` or `\pend`, this text will be considered to be an optional argument of `\pstart` or `\pend` (see 5.2.3 p. 19). If so, add a `\relax` between `\pstart/\pend` and the first bracket.

The version 1.12.0 also introduce a better way to handle sectional divisions inside numbered text. Please read 16.2 p. 73.

A.5 Migration to elemac 17.1

This version changes the default setting of `\Xpstart`. Henceforth, pstart numbers will be printed in footnotes within the section of text where you have called `\numberpstarttrue`.

We do not see any reason to print them in the other sections. However, if you want to print the `\pstart` numbers in every footnote, whatever the section, without having to use `\numberpstarttrue`, you can use `\Xpstarteverytime`.

A.6 Migration to elemac 1.21.0

A.6.1 `\Xledsetnormalparstuff` and `\ledsetnormalparstuffX`

The `\ledsetnormalparstuff` has been split into two different commands:

- `\Xledsetnormalparstuff` for critical notes;
- `\ledsetnormalparstuffX` for familiar notes.

Both commands can take an optional argument which is the series letter. If you have redefined `\ledsetnormalparstuff` or any of the commands which call them, you must change them accordingly.

A.6.2 Endnotes

In any case, delete the `.end` file before the next run.

The previous version of Elemac had a bug: there were two spaces between the starting page number and the starting line number, but only one space between the ending page number and the ending line number.

As a matter of fact, a spurious space was added after the first `\printnpnum`. This spurious space has been deleted. However, if you want to keep the previous spurious space, you may load the package with the `oldprintnpnumspace` option.

If you have redefined `\endprint`, you must:

- Contact us and ask for the feature that required your hack, in order to avoid such a hack in the future.
- Use the new fifth argument.
- Add `\xdef\@currentseries{#4}` at the beginning of your own command.

A.7 Migration to elemac 1.22.0

The `\ledinnote` command now takes a first optional argument, which is the label for the hyperreference. If you have redefined it, change your redefinition, and check whether you can avoid this redefinition by only redefining `\ledinnotemark`.

A.8 Migration to elemac 1.23.0

You must delete the numbered auxiliary files before compiling with the new version of elemac.

A.9 Migration from elecmac to reledmac

There are many changes in `reledmac` which require the user to make modifications.

A.9.1 Risk of ‘no room for a new’

The risk to obtain a ‘no room for a new something’ error is greater in `reledmac` than it is in `elecmac`. See 19.1.3 p. 76 in order to know how to limit it.

A.9.2 Multiple indices with memoir

`Elecmac` and `ledmac` used the specific indexing tools of the `memoir` class designed to produce multiple indices. However, `elecmac` could also use `imakeidx` or `indextools` tools independently of the `memoir` class. This system forced to maintain redundant code. Since `reledmac`, we use only the `imakeidx` or `indextools` tools.

Consequently: Users of `memoir` are invited to use `indextool` or `imakeidx` to produce multiple indices.

A.9.3 Deprecated commands and options

The table of deprecated commands and their alternatives follows. Note that the way some commands must be used may have changed. Please read the handbook.

<i>Deprecated command</i>	<i>Replaced with</i>
<code>\addfootins</code>	<code>\newseries</code>
<code>\addfootinsX</code>	<code>\newseries</code>
<code>\critext</code>	<code>\edtext</code>
<code>\falseverse</code>	<code>\newverse</code>
<code>\interparanote glue</code>	<code>\Xafternote</code> and <code>\afternoteX</code>
<code>\ledchapter</code>	<code>\elecchapter</code>
<code>\ledsection</code>	<code>\elecsection</code>
<code>\ledsetnormalparstuff</code>	<code>\Xledsetnormalparstuff</code> and <code>\ledsetnormalparstuffX</code>
<code>\ledsubsection</code>	<code>\elecsubsection</code>
<code>\ledsubsubsection</code>	<code>\elecsubsubsection</code>
<code>\noeledsec</code>	Package option <code>noeledsec</code>
<code>\noendnotes</code>	Package option <code>noendnotes</code>
<code>\pageparbreak</code>	<code>\ledpb</code>

The `ledsecnolinenumbers` option has been removed, because it was related to deprecated commands.

The `oldprintnppnumspace` option has been removed too, because it was related to a historical bug. The `\usingedtext` and `\usingcritext` commands are also deprecated.

A.9.4 \renewcommand replaced by command

Many uses of \renewcommand have been replaced with uses of specific commands. Please read handbook about specific commands.

<i>Deprecated \renewcommand</i>	<i>Replaced with</i>
\@led@extranofeet	\newseries
\apprefprefixmore	\setapprefprefixmore
\apprefprefixsingle	\setapprefprefixsingle
\endstanzaextra	Optional argument of \&
\hangingsymbol	\sethangingsymbol
\ledfootinsdim	\Xmaxhnotes and \maxhnotesX
\parafootftmsep	\Xparafootsep and \parafootsepX
\notenumfont	\Xnotenumfont, \Xendnotenumfont and \notenumfontX
\notefontsetup	\Xnotefontsize, \Xendnotefontsize and \notefontsizeX
\sidenotesep	\setsidenotesep
\startstanzahook	Optional argument of \stanza
\symlinenum	\Xsymlinenum

A.9.5 Commands the names of which have been changed

In order to help the migration from eleedmac to reledmac, you may load `reledmac` with `eleedmac-compat` option. However, it is advised not to, and to change the command names themselves instead. In many cases, you use only a few of them, except the \footparagraph command.

<i>Old command</i>	<i>New command</i>
\footparagraph	\Xarrangement
\footnormal	\Xarrangement
\foottwocol	\Xarrangement
\footthreecol	\Xarrangement
\footparagraphX	\arrangementX
\footnormalX	\arrangementX
\foottwocolX	\arrangementX
\footthreecolX	\arrangementX
\afterlemmaseparator	\Xafterlemmaseparator
\afternote	\Xafternote and \afternoteX
\afternumberinfofnote	\Xafternumber
\afterXrule	\Xafterrule
\afterXsymlinenum	\Xaftersymlinenum
\beforelemmaseparator	\Xbeforelemmaseparator
\beforenumberinfofnote	\Xbeforenumber
\beforeXnotes	\Xbeforenotes
\beforeXsymlinenum	\Xbeforesymlinenum

<i>Old command</i>	<i>New command</i>
\bhookXnote	\Xbhookendnote
\bhookXnote	\Xbhooknote
\boxendlinenum	\Xboxendlinenum
\boxlinenum	\Xboxlinenum
\boxlinenumalign	\Xboxlinenumalign
\boxstartlinenum	\Xboxstartlinenum
\boxsymlinenum	\Xboxsymlinenum
\boxXendlinenum	\Xendboxlinenum
\boxXendlinenumalign	\Xendboxlinenumalign
\boxXendstartlinenum	\boxXendstartlinenum
\letboxXendendlinenum	\Xendletboxendlinenum
\hsizetwocol	\Xhsizetwocol
\hsizethreecol	\Xhsizethreecol
\inplaceoflemmaseparator	\Xinplaceoflemmaseparator
\inplaceofnumber	\Xinplaceofnumber
\lemmaseparator	\Xlemmaseparator
\maxhXnotes	\Xmaxhnotes
\morethanwolines	\Xmorethanwolines
\nonumberinfofootnote	\Xnonumber
\notesXwidthliketwocolumns	\noteswidthliketwocolumnsX
\noXlemmaseparator	\Xnolemmaseparator
\numberonlyfirstinline	\Xnumberonlyfirstinline
\numberonlyfirstintwolines	\Xnumberonlyfirstintwolines
\nonbreakableafternumber	\Xnonbreakableafternumber
\onlyXpstart	\Xonlypstart
\parafootsep	\Xparafootsep and \parafootsepX
\pstartinfofootnote	\Xpstart
\pstartinfofootnoteeverytime	\Xpstarteverytime
\symlinenum	\Xsymlinenum
\twolines	\Xtwolines
\twolinesbutnotmore	\Xtwolinesbutnotmore
\twolinesonlyinsamepage	\Xtwolinesonlyinsamepage
\txtbeforeXnotes	\Xtxtbeforenotes
\XendXafterlemmaseparator	\Xendafterlemmaseparator
\XendXbeforelemmaseparator	\Xendbeforelemmaseparator
\XendXinplaceoflemmaseparator	\Xendinplaceoflemmaseparator
\XendXlemmaseparator	\Xendlemmaseparator
\XendXmorethanwolines	\Xendmorethanwolines
\XendXtwolines	\Xendtwolines
\Xnonumberinfofootnote	\Xnonumber
\lineref	\edlineref

A.9.6 Endnotes

With `reledmac`, there is now one auxiliary file for each endnotes set (`.Aend`, `.Bend`, `.Cend` etc.). If you have overridden `\doendnotes` (which you should not have done) you must adapt your code.

A.9.7 Z Series

The ‘Z’ series of notes has been removed. Only five series are provided now by default: A, B, C, D, E.

A.9.8 Internal commands

Users who have overriden internal commands, which is wrong, must adapt according to the following. Or better, they should not override any of such commands and use `reledmac` options instead.

- If you have modified `\Xfootfmt`, note that the fourth argument is now mandatory.
- `\unvxh` has been replaced with `\Xunvxh` and `\unvxhX` with two mandatory arguments.

A.10 Migration to `reledmac 2.1.0`

`Reledmac 2.1.0` fix some bugs when using `\Xbhooknote` and `\bhooknoteX` not in order to execute code at the beginning of each notes, but to insert content of at the beginning of each notes.

People who use these commands to do it, which is not the original idea, must change the following:

1. Horizontal space is no longer automatically added after the content of the `\Xbhooknote/\bhooknoteX` argument. You must include it manually. So instead of `\Xbhooknote{content}`, use `\Xbhooknote{content }.`
2. Indent is no longer automatically added before the content of the `\Xbhooknote/\bhooknoteX` argument. If you want to keep it, add `\indent` to the argument of `\Xbhooknote/\bhooknoteX`.

A.11 Migration to `reledmac 2.1.3`

`Reledmac 2.1.3` fix an historical bug, (style in `ledmac 0.7!`) which doubled the space before the rules of paragraphed familiar footnotes. Consequently, if you use paragraphed familiar footnotes, you should maybe adapt it, playing with `\beforenotesX`.

A.12 Migration to `reledmac 2.3.0`

Before `reledmac 2.3.0`, for typesetting verse, any empty line was considered a paragraph inside verses. Counting empty lines this created breaking verse, hanging verses, and also added spurious vertical spaces. Version 2.3.0 disables paragraph in stanza. If you want vertical space, use the optional argument of `\stanza` or `\endverse`.

A.13 Migration to *reledmac* 2.4.0

It is not mandatory, but strongly recommended, to change any `\renewcommand{\endashchar}{<...>}` to the use of `\Xlinerangeseparator` or / and `\Xendlinerangeseparator` (7.2.4 p. 44).

A.14 Migration to *reledmac* 2.5.0

It is strongly recommended to stop redefining `\printnpnum` and to use the hooks documented in 7.2.3 p. 44.

`\xlineref` does not print anymore the side flag (R for right side), because it is incompatible with numerical test. Use `\xflagref` to obtain it.

The `\printlines` and `\printendlines` commands take now an eighth argument, which is the side flag. It is strongly recommended to NEVER redefine these two commands and to use the setting commands instead (or to ask for new setting commands if the actual does not answer to your needs). However, if you have done it, just change your redefinition to have a new argument.

It is strongly recommended to stop redefining `\fullstop` and to use `\Xsublinesep` instead.

A.15 Migration to *reledmac* 2.7.0

`\SErefonlypage` (introduced in *reledmac* 2.5.0) added an parenthesis after the page number. This was just an error, linked to a bad imitation of `\SErefwithpage`. That has been deleted. And so, the `\XendafterpagenumberSErefonlypage` to set it was also deleted.

`\rigidbalance` is split to two new commands: `\Xrigidbalance` for critical footnotes and `\rigidbalanceX` for familiar footnotes. If you have redefined it — but why should you have ?—, you should split your single redefinition in two redefinitions.

A.16 Migration to *reledmac* 2.7.2

`\Xhspace` is already defined in the *floatrow* package. It becomes `\Xwidth`, and, consequently, `\hspaceX` becomes `\widthX`.

The ancient names are temporarily maintained as aliases.

A.17 Migration to *reledmac* 2.8.0

Reledmac 2.8.0 fix spurious indents for paragraphed critical and familiar footnotes in *ledgroup* and *minipage*. You can re-establish the indent with `\Xparindent` and `\parindentX`.

A.18 Migration to *reledmac* 2.13.1

Reledmac 2.5.0 added a bug, which makes the right flag to be printed on the right side of critical footnotes, even if not explicitly requested by using `\Xlineflag`.

Version 2.13.1 solves this issue. Please use `\Xlineflag` if you want to add the right flag.

A.19 Migration to `reledmac 2.18.0`

After updating `reledmac`, and before any new compilation, you need to clean your `.aux` files, if you use `\edlabel` or related.

A.20 Migration to `reledmac 2.21.0`

Previously, there was a bug, which meant that the description in the handbook was incorrect. If you wrote

```
The \edtext{creature}\edindex{elephant} was quite
unafraid}{\Afootnote{\edindex{elephant}of the mouse, that is.}}
```

“elephant” was indexed in the main text and in the critical footnotes. With the new version of `reledmac`, it is indexed only in main text. If you also want to index it in critical footnotes, do

```
The \edtext{creature}\edindex{elephant} was quite
unafraid}{\Afootnote{\edindex{elephant}of the mouse, that is.}}
```

A.21 Migration to `reledmac 2.24.0`

When using `\labelpstarttrue`, a spurious space^a was introduced after the pstart number (only for normal typesetting, not while typesetting in parallel). The new version of the package has deleted this spurious space. If you consider that it was NOT a spurious space, you should add it manually in your definition of `\thepstart`.

A.22 Migration to `reledmac 2.26.0`

You must delete your `.aux` file after having upgraded to this new version of `reledmac`.

A.23 Migration to `reledmac 2.27.1`

This release fixes spurious space in `\hidenumbering`. If you considered this spurious space as normal, you must insert it manually using.

```
xx\hidenumbering\ xx
```

To get the space after `xx`.

A.24 Migration to `reledmac 2.30.0`

If you have multiple annotations for the same line, these are now separated with a comma in the margin. You can use `\setlinenumannotationsep` to change the separator.

A.25 Migration to *reledmac* 2.31.1

If you use `\Xgroupbyline`, the indentation of the notes has been deleted, in order to have the same behavior as for normal critical notes.

Use `\Xparindent` to restore indentation.

Appendix B Auxiliary softwares

This appendix lists some software and tools related to *reledmac* that may be useful.

B.1 *samewords*

The *samewords* program (Michael Stenskjær Christensen) automatically adds `\sameword` commands (6.3 p. 33) into a `.tex` file.

<https://samewords.readthedocs.io/en/latest/>

B.2 critical-keys for *Emacs*

The *Emacs* editor has a package to help inserting *reledmac*'s commands (Juan Manuel Macías Chaín).

<https://gitlab.com/maciaschain/critical-keys>

B.3 Import from TEI

There are multiple tools to convert from XML-TEI to *reledmac*. Here is a non exhaustive-list:

- <http://ciham-digital.huma-num.fr/teicat/>
- https://github.com/fizzbucket/tei_transformer
- <https://github.com/TEIC/Stylesheets>
- <http://lombardpress.org/print/>
- <https://github.com/Jean-Baptiste-Camps/TEIToLaTeX>

Please, tell us if you know of other tools.

References

- [Bre96] Herbert Breger. *tabmac*. October 1996. (Available from CTAN in `macros/plain/contrib/tabmac`)
- [Bur01] John Burt. ‘Typesetting critical editions of poetry’. *TUGboat*, **22**, 4, pp. 353–361, December 2001. (Code available from CTAN in `macros/latex/contrib/poemscol`)
- [Eck03] Matthias Eckermann. *The Parallel-Package*. April 2003. (Available from CTAN in `macros/latex/contrib/parallel`)
- [Fai03] Robin Fairbairns. *footmisc—a portmanteau package for customising footnotes in L^AT_EX*. February 2003. (Available from CTAN in `macros/latex/contrib/footmisc`)
- [LW90] John Lavagnino and Dominik Wujastyk. ‘An overview of edmac: a PLAIN TeX format for critical editions’. *TUGboat*, **11**, 4, pp. 623–643, November 1990. (Code available from CTAN in `macros/plain/contrib/edmac`)
- [Lüc03] Uwe Lück. ‘ednotes—critical edition typesetting with L^AT_EX’. *TUGboat*, **24**, 2, pp. 224–236, 2003. (Code available from CTAN in `macros/latex/contrib/ednotes`)
- [Sul92] Wayne G. Sullivan. *The file edstanza.doc*. June 1992. (Available from CTAN in `macros/plain/contrib/edmac`)
- [Wil02] Peter Wilson. *The memoir class for configurable typesetting*. November 2002. (Available from CTAN in `macros/latex/contrib/memoir`)
- [Wil04] Peter Wilson and Maïeul Rouquette. *Parallel typesetting for critical editions: the eledpar package*. December 2004. (Available from CTAN in `macros/latex/contrib/ledmmac`)

Index

Symbols

\&	55
\@EDROWFILL@	1
\@adv	1
\@advancestanzanumber	1
\@cannot	1
\@cannot@end@print	1
\@cannot@start@print	1
\@beforeinsertofthisedtext	1
\@check@edtext@args	1
\@doclearpage	1
\@doreinfeetX	1

\@edindex@fornote@	1
\@edindex@hyperref	1
\@edrowfill@	1
\@edtext@level	1
\@emptytoks	1
\@fnpos	1
\@footnotemark	1
\@footnotetext	1
\@getfirstseries	1
\@gobblefour	1
\@gobbleseven	1
\@gobblethree	1
\@h	1
\@hangingsymbol	1
\@iiminiplate	1
\@insertstanzanumber	1
\@insidethisline	1
\@k	1
\@l@dtmpcnta	1
\@l@dtmpcntb	1
\@lab	1
\@led@testifnofoot	1
\@lemma	1
\@line@&num	1
\@linenumannotationsep	1
\@clock	1
\@lopL	1
\@lopR	1
\@makechapterhead	1
\@makeschapterhead	1
\@mem@extranofeet	1
\@mem@old@ssect	1
\@mpfnpos	1
\@msd	1
\@msd@c	1
\@msd@options@iffullpage	1
\@msdata@list	1
\@nl	1
\@nl@reg	1
\@opXfeet	1
\@outputpage	1
\@page	1
\@pend	1
\@pendR	1
\@ref	1
\@ref@reg	1
\@ref@reg@parse	1
\@sect	1
\@series	1
\@set	1

\@sidenotesep	1
\@sect	1
\@startstanzas	1
\@stopmsd	1
\@stopstanza	1
\@sw	1
\@tag	1
\@wredindex	1
\@xloop	1
\@xympar	1
CLASSarticle	76
CLASSbook	76, 372
CLASSmemoir	219, 220, 283–286, 321, 372, 391, 454, 458
CLASSscrbook	458
COMMAND*footnote	77
COMMAND\...@footnotemark...	223
COMMAND\...d@ta	163
COMMAND\<hook	
@<series	270
COMMAND\<hookname	
<pseudoseries	272, 273
COMMAND\<type	
footfmt	207
COMMAND\@@line	198
COMMAND\@MM	184, 455
COMMAND\@Rlineflag	323, 455
COMMAND\@SRefprefix	300
COMMAND\@SRefprefixmore	300
COMMAND\@add@	362
COMMAND\@adv	117
COMMAND\@annot	169
COMMAND\@annot@end@print	210
COMMAND\@annot@start@print	210
COMMAND\@apprefprefixmore	300
COMMAND\@apprefprefixsingle	300
COMMAND\@beforeinsertofthisedtext	140, 141
COMMAND\@bsphack	288
COMMAND\@doclearpage	284, 285, 448, 458
COMMAND\@doreinfeetX	458
COMMAND\@dprintingcolumns	455
COMMAND\@edindex@hyperref	324, 325
COMMAND\@edtext@level	137
COMMAND\@esphack	288
COMMAND\@firstofone	37
COMMAND\@fnpos	241, 280
COMMAND\@footnotemark	220, 448, 458
COMMAND\@footnotetext	220, 221, 448
COMMAND\@gobble	27, 37, 135, 136, 169, 265
COMMAND\@gobblefive	457
COMMAND\@gobblefour	454

COMMAND\@gobbleseven	267
COMMAND\@gobblethree	447
COMMAND\@h	201
COMMAND\@hangingsymbol	329
COMMAND\@iiiminipage	312, 315, 447, 458
COMMAND\@iiiminskip	313
COMMAND\@l	452
COMMAND\@l@dtempcnta	166, 170, 178
COMMAND\@l@dtempcntb	170
COMMAND\@l@reg	452
COMMAND\@lab	113, 288, 291, 296, 447
COMMAND\@ldunboxmpfoot	315
COMMAND\@led@extranofeet	392
COMMAND\@ledinnote@command	319, 320
COMMAND\@lemma	140, 143
COMMAND\@lock	107, 329
COMMAND\@lopL	448
COMMAND\@lopR	448
COMMAND\@makecol	280, 281, 283, 284, 458
COMMAND\@memppnum	286
COMMAND\@mpfnpos	241
COMMAND\@msd	338, 339
COMMAND\@msd@c	338
COMMAND\@msd@options@iffullpage	345
COMMAND\@msdata@list	338, 340
COMMAND\@nl	113–118, 128, 169, 291, 447, 448
COMMAND\@nl@reg	114, 389, 448, 452
COMMAND\@opXfeet	448
COMMAND\@opfeetX	458
COMMAND\@opxtrafeeti	458
COMMAND\@outputpage	286, 287
COMMAND\@page	113, 115, 291
COMMAND\@pend	448
COMMAND\@pendR	448
COMMAND\@ref	113, 123–125, 129, 130, 135
COMMAND\@ref@later	125, 131
COMMAND\@ref@reg	124, 169, 448
COMMAND\@ref@reg@parsearg	125
COMMAND\@reinserts	280, 282–284, 458
COMMAND\@secondoftwo	78
COMMAND\@sect	374
COMMAND\@series	269
COMMAND\@set	118
COMMAND\@sidenotesep	311
COMMAND\@stopmsd	339
COMMAND\@sw	125, 145, 148, 149
COMMAND\@tag	137, 138, 142
COMMAND\@tempcnta	91
COMMAND\@tempcntb	91
COMMAND\@this@crossref@start	219

COMMAND\@toksa	98
COMMAND\@toksb	98
COMMAND\xloop	179
COMMAND\xympar	305, 458
COMMAND\Aendnote	16, 30
COMMAND\Afootfmt	184
COMMAND\Afootgroup	184
COMMAND\Afootnote	9, 16, 28–30, 32, 139, 192, 219, 242, 259, 457
COMMAND\Afootstart	184
COMMAND\AtBeginDocument	284
COMMAND\AtEndEveryPend	19, 464
COMMAND\AtEveryPend	19, 58, 156, 454, 456, 458, 464
COMMAND\AtEveryPend*	19
COMMAND\AtEveryPstart	19, 58, 454, 456, 458, 461, 464
COMMAND\AtEveryPstart*	19
COMMAND\AtEveryStanza	58, 462, 464
COMMAND\AtEveryStopStanza	59, 462, 464
COMMAND\AtStartEveryPstart	19, 464
COMMAND\AtStartEveryStanza	58, 464
COMMAND\BeforeEveryStopStanza	59, 464
COMMAND\Bendnote	16, 28
COMMAND\Bfootnote	9, 16, 219, 242, 259
COMMAND\Centering	51
COMMAND\Cfootnote	219
COMMAND\Columns	92, 152, 189
COMMAND\Dfootnote	219
COMMAND\Efootnote	219
COMMAND\Gls	69
COMMAND\Hy@raisedlink	384
COMMAND\Hy@raisedlink@left	384
COMMAND\LTR	51
COMMAND\NR	374
COMMAND\Pages	92, 152, 281, 283, 286
COMMAND\ProcessOptionsX	82
COMMAND\RL	50
COMMAND\RaggedLeft	51
COMMAND\RaggedRight	51
COMMAND\RenewExpandableDocumentCommand	37, 147
COMMAND\SEonlypage	298, 460
COMMAND\SEref	63–65, 298, 301, 461, 463, 467
COMMAND\SErefonlypage	63–65, 395, 460
COMMAND\SErefwithpage	63–65, 298, 301, 395, 460, 462
COMMAND\Stanza	453
COMMAND\Waklam	362
COMMAND\X@doreinfeet	282, 458
COMMAND\XR@prefix	304
COMMAND\XR@test	304
COMMAND\XR@test@mac	304
COMMAND\XR@test@mac@test	304
COMMAND\XXXXXfmt	388

COMMAND\XXXXXfmt	388
COMMAND\Xafterenum	46
COMMAND\Xafterlemmaseparator	48, 392
COMMAND\Xafternote	52, 391, 392
COMMAND\Xafternumber	46, 392
COMMAND\Xafterrule	53, 242, 392, 453, 456
COMMAND\Xafersymlinenum	46, 47, 392
COMMAND\Xarrangement	42, 52, 77, 185, 271, 392
COMMAND\Xarrangement@footparagraph	191
COMMAND\Xarrangement@normal	185
COMMAND\Xarrangement@paragraph	190
COMMAND\Xbeforeinserting	51
COMMAND\Xbeforelemmaseparator	48, 392
COMMAND\Xbeforenotes	53, 242, 392, 453, 456
COMMAND\Xbeforenumber	44, 46, 392
COMMAND\Xbeforesymlinenum	46, 47, 392
COMMAND\Xhookendnote	393
COMMAND\Xhookgroup	53, 460, 461
COMMAND\Xhooknote	51, 393, 394, 458, 459
COMMAND\Xboxendlinenum	47, 48, 393, 457
COMMAND\Xboxlinenum	47, 48, 393
COMMAND\Xboxlinenumalign	47, 48, 393, 457
COMMAND\Xboxstartlinenum	47, 48, 393, 457
COMMAND\Xboxsymlinenum	47, 393
COMMAND\Xcolalign	51, 456
COMMAND\Xdo@feet	458, 463
COMMAND\Xemdnoindenticallinenumannotation	65
COMMAND\Xend	267
COMMAND\XendXafterlemmaseparator	393
COMMAND\XendXbeforelemmaseparator	393
COMMAND\XendXinplaceoflemmaseparator	393
COMMAND\XendXlemmaseparator	393
COMMAND\XendXmorethantwolines	393
COMMAND\XendXtwolines	393
COMMAND\Xendafternumber	46, 459
COMMAND\Xendafterlemmaseparator	49, 393
COMMAND\Xendafternote	55, 461
COMMAND\Xendafternumber	48
COMMAND\Xendafterpagenumber	462
COMMAND\Xendafterpagenumber	44, 64
COMMAND\XendafterpagenumberSErefonlypage	395
COMMAND\Xendaftersymlinenum	46, 48, 459
COMMAND\Xendahookinplaceofnumber	48, 459
COMMAND\Xendahooklinenum	48, 459
COMMAND\Xendbeforelemmaseparator	49, 393
COMMAND\Xendbeforelinenum	48
COMMAND\Xendbeforenumber	46, 459
COMMAND\Xendbeforepagenumber	44, 64
COMMAND\XendbeforepagenumberSErefonlypage	64
COMMAND\Xendbeforesymlinenum	46, 48, 459

COMMAND\Xendbhookinplaceofnumber	48, 459
COMMAND\Xendbhooklinenumber	48, 459
COMMAND\Xendbhooknote	51
COMMAND\Xendboxendlinenum	48, 457
COMMAND\Xendboxlinenum	48, 393, 455
COMMAND\Xendboxlinenumalign	48, 393, 457
COMMAND\Xendboxstartlinenum	48, 457
COMMAND\Xendboxsymlinenum	47, 459
COMMAND\Xendhangindent	50, 459, 461
COMMAND\Xendinplaceoflemmaseparator	30, 49, 393
COMMAND\Xendinplaceofnumber	47, 458
COMMAND\Xendinplaceofpagenumber	44, 463
COMMAND\Xendinsertsep@	249
COMMAND\Xendlemmadisablefontselection	49
COMMAND\Xendlemmafnt	49, 460
COMMAND\Xendlemmaseparator	31, 48, 393
COMMAND\Xendletboxendlinenum	393
COMMAND\Xendlineflag	64
COMMAND\Xendlinenumannotationposition	26, 65
COMMAND\Xendlineprefixmore	44, 64
COMMAND\Xendlineprefixsingle	44, 64
COMMAND\Xendlinerangeseparator	44, 64, 205, 395, 459
COMMAND\Xendmorethanwolines	30, 45, 64, 393, 456, 457
COMMAND\Xendnoidenticallinenumannotation	27, 252, 466
COMMAND\Xendnonumber	45, 458
COMMAND\Xendnote	245, 265–267, 456
COMMAND\Xendnotefontsize	50, 392
COMMAND\Xendnotenumfont	48, 49, 392
COMMAND\Xendnotes	248
COMMAND\Xendnumberonlyfirstininline	43, 459
COMMAND\Xendnumberonlyfirstintwolines	43, 459
COMMAND\Xendpagenumberonlyfirst	43, 463
COMMAND\Xendpagenumberonlyfirstifsingle	43, 463
COMMAND\Xendpagenumberonlyfirstintwo	44, 463
COMMAND\Xendparagraph	55, 453
COMMAND\Xendsep	55
COMMAND\Xendsublinesep	46, 64, 205
COMMAND\Xendsymlinenum	43, 459
COMMAND\Xendsympagenum	44, 463
COMMAND\Xendtwolines	30, 45, 65, 393, 456, 457
COMMAND\Xendtwolinesbutnotmore	45, 65, 456, 457
COMMAND\Xendtwolinesonlyinsamepage	45, 65, 456, 457
COMMAND\Xendtxtbeforenotes	53, 465
COMMAND\Xendwrapcontent	50, 462
COMMAND\Xendwraplemma	50, 462
COMMAND\Xendwraplinenumannotation	27, 65
COMMAND\Xfootfmt	394
COMMAND\Xfootgroup	190
COMMAND\Xfootins	189
COMMAND\Xfootnote	61, 68, 137, 388, 450, 454–456, 460, 462

COMMAND\Xfootstarts	190
COMMAND\Xgroupbyline	52, 177, 217, 278, 397, 465–467
COMMAND\Xgroupbylines	463
COMMAND\Xgroupbylinesseparatwolines	52
COMMAND\Xhangindent	50, 459, 467
COMMAND\Xsize	395, 460, 461
COMMAND\Xsizethreecol	51, 54, 393
COMMAND\Xsizetwocol	51, 54, 272, 393
COMMAND\Xinplaceoffemmaseparator	29, 48, 393
COMMAND\Xinplaceofnumber	47, 393, 455, 457
COMMAND\Xinplaceofnunber	29
COMMAND\Xinsertparafootsep	195, 197
COMMAND\Xledsetnormalparstuff	390, 391, 456
COMMAND\Xlemmadisablefontselection	49
COMMAND\Xlemmafont	49, 460
COMMAND\Xemmaseparator	48, 205, 273, 276, 280, 393
COMMAND\Xlineflag	64, 395, 396, 462
COMMAND\Xlinenumannotationposition	26, 64, 168
COMMAND\Xlinenumannotationposition@side	168
COMMAND\Xlinenumannotationpositionside	26
COMMAND\Xlinerangeseparator	44, 64, 205, 395, 459
COMMAND\Xmaxhnotes	54, 76, 77, 392, 393, 453, 455
COMMAND\Xmorethantwolines	29, 45, 64, 393, 455
COMMAND\Xnoindenticallinenumannotation	27, 64, 214, 466
COMMAND\Xnoindent	459
COMMAND\Xnolemmaseparator	48, 280, 393
COMMAND\Xnonbreakableafternumber	46, 393, 451
COMMAND\Xnonumber	45, 393
COMMAND\Xnonumberinfootnote	393
COMMAND\Xnotefontsize	49, 392
COMMAND\Xnotefontsize@⟨s⟩	195, 199, 201
COMMAND\Xnotenumfont	49, 392
COMMAND\Xnoteswidthliketwocolumns	54, 454
COMMAND\Xnumberonlyfirstinline	43, 44, 52, 110, 207, 273, 276, 393, 450, 455, 464
COMMAND\Xnumberonlyfirstintwolines	43, 52, 393, 450, 464
COMMAND\Xonlypstart	45, 393, 450, 455
COMMAND\Xpagelinesep	46, 463
COMMAND\Xparafootsep	52, 110, 392, 393, 462, 464, 465
COMMAND\Xparafootsep@series	195
COMMAND\Xparindent	50, 395, 397, 456, 459, 461
COMMAND\Xprenotes	53, 242, 462
COMMAND\Xprenotes@	189, 242, 450
COMMAND\Xprintlines	109
COMMAND\Xpstart	45, 390, 393, 450, 455
COMMAND\Xpstarteverytime	45, 390, 393, 455
COMMAND\Xragged	52
COMMAND\Xrigidbalance	198, 395, 460
COMMAND\Xsethangindent	204
COMMAND\Xstanza	46, 59
COMMAND\Xstanzaseparator	46

COMMAND\Xstorelineinfo	207
COMMAND\Xsublinesep	23, 46, 64, 205, 395
COMMAND\Xsublinesepside	23, 46
COMMAND\Xsymlinenum	43, 52, 392, 393, 457, 464
COMMAND\Xtextbeforenotes	180
COMMAND\Xtoendnotes	31, 267
COMMAND\Xtwolines	29, 45, 64, 213, 214, 272, 393, 455
COMMAND\Xtwolinesappref	272
COMMAND\Xtwolinesbutnotmore	45, 64, 393, 456
COMMAND\Xtwolinesbutnotmoreappref	273
COMMAND\Xtwolinesonlyinsamepage	45, 64, 393, 456
COMMAND\Xtxtbeforenotes	53, 393, 462, 463, 465
COMMAND\Xtxtbeforenotesonlyonce	53, 465
COMMAND\Xunvxh	193, 394
COMMAND\Xwidth	54, 395, 461
COMMAND\Xwrapcontent	50, 462
COMMAND\Xwraplemma	50, 51, 462
COMMAND\Xwraplinenumannotation	26, 27, 64, 168
COMMAND\Xwraplinenumannotation@ref	168
COMMAND\Xwraplinenumannotation@side	168
COMMAND\Xwraplinenumannotationref	27
COMMAND\Xwraplinenumannotationside	26
COMMAND\&	392
COMMAND\absline@num	106, 107, 164
COMMAND\accent	136
COMMAND\actionlines@list	108, 166
COMMAND\actions@list	108
COMMAND\add@Xgroupbyline	177
COMMAND\add@hooktoggle@specific@to@cs	278
COMMAND\add@inserts	107, 176, 177
COMMAND\add@inserts@next	176, 177
COMMAND\add@msd@	338
COMMAND\add@msdata	338, 339
COMMAND\add@msdata@firstlineofpage	342
COMMAND\add@mssqldata	338
COMMAND\add@penalties	164, 178
COMMAND\addcontentsline	369
COMMAND\addfootins	388, 391
COMMAND\addfootinsX	388, 391
COMMAND\addtoendnotes	267
COMMAND\advancelabel@refs	290
COMMAND\advanceline	23, 109, 117, 132, 458
COMMAND\affixline@num	170, 173, 175, 311, 448
COMMAND\affixpstart@num	175
COMMAND\afterXrule	392
COMMAND\afterXsymlinenum	392
COMMAND\aftergroup	135, 139
COMMAND\afterlemmaseparator	392
COMMAND\afternote	392
COMMAND\afternoteX	52, 391, 392

COMMAND\afternumberinfofootnote	392
COMMAND\afterruleX	53, 453, 456
COMMAND\annot@list	109, 170
COMMAND\annotationref	26, 27, 60
COMMAND\applabel	63, 292, 293, 456, 462
COMMAND\appref	61, 63–65, 298, 301, 460, 461, 467
COMMAND\apprefprefixmore	63, 392
COMMAND\apprefprefixsingle	63, 392
COMMAND\apprefwithpage	63–65, 298, 301, 457, 460
COMMAND\arrangementX	42, 77, 223, 271, 392
COMMAND\arrangementX@normal	229
COMMAND\article	15
COMMAND\at@every@pend	156
COMMAND\autopar	18, 152, 157, 158, 239, 449, 451, 452, 456, 466
COMMAND\ballast	77
COMMAND\ballast@count	164, 178
COMMAND\baselineskip	43, 191, 195
COMMAND\beforeXnotes	392
COMMAND\beforeXsymlinenum	392
COMMAND\beforeeeldchapter	10, 74, 370, 371
COMMAND\beforeinsertingX	51
COMMAND\beforelemmaseparator	392
COMMAND\beforenotesX	53, 394, 452, 453, 456
COMMAND\beforenumberinfofootnote	392
COMMAND\begin	346, 347
COMMAND\beginnumbering	17, 18, 20, 92, 93, 96, 97, 106, 110, 111, 127, 157, 244, 337, 450, 453, 457, 458, 463, 464
COMMAND\beginnumberingR	92
COMMAND\bf	450
COMMAND\bfseries	49, 450
COMMAND\bhookXnote	393
COMMAND\bhookgroupX	53, 460
COMMAND\bhooknoteX	51, 394, 458, 459
COMMAND\body	329
COMMAND\bodyfootmarkA	39
COMMAND\book	15
COMMAND\boxXendlinenum	393
COMMAND\boxXendlinenumalign	393
COMMAND\boxXendstartlinenum	393
COMMAND\boxendlinenum	393
COMMAND\boxlinefootnote	209
COMMAND\boxlinenum	393
COMMAND\boxlinenumalign	393
COMMAND\boxstartlinenum	393
COMMAND\boxsymlinenum	393
COMMAND\break	43, 193
COMMAND\brokenpenalty	178
COMMAND\c@page	128
COMMAND\c@page@page	128
COMMAND\centering	51

COMMAND\ch@ck@l@ck	448
COMMAND\ch@cksub@l@ck	173, 448
COMMAND\chapter	73, 372, 376, 453, 456, 458, 462
COMMAND\chaptermark	370
COMMAND\check@pb@in@verse	383
COMMAND\colalignX	51, 456
COMMAND\collect@body	347
COMMAND\color	462
COMMAND\colorbox	78
COMMAND\columns	54
COMMAND\columnwidth	191, 454
COMMAND\command names	272, 273
COMMAND\continuousnumberingwithcolumns@sync@linenumber@singletext	167
COMMAND\copyright	136
COMMAND\correct@Xfootins@box	455
COMMAND\correct@footinsX@box	455
COMMAND\count	199
COMMAND\critex	449
COMMAND\critext	143, 387, 388, 391
COMMAND\csname	82, 146, 147
COMMAND\csquotes	263
COMMAND\ctab	363, 368
COMMAND\ctabtext	368
COMMAND\current@annot	169
COMMAND\dcol	357
COMMAND\def	79, 95
COMMAND\detokenize	147
COMMAND\dimen	199
COMMAND\dimexpr	54
COMMAND\discretionary	193
COMMAND\displaywidowpenalty	178
COMMAND\do@Xfeet	281, 448, 458, 463
COMMAND\do@actions	164–166, 448
COMMAND\do@actions@fixedcode	448
COMMAND\do@actions@next	165, 166
COMMAND\do@ballast	164, 178
COMMAND\do@feet@custom@order	280
COMMAND\do@insidelinehook	451
COMMAND\do@line	107, 134, 154, 158, 162, 163, 176, 178, 329, 448, 449, 451, 453
COMMAND\do@linehook	448
COMMAND\do@lockoff	108
COMMAND\do@lockon	108
COMMAND\dodoreinxtrafeet	447
COMMAND\doendnotes	30, 249, 394, 457, 464
COMMAND\doendnotesbysection	30, 249, 267, 457, 464
COMMAND\doennotes	464
COMMAND\doinsidelinehook	27, 453
COMMAND\doinsidethislinehook	28, 162, 466
COMMAND\dolinehook	27, 453
COMMAND\doreinxtrafeeti	458

COMMAND\doreinxtrafeetii	458
COMMAND\doxtrafeet	447
COMMAND\doxtrafeeti	458
COMMAND\doxtrafeetii	458
COMMAND\dummy@ref	135
COMMAND\edaftertab	72, 363, 364
COMMAND\edannotationref	295
COMMAND\edatleft	72, 361
COMMAND\edatright	72, 361
COMMAND\edbforetab	72, 363
COMMAND\edfilldimen	362
COMMAND\edfont@info	142
COMMAND\edgls	69, 318
COMMAND\edglsadd	464
COMMAND\edgls...	461
COMMAND\edindex	37, 67–69, 318, 319, 322, 324, 325, 351, 451, 453, 455, 458, 459, 463–465
COMMAND\edindexlab	69
COMMAND\edlabel	60– 63, 65, 136, 288, 290, 291, 294, 295, 303, 318, 351, 384, 396, 447, 450–452, 455, 460, 465
COMMAND\edlabelE	63, 293
COMMAND\edlabelS	63, 293
COMMAND\edlabelSE	63
COMMAND\edlineref	60, 61, 288, 393, 455, 457, 460, 464
COMMAND\edmakelabel	62, 303, 304
COMMAND\edpageref	60, 61, 288, 294, 303
COMMAND\edrowfill	362
COMMAND\edsublineref	60
COMMAND\edtabcolsep	356
COMMAND\edtext	7, 25, 28, 29, 31, 32, 34–36, 55, 61–63, 67, 70, 77, 95, 107, 109, 123, 125, 129, 130, 134–143, 145, 146, 148, 150, 168–170, 292, 293, 297, 351, 353, 372, 384, 387, 388, 391, 447, 449, 451, 453–457, 463–466
COMMAND\edtext@level	457
COMMAND\edtextlater	126
COMMAND\edvertdots	73, 361
COMMAND\edvertline	72, 73, 361
COMMAND\elechapter	74
COMMAND\eled@sectioning@out	377
COMMAND\eledchapter	73, 391, 453, 458
COMMAND\eledchapter*	73
COMMAND\eledmac@error	447
COMMAND\eledsection	7, 16, 73, 135, 161, 370, 391, 455, 464, 466
COMMAND\eledsection*	73
COMMAND\eledsubsection	73, 391
COMMAND\eledsubsection*	73
COMMAND\eledsubsubsection	73, 391
COMMAND\eledsubsubsubsection	73
COMMAND\eledxxx	10, 74, 376, 377, 453
COMMAND\eledxxxx	370
COMMAND\elesection	377
COMMAND\else	317, 370

COMMAND\emph	37
COMMAND\empty	91, 171, 288
COMMAND\end	346, 347
COMMAND\end@lemmas	135
COMMAND\endashchar	205
COMMAND\endgraf	154, 195, 239
COMMAND\endlock	23, 109, 133, 334
COMMAND\endminipage	312, 313, 315, 447, 458
COMMAND\endmsdata	39
COMMAND\endnotes	456, 460
COMMAND\endnumbering	17, 18, 20, 92, 93, 95, 96, 127, 448, 457, 463, 464
COMMAND\endnumberingR	92
COMMAND\endprint	245, 247, 267, 390
COMMAND\endstanzaextra	392
COMMAND\endsub	23, 108, 131
COMMAND\endverse	394
COMMAND\everypar	157
COMMAND\extensionchars	75, 93
COMMAND\externaldocument	65, 304
COMMAND\f@x@l@cks	448
COMMAND\falseverse	391, 451, 453
COMMAND\fi	370
COMMAND\firstlinenum	21, 170, 449
COMMAND\firstsublinenum	21, 449
COMMAND\flag@end	129, 130, 141, 453
COMMAND\flag@end@RTL	130
COMMAND\flag@end@later	131
COMMAND\flag@start	129, 130, 141, 453, 454
COMMAND\flag@start@RTL	130
COMMAND\flag@start@later	131
COMMAND\flagstanza	59
COMMAND\floatingpenalty	184, 455
COMMAND\flush@notes	179
COMMAND\fnpos	41, 241, 452, 463
COMMAND\footfmt	184, 186
COMMAND\footfmt...	224
COMMAND\footfootmarkA	40
COMMAND\footfudgefactor	193
COMMAND\footfudgefiddle	77, 191, 447
COMMAND\footgroup	184
COMMAND\footins	189
COMMAND\footnormal	272, 392, 447
COMMAND\footnormalX	392
COMMAND\footnote	39, 76, 219–221, 389, 448
COMMAND\footnote@lang	205
COMMAND\footnoteA	17, 39
COMMAND\footnoteB	17
COMMAND\footnoteC	28
COMMAND\footnoteE	39
COMMAND\footnoteX	9, 40, 263, 265, 463

COMMAND\footnoteX@reading	264
COMMAND\footnoteXmark	265, 464
COMMAND\footnoteXmk	280
COMMAND\footnoteXtext	265, 464
COMMAND\footnote{X}	136
COMMAND\footnote{X}mark	40
COMMAND\footnote{X}mk	40
COMMAND\footnote{X}nomk	40
COMMAND\footnote{X}text	40
COMMAND\footnotelang@lua	182
COMMAND\footnotelang@poly	183
COMMAND\footnotemark	40, 265
COMMAND\footnoteoption@	182, 459
COMMAND\footnoterule	199
COMMAND\footnotesize	49, 50
COMMAND\footnotetext	40, 265
COMMAND\footparagraph	191, 272, 392, 453
COMMAND\footparagraphX	234, 392, 453
COMMAND\fotsplitskips	448, 455
COMMAND\footstart	184, 189, 199
COMMAND\footstrut	195
COMMAND\foothreecol	392
COMMAND\foothreecolX	392, 456
COMMAND\foottwocol	392
COMMAND\foottwocolX	392, 456
COMMAND\foreignlanguage	50
COMMAND\fullstop	395
COMMAND\get@edindex@hyperref	324
COMMAND\get@edindex@ledinnote@command	319
COMMAND\get@fnmark	221
COMMAND\get@index@command	452
COMMAND\get@linelistfile	448
COMMAND\get@thisfootnote	227
COMMAND\getline@num	164, 165
COMMAND\gl@p	99
COMMAND\global	113
COMMAND\globaldefs	113
COMMAND\gls	69, 326
COMMAND\hangindentX	50, 456, 459, 467
COMMAND\hangingsymbol	392, 449
COMMAND\hbox	193
COMMAND\hfill	451
COMMAND\hidenumbering	24, 122, 396, 456, 466
COMMAND\hidenumberingonleftpage	24, 122, 462
COMMAND\hidenumberingonrightpage	24, 122, 462
COMMAND\hline	70
COMMAND\hooktoggle@specific	278
COMMAND\hrulefill	362
COMMAND\hsize	43, 189, 191–193, 200, 202, 240, 448, 454
COMMAND\hsizeX	395, 460, 461

COMMAND\hsizethreecol	393
COMMAND\hsizethreecolX	52, 54
COMMAND\hsizetwocol	393
COMMAND\hsizetwocolX	52, 54
COMMAND\hyperlinkR	323
COMMAND\hyperlinkformat	323
COMMAND\hyperlinkformatR	323
COMMAND\if@RTL	83, 139
COMMAND\if@edtext@	454, 457
COMMAND\if@eled@sectioning	376
COMMAND\if@firstlineofpage	84
COMMAND\if@firstlineofpageR	84
COMMAND\if@msd@options@fullpage	345
COMMAND\if@msdata@insertedfrompreviouspage	342
COMMAND\if@nobreak	156
COMMAND\if@noneed@Footnote	129
COMMAND\ifXnote@	92
COMMAND\ifafterendnumberingR	92
COMMAND\ifautopar	157
COMMAND\ifby@autopar	157
COMMAND\ifbypage@	99
COMMAND\ifbypage@R	99
COMMAND\ifbypstart@	99
COMMAND\ifbypstart@R	99
COMMAND\iffirst@linenum@out@	126, 127
COMMAND\ifindtl@innote	92
COMMAND\ifindtl@notenumber	92
COMMAND\ifinserthangingsymbol	329
COMMAND\ifinstanza	329
COMMAND\ifistwoofollowinglines	214, 215
COMMAND\ifl@d@Xmorethanwolines	210, 455
COMMAND\ifl@d@Xtwolines	210
COMMAND\ifl@d@dash	210
COMMAND\ifl@d@elin	210
COMMAND\ifl@d@esl	210
COMMAND\ifl@d@pnum	210
COMMAND\ifl@d@ssub	210
COMMAND\ifl@dend@X	266
COMMAND\ifl@dmemoir	447
COMMAND\ifl@dpaging	454
COMMAND\ifl@dpairing	91, 449
COMMAND\ifl@dprintingpages	455
COMMAND\ifl@dskipnumber	170
COMMAND\ifl@dstartendok	362
COMMAND\ifl@imakeidx	83
COMMAND\ifledRcol	92, 449
COMMAND\ifledRcol@	92, 453
COMMAND\iflemmacommand@	454
COMMAND\ifnoend@	249
COMMAND\ifnoledgroup@	317

COMMAND\ifnoteschanged@	110
COMMAND\ifnumberedpar@	152
COMMAND\ifnumbering	93, 96
COMMAND\ifnumberingR	92, 449
COMMAND\ifnumberline	141, 170
COMMAND\ifpst@rted	449
COMMAND\ifpst@rtedL	93
COMMAND\ifresumenumbering@start	96
COMMAND\ifseriesbefore	270
COMMAND\ifstopmsdata@inserted@	337
COMMAND\ifsblines@	106, 119
COMMAND\iftrue	457
COMMAND\ifvmode	290
COMMAND\ifxxx	370
COMMAND\ignorespaces	139
COMMAND\imki@wrindexentry	83
COMMAND\immediate	126, 127, 244
COMMAND\indent	18, 157, 394
COMMAND\index	326, 463
COMMAND\indl@wrindexentry	83
COMMAND\initnumbering@quote	368, 458
COMMAND\initnumbering@reg	448
COMMAND\initnumbering@seccmd	458
COMMAND\inplaceoflemmaseparator	393
COMMAND\inplaceofnumber	393
COMMAND\insert	141, 176, 184, 186, 187, 200, 217, 224
COMMAND\insert@Xtxtbeforenotes	180, 200
COMMAND\insert@count	123, 129, 139
COMMAND\insert@countR	139
COMMAND\insert@msdata	338, 345
COMMAND\insert@txtbeforenotesX	180
COMMAND\inserthangingsymbol	451
COMMAND\insertlines@list	107, 123, 124
COMMAND\insertparafootsepX	237
COMMAND\inserts@list	134, 152, 176, 192
COMMAND\interAfootnotelinepenalty	449
COMMAND\interfootnotelinepenalty	449
COMMAND\interlinepenalty	184
COMMAND\interparanote glue	391
COMMAND\justifying	51
COMMAND\keep@this@crossref@forinserting	219
COMMAND\l@advance@parledegrou@beforeenormalnotes	458
COMMAND\l@d@@wrindexhyp	454
COMMAND\l@d@add	144
COMMAND\l@d@end	244, 266
COMMAND\l@d@nums	138, 141, 143, 144, 210, 211
COMMAND\l@d@section	245
COMMAND\l@d@set	118, 132
COMMAND\l@d@dampcount	353
COMMAND\l@dbfnote	221, 448

COMMAND\l@dcheckstartend	362
COMMAND\l@dchset@num	118
COMMAND\l@dcolcount	353, 354
COMMAND\l@dcollect@@body	347
COMMAND\l@dcollect@body	346
COMMAND\l@dcsnote	453
COMMAND\l@dcsnotetext	163, 309
COMMAND\l@dcsnotetext@l	163, 309
COMMAND\l@dcsnotetext@r	163, 309
COMMAND\l@ddodoreinxtrafeet	282, 447
COMMAND\l@ddoxtrafeet	280, 282, 447
COMMAND\l@demptyd@ta	448
COMMAND\l@dend@close	244
COMMAND\l@dend@open	244
COMMAND\l@dend@stuff	244
COMMAND\l@denvbody	346
COMMAND\l@freetbeginmini	447
COMMAND\l@freetendmini	447
COMMAND\l@dgetline@margin	449
COMMAND\l@dgetlock@disp	449
COMMAND\l@dgetref@num	296
COMMAND\l@dgetsidenote@margin	305, 449
COMMAND\l@dgobbleoptarg	454
COMMAND\l@dgobblearg	454
COMMAND\l@dgobbleoptarg	352
COMMAND\l@dlabel@parse	296
COMMAND\l@dld@ta	170, 172
COMMAND\l@dlp@rbox	310
COMMAND\l@dlsn@te	449
COMMAND\l@dlsnote	453
COMMAND\l@dmake@labels	290, 291, 304
COMMAND\l@dmake@labelsR	304
COMMAND\l@dnumpstartsL	93, 449
COMMAND\l@dp@rsefootspec	211
COMMAND\l@dparsefootspec	211
COMMAND\l@dpush@begins	347
COMMAND\l@drd@ta	170, 172
COMMAND\l@dref@undefined	296
COMMAND\l@drsn@te	449
COMMAND\l@drsnote	453
COMMAND\l@dtabaddcols	362
COMMAND\l@dtabnoexpands	447
COMMAND\l@dumboxmpfoot	458
COMMAND\l@dunboxmpfoot	448
COMMAND\l@dunhbox@line	158
COMMAND\l@dzeropenalties	449, 454
COMMAND\l@pb	383
COMMAND\l@prev@nopb	382
COMMAND\l@prev@pb	382
COMMAND\l@reg	389

COMMAND\l@secondoptarg	352
COMMAND\l@wrap@ifnotemptybox	90
COMMAND\label	20, 62, 65, 69, 288, 289, 297
COMMAND\label@refs	288
COMMAND\labelpstarttrue	20, 396, 450, 465
COMMAND\labelref@list	288, 291
COMMAND\language	193
COMMAND\lastbox	157
COMMAND\lastskip	131
COMMAND\latex@makecol	284
COMMAND\leavevmode	19, 157
COMMAND\led@check@nopb	383
COMMAND\led@check@pb	383
COMMAND\led@nopb	382, 383
COMMAND\led@nopbnum	382
COMMAND\led@pb	382, 383
COMMAND\led@pb@macro	382
COMMAND\led@pbnum	382
COMMAND\led@reinit@index@fornote	326
COMMAND\led@set@index@fornote	326
COMMAND\ledRflag	323
COMMAND\ledchapter	391, 450
COMMAND\ledfootinsdim	392
COMMAND\ledinernote	66, 306, 453, 462
COMMAND\ledinnote	321, 390, 457
COMMAND\ledinnotemark	68, 390, 456
COMMAND\ledleftnote	66, 306
COMMAND\ledlinenum	105, 449
COMMAND\ledllfill	163
COMMAND\ledlsnotefontsetup	462
COMMAND\ledlsnotesep	66
COMMAND\ledlsnotewidth	66
COMMAND\lednophb	75, 382
COMMAND\lednopbinverse	383
COMMAND\lednopbinversetrue	58, 75
COMMAND\lednopbnum	382
COMMAND\ledouternote	66, 306, 453, 462
COMMAND\ledpb	75, 382, 391
COMMAND\ledpbnum	382
COMMAND\ledpbsetting	75, 382, 459
COMMAND\ledrightnote	66, 306
COMMAND\ledrsnotefontsetup	462
COMMAND\ledrsnotesep	66
COMMAND\ledrsnotewidth	66
COMMAND\ledsection	391
COMMAND\ledsectnomark	370
COMMAND\ledsectnotoc	369
COMMAND\ledsetnormalparstuff	390, 391, 456
COMMAND\ledsetnormalparstuff@common	239
COMMAND\ledsetnormalparstuffX	390, 391, 456

COMMAND\ledsidenote	66, 306, 309
COMMAND\ledsubsection	391
COMMAND\ledsubsubsection	391
COMMAND\ledxxx	453
COMMAND\left	72
COMMAND\leftctab	363
COMMAND\leftheadline	104
COMMAND\leftlinenum	22, 104, 447, 449
COMMAND\leftltab	363
COMMAND\leftnoteupfalse	66
COMMAND\leftpstartnum	175
COMMAND\leftrtab	363
COMMAND\leftsidenote	309
COMMAND\leftskip	189, 192, 193
COMMAND\lemma	3, 29, 31, 32, 34–36, 134, 138, 139, 142, 143, 145, 387, 449, 450, 457, 458, 460
COMMAND\lemmaseparator	393
COMMAND\let	32, 55, 136, 141, 265, 284, 334, 447
COMMAND\letboxXendendlinenum	393
COMMAND\line	198, 201
COMMAND\line@list	107, 109, 124, 141
COMMAND\line@list@stuff	93, 110, 111, 127, 447, 449
COMMAND\line@list@version	113
COMMAND\line@margin	101, 172, 305
COMMAND\line@num	106–108, 170, 447
COMMAND\line@set	143, 144
COMMAND\lineannot	26, 62, 144
COMMAND\lineannot@set	144
COMMAND\lineation	22, 99, 465, 466
COMMAND\linebreak	43
COMMAND\lineneation	461
COMMAND\linenum	26, 29, 32, 61–63, 134, 143, 144, 294, 297, 304, 387
COMMAND\linenum@out	126, 288, 291
COMMAND\linenumannotation	25, 168, 465, 466
COMMAND\linenumberlist	21, 22, 91, 171, 447
COMMAND\linenumberstyle	24, 104, 447, 464
COMMAND\linenumincrement	21, 449
COMMAND\linenummargin	22, 101, 305
COMMAND\linenumr@p	104, 447, 449
COMMAND\linenumrep	104, 449
COMMAND\linenumsep	22, 66, 104, 306
COMMAND\linerangesep@	279
COMMAND\lineref	288, 294, 303, 393, 455
COMMAND\list@clear	98
COMMAND\list@clearing@reg	449
COMMAND\list@create	98
COMMAND\lock@disp	103
COMMAND\lock@off	121
COMMAND\lock@on	120
COMMAND\lockdisp	23, 103
COMMAND\loop	179, 329

COMMAND\ltab	363, 364, 368
COMMAND\ltabtext	368
COMMAND\m@mmf@prepare	220
COMMAND\mainmatter	465, 466
COMMAND\makeatletter	162
COMMAND\makehboxofhboxes	194, 195
COMMAND\makeindex	67, 322
COMMAND\makelabel	304
COMMAND\managestanza@modulo	331
COMMAND\marginpar	66, 76, 305, 448
COMMAND\marginparwidth	66, 306
COMMAND\markboth	28, 162
COMMAND\mathchardef	330
COMMAND\maxhXnotes	393
COMMAND\maxhnotesX	54, 77, 392, 452, 453, 455, 456
COMMAND\maxlinesinpar@list	111
COMMAND\measurebody	365
COMMAND\measurebody	365
COMMAND\memorybreak	21
COMMAND\metaXXXvfootnote	217
COMMAND\microtype	158
COMMAND\morenoexpands	77, 78, 134, 136
COMMAND\morethantwolines	393
COMMAND\mpfnpos	41, 241, 452, 463
COMMAND\mpnnormalfootgroup	447
COMMAND\mpnnormalvfootnote	448
COMMAND\msdata	38, 39, 336, 337, 339, 464, 466
COMMAND\msdataposition	39
COMMAND\multfootsep	40, 219
COMMAND\multiplefootnotemarker	219
COMMAND\musixtex	452
COMMAND\n@num	449, 456
COMMAND\n@num@ref	456
COMMAND\new@line	128, 448
COMMAND\new@series	136
COMMAND\newcommand	32, 79, 95, 219, 291
COMMAND\newcommandx	32
COMMAND\newhookarg@specific	278
COMMAND\newhookcommand@series	272, 273, 456
COMMAND\newhookcommand@series@reload	273
COMMAND\newhookcommand@toggle@reload	273, 454
COMMAND\newhooktoggle@series	273, 456
COMMAND\newhooktoggle@specific	278
COMMAND\newif	456
COMMAND\newline	43
COMMAND\newlinechar	266
COMMAND\newseries	40, 388, 391, 392
COMMAND\newseries@	257, 270
COMMAND\newverse	58, 59, 391, 453, 464
COMMAND\next	329

COMMAND\next@action	111
COMMAND\next@actionline	111
COMMAND\next@insert	176
COMMAND\next@line@list@stuff	127, 465
COMMAND\nl@regR	114
COMMAND\no@expands	77, 136, 142, 265, 447
COMMAND\noXlemmaseparator	393
COMMAND\nobreak	210
COMMAND\nocritical	257
COMMAND\neoledsec	74, 391
COMMAND\noendnotes	391
COMMAND\noexpand	389
COMMAND\nofamiliar	275
COMMAND\noindent	18, 19, 58, 59, 157, 459
COMMAND\noindentX	459
COMMAND\nomk@	280
COMMAND\nonbreakableafternumber	393
COMMAND\nonumberinfootnote	393
COMMAND\norelax	56
COMMAND\normal@footnotemarkX	223
COMMAND\normal@page@break	382
COMMAND\normal@pars	239
COMMAND\normalbfnoteX	449
COMMAND\normalbodyfootmarkX	223
COMMAND\normalfont	463
COMMAND\normalfootfmt	55, 188, 195, 205, 245, 462
COMMAND\normalfootfmtX	224, 225
COMMAND\normalfootfootmarkX	225
COMMAND\normalfootgroup	190
COMMAND\normalfootgroupX	226
COMMAND\normalfootnoterule	185
COMMAND\normalfootstart	188, 192
COMMAND\normalfootstartX	225
COMMAND\normalvfootnote	186, 187
COMMAND\normalvfootnote@inserted	187
COMMAND\normalvfootnoteX	224
COMMAND\notbool	370
COMMAND\notefontsetup	392
COMMAND\notefontsizeX	50, 392
COMMAND\notenumfont	392
COMMAND\notenumfontX	49, 392
COMMAND\notesXwidthliketwocolumns	393
COMMAND\noteswidthliketwocolumnsX	54, 393, 454, 456
COMMAND\num@lines	152, 178
COMMAND\numberlinefalse	21, 466
COMMAND\numberlinetrue	21, 466
COMMAND\numberonlyfirstinline	270, 393
COMMAND\numberonlyfirstintwo-lines	393
COMMAND\numberpstartfalse	19
COMMAND\numberpstarttrue	19, 45, 390, 449, 458, 464, 466

COMMAND\numberstanza	46
COMMAND\numberstanzafalse	59
COMMAND\numberstanzatru	59
COMMAND\numlabfont	22, 55, 105
COMMAND\one@line	152
COMMAND\onehalfspacing	459
COMMAND\onlyXpstart	393
COMMAND\onlysideX	264
COMMAND\page@action	108, 118
COMMAND\page@start	108, 449
COMMAND\pagecontents	108
COMMAND\pagenumbering	286
COMMAND\pageparbreak	391
COMMAND\pageref	62, 294
COMMAND\par	31, 43, 157, 239
COMMAND\par@line	152, 178
COMMAND\par@patch@pagenumbering	286
COMMAND\par@patch@thepage	128, 286
COMMAND\para@footgroup	192
COMMAND\para@footgroupX	237
COMMAND\para@footsetup	191, 447
COMMAND\para@footsetupX	234, 447, 454
COMMAND\para@vfootnoteX	235
COMMAND\parafootfmt	194, 195, 462
COMMAND\parafootfmtX	236
COMMAND\parafootftm	197
COMMAND\parafootftmx	237
COMMAND\parafootftmse	392
COMMAND\parafootsep	393, 452, 457
COMMAND\parafootsepX	52, 110, 392, 393, 462
COMMAND\parafootstart	192
COMMAND\parafootstartX	235
COMMAND\paravfootnote	192, 195
COMMAND\parfillskip	195
COMMAND\parindent	459
COMMAND\parindentX	50, 395, 459, 461
COMMAND\parse@annot	170
COMMAND\parshape	77
COMMAND\parskip	19, 58, 59, 157
COMMAND\pause@numbering	96
COMMAND\pausenumbering	20, 96, 111, 113, 158, 452, 454, 461
COMMAND\pausenumbering@page@num	96
COMMAND\penalty	195
COMMAND\pend	2, 7, 18, 19, 21–23, 74, 132, 134, 137, 144, 152, 154–158, 175, 176, 389, 452, 453, 462–465
COMMAND\preXnotes	456, 462
COMMAND\prenotesX	53, 243, 456
COMMAND\prepare@Xgroupbyline	217, 219
COMMAND\prepare@Xprenotes	242
COMMAND\prev@nopb	382

COMMAND\prev@pb	382
COMMAND\prevlineX	110
COMMAND\prevpageX@num	110
COMMAND\print@Xfootnoterule	456
COMMAND\print@Xnotes	281, 283
COMMAND\print@Xnotes@forpages	455
COMMAND\print@eledsection	161
COMMAND\print@footnoteXrule	456
COMMAND\print@leftmargin@eledsection	371
COMMAND\print@lemma	206
COMMAND\print@line	159
COMMAND\print@notesX@forpages	455
COMMAND\print@rightmargin@eledsection	371
COMMAND\printendlines	250, 256, 301, 395, 447, 449
COMMAND\printlinefootnote	207, 209, 455
COMMAND\printlinefootnotearea	209, 210, 455
COMMAND\printlinefootnotenumbers	207
COMMAND\printlines	188, 205, 210, 211, 250, 301, 395, 447, 449, 455, 460
COMMAND\printnpnum	390, 395
COMMAND\printpstart	206
COMMAND\protect	136, 389
COMMAND\providecommand	219, 447
COMMAND\pstarL	152
COMMAND\pstart	2, 7, 18–23, 73, 74, 118, 132, 137, 141, 144, 152, 155–157, 161, 176, 376, 389, 390, 449–451, 453, 454, 454, 456–458, 461–466
COMMAND\pstartinfofootnote	393
COMMAND\pstartinfofootnoteeverytime	393
COMMAND\pstartnum	175
COMMAND\pstartref	60, 61, 288, 295, 452, 464
COMMAND\pstarts	449, 450
COMMAND\pstarts@readL	152
COMMAND\pstarts@typeset@L	152
COMMAND\raggedX	52
COMMAND\raggedleft	51
COMMAND\raggedright	51
COMMAND\raw@text	152
COMMAND\rbracket	48
COMMAND\read@linelist	110, 112
COMMAND\ref	62, 65, 69
COMMAND\reformatted@	301
COMMAND\reformattedwithpage	301
COMMAND\relax	19, 118, 141, 165, 176, 334, 352, 389
COMMAND\renewcommand	77, 392, 395
COMMAND\reset@current@annot	169
COMMAND\reset@msd@options@iffullpage	345
COMMAND\resetprevline@	110
COMMAND\resetprevpage@	110
COMMAND\resumenumbering	20, 92, 96, 97, 111, 113, 158, 449, 453, 454, 461
COMMAND\right	72
COMMAND\rightctab	363

COMMAND\rightlinenum	22, 104, 447, 449
COMMAND\rightltab	364
COMMAND\rightnoteupfalse	66
COMMAND\rightrtab	364
COMMAND\rightsidenote	309
COMMAND\rightskip	189, 192, 193, 195
COMMAND\rightstartnum	175
COMMAND\rigidbalance	197–199, 201, 395, 460
COMMAND\rigidbalanceX	198, 395, 460
COMMAND\robustify	43
COMMAND\roman	357, 460
COMMAND\rtab	363, 364, 368
COMMAND\rtabtext	365, 368
COMMAND\sameparallelpagenumber	128
COMMAND\sameword	16, 33–37, 126, 144–148, 150, 397, 455, 457, 459, 462, 465
COMMAND\sameword@inedtext	146
COMMAND\saweword	145
COMMAND\scriptsize	105
COMMAND\section	73, 449, 463
COMMAND\section@num	92
COMMAND\sectionmark	370
COMMAND\select@lemm.getFont	55, 182
COMMAND\series	257
COMMAND\series@	257
COMMAND\seriesatbegin	41, 269, 456
COMMAND\seriesatend	41, 269, 456
COMMAND\set@Xtxtbeforenotes	180
COMMAND\set@continuousnumberingforl	97
COMMAND\set@line	141
COMMAND\set@line@action	109, 119
COMMAND\set@txtbeforenotesX	180
COMMAND\setSErefonlypageprefixmore	63, 64, 301, 461, 464
COMMAND\setSErefonlypageprefixsingle	63, 64, 301, 461, 464
COMMAND\setSErefprefixmore	63
COMMAND\setSErefprefixsingle	63
COMMAND\setapprefprefixmore	63, 392
COMMAND\setapprefprefixsingle	63, 65, 392, 460
COMMAND\setcommand@series	271
COMMAND\sethangindentX	204
COMMAND\sethangingsymbol	57, 329, 392, 459
COMMAND\sethanginsymbol	56
COMMAND\setistwofollowinglines	214
COMMAND\setl@dlprbox	310
COMMAND\setline	23, 109, 113, 118, 132, 136, 155, 458
COMMAND\setlinenum	23, 113, 118, 132, 447, 465
COMMAND\setlinenumannotationsep	27, 396, 466
COMMAND\setsmsdatalabel	39
COMMAND\setsmsdataposition	464
COMMAND\setsmsdataseries	39
COMMAND\setprintendlines	250, 253, 449

COMMAND\setprintlines	211, 214, 250, 449
COMMAND\setsidenotesep	67
COMMAND\setsidenotsep	392
COMMAND\setstanzaindent	331
COMMAND\setstanzaindents	57, 330, 389
COMMAND\setstanzapenalties	330
COMMAND\setstanzavalues	330
COMMAND\settoggle@series	271, 450, 454
COMMAND\showlemma	135, 447, 448
COMMAND\showwordrank	36, 146
COMMAND\sidenote@margin	448
COMMAND\sidenotemargin	66, 448, 453
COMMAND\sidenotesep	392
COMMAND\sidepstartnumtrue	20
COMMAND\skip	189
COMMAND\skipnumbering	24, 121, 122, 133, 449, 456, 457
COMMAND\skipnumbering@reg	456
COMMAND\small	49, 50
COMMAND\somemacro	37
COMMAND\special	13
COMMAND\splitmaxdepth	184, 199
COMMAND\splitoff	198
COMMAND\splittopskip	184, 199, 201
COMMAND\stanza	23, 24, 58, 59, 334, 392, 394, 459, 464
COMMAND\stanza@hang	333
COMMAND\stanza@line	333
COMMAND\stanzaindent	57, 331, 455
COMMAND\stanzaindent*	57
COMMAND\stanzaindentbase	330
COMMAND\stanzanumwrapper	59
COMMAND\startlock	21, 23, 109, 133, 334
COMMAND\startstanzahook	392
COMMAND\startsub	23, 108, 131
COMMAND\stopmsd	339
COMMAND\stopmsdata	38, 337
COMMAND\store@annot@to@absline	169
COMMAND\strip@pt	192
COMMAND\strutbox	199
COMMAND\sub@action	108, 119
COMMAND\sub@lock	107
COMMAND\sub@off	116, 291
COMMAND\sub@on	116, 291
COMMAND\subline@num	106–108
COMMAND\sublinenum@rep	447
COMMAND\sublinenumstyle	24, 104, 447
COMMAND\sublinenumincrement	21
COMMAND\sublinenumr@p	104, 447, 449
COMMAND\sublinenumrep	104, 449
COMMAND\sublineref	61, 288, 294
COMMAND\subsectionmark	370

COMMAND\sw@inthisedtext	138
COMMAND\sw@list@inedtext	142, 150
COMMAND\sw@txt	147
COMMAND\swnoexpands	37, 465
COMMAND\symlinenum	393
COMMAND\symlinenenum	392
COMMAND\sza@penalty	333
COMMAND>tag	455
COMMAND{text	387
COMMAND{text $\langle language \rangle$	50
COMMAND{textbeforenotesX	180
COMMAND{textcolor	78
COMMAND{textheight	77
COMMAND{textsuperscript	26, 90, 168
COMMAND\the	128, 447
COMMAND\thefootnoteA	39
COMMAND\thefootnoteX	451
COMMAND\thelabidx	324, 325
COMMAND\thepage	113, 128, 286
COMMAND\thepstart	19, 396
COMMAND\thepstartL	450
COMMAND\thepstartR	450
COMMAND\thestanza	59
COMMAND>this@crossref@end	219
COMMAND>this@line@list@version	126
COMMAND>this@section@next@page@num	96
COMMAND>this@section@page@num	109
COMMAND>thisfootnote	227
COMMAND\threecol@begin@insert	200
COMMAND\threecolfootfmt	200, 462
COMMAND\threecolfootfmtX	233
COMMAND\threecolfootgroup	199
COMMAND\threecolfootgroupX	233
COMMAND\threecolfootsetup	199
COMMAND\threecolfootsetupX	232
COMMAND\threecolvfootnote	199
COMMAND\threecolvfootnote@inserted	199
COMMAND\threecolvfootnoteX	232
COMMAND\toendnotes	31, 248, 462
COMMAND\twocolfootfmt	462
COMMAND\twocolfootfmtX	230
COMMAND\twocolfootgroupX	231
COMMAND\twocolfootsetupX	230
COMMAND\twocolvfootnoteX	230
COMMAND\twolines	270, 393
COMMAND\twolines@A	270
COMMAND\twolines@B	270
COMMAND\twolines@C	270
COMMAND\twolinesbutnotmore	393
COMMAND\twolinesonlyinsamepage	393

COMMAND\txtbeforeXnotes	393
COMMAND\txtbeforenotesX	53, 465
COMMAND\txtbeforenotesonlyonceX	53, 465
COMMAND\uline	40
COMMAND\unhbox	158, 193
COMMAND\unpenalty	194, 195
COMMAND\unskip	195
COMMAND\unvxh	195, 394
COMMAND\unvxhX	394
COMMAND\upbracefill	362
COMMAND\usingcritext	388, 391
COMMAND\usingedtext	388, 391
COMMAND\vAfootnote	184
COMMAND\vadjust	130
COMMAND\variant	32
COMMAND\vbox	154, 157, 193, 198, 241
COMMAND\vfootnote	184, 189, 192, 199
COMMAND\vl@dbfnote	221, 448
COMMAND\vl@disnote	309
COMMAND\vl@dlsnote	309
COMMAND\vl@dosnote	309
COMMAND\vl@drsnote	309
COMMAND\vnumfootnoteX	449
COMMAND\vszie	54, 77
COMMAND\vspli	178
COMMAND\waklam	362
COMMAND\waklamec	362
COMMAND\wapunktel	362
COMMAND\wastricht	362
COMMAND\widthX	54, 395, 461
COMMAND\wrap@edcrossref	294, 454
COMMAND\wrapcontentX	50, 462
COMMAND\wrapped@bodyfootmarkX	238
COMMAND\wrapped@footfootmarkX	238
COMMAND\x...	61
COMMAND\xabslineref	295
COMMAND\xannotationref	61
COMMAND\xdef	98, 334
COMMAND\xflagref	61, 295, 395, 460
COMMAND\xleft@appenditem	99, 135
COMMAND\xlineref	61, 395, 460
COMMAND\xpageref	61
COMMAND\xparse	37
COMMAND\xpstartref	61, 452, 465
COMMAND\xr	65
COMMAND\xright@appenditem	98, 99
COMMAND\xsublineref	61
COMMAND\xxref	62, 297, 304, 452, 455, 462
COMMAND\xxxmatter	286
ENVIRONMENTastanza	460

ENVIRONMENTedarrayc	368
ENVIRONMENTedarrayl	368
ENVIRONMENTedarrayr	368
ENVIRONMENTedtabularc	368
ENVIRONMENTedtabularl	368
ENVIRONMENTedtabularr	368
ENVIRONMENTledgroup	83, 316, 395, 460
ENVIRONMENTledgroupsized	316
PACKAGE(r)(e)ledmac	41
PACKAGEEledmac	108, 321, 390, 391, 455, 456
PACKAGEEledpar	456
PACKAGEEtoolbox	82
PACKAGEParallel	398
PACKAGEReledmac	394, 395
PACKAGEamsgen	346
PACKAGEamsmath	345, 346
PACKAGEbabel	50, 78, 357, 460
PACKAGEbiblatex	76
PACKAGEbidi	50, 51, 83, 459
PACKAGEccaption	91
PACKAGEcolor	78
PACKAGEcsquotes	464
PACKAGEedmac	1, 6, 11, 13, 14, 79, 210, 219, 288, 330, 387, 398, 447
PACKAGEedstanza	1, 14, 328
PACKAGEeledmac	1, 11, 14–16, 68, 219, 318, 321, 349, 372, 385, 388, 390–392, 451, 453, 455
PACKAGEeledpar	184, 398, 449, 453–455
PACKAGEetex	459
PACKAGEtoolbox	98, 144, 257, 270, 280, 309, 370, 382
PACKAGEfancyhdr	284, 463
PACKAGEfloatrow	76, 395
PACKAGEfootmisc	40, 78, 83, 219, 398, 463
PACKAGEgeometry	15
PACKAGEglossaries	69, 326, 460
PACKAGEhandout	454
PACKAGEhyperlink	264
PACKAGEhyperref	61, 138, 238, 289, 324, 374, 384, 452–454, 461, 464, 467
PACKAGEifluatex	82
PACKAGEifxetex	82
PACKAGEimakeidx	67, 76, 83, 318, 321, 391, 451–453, 455
PACKAGEindextols	326
PACKAGEindextool	391
PACKAGEindextools	67, 76, 83, 92, 318, 321, 326, 391, 455, 460, 463
PACKAGEinputenc	146
PACKAGEledarab	78
PACKAGEledmac	1, 11, 14, 78, 98, 321, 387, 388, 391, 394
PACKAGEledpar	78
PACKAGEMemoir	83, 321, 391, 398, 453
PACKAGEmorewrites	76
PACKAGEmusixtex	453
PACKAGEperpage	460

PACKAGEpolyglossia	48, 78, 183, 205, 460
PACKAGERagged2e	51, 82
PACKAGEReledmac	1, 2, 6, 11, 12, 14–17, 20, 21, 24, 25, 27, 28, 30, 32–34, 37, 38, 40, 43, 44, 47, 50, 51, 53, 55, 57, 59, 61–63, 65, 67–70, 74, 76–80, 99, 102, 108, 109, 112, 113, 116, 126–128, 136, 139, 141, 144, 145, 176, 185, 189, 193, 205, 219, 245, 257, 262, 270, 280, 286, 294, 295, 298, 304, 321, 342, 349, 370, 371, 383, 384, 391, 392, 394–397, 458, 461, 463
PACKAGEReledpar	1, 4, 6, 8, 16, 19, 21, 40, 54, 61, 64, 74–76, 78, 80, 91, 99, 111, 116, 127, 128, 139, 141, 152, 186, 189, 239, 240, 257, 263, 280, 281, 283, 286, 317, 328, 370, 459, 460, 462, 463, 465, 466
PACKAGESuffix	82
PACKAGETabmac	1, 14, 398
PACKAGEulem	40
PACKAGEuninormalize	34
PACKAGEXargs	32, 82
PACKAGEXkeyval	80, 279
PACKAGEXparse	82, 466
PACKAGEXR	5, 65, 304, 461
PACKAGEXref	304
PACKAGEXstring	82, 324

A

\absline@num	1
Abu Kamil Shuja' b. Aslam	13
\actionlines@list	1
\actions@list	1
\add@hookarg@specific@to@cs	1
\add@hooktoggle@specific@to@cs	1
\add@inserts	1
\add@inserts@next	1
\add@msd@	1
\add@msdata	1
\add@msdata@firstlineofpage	1
\add@penalties	1
\add@Xgroupbyline	1
\addtol@denvbody	1
Adelard II	13
\advancelabel@refs	1
\advanceline	1, 23
\Aendnote	30
\affixline@num	1
\affixpstart@num	1
\affixside@note	1
\Afootnote	29
\afternoteX	52
\afterruleX	53
\ampersand	1, 59
\annot@list	1
\annotationref	1, 60
\append@notesX	1
\append@Xnotes	1

\applabel	1, 63
\appref	1, 63
\apprefwithpage	1, 63
\arrangementX	1, 42
\arrangementX@normal	1
\arrangementX@paragraph	1
\arrangementX@threecol	1
\arrangementX@twocol	1
\at@every@pend	1
\AtEndEveryPend	1, 19
\AtEveryPend	1, 19
\AtEveryPstart	1, 19
\AtEveryStanza	1, 58
\AtEveryStopStanza	1, 59
\AtStartEveryPstart	1, 19
\AtStartEveryStanza	1, 58
\autopar	1, 18

B

\ballast	77
\ballast@count	1
Beeton, Barbara Ann Neuhaus Friend	19
\beforeeledchapter	1
\BeforeEveryStopStanza	1, 59
\beforeinsertingX	51
\beforeinsertion@X	1
\beforenotesX	53
\beginnumbering	1, 17
\Bendnote	30
\Bfootnote	29
\bhookgroupX	53
\bhooknoteX	51
\bodyfootmarkA	39
\boxfootnotenumbers	1
Bredon, Simon	13
Breger, Herbert	14, 349
Brey, Gerhard	13
Busard, Hubert L. L.	13
\bypage@false	1
\bypage@true	1
\bypstart@false	1
\bypstart@true	1

C

\c@addcolcount	1
\c@ballast	1
\c@firstlinenum	1
\c@firstsublinenum	1
\c@labidx	1
\c@linenumincrement	1

\c@sublinenumincrement	1
\Cendnote	30
\Cfootnote	29
\ch@ck@l@ck	1
\ch@cksub@l@ck	1
\chapter	1
\check@pb@in@verse	1
Chester, Robert of	13
Claassens, Geert H. M.	14
\colalignX	51
\continuousnumberingwithcolumns@sync@linenumber@singletext	1
Copernicus, Nicolaus	13
\critext	387
\ctab	1
\ctabtext	1
\current@annot	1

D

Dekker, Dirk-Jan	78
\Dendnote	30
\Dfootnote	29
\disable@endnotes	1
\disable@familiarnotes	1
\disable@notes	1
\disable@sidenotes	1
\disablel@dtabfeet	1
\do@actions	1
\do@actions@fixedcode	1
\do@actions@next	1
\do@ballast	1
\do@feet@custom@order	1
\do@feetX	1
\do@insidelinehook	1
\do@line	1
\do@linehook	1
\do@lockoff	1
\do@lockoffL	1
\do@lockon	1
\do@clockonL	1
\do@Xfeet	1
\doedindexlabel	1
\doendnotes	1, 30
\doendnotesbysection	1, 30
\doinsidelinehook	1, 27
\doinsidethislinehook	1, 28
\dolinehook	1, 27
\dosplits	1
Downes, Michael	77, 193, 195
\dummy@edindex	1
\dummy@edtext	1

\dummy@edtext@showlemma	1
\dummy@ref	1

E

\edaftertab	1, 72, 363
edarrayc (environment)	70
edarrayl (environment)	70
edarrayr (environment)	70
\edatleft	1, 72
\edatright	1, 72
\edbforetab	1, 72, 363
\edfilldimen	1
\edfont@info	1
\edindex	1, 67
\edindexlab	1, 69
\EDLABEL	1
\edlabel	1, 60
\edlabelE	1, 63
\edlabelS	1, 63
\edlabelSE	1, 63
\edlineref	1, 60
\edmakelabel	1, 62
\edpageref	1, 60
\edrowfill	1, 71
\EDTAB	1
\edtabcolsep	1, 70
\EDTABINDENT	1
\edtabindent	1
\EDTABtext	1
edtabularc (environment)	70
edtabularl (environment)	70
edtabularr (environment)	70
\EDTEXT	1
\edtext	1, 28
\edvertdots	1, 72
\edvertline	1, 72
\Eendnote	30
\Efootnote	29
\eled@chapter	1
\eled@section	1
\eled@sectioning@out	1
\eled@subsection	1
\eled@subsubsection	1
\eledchapter	1
\eledchapter*	1
\eledsection	1
\eledsection*	1
\eledsubsection	1
\eledsubsection*	1
\eledsubsubsection	1

\eledsubsubsection*	1
\enablel@dtabfeet	1
\end@lemmas	1
\endashchar	1
\endline@num	1
\endlock	1, 23
\endminipage	1
\endnumbering	1, 17
\endpage@num	1
\endprint	1
\endquotation	1
\endquote	1
\endsub	1, 23
\endsubline@num	1
environments:	
edarrayc	70
edarrayl	70
edarrayr	70
edtabularc	70
edtabularl	70
edtabularr	70
ledgroup	60
ledgroupsized	60
minipage	60
Euclid	13
\extensionchars	1, 75

F

\f@x@cks	1
Fairbairns, Robin	40
\first@linenum@out@false	1
\first@linenum@out@true	1
\firstlinenum	1, 21
\firstseriesX@	1
\firstsublinenum	1, 21
\firstXseries@	1
\flag@end	1
\flag@end@later	1
\flag@end@RTL	1
\flag@start	1
\flag@start@later	1
\flag@start@RTL	1
\flagstanza	1, 59
\flush@notes	1
\fnpos	1, 41
Folkerts, Menso	13
\footfootmarkA	39
\footfudgefiddle	1, 77
\footnote	1
\footnoteA	39

\footnoteB	39
\footnoteC	39
\footnoteD	39
\footnoteE	39
\footnotelang@lua	1
\footnotelang@poly	1
\footnoteoptions@	1
\footnoteXmark	40
\footnoteXtext	40
\footnoteskip	1
\fullstop	1

G

Gädeke, Nora	14
\get@edindex@hyperref	1
\get@edindex@ledinnote@command	1
\get@fnmark	1
\get@fnmarkX	1
\get@index@command	1
\get@linelistfile	1
\get@sw@txt	1
\get@thisfootnote	1
\get@thisfootnoteX	1
\getline@num	1
\gl@p	1

H

\h@num	1
\hangindentX	50
\hidenumbering	1, 24
\hidenumberingonleftpage	1, 24
\hidenumberingonrightpage	1
\Hilfsbox	1
\hilfsbox	1
\hilfscount	1
\HILFSskip	1
\Hilfsskip	1
\hilfsskip	1
\hookarg@specific	1
\hooktoggle@specific	1
\hsizethreecolX	52
\hsizetwocolX	52
\Hy@raisedlink@left	1
\hyperlinkformat	1
\hyperlinkformatR	1
\hyperlinkR	1

I

\if@addsw	1
\if@edtext@secondarg@	1

\if@eled@sectioning	1
\if@firstlineofpage	1
\if@led@nofoot	1
\if@ledgroup	1
\if@lemmacommand@	1
\if@msdata@insertedfrompreviouspage	1
\if@noeled@sec	1
\if@noneed@Footnote	1
\if@RTL	1
\ifafterendnumberingR	1
\ifat@every@pend@star@	1
\ifat@every@pstart@star@	1
\ifautopar@pause	1
\ifbypage@	1
\ifbypage@R	1
\ifbypstart@	1
\ifbypstart@R	1
\ifeledmaccompat@	1
\iffirst@linenum@out@	1
\ifindtl@innote	1
\ifindtl@notenumber	1
\ifinserthangingsymbol	1
\ifinstanza	1
\ifl@d@dash	1
\ifl@d@elin	1
\ifl@d@esl	1
\ifl@d@pnum	1
\ifl@d@ssub	1
\ifl@d@Xmorethanwolines	1
\ifl@d@Xtwolines	1
\ifl@d@nd@X	1
\ifl@dhidenumber	1
\ifl@dmemoir	1
\ifl@dpaging	1
\ifl@dpairing	1
\ifl@dprintingcolumns	1
\ifl@dprintingpages	1
\ifl@dskipnumber	1
\ifl@dskipversenumber	1
\ifl@dstartendok	1
\ifl@footmisc	1
\ifl@imakeidx	1
\ifl@indextools	1
\ifledfinal	1, 75
\ifledgroupnotesL@	1
\ifledgroupnotesR@	1
\iflednopbinverse	1
\ifledRcol	1
\ifledRcol@	1
\ifnocritical@	1

\ifnoend@	1
\ifnofamiliar@	1
\ifnoledgroup@	1
\ifnoquotation@	1
\ifnoresetlinenumannotation@	1
\ifnoteschanged@	1
\ifnumberedpar@	1
\ifnumbering	1
\ifnumberingR	1
\ifnumberline	1
\ifnumberstanza	1
\ifparapparatus@	1
\ifparledgroup	1
\ifprevpgnotnumbered	1
\ifpst@rteL	1
\ifresumenumbers@start	1
\ifsameparallelpagenumber	1
\ifseriesbefore	1
\ifsidepstartnum	1
\ifstopmsdata@inserted@	1
\ifsublines@	1
\ifwidthliketwocolumns	1
\ifXendinsertsep@	1
\ifxindy@	1
\ifxindyhyperref@	1
\initnumbering@quote	1
\initnumbering@reg	1
\insert@count	0, 1
\insert@msdata	1
\insert@txtbeforenotesX	1
\insert@Xtxtbeforenotes	1
\inserthangingymbol	1
\insertlines@list	1
\insertparafootsepX	1
\inserts@list	1

J

Jayaditya	14
---------------------	----

K

Kabelschacht, Alois	179
\keep@this@crossref@forinserting	1

L

\l@advance@parledgroup@beforenormalnotes	1
\l@d@add	1
\l@d@nums	1
\l@d@section	1
\l@d@set	1
\l@d@Xend	1

\l@dampcount	1
\l@dbfnote	1
\l@dcheckcols	1
\l@dcheckstartend	1
\l@dchset@num	1
\l@dcolcount	1
\l@collect@@body	1
\l@collect@body	1
\l@dcolwidth	1
\l@dcsnote	1
\l@dcsonotetext	1
\l@dcsonotetext@1	1
\l@dcsonotetext@r	1
\l@ddodoreinxtrafeet	1
\l@ddoxtrafeet	1
\l@dedbeginmini	1
\l@dedendmini	1
\l@emptyd@ta	1
\l@end@close	1
\l@end@open	1
\l@end@stuff	1
\l@end@Xfalse	1
\l@end@Xtrue	1
\l@envbody	1
\l@esnote	1
\l@dfambeginmini	1
\l@dfamendmini	1
\l@feetbeginmini	1
\l@feetendmini	1
\l@getline@margin	1
\l@getlock@disp	1
\l@getref@num	1
\l@get sidenote@margin	1
\l@gobbleoptarg	1
\l@isnote	1
\l@label@parse	1
\l@lld@ta	1
\l@lp@rbox	1
\l@lsn@te	1
\l@lsnote	1
\l@make@labels	1
\l@modforedtext	1
\l@nullfills	1
\l@numpstartsL	1
\l@oldold@footnotetext	1
\l@dp@rsefootspec	1
\l@parsedendline	1
\l@parsedendpage	1
\l@parsedendsub	1
\l@parsedstartline	1

\l@dparsedstartpage	<u>1</u>
\l@dparsedstartsub	<u>1</u>
\l@dparsefootspec	<u>1</u>
\l@dpush@begins	<u>1</u>
\l@drd@ta	<u>1</u>
\l@dref@undefined	<u>1</u>
\l@drestorefills	<u>1</u>
\l@drestoreforedtext	<u>1</u>
\l@drp@rbox	<u>1</u>
\l@drsn@te	<u>1</u>
\l@drsnote	<u>1</u>
\l@dsetmaxcolwidth	<u>1</u>
\l@dskipnumberfalse	<u>1</u>
\l@dskipnumbertrue	<u>1</u>
\l@dtabaddcols	<u>1</u>
\l@dtabnoexpands	<u>1</u>
\l@dunboxmpfoot	<u>1</u>
\l@dunhbox@line	<u>1</u>
\l@zeropenalties	<u>1</u>
\l@secondmandarg	<u>1</u>
\l@the@c@page	<u>1</u>
\l@wrap@ifnotemptybox	<u>1</u>
\l@wrapcs@ifnotemptybox	<u>1</u>
\label	62
\labelpstartfalse	<u>1</u>
\labelpstarttrue	<u>1, 20</u>
\labelref@list	<u>1</u>
\labelrefsparseline	<u>1</u>
\labelrefsparsesubline	<u>1</u>
\last@page@num	<u>1</u>
Lavagnino, John	13
\led@check@nopb	<u>1</u>
\led@check@pb	<u>1</u>
\led@err@AutoparNotNumbered	<u>1</u>
\led@err@BadAction	<u>1</u>
\led@err@edtextoutsidepstart	<u>1</u>
\led@err@EdtextWithoutFootnote	<u>1</u>
\led@err@FootnoteNotInSecondArgEdtext	<u>1</u>
\led@err@HighEndColumn	<u>1</u>
\led@err@LineationInNumbered	<u>1</u>
\led@err@LowStartColumn	<u>1</u>
\led@err@ManyLeftnotes	<u>1</u>
\led@err@ManyRightnotes	<u>1</u>
\led@err@ManySidenotes	<u>1</u>
\led@err@NumberingNotStarted	<u>1</u>
\led@err@NumberingShouldHaveStarted	<u>1</u>
\led@err@NumberingStarted	<u>1</u>
\led@err@NumberingWithoutPstart	<u>1</u>
\led@err@PendInEdtext	<u>1</u>
\led@err@PendNoPstart	<u>1</u>

\led@err@PendNotNumbered	1
\led@err@PstartInEdtext	1
\led@err@PstartInPstart	1
\led@err@PstartNotNumbered	1
\led@err@ReverseColumns	1
\led@err@toendnotes@outsidenumbering	1
\led@err@TooManyColumns	1
\led@err@UnequalColumns	1
\led@error@fail@patch@@doclearpage	1
\led@error@fail@patch@@iiminipage	1
\led@error@fail@patch@@makecol	1
\led@error@fail@patch@@reinserts	1
\led@error@fail@patch@endminipage	1
\led@error@PackageAfterEledmac	1
\led@mess@NotesChanged	1
\led@mess@SectionContinued	1
\led@nopb	1
\led@nopbnum	1
\led@pb	1
\led@pb@setting	1
\led@pbnum	1
\led@reinit@index@fornote	1
\led@set@index@fornote	1
\led@toksa	1
\led@toksb	1
\led@warn@AppLabelOutSecondArgEdtext	1
\led@warn@BadAction	1
\led@warn@BadAdvancelineLine	1
\led@warn@BadAdvancelineSubline	1
\led@warn@BadLineation	1
\led@warn@BadLinenummargin	1
\led@warn@BadLockdisp	1
\led@warn@BadSetline	1
\led@warn@BadSetlinenum	1
\led@warn@BadSidenotemargin	1
\led@warn@BadSubblockdisp	1
\led@warn@DuplicateLabel	1
\led@warn@edinde@outsidenumbering	1
\led@warn@LineFileObsolete	1
\led@warn@NoFile	1
\led@warn@NoIndexFile	1
\led@warn@NoMarginpars	1
\led@warn@RefUndefined	1
\led@warn@SeriesStillExist	1
\led@warning@hsizex@deprecated	1
\led@warning@msdatawithoutstop	1
\led@warning@preXnotes@deprecated	1
\led@warning@Xhsizex@deprecated	1
ledgroup (environment)	60
ledgroupsized (environment)	60

\ledinnoteinner	1, 66
\ledinnote	1
\ledinnotehyperpage	1
\ledinnotemark	1
\leddleftnote	1, 66
\ledlinenum	1
\ledllfill	1
\ledlsnotefontsetup	1, 66
\ledlsnotesep	1, 66
\ledlsnotewidth	1, 66
\lednopb	1, 74
\lednopbinversetrue	75
\lednopbnum	1
\ledouternote	1, 66
\ledpb	1, 74
\ledpbnum	1
\ledpbsetting	1, 75
\ledrightnote	1, 66
\ledrlfill	1
\ledrsnotefontsetup	1, 66
\ledrsnotesep	1, 66
\ledrsnotewidth	1, 66
\ledsectnomark	1
\ledsectnotoc	1
\ledsetnormalparstuff@common	1
\ledsetnormalparstuffX	1
\ledsidenote	1, 66
\leftctab	1
\leftlinenum	1, 22
\leftltab	1
\leftnoteupfalse	66
\leftpstartnum	1
\leftrtab	1
Leibniz	14
\lemma	1, 31
\letsforverteilen	1
\line@list	1
\line@list@stuff	1
\line@list@version	1
\line@margin	1
\line@num	1
\line@set	1
\lineannot	1, 26
\lineannot@set	1
\lineation	1, 22
\linenum	1, 32
\linenum@out	1
\linenumannotation	1, 24
\linenumberlist	1, 21
\linenumberstyle	1, 24

\linenumincrement	1, 21
\linenummargin	1, 22
\linenumr@p	1
\linenumrep	1
\linenumsep	1, 22
\linerangesep@	1
\list@clear	1
\list@clearing@reg	1
\list@create	1
\lock@disp	1
\lock@off	1
\lock@on	1
\lockdisp	1, 23
Lorch, Richard	13
\ltab	1
\ltabtext	1
Luecking, Dan	82

M

\m@mmf@check	1
\m@mmf@prepare	1
\M@sect	1
\makehboxofhboxes	1
\managesanza@modulo	1
\maxhnotesX	54
Mayer, Gyula	14
\measurembody	1
\measuremcell	1
\measuremrow	1
\measuretbody	1
\measuretcell	1
\measuretrow	1
Middleton, Thomas	14, 106
\minipage (environment)	60
Mittelbach, Frank	13
\morenoexpands	1, 77
\mp@append@notesX	1
\mp@append@Xnotes	1
\mpfnpos	1, 41
\mpnormalfootgroup	1
\mpnormalfootgroupX	1
\mpnormalvfootnote	1
\mpnormalvfootnote@inserted	1
\mpnormalvfootnoteX	1
\mppara@footgroupX	1
\mppara@vfootnoteX	1
\mpparafootgroup	1
\mpparavfootnote	1
\mpthreeocolfootgroup	1
\mpthreeocolfootgroupX	1

\mpthreeecolfootsetup	1
\mpthreeecolfootsetupX	1
\mptwocolfootgroup	1
\mptwocolfootgroupX	1
\mptwocolfootsetup	1
\mptwocolfootsetupX	1
\msdata	1, 38
\msdata@c	1
\msdata@cR	1
\multfootsep	1, 40
\multiplefootnotemarker	1

N

\n@num	1
\n@num@stanza	1
\new@line	1
\newhookarg@specific	1
\newhookcommand@series	1
\newhookcommand@series@reload	1
\newhooktoggle@series	1
\newhooktoggle@series@reload	1
\newhooktoggle@specific	1
\newseries@	1
\newverse	1
\NEXT	1
\next@line@list@stuff	1
\no@expands	1
\noeledsec	74
\nomk@	1
\normal@footnotemarkX	1
\normal@page@break	1
\normal@pars	1
\normalbfnoteX	1
\normalbodyfootmarkX	1
\normalfootfmt	1
\normalfootfmtX	1
\normalfootfootmarkX	1
\normalfootgroup	1
\normalfootgroupX	1
\normalfootnoterule	1
\normalfootnoteruleX	1
\normalfootstart	1
\normalfootstartX	1
\normalvfootnote	1
\normalvfootnote@inserted	1
\normalvfootnoteX	1
\notefontsizeX	50
\notenumfontX	49
\noteschanged@false	1
\noteschanged@true	1

\noteswidthliketwocolumnsX	54
\nulledindex	1
\nullsetzen	1
\num@lines	1
\numberedpar@false	1
\numberedpar@true	1
\numberingfalse	1
\numberingtrue	1
\numberlinefalse	21
\numberlinetrue	21
\numberpstartfalse	1, 19
\numberpstarttrue	1, 19
\numberstanzafalse	59
\numberstanzatrue	59
\numlabfont	1, 55

O

\old@hsize	1
\one@line	1
optionafter	26
optionauxdir	16, 462
optionbefore	26
optioncontinuousnumberingwithcolumns	92, 160, 167, 461, 466
optioninnnote	460
optioninnote	460
optionlinerangesep	279
optionnocritical	460
optionnoeledsec	376, 462
optionnoend	460
optionnoppenalties	77
optionnoprefix	65, 467
optionnoresetlinenumannotation	25, 466
optionnotenumber	460
optionprefixmore	65, 467
optionsameparallelpagENUMer	466
optionswcaseinsensitive	33, 465

P

\page@action	1
\page@num	1
\pagelinesep	1, 68
\pageref	62
\par@line	1
\par@patch@pagENUMer	1
\par@patch@thEPAGE	1
\para@footgroupX	1
\para@footsetup	1
\para@footsetupX	1
\para@vfootnoteX	1
\parafootfmt	1

\parafootfmtX	1
\parafootgroup	1
\parafootsepX	52
\parafootstart	1
\parafootstartX	1
\paravfootnote	1
\parindentX	50
\parse@annot	1
\pausenumbering	1, 20
\pausenumbering@page@num	1
\pend	1, 17
Plato of Tivoli	13
\postbodyfootmark	1
\prebodyfootmark	1
\prenotesX	53
\prepare@edindex@fornote	1
\prepare@prenotesX	1
\prepare@Xgroupbyline	1
\prepare@Xprenotes	1
\prev@nopb	1
\prev@pb	1
\prevpage@num	1
\print@eledsection	1
\print@footnoteXrule	1
\print@leftmargin@eledsection	1
\print@lemma	1
\print@line	1
\print@notesX	1
\print@rightmargin@eledsection	1
\print@Xfootnoterule	1
\print@Xnotes	1
\printendlines	1
\printlineendnote	1
\printlineendnotearea	1
\printlinefootnote	1
\printlinefootnotearea	1
\printlinefootnotenumbers	1
\printlines	1
\printpnum	1
\printpstart	1
\printsymlineendnotearea	1
\printsymlinefootnotearea	1
\printXafternumber	1
\printXbeforenumber	1
\pstart	1, 17
\pstarteref	1
\pstartnum	1
\pstartref	60
\pstarts@read@L	1
\pstarts@typeset@L	1

Q	
\quotation	<u>1</u>
\quote	<u>1</u>
R	
\raggedX	<u>52</u>
\raw@text	<u>1</u>
\rbracket	<u>1</u>
\read@linelist	<u>1</u>
\ref	<u>62</u>
\ref@reg@later	<u>1</u>
\Relax	<u>1</u>
\reledmac@error	<u>1</u>
\reledmac@warning	<u>1</u>
\removehboxes	<u>1</u>
\reset@current@annot	<u>1</u>
\reset@msd@options@iffullpage	<u>1</u>
\resetprevline@	<u>1, 110</u>
\resetprevpage@	<u>1</u>
\resetprevpage@num	<u>110</u>
\restore@endnotes	<u>1</u>
\restore@familiarnotes	<u>1</u>
\restore@notes	<u>1</u>
\restore@sidenotes	<u>1</u>
\resumenumbering	<u>1, 20</u>
\rightctab	<u>1</u>
\rightlinenum	<u>1, 22</u>
\rightltab	<u>1</u>
\rightnoteupfalse	<u>66</u>
\rightrtab	<u>1</u>
\rightstartnum	<u>1</u>
\rigidbalance	<u>1</u>
\rigidbalanceX	<u>1</u>
\rtab	<u>1</u>
\rtabtext	<u>1</u>
S	
Sacrobosco	<u>14</u>
\sameword	<u>1, 33</u>
\sameword@inedtext	<u>1</u>
Schöpf, Rainer	<u>13</u>
\section@num	<u>1</u>
\select@lemmafont	<u>1</u>
\select@lemmafont	<u>1, 55</u>
\SRef	<u>1, 63</u>
\SRefonlypage	<u>63</u>
\SRefwithpage	<u>1, 63</u>
\series	<u>1</u>
\seriesatbegin	<u>1, 41</u>
\seriesatend	<u>1, 41</u>

\set@continuousnumberingforL	1
\set@line	1
\set@line@action	1
\set@txtbeforenotesX	1
\set@Xtxtbeforenotes	1
\setapprefprefixmore	63
\setapprefprefixsingle	63
\setcommand@series	1
\sethangindentX	1
\sethangingsymbol	1, 57
\setistwofollowinglines	1
\setl@dlp@rbox	1
\setl@drpr@box	1
\setline	1, 23
\setlinenum	1, 23
\setlinenumannotationsep	1, 27
\setmcellcenter	1
\setmcellleft	1
\setmcellright	1
\setmrowcenter	1
\setmrowleft	1
\setmrowright	1
\setmsdatalabel	1, 39
\setmsdataposition	1, 39
\setmsdataseries	1, 39
\setnoteswidthliketwocolumnsX@	1
\setnotesXpositionliketwocolumns@	1
\setprintendlines	1
\setprintlines	1
\setSErefonlypageprefixmore	63
\setSErefonlypageprefixsingle	63
\setSErefprefixmore	63
\setSErefprefixsingle	63
\setsidenotessep	67
\setstanzaindent	1, 56
\setstanzapenalties	1, 57
\setstanzavalues	1
\settcellcenter	1
\settcellleft	1
\settcellright	1
\settoggle@series	1
\settrowcenter	1
\settrowleft	1
\settrowright	1
\setXnotespositionliketwocolumns@	1
\setXnoteswidthliketwocolumns@	1
\showlemma	1, 75
\showwordrank	1, 36
\sidenote@margin	1
\sidenotemargin	1, 66

\sidepstartnumtrue	20
\skip@lockoff	1
\skipnumbering	1, 24
\splitoff	1
\spreadmath	1, 71
\spreadtext	1, 71
\stanza	1, 55
\stanza@count	1
\stanza@hang	1
\stanza@line	1
\stanzaindent	1, 57
\stanzaindent*	1, 57
\stanzaindentbase	1, 56
\stanzanumwrapper	1, 59
\startlock	1, 23
\startsub	1, 23
\stepl@dcolcount	1
\stopmsdata	1, 38
\store@cannot@to@absline	1
\strip@szacnt	1
\sub@action	1
\sub@lock	1
\sub@off	1
\sub@on	1
\subline@num	1
\sublinenumberstyle	1, 24
\sublinenumincrement	1, 21
\sublinenumr@p	1
\sublinenumrep	1
\sublineref	1, 60
\sublines@false	1
\sublines@true	1
\subblock@disp	1
\subblockdisp	1
Sullivan, Wayne	13, 14, 77, 91, 96, 193, 194, 288, 328
\sw@noexpand	1
\swnoexpands	37
\sza@penalty	1

T

\tabHilfbox	1
\tabhilfbox	1
\theaddcolcount	1
\theedtext	1
\theendpageline	1
\thefootnoteA	39
Theodosius	14
\thepageline	1
\thepar@page	1
\thepstart	1, 19

\thestanza	1, 59
\thestartpageline	1
\this@line@list@version	1
\this@section@last@page@num	1
\this@section@page@num	1
\threecol@begin@insert	1
\threecolfootfmt	1
\threecolfootfmtX	1
\threecolfootgroup	1
\threecolfootgroupX	1
\threecolfootsetup	1
\threecolfootsetupX	1
\threecolvfootnote	1
\threecolvfootnote@inserted	1
\threecolvfootnoteX	1
\toendnotes	1, 31
\toendnotes*	1
\twocolfootfmt	1
\twocolfootfmtX	1
\twocolfootgroup	1
\twocolfootgroupX	1
\twocolfootsetup	1
\twocolfootsetupX	1
\twocolvfootnote	1
\twocolvfootnote@inserted	1
\twocolvfootnoteX	1
\txtbeforenotesonlyonceX	53
\txtbeforenotesX	53

U

\unvxhX	1
---------------	---

V

Vamana	14
\variab	1
\vbfnoteX	1
\vl@dbfnote	1
\vl@dcsnote	1
\vl@disnote	1
\vl@dlsnote	1
\vl@dosnote	1
\vl@drsnote	1
\vnumfootnoteX	1

W

Whitney, Ron	13
\widthX	54
\wrap@edcrossref	1
\wrapcontentX	50
\wrapped@bodyfootmarkX	1

\wrapped@footfootmarkX	1
Wujastyk, Dominik	13

X

\X@atbegininsertion	1
\X@beforeinsertion	1
\X@doreinfeet	1
\xabslineref	1
\Xafterlemmaseparator	48
\Xafternote	52
\Xafternumber	46
\Xafterrule	53
\Xaftersymlinenum	46
\xannotationref	1, 61
\Xarrangement	1, 42
\Xarrangement@normal	1
\Xarrangement@paragraph	1
\Xarrangement@threecol	1
\Xarrangement@twocol	1
\Xbeforeinserting	51
\Xbeforelemmaseparator	48
\Xbeforenotes	53
\Xbeforenumber	44, 46
\Xbeforesymlinenum	46
\Xhookgroup	53
\Xhooknote	51
\Xboxlinenum	47
\Xboxlinenumalign	47
\Xboxsymlinenum	47
\Xcolalign	51
\xedindex	1
\xedlabel	1
\xedtext	1
\Xendafterlemmaseparator	49
\Xendafternote	55
\Xendafterpagenumber	44
\Xendaftersymlinenum	46
\Xendaftrenumber	46
\Xendahookinplaceofnumber	48
\Xendahooklinenum	48
\Xendbeforelemmaseparator	49
\Xendbeforenumber	46
\Xendbeforepagenumber	44
\Xendbeforesymlinenum	46
\Xendbhookinplaceofnumber	48
\Xendbhooklinenum	48
\Xendbhooknote	51
\Xendboxendlinenumalign	48
\Xendboxlinenum	48
\Xendboxlinenumalign	48

\Xendboxstartlinenumalign	48
\Xendboxsymlinenum	47
\Xendhangindent	50
\Xendinplaceoflemmaseparator	49
\Xendinplaceofnumber	47
\Xendinplaceofpagenumber	44
\Xendlemmadisablefontselection	49
\Xendlemmafont	49
\Xendlemmaseparator	48
\Xendlinenumannotationposition	26
\Xendlineprefixmore	44
\Xendlineprefixsingle	44
\Xendlinerangeseparator	44
\Xendmorethanwolines	45
\Xendnoidenticallinenumannotation	27
\Xendnonumber	45
\Xendnotefontsize	50
\Xendnotenumfont	49
\Xendnumberonlyfirstinline	43
\Xendnumberonlyfirstintwolines	43
\Xendpagenumberonlyfirst	43
\Xendparagraph	55
\Xendsep	55
\Xendsublinesep	46
\Xendsymlinenum	43
\Xendsympagenum	44
\Xendtwolines	45
\Xendtwolinesbutnotmore	45
\Xendtxtbeforenotes	53
\Xendwrapcontent	50
\xflagref	1
\Xgroupbyline	52
\Xgroupbylineseparatetwolines	52
\Xhangindent	50
\Xhsizethreecol	51
\Xhsizetwocol	51
\Xinplaceoflemmaseparator	48
\Xinplaceofnumber	47
\Xinsertparafootsep	1
\Xledsetnormalparstuff	1
\xleft@appenditem	1
\Xlemmadisablefontselection	49
\Xlemmafont	49
\Xlemmaseparator	48
\Xlinenumannotationposition	26
\Xlinenumannotationposition@side	1
\Xlinerangeseparator	44
\xlineref	1, 61
\Xmaxhnotes	54
\Xmorethanwolines	44

\Xnidenticalinenumannotation	27
\Xnolemmaseparator	<u>1</u> , 48
\Xnonbreakableafternumber	46
\Xnonumber	45
\Xnotefontsize	49
\Xnotenumfont	49
\Xnoteswidthliketwocolumns	54
\Xnumberonlyfirstinline	43
\Xnumberonlyfirstintwo-lines	43
\Xonlypstart	45
\Xpagelinesep	46
\xpage-ref	<u>1</u> , 61
\Xparafootsep	52
\Xparindent	50
\Xprenotes	<u>1</u> , 53
\Xprenotes@	1
\Xpstart	45
\Xpstarteverytime	45
\xpstartref	<u>1</u> , 61
\XR@test	1
\XR@test@mac	1
\XR@test@mac@test	1
\Xragged	52
\xright@appenditem	1
\Xrigidbalance	1
\Xsethangindent	1
\Xstanza	46
\Xstanzaseparator	46
\Xstorelineinfo	1
\xsublineref	<u>1</u> , 61
\Xsublinesep	23, 46
\Xsublinesepside	23
\Xsymlinenum	43
\Xtoendnotes	31
\Xtwolines	44
\Xtwolinesonlyinsamepage	45
\Xtxtbeforenotes	53
\Xtxtbeforenotesonlyonce	53
\Xunvh	1
\Xwidth	54
\Xwrapcontent	50
\Xwrapdlemma	50
\Xwraplemma	50
\Xwraplinenumannotation@ref	1
\Xwraplinenumannotation@side	1
\xxref	<u>1</u> , 62
 Z	
\zz@000	1
\zz@0000	1

Change History

v0.1.0.

General: First public release 1

v0.2.0.

\ifl@dmemoir: Added \ifl@dmemoir for memoir class having been used 83

\morenoexpands: Added \l@dtabnoexpands to \no@expands 136

\reledmac@error: Added \eledmac@error and replaced error messages 84

General: Added tabmac code, and extended indexing 1

v0.2.1.

\@lab: Removed page setting from \@lab 291

\edlabel: Tweaked \edlabel to get correct page numbers 288

\l@ddodoreinxtrafeet: Renamed \dodoreinxtrafeet to \l@ddodoreinxtrafeet 282

\l@ddoxtrafeet: Renamed \doxtrafeet to \l@ddoxtrafeet 280

\morenoexpands: Removed some \lets from \no@expands. These were in edmac but

Peter Wilson feels that they should not have been as they disabled page/line refs in a
footnotes 136

General: Added text about normal labeling 62

Bug fixes and match with mempatch v1.8 1

Major changes to insert code when memoir is loaded 283

v0.2.2.

\footfudgefiddle: Added \footfudgefiddle 191

\next@line@list@stuff: Added initial write of page number in \line@list@stuff 127

\para@footsetup: Added \footfudgefiddle to \para@footsetup 191

\para@footsetupX: Added \footfudgefiddle to \para@footsetupX 234

General: Improved paragraph footnotes 1

New Dekker example 1

Used \providecommand for \gobblethree to avoid clash with the amsfonts
package 90

v0.3.0.

\@lab: Replaced \the\line@num by \linenumr@p\line@num in \@lab, and similar
for sub-lines 291

\@nl@reg: Added a bunch of code to \@nl for handling \setlinenum 114

\ledlinenum: Added \linenumr@p and \sublinenumr@rep to \leftlinenum and
\rightlinenum 105

\linenumberlist: Added \linenumberlist mechanism 91

\printendlines: Added \linenumr@p and \sublinenumr@p to \printendlines . 253

\printlines: Added \linenumr@p and \sublinenumr@p to \printlines 216

\sublinenumr@p: Added \linenumberstyle and \sublinenumberstyle 104

General: Includes edstanza and more 1

v0.3.1.

General: Not released. Added remarks about the parallel package 1

v0.4.0.

\@iiiminipage: Modified kernel \@iiiminipage and \endminipage to cater for
critical footnotes 315

\Xarrangement@normal: Added minpage footnote setup to \footnormal 186

\edtext: Added \showlemma to \edtext 137

\l@dfteetendmini: Added \l@dfteetbeginmini, \l@dfteetendmini and all their
supporting code 313

\mpnrmalfootgroup: Added \mpnrmalfootgroup 190

\mpnormalvfootnote: Added \mpnormalvfootnote	188
\showlemma: Added \showlemma	91
General: Added final/draft options	80
Added ledgroup environment	316
Added ledgroupsized environment	316
Added minipage, etc., support	1
v0.4.1.	
\do@Xfeet: Changed \do@Xfeet code for easier extensions	281
\edindex: Let elemac take advantage of memoir's indexing	321
\print@Xnotes: Added \opXfeet	281
General: Added code for changing \doclearpage	284
Not released. Minor editorial improvements and code tweaks	1
Only change \footnotetext and \footnotemark if memoir not used	220
v0.5.0.	
\footnotetext: Enabled regular \footnote in numbered text	220
\cypar: Eliminated \marginpar disturbance	305
General: Added left and right sidenotes	305
Added sidenotes, familiar footnotes in numbered text	1
v0.5.1.	
\affixline@num: Changed \affixline@num to cater for sidenotes	170
\l@getsidene@margin: Added \sidenotemargin and \sidene@margin	305
General: Added moveable sidenote	305
Fixed right line numbers killed in v0.5	1
Only change \hsize in ledgroupsized environment otherwise page number can be in wrong place	316
v0.6.0.	
\clopR: Added \pend, \pendR, \clopL and \clopR in anticipation of parallel processing	116
\cnl@reg: Extended \cnl to include the page number	114
\get@thisfootnote: Changed \l@dbfnote and \vl@dbfnote as originals could give incorrect markers in the footnotes	221
\l@the@c@page: Extended \new@line to output page numbers	128
General: Fixed long paragraphs looping	1
Fixed minor typos	1
Prepared for elepar package	1
v0.7.0.	
\cnl@reg: Added \cnl@reg	114
\ref@reg: Added \ref@reg	124
\affixline@num: Added skipnumbering to \affixline@num	170
\do@actions@fixedcode: Added \do@actions@fixedcode	166
\do@actions@next: Added number skipping to \do@actions	165
\do@insidelinehook: Added \do@linehook for use in \do@line	162
\endnumbering: Changed \endnumbering for elepar	95
\f@x@l@cks: Added \ch@cksub@l@ck, \ch@ck@l@ck and \f@x@l@cks	173
\footssplitskips: Added \footssplitskips for use in many footnote styles	184
\get@linelistfile: Added \get@linelistfile	112
\initnumbering@reg: Added \initnumbering@reg	93
\l@advance@parledgroup@beforenormalnotes: Added \l@dunboxmpfoot containing some common code	315
\l@dcsnotetext@r: Added \l@demptyd@ta	163

\l@dgepline@margin: Added \l@dgepline@margin	101
\l@dgeclock@disp: Added \l@dgeclock@disp	103
\l@dgegetsidenote@margin: Added \l@dgegetsidenote@margin	305
\l@dnumpstartsL: Added \l@dnumpstartsL, \ifl@dpairing and \ifpst@rted for/from elepar	91
\l@drsn@te: Added \l@drsn@te and \l@drsn@te for use in \do@line	163
\l@dzopenalties: Added \l@dzopenalties	157
\ledlinenum: Added \ledlinenum for use by \leftlinenum and \rightlinenum .	105
\list@clearing@reg: Added \list@clearing@reg	112
\n@num: Added \n@num	121
\next@line@list@stuff: Deleted \page@start from \line@list@stuff	127
\normalbfnoteX: Removed extraneous space from \normalbfnoteX	226
\pausenumbering@page@num: Changed \resumenumbering for elepar	96
\setprintendlines: Added \setprintendlines for use by \printendlines . . .	250
\setprintlines: Added \setprintlines for use by \printlines	211
\skipnumbering: Added \skipnumbering and supports	133
\sublinenumincrement: Added \firstlinenum, \linenumincrement, \firstsublinenum and \linenumincrement	102
\sublinenumr@p: Using \linenumrep instead of \linenumr@p	104
Using \sublinenumrep instead of \sublinenumr@p	104
\vnumfootnoteX: Removed extraneous space from \vnumfootnoteX	228
General: elemac having been available for 2 years, deleted the commented out original edmac texts	1
Maïeul Rouquette new maintainer	1
Made macros of all messages	84
Replaced all \interAfootnotelinepenalty, etc., by just \interfootnotelinepenalty	1
Tidying up for elepar and ledarab packages	1
v0.8.0.	
General: Bug on endnotes fixed: in a // text, all endnotes will print and be placed at the ends of columns ()	1
v0.8.1.	
General: Bug on \edtext ; \critex ; \lemma fixed: we can now us non-switching commands	1
v0.9.0.	
General: No more ledpatch. All patches are now in the main file.	1
v0.9.1.	
General: Fix some bugs linked to integrating ledpatch on the main file.	1
v0.10.0.	
General: Corrections to \section and other titles in numbered sections	1
v0.11.0.	
General: Makes it possible to add a symbol on each verse's hanging, as in French typography. Redefines the command \hangingsymbol to define the character. . . .	1
v0.12.0.	
\l@dnumpstartsL: Added \ifledRcol and \ifnumberingR for/from elepar	91
General: For compatibility with elepar, possibility to use \autopar on the right side. . .	1
Possibility to number \pstart.	19
Possibility to number the pstart with the commands \numberpstarttrue.	1
v0.12.1.	
General: Don't number \pstarts of stanza.	1

The numbering of \pstarts restarts on each \beginnumbering.	1
v0.13.0.	
\managestanza@modulo: New stanzaindentsrepetition counter to repeat stanza indents every <i>n</i> verses.	331
General: New stanzaindentsrepetition counter to repeat stanza indents every <i>n</i> verses.	56
New stanzaindentsrepetition counter: to repeat stanza indents every <i>n</i> verses.	1
v0.13.1.	
General: \thepstartL and \thepstartR use now \bfseries and not \bf, which is deprecated and makes conflicts with memoir class.	1
v0.14.0.	
\edlabel: Tweaked \edlabel to get correct line number if the command is first element of a paragraph.	288
General: Tweaked \edlabel to get correct line number if the command is first element of a paragraph.	1
v0.15.0.	
\affixline@num: Line numbering can be disabled.	170
\ifinserthangingsymbol: New management of hangingsymbol insertion, preventing undesirable insertions.	329
\printlines: Line numbering can be reset at each pstart.	215
General: Line numbering can be reset at each pstart.	99
Possibility to print \pstart number at the sides of the text.	20
v0.17.0.	
\ifinserthangingsymbol: New new management of hangingsymbol insertion, preventing undesirable insertions.	329
v1.0.0.	
\morenoexpands: Change to be compatible with new features	136
General: \lemma can contain commands.	31
Debug in lineation command	22
New generic commands to customize footnote display.	42, 270
Options nonum and nosep in \Xfootnote.	29
Options of \Xfootnotes.	182
Possibility to have commands in sidenotes.	66
Some compatibility break with elemac. Change of name: elemac.	1
v1.0.1.	
General: Correction on \Xnumberonlyfirstinline with lineation by pstart or by page.	43
v1.1.0.	
\Xprenotes: New skip \Xprenotes@	242
\settoggle@series: \settoggle@series switch the global value of the toggle, not only the local value.	271
General: Add \labelpstarttrue.	20
Add \Xnumberonlyfirsttwolines	43
Add \Xpstart and \Xonlpstart	45
New hook to add arbitrary code at the beginning of the notes	50
New options for block of notes.	53
New package option: parapparatus.	1
New tools to change order of series	269
Sectioning commands.	73
v1.2.0.	
\Xprenotes: Debug in familiar footnotes (bug introduced by v1.1).	242
\endquote: Compatibility of \ledchapter with the <i>memoir</i> class.	368

v1.3.0.	
\endquote: <i>Quotation</i> and quote environment inside numbered sections.	368
v1.4.0.	
\edtext: Compatibility of \edtext with the right-to-left direction (with Polyglossia).	137
\ledsetnormalparstuffX: Direction of footnotes with polyglossia.	239
\newseries@: Remembers the language of the lemma, in order to create a correct direction for the footnote separator.	259
\rbracket: Switch the right bracket to a left bracket when the lemma is RTL (needs polyglossia or LuaTeX).	205
General: Compatibility with LaTeX of RTL notes.	1
v1.4.1.	
\affixside@note: Remove spurious spaces.	311
\endquote: New option <i>noquotation</i>	368
\get@thisfootnote: Compatibility of standard footnotes with <i>eledmac</i> when these footnotes contain any commands.	221
\labelrefsparsesubline: Fix a bug with \edlabel.	290
v1.4.2.	
General: Debug with some special classes.	1
v1.4.3.	
General: Add \Xnonbreakableafternumber.	46
Spurious space after familiar footnotes.	1
v1.4.4.	
General: Label inside familiar footnotes.	1
v1.4.5.	
General: Bug with komascript + elepar + chapter.	1
v1.4.6.	
General: Bug with memoir class introduced by 1.4.5.	1
v1.4.7.	
\endquote: Compatibility of sectioning commands with \autopar.	368
v1.4.8.	
General: Corrects a bug with parallel texts introduced by 1.1.	1
v1.4.9.	
\normalbfnoteX: Allow to redefine \thefootnoteX with alph when some packages are loaded.	226
v1.5.0.	
\do@insidelinehook: Added \do@insidelinehook for use in \do@line	162
\edindex: Compatibility with imakeidx package, and possibility to use multiple index with \edindex.	321
General: Correct indexing when the call is made in critical notes.	317
v1.5.1.	
\managestanza@modulo: Correct stanzaidentsrepetition counter	331
\normalvfootnoteX: Fix a bug with normal familiar footnotes when mixing RTL and LTR text.	224
v1.6.0.	
\newverse: Add \falseverse macro.	334
v1.6.1.	
\AtStartEveryPstart: Spurious space in \pstart.	152
\ifinserthangingsymbol: Hang verse is now not automatically flush right.	329
\l@ dunhbox@line: Move the call to \inserthangingsymbol to allow use \hfill inside.	158

\pend: Spurious space in \pend.	154
General: Corrects a false hanging verse when a verse is exactly the length of a line.	1
v1.7.0.	
General: New features for managing page breaks.	74
v1.8.0.	
\endquote: Correction of sectioning commands in parallel texts.	368
\get@index@command: Debug \get@index@command and compatibility with	
hyperref package.	320
\newhookcommand@series@reload: Debug \beforenotesX and \maxhnotesX which	
did not work.	273
\prevpage@num: Correct \parafootsep when using with ledgroup.	197
General: Compatibility with parledgroup option of elepar package.	1
If imakeidx and hyperref are loaded, adds hyperref in the index.	317
v1.8.1.	
General: Debug endnotes when more than one series is used (change the position where	
tools for endnotes are defined).	244
v1.8.2.	
General: Debug compatibility problem with hebrew option of babel package.	1
v1.8.3.	
General: Fixes spurious spaces added by v1.7.0.	1
v1.8.5.	
General: Debug indexing in right column, with elepar.	317
v1.9.0.	
\l@ddoxtrafeet: Add \fnpos to choice the order of footnotes.	280
\l@dfteetendmini: Add \mpfnpos to choice the order of footnotes in minipage /	
ledgroup.	313
v1.10.0.	
\endquote: Correction of sectioning commands in parallel texts.	368
General: Add \pstartref and \xpstartref to refer to a pstart number (extension of	
\edlabel).	1
v1.10.1.	
General: Compatibility with cleveref.	1
v1.10.2.	
General: Compatibility of stanza with v1.8a of babel-greek.	1
v1.10.3.	
General: Debug of cross-referencing.	1
v1.10.4.	
General: Debug of critical notes in edtabular environment.	1
v1.10.5.	
General: Debug of \pausenumbering.	1
Debug of \xxref.	1
v1.10.6.	
General: Debug of interaction between \autopar and \pausenumbering.	1
v1.11.0.	
General: Add hooks to disable the font selection for lemma in footnote.	49
v1.11.1.	
General: Correct a bug when a critical note starts with plus or minus.	1
v1.12.0.	
\@nl@reg: To ensure compatibility with \musixtex, \@l becomes \@l. Consequently,	
\@l@reg becomes \@nl@reg.	113

\AtStartEveryPstart: New optional argument for \pstart, to execute code before it.	152
\edindex: Use correctly default index when imakeidx is loaded.	321
\endquote: \ledxxx sectioning commands are deprecated and replaced by \eledxxx commands.	368
\initnumbering@reg: \beginnumbering is defined only on eleedmac, not on eleedpar.	93
\l@getside@margin: \sidenotemargin is now directly defined in eleedmac to be able to manage eleedpar.	305
\l@disnote: \l@dlsnote, \l@drsnote and \l@dcsnote defined only one time, in eleedmac, including needs for eleedpar case.	307
\l@dnumpstartsL: Add \ifledRcol@ for eleedpar	91
\l@dunhbox@line: \do@line is split in more little commands.	159
\newhookcommand@series@reload: Debug \beforenotesX and \maxnotesX which did not work when called after \footparagraphX.	273
Debug \Xbeforenotes and \Xmaxnotes which did not work when called after \footparagraph.	273
\pend: New optional argument for \pend, to execute code after it.	154
\stanza: &can have an optional argument: content to be printed after.	334
\Stanza can have an optional argument: content to be printed before.	334
Add \newverse macro, \falseverse deprecated.	334
General: Add \ledinnernote and \ledouternote commands.	66
Add \Xendparagraph and related settings.	55
Add hyperlink to crossref (needs hyperref package).	60
Compatibility with musixtex.	1
Debug eleedmac sectioning command after using \resumenumbers.	1
Ensure that imakeidx is loaded <i>before</i> eleedmac	318
New hooks: \Xafterrule and \afterruleX	53
New options for ragged-paragraph notes	52
New sectioning commands.	73
Optional arguments for \pstart and \pend.	19
v1.12.1.	
\wrap@edcrossref: Fix spurious spaces.	294
v1.12.2.	
\l@dunhbox@line: Fix a bug with critical notes at the tops of pages (added by v12.0.0)	158
v1.12.3.	
\flag@end: \flag@start and \flag@end are now defined only one time for eleedmac and eleedpar	129
\flag@start send a error message when a \edtext is done without insert (note)	129
\reledmac@error: Replaced error messages	84
General: Add macros for new messages since v0.7	84
Correct bug with side and familiar notes in tabular environments.	1
Debug \eledxxx with some paper size	1
Debug \ledinnernote and \ledouternote commands in the top of pages.	66
Debug left and right notes (bugs added by 1.12.0)	1
Underline lemma in \eledxxx when using draft mode.	1
v1.12.4.	
General: Debug spurious page breaks before \chapter (bug added in 1.12.0)	1
v1.12.5.	
\@edindex@hyperref: Debug \edindex when hyperref is not loaded	324
\@ssect: Debug \eledchapter in parallel with memoir	372
\doinsidelinehook: Added \dolinehook and \doinsidelinehook	162

\endnumbering: Allow to mix parallel columns and normal text when using \pausenumbering	95
\l@dgobbleoptarg: \l@dgobblearg becomes \l@dgobbleloptarg	352
\l@drestoreforedtext: Debug optional arguments of \Xfootnote in tabular context	352
\pausenumbering@page@num: Debug \resumenumbering	96
v1.12.7.	
\wrap@edcrossref: \wrap@edcrossref is now robust	294
v1.12.8.	
\f@l@end: \f@l@start do not send a error message when a \edtext is done without insert (note) but have a endnote	129
v1.13.0.	
\newhooktoggle@series@reload: Add \newhookcommand@toggle@reload	273
\para@footsetupX: In \para@footsetupX, use \columnwidth instead of \hsize	234
\settoggle@series: \settoggle@series can take an optional arguments to reload series setup	271
General: Add \Xnoteswidthliketwocolumns and \noteswidthliketwocolumnsX	54
Added widthliketwocolumns option	80
v1.13.1.	
\f@fat@every@pstart@star@: Add \l@dzopenalties in \pstart	152
General: Coming back of page and line breaking penalties's management, deleted by error in v0.17	1
Debug quotation environment inside of a \pstart preceded by a sectioning command.	1
v1.13.2.	
\l@dnumpstartsL: Add \ifl@dpaging for eleddpar	91
General: Fix a bug with normal footnotes, added by v1.13.0.	1
v1.13.3.	
General: Fix extra spaces with paragraphed footnotes, added by v1.13.0.	1
v1.13.4.	
General: Fix a bug with index when memoir class is used without hyperref	1
v1.14.0.	
\edindex: Let eleddmac take advantage of imakeidx even when memoir class is used	321
General: Debug spurious characters before endnotes.	244
Delete previous override of \l@d@wrindexhyp at the beginning of a document when hyperref is not loaded.	325
Move gobbling command	90
Provide \gobblefour	90
v1.14.1.	
\@ssect: Debug sectioning commands when using both handout and hyperref package.	374
v1.14.2.	
\@ssect: Debug \edtext after starred sectioning commands when using memoir class.	372
v1.15.0.	
\@edtext@level: New boolean \if@edtext@.	137
\arrangementX@paragraph: Correct bug with paragraphed familiar footnotes setting.	234
\endsub: Restore subline feature (disabled by mistake in v1.8.0).	131
\if@lemmacommand@: New boolean \iflemmacommand@.	143
General: Fix a bug with footnotes layout when using some options of the geometry package (bug add by v1.13.0).	1
New commands \AtEveryPstart and \AtEveryPend.	19
New tools to prevent ambiguous references in lemma	33

v1.15.1.		
\next@line@list@stuff:	Revert modification of 1.5.2 which makes bug with numbering. Leave vertical mode to solve spurious space before minipage.	127
v1.16.0.		
General:	\edtext is now defined only in <code>eledmac</code> , not in <code>eledpar</code> . Debug wrong numbering when using <code>\samedword + \eledpar + \tag</code> command.	137
	Compatibility of standard footnotes with some biblatex styles.	1
	New <code>\stanzaindent</code> command.	1
v1.16.1.		
\xlineref:	\lineref is not defined if defined by some other package, like <code>lineno</code> . Eledmac provides <code>\edlineref</code> instead.	294
v1.17.0.		
\edtext:	Error message when calling <code>\edtext</code> outside of a numbered paragraph.	137
v1.18.0.		
@\edindex@hyperref:	Fix spurious space with <code>\edindex</code> when using <code>\imakeidx/indextools + hyperref</code>	324
\edlabel:	<code>\edlabel</code> is now defined only one time for both <code>eledmac</code> and <code>eledpar</code>	288
\l@d@section:	Option <code>parapparatus</code> works for endnotes.	245
\l@dnumpstartsL:	Add <code>\ifl@dprintingpages</code> and <code>\@dprintingcolumns</code> for <code>\eledpar</code>	91
\print@line:	Compatibility with Lua ^{LT} E _X RTL languages.	159
\printlinefootnote:	Code refactoring in <code>\printlinefootnote</code> : the printing of the numbers are factorized in <code>\printlinefootnotearea</code>	207
\printpstart:	Debug <code>\Xpstart</code> with parallel pages and columns (<code>eledpar</code>)	206
General:	Add <code>\Xpstarteverytime</code>	45
	Compatibility with Lua ^{LT} E _X RTL languages.	1
	Debug <code>\Xonlypstart</code> when using <code>\Xnumberonlyfirstinline</code> and the current line number differs from the previous.	45
v1.19.0.		
\footsplitskips:	<code>\footsplitskips</code> doesn't set <code>\floatingpenalty</code> to <code>\@MM</code> when processing parallel pages.	184
\xxref:	<code>\xxref</code> works also with right side numbers, when <code>\@Rlineflag</code> is not empty.	297
General:	<code>\Xmaxhnotes</code> and <code>\maxhnotesX</code> work now for both two-columns and three-columns setting.	1
	Compatibility with <code>eledpar</code> v.1.13.0.	1
v1.19.1.		
General:	Call <code>\correct@footinsX@box</code> and <code>\correct@Xfootins@box</code> directly in <code>\print@notesX@forpages</code> and <code>\print@Xnotes@forpages</code> , that is in <code>eledpar</code>	1
v1.20.0.		
\printlines:	Added <code>\ifl@d@Xmorethantwolines</code> and <code>\ifl@d@Xmorethantwolines</code> to <code>\printlines</code>	216
\stanza:	& and \& can be preceded by spaces.	334
\xxref:	Debug <code>\xxref</code> when not loading <code>eledpar</code> (Fix a bug added in 1.19.0).	297
General:	Add <code>\Xendboxlinenum</code>	48
	Add <code>\Xtwolines</code> and <code>\Xmorethantwolines</code> hooks	44
	Add series option.	1
	Correct <code>\Xinplaceofnumber</code> hook.	1
	Explicit error message when calling <code>\Xfootnote</code> outside of <code>\edtext</code>	1
	Fix a bug with line number typesetting direction when using <code>\eledsection</code> and similar commands for RTL texts with Lua ^{LT} E _X	1

Fix issues with RTL text in notes when using Lua ^{LT} _E X	1
Options fulllines in \Xfootnote	29
The \newifs are not followed by boolean values set to false, because it is the _T _E X default setting	1
v1.21.0.	
\@edindex@hyperref: Look at the hyperindex option of hyperref before inserting hyperref	324
\l@d@section: \endnotes take five arguments	245
\ledinnotemark: Add \ledinnotemark	321
\ledsetnormalparstuffX: \ledsetnormalparstuff is deprecated and becomes \ledsetnormalparstuffX and \Xledsetnormalparstuff	239
\n@num: \n@num@ref deleted	121
\n@num defined only one time for both Eledmac and Eledpar	121
\newhookcommand@series: \newhookcommand@series can take an optional argument	272
\newhooktoggle@series: \newhooktoggle@series can take an optional argument	273
\print@footnoteXrule: Code refactoring: the spaces after the footnote rules are directly managed in \print@Xfootnoterule and \print@footnoteXrule	241
\seriesatend: Fix spurious space in \seriesatend	269
\skipnumbering: \skipnumbering defined only one time for both Eledmac and Eledpar	133
Correct \skipnumbering for stanza	133
Delete \skipnumbering@reg	133
General: \AtEveryPstart and \AtEveryPend are now compatible with \autopar	1
\Xafterrule and \afterruleX features no longer create problems of overflowing at the bottom of the page	1
\chapter inside optional argument of \pstart works when typesetting parallel pages	1
\preXnotes and \prenotesX features no longer create problems of overflowing at the bottom of the page	1
\seriesatbegin and \seriesatbegin more efficient	269
Add \applabel and related	63
Add \beforenotesX and \Xbeforenotes features for notes set in two and three column	1
Add \hidenumbering	24
Add \Xcolalign and \colalignX hooks	51
Add \Xendtwolines, \Xendmorethanwolines, \Xendtwolinesbutnotmore and \Xendtwolinesonlyinsamepage	45
Add \Xparindent and \hangindentX	50
Add \Xtwolinesbutnotmore and \Xtwolinesonlyinsamepage	1
Add nocritical, noend,nofamiliar and noledgroup options	1
Add noeledsec package option	1
Debug \beforenotesX \maxhnotesX \noteswidthliketwocolumnsX and \afterruleX with footnotes set in two and three columns	1
Fix a bug when a \Xfootnote follows a \Xendnote in the second argument of \edtext (bug added in elemdac 1.0.0)	1
Fix a bug with \maxhnotesX when using \foottwocolX or \footthreecolX	1
Fix a bug with space between columns with notes in two columns (bug added in v1.13.0)	1

Fix spurious space after first page number in \doendnotes. oldprintnpnumspace option allows to come back to previous setting	1
parapparatus option works now with familiar footnotes.	1
Provide \@gobblefive	90
v1.22.0.	
\ledinnote: \ledinnote takes a first optional argument, which is the label for hyperlinks.	321
General: Add \doendnotesbysection command.	30
Add option for lemma separator inside endnotes	48
Adds hyperlink for references to notes in indices.	1
Fix conflict between noend package option and edtabularx environments	1
Provides support for xindy.	1
Standardize endnotes handbook.	30
When using hyperref package, internal links in index or with \edlineref are now targeted to the top and not longer to the bottom of the lines they refer to.	1
v1.22.1.	
\prevpage@num: Correct double symbol when using both \parafootsep and \Xsymlinenum.	197
General: Fix a bug (added on v1.22.0) with \Xinplaceofnumber hook.	1
v1.23.0.	
@\edtext@level: The boolean \if@edtext@ becomes the counter \edtext@level.	137
\SErefwithpage: Debug \Xendtwolines, \Xendmorethan twolines, \Xendtwolinesbutnotmore and \Xendtwolinesonlyinsamepage when using \apprefwithpage.	301
\lemma: Fix spurious space after \lemma command	142
\newseries@: Prevent spurious spaces when \Afootnote and similar commands are followed by spaces (bug added on 1.0.0).	259
\sameword: In order to allow use of \sameword with inputenc, we detokenize its mandatory argument before using it in control sequence names.	148
General: Add \Xboxlinenumalign and \Xendboxlinenumalign.	47
Add \Xboxstartlinenum, \Xendboxstartlinenum, \Xboxendlinenum, \Xendboxendlinenum.	47
Allow use of \sameword with inputenc managing of UTF-8.	1
Compatibility between nofamiliar/nocriticals option and minipage/ledgroup.	1
Error message when using \beginnumbering ... \endnumbering without \pstart.	1
Fix a bug with \sameword when the lemma overlaps multiple line.	33
Fix a bug with \sameword when the same lemma is used for multiple notes or for nested \edtexts.	33
Fix a bug with \skipnumbering called immediately after a \pstart.	1
Fix error of \iftrue not closed.	1
Fix spurious space with \skipnumbering (bug added on v1.21.0).	1
New tools to ensure the line-list file uses the right version of commands when upgrading the elemac version.	1
Optional argument of \sameword can be a comma-separated list of \edtext depth.	33
v1.23.1.	
General: Fix a bug with \lemma command in the right side.	1
v1.23.2.	
General: Compatibility with L ^A T _E X's release 2015.	1

v1.24.0.	
General: We can reinitialize \AtEveryPstart and \AtEveryPend providing to it an empty argument.	1
v1.24.1.	
General: \lemma is disabled when using ‘nocritical’ option.	1
v1.24.2.	
General: Fix incompatibility between ‘nofamiliar’ option and ‘memoir’ package.	1
v1.24.3.	
General: Restore marginal numbers and notes with sectioning command (bug introduced in v1.21.0)	1
v1.24.4.	
General: Fix spurious space with \edindex when using xindy+hyperref option.	1
v1.24.5.	
General: Fix a bug of indent, when a added in 1.1.0, when a \beginnumbering immediately follow a sectioning command.	1
v2.0.0.	
\@iiminipage: Patch \@iiminipage instead of redefining it.	315
\@xympar: Patching \@xympar instead of redefining it	305
\endminipage: Patch \endminipage instead of redefining it.	315
\initnumbering@quote: \initnumbering@sectcmd becomes \initnumbering@quote	368
\l@advance@parledgroup@beforenormalnotes: Some conde of \l@dumboxmpfoot moved to \l@advance@parledegrou@beforenormalnotes	315
\newseries@: One endnotes file by series.	265
General: \@makecol, \@reinserts and \@doclearpage are patched instead of begin redefined	283
\doxtrafeeti becomes \Xdo@feet; \doxtrafeetii becomes \do@Xfeet; \opxtrafeeti becomes \opfeetX; \doreinxtrafeetii becomes \X@doreinfeet; \doreinxtrafeeti becomes \doreinfeetX.	283
Add \Xendinplaceofnumber hook.	1
Add \Xendnonumber hook.	1
Add nonum option for endnotes.	1
Fix a bug when printing only one series of endnotes, but wanted to keep endnotes for other series.	1
In order to have a more consistent name’s convention, many names has been changed.	1
Many L ^A T _E X’s output macros are now patched and not override.	1
Package’s name becomes reledmac	1
Patch \@footnotemark instead of redefine it	220
Suppress indexing command specific to memoir	321
v2.0.1.	
General: Fix a bug in elemac-compat option	1
Fix incompatibility between optional argument of \pstart and \numberpstarttrue	1
v2.1.0.	
General: Fix a bug with \advanceline at the beginning of a \pstart.	1
Fix a bug with \chapter in optional argument of \pstart in parallel typesetting with scrbook	1
Fix a bug with \eledchapter in parallel typesetting with scrbook	1
Fix a bug with \setline at the beginning of a \pstart.	1
Fix spacing bug with \Xbhooknote and \bhooknoteX when using them to insert text and not to execute code.	1

New tools to number stanzas	1
v2.1.1.	
General: Fix a bug with \ledpbsetting{before}.	1
v2.1.2.	
General: Fix a bug with lineation by pstart and tabular environments (added in 2.1.0).	1
v2.1.3.	
\ledsetnormalparstuffX: Replaced \noindent with \parindent set to 0pt.	239
General: \Xhangindent and \hangindentX work now with all the paragraphs in the note.	1
\Xnoindent and \noindentX work now again (broken in 2.0.0).	1
Change some internal code in order to provide compatibility with L ^A T _E X release of october 2015	1
Fix a bug which inserted double space before paragraphed familiar notes.	1
Fix a bug with \ledindex when using not-Latin characters without UTF-8 engines	1
v2.2.0.	
General: Fix a bug with combination of \onehalfspacing and two columns and three columns notes typeset.	1
Fix a bug with some setting command and optimization option.	1
Fix spurious space with paragraphed critical notes when using LuaL ^A T _E X.	1
Increase line list version number to ensure compatibility with new options of <code>reledpar</code> package.	1
New setting tools for endnotes: \Xendnumberonlyfirstinline, \Xendnumberonlyfirstintwolines, \Xendsymlinenum, \Xendbeforenumber, \Xendafternumber, \Xendbeforesymlinenum, \Xendaftersymlinenum, \Xendboxsymlinenum, \Xendhangindent, \Xendbhooklinenum, \Xendahooklinenum, \Xendbhookinplaceofnumber, \Xendahookinplaceofnumber.	1
v2.2.1.	
General: Compatibility with L ^A T _E Xformat 2015/10/01.	1
v2.2.2.	
General: Fix a bug in \sethangingsymbol.	1
Fix a bug with old version of etex.	1
v2.3.0.	
General: Disable empty lines as paragraph in stanza.	1
Fix incompatibility of paragraphed footnotes with <code>bidi</code> v17.9 and following.	1
Warning message when using some setting commands inside rightside environment (deprecated behavior)	1
v2.3.1.	
General: Fix spurious space when using optional argument of \stanza (introduced in v2.3.0).	1
v2.4.0.	
\footnoteoptions@: First argument of \footnoteoption@ is now mandatory, not optional.	182
General: \Xbhooknote and \bhooknoteX work with notes in columns.	1
Fix a bug of \parindentX and \Xparindent with two columns and three columns notes.	1
Fix a bug with \sameword in right side.	1
Fix spurious space in two columns and three columns notes.	1
Fix spurious space when using optional argument of stanza (introduced in v2.3.0).	1
New hooks: \Xlinerangeseparator and \Xendlinerangeseparator.	44

Option linerangesep for critical footnotes and endnotes.	44
v2.4.1.	
General: Fix a bug with \appref and \apprefwithpage (introduced in v2.4.0).	1
Fix a bug with tabular environments when using babel or polyglossia languages that override L ^A T _E X \roman command, like Greek language.	1
Fix a bug with tabular environments when using babel or polyglossia languages that override L ^A T _E X \roman command, like Greek.	1
v2.5.0.	
\SErefwithpage: Debug \setapprefprefixsingle	300
\edlabel: Fix a bug when calling \edlabel in a footnotes of the right side	288
\l@d@section: \endnotes take six arguments.	245
\printlines: \printlines takes an eighth argument: the line flag	215
\xlineref: \xlineref does not include anymore the side flag. Use \xflagref to get it. Not that \edlineref still contains the flag.	294
General: \apprefwithpage and \appref print double quotation mark when the label was not defined.	1
\apprefwithpage and \appref work with right side crossref.	1
\apprefwithpage works also when noend option is enabled.	1
\appref and \apprefwithpage can take linerangesep optional argument.	1
\edlabel works now in \Xfootnote.	1
\lemma can be used even when the nocritical is enabled.	1
Compatibility with new hook and tools of reledpar 2.6.0.	1
Fix spurious vertical space in astanza environment (reledpar)	1
Log now states ‘There were undefined references’ when using wrong references in \edlineref or edpageref.	1
New hooks to customize page and line number appearance in endnotes.	1
New hooks: \Xbhookgroup and \bhookgroupX.	1
New tools to easily make cross-reference to a passage defined by a start and an end line	62
v2.6.0.	
General: Adds compatibility with innnote and notenumber options of indextools package.	1
Fix a bug with footnote counter in ledgroup (added in v2.5.0).	1
Fix bug, introduced in v2.5.0, with footnote numbering in parallel typesetting when using perpage package.	1
v2.7.0.	
\@k: \rigidbalance is split in \Xrigidbalance and \rigidbalanceX.	198
\l@d@section: \endnotes take seven arguments.	245
General: Add dash as default page range separator for \SEonlypage	1
Debug \SErefonlypage when referring to only one page.	1
Delete parenthesis after \SErefonlypage.	1
Fix (again) bugs with footnote numbering in parallel typesetting while using ledgroup environments (bug added in v2.5.0).	1
Fix a bug with \SErefwithpage.	1
Fix bugs in compatibility with innote and notenumber options of indextools package, when indexing outside of a ledgroup.	1
New commands to make glossaries connected to page and linenumbers with the glossaries package	1
New hooks: \Xhsizen and \hsizenX	54
New hooks: \Xlemmamfont and \Xendlemmamfont	49

New setting commands: <code>\setSErefonlypageprefixsingle</code> and <code>\setSErefonlypageprefixmore</code>	1
Warning for duplicate and undefined labels are parsable by latexmk	1
Warning for duplicate labels does not send any more a false line and page number	1
When using <code>hyperref</code> package, add link in familiar footnotes between the footnote marks in the text and the footnote marks in the footnote	1
When using <code>hyperref</code> package, add links for <code>\SEref</code> and related, <code>\appref</code> and related	1
When using <code>hyperref</code> package, add links from critical footnotes and critical endnotes to the line of text they refers	1
v2.7.1.	
General: Debug <code>\Xbhookgroup</code> hooks executed on columnar footnotes (moved to a larger group, to take effect)	1
v2.7.2.	
General: <code>\Xhsizex</code> and <code>\hsizex</code> become <code>\Xwidthx</code> and <code>\widthx</code>	54
Fix problem of hyphenation when using <code>hyperref</code> package (added in v2.7.0)	1
v2.8.0.	
<code>\l@od@section</code> : <code>\Xendhangindent</code> and <code>\Xendafternote</code> can take values which are relative to the font size of the endnote	245
General: <code>reledmac</code> cross-referencing can take advantage of <code>xr</code> package	1
More <code>\edgls...</code> commands	1
No indentation for paragraphed notes in ledgroup. Can be changed with <code>\Xparindent</code> and <code>\parindentx</code>	1
v2.8.1.	
General: Warnings for undefined labels are really parsable by latexmk	1
v2.8.2.	
General: Fix a bug concerning indent in a paragraph immediately following a sectioning command (bug NOT fixed on <code>reledpar</code>)	1
Fix a bug with <code>\AtEveryPstart</code> added in version 2.0.0	1
Fix a bug with vertical space after the between-sectioning command as optional argument of a <code>\pstart</code> and <code>\pstart</code> content	1
v2.9.0.	
General: Allow continuing line numbering between normal text and parallel text, using <code>\pausenumbering</code> and <code>\resumenumbers</code> and the <code>continuousnumberingwithcolumns</code> option	1
Fix a bug when using <code>\lineneation[page]</code> and <code>\pausenumbering...\resumenumbers</code>	1
Fix a bug with three- and two-column footnote setting (added in v.2.4.0)	1
Fix spurious space inside three-column familiar footnote	1
Write correct metadata in numbered files when using <code>\pausenumbering...\resumenumbers</code>	1
v2.9.1.	
General: Fix a bug when notes start with “plus” or “minus”	1
v2.9.2.	
General: Fix a bug with <code>hyperref</code> package when a lemma starts with “plus” or “minus” (bug introduced in v. 2.7.0)	1
v2.9.3.	
General: Fix a bug with line number position and reset added by v. 2.9.0	1

v2.10.0.	
\print@lemma: Code refactoring between \parafootfmt, \twocolfootfmt, \threecolfootfmt and \normalfootfmt.	206
General: Add \AtEveryStanza and \AtEveryStopStanza.	1
Fix a bug in \ledlsnotefontsetup and \ledrsnotefontsetup which could not handle \color command properly.	1
More specific error messages.	1
New hooks: \Xwrapcontent, \Xendwrapcontent and \wrapcontentX.	50
New hooks: \Xwraplemma and \Xendwraplemma	50
v2.10.1.	
General: Add ‘nopenalties’ option.	1
Fix a bug introduced in v. 1.4: not paragraphed critical footnotes could prevent marginal line number from being displayed	1
v2.11.0.	
\do@actions@fixedcode: Add action 1010	166
General: Add new tools to produce an apparatus of manuscripts	1
Fix a bug in \Xparafootsep in parallel typesetting	1
Make \parafootsepX work	1
Prevent \Xtxtbeforenotes hook from causing notes to go beyond the bottom margin	1
v2.12.0.	
General: \preXnotes becomes \Xprenotes (naming convention)	1
Add \hidenumberingonleftpage and \hidenumberingonrightpage	1
Add \toendnotes and related.	1
Add auxdir option.	1
Fix a bug in critical and familiar footnotes when using uppercase letters with accent mark	1
Fix a bug when using \chapter in optional argument of \pstart in parallel typesetting in combination with the noeledsec option.	1
Fix a bug with \ledinnernote and \ledouternote in parallel typesetting	1
Fix a bug with familiar footnote number in optional argument of \pstart or \pend in parallel typesetting	1
Fix spurious vertical space in \chapter when used as optional argument of \pstart in parallel typesetting.	1
Make endnote compatible with \samedword mechanism	1
More accurate message to control the position of \Xfootnote and \applabel in the \TeX code	1
v2.13.0.	
General: Version 2.13.0 never existed.	1
v2.13.1.	
General: In critical footnotes, the right side flag is printed only if requested explicitly with \Xlineflag (bug added in v. 2.5.0).	1
v2.13.2.	
General: Fix a bug added in v. 11.2 which could make parallel typesetting not work.	1
v2.13.3.	
General: Makes \Xendafterpagenumbe affecting \SErefwithpage	1
v2.14.0.	
General: Hyperref with the line number inside critical footnotes is correct when using \xxref	1
Some internal changes for new features of reledpar.	1

v2.14.1.	
General: Fix a bug when using \footnoteX in the first argument of \edtext.	1
v2.14.1a.	
General: Fix problematic typos in the handbook.	1
v2.15.0.	
General: Add ‘byline’ arrangement.	1
Fix \Xtxtbeforenotes in ledgroup.	1
v2.15.1.	
General: Fix \edindex in tabular environments.	1
v2.15.2.	
General: Fix a bug with fancyhdr package 3.8 and later.	1
v2.15.3.	
General: Fix a bug with \section in optional argument of \pstart and empty line before \pend (bug added in v2.8.2).	1
Simplification of the sectioning command code.	1
v2.16.0.	
General: \Xdo@feet becomes \do@Xfeet	283
Add \Xendpagenumberonlyfirst, \Xendpagenumberonlyfirstifsingle, \Xendpagenumberonlyfirstintwo, \Xendinplaceofpagenumber and \Xendsympagenum hooks.	1
Add \Xpagelinesep hook.	46
Compatibility with new features of reledpar	1
Deleted dead code.	1
Display a warning message if using a version of L ^A T _E X that is too old.	1
Fix a bug with \Xgroupbylines for notes in two columns	1
Fix a bug with \Xtxtbeforenotes for notes in three or two columns	1
Fix a bug with ‘notenumber’ option of indextools package when indexing texts in familiar footnotes.	1
Fix potential bug when using \edindex in critical footnotes.	1
More explicit error message in case the stanza indentation is not defined.	283
New options for \fnpos and \mpfnpos to set a customized order for familiar and critical footnotes.	1
When \edindex is called outside of a \beginnumbering... \endnumbering structure, it is automatically switched to \index, with a warning message.	1
When indexing texts in familiar footnotes with \edtext, refer to the line number where the footnote is called.	1
When indexing texts in sidenotes with \edtext, refer to the line number where the sidenote is called.	1
v2.16.1.	
General: Fix a bug with redefinition of the style of the footnote number (bug added in v2.12.0)	1
v2.16.2.	
General: Error message if footmisc is loaded after reledmac.	1
Fix a bug introduced by v2.16.1 when using non-expandable control sequence, like \normalfont, in the footnote number style.	1
v2.16.3.	
General: Fix a bug with \SEref (bug added in v2.7.0).	1
v2.16.4.	
General: Fix a bug with vertical space before sectioning command in optional argument of \pstart (bug added in v2.15.3).	1

v2.16.5.		
General: Fix potential spurious spaces in endnotes.	1	
v2.16.6.		
General: Fix a bug with the line number style in \doenotes when referring to right side line in parallel typesetting.	1	
Take into account \linenumberstyle when using \edlineref.	1	
v2.16.7.		
General: Fix a bug with \msdata when using multiple \beginnumbering ... \endnumbering.	1	
Fix a bug with \numberpstarttrue when using multiple \beginnumbering ... \endnumbering.	1	
v2.16.8.		
General: Fix a bug with \edindex in footnotes in parallel typesetting.	1	
v2.17.0.		
General: Add \edglsadd command.	1	
Add \setmsdataposition setting.	1	
v2.17.1.		
General: Fix spurious space in paragraphed footnotes when using Lua ^E T _E X without using Right-To-Left text.	1	
v2.17.2.		
General: Change log message when numbered files still don't exist, in order to improve compatibility with <i>latexmk</i>	1	
v2.17.3.		
General: Fix a bug with \doendnotesbysection and \doendnotes.	1	
v2.17.4.		
General: Fix a bug with \setSerefonlypageprefixsingle and \setSerefonlypageprefixmore.	1	
v2.17.5.		
General: Fix a bug with \pstartref when referring to the left side in parallel typesetting.	1	
v2.18.0.		
General: Fix a bug when using a \edtext in two lines or more in right-to-left typesetting with X _U ^E T _E X.	1	
Fix a bug when using both \Xnumberonlyfirstintwolines or \Xnumberonlyfirstinline and \Xparafootsep and \Xsymlinenum.	1	
v2.18.1.		
General: Fix a bug when using \msdata with Lua ^E T _E X or with the hyperref package.	1	
v2.19.0.		
General: Add \footnoteXmark and \footnoteXtext commands.	1	
Add better compatibility with the csquotes package when using familiar footnotes.	1	
Fix a bug with paragraph indent after sectioning command.	1	
v2.20.0.		
General: Add \AtStartEveryStanza, \BeforeEveryStopStanza, \AtEndEveryPend, \AtStartEveryPstart.	1	
Add second optional argument to \pstart, \pend and \stanza.	1	
Add starred version of \AtEveryPstart, \AtEveryPend, \AtEveryStanza and \AtEveryStopStanza.	1	
Add third and fourth optional argument to \newverse.	1	
Fix a bug when using familiar footnotes in \eledsection and related.	1	
Reset font specification at the beginning of familiar footnotes.	1	

v2.21.0.	
General: Add the possibility of nested \sameword commands.	1
Fix a bug when using formatting command in the argument of \edindex inside \edtext.	1
Now, as explained in the handbook, a \edindex inside \edtext only creates an index reference to the main text, and not to the critical footnote.	1
v2.22.0.	
General: Add \txtbeforenotesonlyonceX and \Txtbeforenotesonlyonce hooks.	1
Add \txtbeforenotesX hook.	1
Fix a bug added in v2.16.0 when using \Txtbeforenotes with paragraphed or normal footnotes.	1
Fix a bug with three and two columns critical footnotes, broken in v. 2.17.6.	1
v2.22.1.	
General: Compatibility with new version of reledpar.	1
Fix a bug with some commands inside \sameword.	1
v2.22.2.	
General: Do not print footnotes at the first run.	1
v2.23.0.	
General: Add swcaseinsensitive option	1
Optimisation of the code added on v2.22.2 to not print footnotes at the first run.	1
v2.24.0.	
\next@line@list@stuff: Add \next@line@list@stuff internal hook.	127
General: Add \swnoexpands macro to avoid problems with not fully expandable macro inside \sameword.	1
Fix a bug with \edlabel at the beginning of a \pstart.	1
Fix spurious space with \labelpstarttrue	1
When a \setlinenum is used, it is stronger than the \lineation{page} setting.	1
v2.24.1.	
General: Compatibility with reledpar 2.20.2	1
v2.24.2.	
General: Fix bug between tabular environments and endnotes	1
v2.25.0.	
General: Add \Xendtxtbeforenotes hook	1
v2.26.0.	
General: Add a mechanism for annotation of stanza line numbering	1
Fix bug in \xpstartref	1
v2.26.1.	
General: Fix bug with \linenumannotation	1
v2.26.10.	
General: Add error message when insertion a \pstart or \pend inside \edtext arguments	1
Really fix bug with page number in footnote after \mainmatter (bug introduced in v2.26.7)	1
v2.26.11.	
General: Allow to use \edtext inside \sameword	1
v2.26.12.	
General: Precise minimal version of xpparse package required.	1
v2.26.2.	
General: Fix bug with \linenumannotation in parallel typesetting	1
Fix bug with \Xgroupbyline and \Xparafootsep.	1

Fix bug with <code>\Xgroupbyline</code> and optional argument of critical footnotes.	1
Fix bug with <code>\Xgroupbyline</code> for the series after the first one.	1
v2.26.3.	
General: Fix bug added by v2.26.0 with notes in parallel typesetting	1
v2.26.4.	
General: Fix bug when using <code>\numberpstarttrue</code> and alternating between manual <code>\pstart</code> and automatic <code>\pstart</code> produced by <code>\autopar</code>	1
v2.26.5.	
General: Check that users have a enough recent version of <code>xparse</code>	1
Fix bug when using <code>\uledsection</code> with the <code>continuousnumberingwithcolumns</code> of <code>reledpar</code>	1
Fix bug with <code>continuousnumberingwithcolumns</code>	1
Fix bug with using <code>\uledsection</code> and related when alternate normal typesetting and parallel typesetting	1
v2.26.6.	
General: Fix bug with <code>\lineation</code> by page and nexted <code>\edtext</code> between two pages (added in v. 2.24.0)	1
v2.26.7.	
General: Fix page number in footnote and endnotes when using <code>sameparallelpagenumber</code> option of <code>reledpar</code> and typesetting critical text in single mode after critical text in double page mode	1
v2.26.8.	
General: Fix bug in some specific cases, introduced by v.2.27.7	1
v2.26.9.	
General: Fix bug with critical footnotes line number when alternating between <code>\numberlinefalse</code> and <code>\numberlinetrue</code>	1
Fix bug with page number in footnote after <code>\mainmatter</code> (bug introduced in v2.26.7) .	1
Workaround with a bug of L ^A T _E X2018/04/01 patch level 3 to generate the .sty file from a .ins file	1
v2.27.0.	
General: Add <code>\doinsidethislinehook</code>	1
v2.27.1.	
General: Fix spurious space in <code>\hidenumbers</code>	1
v2.28.0.	
General: Familiar footnotes can take an optional argument to manually define the footnote mark.	1
v2.28.1.	
General: Fix bug with the alignment of the columns of two and three columns critical footnotes.	1
v2.29.0.	
General: Add <code>\noresetlinenumannotation</code>	1
Fix bug with <code>\linenumannotation</code> and ‘nofamiliar’ option.	1
Fix little bug with <code>\msdata</code>	1
Really reset line number annotation at each line	1
v2.30.0.	
General: Add <code>\Xnoidenticallinenumannotation</code> and <code>\Xendnoidenticallinenumannotation</code> hooks	1
Add separator between line number annotations in margin. Add <code>\setlinenumannotationsep</code>	1

v2.31.0.

General: Add `noprefix` and `prefixmore` to `\appref` and `\SEref`. 1

v2.31.1.

General: Fix bug in vertical spacing with `\Xgroupbyline`. 1Fix bug with `\Xgroupbyline`, which could produce spurious blank lines. 1Fix bug with `\Xhangindent` and `\hangindentX` for right-to-left texts. 1Fix bug with indentation with `\Xgroupbyline`. 1Fix bug with multiple footnote layer and `\Xgroupbyline`. 1Fix incompatibility between `\Xgroupbyline` and `hyperref` package. 1Fix incompatibility between `\Xgroupbyline` and optional argument of critical
footnotes. 1

v2.31.2.

General: Fix bug with familiar footnote containing not default font (introduced with
v. 2.20.0). 1