

reledmac

Typeset scholarly editions with L^AT_EX*

Maïeul Rouquette[†]

based on the original ledmac by
Peter Wilson
Herries Press

which was based on the original edmac, tabmac and edstanza by
John Lavagnino, Dominik Wujastyk, Herbert Breger and Wayne Sullivan.

Abstract

The **reledmac** provides many tools in order to typeset scholarly editions. It is based on the **eledmac** package, which was based on the **ledmac** package, which was based on the **edmac** TeX package.

It can be used in combination with **reledpar** in order to typeset two texts in parallel, like an original text and its translation in a modern language.

reledmac provides many tools and options. Normally, they are all documented in this file. Also provided is a help folder, “examples”. The folder contains additional examples (although not for every possible case). Examples starting with “1-” are for basic uses, those starting with “2-” are for advanced uses.

To report bugs or request a new feature, please go to ledmac GitHub page and click on “New Issue”: <https://github.com/maieul/ledmac/issues/>. You must create an account on github.com to access my page (maieul/ledmac). GitHub accounts are free for open-source users. You can post messages in English or in French (preferred).

You can subscribe to the **reledmac** mail list at:
<http://geekographie.maieul.net/146>

Contents

1 Introduction	11
1.1 Aim of the package	11
1.2 History	12
1.2.1 edmac	12
1.2.2 ledmac	14
1.2.3 elledmac	14

*This file (**reledmac.dtx**) has version number v2.26.1, last revised 2017/11/26.

[†]maieul at maieul dot net

1.2.4 <code>reledmac</code>	14
1.3 Bibliography	14
2 How the package works – the problem of the number of L^AT_EX runs	15
3 Compatibility warning	15
4 Options	15
4.1 Specific features	15
4.2 Optimizing package performance	16
5 Text lines and paragraphs numbering	17
5.1 Text lines numbering	17
5.2 Paragraphs	17
5.2.1 Basics	17
5.2.2 Automatically producing <code>\pstart ... \pend</code>	18
5.2.3 Content before specific <code>\pstart</code> and after specific <code>\pend</code>	18
5.2.4 Content before every <code>\pstart</code> and after every <code>\pend</code>	19
5.2.5 Numbering paragraphs (<code>\pstart</code>)	19
5.2.6 Languages written in Right to Left	20
5.2.7 Memory limits	20
5.3 Lineation commands	20
5.3.1 Disabling lineation	20
5.3.2 Setting lineation start and step	21
5.3.3 Setting lineation reset	21
5.3.4 Setting line number margin	21
5.3.5 Other settings	22
5.4 Changing the line numbers	22
5.4.1 Sublineation	22
5.4.2 Locking lineation	22
5.4.3 Setting and changing line number	22
5.4.4 Line number style	23
5.4.5 Skipping and hiding number	23
5.5 Executing code at each line	24
6 Apparatus commands	24
6.1 Terminology	24
6.2 Critical notes	24
6.2.1 The lemma	24
6.2.2 Footnotes	25
6.2.3 Endnotes	25
6.2.4 Paragraph in critical apparatus	27
6.2.5 Change lemma and line number	27
6.2.6 Changing the names of commands for critical apparatus	28
6.3 Disambiguation of identical words in the apparatus	28
6.3.1 Basic use	28

6.3.2 Case setting	29
6.3.3 Notes about input encoding with UTF-8 processor	29
6.3.4 Use with \lemma command	30
6.3.5 Sameword for a group of words	31
6.3.6 Customizing	32
6.3.7 Problems with some macros	32
6.3.8 Automatic sameword annotation	33
6.4 Apparatus of manuscripts	33
6.4.1 Marking sections of text	34
6.4.2 Layout of the apparatus of manuscripts	34
6.4.3 Settings	35
6.5 Familiar notes	35
6.5.1 Basic use	35
6.5.2 Customizing mark	35
6.5.3 Separator for multiple footnotes	36
6.6 Printing the footnote mark without printing the footnote text	36
6.7 Changing series	36
6.7.1 Create a new series	36
6.7.2 Delete series	36
6.7.3 Series order	36
6.8 Position of critical and familiar footnotes	37
7 Apparatus customization	38
7.1 Notes arrangement in a series	38
7.2 Control line number printing	39
7.2.1 Print line number only at first time	39
7.2.2 Print page number only at first time	39
7.2.3 Arbitrary text before line number	40
7.2.4 Separator for line range	40
7.2.5 Abbreviate line range	40
7.2.6 Disable line number	41
7.2.7 Printing pstart number	41
7.2.8 Printing stanza number	42
7.2.9 Separator between line and subline numbers	42
7.2.10 Separator between page and line numbers	42
7.2.11 Space around number	42
7.2.12 Space around line symbol	42
7.2.13 Space in place of number	43
7.2.14 Boxing line number and line symbol	43
7.3 Arbitrary code around line number	44
7.4 Separator between the lemma and the note	44
7.4.1 For footnotes	44
7.4.2 For endnotes	44
7.5 Font style	45
7.5.1 For line number	45
7.5.2 For the lemma	45

7.5.3 For all notes	45
7.6 Wrapping notes	46
7.6.1 Wrapping lemmas	46
7.6.2 Wrapping contents	46
7.7 Indent of notes content	46
7.8 Arbitrary code at the beginning of notes	46
7.9 Arbitrary code before inserting note	47
7.10 Options for footnotes in columns	47
7.10.1 Alignment	47
7.10.2 Size of the columns	47
7.11 Options for paragraphed footnotes and notes grouped by line	48
7.11.1 Mark separation of notes	48
7.11.2 Ragged text	48
7.12 Options for block of notes	48
7.12.1 Grouping notes by line	48
7.12.2 Text before notes	49
7.12.3 Code before notes	49
7.12.4 Spacing	49
7.12.5 Rule	49
7.12.6 Maximum height	50
7.12.7 Width	50
7.13 Footnotes and the <code>reledpar</code> columns	50
7.14 Line number annotation	50
7.15 Endnotes in one paragraph	51
8 Fonts	51
9 Verse	51
9.1 Basic	51
9.2 Define stanza indents	52
9.3 Repeating stanza indents	52
9.4 Manual stanza indent	53
9.5 Stanza breaking	53
9.6 Hanging symbol	53
9.7 Long verse and page break	54
9.8 Content before/after verses	54
9.9 Numbering stanza	55
9.10 Adding annotations to line numbers	55
9.10.1 Modifying annotation associated with a specific note	57
9.10.2 Changing the position of the annotation	57
9.10.3 Changing the macro in which annotations are wrapped	57
9.11 Various tools	58
9.12 Notes on empty lines	58
10 Grouping	58

<i>Contents</i>	5
-----------------	---

11 Cross referencing	59
11.1 Basic use	59
11.2 Cross-referencing to a critical note	60
11.3 Cross-referencing which return a number in any case	60
11.3.1 Cross-referencing in order to define line number of a critical note .	60
11.4 Not automatic cross-referencing	61
11.5 Normal L ^A T _E X cross-referencing	61
11.6 References to start and end lines	61
11.6.1 Reference to main text lines	61
11.6.2 References to lines that are commented on in the apparatus	62
11.6.3 Settings	62
11.7 Compatibility with xr package	64
12 Sidenotes	64
12.1 Basics	64
12.2 Setting	64
12.2.1 Width	64
12.2.2 Vertical position	65
12.2.3 Distance to the main text	65
12.2.4 Font	65
12.2.5 Separator between notes	65
13 Indexing	65
13.1 Basics	65
13.2 Referring to critical notes	66
13.3 Separator between page and line numbers	66
13.4 Using xindy	66
13.5 Advanced setting	67
14 Glossary	67
14.1 Preamble setting	67
14.2 Commands	68
15 Tabular material	68
16 Sectioning commands	71
16.1 Sectioning commands without line numbers or critical notes	71
16.2 Sectioning commands with line numbering and critical notes	71
16.3 Optimization	72
17 Quotation environments	72
18 Page breaks	73
18.1 Control page breaking	73
18.2 Prevent page break in a long verses	73

19 Miscellaneous	73
19.1 Known and suspected limitations	74
19.1.1 Non-standard geometry	74
19.1.2 <i>floatrow</i> package compatibility	74
19.1.3 ‘No room for a new’	74
19.1.4 Marginal notes	74
19.1.5 Paragraph shape	75
19.1.6 Paragraphed footnotes	75
19.1.7 Use with other packages	75
19.2 Parallel typesetting	76
I Implementation overview	77
II Preliminaries	77
II.1 Links with original <i>edmac</i>	77
II.2 Package declaration	77
II.3 Package options	78
II.4 Loading packages	80
II.5 Compatibility with <i>LuaTeX</i>	80
II.6 Boolean flags	81
II.7 Messages	82
II.8 Gobbling	88
II.9 Wrapping content	88
II.10 Miscellaneous commands	89
II.11 Prepare <i>reledpar</i>	89
II.12 Booleans provided by other optional packages which are required in any case	90
III Sectioning commands	90
IV List macros	95
V Line counting	97
V.1 Choosing the system of lineation	97
V.2 Line number margin	98
V.3 Line number initialization and increment	99
V.4 Line number locking	100
V.5 Line number style	101
V.6 Line number printing	102
V.7 Line number counters and lists	103
V.8 Line number locking counter	104
V.9 Line number associated to lemma	104
V.10 Reading the line-list file	108
V.11 Commands within the line-list file	110
V.12 Writing to the line-list file	123

VI Marking text for notes	130
VI.1 \edtext itself	131
VI.2 Substitute lemma	138
VI.3 Substitute line numbers	139
VI.4 Lemma disambiguation	140
VII Paragraph decomposition and reassembly	147
VII.1 Boxes, counters, \pstart and \pend	147
VII.2 Processing one line	153
VII.2.1 General process	153
VII.2.2 Process for “normal” line	154
VII.2.3 Process for line containing \eledsection command	156
VII.2.4 Hooks	157
VII.2.5 Sidenotes and marginal line number initialization	157
VIII Line and page number computation	158
IX Line number annotation	162
X Line number printing	164
XI Pstart number printing inside	168
XII Restoring footnotes and penalties	169
XII.1 Add insertions to the vertical list	170
XII.2 Penalties	172
XII.3 Printing leftover notes	172
XII.4 Text before notes	173
XIII Critical footnotes	175
XIII.1 Fonts	175
XIII.2 Individual note options	176
XIII.3 Notes language	176
XIII.4 General survey of the way we manage notes	177
XIII.5 General setup	178
XIII.6 Footnotes arrangement	178
XIII.6.1 User level macro	178
XIII.6.2 Normal footnote	179
XIII.6.3 Paragraphed footnotes	184
XIII.6.4 Columnar footnotes	191
XIII.7 Critical notes presentation	198
XIII.7.1 Font tools	198
XIII.7.2 Pstart number in footnote	199
XIII.7.3 Lemma printing	199
XIII.7.4 Line number printing	200
XIII.7.5 Footnote grouped by line	210

XIV Familiar footnotes	211
XIV.1 Adjacent footnotes	211
XIV.2 Regular footnotes for numbered texts	213
XIV.3 Footnote formats	215
XIV.4 Footnote arrangement	215
XIV.4.1 User level macro	215
XIV.4.2 Normal footnotes	216
XIV.4.3 Two columns footnotes	222
XIV.4.4 Three columns footnotes	224
XIV.4.5 Paragraphed footnotes	226
XIV.5 Wrapping footnote marks in hyperlink	230
XV Code common to both critical and familiar footnote in normal arrangement	231
XVI Footnotes' width for two columns	232
XVII Footnotes' order	233
XVIII Footnotes' rule	233
XIX Specific skip for first series of footnotes	234
XIX.1 Overview	234
XIX.2 User level command	235
XIX.3 Internal commands	235
XX Endnotes	236
XX.1 Internal commands	236
XX.2 User level commands	240
XX.2.1 Inserting contents to endnotes	240
XX.2.2 Printing endnotes	241
XXI Generate series of notes	249
XXI.1 Test if series is still existing	249
XXI.2 Init specific to <code>reledpar</code>	249
XXI.3 For critical footnotes	249
XXI.3.1 Options	250
XXI.3.2 Create inserts, needed to add notes in foot	251
XXI.3.3 Create commands for critical apparatus, <code>\Afootnote</code> , <code>\Bfootnote</code> etc.	251
XXI.3.4 Set standard display	254
XXI.4 For familiar footnotes	254
XXI.4.1 Options	254
XXI.4.2 Create tools for familiar footnotes (<code>\footnoteX</code>)	255
XXI.5 The endnotes	257
XXI.5.1 The auxiliary file	257
XXI.5.2 The main macro	258

XXI.5.3 Tools	258
XXI.5.4 Internal commands	259
XXI.5.5 The options	259
XXI.6 Init standards series (A,B,C,D,E)	261
XXII Setting series display	261
XXII.1 Change series order	261
XXII.2 Test series order	261
XXII.2.1 Get the first series	262
XXII.3 Series setting	262
XXII.3.1 General way of working	262
XXII.3.2 Tools to set options	262
XXII.3.3 Tools to generate options commands	264
XXII.3.4 Options for critical notes	265
XXII.3.5 Options for familiar notes	267
XXII.3.6 Options for endnotes	268
XXII.4 Hooks for a particular footnote	270
XXII.5 Alias	270
XXIII Output routine	271
XXIII.1 Extra footnotes output	271
XXIII.2 Patching standard output's commands	274
XXIV Cross referencing	277
XXIV.1 Compatibility with xref	293
XXV Sidenotes	293
XXVI Minipages and such	301
XXVII Indexing	306
XXVII.1 Looking on package order	306
XXVII.2 Auxiliary macros for \edindex	307
XXVII.3 Code specific to \edindexin critical footnotes	308
XXVII.4 Analysis of command in indexed text	309
XXVII.5 Code for the formatted index	309
XXVII.6 Main code	310
XXVII.7 Hyperlink	312
XXVII.8 'innote' and 'notenumber' option of <code>indextools</code> package	314
XXVIII Glossaries	315
XXIX Verse	317
XXIX.1 Hanging symbol management	317
XXIX.2 Using & character	318
XXIX.3 Code category setting	318
XXIX.4 Stanza count and indent	318

XXIX.5 Numbering stanza	320
XXIX.6 Stanza number in note	321
XXIX.7 Main work	321
XXIX.8 Restore catcode and penalties	324
XXX Apparatus of Manuscripts	325
XXX.1 User level macro	325
XXX.2 Setting macro	326
XXX.3 Counters and lists	327
XXX.4 Auxiliary file macros	327
XXX.5 Action macro	328
XXX.6 Inserting footnote	333
XXX.7 Other	333
XXXI Arrays and tables	334
XXXI.1 Preamble: macro as environment	334
XXXI.2 Tabular environments	337
XXXI.2.1 Disabling and restoring commands	337
XXXI.2.2 Counters, boxes and lengths	341
XXXI.2.3 Tabular typesetting	345
XXXI.2.4 Environments	356
XXXII Quotation's commands	356
XXXIII Section's title commands	357
XXXIII.1 Commands to disable some feature	357
XXXIII.2 General overview	358
XXXIII.3 \beforeeledchapter command	358
XXXIII.4 Auxiliary commands	359
XXXIII.5 Patching standard commands	360
XXXIII.6 Main code of \eledxxx commands	365
XXXIII.7 Macros written in the auxiliary file	367
XXXIV Page breaking or no page breaking depending of specific lines	370
XXXV Long verse: prevents being separated by a page break	371
XXXVI Tools for hyperref package	372
XXXVII Compatibility with eledmac	373
Appendix A Things to do when changing versions	375
Appendix A.1 Migrating from edmac to ledmac	375
Appendix A.2 Migration from ledmac to eledmac	376
Appendix A.3 Migration to eledmac 1.5.1	377
Appendix A.4 Migration to eledmac 1.12.0	377
Appendix A.5 Migration to eledmac 17.1	378

Appendix A.6 Migration to elemac 1.21.0	378
Appendix A.6.1 \Xledsetnormalparstuff and \ledsetnormalparstuffX	378
Appendix A.6.2 Endnotes	378
Appendix A.7 Migration to elemac 1.22.0	378
Appendix A.8 Migration to elemac 1.23.0	378
Appendix A.9 Migration from elemac to reledmac	379
Appendix A.9.1 Risk of ‘no room for a new’	379
Appendix A.9.2 Multiple indices with memoir	379
Appendix A.9.3 Deprecated commands and options	379
Appendix A.9.4 \renewcommand replaced by command	380
Appendix A.9.5 Commands the names of which have been changed	380
Appendix A.9.6 Endnotes	382
Appendix A.9.7 Z Series	382
Appendix A.9.8 Internal commands	382
Appendix A.10 Migration to reledmac 2.1.0	382
Appendix A.11 Migration to reledmac 2.1.3	382
Appendix A.12 Migration to reledmac 2.3.0	382
Appendix A.13 Migration to reledmac 2.4.0	383
Appendix A.14 Migration to reledmac 2.5.0	383
Appendix A.15 Migration to reledmac 2.7.0	383
Appendix A.16 Migration to reledmac 2.7.2	383
Appendix A.17 Migration to reledmac 2.8.0	383
Appendix A.18 Migration to reledmac 2.13.1	383
Appendix A.19 Migration to reledmac 2.18.0	384
Appendix A.20 Migration to reledmac 2.21.0	384
Appendix A.21 Migration to reledmac 2.24.0	384
Appendix A.22 Migration to reledmac 2.26.0	384
References	385
Index	385
Change History	435

1 Introduction

1.1 Aim of the package

The `reledmac` package, together with `LATEX`, provides several important facilities for formatting critical editions of texts in a traditional manner. Major features include:

- automatic stepped line numbering, by page, section or paragraph;
- sub-lineation within the main series of line numbers;
- variant readings automatically keyed to line numbers;

- caters to both prose and verse;
- multiple series of footnotes and endnotes;
- block or columnar formatting of the footnotes;
- simple tabular material may be line numbered;
- indexing keyed to page and line numbers.

`reledmac` allows the scholar engaged in preparing a critical edition to focus attention wholly on the task of creating the critical text and evaluating the variant readings, text-critical notes and testimonia. `LATEX` and `reledmac` will take care of the formatting and visual correlation of all the disparate types of information.

Apart from `reledmac` there are other `LATEX` packages for typesetting critical editions. However, the aim of `reledmac` is to provide an “all in one” and flexible tool in the field of critical editions.

Any suggestions for new features are welcome.

This manual contains a general description of how to use `reledmac` followed by the complete source code and its extensive documentation (in sections I and following, enumerated with Roman numerals). It ends with a list of actions to do when migrating from one version to other, a change history and an index to the source code.

You do not need to read the source code for this package in order to use it; we provide this code primarily for reference, and many of our comments on it repeat material that is also found in earlier sections. But no documentation, however thorough, can cover every question that comes up and many can be answered quickly by consulting the code. On a first reading, we suggest that you read only the general documentation in sections 2, unless you are particularly interested in the innards of `reledmac`.

1.2 History

1.2.1 `edmac`

The original version of `edmac` was `TEXTED.TEX`, written by John Lavagnino in late 1987 and early 1988 for formatting critical editions of English plays.

John passed these macros on to Dominik Wujastyk who, in September–October 1988, added the footnote paragraphing mechanism, margin swapping and other changes to suit his own purposes, making the style more like that traditionally used for classical texts in Latin and Greek (e.g., the Oxford Classical Texts series). He also wrote some extra documentation and sent the files out to several people. This version of the macros was the first to be called `edmac`.

The present version was developed in the summer of 1990, with the intent of adding necessary features, streamlining and documenting the code, and further generalizing it to make it easily adaptable to the needs of editors in different disciplines. John did most of the general reworking and documentation, with the financial assistance of the Division of the Humanities and Social Sciences, California Institute of Technology. Dominik adapted the code to the conventions of Frank Mittelbach’s `doc` option, and added some

documentation, multiple-column footnotes, cross-references, and crop marks.¹ A description by John and Dominik of this version of `edmac` was published as ‘An overview of `edmac`: a PLAIN TeX format for critical editions’, *TUGboat* 11 (1990), pp. 623–643.

From 1991 through 1994, the macros continued to evolve, and were tested at a number of sites. We are very grateful to all the members of the (now defunct) `edmac@mailbase.ac.uk` discussion group who helped us with smoothing out the bugs and infelicities in the macros. Ron Whitney and our anonymous reviewer at the TUG were both of great help in ironing out last-minute wrinkles, while Ron made some important suggestions which may help to make future versions of `edmac` even more efficient. Wayne Sullivan, in particular, provided several important fixes and contributions, including adapting the Mittelbach/Schöpf ‘New Font Selection Scheme’ for use with PLAIN TeX and `edmac`. Another project Wayne has worked on is a DVI post-processor which works with an `edmac` that has been slightly modified to output `\specials`. This combination enables you to recover to some extent the text of each line as ASCII code, facilitating the creation of concordances, an *index verborum*, etc.

As of 1994, we were pleased to be able to say that `edmac` was being used for the real-life book production of several interesting editions, such as the Latin texts of Euclid’s *Elements*,² an edition of the letters of Nicolaus Copernicus,³ Simon Bredon’s *Arithmetica*,⁴ a Latin translation by Plato of Tivoli of an Arabic astrolabe text,⁵ a Latin translation of part II of the Arabic *Algebra* by Abū Kāmil Shujā’ b. Aslam,⁶ the Latin *Rithmacha* of Werinher von Tegernsee,⁷ a middle-Dutch romance epic on the Crusades,⁸ a seventeenth-century Hungarian politico-philosophical tract,⁹ an anonymous Latin compilation from Hungary entitled *Sermones Compilati in Studio Gererali Quinquecclesiensi in Regno Ungarie*,¹⁰ the collected letters and papers of Leibniz,¹¹ Theodosius’s *Spherics*, the German *Algorithmus* of Sacrobosco, the Sanskrit text of the *Kāśikāvṛtti* of Vāmana and Jayāditya,¹² and the English texts of Thomas Middleton’s collected works.

¹This version of the macros was used to format the Sanskrit text in volume I of *Metarules of Pāṇinian Grammar* by Dominik Wujastyk (Groningen: Forsten, 1993).

²Gerhard Brey used `edmac` in the production of Hubert L. L. Busard and Menso Folkerts, *Robert of Chester’s (?) Redaction of Euclid’s Elements, the so-called Adelard II Version*, 2 vols., (Basel, Boston, Berlin: Birkhäuser, 1992).

³Being prepared at the German Copernicus Research Institute, Munich.

⁴Being prepared by Menso Folkerts *et al.*, at the Institut für Geschichte der Naturwissenschaften in Munich.

⁵Richard Lorch, Gerhard Brey *et al.*, at the same Institute.

⁶Richard Lorch, ‘Abū Kāmil on the Pentagon and Decagon’ in *Vestigia Mathematica*, ed. M. Folkerts and J. P. Hogendijk (Amsterdam, Atlanta: Rodopi, 1993).

⁷Menso Folkerts, ‘Die *Rithmacha* des Werinher von Tegernsee’, *ibid.*

⁸Geert H. M. Claassens, *De Middelnederlandse Kruisvaartromans*, (Amsterdam: Schiphower en Brinkman, 1993).

⁹Emil Hargittay, *Csáky István: Politica philosophiae Okoskodás-szerint való rendes életnek példája (1664–1674)* (Budapest: Argumentum Kiadó, 1992).

¹⁰Being produced, as was the previous book, by Gyula Mayer in Budapest.

¹¹Leibniz, *Sämtliche Schriften und Briefe*, series I, III, VII, being edited by Dr. H. Breger, Dr. N. Gädeke and others at the Leibniz-Archiv, Niedersächsische Landesbibliothek, Hannover. (see <http://www.nlb-hannover.de/Leibniz>)

¹²Being prepared at Poona and Lausanne Universities.

1.2.2 ledmac

Version 1.0 of `tabmac` was released by Herbert Breger in October 1996. This added the capability for typesetting tabular material.

Version 0.01 of `edstanza` was released by Wayne Sullivan in June 1992, to help a colleague with typesetting Irish verse.

In March 2003 Peter Wilson started an attempt to port `edmac` from TeX to LaTeX. The starting point was `edmac` version 3.16 as documented on 19 July 1994 (available from CTAN). In August 2003 the `tabmac` functions were added; the starting point for these being version 1.0 of October 1996. The `edstanza` (v0.01) functions were added in February 2004. Sidenotes and regular footnotes in numbered text were added in April 2004. This port was called `ledmac` (*ATeX edmac*).

Since July 2011, `ledmac` is maintained by Maïeul Rouquette. It is increasingly powerful and flexible, but it also has become increasingly divergent from the original TeX macro.

1.2.3 eleedmac

Important changes were put in version 1.0, to make `ledmac` more easily extensible (see 7 p. 38). These changes can trigger small problems with the old customization. That is why a new name was selected: `eleedmac` (extended `ledmac`).

To migrate from `ledmac` to `eleedmac`, please read Appendix A.2 p. 376.

1.2.4 reledmac

`eleedmac` has facilitated the creation of customized critical editions. However, the changes made to allow such customization were made in a non-systematic way. Many deprecated commands were kept and many technical ‘debts’ were accumulated, hindering the future evolution of the package.

For these reasons, Maïeul Rouquette decided on a spring cleaning of the code. As some commands name were changed, the resulting compatibility was broken (a little).

A new name was selected: `reledmac` (extended renewed `eleedmac`). To migrate from `eleedmac` to `reledmac`, please read Appendix A.9 p. 379.

1.3 Bibliography

A collaborative list of works edited with (r)(e)`ledmac` is available at https://www.zotero.org/groups/critical_editions_typeset_with_edmac_ledmac_and_eleedmac/items. Please add your own edition made with (r)(e)`ledmac`.

If you write book or article about (r)(e)`ledmac`, please add it on the collaborative bibliography on https://www.zotero.org/groups/articles_and_books_about_reledmac/items.

2 How the package works – the problem of the number of L^AT_EX runs

The `reledmac` package is a three-pass package like L^AT_EX itself. Although your textual apparatus and line numbers will be printed on the first run, it takes two more compilations by L^AT_EX to be sure that everything is correctly placed, and one more if you typeset right-to-left text with X_EL^AT_EX. If you make any subsequent changes altering the number of lines or notes, the input file may similarly require three passes to get everything to the right place. `reledmac` will tell you that you need to make more runs when it detects changes, but it does not expend the labor to check this thoroughly. If you have problems with a line or two misnumbered at the top of a page, try running L^AT_EX once or twice more.

However, the best way to be sure that one has made the right number of runs is to use some of L^AT_EX's run scripts like *latexmk*.

3 Compatibility warning

If you use other classes than `\article` or `\book`, or modify the layout with `geometry`, some settings should be made to have correct height for the blocks of notes.

Please read 7.12.6 p. 50.

A file may mix *numbered* and *unnumbered* text.

Numbered text is printed with marginal line numbers and can include footnotes and endnotes that are referenced to those line numbers: this is how you will want to print the text that you are editing.

Unnumbered text is not printed with line numbers, and you can't use `reledmac`'s note commands with it: this is appropriate for introductions and other material added by the editor around the edited text.

4 Options

The package can be loaded with a number of global options which are listed here. There are two types of options: 1) options which provide specific features, and, 2) options which optimize the package's performance. It is advisable for you to read the relevant parts of the handbook, before reading about the first type of option (specific features), but you can look at the second type (package optimization) in your first reading of the manual.

4.1 Specific features

`draft` underlines lemmas in the main text.

`auxdir` `reledmac` generates auxiliary files. It could be useful to store them in a specific directory. You can set it using `auxdir=<folder>` option. Note the two following point:

1. \TeX is not able to create folder. You should create it yourself.
2. The option does not change the default \LaTeX auxiliary files (.aux, .toc, ...).

eledmac-compat help to migrate from `eledmac` to `reledmac` (see Appendix A.9.5 p. 380).

sweaseinsensitive make `\samedword` command case insensitive.

nopenalties must be called in some cases when using paragraphed endnotes (?? p. ??

nopbinverse prevents page break within verse environment.

noquotation by default, the quotation environment is redefined within numbered text.
You can disable this redefinition with `noquotation` (see 17 p. 72).

parapparatus by default, the apparatus cannot contain paragraph breaks; this option enables paragraphing inside the apparatus.

widthliketwocolumns set the width of the text printed in a single column to be the same as the width of the text printed in two parallel columns with `reledpar`. This is useful when alternating between normal and parallel typesetting.

xindy and **xindy+hyperref** select `xindy` as the index processor (13.4 p. 66).

4.2 Optimizing package performance

nocritical disables tools for critical footnotes (`\Afootnote`, `\Bfootnote` etc.). If you do not need critical footnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.

noeledsec disables tools for `\eledsection` and related commands (16.2 p. 71).

noend disables tools for endnotes (`\Aendnote`, `\Bendnote` etc.). If you do not need endnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.

nofamiliar disables tools for familiar footnotes (`\footnoteA`, `\footnoteB` etc.). If you do not need familiar footnotes, this option lets `reledmac` run faster. It will also preserve room for other packages.

noledgroup `reledmac` allows use of a series of critical notes and a new series of normal notes inside `minipage` and `ledgroup` environments (see 10 p. 58). However, such features use up computer memory, at the expense of other processing needs. So if you do not need this feature, use `noledgroup` option. This should make `reledmac` faster.

series `reledmac` defines five levels of notes: A, B, C, D, E. Using all these levels consumes memory space and processing speed. This is why, if your work does not require the entire A–E series, you can narrow down the available number of series. For example, if you only need A and B series, call the package with `series={A,B}` option.

5 Text lines and paragraphs numbering

5.1 Text lines numbering

`\beginnumbering` Each section of numbered text must be preceded by `\beginnumbering` and followed by `\endnumbering`, as in the following example.

```
\beginnumbering
Text
\endnumbering
```

The `\beginnumbering` macro resets the line number to zero, reads an auxiliary file called `<jobname>.nn` (where `<jobname>` is the name of the main input file for this job, and `nn` is 1 for the first numbered section, 2 for the second section, and so on), and then creates a new version of this auxiliary file to collect information during this run. The first instance of `\beginnumbering` also opens a file called `<jobname>.<series>end` to receive the text of the endnotes. `\endnumbering` closes the `<jobname>.nn` file.

If the line numbering of a text is to be continuous from start to end, then the whole text will be typed between one pair of `\beginnumbering` and `\endnumbering` commands. But your text will most often contain chapter or other divisions marking sections that should be independently numbered, and these will be appropriate places to begin new numbered sections.

`reledmac` has to read and store in memory a certain amount of information about the entire section when it encounters a `\beginnumbering` command, so it speeds up the processing and reduces memory use when a text is divided into a larger number of sections (at the expense of multiplying the number of external files that are generated).

5.2 Paragraphs

5.2.1 Basics

`\pstart` Within a numbered section, each paragraph of numbered text must be marked using the
`\pend` `\pstart` and `\pend` commands like this:

```
\pstart
Paragraph of text.
\pend
```

Text that appears within a numbered section but is not marked with `\pstart` and `\pend` will not be numbered.

The following example shows the proper section and paragraph markup and the kind of output that would typically be generated:

```
\beginnumbering
\pstart
This is a sample paragraph, with
lines numbered automatically.
\pend

\pstart
This paragraph too has its
lines automatically numbered.
\pend

The lines of this paragraph are
not numbered.

\pstart
And here the numbering begins
again.
\pend
\endnumbering
```

5.2.2 Automatically producing \pstart ... \pend

`\autopar` You can use `\autopar` to avoid the nuisance of this paragraph markup and still have every paragraph automatically numbered. The scope of the `\autopar` command needs to be limited by keeping it within a group, as follows:

```
\begingroup
\beginnumbering
\autopar

A paragraph of numbered text.

Another paragraph of numbered
text.

\endnumbering
\endgroup
```

`\autopar` fails, however, on paragraphs that start with a { or with any other command that starts a new group before it generates any text. Such paragraphs need to be started explicitly, before the new group is opened, using `\indent`, `\noindent`, or `\leavevmode`, or using `\pstart` itself.¹³

5.2.3 Content before specific \pstart and after specific \pend

Both `\pstart` and `\pend` can take an optional argument in brackets. Its content will be printed before the beginning of `\pstart` / after the end of `\pend` instead of the argument of `\AtEveryPstart` / `\AtEveryPend`.

¹³For a detailed study of the reasons for this restriction, see Barbara Beeton, ‘Initiation rites’, *TUGboat* 12 (1991), pp. 257–258.

Note that a `\noindent` will be automatically added before this argument, and, consequently, a `\parskip` will be inserted. You can use a second optional argument in brackets to avoid that `\noindent`.

```
\pstart[foo] % A \noindent will be inserted before foo.  
\pstart[] [foo] % No \noindent before foo.
```

The second optional argument of `\pstart` / `\pend` replaces the argument of `\AtEveryPstart*` / `\AtEveryPend*`.

If you need to start a `\pstart` with brackets, or to add brackets after a `\pend`, just add a `\relax` between `\pstart ... \pend` and the brackets.

This feature is also useful when typesetting verses (see 9 p. 51) or `reledpar` (see 19.2 p. 76).

A `\noindent` is automatically added before this argument.

5.2.4 Content before every `\pstart` and after every `\pend`

`\AtEveryPstart` You can use both `\AtEveryPstart` and `\AtEveryPend`. Their arguments will be printed before every `\pstart` begins / after every `\pend` ends.

Note that a `\noindent` will be inserted before the argument, and, consequently, a `\parskip`. You can use the starred version of `\AtEveryPstart` and `\AtEveryPend` to avoid the `\noindent`.

`\AtStartEveryPstart` `\AtEndEveryPend` The argument of `\AtStartEveryPstart` / `\AtEndEveryPend` will be inserted at the beginning / the end of every `\pstart` / `\pend` in the same paragraph. For example, if you want each `\pstart` to start with a star, you can use:

```
\AtStartEveryPstart{*}
```

Instead of manually doing

```
\pstart * Real pstart content.\pend
```

5.2.5 Numbering paragraphs (`\pstart`)

It is possible to insert a number at every `\pstart` command; you must use the `\numberpstarttrue` command to have it. You can stop the numbering with `\numberpstartfalse`. You can redefine the command `\thepstart` to change style. You can change the value of the pstart number by using `after \beginnumbering`:

```
\setcounter{pstart}{value}
```

On each `\beginnumbering` the numbering restarts.

With the `\sidepstartnumtrue` command, the number of `\pstart` will be printed inside. In this case, the line number will be not printed.

With the `\labelpstarttrue` command, a `\label` added just after a `\pstart` will refer to the number of this pstart.

5.2.6 Languages written in Right to Left

If you use languages written right to left with $\text{Lua}\text{\TeX}$ or $\text{Xe}\text{\TeX}$, you must switch text direction *before* the $\text{\textbackslash pstart}$ command.

5.2.7 Memory limits

This paragraph is kept for history, but the problems described below should not appear with the most recent version of \TeX .

$\text{\textbackslash pausenumbering}$
 $\text{\textbackslash resumenumbering}$

reledmac stores a lot of information about line numbers and footnotes in memory as it goes through a numbered section. But at the end of such a section, it empties its memory out, so to speak. If your text has a very long numbered section it is possible that your \TeX may reach its memory limit. There are two solutions to this.

The first solution is to get a larger \TeX with increased memory.

The second solution is to split your long section into several smaller ones. The trouble with this is that your line numbering will start again at zero with each new section. To avoid this problem, we provide $\text{\textbackslash pausenumbering}$ and $\text{\textbackslash resumenumbering}$ which are just like $\text{\textbackslash endnumbering}$... $\text{\textbackslash beginnumbering}$, except that they arrange for your line numbering to continue across the break. Use $\text{\textbackslash pausenumbering}$ only between numbered paragraphs:

```
\begin{numbering}
\pstart
Paragraph of text.
\pend
\pausenumbering

\resumenumbering
\pstart
Another paragraph.
\pend
\endnumbering
```

We have defined these commands as two macros, in case you find it necessary to insert text between numbered sections without disturbing the line numbering. But if you are really just using these macros to save memory, you might as well type,

```
\newcommand{\memorybreak}{\pausenumbering\resumenumbering}
```

and type $\text{\textbackslash memorybreak}$ between the relevant $\text{\textbackslash pend}$ and $\text{\textbackslash pstart}$.

5.3 Lineation commands

5.3.1 Disabling lineation

$\text{\textbackslash numberlinefalse}$ Line numbering can be disabled with $\text{\textbackslash numberlinefalse}$. It can be enabled again with $\text{\textbackslash numberlinetrue}$.

5.3.2 Setting lineation start and step

`\firstlinenum`
`\linenumincrement`

By default, `reledmac` numbers every 5th line. There are two counters that control this behaviour: `firstlinenum` and `linenumincrement`. They can be changed using `\firstlinenum{<num>}` and `\linenumincrement{<num>}`. `\firstlinenum` specifies the first line that will have a printed number, and `\linenumincrement` is the difference between successive numbered lines. For example, to start printing numbers at the first line and to have every other line numbered:

`\firstlinenum{1} \linenumincrement{2}`

There are similar commands, `\firstsublinenum{<num>}` and `\sublinenumincrement{<num>}` for controlling sub-line numbering.

You can define `\linenumberlist` to specify a non-uniform distribution of printed line numbers. For example:

`\gdef\linenumberlist{1,2,3,5,7,11,13,17,19,23,29}`

to have numbers printed on prime-numbered lines only. There must be no spaces within the definition which consists of comma-separated integer numbers. The numbers can be in any order but it is easier to read if you put them in numerical order. Either omitting the definition of `\linenumberlist` or following the empty definition

`\gdef\linenumberlist{}`

the standard numbering sequence is applied. The standard sequence is that specified by the combination of the `firstlinenum`, `linenumincrement`, `firstsublinenum` and `linenumincrement` counter values.

5.3.3 Setting lineation reset

`\lineation`

Lines can be numbered either by page, by `pstart` or by section; you specify this using the `\lineation{<arg>}` macro, where `<arg>` is either `page`, `pstart` or `section`.

You may only use this command at places where numbering is not in effect; you can't change the lineation system within a section. You can change it between sections: they don't all have to use the same lineation system. The package's standard setting is `\lineation{section}`. If the lineation is by `pstart`, the `pstart` number will be printed before the line number in the notes.

5.3.4 Setting line number margin

`\linenummargin`

The command `\linenummargin{<location>}` specifies the margin where the line (or `pstart`) numbers will be printed. The permissible values for `<location>` are `left`, `right`, `inner`, or `outer`: for example, `\linenummargin{inner}`. The package's default setting is

`\linenummargin{left}`

to typeset the numbers in the left hand margin. You can change this whenever you're not in the middle of making a paragraph.

More precisely, the value of `\linenummargin` used is the value in effect at the `\pend` of a numbered paragraph. Apart from an initial setting for `\linenummargin`, only change `\linenummargin` after a `\pend`, whereupon it will apply to all following numbered paragraphs, until changed again (changing it between a `\pstart` and `\pend` pair will apply the change to all of the current paragraph).

5.3.5 Other settings

```
\leftlinenum
\rightlinenum
\linenumsep
```

When a marginal line number is to be printed, there are many ways to display it. You can redefine `\leftlinenum` and `\rightlinenum` to change the way marginal line numbers are printed in the left and right margins respectively; the initial versions print the number in font `\numlabfont` (described below) at a distance `\linenumsep` (initially set to one pica) from the text.

5.4 Changing the line numbers

Normally, line numbering starts at 1 for the first line of a section and increments by one for each line thereafter. There are various common modifications of this system and the commands described here allow you to put such modifications into effect.

5.4.1 Sublineation

```
\startsub
\endsub
```

You insert the `\startsub` and `\endsub` commands in your text to turn sub-lineation on and off. For example, stage directions in plays are often numbered with sub-line numbers: as line 10.1, 10.2, 10.3, rather than as 11, 12, and 13. Titles and headings are sometimes numbered with sub-line numbers as well.

When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it doesn't take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if it changes in the middle.

```
Xsublinesep
Xsublinesepside
```

You can change the separator between the line number and the subline number either by using `\Xsublinesep` without any optional argument (7.2.9 p. 42) or by using `\Xsublinesepside`. In the second case, it will change the separator only for line numbers in the margins, not in the footnotes.

5.4.2 Locking lineation

```
\startlock
\endlock
```

The `\startlock` command, used in running text, locks the line number at its current value, until you insert `\endlock`. It can tell for itself whether you are in a patch of line or sub-line numbering. One use for line-number locking is in printing poetry: there the line numbers should be those of verse lines rather than of printed lines, even when a verse line requires several printed lines. But in this case you may use the `\stanza` mechanism, see 9 p. 51.

```
\lockdisp
```

When line-number locking is used, several printed lines may have the same line number, and you have to specify whether you want the number attached to the first printed line or the last, or whether you just want the number printed by them all, assuming that the settings of the previous parameters requires the display of a line number for this line. You specify your preference using `\lockdisp{<arg>}`; its argument is a word, either `first`, `last`, or `all`. The package initially sets this as `\lockdisp{first}`.

5.4.3 Setting and changing line number

```
\setline
\advanceline
```

In some cases you may want to modify the line numbers that are automatically cal-

culated: if you are printing only fragments of a work but want to print line numbers appropriate to a complete version, for example. The `\setline{\langle num \rangle}` and `\advanceline{\langle num \rangle}` commands may be used to change the current line's number (or the sub-line number, if sub-lineation is currently on). They change both the marginal line numbers and the line numbers passed to the notes. `\setline` takes one argument, the value to which you want the line number set; it must be 0 or greater. `\advanceline` takes one argument, an amount that should be added to the current line number; it may be positive or negative.

`\setlinenum` The `\setline` and `\advanceline` macros should only be used within a `\pstart...\pend` group. The `\setlinenum{\langle num \rangle}` command can be used outside such a group, for example, between a `\pend` and a `\pstart`. It sets the line number to `\langle num \rangle`. It has no effect if used within a `\pstart...\pend` group.

5.4.4 Line number style

`\linenumberstyle` Line numbers are normally printed as arabic numbers. You can use `\linenumberstyle{\langle style \rangle}` to change the numbering style. `\langle style \rangle` must be one of:

`Alph` Uppercase letters (A ... Z).

`alph` Lowercase letters (a ... z).

`arabic` Arabic numerals (1, 2, ...)

`Roman` Uppercase Roman numerals (I, II, ...)

`roman` Lowercase Roman numerals (i, ii, ...)

Note that with the `Alph` or `alph` styles, ‘numbers’ must be between 1 and 26 inclusive.

Similarly `\sublinenumberstyle{\langle style \rangle}` can be used to change the numbering style of sub-line numbers, which is normally arabic numerals.

5.4.5 Skipping and hidding number

`\skipnumbering` When inserted into a numbered line the macro `\skipnumbering` causes the numbering of that particular line to be skipped; that is, the line number is unchanged and no line number will be printed. Note that if you use it in `\stanza`, you must call it at the beginning of the verse.

`\hidenumbering` When inserted into a numbered line, the macro `\hidenumbering` causes the number for that particular line to be hidden; namely, no line number will print. Note that if you use it in `\stanza`, you must call it at the beginning of the verse.

`\hidenumberingonleftpage` is like `hidenumbering`, but is applied only on left page. `\hidenumberingonrightpage` is applied on right page. They can be useful if the position of the line number is depending of the position of the page, but the position of marginal note is fixed.

5.5 Executing code at each line

`\dolinehook`
`\doinsidelinehook`

`\reledmac` provides an advanced feature for users. The argument passed to `\dolinehook{\arg}` will be executed before slicing a new line in the paragraph. The argument passed to `\doinsidelinehook{\arg}` will be executed before printing a new line, when the line number has already been fixed. In many cases, the latter is more useful than the former. The file `examples/2-line_numbers_in_header.tex` provides an example for printing the first and last line numbers of a page in the header.

6 Apparatus commands

6.1 Terminology

We call “critical notes” notes which refer to both a lemma, that is a part of text and a line number. Critical notes are subdivided in critical footnotes and critical endnotes.

We call “familiar notes” notes which refer to a footnote mark in the main text.

`\reledmac` manages many series of notes of each category. A series of notes is identified by an uppercase letter. When the series letter is at the *beginning* of a command name, it refers to a critical footnote. When the series letter is at the *end* of a command name, it refers to a familiar footnote.

So :

- `\Afootnote` is a critical footnote of the series A.
- `\Bendnote` is a critical endnote of the series B.
- `\footnoteC` is a familiar footnote of the series C.

6.2 Critical notes

6.2.1 The lemma

`\edtext`

Within numbered paragraphs, all footnotes and endnotes are generated by the `\edtext` macro:

`\edtext{\<lemma\>}{\<commands\>}`

The `\<lemma\>` argument is the lemma in the main text: `\edtext` both prints this as part of the text, and makes it available to the `\<commands\>` you specify to generate notes.

For example:

I am happy : I saw my friend <code>\edtext{Smith}{</code> <code>\Afootnote{Jones C, D.}}</code> on Tuesday.	1 I am happy : I saw my friend Smith on 2 Tuesday. <hr style="width: 20%; margin-left: auto; margin-right: 0;"/> 1 Smith] Jones C, D.
--	--

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D.` The footnote macro is supplied with the line number at which the lemma appears in the main text.

The *<lemma>* may contain further \edtext commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

```
I am happy : \edtext{I saw my friend}{\Afootnote{Jones C, D.}} on Tuesday.\Bfootnote{The date was July 16, 1954.}
} 1 I am happy : I saw my friend Smith on
  \edtext{Smith}{\Afootnote{Jones C, D.}} 2 Tuesday.
  _____
  1 Smith ] Jones C, D.
  _____
  1-2 I saw my friend Smith on Tuesday.] The
  date was July 16, 1954.
```

However, \edtext cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; an \edtext that starts in the *<lemma>* argument of another \edtext must end there, too. (The \lemma and \linenum commands may be used to generate overlapping notes if necessary.)

6.2.2 Footnotes

The second argument of the \edtext macro, *<commands>*, may contain a series of subsidiary commands that generate various kinds of notes.

\Afootnote
\Bfootnote
\Cfootnote
\Dfootnote
\Efootnote

Five separate series of the footnotes are maintained; each macro takes one argument like \Afootnote{<text>}. When all of the six are used, the A notes appear in a layer just below the main text, followed by the rest in turn, down to the E notes at the bottom. These are the main macros that you will use to construct the critical apparatus of your text.

If you need more series of critical notes, please look at 6.7.1 p. 36.

An optional argument can be added before the text of the footnote. Its value is a comma-separated list of options. The available options are:

- `fulllines` to disable `Xtwolines` and `Xmorethanwolines` features for this note (cf. 7.2.5 p. 40).
- `nonum` disables line numbering for this note. A horizontal blank space is added instead. You can use `\Xinplaceoflemmaseparator` to set it (7.4.1 p. 44).
- `nosep` to disable the lemma separator for this note.
- `linerangesep=<c>` to change to `<c>` the separator between start line and end line for this particular note.

Example: \Afootnote[nonum]{<text>}.

6.2.3 Endnotes

\Aendnote
\Bendnote
\Cendnote
\Dendnote
\Eendnote

Inserting endnotes The package also maintains five separate series of endnotes. If you do not need the endnotes facility, you should use `noend` option when loading `reledmac`.

The mechanism is similar to the one for footnotes: each macro takes one or more optional arguments and one single argument, like:

\Aendnote[<option>]{<text>}.

$\langle option \rangle$ can contain a comma-separated list of values. Allowed values are:

- `fulllines` to disable `\Xendtwolines` and `\Xendmorethanwolines` features for this particular note (cf. 7.2.5 p. 40).
- `nonum` to disable line number for this particular note.
- `nosep` to disable the lemma separator for this particular note. A horizontal blank space is added instead. You can use `\Xendinplaceoflemmaseparator` to set it (7.4.2 p. 45).
- `linerangesep=⟨c⟩` to change to $\langle c \rangle$ the separator between start line and end line for this particular note.

`\doendnotes`

Printing endnotes Normally, endnotes are not printed: you must use the `\doendnotes{⟨s⟩}`, where $\langle s \rangle$ is the letter of the series to be printed. Put this command where you want the corresponding set of endnotes printed. In this case, all the endnotes of the $\langle s \rangle$ series are printed, for all numbered sections.

`\doendnotesbysection`

However, you may want to print the endnotes of one given series covering the first numbered section, then the endnotes of another given series covering the first numbered section, then the endnotes of the first given series covering the second numbered section, then the endnotes of the second given series covering the second numbered section, and so forth. In this case, use `\doendnotesbysection{⟨s⟩}`. For each value of $\langle s \rangle$, the first call of the command will print the notes for the first series, the second call will print the notes for the second series etc. For example, do:

```
\section{Endnotes}
\subsection{First text}
\doendnotesbysection{A}
\doendnotesbysection{B}
\subsection{Second text}
\doendnotesbysection{A}
\doendnotesbysection{B}
```

Note that by default inside endnotes no separator is used between the lemma and the content. However you can use the `\Xendlemmaseparator` macro to define one (7.4.2 p. 44).

As endnotes may be printed at any point in the document they always start with the page number where they are called.

`\toendnotes` `\Xtoendnotes`

Code between endnotes Sometimes, it is useful to insert content between endnotes of the same series: for example to separate endnotes of different sections of the same text. In this case, you could use *inside numbered text* the command:

`\toendnotes[⟨series⟩]{⟨content⟩}` where $\langle series \rangle$ is a comma-separated list of the series of endnotes where $\langle content \rangle$ must be inserted. If $\langle series \rangle$ is empty, then $\langle content \rangle$ is inserted to all the series.

For example:

```
\toendnotes{\section{Section's title}}
```

Alternatively, you can use `\Xtoendnotes{<content>}`, where “X” must be replaced by a series letter.

Remember that the endnotes are temporarily stored in an auxiliary file. That means in general you want to write the `<content>` in the auxiliary file *without expanding it*, that is without interpreting TeX content.

However, in some cases, you may want to write a once-expanded¹⁴ version of the `<content>`, that is the version where the commands are expanded on the first level. This can be, for example, to get a counter value. Use the starred version in this case. For example:

```
\atoendnotes*{\string\section{Letter 1 (chap. \thechapter)}}
```

6.2.4 Paragraph in critical apparatus

By default, no paragraph can be made in the notes of the critical apparatus. You can allow it by adding the options `parapparatus` when loading the package :

```
\usepackage[parapparatus]{eledmac}
```

Note that you *cannot* use paragraphs (e.g. blank lines or `\par`) inside of notes, when they are set to `paragraph` arrangement!

6.2.5 Change lemma and line number

\lemma If you want to change the lemma that gets passed to the notes, you can do this by using `\lemma{<alternative>}` within the second argument to `\edtext` and before the note commands. The most common use of this command is to abbreviate the lemma that’s printed in the notes. For example:

```
I am happy :  

\edtext{I saw my friend  

\edtext{Smith}{\Afootnote{Jones  

C, D.}} on Tuesday.}  

{\lemma{I \dots\ Tuesday.}  

\Bfootnote{The date was  

July 16, 1954.}}  

} 1 I am happy : I saw my friend Smith on  

2 Tuesday.  

_____  

1 Smith ] Jones C, D.  

_____  

1-2 I ... Tuesday. ] The date was July 16, 1954.
```

\linenum You can use `\linenum{<arg>}` to change the line numbers passed to the notes. `<arg>` actually consist of seven parameters: the page, line, and sub-line number for the start of the lemma; the same three numbers for the end of the lemma; and the font specifier for the lemma. As the argument to `\linenum`, you specify those seven parameters in that order, separated by vertical bars (the `|` character). I.e.

¹⁴The expansion mechanism of TeX is a quite complex problem, but fundamental. We have no place to explain it fully here. Read introduction to TeX to understand well.

\linenum{\langle start page\rangle | \langle s. line\rangle | \langle s. sub-l.\rangle | \langle end p.\rangle | \langle e. l.\rangle | \langle e. sub-l.\rangle | \langle font\rangle | }

However, you can retain the value computed by `reledmac` for any number by simply omitting it; and you can omit a sequence of vertical bars at the end of the argument. For example, `\linenum{|||23}` changes only the ending page number of the current lemma.

This command does not change the marginal line numbers in any way; it just changes the numbers passed to the notes. Its use comes in situations that `\edtext` has trouble dealing with for whatever reason. If you need notes for overlapping passages that aren't nested, for instance, you can use `\lemma` and `\linenum` to generate such notes despite the limitations of `\edtext`. If the `\langle lemma\rangle` argument to `\edtext` is extremely long, you may run out of memory; here again you can specify a note with an abbreviated lemma using `\lemma` and `\linenum`. The numbers used in `\linenum` need not be entered manually; you can use the ‘x-’ symbolic cross-referencing commands below (11 p. 59) to compute them automatically.

Similarly, being able to manually change the lemma's font specifier in the notes might be important if you were using multiple scripts or languages. The form of the font specifier is three separate codes separated by / characters, giving the family, series, and shape codes as defined within NFSS.

6.2.6 Changing the names of commands for critical apparatus

The commands for generating the apparatus have been given rather bland names, because editors in different fields have widely divergent notions of what sort of notes are required, where they should be printed, and what they should be called. But this does not mean you have to type `\Afootnote` when you would rather type something you find more meaningful, like `\variant`.

We recommend that you create a series of such aliases and use them instead of the names chosen here; all you have to do is put commands of this form at the start of your file:¹⁵

```
\newcommandx{\variant}[2][1,usedefault]{\Afootnote[#1]{#2}}
\newcommandx{\explanatory}[2][1,usedefault]{\Bfootnote[#1]{#2}}
\newcommand{\trivial}[1]{\Aendnote{#1}}
\newcommandx{\testimonia}[2][1,usedefault]{\Cfootnote[#1]{#2}}
```

6.3 Disambiguation of identical words in the apparatus

Sometimes, the same word occurs twice (or more) in the same line. `reledmac` provides tools to disambiguate references in the critical notes. The lemma will be followed by a reference number if a given word occurs more than once in the same line.

6.3.1 Basic use

`\sameword` To use this tool, you have to mark every occurrence of the potentially ambiguous term

¹⁵We use `\newcommand` and `\newcommandx` instead of classical `\let` command because the `edtabular` environments have to modify the notes definition, and we need to use the newest definition of notes. Read the

with the `\sameword` command:

```
Lupus \sameword{aut} canis \edtext{\sameword{aut}}{\Afootnote{et}} felix
```

In this example, `aut` will be followed, in the critical note, by the exponent 2 if it is printed in the same line as the first `aut`, but it will not if it is printed in a different line. The number is printed only after the second run.

6.3.2 Case setting

By default, `\sameword` is sensitive to the case. E.g. “foo” is considered as a different word to “Foo”.

You can use the `swcaseinsensitive` when loading the package to make `\sameword` insensitive to the case, i.e. to consider “foo” as identical “Foo”.

6.3.3 Notes about input encoding with UTF-8 processor

If you use UTF-8 processor, like Xe^TE_X or Lua^TE_X, there should not be any glitches. However, pay attention to how characters are encoded. Similar-looking characters may be represented differently in unicode numbering.

For instance, in Greek, “*q*” has two possible unicode numbers:

- GREEK SMALL LETTER ALPHA (U+03B1) + COMBINING GREEK YPOGEGRAMMENI (U+0345)
- GREEK SMALL LETTER ALPHA WITH YPOGEGRAMMENI (U+1FB3)

Which unicode number you use depends, many times, on your keyboard configuration (the computer-input system).

Inside `reledmac`, the `\sameword` command considers these two unicodes (code positions) as different characters. If you use only one unicode number consistently, the distinction will probably make no difference to how your text looks, but `\sameword` will process the text inaccurately, based on the unicode numbers. To prevent this, do the following:

- If you use Xe^TE_X, add this line in your preamble: `\XeTeXinputnormalization 1`.
- If you use Lua^TE_X, use the `uninormalize` package of Michal Hoftich¹⁶ with the `buffer` option set to true.

With these tools, Xe^TE_X / Lua^TE_X will dynamically normalize unicode input when reading the file. Consequently, you will have no problems with the `\sameword` command.

handbook of `xargs` to know more about `\newcommandx`.

¹⁶<https://github.com/michal-h21/uninormalize>.

6.3.4 Use with \lemma command

If you use the `\lemma` command, `reledmac` cannot know to which occurrence of `\sameword` in the first argument of `\edtext` a word marked with `\sameword` in `\lemma` should refer.

For example, in the following example:

```
some thing
\edtext{\sameword{sw}}
    and other \sameword{sw}
    and again \sameword{sw}
    it is all}%
{\lemma{\sameword{sw} \ldots all}\Afootnote{critical note}}.%
```

`reledmac` cannot know if the “sw” in `\lemma` refers to the word after “thing”, after “other”, or after “again”.

Consequently, you must tell `reledmac` to which instance of `\sameword` you are referring in the first argument of `\edtext`:

- In the content of `\lemma`, use `\sameword` with no optional argument.
- In the first argument of `\edtext`, use `\sameword` with the optional argument $[\langle X \rangle]$. $\langle X \rangle$ is the depth of the `\edtext` where the `\lemma` is used. So if the `\lemma` is called in a `\edtext` inside another `\edtext`, $\langle X \rangle$ is equal to 2. If the `\lemma` is called in a `\edtext` “of first level”, $\langle X \rangle$ is equal to 1. If the lemma is called in both 1 and 2 `\edtext` depth, $\langle X \rangle$ is 1,2. If that word is referenced in the lemma of every `\edtext` depth, $\langle X \rangle$ can also be set to `inlemma`.


Note that only words that are actually referenced in a `\lemma` need the optional argument. Therefore, the first `\sameword` in the example above should have “1” as its optional argument, to be referenced correctly in the lemma.

Note also that the $\langle X \rangle$ does not refer to the level where the `\sameword` occurs, but to the level of the `\lemma` that refers to that `\sameword`. For example:

```
\edtext{some \edtext{\sameword[1]{word}}{\Afootnote{om. M}}}
    and other \sameword{word}
    and again a \sameword{word}
    it is all}%
{\lemma{some \sameword{word} \ldots all}\Afootnote{critical note}}.%
```

Here the `\sameword` occurs in an `\edtext` of level 2, but since it is referenced by `\lemma` on level 1, it has “1” in the optional argument.

In the following example figure, each framed box represents an `\edtext` level. Each number is an occurrence of `\sameword`. After a framed box, the text in superscript represents the content of `\lemma` for that `\edtext` level. The text in subscript at the right of a number represents the content of the optional argument of `\sameword`.



The \sameword number 3 is called in a \lemma related to an \edtext of level 2. It must be marked by “2”.

The \sameword number 5 is called in a \lemma related to \edtext of level 1. It must be marked by “1”.

The \sameword number 1 is called in two \lemmas: one related to a \edtext of level 1, the other related to \edtext of level 2. It must be marked by “1,2”. However, as \lemma is called only in level 1 and 2, “1,2” could replaced by “inlemma”.

The \sameword number 2 is in the first argument of a \edtext of level 3, but it has no \lemma-command, so there is no need to mark it.

Here, the corresponding code:

```
\edtext{%
  \edtext{%
    \sameword[inlemma]{A} (1)
    \edtext{%
      \sameword{A} (2)
    }%
  }%
  \Afootnote{level~3}%
}%
\sameword[2]{A} (3)
}%
\lemma{%
  \sameword{A}%
  \ldots%
  \sameword{A}%
}%
\Afootnote{level~2}%
}%
\sameword{A} (4)
\sameword[1]{A} (5)
}%
\lemma{\sameword{A}\ldots\sameword{A}}%
\Afootnote{level~1}%
}
```

1	A (1) A (2) A (3) A (4) A (5)
	—————
	1 A ¹ ...A ⁵] level 1
	1 A ¹ ...A ³] level 2
	1 A ² (2)] level 3

6.3.5 Sameword for a group of words

Sometimes a group of words and not only a single word, occurs multiple times. In this case, you have two possibilities.

First, you can consider only the individual words, and not groups of word. For example:

```
\sameword{per} \sameword{causam}
tamen scire
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
est
```

```
\edtext{\sameword{per} \sameword{causam}}{\Bfootnote{causam rei B}}
cognoscere
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
```

1 per causam tamen scire causam est per causam cognoscere causam

1 causam²] fnote
 1 per² causam³] causam rei B
 1 causam⁴] fnote

In this case it is clear which “per causam” is meant.

However, in the case that “per causam” is the lemma of the second note, there should be only one number for that whole lemma. In this case we can mark all “per causam” groups. But as “causam” is also called as lemma in note 1 and 3, we need to use nested \sameword commands. Consequently, we need to use \lemma for the \edtext linked to “per causam”, as we don’t want to number each individual word.

```
\sameword{per \sameword{causam}} tamen scire
\edtext{\sameword{causam}}{\Bfootnote{fnote}} est
\edtext{\sameword[1]{per \sameword{causam}}}{\lemma{\sameword{per causam}}}\Bfootnote{causam}
\edtext{\sameword{causam}}{\Bfootnote{fnote}}
```

1 per causam tamen scire causam est per causam cognoscere causam

1 causam²] fnote
 1 per causam²] causam rei B
 1 causam⁴] fnote

6.3.6 Customizing

`\showwordrank` You can redefine the \showwordrank macro to change the way the number is printed. The default value is

```
\newcommand{\showwordrank}[2]{%
  #1\textsuperscript{#2}%
}
```

6.3.7 Problems with some macros

`\swnoexpands` Macros inside \sameword that are not fully expandable, mainly macros which manipulate font features, write on full or have optional argument, may cause problems during compilation. Custom commands inside \sameword may therefore result in errors saying that “Use of sameword doesn’t match its definition.” To solve this, include a redefinition of your custom commands in the \swnoexpands macro. In order to not include any content of a macro during comparison, identify the command with \gobble. For example:

```
\makeatletter
\appto{\swnoexpands}{%
  \let\somemacro\gobble%
}
\makeatother
```

This will drop the content of `\somemacro` during comparison.

To include the content of the first and only one argument of a custom command in sameword comparison, use the `\@firstofone` command. For example, this is how `\emph` is handled:

```
\makeatletter
\appto{\swnoexpands}{%
  \let\emph\@firstofone%
}
\makeatother
```

To include command which can take optional argument, use `\RenewExpandableDocumentCommand` of `\xparse`. For example, this is how `\edindex` is handled:

```
\makeatletter
\appto{\swnoexpands}{%
  \RenewExpandableDocumentCommand{\edindex}{om}{}%
}
\makeatother
```

6.3.8 Automatic sameword annotation

All potentially ambiguous apparatus entries must be annotated manually. That annotation process is laborious and includes a risk of errors. *Samewords* is a Python script that can automate this step of the process. It can be installed via the *Python Package Index*, but see <https://github.com/stenskjaer/samewords> for more info and documentation. The script is still at a beta stage, so comments and questions as well as error reports are very welcome at <https://github.com/stenskjaer/samewords/issues>.

Please note that the maintainer of this script is not identical with the maintainer of `reledmac`.

6.4 Apparatus of manuscripts

The critical notes mostly refer to textual variants between manuscripts which contain the text to be edited. It may so happen that the manuscripts only contain parts of the text. Depending on one's wishes, `reledmac` can generate lists of relevant manuscripts for any delimited portion of text. Such lists are referred to as "apparatuses of manuscripts".

To produce an apparatus of manuscripts with `reledmac`, you have to insert specific commands that are used to mark the sections for which only part of the manuscripts

are relevant. These commands will be processed, and **after the second TeX run**, corresponding apparatuses of manuscripts will be inserted in the first (viz. 'A' series) level of footnotes.

As the insertion of this apparatus can change the page breaks, you may have to run TeX two or more times. We strongly recommend to use tools like *latexmk* to do that.

6.4.1 Marking sections of text

`\msdata` `\msdata{\langle text\rangle}` must be inserted at the point where a section for which only part of the manuscripts are relevant starts. `\langle text\rangle` can be any arbitrary text, viz. a list of the manuscripts that are used for the section that starts. The command must be attached right at the point where the section starts, with no space, like so:

```
\msdata{ABC}Lorem ipsum
```

Which means that the section of text starting by “Lorem ipsum” is witnessed by manuscripts A, B and C.

`\stopmsdata` `\stopmsdata` must be inserted at the point where the section of text previously marked by `\msdata` ends. The command must be attached right to the end of the section, with no space. As `\stopmsdata` is a L^AT_EX argumentless macro, it will gobble the following space. To keep that space, you have to either append a backslash followed by a space or {} to `\stopmsdata`, like so:

```
\msdata{ABC}Lorem ipsum dolor
[...]
amet\stopmsdata{} \msdata{ABCD}sic transit [...]
```

Which means that the part of text containing “Lorem ipsum dolor [...] amet” is witnessed by manuscripts A, B and C, while the part of text starting by “sic transit” is witnessed by manuscripts A, B, C and D.

`\stopmsdata` is also automatically inserted by `\msdata`.

Note that in most cases, any `\stopmsdata` is followed by `\msdata`. However, as these two command are usually separated by a space, it may happen that a line break be automatically inserted between them. This is why it is advised to always insert `\stopmsdata`, even if `\msdata` inserts it in case it is forgotten.

6.4.2 Layout of the apparatus of manuscripts

On every page, the apparatus of manuscripts marks the corresponding section with starting and ending line numbers. However, the following rules will be applied:

- If the section does not start on the current page, the starting line number will be the line number of the first line on the page.
- If the section does not stop on the current page, the ending line number will be the line number of the last line on the page.

- If the section neither starts nor ends on the current page, no line number will be printed. The same is true in case both `\msdata` is called at the very beginning of the page and `\endmsdata` is called at the very end of the page.

6.4.3 Settings

As the apparatus of manuscripts technically consists of first-level critical notes ('A' series), any setting available for critical notes can be applied (7 p. 38). However, the following *additional* commands are available.

`\setmsdataseries`

`\setmsdatalabel`

`\setmsdataposition`

The series used by default for the apparatus of manuscripts is series A. However, you can change it with `\setmsdataseries{<series>}`.

As the apparatus of manuscripts consists of regular critical footnotes, a lemma is associated to them. By default, it is "Ms.". You can change it using `\setmsdatalabel{<txt>}`.

If you want the manuscript apparatus to be on the same level of critical footnotes as the other apparatuses, for each line, reledmac will first insert the manuscript apparatus, then the other footnotes. You can change it using:

`\msdataposition{regular-msdata}`

And restore the default behaviour using `\msdataposition{msdata-regular}`

6.5 Familiar notes

6.5.1 Basic use

`\footnoteA`
`\footnoteB`
`\footnoteC`
`\footnoteD`
`\footnoteE`

As well as the standard L^AT_EX footnotes generated via `\footnote`, the package also provides five series of additional footnotes called `\footnoteA` through `\footnoteE`. These have the familiar marker in the text, and the marked text at the foot of the page can be formated using any of the styles described for the critical footnotes. Note that the 'regular' footnotes have the series letter at the end of the macro name whereas the critical footnotes have the series letter at the start of the name.

6.5.2 Customizing mark

`\thefootnoteA`
`\bodyfootmarkA`
`\footfootmarkA`

Each series uses a set of macros for styling the marks. The mark numbering scheme of series A is defined by the `\thefootnoteA` macro; the default is:

`\renewcommand*{\thefootnoteA}{\arabic{footnoteA}}`

The appearance of the mark in the text is controlled by `\bodyfootmarkA` which is defined as:

`\newcommand*{\bodyfootmarkA}{%`
`\hbox{\textsuperscript{\normalfont\@nameuse{@thefnmarkA}}}}`

The command `\footfootmarkA` controls the appearance of the mark at the start of the footnote text. It is defined as:

`\newcommand*{\footfootmarkA}{\textsuperscript{\@nameuse{@thefnmarkA}}}`

There are similar command triples for the other series.

6.5.3 Separator for multiple footnotes

The `footmisc` package [Fai03] by Robin Fairbairns has an option whereby sequential footnote marks in the text can be separated by commas^{3,4} like so. As a convenience `reledmac` provides this automatically.

`\multfootsep`

`\multfootsep` is used as the separator between footnote markers. Its default definition is:

```
\providecommand*\multfootsep{\textsuperscript{\normalfont,}}
```

and can be changed if necessary.

6.6 Printing the footnote mark without printing the footnote text

`\footnoteXmark`
`\footnoteXtext`

In certain cases, you can't directly use `\footnoteX`; for example, when using `\uline` command of the `ulem` package. You need to print the footnote mark first, then call the footnote text to be inserted.

For all $\langle X \rangle$ command, `reledmac` provides a `\footnoteXmark` command and a `\footnoteXtext` command, equivalent to standard L^AT_EX's command `\footnotemark` and `\footnotetext`. For example, to use with `\uline`, do:

```
This is \uline{a test containing\mbox{\footnoteAmark}}\footnoteAtext{A simple footnote.}\uline{ a simple footnote.}
```

If you use `reledpar`, you can't use these two commands to print the footnote mark on one side and the footnote text on the other side.

You must use `\footnoteXnomk` and `\footnoteXmk`, defined in `reledpar` (?? p. ??)

6.7 Changing series

6.7.1 Create a new series

If you need more than five series of critical footnotes, you can create extra series, using `\newseries` command. For example, to create F and G series `\newseries{G,H}`.

6.7.2 Delete series

As the number of series which are defined increases, `reledmac` gets slower. If you do not need all of the six standard series (A–E), you can load the package with the `series` option. For example, if you need only series A and B, use:

```
\usepackage[series={A,B}]{reledmac}
```

6.7.3 Series order

The default series order is the one called with the `series` option of the package, or, if this option is not used, A, B, C, D, E. Series order determines footnotes order.

`\seriesatbegin` However in some specific cases, you need to change the series order at some point
`\seriesatend` inside the document. You can use `\seriesatbegin{⟨s⟩}` to pull up a given series ⟨s⟩ to the beginning, or `\seriesatend{⟨s⟩}` to push it down to the end.

6.8 Position of critical and familiar footnotes

`\fnpos` There is a historical incoherence in (r)(e)ledmac. The familiar footnotes are before the critical footnotes in a normal page, but after in a minipage or in a ledgroup. However, it is possible to change the relative position of both types of footnotes. If you want to have familiar footnotes after critical footnotes in a normal page, use:

```
\fnpos{critical-familiar}
```

Or, if you want a minipage or ledgroup to have critical footnotes after familiar footnotes, use:

```
\mpfnpos{familiar-critical}
```

You can also decide to alternate familiar and critical footnotes with your own order. In this case, the second argument of `\fnpos` or `\mpfnpos` is a comma-separated list of values. Each value has the following form:

`⟨series⟩⟨type⟩`

`⟨series⟩` is a series letter (A,B,C etc.), while `⟨type⟩` must be either “critical” or “familiar”.

For example, suppose you want to first print the familiar footnotes of the “A” series, then all the series of critical footnotes, and finally all the series of familiar footnotes, except the “A” series. In this case, use the following command:

```
\fnpos{%
  {A}{familiar},
  {A}{critical},%
  {B}{critical},%
  {C}{critical},%
  {D}{critical},%
  {E}{critical},%
  {B}{familiar},%
  {C}{familiar},%
  {D}{familiar},%
  {E}{familiar}%
}
```

Note that you must define the position of all the series of footnotes you use. If you don’t, you will have infinite runs of L^AT_EX.

7 Apparatus customization

Some commands can be used to change the display of the footnotes. All can have an optional argument [$\langle s \rangle$], which is the letter of the series – or a list of letters separated by comma – depending on which option is applied. If the optional argument is omitted or empty, the setting will apply to the entire series.

When a length, noted $\langle l \rangle$, is used, it can be stretchable: a plus b minus c . The final length m is calculated by L^AT_EX to have: $a - c \leq m \leq a + b$. If you use some relative unit¹⁷, it will be relative to font size of the footnote, except for commands concerning the place kept by the notes – including blank space.

Some commands are boolean, indicating when an option is enabled. If you want to disable the option after enabling it, you must use [false] as the second optional argument. For example:

- `\XX[A] [false]` to disable the ‘XX’ option for the series A.
- `\XX[] [false]` to disable it for all series.

There is also name convention:

- Names prefixed by X are for setting of critical footnotes.
- Names prefixed by Xend are for setting of critical endnotes.
- Names suffixed by X are for setting of familiar footnotes.

7.1 Notes arrangement in a series

`\Xarrangement` By default, all footnotes are formatted as a series of separate paragraphs in one column.
`\arrangementX` Three other formats are also available for notes.

Use `\Xarrangement[<s>]{<a>}` to change the arrangement of the $\langle s \rangle$ series of critical footnotes and `\arrangementX[<s>]{<a>}` to change the arrangement of the $\langle s \rangle$ series of familiar footnotes.

The value of $\langle a \rangle$ can be one of the following

- `paragraph` formats all of the footnotes of a series as a single paragraph; if you use this arrangement, you are strongly encouraged to read 19.1.6 p. 75.
- `twocol` formats them as separate paragraphs, but in two columns;
- `threecol`, in three columns.
- `normal`, restore normal arrangement.

You should set up the page layout parameters, and in particular the `\baselineskip` of the footnotes, before you call this macro because its action depends on these; too much or too little space will be allotted for the notes on the page if these macros use the wrong values.

¹⁷Like `em` which is the width of an ‘m’ in a given font.

Note that you *cannot* use paragraphs (e.g. blank lines or `\par`) or line breaks (`\break` or `\linebreak` or `\newline` etc.) inside of notes, when they are set to paragraph arrangement!

The notes arrangement must be called after having defined the document geometry setting. If you must change geometry setting inside your document, do not forget to call note arrangement again.

`\hsize` has been set for the pages that use this series of notes; otherwise TEX will try to put too many or too few of these notes on each page. If you need to change the `\hsize` within the document, call the arrangement macro again afterwards to take account of the new value.

7.2 Control line number printing

7.2.1 Print line number only at first time

By default, the line number is printed in every note. If you want to print it only the first time for a given line number (i.e., once for line 1, once for line 2, etc.), you can use `\Xnumberonlyfirstinline[⟨s⟩]`.

Suppose you have a lemma on line 2 and a lemma between line 2 and line 3. With `\Xnumberonlyfirstinline`, the second lemma is considered to be on the same line as the first lemma. But if you use both `\Xnumberonlyfirstinline[⟨s⟩]` and `\Xnumberonlyfirstintwolines[⟨s⟩]`, a distinction is made.

For setting a particular symbol in place of the line number, you can use `\Xsymlinenum[⟨s⟩]{⟨symbol⟩}` in combination with `\Xnumberonlyfirstinline[⟨s⟩]`. From the second lemma of the same line, the symbol will be used instead of the line number. Note that any command called in `⟨symbol⟩` must be robust. Use `\robustify` to robustify a non-robust command.

For endnotes, `\Xendnumberonlyfirstinline`; `\Xendnumberonlyfirstintwolines` and `\Xendsymlinenum` are the equivalents of `\Xnumberonlyfirstinline`; `\Xnumberonlyfirstintwolines` and `\Xsymlinenum`.

7.2.2 Print page number only at first time

For endnotes, `reledmac` provides a mechanism for printing the page number only the first time it is seen. However, when a lemma spans over two pages, the line numbers are normally printed in the following pattern: starting page number - starting line number - ending page number - ending line number. It follows that what corresponds to the actual ‘page number’ may not be self-evident. So: `\Xendpagenumberonlyfirst[⟨s⟩]` can be called to ensure that the starting page number of a lemma be not printed if it is the same as the ending page number of the preceding lemma. You can use *additionally* one (and only one) of the following commands:

- `\Xendpagenumberonlyfirstifsingle[⟨s⟩]`: the first page number of the lemma will not be printed only if the following conditions are true:
 1. The starting page number of the lemma is the same as the ending page number of the preceding lemma.

2. The ending page number of the lemma is the same as the starting page number of the lemma.

In this case the ending page number will always be printed if it is different from the starting page number.

- `\Xendpagenumberonlyfirstintwo[⟨s⟩]`: both the starting page number and the ending page number of a lemma are not printed if they are both the same as the starting page number and the ending page number of the preceding lemma respectively.

In any case, you can use:

`\Xendsympagenum`

`\Xendinplaceofpagenumber`

- `\Xendsympagenum[⟨series⟩]{⟨c⟩}` to print `⟨c⟩` when the page number is not printed.
- `\Xendinplaceofpagenumber[⟨series⟩]{⟨l⟩}` to print a `⟨l⟩` length horizontal space in case no symbol is printed instead of the page number.

7.2.3 Arbitrary text before line number

`\Xbeforenumber`

`\Xbeforenumber[⟨s⟩]{⟨txt⟩}` allows the insertion of `⟨txt⟩` before the line number only when the line number is printed, so taking into account `\Xnumberonlyfirstinline` and the like.

`\Xendbeforepagenumber`

For endnotes `\Xendbeforepagenumber[⟨s⟩]{⟨text⟩}` defines the text before the page number in endnotes. Default value is p. (“p” followed by a dot).

`\Xendafterpagenumber`
`\Xendlineprefixsingle`

`\Xendafterpagenumber[⟨s⟩]{⟨text⟩}` defines the text after the page number in endnotes. Default value is) (open parenthesis followed by a single space). `\Xendlineprefixsingle[⟨s⟩]` defines the text before the line number in endnotes when there is only one line. Default value is empty. `\Xendlineprefixmore[⟨s⟩]{⟨text⟩}` defines the text before the line number in endnotes when there is more than one line. Default value is empty. If you don’t define it, it will use the value defined by `\Xendlineprefixsingle`.

`\Xendlineprefixmore`

7.2.4 Separator for line range

`\Xlinerangeseparator`
`\Xendlinerangeseparator`

By default, the separator between the begin line and the end line in a lines’ range is an en-dash in a normal font (`\textnormal{--}`). You can change it for critical footnotes with `\Xlinerangeseparator[⟨s⟩]{⟨text⟩}`, and with `\Xendlinerangeseparator[⟨s⟩]{⟨text⟩}` for critical endnotes.

7.2.5 Abbreviate line range

`\Xtwolines`
`\Morethantwolines`

If a lemma is printed on two subsequent lines, `reledmac` will print the first and the last line numbers. Instead of this, it is also possible to print an abbreviation which stands for “line 1 and subsequent line(s)”.

To achieve this, use `\Xtwolines[⟨s⟩]{⟨text⟩}` and `\Morethantwolines[⟨s⟩]{⟨text⟩}`. The `⟨text⟩` argument of `\Xtwolines` will be printed if the lemma is on two lines, and

the $\langle text \rangle$ argument of `\Xmorethanwolines` will be printed if the lemma is on three or more lines. For example:

```
\Xtwolines{sq.}
\Xmorethanwolines{sqq.}
```

will print “1sq.” for a lemma which falls on lines 1–2 and “1sqq.” for a lemma which falls on lines 1–4.

If you use `\Xtwolines` without setting `\Xmorethanwolines`, the $\langle text \rangle$ argument of `\Xtwolines` will be used for lemmas which fall on three or more lines.

However, if you want to use a short form (when the lemma overlaps two lines, but not more than two), use `\Xtwolinesbutnotmore[⟨series⟩]`.

When you use lineation by page, the final page number, if different from the initial page number, will not be printed, because the final page number is included in the `\Xendtwolines` symbol.

However, you can force print the final page number with `\Xtwolinesonlyinsamepage[⟨series⟩]`.

You can disable `\Xtwolines` and related for a specific note by using the ‘`[fulllines]`’ argument in the note macro cf. 6.2.2 p. 25.

For endnotes, use these macros: `\Xendtwolines`; `\Xendmorethanwolines`; `\Xendtwolinesbutnotmore`; `\Xendtwolinesonlyinsamepage` instead of `\Xtwolines`; `\Xmorethanwolines`; `\Xtwolinesbutnotmore`; `\Xtwolinesonlyinsamepage`.

7.2.6 Disable line number

`\Xnonumber` You can use `\Xnonumber[⟨s⟩]` if you do not want to have the line number in a footnote.
`\Xendnonumber` `\Xendnonumber[⟨s⟩]` is the same for endnote.

7.2.7 Printing pstart number

`\Xpstart` You can use `\Xpstart[⟨s⟩]` if you want to print the pstart number in the footnote, before the line and subline number. Note that when you change the lineation system, the option is automatically switched :

- If you use lineation by pstart, the option is enabled.
- If you use lineation by section or by page, the option is disabled.

`\Xpstarteverytime` By default, the pstart number is printed only in the part of text where you have called `\numberpstarttrue`. We don’t know why you would like to print the pstart number in the notes and not in the main text. However, if you want to do it, you can call `\Xpstarteverytime[⟨s⟩]`. In this case, the pstart number will be printed every time in footnote.

`\Xonlypstart` In combination with `\Xpstart`, you can use `\Xonlypstart[⟨s⟩]` if you want to print only the pstart number in the footnote, and not the line and subline number.

7.2.8 Printing stanza number

`\Xstanza` You can use `\Xstanza[⟨s⟩]` if you want to print the stanza number in the footnote, before the line and subline number.

Of course the stanza number is printed only when you use `\numberstanza`

`\Xstanzaseparator` When using `\Xstanza`, you can use `\Xstanzaseparator[⟨s⟩]{⟨text⟩}` to print `⟨text⟩` after the stanza number. Default value is empty.

7.2.9 Separator between line and subline numbers

`\Xsublinesep` `\Xsublinesep[⟨s⟩]{⟨txt⟩}` changes the separator between line and subline in footnotes.

Employed without optional argument, it also changes the separator in side numbering.

`\Xendsublinesep[⟨s⟩]{⟨txt⟩}` does the same thing for endnotes.

However, it does not change anything for the separator in side numbering. Use `\Xsublinesep` without optional argument or `\Xsublinesepside{⟨txt⟩}` to do it.

The default value is `\textnormal{.}`.

7.2.10 Separator between page and line numbers

`\Xpagelinesep` `\Xpagelinesep[⟨s⟩]{⟨txt⟩}` changes the separator between the page and line number in footnotes.

By default, the value defined for `\Xsublinesep` is used.

7.2.11 Space around number

`\Xbeforenumber` With `\Xbeforenumber[⟨s⟩]{⟨l⟩}`, you can add some space before the line number in a footnote. If the line number is not printed, the space is not either. The default value is 0 pt.

`\Xafternumber` With `\Xafternumber[⟨s⟩]{⟨l⟩}` you can add some space after the line number in a footnote. If the line number is not printed, neither is the space. The default value is 0.5 em.

`\Xendbeforenumber` and `\Xendafternumber` are the equivalents of `\Xbeforenumber` and `\Xafternumber` for endnotes.

By default, the space defined by `\Xafternumber` is breakable. With `\Xnonbreakableafternumber[⟨s⟩]` it becomes nonbreakable.

7.2.12 Space around line symbol

`\Xbeforesymlinenum` With `\Xbeforesymlinenum[⟨s⟩]{⟨l⟩}` you can add some space before the line symbol in a footnote. The default value is value set by `\Xbeforenumber`.

`\Xaftersymlinenum` With `\Xaftersymlinenum[⟨s⟩]{⟨l⟩}` you can add some space after the line symbol in a footnote. The default value is value set by `\Xafternumber`.

`\Xendbeforesymlinenum` and `\Xendaftersymlinenum` are the equivalents of

`\Xnonbreakableafternumber` and `\Xnonbreakablebeforenumber` for endnotes.

\Xbeforesymlinenum and \Xaftersymlinenum for the endnotes.

7.2.13 Space in place of number

\Xinplaceofnumber If no number or symbolic line number is printed, you can add a space, with \Xinplaceofnumber[⟨s⟩]{⟨l⟩}.

The default value is 1 em.

\Xendinplaceofnumber[⟨s⟩]{⟨l⟩} is the same, for critical endnotes.

7.2.14 Boxing line number and line symbol

\Xboxlinenum It could be useful to put the line number inside a fixed box: the content of the note will be printed after this box. You can use \Xboxlinenum[⟨s⟩]{⟨l⟩} to do that. To subsequently disable this feature, use \Xboxlinenum with length equal to 0 pt. One use of this feature is to print line number in a column, and the note in an other column:

```
\Xhangindent{1em}
\Xafternumber{0em}
\Xboxlinenum{1em}
```

\Xboxsymlinenum \Xboxsymlinenum[⟨s⟩]{⟨l⟩} is the same as \Xboxlinenum but for the line number symbol.

\Xendboxsymlinenum \Xendboxsymlinenum[⟨s⟩]{⟨l⟩} is the same as \Xboxsymlinenum but for endnotes.

\Xboxlinenumalign If you put line number in box, it will be aligned left inside the box. However, you can change it using \Xboxlinenumalign[⟨s⟩]{⟨text⟩} where ⟨text⟩ can be the following:

L to align left (default value);

R to align right;

C to center.

When using \Xboxlinenum, reledmac put all the line number description in the same box. That is, the same box will contain: the start line number, the dash, and either the end line number or the range symbol (like ff.). However, it is possible to box them in two different boxes.

- \Xboxstartlinenum[⟨s⟩]{⟨l⟩} will box the start line number in a box of length ⟨l⟩. The content will be put at the right of the box.
- \Xboxendlinenum[⟨s⟩]{⟨l⟩} will box the dash plus the end line number or the range symbol in a box of length ⟨l⟩. The content will be put at the left of the box.

With these two commands, it is possible to horizontally align the dash of line number when using critical notes, to obtain something like:

```
1
12-23
24ff.
```

\Xendboxlinenum
 \Xendboxlinenumalign
 \Xendboxstartlinenumalign
 \Xendboxendlinenumalign

\Xendboxlinenum[$\langle s \rangle$]{ $\langle l \rangle$ }, \Xendboxlinenumalign[$\langle s \rangle$]{ $\langle text \rangle$ }, \Xendboxstartlinenum[$\langle s \rangle$]{ $\langle l \rangle$ } and \Xendboxendlinenum[$\langle s \rangle$]{ $\langle l \rangle$ } are the same as, respectively, \Xboxlinenum and \Xboxlinenumalign, \Xboxstartlinenum, \Xboxendlinenum except in endnotes.

7.3 Arbitrary code around line number

\Xendbhooklinenumber
 \Xendahooklinenumber
 \Xendbhookinplaceofnumber
 \Xendahookinplaceofnumber

\Xendbhooklinenumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code before line numbers in endnotes. The code is executed before the \Xendbeforelinenumber space and before the \Xendnotenumfont font setting.

\Xendahooklinenumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code after line number in endnotes. The code is executed after the \Xendafternumber space.

\Xendbhookinplaceofnumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code before space or symbol which replace line number in endnotes. The code is executed before the \Xendbeforesymlinenum space and before the \Xendnotenumfont font setting.

\Xendahookinplaceofnumber[$\langle s \rangle$]{ $\langle code \rangle$ } is used to execute code after space or symbol which replace line number in endnotes. The code is executed after the \Xendaftersymlinenum space.

7.4 Separator between the lemma and the note

7.4.1 For footnotes

\Xlemmaseparator
 \Xbeforelemmaseparator
 \Xafterlemmaseparator
 \Xnolemmaseparator
 \Xinplaceoflemmaseparator

By default, in a footnote, the separator between the lemma and the note is a right bracket (\rbracket)¹⁸. You can use \Xlemmaseparator[$\langle s \rangle$]{ $\langle Xlemmaseparator \rangle$ } to change it. The optional argument can be used to specify the series in which it is used. Note that there is a non-breakable space between the lemma and the separator, but a **breakable** space between the separator and the following text.

Using \Xbeforelemmaseparator[$\langle s \rangle$]{ $\langle l \rangle$ } you can add some space between lemma and separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

Using \Xafterlemmaseparator[$\langle s \rangle$]{ $\langle l \rangle$ } you can add some space between separator and note. If your lemma separator is empty, this space will not be printed. The default value is 0.5 em.

You can suppress the lemma separator, using \Xnolemmaseparator[$\langle s \rangle$], which is simply a alias of \Xlemmaseparator[$\langle s \rangle$]{ $\langle \rangle$ }.

With \Xinplaceoflemmaseparator[$\langle s \rangle$]{ $\langle l \rangle$ } you can add a space if no lemma separator is printed. The default value is 1 em.

7.4.2 For endnotes

\Xendlemmaseparator

By default, there is no separator inside endnotes between the lemma and the content of the note. You can use \Xendlemmaseparator[$\langle s \rangle$]{ $\langle Xendlemmaseparator \rangle$ } to change this. The optional argument can be used to specify the series in which it is used. A common value of $\langle Xendlemmaseparator \rangle$ is \lbracket.

¹⁸For *polyglossia*, when the lemma is RTL, the bracket automatically switches to a left bracket.

Note that there is a non-breakable space between the lemma and the separator, but a **breakable** space between the separator and the following text.

Using `\Xendbeforelemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between the lemma and the separator. If your lemma separator is empty, this space won't be printed. The default value is 0 em.

Using `\Xendafterlemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space between the separator and the content of the note. If your lemma separator is empty, this space won't be printed. The default value is 0.5 em.

With `\Xendinplaceoflemmaseparator[⟨s⟩]{⟨l⟩}` you can add some space if you choose to remove the lemma separator. The default value is 0.5 em.

7.5 Font style

7.5.1 For line number

`\Xnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes ; `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\Xendnotenumfont[⟨s⟩]{⟨command⟩}` is used to change the font style for line numbers in critical footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

`\notenumfontX[⟨s⟩]{⟨command⟩}` is used to change the font style for note numbers in familiar footnotes. `⟨command⟩` must be one (or more) switching command, like `\bfseries`.

7.5.2 For the lemma

By default, font of the lemma in footnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The `\Xlemmadisablefontselection[⟨s⟩]` command allows to disable it for a specific series.

By default, font of the lemma in endnote is the same as font of the lemma in the main text. For example, if the lemma is in italic in the main text, it is also in italic in note. The command allows `\Xendlemmadisablefontselection[⟨s⟩]` to disable it for a specific series.

Use `\Xlemmafont[⟨s⟩]{⟨cmd⟩}` to apply a TeX font command to the lemma. For example, to have boldface lemma:

```
\Xlemmafont{\bfseries}
```

`\Xendlemmafont[⟨s⟩]{⟨cmd⟩}` is the same for endnotes.

7.5.3 For all notes

`\Xnotefontsize[⟨s⟩]{⟨command⟩}` is used to define the font size of critical footnotes of the series. The default value is `\footnotesize`. The `⟨command⟩` must not be a size in pt, but a standard L^ET_EX size, like `\small`.

```
\notefontsizeX[⟨s⟩]{⟨command⟩} is used to define the font size of familiar footnotes of the series. The default value is \footnotesize. The ⟨command⟩ must not be a size in pt, but a standard LATEX size, like \small.  

\Xendnotefontsize
```

\Xendnotefontsize[⟨s⟩]{⟨l⟩} is used to define the font size of end critical footnotes of the series. The default value is \footnotesize. The ⟨command⟩ must not be a size in pt, but a standard L^AT_EX size, like \small.

7.6 Wrapping notes

7.6.1 Wrapping lemmas

```
\Xwraplemma[⟨s⟩]{⟨cmd⟩} is used to wrap, in the footnote, the lemma in a LATEX command. For example, with the bidi package, to ensure having a lemma written right to left, use \Xwraplemma{\RL}.  

\Xendwraplemma[⟨s⟩]{⟨cmd⟩} is the same for endnotes.
```

7.6.2 Wrapping contents

```
\Xwrapcontent[⟨s⟩]{⟨cmd⟩} is used to wrap the footnote contents — excluding the lemma — in a LATEX command.  

For example, if the language of your note is not the same as the language of the lemma, use \Xwrapcontent{\foreignlanguage{⟨language⟩}} (with babel) or \Xwrapcontent{\text{⟨language⟩}} (for babel).  

\Xendwrapcontent[⟨s⟩]{⟨cmd⟩} is the same for endnotes.  

\wrapcontentX[⟨s⟩]{⟨cmd⟩} is the same for familiar footnotes.
```

7.7 Indent of notes content

```
\Xparindent By default, reledmac does not add indentation before the paragraphs inside critical footnotes. Use \Xparindent[⟨s⟩] to enable indentation.  

\parindentX By default, reledmac does not add indentation before the paragraphs inside familiar footnotes. Use \parindentX[⟨s⟩] to enable indentation.  

\Xhangindent For critical notes NOT paragraphed you can define an indent with \Xhangindent[⟨s⟩]{⟨l⟩}, which will be applied in the second line of notes. It can help to make distinction between a new note and a break in a note. The default value is 0 pt.  

\hangindentX For familiar notes NOT paragraphed you can define an indentation with \hangindentX[⟨s⟩]{⟨l⟩}, which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.  

\Xendhangindent For critical endnotes NOT paragraphed you can define an indentation with \Xendhangindent[⟨s⟩]{⟨l⟩}, which will be applied in the second line of notes. It can help to make a distinction between a new note and a break in a note.
```

7.8 Arbitrary code at the beginning of notes

The three next commands add arbitrary code at the beginning of notes. As the name's space is local to the notes, you can use it to redefine some style inside the notes. For

example, if you don't want the pstart number to be in bold, use :

```
\Xbhooknote{\renewcommand{\thepstart}{\arabic{pstart}.}}
```

`\Xbhooknote` `\Xbhooknote[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each critical footnote.
`\bhooknoteX` `\bhooknoteX[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each familiar footnote.
`\Xendbhooknote` `\Xendbhooknote[⟨s⟩]{⟨code⟩}` is to be used at the beginning of each endnote.

7.9 Arbitrary code before inserting note

`\Xbeforeinserting` `\Xbeforeinserting[⟨s⟩]{⟨code⟩}` and `\beforeinsertingX` `\beforeinsertingX[⟨s⟩]{⟨code⟩}` are very technical commands.

They allow one to add any arbitrary code just before the footnotes are added in the list of footnotes. The main use is to insert text direction code. For example, if you edit right-to-left text with `bidi`, but want your critical footnote be left-to-right, use `\Xbeforeinserting\LTR`. You should also use `\Xwraplemma` to ensure your lemmas are right-to-left in a left-to-right paragraph (7.6.1 p. 46)).

Note that the changes are local to the footnote.

7.10 Options for footnotes in columns

7.10.1 Alignment

`\Xcolalign` `\colalignX` By default, text in footnotes of two or three columns are flush left and without hyphenation. However, you can change this with `\Xcolalign[⟨s⟩]{⟨code⟩}` for critical footnotes, and `\colalignX[⟨s⟩]{⟨code⟩}` for familiar footnotes.

`<code>` must be one of the following command:

`\justifying` to have text justified, as usual with L^AT_EX. You can also let `<code>` empty.

`\raggedright` to have text left aligned, but *without hyphenation*. That is the default `reledmac` setting.

`\RaggedRight` to have text left aligned *with hyphenation* (requires `ragged2e`).

`\raggedleft` to have text right aligned, but *without hyphenation*.

`\RaggedLeft` to have text right aligned *with hyphenation* (requires `ragged2e`).

`\centering` to have text centered, but *without hyphenation*.

`\Centering` to have text centered *with hyphenation* (requires `ragged2e`).

7.10.2 Size of the columns

For the following four macros, be careful that the columns are made from right to left.

`\Xhsizetwocol` `\hsizetwocol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical notes are displaying in two columns. Default value is `.45 \hspace`.

`\Xhsizethreecol` `\hsizethreecol[⟨s⟩]{⟨l⟩}` is used to change width of a column when critical

notes are displaying in three columns. Default value is `.3 \hsize`.

`\hsizetwocolX` `\hsizetwocolX[⟨s⟩]{⟨l⟩}` is used to change width of a column when familiar notes are displaying in two columns. Default value is `.45 \hsize`.
`\hsizethreecolX` `\hsizethreecolX[⟨s⟩]{⟨l⟩}` is used to change width of a column when familiar notes are displaying in three columns. Default value is `.3 \hsize`.

7.11 Options for paragraphed footnotes and notes grouped by line

7.11.1 Mark separation of notes

`\Xafternote` `\afternoteX` You can add some horizontal space after a note by using `\Xafternote[⟨s⟩]{⟨l⟩}` (for critical footnotes) or `\afternoteX[⟨s⟩]{⟨l⟩}` (for familiar footnotes). The default value is `1em plus .4em minus .4em`.

`\Xparafootsep` `\parafootsepX` For paragraphed footnotes (see below), you can choose the separator between each note by using `\Xparafootsep[⟨s⟩]{⟨text⟩}` for critical notes and `\parafootsepX` for familiar notes. A common separator is the double pipe (`||`), which you can set by using `\Xparafootsep{\parallel}`.

Note that if the symbol defined by `\Xsymlinenum` must be used at the beginning of a note, the `\Xparafootsep` / `\parafootsepX` is not used before this note.

7.11.2 Ragged text

`\Xragged` Text in paragraphed critical notes is justified, but you can use `\Xragged[⟨s⟩]{L}` if you want it to be ragged left (i.e., right justified), or `\Xragged[⟨s⟩]{R}` if you want it to be ragged right (i.e., left justified).

`\raggedX` Text in paragraphed footnotes is justified, but you can use `\raggedX[⟨s⟩]{L}` if you want it to be ragged left, or `\raggedX[⟨s⟩]{R}` if you want it to be ragged right.

7.12 Options for block of notes

7.12.1 Grouping notes by line

`\Xgroupbyline` If you do not use `\Xarrangement{paragraph}`, you may want to group all the critical footnotes related to the same line in the same paragraph. In this case, use `\Xgroupbyline[⟨series⟩]`.

In many cases, you might like to use it in combination with `\Xnumberonlyfirstinline` (7.2.1 p. 39).

Note that the `\Xafternote` and `\Xparafootsep` settings are used to determine space and content between footnotes (7.11 p. 48). Suppose you have two notes on line 1 which overlap lines 1 and 2. This last note will be printed, if you use `\Xgroupbyline` in the same group as the previous one. In the case you want that note to be distinct, you must use both `\Xgroupbyline` and `\Xgroupbylinesparetwolines[⟨s⟩]`.

In many cases, you might like to use it in combination with `\Xnumberonlyfirstintwolines` (7.2.1 p. 39)

7.12.2 Text before notes

- \Xtxtbeforenotes
 \txtbeforenotesX
 \Xendtxtbeforenotes
- \Xtxtbeforenotesonlyonce
 \txtbeforenotesonlyonceX
- You can add text before critical footnotes with \Xtxtbeforenotes[*s*]{*text*}.
 You can add text before familiar footnotes with \txtbeforenotesX[*s*]{*text*}.
 You can add text before endnotes with \Xendtxtbeforenotes[*s*]{*text*}. The text will be typeset only if there are endnotes.
 By default, such texts are inserted at the beginning of the groups of notes on each page. You can add \Xtxtbeforenotesonlyonce (for critical footnotes) and \txtbeforenotesonlyonceX (for familiar footnotes) to insert them only the first time notes are typeset.

7.12.3 Code before notes

- \Xbhookgroup
 \bhookgroupX
- While \Xtxtbeforenotes is for typesetting text before notes, \Xbhookgroup[*s*]{*code*} and \bhookgroupX[*s*]{*code*} (for critical and familiar respectively) are for executing code before a group of notes, between the rules and the printing of the notes.

7.12.4 Spacing

- \Xbeforenotes
 \beforenotesX
- \Xprenotes
 \prenotesX
- You can change the vertical space before the rule of the critical notes with \Xbeforenotes[*s*]{*l*}. The default value is 1.2em plus .6em minus .6em.
Be careful, the standard L^AT_EX footnote rule used by reledmac decreases by 3pt. This 3pt decrease is not changed by this command.
 You can change the vertical space printed before the rule of the familiar notes with \beforenotesX[*s*]{*l*}. The default value is 1.2em plus .6em minus .6em.
Be careful, the standard L^AT_EX footnote rule, which is used by reledmac, decreases 3pt. These 3pt are not changed by this command.
 You can set the space before the first series of critical notes printed on each page and set a different amount of space for each subsequent series on the page. You can do it with \Xprenotes{*l*}. The default value is 0pt. You can disable this feature by setting the length to 0pt.
 You can set the space before the first printed (in a page) series of familiar notes to be different from the space before other series. The default value is 0pt. You can do this with \prenotesX{*l*}. You can disable this feature by setting the length to 0pt.

7.12.5 Rule

- \Xafterrule
 \afterruleX
- You can change the vertical space printed after the rule of the critical notes with \Xafterrule[*s*]{*l*}. The default value is 0pt.
Be careful, the standard L^AT_EX footnote rule, which is used by reledmac, adds 2.6pt. These 2.6pt are not changed by this command.
 You can change the vertical space printed after the rule of the familiar notes with \afterruleX[*s*]{*l*}. The default value is 0pt.
Be careful, the standard L^AT_EX footnote rule, which is used by reledmac, adds 2.6pt. These 2.6pt are not changed by this command.

7.12.6 Maximum height

`\Xmaxhnotes`

By default, one series of critical notes can take up to 80% of `\vsize`, before being broken to the next page. If you want to change the size use `\Xmaxhnotes[⟨s⟩]{⟨l⟩}`. Be careful : the length can't be flexible, and is relative to the current font. For example, if you want the note to take, at most, 33% of the text height, do `\Xmaxhnotes{.33\textheight}`.

`\maxhnotesX`

`\maxhnotesX[⟨s⟩]{⟨l⟩}` is the same as previous, but for familiar footnotes.

Note that in many cases, you should call these commands in the begin of the document, because the `\vsize` in the preamble is not the same as `\vsize` after the preamble. That why we recommend to you to add in your preamble

```
\AtBeginDocument{
  \maxhnotesX{0.8\textheight}
  \Xmaxhnotes{0.8\textheight}
}
```

Be careful with the two previous commands. Actually, for technical purposes, one paragraphed note is considered as one block. Consequently, it cannot be broken between two pages, even if you used these commands. The debug is in the todolist.

7.12.7 Width

`\Xwidth` `\Xwidth[⟨s⟩]{⟨l⟩}` sets the total width of critical footnotes. `\widthX[⟨s⟩]{⟨l⟩}` does the same for familiar footnotes.

`⟨l⟩` can be a length expression, parsable with `\dimexpr`. For example:

```
\Xwidth{\columnwidth+\marginparsep+\ledrsnotewidth}
\widthX{\columnwidth+\marginparsep+\ledrsnotewidth}
```

Note that changes the width of the block of notes. If you want to change the width of each column when typesetting notes in columns, use `\Xsizetwocol`, `\Xsizethreecol`, `\hsizetwocolX`, `\hsizethreecolX`, see 7.10.2 p. 47.

7.13 Footnotes and the `reledpar` columns

`\Xnoteswidthliketwocolumns`
`\noteswidthliketwocolumnsX`

If you use `reledpar` `\columns` macro, you can call :

- `\Xnoteswidthliketwocolumns[⟨s⟩]` to create critical notes with a two-column size width.
- `\noteswidthliketwocolumnsX[⟨s⟩]` to create familiar notes with a two-column size width.

7.14 Line number annotation

The way line number annotations are typeset can be changed using hooks as described in 9.10.2 p. 57 and 9.10.3 p. 57.

7.15 Endnotes in one paragraph

- `\Xendparagraph` By default, any new endnote starts a new paragraph. Use `\Xendparagraph[⟨s⟩]` to have all end notes of one given series set in one paragraph.
- `\Xendafternote` You can add some space after a endnote series by using `\Xendafternote[⟨s⟩]{⟨l⟩}`. The default value is `1em plus .4em minus .4em`.
- `\Xendsep` You can choose the separator between each note by `\Xendsep[⟨s⟩]{⟨text⟩}`. A common separator is the double pipe (||), which you can set by using `\Xendsep{\parallel}`.

8 Fonts

One of the most important features of the appearance of the notes, and indeed of your whole document, will be the fonts used. We will first describe the commands that give you control over the use of fonts in the different structural elements of the document, especially within the notes, and then in subsequent sections specify how these commands are used.

- `\numlabfont` Line numbers for the main text are usually printed in a smaller font in the margin. The `\numlabfont` macro is provided as a standard name for that font: it is initially defined as
`\newcommand{\numlabfont}{\normalfont\scriptsize}`
 You might wish to use a different font if, for example, you preferred to have these line numbers printed using old-style numerals.
- `\select@lemmafont` We will briefly discuss `\select@lemmafont` here because it is important to know about it now, although it is not one of the macros you would expect to change in the course of a simple job. Hence it is ‘protected’ by having the @-sign in its name.

When you use the `\edtext` macro to mark a word in your text as a lemma, that word will normally be printed again in your apparatus. If the word in the text happens to be in a font such as italic or bold you would probably expect it to appear in the apparatus in the same font. This becomes an absolute necessity if the font is actually a different script, such as Arabic or Cyrillic. `\select@lemmafont` does the work of decoding `reledmac`’s data about the fonts used to print the lemma in the main text and calling up those fonts for printing the lemma in the note.

`\select@lemmafont` is a macro that takes one long argument—the cluster of line numbers passed to the note commands. This cluster ends with a code indicating what fonts were in use at the start of the lemma. `\select@lemmafont` selects the appropriate font for the note using that font specifier.

`reledmac` uses `\select@lemmafont` in a standard footnote format macro called `\normalfootfmt`. The footnote formats for each of the layers A to E are `\let` equal to `\normalfootfmt`. So all the layers of the footnotes are formatted in the same way.

9 Verse

9.1 Basic

- `\stanza` Use `\stanza` at the start of a stanza. Each line in a stanza is ended by an ampersand (&),
`\&`

and the stanza itself is ended by putting `\&` at the end of the last line.

If you need to add brackets directly after `\stanza`, `&` or `\&`, add `\norelax`. Otherwise, the brackets will be interpreted as delimitation of an optional argument (cf. 9.8 p. 54)

9.2 Define stanza indents

`\stanzaindentbase`

Lines within a stanza may be indented. The indents are integer multiples of the length `\stanzaindentbase`, whose default value is 20pt.

`\setstanzaindents`

In order to use the stanza macros, **one must set the indentation values**. First the value of `\stanzaindentbase` should be set, unless the default value 20pt is desired. Every stanza line indentation is a multiple of this.

To specify these multiples one invokes, for example

`\setstanzaindents{3,1,2,1,2}.`

The numerical entries must be whole numbers, 0 or greater, separated by commas without embedded spaces. The first entry gives the hanging indentation to be used if the stanza line requires more than one print line.

If it is known that each stanza line will fit in one print line, then this first entry should be 0; TeX does less work in this case, but no harm ensues if the hanging indentation is not 0 but is never used.

If you want the hanging verse to be flush right, you can use `\sethangingsymbol`: see p. 9.6 p. 54.

Enumeration is by stanza lines, not by print lines. In the above example the lines are indented one unit, two units, one unit, two units, with 3 units of hanging indentation in case a stanza line is too long to fit on one print line.

9.3 Repeating stanza indents

Since version 0.13, if the indentation is repeated every n verses of the stanza, you can define only the n first indentations, and indicate that they are repeated, defining the value of the `stanzaindentsrepetition` counter at n . For example:

```
\setstanzaindents{5,1,0}
\setcounter{stanzaindentsrepetition}{2}
```

is like

```
\setstanzaindents{5,1,0,1,0,1,0,1,0,1,0}
```

Be careful: the feature is changed in eledmac 1.5.1. See Appendix A.3 p. 377.

If you don't use the `stanzaindentsrepetition` counter, make sure you have at least one more numerical entry in `\setstanzavalue`s than the number of lines in the stanza.

If you want to disable this feature again, just put the counter to 0:

```
\setcounter{stanzaindent}{0}
```

The macros make no restriction on the number of lines in a stanza. Stanza indentation values (and penalty values) obey T_EX's grouping conventions, so if one stanza among several has a different structure, its indentations (penalties) may be set within a group; the prior values will be restored when the group ends.

9.4 Manual stanza indent

`\stanzaindent` You can set the indent of some specific verse by calling `\stanzaindent{<value>}` at the beginning of the verse, before any other character. In this case, the indent defined by `\setstanzaindent` for this verse is skipped, and `{<value>}` is used instead.

If you use the mechanism of indent repetition, the next verse will be printed as it should be even if the current verse would have its normal indent value. In other words, using `\stanzaindent` in a verse does not shift the indent repetition.

However, if you want to shift the indent repetition, so the next verse has the indent normally used for the current verse, use `\stanzaindent*` instead of `\stanzaindent`.

9.5 Stanza breaking

`\setstanzapenalties` When the stanzas run over several pages, it is often desirable that page breaks should arise between certain lines in the stanza, so a facility for including penalties after stanza lines is provided. If you are satisfied with the page breaks, you need not set the penalty values.

The command
`\setstanzapenalties{1,5000,10100,5000,0}`
 results in a penalty of 5000 being placed after the first and third lines of the stanza, and a penalty of -100 after the second.

The first entry “1” is a control value. If it is zero, then no penalties are passed on to T_EX, which is the default. Values between 0 and 10000 are penalty values; values between 10001 and 20000 have 10000 subtracted and the result is given as a negative penalty. The mechanism used for indentations and penalties requires unsigned values less than 32768. No penalty is placed after the last line, so the final ,0 in the example above could be omitted. A penalty of 10000 will prevent a page break; such a penalty is included automatically where there is stanza hanging indentation. A penalty of -10000 (corresponding to the entry value 20000 in this context) forces a page break. Values in between act as suggestions as to the desirability of a page break at a given line. There is a subtle interaction between penalties and *glue*, so it may take some adjustment of skips and penalties to achieve the best results.

9.6 Hanging symbol

It is possible to insert a symbol in each line of hanging verse, as in French typography; for example, the opening bracket ‘[’. To insert it in `reledmac`, use macro `\sethangingsymbol{<h>}` with this code. In the example of French typography, do

```
\sethangingsymbol{[\,]}
```

You can also use it to force hanging verse to be flush right:

```
\sethangingsymbol{\protect\hfill}
```

9.7 Long verse and page break

If you want to prevent page breaks inside long verses, use the option `nopbinverse` when loading package, or use `\lednopbinversetrue`. Read 18.2 p. 73 for further details.

9.8 Content before/after verses

It is possible to add content, like a subtitle or a spacing, before or after verse:

- The `\stanza` command can take an optional argument (in brackets). Its content will be printed before the stanza. A `\noindent` is inserted before the content of first optional argument. If you don't want this `\noindent`, you can use the second optional argument (also in brackets):

```
\stanza[foo] % \noindent is inserted before foo.  
\stanza[] [foo] % There is no \noindent inserted before foo.
```

`\AtEveryStanza`

- Use `\AtEveryStanza{\<arg>}` to automatically add content before the stanza (not in the same paragraph).

Note that a `\noindent` will be inserted before the argument, and, consequently, a `\parskip`. You can use the starred version of `\AtEveryStanza` to avoid this `\noindent`.

`\AtStartEveryStanza`

- Use `\AtStartEveryStanza` to automatically add content at the beginning of stanza (in the same paragraph).

- `&` can be replaced by `\newverse` with two optional arguments (in brackets). The first will be printed after the current verse, the second before the next verse.

A `\noindent` is automatically inserted before the contents of these optional arguments.

Use a third and fourth optional argument to not add these `\noindents` (to add content respectively after the current verse / before the next verse).

- Use `\AtEveryPend{\<arg>}` to automatically add content after verses (including the final one) and `\AtEveryPstart{\<arg>}` to automatically add content before verses (including the first one).

- `\&` can take an optional argument (in brackets). Its content will be printed after the stanza.

\AtEveryStopStanza

- Use \AtEveryStopStanza to automatically add content after the end of stanzas (not in the same paragraph).

Note that a \noindent will be inserted before the argument, and, consequently, a \parskip. You can use the starred version of \AtEveryStopStanza to avoid this \noindent.

\AtStartEveryStanza

- Use \AtStartEveryStanza to automatically add content at the end of stanza (in the same paragraph).

9.9 Numbering stanza

\numberstanzatrue
\numberstanzafalse

If you want to automatically number stanzas, use \numberstanzatrue. In this case, the line number will restart at each \stanza.

If you want to disable this feature again, use \numberstanzafalse.

You can use this feature in combination with \Xstanza (7.2.8 p. 42).

\thestanza

You can redefine \thestanza to change the aspect of stanza number. Default value is:

```
\renewcommand{\thestanza}{%
  \textbf{\arabic{stanza}}%
```

You can change the value of the stanza counter with the usual commands of L^AT_EX.

\stanzанumwrapper

You can redefine \stanzанumwrapper in order to modify the way the stanza number is inserted in the flow of text. Default value is:

```
\newcommand{\stanzанumwrapper}[1]{%
  \flagstanza{#1}%
```

9.10 Adding annotations to line numbers

You may want to have two or more numbers associated with a line of verse. Consider, for example, the following cases:

- You want to split a line of verse into two parts depending upon some stylistic / rhythmic / linguistic convention.
- You want to add the line number used by a previous edition of the work.

In such instances, you must add the second number manually, as reledmac can't determine a general pattern for such numbering, which depends too heavily upon the edited text.¹⁹

\linenumannotation

To resolve this issue, reledmac allows you to annotate line numbers using the fol-

¹⁹However, you may create your own commands dealing with such patterns which will in turn call reledmac commands.

lowing command:

```
\linenumannotation{<annotation>}
```

The annotation can contain any textual value (whether number, text, or other) such as the line number from the older edition. Here are some characteristics of line number annotation:

- An annotation is associated with a line of verse. It is reset with each new line of verse.
- It is printed alongside the line number in the margin.
- It is printed following the line number in critical footnotes and endnotes.
- And of particular interest: the annotation is printed in the critical note *only* when the \edtext is issued after the \linenumannotation.
- If two or more annotations are called before na \edtext, the last one is used in associated notes.
- If an annotation is called within an \edtext, it is printed as an annotation for the end of the lemma.

Here is an example, supposing we are on line 1:

```
\edtext{first lemma}
\linenumannotation{A}
\edtext{second lemma}{...}
\edtext{third%
\linenumannotation{B}
lemma}{...}
\edtext{fourth lemma}&
```

In the critical notes, the line number will be followed

- by nothing in the first lemma, as there is no annotation for this line;
- by “A” for the second lemma;
- by “A-B” for the third lemma, as it starts while annotation A is still in effect and it finishes after annotation B has already taken effect;
- by “B” for the fourth lemma.

9.10.1 Modifying annotation associated with a specific note

`\lineannot` The `\linenum` (6.2.5 p. 27) macro changes the line number passed to a note. The `\lineannot` macro does the same for the annotations. It takes one argument, containing the beginning and ending annotations separated by a pipe (|). As with `\linenum`, if one wishes to change some specific part of the annotation, one can use

```
\lineannot{|b}|% to change the ending annotation
\lineannot{a|}|% to change the beginning annotation
\lineannot{a|b}|% to change both
\lineannot{\emptyset|}|% to delete the beginning annotation
```

9.10.2 Changing the position of the annotation

By default, annotations are placed after line numbers in both margin and footnote.

To change this behaviour, one can use one of the following commands:

- `\Xlinenumannotationposition[⟨s⟩]{⟨v⟩}` changes the position in critical footnotes with $⟨s⟩$ for the series of footnotes to which it applies, where $⟨s⟩$ may be a comma-separated list of series. When $⟨s⟩$ is empty, the change applies also to annotations at the sides of the page, alongside the line number.
 - `\Xlinenumannotationpositionsides{⟨v⟩}` changes the position at the sides of the page, alongside the line numbers.
- Note that `\Xlinenumannotationposition` without any optional argument will override this setting.
- `\Xendlinenumannotationposition[⟨s⟩]{⟨v⟩}` changes the position in critical endnotes, $⟨s⟩$ for the series of endnotes to which it applies, where $⟨s⟩$ may once again be a comma-separated list of series.

In each of these three commands, $⟨v⟩$ can be `after` or `before` to indicate position with regards to the line number.

9.10.3 Changing the macro in which annotations are wrapped

By default, annotations are wrapped in the `\textsuperscript` macro. You can modify this using one of the following:

- `\Xwraplinenumannotation[⟨s⟩]{⟨cmd⟩}` for critical footnotes; $⟨s⟩$ indicates the series of notes to which it applies and may be a comma-separated list of series. When $⟨s⟩$ is empty, the change applies to the annotations in the margins also—around the line number—as well as to the annotations referenced using the `\annotationref` command of the crossref mechanism (11 p. 59).
 - `\Xwraplinenumannotationsides{⟨cmd⟩}` for annotations in the margins only.
- Note that `\Xwraplinenumannotation` without any optional argument will override this setting.

- `\Xwraplinenumannotationref{<cmd>}` for annotations referenced using the `\annotationref` command of the crossref mechanism (11 p. 59).
Note that `\Xwraplinenumannotation` without any optional argument will override this setting.
- `\Xendwraplinenumannotation[<s>]{<cmd>}` for critical endnotes, where `<s>` indicates the series of notes to which it applies, which may be a comma-separated list.

`<cmd>` is a command which can take one argument; the backslash is required though.

For example, if you do not wish to have annotations in the margins, but do want to have them in bold in the critical footnotes and endnotes, you say:²⁰

```
\makeatletter
\Xwraplinenumannotation{\textbf}
\Xendwraplinenumannotation{\textbf}
\Xwraplinenumannotationside{\@gobble}
\makeatother
```

9.11 Various tools

`\ampersand`

If you need to print an & symbol in a stanza, use the `\ampersand` macro, not `\&` as this will end the stanza.

`\flagstanza`

Putting `\flagstanza[<len>]{<text>}` at the start of a line in a stanza (or elsewhere) will typeset `<text>` at a distance `<len>` before the line. The default `<len>` is `\stanzaindentbase`.

9.12 Notes on empty lines

Since v2.3.0 of `reledmac`, empty lines when typesetting verses no longer produce new paragraphs, and consequently, do not insert vertical spaces. Use optional argument of `\stanza` or `\newverse` to insert vertical space (9.8 p. 54).

10 Grouping

In a `minipage` environment `LATEX` changes `\footnote` numbering from arabic to alphabetic and puts the footnotes at the end of the `minipage`.

`minipage`

You can put numbered text with critical footnotes in a `minipage` and the footnotes are set at the end of the `minipage`.

You can also put familiar footnotes (see section 6.5) in a `minipage` but unlike with `\footnote` the numbering scheme is unaltered.

`ledgroup`

Minipages, of course, are not broken across pages. Footnotes in a `ledgroup` environment are typeset at the end of the environment, as with minipages, but the environment includes normal page breaks. The environment makes no change to the `textwidth`

²⁰The `\@gobble` command takes one argument, and returns nothing.

so it appears as normal text; it just might be that footnotes appear in the middle of a page, with text above and below.

`\ledgroupsized` The `\ledgroupsized` environment is similar to `\ledgroup` except that you must specify a width for the environment, as with a `minipage`.

`\begin{ledgroupsized}[\langle pos \rangle]{\langle width \rangle}`.

The required `\langle width \rangle` argument is the text width for the environment. The optional `\langle pos \rangle` argument is for positioning numbered text within the normal `textwidth`. It may be one of the characters:

`l` (left) numbered text is flush left with respect to the normal `textwidth`. This is the default.

`c` (center) numbered text is in the center of the `textwidth`.

`r` (right) numbered text is flush right with respect to the normal `textwidth`.

Note that normal text, footnotes, and so forth are all flush left.

`\begin{ledgroupsized}{\textwidth}` is effectively the same as `\begin{ledgroup}`

11 Cross referencing

The package provides a simple cross-referencing facility that allows you to mark places in the text with labels, and generate page and line number references to those places elsewhere using those labels.

11.1 Basic use

`\edlabel` First you place a label in the text using the command `\edlabel{\langle lab \rangle}`. `\langle lab \rangle` can be almost anything you like, including letters, numbers, punctuation, or a combination—anything but spaces; you might type `\edlabel{toves-3}`, for example.²¹

`\edpageref` Elsewhere in the text, either before or after the `\edlabel`, you can refer to its location with `\edpageref{\langle lab \rangle}`, `\edlineref{\langle lab \rangle}`, `\edsublineref{\langle lab \rangle}`, `\pstartref{\langle lab \rangle}` or `\annotref{\langle lab \rangle}`, that will produce, respectively, the page, line, sub-line, pstart, the annotation, on which the `\edlabel{\langle lab \rangle}` command occurred.

`\sublineref` Note that the `\edlineref` command insert the side flag after the line number.

`\pstartref` An `\edlabel` command may appear in the main text, or in the first argument of `\edtext`, but not in the apparatus itself. But `\edpageref`, `\edlineref`, `\sublineref`, `\pstartref` commands can also be used in the apparatus to refer to `\edlabels` in the text.

`\annotref` The `\edlabel` command works by writing macros to `LATEX.aux` file. You will need to process your document through `LATEX` twice in order for the references to be resolved.

You will be warned if you use `\edlabel{foo}` and `foo` has been used as a label before. The `ref` commands will return references to the last place in the file marked with this label. You will also be warned if a reference is made to an undefined label. (This will also happen the first time you process a document after adding a new `\edlabel` command: the auxiliary file will not have been updated yet.)

²¹More precisely, you should stick to characters in the `TEX` categories of “letter” and “other”.

11.2 Cross-referencing to a critical note

If you want to refer to a word which is a lemma word, the `\edlabel` command should be in the first argument of `\edtext` command.

If you want to refer to the content of a `\Xfootnote`, the line and subline number printed will be the start line.

If you want to refer to starting and ending lines, you should use `\appref` and related tools (11.6.2 p. 62).

11.3 Cross-referencing which return a number in any case

```
\xpageref
\xlineref
\xsublineref
\xpstartref
\xannotref
```

However, there are situations in which you will want `reledmac` to return a number without displaying any warning messages about undefined labels or the like: if you want to use the reference in a context where `LATEX` is looking for a number, such a warning will lead to a complaint that the number is missing. This is the case for references used within the argument to `\linenum`, for example (see 6.2.5 p. 27).

For this situation, `reledmac` supplies variants of the reference commands, with the `x` prefix: `\xpageref`, `\xlineref`, `\xsublineref`, `\xpstartref` and `\xannotationref`. They have the following limitations:

- They will not tell you if the label is undefined.
- They must be preceded in the file by at least one of the four other cross-reference commands—e.g., a `\edlabel{foo}` command, even if you never refer to that label—since those commands can all do the necessary processing of the `.aux` file, and the `\x...` ones cannot.
- When `hyperref` is loaded, the hyperref link will not be added. (Indeed, it is not a limitation, but a feature.)
- With `reledpar`, the `\xlineref` does not insert the right side flag, in order to obtain a line number. Use `\xflagref` to obtain the side flag, depending of your flag.

11.3.1 Cross-referencing in order to define line number of a critical note

```
\xxref
```

The `\xxref{\langle lab1 \rangle}{\langle lab2 \rangle}` command generates a reference to a sequence of lines, for use in the second argument of `\edtext`. It takes two arguments, both of which are labels: e.g., `\xxref{mouse}{elephant}`.

It automatically calls `\linenum` (6.2.5 p. 27) and `\lineannot` (?? p. ??) and sets the beginning page, line, subline numbers and line annotations to those of the place where `\edlabel{mouse}` was placed, and the ending ones to those where `\edlabel{elephant}` occurs.

For example, one might use the following:

```
\begin{numbering}
```

```
\pstart
\edlabel{Queritur}Queritur utrum metaphysica sit scientia una.
\pend

\pstart
\edtext{Et videtur quod non\edlabel{non}.}{\xxref{Queritur}{non}\lemma{queritur \dots{} non}\Afootnote{%
\pend

\endnumbering
```

11.4 Not automatic cross-referencing

\edmakelabel Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired—for example, if you want to refer to a page and line number in another volume of your edition. In such cases, you can use the `\edmakelabel{\langle lab\rangle}{\langle numbers\rangle}` macro so that you can ‘roll your own’ label.

For example, if you type ‘`\edmakelabel{elephant}{10|25|0}`’ you will create a new label, and a later call to `\edpageref{elephant}` would print ‘10’ and `\lineref{elephant}` would print ‘25’. The sub-line number here is zero. It is usually best to collect your `\edmakelabel` statements near the top of your document, so that you can see them at a glance.

11.5 Normal L^AT_EX cross-referencing

\label The normal `\label`, `\ref` and `\pageref` macros may be used within numbered text, and operate in the familiar fashion.
\ref

\pageref

11.6 References to start and end lines

11.6.1 Reference to main text lines

Many times, you may want to make a cross-reference to a passage that is defined by a start line and an end line. `reledmac` provides specific tools for this scenario.

\edlabelS Use `\edlabelS{\langle label\rangle}` to mark the start line of the passage.

\edlabelE Use `\edlabelE{\langle label\rangle}` to mark the end the end line of the passage. These two commands just create to label which are named `\langle label\rangle:start` and `\langle label\rangle:end`.

\edlabelSE Use `\edlabelSE{\langle label\rangle}` to mark just one location in the text. Contrary to a classical `\edlabel`, the `\langle label\rangle` could be use with `\Seref` and `\Serefwithpage`.

\Seref The main utility is to use them with three other commands. `\Seref{\langle label\rangle}` will make a cross-reference printed as a reference in critical footnotes.

\Serefwithpage `\Serefwithpage` will make a cross-reference printed as a reference in critical end-notes.

\Serefonlypage `\Serefonlypage` will make a cross-reference printed only with page number.

11.6.2 References to lines that are commented on in the apparatus

You may want to make a cross-reference to a passage that is referred to by \edtext. reledmac provides specific tools for this scenario.

\applabel

If you use \applabel{\langle label \rangle} inside the second argument of a \edtext, reledmac will add a \edlabel at the beginning and end of the marked passage. The label at the beginning of the passage will have the title \langle label \rangle : start, while the label at the end will have the title \langle label \rangle : end.

If you use \linenum (6.2.5 p. 27) to refer to these labels, reledmac will use your line settings to refer to the passage.

\appref
\apprefwithpage

You can also use \appref{\langle label \rangle} and \apprefwithpage{\langle label \rangle} to refer to these lines. The first one will print the lines as they are printed in the critical footnotes, while the second will print the lines as they are printed in endnotes.

11.6.3 Settings

\setapprefprefixsingle
\setapprefprefixmore

Specific to these tools If you use \apprefprefixsingle{\langle prefix \rangle}, \langle prefix \rangle will be printed before the line numbers of a \appref-reference. If you use \apprefprefixmore{\langle prefix \rangle}, \langle prefix \rangle will be printed before the line numbers, if you refer to more than one line.

For example, you may use:

```
\setapprefprefixsingle{line~}
\setapprefprefixmore{lines~}
```

Note that if you do not use \setapprefprefixmore, the argument of \setapprefprefixsingle will be used in any case.

\setSErefprefixsingle and \setSErefprefixmore are similar for \SEref command.

Use \setSErefonlypageprefixsingle{\langle prefix \rangle} to set the page prefix for \SErefonlypage when there is only one page. Use \setSErefonlypageprefixmore{\langle prefix \rangle} to set it when there is more than one page. For example:

```
\setSErefonlypageprefixsingle{p.~}
\setSErefonlypageprefixmore{pp.~}
```

Note that if you do not use \setSErefonlypageprefixmore, the value of \setSErefonlypageprefixsingle is used instead.

Also note that \setSErefonlypageprefixsingle is only a shortcut for \Xendbeforepagenumber (see 11.6.3 p. 62). So if you use \Xendbeforepagenumber without any optional argument, it will override this setting.

Linked to setting of critical footnotes and endnotes Some commands which set the appearance of line numbers in critical footnotes also set the appearance of line numbers in \appref and \SEref if called *without the optional series argument*.

These commands are the following:

- \Xlineflag (for reledpar), enabled by default.

- \Xlinerangeseparator
- \Xmorethanwolines
- \Xsublinesep
- \Xtwolines
- \Xtwolinesbutnotmore
- \Xtwolinesonlyinsamepage
- \Xlinenumannotationposition
- \Xwraplinenumannotation

If you want to make settings specific to \appref or \SEref, just call them with an optional argument containing a comma-separated list of command names (for example `appref,SEref`) or with a suffix equal to the command name (for example `appref`).

The same principle is available for \apprefwithpage, \SErefwithpage and \SErefonlypage with the following commands:

- \Xendafterpagenumber (not for \SErefonlypage)
- \Xendbeforepagenumber
- \Xendlineflag (for reledpar), enabled by default.
- \Xendlineprefixmore
- \Xendlineprefixsingle
- \Xendlinerangeseparator
- \Xendmorethanwolines
- \Xendsublinesep
- \Xendtwolines
- \Xendtwolinesbutnotmore
- \Xendtwolinesonlyinsamepage
- \Xendlinenumannotationposition
- \Xendwraplinenumannotation

For one specific command When calling \appref and \SEref, you can use as a first optional argument, in brackets ([]), any optional argument which can be used for critical footnotes (6.2.2 p. 25).

When calling \apprefwithpage, \SErefwithpage or \SErefonlypage you can use as a first optional argument, in brackets ([]), any optional argument which can be used for critical endnotes (6.2.3 p. 25).

11.7 Compatibility with xr package

The `\externaldocument` command of the `\xr` package allows making cross-references from an external document, with the standard L^AT_EX commands `\label` and `\ref` (and related).

To use it with the `reledmac` cross-reference commands (i.e. `\edlabel` and related), you must do the following:

1. Load the `xr` package.
2. Load the `reledmac` package.
3. Use the `\externaldocument` document command.

12 Sidenotes

12.1 Basics

The `\marginpar` command does not work in numbered text. Instead, the package provides for non-floating sidenotes in either margin.

```
\ledinnernote
\ledouternote
\ledleftnote
\ledrightnote
\ledsidenote
\sidenotemargin
```

`\ledinnernote{<text>}` will put `<text>` into the inner margin level with where the command was issued. Similarly, `\ledouternote{<text>}` puts `<text>` in the outer margin.

`\ledsidenote{<text>}` will put `<text>` into the margin specified by the current setting of `\sidenotemargin{<location>}`. The permissible value for `<location>` is one out of the list `left`, `right`, `inner`, or `outer`, for example `\sidenotemargin{outer}`. The package's default setting is `\sidenotemargin{right}`

to typeset `\ledsidenotes` in the right hand margin. This is the opposite of the default margin for line numbers. The style for a `\ledsidenote` follows that for a `\ledleftnote` or a `\ledrightnote` depending on the margin it is put in.

If two note commands for the same side are called in the same line, they will be appended and separated by a comma.

The notes will appear only after the second L^AT_EX run. If the note positions change in your .tex file, you need two runs to get the correction position in the output file. You are strongly encouraged to use tools like *latexmk*, to be sure to get the correct number of runs.

12.2 Setting

12.2.1 Width

```
\ledlnotewidth
\ledrnotewidth
```

The left sidenote text is put into a box of width `\ledlnotewidth` and the right text into a box of width `\ledrnotewidth`. These are initially set to the value of `\marginparwidth`.

12.2.2 Vertical position

`\rightnoteupfalse` By default, sidenotes are placed to align with the last line of the note to which it refers.
`\leftnoteupfalse` If you want them to be placed to align with the first line of the note to which it refers, use `\leftnoteupfalse` (for left note) and/or `\rightnoteupfalse` (for right note).

12.2.3 Distance to the main text

`\ledlnotesep` The texts are put a distance `\ledlnotesep` (or `\ledrsnotesep`) into the left (or right)
`\ledrsnotesep` margin. These lengths are initially set to the value of `\linenumsep`.

12.2.4 Font

`\ledlnotefontsetup` These macros specify how the sidenote texts are to be typeset. The initial definitions are:
`\ledrsnotefontsetup`

```
\newcommand*{\ledlnotefontsetup}{\raggedleft\footnotesize}%
\newcommand*{\ledrsnotefontsetup}{\raggedright\footnotesize}%
```

These can of course be changed to suit.

12.2.5 Separator between notes

`\setsidenotesep` If you have two or more sidenotes for the same line, they are separated by a comma. But if you want to change this separator, you can use `\setsidenotesep{<sep>}`.

13 Indexing

13.1 Basics

`\edindex` L^AT_EX provides the `\index{<item>}` command for specifying that `<item>` and the current page number should be added to the raw index (`.idx`) file. The `\edindex{<item>}` macro can be used in numbered text to specify that `<item>` and the current page & linenumber should be added to the raw index file.

Note that the file `.idx` will contain the right reference only after the third run, because of the internal indexing mechanism of `reledmac`. That means you must first run (Xe/Lua)L^AT_EX three times, then run `makeindex`, and then finally run (Xe/Lua)L^AT_EX again, in order to get an index with the right page numbers.

If the `imakeidx` or `indextools` package is used then the macro takes an optional argument, which is the name of a raw index file. For example `\edindex[line]{item}` will use `line.idx` as the raw file instead of `\jobname.idx`.

The minimal version of `imakeidx` package to be used is the version 1.3a uploaded on CTAN on 2013/07/11.

Be careful with the order of package loading and index declaration. You must use this order:

1. Load `imakeidx` or `indextools`.
2. Load `reledmac`.

3. Declare the index with the macro `\makeindex` of `imakeidx` and `indextools`.

Also note that using `\edtext` in familiar footnotes refers to the line where the footnotes are called

13.2 Referring to critical notes

If you want to refer to a word inside an `\edtext{<lemma>}{<app>}` command, `\edindex` should be defined inside the first argument, e.g.,

```
The \edtext{creature}\edindex{elephant} was quite
unafraid}{\Afootnote{Of the mouse, that is.}}
```

If you add `\edindex` inside some `\Xfootnote` command, it will refer to that note, and a suffix *n* will be appended to the reference. You can redefine this suffix by redefining the command `\ledinnotemark`. Its actual definition is:

```
\newcommand{\ledinnotemark}[1]{\#1\emph{n}}
```

Where #1 stands for the reference.

13.3 Separator between page and line numbers

`\pagelinesep`

The page & linenumber combination is written as `page\pagelinesep` line, where the default definition is `\newcommand{\pagelinesep}{-}` so that an item on page 3, line 5 will be noted as being at 3-5. You can renew `\pagelinesep` to get a different separator.

- is the default separator used by the `MAKEINDEX` program.

You can reconfigure it, this example defines a colon as separator:

```
\renewcommand{\pagelinesep}{:}
```

However, you also have to configure your `.ist` index style file. For example, if you use : as separator²².

```
page_compositor ":"
```

Read the `MAKEINDEX` program's handbook about the `.ist` file.

13.4 Using xindy

Should you decide to use `xindy` instead of `makeindex` to transform your `.idx` files into `.ind` files, you must use some specific configuration file (`.xdy`) so that `xindy` can understand `eledmac` reference syntax of which the scheme is:

`pagenumber-linenumber`

²²For further detail, you can read <http://tex.stackexchange.com/a/32783/7712>.

An example of such a file is provided in the “examples” folder. Read the `xindy` handbook to learn how to use it.²³

This file also provides, with an explanation, the settings that are needed to put `reledmac` lines numbers in parenthesis, in order to make a better distinction between line numbers and page ranges.

In any case, you must load `reledmac` with the `xindy` option, in order to generate a `.xdy` file which is specific to your document. This file is needed by the `.xdy` example file which is in the “examples” folder. Its default name is `reledmac-markup-attr.xdy`, but you can change it by using your own as an argument of the `xindy+hyperref` option.

If you choose to use both `xindy` and the `hyperref` package, you must do three more things:

1. Use `xindy+hyperref` option when loading the `reledmac` package. When you run (Xe/Lua)TeX with this option, a `.xdy` configuration file will be generated with all the settings needed to allow internal hyperlinking in each index entry which is created by `\edindex`.
2. Use `hyperindex=false` option when loading `hyperref`.
3. Uncomment – by removing the semicolons at the beginning of the relevant lines – some lines in the `<code>.xdy</code>` file provided in the “examples” folder in order to restore internal links in the index to be used by the standard `index` command.²⁴.

13.5 Advanced setting

`\edindexlab` The `\edindex` process uses a `\label` and `\ref` mechanism to get the correct line number. It automatically generates labels of the form `\label{\edindexlab N}`, where `N` is a number, and the default definition of `\edindexlab` is:

`\newcommand*\{\edindexlab\}{\$&}`

in the hopes that this will not be used by any other labels (`\edindex`’s labels are like `\label{\$&27}`). You can change `\edindexlab` to something else if you need to.

14 Glossary

`reledmac` provides mechanism to make glossaries with the `glossaries` package, referring not to the page, but to the page and line.

14.1 Preamble setting

The standard compositor between page and line number in `reledmac` is a dash, while `glossaries` uses, by default, a dot. Consequently, you must:

²³Or, for people who read French, read <http://geekographie.maieu1.net/174>.

²⁴These are the recommended lines to provide the best possible compatibility between `hyperref` and `xindy`, even without using `reledmac`.

- Or set `.glossaries`:
`\glsSetCompositor{-}`
- Or set `reledmac`:
`\renewcommand{\pagelinesep}{-}`
In this case, the above will have consequences for your use of `\edindex` and you should set your `.ist` file (13.3 p. 66).

14.2 Commands

The `\gls`, `\Gls`, and related commands of `glossaries` packages have a prefixed version with `ed`, which refers to the page line. The argument are the same as for the standard commands. So for example:

```
\edgls[<options>]{<label>} [<insert>]
```

15 Tabular material

`LATEX`'s normal `tabular` and `array` environments cannot be used where line numbering is being done; more precisely, they can be used but with odd results, so don't use them. However, `reledmac` provides some simple tabulation environments that can be line numbered. The environments can also be used in normal unnumbered text.

There are six environments; the `edarray*` environments are for math and `edtabular*` for text entries. The final `l`, `c`, or `r` in the environment names indicate that the entries will be flushleft (`l`), centered (`c`) or flushright (`r`). There is no means of specifying different formats for each column, nor for specifying a fixed width for a column. The environments are centered with respect to the surrounding text.

```
\begin{edtabularc}
1 & 2 & 3 \\
a & bb & ccc \\
AAA & BB & C
\end{edtabularc}
```

1	2	3
a	bb	ccc
AAA	BB	C

Entries in the environments are the same as for the normal `array` and `tabular` environments but there must be no ending `\\"` at the end of the last row. *There must be the same number of column designators (the &) in each row*. There is no equivalent to any line drawing commands (such as `\hline`). However, unlike the normal environments, the `ed...` environments can cross page breaks.

Macros like `\edtext` can be used as part of an entry.

For example:

```
\begin{numbering}
\pstart
\begin{edtabularl}
\textbf{\Large I} & wish I was a little bug\edindex{bug} &
\textbf{\Large I} & eat my peas with honey\edindex{honey} \\
& With whiskers \edtext{round}{\Afootnote{around}} my tummy &
& I've done it all my life. \\
& I'd climb into a honey\edindex{honey} pot &

```

```

& It makes the peas taste funny \\
& And get my tummy gummy.\edindex{gummy} &
& But it keeps them on the knife.
\end{edtabularr}
\pend
\endnumbering

```

produces the following parallel pair of verses.

1 I wish I was a little bug 2 With whiskers round my tummy 3 I'd climb into a honey pot 4 And get my tummy gummy.	I eat my peas with honey I've done it all my life. It makes the peas taste funny But it keeps them on the knife.
--	--

\edtabcolsep The distance between the columns is controlled by the length \edtabcolsep.
\spreadmath{ $\langle math \rangle$ } typesets { $\langle math \rangle$ } but the { $\langle math \rangle$ } has no effect on the calculation of column widths. \spreadtext{ $\langle text \rangle$ } is the analogous command for use in edtabular environments.
\begin{edarrayl}

1 & 2 & 3 & 4 \\ & \spreadmath{F+G+C} & & \\ a & bb & ccc & dddd	1 2 3 4 F + G + C a bb ccc dddd
--	---

\edrowfill The macro \edrowfill{ $\langle start \rangle$ }{ $\langle end \rangle$ }{ $\langle fill \rangle$ } fills columns number $\langle start \rangle$ to $\langle end \rangle$ inclusive with $\langle fill \rangle$. The $\langle fill \rangle$ argument can be any horizontal 'fill'. For example, \hrulefill or \upbracefill.

Note that every row must have the same number of columns, even if some would not appear to be necessary.

The \edrowfill macro can be used in both tabular and array environments. The typeset appearance of the following code is shown below.

```

\begin{edtabularr}
1 & 2 & 3 & 4 & 5 \\
Q & & fd & h & qwertziohg \\
v & wptz & x & y & vb \\
g & nnn & & \edrowfill{3}{5}{\upbracefill} & & \\
\edrowfill{1}{3}{\downbracefill} & & & pq & dgh \\
k & & & 1 & co & ghweropjklmnbcxys \\
1 & & & 2 & 3 & \edrowfill{4}{5}{\hrulefill} &
\end{tabularr}

```

1 2 3 4	5
Q fd h qwertziohg	vb
v wptz x y	
g nnn	
k	
1 2 3	

You can also define your own ‘fill’. For example:

```
\newcommand*{\upbracketfill}{%
  \vrule height 4pt depth 0pt\hrulefill\vrule height 4pt depth 0pt}
```

is a fill like `\upbracefill` except it has the appearance of a (horizontal) bracket instead of a brace. It can be used like this:

```
\begin{edarrayc}
 1 & 2 & 3 & 4 \\
 a & \edrowfill{2}{3}{\upbracketfill} & & d \\
 A & B & C & D
\end{edarrayc}
```

$$\begin{matrix} 1 & 2 & 3 & 4 \\ a & \sqcup & & d \\ A & B & C & D \end{matrix}$$

`\edatleft` `\edatleft[<math>]{<symbol>}{<halfheight>}` typesets the math `<symbol>` as `\left{<symbol>` with the optional `<math>` centered before it. The `<symbol>` is twice `<halfheight>` tall. The `\edatright` macro is similar and it typesets `\right{<symbol>}` with `<math>` centered after it.

```
\begin{edarrayc}
  & 1 & 2 & 3 & \\
  & 4 & 5 & 6 & \\
\edatleft[left =]{\{}{1.5\baselineskip}
  & 7 & 8 & 9 & \\
\edatright[= right]{\}}{1.5\baselineskip}
\end{edarrayc}
```

$$left = \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} = right$$

`\edbforetab` `\edbforetab{<text>}{<entry>}`, where `<entry>` is an entry in the leftmost column, typesets `<text>` left justified before the `<entry>`. Similarly `\edaftertab{<entry>}{<text>}`, where `<entry>` is an entry in the rightmost column, typesets `<text>` right justified after the `<entry>`.

For example:

```
\begin{edarrayl}
  A & 1 & 2 & 3 \\
\edbforetab{Before}{B} & 1 & 3 & 6 \\
  C & 1 & 4 & \edaftertab{8}{After} \\
  D & 1 & 5 & 0
\end{edarrayl}
```

Before	$\begin{array}{cccc} A & 1 & 2 & 3 \\ B & 1 & 3 & 6 \\ C & 1 & 4 & 8 \\ D & 1 & 5 & 0 \end{array}$	After
--------	--	-------

`\edvertline` The macro `\edvertline{<height>}` draws a vertical line `<height>` high (contrast this with `\edatright` where the size argument is half the desired height).

```
\begin{edarrayr}
a & b & C & d   & \\
v & w & x & y   & \\
m & n & o & p   & \\
k &   & L & cvb & \edvertline{4pc}
\end{edarrayr}
```

a	b	C	d	
v	w	x	y	
m	n	o	p	
k		L	cvb	

The `\edvertdots` macro is similar to `\edvertline` except that it produces a vertical dotted instead of a solid line.

16 Sectioning commands

16.1 Sectioning commands without line numbers or critical notes

The standard sectioning commands (`\chapter`, `\section` etc.) can be used inside numbered text. In this case, you must call them as an optional argument of `\pstart` (5.2.3 p. 18):

```
\pstart[\section{section}]
Pstart content.
\pend
```

The line which contains them will not be numbered, and you cannot add critical notes inside.

16.2 Sectioning commands with line numbering and critical notes

You have to use the following commands:

- `\eledchapter[<text>]{<critical text>}`,
- `\eledchapter*`,

- `\uledsection[⟨text⟩]{⟨critical text⟩},`
- `\uledsection*,`
- `\uledsubsection[⟨text⟩]{⟨critical text⟩},`
- `\uledsubsection*,`
- `\uledsubsubsection[⟨text⟩]{⟨critical text⟩},`
- `\uledsubsubsection*.`

These are equivalent to the L^AT_EX commands. Each individual command must be called alone in a `\pstart ... \pend`:

```
\pstart
\uledsection*{xxxx\ledsidenote{section}}
\pend
\pstart
\uledsubsection*{xxxx\ledsidenote{sub}}
\pend
\pstart
normal text
\pend
```

After the first run, you will see only the text. This is normal. After the second run, you will see the formatting. Finally, with the third run, you will see the table of contents.

For technical reasons, the page break before `\elechapter` cannot be added automatically. You have to insert it manually via `\beforeeledchapter`, which must be called outside of a numbered section.

16.3 Optimization

`\noeledsec` If you are not going to have any `\uledxxx` commands, then load `reledmac` with `\noeledsec` option. That will suppress the generation of unneeded `.eledsec` files, save memory, and make `reledmac` run faster.

17 Quotation environments

The quotation and quote environments can be used so that the same definition/note appears both inside and outside a numbered section. The typographical consequences will resemble the outside numbered sections, based on the styles of the *book* class. However, if you use a package that redefines these environments, these redefinitions won't be available inside the numbered section. You must open any quotation environments inside a `\pstart ... \pend` block, not outside. A quotation environment MUST NOT be opened immediately after a `\pstart` and MUST NOT be closed immediately before a `\pend`.

In some cases, you do not want these environments to be redefined in numbered sections. You can load the package with the option `noquotation` to prevent this redefinition.

18 Page breaks

18.1 Control page breaking

`\ledpb` and `\reledmac` break pages automatically. However, you may sometimes want to either force page breaks, or prevent them. The packages provide two macros:

- `\ledpb` adds a page break.
- `\lednomp` prevents a page break, by adding one line to the current page if needed.

These commands have effect only at the second run.

These two commands take effect at the beginning of line in which they are called. For example, if you call `\ledpb` at l. 444, then l. 443 will be at p. *n*, and l. 444 at p. *n* + 1. However, you can change the behavior and decide they will have effect after the end of the line, adding `\ledpbsetting{after}` at the beginning of your file (better: in your preamble). With the previous example, l. 444 will be on p. *n* and l. 445 will be on p. *n* + 1.

If you are using `\reledpar` to typeset parallel pages, you must use `\lednomp` on both sides in the two corresponding lines. This is especially important when you are using stanzas; otherwise, the pages will be out of sync.

18.2 Prevent page break in a long verses

`\lednompinversetrue` You can also decide to prevent page breaks between two lines of a long verse. To do this, use `nopbinverse` when loading package, or add `\lednompinversetrue` in the beginning of your file (better: in your preamble).

This feature works only with verse of 2 lines and no more. It works on the third run, or on the fourth run if using `\reledpar`. By default, when a long verse runs between two pages, a page break will be placed at the beginning of the verse. However, if you have added `\ledpbsetting{after}`, the page break will be placed at the end of the long verse and the page containing the long verse will have one extra line.

19 Miscellaneous

`\extensionchars` When the package assembles the name of the auxiliary file for a section, it prefixes `\extensionchars` to the section number. This is initially defined to be empty, but you can add some characters to help distinguish these files if you like; what you use is likely to be system-dependent. If, for example, you said `\renewcommand{\extensionchars}{!}`, then you would get temporary files called `jobname . !1`, `jobname . !2`, etc.

`\ifledfinal` The package can take options. The option ‘final’, which is the default is for final typesetting; this sets `\ifledfinal` to TRUE. The other option, ‘draft’, may be useful during earlier stages and sets `\ifledfinal` to FALSE.

The lemma within the text is printed via `\showlemma{lemma}`. Normally, or with the ‘final’ option, the definition of `\showlemma` is:

```
\newcommand*{\showlemma}[1]{#1}
so it just produces its argument. With the ‘draft’ option it is defined as
\newcommand*{\showlemma}[1]{\textit{#1}}
```

so that its argument is typeset in an italic font, which may make it easier to check that all lemmas have been treated.

If you would prefer some other style, you could put something like this in the preamble:

```
\ifledfinal\else
    \renewcommand{\showlemma}[1]{\textbf{\#1}}% or simply ...[1]{#1}
\fi
```

19.1 Known and suspected limitations

19.1.1 Non-standard geometry

If you use classes other than `article` or `book`, or if you use the `geometry` package, you should use `maxnotesX` and/or `\Xmaxnotes` as explained in 7.12.6 p. 50 in order to prevent footnotes from overlapping the bottom margin.

19.1.2 floatrow package compatibility

The `floatrow` package must be loaded before the `reledmac`.

19.1.3 ‘No room for a new’

Sometimes, especially when using `reledmac` with other packages, you could obtain warning messages such ‘no room for a new count’ or ‘no room for a new write’.

In order to prevent such problems, the first thing is to use the options to optimize `reledmac`. For example, if you need only two series of notes, use the `series={A,B}` option. Read 16.3 p. 72 in order to know which are the available options.

However, if with these options you still have such messages, here are some tricks.

‘**no room for a new count**’ is often caused by `biblatex` being used at the same time.
Load `reledmac` (and `reledpar`) *before* `biblatex`.

‘**no room for a new write**’ can be caused by multiple indexes. In this case, use `indextools` of `imakeidx` with the `splitindex` option, in order to obtain only one `.idx` file. If that does not solve your problem, you can use `morewrites` package. That should solve the problem, but `LATEX` will be slower.

If after reading and applying these advices you have still problem, contact us with a minimal working example.

19.1.4 Marginal notes

In general, `reledmac`’s system for adding marginal line numbers breaks anything that makes direct use of the `LATEX` insert system, which includes `margipars`, `footnotes` and `floats`.

However, you can use both `\footnote` and the familiar footnote series notes in numbered text. A `\marginpar` in numbered text will throw away its contents and send a warning message to the terminal and log file, but will do no harm.

19.1.5 Paragraph shape

\parshape cannot be used within numbered text, except in a very restricted way.

\ballast L^AT_EX is a three-pass system, but even after a document has been processed three times, there are some tricky situations in which the page breaks decided by T_EX never settle down. At each successive run, reledmac may oscillate between two different sets of page decisions. To stop this happening, should it arise, Wayne Sullivan suggested the inclusion of the quantity \ballast. The amount of \ballast will be subtracted from the penalties which apply to the page breaks calculated on the *previous* run through T_EX, thus reinforcing these breaks. So if you find your page breaks oscillating, insert
\setcounter{ballast}{100}
or some such figure, and with any luck the page breaks will settle down. Luckily, this problem does not crop up at all often.

19.1.6 Paragraphed footnotes

The restriction on explicit line-breaking in paragraphed footnotes, mentioned on 7.1 p. 38, and described in more detail on XIII.6.3 p. 187, really is a nuisance if that is something you need to do. There are some possible solutions, described by Michael Downes, but this area remains unsatisfactory.

If you use more than one series of paragraphed notes, it may happen, in some particular cases, that only the footnote rule, with no accompanying footnotes, be printed. In this case use reledmac package option nopenalties which should solve the problem, but also may produce widow or orphan lines. For the time being, we have no solution of this problem.

\footfudgefiddle For paragraphed footnotes T_EX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. \footfudgefiddle can be increased from its default 64 (say, to 68) to increase the estimate. You have to use \renewcommand for this, like:

\renewcommand{\footfudgefiddle}{68}

Note that you must call it *before* \Xarrangement{paragraph} or \arrangementX{paragraph}.

Any settings to ‘geometry’ must be made before \Xarrangement / \arrangementX.

Finally, in many cases you should use \Xmaxhnotes and / or \maxhnotesX (7.12.6 p. 50), in order to define the maximum height relative to \textheight and not to \vsize, because the \vsize value is not the same inside and outside of the preamble.

19.1.7 Use with other packages

Because of reledmac’s complexity, it may not play well with other packages. In particular reledmac is sensitive to commands in the arguments to the \edtext and *footnote macros (this is discussed in more detail in section VI, and in particular the discussion about \no@expands and \morenoexpands). You will have to see what works or doesn’t work in your particular case.

\morenoexpands You can define the macro \morenoexpands to modify macros that you call within \edtext. Because of the way reledmac numbers the lines the arguments to \edtext can be processed more than once and in some cases a macro should only be processed

once. One example is the `\colorbox` macro from the `color` package, which you might use like this:

```
... \edtext{\colorbox{mycolor}{lemma}}{\Afootnote{... \colorbox{...}}}
```

If you actually try this²⁵ you will find L^AT_EX whining ‘Missing { inserted’, and then things start to fall apart. The trick in this case is to specify either:

```
\newcommand{\morenoexpands}{\let\colorbox=0}
```

or

```
\makeatletter
\newcommand{\morenoexpands}{\let\colorbox\@secondoftwo}
\makeatother
```

(`\@secondoftwo` is an internal L^AT_EX macro that takes two arguments and throws away the first one.) The first incantation lets color show in both the main text and footnotes whereas the second one shows color in the main text but kills it in the lemma and footnotes. On the other hand if you use `\textcolor` instead, like

```
... \edtext{\textcolor{mycolor}{lemma}}{\Afootnote{... \textcolor{...}}}
```

there is no need to fiddle with `\morenoexpands` as the color will naturally be displayed in both the text and footnotes. To kill the color in the lemma and footnotes, though, you can do:

```
\makeatletter
\newcommand{\morenoexpands}{\let\textcolor\@secondoftwo}
\makeatother
```

It took Peter Wilson a little while to discover all this. If you run into this sort of problem you may have to spend some time experimenting before hitting on a solution.

If you want to use the option *bottom* of the `footmisc` package, you must load this package *before* the `reledmac` package.

19.2 Parallel typesetting

Peter Wilson has developed the `ledpar` package as an extension to `ledmac` specifically for parallel typesetting of critical texts. This also cooperates with the `babel` / `polyglossia` packages for typesetting in multiple languages. `reledpar` is the successor of the primitive `ledpar` package.

Peter Wilson also developed the `ledarab` package for handling parallel Arabic text in critical editions. However, this package is not maintained by Maïeul Rouquette. You should use the capabilities of a modern TeX processor, like Xe(La)TeX

²⁵Reported by Dirk-Jan Dekker in the CTT thread ‘Incompatibility of “color” package’ on 2003/08/28.

I Implementation overview

We present the `reledmac` code in roughly the order in which it is used during a run of \TeX . The order is *exactly* that in which it is read when you load The `Eledmac` package, because the same file is used to generate this manual and to generate the `L\TeX` package file.

Most of what follows consists of macro definitions, but there are some commands that are executed immediately—especially at the start of the code. The documentation generally describes the code from the point of view of what happens when the macros are executed, though. As each macro is introduced, its name is printed in the margin.

After package options, we begin with the commands you use to start and stop line numbering in a section of text (Section II). Next comes the machinery for writing and reading the auxiliary file for each section that helps us count lines, and for creating list macros encoding the information from that file (Section V); this auxiliary file will be read at the start of each section, to create those list macros, and a new version of the file will be started to collect information from the body of the section.

Next are commands for marking sections of the text for footnotes (Section VI), followed by the macros that take each paragraph apart, attach the line numbers and insertions, and send the result to the vertical list (Section VII). The footnote commands (Section XIII) and output routine (Section XXIII) finish the main part of the processing; cross-referencing (Section XXIV) and endnotes (Section XX) complete the story.

In what follows, macros with an @ in their name are more internal to the workings of `reledmac` than those made up just of ordinary letters, just as in PLAIN \TeX (see *The TeXbook*, p. 344). You are meant to be able to make free with ordinary macros, but the '@' ones should be treated with more respect, and changed only if you are pretty sure of what you are doing.

II Preliminaries

II.1 Links with original `edmac`

Generally, these are the modifications to the original. `edmac` code:

- Replace as many `\def`'s by `\newcommand`'s as possible to avoid overwriting `L\TeX` macros.
- Replace user-level \TeX counts by `L\TeX` counters.
- Use the `L\TeX` font handling mechanisms.
- Use `L\TeX` messaging and file facilities.

II.2 Package declaration

Announce the name and version of the package, which is targetted for LaTeX2e .

```

1  %<*code>
2  \NeedsTeXFormat{LaTeX2e}
3  \ProvidesPackage{reledmac}[2017/11/26 v2.26.1 typesetting critical editions
]%
4 %

```

II.3 Package options

\ifledfinal Use this to remember which option is used, set and execute the options with final as the default. We use `xkeyval` in order to manage options with argument.

\ifnocritical@sec
\ifnoend@
\ifnofamiliar@
\ifnoledgroup@ The `parledgroup` option is for `reledpar`. However, it has consequence on `reledmac` internal command. So we need to define the boolean now.
\ifparapparatus@
\ifnoquotation@
\iflednoprinv
\ifparledgroup
\ifwidthliketwocolumns And now, the options of `reledmac`.

\ifxindy@
\ifxindyhyperref@
\ifeledmaccompat@
\ifnoeled@sec%
\DeclareOptionX{series}{A,B,C,D,E}{\xdef\default@series{\#1}}%
\ExecuteOptionsX{series}%
\ifeledmaccompat@
\newif\if@noeled@sec%
\DeclareOptionX{noeledsec}{\@noeled@sectrue}%
\newif\ifnocritical@%
\DeclareOptionX{nocrical}{\nocritical@true}%
\newif\ifnofamiliar@%
\DeclareOptionX{nofamiliar}{\nofamiliar@true}%
\newif\ifnoledgroup@%
\DeclareOptionX{noledgroup}{\noledgroup@true}%
\newif\ifnoend@%
\DeclareOptionX{noend}{\@noend@true}%
\let\l@dend@open\@gobble%
\let\l@dend@close\relax%
\global\let\l@dend@stuff=\relax%
\noend@true%
}%
\newif\ifnoquotation@%
\DeclareOptionX{noquotation}{\noquotation@true}%
\newif\ifledfinal%
\DeclareOptionX{final}{\ledfinaltrue}%
\DeclareOptionX{draft}{\ledfinalfalse}

```

38 \ExecuteOptionsX{final}
39
40 \newif\ifparapparatus@
41 \DeclareOptionX{parapparatus}{\parapparatus@true}
42
43 \newif\iflednopbinverse
44 \DeclareOptionX{nopbinverse}{\lednopbinversetrue}
45
46 \newif\ifwidthliketwocolumns%
47 \DeclareOptionX{widthliketwocolumns}{\widthliketwocolumnstrue}%
48
49 \newif\ifcontinuousnumberingwithcolumns
50 \DeclareOptionX{continuousnumberingwithcolumns}{\
51   continuousnumberingwithcolumnstrue}%
52
53 \newif\ifxindy@
54 \DeclareOptionX{xindy}[eledmac-markup-attr.xdy]{%
55   \AtBeginDocument{\immediate\openout\eledmac@xindy@out=#1}%
56   \newwrite\eledmac@xindy@out%
57   \xindy@true%
58   \gdef\eledmacmarkuplocrefdepth{:depth 1}%
59   \AtEndDocument{\immediate\closeout\eledmac@xindy@out}%
60 }%
61
62 \newif\ifxindyhyperref@
63 \DeclareOptionX{xindy+hyperref}{%
64   \xindyhyperref@true%
65 }%
66
67 \newif\ifeledmaccompat@
68 \DeclareOptionX{eledmac-compat}{%
69   \eledmaccompat@true%
70 }%
71 \DeclareOptionX{nopenalties}{%
72   \AtBeginDocument{\let\add@penalties\relax}%
73 }
74 \def\l@auxdir{}%
75 \DeclareOptionX{auxdir}{%
76   \xdef\l@auxdir{\#1}%
77 }%
78 \newif\ifsw@caseinsensitive%
79 \DeclareOptionX{swcaseinsensitive}{%
80   \sw@caseinsensitivetrue%
81 }%
82 %

```

We use the starred form of `\ProcessOptionsX` which executes options in the order listed in the source file: class options, then listed package options, so a package option can override a class option with the same name. This was suggested by Dan Luecking

in the ctt thread *Class/package option processing*, on 27 February 2004.

```
83 \ProcessOptionsX*\relax
84 %
85 %
```

II.4 Loading packages

Loading package `xargs` to declare commands with optional arguments. Loading package `xparse` to declare fully expandable commands with optional argument. Ideally, we should use only `xparse` and not `xargs`. For historical reasons, we use both. `Etoolbox` is also used to make code clearer - for example, in dynamic command names (which can replace `\csname` etc.). Use `suffix` to declare commands with a starred version, `xstring` to work with strings, `ifluatex` and `ifxetex` to test if `LuaTeX` or `X\mathbb{E}T\mathbb{E}X` is running, and `ragged2e` to manage ragged justification for paragraphed notes.

```
86 \RequirePackage{xargs}
87 \RequirePackage{xparse}%
88 \RequirePackage{etoolbox}
89 \@ifl@t@r\fmtversion{2015/10/01}
90 {\@ifboolexpr{not \test{\@ifl@t@r\fmtversion{2016/03/31}} or (\test{\\
91 \ifdefstring{\fmtversion}{2016/03/31}} and \test{\ifnumless{\patch@level
92 }{3}})}%}
93 {\@PackageWarning{reledmac}{You are using a LaTeX version older than
94 2016/03/31 patch 3.}%
95 \MessageBreak You are strongly encouraged to use a newer version.}%
96 \csname reserveinserts\endcsname{32}%
97 }%
98 \RequirePackage{suffix}
99 \RequirePackage{xstring}
100 \RequirePackage{ifluatex}
101 \RequirePackage{ragged2e}
102 \RequirePackage{ifxetex}%
103 %
```

II.5 Compatibility with `LuaTeX`

Here, we enable some primitives for `LuaTeX`.

```
104 \ifx\directlua\undefined\else%
105   \directlua{tex.enableprimitives("", {"textdir", "pardir", "bodydir"})}
106 \fi
107 %
```

II.6 Boolean flags

\ifl@dmemoir Define a flag for if the memoir class has been used.

```
108 \newif\ifl@dmemoir
109 \@ifclassloaded{memoir}{\l@dmemoirtrue}{\l@dmemoirfalse}
110 %
111 %
```

\if@ledgroup Flag set to true inside a ledgroup environment.

```
112 \newif\if@ledgroup%
113 %
```

\ifl@imakeidx Define a flag for if the imakeidx package has been used.

```
114 \newif\ifl@imakeidx
115 \@ifpackageloaded{imakeidx}{\l@imakeidxtrue}{%False is the default value
116 %
```

\ifl@indextools Define a flag for if the indextools package has been used.

```
117 \newif\ifl@indextools%
118 \@ifpackageloaded{indextools}{%
119   \l@indextoolstrue%
120   \l@imakeidxtrue%
121   \let\imki@wrindexentry\indtl@wrindexentry%
122 }{}%
123 %
```

False is the default value. We consider indextools as a variant of imakeidx. That is why we set \ifl@imakeidx to true. We also let \imki@wrindexentry to \indtl@wrindexentry.

\ifl@footmisc Define a flag if the footmisc package has been loaded.

```
124 \newif\ifl@footmisc
125 \@ifpackageloaded{footmisc}{\l@footmisctrue}{%False is the default value
126 %
```

\if@RTL The \if@RTL is defined by the bidi package, which is sometimes loaded by *Polyglossia*. But we define it as well if the bidi package is not loaded.

```
127 \ifdef{\if@RTL}{}{\newif\if@RTL}
128 %
```

\if@firstlineofpage \if@firstlineofpage is set to TRUE at the first line of every page. \if@firstlineofpageR is for the right side.

```
129 \newif\if@firstlineofpage%
130 \newif\if@firstlineofpageR%
131 %
```

II.7 Messages

All the messages are grouped here as macros. This saves T_EX's memory when the same message is repeated and also lets them be edited easily.

`\reledmac@warning` Write a warning message.

```
132 \newcommand{\reledmac@warning}[1]{\PackageWarning{reledmac}{#1}}
133 %
```

`\reledmac@error` Write an error message.

```
134 \newcommand{\reledmac@error}[2]{\PackageError{reledmac}{#1}{#2}}
135 %
```

```
\led@err@NumberingStarted36 \newcommand*{\led@err@NumberingStarted}{%
\led@err@NumberingNotStarted37   \reledmac@error{Numbering has already been started}{\@ehc}}
\led@err@NumberingShouldHaveStarted38 \newcommand*{\led@err@NumberingNotStarted}{%
\reledmac@error{Numbering was not started}{\@ehc}}
\newcommand*{\led@err@NumberingShouldHaveStarted}{%
\reledmac@error{Numbering should already have been started}{\@ehc}}
141 %
142 %
```

```
\led@err@edtextoutsidepstart43 \newcommand*{\led@err@edtextoutsidepstart}{%
144   \reledmac@error{\string\edtext\space outside numbered paragraph (\pstart\%
145   space ... \space\pend)}{\@ehc}}%
145 %
```

```
\led@mess@NotesChanged46 \newcommand*{\led@mess@NotesChanged}{%
147   \typeout{reledmac reminder: }%
148   \typeout{ The number of the footnotes in this section}
149   \typeout{ has changed since the last run.}%
150   \typeout{ You will need to run LaTeX two more times}
151   \typeout{ before the footnote placement}%
152   \typeout{ and line numbering in this section are}
153   \typeout{ correct.}%
154 %
```

```
\led@mess@SectionContinued55 \newcommand*{\led@mess@SectionContinued}[1]{%
156   \message{Section #1 (continuing the previous section)}%
157 %
```

```
\led@err@LineationInNumbered58 \newcommand*{\led@err@LineationInNumbered}{%
159   \reledmac@error{You can't use \string\lineation\space within}
160   \reledmac@error{a numbered section}{\@ehc}}
161 %
```

```
\led@warn@BadLineation62 \newcommand*{\led@warn@BadLineation}{%
\led@warn@BadLinenummargin63   \reledmac@warning{Bad \string\lineation\space argument}}
\led@warn@BadLockdisp64 \newcommand*{\led@warn@BadLinenummargin}{%
\led@warn@BadSublockdisp65   \reledmac@warning{Bad \string\linenummargin\space argument}}
\led@warn@BadSublockdisp66 \newcommand*{\led@warn@BadLockdisp}{%
\led@warn@BadSublockdisp67   \reledmac@warning{Bad \string\lockdisp\space argument}}
\led@warn@BadSublockdisp68 \newcommand*{\led@warn@BadSublockdisp}{%
\led@warn@BadSublockdisp69   \reledmac@warning{Bad \string\sublockdisp\space argument}}
\led@warn@BadSublockdisp70 %
```

```
\led@warn@NoFile71 \newcommand*{\led@warn@NoFile}[1]{%
\led@warn@NoFile72   \reledmac@warning{File '#1' not found}}
\led@warn@NoFile73 %
```

```
\led@warn@LineFileObsolete74 \newcommand*{\led@warn@Obsolete}[1]{%
\led@warn@LineFileObsolete75   \reledmac@warning{Line-list file #1 was obsolete. We have not read it.
\led@warn@LineFileObsolete76     Please run LaTeX again.}}
\led@warn@LineFileObsolete77 %
```

```
\led@warn@BadAdvancelineSubline77 \newcommand*{\led@warn@BadAdvancelineSubline}{%
\led@warn@BadAdvancelineLine78   \reledmac@warning{\string\advanceline\space produced a sub-line
\led@warn@BadAdvancelineLine79     number less than zero.}}
\led@warn@BadAdvancelineLine80 \newcommand*{\led@warn@BadAdvancelineLine}{%
\led@warn@BadAdvancelineLine81   \reledmac@warning{\string\advanceline\space produced a line
\led@warn@BadAdvancelineLine82     number less than zero.}}
\led@warn@BadAdvancelineLine83 %
```

```
\led@warn@BadSetline84 \newcommand*{\led@warn@BadSetline}{%
\led@warn@BadSetlinenum85   \reledmac@warning{Bad \string\setline\space argument}}
\led@warn@BadSetlinenum86 \newcommand*{\led@warn@BadSetlinenum}{%
\led@warn@BadSetlinenum87   \reledmac@warning{Bad \string\setlinenum\space argument}}
\led@warn@BadSetlinenum88 %
```

```
\led@err@PstartNotNumbered89 \newcommand*{\led@err@PstartNotNumbered}{%
\led@err@PstartInPstart90   \reledmac@error{\string\pstart\space must be used within a
\led@err@PstartInPstart91     numbered section %
\led@err@PstartInPstart92     (\string\beginnumbering\space ... \space \string\endnumbering)
\led@err@PstartInPstart93   }{\@ehc}}%
\led@err@PendNotNumbered94 \newcommand*{\led@err@PstartInPstart}{%
\led@err@PendNotNumbered95   \reledmac@error{\string\pstart\space encountered while another
\led@err@PendNotNumbered96     \string\pstart\space was in effect}{\@ehc}}
\led@err@PendNotNumbered97 \newcommand*{\led@err@PendNotNumbered}{%
\led@err@PendNotNumbered98   \reledmac@error{\string\pend\space must be used within a
\led@err@PendNotNumbered99     numbered section}{\@ehc}}
```

```

199 \newcommand*{\led@err@PendNoPstart}{%
200   \reledmac@error{\string\pend\space must follow a \string\pstart}{\@ehc}}
201 \newcommand*{\led@err@AutoparNotNumbered}{%
202   \reledmac@error{\string\autopar\space must be used within a
203     numbered section}{\@ehc}}
204 \newcommand*{\led@err@NumberingWithoutPstart}{%
205   \reledmac@error{\string\beginnumbering... \string\endnumbering\space
206     without \string\pstart}{\@ehc}}%
207 %

```

```

\led@warn@BadAction207 \newcommand*{\led@warn@BadAction}{%
208   \reledmac@warning{Bad action code, value \next@action.}}%
209 %

```

```

\led@warn@DuplicateLabel210 \newcommand*{\led@warn@DuplicateLabel}[1]{%
211   \reledmac@warning{Duplicate definition of label `#1'\@gobble}%
\led@warn@AppLabelOutSecondArgEdtext212 \@latex@warning@no@line{Label `#1' multiply defined}%
\led@warn@RefUndefined213 }%
214 \newcommand*{\led@warn@AppLabelOutSecondArgEdtext}[1]{%
215   \reledmac@warning{\string\applabel\space outside of the second argument
216     of an \string\edtext\space `#1' on page \thepage.}}%
217 \newcommand*{\led@warn@RefUndefined}[1]{%
218   \G@refundefinedtrue%
219   \reledmac@warning{Reference `#1' on page \thepage\space undefined.%
220     Using `000'.}}%
221 \@latex@warning{Reference `#1' undefined\on@line}%
222 }%
223 \newcommand*{\led@warn@pairRefUndefined}[1]{%
224   \G@refundefinedtrue%
225   \reledmac@warning{Reference `#1:start' and/or `#1:end' on page \thepage\space
226     undefined.%
227     Using `??'.}}%
228 %

```

```

\led@warn@NoMarginpars229 \newcommand*{\led@warn@NoMarginpars}{%
230   \reledmac@warning{You can't use \string\marginpar\space in numbered text
231 }}%

```

```

\led@warn@BadSidenotemargin32 \newcommand*{\led@warn@BadSidenotemargin}{%
233   \reledmac@warning{Bad \string\sidenotemmargin\space argument}}%
234 %

```

```

\led@warn@NoIndexFile35 \newcommand*{\led@warn@NoIndexFile}[1]{%
 236   \reledmac@warning{Undefined index file #1}%
 237 %
}

\led@warn@SeriesStillExist38 \newcommand{\led@warn@SeriesStillExist}[1]{%
 239   \reledmac@warning{Series #1 is still existing !}%
 240 }%
 241 %
}

\led@err@BadAction42 \newcommand*{\led@err@StanzaIndentNotDefined}{%
 243   \reledmac@error{You have not defined the indentation for the line \number
 244   \stanza@count}{\@ehc}}%
 244 %

\led@err@ManySidenotes45 \newcommand{\led@err@ManySidenotes}{%
\led@err@ManyLeftnotes46   \ifledRcol@%
\led@err@ManyRightnotes47     \reledmac@warning{\itemcount@space sidenotes on line \the\line@numR\
 248   space p. \the\page@numR}%
 248   \else%
 249     \reledmac@warning{\itemcount@space sidenotes on line \the\line@num\
 249   space p. \the\page@num}%
 250   \fi%
 251 }%
 252 \newcommand{\led@err@ManyLeftnotes}{%
 253   \ifledRcol@%
 254     \reledmac@warning{\itemcount@space leftnotes on line \the\line@numR\
 254   space p. \the\page@numR}%
 255   \else%
 256     \reledmac@warning{\itemcount@space leftnotes on line \the\line@num\
 256   space p. \the\page@num}%
 257   \fi%
 258 }%
 259 \newcommand{\led@err@ManyRightnotes}{%
 260   \ifledRcol@%
 261     \reledmac@warning{\itemcount@space rightnotes on line \the\line@numR\
 261   space p. \the\page@numR}%
 262   \else%
 263     \reledmac@warning{\itemcount@space rightnotes on line \the\line@num\
 263   space p. \the\page@num}%
 264   \fi%
 265 }%
 266 %

\led@err@TooManyColumns67 \newcommand*{\led@err@TooManyColumns}{%
\led@err@UnequalColumns68   \reledmac@error{Too many columns}{\@ehc}%
\led@err@LowStartColumn
\led@err@HighEndColumn
\led@err@ReverseColumns

```

```

269 \newcommand*{\led@err@UnequalColumns}{%
270   \reledmac@error{Number of columns is not equal to the number
271   in the previous row (or \protect\\ \space forgotten?)}{\%
272   @ehc}}
273 \newcommand*{\led@err@LowStartColumn}{%
274   \reledmac@error{Start column is too low}{\@ehc}}
275 \newcommand*{\led@err@HighEndColumn}{%
276   \reledmac@error{End column is too high}{\@ehc}}
277 \newcommand*{\led@err@ReverseColumns}{%
278   \reledmac@error{Start column is greater than end column}{\@ehc}}
279 %

```

```

\led@err@toendnotes@outsidenumbering79 \newcommand{\led@err@toendnotes@outsidenumbering}{%
280   \reledmac@error{\string\toendnotes\space and related commands must be
281   called inside a numbered texte (\string\beginnumbering\space ... \space\string
282   \endnumbering)}{\@ehc}%
283 }%
284 %

```

```

\led@err@EdtextWithoutFootnote83 \newcommand{\led@err@EdtextWithoutFootnote}{%
284   \reledmac@error{edtext without Xfootnote. Check syntax}{\@ehc}%
285 }%
286 %

```

```

\led@err@FootnoteNotInSecondArgEdtext87 \newcommand{\led@err@FootnoteNotInSecondArgEdtext}[1]{%
288   \reledmac@error{#1 footnote outside of the second argument of an edtext.
289   Check syntax}{\@ehc}%
290 }%
291 %

```

```

\led@error@PackageAfterEledmac91 \newcommand{\led@error@PackageAfterEledmac}[1]{%
292   \reledmac@error{#1 must be loaded before reledmac}{\@ehc}%
293 }%
294 %

```

```

\led@error@fail@patch@@makecol95 \newcommand{\led@error@fail@patch@@makecol}{%
296   \reledmac@error{Fail to patch \string\@makecol\space command}{\@ehc}%
297 }%
298 %

```

```

\led@error@fail@patch@@reinserts99 \newcommand{\led@error@fail@patch@@reinserts}{%
300   \reledmac@error{Fail to patch \string\@reinserts\space command}{\@ehc}%
301 }%
302 %

```

```
r@fail@patch@@docclearpage03 \newcommand{\led@error@fail@patch@@docclearpage}{%
 304   \reledmac@error{Fail to patch \string\@docclearpage\space command}{\@ehc}%
 305 }%
 306 %
 307 %

r@fail@patch@@iiiminipage07 \newcommand{\led@error@fail@patch@@iiiminipage}{%
 308   \reledmac@error{Fail to patch \string\@iiiminipage\space command}{\@ehc}%
 309 }%
 310 %

or@fail@patch@endminipage11 \newcommand{\led@error@fail@patch@endminipage}{%
 312   \reledmac@error{Failed to patch the \string\endminipage\space command}{\%
 313   \@ehc}%
 314 }%
 315 %

or@fail@patch@endminipage15 \newcommand{\led@error@fail@patch@makeindex}{%
 316   \reledmac@error{Failed to patch the \string\makeindex\space command}{\%
 317   \@ehc}%
 318 }%
 319 %

n@edinde@outsidenumbering19 \newcommand{\led@warn@edinde@outsidenumbering}{%
 320   \reledmac@warning{\string\edindex\space called outside of \string\
 321   beginnumbering\space ... \space \string\endnumbering. \MessageBreak
 322   Automatically switched to \string\index.}%
 323 }%
 324 %

warning@hsizeX@deprecated23 \newcommand{\led@warning@hsizeX@deprecated}{%
 324   \reledmac@warning{\string\hsizeX\space command deprecated, use \string\
 325   widthX\space instead.}%
 326 }%
 327 %

warning@Xhsize@deprecated27 \newcommand{\led@warning@Xhsize@deprecated}{%
 328   \reledmac@warning{\string\Xhsize\space command deprecated, use \string\
 329   Xwidth\space instead.}%
 330 }%
 331 %
```

```
\led@warning@msdatawithoutstop31 \newcommand{\led@warning@msdatawithoutstop}{%
332   \reledmac@warning{\string\msdata\space without corresponding \string\stopmsdata}%
333 }%
334 %
```

```
\led@warning@preXnotes@deprecated35 \newcommand{\led@warning@preXnotes@deprecated}{%
336   \reledmac@warning@preXnotes@deprecated%
337 }%
338 %
```

II.8 Gobbling

Here, we define some commands which gobble their arguments.

```
\@gobblethree39 \providecommand*\{@gobblethree}[3]{}
\@gobblefour40 \providecommand*\{@gobblefour}[4]{}
\@gobbleseven41 \providecommand*\{@gobbleseven}[7]{}
342 %
```

II.9 Wrapping content

The `\l@wrap@ifnotemptybox` macro wraps its second argument in the command passed as the first argument, but only if the second argument does not produce an empty box. That is useful for example when we need to wrap something on a `\textsuperscript`.

Indeed `a\textsuperscript{}b` does not produce the same typographical result as `ab`.²⁶ The `\l@wrapcs@ifnotemptybox` does the same, but take as argument a control sequence name, so without backslash.

```
343 \newcommand{\l@wrap@ifnotemptybox}[2]{%
344   \setbox0=\hbox{\#2}%
345   \ifdim\wd0=\z@\else%
346     #1{\#2}%
347   \fi%
348 }%
349 \newcommand{\l@wrapcs@ifnotemptybox}[2]{%
350   \l@wrap@ifnotemptybox{\csname #1\endcsname}{\#2}%
351 }%
352 %
```

²⁶Compare the distance between letters in the first case (ab) and in the second one (ab).

II.10 Miscellaneous commands

`\showlemma` `\showlemma{<lemma>}` typesets the lemma text in the body. It depends on the option.

```
353 \iffilefinal
354   \newcommand*{\showlemma}[1]{#1}
355 \else
356   \newcommand*{\showlemma}[1]{\underline{#1}}
357 \fi
358 %
359 %
```

\linenumberlist The code for the \linenumberlist mechanism was given to Peter Wilson by Wayne Sullivan on 2004/02/11.

Initialize it as \empty.

```
360 \let\linenumberlist=\emptyset  
361  
362 %
```

\@1@dttempcnta In imitation of L^AT_EX, we create a couple of scratch counters.

`\@l@dtmpcntb` L^AT_EX already defines `\@tempcnta` and `\@tempcntb` but Peter Wilson found in the past that it can be dangerous to use these (for example one of the AMS packages did something nasty to the `ccaption` package's use of one of these).

363 \newcount\@l@dtmcnta \newcount\@l@dtmcntb
364 %

II.11 Prepare reledpar

\ifl@dpairing
\ifl@dpage In preparation for the `reledpar` package, these are related to the ‘right’ text of parallel texts (when `\ifl@dpairing` is TRUE). They are explained in the `reledpar` manual.

```
\ifl@dprintingpages  
\ifl@dprintingcolumns 365 \newif\ifl@dpairing  
          \ifpst@rtedL 366 \newif\ifl@dpaging%  
  \l@dnumpstartsL 367 \newif\ifl@dprintingpages%  
  368 \newif\ifl@dprintingcolumns%  
  369 \newif\ifpst@rtedL  
  370 \newcount\l@dnumpstartsL  
  371 %
```

`\ifiledRcol` \ifiledRcol is set to true in the Rightside environnement. It must be not confused with `\ifiledRcol@` which is set to true when a right line is processed, in `\Pages` or `\Columns`.

```
372 \newif\ifledRcol  
373 \newif\ifledRcol@  
374 %
```

`\ifnumberingR` The `\ifnumberingR` flag is set to true if we're within a right text numbered section.

```
375 \newif\ifnumberingR
376 %
```

`\ifafterendnumberingR` The `\ifafterendnumberingR` boolean is set to TRUE at `\endnumberingR` and to FALSE at next `\beginnumberingR` or real `\beginnumbering` (not `\resumenumbering`). It is mainly used for the `continuousnumberingwithcolumns`, to avoid incrementing right column line counters after a `\endnumberingR`.

```
377 \newif\ifafterendnumberingR%
378 %
```

The `\ifXnote@` macro is set to true when we are typesetting a critical footnote.

```
379 \newif\ifXnote@%
380 %
```

II.12 Booleans provided by other optional packages which are required in any case

`\ifindtl@innote` The `\ifindtl@innote` and `\ifindtl@notenumber` are required even if `indextools` is not used.

```
381 \providebool{indtl@innote}%
382 \providebool{indtl@notenumber}%
383 %
```

III Sectioning commands

`\section@num` You use `\beginnumbering` and `\endnumbering` to begin and end a line-numbered section of the text; the pair of commands may be used as many times as you like within one document to start and end multiple, separately line-numbered sections. L^AT_EX will maintain and display a ‘section number’ as a count named `\section@num` that counts how many `\beginnumbering` and `\resumenumbering` commands have appeared; it need not be related to the logical divisions of your text.

`\extensionchars` Each section will read and write an associated ‘line-list file’, containing information used to do the numbering; the file will be called `<jobname>.nn`, where `nn` is the section number. However, you may direct that an extra string be added before the `nn` in that filename, in order to distinguish these temporary files from others: that string is called `\extensionchars`. Initially it’s empty, since different operating systems have greatly varying ideas about what characters are permitted in file names. So `\renewcommand{\extensionchars}{-}` gives temporary files called `jobname.-1`, `jobname.-2`, etc.

```

384 \newcount\section@num
385 \section@num=0
386 \let\extensionchars=\empty
387 %

```

\ifnumbering The `\ifnumbering` flag is set to true if we are within a numbered section (that is, between `\beginnumbering` and `\endnumbering`). You can use `\ifnumbering` in your own code to check whether you are in a numbered section, but do not change the flag's value.

```

388 \newif\ifnumbering
389 %

```

\beginnumbering `\beginnumbering` begins a section of numbered text. When it is executed we increment the section number, initialize our counters, send a message to your terminal, and call macros to start the lineation machinery and endnote files.

The initializations here are trickier than they look. `\line@list@stuff` will use all of the counters that are zeroed here when it assembles the line-list and other lists of information about the lineation. But it will do all of this locally and within a group, and when it is done the lists will remain but the counters will return to zero. Those same counters will then be used as we process the text of this section, but the assignments will be made globally. These initializations actually apply to both uses, though in all other respects there should be no direct interaction between the use of these counters and variables in the two processing steps. For parallel processing :

- zero `\l@dnumpstartsL` — the number of chunks to be processed.
- set `\ifpst@rtedL` to FALSE.

```

390 \newcommand*{\beginnumbering}{%
391   \ifnumbering
392     \led@err@NumberingStarted
393     \endnumbering
394   \fi
395   \global\numberingtrue
396   \global\afterendnumberingRfalse%
397   \global\advance\section@num \cne
398   \initnumbering@reg
399   \message{Section \the\section@num }%
400   \line@list@stuff{\jobname.\extensionchars\the\section@num}%
401   \ifcontinuousnumberingwithcolumns%
402     \unless\ifafterendnumberingR%
403       \unless\ifl@dpairing%
404         \ledRcoltrue%
405         \global\advance\section@numR \cne%
406         \message{Section \the\section@numR R (continuousnumbering)}%
407         \line@list@stuffR{\jobname.\extensionchars\the\section@numR R}%
408       \ledRcolfalse%
409     \fi%

```

```

410   \fi%
411   \fi%
412   \l@dend@stuff
413   \setcounter{pstart}{1}
414   \ifl@dpairing
415     \global\l@dnumpstartsL \z@%
416     \global\pst@rtdLfalse
417 %

```

The tools for section's title commands are called:

- Define an empty list of pstart number where sectioning commands are called.
- Input auxiliary file with the description of section titles.
- Open the same auxiliary file to write in.

```

418 \else
419   \begingroup
420   \global\@afterindenttrue%In order to reestablish normal feature if the \
421   begingroup was not here
422   \initnumbering@quote
423   \ifwidthliketwocolumns%
424     \setwidthliketwocolumns%
425     \csuse{setpositionliketwocolumns@\columns@position}%
426   \fi%
427   \gdef\eled@sections@@{}%
428   \if@noeled@sec\else%
429     \makeatletter%
430     \InputIfFileExists%
431       {\l@auxdir\jobname.eledsec\the\section@num}%
432       {}%
433       {\l@warn@NoFile{\l@auxdir\jobname.eledsec\the\section@num}}%
434     \makeatother%
435     \immediate\openout\eled@sectioning@out=\l@auxdir\jobname.eledsec\the\
436     section@num\relax%
437   \fi%
438 }
439 \newcommand*{\initnumbering@reg}{%
440   \global\pst@rtdLfalse
441   \global\l@dnumpstartsL \z@%
442   \global\absline@num \z@%
443   \gdef\normal@page@break{}%
444   \gdef\l@prev@pb{}%
445   \gdef\l@prev@nompb{}%
446   \global\line@num \z@%
447   \global\subline@num \z@%
448   \global\@clock \z@%
449   \global\sub@clock \z@%
450   \global\sublines@false

```

```

450 \global\let\next@page@num=\relax
451 \global\let\sub@change=\relax
452 \global\last@page@num=-10000%
453 \ifdefined\line@numR%
454   \line@numR=\z@%
455   \last@page@numR=\z@%
456 \fi%
457 \resetprevline@
458 \resetprevpage@num
459 \global\stopmsdata@inserted@true%
460 \global\let\@msdata@list\relax%
461 \global\csundef{\@msdata@\add@msd@c @data}%
462 }
463 %
464 %

```

`\endnumbering` `\endnumbering` must follow the last text for a numbered section. It takes care of notifying you when changes have been noted in the input that require running the file through again to move everything to the right place. We define it using `\def` and not `\newcommand` because L^AT_EX does not allow defining command whose name starts by “end” except if we are currently creating an environment, which is not the case here.

```

465 \def\endnumbering{%
466   \ifnumbering
467     \global\numberingfalse
468     \normalpars
469     \ifnum\l@dnumptstartsL=0%
470       \led@err@NumberingWithoutPstart%
471     \fi%
472     \ifl@dpairing
473       \global\pst@rtedLfalse
474     \else
475       \ifx\insertlines@list\empty\else
476         \global\noteschanged@true
477       \fi
478       \ifx\line@list\empty\else
479         \global\noteschanged@true
480       \fi
481     \fi
482     \ifnoteschanged@
483       \led@mess@NotesChanged
484     \fi
485   \else
486     \led@err@NumberingNotStarted
487   \fi
488   \autoparfalse
489   \if@noeled@sec\else%
490     \immediate\closeout\eled@sectioning@out%
491   \fi%
492   \ifl@dpairing\else

```

```

493   \global\l@dnumpstartsL=\z@%
494   \endgroup
495   \fi
496 }
497 %

```

\pausenumbering
 \resumenumbering
 \ifresumenumbering@start
 \pausenumbering@page@num

The \pausenumbering macro is just the same as \endnumbering, but with the \ifnumbering flag set to true, to show that numbering continues across the gap.²⁷ The \pausenumbering@page@num counter stores the \next@page@num when the \pause@numbering is called.

```

498 \newcount\pausenumbering@page@num%
499 \newcommand{\pausenumbering}{%
500   \ifx\next@page@num\relax%
501     \global\pausenumbering@page@num=0%
502   \else%
503     \global\pausenumbering@page@num=\next@page@num%
504   \fi%
505   \ifautopar\global\autopar@pausetrue\fi%
506   \endnumbering\global\numberingtrue}
507 %

```

The \resumenumbering macro is a bit more involved, but not much. It does most of the same things as \beginnumbering, but without resetting the various counters. Note that no check is made by \resumenumbering to ensure that \pausenumbering was actually invoked. The boolean \ifresumenumbering@start is set to true. That allows us to avoid resetting the line number at the first line of \resumenumbering if the lineation is by page. This boolean is set to false after the first action.

```

508 \newif\ifresumenumbering@start%
509 \newcommand*{\resumenumbering}{%
510   \ifnumbering
511     \ifautopar@pause\autopar\fi
512     \global\pst@rtedLtrue
513     \global\advance\section@num \cne
514     \global\resumenumbering@starttrue%
515     \led@mess@sectionContinued{\the\section@num}%
516     \set@continuousnumberingforL%
517     \line@list@stuff{\jobname.\extensionchars\the\section@num}%
518     \ifcontinuousnumberingwithcolumns%
519       \unless\ifafterendnumberingR%
520         \unless\ifl@dpairing%
521           \ledRcoltrue%
522           \global\advance\section@numR \cne%
523           \message{Section \the\section@numR R (continuousnumbering)}%
524           \line@list@stuffR{\jobname.\extensionchars\the\section@numR}%
525           \ledRcolfalse%
526     \fi%

```

²⁷Peter Wilson's thanks to Wayne Sullivan, who suggested the idea behind these macros.

```

527     \fi%
528     \fi%
529     \l@dend@stuff
530     \ifl@dpairing\else%
531         \begingroup%
532             \initnumbering@quote%
533             \ifwidthliketwocolumns%
534                 \setwidthliketwocolumns%
535                 \csuse{setpositionliketwocolumns@\columns@position}%
536             \fi%
537         \fi%
538     \else
539         \led@err@NumberingShouldHaveStarted
540         \endnumbering
541         \beginnumbering
542     \fi}
543
544
545 %

```

`t@continuousnumberingforL` `\set@continuousnumberingforl` sets pstart counters at a `\beginnumbering` or a `\resumenumbering` in order to have continuous numbering with single column text.

```

546 \newcommand{\set@continuousnumberingforL}{%
547     \ifcontinuousnumberingwithcolumns%
548         \ifl@dpairing%
549             \unless\ifl@dpaging%
550                 \global\c@pstartL=\c@pstart%
551             \fi%
552         \fi%
553     \fi%
554 }%
555 %

```

IV List macros

We will make heavy use of lists of information, which will be built up and taken apart by the following macros; they are adapted from *The TeXbook*, pp. 378–379, which discusses their use in more detail.

These macros consume a large amount of the run-time of this code. We intend to replace them in a future version, and in anticipation of doing so have defined their interface in such a way that it is not sensitive to details of the underlying code.

The historical list tools of `ledmac` are kept, because in many cases there are more useful than `etoolbox`'s lists. They allow to get and delete the first element of a list in one operation. They also expands the items add to the list.

However, `etoolbox`'s lists are more useful to loop on them. Consequently, depending of what we need, we use one or either.

It could be nice to unify them to the L^AT_EX3 list, however such migration would take quite time with some risk of error, for a gain which will be minor.

- \list@create** The `\list@create` macro creates a new list. This macro does not do anything beyond initializing an empty list macro.

```
556 \newcommand*{\list@create}[1]{%
557   \global\let#1=\emptyset%
558 }%
559 %
```

- \list@clear** The `\list@clear` macro just initializes a list to the empty list; it is no different from `\list@create` in its effect, but it is in its semantic .

```
560 \newcommand*{\list@clear}[1]{%
561   \global\let#1=\emptyset%
562 }%
563 %
```

- \xright@appenditem** `\xright@appenditem` expands an item and appends it to the right end of a list macro.
\led@toksa We want the expansion because we will often be using this to store the current value
\led@toksb of a counter. `\xright@appenditem` creates global control sequences, like `\xdef`, and uses two temporary token-list registers, `\@toksa` and `\@toksb`.

```
564 \newtoks\led@toksa \newtoks\led@toksb
565 \global\led@toksa={\}
566 \long\def\xright@appenditem#1\to#2{%
567   \global\led@toksb=\expandafter{#2}%
568   \xdef#2{\the\led@toksb\the\led@toksa\expandafter{#1}}%
569   \global\led@toksb={}%
570 }%
```

- \xleft@appenditem** `\xleft@appenditem` expands an item and appends it to the left end of a list macro; it is otherwise identical to `\xright@appenditem`.

```
571 \long\def\xleft@appenditem#1\to#2{%
572   \global\led@toksb=\expandafter{#2}%
573   \xdef#2{\the\led@toksa\expandafter{#1}\the\led@toksb}%
574   \global\led@toksb={}%
575 }%
```

- \g1@p** The `\g1@p` macro removes the leftmost item from a list and places it in a control sequence. You type `\g1@p\l\to\z` (where `\l` is the list macro, and `\z` receives the left item). `\l` is assumed nonempty:use `\ifx\l\empty` to test for an empty `\l`. The control sequences created by `\g1@p` are all global.

```
576 \def\g1@p#1\to#2{\expandafter\g1@poff#1\g1@poff#1#2}
577 \long\def\g1@poff\#1#2\g1@poff\#3#4{\gdef\#4{\#1}\gdef\#3{\#2}}
578 %
579 %
```

V Line counting

V.1 Choosing the system of lineation

Line number can be reset at each section (default) ; at each page ; at each pstart. Here we define internal codes for these systems and the macros.

\ifbypstart@ The \ifbypage@ and \ifbypstart@ flag specifie the current lineation system:
\bystart@true
\bystart@false • line-of-page: bystart@ = false and bypage@ = true.
\ifbypage@ • line-of-pstart: bystart@ = true and bypage@ = false.
\bypage@true
\bypage@false reledmac will use the line-of-section system unless instructed otherwise.

```
580 \newif\ifbypage@  
581 \newif\ifbypstart@  
582 %
```

The \ifbypage@R and \ifbypstart@R flag specifie the current lineation for right side in case of using reledpar. They are now defined because they are used in some specific code. reledpar will use the line-of-section system unless instructed otherwise.

```
\ifbypage@R83 \newif\ifbypage@R  
\ifbypstart@R84 \newif\ifbypstart@R  
585 %
```

\lineation \lineation{<word>} is the macro you use to select the lineation system. Its argument is a string: either page, section or pstart.

```
586 \newcommand*{\lineation}[1]{  
587 %
```

We can't change the lineation system inside numbering section.

```
588 \ifnumbering  
589     \led@err@LineationInNumbered  
590 \else  
591 %
```

If the argument is page.

```
592 \def\@tempa{\#1}\def\@tempb{page}%
593 \ifx\@tempa\@tempb
594     \global\bypage@true
595     \global\bystart@false
596     \unless\ifnocritical@%
597         \Xpstart[] [false]%
598     \fi%
599 %
```

If the argument is pstart.

```

600   \else
601     \def\@tempb{pstart}%
602     \ifx\@tempa\@tempb
603       \global\bypage@false
604       \global\bypstart@true
605       \unless\ifnocritical@%
606         \Xpstart%
607       \fi%
608 %

```

And finally, if the argument is `section` (default).

```

609   \else
610     \def\@tempb{section}
611     \ifx\@tempa\@tempb
612       \global\bypage@false
613       \global\bypstart@false
614       \unless\ifnocritical@%
615         \Xpstart[] [false]%
616       \fi%
617 %

```

In other case, it is an error.

```

618   \else
619     \led@warn@BadLineation
620   \fi
621   \fi
622   \fi}
623 %
624 %

```

V.2 Line number margin

`\linenummargin` specify which margin line numbers are in; it takes one argument, a string, which value can be `left`; `right`; `inner` or `outer`.
`\l@dgepline@margin` The selection is recorded in the count `\line@margin`: 0 for left, 1 for right, 2 for outer, and 3 for inner.

```

625 \newcount\line@margin%
626 \newcount\line@margin@columns%Only for parallel typesetting
627 \line@margin@columns=\m@ne%
628
629 \newcommand*{\linenummargin}[1]{%
630   \l@dgepline@margin{\#1}%
631   \ifnum\@l@dtmcntb>\m@ne
632     \ifledRcol
633       \global\line@marginR=\@l@dtmcntb
634       \led@warn@setting@in@rightside{\linenummargin}%
635     \else
636       \global\line@margin=\@l@dtmcntb

```

```

637     \fi
638   \fi}
639
640 \newcommand*{\l@dgepline@margin}[1]{%
641   \def\@tempa{\#1}\def\@tempb{left}%
642   \ifx\@tempa\@tempb
643     \l@dgeplinecntb \z@
644   \else
645     \def\@tempb{right}%
646   \ifx\@tempa\@tempb
647     \l@dgeplinecntb \cne
648   \else
649     \def\@tempb{outer}%
650   \ifx\@tempa\@tempb
651     \l@dgeplinecntb \tw@
652   \else
653     \def\@tempb{inner}%
654   \ifx\@tempa\@tempb
655     \l@dgeplinecntb \thr@@
656   \else
657     \l@warn@BadLinenummargin
658     \l@dgeplinecntb \m@cne
659   \fi
660   \fi
661   \fi
662 }
663 %

```

V.3 Line number initialization and increment

`\c@firstlinenum` The following counters tell `reledmac` which lines should be printed with line numbers. `firstlinenum` is the number of the first line in each section that gets a number; `linenumincrement` is the difference between successive numbered lines. The initial values of these counters produce labels on lines 5, 10, 15, etc. `linenumincrement` must be at least 1.

```

665 \newcounter{firstlinenum}
666   \setcounter{firstlinenum}{5}
667 \newcounter{linenumincrement}
668   \setcounter{linenumincrement}{5}
669 %

```

`\c@firstsublinenum` The following parameters are just like `firstlinenum` and `linenumincrement`, but for sub-line numbers. `sublinenumincrement` must be at least 1.

```

670 \newcounter{firstsublinenum}
671   \setcounter{firstsublinenum}{5}
672 \newcounter{sublinenumincrement}

```

```

673 \setcounter{sublinenumincrement}{5}
674 %
675 %

```

```

\firstlinenum
\linenumincrement
676 \firstsublinenum
677 \sublinenumincrement
678
679 \newcommand*{\firstlinenum}[1]{%
680   \ifledRcol%
681     \setcounter{firstlinenumR}{#1}%
682     \led@warn@setting@in@rightside{\firstlinenum}%
683   \else%
684     \setcounter{firstlinenum}{#1}%
685   \fi%
686 }
687 \newcommand*{\linenumincrement}[1]{%
688   \ifledRcol%
689     \setcounter{linenumincrementR}{#1}%
690     \led@warn@setting@in@rightside{\linenumincrement}%
691   \else%
692     \setcounter{linenumincrement}{#1}%
693   \fi%
694 }
695 \newcommand*{\firstsublinenum}[1]{%
696   \ifledRcol%
697     \setcounter{firstsublinenumR}{#1}%
698     \led@warn@setting@in@rightside{\firstsublinenum}%
699   \else%
700     \setcounter{firstsublinenum}{#1}%
701   \fi%
702 }
703 \newcommand*{\sublinenumincrement}[1]{%
704   \ifledRcol%
705     \setcounter{sublinenumincrementR}{#1}%
706     \led@warn@setting@in@rightside{\sublinenumincrement}%
707   \else%
708     \setcounter{sublinenumincrement}{#1}%
709   \fi%
710 }

```

V.4 Line number locking

`\lockdisp` When line locking is being used, the `\lockdisp{<word>}` macro specifies whether a line number—if one is due to appear—should be printed on the first printed line or on the last, or by all of them. Its argument is a word, either `first`, `last`, or `all`. Initially, it is set to `first`.

`\lock@disp` encodes the selection: 0 for `first`, 1 for `last`, 2 for `all`.

```

711 \newcount\lock@disp
712 \newcommand{\lockdisp}[1]{{%
713   \l@dge@lock@disp{#1}%
714   \ifnum\l@dtmpcntb>\m@ne
715     \global\lock@disp=\l@dtmpcntb
716   \else
717     \led@warn@BadLockdisp
718   \fi}%
719 \newcommand*\l@dge@lock@disp[1]{%
720   \def\@tempa{#1}\def\@tempb{first}%
721   \ifx\@tempa\@tempb
722     \l@dtmpcntb \z@
723   \else
724     \def\@tempb{last}%
725     \ifx\@tempa\@tempb
726       \l@dtmpcntb \one
727     \else
728       \def\@tempb{all}%
729       \ifx\@tempa\@tempb
730         \l@dtmpcntb \tw@
731       \else
732         \l@dtmpcntb \m@ne
733       \fi
734     \fi
735   \fi}
736 %
737 %

```

`\sublockdisp` The same questions about where to print the line number apply to sub-lines, and these
`\sublock@disp` are the analogous macros for dealing with the problem.

```

738 \newcount\sublock@disp
739 \newcommand{\sublockdisp}[1]{{%
740   \l@dge@lock@disp{#1}%
741   \ifnum\l@dtmpcntb>\m@ne
742     \global\sublock@disp=\l@dtmpcntb
743   \else
744     \led@warn@BadSublockdisp
745   \fi}%
746 %
747 %

```

V.5 Line number style

`\linenumberstyle` We provide a mechanism for using different representations of the line numbers, not just the normal arabic.

`\linenumrep` NOTE: In v0.7 `\linenumrep` and `\sublinenumrep` replaced the internal `\linenumr@p`

`\sublinenumberstyle` and `\sublinenumr@p`.

`\sublinenumrep`
`\sublinenumr@p`

\linenumberstyle and \sublinenumberstyle are user level macros for setting the number representation (\linenumrep and \sublinenumrep) for line and sub-line numbers.

```

748 \newcommand*{\linenumberstyle}[1]{%
749   \def\linenumrep##1{\@nameuse{@#1}{##1}}%
750 \newcommand*{\sublinenumberstyle}[1]{%
751   \def\sublinenumrep##1{\@nameuse{@#1}{##1}}%
752 %

```

Initialise the number styles to arabic.

```

753 \linenumberstyle{arabic}
754   \let\linenumr@p\linenumrep
755 \sublinenumberstyle{arabic}
756   \let\sublinenumr@p\sublinenumrep
757 %
758 %

```

V.6 Line number printing

\leftlinenum and \rightlinenum are the macros that are called to print marginal line numbers on a page, for left- and right-hand margins respectively. They are made easy to access and change, since you may want to change the styling in some way. These standard versions illustrate the general sort of thing that will be needed; they are based on the \leftheadline macro in *The TeXbook*, p. 416.

Whatever these macros output gets printed in a box that will be put into the appropriate margin without any space between it and the line of text. You will generally want a kern between a line number and the text, and \linenumsep is provided as a standard way of storing its size. Line numbers are usually printed in a smaller font, and \numlabfont is provided as a standard name for that font. When called, these macros will be executed within a group, so font changes and the like will remain local.

\ledlinenum typesets the line (and subline) number.

The original \numlabfont specification is equivalent to the L^AT_EX \scriptsize for a 10pt document.

```

759 \newlength{\linenumsep}
760   \setlength{\linenumsep}{1pc}
761 \newcommand*{\numlabfont}{\normalfont\scriptsize}
762 \newcommand*{\ledlinenum}{%
763   \bgroup%
764   \ifluatex%
765     \textdir TLT%
766   \fi%
767   \numlabfont%
768   \ifdefstring{\Xlinenumannotationposition@side}{before}{%
769     \l@wrap@ifemptybox{\Xwraplinenumannotation@side}{%
770       \csuse{annot@\the\absline@num @\the\section@num}%
771       }%
772   }%

```

```

773   \linenumrep{\line@num}%
774   \ifsblines@
775     \ifnum\sbline@num>0\relax
776       \unskip%
777       \Xsblinesep@side%
778       \sblinenumrep{\sbline@num}%
779     \fi
780   \fi%
781   \ifdefstring{\Xlinenumannotationposition@side}{after}{%
782     \l@wrap@ifemptybox{\Xwraplinenumannotation@side}{%
783       \csuse{annot@\the\absline@num @\the\section@num}%
784     }%
785   }{%
786     \egroup%
787   }%
788   \newcommand*{\leftlinenum}{%
789     \ledlinenum
790     \kern\linenumsep}
792   \newcommand*{\rightlinenum}{%
793     \kern\linenumsep
794     \ledlinenum}
795   %
796 %

```

V.7 Line number counters and lists

Footnote references using line numbers rather than symbols can't be generated in one pass, because we do not know the line numbers till we ship out the pages. It would be possible if footnotes were never keyed to more than one line; but some footnotes gloss passages that may run for several lines, and they must be tied to the first line of the passage glossed. And even one-line passages require two passes if we want line-per-page numbering rather than line-per-section numbering.

So we run LATEX over the text several times, and each time save information about page and line numbers in a ‘line-list file’ to be used during the next pass. At the start of each section—whenever `\beginnumbering` is executed—the line-list file for that section is read, and the information from it is encoded into a few list macros.

We need first to define the different line numbers that are involved in these macros, and the associated counters.

`\line@num` The count `\line@num` stores the line number that is used in marginal line numbering and in notes: counting either by section, page or pstart, depending on your choice for this section. This may be qualified by `\sbline@num`.

```

797 \newcount\line@num
798 %

```

`\subline@num` The count `\subline@num` stores a sub-line number that qualifies `\line@num`. For example, line 10 might have sub-line numbers 1, 2 and 3, which might be printed as lines 10.1, 10.2, 10.3.

```
799 \newcount\subline@num
800 %
```

`\ifsublines@` We maintain an associated flag, `\ifsublines@`, to tell us whether we're within a sub-line range or not.

`\sublines@true` You may wonder why we do not just use the value of `\subline@num` to determine this—treating anything greater than 0 as an indication that sub-lineation is on. We need a separate flag because sub-lineation can be used together with line-number locking in odd ways: several pieces of a logical line might be interrupted by pieces of sub-lineated text, and those sub-line numbers should not return to zero until the next change in the major line number. This is common in the typesetting of English Renaissance verse drama, in which stage directions are given sub-line numbers: a single line of verse may be interrupted by several stage directions.

```
801 \newif\ifsublines@
802 %
```

`\absline@num` The count `\absline@num` stores the absolute number of lines since the start of the section: that is, the number we have actually printed, no matter what numbers we attached to them. This value is never printed on an output page, though `\line@num` will often be equal to it. It is used internally to keep track of where notes are to appear and where new pages start: using this value rather than `\line@num` is a lot simpler, because it does not depend on the lineation system in use.

```
803 \newcount\absline@num
804 %
```

We will call `\absline@num` numbers “absolute” numbers, and `\line@num` and `\subline@num` numbers “visible” numbers.

V.8 Line number locking counter

`\@lock` The counts `\@lock` and `\sub@lock` tell us the state of line-number and sub-line-number locking. 0 means we are not within a locked set of lines; 1 means we are at the first line in the set; 2, at some intermediate line; and 3, at the last line.

```
805 \newcount\@lock
806 \newcount\sub@lock
807 %
```

V.9 Line number associated to lemma

`\line@list` Now we can define the list of macros which will be created from the line-list file. We
`\insertlines@list` will maintain the following lists:
`\actionlines@list`
`\actions@list`
`\annot@list`

- `\line@list`: the page and line numbers for every lemma marked by `\edtext`. There are seven pieces of information, separated by vertical bars:

1. the starting page,
2. line, and
3. sub-line numbers, followed by the
4. ending page,
5. line, and
6. sub-line numbers, and then the
7. font specifier for the lemma.

These line numbers are all visible numbers. The font specifier is a set of four codes for font encoding, family, series, and shape, separated by / characters. Thus a lemma that started on page 23, line 35 and went on until page 24, line 3 (with no sub-line numbering), and was typeset in a normal roman font would have a line list entry like this:

`23|35|0|24|3|0|0T1/cmr/m/n.`

There is one item in this list for every lemma marked by `\edtext`, even if there are several notes to that lemma, or no notes at all. `\edtext` reads the data in this list, making it available for use in the text of notes.

- `\insertlines@list`: the line numbers of lines that have footnotes or other insertions. These are the absolute numbers where the corresponding lemmas begin. This list contains one entry for every footnote in the section; one lemma may contribute no footnotes or many footnotes. This list is used by `\add@inserts` within `\do@line`, to tell it where to insert notes.
- `\actionlines@list`: a list of absolute line numbers at which we are to perform special actions; these actions are specified by the `\actions@list` list defined below.
- `\actions@list`: action codes corresponding to the line numbers in `\actionlines@list`. These codes tell `reledmac` what action it is supposed to take at each of these lines. One action, the page-start action, is generated behind the scenes by `reledmac` itself; the others, for specifying sub-lineation, line-number locking, and line-number alteration, are generated only by explicit commands in your input file. The page-start and line-number-alteration actions require arguments, to specify the new values for the page or line numbers; instead of storing those arguments in another list, we have chosen the action-code values so that they can encode both the action and the argument in these cases. Action codes greater than -1000 are page-start actions, and the code value is the page number; action codes less than -5000 specify line numbers, and the code value is a transformed version of the line number; action codes between these two values specify other actions which require no argument.

Here is the full list of action codes and their meanings:

Any number greater than -1000 is a page-start action: the line number associated with it is the first line on a page, and the action number is the page number. (The cutoff of -1000 is chosen because negative page-number values are used by some

macro packages; we assume that page-number values less than -1000 are not common.) Page-start action codes are added to the list by the `\page@action` macro, which is (indirectly) triggered by the workings of the `\page@start` macro; that macro should always be called in the output routine, just before the page contents are assembled. `Eledmac` calls it in `\pagecontents`.

The action code -1001 specifies the start of sub-lineation: meaning that, starting with the next line, we should be advancing `\subline@num` at each start-of-line command, rather than `\line@num`.

The action code -1002 specifies the end of sub-lineation. At the next start-of-line, we should clear the sub-line counter and start advancing the line number. The action codes for starting and ending sub-lineation are added to the list by the `\sub@action` macro, as called to implement the `\startsub` and `\endsub` macros.

The action code -1003 specifies the start of line number locking. After the number for the current line is computed, it will remain at that value through the next line that has an action code to end locking.

The action code -1004 specifies the end of line number locking.

The action code -1005 specifies the start of sub-line number locking. After the number for the current sub-line is computed, it will remain at that value through the next sub-line that has an action code to end locking.

The action code -1006 specifies the end of sub-line number locking.

The four action codes for line and sub-line number locking are added to the list by the `\do@lockon` and `\do@lockoff` macros, as called to implement the `\startlock` and `\endlock` macros.

An action code of -5000 or less sets the current visible line number (either the line number or the sub-line number, whichever is currently being advanced) to a specific positive value. The value of the code is $-(5000 + n)$, where n is the value (always ≥ 0) assigned to the current line number. Action codes of this type are added to the list by the `\set@line@action` macro, as called to implement the `\advanceline` and `\setline` macros: this action only occurs when the user has specified some change to the line numbers using those macros. Normally `reledmac` computes the visible line numbers from the absolute line numbers with reference to the other action codes and the settings they invoke; it does not require an entry in the action-code list for every line.

- `\annot@list` stores line number annotations for the start and the end lines of each `\edtext`, as `\line@list` does for line numbers. We don't store that in the same list as line numbers as `\printlines` already have height arguments, and a `TeX` macro can take at most nine arguments.

Here are the commands to create these lists:

```
808 \list@create{\line@list}
809 \list@create{\insertlines@list}
810 \list@create{\actionlines@list}
```

```

811 \list@create{\actions@list}
812 \list@create{\annot@list}%
813 %

```

\page@num We will need some counts while we read the line-list, for the page number and the ending page, line, and sub-line numbers. Some of these will be used again later on, when we are acting on the data in our list macros.

```

\endsubline@num
814 \newcount\page@num
815 \newcount\endpage@num
816 \newcount\endline@num
817 \newcount\endsubline@num
818 %

```

\ifnoteschanged@ If the number of the footnotes in a section is different from what it was during the last run, or if this is the very first time you've run L^AT_EX, on this file, the information from the line-list used to place the notes will be wrong, and some notes will probably be misplaced. When this happens, we prefer to give a single error message for the whole section rather than messages at every point where we notice the problem, because we do not really know where in the section notes were added or removed, and the solution in any case is simply to run L^AT_EX two more times; there is no fix needed to the document. The \ifnoteschanged@ flag is set if such a change in the number of notes is discovered at any point.

```

819 \newif\ifnoteschanged@
820 %

```

\resetprevline@ Inside the apparatus, at each note, the line number is stored in a macro called \prevlineX, where X is the letter of the current series. This macro is called when using \Xnumberonlyfirstinline. This macro must be reset at the same time as the line number. The \resetprevline@ does this resetting for every series.

```

\resetprevline@{ \newcommand*{\resetprevline@}{%
822   \def\do##1{\global\csundef{prevline##1}}%
823   \dolistloop{\@series}%
824 }
825 %

```

\resetprevpage@num Inside the apparatus, at each note, the page number is stored in a macro called \prevpageX@num, where X is the letter of the current series. This macro is called when using \Xparafootsep or \parafootsepX. This macro must be reset at the beginning of each numbered section. The \resetprevpage@ command resets this macro for every series.

```

\resetprevpage@{ \newcommand*{\resetprevpage@}{%
827   \def\do##1{%
828     \ifcsdef{prevpage##1@num}{%

```

```

829   \global\csname prevpage##1@num\endcsname=\z@%
830   \global\csname prevpage##1@numR\endcsname=\z@%
831   }%
832   {}%
833   \ifcsdef{##1prevpage@num}{%
834     \global\csname ##1prevpage@num\endcsname=\z@%
835     \global\csname ##1prevpage@numR\endcsname=\z@%
836   }%
837   {}%
838   }%
839   \dolistloop{\@series}%
840 }
841 %

```

V.10 Reading the line-list file

`\read@linelist` `\read@linelist{\langle file\rangle}` is the control sequence that is called by `\beginnumbering` (via `\line@list@stuff`) to open and process a line-list file; its argument is the name of the file. . First, it clear all previous line's list.

```

842 \newread\@inputcheck
843 \newcommand*{\read@linelist}[1]{%
844   \ifledRcol%
845     \list@clearing@regR%
846   \else%
847     \list@clearing@reg%
848   \fi%
849 %

```

When using `reledpar`, make sure that the `\maxlinesinpar@list` is empty (otherwise things will be thrown out of kilter if there is any old stuff still hanging in there).

```

850   \list@clear{\maxlinesinpar@list}
851 %

```

Now get the file and interpret it. When the file is there we start a new group and make some special definitions we will need to process it. It is a sequence of `\TeX` commands, but they require a few special settings. We make [and] become grouping characters: they are used that way in the line-list file, because we need to write them out one at a time rather than in balanced pairs, and it is easier to just use something other than real braces. @ must become a letter, since this is run in the ordinary `\LaTeX` context. We ignore carriage returns, since if we are in horizontal mode they can get interpreted as spaces to be printed.

Our line, page, and line-locking counters were already zeroed by `\line@list@stuff` if this is being called from within `\beginnumbering`; sub-lineation will be turned off as well in that case. On the other hand, if this is being called from `\resumenumbering`, those things should still have the values they had when `\pausenumbering` was executed.

If the file is not there, we print an informative message.

Now, after these preliminaries, we start interpreting the file.

```

852   \get@linelistfile{#1}%
853   \@stopmsd%Security if last \endms{} is forgotten
854   \unless\ifledRcol%Get the last line of the last page
855     \csnumgdef{@lastabsline@forpage@{\the\page@num}}{\the\absline@num}%
856     \csnumgdef{@lastline@forpage@{\the\page@num}}{\the\line@num}%
857   \else%
858     \csnumgdef{@lastabsline@forpageR@{\the\page@numR}}{\the\absline@numR}%
859     \csnumgdef{@lastline@forpageR@{\the\page@numR}}{\the\line@numR}%
860   \fi%
861   \endgroup
862 %

```

When the reading is done, we are all through with the line-list file. All the information we needed from it will now be encoded in our list macros.

Finally, we initialize the `\next@actionline` and `\next@action` macros, which specify where and what the next action to be taken is.

```

863 \ifledRcol
864   \global\page@numR=\m@ne
865   \ifx\actionlines@listR\empty
866     \gdef\next@actionlineR{1000000}%
867   \else
868     \gl@p\actionlines@listR\to\next@actionlineR
869     \gl@p\actions@listR\to\next@actionR
870   \fi
871 \else
872   \global\page@num=\m@ne
873   \ifx\actionlines@list\empty
874     \gdef\next@actionline{1000000}%
875   \else
876     \gl@p\actionlines@list\to\next@actionline
877     \gl@p\actions@list\to\next@action
878   \fi
879 \fi
880 }
881 %

```

`\list@clearing@reg` Clears the lists for `\read@linelist`

```

882 \newcommand*{\list@clearing@reg}{%
883   \list@clear{\line@list}%
884   \list@clear{\insertlines@list}%
885   \list@clear{\actionlines@list}%
886   \list@clear{\actions@list}%
887   \list@clear{\linesinpar@listL}%
888   \list@clear{\linesonpage@listL}%
889 }%
890 %

```

`\get@linelistfile` reledmac can take advantage of the L^AT_EX ‘safe file input’ macros to get the line-list file.

```

891 \newcommand*{\get@linelistfile}[1]{%
892   \InputIfFileExists{\l@auxdir#1}{%
893     \global\noteschanged@false
894     \begingroup
895       \catcode`\\=1 \catcode`\\=2
896       \makeatletter \catcode`\\^M=9}{%
897         \led@warn@NoFile{\l@auxdir#1}%
898         \global\noteschanged@true
899         \begingroup}%
900   }
901 %
902 %

```

This version of `\read@linelist` creates list macros containing data for the entire section, so they could get rather large. It would be no more difficult to read the line-list file incrementally rather than all at once: we could read, at the start of each paragraph, only the commands relating to that paragraph. But this would require that we have two line-lists open at once, one for reading, one for writing, and on systems without version numbers we would have to do some file renaming outside of L^AT_EX for that to work. We have retained this slower approach to avoid that sort of hacking about, but have provided the `\pausenumbering` and `\resumenumbers` macros to help you if you run into macro memory limitations (see 5.2.7 p. 20 above).

V.11 Commands within the line-list file

This section defines the commands that can appear within a line-list file. They all have very short names because we are likely to be writing very large numbers of them out. One macro, `\@nl`, is especially short, since it will be written to the line-list file once for every line of text in a numbered section. (Another of these commands, `\@lab`, will be introduced in a later section, among the cross-referencing commands it is associated with.)

When these commands modify the various page and line counters, they deliberately do not use `\global`. This is because we want them to affect only the counter values within the current group when nested calls of `\@ref` occur. (The code assumes throughout that the value of `\globaldefs` is zero.)

The macros with `action` in their names contain all the code that modifies the action-code list: again, this is so that they can be turned off easily for nested calls of `\@ref`.

`\line@list@version` The `\line@list@version` check if the line-list file does not refer to the older commands of `reledmac`. In this case, we stop reading the line-list file. Consequently, `\line@list@version` must be the first line of a line-number file.

```

903 \newcommand{\line@list@version}[1]{%
904   \IfStrEq{#1}{\this@line@list@version}%
905   {}%
906   {\ifledRcol%
907     \led@warn@Obsolete{\jobname.\extensionchars\the\section@num}%
908   \else%

```

```

909     \led@warn@Obsolete{\jobname.\extensionchars\the\section@num}%
910     \fi%
911     \endinput%
912   }%
913 }%
914 %

```

\@nl \@nl does everything related to the start of a new line of numbered text.

\@nl@reg In order to get the \setlinenum to work Peter Wilson had to slip in some new code at the start of the macro, to get the timing of the actions correct. The problem was that his original naive implementation of \setlinenum had a unfortunate tendency to change the number of the last line of the *preceding* paragraph. The new code is sort of based on the page number handling and \setline. It seems that a lot of fiddling with the line number internals is required.

In November 2004 in order to accurately determine page numbers Peter Wilson added these to the macro. It is now:

\@nl{\⟨page counter number⟩}{⟨printed page number⟩}

We do not (yet) use the printed number (i.e., the \thepage) but it may come in handy later. The macro \fix@page checks if a new page has started.

Exactly what \@nl does depends on whether right text is being processed. That's why many code is defined in \@nl@reg or \nl@regR.

```

915
916 \newcommand*{\@nl}[2]{%
917   \fix@page{#1}%
918   \ifldRcol%
919     \@nl@regR%
920   \else%
921     \@nl@reg%
922   \fi%
923 }
924 \newcommand*{\@nl@reg}{%
925   \ifx\l@dchset@num\relax \else
926     \reset@current@annot%
927     \advance\absline@num \c@ne
928     \csgdef{\l@dchset@num@{\the\absline@num}}{}%To remember this line have
been marked by a \setlinenum
929     \set@line@action
930     \let\l@dchset@num=\relax
931     \advance\absline@num \m@ne
932     \advance\line@num \m@ne
933   \fi
934 %

```

First increment the absolute line-number, and perform deferred actions relating to page starts and sub-lines.

```

935   \advance\absline@num \c@ne
936   \ifx\next@page@num\relax \else
937     \page@action

```

```

938     \let\next@page@num=\relax
939     \fi
940     \ifx\sub@change\relax \else
941         \ifnum\sub@change>\z@
942             \sublines@true
943         \else
944             \sublines@false
945         \fi
946         \sub@action
947         \let\sub@change=\relax
948     \fi
949 %

```

Fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

950     \ifcase\@lock
951         \or
952             \@lock \tw@
953         \or \or
954             \@lock \z@
955         \fi
956     \ifcase\sub@lock
957         \or
958             \sub@lock \tw@
959         \or \or
960             \sub@lock \z@
961     \fi
962 %

```

Now advance the visible line number, unless it has been locked.

```

963     \ifsublines@%
964         \ifnum\sub@lock<\tw@
965             \advance\subline@num \cne
966         \fi
967     \else
968         \ifnum\@clock<\tw@
969             \advance\line@num \cne \subline@num \z@
970         \fi
971     \fi}
972 %
973 %

```

\last@page@num \fix@page basically replaces \@page. It determines whether or not a new page has been started, based on the page values held by \@nl.

```

974 \newcount\last@page@num
975 \last@page@num=-10000
976
977 \newcommand*{\fix@page}[1]{%
978     \ifledRcol

```

```

979   \ifnum #1=\last@page@numR
980   \else
981     \csnumgdef{@lastabsline@forpage@{\the\page@numR}{\the\absline@numR}%
982     \csnumgdef{@lastline@forpage@{\the\page@numR}{\the\line@numR}%
983     \ifbypage@R
984       \ifx\l@dchset@num\relax%Not resetting if preceded by a \setlinenum
985         \ifboolexpr{%
986           bool{resumenumeratingR@start}%
987           and test {\ifnumequal{\last@page@numR}{-10000}}%
988         }%
989         {}%
990         {}%
991         \line@numR \z@%
992         \subline@numR \z@%
993         \global\csdef{reset@lineR}{\numexpr\absline@numR+1\relax @\%
994         the\section@numR}%
995         }%
996         \fi%
997         \global\page@numR=#1%
998         \global\last@page@numR=#1%
999         \global\def\next@page@numR{#1}%
1000         \fi
1001     \else
1002       \ifnum #1=\last@page@num
1003       \else
1004         \csnumgdef{@lastabsline@forpage@{\the\page@num}{\the\absline@num}%
1005         \csnumgdef{@lastline@forpage@{\the\page@num}{\the\line@num}%
1006         \ifbypage@R
1007           \ifx\l@dchset@num\relax%Not resetting if preceded by a \setlinenum
1008             \line@num \z@ \subline@num \z@%
1009             \global\csdef{reset@line}{\numexpr\absline@num+1\relax @\the\
1010             section@num}%
1011             \fi%
1012             \global\page@num=#1%
1013             \global\last@page@num=#1%
1014             \global\def\next@page@num{#1}%
1015             \listxadd{\normal@page@break}{\the\absline@num}
1016             \fi
1017           \fi}
1018 %

```

\@pend These do not do anything at this point, but will have been added to the auxiliary file(s)
 \@pendR if the reledpar package has been used. They are just here to stop reledmac from
 \@lopL moaning if the reledpar is used for one run and then not for the following one.
 \@lopR

```

1019 \newcommand*{\@pend}[1]{}
1020 \newcommand*{\@pendR}[1]{}
1021 \newcommand*{\@lopL}[1]{}

```

```

1022 \newcommand*{\@lopR}[1]{}
1023 %
1024 %

```

\sub@on The `\sub@on` and `\sub@off` macros turn sub-lineation on and off: but not directly, since such changes do not really take effect until the next line of text. Instead they set a flag that notifies `\@nl` of the necessary action.

```

1025 \newcommand*{\sub@on}{\ifsublines@%
1026   \let\sub@change=\relax
1027   \else
1028     \def\sub@change{1}%
1029   \fi}
1030 \newcommand*{\sub@off}{\ifsublines@%
1031   \def\sub@change{-1}%
1032   \else
1033     \let\sub@change=\relax
1034   \fi}
1035 %
1036 %

```

\@adv The `\@adv{<num>}` macro advances the current visible line number by the amount specified as its argument. This is used to implement `\advanceline`.

```

1037 \newcommand*{\@adv}[1]{%
1038   \ifsublines@%
1039     \ifledRcol
1040       \advance\subline@numR by #1\relax
1041       \ifnum\subline@numR<\z@
1042         \led@warn@BadAdvancelineSubline
1043         \subline@numR \z@
1044       \fi
1045     \else
1046       \advance\subline@num by #1\relax
1047       \ifnum\subline@num<\z@
1048         \led@warn@BadAdvancelineSubline
1049         \subline@num \z@
1050       \fi
1051     \fi
1052   \fi
1053 \else
1054   \ifledRcol
1055     \advance\line@numR by #1\relax
1056     \ifnum\line@numR<\z@
1057       \led@warn@BadAdvancelineLine
1058       \line@numR \z@
1059     \fi
1060   \else
1061     \advance\line@num by #1\relax
1062     \ifnum\line@num<\z@

```

```

1063           \led@warn@BadAdvanceLineLine
1064           \line@num \z@
1065       \fi
1066   \fi
1067 \fi
1068 \set@line@action}
1069 %
1070 %

```

\@set The `\@set{<num>}` macro sets the current visible line number to the value specified as its argument. This is used to implement `\setline`.

```

1071 \newcommand*{\@set}[1]{%
1072     \ifledRcol
1073         \ifsblines@
1074             \subline@numR=#1\relax
1075         \else
1076             \line@numR=#1\relax
1077         \fi
1078         \set@line@action
1079     \else
1080         \ifsblines@
1081             \subline@num=#1\relax
1082         \else
1083             \line@num=#1\relax
1084         \fi
1085         \set@line@action
1086     \fi}
1087 %
1088 %
1089 %

```

\l@d@set The `\l@d@set{<num>}` macro sets the line number for the next `\pstart` to the value `\l@dchset@num` specified as its argument. This is used to implement `\setlinenum`.

`\l@dchset@num` is a flag to the `\@nl?` macro. If it is not `\relax` then a linenumber change is to be done.

```

1090 \newcommand*{\l@d@set}[1]{%
1091     \ifledRcol
1092         \line@numR=#1\relax
1093         \advance\line@numR \@ne
1094         \def\l@dchset@num{\#1}
1095     \else
1096         \line@num=#1\relax
1097         \advance\line@num \@ne
1098         \def\l@dchset@num{\#1}
1099     \fi}
1100 \let\l@dchset@num\relax
1101 %
1102 %

```

1103 %

\page@action \page@action adds an entry to the action-code list to change the page number.

```

1104
1105 \newcommand*{\page@action}{%
1106   \ifledRcol
1107     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1108     \xright@appenditem{\next@page@numR}\to\actions@listR
1109   \else
1110     \xright@appenditem{\the\absline@num}\to\actionlines@list
1111     \xright@appenditem{\next@page@num}\to\actions@list
1112   \fi
1113 %

```

\set@line@action \set@line@action adds an entry to the action-code list to change the visible line number.

```

1114
1115 \newcommand*{\set@line@action}{%
1116   \ifledRcol
1117     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1118     \ifsblines@
1119       \@l@dtempcnta=-\subline@numR
1120     \else
1121       \@l@dtempcnta=-\line@numR
1122     \fi
1123     \advance\@l@dtempcnta by -5000\relax
1124     \xright@appenditem{\the\@l@dtempcnta}\to\actions@listR
1125   \else
1126     \xright@appenditem{\the\absline@num}\to\actionlines@list
1127     \ifsblines@
1128       \@l@dtempcnta=-\subline@num
1129     \else
1130       \@l@dtempcnta=-\line@num
1131     \fi
1132     \advance\@l@dtempcnta by -5000\relax
1133     \xright@appenditem{\the\@l@dtempcnta}\to\actions@list
1134   \fi
1135 %

```

\sub@action \sub@action adds an entry to the action-code list to turn sub-lineation on or off, according to the current value of the \ifsblines@ flag.

```

1136
1137 \newcommand*{\sub@action}{%
1138   \ifledRcol
1139     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1140     \ifsblines@
1141       \xright@appenditem{-1001}\to\actions@listR

```

```

1142     \else
1143         \xright@appenditem{-1002}\to\actions@listR
1144     \fi
1145 \else
1146     \xright@appenditem{\the\absline@num}\to\actionlines@list
1147 \ifsublines@
1148     \xright@appenditem{-1001}\to\actions@list
1149 \else
1150     \xright@appenditem{-1002}\to\actions@list
1151     \fi
1152 \fi}
1153 %

```

`\lock@on` `\lock@on` adds an entry to the action-code list to turn line number locking on. The `\do@clockon` current setting of the sub-lineation flag tells us whether this applies to line numbers or `\do@lockonL` sub-line numbers.

Adding commands to the action list is slow, and it is very often the case that a lock-on command is immediately followed by a lock-off command in the line-list file, and therefore really does nothing. We use a look-ahead scheme here to detect such pairs, and add nothing to the line-list in those cases.

```

1154 \newcommand*{\lock@on}{\futurelet\next\do@lockon}
1155
1156 \newcommand*{\do@lockon}{%
1157     \ifx\next\lock@off
1158         \global\let\lock@off=\skip@lockoff
1159     \else
1160         \ifledRcol
1161             \do@lockonR
1162         \else
1163             \do@lockonL
1164         \fi
1165     \fi}
1166
1167
1168 \newcommand*{\do@lockonL}{%
1169     \xright@appenditem{\the\absline@num}\to\actionlines@list
1170 \ifsublines@
1171     \xright@appenditem{-1005}\to\actions@list
1172     \ifnum\sub@clock=\z@
1173         \sub@clock \@ne
1174     \else
1175         \ifnum\sub@clock=\thr@@
1176             \sub@clock \@ne
1177         \fi
1178     \fi
1179 \else
1180     \xright@appenditem{-1003}\to\actions@list
1181     \ifnum\@clock=\z@

```

```

1182     \@clock \@ne
1183   \else
1184     \ifnum\@clock=\thr@@
1185       \@clock \@ne
1186     \fi
1187   \fi
1188 \fi}
1189 %
1190 %

\lock@off \lock@off adds an entry to the action-code list to turn line number locking off.
\do@lockoff
\do@lockoffL
\skip@lockoff
1191 \newcommand*{\do@lockoffL}{%
1192   \xright@appenditem{\the\absline@num}\to\actionlines@list
1193   \ifsublines@
1194     \xright@appenditem{-1006}\to\actions@list
1195     \ifnum\sub@lock=\tw@
1196       \sub@lock \thr@@
1197     \else
1198       \sub@lock \z@%
1199     \fi
1200   \else
1201     \xright@appenditem{-1004}\to\actions@list
1202     \ifnum\@clock=\tw@
1203       \@clock \thr@@
1204     \else
1205       \@clock \z@%
1206     \fi
1207   \fi}
1208 %
1209 \newcommand*{\do@lockoff}{%
1210   \reset@current@annot%
1211   \ifledRcol
1212     \do@lockoffR
1213   \else
1214     \do@lockoffL
1215   \fi}
1216 \newcommand*{\skip@lockoff}{\global\let\lock@off=\do@lockoff}
1217 \global\let\lock@off=\do@lockoff
1218 %
1219 %

```

\n@num These macros implement the \skipnumbering command. They use action code 1007.

```

1220 \newcommand*{\n@num}{%
1221   \ifledRcol%
1222     \xright@appenditem{\the\absline@numR}\to\actionlines@listR
1223     \xright@appenditem{-1007}\to\actions@listR
1224   \else%

```

```

1225      \xright@appenditem{\the\absline@num}\to\actionlines@list%
1226      \xright@appenditem{-1007}\to\actions@list%
1227      \fi%
1228  }%
1229 %
1230 %

```

`\n@num@stanza` This macro implements the `\skipnumbering` for stanza command. It uses action code 1008.

```

1231 \newcommand*{\n@num@stanza}{%
1232     \ifledRcol%
1233         \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1234         \xright@appenditem{-1008}\to\actions@listR%
1235     \else%
1236         \xright@appenditem{\the\absline@num}\to\actionlines@list%%
1237         \xright@appenditem{-1008}\to\actions@list%
1238     \fi%
1239 }
1240 %

```

`\ifl@dhidenumber` `\hidenumbering` `\hidenumbering` hides number in margin. It uses action code 1009. `\hidenumberingonleftpage` and `\hidenumberingonrightpage` are variants, using action code only conditionally

```

\hidenumberingonleftpage
\hidenumberingonrightpage41 \newif\ifl@dhidenumber
1242 \newcommand*{\hidenumbering}{%
1243     \ifledRcol%
1244         \write\linenum@outR{\string\hide@num}%
1245     \else%
1246         \write\linenum@out{\string\hide@num}%
1247     \fi%
1248 }%
1249 \newcommand*{\hide@num}{%
1250     \ifledRcol%
1251         \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1252         \xright@appenditem{-1009}\to\actions@listR%
1253     \else%
1254         \xright@appenditem{\the\absline@num}\to\actionlines@list%%
1255         \xright@appenditem{-1009}\to\actions@list%
1256     \fi%
1257 }
1258 \newcommand*{\hidenumberingonleftpage}{%
1259     \ifledRcol%
1260         \write\linenum@outR{\string\hide@num@left}%
1261     \else%
1262         \write\linenum@out{\string\hide@num@left}%
1263     \fi%
1264 }%
1265

```

```

1266 \newcommand*{\hide@num@left}{%
1267   \ifledRcol%
1268     \ifodd\page@numR\else%
1269       \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1270       \xright@appenditem{-1009}\to\actions@listR%
1271     \fi%
1272   \else%
1273     \ifodd\page@num\else%
1274       \xright@appenditem{\the\absline@num}\to\actionlines@list%%
1275       \xright@appenditem{-1009}\to\actions@list%
1276     \fi%
1277   \fi%
1278 }%
1279
1280 \newcommand*{\hidenumberingonrightpage}{%
1281   \ifledRcol%
1282     \write\linenum@outR{\string\hide@num@right}%
1283   \else%
1284     \write\linenum@out{\string\hide@num@right}%
1285   \fi%
1286 }%
1287
1288 \newcommand*{\hide@num@right}{%
1289   \ifledRcol%
1290     \ifodd\page@numR%
1291       \xright@appenditem{\the\absline@numR}\to\actionlines@listR%
1292       \xright@appenditem{-1009}\to\actions@listR%
1293     \fi%
1294   \else%
1295     \ifodd\page@num%
1296       \xright@appenditem{\the\absline@num}\to\actionlines@list%%
1297       \xright@appenditem{-1009}\to\actions@list%
1298     \fi%
1299   \fi%
1300 }%
1301
1302 %

```

\@ref \@ref marks the start of a passage, for creation of a footnote reference. It takes two arguments:

- #1, the number of entries to add to \insertlines@list for this reference. This value, here and within \edtext, which computes it and writes it to the line-list file, will be stored in the count \insert@count.

```

1303 \newcount\insert@count
1304 %

```

- #2, a sequence of other line-list-file commands, executed to determine the ending line-number. (This may also include other \@ref commands, corresponding to

uses of \edtext within the first argument of another instance of \edtext.)

\dummy@ref When nesting of \eref commands does occur, it is necessary to temporarily redefine \eref within \eref, so that we are only doing one of these at a time.

```
1305 \newcommand*{\dummy@ref}[2]{#2}
1306 %
```

\eref@reg The first thing \eref (i.e. \eref@reg) itself does is to add the specified number of items to the \insertlines@list list.

```
1307 \newcommand*{\eref}[2]{%
1308   \ifledRcol%
1309     \eref@regR{#1}{#2}%
1310   \else%
1311     \eref@reg{#1}{#2}%
1312   \fi%
1313 }%
1314 \newcommand*{\eref@reg}[2]{%
1315   \global\insert@count=#1\relax
1316   \global\advance\@edtext@level by 1%
1317   \loop\ifnum\insert@count>\z@
1318     \xright@appenditem{\the\absline@num}\to\insertlines@list
1319     \global\advance\insert@count \m@ne
1320   \repeat
1321 %
```

Next, process the second argument to determine the page and line numbers for the end of this lemma. We temporarily equate \eref to a different macro that just executes its argument, so that nested \eref commands are just skipped this time. Some other macros need to be temporarily redefined to suppress their action.

```
1322 \begingroup
1323   \let\eref=\dummy@ref
1324   \let\@lopL\gobble
1325   \let\page@action=\relax
1326   \let\sub@action=\relax
1327   \let\set@line@action=\relax
1328   \let\@lab=\relax
1329   \let\@lemma=\relax%
1330   \let\@sw\gobblethree%
1331   \let\store@annot@to@absline\gobble%
1332   #2
1333   \global\endpage@num=\page@num
1334   \global\endline@num=\line@num
1335   \global\endsubline@num=\subline@num
1336   \global\let\endcurrent@annot=\current@annot%
1337 \endgroup
1338 %
```

Now store all the information about the location of the lemma's start and end in \line@list.

```

1339 \xright@appenditem%
1340   {\the\page@num|\the\line@num|%
1341     \ifsublines@ \the\subline@num \else 0\fi|%
1342     \the\endpage@num|\the\endline@num|%
1343     \ifsublines@ \the\endsubline@num \else 0\fi}\to\line@list
1344 \xright@appenditem%
1345   {\current@annot|\endcurrent@annot}\to\annot@list%
1346 %

```

And now, call `\@ref@reg@parsearg`, which can be also called by `\@ref@later`

```

1347 \@ref@reg@parse{\#2}%
1348 %

```

Decrease edtext level counter.

```

1349 \global\advance\@edtext@level by -1%
1350 }
1351 %

```

\@ref@reg@parse The `\@ref@reg@parsearg` command parses the second argument of a `\@ref` or the unique argument of `\@ref@later` written in the auxiliary fill.

First, create a list which stores every second argument of each `\@sw` in this lemma, at this level. Also set the boolean about the use of lemma in this edtext level to false.

```

1352 \newcommand{\@ref@reg@parse}[1]{%
1353   \expandafter\list@create\expandafter{\csname sw@list@edtext@tmp@\the\
1354   @edtext@level\endcsname}%
1355   \providebool{lemmacommand@\the\@edtext@level}%
1356   \boolfalse{lemmacommand@\the\@edtext@level}%
1357 %

```

Execute the second argument of `\@ref` again, to perform for real all the commands within it.

```

1357 #1%
1358 %

```

Now, we store the list of `\@sw` of this current `\@edtext` as an element of the global list of list of `\@sw` for a `\@edtext` depth.

```

1359 \ifnum\@edtext@level>0%
1360   \def\create@this@edtext@level{\expandafter\list@create\expandafter{\
1361   \csname sw@list@edtext@\the\@edtext@level\endcsname}%
1362   \ifcsundef{sw@list@edtext@\the\@edtext@level}{\create@this@edtext@level
1363   }{}%
1364   \letcs{\@tmp}{sw@list@edtext@\the\@edtext@level}%
1365   \letcs{\@tmp}{sw@list@edtext@tmp@\the\@edtext@level}%
1366   \xright@appenditem{\expandonce{\@tmp}\to\@tmp}%
1367   \global\cslet{sw@list@edtext@\the\@edtext@level}{\@tmp}%
1368   \fi%
1369 %

```

```
1368 }
1369 %
1370 %
```

\ref@reg@later This macro is stored in the auxiliary file when using \edtextlater. It is used only to get the correct value for the \sameword tools.

```
1371 \newcommand{\@ref@later}[1]{%
1372   \global\advance\@edtext@level by \cne%
1373   \ifledRcol%
1374     \@ref@reg@parseR{#1}%
1375   \else%
1376     \@ref@reg@parse{#1}%
1377   \fi%
1378   \global\advance\@edtext@level by -\cne%
1379 }%
1380 %
```

V.12 Writing to the line-list file

We have now defined all the counters, lists, and commands involved in reading the line-list file at the start of a section. Now we will cover the commands that reledmac uses within the text of a section to write commands out to the line-list.

\linenum@out The file will be opened on output stream \linenum@out.

```
1381 \newwrite\linenum@out
1382 %
```

\iffirst@linenum@out@ Once any file is opened on this stream, we keep it open forever, or else switch to another file that we keep open. The reason is that we want the output routine to write the page number for every page to this file; otherwise we would have to write it at the start of every line. But it is not very easy for the output routine to tell whether an output stream is open or not. There is no way to test the status of a particular output stream directly, and the asynchronous nature of output routines makes the status hard to determine by other means.

We can manage pretty well by means of the \iffirst@linenum@out@ flag; its inelegant name suggests the nature of the problem that made its creation necessary. It is set to be true before any \linenum@out file is opened. When such a file is opened for the first time, it is done using \immediate, so that it will at once be safe for the output routine to write to it; we then set this flag to false.

```
1383 \newif\iffirst@linenum@out@
1384   \first@linenum@out@true
1385 %
```

\this@line@list@version The commands allowed in the line-list file and their arguments can change between two version of reledmac. The \this@line@list@version command is upgraded when

it happens. It is written in the file list. If we process a line-list file which used a older version, that means the commands used inside are deprecated, and we can't use them.

```
1386 \newcommand{\this@line@list@version}{7}%
1387 %
```

\line@list@stuff The \line@list@stuff{<file>} macro, which is called by \beginnumbering, performs all the line-list operations needed at the start of a section. Its argument is the name of the line-list file.

```
1388 \let\next@line@list@stuff\relax%
1389 \newcommand*{\line@list@stuff}[1]{%
1390 %
```

First, define a toggle set to true when we are not in the first run.

```
1391 \global\newtoggle{notfirstrun@\#1}%
1392 \IfExists{l@auxdir@\#1}%
1393   {\global\toggletrue{notfirstrun@\#1}%
1394   {\global\togglefalse{notfirstrun@\#1}}%
1395 %
```

A internal hook (not used yet).

```
1396 \next@line@list@stuff%
1397 \global\let\next@line@list@stuff\relax%
1398 %
```

Use the commands of the previous section to interpret the line-list file from the last run.

```
1399 \read@linelist{\#1}%
1400 %
```

Now close the current output line-list file, if any, and open a new one. The first time we open a line-list file for output, we do it using \immediate, and clear the \iffirst@linenum@out@ flag. reledmac and reledpar can fill the \next@line@list@stuff hook between a \endnumbering (associated with numbered file n) and a \beginnumbering (associated with numbered file $n + 1$). It allows adding content to the numbered file $n + 1$ and not n .

```
1401 \iffirst@linenum@out@
1402   \global\first@linenum@out@false%
1403   \immediate\openout\linenum@out=\l@auxdir@\#1\relax%
1404   \immediate\write\linenum@out{\string\line@list@version{\%
1405     this@line@list@version}}%
1406   \ifl@dpaging%
1407     \immediate\write\linenum@out{\string\@par@sync@option{\%
1408       @par@this@sync@option}}%
1409     \fi%
1410   \else
1411   %
```

If we get here, then this is not the first line-list we have seen, so we do not open or close the files immediately.

```

1410     \if@minipage%
1411         \leavevmode%
1412     \fi%
1413     \closeout\linenum@out%
1414     \openout\linenum@out=\l@auxdir#1\relax%
1415     \write\linenum@out{\string\line@list@version{\this@line@list@version}}
%
1416     \ifl@dpaging%
1417         \write\linenum@out{\string\@par@sync@option{\@par@this@sync@option}}
%
1418     \fi%
1419     \fi%
1420 }%
1421 %
1422 %

```

\new@line The `\new@line` macro sends the `\@nl` command to the line-list file, to mark the start of a new text line, and its page number.

```

1423 \newcommand*{\new@line}{%
1424     \IfStrEq{\led@pb@setting}{after}%
1425         {\xifinlist{\the\absline@num}{\l@prev@nopb}%
1426          {\xifinlist{\the\absline@num}{\normal@page@break}%
1427             {\numgdef{\@next@page}{\c@page+\@ne}%
1428              \write\linenum@out{\string\@nl[\@next@page] [\@next@page]}%
1429            }%
1430            {\write\linenum@out{\string\@nl[\the\c@page] [\thepage]}%
1431            }%
1432            {\write\linenum@out{\string\@nl[\the\c@page] [\thepage]}%
1433            }%
1434     \IfStrEq{\led@pb@setting}{before}%
1435         {\numdef{\next@absline}{\the\absline@num+\@ne}%
1436         \xifinlist{\next@absline}{\l@prev@nopb}%
1437             {\xifinlist{\the\absline@num}{\normal@page@break}%
1438                 {\numgdef{\nc@page}{\c@page+\@ne}%
1439                 \write\linenum@out{\string\@nl[\nc@page] [\nc@page]}%
1440                 }%
1441                 {\write\linenum@out{\string\@nl[\the\c@page] [\thepage]}%
1442                 }%
1443                 {\write\linenum@out{\string\@nl[\the\c@page] [\thepage]}%
1444                 }%
1445                 {\write\linenum@out{\string\@nl[\the\c@page] [\thepage]}%
1446         \IfStrEqCase{\led@pb@setting}{{before}{\relax}{after}{\relax}}{[\write\linenum@out{\string\@nl[\the\c@page] [\thepage]}]}%
1447     }%
1448     %
1449 }

```

\if@noneed@Footnote `\if@noneed@Footnote` is a boolean to check if we have to print a error message when a `\edtext` is called without any critical notes.

`\flag@start` We enclose a lemma marked by `\edtext` in `\flag@start` and `\flag@end`: these send the `\@ref` command to the line-list file. `\edtext` is responsible for setting the value of `\insert@count` appropriately; it actually gets done by the various footnote macros.

```

1450 \newif\if@noneed@Footnote%
1451
1452 \newcommand*{\flag@start}{%
1453   \ifledRcol%
1454     \edef\next{\write\linenum@outR{%
1455       \string\@ref [\the\insert@countR] {}%
1456     }%
1457     \ifnum\insert@countR<1%
1458       \if@noneed@Footnote\else%
1459         \led@err@EdtextWithoutFootnote%
1460       \fi%
1461     \fi%
1462   \else%
1463     \edef\next{\write\linenum@out{%
1464       \string\@ref [\the\insert@count] {}%
1465     }%
1466     \ifnum\insert@count<1%
1467       \if@noneed@Footnote\else%
1468         \led@err@EdtextWithoutFootnote%
1469       \fi%
1470     \fi%
1471   \fi}%
1472
1473 \newcommand*{\flag@end}{%
1474   \ifledRcol%
1475     \write\linenum@outR{}%
1476   \else%
1477     \write\linenum@out{}%
1478   \fi}%
1479
1480 %
1481 %

```

`\flag@start@RTL` With X_ET_EX, there is a problem when using RTL: the writing of a command in the numbered auxiliary files (.1, .2 etc) is reversed when the first argument of `\edtext` is typeset in one line, but it is **not** reversed when this first argument is typeset in two lines or more.²⁸

To solve this problem, we use a crossref mechanism. At the first run, we put a label, but we do not write any `\@ref` command. When the value of the label can be tested, that is after three runs, we're doing:

²⁸This problem is caused by the way X_ET_EX manages right-to-left typesetting. David Carlisle explains it on <http://tex.stackexchange.com/a/333373/7712> and provides a potential solution, using `\vadjust`. However in some cases this adds spurious vertical spaces in reledmac. That is why we are using the solution explained below.

- If the first argument of \edtext is typeset on only one line, we first call \flag@end, at the point we normally call \flag@start, at the beginning of the content of the first argument, and we call \flag@end at the point we normally call \flag@start, at the end of the content of the first argument.
- If the first argument of \edtext is typeset on only two lines, we use the normal order.

This system is a workaround for the problem of order when writing in auxiliary files.

The \flag@start@RTL and \flag@end@RTL macro put the label, do the test and call the right commands.

```

1482 \newcommand{\flag@start@RTL}{%
1483   \edlabel{edtext:start:\csuse{thisedtext@\the\@edtext@level}}%
1484   \IfStrEq{\xabslineref{edtext:start:\csuse{thisedtext@\the\@edtext@level}}}{%
1485     {000}%
1486     {}%
1487     {%
1488       \ifnumequal{%
1489         {\xabslineref{edtext:start:\csuse{thisedtext@\the\@edtext@level}}}{%
1490         {\xabslineref{edtext:end:\csuse{thisedtext@\the\@edtext@level}}}}{%
1491           {\flag@end}%
1492           {\flag@start}%
1493         }%
1494       }%
1495     }%
1496   \newcommand{\flag@end@RTL}{%
1497     \edlabel{edtext:end:\csuse{thisedtext@\the\@edtext@level}}%
1498     \IfStrEq{\xabslineref{edtext:start:\csuse{thisedtext@\the\@edtext@level}}}{%
1499       {000}%
1500       {}%
1501       {%
1502         \ifnumequal{%
1503           {\xabslineref{edtext:start:\csuse{thisedtext@\the\@edtext@level}}}{%
1504           {\xabslineref{edtext:end:\csuse{thisedtext@\the\@edtext@level}}}}{%
1505             {\flag@start}%
1506             {\flag@end}%
1507           }%
1508         }%
1509       }%

```

\flag@start@later \flag@start@later and \flag@end@later: these send the \ref@later to the line-list file command to the line-list file

```

1510 \newcommand*{\flag@start@later}{%
1511   \ifledRcol{%
1512     \write\linenum@outR{\string\@ref@later[]}%
1513   \else%

```

```

1514     \write\linenum@out{\string\@ref@later[]}%
1515     \fi%
1516 }%
1517 \newcommand{\flag@end@later}{%
1518     \ifledRcol%
1519         \write\linenum@outR[]}%
1520     \else%
1521         \write\linenum@out[]}%
1522     \fi%
1523 }
1524 %

```

\startsub **\endsub** **\startsub** and **\endsub** turn sub-lineation on and off, by writing appropriate instructions to the line-list file. When sub-lineation is in effect, the line number counter is frozen and the sub-line counter advances instead. If one of these commands appears in the middle of a line, it does not take effect until the next line; in other words, a line is counted as a line or sub-line depending on what it started out as, even if that changes in the middle.

We tinker with `\lastskip` because a command of either sort really needs to be attached to the last word preceding the change, not the first word that follows the change. This is because sub-lineation will often turn on and off in mid-line—stage directions, for example, often are mixed with dialogue in that way—and when a line is mixed we want to label it using the system that was in effect at its start. But when sub-lineation begins at the very start of a line we have a problem, if we don't put in this code.

```

1525
1526
1527 \newcommand*{\startsub}{\dimen0\lastskip
1528     \ifdim\dimen0>0pt \unskip \fi
1529     \ifledRcol \write\linenum@outR{\string\sub@on}%
1530     \else \write\linenum@out{\string\sub@on}%
1531     \fi
1532     \ifdim\dimen0>0pt \hskip\dimen0 \fi}
1533 \def\endsub{\dimen0\lastskip
1534     \ifdim\dimen0>0pt \unskip \fi
1535     \ifledRcol \write\linenum@outR{\string\sub@off}%
1536     \else \write\linenum@out{\string\sub@off}%
1537     \fi
1538     \ifdim\dimen0>0pt \hskip\dimen0 \fi}
1539 %

```

\advanceline You can use `\advanceline{<num>}` in running text to advance the current visible line-number by a specified value, positive or negative.

```

1541 \newcommand*{\advanceline}[1]{\leavevmode%
1542     \ifledRcol \write\linenum@outR{\string\@adv[#1]}%
1543     \else \write\linenum@out{\string\@adv[#1]}%
1544     \fi%

```

```
1545 }
1546 %
```

\setline You can use `\setline{<num>}` in running text (i.e., within `\pstart...\\pend`) to set the current visible line-number to a specified positive value.

```
1547
1548 \newcommand*{\setline}[1]{%
1549   \leavevmode%
1550   \ifnum#1<\z@%
1551     \led@warn@BadSetline%
1552   \else%
1553     \ifledRcol%
1554       \write\linenum@outR{\string\@set[#1]}%
1555     \else%
1556       \write\linenum@out{\string\@set[#1]}%
1557     \fi%
1558   \fi%
1559 }%
1560 %
1561 %
```

\setlinenum You can use `\setlinenum{<num>}` before a `\pstart` to set the visible line-number to a specified positive value. It writes a `\l@d@set` command to the line-list file.

```
1562
1563 \newcommand*{\setlinenum}[1]{%
1564   \ifnum#1<\z@%
1565     \led@warn@BadSetlinenum%
1566   \else%
1567     \ifledRcol \write\linenum@outR{\string\l@d@set[#1]}%
1568     \else \write\linenum@out{\string\l@d@set[#1]} \fi%
1569   \fi%
1570 %
1571 %
```

\startlock You can use `\startlock` or `\endlock` in running text to start or end line number locking at the current line. They decide whether line numbers or sub-line numbers are affected, depending on the current state of the sub-lineation flags.

```
1572
1573 \newcommand*{\startlock}{%
1574   \ifledRcol \write\linenum@outR{\string\lock@on}%
1575   \else \write\linenum@out{\string\lock@on}%
1576   \fi}
1577 \def\endlock{%
1578   \ifledRcol \write\linenum@outR{\string\lock@off}%
1579   \else \write\linenum@out{\string\lock@off}%
1580   \fi}
1581 %
```

```

\ifl@dskipnumber In numbered text \skipnumbering will suspend the numbering for that particular line.
\ifl@dskipversenumber
\l@dskipnumbertrue1582 \newif\ifl@dskipnumber
\l@dskipnumberfalse1583 \newif\ifl@dskipversenumber%
\skipnumbering1584 \newcommand*\{skipnumbering}{%
  \leavevmode%
  \ifledRcol%
    \ifinstanza%
      \write\linenum@outR{\string\n@num@stanza}%
    \else%
      \write\linenum@outR{\string\n@num}%
    \fi%
    \advanceline{-1}%
  \else%
    \ifinstanza%
      \write\linenum@out{\string\n@num@stanza}%
    \else%
      \write\linenum@out{\string\n@num}%
    \fi%
    \advanceline{-1}%
  \fi%
}
\%1601
\%1602
\%1603

```

VI Marking text for notes

The \edtext macro is used to create all footnotes and endnotes, as well as to print the portion of the main text to which a given note or notes is keyed. The idea is to have that lemma appear only once in the .tex file: all instances of it in the main text and in the notes are copied from that one appearance.

The \edtext macro takes two arguments.

```
\edtext{#1}{#2}
```

- #1 is the piece of the main text being glossed; it gets added to the main text, and is also used as a lemma for notes to it.
- #2 is a series of subsidiary macros that generate various kinds of notes.

The \edtext macro may be used (somewhat) recursively; that is, \edtext may be used within its own first argument. The code would be much simpler without this feature, but nested notes will commonly be necessary: it is quite likely that we will have an explanatory note for a long passage and notes on variants for individual words within that passage. The situation we can't handle is overlapping notes that are not nested: for example, one note covering lines 10–15, and another covering 12–18. You can handle such cases by using the \lemma and \linenum macros within #2: they alter the copy

of the lemma and the line numbers that are passed to the notes, and hence allow you to overcome any limitations of this system, albeit with extra effort.

The recursive operation of \edtext will fail if you try to use a copy that is called something other than \edtext. In order to handle recursion, \edtext needs to redefine its own definition temporarily at one point, and that does not work if the macro you are calling is not actually named \edtext. There is no problem as long as \edtext is not invoked in the first argument. If you want to call \edtext something else, it is best to create instead a macro that expands to an invocation of \edtext, rather than copying \edtext and giving it a new name; otherwise you will need to add an appropriate definition for your new macro to \morenoexpands.

Side-effects of our line-numbering code make it impossible to use the usual footnote macros directly within a paragraph whose lines are numbered (see comments to \do@line, VII.2.1 p. 153). Instead, the appropriate note-generating command is appended to the list macro \inserts@list, and when \pend completes the paragraph it inserts all the notes at the proper places.

Note that we do not provide previous-note information, although it is often wanted; your own macros must handle that. We can not do it correctly without keeping track of what kind of notes have gone past: it is not just a matter of remembering the line numbers associated with the previous invocation of \edtext, because that might have been for a different kind of note. It is preferable for your footnote macros to store and recall this kind of information if they need it.

VI.1 \edtext itself

The various note-generating macros might want to request that commands be executed not at once, but in close connection with the start or end of the lemma. For example, footnote numbers in the text should be connected to the end of the lemma; or, instead of a single macro to create a note listing variants, you might want to use several macros in series to create individual variants, which would each add information to a private macro or token register, which in turn would be formatted and output when all of #2 for the lemma has been read.

\end@lemmas To accommodate this, we provide a list macro to which macros may add commands that should subsequently be executed at the end of the lemma when that lemma is added to the text of the paragraph. A macro should add its contribution to \end@lemmas by using \xleft@appenditem. (Anything that needs to be done at the *start* of the lemma may be handled using \aftergroup, since the commands specified within \edtext's second argument are executed within a group that ends just before the lemma is added to the main text.)

\end@lemmas is intended for the few things that need to be associated with the end of the lemma, like footnote numbers. Such numbers are not implemented in the current version, and indeed no use is currently made of \end@lemmas or of the \aftergroup trick. The general approach would be to define a macro to be used within the second argument of \edtext that would add the appropriate command to \end@lemmas.

Commands that are added to this list should always take care not to do anything that adds possible line-breaks to the output; otherwise line numbering could be thrown off.

```
1604 \list@create{\end@lemmas}
1605 %
```

\dummy@edtext We now need to define a number of macros that allow us to weed out nested instances of `\edtext`, and other problematic macros, from our lemma. This is similar to what we did in reading the line-list file using `\dummy@ref` and various redefinitions—and that is because nested `\edtext`s macros create nested `\@ref` entries in the line-list file.

```
1606 \newcommand{\dummy@edtext}[2]{#1}
1607 %
```

\dummy@edtext@showlemma Some time, we want to obtain only the first argument of `\edtext`, while also wrapping it in `\showlemma`. For example, when printing a `\eledsection`.

```
1608 \newcommand{\dummy@edtext@showlemma}[2]{\showlemma{#1}}%
1609 %
```

We are going to need another macro that takes one argument and ignores it entirely. This is supplied by the L^AT_EX `\gobble{<arg>}`.

\no@expands **\morenoexpands** We need to turn off macro expansion for certain sorts of macros we are likely to see within the lemma and within the notes.

The first class is font-changing macros. We suppress expansion for them by letting them become equal to zero.²⁹ This is done because we want to pass into our notes the generic commands to change to roman or whatever, and not their expansions that will ask for a particular style at a specified size. The notes may well be in a smaller font, so the command should be expanded later, when the note's environment is in effect.

A second sort to turn off includes a few of the accent macros. Most are not a problem: an accent that is expanded to an `\accent` command may be harder to read but it works just the same. The ones that cause problems are: those that use alignments— \TeX seems to get confused about the difference between alignment parameters and macro parameters; those that use temporary control sequences; and those that look carefully at what the current font is.

(The `\copyright` macro defined in PLAIN \TeX has this sort of problem as well, but is not used enough to bother with. That macro, and any other that causes trouble, will get by all right if you put a `\protect` in front of it in your file.)

We also need to eliminate all `reledmac` macros like `\edlabel` and `\setline` that write things to auxiliary files: that writing should be done only once. And we make `\edtext` itself, if it appears within its own argument, do nothing but copy its first argument.

Finally, we execute `\morenoexpands`. The version of `\morenoexpands` defined here does nothing; but you may define a version of your own when you need to add more expansion suppressions as needed with your macros. That makes it possible to make such additions without needing to copy or modify the standard `reledmac` code. If you define your own `\morenoexpands`, you must be very careful about spaces: if the

²⁹Since ‘control sequences equivalent to characters are not expandable’—*The TeXbook*, answer to Exercise 20.14.

macro adds any spaces to the text when it runs, extra space will appear in the main text when \edtext is used.

The \new@series command also adds \let\footnote{*X*}@\gobble to the end of the \no@expands macro for the series *X*.

(A related problem, not addressed by these two macros, is that of characters whose category code are changed by any of the macros used in the arguments to \edtext. Since the category codes are set when the arguments are scanned, macros that depend on changing them will not work. We have most often encountered this with characters that are made ‘active’ within text in some, but not all, of the languages used within the document. One way around the problem, if it takes this form, is to ensure that those characters are *always* active. Within languages that make no special use of them, their associated control sequences should simply return the proper character. A simpler solution is to avoid active characters, using LuaTeX or X_ET_X.)

```

1610 \newcommand*{\no@expands}{%
1611   \let\select@olemmafont=0%
1612   \let\startsub=\relax \let\endsub=\relax
1613   \let\startlock=\relax \let\endlock=\relax
1614   \let\edlabel=\@gobble
1615   \let\setline=\@gobble \let\advanceline=\@gobble
1616   \let\sameword\sameword@inedtext%
1617   \let\edtext=\dummy@edtext
1618   \let\edindex\dummy@edindex%
1619   \let\dtabnoexpands
1620   \let\linenumannotation=\@gobble%
1621   \morenoexpands}
1622 \let\morenoexpands=\relax
1623 %
1624 %

```

\@tag Now, we define an empty \@tag command. It will be redefine by \edtext: its value is the first argument. It will be used by the \Xfootnote commands.

```

1625 \newcommand{\@tag}{}%
1626 %

```

\@edtext@level This counter is increased by 1 at each level of \edtext.

```

1627 \newcount\@edtext@level%
1628 \@edtext@level=0%
1629 %

```

\if@edtext@secondarg@ This boolean is set to TRUE before reading the second argument of a \edtext. It is tested on some macro which must be executed only inside a second argument.

```

1630 \newif\if@edtext@secondarg@
1631 %

```

\theedtext The edtext counter is increased at each \edtext command. It is used to add to insert hyperlinks between a notes and the lemma.

```
1632 \newcounter{edtext}
1633 \renewcommand{\theedtext}{\edtxt@arabic{edtext}}%
1634 %
```

\edtext When executed, \edtext first ensures that we are in horizontal mode.

```
1635 \newcommand{\edtext}[2]{\leavevmode%
1636 %
```

Then, check if we are in a numbered paragraph (\pstart... \pend)..

```
1637 \ifnumberedpar%
1638 %
```

we increment the \edtext@level \TeX counter to know in which level of \edtext we are.

```
1639 \global\advance\edtext@level by 1%
1640 %
```

We also increase the edtext \TeX counter to insert a hypertarget if the hyperref package is loaded, and also works with \edtext on right-to-left typesetting with X \TeX .

We store the value for the current level in a global macro. So we have one macro by level of \edtext. That is required, because \edtext can contain \edtext.

```
1641 \stepcounter{edtext}%
1642 \csxdef{thisedtext@\the\edtext@level}{\theedtext}%
1643 %
```

By default, we do not use \lemma

```
1644 \global@lemmacommand@false%
1645 %
1646 \begingroup%
1647 %
```

We get the next series of samewords data in the list of samewords data for the current edtext level. We push them inside \sw@inthisedtext.

```
1648 \ifledRcol%
1649 \ifcsvoid{sw@list@edtextR@\the\edtext@level}%
1650 { \global\let\sw@inthisedtext\empty}%
1651 { \expandafter\gl@p\csname sw@list@edtextR@\the\edtext@level\endcsname\to\sw@inthisedtext}%
1652 \else%
1653 \ifcsvoid{sw@list@edtext@\the\edtext@level}%
1654 { \global\let\sw@inthisedtext\empty}%
1655 { \expandafter\gl@p\csname sw@list@edtext@\the\edtext@level\endcsname\to\sw@inthisedtext}%
1656 \fi%
1657 %
```

\@tag Our normal lemma is just argument #1; but that argument could have further invocations of \edtext within it. We get a copy of the lemma without any \edtext macros within it by temporarily redefining \edtext to just copy its first argument and ignore the other, and then expand #1 into \@tag, our lemma.

This is done within a group that starts here, in order to get the original \edtext restored; within this group we have also turned off the expansion of those control sequences commonly found within text that can cause trouble for us.

```
1658     \global\renewcommand{\@tag}{%
1659         \noexpand\expandafter #1%
1660     }%
1661     %
```

\l@d@nums Prepare more data for the benefit of note-generating macros: the line references and font specifier for this lemma go to \l@d@nums.

```
1662     \set@line%
1663     %
```

\insert@count will be altered by the note-generating macros: it counts the number of deferred footnotes or other insertions generated by this instance of \edtext. If we are in a right column (reledpar), we use \insert@countR instead of \insert@count.

```
1664     \ifledRcol \global\insert@countR \z@%
1665     \else      \global\insert@count \z@ \fi%
1666     %
```

Now process the note-generating macros in argument #2 (i.e., \Afootnote, \lemma, etc.). \ignorespaces is here to skip over any spaces that might appear at the start of #2; otherwise they wind up in the main text. Footnote and other macros that are used within #2 should all end with \ignorespaces as well, to skip any spaces between macros when several are used in series.

```
1667     \edtext@secondarg@true%
1668     \ignorespaces #2\relax%
1669     \edtext@secondarg@false%
1670     %
```

With X_ET_EX, you must track whether the language reads left to right (English) or right to left (Arabic). reledmac defines an \if@RTL boolean test is not already defined.

```
1671     \if@RTL%
1672         \flag@start@RTL%
1673     \else%
1674         \flag@start%
1675     \fi%
1676     %
```

We write in the numbered file wether the current \edtext has a \lemma in the the second argument.

```

1677 \if@lemmacommand@%
1678   \ifledRcol%
1679     \write\linenum@outR{\string\@lemma}%
1680   \else%
1681     \write\linenum@out{\string\@lemma}%
1682   \fi%
1683 \fi%
1684 %

```

Finally, we are ready to admit the first argument into the current paragraph.

It is important that we generate and output all the notes for this chunk of text *before* putting the text into the paragraph: notes that are referenced by line number should generally be tied to the start of the passage they gloss, not the end. That should all be done within the expansion of #2 above, or in \aftergroup commands within that expansion.

```

1685 \endgroup%
1686 \ifdef{\hypertarget}{%
1687   {%
1688     \Hy@raisedlink@left{\hypertarget{\csuse{thisedtext@\the\%
1689 @edtext@level}:start}{}}%
1690     \showlemma{\#1}%
1691     \Hy@raisedlink{\hypertarget{\csuse{thisedtext@\the\@edtext@level}:
1692 end}{}}%
1693   }%
1694   {%
1695     \showlemma{\#1}%
1696   }%
1697 %

```

Finally, we add any insertions that are associated with the *end* of the lemma. Footnotes that are identified by symbols rather than by where the lemma begins in the main text need to be done here, and not above.

```

1696 \ifx\end@lemmas\empty \else%
1697   \gl@p\end@lemmas\to\x@lemma%
1698   \x@lemma%
1699   \global\let\x@lemma=\relax%
1700 \fi%
1701 \if@RTL%
1702   \flag@end@RTL%
1703 \else%
1704   \flag@end%
1705 \fi%
1706 %

```

We switch some flags to false.

- The one that checks having footnotes inside a \edtext.
- The one that says we are inside a \edtext. In fact, it is not a flag, but a counter which is increased to 1 in each leavel of \edtext.

- The one that says we are inside a \lemma.

```

1707     \global\@noneed@Footnotefalse%
1708     \global\advance\@edtext@level by -1%
1709     \global\@lemma@command@false%
1710 %

```

We also reset \beforeinsertofthisedtext

```

1711     \global\let\@beforeinsertofthisedtext\relax%
1712 %

```

If we are outside of a numbered paragraph, we send an error message and print the first argument.

```

1713     \else%
1714     \showlemma{\#1} (\textbf{\textsf{Edtext outside numbered paragraph}})%
1715     \led@err@edtextoutsidestart%
1716     \fi%
1717 %
1718 %
1719 %

```

`\beforeinsertofthisedtext` `\beforeinsertofthisedtext` is an internal macro. `reledmac` or `reledpar` can add in this macro any content required to be executed before doing any `\insert` related to a `\edtext`. Its content is `\let` equal to `\relax` at the end of every `\edtext`.

```

1720 \let\@beforeinsertofthisedtext\relax
1721 %

```

`\ifnumberline` The `\ifnumberline` option can be set to FALSE to disable line numbering.

```

1722 \newif\ifnumberline
1723 \numberlinetrue
1724 %

```

`\set@line` The `\set@line` macro is called by `\edtext` to put the line-reference field and font specifier for the current block of text into `\l@d@nums`.

One instance of `\edtext` may generate several notes, or it may generate none – it is legitimate for argument #2 to `\edtext` to be empty. But `\flag@start` and `\flag@end` induce the generation of a single entry in `\line@list` during the next run, and it is vital to also remove one and only one `\line@list` entry here.

If no more lines are listed in `\line@list`, something is wrong – probably just some change in the input. We set all the numbers to zeros, following an old publishing convention for numerical references that have not yet been resolved.

```

1725 \newcommand*{\set@line}{%
1726   \ifledRcol
1727     \ifx\line@listR\empty

```

```

1728   \global\noteschanged@true
1729   \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
1730   \else
1731     \gl@p\line@listR\to\@tempb
1732     \xdef\l@d@nums{@tempb|\edfont@info}%
1733     \global\let\@tempb=\undefined
1734   \fi
1735   \ifx\annot@listR\empty%
1736     \xdef\l@current@annotR{}%
1737   \else%
1738     \gl@p\annot@listR\to\@tempb%
1739     \xdef\l@current@annotR{@tempb}%
1740     \global\let\@tempb=\undefined%
1741   \fi%
1742 \else
1743   \ifx\line@list\empty%
1744     \global\noteschanged@true
1745     \xdef\l@d@nums{000|000|000|000|000|000|\edfont@info}%
1746   \else
1747     \gl@p\line@list\to\@tempb
1748     \xdef\l@d@nums{@tempb|\edfont@info}%
1749     \global\let\@tempb=\undefined
1750   \fi
1751   \ifx\annot@list\empty%
1752     \xdef\l@current@annot{}%
1753   \else%
1754     \gl@p\annot@list\to\@tempb%
1755     \xdef\l@current@annot{@tempb}%
1756     \global\let\@tempb=\undefined%
1757   \fi%
1758 \fi}
1759 %
1760 %

```

\edfont@info The macro `\edfont@info` returns coded information about the current font.

```

1761 \newcommand*{\edfont@info}{\f@encoding/\f@family/\f@series/\f@shape}
1762 %
1763 %

```

VI.2 Substitute lemma

\lemma The `\lemma{<text>}` macro allows you to change the lemma that is passed on to the notes. Read about `\@tag` in normal `\edtext` macro for more details about `\sw@list@inedtext` and `\no@expands` (VI.1 p. 135).

```

1764 \newcommand*{\lemma}[1]{%
1765   \global\@lemmacommand@true%
1766   \global\renewcommand{\@tag}{%

```

```

1767     \no@expands #1%
1768     }%
1769     \ignorespaces%
1770     }%
1771 %

```

\@lemma The `\@lemma` is written in the numbered file to set which `\edtext` has an `\lemma` as second argument.

```

1772 \newcommand{\@lemma}{%
1773   \booltrue{lemmacommand@\the\@edtext@level}%
1774 }%
1775 %

```

\if@lemmacommand@ This boolean is set to TRUE inside a `\edtext` (or `\critext`) when a `\lemma` command is called. That is useful for some commands which can have a different behavior if the lemma in the note is different from the lemma in the main text.

```

1776 \newif\if@lemmacommand@
1777 %

```

VI.3 Substitute line numbers

\linenum The `\linenum` macro can change any or all of the page and line numbers that are passed on to the notes.

As argument `\linenum` takes a set of seven parameters separated by vertical bars, in the format used internally for `\l@d@nums` (see V.9 p. 105): the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma. However, you can omit any parameters you do not want to change, and you can omit a string of vertical bars at the end of the argument. Hence `\linenum{18|4|0|18|7|1|0}` is an invocation that changes all the parameters, but `\linenum{|3|}` only changes the starting line number, and leaves the rest unaltered.

We use `\`` as an internal separator for the macro parameters.

```

1778 \newcommand*{\linenum}[1]{%
1779   \xdef\@tempa{\#1|||||\noexpand\\l@d@nums}%
1780   \global\let\l@d@nums=\empty
1781   \expandafter\line@set\@tempa\\\ignorespaces}
1782 %

```

\line@set `\linenum` calls `\line@set` to do the actual work; it looks at the first number in the argument to `\linenum`, sets the corresponding value in `\l@d@nums`, and then calls itself to process the next number in the `\linenum` argument, if there are more numbers in `\l@d@nums` to process.

```

1783 \def\line@set#1#2#3#4{\%
1784   \gdef\@tempb{#1}%
1785   \ifx\@tempb\empty

```

```

1786      \l@d@add{#3}%
1787  \else
1788      \l@d@add{#1}%
1789  \fi
1790  \gdef\@tempb{#4}%
1791  \ifx\@tempb\empty\else
1792      \l@d@add{}{\line@set#2\\#4\\}
1793  \fi}
1794 %

```

\l@d@add \line@set uses \l@d@add to tack numbers or vertical bars onto the right hand end of \l@d@nums.

```

1795 \newcommand{\l@d@add}[1]{\xdef\l@d@nums{\l@d@nums#1}}
1796 %
1797 %

```

\lineannot \lineannot@set Last but not least, \lineannot allows us to substitute line number annotation. It is different from \linenum for backward compatibility with older versions of reledmac. It calls \lineannot@set to determine whether we must change only one annotation or two, or none.

```

1798 \newcommand*{\lineannot}[1]{%
1799   \lineannot@set#1%
1800 }
1801 \def\lineannot@set#1#2{%
1802   \expandafter\parse@annot#1#2%
1803   \IfStrEq{#1}{%
1804     {\let\@tempa\annot@start}%
1805     {\def\@tempa{#1}}%
1806   \IfStrEq{#2}{%
1807     {\let\@tempb\annot@start}%
1808     {\def\@tempb{#2}}%
1809   \xdef\l@current@annot{\@tempa\@tempb}%
1810 }
1811 %

```

VI.4 Lemma disambiguation

The mechanism which counts the occurrence of a same word in a same line is quite complex, because, when L^AT_EX reads a command between a \pstart and a \pend, it does not know yet which are the line numbers.

The general mechanism is the following:

- **At the first run**, each \sameword command increments an etoolbox counter the name of which contains the argument of the \sameword commands.
- Then this counter, associated with the argument of \sameword is stored with the \csw command in the auxiliary file of the current reledmac section (the .1, .2... file).

- When this auxiliary file is read at the second run, different operations are achieved:

1. Get the rank of each \sameword in a line (relative rank) from the rank of each \sameword in all the numbered section (absolute rank):

- For each paired \sameword argument and absolute line number, a counter is defined. Its value corresponds to the number of times \sameword{<argument>} is called from the beginning of the lineation to the end of the current line. We also store the same data for the preceding absolute line number, if it does not have \sameword{<argument>}.
- For each \sameword having the same argument, we subtract from its absolute rank the number stored for the paired \sameword argument and previous absolute line number. Consequently, we obtain the relative rank.
- See the following example which explains how, for same \sameword, absolute ranks are transformed to relative ranks.

```

At line 1:
absolute rank 1 becomes relative rank 1-0 = 1
1 is stored for this \sameword and line 1
At line 2:
absolute rank 2 becomes relative rank 2-1 = 1
absolute rank 3 becomes relative rank 3-1 = 2
3 is stored for this \sameword and line 2
At line 3:
no \sameword for this line.
3 is stored for this \sameword and line 3
At line 4:
absolute rank 4 becomes relative rank 4-3 = 1
4 is stored for this \sameword and line 4

```

2. Create lists of lists of \sameword by depth of \edtext. That is: create a list for \edtexts of level 1, a list for \edtexts of level 2, a list for \edtexts of level 3 etc. For each \edtext in these lists, we store all of the relative ranks of \sameword which are called as lemma information. That is: 1) either called in the first argument of \sameword, or, 2) called in the \lemma macro of the second argument of \sameword AND marked by the optional argument of \sameword in first argument of \edtext.

For example, suppose a line with nested \edtexts which contains some word marked by \sameword and having the following relative rank:

bar ¹	foo ¹ foo ² bar ² foo ³	(A)(B) foo ⁴ bar ³	(C)	foo ⁵	(D) bar ⁴	(E)
------------------	---	--	-----	------------------	----------------------	-----

In this example, all lemma information for \edtext is framed. The text in parenthesis is the content of critical notes associated to the preceding frame. As you can see, we have two levels of \edtext.

The list for \edtexts of level 1 is $\{\{1, 2, 2, 3, 4, 3\}, \{5, 4\}\}$.

The list for `\edtexts` of level 2 is $\{\{1, 2, 2, 3\}, \{5\}\}$.

As you can see, the mandatory argument of `\sameword` does not matter: we store the rank informations for every word potentially ambiguous.

- At the second run, when a critical notes is called, we associate it to the next item of the list associated to its `\edtext` level. So, in the previous example:
 - Critical notes (A) and (B) are associated with $\{1, 2, 2, 3\}$.
 - Critical note (C) is associated with $\{1, 2, 2, 3, 4, 3\}$.
 - Critical note (D) is associated with $\{5\}$.
 - Critical note (E) is associated with $\{5, 4\}$.
- At the second run, when a critical note is printed:
 - The `\sameword` command is let `\sameword@inedtext`.
 - At each call of this `\sameword@inedtext`, we step to the next element of the list associated to the note. Let it be r .
 - For the word marked by `\sameword`, we calculate how many time it is called in its line. To do it:
 - * We get the absolute line number of the current `\sameword`. This absolute line number was stored with a list of relative ranks for the current `\edtext`. That means, in the previous example, that if the absolute line number of `\edtext` was 1, that critical notes (A) and (B) were not associated with $\{1, 2, 2, 3\}$ but with $\{(1, 1), (2, 1), (2, 1), (3, 1)\}$. Such a method of knowing the absolute line number associated to a `\sameword` is required because a `\edtext` can overlap many lines, but `\sameword` can't get it.
 - * When reading the auxiliary file, we get the value associated to the pair composed by the current marked word and the current absolute line number. To this value, we subtract the value associated to the pair composed by the current marked word and the previous absolute line number. Let the result be n .
 - If $n > 1$, that means the current word appears more than once in its line. In this case, we call `\showwordrank` with the word as the first argument and r as the second argument. If the word is called only once, we just print it.

After theory, implementation.

`\get@sw@txt` As the argument of `\sameword` can contain an active character if we use `inputenc` with `utf8` option instead of native UTF-8 engine, we store its detokenized content in a macro in order to allow the dynamic name of macro with `\csname`.³⁰

Because there is a bug with `\detokenize` and X_ET_EX when using non BMP characters³¹, we detokenize only for non-X_ET_EXengines. In any case, in X_ET_EXa `\csname` construction can contain UTF-8 characters without a problem, as UTF-8 characters are not managed with category codes, but instead read directly as UTF-8 characters.

³⁰See <http://tex.stackexchange.com/q/244538/7712>.

³¹<http://sourceforge.net/p/xetex/bugs/108/>

```

1812 \newcommand{\get@sw@txt}[1]{%
1813   \begingroup%
1814   \swnoexpands%
1815 }.

```

Using case sensibility option.

```

1816   \ifsw@caseinsensitive%
1817     \def\@tmpa##1{\lowercase{##1}}%
1818   \else%
1819     \def\@tmpa##1{##1}%
1820   \fi%
1821 %

```

And now, define \sw@txt.

```

1822   \ifxetex%
1823     \@tmpa{\xdef\sw@txt{#1}}%
1824   \else%
1825     \@tmpa{\expandafter\xdef\expandafter\sw@txt\expandafter{\detokenize
1826     {#1}}}%
1827   \fi%
1828 \endgroup%
1829 }%
1830 %

```

Allow some macros inside \sameword. We use \RenewExpandableDocumentCommand to get expandable command with optional argument. Cf. <https://tex.stackexchange.com/a/384783/7712>.

```

\sw@noexpand30 \newcommand{\swnoexpands}{%
1831   \let\sameword\@firstofone% Allow to have nested \sameword
1832   \let\emph\@firstofone%
1833   \let\textit\@firstofone%
1834   \let\textbf\@firstofone%
1835   \let\textsc\@firstofone%
1836   \let\framebox\@firstofone%
1837   \RenewExpandableDocumentCommand{\edindex}{om}{}%
1838   \ifdefinable\index{%
1839     \RenewExpandableDocumentCommand{\index}{om}{}%
1840   }%
1841   \let\selectlanguage@gobble%
1842   \let\foreignlanguage@secondoftwo%
1843   \ifdef\xpg@loaded{%
1844     \renewcommand\do[1]{%
1845       \expandafter\RenewExpandableDocumentCommand\expandafter{\csname
1846       text##1\endcsname}{om}{####2}%
1847     }%
1848     \expandafter\docslist\expandafter{\xpg@loaded}%
1849   }%
1850 %

```

\sameword The hight level macro `\sameword`, used by the editor.

```
1851 \newcommandx{\sameword}[2][1,usedefault]{%
1852     \leavevmode%
1853     \get@sw@txt{#2}%
1854 }
```

Now, the real code. First, increment the counter corresponding to the argument.

```
1855 \unless\ifledRcol%
1856     \csnumgdef{sw@\sw@txt}{\csuse{sw@\sw@txt}+\@ne}%
1857 %
```

Then, write its value to the numbered file.

```
1858 \protected@write\linenum@out{}{\string\@sw{\sw@txt}{\csuse{sw@\sw@txt}%
1859 }{#1}}%
1860 %
```

Do the same thing if we are in the right column.

```
1860 \else%
1861     \csnumgdef{sw@\sw@txt}{\csuse{sw@\sw@txt}+\@ne}%
1862     \protected@write\linenum@outR{}{\string\@sw{\sw@txt}{\csuse{sw@\sw@txt}%
1863 }{#1}}%
1864 \fi%
1865 %
```

And print the word.

```
1865 #2%
1866 }%
1867 %
```

A flag set to true if a `\@sw` relative rank must be added to the list of ranks for a specific `\edtext`.

```
\if@addsw68 \newif\if@addsw%
```

```
1869 %
```

\@sw The command printed in the auxiliary files.

```
1870 \newcommand{\@sw}[3]{%
1871     \get@sw@txt{#1}%
1872     \unless\ifledRcol%
1873 }
```

First, define a counter which store the second argument as value for a each paired absolute line number/first argument

```
1874 \csxdef{sw@\sw@txt} {\the\absline@num \the\section@num}{#2}%
1875 %
```

If such argument was not defined for the preceding line, define it.

```

1876 \numdef{\prev@line}{\the\absline@num-1}%
1877 \ifcsundef{sw@\sw@txt @\prev@line @\the\section@num}{%
1878   \csnumgdef{sw@\sw@txt @\prev@line @\the\section@num}{#2-1}%
1879 }{}%
1880 %

```

Then, calculate the position of the word in the line.

```

1881 \numdef{\the@sw}{#2-\csuse{sw@\sw@txt @\prev@line @\the\section@num}}%
1882 %

```

And do the same thing for the right side.

```

1883 \else%
1884   \csxdef{sw@\sw@txt @\the\absline@numR @\the\section@numR @R}{#2}%
1885   \numdef{\prev@line}{\the\absline@numR-1}%
1886   \ifcsundef{sw@\sw@txt @\prev@line @\the\section@numR @R}{%
1887     \csnumgdef{sw@\sw@txt @\prev@line @\the\section@numR @R}{#2-1}%
1888   }{}%
1889   \numdef{\the@sw}{#2-\csuse{sw@\sw@txt @\prev@line @\the\section@numR @R}}%
1890 }%
1891 %

```

And now, add it to the list of \@sw for the current edtext, in all depth.

```

1892 \@tempcpta=\@edtext@level
1893 \@whilenum{\@tempcpta>0}\do{%
1894   \ifcsdef{sw@list@edtext@tmp@\the\@tempcpta}{%
1895     {%
1896       \caddswfalse%
1897       \notbool{lemmacommand@\the\@tempcpta}{%
1898         {\caddswtrue}%
1899         {\IfStrEq{#3}{inlemma}{%
1900           {\caddswtrue}%
1901           {%
1902             \def\do##1{%
1903               \ifnumequal{##1}{\the\@tempcpta}{%
1904                 {\caddswtrue\listbreak}%
1905               }{}%
1906             }%
1907             \docslist{#3}%
1908           }%
1909         }%
1910       \cif@addsw{%
1911         \letcs{@tmp}{sw@list@edtext@tmp@\the\@tempcpta}%
1912         \ifledRcol{%
1913           \xrightappenditem{\the@sw}{\the\absline@numR}\to@tmp%
1914         }%
1915         \xrightappenditem{\the@sw}{\the\absline@num}\to@tmp%
1916       }%
1917     \cslet{sw@list@edtext@tmp@\the\@tempcpta}{@tmp}%

```

```

1918      \fi%
1919      }%
1920      {}%
1921      \advance\@tempcnta by -1%
1922      }%
1923      }%
1924      %

```

`\sameword@inedtext` The command called when `\sameword` is called in a `\edtext`.

```

1925  \newcommandx{\sameword@inedtext}[2][1,usedefault]{%
1926    \get@sw@txt{#2}%
1927    \unless\ifledRcol@%
1928    %

```

Just a precaution.

```

1929      \ifx\sw@list@inedtext\empty%
1930      \def\the@sw{999}%
1931      \def\this@absline{-99}%
1932      \else%
1933      %

```

But in many cases, at this step, we should have some content in the list `\sw@list@inedtext`, which contains the reference for `\edtext`.

```

1934  \gl@p\sw@list@inedtext\to\@tmp%
1935  \edef\the@sw{\expandafter\@firstoftwo\@tmp}%
1936  \edef\this@absline{\expandafter\@secondoftwo\@tmp}%
1937  \fi%
1938 %

```

First, calculate the number of occurrences of the word in the current line

```

1939  \ifcsdef{sw@\sw@txt}{\this@absline}{\the\section@num}{%
1940    \numdef{\prev@line}{\this@absline-1}%
1941    \numdef{\sw@atthisline}{\csuse{sw@\sw@txt}{\this@absline}{\the\section@num}-\csuse{sw@\sw@txt}{\prev@line}{\the\section@num}}%
1942    }%
1943    {\numdef{\sw@atthisline}{0}}%
1944 %

```

Finally, print the rank, but only if there is more than one occurrence of the word in the current line.

```

1945  \ifnumgreater{\sw@atthisline}{1}{%
1946    \showwordrank{#2}{\the@sw}%
1947    {#2}%
1948 %

```

And the same for right side.

```

1949  \else%
1950  \ifx\sw@list@inedtext\empty%

```

```

1951      \def\the@sw{999}%
1952      \def>this@absline{-99}%
1953  \else%
1954      \gl@p\sw@list@inedtext\to\@tmp%
1955      \edef\the@sw{\expandafter\@firstoftwo\@tmp}%
1956      \edef>this@absline{\expandafter\@secondoftwo\@tmp}%
1957  \fi%
1958  \ifcsdef{sw@\sw@txt}{\this@absline}{\the\section@numR@R}{%
1959      \numdef{\prev@line}{\this@absline-1}%
1960      \numdef{\sw@atthisline}{\csuse{sw@\sw@txt}{\this@absline}{\the\section@numR@R}}{%
1961          \csuse{sw@\sw@txt}{\prev@line}{\the\section@numR@R}}{%
1962          }%
1963          \numdef{\sw@atthisline}{0}%
1964          \ifnumgreater{\sw@atthisline}{1}{%
1965              \showwordrank{\#2}{\the@sw}%
1966              \#2}%
1967          }%
1968      %

```

`\showwordrank` Finally, the way the rank will be printed.

```

1969  \newcommand{\showwordrank}[2]{%
1970      #1\textsuperscript{#2}%
1971  }%
1972  %

```

VII Paragraph decomposition and reassembly

In order to be able to count the lines of text and affix line numbers, we add an extra stage of processing for each paragraph. We send the paragraph into a box register, rather than straight onto the vertical list, and when the paragraph ends we slice the paragraph into its component lines; to each line we add any notes or line numbers, add a command to write to the line-list, and then at last send the line to the vertical list. This section contains all the code for this processing.

VII.1 Boxes, counters, `\pstart` and `\pend`

`\raw@text` Here are numbers and flags that are used internally in the course of the paragraph decomposition.
`\ifnumberedpar@`
`\numberedpar@true` When we first form the paragraph, it goes into a box register, `\raw@text`, instead of onto the current vertical list. The `\ifnumberedpar@` flag will be true while a paragraph is being processed in that way. `\num@lines` will store the number of lines in the paragraph when it is complete. When we chop it up into lines, each line in turn goes into the `\one@line` register, and `\par@line` will be the number of that line within the paragraph.
`\numberedpar@false`
`\num@lines`
`\one@line`
`\par@line`

```

1973 \newbox\raw@text
1974 \newif\ifnumberedpar@
1975 \newcount\num@lines
1976 \newbox\one@line
1977 \newcount\par@line
1978 %

```

\pstart starts the paragraph by clearing the \inserts@list list and other relevant variables, and then arranges for the subsequent text to go into the \raw@text box. \pstart needs to appear at the start of every paragraph that is to be numbered; the \autopar command below may be used to insert these commands automatically.

Beware: everything that occurs between \pstart and \pend is happening within a group; definitions must be global if you want them to survive past the end of the paragraph.

```

\pstart
  \AtEveryPstart
  \AtStartEveryPstart
    \numberpstarttrue
    \numberpstartfalse
      \labelpstarttrue
      \labelpstartfalse
        \the\pstart
\ifat@every@pstart@star@%
  \newcommand{\AtStartEveryPstart}[1]{%
    \ifstrempty{#1}%
      {\gdef\at@start@every@pstart{}%}
      {\gdef\at@start@every@pstart{#1}}%
  }%
  \def\at@start@every@pstart{}%
\newif\ifat@every@pstart@star@%
\newcommand{\AtEveryPstart}[1]{%
  \ifstrempty{#1}%
    {\gdef\at@every@pstart{}%}
    {\gdef\at@every@pstart{\noindent#1}}%
  \global\at@every@pstart@star@false%
}%
\WithSuffix\newcommand{\AtEveryPstart*}[1]{%
  \ifstrempty{#1}%
    {\gdef\at@every@pstart{}%}
    {\gdef\at@every@pstart{#1}}%
  \global\at@every@pstart@star@true%
}%
\def\at@every@pstart{}%
\newcounter{pstart}
\renewcommand{\the\pstart}{\bfseries\@arabic\c@pstart}. }
\newif\ifnumberpstart
\numberpstartfalse
\newif\iflabelpstart
\labelpstartfalse
\newcommandx*{\pstart}[2][1,2]{\usedefault}{%
  \normal@pars%
  \ifboolexpr{%
    test {\ifstrempty{#1}}%
    and test {\ifstrempty{#2}}%
  }%
}
```

```

2013 }%
2014   {\at@everypstart}%
2015   {%
2016     \ifstrempty{\#1}{}{\noindent\#1}%
2017     \ifstrempty{\#2}{}{\#2}%
2018   }%
2019   \ifaupar%
2020     \autopar%
2021   \fi%
2022   \ifluatex%
2023     \edef\l@luatextextdir@L{\the\textrm{dir}}%
2024   \fi%
2025   \nobreaktrue%
2026   \ifnumbering \else%
2027     \led@err@PstartNotNumbered%
2028     \beginnumbering%
2029   \fi%
2030   \ifnumberedpar@%
2031     \led@err@PstartInPstart%
2032     \pend%
2033   \fi%
2034   \list@clear{\inserts@list}%
2035   \global\let\next@insert=\empty%
2036   \begingroup\normal@pars%
2037   \global\advance \l@dnumpstartsL@ne%
2038   \global\setbox\raw@text=\vbox\bgroup%
2039     \ifnobreak%
2040       \if@afterindent\else%
2041         \noindent%
2042         \global\@afterindenttrue%
2043       \fi%
2044     \fi%
2045     \ifaupar\else%
2046     \ifnumberpstart%
2047       \ifinstanza\else%
2048         \ifsidepstartnum\else%
2049           \thepstart%
2050         \fi%
2051       \fi%
2052     \fi%
2053   \fi%
2054   \numberedpar@true%
2055   \iflabelpstart%
2056     \protected@edef\@currentlabel{\p@pstart\thepstart}%
2057   \fi%
2058   \l@dzopenalties%
2059   \cat@start@everypstart%
2060   \ignorespaces%because not automatically ignored if an optional argument
is used (classical TeX behavior for space after commands)
2061 }

```

2062 %

\pend \pend must be used to end a numbered paragraph.

```

2063 \newcommandx*{\pend}[2][1,2]{\usedefault}{\ifnumbering \else%
2064   \led@err@PendNotNumbered%
2065   \fi%
2066   \global\l@dskipversenumberfalse%
2067   \ifnumberedpar@ \else%
2068     \led@err@PendNoPstart%
2069   \fi%
2070 %

```

We set all the usual interline penalties to zero and then immediately call \endgraf to end the paragraph; this ensures that there will be no large interline penalties to prevent us from slicing the paragraph into pieces. These penalties revert to the values that you set when the group for the \vbox ends. Then we call \do@line to slice a line off the top of the paragraph, add a line number and footnotes, and restore it to the page; we keep doing this until there are not any more lines left.

```

2071 \l@dzopenalties%
2072 \cat@end@every@pend%
2073 \endgraf\global\num@lines=\prevgraf\egroup%
2074 \global\par@line=0%
2075 %

```

We check if lineation is by pstart: in this case, we reset the line number, but only in the second line of the pstart. We can't reset line number at the beginning of \pstart, as \setline is parsed at the end of previous \pend, and so, we must do it at the end of first line of pstart.

```

2076 \csnumdef{pstartline}{0}%
2077 \loop\ifvbox\raw@text%
2078   \csnumdef{pstartline}{\pstartline+\@ne}%
2079   \do@line%
2080   \ifbypstart@%
2081     \ifnumequal{\pstartline}{1}{}{%
2082       \bgroup%
2083       \let\leavevmode\relax%
2084       \setline{1}%
2085       \egroup%
2086       \resetprevline@{}%
2087     \fi%
2088   \repeat%
2089 %

```

Deal with any leftover notes, and then end the group that was begun in the \pstart.

```

2090 \flush@notes%
2091 \endgroup%
2092 \ignorespaces%
2093 %

```

Increase pstart counter.

```

2094     \ifnumberpstart%
2095         \global\pstartnumtrue%
2096     \fi%
2097     \addtocounter{pstart}{1}%
2098     \ifcontinuousnumberingwithcolumns%
2099         \addtocounter{pstartL}{1}%
2100         \addtocounter{pstartR}{1}%
2101     \fi%
2102 %

```

Print the optional arguments of \pend or the content printed after every \pend

```

2103     \normal@pars%
2104     \ifboolexpr{%
2105         test {\ifstrempty{\#1}}%
2106         and test {\ifstrempty{\#2}}%
2107     }%
2108     {\at@every@pend}%
2109     {%
2110         \ifstrempty{\#1}{}{\noindent\#1}%
2111         \ifstrempty{\#2}{}{\#2}%
2112     }%
2113 %

```

Restore standard “nobreak” and “autopar” settings. Normally, \if@nobreak is true only immediately after a sectioning command (see latex.ltx file). As a \pstart ... \pend structure can't contain any sectioning command, we set \if@nobreak to false.

```

2114     \nobreakfalse%
2115     \ifautopar%
2116         \autopar%
2117     \fi%
2118 }
2119 %

```

Here, two macros to insert content after every \pend, between numbered line. \AtEveryPend is the user macro, \at@every@pend is macro set by it.

```

\AtEveryPend20
\at@every@pend21
\ifat@every@pend@star22 \newif\ifat@every@pend@star@%
2123 \newcommand{\AtEveryPend}[1]{%
2124     \ifstrempty{\#1}%
2125         {\gdef\at@every@pend{}%}
2126         {\gdef\at@every@pend{\noindent\#1}}%
2127         \global\at@every@pend@star@false%
2128     }%
2129 \WithSuffix\newcommand\AtEveryPend*[1]{%
2130     \ifstrempty{\#1}%

```

```

2131   {\gdef\at@every@pend{}%
2132   {\gdef\at@every@pend{\#1}}%
2133   \global\at@every@pend@star@true%
2134 }%
2135 \xdef\at@every@pend{}%
2136 %
2137 %

```

\AtEndEveryPend Here a macro to insert automatically any content at the end of \pend, in numbered lines.

```

2138 \newcommand{\AtEndEveryPend}[1]{%
2139   \ifstrempty{\#1}{%
2140     {\xdef\@atend@every@pend{}%
2141     {\gdef\@atend@every@pend{\#1}}%
2142 }%
2143 \def\@atend@every@pend{}%
2144 %

```

\l@dzeropenalties A macro to zero penalties for \pend or \pstart.

```

2145 \newcommand*{\l@dzeropenalties}{%
2146   \brokenpenalty \z@ \clubpenalty \z@
2147   \displaywidowpenalty \z@ \interlinepenalty \z@ \predisplaypenalty \z@
2148   \postdisplaypenalty \z@ \widowpenalty \z@}
2149 %
2150 %

```

\autopar In most cases it is only an annoyance to have to label the paragraphs to be numbered with \pstart and \pend. \autopar will do that automatically, allowing you to start a paragraph with its first word and no other preliminaries, and to end it with a blank line or a \par command. The command should be issued within a group, after \beginnumbering has been used to start the numbering; all paragraphs within the group will be affected.

A few situations can cause problems. One is a paragraph that begins with a begin-group character or command: \pstart will not get invoked until after such a group beginning is processed; as a result the character that ends the group will be mistaken for the end of the \vbox that \pstart creates, and the rest of the paragraph will not be numbered. Such paragraphs need to be started explicitly using \indent, \noindent, or \leavevmode – or \pstart, since you can still include your own \pstart and \pend commands even with \autopar on.

Prematurely ending the group within which \autopar is in effect will cause a similar problem. You must either leave a blank line or use \par to end the last paragraph before you end the group.

The functioning of this macro is more tricky than the usual \everypar: we do not want anything to go onto the vertical list at all, so we have to end the paragraph, erase any evidence that it ever existed, and start it again using \pstart. We remove the paragraph-indentation box using \lastbox and save the width, and then skip backwards over the \parskip that has been added for this paragraph. Then we start again

with `\pstart`, restoring the indentation that we saved, and locally change `\par` so that it will do our `\pend` for us.

```

2151 \newif\ifautopar
2152 \autoparfalse
2153 \newcommand*{\autopar}{%
2154   \ifledRcol
2155     \ifnumberingR \else
2156     \led@err@AutoparNotNumbered
2157     \beginnumberingR
2158     \fi
2159   \else
2160     \ifnumbering \else
2161     \led@err@AutoparNotNumbered
2162     \beginnumbering
2163     \fi
2164   \fi
2165   \autopartrue
2166   \everypar{\setbox0=\lastbox
2167     \endgraf \vskip-\parskip
2168     \pstart \noindent \kern\wd0 \ifnumberpstart\ifinstanza\else\thepstart\
2169     \fi\fi
2170     \let\par=\pend}%
2171   \ignorespaces}
2172 %

```

`\normal@pars` We also define a macro which we can rely on to turn off the `\autopar` definitions at various important places, if they are in force. We will want to do this within a footnotes, for example.

```

2172 \newcommand*{\normal@pars}{\everypar{}\let\par\endgraf}
2173 %
2174 %

```

`\ifautopar@pause` We define a boolean test switched to true at the beginning of the `\pausenumbering` command if the autopar is enabled. This boolean will be tested at the beginning of `\resumenumbering` to continue the autopar if needed.

```

2175 \newif\ifautopar@pause
2176 %

```

VII.2 Processing one line

VII.2.1 General process

`\do@line` The `\do@line` macro is called by `\pend` to do all the processing for a single line of text.

`\l@dunhbox@line`

```

2177 \newcommand*{\l@dunhbox@line}[1]{\unhbox #1}
2178 \newcommand*{\do@line}{%

```

```

2179  {\vbadness=10000
2180   \splittopskip=\z@
2181   \do@linehook
2182   \l@emptyd@ta
2183   \global\setbox\one@line=\vsplit\raw@text to\baselineskip}%
2184   \unvbox\one@line \global\setbox\one@line=\lastbox
2185   \getline@num
2186   \IfStrEq{\led@pb@setting}{before}{\led@check@pb\led@check@nopb}{}
2187   \ifnum\@clock>\@ne
2188     \inserthangingsymboltrue
2189   \else
2190     \inserthangingsymbolfalse
2191   \fi
2192   \check@pb@in@verse
2193   \ifl@hidenumber%
2194     \global\l@dhidenumberfalse%
2195     \f@x@l@cks%
2196   \else%
2197     \affixline@num%
2198   \fi%
2199 %

```

Depending whether a sectioning command is called at this pstart or not we print sectioning command or normal line,

```

2200 \xifinlist{\the\l@dnumpstartsL}{\eled@sections@@}%
2201   {\print@eledsection}%
2202   {\print@line}%
2203   \IfStrEq{\led@pb@setting}{after}{\led@check@pb\led@check@nopb}{}
2204 }%
2205 %

```

VII.2.2 Process for “normal” line

`\print@line` `\print@line` is for normal line, i. e line without sectioning command.

```

2206 \def\print@line{
2207 %

```

Insert the pstart number inside, if we are in the first line of a pstart.

```

2208   \affixpstart@num%
2209 %

```

The line will be boxed, to have the good width.

```

2210   \hb@xt@ \linewidth{%
2211 %

```

User hook.

```

2212   \do@insidelinehook%
2213 %

```

Left line number

```
2214 \l@ldld@ta%
2215 %
```

Prepare text to be inserted before notes.

```
2216 \if@firstlineofpage%
2217   \set@Xtxtbeforenotes%
2218   \set@txtbeforenotesX%
2219   \global\@firstlineofpagefalse%
2220 \fi%
2221 %
```

Insert footnotes made of manuscripts data and critical footnotes.

```
2222 \ifdefstring{\ms@data@position}{msdata-regular}{%
2223   \insert@msdata%
2224   \add@inserts%
2225   \add@Xgroupbyline%
2226 }{%
2227   \add@inserts%
2228   \add@Xgroupbyline%
2229   \insert@msdata%
2230 }%
2231 %
```

Insert marginal notes.

```
2232 \affixside@note%
2233 %
```

Print left notes.

```
2234 \l@dlsn@te
2235 %
```

Boxes the line, writes information about new line in the numbered file.

```
2236 {\ledllfill\hb@xt@ \wd\one@line{%
2237   \new@line%
2238 }%
```

If we use the `continuousnumberingwithcolumns`, we increase right line number.

```
2239 \ifcontinuousnumberingwithcolumns%
2240   \unless\ifafterendnumberingR%
2241   \new@lineR%
2242   \xappto\next@line@list@stuffR{%
2243     \unexpanded{\global\line@numR=\the\line@num}%
2244   }%
2245 \fi%
2246 \fi%
2247 %
```

If we use `LuaTeX` then restore the direction.

```

2248      \ifluatex%
2249          \textdir\l@luatextextdir@L%
2250          \fi%
2251 %

```

Insert, if needed, the hanging symbol.

```

2252      \inserthangingsymbol%
2253 %

```

And so, print the line.

```

2254      \l@dunhbox@line{\one@line}%
2255 %

```

Right line number

```

2256      \ledrlfill\l@drd@ta%
2257 %

```

Print right notes.

```

2258      \l@drsn@te%
2259      }%
2260 %

```

And reinsert penalties (for page breaking)...

```

2261      \add@penalties%
2262 }
2263 %

```

VII.2.3 Process for line containing \eledsection command

\print@eledsection \print@eledsection to print sectioning command with line number. It sets the correct spacing, depending whether a sectioning command was called at previous \pstart, calls the sectioning command, prints the normal line outside of the paper, to be able to have critical footnotes. Because of how this prints, a vertical spacing correction is added.

```

2264 \def\print@eledsection{%
2265     \if@firstlineofpage%
2266         \set@Xtxtbeforenotes%
2267         \set@txtbeforenotesX%
2268         \global\@firstlineofpagefalse%
2269     \fi%
2270     \ifdefstring{\ms@data@position}{msdata-regular}{%
2271         \insert@msdata%
2272         \add@inserts%
2273         \add@Xgroupbyline%
2274     }{%
2275         \add@inserts%
2276         \add@Xgroupbyline%
2277         \insert@msdata%
2278     }%
}

```

```

2279   \affixside@note%
2280   \numdef{\temp@}{\l@dnumstartsL-1}%
2281   \xifinlist{\temp@}{\eled@sections@@}{\nobreaktrue}{\nobreakfalse}%
2282   \eled@sectioningtrue%
2283   \csuse{\eled@sectioning@\the\l@dnumstartsL}%
2284   \eled@sectioningfalse%
2285   \global\csundef{\eled@sectioning@\the\l@dnumstartsL}%
2286   \if@RTL%
2287     \hspace{-3\paperwidth}%
2288     {\hbox{\l@dunhbox@line{\one@line}} \new@line}%
2289   \else%
2290     \hspace{3\paperwidth}%
2291     {\new@line \hbox{\l@dunhbox@line{\one@line}}}%
2292   \fi%
2293   \vskip-\baselineskip%
2294 }
2295 %

```

VII.2.4 Hooks

`\do@linehook` Two hooks into `\do@line`. The first is called at the beginning of `\do@line`, the second is called in the line box. The second can, for example, have a `\markboth` command inside, the first can not.

```

2296 \newcommand*{\do@linehook}{}%
2297 \newcommand*{\do@insidelinehook}{}%
2298 %

```

`\dolinehook` These high level commands just redefine the low level commands. They have to be used
`\doinsidelinehook` by user, without `\makeatletter`.

```

2299 \newcommand*{\dolinehook}[1]{\gdef\do@linehook{#1}}%
2300 \newcommand*{\doinsidelinehook}[1]{\gdef\do@insidelinehook{#1}}%
2301 %
2302 %

```

VII.2.5 Sidenotes and marginal line number initialization

`\l@emptyd@ta` Nulls the `\dots d@ta`, which may later hold line numbers. Similarly for `\l@dcsnotetext`,
`\l@dl@ta` `\l@dcsnotetext@l`, `\l@dcsnotetext@r` for the texts of the sidenotes, left and right
`\l@dr@ta` notes.

`\l@dcsnotetext`

```

2303 \newcommand*{\l@emptyd@ta}{}%
2304   \gdef\l@dl@ta{}%
2305   \gdef\l@dr@ta{}%
2306   \gdef\l@dcsnotetext@l{}%
2307   \gdef\l@dcsnotetext@r{}%
2308   \gdef\l@dcsnotetext{}%
2309 %
2310 %

```

`\l@dlsn@te` Zero width boxes of the left and right sidenotes, together with their kerns, and, eventually, with additional space if we are in parallel columns typesetting.
`\l@drsn@te`

```

2311 \newcommand{\l@dlsn@te}{%
2312   \ifboolexpr{%
2313     bool {l@dprintingcolumns}%
2314     and bool {ledRcol@}%
2315   }{%
2316     If we are on a right column
2317     \tempdima=\morespace@leftnote@rightcolumn%
2318   }{%
2319     \tempdima=\z@%
2320   }%
2321   \hbox@xt@ \z@{\hss\box\l@dlp@rbox\kern\ledlsnotesep\hskip\tempdima}%
2322 }%
2323 \newcommand{\l@drsn@te}{%
2324   \ifboolexpr{%
2325     bool {l@dprintingcolumns}%
2326     and not bool {ledRcol@}%
2327   }{%
2328     If we are on a left column
2329     \tempdima=\morespace@rightnote@leftcolumn%
2330   }{%
2331     \tempdima=\z@%
2332   }%
2333 }%
2334 %

```

`\ledllfill` These macros are called at the left (`\ledllfill`) and the right (`\ledrlfill`) of each
`\ledrlfill` numbered line. The initial definitions correspond to the original code for `\do@line`.

```

2335 \newcommand*{\ledllfill}{\hfil}
2336 \newcommand*{\ledrlfill}{}
2337 %
2338 %

```

VIII Line and page number computation

`\getline@num` The `\getline@num` macro determines the page and line numbers for the line we are about to send to the vertical list.

```

2339 \newcommand*{\getline@num}{%
2340   \global\advance\absline@num \one@
2341   \do@actions
2342   \do@ballast
2343   \ifnumberline
2344     \ifsblines@
2345       \ifnum\sub@lock<\tw@
2346         \global\advance\subline@num \one@

```

```

2347     \fi
2348 \else
2349   \ifnum\@clock<\tw@
2350     \global\advance\line@num \cne
2351     \global\subline@num \z@
2352   \fi
2353 \fi
2354 \fi
2355 }
2356 %

```

\do@ballast The real work in the macro above is done in `\do@actions`, but before we plunge into that, let's get `\do@ballast` out of the way. This macro looks to see if there is an action to be performed on the *next* line, and if it is going to be a page break action, `\do@ballast` decreases the count `\ballast@count` counter by the amount of `ballast`. This means, in practice, that when `\add@penalties` assigns penalties at this point, TeX will be given extra encouragement to break the page here (see XII.2 p. 172).

\ballast@count First we set up the required counters; they are initially set to zero, and will remain so
\c@ballast unless you type `\setcounter{ballast}{<some figure>}` in your document.

```

2357 \newcount\ballast@count
2358 \newcounter{ballast}
2359   \setcounter{ballast}{0}
2360 %

```

And here is `\do@ballast` itself. It advances `\absline@num` within the protection of a group to make its check for what happens on the next line.

```

2361 \newcommand*{\do@ballast}{\global\ballast@count \z@
2362   \begingroup
2363     \advance\absline@num \cne
2364     \ifnum\next@actionline=\absline@num
2365       \ifnum\next@action>-1001\relax
2366         \global\advance\ballast@count by -\c@ballast
2367       \fi
2368     \fi
2369   \endgroup}
2370 %

```

\do@actions The `\do@actions` macro looks at the list of actions to take at particular absolute line numbers, and does everything that is specified for the current line.
\do@actions@next

It may call itself recursively, and to do this efficiently (using TeX's optimization for tail recursion), we define a control-sequence called `\do@actions@next` that is always the last thing that `\do@actions` does. If there could be more actions to process for this line, `\do@actions@next` is set equal to `\do@actions`; otherwise it is just `\relax`.

```

2371 \newcommand*{\do@actions}{%
2372   \global\let\do@actions@next=\relax

```

```

2373   \ifnum\absline@num<\next@actionline\else
2374   %

```

First, page number changes, which will generally be the most common actions. If we are restarting lineation on each page, this is where it happens.

```

2375   \ifnum\next@action>-1001
2376     \global\page@num=\next@action
2377     \ifresumenumbering@start%
2378       \setbox0=\hbox{}%Required to get the correct page number, when the
2379       \resumenumbering is just after a \newpage
2380       \ifnum\pausenumbering@page@num<\page@num%
2381         \global\resumenumbering@startfalse%
2382       \fi%
2383     \fi%
2384     \ifboolexpr{%
2385       bool{resumenumbering@start}%
2386       and test {\ifdimgreater{\pagedepth}{\z@}}%
2387     }%
2388     {}%
2389     {\global\@firstlineofpagetrue}%
2390     \ifcsdef{reset@line\the\absline@num @\the\section@num}%
2391     {}%
2392     \global\line@num=\z@ \global\subline@num=\z@%
2393     \resetprevline@%
2394     {}%
2395     \global\resumenumbering@startfalse%
2396     \add@msdata@firstlineofpage%
2397   %

```

Next, we handle commands that change the line-number values. (We subtract 5001 rather than 5000 here because the line number is going to be incremented automatically in `\getline@num`.)

```

2398   \else
2399     \ifnum\next@action<-4999
2400       \global@dtempcnta=-\next@action
2401       \advance\global@dtempcnta by -5001
2402       \ifsublines@
2403         \global\subline@num=\global@dtempcnta
2404       \else
2405         \global\line@num=\global@dtempcnta
2406       \fi
2407   %

```

We rescale the value in `\global@dtempcnta` so that we can use a case statement.

```

2408   \else
2409     \global@dtempcnta=-\next@action
2410     \advance\global@dtempcnta by -1000
2411     \do@actions@fixedcode

```

```

2412   \fi
2413   \fi
2414 %

```

Now we get information about the next action off the list, and then set `\do@actions@next` so that we will call ourselves recursively: the next action might also be for this line.

There is no warning if we find `\actionlines@list` empty, since that will always happen near the end of the section.

```

2415   \ifx\actionlines@list\empty
2416     \gdef\next@actionline{1000000}%
2417   \else
2418     \gl@p\actionlines@list\to\next@actionline
2419     \gl@p\actions@list\to\next@action
2420     \global\let\do@actions@next=\do@actions
2421   \fi
2422 \fi
2423 %

```

Make the recursive call, if necessary.

```

2424 \do@actions@next}
2425
2426 %

```

`\do@actions@fixedcode` This macro handles the fixed codes for `\do@actions`. It is one big case statement.

```

2427 \newcommand*{\do@actions@fixedcode}{%
2428   \ifcase\@l@dtmcnta
2429     \or%                                % 1001 = starting sublineation
2430     \global\sublines@true
2431     \or%                                % 1002 = ending sublineation
2432     \global\sublines@false
2433     \or%                                % 1003 = starting locking number
2434     \global\@lock=\@ne
2435     \or%                                % 1004 = ending locking number
2436     \ifnum\@lock=\tw@
2437       \global\@lock=\thr@@
2438     \else
2439       \global\@lock=\z@
2440     \fi
2441     \or%                                % 1005 = starting locking subnumber
2442       \global\sub@lock=\@ne
2443     \or%                                % 1006 = ending locking subnumber
2444       \ifnum\sub@lock=\tw@
2445         \global\sub@lock=\thr@@
2446       \else
2447         \global\sub@lock=\z@
2448       \fi
2449     \or%                                % 1007 = skipping numbering
2450       \l@dskipnumbertrue

```

```

2451 \or%                                % 1008 = skipping numbering in stanza
2452   \l@dskipversenumbertrue%
2453 \or%                                % 1009 = hiding number
2454   \l@dhidenumbertrue%
2455 \or%                                % 1010 = inserting msdata
2456   \add@msdata%
2457 \else
2458   \led@warn@BadAction
2459 \fi}
2460
2461 %
2462 %

```

IX Line number annotation

The `\linenumannotation` allows users to add manual annotations to line numbers, for example to refer to line numbers from an older edition.

That implies that annotations be added

- in marginal line numbers. This feature is implemented by associating annotations with the absolute line numbers when reading the auxiliary numbered files (.1, .2 etc.).
- in critical footnotes. This feature is implemented by associating start / end line number annotations with each `\edtext` when reading the auxiliary numbered files.
- to crossref commands which refer to line numbers (to be completed when I will have resolved this issue).

`\linenumannotation` First, the user-level command, which only writes commands to the numbered files, storing the annotation.

```

2463 \newcommand{\linenumannotation}[1]{%
2464   \leavevmode%In case it begins with a \pstart, ensure the \@cannot is
written after \onl
2465   \ifledRcol%
2466     \write\linenum@outR{\string\@cannot[#1]}%
2467   \else%
2468     \write\linenum@out{\string\@cannot[#1]}%
2469   \fi%
2470 }%
2471 %

```

`\Xlinenumannotationposition@side` The `\Xlinenumannotationposition@side` macro, to determine the position of line number annotations in lines printed in the side, relative to the line number position. The default value is “after”, but it can be changed to “before”, using the `\Xlinenumannotationposition` macro.

```
2472 \def\Xlinenumannotationposition@side{after}%
2473 %
```

`\wraplinenumannotation@ref` The `\wraplinenumannotation@ref` macro is applied to crossrefs made to line annotations. The `\wraplinenumannotation@side` macro is applied to line annotation in sides. They must be modified by users using `\wraplinenumannotation`. By default, they call `\textsuperscript`.

```
2474 \def\Xwraplinenumannotation@ref{\textsuperscript}%
2475 \def\Xwraplinenumannotation@side{\textsuperscript}%
2476 %
```

`\@cannot` Then, the numbered files command `\@cannot`, which

`\store@cannot@to@absline`

- associates the annotation to the absolute lines number.
- stores the current annotation in a macro to be used by the `\@ref@reg` macro, which manages all things related to `\edtext` in numbered files. As we don't want to store it multiple times in the event of nested `\edtext`, we use an auxiliary macro, `\store@cannot@to@absline`, which is set to `\gobble` when we parse nested `\edtext` in numbered auxiliary files.

```
2477 \newcommand{\@cannot}[1]{%
2478   \store@cannot@to@absline{#1}%
2479   \def\current@annot{#1}%
2480 }%
2481 \newcommand{\store@cannot@to@absline}[1]{%
2482   \ifledRcol%
2483     \csgappto{\annotR@\the\absline@numR}{\the\section@numR}{#1}%
2484   \else%
2485     \csgappto{\annot@{\the\absline@num}}{\the\section@num}{#1}%
2486   \fi%
2487 }%
2488 %
```

`\current@annot` By default, there is no annotation to a line number, so we store an empty `\current@annot`

```
2489 \let\current@annot=\empty%
2490 %
```

`\reset@current@annot` `\reset@current@annot` is called at each `\onl` in numbered auxiliary files. It resets the annotation of line numbers at each line.

```
2491 \newcommand{\reset@current@annot}{%
2492   \let\current@annot\empty%
2493 }%
2494 %
```

\parse@annot In the \annot@list list, each individual \edtext is associated with a starting and an ending line number annotation, which is stored this way: start annotation|end annotation
The \parse@annot reads the format and defines two global macros.

```
2495 \def\parse@annot#1|#2|{
2496   \gdef\annot@start{#1}%
2497   \gdef\annot@end{#2}%
2498 }%
2499 %
```

X Line number printing

\affixline@num \affixline@num just puts a left line number into \l@dld@ta or a right line number into \l@drd@ta as required.

To determine whether we need to affix a line number to this line, we compute the following:

$$\begin{aligned} n &= \text{int}((\text{linenum} - \text{firstlinenum}) / \text{linenumincrement}) \\ m &= \text{firstlinenum} + (n \times \text{linenumincrement}) \end{aligned}$$

(where `int` truncates a real number to an integer). m will be equal to `linenum` only if we are to paste a number on here. However, the formula breaks down for the first line to number (and any before that), so we check that case separately: if \line@num \leq \firstlinenum, we compare the two directly instead of making these calculations.

We compute, in the scratch counter \l@dtmpcnta, the number of the next line that should be printed with a number (m in the above discussion), and move the current line number into the counter \l@dtmpcntb for comparison.

First, the case when we are within a sub-line range.

```
2500 \newcommand*{\affixline@num}{%
2501   %
```

No number is attached if \ifl@dskipnumber is TRUE (and then it is set to its normal FALSE value). No number is attached if \ifnumberline is FALSE (the normal value is TRUE).

```
2502 \ifledgroupnotesL@\else
2503   \ifnumberline
2504     \ifl@dskipnumber
2505       \global\l@dskipnumberfalse
2506     \else
2507       \ifsblines@
2508         \l@dtmpcntb=\subline@num
2509         \ifnum\subline@num>\c@firstsublinenum
2510           \l@dtmpcnta=\subline@num
2511           \advance\l@dtmpcnta by-\c@firstsublinenum
2512           \divide\l@dtmpcnta by\c@sblinenumincrement
2513           \multiply\l@dtmpcnta by\c@sblinenumincrement
2514           \advance\l@dtmpcnta by\c@firstsublinenum
```

```

2515     \else
2516         \c@l@dtmpcnta=\c@firstsublinenum
2517     \fi
2518 %

```

That takes care of computing the values for comparison, but if line number locking is in effect we have to make a further check. If this check fails, then we disable the line-number display by setting the counters to arbitrary but unequal values.

```

2519     \ch@cksub@l@ck
2520 %

```

Now the line number case, which works the same way.

```

2521     \else
2522         \c@l@dtmpcntb=\line@num
2523 %

```

Check on the `\linenumberlist` If it is `\empty` use the standard algorithm.

```

2524     \ifx\linenumberlist\empty
2525         \ifnum\line@num>\c@firstlinenum
2526             \c@l@dtmpcnta=\line@num
2527             \advance\c@l@dtmpcnta by-\c@firstlinenum
2528             \divide\c@l@dtmpcnta by\c@linenumincrement
2529             \multiply\c@l@dtmpcnta by\c@linenumincrement
2530             \advance\c@l@dtmpcnta by\c@firstlinenum
2531         \else
2532             \c@l@dtmpcnta=\c@firstlinenum
2533         \fi
2534     \else
2535 %

```

The `\linenumberlist` was not `\empty`, so here is Wayne's numbering mechanism. This takes place in TeX's mouth.

```

2536         \c@l@dtmpcnta=\line@num
2537         \edef\rem@nder{\linenumberlist,\number\line@num,}%
2538         \edef\sc@n@list{\def\noexpand\sc@n@list
2539             #####1,\number\c@l@dtmpcnta,#####2|\def\noexpand\rem@nder
2540             {####2}}}}%
2541         \sc@n@list\expandafter\sc@n@list\rem@nder%
2542         \ifx\rem@nder\empty%
2543             \advance\c@l@dtmpcnta\@ne
2544         \fi
2545 %

```

A locking check for lines, just like the version for sub-line numbers above.

```

2546     \ch@ck@l@ck
2547     \fi
2548 %

```

The following tests are true if we need to print a line number.

```

2549 \ifnum\@l@dtempcpta=\@l@dtempcntb
2550   \ifl@dskipversenumber\else
2551 %

```

If we got here, we are going to print a line number; so now we need to calculate a number that will tell us which side of the page will get the line number. We start from `\line@margin`, which asks for one side always if it is less than 2; and then if the side does depend on the page number, we simply add the page number to this side code—because the values of `\line@margin` have been devised so that this produces a number that is even for left-margin numbers and odd for right-margin numbers.

For L^AT_EX we have to consider two column documents as well. In this case Peter Wilson thought we need to put the numbers at the outside of the column—the left of the first column and the right of the second. Do the `twocolumn` stuff before going on with the original code.

```

\l@dld@ta A left line number is stored in \l@dld@ta and a right one in \l@drd@ta.
\l@drd@ta
2552   \if@twocolumn
2553     \if@firstcolumn
2554       \gdef\l@dld@ta{\llap{{\leftlinenum}}}
2555     \else
2556       \gdef\l@drd@ta{\rlap{{\rightlinenum}}}
2557     \fi
2558   \else
2559     \ifboolexpr{bool {\l@dpriintingcolumns} and test {\i
2560 ifnumgreater{\line@margin@columns}{\m@ne}}}{%
2561   {\@l@dtempcntb=\line@margin@columns}%
2562   {\@l@dtempcntb=\line@margin}%
2563   \ifnum\@l@dtempcntb>\@ne
2564     \advance\@l@dtempcntb \page@num
2565   \fi
2566   \ifboolexpr{%
2567     bool {\l@dpriintingcolumns}%
2568     and (%
2569     (test {\ifdefstring{\linenum@OnlyPages@ForColumns}{left
2570 }}}%
2571     and test {\ifnumodd{\page@num}}%
2572   )%
2573   or%
2574   (test {\ifdefstring{\linenum@OnlyPages@ForColumns}{right
2575 }}}%
2576   and not test {\ifnumodd{\page@num}}%
2577   )%
2578 }%
2579   \ifodd\@l@dtempcntb%
2580     \gdef\l@drd@ta{\rlap{{\rightlinenum}}}
2581   \else%

```

```

2582           \gdef\l@ld@ta{\llap{\leftlinenum}}}%
2583           \fi%
2584       }%
2585       \fi
2586   \fi
2587 \fi
2588 %

```

Now fix the lock counters, if necessary. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

2589 \f@x@l@cks
2590   \fi
2591   \fi
2592   \fi
2593 }
2594 %

```

\ch@cksub@l@ck These macros handle line number locking for **\affixline@num**. **\ch@cksub@l@ck** checks subline locking. If it fails, then we disable the line-number display by setting the **\f@x@l@cks** counters to arbitrary but unequal values.

```

2596 \newcommand*{\ch@cksub@l@ck}{%
2597   \ifcase\sub@lock
2598     \or
2599       \ifnum\subblock@disp=\@ne
2600         \z@ \z@ \z@
2601       \fi
2602     \or
2603       \ifnum\subblock@disp=\tw@ \else
2604         \z@ \z@ \z@
2605       \fi
2606     \or
2607       \ifnum\subblock@disp=\z@ \else
2608         \z@ \z@ \z@
2609       \fi
2610     \fi}
2611 %

```

Similarly for line numbers.

```

2612 \newcommand*{\ch@ck@l@ck}{%
2613   \ifcase\@clock
2614     \or
2615       \ifnum\lock@disp=\@ne
2616         \z@ \z@ \z@
2617       \fi
2618     \or
2619       \ifnum\lock@disp=\tw@ \else
2620         \z@ \z@ \z@

```

```

2621      \fi
2622      \or
2623          \ifnum\lock@disp=\z@
2624              \o1@dtmpcntb=\z@ \o1@dtmpcnta=\@ne
2625          \fi
2626      \fi}
2627 %

```

Fix the lock counters. A value of 1 is advanced to 2; 3 advances to 0; other values are unchanged.

```

2628 \newcommand*{\f@x@l@cks}{%
2629     \ifcase\@clock
2630     \or
2631         \global\@clock=\tw@
2632     \or \or
2633         \global\@clock=\z@
2634     \fi
2635     \ifcase\sub@clock
2636     \or
2637         \global\sub@clock=\tw@
2638     \or \or
2639         \global\sub@clock=\z@
2640     \fi}
2641 %
2642 %

```

XI Pstart number printing inside

Inside, the printing of the pstart number runs like the printing of the line number. There are only a few differences:

- The pstarts counter is upgraded in the `\pend` command. Consequently, the `\affixpstart@num` command has not to upgrade it, unlike the `\affixline@num` which upgrades the lines counter.
- To print the pstart number only at the beginning of a pstart, and not in every line, a boolean test is made. The `\pstartnum` boolean is set to TRUE at every `\pend`. It is tried in the `\leftpstartnum` and `\rightstartnum` commands. After the try, it is set to FALSE.

```

\leftpstartnum43
\rightstartnum44 \newif\ifsidepstartnum
\ifsidepstartnum45 \newcommand*{\affixpstart@num}{%
2646     \ifsidepstartnum
2647         \if@twocolumn
2648             \if@firstcolumn
2649                 \gdef\l@ld@ta{\llap{{\leftpstartnum}}}
2650             \else

```

```

2651           \gdef\l@drd@ta{\rlap{{\rightpstartnum}}}%
2652           \fi
2653     \else
2654       \l@dtmpcntb=\line@margin%
2655       \ifnum\l@dtmpcntb>\@ne
2656         \advance\l@dtmpcntb \page@num
2657       \fi
2658       \ifodd\l@dtmpcntb
2659         \gdef\l@drd@ta{\rlap{{\rightpstartnum}}}%
2660       \else
2661         \gdef\l@dld@ta{\llap{{\leftpstartnum}}}%
2662       \fi
2663     \fi
2664   \fi
2665 }
2666 %
2667 %
2668 \newif\ifpstartnum
2669 \pstartnumtrue
2670 \newcommand*{\leftpstartnum}{%
2671   \ifpstartnum\the\pstart
2672   \kern\linenumsep\fi
2673   \global\pstartnumfalse
2674 }
2675 \newcommand*{\rightpstartnum}{%
2676   \ifpstartnum
2677   \kern\linenumsep
2678   \the\pstart
2679   \fi
2680   \global\pstartnumfalse
2681 }
2682 %
2683 %

```

XII Restoring footnotes and penalties

Because of the paragraph decomposition process in order to number line, `reledmac` must hack the standard way `TeX` works in order to manage insertion of footnotes, both critical and familiar.

We need to call the `\insert` commands not when the content of `\pstart...\\pend` is read by `TeX` by when each individual line is typeset.

Consequently, when reading the content of `\pstart...\\pend`, we store the insertion (footnotes) in an specific `reledmac`'s list, and we restore them to the vertical list when printing each individual line.

XII.1 Add insertions to the vertical list

`\inserts@list` `\inserts@list` is the list macro that contains the inserts that we save up for one paragraph.

```
2684 \list@create{\inserts@list}
2685 %
```

`\add@inserts` `\add@inserts` is the penultimate macro used by `\do@line`; it takes insertions saved in a list macro and sends them onto the vertical list.

It may call itself recursively, and to do this efficiently (using TeX's optimization for tail recursion), we define a control-sequence called `\add@inserts@next` that is always the last thing that `\add@inserts` does. If there could be more inserts to process for this line, `\add@inserts@next` is set equal to `\add@inserts`; otherwise it is just `\relax`.

```
2686 \newcommand*{\add@inserts}{%
2687   \global\let\add@inserts@next=\relax
2688 %}
```

If `\inserts@list` is empty, there are not any more notes or insertions for this paragraph, and we need not waste our time.

```
2689 \ifx\inserts@list\empty \else
2690 %
```

The `\next@insert` macro records the number of the line that receives the next footnote or other insert; it is empty when we start out, and just after we have affixed a note or insert.

```
2691 \ifx\next@insert\empty
2692   \ifx\insertlines@list\empty
2693     \global\noteschanged@true
2694     \gdef\next@insert{100000}%
2695   \else
2696     \gl@p\insertlines@list\to\next@insert
2697   \fi
2698 \fi
2699 %
```

If the next insert's for this line, tack it on (and then erase the contents of the insert macro, as it could be quite large). In that case, we also set `\add@inserts@next` so that we will call ourselves recursively: there might be another insert for this same line.

```
2700 \ifnum\next@insert=\absline@num
2701   \gl@p\inserts@list\to@\insert
2702   \cinsert
2703   \global\let@\insert=\undefined
2704   \global\let\next@insert=\empty
2705   \global\let\add@inserts@next=\add@inserts
2706 \fi
2707 \fi
2708 %
```

Make the recursive call, if necessary.

```
2709 \add@inserts@next}
2710 %
2711 %
```

\add@Xgroupbyline If you use `\Xgroupbyline`, the insertion of the critical footnotes are not made immediately in `\add@inserts`, but the content to be inserted is stored, to be inserted in one block. This insertion in one block is made by `\add@Xgroupbyline`.

```
2712 \newcommand{\add@Xgroupbyline}{%
2713   \unless\ifnocritical%
2714     \def\do##1{%
2715       \def\do####1{%
2716         \ifcsdef{##1@forinserting@####1}{%
2717           \X@beforeinsertion{##1}%
2718           \if@ledgroup%
2719             \global\setbox\@nameuse{mp##1footins}=\vbox%
2720           \else%
2721             \insert\csname ##1footins\endcsname%
2722           \fi%
2723         }%
2724         \ifcsdef{Xhsiz\csuse{series@display##1}@##1}{%
2725           \hsiz\csuse{Xhsiz\csuse{series@display##1}@##1}%
2726           {}%
2727           \if@ledgroup%
2728             \unvbox\@nameuse{mp##1footins}%
2729           \fi%
2730           \X@atbegininsertion{##1}%
2731           \ifcsstring{series@display##1}{%
2732             {}%
2733               \Xledsetnormalparstuff{##1}%
2734               \rule\z@\splittopskip%
2735               {}%
2736             {}%
2737             \csuse{##1@forinserting@####1}%
2738             \strut\par%
2739           }%
2740           \global\csundef{##1@forinserting@####1}%
2741           {}%
2742           {}%
2743         }%
2744         \ifcsdef{##1@forinserting}{%
2745           \dolistcsloop{##1@forinserting}%
2746           {}%
2747           \global\csundef{##1@forinserting}%
2748           {}%
2749           \dolistloop{\@series}%
2750           \fi%
2751       }%
2752     }%
```

```
2752
2753
2754 %
```

XII.2 Penalties

`\add@penalties` `\add@penalties` is the last macro used by `\do@line`. It adds up the club, widow, and interline penalties, and puts a single penalty of the appropriate size back into the paragraph; these penalties get removed by the `\vsplit` operation. `\displaywidowpenalty` and `\brokenpenalty` are not restored, since we have no easy way to find out where we should insert them.

In this code, `\num@lines` is the number of lines in the whole paragraph, and `\par@line` is the line we are working on at the moment. The count `\@l@dtempcnta` is used to calculate and accumulate the penalty; it is initially set to the value of `\ballast@count`, which has been worked out in `\do@ballast` above (VIII p. 159). Finally, the penalty is checked to see that it does not go below -10000 .

```
2755 \newcommand*{\add@penalties}{\@l@dtempcnta=\ballast@count
2756   \ifnum\num@lines>\@ne
2757     \global\advance\par@line \@ne
2758     \ifnum\par@line=\@ne
2759       \advance\@l@dtempcnta \clubpenalty
2760     \fi
2761     \@l@dtempcntb=\par@line \advance\@l@dtempcntb \@ne
2762     \ifnum\@l@dtempcntb=\num@lines
2763       \advance\@l@dtempcnta \widowpenalty
2764     \fi
2765     \ifnum\par@line<\num@lines
2766       \advance\@l@dtempcnta \interlinepenalty
2767     \fi
2768   \fi
2769   \ifnum\@l@dtempcnta=\z@
2770     \relax
2771   \else
2772     \ifnum\@l@dtempcnta>-10000
2773       \penalty\@l@dtempcnta
2774     \else
2775       \penalty -10000
2776     \fi
2777   \fi}
2778 %
2779 %
```

XII.3 Printing leftover notes

`\flush@notes` The `\flush@notes` macro is called after the entire paragraph has been sliced up and sent on to the vertical list. If the number of notes to this paragraph has increased since the previous run of TeX, then there can be leftover notes that have not yet been printed.

An appropriate error message will be printed elsewhere; but it is best to go ahead and print these notes somewhere, even if it is not in quite the right place. What we do is dump them all out here, so that they should be printed on the same page as the last line of the paragraph. We can hope that is not too far from the proper location, to which they will move on the next run. For the first run, we do not flush the notes, as that means all the notes will be added at the end of numbered section, and so, very far of the expected position

```

2780 \newcommand{\flush@notes}{%
2781   \iftoggle{notfirstrun@\jobname.\extensionchars\the\section@num}{%
2782     \xloop%
2783       \ifx\inserts@list\empty \else%
2784         \gl@p\inserts@list\to\@insert%
2785         \@insert%
2786         \global\let\@insert=\undefined%
2787         \repeat%
2788   }{}%
2789 }%
2790 %
2791 %
2792 %

```

\xloop *\xloop* is a variant of the PLAIN TeX *\loop* macro, useful when it's hard to construct a positive test using the TeX *\if* commands—as in *\flush@notes* above. One types *\xloop ... \if ... \else ... \repeat*, and the action following *\else* is repeated as long as the *\if* test fails. (This macro will work wherever the PLAIN TeX *\loop* is used, too, so we could just call it *\loop*; but it seems preferable not to change the definitions of any of the standard macros.)

This variant of *\loop* was introduced by Alois Kabelschacht in *TUGboat* 8 (1987), pp. 184–5.

```

2793 \def\xloop#1\repeat{%
2794   \def\body{#1\expandafter\body\fi}%
2795   \body}%
2796 %
2797 %

```

XII.4 Text before notes

\set@Xtxtbeforenotes The *\set@Xtxtbeforenotes* macro resets the *Xtxtbeforesnotes@⟨series⟩@typeset* boolean to false. Just before the first note of the ⟨series⟩ in a page, the *\Xtextbeforenotes* will be inserted.

```

2798 \newcommand{\set@Xtxtbeforenotes}{%
2799   \unless\ifnocritical%
2800     \def\do##1{%
2801       \nottoggle{Xtxtbeforenotesonlyonce@##1}{%
2802         \global\togglefalse{Xtxtbeforesnotes@##1@typeset}%
2803       }{}%
2804     }%

```

```

2804 }%
2805 \dolistloop{\@series}%
2806 \fi%
2807 }%
2808 %

```

`\set@txtbeforenotesX` The `\set@txtbeforenotesX` does the same for the `\textbeforenotesX`.

```

2809 \newcommand{\set@txtbeforenotesX}{%
2810 \unless\ifnofamiliar@%
2811 \def\do##1{%
2812 \notoggle{txtbeforenotesonlyonceX@##1}{%
2813 \global\togglefalse{txtbeforenotesX@##1@typeset}%
2814 }{}}%
2815 }%
2816 \dolistloop{\@series}%
2817 \fi%
2818 }%
2819 %

```

`\insert@Xtxtbeforenotes` `\insert@Xtxtbeforenotes{\langle series \rangle}`, called when inserting a familiar footnote, will insert the text before the note if it is not already inserted. For paragraphed footnotes, it will insert it as a component of the first footnote. For other types of footnotes, it will insert it as a regular footnote.

`\insert@txtbeforenotesX` is the same for familiar footnotes.

```

2820 \newcommand{\insert@Xtxtbeforenotes}[1]{%
2821 \notoggle{Xtxtbeforenotes@#1@typeset}{}%
2822 \global\toggletrue{Xtxtbeforenotes@#1@typeset}%
2823 \ifcscvoid{Xtxtbeforenotes@#1}{}{%
2824 \ifcstrue{series@display#1}{paragraph}{%
2825 {\noindent\csuse{Xtxtbeforenotes@#1}}%
2826 {\expandafter\insert\csname#1footins\endcsname{%
2827 \bgroup%
2828 \noindent%
2829 \ifcstrue{\csuse{series@display#1}@begin@insert}{}{%
2830 {\csuse{\csuse{series@display#1}@begin@insert}{#1}}%
2831 }{}}%
2832 \strut\csuse{Xnotefontsize@#1}%
2833 \csuse{Xtxtbeforenotes@#1}%
2834 \egroup%
2835 }{}}%
2836 }{}}%
2837 }{}}%
2838 }{}}%
2839 }%
2840
2841 \newcommand{\insert@txtbeforenotesX}[1]{%
2842 \notoggle{txtbeforenotesX@#1@typeset}{}%

```

```

2844 \global\toggletrue{txtbeforesnotesX@#1@typeset}%
2845 \ifcsvoid{txtbeforenotesX@#1}{\{}%
2846   \ifcsstring{series@displayX#1}{paragraph}%
2847     {\noindent\csuse{txtbeforenotesX@#1}}%
2848     {\expandafter\insert\csname footins#1\endcsname%
2849       \bgroup%
2850         \noindent%
2851         \ifcsdef{\csuse{series@displayX#1}@begin@insert}{%
2852           \csuse{\csuse{series@displayX#1}@begin@insert}{#1}%
2853         }{}%
2854         \strut\csuse{notefontsizeX@#1}\csuse{txtbeforenotesX@#1}%
2855       \egroup%
2856     }%
2857   }%
2858 }%
2859 {}%
2860 }%
2861 %
2862 %
2863 %

```

XIII Critical footnotes

The footnote macros are adapted from those in PLAIN TeX, but they differ in these respects: the outer-level commands must add other commands to a list macro rather than doing insertions immediately; there are many separate levels of the footnotes, not just one; and there are options to reformat footnotes into paragraphs or into multiple columns.

XIII.1 Fonts

Before getting into the details of formatting the notes, we set up some font macros. It is the notes that present the greatest challenge for our font-handling mechanism, because we need to be able to take fragments of our main text and print them in different forms: it is common to reduce the size, for example, without otherwise changing the fonts used.

`\select@lemmafont` `\select@lemmafont` is provided to set the right font for the lemma in a note. This macro extracts the font specifier from the line and page number cluster, and issues the associated font-changing command, so that the lemma is printed in its original font.

```

2864 \def\select@lemmafont#1|#2|#3|#4|#5|#6|#7|{\select@@lemmafont#7|}%
2865 \def\select@@lemmafont#1/#2/#3/#4|%
2866   {\fontencoding{#1}\fontfamily{#2}\fontseries{#3}\fontshape{#4}%
2867   \selectfont}%
2868 %
2869 %

```

XIII.2 Individual note options

\footnoteoptions@ The \footnoteoption@[*side*] {*options*} {*value*} changes the value of on options of Xfootnote, to switch between true and false.

```

2870 \newcommand*\footnoteoptions@[3]{%
2871   \def\do##1{%
2872     \ifstreq{\#1}{L}{%
2873       \xright@appenditem{\noexpand\setkeys[mac]{#3footnoteoption}{%
2874         unexpanded{##1}}}\to\inserts@list%
2875       \global\advance\insert@count \z@ne% Increment the left insert
2876       counter.%
2877     }%
2878     \xright@appenditem{\noexpand\setkeys[mac]{#3footnoteoption}{%
2879       unexpanded{##1}}}\to\inserts@listR%
2880       \global\advance\insert@countR \z@ne% Increment the right insert
2881       counter insert.%
2882     }%
2883   }%
2884 }
```

XIII.3 Notes language

\footnotelang@lua \footnotelang@lua is called to remember the information about the direction of a lemma when Lua^{AT}E_X is used.

```

2884 \newcommandx*\footnotelang@lua[1][1=L,usedefault]{%
2885   \ifstreq{\#1}{L}{%
2886     \xright@appenditem{\{\csxdef{footnote@luatextdir}{\the\textdir}\}}\to\inserts@list%Know the dir of lemma
2887     \global\advance\insert@count \z@ne%
2888     \xright@appenditem{\{\csxdef{footnote@luatpardir}{\the\pardir}\}}\to\inserts@list%Know the dir of lemma
2889     \global\advance\insert@count \z@ne%
2890   }%
2891   \{%
2892     \xright@appenditem{\{\csxdef{footnote@luatextdir}{\the\textdir}\}}\to\inserts@listR%Know the dir of lemma
2893     \global\advance\insert@countR \z@ne%
2894     \xright@appenditem{\{\csxdef{footnote@luatpardir}{\the\pardir}\}}\to\inserts@listR%Know the dir of lemma
2895     \global\advance\insert@countR \z@ne%
2896   }%
2897 }
```

\footnotelang@poly \footnotelang@poly is called to remember the information about the language of a lemma when polyglossia is used.

```

2899 \newcommandx*\footnotelang[1][1=L,usedefault]{%
2900   \ifstreq{\#1}{L}{%
2901     \if@RTL{%
2902       \xright@appenditem{\{\csxdef{footnote@dir}{@RTLtrue}\}}\to\
2903       inserts@list%Know the language used in the lemma
2904       \global\advance\insert@count \cne{%
2905     }%
2906     \else{%
2907       \xright@appenditem{\{\csxdef{footnote@dir}{@RTLfalse}\}}\to\
2908       inserts@list%Know the language of lemma
2909       \global\advance\insert@count \cne{%
2910     }%
2911     \fi{%
2912       \xright@appenditem{\{\csxdef{footnote@lang}{\expandonce\languagename}\}}\to\
2913       inserts@list%Know the language of lemma
2914       \global\advance\insert@count \cne{%
2915     }%
2916     \else{%
2917       \xright@appenditem{\{\csxdef{footnote@dir}{@RTLfalse}\}}\to\
2918       inserts@listR%Know the language of lemma
2919       \global\advance\insert@countR \cne{%
2920     }%
2921   }%
2922 }%
2923 %

```

XIII.4 General survey of the way we manage notes

The processing of each note is done by four principal macros: the \vfootnote macro takes the text of the footnote and does the \insert; it calls on the \footfmt macro to select the right fonts, print the line number and lemma, and do any other formatting needed for that individual note. Within the output routine, the two other macros, \footstart and \footgroup, are called; the first prints extra vertical space and a footnote rule, if desired; the second does any reformatting of the whole set of the footnotes in this series for this page—such as paragraphing or division into columns—and then sends them to the page.

These four macros, and the other macros and parameters shown here, are distinguished by the ‘series letter’ that indicates which set of the footnotes we are dealing with—A, B, C, D, or E. The series letter always precedes the string *foot* in macro and

parameter names. Hence, for the A series, the four macros are called `\vAfootnote`, `\Afootfmt`, `\Afootstart`, and `\Afootgroup`.

These macros are changed depending of the footnotes arrangement: “normal”, “paragraphed”, “two columns” or “three columns”.

XIII.5 General setup

`\footssplitskips` Some setup code that is common for a variety of the footnotes. The setup is for:

- `\interlinepenalty`.
- `\splittopskip` (skip before last part of notes that flow from one page to another).
- `\splitmaxdepth`.
- `\floatingpenalty`, that is penalty values being added when a long note flows from one page to another. Here, we let it to 0 when we are processing parallel pages in `eledpar`, in order to allow notes to flow from left to right pages and *vice-versa*. Otherwise, we let it to `\@MM`, which is the standard L^AT_EX `\floatingpenalty`.

```

2924 \newcommand*{\footssplitskips}{%
2925   \interlinepenalty=\interfootnotelinepenalty
2926   \unless\ifl@dprintingpages%
2927     \floatingpenalty=\@MM%
2928   \fi%
2929   \splittopskip=\ht\strutbox \splitmaxdepth=\dp\strutbox
2930   \leftskip=\z@skip \rightskip=\z@skip}
2931 %
2932 %

```

`\normalfootnoterule` `\normalfootnoterule` is a standard footnote-rule macro, for use by a `footstart` macro: just the same as the PLAIN T_EX footnote rule.

```

2933 \let\normalfootnoterule=\footnoterule
2934 %

```

XIII.6 Footnotes arrangement

XIII.6.1 User level macro

`\Xarrangement` `\Xarrangement[⟨s⟩]{⟨arrangement⟩}` The command calls, for each series, a specific command which set many counters and commands in order to define specific arrangement.

```

2935 \newcommandx{\Xarrangement}[2][1,usedefault]{%
2936   \def\do##1{%
2937     \csname Xarrangement@##2\endcsname{##1}%
2938   }%

```

```

2939   \ifstrempty{#1}%
2940     {%
2941       \dolistloop{\@series}%
2942     }%
2943   {
2944     \docs vlist{#1}%
2945   }%
2946 }%
2947 %

```

XIII.6.2 Normal footnote

`\Xarrangement@normal` We can now define all the parameters for the series of footnotes; initially they use the “normal” footnote formatting.

What we want to do here is to insert something like the following for each footnote series. (This is an example, not part of the actual `reledmac` code.)

```

\skip\Afootins=12pt plus5pt minus5pt
\count\Afootins=1000
\dimen\Afootins=0.8\vsiz
\let\vAfootnote=\normalvfootnote \let\Afootfmt=\normalfootfmt
\let\Afootstart=\normalfootstart \let\Afootgroup=\normalfootgroup
\let\Afootnoterule=\normalfootnoterule

```

(Read *The TeXbook* in order to understand what are the counter, skip and dimen associated to an insertion.)

Instead of repeating ourselves, we define a `\Xarrangement@normal` macro that makes all these assignments for us, for any given series letter. This command is called when people use `\Xarrangement[⟨series⟩]{normal}`

Now we set up the `\Xarrangement@normal` macro itself. It takes one argument: the footnote series letter.

```

2948 \newcommand*{\Xarrangement@normal}[1]{%
2949   \csgdef{series@display#1}{normal}
2950   \expandafter\let\csname #1footstart\endcsname=\normalfootstart
2951   \expandafter\let\csname v#1footnote\endcsname=\normalvfootnote
2952   \expandafter\let\csname #1footfmt\endcsname=\normalfootfmt
2953   \expandafter\let\csname #1footgroup\endcsname=\normalfootgroup
2954   \expandafter\let\csname #1footnoterule\endcsname=%
2955   \normalfootnoterule
2956   \count\csname #1footins\endcsname=1000
2957   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}
2958   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
2959   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
2960 %

```

The `reledpar` provides tools in order to confine notes to one side. The mechanism is explained in the `reledpar`'s handbook. For now, just retain we need to store default value of the counter associated to the notes `TEX`'s inserts.

```

2961   \csxdef{default@#1footins}{1000}%Use this to confine the notes to one
2962   side only
2963 %

```

Now do the setup for minipage footnotes. We use as much as possible of the normal setup as we can (so the notes will have a similar layout).

```

2963 \ifnoledgroup@\else%
2964   \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
2965   \expandafter\let\csname mp#1footgroup\endcsname=\mpnormalfootgroup
2966   \count\csname mp#1footins\endcsname=1000
2967   \dimen\csname mp#1footins\endcsname=\csuse{Xmaxhnotes@#1}
2968   \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
2969   \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
2970 \fi
2971 }
2972 %
2973 %

```

\normalvfootnote We now begin a series of commands that do ‘normal’ footnote formatting: a format much like that implemented in PLAIN TeX, in which each footnote is a separate paragraph.

\normalvfootnote takes the series letter as #1 and the entire text of the footnote is #2. It does the \insert for this note, calling on the \footfmt macro for this note series to format the text of the note.

```

2974 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalvfootnote}[2]{%
2975   \iftoggle{Xgroupbyline@#1}{%In the case we use \Xgroupbyline, the
      insertion is done later, in \add@Xgroupbyline.
      \prepare@Xgroupbyline{#1}{#2}{\normalvfootnote@inserted}%
2976   }{%In the case we don't use \Xgroupbyline, the insertion is made directly
      \X@beforeinsertion{#1}%
2977   \insert\csname #1footins\endcsname{%
2978     \X@atbegininsertion{#1}%
2979     \normalvfootnote@inserted{#1}{#2}%
2980   }%
2981 }%
2982 }%
2983 }%
2984 }%
2985 %

```

\normalvfootnote@inserted The \normalvfootnote@inserted macro is expanded to the content to be add to a \insert for normal critical footnote.

```

2986 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalvfootnote@inserted}[2]{%
2987   \nottoggle{Xgroupbyline@#1}{\noindent}{}\csuse{Xhooknote@#1}%
2988   \csuse{Xnotefontsize@#1}%
2989   \footsplitskips
2990   \ifl@dpairing\ifl@dpaging\else%
2991     \setXnoteswidthliketwocolumns@{#1}%
2992   \fi\fi%

```

```

2993     \setXnotespositionliketwocolumns@{\#1}%
2994     \spaceskip=\z@skip \xspaceskip=\z@skip%
2995     \csname #1footfmt\endcsname #2{\#1}%
2996 }%
2997 %

```

```

\X@beforeinsertion98 \newcommand{\X@beforeinsertion}[1]{%
2999     \if@ledgroup\else%
3000         \insert@Xtxtbeforenotes{\#1}%
3001     \fi%
3002     \csuse{Xbeforeinserting@\#1}%
3003 }%
3004 %

```

```

\beforeinsertion@X105 \newcommand{\beforeinsertion@X}[1]{%
3006     \if@ledgroup\else%
3007         \insert@txtbeforenotesX{\#1}%
3008     \fi%
3009     \csuse{beforeinsertingX@\#1}%
3010 }%
3011 %

```

```

\X@atbegininsertion112 \newcommand{\X@atbegininsertion}[1]{%
3013     \hsize=\expandafter\dimexpr\csuse{Xwidth@\#1}\relax%
3014 }%
3015 %

```

And somewhat different versions of `\normalvfootnote` and `\normalvfootnote@inserted` for minipages.

```

\mpnnormalvfootnote16 \notbool{parapparatus@}{\newcommand*{\newcommand}{\mpnnormalvfootnote}[2]{%
3017     \iftoggle{Xgroupbyline@{\#1}}{%
3018         \prepare@Xgroupbyline{\#1}{\#2}{\mpnnormalvfootnote@inserted}%
3019     }%
3020     {%
3021         \global\setbox\@nameuse{mp#1footins}%
3022         \vbox{%
3023             \unvbox\@nameuse{mp#1footins}%
3024             \mpnnormalvfootnote@inserted{\#1}{\#2}%
3025         }%
3026     }%
3027 }%
3028 %
3029 %

```

```
\mpnrmalvfootnote@inserted30 \newcommand{\mpnrmalvfootnote@inserted}[2]{%
```

```
3031   \noindent\csuse{Xbhooknote@#1}%
3032   \csuse{Xnotefontsize@#1}%
3033   \hsize\columnwidth%
3034   \parboxrestore%
3035   \color@begingroup%
3036   \csname #1footfmt\endcsname #2{#1}\color@endgroup%
3037 }%
3038 %
```

\normalfootfmt *\normalfootfmt* is a ‘normal’ macro to take the footnote line and page number information (see V.9 p. 105), and the desired text, and output what’s to be printed. Argument #1 contains the line and page number information and lemma font specifier; #2 is the lemma; #3 is the note’s text; #4 is the note’s series. This version is very rudimentary—it uses *\printlines* to print just the range of line numbers, followed by a square bracket, the lemma, and the note text.

```
3039 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalfootfmt}[4]{%
3040   \Xstorelineinfo{#1}{#4}%
3041   \nottoggle{Xgroupbyline@#4}{\Xledsetnormalparstuff{#4}}{}%
3042   \hangindent=\csuse{Xhangindent@#4}%
3043   \everypar{\hangindent=\csuse{Xhangindent@#4}}%
3044   \nottoggle{Xgroupbyline@#4}{\rule{z@}{\splittopskip}}{}%
3045   {\printlinefootnote{#1}{#4}}%
3046   \print@lemma{#1}{#2}{#4}%
3047   \csuse{Xwrapcontent@#4}{#3}%
3048   \nottoggle{Xgroupbyline@#4}{\strut\par}{}%
3049 }%
3050 %}
```

\normalfootstart *\normalfootstart* is a standard footnote-starting macro, called in the output routine whenever there are footnotes of this series to be printed: it skips a bit and then draws a rule.

Any *\footstart* macro must put onto the page something that takes up space exactly equal to the *\skip\footins* value for the associated series of notes. *T_EX* makes page computations based on that *\skip* value, and the output pages will suffer from spacing problems if what you add takes up a different amount of space.

But if the skip *\Xprenotes@* is greater than 0 pt, it is used instead of *\skip\footins* for the first printed series in one page.

The *\leftskip* and *\rightskip* values are both zeroed here. Similarly, these skips are cancelled in the *\vfootnote* macros for the various types of notes. Strictly speaking, this is necessary only if you are using paragraphed footnotes, but we have put it here and in the other *\vfootnote* macros too so that the behavior of *reledmac* in this respect is general across all footnote types. What this means is that any *\leftskip* and *\rightskip* you specify applies to the main text, but not the footnotes. The footnotes continue to be of width *\hsize*.

```
3051 \newcommand*{\normalfootstart}[1]{%
3052 }
```

The first series of notes printed in a page can have a specific skip before it. In order to insert this specific skip without overlap the bottom margin of the page, Maëul Rouquette have defined an algorithm explained in XIX p. 234. Here is part of this algorithm, when the block of notes are ready to be printed.

```

3053   \ifdim\equal{0pt}{\Xprenotes@}{}
3054     {%
3055       \iftoggle{\Xprenotes@}{%
3056         \togglefalse{\Xprenotes@}%
3057         \skip\csname #1footins\endcsname=%
3058           \glueexpr\csuse{\Xprenotes@}+\csuse{\Xafterrule@#1}\relax%
3059         }%
3060       {}%
3061     }%
3062   \vskip\skip\csname #1footins\endcsname%
3063 %

```

And now, the problem of left and right skip for notes. Especially when using one feature of `reledpar` which allows to have the footnotes horizontal size as the size of columns printed by `\Columns`. Read XVI p. 232 for the general description of the problem.

```

3064   \leftskip0pt \rightskip0pt
3065   \ifl@dpairing\else%
3066     \hsize=\old@hsize%
3067   \fi%
3068   \setXnoteswidthliketwocolumns@{\#1}%
3069   \setXnotespositionliketwocolumns@{\#1}%
3070 %

```

And now, print the footnote's rule to finish the footnote's introduction.

```

3071   \print@Xfootnoterule{\#1}%
3072 }%
3073 %

```

\normalfootgroup `\normalfootgroup` is a standard footnote-grouping macro: it sends the contents of the footnote-insert box to the output page without alteration.

```

3074 \newcommand*{\normalfootgroup}[1]{%
3075   \csuse{\Xbhookgroup@#1}%
3076   \unvbox\csname #1footins\endcsname%
3077   \hsize=\old@hsize%
3078 }%
3079 %
3080 %

```

\mpnnormalfootgroup A somewhat different version for minipages. Note that, in this case, we do not make distinctions between the `\Xfootgroup` and `\Xfootstarts` macros.

```

3081 \unless\ifnoledgroup@
3082 \newcommand*{\mpnnormalfootgroup}[1]{{
3083   \vskip\skip\@nameuse{mp#1footins}

```

```

3084 \ifl@dpairing\ifparledgroup%
3085   \leavevemode\marks\parledgroup@{begin}%
3086   \marks\parledgroup@series{\#1}%
3087   \marks\parledgroup@type{Xfootnote}%
3088 \fi\fi\normalcolor%
3089 \ifparledgroup%
3090   \ifl@dpairing%
3091   \else%
3092     \setXnoteswidthliketwocolumns{\#1}%
3093     \setXnotespositionliketwocolumns{\#1}%
3094     \print@Xfootnoterule{\#1}%
3095   \fi%
3096 \else%
3097   \setXnoteswidthliketwocolumns{\#1}%
3098   \setXnotespositionliketwocolumns{\#1}%
3099   \print@Xfootnoterule{\#1}%
3100 \fi%
3101 \setlength{\parindent}{0pt}
3102 \csuse{Xhookgroup{\#1}}%
3103 \unvbox\csname mp{\#1}footins\endcsname}%
3104 \fi
3105 %

```

XIII.6.3 Paragraphed footnotes

The paragraphed-footnote option reformats all the footnotes of one series for a page into a single paragraph; this is especially appropriate when the notes are numerous and brief. The code is based on *The TeXbook*, pp. 398–400, with alterations for our environment. This algorithm uses a considerable amount of save-stack space: a \TeX of ordinary size may not be able to handle more than about 100 notes of this kind on a page.

\Xarrangement@paragraph The `\Xarrangement@paragraph` macro sets up everything for one series of the footnotes so that they will be paragraphed; it takes the series letter as argument. We include the setting of `\count\footins` to 1000 for the footnote series just in case user is switching to paragraphed footnotes after having columnar ones, since they change this value (see below).

The argument of `\Xarrangement@footparagraph` is the letter denoting the series of notes to be paragraphed.

```

3106 \newcommand*{\Xarrangement@paragraph}[1]{%
3107   \csgdef{series@display#1}{paragraph}
3108   \expandafter\let\csname #1footstart\endcsname=\parafootstart
3109   \expandafter\let\csname v#1footnote\endcsname=\paravfootnote
3110   \expandafter\let\csname #1footfmt\endcsname=\parafootfmt
3111   \expandafter\let\csname #1footgroup\endcsname=\parafootgroup
3112   \count\csname #1footins\endcsname=1000
3113   \csxdef{default@#1footins}{1000}%Use this to confine the notes to one
3114   side only
3115   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}

```

```

3115   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3116   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3117   \para@footsetup{#1}
3118 %

```

And the extra setup for minipages.

```

3119 \ifnoledgroup@\else
3120   \expandafter\let\csname mpv#1footnote\endcsname=\mpparavfootnote
3121   \expandafter\let\csname mp#1footgroup\endcsname=\mpparafootgroup
3122   \count\csname mp#1footins\endcsname=1000
3123   \dimen\csname mp#1footins\endcsname=\csuse{Xmaxnotes@#1}
3124   \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3125   \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3126 \fi
3127 }
3128 %

```

\footfudgefiddle For paragraphed footnotes TeX has to estimate the amount of space required. If it underestimates this then the notes may get too long and run off the bottom of the text block. **\footfudgefiddle** can be increased from its default 64 (say, to 70) to increase the estimate.

```

3129 \providetcommand{\footfudgefiddle}{64}
3130 %

```

\para@footsetup **\footparagraph** calls the **\para@footsetup** macro to calculate a special fudge factor, which is the ratio of the **\baselineskip** to the **\hsize**. We assume that the proper value of **\baselineskip** for the footnotes (normally 9 pt) has been set already. The argument of the macro is again the note series letter.

Peter Wilson thinks that **\columnwidth** should be used here for L^AT_EX not **\hsize**. Peter Wilson have also included **\footfudgefiddle**.

```

3131 \newcommand*{\para@footsetup}[1]{{\csuse{Xbhookgroup@#1}\csuse{
3132   Xnotefontsize@#1}
3133   \setXnoteswidthliketwocolumns@{#1}%
3134   \ifcsempty{Xwidth@#1}%
3135     {}%
3136     {\columnwidth=\expandafter\dimexpr\csuse{Xwidth@#1}\relax}%
3137   \dimen0=\baselineskip
3138   \multiply\dimen0 by 1024
3139   \divide\dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\relax
3140   \csxdef{#1footfudgefactor}{%
3141     \expandafter\strip@pt\dimen0 }}}
3142 %

```

\strip@pt strip the characters pt from a dimen value.

\parafootstart \parafootstart is the same as \normalfootstart, but we give it again to ensure that \rightskip and \leftskip are zeroed (this needs to be done before \para@footgroup in the output routine). The size of paragraphed notes is calculated using a fudge factor which in turn is based on \hsize. So the paragraph of notes needs to be that wide.

The argument of the macro is again the note series letter.

```

3143 \newcommand*{\parafootstart}[1]{%
3144   \rightskip=0pt \leftskip=0pt%
3145   \notoggle{Xparindent@#1}{\parindent=\z@}{}
3146   \ifdim\equal{0pt}{\Xprenotes@}{}
3147     {%
3148       \iftoggle{\Xprenotes@}{%
3149         \togglefalse{\Xprenotes@}%
3150         \skip\csname #1footins\endcsname=%
3151         \glueexpr\csuse{\Xprenotes@}+\csuse{\Xafterrule@#1}\relax%
3152       }%
3153     {}%
3154   }%
3155   \vskip\skip\csname #1footins\endcsname%
3156   \setXnoteswidthliketwocolumns@{#1}%
3157   \setXnotespositionliketwocolumns@{#1}%
3158   \print@Xfootnoterule{#1}%
3159   \let\bidi@RTL@everypar\empty%
3160   \noindent\leavevmode}
3161 %

```

\paravfootnote \paravfootnote is a version of the \vfootnote command that is used for paragraphed notes. It gets appended to the \inserts@list list by an outer-level footnote command like \Afootnote. The first argument is the note series letter; the second is the full text of the printed note itself, including line numbers, lemmata, and footnote text.

The initial model for this insertion is, of course, the \insert\footins definition in *The TeXbook*, p. 398. There, the footnotes are first collected up in hboxes, and these hboxes are later unpacked and stuck together into a paragraph.

However, Michael Downes has pointed out that because text in hboxes gets typeset in restricted horizontal mode, there are some undesirable side-effects if you later want to break such text across lines. In restricted horizontal mode, where TeX does not expect to have to break lines, it does not insert certain items like \discretionary. If you later unbox these hboxes and stick them together, as the *TeXbook* macros do to make these footnotes, you lose the ability to hyphenate after an explicit hyphen. This can lead to overfull \hboxes when you would not expect to find them, and to the uninitiated it might be very hard to see why the problem had arisen.³²

Wayne Sullivan pointed out to us another subtle problem that arises from the same cause: TeX also leaves the \language whatsit nodes out of the horizontal list.³³ So changes from one language to another will not invoke the proper hyphenation rules in

³²Michael Downes, ‘Line Breaking in \unboxed Text’, *TUGboat* 11 (1990), pp. 605–612.

³³See *The TeXbook*, p. 455 (editions after January 1990).

such footnotes. Since critical editions often do deal with several languages, especially in a footnotes, we really ought to get this bit of code right.

To get around these problems, Wayne suggested emendations to the *TeXbook* versions of these macros which are broadly the same as those described by Michael: the central idea (also suggested by Donald Knuth in a letter to Michael) is to avoid collecting the text in an `\hbox` in the first place, but instead to collect it in a `\vbox` whose width is (virtually) infinite. The text is therefore typeset in unrestricted horizontal mode, as a paragraph consisting of a single long line. Later, there is an extra level of unboxing to be done: we have to unpack the `\vbox`, as well as the `\hbox`s inside it, but that is not too hard. For details, we refer you to Michael's article, where the issues are clearly explained.³⁴ Michael's unboxing macro is called `\Xunvxh`: unbox, extract the last line, and `unhbox` it.

Doing things this way has an important consequence: as Michael pointed out, you really can't put an explicit line-break into a note built in a `\vbox` the way we are doing.³⁵ In other words, be very careful not to use `\break`, or `\penalty-10000`, or any equivalent inside your para-footnote. If you do, most of the note will probably disappear. You *are* allowed to make strong suggestions; in fact `\penalty-9999` will be quite okay. Just do not make the break mandatory. We have not applied any of Michael's solutions here, since we feel that the problem is exiguous, and `reledmac` is quite baroque enough already. If you think you are having this problem, look up Michael's solutions.

One more thing: we set `\leftskip` and `\rightskip` to zero. This has the effect of neutralizing any such skips which may apply to the main text (cf. XIII.6.2 p. 182 above). We need to do this, since `\footfudgefactor` is calculated on the assumption that the notes are `\hsize` wide.

So, finally, here is the modified foot-paragraph code, which sets the footnote in vertical mode so that language and discretionary nodes are included.

```

3162 \newcommand*{\paravfootnote}[2]{%
3163   \csuse{Xbeforeinserting@#1}%
3164   \insert\csname #1footins\endcsname
3165   \bgroup
3166     \csuse{Xnotefontsize@#1}
3167     \footsplitskips
3168     \setbox0=\vbox{\hsize=\maxdimen%
3169       \let\bidi@RTL@everypar\@empty%
3170       \insert\Xtxtbeforenotes{#1}%
3171       \noindent\csuse{Xhooknote@#1}%
3172       \csname #1footfmt\endcsname #2{#1}}%
3173     \setbox0=\hbox{\Xunvxh{0}{#1}}%
3174     \dp0=0pt
3175     \ht0=\csname #1footfudgefactor\endcsname\wd0
3176   %

```

Here we produce the contents of the footnote from box 0, and add a penalty of 0 between boxes in this insert.

³⁴Wayne supplied his own macros to do this, but since they were almost identical to Michael's, Peter Wilson have used the latter's `\Xunvxh` macro since it is publicly documented.

³⁵'Line Breaking', p. 610.

```

3177   \if@RTL\noindent \leavevmode\fi\box0%
3178   \penalty0
3179   \egroup}
3180
3181 %

```

The final penalty of 0 was added here at Wayne's suggestion to avoid a weird page-breaking problem, which occurs on those occasions when TeX attempts to split foot paragraphs. After trying out such a split (see *The TeXbook*, p. 124), TeX inserts a penalty of -10000 here, which nearly always forces the break at the end of the whole footnote paragraph (since individual notes can't be split) even when this leads to an overfull vbox. The change above results in a penalty of 0 instead which allows, but does not force, such breaks. This penalty of 0 is later removed, after page breaks have been decided, by the \unpenalty macro in \makehboxofhboxes. So it does not affect how the footnote paragraphs are typeset (the notes still have a penalty of -10 between them, which is added by \parafootfmt).

\mpparavfootnote This version is for minipages.

```

3182 \newcommand*{\mpparavfootnote}[2]{%
3183   \global\setbox\@nameuse{mp#1footins}\vbox{%
3184     \unvbox\@nameuse{mp#1footins}%
3185     \csuse{Xnotefontsize@#1}%
3186     \footsplitskips%
3187     \setbox0=\vbox{\hsize=\maxdimen%
3188       \let\bidi@RTL@everypar\empty%
3189       \insert\Xtxtbeforenotes{#1}%
3190       \noindent\color@begingroup%
3191       \csuse{Xbhooknote@#1}%
3192       \csname #1footfmt\endcsname #2{#1}\color@endgroup}%
3193     \setbox0=\hbox{\Xunvxh{0}{#1}}%
3194     \dp0=\z@%
3195     \ht0=\csname #1footfudgefactor\endcsname\wd0%
3196     \box0%
3197     \penalty0%
3198   }%
3199
3200 %

```

\Xunvxh Here is (modified) Michael's definition of \unvxh, used above. Michael's macro also takes care to remove some unwanted penalties and glue that TeX automatically attaches to the end of paragraphs. When TeX finishes a paragraph, it throws away any remaining glue, and then tacks on the following items: a \penalty of 10000, a \parfillskip and a \rightskip (*The TeXbook*, pp. 99–100). \unvxh cancels these unwanted paragraph-final items using \unskip and \unpenalty.

```

3201 \newcommand*{\Xunvxh}[2]{%
3202   \setbox0=\vbox{\unvbox#1%
3203   \global\setbox1=\lastbox}%
3204   \unhbox1

```

```

3205 \unskip          % remove \rightskip,
3206 \unskip          % remove \parfillskip,
3207 \unpenalty       % remove \penalty of 10000,
3208 \hskip\csuse{Xafternote@#2}\relax% add the glue to go between the notes
3209 %
3210 %

```

\parafootfmt \parafootfmt is \normalfootfmt adapted to do the special stuff needed for paragraphed notes – leaving out the \endgraf at the end, sticking in special penalties and kern and leaving out the \footstrut. The first argument is the line and page number information, the second is the lemma, the third is the text of the footnote, and the fourth is the series (optional, for backward compatibility).

```

3211 \newcommand*{\parafootfmt}[4]{%
3212   \Xstorelineinfo{#1}{#4}%
3213   \Xinsertparafootsep{#4}%
3214   \ledsetnormalparstuff@common%
3215   \printlinefootnote{#1}{#4}%
3216   \print@lemma{#1}{#2}{#4}%
3217   \csuse{Xwrapcontent@#4}{#3}%
3218   \penalty-10 }
3219 %

```

Note that in the above definition, the penalty of -10 encourages a line break between notes, so that notes have a slight tendency to begin on new lines. The \Xinsertparafootsep command is used to insert the \Xparafootsep@series between each note in the *same* page.

\parafootgroup This footgroup code is modelled on the macros in *The TeXbook*, p. 399. The only difference is the \unpenalty in \makehboxofhboxes, which is there to remove the penalty of 0 which was added to the end of each footnote by \paravfootnote.

The call to \Xnotefontsize@ $\langle s \rangle$ is to ensure that the correct \baselineskip for the footnotes is used. The argument is the note series letter.

```

3220 \newcommand*{\parafootgroup}[1]{%
3221   \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3222   \unvbox\csname #1footins\endcsname
3223   \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
3224   \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
3225   \makehboxofhboxes
3226   \setbox0=\hbox{\unhbox0 \removehboxes}%
3227   \csuse{Xbhookgroup@#1}%
3228   \csuse{Xnotefontsize@#1}%
3229   \unhbox0\par%
3230   \global\hsize=\old@hsize%
3231 }%
3232 %
3233 %

```

\mpparafootgroup The minipage version.

```

3234 \newcommand*{\mpparafootgroup}[1]{%
3235   \setXnoteswidthliketwocolumns@{#1}%
3236   \vskip\skip\cnameuse{mp#1footins}
3237   \ifl@dpairing\ifparledgroup%
3238     \leavevmode\marks\parledgroup@{begin}%
3239     \marks\parledgroup@series{#1}%
3240     \marks\parledgroup@type{Xfootnote}%
3241   \fi\fi\normalcolor
3242   \ifparledgroup%
3243     \ifl@dpairing%
3244     \else%
3245       \setXnoteswidthliketwocolumns@{#1}%
3246       \setXnotespositionliketwocolumns@{#1}%
3247       \print@Xfootnoterule{#1}%
3248     \fi%
3249   \else%
3250     \setXnoteswidthliketwocolumns@{#1}%
3251     \setXnotespositionliketwocolumns@{#1}%
3252     \print@Xfootnoterule{#1}%
3253   \fi%
3254   \unvbox\csname mp#1footins\endcsname
3255   \ifcsstring{Xragged@#1}{L}{\RaggedLeft}{}%
3256   \ifcsstring{Xragged@#1}{R}{\RaggedRight}{}%
3257   \makehboxofhboxes
3258   \setbox0=\hbox{\unhbox0 \removehboxes}%
3259   \csuse{Xhookgroup@#1}%
3260   \csuse{Xnotefontsize@#1}%
3261   \notoggle{Xparindent@#1}{\parindent=\z@}{}%
3262   \unhbox0\par}
3263 %
3264 %

```

And finally, the two macros which are required to transform the long horizontal box stored in the insert' box to a printable text.

```

\makehboxofhboxes65 \newcommand*{\makehboxofhboxes}{\setbox0=\hbox{}%
\removehboxes66 \loop
3267   \unpenalty
3268   \setbox2=\lastbox
3269   \ifhbox2
3270     \setbox0=\hbox{\box2\unhbox0}%
3271   \repeat}
3272 \newcommand*{\removehboxes}{\setbox0=\lastbox
3273   \ifhbox0{\removehboxes}\unhbox0 \fi}
3274 %
3275 %
3276 %

```

Insertion of the footnotes separator The command `\Xinsertparafootsep{<series>}` must be called at the beginning of `\parafootfmt`.

```

\prevpage@num77 \newcommand{\Xinsertparafootsep}[1]{%
\Xinsertparafootsep78   \ifldRcol@%
 3279     \ifnumequal{\csuse{#1prevpage@numR}}{\page@numR}%
    {\ifcsdef{prevline#1}{ Be sur \prevline#1 exists.%
      \ifcsequal{prevline#1}{lineinfo@}{%
        {\ifcsempty{Xsymlinenum@#1}{\csuse{Xparafootsep@#1}{}{}}%
          {\csuse{Xparafootsep@#1}}%}
      }%
    }%
    {\csuse{Xparafootsep@#1}}%
  }%
  \global\csname #1prevpage@numR\endcsname=\page@numR%
\else%
 3290     \ifnumequal{\csuse{#1prevpage@num}}{\page@num}%
    {\ifcsdef{prevline#1}{ Be sur \prevline#1 exists.%
      \ifcsequal{prevline#1}{lineinfo@}{%
        {\ifcsempty{Xsymlinenum@#1}{\csuse{Xparafootsep@#1}{}{}}%
          {\csuse{Xparafootsep@#1}}%}
      }%
    }%
    {\csuse{Xparafootsep@#1}}%
  }%
  \global\csname #1prevpage@num\endcsname=\page@num%
\fi%
}%
\%
}

```

XIII.6.4 Columnar footnotes

Common tools

`\rigidbalance` We will now define macros for three-column notes and two-column notes. Both sets of macros will use `\rigidbalance`, which splits a box (#1) into a number (#2) of columns, each with a space (#3) between the top baseline and the top of the `\vbox`. The `\rigidbalance` macro is taken from *The TeXbook*, p. 397, with a slight change to the syntax of the arguments so that they do not depend on white space. Note also the extra unboxing in `\splitoff`, which allows the new `\vbox` to have its natural height as it goes into the alignment.
`\rigidbalanceX`
`\Xrigidbalance`
`\dosplits`
`\splitoff`
`\@h`
`\@k`

The `\line` macro has no relationship to the TeX `\line`. The `\ETEX` equivalent is `\@@line`.

We do not call directly `\rigidbalance`, but we call `\Xrigidbalance` for critical notes and `\rigidbalanceX` for familiar notes. Both of them call `\rigidbalance`.

```

3303 \newcount\@k \newdimen\@h
3304 \newcommand*\Xrigidbalance[3]{%
 3305   \hsize=\expandafter\dimexpr\csuse{Xwidth@\@currentseries}\relax%

```

```

3306     \rigidbalance{#1}{#2}{#3}%
3307 }%
3308
3309 \newcommand*{\rigidbalanceX}[3]{%
3310     \hsize=\expandafter\dimexpr\csuse{widthX@\@currentseries}\relax%
3311     \rigidbalance{#1}{#2}{#3}%
3312 }%
3313
3314 \newcommand*{\rigidbalance}[3]{%
3315     \setbox0=\box#1 \kern#2 \hskip#3%
3316     \vbadness=\OM \hfilneg
3317     \valign{##\vfil\cr\dosplits}}}
3318
3319 \newcommand*{\dosplits}{\ifnum\kern>0 \noalign{\hfil}\splitoff
3320     \global\advance\kern-1\cr\dosplits\fi}
3321
3322 \newcommand*{\splitoff}{\dimen0=\ht0
3323     \divide\dimen0 by\kern \advance\dimen0 by\kern
3324     \setbox2 \vsplit0 to \dimen0
3325     \unvbox2 }
3326
3327 %

```

Three columns

```

\Xarrangement@threecol 28 \newcommand*{\Xarrangement@threecol}[1]{%
3329     \csgdef{series@display#1}{threecol}
3330     \expandafter\let\csname v#1footnote\endcsname=\threecolvfootnote
3331     \expandafter\let\csname #1footfmt\endcsname=\threecolfootfmt
3332     \expandafter\let\csname #1footgroup\endcsname=\threecolfootgroup
3333     \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}%
3334     \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
3335     \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
3336     \threecolfootsetup{#1}
3337 %

```

The additional setup for minipages.

```

3338 \ifnoledgroup@ \else
3339     \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
3340     \expandafter\let\csname mp#1footgroup\endcsname=\mpthreecolfootgroup
3341     \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
3342     \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
3343     \mpthreecolfootsetup{#1}
3344 \fi
3345 %
3346 %
3347 %

```

The `\footstart` and `\footnoterule` macros for these notes assume the normal values (XIII.6.2 p. 182 above).

`\threecolfootsetup` The `\threecolfootsetup` macro calculates and sets some numbers for three-column footnotes.

We set the `\count` of the foot insert to 333. Each footnote can be thought of as contributing only one third of its height to the page, since the footnote insertion has been made as a long narrow column, which then gets trisectioned by the `\rigidbalance` routine (inside `\threecolfootgroup`). These new, shorter columns are saved in a box, and then that box is *put back* into the footnote insert, replacing the original collection of the footnotes. This new box is, therefore, only about a third of the height of the original one.

The `\dimen` value for this note series has to change in the inverse way: it needs to be three times the actual limit on the amount of space these notes are allowed to fill on the page, because when TeX is accumulating material for the page and checking that limit, it does not apply the `\count` scaling.

```
3348 \newcommand*{\threecolfootsetup}[1]{%
3349   \count\csname #1footins\endcsname 333
3350   \csxdef{default@#1footins}{333}%Use this to confine the notes to one
      side only
3351   \multiply\dimen\csname #1footins\endcsname \thr@@%
3352 }
```

`\mpthreecolfootsetup` The setup for minipages.

```
3353 \newcommand*{\mpthreecolfootsetup}[1]{%
3354   \count\csname mp#1footins\endcsname 333
3355   \multiply\dimen\csname mp#1footins\endcsname \thr@@%
3356
3357 }%
```

`\threecolvfootnote` `\threecolvfootnote` This is the `\vfootnote` command for three-column notes. However, most of the code is deported on `\threecolvfootnote@inserted`. The call to `\Xnotefontsize@{s}` ensures that the `\splittopskip` and `\splitmaxdepth` take their values from the right `\strutbox`: the one used in a footnotes. Note especially the importance of temporarily reducing the `\hsize` to 0.3 of its normal value. This determines the widths of the individual columns. So if the normal `\hsize` is (say) 10 cm, then each column will be $0.3 \times 10 = 3$ cm wide, leaving a gap of 1 cm spread equally between columns (i.e., .5 cm between each).

The arguments are #1 the note series letter and #1 the full text of the note (including numbers, lemma and text).

```
3358 \notbool{parapparatus@}{\newcommand*{\newcommand}{\threecolvfootnote}[2]{%
3359   \iftoggle{Xgroupbyline@#1}{%
3360     \prepare@Xgroupbyline{#1}{#2}{\threecolvfootnote@inserted}%
3361   }%
3362 }}
```

```

3363      \X@beforeinsertion{#1}%
3364      \insert\csname #1footins\endcsname{%
3365          \threecolvfootnote@inserted{#1}{#2}%
3366      }%
3367  }%
3368 }%
3369 %

```

```

\threecolvfootnote@inserted70 \notbool{parapparatus@}{\newcommand*{\newcommand}{\threecolvfootnote@inserted}[2]{%
3371      \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
3372      \noindent\csuse{Xhooknote@#1}%
3373      \csuse{Xnotefontsize@#1}%
3374      \footskip%
3375      \csname #1footfmt\endcsname #2{#1}%
3376  }%
3377 %

```

\threecolfootfmt *\threecolfootfmt* is the command that formats one note. The arguments are #1 the line numbers, #2 the lemma and #4 the text of the -footnote command #4 optional (for backward compatibility): the series.

```

3378 \notbool{parapparatus@}{\newcommand*{\newcommand}{\threecolfootfmt}[4]{%
3379      \Xstorelineinfo{#1}{#4}%
3380      \threecol@begin@insert{#4}%
3381      \hspace{\parindent}%
3382      \printlinefootnote{#1}{#4}%
3383      \print@lemma{#1}{#2}{#4}%
3384      \csuse{Xwrapcontent@#4}{#3}%
3385      \nottoggle{Xgroupbyline@#4}%
3386          {\strut\par\allowbreak}%
3387      {}%
3388  }%
3389 %

```

\threecol@begin@insert The *\threecol@begin@insert* contains code used at the beginning of any *\insert* for critical footnotes in three columns. It is used both by *\threecolfootfmt* and by *\insert@Xtxtbeforenotes*.

```

3390 \newcommand{\threecol@begin@insert}[1]{%
3391     \normal@pars%
3392     \nottoggle{Xgroupbyline@#1}%
3393         {\hsize \csuse{Xsizethreecol@#1}}%
3394     {}%
3395     \nottoggle{Xparindent@#1}{\parindent=\z@}{}%
3396     \tolerance=5000%
3397     \hangindent=\csuse{Xhangindent@#1}%
3398     \everypar{\hangindent=\csuse{Xhangindent@#1}}%
3399     \tempdima=\parindent%

```

```

3400   \csuse{Xcolalign@#1}%
3401   \parindent=\@tempdima%
3402   \strut%
3403 }%
3404 %

```

\threecolfootgroup And here is the `footgroup` macro that is called within the output routine to regroup the notes into three columns. Once again, the call to `\Xnotefontsize@s` is there to ensure that it is the right `\splittopskip`—the one used in footnotes—which is used to provide the third argument for `\rigidbalance`. This third argument (`\@h`) is the `topskip` for the box containing the text of the footnotes, and does the job of making sure the top lines of the columns line up horizontally. In *The TeXbook*, p. 398, Donald Knuth suggests retrieving the ouput of `\rigidbalance`, putting it back into the insertion box, and then printing the box. Here, we just print the `\line` which comes out of `\rigidbalance` directly, without any re-boxing.

```

3405 \newcommand*{\threecolfootgroup}[1]{%
3406   \csuse{Xbhookgroup@#1}\par%
3407   \splittopskip=\ht\strutbox
3408   \expandafter
3409   \Xrigidbalance\csname #1footins\endcsname \thr@@ \splittopskip}
3410 %

```

\mpthreecolfootgroup The setup for minipages.

```

3411 \newcommand*{\mpthreecolfootgroup}[1]{{%
3412   \vskip\skip\@nameuse{mp#1footins}
3413   \ifl@dpairing\ifparledgroup%
3414     \leavevmode\marks\parledgroup@{begin}%
3415     \marks\parledgroup@series{#1}%
3416     \marks\parledgroup@type{Xfootnote}%
3417   \fi\fi\normalcolor
3418   \ifparledgroup%
3419     \ifl@dpairing%
3420     \else%
3421       \setXnoteswidthliketwocolumns{#1}%
3422       \setXnotespositionliketwocolumns{#1}%
3423       \print@Xfootnoterule{#1}%
3424     \fi%
3425   \else%
3426     \setXnoteswidthliketwocolumns{#1}%
3427     \setXnotespositionliketwocolumns{#1}%
3428     \print@Xfootnoterule{#1}%
3429   \fi%
3430   \csuse{Xbhookgroup@#1}\par%
3431   \splittopskip=\ht\strutbox
3432   \expandafter
3433   \Xrigidbalance\csname mp#1footins\endcsname \thr@@ \splittopskip}}%
3434 %

```

Two columns

```
\Xarrangement@twocol3436 \newcommand*{\Xarrangement@twocol}[1]{%
 3437   \csgdef{series@display#1}{twocol}
 3438   \expandafter\let\csname v#1footnote\endcsname=\twocolvfootnote
 3439   \expandafter\let\csname #1footfmt\endcsname=\twocolfootfmt
 3440   \expandafter\let\csname #1footgroup\endcsname=\twocolfootgroup
 3441   \dimen\csname #1footins\endcsname=\csuse{Xmaxhnotes@#1}%
 3442   \skip\csname #1footins\endcsname=\csuse{Xbeforenotes@#1}%
 3443   \advance\skip\csname #1footins\endcsname by\csuse{Xafterrule@#1}%
 3444   \twocolfootsetup{#1}
 3445 %
```

The additional setup for minipages.

```
3446 \ifnoledgroup@ \else
 3447   \expandafter\let\csname mpv#1footnote\endcsname=\mpnormalvfootnote
 3448   \expandafter\let\csname mp#1footgroup\endcsname=\mptwocolfootgroup
 3449   \skip\csname mp#1footins\endcsname=\csuse{Xbeforenotes@#1}%
 3450   \advance\skip\csname mp#1footins\endcsname by\csuse{Xafterrule@#1}%
 3451   \mptwocolfootsetup{#1}
 3452 \fi
 3453 }
 3454 %
 3455 %
```

\twocolfootsetup Here is a series of macros which are very similar to their three-column counterparts. In this case, each note is assumed to contribute only a half a line of text. And the notes are set in columns giving a gap between them of one tenth of the `\hsize`.

```
\twocolfootnote3456 \newcommand*{\twocolfootnote}[1]{%
 3457   \count\csname #1footins\endcsname 500
 3458   \csxdef{default@#1footins}{500}%
 3459   \multiply\dimen\csname #1footins\endcsname \tw@%
 3460 %

 3461 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolvfootnote}[2]{%
 3462   \iftoggle{Xgroupbyline@#1}{%
 3463     \prepare@Xgroupbyline{#1}{#2}{\twocolvfootnote@inserted}%
 3464   }{%
 3465     \X@beforeinsertion{#1}%
 3466     \insert\csname #1footins\endcsname{%
 3467       \twocolvfootnote@inserted{#1}{#2}%
 3468     }%
 3469   }%
 3470 }%
 3471 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolvfootnote@inserted}[2]{%
 3472   \hsize=\expandafter\dimexpr\csuse{Xwidth@#1}\relax%
 3473   \noindent\csuse{Xhooknote@#1}%
}
```

```

3474     \csuse{Xnotefontsize@#1}%
3475     \footskip%
3476     \csname #1footfmt\endcsname #2{#1}%
3477 }%
3478 %

3479 \notbool{parapparatus@}{\newcommand*{\newcommand}{\twocolfootfmt}[4]{%
3500   4th
3501   arg is optional, for backward compatibility
3502   \Xstorelineinfo{#1}{#4}%
3503   \twocol@begin@insert{#4}%
3504   \hspace{\parindent}%
3505   \printlinefootnote{#1}{#4}%
3506   \print@lemma{#1}{#2}{#4}%
3507   \csuse{Xwrapcontent@#4}{#3}%
3508   \nottoggle{Xgroupbyline@#4}%
3509   {\strut\par\allowbreak}%
3510 }%
3511 }%
3512 %

3513 \newcommand{\twocol@begin@insert}[1]{%
3514   \normal@pars%
3515   \hsize \csuse{Xhsize@#1}%
3516   \nottoggle{Xparindent@#1}{\parindent=\z@}{}%
3517   \tolerance=5000%
3518   \hangindent=\csuse{Xhangindent@#1}%
3519   \everypar{\hangindent=\csuse{Xhangindent@#1}}%
3520   \tempdima=\parindent%
3521   \csuse{Xcolalign@#1}%
3522   \parindent=\tempdima%
3523   \strut%
3524 }%
3525 %

3526 \newcommand*{\twocolfootgroup}[1]{%
3527   \csuse{Xbhookgroup@#1}\par%
3528   \splittopskip=\ht\strutbox
3529   \expandafter
3530   \Xrigidbalance\csname #1footins\endcsname \tw@ \splittopskip}
3531 %

3532 %

```

\mptwocolfootsetup The versions for minipages.

```

\mptwocolfootgroup
3511 \newcommand*{\mptwocolfootsetup}[1]{%
3512   \count\csname mp#1footins\endcsname 500
3513   \multiply\dimen\csname mp#1footins\endcsname \tw@}
3514 %

3515 \newcommand*{\mptwocolfootgroup}[1]{%
3516   \vskip\skip\nameuse{mp#1footins}

```

```

3517 \ifl@dpairing\ifparledgroup%
3518   \leavevmode\marks\parledgroup@\begin{%
3519     \marks\parledgroup@series{\#1}%
3520     \marks\parledgroup@type{Xfootnote}%
3521   }\fi\fi\normalcolor
3522 \ifparledgroup%
3523   \ifl@dpairing%
3524   \else%
3525     \setXnoteswidthliketwocolumns{\#1}%
3526     \setXnotespositionliketwocolumns{\#1}%
3527     \print@Xfootnoterule{\#1}%
3528   \fi%
3529 \else%
3530   \setXnoteswidthliketwocolumns{\#1}%
3531   \setXnotespositionliketwocolumns{\#1}%
3532   \print@Xfootnoterule{\#1}%
3533 \fi%
3534 \csuse{Xbhookgroup@\#1}\par%
3535 \splittopskip=\ht\strutbox
3536 \expandafter
3537 \Xrigidbalance\csname mp#1footins\endcsname \tw@ \splittopskip}%
3538 %
3539 %

```

XIII.7 Critical notes presentation

Here, we define some commons macro which are used in order to print a critical notes, that is a note with 1) line number 2) lemma 3) lemma separator 4) text associated to the lemma.

XIII.7.1 Font tools

\endashchar The fonts that are used for printing notes might not have the character mapping we expect: for example, the Computer Modern font that contains old-style numerals does not contain an en-dash or square brackets, and its period and comma are in odd locations. To allow use of the standard footnote macros with such fonts, we use the following macros for certain characters.

The \endashchar macro is simply an en-dash from the normal font and is immune to changes in the surrounding font. The same goes for the full stop. These two are used in \printlines. The right bracket macro is the same again; it crops up in \normalfootfmt and the other footnote macros for controlling the format of the footnotes.

Note that these commands are not directly called by reledmac, but are enclosed as default value of specific hooks. Consequently, people should not redefine them, but use instead the \Xlinerangeseparator, \Xendlinerangeseparator, \Xsublinesep, \Xendsublinesep and \Xlemmaseparator macros.

With *polyglossia*, each critical note has a \footnote@lang which shows the language of the lemma, and which can be used to switch the bracket from right to left.

```

3540 \def\endashchar{\textnormal{--}}
3541
3542 \newcommand*{\fullstop}{\textnormal{.}}
3543 \def\xsublinesep@side{\fullstop}
3544
3545 \newcommand*{\rbracket}{\textnormal{%
3546   \csuse{text}\csuse{footnote@lang}{%
3547     \ifluatex%
3548       \ifdefstring{\footnote@luatextextdir}{TRT}{\thinspace[]\thinspace}%
3549     \else%
3550       \thinspace\%
3551     \fi\%
3552   }%
3553 }%
3554 %
3555 %

```

XIII.7.2 Pstart number in footnote

`\printpstart` The `\printpstart` macro prints the pstart number for a note.

```

3556 \newcommand{\printpstart}[0]{%
3557   \ifboolexpr{bool{l0dpairing} or bool{l0dprintingpages} or bool{%
3558     l0dprintingcolumns}}{%
3559     \ifledRcol%
3560       \theppstartR%
3561     \else%
3562       \theppstartL%
3563     \fi%
3564   }%
3565   \theppstart%
3566 }%
3567 %

```

XIII.7.3 Lemma printing

`\print@lemma` `\print@lemma` is called inside critical footnotes to print the lemma and the lemma separator (#1: line number and font information, #2: lemma, #3: series).

```

3568 %
3569 \newcommand{\print@lemma}[3]{%
3570   \bgroup%
3571   \nottoggle{Xlemmadisablefontselection@#3}{%
3572     {\select@lemm.getFont#1|}%
3573     {}%
3574   }%
3575   \bgroup%
3576   \csuse{Xlemm.getFont@#3}%

```

```

3576 \csuse{Xwraplemma@#3}{#2}%
3577 \egroup%
3578 \egroup%
3579 \iftoggle{nosep@}{%
3580   \hskip\csuse{Xinplaceoflemmaseparator@#3}%
3581   \relax%
3582 }%
3583 {\ifcsempty{Xlemmaseparator@#3}%
3584   \t%
3585   \hskip\csuse{Xinplaceoflemmaseparator@#3}%
3586   \relax%
3587 }%
3588 \t%
3589 \nobreak%
3590 \hskip\csuse{Xbeforelemmaseparator@#3}%
3591 \csuse{Xlemmaseparator@#3}%
3592 \hskip\csuse{Xafterlemmaseparator@#3}%
3593 \relax%
3594 }%
3595 }%
3596 }%
3597 %

```

XIII.7.4 Line number printing

- \Xstorelineinfo** The `\Xstorelineinfo` macro is used to store some data about line number of the current critical footnote, data which will be reused later for the `\Xnumberonlyfirstinline` and related setting.

#1 footnote specification for the current footnote ; #2 footnote series.

```

3598 \newcommand{\Xstorelineinfo}[2]{%
3599   \l@dp@rsefootspec#1%
3600   \iftoggle{Xnumberonlyfirsttwolines@#2}{%
3601     \xdef\lineinfo@{\l@dparsedstartline - \l@dparsedstartsub - \
3602     \l@dparsedendline - \l@dparsedendsub}%
3603   }%
3604   \xdef\lineinfo@{\l@dparsedstartline - \l@dparsedstartsub}%
3605 }%
3606 }%
3607 %

```

- \printlinefootnote** The `\printlinefootnote` macro is called in each `\<type>footfmt` command. It controls whether the line number is printed or not, according to the series options. Its first argument is the information about lines; its second is the series of the footnote. The printing of the line number is shared in `\printlinefootnotenumbers`.

```

3608 \newcommand{\printlinefootnote}[2]{%
3609   \iftoggle{nonum@}{% Try if the line number must printed for this specific
                      not (by default, yes)

```

```

3610   \hspace{\csuse{Xinplaceofnumber@#2}}%
3611   }%
3612   {%
3613   {%
3614       \iftoggle{Xnonumber@#2}{% Try if the line number must printed (by
3615       default, yes)
3616           {%
3617               \hspace{\csuse{Xinplaceofnumber@#2}}%
3618           }%
3619           {\iftoggle{Xnumberonlyfirstinline@#2}{% If for this series the
3620           line number must be printed only in the first time.
3621               {%
3622                   \ifcsdef{prevline}{%
3623                       {%
3624                           {%
3625                               \ifcsequal{prevline}{\lineinfo}{%
3626                                   {%
3627                                       \hspace{\csuse{Xinplaceofnumber@#2}}%
3628                                   }%
3629                                   {\printsymlinefootnotearea{#2}}%
3630                                   }%
3631                                   {%
3632                                       \printlinefootnotearea{#1}{#2}%
3633                                   }%
3634                                   }%
3635                                   {%
3636                                       \printlinefootnotearea{#1}{#2}%
3637                                   }%
3638                                   }%
3639                                   {%
3640                                       \printlinefootnotearea{#1}{#2}%
3641                                   }%
3642                                   \csxdef{prevline}{\lineinfo}%
3643                                   }%
3644                               }%
3645                           }%
3646                         }%
3647                     }%
3648 %

```

\printsymlinefootnotearea This macro prints the space before the line symbol, changes the font, when prints the line symbol and the space after it.

```

3649 \newcommand{\printsymlinefootnotearea}[1]{%
3650   \hspace{\csuse{Xbeforesymlinenum@#1}}%
3651   \csuse{Xnotenumfont@#1}%
3652   \ifdim\equal{\csuse{Xboxsymlinenum@#1}}{\z@}{%
3653     \csuse{Xsymlinenum@#1}}%

```

```

3654   {\hbox to \csuse{Xboxsymlinenum@#1}%
3655     {\csuse{Xsymlinenum@#1}\hfill}%
3656   }%
3657   \hspace{\csuse{Xaftersymlinenum@#1}}%
3658 }%
3659 %

```

- \printlinefootnotearea** This macro prints the space before the line number, changes the font, then prints the line number and the space after it. It is called by `\printlinefootnote` depending of the options about repeating line numbers. The first argument is line information, the second is the notes series (A, B, C, etc.)

```

3660 \newcommand{\printlinefootnotearea}[2]{%
3661   \printXbeforenumber{#2}%
3662   \csuse{Xnotenumfont@#2}%
3663   \boxfootnotenumbers{#1}{#2}%
3664   \printXafternumber{#2}%
3665 }%
3666 %

```

- \boxfootnotenumbers** Depending on the user settings, this macro will box line numbers (or not). The first argument is line information, the second is the notes series (A, B, C, etc.) The previous `\printlinefootnotearea` calls it.

```

3667 \newcommand{\boxfootnotenumbers}[2]{%
3668   \ifdim\equal{\csuse{Xboxlinenum@#2}}{0pt}{%
3669     \printlinefootnotenumbers{#1}{#2}%
3670   }%
3671   \{%
3672     \hbox to \csuse{Xboxlinenum@#2}%
3673       {%
3674         \IfSubStr{RC}{\csuse{Xboxlinenumalign@#2}}{\hfill}{}
3675         \printlinefootnotenumbers{#1}{#2}%
3676         \IfSubStr{LC}{\csuse{Xboxlinenumalign@#2}}{\hfill}{}
3677       }%
3678   }%
3679 }%
3680 %

```

- \printlinefootnotenumbers** This macro prints, if needed, the pstart number and the line number. The first argument is line information, the second is the notes series (A, B, C, etc.) The previous `\boxlinefootnote` calls it.

```

3681 \newcommand{\printlinefootnotenumbers}[2]{%
3682   \xdef\@currentseries{#2}%
3683   \ifboolexpr{%
3684     (togl{Xpstart@#2} and bool{numberpstart})%
3685     or togl{Xpstarteverytime@#2}}{%
3686   {\printpstart}{}%

```

```

3687 \iftoggle{Xstanza@#2}{%
3688   \ifnumberstanza%
3689     \printstanza%
3690     \csuse{Xstanzaseparator@#2}%
3691   \fi%
3692 }{%
3693 \iftoggle{Xonlypstart@#2}{%
3694   \csuse{Xtxtbeforenumber@#2}%
3695   \printlines#1\ifledRcol@\@Rlineflag\fi|}%
3696 }%
3697 %

```

\printXbeforenumber This macro prints a space (before the line number) in footnote. It is called by **\printlinefootnotearea**. Its only argument is the note series (A, B, C, etc.)

```

3698 \newcommand{\printXbeforenumber}[1]{%
3699   \hspace{\csuse{Xbeforenumber@#1}}%
3700 }%
3701 %

```

\printXafternumber This macro prints the space, adding eventually a **\nobreak**, after the line number, in footnote. It is called by **\printlinefootnotearea**. Its only argument is the series

```

3702 \newcommand{\printXafternumber}[1]{%
3703   \iftoggle{Xnonbreakableafternumber@#1}{\nobreak}{}
3704   \hspace{\csuse{Xafternumber@#1}}%
3705 }%
3706 %

```

If we have decided to print the line number in a specific notes, the **\printlines** macro prints the line numbers for a note—which, in the general case, is a rather complicated task. The seven parameters of the argument are the line numbers as stored in **\l@d@nums**, in the form described on V.9 p. 105: the starting page, line, and sub-line numbers, followed by the ending page, line, and sub-line numbers, and then the font specifier for the lemma.

edmac' creator have defined six boolean in order to know which component of line number description we have to print:

- **\ifl@d@pnum** for page numbers;
- **\ifl@d@ssub** for starting sub-line;
- **\ifl@d@elin** for ending line;
- **\ifl@d@esl** for ending sub-line; and
- **\ifl@d@dash** for the dash between the starting and ending groups.

There is no boolean for the line number because it is always printed.

Maïeul Rouquette has added `\ifl@d@Xtwolines` and `\ifl@d@Xmorethanwolines` to print a symbol which stands for “and subsequent” when there are two, three or more lines. It also defines `\@cannot@start@print` and `\@cannot@end@print` which define annotations associated with the starting and ending line numbers in critical footnotes.

```

\ifl@d@pnum07 \newif\ifl@d@pnum
\ifl@d@ssub08 \newif\ifl@d@ssub
\ifl@d@celin09 \newif\ifl@d@celin
\ifl@d@esl10 \newif\ifl@d@esl
\ifl@d@dash11 \newif\ifl@d@dash
\ifl@d@Xtwolines12 \newif\ifl@d@Xtwolines%
\ifl@d@Xmorethanwolines3713 \newif\ifl@d@Xmorethanwolines%
\let\@cannot@start@print\relax3714
\let\@cannot@end@print\relax3715
%
```

```

\l@dparsefootspec \l@dparsefootspec{\langle spec\rangle}{\langle lemma\rangle}{\langle text\rangle} parses a footnote specification. (lemma) and (text) are the lemma and text respectively. (spec) is the line and page number and lemma font specifier in \l@d@nums style format. The real work is done by \l@dp@rsefootspec which defines macros holding the numeric values. In many cases, this last command is called directly. Just a reminder of the arguments:
\printlines #1 | #2 | #3 | #4 | #5 | #6 | #7
\printlines start-page | line | subline | end-page | line | subline | fontflag
\l@dparsedendsub3717 \newcommand*\l@dparsefootspec[3]{\l@dp@rsefootspec#1}
\def\l@dp@rsefootspec#1|#2|#3|#4|#5|#6|#7|{%
  \gdef\l@dparsedstartpage{#1}%
  \gdef\l@dparsedstartline{#2}%
  \gdef\l@dparsedstartsub{#3}%
  \gdef\l@dparsedendpage{#4}%
  \gdef\l@dparsedendline{#5}%
  \gdef\l@dparsedendsub{#6}%
}
%
```

Initialise the several number value macros.

```

\def\l@dparsedstartpage{0}%
\def\l@dparsedstartline{0}%
\def\l@dparsedstartsub{0}%
\def\l@dparsedendpage{0}%
\def\l@dparsedendline{0}%
\def\l@dparsedendsub{0}%
%
```

`\setprintlines` The macro `\setprintlines` does the work of deciding what numbers should be printed. Its arguments are the same as the first 6 of `\printlines`.

```

3735 \newcommand*{\setprintlines}[6]{%
3736   \let\@cannot@start@print\relax%
3737   \let\@cannot@end@print\relax%
3738   \l@d@pnumfalse%
3739   \l@d@dashfalse%
3740   \l@d@elinfalse%
3741 %

```

We print the page numbers only if: 1) we are doing the lineation by page, and 2) the ending page number is different from the starting page number.a

```

3742 \ifbypage@
3743   \ifnum#4=#1 \else
3744     \l@d@pnumtrue
3745     \l@d@dashtrue
3746   \fi
3747 \fi
3748 %

```

We print the ending line number if: (1) we are printing the ending page number, or (2) the ending line number is different from the starting line number. If either of these conditions is true, we also print the annotation linked to the ending line number annotations.

```

3749 \ifboolexpr{%
3750   bool{\l@d@pnum}%
3751   or not test{\ifnumequal{#2}{#5}}%
3752 }{%
3753   \l@d@elintrue%
3754   \l@d@dashtrue%
3755   \unless\ifx\relax\annot@end%
3756   \def\@cannot@end@print{%
3757     \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{\
3758     annot@end}%
3759   }%
3760 }{%
3761 %

```

We define the starting line number annotation as a merge of the starting annotation and ending annotation if we don't print the ending line number. Otherwise, it is only the starting annotation.

```

3762 \ifl@d@elin%
3763   \def\@cannot@start@print{%
3764     \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{\
3765     annot@start}%
3766   }%
3767 \else%
3768   \ifx\annot@start\annot@end%
3769   \unless\ifx\@cannot@start\relax%

```

```

3770      \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{\
3771          annot@start}%
3772          }%
3773      \fi%
3774  \else%
3775      \ifx\@cannot@end@print\relax%
3776          \def\@cannot@start@print{%
3777              \l@wrapcs@ifnotemptybox{Xwraplinenumannotation@\@currentseries}{\
3778                  \ifx\annot@start\empty\else%
3779                      \annot@start%
3780                      \ifdefined\linerangesep@%
3781                          \linerangesep@%
3782                      \else%
3783                          \csuse{Xlinerangeseparator@\@currentseries}%
3784                      \fi%
3785                      \annot@end%
3786                  }%
3787              }%
3788          \else%
3789              \let\@cannot@start@print\@cannot@end@print%
3790              \let\@cannot@end@print\relax%
3791              \fi%
3792          \fi%
3793      \fi%
3794  %

```

We print the starting sub-line if it is nonzero.

```

3795      \l@d@ssubfalse
3796      \ifnum#3=0 \else
3797          \l@d@ssubtrue
3798      \fi
3799  %

```

We print the ending sub-line if it is nonzero and: (1) it is different from the starting sub-line number, or (2) the ending line number is being printed.

```

3800      \l@d@eslfalse
3801      \ifnum#6=0 \else
3802          \ifnum#6=#3
3803              \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
3804          \else
3805              \l@d@esltrue
3806              \l@d@dashtrue
3807          \fi
3808      \fi%
3809  %

```

However, if the `\Xtwolines` is set for the current series, we do not print the last line number.

```

3810   \ifl@d@dash%
3811     \ifboolexpr{togl{\fulllines@} or test{\ifcsempy{\twolines@\
3812       @currentseries}}}{%
3813       {}%
3814       {%
3815         \setistwofollowinglines{#1}{#2}{#4}{#5}%
3816         \ifboolexpr{%
3817           toglob{\twolinesbutnotmore@}{\@currentseries}%
3818           and not{%
3819             {}%
3820             \bool{istwofollowinglines@}%
3821             }%
3822             {}%
3823             or{%
3824               {}%
3825               (not \ifnumequal{#1}{#4})%
3826                 and \ifgl{\twolinesonlyinsamepage@}{\@currentseries}%
3827                 }%
3828               {}%
3829               {}%
3830               {}%
3831               \l@dashfalse%
3832               \l@Xtwolinestrue%
3833               \l@elinfalse%
3834               \l@eslfalse%
3835               \ifcsempy{\morethan{\twolines@}{\@currentseries}}{%
3836                 {}%
3837                 {\ifistwofollowinglines@ \else{%
3838                   \l@Xmorethan{\twolinestrue}%
3839                   \fi}%
3840                 }%
3841               }%
3842             }%
3843           \fi%
3844         }%
}

```

End of `\setprintlines`.

```

3845 }%
3846 %

```

`\setistwofollowinglines` The `\ifistwofollowinglines` boolean, used by the `\twolines` and related setting, is set to true by `\setistwofollowinglines`. This command takes the following arguments:

- #1 First page number.
- #2 First line number.
- #3 Last page number.

- #4 Last line number.

If #3-#2 = 1, then that means the two lines are subsequent, and consequently `\ifistwofollowinglines` is set to true. However, if we use lineation by page, two given lines can be subsequent if:

- The first line number is equal to the last line number of the first page.
- The last line number is equal to 1.
- #3-#1 is equal to 1.

```

3847 \newif\ifistwofollowinglines%
3848 \newcommand{\setistwofollowinglines}[4]{%
3849   \ifcsdef{lastlinenumberon@#1}%
3850     {\numdef{\tmp}{\csuse{lastlinenumberon@#1}}}%
3851     {\numdef{\tmp}{0}}%
3852   \istwofollowinglines@false%
3853   \ifnumequal{#4-#2}{1}%
3854     {\istwofollowinglines@true}%
3855   {\ifbypage@%
3856     \ifnumequal{#3-#1}{1}%
3857     {%
3858       \ifnumequal{#2}{\tmp}%
3859         {\ifnumequal{#4}{1}{\istwofollowinglines@true}{}%}
3860         {}%
3861     }%
3862     {}%
3863   \fi%
3864 }%
3865 }%
3866 %

```

`\printlines` So, we have decided which part of line number sets will be printed depending of these value. Now we are ready to print them. If the lineation is by pstart, we print the pstart. Arguments are 1) start page number 2) start line number 3) start subline number 4) end page number 5) end line number 6) end subline number 7) font specification 8) side flag

```

3867 \def\printlines#1|#2|#3|#4|#5|#6|#7|#8|{%
3868   \begingroup%
3869 %

```

If we use LuaTeX, ensure we use good text's direction.

```

3870 \ifluatex%
3871   \edef\@tmp{\the\textdir}%
3872   \ifdefstring{\@tmp}{TLT}{}{\textdir TLT}%Test in order to prevent
3873   %spurious space (bug #397)
3874   \fi%
3875 %

```

Decide which part of line number components we will print.

```

3875   \setprintlines{#1}{#2}{#3}{#4}{#5}{#6}%
3876 %

```

One subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could come after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period). So, first, print the start line number.

```

3877   \ifdimequal{\csuse{Xboxstartlinenum@\@currentseries}}{0pt}%
3878     {\bgroup}%
3879     {\leavevmode\hbox to \csuse{Xboxstartlinenum@\@currentseries}\bgroup\hfill}%
3880   \ifcsstring{Xlinenumannotationposition@\@currentseries}{before}%
3881     {\@annot@start@print}%
3882     {}%
3883   \ifl@d@pnum%
3884     \wrap@edcrossref{\@this@crossref@start}{#1}%
3885     \csuse{Xpagelinesep@\@currentseries}%
3886   \fi%
3887   \wrap@edcrossref{\@this@crossref@start}{%
3888     \linenumrep{#2}%
3889     \iftoggle{Xlineflag@\@currentseries}{#8}{()}%
3890   }%
3891   \ifl@d@ssub%
3892     \csuse{Xsublinesep@\@currentseries}%
3893     \wrap@edcrossref{\@this@crossref@start}{\sublinenumrep{#3}}%
3894   \fi
3895   \ifcsstring{Xlinenumannotationposition@\@currentseries}{after}%
3896     {\@annot@start@print}%
3897     {}%
3898   \egroup%
3899 %

```

Then print the dash + end line number, or the range symbol.

```

3900   \ifdimequal{\csuse{Xboxendlinenum@\@currentseries}}{0pt}%
3901     {\bgroup}%
3902     {\hbox to \csuse{Xboxendlinenum@\@currentseries}\bgroup}%
3903   \ifl@d@Xtwolines%
3904     \ifl@d@Xmorethantwolines%
3905       \csuse{Xmorethantwolines@\@currentseries}%
3906     \else%
3907       \csuse{Xtwolines@\@currentseries}%
3908     \fi%
3909   \else%
3910     \ifl@d@dash%
3911       \ifdefined\linerangesep@%
3912         \linerangesep@%
3913       \else%
3914         \csuse{Xlinerangeseparator@\@currentseries}%
3915       \fi%

```

```

3916   \fi%
3917   \ifcsstring{Xlinenumannotationposition@{\currentseries}}{before}%
3918     {\@annot@end@print}%
3919     {}%
3920   \ifl@d@pnum%
3921     \wrap@edcrossref{\@this@crossref@end}{#4}%
3922     \csuse{Xpagelinesep@{\currentseries}}%
3923   \fi%
3924   \ifl@d@elin%
3925     \wrap@edcrossref{\@this@crossref@end}{%
3926       \linenumrep{#5}%
3927       \iftoggle{Xlineflag@{\currentseries}}{#8}{}%
3928     }%
3929   \fi%
3930   \ifl@d@esl%
3931     \ifl@d@elin%
3932       \csuse{Xsublinesep@{\currentseries}}%
3933     \fi%
3934     \wrap@edcrossref{\@this@crossref@end}{\sublinenumrep{#6}}%
3935   \fi%
3936   \ifcsstring{Xlinenumannotationposition@{\currentseries}}{after}%
3937     {\@annot@end@print}%
3938     {}%
3939   \fi%
3940   \ifdimequal{\csuse{Xboxendlinenum@{\currentseries}}}{0pt}%
3941     {}%
3942     {\hfill}\% Prevent underfull hbox
3943   \egroup%
3944   \endgroup%
3945 }%
3946 %

```

XIII.7.5 Footnote grouped by line

\prepare@Xgroupbyline \prepare@Xgroupbyline is a macro called on the \meta{XXXvfootnote} if \Xgroupbyline is set to true, instead of calling \insert directly.

```

3947 \newcommand{\prepare@Xgroupbyline}[3]{%
3948   \iftoggle{Xgroupbylineseparatwolines@#1}{%
3949     \l@dparsesoftspec#2\%
3950     \ifcsdef{#1forinserting@\l@parsedendpage-\l@parsedendline-\%
3951       \l@dparsedendsub\}%
3952     {}%
3953     \csgappto\%
3954     {#1forinserting@\l@parsedendpage-\l@parsedendline-\%
3955       \l@dparsedendsub\}%
3956     {}%
3957     \ifcseempty{Xsymlinenum@#1}%
3958       {\csuse{Xparafootsep@#1}}%
3959     {}%

```

```

3958      #3{#1}{#2}%
3959      \hskip\csuse{Xafternote@#1}\relax%
3960      }%
3961      }%
3962      }%
3963      \csdef%
3964      {#1@forinserting@\l@dparsedendpage-\l@dparsedendline-\%
3965      \l@dparsedendsub}%
3966      {%
3967      #3{#1}{#2}%
3968      \hskip\csuse{Xafternote@#1}\relax%
3969      }%
3970      \listcsxadd{#1@forinserting}{\l@dparsedendpage-\l@dparsedendline-\%
3971      \l@dparsedendsub}%
3972      }{%
3973      \ifcsdef{#1@forinserting@all}{%
3974      \csgappto%
3975      {#1@forinserting@all}%
3976      {%
3977      \ifcsempty{Xsymlinenum@#1}%
3978      {\csuse{Xparafootsep@#1}}%
3979      {}%
3980      #3{#1}{#2}%
3981      \hskip\csuse{Xafternote@#1}\relax%
3982      }%
3983      }%
3984      \csdef%
3985      {#1@forinserting@all}%
3986      {%
3987      #3{#1}{#2}%
3988      \hskip\csuse{Xafternote@#1}\relax%
3989      }%
3990      }%
3991      \listcsgadd{#1@forinserting}{all}%
3992      }{%
3993      }%
3994      %

```

XIV Familiar footnotes

XIV.1 Adjacent footnotes

The original *edmac* provided users with five series of critical footnotes (*\Afootnote* *\Bfootnote* *\Cfootnote* *\Dfootnote* *\Efootnote*), and *L^AT_EX* provides a single numbered footnote. The *reledmac* package uses the *edmac* mechanism to provide six series of numbered footnotes.

First, though, the `footmisc` package has an option whereby two or more consecutive `\footnotes` have their marks separated by commas. This seemed to Peter Wilson such a useful ability that it was provided automatically by `eledmac`.

Maïel Rouquette has maintained this feature in `reledmac`, despite he thought that is not directly in relationship with the aim of `reledmac`.

- `\multiplefootnotemarker` These macros may have been defined by the `memoir` class, are provided by the `footmisc` package and perhaps by other footnote packages. That is why we use `\providecommand` and not `\newcommand`.

```
3995 \providecommand*\{\multiplefootnotemarker\}{3sp}
3996 \providecommand*\{\multfootsep\}{\textsuperscript{\normalfont,}}
3997 %
3998 %
```

- `\m@mmf@prepare` A pair of self-cancelling kerns. This may have been defined in the `memoir` class.

```
3999 \providecommand*\{\m@mmf@prepare\}{%
4000   \kern-\multiplefootnotemarker
4001   \kern\multiplefootnotemarker\relax}
4002 %
```

- `\m@mmf@check` This may have been defined in the `memoir` class. If it recognises the last kern as `\multiplefootnotemarker` it typesets `\multfootsep`.

```
4003 \providecommand*\{\m@mmf@check\}{%
4004   \ifdim\lastkern=\multiplefootnotemarker\relax
4005     \edef\x@sf{\the\spacefactor}%
4006     \unkern
4007     \multfootsep
4008     \spacefactor\x@sf\relax
4009   \fi
4010 %
4011 %
```

We have to modify `\@footnotetext` and `\@footnotemark`. However, if `memoir` is used the modifications have already been made.

```
4012 \@ifclassloaded{memoir}{}{%
4013 %}
```

- `\@footnotetext` Add `\m@mmf@prepare` at the end of `\@footnotetext`.

```
4014 \apptocmd{\@footnotetext}{\m@mmf@prepare}{}{%
4015 %}
```

- `\@footnotemark` Modify `\@footnotemark` to cater for adjacent `\footnotes`.

```

4016 \patchcmd{\@footnotemark}
4017   {\nobreak}
4018   {\m@mmf@check
4019     \nobreak
4020   }
4021   {}{}
4022 \patchcmd{\@footnotemark}
4023   {\@makefnmark}
4024   {\@makefnmark
4025     \m@mmf@prepare
4026   }
4027   {}{%
4028   }%
4029 %

```

Finished the modifications for the non-memoir case.

```

4030 }
4031 %
4032 %

```

XIV.2 Regular footnotes for numbered texts

`\l@boldold@footnotetext` In order to enable the regular `\footnotes` in numbered text we have to play around
`\@footnotetext` with its `\@footnotetext`, using different forms for when in numbered or regular text.

```

4033 \preto{\@footnotetext}{%
4034   \ifnumberedpar@
4035     \edtext{}{\l@dbfnote{\#1}}%
4036   \else
4037   {}{%
4038 \appto{\@footnotetext}{\fi}{}{}%
4039 %

```

`\l@dbfnote` `\l@dbfnote` adds the footnote to the insert list, and `\v{l@dbfnote}` calls the original
`\v{l@dbfnote}` `\@footnotetext`. We also patch `\footnote` in order to get the correct footnote
`\v{l@dbfnote}` numbers when typesetting parallel texts. This is moved into a `\get@fnmark` command.

```

\footnote
\get@fnmark
\get@thisfootnote
4040 \patchcmd%
4041   {\footnote}%
4042   {\stepcounter{\mpfn}}%
4043   {}%
4044   \ifboolexpr{bool{\l@dpairing} or bool{\l@dprintingpages} or bool{%
4045     \l@dprintingcolumns}}{%
4046     \global\advance\footnote@reading by \cne%
4047     \get@thisfootnote%

```

```

4048   \get@fnmark{\thisc@footnote}%
4049   \ifcsdef{footnotereading}{\the\footnote@reading=typeset}%
4050     {\setcounter{\@mpfn}{\csuse{footnotereading}\the\footnote@reading=}
4051       {\setcounter{\@mpfn}{\footnote@reading}}%
4052     }{%
4053       \stepcounter{\@mpfn}%
4054     }%
4055   }%
4056   {}%
4057   {}%
4058
4059 \newcommand{\get@thisfootnote}{%
4060   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{
4061     l@dprintingcolumns}}{%
4062     \protected@xdef{\thisc@footnote}{\the\footnote@reading}%
4063   }{%
4064     \protected@xdef{\thisc@footnote}{\the\c@footnote}%
4065   }%
4066 }
4067 \newcommand{\l@dbfnote}[1]{%
4068   \get@thisfootnote%
4069   \gdef\@tag{\#1\relax}%
4070   \ifledRcol%
4071     \xright@appenditem{%
4072       \ifdefined\Hy@footnote@currentHref{%
4073         \noexpand\def\noexpand\Hy@footnote@currentHref{\%
4074           \Hy@footnote@currentHref}%
4075         \fi%
4076         \noexpand\v@l@dbfnote{\{\expandonce\@tag\}}{\thisc@footnote}%
4077       }%
4078       \to\inserts@listR%
4079     \global\advance\insert@countR \one%
4080   \else%
4081     \xright@appenditem{%
4082       \ifdefined\Hy@footnote@currentHref{%
4083         \noexpand\def\noexpand\Hy@footnote@currentHref{\%
4084           \Hy@footnote@currentHref}%
4085         \fi%
4086         \noexpand\v@l@dbfnote{\{\expandonce\@tag\}}{\thisc@footnote}%
4087       }%
4088       \to\inserts@list%
4089     \global\advance\insert@count \one%
4090   \fi%
4091   \ignorespaces%
4092 }
4093 \newcommand{\get@fnmark}[1]{%
4094   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{

```

```

1@dp@printingcolumns}}%
4094   }%
4095   \stepcounter{footnote@typeset}%
4096   \setcounter{footnote}{\c@footnote@typeset}%
4097   \immediate\write\@mainaux{%
4098     \csgdef{footnotereading#1=typeset}{\the\c@footnote@typeset}%
4099   }%
4100   \def\@thefnmark{\thefootnote}%
4101 }%
4102 }%
4103   \setcounter{footnote}{#1}%
4104   \def\@thefnmark{\thefootnote}%
4105 }%
4106 }%
4107
4108 \newcommand{\vl@dbfnote}[2]{%
4109   \get@fnmark{#2}%
4110   \g@footnotetext{#1}%
4111 }%
4112 %

```

XIV.3 Footnote formats

Some of the code for the various formats is remarkably similar to that in section ??.

The following macros generally set things up for the ‘standard’ footnote format.

`\prebodyfootmark` Two convenience macros for use by `\...@footnotemark...` macros.

```

\postbodyfootmark
4113 \newcommand*{\prebodyfootmark}{%
4114   \leavevmode
4115   \ifhmode
4116     \edef\x@sf{\the\spacefactor}%
4117     \m@mmf@check
4118     \nobreak
4119   \fi}
4120 \newcommand{\postbodyfootmark}{%
4121   \m@mmf@prepare
4122   \ifhmode\spacefactor\x@sf\fi\relax}
4123 %

```

XIV.4 Footnote arrangement

XIV.4.1 User level macro

`\arrangementX` `\arrangementX[⟨s⟩]{⟨arrangement⟩}` command calls, for each series, a specific command which set many counters and commands in order to define specific arrangement.

```

4125 \newcommandx{\arrangementX}[2][1,usedefault]{%

```

```

4126 \def\do##1{%
4127   \csname arrangementX@#2\endcsname{##1}%
4128 }%
4129 \ifstrempty{#1}%
4130   {%
4131     \dolistloop{\@series}%
4132   }%
4133   {%
4134     \docs vlist{#1}%
4135   }%
4136 }%
4137 %

```

XIV.4.2 Normal footnotes

`\normal@footnotemarkX` `\normal@footnotemarkX{<series>}` sets up the typesetting of the marker at the point where the footnote is called for.

```

4138 \newcommand*{\normal@footnotemarkX}[1]{%
4139   \prebodyfootmark
4140   \wrapped@bodyfootmarkX{#1}%
4141   \postbodyfootmark}
4142 %
4143 %

```

`\normalbodyfootmarkX` The `\normalbodyfootmarkX{<series>}` *really* typesets the in-text marker. The style is the normal superscript.

```

4144 \newcommand*{\normalbodyfootmarkX}[1]{%
4145   \hbox{\textsuperscript{\normalfont\nameuse{@thefnmark#1}}}}
4146 %

```

`\normalvfootnoteX` `\normalvfootnoteX{<series>}{<text>}` does the `\insert` for the `<series>` and calls the series' `\footfmt...` to format the `<text>`.

```

4147 \notbool{paraparatus@}{\newcommand*{\newcommand}{\newcommand}{\normalvfootnoteX}[2]{%
4148   \beforeinsertion@X{#1}%
4149   \insert\nameuse{footins#1}\bgroup
4150   \reset@font%
4151   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4152   \noindent\csuse{bhooknoteX@#1}%
4153   \csuse{notefontsizeX@#1}%
4154   \footsplitskips
4155   \ifl@dpairing\ifl@dpaging\else%
4156     \setnoteswidthliketwocolumnsX@{#1}%
4157   \fi\fi%
4158   \setnotesXpositionliketwocolumns@{#1}%
4159   \spaceskip=\z@skip \xspaceskip=\z@skip
4160   \csuse{\csuse{footnote@dir}}\nameuse{footfmt#1}{#1}{#2}\egroup}
4161 %
4162 %

```

\mpnnormalvfootnoteX The minipage version.

```

4163 \newcommand*{\mpnnormalvfootnoteX}[2]{%
4164   \get@thisfootnoteX{#1}%
4165   \get@fnmarkX{#1}{\thisc@footnote}%
4166   \edef\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
4167   \global\setbox\@nameuse{mpfootins#1}\vbox{%
4168     \unvbox\@nameuse{mpfootins#1}%
4169     \noindent\csuse{bhooknoteX@#1}%
4170     \csuse{notefontsizeX@#1}%
4171     \hsize\columnwidth
4172     \parboxrestore
4173     \color@begingroup
4174     \nameuse{footfmt#1}{#1}{#2}\color@endgroup}}
4175 %
4176 %

```

\normalfootfmtX \normalfootfmtX{\langle series\rangle}{\langle text\rangle} typesets the footnote text, prepended by the marker.

```

4177 \notbool{parapparatus@}{\newcommand*{\newcommand}{\normalfootfmtX}[2]{%
4178   \ifluatex%
4179     \textdir\footnote@luatextextdir%
4180     \pardir\footnote@luatexpardir%
4181     \par%
4182   \fi%
4183   \protected@edef\@currentlabel{%
4184     \nameuse{@thefnmark#1}%
4185   }%
4186   \ledsetnormalparstuffX{#1}%
4187   \hangindent=\csuse{hangindentX@#1}%
4188   \everypar{\hangindent=\csuse{hangindentX@#1}}%
4189   \rule{z@\splittopskip}%
4190   {{\csuse{notenumfontX@#1}\wrapped@footfootmarkX{#1}}%
4191   \csuse{wrapcontentX@#1}{#2}%
4192   \strut\par}}
4193 %
4194 %

```

\normalfootfootmarkX \normalfootfootmarkX{\langle series\rangle} is called by \normalfootfmtX to typeset the footnote marker in the footer before the footnote text.

```

4195 \newcommand*{\normalfootfootmarkX}[1]{%
4196   \textsuperscript{\nameuse{@thefnmark#1}}}
4197 %
4198 %

```

\normalfootstartX \normalfootstartX{\langle series\rangle} is the \langle series\rangle footnote starting macro used in the output routine.

```

4199 \newcommand*{\normalfootstartX}[1]{%
4200   \ifdim\equal{0pt}{\prenotesX@}{\}{}{%
4201     {%
4202       \iftoggle{\prenotesX@}{%
4203         \togglefalse{\prenotesX@}%
4204         \skip\csname footins#1\endcsname=%
4205         \glueexpr\csuse{\prenotesX@}+\csuse{afterruleX@#1}\relax%
4206       }%
4207     {}%
4208   }%
4209   \vskip\skip\csname footins#1\endcsname%
4210   \leftskip=\z@%
4211   \rightskip=\z@%
4212   \ifl@dpairing\else%
4213     \hsize=\old@hsize%
4214   \fi%
4215   \setnoteswidthlike\twocolumnsX@{\#1}%
4216   \setnotesXpositionlike\twocolumns@{\#1}%
4217   \print@footnoteXrule{\#1}%
4218 }%
4219 %
4220 %

```

\normalfootnoteruleX The rule drawn before the footnote series group.

```

4221 \let\normalfootnoteruleX=\footnoterule
4222 %
4223 %

```

\normalfootgroupX **\normalfootgroupX{<series>}** sends the contents of the **<series>** insert box to the output page without alteration.

```

4224 \newcommand*{\normalfootgroupX}[1]{%
4225   \csuse{bhookgroupX@#1}%
4226   \unvbox\cnameuse{footins#1}%
4227   \hsize=\old@hsize%
4228 }%
4229 %
4230 %

```

\mpnormalfootgroupX The minipage version.

```

4231 \newcommand*{\mpnormalfootgroupX}[1]{%
4232   \vskip\skip\@nameuse{mpfootins#1}%
4233   \ifl@dpairing\ifparledgroup%
4234     \leavevmode\marks\parledgroup@{begin}%
4235     \marks\parledgroup@series{\#1}%
4236     \marks\parledgroup@type{footnoteX}%
4237   \fi\fi\normalcolor
4238   \ifparledgroup%

```

```

4239   \ifl@dpairing%
4240   \else%
4241     \setnoteswidthliketwocolumnsX{\#1}%
4242     \setnotesXpositionliketwocolumns{\#1}%
4243     \print@footnoteXrule{\#1}%
4244   \fi%
4245 \else%
4246   \setnoteswidthliketwocolumnsX{\#1}%
4247   \setnotesXpositionliketwocolumns{\#1}%
4248   \print@footnoteXrule{\#1}%
4249 \fi%
4250 \csuse{bhookgroupX{\#1}}%
4251 \unvbox\nameuse{mpfootins{\#1}}
4252 %
4253 %

```

```

\normalbfnoteX54
4255 \newcommand{\normalbfnoteX}[2]{%
4256   \get@thisfootnoteX{\#1}%
4257   \ifledRcol%
4258     \ifluatex
4259       \footnotelang@lua[R]%
4260     \fi
4261     \@ifundefined{xpg@main@language}{%if polyglossia
4262       {}%
4263       {\footnotelang@poly[R]}%
4264     \xright@appenditem{%
4265       \noexpand\led@set@index@fornote{\#1}%
4266       \noexpand\prepare@edindex@fornote{\l@d@nums}%
4267       \unexpanded{\def\this@footnoteX@reading}{\the\csname footnote#1
4268 @reading\endcsname}%
4269       \noexpand\vbfnoteX{\#1}{\#2}{\thisc@footnote}%
4270       \noexpand\led@reinit@index@fornote%
4271       \unexpanded{\advance\edindex@fornote@\m@ne}%
4272     }%
4273     \to\inserts@listR
4274     \global\advance\insert@countR \c@ne%
4275   \else%
4276     \ifluatex
4277       \footnotelang@lua%
4278     \fi
4279     \@ifundefined{xpg@main@language}{%if polyglossia
4280       {}%
4281       {\footnotelang@poly}%
4282     \xright@appenditem{%
4283       \noexpand\led@set@index@fornote{\#1}%
4284       \noexpand\prepare@edindex@fornote{\l@d@nums}%
4285       \unexpanded{\def\this@footnoteX@reading}{\the\csname footnote#1
4286 @reading\endcsname}%

```

```

4285   \noexpand\vbfnoteX{\#1}{\#2}{\thisc@footnote}%
4286   \noexpand\led@reinit@index@fornote%
4287   \unexpanded{\advance\@edindex\fornote@\m@ne}%
4288 }%
4289           \to\inserts@list
4290           \global\advance\insert@count \cne%
4291     \fi
4292   \ignorespaces}
4293 %
4294 %

```

\get@thisfootnoteX The macro `\get@thisfootnote` command just saves the footnote number in the `\thisfootnote` macro, depending on the use of pairing environments.

```

4295 \newcommand{\get@thisfootnoteX}[1]{%
4296   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{%
4297     l@dprintingcolumns}}{%
4298     \protected@xdef\thisc@footnote{\the\csname footnote#1@reading\%
4299     endcsname}%
4300   }{%
4301     \protected@xdef\thisc@footnote{\the\csname c@footnote#1\endcsname}%
4302   }%
4303 %

```

\vbfnoteX This command calls the correct footnote-inserting commands.

```

4303 \newcommand{\vbfnoteX}[3]{%
4304   \get@fnmarkX{\#1}{\#3}%
4305   \nameuse{regvfootnote#1}{\#1}{\#2}%
4306 }%
4307 %
4308 %

```

\get@fnmarkX This command gets the correct footnote number when typesetting parallel texts.

```

4309 \newcommand{\get@fnmarkX}[2]{%
4310   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{%
4311     l@dprintingcolumns}}{%
4312     {%
4313       \stepcounter{footnote#1@typeset}%
4314       \setcounter{footnote#1}{\value{footnote#1@typeset}}%
4315       \nameuse{@hefnmark#1}{\csuse{thefootnote#1}}%
4316       \immediate\write\@mainaux{%
4317         \csgdef{footnote#1reading#2=typeset}{\the\csname c@footnote#1%
4318         @typeset\endcsname}%
4319       }%
4320     }%
4321   }%
4322   \setcounter{footnote#1}{\#2}%

```

```

4321     \@namedef{@thefnmark#1}{\csuse{thefootnote#1}}%
4322   }%
4323 }
4324 %
4325 %

```

```

\vnumpfootnoteX26 \newcommand{\vnumpfootnoteX}[2]{%
4327   \ifnumberedpar@
4328     \edtext{}{\normalbfnoteX{\#1}{\#2}}%
4329   \else
4330     \def\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
4331     \get@thisfootnoteX{\#1}%
4332     \get@fnmarkX{\#1}{\expandonce\thisc@footnote}%
4333     \nameuse{regvfootnote#1}{\#1}{\#2}%
4334   \fi}
4335 %
4336 %

```

`arrangementX@normal` `\arrangementX@normal{<series>}` initialises the settings for the `<series>` footnotes. This should always be called for each series.

```

4337 \newcommand*{\arrangementX@normal}[1]{%
4338   \csgdef{series@displayX#1}{normal}
4339   \expandafter\let\csname footstart#1\endcsname=\normalfootstartX
4340   \@namedef{@footnotemark#1}{\normal@footnotemarkX{\#1}}
4341   \@namedef{bodyfootmark#1}{\normalbodyfootmarkX{\#1}}
4342   \expandafter\let\csname regvfootnote#1\endcsname=\normalvfootnoteX
4343   \expandafter\let\csname vfootnote#1\endcsname=\vnumpfootnoteX
4344   \expandafter\let\csname footfmt#1\endcsname=\normalfootfmtX
4345   \@namedef{footfootmark#1}{\normalfootfootmarkX{\#1}}
4346   \expandafter\let\csname footgroup#1\endcsname=\normalfootgroupX
4347   \expandafter\let\csname footnoterule#1\endcsname=\normalfootnoteruleX
4348   \count\csname footins#1\endcsname=1000
4349   \csxdef{default@footins#1}{1000}%Use to have note only for one side
4350   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}
4351   \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
4352   \advance\skip\csname footins#1\endcsname by\csuse{afterruleX@#1}%
4353 %

```

Additions for minipages.

```

4354   \ifnoledgroup@\else%
4355     \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
4356     \expandafter\let\csname mpfootgroup#1\endcsname=\mpnormalfootgroupX
4357     \count\csname mpfootins#1\endcsname=1000
4358     \dimen\csname mpfootins#1\endcsname=\csuse{maxhnotesX@#1}
4359     \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
4360     \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}%
4361   \fi
4362 }

```

4363
4364 %

XIV.4.3 Two columns footnotes

The following macros set footnotes in two columns. It is assumed that the length of each footnote is less than the column width.

```
\arrangementX@twocol4365 \newcommand*{\arrangementX@twocol}[1]{%
 4366   \csgdef{series@displayX#1}{twocol}
 4367   \expandafter\let\csname regvfootnote#1\endcsname=\twocolvfootnoteX
 4368   \expandafter\let\csname footfmt#1\endcsname=\twocolfootfmtX
 4369   \expandafter\let\csname footgroup#1\endcsname=\twocolfootgroupX
 4370   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@#1}%
 4371   \skip\csname footins#1\endcsname=\csuse{beforenotesX@#1}%
 4372   \advance\skip\csname footins#1\endcsname by \csuse{afterruleX@#1}\relax%
 4373   \twocolfootsetupX{#1}
 4374   \ifnoledgroup@{\else%
 4375     \expandafter\let\csname mpvfootnote#1\endcsname=\mpnormalvfootnoteX
 4376     \expandafter\let\csname mpfootgroup#1\endcsname=\mptwocolfootgroupX
 4377     \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@#1}%
 4378     \advance\skip\csname mpfootins#1\endcsname by \csuse{afterruleX@#1}%
 4379     \mptwocolfootsetupX{#1}
 4380   \fi%
 4381 }
 4382 %
 4383 %

\twocolfootsetupX \twocolfootsetupX{\langle series\rangle}
\mptwocolfootsetupX4384 \newcommand*{\twocolfootsetupX}[1]{%
 4385   \count\csname footins#1\endcsname 500
 4386   \csxdef{default@footins#1}{500}%Use this to confine the notes to one
 4387   side only
 4388   \multiply\dimen\csname footins#1\endcsname by \tw@}
 4389   \newcommand*{\mptwocolfootsetupX}[1]{%
 4390     \count\csname mpfootins#1\endcsname 500
 4391     \multiply\dimen\csname mpfootins#1\endcsname by \tw@}
 4392 %

\twocolvfootnoteX \twocolvfootnoteX{\langle series\rangle}
 4393 \notbool{parapparatus@}{\newcommand*{\newcommand}{\newcommand}{\twocolvfootnoteX}[2]{%
 4394   \beforeinsertion@X{#1}%
 4395   \insert\csname footins#1\endcsname\bgroup%
 4396   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
 4397   \noindent\csuse{bhooknoteX@#1}%
 4398   \csuse{notefontsizeX@#1}%
 4399 }}
```

```

4399      \footnoteskip%
4400      \spaceskip=\z@skip \xspaceskip=\z@skip%
4401      \nameuse{footfmt#1}{\#1}{\#2}\egroup}
4402
4403 %

```

```

\twocolfootfmtX \twocolfootfmtX{\langle series\rangle}

4404 \notbool{parapparatus@}{\newcommand*\newcommand{\twocolfootfmtX}[2]{%
4405   \protected\edef\currentlabel{%
4406     \nameuse{@thefnmark#1}%
4407   }%
4408   \normalpars%
4409   \hangindent=\csuse{hangindentX@#1}%
4410   \everypar{\hangindent=\csuse{hangindentX@#1}}%
4411   \hsize \csuse{hsize\twocolX@#1}%
4412   \nottoggle{parindentX@#1}{\parindent=\z@}{%
4413     \tolerance=5000\relax%
4414     \par%
4415     \tempdima=\parindent%
4416     \csuse{colalignX@#1}%
4417     \parindent=\tempdima%
4418     {\hspace{\parindent}}%
4419     \csuse{notenumfontX@#1}\wrapped@footfootmarkX{\#1}\strut%
4420     \csuse{wrapcontentX@#1}{\#2}%
4421     \strut\par}%
4422   \allowbreak%
4423 }%
4424
4425 %

```

```

\twocolfootgroupX \twocolfootgroupX{\langle series\rangle}
\mptwocolfootgroupX
4426 \newcommand*\twocolfootgroupX[1]{{\csuse{bhookgroupX@#1}\csuse{%
4427   note fontsizeX@#1}%
4428   \splittopskip=\ht\strutbox%
4429   \expandafter
4430   \rigidbalanceX\csname footins#1\endcsname \tw@ \splittopskip}%
4431
4432 \newcommand*\mptwocolfootgroupX[1]{%
4433   \vskip\skip\nameuse{mpfootins#1}%
4434   \ifl@dpairing\ifparledgroup%
4435     \leavevemode\marks\parledgroup@{begin}%
4436     \marks\parledgroup@series{\#1}%
4437     \marks\parledgroup@type{footnoteX}%
4438   \fi\fi\normalcolor%
4439   \ifparledgroup%
4440     \ifl@dpairing%
4441     \else%
4442       \setnoteswidthliketwocolumnsX{\#1}%

```

```

4442   \setnotesXpositionliketwocolumns@{\#1}%
4443   \print@footnoteXrule{\#1}%
4444   \fi%
4445 \else%
4446   \setnoteswidthliketwocolumnsX@{\#1}%
4447   \setnotesXpositionliketwocolumns@{\#1}%
4448   \print@footnoteXrule{\#1}%
4449 \fi%
4450 \csuse{bhookgroupX@\#1}%
4451 \splittopskip=\ht\strutbox
4452 \expandafter
4453 \rigidbalanceX\csname mpfootins#1\endcsname \tw@ \splittopskip}%
4454 %
4455 %

```

XIV.4.4 Three columns footnotes

The following macros set footnotes in three columns. It is assumed that the length of each footnote is less than the column width.

```

\arrangementX@threecol456 \newcommand*{\arrangementX@threecol}[1]{%
4457   \csgdef{series@displayX#1}{threecol}
4458   \expandafter\let\csname regvfootnote#1\endcsname=\threecolvfootnoteX
4459   \expandafter\let\csname footfmt#1\endcsname=\threecolfootfmtX
4460   \expandafter\let\csname footgroup#1\endcsname=\threecolfootgroupX
4461   \dimen\csname footins#1\endcsname=\csuse{maxhnotesX@\#1}%
4462   \skip\csname footins#1\endcsname=\csuse{beforenotesX@\#1}%
4463   \advance\skip\csname footins#1\endcsname by \csuse{afterruleX@\#1}\relax%
4464   \threecolfootsetupX{\#1}
4465   \ifnoledgroup@ \else%
4466     \expandafter\let\csname mpvfootnote#1\endcsname=\mpnrmalvfootnoteX
4467     \expandafter\let\csname mpfootgroup#1\endcsname=\mpthreecolfootgroupX
4468     \skip\csname mpfootins#1\endcsname=\csuse{beforenotesX@\#1}%
4469     \advance\skip\csname mpfootins#1\endcsname by \csuse{afterruleX@\#1}%
4470     \mpthreecolfootsetupX{\#1}
4471   \fi%
4472 }
4473 %
4474 %

\threecolfootsetupX \threecolfootsetupX{\langle series\rangle}
\mpthreecolfootsetupX475 \newcommand*{\threecolfootsetupX}[1]{%
4476   \count\csname footins#1\endcsname 333
4477   \csxdef{default@footins#1}{333}%Use this to confine the notes to one
      side only
4478   \multiply\dimen\csname footins#1\endcsname by \thr@@
4479 \newcommand*{\mpthreecolfootsetupX}[1]{%
4480   \count\csname mpfootins#1\endcsname 333

```

```

4481   \multiply\dimen\csname mpfootins#1\endcsname by \thr@@%
4482 %
4483 %

\threecolvfootnoteX \threecolvfootnoteX{\langle series\rangle}{\langle text\rangle}

4484 \notbool{parapparatus@}{\newcommand*\newcommand{\threecolvfootnoteX}[2]{%
4485   %
4486   \beforeinsertion@X{\#1}%
4487   \insert\csname footins#1\endcsname\bgroup%
4488   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4489   \noindent\csuse{bhooknoteX@#1}%
4490   \csuse{notefontsizeX@#1}%
4491   \footnoteskip%
4492   \nameuse{footfmt#1}{#1}{#2}\egroup}
4493 %

\threecolfootfmtX \threecolfootfmtX{\langle series\rangle}

4494 \notbool{parapparatus@}{\newcommand*\newcommand{\threecolfootfmtX}[2]{%
4495   \protected\edef\@currentlabel{%
4496     \nameuse{@thefnmark#1}%
4497   }%
4498   \hangindent=\csuse{hangindentX@#1}%
4499   \everypar{\hangindent=\csuse{hangindentX@#1}}%
4500   \normalpars%
4501   \hsize\csuse{hsizethreecolX@#1}%
4502   \nottoggle{parindentX@#1}{\parindent=\z@}{%
4503     \tolerance=5000\relax%
4504     \tempdima=\parindent%
4505     \csuse{colalignX@#1}%
4506     \parindent=\tempdima%
4507     {\hskip\parindent}%
4508     \csuse{notenumfontX@#1}\wrapped@footfootmarkX{\#1}\strut%
4509     \csuse{wrapcontentX@#1}{#2}%
4510     \strut\par}\allowbreak}
4511 %
4512 %

\threecolfootgroupX \threecolfootgroupX{\langle series\rangle}

\mpthreecolfootgroupX \newcommand*\threecolfootgroupX[1]{%
4513   \newcommand*{\threecolfootgroupX}[1]{\csuse{bhookgroupX@#1}\csuse{%
4514     notefontsizeX@#1}%
4515     \splittopskip=\ht\strutbox%
4516     \expandafter%
4517     \rigidbalanceX\csname footins#1\endcsname \thr@@ \splittopskip}}
4518 %
4519 \newcommand*\mpthreecolfootgroupX[1]{%
4520   \vskip\skip\nameuse{mpfootins#1}

```

```

4520 \ifl@dpairing\ifparledgroup
4521   \leavevemode\marks\parledgroup@{begin}%
4522   \marks\parledgroup@series{\#1}%
4523   \marks\parledgroup@type{footnoteX}%
4524 \fi\fi\normalcolor
4525 \ifparledgroup%
4526   \ifl@dpairing%
4527   \else%
4528     \setnoteswidthliketwocolumnsX{\#1}%
4529     \setnotesXpositionliketwocolumns@{\#1}%
4530     \print@footnoteXrule{\#1}%
4531   \fi%
4532 \else%
4533   \setnoteswidthliketwocolumnsX{\#1}%
4534   \setnotesXpositionliketwocolumns@{\#1}%
4535   \print@footnoteXrule{\#1}%
4536 \fi%
4537 \csuse{bhookgroupX@{\#1}}%
4538 \splittopskip=\ht\strutbox
4539 \expandafter
4540 \rigidbalanceX\csname mpfootins\#1\endcsname \thr@@ \splittopskip}%
4541 %
4542 %

```

XIV.4.5 Paragraphed footnotes

The following macros set footnotes as one paragraph.

```

\arrangementX@threecol \footparagraphX{\langle series\rangle}

4543 \newcommand*{\arrangementX@paragraph}[1]{%
4544   \csgdef{series@displayX\#1}{\paragraphe}%
4545   \expandafter\let\csname footstart\#1\endcsname=\parafootstartX
4546   \expandafter\let\csname regvfootnote\#1\endcsname=\para@vfootnoteX
4547   \expandafter\let\csname footfmt\#1\endcsname=\parafootfmtX
4548   \expandafter\let\csname footgroup\#1\endcsname=\para@footgroupX
4549   \expandafter\let\csname footnoterule\#1\endcsname=\normalfootnoteruleX
4550   \count\csname footins\#1\endcsname=1000
4551   \csxdef{default@footins\#1}{1000}%Use this to confine the notes to one
4552   side only
4553   \dimen\csname footins\#1\endcsname=\csuse{maxhnotesX@{\#1}}
4554   \skip\csname footins\#1\endcsname=\csuse{beforenotesX@{\#1}}%
4555   \advance\skip\csname footins\#1\endcsname by\csuse{afterruleX@{\#1}}%
4556   \para@footsetupX{\#1}
4557   \ifnoledgroup@{\else
4558     \expandafter\let\csname mpvfootnote\#1\endcsname=\mppara@vfootnoteX
4559     \expandafter\let\csname mpfootgroup\#1\endcsname=\mppara@footgroupX
4560     \count\csname mpfootins\#1\endcsname=1000
4561     \dimen\csname mpfootins\#1\endcsname=\csuse{maxhnotesX@{\#1}}
4562     \skip\csname mpfootins\#1\endcsname=\csuse{beforenotesX@{\#1}}%

```

```

4562     \advance\skip\csname mpfootins#1\endcsname by\csuse{afterruleX@#1}%
4563     \fi
4564 }
4565 %
4566 %

\para@footsetupX \para@footsetupX{\langle series\rangle}

4567 \newcommand*{\para@footsetupX}[1]{\csuse{bhookgroupX@#1}\csuse{
4568   note fontsize X@#1}
4569   \setnoteswidth like two columns X@{#1}%
4570   \ifcsempty{width X@#1}%
4571     {}%
4572     {\columnwidth=\expandafter\dimexpr\csuse{width X@#1}\relax}%
4573   \dimen0=\baselineskip
4574   \multiply\dimen0 by 1024
4575   \divide\dimen0 by \columnwidth \multiply\dimen0 by \footfudgefiddle\relax
4576   \expandafter
4577   \xdef\csname footfudgefactor#1\endcsname{%
4578     \expandafter\strip@pt\dimen0 }}}
4579 %

\parafootstartX \parafootstartX{\langle series\rangle}

4580 \newcommand*{\parafootstartX}[1]{%
4581   \ifdim equal{0pt}{\prenotesX@}{}
4582     {}%
4583     \iftoggle{\prenotesX@}{%
4584       \togglefalse{\prenotesX@}%
4585       \skip\csname footins#1\endcsname=%
4586         \glueexpr\csuse{\prenotesX@}+\csuse{afterruleX@#1}\relax%
4587       }%
4588     {}%
4589   }%
4590   \leftskip=\z@
4591   \rightskip=\z@
4592   \nottoggle{\parindent X@#1}{\parindent=\z@}%
4593   \vskip\skip\@nameuse{footins#1}%
4594   \setnoteswidth like two columns X@{#1}%
4595   \setnotesXposition like two columns@{#1}%
4596   \print@footnoteXrule{#1}%
4597 }

4598 %

\para@vfootnoteX \para@vfootnoteX{\langle series\rangle}{\langle text\rangle}
\mp para@vfootnoteX

```

```

4600 \newcommand*{\para@vfootnoteX}[2]{%
4601   \csuse{beforeinsertingX@#1}%
4602   \insert\csname footins#1\endcsname%
4603   \bgroup
4604     \csuse{notefontsizeX@#1}%
4605     \footsplitskips
4606     \setbox0=\vbox{\hsize=\maxdimen%
4607       \let\bidi@RTL@everypar\empty%
4608       \insert@txtbeforenotesX{#1}%
4609       \noindent\csuse{bhooknoteX@#1}%
4610       \nameuse{footfmt#1}{#1}{#2}}%
4611     \setbox0=\hbox{\unvhx{0}{#1}}%
4612     \dp0=\z@
4613     \ht0=\csname footfudgefactor#1\endcsname\wd0
4614     \box0
4615     \penalty0
4616   \egroup}
4617 \newcommand*{\mppara@vfootnoteX}[2]{%
4618   \get@thisfootnoteX{#1}%
4619   \get@fnmarkX{#1}{\thisc@footnote}%
4620   \edef\this@footnoteX@reading{\the\csname footnote#1@reading\endcsname}%
4621   \global\setbox\nameuse{mpfootins#1}\vbox{%
4622     \unvbox\nameuse{mpfootins#1}%
4623     \csuse{notefontsizeX@#1}%
4624     \footsplitskips
4625     \setbox0=\vbox{\hsize=\maxdimen%
4626       \let\bidi@RTL@everypar\empty%
4627       \noindent\color@begingroup%
4628       \csuse{bhooknoteX@#1}%
4629       \nameuse{footfmt#1}{#1}{#2}\color@endgroup}%
4630     \setbox0=\hbox{\unvhx{0}{#1}}%
4631     \dp0=\z@
4632     \ht0=\csname footfudgefactor#1\endcsname\wd0
4633     \box0
4634     \penalty0}}
4635 %
4636 %

```

```

\unvhx37 \newcommand*{\unvhx}[2]{% 2th is optional for retro-compatibility
4638   \setbox0=\vbox{\unvbox#1%
4639     \global\setbox1=\lastbox}%
4640   \unhbox1
4641   \unskip          % remove \rightskip,
4642   \unskip          % remove \parfillskip,
4643   \unpenalty        % remove \penalty of 10000,
4644   \hskip\csuse{afternoteX@#2}%
4645   \relax}%
4646 %
4647 %

```

```

\parafotfmtX \parafotfmtX{\series}

4648 \newcommand*{\parafotfmtX}[2]{%
4649   \protected@edef\@currentlabel{%
4650     \nameuse{@thefnmark#1}%
4651   }%
4652   \insertparafotsepX{#1}%
4653   \ledsetnormalparstuff@common%
4654   {\csuse{notenumfontX@#1}%
4655   \csuse{notenumfontX@#1}%
4656   \wrapped@footfootmarkX{#1}%
4657   \strut%
4658   \csuse{wrapcontentX@#1}{#2}%
4659   \penalty-10}%
4660 %
4661 %

```

```

\para@footgroupX \para@footgroupX{\series}
\mppara@footgroupX
4662 \newcommand*{\para@footgroupX}[1]{%
4663   \hsize=\expandafter\dimexpr\csuse{widthX@#1}\relax%
4664   \unvbox\csname footins#1\endcsname
4665   \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
4666   \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
4667   \makehboxofhboxes
4668   \setbox0=\hbox{\unhbox0 \removehboxes}%
4669   \csuse{bhookgroupX@#1}%
4670   \csuse{notefontsizeX@#1}%
4671   \unhbox0\par}
4672 %
4673 \newcommand*{\mppara@footgroupX}[1]{%
4674   \setnoteswidthliketwocolumnsX@{#1}%
4675   \vskip\skip\nameuse{mpfootins#1}%
4676   \ifl@dpairing\ifparledgroup
4677     \leavevmode%
4678     \leavevmode\marks\parledgroup@{begin}%
4679     \marks\parledgroup@series{#1}%
4680     \marks\parledgroup@type{footnoteX}%
4681   \fi\fi\normalcolor
4682   \ifparledgroup%
4683     \ifl@dpairing%
4684     \else%
4685       \setnoteswidthliketwocolumnsX@{#1}%
4686       \setnotesXpositionliketwocolumns@{#1}%
4687       \print@footnoteXrule{#1}%
4688     \fi%
4689   \else%
4690     \setnoteswidthliketwocolumnsX@{#1}%
4691     \setnotesXpositionliketwocolumns@{#1}%
4692     \print@footnoteXrule{#1}%

```

```

4693 \fi%
4694 \unvbox\csname mpfootins#1\endcsname
4695 \ifcsstring{raggedX@#1}{L}{\RaggedLeft}{}%
4696 \ifcsstring{raggedX@#1}{R}{\RaggedRight}{}%
4697 \makeboxofhboxes
4698 \setbox0=\hbox{\unhbox0 \removehboxes}%
4699 \csuse{bhookgroupX@#1}%
4700 \csuse{notefontsizeX@#1}%
4701 \notoggle{parindentX@#1}{\parindent=\z@}{}%
4702 \unhbox0\par}%
4703 %
4704 %

```

Insertion of the footnotes separator The command `\insertparafootsepX{<series>}` must be called at the beginning of `\parafootfmtX`.

```

\insertparafootsepX405 \newcommand{\insertparafootsepX}[1]{%
4706   \ifledRcol@%
4707     \ifnumequal{\csuse{prevpage#1@numR}}{\page@numR}%
4708       {\csuse{Xparafootsep@#1}}%
4709       {}%
4710     \global\csname prevpage#1@numR\endcsname=\page@numR%
4711   \else%
4712     \ifnumequal{\csuse{prevpage#1@num}}{\page@num}%
4713       {\csuse{Xparafootsep@#1}}%
4714       {}%
4715     \global\csname prevpage#1@num\endcsname=\page@num%
4716   \fi%
4717 }
4718 %

```

XIV.5 Wrapping footnote marks in hyperlink

`\wrapped@footfootmarkX` `\wrapped@footfootmarkX` prints the footnote mark of the footpage, wrapped in `hyperref` package's commands, if needed.

```

4719 \newcommand{\wrapped@footfootmarkX}[1]{%
4720   \ifdefined\hypertarget%
4721     \hyperlink{%
4722       {@bodyfootmark#1@\this@footnoteX@reading}%
4723       {@nameuse{footfootmark#1}}%
4724     \Hy@raisedlink{%
4725       \hypertarget{%
4726         {@footnotemark#1@\this@footnoteX@reading}%
4727         {}%
4728       }%
4729     \else%
4730       {@nameuse{footfootmark#1}}%

```

```

4731     \fi%
4732 }%
4733 %

```

\wrapped@bodyfootmarkX \wrapped@bodyfootmarkX prints the footnote mark of the text body, wrapped in hyperref package's commands, if needed.

```

4734 \newcommand{\wrapped@bodyfootmarkX}[1]{%
4735   \ifdefined\hypertarget%
4736     \hyperlink{%
4737       {@footnotemark#1@\expandafter\the\csname footnote#1@reading\endcsname}%
4738       {\@nameuse{bodyfootmark#1}}%
4739     }%
4740     \hypertarget{%
4741       {@bodyfootmark#1@\expandafter\the\csname footnote#1@reading\endcsname}%
4742       {}%
4743     }%
4744   \else%
4745     \@nameuse{bodyfootmark#1}%
4746   \fi%
4747 }%
4748 %

```

XV Code common to both critical and familiar footnote in normal arrangement

\par should always be redefined to \endgraf within the format macro (this is what \normal@pars does), to override tricky material in the main text to get the lines numbered automatically (as set up by \autopar, for example).

In the case of footnote arranged in a “normal” way, we also must set some setting for paragraph indent and text direction when using Lua^{TEX}.

That why we have defined \ledsetnormalparstuff@common in order to make this setting for both familiar and critical notes. This command is called by command to make specific setting to critical or familiar footnote.

```

dsetnormalparstuff@common49 \newcommand*{\ledsetnormalparstuff@common}{%
\Xledsetnormalparstuff50 \ifluatex%
\ifdefinedstring{\footnote@luatextextdir}{TLT}{}%
4752   {\textdir\footnote@luatextextdir}%
4753   \pardir\footnote@luatexpardir%
4754 \fi%
4755 \csuse{\csuse{footnote@dir}}%
4756 \normal@pars%
4757 \parfillskip \z@\oplus 1fil}%
4758 %

```

```

4759 \newcommand*{\Xledsetnormalparstuff}[1]{%
4760   \ledsetnormalparstuff@common%
4761   \nottoggle{Xparindent@#1}{\parindent=\z@}{\hspace{\parindent}}%
4762 }%
4763
4764 \newcommand*{\ledsetnormalparstuffX}[1]{%
4765   \ledsetnormalparstuff@common%
4766   \nottoggle{parindentX@#1}{\parindent=\z@}{\hspace{\parindent}}%
4767 }%
4768 %

```

XVI Footnotes' width for two columns

We define here some commands which make sense only with `reledpar`, but must be called when defining notes parameters. These commands change the width of block notes to allow them to have the same size than two parallel columns.

`\old@hsize`
`\setXnoteswidthliketwocolumns@`
`\setnoteswidthliketwocolumnsX@`

These two commands are called at the beginning of critical or familiar notes groups. They set, if the option is enabled, the `\hsize`. They are also called at the on the setup for paragraphed notes.

```

4769 \newdimen\old@hsize%
4770 \AtBeginDocument{\old@hsize=\hsize}%
4771
4772 \newcommand{\setXnoteswidthliketwocolumns@}[1]{%
4773   \global\let\hsize@fornote=\hsize%
4774   \global\old@hsize=\hsize%
4775   \let\old@columnwidth=\columnwidth%
4776   \iftoggle{Xnoteswidthliketwocolumns@#1}{%
4777     {%
4778       \setwidthliketwocolumns%
4779       \global\let\hsize@fornote=\hsize%
4780     }%
4781   }%
4782   {}%
4783   \let\hsize=\hsize@fornote%
4784   \let\columnwidth=\old@columnwidth%
4785 }%
4786
4787 \newcommand{\setnoteswidthliketwocolumnsX@}[1]{%
4788   \global\let\hsize@fornote=\hsize%
4789   \global\old@hsize=\hsize%
4790   \let\old@columnwidth=\columnwidth%
4791   \iftoggle{noteswidthliketwocolumnsX@#1}{%
4792     {%
4793       \setwidthliketwocolumns%
4794       \global\let\hsize@fornote=\hsize%
4795     }%
4796   }%

```

```

4797     \let\hsizetofornote%
4798     \let\columnwidth=\old@columnwidth%
4799 }%
4800 %
4801 %

```

`\espositionliketwocolumns@` These two commands set the position of the critical / familiar footnotes, depending on the hooks `Xnoteswidthliketwocolumns` and `noteswidthliketwocolumnsX`. They call commands which are defined only in `reledpar`, because this feature has no sens without `reledpar`.

```

4802 \newcommand{\setXnotespositionliketwocolumns@}[1]{%
4803   \iftoggle{Xnoteswidthliketwocolumns@#1}{%
4804     \csuse{setnotespositionliketwocolumns@\columns@position}%
4805   }{}%
4806 }%
4807 %
4808 \newcommand{\setnotesXpositionliketwocolumns@}[1]{%
4809   \iftoggle{noteswidthliketwocolumnsX@#1}{%
4810     \csuse{setnotespositionliketwocolumns@\columns@position}%
4811   }{}%
4812 }%
4813 %
4814 %

```

XVII Footnotes' order

`\fnpos` The `\fnpos` and `\mpfnpos` simply place their arguments in `\@fnpos` and `\@mpfnpos`, which will be used later in the output routine.

```

4815 \def\@fnpos{familiar-critical}
4816 \def\@mpfnpos{critical-familiar}
4817 \newcommand{\fnpos}[1]{\xdef\@fnpos{#1}}
4818 \newcommand{\mpfnpos}[1]{\xdef\@mpfnpos{#1}}
4819 %

```

XVIII Footnotes' rule

Because the footnotes' rules can be shifted to the right when footnotes are set like two columns, we do not print them directly, but we put them in a `\vbox`.

```

\print@Xfootnoterule20 \newcommand{\print@Xfootnoterule}[1]{%
\print@footnoteXrule21   \vskip-\csuse{Xafterrule@#1}%Because count in \dimen\csuse{#1footins}
4822   \nointerlineskip%
4823   \moveleft-\leftskip\vbox{\csuse{#1footnoterule}}%
4824   \nointerlineskip%

```

```

4825   \vskip\csuse{Xafterrule@#1}%
4826 }%
4827
4828 \newcommand{\print@footnoteXrule}[1]{%
4829   \vskip-\csuse{afterruleX@#1}%Because count in \dimen\csuse{footins#1}
4830   \nointerlineskip%
4831   \moveleft-\leftskip\vbox{\csuse{footnoterule#1}}%
4832   \nointerlineskip%
4833   \vskip\csuse{afterruleX@#1}%
4834 }%
4835 %
4836 %

```

XIX Specific skip for first series of footnotes

XIX.1 Overview

\Xbeforenotes inserts a specific skip for the first series of notes in a page. As we can't know in advance which series will be the first, we call \prepare@Xprenotes before inserting any critical notes in order to prevent page number overlapping.

1. If it is the first note of the current page, it changes the footnote skip for the series to the value specified to \Xbeforenotes. It also keeps the series of the note as the first one of the current page.
2. If it is not the first note of the current page:
 - If the current series is printed after the series kept as the first of the current page, then nothing happens.
 - If the current series is printed before the series kept as the first of the current page, then it changes the footnote skip of the current series to the value normally used by the series which was marked as the first of the page. It also keeps the current series as the new first one of the current page.

For example, suppose the series order is A,B. We call first a \Bfootnote and a \Afootnote. The only skips used are, finally, the skip specific to the first series of the page, and the skip for the B series. If we have not called \Afootnote, the only skip used is the skip specific to the first series of the page.

That is perfect.

The series skip and the first series of the current page are reset before the footnotes are printed. Then, the footstart macros manage the problem of the first series of the page.

After the rule, the space which is defined by \Xafterrule does not depend on whether the series is the first one of the page or not. So we use its normal value for each series.

And now, implementation !

XIX.2 User level command

\Xprenotes@ If user redefines \Xprenotes@, via \Xprenotes to a value greater than 0 pt, this skip
 \Xprenotes will be added before first series notes instead of the notes skip.

```

4837 \newtoggle{\Xprenotes@}%
4838 \toggletrue{\Xprenotes@}%
4839 \newcommand{\Xprenotes@}{0pt}%
4840 \newcommand*{\Xprenotes}[1]{\renewcommand{\Xprenotes@}{#1}}%
4841 \newcommand{\preXnotes}[1]{\led@warning@preXnotes@deprecated{\Xprenotes{#1}}%
  %For compatibility
4842 %

```

The same, but for familiar footnotes.

```

\Xprenotes@ \newtoggle{prenotesX@}%
\Xprenotes@ \toggletrue{prenotesX@}%
4845 \newcommand{\prenotesX@}{0pt}%
4846 \newcommand*{\prenotesX}[1]{\renewcommand{\prenotesX@}{#1}}%
4847 %

```

XIX.3 Internal commands

```

firstXseries@ \gdef\firstXseries@{}%
prepare@Xprenotes@ \newcommand{\prepare@Xprenotes}[1]{%
 4850   \ifdim\equal{0pt}{\Xprenotes@}%
 4851     {}%
 4852   {}%
 4853     \IfStrEq{\firstXseries@}{}{%
 4854       \global\skip\csuse{\#1footins}=\Xprenotes@%
 4855       \global\advance\skip\csname #1footins\endcsname by\csuse{\Xafterrule@%
 4856       \#1}%
 4857       \gdef\firstXseries@{\#1}%
 4858     }%
 4859   {}%
 4860   \ifseriesbefore{\#1}{\firstXseries@}%
 4861     \global\skip\csuse{\#1footins}=\csuse{\Xbeforenotes@\firstXseries@}%
 4862     \global\advance\skip\csname #1footins\endcsname by\csuse{\Xafterrule@%
 4863     \#1}%
 4864     \gdef\firstXseries@{\#1}%
 4865   }%
 4866   {}%
 4867 }%
 4868 }
 4869 %

```

The same thing is required for familiar notes and \prenotesX.

```

firstseriesX@70 \gdef\firstseriesX@{}
prepare@prenotesX71 \newcommand{\prepare@prenotesX}[1]{%
 4872   \ifdim\zpt=\prenotesX@%
 4873     {}%
 4874   {}%
 4875   \IfStrEq{\firstseriesX@}{}{%
 4876     \global\skip\csuse{footins#1}=\prenotesX@%
 4877     \global\advance\skip\csname footins#1\endcsname by\csuse{afterruleX@%
 4878       #1}%
 4879     \gdef\firstseriesX@{\#1}%
 4880   }%
 4881   \ifseriesbefore{\#1}{\firstseriesX@}%
 4882   {}%
 4883   \global\skip\csuse{footins#1}=\csuse{beforenotesX@\firstseriesX@}%
 4884   \global\advance\skip\csname footins#1\endcsname by\csuse{afterruleX@%
 4885     #1}%
 4886   \gdef\firstXseries@{\#1}%
 4887   }%
 4888   }%
 4889 }%
 4890 }%
 4891 %

```

XX Endnotes

First, check the noend option.

```

4892 \ifbool{noend@}{}{%
4893   % Used instead of \ifnoend@ to prevent expansion problem

```

XX.1 Internal commands

\l@dend@open and \l@dend@close are the macros that are used to open and close the endnote file. Note that all our writing to this file is \immediate: all page and line numbers for the endnotes are generated by the same mechanism we use for the footnotes, so that there is no need to defer any writing to catch information from the output routine. The argument of these two command is the series letter.

```

4894 \newcommand{\l@dend@open}[1]{%
4895   \global\booltrue{l@dend@#1}%
4896   \expandafter\immediate%
4897   \expandafter\openout%
4898   \csname l@d@#1end\endcsname%
4899   =\l@auxdir\jobname.#1end\relax%

```

```

4900 }%
4901 \newcommand{\l@dend@close}[1]{%
4902   \global\boolfalse{l@dend@#1}%
4903   \expandafter\immediate%
4904   \expandafter\closeout\csname l@d@#1end\endcsname%
4905 }%
4906 %
4907 %

```

\l@dend@stuff \l@dend@stuff is used by \beginnumbering to do everything that is necessary for the endnotes at the start of each section: it opens the \l@d@end file, if necessary, and writes the section number to the endnote file.

```

4908 \newcommand{\l@dend@stuff}{%
4909   \def\do##1{%
4910     \ifbool{l@dend@##1}{%
4911       {\l@dend@open{##1}}%
4912       \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname{%
4913         string\l@d@section{\the\section@num}\@percentchar}%
4914     }%
4915     \dolistloop{\@series}%
4916   }%
4917 }%

```

\endprint The \endprint here is nearly identical in its functioning to \normalfootfmt.

\l@d@section The endnote file also contains \l@d@section commands, which supply the section numbers from the main text; standard reledmac does nothing with this information, but it is there if you want to write custom macros to do something with it. Arguments are:

- #1 Line numbers and font selection.
- #2 Lemma.
- #3 Note content.
- #4 Series.
- #5 Optional argument of \Xendnote.
- #6 Side (L or R).
- #7 Label for cross-referencing.

```

4918 \global\notbool{parapparatus@}{\long}\def\endprint#1#2#3#4#5#6#7{%
4919   \iftoggle{Xendfirstnote@#4}{%
4920     \global\togglefalse{Xendfirstnote@#4}%
4921     \csuse{Xendtxtbeforenotes@#4}%
4922   }%

```

```

4923   \csuse{Xendbhooknote@#4}%
4924   \csuse{Xendnotefontsize@#4}%
4925   \hangindent=\csuse{Xendhangindent@#4}%
4926   \ifXendinsertsep@%
4927     \hskip\csuse{Xendafternote@#4}\relax%
4928     \csuse{Xendsep@#4}%
4929   \else%
4930     \iftoggle{Xendparagraph@#4}%
4931       {\global\Xendinsertsep@true}%
4932     {}%
4933   \fi%
4934   \xdef\@currentseries{#4}%
4935   \def\do##1{%
4936     \setkeys[mac]{truefootnoteoption}{##1}%
4937   }%
4938   \notblank{#5}{\docslist{#5}}{%
4939     \IfStrEq{#6}{R}{\ledRcol@true}{}%
4940     \def\@this@crossref@start{#7:start}%
4941     \def\@this@crossref@end{#7:end}%
4942     \printlineendnote{#1}{#4}%
4943     \IfStrEq{#6}{R}{\ledRcol@false}{}%
4944     \undef\@this@crossref@start%
4945     \undef\@this@crossref@end%
4946     \notoggle{Xendlemmadisablefontselection@#4}%
4947       {\select@lemm.getFont#1}%
4948     {}%
4949   \bgroup%
4950     \csuse{Xendlemmafont@#4}%
4951     \csuse{Xendwraplemma@#4}{#2}%
4952   \egroup%
4953   \ifboolexpr{%
4954     \t gl {nosep@}%
4955     \or \test{\ifcsempty{Xendlemmaseparator@#4}}%
4956   }{%
4957     {\hskip\csuse{Xendinplaceoflemmaseparator@#4}\relax}%
4958     {\nobreak}%
4959     \hskip\csuse{Xendbeforelemmaseparator@#4}%
4960     \csuse{Xendlemmaseparator@#4}%
4961     \hskip\csuse{Xendafterlemmaseparator@#4}%
4962     \relax%
4963   }%
4964   \csuse{Xendwrapcontent@#4}{#3}%
4965   \notoggle{Xendparagraph@#4}{\par}{%
4966     \def\do##1{%
4967       \setkeys[mac]{falsefootnoteoption}{##1}%
4968     }%
4969     \notblank{#5}{\docslist{#5}}{%
4970   }%
4971   \let\l@d@section=\@gobble

```

```
4973 %
4974 %
```

\printlineendnote This macro controls, in endnote, whether the line number is printed or not, according to the series options. Its first argument is the information about lines; its second is the series of the footnote.

```
4975 \newcommand{\printlineendnote}[2]{%
4976   \l@dp@rsefootspec#1%
4977   \iftoggle{Xendnumberonlyfirstintwolines@#2}{%
4978     \xdef\lineinfo@{\l@dparsedstartpage - \l@dparsedstartline - \
4979     \l@dparsedstartsub - \l@dparsedendpage - \l@dparsedendline - \
4980     \l@dparsedendsub}%
4981     }%
4982   }%
4983   \ifboolexpr{%
4984     \togl {nonum@}%
4985     \or \togl {Xendnonumber@#2}%
4986   }%
4987   {\hspace{\csuse{Xendinplaceofnumber@#2}}}%
4988   \t%
4989   \iftoggle{Xendnumberonlyfirstinline@#2}{%
4990     \ifcsdef{prevendline#2}{%
4991       \ifcsequal{prevendline#2}{lineinfo@}{%
4992         }%
4993         \csuse{Xendbhookinplaceofnumber@#2}%
4994         \ifcsempty{Xendsymlinenum@#2}{%
4995           {\hspace{\csuse{Xendinplaceofnumber@#2}}}%
4996           {\printsymlineendnotearea{#2}}%
4997           \csuse{Xendahookinplaceofnumber@2}%
4998         }%
4999         {\printlineendnotearea{#1}{#2}}%
5000         {\printlineendnotearea{#1}{#2}}%
5001       }%
5002       {\printlineendnotearea{#1}{#2}}%We keep every time line
5003       \csxdef{prevendline#2}{\lineinfo@}%
5004     }%
5005   }%
5006 }
```

```
\printsymlineendnotearea07 \newcommand{\printsymlineendnotearea}[1]{%
5008   \hspace{\csuse{Xendbeforesymlinenum@#1}}%
5009   \csuse{Xendnotenumfont@#1}%
5010   \ifdimequal{\csuse{Xendboxsymlinenum@#1}}{\z@}{%
5011     \csuse{Xendsymlinenum@#1}}%
5012     {\hbox to \csuse{Xendboxsymlinenum@#1}}%
```

```

5013   {\csuse{Xendsymlinenum@#1}\hfill}%
5014   }%
5015   \hspace{\csuse{Xendaftersymlinenum@#1}}%
5016 }%
5017 %

```

`\printlineendnotearea` This macro prints the space before the line number, changes the font, then prints the line number and the space after it. It is called by `\endprint` depending of the options about repeating line numbers. The first argument is line information, the second is the notes series (A, B, C, etc.)

```

5018 \newcommand{\printlineendnotearea}[2]{%
5019   \csuse{Xendbhooklinenumber@#2}%
5020   \hspace{\csuse{Xendbeforenumber@#2}}%
5021   \bgroup%
5022     \csuse{Xendnotenumfont@#2}%
5023     \ifdimequal{\csuse{Xendboxlinenum@#2}}{0pt}%
5024       {\printendlines#1|\!| \ifledRcol@\@Rlineflag\fi}%
5025       {\leavevmode%
5026         \hbox to \csuse{Xendboxlinenum@#2}%
5027         {%
5028           \IfSubStr{RC}{\csuse{Xendboxlinenumalign@#2}}{\hfill}{}%
5029           \printendlines#1|\!| \ifledRcol@\@Rlineflag\fi%
5030           \IfSubStr{LC}{\csuse{Xendboxlinenumalign@#2}}{\hfill}{}%
5031         }%
5032       \egroup%
5033       \hspace{\csuse{Xendafternumber@#2}}%
5034       \csuse{Xendahooklinenumber@#2}%
5035     }%
5036   %

```

XX.2 User level commands

XX.2.1 Inserting contents to endnotes

The `\Xendnotes` commands are defined above, when defining apparatus commands by series. Here, we define only `\toendnotes` command not specific to a series, in order to insert arbitrary code. The regular version writes an unexpanded argument, while the regular version writes a once-expanded argument.

```

\toendnotes37 \newcommandx{\toendnotes}[2][1,usedefault]{%
\toendnotes*38 \ifboolexpr{bool{numbering} or bool{numberingR}}{%
5039   \def\do##1{%
5040     \expandafter\immediate\expandafter\write\csname 1d@##1end\endcsname{%
5041       \unexpanded{##2}\@percentchar}%
5042   }%
5043   \ifstrempty{##1}{%
5044     \dolistloop{\@series}%
5045     \docslist{##1}%

```

```

5046   }{\led@err@toendnotes@outsidenumbering}%
5047 }%
5048 \WithSuffix\newcommandx\toendnotes*[2][1,usedefault]{%
5049   \ifboolexpr{bool{numbering} or bool{numberingR}}{%
5050     \def\do##1{%
5051       \expandafter\immediate\expandafter\write\csname l@d@##1end\endcsname{%
5052         {##2}\@percentchar}%
5053     }%
5054     \ifstrempty{#1}{%
5055       {\dolistloop{\@series}}%
5056       {\docslist{#1}}%
5057     }{\led@err@toendnotes@outsidenumbering}%
5058   }%
5059 }%

```

XX.2.2 Printing endnotes

`\doendnotes` `\doendnotes` is the command you use to print one series of endnotes; it takes one argument: the series letter of the note series you want to print. `\Xendinsertsep@` is set to true at the first note of the series, and to false at the last one.

```

5060 \newif\ifXendinsertsep@
5061 \newcommand*{\doendnotes}[1]{%
5062   \l@dend@close{#1}%
5063   \begingroup
5064     \csxdef{prevpagenum@#1}{}%
5065     \csxdef{prevpagerange@#1}{}%
5066     \global\toggletrue{Xendfirstnote@#1}%
5067     \makeatletter
5068     \expandafter\let\csname #1end\endcsname=\endprint
5069     \input{l@auxdir\jobname.#1end}%
5070     \global\Xendinsertsep@false%
5071   \endgroup
5072 }%

```

`\doendnotesbysection` `\doendnotesbysection` is a variant of the previous macro. While `\doendnotes` print endnotes for all of numbered sections `\doendnotesbysection` print the endnotes for the first numbered section at its first call for a series, then for the second section at its second call for the same series, then for the third section at its third call for the same series, and so on.

```

5073 \newcommand*{\doendnotesbysection}[1]{%
5074   \l@dend@close{#1}%
5075   \csxdef{prevpagenum@#1}{}%
5076   \csxdef{prevpagerange@#1}{}%
5077   \global\expandafter\advance\csname #1end@bysection\endcsname by 1%
5078   \begingroup%
5079     \makeatletter%
5080     \def\l@d@section##1{%

```

```

5081 \global\toggletrue{Xendfirstnote@#1}%
5082 \ifnumequal{##1}{\csname #1end@bysection\endcsname}%
5083   {\cslet{#1end}{\endprint}%
5084   {\cslet{#1end}{\gobbleseven}%
5085 }%
5086   \input{l@auxdir\jobname.#1end}%
5087   \global\Xendinsertsep@false%
5088 \endgroup%
5089 }%
5090 %

```

We close now the conditional period, which depends on `\ifnoend@`, because the following commands can be used by other commands than those specific to endnotes.

```

5091 }%
5092 %

```

\setprintendlines The `\printendlines` macro is similar to `\printlines` but is for printing endnotes rather than footnotes.

The principal difference between foot- and endnotes is that footnotes are printed on the page where they are specified but endnotes are printed at a different point in the document. We need an indication of the source of an endnote; `\setprintendlines` provides this by always printing the page number. The coding is slightly simpler than `\setprintlines`.

from the starting page number.

```

5093 \newcommand*{\setprintendlines}[6]{%
5094   \let\@cannot@start@print\relax%
5095   \let\@cannot@end@print\relax%
5096   \l@d@pnumfalse%
5097   \l@d@dashfalse%
5098   \l@d@elinfalse%
5099 %

```

First of all, we print the second page number only if the ending page number is different

```

5100 \ifnum#4=>#1 \else
5101   \l@d@pnumtrue
5102   \l@d@dashtrue
5103 \fi
5104 %

```

We print the ending line number if: (1) we are printing the ending page number, or (2) the ending line is different from the starting line number.

```

5105 \ifboolexpr{%
5106   bool{\l@d@pnum}%
5107   or not test{\ifnumequal{#2}{#5}}%
5108 }{%
5109   \l@d@elintrue%
5110   \l@d@dashtrue%

```

```

5111     \l@d@elintrue
5112     \l@d@dashtrue
5113     \unless\ifx\relax\annot@end%
5114     \def\cannot@end@print{%
5115         \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries
5116             }{\annot@end}%
5117             }%
5118         }%
5119     }%
5120 %

```

We define the starting line number annotation as a merge of the starting annotation and ending annotation if we don't print the ending line number. Otherwise, it is only the starting annotation.

```

5121     \ifl@d@elin%
5122     \def\cannot@start@print{%
5123         \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries}{\
5124             annot@start}%
5125             }%
5126         \else%
5127             \ifx\annot@start\annot@end%
5128                 \unless\ifx\cannot@start\relax%
5129                     \def\cannot@start@print{%
5130                         \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries
5131                             }{\annot@start}%
5132                             }%
5133                         \fi%
5134                     \else%
5135                         \ifx\cannot@end@print\relax%
5136                             \def\cannot@start@print{%
5137                                 \l@wrapcs@ifnotemptybox{Xendwraplinenumannotation@\@currentseries
5138                                     }{%
5139                                         \ifdefined\linerangesep@
5140                                             \linerangesep@
5141                                         \else%
5142                                             \csuse{Xendlinerangeseparator@\@currentseries}%
5143                                         \fi%
5144                                         \fi%
5145                                         \annot@end%
5146                                         }%
5147                                         }%
5148                                         \let\cannot@start@print\cannot@end@print%
5149                                         \let\cannot@end@print\relax%
5150                                         \fi%
5151                                         \fi%
5152                                         \fi%

```

5153 %

We print the starting sub-line if it is nonzero.

```

5154 \l@d@ssubfalse
5155 \ifnum#3=0 \else
5156   \l@d@ssubtrue
5157 \fi
5158 %

```

We print the ending sub-line if it is nonzero and: (1) it is different from the starting sub-line number, or (2) the ending line number is being printed.

```

5159 \l@d@eslfalse
5160 \ifnum#6=0 \else
5161   \ifnum#6=#3
5162     \ifl@d@elin \l@d@esltrue \else \l@d@eslfalse \fi
5163   \else
5164     \l@d@esltrue
5165     \l@d@dashtrue
5166   \fi
5167 \fi%
5168 %

5169 \ifl@d@dash%
5170   \ifboolexpr{togl{fulllines@} or test{\ifcsempy{Xendtwolines@\
5171 @currentseries}}}{%
5172     {}%
5173     {}%
5174     \setistwofollowinglines{#1}{#2}{#4}{#5}%
5175     \ifboolexpr{%
5176       (%
5177         togl {Xendtwolinesbutnotmore@{@currentseries}}%
5178         and not%
5179         (%
5180           bool {istwofollowinglines@}%
5181         )%
5182       or%
5183       (%
5184         (not test{\ifnumequal{#1}{#4}})%
5185         and togl{Xendtwolinesonlyinsamepage@{@currentseries}}%
5186       )%
5187     }%
5188     {}%
5189     {}%
5190     \l@d@dashfalse%
5191     \l@d@Xtwolinestrue%
5192     \l@d@elinfalse%
5193     \l@d@eslfalse%
5194     \ifcsempy{Xendmorethanwolines@{@currentseries}}{%
5195       {}%

```

```

5196      {\ifistwoofollowinglines@{\else%
5197          \l@d@Xmorethanwolinestrue%
5198          \fi%
5199          }%
5200      }%
5201      \fi%
5202      %
5203  %

```

End of `\setprintendlines`.

```

5204  }%
5205  %

```

`\printendlines` Now we are ready to print it all.

```

5206 \def\printendlines#1|#2|#3|#4|#5|#6|#7|#8|{%
5207   \begingroup
5208   \setprintendlines{#1}{#2}{#3}{#4}{#5}{#6}%
5209   %

```

The only subtlety left here is when to print a period between numbers. But the only instance in which this is tricky is for the ending sub-line number: it could be coming after the starting sub-line number (in which case we want only the dash) or after an ending line number (in which case we need to insert a period).

So, first, start the starting line box, if needed.

```

5210 \ifdimequal{\csuse{Xendboxstartlinenum@\@currentseries}}{0pt}%
5211   {\bgroup%
5212   {\leavevmode\hbox to \csuse{Xendboxstartlinenum@\@currentseries}\bgroup%
5213   \hfill}%
5214   %

```

Then, print the starting page number-

```

5214 \ifboolexpr{%
5215   ()%
5216   test{\ifcsstring{prevpagenum@\@currentseries}{#1}}%
5217   and not%
5218   (togl{Xendpagenumberonlyfirstifsingle@\@currentseries} and bool{%
5219     1@d@pnum})%
5220   )%
5221   or%
5222   ()%
5223   test {\ifcsstring{prevpagerange@\@currentseries}{#1-#4}}%
5224   )%
5225   }%
5226   \ifcsempty{Xendsympagenum@\@currentseries}%
5227   {\hspace{\csuse{Xendinplaceofpagenumber@\@currentseries}}}%
5228   {\csuse{Xendsympagenum@\@currentseries}}%
5229   }%

```

```

5230   {%
5231     \wrap@edcrossref{@this@crossref@start}{\printnpnum{#1}}%
5232   }%
5233 %

```

Then, determine what must be printed before the start line.

```

5234   \ifl@d@dash%
5235     \ifl@d@pnum%
5236       \csuse{Xendlineprefixsingle@\@currentseries}%
5237     \else%
5238       \ifcsempty{Xendlineprefixmore@\@currentseries}%
5239         {\csuse{Xendlineprefixsingle@\@currentseries}}%
5240         {\csuse{Xendlineprefixmore@\@currentseries}}%
5241       \fi%
5242     \else%
5243       \csuse{Xendlineprefixsingle@\@currentseries}%
5244     \fi%
5245 %

```

Then print the starting line, followed, if needed, by the side flag and the starting sub line number, then the line number annotation.

```

5246   \ifcsstring{Xendlinenumannotationposition@\@currentseries}{before}%
5247     {\@cannot@start@print}%
5248   {}%
5249   \wrap@edcrossref{@this@crossref@start}{%
5250     \ifledRcol@%
5251       \linenumrepR{#2}%
5252     \else%
5253       \linenumrep{#2}%
5254     \fi%
5255   }%
5256   \iftoggle{Xendlineflag@\@currentseries}{\ifledRcol@\@Rlineflag\fi}{}
5257   \ifl@d@ssub%
5258     \csuse{Xendsublinesep@\@currentseries}%
5259     \wrap@edcrossref{@this@crossref@start}{%
5260       \ifledRcol@%
5261         \sublinenumrepR{#3}%
5262       \else%
5263         \sublinenumrep{#3}%
5264       \fi%
5265     }%
5266   \fi%
5267   \ifcsstring{Xendlinenumannotationposition@\@currentseries}{after}%
5268     {\@cannot@start@print}%
5269   {}%
5270 %

```

Close the box.

```

5271   \egroup%
5272 %

```

Open the box for the ending line number.

```

5273   \ifdim\equal{\csuse{Xendboxendlinenum@\@currentseries}}{0pt}%
5274     {\bgroup}%
5275     {\hbox to \csuse{Xendboxendlinenum@\@currentseries}\bgroup}%
5276   %

```

Print the dash + the ending line number, or the line number range symbol.

```

5277   \ifl@d@Xtwolines%
5278     \ifl@d@Xmorethan twolines%
5279       \csuse{Xendmorethan twolines@\@currentseries}%
5280     \else%
5281       \csuse{Xendtwolines@\@currentseries}%
5282     \fi%
5283   \else%
5284     \ifl@d@dash%
5285       \ifdefined\linerangesep@%
5286         \linerangesep@%
5287       \else%
5288         \csuse{Xendlinerangeseparator@\@currentseries}%
5289       \fi%
5290     \fi%
5291   %

```

Print the ending page number.

```

5292   \ifl@d@pnum%
5293     \ifcsstring{prevpagerange@\@currentseries}{#1-#4}%
5294     {%
5295       \ifcseempty{Xendsympagenum@\@currentseries}%
5296         {\hspace{\csuse{Xendinplaceofpagenumber@\@currentseries}}}%
5297         {\csuse{Xendsympagenum@\@currentseries}}%
5298       }%
5299     {%
5300       \wrap@edcrossref{@this@crossref@end}\printnpnum{#4}%
5301     }%
5302   \fi%
5303 %

```

Print the ending line number, with, if needed, the line prefix, and followed by the side flag, the subline number, and line number annotation.

```

5304   \ifcsstring{Xendlinenumannotationposition@\@currentseries}{before}%
5305     {\cannot@end@print}%
5306     {}%
5307   \ifl@d@elin%
5308     \ifl@d@pnum\csuse{Xendlineprefixsingle@\@currentseries}\fi%
5309     \wrap@edcrossref{@this@crossref@end}{%
5310       \ifledRcol@%
5311         \linenumrepR{#5}%
5312       \else%
5313         \linenumrep{#5}%

```

```

5314     \fi%
5315   }%
5316   \iftoggle{Xendlineflag@{@currentseries}{\ifledRcol@{@Rlineflag\fi}{}}{%
5317     \fi%
5318     \ifl@d@esl%
5319       \ifl@d@elin%
5320         \csuse{Xendsublinesep@{@currentseries}}%
5321       \fi%
5322       \wrap@edcrossref{\@this@crossref@end}{}{%
5323         \ifledRcol@{%
5324           \sublinenumrepR{#6}%
5325         \else%
5326           \sublinenumrep{#6}%
5327         \fi%
5328       }%
5329     \fi%
5330     \ifcsstring{Xendlinenumannotationposition@{@currentseries}{after}}{%
5331       {\@annot@end@print}%
5332     {}%
5333   \fi%
5334 %

```

Close the ending line box.

```

5335   \ifdimequal{\csuse{Xendboxendlinenum@{@currentseries}}{0pt}}{%
5336     {}%
5337     {\hfill}\% Prevent underfull hbox
5338   \egroup%
5339 %

```

And, finally, save, if needed, the current page number for the Xendpagenumberonlyfirst hooks.

```

5340   \iftoggle{Xendpagenumberonlyfirst@{@currentseries}}{%
5341     \iftoggle{Xendpagenumberonlyfirstintwo@{@currentseries}}{%
5342       {\csxdef{prevpagerange@{@currentseries}}{\#1-\#4}}{%
5343         {\csxdef{prevpagenum@{@currentseries}}{\#4}}{%
5344       }%
5345     {}%
5346   %

```

Now, the end of \printendlines macro.

```

5347   \endgroup%
5348 }%
5349 %
5350 %

```

\printnpnum A macro to print a page number in an endnote. Should not be override anymore

```

5351 \newcommand*{\printnpnum}[1]{\csuse{Xendbeforepagenumber@{@currentseries}}{%
5348 }#1\csuse{Xendafterpagenumber@{@currentseries}}{%

```

```
5352 %
5353 %
```

XXI Generate series of notes

In this section, X means the name of the series (A, B etc.)

`\series` `\series\series` creates one more new series. It is a public command, which just loops on the private command `\newseries@`.

```
5354 \newcommand{\newseries}[1]{%
5355   \def\do##1{\newseries@{##1}}%
5356   \doCSVlist{#1}
5357 }
5358 %
```

`\@series` The `\series@` macro is an etoolbox list, which contains the name of all series.

```
5359 \newcommand{\@series}{}%
5360 %
```

The command `\newseries@\series` creates a new series of the footnote.

```
\newseries@_61 \newcommand{\newseries@}[1]{%
5362 %
```

XXI.1 Test if series is still existing

```
5363 \xifinlist{#1}{\@series}{\led@warn@SeriesStillExist{#1}}%
5364 \fi%
5365 %
```

XXI.2 Init specific to reledpar

When calling `\newseries@` after having loaded `reledpar`, we need to load specific setting.

```
5366 \ifdef{\newseries@}{%
5367   \newseries@{#1}%
5368 \fi%
5369 %
```

XXI.3 For critical footnotes

Critical footnotes are those which start with letters. We look for the `\nocritical` option of `reledmac`.

```
5370 \unless\ifnocritical@
5371 %
```

XXI.3.1 Options

```

5372      \newtoggle{Xlineflag@#1}
5373      \newtoggle{Xparindent@#1}
5374      \newtoggle{Xlemmadisablefontselection@#1}
5375      \csgdef{Xwrapcontent@#1}{}%
5376      \csgdef{Xbeforeinserting@#1}{}%
5377      \csgdef{Xhangindent@#1}{0pt}%
5378      \csgdef{Xragged@#1}{}%
5379      \csgdef{Xhsizetwocol@#1}{0.45 \hsize}%
5380      \csgdef{Xhsizethreecol@#1}{.3 \hsize}%
5381      \csgdef{Xcolalign@#1}{\raggedright}%
5382      \csgdef{Xnotenumfont@#1}{\normalfont}%
5383      \csgdef{Xnotefontsize@#1}{\footnotesize}%
5384      \csgdef{Xbhooknote@#1}{}%
5385      \csgdef{Xbhookgroup@#1}{}%
5386
5387      \csgdef{Xboxlinenum@#1}{0pt}%
5388      \csgdef{Xboxlinenumalign@#1}{L}%
5389
5390      \csgdef{Xboxstartlinenum@#1}{0pt}%
5391      \csgdef{Xboxendlinenum@#1}{0pt}%
5392
5393      \csgdef{Xboxsymlinenum@#1}{0pt}%
5394      \newtoggle{Xnumberonlyfirstinline@#1}%
5395      \newtoggle{Xgroupbyline@#1}%
5396      \newtoggle{Xgroupbylineseparetwolines@#1}%
5397      \newtoggle{Xnumberonlyfirstintwolines@#1}%
5398      \csgdef{Xtwolines@#1}{}%
5399      \csgdef{Xmorethantwolines@#1}{}%
5400      \csgdef{Xsublinesep@#1}{\fullstop}%
5401      \csgdef{Xpagelinesep@#1}{\csname Xsublinesep@#1\endcsname}%
for
backward compatibility, call Xsublinesep@#1
5402      \newtoggle{Xtwolinesbutnotmore@#1}%
5403      \newtoggle{Xtwolinesonlyinsamepage@#1}%
5404      \newtoggle{Xonlypstart@#1}%
5405      \newtoggle{Xpstarteverytime@#1}%
5406      \newtoggle{Xpstart@#1}%
5407      \newtoggle{Xstanzao@#1}%
5408      \csgdef{Xstanzaseparator@#1}{}%
5409      \csgdef{Xsymlinenum@#1}{}%
5410      \newtoggle{Xnonumber@#1}%
5411      \csgdef{Xbeforenumber@#1}{0pt}%
5412      \csgdef{Xtxtbeforenumber@#1}{}%
5413      \csgdef{Xafternumber@#1}{0.5em}%
5414      \newtoggle{Xnonbreakableafternumber@#1}%
5415      \csgdef{Xbeforesymlinenum@#1}{\csuse{Xbeforenumber@#1}}%
5416      \csgdef{Xaftersymlinenum@#1}{\csuse{Xafternumber@#1}}%
5417      \csgdef{Xinplaceofnumber@#1}{1em}%
5418      \global\cslet{Xlemmaseparator@#1}{\rbracket}%

```

```

5419 \csgdef{Xbeforelemmaseparator@#1}{0em}%
5420 \csgdef{Xafterlemmaseparator@#1}{0.5em}%
5421 \csgdef{Xinplaceoflemmaseparator@#1}{1em}%
5422 \csgdef{Xbeforenotes@#1}{1.2em \oplus .6em \ominus .6em}
5423 \csgdef{Xafterrule@#1}{0pt}

5424
5425 \csgdef{Xtxtbeforenotes@#1}{}
5426 \newtoggle{Xtxtbeforenotes@#1@typeset}%Not directly used by user,
but internal
5427 \newtoggle{Xtxtbeforenotesonlyonce@#1}%

5428
5429 \csgdef{Xmaxhnotes@#1}{0.8\vsizex}
5430 \newtoggle{Xnoteswidthliketwocolumns@#1}%
5431 \csgdef{Xparafootsep@#1}{}
5432 \csgdef{Xafternote@#1}{1em plus .4em minus .4em}
5433 \csgdef{Xlinerangeseparator@#1}{\endashchar}%

5434
5435 \csgdef{Xlemmafont@#1}{}
5436 \csgdef{Xwraplemma@#1}{}
5437 \csgdef{Xwidth@#1}{\hsize}%
5438 \csgdef{Xwraplinenumannotation@#1}{\textsuperscript}%

5439 %

```

XXI.3.2 Create inserts, needed to add notes in foot

As regards inserts, see chapter 15 of *The TeXbook* by D. Knuth.

```

5440 \expandafter\newinsert\csname #1footins\endcsname%
5441 \unless\ifnoledgroup@%
5442 \expandafter\newinsert\csname mp#1footins\endcsname%
5443 \fi%
5444 %

```

XXI.3.3 Create commands for critical apparatus, \Afootnote, \Bfootnote etc.

Note the double # in command: it is because command it is made inside another command.

```

5445 \global\notbool{parapparatus@}{\expandafter\newcommand\expandafter
*}{\expandafter\newcommand}\csname #1footnote\endcsname[2] []{%
5446 \if@edtext@secondarg@%
5447 \ifledRco1%
5448 \ifcsstring{Xonlyside@#1}{L}{%
5449 led@error@note@called@onrightside{#1footnote}}{}%
5450 \else%
5451 \ifcsstring{Xonlyside@#1}{R}{%
5452 led@error@note@called@onleftside{#1footnote}}{}%
5453 \fi%
5454 \begingroup%
\newcommand{\content}{##2}%
\ifnumberedpar@%

```

```

5455   \ifledRcol%
5456     \ifluatex%
5457       \footnotelang@lua[R]%
5458     \fi%
5459     \@ifundefined{ xpg@main@language}%
5460       {}%
5461       {\footnotelang@poly[R]}%
5462     \footnoteoptions@{R}{##1}{true}%
5463     \xright@appenditem{%
5464       \ifbool{indtl@innote}%
5465         {\unexpanded{\let\index\nindex}}%
5466         {}%
5467       \ifbool{indtl@notenumber}%
5468         {\unexpanded{\let\index\nindex}}%There is no note
      ...number so
5469         {}%
5470       \noexpand\Xnote@true%
5471       \noexpand\prepare@Xprenotes{#1}%
5472       \noexpand\prepare@edindex@fornote{\l@d@nums}%
5473       \unexpanded{\def\sw@list@inedtext}{\expandafter\
5474       unexpanded\expandafter{\sw@inthisedtext}}%The value of the \sw@inthisedtext
5475       of current \edtext will be pushed to \sw@list@inedtext when the notes are
5476       expanded.
5477       \noexpand\setcounter{stanzaR}{\the\c@stanzaR}%Save
5478       stanzaR counter for footnote
5479       \unexpanded{\def\@this@crossref@start}{\theedtext:
5480       start}%
5481       \unexpanded{\def\@this@crossref@end}{\theedtext:end}%
5482       \expandonce{\@beforeinsertofthisedtext}% Internal for
5483       now, no reason to make it public
5484       \noexpand\parse@annot\l@current@annot|%
5485       \noexpand\csuse{v#1footnote}{#1}%
5486       {\l@d@nums}{\expandonce{@tag}{\expandonce\content}}%
5487       %
5488       \noexpand\Xnote@false%
5489       \unexpanded{\advance\@edindex@fornote@\m@ne}%
5490       \unexpanded{\ undef\@this@crossref@start}%
5491       \unexpanded{\ undef\@this@crossref@end}%
5492       \ifbool{indtl@innote}%
5493         {\unexpanded{\let\index\orig@@index}}%
5494       \else%
5495         \ifluatex%
5496           \footnotelang@lua%

```

```

5497          \fi%
5498  \@ifundefined{xpg@main@language}{%if polyglossia
5499      {}%
5500      {\footnotelang@poly}%
5501      \footnoteoptions@{L}{##1}{true}%
5502      \xright@appenditem{%
5503          \ifbool{indtl@innote}%
5504              {\unexpanded{\let\index\nindex}}%
5505              {}%
5506          \ifbool{indtl@notenumber}%
5507              {\unexpanded{\let\index\nindex}}%There is no note
...number so
5508          {}%
5509          \noexpand\Xnote@true%
5510          \noexpand\prepare@Xprenotes{#1}%
5511          \noexpand\prepare@edindex@fornote{\l@d@nums}%
5512          \unexpanded{\def\sw@list@inedtext}{\expandafter\
5513          unexpanded\expandafter{\sw@inthisedtext}}%The value of the \sw@inthisedtext
5514          of current edtext will be pushed to \sw@list@inedtext when the notes are
5515          expanded.
5516          \ifl@dpairing%
5517              \noexpand\setcounter{stanzaL}{\the\c@stanzaL}%Save
5518          stanzaR counter for footnote
5519          \fi%
5520          \unexpanded{\def\@this@crossref@start}{\theedtext:
5521          start}%
5522          \unexpanded{\def\@this@crossref@end}{\theedtext:end}%
5523          \expandonce{\@beforeinsertofthisedtext}%Internal for
5524          now, no reason to make it public
5525          \noexpand\parse@annot\l@current@annot|%
5526          \noexpand\csuse{v#1footnote}%
5527          {#1}%
5528          {{\l@d@nums}{\expandonce\@tag}{\expandonce\content
}%
5529          }%
5530          \unexpanded{\ undef\@this@crossref@start}%
5531          \unexpanded{\ undef\@this@crossref@end}%
5532          \noexpand\Xnote@false%
5533          \unexpanded{\advance\@edindex@fornote@\m@ne}%
5534          \ifbool{indtl@innote}%
5535              {\unexpanded{\let\index\orig@@index}}%
5536              {}%
5537          \ifbool{indtl@notenumber}%
5538              {\unexpanded{\let\index\orig@@index}}%
              {}%
              }\to\inserts@list
              \global\advance\insert@count \one%
              \footnoteoptions@{L}{##1}{false}%
          \fi
      \else
          \csuse{v#1footnote}{#1}{{0|0|0|0|0|0|0|}{}{##1}}%
      
```

```

5539      \fi%
5540      \endgroup%
5541      \else%
5542      \led@err@FootnoteNotInSecondArgEdtext{\#1}%
5543      \fi%
5544      \ignorespaces%
5545      }
5546 %

```

Create counter used to determine on which page the previous note was called.

```

5547      \expandafter\newcount\csname #1prevpage@num\endcsname%
5548      \expandafter\newcount\csname #1prevpage@numR\endcsname%
5549 %

```

We need to be able to modify `reledmac`'s footnote macros and restore their

```

5550      \global\csletcs{\#1@@footnote}{\#1footnote}
5551 %

```

XXI.3.4 Set standard display

```

5552      \Xarrangement@normal{\#1}%
5553 %

```

End of for critical footnotes.

```

5554      \fi
5555 %

```

XXI.4 For familiar footnotes

Familiar footnotes are those which end with letters. We look for the `nofamiliar` option of `reledmac`.

```

5556      \unless\ifnofamiliar@
5557 %

```

XXI.4.1 Options

```

5558      \newtoggle{parindentX@\#1}
5559      \csgdef{wrapcontentX@\#1}{}%
5560      \csgdef{hangindentX@\#1}{0pt}%
5561      \csgdef{beforeinsertingX@\#1}{}%
5562      \csgdef{raggedX@\#1}{}%
5563      \csgdef{hsizetwocolX@\#1}{0.45 \hsize}%
5564      \csgdef{hsizethreecolX@\#1}{.3 \hsize}%
5565      \csgdef{colalignX@\#1}{\raggedright}%
5566      \csgdef{notenumfontX@\#1}{\normalfont}%
5567      \csgdef{notefontsizeX@\#1}{\footnotesize}%
5568      \csgdef{bhooknoteX@\#1}{}%

```

```

5569 \csgdef{bhookgroupX@#1}{}%
5570 \csgdef{afterruleX@#1}{0pt}
5571 \csgdef{beforenotesX@#1}{1.2em \oplus .6em \ominus .6em}
5572 \csgdef{maxhnotesX@#1}{0.8\vsizex}%
5573 \newtoggle{noteswidthliketwocolumnsX@#1}%
5574 \csgdef{parafootsepX@#1}{}%
5575 \csgdef{afternoteX@#1}{1em plus .4em minus .4em}
5576 \csgdef{widthX@#1}{\hsize}%
5577 \csgdef{txtbeforenotesX@#1}{}%
5578 \newtoggle{txtbeforesnotesX@#1@typeset}%"Not directly used by user,
but internal
5579 \newtoggle{txtbeforenotesonlyonceX@#1}%
5580 \csgdef{Xlinenumannotationposition@#1}{after}%
5581 % End of for familiar footnotes.
5582 % \subsubsection{Create inserts, needed to add notes in foot}
5583 % As regards inserts, see chapter 15 of the TeXBook by D. Knuth.
5584 % \begin{macrocode}
5585 \expandafter\newinsert\csname footins#1\endcsname%
5586 \unless\ifnoledgroup@%
5587 \expandafter\newinsert\csname mpfootins#1\endcsname%
5588 \fi%
5589 %

```

XXI.4.2 Create tools for familiar footnotes (\footnoteX)

First, create the \footnoteX command. Note the double # in command: it is because a command is called inside another command.

```

5590 \global\expandafter\newcommand\csname footnote#1\endcsname[1]{%
5591 \begingroup%
5592 \prepare@prenotesX{#1}%
5593 \newcommand{\content}{##1}%
5594 %
5595 %

```

If we use the \csquotes package, we reset the quotation level.

```

5596 \ifdefined\csq@qlevel%
5597 \csq@qlevel=0\relax%
5598 \fi%
5599 %

```

If we are preparing parallel typesetting, we cannot just increase the footnote counter. Read *reledpar*'s handbook about that (V.1.2 p. 53).

```

5600 \global\expandafter\advance\csname footnote#1@reading\
5601 endcsname by \one%
5602 \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or
5603 bool{l@dprintingcolumns}}{%
5604 \ifcsdef{footnote#1reading}{\the\csname footnote#1@reading\endcsname=typeset}%
5605 {\setcounter{footnote#1}{\csuse{footnote#1reading}{\the\csname footnote#1@reading\endcsname=typeset}}}%

```

```

5604      {\setcounter{footnote#1}{\the\csname footnote#1@reading
5605      \endcsname}}%
5606      }%
5607      \stepcounter{footnote#1}%
5608      }%

```

We also have to check consistency with `\onlysideX` setting.

```

5609      \ifledRcol%
5610          \ifcsstring{\onlysideX@#1}{L}{\
5611              \led@error@note@called@onrightside{footnote#1}}{}%
5612          \else%
5613              \ifcsstring{\onlysideX@#1}{R}{\
5614                  \led@error@note@called@onleftside{footnote#1}}{}%
5615          \fi%
5616      }%

```

And now, the feature not depending of wether we are preparing parallel typesetting

```

5615      \protected@csxdef{@thefnmark#1}{\csuse{the\footnote#1}}%
5616          \notoggle{nomk@}% Nomk is set to true when using \
5617          footnoteXnomk with \parpackage
5618              {\csuse{@footnotemark#1}}%
5619              {}%
5620              \ifluatex%
5621                  \xdef\footnote@luatextextdir{\the\textdir}%
5622                      \xdef\footnote@luatexpardir{\the\pardir}%
5623                  \fi%
5624                  \if@ledgroup%
5625                      \led@set@index@fornote{#1}%
5626                  \fi%
5627                  \csuse{vfootnote#1}{#1}{\expandonce\content}\m@mmf@prepare%
5628                      \ifbool{indtl@innote}%
5629                          {\let\index\orig@@index}%
5630                          {}%
5631                          \ifbool{indtl@notenumber}%
5632                              {\let\index\orig@@index}%
5633                              {}%
5634                      \endgroup%
5635      }%

```

Then define the counters. The \LaTeX counter `footnoteX` is the only one manipulated by the user. This is the one which is printed. The \TeX counter `\footnoteX@reading` is increased at each footnote. It is used for hyperlinks, for using `hyperlink` package, and for getting the correct footnote number when using parallel typesetting (V.1.2 p. 53).

```

5636      \newcounter{footnote#1}
5637          \global\expandafter\renewcommand\csname the\footnote#1\endcsname{\
5638              \arabic{footnote#1}}
5639          \expandafter\newcount\csname footnote#1@reading\endcsname%

```

Create counter used to determine on which page the previous note was called.

```
5640     \expandafter\newcount\csname prevpage#1@num\endcsname%
5641     \expandafter\newcount\csname prevpage#1@numR\endcsname%
5642     %
```

Add `\let\footnoteX\@gobble` to `\no@expands`.

```
5643     \expandafter\gappto\expandafter\no@expands\expandafter{\expandafter\
5644     let\csname footnote#1\endcsname\@gobble}%
5644     %
```

And now, define `\footnoteXmark` and `\footnoteXtext`, equivalent to classical `\footnotemark` and `\footnotetext`.

```
5645     \expandafter\newcommand\csname footnote#1mark\endcsname{%
5646     \begingroup%
5647     \prepare@prenotesX{#1}%
5648     \stepcounter{footnote#1}%
5649     \protected@csxdef{@thefnmark#1}{\csuse{thefootnote#1}}%
5650     \csuse{@footnotemark#1}%
5651     \m@mmf@prepare%
5652     \endgroup%
5653 }%
5654     \expandafter\newcommand\csname footnote#1text\endcsname[1]{%
5655     \begingroup%
5656     \csuse{vfootnote#1}{#1}{\expandonce{##1}}%
5657     \endgroup%
5658 }%
5659     %
```

Do not forget to initialize the series.

```
5660     \arrangementX@normal{#1}%
5661     \fi
5662     %
```

XXI.5 The endnotes

Endnotes are commands like `\Xendnote`, where X is a series letter. First, we check for the `noend` options.

```
5663     \unless\ifnoend@
5664     %
```

XXI.5.1 The auxiliary file

`\l@d@Xend` Endnotes of all varieties are saved up in a file, one by series, typically named $\langle jobname \rangle . Xend$.
`\ifl@dend@X` `\l@d@end` is the output stream number for this file, and `\ifl@dend@X` is a flag that is
`\l@dend@Xtrue` true when the file is open.
`\l@dend@Xfalse`

```

5665   \expandafter\newwrite\csname l@d@#1end\endcsname%
5666   \expandafter\newif\csname ifl@dend@#1\endcsname%
5667 %

```

XXI.5.2 The main macro

The `\Xendnote` macro functions to write one endnote to the `.Xend` file. We change `\newlinechar` so that in the file every space becomes the start of a new line; this generally ensures that a long note does not exceed restrictions on the length of lines in files.

```

5668
5669   \global\expandafter\newcommandx\csname #1endnote\endcsname[2][1,
5670     usedefault]{%
5671     \bgroup%
5672     \newlinechar='40%
5673     \global\@noneed@Footnotetru%
5674     \newcommand{\content}{##2}%
5675     \stepcounter{labidx}%
5676     \expandafter\immediate\expandafter\write\csname l@d@#1end\endcsname{%
5677       \unexpanded{\def\sw@list@inedtext}{%
5678         \expandafter\unexpanded\expandafter{\sw@inthisedtext}}%
5679         \@percentchar\space%Explicit space, to add a linebreak in the
5680         output file%
5681         \noexpand\parse@annot{l@current@annot}\@percentchar\space%
5682         \expandafter\string\csname #1end\endcsname%
5683         {\ifnumberedpar@\l@d@nums\fi}%
5684         {\ifnumberedpar@\expandonce@\tag\fi}%
5685         {\expandonce\content}%
5686         {##1}%
5687         {\unexpanded{##1}}%
5688         {\ifledRcol R\else L\fi}%
5689         {\theedtext}%
5690         \@percentchar%
5691       }%
5692     }%
5693 %

```

XXI.5.3 Tools

The `\Xtoendnotes` command inserts any arbitrary content into the endnote file. It is an alias of the more generalist `\addtoendnotes`

```

5694
5695   \global\expandafter\newcommand\csname #1toendnotes\endcsname[1]{%
5696     \toendnotes[#1]{##1}%

```

```

5697 }%
5698
5699 \expandafter\WithSuffix\expandafter\newcommand\csname #1toendnotes\
5700 endcsname*[1]{%
5701     \toendnotes*[#1]{##1}%
5702 }%
5703 %

```

XXI.5.4 Internal commands

\Xendnote commands called \Xend commands on to the endnote file; these are analogous to the various footfmt commands above, and they take the same arguments. When we process this file, we want to pick out the notes of one series and ignore all the rest. To do that, we equate the end command for the series we want to \endprint, and leave the rest equated to \@gobbleseven, which just skips over its seven arguments.

```

5704
5705     \global\cslet{\#1end}{\@gobbleseven}
5706 %

```

We need to store the number of times \doendnotesbysection is called for one series.

```

5707     \global\expandafter\newcount\csname #1end@bysection\endcsname%
5708 %

```

XXI.5.5 The options

```

5709     \csgdef{Xendwraplemma@#1}{}%
5710     \csgdef{Xendwrapcontent@#1}{}%
5711     \csgdef{Xendtwolines@#1}{}%
5712     \csgdef{Xendmorethan twolines@#1}{}%
5713     \newtoggle{Xendtwolinesbutnotmore@#1}{}%
5714     \newtoggle{Xendtwolinesonlyinsamepage@#1}{}%
5715     \newtoggle{Xendlemmadisablefontselection@#1}{}%
5716     \csgdef{Xendnotenumfont@#1}{\normalfont}%
5717     \csgdef{Xendnotefontsize@#1}{\footnotesize}%
5718     \csgdef{Xendbhooknote@#1}{}%
5719
5720     \csgdef{Xendsublinesep@#1}{\fullstop}%
5721
5722     \csgdef{Xendbeforenumber@#1}{0pt}%
5723     \csgdef{Xendafternumber@#1}{0.5em}%
5724
5725     \csgdef{Xendboxlinenum@#1}{0pt}%
5726     \csgdef{Xendboxlinenumalign@#1}{L}%
5727
5728     \csgdef{Xendboxstartlinenum@#1}{0pt}%
5729     \csgdef{Xendboxendlinenum@#1}{0pt}%

```

```

5730
5731 \csgdef{Xendlemmaseparator@#1}{}%
5732 \csgdef{Xendbeforelemmaseparator@#1}{0em}%
5733 \csgdef{Xendafterlemmaseparator@#1}{0.5em}%
5734 \csgdef{Xendinplaceoflemmaseparator@#1}{0.5em}%
5735
5736 \newtoggle{Xendparagraph@#1}%
5737 \csgdef{Xendafternote@#1}{\em plus .4em minus .4em}%
5738 \csgdef{Xendsep@#1}{}%
5739
5740 \csgdef{Xendinplaceofnumber@#1}{0pt}%
5741 \newtoggle{Xendnonumber@#1}%
5742
5743 \csgdef{Xendhangindent@#1}{0pt}%
5744 \newtoggle{Xendnumberonlyfirstinline@#1}%
5745 \newtoggle{Xendnumberonlyfirstintwolines@#1}%
5746
5747 \csgdef{Xendbeforesymlinenum@#1}{\csuse{Xendbeforenumber@#1}}%
5748 \csgdef{Xendaftersymlinenum@#1}{\csuse{Xendafternumber@#1}}%
5749 \csgdef{Xendsymlinenum@#1}{}%
5750 \csgdef{Xendboxsymlinenum@#1}{0pt}%
5751
5752 \csgdef{Xendbhooklinenumber@#1}{}%
5753 \csgdef{Xendehooklinenumber@#1}{}%
5754 \csgdef{Xendbhookinplaceofnumber@#1}{}%
5755 \csgdef{Xendehookinplaceofnumber@#1}{}%
5756
5757 \csgdef{Xendlinerangeseparator@#1}{\endashchar}%
5758
5759 \csgdef{Xendbeforepagenumber@#1}{\p.}%
5760 \csgdef{Xendafterpagenumber@#1}{}%
5761 \csgdef{Xendlineprefixsingle@#1}{}%
5762 \csgdef{Xendlineprefixmore@#1}{}%
5763
5764 \newtoggle{Xendlineflag@#1}%
5765
5766 \csgdef{Xendlemmafont@#1}{}%
5767
5768 \csgdef{Xendlinenumannotationposition@#1}{after}%
5769 \csgdef{Xendwraplinenumannotation@#1}{\textsuperscript}%
5770
5771 \newtoggle{Xendpagenumberonlyfirst@#1}%
5772 \newtoggle{Xendpagenumberonlyfirstifsingle@#1}%
5773 \newtoggle{Xendpagenumberonlyfirstintwo@#1}%
5774 \csgdef{Xendsympagenum@#1}{}%
5775 \csgdef{Xendinplaceofpagenumber@#1}{0pt}%
5776
5777 \csgdef{Xendtxtbeforenotes@#1}{}%
5778 \newtoggle{Xendifirstnote@#1}%
      Not a hook, but used to apply
      Xendtxtbeforenotes

```

```

5779 %
5780 %

```

End of endnotes declaration

```

5781 \fi%
5782 %

```

```

Dump series in \@series
5783 \listxadd{\@series}{#1}
5784 }
5785 }% End of \newseries
5786 %

```

XXI.6 Init standards series (A,B,C,D,E)

```

5787 \expandafter\newseries\expandafter{\default@series}
5788 %

```

XXII Setting series display

XXII.1 Change series order

\seriesatbegin `\seriesatbegin{⟨s⟩}` changes the order of series, to put the series ⟨s⟩ at the beginning of the list. The series can be the result of a command.

```

5789 \newcommand{\seriesatbegin}[1]{%
5790   \StrDel{\@series}{#1}[\@series]%
5791   \edef\@new{}%
5792   \listxadd{\@new}{#1}%
5793   \listxadd{\@new}{\@series}%
5794   \xdef\@series{\@new}%
5795 }
5796 %

```

\seriesatend And `\seriesatend` moves the series to the end of the list.

```

5797 \newcommand{\seriesatend}[1]{%
5798   \StrDel{\@series}{#1}[\@series]%
5799   \edef\@new{}%
5800   \listxadd{\@new}{\@series}%
5801   \listxadd{\@new}{#1}%
5802   \xdef\@series{\@new}%
5803 }
5804 %

```

XXII.2 Test series order

\ifseriesbefore `\ifseriesbefore{⟨seriesA⟩}{⟨seriesB⟩}{⟨true⟩}{⟨false⟩}` expands ⟨true⟩ if ⟨seriesA⟩ is printed before ⟨seriesB⟩, expands ⟨false⟩ otherwise.

```

5805 \newcommand{\ifseriesbefore}[4]{%
5806   \StrPosition{@series}{#1}[\@first]%
5807   \StrPosition{@series}{#2}[\@second]%
5808   \ifnumgreater{@second}{@first}{#3}{#4}%
5809 }
5810 %

```

XXII.2.1 Get the first series

In some specific case, we need to know the first series of the list of series.

```

\@getfirstseries \newcommand{\@getfirstseries}{%
5812   \ifdefempty{@series}{%
5813     \xdef@firstseries{}%
5814     {\StrChar{@series}{1}[\@firstseries]}%
5815   }%
5816 %

```

XXII.3 Series setting

XXII.3.1 General way of working

The setting's command (like `\numberonlyfirstinline`), also called “hooks” can be divided in two categories: those which require a string values and those which require a boolean value. The first category includes those which require a length value, because we store the length's expression send by user and we evaluate it only in the commands which requires to know the setting. The second category require boolean value only when it is set to FALSE. Otherwise, we understand the insinuated value is TRUE.

For each “hook” command, we store the value in commands (first category) or a etoolbox's toggle (second category) which names are in the form `\<hook>@<series>`. For example, when calling `\twolines{<sq.>}`, we store `sq.` in commands `\twolines@A`, `\twolines@B`, `\twolines@C...`for each series defined for use with `reledmac`, or, if the `[<series>]` optional argument was send, for each series of this argument.

These values are tested in some specific places, scattered in all the code, depending of their effects. The default values are defined by the `\newseries@` command.

In order to prevent code duplication, we have created some generic commands. Some of them change the value of any hook send as argument. Some other, getting a hook name, generate the user level commands.

XXII.3.2 Tools to set options

`\settoggle@series` `\settoggle@series{<series>}{<toggle>}{<value>}` is a generic command to switch toggles for some series. The arguments are:

- #1 (mandatory): the series for which the hooks should be set. If empty, all the series will be affected.

- #2 (mandatory): the name of the hook.
- #3 (mandatory): the new value of toggle (true or false).
- #4 (optional): if equal to `reload`, reload the footnote setting (call again `\Xarrangement` or `\arrangementX` or ... depending of the footnote display).
- #5 (optional): if not empty, and if #1 is empty, change the hook setting for pseudo-series, as `appref`.

```

5817 \newcommandx{\settoggle@series}[5][4,5,usedefault]{%
5818   \def\do##1{%
5819     \global\settoggle{#2@##1}{#3}%
5820     \ifstreq{#4}{critical}{%
5821       \csuse{Xarrangement@\csuse{series@display##1}}{##1}%
5822     }{%
5823       \ifstreq{#4}{familiar}{%
5824         \csuse{arrangementX@\csuse{series@displayX##1}}{##1}%
5825       }{%
5826     }%
5827     \ifstrempty{#1}{%
5828       \dolistloop{@series}%
5829       \ifstrempty{#5}{%
5830         \docslist{#5}%
5831       }{%
5832         \ifstrempty{#5}{%
5833           \docslist{#1}%
5834         }{%
5835       }%
5836     }%
5837   }%

```

`\setcommand@series` `\setcommand@series{<series>}{<command>}{<value>}` is a generic command to store hook's value into commands specific to some series. The arguments are:

- #1 (mandatory): the series for which the hooks should be set. If empty, all the series will be affected.
- #2 (mandatory): the name of the hook.
- #3 (mandatory): the new value of the hook/command.
- #4 (optional): if equal to `reload`, reload the footnote setting (call `\footnormal` or `\footparagraph` or ... depending of the footnote display).
- #5 (optional): if not empty, and if #1 is empty, change the hook setting for pseudo-series, as `appref`.

```

5838 \newcommandx{\setcommand@series}[5][4,5,usedefault]{%
5839   \def\do##1{%
5840     \csgdef{#2@##1}{#3}%
5841     \ifstrequal{#4}{critical}{%
5842       \csuse{Xarrangement@}\csuse{series@display##1}{##1}%
5843     }{}%
5844     \ifstrequal{#4}{familiar}{%
5845       \csuse{arrangementX@}\csuse{series@displayX##1}{##1}%
5846     }{}%
5847   }%
5848   \ifstrempty{#1}{%
5849     \dolistloop{\@series}%
5850     \ifstrempty{#5}{%
5851       \docslist{#5}%
5852     }%
5853   }%
5854   {%
5855     \docslist{#1}%
5856   }%
5857 }%
5858 %

```

XXII.3.3 Tools to generate options commands

\newhookcommand@series \newhookcommand@series\command names is a generic command to add new commands for hooks, like \Xhsizetwocol. The first argument is the name of the hook, the second a comma-separated list of pseudo-series where the hook can be used, like appref in the case of \Xtwolines. The second argument is also used to create commands named \<hookname>\<pseudoseries>, like \Xtwolinesappref.

```

5859 \newcommandx{\newhookcommand@series}[2][2,usedefault]{%
5860   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][]{%
5861     \setcommand@series{##1}{##1}{##2}[] [#2]%
5862   }%
5863   \ifstrempty{#2}{%
5864     \def\do##1{%
5865       \global\expandafter\newcommand\expandafter*\csname #1##1\endcsname
5866       [1]{%
5867         \csuse{##1}##1{####1}%
5868       }%
5869     }%
5870     \docslist{#2}%
5871   }%
5872 %

```

\newhooktoggle@series \newhooktoggle@series\command names is a generic command to add new commands for a new toggle hook, like \Xnumberonlyfirstinline. The second argu-

ment is also used to create commands named `\<hookname>\<pseudoseries>`, like `\Xtwolinesbutnotmoreappref`.

```

5873 \newcommandx{\newhooktoggle@series}[2][2,usedefault]{%
5874   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={%
5875     true},usedefault]{%
5876     \settoggle@series{##1}{#1}{##2}[] [#2]%
5877   }%
5878   \ifstrempty{#2}{}{%
5879     \def\do##1{%
5880       \global\expandafter\newcommand\expandafter*\csname #1##1\endcsname{%
5881         \csuse{#1}[##1]%
5882       }%
5883       \do csvlist{#2}%
5884     }%
5885   }%
5886 }

```

`\newhooktoggle@series@reload` `\newhookcommand@toggle@reload` does the same thing as `\newhooktoggle@series` but the commands created by this macro also reload the series arrangement, depending of type os notes

```

5887 \newcommand{\newhooktoggle@series@reload}[2]{%
5888   \global\expandafter\newcommandx\expandafter*\csname #1\endcsname[2][1,2={%
5889     true},usedefault]{%
5890     \settoggle@series{##1}{#1}{##2}[#2]%
5891   }%
5892 }

```

`\newhookcommand@series@reload` `\newhookcommand@series@reload` does the same thing as `\newhookcommand@series` but the commands created by this macro also reload the series' arrangement.

```

5893 \newcommand{\newhookcommand@series@reload}[2]{%
5894   \global\expandafter\newcommand\expandafter*\csname #1\endcsname[2][] {%
5895     \setcommand@series{##1}{#1}{##2}[#2]%
5896   }%
5897 }
5898 %

```

XXII.3.4 Options for critical notes

Before generating the commands that are used to set the critical notes, such as `\Xnumberonlyfirstinline`, `\Xlemmaseparator` and the like, we check the `nocritical` option.

```

5899 \unless\ifnocritical@
5900   \newhookcommand@series{Xwrapcontent}%
5901   \newhookcommand@series{Xbeforeinserting}%

```

```

5902 \newhookcommand@series{Xlemmafont}%
5903 \newhookcommand@series{Xwraplemma}%
5904 \newhooktoggle@series{Xparindent}
5905 \newhookcommand@series{Xhangindent}
5906 \newhookcommand@series{Xragged}
5907 \newhookcommand@series{Xsizetwocol}
5908 \newhookcommand@series{Xsizethreecol}
5909 \newhookcommand@series{Xcolalign}%
5910 \newhookcommand@series{Xnotenumfont}
5911 \newhookcommand@series{Xhooknote}
5912 \newhookcommand@series@reload{Xhookgroup}{critical}
5913 \newhookcommand@series{Xboxsymlinenum}%
5914 \newhookcommand@series{Xsymlinenum}
5915 \newhookcommand@series{Xbeforenumber}
5916 \newhookcommand@series{Xtxtbeforenumber}
5917 \newhookcommand@series{Xafternumber}
5918 \newhookcommand@series{Xbeforesymlinenum}
5919 \newhookcommand@series{Xaftersymlinenum}
5920 \newhookcommand@series{Xinplaceofnumber}
5921 \newhookcommand@series{Xlemmaseparator}
5922 \newhookcommand@series{Xbeforelemmaseparator}
5923 \newhookcommand@series{Xafterlemmaseparator}
5924 \newhookcommand@series{Xinplaceoflemmaseparator}
5925 \newhookcommand@series{Xtxtbeforenotes}
5926 \newhooktoggle@series{Xtxtbeforenotesonlyonce}%
5927 \newhookcommand@series@reload{Xafterrule}{critical}
5928 \newhooktoggle@series{Xnumberonlyfirstinline}
5929 \newhooktoggle@series{Xnumberonlyfirstintwo-lines}%
5930 \newhooktoggle@series{Xgroupbyline}%
5931 \newhooktoggle@series{Xgroupbylineseparatetwo-lines}%
5932 \newhooktoggle@series{Xnonumber}
5933 \newhooktoggle@series{Xpstart}
5934 \newhooktoggle@series{Xpstarteverytime}%

5935 \newhooktoggle@series{Xstanza}%
5936 \newhookcommand@series{Xstanzaseparator}%

5938 \newhooktoggle@series{Xonlypstart}
5939 \newhooktoggle@series{Xnonbreakableafternumber}
5940 \newhooktoggle@series{Xlemmadisablefontselection}
5941 \newhookcommand@series@reload{Xmaxhnotes}{critical}
5942 \newhookcommand@series@reload{Xbeforenotes}{critical}
5943 \newhooktoggle@series@reload{Xnoteswidthliketwocolumns}{critical}%
5944 \newhookcommand@series@reload{Xnotefontsize}{critical}

5946 \newhookcommand@series{Xboxlinenum}%
5947 \newhookcommand@series{Xboxlinenumalign}%

5949 \newhookcommand@series{Xboxstartlinenum}%
5950 \newhookcommand@series{Xboxendlinenum}%

```

```

5952   \newhookcommand@series{Xafternote}%
5953   \newhookcommand@series{Xparafootsep}
5954   \newhookcommand@series@reload{Xwidth}{critical}%
5955
5956   \ifundef{\Xhsizenodef}%
5957   {%
5958     \newcommandx{\Xhsizenodef}[2][1,usedefault]{%
5959       \led@warning@Xhsizenodef@deprecated%
5960       \Xwidth[#1]{#2}%
5961     }%
5962   }%
5963   {}%
5964   {}%
5965 \fi
5966 %

```

Now, hooks for critical notes which also apply to crossreferencing and line numbering at the sides of the page.

```

5967 \newhooktoggle@series{Xlineflag}[appref,SEref]
5968 \newhookcommand@series{Xtwolines}[appref,SEref]
5969 \newhookcommand@series{Xmorethantwolines}[appref,SEref]
5970 \newhookcommand@series{Xsublinesep}[appref,SEref,side]%
5971 \newhookcommand@series{Xpagelinesep}[appref,SEref,side]%
5972 \newhooktoggle@series{Xtwolinesbutnotmore}[appref,SEref]
5973 \newhooktoggle@series{Xtwolinesonlyinsamepage}[appref,SEref]
5974 \newhookcommand@series{Xlinerangeseparator}[appref,SEref]
5975 \newhookcommand@series{Xlinenumannotationposition}[side,appref,SEref]%
5976 \newhookcommand@series{Xwraplinenumannotation}[side,ref,appref,SEref]%
5977 %

```

XXII.3.5 Options for familiar notes

Before generating the optional commands for familiar notes, we check the `\nofamiliar` option.

```

5978 \unless\ifnofamiliar@
5979   \newhookcommand@series{wrapcontentX}%
5980   \newhookcommand@series{beforeinsertingX}%
5981   \newhooktoggle@series{parindentX}
5982   \newhookcommand@series{hangindentX}
5983   \newhookcommand@series{raggedX}
5984   \newhookcommand@series{hsizetwocolX}
5985   \newhookcommand@series{hsizethreecolX}%
5986   \newhookcommand@series{colalignX}%
5987   \newhookcommand@series{notenumfontX}%
5988   \newhookcommand@series{bhooknoteX}
5989   \newhookcommand@series@reload{bhookgroupX}{familiar}
5990   \newhookcommand@series@reload{beforenotesX}{familiar}
5991   \newhookcommand@series@reload{maxhnotesX}{familiar}

```

```

5992 \newhooktoggle@series@reload{noteswidthliketwocolumnsX}{familiar}%
5993 \newhookcommand@series@reload{afterruleX}{familiar}
5994 \newhookcommand@series@reload{notefontsizeX}{familiar}
5995 \newhookcommand@series{afternoteX}
5996 \newhookcommand@series{parafootsepX}
5997 \newhookcommand@series{txtbeforenotesX}%
5998 \newhooktoggle@series{txtbeforenotesonlyonceX}%
5999 \newhookcommand@series@reload{widthX}{familiar}%
6000 \ifundef{\hsizex}%
6001 {%
6002     \newcommandx{\hsizex}[2][1,usedefault]{%
6003         \led@warning@hsizex@deprecated%
6004         \widthX[#1]{#2}%
6005     }%
6006 }%
6007 { }%
6008 \fi
6009 %

```

XXII.3.6 Options for endnotes

Before generating the commands that are used to set the endnotes, such as `\Xnumberonlyfirstinline`, `\Xlemmaseparator+` and the like, we check the `noend` option.

```

6010 \unless\ifnoend@
6011     \newhookcommand@series{Xendwraplemma}
6012     \newhookcommand@series{Xendwrapcontent}
6013     \newhookcommand@series{Xendnotenumfont}
6014     \newhookcommand@series{Xendlemmafont}%
6015     \newhookcommand@series{Xendbhooknote}

6016
6017     \newhookcommand@series{Xendboxlinenum}%
6018     \newhookcommand@series{Xendboxlinenumalign}%

6019
6020     \newhookcommand@series{Xendboxstartlinenum}%
6021     \newhookcommand@series{Xendboxendlinenum}%

6022
6023     \newhookcommand@series{Xendnotefontsize}
6024     \newhooktoggle@series{Xendlemmadisablefontselection}
6025     \newhookcommand@series{Xendlemmaseparator}
6026     \newhookcommand@series{Xendbeforelemmaseparator}
6027     \newhookcommand@series{Xendafterlemmaseparator}
6028     \newhookcommand@series{Xendinplaceoflemmaseparator}

6029
6030     \newhookcommand@series{Xendbeforenumber}%
6031     \newhookcommand@series{Xendafternumber}%

6032
6033     \newhooktoggle@series{Xendparagraph}
6034     \newhookcommand@series{Xendafternote}
6035     \newhookcommand@series{Xendsep}

```

```

6036
6037   \newhookcommand@series{Xendinplaceofnumber}%
6038   \newhooktoggle@series{Xendnonumber}%
6039
6040   \newhooktoggle@series{Xendnumberonlyfirstinline}%
6041   \newhooktoggle@series{Xendnumberonlyfirstintwolines}%
6042
6043   \newhookcommand@series{Xendsymlinenum}%
6044   \newhookcommand@series{Xendbeforesymlinenum}%
6045   \newhookcommand@series{Xendaftersymlinenum}%
6046   \newhookcommand@series{Xendboxsymlinenum}%
6047
6048   \newhookcommand@series{Xendbhooklinenumber}%
6049   \newhookcommand@series{Xendahooklinenumber}%
6050   \newhookcommand@series{Xendbhookinplaceofnumber}%
6051   \newhookcommand@series{Xendahookinplaceofnumber}%
6052
6053   \newhookcommand@series{Xendhangindent}%
6054
6055   \newhooktoggle@series{Xendpagenumberonlyfirst}%
6056   \newhooktoggle@series{Xendpagenumberonlyfirstifsingle}%
6057   \newhooktoggle@series{Xendpagenumberonlyfirstintwo}%
6058   \newhookcommand@series{Xendsympagenum}%
6059   \newhookcommand@series{Xendinplaceofpagenumber}%
6060
6061   \newhookcommand@series{Xendtxtbeforenotes}%
6062
6063 \fi
6064   \newhooktoggle@series{Xendlineflag} [apprefwithpage,SErefwithpage]
6065   \newhookcommand@series{Xendtwolines} [apprefwithpage,SErefwithpage]
6066   \newhookcommand@series{Xendmorethan twolines} [apprefwithpage,SErefwithpage]
6067   \newhooktoggle@series{Xendtwolinesbutnotmore} [apprefwithpage,SErefwithpage]
6068   \newhooktoggle@series{Xendtwolinesonlyinsamepage} [apprefwithpage,
6069     SErefwithpage]
6070   \newhookcommand@series{Xendlinerangeseparator} [apprefwithpage,SErefwithpage
6071     ]
6072   \newhookcommand@series{Xendbeforepagenumber} [apprefwithpage,SErefwithpage,
6073     SErefonlypage]
6074   \newhookcommand@series{Xendafterpagenumber} [apprefwithpage,SErefwithpage]
6075   \newhookcommand@series{Xendlineprefixsingle} [apprefwithpage,SErefwithpage]
6076   \newhookcommand@series{Xendlineprefixmore} [apprefwithpage,SErefwithpage]
6077   \newhookcommand@series{Xendsublinesep} [apprefwithpage,SErefwithpage]
6078
6079 \newhookcommand@series{Xendlinenumannotationposition} [apprefwithpage,
6080   SErefwithpage]%
6081 \newhookcommand@series{Xendwraplinenumannotation} [apprefwithpage,
6082   SErefwithpage]%
6083 %

```

XXII.4 Hooks for a particular footnote

`\newhooktoggle@specific` `\newhooktoggle@specific` is a generic command to create boolean hook specific to a note.

```

6079 \newcommand{\newhooktoggle@specific}[1]{%
6080   \newtoggle{#1}%
6081   \define@key[mac]{truefootnoteoption}{#1}[]{\global\settoggle{#1@}{true}}%
When enabling footnote option
6082   \define@key[mac]{falsefootnoteoption}{#1}[]{\global\settoggle{#1@}{false}}
6083 }
6084 %

```

`\newhookarg@specific` `\newhookarg@specific` is a generic command to create argument hook specific to a note.

```

6085 \newcommand{\newhookarg@specific}[1]{%
6086   \define@key[mac]{truefootnoteoption}{#1}{\csgdef{#1@}{##1}}%
When enabling
footnote option
6087   \define@key[mac]{falsefootnoteoption}{#1}{\global\csundef{#1@}}%
When
disabling footnote option
6088 }
6089 %

```

And now, we define some hooks specific to a note.

```

6090 \newhooktoggle@specific{fulllines}%
6091 \newhooktoggle@specific{nonum}%
6092 \newhooktoggle@specific{nosep}%
6093 \newhookarg@specific{linerangesep}%
6094 %

```

`linerangesep@` `\linerangesep@` is defined by the option `linerangesep` of critical notes to change temporarily the line range separator for a specific line. As we have to define it before typesetting the line and undefine it after, we use the family of `xkeyval` package's key.

```
6095 %
```

`\nomk@` `\nomk@` toggle is used by `reledpar` to remove the footnote mark in the text when using `\footnoteXmk`. Read `reledpar` handbook.

```

6096 \newtoggle{nomk@}%
6097 %

```

XXII.5 Alias

`\Xnolemmaseparator` `\Xnolemmaseparator[⟨series⟩]` is just an alias for `\Xlemmaseparator[⟨series⟩]{}`.

```

6098 \newcommandx*\{\Xnolemmaseparator\}[1][1]{\Xlemmaseparator[#1]{}}
6099 %

```

XXIII Output routine

Now we begin the output routine and associated things.

XXIII.1 Extra footnotes output

With luck we might only have to change `\@makecol` and `\@reinserts` of the L^AT_EX's kernel. Since `reledmac`, we use `etoolbox`'s patching commands instead of overriding. It should provides better compatibility with other package which modify these commands

\doxtrafeet `\doxtrafeet` is the code extending `\@makecol` to cater for the extra `reledmac` feet. We have two categories of extra footnotes. By default, we order the footnote inserts so that the regular footnotes of L^AT_EX are first, then familiar familiar footnotes and finally the critical footnotes.

```

6100 \newcommand*{\l@ddoxtrafeet}{%
6101   \IfStrEq{familiar-critical}{\@fnpos}%
6102     {\do@feetX\do@Xfeet}%
6103     {f}%
6104   \IfStrEq{critical-familiar}{\@fnpos}%
6105     {\do@Xfeet\do@feetX}%
6106     {f}%
6107     \setbox\@outputbox \vbox{%
6108       \unvbox\@outputbox%
6109       \do@feet@custom@order{}{\@fnpos}%
6110     }%
6111   }%
6112 }%
6113 }%
6114 %
6115 %

```

\do@feet@custom@order `\do@feet@custom@order` is called when `\@fnpos` is neither ‘familiar-critical’, nor ‘critical-familiar’, that is, when the order is more complex. In this case, people must define the order for all footnote series. If they don't, L^AT_EX could perform an infinite run.

```

6116 \newcommand{\do@feet@custom@order}[2]{%
6117   \def\do##1{%
6118     \edef\@@notesseries{\@firstoftwo##1}%
6119     \edef\@@notetype{\@secondoftwo##1}%
6120     \ifdefstring{\@@notetype}{critical}%
6121       {\csuse{\#1append@Xnotes}{\@@notesseries}}%
6122       \ifdefstring{\@@notetype}{familiar}%
6123         {\csuse{\#1append@notesX}{\@@notesseries}}%
6124         {}%
6125       }%
6126     }%
6127     \expandafter\docs vlist\expandafter{#2}%
6128   }%

```

6129 %

\do@Xfeet \do@Xfeet is the code extending \makecol to cater to the extra critical feet.

```
6130 \newcommand*\do@Xfeet{%
6131   \setbox\outputbox \vbox{%
6132     \unvbox\outputbox
6133     \copXfeet}
6134 }
```

\@opXfeet The extra critical feet to be added to the output. . . A macro which appends critical notes to the output's routine, also adding vertical space before notes

```
\print@Xnotes \newcommand{\append@Xnotes}[1]{%
6135   \ifvoid\csuse{\#1footins}\else%
6136     \global\skip\csuse{\#1footins}=\csuse{Xbeforenotes@\#1}%
6137     \global\advance\skip\csuse{\#1footins} by\csuse{Xafterrule@\#1}%
6138     \print@Xnotes{\#1}%
6139   \fi%
6140 }
6141 }%
6142 %
```

The normal way to add one series, \print@Xnotes, is replaced by `reledpar` when using \Pages.

```
6143 \newcommand\print@Xnotes[1]{%
6144   \xdef\@currentseries{\#1}%
6145   \csuse{\#1footstart}{\#1}%
6146   \csuse{\#1footgroup}{\#1}%
6147 }%
6148 %
```

We print all series of notes by looping on them. We check before printing them that they are not voided.

```
6149 \newcommand*\@opXfeet{%
6150   \unless\ifnocritical%
6151     \gdef\firstXseries{}%
6152     \def\do##1{%
6153       \append@Xnotes{##1}%
6154     }%
6155     \dolistloop{\@series}%
6156   \fi%
6157 }%
6158 %
```

\l@ddodoreinxtrafeet \l@ddodoreinxtrafeet is the code for catering for the extra footnotes within \reinserts. We use the same category and ordering as in \l@ddoxtrafeet.

```
6159 \newcommand*\l@ddodoreinxtrafeet{%
6160   \IfStrEq{familiar-critical}{\@fnpos}
```

```

6161   {\@doreinfeetX\X@doreinfeet}%
6162   {%
6163     \IfStrEq{critical-familiar}{\@fnpos}%
6164       {\X@doreinfeet\@doreinfeetX}%
6165       {\@doreinfeetX\X@doreinfeet}%
6166     }%
6167   }%
6168   %
6169 %

```

\X@doreinfeet \X@doreinfeet is the code for catering for the extra critical footnotes within \@reinserts.

```

6170 \newcommand*\{\X@doreinfeet}{%
6171   \unless\ifnocritical%
6172     \def\do##1{%
6173       \ifvoid\csuse{##1footins}\else%
6174         \insert\csuse{##1footins}{\unvbox\csuse{##1footins}}%
6175       \fi}%
6176     \dolistloop{\@series}%
6177   \fi%
6178 }%
6179 %
6180 %

```

\print@notesX We have to add all the new kinds of familiar footnotes to the output routine. A macro \append@notesX which appends the familiar footnotes of one series onto the output routine, also adding \do@feetX vertical skip before notes.

```

\@doreinfeetX
6181 \newcommand{\append@notesX}[1]{%
6182   \ifvoid\csuse{footins#1}\else%
6183     \global\skip\csuse{footins#1}=\csuse{beforenotesX@#1}%
6184     \global\advance\skip\csuse{footins#1} by\csuse{afterruleX@#1}%
6185     \print@notesX{#1}%
6186   \fi%
6187 }%
6188 %

```

The normal way to print one series of notes. \print@Xnotes is replaced by reledpar when using \Pages.

```

6189 \newcommand\print@notesX[1]{%
6190   \xdef\@currentseries{#1}%
6191   \csuse{footstart#1}{#1}%
6192   \csuse{footgroup#1}{#1}%
6193 }%
6194 %

```

We print all the series of notes by looping on them. We check before printing them that they are not voided.

```

6195 \newcommand*\{\do@feetX}{%

```

```

6196 \unless\ifnofamiliar@%
6197   \gdef\firstseriesX@{ }%
6198   \setbox\@outputbox \vbox{%
6199     \unvbox\@outputbox%
6200     \def\do##1{%
6201       \append@notesX{##1}%
6202     }%
6203     \dolistloop{\@series}%
6204   \fi%
6205 }%
6206 %
6207 \newcommand{\@doreinfeetX}{%
6208   \unless\ifnofamiliar@%
6209   \def\do##1{%
6210     \ifvoid\csuse{footins##1}\else
6211       \insert%
6212         \csuse{footins##1}
6213         {\unvbox\csuse{footins##1}}%
6214     \fi%
6215   }%
6216   \dolistloop{\@series}%
6217 \fi%
6218 }%
6219 %
6220 %

```

XXIII.2 Patching standard output's commands

The `memoir` class does not use the ‘standard’ versions of `\@makecol` and `\@reinserts`, due to its sidebar insert. We had better add that code if `memoir` is used. (It can be awkward dealing with `\if` code within `\if` code, so don’t use `\ifl@dmemoir` here.)

```

6221 \@ifclassloaded{memoir}{%
6222 %

```

`memoir` is loaded so we use `memoir`’s built in hooks.

```

6223 \g@addto@macro{\m@ndoextrafeet}{\l@ddoxtrafeet}%
6224 \g@addto@macro{\m@mdodoreinextrafeet}{\l@ddodoreinxtrafeet}%
6225 }{%
6226 %

```

`memoir` has not been loaded, so patch `\@makecol` and `\@reinserts`. If the `fancyhdr` package < version 3.8 has been loaded, we patch the `\@makecol` command, because this package redefines the standard `\@makecol` in the preamble, to call `\@makecol` which have been `\let` to `\@makecol`. If this package is not loaded, we directly patch `\@makecol`. If the `fancyhdr` package \geq version 3.8, we also directly patch `\@makecol`, because `fancyhdr` does its own patch `\AtBeginDocument`.

```

6227 \ifboolexpr{%
6228   test{\@ifpackageloaded{fancyhdr}}%
6229   and test {\ifdef{\@latex@makecol}}%
6230 }{%
6231   \patchcmd{%
6232     {\@latex@makecol}%
6233     {\xdef\@freelist{\@freelist\@midlist}}%
6234     {\xdef\@freelist{\@freelist\@midlist}\l@ddoxtrafeet}%
6235     {}%
6236     {\led@error@fail@patch@@makecol}%
6237 }{%
6238   \patchcmd{%
6239     {\@makecol}%
6240     {\xdef\@freelist{\@freelist\@midlist}}%
6241     {\xdef\@freelist{\@freelist\@midlist}\l@ddoxtrafeet}%
6242     {}%
6243     {\led@error@fail@patch@@makecol}%
6244 }{%
6245   \patchcmd{%
6246     {\@reinserts}%
6247     {\ifvbox}%
6248     {\l@ddoreinextrafeet\ifvbox}%
6249     {}%
6250     {\led@error@fail@patch@@reinserts}%
6251   }{%
6252 }{%
6253 }%

```

It turns out that `\@doclearpage` also needs modifying.

`\if@led@nofoot` We have to check if there are any leftover feet.

```

6255 \newif\if@led@nofoot
6256
6257 %

```

```

6258 \@ifclassloaded{memoir}{%
6259 %

```

If the `memoir` class is loaded we hook into its modified `\@doclearpage`.

```

\@mem@extranofeet160 \g@addto@macro{\@mem@extranofeet}{%%
6261   \def\do#1{%
6262     \unless\ifnocritical@%
6263       \ifvoid\csuse{\#1footins}\else\@mem@nofootfalse\fi%
6264     \fi%
6265     \unless\ifnofamiliar@%
6266       \ifvoid\csuse{footins#1}\else\@mem@nofootfalse\fi%
6267     \fi%

```

```

6268   }
6269   \dolistloop{\@series}%
6270   }%
6271 }{%
6272 %

```

As `memoir` is not loaded we have patch `\@doclearpage`.

```

\@led@testifnofoot_{\newcommand*{\@led@testifnofoot}{%
  \@doclearpage{%
    \@led@nofoottrue%
    \ifvoid\footins\else%
      \@\led@nofootfalse%
    \fi%
    \def\do##1{%
      \unless\ifnocritical{%
        \ifvoid\csuse{##1footins}\else%
          \@\led@nofootfalse%
        \fi%
        \fi%
      \unless\ifnofamiliar{%
        \ifvoid\csuse{footins##1}\else%
          \@\led@nofootfalse%
        \fi%
        \fi%
      }%
      \dolistloop{\@series}%
    }%
  }%
  \pretocmd{%
    {\@doclearpage}%
    {\@led@testifnofoot}%
  }%
  {\led@error@fail@patch@@doclearpage}%
}
\patchcmd{%
  {\@doclearpage}%
  {\ifvoid\footins}%
  {\if@led@nofoot}%
}{%
  {\led@error@fail@patch@@doclearpage}%
}
}
%
```

XXIV Cross referencing

You can mark a place in the text using a command of the form `\edlabel{<foo>}`, and later refer to it using the label `<foo>` by typing `\edpageref{<foo>}`, or `\lineref{<foo>}` or `\sublineref{<foo>}` or `\pstartref`. These reference commands will produce, respectively, the page, line sub-line and pstart on which the `\edlabel{<foo>}` command occurred.

The reference macros warn you if a reference is made to an undefined label. If `{<foo>}` has been used as a label before, the `\edlabel{<foo>}` command will issue a complaint; subsequent `\edpageref` and `\edlineref` commands will refer to the latest occurrence of `\edlabel{<foo>}`.

\labelref@list Set up a new list, `\labelref@list`, to hold the page, line and sub-line numbers for each label.

```
6309 \list@create{\labelref@list}
6310 %
```

\zz@@@ Two convenience macros to zero three / four labeling counters in one go.

```
\zz@@@ 6311 \newcommand*{\zz@@@}{000|000|000}% Set three counters to zero in one go
       6312 \newcommand*{\zz@@@@}{000|000|000|000}% Set four counters to zero in one go
       6313 %
       6314 %
```

\edlabel The `\edlabel` command first writes a `\@lab` macro to the `\linenum@out` file. It then checks to see that the `\labelref@list` actually has something in it (if not, it creates a dummy entry), and pops the next value for the current label, storing it in `\label@refs`. Finally it defines the label to be `\empty` so that any future check will turn up the fact that it has been used.³⁶

This version of the original edmac `\label` uses `\@bsphack` and `\@esphack` to eliminate extra space problems and also use the L^AT_EX write methods for the `.aux` file.

Jesse Billett³⁷ found that the original code could be off by several pages. This version, hopefully cures that, and also allows for non-arabic page numbering.

```
6315 \newcommand*{\edlabel}[1]{%
6316   \leavevmode%
6317   \@bsphack%
6318   \ifboolexpr{bool{ledRcol} \or bool{ledRcol@}}{%
6319     \ifXnote@%
6320       \protected@write\@auxout{}{%
6321         {\string\l@dmake@labelsR\space\the\page|\l@dparsedstartline|\
6322           \l@dparsedstartsub|\l@annot@start|\the\c@pstartR|\#1}}%
6323       \ifdef{\hypertarget}{%
6324         \Hy@raisedlink{\hypertarget{\#1}{}}}}%
6325   }%
```

³⁶The remaining macros in this section were kindly revised by Wayne Sullivan, who substantially improved their efficiency and flexibility.

³⁷(jdb43@cam.ac.uk) via the `ctt` thread ‘ledmac cross referencing’, 25 August 2003.

```

6325 \else%
6326   \write\linenum@outR{\string\@lab}%
6327   \ifx\labelref@listR\empty%
6328     \xdef\label@refs{\zz@@@@}%
6329   \else%
6330     \gl@p\labelref@listR\to\label@refs%
6331   \fi%
6332   \ifvmode%
6333     \advancelabel@refs%
6334   \fi%
6335 %

```

Use code from the kernel \label command to write the correct page number. Also define an hypertarget if hyperref package is loaded.

```

6336   \protected@write\@auxout{}%
6337   {\string\l@dmake@labelsR\space\thepage|\label@refs|\the\c@pstartR
6338   |{\#1}|}%
6339   \ifdef{\hypertarget}%
6340     {\Hy@raisedlink{\hypertarget{\#1}{}}}%
6341   \fi%
6342 }{%
6343   \ifXnote@%
6344     \ifl@dpairing%pstart or pstartL?
6345       \protected@write\@auxout{}%
6346       {\string\l@dmake@labels\space\thepage|\l@dparsedstartline|\
6347       \l@dparsedstartsub||\annot@start|\the\c@pstart|{\#1}}%
6348       \ifdef{\hypertarget}%
6349         {\Hy@raisedlink{\hypertarget{\#1}{}}}%
6350       \else%
6351         \protected@write\@auxout{}%
6352         {\string\l@dmake@labels\space\thepage|\l@dparsedstartline|\
6353         \l@dparsedstartsub||\annot@start|\the\c@pstart|{\#1}}%
6354         \ifdef{\hypertarget}%
6355           {\Hy@raisedlink{\hypertarget{\#1}{}}}%
6356         \fi%
6357     \else%
6358       \write\linenum@out{\string\@lab}%
6359       \ifx\labelref@list\empty%
6360         \xdef\label@refs{\zz@@@@}%
6361       \else%
6362         \gl@p\labelref@list\to\label@refs%
6363       \fi%
6364       \ifvmode%
6365         \advancelabel@refs%
6366       \fi%
6367     \ifl@dpairing%Pstart or PstartL?
6368       \protected@write\@auxout{}%

```

```

6369      {\string\l@dmake@labels\space\thepage|\label@refs|\the\c@pstartL
|{#1}}%
6370      \ifdef{\hypertarget}%
6371          {\Hy@raisedlink{\hypertarget{#1}{}}{}}
6372          {}%
6373      \else%
6374          \protected@write\@auxout{}%
6375          {\string\l@dmake@labels\space\thepage|\label@refs|\the\c@pstart
|{#1}}%
6376          \ifdef{\hypertarget}%
6377              {\Hy@raisedlink{\hypertarget{#1}{}}{}}
6378              {}%
6379          \fi%
6380          \fi%
6381      }%
6382  \esphack}%
6383 %
6384 %

```

\advancelabel@refs In cases where `\edlabel` is the first element in a paragraph, we have a problem with line counts, because line counts change only at the first horizontal box of the paragraph. **\labelrefsparseline** Hence, we need to test `\edlabel` if it occurs at the start of a paragraph. To do so, we use `\ifvmode`. If the test is true, we must advance by one unit the amount of text we write into the `.aux` file. We do so using `\advancelabel@refs` command.

```

6385 \newcounter{line}%
6386 \newcounter{subline}%
6387 \newcounter{absline}%
6388 \newcommand{\advancelabel@refs}{%
6389     \setcounter{line}{\expandafter\labelrefsparseline\label@refs}%
6390     \stepcounter{line}%
6391     \setcounter{absline}{\expandafter\labelrefsparseabsline\label@refs}%
6392     \stepcounter{absline}%
6393     \ifsublines@%
6394         \setcounter{subline}{\expandafter\labelrefsparseline\label@refs}%
6395         %
6396         \stepcounter{subline}{1}%
6397         \def\label@refs{\theline|\thesubline|\theabsline}%
6398     \else%
6399         \def\label@refs{\theline|0|\theabsline}%
6400     \fi%
6401 }
6402 \def\labelrefsparseline#1|#2|#3{#1}%
6403 \def\labelrefsparseline#1|#2|#3{#2}%
6404 \def\labelrefsparseabsline#1|#2|#3{#3}%
6405 %

```

\l@dmake@labels The `\l@dmake@labels` macro gets executed when the labels file is read. For each label it defines a macro, whose name is made up partly from the label you supplied, that

contains the page, line and sub-line numbers. But first it checks to see whether the label has already been used (and complains if it has).

The initial use of `\newcommand` is to catch if `\l@dmakelabels` has been previously defined (by a class or package).

#1 page number, #2 line number, #3 sub-line number, #4 absolute line number, #5 line number annotation, #6 pstart number, #7 label.

```

6405 \newcommand*\l@dmakelabels(){}
6406 \def\l@dmakelabels#1|#2|#3|#4|#5|#6|#7{%
6407   \expandafter\ifx\csname the@label\csuse{XR@prefix}#7\endcsname%
6408     \relax%
6409   \else%
6410     \led@warn@DuplicateLabel{\csuse{XR@prefix}#7}%
6411   \fi%
6412   \global\providetoggle{label@#7@ledRcol}%False is the default value of
       this toggle, which tells us whether a label is linked to the right or left
       side%
6413   \csgdef{the@label\csuse{XR@prefix}#7}{#1|#2|#3|#4|#5|#6|\relax}%
6414   \ignorespaces}
6415 %
6416 %

```

L^AT_EX reads the aux file at both the beginning and end of the document, so we have to switch off duplicate label checking after the first time the file is read.

```

6417 \AtBeginDocument{%
6418   \def\l@dmakelabels#1|#2|#3|#4|#5|#6|#7{}%
6419 }
6420 %
6421 %

```

\@lab The `\@lab` command, which appears in the `\linenum@out` file, appends the current value of page, line, sub-line, and absolute line to the `\labelref@list`. These values are defined by the earlier `\@page`, `\@nl`, and the `\sub@on` and `\sub@off` commands appearing in the `\linenum@out` file.

L^AT_EX uses the page counter for page numbers. However, it appears that this is not the right place to grab the page number. That task is now done in the `\edlabel` macro. This version of `\@lab` appends just the current line and sub-line numbers to `\labelref@list`.

```

6422 \newcommand*\@lab{%
6423   \l@dmakelabels{%
6424     \ifledRcol
6425       \xright@appenditem{\linenumr@p{\line@numR}|%
6426         \iifsublines@ \sublinenumr@p{\subline@numR}\else 0\fi|%
6427         \the\absline@numR|%
6428         \current@annot|%
6429       }%
6430     \to\labelref@listR
6431   }
6432 }

```

```

6431   \else
6432     \xright@appenditem{%
6433       \linenumr@p{\line@num}|%
6434       \ifsblines@ \sublinenumr@p{\subline@num}\else 0\fi|%
6435       \the\absline@num|%
6436       \current@annot%
6437     }%
6438     \to\labelref@list
6439   \fi}
6440 %

```

\applabel \applabel, if called in \edtext will insert automatically both a starting and an ending label for the current edtext lines.

```

6441 \newcommand*{\applabel}[1]{%
6442   \if@edtext@secondarg@%
6443   %

```

Label should not be already defined.

```

6444 \ifcsundef{the@label#1}{%
6445   \csdef{the@label#1}{applabel}%
6446 }%
6447 {%
6448   \led@warn@DuplicateLabel{#1 (applabel)}%
6449 }%
6450 %

```

Parse the \edtext line numbers and annotations.

```

6451 \expandafter\l@dp@rsefotspec\l@d@nums|%
6452 \expandafter\parse@annot\l@current@annot|%
6453 %

```

Use the L^AT_EX standard hack for label.

```

6454 \@bsphack%
6455 %

```

And now, write the data in the auxiliary file.

```

6456 \ifledRcol%
6457   \protected@write\@auxout{}{%
6458     {\string\l@dmake@labelsR\space\l@dparsedstartpage|\l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstartR|{\#1: start}}%
6459     \ifdef{\hypertarget}{%
6460       {\Hy@raisedlink{\hypertarget{\#1:start}{}{}}{}}%
6461     }%
6462     \protected@write\@auxout{}{%
6463       {\string\l@dmake@labelsR\space\l@dparsedendpage|\l@dparsedendline||\l@dparsedendsub||\annot@end|\the\c@pstartR|{\#1:end}}%
6464   \else%

```

```

6465   \ifl@dpairing%pstart or pstartL?
6466     \protected@write\@auxout{%
6467       {\string\l@dmake@labels\space\l@dparsedstartpage|\
6468       \l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstartL|{\#1:
6469       start}}}%
6470       \ifdef{\hypertarget}{%
6471         {\Hy@raisedlink{\hypertarget{\#1:start}{}{}}{}}%
6472         {}%
6473       \protected@write\@auxout{%
6474         {\string\l@dmake@labels\space\l@dparsedendpage|\
6475         \l@dparsedendline|\l@dparsedendsub||\annot@end|\the\c@pstartL|{\#1:end}}{}}%
6476       \else%
6477         \protected@write\@auxout{%
6478           {\string\l@dmake@labels\space\l@dparsedstartpage|\
6479           \l@dparsedstartline|\l@dparsedstartsub||\annot@start|\the\c@pstart|{\#1:start}}{}}%
6480           \ifdef{\hypertarget}{%
6481             {\Hy@raisedlink{\hypertarget{\#1:start}{}{}}{}}%
6482             {}%
6483           \protected@write\@auxout{%
6484             {\string\l@dmake@labels\space\l@dparsedendpage|\
6485             \l@dparsedendline|\l@dparsedendsub||\annot@end|\the\c@pstart|{\#1:end}}{}}%
6486           \fi%
6487           \fi%
6488         %

```

Use the L^AT_EX standard hack for label.

```

6484   \@esphack%
6485 %

```

Warning if \applabel is called outside of \edtext.

```

6486   \else%
6487     \led@warn@AppLabel0utSecondArgEdtext{\#1}%
6488   \fi%
6489 %

```

End of \applabel

```

6490 }%
6491 %

```

```

\edlabelS \edlabelS and \edlabelE are just used to mark the beginning and the end of a passage.
\edlabelE
\edlabelSE
6492 \newcommand{\edlabelS}[1]{%
6493   \edlabel{\#1:start}%
6494 }
6495 \newcommand{\edlabelE}[1]{%
6496   \edlabel{\#1:end}%
6497 }
6498 \newcommand{\edlabelSE}[1]{%

```

```

6499     \edlabelS{#1}%
6500     \edlabelE{#1}%
6501 }
6502 %

```

\wrap@edcrossref \wrap@edcrossref is called around all reledmac crossref commands, except those which start with x. It adds the hyperlink.

```

6503 \newrobustcmd{\wrap@edcrossref}[2]{%
6504   \ifdef{\hyperlink}{%
6505     {\hyperlink{#1}{#2}}{%
6506       {#2}}{%
6507     }%
6508   }%

```

\edpageref If the specified label exists, \edpageref gives its page number.

\xpageref For this reference command, as for the other two, a special version with prefix x is provided for use in places where the command is to be scanned as a number, as in \linenum. These special versions have two limitations: they do not print error messages if the reference is unknown, and they can't appear as the first label or reference command in the file; you must ensure that a \edlabel or a normal reference command appears first, or these x-commands will always return zeros.

LaTeX already defines a \pageref, so changing the name to \edpageref.

```

6509 \newcommand*{\edpageref}[1]{\l@eref@undefined{#1}\wrap@edcrossref{#1}{\l@getref@num{1}{#1}}}
6510 \newcommand*{\xpageref}[1]{\l@getref@num{1}{#1}}
6511 %
6512 %

```

\edlineref If the specified label exists, \lineref gives its line number.

\xlineref

```

6513 \newcommand*{\edlineref}[1]{%
6514   \l@eref@undefined{#1}%
6515   \wrap@edcrossref{#1}{%
6516     \providetoggle{label@#1@ledRcol}% Required for the first run, when the
6517     label has not yet been parsed on the .aux file
6518     \iftoggle{label@#1@ledRcol}{%
6519       {\linenumrep{\l@getref@num{2}{#1}}}{%
6520         {\linenumrep{\l@getref@num{2}{#1}}}{%
6521           \xflagref{#1}}{%
6522         }%
6523       \newcommand*{\xlineref}[1]{\l@getref@num{2}{#1}}%
6524     }%
6525   }%

```

\sublineref If the specified label exists, \sublineref gives its sub-line number.

\xsublineref

```

6526 \newcommand*{\sublineref}[1]{%
6527   \l@dref@undefined{#1}%
6528   \wrap@edcrossref{#1}{%
6529     \providetoggle{label@#1@ledRcol}%Required for the first run, when the
       label has not yet been parsed on the .aux file
     \iftoggle{label@#1@ledRcol}{%
6531       {\sublinenumrepR{\l@dgetref@num{3}{#1}}}{%
6532       {\sublinenumrep{\l@dgetref@num{3}{#1}}}{%
6533     }%
6534   }%
6535 \newcommand*{\xsublineref}[1]{\l@dgetref@num{3}{#1}}
6536 %
6537 %

```

\xabslineref If the specified label exists, `\xabslineref` gives its absolute line number. This is generally used only by `reledmac` internal macros.

```

6538 \newcommand*{\xabslineref}[1]{\l@dgetref@num{4}{#1}}%
6539 %

```

\annotationref If the specified label exists, `\edannotationref` gives the line number annotation with
\xannotationref which it is associated.

```

6540 \newcommand*{\annotationref}[1]{%
6541   \l@dref@undefined{#1}%
6542   \wrap@edcrossref{#1}{%
6543     \l@wrap@ifemptybox{\Xwraplinenumannotation@ref}{%
6544       \l@dgetref@num{5}{#1}}%
6545     }%
6546   }%
6547 }%
6548 \newcommand*{\xannotationref}[1]{%
6549   \l@dgetref@num{5}{#1}}%
6550 }%
6551 %

```

\pstarteref If the specified label exists, `\pstarteref` gives its pstart number.

```

\pstarteref
6552 \newcommand*{\pstartref}[1]{\l@dref@undefined{#1}\wrap@edcrossref{#1}{\l@dgetref@num{6}{#1}}}{%
6553 \newcommand*{\xpstartref}[1]{\l@dgetref@num{6}{#1}}{%
6554 %
6555 %

```

\xflagref `\xflagref` finds the side flag of any ref defined with `\edlabel`.

```

6556 \newcommand*{\xflagref}[1]{\l@dgetref@num{7}{#1}}%
6557 %

```

The next three macros are used by the referencing commands above, and do the job of extracting the right numbers from the label macro that contains the page, line, and sub-line number.

\l@eref@undefined The **\l@eref@undefined** macro is called when you refer to a label with the normal referencing macros. Its argument is a label, and it just checks that the label has been defined.

```
6558 \newcommand*{\l@eref@undefined}[1]{%
6559   \expandafter\ifx\csname the@label#1\endcsname\relax
6560     \l@warn@RefUndefined{#1}%
6561   \fi}
6562 %
6563 %
```

\l@getref@num Next, **\l@getref@num** fetches the number we want. It has two arguments: the first is simply a digit, specifying whether to fetch a page (1), line (2), sub-line (3), (4) pstart number or (5) side flag. (This switching is done by calling **\l@dlabel@parse**.) The second argument is the label-macro, which because of the **\@lab** macro above is defined to be a string of the type 123|456|789.

```
6564 \newcommand*{\l@getref@num}[2]{%
6565   \expandafter
6566   \ifx\csname the@label#2\endcsname \relax
6567     000%
6568   \else
6569     \expandafter\expandafter\expandafter
6570     \l@dlabel@parse\csname the@label#2\endcsname|#1%
6571   \fi}
6572 %
6573 %
```

\l@dlabel@parse Notice that we slipped another | delimiter into the penultimate line of **\l@getref@num**, to keep the ‘switch-number’ separate from the reference numbers. This | is used as another parameter delimiter by **\l@dlabel@parse**, which extracts the appropriate number from its first argument. The |-delimited arguments consist of the expanded label-macro (three reference numbers), followed by the switch-number (1, 2, 3, 4, 5, 6) which defines which of the former seven numbers to extract. (It was given earlier as the first argument of **\l@getref@num**.)

```
6574 \newcommand*{\l@dlabel@parse}{}%
6575 \def\l@dlabel@parse#1|#2|#3|#4|#5|#6|#7|#8{%
6576   \ifcase #8%
6577     \or #1%
6578     \or #2%
6579     \or #3%
6580     \or #4%
6581     \or #5%
6582     \or #6%
```

```

6583   \or #7%
6584   \fi}
6585 %

```

- \xxref** The `\xxref` command takes two arguments, both of which are labels, e.g., `\xxref{mouse}{elephant}`. It first does some checking to make sure that the labels do exist (if one does not, those numbers are set to zero). Then it calls `\linenum` and sets the beginning page, line, and sub-line numbers to those of the place where `\label{mouse}` was placed, and the ending numbers to those at `{elephant}`. The point of this is to be able to manufacture footnote line references to passages which cannot be specified in the normal way as the first argument to `\edtext` for one reason or another. Using `\xxref` in the second argument of `\edtext` lets you set things up at least semi-automatically.

```

6586 \newcommand*{\xxref}[2]{%
6587   {%
6588     \expandafter\ifx\csname the@label#1\endcsname\relax%
6589       \let\@tempa\zz@@@%
6590       \def\@tempc{}%
6591     \else%
6592       \def\@tempa{%
6593         \l@dgetref@num{1}{#1}|%
6594         \l@dgetref@num{2}{#1}|%
6595         \l@dgetref@num{3}{#1}%
6596       }%
6597       \edef\@tempc{%
6598         \l@dgetref@num{5}{#1}%
6599       }%
6600     \fi%
6601     \expandafter\ifx\csname the@label#2\endcsname\relax%
6602       \let\@tempb\zz@@@%
6603       \def\@tempd{}%
6604     \else%
6605       \def\@tempb{%
6606         \l@dgetref@num{1}{#2}|%
6607         \l@dgetref@num{2}{#2}|%
6608         \l@dgetref@num{3}{#2}%
6609       }%
6610       \edef\@tempd{%
6611         \l@dgetref@num{5}{#2}%
6612       }%
6613     \fi%
6614     \global\appto{@beforeinsertofthisedtext}{%
6615       \def\@this@crossref@start{#1}%
6616     }%
6617     \global\appto{@beforeinsertofthisedtext}{%
6618       \def\@this@crossref@end{#2}%
6619     }%
6620     \linenum{\@tempa|\@tempb}%
6621     \edef\@tempc{\@tempc|\@tempd}%

```

```

6622      \expandafter\lineannot\expandafter{\@tempe}%
6623  }%
6624 }%
6625
6626 %
6627 %

```

`\appref` `\appref, \SEref, \apprefwithpage, \SErefwithpage and \SEonlypage` print cross-ref to some start / end lines defined by specific commands. It prints the lines as they should be printed in the apparatus (critical notes for not suffixed versions, endnotes for suffixed versions).

`\SErefwithpage` Here we define hooks similar to some those related to critical footnotes or endnotes.

So, first declare the default value of the hooks for the pseudo-series. Also declare the internal toggle which are switch by `reledmac`.

```

6628 \def\Xtwolines@appref{}%
6629 \def\Xtwolines@SEref{}%
6630
6631 \def\Xmorethantwolines@appref{}%
6632 \def\Xmorethantwolines@SEref{}%
6633
6634 \def\Xlinerangeseparator@appref{\endashchar}%
6635 \def\Xlinerangeseparator@SEref{\endashchar}%
6636
6637 \def\Xsublinesep@appref{\fullstop}%
6638 \def\Xsublinesep@SEref{\fullstop}%
6639
6640 \def\Xpagelinesep@appref{\fullstop}%
6641 \def\Xpagelinesep@SEref{\fullstop}%
6642
6643
6644 \newtoggle{Xtwolinesbutnotmore@appref}%
6645 \newtoggle{Xtwolinesbutnotmore@SEref}%
6646
6647 \newtoggle{Xtwolinesonlyinsamepage@appref}%
6648
6649 \newtoggle{Xtwolinesonlyinsamepage@SEref}%
6650
6651 \newtoggle{Xlineflag@appref}%
6652 \toggletrue{Xlineflag@appref}%
6653 \newtoggle{Xlineflag@SEref}%
6654 \toggletrue{Xlineflag@SEref}%
6655
6656 \def\Xlinenumannotationposition@appref{after}%
6657 \def\Xlinenumannotationposition@SEref{after}%
6658
6659 \def\Xwraplinenumannotation@appref{\textsuperscript}%
6660 \def\Xwraplinenumannotation@SEref{\textsuperscript}%
6661

```

```

6662 \def\Xendtwolines@apprefwithpage{}%
6663 \def\Xendtwolines@SErefwithpage{}%
6664
6665 \def\Xendmorethan twolines@apprefwithpage{}%
6666 \def\Xendmorethan twolines@SErefwithpage{}%
6667
6668 \def\Xendlinerangeseparator@apprefwithpage{\endashchar}
6669 \def\Xendlinerangeseparator@SErefwithpage{\endashchar}
6670 \def\Xendlinerangeseparator@SErefonlypage{\endashchar}
6671
6672 \def\Xendbeforepagenumber@apprefwithpage{p.}%
6673 \def\Xendbeforepagenumber@SErefwithpage{p.}%
6674 \def\Xendbeforepagenumber@SEonlypage{p.}%
6675
6676 \def\Xendafterpagenumber@apprefwithpage{} }%
6677 \def\Xendafterpagenumber@SErefwithpage{} }%
6678
6679
6680 \def\Xendlineprefixsingle@apprefwithpage{}%
6681 \def\Xendlineprefixsingle@SErefwithpage{}%
6682
6683 \def\Xendlineprefixmore@apprefwithpage{}%
6684 \def\Xendlineprefixmore@SErefwithpage{}%
6685
6686 \newtoggle{Xendtwolinesbutnotmore@apprefwithpage}%
6687 \newtoggle{Xendtwolinesbutnotmore@SErefwithpage}%
6688
6689 \def\Xendsublinesep@apprefwithpage{\fullstop}%
6690 \def\Xendsublinesep@SErefwithpage{\fullstop}%
6691
6692 \newtoggle{Xendtwolinesonlyinsamepage@apprefwithpage}%
6693 \newtoggle{Xendtwolinesonlyinsamepage@SErefwithpage}%
6694
6695 \newtoggle{Xendlineflag@apprefwithpage}
6696 \togglettrue{Xendlineflag@apprefwithpage}%Here, exception
6697 \newtoggle{Xendlineflag@SErefwithpage}
6698 \togglettrue{Xendlineflag@SErefwithpage}%Here, exception
6699
6700 \def\Xendlinenumannotationposition@apprefwithpage{after}%
6701 \def\Xendlinenumannotationposition@apprefwithpage@SErefwithpage{after}%
6702
6703 \def\Xendwraplinenumannotation@apprefwithpage{\textsuperscript}%
6704 \def\Xendwraplinenumannotation@SErefwithpage{\textsuperscript}%
6705 %
6706 \gdef\Xboxstartlinenum@appref{0pt}

```

Note that some of these hooks are declared but no user command can change their values. Such hooks are not pertinent for appref and apprefwithpage pseudo-series, but their values are nonetheless tested in some macros.

```

6708 \gdef \Xboxstartlinenum@SEref{0pt}
6709 \gdef \Xboxendlinenum@appref{0pt}
6711 \gdef \Xboxendlinenum@SEref{0pt}
6712
6713 \gdef \Xendboxstartlinenum@apprefwithpage{0pt}
6714 \gdef \Xendboxstartlinenum@SErefwithpage{0pt}
6715
6716 \gdef \Xendboxendlinenum@apprefwithpage{0pt}
6717 \gdef \Xendboxendlinenum@SErefwithpage{0pt}
6718
6719 \newtoggle{Xendpagenumberonlyfirst@apprefwithpage}
6720 \newtoggle{Xendpagenumberonlyfirst@SErefwithpage}
6721
6722 \newtoggle{Xendpagenumberonlyfirstifsingle@apprefwithpage}
6723 \newtoggle{Xendpagenumberonlyfirstifsingle@SErefwithpage}
6724
6725 \newtoggle{Xendpagenumberonlyfirstintwo@apprefwithpage}
6726 \newtoggle{Xendpagenumberonlyfirstintwo@SErefwithpage}
6727
6728 \gdef \Xendsympagenum@apprefwithpage{}
6729 \gdef \Xendsympagenum@SErefwithpage{}
6730
6731 \gdef \Xendinplaceofpagenumber@apprefwithpage{}
6732 \gdef \Xendinplaceofpagenumber@SErefwithpage{}
6733 %
6734 %

```

Now, declare the default values of `\@apprefprefixsingle` and `\@apprefprefixmore`, `\@SErefprefix`, `\@SErefprefixmore` and the commands which defines them.

```

6735 \newcommand{\@apprefprefixsingle}{}
6736 \newcommand{\@SErefprefixsingle}{}
6737
6738 \newcommand{\@apprefprefixmore}{}
6739 \newcommand{\@SErefprefixmore}{}
6740
6741 \newcommand{\setapprefprefixsingle}[1]{%
6742   \gdef \@apprefprefixsingle{\#1}%
6743 }
6744 \newcommand{\setSErefprefixsingle}[1]{%
6745   \gdef \@SErefprefixsingle{\#1}%
6746 }
6747
6748 \newcommand{\setapprefprefixmore}[1]{%
6749   \gdef \@apprefprefixmore{\#1}%
6750 }
6751 \newcommand{\setSErefprefixmore}[1]{%
6752   \gdef \@SErefprefixmore{\#1}%
6753 }
6754

```

```

6755 %
And not \setSErefonlypageprefixsingle and \setSErefonlypageprefixmore.

6756 \newcommand{\setSErefonlypageprefixsingle}[1]{%
6757   \gdef\SErefonlypage@prefixsingle{#1}%
6758 }%
6759 \newcommand{\setSErefonlypageprefixmore}[1]{%
6760   \gdef\SErefonlypage@prefixmore{#1}%
6761 }%
6762 %

```

And now, the main commands: \appref, \apprefwithpage, \SEref and \SErefwithpage. These commands call \reformatted@ and \reformattedwithpage, which calls \printlines and \printendlines. That is why we have previously declared all hooks values tested inside these last commands.

```

6763
6764 \newcommandx{\appref}[2][1,usedefault]{\reformatted@{#1}{#2}{appref}}
6765 \newcommandx{\SEref}[2][1,usedefault]{\reformatted@{#1}{#2}{SEref}}
6766
6767 \newcommandx{\apprefwithpage}[2][1,usedefault]{\reformattedwithpage@{#1}{#2}{appref}}
6768 \newcommandx{\SErefwithpage}[2][1,usedefault]{\reformattedwithpage@{#1}{#2}{SEref}}
6769 \newcommandx{\SErefonlypage}[2][1,usedefault]{\reformattedonlypage@{#1}{#2}{SEref}}
6770
6771
6772 \newcommand{\reformatted@}[3]{%
6773   \def\do##1{%
6774     \setkeys[mac]{truefootnoteoption}{##1}%
6775   }%
6776   \notblank{#1}{\docslist{#1}}{%
6777     \xdef\@currentseries{#3}%
6778     \ifcsempty{@#3prefixmore}{%
6779       {\@apprefprefixsingle}%
6780     }{%
6781       \IfEq{\xlineref{#2:start}}{\xlineref{#2:end}}{%
6782         {\csuse{@#3prefixsingle}}{%
6783           {\csuse{@#3prefixmore}}{%
6784         }%
6785       }%
6786       \ifboolexpr{%
6787         test{\ifcsempty{the@label#2:start}}{%
6788           or test{\ifcsempty{the@label#2:end}}{%
6789             {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}{%
6790               {%
6791                 \def\@this@crossref@start{#2:start}%
6792                 \def\@this@crossref@end{#2:end}%
6793                 \xdef\annot@start{\xannotationref{#2:start}}%

```

```

6794   \xdef\annot@end{\xannotationref{#2:end}}%
6795   \printlines\xpageref{#2:start}|\xlineref{#2:start}|\xsublineref{#2:
6796   start}|\xpageref{#2:end}|\xlineref{#2:end}|\xsublineref{#2:end}|\relax|\
6797   xflagref{#2:start}|%
6798   \undef@\this@crossref@end%
6799   \undef@\this@crossref@start%
6800   }%
6801   \def\do##1{%
6802     \setkeys[mac]{falsefootnoteoption}{##1}%
6803   }%
6804   \notblank{#1}{\docslist{#1}}{%
6805   }%
6806   \newcommand{\reformattedwithpage@}[3]{%
6807     \def\do##1{%
6808       \setkeys[mac]{truefootnoteoption}{##1}%
6809     }%
6810     \notblank{#1}{\docslist{#1}}{%
6811     \xdef@\currentseries{#3withpage}%
6812     \ifboolexpr{%
6813       test{\ifcsundef{the@label#2:start}}%
6814       or test{\ifcsundef{the@label#2:end}}%
6815     }%
6816     {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}%
6817     \def@\this@crossref@start{#2:start}%
6818     \def@\this@crossref@end{#2:end}%
6819     \printendlines\xpageref{#2:start}|\xlineref{#2:start}|\xsublineref{#2:
6820     start}|\xpageref{#2:end}|\xlineref{#2:end}|\xsublineref{#2:end}|\relax|\
6821     xflagref{#2:start}|%
6822     \undef@\this@crossref@end%
6823     \undef@\this@crossref@start%
6824   }%
6825   \def\do##1{%
6826     \setkeys[mac]{falsefootnoteoption}{##1}%
6827   }%
6828   \notblank{#1}{\docslist{#1}}{%
6829   }%
6830   \newcommand{\reformattedonlypage@}[3]{%
6831     \def\do##1{%
6832       \setkeys[mac]{truefootnoteoption}{##1}%
6833     }%
6834     \notblank{#1}{\docslist{#1}}{%
6835     \xdef@\currentseries{#3onlypage}%
6836     \ifboolexpr{%
6837       test{\ifcsundef{the@label#2:start}}%
6838       or test{\ifcsundef{the@label#2:end}}%
6839     }%
6840     {\led@warn@pairRefUndefined{#2}\nfss@text{\reset@font\bfseries ??}}%

```

```

6840 {\ifnumequal{\xpageref{#2:end}}{\xpageref{#2:start}}}{%
6841   {%
6842     \ifcvoid{#3onlypage@prefixsingle}{%
6843       {}%
6844       {\csletcs{Xendbeforepagenumber@#3onlypage}{#3onlypage@prefixsingle}{}}
6845     }%
6846     \printnpnum{%
6847       \wrap@edcrossref{#2:start}{\xpageref{#2:start}}%
6848     }%
6849   }%
6850   \ifcvoid{#3onlypage@prefixmore}{%
6851     {}%
6852     {\csletcs{Xendbeforepagenumber@#3onlypage}{#3onlypage@prefixmore}{}}
6853   \ifdef\linerangesep{%
6854     \printnpnum{%
6855       \wrap@edcrossref{#2:start}{\xpageref{#2:start}}%
6856       \linerangesep@%
6857       \wrap@edcrossref{#2:end}{\xpageref{#2:end}}%
6858     }%
6859   \else{%
6860     \printnpnum{%
6861       \wrap@edcrossref{#2:start}{\xpageref{#2:start}}%
6862       \csuse{Xendlinerangeseparator@\currentseries}%
6863       \wrap@edcrossref{#2:end}{\xpageref{#2:end}}%
6864     }%
6865   \fi%
6866 }%
6867 }%
6868 \def\do##1{%
6869   \setkeys[mac]{falsefootnoteoption}{##1}%
6870 }%
6871 \notblank{#1}{\docslist{#1}}{}%
6872 }%
6873 %

```

- `\edmakelabel` Sometimes the `\edlabel` command cannot be used to specify exactly the page and line desired; you can use the `\edmakelabel` macro make your own label. For example, if you insert `\edmakelabel{elephant}{10|25|0}` you will have created a new label, and a later call to `\edpageref{elephant}` would print ‘10’ and `\lineref{elephant}` would print ‘25’. The sub-line number here is zero. `\edmakelabel` takes a label, followed by a page and a line number(s) as arguments. L^AT_EX defines a `\makelabel` macro which is used in lists. Peter Wilson has changed the name to `\edmakelabel`.

```
6874 \newcommand*{\edmakelabel}[2]{\expandafter\xdef\csname the@label#1\endcsname{#2}}
```

6875
6876 %

(If you are only going to refer to such a label using \xxref, then you can omit entries in the same way as with \linenum (see VI.3 p. 139 and V.9 p. 105), since \xxref makes a call to \linenum in order to do its work.)

XXIV.1 Compatibility with xref

Here, we provide compatibility with the xref to enable reledmac's cross-referencing to external documents. We assume that the user loads xref *before* reledmac, but uses \externaldocument *after* loading reledmac.

\XR@test First, we patch the xr macro \XR@test, which is called on every line of the external .aux file, in order to also call macros specific to reledmac.

```
6877 \preto{cmd{\XR@test}}%
6878   {\XR@test@mac###1#2#3#4###}%
6879   {}%
6880   {}%
6881 %
```

\XR@test@mac The \XR@test@mac takes the full content of a line of the external .aux files, with the three final dots added by xr.

```
6882 \long\def{\XR@test@mac###1###{\XR@test@mac@test#1}%
6883 %
```

\XR@test@mac@test And finally, \XR@test@mac@test does the job. This code is based on the \XR@test macro of the xr package. However, note that the \XR@prefix is not called here, but it is integrated directly in \l@dmake@labels and \l@dmake@labelsR.

```
6884 \long\def{\XR@test@mac@test#1#2...{%
  The triple dots (NOT \ldots) are because
  of the line 22 of xr.sty v5.02 1994/05/28
6885   \ifx#1\l@dmake@labels%
6886     \l@dmake@labels#2%
6887   \else
6888     \ifx#1\l@dmake@labelsR%
6889       \l@dmake@labelsR #2%
6890     \fi%
6891   \fi%
6892 }%
6893 %
```

XXV Sidenotes

Regular \marginpars do not work inside numbered text — they do not produce any note but do put an extra unnumbered blank line into the text.

\@xympar Changing \@xympar a little at least ensures that \marginpars in numbered text do not disturb the flow.

```

6894 \pretocmd{\@xympar}{%
6895   {\ifnumberedpar@
6896     \led@warn@NoMarginpars
6897     \Cesphack
6898   \else}%
6899   {}%
6900   {}%
6901
6902 \apptocmd{\@xympar}{%
6903   {\fi}%
6904   {}%
6905   {}%
6906
6907 %

```

We provide sidenotes as replacement for `\marginpar` in numbered text.

`\sidenote@margin` These are the sidenote equivalents to `\line@margin` and `\linenummargin` for specifying which margin. The default is the right margin (opposite to the default for line numbers). `\l@getssidenote@margin` returns the number associated to sidenote margin:

left: 0

right: 1

outer: 2

inner: 3

```

6908 \newcount\sidenote@margin
6909 \newcommand*{\sidenotemargin}[1]{%
6910   \l@getssidenote@margin{#1}%
6911   \ifnum\@l@tempcntb>\m@ne
6912     \ifledRcol
6913       \global\sidenote@marginR=\@l@tempcntb
6914     \else
6915       \global\sidenote@margin=\@l@tempcntb
6916     \fi
6917   \fi}%
6918 \newcommand*{\l@getssidenote@margin}[1]{%
6919   \def\@tempa{#1}\def\@tempb{left}%
6920   \ifx\@tempa\@tempb
6921     \@l@tempcntb \z@
6922   \else
6923     \def\@tempb{right}%
6924     \ifx\@tempa\@tempb
6925       \@l@tempcntb \cne
6926     \else
6927       \def\@tempb{outer}%

```

```

6928   \ifx\@tempa\@tempb
6929     \@l@dtmcntb \tw@
6930   \else
6931     \def\@tempb{inner}%
6932     \ifx\@tempa\@tempb
6933       \@l@dtmcntb \thr@@
6934     \else
6935       \led@warn@BadSidenotemargin
6936       \@l@dtmcntb \m@ne
6937     \fi
6938   \fi
6939   \fi
6940 \fi}
6941 \sidenotemargin{right}
6942 %
6943 %

```

\l@dlp@rbox We need two boxes to store sidenote texts.

```

\l@drp@rbox
6944 \newbox\l@dlp@rbox
6945 \newbox\l@drp@rbox
6946 %
6947 %

```

\ledlsnotewidth These specify the width of the left/right boxes (initialised to \marginparwidth), their \ledrsnotewidth distance from the text (initialised to \linenumsep), and the fonts used.

```

\ledlsnotesep
6948 \newdimen\ledlsnotewidth \ledlsnotewidth=\marginparwidth
\ledrsnotesep
6949 \newdimen\ledrsnotewidth \ledrsnotewidth=\marginparwidth
\ledlsnotefontsetup
6950 \newdimen\ledlsnotesep \ledlsnotesep=\linenumsep
\ledrsnotefontsetup
6951 \newdimen\ledrsnotesep \ledrsnotesep=\linenumsep
6952 \newcommand*\{\ledlsnotefontsetup}{\raggedleft\footnotesize}
6953 \newcommand*\{\ledrsnotefontsetup}{\raggedright\footnotesize}
6954 %
6955 %

```

\ledleftnote \ledleftnote, \ledrightnote, \ledinernote, \ledouternote are the user commands for left, right, inner and outer sidenotes. The two last one are just alias for the \ledinernote two first one, depending of the page number. \ledsidenote{\text} is the command \ledouternote for a moveable sidenote.

```

\ledsidenote
6956 \newcommand*\{\ledleftnote}[1]{\edtext{}{\l@dlnote{#1}}}
6957 \newcommand*\{\ledrightnote}[1]{\edtext{}{\l@drnote{#1}}}
6958 \newcommand*\{\ledsidenote}[1]{\edtext{}{\l@dcnote{#1}}}%
6959 \newcommand*\{\ledinernote}[1]{\edtext{}{\l@disnote{#1}}}%
6960 \newcommand*\{\ledouternote}[1]{\edtext{}{\l@dosnote{#1}}}%
6961 %

```

\l@dlnote . The ‘footnotes’ for left, right, and moveable sidenotes. The whole scheme is reminiscent \l@drnote of the critical footnotes code.

```

\l@dcnote
\l@desnote
\l@disnote

```

```

6962 \newif\ifrightnoteup
6963   \rightnoteuptrue
6964
6965 \newcommand*{\l@dlsnote}[1]{%
6966   \begingroup%
6967   \newcommand{\content}{#1}%
6968   \ifnumberedpar@
6969     \ifledRcol%
6970       \xright@appenditem{\noexpand\vl@dlsnote{\expandonce\content}}%
6971         \to\inserts@listR
6972       \global\advance\insert@countR \cne%
6973     \else%
6974       \xright@appenditem{\noexpand\vl@dlsnote{\expandonce\content}}%
6975         \to\inserts@list
6976       \global\advance\insert@count \cne%
6977     \fi
6978   \fi%
6979   \ignorespaces%
6980   \endgroup%
6981 }%
6982
6983 \newcommand*{\l@drsnote}[1]{%
6984   \begingroup%
6985   \newcommand{\content}{#1}%
6986   \ifnumberedpar@
6987     \ifledRcol%
6988       \xright@appenditem{\noexpand\vl@drsnote{\expandonce\content}}%
6989         \to\inserts@listR
6990       \global\advance\insert@countR \cne%
6991     \else%
6992       \xright@appenditem{\noexpand\vl@drsnote{\expandonce\content}}%
6993         \to\inserts@list
6994       \global\advance\insert@count \cne%
6995     \fi
6996   \fi\ignorespaces%
6997   \endgroup%
6998 }%
6999
7000 \newcommand*{\l@dcsnote}[1]{%
7001   \begingroup%
7002   \newcommand{\content}{#1}%
7003   \ifnumberedpar@
7004     \ifledRcol%
7005       \xright@appenditem{\noexpand\vl@dcsnote{\expandonce\content}}%
7006         \to\inserts@listR
7007       \global\advance\insert@countR \cne%
7008     \else%
7009       \xright@appenditem{\noexpand\vl@dcsnote{\expandonce\content}}%
7010         \to\inserts@list
7011       \global\advance\insert@count \cne%

```

```

7012     \fi
7013     \fi\ignorespaces%
7014     \endgroup%
7015 }%
7016
7017 \newcommand*{\l@disnote}[1]{%
7018     \begingroup%
7019     \newcommand{\content}{#1}%
7020     \ifnumberedpar@%
7021         \ifledRcol%
7022             \xright@appenditem{\noexpand\vl@disnote{\expandonce\content}}{%
7023                 \to\inserts@listR%
7024             \global\advance\insert@countR \cne%
7025         \else%
7026             \xright@appenditem{\noexpand\vl@disnote{\expandonce\content}}{%
7027                 \to\inserts@list%
7028             \global\advance\insert@count \cne%
7029         \fi%
7030     \fi\ignorespaces%
7031     \endgroup%
7032 }%
7033
7034 \newcommand*{\l@dosnote}[1]{%
7035     \begingroup%
7036     \newcommand{\content}{#1}%
7037     \ifnumberedpar@%
7038         \ifledRcol%
7039             \xright@appenditem{\noexpand\vl@dosnote{\expandonce\content}}{%
7040                 \to\inserts@listR%
7041             \global\advance\insert@countR \cne%
7042         \else%
7043             \xright@appenditem{\noexpand\vl@dosnote{\expandonce\content}}{%
7044                 \to\inserts@list%
7045             \global\advance\insert@count \cne%
7046         \fi%
7047     \fi\ignorespaces%
7048     \endgroup%
7049 }%
7050 %

```

\vl@dlsnote Put the left/right text into boxes, but just save the moveable text. **\l@dcsnotetext**,
\vl@drsnote **\l@dcsnotetext@l** and **\l@dcsnotetext@r** are etoolbox's lists which will store the
\vl@dcnote content of sidenotes. We store the content in lists, because we need to loop later on
\vl@disnote them, in case many sidenote co-exist for the same line. That is there some special test
\vl@dosnote to do, in order to:

- Store the content of **\leadsidenote** to **\l@dcsnotetext** in any cases.
- Store the content of **\rightsidenote** to:

- `\l@dcsnotetext` if `\ledsidenote` is to be put on right.
- `\l@dcsnotetext@r` if `\ledsidenote` is to be put on left.
- Store the content of `\leftsidenote` to:
 - `\l@dcsnotetext` if `\ledsidenote` is to be put on left.
 - `\l@dcsnotetext@l` if `\ledsidenote` is to be put on right.

`\vl@disnote` and `\vl@dosnote` just call `\vl@dlsnote` or `\vl@drsnote`, depending of the page.

```

7052 \newcommand*{\vl@dlsnote}[1]{%
7053   \ifledRcol@%
7054     \l@l@dtempcntb=\sidenote@margin%
7055     \ifnum\l@l@dtempcntb>\@ne%
7056       \advance\l@l@dtempcntb by\page@numR%
7057     \fi%
7058   \else%
7059     \l@l@dtempcntb=\sidenote@margin%
7060     \ifnum\l@l@dtempcntb>\@ne%
7061       \advance\l@l@dtempcntb by\page@num%
7062     \fi%
7063   \fi%
7064   \ifodd\l@l@dtempcntb%
7065     \listgadd{\l@dcsnotetext@l}{#1}%
7066   \else%
7067     \listgadd{\l@dcsnotetext}{#1}%
7068   \fi
7069 }
7070 \newcommand*{\vl@drsnote}[1]{%
7071   \ifledRcol@%
7072     \l@l@dtempcntb=\sidenote@margin%
7073     \ifnum\l@l@dtempcntb>\@ne%
7074       \advance\l@l@dtempcntb by\page@numR%
7075     \fi%
7076   \else%
7077     \l@l@dtempcntb=\sidenote@margin%
7078     \ifnum\l@l@dtempcntb>\@ne%
7079       \advance\l@l@dtempcntb by\page@num%
7080     \fi%
7081   \fi%
7082   \ifodd\l@l@dtempcntb%
7083     \listgadd{\l@dcsnotetext}{#1}%
7084   \else%
7085     \listgadd{\l@dcsnotetext@r}{#1}%
7086   \fi%
7087 }
7088 \newcommand*{\vl@dcsnote}[1]{\listgadd{\l@dcsnotetext}{#1}}
7089 \newcommand{\vl@disnote}[1]{%

```

```

7091 \ifledRcol@%
7092   \tempcnta=\page@numR%
7093 \else%
7094   \tempcnta=\page@num%
7095 \fi%
7096 \ifodd\tempcnta% ODD => right page => inner side = left side
7097   \vl@dlsnote{#1}%
7098 \else%
7099   \vl@drsnote{#1}%
7100 \fi%
7101 }%
7102
7103 \newcommand{\vl@dosnote}[1]{%
7104   \ifledRcol@%
7105     \tempcnta=\page@numR%
7106   \else%
7107     \tempcnta=\page@num%
7108   \fi%
7109   \ifodd\tempcnta% ODD => right page => outer side = right side
7110     \vl@drsnote{#1}%
7111   \else%
7112     \vl@dlsnote{#1}%
7113   \fi%
7114 }%
7115 %
7116 %

```

`\setl@dlp@rbox` `\setl@dlprbox{\langle lednums\rangle}{\langle tag\rangle}{\langle text\rangle}` puts `\langle text\rangle` into the `\l@dlp@rbox` box.
`\setl@drpr@box` And similarly for the right side box. It is these boxes that finally get displayed in the margins.

```

7117 \newcommand*{\setl@dlp@rbox}[1]{%
7118   \begingroup%
7119     \parindent\z@\hspace{ledlsnotewidth}%
7120     \ledlsnotefontsetup%We kept it outside of the vbox, because can affect
the ragging
7121     \global\setbox\l@dlp@rbox%
7122     \ifleftnoteup%
7123       =\vbox to\z@{\{\ledlsnotefontsetup\vss #1\}}%We put \
ledlsnotefontsetup inside footnote because required for color command. Note
the {} to keep setting local.
7124     \else%
7125       =\vbox to 0.70\baselineskip{\{\ledlsnotefontsetup\strut#1\vss\}}%
7126     \fi%
7127   \endgroup%
7128 }
7129
7130 \newcommand*{\setl@drp@rbox}[1]{%
7131   \begingroup%
7132     \parindent\z@\hspace{ledrsnotewidth}%

```

```

7133 \ledrsnotefontsetup%We kept it outside of the vbox, because can affect
7134 the ragging
7135 \global\setbox\l@drp@rbox%
7136 \ifrightnoteup%
7137     =\vbox to\z@{\{\ledrsnotefontsetup\vss#1\}}%We put \ledrsnotefontsetup
7138     inside footnote because required for color command. Note the {} to keep
7139     setting local.
7140 \else%
7141     =\vbox to0.7\baselineskip{\{\ledrsnotefontsetup\strut#1\vss\}}%
7142 \fi%
7143 \endgroup%
7144 }%
7145 \newif\ifleftnoteup
7146 \leftnoteuptrue
7147 %

```

\@sidenotesep This macro is used to separate sidenotes of the same line.

```

7145 \newcommand{\setsidenotesep}[1]{\gdef\@sidenotesep{#1}}
7146 \newcommand{\@sidenotesep}{, }
7147 %

```

\affixside@note This macro puts any moveable sidenote text into the left or right sidenote box, depending on which margin it is meant to go in. It's a very much stripped down version of **\affixlin@num**.

Before do it, we concatenate all moveable sidenotes of the line, using **\@sidenotesep** as separator. It is the result that we put on the sidenote.

```

7148 \newcommand*{\affixside@note}{%
7149     \prepare@edindex@fornote{\the\page@num|\the\line@num|\the\subline@num|\
7150     the\page@num|\the\line@num|\the\subline@num|}%
7151     \def\sidenotecontent@{}%
7152     \numgdef{\itemcount@}{0}%
7153     \def\do##1{%
7154         \ifnumequal{\itemcount@}{0}%
7155             {%
7156                 \appto\sidenotecontent@{\@sidenotesep ##1}}% Not print not separator before
7157             {}%
7158             \numgdef{\itemcount@}{\itemcount@+\@ne}%
7159         }%
7160     \dolistloop{\l@dcsnotetext}%
7161     \ifnumgreater{\itemcount@}{1}{\led@err@ManySidenotes}{}%
7162 %

```

And we do the same for left and right notes (not movable).

```

7163 \gdef\@temp1@d{}%
7164 \gdef\@temp1@n{\l@dcsnotetext\l@dcsnotetext@l\l@dcsnotetext@r}%

```

```

7165 \ifx\@tempd@d\@tempd@n \else%
7166   \if@twocolumn%
7167     \if@firstcolumn%
7168       \setl@dlp@rbox{##1}{\sidenotecontent@}%
7169     \else%
7170       \setl@drp@rbox{\sidenotecontent@}%
7171     \fi%
7172   \else%
7173     \@l@dtmpcntb=\sidenote@margin%
7174     \ifnum\@l@dtmpcntb>\@ne%
7175       \advance\@l@dtmpcntb by\page@num%
7176     \fi%
7177     \ifodd\@l@dtmpcntb%
7178       \setl@drp@rbox{\sidenotecontent@}%
7179       \gdef\sidenotecontent@{}%
7180       \numgdef{\itemcount@}{0}%
7181       \dolistloop{\l@dcsnotetext@l}%
7182       \ifnumgreater{\itemcount@}{1}{\led@err@ManyLeftnotes}{}%
7183       \setl@dlp@rbox{\sidenotecontent@}%
7184     \else%
7185       \setl@dlp@rbox{\sidenotecontent@}%
7186       \gdef\sidenotecontent@{}%
7187       \numgdef{\itemcount@}{0}%
7188       \dolistloop{\l@dcsnotetext@r}%
7189       \ifnumgreater{\itemcount@}{1}{\led@err@ManyRightnotes}{}%
7190       \setl@drp@rbox{\sidenotecontent@}%
7191     \fi%
7192   \fi%
7193 \fi%
7194 \advance\@edindex@fornote@\m@ne%
7195 }
7196 %

```

XXVI Minipages and such

We can put footnotes into minipages. The preparatory code has been set up earlier, all that remains is to ensure that it is available inside a minipage box. This requires some alteration to the kernel code, specifically the `\@iiiminipage` and `\endminipage` macros. We will arrange this so that additional series can be easily added.

`\l@dfbeginmini` These will be the hooks in `\@iiiminipage` and `\endminipage`.

`\l@dfendmini` They can be extended to handle other things if necessary.

```

7197 \ifnoledgroup@ \else%
7198 \newcommand*{\l@dfbeginmini}{\@ledgrouptrue\l@dedbeginmini\
7199   \l@dfambeginmini}
7200   \newcommand*{\l@dfendmini}{%
7201     \IfStrEq{critical-familiar}{\@mpfnpos}%
7202       {\l@dedendmini\l@dfamendmini}%

```

```

7202      {%
7203          \IfStrEq{familiar-critical}{\@mpfnpos}{%
7204              {\l@dfamendmini\l@dedendmini}%
7205              {\do@feet@custom@order{mp@}{\@mpfnpos}}%
7206          }%
7207      }%
7208  %

```

\l@dedbeginmini These handle the initiation and closure of critical footnotes in a minipage environment.

```

7209  \l@dedendmini%
7210  \mp@append@Xnotes%
7211      \newcommand*{\l@dedbeginmini}{%
7212          \unless\ifnocritical%
7213              \def\do##1{%
7214                  \csletcs{v##1footnote}{mpv##1footnote}%
7215              }%
7216              \dolistloop{\@series}%
7217          \fi%
7218      }
7219      \newcommand*{\l@dedendmini}{%
7220          \unless\ifnocritical%
7221              \ifl@dpairing%
7222                  \ifledRcol%
7223                      \flush@notesR%
7224                  \else%
7225                      \flush@notes%
7226                  \fi%
7227              \def\do##1{%
7228                  \mp@append@Xnotes{##1}%
7229              }%
7230              \dolistloop{\@series}%
7231          \fi%
7232      \newcommand{\mp@append@Xnotes}[1]{%
7233          \ifvoid\csuse{mp#1footins}\else%
7234              \ifl@dpairing%
7235                  \ifparledgroup%
7236                      \ifledRcol%
7237                          \dimgdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+\skip%
7238 @nameuse{mp#1footins}}%
7239                  \else%
7240                      \dimgdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+\skip%
7241 @nameuse{mp#1footins}}%
7242                  \fi%
7243          \ifcsstring{series@display#1}{paragraph}{}{%
7244              \setbox\@nameuse{mp#1footins}=\vbox{%
7245                  \csuse{Xnotefontsize##1}%
7246                  \ifcsdef{Xhsize}{\csuse{series@display#1}##1}{}%

```

```

7247     \hsize\csuse{Xhsize\csuse{series@display#1}@\#1}%
7248 }{ }%
7249 \noindent\csuse{Xtxtbeforenotes@\#1}%
7250 \unvbox\nameuse{mp#1footins}%
7251 \parboxrestore%
7252 }%
7253 }%
7254 \csuse{mp#1footgroup}{\#1}%
7255 \fi%
7256 }%
7257 %

```

\l@dfambeginmini These handle the initiation and closure of familiar footnotes in a minipage environment.

```

\l@dfamendmini
\mp@append@notesX
7258 \newcommand*{\l@dfambeginmini}{%
7259   \unless\ifnofamiliar@%
7260     \def\do##1{\csletcs{vfootnote##1}{mpvfootnote##1}}%
7261     \dolistloop{\@series}%
7262   \fi%
7263 }%
7264
7265 \newcommand*{\l@dfamendmini}{%
7266   \unless\ifnofamiliar@%
7267     \def\do##1{%
7268       \mp@append@notesX{\##1}%
7269     }%
7270     \dolistloop{\@series}%
7271   \fi%
7272 }%
7273 \newcommand{\mp@append@notesX}[1]{%
7274   \ifvoid\csuse{mpfootins#1}\else%
7275     \ifcstr{series@displayX#1}{paragraph}{}{%
7276       \setbox\nameuse{mpfootins#1}=\vbox{%
7277         \csuse{notefontsizeX@\#1}%
7278         \ifcstr{hsize\csuse{series@display#1}X@\#1}{%
7279           \hsize\csuse{hsize\csuse{series@display#1}X@\#1}%
7280         }{ }%
7281           \noindent\csuse{txtbeforenotesX@\#1}%
7282           \unvbox\nameuse{mpfootins#1}%
7283           \parboxrestore%
7284         }%
7285       }%
7286     \csuse{mpfootgroup#1}{\#1}%
7287   \fi%
7288 }%
7289 %

```

\@iiiminipage This is our extended form of the kernel \@iiiminipage defined in `ltboxes.dtx`.

```

7290 \patchcmd{%

```

```

7291   {\@iiiminipage}%
7292   {\let\@footnotetext\@mpfootnotetext}%
7293   {\let\@footnotetext\@mpfootnotetext\l@dfreetbeginmini}%
7294   {}%
7295   {\@led@error@fail@patch@@iiiminipage}%
7296 %

```

\endminipage This is our extended form of the kernel \endminipage defined in `ltboxes.dtx`.

```

7297 \patchcmd{%
7298   {\endminipage}%
7299   {\footnoterule}%
7300   {\footnoterule\l@advance@parledgroup@beforenormalnotes}%
7301   {}%
7302   {\@led@error@fail@patch@endminipage}%
7303 %
7304 \patchcmd{%
7305   {\endminipage}%
7306   {\minipagefalse}%
7307   {\l@dfreetendmini\minipagefalse}%
7308   {}%
7309   {\@led@error@fail@patch@endminipage}%
7310 %
7311 %

```

\l@dunboxmpfoot \oldunboxmpfoot insert normal footnotes for ledgroup.

```

7312 \newcommand*{\l@dunboxmpfoot}{%
7313   \vskip\skip\@mpfootins
7314   \normalcolor
7315   \footnoterule
7316   \l@advance@parledgroup@beforenormalnotes
7317   \unvbox\@mpfootins%
7318 }
7319 %

```

When using parallel ledgroup, we need to store the vertical space added before footnote, in order to compensate them between left and right pages.

```

7320 \newcommand{\l@advance@parledgroup@beforenormalnotes}{%
7321   \ifparledgroup
7322     \ifl@dpairing
7323       \ifledRcol
7324         \dimgdef{\parledgroup@beforenotesR}{\parledgroup@beforenotesR+\
7325           \skip\@mpfootins}
7326         \else
7327           \dimgdef{\parledgroup@beforenotesL}{\parledgroup@beforenotesL+\
7328             \skip\@mpfootins}
7329       \fi
7328     \fi
7329   \fi

```

```
7330 }
7331 %
```

ledgroup This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, fixed width minipage.

```
7332 \newenvironment{ledgroup}{%
7333   \resetprevpage@num%
7334   \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
7335   \let\@footnotetext\@mpfootnotetext
7336   \l@dfetebeginmini%
7337 }{%
7338   \par
7339   \unskip
7340   \ifvoid\@mpfootins\else
7341     \l@unboxmpfoot
7342   \fi
7343   \l@dfeteendmini%
7344   \g@ledgroupfalse%
7345 }
7346 }
7347
7348 %
7349 %
```

ledgroupsized \begin{ledgroupsized}[\langle pos\rangle]{\langle width\rangle}

This environment puts footnotes at the end, even if that happens to be in the middle of a page, or crossing a page boundary. It is a sort of unboxed, variable \langle width\rangle minipage. The optional \langle pos\rangle controls the sideways position of numbered text.

```
7350 \newenvironment{ledgroupsized}[2][1]{%
7351   %
```

Set the various text measures.

```
7352   \hsize #2\relax
7353   %
```

Initialize fills for centering.

```
7354   \let\ledllfill\hfil
7355   \let\ledrlfill\hfil
7356   \def\@tempa{\#1}\def\@tempb{1}%
7357 %
```

Left adjusted numbered lines

```
7358   \ifx\@tempa\@tempb
7359     \let\ledllfill\relax
7360   \else
7361     \def\@tempb{r}%
7362     \ifx\@tempa\@tempb
7363 %
```

Right adjusted numbered lines

```

7364     \let\ledrlfill\relax
7365     \fi
7366     \fi
7367 %

```

Set up the footnoting.

```

7368 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
7369 \let\@footnotetext\@mpfootnotetext
7370 \l@dfreetbeginmini%
7371 }{%
7372 \par
7373 \unskip
7374 \ifvoid\@mpfootins\else
7375   \l@unboxmpfoot
7376 \fi
7377 \l@dfreetendmini%
7378 }
7379 %
7380 %

```

Close the \ifnoledgroup@ \else.

```

7381 \fi%
7382 %

```

\ifledgroupnotesL@ These boolean tests check if we are in the notes of a ledgroup. If we are, we do not
\ifledgroupnotesR@ number the lines. It could be useful for parallel ledgroup of `reledpar`.

```

7383 \newif\ifledgroupnotesL@
7384 \newif\ifledgroupnotesR@
7385 %

```

XXVII Indexing

Here is some code for indexing using page and line numbers.

XXVII.1 Looking on package order

First, ensure that `imakeidx` or `indextools` is loaded *before* `eledmac`.

```

7386 \AtBeginDocument{%
7387   \unless\ifl@imakeidx%
7388     \c@ifpackageloaded{imakeidx}{\led@error@PackageAfterEledmac{imakeidx}}{}%
7389   %
7390   \fi%
7391   \unless\ifl@indextools%
7392     \c@ifpackageloaded{indextools}{\led@error@PackageAfterEledmac{indextools}}{}%
7393   %
7394 }

```

```

7392     \fi%
7393     \unless\ifl@footmisc%
7394       \ifpackageloaded{footmisc}{\led@error@PackageAfterEledmac{footmisc}}{}%
7395     %
7396   }
7397 %

```

XXVII.2 Auxiliary macros for \edindex

`\pagelinesep` In order to get a correct line number we have to use the label/ref mechanism. These `\edindexlab` macros are for that.

```

\c@labidx
7398 \newcommand{\pagelinesep}{-}
7399 \newcommand{\edindexlab}{$&}
7400 \newcounter{labidx}
7401 \setcounter{labidx}{0}
7402 %
7403 %

```

`\doedindexlabel` This macro sets an `\edlabel`.

```

7404 \newcommand{\doedindexlabel}{%
7405   \stepcounter{labidx}%
7406   \edlabel{\edindexlab\thelabidx}%
7407 }
7408 %
7409 %

```

`\thepageline` This macro makes up the page/line number combo from the label/ref. The associated counter is never directly used, but it is required in order to not have any error message with `\edgls`.

```

7410 \newcounter{pageline}%
7411 \renewcommand{\thepageline}{%
7412   \thepage%
7413   \pagelinesep%
7414   \xlineref{\edindexlab\thelabidx}%
7415 }
7416 %

```

`\thestartpageline` These macros make up the page/line start/end number when the `\edindex` command
`\theendpageline` is called in critical notes.

```

7417 \newcommand{\thestartpageline}{%
7418   \l@dparsedstartpage%
7419   \pagelinesep%
7420   \l@dparsedstartline%
7421 }

```

```

7422 \newcommand{\theendpageline}{%
7423   \l@dparsedendpage%
7424   \pagelinesep%
7425   \l@dparsedendline%
7426 }
7427 %

```

XXVII.3 Code specific to \edindex in critical footnotes

- \@edindex@fornote@ This counter is incremented at the beginning of each note (either a footnote or a side-note), and decremented at the end of each note. If its value is greater than 0, that means we are inside a note.

```

7428 \newcount\@edindex@fornote@
7429 %

```

- \prepare@edindex@fornote@ This macro is called at the beginning of each critical note. It switches some parameters, to allow index referring to this note, with reference to page and line number. It also defines \@ledinnote@command which will be printed as an encapsulating command after the |.

```

7430 \newcommand{\prepare@edindex@fornote}[1]{%
7431   \l@dp@rsefootspec#1%
7432   \advance\@edindex@fornote@\@ne%
7433 }
7434 %

```

- \get@edindex@ledinnote@command@ The \get@edindex@ledinnote@command macro defines a \@ledinnote@command command which is added as an attribute (text inserted after |) of the next index entry.

Consequently, we write the definition of the location reference attribute in the .xdy file.

```

7435 \newcommand{\get@edindex@ledinnote@command}{%
7436   \ifxindy@%
7437     \gdef\@ledinnote@command{%
7438       ledinnote\thelabidx%
7439     }%
7440     \ifxindyhyperref@%
7441       \immediate\write\eledmac@xindy@out{%
7442         (define-attributes ("ledinnote\thelabidx"))^^J
7443         \space\space(markup-locref^^J
7444           \eledmacmarkuplocrefdepth^^J
7445           :open "\string\ledinnote[\edindexlab\thelabidx]{\@index@command
7446           }"^^J
7447             :close "}"^^J
7448             :attr "ledinnote\thelabidx"^^J
7449           )
7450     }%
7451   \else%

```

```

7451 \immediate\write\eledmac@xindy@out{%
7452   (define-attributes ("ledinnote\thelabidx"))^^J
7453   \space\space(markup-locref^^J
7454     \eledmacmarkuplocrefdepth^^J
7455     :open "\string\ledinnote{\@index@command}{""^^J
7456     :close "}"^^J
7457     :attr "ledinnote\thelabidx"^^J
7458   )
7459 }
7460 \fi%
7461 %

```

If we do not use `xindy` option, `\@ledinnote@command` will produce something like `ledinnote{formattingcommand}`.

```

7462 \else%
7463   \gdef\@ledinnote@command{%
7464     \ledinnote[\edindexlab\thelabidx]{\@index@command}%
7465   }%
7466 \fi%
7467 }%
7468 %

```

XXVII.4 Analysis of command in indexed text

`\get@index@command` This macro is used to analyze if a text to be indexed has a command after a `|`.

```

7469 \def\get@index@command#1|#2+{%
7470   \gdef\@index@txt{#1}%
7471   \gdef\@index@command{#2}%
7472   \xdef\@index@parenthesis{}%
7473   \IfBeginWith{\@index@command}{}{%
7474     \StrGobbleLeft{\@index@command}{1}[\@index@command@]%
7475     \global\let\@index@command\@index@command@%
7476     \xdef\@index@parenthesis{}%
7477   }{%
7478   \IfBeginWith{\@index@command}{}{%
7479     \StrGobbleLeft{\@index@command}{1}[\@index@command@]%
7480     \global\let\@index@command\@index@command@%
7481     \xdef\@index@parenthesis{}%
7482   }{%
7483 }
7484 %

```

XXVII.5 Code for the formatted index

`\ledinnote` These macros are used to specify that an index reference points to a note. Arguments of `\ledinnote` are: #1 (optional): the label for the hyperlink, #2: command applied to `\ledinnotemark` the number, #3: the number itself.

```

7485 \newcommandx{\ledinnote}[3][1,usedefault]{%
7486   \ifboolexpr{%
7487     test{\ifdefequal{\iftrue}{\ifHy@hyperindex}}%
7488     or%
7489     bool {xindyhyperref@}%
7490   }%
7491   {%
7492     \csuse{#2}{\hyperlink{#1}{\ledinnotemark{#3}}}%
7493   }%
7494   {%
7495     \csuse{#2}{\ledinnotemark{#3}}%
7496   }%
7497 }%
7498 \newcommand{\ledinnotehyperpage}[2]{\csuse{#1}{\ledinnotemark{\hyperpage{#2}}}}%
7499 \newcommand{\ledinnotemark}[1]{#1\emph{n}}%
7500 %

```

XXVII.6 Main code

Eledmac and ledmac were using the specific indexing tools of the `memoir` in order to allow multiple index. However, eledmac used `imakeidx` or `indextools` tools when one these two package was loaded. This system forced to maintained a double code, which was not very useful. Since `reledmac`, we use only the `imakeidx` or `indextools` tools.

The `memoir` class provides more flexible indexing than the standard classes. We need different code if the `memoir` class is being used, except if `imakeidx` or `indextools` is used.

```

\edindex Write the index information to the idx file.
\@wredindex
\dummy@edindex
7501 \newcommandx{\@wredindex}[2][1=\expandonce\jobname,usedefault]{% #1 = the
index name, #2 = the text
7502   \begingroup%
7503     \let\emph\@firstofone%
7504     \let\textbf\@firstofone%
7505     \let\textit\@firstofone%
7506     \let\textmd\@firstofone%
7507     \let\textnormal\@firstofone%
7508     \let\textrm\@firstofone%
7509     \let\textsc\@firstofone%
7510     \let\textsf\@firstofone%
7511     \let\textsl\@firstofone%
7512     \let\texttt\@firstofone%
7513     \let\textup\@firstofone%
7514     \xdef\@tmp{#2}%To be used in IfSubStr instead of #2 directly. Avoid
some expansion bugs (for example with \edindex{textsc{something}})
7515   \endgroup%
7516   \ifl@imakeidx%

```

```

7517      \ifnum\@edindex@fornote@>\z@%
7518          \IfSubStr[1]{\@tmp}{|}{\get@index@command#2+}{\get@index@command#2|+}
7519          %
7520          \get@edindex@ledinnote@command%
7521          \expandafter\imki@wrindexentry{#1}{\@index@txt|(\@ledinnote@command
7522          }{\thestartpageline}%
7523          \expandafter\imki@wrindexentry{#1}{\@index@txt|)\@ledinnote@command
7524          }{\theendpageline}%
7525          \else%
7526              \get@edindex@hyperref{#2}%
7527              \imki@wrindexentry{#1}{\@index@txt\@edindex@hyperref}{\thepageline}%
7528              \fi%
7529          \else%
7530              \ifnum\@edindex@fornote@>\z@%
7531                  \IfSubStr[1]{\@tmp}{|}{\get@index@command#2+}{\get@index@command#2|+}
7532                  %
7533                  \get@edindex@ledinnote@command%
7534                  \expandafter\protected@write\@indexfile{}%
7535                  {\string\indexentry{\@index@txt|(\@ledinnote@command}{\thestartpageline}
7536                  }%
7537                  \expandafter\protected@write\@indexfile{}%
7538                  {\string\indexentry{\@index@txt|)\@ledinnote@command}{\theendpageline}
7539                  }%
7540                  \else%
7541                      \protected@write\@indexfile{}%
7542                      {\string\indexentry{#2}{\thepageline}}
7543                      }%
7544                      \fi%
7545                      \fi%
7546      }
7547      %

```

Need to add the definition of \edindex to \makeindex, and initialise \edindex to do nothing.

```

7546 \pretocmd{\makeindex}{%
7547     \def\edindex{%
7548         \ifboolexpr{bool{numbering} or bool{numberingR} or bool{
7549             l@dprintingpages} or bool{l@dprintingcolumns}}{%
7550             \@bsphack%
7551             \doedindexlabel%
7552             \begingroup%
7553             \@sanitize%
7554             \@wredindex%
7555         }%
7556         \t%
7557         \led@warn@edinde@outsidenumbering%
7558         \index%
7559     }%

```

```

7559   }%
7560 }%
7561 {}%
7562 {\led@error@fail@patch@makeindex}%
7563 \newcommand{\edindex}[1]{\@bsphack\@esphack}
7564 \newcommandx{\dummy@edindex}[2][1=\expandonce\jobname,usedefault]{}%
7565 %

```

XXVII.7 Hyperlink

`\hyperlinkformat` `\hyperlinkformat` command is to be used to have both a internal hyperlink and a format, when indexing.

```

7566 \newcommand{\hyperlinkformat}[3]{%
7567   \ifstrempty{#1}{%
7568     {\hyperlink{#2}{#3}}%
7569     {\csuse{#1}{\hyperlink{#2}{#3}}}%
7570   }%
7571 %

```

`\hyperlinkR` `\hyperlinkR` command is to be used to create a internal hyperlink and `\ledRflag`, when indexing.

```

7572 \newcommand{\hyperlinkR}[2]{%
7573   \hyperlink{#1}{#2\@Rlineflag}%
7574 }%
7575 %
7576 %

```

`\hyperlinkformatR` `\hyperlinkformatR` command is to be used to create a internal hyperlink, a format and a `\@Rlineflag`, when indexing.

```

7577 \newcommand{\hyperlinkformatR}[3]{%
7578   \hyperlinkformat{#1}{#2}{#3\@Rlineflag}%
7579 }%
7580 %
7581 %

```

`\get@edindex@hyperref` `\get@edindex@hyperref` is to be used to define the `\@edindex@hyperref` macro, which, in index, links to the point where the index was called (with `hyperref`).

```

7582 \newcommand{\get@edindex@hyperref}[1]{%
7583 %

```

We have to disable temporary spaces to work through a `xstring` bug (or feature?)

```

7584 \edef\temp@{%
7585   \catcode`\ =9 %space need for catcode
7586   \detokenize{#1}%For active character in unicode
7587   \catcode`\ =10 % space need for catcode
7588 }%
7589 %

```

Now, we define `\@edindex@hyperref` if the `hyperindex` of `hyperref` is enabled.

```

7590  \ifdef{\iftrue}{\ifHy@hyperindex}{%
7591    \IfSubStr{\temp@}{|}%
7592      {\get@index@command#1+%
7593        \ifledRcol%
7594          \gdef\@edindex@hyperref{| \index@parenthesis %space kept
7595            hyperlinkformat{\index@command}%
7596            {\edindexlab\thelabidx}}%
7597        \else%
7598          \gdef\@edindex@hyperref{| \index@parenthesis %space kept
7599            hyperlinkformat{\index@command}%
7600            {\edindexlab\thelabidx}}%
7601        \fi%
7602      }%
7603      {\get@index@command#1+%
7604        \ifledRcol%
7605          \gdef\@edindex@hyperref{| hyperlinkR{\edindexlab\thelabidx}}%
7606        \else%
7607          \gdef\@edindex@hyperref{| hyperlink{\edindexlab\thelabidx}}%
7608        \fi%
7609      }%
7610    }%
7611  }%
7612  % If we use both xindy and hyperref, first get the \protect\cs{
7613  % index@command} command.
7614  % Then define \protect\cs{@edindex@hyperref} in the form \verb+eledmacXXX+
7615  % \begin{macrocode}
7616  % \ifxindyhyperref@%
7617  %   \IfSubStr{\temp@}{|}%
7618  %     {\get@index@command#1+}%
7619  %     {\get@index@command#1+}%
7620  %   \gdef\@edindex@hyperref{| eledmac\thelabidx}%
7621  %

```

If we start a reference range by a opening parenthesis, store the `\thelabidx` for the current `\edindex`, then define `\@edindex@hyperref` in the form `| (eledmac\thelabidx`.

```

7621  \IfStrEq{\index@parenthesis}{()}{%
7622    {%
7623      \csxdef{xindyparenthesis@\index@txt}{\thelabidx}%
7624      \gdef\@edindex@hyperref{| (eledmac\thelabidx}%
7625    }%
7626    {}%
7627  }%

```

This `\thelabidx` will be called back at the closing parenthesis, to have the same number in `\@edindex@hyperref` command that we had at the opening parenthesis. `\@edindex@hyperref` start by a closing parenthesis, then followed by `eledmacXXX` where `XXX` is the `\thelabidx` of the opening `\edindex`.

```

7628 \IfStrEq{\@index@parenthesis}{}{%
7629   {%
7630     \xdef\@edindex@hyperref{} \eledmac\csuse{xindy@{\@index@txt}}{%
7631       \global\csundef{xindy@{\@index@txt}}{%
7632     }%
7633   }%

```

Write in the .xdy file the attributes of the location.

```

7634 {%
7635   \immediate\write\eledmac@xindy@out{%
7636     (define-attributes ("eledmac\thelabidx"))^^J
7637     \space\space(markup-locref^^J
7638       \eledmacmarkuplocrefdepth^^J
7639       :open "\string\hyperlink{%
7640         \ifledRcol R\fi}{%
7641           {\@edindexlab\thelabidx}}{%
7642             {\ifdefempty{\@index@command}{%
7643               {}{%
7644                 {\@backslashchar\@index@command}}{%
7645               {"^^J
7646             :close "}}}"^^J
7647             :attr "eledmac\thelabidx"^^J
7648           )%
7649         }%
7650       }%
7651 }%

```

And now, in any other case.

```

7652 \else{%
7653   \gdef\@index@txt{\#1}{%
7654     \gdef\@edindex@hyperref{}{%
7655       \fi{%
7656     }%
7657   }%
7658 }%

```

XXVII.8 ‘innote’ and ‘notenumber’ option of `indextools` package

`\led@set@index@fornote` The `\led@set@index@fornote` is called when a familiar footnote is inserted — and not when it is read — and changes the `\index` command depending of the option of the `indextools` package. Its only argument is the note series.

```

7659 \newcommand{\led@set@index@fornote}[1]{%
7660   \ifboolext@innote{%
7661     {\let\index\nindex}{%
7662       {}{%
7663     \ifboolext@notenumber{%

```

```

7664   }%
7665   \renewcommand{\index}[2][\indtl@jobname]{%
7666     \orig@@index[##1]{%
7667       ##2|innotenumber{\this@footnoteX@reading}%
7668     }%
7669   }%
7670 }%
7671 {}%
7672 }%
7673 %

```

\led@reinit@index@fornote The \led@reinit@index@fornote just reset the default value of \index.

```

7674 \newcommand{\led@reinit@index@fornote}{%
7675   \ifbool{\indtl@innote}{%
7676     {\let\index\orig@@index}%
7677   }{%
7678   \ifbool{\indtl@notenumber}{%
7679     {\let\index\orig@@index}%
7680   }{%
7681 }%
7682 %

```

XXVIII Glossaries

Here, we define the \gls-like commands prefixed by ed, only if the package `glossaries` is loaded.

```

7683 \AtBeginDocument{%
7684   \@ifpackageloaded{glossaries}{%
7685   %

```

First those which arguments are [*options*] {*label*} [*insert*].

```

7686   \renewcommand{\do}[1]{%
7687     \expandafter\DeclareRobustCommandx\csname ed#1\endcsname[3][1,3,
7688     usedefault]{%
7689       \doedindexlabel%
7690       \csname#1\endcsname[counter=pageline,##1][##2][##3]%
7691     }%
7692     \expandafter\WithSuffix\expandafter\DeclareRobustCommandx\csname ed
7693     #1\endcsname*[3][1,3,usedefault]{%
7694       \doedindexlabel%
7695       \csname#1\endcsname*[counter=pageline,##1][##2][##3]%
7696     }%
7697     \docslist{%
7698       \gls,%
7699       \Gls,%
7700       \GLS,%

```

```

7700    glspl,%
7701    Glspl,%
7702    GLSpl,%
7703    glstext,%
7704    Glstext,%
7705    GLStext,%
7706    Glsfirst,%
7707    GLSfirst,%
7708    glsplural%
7709    Glsplural,%
7710    GLSplural,%
7711    glsfirstplural,%
7712    Glsfirstplural,%
7713    GLSfirstplural,%
7714    glsname,%
7715    Glsname,%
7716    GLSname,%
7717    glssymbol,%
7718    Glssymbol,%
7719    GLSsymbol,%
7720    gldesc,%
7721    Glsdesc,%
7722    GLSdesc,%
7723    glsuseri,%
7724    Glsuseri,%
7725    GLSuseri,%
7726    glsuserii,%
7727    Glsuserii,%
7728    GLSuserii,%
7729    glsuseriii,%
7730    Glsuseriii,%
7731    GLSuseriii,%
7732    glsuseriv,%
7733    Glsuseriv,%
7734    GLSuseriv,%
7735    glsuserv,%
7736    Glsuserv,%
7737    GLSuserv,%
7738    glsuservi,%
7739    Glsuservi,%
7740    GLSuservi%
7741    }%
7742    %

```

Then those which arguments are $\langle options \rangle \{ \langle label \rangle \} \{ \langle link text \rangle \}$.

```

7743    \renewcommand{\do}[1]{%
7744        \expandafter\DeclareRobustCommandx\csname ed#1\endcsname[3][1,
7745        usedefault]{%
7746            \doedindexlabel%
7747            \csname#1\endcsname[counter=pageline,##1]{##2}{##3}%

```

```

7747 }%
7748 \expandafter\WithSuffix\expandafter\DeclareRobustCommandx\csname ed
#1\endcsname*[3][1,usedefault]{%
7749   \doedindexlabel%
7750   \csname#1\endcsname*[counter=pageline,##1]{##2}{##3}%
7751 }%
7752 }%
7753 \docsylist{glsdisp,glslink}%
7754 %

```

Then those which arguments are [$\langle options \rangle$] { $\langle label \rangle$ }.

```

7755 \renewcommand{\do}[1]{%
7756   \expandafter\DeclareRobustCommandx\csname ed#1\endcsname[2][1,
    usedefault]{%
7757     \doedindexlabel%
7758     \csname#1\endcsname*[counter=pageline,##1]{##2}%
7759   }%
7760   \expandafter\WithSuffix\expandafter\DeclareRobustCommandx\csname ed
#1\endcsname*[2][1,usedefault]{%
7761     \doedindexlabel%
7762     \csname#1\endcsname*[counter=pageline,##1]{##2}%
7763   }%
7764 }%
7765 \docsylist{glsadd}%
7766 }{}%
7767 }%
7768 %

```

XXIX Verse

The original code is principally Wayne Sullivan's code from `edstanza`. However, the code has been many time modified by Maïeul Rouquette in order to obtain new features and improved compatibility with `reledpar`.

XXIX.1 Hanging symbol management

- `\@hangingsymbol` The macro `\@hangingsymbol` is used to insert a symbol on each hanging of verses. It is set by user level macro `\sethangingsymbol`.
- `\ifinstanza` For example, in French typography, the symbol is ‘[’. We obtain it by means of the following code:

```
\sethangingsymbol{[\,]}
```

The `\ifinstanza` boolean is used to ensure that we are in a stanza part.

```

7769 \def\@hangingsymbol{}%
7770 \newcommand*{\sethangingsymbol}[1]{%
7771   \gdef\@hangingsymbol{#1}%
7772 }%

```

```
7773 \newif\ifinstanza
7774 %
```

`\inserthangingsymbol` The boolean `\ifinserthangingsymbol` is set to TRUE when `\@lock` is greater than 1, i.e. when we are not in the first line of a verse. The switch of `\ifinserthangingsymbol` is made in `\do@line` before the printing of line but after the line number calculation.

```
7775 \newif\ifinserthangingsymbol
7776 \newcommand{\inserthangingsymbol}{%
7777 \ifinserthangingsymbol%
7778   \ifinstanza%
7779     \hangingsymbol%
7780   \fi%
7781 \fi%
7782 }%
7783 %
```

XXIX.2 Using & character

`\ampersand` Within a stanza the `\&` macro is going to be usurped. We need an alias in case an `&` needs to be typeset in a stanza. Define it rather than letting it in case some other package has already defined it.

```
7784 \newcommand*{\ampersand}{\char`\\&}
7785 %
7786 %
```

XXIX.3 Code category setting

`\stanza@count` Before we can define the main macros we need to save and reset some category codes.
`\stanzaindentbase` To save the current values we use `\next` and `\body` from the `\loop` macro.

```
7787 \chardef\body=\catcode`\@
7788 \catcode`\@=11
7789 \chardef\next=\catcode`\&
amp; \catcode`\&=\active
7791 %
7792 %
```

XXIX.4 Stanza count and indent

A count register is allocated for counting lines in a stanza; also allocated is a dimension register which is used to specify the base value for line indentation; all stanza indentations are multiples of this value. The default value of `\stanzaindentbase` is 20pt.

```
7793 \newcount\stanza@count
7794 \newlength{\stanzaindentbase}
```

```

7795     \setlength{\stanzaindentbase}{20pt}
7796
7797 %

```

- \strip@szacnt** The indentations of stanza lines are non-negative integer multiples of the unit called **\stanzaindentbase**. To make it easier for the user to specify these numbers, some list macros are defined. These take numerical values in a list separated by commas and assign the values to special control sequences using **\mathchardef**. Though this does limit the range from 0 to 32767, it should suffice for most applications, including *penalties*, which will be discussed below.

```

7798 \def\strip@szacnt#1,#2{\def\@tempb{#1}\def\@tempa{#2|}}
7799 \newcommand*{\setstanzavalues}[2]{\def\@tempa{#2,,|}%
7800     \stanza@count\z@%
7801     \def\next{\expandafter\strip@szacnt\@tempa%
7802         \ifx\@tempb\empty\let\next\relax\else%
7803             \expandafter\mathchardef\csname #1@\number\stanza@count%
7804             @\endcsname\@tempb\relax%
7805             \advance\stanza@count\@ne\fi\next}%
7806     \next}%
7807
7808 %

```

- \setstanzaindents** In the original edmac, **\setstanzavalues{sza}{(...)}** had to be called to set the indents, and similarly **\setstanzavalues{szp}{(...)}**. to set the penalties. **\setstanzaindents** and **\setstanzapenalties** macros are a convenience to give the user one less thing to worry about (misspelling the first argument).

```

7809 \newcommand*{\setstanzaindents}[1]{\setstanzavalues{sza}{#1}}
7810 \newcommand*{\setstanzapenalties}[1]{\setstanzavalues{szp}{#1}}
7811 %
7812 %

```

- \managestanza@modulo** Since version 0.13, the **stanzaindent repetition** counter can be used when the indentation is repeated every n verses. The **\managestanza@modulo** is a command which modifies the counter **stanza@modulo**. The command adds 1 to **stanza@modulo**, but if **stanza@modulo** is equal to the **stanzaindent repetition** counter, the command restarts it.

```

7813 \newcounter{stanzaindent repetition}
7814 \newcount\stanza@modulo
7815
7816 \newcommand*{\managestanza@modulo}[0]{%
7817     \advance\stanza@modulo\@ne%
7818     \ifnum\stanza@modulo>\value{stanzaindent repetition}%
7819         \stanza@modulo\@ne%
7820     \fi%
7821 }
7822 %

```

\stanzaindent The macro \stanzaindent, when called at the beginning of a verse, changes the indentation normally defined for this verse by \setstanzaindent. The starred version skips the current verse for the repetition of stanza indent.

```

7823 \newcommand{\stanzaindent}[1]{%
7824   \hspace{\dimexpr#1\stanzaindentbase-\parindent\relax}%
7825   \ignorespaces%
7826 }%
7827 \WithSuffix\newcommand\stanzaindent*[1]{%
7828   \stanzaindent{#1}%
7829   \global\advance\stanzat@modulo-\@ne%
7830   \ifnum\stanzat@modulo=0%
7831     \global\stanzat@modulo=\value{stanzaindentsrepetition}%
7832   \fi%
7833   \ignorespaces%
7834 }%
7835 %

```

XXIX.5 Numbering stanza

Here, macro for numbering stanza. First, the stanza counter.

```

\thestanza36 \newcounter{stanza}
7837 \renewcommand{\thestanza}{%
7838   \textbf{\arabic{stanza}}%
7839 }
7840 %

```

\ifnumberstanza Then, macro to activate automatically numbering of stanza.

```

7841 \newif\ifnumberstanza%
7842 %

```

\@insertstanzanumber Now, macro called at the first line of of verse of a stanza.

```

7843 \newcommand{\@insertstanzanumber}[0]{%
7844   \ifnumberstanza%
7845     \ifl@dpairing%
7846       \ifledRcol%
7847         \stanzanumwrapper{\thestanzaR}%
7848       \else%
7849         \stanzanumwrapper{\thestanzaL}%
7850       \fi%
7851     \else%
7852       \stanzanumwrapper{\thestanza}%
7853     \fi%
7854     \setline{1}%
7855   \fi%
7856 }%
7857 %

```

\@advancestanzanumber Also a command to advance the counter of stanza.

```

7858 \newcommand{\@advancestanzanumber}[0]{%
7859   \ifnumberstanza%
7860     \ifl@dpairing%
7861       \ifledRcol%
7862         \addtocounter{stanzaR}{1}%
7863       \else%
7864         \addtocounter{stanzaL}{1}%
7865       \fi%
7866     \else%
7867       \addtocounter{stanza}{1}%
7868     \fi%
7869   \fi%
7870 }%
7871 %

```

\stanzanumwrapper And finally, the wrapper for stanza number

```

7872 \newcommand{\stanzanumwrapper}[1]{%
7873   \flagstanza{#1}%
7874 }%
7875 %

```

XXIX.6 Stanza number in note

Here, the command called when printing stanza number in notes.

```

7876 \newcommand{\printstanza}[0]{%
7877   \ifboolexpr{bool{l@dpairing} or bool{l@dprintingpages} or bool{%
7878     l@dprintingcolumns}}{%
7879     \ifledRcol%
7880       \thestanzaR%
7881     \else%
7882       \thestanzaL%
7883     \fi%
7884   }{%
7885     \thestanza%
7886   }%
7887 }%
7888 %

```

XXIX.7 Main work

\stanza@line Now we arrive at the main works. \stanza@line sets the indentation for the line and starts a numbered paragraph—each line is treated as a paragraph. \stanza@hang sets \sza@penalty the hanging indentation to be used if the stanza line requires more than one print line.

If it is known that each stanza line will fit on one print line, it is advisable to set the hanging indentation to zero. \sza@penalty places the specified penalty following each

stanza line. By default, this facility is turned off so that no penalty is included. However, the user may initiate these penalties to indicate good and bad places in the stanza for page breaking.

```

7888 \newcommandx{\stanza@line}[2][1,2]{\usedefault}{%
7889   \ifnum\value{stanzaindentsrepetition}=0
7890     \ifcsdef{sza@\number\stanza@count 0}{%
7891       {%
7892         \parindent=\csname sza@\number\stanza@count 0\endcsname\%
7893         stanzaindentbase%
7894       }{%
7895         \led@err@StanzaIndentNotDefined%
7896       }%
7897     \else
7898       \ifcsdef{sza@\number\stanza@modulo 0}{%
7899         \parindent=\csname sza@\number\stanza@modulo 0\endcsname\%
7900         stanzaindentbase%
7901       }{%
7902         \led@err@StanzaIndentNotDefined%
7903       }%
7904     \fi
7905     \pstart[#1][#2]\stanza@hang\ignorespaces%
7906   }%
7907   \xdef\stanza@hang{\noexpand\leavevmode\noexpand\startlock
7908     \hangindent\expandafter
7909     \noexpand\csname sza@00\endcsname\stanzaindentbase
7910     \hangafter\@ne}
7911   \def\sza@penalty{\count@\csname szp@\number\stanza@count 0\endcsname
7912     \ifnum\count@>\@M\advance\count@-\@M\penalty-\else
7913     \penalty\fi\count@}
7914   %

```

\@startstanza Now we have the components of the `\stanza` macro, which appears at the start of a group of lines. This macro initializes the count and checks to see if hanging indentation and penalties are to be included. Hanging indentation suspends the line count, so that the enumeration is by verse line rather than by print line. If the print line count is desired, invoke `\let\startlock\relax` and do the same for `\endlock`. Here and above we have used `\xdef` to make the stored macros take up a bit less space, but it also makes them more obscure to the reader. Lines of the stanza are delimited by ampersands &. The last line of the stanza must end with `\&`.

```

7915 \xdef\@startstanza[#1][#2]{%
7916   \noexpand\instanzatrue\expandafter
7917   \begingroup%
7918   \catcode`\noexpand\&\active%
7919   \global\stanza@count\@ne\stanza@modulo\@ne
7920   \noexpand\ifnum\expandafter\noexpand
7921   \csname sza@00\endcsname=\z@\let\noexpand\stanza@hang\relax

```

```

7922 \let\noexpand\endlock\relax\noexpand\else\interlinepenalty
7923 \OM\rightskip\z@ plus 1fil\relax\noexpand\fi\noexpand\ifnum
7924 \expandafter\noexpand\csname szp@0@\endcsname=\z@
7925 \let\noexpand\sza@penalty\relax\noexpand\fi%
7926 \def\noexpand&{%
7927     \noexpand\newverse[] [] }%
7928 \def\noexpand\&{\noexpand\@stopstanza}%
7929 \noexpand\@advancestanzanumber%
7930 \noexpand\stanza@line[#1] [#2]%
7931 \noexpand\@insertstanzanumber%
7932 \let\par\relax\ignorespaces%No paragraph in verses
7933 }
7934
7935 \newcommandx{\stanza}[2][1,2]{\usedefault}{%
7936     \ifboolexpr{%
7937         not test{\ifdefvoid{\at@every@stanza}}%
7938         and test{\ifstrempty{#1}}%
7939         and test{\ifstrempty{#2}}}}{%
7940         {\@startstanza[] [\at@every@stanza]\at@start@every@stanza}%
7941         {\@startstanza[#1] [#2]\at@start@every@stanza}}%
7942 }%
7943
7944 \newcommandx{\@stopstanza}[2][1,2]{\usedefault}{%
7945     \unskip%
7946     \endlock%
7947     \ifboolexpr{%
7948         not test{\ifdefvoid{\at@every@stop@stanza}}%
7949         and test{\ifstrempty{#1}}%
7950         and test{\ifstrempty{#2}}}}{%
7951         {\before@every@stop@stanza\pend[] [\at@every@stop@stanza]}%
7952         {\before@every@stop@stanza\pend[#1] [#2]}%
7953     \endgroup%
7954     \instanzafalse%
7955 }
7956
7957 \newcommand{\AtEveryStopStanza}[1]{%
7958     \ifstrempty{#1}{%
7959         {\gdef\at@every@stop@stanza{} }%
7960         {\gdef\at@every@stop@stanza{\noindent#1}}%
7961     }%
7962     \WithSuffix\newcommand{\AtEveryStopStanza*}[1]{%
7963         \ifstrempty{#1}{%
7964             {\gdef\at@every@stop@stanza{} }%
7965             {\gdef\at@every@stop@stanza{#1}}%
7966         }%
7967         \def\at@every@stop@stanza{}%
7968
7969     \newcommand{\AtEveryStanza}[1]{%
7970         \ifstrempty{#1}{%
7971             {\gdef\at@every@stanza{} }%

```

```

7972   {\gdef\at@every@stanza{\noindent#1}}%
7973 }%
7974 \WithSuffix\newcommand\AtEveryStanza*[1]{%
7975   \ifstrempty{#1}{%
7976     {\gdef\at@every@stanza{}%}
7977     {\gdef\at@every@stanza{#1}}%
7978 }%
7979
7980
7981
7982 \newcommand{\AtStartEveryStanza}[1]{%
7983   \ifstrempty{#1}{%
7984     {\gdef\at@start@every@stanza{}%}
7985     {\gdef\at@start@every@stanza{#1}}%
7986 }%
7987 \def\at@start@every@stanza{}%
7988
7989 \newcommand{\BeforeEveryStopStanza}[1]{%
7990   \ifstrempty{#1}{%
7991     {\gdef\before@every@stop@stanza{}%}
7992     {\gdef\before@every@stop@stanza{#1}}%
7993 }%
7994 \def\before@every@stop@stanza{}%
7995
7996 \newcommandx*\newverse}[4][1,2,3,4]{\usedefault}%
7997   \unskip%
7998   \endlock\pend[#1][#3]\sza@penalty\global%
7999   \advance\stanza@count@ne\stanza@line[#2][#4]%
8000 }
8001
8002 %

```

\flagstanza Use `\flagstanza[len]{text}` at the start of a line to put `text` a distance `len` before the start of the line. The default for `len` is `\stanzaindentbase`.

```

8003 \newcommand*{\flagstanza}[2][\stanzaindentbase]{%
8004   \hskip -#1\llap{#2}\hskip #1\ignorespaces}
8005
8006 %

```

XXIX.8 Restore catcode and penalties

The ampersand & is used to mark the end of each stanza line, except the last, which is marked with \&. This means that `\halign` may not be used directly within a stanza line. This does not affect macros involving alignments defined outside `\stanza \&`. Since these macros usurp the control sequence `\&`, the replacement `\ampersand` is defined to be used if this symbol is needed in a stanza. Also we reset the modified category codes and initialize the penalty default.

```

8007     \catcode`&=\next
8008     \catcode`@=\body
8009     \setstanzavalues{szp}{0}
8010
8011 %

```

XXX Apparatus of Manuscripts

XXX.1 User level macro

\msdata The user level \msdata command only writes the manuscripts data in a numbered auxiliary file. There are two associated etoolbox counters.

```

\msdata@cR
8012 \def\msdata@c{}%
8013 \def\msdata@cR{}%
8014 \newcommand{\msdata}[1]{%
8015     \leavevmode%
8016     \unless\ifstopmsdata@inserted@%
8017         \stopmsdata@%
8018         \led@warning@msdata@withoutstop%
8019     \fi%
8020     \global\stopmsdata@inserted@false%
8021     \unless\ifledRcol%
8022         \numgdef{\msdata@c}{\msdata@c+1}%
8023         \ifdef{\hypertarget}{%
8024             \edlabel{\msdata@c:start:msdata}%
8025         }%
8026         \protected@write\linenum@out{}{%
8027             \string\@msd{\#1}%
8028         }%
8029     \else%
8030         \numgdef{\msdata@cR}{\msdata@cR+1}%
8031         \ifdef{\hypertarget}{%
8032             \edlabel{\msdata@cR:start:msdata}%
8033         }%
8034         \protected@write\linenum@outR{}{%
8035             \string\@msd{\#1}%
8036         }%
8037     \fi%
8038 }%
8039 %

```

\stopmsdata The user level \stopmsdata command only writes information about the end of manuscripts data in numbered auxiliary file.

```

8040 \newcommand{\stopmsdata}[0]{%
8041     \leavevmode%
8042     \unless\ifledRcol%
8043         \protected@write\linenum@out{}{%

```

```

8044     \string\@stopmsd%
8045   }%
8046   \ifdef{\hypertarget}{%
8047     \edlabel{\msdata@c:end:msdata}%
8048   }{%
8049   \else%
8050     \protected@write\linenum@outR{}{%
8051       \string\@stopmsd%
8052     }%
8053     \ifdef{\hypertarget}{%
8054       \edlabel{\msdata@cR:end:msdata}%
8055     }{%
8056     \fi%
8057     \global\stopmsdata@inserted@true%
8058   }%
8059 %

```

\ifstopmsdata@inserted@ The `\ifstopmsdata@inserted@` boolean is set to TRUE at every `\stopmsdata` and reset to FALSE at all `\msdata`. It also set to TRUE at every `\beginnumbering`. It is used to automatically insert `\stopmsdata` if forgotten before `\msdata`

```

8060 \newif\ifstopmsdata@inserted@
8061 %

```

XXX.2 Setting macro

Setting macros for the manuscripts apparatus tools is very easy: they just save their argument in an internal macro.

\setmsdataseries In which series of notes will be printed the apparatus of manuscripts?

```

8062 \newcommand{\setmsdataseries}[1]{%
8063   \gdef\@msdata@series{\#1}%
8064 }%
8065 \def\@msdata@series{A}%
8066 %

```

\setmsdataposition The label for the manuscripts data.

```

8067 \def\ms@data@position{msdata-regular}%
8068 \newcommand{\setmsdataposition}[1]{%
8069   \gdef\ms@data@position{\#1}%
8070 }%
8071 %

```

\setmsdatalabel The label for the manuscripts data.

```

8072 \def\ms@data@label{Ms.}%
8073 \newcommand{\setmsdatalabel}[1]{%

```

```

8074     \gdef\ms@data@label{#1}%
8075 }%
8076 %

```

XXX.3 Counters and lists

\@msd@c \@msd@c is a counter incremented at each \@msd read in auxiliary file.

```

8077 \numdef{\@msd@c}{0}
8078 \numdef{\@msd@cR}{0}
8079 %

```

\add@msd@ \add@msd@ is a counter incremented at each \add@msddata, that is at each time we prepare the insertion of manuscripts data footnote.

```

8080 \numdef{\add@msd@c}{0}%
8081 \numdef{\add@msd@cR}{0}%
8082 %

```

\@msdata@list The \@msdata@list will contain, for each line, the lists of command to be executed to insert the manuscripts apparatus. It will be filled on \add@msdata and looped on \insert@msdata, then emptied.

```

8083 \def\@msdata@list{}%
8084 %

```

XXX.4 Auxiliary file macros

\@msd The \@msd macro is written in the auxiliary file. It just defines three macros by \msdata macro, which allow us to know the manuscripts data, the line number and the absolute line number where it was called

It also stores the action code 1010 in the list of actions by line.

```

8085 \newcommand{\@msd}[1]{%
8086   \unless\ifledRcol%
8087     \global\numdef{\@msd@c}{\@msd@c+\@ne}%
8088     \csgdef{\msdata@\@msd@c @data}{#1}%
8089     \csxdef{\msdata@\@msd@c @linenumber}{\the\line@num}%
8090     \csxdef{\msdata@\@msd@c @abslinenumber}{\the\absline@num}%
8091     \xright@appenditem{\the\absline@num}{\actionlines@list}%
8092     \xright@appenditem{-1010}{\actions@list}%
8093   \else%
8094     \global\numdef{\@msd@cR}{\@msd@cR+\@ne}%
8095     \csgdef{\msdata@\@msd@cR @dataR}{#1}%
8096     \csxdef{\msdata@\@msd@cR @linenumberR}{\the\line@numR}%
8097     \csxdef{\msdata@\@msd@cR @abslinenumberR}{\the\absline@numR}%
8098     \xright@appenditem{\the\absline@numR}{\actionlines@listR}%
8099     \xright@appenditem{-1010}{\actions@listR}%
8100   \fi%

```

```
8101 }%
8102 %
```

- \@stopmsd Inserted in the auxiliary file by \stopmsd, the \@stopmsd macro will store in two commands the line number and the absolute line number on which it is called.

```
8103 \newcommand{\@stopmsd}[0]{%
8104   \unless\ifledRcol%
8105     \ifcsundef{@msdata@\@msdCc \@stoplinenumber}{%
8106       \csxdef{@msdata@\@msdCc \@stopabslinenumber}{\the\absline@num}%
8107       \csxdef{@msdata@\@msdCc \@stoplinenumber}{\the\line@num}%
8108     }{%
8109   \else%
8110     \ifcsundef{@msdata@\@msdCcR \@stoplinenumberR}{%
8111       \csxdef{@msdata@\@msdCcR \@stopabslinenumberR}{\the\absline@numR}%
8112       \csxdef{@msdata@\@msdCcR \@stoplinenumberR}{\the\line@numR}%
8113     }{%
8114   }{%
8115   \fi%
8116 }{%
8117 }
```

XXX.5 Action macro

- \add@msdata \add@msdata is executed on each line when action code 1010 is seen. It will not insert immediately the manuscript data footnote, as action code are executed before the line be typeset, and, consequently, could be on the previous page. So it just stores the manuscript data footnote to \@msdata@list.

```
8118 \newcommand{\add@msdata}{%
8119   \bgroup%
8120   \normalfont%
8121   \unless\ifledRcol@%
8122     \numgdef{\add@msdCc}{\add@msdCc+\@ne}%
8123     \ifcsdef{@msdata@\add@msdCc @data}{%
8124       \letcs{\@data}{@msdata@\add@msdCc @data}%
8125       \edef\l@d@num{%
8126         000% Start page = we don't print it
8127         \csuse{@msdata@\add@msdCc @linenumber}|% Start line number
8128         000% Start subline number, for now, not used
8129         000% End page number, we don't print it
8130         \ifnumless{\csuse{@msdata@\add@msdCc \@stopabslinenumber}}{\csuse{%
8131           @lastabsline@forpage@\the\page@num}}%
8132             {\csuse{@msdata@\add@msdCc \@stoplinenumber}}%End line number if
8133             in the same page
8134               {\csuse{@lastline@forpage@\the\page@num}}%Otherwise, last
8135               number of the page
8136               |%
8137             000% End sub line number, for now, not used
8138 }
```

```

8135     \edef\font@info{\Font
8136   }%
8137   \c@msd@options{fullpage=false}%
8138   \if\c@firstlineofpage% Try if the data are for the full page. If yes
8139   , will add options to the list.
8140     \unless\if\c@msd@data@insertedfrompreviouspage%
8141       \ifnumless{\c@use{\lastabsline}{\forpage}{\thepage}{\c@num}}{\c@use
8142         {\c@msd@add{\c@msd@c}{\stopabslinenumber}}+\c@ne}%
8143       {%
8144         \numdef{\c@tmp}{\add{\c@msd@c}{\c@ne}}%
8145         \ifcsdef{\c@msd@data}{\c@tmp}{\c@abslinenumber}%
8146           {\ifnumequal{\c@use{\c@msd@data}{\c@tmp}}{\c@use{
8147             \lastabsline}{\forpage}{\thepage}{\c@num}}%
8148             {}%
8149           {\c@msd@options{fullpage=true}}%
8150             {}%
8151             \fi%
8152           \fi%
8153         \listxadd{\c@msd@list}{%
8154           \c@msd@options{iffullpage}%
8155           \ifluatex%
8156             \c@sxdef{footnote}{\luatextextdir}{\textdir}%
8157             \c@sxdef{footnote}{\luatexpardir}{\pardir}%
8158             \fi%
8159             \c@def{\this@crossref@start}{\add{\c@msd@c}{\start:\c@msd@data}}%
8160             \c@def{\this@crossref@end}{\add{\c@msd@c}{\end:\c@msd@data}}%
8161             \noexpand\c@use{v}{\c@msd@series}{footnote}{\c@msd@series}{\c@msd@data}%
8162             \expandonce{\l@d@nums}{\ms@data@label}{\expandonce{\c@data}}%
8163             \reset{\c@msd@options}{iffullpage}%
8164           }%
8165           {}%
8166         \else%
8167           \numgdef{\add{\c@msd@c}{\c@R}}{\add{\c@msd@c}{\c@R}+\c@ne}%
8168           \ifcsdef{\c@msd@data}{\add{\c@msd@c}{\c@R}}{\c@data}{\c@R}%
8169             \let\c@cs{\c@data}{\c@msd@data}{\add{\c@msd@c}{\c@R}}{\c@data}{\c@R}%
8170             \edef\l@d@nums{%
8171               000% Start page = we don't print it
8172               \c@use{\c@msd@data}{\add{\c@msd@c}{\c@R}}{\linenumber}{\c@R}% Start line number
8173               000% Start subline number, for now, not used
8174               000% End page number, we don't print it
8175               \ifnumless{\c@use{\c@msd@data}{\add{\c@msd@c}{\c@R}}{\stopabslinenumber}}{\c@use
8176                 {\lastline}{\forpage}{\thepage}{\c@num}}{%
8177                   \c@use{\c@msd@data}{\add{\c@msd@c}{\c@R}}{\stoplinenumber}{\c@R}}%End line number
8178                   if in the same page
8179                   \c@use{\c@lastline}{\forpage}{\thepage}{\c@num}}%Otherwise, last
8180                   number of the page

```

```

8178   |%
8179   000|% End sub line number, for now, not used
8180   \edfont@info%Font
8181   }%
8182   \@msd@options@fullpagefalse%
8183   \if@firstlineofpageR%
8184     \unless\if@msdata@insertedfrompreviouspage%
8185       \ifnumless{\csuse{@lastabsline@forpageR}{\the\page@numR}}{\csuse{@msdata@add@msd@c}{\stopabslinenumberR}+\@ne}%
8186         }%
8187         \numdef{\@tmp}{\add@msd@cR+\@ne}%
8188         \ifcsdef{@msdata@\@tmp @abslinenumberR}%
8189           \ifnumequal{\csuse{@msdata@\@tmp @abslinenumberR}}{\csuse{@lastabsline@forpageR}{\the\page@numR}}%
8190             }%
8191             \{@msd@options@fullpagetrue}%
8192             }%
8193             \{@msd@options@fullpagetrue}%
8194             }%
8195             }%
8196             \fi%
8197             \fi%
8198             \listxadd{@msdata@list}%
8199               \{@msd@options@iffullpage}%
8200               \ifluatex%
8201                 \csxdef{footnote@luatextextdir}{\the\textdir}%
8202                 \csxdef{footnote@luatexpardir}{\the\pardir}%
8203                 \fi%
8204                 \csdef{@this@crossref@start}{\add@msd@cR:start:msdata}%
8205                 \csdef{@this@crossref@end}{\add@msd@cR:end:msdata}%
8206                 \noexpand\csuse{v{@msdata@series footnote}{\@msdata@series}{\{ \expandonce{l@d@nums}{\msdata@label}{\expandonce{@data}}\}}%
8207                   \reset@msd@options@iffullpage}%
8208                   }%
8209                   }%
8210                   }%
8211                   \fi%
8212                   \egroup%
8213                   }%
8214                   %

```

\if@msdata@insertedfrompreviouspage The `\if@msdata@insertedfrompreviouspage` boolean is set to TRUE if `reledmac` automatically inserts data from previous page in the first line of a page.

```

8215   \newif\if@msdata@insertedfrompreviouspage%
8216   %

```

\add@msdata@firstlineofpage `\add@msdata@firstlineofpage` is called at the first line of every page. It inserts manuscript data which start on one of the previous pages and continue on this page.

```

8217 \newcommand{\add@msdata@firstlineofpage}{%
8218   \bgroup%
8219   \normalfont%
8220   \unless\ifledRcol@%
8221   \ifcsdef{@msdata@\add@msd@c @data}{%
8222     \ifnumless{\the\absline@num-\@ne}{\csuse{@msdata@\add@msd@c
8223       @stopabslinenumber}}{%
8224       {%
8225         \global\@msdata@insertedfrompreviouspagetrue%
8226         \letcs{\@data}{@msdata@\add@msd@c @data}%
8227         \edef\l@d@nums{%
8228           000!% Start page = we don't print it
8229           \numexpr\the\line@num+\@ne\relax% Start line number = first line
8230             of the page. As \add@msdata@firstlineofpage is called before line number
8231             has been incremented, we increment it for printing
8232             000!% Start subline number, for now, not used
8233             000!% End page number, we don't print it
8234             \ifnumless{\csuse{@msdata@\add@msd@c @stopabslinenumber}}{\csuse{
8235               @lastabsline@forpage@\the\page@num}}{%
8236               \csuse{@msdata@\add@msd@c @stoplinenumber}}%End line number if
8237               in the same page
8238               \csuse{@lastline@forpage@\the\page@num}}%Otherwise, last
8239               number of the page
8240               !%
8241               000!% End sub line number, for now, not used
8242               \edfont@info%Font
8243               }%
8244               \@msd@options@fullpagefalse%
8245               \ifnumless{\csuse{@lastabsline@forpage@\the\page@num}}{\csuse{
8246                 @msdata@\add@msd@c @stopabslinenumber}+\@ne}{%We will test if the ms data is
8247                 for the full page
8248                 {%
8249                   \numdef{\@tmp}{\add@msd@c+\@ne}%
8250                   \ifcsdef{@msdata@\@tmp @abslinenumber}{%
8251                     \ifnumequal{\csuse{@msdata@\@tmp @abslinenumber}}{\csuse{
8252                       @lastabsline@forpage@\the\page@num}}{%
8253                         {}%
8254                         {\@msd@options@fullpagetrue}%
8255                         }%
8256                         {\@msd@options@fullpagetrue}%
8257                         }%
8258                         {}%
8259                         \listxadd{@msdata@list}{%
8260                           \@msd@options@iffullpage%
8261                           \ifluatex%
8262                             \csxdef{footnote@luatextextdir}{\the\textrdir}%
8263                             \csxdef{footnote@luatexpardir}{\the\pardir}%
8264                           \fi%
8265                           \csdef{@this@crossref@start}{\add@msd@c:start:msdata}%
8266                           \csdef{@this@crossref@end}{\add@msd@c:end:msdata}%
8267                         }
8268                       }
8269                     }
8270                   }
8271                 }
8272               }
8273             }
8274           }
8275         }
8276       }
8277     }
8278   }
8279 }
```

```

8258     \noexpand\csuse{v@\msdata@series footnote}{\@msdata@series}{{\
8259     expandonce\l@d@nums}{\ms@data@label}{\expandonce\data}}%  

8260         \reset@msd@options@iffullpage%  

8261             }%  

8262             }%  

8263             {\global\@msdata@insertedfrompreviouspagefalse}%  

8264 }{}%  

8265 \else%  

8266     \ifcsdef{\msdata@add@msd@cR \dataR}{%  

8267         \ifnumless{\the\absline@numR-\@ne}{\csuse{\msdata@add@msd@cR  

8268             @stopabslinenumberR}}%  

8269             }%  

8270             \global\@msdata@insertedfrompreviouspagetrue%  

8271             \letcs{\data}{\msdata@add@msd@cR \dataR}%  

8272             \edef\l@d@nums{%
8273                 000}% Start page = we don't print it  

8274             \numexpr\the\line@numR+\@ne\relax}% Start line number = first  

8275             line of the page. As \add@msdata@firstlineofpage is called before line  

8276             number has been incremented, we increment it for printing  

8277             000}% Start subline number, for now, not used  

8278             000}% End page number, we don't print it  

8279             \ifnumless{\csuse{\msdata@add@msd@cR @stopabslinenumberR}}{\  

8280                 csuse{@lastline@forpageR@\the\page@numR}}%  

8281                 \csuse{\msdata@add@msd@cR @stoplinenumberR}}%End line number  

8282             if in the same page  

8283                 \csuse{@lastline@forpageR@\the\page@numR}}%Otherwise, last  

8284             number of the page  

8285             }%  

8286             000}% End sub line number, for now, not used  

8287             \edfont@info%Font  

8288             }%  

8289             \@msd@options@fullpagefalse%  

8290             \ifnumless{\csuse{@lastabsline@forpageR@\the\page@numR}}{\  

8291                 csdata@add@msd@cR @stopabslinenumberR}+\@ne}{%  

8292                 }%  

8293                 \numdef{\@tmp}{\add@msd@cR+\@ne}%  

8294                 \ifcsdef{\msdata@tmp @abslinenumberR}{%  

8295                     \ifnumequal{\csuse{\msdata@tmp @abslinenumberR}}{\  

8296                         csuse{@lastabsline@forpageR@\the\page@numR}}%  

8297                         }%  

8298                         {\@msd@options@fullpagetrue}%  

8299                         }%  

8300                         {\@msd@options@fullpagetrue}%  

8301                         }%  

8302                         }%  

8303                         \listxadd{\msdata@list}{%  

8304                             \@msd@options@iffullpage%  

8305                             \ifluatex%  

8306                                 \csxdef{footnote@luatextextdir}{\the\textrdir}%  

8307                                 \csxdef{footnote@luatexpardir}{\the\pardir}%

```

```

8299     \fi%
8300     \csdef{@this@crossref@start}{\add@msd@cR:start:msdata}%
8301     \csdef{@this@crossref@end}{\add@msd@cR:end:msdata}%
8302     \noexpand\csuse{v\@msdata@series footnote}{\@msdata@series}{\{%
8303       \expandonce\l@d@nums}{\ms@data@label}\{\expandonce\@data}\}%
8304       \reset@msd@options@iffullpage}%
8305   }%
8306   {\global\@msdata@insertedfrompreviouspagefalse}%
8307 }{}%
8308 \fi%
8309 \egroup%
8310 }%
8311 %

```

XXX.6 Inserting footnote

Just before inserting standard insert (familiar and critical footnotes, sidenotes), we call `\insert@msdata` to insert manuscripts data's footnotes.

```

\insert@msdata12 \newcommand{\insert@msdata}{%
8313   \def\do##1{##1}%
8314   \dolistloop{\@msdata@list}%
8315   \global\let\@msdata@list\relax%
8316 }%
8317 %

```

XXX.7 Other

`\@msd@options@iffullpage` `\@msd@options@iffullpage` sets some options if the manuscripts data are for all the page. `\reset@msd@options@iffullpage` resets them after the footnote. `\if@msd@options@fullpage` is switch to true in `add@msdata@firstlineofpage` if these option must be inserted.

```

8318 \newif\if@msd@options@fullpage%
8319 \newcommand{\@msd@options@iffullpage}[0]{%
8320   \if@msd@options@fullpage%
8321     \noexpand\toggletrue{nonum@}%
8322     \ifdefvoid{\ms@data@label}{%
8323       {\noexpand\toggletrue{nosep@}}%
8324     }{}%
8325   \fi%
8326 }%
8327 \newcommand{\reset@msd@options@iffullpage}[0]{%
8328   \noexpand\togglefalse{nonum@}%
8329   \noexpand\togglefalse{nosep@}%
8330 }%
8331 %

```

XXXI Arrays and tables

XXXI.1 Preamble: macro as environment

The following is borrowed, and renamed, from the `amsmath` package. See also the CTT thread ‘`eeq` and `amstex`’, 1995/08/31, started by Keith Reckdahl and ended definitively by David M. Jones.

Several of the [math] macros scan their body twice. This means we must collect all text in the body of an environment form before calling the macro.

`\@emptytoks` This is actually defined in the `amsgen` package.

```
8332 \newtoks\@emptytoks
8333 %
8334 %
```

The rest is from `amsmath`.

`\l@denvbody` A token register to contain the body.

```
8335 \newtoks\l@denvbody
8336 %
8337 %
```

`\addtol@denvbody` `\addtol@denvbody{arg}` adds `arg` to the token register `\l@denvbody`.

```
8338 \newcommand{\addtol@denvbody}[1]{%
8339   \global\l@denvbody\expandafter{\the\l@denvbody#1}}
8340 %
8341 %
```

`\l@dcollect@body` The macro `\l@dcollect@body` starts the scan for the `\end{<env>}` command of the current environment. It takes a macro name as argument. This macro is supposed to take the whole body of the environment as its argument. For example, given `cenv#1{...}` as a macro that processes #1, then the environment form, `\begin{cenv}` would call `\l@dcollect@body\cenv`.

```
8342 \newcommand{\l@dcollect@body}[1]{%
8343   \l@denvbody{\expandafter#1\expandafter{\the\l@denvbody}}%
8344   \edef\processl@denvbody{\the\l@denvbody\noexpand\end{@currenvir}}%
8345   \l@denvbody\@emptytoks \def\l@dbegin@stack{b}%
8346   \begingroup
8347     \expandafter\let\csname@currenvir\endcsname\l@dcollect@@body
8348     \edef\processl@denvbody{\expandafter\noexpand\csname@currenvir\
8349     endcsname}%
8350     \processl@denvbody%
8351   }%
8352 %
```

\l@dpush@begins When adding a piece of the current environment's contents to \l@denvbody, we scan it to check for additional \begin tokens, and add a 'b' to the stack for any that we find.

```
8353 \def\l@dpush@begins#1\begin#2{%
8354   \ifx\end#2\else b\expandafter\l@dpush@begins\fi}
8355 %
8356 %
```

\l@dcollect@@body \l@dcollect@@body takes two arguments: the first will consist of all text up to the next \end command, and the second will be the \end command's argument. If there are any extra \begin commands in the body text, a marker is pushed onto a stack by the \l@dpush@begins function. Empty state for this stack means we have reached the \end that matches our original \begin. Otherwise we need to include the \end and its argument in the material we are adding to the environment body accumulator.

```
8357 \def\l@dcollect@@body#1\end#2{%
8358   \edef\l@dbegin@stack{\l@dpush@begins#1\begin\end
8359     \expandafter\@gobble\l@dbegin@stack}%
8360   \ifx\@empty\l@dbegin@stack
8361     \endgroup
8362     \@checkend{#2}%
8363     \addtol@denvbody{#1}%
8364   \else
8365     \addtol@denvbody{#1\end{#2}}%
8366   \fi
8367   \processl@denvbody % A little tricky! Note the grouping
8368 }
8369 %
8370 %
```

There was a question on CTT about how to use \collect@body for a macro taking an argument. The following is part of that thread.

From: Heiko Oberdiek <oberdiek@uni-freiburg.de>
 Newsgroups: comp.text.tex
 Subject: Re: Using \collect@body with commands that take >1 argument
 Date: Fri, 08 Aug 2003 09:03:20 +0200

eed132@psu.edu (Evan) wrote:
 > I'm trying to make a new Latex environment that acts like the>
 \colorbox command that is part of the color package. I looked through
 > the FAQ and ran across this bit about using the \collect@body command
 > that is part of AMSLaTeX:
 > http://www.tex.ac.uk/cgi-bin/texfaq2html?label=cmdasenv
 >
 > It almost works. If I do something like the following:
 > \newcommand{\redbox}[1]{\colorbox{red}{#1}}
 >
 > \makeatletter
 > \newenvironment{redbox}{\collect@body \redbox{}}

You will get an error message: Command \redbox already defined.
 Thus you must rename either the command \redbox or the environment name.

```
> \begin{coloredbox}{blue}
>     Yadda yadda yadda... this is on a blue background...
> \end{coloredbox}
> and can't figure out how to make the \collect@body take this.

> \collect@body \colorbox{red}
> \collect@body {\colorbox{red}}
```

The argument of \collect@body has to be one token exactly.

```
\documentclass{article}
\usepackage{color}
\usepackage{amsmath}

\newcommand{\redbox}[1]{\colorbox{red}{#1}}
\makeatletter
\newenvironment{coloredbox}[1]{%
  \def\next@\{\colorbox{#1}\}%
  \collect@body\next@
}{}

% ignore spaces at begin and end of environment
\newenvironment{coloredboxII}[1]{%
  \def\next@\{mycoloredbox{#1}\}%
  \collect@body\next@
}{}

\newcommand{\mycoloredbox}[2]{%
  \colorbox{#1}{\ignorespaces#2\unskip}%
}

% support of optional color model argument
\newcommand\coloredboxIII\endcsname{%
\def\coloredboxIII#1{%
  \colorbox{#1}%
}
\def\@coloredboxIII#1{%
}
\def\coloredboxIII#1#2{%
  \def\next@\{mycoloredboxIII{#1}{#2}\}%
  \collect@body\next@
}
\newcommand{\mycoloredboxIII}[3]{%
  \colorbox{#1}{#2}{\ignorespaces#3\unskip}%
}
\makeatother
```

```

\begin{document}
  Black text before
  \begin{coloredbox}{blue}
    Hello World
  \end{coloredbox}
  Black text after

  Black text before
  \begin{coloredboxII}{blue}
    Hello World
  \end{coloredboxII}
  Black text after

  Black text before
  \begin{coloredboxIII}[rgb]{0,0,1}
    Hello World
  \end{coloredboxIII}
  Black text after

\end{document}

Yours sincerely
Heiko <oberdiek@uni-freiburg.de>

```

XXXI.2 Tabular environments

This is based on the work by Herbert Breger in developing `tabmac.tex`.

The original `tabmac.tex` file was void of comments or any explanatory text other than the above notice. The algorithm is Breger's. Peter Wilson have made some cosmetic changes to the original code and reimplemented some things so they are more LaTeX-like. All the commentary are from Peter Wilson, as are any mistake or errors.

However, Maïeul Rouquette has modified code in order to add new features of `eledmac` and `reledmac`.

XXXI.2.1 Disabling and restoring commands

`\l@dtabnoexpands` More no expansion for critical and familiar footnotes in tabular environment.

```

8371 \newcommand*\l@dtabnoexpands{%
8372   \let\rtab=0%
8373   \let\ctab=0%
8374   \let\ltab=0%
8375   \let\rtabtext=0%
8376   \let\ltabtext=0%
8377   \let\ctabtext=0%
8378   \let\edbeforetab=0%
8379   \let\edaftertab=0%
8380   \let\edatleft=0%

```

```

8381   \let\edatright=0%
8382   \let\edvertline=0%
8383   \let\edvertdots=0%
8384   \let\edrowfill=0%
8385 }
8386
8387 %

```

`\disable@familiarnotes` Macros to disable and restore familiar notes, to prevent them from printing multiple times in edtabularx and edarrayx environments.

```

8388 \newcommand{\disable@familiarnotes}{%
8389   \unless\ifnofamiliar@
8390     \def\do##1{%
8391       \csletcs{footnote@@##1}{footnote##1}%
8392       \expandafter\renewcommand \csname footnote##1\endcsname[1]{%
8393         \protected@csxdef{@thefnmark##1}{\csuse{thefootnote##1}}%
8394         \csuse{@footnotemark##1}%
8395       }%
8396     }%
8397     \dolistloop{\@series}%
8398   \fi%
8399 }%
8400 \newcommand{\restore@familiarnotes}{%
8401   \unless\ifnofamiliar@
8402     \def\do##1{%
8403       \csletcs{footnote##1}{footnote@@##1}%
8404     }%
8405     \dolistloop{\@series}%
8406   \fi%
8407 }%
8408
8409 %

```

`\disable@sidenotes` The same for sidenotes.

```

8410 \newcommand{\disable@sidenotes}{%
8411   \let\@oledrightnote\ledrightnote%
8412   \let\@oledleftnote\ledleftnote%
8413   \let\@oledsidenote\ledsidenote%
8414   \let\ledrightnote@gobble%
8415   \let\ledleftnote@gobble%
8416   \let\ledsidenote@gobble%
8417 }%
8418 \newcommand{\restore@sidenotes}{%
8419   \let\ledrightnote\@oledrightnote%
8420   \let\ledleftnote\@oledleftnote%
8421   \let\ledsidenote\@oledsidenote%
8422 }%
8423 %

```

\disable@endnotes The same for endnotes.

```

\restore@endnotes
8424 \newcommand{\disable@endnotes}{%
8425   \unless\ifnoend@%
8426   \def\do##1{%
8427     \csletcs{##1@@endnote}{##1endnote}%
8428     \expandafter\renewcommand \csname ##1endnote\endcsname[1]{}%
8429   }%
8430   \dolistloop{\@series}%
8431   \fi%
8432 }%
8433 \newcommand{\restore@endnotes}{%
8434   \unless\ifnofamiliar@%
8435   \def\do##1{%
8436     \csletcs{##1endnote}{##1@@endnote}%
8437   }%
8438   \dolistloop{\@series}%
8439   \fi%
8440 }%
8441 %

```

\disable@notes Disable/restore side, familiar and end notes.

```

\restore@notes
8442 \newcommand{\disable@notes}{%
8443   \disable@sidenotes%
8444   \disable@familiarnotes%
8445   \disable@endnotes%
8446 }%
8447 \newcommand{\restore@notes}{%
8448   \restore@sidenotes%
8449   \restore@familiarnotes%
8450   \restore@endnotes%
8451 }%
8452 %

```

\EDTEXT We need to be able to modify the \edtext macros and also restore their original definitions.

```

8453 \let\EDTEXT=\edtext
8454 \newcommand{\xedtext}[2]{\EDTEXT{#1}{#2}}
8455 %

```

\EDLABEL We need to be able to modify and restore the \edlabel macro.

```

\xedlabel
8456 \let\EDLABEL=\edlabel
8457 \newcommand*\xedlabel[1]{\EDLABEL{#1}}
8458 %

```

\xedindex Macros supporting modification and restoration of \edindex.
\nullindex

```

8459 \AtBeginDocument{\let\xedindex\édindex}%
8460 \newcommand{\nulledindex}[2][\jobname]{\@bsphack\@esphack}
8461 %
8462 %

```

\@line@@num Macro supporting restoration of \linenum.

```

8463 \let\@line@@num=\linenum
8464 %

```

\l@dgobblearg \l@dgobbleoptarg[⟨arg⟩]{⟨arg⟩} replaces these two arguments (first is optional) by \relax.

```

8465 \newcommand*{\l@dgobbleoptarg}[2][]{\relax}%
8466 %
8467 %

```

```

\Relax68 \let\Relax=\relax
\next69 \let\next=\next
8470 %
8471 %

```

\l@dmforedtext Modify and restore various macros for when \edtext is used.

```

\l@restoreforedtext
8472 \newcommand{\l@dmforedtext}{%
8473   \let\edtext\relax
8474   \def\do##1{\global\csletcs{##1footnote}{\l@dgobbleoptarg}}%
8475   \dolistloop{\@series}%
8476   \let\edindex\nulledindex
8477   \let\linenum\@gobble}
8478 \newcommand{\l@restoreforedtext}{%
8479   \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}%
8480   \dolistloop{\@series}%
8481   \let\edindex\xedindex}
8482 %

```

\l@dnnullfills Nullify and restore some column fillers, etc.

```

\l@restorefills
8483 \newcommand{\l@dnnullfills}{%
8484   \def\edlabel##1{}%
8485   \def\edrowfill##1##2##3{}%
8486 }
8487 \newcommand{\l@restorefills}{%
8488   \def\edrowfill##1##2##3{\@EDROWFILL{##1}{##2}{##3}}%
8489 }
8490 %
8491 %

```

`\letsforverteilen` Gathers some lets and other code that is common to the `*verteilen*` macros.

```

8492 \newcommand{\letsforverteilen}{%
8493   \let\edtext\xedtext
8494   \let\edindex\xídex
8495   \def\do##1{\global\csletcs{##1footnote}{##1@footnote}}
8496   \dolistloop{@series}%
8497   \let\linenum@line@@num
8498   \hilfsskip=\l@dcolwidth%
8499   \advance\hilfsskip by -\wd\hilfsbox
8500   \def\edlabel##1{\xídelabel{##1}}}
8501 %
8502 %

```

`\disablel@tabfeet` Declarations for using or using `\edtext` inside tabulars. The default at this point is for
`\enablel@tabfeet` `\edtext`.

```

8503 \newcommand\disablel@tabfeet{\l@dmodforedtext}%
8504 \newcommand\enablel@tabfeet{\l@drestoreforedtext}%
8505 %

```

XXXI.2.2 Counters, boxes and lengths

`\l@dampcount` `\l@dampcount` is a counter for the & column dividers and `\l@dcolcount` is a counter
`\l@dcolcount` for the columns.

```

8506 \newcount\l@dampcount
8507   \l@dampcount=1\relax
8508 \newcount\l@dcolcount
8509   \l@dcolcount=0\relax
8510 %
8511 %

```

`\hilfsbox` Some (temporary) helper items.

```

8512 \newbox\hilfsbox
8513 \newskip\hilfsskip
8514 \newbox\Hilfsbox
8515 \newcount\hilfscount
8516 %
8517 %

```

30 columns should be adequate (compared to the original 60). These are the column widths. (Originally these were German spelled numbers e.g., `\eins`, `\zwei`, etc).

```

8518 \newdimen\dcoli
8519 \newdimen\dcolii
8520 \newdimen\dcoliii
8521 \newdimen\dcoliv
8522 \newdimen\dcolv

```

```

8523 \newdimen\dcollvi
8524 \newdimen\dcollvii
8525 \newdimen\dcollviii
8526 \newdimen\dcollix
8527 \newdimen\dcollx
8528 \newdimen\dcollxi
8529 \newdimen\dcollxii
8530 \newdimen\dcollxiii
8531 \newdimen\dcollxiv
8532 \newdimen\dcollxv
8533 \newdimen\dcollxvi
8534 \newdimen\dcollxvii
8535 \newdimen\dcollxviii
8536 \newdimen\dcollxix
8537 \newdimen\dcollxx
8538 \newdimen\dcollxxi
8539 \newdimen\dcollxxii
8540 \newdimen\dcollxxiii
8541 \newdimen\dcollxxiv
8542 \newdimen\dcollxxv
8543 \newdimen\dcollxxvi
8544 \newdimen\dcollxxvii
8545 \newdimen\dcollxxviii
8546 \newdimen\dcollxxix
8547 \newdimen\dcollxxx
8548 \newdimen\dcollerr % added for error handling
8549 %
8550 %

```

\l@dcollwidth This is a cunning way of storing the columnwidths indexed by the column number **\l@dcollcount**, like an array. (was \Dimenzuordnung)

```

8551 \newcommand{\l@dcollwidth}{\ifcase \the\l@dcollcount \dcoll %??
8552   \or \dcoll \or \dcollii \or \dcolliii
8553   \or \dcolliv \or \dcollv \or \dcollvi
8554   \or \dcollvii \or \dcollviii \or \dcollix \or \dcollx
8555   \or \dcollxi \or \dcollxii \or \dcollxiii
8556   \or \dcollxiv \or \dcollxv \or \dcollxvi
8557   \or \dcollxvii \or \dcollxviii \or \dcollxix \or \dcollxx
8558   \or \dcollxxi \or \dcollxxii \or \dcollxxiii
8559   \or \dcollxxiv \or \dcollxxv \or \dcollxxvi
8560   \or \dcollxxvii \or \dcollxxviii \or \dcollxxix \or \dcollxxx
8561   \else \dcollerr \fi}
8562 %
8563 %

```

\stepl@dcollcount This increments the column counter, and issues an error message if it is too large.

```

8564 \newcommand*{\stepl@dcollcount}{\advance\l@dcollcount\@ne
8565   \ifnum\l@dcollcount>30\relax

```

```

8566     \led@err@TooManyColumns
8567     \fi}
8568
8569 %

```

\l@dsetmaxcolwidth Sets the column width to the maximum value seen so far.

```

8570 \newcommand{\l@dsetmaxcolwidth}{%
8571   \ifdim\l@dcolwidth < \wd\hilfsbox
8572     \l@dcolwidth = \wd\hilfsbox
8573   \else \relax \fi}
8574
8575 %

```

\measuremcell Measure (recursively) the width required for a math cell.

```

8576 \def\measuremcell #1&{%
8577   \ifx #1\ \
8578     \ifnum\l@dcollcount=0\let\next\relax%
8579       \else\l@dcheckcols%
8580         \l@dcollcount=0%
8581         \let\next\measuremcell%
8582       \fi%
8583     \else\setbox\hilfsbox=\hbox{\$#1\$}%
8584       \step\l@dcollcount%
8585       \l@dsetmaxcolwidth%
8586       \let\next\measuremcell%
8587     \fi\next}
8588 %

```

\measuretcell Measure (recursively) the width required for a text cell.

```

8589 \def\measuretcell #1&{%
8590   \ifx #1\ \
8591     \ifnum\l@dcollcount=0\let\next\relax%
8592       \else\l@dcheckcols%
8593         \l@dcollcount=0%
8594         \let\next\measuretcell%
8595       \fi%
8596     \else\setbox\hilfsbox=\hbox{#1}%
8597       \step\l@dcollcount%
8598       \l@dsetmaxcolwidth%
8599       \let\next\measuretcell%
8600     \fi\next}
8601 %

```

\measuremrow Measure (recursively) the width required for a math row.

```

8602 \def\measuremrow #1\\{%
8603   \ifx #1\&\let\next\relax%

```

```

8604   \else\measuremcell #1&\&\\&%
8605     \let\NEXT\measuremrw%
8606   \fi\NEXT}
8607 %

```

\measuretrw Measure (recursively) the width required for a text row.

```

8608 \def\measuretrw #1\\{%
8609   \ifx #1\&\let\NEXT\relax%
8610   \else\measuretrcell #1&\&\\&%
8611     \let\NEXT\measuretrw%
8612   \fi\NEXT}
8613 %
8614 %

```

\edtabcolsep The length **\edtabcolsep** controls the distance between columns.

```

8615 \newskip\edtabcolsep
8616 \global\edtabcolsep=10pt
8617 %
8618 %

```

```

\variab19 \newcommand{\variab}{\relax}
8620 %
8621 %

```

\l@dcheckcols Check that the number of columns is consistent.

```

8622 \newcommand*\l@dcheckcols{%
8623   \ifnum\l@dcolcount=1\relax
8624   \else
8625     \ifnum\l@dampcount=1\relax
8626     \else
8627       \ifnum\l@dcollcount=\l@dampcount\relax
8628       \else
8629         \l@d@err@UnequalColumns
8630       \fi
8631     \fi
8632     \l@dampcount=\l@dcollcount
8633   \fi}
8634 %
8635 %

```

\edfillldimen A length.

```

8636 \newdimen\edfillldimen
8637 \edfillldimen=0pt
8638 %
8639 %

```

`\c@addcolcount` A counter to hold the number of a column. We use a roman number so that we can grab the column dimension from `\dcol`. We do not use the `\romannumeral` L^AT_EX command, because some packages, like `babel` can override it in some specific cases (Greek, for example).

```
8640 \newcounter{addcolcount}
8641   \renewcommand{\theaddcolcount}{\romannumeral \c@addcolcount}
8642 %
```

XXXI.2.3 Tabular typesetting

`\setmcellright` Typeset (recursively) cells of display math right justified.

```
8643 \def\setmcellright #1&{\def\edlabel##1{}%
8644   \let\edindex\nulledindex
8645   \ifx #1\relax\ifnum\l@dcolcount=0%\removelastskip
8646     \let\Next\relax%
8647   \else\l@dcolcount=0%
8648     \let\Next=\setmcellright%
8649   \fi%
8650 \else%
8651   \disablel@tabfeet%
8652   \stepl@dcolcount%
8653   \disable@notes%
8654   \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
8655   \restore@notes%
8656   \letsforverteilen%
8657   \hskip\hilfsskip$\displaystyle{#1}$%
8658   \hskip\edtabcolsep%
8659   \let\Next=\setmcellright%
8660 \fi\Next}
8661 %
8662 %
```

`\settcellright` Typeset (recursively) cells of text right justified.

```
8663 \def\settcellright #1&{\def\edlabel##1{}%
8664   \let\edindex\nulledindex
8665   \ifx #1\relax\ifnum\l@dcolcount=0%\removelastskip
8666     \let\Next\relax%
8667   \else\l@dcolcount=0%
8668     \let\Next=\settcellright%
8669   \fi%
8670 \else%
8671   \disablel@tabfeet%
8672   \stepl@dcolcount%
8673   \disable@notes%
8674   \setbox\hilfsbox=\hbox{#1}%
8675   \restore@notes%
8676   \letsforverteilen%
8677   \hskip\hilfsskip#1%
```

```

8678     \hskip\edtabcolsep%
8679     \let\Next=\settcellright%
8680   \fi\Next}
8681 %

```

\setmcellleft Typeset (recursively) cells of display math left justified.

```

8682 \def\setmcellleft #1{\def\edlabel##1{}%
8683   \let\edindex\nulledindex
8684   \ifx #1\ \
8685     \ifnum\l@dcolcount=0 \let\Next\relax%
8686       \else\l@dcolcount=0%
8687         \let\Next=\setmcellleft%
8688       \fi%
8689     \else \disablel@dtabfeet%
8690       \stepl@dcolcount%
8691       \disable@notes%
8692       \setbox\hilfsbox=\hbox{\$displaystyle{#1}\$}%
8693       \restore@notes%
8694       \letsforverteilen%
8695       \$displaystyle{#1}\$ \hskip\hilfsskip\hskip\edtabcolsep%
8696       \let\Next=\setmcellleft%
8697     \fi\Next}
8698 %

```

\settcellleft Typeset (recursively) cells of text left justified.

```

8699 \def\settcellleft #1{\def\edlabel##1{}%
8700   \let\edindex\nulledindex
8701   \ifx #1\ \
8702     \ifnum\l@dcolcount=0 \let\Next\relax%
8703       \else\l@dcolcount=0%
8704         \let\Next=\settcellleft%
8705       \fi%
8706     \else \disablel@dtabfeet%
8707       \stepl@dcolcount%
8708       \disable@notes%
8709       \setbox\hilfsbox=\hbox{#1}%
8710       \restore@notes%
8711       \letsforverteilen%
8712       #1\hskip\hilfsskip\hskip\edtabcolsep%
8713       \let\Next=\settcellleft%
8714 \fi\Next}

```

\setmcellcenter Typeset (recursively) cells of display math centered.

```

8715 \def\setmcellcenter #1{\def\edlabel##1{}%
8716   \let\edindex\nulledindex
8717   \ifx #1\ \
8718     \ifnum\l@dcolcount=0\let\Next\relax%

```

```

8719          \let\Next=\setmcellcenter%
8720          \fi%
8721      \else  \disable@dtabfeet%
8722          \stepl@dcolcount%
8723          \disable@notes%
8724          \setbox\hilfsbox=\hbox{$\displaystyle{#1}$}%
8725          \restore@notes%
8726          \letsforverteilen%
8727          \hskip 0.5\hifskip$\displaystyle{#1}\$ \hskip 0.5\hifskip%
8728          \hskip\edtabcolsep%
8729          \let\Next=\setmcellcenter%
8730      \fi\Next}
8731 %
8732 %

```

\settcellcenter Typeset (recursively) cells of text centered.

```

8733 \def\settcellcenter #1&{\def\edlabel##1{}%
8734     \let\edindex\nulledindex
8735     \ifx #1\` \ ifnum\l@dcolcount=0 \let\Next\relax%
8736     \else\l@dcolcount=0%
8737         \let\Next=\settcellcenter%
8738         \fi%
8739     \else  \disable@dtabfeet%
8740         \stepl@dcolcount%
8741         \disable@notes%
8742         \setbox\hilfsbox=\hbox{#1}%
8743         \restore@notes%
8744         \letsforverteilen%
8745         \hskip 0.5\hifskip #1\hskip 0.5\hifskip%
8746         \hskip\edtabcolsep%
8747         \let\Next=\settcellcenter%
8748     \fi\Next}
8749 %
8750 %

```

\NEXT₅₁ \let\NEXT=\relax

```

8752 %
8753 %

```

\setmrowright Typeset (recursively) rows of right justified math.

```

8754 \def\setmrowright #1\`{%
8755     \ifx #1& \let\NEXT\relax
8756     \else \centerline{\setmcellright #1&\&\&\&}%
8757     \let\NEXT=\setmrowright
8758     \fi\NEXT}
8759 %

```

\settowright Typeset (recursively) rows of right justified text.

```

8760 \def\settowright #1\\{%
8761   \ifx #1& \let\next\relax
8762   \else \centerline{\setcellright #1&\&\&}%
8763     \let\next=\settowright
8764   \fi\next}
8765 %
8766 %

```

\setmrowleft Typeset (recursively) rows of left justified math.

```

8767 \def\setmrowleft #1\\{%
8768   \ifx #1& \let\next\relax
8769   \else \centerline{\setmcellleft #1&\&\&}%
8770     \let\next=\setmrowleft
8771   \fi\next}
8772 %

```

\settowleft Typeset (recursively) rows of left justified text.

```

8773 \def\settowleft #1\\{%
8774   \ifx #1& \let\next\relax
8775   \else \centerline{\setcellleft #1&\&\&}%
8776     \let\next=\settowleft
8777   \fi\next}
8778 %
8779 %

```

\setmrowcenter Typeset (recursively) rows of centered math.

```

8780 \def\setmrowcenter #1\\{%
8781   \ifx #1& \let\next\relax%
8782   \else \centerline{\setmcellcenter #1&\&\&}%
8783     \let\next=\setmrowcenter
8784   \fi\next}
8785 %

```

\settowcenter Typeset (recursively) rows of centered text.

```

8786 \def\settowcenter #1\\{%
8787   \ifx #1& \let\next\relax
8788   \else \centerline{\setcellcenter #1&\&\&}%
8789     \let\next=\settowcenter
8790   \fi\next}
8791 %
8792 %

```

```

\nullsetzen93 \newcommand{\nullsetzen}{%
8794     \step1@dcolcount%
8795     \l@dcolwidth=0pt%
8796     \ifnum\l@dcolcount=30\let\next\relax%
8797         \l@dcolcount=0\relax
8798     \else\let\next\nullsetzen%
8799     \fi\next}
8800
8801 %

```

\edatleft \edatleft[$\langle math \rangle$] { $\langle symbol \rangle$ } { $\langle len \rangle$ }. Left $\langle symbol \rangle$, 2 $\langle len \rangle$ high with prepended $\langle math \rangle$ vertically centered.

```

8802 \newcommand{\edatleft}[3][\emptyset]{%
8803     \ifx#1\emptyset
8804         \vbox to 10pt{\vss\hbox{$\left.\rule{0pt}{#3}\right.$}%
8805             depth 0pt \right. \$\hss}\vfil}
8806     \else
8807         \vbox to 4pt{\vss\hbox{$\left.\rule{#1pt}{#3}\right.$}%
8808             depth 0pt \right. \$}\vfil}
8809     \fi}
8810 %

```

\edatright \edatright[$\langle math \rangle$] { $\langle symbol \rangle$ } { $\langle len \rangle$ }. Right $\langle symbol \rangle$, 2 $\langle len \rangle$ high with appended $\langle math \rangle$ vertically centered.

```

8811 \newcommand{\edatright}[3][\emptyset]{%
8812     \ifx#1\emptyset
8813         \vbox to 10pt{\vss\hbox{$\left.\rule{0pt}{#3}\right.$}%
8814             depth 0pt \right. \$\hss}\vfil}
8815     \else
8816         \vbox to 4pt{\vss\hbox{$\left.\rule{#1pt}{#3}\right.$}%
8817             depth 0pt \right. \$1}\vfil}
8818     \fi}
8819
8820 %

```

\edvertline \edvertline{ $\langle len \rangle$ } vertical line $\langle len \rangle$ high.

```

8821 \newcommand{\edvertline}[1]{\vbox to 8pt{\vss\hbox{\vrule height #1}\vfil}}
8822
8823 %

```

\edvertdots \edvertdots{ $\langle len \rangle$ } vertical dotted line $\langle len \rangle$ high.

```

8824 \newcommand{\edvertdots}[1]{\vbox to 1pt{\vss\vbox to #1{%
8825     \cleaders\hbox{$\cdot$\kern-.1em}\vbox to 0.5em{ }\$}\vfil}}
8826
8827 %

```

`\l@dtabaddcols \l@dtabaddcols{\langle startcol\rangle}{\langle endcol\rangle}` adds the widths of the columns $\langle startcol\rangle$ through $\langle endcol\rangle$ to `\edfilldimen`. It is a L^AT_EX style reimplementation of the original `\@add@`.

```

8828 \newcommand{\l@dtabaddcols}[2]{%
8829   \l@dcheckstartend{#1}{#2}%
8830   \ifl@dstartendok
8831     \setcounter{addcolcount}{#1}%
8832     \@whilenum {\value{addcolcount}<#2}\relax \do
8833       \advance\edfilldimen by \the\csname dcol\theaddcolcount\endcsname
8834       \advance\edfilldimen by \edtabcolsep
8835       \stepcounter{addcolcount}%
8836     \advance\edfilldimen by \the\csname dcol\theaddcolcount\endcsname
8837   \fi
8838 }
8839 %
8840 %

```

`\ifl@dstartendok \l@dcheckstartend{\langle startcol\rangle}{\langle endcol\rangle}` checks that the values of $\langle startcol\rangle$ and $\langle endcol\rangle$ are sensible. If they are then `\ifl@dstartendok` is set TRUE, otherwise it is set FALSE.

```

8841 \newif\ifl@dstartendok
8842 \newcommand{\l@dcheckstartend}[2]{%
8843   \l@dstartendoktrue
8844   \ifnum #1<\@ne
8845     \l@dstartendokfalse
8846     \led@err@LowStartColumn
8847   \fi
8848   \ifnum #2>30\relax
8849     \l@dstartendokfalse
8850     \led@err@HighEndColumn
8851   \fi
8852   \ifnum #1>#2\relax
8853     \l@dstartendokfalse
8854     \led@err@ReverseColumns
8855   \fi
8856 }
8857 %
8858 %

```

`\edrowfill \edrowfill{\langle startcol\rangle}{\langle endcol\rangle}fill` fills columns $\langle startcol\rangle$ to $\langle endcol\rangle$ inclusive with `\@edrowfill@` $\langle fill\rangle$ (e.g. `\hrulefill`, `\upbracefill`). This is a L^AT_EX style reimplementation and generalization of the original `\waklam`, `\Waklam`, `\waklamec`, `\wastricht` and `\wapunktel` macros.

```

8859 \newcommand*\edrowfill[3]{%
8860   \l@dtabaddcols{#1}{#2}%
8861   \hb@xt@ \the\l@dcolwidth{\hb@xt@ \the\edfilldimen{#3}\hss}%
8862   \let\@edrowfill@\edrowfill
8863   \def\@EDROWFILL@#1#2#3{\@edrowfill@{#1}{#2}{#3}}%

```

```
8864 %
8865 %
```

\edbeforetab The macro `\edbeforetab{text}{{math}}` puts *text* at the left margin before array cell entry *math*. Conversely, the macro `\edaftertab{math}{{text}}` puts *text* at the right margin after array cell entry *math*. `\edbeforetab` should be in the first column and `\edaftertab` in the last column. The following macros support these.

\leftltab `\leftltab{text}` for `\edbeforetab` in `\ltab`.

```
8866 \newcommand{\leftltab}[1]{%
8867   \hb@xt@z@{\vbox{\edtabindent%
8868     \moveleft\Hilfsskip\hbox{\#1}\hss}}%
8869 %
8870 %
```

\leftrrtab `\leftrrtab{text}{{math}}` for `\edbeforetab` in `\rtab`.

```
8871 \newcommand{\leftrrtab}[2]{%
8872   #2\hb@xt@z@{\vbox{\edtabindent%
8873     \advance\Hilfsskip by\dcoli%
8874     \moveleft\Hilfsskip\hbox{\#1}\hss}}%
8875 %
8876 %
```

\leftctab `\leftctab{text}{{math}}` for `\edbeforetab` in `\ctab`.

```
8877 \newcommand{\leftctab}[2]{%
8878   \hb@xt@z@{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
8879     \advance\Hilfsskip by 0.5\dcoli%
8880     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
8881       \disablel@tabfeet$\displaystyle{##2}$%
8882       \advance\Hilfsskip by -0.5\wd\hilfsbox%
8883       \moveleft\Hilfsskip\hbox{\#1}\hss}%
8884     #2}%
8885 %
8886 %
```

\rightctab `\rightctab{{math}}{text}` for `\edaftertab` in `\ctab`.

```
8887 \newcommand{\rightctab}[2]{%
8888   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
8889   \disablel@tabfeet#2}\l@dampcount=\l@dcolcount%
8890   #1\hb@xt@z@{\vbox{\edtabindent\l@dcolcount=\l@dampcount%
8891     \advance\Hilfsskip by 0.5\l@dcolwidth%
8892     \advance\Hilfsskip by -\wd\hilfsbox%
8893     \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
8894       \disablel@tabfeet$\displaystyle{##1}$%
8895       \advance\Hilfsskip by -0.5\wd\hilfsbox%
```

```

8896   \advance\Hilfsskip by \edtabcolsep%
8897   \moveright\Hilfsskip\hbox{ #2}\}\hss}%
8898 }
8899 %
8900 %

```

\rightltab \rightltab{\langle math\rangle}{\langle text\rangle} for \edaftertab in \ltab.

```

8901 \newcommand{\rightltab}[2]{%
8902   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
8903   \disablel@dtabfeet#2}\l@dampcount=\l@dcollcount%
8904   #1\hb@xt@z@\vbox{\edtabindent\l@dcollcount=\l@dampcount%
8905   \advance\Hilfsskip by\l@dcollwidth%
8906   \advance\Hilfsskip by-\wd\hilfsbox%
8907   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
8908   \disablel@dtabfeet$\displaystyle{#1}$}%
8909   \advance\Hilfsskip by-\wd\hilfsbox%
8910   \advance\Hilfsskip by\edtabcolsep%
8911   \moveright\Hilfsskip\hbox{ #2}\}\hss}%
8912 }
8913 %
8914 %

```

\rightrtab \rightrtab{\langle math\rangle}{\langle text\rangle} for \edaftertab in \rtab.

```

8915 \newcommand{\rightrtab}[2]{%
8916   \setbox\hilfsbox=\hbox{\def\edlabel##1{}%
8917   \disablel@dtabfeet#2}%
8918   #1\hb@xt@z@\vbox{\edtabindent%
8919   \advance\Hilfsskip by-\wd\hilfsbox%
8920   \advance\Hilfsskip by\edtabcolsep%
8921   \moveright\Hilfsskip\hbox{ #2}\}\hss}%
8922 }
8923 %
8924 %

```

\rtab \rtab{\langle body\rangle} typesets \langle body\rangle as an array with the entries right justified.

\edbforetab The process is first to measure the \langle body\rangle to get the column widths, and then in a \edaftertab second pass to typeset the body.

```

8925 \newcommand{\rtab}[1]{%
8926   \l@dnnullfills
8927   \def\edbforetab##1##2{\leftrtab{##1}{##2}%
8928   \def\edaftertab##1##2{\rightrtab{##1}{##2}%
8929   \measurebody{#1}%
8930   \l@drestorefills
8931   \variab
8932   \setmrowright #1\&\%
8933   \enablel@dtabfeet}
8934 %
8935 %

```

\measurembody `\measurembody{\langle body \rangle}` measures the array `\langle body \rangle`.

```

8936 \newcommand{\measurembody}[1]{%
8937   \disable@dtabfeet%
8938   \l@dcollcount=0%
8939   \nullsetzen%
8940   \l@dcollcount=0%
8941   \measuremrow #1\\&\\%
8942   \global\l@dampcount=1}
8943 %
8944 %

```

\ratabtext `\ratabtext{\langle body \rangle}` typesets `\langle body \rangle` as a tabular with the entries right justified.

```

8945 \newcommand{\ratabtext}[1]{%
8946   \l@dnnullfills
8947   \measuretbody{#1}%
8948   \l@drestorefills
8949   \variab
8950   \settowright #1\\&\\%
8951   \enable@dtabfeet}
8952 %
8953 %

```

\measuretbody `\measuretbody{\langle body \rangle}` measures the tabular `\langle body \rangle`.

```

8954 \newcommand{\measuretbody}[1]{%
8955   \disable@notes%
8956   \disable@dtabfeet%
8957   \l@dcollcount=0%
8958   \nullsetzen%
8959   \l@dcollcount=0%
8960   \measuretrow #1\\&\\%
8961   \restore@notes%
8962   \global\l@dampcount=1}
8963 %
8964 %

```

\ltab Array with entries left justified.

```

\edbeforetab
8965 \newcommand{\ltab}[1]{%
8966   \l@dnnullfills
8967   \def\edbeforetab##1##2{\leftltab{##1}{##2}}%
8968   \def\edaftertab##1##2{\rightltab{##1}{##2}}%
8969   \measurebody{#1}%
8970   \l@drestorefills
8971   \variab
8972   \setmrowleft #1\\&\\%
8973   \enable@dtabfeet}
8974 %
8975 %

```

\latabtext Tabular with entries left justified.

```

8976 \newcommand{\latabtext}[1]{%
8977   \l@dnnullfills
8978   \measuretbody{#1}%
8979   \l@drestorefills
8980   \variab
8981   \setrowleft #1\\&\\%
8982   \enablel@dtabfeet}
8983 %
8984 %

```

\ctab Array with centered entries.

```

\edbeforetab 8985 \newcommand{\ctab}[1]{%
\edaftertab 8986   \l@dnnullfills
8987   \def\edbeforetab##1##2{\leftctab{##1}{##2}}%
8988   \def\edaftertab##1##2{\rightctab{##1}{##2}}%
8989   \measuretbody{#1}%
8990   \l@drestorefills
8991   \variab
8992   \setmrowcenter #1\\&\\%
8993   \enablel@dtabfeet}
8994 %
8995 %

```

\ctabtext Tabular with entries centered.

```

8996 \newcommand{\ctabtext}[1]{%
8997   \l@dnnullfills
8998   \measuretbody{#1}%
8999   \l@drestorefills
9000   \variab
9001   \setrowcenter #1\\&\\%
9002   \enablel@dtabfeet}
9003 %
9004 %

```

```

\spreadtext 905 \newcommand{\spreadtext}[1]{%\l@dcollcount=\l@dampcount%
906   \hb@xt@ \the\l@dcollwidth{\hbox{#1}\hss}}
907 %

```

```

\spreadmath 908 \newcommand{\spreadmath}[1]{%
909   \hb@xt@ \the\l@dcollwidth{\hbox{$\displaystyle{#1}$}\hss}}
910 %
911 %

```

\HILFSskip More helpers.
\Hilfsskip

```

9012 \newskip\HILFSskip
9013 \newskip\Hilfsskip
9014 %
9015 %

```

```

\EDTABINDENT16 \newcommand{\EDTABINDENT}{%
9017   \ifnum\l@dcollcount=30\let\NEXT\relax\l@dcollcount=0%
9018   \else\step\l@dcollcount%
9019     \advance\Hilfsskip by\l@dcollwidth%
9020     \ifdim\l@dcollwidth=0pt\advance\hilfscount\@ne
9021     \else\advance\Hilfsskip by \the\hilfscount\edtabcolsep%
9022     \hilfscount=1\fi%
9023     \let\NEXT=\EDTABINDENT%
9024   \fi\NEXT}%
9025 %

```

\edtabindent (was \tabindent)

```

9026 \newcommand{\edtabindent}{%
9027   \l@dcollcount=0\relax
9028   \Hilfsskip=0pt%
9029   \hilfscount=1\relax
9030   \EDTABINDENT%
9031   \hilfsskip=\hspace{%
9032   \advance\hilfsskip -\Hilfsskip%
9033   \Hilfsskip=0.5\hilfsskip%
9034 }%
9035 %
9036 %

```

\EDTAB (was \TAB)

```

9037 \def\EDTAB #1|#2|{%
9038   \setbox\tabhilfbox=\hbox{$\displaystyle{#1}$}%
9039   \setbox\tabHilfbox=\hbox{$\displaystyle{#2}$}%
9040   \advance\tabelskip -\wd\tabhilfbox%
9041   \advance\tabelskip -\wd\tabHilfbox%
9042   \unhbox\tabhilfbox\hskip\tabelskip%
9043   \unhbox\tabHilfbox}%
9044 %
9045 %

```

\EDTABtext (was \TABtext)

```

9046 \def\EDTABtext #1|#2|{%
9047   \setbox\tabhilfbox=\hbox{\#1}%
9048   \setbox\tabHilfbox=\hbox{\#2}%
9049   \advance\tabelskip -\wd\tabhilfbox%
9050   \advance\tabelskip -\wd\tabHilfbox%

```

```

9051   \unhbox\tabhilfbox\hskip\tabelskip%
9052   \unhbox\tabHilfbox}%
9053 %

```

\tabhilfbox Further helpers.

```

9054 \newbox\tabhilfbox
9055 \newbox\tabHilfbox
9056 %
9057 %

```

XXXI.2.4 Environments

`edarrayl edarrayc edarrayr` The ‘environment’ forms for `\ltab`, `\ctab` and `\rtab`.

```

9058 \newenvironment{edarrayl}{\l@ddcollect@body\ltab}{}%
9059 \newenvironment{edarrayc}{\l@ddcollect@body\ctab}{}%
9060 \newenvironment{edarrayr}{\l@ddcollect@body\rtab}{}%
9061 %
9062 %

```

`edtabularl edtabularc edtabularr` The ‘environment’ forms for `\ltabtext`, `\ctabtext` and `\rtabtext`.

```

9063 \newenvironment{edtabularl}{\l@ddcollect@body\ltabtext}{}%
9064 \newenvironment{edtabularc}{\l@ddcollect@body\ctabtext}{}%
9065 \newenvironment{edtabularr}{\l@ddcollect@body\rtabtext}{}%
9066 %
9067 %

```

XXXII Quotation's commands

`\initnumbering@quote` This macro, called at the beginning of any numbered section, locally redefines the quotation and quote environments, in order to allow their use inside of numbered sections.

```

\quotation \initnumbering@quote defines quotation environment.
\endquotation
\quote \newcommand{\initnumbering@quote}%
\endquote \ifnoquotation@\else
9068   \renewcommand{\quotation}{\par\leavevmode%
9069     \parindent=1.5em%
9070     \skipnumbering%
9071     \ifautopar%
9072       \vskip-\parskip%
9073     \else%
9074       \vskip\topsep%
9075     \fi%
9076   \global\leftskip=\leftmargin%
9077 }

```

```

9079           \global\rightskip=\leftmargin%
9080       }
9081   \renewcommand{\endquotation}{\par%
9082     \global\leftskip=0pt%
9083     \global\rightskip=0pt%
9084     \leavevmode%
9085     \skipnumbering%
9086     \ifautopar%
9087       \vskip-\parskip%
9088     \else%
9089       \vskip\topsep%
9090     \fi%
9091   }
9092   \renewcommand{\quote}{\par\leavevmode%
9093     \parindent=0pt%
9094     \skipnumbering%
9095     \ifautopar%
9096       \vskip-\parskip%
9097     \else%
9098       \vskip\topsep%
9099     \fi%
9100     \global\leftskip=\leftmargin%
9101     \global\rightskip=\leftmargin%
9102   }
9103   \renewcommand{\endquote}{\par%
9104     \global\leftskip=0pt%
9105     \global\rightskip=0pt%
9106     \leavevmode%
9107     \skipnumbering%
9108     \ifautopar%
9109       \vskip-\parskip%
9110     \else%
9111       \vskip\topsep%
9112     \fi%
9113   }
9114   \fi
9115 }
9116 %

```

XXXIII Section's title commands

XXXIII.1 Commands to disable some feature

`\ledsectnotoc` The `\ledsectnotoc` only disables the `\addcontentsline` macro.

```

9117 \newcommand{\ledsectnotoc}{\let\addcontentsline\@gobblethree}
9118 %

```

`\ledsectnomark` The `\ledsectnomark` only disables the `\chaptermark`, `\sectionmark` and `\subsectionmark` macros.

```

9119 \newcommand{\ledsectnomark}{%
9120   \let\chaptermark\@gobble%
9121   \let\sectionmark\@gobble%
9122   \let\subsectionmark\@gobble%
9123 }
9124 %

```

XXXIII.2 General overview

The system of `\eledxxxx` commands to section text work like this:

1. When one of these commands is called, `reledmac` writes to an auxiliary files:
 - The section level.
 - The section title.
 - The side (when `eledpar` is used).
 - The pstart where the command is called.
 - If we have starred version or not.
2. `reledmac` adds the title of the section to pstart, as normal content. This is to enable critical notes.
3. When `TeX` is run a other time, this file is read. That:
 - Adds the pstart number to a list of pstarts where a sectioning command is used.
 - Defines a command, the name of which contains the pstart number, and which calls the normal `TeX` sectioning command.
4. This last command is called when the pstart is effectively printed.

XXXIII.3 `\beforeeledchapter` command

We do not define commands for `\eledsection` and related if the `noeledsec` option is loaded. We use `etoolbox` tests and not the `\ifxxx... \else... \fi` structure to prevent problem of expansions with command after the `\ifxxx` which contains `\fi`. As we patch command inside this test, we need to change the category code of `#` character *before* `\notbool` statement, because the second argument is read with the standard catcode (read *The TeXbook* to understand when the catcode's change has effect).

```

9125 \catcode`\#=12
9126 \notbool{@noeled@sec}{%
9127 %

```

\beforeeledchapter For technical reasons, not yet solved, page-breaking before chapters can't be made automatically by eledmac. Users have to use **\beforeeledchapter**.

```

9128 \ifl@dmemoir
9129   \newcommand\beforeeledchapter{%
9130     \clearforchapter%
9131   }
9132 \else
9133   \newcommand\beforeeledchapter{%
9134     \if@openright%
9135       \cleardoublepage%
9136     \else%
9137       \clearpage%
9138     \fi%
9139   }
9140 \fi
9141 %

```

XXXIII.4 Auxiliary commands

nt@leftmargin@eledsection **t@rightmargin@eledsection** **\print@leftmargin@eledsection** and **\print@rightmargin@eledsection** are added by reledmac inside the code of sectioning command, in order to affix lines numbers. They include tests for RTL languages.

```

9142 \def\print@rightmargin@eledsection{%
9143   \if@eled@sectioning%
9144     \begingroup%
9145     \if@RTL%
9146       \let\llap\rlap%
9147       \let\leftlinenum\rightlinenum%
9148       \let\leftlinenumR\rightlinenumR%
9149       \let\l@drd@ta\l@dld@ta%
9150       \let\l@drsn@te\l@dlsn@te%
9151     \fi%
9152     \hfill\l@drd@ta \csuse{LR}{\l@drsn@te}%
9153     \endgroup%
9154   \fi%
9155 }%
9156
9157 \def\print@leftmargin@eledsection{%
9158   \if@eled@sectioning%
9159     \leavevmode%
9160     \begingroup%
9161     \if@RTL%
9162       \let\rlap\llap%
9163       \let\rightlinenum\leftlinenum%
9164       \let\rightlinenumR\leftlinenumR%
9165       \let\l@dld@ta\l@drd@ta%
9166       \let\l@dlsn@te\l@drsn@te%
9167     \fi%

```

```

9168 \l@old@ta\csuse{LR}{\l@old@te}%
9169 \endgroup%
9170 \fi%
9171 }%
9172 %
9173 %

```

XXXIII.5 Patching standard commands

We have to patch L^AT_EX, book and memoir sectioning commands in order to:

- Disable \edtext inside.
- Disable page breaking (for \chapter).
- Add line numbers and sidenotes.

Unfortunately, Maïeul Rouquette was not able to try if `memoir` is loaded. That is why `eledmac` tries to define for both standard class and `memoir` class.

```

9174 \AtBeginDocument{%
9175
9176
9177 \preto{\M@sect}{%
9178   {\let\old@edtext=\edtext%
9179   \let\edtext=\dummy@edtext@showlemma%
9180   }
9181   {}
9182   {}}
9183
9184 \appto{\M@sect}{%
9185   {\let\edtext=\old@edtext}
9186   {}
9187   {}}
9188
9189 \patchcmd{\M@sect}{%
9190   {#9}
9191   {#9}%
9192   \print@rightmargin@eledsection%
9193   }
9194   {}
9195   {}}
9196
9197 \patchcmd{\M@sect}{%
9198   {\hskip #3\relax}
9199   {\hskip #3\relax%
9200   \print@leftmargin@eledsection%
9201   }
9202   {}
9203   {}}

```

```

9204
9205 \patchcmd{\@mem@old@ssect}
9206   {#5}
9207   {#5%
9208   \print@leftmargin@eledsection%
9209   }
9210   {}
9211   {}
9212
9213 \patchcmd{\@mem@old@ssect}
9214   {\hskip #1}
9215   {\hskip #1%
9216   \print@rightmargin@eledsection%
9217   }
9218   {}
9219   {}

9220
9221
9222
9223 \patchcmd{\scr@startchapter}{\if@openright\cleardoublepage\else\clearpage\
9224   fi}{}%
9225   \if@eled@sectioning\else%
9226     \ifl@printingpages\else%
9227       \if@openright\cleardoublepage\else\clearpage\fi%No clearpage inside a
9228       \Pages: will keep critical notes from printing on the title page. Here for
9229       scrbook.
9230       \fi%
9231       \fi%
9232   }
9233 \patchcmd{\@makechapterhead}
9234   {#1}
9235   {\print@leftmargin@eledsection%
9236     #1%
9237   \print@rightmargin@eledsection%
9238   }
9239   {}
9240   {}

9241
9242 \patchcmd{\@makechapterhead}{% For BIDI
9243   {\if@RTL\raggedleft\else\raggedright\fi}%
9244   {\if@eled@sectioning\else%
9245     \if@RTL\raggedleft\else\raggedright\fi%
9246     \fi%
9247   }%
9248   {}%
9249   {}%
9250

```

```

9251 \patchcmd{\makeschapterhead}
9252   {#1}
9253   {\print@leftmargin@eledsection%
9254     #1%
9255     \print@rightmargin@eledsection%
9256   }
9257   {}
9258   {}
9259
9260 \preto{\@sect}{%
9261   {\let\old@edtext=\edtext
9262   \let\edtext=\dummy@edtext@showlemma%
9263   }
9264   {}
9265   {}
9266
9267 \appto{\@sect}{%
9268   {\let\edtext=\old@edtext}
9269   {}
9270   {}
9271
9272 \preto{\@ssect}{%
9273   {\let\old@edtext=\edtext%
9274   \let\edtext=\dummy@edtext@showlemma%
9275   }
9276   {}
9277   {}
9278
9279 \appto{\@ssect}{%
9280   {\let\edtext=\old@edtext}
9281   {}
9282   {}
9283
9284 %

```

`hyperref` also redefines `\@sect`. That is why, when manipulating arguments, we patch `\@sect` and the same only if `hyperref` is not used. If it is, we patch the `\NR` commands.

```

9285 \@ifpackageloaded{nameref}{%
9286
9287   \patchcmd{\NR@sect}{%
9288     {#8}
9289     {#8%
9290       \print@rightmargin@eledsection%
9291     }
9292     {}
9293     {}
9294
9295   \patchcmd{\NR@sect}{%
9296     {\hskip #3\relax}
9297     {\hskip #3\relax%

```

```
9298     \print@leftmargin@eledsection%
9299 }
9300 {}
9301 {}
9302
9303 \patchcmd{\NR@ssect}
9304   {#5}
9305   {#5%
9306   \print@rightmargin@eledsection%
9307   }
9308   {}
9309   {}
9310
9311 \patchcmd{\NR@ssect}
9312   {\hskip #1}
9313   {\hskip #1%
9314   \print@leftmargin@eledsection%
9315   }
9316   {}
9317   {}
9318 }%
9319 {
9320 \patchcmd{\@sect}
9321   {#8}
9322   {#8%
9323   \print@rightmargin@eledsection%
9324   }
9325   {}
9326   {}
9327
9328 \patchcmd{\@sect}
9329   {\hskip #3\relax}
9330   {\hskip #3\relax%
9331   \print@leftmargin@eledsection%
9332   }
9333   {}
9334   {}
9335
9336 \patchcmd{\@ssect}
9337   {#5}
9338   {#5%
9339   \print@rightmargin@eledsection%
9340   }
9341   {}
9342   {}
9343
9344 \patchcmd{\@ssect}
9345   {\hskip #1}
9346   {\hskip #1%
9347   \print@leftmargin@eledsection%
```

```

9348   }
9349   {}
9350   {}
9351   }%
9352 }%
9353 %

```

Close the `\notbool{@noeled@sec}` statement. Also, we have finished patching the commands, using # with a catcode equal to 12, so we are restoring the normal catcode for #.

```

9354 {}}%
9355 \protect\catcode`\#=6 %Space NEEDS by \catcode
9356 %

```

\chapter We patch the `\chapter` command even if the `noeledsec` option is called, because we can use `\chapter` in the optional argument of a `\pstart` in parallel typesetting.

```

9357 \AtBeginDocument{%
9358 \patchcmd{\chapter}{\clearforchapter}{%
9359   \if@eled@sectioning\else%
9360     \ifl@dprintingpages\else%
9361       \clearforchapter%
9362     \fi%
9363   \fi%
9364 }%
9365 {}%
9366 {}%
9367
9368 \patchcmd{\chapter}{\if@openright\cleardoublepage\else\clearpage\fi}{%
9369   \if@eled@sectioning\else%
9370     \ifl@dprintingpages%
9371       \endgraf%
9372     \else%
9373       \if@openright\cleardoublepage\else\clearpage\fi%No clearpage inside a
9374       \Pages: will keep critical notes from printing on the title page. Here for
9375       classical classes
9376     \fi%
9377   \fi%
9378 }%
9379 }%
9380 %

```

\if@eled@sectioning The boolean `\if@eled@sectioning` is set to true when a sectioning command is called by a `\eledxxx` command, and set to false after. It is used to enable/disable line number printing.

```

9381 \newif\if@eled@sectioning%
9382 %

```

We reopen a new `\notbool{@noeled@sec}` statement, as we will define the `\eleselection` commands.

```
9383 \notbool{@noeled@sec}{%
9384 %
```

XXXIII.6 Main code of \eledxxx commands

`\eled@sectioning@out` `\eled@sectioning@out` is the output file, to dump the pstarts where a sectioning command is used.

```
9385 \newwrite\eled@sectioning@out
9386 %
```

`\eledchapter` And now, the user sectioning commands, which write to the file, and also add content
`\eledsection` as a “normal” line.

```
\eledsubsection
9387 \newcommand{\eledchapter}[2][]{%
9388   \disable@familiarnotes%
9389   #2%
9390   \restore@familiarnotes%
9391   \ifledRcol%
9392     \immediate\write\eled@sectioning@out{%
9393       \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dnumstartsR}{}{R}
9394     }%
9395   \else%
9396     \immediate\write\eled@sectioning@out{%
9397       \string\eled@chapter{#1}{\unexpanded{#2}}{\the\l@dnumstartsL}{}{L}
9398     }%
9399   \fi%
9400 }
9401
9402 \newcommand{\eledsection}[2][]{%
9403   \disable@familiarnotes%
9404   #2%
9405   \restore@familiarnotes%
9406   \ifledRcol%
9407     \immediate\write\eled@sectioning@out{%
9408       \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumstartsR}{}{R}
9409     }%
9410   \else%
9411     \immediate\write\eled@sectioning@out{%
9412       \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumstartsL}{}{L}
9413     }%
9414   \fi%
9415 }
9416
9417 \newcommand{\eledsubsection}[2][]{%
9418   \disable@familiarnotes%
9419   #2%
```

```

9420   \restore@familiarnotes%
9421   \ifledRcol%
9422     \immediate\write\eled@sectioningR@out{%
9423       \string\eled@subsection{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsR}{\#R}
9424     }
9425   }%
9426   \else%
9427     \immediate\write\eled@sectioningR@out{%
9428       \string\eled@subsection{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsL}{\#L}
9429     }%
9430   \fi%
9431 \newcommand{\eledsubsubsection}[2] [] {%
9432   \disable@familiarnotes%
9433   #2%
9434   \restore@familiarnotes%
9435   \ifledRcol%
9436     \immediate\write\eled@sectioningR@out{%
9437       \string\eled@subsubsection{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsR}
9438     }%
9439   \else%
9440     \immediate\write\eled@sectioningR@out{%
9441       \string\eled@subsubsection{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsL}
9442     }%
9443   \fi%
9444 }
9445
9446 \WithSuffix\newcommand\eledchapter*[2] [] {%
9447   \disable@familiarnotes%
9448   #2%
9449   \restore@familiarnotes%
9450   \ifledRcol%
9451     \immediate\write\eled@sectioningR@out{%
9452       \string\eled@chapter{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsR}{\#R}
9453     }%
9454   \else%
9455     \immediate\write\eled@sectioningR@out{%
9456       \string\eled@chapter{\#1}{\unexpanded{\#2}}{\the\l@dnumpststartsL}{\#L}
9457     }%
9458   \fi%
9459 }
9460
9461 \WithSuffix\newcommand\eledsection*[2] [] {%
9462   \disable@familiarnotes%
9463   #2%
9464   \restore@familiarnotes%
9465   \ifledRcol%

```

```

9467   \immediate\write\eled@sectioningR@out{%
9468     \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpststartsR}{*}{R}
9469   }%
9470 \else%
9471   \immediate\write\eled@sectioning@out{%
9472     \string\eled@section{#1}{\unexpanded{#2}}{\the\l@dnumpststartsL}{*}{}
9473   }%
9474 \fi%
9475 }
9476
9477 \WithSuffix\newcommand\eledsubsection*[2] []{%
9478   \disable@familiarnotes%
9479   #2%
9480   \restore@familiarnotes%
9481   \ifledRcol%
9482     \immediate\write\eled@sectioningR@out{%
9483       \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dnumpststartsR}{*}{R}
9484     }%
9485   \else%
9486     \immediate\write\eled@sectioning@out{%
9487       \string\eled@subsection{#1}{\unexpanded{#2}}{\the\l@dnumpststartsL}{*}{}
9488     }%
9489   \fi%
9490 }
9491
9492 \WithSuffix\newcommand\eledsubsubsection*[2] []{%
9493   \disable@familiarnotes%
9494   #2%
9495   \restore@familiarnotes%
9496   \ifledRcol%
9497     \immediate\write\eled@sectioningR@out{%
9498       \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dnumpststartsR}{*}{R}
9499     }%
9500   \else%
9501     \immediate\write\eled@sectioning@out{%
9502       \string\eled@subsubsection{#1}{\unexpanded{#2}}{\the\l@dnumpststartsL}{*}{}
9503     }%
9504   \fi%
9505 }
9506 %

```

XXXIII.7 Macros written in the auxiliary file

`\eled@chapter` The sectioning macros, called in the auxiliary file. They have five arguments:

`\eled@section` 1. Optional arguments of L^AT_EX sectioning command.

`\eled@subsection`

`\eled@subsubsection`

2. Mandatory arguments of L^AT_EX sectioning command.
3. Pstart number.
4. Side: R if right, nothing if left.
5. Starred or not.

```

9507 \def\eled@chapter#1#2#3#4#5{%
9508   \ifstrempty{#4}{%
9509     {%
9510       \ifstrempty{#1}{%
9511         {%
9512           \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
9513             chapter[#2]}%
9514             \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}}\chaptermark{#2}%
9515           }%Need for \pairs, because of using parbox.
9516           {%
9517             \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
9518               chapter[#1]{#2}}%
9519               \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}}\chaptermark{#2}%
9520             }%Need for \pairs, because of using parbox.
9521             {%
9522               \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
9523                 chapter*{#2}}%
9524                 \csgdef{eled@sectioning@#3#5}{\let\edtext=\dummy@edtext@showlemma\
9525                   chapter*[#1]{#2}}}%Bug in LaTeX!
9526               }%
9527   \listcsgadd{eled@sections#5@0}{#3}%
9528 }
9529 \def\eled@section#1#2#3#4#5{%
9530   \ifstrempty{#4}{%
9531     {\ifstrempty{#1}{%
9532       {%
9533         \csgdef{eled@sectioning@#3#5}{\section{#2}}%
9534         \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}}\sectionmark{#2}%
9535       }%Need for \pairs, because of using parbox.
9536       {%
9537         \csgdef{eled@sectioning@#3#5}{\section[#1]{#2}}%
9538         \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext{}}\sectionmark{#1}%
9539       }%Need for \pairs, because of using parbox.
9540       {%
9541         \csgdef{eled@sectioning@#3#5}{\section*{#2}}%
9542       }%
9543     }%
9544   }%
9545 }
```

```

9541         {\csgdef{eled@sectioning@#3#5}{\section*[#1]{#2}}}%Bug in LaTeX!
9542     }
9543     \listcsgadd{eled@sections#5@0}{#3}%
9544   }
9545 \def\eled@subsection#1#2#3#4#5{%
9546   \ifstrempty{#4}%
9547     {\ifstrempty{#1}%
9548       {%
9549         \csgdef{eled@sectioning@#3#5}{\subsection{#2}}%
9550         \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext}\csuse{%
9551           subsectionmark}{#2}}%Need for \pairs, because of using parbox. \csuse in
9552           case of \subsectionmark is not defined (book)
9553         }%
9554       {%
9555         \csgdef{eled@sectioning@#3#5}{\subsection[#1]{#2}}%
9556         \csgdef{eled@sectmark@#3#5}{\let\edtext=\dummy@edtext}\csuse{%
9557           subsectionmark}{#1}}%Need for \pairs, because of using parbox. \csuse in
9558           case of \subsectionmark is not defined (book)
9559         }%
9560       }%
9561     \listcsgadd{eled@sections#5@0}{#3}%
9562   }
9563 \def\eled@subsubsection#1#2#3#4#5{%
9564   \ifstrempty{#4}%
9565     {\ifstrempty{#1}%
9566       {%
9567         \csgdef{eled@sectioning@#3#5}{\subsubsection{#2}}%
9568         \csgdef{eled@sectioning@#3#5}{\subsubsection[#1]{#2}}%Bug in
9569           LaTeX!
9570       }%
9571     \listcsgadd{eled@sections#5@0}{#3}%
9572   }
9573   \listcsgadd{eled@sections#5@0}{#3}%
9574 }
9575 %

```

End of the conditional test about noeledsec option.

```

9577 }{}%
9578 %

```

XXXIV Page breaking or no page breaking depending of specific lines

By default, page breaks are automatic. However, the user can define lines which will force page breaks, or prevent page breaks around one specific line. On the first run, the line-list file records the line number of where the page break is being changed (either forced, or prevented). On the next run, page breaks occur either before or after this line, depending on how the user sets the command. The default setting is after the line.

`\normal@page@break` `\normal@page@break` is an etoolbox list which contains the absolute line number of the last line, for each page.

```
9579 \def\normal@page@break{}  
9580 %
```

`\prev@pb` The `\l@prev@pb` macro is a etoolbox list, which contains the lines in which page breaks occur (before or after). The `\l@prev@nopb` macro is a etoolbox list, which contains the lines with NO page break before or after.

```
9581 \def\l@prev@pb{}  
9582 \def\l@prev@nopb{}  
9583 %
```

`\ledpb` The `\ledpb` macro writes the call to `\led@pb` in line-list file. The `\ledpbnum` macro writes the call to `\led@pbnum` in line-list file. The `\lednompb` macro writes the call to `\led@nompb` in line-list file. The `\lednopbnum` macro writes the call to `\led@nopbnum` in line-list file.

```
9584 \newcommand{\ledpb}{\write\linenum@out{\string\led@pb}}  
9585 \newcommand{\ledpbnum}[1]{\write\linenum@out{\string\led@pbnum{#1}}}  
9586 \newcommand{\lednompb}{\write\linenum@out{\string\led@nompb}}  
9587 \newcommand{\lednopbnum}[1]{\write\linenum@out{\string\led@nopbnum{#1}}}  
9588 %
```

`\led@pb` The `\led@pb` adds the absolute line number in the `\prev@pb` list. The `\led@pbnum` adds the argument in the `\prev@pb` list. The `\led@nompb` adds the absolute line number in the `\prev@nopb` list. The `\led@nopbnum` adds the argument in the `\prev@nopb` list.

```
9589 \newcommand{\led@pb}{\listxadd{\l@prev@pb}{\the\absline@num}}  
9590 \newcommand{\led@pbnum}[1]{\listxadd{\l@prev@pb}{#1}}  
9591 \newcommand{\led@nompb}{\listxadd{\l@prev@nompb}{\the\absline@num}}  
9592 \newcommand{\led@nopbnum}[1]{\listxadd{\l@prev@nompb}{#1}}  
9593 %
```

`\ledpbsetting` The `\ledpbsetting` macro only changes the value of `\led@pb@macro`, for which the default value is before.

```
9594 \def\led@pb@setting{before}  
9595 \newcommand{\ledpbsetting}[1]{\gdef\led@pb@setting{#1}}  
9596 %
```

`\led@check@pb` The `\led@check@pb` and `\led@check@nopb` are called before or after each line. They check if a page break must occur, depending on the current line and on the content of `\l@pb`.

```

9597 \newcommand{\led@check@pb}{\xifinlist{\the\absline@num}{\l@prev@pb}{%
9598 pagebreak[4]}}
9599 \newcommand{\led@check@nopb}{%
9600   \IfStrEq{\led@pb@setting}{before}{%
9601     \xifinlist{\the\absline@num}{\l@prev@nopb}{%
9602       {\numdef{\abs@prevline}{\the\absline@num-1}%
9603       \xifinlist{\abs@prevline}{\normal@page@break}{%
9604         {\nopagebreak[4]\enlargethispage{\baselineskip}}%
9605         {}}}%
9606       {}}%
9607     {}%
9608   \IfStrEq{\led@pb@setting}{after}{%
9609     \xifinlist{\the\absline@num}{\l@prev@nopb}{%
9610       \xifinlist{\the\absline@num}{\normal@page@break}{%
9611         {\nopagebreak[4]\enlargethispage{\baselineskip}}%
9612         {}}}%
9613     {}%
9614     {}}%
9615     {}%
9616   {}%
9617 }
9618 %

```

XXXV Long verse: prevents being separated by a page break

`\iflednoprinv` The `\lednoprinv` boolean is set to false by default. If set to true, `reledmac` will automatically prevent page breaks inside verse. The declaration is made at the beginning of the file, because it is used as a package option.

The \check@pb@in@verse checks if a verse is broken in two page. If true, it adds:

- The absolute line number of the first line of the verse -1 in the \led@pb list, if the page break must occur before the verse.
 - The absolute line number of the first line of the verse -1 in the \led@nspb list, if the page break must occur after the verse.

```
9619 \newcommand{\check@pb@in@verse}{%
9620     \ifinstanza\iflednoprinv\ifinserthangingsymbol% Using stanzas and
9621         enabling page breaks in verse control, while on a hanging verse.
9622         \ifnum\page@num=\last@page@num\else%If we have change page
9623             \IfStrEq{\led@pb@setting}{before}{%
```

```

9623      \numgdef{\abs@line@verse}{\the\absline@num-1}%
9624      \ledpbnum{\abs@line@verse}%
9625      }{}%
9626      \IfStrEq{\led@pb@setting}{after}{%
9627          \numgdef{\abs@line@verse}{\the\absline@num-1}%
9628          \lednopbnum{\abs@line@verse}%
9629      }{}%
9630      \fi%
9631      \fi\fi\fi%
9632  }
9633 %

```

XXXVI Tools for hyperref package

\Hy@raisedlink@left The hyperref package provides a \Hy@raisedlink command, to be used to add an anchor to the top of a line and not to the bottom of it.³⁸

However, this command disrupts the line breaking mechanism when it is called before any word. This is why reledmac defines \Hy@raisedlink@left that is called to the left of words, at the beginning of \edtext or inside the \edlabel commands.³⁹

```

9634 \def\Hy@raisedlink@left#1{%
9635   \ifvmode
9636     #1%
9637   \else
9638     \Hy@SaveSpaceFactor
9639     \llap{\smash{%
9640       \begingroup
9641         \let\HyperRaiseLinkLength\@tempdima
9642         \setlength\HyperRaiseLinkLength\HyperRaiseLinkDefault
9643         \HyperRaiseLinkHook
9644       \expandafter\endgroup
9645       \expandafter\raise\the\HyperRaiseLinkLength\hbox{%
9646         \Hy@RestoreSpaceFactor
9647         #1%
9648         \Hy@SaveSpaceFactor
9649       }%
9650     }%
9651     \Hy@RestoreSpaceFactor
9652     \penalty\@M\hskip\z@\relax
9653   \fi
9654 }
9655 %

```

³⁸<http://tex.stackexchange.com/a/17138/7712>.

³⁹The code is inspired by an answer given by @unbonpetit. Thanks to him. <http://texnique.fr:80/osqa/questions/781/hyraisedlink-perturbe-la-maniere-dont-se-fait-la-coupure-de-ligne/801>.

XXXVII Compatibility with `eledmac`

Here, we define some commands for the `eledmac-compat` option.

```

9656 \ifeledmaccompat%
9657
9658   \newcommand{\footnormalX}[1]{\arrangementX[#1]{normal}}%
9659   \newcommand{\footparagraphX}[1]{\arrangementX[#1]{paragraph}}%
9660   \newcommand{\foottwocolX}[1]{\arrangementX[#1]{twocol}}%
9661   \newcommand{\footthreecolX}[1]{\XarrangementX[#1]{threecol}}%
9662
9663 \unless\ifnocritical@
9664   \newcommand{\footnormal}[1]{\Xarrangement[#1]{normal}}%
9665   \newcommand{\footparagraph}[1]{\Xarrangement[#1]{paragraph}}%
9666   \newcommand{\foottwocol}[1]{\Xarrangement[#1]{twocol}}%
9667   \newcommand{\footthreecol}[1]{\Xarrangement[#1]{threecol}}%
9668   \let\hsizetwocol\Xsizetwocol
9669   \let\hsizethreecol\Xsizethreecol
9670   \let\bhookXnote\Xbhooknote
9671   \let\boxsymlinenum\Xboxsymlinenum
9672   \let\symlinenum\Xsymlinenum
9673   \let\beforenumberinfofootnote\Xbeforenumber
9674   \let\afternumberinfofootnote\Xafternumber
9675   \let\beforeXsymlinenum\Xbeforesymlinenum
9676   \let\afterXsymlinenum\Xaftersymlinenum
9677   \let\inplaceofnumber\Xinplaceofnumber
9678   \let\Xlemmaseparator\lemmaseparator
9679   \let\afterlemmaseparator\Xafterlemmaseparator
9680   \let\beforelemmaseparator\Xbeforelemmaseparator
9681   \let\inplaceoflemmaseparator\Xinplaceoflemmaseparator
9682   \let\txtbeforeXnotes\Txtbeforenotes
9683   \let\afterXrule\Xafterrule
9684   \let\numberonlyfirstinline\Xnumberonlyfirstinline
9685   \let\numberonlyfirstintwo\Xnumberonlyfirstintwo
9686   \let\nonumberinfofootnote\Xnonumberinfofootnote
9687   \let\pstartinfofootnote\Xpstart
9688   \let\pstartinfofootnoteeverytime\Xpstarteverytime
9689   \let\onlyXpstart\Xonlypstart
9690   \let\Xnonumberinfofootnote\Xnonumber
9691   \let\nonbreakableafternumber\Xnonbreakableafternumber
9692   \let\maxhXnotes\Xmaxhnotes
9693   \let\beforeXnotes\Xbeforenotes
9694   \let\boxlinenum\Xboxlinenum
9695   \let\boxlinenumalign\Xboxlinenumalign
9696   \let\boxstartlinenum\Xboxstartlinenum
9697   \let\boxendlinenum\Xboxendlinenum
9698   \let\twolines\Xtwolines
9699   \let\morethan twolines\Xmorethan twolines
9700   \let\twolinesbutnotmore\Xtwolinesbutnotmore
9701   \let\twolinesonlyinsamepage\Xtwolinesonlyinsamepage

```

```

9702 \fi
9703
9704 \unless\ifnofamiliar@
9705   \let\notesXwidthliketwocolumns\noteswidthliketwocolumnsX
9706 \fi
9707 \newcommandx{\parafootsep}[2][1,usedefault]{%
9708   \Xparafootsep[#1]{#2}%
9709   \parafootsepX[#1]{#2}%
9710 }%
9711
9712 \newcommandx{\afternote}[2][1,usedefault]{%
9713   \Xafternote[#1]{#2}%
9714   \afternoteX[#1]{#2}%
9715 }%
9716
9717 \unless\ifnoend@
9718   \let\XendXtwolines\Xendtwolines
9719   \let\XendXmorethanTwolines\XendmorethanTwolines
9720   \let\bhookXendnote\Xendbhooknote
9721   \let\boxXendlinenum\Xendboxlinenum%
9722   \let\boxXendlinenumalign\Xendboxlinenumalign%
9723   \let\boxXendstartlinenum\Xendboxstartlinenum%
9724   \let\boxXendendlinenum\Xendboxendlinenum%
9725   \let\XendXlemmaseparator\Xendlemmaseparator
9726   \let\XendXbeforelemmaseparator\Xendbeforelemmaseparator
9727   \let\XendXafterlemmaseparator\Xendafterlemmaseparator
9728   \let\XendXinplaceoflemmaseparator\Xendinplaceoflemmaseparator
9729 \fi
9730
9731 \AtBeginDocument{%
9732   \ifdef\lineref{}{\let\lineref\edlineref}%
9733 }%
9734
9735 \fi%
9736 %
9737 %

```

</code>

Appendix A Things to do when changing versions

Appendix A.1 Migrating from `edmac` to `ledmac`

If you have never used `edmac`, ignore this section. If you have used `edmac` and are starting on a completely new document, ignore this section. Only read this section if you are converting an original `edmac` document to use `ledmac`.

The package still provides the original `\text` command, but it is (a) deprecated, and (b) its name has been changed⁴⁰ to `\critext`; use the `\edtext` macro instead. However, if you do use `\critext` (the new name for `\text`), the following is a reminder.

`\critext` Within numbered paragraphs, footnotes and endnotes are generated by forms of the `\critext` macro:

```
\critext{\langle lemma\rangle}{\langle commands\rangle}/
```

The `\langle lemma\rangle` argument is the lemma in the main text: `\critext` both prints this as part of the text, and makes it available to the `\langle commands\rangle` you specify to generate notes. The `/` at the end terminates the command; it is part of the macro's definition so that spaces after the macro will be treated as significant.

For example:

I saw my friend <code>\critext{Smith}</code>	1 I saw my friend
<code>\Afootnote{Jones C, D.}/</code>	2 Smith on Tuesday.
on Tuesday.	<u>2 Smith] Jones C, D.</u>

The lemma `Smith` is printed as part of this sentence in the text, and is also made available to the footnote that specifies a variant, `Jones C, D.` The footnote macro is supplied with the line number at which the lemma appears in the main text.

The `\langle lemma\rangle` may contain further `\critext` commands. Nesting makes it possible to print an explanatory note on a long passage together with notes on variants for individual words within the passage. For example:

<code>\critext{I saw my friend</code>	1 I saw my friend
<code>\critext{Smith}{\Afootnote{Jones</code>	2 Smith on Tuesday.
<code>C, D.}/ on Tuesday.}</code>	<u>2 Smith] Jones C, D.</u>
<code>\Bfootnote{The date was</code>	1-2 I saw my friend
<code>July 16, 1954.}</code>	Smith on Tuesday.] The
<code>/</code>	date was July 16, 1954.

However, `\critext` cannot handle overlapping but unnested notes—for example, one note covering lines 10–15, and another covering 12–18; a `\critext` that starts in the `\langle lemma\rangle` argument of another `\critext` must end there, too. (The `\lemma` and `\linenum` commands may be used to generate overlapping notes if necessary.)

The second argument of the `\critext` macro, `\langle commands\rangle`, is the same as the second argument to the `\edtext` macro.

It is possible to define aliases for `\critext`, which can be easier to type. You can make a single character substitute for `\critext` by saying this:

```
\catcode`\<=\active
```

⁴⁰A name like `\text` is likely to be defined by other `TeX` packages (it certainly is by the AMS packages) and it seems sensible to try and avoid clashes with other definitions.

```
\let<=\critext
```

Then you might say `<{Smith}\variant{Jones}/`. This of course destroys the ability to use `<` in any new macro definitions, so long as it remains in effect; hence it should be used with care.

Changing the character at the end of the command requires more work:

```
\catcode`<=\active
\def\xtext#1#2{\critext{#1}{#2}/}
\let<=\xtext
```

This allows you to say `<{Smith}\Afootnote{Jones}>`.

Aliases for `\critext` of the first kind shown here also can't be nested—that is, you can't use the alias in the text that forms the first argument to `\critext`. (See VI p. 130 to find out why.) Aliases of the second kind may be nested without any problem.

If you really have to use `\critext` in any of the tabular or array environments, then `\edtext` must not be used in the same environment. If you use `\critext` in one of these environments then you have to issue the declaration `\usingcritext` beforehand. The declaration `\usingedtext` must be issued to revert to the default assumption that `\edtext` will be used.

Appendix A.2 Migration from ledmac to elemac

In elemac, some changes were made in the code to allow easy customization. This may cause problems for people who have already made their own. The next sections explain how to handle this.

If you have created your own series using `\addfootins` and `\addfootinsX`, you must use instead the `\newseries` command (see 6.7.1 p. 36), and remove any `\Xfootnote` command.

If you have customized the `\XXXXXXfmt` command, please check whether you can achieve the same by the commands documented for display options (7 p. 38) or `\Xfootnote` options (6.2.2 p. 25). Otherwise please add a new ticket on Github to request a new function for doing this.⁴¹

If for some reason you do not want to make the modifications to use the new functions of elemac, you can continue using your own `\XXXXXXfmt` command, but you must replace:

```
\renewcommand*{XXXXfmt}[3]
```

with

```
\renewcommandx*{XXXXfmt}[4][4=Z]
```

⁴¹<https://github.com/maieul/ledmac/issues>

If you do not make that, you will get a spurious [X], where X is series letter.

If you used a \protect command inside a \footnote command inside a numbered section, you must change the \protect to \noexpand. Otherwise the command after the \protect will be discarded.

Appendix A.3 Migration to elemac 1.5.1

The version 1.5.1 corrects a bug in `stanzaindent repetition` (cf. 9.3 p. 52). This bug had two consequences:

1. `stanzaindent repetition` did not work when its value was greater than 2.
2. `stanzaindent repetition` worked wrong when its value was equal to 2.

So, if you used `stanzaindent repetition` with a value equal to 2, you had to change your `\setstanzaindent`. Explanation:

```
\setcounter{stanzaindent repetition}{2}
\setstanzaindent{5,1,0}
```

This code, in versions prior to 1.5.1, made the first line have an indentation of 0, the second line of 1, the third verse of 0, the fourth verse of 1 and so forth.

But this code should have instead achieved quite the contrary: the first line would have an indentation of 1, the second line of 0, the third line of 1, the fourth line of 0 and so forth.

So version 1.5.1 corrected this bug. If you want to keep the former presentation, you must change:

```
\setcounter{stanzaindent repetition}{2}
\setstanzaindent{5,1,0}
```

to:

```
\setcounter{stanzaindent repetition}{2}
\setstanzaindent{5,0,1}
```

Appendix A.4 Migration to elemac 1.12.0

The migration to elemac 1.12.0 is easy:

- You must first delete all the auxiliary files, then compile your document three times as usual.
- If you have modified `\l@reg`, which is not advisable, you must rename it to `\@nl@reg`.

There is an additional problem. If you have put text into brackets just after `\pstart` or `\pend`, this text will be considered to be an optional argument of `\pstart` or `\pend` (see 5.2.3 p. 18). If so, add a `\relax` between `\pstart/\pend` and the first bracket.

The version 1.12.0 also introduce a better way to handle sectional divisions inside numbered text. Please read 16.2 p. 71.

Appendix A.5 Migration to elemac 17.1

This version changes the default setting of `\Xpstart`. Henceforth, pstart numbers will be printed in footnotes within the section of text where you have called `\numberpstarttrue`.

We do not see any reason to print them in the other sections. However, if you want to print the pstart numbers in all of the footnotes, whatever the section, without having to use `\numberpstarttrue`, you can use `\Xpstarteverytime`.

Appendix A.6 Migration to elemac 1.21.0

Appendix A.6.1 `\Xledsetnormalparstuff` and `\ledsetnormalparstuffX`

The `\ledsetnormalparstuff` has been split into two different commands:

- `\Xledsetnormalparstuff` for critical notes;
- `\ledsetnormalparstuffX` for familiar notes.

Both commands can take an optional argument which is the series letter. If you have redefined `\ledsetnormalparstuff` or any of the commands which call them, you must change them accordingly.

Appendix A.6.2 Endnotes

In any case, delete the `.end` file before the next run.

The previous version of Elemac had a bug: there were two spaces between the starting page number and the starting line number, but only one space between the ending page number and the ending line number.

As a matter of fact, a spurious space was added after the first `\printnpnum`. This spurious space has been deleted. However, if you want to keep the previous spurious space, you may load the package with the `oldprintnpnumspace` option.

If you have redefined `\endprint`, you must:

- Contact us and ask for the feature that required your hack, in order to avoid such a hack in the future.
- Use the new fifth argument.
- Add `\xdef\@currentseries{#4}` at the beginning of your own command.

Appendix A.7 Migration to elemac 1.22.0

The `\ledinnote` command now takes a first optional argument, which is the label for the hyperreference. If you have redefined it, change your redefinition, and check whether you can avoid this redefinition by only redefining `\ledinnotemark`.

Appendix A.8 Migration to elemac 1.23.0

You must delete the numbered auxiliary files before compiling with the new version of elemac.

Appendix A.9 Migration from `eledmac` to `reledmac`

There are many changes in `reledmac` which require the user to make modifications.

Appendix A.9.1 Risk of ‘no room for a new’

The risk to obtain a ‘no room for a new something’ error is greater in `reledmac` than it is in `eledmac`. See 19.1.3 p. 74 in order to know how to limit it.

Appendix A.9.2 Multiple indices with `memoir`

`Eledmac` and `ledmac` used the specific indexing tools of the `memoir` class designed to produce multiple indices. However, `eledmac` could also use `imakeidx` or `indextools` tools independently of the `memoir` class. This system forced to maintain redundant code. Since `reledmac`, we use only the `imakeidx` or `indextools` tools.

Consequently: Users of `memoir` are invited to use `indextool` or `imakeidx` to produce multiple indices.

Appendix A.9.3 Deprecated commands and options

The table of deprecated commands and their alternatives follows. Note that the way some commands must be used may have changed. Please read the handbook.

<i>Deprecated command</i>	<i>Replaced with</i>
<code>\addfootins</code>	<code>\newseries</code>
<code>\addfootinsX</code>	<code>\newseries</code>
<code>\critext</code>	<code>\edtext</code>
<code>\falseverse</code>	<code>\newverse</code>
<code>\interparanote glue</code>	<code>\Xafternote</code> and <code>\afternoteX</code>
<code>\ledchapter</code>	<code>\eledchapter</code>
<code>\ledsection</code>	<code>\eledsection</code>
<code>\ledsetnormalparstuff</code>	<code>\Xledsetnormalparstuff</code> and <code>\ledsetnormalparstuffX</code>
<code>\ledsubsection</code>	<code>\eledsubsection</code>
<code>\ledsubsubsection</code>	<code>\eledsubsubsection</code>
<code>\noeledsec</code>	Package option <code>noeledsec</code>
<code>\noendnotes</code>	Package option <code>noendnotes</code>
<code>\pageparbreak</code>	<code>\ledpb</code>

The `ledsecnolinenumbers` option has been removed, because it was related to deprecated commands.

The `oldprintnppnumspace` option has been removed too, because it was related to a historical bug. The `\usingedtext` and `\usingcritext` commands are also deprecated.

Appendix A.9.4 \renewcommand replaced by command

Many uses of \renewcommand have been replaced with uses of specific commands. Please read handbook about specific commands.

<i>Deprecated \renewcommand</i>	<i>Replaced with</i>
\@led@extranofeet	\newseries
\apprefprefixmore	\setapprefprefixmore
\apprefprefixsingle	\setapprefprefixsingle
\endstanzaextra	Optional argument of \&
\hangingsymbol	\sethangingsymbol
\ledfootinsdim	\Xmaxhnotes and \maxhnotesX
\parafootftmsep	\Xparafootsep and \parafootsepX
\notenumfont	\Xnotenumfont, \Xendnotenumfont and \notenumfontX
\notefontsetup	\Xnotefontsize, \Xendnotefontsize and \notefontsizeX
\sidenotesep	\setsidenotesep
\startstanzahook	Optional argument of \stanza
\symlinenum	\Xsymlinenum

Appendix A.9.5 Commands the names of which have been changed

In order to help the migration from eleedmac to reledmac, you may load reledmac with eleedmac-compat option. However, it is advised not to, and to change the command names themselves instead. In many cases, you use only a few of them, except the \footparagraph command.

<i>Old command</i>	<i>New command</i>
\footparagraph	\Xarrangement
\footnormal	\Xarrangement
\foottwocol	\Xarrangement
\footthreecol	\Xarrangement
\footparagraphX	\arrangementX
\footnormalX	\arrangementX
\foottwocolX	\arrangementX
\footthreecolX	\arrangementX
\afterlemmaseparator	\Xafterlemmaseparator
\afternote	\Xafternote and \afternoteX
\afternumberinfofnote	\Xafternumber
\afterXrule	\Xafterrule
\afterXsymlinenum	\Xaftersymlinenum
\beforelemmaseparator	\Xbeforelemmaseparator
\beforenumberinfofnote	\Xbeforenumber
\beforeXnotes	\Xbeforenotes
\beforeXsymlinenum	\Xbeforesymlinenum

<i>Old command</i>	<i>New command</i>
\bhookXnote	\Xbhookendnote
\bhookXnote	\Xbhooknote
\boxendlinenum	\Xboxendlinenum
\boxlinenum	\Xboxlinenum
\boxlinenumalign	\Xboxlinenumalign
\boxstartlinenum	\Xboxstartlinenum
\boxsymlinenum	\Xboxsymlinenum
\boxXendlinenum	\Xendboxlinenum
\boxXendlinenumalign	\Xendboxlinenumalign
\boxXendstartlinenum	\boxXendstartlinenum
\letboxXendendlinenum	\Xendletboxendlinenum
\hsizetwocol	\Xhsizetwocol
\hsizethreecol	\Xhsizethreecol
\inplaceoflemmaseparator	\Xinplaceoflemmaseparator
\inplaceofnumber	\Xinplaceofnumber
\lemmaseparator	\Xlemmaseparator
\maxhXnotes	\Xmaxhnotes
\morethanwolines	\Xmorethanwolines
\nonumberinfofootnote	\Xnonumber
\notesXwidthliketwocolumns	\noteswidthliketwocolumnsX
\noXlemmaseparator	\Xnolemmaseparator
\numberonlyfirstinline	\Xnumberonlyfirstinline
\numberonlyfirstintwolines	\Xnumberonlyfirstintwolines
\nonbreakableafternumber	\Xnonbreakableafternumber
\onlyXpstart	\Xonlypstart
\parafootsep	\Xparafootsep and \parafootsepX
\pstartinfofootnote	\Xpstart
\pstartinfofootnoteeverytime	\Xpstarteverytime
\symlinenum	\Xsymlinenum
\twolines	\Xtwolines
\twolinesbutnotmore	\Xtwolinesbutnotmore
\twolinesonlyinsamepage	\Xtwolinesonlyinsamepage
\txtbeforeXnotes	\Xtxtbeforenotes
\XendXafterlemmaseparator	\Xendafterlemmaseparator
\XendXbeforelemmaseparator	\Xendbeforelemmaseparator
\XendXinplaceoflemmaseparator	\Xendinplaceoflemmaseparator
\XendXlemmaseparator	\Xendlemmaseparator
\XendXmorethanwolines	\Xendmorethanwolines
\XendXtwolines	\Xendtwolines
\Xnonumberinfofootnote	\Xnonumber
\lineref	\edlineref

Appendix A.9.6 Endnotes

With `reledmac`, there is now one auxiliary file for every endnotes set (`.Aend`, `.Bend`, `.Cend` etc.). If you have overriden `\doendnotes` (which you would not have done) you must adapt your code.

Appendix A.9.7 Z Series

The ‘Z’ series of notes has been removed. Only five series are provided now by default: A, B, C, D, E.

Appendix A.9.8 Internal commands

Users who have overriden internal commands, which is wrong, must adapt according to the following. Or better, they should not override any of such commands and use `reledmac` options instead.

- If you have modified `\Xfootfmt`, note that the fourth argument is now mandatory.
- `\unvxh` has been replaced with `\Xunvxh` and `\unvxhX` with two mandatory arguments.

Appendix A.10 Migration to `reledmac 2.1.0`

`Reledmac 2.1.0` fix some bugs when using `\Xbhooknote` and `\bhooknoteX` not in order to execute code at the beginning of each notes, but to insert content of at the beginning of each notes.

People who use these commands to do it, which is not the original idea, must change the following:

1. Horizontal space is no longer automatically added after the content of the `\Xbhooknote/\bhooknoteX` argument. You must include it manually. So instead of `\Xbhooknote{content}`, use `\Xbhooknote{content }.`
2. Indent is no longer automatically added before the content of the `\Xbhooknote/\bhooknoteX` argument. If you want to keep it, add `\indent` in the argument of `\Xbhooknote/\bhooknoteX`.

Appendix A.11 Migration to `reledmac 2.1.3`

`Reledmac 2.1.3` fix an historical bug, (style in `ledmac 0.7!`) which doubled the space before the rules of paragraphed familiar footnotes. Consequently, if you use paragraphed familiar footnotes, you should maybe adapt it, playing with `\beforenotesX`.

Appendix A.12 Migration to `reledmac 2.3.0`

Before `reledmac 2.3.0`, for typesetting verse, any empty line was considered a paragraph inside verses. Counting empty lines this created breaking verse, hanging verses, and also added spurious vertical spaces. Version `2.3.0` disables paragraph in stanza. If you want vertical space, use optional argument of `\stanza` or `\endverse`.

Appendix A.13 Migration to *reledmac* 2.4.0

It is not mandatory, but strongly recommended, to change any `\renewcommand{\endashchar}{<...>}` to the use of `\Xlinerangeseparator` or / and `\Xendlinerangeseparator` (7.2.4 p. 40).

Appendix A.14 Migration to *reledmac* 2.5.0

It is strongly recommended to stop redefining `\printnpnum` and to use the hooks documented in 7.2.3 p. 40.

`\xlineref` does not print anymore the side flag (R for right side), because it is incompatible with numerical test. Use `\xflagref` to obtain it.

The `\printlines` and `\printendlines` commands take now an eighth argument, which is the side flag. It is strongly recommended to NEVER redefine these two commands and to use the setting commands instead (or to ask for new setting commands if the actual does not answer to your needs). However, if you have done it, just change your redefinition to have a new argument.

It is strongly recommended to stop redefining `\fullstop` and to use `\Xsublinesep` instead.

Appendix A.15 Migration to *reledmac* 2.7.0

`\SErefonlypage` (introduced in *reledmac* 2.5.0) added an parenthesis after the page number. This was just an error, linked to a bad imitation of `\SErefwithpage`. That has been deleted. And so, the `\XendafterpagenumberSErefonlypage` to set it was also deleted.

`\rigidbalance` is split to two new commands: `\Xrigidbalance` for critical footnotes and `\rigidbalanceX` for familiar footnotes. If you have redefined it — but why should you have ?—, you should split your single redefinition in two redefinitions.

Appendix A.16 Migration to *reledmac* 2.7.2

`\Xhspace` is already defined in the *floatrow* package. It becomes `\Xwidth`, and, consequently, `\hspaceX` becomes `\widthX`.

The ancient names are temporarily maintained as aliases.

Appendix A.17 Migration to *reledmac* 2.8.0

Reledmac 2.8.0 fix spurious indents for paragraphed critical and familiar footnotes in *ledgroup* and *minipage*. You can re-establish the indent with `\Xparinden` and `\parindentX`.

Appendix A.18 Migration to *reledmac* 2.13.1

Reledmac 2.5.0 added a bug, which makes the right flag to be printed on the right side of critical footnotes, even if not explicitly requested by using `\Xlineflag`.

Version 2.13.1 solves this issue. Please use `\Xlineflag` if you want to add the right flag.

Appendix A.19 Migration to `reledmac 2.18.0`

After updating `reledmac`, and before any new compilation, you need to clean your `.aux` files, if you use `\edlabel` or related.

Appendix A.20 Migration to `reledmac 2.21.0`

Previously, there was a bug, which meant that the description in the handbook was incorrect. If you wrote

```
The \edtext{creature}{\edindex{elephant}} was quite  
unafrican}{\Afootnote{Of the mouse, that is.}}
```

“elephant” was indexed in the main text and in the critical footnotes. With the new version of `reledmac`, it is indexed only in main text. If you also want to index it in critical footnotes, do

```
The \edtext{creature}{\edindex{elephant}} was quite  
unafrican}{\Afootnote{\edindex{elephant}Of the mouse, that is.}}
```

Appendix A.21 Migration to `reledmac 2.24.0`

When using `\labelpstarttrue`, a spurious space^a was introduced after the pstart number (only for normal typesetting, not while typesetting in parallel). The new version of the package has deleted this spurious space. If you consider that it was NOT a spurious space, you should add it manually in your definition of `\thepstart`.

Appendix A.22 Migration to `reledmac 2.26.0`

You must delete your `.aux` file after having upgraded to this new version of `reledmac`.

References

- [Bre96] Herbert Breger. *tabmac*. October 1996. (Available from CTAN in `macros/plain/contrib/tabmac`)
- [Bur01] John Burt. ‘Typesetting critical editions of poetry’. *TUGboat*, **22**, 4, pp. 353–361, December 2001. (Code available from CTAN in `macros/latex/contrib/poemscol`)
- [Eck03] Matthias Eckermann. *The Parallel-Package*. April 2003. (Available from CTAN in `macros/latex/contrib/parallel`)
- [Fai03] Robin Fairbairns. *footmisc—a portmanteau package for customising footnotes in L^AT_EX*. February 2003. (Available from CTAN in `macros/latex/contrib/footmisc`)
- [LW90] John Lavagnino and Dominik Wujastyk. ‘An overview of edmac: a PLAIN TeX format for critical editions’. *TUGboat*, **11**, 4, pp. 623–643, November 1990. (Code available from CTAN in `macros/plain/contrib/edmac`)
- [Lüc03] Uwe Lück. ‘ednotes—critical edition typesetting with L^AT_EX’. *TUGboat*, **24**, 2, pp. 224–236, 2003. (Code available from CTAN in `macros/latex/contrib/ednotes`)
- [Sul92] Wayne G. Sullivan. *The file edstanza.doc*. June 1992. (Available from CTAN in `macros/plain/contrib/edmac`)
- [Wil02] Peter Wilson. *The memoir class for configurable typesetting*. November 2002. (Available from CTAN in `macros/latex/contrib/memoir`)
- [Wil04] Peter Wilson and Maïeul Rouquette. *Parallel typesetting for critical editions: the eledpar package*. December 2004. (Available from CTAN in `macros/latex/contrib/ledmmac`)

Index

Symbols

\&	51
\@EDROWFILL@	1
\@adv	1
\@advancestanzanumber	1
\@annot	1
\@cannot@end@print	1
\@cannot@start@print	1
\@beforeinsertofthisedtext	1
\@doclearpage	1
\@doreinfeetX	1
\@edindex@fornote@	1

\@edindex@hyperref	1
\@edrowfill@	1
\@edtext@level	1
\@emptytoks	1
\@fnpos	1
\@footnotemark	1
\@footnotetext	1
\@getfirstseries	1
\@gobblefour	1
\@gobbleseven	1
\@gobblethree	1
\@h	1
\@changingsymbol	1
\@iiiminipage	1
\@insertstanza@number	1
\@k	1
\@l@dttempcnta	1
\@l@dttempcntb	1
\@lab	1
\@led@testifnofoot	1
\@lemma	1
\@line@@num	1
\@clock	1
\@lopL	1
\@lopR	1
\@makechapterhead	1
\@makeschapterhead	1
\@mem@extranofeet	1
\@mem@old@ssect	1
\@mpfnpos	1
\@msd	1
\@msd@C	1
\@msd@options@iffullpage	1
\@msd@list	1
\@nl	1
\@nl@reg	1
\@opXfeet	1
\@pend	1
\@pendR	1
\@ref	1
\@ref@reg	1
\@ref@reg@parse	1
\@sect	1
\@series	1
\@set	1
\@sidenotesep	1
\@ssect	1
\@startstanza	1
\@stopmsd	1
\@stopstanza	1

\@sw	1
\@tag	1
\@wredindex	1
\@xloop	1
\@xympar	1
CLASSarticle	74
CLASSbook	74, 360
CLASSmemoir	212, 274–276, 310, 360, 379, 442, 446
CLASSscrbook	446
COMMAND*footnote	75
COMMAND\...@footnotemark...	215
COMMAND\...d@ta	157
COMMAND\<hook @<series	262
COMMAND\<hookname <pseudoseries	264, 265
COMMAND\<type footfmt	200
COMMAND\@@line	191
COMMAND\@MM	178, 443
COMMAND\@Rlineflag	312, 443
COMMAND\@SErefprefix	289
COMMAND\@SErefprefixmore	289
COMMAND\@add@	350
COMMAND\@adv	114
COMMAND\@annot	163
COMMAND\@annot@end@print	204
COMMAND\@annot@start@print	204
COMMAND\@apprefprefixmore	289
COMMAND\@apprefprefixsingle	289
COMMAND\@beforeinsertofthisedtext	137
COMMAND\@bsphack	277
COMMAND\@doclearpage	275, 276, 436, 446
COMMAND\@doreinfeetX	446
COMMAND\@dprintingcolumns	443
COMMAND\@edindex@hyperref	312, 313
COMMAND\@edtext@level	134
COMMAND\@esphack	277
COMMAND\@firstofone	33
COMMAND\@fnpos	233, 271
COMMAND\@footnotemark	212, 436, 446
COMMAND\@footnotetext	212, 213, 436
COMMAND\@gobble	32, 58, 132, 133, 163, 257
COMMAND\@gobblefive	445
COMMAND\@gobblefour	442
COMMAND\@gobbleseven	259
COMMAND\@gobblethree	435
COMMAND\@h	195
COMMAND\@hangingsymbol	317
COMMAND\@iiiminipage	301, 303, 435, 446

COMMAND\@iiimimage	301
COMMAND\@l	441
COMMAND\@l@dtmpcnta	160, 164, 172
COMMAND\@l@dtmpcntb	164
COMMAND\@l@reg	441
COMMAND\@lab	110, 277, 280, 285, 435
COMMAND\@ldunboxmpfoot	304
COMMAND\@led@extranofeet	380
COMMAND\@ledinnote@command	308, 309
COMMAND\@lemma	137, 139
COMMAND\@lock	104, 318
COMMAND\@lopL	436
COMMAND\@lopR	436
COMMAND\@makecol	271, 272, 274, 446
COMMAND\@mpfnpos	233
COMMAND\@msd	327
COMMAND\@msd@c	327
COMMAND\@msd@options@iffullpage	333
COMMAND\@msdata@list	327, 328
COMMAND\@nl	110–112, 114, 115, 125, 163, 280, 435, 436
COMMAND\@nl@reg	111, 377, 436, 441
COMMAND\@opXfeet	436
COMMAND\@opfeetX	446
COMMAND\@opxtrafeeti	446
COMMAND\@page	112, 280
COMMAND\@pend	436
COMMAND\@pendR	436
COMMAND\@ref	110, 120–122, 126, 132
COMMAND\@ref@later	122, 127
COMMAND\@ref@reg	121, 163, 436
COMMAND\@ref@reg@parsearg	122
COMMAND\@reinserts	271–274, 446
COMMAND\@secondoftwo	76
COMMAND\@sect	362
COMMAND\@series	261
COMMAND\@set	115
COMMAND\@sidenotesep	300
COMMAND\@stopmsd	328
COMMAND\@sw	122, 140, 144, 145
COMMAND\@tag	133, 135, 138
COMMAND\@tempcnta	89
COMMAND\@tempcntb	89
COMMAND\@toksa	96
COMMAND\@toksb	96
COMMAND\@xloop	173
COMMAND\@xympar	293, 446
COMMAND\Aendnote	16, 25
COMMAND\Afootfmt	178
COMMAND\Afootgroup	178
COMMAND\Afootnote	8, 16, 24, 25, 28, 135, 186, 211, 234, 251, 445

COMMAND\Afootstart	178
COMMAND\AtBeginDocument	274
COMMAND\AtEndEveryPend	19, 452
COMMAND\AtEveryPend	18, 19, 54, 151, 443, 444, 446, 452
COMMAND\AtEveryPend*	19
COMMAND\AtEveryPstart	18, 19, 54, 443, 444, 446, 449, 452
COMMAND\AtEveryPstart*	19
COMMAND\AtEveryStanza	54, 450, 452
COMMAND\AtEveryStopStanza	55, 450, 452
COMMAND\AtStartEveryPstart	19, 452
COMMAND\AtStartEveryStanza	54, 55, 452
COMMAND\BeforeEveryStopStanza	452
COMMAND\Bendnote	16, 24
COMMAND\Bfootnote	8, 16, 211, 234, 251
COMMAND\Centering	47
COMMAND\Cfootnote	211
COMMAND\Columns	89, 183
COMMAND\Dfootnote	211
COMMAND\Efootnote	211
COMMAND\Gls	68
COMMAND\Hy@raisedlink	372
COMMAND\Hy@raisedlink@left	372
COMMAND\LTR	47
COMMAND\NR	362
COMMAND\Pages	89, 272, 273
COMMAND\ProcessOptionsX	79
COMMAND\RL	46
COMMAND\RaggedLeft	47
COMMAND\RaggedRight	47
COMMAND\RenewExpandableDocumentCommand	33, 143
COMMAND\SEonlypage	287, 448
COMMAND\SEref	61–63, 287, 290, 449, 451
COMMAND\SErefonlypage	61–63, 383, 448
COMMAND\SErefwithpage	61, 63, 287, 290, 383, 448, 450
COMMAND\Stanza	441
COMMAND\Waklam	350
COMMAND\X@doreinfeet	273, 446
COMMAND\XR@prefix	293
COMMAND\XR@test	293
COMMAND\XR@test@mac	293
COMMAND\XR@test@mac@test	293
COMMAND\XXXXXXfmt	376
COMMAND\XXXXXfmt	376
COMMAND\Xafternumber	42
COMMAND\Xafterlemmaseparator	44, 380
COMMAND\Xafternote	48, 379, 380
COMMAND\Xafternumber	42, 380
COMMAND\Xafterrule	49, 234, 380, 441, 444
COMMAND\Xaftersymlinenum	42, 43, 380
COMMAND\Xarrangement	38, 48, 75, 178, 179, 263, 380

COMMAND\Xarrangement@footparagraph	184
COMMAND\Xarrangement@normal	179
COMMAND\Xarrangement@paragraph	184
COMMAND\Xbeforeinserting	47
COMMAND\Xbeforelemmaseparator	44, 380
COMMAND\Xbeforenotes	49, 234, 380, 441, 444
COMMAND\Xbeforenumber	40, 42, 380
COMMAND\Xbeforesymlinenum	42, 43, 380
COMMAND\Xhookendnote	381
COMMAND\Xhookgroup	49, 448, 449
COMMAND\Xhooknote	47, 381, 382, 447
COMMAND\Xboxendlinenum	43, 44, 381, 445
COMMAND\Xboxlinenum	43, 44, 381
COMMAND\Xboxlinenumalign	43, 44, 381, 445
COMMAND\Xboxstartlinenum	43, 44, 381, 445
COMMAND\Xboxsymlinenum	43, 381
COMMAND\Xcolalign	47, 444
COMMAND\Xdo@feet	446, 451
COMMAND\Xend	259
COMMAND\XendXafterlemmaseparator	381
COMMAND\XendXbeforelemmaseparator	381
COMMAND\XendXinplaceoflemmaseparator	381
COMMAND\XendXlemmaseparator	381
COMMAND\XendXmorethantwolines	381
COMMAND\XendXtwolines	381
COMMAND\Xendafternumber	42, 447
COMMAND\Xendafterlemmaseparator	45, 381
COMMAND\Xendafternote	51, 449
COMMAND\Xendafternumber	44
COMMAND\Xendafterpagenumbe	450
COMMAND\Xendafterpagenumber	40, 63
COMMAND\XendafterpagenumberSErefonlypage	383
COMMAND\Xendaftersymlinenum	42, 44, 447
COMMAND\Xendhookinplaceofnumber	44, 447
COMMAND\Xendhooklinenumber	44, 447
COMMAND\Xendbeforelemmaseparator	45, 381
COMMAND\Xendbeforelinenum	44
COMMAND\Xendbeforenumber	42, 447
COMMAND\Xendbeforepagenumber	40, 62, 63
COMMAND\XendbeforepagenumberSErefonlypage	62
COMMAND\Xendbeforesymlinenum	42, 44, 447
COMMAND\Xendbhookinplaceofnumber	44, 447
COMMAND\Xendbhooklinenumber	44, 447
COMMAND\Xendbhooknote	47
COMMAND\Xendboxendlinenum	44, 445
COMMAND\Xendboxlinenum	44, 381, 443
COMMAND\Xendboxlinenumalign	44, 381, 445
COMMAND\Xendboxstartlinenum	44, 445
COMMAND\Xendboxsymlinenum	43, 447
COMMAND\Xendhangindent	46, 447, 449

COMMAND\Xendinplaceoflemmaseparator	26, 45, 381
COMMAND\Xendinplaceofnumber	43, 446
COMMAND\Xendinplaceofpagenumber	40, 451
COMMAND\Xendinsertsep@	241
COMMAND\Xendlemmadisablefontselection	45
COMMAND\Xendlemmafnt	45, 449
COMMAND\Xendlemmaseparator	26, 44, 381
COMMAND\Xendletboxendlinenum	381
COMMAND\Xendlineflag	63
COMMAND\Xendlinenumannotationposition	57, 63
COMMAND\Xendlineprefixmore	40, 63
COMMAND\Xendlineprefixsingle	40, 63
COMMAND\Xendlinerangeseparator	40, 63, 198, 383, 448
COMMAND\Xendmorethanwolines	26, 41, 63, 381, 444, 445
COMMAND\Xendnonumber	41, 446
COMMAND\Xendnote	237, 257–259, 444
COMMAND\Xendnotefontsize	46, 380
COMMAND\Xendnotenumfont	44, 45, 380
COMMAND\Xendnotes	240
COMMAND\Xendnumberonlyfirstinline	39, 447
COMMAND\Xendnumberonlyfirstintwo	39, 447
COMMAND\Xendpagenumberonlyfirst	39, 451
COMMAND\Xendpagenumberonlyfirstifsingle	39, 451
COMMAND\Xendpagenumberonlyfirstintwo	40, 451
COMMAND\Xendparagraph	51, 441
COMMAND\Xendsep	51
COMMAND\Xendsublinesep	42, 63, 198
COMMAND\Xendsymlinenum	39, 447
COMMAND\Xendsympagenum	40, 451
COMMAND\Xendtwolines	26, 41, 63, 381, 444, 445
COMMAND\Xendtwolinesbutnotmore	41, 63, 444, 445
COMMAND\Xendtwolinesonlyinsamepage	41, 63, 444, 445
COMMAND\Xendtxtbeforenotes	49, 453
COMMAND\Xendwrapcontent	46, 450
COMMAND\Xendwraplemma	46, 450
COMMAND\Xendwraplinenumannotation	58, 63
COMMAND\Xfootfmt	382
COMMAND\Xfootgroup	183
COMMAND\Xfootins	182
COMMAND\Xfootnote	60, 66, 133, 376, 438, 442, 444, 448, 450
COMMAND\Xfootstarts	183
COMMAND\Xgroupbyline	48, 171, 210
COMMAND\Xgroupbylines	451
COMMAND\Xgroupbylinesparetwolines	48
COMMAND\Xhangindent	46, 447
COMMAND\Xsize	383, 448, 449
COMMAND\Xsizethreecol	47, 50, 381
COMMAND\Xsizetwocol	47, 50, 264, 381
COMMAND\Xinplaceoflemmaseparator	25, 44, 381
COMMAND\Xinplaceofnnumber	43, 381, 444, 445

COMMAND\Xinsertparafootsep	189, 191
COMMAND\Xledsetnormalparstuff	378, 379, 444
COMMAND\Xlemmadisablefontselection	45
COMMAND\Xlemmafont	45, 449
COMMAND\Xlemmaseparator	44, 198, 265, 268, 270, 381
COMMAND\Xlineflag	62, 383, 384, 450
COMMAND\Xlinenumannotationposition	57, 63, 162
COMMAND\Xlinenumannotationposition@side	162
COMMAND\Xlinenumannotationpositionsides	57
COMMAND\Xlinerangeseparator	40, 63, 198, 383, 448
COMMAND\Xmaxhnotes	50, 74, 75, 380, 381, 441, 443
COMMAND\Xmorethanwolines	25, 40, 41, 63, 381, 443
COMMAND\Xnoindent	447
COMMAND\Xnolemmaseparator	44, 270, 381
COMMAND\Xnonbreakableafternumber	42, 381, 439
COMMAND\Xnonumber	41, 381
COMMAND\Xnonumberinfofootnote	381
COMMAND\Xnotefontsize	45, 380
COMMAND\Xnotefontsize@(< s)	189, 193, 195
COMMAND\Xnotenumfont	45, 380
COMMAND\Xnoteswidthliketwocolumns	50, 442
COMMAND\Xnumberonlyfirstinline	39, 40, 48, 107, 200, 264, 265, 268, 381, 438, 443, 452
COMMAND\Xnumberonlyfirstintwolines	39, 48, 381, 438, 452
COMMAND\Xonlypststart	41, 381, 438, 443
COMMAND\Xpagelinesep	42, 451
COMMAND\Xparafootsep	48, 107, 380, 381, 450, 452
COMMAND\Xparafootsep@series	189
COMMAND\Xparinden	383
COMMAND\Xparindent	46, 444, 447, 449
COMMAND\Xprenotes	49, 235, 450
COMMAND\Xprenotes@	182, 235, 438
COMMAND\Xpstart	41, 378, 381, 438, 443
COMMAND\Xpstarteverytime	41, 378, 381, 443
COMMAND\Xragged	48
COMMAND\Xrigidbalance	191, 383, 448
COMMAND\Xstanza	42, 55
COMMAND\Xstanzaseparator	42
COMMAND\Xstorelineinfo	200
COMMAND\Xsublinesep	22, 42, 63, 198, 383
COMMAND\Xsublinesepside	22, 42
COMMAND\Xsymlineum	39, 48, 380, 381, 445, 452
COMMAND\Xtextbeforenotes	173
COMMAND\Xtoendnotes	27, 258
COMMAND\Xtwolines	25, 40, 41, 63, 206, 207, 264, 381, 443
COMMAND\Xtwolinesappref	264
COMMAND\Xtwolinesbutnotmore	41, 63, 381, 444
COMMAND\Xtwolinesbutnotmoreappref	265
COMMAND\Xtwolinesonlyinsamepage	41, 63, 381, 444
COMMAND\Xtxtbeforenotes	49, 381, 450, 451, 453
COMMAND\Xtxtbeforenotesonlyonce	49, 453

COMMAND\Xunvxh	187, 382
COMMAND\Xwidth	50, 383, 449
COMMAND\Xwrapcontent	46, 450
COMMAND\Xwraplemma	46, 47, 450
COMMAND\Xwraplinenumannotation	57, 58, 63, 163
COMMAND\Xwraplinenumannotation@ref	163
COMMAND\Xwraplinenumannotation@side	163
COMMAND\Xwraplinenumannotationref	58
COMMAND\Xwraplinenumannotationside	57
COMMAND\&	380
COMMAND\absline@num	104, 159
COMMAND\accent	132
COMMAND\actionlines@list	105, 161
COMMAND\actions@list	105
COMMAND\add@Xgroupbyline	171
COMMAND\add@inserts	105, 170, 171
COMMAND\add@inserts@next	170
COMMAND\add@msd@	327
COMMAND\add@msdata	327, 328
COMMAND\add@msdata@firstlineofpage	330
COMMAND\add@msddata	327
COMMAND\add@penalties	159, 172
COMMAND\addcontentsline	357
COMMAND\addfootins	376, 379
COMMAND\addfootinsX	376, 379
COMMAND\addtoendnotes	258
COMMAND\advancelabel@refs	279
COMMAND\advanceline	23, 106, 114, 128, 446
COMMAND\affixlin@num	300
COMMAND\affixline@num	164, 167, 168, 436
COMMAND\affixpstart@num	168
COMMAND\afterXrule	380
COMMAND\afterXsymlinenum	380
COMMAND\aftergroup	131, 136
COMMAND\afterlemmaseparator	380
COMMAND\afternote	380
COMMAND\afternoteX	48, 379, 380
COMMAND\afternumberinfofootnote	380
COMMAND\afterruleX	49, 441, 444
COMMAND\annot@list	106, 164
COMMAND\annotationref	57, 58
COMMAND\annotref	59
COMMAND\applabel	62, 281, 282, 444, 450
COMMAND\appref	60, 62, 63, 287, 290, 448, 449
COMMAND\apprefprefixmore	62, 380
COMMAND\apprefprefixsingle	62, 380
COMMAND\apprefwithpage	62, 63, 287, 290, 445, 448
COMMAND\arrangementX	38, 75, 215, 263, 380
COMMAND\arrangementX@normal	221
COMMAND\article	15

COMMAND\at@every@pend	151
COMMAND\autopar	18, 148, 152, 153, 231, 437, 439, 440, 444
COMMAND\ballast	75
COMMAND\ballast@count	159, 172
COMMAND\baselineskip	38, 185, 189
COMMAND\beforeXnotes	380
COMMAND\beforeXsymlinenum	380
COMMAND\beforeeledchapter	10, 72, 358, 359
COMMAND\beforeinsertingX	47
COMMAND\beforelemmaseparator	380
COMMAND\beforenotesX	49, 382, 440, 441, 444
COMMAND\beforenumberinfootnote	380
COMMAND\begin	335
COMMAND\beginnumbering	
17, 19, 20, 90, 91, 94, 95, 103, 108, 124, 152, 237, 326, 438, 441, 445, 446, 451, 452	
COMMAND\beginnumberingR	90
COMMAND\bf	438
COMMAND\bfsries	45, 438
COMMAND\bhookXnote	381
COMMAND\bhookgroupX	49, 448
COMMAND\bhooknoteX	47, 382, 447
COMMAND\body	318
COMMAND\bodyfootmarkA	35
COMMAND\book	15
COMMAND\boxXendlinenum	381
COMMAND\boxXendlinenumalign	381
COMMAND\boxXendstartlinenum	381
COMMAND\boxendlinenum	381
COMMAND\boxlinefootnote	202
COMMAND\boxlinenum	381
COMMAND\boxlinenumalign	381
COMMAND\boxstartlinenum	381
COMMAND\boxsymlinenum	381
COMMAND\break	39, 187
COMMAND\brokenpenalty	172
COMMAND\centering	47
COMMAND\ch@ck@l@ck	436
COMMAND\ch@cksub@l@ck	167, 436
COMMAND\chapter	71, 360, 364, 441, 444, 446, 450
COMMAND\chapterterm	358
COMMAND\check@pb@in@verse	371
COMMAND\colalignX	47, 444
COMMAND\collect@body	335
COMMAND\color	450
COMMAND\colorbox	76
COMMAND\columns	50
COMMAND\columnwidth	185, 442
COMMAND\command names	264
COMMAND\copyright	132
COMMAND\correct@Xfootins@box	443

COMMAND\correct@footinsX@box	443
COMMAND\count	193
COMMAND\critex	437
COMMAND\critext	139, 375, 376, 379
COMMAND\csname	80, 142
COMMAND\csquotes	255
COMMAND\ctab	351, 356
COMMAND\ctabtext	356
COMMAND\current@annot	163
COMMAND\dcol	345
COMMAND\def	77, 93
COMMAND\detokenize	142
COMMAND\dimen	193
COMMAND\dimexpr	50
COMMAND\discretionary	186
COMMAND\displaywidowpenalty	172
COMMAND\do@Xfeet	272, 436, 446, 451
COMMAND\do@actions	159, 161, 436
COMMAND\do@actions@fixedcode	436
COMMAND\do@actions@next	159, 161
COMMAND\do@ballast	159, 172
COMMAND\do@feet@custom@order	271
COMMAND\do@insidelinehook	439
COMMAND\do@line	105, 131, 150, 153, 157, 158, 170, 172, 318, 436, 437, 439, 441
COMMAND\do@linehook	436
COMMAND\do@lockoff	106
COMMAND\do@lockon	106
COMMAND\dodoreinxtrafeet	435
COMMAND\doendnotes	26, 241, 382, 445, 452
COMMAND\doendnotesbysection	26, 241, 259, 445, 452
COMMAND\doennotes	452
COMMAND\doinsidelinehook	24, 442
COMMAND\dolinehook	24, 442
COMMAND\doreinxtrafeeti	446
COMMAND\doreinxtrafeeti	446
COMMAND\doxtrafeet	271, 435
COMMAND\doxtrafeeti	446
COMMAND\doxtrafeeti	446
COMMAND\dummy@ref	132
COMMAND\edaftertab	70, 351, 352
COMMAND\edannotationref	284
COMMAND\edatleft	70, 349
COMMAND\edatright	70, 71, 349
COMMAND\edbforetab	70, 351
COMMAND\edfilldimen	350
COMMAND\edfont@info	138
COMMAND\edgls	68, 307
COMMAND\edglsadd	452
COMMAND\edgls...	449
COMMAND\edindex	33, 66–68, 307, 308, 311, 313, 339, 439, 442, 443, 446, 447, 451–453

COMMAND\edindexlab	67
COMMAND\edlabel	59–
62, 64, 132, 277, 279, 280, 283, 284, 292, 307, 339, 372, 384, 435, 438–440, 443, 448, 453	
COMMAND\edlabelE	61, 282
COMMAND\edlabelS	61, 282
COMMAND\edlabelSE	61
COMMAND\edlineref	59, 277, 381, 443, 445, 448, 452
COMMAND\edmakelabel	61, 292
COMMAND\edpageref	59, 277, 283, 292
COMMAND\edrowfill	350
COMMAND\edsublineref	59
COMMAND\edtabcolsep	344
COMMAND\edtext	7, 24, 25, 27, 28, 30–32, 51, 56, 59, 60, 62, 66, 68, 75, 105, 106, 120–122, 125–127, 130–139, 141, 142, 144, 146, 162–164, 281, 282, 286, 339, 341, 360, 372, 375, 376, 379, 435, 437, 439, 441–445, 451–453
COMMAND\edtext@level	445
COMMAND\edtextlater	123
COMMAND\edvertdots	71, 349
COMMAND\edvertline	71, 349
COMMAND\elechapter	72
COMMAND\eled@sectioning@out	365
COMMAND\eledchapter	71, 379, 442, 446
COMMAND\eledchapter*	71
COMMAND\eledmac@error	435
COMMAND\eledsection	7, 16, 72, 132, 156, 358, 379, 444, 452
COMMAND\eledsection*	72
COMMAND\eledsubsection	72, 379
COMMAND\eledsubsection*	72
COMMAND\eledsubsubsection	72, 379
COMMAND\eledsubsubsection*	72
COMMAND\eledxxx	10, 72, 364, 365, 441
COMMAND\eledxxxx	358
COMMAND\elesection	365
COMMAND\else	306, 358
COMMAND\emph	33
COMMAND\empty	89, 165, 277
COMMAND\end	334, 335
COMMAND\end@lemmas	131
COMMAND\endashchar	198
COMMAND\endgraf	150, 189, 231
COMMAND\endlock	22, 106, 129, 322
COMMAND\endminipage	301, 304, 435, 446
COMMAND\endmsdata	35
COMMAND\endnotes	444, 448
COMMAND\endnumbering	17, 20, 90, 91, 93, 94, 124, 436, 445, 451, 452
COMMAND\endnumberingR	90
COMMAND\endprint	237, 240, 259, 378
COMMAND\endstanzaextra	380
COMMAND\endsub	22, 106, 128
COMMAND\endverse	382

COMMAND\everypar	152
COMMAND\extensionchars	73, 90
COMMAND\externaldocument	64, 293
COMMAND\f@x@l@cks	436
COMMAND\falseverse	379, 439, 441
COMMAND\fi	358
COMMAND\firstlinenum	21, 164, 437
COMMAND\firstsublinenum	21, 437
COMMAND\fix@page	111, 112, 436
COMMAND\flag@end	126, 127, 137, 441
COMMAND\flag@end@RTL	127
COMMAND\flag@end@later	127
COMMAND\flag@start	126, 127, 137, 441, 442
COMMAND\flag@start@RTL	127
COMMAND\flag@start@later	127
COMMAND\flagstanza	58
COMMAND\floatingpenalty	178, 443
COMMAND\flush@notes	172, 173
COMMAND\fnpos	37, 233, 440, 451
COMMAND\footfmt	177, 180
COMMAND\footfmt...	216
COMMAND\footfootmarkA	35
COMMAND\footfudgefactor	187
COMMAND\footfudgefiddle	75, 185, 435
COMMAND\footgroup	177
COMMAND\footins	182
COMMAND\footnormal	263, 380, 435
COMMAND\footnormalX	380
COMMAND\footnote	35, 74, 212, 213, 377, 436
COMMAND\footnote@lang	198
COMMAND\footnoteA	16, 35
COMMAND\footnoteB	16
COMMAND\footnoteC	24
COMMAND\footnoteE	35
COMMAND\footnoteX	8, 36, 255, 257, 451
COMMAND\footnoteX@reading	256
COMMAND\footnoteXmark	257, 452
COMMAND\footnoteXmk	270
COMMAND\footnoteXtext	257, 452
COMMAND\footnote(X)	133
COMMAND\footnote(X)mark	36
COMMAND\footnote(X)mk	36
COMMAND\footnote(X)nomk	36
COMMAND\footnote(X)text	36
COMMAND\footnotelang@lua	176
COMMAND\footnotelang@poly	177
COMMAND\footnotemark	36, 257
COMMAND\footnoteoption@	176, 447
COMMAND\footnoterule	193
COMMAND\footnotesize	45, 46

COMMAND\footnotetext	36, 257
COMMAND\footparagraph	185, 263, 380, 441
COMMAND\footparagraphX	226, 380, 441
COMMAND\footprints skips	436, 443
COMMAND\footstart	177, 182, 193
COMMAND\footstrut	189
COMMAND\footthreecol	380
COMMAND\footthreecolX	380, 445
COMMAND\foottwoocol	380
COMMAND\footwoocolX	380, 445
COMMAND\foreignlanguage	46
COMMAND\fullstop	383
COMMAND\get@edindex@hyperref	312
COMMAND\get@edindex@ledinnote@command	308
COMMAND\get@fnmark	213
COMMAND\get@index@command	440
COMMAND\get@linelistfile	436
COMMAND\get@thisfootnote	220
COMMAND\getline@num	158, 160
COMMAND\gl@p	96
COMMAND\global	110
COMMAND\globaldefs	110
COMMAND\gls	68, 315
COMMAND\hangindentX	46, 444, 447
COMMAND\hangingsymbol	380, 437
COMMAND\hbox	186, 187
COMMAND\hfill	440
COMMAND\hidenumbering	23, 119, 444
COMMAND\hidenumberingonleftpage	23, 119, 450
COMMAND\hidenumberingonrightpage	23, 119, 450
COMMAND\hline	68
COMMAND\hrulefill	350
COMMAND\hsize	39, 182, 185–187, 193, 196, 232, 436, 442
COMMAND\hsizeX	383, 448, 449
COMMAND\hsizethreecol	381
COMMAND\hsizethreecolX	48, 50
COMMAND\hsizetwocol	381
COMMAND\hsizetwocolX	48, 50
COMMAND\hyperlinkR	312
COMMAND\hyperlinkformat	312
COMMAND\hyperlinkformatR	312
COMMAND\if@RTL	81, 135
COMMAND\if@edtext@	442, 445
COMMAND\if@eled@sectioning	364
COMMAND\if@firstlineofpage	81
COMMAND\if@firstlineofpageR	81
COMMAND\if@msd@options@fullpage	333
COMMAND\if@msdata@insertedfrompreviouspage	330
COMMAND\if@nobreak	151
COMMAND\if@noneed@Footnote	125

COMMAND\ifXnote@	90
COMMAND\ifafterendnumberingR	90
COMMAND\ifbypage@	97
COMMAND\ifbypage@R	97
COMMAND\ifbypstart@	97
COMMAND\ifbypstart@R	97
COMMAND\iffirst@linenum@out@	123, 124
COMMAND\ifindtl@innote	90
COMMAND\ifindtl@notenumber	90
COMMAND\ifinserthangingsymbol	318
COMMAND\ifinstanza	317
COMMAND\ifistwofollowinglines	207, 208
COMMAND\ifl@d@Xmorethan two lines	204, 443
COMMAND\ifl@d@Xtwolines	204
COMMAND\ifl@d@dash	203
COMMAND\ifl@d@elin	203
COMMAND\ifl@d@esl	203
COMMAND\ifl@d@pnum	203
COMMAND\ifl@d@ssub	203
COMMAND\ifl@dend@X	257
COMMAND\ifl@dmemoir	435
COMMAND\ifl@dpaging	442
COMMAND\ifl@dpairing	89, 437
COMMAND\ifl@dprintingpages	443
COMMAND\ifl@dskipnumber	164
COMMAND\ifl@dstartendok	350
COMMAND\ifl@imakeidx	81
COMMAND\ifledRcol	89, 437
COMMAND\ifledRcol@	89, 441
COMMAND\iflemmacommand@	442
COMMAND\ifnoend@	242
COMMAND\ifnoledgroup@	306
COMMAND\ifnoteschanged@	107
COMMAND\ifnumberedpar@	147
COMMAND\ifnumbering	91, 94
COMMAND\ifnumberingR	90, 437
COMMAND\ifnumberline	137, 164
COMMAND\ifpst@rted	437
COMMAND\ifpst@rtedL	91
COMMAND\ifresumenumerating@start	94
COMMAND\ifseriesbefore	261
COMMAND\ifstopmsdata@inserted@	326
COMMAND\ifsublines@	104, 116
COMMAND\iftrue	445
COMMAND\ifvmode	279
COMMAND\ifxxx	358
COMMAND\ignorespaces	135
COMMAND\imki@wrindexentry	81
COMMAND\immediate	123, 124, 236
COMMAND\indent	18, 152, 382

COMMAND\index	314, 315, 451
COMMAND\indtl@wrindexentry	81
COMMAND\initnumbering@quote	356, 446
COMMAND\initnumbering@reg	436
COMMAND\initnumbering@sectcmd	446
COMMAND\inplaceoflemmaseparator	381
COMMAND\inplaceofnumber	381
COMMAND\insert	137, 169, 177, 180, 194, 210, 216
COMMAND\insert@Txtbeforenotes	174, 194
COMMAND\insert@count	120, 126, 135
COMMAND\insert@countR	135
COMMAND\insert@msdata	327, 333
COMMAND\insert@txtbeforenotesX	174
COMMAND\inserthangingsymbol	440
COMMAND\insertlines@list	105, 120, 121
COMMAND\insertparafootsepX	230
COMMAND\inserts@list	131, 148, 170, 186
COMMAND\interAfootnotelinepenalty	437
COMMAND\interfootnotelinepenalty	437
COMMAND\interlinepenalty	178
COMMAND\interparanoteglue	379
COMMAND\justifying	47
COMMAND\l@advance@parledegroup@beforenormalnotes	446
COMMAND\l@d@@wrindexhyp	442
COMMAND\l@d@add	140
COMMAND\l@d@end	237, 257
COMMAND\l@d@nums	135, 137, 139, 140, 203, 204
COMMAND\l@d@section	237
COMMAND\l@d@set	115, 129
COMMAND\l@d@dampcount	341
COMMAND\l@dbfnote	213, 436
COMMAND\l@d@checkstartend	350
COMMAND\l@d@chset@num	115
COMMAND\l@d@colcount	341, 342
COMMAND\l@d@collect@@body	335
COMMAND\l@d@collect@body	334
COMMAND\l@d@csnote	441
COMMAND\l@d@csnotetext	157, 297, 298
COMMAND\l@d@csnotetext@l	157, 297, 298
COMMAND\l@d@csnotetext@r	157, 297, 298
COMMAND\l@ddodoreinxtrafeet	272, 435
COMMAND\l@ddoxtrafeet	272, 435
COMMAND\l@demptyd@ta	437
COMMAND\l@dend@close	236
COMMAND\l@dend@open	236
COMMAND\l@dend@stuff	237
COMMAND\l@denvbody	335
COMMAND\l@feetbeginmini	435
COMMAND\l@feetendmini	435
COMMAND\l@dgetline@margin	437

COMMAND\l@dgetlock@disp	437
COMMAND\l@dgetref@num	285
COMMAND\l@dgetsidenote@margin	294, 437
COMMAND\l@dgobbleloptarg	442
COMMAND\l@dgobblearg	442
COMMAND\l@dgobbleoptarg	340
COMMAND\l@dlabel@parse	285
COMMAND\l@dld@ta	164, 166
COMMAND\l@dlp@rbox	299
COMMAND\l@dlsn@te	437
COMMAND\l@dsnote	441
COMMAND\l@dmake@labels	279, 280, 293
COMMAND\l@dmake@labelsR	293
COMMAND\l@dnumpstartsL	91, 437
COMMAND\l@dp@rsefootspec	204
COMMAND\l@dparsefootspec	204
COMMAND\l@dpush@begins	335
COMMAND\l@drd@ta	164, 166
COMMAND\l@dref@undefined	285
COMMAND\l@drsn@te	437
COMMAND\l@drsnote	441
COMMAND\l@dtabaddcols	350
COMMAND\l@dtabnoexpands	435
COMMAND\l@dumboxmpfoot	446
COMMAND\l@dunboxmpfoot	437
COMMAND\l@dzopenalties	437, 442
COMMAND\l@pb	371
COMMAND\l@prev@nopb	370
COMMAND\l@prev@pb	370
COMMAND\l@reg	377
COMMAND\l@wrap@ifnotemptybox	88
COMMAND\label	19, 61, 64, 67, 277, 278, 286
COMMAND\label@refs	277
COMMAND\labelpstarttrue	19, 384, 438, 453
COMMAND\labelref@list	277, 280
COMMAND\language	186
COMMAND\last@page@num	436
COMMAND\lastbox	152
COMMAND\lastskip	128
COMMAND\latex@makecol	274
COMMAND\leavevmode	18, 152
COMMAND\led@check@nopb	371
COMMAND\led@check@pb	371
COMMAND\led@nopb	370, 371
COMMAND\led@nopbnum	370
COMMAND\led@pb	370, 371
COMMAND\led@pb@macro	370
COMMAND\led@pbnum	370
COMMAND\led@reinit@index@fornote	315
COMMAND\led@set@index@fornote	314

COMMAND\ledRflag	312
COMMAND\ledchapter	379, 439
COMMAND\ledfootinsdim	380
COMMAND\ledininnernote	64, 295, 441, 450
COMMAND\ledinnote	309, 378, 445
COMMAND\ledinnotemark	66, 378, 444
COMMAND\ledleftnote	64, 295
COMMAND\ledlinenum	102, 437
COMMAND\ledllfill	158
COMMAND\ledlsnotefontsetup	450
COMMAND\ledlsnotesep	65
COMMAND\ledlsnotewidth	64
COMMAND\lednopb	73, 370
COMMAND\lednopbinverse	371
COMMAND\lednopbinversetrue	54, 73
COMMAND\lednopbnum	370
COMMAND\ledouternote	64, 295, 441, 450
COMMAND\ledpb	73, 370, 379
COMMAND\ledpbnum	370
COMMAND\ledpbsetting	73, 370, 447
COMMAND\ledrightnote	64, 295
COMMAND\ledrsnotefontsetup	450
COMMAND\ledrsnotesep	65
COMMAND\ledrsnotewidth	64
COMMAND\ledsection	379
COMMAND\ledsectnomark	358
COMMAND\ledsectnotoc	357
COMMAND\ledsetnormalparstuff	378, 379, 444
COMMAND\ledsetnormalparstuff@common	231
COMMAND\ledsetnormalparstuffX	378, 379, 444
COMMAND\ledsidenote	64, 295, 297, 298
COMMAND\ledsubsection	379
COMMAND\ledsubsubsection	379
COMMAND\ledxxx	441
COMMAND\left	70
COMMAND\leftctab	351
COMMAND\leftheadline	102
COMMAND\leftlinenum	22, 102, 435, 437
COMMAND\leftltab	351
COMMAND\leftnoteupfalse	65
COMMAND\leftpstartnum	168
COMMAND\leftrtab	351
COMMAND\leftsidenote	298
COMMAND\leftskip	182, 186, 187
COMMAND\lemma	3, 25, 27, 28, 30–32, 130, 134, 135, 138, 139, 141, 375, 437, 438, 445, 446, 448
COMMAND\lemmaseparator	381
COMMAND\let	28, 51, 133, 137, 257, 274, 322, 435
COMMAND\letboxXendlinenum	381
COMMAND\line	191, 195
COMMAND\line@list	105, 106, 121, 137

COMMAND\line@list@stuff	91, 108, 124, 435, 437
COMMAND\line@list@version	110
COMMAND\line@margin	98, 166, 294
COMMAND\line@num	103, 104, 106, 164, 435
COMMAND\line@set	139, 140
COMMAND\lineannot	57, 60, 140
COMMAND\lineannot@set	140
COMMAND\lineation	21, 97, 453
COMMAND\linebreak	39
COMMAND\lineneation	449
COMMAND\linenum	25, 27, 28, 57, 60, 62, 130, 139, 140, 283, 286, 293, 375
COMMAND\linenum@out	123, 277, 280
COMMAND\linenumannotation	56, 162
COMMAND\linenumberannotation	453
COMMAND\linenumberlist	21, 89, 165, 435
COMMAND\linenumberstyle	23, 102, 435, 452
COMMAND\linenumincrement	21, 437
COMMAND\linenummargin	21, 98, 294
COMMAND\linenumr@p	101, 435, 437
COMMAND\linenumrep	101, 102, 437
COMMAND\linenumsep	22, 65, 102, 295
COMMAND\linerangesep@	270
COMMAND\lineref	277, 283, 292, 381, 443
COMMAND\list@clear	96
COMMAND\list@clearing@reg	437
COMMAND\list@create	96
COMMAND\lock@disp	100
COMMAND\lock@off	118
COMMAND\lock@on	117
COMMAND\lockdisp	22, 100
COMMAND\loop	173, 318
COMMAND\ltab	351, 352, 356
COMMAND\ltabtext	356
COMMAND\m@mmf@prepare	212
COMMAND\makeatletter	157
COMMAND\makehboxofhboxes	188, 189
COMMAND\makeindex	66, 311
COMMAND\makelabel	292
COMMAND\managestanza@modulo	319
COMMAND\marginpar	64, 74, 293, 294, 436
COMMAND\marginparwidth	64, 295
COMMAND\markboth	157
COMMAND\mathchardef	319
COMMAND\maxhXnotes	381
COMMAND\maxhnotesX	50, 75, 380, 440, 441, 443–445
COMMAND\maxlinesinpar@list	108
COMMAND\measurembdy	353
COMMAND\measuretbdy	353
COMMAND\memorybreak	20
COMMAND\metaXXXvfootnote	210

COMMAND\morenoexpands	75, 76, 131, 132
COMMAND\morethantwolines	381
COMMAND\mpfnpos	37, 233, 440, 451
COMMAND\mpnnormalfootgroup	435
COMMAND\mpnnormalvfootnote	436
COMMAND\msdata	34, 35, 325–327, 452
COMMAND\msdataposition	35
COMMAND\multfootsep	36, 212
COMMAND\multiplefootnotemarker	212
COMMAND\musixtex	441
COMMAND\n@num	437, 444
COMMAND\n@num@ref	444
COMMAND\new@line	125, 436
COMMAND\new@series	133
COMMAND\newcommand	28, 77, 93, 212, 280
COMMAND\newcommandx	28, 29
COMMAND\newhookarg@specific	270
COMMAND\newhookcommand@series	264, 265, 444
COMMAND\newhookcommand@series@reload	265
COMMAND\newhookcommand@toggle@reload	265, 442
COMMAND\newhooktoggle@series	264, 265, 444
COMMAND\newhooktoggle@specific	270
COMMAND\newif	444
COMMAND\newline	39
COMMAND\newlinechar	258
COMMAND\newseries	36, 376, 379, 380
COMMAND\newseries@	249, 262
COMMAND\newverse	54, 58, 379, 441, 452
COMMAND\next	318
COMMAND\next@action	109
COMMAND\next@actionline	109
COMMAND\next@insert	170
COMMAND\next@line@list@stuff	124, 453
COMMAND\next@page@num	94
COMMAND\nl@regR	111
COMMAND\no@expands	75, 133, 138, 257, 435
COMMAND\noXlemmaseparator	381
COMMAND\nobreak	203
COMMAND\nocritical	249
COMMAND\ noeledsec	72, 379
COMMAND\noendnotes	379
COMMAND\noexpand	377
COMMAND\nofamiliar	267
COMMAND\noident	18, 19, 54, 55, 152, 447
COMMAND\noidentX	447
COMMAND\nomk@	270
COMMAND\nonbreakableafternumber	381
COMMAND\nonumberinfootnote	381
COMMAND\norelax	52
COMMAND\normal@footnotemarkX	216

COMMAND\normal@page@break	370
COMMAND\normal@pars	231
COMMAND\normalbfnoteX	437
COMMAND\normalbodyfootmarkX	216
COMMAND\normalfont	451
COMMAND\normalfootfmt	51, 182, 189, 198, 237, 450
COMMAND\normalfootfmtX	217
COMMAND\normalfootfootmarkX	217
COMMAND\normalfootgroup	183
COMMAND\normalfootgroupX	218
COMMAND\normalfootnoterule	178
COMMAND\normalfootstart	182, 186
COMMAND\normalfootstartX	217
COMMAND\normalvfootnote	180, 181
COMMAND\normalvfootnote@inserted	180, 181
COMMAND\normalvfootnoteX	216
COMMAND\notbool	358
COMMAND\notefontsetup	380
COMMAND\notefontsizeX	46, 380
COMMAND\notenumberfont	380
COMMAND\notenumberfontX	45, 380
COMMAND\notesXwidthliketwocolumns	381
COMMAND\noteswidthliketwocolumnsX	50, 381, 442, 444
COMMAND\num@lines	147, 172
COMMAND\numberlinefalse	20
COMMAND\numberlinetrue	20
COMMAND\numberonlyfirstinline	262, 381
COMMAND\numberonlyfirstintwo-lines	381
COMMAND\numberpstartfalse	19
COMMAND\numberpstarttrue	19, 41, 378, 438, 446, 452
COMMAND\numberstanza	42
COMMAND\numberstanzafalse	55
COMMAND\numberstanzatru	55
COMMAND\numlabfont	22, 51, 102
COMMAND\one@line	147
COMMAND\onehalfspacing	447
COMMAND\onlyXpstart	381
COMMAND\onlysideX	256
COMMAND\page@action	106, 116
COMMAND\page@start	106, 437
COMMAND\pagecontents	106
COMMAND\pageparbreak	379
COMMAND\pageref	61, 283
COMMAND\par	27, 39, 152, 153, 231
COMMAND\par@line	147, 172
COMMAND\para@footgroup	186
COMMAND\para@footgroupX	229
COMMAND\para@footsetup	185, 435
COMMAND\para@footsetupX	227, 435, 442
COMMAND\para@vfootnoteX	227

COMMAND\parafootfmt	188, 189, 450
COMMAND\parafootfmtX	229
COMMAND\parafootftm	191
COMMAND\parafootftmX	230
COMMAND\parafootftmsep	380
COMMAND\parafootsep	381, 440, 445
COMMAND\parafootsepX	48, 107, 380, 381, 450
COMMAND\parafootstart	186
COMMAND\parafootstartX	227
COMMAND\paravfootnote	186, 189
COMMAND\parfillskip	188
COMMAND\parindent	447
COMMAND\parindentX	46, 383, 447, 449
COMMAND\parse@annot	164
COMMAND\parshape	75
COMMAND\parskip	19, 54, 55, 152
COMMAND\pause@numbering	94
COMMAND\pausenumbering	20, 94, 108, 110, 153, 440, 442, 449
COMMAND\pausenumbering@page@num	94
COMMAND\penalty	188
COMMAND\pend	2, 7, 17–21, 23, 72, 129, 131, 134, 140, 147, 148, 150–153, 168, 169, 377, 440, 441, 450–452
COMMAND\preXnotes	444, 450
COMMAND\prenotesX	49, 236, 444
COMMAND\prepare@Xgroupbyline	210
COMMAND\prepare@Xprenotes	234
COMMAND\prev@nopb	370
COMMAND\prev@pb	370
COMMAND\prevlineX	107
COMMAND\prevpageX@num	107
COMMAND\print@Xfootnoterule	444
COMMAND\print@Xnotes	272, 273
COMMAND\print@Xnotes@forpages	443
COMMAND\print@eledsection	156
COMMAND\print@footnoteXrule	444
COMMAND\print@leftmargin@eledsection	359
COMMAND\print@lemma	199
COMMAND\print@line	154
COMMAND\print@notesX@forpages	443
COMMAND\print@rightmargin@eledsection	359
COMMAND\printendlines	242, 248, 290, 383, 435, 437
COMMAND\printlinefootnote	200, 202, 443
COMMAND\printlinefootnotearea	202, 203, 443
COMMAND\printlinefootnotenumbers	200
COMMAND\printlines	106, 182, 198, 203, 204, 242, 290, 383, 435, 437, 443, 448
COMMAND\printnpnum	378, 383
COMMAND\printpstart	199
COMMAND\protect	132, 377
COMMAND\providecommand	212, 435

COMMAND\pstart	2, 7, 17–21, 23, 71, 72, 115, 129, 134, 140, 147, 148, 150–153, 156, 169, 364, 377, 437–439, 441, 442, 444–446, 449–453
COMMAND\pstartinfofootnote	381
COMMAND\pstartinfofootnoteeverytime	381
COMMAND\pstartnum	168
COMMAND\pstartref	59, 277, 284, 440, 452
COMMAND\pstarts	438
COMMAND\raggedX	48
COMMAND\raggedleft	47
COMMAND\raggedright	47
COMMAND\raw@text	147, 148
COMMAND\rbracket	44
COMMAND\read@linelist	108–110
COMMAND\ref	61, 64, 67
COMMAND\reformatted@	290
COMMAND\reformattedwithpage	290
COMMAND\relax	19, 115, 137, 159, 170, 322, 340, 377
COMMAND\renewcommand	75, 380, 383
COMMAND\reset@current@annot	163
COMMAND\reset@msd@options@iffullpage	333
COMMAND\resetprevline@	107
COMMAND\resetprevpage@	107
COMMAND\resumenumbering	20, 90, 94, 95, 108, 110, 153, 437, 441, 442, 449
COMMAND\right	70
COMMAND\rightctab	351
COMMAND\rightlinenum	22, 102, 435, 437
COMMAND\rightltab	352
COMMAND\rightnoteupfalse	65
COMMAND\rightrtab	352
COMMAND\rightsidenote	297
COMMAND\rightskip	182, 186–188
COMMAND\rightstartnum	168
COMMAND\rigidbalance	191, 193, 195, 383, 448
COMMAND\rigidbalanceX	191, 383, 448
COMMAND\robustify	39
COMMAND\roman	345, 448
COMMAND\rtab	351, 352, 356
COMMAND\rtabtext	353, 356
COMMAND\sameword	16, 29–32, 123, 140–144, 146, 443, 445, 447, 450, 453
COMMAND\sameword@inedtext	142
COMMAND\saweword	141
COMMAND\scriptsize	102
COMMAND\section	71, 437, 451
COMMAND\section@num	90
COMMAND\sectionmark	358
COMMAND\select@lemmafont	51, 175
COMMAND\series	249
COMMAND\series@	249
COMMAND\seriesatbegin	37, 261, 444
COMMAND\seriesatend	37, 261, 444

COMMAND\set@Xtxtbeforenotes	173
COMMAND\set@continuousnumberingfor	95
COMMAND\set@line	137
COMMAND\set@line@action	106, 116
COMMAND\set@txtbeforenotesX	174
COMMAND\setSErefonlypageprefixmore	62, 290, 449, 452
COMMAND\setSErefonlypageprefixsingle	62, 290, 449, 452
COMMAND\setSErefprefixmore	62
COMMAND\setSErefprefixsingle	62
COMMAND\setapprefprefixmore	62, 380
COMMAND\setapprefprefixsingle	62, 380, 448
COMMAND\setcommand@series	263
COMMAND\sethangingsymbol	53, 317, 380, 447
COMMAND\sethanginsymbol	52
COMMAND\setistwoofollowinglines	207
COMMAND\setl@dprbox	299
COMMAND\setline	23, 106, 111, 115, 129, 132, 150, 446
COMMAND\setlinenum	23, 111, 115, 129, 435, 453
COMMAND\setmsdatalabel	35
COMMAND\setmsdataposition	452
COMMAND\setmsdataseries	35
COMMAND\setprintendlines	242, 245, 437
COMMAND\setprintlines	204, 207, 242, 437
COMMAND\setsidenotesep	65
COMMAND\setsidenotsep	380
COMMAND\setstanzaindent	320
COMMAND\setstanzaindents	53, 319, 377
COMMAND\setstanzapenalties	319
COMMAND\setstanzavalues	319
COMMAND\settoggle@series	262, 438, 442
COMMAND\showlemma	132, 435, 436
COMMAND\showwordrank	32, 142
COMMAND\sidenote@margin	436
COMMAND\sidenotemargin	64, 436, 441
COMMAND\sidenotesep	380
COMMAND\sidepstartnumtrue	19
COMMAND\skip	182
COMMAND\skipnumbering	23, 118, 119, 130, 437, 444, 445
COMMAND\skipnumbering@reg	444
COMMAND\small	45, 46
COMMAND\somemacro	33
COMMAND\special	13
COMMAND\splitmaxdepth	178, 193
COMMAND\splitoff	191
COMMAND\splittopskip	178, 193, 195
COMMAND\stanza	22, 23, 54, 55, 58, 322, 380, 382, 447, 452
COMMAND\stanza@hang	321
COMMAND\stanza@line	321
COMMAND\stanzaindent	53, 320, 443
COMMAND\stanzaindent*	53

COMMAND\stanzaindentbase	318, 319
COMMAND\stanzanumwrapper	55
COMMAND\startlock	22, 106, 129, 322
COMMAND\startstanzahook	380
COMMAND\startsub	22, 106, 128
COMMAND\stopmsd	328
COMMAND\stopmsdata	34, 325, 326
COMMAND\store@annot@to@absline	163
COMMAND\strip@pt	185
COMMAND\strutbox	193
COMMAND\sub@action	106, 116
COMMAND\sub@lock	104
COMMAND\sub@off	114, 280
COMMAND\sub@on	114, 280
COMMAND\subline@num	103, 104, 106
COMMAND\sublinenum@rep	435
COMMAND\sublinenumberstyle	23, 102, 435
COMMAND\sublinenumincrement	21
COMMAND\sublinenumr@p	101, 435, 437
COMMAND\sublinenumrep	101, 102, 437
COMMAND\sublineref	59, 277, 283
COMMAND\subsectionmark	358
COMMAND\sw@inthisedtext	134
COMMAND\sw@list@inedtext	138, 146
COMMAND\sw@txt	143
COMMAND\swnoexpands	32, 453
COMMAND\symlinenum	381
COMMAND\symplinenum	380
COMMAND\sza@penalty	321
COMMAND>tag	443
COMMAND{text}	375
COMMAND{text}(language)	46
COMMAND{textbeforenotesX}	174
COMMAND{textcolor}	76
COMMAND{textheight}	75
COMMAND{textsuperscript}	57, 88, 163
COMMAND{the}	435
COMMAND{thefootnoteA}	35
COMMAND{thefootnoteX}	439
COMMAND{thelabidx}	313
COMMAND{thepage}	111
COMMAND{thepstart}	19, 384
COMMAND{thepstartL}	438
COMMAND{thepstartR}	438
COMMAND{thestanza}	55
COMMAND>this@line@list@version	123
COMMAND>thisfootnote	220
COMMAND{threecol}@begin@insert	194
COMMAND{threecolfootfmt}	194, 450
COMMAND{threecolfootfmtX}	225

COMMAND\threecolfootgroup	193
COMMAND\threecolfootgroupX	225
COMMAND\threecolfootsetup	193
COMMAND\threecolfootsetupX	224
COMMAND\threecolvfootnote	193
COMMAND\threecolvfootnote@inserted	193
COMMAND\threecolvfootnoteX	225
COMMAND\toendnotes	26, 240, 450
COMMAND\twocolfootfmt	450
COMMAND\twocolfootfmtX	223
COMMAND\twocolfootgroupX	223
COMMAND\twocolfootsetupX	222
COMMAND\twocolvfootnoteX	222
COMMAND\twolines	262, 381
COMMAND\twolines@A	262
COMMAND\twolines@B	262
COMMAND\twolines@C	262
COMMAND\twolinesbutnotmore	381
COMMAND\twolinesonlyinsamepage	381
COMMAND\txtbeforeXnotes	381
COMMAND\txtbeforenothesX	49, 453
COMMAND\txtbeforenothesonlyonceX	49, 453
COMMAND\uline	36
COMMAND\unhbox	186
COMMAND\unpenalty	188, 189
COMMAND\unskip	188
COMMAND\unvxh	188, 382
COMMAND\unvxhX	382
COMMAND\upbracefill	350
COMMAND\usingcritext	376, 379
COMMAND\usingedtext	376, 379
COMMAND\vAfootnote	178
COMMAND\vadjust	126
COMMAND\variant	28
COMMAND\vbox	150, 152, 187, 191, 233
COMMAND\vfootnote	177, 182, 186, 193
COMMAND\vl@dbfnote	213, 436
COMMAND\vl@disnote	298
COMMAND\vl@dlsnote	298
COMMAND\vl@dosnote	298
COMMAND\vl@drsnote	298
COMMAND\vnumfootnoteX	437
COMMAND\vsizE	50, 75
COMMAND\vspliT	172
COMMAND\waklam	350
COMMAND\waklamec	350
COMMAND\wapunktel	350
COMMAND\wastricht	350
COMMAND\widthX	50, 383, 449
COMMAND\wrap@edcrossref	283, 442

COMMAND\wrapcontentX	46, 450
COMMAND\wrapped@bodyfootmarkX	231
COMMAND\wrapped@footfootmarkX	230
COMMAND\x...	60
COMMAND\xabslineref	284
COMMAND\xannotationref	60
COMMAND\xdef	96, 322
COMMAND\xflagref	60, 284, 383, 448
COMMAND\xleft@appenditem	96, 131
COMMAND\xlineref	60, 383, 448
COMMAND\xpageref	60
COMMAND\xparse	33
COMMAND\xpstartref	60, 440, 453
COMMAND\xr	64
COMMAND\xright@appenditem	96
COMMAND\xsublineref	60
COMMAND\xxref	60, 286, 293, 440, 443, 450
ENVIRONMENTastanza	448
ENVIRONMENTedarrayc	356
ENVIRONMENTedarrayl	356
ENVIRONMENTedarrayr	356
ENVIRONMENTedtabularc	356
ENVIRONMENTedtabularl	356
ENVIRONMENTedtabularr	356
ENVIRONMENTledgroup	81, 305, 383, 448
ENVIRONMENTledgroupsized	305
PACKAGE(r)(e)ledmac	37
PACKAGEEledmac	77, 106, 310, 378, 379, 443, 444
PACKAGEEledpar	444
PACKAGEEtoolbox	80
PACKAGEParallel	385
PACKAGEReledmac	382, 383
PACKAGEamsgen	334
PACKAGEamsmath	334
PACKAGEbabel	46, 76, 345, 448
PACKAGEbiblatex	74
PACKAGEbidi	46, 47, 81, 447
PACKAGEccaption	89
PACKAGEcolor	76
PACKAGEcsquotes	452
PACKAGEedmac	1, 6, 10, 12–14, 77, 203, 211, 277, 319, 375, 385, 435
PACKAGEedstanza	1, 14, 317
PACKAGEeledmac	1, 10, 11, 14, 16, 66, 212, 306, 310, 337, 360, 373, 376, 378–380, 439, 441, 443
PACKAGEeledpar	178, 358, 385, 437, 441–443
PACKAGEetex	447
PACKAGEtoolbox	95, 140, 249, 262, 271, 297, 358, 370
PACKAGEfancyhdr	274, 451
PACKAGEfloatrow	74, 383
PACKAGEfootmisc	36, 76, 81, 212, 385, 451
PACKAGEgeometry	15

PACKAGEglossaries	67, 68, 315, 448
PACKAGEhandout	442
PACKAGEhyperlink	256
PACKAGEhyperref	60, 134, 230, 231, 278, 312, 313, 362, 372, 440–442, 449, 452
PACKAGEifluatex	80
PACKAGEifxetex	80
PACKAGEimakeidx	65, 66, 74, 81, 306, 310, 379, 439–441, 443
PACKAGEindextols	314
PACKAGEindextool	379
PACKAGEindextools	65, 66, 74, 81, 90, 306, 310, 314, 379, 443, 448, 451
PACKAGEinputenc	142
PACKAGEledarab	76
PACKAGEledmac	1, 10, 14, 76, 95, 310, 375, 376, 379, 382
PACKAGEledpar	76
PACKAGEMemoir	81, 310, 379, 385, 442
PACKAGEmorewrites	74
PACKAGEmusixtex	441
PACKAGEperpage	448
PACKAGEpolyglossia	44, 76, 177, 198, 448
PACKAGERagged2e	47, 80
PACKAGEReledmac	1, 2, 11, 12, 14–17, 20, 21, 24, 25, 28–30, 33, 36, 39, 40, 43, 46, 47, 49, 51, 53, 55, 58, 60–62, 64, 65, 67, 68, 72–78, 97, 99, 105, 106, 109, 110, 113, 123, 124, 132, 135, 137, 140, 169, 179, 182, 187, 198, 211, 212, 237, 249, 254, 262, 271, 283, 284, 287, 293, 310, 330, 337, 358, 359, 371, 372, 379, 380, 382–384, 446, 449, 451
PACKAGEReledpar	1, 4, 6, 8, 16, 19, 36, 50, 60, 62, 63, 73, 74, 76, 78, 89, 97, 108, 113, 124, 135, 137, 179, 183, 232, 233, 249, 255, 270, 272, 273, 306, 317, 447, 448, 450, 451, 453
PACKAGESuffix	80
PACKAGETabmac	1, 14, 385
PACKAGEulem	36
PACKAGEuninormalize	29
PACKAGExargs	29, 80
PACKAGExkeyval	78, 270
PACKAGExparse	80
PACKAGEXRI	5, 64, 293, 449
PACKAGEXref	293
PACKAGEXstring	80, 312

A

\absline@num	1
Abu Kamil Shuja' b. Aslam	13
\actionlines@list	1
\actions@list	1
\add@inserts	1
\add@inserts@next	1
\add@msd@	1
\add@msdata	1
\add@msdata@firstlineofpage	1
\add@penalties	1
\add@Xgroupbyline	1
\addtol@envbody	1

Adelard II	13
\advancelabel@refs	1
\advanceline	1, 22
\Aendnote	25
\affixline@num	1
\affixpstart@num	1
\affixside@note	1
\Afootnote	25
\afternoteX	48
\afterruleX	49
\ampersand	1, 58
\annot@list	1
\annotationref	1
\annotref	59
\append@notesX	1
\append@Xnotes	1
\applabel	1, 62
\appref	1, 62
\apprefwithpage	1, 62
\arrangementX	1, 38
\arrangementX@normal	1
\arrangementX@threecol	1
\arrangementX@twocol	1
\at@every@pend	1
\AtEndEveryPend	1, 19
\AtEveryPend	1, 19
\AtEveryPstart	1, 19
\AtEveryStanza	1, 54
\AtEveryStopStanza	1, 55
\AtStartEveryPstart	1, 19
\AtStartEveryStanza	1, 54, 55
\autopar	1, 18

B

\ballast	75
\ballast@count	1
Beeton, Barbara Ann Neuhaus Friend	18
\beforeeledchapter	1
\BeforeEveryStopStanza	1
\beforeinsertingX	47
\beforeinsertion@X	1
\beforenotesX	49
\beginnumbering	1, 17
\Bendnote	25
\Bfootnote	25
\bhookgroupX	49
\bhooknoteX	47
\bodyfootmarkA	35
\boxfootnotenumbers	1
Bredon, Simon	13

Breger, Herbert	13, 14, 337
Brey, Gerhard	13
Busard, Hubert L. L.	13
\bypage@false	1
\bypage@true	1
\bypstart@false	1
\bypstart@true	1

C

\c@addcolcount	1
\c@ballast	1
\c@firstlinenum	1
\c@firstsublinenum	1
\c@labidx	1
\c@linenumincrement	1
\c@sulinenumincrement	1
\Cendnote	25
\Cfootnote	25
\ch@ck@l@ck	1
\ch@cksub@l@ck	1
\chapter	1
\check@pb@in@verse	1
Chester, Robert of	13
Claassens, Geert H. M.	13
\colalignX	47
Copernicus, Nicolaus	13
\critext	375
\ctab	1
\ctabtext	1
\current@annot	1

D

Dekker, Dirk-Jan	76
\Dendnote	25
\Dfootnote	25
\disable@endnotes	1
\disable@familiarnotes	1
\disable@notes	1
\disable@sidenotes	1
\disable@dtabfeet	1
\do@actions	1
\do@actions@fixedcode	1
\do@actions@next	1
\do@ballast	1
\do@feet@custom@order	1
\do@feetX	1
\do@insidelinehook	1
\do@line	1
\do@linehook	1
\do@lockoff	1

\do@lockoffL	1
\do@lockon	1
\do@lockonL	1
\do@Xfeet	1
\doedindexlabel	1
\doendnotes	1, 26
\doendnotesbysection	1, 26
\doinsidelinehook	1, 24
\dolinehook	1, 24
\dosplits	1
Downes, Michael	75, 186, 188
\doxtrafeet	1
\dummy@edindex	1
\dummy@edtext	1
\dummy@edtext@showlemma	1
\dummy@ref	1

E

\edaftertab	1, 70, 351
edarrrayc (environment)	68
edarrrayl (environment)	68
edarrrayr (environment)	68
\edatleft	1, 70
\edatright	1, 70
\edbforetab	1, 70, 351
\edfilldimen	1
\edfont@info	1
\edindex	1, 65
\edindexlab	1, 67
\EDLABEL	1
\edlabel	1, 59
\edlabelE	1, 61
\edlabels	1, 61
\edlabelSE	1, 61
\edlineref	1, 59
\edmakelabel	1, 61
\edpageref	1, 59
\edrowfill	1, 69
\EDTAB	1
\edtabcolsep	1, 69
\EDTABINDENT	1
\edtabindent	1
\EDTABtext	1
edtabularc (environment)	68
edtabularl (environment)	68
edtabularr (environment)	68
\EDTEXT	1
\edtext	1, 24
\edvertdots	1, 71
\edvertline	1, 71

\Eendnote	25
\Efootnote	25
\eled@chapter	1
\eled@section	1
\eled@sectioning@out	1
\eled@subsection	1
\eled@subsubsection	1
\eledchapter	1
\eledchapter*	1
\eledsection	1
\eledsection*	1
\eledsubsection	1
\eledsubsection*	1
\eledsubsubsection	1
\eledsubsubsection*	1
\enablel@dtabfeet	1
\end@lemmas	1
\endashchar	1
\endline@num	1
\endlock	1, 22
\endminipage	1
\endnumbering	1, 17
\endpage@num	1
\endprint	1
\endquotation	1
\endquote	1
\endsub	1, 22
\endsubline@num	1
environments:	
edarrayc	68
edarrayl	68
edarrayr	68
edtabularc	68
edtabularl	68
edtabularr	68
ledgroup	58
ledgroupsized	59
minipage	58
Euclid	13
\extensionchars	1, 73

F

\f@x@l@cks	1
Fairbairns, Robin	36
\first@linenum@out@false	1
\first@linenum@out@true	1
\firstlinenum	1, 21
\firstseriesX@	1
\firstsublinenum	1, 21
\firstXseries@	1

\fix@page	1
\flag@end	1
\flag@end@later	1
\flag@end@RTL	1
\flag@start	1
\flag@start@later	1
\flag@start@RTL	1
\flagstanza	1, 58
\flush@notes	1
\fnpos	1, 37
Folkerts, Menso	13
\footfootmarkA	35
\footfudgefiddle	1, 75
\footnote	1
\footnoteA	35
\footnoteB	35
\footnoteC	35
\footnoteD	35
\footnoteE	35
\footnotelang@lua	1
\footnotelang@poly	1
\footnoteoptions@	1
\footnoteXmark	36
\footnoteXtext	36
\footsplitskips	1
\fullstop	1

G

Gädeke, Nora	13
\get@edindex@hyperref	1
\get@edindex@ledinnote@command	1
\get@fnmark	1
\get@fnmarkX	1
\get@index@command	1
\get@linelistfile	1
\get@sw@txt	1
\get@thisfootnote	1
\get@thisfootnoteX	1
\getline@num	1
\gl@p	1

H

\h@num	1
\hangindentX	46
\hidenumbering	1, 23
\hidenumberingonleftpage	1, 23
\hidenumberingonrightpage	1
\Hilfsbox	1
\hilfsbox	1
\hilfscount	1

\HILFSskip	1
\Hilfsskip	1
\hilfsskip	1
\hsizethreecolX	48
\hsizetwocolX	48
\Hy@raisedlink@left	1
\hyperlinkformat	1
\hyperlinkformatR	1
\hyperlinkR	1
 I	
\if@addsw	1
\if@edtext@secondarg@	1
\if@eled@sectioning	1
\if@firstlineofpage	1
\if@led@nofoot	1
\if@ledgroup	1
\if@lemmacommand@	1
\if@msdata@insertedfrompreviouspage	1
\if@noeled@sec	1
\if@noneed@Footnote	1
\if@RTL	1
\ifafterendnumberingR	1
\ifat@every@pend@star@	1
\ifat@every@pstart@star@	1
\ifautopar@pause	1
\ifbypage@	1
\ifbypage@R	1
\ifbypstart@	1
\ifbypstart@R	1
\ifeledmaccompat@	1
\iffirst@linenum@out@	1
\ifindtl@innote	1
\ifindtl@notenumber	1
\ifinserthangingsymbol	1
\ifinstanza	1
\ifl@d@dash	1
\ifl@d@elin	1
\ifl@d@esl	1
\ifl@d@pnum	1
\ifl@d@ssub	1
\ifl@d@Xmorethanwolines	1
\ifl@d@Xtwolines	1
\ifl@dend@X	1
\ifl@dhidenumber	1
\ifl@dmemoir	1
\ifl@dpaging	1
\ifl@dpairing	1
\ifl@dprintingcolumns	1
\ifl@dprintingpages	1

\ifl@dskipnumber	1
\ifl@dskipversenumber	1
\ifl@dstartendok	1
\ifl@footmisc	1
\ifl@imakeidx	1
\ifl@indextools	1
\ifledfinal	1, 73
\ifledgroupnotesL@	1
\ifledgroupnotesR@	1
\iflednopbinverse	1
\ifledRcol	1
\ifledRcol@	1
\ifnocritical@	1
\ifnoend@	1
\ifnofamiliar@	1
\ifnoledgrou@	1
\ifnoquotation@	1
\ifnoteschanged@	1
\ifnumberedpar@	1
\ifnumbering	1
\ifnumberingR	1
\ifnumberline	1
\ifnumberstanza	1
\ifparapparatus@	1
\ifparledgroup	1
\ifpst@rtedL	1
\ifresumenumbering@start	1
\ifseriesbefore	1
\ifsidepstartnum	1
\ifstopmsdata@inserted@	1
\ifsublines@	1
\ifwidthliketwocolumns	1
\ifXendinsertsep@	1
\ifxindy@	1
\ifxindyhyperref@	1
\initnumbering@quote	1
\initnumbering@reg	1
\insert@count	0, 1
\insert@msdata	1
\insert@txtbeforenotesX	1
\insert@Xtxtbeforenotes	1
\inserthangingymbol	1
\insertlines@list	1
\insertparafootsepX	1
\inserts@list	1
J	
Jayaditya	13

K

Kabelschacht, Alois 173

L

\l@advance@parledgroup@beforenormalnotes	1
\l@d@add	1
\l@d@nums	1
\l@d@section	1
\l@d@set	1
\l@d@Xend	1
\l@dampcount	1
\l@dbfnote	1
\l@dcheckcols	1
\l@dcheckstartend	1
\l@dchset@num	1
\l@dcolcount	1
\l@dcollect@@body	1
\l@dcollect@body	1
\l@dcolwidth	1
\l@dcsnote	1
\l@dcsnotetext	1
\l@dcsnotetext@l	1
\l@dcsnotetext@r	1
\l@ddodoreinxtrafeet	1
\l@dedbeginmini	1
\l@dedendmini	1
\l@emptyd@ta	1
\l@dend@close	1
\l@dend@open	1
\l@dend@stuff	1
\l@dend@Xfalse	1
\l@dend@Xtrue	1
\l@denvbody	1
\l@desnote	1
\l@dfambeginmini	1
\l@dfamendmini	1
\l@feetbeginmini	1
\l@feetendmini	1
\l@getline@margin	1
\l@getlock@disp	1
\l@getref@num	1
\l@getsidenote@margin	1
\l@gobblearg	1
\l@disnote	1
\l@label@parse	1
\l@ld@ta	1
\l@lp@box	1
\l@lsn@te	1
\l@lsnote	1
\l@make@labels	1

\l@dmforedtext	1
\l@dnnullfills	1
\l@dnumpstartsL	1
\l@doldold@footnotetext	1
\l@dp@rsefootspec	1
\l@dparsedendline	1
\l@dparsedendpage	1
\l@dparsedendsub	1
\l@dparsedstartline	1
\l@dparsedstartpage	1
\l@dparsedstartsub	1
\l@dparsefootspec	1
\l@dpush@begins	1
\l@drd@ta	1
\l@dref@undefined	1
\l@restorefills	1
\l@restoreforedtext	1
\l@drp@rbox	1
\l@drsn@te	1
\l@drsnote	1
\l@setmaxcolwidth	1
\l@skipnumberfalse	1
\l@skipnumbertrue	1
\l@tabaddcols	1
\l@tabnoexpands	1
\l@unboxmpfoot	1
\l@unhbox@line	1
\l@zeropenalties	1
\l@wrap@ifemptybox	1
\l@wrapcs@ifemptybox	1
\label	61
\labelpstartfalse	1
\labelstarttrue	1, 19
\labelref@list	1
\labelrefsparseline	1
\labelrefsparsesubline	1
\last@page@num	1
Lavagnino, John	12
\led@check@nopb	1
\led@check@pb	1
\led@err@AutoparNotNumbered	1
\led@err@BadAction	1
\led@err@edtextoutsidestart	1
\led@err@EdtextWithoutFootnote	1
\led@err@FootnoteNotInSecondArgEdtext	1
\led@err@HighEndColumn	1
\led@err@LineationInNumbered	1
\led@err@LowStartColumn	1
\led@err@ManyLeftnotes	1
\led@err@ManyRightnotes	1

\led@err@ManySidenotes	1
\led@err@NumberingNotStarted	1
\led@err@NumberingShouldHaveStarted	1
\led@err@NumberingStarted	1
\led@err@NumberingWithoutPstart	1
\led@err@PendNoPstart	1
\led@err@PendNotNumbered	1
\led@err@PstartInPstart	1
\led@err@PstartNotNumbered	1
\led@err@ReverseColumns	1
\led@err@toendnotes@outsidenumbering	1
\led@err@TooManyColumns	1
\led@err@UnequalColumns	1
\led@error@fail@patch@@doclearpage	1
\led@error@fail@patch@@iiminipage	1
\led@error@fail@patch@@makecol	1
\led@error@fail@patch@@reinserts	1
\led@error@fail@patch@endminipage	1
\led@error@PackageAfterEledmac	1
\led@mess@NotesChanged	1
\led@mess@SectionContinued	1
\led@nopb	1
\led@nopbnum	1
\led@pb	1
\led@pb@setting	1
\led@pbnum	1
\led@reinit@index@fornote	1
\led@set@index@fornote	1
\led@toksa	1
\led@toksb	1
\led@warn@AppLabelOutSecondArgEdtext	1
\led@warn@BadAction	1
\led@warn@BadAdvancelineLine	1
\led@warn@BadAdvancelineSubline	1
\led@warn@BadLineation	1
\led@warn@BadLinenummargin	1
\led@warn@BadLockdisp	1
\led@warn@BadSetline	1
\led@warn@BadSetlinenum	1
\led@warn@BadSidenotemargin	1
\led@warn@BadSubblockdisp	1
\led@warn@DuplicateLabel	1
\led@warn@edinde@outsidenumbering	1
\led@warn@LineFileObsolete	1
\led@warn@NoFile	1
\led@warn@NoIndexFile	1
\led@warn@NoMarginpars	1
\led@warn@RefUndefined	1
\led@warn@SeriesStillExist	1
\led@warning@hsizex@deprecated	1

\led@warning@msdatawithoutstop	1
\led@warning@preXnotes@deprecated	1
\led@warning@Xhsize@deprecated	1
ledgroup (environment)	58
ledgroupsized (environment)	59
\ledinnoteinner	1, 64
\ledinnote	1
\ledinnotehyperpage	1
\ledinnotemark	1
\ledleftnote	1, 64
\ledlinenum	1
\ledllfill	1
\ledlsnotefontsetup	1, 65
\ledlsnotesep	1, 65
\ledlsnotewidth	1, 64
\lednopp	1, 73
\lednopbinversetrue	73
\lednopbnum	1
\ledouternote	1, 64
\ledpb	1, 73
\ledpbnum	1
\ledpbsetting	1, 73
\ledrightnote	1, 64
\ledrlfill	1
\ledrsnotefontsetup	1, 65
\ledrsnotesep	1, 65
\ledrsnotewidth	1, 64
\ledsectnomark	1
\ledsectnotoc	1
\ledsetnormalparstuff@common	1
\ledsetnormalparstuffX	1
\ledsidenote	1, 64
\leftctab	1
\leftlinenum	1, 22
\leftltab	1
\leftnoteupfalse	65
\leftpstartnum	1
\leftrtab	1
Leibniz	13
\lemma	1, 27
\letsforverteilen	1
\line@list	1
\line@list@stuff	1
\line@list@version	1
\line@margin	1
\line@num	1
\line@set	1
\lineannot	1, 57
\lineannot@set	1
\lineation	1, 21

\linenum	1, 27
\linenum@out	1
\linenumannotation	1, 55
\linenumberlist	1, 21
\linenumberstyle	1, 23
\linenumincrement	1, 21
\linenummargin	1, 21
\linenumr@p	1
\linenumrep	1
\linenumsep	1, 22
\linerangesep@	1
\list@clear	1
\list@clearing@reg	1
\list@create	1
\lock@disp	1
\lock@off	1
\lock@on	1
\lockdisp	1, 22
Lorch, Richard	13
\ltab	1
\ltabtext	1
Luecking, Dan	79

M

\m@mmf@check	1
\m@mmf@prepare	1
\M@sect	1
\makehboxofhboxes	1
\managesanza@modulo	1
\maxhnotesX	50
Mayer, Gyula	13
\measurembody	1
\measuremcell	1
\measuremrow	1
\measuretbody	1
\measuretcell	1
\measuretrow	1
Middleton, Thomas	13, 104
\minipage (environment)	58
Mittelbach, Frank	12, 13
\morenoexpands	1, 75
\mp@append@notesX	1
\mp@append@Xnotes	1
\mpfnpos	1, 37
\mpnnormalfootgroup	1
\mpnnormalfootgroupX	1
\mpnmalvfootnote	1
\mpnmalvfootnote@inserted	1
\mpnmalvfootnoteX	1
\mppara@footgroupX	1

\mppara@vfootnoteX	1
\mpparafootgroup	1
\mpparavfootnote	1
\mpthreecolfootgroup	1
\mpthreecolfootgroupX	1
\mpthreecolfootsetup	1
\mpthreecolfootsetupX	1
\mptwocolfootgroup	1
\mptwocolfootgroupX	1
\mptwocolfootsetup	1
\mptwocolfootsetupX	1
\msdata	1, 34
\msdata@c	1
\msdata@cR	1
\multfootsep	1, 36
\multiplefootnotemarker	1

N

\n@num	1
\n@num@stanza	1
\new@line	1
\newhookarg@specific	1
\newhookcommand@series	1
\newhookcommand@series@reload	1
\newhooktoggle@series	1
\newhooktoggle@series@reload	1
\newhooktoggle@specific	1
\newseries@	1
\newverse	1
\NEXT	1
\next@line@list@stuff	1
\no@expands	1
\noeledsec	72
\nomk@	1
\normal@footnotemarkX	1
\normal@page@break	1
\normal@pars	1
\normalbfnoteX	1
\normalbodyfootmarkX	1
\normalfootfmt	1
\normalfootfmtX	1
\normalfootfootmarkX	1
\normalfootgroup	1
\normalfootgroupX	1
\normalfootnoterule	1
\normalfootnoteruleX	1
\normalfootstart	1
\normalfootstartX	1
\normalvfootnote	1
\normalvfootnote@inserted	1

\normalvfootnoteX	1
\notefontsizeX	46
\notenumfontX	45
\noteschanged@false	1
\noteschanged@true	1
\noteswidthliketwocolumnsX	50
\nulledindex	1
\nullsetzen	1
\num@lines	1
\numberedpar@false	1
\numberedpar@true	1
\numberingfalse	1
\numberingtrue	1
\numberlinefalse	20
\numberlinetrue	20
\numberpstartfalse	1, 19
\numberpstarttrue	1, 19
\numberstanzafalse	55
\numberstanzatrue	55
\numlabfont	1, 51

O

\old@hsize	1
\one@line	1
optionafter	57
optionauxdir	15, 450
optionbefore	57
optioncontinuousnumberingwithcolumns	90, 155, 449
optioninnnote	448
optioninnnote	448
optionlinerangesep	270
optionnocritical	448
optionnoeledsec	364, 450
optionnoend	448
optionnonpenalties	75
optionnotenumber	448
optionswcaseinsensitive	29, 453

P

\page@action	1
\page@num	1
\pagelinesep	1, 66
\pageref	61
\par@line	1
\para@footgroupX	1
\para@footsetup	1
\para@footsetupX	1
\para@vfootnoteX	1
\parafootfmt	1
\parafootfmtX	1

\parafootgroup	1
\parafootsepX	48
\parafootstart	1
\parafootstartX	1
\paravfootnote	1
\parindentX	46
\parse@annot	1
\pausenumbering	1, 20
\pausenumbering@page@num	1
\pend	1, 17
Plato of Tivoli	13
\postbodyfootmark	1
\prebodyfootmark	1
\prenotesX	49
\prepare@edindex@fornote	1
\prepare@prenotesX	1
\prepare@Xgroupbyline	1
\prepare@Xprenotes	1
\prev@nopb	1
\prev@pb	1
\prevpage@num	1
\print@eledsection	1
\print@footnoteXrule	1
\print@leftmargin@eledsection	1
\print@lemma	1
\print@line	1
\print@notesX	1
\print@rightmargin@eledsection	1
\print@Xfootnoterule	1
\print@Xnotes	1
\printendlines	1
\printlineendnote	1
\printlineendnotearea	1
\printlinefootnote	1
\printlinefootnotearea	1
\printlinefootnotenumbers	1
\printlines	1
\printnpnum	1
\printpstart	1
\printsymlineendnotearea	1
\printsymlinefootnotearea	1
\printXafternumber	1
\printXbeforenumber	1
\pstart	1, 17
\pstarteref	1
\pstartnum	1
\pstartref	59
Q	
\quotation	1

\quote	1
R	
\raggedX	48
\raw@text	1
\rbracket	1
\read@linelist	1
\ref	61
\ref@reg@later	1
\Relax	1
\reledmac@error	1
\reledmac@warning	1
\removehboxes	1
\reset@current@annt	1
\reset@msd@options@iffullpage	1
\resetprevline@	1, 107
\resetprevpage@	1
\resetprevpage@num	107
\restore@endnotes	1
\restore@familiarnotes	1
\restore@notes	1
\restore@sidenotes	1
\resumenumbering	1, 20
\rightctab	1
\rightlinenum	1, 22
\rightltab	1
\rightnoteupfalse	65
\rightrtab	1
\rightstartnum	1
\rigidbalance	1
\rigidbalanceX	1
\rtab	1
\rtabtext	1
S	
Sacrobosco	13
\sameword	1, 28
\sameword@inedtext	1
Schöpf, Rainer	13
\section@num	1
\select@lemmafont	1
\select@lemmafont	1, 51
\SEref	1, 61
\SErefonlypage	61
\SErefwithpage	1, 61
\series	1
\seriesatbegin	1, 37
\seriesatend	1, 37
\set@continuousnumberingforL	1
\set@line	1

\set@line@action	1
\set@txtbeforenotesX	1
\set@Xtxtbeforenotes	1
\setapprefprefixmore	62
\setapprefprefixsingle	62
\setcommand@series	1
\sethangingsymbol	1, 53
\setistwoofollowinglines	1
\setl@lp@rbox	1
\setl@drpr@box	1
\setline	1, 22
\setlinenum	1, 23
\setmcellcenter	1
\setmcellleft	1
\setmcellright	1
\setmrowcenter	1
\setmrowleft	1
\setmrowright	1
\setmsdatalabel	1, 35
\setmsdataposition	1, 35
\setmsdataseries	1, 35
\setnoteswidthliketwocolumnsX@	1
\setnotesXpositionliketwocolumns@	1
\setprintendlines	1
\setprintlines	1
\setSErefonlypageprefixmore	62
\setSErefonlypageprefixsingle	62
\setSErefprefixmore	62
\setSErefprefixsingle	62
\setsidenotessep	65
\setstanzaindent	1, 52
\setstanzapenalties	1, 53
\setstanzavalues	1
\settcellcenter	1
\settcellleft	1
\settcellright	1
\settoggle@series	1
\settrrowcenter	1
\settrrowleft	1
\settrrowright	1
\setXnotespositionliketwocolumns@	1
\setXnoteswidthliketwocolumns@	1
\showlemma	1, 73
\showwordrank	1, 32
\sidenote@margin	1
\sidenotemargin	1, 64
\sidepstartnumtrue	19
\skip@lockoff	1
\skipnumbering	1, 23
\splitoff	1

\spreadmath	1, 69
\spreadtext	1, 69
\stanza	1, 51
\stanza@count	1
\stanza@hang	1
\stanza@line	1
\stanzaindent	1, 53
\stanzaindent*	1, 53
\stanzaindentbase	1, 52
\stanzanumwrapper	1, 55
\startlock	1, 22
\startsub	1, 22
\step1@dcollcount	1
\stopmsdata	1, 34
\store@annot@to@absline	1
\strip@szacnt	1
\sub@action	1
\sub@lock	1
\sub@off	1
\sub@on	1
\subline@num	1
\sublinenumberstyle	1, 23
\sublinenumincrement	1, 21
\sublinenumr@p	1
\sublinenumrep	1
\sublineref	1, 59
\sublines@false	1
\sublines@true	1
\subblock@disp	1
\subblockdisp	1
Sullivan, Wayne	13, 14, 75, 89, 94, 186, 188, 277, 317
\sw@noexpand	1
\swnoexpands	32
\sza@penalty	1

T

\tabHilfbox	1
\tabhilfbox	1
\theaddcolcount	1
\theedtext	1
\theendpageline	1
\thefootnoteA	35
Theodosius	13
\thepageline	1
\thepstart	1, 19
\thestanza	1, 55
\thestrartpageline	1
\this@line@list@version	1
\threecol@begin@insert	1
\threecolfootfmt	1

\threecolfootfmtX	1
\threecolfootgroup	1
\threecolfootgroupX	1
\threecolfootsetup	1
\threecolfootsetupX	1
\threecolvfootnote	1
\threecolvfootnote@inserted	1
\threecolvfootnoteX	1
\toendnotes	1, 26
\toendnotes*	1
\twocolfootfmt	1
\twocolfootfmtX	1
\twocolfootgroup	1
\twocolfootgroupX	1
\twocolfootsetup	1
\twocolfootsetupX	1
\twocolvfootnote	1
\twocolvfootnote@inserted	1
\twocolvfootnoteX	1
\txtbeforenotesonlyonceX	49
\txtbeforenotesX	49

U

\unvxhX	1
-------------------	---

V

Vamana	13
\variab	1
\vbfnoteX	1
\vl@dbfnote	1
\vl@dcsnote	1
\vl@disnote	1
\vl@dlsnote	1
\vl@dosnote	1
\vl@drsnote	1
\vnumfootnoteX	1

W

Whitney, Ron	13
\widthX	50
\wrap@edcrossref	1
\wrapcontentX	46
\wrapped@bodyfootmarkX	1
\wrapped@footfootmarkX	1
Wujastyk, Dominik	12

X

\X@atbegininsertion	1
\X@beforeinsertion	1
\X@doreinfeet	1

\xabslineref	1
\Xafterlemmaseparator	44
\Xafternote	48
\Xafternumber	42
\Xafterrule	49
\Xafersymlinenum	42
\xannotationref	1
\xannotref	60
\Xarrangement	1, 38
\Xarrangement@normal	1
\Xarrangement@paragraph	1
\Xarrangement@threecol	1
\Xarrangement@twocol	1
\Xbeforeinserting	47
\Xbeforelemmaseparator	44
\Xbeforenotes	49
\Xbeforenumber	40, 42
\Xbeforesymlinenum	42
\Xbhookgroup	49
\Xbhooknote	47
\Xboxlinenum	43
\Xboxlinenumalign	43
\Xboxsymlinenum	43
\Xcolalign	47
\xedindex	1
\xedlabel	1
\xedtext	1
\Xendafterlemmaseparator	45
\Xendafternote	51
\Xendafterpagenumber	40
\Xendaftersymlinenum	42
\Xendaftrenumber	42
\Xendahookinplaceofnumber	44
\Xendahooklinenum	44
\Xendbeforelemmaseparator	45
\Xendbeforenumber	42
\Xendbeforepagenumber	40
\Xendbeforesymlinenum	42
\Xendbhookinplaceofnumber	44
\Xendbhooklinenum	44
\Xendbhooknote	47
\Xendboxendlinenumalign	44
\Xendboxlinenum	44
\Xendboxlinenumalign	44
\Xendboxstartlinenumalign	44
\Xendboxsymlinenum	43
\Xendhangindent	46
\Xendinplaceoflemmaseparator	45
\Xendinplaceofnumber	43
\Xendinplaceofpagenumber	40

\Xendlemmadisablefontselection	45
\Xendlemmafont	45
\Xendlemmaseparator	44
\Xendlinenumannotationposition	57
\Xendlineprefixmore	40
\Xendlineprefixsingle	40
\Xendlinerangeseparator	40
\Xendmorethanwolines	41
\Xendnonumber	41
\Xendnotefontsize	46
\Xendnotenumfont	45
\Xendnumberonlyfirstinline	39
\Xendnumberonlyfirstintwolines	39
\Xendpagenumberonlyfirst	39
\Xendparagraph	51
\Xendsep	51
\Xendsublinesep	42
\Xendsymlinenum	39
\Xendsympagenum	40
\Xendtwolines	41
\Xendtwolinesbutnotmore	41
\Xendtxtbeforenotes	49
\Xendwrapcontent	46
\xflagref	1
\Xgroupbyline	48
\Xgroupbylinesparetwolines	48
\Xhangindent	46
\Xhsizethreecol	47
\Xhsizetwocol	47
\Xinplaceoflemmaseparator	44
\Xinplaceofnumber	43
\Xinsertparafootsep	1
\Xledsetnormalparstuff	1
\xleft@appenditem	1
\Xlemmadisablefontselection	45
\Xlemmafont	45
\Xlemmaseparator	44
\Xlinenumannotationposition	57
\Xlinenumannotationposition@side	1
\Xlinerangeseparator	40
\Xlineref	1, 60
\Xmaxhnotes	50
\Xmorethanwolines	40
\Xnolemmaseparator	1, 44
\Xnonbreakableafternumber	42
\Xnonumber	41
\Xnotefontsize	45
\Xnotenumfont	45
\Xnoteswidthliketwocolumns	50
\Xnumberonlyfirstinline	39

\Xnumberonlyfirstintwolines	39
\Xonlypstart	41
\Xpagelinesep	42
\xpageref	1, 60
\Xparafootsep	48
\Xparindent	46
\Xprenotes	1, 49
\Xprenotes@	1
\Xpstart	41
\Xpstarteverytime	41
\xpstartref	1, 60
\XR@test	1
\XR@test@mac	1
\XR@test@mac@test	1
\Xragged	48
\xright@appenditem	1
\Xrigidbalance	1
\Xstanza	42
\Xstanzaseparator	42
\Xstorelineinfo	1
\xsublineref	1, 60
\Xsublinesep	22, 42
\Xsublinesepside	22
\Xsymlinenum	39
\Xtoendnotes	26
\Xtwolines	40
\Xtwolinesonlyinsamepage	41
\Xtxtbeforenotes	49
\Xtxtbeforenotesonlyonce	49
\Xunvh	1
\Xwidth	50
\Xwrapcontent	46
\Xwrapdlemma	46
\Xwraplemma	46
\Xwraplinenumannotation@ref	1
\Xwraplinenumannotation@side	1
\xxref	1, 60
 Z	
\zz@000	1
\zz@0000	1

Change History

v0.1.0.

General: First public release 1

v0.2.0.

\ifl@dmemoir: Added \ifl@dmemoir for memoir class having been used 81

\morenoexpands: Added \l@dtabnoexpands to \no@expands 133

\reledmac@error: Added \eledmac@error and replaced error messages 82

General: Added tabmac code, and extended indexing 1

v0.2.1.

\@lab: Removed page setting from \@lab 280

\doxtrafeet: Renamed \doxtrafeet to \l@ddoxtrafeet 271

\edlabel: Tweaked \edlabel to get correct page numbers 277

\l@ddodoreinxtrafeet: Renamed \dodoreinxtrafeet to \l@ddodoreinxtrafeet 272

\morenoexpands: Removed some \lets from \no@expands. These were in edmac but

Peter Wilson feels that they should not have been as they disabled page/line refs in a
footnotes 133

General: Added text about normal labeling 61

Bug fixes and match with mempatch v1.8 1

Major changes to insert code when memoir is loaded 274

v0.2.2.

\footfudgefiddle: Added \footfudgefiddle 185

\next@line@list@stuff: Added initial write of page number in \line@list@stuff 124

\para@footsetup: Added \footfudgefiddle to \para@footsetup 185

\para@footsetupX: Added \footfudgefiddle to \para@footsetupX 227

General: Improved paragraph footnotes 1

New Dekker example 1

Used \providecommand for \gobblethree to avoid clash with the amsfonts
package 88

v0.3.0.

\@lab: Replaced \the\line@num by \linenumr@p\line@num in \@lab, and similar
for sub-lines 280

\@nl@reg: Added a bunch of code to \@nl for handling \setlinenum 111

\ledlinenum: Added \linenumr@p and \sublinenumr@rep to \leftlinenum and
\rightlinenum 102

\linenumberlist: Added \linenumberlist mechanism 89

\printendlines: Added \linenumr@p and \sublinenumr@p to \printendlines . 245

\printlines: Added \linenumr@p and \sublinenumr@p to \printlines 209

\sublinenumr@p: Added \linenumberstyle and \sublinenumberstyle 102

General: Includes edstanza and more 1

v0.3.1.

General: Not released. Added remarks about the parallel package 1

v0.4.0.

\@iiiminipage: Modified kernel \@iiiminipage and \endminipage to cater for
critical footnotes 303

\Xarrangement@normal: Added minpage footnote setup to \footnormal 180

\edtext: Added \showlemma to \edtext 134

\l@dfteetendmini: Added \l@dfteetbeginmini, \l@dfteetendmini and all their
supporting code 301

\mpnrmalfootgroup: Added \mpnrmalfootgroup 183

\mpnormalvfootnote: Added \mpnormalvfootnote	181
\showlemma: Added \showlemma	89
General: Added final/draft options	78
Added ledgroup environment	305
Added ledgroupsized environment	305
Added minipage, etc., support	1
v0.4.1.	
\do@Xfeet: Changed \do@Xfeet code for easier extensions	272
\edindex: Let elemac take advantage of memoir's indexing	310
\print@Xnotes: Added \opXfeet	272
General: Added code for changing \doclearpage	275
Not released. Minor editorial improvements and code tweaks	1
Only change \footnotetext and \footnotemark if memoir not used	212
v0.5.0.	
\@footnotetext: Enabled regular \footnote in numbered text	213
\@xypar: Eliminated \marginpar disturbance	293
General: Added left and right sidenotes	294
Added sidenotes, familiar footnotes in numbered text	1
v0.5.1.	
\affixline@num: Changed \affixline@num to cater for sidenotes	164
\l@getssidenote@margin: Added \sidenotemargin and \sidenote@margin	294
General: Added moveable sidenote	294
Fixed right line numbers killed in v0.5	1
Only change \hsize in ledgroupsized environment otherwise page number can be in wrong place	305
v0.6.0.	
\@lopR: Added \pend, \pendR, \lopL and \lopR in anticipation of parallel processing	113
\@nl@reg: Added \fix@page to \@nl	111
Extended \@nl to include the page number	111
\fix@page: Added \last@page@num and \fix@page	112
\get@thisfootnote: Changed \l@dbfnote and \v@dbfnote as originals could give incorrect markers in the footnotes	213
\new@line: Extended \new@line to output page numbers	125
General: Fixed long paragraphs looping	1
Fixed minor typos	1
Prepared for elepar package	1
v0.7.0.	
\@nl@reg: Added \@nl@reg	111
\@ref@reg: Added \@ref@reg	121
\affixline@num: Added skipnumbering to \affixline@num	164
\do@actions@fixedcode: Added \do@actions@fixedcode	161
\do@actions@next: Added number skipping to \do@actions	159
\do@insidelinehook: Added \do@linehook for use in \do@line	157
\endnumbering: Changed \endnumbering for elepar	93
\f@x@l@cks: Added \ch@cksub@l@ck, \ch@ck@l@ck and \f@x@l@cks	167
\footsplitskips: Added \footsplitskips for use in many footnote styles	178
\get@linelistfile: Added \get@linelistfile	109
\initnumbering@reg: Added \initnumbering@reg	91

\l@advance@parledgroup@beforenormalnotes: Added \l@dunboxmpfoot containing some common code	304
\l@dcsnotetext@r: Added \l@demptyd@ta	157
\l@dgetline@margin: Added \l@dgetline@margin	98
\l@dgetlock@disp: Added \l@dgetlock@disp	100
\l@get sidenote@margin: Added \l@get sidenote@margin	294
\l@dnumpstartsL: Added \l@dnumpstartsL, \ifl@dpairing and \ifpst@rted for/from elepar	89
\l@drsn@te: Added \l@drsn@te and \l@drsn@te for use in \do@line	158
\l@dzopenalties: Added \l@dzopenalties	152
\ledlinenum: Added \ledlinenum for use by \leftlinenum and \rightlinenum .	102
\list@clearing@reg: Added \list@clearing@reg	109
\n@num: Added \n@num	118
\next@line@list@stuff: Deleted \page@start from \line@list@stuff	124
\normalbfnoteX: Removed extraneous space from \normalbfnoteX	219
\pausenumbering@page@num: Changed \resumenumbering for elepar	94
\setprintendlines: Added \setprintendlines for use by \printendlines . . .	242
\setprintlines: Added \setprintlines for use by \printlines	204
\skipnumbering: Added \skipnumbering and supports	130
\sublinenumincrement: Added \firstlinenum, \linenumincrement, \firstsublinenum and \linenumincrement	100
\sublinenumr@p: Using \linenumrep instead of \linenumr@p	102
Using \sublinenumrep instead of \sublinenumr@p	102
\vnumfootnoteX: Removed extraneous space from \vnumfootnoteX	221
General: elemac having been available for 2 years, deleted the commented out original edmac texts	1
Maïeul Rouquette new maintainer	1
Made macros of all messages	82
Replaced all \interAfootnotelinepenalty, etc., by just \interfootnotelinepenalty	1
Tidying up for elepar and ledarab packages	1
v0.8.0.	
General: Bug on endnotes fixed: in a // text, all endnotes will print and be placed at the ends of columns ()	1
v0.8.1.	
General: Bug on \edtext ; \critex ; \lemma fixed: we can now use non-switching commands	1
v0.9.0.	
General: No more ledpatch. All patches are now in the main file.	1
v0.9.1.	
General: Fix some bugs linked to integrating ledpatch on the main file.	1
v0.10.0.	
General: Corrections to \section and other titles in numbered sections	1
v0.11.0.	
General: Makes it possible to add a symbol on each verse's hanging, as in French typography. Redefines the command \hangingsymbol to define the character. . . .	1
v0.12.0.	
\l@dnumpstartsL: Added \ifledRcol and \ifnumberingR for/from elepar . . .	89
General: For compatibility with elepar, possibility to use \autopar on the right side. . .	1
Possibility to number \pstart	19

Possibility to number the pstart with the commands \numberpstarttrue.	1
v0.12.1.	
General: Don't number \pstarts of stanza.	1
The numbering of \pstarts restarts on each \beginnumbering.	1
v0.13.0.	
\managestanza@modulo: New stanzaindent repetition counter to repeat stanza indents every <i>n</i> verses.	319
General: New stanzaindent repetition counter to repeat stanza indents every <i>n</i> verses.	52
New stanzaindent repetition counter: to repeat stanza indents every <i>n</i> verses.	1
v0.13.1.	
General: \thepstartL and \thepstartR use now \bfseries and not \bf, which is deprecated and makes conflicts with memoir class.	1
v0.14.0.	
\edlabel: Tweaked \edlabel to get correct line number if the command is first element of a paragraph.	277
General: Tweaked \edlabel to get correct line number if the command is first element of a paragraph.	1
v0.15.0.	
\affixline@num: Line numbering can be disabled.	164
\ifinserthangingsymbol: New management of hangingsymbol insertion, preventing undesirable insertions.	318
\printlines: Line numbering can be reset at each pstart.	208
General: Line numbering can be reset at each pstart.	97
Possibility to print \pstart number inside.	19
v0.17.0.	
\ifinserthangingsymbol: New new management of hangingsymbol insertion, preventing undesirable insertions.	318
v1.0.0.	
\morenoexpands: Change to be compatible with new features	133
General: \lemma can contain commands.	27
Debug in lineation command	21
New generic commands to customize footnote display.	38, 262
Options nonum and nosep in \Xfootnote.	25
Options of \Xfootnotes.	176
Possibility to have commands in sidenotes.	64
Some compatibility break with elemac. Change of name: elemac.	1
v1.0.1.	
General: Correction on \Xnumberonlyfirstinline with lineation by pstart or by page.	39
v1.1.0.	
\Xprenotes: New skip \Xprenotes@	235
\settoggle@series: \settoggle@series switch the global value of the toggle, not only the local value.	262
General: Add \labelpstarttrue.	19
Add \Xnumberonlyfirstintwolines	39
Add \Xpstart and \Xonlypstart	41
New hook to add arbitrary code at the beginning of the notes	46
New options for block of notes.	49
New package option: parapparatus.	1
New tools to change order of series	261
Sectioning commands.	71

v1.2.0.		
\Xprenotes:	Debug in familiar footnotes (bug introduced by v1.1).	235
\endquote:	Compatibility of \ledchapter with the <i>memoir</i> class.	356
v1.3.0.		
\endquote:	<i>Quotation</i> and quote environment inside numbered sections.	356
v1.4.0.		
\edtext:	Compatibility of \edtext with the right-to-left direction (with Polyglossia).	134
\ledsetnormalparstuffX:	Direction of footnotes with polyglossia.	231
\newseries@:	Remembers the language of the lemma, in order to create a correct direction for the footnote separator.	251
\rbracket:	Switch the right bracket to a left bracket when the lemma is RTL (needs polyglossia or LuaTeX).	198
General:	Compatibility with LuaTeX of RTL notes.	1
v1.4.1.		
\affixside@note:	Remove spurious spaces.	300
\endquote:	New option <i>noquotation</i>	356
\get@thisfootnote:	Compatibility of standard footnotes with <i>eledmac</i> when these footnotes contain any commands.	213
\labelrefsparsesubline:	Fix a bug with \edlabel.	279
v1.4.2.		
General:	Debug with some special classes.	1
v1.4.3.		
General:	Add \Xnonbreakableafternumber.	42
Spurious space after familiar footnotes.	1
v1.4.4.		
General:	Label inside familiar footnotes.	1
v1.4.5.		
General:	Bug with komascript + eledpar + chapter.	1
v1.4.6.		
General:	Bug with memoir class introduced by 1.4.5.	1
v1.4.7.		
\endquote:	Compatibility of sectioning commands with \autopar.	356
v1.4.8.		
General:	Corrects a bug with parallel texts introduced by 1.1.	1
v1.4.9.		
\normalbfnoteX:	Allow to redefine \thefootnoteX with alph when some packages are loaded.	219
v1.5.0.		
\do@insidelinehook:	Added \do@insidelinehook for use in \do@line	157
\edindex:	Compatibility with <i>imakeidx</i> package, and possibility to use multiple index with \edindex.	310
General:	Correct indexing when the call is made in critical notes.	306
v1.5.1.		
\managestanza@modulo:	Correct stanzaidentsrepetition counter	319
\normalvfootnoteX:	Fix a bug with normal familiar footnotes when mixing RTL and LTR text.	216
v1.6.0.		
\newverse:	Add \falseverse macro.	322
v1.6.1.		
\AtStartEveryPstart:	Spurious space in \pstart.	148

\ifinserthangingsymbol: Hang verse is now not automatically flush right.	318
\l@dunhbox@line: Move the call to \inserthangingsymbol to allow use \hfill inside.	153
\pend: Spurious space in \pend.	150
General: Corrects a false hanging verse when a verse is exactly the length of a line.	1
v1.7.0.	
General: New features for managing page breaks.	73
v1.8.0.	
\endquote: Correction of sectioning commands in parallel texts.	356
\get@index@command: Debug \get@index@command and compatibility with hyperref package.	309
\newhookcommand@series@reload: Debug \beforenotesX and \maxnotesX which did not work.	265
\prevpage@num: Correct \parafootsep when using with ledgroup.	191
General: Compatibility with parledgroup option of elepar package.	1
If imakeidx and hyperref are loaded, adds hyperref in the index.	306
v1.8.1.	
General: Debug endnotes when more than one series is used (change the position where tools for endnotes are defined).	236
v1.8.2.	
General: Debug compatibility problem with hebrew option of babel package.	1
v1.8.3.	
General: Fixes spurious spaces added by v1.7.0.	1
v1.8.5.	
General: Debug indexing in right column, with elepar.	306
v1.9.0.	
\doxtrafeet: Add \fnpos to choice the order of footnotes.	271
\l@dfeetendmini: Add \mpfnpos to choice the order of footnotes in minipage / ledgroup.	301
v1.10.0.	
\endquote: Correction of sectioning commands in parallel texts.	356
General: Add \pstartref and \xpstartref to refer to a pstart number (extension of \edlabel).	1
v1.10.1.	
General: Compatibility with cleveref.	1
v1.10.2.	
General: Compatibility of stanza with v1.8a of babel-greek.	1
v1.10.3.	
General: Debug of cross-referencing.	1
v1.10.4.	
General: Debug of critical notes in edtabular environment.	1
v1.10.5.	
General: Debug of \pausenumbering.	1
Debug of \xxref.	1
v1.10.6.	
General: Debug of interaction between \autopar and \pausenumbering.	1
v1.11.0.	
General: Add hooks to disable the font selection for lemma in footnote.	45
v1.11.1.	
General: Correct a bug when a critical note starts with plus or minus.	1

v1.12.0.

\@nl@reg: To ensure compatibility with \musixtex, \@l becomes \@l. Consequently,	111
\@l@reg becomes \@nl@reg.	111
\AtStartEveryPstart: New optional argument for \pstart, to execute code before it.	148
\edindex: Use correctly default index when imakeidx is loaded.	310
\endquote: \ledxxx sectioning commands are deprecated and replaced by \eledxxx	
commands.	356
\initnumbering@reg: \beginnumbering is defined only on elemac, not on elepar.	91
\l@getside@margin: \sidenotemargin is now directly defined in elemac to	
be able to manage elepar.	294
\l@disnote: \l@dsnote, \l@drsnote and \l@dcsnote defined only one time, in	
elemac, including needs for elepar case.	295
\l@dnumpstartsL: Add \ifledRcol@ for elepar	89
\l@dunhbox@line: \do@line is split in more little commands.	154
\newhookcommand@series@reload: Debug \beforenotesX and \maxhnotesX which	
did not work when called after \footparagraphX.	265
Debug \beforenotes and \maxhnotes which did not work when called after	
\footparagraph.	265
\pend: New optional argument for \pend, to execute code after it.	150
\stanza: &can have an optional argument: content to be printed after.	322
\Stanza can have an optional argument: content to be printed before.	322
Add \newverse macro, \falseverse deprecated.	322
General: Add \ledinnernote and \ledouternote commands.	64
Add \endparagraph and related settings.	51
Add hyperlink to crossref (needs hyperref package).	59
Compatibility with \musixtex.	1
Debug elemac sectioning command after using \resumenumbers.	1
Ensure that imakeidx is loaded <i>before</i> elemac	306
New hooks: \Xafterrule and \afterruleX	49
New options for ragged-paragraph notes	48
New sectioning commands.	71
Optional arguments for \pstart and \pend.	18

v1.12.1.

\wrap@edcrossref: Fix spurious spaces.	283
--	-----

v1.12.2.

\l@dunhbox@line: Fix a bug with critical notes at the tops of pages (added by v12.0.0)	153
--	-----

v1.12.3.

\flag@end: \flag@start and \flag@end are now defined only one time for elemac	
and elepar	126
\flag@start send a error message when a \edtext is done without insert (note)	126
\releldmac@error: Replaced error messages	82
General: Add macros for new messages since v0.7	82
Correct bug with side and familiar notes in tabular environments.	1
Debug \ledxxx with some paper size	1
Debug \ledinnernote and \ledouternote commands in the top of pages.	64
Debug left and right notes (bugs added by 1.12.0)	1
Underline lemma in \ledxxx when using draft mode.	1

v1.12.4.

General: Debug spurious page breaks before \chapter (bug added in 1.12.0)	1
---	---

v1.12.5.	\@edindex@\hyperref: Debug \edindex when hyperref is not loaded	312
	\@ssect: Debug \eledchapter in parallel with memoir	360
	\doinsidelinehook: Added \dolinehook and \doinsidelinehook	157
	\endnumbering: Allow to mix parallel columns and normal text when using \pausenumbering	93
	\l@dgobblearg: \l@dgobblearg becomes \l@dgobbleoptarg	340
	\l@restoreforedtext: Debug optional arguments of \Xfootnote in tabular context	340
	\pausenumbering@page@num: Debug \resumenumbers	94
v1.12.7.	\wrap@\edcrossref: \wrap@\edcrossref is now robust	283
v1.12.8.	\flag@end: \flag@start do not send a error message when a \edtext is done without insert (note) but have a endnote	126
v1.13.0.	\newhooktoggle@series@reload: Add \newhookcommand@toggle@reload	265
	\para@footsetupX: In \para@footsetupX, use \columnwidth instead of \hsize .	227
	\settoggle@series: \settoggle@series can take an optional arguments to reload series setup	262
	General: Add \Xnoteswidthliketwocolumns and \noteswidthliketwocolumnsX .	50
	Added widthliketwocolumns option	78
v1.13.1.	\ifat@every@pstart@star@: Add \l@dzero penalties in \pstart	148
	General: Coming back of page and line breaking penalties's management, deleted by error in v0.17	1
	Debug quotation environment inside of a \pstart preceded by a sectioning command.	1
v1.13.2.	\l@dnumpstartsL: Add \ifl@dpaging for \eledpar	89
	General: Fix a bug with normal footnotes, added by v1.13.0	1
v1.13.3.	General: Fix extra spaces with paragraphed footnotes, added by v1.13.0	1
v1.13.4.	General: Fix a bug with index when memoir class is used without hyperref	1
v1.14.0.	\edindex: Let elemac take advantage of imakeidx even when memoir class is used .	310
	General: Debug spurious characters before endnotes	236
	Delete previous override of \l@d@@wrindexhyp at the beginning of a document when hyperref is not loaded	314
	Move gobbling command	88
	Provide \gobblefour	88
v1.14.1.	\@ssect: Debug sectioning commands when using both handout and hyperref package	362
v1.14.2.	\@ssect: Debug \edtext after starred sectioning commands when using memoir class.	360
v1.15.0.	\@edtext@level: New boolean \if@edtext@.	133
	\arrangementX@threecol: Correct bug with paragraphed familiar footnotes setting.	226
	\endsub: Restore subline feature (disabled by mistake in v1.8.0).	128
	\if@lemmacommand@: New boolean \iflemmacommand@.	139

General: Fix a bug with footnotes layout when using some options of the geometry package (bug add by v1.13.0).	1
New commands \AtEveryPstart and \AtEveryPend.	19
New tools to prevent ambiguous references in lemma	28
v1.15.1.	
\next@line@list@stuff: Revert modification of 1.5.2 which makes bug with numbering. Leave vertical mode to solve spurious space before minipage.	124
v1.16.0.	
General: \edtext is now defined only in elemac, not in elepar. Debug wrong numbering when using \sameword + elepar + \tag command.	133
Compatibility of standard footnotes with some biblatex styles.	1
New \stanzaindent command.	1
v1.16.1.	
\xlineref: \lineref is not defined if defined by some other package, like lineno. Elemac provides \edlineref instead.	283
v1.17.0.	
\edtext: Error message when calling \edtext outside of a numbered paragraph.	134
v1.18.0.	
\@edindex@hyperref: Fix spurious space with \edindex when using imakeidx/indextools + hyperref.	312
\edlabel: \edlabel is now defined only one time for both elemac and elepar	277
\l@d@section: Option parapparatus works for endnotes.	237
\l@dnumpstartsL: Add \ifl@dprintingpages and \@dprintingcolumns for elepar	89
\print@line: Compatibility with Lua ^{LT} E RTL languages.	154
\printlinefootnote: Code refactoring in \printlinefootnote: the printing of the numbers are factorized in \printlinefootnotearea	200
\printpstart: Debug \Xpstart with parallel pages and columns (elepar)	199
General: Add \Xpstarteverytime	41
Compatibility with Lua ^{LT} E RTL languages.	1
Debug \Xonlypstart when using \Xnumberonlyfirstinline and the current line number differs from the previous.	41
v1.19.0.	
\footsplitskips: \footsplitskips doesn't set \floatingpenalty to \@MM when processing parallel pages.	178
\xxref: \xxref works also with right side numbers, when \@Rlineflag is not empty.	286
General: \Xmaxnotes and \maxnotesX work now for both two-columns and three-columns setting.	1
Compatibility with elepar v.1.13.0.	1
v1.19.1.	
General: Call \correct@footinsX@box and \correct@Xfootins@box directly in \print@notesX@forpages and \print@Xnotes@forpages, that is in elepar.	1
v1.20.0.	
\printlines: Added \ifl@d@Xmorethanwolines and \ifl@d@Xmorethanwolines to \printlines	209
\stanza: & and \& can be preceded by spaces.	322
\xxref: Debug \xxref when not loading elepar (Fix a bug added in 1.19.0).	286
General: Add \Xendboxlinenum	44
Add \Xtwolines and \Xmorethanwolines hooks	40
Add series option.	1

Correct \Xinplaceofnumber hook.	1
Explicit error message when calling \Xfootnote outside of \edtext.	1
Fix a bug with line number typesetting direction when using \eledsection and similar commands for RTL texts with Lua ^{LT} EX.	1
Fix issues with RTL text in notes when using Lua ^{LT} EX.	1
Options fulllines in \Xfootnote.	25
The \newifs are not followed by boolean values set to false, because it is the ^T EX default setting.	1
v1.21.0.	
\@edindex@\hyperref: Look at the hyperindex option of hyperref before inserting hyperref	312
\l@d@section: \endnotes take five arguments.	237
\ledinnotemark: Add \ledinnotemark.	309
\ledsetnormalparstuffX: \ledsetnormalparstuff is deprecated and becomes \ledsetnormalparstuffX and \Xledsetnormalparstuff.	231
\n@num: \n@num@ref deleted	118
\n@num defined only one time for both Eledmac and Eledpar	118
\newhookcommand@series: \newhookcommand@series can take an optional argument.	264
\newhooktoggle@series: \newhooktoggle@series can take an optional argument.	265
\print@footnoteXrule: Code refactoring: the spaces after the footnote rules are directly managed in \print@Xfootnoterule and \print@footnoteXrule	233
\seriesatend: Fix spurious space in \seriesatend	261
\skipnumbering: \skipnumbering defined only one time for both Eledmac and Eledpar.	130
Correct \skipnumbering for stanza.	130
Delete \skipnumbering@reg.	130
General: \AtEveryPstart and \AtEveryPend are now compatible with \autopar	1
\Xafterrule and \afterruleX features no longer create problems of overflowing at the bottom of the page.	1
\chapter inside optional argument of \pstart works when typesetting parallel pages	1
\preXnotes and \prenotesX features no longer create problems of overflowing at the bottom of the page.	1
\seriesatbegin and \seriesatbegin more efficient	261
Add \applabel and related	62
Add \beforenotesX and \Xbeforenotes features for notes set in two and three column.	1
Add \hidenumbers	23
Add \Xcolalign and \colalignX hooks	47
Add \Xendtwolines, \Xendmorethan twolines, \Xendtwolinesbutnotmore and \Xendtwolinesonlyinsamepage.	41
Add \Xparindent and \hangindentX	46
Add \Xtwolinesbutnotmore and \Xtwolinesonlyinsamepage.	1
Add nocritical, noend, nofamiliar and noledgroup options.	1
Add noeledsec package option	1
Debug \beforenotesX \maxhnotesX \noteswidthliketwocolumnsX and \afterruleX with footnotes set in two and three columns.	1
Fix a bug when a \Xfootnote follows a \Xendnote in the second argument of \edtext (bug added in eledmac 1.0.0).	1

Fix a bug with <code>\maxhnotesX</code> when using <code>\foottwocolX</code> or <code>\footthreecolX</code>	1
Fix a bug with space between columns with notes in two columns (bug added in v1.13.0).	1
Fix spurious space after first page number in <code>\doendnotes</code> . <code>oldprintnpnumspace</code> option allows to come back to previous setting	1
<code>parapparatus</code> option works now with familiar footnotes.	1
Provide <code>\@gobblefive</code>	88
v1.22.0.	
<code>\ledinnote</code> : <code>\ledinnote</code> takes a first optional argument, which is the label for hyperlinks.	309
General: Add <code>\doendnotesbysection</code> command.	26
Add option for lemma separator inside endnotes	44
Adds hyperlink for references to notes in indices.	1
Fix conflict between <code>noend</code> package option and <code>edtabularx</code> environments	1
Provides support for <code>xindy</code>	1
Standardize endnotes handbook.	26
When using <code>hyperref</code> package, internal links in index or with <code>\edlineref</code> are now targeted to the top and not longer to the bottom of the lines they refer to.	1
v1.22.1.	
<code>\prevpage@num</code> : Correct double symbol when using both <code>\parafootsep</code> and <code>\Xsymlinenum</code>	191
General: Fix a bug (added on v1.22.0) with <code>\Xinplaceofnumber</code> hook.	1
v1.23.0.	
<code>\@edtext@level</code> : The boolean <code>\if@edtext@</code> becomes the counter <code>\edtext@level</code>	133
<code>\Serefwithpage</code> : Debug <code>\Xendtwolines</code> , <code>\Xendmorethantwolines</code> , <code>\Xendtwolinesbutnotmore</code> and <code>\Xendtwolinesonlyinsamepage</code> when using <code>\apprefwithpage</code>	290
<code>\lemma</code> : Fix spurious space after <code>\lemma</code> command	138
<code>\newseries@</code> : Prevent spurious spaces when <code>\Afootnote</code> and similar commands are followed by spaces (bug added on 1.0.0).	251
<code>\sameword</code> : In order to allow use of <code>\sameword</code> with <code>inputenc</code> , we detokenize its mandatory argument before using it in control sequence names.	144
General: Add <code>\Xboxlinenumalign</code> and <code>\Xendboxlinenumalign</code>	43
Add <code>\Xboxstartlinenum</code> , <code>\Xendboxstartlinenum</code> , <code>\Xboxendlinenum</code> , <code>\Xendboxendlinenum</code>	43
Allow use of <code>\sameword</code> with <code>inputenc</code> managing of UTF-8.	1
Compatibility between <code>nofamiliar/nocriticals</code> option and <code>minipage/ledgroup</code>	1
Error message when using <code>\beginnumbering ... \endnumbering</code> without <code>\pstart</code>	1
Fix a bug with <code>\sameword</code> when the lemma overlaps multiple line.	28
Fix a bug with <code>\sameword</code> when the same lemma is used for multiple notes or for nested <code>\edtexts</code>	28
Fix a bug with <code>\skipnumbering</code> called immediately after a <code>\pstart</code>	1
Fix error of <code>\iftrue</code> not closed.	1
Fix spurious space with <code>\skipnumbering</code> (bug added on v1.21.0).	1
New tools to ensure the line-list file uses the right version of commands when upgrading the <code>eledmac</code> version.	1
Optional argument of <code>\sameword</code> can be a comma-separated list of <code>\edtext</code> depth.	28
v1.23.1.	
General: Fix a bug with <code>\lemma</code> command in the right side.	1

v1.23.2.	
General: Compatibility with L ^A T _E X's release 2015.	1
v1.24.0.	
General: We can reinitialize \AtEveryPstart and \AtEveryPend providing to it an empty argument.	1
v1.24.1.	
General: \lemma is disabled when using 'nocritical' option.	1
v1.24.2.	
General: Fix incompatibility between 'nofamiliar' option and 'memoir' package.	1
v1.24.3.	
General: Restore marginal numbers and notes with sectioning command (bug introduced in v1.21.0)	1
v1.24.4.	
General: Fix spurious space with \edindex when using xindy+hyperref option.	1
v1.24.5.	
General: Fix a bug of indent, when a added in 1.1.0, when a \beginnumbering immediately follow a sectioning command.	1
v2.0.0.	
\@iiiminipage: Patch \@iiiminipage instead of redefining it.	303
\@xypar: Patching \@xypar instead of redefining it	293
\endminipage: Patch \endminipage instead of redefining it.	304
\initnumbering@quote: \initnumbering@sectcmd becomes \initnumbering@quote	356
\l@advance@parledgroup@beforenormalnotes: Some conde of \l@dumboxmpfoot moved to \l@advance@parledegrou@beforenormalnotes	304
\newseries@: One endnotes file by series.	257
General: \@makecol, \@reinserts and \@doclearpage are patched instead of begin redefined	274
\doxtrafeeti becomes \Xdo@feet; \doxtrafeetii becomes \do@Xfeet; \@opxtrafeeti becomes \@opfeetX; \doreinxtrafeetii becomes \X@doreinfeet; \doreinxtrafeeti becomes \@doreinfeetX.	274
Add \Xendinplaceofnumber hook.	1
Add \Xendnonumber hook.	1
Add nonum option for endnotes.	1
Fix a bug when printing only one series of endnotes, but wanted to keep endnotes for other series.	1
In order to have a more consistent name's convention, many names has been changed.	1
Many L ^A T _E X's output macros are now patched and not override.	1
Package's name becomes reledmac	1
Patch \@footnotemark instead of redefine it	212
Suppress indexing command specific to memoir	310
v2.0.1.	
General: Fix a bug in elemac-compat option	1
Fix incompatibility between optional argument of \pstart and \numberpstarttrue	1
v2.1.0.	
General: Fix a bug with \advanceline at the beginning of a \pstart.	1
Fix a bug with \chapter in optional argument of \pstart in parallel typesetting with scrbook	1
Fix a bug with \elechapter in parallel typesetting with scrbook	1
Fix a bug with \setline at the beginning of a \pstart.	1

Fix spacing bug with <code>\Xbhooknote</code> and <code>\bhooknoteX</code> when using them to insert text and not to execute code.	1
New tools to number stanzas	1
v2.1.1.	
General: Fix a bug with <code>\ledpb{before}</code>	1
v2.1.2.	
General: Fix a bug with lineation by <code>pstart</code> and <code>tabular</code> environments (added in 2.1.0).	1
v2.1.3.	
<code>\ledsetnormalparstuffX</code> : Replaced <code>\noindent</code> with <code>\parindent</code> set to 0pt.	231
General: <code>\Xhangindent</code> and <code>\hangindentX</code> work now with all the paragraphs in the note.	1
<code>\Xnoindent</code> and <code>\noindentX</code> work now again (broken in 2.0.0).	1
Change some internal code in order to provide compatibility with L ^A T _E X release of october 2015	1
Fix a bug which inserted double space before paragraphed familiar notes.	1
Fix a bug with <code>\edindex</code> when using not-Latin characters without UTF-8 engines	1
v2.2.0.	
General: Fix a bug with combination of <code>\onehalfspacing</code> and two columns and three columns notes typeset.	1
Fix a bug with some setting command and optimization option.	1
Fix spurious space with paragraphed critical notes when using LuaL ^A T _E X.	1
Increase line list version number to ensure compatibility with new options of <code>uledpar</code> package.	1
New setting tools for endnotes: <code>\Xendnumberonlyfirstinline</code> , <code>\Xendnumberonlyfirsttwolines</code> , <code>\Xendsymlinenum</code> , <code>\Xendbeforeenum</code> , <code>\Xendafterenum</code> , <code>\Xendbeforesymlinenum</code> , <code>\Xendaftersymlinenum</code> , <code>\Xendboxsymlinenum</code> , <code>\Xendhangindent</code> , <code>\Xendbhooklinenum</code> , <code>\Xendahooklinenum</code> , <code>\Xendbhookinplaceofnumber</code> , <code>\Xendahookinplaceofnumber</code>	1
v2.2.1.	
General: Compatibility with L ^A T _E Xformat 2015/10/01.	1
v2.2.2.	
General: Fix a bug in <code>\sethangingsymbol</code>	1
Fix a bug with old version of <code>etex</code>	1
v2.3.0.	
General: Disable empty lines as paragraph in stanza.	1
Fix incompatibility of paragraphed footnotes with <code>bidi</code> v17.9 and following.	1
Warning message when using some setting commands inside rightside environment (deprecated behavior)	1
v2.3.1.	
General: Fix spurious space when using optional argument of <code>\stanza</code> (introduced in v2.3.0).	1
v2.4.0.	
<code>\footnoteoptions@</code> : First argument of <code>\footnoteoption@</code> is now mandatory, not optional.	176
General: <code>\Xbhooknote</code> and <code>\bhooknoteX</code> work with notes in columns.	1
Fix a bug of <code>\parindentX</code> and <code>\Xparindent</code> with two columns and three columns notes.	1
Fix a bug with <code>\sameword</code> in right side.	1
Fix spurious space in two columns and three columns notes.	1

Fix spurious space when using optional argument of stanza (introduced in v2.3.0).	1
New hooks: <code>\Xlinerangeseparator</code> and <code>\Xendlinerangeseparator</code>	40
Option linerangesep for critical footnotes and endnotes.	40
v2.4.1.	
General: Fix a bug with <code>\appref</code> and <code>\apprefwithpage</code> (introduced in v2.4.0).	1
Fix a bug with tabular environments when using <code>babel</code> or <code>polyglossia</code> languages that override L ^A T _E X <code>\roman</code> command, like Greek language.	1
Fix a bug with tabular environments when using <code>babel</code> or <code>polyglossia</code> languages that override L ^A T _E X <code>\roman</code> command, like Greek.	1
v2.5.0.	
<code>\SRefwithpage</code> : Debug <code>\setapprefprefixsingle</code>	289
<code>\edlabel</code> : Fix a bug when calling <code>\edlabel</code> in a footnotes of the right side	277
<code>\l@d@section</code> : <code>\endnotes</code> take six arguments.	237
<code>\printlines</code> : <code>\printlines</code> takes an eighth argument: the line flag	208
<code>\xlineref</code> : <code>\xlineref</code> does not include anymore the side flag. Use <code>\xflagref</code> to get it. Not that <code>\edlineref</code> still contains the flag.	283
General: <code>\apprefwithpage</code> and <code>\appref</code> print double quotation mark when the label was not defined.	1
<code>\apprefwithpage</code> and <code>\appref</code> work with right side crossref.	1
<code>\apprefwithpage</code> works also when <code>noend</code> option is enabled.	1
<code>\appref</code> and <code>\apprefwithpage</code> can take <code>linerangesep</code> optional argument.	1
<code>\edlabel</code> works now in <code>\Xfootnote</code>	1
<code>\lemma</code> can be used even when the <code>nocritical</code> is enabled.	1
Compatibility with new hook and tools of <code>reledpar</code> 2.6.0.	1
Fix spurious vertical space in <code>astanza</code> environment (<code>reledpar</code>)	1
Log now states ‘There were undefined references’ when using wrong references in <code>\edlineref</code> or <code>edpageref</code>	1
New hooks to customize page and line number appearance in endnotes.	1
New hooks: <code>\Xbhookgroup</code> and <code>\bhookgroupX</code>	1
New tools to easily make cross-reference to a passage defined by a start and an end line	61
v2.6.0.	
General: Adds compatibility with <code>innnote</code> and <code>notenumber</code> options of <code>indextools</code> package.	1
Fix a bug with footnote counter in <code>ledgroup</code> (added in v2.5.0).	1
Fix bug, introduced in v2.5.0, with footnote numbering in parallel typesetting when using <code>perpage</code> package.	1
v2.7.0.	
<code>\@k</code> : <code>\rigidbalance</code> is split in <code>\Xrigidbalance</code> and <code>\rigidbalanceX</code>	191
<code>\l@d@section</code> : <code>\endnotes</code> take seven arguments.	237
General: Add dash as default page range separator for <code>\SEonlypage</code>	1
Debug <code>\SRefonlypage</code> when referring to only one page.	1
Delete parenthesis after <code>\SRefonlypage</code>	1
Fix (again) bugs with footnote numbering in parallel typesetting while using <code>ledgroup</code> environments (bug added in v2.5.0).	1
Fix a bug with <code>\SRefwithpage</code>	1
Fix bugs in compatibility with <code>innote</code> and <code>notenumber</code> options of <code>indextools</code> package, when indexing outside of a <code>ledgroup</code>	1
New commands to make glossaries connected to page and linenumbers with the <code>glossaries</code> package	1
New hooks: <code>\Xhsizesize</code> and <code>\hsizesizeX</code>	50

New hooks: \Xlemmafont and \Xendlemmapfont	45
New setting commands: \setSErefonlypageprefixsingle and \setSErefonlypageprefixmore	1
Warning for duplicate and undefined labels are parsable by latexmk	1
Warning for duplicate labels does not send any more a false line and page number	1
When using hyperref package, add link in familiar footnotes between the footnote marks in the text and the footnote marks in the footnote	1
When using hyperref package, add links for \SEref and related, \appref and related	1
When using hyperref package, add links from critical footnotes and critical endnotes to the line of text they refers	1
v2.7.1.	
General: Debug \Xbhookgroup hooks executed on columnar footnotes (moved to a larger group, to take effect)	1
v2.7.2.	
General: \Xhsize and \hsizex become \Xwidth and \widthx	50
Fix problem of hyphenation when using hyperref package (added in v2.7.0)	1
v2.8.0.	
\l@d@section: \Xendhangindent and \Xendafternote can take values which are relative to the font size of the endnote.	237
General: reledmac cross-referencing can take advantage of xr package.	1
More \edgls... commands.	1
No indentation for paragraphed notes in ledgroup. Can be changed with \Xparindent and \parindentx.	1
v2.8.1.	
General: Warnings for undefined labels are really parsable by latexmk	1
v2.8.2.	
General: Fix a bug concerning indent in a paragraph immediately following a sectioning command (bug NOT fixed on reledpar)	1
Fix a bug with \AtEveryPstart added in version 2.0.0.	1
Fix a bug with vertical space after the between-sectioning command as optional argument of a \pstart and \pstart content	1
v2.9.0.	
General: Allow continuing line numbering between normal text and parallel text, using \pausenumbering and \resumenumbers and the continuousnumberingwithcolumns option.	1
Fix a bug when using \linenearation{page} and \pausenumbering...\resumenumbers.	1
Fix a bug with three- and two-column footnote setting (added in v.2.4.0).	1
Fix spurious space inside three-column familiar footnote.	1
Write correct metadata in numbered files when using \pausenumbering...\resumenumbers.	1
v2.9.1.	
General: Fix a bug when notes start with “plus” or “minus”.	1
v2.9.2.	
General: Fix a bug with hyperref package when a lemma starts with “plus” or “minus” (bug introduced in v. 2.7.0).	1
v2.9.3.	
General: Fix a bug with line number position and reset added by v. 2.9.0	1

v2.10.0.	
\print@lemma: Code refactoring between \parafootfmt, \twocolfootfmt, \threecolfootfmt and \normalfootfmt.	199
General: Add \AtEveryStanza and \AtEveryStopStanza.	1
Fix a bug in \ledlsnotefontsetup and \ledrsnotefontsetup which could not handle \color command properly.	1
More specific error messages.	1
New hooks: \Xwrapcontent, \Xendwrapcontent and \wrapcontentX.	46
New hooks: \Xwraplemma and \Xendwraplemma	46
v2.10.1.	
General: Add ‘nopenalties’ option.	1
Fix a bug introduced in v. 1.4: not paragraphed critical footnotes could prevent marginal line number from being displayed	1
v2.11.0.	
\do@actions@fixedcode: Add action 1010	161
General: Add new tools to produce an apparatus of manuscripts	1
Fix a bug in \Xparafootsep in parallel typesetting	1
Make \parafootsepX work	1
Prevent \Xtxtbeforenotes hook from causing notes to go beyond the bottom margin	1
v2.12.0.	
General: \preXnotes becomes \Xprenotes (naming convention)	1
Add \hidenumberingonleftpage and \hidenumberingonrightpage	1
Add \toendnotes and related.	1
Add auxdir option.	1
Fix a bug in critical and familiar footnotes when using uppercase letters with accent mark	1
Fix a bug when using \chapter in optional argument of \pstart in parallel typesetting in combination with the noeledsec option.	1
Fix a bug with \ledinernote and \ledouternote in parallel typesetting	1
Fix a bug with familiar footnote number in optional argument of \pstart or \pend in parallel typesetting	1
Fix spurious vertical space in \chapter when used as optional argument of \pstart in parallel typesetting.	1
Make endnote compatible with \samedword mechanism	1
More accurate message to control the position of \Xfootnote and \applabel in the \TeX code	1
v2.13.0.	
General: Version 2.13.0 never existed.	1
v2.13.1.	
General: In critical footnotes, the right side flag is printed only if requested explicitly with \Xlineflag (bug added in v. 2.5.0).	1
v2.13.2.	
General: Fix a bug added in v. 11.2 which could make parallel typesetting not work.	1
v2.13.3.	
General: Makes \Xendafterpagenumbe affecting \Serefwithpage	1
v2.14.0.	
General: Hyperref with the line number inside critical footnotes is correct when using \xxref	1
Some internal changes for new features of reledpar.	1

v2.14.1.	
General: Fix a bug when using \footnoteX in the first argument of \edtext.	1
v2.14.1a.	
General: Fix problematic typos in the handbook.	1
v2.15.0.	
General: Add ‘byline’ arrangement.	1
Fix \Xtxtbeforenotes in ledgroup.	1
v2.15.1.	
General: Fix \edindex in tabular environments.	1
v2.15.2.	
General: Fix a bug with fancyhdr package 3.8 and later.	1
v2.15.3.	
General: Fix a bug with \section in optional argument of \pstart and empty line before \pend (bug added in v2.8.2).	1
Simplification of the sectioning command code.	1
v2.16.0.	
General: \Xdo@feet becomes \do@Xfeet	274
Add \Xendpagenumberonlyfirst, \Xendpagenumberonlyfirstifsingle, \Xendpagenumberonlyfirstintwo, \Xendinplaceofpagenumber and \Xendsympagenum hooks.	1
Add \Xpagelinesep hook.	42
Compatibility with new features of reledpar	1
Deleted dead code.	1
Display a warning message if using a version of L ^A T _E X that is too old.	1
Fix a bug with \Xgroupbylines for notes in two columns	1
Fix a bug with \Xtxtbeforenotes for notes in three or two columns	1
Fix a bug with ‘notenumber’ option of indextools package when indexing texts in familiar footnotes.	1
Fix potential bug when using \edindex in critical footnotes.	1
More explicit error message in case the stanza indentation is not defined.	274
New options for \fnpos and \mpfnpos to set a customized order for familiar and critical footnotes.	1
When \edindex is called outside of a \beginnumbering... \endnumbering structure, it is automatically switched to \index, with a warning message.	1
When indexing texts in familiar footnotes with \edtext, refer to the line number where the footnote is called.	1
When indexing texts in sidenotes with \edtext, refer to the line number where the sidenote is called.	1
v2.16.1.	
General: Fix a bug with redefinition of the style of the footnote number (bug added in v2.12.0)	1
v2.16.2.	
General: Error message if footmisc is loaded after reledmac.	1
Fix a bug introduced by v2.16.1 when using non-expandable control sequence, like \normalfont, in the footnote number style.	1
v2.16.3.	
General: Fix a bug with \SEref (bug added in v2.7.0).	1
v2.16.4.	
General: Fix a bug with vertical space before sectioning command in optional argument of \pstart (bug added in v2.15.3).	1

v2.16.5.		
General: Fix potential spurious spaces in endnotes.	1	
v2.16.6.		
General: Fix a bug with the line number style in \doenotes when referring to right side line in parallel typesetting.	1	
Take into account \linenumberstyle when using \edlineref.	1	
v2.16.7.		
General: Fix a bug with \msdata when using multiple \beginnumbering ... \endnumbering.	1	
Fix a bug with \numberpstarttrue when using multiple \beginnumbering ... \endnumbering.	1	
v2.16.8.		
General: Fix a bug with \edindex in footnotes in parallel typesetting.	1	
v2.17.0.		
General: Add \edglsadd command.	1	
Add \setmsdataposition setting.	1	
v2.17.1.		
General: Fix spurious space in paragraphed footnotes when using Lua ^E T _E X without using Right-To-Left text.	1	
v2.17.2.		
General: Change log message when numbered files still don't exist, in order to improve compatibility with <i>latexmk</i>	1	
v2.17.3.		
General: Fix a bug with \doendnotesbysection and \doendnotes.	1	
v2.17.4.		
General: Fix a bug with \setSerefonlypageprefixsingle and \setSerefonlypageprefixmore.	1	
v2.17.5.		
General: Fix a bug with \pstartref when referring to the left side in parallel typesetting.	1	
v2.18.0.		
General: Fix a bug when using a \edtext in two lines or more in right-to-left typesetting with X _U ^E T _E X.	1	
Fix a bug when using both \Xnumberonlyfirstintwolines or \Xnumberonlyfirstinline and \Xparafootsep and \Xsymlinenum.	1	
v2.18.1.		
General: Fix a bug when using \msdata with Lua ^E T _E X or with the hyperref package.	1	
v2.19.0.		
General: Add \footnoteXmark and \footnoteXtext commands.	1	
Add better compatibility with the csquotes package when using familiar footnotes.	1	
Fix a bug with paragraph indent after sectioning command.	1	
v2.20.0.		
General: Add \AtStartEveryStanza, \BeforeEveryStopStanza, \AtEndEveryPend, \AtStartEveryPstart.	1	
Add second optional argument to \pstart, \pend and \stanza.	1	
Add starred version of \AtEveryPstart, \AtEveryPend, \AtEveryStanza and \AtEveryStopStanza.	1	
Add third and fourth optional argument to \newverse.	1	
Fix a bug when using familiar footnotes in \eledsection and related.	1	
Reset font specification at the beginning of familiar footnotes.	1	

v2.21.0.	
General: Add the possibility of nested \sameword commands.	1
Fix a bug when using formatting command in the argument of \edindex inside \edtext.	1
Now, as explained in the handbook, a \edindex inside \edtext only creates an index reference to the main text, and not to the critical footnote.	1
v2.22.0.	
General: Add \txtbeforenotesonlyonceX and \Txtbeforenotesonlyonce hooks.	1
Add \txtbeforenotesX hook.	1
Fix a bug added in v2.16.0 when using \Txtbeforenotes with paragraphed or normal footnotes.	1
Fix a bug with three and two columns critical footnotes, broken in v. 2.17.6.	1
v2.22.1.	
General: Compatibility with new version of reledpar.	1
Fix a bug with some commands inside \sameword.	1
v2.22.2.	
General: Do not print footnotes at the first run.	1
v2.23.0.	
General: Add s wcaseinsensitive option	1
Optimisation of the code added on v2.22.2 to not print footnotes at the first run.	1
v2.24.0.	
\next@line@list@stuff: Add \next@line@list@stuff internal hook.	124
General: Add \swnoexpands macro to avoid problems with not fully expandable macro inside \sameword.	1
Fix a bug with \edlabel at the beginning of a \pstart.	1
Fix spurious space with \labelpstarttrue	1
When a \setlinenum is used, it is stronger than the \lineation{page} setting.	1
v2.24.1.	
General: Compatibility with reledpar 2.20.2	1
v2.24.2.	
General: Fix bug between tabular environments and endnotes	1
v2.25.0.	
General: Add \Xendtxtbeforenotes hook	1
v2.26.0.	
General: Add a mechanism for annotation of stanza line numbering	1
Fix bug in \xpstartref	1
v2.26.1.	
General: Fix bug with \linenumberannotation	1