

Typesetting Articles for *Res Philosophica*^{*}[†]

Boris Veytsman[‡]

2013/09/12, v1.15

Abstract

This package provides a class for typesetting articles for the journal *Res Philosophica*, <http://www.resphilosophica.org>.

Contents

1	Introduction	2
2	User Interface	2
2.1	Commercial Fonts	2
2.2	Invocation and Options	2
2.3	Topmatter	3
2.3.1	Commands for Authors	3
2.3.2	Commands for Editors	4
2.4	Bibliography	5
3	Implementation	8
3.1	Options	8
3.2	Loading Classes and Packages	10
3.3	Page Dimensions and Paragraphing	11
3.4	Headers	11
3.5	Top Matter Macros	13
3.6	Typesetting Top Matter	16
3.7	Typesetting End Matter	19
3.8	Sectioning	20
3.9	Additional Commands	21
3.10	The End	22

^{*}©2012, Boris Veytsman

[†]This work was commissioned by the Saint Lois University

[‡]borisv@lk.net, boris@varphi.com

1 Introduction

According to the statement at <http://www.resphilosophica.org/>, *Res Philosophica* is an international, quarterly journal of philosophy that publishes research in all areas of philosophy, historical and topical. Founded as *The Modern Schoolman* by Jesuit Scholastics in 1925, the journal is edited by members of the Philosophy Department at Saint Louis University and supported generously by the College of Arts and Sciences.

This package is intended for the authors and editors of the journal to typeset the articles in L^AT_EX. Note that the journal is typeset in *Linotype Sabon*, with some elements in MT Imprint Shadow. The users may buy the fonts and install their free L^AT_EX support [1, 2], or use the options `bodyfont=cm` and `rfont=cm` to typeset the articles using Computer Modern. Of course, the line and page breaks in the latter case are different from those in the final version typeset with commercial fonts.

2 User Interface

2.1 Commercial Fonts

The package can be used with free Computer Modern fonts or with commercial fonts to mimick the journal typesetting. The installation of additional fonts is therefore fully optional.

Res Philosophica uses Linotype Sabon for the body text, Monotype Imprint Shadow for some titles and URW Garamond for mathematics. Sabon and MT Imprint Shadow are commercial fonts. URW Garamond is free, but due to license restrictions it is usually not included with TeXLive, MikTeX and other major distributives. If you bought Linotype Sabon, you need to install the package `lsabon` [1]. If you bought MT Imprint Shadow, you need to install the package `imprintshadow` [2]. To use URW Garamond, you need to download the `pfb` files from a CTAN mirror (<http://ctan.org/tex-archive/fonts/urw/garamond>), install them in the directory `fonts/type1/urw/garamond` under \$TEXMFLOCAL and run `texhash`.

2.2 Invocation and Options

To use the class put in the preamble of your document

```
\documentclass[<options>]{resphilosophica}
```

The class `resphilosophica` internally loads `amsart`, and therefore all class options for `amsart` are technically valid. However, most of them are not especially meaningful for `resphilosophica`. There are several options specific for this class. They are described below. Note that the class uses key-value interface for some options, for example

```
\documentclass[bodyfont=sabon]{resphilosophica}
```

option
bodyfont The option **bodyfont** can have three values: **sabon** for Sabon/Garamond fonts, **cm** for Computer Modern and **auto** (default). The later option switches to the use of Sabon if the font metrics are present in your system, and to the use of Computer Modern otherwise.

option
rpfont The name of journal, *Res Philosophica*, is typeset with the special font. The option **rpfont** can have three values: **imprintshadow** for MT Imprint Shadow, **cm** for Computer Modern and **auto** (default). The later option switches to the use of MT Imprint Shadow if the font metrics are present in your system, and to the use of Computer Modern otherwise.

option
manuscript The option **manuscript** is intended to facilitate the communications between the editor and the author. It enables two things:

1. The numbering of lines in the manuscript is switched off in the normal mode, but is on in the manuscript mode.
2. The command `\EditorialComment` is no-op in normal mode, but produces marginal commentaries in the manuscript

option
preprint The option **preprint** is for the final version of the manuscript. In this mode there are no editorial comments, but the numbering of lines is preserved

option
screen The option **screen** is intended for the screen reading. When this option is selected, the links become highlighted.

option
forthcoming The option **forthcoming** is like **screen**, but it is used when there is no information about the volume and or dates for publication.

option
natbib The preferred solution for bibliography is **natbib** package [3]. The option **natbib=true** (default) sets the package and the proper options, including bibliography style. The option **natbib=false** switches this behavior off, and the formatting of the bibliography becomes the full responsibility of the author. The package includes the BibTeX bibliography style **resphilosophica.bst**.

2.3 Topmatter

Topmatter is the part of the article with the informations about the authors, their affiliations, the publication data, etc.

There are two kinds of top matter commands: the ones used primarily for authors and the ones used primarily for editors. We describe them separately.

2.3.1 Commands for Authors

`\title` The command `\title`, as in **amsart** class, has two arguments: one optional, and one mandatory:

`\title[<ShortTitle>]{<FullTitle>}`

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

`\author` The interface for specifying the authors and their affiliations is close the the

`\email`

`\address`

`\curraddr`

`\urladdr`

one of `amsart` [4] (and different from the standard L^AT_EX). For each author a separate command `\author` should be used, followed by `\address` and (optionally) `\curraddr`, `\email` and `\urladdr`.

`\shortauthors`

In some cases the authors list may be too long for the running head, even if the abbreviated forms are used for each author. In this case it is possible to change the running head by a *redefinition* of the command `\shortauthors`. This redefinition must be done after all `\author` commands, but before `\maketitle`:

```
\renewcommand{\shortauthors}{A.~Smith et al}
```

`\thanks`

Like `amsart` (and unlike standard L^AT_EX), `resphilosophica` allows `\thanks` only *outside* of commands `\title` and `\author`. The text of `\thanks` is typeset at the end of the paper as a footnote marked ‘Acknowledgements’. Note that the right vertical positioning of this footnote might require an additional run of L^AT_EX.

`\titlenote`

The `\titlenote{<note>}` command creates a specific footnote for the title. This command should be issued *outside* the `\title` command.

`\copyrightnote`

Normally each paper is copyrighted by the authors and by the journal. This is reflected in the footnote on the first page of the article. However, by arrangement with the editors, certain papers may have different copyright. The command `\copyrightnote{<copyright statement>}`, if issued, changes the footnote to the corresponding text, for example:

```
\copyrightnote{\textcopyright 2012 by the authors. This paper may  
be reproduced, in its entirety, for noncommercial purposes.}
```

Note that if you issue this command, you should explicitly include both the copyright sign and the year unless the paper does not have a copyright, for example:

```
\copyrightnote{This paper is in the public domain}
```

`\copyrightyear`

Normally the copyright statement includes the year of copyright, which is assumed to be the publication year as specified by the `\publicationyear` command (see below). If this assumption is wrong, you may correct it, for example,

```
\copyrightyear{1998}
```

`\abstract`

The abstract of the paper must be put between `\begin{abstract}` and `\end{abstract}`. Unlike the situation in `amsart` class, abstract may be put *after* `\maketitle`.

`\maketitle`

The macro `\maketitle` typesets the top matter. All top matter information should be specified before this command.

2.3.2 Commands for Editors

The commands described in this section should be used by the editors to insert the information about the published paper. They must be put before the `\maketitle` command.

```

\volumenumber
\issuenumber
\publicationyear
\publicationmonth
\papernumber
\startpage
\endpage

```

The macros `\volumenumber`, `\issuenumber`, `\publicationyear`, `\publicationmonth`, `\papernumber`, `\startpage`, `\endpage` set up the corresponding data for the paper, for example:

```

\volumenumber{88}
\issuenumber{1--2}
\publicationyear{2012}
\publicationmonth{January and April}
\papernumber{2}
\startpage{1}
\endpage{39}

```

Note that if the argument of `\endpage` is empty, L^AT_EX tries to calculate the last page number as best as it can.

`\doinumber`

Normally you do not need to set the DOI of the paper: T_EX will construct the number using the paper data (including paper number in the current issue). However, you *may* override its decision using the command `\doinumber` which sets the DOI explicitly, for example, `\doinumber{\langle10.11612/resphilosophica.2013.01.01\rangle}`. You probably should not use this macro.

`\prevpaper`

Instead of setting `\startpage`, one can use the the command `\prevpaper{\langle previous paper\rangle}`, with the argument being the location and file name of the previous paper in the journal, for example:

```
\prevpaper{../infinity/concept_of_infinity}
```

Note that the `.tex` suffix should *not* be used. The previous paper must be processed by `latex` prior to the current one. In this case `latex` will read the last page of the previous paper, and start the current one from the proper page number.

`\EditorialComment`

The macro `\EditorialComment[(comments)]` typesets the comments on the margins in the `manuscript` mode, for example,

```
Which is a well known fact.\EditorialComment{A citation is
needed}
```

2.4 Bibliography

As mentioned above, `resphilosophica` by default uses `natbib` [3]. You should use `natbib` commands like `\citet`, `\citep` etc.

Note that `\bibliographystyle` command should *not* be issued by the author: the package takes care of this. You just need to type

```
\bibliography{DATABASE, DATABASE...}
```

The bibliography style used for the articles is `resphilosophica.bst`. Compared to standard styles it has two additional fields:

doi: DOI number of the publication. Write there only the number: the style will automatically add <http://dx.doi.org> and make the reference clickable.

titlenote: the note that should be put after the title rather than at the end of the entry¹, for example, the information about translators, editors of critical editions, etc:

```
@book{Knuth94:TheTeXbook,
  address = {Reading, MA},
  author = {Knuth, Donald Ervin},
  titlenote = {Illustrations by Duane Bibby},
  publisher = {Addison-Wesley Publishing Company},
  series = {Computers \& Typesetting A},
  title = {The \TeX book},
  year = {1994},
}
```

\suppresscomma Sometimes BibTeX inserts an unwanted comma into an entry, for example, in the following one:

```
@incollection{ande97a,
  Address = {Macon, GA},
  Author = {Anderson, Thomas C.},
  Booktitle = {Concluding Unscientific Postscript to
  \enquote{Philosophical Fragments},},
  Date-Modified = {2013-09-04 21:27:17 +0000},
  Editor = {Robert Perkins},
  Owner = {Andrew},
  Pages = {187--204},
  Publisher = {Mercer University Press},
  Series = {International Kierkegaard Commentary},
  Timestamp = {2013.09.04},
  Title = {Kierkegaard and Approximation Knowledge},
  Volume = {12},
  Year = {1997}}
```

The command `\suppresscomma` suppresses the next comma:

```
Booktitle = {Concluding Unscientific Postscript to
\enquote{Philosophical Fragments,\suppresscomma}},
```

\AddtoEndMatter If you decide to forgo `natbib`, you can use `natbib=false` option. Then you should remember to put the bibliography *after* the end matter (authors' addresses etc) using the command `\AddtoEndMatter`:

```
\AddtoEndMatter{MY BIBLIOGRAPHY COMMANDS}
```

¹This field was proposed by Maureen Shupsky for the *Annals of Mathematics* bibliography style.

Acknowledgements

This package was commissioned by the journal *Res Philosophica* and funded by Saint Louis University. I am grateful to Jonathan Jacobs for tireless testing of the package.

3 Implementation

3.1 Options

We need `xkeyval` since some of our options may have values:

```
1 \RequirePackage{xkeyval}
```

`\ifRESP@fontauto` First, check whether the user have the body font explicitly configured:

```
2 \newif\ifRESP@fontauto
3 \RESP@fontautotrue
```

`\ifRESP@rpfontauto` Same for *Res Philosophica* font

```
4 \newif\ifRESP@rpfontauto
5 \RESP@rpfontautotrue
```

`\ifRESP@lsabon` Are we using linotype sabon?

```
6 \newif\ifRESP@lsabon
7 \RESP@lsabonfalse
```

`\ifRESP@mtshadow` Are we using MT Imprint Shadow?

```
8 \newif\ifRESP@mtshadow
9 \RESP@mtshadowfalse
```

`bodyfont` And the option to check the user input:

```
10 \define@choicekey**+{resphilosophica.cls}{bodyfont}[\val\nr]{auto,
11   sabon, lsabon, cm}[auto]{%
12   \ifcase\nr\relax
13     \RESP@fontautotrue
14   \or
15     \RESP@fontautofalse
16     \RESP@lsabontrue
17   \or
18     \RESP@fontautofalse
19     \RESP@lsabontrue
20   \or
21     \RESP@fontautofalse
22     \RESP@lsabonfalse
23 \fi}{%
24 \PackageWarning{resphilosophica}{The option bodyfont must be auto,
25   sabon or cm. Using auto}\RESP@fontautotrue}
```

`rpfont` And the option to check the user input:

```
26 \define@choicekey**+{resphilosophica.cls}{rpfont}[\val\nr]{auto,
27   imprint, imprintshadow, cm}[auto]{%
28   \ifcase\nr\relax
29     \RESP@rpfontautotrue
30   \or
31     \RESP@rpfontautofalse
32     \RESP@mtshadowtrue
```

```

33   \or
34     \RESP@rpfontautofalse
35     \RESP@mtshadowtrue
36   \or
37     \RESP@rpfontautofalse
38     \RESP@mtshadowfalse
39   \fi}%%
40 \PackageWarning{resphilosophica}{The option rpfont must be auto,
41   imprintshadow or cm. Using auto}\RESP@rpfontautotrue}

natbib Checking natbib option:
42 \define@boolkey+{resphilosophica.cls}[RESP@]{natbib}[tue]{}{%
43   \PackageWarning{resphilosophica}{The option natbib must be
44     yes or no. Using yes}}
45 \RESP@natbibtrue

The size-changing options produce a warning:
46 \long\def\RESP@size@warning#1{%
47   \ClassWarning{RESPart}{Size-changing option #1 will not be
48     honored}}%
49 \DeclareOptionX{8pt}{\RESP@size@warning{\CurrentOption}}%
50 \DeclareOptionX{9pt}{\RESP@size@warning{\CurrentOption}}%
51 \DeclareOptionX{10pt}{\RESP@size@warning{\CurrentOption}}%
52 \DeclareOptionX{11pt}{\RESP@size@warning{\CurrentOption}}%
53 \DeclareOptionX{12pt}{\RESP@size@warning{\CurrentOption}}%

\ifRESP@manuscript Manuscript mode:
54 \newif\ifRESP@manuscript
55 \RESP@manuscriptfalse
56 \DeclareOptionX{manuscript}{\RESP@manuscripttrue}

\ifRESP@screen Screen mode:
57 \newif\ifRESP@screen
58 \RESP@screenfalse
59 \DeclareOptionX{screen}{\RESP@screentrue}

\ifRESP@preprint Whether we are in the preprint mode
60 \newif\ifRESP@preprint
61 \RESP@preprintfalse
62 \DeclareOptionX{preprint}{\RESP@preprinttrue}

\ifRESP@forthcoming Whether we are in the forthcoming mode
63 \newif\ifRESP@forthcoming
64 \RESP@forthcomingfalse
65 \DeclareOptionX{forthcoming}{\RESP@forthcomingtrue}

All other options are passed to amsart:
66 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
And executing options:
67 \ProcessOptionsX

```

3.2 Loading Classes and Packages

We use `amsart` since it has nice features for front matter:

```

68 \LoadClass[noamsfonts]{amsart}
    Some packages
69 \RequirePackage{microtype, fancyhdr, xcolor, lastpage}
70 \RequirePackage[bottom,multiple]{footmisc}
71 \RequirePackage[hyperfootnotes=false]{hyperref}
72 \urlstyle{rm}
73 \ifRESP@manuscript\hypersetup{colorlinks,allcolors=blue}\else
74   \ifRESP@screen\hypersetup{colorlinks,allcolors=blue}\else
75     \ifRESP@preprint\hypersetup{colorlinks,allcolors=blue}\else
76       \ifRESP@forthcoming\hypersetup{colorlinks,allcolors=blue}\else
77         \hypersetup{hidelinks}\fi\fi\fi\fi

```

The font to use depends on the options. Note that L^AT_EX cannot reliably determine whether a binary file like `SabonLTRom.pfb` exists in the system, so we check for the `.fd` file instead (sigh):

```

78 \ifRESP@fontauto
79   \IfFileExists{t1lsb.fd}{\RESP@lsabontrue}{\RESP@lsabonfalse}\fi

```

If the user wants, we load Sabon and URW Garamond. Note that `mathdesign` defines `sc` to be `fsc`, so we need to redefine it for Sabon:

```

80 \ifRESP@lsabon
81   \RequirePackage[mdugm]{mathdesign}
82   \RequirePackage[rmdefault]{lsabon}
83   \renewcommand\scdefault{sc}
84 \fi

```

Checking the existence of `miih` font metrics:

```

85 \ifRESP@rpfontauto
86   \IfFileExists{t1miih.fd}{\RESP@mtshadowtrue}{\RESP@mtshadowfalse}\fi

```

`\rpdefault` This is the font for *Res Philosophica*:

```

87 \ifRESP@mtshadow
88   \def\rpdefault{miih}\else
89   \def\rpdefault{\rmdefault}\fi

```

`\AddtoEndMatter` A syntax sugar to add something after signature:

```

90 \def\AddtoEndMatter#1{\g@addto@macro\enddoc@text{#1}}

```

And loading natbib:

```

91 \ifRESP@natbib
92   \RequirePackage[round]{natbib}
93   \AtEndDocument{\bibliographystyle{resphilosophica}}
94   \let\RESP@bibliography=\bibliography
95   \def\bibliography#1{\AddtoEndMatter{\RESP@bibliography{#1}}}
96   \def\bibsection{\par\addpenalty\@secpenalty\addvspace{\bigskipamount}%
97     \noindent \Small References:\par\nobreak\vskip\medskipamount\@afterheading}
98   \def\bibfont{\Small}
99 \fi

```

3.3 Page Dimensions and Paragraphing

```
\pdfpaperwidth Paper:  
\pdfpaperheight 100 \ifRESP@manuscript\else  
101 \AtBeginDocument{\setlength{\pdfpagewidth}{432bp}}%  
102 \setlength{\pdfpageheight}{648bp}  
103 \fi  
  
\textwidth The size of the type block:  
\textheight 104 \setlength{\textwidth}{318pt}  
105 \setlength{\textheight}{540pt}  
  
\evensidemargin The margins:  
\oddsidemargin 106 \setlength{\evensidemargin}{-18pt}  
107 \setlength{\oddsidemargin}{\evensidemargin}  
  
\topmargin Top margin  
108 \setlength{\topmargin}{-48pt}  
  
\listsep This is the space around lists. amsart defines it as \smallskipamount. We slightly  
increase it:  
109 \listsep\medskipamount
```

3.4 Headers

```
\headsep Separation between the header and the body  
110 \setlength{\headsep}{14pt}  
  
\headheight The height of the headers:  
111 \setlength{\headheight}{12pt}  
  
\headrulewidth We do not want decorative rules in the journal:  
\footrulewidth 112 \renewcommand{\headrulewidth}{0pt}  
113 \renewcommand{\footrulewidth}{0pt}  
  
\footskip Separation between the footer and the body  
114 \setlength{\footskip}{20pt}  
  
\RESP@printlinecount Do we want to print line count?  
115 \newif\ifRESP@printlinecount  
116 \RESP@printlinecountfalse  
117 \ifRESP@manuscript\RESP@printlinecounttrue\fi  
118 \ifRESP@preprint\RESP@printlinecounttrue\fi  
  
\RESP@linecount This is the box displayed in the manuscript mode  
119 \ifRESP@printlinecount  
120 \newsavebox{\RESP@linecount}  
121 \savebox{\RESP@linecount}[4em][t]{\parbox[t]{4em}{%
```

```

122      \atempcpta\@ne\relax
123      \loop{\color{red}\scriptsize\the\atempcpta} \\
124      \advance\atempcpta by \atempcpta<47\repeat}
125 \fi

```

It is easy to set up headers with `fancyhdr`:

```

126 \pagestyle{fancy}
127 \fancyhead{}
128 \fancyfoot{}
129 \fancyhead[LE]{\footnotesize\thepage\qquad\itshape\shortauthors}
130 \fancyhead[RO]{\footnotesize\textit{\shorttitle}\qquad\thepage}
131 \ifRESP@printlinecount
132   \fancyhead[LE]{\begin{picture}(0,0)%
133     \put(-26,-22){\usebox{\RESP@linecount}}%
134   \end{picture}\footnotesize\thepage\qquad\itshape\shortauthors}
135   \fancyhead[LO]{\begin{picture}(0,0)%
136     \put(-21,-22){\usebox{\RESP@linecount}}%
137   \end{picture}}
138 \fi
139 \ifRESP@manuscript
140   \fancyfoot[C]{\scriptsize\color{red}Author's Proof}%
141 \fi
142 \ifRESP@preprint
143   \fancyfoot[C]{\scriptsize\color{red}Author's Pre-Print}%
144 \fi

```

The first page has the special headers. The style `firstpage` is invoked by `amsart`; here we just redefine it.

```

145 \fancypagestyle{firstpage}{%
146   \fancyhf{}%
147   \ifRESP@printlinecount
148     \lhead{\begin{picture}(0,0)%
149       \put(-26,-20){\usebox{\RESP@linecount}}%
150     \end{picture}}
151   \fi
152   \ifRESP@preprint
153     \cfoot{\footnotesize\fontfamily{\rpdefault}\selectfont Res Philosophica,}
154     \itshape Vol.\~\currentvolume, No.\~\currentissue,
155     \currentmonth\~\currentyear
156     \ifx\@doinumber\empty\else\%\%
157     \doi{\@doinumber}\fi
158     \\
159     \copyrightnote{%
160       \chead{\scriptsize\color{red}Author's Pre-print. Forthcoming in
161       Res Philosophica. Pagination may change. Published version will
162       be available at \url{http://pdcnet.org/resphilosophica/}}}
163   \else
164   \ifRESP@forthcoming
165     \cfoot{\footnotesize\itshape Res
166       Philosophica}%

```

```

167      \ifx\currentvolume\empty\else, %
168      Vol.\~\currentvolume\fi
169      \ifx\currentissue\empty\else, No.\~\currentissue\fi
170      \ifx\currentmonth\empty
171          \ifx\currentyear\empty\else, \currentyear\fi
172      \else,
173          \currentmonth\~\currentyear
174      \fi
175      \ifx\@doinumber\empty\else\\%
176      \doi{\@doinumber}\fi
177      \\
178      \copyrightnote%
179      \chead{\vspace*{-\bigskipamount}\footnotesize Forthcoming in \emph{Res
180      Philosophica}%
181      \ifx\currentvolume\empty\else\~\currentvolume
182      \ifx\currentissue\empty\else:\currentissue\fi\fi
183      \ifx\currentyear\empty\else\~(\currentyear)\fi.}
184  \else
185      \cfoot{\footnotesize\fontfamily{\rpdefault}\selectfont Res Philosophica,}
186      \itshape Vol.\~\currentvolume, No.\~\currentissue,
187      \currentmonth\~\currentyear, pp.\~\start@page--\end@page
188      \ifx\@doinumber\empty\else\\%
189      \doi{\@doinumber}\fi
190      \\
191      \copyrightnote%
192  \fi\fi}

```

3.5 Top Matter Macros

Most top matter macros are defined in `amsart`. Here we just add some new macros and redefine some.

The next macros mimic the functionality of `amsart \issueinfo` command.
Note that `\issueinfo` still works.

<code>\volumenumber</code>	This sets the volume of the paper
	193 <code>\def\volumenumber#1{\def\currentvolume{#1}}</code>
	194 <code>\volumenumber{}</code>
<code>\issuenumber</code>	This sets the issue of the paper:
	195 <code>\def\issuenumber#1{\def\currentissue{#1}}</code>
	196 <code>\issuenumber{}</code>
<code>\publicationyear</code>	This sets the year of the paper
	197 <code>\def\publicationyear#1{\def\currentyear{#1}}</code>
	198 <code>\publicationyear{}</code>
<code>\publicationmonth</code>	This sets the month of the paper
	199 <code>\def\publicationmonth#1{\def\currentmonth{#1}}</code>
	200 <code>\publicationmonth{}</code>

- \papernumber This is absent from the \issueinfo.
- ```

201 \def\papernumber#1{\def\currentpaper{#1}}
202 \papernumber{0000}
203 %
204 % \end{macro}
205 %
206 %
207 % \begin{macro}{\doinumber}
208 % \changes{v1.11}{2012/12/25}{Added default}
209 % DOI number for the article:
210 % \begin{macrocode}
211 \def\doinumber#1{\gdef\@doinumber{#1}}
212 \doinumber{10.11612/resphil.\currentyear.\currentvolume.\currentissue.\currentpaper}

```
- \startpage This defines the starting page of the paper. We have some nice features to set up roman page numbers for editorial stuff—probably not needed for this journal at this time...
- ```

213 \def\startpage#1{\pagenumbering{arabic}\setcounter{page}{#1}%
214   \def\start@page{#1}%
215   \ifnum\c@page<\z@ \pagenumbering{roman}\setcounter{page}{-#1}%
216     \def\start@page{\romannumeral#1}%
217   \fi}

```
- \endpage This macro again has a twist in it: if the argument is not set, it calculates the last page number itself.
- ```

218 \def\endpage#1{\def\@tempa{#1}%
219 \ifx\@tempa\empty\def\end@page{\pageref{LastPage}}%
220 \else\def\end@page{#1}\fi}

```
- \pagespan This macro is different from the one provided by `amsart` because we want to have the option of automatic calculation of the last page number.
- ```

221 \def\pagespan#1#2{\startpage{#1}\endpage{#2}}
222 \pagespan{1}{}

```
- \articleentry This is necessary for \prevpaper command. We read the TOC entry from the previous paper and increment it by 1. Note that we always start with an odd page, since the additional check
- ```

223 \def\articleentry#1#2#3#4{@tempcnta=#4\relax
224 \advance\@tempcnta by 1\relax
225 \ifodd\the\@tempcnta\else\advance\@tempcnta by 1\relax\fi
226 \startpage{\the\@tempcnta}}

```
- \prevpaper This sets the previous paper location and reads the information from the previous paper
- ```

227 \def\prevpaper#1{\IfFileExists{#1.rpi}{%
228   \ClassInfo{resphilosophica}{%
229     Reading first page number from the file #1.rpi}%
230   \input{#1.rpi}}

```

```

231 }{\ClassWarning{resphilosophica}{Cannot find the file #1.rpi.
232 Did you run latex on the previous paper?}}}

abstract We slightly redefine abstract comparing to amsart conventions:
233 \renewenvironment{abstract}{%
234   \ifx\maketitle\relax
235     \ClassWarning{resphilosophica}{Abstract should precede
236       \protect\maketitle\space in AMS derived classes}%
237   \fi
238   \global\setbox\abstractbox=\vtop\bgroup%
239   \vglue1pc%
240   \list{}{\labelwidth\z@%
241     \leftmargin3pc \rightmargin\leftmargin%
242     \listparindent\normalparindent \itemindent\z@%
243     \parsep\z@ \z@plus\p@%
244     \let\fullwidthdisplay\relax%
245   }%
246   \item[]\normalfont\normalsize\textrm{\bf{\abstractname:}}\space
247 }%
248 \endlist\egroup%
249 \ifx\@setabstract\relax\@setabstract\fi%
250 }

\copyrightyear This is the copyright year in case it does not coincide with the publication year:
251 \def\copyrightyear#1{\def\@copyrightyear{#1}}
252 \ifRESP@forthcoming
253   \copyrightyear{\the\year}\else
254   \copyrightyear{}\fi

\RESP@bulletboxwidth This is the width of a box with a bullet for copyright note:
255 \newlength\RESP@bulletboxwidth
256 \settowidth\RESP@bulletboxwidth{\quad\textrm{\textbullet}\quad}

\copyrightnote This is the copyrightnote. The default has some trickery with the year and short authors.
The disappearing bullet is based on the trick by Marcin Woliniński, who noted that \cleders are discardable (see [5]).
257 \def\copyrightnote#1{\def\@copyrightnote{#1}}
258 \copyrightnote{\textcopyright~}
259 \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
260 \shortauthors\cleders\hbox{\quad\textrm{\textbullet}\quad}\hskip\RESP@bulletboxwidth
261 \textcopyright~%
262 \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
263 {\ifRESP@forthcoming\else\normalfont\fontfamily{\rpdefault}\selectfont\fi Res~Philosophica}%

\author The base class puts into \addresses the strange line \author{}. We correct this:
264 \renewcommand{\author}[2][]{%
265   \ifx\@empty\addresses
266     \gdef\addresses{\author{#2}}%

```

```

267   \else
268     \g@addto@macro\addresses{\author{\#2}}%
269   \fi
270 \ifx\empty\authors
271   \gdef\authors{\#2}%
272 \else
273   \g@addto@macro\authors{\and\#2}%
274 \fi
275 \ifnotempty{\#1}{%
276   \ifx\empty\shortauthors
277     \gdef\shortauthors{\#1}%
278   \else
279     \g@addto@macro\shortauthors{\and\#1}%
280   \fi
281 }%
282 }
283 \edef\author{\@nx\@dblarg
284   \exp\@nx\csname\string\author\endcsname}

```

\titlenote This command adds an entry to the list of titlenotes

```

285 \def\@titlenotes{}%
286 \def\titlenote#1{%
287   \ifx\empty\@titlenotes\gdef\@titlenotes{\footnote{\#1}}%
288   \else\g@addto@macro\@titlenotes{\footnote{\#1}}\fi}

```

3.6 Typesetting Top Matter

\@settitle We do not uppercase title. Also, we use this occasion to set PDF information:

```

289 \def\@settitle{\begin{center}%
290   \baselineskip20\p@\relax
291   \LARGE\scshape
292   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
293   \title\@titlenotes
294   \hypersetup[pdftitle=\@title]%
295   \end{center}%
296 }

```

\@setauthors Now we typeset authors according to our specs. Again, we use this occasion to set some PDF information:

```

297 \def\@setauthors{%
298   \ifx\authors\empty\relax\else
299     \begingroup
300     \def\thanks{\protect\thanks@warning}%
301     \trivlist
302     \centering\footnotesize \topsep30\p@\relax
303     \advance\topsep by -\baselineskip
304     \item\relax
305     \def\@@and{{\and}}
306     \author@andify\authors

```

```

307   \hypersetup{pdfauthor=\authors}%
308   \def\\{\protect\linebreak}%
309   \large\normalfont\authors%
310   \endtrivlist
311   \endgroup
312   \fi}

```

\maketitle We redefine \maketitle—mostly to prevent uppercasing of shorttitle and to write down the journal information:

```

313 \def\maketitle{\par
314   \atopnum{z@} % this prevents figures from falling at the top of page 1
315   \setcopyright
316   \thispagestyle{firstpage} % this sets first page specifications
317   \ifx\empty\shortauthors \let\shortauthors\shorttitle
318   \else \andify\shortauthors
319   \fi
320   \maketitle@hook
321   \RESP@write@paper@info
322   \begingroup
323   \maketitle
324   \toks@\exp{\shortauthors}\temptokena\exp{\shorttitle}%
325   \toks4{\def\\{\ignorespaces}}% defend against questionable usage
326   \edef\tempa{%
327     \nx\markboth{\the\toks4}
328     \nx\MakeUppercase{\the\toks@}{\the\temptokena}%
329   \tempa
330   \endgroup
331   \c@footnote{z@}
332   \cleartopmattertags
333 }

```

\@maketitle We delete top space introduced by amsart:

```

334 \def\@maketitle{%
335   \normalfont\normalsize
336   \adminfootnotes
337   \mkboth{\nx\shortauthors}{\nx\shorttitle}%
338   \setttitle
339   \ifx\empty\authors \else \setauthors \fi
340   \ifx\empty\dedication
341   \else
342     \baselineskip18\p@
343     \vtop{\centering{\footnotesize\itshape\dedication\@@par}%
344       \global\dimen@i\prevdepth\prevdepth\dimen@i
345     \fi
346   \setabstract
347   \normalsize
348   \iftitlepage
349     \newpage
350   \else
351     \dimen@34\p@ \advance\dimen@-\baselineskip

```

```

352     \vskip\dimen@relax
353   \fi
354 } % end \maketitle

\@mainrpi The stream for the rpi file:
355 \newwrite\@mainrpi

\RESP@write@paper@info This writes the information about the paper into the file jobname.rpi. Note that hyperref makes our life a little bit more complex
356 \def\RESP@write@paper@info{%
357   \bgroup
358   \if@filesw
359     \openout\@mainrpi\jobname.rpi%
360     \write\@mainrpi{\relax}%
361     \ifx\r@LastPage@\undefined
362       \edef\@tempa{\start@page}%
363     \else
364       \def\@tempb##1##2##3##4##5{##2}%
365       \edef\@tempa{\expandafter\@tempb\r@LastPage}%
366     \fi
367     \def\and{\string\and\space}%
368     \protected@write\@mainrpi{}{%
369       \string\articleentry{\authors}{\@title}{\start@page}{\@tempa}}%
}

The next lines are for crossref software
370 \protected@write\@mainrpi{}{%
371   {\@percentchar authors=\authors}%
372 \protected@write\@mainrpi{}{%
373   {\@percentchar title=\@title}%
374 \protected@write\@mainrpi{}{%
375   {\@percentchar year=\currentyear}%
376 \protected@write\@mainrpi{}{%
377   {\@percentchar volume=\currentvolume}%
378 \protected@write\@mainrpi{}{%
379   {\@percentchar issue=\currentissue}%
380 \protected@write\@mainrpi{}{%
381   {\@percentchar paper=\currentpaper}%
382 \protected@write\@mainrpi{}{%
383   {\@percentchar startpage=\start@page}%
384 \protected@write\@mainrpi{}{%
385   {\@percentchar endpage=\@tempa}%
386 \protected@write\@mainrpi{}{%
387   {\@percentchar doi=\doinumber}%
388   \closeout\@mainrpi
389   \fi
390 \egroup}
}

\@adminfootnotes We just define this to noop:
391 \def\@adminfootnotes{}
```

\@cleartopmattertags We typeset thankses at the end of the paper so we do not clear them:

```
392 \def\@cleartopmattertags{%
393   \def\do##1{\let##1\relax}%
394   \do\maketitle \do\@maketitle \do\title \do\@xttitle \do\@title
395   \do\author \do\@xauthor \do\address \do\@xaddress
396   \do\contrib \do\@contribs \do\xcontribs \do\@toccontribs
397   \do\email \do\@xemail \do\curraddr \do\@xcurraddr
398   \do\commby \do\@commby
399   \do\dedicatory \do\@dedicatory \do\thanks
400   \do\keywords \do\@keywords \do\subjclass \do\@subjclass
```

\sf@size It seems there is a bug in `mdugm` when calculating `\sf@size`. Here we work around it:

```
401 \def\sf@size{7}%
402 }
```

3.7 Typesetting End Matter

End matter is typeset at the end of the paper.

\if@enddoc Check whether we are in the end matter

```
403 \newif\if@enddoc
404 \ifenddocfalse
```

\enddoc@text We put thankses into end matter. Also, we redefine bibliography back to the original definition in case someone writes `\AddtoEndMatter{\bibliography{}}`

```
405 \def\enddoc@text{%
406   \ifenddoctrue\def\bibliography{\RESP@bibliography}%
407   \ifx\empty\thankses\else
408     \bgroup
409     \let\@makefnmark\relax
410     \let\@thefnmark\relax
```

Check, whether we are at the same page as the last footnote; if yes, add medskip.

```
411   \ifx\lastfootnote@page\undefined\else
412     \tempcnta=\lastfootnote@page\relax
413     \ifnum\c@page=\tempcnta\relax
414       \insert\footins{\medskip}%
415     \fi
416   \fi
417   \footnotetext{%
418     \def\par{\let\par\@par}\textbf{Acknowledgements}\quad\@setthanks}%
419   \egroup
420 \fi
421 \ifx\empty@translators\else\@settranslators\fi
422 \ifx\empty@addresses\else\@setaddresses\fi}
```

\ifRESP@firstingroup	A group of authors is separated by a skip from another group. This macro checks whether this is the first one
423 \newif\ifRESP@firstingroup	
\emailaddrname	The name for e-mail address:
424 \def\emailaddrname{E-mail}	
\@setaddresses	Unlike <code>aomart</code> , we want to preserve author's name in the address block. Also, we want to keep linebreaks and to have clickable e-mail and URL.
	We want to skip between the author groups (several authors with the same affiliation), so we check whether the previous line contains another author:
425 \def\@setaddresses{\par	
426 \nobreak \begingroup\flushright\clubpenalty\@MM\interlinepenalty\@MM	
427 \widowpenalty\@MM	
428 \RESP@firstingrouptrue	
429 \Small	
430 \def\author##1{\nobreak\ifRESP@firstingroup\par	
431 \addvspace\bigskipamount\penalty-1000\fi	
432 \RESP@firstingroupfalse##1\par\nobreak}%	
433 \parindent\z@	
434 \def\address##1##2{\RESP@firstingrouptrue\begingroup	
435 \par\nobreak	
436 \@ifnotempty{##1}{(\ignorespaces##1\unskip) }%	
437 {\ignorespaces##2}\par\endgroup}%	
438 \def\curraddr##1##2{\RESP@firstingrouptrue\begingroup	
439 \ifnotempty{##2}{\nobreak\indent\curraddrname	
440 \ignorespaces##1\unskip}\hskip0.2em:\space	
441 ##2\par}\endgroup}%	
442 \def\email##1##2{\RESP@firstingrouptrue\begingroup	
443 \ifnotempty{##2}{\nobreak\indent\emailaddrname	
444 \ignorespaces##1\unskip}\hskip0.2em:\space	
445 \href{mailto:##2}{\nolinkurl{##2}}\par}\endgroup}%	
446 \def\urladdr##1##2{\RESP@firstingrouptrue\begingroup	
447 \ifnotempty{##2}{\nobreak\indent	
448 \ignorespaces##1\unskip}%	
449 \url{##2}\par}\endgroup}%	
450 \addresses	
451 \endgroup	
452 }	
	At the end we eject the last page
453 \AtEndDocument{\cleardoublepage}	

3.8 Sectioning

\@secCntformat	We do not want our numbers to be upright and medium series, as <code>amsart</code> wants:
454 \def\@secCntformat#1{%	
455 \csname the#1\endcsname\enspace	
456 }	

```

\section We want our sections to be large and bold:
457 \renewcommand\section{\@startsection {section}{1}{\z@}%
458                                     {-3.5ex \oplus -1ex \ominus -.2ex}%
459                                     {2.3ex \oplus .2ex}%
460                                     {\normalsize\large\bfseries}%

\subsection Subsections are bold
461 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
462                                     {-3.25ex \oplus -1ex \ominus -.2ex}%
463                                     {1.5ex \oplus .2ex}%
464                                     {\normalsize\bfseries}%

\subsubsection Subsubsections are normalsize and italic
465 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
466                                     {-3.25ex \oplus -1ex \ominus -.2ex}%
467                                     {1.5ex \oplus .2ex}%
468                                     {\normalsize\itshape}%

\paragraph Paragraphs:
469 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
470                                     {3.25ex \oplus 1ex \ominus .2ex}%
471                                     {-1em}%
472                                     {\normalsize\bfseries}%

\ subparagraph Paragraphs:
473 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
474                                     {3.25ex \oplus 1ex \ominus .2ex}%
475                                     {-1em}%
476                                     {\normalsize\bfseries}}

```

3.9 Additional Commands

```

\@mparswitch We always put marginpars on the right since the line box is on the left
477 \@mparswitchfalse

\EditorialComment This macro is noop in normal mode, but is a tiny marginpar in the manuscript
mode
478 \def\EditorialComment#1{\ifRESP@manuscript\bgroup
479   \marginparwidth=200pt\marginpar{\color{red}%
480     \raggedright#1}\egroup\fi}

\doi Typesetting doi...
481 \def\doi#1{\url{http://dx.doi.org/#1}}

\@makefntext Unlike amsart, we do not indent footnotes:
482 \def\@makefntext{\noindent\@makefnmark
483   \if@enddoc\else
484     \immediate\write\@mainaux\%

```

```

485      {\string\xdef\string\lastfootnote@page{\the\c@page}}%
486  \fi}
487 \long\def\@footnotetext#1{%
488   \insert\footins{%
489     \normalsize\footnotesize
490     \interlinepenalty\interfootnotelinepenalty
491     \splittopskip\footnotesepr \splitmaxdepth \dp\strutbox
492     \floatingpenalty\@MM \hsize\columnwidth
493     \parboxrestore \parindent\normalparindent \sloppy
494     \protected@edef\@currentlabel{%
495       \csname p@footnote\endcsname\@thefnmark}%
496     \makefntext{%
497       \rule\z@\footnotesepr\ignorespaces#1\unskip\strut\par}}}

```

3.10 The End

Philosophers love footnotes, since `\raggedbottom`

```

498 \raggedbottom\normalsize\normalfont
499 </class>

```

References

- [1] Boris Veytsman. *Support files for the Linotype Sabon Fonts*, August 2012. <http://mirrors.ctan.org/fonts/lsabon/>.
- [2] Boris Veytsman. *L^AT_EX Support for Monotype Imprint Shadow Font*, August 2012. <http://mirrors.ctan.org/fonts/imprintshadow/>.
- [3] Patrick W. Daly. *Natural Sciences Citations and References (Author-Year and Numerical Schemes)*, February 2009. <http://mirrors.ctan.org/macros/latex/contrib/natbib>.
- [4] American Mathematical Society. *Instructions for Preparation of Papers and Monographs, AMSL^AT_EX*, August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/instr-1.pdf>.
- [5] Paweł Jackowski. T_EX beauties and oddities. *TUGboat*, 29:207–215, 2008. <http://www.tug.org/TUGboat/tb29-1/tb91pearls.pdf>.

Change History

v1.1	\@maketitle: Redefined macro	17	\publicationyear: The default is now empty	13
	\@mparswitch: Changed default	21	\RESP@printlinecount: Added macro	11
	\@setauthors: Changed font	16	\titlenote: Added command	16
	General: Added DOI number	1	\volumenumber: The default is now empty	13
	Added MT Shadow Imprint code	1	v1.14	
	\doi: Added macro	21	\sf@size: Bug corrected	19
	\EditorialComment: Added macro	21	v1.15	
	\ifRESP@mtshadow: Added macro	8	General: Added new bibliography command	1
	\ifRESP@rpfontauto: Added macro	8	v1.2	
	\rpfont: Added option	8	\@adminfootnotes: Redefined	18
	\RESP@write@paper@info: Added protection for \\	18	\@cleartopmattertags: Redefined	19
	\rpdefault: Added macro	10	\@setaddresses: Changed font	20
	\section: Moved to LaTeX defaults	21	\@setauthors: Changed font	16
	\subsection: Moved to LaTeX defaults	21	General: Changed font for bibliography	10
	\subsubsection: Moved to LaTeX defaults	21	Changed skip for bibliography	10
v1.10	\@settitle: Added titlenotes	16	\copyrightnote: Used \rpdefault for RP font	15
	General: Bibliography changes	1	\enddoc@text: Redefined	19
v1.11	General: Bibliography changes	1	\listisep: Redefined	11
	\papernumber: Added macro	14	\RESP@write@paper@info: Used \protected@write	18
	\RESP@write@paper@info: Added writing info for crossref	18	\section: Changed font	21
v1.12	General: Bibliography changes	1	\subsection: Changed font	21
	New command: titlenote	1	\subsubsection: Changed font	21
	New options: preprint and forthcoming	1	\@setaddresses: Added penalties	20
	\copyrightnote: Changed font family for forthcoming mode	15	\@setauthors: Deleted ifpdf	16
	\ifRESP@forthcoming: Added option	9	\@settitle: Deleted ifpdf	16
	\ifRESP@preprint: Added option	9	General: Added penalties	10
	\issuenumber: The default is now empty	13	Ifpdf is no longer needed with modern engines	10
	\publicationmonth: The default is now empty	13	\copyrightyear: In the forthcoming mode the copyright year is the present year	15
	\@makefntext: Redefined	21	\pdfpaperheight: Deleted ifpdf	11
	General: Added footmisc package with ‘bottom’ option	10	\RESP@linecount: Changed check for linecount	11
	Added screen option	1	v1.4	

Changed bibsection font	10	\enddoc@text: Added flag	19
Changed color of ‘Author’s proof’ mark	12	\if@enddoc: Added macro	19
\EditorialComment: Changed color	21	\RESP@linecount: Changed color	11
Changed font	21	v1.6	
\ifRESP@screen: Added option	9	General: Changed bib style	1
\paragraph: Moved to LaTeX default	21	v1.7	
\pdfpaperheight: Changed paper in the manuscript mode	11	General: Added new bibliography fields	1
\RESP@linecount: Changed color	11	Changed formatting of doi	12
\subparagraph: Moved to LaTeX default	21	\doi: Changed formatting	21
v1.5		\footskip: Decreased to fit doi number	11
\maketitle: Added writing the current footnote page to the aux file	21	v1.8	
General: Changed color for headers and footers	12	General: Added blank last page if the last page is odd	1
Color change for links	1	\enddoc@text: Changed bibliography	19
Hyperfootnotes are incompatible with hyperref	10	\sf@size: Added definition	19
\EditorialComment: Changed color	21	v1.9	
		\@setaddresses: Added penalties	20
		\copyrightnote: Made bullet disappear at break	15
		\RESP@bulletboxwidth: Added macro	15

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@and	305
\@par	343
\@MM	426, 427, 492
\@adminfootnotes	...
	336, 391
\@afterheading	97
\@cleartopmattertags	...
	332, 392
\@commby	398
\@copyrightnote	...
	159, 178, 191, 257
\@copyrightyear	...
	251, 259, 262
\@currentlabel	494
\@dblarg	283
\@dedicator	...
	340, 343, 399
\@doinumber	...
	156, 157, 175, 176, 188, 189, 211, 387
\@empty	...
	156, 167, 169, 170, 171, 175, 181, 182, 183, 188, 219, 259, 262, 265, 270, 276, 287, 298, 317, 339, 340, 407, 421, 422
\@enddocfalse	...
	404
\@enddocttrue	...
	406
\@fnsymbol	...
	292
\@footnotetext	417, 487
\@ifnotempty	...
	275, 436, 439, 440, 443, 444, 447, 448
\@keywords	...
	400
\@mainaux	...
	484
\@mainrpi	...
	355, 359, 360, 368, 370, 372, 374, 376, 378, 380, 382, 384, 386, 388
\@makefnmark	...
	409, 482
\@makefntext	...
	482
\@maketitle	323, <u>334</u> , 394
\@maketitle@hook	...
	320
\@minus	...
	458, 462, 466, 470, 474
\@mkboth	...
	337
\@mparswitch	...
	<u>477</u>
\@mparswitchfalse	...
	477
\@ne	...
	122, 124
\@nx	...
	283, 284, 327, 328, 337
\@par	...
	418
\@parboxrestore	...
	493
\@percentchar	...
	371, 373, 375, 377, 379, 381, 383, 385, 387
\@plus	...
	243, 458, 459, 462, 463, 466, 467, 470, 474
\@secCntformat	...
	<u>454</u>
\@secpenalty	...
	96
\@setabstract	...
	249, 346
\@setabstracta	...
	249
\@setaddresses	...
	422, <u>425</u>
\@setauthors	...
	<u>297</u> , 339
\@setcopyright	...
	315
\@setthanks	...
	418
\@setttitle	...
	<u>289</u> , 338
\@settranslators	...
	421
\@startsection	...
	457, 461, 465, 469, 473
\@subjclass	...
	400
\@tempa	...
	218, 219, 326, 329,
\@tempb	...
	362, 365, 369, 385
\@tempcnta	...
	122, 123, 124, 223, 224,
\@temptokena	...
	225, 226, 412, 413
\@thefnmark	...
	324, 328, 410, 495

A

\@abstract	...
abstract	(environment) ...
	4
\@abstractbox	...
	238
\@abstractname	...
	246
\@addpenalty	...
	96
\@address	...
	3, 395, 434
\@addresses	...
	265, 266, 268, 422, 450
\@AddtoEndMatter	6, <u>90</u> , 95
\@addvspace	...
	96, 431
\@advance	...
	124, 224, 225, 303, 351
\@and	...
	273, 279, 367
\@andify	...
	318
\@articleentry	...
	<u>223</u> , 369
\@AtBeginDocument	..
	101
\@AtEndDocument	..
	93, 453
\@author	..
	3, <u>264</u> , 395, 430
\@author@andify	...
	306
\@authors	...
	270, 271, 273, 298, 306, 307, 309, 339, 369, 371

B	D	F
\baselineskip	\CurrentOption	\else 73, 74, 75, 76, 88,
. 290, 303, 342, 351	50, 51, 52, 53, 66	100, 156, 163,
\begin	\currentpaper	167, 169, 171,
132, 135, 148, 207, 210, 289 201, 212, 381	172, 175, 181,
\begingroup	\currentvolume 154,	182, 183, 184,
. 299, 322, 426, 434, 438, 442, 446	167, 168, 181, 186, 193, 212, 377	188, 220, 225,
\bfseries 155, 171, 173,	253, 259, 262,
. 460, 464, 472, 476	183, 187, 197,	263, 267, 272,
\bgroup 238, 357, 408, 478	212, 259, 262, 375	278, 288, 298,
\bibfont	\currentyear	318, 339, 341,
98 \bibliography 94, 95, 406 155, 171, 173,	350, 363, 407,
\bibliographystyle . 93	\DeclareOptionX 49,	411, 421, 422, 483
\bibsection	50, 51, 52, 53,	\email 3, 397, 442
\bigskipamount	56, 59, 62, 65, 66	\emailaddrname 424, 443
. 96, 179, 431	\dedicatory 399	\emph 179
\bodyfont 10	\def 46, 88, 89,	\end 134,
bodyfont (option) 3	90, 95, 96, 98,	137, 150, 204, 295
	193, 195, 197,	\end@page . 187, 219, 220
C	199, 201, 211,	\endcsname 284, 455, 495
\c@footnote 292, 331	213, 214, 216,	\enddoc@text 90, 405
\c@page 215, 413, 485	218, 219, 220,	\endgroup
\centering 302, 343	221, 223, 227,	. 311, 330, 437,
\cfoot 153, 165, 185	251, 257, 285,	441, 445, 449, 451
\changes 208	286, 289, 297,	\endlist 248
\chead 160, 179	300, 305, 308,	\endpage 5, 218, 221
\ClassInfo 228	313, 325, 334,	\endtrivlist 310
\ClassWarning	356, 364, 367,	\enspace 455
. 47, 231, 235	391, 392, 393,	environments:
\cleaders 260	401, 405, 406,	abstract 4
\cleardoublepage 453	418, 424, 425,	\evensidemargin 106
\closeout 388	430, 434, 438,	\expandafter 365
\clubpenalty 426	442, 446, 454,	
\color 123, 140, 143, 160, 479	478, 481, 482, 487	F
\columnwidth 492	\define@boolkey 42	\fancyfoot 128, 140, 143
\commby 398	\define@choicekey 10, 26	\fancyhead 127,
\contrib 396	\dimen@ 351, 352	129, 130, 132, 135
\contribs 396	\dimen@i 344	\fancyhf 146
\copyrightnote 4, 257	\do 393, 394, 395, 396,	\fancypagestyle 145
\copyrightyear 4, 251	397, 398, 399, 400	\fi 23, 39, 77, 79,
\csname 284, 455, 495	\doi 157, 176, 189, 481	84, 86, 89, 99,
\curraddr 3, 397, 438 5, 207, 211, 212	103, 117, 118,
\curraddrname 439	\doinumber	125, 138, 141,
\currentissue	\dp 491	144, 151, 157,
. 154, 169, 182, 186, 195, 212, 379	\edef 283, 326, 362, 365	168, 169, 171,
\currentmonth 155, 170, 173, 187, 199	\EditorialComment 5, 478	174, 176, 182,
	\egroup 248, 390, 419, 480	183, 189, 192,
E		217, 220, 225,
		237, 249, 254,
		259, 262, 263,
		269, 274, 280,

288, 312, 319,	\ifRESP@forthcoming	63, 76, 164, 252, 263	\lastfootnote@page 411, 412, 485
339, 345, 353,			
366, 389, 415,	\ifRESP@lsabon 6, 80		\leftmargin 241
416, 420, 421,	\ifRESP@manuscript 54, 73,		\let 94, 244, 317, 393, 409, 410, 418
422, 431, 480, 486			
\floatingpenalty 492	100, 117, 139, 478		\lhead 148
\flushright 426	\ifRESP@mtshadow 8, 87		\linebreak 308
\fontfamily 153, 185, 263	\ifRESP@natbib 91		\list 240
\footins 414, 488	\ifRESP@preprint 60, 75, 118, 142, 152		\listsep 109
\footnote 287, 288			\listparindent 242
\footnotesep 491, 497	\ifRESP@printlinecount 115, 119, 131, 147		\LoadClass 68
\footnotesize 129, 130, 134,	\ifRESP@rpfontauto 4, 85		\long 46, 487
153, 165, 179,	\ifRESP@screen 57, 74		\loop 123
185, 302, 343, 489	\ifx 156, 167, 169,		
\footrulewidth 112	170, 171, 175,	M	
\footskip 114	181, 182, 183,		\maketitle 4, 234, 236, 313, 394
forthcoming (option) 3	188, 219, 234,		\MakeUppercase 328
\fullwidthdisplay 244	249, 259, 262,		manuscript (option) 3
	265, 270, 276,		\marginpar 479
G	287, 298, 317,		\marginparwidth 479
\g@addto@macro 90,	339, 340, 361,		\markboth 327
268, 273, 279, 288	407, 411, 421, 422		\medskip 414
\gdef 211,	\ignorespaces 325, 436, 437,		\medskipamount 97, 109
266, 271, 277, 287	440, 444, 448, 497	N	
\global 238, 344	\immediate 484		\natbib 42
	\indent 439, 443, 447		natbib (option) 3
H	\input 230		\newif 2, 4, 6, 8, 54, 57, 60, 63, 115, 403, 423
\hbox 260	\insert 414, 488		\newlength 255
\headheight 111	\interfootnotelinepenalty 490		\newpage 349
\headrulewidth 112	\interlinepenalty 426, 490		\newsavebox 120
\headsep 110	\issuenumber 5, 195		\newwrite 355
\href 445	\item 246, 304		\nobreak 97, 426, 430, 432, 435, 439, 443, 447
\hsize 492	\itemindent 242		\noindent 97, 482
\hskip 260, 440, 444	\itshape 129, 134, 154,		\nolinkurl 445
\hypersetup 73, 74,	165, 186, 343, 468		\normalfont 246, 263, 309, 335, 460, 464, 468, 472, 476, 489, 498
75, 76, 77, 294, 307		K	\normalparindent 242, 493
	\jobname 359		\normalsize 246, 335, 347, 464, 468, 472, 476, 476, 498
I		L	\large 309, 460
\if@enddoc 403, 483	\labelwidth 240		\nr 10, 12, 26, 28
\if@files w 358	\LARGE 291		
\if@titlepage 348	\large 309, 460		
\ifcase 12, 28			
\IfFileExists 79, 86, 227			
\ifnum 124, 215, 413			
\ifodd 225			
\ifRESP@firstingroup 423, 430			
\ifRESP@fontauto 2, 78			

O	Q	R
\oddsidemargin 106	\quadqquad 129, 130, 134	\RESP@mtshadowtrue .. .
\openout 359	\quadquad 256, 260, 418 32, 35, 86
options:		\RESP@natbibtrue .. 45
bodyfont 3		\RESP@preprintfalse 61
forthcoming 3	\r@LastPage 361, 365	\RESP@preprinttrue .. 62
manuscript 3	\raggedbottom 498	\RESP@printlinecount .. . 115
natbib 3	\raggedright 480	\RESP@printlinecountfalse
preprint 3	\relax 12, 28, 122, 223, 116
rpfont 3	224, 225, 234,	\RESP@printlinecounttrue
screen 3	244, 249, 290, 117, 118
\or 14, 17, 20, 30, 33, 36	298, 302, 304,	\RESP@rpfontautofalse
	352, 360, 393, 31, 34, 37
	409, 410, 412, 413	\RESP@rpfontautotrue
	 5, 29, 41
	\renewcommand .. .	\RESP@screenfalse .. 58
\p@ 243, 290, 302, 342, 351 83, 112, 113,	\RESP@screentrue .. 59
\PackageWarning ...	264, 292, 457,	\RESP@size@warning ..
..... 24, 40, 43	461, 465, 469, 473 46,
\pagenumbering 213, 215	\renewenvironment .. 233	49, 50, 51, 52, 53
\pageref 219	\repeat 124	\RESP@write@paper@info
\pagespan 221	\RequirePackage 1, 69, 321, <u>356</u>
\pagestyle 126	70, 71, 81, 82, 92	\rightmargin 241
\papernumber 5, <u>201</u>	\RESP@bibliography ..	\rmdefault 89
\par 96, 97, 313, 94, 95, 406	\romannumeral 216
418, 425, 430,	\RESP@bulletboxwidth	\rpdefault .. .
432, 435, 437, 255, 260 87, 153, 185, 263
441, 445, 449, 497	\RESP@firstingroupfalse	\rpfont 26
\paragraph 469 432	rpfont (option) 3
\parbox 121	\RESP@firstingrouptrue	\rule 497
\parindent 433, 473, 493 428,	
\parsep 243	434, 438, 442, 446	
\PassOptionsToClass 66	\RESP@fontautofalse	S
\pdfpageheight 102 15, 18, 21	\savebox 121
\pdfpagewidth 101	\RESP@fontautotrue ..	\scdefault 83
\pdfpaperheight ... <u>100</u> 3, 13, 25	screen (option) 3
\pdfpaperwidth <u>100</u>	\RESP@forthcomingfalse	\scriptsize .. .
\penalty 431 64 123, 140, 143, 160
preprint (option) 3	\RESP@forthcomingtrue	\scshape 291
\prevdepth 344 65	\section 457
\prevpaper 5, <u>227</u>	\RESP@linecount ...	\selectfont 153, 185, 263
\ProcessOptionsX .. 67 <u>119</u> , 133, 136, 149	\setbox 238
\protect .. 236, 300, 308	\RESP@lsabonfalse ..	\setcounter ... 213, 215
\protected@edef ... 494 7, 22, 79	\setlength .. .
\protected@write ..	\RESP@lsabontrue 101, 102, 104,
. 368, 370, 372, 16, 19, 79	105, 106, 107,
374, 376, 378,	\RESP@manuscriptfalse	108, 110, 111, 114
380, 382, 384, 386 55	\setwidt .. . 256
\publicationmonth 5, <u>199</u>	\RESP@manuscripttrue 56	\sf@size <u>401</u>
\publicationyear 5, <u>197</u>	\RESP@mtshadowfalse	\shortauthors .. .
\put 133, 136, 149 9, 38, 86	4, 129, 134, 260,

276, 277, 279,	\textcopyright	258, 261	\usebox	... 133, 136, 149
317, 318, 324, 337	\textheight	... 104		
\shorttitle	\textit	130	V	
. 130, 317, 324, 337	\textwidth	... 104	\val	... 10, 26
\sloppy	\thanks	... 4, 300, 399	\vglue	... 239
\Small	\thanks@warning	... 300	\volumenumber	... 5, 193
\space	\thankses	... 407	\vskip	... 97, 352
236, 246, 367, 440, 444	\the	... 123, 225, 226,	\vspace	... 179
\splitmaxdepth	253, 327, 328, 485		\vtop	... 238, 343
\splittopskip	\the footnote	... 292		
\start@page	\thepage	... 129, 130, 134	W	
187, 214, 216, 362, 369, 383	\thispagestyle	... 316	\widowpenalty	... 427
\startpage	\title	... 3, 394	\write	... 360, 484
... 5, 213, 221, 226	\titlenote	... 4, 285		
\string	\toccontribs	... 396	X	
284, 367, 369, 485	\strut	... 325, 327	\xcontribs	... 396
\strut	\toks	... 325, 327	\xdef	... 485
497	\toks@	... 324, 328		
\strutbox	\subjclass	\topmargin	Y	
491	400	... 108		
\subparagraph	\trivlist	... 301	\year	... 253
473				
\subsection	\unskip	... 436,	Z	
461		440, 444, 448, 497	\z@	... 215, 240,
\subsubsection				242, 243, 314,
465	\url	... 162, 449, 481		331, 433, 457,
6	\urladdr	... 3, 446		461, 465, 469, 497
\suppresscomma	\urlstyle	... 72		
T				
\textbf				
246, 418				
\textbullet				
... 256, 260				