

Typesetting Articles for *Res Philosophica*^{*†}

Boris Veytsman[‡]

2015/01/14, v1.24

Abstract

This package provides a class for typesetting articles for the journal *Res Philosophica*, <http://www.resphilosophica.org>.

Contents

1	Introduction	2
2	User Interface	2
2.1	Commercial Fonts	2
2.2	Invocation and Options	2
2.3	Topmatter	3
2.3.1	Commands for Authors	3
2.3.2	Commands for Editors	4
3	Special Notes	6
3.1	Bibliography	6
4	Implementation	9
4.1	Options	9
4.2	Loading Classes and Packages	11
4.3	Page Dimensions and Paragraphing	12
4.4	Headers	12
4.5	Top Matter Macros	14
4.6	Typesetting Top Matter	18
4.7	Notes	21
4.8	Typesetting End Matter	21
4.9	Sectioning	22
4.10	Additional Commands	23
4.11	The End	24

^{*}©2012, Boris Veytsman

[†]This work was commissioned by the Saint Lois University

[‡]borisv@lk.net, boris@varphi.com

1 Introduction

According to the statement at <http://www.resphilosophica.org/>, *Res Philosophica* is an international, quarterly journal of philosophy that publishes research in all areas of philosophy, historical and topical. Founded as *The Modern Schoolman* by Jesuit Scholastics in 1925, the journal is edited by members of the Philosophy Department at Saint Louis University and supported generously by the College of Arts and Sciences.

This package is intended for the authors and editors of the journal to typeset the articles in L^AT_EX. Note that the journal is typeset in *Linotype Sabon*. The users may buy the fonts and install their free L^AT_EX support [1], or use the options `bodyfont=cm` and `rpfont=cm` to typeset the articles using Computer Modern. Of course, the line and page breaks in the latter case are different from those in the final version typeset with commercial fonts.

2 User Interface

2.1 Commercial Fonts

The package can be used with free Computer Modern fonts or with commercial fonts to mimick the journal typesetting. The installation of additional fonts is therefore fully optional.

Res Philosophica uses Linotype Sabon for the body text and URW Garamond for mathematics. Sabon is a commercial font. URW Garamond is free, but due to license restrictions it is usually not included with T_EXLive, MikT_EX and other major distributives. If you bought Linotype Sabon, you need to install the package `lsabon` [1]. To use URW Garamond, you need to download the `pfb` files from a CTAN mirror (<http://ctan.org/tex-archive/fonts/urw/garamond>), install them in the directory `fonts/type1/urw/garamond` under `$TEXMFLOCAL` and run `texhash`.

2.2 Invocation and Options

To use the class put in the preamble of your document

```
\documentclass[<options>]{resphilosophica}
```

The class `resphilosophica` internally loads `amsart`, and therefore all class options for `amsart` are technically valid. However, most of them are not especially meaningful for `resphilosophica`. There are several options specific for this class. They are described below. Note that the class uses key-value interface for some options, for example

```
\documentclass[bodyfont=sabon]{resphilosophica}
```

option
bodyfont

The option `bodyfont` can have three values: `sabon` for Sabon/Garamond fonts,

`cm` for Computer Modern and `auto` (default). The later option switches to the use of Sabon if the font metrics are present in your system, and to the use of Computer Modern otherwise.

option `manuscript` The option `manuscript` is intended to facilitate the communications between the editor and the author. It enables two things:

1. The numbering of lines in the manuscript is switched off in the normal mode, but is on in the manuscript mode.
2. The command `\EditorialComment` is no-op in normal mode, but produces marginal commentaries in the manuscript

option `preprint` The option `preprint` is for the final version of the manuscript. In this mode there are no editorial comments, but the numbering of lines is preserved

option `screen` The option `screen` is intended for the screen reading. When this option is selected, the links become highlighted.

option `forthcoming` The option `forthcoming` is like `screen`, but it is used when there is no information about the volume. The macro `\onlinedate{<date>}` can be used to set the date of online publication.

`\onlinedate` *option* `natbib` The preferred solution for bibliography is `natbib` package [2]. The option `natbib=true` (default) sets the package and the proper options, including bibliography style. The option `natbib=false` switches this behavior off, and the formatting of the bibliography becomes the full responsibility of the author. The package includes the BibTeX bibliography style `resphilosophica.bst`.

2.3 Topmatter

Topmatter is the part of the article with the informations about the authors, their affiliations, the publication data, etc.

There are two kinds of top matter commands: the ones used primarily for authors and the ones used primarily for editors. We describe them separately.

2.3.1 Commands for Authors

`\title` The command `\title`, as in `amsart` class, has two arguments: one optional, and one mandatory:

`\title[<ShortTitle>]{<FullTitle>}`

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

`\author` The interface for specifying the authors and their affiliations is close the the one of `amsart` [3] (and different from the standard L^AT_EX). For each author a separate command `\author` should be used, followed by `\address` and (optionally) `\curraddr`, `\email` and `\urladdr`.

`\urladdr` In some cases the authors list may be too long for the running head, even `\shortauthors` if the abbreviated forms are used for each author. In this case it is possible to

change the running head by a *redefinition* of the command `\shortauthors`. This redefinition must be done after all `\author` commands, but before `\maketitle`:

```
\renewcommand{\shortauthors}{A.~Smith et al}
```

<code>\thanks</code>	Like <code>amsart</code> (and unlike standard \LaTeX), <code>resphilosophica</code> allows <code>\thanks</code> only <i>outside</i> of commands <code>\title</code> and <code>\author</code> . The text of <code>\thanks</code> is typeset at the end of the paper as a footnote marked ‘Acknowledgements’. Note that the right vertical positioning of this footnote might require an additional run of \LaTeX .
<code>\titlenote</code>	The <code>\titlenote{<note>}</code> command creates a special footnote for the title. This command should be issued <i>outside</i> the <code>\title</code> command.
<code>\authornote</code>	The similar <code>\authornote{<note>}</code> command creates a special footnote for the author. This command should be issued <i>outside</i> the <code>\author</code> command.
<code>\copyrightnote</code>	Normally each paper is copyrighted by the authors and by the journal. This is reflected in the footnote on the first page of the article. However, by arrangement with the editors, certain papers may have different copyright. The command <code>\copyrightnote{<copyright statement>}</code> , if issued, changes the footnote to the corresponding text, for example:

```
\copyrightnote{\textcopyright~2012 by the authors. This paper may
be reproduced, in its entirety, for noncommercial purposes.}
```

Note that if you issue this command, you should explicitly include both the copyright sign and the year unless the paper does not have a copyright, for example:

```
\copyrightnote{This paper is in the public domain}
```

<code>\copyrightyear</code>	Normally the copyright statement includes the year of copyright, which is assumed to be the publication year as specified by the <code>\publicationyear</code> command (see below). If this assumption is wrong, you may correct it, for example,
-----------------------------	---

```
\copyrightyear{1998}
```

<code>abstract</code>	The abstract of the paper must be put between <code>\begin{abstract}</code> and <code>\end{abstract}</code> . Unlike the situation in <code>amsart</code> class, abstract may be put <i>after</i> <code>\maketitle</code> .
-----------------------	---

<code>\maketitle</code>	The macro <code>\maketitle</code> typesets the top matter. All top matter information should be specified before this command.
-------------------------	--

2.3.2 Commands for Editors

The commands described in this section should be used by the editors to insert the information about the published paper. They must be put before the `\maketitle` command.

<code>\volumenumber</code>	The macros <code>\volumenumber</code> , <code>\issuenummer</code> , <code>\publicationyear</code> , <code>\publicationmonth</code> , <code>\papernumber</code> , <code>\startpage</code> and <code>\endpage</code>
<code>\issuenummer</code>	
<code>\publicationyear</code>	
<code>\publicationmonth</code>	
<code>\papernumber</code>	
<code>\startpage</code>	
<code>\endpage</code>	

`\papernumber`, `\startpage`, `\endpage` set up the corresponding data for the paper, for example:

```
\volumenumber{88}
\issuenumber{1--2}
\publicationyear{2012}
\publicationmonth{January--February}
\papernumber{2}
\startpage{1}
\endpage{39}
```

Note that if the argument of `\endpage` is empty, L^AT_EX tries to calculate the last page number as best as it can.

Sometimes publication month for double issues is too long to fit on the back cover. For this case `\publicationmonth` has the optional argument, abbreviated month, for example

```
\publicationmonth[Jan--Feb]{January--February}
```

`\doinumber` Normally you do not need to set the DOI of the paper: T_EX will construct the number using the paper data (including paper number in the current issue). However, you *may* override its decision using the command `\doinumber` which sets the DOI explicitly, for example, `\doinumber{\langle 10.11612/resphilosophica.2013.01.01 \rangle}`. You probably should not use this macro.

`\prevpaper` Instead of setting `\startpage`, one can use the the command `\prevpaper{\langle previous paper \rangle}`, with the argument being the location and file name of the previous paper in the journal, for example:

```
\prevpaper{../infinity/concept_of_infinity}
```

Note that the `.tex` suffix should *not* be used. The previous paper must be processed by `latex` prior to the current one. In this case `latex` will read the last page of the previous paper, and start the current one from the proper page number.

`\paperUrl` When a paper is submitted to the Crossref service, which keeps the database of Digital Object Identifiers, its URL is calculated by the script used by editors. The command `\paperURL{\langle url \rangle}` overrides this choice.

`\EditorialComment` The macro `\EditorialComment[\langle level \rangle]{\langle comments \rangle}` typesets the comments on the margins in the `manuscript` mode, for example,

```
Which is a well known fact.\EditorialComment{A citation is
needed}\EditorialComment[1]{Please make the citation more
explicit}.
```

Editorial comments have *levels*. A level can be numeric or symbolic; symbolic levels can contain letters and numbers. The default level is 0, so `\EditorialComment{text}` is equivalent to `\EditorialComment[0]{text}`.

`\ECSelect` The command `\ECSelect{<level,level,...>}` selects the levels of editorial comments to display in the manuscript mode. Note that 0 corresponds to the default level, so the command `\ECSelect{0}` should be used to show these comments.

Sometimes it is useful to tell the author about typesetter's changes in the manuscript. The dialog between the author and typesetter might take several iterations, so the class provides a system for this dialog.

`\TC` The macro `\TC[<level>]{<text>}` makes `{<text>}` highlighted in the manuscript mode if the level `[<level>]` is chosen. For example,

```
This proposition \TC[1]{(first discussed by the author in 2010)} can
be stated as the following.
```

The level can be numerical, or logical, e.g. `\TC[new]{text}`. Actually any combination of letters and numbers that does not contain commas or spaces can be used for level. By default the level is 0, so `\TC{<text>}` is equivalent to `\TC[0]{<text>}`.

`\TCSelect` The decision to highlight certain levels is done by the command `\TCSelect[<color>]{<level,level,level...>}`. The first optional argument is the color used for highlighting; by default **magenta**. Actually any color expression understandable by `xcolor` can be used. The second argument is a comma-separated list of levels that will be highlighted by the selected color. The command `\TCSelect` can be repeated, for example,

```
\TCSelect{0,1,new}
\TCSelect[blue]{second-level}
```

If a level does *not* appear in any `\TCSelect` command, it is not highlighted—that is why we do not need a separate `\TCOff` command.

3 Special Notes

notes Some authors include special notes, for example, bibliography description, that precede list of references, but follow the signature block. The environment **notes** is intended for this purpose. It has one mandatory argument, title, for example

```
\begin{notes}{Bibliography notes}
  The best discussion of the problem can be found in...
\end{notes}
```

3.1 Bibliography

As mentioned above, **resphilosophica** by default uses **natbib** [2]. You should use **natbib** commands like `\citet`, `\citep` etc.

Note that `\bibliographystyle` command should *not* be issued by the author: the package takes care of this. You just need to type

```
\bibliography{DATABASE, DATABASE...}
```

The bibliography style used for the articles is `resphilosophica.bst`. Compared to standard styles it has two additional fields:

doi: DOI number of the publication. Write there only the number: the style will automatically add `http://dx.doi.org` and make the reference clickable.

titlenote: the note that should be put after the title rather than at the end of the entry¹, for example, the information about translators, editors of critical editions, etc:

```
@book{Knuth94:TheTeXbook,
  address =      {Reading, MA},
  author =      {Knuth, Donald Ervin},
  titlenote =    {Illustrations by Duane Bibby},
  publisher =    {Addison-Wesley Publishing Company},
  series =      {Computers \& Typesetting A},
  title =       {The \TeX book},
  year =        {1994},
}
```

`\suppresscomma` Sometimes BibTeX inserts an unwanted comma into an entry, for example, in the following one:

```
@incollection{ande97a,
  Address = {Macon, GA},
  Author = {Anderson, Thomas C.},
  Booktitle = {Concluding Unscientific Postscript to
\enquote{Philosophical Fragments,}},
  Date-Modified = {2013-09-04 21:27:17 +0000},
  Editor = {Robert Perkins},
  Owner = {Andrew},
  Pages = {187--204},
  Publisher = {Mercer University Press},
  Series = {International Kierkegaard Commentary},
  Timestamp = {2013.09.04},
  Title = {Kierkegaard and Approximation Knowledge},
  Volume = {12},
  Year = {1997}}
```

The command `\suppresscomma` suppresses the next comma:

```
Booktitle = {Concluding Unscientific Postscript to
\enquote{Philosophical Fragments,\suppresscomma}},
```

¹This field was proposed by Maureen Shupsky for the *Annals of Mathematics* bibliography style.

The bibliography style has a special entry type, `inloosecollection`. It resembles the standard `incollection` entry, but it refers to a collection of papers written by separate authors that are quotable separately as an independent entity. This entry is typeset slightly differently than the standart `incollection` entry.

`\AddtoEndMatter` If you decide to forgo `natbib`, you can use `natbib=false` option. Then you should remember to put the bibliogrtaphy *after* the end matter (authors' addresses etc) using the command `\AddtoEndMatter`:

```
\AddtoEndMatter{MY BIBLIOGRAPHY COMMANDS}
```

Acknowledgements

This package was commissioned by the journal *Res Philosophica* and funded by Saint Louis University. I am grateful to Jonathan Jacobs for tireless testing of the package.

4 Implementation

4.1 Options

We need `xkeyval` since some of our options may have values:

```
1 \RequirePackage{xkeyval}
```

`\ifRESP@fontauto` First, check whether the user have the body font explicitly configured:

```
2 \newif\ifRESP@fontauto
3 \RESP@fontautottrue
```

`\ifRESP@rpfontauto` Same for *Res Philosophica* font

```
4 \newif\ifRESP@rpfontauto
5 \RESP@rpfontautottrue
```

`\ifRESP@lsabon` Are we using linotype sabon?

```
6 \newif\ifRESP@lsabon
7 \RESP@lsabonfalse
```

`\ifRESP@mtshadow` Are we using MT Imprint Shadow?

```
8 %\newif\ifRESP@mtshadow
9 %\RESP@mtshadowfalse
```

`bodyfont` And the option to check the user input:

```
10 \define@choicekey*+{resphilosophica.cls}{bodyfont}[\val\nr]{auto,
11   sabon, lsabon, cm}[auto]{%
12   \ifcase\nr\relax
13     \RESP@fontautottrue
14   \or
15     \RESP@fontautofalse
16     \RESP@lsabontrue
17   \or
18     \RESP@fontautofalse
19     \RESP@lsabontrue
20   \or
21     \RESP@fontautofalse
22     \RESP@lsabonfalse
23   \fi}{%
24   \PackageWarning{resphilosophica}{The option bodyfont must be auto,
25     sabon or cm. Using auto}\RESP@fontautottrue}
```

`rpfont` And the option to check the user input:

```
26 % \define@choicekey*+{resphilosophica.cls}{rpfont}[\val\nr]{auto,
27 %   imprint, imprintshadow, cm}[auto]{%
28 %   \ifcase\nr\relax
29 %     \RESP@rpfontautottrue
30 %   \or
31 %     \RESP@rpfontautofalse
32 %     \RESP@mtshadowtrue
```

```

33 % \or
34 % \RESP@rpfontautofalse
35 % \RESP@mtshadowtrue
36 % \or
37 % \RESP@rpfontautofalse
38 % \RESP@mtshadowfalse
39 % \fi}{%
40 % \PackageWarning{resphilosophica}{The option rpfont must be auto,
41 % imprintshadow or cm. Using auto}\RESP@rpfontautottrue}

natbib Checking natbib option:
42 \define@boolkey+{resphilosophica.cls}[RESP@]{natbib}[true]{}%
43 \PackageWarning{resphilosophica}{The option natbib must be
44 yes or no. Using yes}}
45 \RESP@natbibtrue

The size-changing options produce a warning:
46 \long\def\RESP@size@warning#1{%
47 \ClassWarning{RESPart}{Size-changing option #1 will not be
48 honored}}%
49 \DeclareOptionX{8pt}{\RESP@size@warning{\CurrentOption}}%
50 \DeclareOptionX{9pt}{\RESP@size@warning{\CurrentOption}}%
51 \DeclareOptionX{10pt}{\RESP@size@warning{\CurrentOption}}%
52 \DeclareOptionX{11pt}{\RESP@size@warning{\CurrentOption}}%
53 \DeclareOptionX{12pt}{\RESP@size@warning{\CurrentOption}}%

\ifRESP@manuscript Manuscript mode:
54 \newif\ifRESP@manuscript
55 \RESP@manuscriptfalse
56 \DeclareOptionX{manuscript}{\RESP@manuscripttrue}

\ifRESP@screen Screen mode:
57 \newif\ifRESP@screen
58 \RESP@screenfalse
59 \DeclareOptionX{screen}{\RESP@screenttrue}

\ifRESP@preprint Whether we are in the preprint mode
60 \newif\ifRESP@preprint
61 \RESP@preprintfalse
62 \DeclareOptionX{preprint}{\RESP@preprinttrue}

\ifRESP@forthcoming Whether we are in the forthcoming mode
63 \newif\ifRESP@forthcoming
64 \RESP@forthcomingfalse
65 \DeclareOptionX{forthcoming}{\RESP@forthcomingtrue}

All other options are passed to amsart:
66 \DeclareOptionX{*}{\PassOptionsToClass{\CurrentOption}{amsart}}
And executing options:
67 \ProcessOptionsX

```

4.2 Loading Classes and Packages

We use `amsart` since it has nice features for front matter:

```
68 \LoadClass[noamsfonts,twoside]{amsart}
```

Some packages

```
69 \RequirePackage{microtype, fancyhdr, xcolor, lastpage, collect}
70 \RequirePackage[bottom,multiple]{footmisc}
71 \RequirePackage[hyperfootnotes=false]{hyperref}
72 \urlstyle{rm}
73 \ifRESP@manuscript\hypersetup{colorlinks,allcolors=blue}\else
74   \ifRESP@screen\hypersetup{colorlinks,allcolors=blue}\else
75     \ifRESP@preprint\hypersetup{colorlinks,allcolors=blue}\else
76       \ifRESP@forthcoming\hypersetup{colorlinks,allcolors=blue}\else
77     \hypersetup{hidelinks}\fi\fi\fi\fi
```

The font to use depends on the options. Note that L^AT_EX cannot reliably determine whether a binary file like `SabonLTRom.pfb` exists in the system, so we check for the `.fd` file instead (sigh):

```
78 \ifRESP@fontauto
79   \IfFileExists{t1lsb.fd}{\RESP@lsabontrue}{\RESP@lsabonfalse}\fi
```

If the user wants, we load Sabon and URW Garamond. Note that `mathdesign` defines `sc` to be `fsc`, so we need to redefine it for Sabon. Also, it defines `b` to `mb`. so we redefine it again.

```
80 \ifRESP@lsabon
81   \RequirePackage[mdugm]{mathdesign}
82   \RequirePackage[rmdefault]{lsabon}
83   \renewcommand\scdefault{sc}
84   \renewcommand{\bfdefault}{b}
85 \fi
```

Checking the existence of miih font metrics:

```
86 %\ifRESP@rpfontauto
87 % \IfFileExists{t1miih.fd}{\RESP@mtshadowtrue}{\RESP@mtshadowfalse}\fi
```

`\rpdefault` This is the font for *Res Philosophica*:

```
88 %\ifRESP@mtshadow
89 % \def\rpdefault{miih}\else
90 % \def\rpdefault{\rmdefault}\fi
```

`\AddtoEndMatter` A syntax sugar to add something after signature:

```
91 \def\AddtoEndMatter#1{\g@addto@macro\enddoc@text{#1}}
```

And loading `natbib`:

```
92 \ifRESP@natbib
93   \RequirePackage[round]{natbib}
94   \AtEndDocument{\bibliographystyle{resphilosophica}}
95   \let\RESP@bibliography=\bibliography
96   \def\bibliography#1{\AddtoEndMatter{\RESP@bibliography{#1}}}
97   \def\bibsection{\par\addpenalty@secpenalty\addvspace{\bigskipamount}}%
```

```

98      \noindent \Small References:\par\nobreak\vskip\medskipamount\@afterheading}
99      \def\bibfont{\Small}
100 \fi

```

4.3 Page Dimensions and Paragraphing

```

\pdfpaperwidth Paper:
\pdfpaperheight 101 \ifRESP@manuscript\else
                  102 \AtBeginDocument{\setlength{\pdfpagewidth}{441bp}%
                  103 \setlength{\pdfpageheight}{648bp}}
                  104 \fi

\textwidth The size of the type block:
\textheight 105 \setlength{\textwidth}{318pt}
              106 \setlength{\textheight}{540pt}

\evensidemargin The margins:
\oddsidemargin 107 \setlength{\evensidemargin}{-9pt}
                108 \setlength{\oddsidemargin}{-18pt}
                109 \ifRESP@screen
                110 \setlength{\evensidemargin}{-13pt}
                111 \setlength{\oddsidemargin}{-13pt}
                112 \fi
                113 \ifRESP@forthcoming
                114 \setlength{\evensidemargin}{-13pt}
                115 \setlength{\oddsidemargin}{-13pt}
                116 \fi

\topmargin Top margin
            117 \setlength{\topmargin}{-48pt}

\listisep This is the space around lists. amsart defines it as \smallskipamount. We slightly
            increase it:
            118 \listisep\medskipamount

```

4.4 Headers

```

\headsep Separation between the header and the body
          119 \setlength{\headsep}{14pt}

\headheight The height of the headers:
            120 \setlength{\headheight}{12pt}

\headrulewidth We do not want decorative rules in the journal:
\footrulewidth 121 \renewcommand{\headrulewidth}{0pt}
                122 \renewcommand{\footrulewidth}{0pt}

```

`\footskip` Separation between the footer and the body

```

123 \setlength{\footskip}{20pt}

\RESP@printlinecount Do we want to print line count?
124 \newif\ifRESP@printlinecount
125 \RESP@printlinecountfalse
126 \ifRESP@manuscript\RESP@printlinecounttrue\fi
127 \ifRESP@preprint\RESP@printlinecounttrue\fi

\RESP@linecount This is the box displayed in the manuscript mode
128 \ifRESP@printlinecount
129   \newsavebox{\RESP@linecount}
130   \savebox{\RESP@linecount}[4em][t]{\parbox[t]{4em}{%
131     \@tempcnta\@ne\relax
132     \loop{\color{red}\scriptsize\the\@tempcnta}\@tempcnta<47\repeat}}
133   \advance\@tempcnta by \@ne\ifnum\@tempcnta<47\repeat}}
134 \fi

    It is easy to set up headers with fancyhdr:
135 \pagestyle{fancy}
136 \fancyhead{}
137 \fancyfoot{}
138 \fancyhead[LE]{\footnotesize\thepage\qquad\itshape\shortauthors}
139 \fancyhead[RO]{\footnotesize\textit{\shorttitle}\qquad\thepage}
140 \ifRESP@printlinecount
141   \fancyhead[LE]{\begin{picture}(0,0)%
142     \put(-26,-22){\usebox{\RESP@linecount}}}%
143   \end{picture}\footnotesize\thepage\qquad\itshape\shortauthors}
144   \fancyhead[LO]{\begin{picture}(0,0)%
145     \put(-21,-22){\usebox{\RESP@linecount}}}%
146   \end{picture}}
147 \fi
148 \ifRESP@manuscript
149   \fancyfoot[C]{\scriptsize\color{red}Author's Proof}%
150 \fi
151 \ifRESP@preprint
152   \fancyfoot[C]{\scriptsize\color{red}Author's Pre-Print}%
153 \fi

```

The first page has the special headers. The style `firstpage` is invoked by `amsart`; here we just redefine it.

```

154 \fancypagestyle{firstpage}{%
155   \fancyhf{}%
156   \ifRESP@printlinecount
157     \lhead{\begin{picture}(0,0)%
158       \put(-26,-20){\usebox{\RESP@linecount}}}%
159     \end{picture}}
160   \fi
161   \ifRESP@preprint

```

```

162 \cfoot{\footnotesize Res Philosophica, \itshape
163 Vol.~\currentvolume, No.~\currentissue,
164 \currentmonth~\currentyear
165 \ifx\@doinumber\@empty\else\\%
166 \doi{\@doinumber}\fi
167 \\
168 \@copyrightnote}%
169 \thead{\scriptsize\color{red}Author's Pre-print. Forthcoming in
170 Res Philosophica. Pagination may change. Published version will
171 be available at \url{http://pdcnet.org/resphilosophica/}}
172 \else
173 \ifRESP@forthcoming
174 \cfoot{\footnotesize Res
175 Philosophica\itshape
176 \ifx\currentvolume\@empty\else, %
177 Vol.~\currentvolume\fi
178 \ifx\currentissue\@empty\else, No.~\currentissue\fi
179 \ifx\currentmonth\@empty
180 \ifx\currentyear\@empty\else, \currentyear\fi
181 \else,
182 \currentmonth~\currentyear
183 \fi
184 \ifx\@doinumber\@empty\else\\%
185 \doi{\@doinumber}\fi
186 \\
187 \@copyrightnote}%
188 \lhead{\raisebox{1.5\bigskipamount}{\z@}{\z@}{\parbox{\textwidth}{\raggedright\footnotesize
189 \else
190 \cfoot{\footnotesize Res Philosophica, \itshape
191 \itshape Vol.~\currentvolume, No.~\currentissue,
192 \currentmonth~\currentyear, pp.~\start@page--\end@page
193 \ifx\@doinumber\@empty\else\\%
194 \doi{\@doinumber}\fi
195 \\
196 \@copyrightnote}%
197 \fi\fi}

```

4.5 Top Matter Macros

Most top matter macros are defined in `amsart`. Here we just add some new macros and redefine some.

The next macros mimic the functionality of `amsart \issueinfo` command. Note that `\issueinfo` still works.

`\volumenumber` This sets the volume of the paper

```

198 \def\volumenumber#1{\def\currentvolume{#1}}
199 \volumenumber{}

```

`\issuenumber` This sets the issue of the paper:

```

200 \def\issuenum#1{\def\currentissue{#1}}
201 \issuenum{}

\publicationyear This sets the year of the paper
202 \def\publicationyear#1{\def\currentyear{#1}}
203 \publicationyear{}

\publicationmonth This sets the month of the paper
204 \newcommand\publicationmonth[2][\gdef\currentmonth{#2}%
205 \gdef\abbrevcurrentmonth{#1}%
206 \ifx\abbrevcurrentmonth\empty\gdef\abbrevcurrentmonth{#2}\fi}
207 \publicationmonth{}

\papernumber This is absent from the \issueinfo.
208 \def\papernumber#1{\def\currentpaper{#1}}
209 \papernumber{0000}
210 %
211 % \end{macro}
212 %
213 %
214 % \begin{macro}{\doinumber}
215 % \changes{v1.11}{2012/12/25}{Added default}
216 % DOI number for the article:
217 % \begin{macrocode}
218 \def\doinumber#1{\gdef@doinumber{#1}}
219 \doinumber{10.11612/resphil.\currentyear.\currentvolume.\currentissue.\currentpaper}

\paperUrl The url to submit to crossref
220 \def\paperUrl#1{\gdef@paperUrl{#1}}
221 \paperUrl{}

\startpage This defines the starting page of the paper. We have some nice features to set up
roman page numbers for editorial stuff—probably not needed for this journal at
this time...
222 \def\startpage#1{\pagenumbering{arabic}\setcounter{page}{#1}%
223 \def\start@page{#1}%
224 \ifnum\c@page<\z@ \pagenumbering{roman}\setcounter{page}{-#1}%
225 \def\start@page{\romannumeral#1}%
226 \fi}

\endpage This macro again has a twist in it: if the argument is not set, it calculates the last
page number itself.
227 \def\endpage#1{\def@tempa{#1}%
228 \ifx@tempa\empty\def\end@page{\pageref{LastPage}}%
229 \else\def\end@page{#1}\fi}

\pagespan This macro is different from the one provided by amsart because we want to have
the option of automatic calculation of the last page number.
230 \def\pagespan#1#2{\startpage{#1}\endpage{#2}}
231 \pagespan{1}{}

```

`\articleentry` This is necessary for `\prevpaper` command. We read the TOC entry from the previous paper and increment it by 1. Note that we always start with on an odd page, since the additional check

```
232 \def\articleentry#1#2#3#4{\@tempcnta=#4\relax
233   \advance\@tempcnta by 1\relax
234   \ifodd\the\@tempcnta\else\advance\@tempcnta by 1\relax\fi
235   \startpage{\the\@tempcnta}}
```

`\prevpaper` This sets the previous paper location and reads the information from the previous paper

```
236 \def\prevpaper#1{\IfFileExists{#1.rpi}{%
237   \ClassInfo{resphilosophica}{%
238     Reading first page number from the file #1.rpi}%
239   \input{#1.rpi}%
240 }{\ClassWarning{resphilosophica}{Cannot find the file #1.rpi.
241   Did you run latex on the previous paper?}}}
```

`abstract` We slightly redefine abstract comparing to amsart conventions:

```
242 \renewenvironment{abstract}{%
243   \ifx\maketitle\relax
244     \ClassWarning{resphilosophica}{Abstract should precede
245       \protect\maketitle\space in AMS derived classes}%
246   \fi
247   \global\setbox\abstractbox=\vtop\bgroup%
248   \vglue1pc%
249   \list{}{\labelwidth\z@%
250     \leftmargin3pc \rightmargin\leftmargin%
251     \listparindent\normalparindent \itemindent\z@%
252     \parsep\z@ \@plus\p@%
253     \let\fullwidthdisplay\relax%
254   }%
255   \item[]\normalfont\normalsize\textbf{\abstractname:}\space
256 }{%
257   \endlist\egroup%
258   \ifx\@setabstract\relax\@setabstracta\fi%
259 }
```

`\copyrightyear` This is the copyright year in case it does not coincide with the publication year:

```
260 \def\copyrightyear#1{\def\@copyrightyear{#1}}
261 \ifRESP@forthcoming
262   \copyrightyear{\the\year}\else
263   \copyrightyear{}\fi
```

`\onlinedate` Online date for forthcoming issues

```
\@onlinedate 264 \def\onlinedate#1{\gdef\@onlinedate{#1}}
265 \onlinedate{\hspace*{5em}}
```

`\RESP@bulletboxwidth` This is the width of a box with a bullet for copyright note:

```
266 \newlength\RESP@bulletboxwidth
267 \settowidth\RESP@bulletboxwidth{\quad\textbullet\quad}
```


`\copyrightnote` This is the copyrightnote. The default has some trickery with the year and short authors.

The disappearing bullet is based on the trick by Marcin Woliniński, who noted that `\cleaders` are discardable (see [4]).

```
268 \def\copyrightnote#1{\def\@copyrightnote{#1}}
269 \copyrightnote{\textcopyright~%
270   \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
271   \shortauthors\cleaders\hbox{\quad\textbullet\quad}\hskip\RESP@bulletboxwidth
272   \textcopyright~%
273   \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
274   {\upshape Res~Philosophica}}%
```

`\author` The base class puts into `\addresses` the strange line `\author{}`. We correct this:

```
275 \renewcommand{\author}[2][]{%
276   \ifx\@empty\addresses
277     \gdef\addresses{\author{#2}}%
278   \else
279     \g@addto@macro\addresses{\author{#2}}%
280   \fi
281   \ifx\@empty\authors
282     \gdef\authors{#2}%
283   \else
284     \g@addto@macro\authors{\and#2}%
285   \fi
286   \@ifnotempty{#1}{%
287     \ifx\@empty\shortauthors
288       \gdef\shortauthors{#1}%
289     \else
290       \g@addto@macro\shortauthors{\and#1}%
291     \fi
292   }%
293 }
294 \edef\author{\@nx\@dblarg
295   \@xp\@nx\curname\string\author\endcurname}
```

`\titlenote` This command adds an entry to the list of titlenotes

```
296 \def\@titlenotes{%
297 \def\titlenote#1{%
298   \ifx\@empty\@titlenotes\gdef\@titlenotes{\footnote{#1}}%
299   \else\g@addto@macro\@titlenotes{\footnote{#1}}\fi}
```

`\authornote` This command adds an entry to the list of titlenotes

```
300 \def\@authornotes{%
301 \def\authornote#1{%
302   \ifx\@empty\@authornotes\gdef\@authornotes{\footnote{#1}}%
303   \else\g@addto@macro\@authornotes{\footnote{#1}}\fi}
```

4.6 Typesetting Top Matter

`\@settitle` We do not uppercase title. Also, we use this occasion to set PDF information:

```
304 \def\@settitle{\begin{center}%
305   \baselineskip20\p@\relax
306   \LARGE\scshape
307   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
308   \@title\@titlenotes
309   \hypersetup{pdftitle=\@title}%
310   \end{center}%
311 }
```

`\@setauthors` Now we typeset authors according to our specs. Again, we use this occasion to set some PDF information:

```
312 \def\@setauthors{%
313   \ifx\authors\@empty\relax\else
314     \begingroup
315     \def\thanks{\protect\thanks@warning}%
316     \trivlist
317     \centering\footnotesize \@topsep30\p@\relax
318     \advance\@topsep by -\baselineskip
319     \item\relax
320     \def\@and{{and}}
321     \author@andify\authors
322     \hypersetup{pdfauthor=\authors}%
323     \def\{\{\protect\linebreak\}%
324     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
325     \large\normalfont\authors\@authornotes
326     \endtrivlist
327     \endgroup
328   \fi}
```

`\maketitle` We redefine `\maketitle`—mostly to prevent uppercasing of shorttitle and to write down the journal information:

```
329 \def\maketitle{\par
330   \@topnum\z@ % this prevents figures from falling at the top of page 1
331   \@setcopyright
332   \thispagestyle{firstpage}% this sets first page specifications
333   \ifx\@empty\shortauthors \let\shortauthors\shorttitle
334   \else \andify\shortauthors
335   \fi
336   \@maketitle@hook
337   \RESP@write@paper@info
338   \begingroup
339   \@maketitle
340   \toks@{\xp{\shortauthors}\@temptokena\xp{\shorttitle}}%
341   \toks4{\def\{\ \ignorespaces}}% defend against questionable usage
342   \edef\@tempa{%
343     \@nx\markboth{\the\toks4
```

```

344     \@nx\MakeUppercase{\the\toks@}\the\@temptokena}}%
345 \@tempa
346 \endgroup
347 \c@footnote\z@
348 \everypar{\setbox\z@\lastbox\everypar{}}%
349 }

\@maketitle We delete top space introduced by amsart:
350 \def\@maketitle{%
351   \normalfont\normalsize
352   \@adminfootnotes
353   \@mkboth{\@nx\shortauthors}\@nx\shorttitle}%
354   \@settitle
355   \ifx\@empty\authors \else \@setauthors \fi
356   \ifx\@empty\@dedicatory
357   \else
358     \baselineskip18\p@
359     \vtop{\centering{\footnotesize\itshape\@dedicatory\@par}}%
360     \global\dimen@i\prevdepth\prevdepth\dimen@i
361   \fi
362   \@setabstract
363   \normalsize
364   \if@titlepage
365     \newpage
366   \else
367     \dimen@34\p@ \advance\dimen@-\baselineskip
368     \vskip\dimen@\relax
369   \fi
370 } % end \@maketitle

\@mainrpi The stream for the rpi file:
371 \newwrite\@mainrpi

\RESP@write@paper@info This writes the information about the paper into the file jobname.rpi. Note that
hyperref makes our life a little bit more complex
372 \def\RESP@write@paper@info{%
373   \bgroup
374   \if@filesw
375     \openout\@mainrpi\jobname.rpi%
376     \write\@mainrpi{\relax}%
377     \ifx\r@LastPage\undefined
378       \edef\@tempa{\start@page}%
379     \else
380       \def\@tempb##1##2##3##4##5{##2}%
381       \edef\@tempa{\expandafter\@tempb\r@LastPage}%
382     \fi
383     \def\and{\string\and\space}%
384     \protected@write\@mainrpi{%
385       {\string\articleentry{\authors}\@title}\@start@page}\@tempa}}%

```

The next lines are for crossref software

```

386 \protected@write\@mainrpi{}%
387 {\@percentchar authors=\authors}%
388 \protected@write\@mainrpi{}%
389 {\@percentchar title=\@title}%
390 \protected@write\@mainrpi{}%
391 {\@percentchar year=\currentyear}%
392 \protected@write\@mainrpi{}%
393 {\@percentchar volume=\currentvolume}%
394 \protected@write\@mainrpi{}%
395 {\@percentchar issue=\currentissue}%
396 \protected@write\@mainrpi{}%
397 {\@percentchar paper=currentpaper}%
398 \protected@write\@mainrpi{}%
399 {\@percentchar startpage=start@page}%
400 \protected@write\@mainrpi{}%
401 {\@percentchar endpage=@tempa}%
402 \protected@write\@mainrpi{}%
403 {\@percentchar doi=@doinumber}%
404 \ifx\@paperUrl\@empty\else
405 \protected@write\@mainrpi{}%
406 {\@percentchar paperUrl=\@paperUrl}%
407 \fi
408 \closeout\@mainrpi
409 \fi
410 \egroup}

```

\@adminfootnotes We just define this to noop:

```

411 \def\@adminfootnotes{}

```

\@cleartopmattertags We typeset thankses at the end of the paper so we do not clear them:

```

412 \def\@cleartopmattertags{%
413 \def\do##1{\let##1\relax}%
414 \do\maketitle \do\@maketitle \do\title \do\@xtitle \do\@title
415 \do\author \do\@xauthor \do\address \do\@xaddress
416 \do\contrib \do\contribs \do\@xcontribs \do\tocontribs
417 \do\email \do\@xemail \do\curraddr \do\@xcurraddr
418 \do\commby \do\@commby
419 \do\dedicatory \do\@dedicatory \do\thanks
420 \do\keywords \do\@keywords \do\subjclass \do\@subjclass

```

\sf@size It seems there is a bug in mdugm when calculating \sf@size. Here we work around it:

```

421 \def\sfontsize{7}%
422 }

```

4.7 Notes

```
\notes This is like bibliography:
423 \definecollection{notes}
424 \newenvironment{notes}[1]{%
425   \@nameuse{collect}{notes}{}{}}%
426   \makeatletter
427   \par\addpenalty\@secpenalty\addvspace{\bigskipamount}%
428   \noindent \Small #1:\par\nobreak\vskip\medskipamount\@afterheading
429   \makeatother
430 }{\@nameuse{endcollect}\AddtoEndMatter{\includecollection{notes}}}
```

4.8 Typesetting End Matter

End matter is typeset at the end of the paper.

```
\if@enddoc Check whether we are in the end matter
431 \newif\if@enddoc
432 \@enddocfalse
```

```
\enddoc@text We put thankses into end matter. Also, we redefine bibliography back to the
original definition in case someone writes \AddtoEndMatter{\bibliography{}}
```

```
433 \def\enddoc@text{%
434   \@enddoctrue\def\bibliography{\RESP@bibliography}%
435   \ifx\@empty\thankses\else
436     \bgroup
437     \let\@makefnmark\relax
438     \let\@thefnmark\relax
```

Check, whether we are at the same page as the last footnote; if yes, add medskip.

```
439   \ifx\lastfootnote@page\@undefined\else
440     \@tempcnta=\lastfootnote@page\relax
441     \ifnum\c@page=\@tempcnta\relax
442       \insert\footins{\medskip}%
443     \fi
444   \fi
445   \@footnotetext{%
446     \def\par{\let\par\@par}\textbf{Acknowledgements\quad} \@setthanks}%
447   \egroup
448   \fi
449   \ifx\@empty\@translators \else\@settranslators\fi
450   \ifx\@empty\addresses \else\@setaddresses\fi}
```

```
\ifRESP@firstingroup A group of authors is separated by a skip from another group. This macro checks
whether this is the first one
```

```
451 \newif\ifRESP@firstingroup
```

```
\emailaddrname The name for e-mail address:
452 \def\emailaddrname{E-mail}
```

`\@setaddresses` Unlike `aomart`, we want to preserve author's name in the address block. Also, we want to keep linebreaks and to have clickable e-mail and URL.

We want to skip between the author groups (several authors with the same affiliation), so we check whether the previous line contains another author:

```

453 \def\@setaddresses{\par
454   \nobreak \begingroup\flushright\clubpenalty\@MM\interlinepenalty\@MM
455   \widowpenalty\@MM
456   \RESP@firstingroupttrue
457 \Small
458   \def\author##1{\nobreak\ifRESP@firstingroup\par
459     \addvspace\bigskipamount\penalty-1000\fi
460     \RESP@firstingrouptfalse##1\par\nobreak}%
461   \parindent\z@
462   \def\address##1##2{\RESP@firstingroupttrue\begingroup
463     \par\nobreak
464     \ifnotempty{##1}{(\ignorespaces##1\unskip) }%
465     {\ignorespaces##2}\par\endgroup}%
466   \def\curraddr##1##2{\RESP@firstingroupttrue\begingroup
467     \ifnotempty{##2}{\nobreak\indent\curraddrname
468       \ifnotempty{##1}{, \ignorespaces##1\unskip}\hskip0.2em:\space
469       ##2\par}\endgroup}%
470   \def\email##1##2{\RESP@firstingroupttrue\begingroup
471     \ifnotempty{##2}{\nobreak\indent\emailaddrname
472       \ifnotempty{##1}{, \ignorespaces##1\unskip}\hskip0.2em:\space
473       \href{mailto:##2}{\nolinkurl{##2}}\par}\endgroup}%
474   \def\urladdr##1##2{\RESP@firstingroupttrue\begingroup
475     \ifnotempty{##2}{\nobreak\indent
476       \ifnotempty{##1}{, \ignorespaces##1\unskip}%
477       \url{##2}\par}\endgroup}%
478   \addresses
479   \endgroup
480 }
```

At the end we eject the last page. If the document is printed and the last page is odd, we add an empty page.

```

481 \AtEndDocument{\clearpage
482   \ifRESP@manuscript\else
483   \ifRESP@screen\else
484   \ifRESP@preprint\else
485   \ifRESP@forthcoming\else
486   \cleardoublepage
487   \fi\fi\fi\fi}
```

4.9 Sectioning

`\@secntformat` We do not want our numbers to be upright and medium series, as `amsart` wants:

```

488 \def\@secntformat#1{%
489   \csname the#1\endcsname\enspace
490 }
```

```

\section We want our sections to be large and bold:
491 \renewcommand\section{\@startsection {section}{1}{\z@}%
492         {-3.5ex \@plus -1ex \@minus -.2ex}%
493         {2.3ex \@plus .2ex}%
494         {\normalfont\large\bfseries}}

\subsection Subsections are bold
495 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
496         {-3.25ex \@plus -1ex \@minus -.2ex}%
497         {1.5ex \@plus .2ex}%
498         {\normalfont\normalsize\bfseries}}

\subsubsection Subsubsections are normalsize and italic
499 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
500         {-3.25ex \@plus -1ex \@minus -.2ex}%
501         {1.5ex \@plus .2ex}%
502         {\normalfont\normalsize\itshape}}

\paragraph Paragraphs:
503 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
504         {3.25ex \@plus 1ex \@minus .2ex}%
505         {-1em}%
506         {\normalfont\normalsize\bfseries}}

\subparagraph Paragraphs:
507 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
508         {3.25ex \@plus 1ex \@minus .2ex}%
509         {-1em}%
510         {\normalfont\normalsize\bfseries}}

4.10 Additional Commands

\@mparswitch We always put marginpars on the right since the line box is on the left
511 \@mparswitchfalse

\EditorialComment This macro is noop in normal mode, but is a tiny marginpar in the manuscript
mode
512 \newcommand\EditorialComment[2][0]{%
513   \expandafter\ifx\csname EditorialComment@#1\endcsname\relax
514   \else\bgroup
515   \marginparwidth=200pt\marginpar{\color{red}%
516     \raggedright#2}\egroup\fi}

\ECSelect This selects the given levels
517 \def\ECSelect#1{\ifRESP@manuscript
518   \@for\EC@level:=#1\do{%
519     \expandafter\gdef\csname
520       EditorialComment@\EC@level\endcsname{\EditorialComment}}%
521   \fi}

```

`\TC` The command to highlight text if the corresponding level is selected. The first argument is the level, the second is text.

```

522 \newcommand\TC[2][0]{%
523   \expandafter\ifx\csname TC@highlight@#1\endcsname\relax#2\else
524   \csname TC@highlight@#1\endcsname{#2}\fi}

```

`\TCSelect` This switches on the selected levels in the mqnuscript version

```

525 \newcommand\TCSelect[2][magenta]{\ifRESP@manuscript
526   \@for\TC@level:=#2\do{\expandafter
527     \gdef\csname TC@highlight@\TC@level\endcsname##1{\bgroup
528       \Hy@colorlinksfalse
529       \def\Hy@colorlink####1{\begingroup}%
530       \def\Hy@endcolorlink{\endgroup}%
531       \color{#1}##1\egroup}}%
532   \fi}

```

`\doi` Typesetting doi...

```

533 \def\doi#1{\url{http://dx.doi.org/#1}}

```

`\@makefnmark` The definition of `\@makefnmark` in amsart has a bug. Here we return to the L^AT_EX one:

```

534 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}

```

`\@makefntext` Unlike amsart, we do not indent footnotes:

```

535 \def\@makefntext{\noindent\@makefnmark
536   \if@enddoc\else
537     \immediate\write\@mainaux%
538     {\string\xdef\string\lastfootnote@page{\the\c@page}}%
539   \fi}
540 \long\def\@footnotetext#1{%
541   \insert\footins{%
542     \normalfont\footnotesize
543     \interlinepenalty\interfootnotelinepenalty
544     \splittopskip\footnotesep \splitmaxdepth \dp\strutbox
545     \floatingpenalty\MM \hsize\columnwidth
546     \@parboxrestore \parindent\normalparindent \sloppy
547     \protected@edef\currentlabel{%
548       \csname p@footnote\endcsname\@thefnmark}%
549     \@makefntext{%
550       \,\rule\z@\footnotesep\ignorespaces#1\unskip\strut\par}}}

```

4.11 The End

Philosophers love footnotes, since `\raggedbottom`

```

551 \raggedbottom\normalsize\normalfont
552 \end{class}

```


References

- [1] Boris Veytsman. *Support files for the Linotype Sabon Fonts*, August 2012. <http://mirrors.ctan.org/fonts/lsabon/>.
- [2] Patrick W. Daly. *Natural Sciences Citations and References (Author-Year and Numerical Schemes)*, February 2009. <http://mirrors.ctan.org/macros/latex/contrib/natbib>.
- [3] American Mathematical Society. *Instructions for Preparation of Papers and Monographs, AMS \LaTeX* , August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/instr-1.pdf>.
- [4] Paweł Jackowski. \TeX beauties and oddities. *TUGboat*, 29:207–215, 2008. <http://www.tug.org/TUGboat/tb29-1/tb91pearls.pdf>.

Change History

v1.1		\publicationyear: The default is now empty	15
	\@maketitle: Redefined macro . .		19
	\@mparswitch: Changed default . .		23
	\@setauthors: Changed font . . .		18
	General: Added DOI number		1
	Added MT Shadow Imprint code . .		1
	\doi: Added macro		24
	\EditorialComment: Added macro .		23
	\ifRESP@mtshadow: Added macro . .		9
	\ifRESP@rpfontoauto: Added macro		9
	rpfont: Added option		9
	\RESP@write@paper@info: Added protection for \		19
	\rpdefault: Added macro		11
	\section: Moved to LaTeX defaults		23
	\subsection: Moved to LaTeX defaults		23
	\subsubsection: Moved to LaTeX defaults		23
v1.10	General: Bibliography changes . . .		1
v1.11	General: Bibliography changes . . .		1
	\papernumber: Added macro		15
	\RESP@write@paper@info: Added writing info for crossref		19
v1.12	General: Bibliography changes . . .		1
v1.13	\@settitle: Added titlenotes . . .		18
	General: Changed check for line numbering mode		13
	New command: titlenote		1
	New options: preprint and forthcoming		1
	\copyrightnote: Changed font family for forthcoming mode . .		17
	\ifRESP@forthcoming: Added option		10
	\ifRESP@preprint: Added option . .		10
	\issuenumber: The default is now empty		14
	\publicationmonth: The default is now empty		15
	\RESP@printlinecount: Added macro		13
	\titlenote: Added command		17
	\volumenumber: The default is now empty		14
v1.14	\sf@size: Bug corrected		20
v1.15	General: Added new bibliography command		1
v1.16	\@makefntext: Added small space after footnote mark		24
	\@onlinedate: Added macro		16
	General: Added \bfdefault		11
	Added documentation about typesetter changes highlighting .		1
	Deleted Imprint Shadow		1
	\copyrightnote: Deleted rpdefault		17
	\ifRESP@mtshadow: Deleted macro .		9
	\maketitle: Added suppressing first para indentation		18
	\notes: Added macro		21
	\onlinedate: Added macro		16
	rpfont: Deleted option		9
	\publicationmonth: Added \abbrevcurrentmonth		15
	\rpdefault: Deleted macro		11
	\TC: Added macro		24
	\TCSelect: Added macro		24
v1.17	General: Added collect package . .		11
	Added documentation about new editorial comments		1
	Bibliography changes: ‘inloosecollection’ entry		1
	Journal name on the first page footer is now italic		13
	Online date for forthcoming option moved to the left and up .		13
	\ECSelect: Added macro		23
	\EditorialComment: Redefined so levels are supported		23

\notes: Redefined using collect package	21	General: New command: au-	
		thornote	1
v1.18		\authornote: Added command . .	17
General: Journal name in Roman	13	v1.3	
Online date for forthcoming op-		\@setaddresses: Added penalties	22
tion moved down	13	\@setauthors: Deleted ifpdf . . .	18
\copyrightnote: Made journal		\@settitle: Deleted ifpdf	18
name Roman	17	General: Added penalties	11
v1.19		Ifpdf is no longer needed with	
\TCSelect: Switched off colored		modern engines	11
links	24	\copyrightyear: In the forthcom-	
v1.2		ing mode the copyright year is	
\@adminfootnotes: Redefined . .	20	the present year	16
\@cleartopmattertags: Redefined	20	\pdfpaperheight: Deleted ifpdf .	12
\@setaddresses: Changed font . .	22	\RESP@linecount: Changed check	
\@setauthors: Changed font . . .	18	for linecount	13
General: Changed font for bibliog-		v1.4	
raphy	11	\@makefntext: Redefined	24
Changed skip for bibliography	11	General: Added footmisc package	
\copyrightnote: Used \rpdefault		with ‘bottom’ option	11
for RP font	17	Added screen option	1
\enddoc@text: Redefined	21	Changed bibsection font	11
\listisep: Redefined	12	Changed color of “Author’s	
\RESP@write@paper@info: Used		proof’ mark	13
\protected@write	19	\EditorialComment: Changed	
\section: Changed font	23	color	23
\subsection: Changed font	23	Changed font	23
\subsubsection: Changed font . .	23	\ifRESP@screen: Added option . .	10
v1.20		\paragraph: Moved to LaTeX de-	
\@makefnmark: Redefined	24	fault	23
v1.21		\pdfpaperheight: Changed paper	
\paperUrl: Added macro	15	in the manuscript mode	12
\RESP@write@paper@info: Added		\RESP@linecount: Changed color	13
paperUrl	19	\subparagraph: Moved to LaTeX	
v1.22		default	23
General: Now we add empty even		v1.5	
page at the end for printed ver-		\@makefntext: Added writing the	
sion only	22	current footnote page to the aux	
v1.23		file	24
General: Switched to twoside mode		General: Changed color for headers	
of amsart	11	and footers	13
\oddsidemargin: Made even- and		Color change for links	1
odd- side margins different, ex-		Hyperfootnotes are incompatible	
cept in screen and forthcoming		with hyperref	11
modes	12	\EditorialComment: Changed	
\pdfpaperheight: Added to pa-		color	23
per width to accomodate larger		\enddoc@text: Added flag	21
thumb side margins	12	\if@enddoc: Added macro	21
v1.24		\RESP@linecount: Changed color	13
\@setauthors: Added authornotes	18		

v1.6		the last page is odd	1
	General: Changed bib style	\enddoc@text: Changed bibliogra-	
v1.7		phy	21
	General: Added new bibliography	\sf@size: Added definition	20
	fields		
	Changed formatting of doi	v1.9	
	\doi: Changed formatting	\@setaddresses: Added penalties	22
	\footskip: Decreased to fit doi	\copyrightnote: Made bullet dis-	
	number	appear at break	17
v1.8		\RESP@bulletboxwidth: Added	
	General: Added blank last page if	macro	16

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
\,	550	\@mainrpi . 371, 375, 376, 384, 386, 388, 390, 392, 394, 396, 398, 400, 402, 405, 408
\@and	320	\@makefnmark 437, <u>534</u> , 535
\@par	359	\@makefntext <u>535</u>
\@MM	454, 455, 545	\@maketitle 339, <u>350</u> , 414
\@adminfootnotes . .		\@maketitle@hook . . 336
.	352, <u>411</u>	\@minus 492, 496, 500, 504, 508
\@afterheading . 98,	428	\@mkboth 353
\@authornotes		\@mparswitch <u>511</u>
. 300, 302, 303, 325		\@mparswitchfalse . 511
\@cleartopmattertags		\@nameuse 425, 430
.	<u>412</u>	\@ne 131, 133
\@commby	418	\@nx 294, 295, 343, 344, 353
\@copyrightnote . . .		\@onlinedate . . 188, <u>264</u>
. 168, 187, 196, 268		\@paperUrl 220, 404, 406
\@copyrightyear . . .		\@par 446
. 260, 270, 273		\@parboxrestore . . . 546
\@currentlabel	547	\@percentchar 387, 389, 391, 393, 395, 397, 399, 401, 403, 406
\@dblarg	294	\@plus 252, 492, 493, 496, 497, 500, 501, 504, 508
\@dedicatory		\@secCNTformat <u>488</u>
. 356, 359, 419		\@secpenalty . . . 97, 427
\@doinumber . . . 165,		\@setabstract . 258, 362
166, 184, 185,		\@setabstracta 258
193, 194, 218, 403		\@setaddresses 450, <u>453</u>
\@empty . . . 165, 176,		\@setauthors . . <u>312</u> , 355
178, 179, 180,		\@setcopyright 331
184, 193, 206,		\@setthanks 446
228, 270, 273,		\@setttitle . . . <u>304</u> , 354
276, 281, 287,		\@settranslators . . 449
298, 302, 313,		\@startsection 491, 495, 499, 503, 507
333, 355, 356,		\@subjclass 420
404, 435, 449, 450		
\@enddocfalse	432	\@tempa 227, 228, 342, 345, 378, 381, 385, 401
\@enddoctrue	434	\@tempb 380, 381
\@fnsymbol . . . 307, 324		\@tempcnta 131, 132, 133, 232, 233, 234, 235, 440, 441
\@footnotetext 445, 540		\@temptokena . . 340, 344
\@for 518, 526		\@textsuperscript . 534
\@ifnotempty . . 286,		\@thefnmark 438, 534, 548
464, 467, 468,		\@title 308, 309, 385, 389, 414
471, 472, 475, 476		\@titlenotes 296, 298, 299, 308
\@keywords	420	\@topnum 330
\@mainaux	537	\@topsep 317, 318
		\@translators 449
		\@undefined . . . 377, 439
		\@xaddress 415
		\@xauthor 415
		\@xcurraddr 417
		\@xemail 417
		\@xp 295, 340
		\@xtitle 414
		\\ 132, 165, 167, 184, 186, 193, 195, 323, 341

A

\abbrevcurrentmonth 205, 206
\abstract	<u>242</u>
abstract (environ-	ment) 4
\abstractbox	247
\abstractname	255
\addpenalty	97, 427
\address	3, 415, 462
\addresses	276, 277, 279, 450, 478
\AddtoEndMatter 8, <u>91</u> , 96, 430
\addvspace	97, 427, 459

\advance	133,	\clubpenalty	454		446, 452, 453,
233, 234, 318, 367		\color	132, 149,		458, 462, 466,
\and	284, 290, 383	152, 169, 515, 531			470, 474, 488,
\andify	334	\columnwidth	545		517, 529, 530,
\articleentry	<u>232</u> , 385	\commby	418		533, 534, 535, 540
\AtBeginDocument	102	\contrib	416	\define@boolkey	42
\AtEndDocument	94, 481	\contrihs	416	\define@choicekey	10, 26
\author	<u>3</u> , <u>275</u> , 415, 458	\copyrightnote	<u>4</u> , <u>268</u>	\definecollection	423
\author@andify	321	\copyrightyear	<u>4</u> , <u>260</u>	\dimen@	367, 368
\authornote	<u>4</u> , <u>300</u>	\csname	295,	\dimen@i	360
\authors 281, 282, 284,		489, 513, 519,		\do	413, 414, 415,
313, 321, 322,		523, 524, 527, 548		416, 417, 418,	
325, 355, 385, 387		\curraddr	<u>3</u> , 417, 466	419, 420, 518, 526	
		\curraddrname	467	\doi	166, 185, 194, <u>533</u>
		\currentissue		\doinumber	
B		163, 178,	5, 214, 218, 219
\baselineskip	191, 200, 219, 395	\dp	544
.	305, 318, 358, 367				
\begin	141, 144,	\currentmonth	164,		
157, 214, 217, 304		179, 182, 192, 204		E	
\begingroup	314,	\CurrentOption	49,	\EC@level	518, 520
338, 454, 462,		50, 51, 52, 53, 66		\ECSselect	<u>6</u> , <u>517</u>
466, 470, 474, 529		\currentpaper		\edef	294, 342, 378, 381
\bfdefault	84	208, 219, 397	\EditorialComment	
\bfseries		\currentvolume	<u>5</u> , <u>512</u> , 520
.	494, 498, 506, 510	163, 176, 177,	\egroup	257,
\bgroup	247,	191, 198, 219, 393		410, 447, 516, 531	
373, 436, 514, 527		\currentyear 164, 180,		\else	73, 74,
\bibfont	99	182, 192, 202,		75, 76, 89, 101,	
\bibliography 95, 96, 434		219, 270, 273, 391		165, 172, 176,	
\bibliographystyle	94	D		178, 180, 181,	
\bibsection	97	\DeclareOptionX	49,	184, 189, 193,	
\bigskipamount		50, 51, 52, 53,		229, 234, 262,	
.	97, 188, 427, 459	56, 59, 62, 65, 66		270, 273, 278,	
\bodyfont	<u>10</u>	\dedicatory	419	283, 289, 299,	
bodyfont (option)	<u>2</u>	\def	46, 89, 90,	303, 313, 334,	
C		91, 96, 97, 99,		355, 357, 366,	
\c@footnote 307, 324, 347		198, 200, 202,		379, 404, 435,	
\c@page	224, 441, 538	208, 218, 220,		439, 449, 450,	
\centering	317, 359	222, 223, 225,		482, 483, 484,	
\cfoot	162, 174, 190	227, 228, 229,		485, 514, 523, 536	
\changes	215	230, 232, 236,		\email	<u>3</u> , 417, 470
\chead	169	260, 264, 268,		\emailaddrname <u>452</u> , 471	
\ClassInfo	237	296, 297, 300,		\end	143,
\ClassWarning		301, 304, 312,		146, 159, 211, 310	
.	47, 240, 244	315, 320, 323,		\end@page	192, 228, 229
\cleaders	271	329, 341, 350,		\endcsname	295,
\cleardoublepage	486	372, 380, 383,		489, 513, 520,	
\clearpage	481	411, 412, 413,		523, 524, 527, 548	
\closeout	408	421, 433, 434,		\enddoc@text	91, 433

\leftmargin	250	\normalsize	255,	\protected@edef . . .	547
\let	95, 253, 333, 413, 437, 438, 446	351, 363, 498, 502, 506, 510, 551	\protected@write	384, 386, 388, 390, 392, 394, 396, 398, 400, 402, 405
\lhead	157, 188	\notes	<u>423</u>	\publicationmonth	4, <u>204</u>
\linebreak	323	notes (environment) . .	6	\publicationyear	4, <u>202</u>
\list	249	\nr	10, 12, 26, 28	\put	142, 145, 158
\listisep	<u>118</u>	O			
\listparindent	251	\oddsidemargin	<u>107</u>	Q	
\LoadClass	68	\onlinedate	3, <u>264</u>	\qqquad	138, 139, 143
\long	46, 540	\openout	375	\quad	267, 271, 446
\loop	132	options:		R	
M		bodyfont	2	\r@LastPage	377, 381
\makeatletter	426	forthcoming	3	\raggedbottom	551
\makeatother	429	manuscript	3	\raggedright	188, 516
\maketitle	4, 243, 245, <u>329</u> , 414	natbib	3	\raisebox	188
\MakeUppercase	344	preprint	3	\relax	12, 28, 131, 232, 233, 234, 243, 253, 258, 305, 313, 317, 319, 368, 376, 413, 437, 438, 440, 441, 513, 523
manuscript (option) . .	3	screen	3	\renewcommand	83, 84, 121, 122, 275, 307, 324, 491, 495, 499, 503, 507
\marginpar	515	\or 14, 17, 20, 30, 33, 36		\renewenvironment .	242
\marginparwidth . . .	515	P		\repeat	133
\markboth	343	\p@ 252, 305, 317, 358, 367		\RequirePackage	1, 69, 70, 71, 81, 82, 93
\medskip	442	\PackageWarning	24, 40, 43	\RESP@bibliography 95, 96, 434
\medskipamount	98, 118, 428	24, 40, 43	\RESP@bulletboxwidth <u>266</u> , 271
N		\pagenumbering	222, 224	\RESP@firstingroupfalse 460
\natbib	<u>42</u>	\pageref	228	\RESP@firstingrouptrue 456, 462, 466, 470, 474
natbib (option)	3	\pagespan	<u>230</u>	\RESP@fontautofalse 15, 18, 21
\newcommand	204, 512, 522, 525	\pagestyle	135	\RESP@fontautotruer 3, 13, 25
\newenvironment	424	\papernumber	4, <u>208</u>	\RESP@forthcomingfalse 64
\newif	2, 4, 6, 8, 54, 57, 60, 63, 124, 431, 451	\paperUrl	5, <u>220</u>	\RESP@forthcomingtrue 65
\newlength	266	\par	97, 98, 329, 427, 428, 446, 453, 458, 460, 463, 465, 469, 473, 477, 550		
\newpage	365	\paragraph	<u>503</u>		
\newsavebox	129	\parbox	130, 188		
\newwrite	371	\parindent	461, 507, 546		
\nobreak	98, 428, 454, 458, 460, 463, 467, 471, 475	\parsep	252		
\noindent	98, 428, 535	\PassOptionsToClass	66		
\nolinkurl	473	\pdfpageheight	103		
\normalfont	255, 325, 351, 494, 498, 502, 506, 510, 534, 542, 551	\pdfpagewidth	102		
\normalparindent . . .	251, 546	\pdfpaperheight . . .	<u>101</u>		
		\pdfpaperwidth	<u>101</u>		
		\penalty	459		
		preprint (option) . . .	3		
		\prevdepth	360		
		\prevpaper	5, <u>236</u>		
		\ProcessOptionsX . . .	67		
		\protect	245, 315, 323		

