

The RUBIKPATTERNS package

RWD Nickalls (dick@nickalls.org)
A Syropoulos (asyropoulos@yahoo.com)

This file describes version 4.0 (2017/03/03)
www.ctan.org/pkg/rubik

Abstract

The RUBIKPATTERNS package is a small data-base of well-known named Rubik patterns and associated rotation sequences, for use in conjunction with the RUBIKCUBE and RUBIKROTATION packages. It is part of the Rubik ‘bundle’.

Contents

1	Introduction	2
1.1	Installation	2
1.1.1	Placing the files	2
1.2	Usage	3
2	Rubik patterns	3
2.1	Sequence macros	4
2.2	List of macros	4
3	Change history	5
4	References	6
5	The code	6
5.1	Package heading	6
5.2	Patterns	6
5.2.1	Superflip	6
5.2.2	Reid data	7

1 Introduction

The RUBIKPATTERNS package is a small a data-base of well-known Rubik rotation sequences for use in conjunction with the RUBIKCUBE and RUBIKROTATION packages. These sequences, which are well-known and widely available, were sourced from the Rubik-related websites of Reid M and Kociemba H (see References for URLs).

1.1 Installation

Place the file `rubikpatterns.zip` into a temporary directory, and unzip it. This will generate the following files:

```
rubikpatterns.ins
rubikpatterns.dtx
rubikpatterns.pdf      --this document
rubikpatternsLIST.tex
rubikpatternsLIST.pdf
```

The package documentation is the file `rubikpatterns.pdf`. The style option `rubikpatterns.sty` is generated by running (pdf)TeX on the file `rubikpatterns.ins` as follows:

```
pdflatex rubikpatterns.ins
```

The documentation file (`rubikpatterns.pdf`) is then generated using the following sequence of steps¹:

```
pdflatex rubikpatterns.dtx
pdflatex rubikpatterns.dtx
makeindex -s gind.ist rubikpatterns
makeindex -s gglo.ist -o rubikpatterns.gls rubikpatterns.glo
pdflatex rubikpatterns.dtx
pdflatex rubikpatterns.dtx
```

1.1.1 Placing the files

Place the files either in a working directory, or where your system will find them, e.g., in your `/texmf-local/` directory tree. For example, on a Linux platform with a standard TeX Directory Structure (TDS), then:

```
*.sty → /usr/local/texlive/texmf-local/tex/latex/rubik/
*.pdf → /usr/local/texlive/texmf-local/doc/rubik/
```

FILE DATABASE: Finally, (depending on your system) update the TeX file database. For example, on a Linux platform this is achieved using the `texhash` command.

¹Since the documentation includes a complicated indexing system as well a PDF index and hyperref links (the package `hypdoc` is used), then a lot of pdflatex runs are required. Prior to the first run it is a good idea to delete any relevant `.toc`, `.aux`, `.out` files.

1.2 Usage


Load the packages RUBIKCUBE, RUBIKROTATION and RUBIKPATTERNS in the \TeX file preamble *after* loading the TikZ package; for example, as follows:

```
\usepackage{tikz}
\usepackage{rubikcube,rubikrotation,rubikpatterns}
```

Since the sequence macros made available by this package are accessed using commands provided by the RUBIKCUBE and RUBIKROTATION packages, please read the documentation of these packages.

2 Rubik patterns

A Rubik pattern is the configuration generated by a sequence of rotations (or ‘moves’) from some initial starting configuration (typically a ‘solved’ configuration). For example, ‘sixspot’ is a well known pattern generated from a solved Rubik cube by the rotation sequence U,Dp,R,Lp,F,Bp,U,Dp, as follows:



The code for the above image is as follows:

```
\noindent\hfil%
\RUBIKCUBE{SolvedWB}%
\ShowCube{2.4cm}{0.6}{\DrawRubikCubeRU}%
\RUBIKROTATION{\SixSpot}%
\quad\SequenceBraceA{\SixSpot}{\ShowSequence{}{\RUBIK}{\SequenceLong}}\quad%
\ShowCube{2.4cm}{0.6}{\DrawRubikCubeRU}%
\hfil%
```

Note that the appearance of a pattern generated by a given rotation sequence is, of course, sensitive to (a) the particular colour configuration of the solved cube used, and (b) the initial orientation of the Rubik cube.

Consequently the appearance generated by a given sequence may appear slightly different from that on some websites, although the colour configuration (pattern’s *geometry*) will, of course, be the same (isomorphic). You may therefore need to adjust the pre- (and possibly the post-) x,y,z rotations in order to obtain a particular configuration as displayed elsewhere.

2.1 Sequence macros

Each of the rotation sequences of ‘patterns’ made available by the RUBIKPATTERNS package is defined in the file `rubikpatterns.sty` in the following compact macro form. For example, the rotation sequence associated with the pattern known as ‘SixSpot’ (shown in the figure above) is defined as follows:

```
\newcommand{\SixSpot}{[SixSpot],U,Dp,R,Lp,F,Bp,U,Dp,<(8q*, 8f*)>}\newcommand{\sixspot}{\SixSpot}
```

The macro name is `\SixSpot` (the lower-case version `\sixspot` can also be used). Note that the second argument which includes the rotation sequence, also includes the pattern name in square brackets `[SixSpot]` as the first element in the sequence. Additional metadata (held by the macro `\SequenceInfo`) is appended in angle brackets (separated by a comma) as follows: `<(8q*, 8f*)>`. For details see the RUBIKROTATION package documentation.

2.2 List of macros

The following is a list of the macro names of all the Rubik patterns supplied by the RUBIKPATTERNS package. Note that for convenience each macro-name listed has an equivalent lower-case version. See the companion file `rubikpatternsLIST.pdf` for a detailed list showing each pattern and its associated sequence ².

All the pattern names encoded here (as macros) are well-known and widely available. However, some pattern names have been slightly modified in order to avoid spaces and to keep them as similar to the original as possible. On finding different sequences which generate the same pattern, then the shortest sequence has been selected (they can be readily distinguished by their metadata).

Finally, we note that there is a serious need for a standardised one-word nomenclature in order to avoid confusion, and to facilitate computerisation and an electronic database. Such a notation also needs to accommodate those sequence variations which generate the same pattern. We welcome suggestions and/or help for improvement.

```
\PonsAsinorum
\CheckerboardsThree
\CheckerboardsSix
\Stripes
\CubeInCube
\CubeInCubeInCube
\ChristmasCross
\PlummersCross
\Anaconda
\Python
\BlackMamba
```

²We show all these images in a separate file (`rubikpatternsLIST.pdf`) purely because generating them requires using the L^AT_EX command-line option `--shell-escape` in conjunction with the RUBIKROTATION package.

```

\GreenMamba
\FemaleRattlesnake
\MaleRattlesnake
\FemaleBoa
\MaleBoa
\FourSpot
\SixSpot
\OrthogonalBars
\SixTs
\SixTwoOne
\ExchangedPeaks
\TwoTwistedPeaks
\FourTwistedPeaks
\ExchangedChickenFeet
\TwistedChickenFeet
\ExchangedRings
\TwistedRings
\EdgeHexagonTwo
\EdgeHexagonThree
\TomParksPattern
\RonsCubeInCube
\TwistedDuckFeet
\ExchangedDuckFeet
\Superflip

```

Note that the particular superflip sequence made available by this package (shown in `rubikpatternsLIST.pdf`) is due to Reid (1995), and is detailed on the Kociemba webpage <http://www.kociemba.org/math/oh.htm>. Indeed, this was the first sequence to define the ‘20-move’ (HTM) upper boundary for solving a Rubik cube (see Rokicki *et al.*, 2013).

The superflip configuration is also significant since it is its own inverse. For example, the following two `\RubikRotation` commands will generate the same configuration (starting from a solved cube):

```

\RubikRotation{\superflip}
\RubikRotation{\superflip,<inverse>}

```

This property is shown as one of the examples in the Rubik bundle file `rubikexamples.pdf`.

3 Change history

- Version 4.0 (March 2017)
 - First release of this package.

4 References

- Fridrich website (Fridrich J). See the ‘Pretty patterns’ webpage <http://www.ws.binghamton.edu/fridrich/ptrns.html>
- Kociemba website (Kociemba H). <http://www.kociemba.org/cube.htm>
—for superflip see: <http://www.kociemba.org/math/oh.htm>
- Randelshofer website (Randelshofer W). Pretty patterns. <http://www.randelshofer.ch/rubik/patterns/U080.01.html>
- Reid M. Patterns. <http://www.cflmath.com/Rubik/patterns.html>
- Reid M. (1995). Superflip requires 20 face turns. (January 1995) <http://www.math.ucf.edu/~reid/Rubik/CubeLovers/> (see Section 5.2.1)
[cited from Rokicki *et al.*, 2013].
(Note: easier to use is the following html indexed version of the archive of the Cube-Lovers usenet group (1982–1997) <http://www.math.rwth-aachen.de/~Martin.Schoenert/Cube-Lovers/>)
- Rokicki T, Kociemba H, Davidson M and Dethridge J (2013). The diameter of the Rubik’s cube is twenty. *SIAM. J. Discrete Math.*, **27**, 1082–1105. <http://tomas.rokicki.com/rubik20.pdf>

5 The code (`rubikpatterns.sty`)

5.1 Package heading

```
1 {*rubikpatterns}
2 \def\RPfileversion{4.0}%
3 \def\RPfiledate{2017/03/03}%
4 \NeedsTeXFormat{LaTeX2e}
5 \ProvidesPackage{rubikpatterns}[\RPfiledate\space (\v\RPfileversion)]
```

\rubikpatterns First we create a suitable logo
6 \newcommand{\rubikpatterns}{\textsc{rubikpatterns}}

5.2 Patterns

5.2.1 Superflip

This particular superflip sequence is from the Kociemba website (his Oh webpage). It is due to Reid (1995).

```
7 \newcommand{\Superflip}{[Superflip],Dp,R2,Fp,D2,F2,U2,Lp,R,Dp,R2,B,F,Rp,%
8 U2,Lp,F2,Rp,U2,Rp,Up,<(20f*)>}%
9 \newcommand{\superflip}{\Superflip}
```

5.2.2 Reid data

These named sequences are derived from the Reid website.

```

10 \newcommand{\PonsAsinorum}{[PonsAsinorum],F2,B2,R2,L2,U2,D2,<(12q*, 6f*)>}%
11 \newcommand{\ponsasinorum}{\PonsAsinorum}%
12 \newcommand{\CheckerboardsThree}{%
13 {[CheckerboardsThree],F,B2,Rp,D2,B,R,U,Dp,R,Lp,Dp,Fp,R2,D,F2,Bp,<(20q*, 16f*), order 3}>}%
14 \newcommand{\checkerboardsthree}{\CheckerboardsThree}%
15 \newcommand{\CheckerboardsSix}{%
16 {[CheckerboardsSix],R2,L2,U,B,L2,Dp,F,B2,R,Lp,Fp,B,R,D,F2,Lp,Up,<(17f*, 22q), order 6}>}%
17 \newcommand{\checkerboardssix}{\CheckerboardsSix}%
18 \newcommand{\Stripes}{[Stripes],F,U,F,R,L2,B,Dp,R,D2,L,Dp,B,R2,L,F,U,F,<(20q*, 17f*)>}%
19 \newcommand{\stripes}{\Stripes}%
20 \newcommand{\CubeInCube}{[CubeInCube],F,L,F,Up,R,U,F2,L2,Up,Lp,B,Dp,Bp,L2,U,<(18q*, 15f*)>}%
21 \newcommand{\cubeincube}{\CubeInCube}%
22 \newcommand{\CubeInCubeInCube}{%
23 {[CubeInCubeInCube],Fp,U,Bp,Rp,U,F2,Fp,Up,F,U2,D,Bp,Dp,R2,B2,Up,<(17f*, 22q)>}%
24 \newcommand{\cubeincubeincube}{\CubeInCubeInCube}%
25 \newcommand{\ChristmasCross}{[ChristmansCross],U,F,Bp,L2,U2,L2,Fp,B,U2,L2,U,<(16q*, 11f*)>}%
26 \newcommand{\christmascross}{\ChristmasCross}%
27 \newcommand{\PlummersCross}{%
28 {[PlummersCross],R2,Lp,D,F2,Rp,Dp,Rp,L,Up,D,R,D,B2,Rp,U,D2,<(20q*, 16f*)>}%
29 \newcommand{\plummerscross}{\PlummersCross}%
30 \newcommand{\Anaconda}{[Anaconda],L,U,Bp,Up,R,Lp,B,Rp,F,Bp,D,R,Dp,Fp,<(14q*, 14f*)>}%
31 \newcommand{\anaconda}{\Anaconda}%
32 \newcommand{\Python}{[Python],F2,Rp,Bp,U,Rp,L,Fp,L,Fp,B,Dp,R,B,L2,<(16q*, 14f*)>}%
33 \newcommand{\python}{\Python}%
34 \newcommand{\BlackMamba}{[BlackMamba],R,D,L,Fp,R,Lp,D,Rp,U,Dp,B,Up,Rp,Dp,<(14q*, 14f*)>}%
35 \newcommand{\blackmamba}{\BlackMamba}%
36 \newcommand{\GreenMamba}{[GreenMamba],R,D,R,F,Rp,Fp,B,D,Rp,Up,Bp,U,D2,<(14q*, 13f*)>}%
37 \newcommand{\greenmamba}{\GreenMamba}%
38 \newcommand{\FemaleRattlesnake}{%
39 {[FemaleRattlesnake],U2,Dp,L2,D,B,U,Bp,Rp,L2,U2,F,Up,F,R,<(18q*, 14f*)>}%
40 \newcommand{\femalerattlesnake}{\FemaleRattlesnake}%
41 \newcommand{\MaleRattlesnake}{%
42 {[MaleRattlesnake],Rp,Fp,U,Fp,U2,R,L2,B,Up,Bp,Dp,L2,U2,D,<(18q*, 14f*)>}%
43 \newcommand{\malerattlesnake}{\MaleRattlesnake}%
44 \newcommand{\FemaleBoa}{[FemaleBoa],R,Up,R2,U2,F,D2,R2,Up,Dp,R,Dp,Fp,<(16q*, 12f*)>}%
45 \newcommand{\femaleboa}{\FemaleBoa}%
46 \newcommand{\MaleBoa}{[MaleBoa],F,D,Rp,U,D,R2,D2,Fp,U2,R2,U,Rp,<(16q*, 12f*)>}%
47 \newcommand{\maleboa}{\MaleBoa}%
48 \newcommand{\FourSpot}{[FourSpot],F2,B2,U,Dp,R2,L2,U,Dp,<(12q*, 8f*)>}%
49 \newcommand{\fourspot}{\FourSpot}%
50 \newcommand{\SixSpot}{[SixSpot],U,Dp,R,Lp,F,Bp,U,Dp,<(8q*, 8f*)>}%
51 \newcommand{\sixspot}{\SixSpot}%
52 \newcommand{\OrthogonalBars}{%
53 {[OrthogonalBars],F,Rp,U,L,Fp,Lp,F,Up,R,U,Lp,Up,L,Fp,<(14q*, 14f*)>}%
54 \newcommand{\orthogonalbars}{\OrthogonalBars}%
55 \newcommand{\SixTs}{[SixTs],F2,R2,U2,Fp,B,D2,L2,F,B,<(14q*, 9f*)>}%
56 \newcommand{\sixts}{\SixTs}%

```

```

57 \newcommand{\SixTwoOne}{[SixTwoOne] ,U,B2,D2,L,Bp,Lp,Up,Lp,B,D2,B2,<(15q*, 11f*)>}%
58 \newcommand{\sixtwoone}{\SixTwoOne}%
59 \newcommand{\ExchangedPeaks}{%
60 {[ExchangedPeaks],F2,R2,D,R2,U,D,F2,Dp,Rp,Dp,F,L2,Fp,D,R,Up,<(16f*, 21q*)>}%
61 \newcommand{\exchangedpeaks}{\ExchangedPeaks}%
62 \newcommand{\TwoTwistedPeaks}{%
63 {[TwoTwistedPeaks],F,D2,B,R,Bp,Lp,F,Dp,L2,F2,R,Fp,Rp,F2,Lp,Fp,<(16f*, 20q*)>}%
64 \newcommand{\twotwistedpeaks}{\TwoTwistedPeaks}%
65 \newcommand{\FourTwistedPeaks}{%
66 {[FourTwistedPeaks],Up,D,B,Rp,F,R,Bp,Lp,Fp,B,L,F,Rp,Bp,R,Fp,Up,D,<(18q*, 18f*)>}%
67 \newcommand{\fourtwistedpeaks}{\FourTwistedPeaks}%
68 \newcommand{\ExchangedChickenFeet}{%
69 {[ExchangedChickenFeet],F,Lp,Dp,Bp,L,F,U,Fp,Dp,F,L2,Bp,Rp,U,L2,Dp,F,<(19q*, 17f*)>}%
70 \newcommand{\exchangedchickenfeet}{\ExchangedChickenFeet}%
71 \newcommand{\TwistedChickenFeet}{%
72 {[TwistedChickenFeet],F,Lp,D,Fp,Up,B,U,F,Up,F,Rp,F2,L,Up,Rp,D2,<(18q*, 16f*)>}%
73 \newcommand{\twistedchickenfeet}{\TwistedChickenFeet}%
74 \newcommand{\ExchangedRings}{%
75 {[ExchangedRings],F,U,Dp,Lp,B2,L,Up,D,F,U,R2,L2,Up,L2,F2,<(15f*, 20q*)>}%
76 \newcommand{\exchangedrings}{\ExchangedRings}%
77 \newcommand{\TwistedRings}{%
78 {[TwistedRings],F,D,Fp,D2,Lp,Bp,U,L,D,R,U,Lp,Fp,U,L,U2,<(18q*, 16f*)>}%
79 \newcommand{\twistedrings}{\TwistedRings}%
80 \newcommand{\EdgeHexagonTwo}{%
81 {[EdgeHexagonTwo],U,B2,Up,Fp,Up,D,Lp,D2,L,U,Dp,F,Dp,L2,B2,Dp,<(20q*, 16f*) order 2>}%
82 \newcommand{\edgehexagontwo}{\EdgeHexagonTwo}%
83 \newcommand{\EdgeHexagonThree}{%
84 {[EdgeHexagonThree],F,L,B,U,L,F2,B2,Rp,F2,B2,Up,Bp,Lp,Fp,<(14f*, 18q) order 3>}%
85 \newcommand{\edgehexagonthree}{\EdgeHexagonThree}%
86 \newcommand{\TomParksPattern}{%
87 {[TomParksPattern],L,U,F2,R,Lp,U2,Bp,U,D,B2,L,F,Bp,Rp,L,Fp,R,<(20q*, 17f*)>}%
88 \newcommand{\tomparkspattern}{\TomParksPattern}%
89 \newcommand{\RonsCubeInCube}{%
90 {[RonsCubeInCube],L2,D2,Lp,D2,B2,L2,B2,Lp,D2,L2,B2,Lp,B2,<(13f*, 23q*)>}%
91 \newcommand{\ronscubeincube}{\RonsCubeInCube}%
92 \newcommand{\TwistedDuckFeet}{%
93 {[TwistedDuckFeet],F,Rp,B,R,U,Fp,Lp,Fp,U2,Lp,Up,D2,B,Dp,F,Bp,U2,<(20q*, 17f*)>}%
94 \newcommand{\twistedduckfeet}{\TwistedDuckFeet}%
95 \newcommand{\ExchangedDuckFeet}{%
96 {[ExchangedDuckFeet],U,F,R2,Fp,Dp,R,U,B2,U2,Fp,R2,F,D,B2,R,Bp,<(21q*, 16f*)>}%
97 \newcommand{\exchangedduckfeet}{\ExchangedDuckFeet}%

```

End of this package

98 </rubikpatterns>

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

A		P
\Anaconda	30, 31	\femaleboa 45
\anaconda	31	\FemaleRattlesnake 38, 40
		\femalerattlesnake 40
B		\FourSpot 48, 49
\BlackMamba	34, 35	\fourspot 49
\blackmamba	35	\FourTwistedPeaks 65, 67
		\fourtwistedpeaks 67
C		
\CheckerboardsSix	15, 17	G
\checkerboardssix	17	\GreenMamba 36, 37
\CheckerboardsThree	12, 14	\greenmamba 37
\checkerboardsthree	14	
\ChristmansCross	26	M
\ChristmasCross	25	\MaleBoa 46, 47
\christmascross	26	\maleboa 47
\CubeInCube	20, 21	\MaleRattlesnake 41, 43
\cubeincube	21	\malerattlesnake 43
\CubeInCubeInCube	22, 24	
\cubeincubeincube	24	N
		\NeedsTeXFormat 4
D		\newcommand 6,
\def	2, 3	7, 9, 10, 11, 12,
		14, 15, 17, 18,
E		19, 20, 21, 22,
\EdgeHexagonThree	83, 85	24, 25, 26, 27,
\edgehexagonthree	85	29, 30, 31, 32,
\EdgeHexagonTwo	80, 82	33, 34, 35, 36,
\edgehexagontwo	82	37, 38, 40, 41,
\ExchangedChickenFeet	68, 70	43, 44, 45, 46,
		47, 48, 49, 50,
\exchangedchickenfeet	70	51, 52, 54, 55,
		56, 57, 58, 59,
\ExchangedDuckFeet	95, 97	61, 62, 64, 65,
		67, 68, 70, 71,
\exchangedduckfeet	97	73, 74, 76, 77,
\ExchangedPeaks	59, 61	79, 80, 82, 83,
\exchangedpeaks	61	85, 86, 88, 89,
\ExchangedRings	74, 76	91, 92, 94, 95, 97
\exchangedrings	76	
F		O
\FemaleBoa	44, 45	\OrthogonalBars 52, 54
		\orthogonalbars 54
P		
\PlummersCross	27, 29	
\plummerscross	29	
\PonsAsinorum	10, 11	
\ponsasinorum	11	
\ProvidesPackage	5	
\Python	32, 33	
\python	33	
R		
\RonsCubeInCube	89, 91	
\ronscubeincube	91	
\RPfiledate	3, 5	
\RPfileversion	2, 5	
\rubikpatterns	6	
S		
\SixSpot	50, 51	
\sixspot	51	
\SixTs	55, 56	
\sixts	56	
\SixTwoOne	57, 58	
\sixtwoone	58	
\space	5	
\Stripes	18, 19	
\stripes	19	
\Superflip	7, 9	
\superflip	9	
T		
\textsc	6	
\TomParksPattern	86, 88	
\tomparkspattern	88	
\TwistedChickenFeet	71, 73	
		\twistedchickenfeet 73
\TwistedDuckFeet	92, 94	
\twistedduckfeet	94	
\TwistedRings	77, 79	
\twistedrings	79	
\TwoTwistedPeaks	62, 64	
\twotwistedpeaks	64	