

The `savetrees` package*

Scott Pakin
`scott+st@pakin.org`

April 9, 2013

1 Introduction

The goal of the `savetrees` package is to pack as much text as possible onto each page of a L^AT_EX document. Admittedly, this makes the document far less attractive. Nevertheless, `savetrees` provides a simple way to save paper when printing draft copies of a document. It can also be useful when trying to meet a tight page-length requirement. For example, consider the difference between

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitae lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitae augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Aenean odio turpis, laoreet non vulputate eu, fermentum sed metus.

and

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitae lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitae augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Aenean odio turpis, laoreet non vulputate eu, fermentum sed metus.

*This document corresponds to `savetrees` v2.1, dated 2013/04/09.

The former (default) layout looks nicer, but the latter consumes approximately 10% less space.

The easiest way to use `savetrees` is simply to place one of the following in your document's preable:

- `\usepackage[subtle]{savetrees}`
- `\usepackage[moderate]{savetrees}`
- `\usepackage[extreme]{savetrees}`

The first option, `subtle`, preserves all document layout and merely encourages L^AT_EX to try harder to pack text onto the page while introducing white space only when absolutely necessary. The second option, `moderate`, additionally reduces paragraph indentation, typesets lists and mathematical displays without indentation or surrounding vertical space, reduces interline spacing, and makes the font slightly narrower, if supported. The third option, `extreme`, which is in fact the default if no package options are specified, turns on all of the space-saving techniques in `savetrees`'s repertoire, including using smaller title and section fonts, typesetting the bibliography with a smaller font and no inter-item spacing, and substantially reducing the page margins. For a demonstration of these package options, see the accompanying `st-sample2e.pdf` file, which presents Lampert's "An Example Document" typeset both normally and with each of `savetrees`'s `subtle`, `moderate`, and `extreme` options.

The following section describes those and the rest of `savetrees`'s space-saving capabilities in more detail.

2 Usage

Table 1 to Table 3 on pages 3–4 describe `savetrees`'s main package options and summarize their implementation. Some package options merely load a package or redefine some variables. Others redefine entire environments to consume less space. A few resort to some underhanded T_EX trickery to squeeze as much text as possible onto the page. See the annotated source code listing in Section 4 for the definitive description of the mechanics underlying the `savetrees` package.

Each of the options that appears in Table 1 through Table 3 can be set to either `tight` or `normal`. `tight`, the default, enables the space-saving technique while `normal` disables it. For example, specifying `\usepackage[title=normal]{savetrees}` instructs `savetrees` not to modify the font size and spacing used to typeset the document's title. The `all` option can be used to set all of `savetrees`'s options en masse to either `tight` or `normal`. For example, if only a few space-saving techniques should be enabled, it may be more convenient to specify `all=normal` followed by a small list of options set to `tight` than to specify `normal` typesetting for a large set of options. The arguments passed to `\usepackage` are processed left-to-right.

Table 1: `savetrees` package options for enabling/disabling space-saving techniques (`subtle`)

Option	Space-saving technique	Implementation
<code>paragraphs</code>	Discourage \TeX from allowing the last line of a paragraph to contain only a single word.	Reassign <code>\looseness</code> .
<code>floats</code>	Relax float placement (more floats per page, increased ability to share pages with text, etc.).	Reassign $\text{\LaTeX}\ 2\varepsilon$ float variables.
<code>mathspacing</code>	Reduce the amount of space within mathematical expressions.	Reassign <code>\thinmuskip</code> , <code>\medmuskip</code> , and <code>\thickmuskip</code> .
<code>wordspacing</code>	Reduce the amount of space between words.	Reassign <code>\fontdimen2</code> .
<code>tracking</code>	Reduce the amount of space between characters.	Pass options to the <code>microtype</code> package.

Table 2: `savetrees` package options for enabling/disabling space-saving techniques (`moderate`)

Option	Space-saving technique	Implementation
<code>bibnotes</code>	Ignore <code>NOTE</code> fields in the bibliography.	Pass information to <code>savetrees.bst</code> .
<code>charwidths</code>	Allow character glyphs to be drawn slightly narrower than normal.	Pass options to the <code>microtype</code> package.
<code>mathdisplays</code>	Reduce the amount of vertical space surrounding displayed mathematics.	Reassign <code>\abovedisplayskip</code> , <code>\belowdisplayskip</code> , <code>\abovedisplayshortskip</code> , and <code>\belowdisplayshortskip</code> .
<code>leading</code>	Reduce interline spacing.	Reassign <code>\baselinestretch</code> .
<code>indent</code>	Decrease paragraph indentation.	Reassign <code>\parindent</code> .
<code>lists</code>	Remove both indentation and inter-item spacing from the various list environments.	Redefine the <code>itemize</code> , <code>enumerate</code> , and <code>description</code> environments.

Table 3: `savetrees` package options for enabling/disabling space-saving techniques (`extreme`)

Option	Space-saving technique	Implementation
<code>bibliography</code>	Typeset the bibliography in a smaller font and with no inter-item spacing.	Redefine <code>\thebibliography</code> .
<code>title</code>	Typeset the document title with smaller fonts and with less surrounding white space.	Redefine <code>\maketitle</code> .
<code>sections</code>	Typeset section titles with smaller fonts and with less surrounding white space.	Pass options to the <code>titlesec</code> package.
<code>margins</code>	Reduce the page margins.	Pass options to the <code>geometry</code> package.

As convenient shortcuts, the options in Table 1 can be enabled as a group by passing the `subtle` option to `savetrees`; the options in both Table 1 and Table 2 can be enabled as a group by passing the `moderate` option to `savetrees`; and all of the options in Table 1, Table 2, and Table 3 can be enabled as a group by passing the `extreme` option to `savetrees`.

The options in Table 1 through Table 3 are presented in roughly decreasing order of subtlety. If you find that `savetrees`'s default options—or the `subtle`, `moderate`, and `extreme` meta-options—produce too hideous a result, try incrementally setting to `normal` the options from the bottom of the options list up, and see if doing so improves the document's appearance while still saving space over the non-`savetrees` version. That is, start by including `margins=normal` in the optional argument to `\usepackage`. Then add `sections=normal`, then `title=normal`, and so forth, rebuilding the document and examining the result each time. Alternatively, if you need to save just a small amount of space (e.g., if your document is just barely over a maximum page length), specify `all=normal` then incrementally add options from the top of the three tables downwards: `paragraphs=tight`, then `floats=tight`, then `mathspacing=tight`, and so forth. Appendix B presents examples of some of `savetrees`'s space-saving features so you can decide for yourself which are worth the price paid in typesetting elegance.

Saving space in a document is always a balancing act between document aesthetics and the amount of space that can be saved. If you find that a particular space-saving option makes the document formatting just a little too ugly—or if you're willing to make it even uglier to save even more space—`savetrees` provides additional package options that let you adjust the aggressiveness of various space-saving techniques. Table 4 on the following page lists and describes these package options. As an example, L^AT_EX's normal line height is defined to have a value of 1.0. When `savetrees` is loaded with `leading=tight` (the default), Table 4

Table 4: `savetrees` package options for refining the way space is saved

Option	Description	Requires <code>tight</code>	Default
<code>charwidthfraction</code>	Fraction of normal character widths	<code>charwidths</code>	0.95
<code>leadingfraction</code>	Fraction of normal line height	<code>leading</code>	0.95
<code>marginwidth</code>	Width of the page margins	<code>margins</code>	1.5cm
<code>parindent</code>	Paragraph indentation	<code>indent</code>	1em
<code>trackingfraction</code>	Fraction of normal inter-character spacing	<code>tracking</code>	0.975
<code>wordspacingfraction</code>	Fraction of normal inter-word spacing	<code>wordspacing</code>	0.8

indicates that the line height is reduced to 95% of that. Additionally including `leadingfraction=0.98` on the `\usepackage` line increases the line height to 98% of L^AT_EX’s default—still a space reduction but possibly a somewhat less overt one.

There are a few restrictions on the space-saving techniques that can be applied. The `tracking` option requires pdfL^AT_EX. The `charwidths` option requires either pdfL^AT_EX or LuaL^AT_EX. For both options, pdfL^AT_EX must be in PDF mode, not DVI mode. See the `microtype` documentation for additional (and possibly more up-to-date) information.

3 Abbreviating bibliographic information

One of the advantages of a tool like BIBT_EX is that the bibliographic database can—and should—contain complete bibliographic information for each reference while style files determine the subset of that information that is actually typeset. Hence, to help further reduce a document’s length, the `savetrees` package additionally provides a BIBT_EX style file, `savetrees.bst`, which exhibits the following salient differences from `plain.bst`:

- Abbreviations are used wherever possible:

chapter	⇒ chap.
edition	⇒ ed.
editor <i>or</i> editors	⇒ ed. <i>or</i> eds.
January, February, ...	⇒ Jan., Feb., ...
page <i>or</i> pages	⇒ p. <i>or</i> pp.
Technical Report	⇒ Tech. Rep.

- At most two authors are listed. The remainder are replaced by “et al.”
- Authors’ names are abbreviated to their initials plus surname (e.g., “S. D. Pakin”).

In addition, `savetrees.bst` does not normally typeset NOTE fields, although it can be instructed to do so by passing `savetrees` the `bibnotes=normal` package option.

To use `savetrees.bst`, simply replace your document’s existing `\bibliographystyle` line with “`\bibliographystyle{savetrees}`”. Then, to give `savetrees.bst`—or *any* BIBTEX style file—maximum flexibility, you should obey the following rules when writing your `.bib` file:

1. Use the three-letter month macros defined by virtually all BIBTEX style files instead of spelling out month names explicitly:

Good:	<code>MONTH = sep</code> ,	Can be typeset as “September”, “Sept.”, “SEP”, “Septiembre”, etc.
Bad:	<code>MONTH = {September}</code> ,	Can be typeset only as “September”.

2. Include authors’ full names (or as much of each name as is available); let BIBTEX abbreviate as necessary:

Good:	<code>AUTHOR = {Rufus Xavier Sarsaparilla}</code> ,	Can be typeset either in full or abbreviated to “Rufus X. Sarsaparilla”, “R. X. Sarsaparilla”, etc.
Bad:	<code>AUTHOR = {R. X. Sarsaparilla}</code> ,	Can be typeset only as “R. X. Sarsaparilla” and can’t be expanded to the full name.

3. Include the names of *all* authors; let BIBTEX decide where to truncate the list:

Good:	<code>AUTHOR = {Rufus Xavier Sarsaparilla and Rafaella Gabriela Sarsaparilla and Albert Andreas Armadillo}</code> ,	All authors can be named, or the list can be truncated at any point with “et al.”, “and others”, or whatever.
Bad:	<code>AUTHOR = {Rufus Xavier Sarsaparilla and others}</code> ,	At most one author can be named, but “and others” can still be replaced by “et al.” or a different phrase, and the author’s name can still be abbreviated, as discussed in the previous rule.
Worse:	<code>AUTHOR = {{Rufus Xavier Sarsaparilla, et al.}}</code> ,	Can be typeset only precisely as “Rufus Xavier Sarsaparilla, et al.”

The `savetrees` BIB_TE_X style utilizes the same fields as the standard BIB_TE_X styles (`plain`, `alpha`, `abbrv`, `unsrt`, etc.), with the exception that the `NOTE` field is suppressed unless the `bibnotes=normal` package option is provided.

As of version 2.0 of `savetrees`, `savetrees.bib` can be used independently of `savetrees.sty`.

4 Implementation of `savetrees.sty`

This section presents the complete, commented source code for the `savetrees` package. Although reading this section—and the subsequent implementation sections—is not necessary for understanding how to use `savetrees`, it may be a useful teaching instrument for L^AT_EX newcomers who want to learn more about fine-tuning document formatting.

1 `(*package)`

4.1 Default values

`savetrees` attempts to provide a reasonable balance between aesthetics and the amount of space saved in a document. However, `savetrees` does enable the document author to adjust a number of parameters to bias `savetrees`'s behavior towards either reduced document length or prettier output. This section defines the default values for various package parameters.

`\st@margin@width` When `margins=tight`, `\st@margin@width` specifies how wide the page margins should be. The default, 1.5cm, is extremely small, but it can sure save a lot of space on the page.

2 `\newcommand*\{\st@margin@width\}{1.5cm}`

`\st@parindent` The standard L^AT_EX classes (`article`, `report`, and `book`) define paragraph indentation as follows. If `twocolumn` is in effect, `\parindent` is set to 1 em. Otherwise, if the base font size is 10 pt., `\parindent` is set to 15 pt.; if the base font size is 11 pt., `\parindent` is set to 17 pt.; and if the base font size is 12 pt., `\parindent` is set to 1.5 em. When `indent=tight`, `savetrees` uses a default of 1 em—approximately a third of the no-`savetrees` value—regardless of font size.

3 `\newcommand*\{\st@parindent\}{1em}`

`\st@baselinestretch` Depending on font size, the standard L^AT_EX classes (`article`, `report`, and `book`) use 2–2.6 pt. lead (inter-line spacing), or approximately 20% of font size. Specifically, they typeset body text at 10/12, 11/13.6, or 12/14.5. When `leading=tight`, `savetrees` reduces the line spacing to 95% of normal or an average of about 0.67 pt. less lead than L^AT_EX's defaults: 10/11.4, 11/12.92, or 12/13.78. 95% gives very good compression but still prevents descenders from running into successive ascenders.

4 `\newcommand*\{\st@baselinestretch\}{0.95}`

<code>\st@char@shrink</code>	When <code>charwidths=tight</code> , <code>savetrees</code> disables font expansion but enables font compaction. The default contraction of 5% (50/1000) of normal character widths is largely undetectable to the casual observer but can save a great deal of space over the course of a long document.
	5 <code>\newcommand*\{\st@char@shrink\}{50}</code>
<code>\st@cspace@shrink</code>	<code>savetrees</code> reduces tracking (inter-character spacing) when <code>tracking=tight</code> . By default, tracking is set to -2.5% (-25/1000) of an em width. When decreased much more than that, characters begin to overlap and become hard to read.
	6 <code>\newcommand*\{\st@cspace@shrink\}{-25}</code>
<code>\st@wspace@factor</code>	<code>savetrees</code> reduces inter-word spacing when <code>wordspacing=tight</code> . By default, inter-word spacing is set to 80% of normal. If decreased much beyond that, words start to run together and become hard to read.
	7 <code>\newcommand*\{\st@wspace@factor\}{0.8}</code>

4.2 Option processing

4.2.1 Enabling/disabling space-saving techniques

By default, `savetrees` tries to make documents extremely dense. However, this also makes them rather ugly. The package options defined below let the author specify which space-saving routines are unacceptably grotesque and should not be utilized.

`savetrees` uses the `xkeyval` package to parse its package options.

```
8 \RequirePackage{xkeyval}
```

<code>\st@more@packages</code>	As we process the package options we may encounter additional packages that we need to load. Rather than load them eagerly, which may lead to the same package problematically being loaded twice with different options, we merely construct a list of required packages. Then, as <code>savetrees</code> 's last action before finishing, it loads all of the pending packages. <code>\st@RequirePackage</code> takes the same arguments as <code>\RequirePackage</code> but simply adds the package name to the <code>\st@more@packages</code> list and instructs L ^A T _E X 2 _{<} to eventually pass the given arguments, if any, to the package.
<code>\st@RequirePackage</code>	

```
9 \def\st@more@packages{}
10 \newcommand*\{\st@RequirePackage\}[2] []{%
11   \PassOptionsToPackage{\#1}{\#2}%
12   \cons\st@more@packages{\{\#2\}}%
13 }
14 \AtEndOfPackage{%
15   \let\@elt=\RequirePackage
16   \st@more@packages
17   \let\@elt=\relax
18 }
```

```

\st@define@option savetrees accepts a large number of package options, each of which can be set to
    \st@arg tight (the default) to enable a feature or normal to disable it. As the definitions
    \st@arg@num of these options are fairly repetitive, we define a helper macro to assist with the
    processing.

19 \newcommand*{\st@define@option}[1]{%
20   \expandafter\newif\csname if@st@tight@\#1\endcsname
21   \csname @st@tight@\#1true\endcsname
22   \def\choicekey{savetrees}{#1}[\st@arg\st@arg@num]{tight,normal}[tight]{%
23     \ifnum\st@arg@num=0
24       \csname @st@tight@\#1true\endcsname
25     \else
26       \csname @st@tight@\#1false\endcsname
27     \fi
28   }%
29   \DeclareOptionX{#1}[tight]{\csname KV@savetrees@\#1\endcsname{##1}}%
30 }

```

Using the preceding macro we define one conditional and one package option for each trick in `savetrees`'s book. When *true* (caused by passing `tight` to the package option), the conditional enables the corresponding space compression; when *false*, (caused by passing `normal` to the package option), `savetrees` leaves alone that aspect of the formatting.

<code>\if@st@tight@sections</code>	The <code>sections</code> package option enables or disables <code>savetrees</code> 's modifications to section titles by setting <code>\@st@tight@sectionstrue</code> or <code>\@st@tight@sectionsfalse</code> , respectively.
<code>\KV@savetrees@sections</code>	31 <code>\st@define@option{sections}</code>
<code>\if@st@tight@margins</code>	The <code>margins</code> package option enables or disables <code>savetrees</code> 's modifications to page margins by setting <code>\@st@tight@marginstrue</code> or <code>\@st@tight@marginsfalse</code> , respectively.
<code>\KV@savetrees@margins</code>	32 <code>\st@define@option{margins}</code>
<code>\if@st@tight@lists</code>	The <code>lists</code> package option enables or disables <code>savetrees</code> 's modifications to the various list environments by setting <code>\@st@tight@liststrue</code> or <code>\@st@tight@listsfalse</code> , respectively.
<code>\KV@savetrees@lists</code>	33 <code>\st@define@option{lists}</code>
<code>\if@st@tight@floats</code>	The <code>floats</code> package option enables or disables <code>savetrees</code> 's modifications to L ^A T _E X's float-placement parameters by setting <code>\@st@tight@floatstrue</code> or <code>\@st@tight@floatsfalse</code> , respectively.
<code>\KV@savetrees@floats</code>	34 <code>\st@define@option{floats}</code>
<code>\if@st@tight@indent</code>	The <code>indent</code> package option enables or disables <code>savetrees</code> 's modifications to paragraph indentation by setting <code>\@st@tight@indenttrue</code> or <code>\@st@tight@indentfalse</code> , respectively.
<code>\KV@savetrees@indent</code>	35 <code>\st@define@option{indent}</code>

<code>\if@st@tight@title \@st@tight@titletrue \@st@tight@titlefalse \KV@savetrees@title \if@st@tight@leading \@st@tight@leadingtrue \@st@tight@leadingfalse \KV@savetrees@leading</code>	The <code>title</code> package option enables or disables <code>savetrees</code> 's modifications to title formatting by setting <code>\@st@tight@titletrue</code> or <code>\@st@tight@titlefalse</code> , respectively. 36 <code>\st@define@option{title}</code>
	The <code>leading</code> package option enables or disables <code>savetrees</code> 's modifications to inter-line spacing by setting <code>\@st@tight@leadingtrue</code> or <code>\@st@tight@leadingfalse</code> , respectively. This interline spacing is known as “leading” because of the additional strips of lead placed between lines in the days of metal type. 37 <code>\st@define@option{leading}</code>
<code>\if@st@tight@paragraphs \@st@tight@paragraphstrue \@st@tight@paragraphsfalse \KV@savetrees@paragraphs</code>	The <code>paragraphs</code> package option enables or disables <code>savetrees</code> 's modifications to <code>TeX</code> 's paragraph looseness (i.e., the number of lines by which <code>TeX</code> is instructed to shrink each paragraph) by setting <code>\@st@tight@paragraphstrue</code> or <code>\@st@tight@paragraphsfalse</code> , respectively. 38 <code>\st@define@option{paragraphs}</code>
<code>\if@st@tight@charwidths \@st@tight@charwidthstrue \@st@tight@charwidthsfalse \KV@savetrees@charwidths</code>	The <code>charwidths</code> package option enables or disables <code>savetrees</code> 's modifications to character width by setting <code>\@st@tight@charwidthstrue</code> or <code>\@st@tight@charwidthsfalse</code> , respectively. 39 <code>\st@define@option{charwidths}</code>
<code>\if@st@tight@tracking \@st@tight@trackingtrue \@st@tight@trackingfalse \KV@savetrees@tracking</code>	The <code>tracking</code> package option enables or disables <code>savetrees</code> 's modifications to tracking (spacing between letters) by setting <code>\@st@tight@trackingtrue</code> or <code>\@st@tight@trackingfalse</code> , respectively. 40 <code>\st@define@option{tracking}</code>
<code>\if@st@tight@wordspacing \@st@tight@wordspacingtrue \@st@tight@wordspacingfalse \KV@savetrees@wordspacing</code>	The <code>wordspacing</code> package option enables or disables <code>savetrees</code> 's modifications to inter-word spacing by setting <code>\@st@tight@wordspacingtrue</code> or <code>\@st@tight@wordspacingfalse</code> , respectively. 41 <code>\st@define@option{wordspacing}</code>
<code>\if@st@tight@bibliography \@st@tight@bibliographytrue \@st@tight@bibliographyfalse \KV@savetrees@bibliography</code>	The <code>bibliography</code> package option enables or disables <code>savetrees</code> 's modifications to bibliography formatting by setting <code>\@st@tight@bibliographytrue</code> or <code>\@st@tight@bibliographyfalse</code> , respectively. 42 <code>\st@define@option{bibliography}</code>
<code>\if@st@tight@bibnotes \@st@tight@bibnotestrue \@st@tight@bibnotesfalse \KV@savetrees@bibnotes</code>	The <code>bibnotes</code> package option conditionally excludes or includes NOTE fields when using <code>savetrees.bst</code> by setting <code>\@st@tight@bibnotestrue</code> or <code>\@st@tight@bibnotesfalse</code> , respectively. 43 <code>\st@define@option{bibnotes}</code>
<code>\if@st@tight@mathspacing \@st@tight@mathspacingtrue \@st@tight@mathspacingfalse \KV@savetrees@mathspacing</code>	The <code>mathspacing</code> package option enables or disables <code>savetrees</code> 's modifications to horizontal spacing within mathematical expressions by setting <code>\@st@tight@mathspacingtrue</code> or <code>\@st@tight@mathspacingfalse</code> , respectively. 44 <code>\st@define@option{mathspacing}</code>

```

\if@st@tight@mathdisplays
\@st@tight@mathdisplaystrue
\@st@tight@mathdisplaysfalse
\KV@savetrees@mathdisplays
```

The `mathdisplays` package option enables or disables `savetrees`'s modifications to vertical spacing surrounding mathematical displays by setting `\@st@tight@mathdisplaystrue` or `\@st@tight@mathdisplaysfalse`, respectively.

```
45 \st@define@option{mathdisplays}
```

4.2.2 Meta options

`savetrees` provides a large number of package options, which might be overwhelming for a casual user. Here, we define a few “meta options” that set multiple, related, package options en masse.

```

\KV@savetrees@all
\st@arg
\st@arg@num
46 \define@choicekey{savetrees}{all}[\st@arg\st@arg@num]{tight,normal}[tight]{%
47   \ifnum\st@arg@num=0
48     \@st@tight@sectionstrue
49     \@st@tight@marginstrue
50     \@st@tight@liststrue
51     \@st@tight@floatstrue
52     \@st@tight@indenttrue
53     \@st@tight@titletrue
54     \@st@tight@leadingtrue
55     \@st@tight@paragraphstrue
56     \@st@tight@charwidthstrue
57     \@st@tight@trackingtrue
58     \@st@tight@wordspacingtrue
59     \@st@tight@bibliographytrue
60     \@st@tight@bibnotestrue
61     \@st@tight@mathspacingtrue
62     \@st@tight@mathdisplaystrue
63   \else
64     \@st@tight@sectionsfalse
65     \@st@tight@marginsfalse
66     \@st@tight@listsfalse
67     \@st@tight@floatsfals
68     \@st@tight@indentfalse
69     \@st@tight@titlefalse
70     \@st@tight@leadingfalse
71     \@st@tight@paragraphsfals
72     \@st@tight@charwidthsfals
73     \@st@tight@trackingfalse
74     \@st@tight@wordspacingfalse
75     \@st@tight@bibliographyfalse
76     \@st@tight@bibnotesfalse
77     \@st@tight@mathspacingfalse
78     \@st@tight@mathdisplaysfals
79   \fi
80 }
```

```

81 \DeclareOptionX{all}[tight]{\KV@savetrees@all{-#1}}


\KV@savetrees@subtle The subtle package option turns off all of savetrees's space-saving tricks except those that preserve document layout: margins, indentation, font heights, vertical spacing surrounding titles, lists, displays, etc.
82 \define@key{savetrees}{subtle}{%
83   \setkeys{savetrees}{%
84     all=normal,
85     paragraphs=tight,
86     floats=tight,
87     mathspacing=tight,
88     wordspacing=tight,
89     tracking=tight
90   }%
91 }
92 \DeclareOptionX{subtle}{\KV@savetrees@subtle}

\KV@savetrees@moderate The moderate package option includes everything covered by subtle but additionally makes the font narrower, removes vertical white space around lists and displays, cuts back on indentation, reduces interline spacing, and drops NOTE fields from the bibliography,
93 \define@key{savetrees}{moderate}{%
94   \setkeys{savetrees}{%
95     subtle=yes,
96     charwidths=tight,
97     mathdisplays=tight,
98     lists=tight,
99     indent=tight,
100    leading=tight,
101    bibnotes=tight
102  }%
103 }
104 \DeclareOptionX{moderate}{\KV@savetrees@moderate}

\KV@savetrees@extreme The extreme package option is simply a synonym for all=tight.
105 \DeclareOptionX{extreme}{%
106   \setkeys{savetrees}{all=tight}%
107 }

4.2.3 Parameter tuning

While savetrees tries to use reasonable defaults for the numerical values used by its space-saving techniques, many of these parameters can be modified conveniently via package options:
The marginwidth option specifies the width of the page margins when margins=tight.
108 \DeclareOptionX{marginwidth}{\gdef\st@margin@width{#1}}

```

The `parindent` option specifies the paragraph indent when `indent=tight`.

```
109 \DeclareOptionX{parindent}{\gdef\st@parindent{\#1}}
```

The `leadingfraction` option specifies the fraction by which to multiply the line spacing when `leading=tight`.

```
110 \DeclareOptionX{leadingfraction}{\gdef\st@baselinestretch{\#1}}
```

The `charwidthfraction` option specifies the fraction by which to multiply character-glyph widths when `charwidths=tight`. Because the `microtype` package takes a per mill width contraction we have to do some arithmetic to produce `\st@char@shrink`.

```
111 \DeclareOptionX{charwidthfraction}{%
112   \tempdima=#1pt
113   \multiply\tempdima by -1000
114   \advance\tempdima by 1000pt
115   \divide\tempdima by 65536
116   \tempcpta=\tempdima
117   \xdef\st@char@shrink{\the\tempcpta}%
118 }
```

The `trackingfraction` option specifies the fraction by which to multiply character spacing when `tracking=tight`. Because the `microtype` package takes a per mill width expansion we have to do some arithmetic to produce `\st@cspace@shrink`.

```
119 \DeclareOptionX{trackingfraction}{%
120   \tempdima=#1pt
121   \advance\tempdima by -1pt
122   \multiply\tempdima by 1000
123   \divide\tempdima by 65536
124   \tempcpta=\tempdima
125   \xdef\st@cspace@shrink{\the\tempcpta}%
126 }
```

The `wordspacingfraction` option specifies the fraction by which to multiply inter-word spacing when `wordspacing=tight`.

```
127 \DeclareOptionX{wordspacingfraction}{\gdef\st@wspace@factor{\#1}}
```

4.2.4 Obsolete options

`savetrees` used to name all of its options `normal<something>`. None of these took arguments so the only usage model was for `savetrees` to turn all space-saving techniques on by default and let the user selectively disable them. Starting with version 2.0, `savetrees` package options take the form `<something>[=tight]` or `<something>=normal`, which gives a document author the ability to enable or disable options as desired. To move authors to the new set of parameters, we define all of the old options as error-generating calls.

`\st@mark@as@obsolete` We define a helper macro that processes the given option by issuing an error message that instructs the document author to use a different option instead.

```
128 \newcommand*{\st@mark@as@obsolete}[2]{%
129   \define@key{savetrees}{#1}[tight]{%
```

```

130      \PackageError{savetrees}{Package option '#1' is no longer supported}{%
131          Rather than '#1', please specify '#2=normal'.\MessageBreak
132          Instead of enabling all features by default and letting the\MessageBreak
133          user selectively disable them, savetrees now provides the\MessageBreak
134          ability to turn features on or off as desired, including all\MessageBreak
135          features en masse.}%

```

Out of the goodness of our heart, we automatically convert the obsolete option to a new option and evaluate that.

```

136      \csname @st@tight@#2false\endcsname
137  }%
138  \DeclareOptionX{#1}[tight]{\csname KV@savetrees@#1\endcsname{##1}}%
139 }

```

We now invoke `\st@mark@as@obsolete` once for each obsolete `savetrees` option,

```

140 \st@mark@as@obsolete{normalsections}{sections}
141 \st@mark@as@obsolete{normalmargins}{margins}
142 \st@mark@as@obsolete{normallists}{lists}
143 \st@mark@as@obsolete{normalfloats}{floats}
144 \st@mark@as@obsolete{normalindent}{indent}
145 \st@mark@as@obsolete{normaltitle}{title}
146 \st@mark@as@obsolete{normalleading}{leading}
147 \st@mark@as@obsolete{normallooseness}{paragraphs}
148 \st@mark@as@obsolete{normalcharwidths}{charwidths}
149 \st@mark@as@obsolete{normalbib}{bibliography}
150 \st@mark@as@obsolete{normalbibnotes}{bibnotes}

```

At long last, we can process all of the options defined in Section Section 4.2.

```
151 \ProcessOptionsX\relax
```

4.3 Section titles

The L^AT_EX default is to typeset section titles in a large font and with significant surrounding white space. We use the `titlesec` package to typeset section titles in the same font size as the body text and to leave only a single blank line above and below them.

```

152 \if@st@tight@sections
153   \st@RequirePackage[tiny,compact]{titlesec}
154 \fi

```

4.4 Page margins

The typesetting wisdom of the ages says that the human eye is most comfortable reading approximately 60 characters per line of text, and this is what L^AT_EX's default margins aim to achieve. Of course, narrower margins mean fewer pages, and that's what `savetrees` is striving for.

We use the `geometry` package to narrow our page margins unless the author wants to keep L^AT_EX's original ones. Note that we accept `geometry`'s default of zero space allocated to marginal notes.

```

155 \if@st@tight@margins
156   \st@RequirePackage[lmargin=\st@margin@width,
157                      rmargin=\st@margin@width,
158                      tmargin=\st@margin@width,
159                      bmargin=\st@margin@width,
160                      includefoot,
161                      footskip=2ex]{geometry}
162 \fi

```

4.5 List spacing

We try to save space in itemized lists, enumerated lists, and description lists by reducing indentation and by eliminating pre-list and inter-item spacing altogether.

```
163 \if@st@tight@lists
```

The `calc` package helps simplify our list redefinitions.

```
164 \st@RequirePackage{calc}
```

itemize Except where indicated, the following code was taken directly from L^AT_EX 2_&'s definition of the `itemize` environment, in `ltlists.dtx`:

```

165 \def\itemize{%
166   \ifnum \citemdepth > \thr@@\else
167     \advance\citemdepth\@ne
168     \edef\citemitem{\labelitem\romannumeral\the\citemdepth}%
169     \expandafter
170     \list
171       \csname\citemitem\endcsname
172       {\def\makelabel##1{\hss\llap{##1}}}}

```

The following lines have been modified from the original.

```

173   \settowidth{\leftmargin}{\csname\citemitem\endcsname}%
174   \addtolength{\leftmargin}{\labelsep * \citemdepth}%
175   \setlength{\partopsep}{0pt plus 4pt}%
176   \setlength{\topsep}{0pt plus 4pt}%
177   \setlength{\itemsep}{0pt}%
178   \setlength{\parsep}{0pt}%
179   \setlength{\listparindent}{\st@parindent}%

```

That's it for the modifications. We can now finish up the redefinition of `itemize`.

```

180   }%
181 \fi}

```

enumerate Except where indicated, the following code was taken directly from L^AT_EX 2_&'s definition of the `enumerate` environment, in `ltlists.dtx`:

```

182 \def\enumerate{%
183   \ifnum \cenumdepth > \thr@@\else
184     \advance\cenumdepth\@ne
185     \edef\cenumctr{\enum\romannumeral\the\cenumdepth}%
186     \expandafter
187     \list

```

```

188      \csname label\@enumctr\endcsname
189      {\usecounter{\enumctr}\def\makelabel##1{\hss\llap{##1}}%

```

The following lines have been modified from the original.

```

190      \settowidth{\leftmargin}{\csname label\@enumctr\endcsname}%
191      \addtolength{\leftmargin}{\labelsep * \enumdepth}%
192      \setlength{\partopsep}{0pt plus 4pt}%
193      \setlength{\topsep}{0pt plus 4pt}%
194      \setlength{\itemsep}{0pt}%
195      \setlength{\parsep}{0pt}%
196      \setlength{\listparindent}{\listparindent}%

```

That's it for the modifications. We can now finish up the redefinition of `enumerate`.

```

197      }
198  \fi}

```

description The `description` environment is a bit simpler than the `itemize` and `enumerate` environments; it's a direct application of `list`. All we need to do is reduce the left margin from the `list` default of 2em to a slightly denser 1pc.

```

199  \renewenvironment{description}{%
200      \begin{list}{}{\setlength{\leftmargin}{1pc}%
201          \setlength{\itemindent}{-\leftmargin}%
202          \setlength{\partopsep}{0pt plus 4pt}%
203          \setlength{\topsep}{0pt plus 4pt}%
204          \setlength{\itemsep}{0pt}%
205          \setlength{\parsep}{0pt}%
206          \setlength{\labelwidth}{0pt}%
207          \setlength{\listparindent}{\listparindent}%
208          \let\makelabel\descriptionlabel}%
209      }{%
210          \end{list}
211      }
212 \fi

```

4.6 Float placement

`\topfraction` L^AT_EX normally doesn't try very hard to pack floats onto a page. The following parameter changes attempt to reduce the number of float pages (and hence, total pages).

```

\floatautopagefraction 213 \if@st@tight@floats
\dbltopfraction 214     \renewcommand{\topfraction}{0.85}
\dblfloatpagefraction 215     \renewcommand{\bottomfraction}{0.85}
216     \renewcommand{\textfraction}{0.1}
217     \renewcommand{\floatpagefraction}{0.85}
218     \renewcommand{\dbltopfraction}{0.85}
219     \renewcommand{\dblfloatpagefraction}{.85}
220     \setcounter{topnumber}{25}
221     \setcounter{bottomnumber}{25}
222     \setcounter{totalnumber}{25}
223     \setcounter{dbltopnumber}{25}

```

```
224 \fi
```

4.7 Paragraph indentation

L^AT_EX normally provides approximately 1.5 em of indentation at the start of each paragraph. We can save a little space by slightly reducing the indentation amount.

```
225 \if@st@tight@indent
226   \setlength{\parindent}{\st@parindent}
227 \fi
```

4.8 Document title formatting

By default, the document title is typeset in the `\LARGE` font size, and the author list and date are typeset `\large`. We redefine `\@maketitle` to typeset the title `\large` and everything else in the body font. In addition, we remove the extra white space above the title and lessen the white space below the title.

```
228 \if@st@tight@title
```

`\@maketitle` The following was taken largely from `classes.dtx`, but modified as specified above.

```
229 \def\@maketitle{%
230   \newpage
231   \null
232   \begin{center}%
233     \let \footnote \thanks
234     {\large \textbf{\@title}\par}
235     \vskip 0.5\baselineskip
236     \begin{tabular}[t]{c}%
237       \author
238     \end{tabular}\par
239     \vskip 0.5\baselineskip
240     \date
241   \end{center}%
242   \par
243   \vskip \baselineskip
244 }
245 \fi
```

4.9 Interline spacing

`\baselinestretch` A document's page count can be reduced quite significantly by reducing the amount of white space between successive lines of text so that's exactly what we do below.

```
246 \if@st@tight@leading
247   \renewcommand{\baselinestretch}{\st@baselinestretch}
248 \fi
```

4.10 Paragraph looseness

Some paragraphs end with a lone word on the last line. If we can discourage such typesetting we can gain an extra line. The underlying mechanism we use is TEX's `\looseness` primitive, which encourages TEX to expand the current paragraph by a given number of lines. However, `\looseness` can be set to a negative number, which encourages TEX to shrink the current paragraph by a given number of lines. For this technique to work, the paragraph must be relatively long so TEX has enough shrinkable white space to work with.

Unfortunately, `\looseness` applies only to the current paragraph. We therefore use `\everypar` to inject `\looseness=-1` into every paragraph. However, the approach is not quite so simple as the `\looseness=-1` is not injected into list environments. We therefore use some tricky code due to Donald Arseneau to make the effect of `\looseness=-1` as global as possible:

```
249 \if@st@tight@paragraphs
250   \let\markeverypar\everypar
251   \newtoks\everypar
252   \everypar\markeverypar
253   \markeverypar{\the\everypar\looseness=-1\relax}
254 \fi
```

Even when `\everypar` is used in the ordinary fashion it is likely to conflict with various LATEX packages. Because the preceding code is a particularly tricky redefinition of `\everypar` it's likely that many documents will need to disable paragraph looseness by providing the `paragraphs=normal` option to `savetrees`.

4.11 Font width

The `microtype` package provides LATEX support for the font-expansion feature supported by `pdfTEX` and `luaTEX`. Font expansion is intended to improve text “color”—the even balance between ink and absence of ink on a page—by subtly expanding or narrowing character widths instead of by adding or removing white space. `savetrees` hijacks this feature as a space-saving mechanisms by specifying a maximum expansion of 0% of a character’s natural width but a maximum contraction of greater than 0%.

```
255 \if@st@tight@charwidths
256   \st@RequirePackage[stretch=0,shrink=\st@char@shrink]{microtype}
257 \fi
```

4.12 Inter-character spacing

The `microtype` package provides LATEX support for `pdfTEX`’s tracking feature. Rather than using tracking with a light touch and just in certain contexts (e.g., small caps), we instruct `microtype` to track somewhat aggressively, shaving off a few percent of an em width between *every* pair of characters.

```
258 \if@st@tight@tracking
259   \st@RequirePackage[letterspace=\st@cspace@shrink,tracking=all]{microtype}
```

```
260 \fi
```

4.13 Inter-word spacing

Any font used by TeX is required to have at least seven `\fontdimen` parameters. `\fontdimen2` represents the base inter-word spacing. (`\fontdimen3` and `\fontdimen4` represent, respectively, the amount by which inter-word spacing can stretch or shrink; `savetrees` does not currently alter those.) Here, we hook into L^AT_EX 2 _{ε} 's font-loading mechanism. Whenever a new font is loaded, we specify that the inter-word spacing for that font should be reduced.

```
261 \if@st@tight@wordspacing
262   \g@addto@macro\define@newfont{%
263     \fontdimen2\font@name=\st@wspace@factor\fontdimen2\font@name
264   }%
```

We also reduce the inter-word spacing for whatever font is currently loaded.

```
265 \fontdimen2\font@name=\st@wspace@factor\fontdimen2\font@name
266 \fi
```

4.14 Bibliography formatting

There are two ways we save space when typesetting bibliographies. First, we omit blank lines between entries. And second, we typeset the entire bibliography—excluding the section title—with `\small`.

```
267 \if@st@tight@bibliography
```

`thebibliography` The following was taken largely from `classes.dtx`; see that file for additional documentation. `savetrees`'s modifications are indicated below.

```
268 \renewenvironment{thebibliography}[1]{%
```

In the `article` document class, a bibliography is a *section* called “`\refname`”. In the `report` and `book` document classes, a bibliography is a *chapter* called “`\bibname`”. In `classes.dtx`, the correct code is extracted by DocStrip. Here, we have to use an `\ifx` primitive to select the appropriate title and formatting.

```
269 \ifundefined{chapter}{%
270   \section*\{\refname
271   \@mkboth{\MakeUppercase\refname}{\MakeUppercase\refname}}%
272 }{%
273   \chapter*\{\bibname
274   \@mkboth{\MakeUppercase\bibname}{\MakeUppercase\bibname}}%
275 }
```

Back to the original code...

```
276 \list{@biblabel{@arabic@c@enumiv}}%
277   {\settowidth\labelwidth{@biblabel{#1}}%
278   \leftmargin\labelwidth
279   \advance\leftmargin\labelsep
```

We eliminate the space between paragraphs, and we set the space between items to only 1 pt. We could have set this to 0 pt., but the extra space helps keep the citation numbers' brackets from getting too close to each other, vertically.

```
280      \setlength{\parsep}{0pt}%
281      \setlength{\itemsep}{1pt}%
```

Back to the original code...

```
282      \openbib@code
283      \usecounter{enumiv}%
284      \let\p@enumiv\empty
285      \renewcommand{\theenumiv{\@arabic\c@enumiv}}%
```

Although we kept the section title in its original size, we typeset the rest of the bibliography a little bit smaller.

```
286      \small
```

We finish up using the original code.

```
287      \sloppy
288      \clubpenalty4000
289      \clubpenalty \clubpenalty
290      \widowpenalty4000%
291      \sfcode`\. \@m
292  }{%
293      \def\@noitemerr
294      {\@latex@warning{Empty `thebibliography' environment}}%
295      \endlist
296  }
297 \fi
```

4.15 Bibliographic notes

`\savetreesbibnote` The bibliographies output by the `savetrees.bst` BIB^TEX style (presented in Section 5) surround all NOTE fields with a call to the `\savetreesbibnote` macro. As a result, this macro must be defined for `savetrees.bst` to work. By default, `\savetreesbibnote` is defined to do nothing. However, setting `bibnotes=normal` indicates that `\savetreesbibnote` should instead output its argument as is.

```
298 \if@st@tight@bibnotes
```

To suppress a NOTE field, we also have to gobble the period following the note. Otherwise, the bibliography will show two periods surrounding an empty note.

```
299  \newcommand{\savetreesbibnote}[1]{\gobble}
300 \else
301  \newcommand{\savetreesbibnote}[1]{#1}
302 \fi
```

4.16 Mathematical expressions

By default, mathematical expressions contain substantial white space around operators, relations, etc. Here, we shave approximately three math units off each

of `\thinmuskip`, `\medmuskip`, and `\thickmuskip`. This needs to happen after the `\begin{document}` so that the new values don't get overwritten.

```
303 \if@st@tight@mathspacing
304   \AtBeginDocument{%
305     \thinmuskip=0mu plus 3mu
306     \medmuskip=1mu plus 4mu
307     \thickmuskip=2mu plus 5mu
308   }
309 \fi
```

4.17 Displayed mathematics

Displayed mathematical expressions are normally offset from the surrounding text with vertical white space. Here, we set the amount of vertical white space to zero. This needs to happen after the `\begin{document}` so that the new values don't get overwritten.

```
310 \if@st@tight@mathdisplays
311   \AtBeginDocument{%
312     \abovedisplayskip=0pt plus 3pt
313     \belowdisplayskip=0pt plus 3pt
314     \abovedisplayshortskip=0pt plus 3pt
315     \belowdisplayshortskip=0pt plus 3pt
316   }
317 \fi
318 </package>
```

5 Implementation of `savetrees.bst`

In addition to a L^AT_EX 2 _{ε} style, the `savetrees` package also includes a BIBT_EX style, `savetrees.bst`. `savetrees.bst` was generated with the help of Patrick W. Daly's `custom-bib` package. The following options were provided to `merlin.mbs`:

```
lang, nm-init, ed-au, nmdash, nmlm, x2, m2, isbn,
issn, pp, ed, abr, ednx, xedn, jabr, nfss
```

Because `savetrees.bst` is a generated file—and can be regenerated using the options listed above—it is unnecessary to list the complete source code in this document. Rather, only the hand-modified parts are presented below.

```
319 <*bibstyle>
```

```
:
(443 lines of code omitted)
```

```
:
```

`format.note` is the first of two functions modified by hand. The modification involves placing the entire note field within `\savetreesbibnote{...}`. This enables `savetrees.sty` to selectively define `\savetreesbibnote` to either output its argument as is or discard it (and the subsequent period). See Section 4.15 for `savetrees.sty`'s definition of `\savetreesbibnote`.

```

320 FUNCTION {format.note}
321 {
322   note empty$
323   { ""
324   { "\savetreesbibnote{"
325     note #1 #1 substring$
326     duplicate$ "{" =
327     'skip$
328     { output.state mid.sentence =
329       { "l" }
330       { "u" }
331     if$
332     change.case$
333   }
334   if$
335   note #2 global.max$ substring$ *
336   "}" * *
337 }
338 if$
339 }

:
(914 lines of code omitted)
:

```

`begin.bib` is the second of two functions modified by hand. The modification is to have the function write some additional code to the `.bb1` file to define `\savetreesbibnote` as the identity function if that macro is not already defined.

```

340 FUNCTION {begin.bib}
341 { preamble$ empty$
342   'skip$
343   { preamble$ write$ newline$ }
344   if$
345   "\begin{thebibliography}{"
346   longest.label * "}" *
347   write$ newline$
348   "\providecommand*\{\selectlanguage}[1]{\relax}%""
349   "\providecommand*\{\savetreesbibnote}[1]{#1}%""
350   write$ newline$
351 }

:

```

```
(13 lines of code omitted)
:
352 </bibstyle>
```

A Average character widths of common fonts

Question: What's the narrowest font?

Answer: It depends upon how you measure. Table 5 shows, for various 10 pt. fonts, the width in points of 1000 lowercase letters with relative frequencies chosen to match “typical” English text. There are 130 e’s, 93 t’s, 78 n’s, 77 r’s, and so forth down the frequency distribution. According to the table, Times is statistically likely to be the best typeface for maximizing the amount of text on the page. However, Times may not be the narrowest for *your* document; you’ll have to experiment and see.

Typeface	Package	Avg. width (pt.)
Times	<code>mathptmx</code>	4.26901
Computer Modern	(default)	4.62675
Charter	<code>charter</code>	4.6762
Helvetica	<code>helvet</code>	4.70108
Palatino	<code>mathpazo</code>	4.79744
Utopia	<code>utopia</code>	4.92876
New Century Schoolbook	<code>newcent</code>	4.98047
Avant Garde	<code>avant</code>	5.22113
Bookman	<code>bookman</code>	5.23056
Courier	<code>courier</code>	6

Table 5: Common fonts sorted by increasing width

Although `savetrees` does not automatically change the document font it does specify that character glyphs may be typeset narrower than normal (cf. the `charwidth` option). Note, however, that `savetrees` unfortunately has no control over precisely which lines of text are typeset with narrow characters. This narrowing technique works only with pdfLATEX, so that program should be used if possible to maximize the space-saving achievable with `savetrees`.

B Gallery of space-saving techniques

Figure 1 through Figure 7 on pages 24–27 provide examples of some of the ways that `savetrees` saves space when typesetting text. Each figure showcases a single space-saving technique in isolation. The default parameters are used for each technique. Table 4 on page 5 documents the package options that can be used to

refine these parameters either to save more space or to make the typesetting less offensive.

Figure 1 shows how setting `lists=tight` saves space by reducing the white space above, below, and within list environments (in this case, the `itemize` environment). Figure 2 shows how setting `mathspacing=tight` saves space by typesetting mathematical expressions denser. Figure 3 shows how setting `mathdisplays=tight` removes the space around mathematical displays (e.g., `\[...]` or `\begin{equation}...\end{equation}`). Figure 4 shows how setting `wordspacing=tight` saves space by typesetting words closer together. Figure 5 shows how setting `tracking=tight` saves space by typesetting the characters within a word closer together. Figure 6 shows how setting `charwidths=tight` saves space by narrowing the individual character glyphs without affecting the font's point size (height) or amount of white space. Finally, Figure 7 shows how setting `leading=tight` saves space by removing white space between adjacent lines of text. Again, these techniques are shown with their default parameters, which can be adjusted if desired.

While Figure 1 through Figure 7 each illustrate a single space-saving technique, Figure 8 on page 28 demonstrates that when multiple techniques are used in combination, the benefits are essentially additive.

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

- curabitur
- tellus
- nulla

Quisque feugiat lacinia mauris ut tincidunt.

(a) `lists=normal`

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

- curabitur
- tellus
- nulla

Quisque feugiat lacinia mauris ut tincidunt.

(b) `lists=tight`

Figure 1: Effect of the `lists` option

Lorem ipsum dolor sit amet, consectetur adipiscing elit $\mathcal{H} = T + V$ quisque feugiat $T = \frac{p^2}{2m}$ lacinia mauris $V = V(q)$ ut tincidunt. Etiam ligula dolor $\mathcal{H} = \sum_i \dot{q}_i \frac{\partial \mathcal{L}}{\partial \dot{q}_i} - \mathcal{L} = \sum_i \dot{q}_i p_i - \mathcal{L}$ eget nulla.

(a) `mathspacing=normal`

Lorem ipsum dolor sit amet, consectetur adipiscing elit $\mathcal{H} = T + V$ quisque feugiat $T = \frac{p^2}{2m}$ lacinia mauris $V = V(q)$ ut tincidunt. Etiam ligula dolor $\mathcal{H} = \sum_i \dot{q}_i \frac{\partial \mathcal{L}}{\partial \dot{q}_i} - \mathcal{L} = \sum_i \dot{q}_i p_i - \mathcal{L}$ eget nulla.

(b) `mathspacing=tight`

Figure 2: Effect of the `mathspacing` option

<p> Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus</p> $d\mathcal{L} = \sum_i \left(\frac{\partial \mathcal{L}}{\partial q_i} dq_i + p_i d\dot{q}_i \right) + \frac{\partial \mathcal{L}}{\partial t} dt$ <p> tempus dolor ac dignissim. Etiam ligula dolor, varius at rutrum.</p>	<p> Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus</p> $d\mathcal{L} = \sum_i \left(\frac{\partial \mathcal{L}}{\partial q_i} dq_i + p_i d\dot{q}_i \right) + \frac{\partial \mathcal{L}}{\partial t} dt$ <p> tempus dolor ac dignissim. Etiam ligula dolor, varius at rutrum.</p>
---	---

(a) `mathdisplays=normal`(b) `mathdisplays=tight`Figure 3: Effect of the `mathdisplays` option

Change History

v1.0		
General: Initial version	1	
v1.1		
thebibliography : Modified to test for <code>\chapter</code> , not <code>\bibname</code> . . .	19	
v1.2		
General: Added support for reducing paragraph looseness	18	
Made the top margin consistent with the other margins and allocated space for the footer . . .	14	
thebibliography : Modified to use the more robust <code>\@ifundefined</code> macro to test for the existence of <code>\chapter</code>	19	
v1.2a		
General: Appended <code>\relax</code> to <code>\looseness=-1</code> to avoid discarding any leading digits appearing in a paragraph	18	
v1.3		
General: Added support for narrowing font widths	18	
v2.0		
General: Added package options for altering various formatting parameters	12	
Added support for reducing inter-character spacing	18	
		Added support for reducing inter-word spacing
		19
		Made <code>savetrees.bib</code> work independently of <code>savetrees.sty</code> by having it define <code>\savetreesbibnote</code> if not already defined
		22
		Removed the awkward-to-use <code>makethin</code> script now that the <code>microtype</code> package can shrink character widths more automatically
		7
v2.1		
		General: Added support for removing vertical space around displayed mathematics
		21
		Added support for squeezing space out of mathematical expressions
		21
		Introduced the <code>subtle</code> , <code>moderate</code> , and <code>extreme</code> package options .
		12
		description : Reduced vertical space before and within the list
		16
		enumerate : Reduced vertical space before the list
		16
		itemize : Reduced vertical space before the list
		15

Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitæ lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mol- lis, diam ante mollis purus, vel eu- ismod neque velit vitæ augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ul- trices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed me- tus.

(a) wordspacing=normal

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitae lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitae augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Aenean odio turpis, laoreet non vulputate eu, fermentum sed metus.

(b) wordspacing=tight

Figure 4: Effect of the `wordspacing` option

Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitæ lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mol- lis, diam ante mollis purus, vel eu- ismod neque velit vitæ augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ul- trices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed me- tus.

(a) tracking=normal

Lore ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitae lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mol- lis purus, vel euismod neque velit vitae augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed me- tus.

(b) tracking=tight

Figure 5: Effect of the **tracking** option

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitæ lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitæ augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed metus.

(a) `charwidths=normal`

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitae lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitae augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Aenean odio turpis, laoreet non vulputate eu, fermentum sed metus.

(b) `charwidths=tight`

Figure 6: Effect of the `charwidths` option

Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitæ lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mol- lis, diam ante mollis purus, vel eu- ismod neque velit vitæ augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ul- trices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed me- tus.

(a) leading=normal

Lore ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitæ lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitæ augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed meatus.

(b) `leading=tight`

Figure 7: Effect of the **leading** option

<p> Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitæ lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitæ augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed metus.</p>	<p> Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam dapibus tempus dolor ac dignissim. Nam et ante eu velit interdum bibendum. Etiam ligula dolor, varius at rutrum at, porta vitæ lacus. Cras et elit ut lectus aliquet scelerisque ut sed arcu. Morbi eleifend iaculis augue non tristique. Præsent cursus iaculis diam et tristique. Curabitur facilisis, eros in scelerisque mollis, diam ante mollis purus, vel euismod neque velit vitæ augue. In sit amet nulla odio, at ultrices dui. Quisque venenatis velit eget nulla ultrices rutrum. In hac habitasse platea dictumst. Ænean odio turpis, laoreet non vulputate eu, fermentum sed metus.</p>
--	--

(a) `all=normal`(b) `wordspacing=tight, tracking=tight, charwidths=tight, leading=tight`

Figure 8: Combined effect of using multiple options

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
<code>\@cons</code>	<u>12</u> <code>\@st@tight@liststrue</code> <u>33</u> , 50
<code>\@elt</code>	<u>15</u> , 17 <code>\@st@tight@marginsfalse</code> <u>32</u> , 65
<code>\@maketitle</code>	<u>229</u> <code>\@st@tight@marginstrue</code> <u>32</u> , 49
<code>\@st@tight@bibliographyfalse</code> .	<u>42</u> , 75 <code>\@st@tight@mathdisplaysfalse</code> . <u>45</u> , 78
<code>\@st@tight@bibliographytrue</code> .	<u>42</u> , 59 <code>\@st@tight@mathdisplaystrue</code> . <u>45</u> , 62
<code>\@st@tight@bibnotesfalse</code>	<u>42</u> , 59 <code>\@st@tight@mathspacingfalse</code> . <u>44</u> , 77
<code>\@st@tight@bibnotestrue</code>	<u>43</u> , 76 <code>\@st@tight@mathspacingtrue</code> . <u>44</u> , 61
<code>\@st@tight@charwidthsfals</code> e	<u>43</u> , 60 <code>\@st@tight@paragraphsfals</code> e <u>38</u> , 71
<code>\@st@tight@charwidthstrue</code>	<u>39</u> , 72 <code>\@st@tight@paragraphstrue</code> <u>38</u> , 55
<code>\@st@tight@floatsfals</code> e	<u>39</u> , 56 <code>\@st@tight@sectionsfalse</code> <u>31</u> , 64
<code>\@st@tight@floatstrue</code>	<u>34</u> , 67 <code>\@st@tight@sectionstrue</code> <u>31</u> , 48
<code>\@st@tight@indentfalse</code>	<u>34</u> , 51 <code>\@st@tight@titlefalse</code> <u>36</u> , 69
<code>\@st@tight@indenttrue</code>	<u>35</u> , 68 <code>\@st@tight@titltrue</code> <u>36</u> , 53
<code>\@st@tight@leadingfalse</code>	<u>35</u> , 52 <code>\@st@tight@trackingfalse</code> <u>40</u> , 73
<code>\@st@tight@leadingtrue</code>	<u>37</u> , 70 <code>\@st@tight@trackingtrue</code> <u>40</u> , 57
<code>\@st@tight@listsfalse</code>	<u>33</u> , 66 <code>\@st@tight@wordspacingfalse</code> . . <u>41</u> , 74
	<code>\@st@tight@wordspacingtrue</code> . . <u>41</u> , 58

	A	
\abovedisplayshortskip	314
\abovedisplayskip	312
all (package option)	81
\AtBeginDocument	304, 311
\AtEndOfPackage	14
	B	
\baselinestretch	246
\belowdisplayshortskip	315
\belowdisplayskip	313
bibliography (package option)	42
bibnotes (package option)	43
\bottomfraction	213
	C	
charwidthfraction (package option)	..	118
charwidths (package option)	39
	D	
\dblfloatpagefraction	213
\dbltopfraction	213
\DeclareOptionX	29, 81, 92, 104, 105, 108–111, 119, 127, 138
\define@choicekey	22, 46
\define@key	82, 93, 129
\define@newfont	262
description (environment)	199
	E	
\enumerate	182
enumerate (environment)	182
environments:		
description	199
enumerate	182
itemize	165
thebibliography	268
\everypar	250–253
extreme (package option)	107
	F	
\floatpagefraction	213
floats (package option)	34
\font@name	263, 265
\fontdimen	263, 265
	I	
\if@st@tight@bibliography	...	42, 267
\if@st@tight@bibnotes	43, 298
\if@st@tight@charwidths	39, 255
	K	
\KV@savetrees@all	46
\KV@savetrees@bibliography	42
\KV@savetrees@bibnotes	43
\KV@savetrees@charwidths	39
\KV@savetrees@extreme	105
\KV@savetrees@floats	34
\KV@savetrees@indent	35
\KV@savetrees@leading	37
\KV@savetrees@lists	33
\KV@savetrees@margins	32
\KV@savetrees@mathdisplays	45
\KV@savetrees@mathspacing	44
\KV@savetrees@moderate	93
\KV@savetrees@paragraphs	38
\KV@savetrees@sections	31
\KV@savetrees@subtle	82
\KV@savetrees@title	36
\KV@savetrees@tracking	40
\KV@savetrees@wordspacing	41
	L	
\labelsep	174, 191, 279
leading (package option)	37
leadingfraction (package option)	110
\leftmargin	173, 174, 190, 191, 200, 201, 278, 279
\listparindent	179, 196, 207
lists (package option)	33
\looseness	253
	M	
\makelabel	172, 189, 208

margins (package option)	32	\PassOptionsToPackage	11
marginwidth (package option)	108	\ProcessOptionsX	151
\markeverypar	250, 252, 253	\providecommand	347, 349
mathdisplays (package option)	45		
mathspacing (package option)	44		
\medmuskip	306	\RequirePackage	8, 15
moderate (package option)	104		
			S
		\savetreesbibnote	298, 324, 349
		sections (package option)	31
		\selectlanguage	347
P		\setkeys	83, 94, 106
package options:		\st@arg	19, 46
all	81	\st@arg@num	19, 46
bibliography	42	\st@baselinestretch	4, 110, 247
bibnotes	43	\st@char@shrink	5, 117, 256
charwidthfraction	118	\st@cspace@shrink	6, 125, 259
charwidths	39	\st@define@option	19, 31–45
extreme	107	\st@margin@width	2, 108, 156–159
floats	34	\st@mark@as@obsolete	128, 140–150
indent	35	\st@more@packages	9
leading	37	\st@parindent	3, 109, 179, 196, 207, 226
leadingfraction	110	\st@RequirePackage	
lists	33		
margins	32		
marginwidth	108		
mathdisplays	45		
mathspacing	44		
moderate	104		
paragraphs	38		
parindent	109		
sections	31		
subtle	92		
title	36		
tracking	40		
trackingfraction	126		
wordspacing	41		
wordspacingfraction	127		
\PackageError	130		
paragraphs (package option)	38		
\parindent	226		
parindent (package option)	109		
\parsep	178, 195, 205, 280		
\partopsep	175, 192, 202		
			T
		\textfraction	213
		thebibliography (environment) . . .	268
		\thickmuskip	307
		\thinmuskip	305
		title (package option)	36
		\topfraction	213
		\topsep	176, 193, 203
		tracking (package option)	40
		trackingfraction (package option) . . .	126
			W
		wordspacing (package option)	41
		wordspacingfraction (package option) . .	127