

User's Guide to SUFtesi

A document class for typesetting theses, books and articles

v1.9b – 2014/02/16

Ivan Valbusa

Dipartimento di Filosofia, Pedagogia e Psicologia

Università degli Studi di Verona

ivan dot valbusa at univr dot it

Abstract

The standard document classes allow you to typeset beautiful documents but their layout is quite far from the stylistic requests of some humanists (mainly Italian). The *suftesi* class provides a set of “humanistic” page layouts, title styles and heading styles to typeset theses, books and articles. The styles are very simple and sober and also have the aim of finding an aesthetic harmony in its formal simplicity. They are largely inspired by some interesting readings, particularly *The Elements of Typographic Style* by R. Bringhurst, *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie* by J. Tschichold and *First Principles of Typography* by S. Morison.

Contents

1 Use	2	6.7	Text elements	19
		6.7.1	Lists	19
2 Class features	3	6.7.2	Block quotations	20
2.1 Page layouts	3	6.7.3	Footnotes	20
2.2 Font	3	6.7.4	Captions	21
2.3 Frontispiece	4	6.7.5	Marginal notes	21
		6.7.6	Table of contents	21
3 Options	5	6.8	Fonts	22
3.1 Layout	5	6.8.1	Roman fonts	22
3.2 Fonts	5	6.8.2	Greek fonts	22
3.3 Titles	5	6.9	Other options	22
3.4 Headings	6	6.9.1	\parindent	22
3.5 Notes, lists, quotations	7	6.9.2	Part page	22
3.6 Other options	7	6.9.3	Crop marks	22
3.7 Pre-defined styles	8	6.9.4	Draftdate	22
		6.9.5	View mode	23
4 New commands	9	6.9.6	Titlepage	23
4.1 Printing the colophon	9	6.9.7	Pre-defined styles	23
4.2 Breaking titles	10	6.10	Basic packages	28
4.3 Other commands	10	6.11	Greek fonts	28
5 The collection document structure	11	6.12	Page layout	29
5.1 Options	11	6.13	Section titles	29
5.2 Commands	12	6.14	Title page	35
		6.15	The collection document structure	38
References	12	6.16	Frontispiece	40
		6.17	Appendix	41
6 The Code	13	6.18	Headings	42
6.1 Document structure	14	6.19	Text elements	44
6.2 Page layout	14	6.19.1	Block Quotations	44
6.3 Sections style	15	6.19.2	Marginal notes	44
6.4 Sections font	17	6.19.3	Abstract	45
6.5 Section numbers	17	6.19.4	Colophon	46
6.5.1 Part number style	17	6.20	Toc, lof, lot	47
6.5.2 Chapter number	18	6.20.1	'tocpageleft' toc	48
6.5.3 Section number	18	6.20.2	Default toc	50
6.6 Headers	19	6.21	New commands	53
6.6.1 Header style	19	6.22	Backward compatibility	54
6.6.2 Header font	19	6.23	Final settings	54

Copyright notice

Copyright © 2009–2014 Ivan Valbusa. This package is author-maintained. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c.¹ This software is provided "as is", without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

In addition to the terms of this license the author requires an attribution notice (see section 4) like the following one:

This work has been typeset with \LaTeX , using the `suftesi` class by Ivan Valbusa.

The most essence of this class is the set of styles it provides. For this reason **DO NOT MODIFY THE STYLES OF THIS CLASS WITH PACKAGES AND/OR COMMANDS WHICH CHANGE THE LAYOUT OF THE DOCUMENT. IF YOU DO NOT LIKE THESE STYLES, USE ANOTHER CLASS.** If you use `suftesi` in a document typeset with another class (for example book), remember to clean up the preamble from all the layout redefinitions.

A brief history

The `suftesi` class was born as a result of the course *Introduzione a \LaTeX per le scienze umane* (*Introduction to \LaTeX for human sciences*) which I held at the Graduate School of Human Sciences and Philosophy (**Scienze Umane e Filosofia**) of Verona University (Italy) in June 2010.² Originally thought as a class to typeset theses, during these years it has developed many new features and styles. Finally it has become the referential class of the Joint Project *Formal Style for PhD Theses with \LaTeX* of the University of Verona (Italy).³

Acknowledgements

I would like to thank Professors Paola Di Nicola, Director of the Graduate School, and Ugo Savardi who suggested to propose the course precisely to that School; Gilberto D’Arduini, Matteo Lanza and Antonio Rinaldi, who installed \LaTeX on the computers used during the course; Catia Cordioli, for her help in the organization of the lessons; Corrado Ferreri, responsible of the E-Learning Center, who provided the \TeX Live 2009 DVDs. Special thanks to Professors Enrico Gregorio, the Italian guru of \TeX , for the \TeX xpert support and his priceless "magic formulas", and Tommaso Gordini for his valuable advice in choosing and improving the class features during these years. I would finally thank all the participants to the course who patiently resisted the four intensive lessons. This work is dedicated to them.

Feedback

If you have any questions, feedback or requests please email me. My mail address is at the top of this document. If you need specific features not already implemented, remember to attach the example files.

1 Use

The `suftesi` class is called as usual by

```
\documentclass[<options>]{suftesi}
```

You do not need to set the `a4paper` option as it is automatically loaded. All the options defined by the class are in the `<key>=<value>` format. In addition to these you can also use the options defined by the standard `book` class (on which `suftesi` is based) except those modifying the page dimensions (`a5paper`, `b5paper`, `legalpaper`, `executivepaper` and `landscape`), which are automatically disabled.

The document structure

With `suftesi` you can typeset book-style documents (i.e. with chapters) as well as article-style documents (i.e. without chapters). The kind of document is set by the `documentstructure` option which defaults to `book`. With the `collection` document structure you can also create collections of papers (see section 5).

¹<http://www.ctan.org/tex-archive/macros/latex/base/lppl.txt>.

²<http://www.sdsuf.univr.it> – Some informations can be found on
<http://profes.lettere.univr.it/valbusa/2010/06/01/introduzione-a-latex-per-le-scienze-umane/>

³<http://www.univr.it/main?ent=catdoc&id=3727&idDest=6&serv=127#1431>

```
\documentclass[documentstructure=book,<options>]{suftesi}
\documentclass[documentstructure=article,<options>]{suftesi}
\documentclass[documentstructure=collection,<options>]{suftesi}
```

Loaded packages

The class loads the following packages: `beramono`, `caption`, `color`, `enumitem`, `emptypage`, `extramarks`, `fancyhdr`, `fixltxhyph`, `fontenc`, `geometry`, `ifxetex`, `mathpazo`, `microtype`, `multicol`, `substitutefont`, `textcase`, `titlesec`, `titletoc`, `xkeyval`.

Use with X_ET_EX and L_UA_TE_X

The class can be used, of course, with the X_ET_EX and L_UA_TE_X engines. The only difference is that in this case the font options are turned off and the \TeX default font (Computer Modern) is loaded.

2 Class features

The `suftesi` class provides a large set of options to customize the style of page, titles, headings and other text elements (see section 3). The simplest way to get to know the class features is therefore to typeset one of the templates which you can find in the `/doc/latex/suftesi` folder in your \TeX distribution.

2.1 Page layouts

The class provides six page layouts which can be selected by the `pagelayout` option (see section 3.1). The standard layout (set by default) is aimed to typeset standard A₄ documents, while the other five layouts are particularly suitable to typeset compact books and articles (see table 1 for details).

Layout	Dimensions (mm)				Proportions			
	Text		Page		Margins		Text block	Page
	width	height	width	height	t/b	i/o		
<code>standard</code>	110	220	210	297	1 : 2	1 : 2	1 : 2	1 : $\sqrt{2}$
<code>compact</code>	110	165	160	240	2 : 3	2 : 3	2 : 3	2 : 3
<code>compactaureo</code>	118	191	160	240	2 : 3	2 : 3	5 : 8*	2 : 3
<code>supercompact</code>	100	150	140	210	2 : 3	2 : 3	2 : 3	2 : 3
<code>supercompactaureo</code>	108	175	140	210	1 : 1	1 : 1	5 : 8*	2 : 3
<code>periodical</code>	110	165	170	240	2 : 3	2 : 3	2 : 3	1 : $\sqrt{2}$
<code>periodicalaureo</code>	120	194	170	240	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$
<code>elements (pt)</code>	251	502	374	648	1 : 2	2 : 5	1 : 2	1 : $\sqrt{3}$

Table 1: The layouts of `suftesi`

* $5 : 8 \approx 1 : 1, 618$

2.2 Font

The default serif font for body text is Palatino designed by Hermann Zapf and loaded through the `mathpazo` package, but you can simply choose the standard Latin Modern through the `defaultfont` option (see section 3). The sans serif font is Iwona designed by Janusz M. Nowacki and the monospaced typeface is Bera Mono, opportunely scaled to match Palatino. This choice has been inspired by *L’arte di scrivere con \TeX* (Pantieri and Gordini 2012). The Greek text is Artemisia by the Greek Font Society (a) which is particularly suitable for Palatino, but with the `greekfont` option (see section 3) you can choose also Porson (b) or CB Greek (c).⁴

Tò γὰρ καλὸν ἐν μεγέθει καὶ τάξει
ἔστιν. Il bello infatti sta nella
grandezza e nell’ordinata
disposizione delle parti.

(a) Artemisia (Greek Font Society)

Tò γὰρ καλὸν ἐν μεγέθει καὶ τάξει
ἔστιν. Il bello infatti sta nella
grandezza e nell’ordinata
disposizione delle parti.

(b) Porson (Greek Font Society)

Tò γὰρ καλὸν ἐν μεγέθει καὶ τάξει
ἔστιν. Il bello infatti sta nella
grandezza e nell’ordinata
disposizione delle parti.

(c) CB Greek (Claudio Beccari)

You can use other fonts as well. In this case remember to load the `defaultfont=standard` class option which turns off the default font settings.

⁴ The first code for the Porson font has been written by Enrico Gregorio. Claudio Beccari successively added the code to improve the scale factor when using this greek font in combination with Palatino.

2.3 Frontispiece

The class has an original frontispiece (see figure 1) now directly available loading the `frontespizio` package with the `suftesi` option (see Gregorio 2009, version 1.4 or later):

```
\usepackage[suftesi]{frontespizio}
```

The `frontespizio` package produces a frontispiece in the standard Computer Modern typeface. If you prefer a consistent font remember to load the needed packages or commands in the `\Preambolo` command inside the `frontespizio` environment (see package documentation for details).




Figure 1: The frontispiece of `suftesi`

3 Options

3.1 Layout

<code>documentstructure=</code>	<code>book, article</code>	default: book
<code>book</code>	For typesetting texts with chapters.	
<code>article</code>	For typesetting articles or short theses (that is without chapter division).	
<code>collection</code>	For typesetting journals or collections of articles (see section 5).	
<code>pagelayout=</code>	<code>standard, periodical, compact, supercompact, elements</code>	default: standard
<code>standard</code>	Prints an A4 typeblock with a text area of 110 mm × 220 mm.	
With the following values the option prints the typeblock on a an A4 paper showing the crop marks which can be controlled by the <code>version</code> option.		
<code>periodical</code>	Prints a typeblock of 17 cm × 24 cm with a text area of 11 cm × 16.5 cm.	
<code>periodicalaureo</code>	The same of <code>periodical</code> but with a <i>golden ratio</i> text area of 120 cm × 194 mm.	
<code>compact</code>	Prints a typeblock of 16 cm × 24 cm with a text area of 11 cm × 16.5 cm.	
<code>compactaureo</code>	The same as <code>compact</code> but with a <i>golden ratio</i> text area of 11.8 cm × 19.1 cm.	
<code>supercompact</code>	Prints a typeblock of 14 cm × 21 cm with a text area of 10 cm × 15.5 cm.	
<code>supercompactaureo</code>	The same as <code>supercompact</code> but with a <i>golden ratio</i> text area of 10.8 cm × 17.5 cm.	
<code>elements</code>	Prints a typeblock with the dimensions of Bringhurst (1992). To reproduce the whole style of this book use <code>style=elements</code> option instead.	

The details of this option are shown in table 1.

3.2 Fonts

The font options are available only with L^AT_EX. Using X^LT_EX the default font is the Computer Modern but you can change it through the `fontspec` or `mathspec` packages. With this engine I do suggest the Junicode or EB Garamond font families.

<code>defaultfont=</code>	<code>palatino, standard</code>	default: palatino
<code>palatino</code>	Loads the Palatino font family.	
<code>standard</code>	Loads the Latin Modern font family and the standard CB Greek font.	
<code>greekfont=</code>	<code>artemisia, porson, cbgreek</code>	default: artemisia
<code>artemisia</code>	Loads the Artemisia font.	
<code>porson</code>	Loads the Porson font.	
<code>cbgreek</code>	Loads the standard CB Greek font.	

3.3 Titles

<code>(level)font=</code>	<code>roman, italic, smallcaps</code>	default: roman
<code>roman</code>	Prints the <code>(level)</code> title in roman.	
<code>italic</code>	Prints the <code>(level)</code> title in <i>italic</i> .	
<code>smallcaps</code>	Prints the <code>(level)</code> title in SMALL CAPS	
Where <code>(level)</code> can be	<code>part, chap, sec, subsec, subsubsec</code>	
<code>(level)style=</code>	<code>left, center, right, parleft, parcenter, parright</code>	default: left
<code>left</code>	Aligns the <code>(level)</code> title on the left.	
<code>center</code>	Centers the <code>(level)</code> title.	
<code>right</code>	Aligns the <code>(level)</code> title on the right.	

Where $\langle level \rangle$ can be part, chap, sec subsec, subsubsec.

- parleft** As left but with the title below the number.
- parcenter** As center but with the title below the number.
- parright** As right but with the title below the number.

Where $\langle level \rangle$ can be part, chap, sec.

- elements** Print a chapter number in the style of Bringhurst (1992).

Where $\langle level \rangle$ can be chap.

(level)numstyle=arabic, roman, Roman, dotarabic, dotroman, dotRoman default: Roman/arabic/arabic

- arabic** Arabic $\langle level \rangle$ number.
- roman** Small caps lowercase roman $\langle level \rangle$ number.
- Roman** Uppercase roman $\langle level \rangle$ number.
- dotarabic** As arabic but followed by a dot.
- dotroman** As roman but followed by a dot.
- dotRoman** As Roman but followed by a dot.

Where $\langle level \rangle$ can be part, chap, sec.

tocstyle=standard, dotted, ragged, leftpage default: standard

- standard** Prints a standard table of contents with page numbers on the right margin.
- dotted** As the previous one but with dotted lines.
- ragged** Aligns the table of contents on the left as suggested by Bringhurst (1992).
- leftpage** Prints a table of contents with page numbers on the left margin.

twocolcontents=toc, lof, lot, toclof, toclot, loflot, all default: all

This option activates the `tocstyle=ragged` option and disables the other values of `tocstyle`.

- toc** Prints the table of contents in two columns.
- lof** Prints the list of figures in two columns.
- lot** Prints the list of tables in two columns.
- toclof** Prints the table of contents and the list of figures in two columns.
- toclot** Prints the table of contents and the list of tables in two columns.
- loflot** Prints the list of figures and the list of tables in two columns.
- all** Prints the table of contents, the list of figures and the list of tables in two columns.

smallcapsstyle=low, upper default: low

This option is active only with $\langle level \rangle$ `font=smallcaps` options.

- low** Prints lowercase SMALL CAPITALS.
- upper** Prints SMALL CAPITALS without changing the case.

3.4 Headings

headerstyle=inner, center, plain, authortitleinner, authortitlecenter, elements default: inner

- inner** Prints the chapter title and the string “Chapter $\langle n \rangle$ ” in the inner side respectively of even and odd headers, and the page number in the outer side.
- center** Centers the header and footer and puts the page number in the center of the footer.
- plain** Prints no headers and puts the page number in the center of the footer.
- authortitleinner** Prints the author’s name on the even pages and the title on the odd ones. In order to use this option the `\title` and `\author` commands are required.
- authortitlecenter** As the previous one but with centered headers and footers.

elements Prints the chapter title and the section title in the margin respectively of even pages and odd pages. The page number is put in the outer side of the footer. This is the style loaded by the option `style=elements`.

headerfont=roman, italic, smallcaps default: roman

roman Prints the headers in roman.
italic Prints the headers in *italic*.
smallcaps Prints the headers in SMALL CAPS.

3.5 Notes, lists, quotations

quotestyle=center, right default: center

center Indents the block quotations on both the left and right margins.
right Indents the block quotations only on the left margin.

quotesize=footnotesize, small default: footnotesize

footnotesize Prints the block quotations in \footnotesize size.
small Prints the block quotations in \small size.

footnotestyle=bulged, hung, dotted, superscript default: bulged

bulged The footnote number protrudes beyond the left margin.
hung Indents the footnote text, so it will ?hang? under the first line of the text.
dotted The footnote number is aligned to the left margin and followed by a dot.
superscript Prints a superscript footnote number aligned to the left margin.

fewfootnotes=true, false default: false

Uses symbols instead of numbers to mark footnotes. It is active only in documents with three footnotes per page maximum. The symbol sequence is: *, **, ***. With more footnotes you should not need this option.

liststyle=bulged, aligned, indented default: bulged

bulged The item number or symbol protrudes beyond the left margin.
aligned Aligns the lists to the left margin.
indented Prints standard indented lists.

captionstyle=standard, sanserif, italic, smallcaps, elements default: standard

All these values print the caption in small size, changing the shape:

standard Prints the caption text and label in normal font.
sanserif Prints the caption text and label in sanserif.
italic Prints the caption text and label in *italic*.
smallcaps Prints only the caption label in SMALL CAPS.
elements An alias of sanserif.

3.6 Other options

version=screen, draft, final default: print

screen This option is provided to have a better view when you are typesetting and reading the PDF on the screen. It simply executes the `oneside` and `nocrop=false` options and redefines the `\crop` command so you do not need to comment it if it is used in the document.
draft Prints the output on a A4 paper, showing the crop marks. It is the same of `crop=true`.
final Prints the output on a A4 paper, hiding the crop marks.

parindent =compact, wide	default: compact
compact	Sets the indentation of the first line of each paragraph except those following a section title.
wide	Sets indentation to 1 em.
marginpar =true, false	default: true
true	Prints the marginal notes.
false	Hide the marginal notes.
partpage =true, false	default: false
▶ This option is active only with documentstructure=article .	
true	Prints the part title in a separate page as in documentstructure=book
false	Prints a part title similar to the one used in the standard article class.
draftdate =true, false	default: false
If true it prints the string “Version of <date>” in the footer. It requires the <code>\date{<date>}</code> command.	
crop =true, false	default: true
▶ This option is actually useless. Use the version option instead.	
true	Prints the output on a A4 paper, showing the crop marks. It is the same of version=draft .
false	Prints a PDF with page dimensions according to the pagelayout option. It is similar to version=screen but it does not execute oneside option and it does not redefine \crop .

3.7 Pre-defined styles

These pre-defined styles are intended as shotrcuts to some groups of class options. Combining them with **dottedchap** and **romanchapnum** options you can get up to 120 variants.

style =roman(1-6), italic(1-12), smallcaps(1-6), elements, sufelements	default: roman1
roman(1-6)	The titles of chapters and headers are printed in roman. The number of the chapter is on the same line in styles 1-3 and above the title in styles 4-6. The title can be printed on the left (styles 1 and 4), in the center (styles 2 and 5) or on the right (styles 3 and 6).
italic(1-12)	The titles of chapters and headers are in <i>italic</i> . The section title is in <i>italic</i> in styles 1-6 and in SMALL CAPS in styles 7-12. There are three position for the title and two positions for the number as above.
smallcaps(1-12)	The titles of chapters and headers are in SMALL CAPS . The title of the section is in <i>italic</i> in styles 1-6 and in SMALL CAPS in styles 7-12. There are three position for the title and two positions for the chapter as above.
elements	Reproduces the style of the Italian edition of Bringhurst (1992).
sufelements	Combines the elements -style sections with standard small caps headers. It can be used with all the page layouts.

The FSPL styles

The following styles are only meant to typeset a doctoral thesis respecting the features required by the Joint Project *Formal Style for PhD Theses with LaTeX* of the Verona University (Italy).^a

style=FSPLa, FSPLb, FSPLc

FSPLa	Equal to: pagelayout=periodical, style=roman1, footnotestyle=superscript, liststyle=indented, tocstyle=ragged .
FSPLb	Equal to: pagelayout=periodical, style=italic5, headerstyle=center, chapnumstyle=roman, secstyle=center, quotestyle=right, footnotestyle=hung, liststyle=indented, tocstyle=dotted .
FSPLc	Equal to: pagelayout=periodical, style=smallcaps5, secfont=smallcaps,

```
headerstyle=center, footnotestyle=dotted, liststyle=indented,
tocstyle=leftpage.
```

\FSPLcolophon

To typeset the colophon in the FSPL style (see example below), according to the Joint Project *Formal Style for PhD Theses with L^AT_EX* of the Verona University (Italy):

© 2014 *(Name Surname)*

This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/3.0/>.

Typeset with L^AT_EX in collaboration with the Joint Project *Formal Style for PhD Theses with L^AT_EX* (University of Verona, Italy) using the *suftesi* class by Ivan Valbusa. The text face is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by Janusz M. Nowacki.

^a<http://www.univr.it/main?ent=catdoc&id=3727&idDest=6&serv=127#1431>.

4 New commands

4.1 Printing the colophon

As explained at the beginning of this documentation, in addition to the terms of the L^AT_EX Project Public License, *suftesi* requires a specific attribution notice. You can typeset the attribution notice manually or using one of these commands.

\colophon[<OS>]{<name and surname>}{<additional info>}

This command is provided only for Italian documents. It prints a page with a copyright notice and the colophon in the bottom of the page. For different languages use the \bookcolophon instead (see below). If you don't need the copyright notice, leave the second argument of the command empty:

\colophon[<OS>]{ }{<additional info>}

With the *article* option, you can use the \artcolophon command (see below) or the \thanks command:

```
\author{Name Surname}
\thanks{This work has been typeset with \cmd{LaTeX},
using the \textsf{suftesi} class by Ivan Valbusa.}
```

\bookcolophon{<copyright notice>}{<attribution notice and other informations>}

Similar to \colophon but completely customizable. The first argument prints its content (usually the copyright notice) in the center of the page. The second one prints its content at the bottom. For example:

```
\bookcolophon{
Copyright © 2007 by Ivan Valbusa}%
This work has been typeset with \LaTeX,
using the \textsf{suftesi} class
by Ivan Valbusa\index{Valbusa, Ivan}.
The normal font is Palatino by Hermann Zapf.
The sans serif font is Iwona by Janusz M.~Nowacki.}
```

\artcolophon{<copyright notice, attribution and other informations>}

This command only has one argument. It simply prints its content at the bottom of the page.

Here is an example:

```
\artcolophon{%
This work is licensed under the Creative Commons
Attribution-NonCommercial-NoDerivs 3.0 Unported License.
To view a copy of this license, visit
\begin{center}
\texttt{http://creativecommons.org/licenses/by-nc-nd/3.0}
```

```
\end{center}
or send a letter to Creative Commons, 444 Castro Street,
Suite 900, Mountain View, California, 94041, USA.\[1ex]

Typeset with \LaTeX, using the \textsf{suftesi} class
by Ivan Valbusa.}
```

\finalcolophon{<colophon content>}

The same as \artcolophon, but centering its content at the top of the page. It is aimed at typesetting a classical *colophon* at the end of the work.

4.2 Breaking titles in text body, headers and table of contents

\headbreak

A manual break which is active for the table of contents but not in the text or in the headers.

\xheadbreak

A manual break which is active in the text and in the headers but not in the table of contents.

4.3 Other commands

\toclabelwidth{<level>}{<dim>}

Adds the <dim> to the <level> label in the table of contents, where <level> can be part, chap, sec, subsec, subsubsec, par, subpar, fig, tab. For example, when using chapnumstyle=Roman you would probably need to adjust the width of the chapter label with:

```
\toclabelwidth{chap}{1em}
```

\xfootnote{<symbol>}{<footnote text>}

A command to print a footnote with a discretionary symbols given in the optional argument (default=*) . It does not increment the footnote counter.

```
\xfootnote[$\dagger$]{Footnote text}
\xfootnote[\textdagger]{Footnote text}
```

\title{<short title for headers>}{<complete title for titlepage>}

Useful with authortitle option if the title is too long or has some breaks.

\chapterintro

Prints an unnumbered introduction at the beginning of the chapter, with the correct hyperlink. In order to use this command the hyperref package must be loaded.

\chapterintroname{<name>}

(default=Introduzione)

Changes in <name> the title printed by the \chapterintro command.

\appendicesname{<name>}

(default=Appendici)

Changes in <name> the title printed by the \appendix command.

\chapnumfont{<name>}

Sets the font of the chapter number of style=elements/sufelements styles. The default is Palatino (L^AT_EX) or Computer Modern (X_L^AT_EX). Using (pdf)L^AT_EX you can change it simply giving the name of the font family.

For example, to select the Helvetica family you will need:

```
\chapnumfont{phv}
```

With X_ET_EX the \fontspec command is required:

```
\chapnumfont{\fontspec[Numbers=OldStyle]{Helvetica}}
```

5 The collection document structure

The collection document structure is thought to compose a collection of papers. Each paper has to be typeset in a separate .tex file with the following structure:

```
\author{Author}
\title{Title of the paper}

% The abstract is optional.
% \begin{abstract}
%   The abstract
% \end{abstract}

\maketitle

Text of the paper
```

If the names of the papers are article1.tex, article2.tex, article3.tex, etc., then a minimal main file should be similar to this:

```
\documentclass[documentstructure=collection]{suftesi}

\begin{document}
\includeart{article1}
\includeart{article2}
\includeart{article3}
\end{document}
```

5.1 Options

In addition to the following options you can use the other options of the class too. In particular, with the chapstyle and chapfont options you can customize all the section titles which are treated as a normal unnumbered chapters in the book document structure, such as “Table of Contents”, “Index”, “Bibliography”, etc.

papertitlestyle=left, center, right

default: left

- left** Aligns the author-title block on the left.
- center** Centers the author-title block.
- right** Aligns the author-title block on the right.

titlefont=roman, italic, smallcaps

default: italic

- roman** Prints the title of the articles in roman.
- italic** Prints the title of the articles in *italic*.
- smallcaps** Prints the title of the articles in SMALL CAPS.

authorfont=roman, italic, smallcaps

default: roman

- roman** Prints the author's name in roman.
- italic** Prints the author's name in *italic*.
- smallcaps** Prints the s name in SMALL CAPS.

5.2 Commands

`\includeart{\langle file name \rangle}`

Include the `\langle file name \rangle` in the collection.

`\frontispiece`

Typeset the frontispiece of the collection.

It requires the `\collectiontitle` and `\collectioneditor` commands in the preamble of your document.

`\collectiontitle{\langle The Title of the Collection \rangle}`

Sets the title of the collection.

`\collectioneditor{\langle The Editor(s) \rangle}`

Sets the editor(s) of the collection.

References

This bibliography has been typeset with the `biblatex-philosophy` package, created by the same author of this class.

- Bringhurst, Robert (1992), *The Elements of Typographic Style*, 4th ed. (version 4.0), Hurtley & Marks Publisher, Vancouver; trans. *Gli elementi dello stile tipografico*, 5th ed., Sylvestre Bonnard, Milano 2009.
- Gregorio, Enrico (2009), *Il pacchetto frontespizio*, version 1.1, <http://www.guit.sssup.it/phpbb/index.php>.
- Miede, André (2011), *A Classic Thesis style*, <http://www.ctan.org/tex-%20archive/macros/%20latex/contrib/classicthesis/ClassicThesis.%20pdf>.
- Morison, Stanley (1936), *First Principles of Typography*, Cambridge University Press, Cambridge; trans. *I principi fondamentali della tipografia*, Fabrizio Serra editore, Pisa-Roma 2008.
- Pantieri, Lorenzo and Tommaso Gordini (2012), *L’arte di scrivere con L^AT_EX. Un’introduzione a L^AT_EX 2_E*, with a forew. by Enrico Gregorio, new edition, http://www.lorenzopantieri.net/LaTeX_files/ArteLaTeX.pdf.
- Tschichold, Jan (1975), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie*, Birkhäuser Verlag, Basel; trans. *La forma del libro*, Sylvestre Bonnard, Milano 2003.

6 The Code

```

1 \ClassWarningNoLine{suftesi}{%
2   ****\MessageBreak
3   * DO NOT MODIFY THE STYLES OF THIS CLASS\MessageBreak
4   * WITH PACKAGES AND/OR COMMANDS WHICH CHANGE\MessageBreak
5   * THE LAYOUT OF THE DOCUMENT.\MessageBreak
6   * SEE DOCUMENTATION FOR DETAILS.\MessageBreak
7   * ANYWAY, DON'T WORRY!\MessageBreak
8   * THIS IS A HARMLESS MESSAGE :-)\MessageBreak
9   ****\MessageBreak
10 \RequirePackage{xkeyval}
11 \newif\ifsuftesi@standardfont
12 \newif\ifsuftesi@porson
13 \newif\ifsuftesi@centerheader
14 \newif\ifsuftesi@sufplain
15 \newif\ifsuftesi@article
16 \newif\ifsuftesi@authortitle
17 \newif\ifsuftesi@periodical
18 \newif\ifsuftesi@periodicalaureo
19 \newif\ifsuftesi@compact
20 \newif\ifsuftesi@compactaureo
21 \newif\ifsuftesi@supercompact
22 \newif\ifsuftesi@supercompactaureo
23 \newif\ifsuftesi@sufelements
24 \newif\ifsuftesi@nocrop
25 \newif\ifsuftesi@dottedtoc
26 \newif\ifsuftesi@raggedtoc
27 \newif\ifsuftesi@numparpart
28 \newif\ifsuftesi@numparchap
29 \newif\ifsuftesi@numparsec
30 \newif\ifsuftesi@numparsubsec
31 \newif\ifsuftesi@numparsubsubsec
32 \newif\ifsuftesi@smallcapspart
33 \newif\ifsuftesi@smallcapschap
34 \newif\ifsuftesi@smallcapssec
35 \newif\ifsuftesi@elementschap
36 \newif\ifsuftesi@elementsheader
37 \newif\ifsuftesi@elementsstructure
38 \newif\ifsuftesi@elementspagelayout
39 \newif\ifsuftesi@draftdate
40 \newif\ifsuftesi@fewfootnotes
41 \newif\ifsuftesi@partpage
42 \newif\ifsuftesi@FSPL
43 \newif\ifsuftesi@screen
44 \newif\ifsuftesi@pagelefttoc
45 \newif\ifsuftesi@twocolumnmtoc
46 \newif\ifsuftesi@twocolumnllof
47 \newif\ifsuftesi@twocolumnllof
48 \newif\ifsuftesi@reverseauthortitle
49 \newif\ifsuftesi@collection
50 \DeclareOption{a5paper}{%
51   \ClassError{suftesi}{Option 'a5paper' not available}%
52 \DeclareOption{b5paper}{%
53   \ClassError{suftesi}{Option 'b5paper' not available}%
54 \DeclareOption{legalpaper}{%
55   \ClassError{suftesi}{Option 'legalpaper' not available}%
56 \DeclareOption{executivepaper}{%
57   \ClassError{suftesi}{Option 'executivepaper' not available}%
58 \DeclareOption{landscape}{%
59   \ClassError{suftesi}{Option 'landscape' not available}}%
suftesi is based on the standard book class!
60 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{book}}
61 \ProcessOptions
62 \relax
63 \LoadClass{book}
```

6.1 Document structure

```

64 \define@choicekey{}{documentstructure}[\val\nr]
65   {book,article,collection}[book]{%
66 \ifcase\nr\relax
67 \disable@keys{}{secnumstyle}
68 \or
69 \suftesi@articleture
70 \atitlepagefalse
71 \or
72 \suftesi@collectiontrue
73 \setkeys{}{headerstyle=authortitleinner}
74 \fi}
```

6.2 Page layout

```

75 \RequirePackage{geometry}
76 \define@choicekey{}{pagelayout}[\val\nr]
77   {standard,periodical,compact,compactaureo,supercompact,
78   supercompactaureo,elements,periodicalaureo}[standard]{%
79 \ifcase\nr\relax
80 \DeclareRobustCommand{\SUF@chaptersize}{\Large}
81 \geometry{%
82   heightrounded,
83   a4paper,
84   includeheadfoot=true,
85   textwidth= 110mm,
86   textheight= 220mm,
87   marginratio= 1:2,
88   marginparwidth= 30mm,
89   marginparsep= 12pt}
90 \or
91 \suftesi@periodicaltrue
92 \DeclareRobustCommand{\SUF@chaptersize}{\large}
93 \geometry{%
94   heightrounded,
95   includeheadfoot=false,
96   textheight= 165mm,
97   textwidth= 110mm,
98   paperwidth= 170mm,
99   paperheight= 240mm,
100  marginratio= 2:3,
101  marginparwidth= 26mm,
102  marginparsep= 10pt}
103 \or
104 \suftesi@compacttrue
105 \DeclareRobustCommand{\SUF@chaptersize}{\large}
106 \geometry{%
107   heightrounded,
108   includeheadfoot=false,
109   textheight= 165mm,
110   textwidth= 110mm,
111   paperwidth= 160mm,
112   paperheight= 240mm,
113   marginratio= 2:3,
114   marginparwidth= 22mm,
115   marginparsep= 9pt}
116 \or
117 \suftesi@compactaureottrue
118 \DeclareRobustCommand{\SUF@chaptersize}{\large}
119 \geometry{%
120   heightrounded,
121   includeheadfoot=false,
122   textheight= 191mm,
123   textwidth= 118mm,
124   paperwidth= 160mm,
125   paperheight= 240mm,
```

```

126     marginratio=    2:3,
127     marginparwidth= 19mm,
128     marginparsep=   9pt}
129 \or
130 \suftesi@supercompacttrue
131 \DeclareRobustCommand{\SUF@chaptersize}{\large}
132 \geometry{
133     heightrounded,
134     includeheadfoot=false,
135     textheight=      150mm,
136     textwidth=       100mm,
137     paperwidth=      140mm,
138     paperheight=     210mm,
139     marginratio=    2:3,
140     marginparwidth= 18mm,
141     marginparsep=   8pt}
142 \or
143 \suftesi@supercompactaureottrue
144 \DeclareRobustCommand{\SUF@chaptersize}{\large}
145 \geometry{
146     heightrounded,
147     includeheadfoot=false,
148     textheight=      175mm,
149     textwidth=       108mm,
150     paperwidth=      140mm,
151     paperheight=     210mm,
152     marginratio=    1:1,
153     marginparwidth= 11mm,
154     marginparsep=   7pt}\or
155 \suftesi@elementspagelayouttrue
156 \geometry{%
157     heightrounded,
158     includeheadfoot=false,
159     textwidth=       251pt,
160     textheight=      502pt,
161     paperwidth=      374pt,
162     paperheight=     648pt,
163     vmarginratio=   1:2,
164     marginparwidth= 60pt,
165     marginparsep=   18pt,
166     outer=          90pt}
167 \or
168 \suftesi@periodicalaureottrue
169 \DeclareRobustCommand{\SUF@chaptersize}{\large}
170 \geometry{%
171     heightrounded,
172     includeheadfoot=true,
173     textwidth=       120mm,
174     textheight=      194mm,
175     paperwidth=      17cm,
176     paperheight=     24cm,
177     marginratio=    2:3,
178     marginparwidth= 62pt,
179     marginparsep=   10pt}
180 \or
181 \fi}

```

6.3 Sections style

These macros control the position of titles and numbers of parts, chapters, sections, subsections and subsubsection.

```

182 \define@choicekey{}{partstyle}[\val\nr]{%
183     left,center,right,parleft,parcenter,parright}[left]{%
184 \ifcase\nr\relax
185     \def\SUF@lr@PARTSwitch{\filright}
186 \or
187     \def\SUF@lr@PARTSwitch{\filcenter}

```

```
188 \or
189   \def\SUF@lr@PARTSwitch{\filleft}
190 \or%numpar
191   \def\SUF@lr@PARTSwitch{\filright}
192   \suftesi@numparparttrue
193 \or
194   \def\SUF@lr@PARTSwitch{\filcenter}
195   \suftesi@numparparttrue
196 \or
197   \def\SUF@lr@PARTSwitch{\filleft}
198   \suftesi@numparparttrue
199 \fi}
200 \define@choicekey{}{chapstyle}{[\val\nr]}{%
201   left,center,right,parleft,parcenter,parright,elements}[left]{%
202 \ifcase\nr\relax
203   \def\SUF@lr@CHAPSwitch{\filright}
204 \or
205   \def\SUF@lr@CHAPSwitch{\filcenter}
206 \or
207   \def\SUF@lr@CHAPSwitch{\filleft}
208 \or%numparchap
209   \def\SUF@lr@CHAPSwitch{\filright}
210   \suftesi@numparchaptrue
211 \or
212   \def\SUF@lr@CHAPSwitch{\filcenter}
213   \suftesi@numparchaptrue
214 \or
215   \def\SUF@lr@CHAPSwitch{\filleft}
216   \suftesi@numparchaptrue
217 \or
218   \suftesi@elementschaptrue
219 \fi}
220 \define@choicekey{}{secstyle}{[\val\nr]}{%
221   left,center,right,parleft,parcenter,parright}[left]{%
222 \ifcase\nr\relax
223   \def\SUF@lr@SECSwitch{\filright}
224 \or
225   \def\SUF@lr@SECSwitch{\filcenter}
226 \or
227   \def\SUF@lr@SECSwitch{\filleft}
228 \or%numparsec
229   \def\SUF@lr@SECSwitch{\filright}
230   \suftesi@numparsectrue
231 \or
232   \def\SUF@lr@SECSwitch{\filcenter}
233   \suftesi@numparsectrue
234 \or
235   \def\SUF@lr@SECSwitch{\filleft}
236   \suftesi@numparsectrue
237 \fi}
238 \define@choicekey{}{subsecstyle}{[\val\nr]}{left,center,right}[left]{%
239 \ifcase\nr\relax
240   \def\SUF@lr@SUBSECSwitch{\filright}
241 \or
242   \def\SUF@lr@SUBSECSwitch{\filcenter}
243 \or
244   \def\SUF@lr@SUBSECSwitch{\filleft}
245 \fi}
246 \define@choicekey{}{subsubsecstyle}{[\val\nr]}{left,center,right}[left]{%
247 \ifcase\nr\relax
248   \def\SUF@lr@SUBSUBSECSwitch{\filright}
249 \or
250   \def\SUF@lr@SUBSUBSECSwitch{\filcenter}
251 \or
252   \def\SUF@lr@SUBSUBSECSwitch{\filleft}
253 \fi}
```

6.4 Sections font

These macros control the style of part, chapter, section, subsection and subsubsection levels.

```

254 \define@choicekey{}{partfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
255 \ifcase\nr\relax
256 \def\SUF@PART@StyleSwitch{\relax}
257 \or
258 \def\SUF@PART@StyleSwitch{\itshape}
259 \or
260 \def\SUF@PART@StyleSwitch{\expandafter\SUF@titlesmallcaps}
261 \fi}
262 \define@choicekey{}{chapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
263 \ifcase\nr\relax
264 \def\SUF@CHAP@StyleSwitch{\relax}
265 \or
266 \def\SUF@CHAP@StyleSwitch{\itshape}
267 \or
268 \def\SUF@CHAP@StyleSwitch{\expandafter\SUF@titlesmallcaps}
269 \fi}
270 \define@choicekey{}{secfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
271 \ifcase\nr\relax
272 \def\SUF@SEC@StyleSwitch{\relax}
273 \or
274 \def\SUF@SEC@StyleSwitch{\itshape}
275 \or
276 \def\SUF@SEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
277 \fi}
278 \define@choicekey{}{subsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
279 \ifcase\nr\relax
280 \def\SUF@SUBSEC@StyleSwitch{\relax}
281 \or
282 \def\SUF@SUBSEC@StyleSwitch{\itshape}
283 \or
284 \def\SUF@SUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
285 \fi}
286 \define@choicekey{}{subsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
287 \ifcase\nr\relax
288 \def\SUF@SUBSUBSEC@StyleSwitch{\relax}
289 \or
290 \def\SUF@SUBSUBSEC@StyleSwitch{\itshape}
291 \or
292 \def\SUF@SUBSUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
293 \fi}

```

6.5 Section numbers

6.5.1 Part number style

```

294 \define@choicekey{}{partnumstyle}[\val\nr]
295   {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
296 \ifcase\nr\relax
297   \def\SUF@thepart{\arabic{part}}
298   \def\SUF@dotpart{}}
299   \def\SUF@toclabelnum{}
300 \or
301   \def\SUF@thepart{\textsc{\romannumeral{part}}}
302   \def\SUF@dotpart{}}
303   \def\SUF@toclabelnum{\textsc{\romannumeral{part}}}
304 \or
305   \def\SUF@thepart{\Roman{part}}
306   \def\SUF@dotpart{}}
307   \def\SUF@toclabelnum{\textsc{\Roman{part}}}
308 \or
309   \def\SUF@thepart{\arabic{part}}
310   \def\SUF@dotpart{.}
311   \def\SUF@toclabelnum{}

```

```

312 \or
313   \def\SUF@the part{\textsc{\rom{part}}}
314   \def\SUF@dot part{.}
315   \def\SUF@toclabelnum{\scshape\rom{roman}}
316 \or
317   \def\SUF@the part{\Rom{part}}
318   \def\SUF@dot part{.}
319   \def\SUF@toclabelnum{\@Roman}
320 \fi}

```

6.5.2 Chapter number

```

321 \define@choicekey{}{chapnumstyle}[\val\nr]{arabic,roman,Roman,
322 dotarabic,dotroman,dotRoman}[arabic]{%
323 \ifcase\nr\relax
324   \def\SUF@the chapter{\arabic{chapter}}
325   \def\SUF@dot chap{}%
326   \def\SUF@toclabelnum{}%
327 \or
328   \def\SUF@the chapter{\textsc{\rom{chapter}}}
329   \def\SUF@dot chap{}%
330   \def\SUF@toclabelnum{\scshape\rom{roman}}%
331 \or
332   \def\SUF@the chapter{\Rom{chapter}}
333   \def\SUF@dot chap{}%
334   \def\SUF@toclabelnum{\@Roman}%
335 \or
336   \def\SUF@the chapter{\arabic{chapter}}
337   \def\SUF@dot chap{.}%
338   \def\SUF@toclabelnum{}%
339 \or
340   \def\SUF@the chapter{\textsc{\rom{chapter}}}
341   \def\SUF@dot chap{.}%
342   \def\SUF@toclabelnum{\scshape\rom{roman}}%
343 \or
344   \def\SUF@the chapter{\Rom{chapter}}
345   \def\SUF@dot chap{.}%
346   \def\SUF@toclabelnum{\@Roman}%
347 \fi}

```

6.5.3 Section number

```

348 \define@choicekey{}{secnumstyle}[\val\nr]
349   {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
350 \ifcase\nr\relax
351   \def\SUF@thesection{\arabic{section}}
352   \def\SUF@dot sec{}%
353   \def\SUF@toclabelnum{}%
354 \or
355   \def\SUF@thesection{\textsc{\rom{section}}}
356   \def\SUF@dot sec{}%
357   \def\SUF@toclabelnum{\scshape\rom{roman}}%
358 \or
359   \def\SUF@thesection{\Rom{section}}
360   \def\SUF@dot sec{}%
361   \def\SUF@toclabelnum{\@Roman}%
362 \or
363   \def\SUF@thesection{\arabic{section}}
364   \def\SUF@dot sec{.}%
365   \def\SUF@toclabelnum{}%
366 \or
367   \def\SUF@thesection{\textsc{\rom{section}}}
368   \def\SUF@dot sec{.}%
369   \def\SUF@toclabelnum{\scshape\rom{roman}}%
370 \or
371   \def\SUF@thesection{\Rom{section}}
372   \def\SUF@dot sec{.}%
373   \def\SUF@toclabelnum{\@Roman}%

```

```
374 \fi}
```

This option controls the style of small capitals used in the title of chapters and sections using `<level>font=smallcaps` option:

```
375 \define@choicekey{}{smallcapsstyle}[\val\nr]
376   {low,upper}[low]{%
377 \ifcase\nr\relax
378   \def\suftesi@MakeTextLowercase{\MakeTextLowercase}
379 \or
380   \def\suftesi@MakeTextLowercase{\relax}
381 \fi}
```

6.6 Headers

6.6.1 Header style

```
382 \define@choicekey{}{headerstyle}[\val\nr]
383   {inner,center,plain,authortitleinner,
384   authortitlecenter,elements}[inner]{%
385 \ifcase\nr\relax
386   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
387   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}
388 \or
389   \suftesi@centerheadertrue
390   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
391   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}
392 \or
393   \suftesi@sufplaintrue
394 \or
395   \suftesi@authortitletrue
396   \def\SUF@rightmark{\SUF@Rheadstyle{\@headtitle}}
397   \def\SUF@leftmark{\SUF@Lheadstyle{\@author}}
398 \or
399   \suftesi@authortitletrue
400   \def\SUF@rightmark{\SUF@Rheadstyle{\@headtitle}}
401   \def\SUF@leftmark{\SUF@Lheadstyle{\@author}}
402   \suftesi@centerheadertrue
403 \or
404   \suftesi@elementsheadertrue
405 \fi}
```

6.6.2 Header font

```
406 \define@choicekey{}{headerfont}[\val\nr]
407   {roman,italic,smallcaps}[roman]{%
408 \ifcase\nr\relax
409   \def\SUF@Rheadstyle{}
410   \def\SUF@Lheadstyle{}
411   \def\SUF@thepage{\thepage}
412 \or
413   \def\SUF@Rheadstyle{\itshape}
414   \def\SUF@Lheadstyle{\itshape}
415   \def\SUF@thepage{\thepage}
416 \or
417   \def\SUF@Rheadstyle{\SUF@headingsmallcaps}
418   \def\SUF@Lheadstyle{\SUF@headingsmallcaps}
419   \def\SUF@thepage{\SUF@headingsmallcaps{\thepage}}
420 \fi}
```

6.7 Text elements

6.7.1 Lists

```
421 \RequirePackage[inline]{enumitem}
422 \renewcommand\labelitemi{\color{sufgray}\textbullet}
423 \setlist[itemsep=.5ex,parsep=0pt]
424 \setlist[description]{font=\normalfont\itshape}
425 \define@choicekey{}{liststyle}[\val\nr]
426   {bulged,aligned,indented}[bulged]{%
427 \ifcase\nr\relax
```

```

428     \setlist[enumerate,1]{leftmargin=0pt,label=\arabic*.}
429     \setlist[enumerate,2]{leftmargin= 1.3\parindent,label=\alph*.}
430     \setlist[enumerate,3]{leftmargin= 1.3\parindent,label=\roman*.}
431     \setlist[itemize,1]{leftmargin=0pt}
432     \setlist[itemize,2]{leftmargin=1.3\parindent}
433     \setlist[itemize,3]{leftmargin=1.3\parindent}
434 \or
435     \setlist[enumerate,1]{leftmargin=1\parindent,label=\arabic*.}
436     \setlist[enumerate,2]{leftmargin= 1.5\parindent,label=\alph*.}
437     \setlist[enumerate,3]{leftmargin= 1.5\parindent,label=\roman*.}
438     \setlist[itemize,1]{leftmargin=1\parindent}
439     \setlist[itemize,2]{leftmargin=1.5\parindent}
440     \setlist[itemize,3]{leftmargin=1.5\parindent}
441 \or
442     \setlist[enumerate,1]{leftmargin=2\parindent,label=\arabic*.}
443     \setlist[enumerate,2]{leftmargin= 2.5\parindent,label=\alph*.}
444     \setlist[enumerate,3]{leftmargin= 2.5\parindent,label=\roman*.}
445     \setlist[itemize,1]{leftmargin=2\parindent}
446     \setlist[itemize,2]{leftmargin=2.5\parindent}
447     \setlist[itemize,3]{leftmargin=2.5\parindent}
448 \fi}

```

6.7.2 Block quotations

Quotation style

```

449 \define@choicekey{}{quotestyle}[\val\nr]
450   {center,right}[center]{%
451 \ifcase\nr\relax
452 \def\SUF@quote@style{\rightmargin=\parindent}
453 \or
454 \def\SUF@quote@style{}%
455 \fi}

```

Quotation size

```

456 \define@choicekey{}{quotesize}[\val\nr]
457   {footnotesize,small}[footnotesize]{%
458 \ifcase\nr\relax
459 \def\SUF@quotation@size{\footnotesize}
460 \or
461 \def\SUF@quotation@size{\small}%
462 \fi}

```

6.7.3 Footnotes

```

463 \define@choicekey{}{footnotestyle}[\val\nr]
464   {bulged,hung,dotted,superscript}[bulged]{%
465 \ifcase\nr\relax
466   \renewcommand\@makefntext{%
467     \hskip-2.5em\makebox[2em][r]{\@thefnmark}\hskip.5em}
468 \or
469   \renewcommand\@makefntext{%
470     \leftskip=1em\hskip-1.5em%
471     \makebox[1em][r]{\@thefnmark}\hskip.5em}
472 \or
473   \renewcommand\@makefntext{%
474     \atthefnmark.\hskip.5em}
475 \or
476   \renewcommand\@makefntext{%
477     \textsuperscript{\atthefnmark}\hskip.3em}
478 \fi}
479 \define@choicekey{}{fewfootnotes}[\val\nr]
480   {true,false}[true]{%
481 \ifcase\nr\relax
482   \suftesi@fewfootnotestrue
483 \or
484   \relax

```

485 \fi}

6.7.4 Captions

```
486 \RequirePackage{caption}
487 \define@choicekey{}{captionstyle}[\val\nr]
488   {standard,sanserif,italic,smallcaps,elements}[standard]{%
489 \ifcase\nr\relax
490   \captionsetup{labelsep=period,font=small}
491 \or
492   \captionsetup{labelsep=period,font=small}
493   \captionsetup{font+=sf}
494 \or
495   \captionsetup{labelsep=period,font=small}
496   \captionsetup{font+=it}
497 \or
498   \captionsetup{labelsep=period,font=small,labelfont=sc}
499 \or
500   \captionsetup{labelsep=period,font=small}
501   \captionsetup{font+=sf}
502 \fi
503 }
```

6.7.5 Marginal notes

```
504 \define@choicekey{}{marginpar}[\val\nr]
505   {true,false}[true]{%
506 \ifcase\nr\relax
507 \or
508   \renewcommand\marginpar[2][]{}
509 \fi}
```

6.7.6 Table of contents

```
510 \define@choicekey{}{tocstyle}[\val\nr]{%
511   standard,dotted,ragged,leftpage}[standard]{%
512 \ifcase\nr\relax
513   \def\SUF@titlerule{\titlerule*{}}
514   \def\SUF@chaptitlerule{\titlerule*{}}
515 \or
516 \suftesi@dottedtoctrue
517   \def\SUF@titlerule{\titlerule*{\footnotesize .\ }}
518   \def\SUF@chaptitlerule{\titlerule*{}}
519 \or
520 \suftesi@raggedtoctrue
521   \def\SUF@titlerule{\hspace{1em}}
522   \def\SUF@chaptitlerule{\hspace{1em}}
523 \or
524 \suftesi@pagelefttoctrue
525 \fi}
526 \define@choicekey{}{twocolcontents}[\val\nr]{%
527   toc,lof,lot,toclof,toclot,loflot,all}[all]{%
528 \ifcase\nr\relax
529   \suftesi@twocolumnmtoctrue
530   \setkeys{}{tocstyle=ragged}
531 \or
532   \suftesi@twocolumnloftrue
533   \setkeys{}{tocstyle=ragged}
534 \or
535   \suftesi@twocolumnlottrue
536   \setkeys{}{tocstyle=ragged}
537 \or
538   \suftesi@twocolumnmtoctrue
539   \suftesi@twocolumnloftrue
540   \setkeys{}{tocstyle=ragged}
541 \or
542   \suftesi@twocolumnmtoctrue
543   \suftesi@twocolumnlottrue
544   \setkeys{}{tocstyle=ragged}}
```

```

545 \or
546   \suftesi@twocolumnloftrue
547   \suftesi@twocolumnlottrue
548   \setkeys{}{tocstyle=ragged}
549 \or
550   \suftesi@twocolumnmtotrue
551   \suftesi@twocolumnloftrue
552   \suftesi@twocolumnlottrue
553   \setkeys{}{tocstyle=ragged}
554 \fi
555 }

```

6.8 Fonts

6.8.1 Roman fonts

```

556 \define@choicekey{}{defaultfont}[\val\nr]{%
557   palatino,standard}[palatino]{%
558 \ifcase\nr\relax
559 \or
560   \suftesi@standardfonttrue
561 \def\SUF@greekfamily{lmr}
562 \fi}

```

6.8.2 Greek fonts

```

563 \define@choicekey{}{greekfont}[\val\nr]{%
564   artemisia,porson,cbgreek}[artemisia]{%
565 \ifcase\nr\relax
566 \def\SUF@greekfamily{artemisiaeuler}
567 \or
568 \def\SUF@greekfamily{porson}
569 \suftesi@porsontrue
570 \or
571 \def\SUF@greekfamily{lmr}
572 \fi}

```

6.9 Other options

6.9.1 \parindent

```

573 \define@choicekey{}{parindent}[\val\nr]
574   {compact,wide}[compact]{%
575 \ifcase\nr\relax
576 \setlength\parindent{1em}
577 \or
578 \setlength\parindent{1.5em}
579 \fi}

```

6.9.2 Part page

```

580 \define@choicekey{}{partpage}[\val\nr]{true,false}[true]{%
581 \ifcase\nr\relax
582   \suftesi@partpagetrue
583 \or
584   \relax
585 \fi}

```

6.9.3 Crop marks

```

586 \define@choicekey{}{crop}[\val\nr]
587   {true,false}[true]{%
588 \ifcase\nr\relax
589 \or
590   \suftesi@nocropttrue
591 \fi}

```

6.9.4 Draftdate

```

592 \define@choicekey{}{draftdate}[\val\nr]
593   {true,false}[true]{%
594 \ifcase\nr\relax

```

```

595 \suftesi@draftdatetrue
596 \or
597 \fi}

```

6.9.5 View mode

```

598 \define@choicekey{}{version}[\val\nr]
599   {screen,draft,final}[draft]{%
600 \ifcase\nr\relax
601   \suftesi@nocroptrue
602   \geometry{hmarginratio=1:1}
603   \newcommand*\crop[1][]{}
604 \or
605 \or
606   \AtBeginDocument{\crop[off]}
607 \fi}

```

6.9.6 Titlepage

```

608 \define@choicekey{}{titlepage}[\val\nr]
609   {true,false}[true]{%
610 \ifcase\nr\relax
611   \titlepagetrue
612 \or
613   \titlepagefalse
614 \fi}

```

6.9.7 Pre-defined styles

```

615 \define@choicekey{}{style}[\val\nr]
616   {roman1,roman2,roman3,roman4,roman5,roman6,
617   italic1,italic2,italic3,italic4,italic5,italic6,
618   italic7,italic8,italic9,italic10,italic11,italic12,
619   smallcaps1,smallcaps2,smallcaps3,smallcaps4,smallcaps5,smallcaps6,
620   smallcaps7,smallcaps8,smallcaps9,smallcaps10,smallcaps11,smallcaps12,
621   elements,sufelements,FSPLa,FSPLb,FSPLc}
622   [roman1]{%
623 \ifcase\nr\relax

```

The 'roman' styles:

```

624   \setkeys{}{chapstyle=left}
625 \or
626   \setkeys{}{chapstyle=center}
627 \or
628   \setkeys{}{chapstyle=right}
629 \or
630   \setkeys{}{chapstyle=parleft}
631 \or
632   \setkeys{}{chapstyle=parcenter}
633 \or
634   \setkeys{}{chapstyle=parright}
635 \or

```

The 'italic' styles:

```

636   \setkeys{}{
637   chapstyle=left,
638   chapfont=italic,
639   headerfont=italic}
640 \or
641   \setkeys{}{
642   chapstyle=center,
643   chapfont=italic,
644   headerfont=italic}
645 \or
646   \setkeys{}{
647   chapstyle=right,
648   chapfont=italic,
649   headerfont=italic}
650 \or
651   \setkeys{}{

```

```
652 chapstyle=parleft,
653 chapfont=italic,
654 headerfont=italic}
655 \or
656 \setkeys{}{
657 chapstyle=parcenter,
658 chapfont=italic,
659 headerfont=italic}
660 \or
661 \setkeys{}{
662 chapstyle=parright,
663 chapfont=italic,
664 headerfont=italic}
665 \or
666 \setkeys{}{
667 chapstyle=left,
668 chapfont=italic,
669 secfont=smallcaps,
670 headerfont=italic}
671 \or
672 \setkeys{}{
673 chapstyle=center,
674 chapfont=italic,
675 secfont=smallcaps,
676 headerfont=italic}
677 \or
678 \setkeys{}{
679 chapstyle=right,
680 chapfont=italic,
681 secfont=smallcaps,
682 headerfont=italic}
683 \or
684 \setkeys{}{
685 chapstyle=parleft,
686 chapfont=italic,
687 secfont=smallcaps,
688 headerfont=italic}
689 \or
690 \setkeys{}{
691 chapstyle=parcenter,
692 chapfont=italic,
693 secfont=smallcaps,
694 headerfont=italic}
695 \or
696 \setkeys{}{
697 chapstyle=parright,
698 chapfont=italic,
699 secfont=smallcaps,
700 headerfont=italic}
701 \or
The 'smallcaps' styles:
702 \setkeys{}{
703 chapstyle=left,
704 chapfont=smallcaps,
705 headerfont=smallcaps}
706 \or
707 \setkeys{}{
708 chapstyle=center,
709 chapfont=smallcaps,
710 headerfont=smallcaps}
711 \or
712 \setkeys{}{
713 chapstyle=right,
714 chapfont=smallcaps,
715 headerfont=smallcaps}
716 \or
```

```

717 \setkeys{}{
718   chapstyle=parleft,
719   chapfont=smallcaps,
720   headerfont=smallcaps}
721 \or
722 \setkeys{}{
723   chapstyle=parcenter,
724   chapfont=smallcaps,
725   headerfont=smallcaps}
726 \or
727 \setkeys{}{
728   chapstyle=parright,
729   chapfont=smallcaps,
730   headerfont=smallcaps}
731 \or
732 \setkeys{}{
733   chapstyle=left,
734   chapfont=smallcaps,
735   secfont=smallcaps,
736   headerfont=smallcaps}
737 \or
738 \setkeys{}{
739   chapstyle=center,
740   chapfont=smallcaps,
741   secfont=smallcaps,
742   headerfont=smallcaps}
743 \or
744 \setkeys{}{
745   chapstyle=right,
746   chapfont=smallcaps,
747   secfont=smallcaps,
748   headerfont=smallcaps}
749 \or
750 \setkeys{}{
751   chapstyle=parleft,
752   chapfont=smallcaps,
753   secfont=smallcaps,
754   headerfont=smallcaps}
755 \or
756 \setkeys{}{
757   chapstyle=parcenter,
758   chapfont=smallcaps,
759   secfont=smallcaps,
760   headerfont=smallcaps}
761 \or
762 \setkeys{}{
763   chapstyle=parright,
764   chapfont=smallcaps,
765   secfont=smallcaps,
766   headerfont=smallcaps}
767 \or
The 'elements' style:
768 \setkeys{}{
769   pagelayout=elements,
770   headerstyle=elements,
771   chapstyle=elements,
772   secfont=smallcaps,
773   subsecfont=italic,
774   captionstyle=elements}
775 \disable@keys{}
776 {pagelayout,headerstyle,chapstyle,secfont,subsecfont,captionstyle}
777 \or
The 'sufelements' style:
778 \setkeys{}{
779   chapstyle=elements,
780   headerfont=smallcaps,

```

```

781     secfont=smallcaps,
782     subsecfont=italic}
783 \disable@keys{}
784   {headerstyle,chapstyle,secfont,subsecfont}
785 \or

The FSPLa style:
786 \suftesi@periodicalaureottrue
787 \suftesi@FSPLtrue
788   \setkeys{}{%
789     pagelayout=periodicalaureo,
790     style=roman5,
791     chapnumstyle=roman,
792     headerstyle=inner,
793     footnotestyle=hung,
794     liststyle=indented,
795     tocstyle=leftpage}
796 \disable@keys{}

797 {documentstructure,pagelayout,partfont,chapfont,secfont,%
798 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
799 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
800 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
801 quotesize,footnotestyle,liststyle,captionstyle,parindent}
802 \or

The FSPLb style:
803 \suftesi@periodicalaureottrue
804 \suftesi@FSPLtrue
805   \setkeys{}{%
806     pagelayout=periodicalaureo,
807     style=italic5,
808     chapnumstyle=roman,
809     headerstyle=inner,
810     headerfont=italic,
811     footnotestyle=hung,
812     liststyle=indented,
813     tocstyle=leftpage}
814 \disable@keys{}

815 {documentstructure,pagelayout,partfont,chapfont,secfont,%
816 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
817 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
818 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
819 quotesize,footnotestyle,liststyle,captionstyle,parindent}
820 \or

The FSPLc style:
821 \suftesi@periodicalaureottrue
822 \suftesi@FSPLtrue
823   \setkeys{}{%
824     pagelayout=periodicalaureo,
825     style=smallcaps5,
826     chapnumstyle=roman,
827     headerstyle=inner,
828     headerfont=smallcaps,
829     secfont=smallcaps,
830     footnotestyle=hung,
831     liststyle=indented,
832     tocstyle=leftpage}
833 \disable@keys{}

834 {documentstructure,pagelayout,partfont,chapfont,secfont,%
835 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
836 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
837 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
838 quotesize,footnotestyle,liststyle,captionstyle,parindent}
839 \fi}

840 % EXPERIMENTAL
841 \define@choicekey{}{papertitlestyle}[\val\nr]{%
842   left,center,right}[left]{%
```

```
843 \ifcase\nr\relax
844   \def\SUF@lr@coll@titleSwitch{\filright}
845 \or
846   \def\SUF@lr@coll@titleSwitch{\filcenter}
847 \or
848   \def\SUF@lr@coll@titleSwitch{\filleft}
849 \fi}
850 \define@choicekey{}{revauthortitle}[\val\nr]
851   {true,false}[false]{%
852 \ifcase\nr\relax
853   \suftesi@reverseauthortitletrue
854 \or\relax
855 \fi}
856 \define@choicekey{}{titlefont}[\val\nr]{roman,italic,smallcaps}[roman]{%
857 \ifcase\nr\relax
858 \def\SUF@titlefont@Switch{\relax}
859 \or
860 \def\SUF@titlefont@Switch{\itshape}
861 \or
862 \def\SUF@titlefont@Switch{\expandafter\SUF@titlesmallcaps}
863 \fi}
864
865 \define@choicekey{}{authorfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
866 \ifcase\nr\relax
867 \def\SUF@authorfont@Switch{\relax}
868 \or
869 \def\SUF@authorfont@Switch{\itshape}
870 \or
871 \def\SUF@authorfont@Switch{\expandafter\SUF@titlesmallcaps}
872 \fi}
Execute and process options:
873 \ExecuteOptionsX<>{
874   captionstyle=standard,
875   marginpar=true,
876   parindent=compact,
877   tocstyle=standard,
878   greekfont=artemisia,
879   pagelayout=standard,
880   headerstyle=inner,
881   liststyle=bulged,
882   footnotestyle=bulged,
883   quotesize=footnotesize,
884   quotestyle=center,
885   partstyle=left,
886   chapstyle=left,
887   secstyle=left,
888   subsecstyle=left,
889   subsubsecstyle=left,
890   partfont=roman,
891   chapfont=roman,
892   secfont=italic,
893   subsecfont=roman,
894   subsubsecfont=roman,
895   headerfont=roman,
896   secnumstyle=arabic,
897   partnumstyle=Roman,
898   chapnumstyle=arabic,
899   smallcapsstyle=low,
900   titlefont=italic,
901   authorfont=roman,
902   revauthortitle=false,
903   papertitlestyle=left,
904   authorfont=roman,
905   titlefont=italic}
906 \ProcessOptionsX<>\relax
```

The use of the `\XKV@useoption` command, provided by the `xkeyval`, is a trick to delete the option given as its argument from the list stored in `\@unusedoptionlist` so that the option will not produce the “Unused global options” message:

```

907 \XKV@useoption{a4paper}    \XKV@useoption{10pt}
908 \XKV@useoption{11pt}        \XKV@useoption{12pt}
909 \XKV@useoption{oneside}     \XKV@useoption{twoside}
910 \XKV@useoption{onecolumn}   \XKV@useoption{twocolumn}
911 \XKV@useoption{titlepage}   \XKV@useoption{notitlepage}
912 \XKV@useoption{openright}   \XKV@useoption{openany}
913 \XKV@useoption{leqno}       \XKV@useoption{fleqn}
914 \XKV@useoption{a5paper}     \XKV@useoption{b5paper}
915 \XKV@useoption{legalpaper}\XKV@useoption{executivepaper}
916 \XKV@useoption{landscape}
```

A trick to delete the class options from `\XKV@classoptionslist`, in order to avoid incompatibility with packages using options defined by `suftesi` too. Thanks to Enrico Gregorio!

```
917 \def\XKV@classoptionslist{}
```

6.10 Basic packages

```

918 \RequirePackage{color}
919     \definecolor{sufred}{rgb}{0.5,0,0}
920     \definecolor{sufgray}{rgb}{0.5,0.5,0.5}
921 \RequirePackage{multicol}
922 \RequirePackage{emptypage}
923 \RequirePackage{textcase}
924 \RequirePackage{ifxetex}
925 \RequirePackage[final]{microtype}
926 \SetTracking
927     [ name      = default,
928       no ligatures = {f} ]
929     { encoding   = {OT1,T1,T2A,LY1,OT4,QX,EU2} }
930     { 110 }
931 \newcommand{\versionstring}[1]{\def\version@string{#1}}
932 \versionstring{Version of}
```

The FSPL style requires a verbose colophon which uses specific icons:

```

933 \ifsuftesi@FSPL
934     \RequirePackage{cclicenses}
935 \else
936 \fi
```

6.11 Greek fonts

Thanks to Claudio Beccari and Enrico Gregorio for these macros:

```

937 \ifxetex
938 \AtBeginDocument{
939 \@ifpackageloaded{fontspec}
940     {\relax}
941     {\ClassError{suftesi}
942         {*****\MessageBreak
943          * For using suftesi with XeLaTeX\MessageBreak
944          * load either 'fontspec' or 'mathspec'\MessageBreak
945          *****}
946         {*****\MessageBreak
947          * For using suftesi with XeLaTeX\MessageBreak
948          * load either 'fontspec' or 'mathspec'\MessageBreak
949          *****}}
950     }
951 \else
952 \RequirePackage[LGR,T1]{fontenc}
953 \RequirePackage{substitutefont}
954 \AtBeginDocument{\fontencoding{T1}\selectfont}
955 \ifsuftesi@standardfont
956     \RequirePackage{lmodern}
957     \relax
958 \else
959     \RequirePackage[osf,sc]{mathpazo}
960     \RequirePackage[scaled=0.8]{beramono}
```

```

961         \renewcommand{\sfdefault}{iwona}
962 \AtBeginDocument{
963 \substitutefont{LGR}{\rmdefault}{\SUF@greekfamily}
964 \DeclareRobustCommand{\greektext}{%
965   \usefont{LGR}{\SUF@greekfamily}{\f@series}{\f@shape}}
966 \def\encodingdefault{LGR}
967 \DeclareTextFontCommand{\textgreek}{\greektext}
968 }
969 \fi

Scale the Porson font:

970 \ifsuftesi@porson
971 \sbox{z@\fontsize{10}{10}\normalfont A}
972 \sbox{tw@\font\temp=gporsonrg6a at 10pt \temp A}
973 \dimen@=\dimexpr \p@*\ht{z@}/\ht{tw@}\relax
974 \sbox{z@\normalfont\fontsize{10}{10}\selectfont a}
975 \sbox{tw@\font\temp=gporsonrg6a at 10pt \temp a}
976 \dimen2=\dimexpr \p@*\ht{z@}/\ht{tw@}\relax
977 \dimen4= 0.6\p@
978 \dimen@=\dimexpr \dimen@ - \dimen4*\dimen@/\p@+\dimen4*\dimen2/\p@\relax
979 \edef\art@scale{\strip@pt\dimen@}
980 \DeclareFontFamily{LGR}{porson}{}
981 \DeclareFontShape{LGR}{porson}{m}{n}  {<- s * [\art@scale] gporsonrg6a}{}
982 \DeclareFontShape{LGR}{porson}{m}{it} {<- ssub * porson/m/n}{}
983 \DeclareFontShape{LGR}{porson}{b}{n}  {<- ssub * porson/m/n}{}
984 \DeclareFontShape{LGR}{porson}{b}{it} {<- ssub * porson/m/n}{}
985 \DeclareFontShape{LGR}{porson}{m}{sl} {<- ssub * porson/m/n}{}
986 \DeclareFontShape{LGR}{porson}{b}{sl} {<- ssub * porson/m/n}{}
987 \DeclareFontShape{LGR}{porson}{m}{sc} {<- ssub * porson/m/n}{}
988 \DeclareFontShape{LGR}{porson}{bx}{n} {<- ssub * porson/m/n}{}
989 \DeclareFontShape{LGR}{porson}{bx}{it} {<- ssub * porson/m/n}{}
990 \DeclareFontShape{LGR}{porson}{bx}{sl} {<- ssub * porson/m/n}{}
991   \fi
992 \fi

```

6.12 Page layout

```

993 \ifsuftesi@nocrop
994   \relax
995   \else
996   \RequirePackage[a4,cam,center]{crop}
997 \fi

```

A trick to produce one-side documents:

```

998 \if@twoside
999   \relax
1000   \else
1001   \geometry{hmarginratio=1:1}
1002 \fi

```

6.13 Section titles

```

1003 \RequirePackage{titlesec}
1004   \newlength{\sectionsep}
1005   \setlength{\sectionsep}{\dimexpr(\baselineskip) plus 1pt minus 1pt}
1006 \ifxetex
1007   \DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1008     \addfontfeature{LetterSpace=6}\scshape\suftesi@MakeTextLowercase{#1}}
1009   \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1010     \addfontfeature{LetterSpace=6}\scshape\suftesi@MakeTextLowercase{#1}}
1011   \newcommand{\chapnumfont}[1]{%
1012     \def\SUF@chapnumfont{#1}}
1013   \chapnumfont{\relax}%
1014 \else
1015   \DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1016     \scshape\suftesi@MakeTextLowercase{\lsstyle #1}}%
1017   \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1018     \scshape\suftesi@MakeTextLowercase{\lsstyle #1}}%

```

```

1019 \newcommand{\chapnumfont}[1]{%
1020   \def\SUF@chapnumfont{\fontfamily{#1}}%
1021   \chapnumfont{pplj}%
1022 \fi

```

The elements style

```

1023 \define@key[SUF]{elements}{chapsize}[90]{%
1024   \def\cmdSUF@elements@chapsize{\fontsize{#1}{#1}\selectfont}%
1025 \define@key[SUF]{elements}{chapposition}[-83]{%
1026   \def\cmdSUF@elements@chapposition{#1}%

```

The chapter for elements style:

```

1027 \def\SUF@elements@CHAPTER{%
1028   \titleformat{\chapter}[block]%
1029     {\Large}%
1030     {\begin{picture}(0,0)%
1031       \setlength{\unitlength}{1pt}%
1032       \SUF@chapnumfont%
1033       \cmdSUF@elements@chapsize%
1034       \put(0,\cmdSUF@elements@chapposition){%%
1035         \hskip\dimexpr(\textwidth+0.9\marginparsep)%
1036         \textcolor{sufgray}{\SUF@thechapter}}%
1037     \end{picture}}%
1038   {0pt}%
1039   {\SUF@titlesmallcaps}%
1040   [\vspace*{-6pt}\rule{\textwidth}{.1pt}]%
1041 }

```

The sections for elements style:

```

1042 \def\SUF@elements@SECTIONS{%
1043   \titleformat{\section}[block]%
1044     {\extramarks{}{}\filright}%
1045     {\textnormal\thesection}%
1046     {1em}%
1047     {\SUF@titlesmallcaps}%
1048   \titlespacing*\section{0em}{1em}{1em}[0em]%
1049   \titleformat{\subsection}[block]%
1050     {\filright\normalsize\itshape}%
1051     {\textnormal\thesubsection}%
1052     {1em}%
1053     {}%
1054   \titlespacing*\subsection{0em}{\baselineskip}{\baselineskip}[0em]%
1055   \titleformat{\subsubsection}[block]%
1056     {\filright\normalsize}%
1057     {\textnormal\thesubsubsection}%
1058     {1em}%
1059     {}%
1060   \titlespacing*\subsubsection{0em}{\baselineskip}{\baselineskip}[0em]%
1061 }

```

\chapter Default styles:

```

1062 \newlength\SUF@ADJnumparchap
1063 \def\SUF@default@CHAPTER{%
1064   \ifsuftesi@numparchap
1065     \titleformat{\chapter}[display]%
1066       {\SUF@chaptersize\SUF@lr@CHAPSwitch}%
1067       {\SUF@thechapter\SUF@dotchap}%
1068       {2ex}%
1069       {\SUF@CHAP@StyleSwitch}%
1070   \else
1071     \titleformat{\chapter}[hang]%
1072       {\SUF@chaptersize\SUF@lr@CHAPSwitch}%
1073       {\SUF@thechapter\SUF@dotchap}%
1074       {3em}%
1075       {\SUF@CHAP@StyleSwitch}%
1076   \fi
1077   \ifsuftesi@numparchap
1078     \setlength{\SUF@ADJnumparchap}{-2.5\baselineskip}%

```

```

1079      \else
1080      \setlength{\SUF@ADJnumparchap}{0pt}
1081      \fi}

\section
1082 \def\SUF@default@SECTIONS{
1083 \ifsuftesi@numparsec
1084 \titleformat{\section}[display]
1085   {\SUF@lr@SECSwitch}
1086   {\ifsuftesi@article\SUF@thesection
1087     \else\thesection\fi\SUF@dotsec}
1088   {0ex}
1089   {\SUF@SEC@StyleSwitch}
1090 \titlespacing*{\section}{0em}{\sectionsep}{\sectionsep}[0em]
1091 \else
1092 \titleformat{\section}[hang]
1093   {\SUF@lr@SECSwitch}
1094   {\ifsuftesi@article\SUF@thesection
1095     \else\thesection\fi\SUF@dotsec}
1096   {1em}
1097   {\SUF@SEC@StyleSwitch}
1098 \titlespacing*{\section}{0ex}{\sectionsep}{\sectionsep}[0ex]
1099 \fi

\subsection
1100 \ifsuftesi@numparsubsec
1101 \titleformat{\subsection}[display]
1102   {\SUF@lr@SUBSECSwitch}
1103   {\textnormal\thesubsection}
1104   {0ex}
1105   {\SUF@SUBSEC@StyleSwitch}
1106 \titlespacing*{\subsection}{0em}{\sectionsep}{\sectionsep}[0em]
1107 \else
1108 \titleformat{\subsection}[hang]
1109   {\SUF@lr@SUBSECSwitch}
1110   {\textnormal\thesubsection}
1111   {1em}
1112   {\SUF@SUBSEC@StyleSwitch}
1113 \titlespacing*{\subsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1114 \fi

\subsubsection
1115 \ifsuftesi@numparsubsubsec
1116 \titleformat{\subsubsection}[display]
1117   {\SUF@lr@SUBSUBSECSwitch}
1118   {\textnormal\thesubsubsection}
1119   {0ex}
1120   {\SUF@SUBSUBSEC@StyleSwitch}
1121 \titlespacing*{\subsubsection}{0em}{\sectionsep}{\sectionsep}[0em]
1122 \else
1123 \titleformat{\subsubsection}[hang]
1124   {\SUF@lr@SUBSUBSECSwitch}
1125   {\textnormal\thesubsubsection}
1126   {1em}
1127   {\SUF@SUBSUBSEC@StyleSwitch}
1128 \titlespacing*{\subsubsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1129 \fi
1130 }

1131 \ifsuftesi@elementschap
1132 \RequirePackage{extramarks}
1133   \SUF@elements@CHAPTER
1134   \SUF@elements@SECTIONS
1135 \ifsuftesi@periodical
1136   \titlespacing*{\chapter}{0em}{-\baselineskip}{10pt}[0pt]
1137   \setkeys[SUF]{elements}{chapsize=80, chapposition=-83}
1138 \else
1139 \ifsuftesi@periodicalaureo

```

```

1140 \titlespacing*\{chapter\}{0em}{-\baselineskip}{10pt}[0pt]
1141   \setkeys[SUF]{elements}{chapsize=80,chapposition=-83}
1142 \else
1143 \ifsuftesi@compact
1144   \titlespacing*\{chapter\}{0em}{-1\baselineskip}{10pt}[0pt]
1145   \setkeys[SUF]{elements}{chapsize=75,chapposition=-83}
1146 \else
1147 \ifsuftesi@compactaureo
1148   \titlespacing*\{chapter\}{0em}{-1\baselineskip}{10pt}[0pt]
1149   \setkeys[SUF]{elements}{chapsize=75,chapposition=-83}
1150 \else
1151 \ifsuftesi@supercompact
1152   \titlespacing*\{chapter\}{0em}{-1\baselineskip}{10pt}[0pt]
1153   \setkeys[SUF]{elements}{chapsize=70,chapposition=-73}
1154 \else
1155 \ifsuftesi@supercompactaureo
1156   \titlespacing*\{chapter\}{0em}{-1\baselineskip}{10pt}[0pt]
1157   \setkeys[SUF]{elements}{chapsize=70,chapposition=-73}
1158 \else
1159 \ifsuftesi@elementspagelayout
1160   \titlespacing*\{chapter\}{0em}{-\baselineskip}{10pt}[0pt]
1161   \setkeys[SUF]{elements}{chapsize=60,chapposition=-73}
1162 \else
1163   \titlespacing*\{chapter\}{0em}{-\baselineskip}{10pt}[0pt]
1164   \setkeys[SUF]{elements}{chapsize=90,chapposition=-83}
1165     \fi
1166     \fi
1167     \fi
1168     \fi
1169     \fi
1170   \fi
1171 \fi
1172 \else
1173   \SUF@default@CHAPTER
1174   \SUF@default@SECTIONS
1175 \ifsuftesi@periodicalaureo
1176   \titlespacing*\{chapter\}{0em}{0\SUF@ADJnumparchap}{18ex}
1177   \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1178 \else
1179 \ifsuftesi@periodical
1180   \titlespacing*\{chapter\}{0em}{\SUF@ADJnumparchap}{18ex}
1181   \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1182     \else
1183       \ifsuftesi@compact
1184         \titlespacing*\{chapter\}{0em}{\SUF@ADJnumparchap}{18ex}
1185         \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1186         \else
1187           \ifsuftesi@supercompact
1188             \titlespacing*\{chapter\}{0em}{\SUF@ADJnumparchap}{18ex}
1189             \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1190             \else
1191               \titlespacing*\{chapter\}{0em}{%
1192                 \dimexpr(6ex+\SUF@ADJnumparchap){18ex}
1193                 \titlespacing*\{name=\chapter, numberless\}{0em}{6ex}{18ex}
1194                 \fi
1195               \fi
1196             \fi
1197           \fi
1198 \fi

```

Redefinitions for ‘article’ mode

```

1199 \ifsuftesi@article
1200 \def\chapter{\ClassError{suftesi}
1201   {\noexpand\chapter level is undefined
1202    using 'documentstructure=article'}
1203   {\noexpand\chapter level is undefined

```

```

1204     using 'documentstructure=article'//}
1205 \setcounter{tocdepth}{3}
1206   \setcounter{secnumdepth}{3}
1207   \renewcommand\thesection{%
1208     \@arabic\c@section}
1209 \renewcommand\thesubsection{%
1210   \thesection.\@arabic\c@subsection}
1211 \renewcommand\thesubsubsection{%
1212   \thesubsection.\@arabic\c@subsubsection}
1213 \renewcommand\theparagraph{%
1214   \thesubsubsection.\@arabic\c@paragraph}
1215 \renewcommand\thesubparagraph{%
1216   \theparagraph.\@arabic\c@subparagraph}

```

The `\partpage` options allows you to print a standard part page in article mode.

```

1217 \ifsuftesi@partpage
1218   \relax
1219   \else

```

In article mode the `\part` command is similar to a `\section` but with more vertical space before and after.

```

1220 \titleclass{\part}{straight}
1221 \titlespacing*{\part}{0ex}{2\sectionsep}{2\sectionsep}[0ex]
1222 \fi
1223 \ifsuftesi@numparpart
1224 \titleformat{\part}[display]
1225 { \SUF@chaptersize \SUF@lr@PARTSwitch }
1226 { \SUF@PART@StyleSwitch \partname \hskip.5em \SUF@thepart \SUF@dotpart }
1227 {2ex}
1228 { \SUF@PART@StyleSwitch }
1229 \else
1230 \titleformat{\part}[hang]
1231 { \SUF@chaptersize \SUF@lr@PARTSwitch }
1232 { \SUF@PART@StyleSwitch \partname \hskip.5em \SUF@thepart \SUF@dotpart }
1233 {1em}
1234 { \SUF@PART@StyleSwitch }
1235 \fi
1236 \else

```

The default ‘book’ mode

```

1237 \ifsuftesi@numparpart
1238 \titleformat{\part}[display]
1239 { \SUF@chaptersize \SUF@lr@PARTSwitch }
1240 { \SUF@PART@StyleSwitch \partname \hskip.5em \SUF@thepart \SUF@dotpart }
1241 {2ex}
1242 { \SUF@PART@StyleSwitch }
1243 \else
1244 \titleformat{\part}[hang]
1245 { \SUF@chaptersize \SUF@lr@PARTSwitch }
1246 { \SUF@PART@StyleSwitch \partname \hskip.5em \SUF@thepart \SUF@dotpart }
1247 {1em}
1248 { \SUF@PART@StyleSwitch }
1249 \fi
1250 \fi
1251

```

`\paragraph`

```

1252 \titleformat{\paragraph}[runin]
1253 {}
1254 { \theparagraph }
1255 { .5em }
1256 { \itshape }
1257 [ { } \hskip*{1em} ]
1258 \titlespacing*{\paragraph}{\parindent}{.5\sectionsep}{.5\sectionsep}

```

`\subparagraph`

```

1259 \titleformat{\subparagraph}[runin]

```

```

1260  {}
1261  {\thesubparagraph}
1262  {.5em}
1263  {}
1264  [.{ }\hspace*{1em}]
1265 \titlespacing*{\subparagraph}{\parindent}{.5\sectionsep}{.5\sectionsep}

The biblatex package uses the book class definitions of bibliography and list of shorthands, so we must
redefine them according to the styles of suftesi, which does not use uppercase letters in the headings.

1266 \ifsuftesi@article
1267 \AtBeginDocument{%
1268 @ifpackageloading{biblatex}{%
1269   \defbibheading{bibliography}[\refname]{%
1270     \section*{#1}%
1271     \markboth{#1}{#1}%
1272   \defbibheading{shorthands}[\losname]{%
1273     \section*{#1}%
1274     \markboth{#1}{#1}%
1275   \defbibheading{bibintoc}[\refname]{%
1276     \section*{#1}%
1277     \addcontentsline{toc}{section}{#1}%
1278     \markboth{#1}{#1}%
1279   \defbibheading{losintoc}[\losname]{%
1280     \section*{#1}%
1281     \addcontentsline{toc}{section}{#1}%
1282     \markboth{#1}{#1}%
1283   \defbibheading{bibnumbered}[\refname]{%
1284     \section{#1}%
1285     \if@twoside\markright{#1}\fi%
1286   \defbibheading{losnumbered}[\losname]{%
1287     \section{#1}%
1288     \if@twoside\markright{#1}\fi%
1289   \defbibheading{subbibliography}[\refname]{%
1290     \subsection*{#1}%
1291   \defbibheading{subbibintoc}[\refname]{%
1292     \subsection*{#1}%
1293     \addcontentsline{toc}{subsection}{#1}%
1294   \defbibheading{subbibnumbered}[\refname]{%
1295     \subsection{#1}}%
1296     {\relax}%
1297 }%
1298 \else
1299 \AtBeginDocument{%
1300 @ifpackageloading{biblatex}{%
1301   \defbibheading{bibliography}[\bibname]{%
1302     \chapter*{#1}%
1303     \markboth{#1}{#1}%
1304   \defbibheading{shorthands}[\losname]{%
1305     \chapter*{#1}%
1306     \markboth{#1}{#1}%
1307   \defbibheading{bibintoc}[\bibname]{%
1308     \chapter*{#1}%
1309     \addcontentsline{toc}{chapter}{#1}%
1310     \markboth{#1}{#1}%
1311   \defbibheading{losintoc}[\losname]{%
1312     \chapter*{#1}%
1313     \addcontentsline{toc}{chapter}{#1}%
1314     \markboth{#1}{#1}%
1315   \defbibheading{bibnumbered}[\bibname]{%
1316     \chapter{#1}%
1317     \if@twoside\markright{#1}\fi%
1318   \defbibheading{losnumbered}[\losname]{%
1319     \chapter{#1}%
1320     \if@twoside\markright{#1}\fi%
1321   \defbibheading{subbibliography}[\refname]{%
1322     \section*{#1}%
1323     \if@twoside\markright{#1}\fi}

```

```

1324 \defbibheading{subbibintoc}{[\refname]{%
1325   \section*{\#1}%
1326   \addcontentsline{toc}{section}{\#1}%
1327   \if@twoside\markright{\#1}\fi%
1328 \defbibheading{subbibnumbered}{[\refname]{%
1329   \section{\#1}}%
1330   {\relax}%
1331 }%
1332 \fi

```

6.14 Title page

\title The new \title command has an optional argument which can be used in the headers.

```

1333 \renewcommand*{\title}[2][]{\gdef\@headtitle{\#1}\gdef\@title{\#2}%
1334   \edef\@title{\noexpand\@dblarg
1335   \expandafter\noexpand\csname\string\title\endcsname}
1336   \def\@headtitle{--missing title--%
1337     \protect\ClassWarningNoLine{suftesi}{%
1338       No \string\title\space given \MessageBreak%
1339       See the class documentation for explanation}}}
1340 \def\@title{--missing title--%
1341   \protect\ClassWarningNoLine{suftesi}{%
1342     No \string\title\space given\MessageBreak%
1343     See the class documentation for explanation}}}
1344 \def\@author{--missing author--%
1345   \protect\ClassWarningNoLine{suftesi}{%
1346     No \string\author\space given\MessageBreak%
1347     See the class documentation for explanation}}}

```

\maketitle For titlepage (default) option:

```

1348 \if@titlepage% titlepage
1349   \renewcommand\maketitle{\begin{titlepage}%
1350   \let\footnotesize\small
1351   \let\footnoterule\relax
1352   \let\footnote\thanks
1353   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1354   \null\vfil
1355   \vskip 60\p@
1356   \begin{center}%
1357     {\SUF@chaptersize\color{sufred}\sffamily%
1358     \ifsuftesi@smallcapschap%
1359       \SUF@titlesmallcaps{\@title}%
1360     \else
1361       \ifsuftesi@article%
1362         \ifsuftesi@smallcapssec%
1363           \SUF@titlesmallcaps{\@title}%
1364         \else
1365           \@title
1366         \fi
1367       \else
1368         \@title
1369       \fi
1370     \fi\par}%
1371   \vskip 3em%
1372   {\small\lineskip .75em%
1373     \begin{tabular}[t]{c}%
1374       \@author
1375     \end{tabular}\par}%
1376   \vskip 1.5em%
1377   {\small\@date\par}%
1378   \end{center}\par
1379   \thanks
1380   \vfil\null
1381   \end{titlepage}%
1382   \setcounter{footnote}{0}%
1383   \global\let\thanks\relax

```

```

1384 \global\let\maketitle\relax
1385 \global\let\@thanks\empty
1386   \global\let\@date\empty
1387 \global\let\date\relax
1388 \global\let\and\relax

```

\standardtitle Reproduces the standard \maketitle style:

```

1389 \newcommand\standardtitle{\begin{titlepage}%
1390   \let\footnotesize\small
1391   \let\footnoterule\relax
1392   \let\footnote\thanks
1393   \null\vfil
1394   \vskip 60\p@
1395   \begin{center}%
1396     {\LARGE \@title \par}%
1397     \vskip 3em%
1398     {\large
1399       \lineskip .75em%
1400       \begin{tabular}[t]{c}%
1401         \author
1402       \end{tabular}\par}%
1403     \vskip 1.5em%
1404     {\large \@date \par}%
1405   \end{center}\par
1406   \thanks
1407   \vfild\null
1408 \end{titlepage}%
1409 \setcounter{footnote}{0}%
1410 \global\let\thanks\relax
1411 \global\let\maketitle\relax
1412 \global\let\@thanks\empty
1413 \global\let\@date\empty
1414 \global\let\date\relax
1415 \global\let\and\relax
1416 \else

```

\maketitle For notitlepage option:

```

1417 \renewcommand\maketitlef\par
1418   \begingroup
1419     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1420     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1421     \long\def\@makefntext{\parindent 1em\noindent
1422       \hb@xt@1.8em{%
1423         \hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
1424     \if@twocolumn
1425       \ifnum \col@number=\@ne
1426         \@maketitle
1427       \else
1428         \twocolumn[\@maketitle]%
1429       \fi
1430     \else
1431       \newpage
1432       \global\@topnum\z@% Prevents figures from going at top of page.
1433       \@maketitle
1434     \fi
1435     \thispagestyle{plain}\@thanks
1436   \endgroup
1437   \setcounter{footnote}{0}%
1438   \global\let\thanks\relax
1439   \global\let\maketitle\relax
1440   \global\let\@maketitle\relax
1441   \global\let\@thanks\empty
1442   \global\let\@date\empty
1443   \global\let\date\relax
1444   \global\let\and\relax
1445   \def\@maketitle{%
1446     \newpage

```

```

1447 \null
1448 \vskip 2em%
1449 \begin{center}%
1450 \let \footnote \thanks
1451 {\SUF@chaptersize\color{sufred}\sffamily%
1452 \ifsuftesi@smallcapschap%
1453 \SUF@titlesmallcaps{\@title}%
1454 \else
1455 \ifsuftesi@article
1456 \ifsuftesi@smallcapssec%
1457 \SUF@titlesmallcaps{\@title}%
1458 \else
1459 \@title
1460 \fi
1461 \else
1462 \@title
1463 \fi
1464 \fi\par}%
1465 \vskip 1.5em%
1466 {\small\lineskip .5em%
1467 \begin{tabular}[t]{c}%
1468 \author\par
1469 \end{tabular}\par}%
1470 \vskip 1em%
1471 {\small\@date\par}%
1472 \end{center}%
1473 \par
1474 \vskip 1.5em}

```

\standardtitle Reproduces the standard \maketitle style:

```

1475 \newcommand\standardtitle{\par
1476 \begingroup
1477 \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1478 \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1479 \long\def\@makefntext##1{\parindent 1em\noindent
1480 \hb@xt@1.8em{%
1481 \hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
1482 \if@twocolumn
1483 \ifnum \col@number=\@ne
1484 \@standardmaketitle
1485 \else
1486 \twocolumn[\@standardmaketitle]%
1487 \fi
1488 \else
1489 \newpage
1490 \global\@topnum\z@
1491 \@standardmaketitle
1492 \fi
1493 \thispagestyle{plain}\@thanks
1494 \endgroup
1495 \setcounter{footnote}{0}%
1496 \global\let\thanks\relax
1497 \global\let\maketitle\relax
1498 \global\let\@standardmaketitle\relax
1499 \global\let\@thanks\@empty
1500 \global\let\@date\@empty
1501 \global\let\date\relax
1502 \global\let\and\relax}
1503 \def\@standardmaketitle{%
1504 \newpage
1505 \null
1506 \vskip 2em%
1507 \begin{center}%
1508 \let \footnote \thanks
1509 {\LARGE \@title \par}%
1510 \vskip 1.5em%
1511 \large

```

```

1512      \lineskip .5em%
1513      \begin{tabular}[t]{c}%
1514          \author
1515      \end{tabular}\par}%
1516      \vskip 1em%
1517      {\large \@date}%
1518  \end{center}%
1519  \par
1520  \vskip 1.5em}
1521 \fi

6.15 The collection document structure

1522 \ifsuftesi@collection
1523 \newcounter{journalnumber}
1524 \newcounter{journalvolume}
1525 \newcounter{issue}
1526 \newcounter{title}
1527 \setcounter{title}{1}
1528 \setcounter{journalnumber}{0}
1529 \setcounter{tocdepth}{0}
1530 \def\journalname#1{\gdef\@journalname{#1}}
1531 \def\@journalname{\@latex@warning@no@line{%
1532     No \noexpand\journalname given}}
1533 \def\issn#1{\gdef\@issn{#1}}
1534 \def\@issn{\@latex@warning@no@line{%
1535     No \noexpand\issn given}}
1536 \def\doi#1{\gdef\@doi{#1}}
1537 \def\@doi{\@latex@warning@no@line{%
1538     No \noexpand\doi given}}
1539 \def\journalvolume#1{\gdef\@journalvolume{#1}}
1540 \def\@journalvolume{\@latex@warning@no@line{%
1541     No \noexpand\journalvolume given}}
1542 \def\journalnumber#1{\gdef\@journalnumber{#1}}
1543 \def\@journalnumber{\@latex@warning@no@line{%
1544     No \noexpand\journalnumber given}}
1545 \def\issue#1{\gdef\@issue{#1}}
1546 \def\@issue{\@latex@warning@no@line{%
1547     No \noexpand\issue given}}
1548 \def\journalyear#1{\gdef\@journalyear{#1}}
1549 \def\@journalyear{\@latex@warning@no@line{%
1550     No \noexpand\journalyear given}}
1551 \def\journalwebsite#1{\gdef\@journalwebsite{\url{#1}}}
1552 \def\@journalwebsite{\@latex@warning@no@line{%
1553     No \noexpand\journalwebsite given}}
1554 \def\thanks#1{\footnotemark\ \protected@xdef\@thanks{%
1555     \@thanks\protect\footnotetext[\the\c@footnote]{#1}}}
1556 \def\fulljournal{\emph{\@journalname} \@journalnumber, %
1557     \@issue{} \@journalyear}
1558 \def\issuename#1{\gdef\@issuename{#1}}
1559 \def\collectiontitle#1{\gdef\@collectiontitle{#1}}
1560 \def\@collectiontitle{\@latex@warning@no@line{%
1561     No \noexpand\collectiontitle given}}
1562 \def\collectioneditor#1{\gdef\@collectioneditor{#1}}
1563 \def\@collectioneditor{\@latex@warning@no@line{%
1564     No \noexpand\collectioneditor given}}


\l@title
1565 \newcommand*\l@title[2]{%
1566     \ifnum \c@tocdepth >\m@ne
1567         \addpenalty{-\highpenalty}%
1568         \vskip 1.0ex \oplus\p@
1569         \begingroup
1570             \parindent \z@ \rightskip \pnumwidth
1571             \parfillskip -\pnumwidth
1572             \advance\leftskip1em
1573             \hskip -\leftskip

```

```

1574      #1\nobreak%
1575  \ifsuftesi@dottedtoc@dotfill%
1576    \nobreak\hb@xt@0ptnumwidth{\hss #2}\par
1577    \else
1578      \ifsuftesi@raggedtoc%
1579        \nobreak\hskip1em #2 \hfill\null\par
1580        \else
1581          \ifsuftesi@pagelefttoc
1582            \ClassError{suftesi}
1583              {\MessageBreak
1584                You can not use tocstyle=leftpage\MessageBreak
1585                  with documentstructure=collection}
1586                {You can not use tocstyle=leftpage\MessageBreak
1587                  with documentstructure=collection}
1588        \else
1589          \nobreak\hfill #2\par
1590        \fi
1591      \fi
1592    \fi
1593    \penalty\@highpenalty
1594  \endgroup
1595 \fi}

\maketitle
@maketitle 1596 \renewcommand\maketitle{\par
1597   \begingroup
1598     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1599     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1600     \long\def\@makefntext##1{\parindent 1em\noindent
1601       \hb@xt@1.8em{%
1602         \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
1603       \if@twocolumn
1604         \ifnum \col@number=\@ne
1605           \@maketitle
1606         \else
1607           \twocolumn[\@maketitle]%
1608         \fi
1609       \else
1610         \newpage
1611         \global\@topnum\z@
1612         \@maketitle
1613       \fi
1614       \thispagestyle{plain}\@thanks
1615     \endgroup
1616     \setcounter{footnote}{0}%
1617     \global\let\@thanks\empty
1618     \let\thanks\@gobble}
1619 \def\@maketitle{%
1620   \cleardoublepage
1621   \SUF@chaptersize
1622   \SUF@lr@coll@titleSwitch
1623   \let\footnote\thanks
1624   \parindent=0pt
1625   \refstepcounter{title}%
1626   {\ifsuftesi@reverseauthortitle
1627     \SUF@titlefont@Switch{\@title}%
1628     \else\SUF@authorfont@Switch{\@author}\fi}%
1629   \label{begin:\thetitle}%
1630   \begingroup%
1631   \let\thanks\@gobble
1632   \addcontentsline{toc}{title}{\normalfont{\@author}\newline%
1633     \itshape\@headtitle}
1634   \endgroup%
1635   \vspace{2ex}\par
1636   {\ifsuftesi@reverseauthortitle
1637     \SUF@authorfont@Switch{\@author}%
1638     \else

```

```

1639      \SUF@titlefont@Switch{\@title}%
1640      \fi\}%
1641      \vskip2.5cm}

\includeart The command to include a paper in the collection.
1642 \newcommand{\includeart}[1]{%
1643   \begingroup
1644   \clearpage
1645   \setcounter{section}{0}
1646   \input{\#1}\label{end:\thetitle}
1647   \global\let\@thanks\@empty
1648 \endgroup}

\frontispiece The command to typeset the frontispiece of the collection.
1649 \newcommand{\frontispiece}{%
1650   \thispagestyle{empty}%
1651   \begingroup
1652   \centering
1653   \null\vspace{\stretch{1}}
1654   {\SUF@chaptersize\collectiontitle\par}
1655   \vskip5ex
1656
1657   \collectioneditor
1658   \vspace{\stretch{2}}
1660
1661   \date
1662
1663 \endgroup
1664 \clearpage}

```

In the collection document structure the articles are treated as chapters but you would not need to print in the table of contents all the sections of every article. So first of all we include in the table of contents only the author and the title of each paper:

```

1665 \setcounter{tocdepth}{0}

Anyway the sections inside each paper are numbered as in standard articles:
1666 \renewcommand\thesection{%
1667   \arabic{c)section}
1668 \renewcommand\thesubsection{%
1669   \thesection.\arabic{c}subsection}
1670 \renewcommand\thesubsubsection{%
1671   \thesubsection.\arabic{c}subsubsection}
1672 \renewcommand\theparagraph{%
1673   \thesubsubsection.\arabic{c}paragraph}
1674 \renewcommand\thesubparagraph{%
1675   \theparagraph.\arabic{c}subparagraph}
1676 \else
1677 \fi

```

6.16 Frontispiece

```

1678 \AtBeginDocument{%
1679 \@ifpackagewith{frontespizio}{suftesi}{%
1680   \if@suftesi@periodical
1681     \Margini{5.5cm}{7cm}{4.5cm}{0cm}
1682   \else
1683   \if@suftesi@compact
1684     \Margini{4.5cm}{7cm}{4.5cm}{0cm}
1685   \else
1686     \if@suftesi@supercompact
1687       \Margini{4.5cm}{10cm}{6cm}{1cm}
1688     \else
1689     \if@suftesi@periodicalaureo
1690       \Margini{5.5cm}{7cm}{4.5cm}{0cm}
1691     \fi
1692   \fi
1693 \fi
1694 \fi}{%
1695 \if@ifpackageloaded{frontespizio}{%

```

```

1696      {\ifsuftesi@periodical
1697          \Margini {1cm}{7cm}{5cm}{1cm}
1698          \Rientro{1cm}
1699      \else
1700      \ifsuftesi@compact
1701          \Margini {1cm}{7cm}{6cm}{1cm}
1702          \Rientro{1cm}
1703      \else
1704          \ifsuftesi@supercompact
1705          \Margini {1cm}{10cm}{8cm}{1cm}
1706          \Rientro{1cm}
1707      \else
1708          \ifsuftesi@periodicalaureo
1709          \Margini {1cm}{7cm}{5cm}{1cm}
1710          \Rientro{1cm}
1711      \fi
1712  \fi
1713 \fi
1714 \fi}
1715 {\relax}}}

theindex
1716 \renewenvironment{theindex}
1717     {\if@twocolumn
1718         \@restonecolfalse
1719     \else
1720         \@restonecoltrue
1721     \fi
1722     \ifsuftesi@article
1723         \twocolumn[\section*{\indexname}]%
1724     \else
1725         \twocolumn[\@makeschapterhead{\indexname}]%
1726     \fi
1727     \omkboth{\indexname}{\indexname}%
1728     \thispagestyle{plain}%
1729     \raggedright%
1730     \parindent\z@
1731     \parskip\z@ \oplus .3\p@\relax
1732     \columnseprule \z@
1733     \columnsep 35\p@
1734     \let\item@\idxitem
1735     {\if@restonecol\onecolumn\else\clearpage\fi}}

```

6.17 Appendix

```

\appendicesname
\appendixpage 1736 \newcommand{\appendicesname}[1]{\def\SUF@appendices{#1}}
1737     \appendicesname{Appendici}
1738     \newcommand{\appendixpage}{\SUF@appendixpage}
1739 \def\SUF@appendixpage{%
1740     \@mainmattertrue
1741     \titlecontents{part}
1742         [0em]
1743         {\addvspace{3ex}}
1744         {}
1745         {}
1746         {}
1747         [\addvspace{1ex}]
1748 \let\contentspage\relax
1749     \cleardoublepage
1750     \thispagestyle{empty}
1751     \addcontentsline{toc}{part}{\SUF@appendices}
1752 \begin{group}
1753     \centering
1754     \null\vfil
1755     {\LARGE\SUF@appendices\par}

```

```

1756           \vfil
1757     \endgroup
1758   \cleardoublepage
1759 \titlecontents{part}
1760   [0em]
1761   {\addvspace{3ex}\partname~}
1762   {\makebox[\SUF@label@part][1]{%
1763     \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}
1764   {}
1765   {}
1766   [\addvspace{1ex}]
1767 }

\appendix
1768 \ifsuftesi@sufelements
1769 \renewcommand\appendix{\par
1770   \setcounter{chapter}{0}%
1771   \setcounter{section}{0}%
1772   \gdef\@chapapp{\appendixname}%
1773   \gdef\thechapter{\@Alph\c@chapter}
1774   \titleformat{\chapter}[block]
1775   {\vskip-22pt}%
1776   {\small%
1777     \SUF@titlesmallcaps{\appendixname}~\Alph{chapter}:\hskip.5em}
1778   {0pt}
1779   {\small\SUF@titlesmallcaps}
1780   [\rule{\textwidth}{.4pt}]
1781   \titlespacing*{\chapter}{0em}{-16pt}{10pt}[0em]
1782 \else
1783   \ifsuftesi@article
1784     \renewcommand\appendix{\par
1785       \setcounter{section}{0}%
1786       \setcounter{subsection}{0}%
1787       \gdef\SUF@thesection{\@Alph\c@section}}
1788 \else
1789   \renewcommand\appendix{\par
1790     \setcounter{chapter}{0}%
1791     \setcounter{section}{0}%
1792     \gdef\@chapapp{\appendixname}%
1793     \gdef\SUF@thechapter{\@Alph\c@chapter}}
1794 \fi
1795 \fi

```

6.18 Headings

```

1796 \RequirePackage{fancyhdr}
1797 \pagestyle{fancy}
1798 \renewcommand{\headrulewidth}{0pt}
1799 \renewcommand{\footnoterule}{}
1800 \def\SUF@versionstring{\texttt{\version@string} \today}

```

The elements headers

```

1801 \ifsuftesi@elementsheader%
1802   \renewcommand{\chaptermark}[1]{\markboth{\#1}{\#1}}
1803   \renewcommand{\sectionmark}[1]{\markright{\#1}}
1804   \fancypagestyle{elements}{%
1805     \setlength{\unitlength}{1pt}
1806     \fancyhf{}
1807     \fancyfoot[LE,R0]{\thepage}
1808     \fancyhead[R0]{%
1809       \begin{picture}(0,0)
1810         \put(0,-104){%
1811           \hspace*{\marginparsep}
1812           \parbox[t]{\marginparwidth}{\itshape\raggedright\leftmark}}%
1813       \end{picture}}
1814     \fancyhead[LE]{%
1815       \begin{picture}(0,0)

```

```

1816      \put(0,-104){%
1817      \hskip-\dimexpr(\marginparwidth+\marginparsep)
1818      \parbox[t]{\marginparwidth}{\itshape\raggedleft\rightmark}}%
1819      \end{picture}}%
1820  }%
1821 \else

```

The default headers

```

1822 \renewcommand{\chaptermark}[1]{%
1823   \markboth{\chapertitlename\ \SUF@thechapter}{#1}}
1824 \ifsuftesi@article
1825   \renewcommand{\sectionmark}[1]{\markright{\SUF@thesection.\ #1}}
1826   \else
1827   \renewcommand{\sectionmark}[1]{}
1828 \fi
1829 \fi

```

The plain style

```
1830 \fancypagestyle{plain}{\fancyhf{}}
```

The sufplain style

```

1831 \fancypagestyle{sufplain}{%
1832   \fancyhf{}%
1833   \fancyfoot[RE,LO]{%
1834     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
1835   \fancyfoot[C]{\footnotesize\SUF@thepage}}

```

The centerheader style

```

1836 \fancypagestyle{centerheader}{%
1837   \fancyhf{}%
1838   \fancyfoot[RE,LO]{%
1839     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
1840   \fancyhead[CO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
1841   \fancyhead[CE]{\footnotesize\xheadbreakfalse%
1842     \SUF@LR@MarkSwitch}
1843   \fancyfoot[C]{\footnotesize\SUF@thepage}}%
1844 }

```

The sufdefault style

```

1845 \fancypagestyle{sufdefault}{%
1846   \fancyhf{}%
1847   \fancyfoot[RE,LO]{%
1848     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
1849   \fancyhead[LE,RO]{\footnotesize\SUF@thepage}
1850   \fancyhead[LO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
1851   \fancyhead[RE]{\footnotesize\xheadbreakfalse%
1852     \SUF@LR@MarkSwitch}
1853 }
1854 %
1855 \ifsuftesi@article
1856 \ifsuftesi@authortitle
1857 \def\SUF@LR@MarkSwitch{\SUF@leftmark}
1858 \else
1859 \def\SUF@LR@MarkSwitch{\SUF@rightmark}
1860 \fi
1861 \else
1862   \def\SUF@LR@MarkSwitch{\SUF@leftmark}
1863 \fi
1864 \def\SUF@leftrightmark{%
1865   \if@mainmatter\leftmark\else\rightmark\fi}
Setting the default page style:
1866 \pagestyle{sufdefault}
1867 \ifsuftesi@centerheader\pagestyle{centerheader}\else\fi

```

```

1868 \ifsuftesi@sufplain\pagestyle{sufplain}\else\fi
1869 \ifsuftesi@elementsheader\pagestyle{elements}\else\fi

```

6.19 Text elements

6.19.1 Block Quotations

quotation New environments for block quotations according to a popular Italian style. The font size is the same of **quote** the footnotes and the margins are set to **\parindent**.

```

verse 1870 \renewenvironment{quotation}
1871     {\list{}{\listparindent\parindent%
1872         \itemindent \listparindent
1873         \leftmargin \parindent
1874         \SUF@quote@style
1875         \parsep \z@ \oplus\p@}%
1876         \item\relax%
1877         \SUF@quotation@size%
1878         \noindent\ignorespaces}
1879     {\endlist}
1880 \renewenvironment{quote}
1881     {\list{}{\leftmargin \parindent
1882         \SUF@quote@style}%
1883         \item\relax%
1884         \SUF@quotation@size}\ignorespaces?
1885     {\endlist}
1886 \renewenvironment{verse}
1887     {\let\\@centercr
1888     \list{}{\itemsep \z@
1889         \itemindent -1.5em%
1890         \listparindent\itemindent
1891         \rightmargin \leftmargin
1892         \advance\leftmargin 1.5em}%
1893         \item\relax
1894         \SUF@quotation@size}
1895     {\endlist}

```

The fewfootnotes option Enable only with three footnotes per page maximum.

```

1896 \ifsuftesi@fewfootnotes
1897 \AtBeginDocument{%
1898 \def\fnsymbol#1{\ensuremath{\ifcase#1\or*\or{*\!\!}{*}\or{*\!\!}{*}\or{*\!\!}{*}\or{*\!\!}{*}}%
1899 \ClassError{suftesi}%
1900 {Too many footnotes\MessageBreak
1901 Remove the class option 'fewfootnote'}%
1902 {Too many footnotes\MessageBreak
1903 Remove the class option 'fewfootnote'}%
1904 \else\ctrerr\fi}}
1905 \def\thefootnote{\fnsymbol{c@footnote}%
1906 \else\fi

```

\xfootnote Prints a footnote with discretionary symbol give in the first argument.

```

1907 \newcommand*\xfootnote[1][*]{%
1908     \xdef\thefnmark{#1}%
1909     \footnotemark\footnotetext}

```

6.19.2 Marginal notes

\marginpar The **\marginpar** command is redefined according to the look of *Classic Thesis* by André Miede (2011). Thanks to Lorenzo Pantieri and Enrico Gregorio.

```

1910 \def\SUF@mpsetup{%

```

In the *Elements* (i.e. with **elements** option) the marginal notes are printed in roman, but I prefer italic shape for the other options:

```

1911     \ifsuftesi@elementsheader\relax
1912     \else\itshape\fi
1913     \footnotesize%
1914     \parindent=0pt \lineskip=0pt \lineskiplimit=0pt %

```

```

1915     \tolerance=2000 \hyphenpenalty=300 \exhyphenpenalty=300%
1916     \doublehyphendemerits=100000%
1917     \finalhyphendemerits=\doublehyphendemerits}
1918 \let\oldmarginpar\marginpar
1919 \renewcommand{\marginpar}[1]{\oldmarginpar%
1920   [\SUF@mpsetup\raggedleft\hspace{0pt}{#1}]%
1921   {\SUF@mpsetup\raggedright\hspace{0pt}{#1}}}

```

Redefine an internal command of the todonotes package in order to use the class-specific marginal notes when this package is loaded. This redefinition simply substitute `\oldmarginpar` to `\marginpar`:

```

1922 \AtBeginDocument{%
1923 \@ifpackageloaded{todonotes}{%
1924 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
1925 \begin{tikzpicture}[remember picture, overlay, baseline=-0.75ex]%
1926   \node [coordinate] (inText) {};%
1927 \end{tikzpicture}%
1928 \oldmarginpar[{\% Draw note in left margin
1929   \@todonotes@drawMarginNote%
1930   \@todonotes@drawLineToLeftMargin%
1931 }]{\% Draw note in right margin
1932   \@todonotes@drawMarginNote%
1933   \@todonotes@drawLineToRightMargin%
1934 }%
1935 }%
1936 }%
1937 {\relax}}

```

6.19.3 Abstract

quotation This is the macro that defines the `abstract` environment in `article` class. In `suftesi` it simply prints the abstract name in roman font:

```

1938 \ifsuftesi@collection
1939   \newenvironment{abstract}{%
1940     \if@twocolumn
1941       \section*{\abstractname}%
1942     \else
1943       \small
1944       \begin{center}%
1945         {\abstractname\vspace{-.5em}\vspace{\z@}}%
1946       \end{center}%
1947       \quotation
1948     \fi}
1949   {\if@twocolumn\else\endquotation\fi}
1950 \else
1951 \if@titlepage
1952   \newenvironment{abstract}{%
1953     \titlepage
1954     \null\vfil
1955     \begin{parpenalty}\clowpenalty
1956     \begin{center}%
1957       \abstractname
1958       \endparpenalty\OM
1959     \end{center}%
1960     \par\vfil\null\endtitlepage}
1961 \else
1962   \newenvironment{abstract}{%
1963     \if@twocolumn
1964       \section*{\abstractname}%
1965     \else
1966       \small
1967       \begin{center}%
1968         {\abstractname\vspace{-.5em}\vspace{\z@}}%
1969       \end{center}%
1970       \quotation
1971     \fi}
1972   {\if@twocolumn\else\endquotation\fi}

```

```

1973 \fi
1974 \fi
1975 \newcommand{\abstractname}{Abstract}

```

6.19.4 Colophon

\colophon Some useful commands to print a colophon or a copyright notice.

```

1976 \newcommand{\colophon}[3][]{%
1977   \thispagestyle{empty}%
1978   \null%
1979   \vfill%
1980   \def\next{\#2}%
1981   \ifx\next\empty\else%
1982     \noindent Copyright \copyright{} \the\year~\#2\lex]%
1983     Tutti i diritti riservati%
1984   \fi%
1985   \vfill%
1986   {\small\noindent Questo lavoro \`e stato composto con \LaTeX{}%%
1987   \def\next{\#1}%
1988   \ifx\next\empty\else su #1%
1989   \fi usando la classe \textsf{suftesi} di%
1990   Ivan Valbusa\index{Valbusa, Ivan}. #3\par}%
1991   \cleardoublepage}

```

\bookcolophon

```

1992 \newcommand{\bookcolophon}[2]{%
1993   \thispagestyle{empty}%
1994   \null%
1995   \vfill%
1996   \noindent #1%
1997   \vfill%
1998   {\small\noindent #2\par}%
1999   \cleardoublepage}

```

\artcolophon

```

2000 \newcommand{\artcolophon}[1]{%
2001 \thispagestyle{empty}%
2002 \null%
2003 \vfill%
2004 {\small\noindent #1\par}}

```

\finalcolophon

```

2005 \newcommand{\finalcolophon}[1]{%
2006 \thispagestyle{empty}%
2007 \null\vspace*{\stretch{1}}%
2008 \begin{center}%
2009 \begin{minipage}{.5\textwidth}%
2010 \centering\small #1%
2011 \end{minipage}%
2012 \end{center}%
2013 \vspace*{\stretch{6}}}

```

\FSPLcolophon This command is defined only for the style=FSPL* options.

```

2014 \ifsuftesi@FSPL%
2015 \newcommand{\FSPLcolophon}[1][\the\year]{%
2016 \begingroup%
2017 \thispagestyle{empty}%
2018 \null\vspace{\stretch{1}}%
2019 \noindent \hspace{-.5em}\cc #1 \author{}%
2020 \vskip1ex%
2021 %
2022 \small\noindent This work is licensed under the Creative Commons%
2023 Attribution-NonCommercial-NoDerivs 3.0 Unported License.%
2024 To view a copy of this license,%
2025 visit http://creativecommons.org/licenses/by-nc-nd/3.0/.%
2026 %
2027 \endgroup}

```

```

2028
2029 \begingroup
2030 \footnotesize
2031
2032 \null\vspace{\stretch{1}}
2033
2034 \noindent Typeset with \LaTeX{} in collaboration with the Joint Project
2035 \emph{Formal Style for PhD Theses with \LaTeX{}} (University of Verona,
2036 Italy) using the \textsf{suftesi} class by Ivan Valbusa. The text face
2037 is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by
2038 Janusz M. Nowacki.
2039
2040 \endgroup
2041
2042 \clearpage}
2043 \else
2044 \def\FSPLcolophon{%
2045 \ClassError{suftesi}{%
2046 \noexpand\FSPLcolophon is defined\MessageBreak
2047 only for the FSPL styles}
2048 \noexpand\FSPLcolophon is defined\MessageBreak
2049 only for the FSPL styles}}
2050 \fi

```

6.20 Toc, lof, lot

2051 \RequirePackage{titletoc}

All the lengths depend on \SUF@label@chap so we define this first.

2052 \newlength\SUF@label@chap
2053 \setlength\SUF@label@chap{.5em}

\toclabelwidth \toclabelwidth is provided to adjust the label width in the table of contents:

2054 \newcommand*\toclabelwidth[2]{%
2055 \addtolength{\csname SUF@label@#1\endcsname}{#2}%
2056 \addtolength{\csname SUF@tocindent@#1\endcsname}{#2}%
2057 \newcommand{\toclabelspace}{%
2058 \ClassError{suftesi}{%
2059 \MessageBreak
2060 \noexpand\toclabelspace is not more defined\MessageBreak
2061 Use \noexpand\toclabelwidth instead.\MessageBreak
2062 See package documentation for details}
2063 \MessageBreak
2064 \noexpand\toclabelspace is not more defined\MessageBreak
2065 Use \noexpand\toclabelwidth instead.\MessageBreak
2066 See package documentation for details}}

\SUF@tochang This macro controls the space between page number and chapter label using the tocpageleft option:

2067 \newlength{\SUF@tochang}
2068 \setlength{\SUF@tochang}{3em}
2069 \AtBeginDocument{
2070 \newlength\SUF@label@part
2071 \newlength\SUF@label@sec
2072 \newlength\SUF@label@subsec
2073 \newlength\SUF@label@subsubsec
2074 \newlength\SUF@label@par
2075 \newlength\SUF@label@subpar
2076 \newlength\SUF@label@fig
2077 \newlength\SUF@label@tab
2078 \setlength\SUF@label@part{%
2079 \SUF@label@chap}
2080 \setlength\SUF@label@sec{%
2081 \dimexpr(\SUF@label@chap+.5em)}
2082 \setlength\SUF@label@subsec{%
2083 \dimexpr(\SUF@label@sec+.5em)}
2084 \setlength\SUF@label@subsubsec{%
2085 \dimexpr(\SUF@label@subsec+.5em)}
2086 \setlength\SUF@label@par{}}

```

2087      {\dimexpr(\SUF@label@subsubsec+.5em)}
2088 \setlength{\SUF@label@subpar}
2089      {\dimexpr(\SUF@label@par+.5em)}
2090 \setlength{\SUF@label@fig}
2091      {\SUF@label@sec}
2092 \setlength{\SUF@label@tab}
2093      {\SUF@label@sec}
2094 }

Part in article mode
2095 \titlecontents{part}
2096 [0em]
2097 {\addvspace{3ex}\partname\hspace*{.5em}}
2098 {\makebox[\SUF@label@part][1]{%
2099   \SUF@toclabelnum\thecontentslabel\hspace*{1em}}}
2100 {}
2101 {}
2102 [\addvspace{1ex}]

6.20.1 'tocpageleft' toc

2103 \ifsuftesi@pagelefttoc

```

\contentsmargin First we reset the right margin to zero:

```

2104 \contentsmargin{0pt}
2105 \AtBeginDocument{
2106 \newlength{\SUF@tochang@chap}
2107 \newlength{\SUF@tochang@sec}
2108 \newlength{\SUF@tochang@subsec}
2109 \newlength{\SUF@tochang@subsubsec}
2110 \newlength{\SUF@tochang@par}
2111 \newlength{\SUF@tochang@subpar}
2112 \newlength{\SUF@tochang@fig}
2113 \newlength{\SUF@tochang@tab}
2114 \newlength{\SUF@addto@tochang@chap}
2115 \newlength{\SUF@addto@tochang@sec}
2116 \newlength{\SUF@addto@tochang@subsec}
2117 \newlength{\SUF@addto@tochang@subsubsec}
2118 \newlength{\SUF@addto@tochang@par}
2119 \newlength{\SUF@addto@tochang@subpar}
2120 \newlength{\SUF@addto@tochang@fig}
2121 \newlength{\SUF@addto@tochang@tab}
2122 \setlength{\SUF@tochang@chap}
2123  {\dimexpr(1em+\SUF@tochang+\SUF@label@chap+1em)}
2124 \setlength{\SUF@tochang@sec}
2125  {\dimexpr(\SUF@tochang@chap+\SUF@label@sec+1em)}
2126 \setlength{\SUF@tochang@subsec}
2127  {\dimexpr(\SUF@tochang@sec+\SUF@label@subsec+1em)}
2128 \setlength{\SUF@tochang@subsubsec}
2129  {\dimexpr(\SUF@tochang@subsec+\SUF@label@subsubsec+1em)}
2130 \setlength{\SUF@tochang@par}
2131  {\dimexpr(\SUF@tochang@subsubsec+\SUF@label@par+1em)}
2132 \setlength{\SUF@tochang@subpar}
2133  {\dimexpr(\SUF@tochang@par+\SUF@label@subpar+1em)}
2134 \setlength{\SUF@tochang@fig}
2135  {\SUF@tochang@chap}
2136 \setlength{\SUF@tochang@tab}
2137  {\SUF@tochang@chap}
2138 \setlength{\SUF@addto@tochang@chap}
2139  {\SUF@tochang}
2140 \setlength{\SUF@addto@tochang@sec}
2141  {\dimexpr(\SUF@addto@tochang@chap+\SUF@label@sec+.5em)}
2142 \setlength{\SUF@addto@tochang@subsec}
2143  {\dimexpr(\SUF@addto@tochang@sec+\SUF@label@subsec+.5em)}
2144 \setlength{\SUF@addto@tochang@subsubsec}
2145  {\dimexpr(\SUF@addto@tochang@subsec+\SUF@label@subsubsec+.5em)}
2146 \setlength{\SUF@addto@tochang@par}
2147  {\dimexpr(\SUF@addto@tochang@subsubsec+\SUF@label@par+.5em)}

```

```

2148 \setlength{\SUF@addto@tochang@subpar}
2149   {\dimexpr(\SUF@addto@tochang@par+\SUF@label@subpar+.5em)}
2150 \setlength{\SUF@addto@tochang@fig}
2151   {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2152 \setlength{\SUF@addto@tochang@tab}
2153   {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2154 }

TOC entries

2155 \titlecontents{chapter}
2156   [\SUF@tochang@chap]
2157   {\addvspace{2ex}}
2158   {\hspace{-\SUF@tochang@chap%}
2159     \makebox[1em][l]{\thecontentspage}%
2160     \hspace{\SUF@addto@tochang@chap%}
2161     \makebox[\SUF@label@chap][l]{%
2162       \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}%
2163   {\hspace{-\SUF@tochang@chap%}
2164     \makebox[1em][l]{\thecontentspage}%
2165     \hspace{\SUF@addto@tochang@chap}}
2166   {}
2167   [\addvspace{1ex}]
2168 \titlecontents{section}
2169   [\SUF@tochang@sec]
2170   {}
2171   {\hspace{-\SUF@tochang@sec%}
2172     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@sec%}
2173     \makebox[\SUF@label@sec][l]{%
2174       \if sulfesi@article\SUF@toclabelnum%
2175       \else\fi\thecontentslabel}\hspace*{1em}}%
2176   {\hspace{-\SUF@tochang@sec%}
2177     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@sec}}
2178   {}

2179 \titlecontents{subsection}
2180   [\SUF@tochang@subsec]
2181   {}
2182   {\hspace{-\SUF@tochang@subsec%}
2183     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsec%}
2184     \makebox[\SUF@label@subsec][l]{%
2185       \hspace{-\SUF@tochang@subsec%}
2186       \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsec}}%
2187   }

2188 \titlecontents{subsubsection}
2189   [\SUF@tochang@subsubsec]
2190   {}
2191   {\hspace{-\SUF@tochang@subsubsec%}
2192     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsubsec%}
2193     \makebox[\SUF@label@subsubsec][l]{%
2194       \hspace{-\SUF@tochang@subsubsec%}
2195       \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsubsec}}%
2196   }

2197 \titlecontents{paragraph}
2198   [\SUF@tochang@par]
2199   {}
2200   {\hspace{-\SUF@tochang@par%}
2201     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@par%}
2202     \makebox[\SUF@label@par][l]{%
2203       \hspace{-\SUF@tochang@par%}
2204       \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@par}}%
2205   }

2206 \titlecontents{subparagraph}
2207   [\SUF@tochang@subpar]
2208   {}
2209   {\hspace{-\SUF@tochang@subpar%}
2210     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subpar%}
2211     \makebox[\SUF@label@subpar][l]{%
2212       \hspace{-\SUF@tochang@subpar%}

```

```

2213   \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@subpar}
2214   {}
2215 \titlecontents{figure}
2216   [\SUF@tochang@fig]
2217   {}
2218   {\hskip-\SUF@tochang@fig%
2219   \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@fig%
2220   \makebox[\SUF@label@tab] [1]{\thecontentslabel}\hspace*{1em}}
2221   {}
2222   {}
2223 \titlecontents{table}
2224   [\SUF@tochang@tab]
2225   {}
2226   {\hskip-\SUF@tochang@tab%
2227   \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@tab%
2228   \makebox[\SUF@label@tab] [1]{\thecontentslabel}\hspace*{1em}}
2229   {}
2230   {}
2231 \else

```

6.20.2 Default toc

```

2232 \AtBeginDocument{
2233 \newlength\SUF@tocindent@chap
2234 \newlength\SUF@tocindent@sec
2235 \newlength\SUF@tocindent@subsec
2236 \newlength\SUF@tocindent@subsubsec
2237 \newlength\SUF@tocindent@par
2238 \newlength\SUF@tocindent@subpar
2239 \newlength\SUF@tocindent@fig
2240 \newlength\SUF@tocindent@tab
2241 \ifsuftesi@article
2242 \setlength\SUF@tocindent@sec
2243   {\dimexpr(\SUF@label@chap+1.5em)}
2244 \setlength\SUF@tocindent@subsec
2245   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2246 \setlength\SUF@tocindent@subsubsec
2247   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2248 \setlength\SUF@tocindent@par
2249   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2250 \setlength\SUF@tocindent@subpar
2251   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2252 \setlength\SUF@tocindent@fig
2253   {\dimexpr(\SUF@label@chap+1.5em)}
2254 \setlength\SUF@tocindent@tab
2255   {\dimexpr(\SUF@label@chap+1.5em)}
2256 \else
2257 \setlength\SUF@tocindent@chap
2258   {\dimexpr(\SUF@label@chap+1em)}
2259 \setlength\SUF@tocindent@sec
2260   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec+1em)}
2261 \setlength\SUF@tocindent@subsec
2262   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2263 \setlength\SUF@tocindent@subsubsec
2264   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2265 \setlength\SUF@tocindent@par
2266   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2267 \setlength\SUF@tocindent@subpar
2268   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2269 \setlength\SUF@tocindent@fig
2270   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2271 \setlength\SUF@tocindent@tab
2272   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2273 \fi
2274 }

```

TOC entries

```

2275 \titlecontents{chapter}
2276   [‐\SUF@tocindent@chap]
2277   {\addvspace{2ex}}
2278   {‐\hskip‐\SUF@tocindent@chap%
2279     \makebox[‐\SUF@label@chap]{1}{‐\SUF@toclabelnum\thecontentslabel}%
2280     \hspace*{1em}}
2281   {‐\hskip‐\SUF@tocindent@chap}
2282   {‐\SUF@chaptitlerule\contentspage}
2283   [\addvspace{1ex}]
2284 \titlecontents{section}
2285   [‐\SUF@tocindent@sec]
2286   {}
2287   {‐\hskip‐\dimexpr(\SUF@label@sec+1em)%
2288     \makebox[‐\SUF@label@sec]{1}{%
2289       \ifsuftesi@article‐\SUF@toclabelnum%
2290         \else\fi\thecontentslabel}\hspace*{1em}}
2291   {‐\hskip‐\dimexpr(\SUF@label@sec+1em)%
2292   \ifsuftesi@article‐\SUF@chaptitlerule%
2293     \else‐\SUF@titlerule\fi\contentspage}
2294 \titlecontents{subsection}
2295   [‐\SUF@tocindent@subsec]
2296   {}
2297   {‐\hskip‐\dimexpr(\SUF@label@subsec+1em)%
2298     \makebox[‐\SUF@label@subsec]{1}{‐\thecontentslabel}\hspace*{1em}}
2299   {‐\hskip‐\dimexpr(\SUF@label@subsec+1em)%
2300   {‐\SUF@titlerule\contentspage}
2301 \titlecontents{subsubsection}
2302   [‐\SUF@tocindent@subsubsec]
2303   {}
2304   {‐\hskip‐\dimexpr(\SUF@label@subsubsec+1em)%
2305     \makebox[‐\SUF@label@subsubsec]{1}{‐\thecontentslabel}\hspace*{1em}}
2306   {‐\hskip‐\dimexpr(\SUF@label@subsubsec+1em)%
2307   {‐\SUF@titlerule\contentspage}
2308 \titlecontents{paragraph}
2309   [‐\SUF@tocindent@par]
2310   {}
2311   {‐\hskip‐\dimexpr(\SUF@label@par+1em)%
2312     \makebox[‐\SUF@label@par]{1}{‐\thecontentslabel}\hspace*{1em}}
2313   {‐\hskip‐\dimexpr(\SUF@label@par+1em)%
2314   {‐\SUF@titlerule\contentspage}
2315 \titlecontents{subparagraph}
2316   [‐\SUF@tocindent@subpar]
2317   {}
2318   {‐\hskip‐\dimexpr(\SUF@label@subpar+1em)%
2319     \makebox[‐\SUF@label@subpar]{1}{‐\thecontentslabel}\hspace*{1em}}
2320   {‐\hskip‐\dimexpr(\SUF@label@subpar+1em)%
2321   {‐\SUF@titlerule\contentspage}
2322 \titlecontents{figure}
2323   [‐\SUF@tocindent@fig]
2324   {}
2325   {‐\hskip‐\SUF@tocindent@fig%
2326     \makebox[‐\SUF@label@fig]{1}{‐\thecontentslabel}\hspace*{1em}}
2327   {}
2328   {‐\SUF@titlerule\contentspage}
2329 \titlecontents{table}
2330   [‐\SUF@tocindent@tab]
2331   {}
2332   {‐\hskip‐\SUF@tocindent@tab%
2333     \makebox[‐\SUF@label@tab]{1}{‐\thecontentslabel}\hspace*{1em}}
2334   {}
2335   {‐\SUF@titlerule\contentspage}
2336 \fi

```

\tableofcontents With article option the toc, lof and lot are printed as sections.

```

\listoffigures 2337 \ifsuftesi@article
\listoftables 2338 \renewcommand\tableofcontents{%
2339   \vspace{2ex}}%

```

```

2340     \section*{\contentsname}%
2341         \@mkboth{\contentsname}{\contentsname}%
2342             \thispagestyle{empty}%
2343             \ifsuftesi@twocolumntoc
2344                 \begin{multicols}{2}%
2345                     \starttoc{toc}%
2346                 \end{multicols}%
2347             \else
2348                 \starttoc{toc}%
2349             \fi
2350         \vspace{2ex}%
2351     }
2352 \renewcommand\listoffigures{%
2353     \vspace{2ex}%
2354     \section*{\listfigurename}%
2355         \@mkboth{\listfigurename}{\listfigurename}%
2356             \thispagestyle{empty}%
2357             \ifsuftesi@twocolumnlof
2358                 \begin{multicols}{2}%
2359                     \starttoc{lof}%
2360                 \end{multicols}%
2361             \else
2362                 \starttoc{lof}%
2363             \fi
2364         \vspace{2ex}%
2365     }
2366 \renewcommand\listoftables{%
2367     \vspace{2ex}%
2368     \section*{\listtablename}%
2369         \@mkboth{\listtablename}{\listtablename}%
2370             \thispagestyle{empty}%
2371             \ifsuftesi@twocolumnlot
2372                 \begin{multicols}{2}%
2373                     \starttoc{lot}%
2374                 \end{multicols}%
2375             \else
2376                 \starttoc{lot}%
2377             \fi
2378         \vspace{2ex}%
2379     }
2380 \else

```

The default toc, lof and lot are treated as chapters.

```

2381 \renewcommand\tableofcontents{%
2382     \if@twocolumn
2383         \@restonecoltrue\onecolumn
2384     \else
2385         \@restonecolfalse
2386     \fi
2387     \chapter*{\contentsname}%
2388         \@mkboth{%
2389             \contentsname}%
2390             {\contentsname}%
2391             \thispagestyle{empty}%
2392             \ifsuftesi@twocolumntoc
2393                 \begin{multicols}{2}%
2394                     \starttoc{toc}%
2395                 \end{multicols}%
2396             \else
2397                 \starttoc{toc}%
2398             \fi
2399         \if@restonecol\twocolumn\fi
2400     }
2401 \renewcommand\listoffigures{%
2402     \if@twocolumn
2403         \@restonecoltrue\onecolumn
2404     \else

```

```

2405      \restonecolfalse
2406      \fi
2407      \chapter*{\listfigurename}%
2408          \mkboth{\listfigurename}%
2409              {\listfigurename}%
2410      \thispagestyle{empty}
2411          \if@twocolumnlof
2412              \begin{multicols}{2}
2413                  \starttoc{lof}%
2414              \end{multicols}
2415      \else
2416          \starttoc{lof}%
2417      \fi
2418      \if@restonecol\twocolumn\fi
2419  }
2420 \renewcommand{\listoftables}{%
2421     \if@twocolumn
2422         \restonecoltrue\onecolumn
2423     \else
2424         \restonecolfalse
2425     \fi
2426     \chapter*{\listtablename}%
2427         \mkboth{%
2428             \listtablename}%
2429             {\listtablename}%
2430     \thispagestyle{empty}
2431         \if@twocolumnlot
2432             \begin{multicols}{2}
2433                 \starttoc{lot}%
2434             \end{multicols}
2435     \else
2436         \starttoc{lot}%
2437     \fi
2438     \if@restonecol\twocolumn\fi
2439  }
2440 \fi

```

6.21 New commands

\chapterintro A command to typeset an unnumbered section:

```

2441 \ifsuftesi@article
2442 \def\chapterintro{%
2443 \ClassError{suftesi}%
2444   {Command \noexpand\chapterintro is undefined\MessageBreak
2445     using 'documentstructure=article'}
2446   {Command \noexpand\chapterintro is undefined\MessageBreak
2447     using 'documentstructure=article'}}%
2448 \else
2449 \def\chapterintro{%
2450   \@ifstar{\@tempswafalse\@chapterintro}{\@tempswatrue\@chapterintro}}%
2451 \def\@chapterintro{\phantomsection
2452   \if@tempswa\section*{\SUF\fchapterintroname}\fi
2453   \addcontentsline{toc}{section}{\SUF\fchapterintroname}}
2454 \newcommand{\chapterintroname}[1]{\def\SUF\fchapterintroname{#1}}
2455 \chapterintroname{Introduzione}
2456 \fi

```

\headbreak Active in the table of contents but not in the text.

```

2457 \newif\ifheadbreak\headbreakfalse
2458 \DeclareRobustCommand{\headbreak}
2459   {\ifheadbreak\else\fi}

```

\xheadbreak Active in the text but not in the table of contents.

```

2460 \newif\ifxheadbreak\xheadbreaktrue
2461 \DeclareRobustCommand{\xheadbreak}
2462   {\ifxheadbreak\else\fi}

```

```
\tableofcontents
2463 \let\origtableofcontents\tableofcontents
2464   \renewcommand{\tableofcontents}{%
2465     \begingroup\headbreaktrue\xheadbreakfalse%
2466     \origtableofcontents\endgroup}
Renew \frontmatter to have arabic page numbering:
2467 \ifsuftesi@article
2468 \renewcommand{\frontmatter}{\ClassError{suftesi}%
2469   {Command \noexpand\frontmatter is undefined\MessageBreak
2470     using 'documentstructure=article'}
2471   {Command \noexpand\frontmatter is undefined\MessageBreak
2472     using 'documentstructure=article'}}}
2473 \renewcommand{\mainmatter}{\ClassError{suftesi}%
2474   {Command \noexpand\mainmatter is undefined\MessageBreak
2475     using 'documentstructure=article'}
2476   {Command \noexpand\mainmatter is undefined\MessageBreak
2477     using 'documentstructure=article'}}}
2478 \renewcommand{\backmatter}{\ClassError{suftesi}%
2479   {Command \noexpand\backmatter is undefined\MessageBreak
2480     using 'documentstructure=article'}
2481   {Command \noexpand\backmatter is undefined\MessageBreak
2482     using 'documentstructure=article'}}}
2483 \else
2484 \renewcommand{\frontmatter}{\cleardoublepage\@mainmatterfalse}
2485 \renewcommand{\mainmatter}{\cleardoublepage\@mainmattertrue}
2486 \fi
```

6.22 Backward compatibility

bibliografia An environment to manually typeset the bibliography. (Use `biblatex` instead!)

```
2487 \newenvironment{bibliografia}{%
2488   \ifsuftesi@article
2489     \section*{\refname}
2490     \addcontentsline{toc}{section}{\refname}
2491   \else
2492     \chapter{\bibname}%
2493   \fi
2494     \normalfont \list{}{%
2495       \setlength{\itemindent}{-\parindent}
2496       \setlength{\leftmargin}{\parindent}
2497       \setlength{\labelwidth}{\leftmargin}
2498       \setlength{\parsep}{\parskip}
2499       \let\makelabel\label}
2500   \endlist}
```

sigle An environment to manually typeset the list of shorthands. (Use `biblatex` instead!)

```
2501 \newcommand{\losname}{Sigle}
2502 \newcommand{\itlabel}[1]{\itshape\hbox to 6em{\#1}}
2503 \newenvironment{sigle}{%
2504   \chapter{\losname}
2505     \normalfont \list{}{%
2506       \setlength{\labelsep}{0.5em}
2507       \setlength{\itemindent}{0pt}
2508       \setlength{\leftmargin}{6em}
2509       \setlength{\labelwidth}{\leftmargin}
2510       \setlength{\listparindent}{\parindent}
2511       \setlength{\parsep}{\parskip}
2512       \let\makelabel\itlabel}}
2513 \endlist}
```

6.23 Final settings

In a previous version the `\hemp` command was provided to fix a bug in the hyphenation of some italian expressions like “dell’*encyclopaedia*”. Now the bug has been fixed loading the `fixltxhyph` package by Claudio Beccari. The package must be loaded after `babel` or `polyglossia`:

2514 \AtBeginDocument{\RequirePackage{fixltxhyph}}

The \hemph command is provided only for backward compatibility:

2515 \let\hemph\emph

The first line of all sections is indented by default using X_ETEX with italian as main language. Anyway this is incongruous with the L_AT_EX default.

2516 \ifxetex\let\@afterindenttrue\@afterindentfalse\else\fi

Just one touch of french typography:

2517 \frenchspacing

</class>

Change History

vo.5	General: First public release. The frontispiece of <code>suftesi</code> is now included in the package <code>frontespizio</code> . New option <code>fullplain</code> Changed option <code>sctitles</code>	1	New option <code>rightsec</code>	11
	New command <code>chapnumfont</code>	10	New option <code>rmstyle(1-6)</code>	11
	New option <code>compact</code>	11	New option <code>romanchap</code>	11
	New option <code>elements</code>	11	New option <code>scstyle(1-12)</code>	11
	New option <code>nocrop</code>	11	New option <code>smallcapschap</code>	11
	New option <code>nomarginpar</code>	11	New option <code>smallcapsheader</code>	11
	New option <code>sufelements</code>	11	New option <code>smallcapspart</code>	11
	New option <code>supercompact</code>	11	New option <code>smallcapssec</code>	11
vo.6	General: English documentation. Renamed options <code>plain</code> and <code>fullplain</code> to <code>centerheadings</code> and <code>sufplain</code>	1	New option <code>smallquotation</code>	11
	New command <code>\artcolophon</code>	9	New option <code>standardfootnote</code>	11
	New command <code>\bookcolophon</code>	9	New option <code>tocpageleft</code>	11
	New option <code>authortitle</code>	11		
vo.6a	General: Maintenance release, no changes	1		
vo.6b	General: Improved full compatibility with X _{EL} T _E X. <code>varioref</code> and <code>footmisc</code> packages are no longer loaded	1		
vo.6c	General: Maintenance release, no changes	1		
vo.7	General: Maintenance release, no changes. Provided a thesis template	1		
vo.8	General: Added macro for using <code>frontespizio</code> package with <code>compact</code> and <code>supercompact</code> options.	1		
	New option <code>periodical</code>	11		
	Renewed <code>\title</code> command	10		
vo.9	General: Improved compatibility with <code>mathspec</code>	1		
	New option <code>dotteddtoc</code>	11		
	New option <code>raggeddtoc</code>	11		
vo.9a	General: Added inline option to <code>enumitem</code> package. Deleted <code>centertitle</code> option. Deleted <code>sctitles</code> option. Changed code for toc, lot and lof elements.	1		
	New command <code>\toclabelspace</code>	9		
	New option <code>alignlist</code>	11		
	New option <code>centerchap</code>	11		
	New option <code>centerpart</code>	11		
	New option <code>centersec</code>	11		
	New option <code>defaultparindent</code>	11		
	New option <code>dottedchap</code>	11		
	New option <code>dottedfootnote</code>	11		
	New option <code>dottedpart</code>	11		
	New option <code>indentlist</code>	11		
	New option <code>italicchap</code>	11		
	New option <code>italicheader</code>	11		
	New option <code>italicpart</code>	11		
	New option <code>italicsec</code>	11		
	New option <code>italicsubsec</code>	11		
	New option <code>itstyle(1-12)</code>	11		
	New option <code>numparchap</code>	11		
	New option <code>numparpart</code>	11		
	New option <code>numparsec</code>	11		
	New option <code>ralignquotation</code>	11		
	New option <code>rightchap</code>	11		
	New option <code>rightpart</code>	11		
vo.9b	General: Renamed <code>viewmode</code> option to <code>version</code> : renamed <code>print</code> value to <code>draft</code> and added <code>final</code> value. New <code>smallcapsstyle</code> option.	1		
v1.0	General: First stable release. Renamed option <code>bozza</code> to <code>draftdate</code>	7		
v1.1	General: Added the <code>fixltxhyph</code> package. Documentation updated.	1		
v1.2	General: Maintenance release. Added the <code>\toclabelspace</code> command.	1		
v1.3	General: New command <code>\FSPLcolophon</code>	8		
	Updated documentation. Added FSPLa, FSPLb and FSPLc styles.	1		
v1.4	General: New value <code>periodicalaureo</code> for option <code>pagelayout</code> . Changed code for <code>\xfootnote</code> command.	1		
v1.5	General: The <code>microtype</code> package is loaded for all engines. Improved compatibility with <code>todonotes</code> package and with <code>mdframed</code> and <code>bookmark</code> packages when using <code>style</code> class option. New option <code>viewmode</code>	1		
v1.6	General: New option <code>viewmode</code> . Corrected bugs in the definition of <code>\listoffigures</code> , <code>\listoftables</code> and <code>\tableofcontents</code> commands. Updated documentation.	1		
v1.7	General: Renamed <code>viewmode</code> option to <code>version</code> : renamed <code>print</code> value to <code>draft</code> and added <code>final</code> value. New <code>smallcapsstyle</code> option.	1		

v1.8	General: Maintenance release. Corrected a bug in the definition of \appendix	1	\toclabelwidth. New collection document structure	1	
v1.9	General: Added <i>italic</i> , <i>smallcaps</i> and <i>sanserif</i> values for <i>captionstyle</i> option. New <i>twocolcontents</i> option. New <i>supercompactaureo</i> page layout. Changed \toclabelspace command and renamed to	1	v1.9a	General: Maintenance release. Updated greek support. Updated documentation.	1
			v1.9b	General: Corrected a bug in “toc”, “lof” and “lot” commands.	1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@Alph	1773, 1787, 1793
\@M	1958
\@Roman	307, 319, 334, 346, 361, 373
\@afterindentfalse	2516
\@afterindenttrue	2516
\@arabic	1208, 1210, 1212, 1214, 1216, 1667, 1669, 1671, 1673, 1675
\@author	397, 401, 1344, 1374, 1401, 1468, 1514, 1628, 1632, 1637, 2019
\@beginparpenalty	1955
\@centercr	1887
\@chapapp	1772, 1792
\@chapterintro	2450, 2451
\@collectioneditor	1562, 1563, 1658
\@collectiontitle	1559, 1560, 1655
\@ctrerr	1904
\@date	1377, 1386, 1404, 1413, 1442, 1471, 1500, 1517, 1661
\@dblarg	1334
\@doi	1536, 1537
\@endparpenalty	1958
\@fnssymbol 1353, 1419, 1477, 1598, 1898, 1905
\@footnotemark	1909
\@footnotetext	1909
\@headtitle	396, 400, 1333, 1336, 1633
\@highpenalty	1567, 1593
\@idxitem	1734
\@ifpackageloaded 939, 1268, 1300, 1695, 1923
\@ifpackagewith	1679
\@ifstar	2450
\@issn	1533, 1534
\@issue	1545, 1546, 1557
\@issuename	1558
\@journalname	1530, 1531, 1556
\@journalnumber	1542, 1543, 1556
\@journalvolume	1539, 1540
\@journalwebsite	1551, 1552
\@journalyear	1548, 1549, 1557
\@latex@warning@no@line 1531, 1534, 1537, 1540, 1543, 1546, 1549, 1552, 1560, 1563
\@lowpenalty	1955
\@mainmatterfalse	2484
\@mainmattertrue	1740, 2485
\@makefnmark	1420, 1478, 1599
\@makefntext 466, 469, 473, 476, 1421, 1479, 1600
\@makeschapterhead	1725
\@maketitle	1426, 1428, 1433, 1440, 1445, 1605, 1607, 1612, 1619
\@mkboth	1727, 2341, 2355, 2369, 2388, 2408, 2427
\@plus	1568, 1731, 1875
\@pnumwidth	1570, 1571, 1576
\@restonecolfalse 1718, 2385, 2405, 2424
\@restonecoltrue	1720, 2383, 2403, 2422
\@roman	303, 315, 330, 342, 357, 369
\@standardmaketitle 1484, 1486, 1491, 1498, 1503
\@starttoc	2345, 2348, 2359, 2362, 2373, 2376, 2394, 2397, 2413, 2416, 2433, 2436
\@tempswafalse	2450
\@tempswatrue	2450
\@textsuperscript 1420, 1423, 1478, 1481, 1599, 1602
\@thanks	1379, 1385, 1406, 1412, 1435, 1441, 1493, 1499, 1554, 1555, 1614, 1617, 1647
\@thefnmark	467, 471, 474, 477, 1420, 1423, 1478, 1481, 1599, 1602, 1908
\@title	1333, 1340, 1359, 1363, 1365, 1368, 1396, 1453, 1457, 1459, 1462, 1509, 1627, 1639
\@titlepagefalse	70, 613
\@titlepagetrue	611
\@todonotes@drawLineToLeftMargin 1930
\@todonotes@drawLineToRightMargin 1933
\@todonotes@drawMarginNote 1929, 1932
\@todonotes@drawMarginNoteWithLine 1924
\@topnum	1432, 1490, 1611
_	517, 1554, 1823, 1825

A	
\abstractname 1941, 1945, 1957, 1964, 1968, 1975
\addfontfeature	1008, 1010
\addpenalty	1567
\addtolength	2055, 2056
\Alph	1777

B	
\backmatter	2478, 2479, 2481
\baselineskip 1005, 1054, 1060, 1078, 1136, 1140, 1144, 1148, 1152, 1156, 1160, 1163
\bibliografia (environment)	2487
\biblename	1301, 1307, 1315, 2492
\bookcolophon	1992

C	
\c@chapter	1773, 1793
\c@footnote 1353, 1419, 1477, 1555, 1598, 1905
\c@paragraph	1214, 1673
\c@section	1208, 1667, 1787
\c@subparagraph	1216, 1675
\c@subsection	1210, 1669
\c@subsubsection	1212, 1671
\c@tocdepth	1566
\captionsetup	490, 492, 493, 495, 496, 498, 500, 501
\cc	2019
\chapnumfont	1011, 1013, 1019, 1021
\chapter 1028, 1065, 1071, 1136, 1140, 1144, 1148, 1152, 1156, 1160, 1163, 1176, 1177, 1180, 1181, 1184, 1185, 1188, 1189, 1191, 1193, 1200, 1201, 1203, 1302, 1305, 1308, 1312, 1316, 1319, 1774, 1781, 2387, 2407, 2426, 2492, 2504
\chapterintro	2442, 2444, 2446, 2449
\chapterintroname	2454, 2455
\chaptermark	1802, 1822
\chaptertitlename	1823

\ClassError	51, 53,	F	\ifsuftesi@compact
55, 57, 59, 941, 1200, 1582, 1899,			19, 1143, 1183, 1683, 1700
2045, 2058, 2443, 2468, 2473, 2478			\ifsuftesi@compactaureo
\ClassWarningNoLine 1, 1337, 1341, 1345			\ifsuftesi@dottedtoc
\cleardoublepage	1620,		\ifsuftesi@draftdate
1749, 1758, 1991, 1999, 2484, 2485			39, 1834, 1839, 1848
\clearpage	1644, 1664, 1735, 2042		\ifsuftesi@elementschap
\cmdSUF@elements@chapposition	1026, 1034		\ifsuftesi@elementsheader
\cmdSUF@elements@chapsize	1024, 1033		36, 1801, 1869, 1911
\col@number	1425, 1483, 1604		\ifsuftesi@elementspagelayout
\collectioneditor	1562, 1564		38, 1159
\collectiontitle	1559, 1561		\ifsuftesi@elementsstructure
\colophon	1976		37
\columnsep	1733		\ifsuftesi@fewfootnotes
\columnseprule	1732		40, 1896
\contentsmargin	2104		\ifsuftesi@FSPL
\contentsname			42, 933, 2014
2340, 2341, 2387, 2389, 2390			\ifsuftesi@nocrop
\contentspage	1748, 2282, 2293,		24, 993
2300, 2307, 2314, 2321, 2328, 2335			\ifsuftesi@numparchap
\copyright	1982		28, 1064, 1077
\crop	603, 606		\ifsuftesi@numparpart
\csname	1335, 2055, 2056		27, 1223, 1237
		G	\ifsuftesi@numparsec
D			29, 1083
\date	1387, 1414, 1443, 1501		\ifsuftesi@numparsubsec
\DeclareFontFamily	980		30, 1100
\DeclareFontShape	981–990		\ifsuftesi@numparsubsubsec
\DeclareRobustCommand	80,		31, 1115
92, 105, 118, 131, 144, 169, 964,			\ifsuftesi@pagelefttoc
1007, 1009, 1015, 1017, 2458, 2461			44, 1581, 2103
\DeclareTextFontCommand	967		\ifsuftesi@partpage
\defbibheading	1269,		41, 1217
1272, 1275, 1279, 1283, 1286, 1289,			\ifsuftesi@periodical
1291, 1294, 1301, 1304, 1307,			17, 1135, 1179, 1680, 1696
1311, 1315, 1318, 1321, 1324, 1328			\ifsuftesi@periodicalaureo
\define@choicekey	64, 76, 182, 200,		18, 1139, 1175, 1689, 1708
220, 238, 246, 254, 262, 270, 278,			\ifsuftesi@porson
286, 294, 321, 348, 375, 382, 406,			12, 970
425, 449, 456, 463, 479, 487, 504,			\ifsuftesi@raggedtoc
510, 526, 556, 563, 573, 580, 586,			26, 1578
592, 598, 608, 615, 841, 850, 856, 865			\ifsuftesi@reverseauthortitle
\definecolor	919, 920		48, 1626, 1636
\dimen	976–978		\ifsuftesi@screen
\dimen@	973, 978, 979		43
\disable@keys	67, 775, 783, 796, 814, 833		\ifsuftesi@smallcapschap
\doi	1536, 1538		33, 1358, 1452
\dotfill	1575		\ifsuftesi@smallcapspart
\doublehyphendemerits	1916, 1917		32
		H	\ifsuftesi@smallcapssec
E			34, 1362, 1456
\emph	1556, 2035, 2515		\ifsuftesi@standardfont
\encodingdefault	966		11, 955
\endcsname	1335, 2055, 2056		\ifsuftesi@sufelements
\endlist	1879, 1885, 1895, 2500, 2513		23, 1768
\endquotation	1949, 1972		\ifsuftesi@sufplain
\ensuremath	1898		14, 1868
environments:			\ifsuftesi@supercompact
bibliografia	2487		21, 1151, 1187, 1686, 1704
sigle	2501		\ifsuftesi@supercompactaureo
theindex	1716		22, 1155
\ExecuteOptionsX	873		\ifsuftesi@twocolumnlof
\exhyphenpenalty	1915		46, 2357, 2411
\extramarks	1044		\ifsuftesi@twocolumnlot
		I	47, 2371, 2431
			\ifsuftesi@twocolumntoc
			45, 2343, 2392
			\ifxetex
			937, 1006, 2516
			\ifxheadbreak
			2460, 2462
			\ignorespaces
			1878, 1884
			\includeart
			1642
			\index
			1990
			\indexname
			1723, 1725, 1727
			\input
			1646
			\issn
			1533, 1535
			\issue
			1545, 1547
			\issuename
			1558
			\item
			1734, 1876, 1883, 1893
			\itemindent
			1872, 1889, 1890, 2495, 2507
			\itemsep
			1888
			\itlabel
			2502, 2512
			\itshape
			258, 266, 274, 282, 290,
			413, 414, 424, 860, 869, 1050,
			1256, 1633, 1812, 1818, 1912, 2502

- J**
- \journalname 1530, 1532
 - \journalnumber 1542, 1544
 - \journalvolume 1539, 1541
 - \journalwebsite 1551, 1553
 - \journalyear 1548, 1550
- L**
- \l@title 1565
 - \label 1629, 1646
 - \labelitemi 422
 - \labelsep 2506
 - \labelwidth 2497, 2509
 - \LARGE 1396, 1509, 1755
 - \Large 80, 1029
 - \LaTeX 1986, 2034, 2035
 - \leftmargin 1873, 1881, 1891, 1892, 2496, 2497, 2508, 2509
 - \leftmark 1812, 1865
 - \leftskip 470, 1572, 1573
 - \lineskip 1372, 1399, 1466, 1512, 1914
 - \lineskiplimit 1914
 - \list 1871, 1881, 1888, 2494, 2505
 - \listfigurename 2354, 2355, 2407–2409
 - \listoffigures 2352, 2401
 - \listoftables 2366, 2420
 - \listparindent 1871, 1872, 1890, 2510
 - \listtablename 2368, 2369, 2426, 2428, 2429
 - \LoadClass 63
 - \losname 1272, 1279, 1286, 1304, 1311, 1318, 2501, 2504
 - \lsstyle 1016, 1018
- M**
- \mainmatter 2473, 2474, 2476, 2485
 - \makelabel 2499, 2512
 - \MakeTextLowercase 378
 - \maketitle 1349, 1384, 1411, 1417, 1439, 1497, 1596
 - \Margini 1681, 1684, 1687, 1690, 1697, 1701, 1705, 1709
 - \marginpar 508, 1918, 1919
 - \marginparsep 1035, 1811, 1817
 - \marginparwidth 1812, 1817, 1818
 - \markboth 1271, 1274, 1278, 1282, 1303, 1306, 1310, 1314, 1802, 1823
 - \markright 1285, 1288, 1317, 1320, 1323, 1327, 1803, 1825
 - Miede, André 43
- N**
- \newcounter 1523–1526
 - \newlength 1004, 1062, 2052, 2067, 2070–2077, 2106–2121, 2233–2240
 - \newline 1632
 - \nobreak 1574, 1576, 1579, 1589
 - \node 1926
 - \noindent 1421, 1479, 1600, 1878, 1982, 1986, 1996, 1998, 2004, 2019, 2022, 2034
 - Nowacki, Janusz M. 2
 - \nr 64, 66, 76, 79, 182, 184, 200, 202, 220, 222, 238, 239, 246, 247, 254, 255, 262, 263, 270, 271, 278, 279, 286,
- S**
- \sbox 971, 972, 974, 975
 - \section 1043, 1048, 1084, 1090, 1092, 1098, 1270, 1273, 1276, 1280, 1284, 1287, 1322, 1325, 1329, 1723, 1941, 1964, 2340, 2354, 2368, 2452, 2489
 - \sectionmark 1803, 1825, 1827
 - \sectionsep 1004, 1005, 1090, 1098, 1106, 1113, 1121, 1128, 1221, 1258, 1265
 - \setlength 576, 578, 1005, 1031, 1078, 1080, 1805, 2053, 2068, 2078, 2080, 2082, 2084, 2086, 2088, 2090, 2092, 2122, 2124, 2126, 2128, 2130, 2132, 2134, 2136, 2138, 2140, 2142, 2144, 2146, 2148, 2150, 2152, 2242, 2244, 2246, 2248, 2250, 2252, 2254, 2257, 2259, 2261, 2263, 2265, 2267, 2269, 2271, 2495–2498, 2506–2511
 - \setlist 423, 424, 428–433, 435–440, 442–447
 - \SetTracking 926
 - \sfdefault 961
 - \single (environment) 2501
 - \small 461, 1350, 1372, 1377, 1390, 1466, 1471, 1776, 1779, 1943, 1966, 1986, 1998, 2004, 2010, 2022
 - \standardtitle 1389, 1475
 - \strip@pt 979
 - \subparagraph 1259, 1265
 - \subsection 1049, 1054, 1101, 1106, 1108, 1113, 1290, 1292, 1295
 - \substitutefont 963
 - \subsubsection 1055, 1060, 1116, 1121, 1123, 1128
 - \SUF@addto@tochang@chap 2114, 2138, 2141, 2151, 2153, 2160, 2165
 - \SUF@addto@tochang@fig 2120, 2150, 2219
 - \SUF@addto@tochang@par 2118, 2146, 2149, 2201, 2204
 - \SUF@addto@tochang@sec 2115, 2140, 2143, 2172, 2177
 - \SUF@addto@tochang@subpar 2119, 2148, 2210, 2213
 - \SUF@addto@tochang@subsec 2116, 2142, 2145, 2183, 2186
 - \SUF@addto@tochang@subsubsec 2117, 2144, 2147, 2192, 2195
 - \SUF@addto@tochang@tab 2121, 2152, 2227
 - \SUF@ADJnumparchap 1062, 1078, 1080, 1176, 1180, 1184, 1188, 1192
 - \SUF@appendices 1736, 1751, 1755
 - \SUF@appendixpage 1738, 1739
 - \SUF@authorfont@Switch 867, 869, 871, 1628, 1637
 - \SUF@CHAP@StyleSwitch 264, 266, 268, 1069, 1075
 - \SUF@chapnumfont 1012, 1020, 1032
 - \SUF@chaptersize 80, 92, 105, 118, 131, 144, 169, 1066, 1072, 1225, 1231, 1239, 1245, 1357, 1451, 1621, 1655
 - \SUF@chaptitlerule 514, 518, 522, 2282, 2292
 - \SUF@default@CHAPTER 1063, 1173
 - \SUF@default@SECTIONS 1082, 1174
 - \SUF@dotchap 325, 329, 333, 337, 341, 345, 1067, 1073
 - \SUF@dotpart 298, 302, 306, 310, 314, 318, 1226, 1232, 1240, 1246
 - \SUF@dotsec 352, 356, 360, 364, 368, 372, 1087, 1095
 - \SUF@elements@CHAPTER 1027, 1133

\SUF@elements@SECTIONS 1042, 1134
 \SUF@fchapterintroname 2452–2454
 \SUF@greekfamily 561, 566, 568, 571, 963, 965
 \SUF@headingssmallcaps 417–419, 1009, 1017
 \SUF@label@chap 2052, 2053, 2079,
 2081, 2123, 2151, 2153, 2161, 2243,
 2253, 2255, 2258, 2270, 2272, 2279
 \SUF@label@fig 2076, 2090, 2326
 \SUF@label@par 2074, 2086, 2089, 2131,
 2147, 2202, 2249, 2266, 2311–2313
 \SUF@label@part 1762, 2070, 2078, 2098
 \SUF@label@sec 2071, 2080, 2083, 2091,
 2093, 2125, 2141, 2151, 2153, 2173,
 2260, 2270, 2272, 2287, 2288, 2291
 \SUF@label@subpar 2075, 2088, 2133,
 2149, 2211, 2251, 2268, 2318–2320
 \SUF@label@subsec 2072, 2082, 2085, 2127,
 2143, 2184, 2245, 2262, 2297–2299
 \SUF@label@subsubsec 2073, 2084, 2087, 2129,
 2145, 2193, 2247, 2264, 2304–2306
 \SUF@label@tab 2077, 2092, 2220, 2228, 2333
 \SUF@leftmark 387, 391, 397, 401, 1857, 1862
 \SUF@leftrightmark 387, 391, 1864
 \SUF@Lheadstyle 387, 391, 397, 401, 410, 414, 418
 \SUF@lr@CHAPSwitch 203,
 205, 207, 209, 212, 215, 1066, 1072
 \SUF@lr@coll@titleSwitch 844, 846, 848, 1622
 \SUF@LR@MarkSwitch 1842, 1852, 1857, 1859, 1862
 \SUF@lr@PARTSwitch 185, 187, 189,
 191, 194, 197, 1225, 1231, 1239, 1245
 \SUF@lr@SECSwitch 223,
 225, 227, 229, 232, 235, 1085, 1093
 \SUF@lr@SUBSECSwitch 240, 242, 244, 1102, 1109
 \SUF@lr@SUBSUBSECSwitch 248, 250, 252, 1117, 1124
 \SUF@mpsetup 1910, 1920, 1921
 \SUF@PART@StyleSwitch 256, 258, 260, 1226, 1228,
 1232, 1234, 1240, 1242, 1246, 1248
 \SUF@quotation@size 459, 461, 1877, 1884, 1894
 \SUF@quote@style 452, 454, 1874, 1882
 \SUF@Rheadstyle 386, 390, 396, 400, 409, 413, 417
 \SUF@rightmark 386, 390, 396, 400, 1840, 1850, 1859
 \SUF@SEC@StyleSwitch 272, 274, 276, 1089, 1097
 \SUF@SUBSEC@StyleSwitch 280, 282, 284, 1105, 1112
 \SUF@SUBSUBSEC@StyleSwitch 288, 290, 292, 1120, 1127
 \SUF@thechapter 324, 328, 332, 336,
 340, 344, 1036, 1067, 1073, 1793, 1823
 \SUF@thepage 411, 415, 419, 1835, 1843, 1849
 \SUF@thepart 297, 301, 305,
 309, 313, 317, 1226, 1232, 1240, 1246
 \SUF@thesection 351, 355, 359,
 363, 367, 371, 1086, 1094, 1787, 1825
 \SUF@titlefont@Switch 858, 860, 862, 1627, 1639
 \SUF@titlerule 513, 517, 521, 2293,
 2300, 2307, 2314, 2321, 2328, 2335
 \SUF@titlesmallcaps 260, 268, 276, 284, 292,
 862, 871, 1007, 1015, 1039, 1047,
 1359, 1363, 1453, 1457, 1777, 1779
 \SUF@tochang 2067, 2068, 2123, 2139
 \SUF@tochang@chap 2106, 2122,
 2125, 2135, 2137, 2156, 2158, 2163
 \SUF@tochang@fig 2112, 2134, 2216, 2218
 \SUF@tochang@par 2110, 2130, 2133, 2198, 2200, 2203
 \SUF@tochang@sec 2107, 2124, 2127, 2169, 2171, 2176
 \SUF@tochang@subpar 2111, 2132, 2207, 2209, 2212
 \SUF@tochang@subsec 2108, 2126, 2129, 2180, 2182, 2185
 \SUF@tochang@subsubsec 2109, 2128, 2131, 2189, 2191, 2194
 \SUF@tochang@tab 2113, 2136, 2224, 2226
 \SUF@tocindent@chap 2233, 2257,
 2260, 2270, 2272, 2276, 2278, 2281
 \SUF@tocindent@fig 2239, 2252, 2269, 2323, 2325
 \SUF@tocindent@par 2237, 2248, 2251, 2265, 2268, 2309
 \SUF@tocindent@sec 2234, 2242, 2245, 2259, 2262, 2285
 \SUF@tocindent@subpar 2238, 2250, 2267, 2316
 \SUF@tocindent@subsec 2235, 2244, 2247, 2261, 2264, 2295
 \SUF@tocindent@subsubsec 2236, 2246, 2249, 2263, 2266, 2302
 \SUF@tocindent@tab 2240, 2254, 2271, 2330, 2332
 \SUF@toclabelnum 299, 303, 307, 311,
 315, 319, 326, 330, 334, 338, 342,
 346, 353, 357, 361, 365, 369, 373,
 1763, 2099, 2162, 2174, 2279, 2289
 \SUF@versionstring 1800, 1834, 1839, 1848
 \suftesi@articletrue 69
 \suftesi@authortitletrue 395, 399
 \suftesi@centerheadertrue 389, 402
 \suftesi@collectiontrue 72
 \suftesi@compactaureottrue 117
 \suftesi@compactctrue 104
 \suftesi@dotteddototrue 516
 \suftesi@draftdatetrue 595
 \suftesi@elementschaptrue 218
 \suftesi@elementsheadertrue 404
 \suftesi@elementspagelayouttrue 155
 \suftesi@fewfootnotestrue 482
 \suftesi@FSPLtrue 787, 804, 822
 \suftesi@maketextlowercase 378, 380, 1008, 1010, 1016, 1018
 \suftesi@nocropttrue 590, 601
 \suftesi@numparchaptrue 210, 213, 216
 \suftesi@numparparttrue 192, 195, 198
 \suftesi@numparsecttrue 230, 233, 236
 \suftesi@pagelefttotrue 524
 \suftesi@partpagetrue 582
 \suftesi@periodicalaureottrue 168, 786, 803, 821
 \suftesi@periodicaltrue 91
 \suftesi@porsontrue 569
 \suftesi@raggedtotrue 520
 \suftesi@reverseauthortitletrue 853
 \suftesi@standardfonttrue 560
 \suftesi@sufplaintrue 393
 \suftesi@supercompactaureottrue 143
 \suftesi@supercompacttrue 130
 \suftesi@twocolumnloftrue 532, 539, 546, 551
 \suftesi@twocolumnlottrue 535, 543, 547, 552
 \suftesi@twocolumnntotrue 529, 538, 542, 550

T

\tableofcontents 2338, 2381, 2463, 2464
 \temp 972, 975
 \textbullet 422
 \textcolor 1036
 \textgreek 967
 \textnormal 1045, 1051, 1057, 1103, 1110, 1118, 1125
 \textsc 301, 313, 328, 340, 355, 367
 \textsf 1989, 2036
 \textsuperscript 477
 \texttt 1800
 \thanks 1352,
 1383, 1392, 1410, 1438, 1450,
 1496, 1508, 1554, 1618, 1623, 1631
 \thechapter 1773
 \thecontentslabel 1763, 2099,
 2162, 2175, 2184, 2193, 2202,
 2211, 2220, 2228, 2279, 2290,
 2298, 2305, 2312, 2319, 2326, 2333
 \thecontentspage 2159, 2164,
 2172, 2177, 2183, 2186, 2192, 2195,
 2201, 2204, 2210, 2213, 2219, 2227
 \thefootnote 1353, 1419, 1477, 1598, 1905
 theindex (environment) 1716
 \thepage 411, 415, 419, 1807
 \theparagraph 1213, 1216, 1254, 1672, 1675
 \thesection 1045,
 1087, 1095, 1207, 1210, 1666, 1669
 \thesubparagraph 1215, 1261, 1674
 \thesubsection 1051,
 1103, 1110, 1209, 1212, 1668, 1671
 \thesubsubsection 1057, 1118, 1125, 1211, 1214, 1670, 1673
 \thetitle 1629, 1646
 \title 1333–1335, 1338, 1342
 \titleclass 1220
 \titlecontents 1741, 1759, 2095,
 2155, 2168, 2179, 2188, 2197,

2206, 2215, 2223, 2275, 2284, 2294, 2301, 2308, 2315, 2322, 2329	\tolerance 1915	\version@string 931, 1800
\titleformat 1028, 1043, 1049, 1055, 1065, 1071, 1084, 1092, 1101, 1108, 1116, 1123, 1224, 1230, 1238, 1244, 1252, 1259, 1774	\tw@ 972, 973, 975, 976	\versionstring 931, 932
\titlerule 513, 514, 517, 518	\twocolumn 1428, 1486, 1607, 1723, 1725, 2399, 2418, 2438	
\titlespacing 1048, 1054, 1060, 1090, 1098, 1106, 1113, 1121, 1128, 1136, 1140, 1144, 1148, 1152, 1156, 1160, 1163, 1176, 1177, 1180, 1181, 1184, 1185, 1188, 1189, 1191, 1193, 1221, 1258, 1265, 1781	U	
\toclabelspace ... 2057, 2060, 2064	\unitlength 1031, 1805	
\toclabelwidth ... 2054, 2061, 2065	\url 1551	
\today 1800	\usefont 965	
	V	
	\val 64, 76, 182, 200, 220, 238, 246, 254, 262, 270, 278, 286, 294, 321, 348, 375, 382, 406, 425, 449, 456, 463, 479, 487, 504, 510, 526, 556, 563, 573, 580, 586, 592, 598, 608, 615, 841, 850, 856, 865	
	X	
	\xfootnote 1907	
	\xheadbreak 2461	
	\xheadbreakfalse 1840, 1841, 1850, 1851, 2465	
	\xheadbreaktrue 2460	
	\XKV@classoptionslist 917	
	\XKV@useoption 907–916	
	Y	
	\year 1982, 2015	
	Z	
	Zapf, Hermann 2	