

User's Guide to `suftesi`

A document class for typesetting
theses, books and articles

Ivan Valbusa*

v2.9.3 – 2020/01/29

Abstract

The standard document classes allow you to typeset beautiful documents but their layout is quite far from the stylistic requests of some humanists (mainly Italian). The `suftesi` class provides a set of “humanistic” page layouts, title styles and heading styles to typeset books, articles and theses. The styles are very simple and sober and also have the aim of finding an aesthetic harmony in the formal simplicity (see Valbusa 2012). They are largely inspired by some interesting readings, particularly *The Elements of Typographic Style* by Robert Bringhurst (1992), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie* by Jan Tschichold (1975) and *First Principles of Typography* by Stanley Morison (1936).

Contents	3.8 Pre-defined styles	16
1 Use	3	4 New commands 16
2 Class features	3	4.1 Printing the cover page . . 16
2.1 Document structure	3	4.2 Printing the colophon . . 18
2.2 Page layouts	4	4.3 Breaking titles 19
2.3 Fonts	4	4.4 Miscellaneous 20
2.3.1 Mathematics	5	5 Sections font 21
2.3.2 Greek	5	6 Collections 21
2.4 The frontispiece	7	6.1 Options 22
2.5 The cover page	10	6.2 Commands 23
3 Options	10	7 Known issues 23
3.1 Layout	10	8 Backward compatibility 23
3.2 Font	11	References 24
3.3 Titles	12	The Code 25
3.4 Contents lists	13	
3.5 Headings	14	
3.6 Notes, lists, quotations . .	14	
3.7 Miscellaneous	15	

*Dipartimento di Scienze Umane, Università degli Studi di Verona — `ivan dot valbusa at univr dot it`

Legalese

Copyright © 2009-2020 Ivan Valbusa

This package is author-maintained. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c or later (<http://latex-project.org/lppl>). This software is provided “as is”, without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

The main feature of this class is the set of styles it provides. For this reason DO NOT MODIFY THE STYLES OF THIS CLASS WITH PACKAGES AND/OR COMMANDS WHICH CHANGE THE LAYOUT OF THE DOCUMENT. IF YOU DO NOT LIKE THESE STYLES, USE ANOTHER CLASS. If you use `suftesi` in a document typeset with another class (for example `book`), remember to clean up the preamble from all the layout redefinitions.

A brief history

The `suftesi` class was born as a result of the course *Introduzione a L^AT_EX per le scienze umane (Introduction to L^AT_EX for the human sciences)* which I held at the Graduate School of Human Sciences and Philosophy (Scienze Umane e Filosofia) of Verona University (Italy) in June 2010. Originally thought as a class to typeset theses, during these years it has developed many new features and styles. Finally it has become the referential class of the Joint Project *Formal Style for PhD Theses with LaTeX* of the University of Verona.

Acknowledgments

I would like to thank Professors Paola Di Nicola, Director of the Graduate School, and Ugo Savardi who suggested to propose the course precisely to that School; Gilberto D’Arduini, Matteo Lanza and Antonio Rinaldi, who installed L^AT_EX on the computers used during the course; Catia Cordioli, for her help in the organization of the lessons; Corrado Ferreri, responsible of the E-Learning Center, who provided the T_EX Live 2009 DVDs. Special thanks to Professors Enrico Gregorio, the Italian guru of T_EX, for the T_EXpert support and his priceless “magic formulas”, and Tommaso Gordini for his valuable advice in choosing and improving the class features during these years. I would finally thank all the participants to the course who patiently resisted the four intensive lessons. This work is dedicated to them.

Feedback

If you have any questions, feedback or requests please email me at `ivan dot valbusa at univr dot it`. If you need specific features not already implemented, remember to attach the example files.

1 Use

The `suftesi` class is called as usual by

```
\documentclass[options]{suftesi}
```

All the options defined by the class are in the $\langle key \rangle = \langle value \rangle$ format. In addition to these you can also use the options defined by the standard `book` class (on which `suftesi` is based) except those modifying the page dimensions (`a4paper`, `a5paper`, `b5paper`, `legalpaper`, `executivepaper` and `landscape`), which are automatically disabled. The class loads the packages listed in table 1.

For using the class with the $X_{\text{E}}\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ and $\text{Lua}\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ engines you need to load the `fontspec` package (`mathspec` is an alternative only for $X_{\text{E}}\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$) and to select a main font.

Global	caption, color, crop, enumitem, emptypage, extramarks, fancyhdr, fixltxhyph, fontenc, geometry, iftex, microtype, multicol, titlesec, titletoc, xkeyval, (ccllicenses)
pdf $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ only	fontenc, substitutefont
Lu $\text{a}\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ only	luatex85
defaultfont=standard	lmodern
palatino	textcomp, newpxtext, biolinum, inconsolata, newpxmath
libertine	textcomp, libertine, biolinum, inconsolata, newtxmath
cochineal	textcomp, cochineal, biolinum, inconsolata, newtxmath
compatibility	mathpazo, beramono
mathfont=extended	amsthm, mathalfa

Table 1: Packages loaded by `suftesi`

2 Class features

The `suftesi` class provides a large set of options to customize the style of page, titles, headings and other text elements (see section 3). The simplest way to get to know the class features is therefore to typeset one of the templates which you can find in the `/doc/latex/suftesi` folder in your $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ distribution (see also Valbusa 2012). The class files as well as the templates are also available online on the CTAN's website at <http://www.ctan.org/pkg/suftesi>.

2.1 Document structure

With `suftesi` you can typeset book-style documents (with chapters), article-style documents (without chapters) and collections of papers (see section 6). The kind of document is set by the `structure` option which defaults to `book` (see section 3).

```
\documentclass[structure=value],options]{suftesi}
```

2.2 Page layouts

The class provides nine page layouts which can be selected by the `pagelayout` option (table 2). The `standard` layout (default) or `standardaureo` layout are aimed to typeset A4 documents, while the other seven layouts are particularly suitable to typeset compact books, articles or theses. For these compact layouts the `version=screen` and `version=cscreen` options are particularly useful as they show the output in its real size. See section 3.1 for details.

Layout	Dimensions (mm)				Proportions			
	Typeblock		Page		Margins		Stock	
	w	h	w	h	t / b	i / o	Typeblock	Page
<code>standard</code>	110	220	210	297	1 : 2	1 : 2	1 : 2	1 : $\sqrt{2}$
<code>standardaureo</code>	136	220	210	297	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$
<code>compact</code>	110	165	160	240	2 : 3	2 : 3	2 : 3	2 : 3
<code>compactaureo</code>	118	191	160	240	2 : 3	2 : 3	5 : 8*	2 : 3
<code>supercompact</code>	100	150	140	210	2 : 3	2 : 3	2 : 3	2 : 3
<code>supercompactaureo</code>	108	175	140	210	1 : 1	1 : 1	5 : 8*	2 : 3
<code>periodical</code>	110	165	170	240	2 : 3	2 : 3	2 : 3	1 : $\sqrt{2}$
<code>periodicalaureo</code>	120	194	170	240	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$

* 5 : 8 \approx 1 : 1,618

Table 2: The layouts of `suftesi`

2.3 Fonts

The default roman font is Cochineal by Michael Sharpe, the sans serif font is Linux Biolinum O, designed by Philipp H. Poll, and the typewriter face is Inconsolata by Michael Sharpe. Cochineal is a fork of Crimson, by Sebastina Kosch, a font inspired by masterpieces like Sabon (Jan Tschichold) and Minion (Robert Slimbach). It is a very complete typeface and it offers full support for Greek and Cyrillic, real small caps (even in italic shape) and four figure styles. Moreover it provides support for mathematics through the `newtxmath` package.

The `defaultfont` option allows you to can change the default roman font to New PX (Palatino-like), Linux Libertine O, or Latin modern. You can use other fonts as well, but in this case remember to load the `defaultfont=none` option which turns off the default font settings (see section 3 for details).

Another beautiful Garamond-like font, complete of real small caps, bold weight and mathematical support, is made available by the `garamondx` package by Michael Sharpe, which provides an extension of the `ugm` fonts, (URW)++ GaramondNo8. They are not distributed as part of T_EXLive, but they may be downloaded using

the `getnonfreefonts` script. See the instructions for installation at <http://tug.org/fonts/getnonfreefonts/>.

2.3.1 Typesetting mathematics

The class loads by default a ‘minimal’ mathematical support for Cochineal (default), Linux Libertine O or New PX via the `newtxmath` or `newpxmath` packages by Michael Sharpe. Moreover the `mathfont` option is provided to extend or disable the support for mathematics when using these fonts. These non-standard fonts have a very good mathematical support but if you aim at typesetting high mathematics the Latin Modern font family remains, of course, the better choice: `defaultfont=standard`. See section 3.2 for details.

If some of the loaded packages conflict or if you simply want to change some of the default font settings you should first reset the font default with `defaultfont=none` option and then load the packages in the right order and with your favorite options.

2.3.2 Typesetting Greek

The Cochineal default font is complete of Greek and Cyrillic. Anyway the class provides the `greekfont` option (see section 3.2) to select four different Greek fonts for use with the roman typeface set by the `defaultfont` option (except for the `defaultfont=standard` option, i.e. with Latin Modern font family which uses the CB Greek by default). These fonts are: GFS Bodoni, GFS Artemisia, GFS Porson (by the Greek Font Society) and CB Greek (by Claudio Beccari). You may, of course, choose a different font but in this case, as previously cleared, remember to load the `defaultfont=none` option.

Cochineal/Cochineal Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον ειπείν περί τί και τίνος έστιν ή σκέψις, ότι περί απόδειξιν και έπιστήμης άποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον ειπείν περί τί και τίνος έστιν ή σκέψις, ότι περί απόδειξιν και έπιστήμης άποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον ειπείν περί τί και τίνος έστιν ή σκέψις, ότι περί απόδειξιν και έπιστήμης άποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον ειπείν περί τί και τίνος έστιν ή σκέψις, ότι περί απόδειξιν και έπιστήμης άποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Libertine Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρώτον είπεΐν περι τί και τίνος έστιν ή σκέψις, ότι περι απόδειξιν και έπιστήμης αποδεικτικής· είτα διορίσαι τί έστι πρότασις και τί όρος και τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. *Πρώτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἶτα διορίσαι τί ἐστὶ πρότασις καὶ τί ὄρος καὶ τί συλλογισμὸς* Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. *Πρώτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἶτα διορίσαι τί ἐστὶ πρότασις καὶ τί ὄρος καὶ τί συλλογισμὸς* Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Latin Modern/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. *Πρώτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἶτα διορίσαι τί ἐστὶ πρότασις καὶ τί ὄρος καὶ τί συλλογισμὸς* Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

2.4 The frontispiece

The class has an original frontispiece (see figure 1) now directly available loading the `frontespizio` package with the `suftesi` option. It is meant only for Italian users (see Gregorio 2009, version 1.4 or later):

```
\usepackage[suftesi]{frontespizio}
```

Note that this frontispiece requires the use of a logo which could be restricted by some institutions. So before using it you have to be sure that you have the required permissions.

The `frontespizio` package produces a frontispiece in the standard Computer Modern typeface. If you prefer a consistent font remember to load the needed packages or commands in the `\Preambolo` command:

```
\begin{frontespizio}
  \Preambolo{\usepackage[osf]{cochineal}}% <===
  \Universita{Paperopoli}
  \Dipartimento{Filosofia, Pedagogia e Psicologia}
  \Corso[Laurea]{Filosofia}
  \Annoaccademico{2030--2031}
  \Titolo{La mia tesi:\\ una lunga serie di risultati\\
    difficilissimi e complicatissimi}
  \Sottotitolo{Alcune considerazioni mutevoli}
  \Candidato[vr12301231]{Paolo Rossi}
  \Relatore{Guido Bianchi}
\end{frontespizio}
```



University of St. Anford
Department of Typography

Ph.D. degree in $\text{T}_{\text{E}}\text{X}$ and $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$

How to prepare a formal frontispiece

Theory and practice

Candidate:
Enrico Gregorio

Thesis advisor:
Prof. R. J. Drofnsats

Research supervisors:
J. H. Quick
B. L. User

Thesis submitted in 2010

Figure 1: The frontispiece of `suftesi`




Figure 2: An example of the cover page of `suftesi`

2.5 The cover page

Since version 2.6 `suftesi` provides a command to print a simple cover page (figure 2), inspired by the Italian designer Bruno Munari (1966, pp. 85-89). The color used for the text and the circle as well as other graphical elements are partially customizable (see section 3 for details). The cover shown in figure 2 is obtained with the following code:

```
\Cauthor{Bruce Lee}
\Ctitle{The Art of Kicking}
\Csubtitle{How to survive in the modern societies}
\Ceditor{edited by\\ Walker Texas Ranger}
\Cfoot{Punch Press\\ \fbox{\bfseries P&P}}
\Cpagecolor{white!90!black}
\Ctextcolor{white}
\Cfootcolor{black}

\makecover[ball color=DarkBlue,draw=none]
```

To produce a complete book cover, with spine and dust jacket, you should take a look at the `bookcover` package by Tibor Tómacs.

3 Options

3.1 Layout

`structure=book, article, collection` default: `book`

- book** For typesetting texts with chapters.
- article** For typesetting articles or short theses (without chapters).
- collection** For typesetting journals or collections of articles (see section 6).

`pagelayout=standard, standardaureo, periodical,` default: `standard`
`periodicalaureo, compact, compactaureo,`
`supercompact, supercompactaureo`

standard Prints an A4 page with a typeblock of 110 mm × 220 mm.

With the following values the option prints the typeblock on an A4 paper showing the crop marks which can be controlled by the `version` option.

periodical Prints a page of 17 cm × 24 cm with a typeblock of 11 cm × 16.5 cm.

periodicalaureo The same of `periodical` but with a *golden ratio* typeblock of 120 cm × 194 mm.

compact Prints a page of 16 cm × 24 cm with a typeblock of 11 cm × 16.5 cm.

compactaureo The same as `compact` but with a *golden ratio* typeblock of 11.8 cm × 19.1 cm.

supercompact Prints a page of 14 cm × 21 cm with a typeblock of 10 cm × 15.5 cm.

supercompactaureo The same as **supercompact** but with a *golden ratio* typeblock of 10.8 cm × 17.5 cm.

The details of this option are shown in table 2.

version=screen, cscreen, draft, final default: **final**

screen Prints the PDF with its real dimensions.

cscreen The same as **version=screen** but with a centered typeblock.

These previous two options are provided to have a better view when you are typesetting and reading the PDF on the screen or for online publications. The following options meant for printed documents.

draft Prints the output on a A4 paper, showing the crop marks. Useless with **standard** and **standardaureo** layouts.

final Prints the output on a A4 paper, hiding the crop marks. Useless with **standard** and **standardaureo** layouts.

Sometimes it is not desirable to have the crop marks on every page. In such a case you can use the `\crop[off]` command after the first page of the document.

3.2 Font

The first three options are available only with \LaTeX . Using \XeLaTeX or \LuaLaTeX the default font is the Computer Modern but you can change it through the `fontspec` or `mathspec` (\XeLaTeX only) packages. If you do not need to typeset mathematics, with these engines I do suggest the EB Garamond font family by Georg Duffner.

defaultfont=none, cochineal, libertine, palatino, standard default: **cochineal**

none Does not load any font. Use this option if you want full control over the font selection.

cochineal Loads the Cochineal serif, the Linux Biolinum O sans serif and the Inconsolata typewriter.

libertine Loads the Linux Libertine O serif, the Linux Biolinum O sans serif and the Inconsolata typewriter.

palatino Loads the New PX serif, the Linux Biolinum O sans serif and the Inconsolata typewriter. Note that the New PX font does not provide support for Greek. The `greekfont=artemisa` option offers a very good solution.

standard Loads the `lmodern` package: Latin Modern font family and CB Greek.

greekfont=none, artemisia, porson, bodoni, cbgreek default: none

Actually useless with **defaultfont**=none and not available with **defaultfont**=standard options.

- none** Does not load any Greek font.
- artemisia** Loads the Artemisia font by the Greek Font Society.
- porson** Loads the Porson font by the Greek Font Society.¹
- bodoni** Loads the Bodoni font by the Greek Font Society.
- cbgreek** Loads the standard CB Greek font by Claudio Beccari.

mathfont=none,minimal,extended default: minimal

Available only with Cochineal, Libertine and New PX fonts.

- none** Do not load any mathematical support. Use this option if you need some packages that have to be loaded before **newtxmath** and **newpxmath**.
- minimal** Loads **newtxmath** (for Cochineal and Linux Libertine O) or **newpxmath** (for PX Fonts).
- extended** Loads the previous option plus the **amsthm** and **mathalfa** packages.

smallcapsstyle=low, upper default: low

Active only with $\langle level \rangle$ **font**=smallcaps and **toc** $\langle level \rangle$ **font**=smallcaps options (see sections 3.3 and 3.4). With X_YL^AT_EX or LuaL^AT_EX this option is effective only if a font selection command (such as \backslash setmainfont) is given.

- low** Prints lowercase spaced SMALL CAPITALS.
- upper** Prints spaced SMALL CAPITALS with uppercase initials.

3.3 Titles

$\langle level \rangle$ **font**=roman, italic, smallcaps default: roman

- roman** Prints the $\langle level \rangle$ title in roman.
- italic** Prints the $\langle level \rangle$ title in *italic*.
- smallcaps** Prints the $\langle level \rangle$ title in SPACED SMALL CAPS

Where $\langle level \rangle$ can be **part**, **chap**, **sec**, **subsec**, **subsubsec**.

$\langle level \rangle$ **style**=left, center, right, parleft, parcenter, parright default: left

- left** Aligns the $\langle level \rangle$ title on the left.

¹The first code for the Porson font (**suftesi** <v.2.4) has been written by Enrico Gregorio. Claudio Beccari successively added the code to improve the scale factor when using this greek font in combination with Palatino.

center Centers the $\langle level \rangle$ title.
right Aligns the $\langle level \rangle$ title on the right.

Where $\langle level \rangle$ can be `part`, `chap`, `sec`, `subsec`, `subsubsec`.

parleft As `left` but with the title below the number.
parcenter As `center` but with the title below the number.
parright As `right` but with the title below the number.

Where $\langle level \rangle$ can be `part`, `chap`, `sec`.

$\langle level \rangle$ `numstyle=arabic, roman, Roman, dotarabic, dotroman, dotRoman` default: `Roman/arabic/arabic`

arabic Arabic $\langle level \rangle$ number.
roman Small caps lowercase roman $\langle level \rangle$ number.
Roman Uppercase roman $\langle level \rangle$ number.
dotarabic As `arabic` but followed by a dot.
dotroman As `roman` but followed by a dot.
dotRoman As `Roman` but followed by a dot.

Where $\langle level \rangle$ can be `part`, `chap`, `sec`.

3.4 Contents lists

`tocstyle=standard, dotted, ragged, leftpage` default: `standard`

standard Prints a standard table of contents with page numbers on the right margin.
dotted As the previous one but with dotted lines.
ragged Aligns the table of contents on the left as suggested by Bringhurst (1992).
leftpage Prints a table of contents with page numbers on the left margin.

`toc $\langle level \rangle$ font=roman, italic, smallcaps` default: `roman`

roman Prints the $\langle level \rangle$ TOC entry in roman.
italic Prints the $\langle level \rangle$ TOC entry in *italic*.
smallcaps Prints the $\langle level \rangle$ TOC entry in SPACED SMALL CAPS

Where $\langle level \rangle$ can be `chap`, `sec`, `subsec`, `subsubsec`.

`twocolcontents=toc, lof, lot, toclof, tocloc, loflot, all` default: `all`

This option activates the `tocstyle=ragged` option and disables the other values of `tocstyle`.

toc	Prints the table of contents in two columns.
lof	Prints the list of figures in two columns.
lot	Prints the list of tables in two columns.
toclof	Prints the table of contents and the list of figures in two columns.
toclot	Prints the table of contents and the list of tables in two columns.
loflot	Prints the list of figures and the list of tables in two columns.
all	Prints all the contents lists in two columns.

3.5 Headings

headerstyle=inner, center, plain, authortitleinner, authortitlecenter default: inner

inner	Prints the chapter title and the string “Chapter $\langle n \rangle$ ” in the inner side respectively of even and odd headers, and the page number in the outer side.
center	Centers the header and footer and puts the page number in the center of the footer.
plain	Prints no headers and puts the page number in the center of the footer.
authortitleinner	Prints the author’s name on the even pages and the title on the odd ones. In order to use this option the <code>\title</code> and <code>\author</code> commands are required.
authortitlecenter	As the previous one but with centered headers and footers.

headerfont=roman, italic, smallcaps default: roman

roman	Prints the headers in roman.
italic	Prints the headers in <i>italic</i> .
smallcaps	Prints the headers in SPACED SMALL CAPS.

3.6 Notes, lists, quotations

quotestyle=center, right default: center

center	Indents the block quotations on both the left and right margins.
right	Indents the block quotations only on the left margin.

quotesize=footnotesize, small default: footnotesize

footnotesize	Prints the block quotations in <code>\footnotesize</code> size.
small	Prints the block quotations in <code>\small</code> size.

footnotestyle=bulged, hung, dotted, superscript default: bulged

- bulged** The footnote number protrudes beyond the left margin.
- hung** Indents the footnote text, so it will hang under the first line of the text.
- dotted** The footnote number is aligned to the left margin and followed by a dot.
- superscript** Prints a superscript footnote number aligned to the left margin.

fewfootnotes=true, false default: **false**

Uses symbols instead of numbers to mark footnotes. It is active only in documents with three footnotes per page maximum. The symbol sequence is: *, **, ***. With more footnotes you should not need this option.

liststyle=bulged, aligned, indented default: **bulged**

- bulged** The item number or symbol protrudes beyond the left margin.
- aligned** Aligns the lists to the left margin.
- indented** Prints standard indented lists.

captionstyle=standard, sanserif, italic, smallcaps default: **standard**

All these values print the caption in small size, changing the shape:

- standard** Prints the caption text and label in normal font.
- sanserif** Prints the caption text and label in sanserif.
- italic** Prints the caption text and label in *italic*.
- smallcaps** Prints only the caption label in SPACED SMALL CAPS.

3.7 Miscellaneous

parindent=compact, wide default: **compact**

- Sets the indentation of the first line of each paragraph except those following a section title.
- compact** Sets indentation to 1 em.
- wide** Sets indentation to 1.5 em.

marginpar=true, false default: **true**

- true** Prints the marginal notes.
- false** Hide the marginal notes.

partpage=true, false default: **false**

Active only with **structure=article**.

- true** Prints the part title in a separate page as in **structure=book**

false Prints a part title similar to the one used in the standard `article` class.

`draftdate=true, false` default: `false`

If `true` it prints the string “Version of $\langle date \rangle$ ” in the footer. It requires the `\date{\langle date \rangle}` command.

3.8 Pre-defined styles

These pre-defined styles are intended as shortcuts to some groups of class options. Combining them with `chapnumstyle` options you can get up to 120 variants.

`style=roman(1-6), italic(1-12), smallcaps(1-6)` default: `roman1`

roman(1-6) The titles of chapters and headers are printed in roman. The number of the chapter is on the same line in styles 1-3 and above the title in styles 4-6. The title can be printed on the left (styles 1 and 4), in the center (styles 2 and 5) or on the right (styles 3 and 6).

italic(1-12) The titles of chapters and headers are in *italic*. The section title is in *italic* in styles 1-6 and in SPACED SMALL CAPS in styles 7-12. There are three position for the title and two positions for the number as above.

smallcaps(1-12) The titles of chapters and headers are in SPACED SMALL CAPS. The title of the section is in *italic* in styles 1-6 and in SPACED SMALL CAPS in styles 7-12. There are three position for the title and two positions for the chapter as above.

4 New commands

4.1 Printing the cover page

`\makecover`

`\makecover[\langle tikz options \rangle]`

Prints the cover page (figure 2). This command requires `tikz` and the optional arguments accepts the same options of the `\draw` command of that package (see the examples below). Commands available:

`\Cauthor{\langle text \rangle}`

Printed at the top of the circle.

`\Ctitle{\langle text \rangle}`

Printed below the author.

`\Csubtitle{text}`

Printed below the title.

`\Ceditor{text}`

Printed below the subtitle.

`\Cfoot{text}`

Printed in the footer.

The color of the circle can be customized using the optional argument of the `\makecover` command. For the other elements of the cover page the following commands are available. (You can load `xcolor` with your favorite option to access to many beautiful colors.)

`\Cpagecolor{color}`

The color of the cover page.

`\Ctextcolor{color}`

The color of the text inside the circle.

`\Cfootcolor{color}`

The color of the text in the footer.

Some examples of cover pages

First you have to declare the informations you want to put in the cover page. It is better to give these informations in the preamble:

```
\usepackage{tikz}

\Author{Bruce Lee}
\Title{The Art of Kicking}
\Csubtitle{How to survive in the modern societies}
\Ceditor{edited by\\ Walker Texas Ranger}
\Cfoot{Punch Press\\ \includegraphics[width=1cm]{logo}}
```

Then you can print the cover page with:

```
\makecover
```

or

```
\makecover[<tikz options>]
```

You can customize the circle using the optional arguments of the `\makecover` command. Some of these *<tikz options>* require special `tikz` libraries. For example, you can add a shadow to the circle loading the `shadows` library and using the `circular drop shadow` option:

```
\usepackage{tikz}
\usetikzlibrary{shadows}
...
\begin{document}
\makecover[circular drop shadow]
\end{document}
```

There are thousands of possibilities. Here is another (not necessarily good) example:

```
\usepackage{tikz}

\Cpagecolor{gray!30}
\Ctextcolor{blue!50}
\Cfootcolor{black}

\begin{document}
\makecover[fill=blue!30!black,draw=teal,line width=2mm,dashed]
\end{document}
```

4.2 Printing the colophon

```
\colophon[<OS>]{<name and surname>}{<additional info>}
```

This command is provided only for Italian documents. It prints a page with a copyright notice and the colophon in the bottom of the page. For different languages use `\bookcolophon` instead (see below).

If you don't need the copyright notice, leave the second argument of the command empty:

```
\colophon[<OS>]{<additional info>}
```

With the `article` document structure, you can use the `\artcolophon` command (see below) as well as the `\thanks` command:

```
\author{Name Surname
\thanks{This work has been typeset with \LaTeX, using the
\textsf{suftesi} class by Ivan Valbusa}.
```

`\bookcolophon{<copyright notice>}{<attribution notice and other informations>}`

Similar to `\colophon` but fully customizable. The first argument prints its content (usually the copyright notice) in the center of the page. The second one prints its content at the bottom. For example:

```
\bookcolophon{%
  Copyright © 2007 by Ivan Valbusa}{%
  This work has been typeset with \LaTeX, using the \textsf{suftesi}
  class by Ivan Valbusa\index{Valbusa, Ivan}. The serif font is
  Cochineal by Michael Sharpe and the sans serif font is Linux
  Biolinum 0 by Philipp H. Poll.}
```

`\artcolophon{<copyright notice, attribution and other informations>}`

This command only has one argument. It simply prints its content at the bottom of the page. Here is an example:

```
\artcolophon{%
  This work is licensed under the Creative Commons
  Attribution-NonCommercial-NoDerivs 3.0 Unported
  License. To view a copy of this license, visit
  \begin{center}
    http://creativecommons.org/licenses/by-nc-nd/3.0
  \end{center}
  or send a letter to Creative Commons, 444
  Castro Street, Suite 900, Mountain View,
  California, 94041, USA.\\[1ex]

  Typeset with \LaTeX, using the \textsf{suftesi}
  class by Ivan Valbusa.}
```

`\finalcolophon{<colophon content>}`

The same as `\artcolophon`, but centering its content at the top of the page. It is aimed at typesetting a classical *colophon* at the end of the work.

4.3 Breaking titles

`\headbreak`

A manual break which is active for the table of contents but not in the text or in the headers.

```
\section{This title will be break here \headbreak{}}
  inside the table of contents}
```

`\xheadbreak`

A manual break which is active in the text but not in the headers and in the table of contents.

```
\section{This title will be break here \xheadbreak{  
inside the text}
```

4.4 Miscellaneous

`\xfootnote[symbol]{footnote text}`

A command to print a footnote with a discretionary symbols given in the optional argument (default=*). It does not increment the footnote counter.

```
\xfootnote[ $\dagger$ ]{Footnote text}  
\xfootnote[\textdagger]{Footnote text}
```

`\title[short title for headers]{complete title for titlepage}`

Useful with `headerstyle=authortitle` option if the title is too long or has some breaks.

`\toclabelwidth{level}{dim}`

Adds the `<dim>` to the `<level>` label in the table of contents, where `<level>` can be `part`, `chap`, `sec`, `subsec`, `subsubsec`, `par`, `subpar`, `fig`, `tab`. For example, when using `chapnumstyle=Roman` you would probably need to adjust the width of the chapter label with:

```
\toclabelwidth{chap}{1em}
```

`\chapterintro`

Prints an unnumbered introduction at the beginning of the chapter, with the correct hyperlink. In order to use this command the `hyperref` package must be loaded.

`\chapterintroname{name}` (default=`Introduzione`)

Changes in `<name>` the title printed by the `\chapterintro` command.

`\appendixpage`

Prints a page with the argument of `\appendicesname` (default=`Appendici`) at the center. Particularly useful if you have two or more appendices.

`\appendicesname{<name>}` (default=Appendici)

Changes in *<name>* the title printed by the `\appendixpage` command.

5 Sections font

`<level>font{<commands>}` (default=empty)

Changes the font of the *<level>* title. Where *<level>* can be `part`, `chap`, `sec`, `subsec`, `subsubsec`. For example:

```
\chapfont{\bfseries\sffamily\scshape\Huge}
```

Changes the font of the *<level>* number. Where *<level>* can be `part`, `chap`, `sec`, `subsec`, `subsubsec`. Note that you have to adjust the spacing accordingly. For example, with the default chapter style:

```
\chapnumfont{%  
  %\chapnumfont{\bfseries\fontsize{160}{50}\selectfont  
  %\color{gray}\arabic{chapter}\hskip-15cm}
```

6 Collections

The collection document structure is thought to create a collection of papers. Each paper has to be typeset in a separate `.tex` file inside the `article` environment:

```
\begin{article}  
  \author{Author}  
  \title{Title of the paper}  
  % The abstract is optional.  
  % \begin{abstract}  
  % The abstract  
  % \end{abstract}  
  
  \maketitle  
  
  Text of the paper  
\end{article}
```

If the names of the papers are `article1.tex`, `article2.tex`, `article3.tex`, etc., then a minimal main file should be similar to this:

```
\documentclass[structure=collection]{suftesi}  
  
\begin{document}  
  \input{article1}  
  \input{article2}
```

```
\input{article3}
\end{document}
```

6.1 Options

In addition to the following options you can use the other options of the class too. In particular, with the `chapstyle` and `chapfont` options you can customize all the section titles which are treated as a normal unnumbered chapters in the book document structure, such as “Table of Contents”, “Index”, “Bibliography”, etc.

`papertitlestyle=left, center, right` default: left

left Aligns the author-title block on the left.
center Centers the author-title block.
right Aligns the author-title block on the right.

`revauthortitle=true, false` default: false

true Prints the author’s name below the title.
false Prints the author’s name above the title.

`titlefont=roman, italic, smallcaps` default: italic

roman Prints the title of the articles in roman.
italic Prints the title of the articles in *italic*.
smallcaps Prints the title of the articles in SPACED SMALL CAPS.

`authorfont=roman, italic, smallcaps` default: roman

roman Prints the author’s name in roman.
italic Prints the author’s name in *italic*.
smallcaps Prints the author’s name in SPACED SMALL CAPS.
Note that if you use this last option you need to protect the `\thanks` command:

```
\author{The Author\protect\thanks{...}}
```

`toctitlefont=roman, italic, smallcaps` default: italic

roman Prints the title TOC entry in roman.
italic Prints the title TOC entry in *italic*.
smallcaps Prints the title TOC entry in SPACED SMALL CAPS.

`tocauthorfont=roman, italic, smallcaps` default: roman

roman Prints the author’s name TOC entry in roman.
italic Prints the author’s name TOC entry in *italic*.
smallcaps Prints the author’s name TOC entry in SPACED SMALL CAPS.

6.2 Commands

`\frontispiece`

Typeset the frontispiece of the collection.

It requires the `\collectiontitle` and `\collectioneditor` commands in the preamble of your document.

`\collectiontitle{\textit{The Title of the Collection}}`

Sets the title of the collection.

`\collectioneditor{\textit{The Editor(s)}}`

Sets the editor(s) of the collection.

7 Known issues

A problem occurs with the article document structure. The `\part` command resets the headers so if it is the first sectioning command of the page you will get no headers in that page. In this case you have to add the header manually with something like this:

```
\markboth{Section title}{Section title}
\part{The title of the part}
%
\section{Section title}
```

If the title of the part is at the beginning of the page you will need the `afterpage` package and the `\afterpage` command:

```
\afterpage{
  \markboth{Section title}{Section title}
  \part{The title of the part}
}
%
\section{Section title}
```

8 Backward compatibility

`defaultfont=compatibility`

Loads the fonts of `suftesi v2.3` (and previous): Palatino (`mathpazo`), Iwona, Bera Mono. To get the default Greek font of those versions (i.e. Artemisia) add the `greekfont=artemisia` option.

`documentstructure=book, article, collection`

default: book

An alias for `structure`

`crop=true, false`

default: true

`true` An alias for `version=draft` option.

`false` An alias for `version=center` option.

`style=FSPLa, FSPLb, FSPLc`

These styles are only meant to typeset a doctoral thesis respecting the features required by the Joint Project *Formal Style for PhD Theses with LaTeX* of the Verona University (Italy).

The `\FSPLcolophon{<Name Surname>}` command is provided to typeset the colophon according to these styles:

© 2020 <Name Surname>

This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/3.0/>.

Typeset with L^AT_EX in collaboration with the Joint Project *Formal Style for PhD Theses with L^AT_EX* (University of Verona, Italy) using the `suftesi` class by Ivan Valbusa. The text face is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by Janus M. Nowacki.

References

This bibliography has been typeset with the `biblatex-philosophy` package, created by the same author of this class.

- Bringhurst, Robert (1992), *The Elements of Typographic Style*, 4th ed. (version 4.0), Hurtley & Marks Publisher, Vancouver; trans. *Gli elementi dello stile tipografico*, 5th ed., Sylvestre Bonnard, Milano 2009.
- Gregorio, Enrico (2009), *Il pacchetto frontespizio*, version 1.1, <http://www.guit.sssup.it/phpbb/index.php>.
- Miede, André (2011), *A Classic Thesis style*, <http://mirrors.ctan.org/macros/latex/contrib/classicthesis/ClassicThesis.pdf>.
- Morison, Stanley (1936), *First Principles of Typography*, Cambridge University Press, Cambridge; trans. *I principi fondamentali della tipografia*, Fabrizio Serra editore, Pisa-Roma 2008.
- Munari, Bruno (1966), *Arte come mestiere*, Laterza, Roma-Bari.
- Tschichold, Jan (1975), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie*, Birkhäuser Verlag, Basel; trans. *La forma del libro*, Sylvestre Bonnard, Milano 2003.
- Valbusa, Ivan (2012), “La forma del testo umanistico. La classe `suftesi`”, *ArsT_EXnica*, 14 (Oct. 2012), pp. 15-30, <http://www.guitex.org/home/images/ArsTeXnica/AT014/valbusa.pdf>.

The Code

```
1 \ClassWarningNoLine{suftesi}{%
2 *****\MessageBreak
3 * DO NOT MODIFY THE STYLES OF THIS CLASS\MessageBreak
4 * WITH PACKAGES AND/OR COMMANDS WHICH\MessageBreak
5 * MAY CHANGE THE LAYOUT OF THE DOCUMENT.\MessageBreak
6 * SEE DOCUMENTATION FOR DETAILS.\MessageBreak
7 * ANYWAY, DON'T WORRY!\MessageBreak
8 * THIS IS A HARMLESS MESSAGE :-)\MessageBreak
9 *****}
10 \RequirePackage{xkeyval}
11 \newif\ifsuftesi@compatibility
12 \newif\ifsuftesi@nofont
13 \newif\ifsuftesi@greekfont
14 \newif\ifsuftesi@standard
15 \newif\ifsuftesi@cochineal
16 \newif\ifsuftesi@libertine
17 \newif\ifsuftesi@palatino
18 \newif\ifsuftesi@porson
19 \newif\ifsuftesi@artemisia
20 \newif\ifsuftesi@bodoni
21 \newif\ifsuftesi@cbgreek
22 \newif\ifsuftesi@mathminimal
23 \newif\ifsuftesi@mathextended
24 \newif\ifsuftesi@centerheader
25 \newif\ifsuftesi@sufplain
26 \newif\ifsuftesi@article
27 \newif\ifsuftesi@authortitle
28 \newif\ifsuftesi@periodical
29 \newif\ifsuftesi@periodicalaureo
30 \newif\ifsuftesi@compact
31 \newif\ifsuftesi@compactaureo
32 \newif\ifsuftesi@supercompact
33 \newif\ifsuftesi@supercompactaureo
34 \newif\ifsuftesi@screen
35 \newif\ifsuftesi@screencentered
36 \newif\ifsuftesi@dottedtoc
37 \newif\ifsuftesi@raggedtoc
38 \newif\ifsuftesi@numparpart
39 \newif\ifsuftesi@numparchap
40 \newif\ifsuftesi@numparsec
41 \newif\ifsuftesi@numparsubsec
42 \newif\ifsuftesi@numparsubsubsec
43 \newif\ifsuftesi@smallcapspart
44 \newif\ifsuftesi@smallcapschap
45 \newif\ifsuftesi@smallcapssec
46 \newif\ifsuftesi@draftdate
47 \newif\ifsuftesi@fewfootnotes
48 \newif\ifsuftesi@partpage
```

```

49 \newif\ifsuftesi@FSPL
50 \newif\ifsuftesi@pagelefttoc
51 \newif\ifsuftesi@twocolumntoc
52 \newif\ifsuftesi@twocolumnlof
53 \newif\ifsuftesi@twocolumnlot
54 \newif\ifsuftesi@reverseauthortitle
55 \newif\ifsuftesi@collection
56 \DeclareOption{a4paper}{%
57   \ClassWarningNoLine{suftesi}{Option 'a4paper' not available}{}}
58 \DeclareOption{a5paper}{%
59   \ClassWarningNoLine{suftesi}{Option 'a5paper' not available}{}}
60 \DeclareOption{b5paper}{%
61   \ClassWarningNoLine{suftesi}{Option 'b5paper' not available}{}}
62 \DeclareOption{legalpaper}{%
63   \ClassWarningNoLine{suftesi}{Option 'legalpaper' not available}{}}
64 \DeclareOption{executivepaper}{%
65   \ClassWarningNoLine{suftesi}{Option 'executivepaper' not available}{}}
66 \DeclareOption{landscape}{%
67   \ClassWarningNoLine{suftesi}{Option 'landscape' not available}{}}

```

The `suftesi` class is based on the standard book class but the previous options are disabled as they contrast with the layouts provided by the class.

```

68 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{book}}
69 \ProcessOptions
70 \relax
71 \LoadClass{book}

```

Document structure

```

72 \define@choicekey{}{structure}[\val\nr]
73   {book,article,collection}[book]{%
74   \ifcase\nr\relax
75   \disable@keys{}{secnumstyle}
76   \or
77   \suftesi@articletrue
78   \@titlepagefalse
79   \or
80   \suftesi@collectiontrue
81   \setkeys{}{headerstyle=authortitleinner}
82   \fi}
83 \define@choicekey{}{documentstructure}[\val\nr]
84   {book,article,collection}[book]{%
85   \ClassWarningNoLine{suftesi}{%
86     'documentstructure' option is deprecated.\MessageBreak
87     Use 'structure' option instead}
88   \ifcase\nr\relax
89     \setkeys{}{structure=book}
90   \or
91     \setkeys{}{structure=article}
92   \or
93     \setkeys{}{structure=collection}
94   \fi}

```

Page layout

```
95 \RequirePackage{geometry}
96 \define@choicekey{}{pagelayout}[\val\nr]
97   {standard,standardaureo,periodical,compact,compactaureo,supercompact,
98   supercompactaureo,periodicalaureo}[standard]{%
99 \ifcase\nr\relax
100  \DeclareRobustCommand{\SUF@chaptersize}{\Large}
101  \DeclareRobustCommand{\SUF@sectionsize}{\large}
102  \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
103  \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
104  \geometry{%
105    heightrounded,
106    a4paper,
107    includeheadfoot=true,
108    textwidth=    110mm,
109    textheight=   220mm,
110    marginratio=  2:3,
111    marginparwidth= 30mm,
112    marginparsep= 12pt}
113 \or
114  \DeclareRobustCommand{\SUF@chaptersize}{\Large}
115  \DeclareRobustCommand{\SUF@sectionsize}{\large}
116  \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
117  \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
118  \geometry{%
119    heightrounded,
120    a4paper,
121    includeheadfoot=true,
122    textwidth=    136mm,
123    textheight=   220mm,
124    marginratio=  2:3,
125    marginparwidth= 30mm,
126    marginparsep= 12pt}
127 \or
128 \suftesi@periodicaltrue
129  \DeclareRobustCommand{\SUF@chaptersize}{\large}
130  \DeclareRobustCommand{\SUF@sectionsize}{\normalsize}
131  \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
132  \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
133  \geometry{
134    heightrounded,
135    includeheadfoot=false,
136    textheight=   165mm,
137    textwidth=    110mm,
138    paperwidth=   170mm,
139    paperheight=  240mm,
140    marginratio=  2:3,
141    marginparwidth= 26mm,
142    marginparsep= 10pt}
```

```

143 \or
144 \suftesi@compacttrue
145 \DeclareRobustCommand{\SUF@chaptersize}{\large}
146 \DeclareRobustCommand{\SUF@sectionsize}{\normalsize}
147 \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
148 \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
149 \geometry{
150   heightrounded,
151   includeheadfoot=false,
152   textheight= 165mm,
153   textwidth= 110mm,
154   paperwidth= 160mm,
155   paperheight= 240mm,
156   marginratio= 2:3,
157   marginparwidth= 22mm,
158   marginparsep= 9pt}
159 \or
160 \suftesi@compactaureottrue
161 \DeclareRobustCommand{\SUF@chaptersize}{\large}
162 \DeclareRobustCommand{\SUF@sectionsize}{\normalsize}
163 \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
164 \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
165 \geometry{
166   heightrounded,
167   includeheadfoot=false,
168   textheight= 191mm,
169   textwidth= 118mm,
170   paperwidth= 160mm,
171   paperheight= 240mm,
172   marginratio= 2:3,
173   marginparwidth= 19mm,
174   marginparsep= 9pt}
175 \or
176 \suftesi@supercompacttrue
177 \DeclareRobustCommand{\SUF@chaptersize}{\large}
178 \DeclareRobustCommand{\SUF@sectionsize}{\normalsize}
179 \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
180 \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
181 \geometry{
182   heightrounded,
183   includeheadfoot=false,
184   textheight= 150mm,
185   textwidth= 100mm,
186   paperwidth= 140mm,
187   paperheight= 210mm,
188   marginratio= 2:3,
189   marginparwidth= 18mm,
190   marginparsep= 8pt}
191 \or
192 \suftesi@supercompactaureottrue

```

```

193 \DeclareRobustCommand{\SUF@chaptersize}{\large}
194 \DeclareRobustCommand{\SUF@sectionsize}{\normalsize}
195 \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
196 \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
197 \geometry{
198   heightrounded,
199   includeheadfoot=false,
200   textheight= 175mm,
201   textwidth= 108mm,
202   paperwidth= 140mm,
203   paperheight= 210mm,
204   marginratio= 1:1,
205   marginparwidth= 11mm,
206   marginparsep= 7pt}
207 \or
208 \suftesi@periodicalaureottrue
209 \DeclareRobustCommand{\SUF@chaptersize}{\large}
210 \DeclareRobustCommand{\SUF@sectionsize}{\normalsize}
211 \DeclareRobustCommand{\SUF@subsectionsize}{\normalsize}
212 \DeclareRobustCommand{\SUF@subsubsectionsize}{\normalsize}
213 \geometry{%
214   heightrounded,
215   includeheadfoot=true,
216   textwidth= 120mm,
217   textheight= 194mm,
218   paperwidth= 17cm,
219   paperheight= 24cm,
220   marginratio= 2:3,
221   marginparwidth= 62pt,
222   marginparsep= 10pt}
223 \or
224 \fi}

Sections style

225 \define@choicekey{}{partstyle}[\val\nr]{%
226   left,center,right,parleft,parcenter,parright}[left]{%
227 \ifcase\nr\relax
228   \def\SUF@lr@PARTSwitch{\filright}
229   \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
230 \or
231   \def\SUF@lr@PARTSwitch{\filcenter}
232   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
233 \or
234   \def\SUF@lr@PARTSwitch{\filleft}
235   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
236 \or%numpar
237   \def\SUF@lr@PARTSwitch{\filright}
238   \suftesi@numparparttrue
239   \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
240 \or

```

```

241 \def\SUF@lr@PARTSwitch{\filcenter}
242 \suftesi@numparparttrue
243 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
244 \or
245 \def\SUF@lr@PARTSwitch{\filleft}
246 \suftesi@numparparttrue
247 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
248 \fi}
249 \define@choicekey{}{chapstyle}[\val\nr]{%
250 left,center,right,parleft,parcenter,parright}[left]{%
251 \ifcase\nr\relax
252 \def\SUF@lr@CHAPSwitch{\filright}
253 \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
254 \or
255 \def\SUF@lr@CHAPSwitch{\filcenter}
256 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
257 \or
258 \def\SUF@lr@CHAPSwitch{\filleft}
259 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
260 \or%numparchap
261 \def\SUF@lr@CHAPSwitch{\filright}
262 \suftesi@numparchaptrue
263 \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
264 \or
265 \def\SUF@lr@CHAPSwitch{\filcenter}
266 \suftesi@numparchaptrue
267 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
268 \or
269 \def\SUF@lr@CHAPSwitch{\filleft}
270 \suftesi@numparchaptrue
271 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
272 \fi}
273 \define@choicekey{}{secstyle}[\val\nr]{%
274 left,center,right,parleft,parcenter,parright}[left]{%
275 \ifcase\nr\relax
276 \def\SUF@lr@SECSwitch{\filright}
277 \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
278 \or
279 \def\SUF@lr@SECSwitch{\filcenter}
280 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
281 \or
282 \def\SUF@lr@SECSwitch{\filleft}
283 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
284 \or%numparsec
285 \def\SUF@lr@SECSwitch{\filright}
286 \suftesi@numparsectrue
287 \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
288 \or
289 \def\SUF@lr@SECSwitch{\filcenter}
290 \suftesi@numparsectrue

```

```

291 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
292 \or
293 \def\SUF@lr@SECSwitch{\filleft}
294 \suftesi@numparsectrue
295 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
296 \fi}
297 \define@choicekey{}{subsecstyle}[\val\nr]{left,center,right}[left]{%
298 \ifcase\nr\relax
299 \def\SUF@lr@SUBSECSwitch{\filright}
300 \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
301 \or
302 \def\SUF@lr@SUBSECSwitch{\filcenter}
303 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
304 \or
305 \def\SUF@lr@SUBSECSwitch{\filleft}
306 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
307 \fi}
308 \define@choicekey{}{subsubsecstyle}[\val\nr]{left,center,right}[left]{%
309 \ifcase\nr\relax
310 \def\SUF@lr@SUBSUBSECSwitch{\filright}
311 \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
312 \or
313 \def\SUF@lr@SUBSUBSECSwitch{\filcenter}
314 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
315 \or
316 \def\SUF@lr@SUBSUBSECSwitch{\filleft}
317 \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
318 \fi}

```

Sections font

```

319 \define@choicekey{}{partfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
320 \ifcase\nr\relax
321 \def\SUF@PART@StyleSwitch{\relax}
322 \or
323 \def\SUF@PART@StyleSwitch{\itshape}
324 \or
325 \def\SUF@PART@StyleSwitch{\expandafter\SUF@titlesmallcaps}
326 \fi}
327 \define@choicekey{}{chapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
328 \ifcase\nr\relax
329 \def\SUF@CHAP@StyleSwitch{\relax}
330 \or
331 \def\SUF@CHAP@StyleSwitch{\itshape}
332 \or
333 \def\SUF@CHAP@StyleSwitch{\expandafter\SUF@titlesmallcaps}
334 \fi}
335 \define@choicekey{}{secfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
336 \ifcase\nr\relax
337 \def\SUF@SEC@StyleSwitch{\relax}
338 \or

```

```

339 \def\SUF@SEC@StyleSwitch{\itshape}
340 \or
341 \def\SUF@SEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
342 \fi}
343 \define@choicelkey{}{subsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
344 \ifcase\nr\relax
345 \def\SUF@SUBSEC@StyleSwitch{\relax}
346 \or
347 \def\SUF@SUBSEC@StyleSwitch{\itshape}
348 \or
349 \def\SUF@SUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
350 \fi}
351 \define@choicelkey{}{subsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
352 \ifcase\nr\relax
353 \def\SUF@SUBSUBSEC@StyleSwitch{\relax}
354 \or
355 \def\SUF@SUBSUBSEC@StyleSwitch{\itshape}
356 \or
357 \def\SUF@SUBSUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
358 \fi}
359 %

```

TOC font

```

360 \define@choicelkey{}{tocchapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
361 \ifcase\nr\relax
362 \def\SUF@tocCHAP@font{\relax}
363 \or
364 \def\SUF@tocCHAP@font{\itshape}
365 \or
366 \def\SUF@tocCHAP@font{\expandafter\SUF@TOCtitlesmallcaps}
367 \fi}
368 \define@choicelkey{}{tocsecfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
369 \ifcase\nr\relax
370 \def\SUF@tocSEC@font{\relax}
371 \or
372 \def\SUF@tocSEC@font{\itshape}
373 \or
374 \def\SUF@tocSEC@font{\expandafter\SUF@TOCtitlesmallcaps}
375 \fi}
376 \define@choicelkey{}{tocsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
377 \ifcase\nr\relax
378 \def\SUF@tocSUBSEC@font{\relax}
379 \or
380 \def\SUF@tocSUBSEC@font{\itshape}
381 \or
382 \def\SUF@tocSUBSEC@font{\expandafter\SUF@TOCtitlesmallcaps}
383 \fi}
384 \define@choicelkey{}{tocsubsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
385 \ifcase\nr\relax
386 \def\SUF@tocSUBSUBSEC@font{\relax}

```

```

387 \or
388 \def\SUF@tocSUBSUBSEC@font{\itshape}
389 \or
390 \def\SUF@tocSUBSUBSEC@font{\expandafter\SUF@TOCtitlesmallcaps}
391 \fi}
392 \define@choicekey{}{tocauthorfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
393 \ifcase\nr\relax
394 \def\SUF@tocAUT@font{\relax}
395 \or
396 \def\SUF@tocAUT@font{\itshape}
397 \or
398 \def\SUF@tocAUT@font{\expandafter\SUF@TOCtitlesmallcaps}
399 \fi}
400 \define@choicekey{}{toctitlefont}[\val\nr]{roman,italic,smallcaps}[italic]{%
401 \ifcase\nr\relax
402 \def\SUF@tocTIT@font{\relax}
403 \or
404 \def\SUF@tocTIT@font{\itshape}
405 \or
406 \def\SUF@tocTIT@font{\expandafter\SUF@TOCtitlesmallcaps}
407 \fi}

```

Sections number style

Part number style

```

408 \define@choicekey{}{partnumstyle}[\val\nr]
409     {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
410 \ifcase\nr\relax
411   \def\SUF@thepart{\arabic{part}}
412   \def\SUF@dotpart{}
413   \def\SUF@toclabelnum{}
414 \or
415   \def\SUF@thepart{\textsc{\roman{part}}}
416   \def\SUF@dotpart{}
417   \def\SUF@toclabelnum{\scshape\@roman}
418 \or
419   \def\SUF@thepart{\Roman{part}}
420   \def\SUF@dotpart{}
421   \def\SUF@toclabelnum{\@Roman}
422 \or
423   \def\SUF@thepart{\arabic{part}}
424   \def\SUF@dotpart{.}
425   \def\SUF@toclabelnum{}
426 \or
427   \def\SUF@thepart{\textsc{\roman{part}}}
428   \def\SUF@dotpart{.}
429   \def\SUF@toclabelnum{\scshape\@roman}
430 \or
431   \def\SUF@thepart{\Roman{part}}
432   \def\SUF@dotpart{.}

```

```

433 \def\SUF@toclabelnum{\@Roman}
434 \fi}

```

Chapter number style

```

435 \define@choicekey{ }{chapnumstyle}[\val\nr]{arabic,roman,Roman,
436 dotarabic,dotroman,dotRoman}[arabic]{%
437 \ifcase\nr\relax
438 \def\SUF@thechapter{\arabic{chapter}}
439 \def\SUF@HEAD@thechapter{\arabic{chapter}}
440 \def\SUF@dotchap{.}
441 \def\SUF@toclabelnum{ }
442 \or
443 \def\SUF@thechapter{\textsc{\roman{chapter}}}
444 \def\SUF@HEAD@thechapter{\textsc{\roman{chapter}}}
445 \def\SUF@dotchap{.}
446 \def\SUF@toclabelnum{\scshape\@roman}
447 \or
448 \def\SUF@thechapter{\Roman{chapter}}
449 \def\SUF@HEAD@thechapter{\Roman{chapter}}
450 \def\SUF@dotchap{.}
451 \def\SUF@toclabelnum{\@Roman}
452 \or
453 \def\SUF@thechapter{\arabic{chapter}}
454 \def\SUF@HEAD@thechapter{\arabic{chapter}}
455 \def\SUF@dotchap{.}
456 \def\SUF@toclabelnum{ }
457 \or
458 \def\SUF@thechapter{\textsc{\roman{chapter}}}
459 \def\SUF@HEAD@thechapter{\textsc{\roman{chapter}}}
460 \def\SUF@dotchap{.}
461 \def\SUF@toclabelnum{\scshape\@roman}
462 \or
463 \def\SUF@thechapter{\Roman{chapter}}
464 \def\SUF@HEAD@thechapter{\Roman{chapter}}
465 \def\SUF@dotchap{.}
466 \def\SUF@toclabelnum{\@Roman}
467 \fi}

```

Section number style

```

468 \define@choicekey{ }{secnumstyle}[\val\nr]
469 {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
470 \ifcase\nr\relax
471 \def\SUF@thesection{\arabic{section}}
472 \def\SUF@HEAD@thesection{\arabic{section}}
473 \def\SUF@dotsec{.}
474 \def\SUF@toclabelnum{ }
475 \or
476 \def\SUF@thesection{\textsc{\roman{section}}}
477 \def\SUF@HEAD@thesection{\textsc{\roman{section}}}
478 \def\SUF@dotsec{.}

```

```

479 \def\SUF@toclabelnum{\scshape\@roman}
480 \or
481 \def\SUF@thesection{\Roman{section}}
482 \def\SUF@HEAD@thesection{\Roman{section}}
483 \def\SUF@dotsec{}
484 \def\SUF@toclabelnum{\@Roman}
485 \or
486 \def\SUF@thesection{\arabic{section}}
487 \def\SUF@HEAD@thesection{\arabic{section}}
488 \def\SUF@dotsec{.}
489 \def\SUF@toclabelnum{}
490 \or
491 \def\SUF@thesection{\textsc{\roman{section}}}
492 \def\SUF@HEAD@thesection{\textsc{\roman{section}}}
493 \def\SUF@dotsec{.}
494 \def\SUF@toclabelnum{\scshape\@roman}
495 \or
496 \def\SUF@thesection{\Roman{section}}
497 \def\SUF@HEAD@thesection{\Roman{section}}
498 \def\SUF@dotsec{.}
499 \def\SUF@toclabelnum{\@Roman}
500 \fi}

```

Subsection number style

```

501 \define@choicekey{}{subsecnumstyle}[\val\nr]
502 {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
503 \ifcase\nr\relax
504 \def\SUF@thesubsection{\arabic{subsection}}
505 \def\SUF@dotsubsec{}
506 \def\SUF@toclabelnum{}
507 \or
508 \def\SUF@thesubsection{\textsc{\roman{subsection}}}
509 \def\SUF@dotsubsec{}
510 \def\SUF@toclabelnum{\scshape\@roman}
511 \or
512 \def\SUF@thesubsection{\Roman{subsection}}
513 \def\SUF@dotsubsec{}
514 \def\SUF@toclabelnum{\@Roman}
515 \or
516 \def\SUF@thesubsection{\arabic{subsection}}
517 \def\SUF@dotsubsec{.}
518 \def\SUF@toclabelnum{}
519 \or
520 \def\SUF@thesubsection{\textsc{\roman{subsection}}}
521 \def\SUF@dotsubsec{.}
522 \def\SUF@toclabelnum{\scshape\@roman}
523 \or
524 \def\SUF@thesubsection{\Roman{subsection}}
525 \def\SUF@dotsubsec{.}
526 \def\SUF@toclabelnum{\@Roman}

```

```
527 \fi}
```

Sub-subsection number style

```
528 \define@choicekey{}{subsubsecnumstyle}[\val\nr]
529 {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
530 \ifcase\nr\relax
531 \def\SUF@thesubsubsection{\arabic{subsubsection}}
532 \def\SUF@dotsubsubsec{}
533 \def\SUF@toclabelnum{}
534 \or
535 \def\SUF@thesubsubsection{\textsc{\roman{subsubsection}}}
536 \def\SUF@dotsubsubsec{}
537 \def\SUF@toclabelnum{\scshape\@roman}
538 \or
539 \def\SUF@thesubsubsection{\Roman{subsubsection}}
540 \def\SUF@dotsubsubsec{}
541 \def\SUF@toclabelnum{\@Roman}
542 \or
543 \def\SUF@thesubsubsection{\arabic{subsubsection}}
544 \def\SUF@dotsubsubsec{.}
545 \def\SUF@toclabelnum{}
546 \or
547 \def\SUF@thesubsubsection{\textsc{\roman{subsubsection}}}
548 \def\SUF@dotsubsubsec{.}
549 \def\SUF@toclabelnum{\scshape\@roman}
550 \or
551 \def\SUF@thesubsubsection{\Roman{subsubsection}}
552 \def\SUF@dotsubsubsec{.}
553 \def\SUF@toclabelnum{\@Roman}
554 \fi}
```

This option controls the style of small capitals used in the title of chapters and sections using `<level>font=smallcaps` option:

```
555 \define@choicekey{}{smallcapsstyle}[\val\nr]
556   {low,upper}[low]{%
557 \ifcase\nr\relax
558   \def\suftesi@MakeTextLowercase{\MakeLowercase}
559   \def\suftesi@MakeTextTOCLowercase{\lowercase}
560 \or
561   \def\suftesi@MakeTextLowercase{\relax}
562   \def\suftesi@MakeTextTOCLowercase{\relax}
563 \fi}
```

Fine adjustment of sections font

EXPERIMENTAL

```
564 \newcommand{\partfont}[1]{\def\SUF@PART@StyleSwitch{#1}}
565 \newcommand{\chapfont}[1]{\def\SUF@CHAP@StyleSwitch{#1}}
566 \newcommand{\secfont}[1]{\def\SUF@SEC@StyleSwitch{#1}}
567 \newcommand{\subsecfont}[1]{\def\SUF@SUBSEC@StyleSwitch{#1}}
568 \newcommand{\subsubsecfont}[1]{\def\SUF@SUBSUBSEC@StyleSwitch{#1}}
569 \newcommand{\chapnumfont}[1]{\def\SUF@thechapter{#1}}
```

```

570 \newcommand{\secnumfont}[1]{\def\SUF@thesection{#1}}
571 \newcommand{\subsecnumfont}[1]{\def\SUF@thesubsection{#1}}
572 \newcommand{\subsubsecnumfont}[1]{\def\SUF@thesubsubsection{#1}}

```

Headers

Header style

```

573 \define@choicekey{}{headerstyle}[\val\nr]
574     {inner,center,plain,authortitleinner,
575     authortitlecenter}[inner]{%
576 \ifcase\nr\relax
577   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
578   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}
579 \or
580   \suftesi@centerheadertrue
581   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
582   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}
583 \or
584   \suftesi@sufplaintrue
585 \or
586   \suftesi@authortitletrue
587   \def\SUF@rightmark{\let\thanks@gobble\SUF@Rheadstyle{\@headtitle}}
588   \def\SUF@leftmark{\let\thanks@gobble\SUF@Lheadstyle{\@author}}
589 \or
590   \suftesi@authortitletrue
591   \def\SUF@rightmark{\let\thanks@gobble\SUF@Rheadstyle{\@headtitle}}
592   \def\SUF@leftmark{\let\thanks@gobble\SUF@Lheadstyle{\@author}}
593   \suftesi@centerheadertrue
594 \fi}

```

Header font

```

595 \define@choicekey{}{headerfont}[\val\nr]
596     {roman,italic,smallcaps}[roman]{%
597 \ifcase\nr\relax
598   \def\SUF@Rheadstyle{}
599   \def\SUF@Lheadstyle{}
600   \def\SUF@thepage{\thepage}
601 \or
602   \def\SUF@Rheadstyle{\itshape}
603   \def\SUF@Lheadstyle{\itshape}
604   \def\SUF@thepage{\thepage}
605 \or
606   \def\SUF@Rheadstyle{\SUF@headingsmallcaps}
607   \def\SUF@Lheadstyle{\SUF@headingsmallcaps}
608   \def\SUF@thepage{\SUF@headingsmallcaps{\thepage}}
609 \fi}

```

Text elements

Lists

```

610 \RequirePackage[inline]{enumitem}
611 \renewcommand\labelitemi{\color{sufgray}\textbullet}
612 \setlist[itemsep=.5ex,parsep=0pt,listparindent=\parindent]
613 \setlist[description]{font=\normalfont\itshape}
614 \define@choicekey{}{liststyle}[\val\nr]
615     {bulged,aligned,indented}[bulged]{%
616 \ifcase\nr\relax
617     \setlist[enumerate,1]{leftmargin=0pt,label=\arabic*}
618     \setlist[enumerate,2]{leftmargin= 1.3\parindent,label=\alph*}
619     \setlist[enumerate,3]{leftmargin= 1.3\parindent,label=\roman*}
620     \setlist[itemize,1]{leftmargin=0pt}
621     \setlist[itemize,2]{leftmargin=1.3\parindent}
622     \setlist[itemize,3]{leftmargin=1.3\parindent}
623 \or
624     \setlist[enumerate,1]{leftmargin=1\parindent,label=\arabic*}
625     \setlist[enumerate,2]{leftmargin= 1.5\parindent,label=\alph*}
626     \setlist[enumerate,3]{leftmargin= 1.5\parindent,label=\roman*}
627     \setlist[itemize,1]{leftmargin=1\parindent}
628     \setlist[itemize,2]{leftmargin=1.5\parindent}
629     \setlist[itemize,3]{leftmargin=1.5\parindent}
630 \or
631     \setlist[enumerate,1]{leftmargin=2\parindent,label=\arabic*}
632     \setlist[enumerate,2]{leftmargin= 2.5\parindent,label=\alph*}
633     \setlist[enumerate,3]{leftmargin= 2.5\parindent,label=\roman*}
634     \setlist[itemize,1]{leftmargin=2\parindent}
635     \setlist[itemize,2]{leftmargin=2.5\parindent}
636     \setlist[itemize,3]{leftmargin=2.5\parindent}
637 \fi}

```

Quotations

```

638 \define@choicekey{}{quotestyle}[\val\nr]
639     {center,right}[center]{%
640 \ifcase\nr\relax
641 \def\SUF@quote@style{\rightmargin=\parindent}
642 \or
643 \def\SUF@quote@style{}
644 \fi}
645 \define@choicekey{}{quotesize}[\val\nr]
646     {footnotesize,small}[footnotesize]{%
647 \ifcase\nr\relax
648 \def\SUF@quotation@size{\footnotesize}
649 \or
650 \def\SUF@quotation@size{\small}
651 \fi}

```

Footnotes

```

652 \define@choicekey{}{footnotestyle}[\val\nr]
653     {bulged,hung,dotted,superscript}[bulged]{%
654 \ifcase\nr\relax
655     \renewcommand\@makefnrtxt{%

```

```

656     \hskip-2.5em\makebox[2em][r]{\@thefnmark}\hskip.5em}
657 \or
658   \renewcommand\@makefnrest{%
659     \leftskip=1em\hskip-1.5em%
660     \makebox[1em][r]{\@thefnmark}\hskip.5em}
661 \or
662   \renewcommand\@makefnrest{%
663     \@thefnmark.\hskip.5em}
664 \or
665   \renewcommand\@makefnrest{%
666     \textsuperscript{\@thefnmark}\hskip.3em}
667 \fi}
668 \define@choicekey{}{fewfootnotes}[\val\nr]
669   {true,false}[true]{%
670 \ifcase\nr\relax
671   \suf\@thefnmark\hskip.5em}
672 \or
673   \relax
674 \fi}

```

Captions

```

675 \RequirePackage{caption}
676 \define@choicekey{}{captionstyle}[\val\nr]
677   {standard,sanserif,italic,smallcaps}[standard]{%
678 \ifcase\nr\relax
679   \captionsetup{labelsep=period,font=small}
680 \or
681   \captionsetup{labelsep=period,font=small}
682   \captionsetup{font+=sf}
683 \or
684   \captionsetup{labelsep=period,font=small}
685   \captionsetup{font+=it}
686 \or
687   \captionsetup{labelsep=period,font=small,labelfont=sc}
688 \fi
689 }

```

Marginal notes

```

690 \define@choicekey{}{marginpar}[\val\nr]
691   {true,false}[true]{%
692 \ifcase\nr\relax
693 \or
694   \renewcommand\marginpar[2][l]{%
695 \fi}

```

Table of contents

```

696 \define@choicekey{}{tocstyle}[\val\nr]{%
697   standard,dotted,ragged,leftpage}[standard]{%
698 \ifcase\nr\relax
699   \def\SUF@titlerule{\titlerule*{}}

```

```

700 \def\SUF@chaptitlerule{\titlerule*{}}
701 \or
702 \suftesi@dottedtoctrue
703 \def\SUF@titlerule{\titlerule*{\footnotesize .\ }}
704 \def\SUF@chaptitlerule{\titlerule*{}}
705 \or
706 \suftesi@raggedtoctrue
707 \def\SUF@titlerule{\hspace{1em}}
708 \def\SUF@chaptitlerule{\hspace{1em}}
709 \or
710 \suftesi@pagelefttoctrue
711 \fi}
712 \define@choicekey{}{twocolcontents}[\val\nr]{%
713   toc,lof,lot,toclof,toclot,loflot,all}[all]{%
714 \ifcase\nr\relax
715   \suftesi@twocolumntoctrue
716   \setkeys{}{tocstyle=ragged}
717 \or
718   \suftesi@twocolumnloftrue
719   \setkeys{}{tocstyle=ragged}
720 \or
721   \suftesi@twocolumnlottrue
722   \setkeys{}{tocstyle=ragged}
723 \or
724   \suftesi@twocolumntoctrue
725   \suftesi@twocolumnloftrue
726   \setkeys{}{tocstyle=ragged}
727 \or
728   \suftesi@twocolumntoctrue
729   \suftesi@twocolumnlottrue
730   \setkeys{}{tocstyle=ragged}
731 \or
732   \suftesi@twocolumnloftrue
733   \suftesi@twocolumnlottrue
734   \setkeys{}{tocstyle=ragged}
735 \or
736   \suftesi@twocolumntoctrue
737   \suftesi@twocolumnloftrue
738   \suftesi@twocolumnlottrue
739   \setkeys{}{tocstyle=ragged}
740 \fi
741 }

```

Fonts

Roman fonts

```

742 \define@choicekey{}{defaultfont}[\val\nr]{%
743   none,cochineal,libertine,palatino,standard,compatibility}[cochineal]{%
744 \ifcase\nr\relax
745   \suftesi@nofonttrue

```

```

746 \or
747 \suftesi@cochinealtrue
748 \or
749 \suftesi@libertinettrue
750 \or
751 \suftesi@palatinottrue
752 \or
753 \suftesi@standardtrue
754 \or
755 \suftesi@compatibilitytrue
756 \fi}
757 \define@choicekey{}{mathfont}[\val\nr]{%
758     none,minimal,extended}[minimal]{%
759 \ifcase\nr\relax
760     \suftesi@mathminimalfalse
761     \suftesi@mathextendedfalse
762 \or
763     \suftesi@mathminimaltrue
764 \or
765     \suftesi@mathextendedtrue
766 \fi}

Greek fonts

767 \define@choicekey{}{greekfont}[\val\nr]{%
768     none,artemisia,porson,bodoni,cbgreek}[none]{%
769 \ifcase\nr\relax
770 \suftesi@greekfontfalse
771 \or
772 \suftesi@greekfonttrue\suftesi@artemisiatrue
773 \or
774 \suftesi@greekfonttrue\suftesi@porsontrue
775 \or
776 \suftesi@greekfonttrue\suftesi@bodonitrue
777 \or
778 \suftesi@greekfonttrue\suftesi@cbgreektrue
779 \fi}

Other options

Indentation

780 \define@choicekey{}{parindent}[\val\nr]
781     {compact,wide}[compact]{%
782 \ifcase\nr\relax
783 \setlength\parindent{1em}
784 \or
785 \setlength\parindent{1.5em}
786 \fi}

Part page

787 \define@choicekey{}{partpage}[\val\nr]{true,false}[true]{%

```

```

788 \ifcase\nr\relax
789   \suftesi@partpagetrue
790 \or
791   \relax
792 \fi}

```

Draftdate

```

793 \define@choicekey{}{draftdate}[\val\nr]
794   {true,false}[true]{%
795 \ifcase\nr\relax
796   \suftesi@draftdatetrue
797 \or
798 \fi}

```

View mode

```

799 \define@choicekey{}{version}[\val\nr]
800   {screen,cscreen,draft,final}[draft]{%
801 \ifcase\nr\relax
802   \suftesi@screentruetrue
803 \or
804   \suftesi@screentruetrue
805   \suftesi@screencenteredtrue
806 \or
807 \or
808   \AtBeginDocument{\crop[off]}
809 \fi}
810 \define@choicekey{}{crop}[\val\nr]
811   {true,false}[true]{%
812 \ClassWarningNoLine{suftesi}{%
813   'crop' option is deprecated.\MessageBreak
814   Use 'version' option instead}
815 \ifcase\nr\relax
816   \setkeys{}{version=draft}
817 \or
818   \setkeys{}{version=screen}
819 \fi}

```

Titlepage

```

820 \define@choicekey{}{titlepage}[\val\nr]
821   {true,false}[true]{%
822 \ifcase\nr\relax
823   \@titlepagetrue
824 \or
825   \@titlepagefalse
826 \fi}

```

Pre-defined styles

```

827 \define@choicekey{}{style}[\val\nr]
828   {roman1,roman2,roman3,roman4,roman5,roman6,
829   italic1,italic2,italic3,italic4,italic5,italic6,

```

```

830 italic7,italic8,italic9,italic10,italic11,italic12,
831 smallcaps1,smallcaps2,smallcaps3,smallcaps4,smallcaps5,smallcaps6,
832 smallcaps7,smallcaps8,smallcaps9,smallcaps10,smallcaps11,smallcaps12,
833 FSPLa,FSPLb,FSPLc}
834 [roman1]{%
835 \ifcase\nr\relax

```

The ‘roman’ styles

```

836 \setkeys{}{chapstyle=left}
837 \or
838 \setkeys{}{chapstyle=center}
839 \or
840 \setkeys{}{chapstyle=right}
841 \or
842 \setkeys{}{chapstyle=parleft}
843 \or
844 \setkeys{}{chapstyle=parcenter}
845 \or
846 \setkeys{}{chapstyle=parright}
847 \or

```

The ‘italic’ styles

```

848 \setkeys(){
849   chapstyle=left,
850   chapfont=italic,
851   tocchapfont=italic,
852   headerfont=italic}
853 \or
854 \setkeys(){
855   chapstyle=center,
856   chapfont=italic,
857   tocchapfont=italic,
858   headerfont=italic}
859 \or
860 \setkeys(){
861   chapstyle=right,
862   chapfont=italic,
863   tocchapfont=italic,
864   headerfont=italic}
865 \or
866 \setkeys(){
867   chapstyle=parleft,
868   chapfont=italic,
869   tocchapfont=italic,
870   headerfont=italic}
871 \or
872 \setkeys(){
873   chapstyle=parcenter,
874   chapfont=italic,
875   tocchapfont=italic,

```

```

876 headerfont=italic}
877 \or
878 \setkeys{}{
879 chapstyle=parright,
880 chapfont=italic,
881 tocchapfont=italic,
882 headerfont=italic}
883 \or
884 \setkeys{}{
885 chapstyle=left,
886 chapfont=italic,
887 tocchapfont=italic,
888 secfont=smallcaps,
889 headerfont=italic}
890 \or
891 \setkeys{}{
892 chapstyle=center,
893 chapfont=italic,
894 tocchapfont=italic,
895 secfont=smallcaps,
896 headerfont=italic}
897 \or
898 \setkeys{}{
899 chapstyle=right,
900 chapfont=italic,
901 tocchapfont=italic,
902 secfont=smallcaps,
903 headerfont=italic}
904 \or
905 \setkeys{}{
906 chapstyle=parleft,
907 chapfont=italic,
908 tocchapfont=italic,
909 secfont=smallcaps,
910 headerfont=italic}
911 \or
912 \setkeys{}{
913 chapstyle=parcenter,
914 chapfont=italic,
915 tocchapfont=italic,
916 secfont=smallcaps,
917 headerfont=italic}
918 \or
919 \setkeys{}{
920 chapstyle=parright,
921 chapfont=italic,
922 tocchapfont=italic,
923 secfont=smallcaps,
924 headerfont=italic}
925 \or

```

The smallcaps' styles

```
926 \setkeys{}{
927 chapstyle=left,
928 chapfont=smallcaps,
929 tocchapfont=smallcaps,
930 headerfont=smallcaps}
931 \or
932 \setkeys{}{
933 chapstyle=center,
934 chapfont=smallcaps,
935 tocchapfont=smallcaps,
936 headerfont=smallcaps}
937 \or
938 \setkeys{}{
939 chapstyle=right,
940 chapfont=smallcaps,
941 tocchapfont=smallcaps,
942 headerfont=smallcaps}
943 \or
944 \setkeys{}{
945 chapstyle=parleft,
946 chapfont=smallcaps,
947 tocchapfont=smallcaps,
948 headerfont=smallcaps}
949 \or
950 \setkeys{}{
951 chapstyle=parcenter,
952 chapfont=smallcaps,
953 tocchapfont=smallcaps,
954 headerfont=smallcaps}
955 \or
956 \setkeys{}{
957 chapstyle=parright,
958 chapfont=smallcaps,
959 tocchapfont=smallcaps,
960 headerfont=smallcaps}
961 \or
962 \setkeys{}{
963 chapstyle=left,
964 chapfont=smallcaps,
965 tocchapfont=smallcaps,
966 secfont=smallcaps,
967 headerfont=smallcaps}
968 \or
969 \setkeys{}{
970 chapstyle=center,
971 chapfont=smallcaps,
972 tocchapfont=smallcaps,
973 secfont=smallcaps,
```

```

974 headerfont=smallcaps}
975 \or
976 \setkeys{}{
977 chapstyle=right,
978 chapfont=smallcaps,
979 tocchapfont=smallcaps,
980 secfont=smallcaps,
981 headerfont=smallcaps}
982 \or
983 \setkeys{}{
984 chapstyle=parleft,
985 chapfont=smallcaps,
986 tocchapfont=smallcaps,
987 secfont=smallcaps,
988 headerfont=smallcaps}
989 \or
990 \setkeys{}{
991 chapstyle=parcenter,
992 chapfont=smallcaps,
993 tocchapfont=smallcaps,
994 secfont=smallcaps,
995 headerfont=smallcaps}
996 \or
997 \setkeys{}{
998 chapstyle=parright,
999 chapfont=smallcaps,
1000 tocchapfont=smallcaps,
1001 secfont=smallcaps,
1002 headerfont=smallcaps}
1003 \or

```

The FSPL styles

```

1004 \suftesi@periodicalaureotru
1005 \suftesi@FSPLtrue
1006 \setkeys{}{%
1007 pagelayout=periodicalaureo,
1008 style=roman5,
1009 chapnumstyle=roman,
1010 headerstyle=inner,
1011 footnotestyle=hung,
1012 liststyle=indented,
1013 tocstyle=leftpage}
1014 \disable@keys{}
1015 {structure,documentstructure,pagelayout,partfont,chapfont,secfont,%
1016 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
1017 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
1018 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
1019 quotesize,footnotestyle,liststyle,captionstyle,parindent}
1020 \or
1021 \suftesi@periodicalaureotru

```

```

1022 \suftesi@FSPLtrue
1023 \setkeys{}{%
1024   pagelayout=periodicalaureo,
1025   style=italic5,
1026   chapnumstyle=roman,
1027   headerstyle=inner,
1028   headerfont=italic,
1029   footnotestyle=hung,
1030   liststyle=indented,
1031   tocstyle=leftpage}
1032 \disable@keys{}
1033 {structure,documentstructure,pagelayout,partfont,chapfont,secfont,%
1034 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
1035 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
1036 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
1037 quotesize,footnotestyle,liststyle,captionstyle,parindent}
1038 \or
1039 \suftesi@periodicalaureottrue
1040 \suftesi@FSPLtrue
1041 \setkeys{}{%
1042   pagelayout=periodicalaureo,
1043   style=smallcaps5,
1044   chapnumstyle=roman,
1045   headerstyle=inner,
1046   headerfont=smallcaps,
1047   secfont=smallcaps,
1048   footnotestyle=hung,
1049   liststyle=indented,
1050   tocstyle=leftpage}
1051 \disable@keys{}
1052 {structure,documentstructure,pagelayout,partfont,chapfont,secfont,%
1053 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
1054 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
1055 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
1056 quotesize,footnotestyle,liststyle,captionstyle,parindent}
1057 \fi}

```

Options for collection document structure

```

1058 \define@choicekey{}{papertitlestyle}[\val\nr]{%
1059   left,center,right}[left]{%
1060 \ifcase\nr\relax
1061 \def\SUF@lr@coll@titleSwitch{\filright}
1062 \or
1063 \def\SUF@lr@coll@titleSwitch{\filcenter}
1064 \or
1065 \def\SUF@lr@coll@titleSwitch{\filleft}
1066 \fi}
1067 \define@choicekey{}{revauthortitle}[\val\nr]
1068   {true,false}[false]{%

```

```

1069 \ifcase\nr\relax
1070 \suftesi@reverseauthortitletrue
1071 \or\relax
1072 \fi}
1073 \define@choicekey{}{titlefont}[\val\nr]{roman,italic,smallcaps}[roman]{%
1074 \ifcase\nr\relax
1075 \def\SUF@titlefont@Switch{\relax}
1076 \or
1077 \def\SUF@titlefont@Switch{\itshape}
1078 \or
1079 \def\SUF@titlefont@Switch{\expandafter\SUF@titlesmallcaps}
1080 \fi}
1081
1082 \define@choicekey{}{authorfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
1083 \ifcase\nr\relax
1084 \def\SUF@authorfont@Switch{\relax}
1085 \or
1086 \def\SUF@authorfont@Switch{\itshape}
1087 \or
1088 \def\SUF@authorfont@Switch{\expandafter\SUF@titlesmallcaps}
1089 \fi}

```

Execute and process options

```

1090 \ExecuteOptionsX<>{
1091   captionstyle=standard,
1092   marginpar=true,
1093   parindent=compact,
1094   tocstyle=standard,
1095   defaultfont=cochineal,
1096   mathfont=minimal,
1097   greekfont=none,
1098   pagelayout=standard,
1099   headerstyle=inner,
1100   liststyle=bulged,
1101   footnotestyle=bulged,
1102   quotesize=footnotesize,
1103   quotestyle=center,
1104   partstyle=left,
1105   chapstyle=left,
1106   secstyle=left,
1107   subsecstyle=left,
1108   subsubsecstyle=left,
1109   partfont=roman,
1110   chapfont=roman,
1111   secfont=italic,
1112   subsecfont=roman,
1113   subsubsecfont=roman,
1114   headerfont=roman,
1115   partnumstyle=Roman,
1116   chapnumstyle=arabic,

```

```

1117 secnumstyle=arabic,
1118 subsecnumstyle=arabic,
1119 subsubsecnumstyle=arabic,
1120 smallcapsstyle=low,
1121 titlefont=italic,
1122 authorfont=roman,
1123 toctitlefont=italic,
1124 tocauthorfont=roman,
1125 revauthortitle=false,
1126 papertitlestyle=left,
1127 authorfont=roman,
1128 titlefont=italic,
1129 tocchapfont=roman,
1130 tocsecfont=roman,
1131 tocsubsecfont=roman,
1132 tocsubsubsecfont=roman}
1133 \ProcessOptionsX<>\relax

```

The use of the `\XKV@useoption` command, provided by the `xkeyval`, is a trick to delete the option given as its argument from the list stored in `\@unusedoptionlist` so that the option will not produce the “Unused global options” message:

```

1134 \XKV@useoption{a4paper} \XKV@useoption{10pt}
1135 \XKV@useoption{11pt} \XKV@useoption{12pt}
1136 \XKV@useoption{oneside} \XKV@useoption{twoside}
1137 \XKV@useoption{onecolumn} \XKV@useoption{twocolumn}
1138 \XKV@useoption{titlepage} \XKV@useoption{notitlepage}
1139 \XKV@useoption{openright} \XKV@useoption{openany}
1140 \XKV@useoption{leqno} \XKV@useoption{fleqn}
1141 \XKV@useoption{a5paper} \XKV@useoption{b5paper}
1142 \XKV@useoption{legalpaper} \XKV@useoption{executivepaper}
1143 \XKV@useoption{landscape}

```

A trick to delete the class options from `\XKV@classoptionslist`, in order to avoid incompatibility with packages using options defined by `suftesi` too. Thanks to Enrico Gregorio!

```

1144 \def\XKV@classoptionslist{}

```

Basic packages

```

1145 \RequirePackage{color}
1146 \definecolor{sufred}{rgb}{0.5,0,0}
1147 \definecolor{sufgray}{rgb}{0.5,0.5,0.5}
1148 \RequirePackage{multicol}
1149 \RequirePackage{emptypage}
1150 \RequirePackage{microtype}
1151 \RequirePackage{iftex}
1152 \ifLuaTeX
1153 \RequirePackage{luatex85}
1154 \else
1155 \fi

```

The FSPL style requires a verbose colophon which uses specific icons:

```

1156 \ifsuftesi@FSPL
1157 \RequirePackage{ccllicenses}
1158 \else

```

```
1159 \fi
```

Page layout

The `\geometry` command must be declared before the `fontenc` package. If declared after it, the `heightrounded` option becomes ineffective and many underfull vertical boxes may occur.

```
1160 \ifsuftesi@screen
1161   \newcommand*\crop[1] [] {}
1162   \ifsuftesi@screencentered
1163     \geometry{hmarginratio=1:1}
1164   \else
1165     \fi
1166 \else
1167   \RequirePackage[a4, cam, center]{crop}
1168 \fi
```

Fonts

With \XeTeX we do not load any fonts. Anyway the `fontspec` package is required because some commands of the class are based on it.

```
1169 \unless\ifPDFTeX%if xelatex or lualatex
1170 \AtBeginDocument{%
1171   \@ifpackageloaded{fontspec}
1172     {\relax}
1173     {\ClassError{suftesi}
1174       {*****\MessageBreak
1175        * For using suftesi with XeLaTeX\MessageBreak
1176        * load either 'fontspec' or 'mathspec'\MessageBreak
1177        * For using suftesi with LuaLaTeX\MessageBreak
1178        * load 'fontspec' \MessageBreak
1179        *****}
1180       {*****\MessageBreak
1181        * For using suftesi with XeLaTeX\MessageBreak
1182        * load either 'fontspec' or 'mathspec'\MessageBreak
1183        * For using suftesi with LuaLaTeX\MessageBreak
1184        * load 'fontspec' \MessageBreak
1185        *****}}
1186   }
1187 \else% if pdftex
1188 \RequirePackage[LGR, T1]{fontenc}
1189 \RequirePackage{substitutefont}
1190 \AtBeginDocument{\fontencoding{T1}\selectfont}
```

Now we load the macros for the `defaultfont` option. The greek fonts by the Greek Font Society are available only with `palatino`, `libertine` and `cochineal` options. A warning appears if the `cbgreek` option is unused.

```
1191 \ifsuftesi@nofont
1192   \ifsuftesi@greekfont
1193     \ClassWarningNoLine{suftesi}{%
1194       Unused 'greekfont' option}%
1195     \suftesi@greekfontfalse
1196   \else\suftesi@greekfontfalse\fi
```

```

1197 \else
1198 \ifsuftesi@standard
1199   \RequirePackage{lmodern}
1200   \ifsuftesi@greekfont
1201     \ClassWarningNoLine{suftesi}{%
1202       Unused 'greekfont' option}%
1203     \suftesi@greekfontfalse
1204     \else\suftesi@greekfontfalse\fi
1205 \else
  Previous versions of the class were based on Palatino (mathpazo), Iwona and Bera Mono. Now
  this combination is provided only for backward compatibility.
1206 \ifsuftesi@compatibility
1207   \RequirePackage[osf,sc]{mathpazo}
1208   \RequirePackage[scaled=0.8]{beramono}
1209   \renewcommand{\sfdefault}{iwona}
1210   \ifsuftesi@greekfont
1211   \ifsuftesi@bodoni
1212   \gdef\SUFfntscale{0.96}
1213   \else
1214   \ifsuftesi@artemisiasia
1215   \gdef\SUFfntscale{0.97}
1216   \else
1217   \ifsuftesi@porson
1218   \gdef\SUFfntscale{1.18}
1219   \else
1220   \ifsuftesi@cbgreek
1221   \def\lmfntscale{1.06}
1222   \else
1223   \fi
1224   \fi
1225   \fi
1226   \fi
1227   \else
1228   \ClassWarningNoLine{suftesi}{\MessageBreak
1229     If you need the Greek font remember\MessageBreak
1230     to set one of the following options:\MessageBreak
1231     greekfont=artemisiasia,\MessageBreak
1232     greekfont=porson,\MessageBreak
1233     greekfont=cbgreek}
1234   \fi
1235 \else
1236 \ifsuftesi@palatino
1237   \RequirePackage[full]{textcomp}
1238   \RequirePackage{newpxtext}
1239   \RequirePackage[scaled=1.06]{biolinum}
1240   \RequirePackage[varqu,varl]{inconsolata}
1241   \ifsuftesi@mathextended
1242   \RequirePackage{amsthm}
1243   \RequirePackage[bigdelims,vvarbb]{newpxmath}
1244   \RequirePackage[cal=boondoxo]{mathalfa}

```

```

1245         \else
1246         \ifsuftesi@mathminimal
1247         \RequirePackage[bigdelims,vvarbb]{newpxmath}
1248         \else
1249         \fi
1250         \fi
1251         \useosf
1252         \useproportional
1253         \ifsuftesi@greekfont
1254         \ifsuftesi@bodoni
1255         \gdef\SUFffntscale{0.96}
1256         \else
1257         \ifsuftesi@artemisia
1258         \gdef\SUFffntscale{0.97}
1259         \else
1260         \ifsuftesi@porson
1261         \gdef\SUFffntscale{1.18}
1262         \else
1263         \ifsuftesi@cbgreek
1264         \def\lmffntscale{1.06}
1265         \else
1266         \fi
1267         \fi
1268         \fi
1269         \fi
1270         \else
1271         \ClassWarningNoLine{suftesi}{\MessageBreak
1272         If you need the Greek font remember\MessageBreak
1273         to set one of the following options:\MessageBreak
1274         greekfont=artemisia,\MessageBreak
1275         greekfont=porson,\MessageBreak
1276         greekfont=cbgreek}
1277         \fi
1278     \else
1279     \ifsuftesi@libertine
1280     \RequirePackage{textcomp}
1281     \RequirePackage[sb]{libertine}
1282     \RequirePackage[varqu,varl,scaled=0.94]{inconsolata}
1283     \ifsuftesi@mathextended
1284     \RequirePackage{amsthm}
1285     \RequirePackage{libertinust1math}
1286     \RequirePackage[cal=stix,scr=boondoxo,bb=boondox]{mathalfa}
1287     \else
1288     \ifsuftesi@mathminimal
1289     \RequirePackage{libertinust1math}
1290     \else
1291     \fi
1292     \fi
1293     \useosf
1294     \ifsuftesi@bodoni

```

```

1295     \gdef\SUFffntscale{0.9}
1296     \else
1297     \ifsuftesi@artemisia
1298     \gdef\SUFffntscale{0.91}
1299     \else
1300     \ifsuftesi@porson
1301     \gdef\SUFffntscale{1.1}
1302     \else
1303     \fi
1304     \fi
1305     \fi
1306 \else
1307 \ifsuftesi@cochineal
1308   \RequirePackage{textcomp}
1309   \RequirePackage{cochineal}
1310   \RequirePackage[varqu,varl,var0]{inconsolata}
1311   \RequirePackage{biolinum}
1312   \ifsuftesi@mathextended
1313   \RequirePackage{amsthm}
1314   \RequirePackage[cochineal,bigdelims,cmintegrals,vvarbb]{newtxmath}
1315   \RequirePackage[cal=boondoxo]{mathalfa}
1316   \else
1317   \ifsuftesi@mathminimal
1318   \RequirePackage[cochineal,bigdelims,cmintegrals,vvarbb]{newtxmath}
1319   \else
1320   \fi
1321   \fi
1322   \useosf
1323   \useproportional
1324   \ifsuftesi@bodoni
1325   \gdef\SUFffntscale{0.9}
1326   \else
1327   \ifsuftesi@artemisia
1328   \gdef\SUFffntscale{0.905}
1329   \else
1330   \ifsuftesi@porson
1331   \gdef\SUFffntscale{1.1}
1332   \else
1333   \fi
1334   \fi
1335   \fi
1336 \else
1337 \fi
1338 \fi
1339 \fi
1340 \fi
1341 \fi
1342 \fi
1343 \fi

```

```

1344 \unless\ifPDFTeX\else
1345 \ifsuftesi@greekfont
1346   \ifsuftesi@artemisia
1347     \def\SUF@greekfamily{artemisia}
1348   \else
1349     \ifsuftesi@porson
1350       \def\SUF@greekfamily{porson}
1351     \else
1352       \ifsuftesi@bodoni
1353         \def\SUF@greekfamily{bodoni}
1354       \else
1355         \ifsuftesi@cbgreek
1356         \def\SUF@greekfamily{lmr}
1357       \else
1358         \fi
1359       \fi
1360     \fi
1361   \fi

```

Thanks to Claudio Beccari for the following macro.

```

1362 \AtBeginDocument{
1363   \substitutefont{LGR}{\rmdefault}{\SUF@greekfamily}
1364   \DeclareRobustCommand{\greektext}{%
1365     \usefont{LGR}{\SUF@greekfamily}{\f@series}{\f@shape}
1366     \def\encodingdefault{LGR}}
1367   \DeclareTextFontCommand{\textgreek}{\greektext}}
1368 \ifsuftesi@cbgreek
1369   \else

```

We redefine the font definitions of the GFS fonts in order to scale the fonts according to the roman default.

```

1370 \DeclareFontFamily{LGR}{bodoni}{}
1371 \DeclareFontShape{LGR}{bodoni}{m}{n}{<-> s * [\SUFffntscale] gbodonirg6a}{}
1372 \DeclareFontShape{LGR}{bodoni}{m}{it}{<-> s * [\SUFffntscale] gbodonii6a}{}
1373 \DeclareFontShape{LGR}{bodoni}{b}{n}{<-> s * [\SUFffntscale] gbodonib6a}{}
1374 \DeclareFontShape{LGR}{bodoni}{b}{it}{<-> s * [\SUFffntscale] gbodonibi6a}{}
1375 \DeclareFontShape{LGR}{bodoni}{m}{sl}{<-> s * [\SUFffntscale] gbodonio6a}{}
1376 \DeclareFontShape{LGR}{bodoni}{b}{sl}{<-> s * [\SUFffntscale] gbodonibo6a}{}
1377 \DeclareFontShape{LGR}{bodoni}{m}{sc}{<-> s * [\SUFffntscale] gbodonisc6a}{}
1378 \DeclareFontShape{LGR}{bodoni}{m}{sco}{<-> s * [\SUFffntscale] gbodonisco6a}{}
1379
1380 \DeclareFontShape{LGR}{bodoni}{bx}{n}{<-> s * [\SUFffntscale] gbodonib6a}{}
1381 \DeclareFontShape{LGR}{bodoni}{bx}{it}{<-> s * [\SUFffntscale] gbodonibi6a}{}
1382 \DeclareFontShape{LGR}{bodoni}{bx}{sl}{<-> s * [\SUFffntscale] gbodonibo6a}{}
1383
1384 \DeclareFontFamily{LGR}{artemisia}{}
1385 \DeclareFontShape{LGR}{artemisia}{m}{n}{<-> s * [\SUFffntscale] gartemisiarg6a}{}
1386 \DeclareFontShape{LGR}{artemisia}{m}{it}{<-> s * [\SUFffntscale] gartemisiai6a}{}
1387 \DeclareFontShape{LGR}{artemisia}{b}{n}{<-> s * [\SUFffntscale] gartemisiab6a}{}
1388 \DeclareFontShape{LGR}{artemisia}{b}{it}{<-> s * [\SUFffntscale] gartemisiabi6a}{}
1389 \DeclareFontShape{LGR}{artemisia}{m}{sl}{<-> s * [\SUFffntscale] gartemisiao6a}{}

```

```

1390 \DeclareFontShape{LGR}{artemisia}{b}{sl}{<-> s * [\SUFfontscale] gartemisiabo6a}{
1391 \DeclareFontShape{LGR}{artemisia}{m}{sc}{<-> s * [\SUFfontscale] gartemisiasc6a}{
1392 \DeclareFontShape{LGR}{artemisia}{m}{sco}{<-> s * [\SUFfontscale] gartemisiasco6a}{
1393
1394 \DeclareFontShape{LGR}{artemisia}{bx}{n}{<-> s * [\SUFfontscale] gartemisiab6a}{
1395 \DeclareFontShape{LGR}{artemisia}{bx}{it}{<-> s * [\SUFfontscale] gartemisiabi6a}{
1396 \DeclareFontShape{LGR}{artemisia}{bx}{sl}{<-> s * [\SUFfontscale] gartemisiabo6a}{
1397
1398 \DeclareFontFamily{LGR}{porson}{
1399 \DeclareFontShape{LGR}{porson}{m}{n}{<-> s * [\SUFfontscale] gporsonrg6a}{
1400 \DeclareFontShape{LGR}{porson}{m}{it}{<-> s * [\SUFfontscale] gporsonrg6a}{
1401 \DeclareFontShape{LGR}{porson}{b}{n}{<-> s * [\SUFfontscale] gporsonrg6a}{
1402 \DeclareFontShape{LGR}{porson}{b}{it}{<-> s * [\SUFfontscale] gporsonrg6a}{
1403 \DeclareFontShape{LGR}{porson}{m}{sl}{<-> s * [\SUFfontscale] gporsonrg6a}{
1404 \DeclareFontShape{LGR}{porson}{b}{sl}{<-> s * [\SUFfontscale] gporsonrg6a}{
1405 \DeclareFontShape{LGR}{porson}{m}{sc}{<-> s * [\SUFfontscale] gporsonrg6a}{
1406
1407 \DeclareFontShape{LGR}{porson}{bx}{n}{<-> s * [\SUFfontscale] gporsonrg6a}{
1408 \DeclareFontShape{LGR}{porson}{bx}{it}{<-> s * [\SUFfontscale] gporsonrg6a}{
1409 \DeclareFontShape{LGR}{porson}{bx}{sl}{<-> s * [\SUFfontscale] gporsonrg6a}{
1410 \fi
1411 \else
1412 \fi
1413 \fi

```

Section titles

```

1414 \RequirePackage{titlesec}
1415   \newlength{\sectionsep}
1416   \setlength{\sectionsep}{\dimexpr(\baselineskip) plus 1pt minus 1pt}
1417 \unless\ifPDFTeX% if xetex or luatex
1418   \DeclareRobustCommand{\SUF@TOCtitlesmallcaps}[1]{%
1419     \addfontfeature{LetterSpace=10}\scshape\suftesi@MakeTextTOCLowercase{#1}}
1420   \DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1421     \addfontfeature{LetterSpace=10}\scshape\suftesi@MakeTextLowercase{#1}}
1422   \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1423     \addfontfeature{LetterSpace=10}\scshape\suftesi@MakeTextLowercase{#1}}
1424 \else% if pdftex
1425   \DeclareRobustCommand{\SUF@TOCtitlesmallcaps}[1]{%
1426     \scshape\suftesi@MakeTextTOCLowercase{\textls*{#1}}}%
1427   \DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1428     \scshape\suftesi@MakeTextLowercase{\textls*{#1}}}%
1429   \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1430     \scshape\suftesi@MakeTextLowercase{\textls*{#1}}}%
1431 \fi

  Default styles:
1432 \newlength\SUF@ADJnumparchap
1433 \def\SUF@default@CHAPTER{
1434 \ifsuftesi@numparchap
1435   \titleformat{\chapter}[display]

```

```

1436     {\SUF@chaptersize\SUF@lr@CHAPSwitch}
1437     {\SUF@thechapter\SUF@dotchap}
1438     {2ex}
1439     {\SUF@CHAP@StyleSwitch}
1440 \else
1441 \titleformat{\chapter}[hang]
1442     {\SUF@chaptersize\SUF@lr@CHAPSwitch}
1443     {\SUF@thechapter\SUF@dotchap}
1444     {3em}
1445     {\SUF@CHAP@StyleSwitch}
1446 \fi
1447 \ifsuftesi@numparchap
1448 \setlength{\SUF@ADJnumparchap}{-2.5\baselineskip}
1449 \else
1450 \setlength{\SUF@ADJnumparchap}{0pt}
1451 \fi}
1452 \def\SUF@default@SECTIONS{
1453 \ifsuftesi@numparsec
1454 %\titleformat{\section}[display]
1455 %     {\SUF@sectionsize\SUF@lr@SECSwitch}
1456 %     {\ifsuftesi@article\SUF@thesection
1457 %       \else\thesection\fi\SUF@dotsec}
1458 %     {0ex}
1459 %     {\SUF@SEC@StyleSwitch}
1460 \titleformat{\section}[display]
1461 {\SUF@sectionsize\SUF@lr@SECSwitch}
1462 {\SUF@thesection\SUF@dotsec}
1463 {0ex}
1464 {\SUF@SEC@StyleSwitch}
1465 \titlespacing*{\section}{0em}{\sectionsep}{\sectionsep}[0em]
1466 \else
1467 %\titleformat{\section}[hang]
1468 %     {\SUF@sectionsize\SUF@lr@SECSwitch}
1469 %     {\ifsuftesi@article\SUF@thesection
1470 %       \else\thesection\fi\SUF@dotsec}
1471 %     {1em}
1472 %     {\SUF@SEC@StyleSwitch}
1473 \titleformat{\section}[hang]
1474 {\SUF@sectionsize\SUF@lr@SECSwitch}
1475 {\SUF@thesection\SUF@dotsec}
1476 {1em}
1477 {\SUF@SEC@StyleSwitch}
1478 \titlespacing*{\section}{0ex}{\sectionsep}{\sectionsep}[0ex]
1479 \fi

1480 \ifsuftesi@numparsubsec
1481 %\titleformat{\subsection}[display]
1482 %     {\SUF@subsectionsiz\SUF@lr@SUBSECSwitch}
1483 %     {\textnormal\thesubsection}
1484 %     {0ex}

```

```

1485 %   {\SUF@SUBSEC@StyleSwitch}
1486 \titleformat{\subsection}[display]
1487 {\SUF@subsectionsize\SUF@lr@SUBSECSwitch}
1488 {\textnormal\SUF@thesubsection\SUF@dotsubsec}
1489 {0ex}
1490 {\SUF@SUBSEC@StyleSwitch}
1491 \titlespacing*{\subsection}{0em}{\sectionsep}{\sectionsep}[0em]
1492 \else
1493 %\titleformat{\subsection}[hang]
1494 %   {\SUF@subsectionsize\SUF@lr@SUBSECSwitch}
1495 %   {\textnormal\thesubsection}
1496 %   {1em}
1497 %   {\SUF@SUBSEC@StyleSwitch}
1498 \titleformat{\subsection}[hang]
1499 {\SUF@subsectionsize\SUF@lr@SUBSECSwitch}
1500 {\textnormal\SUF@thesubsection\SUF@dotsubsec}
1501 {1em}
1502 {\SUF@SUBSEC@StyleSwitch}
1503 \titlespacing*{\subsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1504 \fi

1505 \ifsuftesi@numparsubsubsec
1506 %\titleformat{\subsubsection}[display]
1507 %   {\SUF@subsectionsize\SUF@lr@SUBSUBSECSwitch}
1508 %   {\textnormal\thesubsubsection}
1509 %   {0ex}
1510 %   {\SUF@SUBSUBSEC@StyleSwitch}
1511 \titleformat{\subsubsection}[display]
1512 {\SUF@subsectionsize\SUF@lr@SUBSUBSECSwitch}
1513 {\textnormal\SUF@thesubsubsection\SUF@dotsubsubsec}
1514 {0ex}
1515 {\SUF@SUBSUBSEC@StyleSwitch}
1516 \titlespacing*{\subsubsection}{0em}{\sectionsep}{\sectionsep}[0em]
1517 \else
1518 %\titleformat{\subsubsection}[hang]
1519 %   {\SUF@subsectionsize\SUF@lr@SUBSUBSECSwitch}
1520 %   {\textnormal\thesubsubsection}
1521 %   {1em}
1522 %   {\SUF@SUBSUBSEC@StyleSwitch}
1523 \titleformat{\subsubsection}[hang]
1524 {\SUF@subsectionsize\SUF@lr@SUBSUBSECSwitch}
1525 {\textnormal\SUF@thesubsubsection\SUF@dotsubsubsec}
1526 {1em}
1527 {\SUF@SUBSUBSEC@StyleSwitch}
1528 \titlespacing*{\subsubsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1529 \fi
1530 }
1531 \SUF@default@CHAPTER
1532 \SUF@default@SECTIONS
1533 \ifsuftesi@periodical

```

```

1534 \titlespacing*{\chapter}{0em}{0\SUF@ADJnumparchap}{18ex}
1535 \titlespacing*{name=\chapter,numberless}{0em}{0pt}{18ex}
1536 \else
1537 \ifsuftesi@periodicalaureo
1538 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1539 \titlespacing*{name=\chapter,numberless}{0em}{0pt}{18ex}
1540 \else
1541 \ifsuftesi@compact
1542 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1543 \titlespacing*{name=\chapter,numberless}{0em}{0pt}{18ex}
1544 \else
1545 \ifsuftesi@compactaureo
1546 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1547 \titlespacing*{name=\chapter,numberless}{0em}{0pt}{18ex}
1548 \else
1549 \ifsuftesi@supercompact
1550 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1551 \titlespacing*{name=\chapter,numberless}{0em}{0pt}{18ex}
1552 \else
1553 \ifsuftesi@supercompactaureo
1554 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1555 \titlespacing*{name=\chapter,numberless}{0em}{0pt}{18ex}
1556 \else%standard/standardaureo
1557 \titlespacing*{\chapter}{0em}{%
1558     \dimexpr(6ex+\SUF@ADJnumparchap)}{18ex}
1559 \titlespacing*{name=\chapter,numberless}{0em}{6ex}{18ex}
1560     \fi
1561     \fi
1562     \fi
1563     \fi
1564 \fi
1565 \fi

```

Redefinitions for ‘article’ mode

```

1566 \ifsuftesi@article
1567 \def\chapter#1{\ClassError{suftesi}
1568   {\noexpand\chapter level is undefined
1569     using ‘structure=article’}
1570   {\noexpand\chapter level is undefined
1571     using ‘structure=article’}}
1572 \setcounter{tocdepth}{3}
1573 \setcounter{secnumdepth}{3}
1574 \renewcommand\thesection{%
1575   \@arabic\c@section}
1576 \renewcommand\thesubsection{%
1577   \thesection.\@arabic\c@subsection}
1578 \renewcommand\thesubsubsection{%
1579   \thesubsection.\@arabic\c@subsubsection}
1580 \renewcommand\theparagraph{%
1581   \thesubsubsection.\@arabic\c@paragraph}

```

```

1582 \renewcommand\thesubparagraph{%
1583     \theparagraph.\@arabic\c@subparagraph}
    The partpage options allows you to print a standard part page in article mode.
1584 \ifsuftesi@partpage
1585     \relax
1586     \else
    In article mode the \part command is similar to a \section but with more vertical space before
    and after.
1587 \titleclass{\part}{straight}
1588 \titlespacing*{\part}{0ex}{2\sectionsep}{2\sectionsep}[0ex]
1589 \fi
1590 \ifsuftesi@numparpart
1591 \titleformat{\part}[display]
1592     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1593     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1594     {2ex}
1595     {\SUF@PART@StyleSwitch}
1596 \else
1597 \titleformat{\part}[hang]
1598     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1599     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1600     {1em}
1601     {\SUF@PART@StyleSwitch}
1602 \fi
1603 \else

The default ‘book’ mode
1604 \ifsuftesi@numparpart
1605 \titleformat{\part}[display]
1606     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1607     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1608     {2ex}
1609     {\SUF@PART@StyleSwitch}
1610 \else
1611 \titleformat{\part}[hang]
1612     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1613     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1614     {1em}
1615     {\SUF@PART@StyleSwitch}
1616 \fi
1617 \fi
1618
1619 \titleformat{\paragraph}[runin]
1620     {}
1621     {\theparagraph}
1622     {.5em}
1623     {\itshape}
1624     [{}.\hspace*{1em}]
1625 \titlespacing*{\paragraph}{\parindent}{.5\sectionsep}{.5\sectionsep}

```

```

1626 \titleformat{\subparagraph}[runin]
1627 {}
1628 {\thesubparagraph}
1629 {.5em}
1630 {}
1631 [{}\hspace*{1em}]
1632 \titlespacing*{\subparagraph}{\parindent}{.5\sectionsep}{.5\sectionsep}

```

The biblatex package uses the book class definitions of bibliography and list of shorthands, so we must redefine them according to the styles of `suftesi`, which does not use uppercase letters in the headings.

```

1633 \ifsuftesi@article
1634 \AtBeginDocument{%
1635 \@ifpackageloaded{biblatex}{%
1636   \defbibheading{bibliography}[\refname]{%
1637     \section*{#1}%
1638     \markboth{#1}{#1}}
1639   \defbibheading{shorthands}[\losname]{%
1640     \section*{#1}%
1641     \markboth{#1}{#1}}
1642   \defbibheading{bibintoc}[\refname]{%
1643     \section*{#1}%
1644     \addcontentsline{toc}{section}{#1}%
1645     \markboth{#1}{#1}}
1646   \defbibheading{losintoc}[\losname]{%
1647     \section*{#1}%
1648     \addcontentsline{toc}{section}{#1}%
1649     \markboth{#1}{#1}}
1650   \defbibheading{bibnumbered}[\refname]{%
1651     \section{#1}%
1652     \if@twoside\markright{#1}\fi}
1653   \defbibheading{losnumbered}[\losname]{%
1654     \section{#1}%
1655     \if@twoside\markright{#1}\fi}
1656   \defbibheading{subbibliography}[\refname]{%
1657     \subsection*{#1}}
1658   \defbibheading{subbibintoc}[\refname]{%
1659     \subsection*{#1}%
1660     \addcontentsline{toc}{subsection}{#1}}
1661   \defbibheading{subbibnumbered}[\refname]{%
1662     \subsection{#1}}%
1663     {\relax}%
1664 }%
1665 \else
1666 \AtBeginDocument{%
1667 \@ifpackageloaded{biblatex}{%
1668   \defbibheading{bibliography}[\bibname]{%
1669     \chapter*{#1}%
1670     \markboth{#1}{#1}}
1671   \defbibheading{shorthands}[\losname]{%
1672     \chapter*{#1}%

```

```

1673     \markboth{#1}{#1}}
1674 \defbibheading{bibintoc}[\bibname]{%
1675     \chapter*{#1}%
1676     \addcontentsline{toc}{chapter}{#1}%
1677     \markboth{#1}{#1}}
1678 \defbibheading{losintoc}[\losname]{%
1679     \chapter*{#1}%
1680     \addcontentsline{toc}{chapter}{#1}%
1681     \markboth{#1}{#1}}
1682 \defbibheading{bibnumbered}[\bibname]{%
1683     \chapter{#1}%
1684     \if@twoside\markright{#1}\fi}
1685 \defbibheading{losnumbered}[\losname]{%
1686     \chapter{#1}%
1687     \if@twoside\markright{#1}\fi}
1688 \defbibheading{subbibliography}[\refname]{%
1689     \section*{#1}%
1690     \if@twoside\markright{#1}\fi}
1691 \defbibheading{subbibintoc}[\refname]{%
1692     \section*{#1}%
1693     \addcontentsline{toc}{section}{#1}%
1694     \if@twoside\markright{#1}\fi}
1695 \defbibheading{subbibnumbered}[\refname]{%
1696     \section{#1}}
1697     {\relax}%
1698 }%
1699 \fi

```

Cover page

```

1700 \newcommand{\Ctitle}[1]{\def\Ctitle{#1}}
1701 \newcommand{\Csubtitle}[1]{\def\Csubtitle{#1}}
1702 \newcommand{\Cauthor}[1]{\def\Cauthor{#1}}
1703 \newcommand{\Ceditor}[1]{\def\Ceditor{#1}}
1704 \newcommand{\Cfoot}[1]{\def\Cfoot{#1}}
1705 \newcommand{\Cpagecolor}[1]{\def\Cpagecolor{#1}}
1706 \newcommand{\Ccirclecolor}[1]{\def\Ccirclecolor{#1}}
1707 \newcommand{\Ctextcolor}[1]{\def\Ctextcolor{#1}}
1708 \newcommand{\Cfootcolor}[1]{\def\Cfootcolor{#1}}
1709 \Cauthor{}
1710 \Ctitle{}
1711 \Csubtitle{}
1712 \Ceditor{}
1713 \Cfoot{}
1714 \Cpagecolor{gray!30}
1715 \Ctextcolor{white}
1716 \Cfootcolor{black}
1717 \AtBeginDocument{
1718 \ifpackageloaded{tikz}{%
1719 \newcommand\makecover[1][1]{%

```

```

1720 \begin{titlepage}
1721 \begin{tikzpicture}[overlay,remember picture]
1722   \draw[draw=none,fill=\Cpagecolor]
1723     (current page.north west) rectangle (current page.south east);
1724   \node[anchor=center,yshift=.22\paperwidth] at (current page.center) (c) {};
1725   \draw[draw=none,fill=gray,#1]
1726     (c) circle (.38\paperwidth) ;
1727   \node[anchor=center] at (c) (author) {%
1728 \parbox{.7\paperwidth}{%
1729   \centering
1730   \ifx\Cauthor\@empty
1731     \else
1732       {\scshape\color{\Ctextcolor}\Cauthor\\}
1733       \vspace*{\baselineskip}
1734     \fi
1735
1736     \ifx\Ctitle\@empty
1737     \else
1738     {\Huge\bfseries\color{\Ctextcolor}\Ctitle\\[1ex]}
1739     \fi
1740
1741     \ifx\Csubtitle\@empty
1742     \else
1743     {\smallskip\Large\color{\Ctextcolor}\Csubtitle\\}
1744     \fi
1745
1746     \ifx\Ceditor\@empty
1747     \else
1748     {\vspace*{2\baselineskip}\color{\Ctextcolor}\Ceditor\\}
1749     \fi}
1750 };
1751 \ifx\Cfoot\@empty\else
1752   \node[xshift=.5\paperwidth,yshift=1cm,
1753     align=center,text=\Cfootcolor,anchor=south]
1754   at (current page.south west) {\Cfoot};
1755 \fi
1756 \end{tikzpicture}
1757 \end{titlepage}
1758 }
1759 }
1760 {\def\makecover{\ClassError{suftesi}{\MessageBreak%
1761 *****\MessageBreak
1762 * To use the \noexpand\makecover command\MessageBreak
1763 * load the 'tikz' package.\MessageBreak
1764 *****}{\MessageBreak%
1765 *****\MessageBreak
1766 * To use the \noexpand\makecover command\MessageBreak
1767 * load the 'tikz' package.\MessageBreak
1768 *****}}}
1769 }

```

Title page

The new `\title` command has an optional argument which can be used in the headers.

```
1770 \def\isbn#1{\gdef\@isbn{#1}}
1771 \def\@issn{\@latex@warning@no@line{%
1772   No \noexpand\isbn given}}
1773 \def\doi#1{\gdef\@doi{#1}}
1774 \def\@doi{\@latex@warning@no@line{%
1775   No \noexpand\doi given}}
1776 \def\isbn#1{\gdef\@issn{#1}}
1777 \def\@issn{\@latex@warning@no@line{%
1778   No \noexpand\isbn given}}
1779
1780 \renewcommand*{\title}[2][\gdef\@headtitle{#1}\gdef\@title{#2}]
1781   \edef\title{\noexpand\@dblarg
1782   \expandafter\noexpand\csname\string\title\endcsname}
1783   \def\@headtitle{--missing title--%
1784     \protect\ClassWarningNoLine{suftesi}{%
1785       No \string\title\space given \MessageBreak%
1786       See the class documentation for explanation}}
1787   \def\@title{--missing title--%
1788     \protect\ClassWarningNoLine{suftesi}{%
1789       No \string\title\space given\MessageBreak%
1790       See the class documentation for explanation}}
1791   \def\@author{--missing author--%
1792     \protect\ClassWarningNoLine{suftesi}{%
1793       No \string\author\space given\MessageBreak%
1794       See the class documentation for explanation}}
```

For `titlepage` (default) option:

```
1795 \if@titlepage% titlepage
1796   \renewcommand\maketitle{\begin{titlepage}%
1797     \let\footnotesize\small
1798     \let\footnoterule\relax
1799     \let \footnote \thanks
1800     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1801     \null\vfil
1802     \vskip 60\p@
1803     \begin{center}%
1804       {\SUF@chaptersize\color{sufred}\sffamily%
1805       \ifsuftesi@smallcapschap%
1806         \SUF@titlesmallcaps{\@title}
1807       \else
1808         \ifsuftesi@article
1809           \ifsuftesi@smallcapssec
1810             \SUF@titlesmallcaps{\@title}
1811           \else
1812             \@title
1813           \fi
1814       \else
1815         \@title
```

```

1816     \fi
1817     \fi\par}%
1818     \vskip 3em%
1819     {\small\lineskip .75em%
1820     \begin{tabular}[t]{c}%
1821     \@author
1822     \end{tabular}\par}%
1823     \vskip 1.5em%
1824     {\small\@date\par}%
1825 \end{center}\par
1826 \@thanks
1827 \vfil\null
1828 \end{titlepage}%
1829 \setcounter{footnote}{0}%
1830 \global\let\thanks\relax
1831 \global\let\maketitle\relax
1832 \global\let\@thanks\@empty
1833 \global\let\@date\@empty
1834 \global\let\date\relax
1835 \global\let\and\relax}
    Reproduces the standard \maketitle style:
1836 \newcommand\standardtitle{\begin{titlepage}%
1837 \let\footnotesize\small
1838 \let\footnoterule\relax
1839 \let \footnote \thanks
1840 \null\vfil
1841 \vskip 60\p@
1842 \begin{center}%
1843 {\LARGE \@title \par}%
1844 \vskip 3em%
1845 {\large
1846 \lineskip .75em%
1847 \begin{tabular}[t]{c}%
1848 \@author
1849 \end{tabular}\par}%
1850 \vskip 1.5em%
1851 {\large \@date \par}%
1852 \end{center}\par
1853 \@thanks
1854 \vfil\null
1855 \end{titlepage}%
1856 \setcounter{footnote}{0}%
1857 \global\let\thanks\relax
1858 \global\let\maketitle\relax
1859 \global\let\@thanks\@empty
1860 \global\let\@date\@empty
1861 \global\let\date\relax
1862 \global\let\and\relax}
1863 \else

```

For notitlepage option:

```
1864 \renewcommand\maketitle{\par
1865   \begin{group}
1866     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1867     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1868     \long\def\@makefntext##1{\parindent 1em\noindent
1869       \hb@xt@1.8em{%
1870         \hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
1871     \if@twocolumn
1872       \ifnum \col@number=\@ne
1873         \@maketitle
1874       \else
1875         \twocolumn[\@maketitle]%
1876       \fi
1877     \else
1878       \newpage
1879       \global\@topnum\z@% Prevents figures from going at top of page.
1880       \@maketitle
1881     \fi
1882     \thispagestyle{plain}\@thanks
1883   \end{group}
1884   \setcounter{footnote}{0}%
1885   \global\let\thanks\relax
1886   \global\let\maketitle\relax
1887   \global\let\@maketitle\relax
1888   \global\let\@thanks\@empty
1889   \global\let\@date\@empty
1890   \global\let\date\relax
1891   \global\let\and\relax}
1892   \def\@maketitle{%
1893   \newpage
1894   \null
1895   \vskip 2em%
1896   \begin{center}%
1897   \let \footnote \thanks
1898     {\SUF@chaptersize\color{sufred}\sffamily%
1899     \ifsuftesi@smallcapschap%
1900       \SUF@titlesmallcaps{\@title}
1901     \else
1902       \ifsuftesi@article
1903         \ifsuftesi@smallcapssec
1904           \SUF@titlesmallcaps{\@title}
1905         \else
1906           \@title
1907         \fi
1908       \else
1909         \@title
1910       \fi
1911     \fi\par}%
```

```

1912     \vskip 1.5em%
1913     {\small\lineskip .5em%
1914     \begin{tabular}[t]{c}%
1915     \author\par
1916     \end{tabular}\par}%
1917     \vskip 1em%
1918     {\small\@date\par}%
1919 \end{center}%
1920 \par
1921 \vskip 1.5em}

Reproduces the standard \maketitle style:
1922 \newcommand\standardtitle{\par
1923 \begingroup
1924 \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1925 \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1926 \long\def\@makefntext##1{\parindent 1em\noindent
1927     \hb@xt@1.8em{%
1928         \hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
1929 \if@twocolumn
1930     \ifnum \col@number=\@one
1931         \@standardmaketitle
1932     \else
1933         \twocolumn[\@standardmaketitle]%
1934     \fi
1935 \else
1936     \newpage
1937     \global\@topnum\z@
1938     \@standardmaketitle
1939 \fi
1940 \thispagestyle{plain}\@thanks
1941 \endgroup
1942 \setcounter{footnote}{0}%
1943 \global\let\thanks\relax
1944 \global\let\maketitle\relax
1945 \global\let\@standardmaketitle\relax
1946 \global\let\@thanks\@empty
1947 \global\let\@date\@empty
1948 \global\let\date\relax
1949 \global\let\and\relax}
1950 \def\@standardmaketitle{%
1951 \newpage
1952 \null
1953 \vskip 2em%
1954 \begin{center}%
1955 \let \footnote \thanks
1956 {\LARGE \@title \par}%
1957 \vskip 1.5em%
1958 {\large
1959     \lineskip .5em%

```

```

1960     \begin{tabular}[t]{c}%
1961         \author
1962     \end{tabular}\par}%
1963     \vskip 1em%
1964     {\large \date}%
1965     \end{center}%
1966     \par
1967     \vskip 1.5em}
1968 \fi

```

The collection document structure

```

1969 \ifsuftesi@collection
1970 \newcounter{journalnumber}
1971 \newcounter{journalvolume}
1972 \newcounter{issue}
1973 \newcounter{title}
1974 \setcounter{title}{1}
1975 \newcounter{article}
1976 \setcounter{article}{0}
1977 \setcounter{journalnumber}{0}
1978 \setcounter{tocdepth}{0}
1979 \def\journalname#1{\gdef\@journalname{#1}}
1980 \def\@journalname{\@latex@warning@no@line{%
1981     No \noexpand\journalname given}}
1982 \def\journalvolume#1{\gdef\@journalvolume{#1}}
1983 \def\@journalvolume{\@latex@warning@no@line{%
1984     No \noexpand\journalvolume given}}
1985 \def\journalnumber#1{\gdef\@journalnumber{#1}}
1986 \def\@journalnumber{\@latex@warning@no@line{%
1987     No \noexpand\journalnumber given}}
1988 \def\issue#1{\gdef\@issue{#1}}
1989 \def\@issue{\@latex@warning@no@line{%
1990     No \noexpand\issue given}}
1991 \def\journalyear#1{\gdef\@journalyear{#1}}
1992 \def\@journalyear{\@latex@warning@no@line{%
1993     No \noexpand\journalyear given}}
1994 \def\journalwebsite#1{\gdef\@journalwebsite{\url{#1}}}
1995 \def\@journalwebsite{\@latex@warning@no@line{%
1996     No \noexpand\journalwebsite given}}
1997 \def\thanks#1{\footnotemark \protected@xdef\@thanks{%
1998     \@thanks\protect\footnotetext[\the\c@footnote]{#1}}}
1999 \def\fulljournal{\emph{\@journalname} \@journalnumber, %
2000     \@issue} \@journalyear}
2001 \def\issuename#1{\gdef\@issuename{#1}}
2002 \def\collectiontitle#1{\gdef\@collectiontitle{#1}}
2003 \def\@collectiontitle{\@latex@warning@no@line{%
2004     No \noexpand\collectiontitle given}}
2005 \def\collectioneditor#1{\gdef\@collectioneditor{#1}}
2006 \def\@collectioneditor{\@latex@warning@no@line{%

```

```

2007     No \noexpand\collectioneditor given}}
2008 \renewcommand*{\title}[2][{}]{%
2009   \gdef\@headtitle{#1}\gdef\@title{#2}\markright{#1}}
2010   \edef\title{\noexpand\@dblarg
2011   \expandafter\noexpand\csname\string\title\endcsname}
2012   \def\@headtitle{--missing title--%
2013     \protect\ClassWarningNoLine{suftesi}{%
2014       No \string\title\space given \MessageBreak%
2015       See the class documentation for explanation}}
2016   \def\@title{--missing title--%
2017     \protect\ClassWarningNoLine{suftesi}{%
2018       No \string\title\space given\MessageBreak%
2019       See the class documentation for explanation}}
2020   \def\@author{--missing author--%
2021     \protect\ClassWarningNoLine{suftesi}{%
2022       No \string\author\space given\MessageBreak%
2023       See the class documentation for explanation}}
2024
2025 \newcommand*\l@title[2]{%
2026   \ifnum \c@tocdepth >\m@ne
2027     \addpenalty{-\@highpenalty}%
2028     \vskip 1.0ex \@plus\p@
2029     \begingroup
2030     \parindent \z@ \rightskip \@pnumwidth
2031     \parfillskip -\@pnumwidth
2032     \advance\leftskip1em
2033     \hskip -\leftskip
2034     #1\nobreak%
2035     \ifsuftesi@dottedtoc\dotfill%
2036     \nobreak\hb@xt@\@pnumwidth{\hss #2}\par
2037     \else
2038       \ifsuftesi@raggedtoc%
2039         \nobreak\hskip1em #2 \hfill\null\par
2040         \else
2041           \ifsuftesi@pagelefttoc
2042             \ClassError{suftesi}
2043             {\MessageBreak
2044              You can not use tocstyle=leftpage\MessageBreak
2045              with structure=collection}
2046             {You can not use tocstyle=leftpage\MessageBreak
2047              with structure=collection}
2048           \else
2049             \nobreak\hfill #2\par
2050           \fi
2051         \fi
2052       \fi
2053     \penalty\@highpenalty
2054   \endgroup
2055 \fi}

```

```

2056 \renewcommand\maketitle{\par
2057   \begingroup
2058     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
2059     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
2060     \long\def\@makefntext##1{\parindent 1em\noindent
2061       \hb@xt@1.8em{%
2062         \hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
2063     \if@twocolumn
2064       \ifnum \col@number=\@ne
2065         \@maketitle
2066       \else
2067         \twocolumn[\@maketitle]%
2068       \fi
2069     \else
2070       \newpage
2071       \global\@topnum\z@ % Prevents figures from going at top of page.
2072       \@maketitle
2073     \fi
2074     \thispagestyle{plain}\@thanks%
2075   \endgroup
2076 % \setcounter{footnote}{0}%
2077 \setcounter{section}{0}%
2078 % \global\let\thanks\relax
2079 % \global\let\maketitle\relax
2080 % \global\let\@maketitle\relax
2081 % \global\let\@thanks\@empty
2082 % \global\let\@author\@empty
2083 % \global\let\@date\@empty
2084 % \global\let\@title\@empty
2085 % \global\let\title\relax
2086 % \global\let\author\relax
2087 % \global\let\date\relax
2088 \global\let\and\relax
2089 \let\thanks@gobble}
2090 \AtBeginDocument{\def\@maketitle{%
2091   \refstepcounter{article}
2092   \SUF@chaptersize
2093   \SUF@lrcoll@titleSwitch
2094   \let\footnote\thanks
2095   \parindent=0pt
2096   {\ifsuftesi@reverseauthortitle
2097     \SUF@titlefont@Switch{\@title}%
2098     \else\SUF@authorfont@Switch{\@author}\fi}%
2099   \label{begin:\thearticle}
2100   \xdef\@currentHref{title.\thearticle}%
2101   \Hy@raisedlink{%
2102     \hyper@anchorstart{\@currentHref}\hyper@anchorend}%
2103   \csname toc@entry@\endcsname
2104   \begingroup%
2105   \let\thanks@gobble

```

```

2106 \addcontentsline{toc}{title}{%
2107 {\SUF@tocAUT@font{\@author}}\texorpdfstring{\newline}{, }%
2108 {\SUF@tocTIT@font{\@headtitle}}}
2109 \endgroup%
2110 \par\nobreak\vspace{2ex}
2111 {\ifsuftesi@reverseauthortitle
2112 \SUF@authorfont@Switch{\@author}%
2113 \else
2114 \SUF@titlefont@Switch{\@title}%
2115 \fi\vskip1.5cm}}%
2116 }
2117 %\newenvironment{article}
2118 % {\begingroup
2119 % \global\let\@thanks\@empty
2120 % \setcounter{footnote}{0}
2121 % \refstepcounter{article}
2122 % \label{begin:\thearticle}
2123 %}
2124 % {\label{end:\thearticle}\endgroup
2125 % }
2126 \newenvironment{article}
2127 {\begingroup
2128 \setcounter{section}{0}
2129 \setcounter{footnote}{0}
2130 \setcounter{figure}{0}
2131 \setcounter{table}{0}}
2132 {\label{end:\thearticle}
2133 \cleardoublepage
2134 \global\let\@thanks\@empty
2135 \endgroup}

```

A command to typeset the frontispiece of the collection.

```

2136 \newcommand{\frontispiece}{%
2137 \thispagestyle{empty}%
2138 \begingroup
2139 \centering
2140 \vspace*{\stretch{1}}
2141
2142 {\SUF@chaptersize\@collectiontitle\par}
2143 \vskip5ex
2144
2145 \@collectioneditor
2146 \vspace*{\stretch{3}}
2147
2148 \endgroup
2149 \clearpage}

```

In the collection document structure the articles are treated as chapters but you would not need to print in the table of contents all the sections of every article. So first of all we include in the table of contents only the author and the title of each paper:

```

2150 \setcounter{tocdepth}{0}

```

Anyway the sections inside each paper are numbered as in standard articles:

```

2151 \renewcommand\thesection{%
2152     \@arabic\c@section}
2153 \renewcommand\thesubsection{%
2154     \thesection.\@arabic\c@subsection}
2155 \renewcommand\thesubsubsection{%
2156     \thesubsection.\@arabic\c@subsubsection}
2157 \renewcommand\theparagraph{%
2158     \thesubsubsection.\@arabic\c@paragraph}
2159 \renewcommand\thesubparagraph{%
2160     \theparagraph.\@arabic\c@subparagraph}
2161 \else
2162 \fi

```

Frontispiece

```

2163 \AtBeginDocument{%
2164 \@ifpackagewith{frontespizio}{sufitesi}{%
2165 \ifsufitesi@periodical
2166     \Margini {5.5cm}{7cm}{4.5cm}{0cm}
2167     \else
2168 \ifsufitesi@compact
2169     \Margini {4.5cm}{7cm}{4.5cm}{0cm}
2170     \else
2171 \ifsufitesi@supercompact
2172     \Margini {4.5cm}{10cm}{6cm}{1cm}
2173     \else
2174 \ifsufitesi@compactaureo
2175     \Margini {4.5cm}{7cm}{4.5cm}{0cm}
2176     \else
2177 \ifsufitesi@supercompactaureo
2178     \Margini {4.5cm}{10cm}{6cm}{1cm}
2179     \else
2180 \ifsufitesi@periodicalaureo
2181     \Margini {5.5cm}{7cm}{4.5cm}{0cm}
2182     \else
2183 \fi\fi\fi\fi\fi\fi}
2184 {\@ifpackageloaded{frontespizio}{%
2185 \ifsufitesi@periodical
2186     \Margini {1cm}{7cm}{5cm}{1cm}
2187     \Rientro{1cm}
2188     \else
2189 \ifsufitesi@compact
2190     \Margini {1cm}{7cm}{6cm}{1cm}
2191     \Rientro{1cm}
2192     \else
2193 \ifsufitesi@supercompact
2194     \Margini {1cm}{10cm}{8cm}{1cm}
2195     \Rientro{1cm}
2196     \else
2197 \ifsufitesi@compactaureo
2198     \Margini {1cm}{7cm}{6cm}{1cm}

```

```

2199 \Rientro{1cm}
2200 \else
2201 \ifsuftesi@supercompactaureo
2202 \Margini {1cm}{10cm}{8cm}{1cm}
2203 \Rientro{1cm}
2204 \else
2205 \ifsuftesi@periodicalaureo
2206 \Margini {1cm}{7cm}{5cm}{1cm}
2207 \Rientro{1cm}
2208 \else
2209 \fi\fi\fi\fi\fi\fi
2210 {\relax}}

2211 \renewenvironment{theindex}
2212     {\if@twocolumn
2213         \@restonecolfalse
2214         \else
2215             \@restonecoltrue
2216         \fi
2217         \ifsuftesi@article
2218         \twocolumn[\section*{\indexname}]%
2219         \else
2220         \twocolumn[\@makeschapterhead{\indexname}]%
2221         \fi
2222         \@mkboth{\indexname}{\indexname}%
2223         \thispagestyle{plain}%
2224         \raggedright%
2225         \parindent\z@
2226         \parskip\z@ \@plus .3\p@\relax
2227         \columnseprule \z@
2228         \columnsep 35\p@
2229         \let\item\@idxitem}
2230     {\if@restonecol\onecolumn\else\clearpage\fi}

```

Appendix

```

2231 \newcommand{\appendicesname}[1]{\def\SUF@appendices{#1}}
2232 \appendicesname{Appendici}
2233 \newcommand{\appendixpage}{\SUF@appendixpage}
2234 \def\SUF@appendixpage{%
2235     \@mainmattertrue
2236     \titlecontents{part}
2237         [0em]
2238         {\addvspace{3ex}}
2239         {}
2240         {}
2241         {}
2242         [\addvspace{1ex}]
2243 \let\contentspage\relax
2244 \cleardoublepage
2245 \thispagestyle{empty}

```

```

2246         \addcontentsline{toc}{part}{\SUF@appendices}
2247     \begingroup
2248         \centering
2249         \null\vfil
2250         {\LARGE\SUF@appendices\par}
2251         \vfil
2252     \endgroup
2253     \cleardoublepage
2254 \titlecontents{part}
2255     [0em]
2256     {\addvspace{3ex}\partname~}
2257     {\makebox[\SUF@label@part][1]{%
2258         \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}
2259     {}
2260     {}
2261     [\addvspace{1ex}]
2262 }
2263 \ifsuftesi@article
2264     \renewcommand\appendix{\par
2265         \setcounter{section}{0}%
2266         \setcounter{subsection}{0}%
2267         \gdef\SUF@thesection{\@Alph@c@section}}
2268 \else
2269     \renewcommand\appendix{\par
2270         \setcounter{chapter}{0}%
2271         \setcounter{section}{0}%
2272         \gdef\@chapapp{\appendixname}%
2273         \gdef\SUF@thechapter{\@Alph@c@chapter}}
2274 \fi

```

Headings

```

2275 \RequirePackage{fancyhdr}
2276 \newcommand{\versionstring}[1]{\def\version@string{#1}}
2277 \versionstring{Version of}
2278 \AtBeginDocument{%
2279     \pagestyle{fancy}
2280     \renewcommand{\headrulewidth}{0pt}
2281     \renewcommand{\footnoterule}{}
2282 \def\SUF@versionstring{\texttt{\version@string} \today}}

```

The default headers

```

2283 \renewcommand{\chaptermark}[1]{%
2284     \markboth{\chaptertitlename\ \protect\SUF@HEAD@thechapter}{#1}}
2285 \ifsuftesi@article
2286     \renewcommand{\sectionmark}[1]{\markright{\protect\SUF@HEAD@thesection.\ #1}}
2287     \else
2288     \renewcommand{\sectionmark}[1]{}
2289 \fi

```

The plain style

```
2290 \fancypagestyle{plain}{\fancyhf{}}
```

The sufplain style

```
2291 \fancypagestyle{sufplain}{%
2292 \fancyhf{}%
2293 \fancyfoot[RE,LO]{%
2294 \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
2295 \fancyfoot[C]{\footnotesize\SUF@thepage}}
```

The centerheader style

```
2296 \fancypagestyle{centerheader}{%
2297 \fancyhf{}%
2298 \fancyfoot[RE,LO]{%
2299 \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
2300 \fancyhead[CO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
2301 \fancyhead[CE]{\footnotesize\xheadbreakfalse%
2302 \SUF@LR@MarkSwitch}
2303 \fancyfoot[C]{\footnotesize\SUF@thepage}%
2304 }%
```

The sufdefault style

```
2305 \fancypagestyle{sufdefault}{%
2306 \fancyhf{}%
2307 \fancyfoot[RE,LO]{%
2308 \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
2309 \fancyhead[LE,RO]{\footnotesize\SUF@thepage}
2310 \fancyhead[LO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
2311 \fancyhead[RE]{\footnotesize\xheadbreakfalse%
2312 \SUF@LR@MarkSwitch}
2313 }%
2314 %
2315 \ifsuftesi@article
2316 \ifsuftesi@authortitle
2317 \def\SUF@LR@MarkSwitch{\SUF@leftmark}
2318 \else
2319 \def\SUF@LR@MarkSwitch{\SUF@rightmark}
2320 \fi
2321 \else
2322 \def\SUF@LR@MarkSwitch{\SUF@leftmark}
2323 \fi
2324 \def\SUF@leftrightmark{%
2325 \if@mainmatter\leftmark\else\rightmark\fi}
2326 \pagestyle{sufdefault}
2327 \ifsuftesi@centerheader\pagestyle{centerheader}\else\fi
2328 \ifsuftesi@sufplain\pagestyle{sufplain}\else\fi

Setting the default page style:
```

Text elements

Block Quotations New environments for block quotations according to a popular Italian style. The font size is the same of the footnotes and the margins are set to `\parindent`.

```
2329 \renewenvironment{quotation}
2330     {\list{}{\listparindent\parindent%
2331             \itemindent \listparindent
2332             \leftmargin \parindent
2333             \SUF@quote@style
2334             \parsep \z@ \@plus\p@}%
2335     \item\relax%
2336     \SUF@quotation@size%
2337     \noindent\ignorespaces}
2338     {\endlist}
2339 \renewenvironment{quote}
2340     {\list{}{\leftmargin \parindent
2341             \SUF@quote@style}%
2342     \item\relax%
2343     \SUF@quotation@size}%\ignorespaces?
2344     {\endlist}
2345 \renewenvironment{verse}
2346     {\let\\\@centercr
2347     \list{}{\itemsep \z@
2348             \itemindent -1.5em%
2349             \listparindent\itemindent
2350             \rightmargin \leftmargin
2351             \advance\leftmargin 1.5em}%
2352     \item\relax
2353     \SUF@quotation@size}
2354     {\endlist}
```

The fewfootnotes option Enable only with three footnotes per page maximum.

```
2355 \ifsufteresi@fewfootnotes
2356 \AtBeginDocument{%
2357 \def\@fnsymbol#1{\ensuremath{\ifcase#1\or*\or{*}{*}\or{*}{*}{*}\or%
2358 \ClassError{sufteresi}%
2359 {Too many footnotes}\MessageBreak
2360 Remove the class option 'fewfootnote'}
2361 {Too many footnotes}\MessageBreak
2362 Remove the class option 'fewfootnote'}
2363 \else\@ctrerr\fi}}
2364 \def\thefootnote{\@fnsymbol\c@footnote}%
2365 \else\fi
    Prints a footnote with discretionary symbol give in the first argument.
2366 \newcommand*\xfootnote[1][*]{%
2367     \xdef\@thefnmark{#1}%
2368     \@footnotemark\@footnotetext}
```

Marginal notes The `\marginpar` command is redefined according to the look of *Classic Thesis* by André Miede (2011).

```

2369 \def\SUF@mpsetup{%
2370   \itshape
2371   \footnotesize%
2372   \parindent=0pt \lineskip=0pt \lineskiplimit=0pt %
2373   \tolerance=2000 \hyphenpenalty=300 \exhyphenpenalty=300%
2374   \doublehyphendemerits=100000%
2375   \finalhyphendemerits=\doublehyphendemerits}
2376 \let\oldmarginpar\marginpar
2377 \renewcommand{\marginpar}[1]{\oldmarginpar%
2378   [\SUF@mpsetup\raggedleft\hspace{0pt}{#1}]%
2379   {\SUF@mpsetup\raggedright\hspace{0pt}{#1}}}
```

Redefine an internal command of the `todonotes` package in order to use the class-specific marginal notes when this package is loaded. This redefinition simply substitute `\oldmarginpar` to `\marginpar`:

```

2380 \AtBeginDocument{%
2381 \ifpackageloaded{todonotes}{%
2382 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
2383 \begin{tikzpicture}[remember picture, overlay, baseline=-0.75ex]%
2384   \node [coordinate] (inText) {};%
2385 \end{tikzpicture}}%
2386 \oldmarginpar[{} Draw note in left margin
2387   \@todonotes@drawMarginNote%
2388   \@todonotes@drawLineToLeftMargin%
2389 ]}{% Draw note in right margin
2390   \@todonotes@drawMarginNote%
2391   \@todonotes@drawLineToRightMargin%
2392 }%
2393 }%
2394 }
2395 {\relax}}
```

Abstract

```

2396 \ifsuftesi@collection
2397 \newenvironment{abstract}{%
2398   \if@twocolumn
2399     \section*{\abstractname}%
2400   \else
2401     \small
2402     \begin{center}%
2403       {\abstractname\vspace{- .5em}\vspace{\z@}}%
2404     \end{center}%
2405     \quotation
2406   \fi}
2407   {\if@twocolumn\else\endquotation\fi\vspace{6ex}}
2408 \else
2409 \if@titlepage
2410 \newenvironment{abstract}{%
2411   \titlepage
2412   \null\vfil
2413   \@beginparpenalty\@lowpenalty
```

```

2414     \begin{center}%
2415         \abstractname
2416     \endparpenalty\@M
2417     \end{center}}%
2418     {\par\vfil\null\endtitlepage}
2419 \else
2420 \newenvironment{abstract}{%
2421     \if@twocolumn
2422     \section*{\abstractname}%
2423     \else
2424     \small
2425     \begin{center}%
2426         {\abstractname\vspace{-.5em}\vspace{\z@}}%
2427     \end{center}%
2428     \quotation
2429     \fi}
2430     {\if@twocolumn\else\endquotation\fi}
2431 \fi
2432 \fi
2433 \newcommand\abstractname{Abstract}

```

Colophon or copyright notice

```

2434 \newcommand{\colophon}[3][ ]{%
2435     \thispagestyle{empty}
2436     \null
2437     \vfill
2438     \def\next{#2}
2439     \ifx\next\@empty\else
2440         \noindent Copyright \copyright{} \the\year~#2\[[lex]
2441         Tutti i diritti riservati
2442     \fi
2443     \vfill
2444     {\small\noindent Questo lavoro \e stato composto con \LaTeX{}%
2445     \def\next{#1}
2446     \ifx\next\@empty\else su #1
2447     \fi usando la classe \textsf{suftesi} di
2448     Ivan Valbusa\index{Valbusa, Ivan}. #3\par}
2449     \cleardoublepage}

2450 \newcommand{\bookcolophon}[2]{%
2451     \thispagestyle{empty}
2452     \null
2453     \vfill
2454     \noindent #1
2455     \vfill
2456     {\small\noindent #2\par}
2457     \cleardoublepage}

2458 \newcommand{\artcolophon}[1]{%
2459     \thispagestyle{empty}
2460     \null

```

```

2461 \vfill
2462 {\small\noindent #1\par}}
2463 \newcommand{\finalcolophon}[1]{%
2464 \thispagestyle{empty}
2465 \null\vspace*{\stretch{1}}
2466 \begin{center}
2467 \begin{minipage}{.5\textwidth}
2468 \centering\small #1
2469 \end{minipage}
2470 \end{center}
2471 \vspace*{\stretch{6}}}

```

The \FSPL colophon This command is defined only for the style=FSPL* options.

```

2472 \ifsuftesi@FSPL
2473 \newcommand{\FSPLcolophon}[1][\the\year]{%
2474 \begingroup
2475 \thispagestyle{empty}
2476 \null\vspace{\stretch{1}}
2477 \noindent \hskip-.5em\cc #1 \@author%
2478 \vskip1ex
2479
2480 \small\noindent This work is licensed under the Creative Commons
2481 Attribution-NonCommercial-NoDerivs 3.0 Unported License.
2482 To view a copy of this license,
2483 visit http://creativecommons.org/licenses/by-nc-nd/3.0/.
2484
2485 \endgroup
2486
2487 \begingroup
2488 \footnotesize
2489
2490 \null\vspace{\stretch{1}}
2491
2492 \noindent Typeset with \LaTeX{} in collaboration with the Joint Project
2493 \emph{Formal Style for PhD Theses with \LaTeX{}} (University of Verona,
2494 Italy) using the \textsf{suftesi} class by Ivan Valbusa. The text face
2495 is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by
2496 Janusz M. Nowacki.
2497
2498 \endgroup
2499
2500 \clearpage}
2501 \else
2502 \def\FSPLcolophon{%
2503 \ClassError{suftesi}
2504 {\noexpand\FSPLcolophon is defined\MessageBreak
2505 only for the FSPL styles}
2506 {\noexpand\FSPLcolophon is defined\MessageBreak
2507 only for the FSPL styles}}

```

2508 \fi

Toc, lof, lot

2509 \RequirePackage{titletoc}

All the lengths depend on \SUF@label@chap so we define this first.

2510 \newlength\SUF@label@chap

2511 \setlength\SUF@label@chap{.5em}

\toclabelwidth is provided to adjust the label width in the table of contents:

2512 \newcommand*\toclabelwidth}[2]{%

2513 \AtBeginDocument{

2514 \addtolength{\csname SUF@label@#1\endcsname}{#2}%

2515 \addtolength{\csname SUF@tocindent@#1\endcsname}{#2}%

2516 }

2517 }

2518 \newcommand\toclabelwidthspace{%

2519 \ClassError{suftesi}

2520 {\MessageBreak

2521 \noexpand\toclabelwidthspace is not more defined\MessageBreak

2522 Use \noexpand\toclabelwidth instead.\MessageBreak

2523 See package documentation for details}

2524 {\MessageBreak

2525 \noexpand\toclabelwidthspace is not more defined\MessageBreak

2526 Use \noexpand\toclabelwidth instead.\MessageBreak

2527 See package documentation for details}}

This macro controls the space between page number and chapter label using the `tocpageleft` option:

2528 \newlength{\SUF@tochang}

2529 \setlength{\SUF@tochang}{3em}

2530 \AtBeginDocument{

2531 \newlength\SUF@label@part

2532 \newlength\SUF@label@sec

2533 \newlength\SUF@label@subsec

2534 \newlength\SUF@label@subsubsec

2535 \newlength\SUF@label@par

2536 \newlength\SUF@label@subpar

2537 \newlength\SUF@label@fig

2538 \newlength\SUF@label@tab

2539 \setlength\SUF@label@part

2540 {\SUF@label@chap}

2541 \setlength\SUF@label@sec

2542 {\dimexpr(\SUF@label@chap+.5em)}

2543 \setlength\SUF@label@subsec

2544 {\dimexpr(\SUF@label@sec+.5em)}

2545 \setlength\SUF@label@subsubsec

2546 {\dimexpr(\SUF@label@subsec+.5em)}

2547 \setlength\SUF@label@par

2548 {\dimexpr(\SUF@label@subsubsec+.5em)}

2549 \setlength\SUF@label@subpar

2550 {\dimexpr(\SUF@label@par+.5em)}

```

2551 \setlength\SUF@label@fig
2552     {\SUF@label@sec}
2553 \setlength\SUF@label@tab
2554     {\SUF@label@sec}
2555 }
    Part in article mode
2556 \titlecontents{part}
2557     [0em]
2558     {\addvspace{3ex}\partname\hspace*{.5em}}
2559     {\makebox[\SUF@label@part][l]{%
2560         \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}
2561     {}
2562     {}
2563     [\addvspace{1ex}]
    ‘tocpageleft’ toc
2564 \ifsuf@pagelefttoc
    First we reset the right margin to zero:
2565 \contentsmargin{0pt}
2566 \AtBeginDocument{
2567 \newlength\SUF@tochang@chap
2568 \newlength\SUF@tochang@sec
2569 \newlength\SUF@tochang@subsec
2570 \newlength\SUF@tochang@subsubsec
2571 \newlength\SUF@tochang@par
2572 \newlength\SUF@tochang@subpar
2573 \newlength\SUF@tochang@fig
2574 \newlength\SUF@tochang@tab
2575 \newlength\SUF@addto@tochang@chap
2576 \newlength\SUF@addto@tochang@sec
2577 \newlength\SUF@addto@tochang@subsec
2578 \newlength\SUF@addto@tochang@subsubsec
2579 \newlength\SUF@addto@tochang@par
2580 \newlength\SUF@addto@tochang@subpar
2581 \newlength\SUF@addto@tochang@fig
2582 \newlength\SUF@addto@tochang@tab
2583 \setlength\SUF@tochang@chap
2584     {\dimexpr(1em+\SUF@tochang+\SUF@label@chap+1em)}
2585 \setlength\SUF@tochang@sec
2586     {\dimexpr(\SUF@tochang@chap+\SUF@label@sec+1em)}
2587 \setlength\SUF@tochang@subsec
2588     {\dimexpr(\SUF@tochang@sec+\SUF@label@subsec+1em)}
2589 \setlength\SUF@tochang@subsubsec
2590     {\dimexpr(\SUF@tochang@subsubsec+\SUF@label@subsubsec+1em)}
2591 \setlength\SUF@tochang@par
2592     {\dimexpr(\SUF@tochang@subsubsec+\SUF@label@par+1em)}
2593 \setlength\SUF@tochang@subpar
2594     {\dimexpr(\SUF@tochang@par+\SUF@label@subpar+1em)}
2595 \setlength\SUF@tochang@fig
2596     {\SUF@tochang@chap}

```

```

2597 \setlength\SUF@tochang@tab
2598     {\SUF@tochang@chap}
2599 \setlength\SUF@addto@tochang@chap
2600     {\SUF@tochang}
2601 \setlength\SUF@addto@tochang@sec
2602     {\dimexpr(\SUF@addto@tochang@chap+\SUF@label@sec+.5em)}
2603 \setlength\SUF@addto@tochang@subsec
2604     {\dimexpr(\SUF@addto@tochang@sec+\SUF@label@subsec+.5em)}
2605 \setlength\SUF@addto@tochang@subsubsec
2606     {\dimexpr(\SUF@addto@tochang@subsec+\SUF@label@subsubsec+.5em)}
2607 \setlength\SUF@addto@tochang@par
2608     {\dimexpr(\SUF@addto@tochang@subsubsec+\SUF@label@par+.5em)}
2609 \setlength\SUF@addto@tochang@subpar
2610     {\dimexpr(\SUF@addto@tochang@par+\SUF@label@subpar+.5em)}
2611 \setlength\SUF@addto@tochang@fig
2612     {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2613 \setlength\SUF@addto@tochang@tab
2614     {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2615 }

```

TOC entries

```

2616 \titlecontents{chapter}
2617     [\SUF@tochang@chap]
2618     {\advvspace{2ex}}
2619     {\hskip-\SUF@tochang@chap%
2620      \makebox[1em][l]{\thecontentspage}%
2621      \hskip\SUF@addto@tochang@chap%
2622      \makebox[\SUF@label@chap][l]{%
2623        \SUF@toclabelnum\thecontentslabel}\hspace*{1em}%
2624        \SUF@tocCHAP@font}
2625     {\hskip-\SUF@tochang@chap%
2626      \makebox[1em][l]{\thecontentspage}%
2627      \hskip\SUF@addto@tochang@chap\SUF@tocCHAP@font}
2628     {}
2629     [\advvspace{1ex}]
2630 \titlecontents{section}
2631     [\SUF@tochang@sec]
2632     {}
2633     {\hskip-\SUF@tochang@sec%
2634      \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@sec%
2635      \makebox[\SUF@label@sec][l]{%
2636        \ifsuftesi@article\SUF@toclabelnum%
2637        \else\fi\thecontentslabel}\hspace*{1em}%
2638        \SUF@tocSEC@font}
2639     {\hskip-\SUF@tochang@sec%
2640      \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@sec%
2641      \SUF@tocSEC@font}
2642     {}
2643 \titlecontents{subsection}
2644     [\SUF@tochang@subsec]

```

```

2645 {}
2646 {\hskip-\SUF@tochang@subsec%
2647 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subsec%
2648 \makebox[\SUF@label@subsec][l]{\thecontentslabel}\hspace*{1em}%
2649 \SUF@tocSUBSEC@font}
2650 {\hskip-\SUF@tochang@subsec%
2651 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subsec%
2652 \SUF@tocSUBSEC@font}
2653 {}
2654 \titlecontents{subsubsection}
2655 [\SUF@tochang@subsubsec]
2656 {}
2657 {\hskip-\SUF@tochang@subsubsec%
2658 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subsubsec%
2659 \makebox[\SUF@label@subsubsec][l]{\thecontentslabel}\hspace*{1em}%
2660 \SUF@tocSUBSUBSEC@font}
2661 {\hskip-\SUF@tochang@subsubsec%
2662 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subsubsec%
2663 \SUF@tocSUBSUBSEC@font}
2664 {}
2665 \titlecontents{paragraph}
2666 [\SUF@tochang@par]
2667 {}
2668 {\hskip-\SUF@tochang@par%
2669 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@par%
2670 \makebox[\SUF@label@par][l]{\thecontentslabel}\hspace*{1em}}
2671 {\hskip-\SUF@tochang@par%
2672 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@par}
2673 {}
2674 \titlecontents{subparagraph}
2675 [\SUF@tochang@subpar]
2676 {}
2677 {\hskip-\SUF@tochang@subpar%
2678 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subpar%
2679 \makebox[\SUF@label@subpar][l]{\thecontentslabel}\hspace*{1em}}
2680 {\hskip-\SUF@tochang@subpar%
2681 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subpar}
2682 {}
2683 \titlecontents{figure}
2684 [\SUF@tochang@fig]
2685 {}
2686 {\hskip-\SUF@tochang@fig%
2687 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@fig%
2688 \makebox[\SUF@label@tab][l]{\thecontentslabel}\hspace*{1em}}
2689 {}
2690 {}
2691 \titlecontents{table}
2692 [\SUF@tochang@tab]
2693 {}
2694 {\hskip-\SUF@tochang@tab%

```

```

2695 \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@tab%
2696 \makebox[\SUF@label@tab][l]{\thecontentslabel}\hspace*{1em}}
2697 {}
2698 {}
2699 \else

```

Default toc

```

2700 \AtBeginDocument{
2701 \newlength\SUF@tocindent@chap
2702 \newlength\SUF@tocindent@sec
2703 \newlength\SUF@tocindent@subsec
2704 \newlength\SUF@tocindent@subsubsec
2705 \newlength\SUF@tocindent@par
2706 \newlength\SUF@tocindent@subpar
2707 \newlength\SUF@tocindent@fig
2708 \newlength\SUF@tocindent@tab
2709 \ifsuftesi@article
2710 \setlength\SUF@tocindent@sec
2711   {\dimexpr(\SUF@label@chap+1.5em)}
2712 \setlength\SUF@tocindent@subsec
2713   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2714 \setlength\SUF@tocindent@subsubsec
2715   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2716 \setlength\SUF@tocindent@par
2717   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2718 \setlength\SUF@tocindent@subpar
2719   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2720 \setlength\SUF@tocindent@fig
2721   {\dimexpr(\SUF@label@chap+1.5em)}
2722 \setlength\SUF@tocindent@tab
2723   {\dimexpr(\SUF@label@chap+1.5em)}
2724 \else
2725 \setlength\SUF@tocindent@chap
2726   {\dimexpr(\SUF@label@chap+1em)}
2727 \setlength\SUF@tocindent@sec
2728   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec+1em)}
2729 \setlength\SUF@tocindent@subsec
2730   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2731 \setlength\SUF@tocindent@subsubsec
2732   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2733 \setlength\SUF@tocindent@par
2734   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2735 \setlength\SUF@tocindent@subpar
2736   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2737 \setlength\SUF@tocindent@fig
2738   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2739 \setlength\SUF@tocindent@tab
2740   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2741 \fi
2742 }

```

TOC entries

```
2743 \titlecontents{chapter}
2744   [\SUF@tocindent@chap]
2745   {\addvspace{2ex}}
2746   {\hskip-\SUF@tocindent@chap%
2747     \makebox[\SUF@label@chap] [l]{\SUF@toclabelnum\thecontentslabel}}%
2748     \hspace*{1em}%
2749     \SUF@tocCHAP@font}
2750   {\hskip-\SUF@tocindent@chap%
2751     \SUF@tocCHAP@font}
2752   {\SUF@chaptitlerule\contentspage}
2753   [\addvspace{1ex}]
2754 \titlecontents{section}
2755   [\SUF@tocindent@sec]
2756   {}
2757   {\hskip-\dimexpr(\SUF@label@sec+1em)%
2758     \makebox[\SUF@label@sec] [l]{%
2759       \ifsuftesi@article\SUF@toclabelnum%
2760       \else\fi\thecontentslabel}\hspace*{1em}}%
2761     \SUF@tocSEC@font}
2762   {\hskip-\dimexpr(\SUF@label@sec+1em)%
2763     \SUF@tocSEC@font}
2764   {\ifsuftesi@article\SUF@chaptitlerule%
2765     \else\SUF@titlerule\fi\contentspage}
2766 \titlecontents{subsection}
2767   [\SUF@tocindent@subsec]
2768   {}
2769   {\hskip-\dimexpr(\SUF@label@subsec+1em)%
2770     \makebox[\SUF@label@subsec] [l]{\thecontentslabel}\hspace*{1em}}%
2771     \SUF@tocSUBSEC@font}
2772   {\hskip-\dimexpr(\SUF@label@subsec+1em)%
2773     \SUF@tocSUBSEC@font}
2774   {\SUF@titlerule\contentspage}
2775 \titlecontents{subsubsection}
2776   [\SUF@tocindent@subsubsec]
2777   {}
2778   {\hskip-\dimexpr(\SUF@label@subsubsec+1em)%
2779     \makebox[\SUF@label@subsubsec] [l]{\thecontentslabel}\hspace*{1em}}%
2780     \SUF@tocSUBSUBSEC@font}
2781   {\hskip-\dimexpr(\SUF@label@subsubsec+1em)%
2782     \SUF@tocSUBSUBSEC@font}
2783   {\SUF@titlerule\contentspage}
2784 \titlecontents{paragraph}
2785   [\SUF@tocindent@par]
2786   {}
2787   {\hskip-\dimexpr(\SUF@label@par+1em)%
2788     \makebox[\SUF@label@par] [l]{\thecontentslabel}\hspace*{1em}}
2789   {\hskip-\dimexpr(\SUF@label@par+1em)}
2790   {\SUF@titlerule\contentspage}
```

```

2791 \titlecontents{subparagraph}
2792   [\SUF@tocindent@subpar]
2793   {}
2794   {\hskip-\dimexpr(\SUF@label@subpar+1em)%
2795     \makebox[\SUF@label@subpar][1]{\thecontentslabel}\hspace*{1em}}
2796   {\hskip-\dimexpr(\SUF@label@subpar+1em)}
2797   {\SUF@titlerule\contentspage}
2798 \titlecontents{figure}
2799   [\SUF@tocindent@fig]
2800   {}
2801   {\hskip-\SUF@tocindent@fig%
2802     \makebox[\SUF@label@fig][1]{\thecontentslabel}\hspace*{1em}}
2803   {}
2804   {\SUF@titlerule\contentspage}
2805 \titlecontents{table}
2806   [\SUF@tocindent@tab]
2807   {}
2808   {\hskip-\SUF@tocindent@tab%
2809     \makebox[\SUF@label@tab][1]{\thecontentslabel}\hspace*{1em}}
2810   {}
2811   {\SUF@titlerule\contentspage}
2812 \fi

```

With article option the toc, lof and lot are printed as sections.

```

2813 \ifsuftesi@article
2814 \renewcommand\tableofcontents{%
2815   \vspace{2ex}%
2816   \section*{\contentsname}%
2817   \@mkboth{\contentsname}{\contentsname}%
2818   \thispagestyle{empty}
2819   \ifsuftesi@twocolumntoc
2820     \begin{multicols}{2}
2821       \starttoc{toc}%
2822     \end{multicols}
2823   \else
2824     \starttoc{toc}%
2825   \fi
2826   \vspace{2ex}%
2827 }
2828 \renewcommand\listoffigures{%
2829   \vspace{2ex}%
2830   \section*{\listfigurename}%
2831   \@mkboth{\listfigurename}{\listfigurename}%
2832   \thispagestyle{empty}
2833   \ifsuftesi@twocolumnlof
2834     \begin{multicols}{2}
2835       \starttoc{lof}%
2836     \end{multicols}
2837   \else
2838     \starttoc{lof}%

```

```

2839     \fi
2840     \vspace{2ex}%
2841   }
2842 \renewcommand\listoftables{%
2843   \vspace{2ex}%
2844   \section*{\listtablename}%
2845   \@mkboth{\listtablename}{\listtablename}%
2846   \thispagestyle{empty}
2847   \ifsuftesi@twocolumnlot
2848     \begin{multicols}{2}
2849     \@starttoc{lot}%
2850   \end{multicols}
2851   \else
2852     \@starttoc{lot}%
2853   \fi
2854   \vspace{2ex}%
2855 }
2856 \else
  The default toc, lof and lot are treated as chapters.
2857 \renewcommand\tableofcontents{%
2858   \if@twocolumn
2859     \@restonecoltrue\onecolumn
2860   \else
2861     \@restonecolfalse
2862   \fi
2863   \chapter*{\contentsname}%
2864   \@mkboth{%
2865     \contentsname
2866     {\contentsname}%
2867   \thispagestyle{empty}
2868   \ifsuftesi@twocolumntoc
2869     \begin{multicols}{2}
2870     \@starttoc{toc}%
2871   \end{multicols}
2872   \else
2873     \@starttoc{toc}%
2874   \fi
2875   \if@restonecol\twocolumn\fi
2876 }
2877 \renewcommand\listoffigures{%
2878   \if@twocolumn
2879     \@restonecoltrue\onecolumn
2880   \else
2881     \@restonecolfalse
2882   \fi
2883   \chapter*{\listfigurename}%
2884   \@mkboth{\listfigurename}%
2885     {\listfigurename}%
2886   \thispagestyle{empty}

```

```

2887     \ifsuftesi@twocolumnlof
2888     \begin{multicols}{2}
2889     \@starttoc{lof}%
2890     \end{multicols}
2891     \else
2892     \@starttoc{lof}%
2893     \fi
2894     \if@restonecol\twocolumn\fi
2895     }
2896 \renewcommand\listoftables{%
2897     \if@twocolumn
2898     \@restonecoltrue\onecolumn
2899     \else
2900     \@restonecolfalse
2901     \fi
2902     \chapter*{\listtablename}%
2903     \@mkboth{%
2904         \listtablename}%
2905     {\listtablename}%
2906     \thispagestyle{empty}
2907     \ifsuftesi@twocolumnlot
2908     \begin{multicols}{2}
2909     \@starttoc{lot}%
2910     \end{multicols}
2911     \else
2912     \@starttoc{lot}%
2913     \fi
2914     \if@restonecol\twocolumn\fi
2915     }
2916 \fi

```

New commands

```

2917 \ifsuftesi@article
2918 \def\chapterintro{%
2919 \ClassError{suftesi}
2920 {Command \noexpand\chapterintro is undefined\MessageBreak
2921   using 'structure=article'}
2922 {Command \noexpand\chapterintro is undefined\MessageBreak
2923   using 'structure=article'}}
2924 \else
2925 \def\chapterintro{\@ifstar{%
2926   \@tempwafalse\@chapterintro}{\@tempwattrue\@chapterintro}}
2927 \def\@chapterintro{\phantomsection
2928   \if@tempswa\section*{\SUF@fchapterintroname}\fi
2929   \addcontentsline{toc}{section}{\SUF@fchapterintroname}}
2930 \newcommand{\chapterintroname}[1]{\def\SUF@fchapterintroname{#1}}
2931 \chapterintroname{Introduzione}
2932 \fi

```

Manual breaks Active in the table of contents but not in the text.

```

2933 \newif\ifheadbreak\headbreakfalse
2934 \DeclareRobustCommand{\headbreak}
2935   {\ifheadbreak\\\else\fi}
    Active in the text but not in the table of contents.
2936 \newif\ifxheadbreak\xheadbreaktrue
2937 \def\xheadbreakNL{\ifxheadbreak\newline\else\fi}
2938 \def\xheadbreakBB{\ifxheadbreak\\\else\fi}
2939 \let\origtableofcontents\tableofcontents
2940 \renewcommand{\tableofcontents}{%
2941   \begingroup\headbreaktrue\xheadbreakfalse%
2942   \origtableofcontents\endgroup}

```

Backward compatibility An environment to manually typeset the bibliography. (Use `biblatex` instead!)

```

2943 \newenvironment{bibliografia}{%
2944   \ifsuftesi@article
2945     \section*{\refname}
2946     \addcontentsline{toc}{section}{\refname}
2947   \else
2948     \chapter{\bibname}%
2949   \fi
2950     \normalfont \list{}{%
2951       \setlength{\itemindent}{-\parindent}
2952       \setlength{\leftmargin}{\parindent}
2953       \setlength{\labelwidth}{0pt}
2954       \setlength{\parsep}{\parskip}
2955       \let\makelabel}}
2956   {\endlist}

```

An environment to manually typeset the list of shorthands. (Use `biblatex` instead!)

```

2957 \newcommand{\losname}{Sigle}
2958 \newcommand{\itlabel}[1]{\itshape\hbox to 6em{#1}}
2959 \newenvironment{sigle}{%
2960   \chapter{\losname}
2961   \normalfont \list{}{%
2962     \setlength{\labelsep}{0.5em}
2963     \setlength{\itemindent}{0pt}
2964     \setlength{\leftmargin}{6em}
2965     \setlength{\labelwidth}{\leftmargin}
2966     \setlength{\listparindent}{\parindent}
2967     \setlength{\parsep}{\parskip}
2968     \let\makelabel\itlabel}}
2969   {\endlist}

```

Final settings

Renew `\frontmatter` to have arabic page numbering:

```

2970 \ifsuftesi@article
2971 \renewcommand\frontmatter{\ClassError{suftesi}

```

```

2972 {Command \noexpand\frontmatter is undefined\MessageBreak
2973   using 'structure=article'}
2974 {Command \noexpand\frontmatter is undefined\MessageBreak
2975   using 'structure=article'}}
2976 \renewcommand\mainmatter{\ClassError{suftesi}
2977 {Command \noexpand\mainmatter is undefined\MessageBreak
2978   using 'structure=article'}
2979 {Command \noexpand\mainmatter is undefined\MessageBreak
2980   using 'structure=article'}}
2981 \renewcommand\backmatter{\ClassError{suftesi}
2982 {Command \noexpand\backmatter is undefined\MessageBreak
2983   using 'structure=article'}
2984 {Command \noexpand\backmatter is undefined\MessageBreak
2985   using 'structure=article'}}
2986 \else
2987 \renewcommand\frontmatter{\cleardoublepage\@mainmatterfalse}
2988 \renewcommand\mainmatter{\cleardoublepage\@mainmattertrue}
2989 \fi

```

In a previous version the `\hemph` command was provided to fix a bug in the hyphenation of some italian expressions like “dell’*encyclopaedia*”. Now the bug has been fixed by the `fixltxhyph` package by Claudio Beccari. The package must be loaded after `babel` or `polyglossia`:

```

2990 \@ifpackageloaded{babel}
2991   {\AtBeginDocument{\RequirePackage{fixltxhyph}}}{ }
2992 \@ifpackageloaded{polyglossia}
2993   {\AtBeginDocument{\RequirePackage{fixltxhyph}}}{ }

```

The `\hemph` command is provided only for backward compatibility:

```
2994 \let\hemph\emph
```

The first line of all sections is indented by default using $X_{\text{q}}\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ with Italian as the main language. Anyway this is incongruous with the $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ default.

```

2995 \unless\ifPDFTeX% if xetex or luatex
2996   \let\@afterindenttrue\@afterindentfalse
2997   \else
2998   \relax
2999 \fi

```

Just one touch of french typography:

```
3000 \frenchspacing
```

Change History

v0.5	New option <code>compact</code>	24
General: First public release. The frontispiece of <code>suftesi</code> is now included in the package	New option <code>elements</code>	24
<code>frontespizio</code> . New option	New option <code>nocrop</code>	24
<code>fullplain</code> Changed option	New option <code>nomarginpar</code>	24
<code>sctitles</code> 1	New option <code>sufelements</code>	24
New command <code>chapnumfont</code> 20	New option <code>supercompact</code>	24
	General: English documentation.	

Renamed options <code>plain</code> and <code>fullplain</code> to <code>centerheadings</code> and <code>sufplain</code>	1	New option <code>italicchap</code>	24
New command <code>\artcolophon</code>	19	New option <code>italicheader</code>	24
New command <code>\bookcolophon</code>	18	New option <code>italicpart</code>	24
New option <code>authortitle</code>	24	New option <code>italicsec</code>	24
v0.6a		New option <code>italicsubsec</code>	24
General: Maintenance release, no changes	1	New option <code>itstyle(1-12)</code>	24
v0.6b		New option <code>numparchap</code>	24
General: Improved full compatibility with $X_{\text{L}}^{\text{L}}\text{A}_{\text{T}}\text{E}_{\text{X}}$. <code>varioref</code> and <code>footmisc</code> packages are no longer loaded	1	New option <code>numparpart</code>	24
v0.6c		New option <code>numparsec</code>	24
General: Maintenance release, no changes	1	New option <code>ralignquotation</code>	24
v0.7		New option <code>rightchap</code>	24
General: Maintenance release, no changes. Provided a thesis template	1	New option <code>rightpart</code>	24
v0.8		New option <code>rightsec</code>	24
General: Added macro for using <code>frontespizio</code> package with <code>compact</code> and <code>supercompact</code> options.	1	New option <code>rmstyle(1-6)</code>	24
New option <code>periodical</code>	24	New option <code>romanchap</code>	24
Renewed <code>\title</code> command	20	New option <code>scstyle(1-12)</code>	24
v0.9		New option <code>smallcapschap</code>	24
General: Improved compatibility with <code>mathspec</code>	1	New option <code>smallcapsheader</code>	24
New option <code>dottedtoc</code>	24	New option <code>smallcapspart</code>	24
New option <code>raggedtoc</code>	24	New option <code>smallcapssec</code>	24
v0.9a		New option <code>smallquotation</code>	24
General: Added inline option to <code>enumitem</code> package. Deleted <code>centertitle</code> option. Deleted <code>sctitles</code> option. Changed code for <code>toc</code> , <code>lot</code> and <code>lof</code> elements.	1	New option <code>standardfootnote</code>	24
New command <code>\toclabelsspace</code>	20	New option <code>tocpageleft</code>	24
New option <code>alignlist</code>	24	v0.9b	
New option <code>centerchap</code>	24	General: Changed	
New option <code>centerpart</code>	24	<code>standardfootnote</code> option and renamed to <code>footnotestyle</code>	14
New option <code>centersec</code>	24	New command <code>\xfootnote</code>	20
New option <code>defaultparindent</code>	24	New option <code>fewfootnotes</code>	15
New option <code>dottedchap</code>	24	New option <code>greekfont</code>	11
New option <code>dottedfootnote</code>	24	New option <code>pagestyle</code>	10
New option <code>dottedpart</code>	24	New option <code>parindent</code>	15
New option <code>indentlist</code>	24	New option <code>partpage</code>	15
		New option <code>quotationfont</code>	14
		New option <code>quotestyle</code>	14
		New option <code>structure</code>	10
		New option <code>tocstyle</code>	13
		Restored 11pt and 12pt option to default	1
		The <code>epigraph</code> package is no longer loaded	2
		The <code>mparhack</code> package is no longer loaded. It is not compatible with <code>crop</code>	3
		v0.9c	
		General: Maintenance release, no changes	1

v1.0	General: First stable release. Renamed option <code>bozza</code> to <code>draftdate</code> 15	and <code>sanserif</code> values for <code>captionstyle</code> option. New <code>twocolcontents</code> option. New <code>supercompactaureo</code> page layout. Changed <code>\toclabelspace</code> command and renamed to <code>\toclabelwidth</code> . New <code>collection</code> document structure 1
v1.1	General: Added the <code>fixltxhyph</code> package. Documentation updated. 1	v1.9a
v1.2	General: Maintenance release. Added the <code>\toclabelspace</code> command. 1	General: Maintenance release. Updated greek support. Updated documentation. 1
v1.3	General: New command <code>\FSPLcolophon</code> 24 Updated documentation. Added <code>FSPLa</code> , <code>FSPLb</code> and <code>FSPLc</code> styles. 1	v1.9b
v1.4	General: New value <code>periodicalaureo</code> for option <code>pagelayout</code> . Changed code for <code>\xfootnote</code> command. 1	General: Corrected a bug in “ <code>toc</code> ”, “ <code>lof</code> ” and “ <code>lot</code> ” commands. 1
v1.5	General: The <code>microtype</code> package is loaded for all engines. Improved compatibility with <code>todonotes</code> package and with <code>mdframed</code> and <code>bookmark</code> packages when using <code>style</code> class option. New option <code>viewmode</code> 1	v1.9c
v1.6	General: New option <code>viewmode</code> . Corrected bugs in the definition of <code>\listoffigures</code> , <code>\listoftables</code> and <code>\tableofcontents</code> commands. Updated documentation. 1	General: The <code>cbgreek</code> value for the <code>greekfont</code> option allows now to use the full set of the CB Greek font together with the default font (Palatino). 1
v1.7	General: Renamed <code>viewmode</code> option to <code>version</code> : renamed <code>print</code> value to <code>draft</code> and added <code>final</code> value. New <code>smallcapsstyle</code> option. 1	v2.0
v1.8	General: Maintenance release. Corrected a bug in the definition of <code>\appendix</code> 1	General: New page layout <code>standardaureo</code> . Enhanced support for Lua ^A TeX. Headers settings are now executed <code>\AtBeginDocument</code> . Loaded <code>ifluatex</code> and <code>ifthen</code> packages. Added <code>listparindent</code> to <code>\setlist</code> options. Updated documentation. 1
v1.9	General: Added <code>italic</code> , <code>smallcaps</code>	v2.0.1
		General: Corrected a bug in <code>version</code> option. 1
		v2.1
		General: New option <code>toc<level>font</code> . Updated documentation. Removed <code>\includeart</code> command 1
		v2.2
		General: Maintenance release. 1
		v2.3
		General: Maintenance release. 1
		v2.4
		General: Changed the default font to Cochineal with Linux Biolinum O sans serif and Inconsolata monospaced. The Palatino is now loaded with

	<code>newpxtext</code> and <code>newpxmath</code> .	(missing some <code>\fi</code> commands).	1
	Bera Mono and Iwona have been substituted by Linux Biolinum O and Inconsolata. New values for font options: <code>cochineal</code> , <code>libertine</code> , <code>bodoni</code> (greek only). Value <code>compatibility</code> for <code>defaultfont</code> option to get the fonts of <code>suftesi</code> v2.3 or previous. Updated documentation.		1
v2.5	General: Corrected a bug when loading CB Greek fonts. Renamed option <code>documentstructure</code> to <code>structure</code> . Updated documentation.		1
v2.6	General: New <code>mathfont</code> option for non-standard fonts. New command <code>\makecover</code> for printing the cover page. Updated documentation.		1
v2.7	General: New value <code>cscreen</code> for <code>version</code> option. Updated documentation. Removed value <code>elements</code> for options: <code>pagelayout</code> , <code>headerstyle</code> , <code>captionstyle</code> , <code>chapstyle</code> , <code>style</code> ; <code>sufelements</code> for option: <code>style</code> . The <code>\chapnumfont</code> command is no longer available.		1
v2.7.1	General: Corrected a bug in v.2.7		
		v2.8	
		General: <code>textcase</code> no longer loaded. Changed definitions of <code>\suftesi@MakeTextLowercase</code> , <code>\SUF@titlesmallcaps</code> , <code>\headbreak</code> , <code>\xheadbreak</code>	1
		v2.9	
		General: New options <code>tocauthorfont</code> and <code>toctitlefont</code> . Added macros <code>\suftesi@MakeTextTOCLowercase</code> and <code>\SUF@TOCTitlesmallcaps</code> . Improved <code>\xheadbreak</code> command. New templates <code>book</code> , <code>theses-template-article</code> , <code>theses-template-book</code>	1
		v2.9.1	
		General: Added <code>libertinust1math</code> package for Libertine font. Added <code>luatex85</code> for LuaTeX engine	1
		v2.9.2	
		General: Added <code>\protect</code> to <code>\SUF@thechapter</code> and <code>\SUF@thesection</code> in the definitions of <code>\chaptermark</code> and <code>\sectionmark</code> to correct a bug when loading <code>greek</code> option with <code>babel</code>	1
		v2.9.3	
		General: New commands to change the font of the section/number title	21
		Updated documentation.	1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined> refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	<code>\@Cfootcolor</code>	1708, 1753	1738, 1743, 1748
<code>\@Alpha</code>	<code>\@Cpagecolor</code>	1705, 1722	<code>\@Ctitle</code> 1700, 1736, 1738
<code>\@Cauthor</code> 1702, 1730, 1732	<code>\@Csubtitle</code>		<code>\@M</code> 2416
<code>\@Ccirclecolor</code>	1701, 1741, 1743	<code>\@Roman</code> 421, 433, 451,
<code>\@Ceditor</code> 1703, 1746, 1748	<code>\@Ctextcolor</code>		466, 484, 499,
<code>\@Cfoot</code> 1704, 1751, 1754	. . .	1707, 1732,	514, 526, 541, 553

<code>\@afterindentfalse</code>	2996	<code>\@issueyear</code>	2001	<code>\@starttoc</code>	2821,
<code>\@afterindenttrue</code>	2996	<code>\@journalname</code>		2824, 2835,
<code>\@arabic</code> 1575,		.. 1979, 1980, 1999		2838, 2849,
	1577, 1579,	<code>\@journalnumber</code>	...		2852, 2870,
	1581, 1583,		.. 1985, 1986, 1999		2873, 2889,
	2152, 2154,	<code>\@journalvolume</code>	...		2892, 2909, 2912
	2156, 2158, 2160	 1982, 1983	<code>\@tempwafalse</code>	... 2926
<code>\@author</code> 588,	<code>\@journalwebsite</code>	..	<code>\@tempwatrue</code> 2926
	592, 1791, 1821,	 1994, 1995	<code>\@textsuperscript</code>	..
	1848, 1915,	<code>\@journalyear</code> 1867,
	1961, 2020,		.. 1991, 1992, 2000		1870, 1925,
	2082, 2098,	<code>\@latex@warning@no@line</code>	...		1928, 2059, 2062
	2107, 2112, 2477		.. 1771, 1774,	<code>\@thanks</code> 1826,
<code>\@beginparpenalty</code>	.. 2413		1777, 1980,		1832, 1853,
<code>\@centercr</code> 2346		1983, 1986,		1859, 1882,
<code>\@chapapp</code> 2272		1989, 1992,		1888, 1940,
<code>\@chapterintro</code>	2926, 2927		1995, 2003, 2006		1946, 1997,
<code>\@collectioneditor</code>	..	<code>\@lowpenalty</code> 2413		1998, 2074,
	.. 2005, 2006, 2145	<code>\@mainmatterfalse</code>	.. 2987		2081, 2119, 2134
<code>\@collectiontitle</code>	..	<code>\@mainmattertrue</code>	..	<code>\@thefnmark</code>	... 656,
	.. 2002, 2003, 2142	 2235, 2988		660, 663, 666,
<code>\@ctrerr</code> 2363	<code>\@makefnmark</code>		1867, 1870,
<code>\@currentHref</code>	2100, 2102		.. 1867, 1925, 2059		1925, 1928,
<code>\@date</code>	.. 1824, 1833,	<code>\@makefntext</code>	.. 655,		2059, 2062, 2367
	1851, 1860,		658, 662, 665,	<code>\@title</code>	.. 1780, 1787,
	1889, 1918,		1868, 1926, 2060		1806, 1810,
	1947, 1964, 2083	<code>\@makeschapterhead</code>	2220		1812, 1815,
<code>\@dblarg</code>	... 1781, 2010	<code>\@maketitle</code>	... 1873,		1843, 1900,
<code>\@doi</code> 1773, 1774		1875, 1880,		1904, 1906,
<code>\@endparpenalty</code>	.. 2416		1887, 1892,		1909, 1956,
<code>\@fnsymbol</code> 1800,		2065, 2067,		2009, 2016,
	1866, 1924,		2072, 2080, 2090		2084, 2097, 2114
	2058, 2357, 2364	<code>\@mkboth</code>	2222, 2817,	<code>\@titlepagefalse</code>	78, 825
<code>\@footnotemark</code>	... 2368		2831, 2845,	<code>\@titlepagetrue</code>	... 823
<code>\@footnotetext</code>	... 2368		2864, 2884, 2903	<code>\@todonotes@drawLineToLeftMargin</code> 2388
<code>\@headtitle</code>	... 587,	<code>\@plus</code>	.. 2028, 2226, 2334	<code>\@todonotes@drawLineToRightMargin</code> 2391
	591, 1780, 1783,	<code>\@pnumwidth</code> 2391
	2009, 2012, 2108		.. 2030, 2031, 2036	<code>\@todonotes@drawMarginNote</code> 2387, 2390
<code>\@highpenalty</code>	2027, 2053	<code>\@restonecolfalse</code> 2382
<code>\@idxitem</code> 2229	 2213,	<code>\@todonotes@drawMarginNoteWithLine</code> 2382
<code>\@ifpackageloaded</code>	..		2861, 2881, 2900	 2382
 1171,	<code>\@restonecoltrue</code>	..	<code>\@topnum</code>	1879, 1937, 2071
	1635, 1667,	 2215,		
	1718, 2184,		2859, 2879, 2898		
	2381, 2990, 2992	<code>\@roman</code>	417, 429, 446,		
<code>\@ifpackagewith</code>	.. 2164		461, 479, 494,	<code>\sqcup</code>	.. 703, 1997, 2284, 2286
<code>\@ifstar</code> 2925		510, 522, 537, 549		
<code>\@isbn</code> 1770	<code>\@standardmaketitle</code>	A	
<code>\@issn</code>	.. 1771, 1776, 1777		... 1931, 1933,	<code>\abstractname</code>	.. 2399,
<code>\@issue</code>	1988, 1989, 2000		1938, 1945, 1950		2403, 2415,

2422, 2426, 2433	\c@subsection 1577, 2154	\cleardoublepage ..
\addfontfeature ...	\c@subsubsection 2133, 2244,
.. 1419, 1421, 1423 1579, 2156	2253, 2449,
\addpenalty	\c@tocdepth	2457, 2987, 2988
2027 2026	\clearpage
\addtolength 2514, 2515	\captionsetup 2149, 2230, 2500
\alph 679, 681,	\col@number
\and	682, 684, 685, 687	.. 1872, 1930, 2064
1891, 1949, 2088	\Cauthor ... 1702, 1709	\collectioneditor ..
\appendicesname ...	\cc 2005, 2007
..... 2231, 2232	\Ccirclecolor 1706	\collectiontitle ..
\appendix .. 2264, 2269	\Ceditor ... 1703, 1712 2002, 2004
\appendixname 2272	\Cfoot	\colophon
\appendixpage 2233	\Cfootcolor . 1708, 1716	2434
\arabic	\chapfont	\columnsep
411, 565	2228
423, 438, 439,	\chapnumfont	\columnseprule ... 2227
453, 454, 471,	\chapter	\contentsmargin .. 2565
472, 486, 487,	1435,	\contentsname
504, 516, 531,	1441, 1534,	... 2816, 2817,
543, 617, 624, 631	1535, 1538,	2863, 2865, 2866
\artcolophon	1539, 1542,	\contentspage
2458	1543, 1546,	... 2243, 2752,
\AtBeginDocument 808,	1547, 1550,	2765, 2774,
1170, 1190,	1551, 1554,	2783, 2790,
1362, 1634,	1555, 1557,	2797, 2804, 2811
1666, 1717,	1559, 1567,	\copyright
2090, 2163,	1568, 1570,	2440
2278, 2356,	1669, 1672,	\Cpagecolor . 1705, 1714
2380, 2513,	1675, 1679,	\crop
2530, 2566,	1683, 1686,	808, 1161
2700, 2991, 2993	2863, 2883,	\csname . 1782, 2011,
\author 1793, 2022, 2086	2902, 2948, 2960	2103, 2514, 2515
B	\chapterintro . 2918,	\Csubtitle .. 1701, 1711
\backmatter	2920, 2922, 2925	\Ctextcolor . 1707, 1715
.. 2981, 2982, 2984	\chapterintroname ..	\Ctitle 1700, 1710
\baselineskip . 1416, 2930, 2931	D
1448, 1733, 1748	\chaptermark	\date ... 1834, 1861,
\bibname	2283	1890, 1948, 2087
1668,	\chaptertitlename . 2284	\DeclareFontFamily .
1674, 1682, 2948	\ClassError 1370, 1384, 1398
\bookcolophon 2450	... 1173, 1567,	\DeclareFontShape ..
C	1760, 2042, 1371–
\c@chapter	2358, 2503,	1378, 1380–
2273	2519, 2919,	1382, 1385–
\c@footnote ... 1800,	2971, 2976, 2981	1392, 1394–
1866, 1924,	\ClassWarningNoLine	1396, 1399–
1998, 2058, 2364 1, 57, 59,	1405, 1407–1409
\c@paragraph 1581, 2158	61, 63, 65, 67,	\DeclareRobustCommand
\c@section	85, 812, 1193, 100–103,
.. 1575, 2152, 2267	1201, 1228,	114–117, 129–
\c@subparagraph ...	1271, 1784,	132, 145–148,
..... 1583, 2160	1788, 1792,	
	2013, 2017, 2021	

161–164, 177–			
180, 193–196,			
209–212, 229,			
232, 235, 239,			
243, 247, 253,			
256, 259, 263,			
267, 271, 277,			
280, 283, 287,			
291, 295, 300,			
303, 306, 311,			
314, 317, 1364,			
1418, 1420,			
1422, 1425,			
1427, 1429, 2934			
<code>\DeclareTextFontCommand</code>			
..... 1367			
<code>\defbibheading</code>			
1636,			
1639, 1642,			
1646, 1650,			
1653, 1656,			
1658, 1661,			
1668, 1671,			
1674, 1678,			
1682, 1685,			
1688, 1691, 1695			
<code>\define@choicekey</code>			
72,			
83, 96, 225, 249,			
273, 297, 308,			
319, 327, 335,			
343, 351, 360,			
368, 376, 384,			
392, 400, 408,			
435, 468, 501,			
528, 555, 573,			
595, 614, 638,			
645, 652, 668,			
676, 690, 696,			
712, 742, 757,			
767, 780, 787,			
793, 799, 810,			
820, 827, 1058,			
1067, 1073, 1082			
<code>\definecolor</code>			
1146, 1147			
<code>\disable@keys</code>			
.....			
75, 1014, 1032, 1051			
<code>\doi</code>			
..... 1773, 1775			
<code>\dotfill</code>			
..... 2035			
<code>\doublehyphendemerits</code>			
..... 2374, 2375			
<code>\draw</code>			
..... 1722, 1725			
	E		
	<code>\emph</code>	.. 1999, 2493, 2994	1258, 1261,
	<code>\encodingdefault</code>	. 1366	1295, 1298,
	<code>\endcsname</code>	1782, 2011,	1301, 1325,
		2103, 2514, 2515	1328, 1331,
	<code>\endlist</code>	2338, 2344,	1770, 1773,
		2354, 2956, 2969	1776, 1780,
	<code>\endquotation</code>	2407, 2430	1979, 1982,
	<code>\ensuremath</code> 2357	1985, 1988,
	<code>\ExecuteOptionsX</code>	. 1090	1991, 1994,
	<code>\exhyphenpenalty</code>	. 2373	2001, 2002,
			2005, 2009,
			2267, 2272, 2273
	F		
	<code>\f@series</code> 1365	<code>\global</code> . 1830–1835,
	<code>\f@shape</code> 1365	1857–1862,
	<code>\fancyfoot</code>	2293, 2295,	1879, 1885–
		2298, 2303, 2307	1891, 1937,
	<code>\fancyhead</code> 2300,	1943–1949,
		2301, 2309–2311	2071, 2078–
	<code>\fancyhf</code> 2290,	2088, 2119, 2134
		2292, 2297, 2306	<code>\greektext</code> .. 1364, 1367
	<code>\fancypagestyle</code>	2290,	
		2291, 2296, 2305	H
	<code>\finalcolophon</code>	... 2463	<code>\hb@xt@</code> 1869,
	<code>\finalhyphendemerits</code> 2375	1927, 2036, 2061
	<code>\fontencoding</code> 1190	<code>\headbreak</code> 2934
	<code>\footnote</code>	1799, 1839,	<code>\headbreakfalse</code> .. 2933
		1897, 1955, 2094	<code>\headbreaktrue</code> ... 2941
	<code>\footnotemark</code> 1997	<code>\headrulewidth</code> ... 2280
	<code>\footnoterule</code>	<code>\hemph</code> 2994
		.. 1798, 1838, 2281	<code>\hfill</code> 2039, 2049
	<code>\footnotesize</code>	. 648,	<code>\hss</code> 1870, 1928, 2036, 2062
		703, 1797, 1837,	<code>\Huge</code> 1738
		2294, 2295,	<code>\Hy@raisedlink</code> ... 2101
		2299–2301,	<code>\hyper@anchorend</code> . 2102
		2303, 2308–	<code>\hyper@anchorstart</code> 2102
		2311, 2371, 2488	<code>\hyphenpenalty</code> ... 2373
	<code>\footnotetext</code> 1998	
	<code>\frenchspacing</code>	... 3000	I
	<code>\frontispiece</code> 2136	<code>\if@mainmatter</code> ... 2325
	<code>\frontmatter</code>	.. 2971,	<code>\if@restonecol</code> 2230,
		2972, 2974, 2987	2875, 2894, 2914
	<code>\FSPLcolophon</code>	. 2473,	<code>\if@tempswa</code> 2928
		2502, 2504, 2506	<code>\if@titlepage</code> 1795, 2409
	<code>\fulljournal</code> 1999	<code>\if@twocolumn</code>
			... 1871, 1929,
			2063, 2212,
			2398, 2407,
			2421, 2430,
			2858, 2878, 2897
	G		<code>\ifheadbreak</code> 2933, 2935
	<code>\gdef</code>	... 1212, 1215,	
		1218, 1255,	

<code>\ifLuaTeX</code> 1152	<code>\ifsufteresi@mathextended</code>	<code>\ifsufteresi@supercompactaureo</code>
<code>\ifPDFTeX</code> 1169,	23, 1241, 1283, 1312	33, 1553, 2177, 2201
1344, 1417, 2995	<code>\ifsufteresi@mathminimal</code>	<code>\ifsufteresi@twocolumnlof</code>
<code>\ifsufteresi@artemisia</code>	22, 1246, 1288, 1317	. . . 52, 2833, 2887
19, 1214, 1257,	<code>\ifsufteresi@nofont</code> . .	<code>\ifsufteresi@twocolumnlot</code>
1297, 1327, 1346 12, 1191	. . . 53, 2847, 2907
<code>\ifsufteresi@article</code> .	<code>\ifsufteresi@numparchap</code>	<code>\ifsufteresi@twocolumntoc</code>
. . . . 26, 1456,	. . . 39, 1434, 1447	. . . 51, 2819, 2868
1469, 1566,	<code>\ifsufteresi@numparpart</code>	<code>\ifxheadbreak</code> 2936–2938
1633, 1808,	. . . 38, 1590, 1604	<code>\ignorespaces</code> 2337, 2343
1902, 2217,	<code>\ifsufteresi@numparsec</code>	<code>\index</code> 2448
2263, 2285, 40, 1453	<code>\indexname</code>
2315, 2636,	<code>\ifsufteresi@numparsubsec</code>	. . 2218, 2220, 2222
2709, 2759, 41, 1480	<code>\isbn</code> 1770,
2764, 2813,	<code>\ifsufteresi@numparsubsubsec</code>	1772, 1776, 1778
2917, 2944, 2970 42, 1505	<code>\issue</code> 1988, 1990
<code>\ifsufteresi@authortitle</code>	<code>\ifsufteresi@pagelefttoc</code>	<code>\issuename</code> 2001
. 27, 2316	. . . 50, 2041, 2564	<code>\item</code> 2229,
<code>\ifsufteresi@bodoni</code> . .	<code>\ifsufteresi@palatino</code>	2335, 2342, 2352
20, 1211, 1254, 17, 1236	<code>\itemindent</code>
1294, 1324, 1352	<code>\ifsufteresi@partpage</code>	. . . 2331, 2348,
<code>\ifsufteresi@cbgreek</code> 48, 1584	2349, 2951, 2963
. . . . 21, 1220,	<code>\ifsufteresi@periodical</code>	<code>\itemsep</code> 2347
1263, 1355, 1368	28, 1533, 2165, 2185	<code>\itlabel</code> . . . 2958, 2968
<code>\ifsufteresi@centerheader</code>	<code>\ifsufteresi@periodicalaureo</code>	<code>\itshape</code> 323,
. 24, 2327	29, 1537, 2180, 2205	331, 339, 347,
<code>\ifsufteresi@cochineal</code>	<code>\ifsufteresi@porson</code> . .	355, 364, 372,
. 15, 1307	18, 1217, 1260,	380, 388, 396,
<code>\ifsufteresi@collection</code>	1300, 1330, 1349	404, 602, 603,
. . . 55, 1969, 2396	<code>\ifsufteresi@raggedtoc</code>	613, 1077, 1086,
<code>\ifsufteresi@compact</code> 37, 2038	1623, 2370, 2958
30, 1541, 2168, 2189	<code>\ifsufteresi@reverseauthortitle</code>	J
<code>\ifsufteresi@compactaureo</code>	. . . 54, 2096, 2111	<code>\journalname</code> 1979, 1981
31, 1545, 2174, 2197	<code>\ifsufteresi@screen</code> . .	<code>\journalnumber</code> 1985, 1987
<code>\ifsufteresi@compatibility</code> 34, 1160	<code>\journalvolume</code> 1982, 1984
. 11, 1206	<code>\ifsufteresi@screencentered</code>	<code>\journalwebsite</code> . . .
<code>\ifsufteresi@dottedtoc</code> 35, 1162 1994, 1996
. 36, 2035	<code>\ifsufteresi@smallcapschap</code>	<code>\journalyear</code> 1991, 1993
<code>\ifsufteresi@draftdate</code>	. . . 44, 1805, 1899	L
46, 2294, 2299, 2308	<code>\ifsufteresi@smallcapspart</code>	<code>\l@title</code> 2025
<code>\ifsufteresi@fewfootnotes</code> 43	<code>\label</code> 2099,
. 47, 2355	<code>\ifsufteresi@smallcapssec</code>	2122, 2124, 2132
<code>\ifsufteresi@FSPL</code> 45, 1809, 1903	<code>\labelitemi</code> 611
. . . 49, 1156, 2472	<code>\ifsufteresi@standard</code>	<code>\labelsep</code> 2962
<code>\ifsufteresi@greekfont</code> 14, 1198	<code>\labelwidth</code> . 2953, 2965
13, 1192, 1200,	<code>\ifsufteresi@sufplain</code>	<code>\LARGE</code> . 1843, 1956, 2250
1210, 1253, 1345 25, 2328	<code>\Large</code> . . . 100, 114, 1743
<code>\ifsufteresi@libertine</code>	<code>\ifsufteresi@supercompact</code>	<code>\LaTeX</code> . 2444, 2492, 2493
. 16, 1279	32, 1549, 2171, 2193	

<code>\leftmargin</code>	<code>\markright</code>	759, 767, 769,
. . . 2332, 2340,	1655, 1684,	780, 782, 787,
2350, 2351,	1687, 1690,	788, 793, 795,
2952, 2964, 2965	1694, 2009, 2286	799, 801, 810,
<code>\leftmark</code>	Miede, André	815, 820, 822,
<code>\leftskip</code> 659, 2032, 2033		827, 835, 1058,
<code>\lineskip</code> 1819, 1846,	N	1060, 1067,
1913, 1959, 2372	<code>\newcounter</code>	1069, 1073,
<code>\lineskiplimit</code> . . . 2372	. . 1970–1973, 1975	1074, 1082, 1083
<code>\list</code> . . . 2330, 2340,	<code>\newlength</code>	O
2347, 2950, 2961	1432, 2510,	<code>\oldmarginpar</code>
<code>\listfigurename</code> 2830,	2528, 2531–	. . 2376, 2377, 2386
2831, 2883–2885	2538, 2567–	<code>\onecolumn</code>
<code>\listoffigures</code> 2828, 2877	2582, 2701–2708	2230,
<code>\listoftables</code> 2842, 2896	<code>\newline</code> . . . 2107, 2937	2859, 2879, 2898
<code>\listparindent</code> 2330,	<code>\nobreak</code> 2034, 2036,	<code>\origtableofcontents</code>
2331, 2349, 2966	2039, 2049, 2110 2939, 2942
<code>\listtablename</code>	<code>\node</code>	P
. . . 2844, 2845,	1724, 1727, 1752, 2384	<code>\p@</code> 1802, 1841, 2028,
2902, 2904, 2905	<code>\noindent</code>	2226, 2228, 2334
<code>\lfnfscale</code> . 1221, 1264	1926, 2060,	<code>\pagestyle</code>
<code>\LoadClass</code>	2337, 2440,	. . 2279, 2326–2328
. 71	2444, 2454,	<code>\paragraph</code> . . 1619, 1625
<code>\losname</code>	2456, 2462,	<code>\parfillskip</code>
1646, 1653,	2477, 2480, 2492	2031
1671, 1678,	<code>\nr</code>	<code>\parsep</code> 2334, 2954, 2967
1685, 2957, 2960 72, 74,	<code>\parskip</code> 2226, 2954, 2967
<code>\lowercase</code>	83, 88, 96, 99,	<code>\part</code> 1587, 1588, 1591,
. 559	225, 227, 249,	1597, 1605, 1611
M	251, 273, 275,	<code>\partfont</code>
<code>\mainmatter</code> . . . 2976,	297, 298, 308, 564
2977, 2979, 2988	309, 319, 320,	<code>\partname</code>
<code>\makecover</code>	327, 328, 335,	1599, 1607,
1760, 1762, 1766	336, 343, 344,	1613, 2256, 2558
<code>\makelabel</code> . . 2955, 2968	351, 352, 360,	<code>\PassOptionsToClass</code> 68
<code>\MakeLowercase</code>	361, 368, 369,	<code>\penalty</code>
. 558	376, 377, 384, 2053
<code>\maketitle</code>	385, 392, 393,	<code>\phantomsection</code> . . 2927
1796,	400, 401, 408,	Poll, Philipp H.
1831, 1858,	410, 435, 437, 4
1864, 1886,	468, 470, 501,	<code>\protect</code> 1784, 1788,
1944, 2056, 2079	503, 528, 530,	1792, 1998,
<code>\Margini</code>	555, 557, 573,	2013, 2017,
. 2166,	576, 595, 597,	2021, 2284, 2286
2169, 2172,	614, 616, 638,	<code>\protected@xdef</code> . . 1997
2175, 2178,	640, 645, 647,	Q
2181, 2186,	652, 654, 668,	<code>\quotation</code> . . 2405, 2428
2190, 2194,	670, 676, 678,	R
2198, 2202, 2206	690, 692, 696,	<code>\raggedleft</code>
<code>\marginpar</code> 694, 2376, 2377	698, 712, 714, 2378
<code>\markboth</code> 1638, 1641,	742, 744, 757,	<code>\raggedright</code> 2224, 2379
1645, 1649,		
1670, 1673,		
1677, 1681, 2284		

<code>\refname</code>	1636, 1642, 1650, 1656, 1658, 1661, 1688, 1691, 1695, 2945, 2946	1516, 1528, 1588, 1625, 1632	<code>\subsubsection</code>	1506, 1511, 1516, 1518, 1523, 1528
<code>\refstepcounter</code>	...	<code>\setlength</code>	...	783, 785, 1416, 1448, 1450, 2511, 2529, 2539, 2541, 2543, 2545, 2547, 2549, 2551, 2553, 2583, 2585, 2587, 2589, 2591, 2593, 2595, 2597, 2599, 2601, 2603, 2605, 2607, 2609, 2611, 2613, 2710, 2712, 2714, 2716, 2718, 2720, 2722, 2725, 2727, 2729, 2731, 2733, 2735, 2737, 2739, 2951– 2954, 2962–2967
<code>\renewenvironment</code>	...	<code>\sfdefault</code>	...	1209
<code>\Rientro</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\rightmargin</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\rightmark</code>	...	<code>\sfdefault</code>	...	1209
<code>\rightskip</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\rlap</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\rmdefault</code>	...	<code>\sfdefault</code>	...	1209
<code>\Roman</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\roman</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
S				
<code>\secfont</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\secnumfont</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\section</code>	...	<code>\sfdefault</code>	...	1209
<code>\sectionmark</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\sectionsep</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\subsubsection</code>	...	<code>\sfdefault</code>	...	1209
<code>\SUF@addto@tochang@chap</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\SUF@addto@tochang@fig</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\SUF@addto@tochang@par</code>	...	<code>\sfdefault</code>	...	1209
<code>\SUF@addto@tochang@sec</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\SUF@addto@tochang@subpar</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\SUF@addto@tochang@subsec</code>	...	<code>\sfdefault</code>	...	1209
<code>\SUF@addto@tochang@subsubsec</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\SUF@addto@tochang@tab</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\SUF@ADJnumparchap</code>	...	<code>\sfdefault</code>	...	1209
<code>\SUF@appendices</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\SUF@appendixpage</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\SUF@authorfont@Switch</code>	...	<code>\sfdefault</code>	...	1209
<code>\SUF@CHAP@StyleSwitch</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\SUF@chaptersize</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636
<code>\subsubsectionfont</code>	...	<code>\sfdefault</code>	...	1209
<code>\subsubsecfont</code>	...	<code>\small</code>	...	650, 1797, 1819, 1824, 1837, 1913, 1918, 2401, 2424, 2444, 2456, 2462, 2468, 2480
<code>\subsubsecnumfont</code>	...	<code>\setlist</code>	...	612, 613, 617–622, 624–629, 631–636

\SUF@chaptitlerule .	\SUF@label@par 2535,	\SUF@LR@MarkSwitch .
..... 700,	2547, 2550,	... 2302, 2312,
704, 708, 2752, 2764	2592, 2608,	2317, 2319, 2322
\SUF@default@CHAPTER	2670, 2717,	\SUF@lr@PARTSwitch .
..... 1433, 1531	2734, 2787–2789 228,
\SUF@default@SECTIONS	\SUF@label@part 2257,	231, 234, 237,
..... 1452, 1532	2531, 2539, 2559	241, 245, 1592,
\SUF@dotchap .. 440,	\SUF@label@sec 2532,	1598, 1606, 1612
445, 450, 455,	2541, 2544,	\SUF@lr@SECSwitch ..
460, 465, 1437, 1443	2552, 2554, 276,
\SUF@dotpart .. 412,	2586, 2602,	279, 282, 285,
416, 420, 424,	2612, 2614,	289, 293, 1455,
428, 432, 1593,	2635, 2728,	1461, 1468, 1474
1599, 1607, 1613	2738, 2740,	\SUF@lr@SUBSECSwitch
\SUF@dotsec ... 473,	2757, 2758, 2762 299,
478, 483, 488,	\SUF@label@subpar ..	302, 305, 1482,
493, 498, 1457,	... 2536, 2549,	1487, 1494, 1499
1462, 1470, 1475	2594, 2610,	\SUF@lr@SUBSUBSECSwitch
\SUF@dotsubsec 505,	2679, 2719, 310,
509, 513, 517,	2736, 2794–2796	313, 316, 1507,
521, 525, 1488, 1500	\SUF@label@subsec ..	1512, 1519, 1524
\SUF@dotsubsubsec 2533, 2543,	\SUF@mpsetup
..... 532,	2546, 2588,	.. 2369, 2378, 2379
536, 540, 544,	2604, 2648,	\SUF@PART@StyleSwitch
548, 552, 1513, 1525	2713, 2730, 321, 323,
\SUF@fchapterintroname	2769, 2770, 2772	325, 564, 1593,
..... 2928–2930	\SUF@label@subsubsec	1595, 1599,
\SUF@greekfamily 2534, 2545,	1601, 1607,
..... 1347,	2548, 2590,	1609, 1613, 1615
1350, 1353,	2606, 2659,	\SUF@quotation@size
1356, 1363, 1365	2715, 2732, 648, 650,
\SUF@HEAD@thechapter	2778, 2779, 2781	2336, 2343, 2353
. 439, 444, 449,	\SUF@label@tab	\SUF@quote@style ..
454, 459, 464, 2284	... 2538, 2553,	641, 643, 2333, 2341
\SUF@HEAD@thesection	2688, 2696, 2809	\SUF@Rheadstyle ...
. 472, 477, 482,	\SUF@leftmark 577, 581, 587,
487, 492, 497, 2286 578, 582,	591, 598, 602, 606
\SUF@headingsmallcaps	588, 592, 2317, 2322	\SUF@rightmark 577,
606–608, 1422, 1429	\SUF@leftrightmark .	581, 587, 591,
\SUF@label@chap 578, 582, 2324	2300, 2310, 2319
... 2510, 2511,	\SUF@Lheadstyle ...	\SUF@SEC@StyleSwitch
2540, 2542,	. 578, 582, 588, 337, 339,
2584, 2612,	592, 599, 603, 607	341, 566, 1459,
2614, 2622,	\SUF@lr@CHAPSwitch .	1464, 1472, 1477
2711, 2721, 252,	\SUF@sectionsize ..
2723, 2726,	255, 258, 261,	. 101, 115, 130,
2738, 2740, 2747	265, 269, 1436, 1442	146, 162, 178,
\SUF@label@fig	\SUF@lr@coll@titleSwitch	194, 210, 1455,
.. 2537, 2551, 2802 1061,	1461, 1468, 1474
	1063, 1065, 2093	

\SUF@SUBSEC@StyleSwitch	2783, 2790,	2738, 2740,
.... 345, 347,	2797, 2804, 2811	2744, 2746, 2750
349, 567, 1485,	\SUF@titlesmallcaps	\SUF@tocindent@fig .
1490, 1497, 1502	. 325, 333, 341,	... 2707, 2720,
\SUF@subsectionsize	349, 357, 1079,	2737, 2799, 2801
. 102, 116, 131,	1088, 1420,	\SUF@tocindent@par .
147, 163, 179,	1427, 1806, 2705,
195, 211, 1482,	1810, 1900, 1904	2716, 2719,
1487, 1494,	\SUF@tocAUT@font ..	2733, 2736, 2785
1499, 1507,	394, 396, 398, 2107	\SUF@tocindent@sec .
1512, 1519, 1524	\SUF@tocCHAP@font 2702,
\SUF@SUBSUBSEC@StyleSwitch 362,	2710, 2713,
.... 353, 355,	364, 366, 2624,	2727, 2730, 2755
357, 568, 1510,	2627, 2749, 2751	\SUF@tocindent@subpar
1515, 1522, 1527	\SUF@tochang .. 2528, 2706,
\SUF@subsectionsize	2529, 2584, 2600	2718, 2735, 2792
..... 103,	\SUF@tochang@chap ..	\SUF@tocindent@subsec
117, 132, 148, 2567, 2703,
164, 180, 196, 212	2583, 2586,	2712, 2715,
\SUF@thechapter 438,	2596, 2598,	2729, 2732, 2767
443, 448, 453,	2617, 2619, 2625	\SUF@tocindent@subsubsec
458, 463, 569,	\SUF@tochang@fig 2704,
1437, 1443, 2273 2573,	2714, 2717,
\SUF@thepage	2595, 2684, 2686	2731, 2734, 2776
. 600, 604, 608,	\SUF@tochang@par ..	\SUF@tocindent@tab .
2295, 2303, 2309 2571,	... 2708, 2722,
\SUF@thepart .. 411,	2591, 2594,	2739, 2806, 2808
415, 419, 423,	2666, 2668, 2671	\SUF@toclabelnum 413,
427, 431, 1593,	\SUF@tochang@sec ..	417, 421, 425,
1599, 1607, 1613 2568,	429, 433, 441,
\SUF@thesection ...	2585, 2588,	446, 451, 456,
. 471, 476, 481,	2631, 2633, 2639	461, 466, 474,
486, 491, 496,	\SUF@tochang@subpar	479, 484, 489,
570, 1456, 1462,	... 2572, 2593,	494, 499, 506,
1469, 1475, 2267	2675, 2677, 2680	510, 514, 518,
\SUF@thesubsection .	\SUF@tochang@subsec	522, 526, 533,
.... 504, 508, 2569,	537, 541, 545,
512, 516, 520,	2587, 2590,	549, 553, 2258,
524, 571, 1488, 1500	2644, 2646, 2650	2560, 2623,
\SUF@thesubsubsection	\SUF@tochang@subsubsec	2636, 2747, 2759
.... 531, 535, 2570,	\SUF@tocSEC@font 370,
539, 543, 547,	2589, 2592,	372, 374, 2638,
551, 572, 1513, 1525	2655, 2657, 2661	2641, 2761, 2763
\SUF@titlefont@Switch	\SUF@tochang@tab ..	\SUF@tocSUBSEC@font
... 1075, 1077, 2574, 378,
1079, 2097, 2114	2597, 2692, 2694	380, 382, 2649,
\SUF@titlerule	\SUF@tocindent@chap	2652, 2771, 2773
.... 699, 703, 2701,	\SUF@tocSUBSUBSEC@font
707, 2765, 2774,	2725, 2728, 386,

388, 390, 2660, 2663, 2780, 2782	\suftesi@FSPLtrue ..	\suftesi@standardtrue
\SUF@tocTIT@font 1005, 1022, 1040 753
402, 404, 406, 2108	\suftesi@greekfontfalse	\suftesi@sufplaintrue
\SUF@TOCtitlesmallcaps 770, 1195, 584
..... 366,	1196, 1203, 1204	\suftesi@supercompactaureottrue
374, 382, 390,	\suftesi@greekfonttrue 192
398, 406, 1418, 1425	. 772, 774, 776, 778	\suftesi@supercompacttrue
\SUF@versionstring .	\suftesi@libertinettrue 176
..... 2282, 749	\suftesi@twocolumnloftrue
2294, 2299, 2308	\suftesi@MakeTextLowercase	. 718, 725, 732, 737
\SUFfontscale .. 1212,	558, 561, 1421,	\suftesi@twocolumnlottrue
1215, 1218,	1423, 1428, 1430	. 721, 729, 733, 738
1255, 1258,	\suftesi@MakeTextTOCLowercase	\suftesi@twocolumntoctrue
1261, 1295,	559, 562, 1419, 1426	. 715, 724, 728, 736
1298, 1301,	\suftesi@mathextendedfalse	
1325, 1328, 761	T
1331, 1371-	\suftesi@mathextendedtrue	\tableofcontents ..
1378, 1380- 765 2814,
1382, 1385-	\suftesi@mathminimalfalse	2857, 2939, 2940
1392, 1394- 760	\texorpdfstring .. 2107
1396, 1399-	\suftesi@mathminimaltrue	\textbullet 611
1405, 1407-1409 763	\textgreek 1367
\suftesi@artemisiatrue	\suftesi@nofonttrue 745	\textls 1426, 1428, 1430
..... 772	\suftesi@numparchaptrue	\textnormal ... 1483,
\suftesi@articletrue 77 262, 266, 270	1488, 1495,
\suftesi@authortitletrue	\suftesi@numparparttrue	1500, 1508,
..... 586, 590 238, 242, 246	1513, 1520, 1525
\suftesi@bodonitrue 776	\suftesi@numparsectrue	\textsc 415,
\suftesi@cbgreektrue 286, 290, 294	427, 443, 444,
..... 778	\suftesi@pagelefttoctrue	458, 459, 476,
\suftesi@centerheadertrue 710	477, 491, 492,
..... 580, 593	\suftesi@palatinotrue	508, 520, 535, 547
\suftesi@cochinealtrue 751	\textsf 2447, 2494
..... 747	\suftesi@partpagetrue	\textsuperscript .. 666
\suftesi@collectiontrue 789	\texttt 2282
..... 80	\suftesi@periodicalaureottrue	\thanks 587, 588, 591,
\suftesi@compactaureottrue 208,	592, 1799, 1830,
..... 160	1004, 1021, 1039	1839, 1857,
\suftesi@compacttrue	\suftesi@periodicaltrue	1885, 1897,
..... 144 128	1943, 1955,
\suftesi@compatibilitytrue	\suftesi@porsontrue 774	1997, 2078,
..... 755	\suftesi@raggedtoctrue	2089, 2094, 2105
\suftesi@dottedtoctrue 706	\thearticle
..... 702	\suftesi@reverseauthortitletrue	... 2099, 2100,
\suftesi@draftdatetrue 1070	\thecontentslabel ..
..... 796	\suftesi@screencenteredtrue 2258,
\suftesi@fewfootnotetrue 805	2560, 2623,
..... 671	\suftesi@screentrue	2637, 2648,
 802, 804	2659, 2670,

2679, 2688,	2791, 2798, 2805	343, 351, 360,
2696, 2747,	<code>\titleformat</code> .. 1435,	368, 376, 384,
2760, 2770,	1441, 1454,	392, 400, 408,
2779, 2788,	1460, 1467,	435, 468, 501,
2795, 2802, 2809	1473, 1481,	528, 555, 573,
<code>\thecontentspage</code> ..	1486, 1493,	595, 614, 638,
..... 2620,	1498, 1506,	645, 652, 668,
2626, 2634,	1511, 1518,	676, 690, 696,
2640, 2647,	1523, 1591,	712, 742, 757,
2651, 2658,	1597, 1605,	767, 780, 787,
2662, 2669,	1611, 1619, 1626	793, 799, 810,
2672, 2678,	<code>\titlerule</code>	820, 827, 1058,
2681, 2687, 2695	.. 699, 700, 703, 704	1067, 1073, 1082
<code>\thefootnote</code>	<code>\titlespacing</code>	<code>\version@string</code> ...
... 1800, 1866,	... 1465, 1478, 2276, 2282
1924, 2058, 2364	1491, 1503,	<code>\versionstring</code> 2276, 2277
<code>\thepage</code> .. 600, 604, 608	1516, 1528,	
<code>\theparagraph</code>	1534, 1535,	X
... 1580, 1583,	1538, 1539,	<code>\xfootnote</code>
1621, 2157, 2160	1542, 1543, 2366
<code>\thesection</code> ... 1457,	1546, 1547,	<code>\xheadbreak</code> 229, 232,
1470, 1574,	1550, 1551,	235, 239, 243,
1577, 2151, 2154	1554, 1555,	247, 253, 256,
<code>\thesubparagraph</code> ..	1557, 1559,	259, 263, 267,
.. 1582, 1628, 2159	1588, 1625, 1632	271, 277, 280,
<code>\thesubsection</code> 1483,	<code>\toclabelspace</code>	283, 287, 291,
1495, 1576,	.. 2518, 2521, 2525	295, 300, 303,
1579, 2153, 2156	<code>\toclabelwidth</code>	306, 311, 314, 317
<code>\thesubsubsection</code> 2512, 2522, 2526	<code>\xheadbreakBB</code> . 232,
..... 1508,	<code>\today</code>	235, 243, 247,
1520, 1578, 2282	256, 259, 267,
1581, 2155, 2158	<code>\tolerance</code>	271, 280, 283,
<code>\title</code>	<code>\twocolumn</code> 1875,	291, 295, 303,
1780–	1933, 2067,	306, 314, 317, 2938
1782, 1785,	2218, 2220,	<code>\xheadbreakfalse</code> ..
1789, 2008,	2875, 2894, 2914	... 2300, 2301,
2010, 2011,	U	2310, 2311, 2941
2014, 2018, 2085	<code>\url</code>	<code>\xheadbreakNL</code>
<code>\titleclass</code> 1994 229, 239,
1587	<code>\usefont</code>	253, 263, 277,
<code>\titlecontents</code>	<code>\useosf</code> 1251, 1293, 1322	287, 300, 311, 2937
... 2236, 2254,	<code>\useproportional</code> ..	<code>\xheadbreaktrue</code> .. 2936
2556, 2616, 1252, 1323	<code>\XKV@classoptionslist</code>
2630, 2643,	V 1144
2654, 2665,	<code>\val</code>	<code>\XKV@useoption</code> 1134–1143
2674, 2683, 72,	Y
2691, 2743,	83, 96, 225, 249,	<code>\year</code>
2754, 2766,	273, 297, 308,	2440, 2473
2775, 2784,	319, 327, 335,	