

User's Guide to *suftesi*

A document class for typesetting theses, books and articles

v1.9a – 2014/02/11

Ivan Valbusa

Dipartimento di Filosofia, Pedagogia e Psicologia

Università degli Studi di Verona

ivan dot valbusa at univr dot it

Abstract

The standard document classes allow you to typeset beautiful documents but their layout is quite far from the stylistic requests of some humanists (mainly Italian). The *suftesi* class provides a set of “humanistic” page layouts, title styles and heading styles to typeset theses, books and articles. The styles are very simple and sober and also have the aim of finding an aesthetic harmony in its formal simplicity. They are largely inspired by some interesting readings, particularly Bringhurst (1992), Tschichold (1975) and Morison (1936).

Contents

1 Use		2	6.7 Text elements	19
2 Class features		3	6.7.1 Lists	19
2.1 Page layouts	3	6.7.2 Block quotations	20	
2.2 Font	3	6.7.3 Footnotes	20	
2.3 Frontispiece	4	6.7.4 Captions	21	
3 Options		6.7.5 Marginal notes	21	
3.1 Layout	5	6.7.6 Table of contents	21	
3.2 Fonts	5	6.8 Fonts	22	
3.3 Titles	5	6.8.1 Roman fonts	22	
3.4 Headings	6	6.8.2 Greek fonts	22	
3.5 Notes, lists, quotations	7	6.9 Other options	22	
3.6 Other options	7	6.9.1 \parindent	22	
3.7 Pre-defined styles	8	6.9.2 Part page	22	
4 New commands		6.9.3 Crop marks	22	
4.1 Printing the colophon	9	6.9.4 Draftdate	22	
4.2 Breaking titles	10	6.9.5 View mode	23	
4.3 Other commands	10	6.9.6 Titlepage	23	
5 The collection document structure		6.9.7 Pre-defined styles	23	
5.1 Options	11	6.10 Basic packages	28	
5.2 Commands	12	6.11 Greek fonts	28	
References		6.12 Page layout	29	
6 The Code		6.13 Section titles	29	
6.1 Document structure	13	6.14 Title page	35	
6.2 Page layout	14	6.15 The collection document structure	38	
6.3 Sections style	15	6.16 Frontispiece	40	
6.4 Sections font	17	6.17 Appendix	41	
6.5 Section numbers	17	6.18 Headings	42	
6.5.1 Part number style	17	6.19 Text elements	44	
6.5.2 Chapter number	18	6.19.1 Block Quotations	44	
6.5.3 Section number	18	6.19.2 Marginal notes	44	
6.6 Headers	19	6.19.3 Abstract	45	
6.6.1 Header style	19	6.19.4 Colophon	46	
6.6.2 Header font	19	6.20 Toc, lof, lot	47	
		6.20.1 'tocpageleft' toc	48	
		6.20.2 Default toc	50	
		6.21 New commands	53	
		6.22 Backward compatibility	54	
		6.23 Final settings	55	

Copyright notice

This package is author-maintained. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c (<http://www.ctan.org/tex-archive/macros/latex/base/lppl.txt>). In addition to the terms of this license the author requires an attribution notice (see section 4) like the following one:

*This work has been typeset with L^AT_EX, using the *suftesi* class by Ivan Valbusa.*

The most essence of this class is the set of styles it provides. For this reason **DO NOT MODIFY THE STYLES OF THIS CLASS WITH PACKAGES AND/OR COMMANDS WHICH CHANGE THE LAYOUT OF THE DOCUMENT. IF YOU DO NOT LIKE THESE STYLES, USE ANOTHER CLASS.** If you use *suftesi* in a document typeset with another class (for example *book*), remember to clean up the preamble from all the layout redefinitions.

A brief history

The *suftesi* class was born as a result of the course *Introduzione a L^AT_EX per le scienze umane* (*Introduction to L^AT_EX for human sciences*) which I held at the Graduate School of Human Sciences and Philosophy (**Scienze Umane e Filosofia**) of Verona University (Italy) in June 2010.¹ Originally thought as a class to typeset theses, during these years it has developed many new features and styles. Finally it has become the referential class of the Joint Project *Formal Style for PhD Theses with LaTe_X* of the University of Verona (Italy).²

Acknowledgements

I would like to thank Professors Paola Di Nicola, Director of the Graduate School, and Ugo Savardi who suggested to propose the course precisely to that School; Gilberto D'Arduini, Matteo Lanza and Antonio Rinaldi, who installed L^AT_EX on the computers used during the course; Catia Cordioli, for her help in the organization of the lessons; Corrado Ferreri, responsible of the E-Learning Center, who provided the T_EX Live 2009 DVDs.

Special thanks to Professors Enrico Gregorio, the Italian guru of T_EX, for the T_EXpert support and his priceless “magic formulas”, and Tommaso Gordini for his valuable advice in choosing and improving the class features during these years.

I would finally thank all the participants to the course who patiently resisted the four intensive lessons. This work is dedicated to them.

1 Use

The *suftesi* class is called as usual by

```
\documentclass[<options>]{suftesi}
```

You do not need to set the *a4paper* option as it is automatically loaded. All the options defined by the class are in the *<key>=<value>* format. In addition to these you can also use the options defined by the standard *book* class (on which *suftesi* is based) except those modifying the page dimensions (*a5paper*, *b5paper*, *legalpaper*, *executivepaper* and *landscape*), which are automatically disabled.

The document structure

With *suftesi* you can typeset book-style documents (i.e. with chapters) as well as article-style documents (i.e. without chapters). The kind of document is set by the *documentstructure* option which defaults to *book*. With the *collection* document structure you can also create collections of papers (see section 5).

```
\documentclass[documentstructure=book,<options>]{suftesi}
\documentclass[documentstructure=article,<options>]{suftesi}
\documentclass[documentstructure=collection,<options>]{suftesi}
```

¹<http://www.sdsuf.univr.it>. Some informations can be found on <http://profs.lettere.univr.it/valbusa/2010/06/01/introduzione-a-latex-per-le-scienze-umane/>

²<http://www.univr.it/main?ent=catdoc&id=3727&idDest=6&serv=127#1431>

Loaded packages

The class loads the following packages: `beramono`, `caption`, `color`, `enumitem`, `emptypage`, `extramarks`, `fancyhdr`, `fixltxhyph`, `fontenc`, `geometry`, `ifxetex`, `mathpazo`, `microtype`, `multicol`, `textcase`, `titlesec`, `titletoc`, `xkeyval`.

Use with X[\]TeX and Lua[\]TeX

The class can be used, of course, with the X[\]TeX and Lua[\]TeX engines. The only difference is that in this case the font options are turned off and the [\]TeX default font (Computer Modern) is loaded.

2 Class features

The `suftesi` class provides a large set of options to customize the style of page, titles, headings and other text elements (see section 3). The simplest way to get to know the class features is therefore to typeset one of the templates which you can find in the `/doc/latex/suftesi` folder in your [\]TeX distribution.

2.1 Page layouts

The class provides six page layouts which can be selected by the `pagelayout` option (see section 3.1). The standard layout (set by default) is aimed to typeset standard A4 documents, while the other five layouts are particularly suitable to typeset compact books and articles (see table 1 for details).

Layout:	Dimensions (mm)				Proportions			
	Text		Page		Margins		Text block	Page
	width	height	width	height	t/b	i/o		
standard	110	220	210	297	1 : 2	1 : 2	1 : 2	1 : $\sqrt{2}$
compact	110	165	160	240	2 : 3	2 : 3	2 : 3	2 : 3
compactaureo	118	191	160	240	2 : 3	2 : 3	5 : 8*	2 : 3
supercompact	100	150	140	210	2 : 3	2 : 3	2 : 3	2 : 3
supercompactaureo	108	175	140	210	1 : 1	1 : 1	5 : 8*	2 : 3
periodical	110	165	170	240	2 : 3	2 : 3	2 : 3	1 : $\sqrt{2}$
periodicalaureo	120	194	170	240	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$
elements (pt)	251	502	374	648	1 : 2	2 : 5	1 : 2	1 : $\sqrt{3}$

* $5 : 8 \approx 1 : 1,618$

Table 1: The layouts of `suftesi`

2.2 Font

The default serif font for body text is Palatino designed by Hermann Zapf and loaded through the `mathpazo` package, but you can simply choose the standard Latin Modern through the `defaultfont` option (see section 3). The sans serif font is Iwona designed by Janusz M. Nowacki and the monospaced typeface is Bera Mono, opportunely scaled to match Palatino. This choice has been inspired by *L'arte di scrivere con [\]TeX* (Pantieri and Gordini 2011). The Greek text is Artemisia by the Greek Font Society which is particularly suitable for Palatino, but with the `greekfont` option (see section 3) you can choose also Porson or CB Greek.³

Tò γὰρ καλὸν ἐν μεγέθει καὶ τάξει
ἐστίν. Il bello infatti sta nella
grandezza e nell'ordinata
disposizione delle parti.

(a) Artemisia

Tò γὰρ καλὸν ἐν μεγέθει καὶ τάξει
ἐστίν. Il bello infatti sta nella
grandezza e nell'ordinata
disposizione delle parti.

(b) Porson

Tò γὰρ καλὸν ἐν μεγέθει καὶ τάξει
ἐστίν. Il bello infatti sta nella
grandezza e nell'ordinata
disposizione delle parti.

(c) CB Greek

Comparison between (a) Artemisia, (b) Porson and (c) CBGreek greek font.

You can use other fonts as well. In this case remember to load the `defaultfont=standard` class option which turns off the default font settings.

³ The first code for the Porson font has been written by Enrico Gregorio. Claudio Beccari successively added the code to improve the scale factor when using this greek font in combination with Palatino.

2.3 Frontispiece

The class has an original frontispiece (see figure 1) now directly available loading the `frontespizio` package with the `suftesi` option (see [Gregorio 2009](#), version 1.4 or later):

```
\usepackage[suftesi]{frontespizio}
```

The `frontespizio` package produces a frontispiece in the standard Computer Modern typeface. If you prefer a consistent font remember to load the needed packages or commands in the `\Preambolo` command inside the `frontespizio` environment (see package documentation for details).




Figure 1: The frontispiece of `suftesi`.

3 Options

3.1 Layout

<code>documentstructure=book, article</code>	default: book
<code>book</code>	For typesetting texts with chapters.
<code>article</code>	For typesetting articles or short theses (that is without chapter division).
<code>collection</code>	For typesetting journals or collections of articles (see section 5).
<code>pagelayout=standard, periodical, compact, supercompact, elements</code>	default: standard
<code>standard</code>	Prints an A4 typeblock with a text area of 110cm × 220mm.
	With the following values the option prints the typeblock on a an A4 paper showing the crop marks which can be controlled by the <code>version</code> option.
<code>periodical</code>	Prints a typeblock of 17cm × 24cm with a text area of 11cm × 16,5cm.
<code>periodicalaureo</code>	The same of <code>periodical</code> but with a <i>golden ratio</i> text area of 120cm × 194mm.
<code>compact</code>	Prints a typeblock of 16cm × 24cm with a text area of 11cm × 16,5cm.
<code>compactaureo</code>	The same as <code>compact</code> but with a <i>golden ratio</i> text area of 11,8cm × 19,1cm.
<code>supercompact</code>	Prints a typeblock of 14cm × 21cm with a text area of 10cm × 15,5cm.
<code>supercompactaureo</code>	The same as <code>supercompact</code> but with a <i>golden ratio</i> text area of 10,8cm × 17,5cm.
<code>elements</code>	Prints a typeblock with the dimensions of <i>The Elements of Typographyc Style</i> by Robert Bringhurst. To reproduce the whole style of Bringhurst (1992) use <code>style=elements</code> option.

The details of this option are shown in table 1.

3.2 Fonts

The font options are available only with L^AT_EX. Using X^LT_EX the default font is the Computer Modern but you can change it through the `fontspec` or `mathspec` packages. With this engine I do suggest the Junicode or EB Garamond font families.

<code>defaultfont=palatino, standard</code>	default: palatino
<code>palatino</code>	Loads the Palatino font family.
<code>standard</code>	Loads the Latin Modern font family and the standard CB Greek font.
<code>greekfont=artemisia, porson, cbgreek</code>	default: artemisia
<code>artemisia</code>	Loads the Artemisia font.
<code>porson</code>	Loads the Porson font.
<code>cbgreek</code>	Loads the standard CB Greek font.

3.3 Titles

<code><level>font=roman, italic, smallcaps</code>	default: roman
<code>roman</code>	Prints the <code><level></code> title in roman.
<code>italic</code>	Prints the <code><level></code> title in <i>italic</i> .
<code>smallcaps</code>	Prints the <code><level></code> title in SMALL CAPS
	Where <code><level></code> can be part, chap, sec, subsec, subsubsec.
<code><level>style=left, center, right, parleft, parcenter, parright</code>	default: left
<code>left</code>	Aligns the <code><level></code> title on the left.
<code>center</code>	Centers the <code><level></code> title.
<code>right</code>	Aligns the <code><level></code> title on the right.

Where $\langle level \rangle$ can be part, chap, sec subsec, subsubsec.

- parleft** As left but with the title below the number.
- parcenter** As center but with the title below the number.
- parright** As right but with the title below the number.

Where $\langle level \rangle$ can be part, chap, sec.

- elements** Print a chapter number in the style of the *Elements of Typographic Style* by Robert Bringhurst.

Where $\langle level \rangle$ can be chap.

<level>numstyle=arabic, roman, Roman, dotarabic, dotroman, dotRoman default: Roman/arabic/arabic

- arabic** Arabic $\langle level \rangle$ number.
- roman** Small caps lowercase roman $\langle level \rangle$ number.
- Roman** Uppercase roman $\langle level \rangle$ number.
- dotarabic** As arabic but followed by a dot.
- dotroman** As roman but followed by a dot.
- dotRoman** As Roman but followed by a dot.

Where $\langle level \rangle$ can be part, chap, sec.

tocstyle=standard, dotted, ragged, leftpage default: standard

- standard** Prints a standard table of contents with page numbers on the right margin.
- dotted** As the previous one but with dotted lines.
- ragged** Aligns the table of contents on the left as suggested by Bringhurst (1992).
- leftpage** Prints a table of contents with page numbers on the left margin.

twocolcontents=toc, lof, lot, toclof, toclot, loflot, all default: all

This option activates the tocstyle=ragged option and disables the other values of tocstyle.

- toc** Prints the table of contents in two columns.
- lof** Prints the list of figures in two columns.
- lot** Prints the list of tables in two columns.
- toclof** Prints the table of contents and the list of figures in two columns.
- toclot** Prints the table of contents and the list of tables in two columns.
- loflot** Prints the list of figures and the list of tables in two columns.
- all** Prints the table of contents, the list of figures and the list of tables in two columns.

smallcapsstyle=low, upper default: low

This option is active only with $\langle level \rangle$ font=smallcaps options.

- low** Prints lowercase SMALL CAPITALS.
- upper** Prints SMALL CAPITALS without changing the case.

3.4 Headings

headerstyle=inner, center, plain, authortitleinner, authortitlecenter, elements default: inner

- inner** Prints the chapter title and the string “Chapter $\langle n \rangle$ ” in the inner side respectively of even and odd headers, and the page number in the outer side.
- center** Centers the header and footer and puts the page number in the center of the footer.
- plain** Prints no headers and puts the page number in the center of the footer.
- authortitleinner** Prints the author’s name on the even pages and the title on the odd ones. In order to use this option the \title and \author commands are required.
- authortitlecenter** As the previous one but with centered headers and footers.

elements Prints the chapter title and the section title in the margin respectively of even pages and odd pages. The page number is put in the outer side of the footer. This is the style loaded by the option `style=elements`.

headerfont=roman, italic, smallcaps default: roman

roman Prints the headers in roman.

italic Prints the headers in *italic*.

smallcaps Prints the headers in SMALL CAPS.

3.5 Notes, lists, quotations

quotestyle=center, right default: center

center Indents the block quotations on both the left and right margins.

right Indents the block quotations only on the left margin.

quotesize=footnotesize, small default: footnotesize

footnotesize Prints the block quotations in \footnotesize size.

small Prints the block quotations in \small size.

footnotestyle=bulged, hung, dotted, superscript default: bulged

bulged The footnote number protrudes beyond the left margin.

hung Indents the footnote text, so it will ‘hang’ under the first line of the text.

dotted The footnote number is aligned to the left margin and followed by a dot.

superscript Prints a superscript footnote number aligned to the left margin.

fewfootnotes=true, false default: false

Uses symbols instead of numbers to mark footnotes. It is active only in documents with three footnotes per page maximum. The symbol sequence is: *, **, ***. With more footnotes you should not need this option.

liststyle=bulged, aligned, indented default: bulged

bulged The item number or symbol protrudes beyond the left margin.

aligned Aligns the lists to the left margin.

indented Prints standard indented lists.

captionstyle=standard, sanserif, italic, smallcaps, elements default: standard

All these values print the caption in small size, changing the shape:

standard Prints the caption text and label in normal font.

sanserif Prints the caption text and label in sanserif.

italic Prints the caption text and label in *italic*.

smallcaps Prints only the caption label in SMALL CAPS.

elements An alias of sanserif.

3.6 Other options

version=screen, draft, final default: print

screen This option is provided to have a better view when you are typesetting and reading the PDF on the screen. It simply executes the `oneside` and `nocrop=false` options and redefines the `\crop` command so you do not need to comment it if it is used in the document.

draft Prints the output on a A4 paper, showing the crop marks. It is the same of `crop=true`.

final Prints the output on a A4 paper, hiding the crop marks.

<code>crop=true, false</code>	default: true
This option is actually useless. Use the <code>version</code> option instead.	
<code>true</code>	Prints the output on a A4 paper, showing the crop marks. It is the same of <code>version=draft</code> .
<code>false</code>	Prints a PDF with page dimensions according to the <code>pagelayout</code> option. It is similar to <code>version=screen</code> but it does not execute <code>oneside</code> option and it does not redefine <code>\crop</code> .
<code>parindent=compact, wide</code>	default: compact
Sets the indentation of the first line of each paragraph except those following a section title.	
<code>compact</code>	Sets indentation to 1em.
<code>wide</code>	Sets indentation to 1.5 em.
<code>marginpar=true, false</code>	default: true
<code>true</code>	Prints the marginal notes.
<code>false</code>	Hide the marginal notes.
<code>partpage=true, false</code>	default: false
► This option is active only with <code>documentstructure=article</code> .	
<code>true</code>	Prints the part title in a separate page as in <code>documentstructure=book</code>
<code>false</code>	Prints a part title similar to the one used in the standard <code>article</code> class.
<code>draftdate=true, false</code>	default: false
If true it prints the string “Version of <code>\date{<date>}</code> ” in the footer. It requires the <code>\date{<date>}</code> command.	

3.7 Pre-defined styles

These pre-defined styles are intended as shotrcuts to some groups of class options. Combining them with `dottedchap` and `romanchapnum` options you can get up to 120 variants.

<code>style=roman(1-6), italic(1-12), smallcaps(1-6), elements, sufelements</code>	default: roman1
<code>roman(1-6)</code>	The titles of chapters and headers are printed in roman. The number of the chapter is on the same line in styles 1-3 and above the title in styles 4-6. The title can be printed on the left (styles 1 and 4), in the center (styles 2 and 5) or on the right (styles 3 and 6).
<code>italic(1-12)</code>	The titles of chapters and headers are in <i>italic</i> . The section title is in <i>italic</i> in styles 1-6 and in <i>SMALL CAPS</i> in styles 7-12. There are three position for the title and two positions for the number as above.
<code>smallcaps(1-12)</code>	The titles of chapters and headers are in <i>SMALL CAPS</i> . The title of the section is in <i>italic</i> in styles 1-6 and in <i>SMALL CAPS</i> in styles 7-12. There are three position for the title and two positions for the chapter as above.
<code>elements</code>	Reproduces the style of the Italian edition of Bringhurst (1992) .
<code>sufelements</code>	Combines the <code>elements</code> -style sections with standard small caps headers. It can be used with all the page layouts.

The following styles are only meant to typeset a doctoral thesis respecting the features required by the Joint Project *Formal Style for PhD Theses with LaTeX* of the Verona University (Italy).⁴

`style=FSPLa, FSPLb, FSPLc`

<code>FSPLa</code>	Equal to: <code>pagelayout=periodical, style=roman1, footnotestyle=superscript, liststyle=indented. tocstyle=ragged.</code>
<code>FSPLb</code>	Equal to: <code>pagelayout=periodical, style=italic5, headerstyle=center, chapnumstyle=roman, secstyle=center, quotestyle=right, footnotestyle=hung, liststyle=indented. tocstyle=dotted.</code>
<code>FSPLc</code>	Equal to: <code>pagelayout=periodical, style=smallcaps5, secfont=smallcaps, headerstyle=center, footnotestyle=dotted, liststyle=indented, tocstyle=leftpage.</code>

⁴<http://www.univr.it/main?ent=catdoc&id=3727&idDest=6&serv=127#1431>.

4 New commands

4.1 Printing the colophon

As explained at the beginning of this documentation, in addition to the terms of the L^AT_EXProject Public License, suftesi requires a specific attribution notice. You can typeset the attribution notice manually or using one of these commands.

```
\colophon[⟨OS⟩]{⟨name and surname⟩}{⟨additional info⟩}
```

This command is provided only for Italian documents. It prints a page with a copyright notice and the colophon in the bottom of the page. For different languages use the \bookcolophon instead (see below).

If you don't need the copyright notice, leave the second argument of the command empty:

```
\colophon[⟨OS⟩]{}{⟨additional info⟩}
```

With the `article` option, you can use the \artcolophon command (see below) or the \thanks command:

```
\author{⟨Name Surname⟩}
\thanks{This work has been typeset with \LaTeX, using the \textsf{suftesi} class by Ivan Valbusa.}
```

```
\bookcolophon{⟨copyright notice⟩}{⟨attribution notice and other informations⟩}
```

Similar to \colophon but completely customizable. The first argument prints its content (usually the copyright notice) in the center of the page. The second one prints its content at the bottom. For example:

```
\bookcolophon{Copyright © 2007 by Ivan Valbusa}{%
This work has been typeset with \LaTeX, using the \sty{suftesi} class by Ivan Valbusa\index{Valbusa, Ivan}. The normal font is Palatino by Hermann Zapf. The sans serif font is Iwona by Janusz M. Nowacki.}
```

```
\artcolophon{⟨copyright notice, attribution and other informations⟩}
```

This command only has one argument. It simply prints its content at the bottom of the page.

Here is an example:

```
\artcolophon{%
This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License. To view a copy of this license, visit
```

```
\begin{center}
\texttt{http://creativecommons.org/licenses/by-nc-nd/3.0/}
\end{center}
```

or send a letter to Creative Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.\[tex]

Typeset with \LaTeX, using the \sty{suftesi} class by Ivan Valbusa.}

```
\finalcolophon{⟨colophon content⟩}
```

The same as \artcolophon, but centering its content at the top of the page. It is aimed at typesetting a classical *colophon* at the end of the work.

```
\FSPLcolophon
```

To typeset the colophon in the FSPL style, according to the Joint Project *Formal Style for PhD Theses with L^AT_EX* of the Verona University (Italy) (See section 3.7).

4.2 Breaking titles in text body, headers and table of contents

\headbreak

A manual break which is active for the table of contents but not in the text or in the headers.

\xheadbreak

A manual break which is active in the text and in the headers but not in the table of contents.

4.3 Other commands

\toclabelwidth{\langle level \rangle}{\langle dim \rangle}

Adds the *dim* to the *level* label in the table of contents, where *level* can be part, chap, sec, subsec, subsubsec, par, subpar, fig, tab. For example, when using chapnumstyle=Roman you would probably need to adjust the width of the chapter label with:

\toclabelwidht{chap}{1em}

\xfootnote[⟨symbol⟩]{⟨footnote text⟩}

A command to print a footnote with a discretionary symbols given in the optional argument (default=∗). It does not increment the footnote counter.

\xfootnote[\$\dagger\$]{Footnote text.}
\xfootnote[\$\ddagger\$]{Footnote text.}

\title[⟨short title for headers⟩]{⟨complete title for titlepage⟩}

Useful with `authortitle` option if the title is too long or has some breaks.

\chapterintro

Prints an unnumbered introduction at the beginning of the chapter, with the correct hyperlink. In order to use this command the `hyperref` package must be loaded.

\chapterintroname{\⟨name⟩}

(default=Introduzione)

Changes in *name* the title printed by the \chapterintro command.

\appendicesname{\⟨name⟩}

(default=Appendici)

Changes in *name* the title printed by the \appendix command.

\chapnumfont{\⟨name⟩}

Sets the font of the chapter number of style=elements/sufelements styles. The default is Palatino (L^ET_EX) or Computer Modern (X^LT_EX). Using (pdf)L^ET_EX you can change it simply giving the name of the font family.

For example, to select the Helvetica family you will need:

\chapnumfont{phv}

With X^LT_EX the \fontspec command is required:

\chapnumfont{\fontspec[Numbers=OldStyle]{Helvetica}}

5 The collection document structure

The collection document structure is thought to compose a collection of papers. Each paper has to be typeset in a separate .tex file with the following structure:

```
\author{Author}
\title{Title of the paper}

% The abstract is optional.
% \begin{abstract}
% The abstract
% \end{abstract}

\maketitle
```

Text of the paper

If the names of the papers are `article1.tex`, `article2.tex`, `article3.tex`, etc., then a minimal main file should be similar to this:

```
\documentclass[documentstructure=collection]{suftesi}

\begin{document}

\includeart{article1}
\includeart{article2}
\includeart{article3}

\end{document}
```

5.1 Options

In addition to the following options you can use the other options of the class too. In particular, with the `chapstyle` and `chapfont` options you can customize all the section titles which are treated as a normal unnumbered chapters in the book document structure, such as “Table of Contents”, “Index”, “Bibliography”, etc.

`papertitlestyle=left, center, right` default: left

- `left` Aligns the author-title block on the left.
- `center` Centers the author-title block.
- `right` Aligns the author-title block on the right.

`titlefont=roman, italic, smallcaps` default: italic

- `roman` Prints the title of the articles in roman.
- `italic` Prints the title of the articles in *italic*.
- `smallcaps` Prints the title of the articles in SMALL CAPS.

`authorfont=roman, italic, smallcaps` default: roman

- `roman` Prints the author's name in roman.
- `italic` Prints the author's name in *italic*.
- `smallcaps` Prints the s name in SMALL CAPS.

5.2 Commands

`\includeart{\langle file name \rangle}`

Include the `\langle file name \rangle` in the collection.

`\frontispiece`

Typeset the frontispiece of the collection.

It requires the `\collectiontitle` and `\collectioneditor` commands in the preamble of your document.

`\collectiontitle{\langle The Title of the Collection \rangle}`

Sets the title of the collection.

`\collectioneditor{\langle The Editor(s) \rangle}`

Sets the editor(s) of the collection.

References

This bibliography has been typeset with the `biblatex-philosophy` package, created by the same author of this class.

Bringhurst, Robert (1992), *The Elements of Typographic Style*, 2nd ed., Hurtley & Marks Publisher, Vancouver.

Gregorio, Enrico (2009), *Il pacchetto frontespizio*, version 1.1, <http://www.guit.sssup.it/phpbb/index.php>.

Miede, André (2011), *A Classic Thesis style*, <http://www.ctan.org/tex-%20archive/macros/%20l4tex/contrib/classicthesis/ClassicThesis.%20pdf>.

Morison, Stanley (1936), *First Principles of Typography*, Cambridge University Press, Cambridge; trans. *I principi fondamentali della tipografia*, Fabrizio Serra editore, Pisa-Roma 2008.

Pantieri, Lorenzo and Tommaso Gordini (2011), *L'arte di scrivere con L^AT_EX. Un'introduzione a L^AT_EX 2_E*, with a forew. by Enrico Gregorio, new edition, http://www.lorenzopantieri.net/LaTeX_files/ArteLaTeX.pdf.

Tschichold, Jan (1975), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie*, Birkhäuser Verlag, Basel; trans. *La forma del libro*, Sylvestre Bonnard, Milano 2003.

6 The Code

```

1 \ClassWarningNoLine{suftesi}{%
2   ****\MessageBreak
3   * DO NOT MODIFY THE STYLES OF THIS CLASS\MessageBreak
4   * WITH PACKAGES AND/OR COMMANDS WHICH CHANGE\MessageBreak
5   * THE LAYOUT OF THE DOCUMENT.\MessageBreak
6   * SEE DOCUMENTATION FOR DETAILS.\MessageBreak
7   * ANYWAY, DON'T WORRY!\MessageBreak
8   * THIS IS A HARMLESS MESSAGE :-)\MessageBreak
9   ****\MessageBreak
10 \RequirePackage{xkeyval}
11 \newif\ifsuftesi@standardfont
12 \newif\ifsuftesi@porson
13 \newif\ifsuftesi@centerheader
14 \newif\ifsuftesi@sufplain
15 \newif\ifsuftesi@article
16 \newif\ifsuftesi@authortitle
17 \newif\ifsuftesi@periodical
18 \newif\ifsuftesi@periodicalaureo
19 \newif\ifsuftesi@compact
20 \newif\ifsuftesi@compactaureo
21 \newif\ifsuftesi@supercompact
22 \newif\ifsuftesi@supercompactaureo
23 \newif\ifsuftesi@sufelements
24 \newif\ifsuftesi@nocrop
25 \newif\ifsuftesi@dottedtoc
26 \newif\ifsuftesi@raggedtoc
27 \newif\ifsuftesi@numparpart
28 \newif\ifsuftesi@numparchap
29 \newif\ifsuftesi@numparsec
30 \newif\ifsuftesi@umparsubsec
31 \newif\ifsuftesi@umparsubsubsec
32 \newif\ifsuftesi@smallcapspart
33 \newif\ifsuftesi@smallcapschap
34 \newif\ifsuftesi@smallcapssec
35 \newif\ifsuftesi@elementschap
36 \newif\ifsuftesi@elementsheader
37 \newif\ifsuftesi@elementsstructure
38 \newif\ifsuftesi@elementspagelayout
39 \newif\ifsuftesi@draftdate
40 \newif\ifsuftesi@fewfootnotes
41 \newif\ifsuftesi@partpage
42 \newif\ifsuftesi@FSPL
43 \newif\ifsuftesi@screen
44 \newif\ifsuftesi@pagelefttoc
45 \newif\ifsuftesi@twocolumnmtoc
46 \newif\ifsuftesi@twocolumnlof
47 \newif\ifsuftesi@twocolumnlot
48 \newif\ifsuftesi@reverseauthortitle
49 \newif\ifsuftesi@collection
50 \DeclareOption{a5paper}{%
51   \ClassError{suftesi}{Option 'a5paper' not available}}
52 \DeclareOption{b5paper}{%
53   \ClassError{suftesi}{Option 'b5paper' not available}}
54 \DeclareOption{legalpaper}{%
55   \ClassError{suftesi}{Option 'legalpaper' not available}}
56 \DeclareOption{executivepaper}{%
57   \ClassError{suftesi}{Option 'executivepaper' not available}}
58 \DeclareOption{landscape}{%
59   \ClassError{suftesi}{Option 'landscape' not available}}
suftesi is based on the standard book class!
60 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{book}}
61 \ProcessOptions
62 \relax
63 \LoadClass{book}

```

6.1 Document structure

```

64 \define@choicekey{}{documentstructure}{\val\nr}
65     {book,article,collection}[book]{%
66 \ifcase\nr\relax
67 \disable@keys{}{secnumstyle}
68 \or
69 \suftesi@articleture
70 \@titlepagefalse
71 \or
72 \suftesi@collectiontrue
73 \setkeys{}{headerstyle=authortitleinner}
74 \fi}

```

6.2 Page layout

```

75 \RequirePackage{geometry}
76 \define@choicekey{}{pagelayout}{\val\nr}
77     {standard,periodical,compact,compactaureo,supercompact,
78      supercompactaureo,elements,periodicalaureo}[standard]{%
79 \ifcase\nr\relax
80 \DeclareRobustCommand{\SUF@chaptersize}{\Large}
81 \geometry{%
82     heightrounded,
83     a4paper,
84     includeheadfoot=true,
85     textwidth= 110mm,
86     textheight= 220mm,
87     marginratio= 1:2,
88     marginparwidth= 30mm,
89     marginparsep= 12pt}
89 \or
90 \suftesi@periodicaltrue
91 \DeclareRobustCommand{\SUF@chaptersize}{\large}
92 \geometry{%
93     heightrounded,
94     includeheadfoot=false,
95     textheight= 165mm,
96     textwidth= 110mm,
97     paperwidth= 170mm,
98     paperheight= 240mm,
99     marginratio= 2:3,
100    marginparwidth= 26mm,
101    marginparsep= 10pt}
102 \or
103 \suftesi@compacttrue
104 \DeclareRobustCommand{\SUF@chaptersize}{\large}
105 \geometry{%
106     heightrounded,
107     includeheadfoot=false,
108     textheight= 165mm,
109     textwidth= 110mm,
110     paperwidth= 160mm,
111     paperheight= 240mm,
112     marginratio= 2:3,
113     marginparwidth= 22mm,
114     marginparsep= 9pt}
115 \or
116 \suftesi@compactaureottrue
117 \DeclareRobustCommand{\SUF@chaptersize}{\large}
118 \geometry{%
119     heightrounded,
120     includeheadfoot=false,
121     textheight= 191mm,
122     textwidth= 118mm,
123     paperwidth= 160mm,
124     paperheight= 240mm,
125 }

```

```

126      marginratio=    2:3,
127      marginparwidth= 19mm,
128      marginparsep=   9pt}
129 \or
130 \suftesi@supercompacttrue
131 \DeclareRobustCommand{\SUF@chaptersize}{\large}
132 \geometry{
133     heightrounded,
134     includeheadfoot=false,
135     textheight=    150mm,
136     textwidth=     100mm,
137     paperwidth=    140mm,
138     paperheight=   210mm,
139     marginratio=   2:3,
140     marginparwidth= 18mm,
141     marginparsep=  8pt}
142 \or
143 \suftesi@supercompactaureottrue
144 \DeclareRobustCommand{\SUF@chaptersize}{\large}
145 \geometry{
146     heightrounded,
147     includeheadfoot=false,
148     textheight=    175mm,
149     textwidth=     108mm,
150     paperwidth=    140mm,
151     paperheight=   210mm,
152     marginratio=   1:1,
153     marginparwidth= 11mm,
154     marginparsep=  7pt}\or
155 \suftesi@elementspagelayouttrue
156 \geometry{%
157     heightrounded,
158     includeheadfoot=false,
159     textwidth=     251pt,
160     textheight=   502pt,
161     paperwidth=   374pt,
162     paperheight=  648pt,
163     vmarginratio= 1:2,
164     marginparwidth= 60pt,
165     marginparsep= 18pt,
166     outer=        90pt}
167 \or
168 \suftesi@periodicalaureottrue
169 \DeclareRobustCommand{\SUF@chaptersize}{\large}
170 \geometry{%
171     heightrounded,
172     includeheadfoot=true,
173     textwidth=     120mm,
174     textheight=   194mm,
175     paperwidth=   17cm,
176     paperheight=  24cm,
177     marginratio=  2:3,
178     marginparwidth= 62pt,
179     marginparsep= 10pt}
180 \or
181 \fi}

```

6.3 Sections style

These macros control the position of titles and numbers of parts, chapters, sections, subsections and subsubsection.

```

182 \define@choicekey{}{partstyle}[\val\nr]{%
183     left,center,right,parleft,parcenter,parright}[left]{%
184 \ifcase\nr\relax
185     \def\SUF@lr@PARTSwitch{\filright}
186 \or
187     \def\SUF@lr@PARTSwitch{\filcenter}

```

```

188 \or
189   \def\SUF@lr@PARTSwitch{\filleft}
190 \or%numpar
191   \def\SUF@lr@PARTSwitch{\filright}
192   \suftesi@numparparttrue
193 \or
194   \def\SUF@lr@PARTSwitch{\filcenter}
195   \suftesi@numparparttrue
196 \or
197   \def\SUF@lr@PARTSwitch{\filleft}
198   \suftesi@numparparttrue
199 \fi}
200 \define@choicekey{}{chapstyle}[\val\nr]{%
201   left,center,right,parleft,parcenter,parright,elements}[left]{%
202 \ifcase\nr\relax
203   \def\SUF@lr@CHAPSwitch{\filright}
204 \or
205   \def\SUF@lr@CHAPSwitch{\filcenter}
206 \or
207   \def\SUF@lr@CHAPSwitch{\filleft}
208 \or%numparchap
209   \def\SUF@lr@CHAPSwitch{\filright}
210   \suftesi@numparchaptrue
211 \or
212   \def\SUF@lr@CHAPSwitch{\filcenter}
213   \suftesi@numparchaptrue
214 \or
215   \def\SUF@lr@CHAPSwitch{\filleft}
216   \suftesi@numparchaptrue
217 \or
218   \suftesi@elementschaptrue
219 \fi}
220 \define@choicekey{}{secstyle}[\val\nr]{%
221   left,center,right,parleft,parcenter,parright}[left]{%
222 \ifcase\nr\relax
223   \def\SUF@lr@SECSwitch{\filright}
224 \or
225   \def\SUF@lr@SECSwitch{\filcenter}
226 \or
227   \def\SUF@lr@SECSwitch{\filleft}
228 \or%numparsec
229   \def\SUF@lr@SECSwitch{\filright}
230   \suftesi@numparsectrue
231 \or
232   \def\SUF@lr@SECSwitch{\filcenter}
233   \suftesi@numparsectrue
234 \or
235   \def\SUF@lr@SECSwitch{\filleft}
236   \suftesi@numparsectrue
237 \fi}
238 \define@choicekey{}{subsecstyle}[\val\nr]{left,center,right}[left]{%
239 \ifcase\nr\relax
240   \def\SUF@lr@SUBSECSwitch{\filright}
241 \or
242   \def\SUF@lr@SUBSECSwitch{\filcenter}
243 \or
244   \def\SUF@lr@SUBSECSwitch{\filleft}
245 \fi}
246 \define@choicekey{}{subsubsecstyle}[\val\nr]{left,center,right}[left]{%
247 \ifcase\nr\relax
248   \def\SUF@lr@SUBSUBSECSwitch{\filright}
249 \or
250   \def\SUF@lr@SUBSUBSECSwitch{\filcenter}
251 \or
252   \def\SUF@lr@SUBSUBSECSwitch{\filleft}
253 \fi}

```

6.4 Sections font

These macros control the style of part, chapter, section, subsection and subsubsection levels.

```

254 \define@choicekey{}{partfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
255 \ifcase\nr\relax
256 \def\SUF@PART@StyleSwitch{\relax}
257 \or
258 \def\SUF@PART@StyleSwitch{\itshape}
259 \or
260 \def\SUF@PART@StyleSwitch{\expandafter\SUF@titlesmallcaps}
261 \fi}
262 \define@choicekey{}{chapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
263 \ifcase\nr\relax
264 \def\SUF@CHAP@StyleSwitch{\relax}
265 \or
266 \def\SUF@CHAP@StyleSwitch{\itshape}
267 \or
268 \def\SUF@CHAP@StyleSwitch{\expandafter\SUF@titlesmallcaps}
269 \fi}
270 \define@choicekey{}{secfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
271 \ifcase\nr\relax
272 \def\SUF@SEC@StyleSwitch{\relax}
273 \or
274 \def\SUF@SEC@StyleSwitch{\itshape}
275 \or
276 \def\SUF@SEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
277 \fi}
278 \define@choicekey{}{subsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
279 \ifcase\nr\relax
280 \def\SUF@SUBSEC@StyleSwitch{\relax}
281 \or
282 \def\SUF@SUBSEC@StyleSwitch{\itshape}
283 \or
284 \def\SUF@SUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
285 \fi}
286 \define@choicekey{}{subsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
287 \ifcase\nr\relax
288 \def\SUF@SUBSUBSEC@StyleSwitch{\relax}
289 \or
290 \def\SUF@SUBSUBSEC@StyleSwitch{\itshape}
291 \or
292 \def\SUF@SUBSUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
293 \fi}

```

6.5 Section numbers

6.5.1 Part number style

```

294 \define@choicekey{}{partnumstyle}[\val\nr]
295     {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
296 \ifcase\nr\relax
297     \def\SUF@thepart{\arabic{part}}
298     \def\SUF@dotpart{}
299     \def\SUF@toclabelnum{}
300 \or
301     \def\SUF@thepart{\textsc{\romannumeral{part}}}
302     \def\SUF@dotpart{}
303     \def\SUF@toclabelnum{\scshape{@roman}}
304 \or
305     \def\SUF@thepart{\Roman{part}}
306     \def\SUF@dotpart{}
307     \def\SUF@toclabelnum{@Roman}
308 \or
309     \def\SUF@thepart{\arabic{part}}
310     \def\SUF@dotpart{.}
311     \def\SUF@toclabelnum{}

```

```

312 \or
313   \def\SUF@theprt{\textsc{\rom{part}}}
314   \def\SUF@dotprt{.}
315   \def\SUF@toclabelnum{\scshape@\rom{part}}
316 \or
317   \def\SUF@theprt{\Roman{part}}
318   \def\SUF@dotprt{.}
319   \def\SUF@toclabelnum{\@Roman}
320 \fi}

```

6.5.2 Chapter number

```

321 \define@choicekey{}{chapnumstyle}[\val\nr]{arabic,roman,Roman,
322 dotarabic,dotroman,dotRoman}[arabic]{%
323 \ifcase\nr\relax
324   \def\SUF@thechapter{\arabic{chapter}}
325   \def\SUF@dotchap{.}
326   \def\SUF@toclabelnum{}
327 \or
328   \def\SUF@thechapter{\textsc{\rom{chapter}}}
329   \def\SUF@dotchap{.}
330   \def\SUF@toclabelnum{\scshape@\rom{chapter}}
331 \or
332   \def\SUF@thechapter{\Roman{chapter}}
333   \def\SUF@dotchap{.}
334   \def\SUF@toclabelnum{\@Roman}
335 \or
336   \def\SUF@thechapter{\arabic{chapter}}
337   \def\SUF@dotchap{.}
338   \def\SUF@toclabelnum{}
339 \or
340   \def\SUF@thechapter{\textsc{\rom{chapter}}}
341   \def\SUF@dotchap{.}
342   \def\SUF@toclabelnum{\scshape@\rom{chapter}}
343 \or
344   \def\SUF@thechapter{\Roman{chapter}}
345   \def\SUF@dotchap{.}
346   \def\SUF@toclabelnum{\@Roman}
347 \fi}

```

6.5.3 Section number

```

348 \define@choicekey{}{secnumstyle}[\val\nr]
349   {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
350 \ifcase\nr\relax
351   \def\SUF@thesection{\arabic{section}}
352   \def\SUF@dotsec{.}
353   \def\SUF@toclabelnum{}
354 \or
355   \def\SUF@thesection{\textsc{\rom{section}}}
356   \def\SUF@dotsec{.}
357   \def\SUF@toclabelnum{\scshape@\rom{section}}
358 \or
359   \def\SUF@thesection{\Roman{section}}
360   \def\SUF@dotsec{.}
361   \def\SUF@toclabelnum{\@Roman}
362 \or
363   \def\SUF@thesection{\arabic{section}}
364   \def\SUF@dotsec{.}
365   \def\SUF@toclabelnum{}
366 \or
367   \def\SUF@thesection{\textsc{\rom{section}}}
368   \def\SUF@dotsec{.}
369   \def\SUF@toclabelnum{\scshape@\rom{section}}
370 \or
371   \def\SUF@thesection{\Roman{section}}
372   \def\SUF@dotsec{.}
373   \def\SUF@toclabelnum{\@Roman}

```

374 \fi}

This option controls the style of small capitals used in the title of chapters and sections using *<level>font=smallcaps* option:

```
375 \define@choicekey{}{smallcapsstyle}[\val\nr]
376   {low,upper}[low]{%
377 \ifcase\nr\relax
378   \def\suftesi@MakeTextLowercase{\MakeTextLowercase}
379 \or
380   \def\suftesi@MakeTextLowercase{\relax}
381 \fi}
```

6.6 Headers

6.6.1 Header style

```
382 \define@choicekey{}{headerstyle}[\val\nr]
383   {inner,center,plain,authortitleinner,
384     authortitlecenter,elements}[inner]{%
385 \ifcase\nr\relax
386   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
387   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}}
388 \or
389   \suftesi@centerheadertrue
390   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
391   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}}
392 \or
393   \suftesi@sufplaintrue
394 \or
395   \suftesi@authortitletrue
396   \def\SUF@rightmark{\SUF@Rheadstyle{@headtitle}}
397   \def\SUF@leftmark{\SUF@Lheadstyle{@author}}}
398 \or
399   \suftesi@authortitletrue
400   \def\SUF@rightmark{\SUF@Rheadstyle{@headtitle}}
401   \def\SUF@leftmark{\SUF@Lheadstyle{@author}}}
402   \suftesi@centerheadertrue
403 \or
404   \suftesi@elementsheadertrue
405 \fi}
```

6.6.2 Header font

```
406 \define@choicekey{}{headerfont}[\val\nr]
407   {roman,italic,smallcaps}[roman]{%
408 \ifcase\nr\relax
409   \def\SUF@Rheadstyle{}
410   \def\SUF@Lheadstyle{}
411   \def\SUF@thepage{\thepage}}
412 \or
413   \def\SUF@Rheadstyle{\itshape}
414   \def\SUF@Lheadstyle{\itshape}
415   \def\SUF@thepage{\thepage}}
416 \or
417   \def\SUF@Rheadstyle{\SUF@headingsmallcaps}
418   \def\SUF@Lheadstyle{\SUF@headingsmallcaps}
419   \def\SUF@thepage{\SUF@headingsmallcaps{\thepage}}}
420 \fi}
```

6.7 Text elements

6.7.1 Lists

```
421 \RequirePackage[inline]{enumitem}
422 \renewcommand\labelitemi{\color{sufgray}\textbullet}
423 \setlist{itemsep=.5ex,parsep=0pt}
424 \setlist[description]{font=\normalfont\itshape}
425 \define@choicekey{}{liststyle}[\val\nr]
426   {bulged,aligned,indented}[bulged]{%
427 \ifcase\nr\relax
```

```

428      \setlist[enumerate,1]{leftmargin=0pt,label=\arabic*.}
429      \setlist[enumerate,2]{leftmargin= 1.3\parindent,label=\alph*.}
430      \setlist[enumerate,3]{leftmargin= 1.3\parindent,label=\roman*.}
431      \setlist[itemize,1]{leftmargin=0pt}
432      \setlist[itemize,2]{leftmargin=1.3\parindent}
433      \setlist[itemize,3]{leftmargin=1.3\parindent}
434 \or
435      \setlist[enumerate,1]{leftmargin=1\parindent,label=\arabic*.}
436      \setlist[enumerate,2]{leftmargin= 1.5\parindent,label=\alph*.}
437      \setlist[enumerate,3]{leftmargin= 1.5\parindent,label=\roman*.}
438      \setlist[itemize,1]{leftmargin=1\parindent}
439      \setlist[itemize,2]{leftmargin=1.5\parindent}
440      \setlist[itemize,3]{leftmargin=1.5\parindent}
441 \or
442      \setlist[enumerate,1]{leftmargin=2\parindent,label=\arabic*.}
443      \setlist[enumerate,2]{leftmargin= 2.5\parindent,label=\alph*.}
444      \setlist[enumerate,3]{leftmargin= 2.5\parindent,label=\roman*.}
445      \setlist[itemize,1]{leftmargin=2\parindent}
446      \setlist[itemize,2]{leftmargin=2.5\parindent}
447      \setlist[itemize,3]{leftmargin=2.5\parindent}
448 \fi}

```

6.7.2 Block quotations

Quotation style

```

449 \define@choicekey{}{quotestyle}{[\val\nr]
450     {center,right}[center]%
451 \ifcase\nr\relax
452 \def\SUF@quote@style{\rightmargin=\parindent}
453 \or
454 \def\SUF@quote@style{}
455 \fi}

```

Quotation size

```

456 \define@choicekey{}{quotesize}{[\val\nr]
457     {footnotesize,small}[footnotesize]%
458 \ifcase\nr\relax
459 \def\SUF@quotation@size{\footnotesize}
460 \or
461 \def\SUF@quotation@size{\small}
462 \fi}

```

6.7.3 Footnotes

```

463 \define@choicekey{}{footnotestyle}{[\val\nr]
464     {bulged,hung,dotted,superscript}[bulged]%
465 \ifcase\nr\relax
466     \renewcommand{@makefntext}%
467         \hskip-2.5em\makebox[2em][r]{\@thefnmark}\hskip.5em}
468 \or
469     \renewcommand{@makefntext}%
470         \leftskip=1em\hskip-1.5em%
471         \makebox[1em][r]{\@thefnmark}\hskip.5em}
472 \or
473     \renewcommand{@makefntext}%
474         \@thefnmark.\hskip.5em}
475 \or
476     \renewcommand{@makefntext}%
477         \textsuperscript{\@thefnmark}\hskip.3em}
478 \fi}
479 \define@choicekey{}{fewfootnotes}{[\val\nr]
480     {true,false}[true]%
481 \ifcase\nr\relax
482     \suftesi@fewfootnotestrue
483 \or
484     \relax

```

```

485 \fi}

6.7.4 Captions

486 \RequirePackage{caption}
487 \define@choicekey{}{captionstyle}[\val\nr]
488   {standard,sanserif,italic,smallcaps,elements}[standard]{%
489   \ifcase\nr\relax
490     \captionsetup{labelsep=period,font=small}
491   \or
492     \captionsetup{labelsep=period,font=small}
493     \captionsetup{font+=sf}
494   \or
495     \captionsetup{labelsep=period,font=small}
496     \captionsetup{font+=it}
497   \or
498     \captionsetup{labelsep=period,font=small,labelfont=sc}
499   \or
500     \captionsetup{labelsep=period,font=small}
501     \captionsetup{font+=sf}
502 \fi
503 }

```

6.7.5 Marginal notes

```

504 \define@choicekey{}{marginpar}[\val\nr]
505   {true,false}[true]{%
506 \ifcase\nr\relax
507 \or
508   \renewcommand\marginpar[2][]{}
509 \fi}

```

6.7.6 Table of contents

```

510 \define@choicekey{}{tocstyle}[\val\nr]{%
511   standard,dotted,ragged,leftpage}[standard]{%
512 \ifcase\nr\relax
513   \def\SUF@titlerule{\titlerule*{}}
514   \def\SUF@chaptitlerule{\titlerule*{}}
515 \or
516 \suftesi@dottedtotrue
517   \def\SUF@titlerule{\titlerule*{\footnotesize .\ } }
518   \def\SUF@chaptitlerule{\titlerule*{}}
519 \or
520 \suftesi@raggedtotrue
521   \def\SUF@titlerule{\hspace{1em}}
522   \def\SUF@chaptitlerule{\hspace{1em}}
523 \or
524 \suftesi@pagelefttotrue
525 \fi}
526 \define@choicekey{}{twocolcontents}[\val\nr]{%
527   toc,lof,lot,toclof,toclot,loflot,all}[all]{%
528 \ifcase\nr\relax
529   \suftesi@twocolumnmtotrue
530   \setkeys{}{tocstyle=ragged}
531 \or
532   \suftesi@twocolumnloftrue
533   \setkeys{}{tocstyle=ragged}
534 \or
535   \suftesi@twocolumnlottrue
536   \setkeys{}{tocstyle=ragged}
537 \or
538   \suftesi@twocolumnmtotrue
539   \suftesi@twocolumnloftrue
540   \setkeys{}{tocstyle=ragged}
541 \or
542   \suftesi@twocolumnmtotrue
543   \suftesi@twocolumnlottrue
544   \setkeys{}{tocstyle=ragged}

```

```

545 \or
546   \suftesi@twocolumnloftrue
547   \suftesi@twocolumnlottrue
548   \setkeys{}{tocstyle=ragged}
549 \or
550   \suftesi@twocolumntoctrue
551   \suftesi@twocolumnloftrue
552   \suftesi@twocolumnlottrue
553   \setkeys{}{tocstyle=ragged}
554 \fi
555 }

```

6.8 Fonts

6.8.1 Roman fonts

```

556 \define@choicekey{}{defaultfont}[\val\nr]{%
557   palatino,standard}[palatino]{%
558 \ifcase\nr\relax
559 \or
560   \suftesi@standardfonttrue
561 \def\SUF@greekfamily{lmr}
562 \fi}

```

6.8.2 Greek fonts

```

563 \define@choicekey{}{greekfont}[\val\nr]{%
564   artemisia,porson,cbgreek}[artemisia]{%
565 \ifcase\nr\relax
566 \def\SUF@greekfamily{artemisiaeuler}
567 \or
568 \def\SUF@greekfamily{porson}
569 \suftesi@porsontrue
570 \or
571 \def\SUF@greekfamily{lmr}
572 \fi}

```

6.9 Other options

6.9.1 \parindent

```

573 \define@choicekey{}{parindent}[\val\nr]
574   {compact,wide}[compact]{%
575 \ifcase\nr\relax
576 \setlength\parindent{1em}
577 \or
578 \setlength\parindent{1.5em}
579 \fi}

```

6.9.2 Part page

```

580 \define@choicekey{}{partpage}[\val\nr]{true,false}[true]{%
581 \ifcase\nr\relax
582   \suftesi@partpagetrue
583 \or
584   \relax
585 \fi}

```

6.9.3 Crop marks

```

586 \define@choicekey{}{crop}[\val\nr]
587   {true,false}[true]{%
588 \ifcase\nr\relax
589 \or
590   \suftesi@nocropttrue
591 \fi}

```

6.9.4 Draftdate

```

592 \define@choicekey{}{draftdate}[\val\nr]
593   {true,false}[true]{%
594 \ifcase\nr\relax

```

```

595   \suftesi@draftdatetrue
596 \or
597 \fi}

```

6.9.5 View mode

```

598 \define@choicekey{}{version}[\val\nr]
599   {screen,draft,final}[draft]{%
600 \ifcase\nr\relax
601   \suftesi@nocroptrue
602   \geometry{hmarginratio=1:1}
603   \newcommand*\crop[1][]{}
604 \or
605 \or
606   \AtBeginDocument{\crop[off]}
607 \fi}

```

6.9.6 Titlepage

```

608 \define@choicekey{}{titlepage}[\val\nr]
609   {true,false}[true]{%
610 \ifcase\nr\relax
611   \@titlepagetrue
612 \or
613   \@titlepagefalse
614 \fi}

```

6.9.7 Pre-defined styles

```

615 \define@choicekey{}{style}[\val\nr]
616   {roman1,roman2,roman3,roman4,roman5,roman6,
617   italic1,italic2,italic3,italic4,italic5,italic6,
618   italic7,italic8,italic9,italic10,italic11,italic12,
619   smallcaps1,smallcaps2,smallcaps3,smallcaps4,smallcaps5,smallcaps6,
620   smallcaps7,smallcaps8,smallcaps9,smallcaps10,smallcaps11,smallcaps12,
621   elements,sufelements,FSPLa,FSPLb,FSPLc}
622   [roman1]{%
623 \ifcase\nr\relax

```

The 'roman' styles:

```

624   \setkeys{}{chapstyle=left}
625 \or
626   \setkeys{}{chapstyle=center}
627 \or
628   \setkeys{}{chapstyle=right}
629 \or
630   \setkeys{}{chapstyle=parleft}
631 \or
632   \setkeys{}{chapstyle=parcenter}
633 \or
634   \setkeys{}{chapstyle=parright}
635 \or

```

The 'italic' styles:

```

636   \setkeys{}{
637   chapstyle=left,
638   chapfont=italic,
639   headerfont=italic}
640 \or
641   \setkeys{}{
642   chapstyle=center,
643   chapfont=italic,
644   headerfont=italic}
645 \or
646   \setkeys{}{
647   chapstyle=right,
648   chapfont=italic,
649   headerfont=italic}
650 \or
651   \setkeys{}{

```

```

652 chapstyle=parleft,
653 chapfont=italic,
654 headerfont=italic}
655 \or
656 \setkeys{}{
657 chapstyle=parcenter,
658 chapfont=italic,
659 headerfont=italic}
660 \or
661 \setkeys{}{
662 chapstyle=parright,
663 chapfont=italic,
664 headerfont=italic}
665 \or
666 \setkeys{}{
667 chapstyle=left,
668 chapfont=italic,
669 secfont=smallcaps,
670 headerfont=italic}
671 \or
672 \setkeys{}{
673 chapstyle=center,
674 chapfont=italic,
675 secfont=smallcaps,
676 headerfont=italic}
677 \or
678 \setkeys{}{
679 chapstyle=right,
680 chapfont=italic,
681 secfont=smallcaps,
682 headerfont=italic}
683 \or
684 \setkeys{}{
685 chapstyle=parleft,
686 chapfont=italic,
687 secfont=smallcaps,
688 headerfont=italic}
689 \or
690 \setkeys{}{
691 chapstyle=parcenter,
692 chapfont=italic,
693 secfont=smallcaps,
694 headerfont=italic}
695 \or
696 \setkeys{}{
697 chapstyle=parright,
698 chapfont=italic,
699 secfont=smallcaps,
700 headerfont=italic}
701 \or
The 'smallcaps' styles:
702 \setkeys{}{
703 chapstyle=left,
704 chapfont=smallcaps,
705 headerfont=smallcaps}
706 \or
707 \setkeys{}{
708 chapstyle=center,
709 chapfont=smallcaps,
710 headerfont=smallcaps}
711 \or
712 \setkeys{}{
713 chapstyle=right,
714 chapfont=smallcaps,
715 headerfont=smallcaps}
716 \or

```

```

717  \setkeys{}{
718    chapstyle=parleft,
719    chapfont=smallcaps,
720    headerfont=smallcaps}
721 \or
722  \setkeys{}{
723    chapstyle=parcenter,
724    chapfont=smallcaps,
725    headerfont=smallcaps}
726 \or
727  \setkeys{}{
728    chapstyle=parright,
729    chapfont=smallcaps,
730    headerfont=smallcaps}
731 \or
732  \setkeys{}{
733    chapstyle=left,
734    chapfont=smallcaps,
735    secfont=smallcaps,
736    headerfont=smallcaps}
737 \or
738  \setkeys{}{
739    chapstyle=center,
740    chapfont=smallcaps,
741    secfont=smallcaps,
742    headerfont=smallcaps}
743 \or
744  \setkeys{}{
745    chapstyle=right,
746    chapfont=smallcaps,
747    secfont=smallcaps,
748    headerfont=smallcaps}
749 \or
750  \setkeys{}{
751    chapstyle=parleft,
752    chapfont=smallcaps,
753    secfont=smallcaps,
754    headerfont=smallcaps}
755 \or
756  \setkeys{}{
757    chapstyle=parcenter,
758    chapfont=smallcaps,
759    secfont=smallcaps,
760    headerfont=smallcaps}
761 \or
762  \setkeys{}{
763    chapstyle=parright,
764    chapfont=smallcaps,
765    secfont=smallcaps,
766    headerfont=smallcaps}
767 \or
The 'elements' style:
768  \setkeys{}{
769    pagelayout=elements,
770    headerstyle=elements,
771    chapstyle=elements,
772    secfont=smallcaps,
773    subsecfont=italic,
774    captionstyle=elements}
775 \disable@keys{}
776   {pagelayout,headerstyle,chapstyle,secfont,subsecfont,captionstyle}
777 \or
The 'suelements' style:
778  \setkeys{}{
779    chapstyle=elements,
780    headerfont=smallcaps,

```

```

781     secfont=smallcaps,
782     subsecfont=italic}
783 \disable@keys{}
784     {headerstyle, chapstyle, secfont, subsecfont}
785 \or

The FSPLa style:
786 \suftesi@periodicalaureotrue
787 \suftesi@FSPLtrue
788 \setkeys{}{%
789     pagelayout=periodicalaureo,
790     style=roman5,
791     chapnumstyle=roman,
792     headerstyle=inner,
793     footnotestyle=hung,
794     liststyle=indented,
795     tocstyle=leftpage}
796 \disable@keys{}

797 {documentstructure, pagelayout, partfont, chapfont, secfont, %
798 subsecfont, subsubsecfont, partstyle, chapstyle, secstyle, %
799 subsecstyle, subsubsecstyle, partnumstyle, chapnumstyle, %
800 secnumstyle, tocstyle, headerstyle, headerfont, quotestyle, %
801 quotesize, footnotestyle, liststyle, captionstyle, parindent}
802 \or

The FSPLb style:
803 \suftesi@periodicalaureotrue
804 \suftesi@FSPLtrue
805 \setkeys{}{%
806     pagelayout=periodicalaureo,
807     style=italic5,
808     chapnumstyle=roman,
809     headerstyle=inner,
810     headerfont=italic,
811     footnotestyle=hung,
812     liststyle=indented,
813     tocstyle=leftpage}
814 \disable@keys{}

815 {documentstructure, pagelayout, partfont, chapfont, secfont, %
816 subsecfont, subsubsecfont, partstyle, chapstyle, secstyle, %
817 subsecstyle, subsubsecstyle, partnumstyle, chapnumstyle, %
818 secnumstyle, tocstyle, headerstyle, headerfont, quotestyle, %
819 quotesize, footnotestyle, liststyle, captionstyle, parindent}
820 \or

The FSPLc style:
821 \suftesi@periodicalaureotrue
822 \suftesi@FSPLtrue
823 \setkeys{}{%
824     pagelayout=periodicalaureo,
825     style=smallcaps5,
826     chapnumstyle=roman,
827     headerstyle=inner,
828     headerfont=smallcaps,
829     secfont=smallcaps,
830     footnotestyle=hung,
831     liststyle=indented,
832     tocstyle=leftpage}
833 \disable@keys{}

834 {documentstructure, pagelayout, partfont, chapfont, secfont, %
835 subsecfont, subsubsecfont, partstyle, chapstyle, secstyle, %
836 subsecstyle, subsubsecstyle, partnumstyle, chapnumstyle, %
837 secnumstyle, tocstyle, headerstyle, headerfont, quotestyle, %
838 quotesize, footnotestyle, liststyle, captionstyle, parindent}
839 \fi}

840 % EXPERIMENTAL
841 \define@choicekey{}{papertitlestyle}[\val\nr]{%
842     left,center,right}[left]{%

```

```

843 \ifcase\nr\relax
844   \def\SUF@lr@coll@titleSwitch{\filright}
845 \or
846   \def\SUF@lr@coll@titleSwitch{\filcenter}
847 \or
848   \def\SUF@lr@coll@titleSwitch{\filleft}
849 \fi}
850 \define@choicekey{}{revauthortitle}[\val\nr]
851   {true, false}[false]{%
852 \ifcase\nr\relax
853 \suftesi@reverseauthortitletrue
854 \or\relax
855 \fi}
856 \define@choicekey{}{titlefont}[\val\nr]{roman, italic, smallcaps}[roman]{%
857 \ifcase\nr\relax
858 \def\SUF@titlefont@Switch{\relax}
859 \or
860 \def\SUF@titlefont@Switch{\itshape}
861 \or
862 \def\SUF@titlefont@Switch{\expandafter\SUF@titlesmallcaps}
863 \fi}
864
865 \define@choicekey{}{authorfont}[\val\nr]{roman, italic, smallcaps}[roman]{%
866 \ifcase\nr\relax
867 \def\SUF@authorfont@Switch{\relax}
868 \or
869 \def\SUF@authorfont@Switch{\itshape}
870 \or
871 \def\SUF@authorfont@Switch{\expandafter\SUF@titlesmallcaps}
872 \fi}

Execute and process options:
873 \ExecuteOptionsX<>{
874   captionstyle=standard,
875   marginpar=true,
876   parindent=compact,
877   tocstyle=standard,
878   greekfont=artemisia,
879   pagelayout=standard,
880   headerstyle=inner,
881   liststyle=bulged,
882   footnotestyle=bulged,
883   quotesize=footnotesize,
884   quotestyle=center,
885   partstyle=left,
886   chapstyle=left,
887   secstyle=left,
888   subsecstyle=left,
889   subsubsecstyle=left,
890   partfont=roman,
891   chapfont=roman,
892   secfont=italic,
893   subsecfont=roman,
894   subsubsecfont=roman,
895   headerfont=roman,
896   secnumstyle=arabic,
897   partnumstyle=Roman,
898   chapnumstyle=arabic,
899   smallcapsstyle=low,
900   titlefont=italic,
901   authorfont=roman,
902   revauthortitle=false,
903   papertitlestyle=left,
904   authorfont=roman,
905   titlefont=italic}
906 \ProcessOptionsX<>\relax

```

The use of the `\XKV@useoption` command, provided by the `xkeyval`, is a trick to delete the option given as its argument from the list stored in `\@unusedoptionlist` so that the option will not produce the “Unused global options” message:

```

907 \XKV@useoption{a4paper}    \XKV@useoption{10pt}
908 \XKV@useoption{11pt}       \XKV@useoption{12pt}
909 \XKV@useoption{oneside}    \XKV@useoption{twoside}
910 \XKV@useoption{onecolumn}   \XKV@useoption{twocolumn}
911 \XKV@useoption{titlepage}  \XKV@useoption{notitlepage}
912 \XKV@useoption{openright}   \XKV@useoption{openany}
913 \XKV@useoption{leqno}      \XKV@useoption{fleqn}
914 \XKV@useoption{a5paper}    \XKV@useoption{b5paper}
915 \XKV@useoption{legalpaper} \XKV@useoption{executivepaper}
916 \XKV@useoption{landscape}
```

A trick to delete the class options from `\XKV@classoptionslist`, in order to avoid incompatibility with packages using options defined by `suftesi` too. Thanks to Enrico Gregorio!

```
917 \def\XKV@classoptionslist{}  

```

6.10 Basic packages

```

918 \RequirePackage{color}
919     \definecolor{sufred}{rgb}{0.5,0,0}
920     \definecolor{sufgray}{rgb}{0.5,0.5,0.5}
921 \RequirePackage{multicol}
922 \RequirePackage{emptypage}
923 \RequirePackage{textcase}
924 \RequirePackage{ifxetex}
925 \RequirePackage[final]{microtype}
926     \SetTracking
927     [ name      = default,
928       no ligatures = {f} ]
929     { encoding    = {OT1,T1,T2A,LY1,OT4,QX,EU2} }
930     { 110 }
931 \newcommand{\versionstring}[1]{\def\version@string{#1}}
932 \versionstring{Version of}
```

The FSPL style requires a verbose colophon which uses specific icons:

```

933 \ifsuftesi@FSPL
934     \RequirePackage{cclicenses}
935 \else
936 \fi
```

6.11 Greek fonts

Thanks to Claudio Beccari and Enrico Gregorio for these macros:

```

937 \ifxetex
938 \AtBeginDocument{
939 \@ifpackageloaded{fontspec}
940     {\relax
941     \ClassError{suftesi}
942         {*****\MessageBreak
943          * For using suftesi with XeLaTeX\MessageBreak
944          * load either 'fontspec' or 'mathspec'\MessageBreak
945          *****}
946         {*****\MessageBreak
947          * For using suftesi with XeLaTeX\MessageBreak
948          * load either 'fontspec' or 'mathspec'\MessageBreak
949          *****}}
950     }
951 \else
952 \RequirePackage[LGR,T1]{fontenc}
953 \RequirePackage{substitutefont}
954 \AtBeginDocument{\fontencoding{T1}\selectfont}
955 \ifsuftesi@standardfont
956     \RequirePackage{lmodern}
957     \relax
958 \else
959     \RequirePackage[osf,sc]{mathpazo}
960     \RequirePackage[scaled=0.8]{beramono}
```

```

961           \renewcommand{\sfdefault}{iwona}
962 \AtBeginDocument{
963 \substitutefont{LGR}{\rmdefault}{\SUF@greekfamily}
964   \DeclareRobustCommand{\greektext}{%
965     \usefont{LGR}{\SUF@greekfamily}{\f@series}{\f@shape}
966     \def\encodingdefault{LGR}}
967   \DeclareTextFontCommand{\textgreek}{\greektext}
968 }
969 \fi

Scale the Porson font:

970 \ifsuftesi@porson
971 \sbox{z@{\fontsize{10}{10}\normalfont A}}
972 \sbox{tw@{\font\temp=gporsong6a at 10pt \temp A}}
973 \dimen@=\dimexpr \p@\ht{z@/\ht{tw@\relax
974 \sbox{z@{\normalfont\fontsize{10}{10}\selectfont a}}
975 \sbox{tw@{\font\temp=gporsong6a at 10pt \temp a}}
976 \dimen2=\dimexpr \p@\ht{z@/\ht{tw@\relax
977 \dimen4= 0.6\p@
978 \dimen@=\dimexpr \dimen@ - \dimen4*\dimen@/\p@+\dimen4*\dimen2/\p@\relax
979 \edef\art@scale{\strip@pt\dimen@}
980 \DeclareFontFamily{LGR}{porson}{}
981 \DeclareFontShape{LGR}{porson}{m}{n}  {<- s * [\art@scale] gporsong6a}{}
982 \DeclareFontShape{LGR}{porson}{m}{it} {<- ssub * porson/m/n}{}
983 \DeclareFontShape{LGR}{porson}{b}{n}  {<- ssub * porson/m/n}{}
984 \DeclareFontShape{LGR}{porson}{b}{it} {<- ssub * porson/m/n}{}
985 \DeclareFontShape{LGR}{porson}{m}{sl} {<- ssub * porson/m/n}{}
986 \DeclareFontShape{LGR}{porson}{b}{sl} {<- ssub * porson/m/n}{}
987 \DeclareFontShape{LGR}{porson}{m}{sc} {<- ssub * porson/m/n}{}
988 \DeclareFontShape{LGR}{porson}{bx}{n}  {<- ssub * porson/m/n}{}
989 \DeclareFontShape{LGR}{porson}{bx}{it} {<- ssub * porson/m/n}{}
990 \DeclareFontShape{LGR}{porson}{bx}{sl} {<- ssub * porson/m/n}{}
991   \fi
992 \fi

```

6.12 Page layout

```

993 \ifsuftesi@nocrop
994   \relax
995   \else
996   \RequirePackage[a4, cam, center]{crop}
997 \fi

```

A trick to produce one-side documents:

```

998 \if@twoside
999   \relax
1000   \else
1001   \geometry{hmarginratio=1:1}
1002 \fi

```

6.13 Section titles

```

1003 \RequirePackage{titlesec}
1004   \newlength{\sectionsep}
1005   \setlength{\sectionsep}{\dimexpr(\baselineskip) plus 1pt minus 1pt}
1006 \ifxetex
1007   \DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1008     \addfontfeature{LetterSpace=6}\scshape\suftesi@MakeTextLowercase{\#1}}
1009   \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1010     \addfontfeature{LetterSpace=6}\scshape\suftesi@MakeTextLowercase{\#1}}
1011   \newcommand{\chapnumfont}[1]{%
1012     \def\SUF@chapnumfont{\#1}}
1013   \chapnumfont{\relax}%
1014 \else
1015   \DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1016     \scshape\suftesi@MakeTextLowercase{\lsstyle \#1}}%
1017   \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1018     \scshape\suftesi@MakeTextLowercase{\lsstyle \#1}}%

```

```

1019 \newcommand{\chapnumfont}[1]{%
1020   \def\@SUF@chapnumfont{\fontfamily{#1}}%
1021   \chapnumfont{pplj}%
1022 \fi

```

The elements style

```

1023 \define@key[SUF]{elements}{chapsize}[90]{%
1024   \def\cmdSUF@elements@chapsize{\fontsize{#1}{#1}\selectfont}%
1025 \define@key[SUF]{elements}{chapposition}[-83]{%
1026   \def\cmdSUF@elements@chapposition{#1}%

```

The chapter for elements style:

```

1027 \def\@SUF@elements@CHAPTER{%
1028   \titleformat{\chapter}[block]%
1029     {\Large}%
1030     {\begin{picture}(0,0)%
1031       \setlength{\unitlength}{1pt}%
1032       \SUF@chapnumfont%
1033       \cmdSUF@elements@chapsize%
1034       \put(0,\cmdSUF@elements@chapposition){%
1035         \hspace*{\dimexpr(\textwidth+0.9\marginparsep)}%
1036         \textcolor{sufgray}{\SUF@thechapter}}%
1037     \end{picture}}%
1038     {0pt}%
1039     {\SUF@titlesmallcaps}%
1040     [\vspace*{-6pt}\rule{\textwidth}{.1pt}]%
1041   }

```

The sections for elements style:

```

1042 \def\@SUF@elements@SECTIONS{%
1043   \titleformat{\section}[block]%
1044     {\extramarks{}{}\filright}%
1045     {\textnormal\thesection}%
1046     {1em}%
1047     {\SUF@titlesmallcaps}%
1048   \titlespacing{\section}{0em}{1em}{1em}[0em]%
1049   \titleformat{\subsection}[block]%
1050     {\filright\normalsize\itshape}%
1051     {\textnormal\thesubsection}%
1052     {1em}%
1053     {}%
1054   \titlespacing{\subsection}{0em}{\baselineskip}{\baselineskip}[0em]%
1055   \titleformat{\subsubsection}[block]%
1056     {\filright\normalsize}%
1057     {\textnormal\thesubsubsection}%
1058     {1em}%
1059     {}%
1060   \titlespacing{\subsubsection}{0em}{\baselineskip}{\baselineskip}[0em]%
1061 }

```

\chapter Default styles:

```

1062 \newlength\SUF@ADJnumparchap
1063 \def\@SUF@default@CHAPTER{%
1064 \ifsuftesi@numparchap
1065   \titleformat{\chapter}[display]%
1066     {\SUF@chaptersize\SUF@lr@CHAPSwitch}%
1067     {\SUF@thechapter\SUF@dotchap}%
1068     {2ex}%
1069     {\SUF@CHAP@StyleSwitch}%
1070   \else
1071   \titleformat{\chapter}[hang]%
1072     {\SUF@chaptersize\SUF@lr@CHAPSwitch}%
1073     {\SUF@thechapter\SUF@dotchap}%
1074     {3em}%
1075     {\SUF@CHAP@StyleSwitch}%
1076   \fi
1077 \ifsuftesi@numparchap
1078   \setlength{\SUF@ADJnumparchap}{-2.5\baselineskip}

```

```

1079      \else
1080      \setlength{\SUF@ADJnumparchap}{0pt}
1081 \fi}

\section
1082 \def\SUF@default@SECTIONS{
1083 \ifsuftesi@numparsec
1084 \titleformat{\section}[display]
1085   {\SUF@lr@SECSwitch}
1086   {\ifsuftesi@article\SUF@thesection
1087     \else\thesection\fi\SUF@dotsec}
1088   {0ex}
1089   {\SUF@SEC@StyleSwitch}
1090 \titlespacing*{\section}{0em}{\sectionsep}{\sectionsep}[0em]
1091 \else
1092 \titleformat{\section}[hang]
1093   {\SUF@lr@SECSwitch}
1094   {\ifsuftesi@article\SUF@thesection
1095     \else\thesection\fi\SUF@dotsec}
1096   {1em}
1097   {\SUF@SEC@StyleSwitch}
1098 \titlespacing*{\section}{0ex}{\sectionsep}{\sectionsep}[0ex]
1099 \fi

\subsection
1100 \ifsuftesi@numparsubsec
1101 \titleformat{\subsection}[display]
1102   {\SUF@lr@SUBSECSwitch}
1103   {\textnormal\thesubsection}
1104   {0ex}
1105   {\SUF@SUBSEC@StyleSwitch}
1106 \titlespacing*{\subsection}{0em}{\sectionsep}{\sectionsep}[0em]
1107 \else
1108 \titleformat{\subsection}[hang]
1109   {\SUF@lr@SUBSECSwitch}
1110   {\textnormal\thesubsection}
1111   {1em}
1112   {\SUF@SUBSEC@StyleSwitch}
1113 \titlespacing*{\subsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1114 \fi

\subsubsection
1115 \ifsuftesi@numparsubsubsec
1116 \titleformat{\subsubsection}[display]
1117   {\SUF@lr@SUBSUBSECSwitch}
1118   {\textnormal\thesubsubsection}
1119   {0ex}
1120   {\SUF@SUBSUBSEC@StyleSwitch}
1121 \titlespacing*{\subsubsection}{0em}{\sectionsep}{\sectionsep}[0em]
1122 \else
1123 \titleformat{\subsubsection}[hang]
1124   {\SUF@lr@SUBSUBSECSwitch}
1125   {\textnormal\thesubsubsection}
1126   {1em}
1127   {\SUF@SUBSUBSEC@StyleSwitch}
1128 \titlespacing*{\subsubsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1129 \fi
1130 }

1131 \ifsuftesi@elementschap
1132 \RequirePackage{extramarks}
1133   \SUF@elements@CHAPTER
1134   \SUF@elements@SECTIONS
1135 \ifsuftesi@periodical
1136   \titlespacing*{\chapter}{0em}{-\baselineskip}{10pt}[0pt]
1137     \setkeys[SUF]{elements}{chapsize=80, chapposition=-83}
1138 \else
1139 \ifsuftesi@periodicalaureo

```

```

1140 \titlespacing*{\chapter}{0em}{-\baselineskip}{10pt}[0pt]
1141   \setkeys[SUF]{elements}{chapsize=80, chaproposition=-83}
1142 \else
1143 \ifsuftesi@compact
1144   \titlespacing*{\chapter}{0em}{-1\baselineskip}{10pt}[0pt]
1145   \setkeys[SUF]{elements}{chapsize=75, chaproposition=-83}
1146 \else
1147 \ifsuftesi@compactaureo
1148   \titlespacing*{\chapter}{0em}{-1\baselineskip}{10pt}[0pt]
1149   \setkeys[SUF]{elements}{chapsize=75, chaproposition=-83}
1150 \else
1151 \ifsuftesi@supercompact
1152   \titlespacing*{\chapter}{0em}{-1\baselineskip}{10pt}[0pt]
1153   \setkeys[SUF]{elements}{chapsize=70, chaproposition=-73}
1154 \else
1155 \ifsuftesi@supercompactaureo
1156   \titlespacing*{\chapter}{0em}{-1\baselineskip}{10pt}[0pt]
1157   \setkeys[SUF]{elements}{chapsize=70, chaproposition=-73}
1158 \else
1159 \ifsuftesi@elementsplagelayout
1160   \titlespacing*{\chapter}{0em}{-\baselineskip}{10pt}[0pt]
1161   \setkeys[SUF]{elements}{chapsize=60, chaproposition=-73}
1162 \else
1163   \titlespacing*{\chapter}{0em}{-\baselineskip}{10pt}[0pt]
1164   \setkeys[SUF]{elements}{chapsize=90, chaproposition=-83}
1165     \fi
1166     \fi
1167     \fi
1168     \fi
1169     \fi
1170   \fi
1171 \fi
1172 \else
1173   \SUF@default@CHAPTER
1174   \SUF@default@SECTIONS
1175 \ifsuftesi@periodicalaureo
1176   \titlespacing*{\chapter}{0em}{0\SUF@ADJnumparchap}{18ex}
1177   \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1178 \else
1179 \ifsuftesi@periodical
1180   \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1181   \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1182     \else
1183       \ifsuftesi@compact
1184         \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1185         \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1186         \else
1187           \ifsuftesi@supercompact
1188             \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1189             \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1190             \else
1191               \titlespacing*{\chapter}{0em}{%
1192                 \dimexpr(6ex+\SUF@ADJnumparchap)}{18ex}
1193                 \titlespacing*{name=\chapter, numberless}{0em}{6ex}{18ex}
1194               \fi
1195             \fi
1196           \fi
1197         \fi
1198       \fi

```

Redefinitions for ‘article’ mode

```

1199 \ifsuftesi@article
1200 \def\chapter{\ClassError{suftesi}}
1201   {\noexpand\chapter level is undefined
1202     using 'documentstructure=article'}
1203   {\noexpand\chapter level is undefined

```

```

1204     using 'documentstructure=article'"}}
1205 \setcounter{tocdepth}{3}
1206   \setcounter{secnumdepth}{3}
1207   \renewcommand\thesection{%
1208     \@arabic\c@section}
1209 \renewcommand\thesubsection{%
1210   \thesection.\@arabic\c@subsection}
1211 \renewcommand\thesubsubsection{%
1212   \thesubsection.\@arabic\c@subsubsection}
1213 \renewcommand\theparagraph{%
1214   \thesubsubsection.\@arabic\c@paragraph}
1215 \renewcommand\thesubparagraph{%
1216   \theparagraph.\@arabic\c@subparagraph}

```

The `\partpage` options allows you to print a standard part page in article mode.

```

1217 \ifsuftesi@partpage
1218   \relax
1219   \else

```

In article mode the `\part` command is similar to a `\section` but with more vertical space before and after.

```

1220 \titleclass{\part}{straight}
1221 \titlespacing*{\part}{0ex}{2\sectionsep}{2\sectionsep}[0ex]
1222 \fi
1223 \ifsuftesi@numparpart
1224 \titleformat{\part}[display]
1225   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1226   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1227   {2ex}
1228   {\SUF@PART@StyleSwitch}
1229 \else
1230 \titleformat{\part}[hang]
1231   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1232   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1233   {1em}
1234   {\SUF@PART@StyleSwitch}
1235 \fi
1236 \else

```

The default ‘book’ mode

```

1237 \ifsuftesi@numparpart
1238 \titleformat{\part}[display]
1239   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1240   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1241   {2ex}
1242   {\SUF@PART@StyleSwitch}
1243 \else
1244 \titleformat{\part}[hang]
1245   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1246   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1247   {1em}
1248   {\SUF@PART@StyleSwitch}
1249 \fi
1250 \fi
1251

```

`\paragraph`

```

1252 \titleformat{\paragraph}[runin]
1253 {}
1254 {\theparagraph}
1255 {.5em}
1256 {\itshape}
1257 [{.}\hspace*{1em}]
1258 \titlespacing*{\paragraph}{.5\sectionsep}{.5\sectionsep}

```

`\subparagraph`

```

1259 \titleformat{\subparagraph}[runin]

```

```

1260  {}
1261  {\thesubparagraph}
1262  {.5em}
1263  {}
1264  [{}]\hspace*{1em}]
1265 \titlespacing*{\subparagraph}{\parindent}{.5\sectionsep}{.5\sectionsep}

The biblatex package uses the book class definitions of bibliography and list of shorthands, so we must
redefine them according to the styles of suftesi, which does not use uppercase letters in the headings.

1266 \ifsuftesi@article
1267 \AtBeginDocument{%
1268 \@ifpackageloaded{biblatex}{%
1269   \defbibheading{bibliography}[\refname]{%
1270     \section*{#1}%
1271     \markboth{#1}{#1}%
1272   \defbibheading{shorthands}[\losname]{%
1273     \section*{#1}%
1274     \markboth{#1}{#1}%
1275   \defbibheading{bibintoc}[\refname]{%
1276     \section*{#1}%
1277     \addcontentsline{toc}{section}{#1}%
1278     \markboth{#1}{#1}%
1279   \defbibheading{losintoc}[\losname]{%
1280     \section*{#1}%
1281     \addcontentsline{toc}{section}{#1}%
1282     \markboth{#1}{#1}%
1283   \defbibheading{bibnumbered}[\refname]{%
1284     \section{#1}%
1285     \if@twoside\markright{#1}\fi%
1286   \defbibheading{losnumbered}[\losname]{%
1287     \section{#1}%
1288     \if@twoside\markright{#1}\fi%
1289   \defbibheading{subbibliography}[\refname]{%
1290     \subsection*{#1}%
1291   \defbibheading{subbibintoc}[\refname]{%
1292     \subsection*{#1}%
1293     \addcontentsline{toc}{subsection}{#1}%
1294   \defbibheading{subbibnumbered}[\refname]{%
1295     \subsection{#1}}%
1296     \relax%
1297 }%
1298 \else
1299 \AtBeginDocument{%
1300 \@ifpackageloaded{biblatex}{%
1301   \defbibheading{bibliography}[\bibname]{%
1302     \chapter*{#1}%
1303     \markboth{#1}{#1}%
1304   \defbibheading{shorthands}[\losname]{%
1305     \chapter*{#1}%
1306     \markboth{#1}{#1}%
1307   \defbibheading{bibintoc}[\bibname]{%
1308     \chapter*{#1}%
1309     \addcontentsline{toc}{chapter}{#1}%
1310     \markboth{#1}{#1}%
1311   \defbibheading{losintoc}[\losname]{%
1312     \chapter*{#1}%
1313     \addcontentsline{toc}{chapter}{#1}%
1314     \markboth{#1}{#1}%
1315   \defbibheading{bibnumbered}[\bibname]{%
1316     \chapter{#1}%
1317     \if@twoside\markright{#1}\fi%
1318   \defbibheading{losnumbered}[\losname]{%
1319     \chapter{#1}%
1320     \if@twoside\markright{#1}\fi%
1321   \defbibheading{subbibliography}[\refname]{%
1322     \section*{#1}%
1323     \if@twoside\markright{#1}\fi%

```

```

1324 \defbibheading{subbibintoc}[\refname]{%
1325   \section*{\#1}%
1326   \addcontentsline{toc}{section}{\#1}%
1327   \if@twoside\markright{\#1}\fi}
1328 \defbibheading{subbibnumbered}[\refname]{%
1329   \section{\#1}}}
1330   {\relax}%
1331 }%
1332 \fi

```

6.14 Title page

\title The new \title command has an optional argument which can be used in the headers.

```

1333 \renewcommand*{\title}[2][]{\gdef\@headtitle{\#1}\gdef\@title{\#2}}
1334   \edef\title{\noexpand\@dblarg
1335   \expandafter\noexpand\csname\string\title\endcsname}
1336   \def\@headtitle{--missing title--%
1337     \protect\ClassWarningNoLine{suftesi}{%
1338       No \string\title\space given \MessageBreak%
1339       See the class documentation for explanation}}
1340   \def\@title{--missing title--%
1341     \protect\ClassWarningNoLine{suftesi}{%
1342       No \string\title\space given\MessageBreak%
1343       See the class documentation for explanation}}
1344   \def\@author{--missing author--%
1345     \protect\ClassWarningNoLine{suftesi}{%
1346       No \string\author\space given\MessageBreak%
1347       See the class documentation for explanation}}

```

\maketitle For \titlepage (default) option:

```

1348 \if@titlepage% titlepage
1349   \renewcommand\maketitle{\begin{titlepage}%
1350   \let\footnotesize\small
1351   \let\footnoterule\relax
1352   \let \footnote \thanks
1353   \renewcommand\thefootnote{@fnsymbol\c@footnote}%
1354   \null\vfil
1355   \vskip 60\p@
1356   \begin{center}%
1357     {\SUF@chaptersize\color{sufred}\sffamily%
1358      \ifsuftesi@smallcapschap%
1359        \SUF@titlesmallcaps{\@title}%
1360        \else
1361          \ifsuftesi@article
1362            \ifsuftesi@smallcapssec
1363              \SUF@titlesmallcaps{\@title}%
1364              \else
1365                \@title
1366                \fi
1367                \else
1368                  \@title
1369                  \fi
1370                  \fi\par}%
1371   \vskip 3em%
1372   {\small\lineskip .75em%
1373     \begin{tabular}[t]{c}%
1374       \author
1375     \end{tabular}\par}%
1376   \vskip 1.5em%
1377   {\small\@date\par}%
1378   \end{center}\par
1379   \thanks
1380   \vfil\null
1381   \end{titlepage}%
1382   \setcounter{footnote}{0}%
1383   \global\let\thanks\relax

```

```

1384 \global\let\maketitle\relax
1385 \global\let{@thanks}@empty
1386   \global\let{@date}@empty
1387 \global\let\date\relax
1388 \global\let\and\relax

```

\standardtitle Reproduces the standard \maketitle style:

```

1389 \newcommand\standardtitle{\begin{titlepage}%
1390   \let\footnotesize\small
1391   \let\footnoterule\relax
1392   \let \footnote \thanks
1393   \null\vfil
1394   \vskip 60\p@
1395   \begin{center}%
1396     {\LARGE \atitle \par}%
1397     \vskip 3em%
1398     {\large
1399       \lineskip .75em%
1400       \begin{tabular}[t]{c}%
1401         \author
1402       \end{tabular}\par}%
1403     \vskip 1.5em%
1404     {\large \atdate \par}%
1405   \end{center}\par
1406   \atthanks
1407   \vfild\null
1408   \end{titlepage}%
1409   \setcounter{footnote}{0}%
1410   \global\let\thanks\relax
1411   \global\let\maketitle\relax
1412   \global\let{@thanks}@empty
1413   \global\let{@date}@empty
1414   \global\let\date\relax
1415   \global\let\and\relax
1416 \else

```

\maketitle For notitlepage option:

```

1417 \renewcommand\maketitle{\par
1418   \begingroup
1419     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1420     \def\@makefnmark{\rlap{\textsuperscript{\normalfont\@thefnmark}}}%
1421     \long\def\@makefntext##1{\parindent 1em\noindent
1422       \hb@xt@1.8em{%
1423         \hss\textsuperscript{\normalfont\@thefnmark}##1}%
1424       \if@twocolumn
1425         \ifnum \col@number=\@ne
1426           \maketitle
1427         \else
1428           \twocolumn[\maketitle]%
1429         \fi
1430       \else
1431         \newpage
1432         \global\@topnum\z@% Prevents figures from going at top of page.
1433         \maketitle
1434       \fi
1435       \thispagestyle{plain}\@thanks
1436     \endgroup
1437     \setcounter{footnote}{0}%
1438     \global\let\thanks\relax
1439     \global\let\maketitle\relax
1440     \global\let\@maketitle\relax
1441     \global\let\@thanks\@empty
1442     \global\let\@date\@empty
1443     \global\let\date\relax
1444     \global\let\and\relax
1445     \def\@maketitle{%
1446       \newpage

```

```

1447 \null
1448 \vskip 2em%
1449 \begin{center}%
1450 \let \footnote \thanks
1451 {\SUF@chaptersize\color{sufred}\sffamily%
1452 \if suftesi@smallcapschap%
1453 \SUF@titlesmallcaps{\@title}%
1454 \else
1455 \if suftesi@article
1456 \if suftesi@smallcapssec%
1457 \SUF@titlesmallcaps{\@title}%
1458 \else
1459 \atitle
1460 \fi
1461 \else
1462 \atitle
1463 \fi
1464 \fi\par}%
1465 \vskip 1.5em%
1466 {\small\lineskip .5em%
1467 \begin{tabular}[t]{c}%
1468 \author\par
1469 \end{tabular}\par}%
1470 \vskip 1em%
1471 {\small\@date\par}%
1472 \end{center}%
1473 \par
1474 \vskip 1.5em}

```

\standardtitle Reproduces the standard \maketitle style:

```

1475 \newcommand\standardtitle{\par
1476 \begingroup
1477 \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1478 \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1479 \long\def\@makefntext##1{\parindent 1em\noindent
1480 \hb@xt@1.8em{%
1481 \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
1482 \if@twocolumn
1483 \ifnum \col@number=\@ne
1484 \@standardmaketitle
1485 \else
1486 \twocolumn[\@standardmaketitle]%
1487 \fi
1488 \else
1489 \newpage
1490 \global\@topnum\z@
1491 \@standardmaketitle
1492 \fi
1493 \thispagestyle{plain}\@thanks
1494 \endgroup
1495 \setcounter{footnote}{0}%
1496 \global\let\thanks\relax
1497 \global\let\maketitle\relax
1498 \global\let\@standardmaketitle\relax
1499 \global\let\@thanks\@empty
1500 \global\let\@date\@empty
1501 \global\let\date\relax
1502 \global\let\and\relax}
1503 \def\@standardmaketitle{%
1504 \newpage
1505 \null
1506 \vskip 2em%
1507 \begin{center}%
1508 \let \footnote \thanks
1509 {\LARGE \atitle \par}%
1510 \vskip 1.5em%
1511 {\large

```

```

1512      \lineskip .5em%
1513      \begin{tabular}[t]{c}%
1514          \author
1515      \end{tabular}\par}%
1516      \vskip 1em%
1517      {\large \@date}%
1518  \end{center}%
1519  \par
1520  \vskip 1.5em}
1521 \fi

```

6.15 The collection document structure

```

1522 \ifsuftesi@collection
1523 \newcounter{journalnumber}
1524 \newcounter{journalvolume}
1525 \newcounter{issue}
1526 \newcounter{title}
1527 \setcounter{title}{1}
1528 \setcounter{journalnumber}{0}
1529 \setcounter{tocdepth}{0}
1530 \def\journalname#1{\gdef\@journalname{#1}}
1531   \def\@journalname{\@latex@warning@no@line{%
1532     No \noexpand\journalname given}}
1533 \def\issn#1{\gdef\@issn{#1}}
1534   \def\@issn{\@latex@warning@no@line{%
1535     No \noexpand\issn given}}
1536 \def\doi#1{\gdef\@doi{#1}}
1537   \def\@doi{\@latex@warning@no@line{%
1538     No \noexpand\doi given}}
1539 \def\journalvolume#1{\gdef\@journalvolume{#1}}
1540   \def\@journalvolume{\@latex@warning@no@line{%
1541     No \noexpand\journalvolume given}}
1542 \def\journalnumber#1{\gdef\@journalnumber{#1}}
1543   \def\@journalnumber{\@latex@warning@no@line{%
1544     No \noexpand\journalnumber given}}
1545 \def\issue#1{\gdef\@issue{#1}}
1546   \def\@issue{\@latex@warning@no@line{%
1547     No \noexpand\issue given}}
1548 \def\journalyear#1{\gdef\@journalyear{#1}}
1549   \def\@journalyear{\@latex@warning@no@line{%
1550     No \noexpand\journalyear given}}
1551 \def\journalwebsite#1{\gdef\@journalwebsite{\url{#1}}}
1552   \def\@journalwebsite{\@latex@warning@no@line{%
1553     No \noexpand\journalwebsite given}}
1554 \def\thanks#1{\footnotemark \protected@xdef\@thanks{%
1555   \@thanks\protect\footnotetext[\the\c@footnote]{#1}}}
1556 \def\fulljournal{\emph{\@journalname} \@journalnumber, %
1557   \@issue{} \@journalyear}
1558 \def\issuename#1{\gdef\@issuename{#1}}
1559 \def\collectiontitle#1{\gdef\@collectiontitle{#1}}
1560   \def\@collectiontitle{\@latex@warning@no@line{%
1561     No \noexpand\collectiontitle given}}
1562 \def\collectioneditor#1{\gdef\@collectioneditor{#1}}
1563   \def\@collectioneditor{\@latex@warning@no@line{%
1564     No \noexpand\collectioneditor given}}
1565 \newcommand*\l@title[2]{%
1566   \ifnum \c@tocdepth >\m@ne
1567     \addpenalty{-\@highpenalty}%
1568     \vskip 1.0ex \@plus\p@
1569     \begingroup
1570       \parindent \z@ \rightskip \@pnumwidth
1571       \parfillskip -\@pnumwidth
1572       \advance\leftskip1em
1573       \hskip -\leftskip

```

```

1574      #1\nobreak%
1575      \ifsuftesi@dottedtoc\dotfill%
1576          \nobreak\hb@xt@{@pnumwidth{\hss #2}\par
1577          \else
1578              \ifsuftesi@raggedtoc%
1579                  \nobreak\hskip1em #2 \hfill\null\par
1580                  \else
1581                      \ifsuftesi@pagelefttoc
1582                          \ClassError{suftesi}
1583                              {\MessageBreak
1584                                  You can not use tocstyle=leftpage\MessageBreak
1585                                      with documentstructure=collection}
1586                          {You can not use tocstyle=leftpage\MessageBreak
1587                                      with documentstructure=collection}
1588                  \else
1589                      \nobreak\hfill #2\par
1590                  \fi
1591          \fi
1592      \fi
1593      \penalty@\highpenalty
1594      \endgroup
1595  \fi}

\maketitle
\@maketitle 1596 \renewcommand\maketitle{\par
1597   \begingroup
1598     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1599     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1600     \long\def\@makefntext##1{\parindent 1em\noindent
1601         \hb@xt@1.8em{%
1602             \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
1603     \if@twocolumn
1604         \ifnum \col@number=\@ne
1605             \@maketitle
1606         \else
1607             \twocolumn[\@maketitle]%
1608         \fi
1609     \else
1610         \newpage
1611         \global\@topnum\z@
1612         \@maketitle
1613     \fi
1614     \thispagestyle{plain}\@thanks
1615   \endgroup
1616   \setcounter{footnote}{0}%
1617   \global\let\@thanks\@empty
1618   \let\thanks\@gobble}
1619 \def\@maketitle{%
1620   \cleardoublepage
1621   \SUF@chaptersize
1622   \SUF@lr@coll@titleSwitch
1623   \let\footnote\thanks
1624   \parindent=0pt
1625   \refstepcounter{title}%
1626   \\\ifsuftesi@reverseauthortitle
1627       \SUF@titlefont@Switch{\@title}%
1628       \else\SUF@authorfont@Switch{\@author}\fi}%
1629 %   \label{begin:\thetitle}%
1630   \begingroup%
1631   \let\thanks\@gobble
1632   \addcontentsline{toc}{title}{\normalfont\@author}\newline%
1633   \itshape\@headtitle}
1634   \endgroup%
1635   \vspace{2ex}\par
1636   \\\ifsuftesi@reverseauthortitle
1637       \SUF@authorfont@Switch{\@author}%
1638       \else

```

```

1639      \SUF@titlefont@Switch{@title}%
1640      \fi\\}
1641      \vskip2.5cm}

\includeart The command to include a paper in the collection.
1642 \newcommand{\includeart}[1]{%
1643   \begingroup
1644   \cleardoublepage
1645   \setcounter{section}{0}
1646   \input{#1}\label{end:\thetitle}
1647   \global\let\@thanks\@empty
1648   \global\let\@author\@empty
1649   \global\let\@headtitle\@empty
1650 \endgroup}

\frontispiece The command to typeset the frontispiece of the collection.
1651 \newcommand{\frontispiece}{%
1652   \thispagestyle{empty}%
1653   \begingroup
1654   \centering
1655   \null\vspace{\stretch{1}}
1656
1657   {\SUF@chaptersize@\collectiontitle\par}
1658   \vskip5ex
1659
1660   \@collectioneditor
1661   \vspace{\stretch{2}}
1662
1663   \@date
1664
1665   \endgroup
1666   \clearpage}

```

In the collection document structure the articles are treated as chapters but you would not need to print in the table of contents all the sections of every article. So first of all we include in the table of contents only the author and the title of each paper:

```
1667 \setcounter{tocdepth}{0}
```

Anyway the sections inside each paper are numbered as in standard articles:

```

1668 \renewcommand{\thesection}{%
1669   \@arabic\c@section}
1670 \renewcommand{\thesubsection}{%
1671   \thesection.\@arabic\c@subsection}
1672 \renewcommand{\thesubsubsection}{%
1673   \thesubsection.\@arabic\c@subsubsection}
1674 \renewcommand{\theparagraph}{%
1675   \thesubsubsection.\@arabic\c@paragraph}
1676 \renewcommand{\thesubparagraph}{%
1677   \theparagraph.\@arabic\c@subparagraph}
1678 \else
1679 \fi

```

6.16 Frontispiece

```

1680 \AtBeginDocument{%
1681   @ifpackagewith{frontespizio}{suftesi}
1682     {\ifsuftesi@periodical
1683       \Margini {5.5cm}{7cm}{4.5cm}{0cm}
1684     \else
1685       \ifsuftesi@compact
1686         \Margini {4.5cm}{7cm}{4.5cm}{0cm}
1687       \else
1688         \ifsuftesi@supercompact
1689           \Margini {4.5cm}{10cm}{6cm}{1cm}
1690         \else
1691           \ifsuftesi@periodicalaureo
1692             \Margini {5.5cm}{7cm}{4.5cm}{0cm}
1693           \fi
1694         \fi
1695       \fi

```

```

1696 \fi}
1697 {\@ifpackageloaded{frontespizio}
1698     {\ifsuftesi@periodical
1699         \Margini {1cm}{7cm}{5cm}{1cm}
1700         \Rientro{1cm}
1701     \else
1702     \ifsuftesi@compact
1703         \Margini {1cm}{7cm}{6cm}{1cm}
1704         \Rientro{1cm}
1705     \else
1706         \ifsuftesi@supercompact
1707             \Margini {1cm}{10cm}{8cm}{1cm}
1708             \Rientro{1cm}
1709     \else
1710         \ifsuftesi@periodicalaureo
1711             \Margini {1cm}{7cm}{5cm}{1cm}
1712             \Rientro{1cm}
1713     \fi
1714     \fi
1715 \fi}
1716 \fi}
1717 {\relax}}

```

theindex

```

1718 \renewenvironment{theindex}
1719     {\if@twocolumn
1720         \@restonecolfalse
1721     \else
1722         \@restonecoltrue
1723     \fi
1724     \ifsuftesi@article
1725         \twocolumn[\section*{\indexname}]%
1726     \else
1727         \twocolumn[\@makeschapterhead{\indexname}]%
1728     \fi
1729     \@mkboth{\indexname}{\indexname}%
1730     \thispagestyle{plain}%
1731     \raggedright%
1732     \parindent\z@
1733     \parskip\z@ \oplus .3\p@\relax
1734     \columnseprule \z@
1735     \columnsep 35\p@
1736     \let\item\idxitem
1737     {\if@restonecol\onecolumn\else\clearpage\fi}

```

6.17 Appendix

```

\appendicesname
\appendixpage 1738 \newcommand{\appendicesname}[1]{\def\SUF@appendices{#1}}
1739     \appendicesname{Appendici}
1740     \newcommand{\appendixpage}{\SUF@appendixpage}
1741 \def\SUF@appendixpage{%
1742     \@mainmattertrue
1743     \titlecontents{part}
1744         [0em]
1745         {\addvspace{3ex}}
1746     {}
1747     {}
1748     {}
1749     [\addvspace{1ex}]
1750 \let\contentspage\relax
1751     \cleardoublepage
1752         \thispagestyle{empty}
1753         \addcontentsline{toc}{part}{\SUF@appendices}
1754     \begingroup
1755         \centering

```

```

1756          \null\vfil
1757          {\LARGE\SUF@appendices\par}
1758          \vfil
1759      \endgroup
1760      \cleardoublepage
1761 \titlecontents{part}
1762     [0em]
1763     {\addvspace{3ex}\partname~}
1764     {\makebox[\SUF@label@part][1]{%
1765       \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}
1766   {}
1767   {}
1768   [\addvspace{1ex}]
1769 }

\appendix
1770 \ifsuftesi@sufelements
1771 \renewcommand\appendix{\par
1772   \setcounter{chapter}{0}%
1773   \setcounter{section}{0}%
1774   \gdef\@chapapp{\appendixname}%
1775   \gdef\thechapter{@Alph\c@chapter}
1776   \titleformat{\chapter}[block]
1777     {\vskip-22pt}%
1778     {\small%
1779       \SUF@titlesmallcaps{\appendixname}\~\Alph{chapter}:\hskip.5em}
1780     {0pt}
1781     {\small\SUF@titlesmallcaps}
1782     [\rule{\textwidth}{.4pt}]
1783     \titlespacing*{\chapter}{0em}{-16pt}{10pt}[0em]
1784 \else
1785   \ifsuftesi@article
1786     \renewcommand\appendix{\par
1787       \setcounter{section}{0}%
1788       \setcounter{subsection}{0}%
1789       \gdef\thesection{@Alph\c@section}%
1790       \gdef\SUF@thesection{@Alph\c@section}}
1791 \else
1792   \renewcommand\appendix{\par
1793     \setcounter{chapter}{0}%
1794     \setcounter{section}{0}%
1795     \gdef\@chapapp{\appendixname}%
1796     \gdef\thechapter{@Alph\c@chapter}%
1797     \gdef\SUF@thechapter{@Alph\c@chapter}}
1798 \fi
1799 \fi

```

6.18 Headings

```

1800 \RequirePackage{fancyhdr}
1801   \pagestyle{fancy}
1802   \renewcommand{\headrulewidth}{0pt}
1803   \renewcommand{\footnoterule}{}
1804 \def\SUF@versionstring{\texttt{\versionstring} \today}

```

The elements headers

```

1805 \ifsuftesi@elementsheader%
1806   \renewcommand{\chaptermark}[1]{\markboth{\#1}{\#1}}
1807   \renewcommand{\sectionmark}[1]{\markright{\#1}}
1808 \fancypagestyle{elements}{%
1809   \setlength{\unitlength}{1pt}
1810   \fancyhf{%
1811     \fancyfoot[LE,RO]{\thepage}
1812     \fancyhead[RO]{%
1813       \begin{picture}(0,0)
1814         \put(0,-104){%
1815           \hskip\marginparsep

```

```

1816      \parbox[t]{\marginparwidth}{\itshape\raggedright\leftmark} }%
1817      \end{picture} }
1818 \fancyhead[LE]{%
1819     \begin{picture}(0,0)
1820         \put(0,-104){%
1821             \hspace{-\dimexpr\marginparwidth+\marginparsep}
1822             \parbox[t]{\marginparwidth}{\itshape\raggedleft\rightmark} }%
1823     \end{picture} }%
1824 }%
1825 \else

```

The default headers

```

1826 \renewcommand{\chaptermark}[1]{%
1827     \markboth{\chapertitlename\ \SUF@thechapter}{#1}}
1828 \ifsuftesi@article
1829     \renewcommand{\sectionmark}[1]{\markright{\SUF@thesection.\ #1}}
1830     \else
1831     \renewcommand{\sectionmark}[1]{}
1832 \fi
1833 \fi

```

The plain style

```
1834 \fancypagestyle{plain}{\fancyhf{}}
```

The sufplain style

```

1835 \fancypagestyle{sufplain}{%
1836     \fancyhf{}%
1837     \fancyfoot[RE,LO]{%
1838         \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
1839     \fancyfoot[C]{\footnotesize\SUF@thepage}}

```

The centerheader style

```

1840 \fancypagestyle{centerheader}{%
1841     \fancyhf{}%
1842     \fancyfoot[RE,LO]{%
1843         \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
1844     \fancyhead[CO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
1845     \fancyhead[CE]{\footnotesize\xheadbreakfalse%
1846         \SUF@LR@MarkSwitch}
1847     \fancyfoot[C]{\footnotesize\SUF@thepage}%
1848 }%

```

The sufdefault style

```

1849 \fancypagestyle{sufdefault}{%
1850     \fancyhf{}%
1851     \fancyfoot[RE,LO]{%
1852         \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
1853     \fancyhead[LE,RO]{\footnotesize\SUF@thepage}
1854     \fancyhead[LO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
1855     \fancyhead[RE]{\footnotesize\xheadbreakfalse%
1856         \SUF@LR@MarkSwitch}
1857 }%
1858 %
1859 \ifsuftesi@article
1860 \ifsuftesi@authortitle
1861 \def\SUF@LR@MarkSwitch{\SUF@leftmark}
1862 \else
1863 \def\SUF@LR@MarkSwitch{\SUF@rightmark}
1864 \fi
1865 \else
1866     \def\SUF@LR@MarkSwitch{\SUF@leftmark}
1867 \fi
1868 \def\SUF@leftrightmark{%
1869     \if@mainmatter\leftmark\else\rightmark\fi}

```

Setting the default page style:

```
1870 \pagestyle{sufdefault}
1871 \ifsuftesi@centerheader\pagestyle{centerheader}\else\fi
1872 \ifsuftesi@sufplain\pagestyle{sufplain}\else\fi
1873 \ifsuftesi@elementsheader\pagestyle{elements}\else\fi
```

6.19 Text elements

6.19.1 Block Quotations

quotation New environments for block quotations according to a popular Italian style. The font size is the same of the footnotes and the margins are set to `\parindent`.

```
1874 \renewenvironment{quotation}
1875     {\list{}{\listparindent\parindent%
1876         \itemindent \listparindent
1877         \leftmargin \parindent
1878         \SUF@quote@style
1879         \parsep \z@ \plus\p@}%
1880         \item\relax%
1881         \SUF@quotation@size%
1882         \noindent\ignorespaces}
1883     {\endlist}
1884 \renewenvironment{quote}
1885     {\list{}{\leftmargin \parindent
1886         \SUF@quote@style}%
1887         \item\relax%
1888         \SUF@quotation@size}\ignorespaces?
1889     {\endlist}
1890 \renewenvironment{verse}
1891     {\let\\@centercr
1892     \list{}{\itemsep \z@
1893         \itemindent -1.5em%
1894         \listparindent\itemindent
1895         \rightmargin \leftmargin
1896         \advance\leftmargin 1.5em}%
1897         \item\relax%
1898         \SUF@quotation@size}
1899     {\endlist}
```

The fewfootnotes option Enable only with three footnotes per page maximum.

```
1900 \ifsuftesi@fewfootnotes
1901 \AtBeginDocument{%
1902 \def\fnsymbol#1{\ensuremath{\ifcase#1\or^*\or^{*}{*}\or^{*}{*}\or^{*}{*}\or%
1903 \ClassError{suftesi}%
1904 {Too many footnotes}\MessageBreak
1905 Remove the class option 'fewfootnote'%
1906 {Too many footnotes}\MessageBreak
1907 Remove the class option 'fewfootnote'%
1908 \else\@ctrerr\fi}}}
1909 \def\thefootnote{\fnsymbol{c@footnote}%
1910 \else\fi}
```

\xfootnote Prints a footnote with discretionary symbol give in the first argument.

```
1911 \newcommand*\xfootnote[1][*]{%
1912     \xdef\@thefnmark{#1}%
1913     \@footnotemark\@footnotetext}
```

6.19.2 Marginal notes

\marginpar The `\marginpar` command is redefined according to the look of *Classic Thesis* by André Miede (2011). Thanks to Lorenzo Pantieri and Enrico Gregorio.

```
1914 \def\SUF@mpsetup{%
```

In the *Elements* (i.e. with `elements` option) the marginal notes are printed in roman, but I prefer italic shape for the other options:

```

1915     \ifsuftesi@elementsheader\relax
1916         \else\itshape\fi
1917     \footnotesize%
1918     \parindent=0pt \lineskip=0pt \lineskiplimit=0pt %
1919     \tolerance=2000 \hyphenpenalty=300 \exhyphenpenalty=300%
1920     \doublehyphendemerits=100000%
1921     \finalhyphendemerits=\doublehyphendemerits}
1922     \let\oldmarginpar\marginpar
1923     \renewcommand{\marginpar}[1]{\oldmarginpar%
1924         [\SUF@mpsetup\raggedleft\hspace{0pt}{#1}]%
1925         {\SUF@mpsetup\raggedright\hspace{0pt}{#1}}}}

```

Redefine an internal command of the `todonotes` package in order to use the class-specific marginal notes when this package is loaded. This redefinition simply substitute `\oldmarginpar` to `\marginpar`:

```

1926 \AtBeginDocument{%
1927     @ifpackageloaded{todonotes}{%
1928         \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
1929             \begin{tikzpicture}[remember picture, overlay, baseline=-0.75ex]%
1930                 \node [coordinate] (inText) {};%}
1931         \end{tikzpicture}}%
1932         \oldmarginpar[{\% Draw note in left margin
1933             \@todonotes@drawMarginNote%
1934             \@todonotes@drawLineToLeftMargin%
1935         }]{\% Draw note in right margin
1936             \@todonotes@drawMarginNote%
1937             \@todonotes@drawLineToRightMargin%
1938     }%
1939     }%
1940 }
1941 {\relax}

```

6.19.3 Abstract

quotation This is the macro that defines the `abstract` environment in `article` class. In `suftesi` it simply prints the abstract name in roman font:

```

1942 \ifsuftesi@collection
1943     \newenvironment{abstract}{%
1944         \if@twocolumn
1945             \section*{\abstractname}%
1946         \else
1947             \small
1948             \begin{center}%
1949                 {\abstractname}\vspace{-.5em}\vspace{\z@}%
1950             \end{center}%
1951             \quotation
1952             \fi
1953             {\if@twocolumn\else\endquotation\fi}
1954 \else
1955 \if@titlepage
1956     \newenvironment{abstract}{%
1957         \titlepage
1958         \null\vfil
1959         @beginparpenalty@lowpenalty
1960         \begin{center}%
1961             \abstractname
1962             @endparpenalty@M
1963             \end{center}%
1964             \par\vfil\null\endtitlepage}
1965 \else
1966     \newenvironment{abstract}{%
1967         \if@twocolumn
1968             \section*{\abstractname}%
1969         \else
1970             \small
1971             \begin{center}%
1972                 {\abstractname}\vspace{-.5em}\vspace{\z@}%

```

```

1973      \end{center}%
1974      \quotation
1975      \fi}
1976      {\if@twocolumn\else\endquotation\fi}
1977 \fi
1978 \fi
1979 \newcommand{\abstractname}{Abstract}
```

6.19.4 Colophon

\colophon Some useful commands to print a colophon or a copyright notice.

```

1980 \newcommand{\colophon}[3][]{%
1981   \thispagestyle{empty}
1982   \null
1983   \vfill
1984   \def\next{\#2}
1985   \ifx\next\@empty\else
1986     \noindent Copyright \copyright{} \the\year~#2\|[1ex]
1987     Tutti i diritti riservati
1988   \fi
1989   \vfill
1990   {\small\noindent Questo lavoro \`e stato composto con \LaTeX{}%
1991   \def\next{\#1}
1992   \ifx\next\@empty\else su #1
1993   \fi usando la classe \textsf{suftesi} di
1994   Ivan Valbusa\index{Valbusa, Ivan}. #3\par}
1995   \cleardoublepage}
```

\bookcolophon

```

1996 \newcommand{\bookcolophon}[2]{%
1997   \thispagestyle{empty}
1998   \null
1999   \vfill
2000   \noindent #1
2001   \vfill
2002   {\small\noindent #2\par}
2003   \cleardoublepage}
```

\artcolophon

```

2004 \newcommand{\artcolophon}[1]{%
2005 \thispagestyle{empty}
2006 \null
2007 \vfill
2008 {\small\noindent #1\par}}
```

\finalcolophon

```

2009 \newcommand{\finalcolophon}[1]{%
2010 \thispagestyle{empty}
2011 \null\vspace*{\stretch{1}}
2012 \begin{center}
2013 \begin{minipage}{.5\textwidth}
2014 \centering\small #1
2015 \end{minipage}
2016 \end{center}
2017 \vspace*{\stretch{6}}}
```

\FSPLcolophon This command is defined only for the style=FSPL* options.

```

2018 \ifsuftesi@FSPL
2019 \newcommand{\FSPLcolophon}[1][\the\year]{%
2020 \begingroup
2021 \thispagestyle{empty}
2022 \null\vspace{\stretch{1}}
2023 \noindent \hspace{-.5em}\cc #1 \@author%
2024 \vskip1ex
2025
2026 \small\noindent This work is licensed under the Creative Commons
2027 Attribution-NonCommercial-NoDerivs 3.0 Unported License.
```

```

2028 To view a copy of this license,
2029 visit http://creativecommons.org/licenses/by-nc-nd/3.0/.
2030
2031 \endgroup
2032
2033 \begingroup
2034 \footnotesize
2035
2036 \null\vspace{\stretch{1}}
2037
2038 \noindent Typeset with \LaTeX{} in collaboration with the Joint Project
2039 \emph{Formal Style for PhD Theses with \LaTeX{}} (University of Verona,
2040 Italy) using the \textsf{suftesi} class by Ivan Valbusa. The text face
2041 is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by
2042 Janusz M. Nowacki.
2043
2044 \endgroup
2045
2046 \clearpage}
2047 \else
2048 \def\FSPLcolophon{%
2049   \ClassError{suftesi}{%
2050     {\noexpand\FSPLcolophon is defined\MessageBreak
2051      only for the FSPL styles}%
2052     {\noexpand\FSPLcolophon is defined\MessageBreak
2053      only for the FSPL styles}}%
2054 \fi

```

6.20 Toc, lof, lot

```
2055 \RequirePackage{titletoc}
```

All the lengths depend on \SUF@label@chap so we define this first.

```
2056 \newlength\SUF@label@chap
2057 \setlength\SUF@label@chap{.5em}
```

\toclabelwidth \toclabelwidth is provided to adjust the label width in the table of contents:

```
2058 \newcommand*{\toclabelwidth}[2]{%
2059   \addtolength{\csname SUF@label@#1\endcsname}{#2}%
2060   \addtolength{\csname SUF@tocindent@#1\endcsname}{#2}}%
2061 \newcommand{\toclabelspace}{%
2062   \ClassError{suftesi}{%
2063     {\MessageBreak
2064       \noexpand\toclabelspace is not more defined\MessageBreak
2065       Use \noexpand\toclabelwidth instead.\MessageBreak
2066       See package documentation for details}%
2067     {\MessageBreak
2068       \noexpand\toclabelspace is not more defined\MessageBreak
2069       Use \noexpand\toclabelwidth instead.\MessageBreak
2070       See package documentation for details}}}
```

\SUF@tochang This macro controls the space between page number and chapter label using the tocpageleft option:

```
2071 \newlength{\SUF@tochang}
2072 \setlength{\SUF@tochang}{3em}
2073 \AtBeginDocument{
2074   \newlength\SUF@label@part
2075   \newlength\SUF@label@sec
2076   \newlength\SUF@label@subsec
2077   \newlength\SUF@label@subsubsec
2078   \newlength\SUF@label@par
2079   \newlength\SUF@label@subpar
2080   \newlength\SUF@label@fig
2081   \newlength\SUF@label@tab
2082   \setlength\SUF@label@part{%
2083     {\SUF@label@chap}%
2084     \setlength\SUF@label@sec{%
2085       {\dimexpr(\SUF@label@chap+.5em)}}%
2086     \setlength\SUF@label@subsec{}}
```

```

2087      {\dimexpr(\SUF@label@sec+.5em)}
2088 \setlength{\SUF@label@subsubsec}
2089      {\dimexpr(\SUF@label@subsec+.5em)}
2090 \setlength{\SUF@label@par}
2091      {\dimexpr(\SUF@label@subsubsec+.5em)}
2092 \setlength{\SUF@label@subpar}
2093      {\dimexpr(\SUF@label@par+.5em)}
2094 \setlength{\SUF@label@fig}
2095      {\SUF@label@sec}
2096 \setlength{\SUF@label@tab}
2097      {\SUF@label@sec}
2098 }

Part in article mode
2099 \titlecontents{part}
2100 [0em]
2101 {\addvspace{3ex}\partname\hspace*{.5em}}
2102 {\makebox[\SUF@label@part][1]{%
2103     \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}
2104 {}
2105 {}
2106 [\addvspace{1ex}]

6.20.1 'tocpageleft' toc

2107 \ifsuftesi@pagelefttoc

```

\contentsmargin First we reset the right margin to zero:

```

2108 \contentsmargin{0pt}
2109 \AtBeginDocument{
2110 \newlength{\SUF@tochang@chap}
2111 \newlength{\SUF@tochang@sec}
2112 \newlength{\SUF@tochang@subsec}
2113 \newlength{\SUF@tochang@subsubsec}
2114 \newlength{\SUF@tochang@par}
2115 \newlength{\SUF@tochang@subpar}
2116 \newlength{\SUF@tochang@fig}
2117 \newlength{\SUF@tochang@tab}
2118 \newlength{\SUF@addto@tochang@chap}
2119 \newlength{\SUF@addto@tochang@sec}
2120 \newlength{\SUF@addto@tochang@subsec}
2121 \newlength{\SUF@addto@tochang@subsubsec}
2122 \newlength{\SUF@addto@tochang@par}
2123 \newlength{\SUF@addto@tochang@subpar}
2124 \newlength{\SUF@addto@tochang@fig}
2125 \newlength{\SUF@addto@tochang@tab}
2126 \setlength{\SUF@tochang@chap}
2127      {\dimexpr(1em+\SUF@tochang+\SUF@label@chap+1em)}
2128 \setlength{\SUF@tochang@sec}
2129      {\dimexpr(\SUF@tochang@chap+\SUF@label@sec+1em)}
2130 \setlength{\SUF@tochang@subsec}
2131      {\dimexpr(\SUF@tochang@sec+\SUF@label@subsec+1em)}
2132 \setlength{\SUF@tochang@subsubsec}
2133      {\dimexpr(\SUF@tochang@subsec+\SUF@label@subsubsec+1em)}
2134 \setlength{\SUF@tochang@par}
2135      {\dimexpr(\SUF@tochang@subsubsec+\SUF@label@par+1em)}
2136 \setlength{\SUF@tochang@subpar}
2137      {\dimexpr(\SUF@tochang@par+\SUF@label@subpar+1em)}
2138 \setlength{\SUF@tochang@fig}
2139      {\SUF@tochang@chap}
2140 \setlength{\SUF@tochang@tab}
2141      {\SUF@tochang@chap}
2142 \setlength{\SUF@addto@tochang@chap}
2143      {\SUF@tochang}
2144 \setlength{\SUF@addto@tochang@sec}
2145      {\dimexpr(\SUF@addto@tochang@chap+\SUF@label@sec+.5em)}
2146 \setlength{\SUF@addto@tochang@subsec}
2147      {\dimexpr(\SUF@addto@tochang@sec+\SUF@label@subsec+.5em)}

```

```

2148 \setlength{\SUF@addto@tochang@subsubsec}
2149   {\dimexpr(\SUF@addto@tochang@subsec+\SUF@label@subsubsec+.5em)}
2150 \setlength{\SUF@addto@tochang@par}
2151   {\dimexpr(\SUF@addto@tochang@subsubsec+\SUF@label@par+.5em)}
2152 \setlength{\SUF@addto@tochang@subpar}
2153   {\dimexpr(\SUF@addto@tochang@par+\SUF@label@subpar+.5em)}
2154 \setlength{\SUF@addto@tochang@fig}
2155   {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2156 \setlength{\SUF@addto@tochang@tab}
2157   {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2158 }

TOC entries

2159 \titlecontents{chapter}
2160   [\SUF@tochang@chap]
2161   {\addvspace{2ex}}
2162   {\hskip-\SUF@tochang@chap%
2163     \makebox[1em][1]{\thecontentspage}%
2164     \hskip\SUF@addto@tochang@chap%
2165       \makebox[\SUF@label@chap][1]{%
2166         \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}%
2167   {\hskip-\SUF@tochang@chap%
2168     \makebox[1em][1]{\thecontentspage}%
2169     \hskip\SUF@addto@tochang@chap}
2170   {}
2171   [\addvspace{1ex}]
2172 \titlecontents{section}
2173   [\SUF@tochang@sec]
2174   {}
2175   {\hskip-\SUF@tochang@sec%
2176     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@sec%
2177       \makebox[\SUF@label@sec][1]{%
2178         \ifsuftesi@article\SUF@toclabelnum%
2179           \else\fi\thecontentslabel}\hspace*{1em}}%
2180   {\hskip-\SUF@tochang@sec%
2181     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@sec}
2182   {}

2183 \titlecontents{subsection}
2184   [\SUF@tochang@subsec]
2185   {}
2186   {\hskip-\SUF@tochang@subsec%
2187     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@subsec%
2188       \makebox[\SUF@label@subsec][1]{\thecontentslabel}\hspace*{1em}}%
2189   {\hskip-\SUF@tochang@subsec%
2190     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@subsec}
2191   {}

2192 \titlecontents{subsubsection}
2193   [\SUF@tochang@subsubsec]
2194   {}
2195   {\hskip-\SUF@tochang@subsubsec%
2196     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@subsubsec%
2197       \makebox[\SUF@label@subsubsec][1]{\thecontentslabel}\hspace*{1em}}%
2198   {\hskip-\SUF@tochang@subsubsec%
2199     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@subsubsec}
2200   {}

2201 \titlecontents{paragraph}
2202   [\SUF@tochang@par]
2203   {}
2204   {\hskip-\SUF@tochang@par%
2205     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@par%
2206       \makebox[\SUF@label@par][1]{\thecontentslabel}\hspace*{1em}}%
2207   {\hskip-\SUF@tochang@par%
2208     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@par}
2209   {}

2210 \titlecontents{subparagraph}
2211   [\SUF@tochang@subpar]
2212   {}

```

```

2213   {\hskip-\SUF@tochang@subpar%
2214     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@subpar%
2215     \makebox[\SUF@label@subpar][1]{\thecontentslabel}\hspace*{1em}}
2216   {\hskip-\SUF@tochang@subpar%
2217     \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@subpar}
2218   {}
2219 \titlecontents{figure}
2220 [\SUF@tochang@fig]
2221 {}
2222 {\hskip-\SUF@tochang@fig%
2223   \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@fig%
2224   \makebox[\SUF@label@tab][1]{\thecontentslabel}\hspace*{1em}}
2225 {}
2226 {}
2227 \titlecontents{table}
2228 [\SUF@tochang@tab]
2229 {}
2230 {\hskip-\SUF@tochang@tab%
2231   \makebox[1em][1]{\thecontentspage}\hskip\SUF@addto@tochang@tab%
2232   \makebox[\SUF@label@tab][1]{\thecontentslabel}\hspace*{1em}}
2233 {}
2234 {}
2235 \else

```

6.20.2 Default toc

```

2236 \AtBeginDocument{
2237 \newlength\SUF@tocindent@chap
2238 \newlength\SUF@tocindent@sec
2239 \newlength\SUF@tocindent@subsec
2240 \newlength\SUF@tocindent@subsubsec
2241 \newlength\SUF@tocindent@par
2242 \newlength\SUF@tocindent@subpar
2243 \newlength\SUF@tocindent@fig
2244 \newlength\SUF@tocindent@tab
2245 \ifsuftesi@article
2246 \setlength\SUF@tocindent@sec
2247   {\dimexpr(\SUF@label@chap+1.5em)}
2248 \setlength\SUF@tocindent@subsec
2249   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2250 \setlength\SUF@tocindent@subsubsec
2251   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2252 \setlength\SUF@tocindent@par
2253   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2254 \setlength\SUF@tocindent@subpar
2255   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2256 \else
2257 \setlength\SUF@tocindent@chap
2258   {\dimexpr(\SUF@label@chap+1em)}
2259 \setlength\SUF@tocindent@sec
2260   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec+1em)}
2261 \setlength\SUF@tocindent@subsec
2262   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2263 \setlength\SUF@tocindent@subsubsec
2264   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2265 \setlength\SUF@tocindent@par
2266   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2267 \setlength\SUF@tocindent@subpar
2268   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2269 \fi
2270 \setlength\SUF@tocindent@fig
2271   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2272 \setlength\SUF@tocindent@tab
2273   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2274 }

```

TOC entries

```

2275 \titlecontents{chapter}
2276   [ \SUF@tocindent@chap]
2277   {\addvspace{2ex}}
2278   {\hskip-\SUF@tocindent@chap%
2279     \makebox[\SUF@label@chap][1]{\SUF@toclabelnum\thecontentslabel}%
2280     \hspace*{1em}}
2281   {\hskip-\SUF@tocindent@chap}
2282   {\SUF@chaptitlerule\contentspage}
2283   [\addvspace{1ex}]
2284 \titlecontents{section}
2285   [ \SUF@tocindent@sec]
2286   {}
2287   {\hskip-\dimexpr(\SUF@label@sec+1em)%
2288     \makebox[\SUF@label@sec][1]{%
2289       \ifsuftesi@article\SUF@toclabelnum%
2290       \else\fi\thecontentslabel}\hspace*{1em}}
2291   {\hskip-\dimexpr(\SUF@label@sec+1em)}
2292   {\ifsuftesi@article\SUF@chaptitlerule%
2293     \else\SUF@titlerule\fi\contentspage}
2294 \titlecontents{subsection}
2295   [ \SUF@tocindent@subsec]
2296   {}
2297   {\hskip-\dimexpr(\SUF@label@subsec+1em)%
2298     \makebox[\SUF@label@subsec][1]{\thecontentslabel}\hspace*{1em}}
2299   {\hskip-\dimexpr(\SUF@label@subsec+1em)}
2300   {\SUF@titlerule\contentspage}
2301 \titlecontents{subsubsection}
2302   [ \SUF@tocindent@subsubsec]
2303   {}
2304   {\hskip-\dimexpr(\SUF@label@subsubsec+1em)%
2305     \makebox[\SUF@label@subsubsec][1]{\thecontentslabel}\hspace*{1em}}
2306   {\hskip-\dimexpr(\SUF@label@subsubsec+1em)}
2307   {\SUF@titlerule\contentspage}
2308 \titlecontents{paragraph}
2309   [ \SUF@tocindent@par]
2310   {}
2311   {\hskip-\dimexpr(\SUF@label@par+1em)%
2312     \makebox[\SUF@label@par][1]{\thecontentslabel}\hspace*{1em}}
2313   {\hskip-\dimexpr(\SUF@label@par+1em)}
2314   {\SUF@titlerule\contentspage}
2315 \titlecontents{subparagraph}
2316   [ \SUF@tocindent@subpar]
2317   {}
2318   {\hskip-\dimexpr(\SUF@label@subpar+1em)%
2319     \makebox[\SUF@label@subpar][1]{\thecontentslabel}\hspace*{1em}}
2320   {\hskip-\dimexpr(\SUF@label@subpar+1em)}
2321   {\SUF@titlerule\contentspage}
2322 \titlecontents{figure}
2323   [ \SUF@tocindent@fig]
2324   {}
2325   {\hskip-\SUF@tocindent@fig%
2326     \makebox[\SUF@label@fig][1]{\thecontentslabel}\hspace*{1em}}
2327   {}
2328   {\SUF@titlerule\contentspage}
2329 \titlecontents{table}
2330   [ \SUF@tocindent@tab]
2331   {}
2332   {\hskip-\SUF@tocindent@tab%
2333     \makebox[\SUF@label@tab][1]{\thecontentslabel}\hspace*{1em}}
2334   {}
2335   {\SUF@titlerule\contentspage}
2336 \fi

```

\tableofcontents With `article` option the toc, lof and lot are printed as sections.

\listoffigures \ifsuftesi@article

\listoftables \renewcommand\tableofcontents{%

2339 \vspace{2ex}%

```

2340      \section* {\contentsname}%
2341          \@mkboth{\contentsname}{\contentsname}%
2342              \thispagestyle{empty}%
2343              \ifsuftesi@twocolumntoc
2344                  \begin{multicols}{2}
2345                      \starttoc{toc}%
2346                  \end{multicols}
2347              \else
2348                  \starttoc{toc}%
2349              \fi
2350          \vspace{2ex}%
2351      }
2352 \renewcommand\listoffigures{%
2353     \vspace{2ex}%
2354     \section* {\listfigurename}%
2355         \@mkboth{\listfigurename}{\listfigurename}%
2356         \thispagestyle{empty}%
2357         \ifsuftesi@twocolumnlof
2358             \begin{multicols}{2}
2359                 \starttoc{lof}%
2360             \end{multicols}
2361         \else
2362             \starttoc{lof}%
2363         \fi
2364     \vspace{2ex}%
2365 }
2366 \renewcommand\listoftables{%
2367     \vspace{2ex}%
2368     \section* {\listtablename}%
2369         \@mkboth{\listtablename}{\listtablename}%
2370         \thispagestyle{empty}%
2371         \ifsuftesi@twocolumnlot
2372             \begin{multicols}{2}
2373                 \starttoc{lot}%
2374             \end{multicols}
2375         \else
2376             \starttoc{lot}%
2377         \fi
2378     \vspace{2ex}%
2379 }
2380 \else
    The default toc, lof and lot are treated as chapters.
2381 \renewcommand\tableofcontents{%
2382     \author{\contentsname}%
2383     \title{\contentsname}%
2384     \if@twocolumn
2385         \restonecoltrue\onecolumn
2386     \else
2387         \restonecolfalse
2388     \fi
2389     \chapter* {\contentsname}%
2390     \@mkboth{%
2391         \contentsname
2392         \{\contentsname\}%
2393     }{\contentsname}%
2394     \thispagestyle{empty}%
2395     \ifsuftesi@twocolumntoc
2396         \begin{multicols}{2}
2397             \starttoc{toc}%
2398         \end{multicols}
2399     \else
2400         \starttoc{toc}%
2401     \if@restonecol\twocolumn\fi
2402     }
2403 \renewcommand\listoffigures{%
2404     \author{\listfigurename}%

```

```

2405   \title{\listfigurename}%
2406     \if@twocolumn
2407       \@restonecoltrue\onecolumn
2408     \else
2409       \@restonecolfalse
2410     \fi
2411   \chapter*{\listfigurename}%
2412     \mkboth{\listfigurename}{\listfigurename}%
2413     {\listfigurename}%
2414   \thispagestyle{empty}
2415   \ifsuftesi@twocolumnlof
2416     \begin{multicols}{2}
2417       \starttoc{lof}%
2418     \end{multicols}
2419   \else
2420     \starttoc{lof}%
2421   \fi
2422 \if@restonecol\twocolumn\fi
2423 }
2424 \renewcommand\listoftables{%
2425   \author{\listtablename}%
2426   \title{\listtablename}%
2427   \if@twocolumn
2428     \@restonecoltrue\onecolumn
2429   \else
2430     \@restonecolfalse
2431   \fi
2432   \chapter*{\listtablename}%
2433   \mkboth{%
2434     \listtablename}%
2435     {\listtablename}%
2436   \thispagestyle{empty}
2437   \ifsuftesi@twocolumnlot
2438     \begin{multicols}{2}
2439       \starttoc{lot}%
2440     \end{multicols}
2441   \else
2442     \starttoc{lot}%
2443   \fi
2444 \if@restonecol\twocolumn\fi
2445 }
2446 \fi

```

6.21 New commands

\chapterintro A command to typeset an unnumbered section:

```

2447 \ifsuftesi@article
2448 \def\chapterintro{%
2449 \ClassError{suftesi}%
2450 {Command \noexpand\chapterintro is undefined\MessageBreak
2451   using 'documentstructure=article'}
2452 {Command \noexpand\chapterintro is undefined\MessageBreak
2453   using 'documentstructure=article'}}%
2454 \else
2455 \def\chapterintro{%
2456   @ifstar{@tempswafalse\@chapterintro}{@tempswatrue\@chapterintro}%
2457 \def\@chapterintro{\phantomsection
2458   \if@tempswa\section*{\SUF\fchapterintroname}\fi
2459   \addcontentsline{toc}{section}{\SUF\fchapterintroname}%
2460 \newcommand{\chapterintroname}[1]{\def\SUF\fchapterintroname{\#1}}%
2461 \chapterintroname{Introduzione}%
2462 \fi

```

\headbreak Active in the table of contents but not in the text.

```

2463 \newif\ifheadbreak\headbreakfalse
2464 \DeclareRobustCommand{\headbreak}{%

```

```

2465      {\ifheadbreak\\else\fi}
\xheadbreak Active in the text but not in the table of contents.
2466 \newif\ifxheadbreak\xheadbreaktrue
2467 \DeclareRobustCommand{\xheadbreak}
2468     {\ifxheadbreak\\else\fi}

\tableofcontents
2469 \let\origtableofcontents\tableofcontents
2470 \renewcommand{\tableofcontents}{%
2471     \begingroup\headbreaktrue\xheadbreakfalse%
2472 \origtableofcontents\endgroup}

Renew \frontmatter to have arabic page numbering:
2473 \ifsuftesi@article
2474 \renewcommand\frontmatter{\ClassError{suftesi}%
2475 {Command \noexpand\frontmatter is undefined\MessageBreak
2476     using 'documentstructure=article'}
2477 {Command \noexpand\frontmatter is undefined\MessageBreak
2478     using 'documentstructure=article'}}%
2479 \renewcommand\mainmatter{\ClassError{suftesi}%
2480 {Command \noexpand\mainmatter is undefined\MessageBreak
2481     using 'documentstructure=article'}%
2482 {Command \noexpand\mainmatter is undefined\MessageBreak
2483     using 'documentstructure=article'}}%
2484 \renewcommand\backmatter{\ClassError{suftesi}%
2485 {Command \noexpand\backmatter is undefined\MessageBreak
2486     using 'documentstructure=article'}%
2487 {Command \noexpand\backmatter is undefined\MessageBreak
2488     using 'documentstructure=article'}}%
2489 \else
2490 \renewcommand\frontmatter{\cleardoublepage@\mainmatterfalse}
2491 \renewcommand\mainmatter{\cleardoublepage@\mainmattertrue}
2492 \fi

```

6.22 Backward compatibility

bibliografia An environment to manually typeset the bibliography. (Use `biblatex` instead!)

```

2493 \newenvironment{bibliografia}{%
2494     \ifsuftesi@article
2495         \section*{\refname}
2496         \addcontentsline{toc}{section}{\refname}
2497     \else
2498     \chapter{\bibname}%
2499     \fi
2500         \normalfont \list{}{%
2501             \setlength{\itemindent}{-\parindent}
2502             \setlength{\leftmargin}{\parindent}
2503             \setlength{\labelwidth}{\leftmargin}
2504             \setlength{\parsep}{\parskip}
2505             \let\makelabel\label}
2506     \endlist}

```

sigle An environment to manually typeset the list of shorthands. (Use `biblatex` instead!)

```

2507 \newcommand{\losname}{Sigle}
2508 \newcommand{\itlabel}[1]{\itshape\hbox to 6em{\#1}}
2509 \newenvironment{sigle}{%
2510     \chapter{\losname}
2511         \normalfont \list{}{%
2512             \setlength{\labelsep}{0.5em}
2513             \setlength{\itemindent}{0pt}
2514             \setlength{\leftmargin}{6em}
2515             \setlength{\labelwidth}{\leftmargin}
2516             \setlength{\listparindent}{\parindent}
2517             \setlength{\parsep}{\parskip}
2518             \let\makelabel\itlabel}
2519     \endlist}

```

6.23 Final settings

In a previous version the `\hemph` command was provided to fix a bug in the hyphenation of some italian expressions like “dell’*encyclopaedia*”. Now the bug has been fixed loading the `fixltxhyph` package by Claudio Beccari. The package must be loaded after `babel` or `polyglossia`:

2520 `\AtBeginDocument{\RequirePackage{fixltxhyph}}`

The `\hemph` command is provided only for backward compatibility:

2521 `\let\hemph\emph`

The first line of all sections is indented by default using X_{EL}T_EX with italian as main language. Anyway this is incongruous with the L_TE_X default.

2522 `\ifxetex\let{@afterindenttrue}@afterindentfalse\else\fi`

Just one touch of french typography:

2523 `\frenchspacing`

`</class>`

Change History

vo.5	New option <code>rightsec</code>	11
	New option <code>rmstyle(1-6)</code>	11
	New option <code>romanchap</code>	11
	New option <code>scstyle(1-12)</code>	11
	New option <code>smallcapschap</code>	11
	New option <code>smallcapsheader</code>	11
	New option <code>smallcapspart</code>	11
	New option <code>smallcapssec</code>	11
	New option <code>smallquotation</code>	11
	New option <code>standardfootnote</code>	11
	New option <code>tocpageleft</code>	11
vo.6	General: First public release. The frontispiece of <code>suftesi</code> is now included in the package <code>frontespizio</code> . New option <code>fullplain</code> Changed option <code>sctitles</code>	1
	New command <code>chapnumfont</code>	10
	New option <code>compact</code>	11
	New option <code>elements</code>	11
	New option <code>nocrop</code>	11
	New option <code>nomarginpar</code>	11
	New option <code>sufelements</code>	11
	New option <code>supercompact</code>	11
vo.6a	General: English documentation. Renamed options <code>plain</code> and <code>fullplain</code> to <code>centerheadings</code> and <code>sufplain</code>	1
	New command <code>\artcolophon</code>	9
	New command <code>\bookcolophon</code>	8
	New option <code>authortitle</code>	11
vo.6c	General: Maintenance release, no changes	1
vo.6b	General: Improved full compatibility with X _E T _E X. <code>varioref</code> and <code>footmisc</code> packages are no longer loaded	1
vo.6c	General: Maintenance release, no changes	1
vo.7	General: Maintenance release, no changes. Provided a thesis template	1
vo.8	General: Added macro for using <code>frontespizio</code> package with <code>compact</code> and <code>supercompact</code> options.	1
	New option <code>periodical</code>	11
	Renewed <code>\title</code> command	9
vo.9	General: Improved compatibility with <code>mathspec</code>	1
	New option <code>dotteddtoc</code>	11
	New option <code>raggeddtoc</code>	11
vo.9a	General: Added inline option to <code>enumitem</code> package. Deleted <code>centertitle</code> option. Deleted <code>sctitles</code> option. Changed code for toc, lot and lof elements.	1
	New command <code>\toclabelspace</code>	9
	New option <code>alignlist</code>	11
	New option <code>centerchap</code>	11
	New option <code>centerpart</code>	11
	New option <code>centersec</code>	11
	New option <code>defaultparindent</code>	11
	New option <code>dottedchap</code>	11
	New option <code>dottedfootnote</code>	11
	New option <code>dottedpart</code>	11
	New option <code>indentlist</code>	11
	New option <code>italicchap</code>	11
	New option <code>italicheader</code>	11
	New option <code>italicpart</code>	11
	New option <code>italicsec</code>	11
	New option <code>italicsubsec</code>	11
	New option <code>itstyle(1-12)</code>	11
	New option <code>numparchap</code>	11
	New option <code>numparpart</code>	11
	New option <code>numparsec</code>	11
	New option <code>ralignquotation</code>	11
	New option <code>rightchap</code>	11
	New option <code>rightpart</code>	11
vo.9b	General: Changed <code>standardfootnote</code> option and renamed to <code>footnotestyle</code>	6
	New command <code>\xfootnote</code>	9
	New option <code>documentstructure</code>	3
	New option <code>fewfootnotes</code>	6
	New option <code>greekfont</code>	5
	New option <code>pagestyle</code>	3
	New option <code>parindent</code>	7
	New option <code>partpage</code>	7
	New option <code>quotationfont</code>	6
	New option <code>quotestyle</code>	6
	New option <code>tocstyle</code>	5
	Restored 11pt and 12pt option to default	1
	The <code>epigraph</code> package is no longer loaded	2
	The <code>mparhack</code> package is no longer loaded. It is not compatible with <code>crop</code>	2
vo.9c	General: Maintenance release, no changes	1
v1.0	General: First stable release. Renamed option <code>bozza</code> to <code>draftdate</code>	7
v1.1	General: Added the <code>fixltxhyph</code> package. Documentation updated.	1
v1.2	General: Maintenance release. Added the <code>\toclabelspace</code> command.	1
v1.3	General: New command <code>\FSPLcolophon</code>	9
	Updated documentation. Added FSPLa, FSPLb and FSPLc styles.	1
v1.4	General: New value <code>periodicalaureo</code> for option <code>pagelayout</code> . Changed code for <code>\xfootnote</code> command.	1
v1.5	General: The <code>microtype</code> package is loaded for all engines. Improved compatibility with <code>todonotes</code> package and with <code>mdframed</code> and <code>bookmark</code> packages when using <code>style</code> class option. New option <code>viewmode</code>	1
v1.6	General: New option <code>viewmode</code> . Corrected bugs in the definition of <code>\listoffigures</code> , <code>\listoftables</code> and <code>\tableofcontents</code> commands. Updated documentation.	1
v1.7	General: Renamed <code>viewmode</code> option to <code>version</code> : renamed <code>print</code> value to <code>draft</code> and added <code>final</code> value. New <code>smallcapsstyle</code> option.	1

v1.8	General: Maintenance release. Corrected a bug in the definition of \appendix	1	supercompactaureo page layout. Changed \toclabelspace command and renamed to \toclabelwidth. New collection document structure	1
v1.9	General: Added italic, smallcaps and sanserif values for captionstyle option. New twocolcontents option. New v1.9a		General: Maintenance release. Updated greek support. Updated documentation.	1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@Alph	1775, 1789, 1790, 1796, 1797
\@M	1962
\@Roman	307, 319, 334, 346, 361, 373
\@afterindentfalse	2522
\@afterindenttrue	2522
\@arabic	1208, 1210, 1212, 1214, 1216, 1669, 1671, 1673, 1675, 1677
\@author	397, 401, 1344, 1374, 1401, 1468, 1514, 1628, 1632, 1637, 1648, 2023
\@beginparpenalty	1959
\@centercr	1891
\@chapapp	1774, 1795
\@chapterintro	2456, 2457
\@collectioneditor	1562, 1563, 1660
\@collectiontitle	1559, 1560, 1657
\@ctrerr	1908
\@date	1377, 1386, 1404, 1413, 1442, 1471, 1500, 1517, 1663
\@dbllarg	1334
\@doi	1536, 1537
\@endparpenalty	1962
\@fnsymbol	1353, 1419, 1477, 1598, 1902, 1909
\@footnotemark	1913
\@footnotetext	1913
\@headtitle	396, 400, 1333, 1336, 1633, 1649
\@highpenalty	1567, 1593
\@idxitem	1736
\@ifpackageloaded	939, 1268, 1300, 1697, 1927
\@ifpackagewith	1681
\@ifstar	2456
\@issn	1533, 1534
\@issue	1545, 1546, 1557
\@issuename	1558
\@journalname	1530, 1531, 1556
\@journalnumber	1542, 1543, 1556
\@journalvolume	1539, 1540
\@journalwebsite	1551, 1552
\@journalyear	1548, 1549, 1557
\@latec@warning@no@line	1531, 1534, 1537, 1540, 1543, 1546, 1549, 1552, 1560, 1563
\@lowpenalty	1959
\@mainmatterfalse	2490
\@mainmattertrue	1742, 2491
\@makefnmark	1420, 1478, 1599
\@makefntext	466, 469, 473, 476, 1421, 1479, 1600
\@makeschapterhead	1727
\@maketitle	1426, 1428, 1433, 1440, 1445, 1605, 1607, 1612, 1619
\@mkboth	1729, 2341, 2355, 2369, 2390, 2412, 2433
\@plus	1568, 1733, 1879
\@pnumwidth	1570, 1571, 1576
\@restonecolfalse	1720, 2387, 2409, 2430
\@restonecoltrue	1722, 2385, 2407, 2428
\@roman	303, 315, 330, 342, 357, 369
\@standardmaketitle	1484, 1486, 1491, 1498, 1503
\@starttoc	2345, 2348, 2359, 2362, 2373, 2376, 2396, 2399, 2417, 2420, 2439, 2442
\@tempswafalse	2456
\@tempswatrue	2456
\@textsuperscript	1420, 1423, 1478, 1481, 1599, 1602
\@thanks	1379, 1385, 1406, 1412, 1435, 1441, 1493, 1499, 1554, 1555, 1614, 1617, 1647
\@thefnmark	467, 471, 474, 477, 1420, 1423, 1478, 1481, 1599, 1602, 1912
\@title	1333, 1340, 1359, 1363, 1365, 1368, 1396, 1453, 1457, 1459, 1462, 1509, 1627, 1639
\@titlepagefalse	70, 613
\@titlepagetrue	611
\@todonotes@drawLineToLeftMargin	1934
\@todonotes@drawLineToRightMargin	1937
\@todonotes@drawMarginNote	1933, 1936
\@todonotes@drawMarginNoteWithLine	1928
\@topnum	1432, 1490, 1611
_	517, 1554, 1827, 1829
A	
\abstractname	1945, 1949, 1961, 1968, 1972, 1979
\addfontfeature	1008, 1010
\addpenalty	1567
\addtolength	2059, 2060
\Alph	1779
\alph	429, 436, 443
\and	1388, 1415, 1444, 1502
B	
\backmatter	2484, 2485, 2487
\baselineskip	1005, 1054, 1060, 1078, 1136, 1140, 1144, 1148, 1152, 1156, 1160, 1163
bibliografia (environment)	2493
\bibname	1301, 1307, 1315, 2498
\bookcolophon	1996
C	
\c@chapter	1775, 1796, 1797
\c@footnote	1353, 1419, 1477, 1555, 1598, 1909
\c@paragraph	1214, 1675
\c@section	1208, 1669, 1789, 1790
\c@subparagraph	1216, 1677
\c@subsection	1210, 1671
\c@subsubsection	1212, 1673
\c@tocdepth	1566
\captionsetup	490, 492, 493, 495, 496, 498, 500, 501
\cc	2023
\chapnumfont	1011, 1013, 1019, 1021
\chapter	1028, 1065, 1071, 1136, 1140, 1144, 1148, 1152, 1156, 1160, 1163, 1176, 1177, 1180, 1181, 1184, 1185, 1188, 1189, 1191, 1193, 1200, 1201, 1203, 1302, 1305, 1308, 1312, 1316, 1319, 1776, 1783, 2389, 2411, 2432, 2498, 2510
\chapterintro	2448, 2450, 2452, 2455
\chapterintroname	2460, 2461
\chaptermark	1806, 1826
\chaptertitlename	1827
\ClassError	51, 53, 55, 57, 59, 941, 1200, 1582, 1903, 2049, 2062, 2449, 2474, 2479, 2484
\ClassWarningNoLine	1, 1337, 1341, 1345

\cleardoublepage	1620, 1644, 1751, 1760, 1995, 2003, 2490, 2491	\fancyfoot	1811, 1837, 1839, 1842, 1847, 1851	\ifsuftesi@draftdate
\clearpage	1666, 1737, 2046	\fancyhead	1812, 1818, 1844, 1845, 1853–1855 39, 1838, 1843, 1852
\cmdSUF@elements@chapposition	1026, 1034	\fancyhf	1810, 1834, 1836, 1841, 1850	\ifsuftesi@elementschap 35, 1131
\cmdSUF@elements@chapsize	1024, 1033	\fancypagestyle	1808, 1834, 1835, 1840, 1849	\ifsuftesi@elementsheader 36, 1805, 1873, 1915
\col@number	1425, 1483, 1604	\finalcolophon	2009	\ifsuftesi@elementspagelayout 38, 1159
\collectioneditor	1562, 1564	\finalhyphendemerits	1921	\ifsuftesi@elementsstructure 37
\collectiontitle	1559, 1561	\font	972, 975	\ifsuftesi@fewfootnotes 40, 1900
\colophon	1980	\fontencoding	954	\ifsuftesi@FSPL 42, 933, 2018
\columnsep	1735	\fontfamily	1020	\ifsuftesi@nocrop 24, 993
\columnseprule	1734	\footnote	1352, 1392, 1450, 1508, 1623	\ifsuftesi@numparchap 28, 1064, 1077
\contentsmargin	2108	\footnotemark	1554	\ifsuftesi@numparpart 27, 1223, 1237
\contentsname	2340, 2341, 2382, 2383, 2389, 2391, 2392	\footnoterule	1351, 1391, 1803	\ifsuftesi@numparsec 29, 1083
\contentspage	1750, 2282, 2293, 2300, 2307, 2314, 2321, 2328, 2335	\footnotesize	459, 517, 1350, 1390, 1838, 1839, 1843–1845, 1847, 1852–1855, 1917, 2034	\ifsuftesi@numparsubsec 30, 1100
\copyright	1986	\footnotetext	1555	\ifsuftesi@numparsubsubsec 31, 1115
\crop	603, 606	\frenchspacing	2523	\ifsuftesi@pagelefttoc 44, 1581, 2107
\csname	1335, 2059, 2060	\frontispiece	1651	\ifsuftesi@partpage 41, 1217
		\frontmatter	2474, 2475, 2477, 2490	\ifsuftesi@periodical 17, 1135, 1179, 1682, 1698
D		\FSPLcolophon	2019, 2048, 2050, 2052	\ifsuftesi@periodicalaureo 18, 1139, 1175, 1691, 1710
\date	1387, 1414, 1443, 1501	\fulljournal	1556	\ifsuftesi@porson 12, 970
\DeclareFontFamily	980			\ifsuftesi@raggedtoc 26, 1578
\DeclareFontShape	981–990			\ifsuftesi@reverseauthortitle 48, 1626, 1636
\DeclareRobustCommand	80, 92, 105, 118, 131, 144, 169, 964, 1007, 1009, 1015, 1017, 2464, 2467	G		\ifsuftesi@screen 43
\DeclareTextFontCommand	967	\gdef	1333, 1530, 1533, 1536, 1539, 1542, 1545, 1548, 1551, 1558, 1559, 1562, 1774, 1775, 1789, 1790, 1795–1797	\ifsuftesi@smallcapschap 33, 1358, 1452
\defbibheading	1269, 1272, 1275, 1279, 1283, 1286, 1289, 1291, 1294, 1301, 1304, 1307, 1311, 1315, 1318, 1321, 1324, 1328	\global	1383–1388, 1410–1415, 1432, 1438–1444, 1490, 1496–1502, 1611, 1617, 1647–1649	\ifsuftesi@smallcapspart 32
\define@choicekey	64, 76, 182, 200, 220, 238, 246, 254, 262, 270, 278, 286, 294, 321, 348, 375, 382, 406, 425, 449, 456, 463, 479, 487, 504, 510, 526, 556, 563, 573, 580, 586, 592, 598, 608, 615, 841, 850, 856, 865	\greektext	964, 967	\ifsuftesi@smallcapssec 34, 1362, 1456
\definecolor	919, 920	Gregorio, Enrico	43	\ifsuftesi@standardfont 11, 955
\dimen	976–978			\ifsuftesi@sufelements 23, 1770
\dimen@	973, 978, 979	H		\ifsuftesi@sufplain 14, 1872
\disable@keys	67, 775, 783, 796, 814, 833	\hb@xt@	1422, 1480, 1576, 1601	\ifsuftesi@supercompact 21, 1151, 1187, 1688, 1706
\doi	1536, 1538	\headbreak	2464	\ifsuftesi@supercompactaureo 22, 1155
\dotfill	1575	\headbreakfalse	2463	\ifsuftesi@twocolumnlof 46, 2357, 2415
\doublehyphendemerits	1920, 1921	\headbreaktrue	2471	\ifsuftesi@twocolumnlot 47, 2371, 2437
		\headrulewidth	1802	\ifsuftesi@twocolumnmtoc 45, 2343, 2394
E		\hemph	2521	\ifxetex 937, 1006, 2522
\emph	1556, 2039, 2521	\hfill	1579, 1589	\ifxheadbreak 2466, 2468
\encodingdefault	966	\hss	1423, 1481, 1576, 1602	\ignorespaces 1882, 1888
\endcsname	1335, 2059, 2060	\ht	973, 976	\includeart 1642
\endlist	1883, 1889, 1899, 2506, 2519	\hyphenpenalty	1919	\index 1994
\endquotation	1953, 1976			\indexname 1725, 1727, 1729
\ensuremath	1902	I		\input 1646
environments:		\if@mainmatter	1869	\issn 1533, 1535
\bibliografia	2493	\if@restonecol	1737, 2401, 2422, 2444	\issue 1545, 1547
\sigle	2507	\if@tempswa	2458	\issuename 1558
\theindex	1718	\if@titlepage	1348, 1955	\item 1736, 1880, 1887, 1897
\ExecuteOptionsX	873	\if@twocolumn 1424, 1482, 1603, 1719, 1944, 1953, 1967, 1976, 2384, 2406, 2427	\itemindent 1876, 1893, 1894, 2501, 2513
\exhyphenpenalty	1919	\ifheadbreak	2463, 2465	\itemsep 1892
\extramarks	1044	\ifsuftesi@article	15, 1086, 1094, 1199, 1266, 1361, 1455, 1724, 1785, 1828, 1859, 2178, 2245, 2289, 2292, 2337, 2447, 2473, 2494	\itlabel 2508, 2518
		\ifsuftesi@authortitle	16, 1860	\itshape 258, 266, 274, 282, 290, 413, 414, 424, 860, 869, 1050, 1256, 1633, 1816, 1822, 1916, 2508
F		\ifsuftesi@centerheader	13, 1871	
\f@series	965	\ifsuftesi@collection	49, 1522, 1942	J
\f@shape	965	\ifsuftesi@compact 19, 1143, 1183, 1685, 1702	\journalname 1530, 1532
		\ifsuftesi@compactlyaureo	20, 1147	\journalnumber 1542, 1544
		\ifsuftesi@dottedtoc	25, 1575	

\journalvolume 1539, 1541
 \journalwebsite 1551, 1553
 \journalyear 1548, 1550

L

\l@title 1565
 \label 1629, 1646
 \labelitemi 422
 \labelsep 2512
 \labelwidth 2503, 2515
 \LARGE 1396, 1509, 1757
 \Large 80, 1029
 \LaTeX 1990, 2038, 2039
 \leftmargin 1877, 1885,
 1895, 1896, 2502, 2503, 2514, 2515
 \leftmark 1816, 1869
 \leftskip 470, 1572, 1573
 \lineskip 1372, 1399, 1466, 1512, 1918
 \lineskiplimit 1918
 \list 1875, 1885, 1892, 2500, 2511
 \listfigurename
 2354, 2355, 2404, 2405, 2411–2413
 \listoffigures 2352, 2403
 \listoftables 2366, 2424
 \listparindent 1875, 1876, 1894, 2516
 \listtablename 2368,
 2369, 2425, 2426, 2432, 2434, 2435
 \LoadClass 63
 \losname 1272, 1279,
 1286, 1304, 1311, 1318, 2507, 2510
 \lsstyle 1016, 1018

M

\mainmatter 2479, 2480, 2482, 2491
 \makelabel 2505, 2518
 \MakeTextLowercase 378
 \maketitle 1349,
 1384, 1411, 1417, 1439, 1497, 1596
 \Margini 1683, 1686,
 1689, 1692, 1699, 1703, 1707, 1711
 \marginpar 508, 1922, 1923
 \marginparsep 1035, 1815, 1821
 \marginparwidth 1816, 1821, 1822
 \markboth 1271, 1274, 1278, 1282,
 1303, 1306, 1310, 1314, 1806, 1827
 \markright 1285, 1288,
 1317, 1320, 1323, 1327, 1807, 1829
 Miede, André 43

N

\newcounter 1523–1526
 \newlength 1004, 1062, 2056, 2071,
 2074–2081, 2110–2125, 2237–2244
 \newline 1632
 \nobreak 1574, 1576, 1579, 1589
 \node 1930
 \noindent 1421,
 1479, 1600, 1882, 1986, 1990,
 2000, 2002, 2008, 2023, 2026, 2038
 Nowacki, Janusz M. 3
 \nr 64, 66,
 76, 79, 182, 184, 200, 202, 220,
 222, 238, 239, 246, 247, 254, 255,
 262, 263, 270, 271, 278, 279, 286,
 287, 294, 296, 321, 323, 348, 350,
 375, 377, 382, 385, 406, 408, 425,
 427, 449, 451, 456, 458, 463, 465

479, 481, 487, 489, 504, 506, 510,
 512, 526, 528, 556, 558, 563, 565,
 573, 575, 580, 581, 586, 588, 592,
 594, 598, 600, 608, 610, 615, 623,
 841, 843, 850, 852, 856, 857, 865, 866

O

\oldmarginpar 1922, 1923, 1932
 \onecolumn 1737, 2385, 2407, 2428
 \origtableofcontents 2469, 2472

P

\p@ 973, 976–
 978, 1355, 1394, 1568, 1733, 1735, 1879
 Pantieri, Lorenzo 43
 \paragraph 1252, 1258
 \parfillskip 1571
 \parsep 1879, 2504, 2517
 \parskip 1733, 2504, 2517
 \part 1220, 1221, 1224, 1230, 1238, 1244
 \partname 1226, 1232, 1240, 1246, 1763, 2101
 \PassOptionsToClass 60
 \penalty 1593
 \phantomsection 2457
 \ProcessOptionsX 906
 \protect 1337, 1341, 1345, 1555
 \protected@xdef 1554
 \put 1034, 1814, 1820

Q

\quotation 1951, 1974

R

\raggedleft 1822, 1924
 \raggedright 1731, 1816, 1925
 \refname 1269, 1275, 1283, 1289, 1291,
 1294, 1321, 1324, 1328, 2495, 2496
 \refstepcounter 1625
 \renewenvironment 1718, 1874, 1884, 1890
 \Rientro 1700, 1704, 1708, 1712
 \rightmargin 452, 1895
 \rightmark 386, 390, 1822, 1869
 \rightskip 1570
 \rlap 1420, 1478, 1599
 \rmdefault 963
 \Roman 305, 317, 332, 344, 359, 371
 \roman 301,
 313, 328, 340, 355, 367, 430, 437, 444
 \rule 1040, 1782

S

\sbox 971, 972, 974, 975
 \section 1043,
 1048, 1084, 1090, 1092, 1098,
 1270, 1273, 1276, 1280, 1284,
 1287, 1322, 1325, 1329, 1725, 1945,
 1968, 2340, 2354, 2368, 2458, 2495
 \sectionmark 1807, 1829, 1831
 \sectionsep 1004, 1005, 1090, 1098,
 1106, 1113, 1121, 1128, 1221, 1258, 1265
 \setlength 576, 578, 1005, 1031,
 1078, 1080, 1809, 2057, 2072,
 2082, 2084, 2086, 2088, 2090,
 2092, 2094, 2096, 2126, 2128,
 2130, 2132, 2134, 2136, 2138,
 2140, 2142, 2144, 2146, 2148,

2150, 2152, 2154, 2156, 2246,
 2248, 2250, 2252, 2254, 2257,
 2259, 2261, 2263, 2265, 2267,
 2270, 2272, 2501–2504, 2512–2517
 \setlist 423,
 424, 428–433, 435–440, 442–447
 \SetTracking 926
 \sfdefault 961
 \sige (environment) 2507
 \small 461, 1350, 1372, 1377,
 1390, 1466, 1471, 1778, 1781, 1947,
 1970, 1990, 2002, 2008, 2014, 2026
 \standardtitle 1389, 1475
 \strip@pt 979
 \subparagraph 1259, 1265
 \subsection 1049, 1054,
 1101, 1106, 1108, 1113, 1290, 1292, 1295
 \substitutefont 963
 \subsubsection
 1055, 1060, 1116, 1121, 1123, 1128
 \SUF@addto@tochang@chap 2118,
 2142, 2145, 2155, 2157, 2164, 2169
 \SUF@addto@tochang@fig
 2124, 2154, 2223
 \SUF@addto@tochang@par
 2122, 2150, 2153, 2205, 2208
 \SUF@addto@tochang@sec
 2119, 2144, 2147, 2176, 2181
 \SUF@addto@tochang@subpar
 2123, 2152, 2214, 2217
 \SUF@addto@tochang@subsec
 2120, 2146, 2149, 2187, 2190
 \SUF@addto@tochang@subsubsec
 2121, 2148, 2151, 2196, 2199
 \SUF@addto@tochang@tab
 2125, 2156, 2231
 \SUF@ADJnumparchap 1062, 1078,
 1080, 1176, 1180, 1184, 1188, 1192
 \SUF@appendices 1738, 1753, 1757
 \SUF@appendixpage 1740, 1741
 \SUF@authorfont@Switch
 867, 869, 871, 1628, 1637
 \SUF@CHAP@StyleSwitch
 264, 266, 268, 1069, 1075
 \SUF@chapnumfont 1012, 1020, 1032
 \SUF@chaptersize 80, 92, 105, 118,
 131, 144, 169, 1066, 1072, 1225,
 1231, 1239, 1245, 1357, 1451, 1621, 1657
 \SUF@chaptitlerule
 514, 518, 522, 2282, 2292
 \SUF@default@CHAPTER 1063, 1173
 \SUF@default@SECTIONS 1082, 1174
 \SUF@dotchap 325,
 329, 333, 337, 341, 345, 1067, 1073
 \SUF@dotpart 298, 302, 306,
 310, 314, 318, 1226, 1232, 1240, 1246
 \SUF@dotsec 352,
 356, 360, 364, 368, 372, 1087, 1095
 \SUF@elements@CHAPTER 1027, 1133
 \SUF@elements@SECTIONS 1042, 1134
 \SUF@fchapterintroname 2458–2460
 \SUF@greekfamily
 561, 566, 568, 571, 963, 965
 \SUF@headingsmallcaps
 417–419, 1009, 1017

\SUF@label@chap	2056, 2057, 2083, 2085, 2127, 2155, 2157, 2165, 2247, 2258, 2271, 2273, 2279	\SUF@titlefont@Switch	858, 860, 862, 1627, 1639	\suftesi@partpagetrue	582
\SUF@label@fig	2080, 2094, 2326	\SUF@titlerule	513, 517, 521, 2293, 2300, 2307, 2314, 2321, 2328, 2335	\suftesi@periodicalaureottrue	168, 786, 803, 821
\SUF@label@par	\SUF@titlesmallcaps	260, 268, 276, 284, 292, 862, 871, 1007, 1015, 1039, 1047, 1359, 1363, 1453, 1457, 1779, 1781	\suftesi@periodicaltrue	91
\SUF@label@part	1764, 2074, 2082, 2102	\SUF@tochang	2071, 2072, 2127, 2143	\suftesi@porsontrue	569
\SUF@label@sec	\SUF@tochang@chap	2110, 2126, 2129, 2139, 2141, 2160, 2162, 2167	\suftesi@raggedtocttrue	520
2075, 2084, 2087, 2095, 2097, 2129, 2145, 2155, 2157, 2177, 2260, 2271, 2273, 2287, 2288, 2291	\SUF@tochang@fig	2116, 2138, 2220, 2222	\suftesi@reverseauthortitletrue	853	
\SUF@label@subpar	2079, 2092, 2137, 2153, 2215, 2255, 2268, 2318–2320	\SUF@tochang@par	2114, 2134, 2137, 2202, 2204, 2207	\suftesi@standardfonttrue	560
\SUF@label@subsec	\SUF@tochang@sec	\suftesi@sufplaintrue	393
2076, 2086, 2089, 2131, 2147, 2188, 2249, 2262, 2297–2299	\SUF@tochang@subpar	2111, 2128, 2131, 2173, 2175, 2180	\suftesi@supercompactaureottrue	143
\SUF@label@subsubsec	\SUF@tochang@subsec	\suftesi@supercompacttrue	130
2077, 2088, 2091, 2133, 2149, 2197, 2251, 2264, 2304–2306	\SUF@tochang@subsubsec	2112, 2130, 2133, 2184, 2186, 2189	\suftesi@twocolumnloftrue	532, 539, 546, 551
\SUF@label@tab	\SUF@toc	\suftesi@twocolumnlottrue	535, 543, 547, 552
2081, 2096, 2224, 2232, 2333	\SUF@leftmark	\SUF@toc@chap	\suftesi@twocolumnmtoctrue	529, 538, 542, 550
387, 391, 397, 401, 1861, 1866	\SUF@leftrightmark	2237, 2257, 2260, 2271, 2273, 2276, 2278, 2281	\SUF@toc@sec	\T	
\SUF@Lheadstyle	\SUF@toc@fig	\tableofcontents	2338, 2381, 2469, 2470
387, 391, 397, 401, 410, 414, 418	\SUF@lr@CHAPSwitch	2243, 2270, 2323, 2325	\SUF@toc@par	\temp	972, 975
205, 207, 209, 212, 215, 1066, 1072	\SUF@lr@coll@titleSwitch	2241, 2252, 2255, 2265, 2268, 2309	\SUF@toc@subpar	\textbullet	422
844, 846, 848, 1622	\SUF@lr@MarkSwitch	2238, 2246, 2249, 2259, 2262, 2285	\SUF@toc@subsec	\textcolor	1036
1846, 1856, 1861, 1863, 1866	\SUF@lr@PARTSwitch	2242, 2244, 2254, 2267, 2316	\SUF@toc@subsubsec	\textgreek	967
191, 194, 197, 1225, 1231, 1239, 1245	\SUF@lr@SECSwitch	2239, 2248, 2251, 2261, 2264, 2295	\SUF@toc@subsubsec	\textnormal	
225, 227, 229, 232, 235, 1085, 1093	\SUF@lr@SUBSECSwitch	2240, 2250, 2253, 2263, 2266, 2302	\SUF@toc@tab	1045, 1051, 1057, 1103, 1110, 1118, 1125	
240, 242, 244, 1102, 1109	\SUF@lr@SUBSUBSECSwitch	2244, 2272, 2330, 2332	\SUF@toc@subsec	\textsc	301, 313, 328, 340, 355, 367
248, 250, 252, 1117, 1124	\SUF@toclabelnum	299, 303, 307, 311, 315, 319, 326, 330, 334, 338, 342, 346, 353, 357, 361, 365, 369, 373, 1765, 2103, 2166, 2178, 2279, 2289	\SUF@toc@subsubsec	\textsf	1993, 2040
1914, 1924, 1925	\SUF@toc@subsubsec	1804, 1838, 1843, 1852	\SUF@toc@subsubsec	\textsuperscript	477
\SUF@PART@StyleSwitch	\SUF@toc@subsubsec	\texttt	1804
256, 258, 260, 1226, 1228, 1232, 1234, 1240, 1242, 1246, 1248	\SUF@quotationsize	2244, 2272, 2330, 2332	\SUF@toc@subsubsec	\thanks	1352,
459, 461, 1881, 1888, 1898	\SUF@quote@style	299, 303, 307, 311, 315, 319, 326, 330, 334, 338, 342, 346, 353, 357, 361, 365, 369, 373, 1765, 2103, 2166, 2178, 2279, 2289	\SUF@toc@subsubsec	1383, 1392, 1410, 1438, 1450, 1496, 1508, 1554, 1618, 1623, 1631	
\SUF@Rheadstyle	1804, 1838, 1843, 1852	\SUF@toc@subsubsec	\thechapter	1775, 1796
386, 390, 396, 400, 1844, 1854, 1863	\SUF@rightmark	\SUF@toc@subsubsec	\thecontentslabel	1765, 2103,
386, 390, 396, 400, 1844, 1854, 1863	\SUF@SEC@StyleSwitch	2244, 2272, 2330, 2332	\SUF@toc@subsubsec	2166, 2179, 2188, 2197, 2206, 2215, 2224, 2232, 2279, 2290, 2298, 2305, 2312, 2319, 2326, 2333	
272, 274, 276, 1089, 1097	\SUF@SUBSEC@StyleSwitch	299, 303, 307, 311, 315, 319, 326, 330, 334, 338, 342, 346, 353, 357, 361, 365, 369, 373, 1765, 2103, 2166, 2178, 2279, 2289	\SUF@toc@subsubsec	\thecontentspage	2163, 2168, 2176, 2181, 2187, 2190, 2196, 2199, 2205, 2208, 2214, 2217, 2223, 2231
\SUF@SUBSUBSEC@StyleSwitch	1804, 1838, 1843, 1852	\SUF@toc@subsubsec	\thefootnote	1353, 1419, 1477, 1598, 1909
288, 290, 292, 1120, 1127	\SUF@toc@subsubsec	\SUF@toc@subsubsec	\theindex (environment)	1718
\SUF@thechapter	324, 328, 332, 336, 340, 344, 1036, 1067, 1073, 1797, 1827	\SUF@toc@subsubsec	\thepage	411, 415, 419, 1811
\SUF@thepage	411, 415, 419, 1839, 1847, 1853	\SUF@toc@subsubsec	\theparagraph	1213, 1216, 1254, 1674, 1677
\SUF@thepart	297, 301, 305, 309, 313, 317, 1226, 1232, 1240, 1246	\SUF@toc@subsubsec	\thesection	1045, 1087, 1095, 1207, 1210, 1668, 1671, 1789
\SUF@thesection	351, 355, 359, 363, 367, 371, 1086, 1094, 1790, 1829	\SUF@toc@subsubsec	\thesubparagraph	1215, 1261, 1676
\SUF@SUBSUBSEC@StyleSwitch	\SUF@toc@subsubsec	\thesubsection	1051, 1103, 1110, 1209, 1212, 1670, 1673
\SUF@SUBSUBSEC@StyleSwitch	\SUF@toc@subsubsec	\thesubsubsection	1057, 1118, 1125, 1211, 1214, 1672, 1675
\SUF@SUBSUBSEC@StyleSwitch	\SUF@toc@subsubsec	\thetitle	1629, 1646
\SUF@SUBSUBSEC@StyleSwitch	\SUF@toc@subsubsec	\title	1333–
\SUF@SUBSUBSEC@StyleSwitch	\SUF@toc@subsubsec	\titleclass	1335, 1338, 1342, 2383, 2405, 2426
\SUF@SUBSUBSEC@StyleSwitch	\SUF@toc@subsubsec	\titlecontents	1743, 1761, 2099, 2159, 2172, 2183, 2192, 2201, 2210, 2219, 2227, 2275, 2284, 2294, 2301, 2308, 2315, 2322, 2329
\SUF@SUBSUBSEC@StyleSwitch	\SUF@toc@subsubsec	\titleformat	1028, 1043, 1049, 1055, 1065, 1071, 1084, 1092, 1101, 1108, 1116, 1123, 1224, 1230, 1238, 1244, 1252, 1259, 1776

\titlerule	513, 514, 517, 518	U		X
\titlespacing	1048, 1054, 1060, 1090, 1098, 1106, 1113, 1121, 1128, 1136, 1140, 1144, 1148, 1152, 1156, 1160, 1163, 1176, 1177, 1180, 1181, 1184, 1185, 1188, 1189, 1191, 1193, 1221, 1258, 1265, 1783	\unitlength	1031, 1809	\xfootnote 1911
\toclabelspace . . .	2061, 2064, 2068	\url	1551	\xheadbreak 2467
\toclabelwidth . . .	2058, 2065, 2069	\usefont	965	\xheadbreakfalse 1844, 1845, 1854, 1855, 2471
\today	1804	V		\xheadbreaktrue 2466
\tolerance	1919	\val	64, 76, 182, 200, 220, 238, 246, 254, 262, 270, 278, 286, 294, 321, 348, 375, 382, 406, 425, 449, 456, 463, 479, 487, 504, 510, 526, 556, 563, 573, 580, 586, 592, 598, 608, 615, 841, 850, 856, 865	\XKV@classoptionslist 917
\tw@	972, 973, 975, 976	\version@string	931, 1804	\XKV@useoption 907-916
\twocolumn	1428, 1486, 1607, 1725, 1727, 2401, 2422, 2444	\versionstring	931, 932	Y
				\year 1986, 2019
				Z
				Zapf, Hermann 3