

User's Guide to **suftesi**

A document class for typesetting
theses, books and articles

Ivan Valbusa*

v2.9.5 – 2020/02/04

Abstract

The standard document classes allow you to typeset beautiful documents but their layout is quite far from the stylistic requests of some humanists (mainly Italian). The **suftesi** class provides a set of “humanistic” page layouts, title styles and heading styles to typeset books, articles and theses. The styles are very simple and sober and also have the aim of finding an aesthetic harmony in the formal simplicity (see Valbusa 2012). They are largely inspired by some interesting readings, particularly *The Elements of Typographic Style* by Robert Bringhurst (1992), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie* by Jan Tschichold (1975) and *First Principles of Typography* by Stanley Morison (1936).

Contents		
1 Use	3	3.7 Miscellaneous 16
		3.8 Pre-defined styles 16
2 Class features	3	4 New commands 17
2.1 Document structure	3	4.1 Printing the cover page . 17
2.2 Page layouts	4	4.2 Printing the colophon . 19
2.3 Fonts	4	4.3 Breaking titles 20
2.3.1 Mathematics	5	4.4 Section titles 20
2.3.2 Greek	5	4.5 Miscellaneous 21
2.4 The frontispiece	7	5 Collections 22
2.5 The cover page	10	5.1 Options 23
2.6 Appendices	10	5.2 Commands 24
3 Options	11	6 Known issues 24
3.1 Layout	11	7 Backward compatibility 25
3.2 Font	12	References 25
3.3 Titles	13	
3.4 Contents lists	14	The Code 26
3.5 Headings	14	
3.6 Notes, lists, quotations . .	15	

*Dipartimento di Scienze Umane, Università degli Studi di Verona — ivan dot valbusa at univr dot it

Legalese

Copyright © 2009-2020 Ivan Valbusa

This package is author-maintained. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c ora later (<http://latex-project.org/lppl>). This software is provided “as is”, without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

The main feature of this class is the set of styles it provides. For this reason DO NOT MODIFY THE STYLES OF THIS CLASS WITH PACKAGES AND/OR COMMANDS WHICH CHANGE THE LAYOUT OF THE DOCUMENT. IF YOU DO NOT LIKE THESE STYLES, USE ANOTHER CLASS. If you use `suftesi` in a document typeset with another class (for example `book`), remember to clean up the preamble from all the layout redefinitions.

A brief history

The `suftesi` class was born as a result of the course *Introduzione a L^AT_EX per le scienze umane* (*Introduction to L^AT_EX for the human sciences*) which I held at the Graduate School of Human Sciences and Philosophy (**S**cienze **U**mane e **F**ilosofia) of Verona University (Italy) in June 2010. Originally thought as a class to typeset theses, during these years it has developed many new features and styles. Finally it has become the referential class of the Joint Project *Formal Style for PhD Theses with L^AT_EX* of the University of Verona.

Acknowledgments

I would like to thank Professors Paola Di Nicola, Director of the Graduate School, and Ugo Savardi who suggested to propose the course precisely to that School; Gilberto D'Arduini, Matteo Lanza and Antonio Rinaldi, who installed L^AT_EX on the computers used during the course; Catia Cordioli, for her help in the organization of the lessons; Corrado Ferreri, responsible of the E-Learning Center, who provided the T_EX Live 2009 DVDs. Special thanks to Professors Enrico Gregorio, the Italian guru of T_EX, for the T_EXpert support and his priceless “magic formulas”, and Tommaso Gordini for his valuable advice in choosing and improving the class features during these years. I would finally thank all the participants to the course who patiently resisted the four intensive lessons. This work is dedicated to them.

Feedback

If you have any questions, feedback or requests please email me at `ivan dot valbusa at univr dot it`. If you need specific features not already implemented, remember to attach the example files.

1 Use

The `suftesi` class is called as usual by

```
\documentclass[<options>]{suftesi}
```

All the options defined by the class are in the $\langle key \rangle = \langle value \rangle$ format. In addition to these you can also use the options defined by the standard `book` class (on which `suftesi` is based) except those modifying the page dimensions (`a4paper`, `a5paper`, `b5paper`, `legalpaper`, `executivepaper` and `landscape`), which are automatically disabled. The class loads the packages listed in table 1.

For using the class with the X_ƎT_EX and LuaT_EX engines you need to load the `fontspec` package (`mathspec` is an alternative only for X_ƎT_EX) and to select a main font.

Global	appendix, caption, color, crop, enumitem, emptytype, extramarks, fancyhdr, fixltxhyph, fontenc, geometry, iftex, microtype, multicol, titlesec, titletoc, xkeyval, (cclicenses)
pdfL _A T _E X only	fontenc, substitutefont
LuaL _A T _E X only	luatex85
defaultfont=standard	lmodern
palatino	textcomp, newpxtext, biolinum, inconsolata, newpxmath
libertine	textcomp, libertine, biolinum, inconsolata, newtxmath
cochineal	textcomp, cochineal, biolinum, inconsolata, newtxmath
compatibility	mathpazo, beramono
mathfont=extended	amsthm, mathalfa

Table 1: Packages loaded by `suftesi`

2 Class features

The `suftesi` class provides a large set of options to customize the style of page, titles, headings and other text elements (see section 3). The simplest way to get to know the class features is therefore to typeset one of the templates which you can find in the `/doc/latex/suftesi` folder in your L_AT_EX distribution (see also Valbusa 2012). The class files as well as the templates are also available online on the CTAN's website at <http://www.ctan.org/pkg/suftesi>.

2.1 Document structure

With `suftesi` you can typeset book-style documents (with chapters), article-style documents (without chapters) and collections of papers (see section 5). The kind of document is set by the `structure` option which defaults to `book` (see section 3).

```
\documentclass[structure=<value>, <options>]{suftesi}
```

2.2 Page layouts

The class provides nine page layouts which can be selected by the `pagelayout` option (table 2). The `standard` layout (default) or `standardaureo` layout are aimed to typeset A4 documents, while the other seven layouts are particularly suitable to typeset compact books, articles or theses. For these compact layouts the `version=screen` and `version=cscreen` options are particularly useful as they show the output in its real size. See section 3.1 for details.

Layout	Dimensions (mm)				Proportions			
	Typeblock		Page		Margins		Stock	
	w	h	w	h	t / b	i / o	Typeblock	Page
<code>standard</code>	110	220	210	297	1 : 2	1 : 2	1 : 2	1 : $\sqrt{2}$
<code>standardaureo</code>	136	220	210	297	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$
<code>compact</code>	110	165	160	240	2 : 3	2 : 3	2 : 3	2 : 3
<code>compactaureo</code>	118	191	160	240	2 : 3	2 : 3	5 : 8*	2 : 3
<code>supercompact</code>	100	150	140	210	2 : 3	2 : 3	2 : 3	2 : 3
<code>supercompactaureo</code>	108	175	140	210	1 : 1	1 : 1	5 : 8*	2 : 3
<code>periodical</code>	110	165	170	240	2 : 3	2 : 3	2 : 3	1 : $\sqrt{2}$
<code>periodicalaureo</code>	120	194	170	240	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$

* $5 : 8 \approx 1 : 1,618$

Table 2: The layouts of `suftesi`

2.3 Fonts

The default roman font is `Cochineal` by Michael Sharpe, the sans serif font is `Linux Biolinum O`, designed by Philipp H. Poll, and the typewriter face is `Inconsolata` by Michael Sharpe. `Cochineal` is a fork of `Crimson`, by Sebastina Kosch, a font inspired by masterpieces like `Sabon` (Jan Tschichold) and `Minion` (Robert Slimbach). It is a very complete typeface and it offers full support for Greek and Cyrillic, real small caps (even in italic shape) and four figure styles. Moreover it provides support for mathematics through the `newtxmath` package.

The `defaultfont` option allows you to change the default roman font to New PX (Palatino-like), `Linux Libertine O`, or Latin modern. You can use other fonts as well, but in this case remember to load the `defaultfont=none` option which turns off the default font settings (see section 3 for details).

Another beautiful Garamond-like font, complete of real small caps, bold weight and mathematical support, is made available by the `garamondx` package by Michael Sharpe, which provides an extension of the `ugm` fonts, (URW)++ `GaramondNo8`. They are not distributed as part of `TEXLive`, but they may be downloaded using

the `getnonfreefonts` script. See the instructions for installation at <http://tug.org/fonts/getnonfreefonts/>.

2.3.1 Typesetting mathematics

The class loads by default a ‘minimal’ mathematical support for Cochineal (default), Linux Libertine O or New PX via the `newtxmath` or `newpxmath` packages by Michael Sharpe. Moreover the `mathfont` option is provided to extend or disable the support for mathematics when using these fonts. These non-standard fonts have a very good mathematical support but if you aim at typesetting high mathematics the Latin Modern font family remains, of course, the better choice: `defaultfont=standard`. See section 3.2 for details.

If some of the loaded packages conflict or if you simply want to change some of the default font settings you should first reset the font default with `defaultfont=none` option and then load the packages in the right order and with your favorite options.

2.3.2 Typesetting Greek

The Cochineal default font is complete of Greek and Cyrillic. Anyway the class provides the `greekfont` option (see section 3.2) to select four different Greek fonts for use with the roman typeface set by the `defaultfont` option (except for the `defaultfont=standard` option, i.e. with Latin Modern font family which uses the CB Greek by default). These fonts are: GFS Bodoni, GFS Artemisia, GFS Porson (by the Greek Font Society) and CB Greek (by Claudio Beccari). You may, of course, choose a different font but in this case, as previously cleared, remember to load the `defaultfont=none` option.

Cochineal/Cochineal Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Cochineal/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Libertine Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Libertine/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὅρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

New PX/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

Latin Modern/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus maris quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἴτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat.

2.4 The frontispiece

The class has an original frontispiece (see figure 1) now directly available loading the `frontespizio` package with the `suftesi` option. It is meant only for Italian users (see Gregorio 2009, version 1.4 or later):

```
\usepackage[suftesi]{frontespizio}
```

Note that this frontispiece requires the use of a logo which could be restricted by some institutions. So before using it you have to be sure that you have the required permissions.

The `frontespizio` package produces a frontispiece in the standard Computer Modern typeface. If you prefer a consistent font remember to load the needed packages or commands in the `\Preambolo` command:

```
\begin{frontespizio}
\Preambolo{\usepackage[osf]{cochineal}}% <===
\Universita{Paperopoli}
\Dipartimento{Filosofia, Pedagogia e Psicologia}
\Corso[Laurea]{Filosofia}
\Annoaccademico{2030--2031}
\Titolo{La mia tesi:\ una lunga serie di risultati\%
      difficilissimi e complicatissimi}
\Sottotitolo{Alcune considerazioni mitevoli}
\Candidato[vr12301231]{Paolo Rossi}
\Relatore{Guido Bianchi}
\end{frontespizio}
```



University of St. Anford
Department of Typography

Ph.D. degree in T_EX and L^AT_EX

How to prepare a formal frontispiece

Theory and practice

Candidate:
Enrico Gregorio

Thesis advisor:
Prof. R. J. Drottnats

Research supervisors:
J. H. Quick
B. L. User

Thesis submitted in 2010

Figure 1: The frontispiece of **suftesi**




Figure 2: An example of the cover page of **suftesi**

2.5 The cover page

Since version 2.6 `suftei` provides a command to print a simple cover page (figure 2), inspired by the Italian designer Bruno Munari (1966, pp. 85-89). The color used for the text and the circle as well as other graphical elements are partially customizable (see section 3 for details). The cover shown in figure 2 is obtained with the following code:

```
\Cauthor{Bruce Lee}
\CTitle{The Art of Kicking}
\CSubtitle{How to survive in the modern societies}
\CEditor{edited by\\ Walker Texas Ranger}
\CFoot{Punch Press\\fbox{\bfseries P\&P}}
\CPagecolor{white!90!black}
\CTextcolor{white}
\CFootcolor{black}

\makecover[ball color=DarkBlue,draw=none]
```

To produce a complete book cover, with spine and dust jacket, you should take a look at the `bookcover` package by Tibor Tómács.

2.6 Appendices

Since version 2.9.5 the class relies on `appendix` package to manage the appendices. To get the correct label in titles, headings and table of contents, you should use the `appendices` environment.

```
\renewcommand{\appendixpagename}{Appendices}
\renewcommand{\appendixname}{Appendix}
\addappheadtotoc

\begin{document}
...
\appendixpage

\begin{appendices}

\chapter{First appendix}
    Lorem ipsum

\chapter{First appendix}
    Lorem ipsum

\end{appendices}
\end{document}
```

3 Options

3.1 Layout

structure=book, article, collection default: book

- book** For typesetting texts with chapters.
- article** For typesetting articles or short theses (without chapters).
- collection** For typesetting journals or collections of articles (see section 5).

pagelayout=standard, standardaureo, periodical, default: standard
periodicalaureo, compact, compactaureo,
supercompact, supercompactaureo

- standard** Prints an A4 page with a typeblock of 110 mm × 220 mm.

With the following values the option prints the typeblock on a an A4 paper showing the crop marks which can be controlled by the **version** option.

- periodical** Prints a page of 17 cm × 24 cm with a typeblock of 11 cm × 16.5 cm.
- periodicalaureo** The same of **periodical** but with a *golden ratio* typeblock of 120 cm × 194 mm.
- compact** Prints a page of 16 cm × 24 cm with a typeblock of 11 cm × 16.5 cm.
- compactaureo** The same as **compact** but with a *golden ratio* typeblock of 11.8 cm × 19.1 cm.
- supercompact** Prints a page of 14 cm × 21 cm with a typeblock of 10 cm × 15.5 cm.
- supercompactaureo** The same as **supercompact** but with a *golden ratio* typeblock of 10.8 cm × 17.5 cm.

The details of this option are shown in table 2.

version=screen, cscreen, draft, final default: final

- screen** Prints the PDF with its real dimensions.
- cscreen** The same as **version=screen** but with a centered typeblock.

These previous two options are provided to have a better view when you are typesetting and reading the PDF on the screen or for online publications. The following options meant for printed documents.

- draft** Prints the output on a A4 paper, showing the crop marks. Useless with **standard** and **standardaureo** layouts.
- final** Prints the output on a A4 paper, hiding the crop marks. Useless with **standard** and **standardaureo** layouts.

Sometimes it is not desirable to have the crop marks on every page. In such a case you can use the `\crop[off]` command after the first page of the document.

3.2 Font

The first three options are available only with L^AT_EX. Using X_EL^AT_EX or LuaL^AT_EX the default font is the Computer Modern but you can change it through the `fontspec` or `mathspec` (X_EL^AT_EX only) packages. If you do not need to typeset mathematics, with these engines I do suggest the EB Garamond font family by Georg Duffner.

`defaultfont=none, cochineal, libertine, palatino, standard` default: `cochineal`

- none** Does not load any font. Use this option if you want full control over the font selection.
- cochineal** Loads the Cochineal serif, the Linux Biolinum O sans serif and the Inconsolata typewriter.
- libertine** Loads the Linux Libertine O serif, the Linux Biolinum O sans serif and the Inconsolata typewriter.
- palatino** Loads the New PX serif, the Linux Biolinum O sans serif and the Inconsolata typewriter. Note that the New PX font does not provide support for Greek. The `greekfont=artemisia` option offers a very good solution.
- standard** Loads the `lmodern` package: Latin Modern font family and CB Greek.

`greekfont=none, artemisia, porson, bodoni, cbgreek` default: `none`

Actually useless with `defaultfont=none` and not available with `defaultfont=standard` options.

- none** Does not load any Greek font.
- artemisia** Loads the Artemisia font by the Greek Font Society.
- porson** Loads the Porson font by the Greek Font Society.¹
- bodoni** Loads the Bodoni font by the Greek Font Society.
- cbgreek** Loads the standard CB Greek font by Claudio Beccari.

`mathfont=none,minimal,extended` default: `minimal`

Available only with Cochineal, Libertine and New PX fonts.

- none** Do not load any mathematical support. Use this option if you need some packages that have to be loaded before `newtxmath` and `newpxmath`.
- minimal** Loads `newtxmath` (for Cochineal and Linux Libertine O) or `newpxmath` (for PX Fonts).
- extended** Loads the previous option plus the `amstext` and `mathalfa` packages.

¹The first code for the Porson font (`suftesi <v.2.4`) has been written by Enrico Gregorio. Claudio Beccari successively added the code to improve the scale factor when using this greek font in combination with Palatino.

smallcapsstyle=low, upper default: low

Active only with $\langle level \rangle$ `font=smallcaps` and `toc<level>font=smallcaps` options (see sections 3.3 and 3.4). With X_LA_TE_X or L_UA_TE_X this option is effective only if a font selection command (such as `\setmainfont`) is given.

low Prints lowercase spaced SMALL CAPITALS.

upper Prints spaced SMALL CAPITALS with uppercase initials.

3.3 Titles

<level>font=roman, italic, smallcaps default: roman

roman Prints the $\langle level \rangle$ title in roman.

italic Prints the $\langle level \rangle$ title in italic.

smallcaps Prints the $\langle level \rangle$ title in SPACED SMALL CAPS

Where $\langle level \rangle$ can be part, chap, sec, subsec, subsubsec.

<level>style=left, center, right, parleft, parcenter, parright default: left

left Aligns the $\langle level \rangle$ title on the left.

center Centers the $\langle level \rangle$ title.

right Aligns the $\langle level \rangle$ title on the right.

Where $\langle level \rangle$ can be part, chap, sec subsec, subsubsec.

parleft As left but with the title below the number.

parcenter As center but with the title below the number.

parright As right but with the title below the number.

Where $\langle level \rangle$ can be part, chap, sec.

<level>numstyle=arabic, roman, Roman, dotarabic, default: Roman/arabic/arabic
dotroman, dotRoman

arabic Arabic $\langle level \rangle$ number.

roman Small caps lowercase roman $\langle level \rangle$ number.

Roman Uppercase roman $\langle level \rangle$ number.

dotarabic As arabic but followed by a dot.

dotroman As roman but followed by a dot.

dotRoman As Roman but followed by a dot.

Where $\langle level \rangle$ can be part, chap, sec, subsec, subsubsec.

3.4 Contents lists

tocstyle=standard, dotted, ragged, leftpage default: standard

- standard** Prints a standard table of contents with page numbers on the right margin.
- dotted** As the previous one but with dotted lines.
- ragged** Aligns the table of contents on the left as suggested by Bringhurst (1992).
- leftpage** Prints a table of contents with page numbers on the left margin.

toc $\langle level \rangle$ **font=**roman, italic, smallcaps default: roman

- roman** Prints the $\langle level \rangle$ TOC entry in roman.
- italic** Prints the $\langle level \rangle$ TOC entry in italic.
- smallcaps** Prints the $\langle level \rangle$ TOC entry in SPACED SMALL CAPS

Where $\langle level \rangle$ can be chap, sec, subsec, subsubsec.

twocolcontents=toc, lof, lot, toclof, toclot, loflot, all default: all

This option activates the **tocstyle=ragged** option and disables the other values of **tocstyle**.

- toc** Prints the table of contents in two columns.
- lof** Prints the list of figures in two columns.
- lot** Prints the list of tables in two columns.
- toclof** Prints the table of contents and the list of figures in two columns.
- toclot** Prints the table of contents and the list of tables in two columns.
- loflot** Prints the list of figures and the list of tables in two columns.
- all** Prints all the contents lists in two columns.

3.5 Headings

headerstyle=inner, center, plain, authortitleinner, authortitlecenter default: inner

- inner** Prints the chapter title and the string “Chapter $\langle n \rangle$ ” in the inner side respectively of even and odd headers, and the page number in the outer side.
- center** Centers the header and footer and puts the page number in the center of the footer.
- plain** Prints no headers and puts the page number in the center of the footer.

authortitleinner Prints the author's name on the even pages and the title on the odd ones. In order to use this option the `\title` and `\author` commands are required.

authortitlecenter As the previous one but with centered headers and footers.

headerfont=roman, italic, smallcaps default: `roman`

roman Prints the headers in roman.

italic Prints the headers in *italic*.

smallcaps Prints the headers in SPACED SMALL CAPS.

3.6 Notes, lists, quotations

quotestyle=center, right default: `center`

center Indents the block quotations on both the left and right margins.

right Indents the block quotations only on the left margin.

quotesize=footnotesize, small default: `footnotesize`

footnotesize Prints the block quotations in `\footnotesize` size.

small Prints the block quotations in `\small` size.

footnotestyle=bulged, hung, dotted, superscript default: `bulged`

bulged The footnote number protrudes beyond the left margin.

hung Indents the footnote text, so it will hang under the first line of the text.

dotted The footnote number is aligned to the left margin and followed by a dot.

superscript Prints a superscript footnote number aligned to the left margin.

fewfootnotes=true, false default: `false`

Uses symbols instead of numbers to mark footnotes. It is active only in documents with three footnotes per page maximum. The symbol sequence is: *, **, ***. With more footnotes you should not need this option.

liststyle=bulged, aligned, indented default: `bulged`

bulged The item number or symbol protrudes beyond the left margin.

aligned Aligns the lists to the left margin.

indented Prints standard indented lists.

captionstyle=standard, sanserif, italic, smallcaps default: standard

All these values print the caption in small size, changing the shape:

- standard** Prints the caption text and label in normal font.
- sanserif** Prints the caption text and label in sanserif.
- italic** Prints the caption text and label in *italic*.
- smallcaps** Prints only the caption label in SPACED SMALL CAPS.

3.7 Miscellaneous

parindent=compact, wide default: compact

Sets the indentation of the first line of each paragraph except those following a section title.

- compact** Sets indentation to 1 em.
- wide** Sets indentation to 1.5 em.

marginpar=true, false default: true

- true** Prints the marginal notes.
- false** Hide the marginal notes.

partpage=true, false default: false

Active only with **structure=article**.

- true** Prints the part title in a separate page as in **structure=book**
- false** Prints a part title similar to the one used in the standard **article** class.

draftdate=true, false default: false

If **true** it prints the string “Version of *<date>*” in the footer. It requires the `\date{<date>}` command.

3.8 Pre-defined styles

These pre-defined styles are intended as shotrcuts to some groups of class options. Combining them with **chapnumstyle** options you can get up to 120 variants.

style=roman(1-6), italic(1-12), smallcaps(1-6) default: roman1

roman(1-6) The titles of chapters and headers are printed in roman. The number of the chapter is on the same line in styles 1-3 and above the title in styles 4-6. The title can be printed on the left (styles 1 and 4), in the center (styles 2 and 5) or on the right (styles 3 and 6).

italic(1-12) The titles of chapters and headers are in *italic*. The section title is in *italic* in styles 1-6 and in SPACED SMALL CAPS in styles 7-12. There are three position for the title and two positions for the number as above.

smallcaps(1-12) The titles of chapters and headers are in SPACED SMALL CAPS. The title of the section is in *italic* in styles 1-6 and in SPACED SMALL CAPS in styles 7-12. There are three position for the title and two positions for the chapter as above.

4 New commands

4.1 Printing the cover page

```
\makecover  
\makecover[tikz options]
```

Prints the cover page (figure 2). This command requires `tikz` and the optional arguments accepts the same options of the `\draw` command of that package (see the examples below). Commands available:

```
\Cauthor{text}
```

Printed at the top of the circle.

```
\Ctitle{text}
```

Printed below the author.

```
\Csubtitle{text}
```

Printed below the title.

```
\Ceditor{text}
```

Printed below the subtitle.

```
\Cfoot{text}
```

Printed in the footer.

The color of the circle can be customized using the optional argument of the `\makecover` command. For the other elements of the cover page the following commands are available. (You can load `xcolor` with your favorite option to access to many beautiful colors.)

```
\Cpagecolor{color}
```

The color of the cover page.

```
\Ctextcolor{color}
```

The color of the text inside the circle.

```
\Cfootcolor{<color>}
```

The color of the text in the footer.

Some examples of cover pages

First you have to declare the informations you want to put in the cover page. It is better to give these informations in the preamble:

```
\usepackage{tikz}

\Caauthor{Bruce Lee}
\CTitle{The Art of Kicking}
\CSubtitle{How to survive in the modern societies}
\CEditor{edited by\\ Walker Texas Ranger}
\Cfoot{Punch Press\\\includegraphics[width=1cm]{logo}}
```

Then you can print the cover page with:

```
\makecover
```

or

```
\makecover[<tikz options>]
```

You can customize the circle using the optional arguments of the `\makecover` command. Some of these `<tikz options>` require special `tikz` libraries. For example, you can add a shadow to the circle loading the `shadows` library and using the `circular drop shadow` option:

```
\usepackage{tikz}
\usetikzlibrary{shadows}
...
\begin{document}
\makecover[circular drop shadow]
\end{document}
```

There are thousands of possibilities. Here is another (not necessarily good) example:

```
\usepackage{tikz}

\CPagelcolor{gray!30}
\CTextcolor{blue!50}
\Cfootcolor{black}

\begin{document}
```

```
\makecover[fill=blue!30!black,draw=teal,line width=2mm,dashed]
\end{document}
```

4.2 Printing the colophon

```
\colophon[⟨OS⟩]{⟨name and surname⟩}{⟨additional info⟩}
```

This command is provided only for Italian documents. It prints a page with a copyright notice and the colophon in the bottom of the page. For different languages use \bookcolophon instead (see below).

If you don't need the copyright notice, leave the second argument of the command empty:

```
\colophon[⟨OS⟩]{}{⟨additional info⟩}
```

With the `article` document structure, you can use the \artcolophon command (see below) as well as the \thanks command:

```
\author{Name Surname}
\thanks{This work has been typeset with \LaTeX, using the
\textsf{suftesi} class by Ivan Valbusa.}
```

```
\bookcolophon{⟨copyright notice⟩}{⟨attribution notice and other informations⟩}
```

Similar to \colophon but fully customizable. The first argument prints its content (usually the copyright notice) in the center of the page. The second one prints its content at the bottom. For example:

```
\bookcolophon{%
Copyright © 2007 by Ivan Valbusa}%
This work has been typeset with \LaTeX, using the \textsf{suftesi}
class by Ivan Valbusa\index{Valbusa, Ivan}. The serif font is
Cochineal by Michael Sharpe and the sans serif font is Linux
Biolinum 0 by Philipp H. Poll.}
```

```
\artcolophon{⟨copyright notice, attribution and other informations⟩}
```

This command only has one argument. It simply prints its content at the bottom of the page. Here is an example:

```
\artcolophon{%
This work is licensed under the Creative Commons
Attribution-NonCommercial-NoDerivs 3.0 Unported
License. To view a copy of this license, visit
\begin{center}
http://creativecommons.org/licenses/by-nc-nd/3.0
\end{center}
or send a letter to Creative Commons, 444}
```

```

Castro Street, Suite 900, Mountain View,
California, 94041, USA.\[1ex]

Typeset with \LaTeX, using the \textsf{suftesi}
class by Ivan Valbusa.}
```

\finalcolophon{\textit{colophon content}}

The same as \artcolophon, but centering its content at the top of the page. It is aimed at typesetting a classical *colophon* at the end of the work.

4.3 Breaking titles

\headbreak

A manual break which is active for the table of contents but not in the text or in the headers.

```
\section{This title will be break here \headbreak{}  
inside the table of contents}
```

\xheadbreak

A manual break which is active in the text but not in the headers and in the table of contents.

```
\section{This title will be break here \xheadbreak{}  
inside the text}
```

4.4 Section titles

The commands in this section are experimental. They provide a fast way to customize the format of section titles and numbers. Note that in some cases you will have to manually adjust the spacing accordingly, using \titlespacing, \hskip/\hskip, \vskip/\vspace, and so on.

\<level>font{\textit{definition}} (default=empty)

Changes the font of the *<level>* title. Where *<level>* can be `part`, `chap`, `sec`, `subsec`, `subsubsec`. For example:

```
\chapfont{\bfseries\sffamily\scshape\Huge}
\secfont{\sffamily\fontsize{15.5}{17.5}}
```

```
\<level>numfont{\<definition>} (default=empty)
```

Changes the font of the *<level>* number. Where *<level>* can be `part`, `chap`, `sec`, `subsec`, `subsubsec`.

```
\chapnumfont{%
\chapnumfont{\bfseries\fontsize{160}{50}\selectfont
\color{gray}\arabic{chapter}\hspace{-15cm}}
```

Combining these commands you can get something like this (or something worse/-better):

```
\documentclass[pagelayout=periodicalaureo,11pt,
version=cscreen,chapstyle=parright]{sufteis}

\chapfont{\bfseries\sffamily\scshape\LARGE}
\secfont{\sffamily\fontsize{14.5}{15.5}\selectfont

\chapnumfont{\hspace{1cm}\bfseries\fontsize{100}{100}\selectfont%
\color{gray}\arabic{chapter}}
\secnumfont{\bfseries---,\arabic{chapter}.\arabic{section}}
\chapnumfont{\hspace{1cm}\hbox{\bfseries\fontsize{100}{100}\selectfont%
\color{gray}\arabic{chapter}}\hspace{-1cm}}
\secnumfont{\bfseries---,\arabic{chapter}.\arabic{section}}

\begin{document}

\chapter{Lorem ipsum dolor sit amet, consectetur adipiscing elit}

\section{Dolor sit amet}
\lipsum[1-2]

\section{Lorem ipsum dolor sit amet}
\subsection{Dolor sit amet}
\lipsum[1]

\end{document}
```

4.5 Miscellaneous

```
\xfootnote[\<symbol>]{\<footnote text>}
```

A command to print a footnote with a discretionary symbols given in the optional argument (default=`*`). It does not increment the footnote counter.

```
\xfootnote[$\dagger$]{\<Footnote text>}
\xfootnote[\textdagger]{\<Footnote text>}
```

```
\title[short title for headers]{complete title for titlepage}
```

Useful with `headerstyle=authortitle` option if the title is too long or has some breaks.

```
\toclabelwidth{level}{dim}
```

Adds the `{dim}` to the `{level}` label in the table of contents, where `{level}` can be `part`, `chap`, `sec`, `subsec`, `subsubsec`, `par`, `subpar`, `fig`, `tab`. For example, when using `chapnumstyle=Roman` you would probably need to adjust the width of the chapter label with:

```
\toclabelwidth{chap}{1em}
```

```
\chapterintro
```

Prints an unnumbered introduction at the beginning of the chapter, with the correct hyperlink. In order to use this command the `hyperref` package must be loaded.

```
\chapterintroname{name} (default=Introduzione)
```

Changes in `{name}` the title printed by the `\chapterintro` command.

```
\appendixpage
```

Prints a page with the argument of `\appendicesname` (default=`Appendici`) at the center. Particularly useful if you have two or more appendices.

```
\appendicesname{name} (default=Appendici)
```

Changes in `{name}` the title printed by the `\appendixpage` command.

5 Collections

The `collection` document structure is thought to create a collection of papers. Each paper has to be typeset in a separate `.tex` file inside the `article` environment:

```
\begin{article}
\author{Author}
\title{Title of the paper}
% The abstract is optional.
% \begin{abstract}
% The abstract
% \end{abstract}

\maketitle
```

```

Text of the paper
\end{article}

```

If the names of the papers are `article1.tex`, `article2.tex`, `article3.tex`, etc., then a minimal main file should be similar to this:

```

\documentclass[structure=collection]{suftesi}

\begin{document}
\input{article1}
\input{article2}
\input{article3}
\end{document}

```

5.1 Options

In addition to the following options you can use the other options of the class too. In particular, with the `chapstyle` and `chapfont` options you can customize all the section titles which are treated as a normal unnumbered chapters in the `book` document structure, such as “Table of Contents”, “Index”, “Bibliography”, etc.

papertitlestyle=`left`, `center`, `right` default: `left`

- left** Aligns the author-title block on the left.
- center** Centers the author-title block.
- right** Aligns the author-title block on the right.

revauthortitle=`true`, `false` default: `false`

- true** Prints the author’s name below the title.
- false** Prints the author’s name above the title.

titlefont=`roman`, `italic`, `smallcaps` default: `italic`

- roman** Prints the title of the articles in roman.
- italic** Prints the title of the articles in *italic*.
- smallcaps** Prints the title of the articles in SPACED SMALL CAPS.

authorfont=`roman`, `italic`, `smallcaps` default: `roman`

- roman** Prints the author’s name in roman.
 - italic** Prints the author’s name in *italic*.
 - smallcaps** Prints the author’s name in SPACED SMALL CAPS.
- Note that if you use this last option you need to protect the `\thanks` command:

```
\author{The Author\protect\thanks{...}}
```

toctitlefont=roman, italic, smallcaps default: italic

- roman** Prints the title TOC entry in roman.
- italic** Prints the title TOC entry in *italic*.
- smallcaps** Prints the title TOC entry in SPACED SMALL CAPS.

tocauthorfont=roman, italic, smallcaps default: roman

- roman** Prints the author's name TOC entry in roman.
- italic** Prints the author's name TOC entry in *italic*.
- smallcaps** Prints the author's name TOC entry in SPACED SMALL CAPS.

5.2 Commands

\frontispiece

Typeset the frontispiece of the collection.

It requires the **\collectiontitle** and **\collectioneditor** commands in the preamble of your document.

\collectiontitle{<The Title of the Collection>}

Sets the title of the collection.

\collectioneditor{<The Editor(s)>}

Sets the editor(s) of the collection.

\titlefont{<definition>} (default=empty)

\authorfont{<definition>} (default=empty)

Changes the font of the title of the articles and of the author's name. For example:

```
\titlefont{\bfseries\sffamily\scshape}
\authorfont{\itshape\sffamily}
```

6 Known issues

A problem occurs with the article document structure. The **\part** command resets the headers so if it is the first sectioning command of the page you will get no headers in that page. In this case you have to add the header manually with something like this:

```
\markboth{Section title}{Section title}
\part{The title of the part}
%
\section{Section title}
```

If the title of the part is at the beginning of the page you will need the `afterpage` package and the `\afterapge` command:

```
\afterpage{
  \markboth{Section title}{Section title}
  \part{The title of the part}
}
%
\section{Section title}
```

7 Backward compatibility

defaultfont=compatibility

Loads the fonts of `suftesi` v2.3 (and previous): Palatino (`mathpazo`), Iwona, Bera Mono. To get the default Greek font of those versions (i.e. Artemisia) add the `greekfont=artemisia` option.

documentstructure=book, article, collection

default: `book`

An alias for `structure`

crop=true, false

default: `true`

true An alias for `version=draft` option.

false An alias for `version=center` option.

style=FSPLa, FSPLb, FSPLc

These styles are only meant to typeset a doctoral thesis respecting the features required by the Joint Project *Formal Style for PhD Theses with LaTeX* of the Verona University (Italy).

The `\FSPLcolophon{\{Name Surname\}}` command is provided to typeset the colophon according to these styles:

© 2020 *{Name Surname}*

This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License.

To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/3.0/>.

Typeset with `LATEX` in collaboration with the Joint Project *Formal Style for PhD Theses with LATEX* (University of Verona, Italy) using the `suftesi` class by Ivan Valbusa. The text face is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by Janus M. Nowacki.

References

This bibliography has been typeset with the `biblatex-philosophy` package, created by the same author of this class.

- Bringhurst, Robert (1992), *The Elements of Typographic Style*, 4th ed. (version 4.0), Hurtley & Marks Publisher, Vancouver; trans. *Gli elementi dello stile tipografico*, 5th ed., Sylvestre Bonnard, Milano 2009.
- Gregorio, Enrico (2009), *Il pacchetto frontespizio*, version 1.1, <http://www.guit.sssup.it/phpbb/index.php>.
- Miede, André (2011), *A Classic Thesis style*, <http://mirrors.ctan.org/macros/latex/contrib/classicthesis/ClassicThesis.pdf>.
- Morison, Stanley (1936), *First Principles of Typography*, Cambridge University Press, Cambridge; trans. *I principi fondamentali della tipografia*, Fabrizio Serra editore, Pisa-Roma 2008.
- Munari, Bruno (1966), *Arte come mestiere*, Laterza, Roma-Bari.
- Tschichold, Jan (1975), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie*, Birkhäuser Verlag, Basel; trans. *La forma del libro*, Sylvestre Bonnard, Milano 2003.
- Valbusa, Ivan (2012), “La forma del testo umanistico. La classe `suftesi`”, *ArsTeXnica*, 14 (Oct. 2012), pp. 15-30, <http://www.guix.org/home/images/ArsTeXnic/a/AT014/valbusa.pdf>.

The Code

```
1 \ClassWarningNoLine{suftesi}{%
2  ****\MessageBreak
3  * DO NOT MODIFY THE STYLES OF THIS CLASS\MessageBreak
4  * WITH PACKAGES AND/OR COMMANDS WHICH\MessageBreak
5  * MAY CHANGE THE LAYOUT OF THE DOCUMENT.\MessageBreak
6  * SEE DOCUMENTATION FOR DETAILS.\MessageBreak
7  * ANYWAY, DON'T WORRY!\MessageBreak
8  * THIS IS A HARMLESS MESSAGE :-)\MessageBreak
9  ****}
10 \RequirePackage{xkeyval}
11 \newif\ifsuftesi@compatibility
12 \newif\ifsuftesi@nofont
13 \newif\ifsuftesi@greekfont
14 \newif\ifsuftesi@standard
15 \newif\ifsuftesi@cochineal
16 \newif\ifsuftesi@libertine
17 \newif\ifsuftesi@palatino
18 \newif\ifsuftesi@porson
19 \newif\ifsuftesi@artemisia
20 \newif\ifsuftesi@bodoni
21 \newif\ifsuftesi@cbgreek
22 \newif\ifsuftesi@mathminimal
23 \newif\ifsuftesi@mathextended
24 \newif\ifsuftesi@centerheader
```

```

25 \newif\ifsuftesi@surfplain
26 \newif\ifsuftesi@article
27 \newif\ifsuftesi@authortitle
28 \newif\ifsuftesi@periodical
29 \newif\ifsuftesi@periodicalaureo
30 \newif\ifsuftesi@compact
31 \newif\ifsuftesi@compactaureo
32 \newif\ifsuftesi@supercompact
33 \newif\ifsuftesi@supercompactaureo
34 \newif\ifsuftesi@screen
35 \newif\ifsuftesi@screencentered
36 \newif\ifsuftesi@dottedtoc
37 \newif\ifsuftesi@raggedtoc
38 \newif\ifsuftesi@numparpart
39 \newif\ifsuftesi@numparchap
40 \newif\ifsuftesi@numparsec
41 \newif\ifsuftesi@numparsubsec
42 \newif\ifsuftesi@numparsubsubsec
43 \newif\ifsuftesi@smallcapspart
44 \newif\ifsuftesi@smallcapschap
45 \newif\ifsuftesi@smallcapssec
46 \newif\ifsuftesi@draftdate
47 \newif\ifsuftesi@fewfootnotes
48 \newif\ifsuftesi@partpage
49 \newif\ifsuftesi@FSPL
50 \newif\ifsuftesi@pagelefttoc
51 \newif\ifsuftesi@twocolumnmtoc
52 \newif\ifsuftesi@twocolumnllof
53 \newif\ifsuftesi@twocolumnlot
54 \newif\ifsuftesi@reverseauthortitle
55 \newif\ifsuftesi@collection
56 \DeclareOption{a4paper}{%
57   \ClassWarningNoLine{suftesi}{Option 'a4paper' not available}{}}
58 \DeclareOption{a5paper}{%
59   \ClassWarningNoLine{suftesi}{Option 'a5paper' not available}{}}
60 \DeclareOption{b5paper}{%
61   \ClassWarningNoLine{suftesi}{Option 'b5paper' not available}{}}
62 \DeclareOption{legalpaper}{%
63   \ClassWarningNoLine{suftesi}{Option 'legalpaper' not available}{}}
64 \DeclareOption{executivepaper}{%
65   \ClassWarningNoLine{suftesi}{Option 'executivepaper' not available}{}}
66 \DeclareOption{landscape}{%
67   \ClassWarningNoLine{suftesi}{Option 'landscape' not available}{}}

The suftesi class is based on the standard book class but the previous options are disabled as
they contrast with the layouts provided by the class.
68 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{book}}
69 \ProcessOptions
70 \relax
71 \LoadClass{book}

```

Document structure

```
72 \define@choicekey{}{structure}[\val\nr]
73   {book,article,collection}[book] {%
74 \ifcase\nr\relax
75 %^A\disable@keys{}{secnumstyle}
76 \def\SUF@chapswitch{\thechapter.}
77 \or
78 \suftesi@articltrue
79 \titlepagefalse
80 \def\SUF@chapswitch{}
81 \or
82 \suftesi@collectiontrue
83 \setkeys{}{headerstyle=authortitleinner}
84 \def\SUF@chapswitch{}
85 \fi}
86 \define@choicekey{}{documentstructure}[\val\nr]
87   {book,article,collection}[book] {%
88 \ClassWarningNoLine{suftesi}{%
89   'documentstructure' option is deprecated.\MessageBreak
90   Use 'structure' option instead}
91 \ifcase\nr\relax
92 \setkeys{}{structure=book}
93 \or
94 \setkeys{}{structure=article}
95 \or
96 \setkeys{}{structure=collection}
97 \fi}
```

Page layout

```
98 \RequirePackage{geometry}
99 \define@choicekey{}{pagelayout}[\val\nr]
100   {standard,standardaureo,periodical,compact,compactaureo,supercompact,
101   supercompactaureo,periodicalaureo}[standard]{%
102 \ifcase\nr\relax
103 \DeclareRobustCommand{\SUF@chaptersize}{\Large}
104 \DeclareRobustCommand{\SUF@sectionsizes}{\large}
105 \DeclareRobustCommand{\SUF@subsectionsizes}{\normalsize}
106 \DeclareRobustCommand{\SUF@subsubsectionsizes}{\normalsize}
107 \geometry{%
108   heightrounded,
109   a4paper,
110   includeheadfoot=true,
111   textwidth= 110mm,
112   textheight= 220mm,
113   marginratio= 2:3,
114   marginparwidth= 30mm,
115   marginparsep= 12pt}
116 \or
117 \DeclareRobustCommand{\SUF@chaptersize}{\Large}
```

```

118 \DeclareRobustCommand{\SUF@sectionsiz}{\large}
119 \DeclareRobustCommand{\SUF@subsectionsiz}{\normalsize}
120 \DeclareRobustCommand{\SUF@subsubsectionsiz}{\normalsize}
121 \geometry{%
122   heightrounded,
123   a4paper,
124   includeheadfoot=true,
125   textwidth= 136mm,
126   textheight= 220mm,
127   marginratio= 2:3,
128   marginparwidth= 30mm,
129   marginparsep= 12pt}
130 \or
131 \suftesi@periodicaltrue
132 \DeclareRobustCommand{\SUF@chaptersiz}{\large}
133 \DeclareRobustCommand{\SUF@sectionsiz}{\normalsize}
134 \DeclareRobustCommand{\SUF@subsectionsiz}{\normalsize}
135 \DeclareRobustCommand{\SUF@subsubsectionsiz}{\normalsize}
136 \geometry{%
137   heightrounded,
138   includeheadfoot=false,
139   textheight= 165mm,
140   textwidth= 110mm,
141   paperwidth= 170mm,
142   paperheight= 240mm,
143   marginratio= 2:3,
144   marginparwidth= 26mm,
145   marginparsep= 10pt}
146 \or
147 \suftesi@compacttrue
148 \DeclareRobustCommand{\SUF@chaptersiz}{\large}
149 \DeclareRobustCommand{\SUF@sectionsiz}{\normalsize}
150 \DeclareRobustCommand{\SUF@subsectionsiz}{\normalsize}
151 \DeclareRobustCommand{\SUF@subsubsectionsiz}{\normalsize}
152 \geometry{%
153   heightrounded,
154   includeheadfoot=false,
155   textheight= 165mm,
156   textwidth= 110mm,
157   paperwidth= 160mm,
158   paperheight= 240mm,
159   marginratio= 2:3,
160   marginparwidth= 22mm,
161   marginparsep= 9pt}
162 \or
163 \suftesi@compactaureottrue
164 \DeclareRobustCommand{\SUF@chaptersiz}{\large}
165 \DeclareRobustCommand{\SUF@sectionsiz}{\normalsize}
166 \DeclareRobustCommand{\SUF@subsectionsiz}{\normalsize}
167 \DeclareRobustCommand{\SUF@subsubsectionsiz}{\normalsize}

```

```

168 \geometry{
169   heightrounded,
170   includeheadfoot=false,
171   textheight=    191mm,
172   textwidth=     118mm,
173   paperwidth=    160mm,
174   paperheight=   240mm,
175   marginratio=   2:3,
176   marginparwidth= 19mm,
177   marginparsep=  9pt}
178 \or
179 \suftesi@supercompacttrue
180 \DeclareRobustCommand{\SUF@chaptersize}{\large}
181 \DeclareRobustCommand{\SUF@sectionsizes}{\normalsize}
182 \DeclareRobustCommand{\SUF@subsectionsizes}{\normalsize}
183 \DeclareRobustCommand{\SUF@subsubsectionsizes}{\normalsize}
184 \geometry{
185   heightrounded,
186   includeheadfoot=false,
187   textheight=    150mm,
188   textwidth=     100mm,
189   paperwidth=    140mm,
190   paperheight=   210mm,
191   marginratio=   2:3,
192   marginparwidth= 18mm,
193   marginparsep=  8pt}
194 \or
195 \suftesi@supercompactaureottrue
196 \DeclareRobustCommand{\SUF@chaptersize}{\large}
197 \DeclareRobustCommand{\SUF@sectionsizes}{\normalsize}
198 \DeclareRobustCommand{\SUF@subsectionsizes}{\normalsize}
199 \DeclareRobustCommand{\SUF@subsubsectionsizes}{\normalsize}
200 \geometry{
201   heightrounded,
202   includeheadfoot=false,
203   textheight=    175mm,
204   textwidth=     108mm,
205   paperwidth=    140mm,
206   paperheight=   210mm,
207   marginratio=   1:1,
208   marginparwidth= 11mm,
209   marginparsep=  7pt}
210 \or
211 \suftesi@periodicalaureottrue
212 \DeclareRobustCommand{\SUF@chaptersize}{\large}
213 \DeclareRobustCommand{\SUF@sectionsizes}{\normalsize}
214 \DeclareRobustCommand{\SUF@subsectionsizes}{\normalsize}
215 \DeclareRobustCommand{\SUF@subsubsectionsizes}{\normalsize}
216 \geometry{%
217   heightrounded,

```

```

218     includeheadfoot=true,
219     textwidth=      120mm,
220     textheight=     194mm,
221     paperwidth=    17cm,
222     paperheight=   24cm,
223     marginratio=   2:3,
224     marginparwidth= 62pt,
225     marginparsep=  10pt}
226 \or
227 \fi}



## Sections style


228 \define@choicekey{}{partstyle}[\val\nr]{%
229     left,center,right,parleft,parcenter,parright}[left]{%
230 \ifcase\nr\relax
231     \def\SUF@lr@PARTSwitch{\filright}
232     \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
233 \or
234     \def\SUF@lr@PARTSwitch{\filcenter}
235     \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
236 \or
237     \def\SUF@lr@PARTSwitch{\filleft}
238     \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
239 \or%numpar
240     \def\SUF@lr@PARTSwitch{\filright}
241     \suftesi@numparparttrue
242     \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
243 \or
244     \def\SUF@lr@PARTSwitch{\filcenter}
245     \suftesi@numparparttrue
246     \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
247 \or
248     \def\SUF@lr@PARTSwitch{\filleft}
249     \suftesi@numparparttrue
250     \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
251 \fi}
252 \define@choicekey{}{chapstyle}[\val\nr]{%
253     left,center,right,parleft,parcenter,parright}[left]{%
254 \ifcase\nr\relax
255     \def\SUF@lr@CHAPSwitch{\filright}
256     \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
257 \or
258     \def\SUF@lr@CHAPSwitch{\filcenter}
259     \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
260 \or
261     \def\SUF@lr@CHAPSwitch{\filleft}
262     \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
263 \or%numparchap
264     \def\SUF@lr@CHAPSwitch{\filright}
265     \suftesi@numparchaptrue

```

```

266  \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
267 \or
268  \def\SUF@lr@CHAPSwitch{\filcenter}
269  \suftesi@numparchaptrue
270  \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
271 \or
272  \def\SUF@lr@CHAPSwitch{\filleft}
273  \suftesi@numparchaptrue
274  \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
275 \fi}
276 \define@choicekey{}{secstyle}[\val\nr]{%
277   left,center,right,parleft,parcenter,parright}[left]{%
278 \ifcase\nr\relax
279   \def\SUF@lr@SECSwitch{\filright}
280   \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
281 \or
282   \def\SUF@lr@SECSwitch{\filcenter}
283   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
284 \or
285   \def\SUF@lr@SECSwitch{\filleft}
286   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
287 \or\numparsec
288   \def\SUF@lr@SECSwitch{\filright}
289   \suftesi@numparsectrue
290   \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
291 \or
292   \def\SUF@lr@SECSwitch{\filcenter}
293   \suftesi@numparsectrue
294   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
295 \or
296   \def\SUF@lr@SECSwitch{\filleft}
297   \suftesi@numparsectrue
298   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
299 \fi}
300 \define@choicekey{}{subsecstyle}[\val\nr]{left,center,right}[left]{%
301 \ifcase\nr\relax
302   \def\SUF@lr@SUBSECSwitch{\filright}
303   \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
304 \or
305   \def\SUF@lr@SUBSECSwitch{\filcenter}
306   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
307 \or
308   \def\SUF@lr@SUBSECSwitch{\filleft}
309   \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
310 \fi}
311 \define@choicekey{}{subsubsecstyle}[\val\nr]{left,center,right}[left]{%
312 \ifcase\nr\relax
313   \def\SUF@lr@SUBSUBSECSwitch{\filright}
314   \DeclareRobustCommand{\xheadbreak}{\xheadbreakNL}
315 \or

```

```

316  \def\SUF@lr@SUBSUBSECSwitch{\filcenter}
317  \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
318 \or
319  \def\SUF@lr@SUBSUBSECSwitch{\filleft}
320  \DeclareRobustCommand{\xheadbreak}{\xheadbreakBB}
321 \fi}

```

Sections font

```

322 \define@choicekey{}{partfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
323 \ifcase\nr\relax
324 \def\SUF@PART@StyleSwitch{\relax}
325 \or
326 \def\SUF@PART@StyleSwitch{\itshape}
327 \or
328 \def\SUF@PART@StyleSwitch{\expandafter\SUF@titlesmallcaps}
329 \fi}
330 \define@choicekey{}{chapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
331 \ifcase\nr\relax
332 \def\SUF@CHAP@StyleSwitch{\relax}
333 \or
334 \def\SUF@CHAP@StyleSwitch{\itshape}
335 \or
336 \def\SUF@CHAP@StyleSwitch{\expandafter\SUF@titlesmallcaps}
337 \fi}
338 \define@choicekey{}{secfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
339 \ifcase\nr\relax
340 \def\SUF@SEC@StyleSwitch{\relax}
341 \or
342 \def\SUF@SEC@StyleSwitch{\itshape}
343 \or
344 \def\SUF@SEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
345 \fi}
346 \define@choicekey{}{subsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
347 \ifcase\nr\relax
348 \def\SUF@SUBSEC@StyleSwitch{\relax}
349 \or
350 \def\SUF@SUBSEC@StyleSwitch{\itshape}
351 \or
352 \def\SUF@SUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
353 \fi}
354 \define@choicekey{}{subsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
355 \ifcase\nr\relax
356 \def\SUF@SUBSUBSEC@StyleSwitch{\relax}
357 \or
358 \def\SUF@SUBSUBSEC@StyleSwitch{\itshape}
359 \or
360 \def\SUF@SUBSUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
361 \fi}
362 %

```

TOC font

```
363 %^^A\define@choicekey{}{tocpartfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
364 %^^A\ifcase\nr\relax
365 %^^A\def\SUF@tocPART@font{\relax}
366 %^^A\or
367 %^^A\def\SUF@tocPART@font{\itshape}
368 %^^A\or
369 %^^A\def\SUF@tocPART@font{\expandafter\SUF@TOCtitlesmallcaps}
370 %^^A\fi}
371 \define@choicekey{}{tocchapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
372 \ifcase\nr\relax
373 \def\SUF@tocCHAP@font{\relax}
374 \or
375 \def\SUF@tocCHAP@font{\itshape}
376 \or
377 \def\SUF@tocCHAP@font{\expandafter\SUF@TOCtitlesmallcaps}
378 \fi}
379 \define@choicekey{}{tocsecfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
380 \ifcase\nr\relax
381 \def\SUF@tocSEC@font{\relax}
382 \or
383 \def\SUF@tocSEC@font{\itshape}
384 \or
385 \def\SUF@tocSEC@font{\expandafter\SUF@TOCtitlesmallcaps}
386 \fi}
387 \define@choicekey{}{tocsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
388 \ifcase\nr\relax
389 \def\SUF@tocSUBSEC@font{\relax}
390 \or
391 \def\SUF@tocSUBSEC@font{\itshape}
392 \or
393 \def\SUF@tocSUBSEC@font{\expandafter\SUF@TOCtitlesmallcaps}
394 \fi}
395 \define@choicekey{}{tocsubsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
396 \ifcase\nr\relax
397 \def\SUF@tocSUBSUBSEC@font{\relax}
398 \or
399 \def\SUF@tocSUBSUBSEC@font{\itshape}
400 \or
401 \def\SUF@tocSUBSUBSEC@font{\expandafter\SUF@TOCtitlesmallcaps}
402 \fi}
403 \define@choicekey{}{tocauthorfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
404 \ifcase\nr\relax
405 \def\SUF@tocAUT@font{\relax}
406 \or
407 \def\SUF@tocAUT@font{\itshape}
408 \or
409 \def\SUF@tocAUT@font{\expandafter\SUF@TOCtitlesmallcaps}
410 \fi}
```

```

411 \define@choicekey{}{toctitlefont}[\val\nr]{roman,italic,smallcaps}[italic]{%
412 \ifcase\nr\relax
413 \def\SUF@tocTIT@font{\relax}
414 \or
415 \def\SUF@tocTIT@font{\itshape}
416 \or
417 \def\SUF@tocTIT@font{\expandafter\SUF@TOCtitlesmallcaps}
418 \fi}

```

Sections number style

Part number style

```

419 \define@choicekey{}{partnumstyle}[\val\nr]
420   {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
421 \ifcase\nr\relax
422   \def\SUF@thepart{\arabic{part}}
423   \def\SUF@dotpart{}
424 %^^A \def\SUF@PART@thecontentslabel{\thecontentslabel}
425 \or
426   \def\SUF@thepart{\textsc{\roman{part}}}
427   \def\SUF@dotpart{}
428 %^^A \def\SUF@PART@thecontentslabel{\@roman{\thecontentslabel}}
429 \or
430   \def\SUF@thepart{\Roman{part}}
431   \def\SUF@dotpart{}
432 %^^A \def\SUF@PART@thecontentslabel{\@Roman{\thecontentslabel}}
433 \or
434   \def\SUF@thepart{\arabic{part}}
435   \def\SUF@dotpart{.}
436 %^^A \def\SUF@PART@thecontentslabel{\thecontentslabel}
437 \or
438   \def\SUF@thepart{\textsc{\roman{part}}}
439   \def\SUF@dotpart{.}
440 %^^A \def\SUF@PART@thecontentslabel{\@roman{\thecontentslabel}}
441 \or
442   \def\SUF@thepart{\Roman{part}}
443   \def\SUF@dotpart{.}
444 %^^A \def\SUF@PART@thecontentslabel{\@Roman{\thecontentslabel}}
445 \fi}

```

Chapter number style

```

446 \define@choicekey{}{chapnumstyle}[\val\nr]{arabic,roman,Roman,
447 dotarabic,dotroman,dotRoman}[arabic]{%
448 \ifcase\nr\relax
449   \def\SUF@thechapter{\arabic{chapter}}
450   \def\SUF@HEAD@thechapter{\arabic{chapter}}
451   \def\SUF@dotchap{}
452   \def\SUF@CHAP@thecontentslabel{\thecontentslabel}
453 \or
454   \def\SUF@thechapter{\textsc{\roman{chapter}}}

```

```

455  \def\SUF@HEAD@thechapter{\textsc{\romannumeral{chapter}}}
456  \def\SUF@dotchap{}
457  \def\SUF@CHAP@thecontentslabel{\textsc{\@romannumeral{\thecontentslabel}}}
458 \or
459  \def\SUF@thechapter{\Roman{chapter}}
460  \def\SUF@HEAD@thechapter{\Roman{chapter}}
461  \def\SUF@dotchap{}
462  \def\SUF@CHAP@thecontentslabel{\@Roman{\thecontentslabel}}
463 \or
464  \def\SUF@thechapter{\arabic{chapter}}
465  \def\SUF@HEAD@thechapter{\arabic{chapter}}
466  \def\SUF@dotchap{.}
467  \def\SUF@CHAP@thecontentslabel{\thecontentslabel}
468 \or
469  \def\SUF@thechapter{\textsc{\romannumeral{chapter}}}
470  \def\SUF@HEAD@thechapter{\textsc{\romannumeral{chapter}}}
471  \def\SUF@dotchap{.}
472  \def\SUF@CHAP@thecontentslabel{\textsc{\@romannumeral{\thecontentslabel}}}
473 \or
474  \def\SUF@thechapter{\Roman{chapter}}
475  \def\SUF@HEAD@thechapter{\Roman{chapter}}
476  \def\SUF@dotchap{.}
477  \def\SUF@CHAP@thecontentslabel{\@Roman{\thecontentslabel}}
478 \fi}

```

Section number style

```

479 \define@choicekey{}{secnumstyle}[\val\nr]
480   {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
481 \ifcase\nr\relax
482   \def\SUF@thesection{\SUF@chapswitch\arabic{section}}
483   \def\SUF@HEAD@thesection{\arabic{section}}
484   \def\SUF@dotsec{}
485   \def\SUF@SEC@thecontentslabel{\thecontentslabel}
486 \or
487   \def\SUF@thesection{\textsc{\SUF@chapswitch\romannumeral{section}}}
488   \def\SUF@HEAD@thesection{\textsc{\romannumeral{section}}}
489   \def\SUF@dotsec{}
490   \def\SUF@SEC@thecontentslabel{\textsc{\@romannumeral{\thecontentslabel}}}
491 \or
492   \def\SUF@thesection{\SUF@chapswitch\Roman{section}}
493   \def\SUF@HEAD@thesection{\Roman{section}}
494   \def\SUF@dotsec{}
495   \def\SUF@SEC@thecontentslabel{\@Roman{\thecontentslabel}}
496 \or
497   \def\SUF@thesection{\SUF@chapswitch\arabic{section}}
498   \def\SUF@HEAD@thesection{\arabic{section}}
499   \def\SUF@dotsec{.}
500   \def\SUF@SEC@thecontentslabel{\thecontentslabel}
501 \or
502   \def\SUF@thesection{\SUF@chapswitch\textsc{\romannumeral{section}}}

```

```

503  \def\SUF@HEAD@thesection{\textsc{\roman{section}}}
504  \def\SUF@dotsec{.}
505  \def\SUF@SEC@thecontentslabel{\textsc{\@roman{\thecontentslabel}}}
506 \or
507  \def\SUF@thesection{\SUF@chapswitch\Roman{section}}
508  \def\SUF@HEAD@thesection{\Roman{section}}
509  \def\SUF@dotsec{.}
510  \def\SUF@SEC@thecontentslabel{\@Roman{\thecontentslabel}}
511 \fi}

```

Subsection number style

```

512 \define@choicekey{}{subsecnumstyle}[\val\nr]
513 {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
514 \ifcase\nr\relax
515 \def\SUF@thesubsection{\SUF@thesection.\arabic{subsection}}
516 \def\SUF@dotsubsec{.}
517 \def\SUF@SUBSEC@thecontentslabel{\thecontentslabel}
518 \or
519 \def\SUF@thesubsection{\SUF@thesection.\textsc{\roman{subsection}}}
520 \def\SUF@dotsubsec{.}
521 \def\SUF@SUBSEC@thecontentslabel{\textsc{\@roman{\thecontentslabel}}}
522 \or
523 \def\SUF@thesubsection{\SUF@thesection.\Roman{subsection}}
524 \def\SUF@dotsubsec{.}
525 \def\SUF@SUBSEC@thecontentslabel{\@Roman{\thecontentslabel}}
526 \or
527 \def\SUF@thesubsection{\SUF@thesection.\arabic{subsection}}
528 \def\SUF@dotsubsec{.}
529 \def\SUF@SUBSEC@thecontentslabel{\thecontentslabel}
530 \or
531 \def\SUF@thesubsection{\SUF@thesection.\textsc{\roman{subsection}}}
532 \def\SUF@dotsubsec{.}
533 \def\SUF@SUBSEC@thecontentslabel{\textsc{\@roman{\thecontentslabel}}}
534 \or
535 \def\SUF@thesubsection{\SUF@thesection.\Roman{subsection}}
536 \def\SUF@dotsubsec{.}
537 \def\SUF@SUBSEC@thecontentslabel{\@Roman{\thecontentslabel}}
538 \fi}

```

Sub-subsection number style

```

539 \define@choicekey{}{subsubsecnumstyle}[\val\nr]
540 {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
541 \ifcase\nr\relax
542 \def\SUF@thesubsubsection{\SUF@thesubsection.\arabic{subsubsection}}
543 \def\SUF@dotsubsubsec{.}
544 \def\SUF@SUBSUBSEC@thecontentslabel{\thecontentslabel}
545 \or
546 \def\SUF@thesubsubsection{\SUF@thesubsection.\textsc{\roman{subsubsection}}}
547 \def\SUF@dotsubsubsec{.}
548 \def\SUF@SUBSUBSEC@thecontentslabel{\textsc{\@roman{\thecontentslabel}}}}

```

```

549 \or
550 \def\SUF@thesubsubsection{\SUF@thesubsection.\Roman{subsubsection}}
551 \def\SUF@dotsubsubsec{}
552 \def\SUF@SUBSUBSEC@thecontentslabel{@\Roman{\thecontentslabel}}
553 \or
554 \def\SUF@thesubsubsection{\SUF@thesubsection.\arabic{subsubsection}}
555 \def\SUF@dotsubsubsec{.}
556 \def\SUF@SUBSUBSEC@thecontentslabel{\thecontentslabel}
557 \or
558 \def\SUF@thesubsubsection{\SUF@thesubsection.\textsc{\roman{subsubsection}}}
559 \def\SUF@dotsubsubsec{.}
560 \def\SUF@SUBSUBSEC@thecontentslabel{\textsc{\@roman{\thecontentslabel}}}
561 \or
562 \def\SUF@thesubsubsection{\SUF@thesubsection.\Roman{subsubsection}}
563 \def\SUF@dotsubsubsec{.}
564 \def\SUF@SUBSUBSEC@thecontentslabel{@\Roman{\thecontentslabel}}
565 \fi}

```

This option controls the style of small capitals used in the title of chapters and sections using *<level>font=smallcaps* option:

```

566 \define@choicekey{}{smallcapsstyle}[\val\nr]
567   {low,upper}[low]{%
568 \ifcase\nr\relax
569   \def\suftesi@MakeTextLowercase{\MakeLowercase}
570   \def\suftesi@MakeTextTOCLowercase{\lowercase}
571 \or
572   \def\suftesi@MakeTextLowercase{\relax}
573   \def\suftesi@MakeTextTOCLowercase{\relax}
574 \fi}

```

Fine adjustment of sections font

EXPERIMENTAL

```

575 \newcommand{\partfont}[1]{\def\SUF@PART@StyleSwitch[#1]}
576 \newcommand{\chapfont}[1]{\def\SUF@CHAP@StyleSwitch[#1]}
577 \newcommand{\secfont}[1]{\def\SUF@SEC@StyleSwitch[#1]}
578 \newcommand{\subsecfont}[1]{\def\SUF@SUBSEC@StyleSwitch[#1]}
579 \newcommand{\subsubsecfont}[1]{\def\SUF@SUBSUBSEC@StyleSwitch[#1]}
580 \newcommand{\chapnumfont}[1]{\def\SUF@thechapter[#1]}
581 \newcommand{\secnumpfont}[1]{\def\SUF@thesection[#1]}
582 \newcommand{\subsecnumpfont}[1]{\def\SUF@thesubsection[#1]}
583 \newcommand{\subsubsecnumpfont}[1]{\def\SUF@thesubsubsection[#1]}
584 %
585 \newcommand{\titlefont}[1]{\def\SUF@titlefont@Switch[#1]}
586 \newcommand{\authorfont}[1]{\def\SUF@authorfont@Switch[#1]}
587 %
588 %~A\newcommand{\tocpartfont}[1]{\def\SUF@tocPART@font[#1]}
589 \newcommand{\tocchapfont}[1]{\def\SUF@tocCHAP@font[#1]}
590 \newcommand{\tocsecfont}[1]{\def\SUF@tocSEC@font[#1]}
591 \newcommand{\tocsubsecfont}[1]{\def\SUF@tocSUBSEC@font[#1]}
592 \newcommand{\tocsubsubsecfont}[1]{\def\SUF@tocSUBSUBSEC@font[#1]}
593

```

```

594 \%^^A\newcommand{\tocpartnumfont}[1]{\def\SUF@PART@thecontentslabel{#1\thecontentslabel}}
595 \newcommand{\tocchapnumfont}[1]{\def\SUF@CHAP@thecontentslabel{#1\thecontentslabel}}
596 \newcommand{\tocsecnumfont}[1]{\def\SUF@SEC@thecontentslabel{#1\thecontentslabel}}
597 \newcommand{\tocsubsecnumfont}[1]{\def\SUF@SUBSEC@thecontentslabel{#1\thecontentslabel}}
598 \newcommand{\tocsubsubsecnumfont}[1]{\def\SUF@SUBSUBSEC@thecontentslabel{#1\thecontentslabel}}
599 %
600 %

```

Headers

Header style

```

601 \define@choicekey{}{headerstyle}{[\val\nr]
602     {inner,center,plain,authortitleinner,
603      authortitlecenter}[inner]{%
604 \ifcase\nr\relax
605   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
606   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}
607 \or
608   \suftesi@centerheadertrue
609   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
610   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}
611 \or
612   \suftesi@sufplaintrue
613 \or
614   \suftesi@authortitletrue
615   \def\SUF@rightmark{\let\thanks{@gobble\SUF@Rheadstyle{\@headtitle}}
616   \def\SUF@leftmark{\let\thanks{@gobble\SUF@Lheadstyle{\@author}}}
617 \or
618   \suftesi@authortitletrue
619   \def\SUF@rightmark{\let\thanks{@gobble\SUF@Rheadstyle{\@headtitle}}
620   \def\SUF@leftmark{\let\thanks{@gobble\SUF@Lheadstyle{\@author}}}
621   \suftesi@centerheadertrue
622 \fi}

```

Header font

```

623 \define@choicekey{}{headerfont}{[\val\nr]
624     {roman,italic,smallcaps}[roman]{%
625 \ifcase\nr\relax
626   \def\SUF@Rheadstyle{}
627   \def\SUF@Lheadstyle{}
628   \def\SUF@thepage{\thepage}
629 \or
630   \def\SUF@Rheadstyle{\itshape}
631   \def\SUF@Lheadstyle{\itshape}
632   \def\SUF@thepage{\thepage}
633 \or
634   \def\SUF@Rheadstyle{\SUF@headingsmallcaps}
635   \def\SUF@Lheadstyle{\SUF@headingsmallcaps}
636   \def\SUF@thepage{\SUF@headingsmallcaps{\thepage}}

```

```
637 \fi}
```

Text elements

Lists

```
638 \RequirePackage[inline]{enumitem}
639 \renewcommand\labelitemi{\color{sufgray}\textbullet}
640 \setlist[itemsep=.5ex,parsep=0pt,listparindent=\parindent}
641 \setlist[description]{font=\normalfont\itshape}
642 \define@choicekey{}{liststyle}{[\val\nr]
643   {bulged,aligned,indented}[bulged]{%
644 \ifcase\nr\relax
645   \setlist[enumerate,1]{leftmargin=0pt,label=\arabic*.}
646   \setlist[enumerate,2]{leftmargin= 1.3\parindent,label=\alph*.}
647   \setlist[enumerate,3]{leftmargin= 1.3\parindent,label=\roman*.}
648   \setlist[itemize,1]{leftmargin=0pt}
649   \setlist[itemize,2]{leftmargin=1.3\parindent}
650   \setlist[itemize,3]{leftmargin=1.3\parindent}
651 \or
652   \setlist[enumerate,1]{leftmargin=1\parindent,label=\arabic*.}
653   \setlist[enumerate,2]{leftmargin= 1.5\parindent,label=\alph*.}
654   \setlist[enumerate,3]{leftmargin= 1.5\parindent,label=\roman*.}
655   \setlist[itemize,1]{leftmargin=1\parindent}
656   \setlist[itemize,2]{leftmargin=1.5\parindent}
657   \setlist[itemize,3]{leftmargin=1.5\parindent}
658 \or
659   \setlist[enumerate,1]{leftmargin=2\parindent,label=\arabic*.}
660   \setlist[enumerate,2]{leftmargin= 2.5\parindent,label=\alph*.}
661   \setlist[enumerate,3]{leftmargin= 2.5\parindent,label=\roman*.}
662   \setlist[itemize,1]{leftmargin=2\parindent}
663   \setlist[itemize,2]{leftmargin=2.5\parindent}
664   \setlist[itemize,3]{leftmargin=2.5\parindent}
665 \fi}
```

Quotations

```
666 \define@choicekey{}{quotestyle}{[\val\nr]
667   {center,right}[center]{%
668 \ifcase\nr\relax
669 \def\SUF@quote@style{\rightmargin=\parindent}
670 \or
671 \def\SUF@quote@style{}
672 \fi}
673 \define@choicekey{}{quotesize}{[\val\nr]
674   {footnotesize,small}[footnotesize]{%
675 \ifcase\nr\relax
676 \def\SUF@quotation@size{\footnotesize}
677 \or
678 \def\SUF@quotation@size{\small}
679 \fi}
```

Footnotes

```
680 \define@choicekey{}{footnotestyle}[\val\nr]
681     {bulged,hung,dotted,superscript}[bulged]{%
682 \ifcase\nr\relax
683     \renewcommand\@makefntext{%
684         \hskip-2.5em\makebox[2em][r]{\@thefnmark}\hskip.5em}
685 \or
686     \renewcommand\@makefntext{%
687         \leftskip=1em\hskip-1.5em%
688         \makebox[1em][r]{\@thefnmark}\hskip.5em}
689 \or
690     \renewcommand\@makefntext{%
691         \vphantom{\@thefnmark}\hskip.5em}
692 \or
693     \renewcommand\@makefntext{%
694         \textsuperscript{\vphantom{\@thefnmark}\hskip.3em}}
695 \fi}
696 \define@choicekey{}{fewfootnotes}[\val\nr]
697     {true,false}[true]{%
698 \ifcase\nr\relax
699     \suffesi@fewfootnotestrue
700 \or
701     \relax
702 \fi}
```

Captions

```
703 \RequirePackage[caption]
704 \define@choicekey{}{captionstyle}[\val\nr]
705     {standard,sanserif,italic,smallcaps}[standard]{%
706 \ifcase\nr\relax
707     \captionsetup{labelsep=period,font=small}
708 \or
709     \captionsetup{labelsep=period,font=small}
710     \captionsetup{font+=sf}
711 \or
712     \captionsetup{labelsep=period,font=small}
713     \captionsetup{font+=it}
714 \or
715     \captionsetup{labelsep=period,font=small,labelfont=sc}
716 \fi
717 }
```

Marginal notes

```
718 \define@choicekey{}{marginpar}[\val\nr]
719     {true,false}[true]{%
720 \ifcase\nr\relax
721 \or
722     \renewcommand\marginpar[2][]{}
723 \fi}
```

Table of contents

```
724 \define@choicekey{}{tocstyle}[\val\nr]{%
725     standard,dotted,ragged,leftpage}[standard]{%
726 \ifcase\nr\relax
727     \def\SUF@titlerule{\titlerule*{}}
728     \def\SUF@chaptitlerule{\titlerule*{}}
729 \or
730 \suftesi@dottedtocttrue
731     \def\SUF@titlerule{\titlerule*{\footnotesize .\ } }
732     \def\SUF@chaptitlerule{\titlerule*{}}
733 \or
734 \suftesi@raggedtocttrue
735     \def\SUF@titlerule{\hspace{1em}}
736     \def\SUF@chaptitlerule{\hspace{1em}}
737 \or
738 \suftesi@pagelefttocttrue
739 \fi}
740 \define@choicekey{}{twocolcontents}[\val\nr]{%
741     toc,lof,lot,toclof,toclot,loflot,all}[all]{%
742 \ifcase\nr\relax
743     \suftesi@twocolumnlocttrue
744     \setkeys{}{tocstyle=ragged}
745 \or
746     \suftesi@twocolumnloftrue
747     \setkeys{}{tocstyle=ragged}
748 \or
749     \suftesi@twocolumnlottrue
750     \setkeys{}{tocstyle=ragged}
751 \or
752     \suftesi@twocolumnlocttrue
753     \suftesi@twocolumnloftrue
754     \setkeys{}{tocstyle=ragged}
755 \or
756     \suftesi@twocolumnlocttrue
757     \suftesi@twocolumnlottrue
758     \setkeys{}{tocstyle=ragged}
759 \or
760     \suftesi@twocolumnloftrue
761     \suftesi@twocolumnlottrue
762     \setkeys{}{tocstyle=ragged}
763 \or
764     \suftesi@twocolumnlocttrue
765     \suftesi@twocolumnloftrue
766     \suftesi@twocolumnlottrue
767     \setkeys{}{tocstyle=ragged}
768 \fi
769 }
```

Fonts

Roman fonts

```
770 \define@choicekey{}{defaultfont}[\val\nr]{%
771     none,cochineal,libertine,palatino,standard,compatibility}[cochineal]{%
772 \ifcase\nr\relax
773     \suftesi@nofonttrue
774 \or
775     \suftesi@cochinealtrue
776 \or
777     \suftesi@libertinetrue
778 \or
779     \suftesi@palatinottrue
780 \or
781     \suftesi@standardtrue
782 \or
783     \suftesi@compatibilitytrue
784 \fi}
785 \define@choicekey{}{mathfont}[\val\nr]{%
786     none,minimal,extended}[minimal]{%
787 \ifcase\nr\relax
788     \suftesi@mathminimalse
789     \suftesi@mathextendedse
790 \or
791     \suftesi@mathminimaltrue
792 \or
793     \suftesi@mathextendedtrue
794 \fi}
```

Greek fonts

```
795 \define@choicekey{}{greekfont}[\val\nr]{%
796     none,artemisia,porson,bodoni,cbgreek}[none]{%
797 \ifcase\nr\relax
798     \suftesi@greekfontfalse
799 \or
800     \suftesi@greekfonttrue\suftesi@artemisiatrue
801 \or
802     \suftesi@greekfonttrue\suftesi@porsontrue
803 \or
804     \suftesi@greekfonttrue\suftesi@bodonittrue
805 \or
806     \suftesi@greekfonttrue\suftesi@cbgreektrue
807 \fi}
```

Other options

Indentation

```
808 \define@choicekey{}{parindent}[\val\nr]
809     {compact,wide}[compact]{%
810 \ifcase\nr\relax
```

```
811 \setlength{\parindent}{1em}
812 \or
813 \setlength{\parindent}{1.5em}
814 \fi}
```

Part page

```
815 \define@choicekey{}{partpage}[\val\nr]{true,false}[true]{%
816 \ifcase\nr\relax
817   \suftesi@partpagetrue
818 \or
819   \relax
820 \fi}
```

Draftdate

```
821 \define@choicekey{}{draftdate}[\val\nr]
822   {true,false}[true]{%
823 \ifcase\nr\relax
824   \suftesi@draftdatetrue
825 \or
826 \fi}
```

View mode

```
827 \define@choicekey{}{version}[\val\nr]
828   {screen,cscreen,draft,final}[draft]{%
829 \ifcase\nr\relax
830   \suftesi@screentru
831 \or
832   \suftesi@screentru
833   \suftesi@screencenteredtru
834 \or
835 \or
836   \AtBeginDocument{\crop[off]}
837 \fi}
838 \define@choicekey{}{crop}[\val\nr]
839   {true,false}[true]{%
840 \ClassWarningNoLine{suftesi}{%
841   'crop' option is deprecated.\MessageBreak
842   Use 'version' option instead}
843 \ifcase\nr\relax
844   \setkeys{}{version=draft}
845 \or
846   \setkeys{}{version=screen}
847 \fi}
```

Titlepage

```
848 \define@choicekey{}{titlepage}[\val\nr]
849   {true,false}[true]{%
850 \ifcase\nr\relax
851   \titlepagetrue
852 \or
```

```

853  \@titlepagefalse
854 \fi}

Pre-defined styles

855 \define@choicekey{}{style}{[\val\nr]
856   {roman1,roman2,roman3,roman4,roman5,roman6,
857   italic1,italic2,italic3,italic4,italic5,italic6,
858   italic7,italic8,italic9,italic10,italic11,italic12,
859   smallcaps1,smallcaps2,smallcaps3,smallcaps4,smallcaps5,smallcaps6,
860   smallcaps7,smallcaps8,smallcaps9,smallcaps10,smallcaps11,smallcaps12,
861   FSPLa,FSPLb,FSPLc}
862   [roman1]{%
863 \ifcase\nr\relax

```

The ‘roman’ styles

```

864   \setkeys{}{chapstyle=left}
865 \or
866   \setkeys{}{chapstyle=center}
867 \or
868   \setkeys{}{chapstyle=right}
869 \or
870   \setkeys{}{chapstyle=parleft}
871 \or
872   \setkeys{}{chapstyle=parcenter}
873 \or
874   \setkeys{}{chapstyle=parright}
875 \or

```

The ‘italic’ styles

```

876   \setkeys{}{
877     chapstyle=left,
878     chapfont=italic,
879     tocchapfont=italic,
880     headerfont=italic}
881 \or
882   \setkeys{}{
883     chapstyle=center,
884     chapfont=italic,
885     tocchapfont=italic,
886     headerfont=italic}
887 \or
888   \setkeys{}{
889     chapstyle=right,
890     chapfont=italic,
891     tocchapfont=italic,
892     headerfont=italic}
893 \or
894   \setkeys{}{
895     chapstyle=parleft,
896     chapfont=italic,

```

```

897     tocchapfont=italic,
898     headerfont=italic}
899 \or
900   \setkeys{}{
901     chapstyle=parcenter,
902     chapfont=italic,
903     tocchapfont=italic,
904     headerfont=italic}
905 \or
906   \setkeys{}{
907     chapstyle=parright,
908     chapfont=italic,
909     tocchapfont=italic,
910     headerfont=italic}
911 \or
912   \setkeys{}{
913     chapstyle=left,
914     chapfont=italic,
915     tocchapfont=italic,
916     secfont=smallcaps,
917     headerfont=italic}
918 \or
919   \setkeys{}{
920     chapstyle=center,
921     chapfont=italic,
922     tocchapfont=italic,
923     secfont=smallcaps,
924     headerfont=italic}
925 \or
926   \setkeys{}{
927     chapstyle=right,
928     chapfont=italic,
929     tocchapfont=italic,
930     secfont=smallcaps,
931     headerfont=italic}
932 \or
933   \setkeys{}{
934     chapstyle=parleft,
935     chapfont=italic,
936     tocchapfont=italic,
937     secfont=smallcaps,
938     headerfont=italic}
939 \or
940   \setkeys{}{
941     chapstyle=parcenter,
942     chapfont=italic,
943     tocchapfont=italic,
944     secfont=smallcaps,
945     headerfont=italic}
946 \or

```

```

947  \setkeys{}{
948    chapstyle=parright,
949    chapfont=italic,
950    tocchapfont=italic,
951    secfont=smallcaps,
952    headerfont=italic}
953 \or

```

The `smallcaps`' styles

```

954  \setkeys{}{
955    chapstyle=left,
956    chapfont=smallcaps,
957    tocchapfont=smallcaps,
958    headerfont=smallcaps}
959 \or
960  \setkeys{}{
961    chapstyle=center,
962    chapfont=smallcaps,
963    tocchapfont=smallcaps,
964    headerfont=smallcaps}
965 \or
966  \setkeys{}{
967    chapstyle=right,
968    chapfont=smallcaps,
969    tocchapfont=smallcaps,
970    headerfont=smallcaps}
971 \or
972  \setkeys{}{
973    chapstyle=parleft,
974    chapfont=smallcaps,
975    tocchapfont=smallcaps,
976    headerfont=smallcaps}
977 \or
978  \setkeys{}{
979    chapstyle=parcenter,
980    chapfont=smallcaps,
981    tocchapfont=smallcaps,
982    headerfont=smallcaps}
983 \or
984  \setkeys{}{
985    chapstyle=parright,
986    chapfont=smallcaps,
987    tocchapfont=smallcaps,
988    headerfont=smallcaps}
989 \or
990  \setkeys{}{
991    chapstyle=left,
992    chapfont=smallcaps,
993    tocchapfont=smallcaps,
994    secfont=smallcaps,

```

```

995   headerfont=smallcaps}
996 \or
997   \setkeys{}{
998     chapstyle=center,
999     chapfont=smallcaps,
1000    tocchapfont=smallcaps,
1001    secfont=smallcaps,
1002    headerfont=smallcaps}
1003 \or
1004   \setkeys{}{
1005     chapstyle=right,
1006     chapfont=smallcaps,
1007     tocchapfont=smallcaps,
1008     secfont=smallcaps,
1009     headerfont=smallcaps}
1010 \or
1011   \setkeys{}{
1012     chapstyle=parleft,
1013     chapfont=smallcaps,
1014     tocchapfont=smallcaps,
1015     secfont=smallcaps,
1016     headerfont=smallcaps}
1017 \or
1018   \setkeys{}{
1019     chapstyle=parcenter,
1020     chapfont=smallcaps,
1021     tocchapfont=smallcaps,
1022     secfont=smallcaps,
1023     headerfont=smallcaps}
1024 \or
1025   \setkeys{}{
1026     chapstyle=parright,
1027     chapfont=smallcaps,
1028     tocchapfont=smallcaps,
1029     secfont=smallcaps,
1030     headerfont=smallcaps}
1031 \or

```

The FSPL styles

```

1032 \suftesi@periodicalaureottrue
1033 \suftesi@FSPLtrue
1034   \setkeys{}{%
1035     pagelayout=periodicalaureo,
1036     style=roman5,
1037     chapnumstyle=roman,
1038     headerstyle=inner,
1039     footnotestyle=hung,
1040     liststyle=indented,
1041     tocstyle=leftpage}
1042 \disable@keys{}

```

```

1043 {structure,documentstructure,pagelayout,partfont,chapfont,secfont,%
1044 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
1045 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
1046 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
1047 quotesize,footnotestyle,liststyle,captionstyle,parindent}
1048 \or
1049 \suftesi@periodicalaureottrue
1050 \suftesi@FSPLtrue
1051 \setkeys{}{%
1052   pagelayout=periodicalaureo,
1053   style=italic5,
1054   chapnumstyle=roman,
1055   headerstyle=inner,
1056   headerfont=italic,
1057   footnotestyle=hung,
1058   liststyle=indented,
1059   tocstyle=leftpage}
1060 \disable@keys{}
1061 {structure,documentstructure,pagelayout,partfont,chapfont,secfont,%
1062 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
1063 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
1064 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
1065 quotesize,footnotestyle,liststyle,captionstyle,parindent}
1066 \or
1067 \suftesi@periodicalaureottrue
1068 \suftesi@FSPLtrue
1069 \setkeys{}{%
1070   pagelayout=periodicalaureo,
1071   style=smallcaps5,
1072   chapnumstyle=roman,
1073   headerstyle=inner,
1074   headerfont=smallcaps,
1075   secfont=smallcaps,
1076   footnotestyle=hung,
1077   liststyle=indented,
1078   tocstyle=leftpage}
1079 \disable@keys{}
1080 {structure,documentstructure,pagelayout,partfont,chapfont,secfont,%
1081 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
1082 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
1083 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
1084 quotesize,footnotestyle,liststyle,captionstyle,parindent}
1085 \fi}

```

Options for collection document structure

```

1086 \define@choicekey{}{papertitlestyle}[\val\nr]{%
1087   left,center,right}[left]{%
1088 \ifcase\nr\relax
1089   \def\SUF@lr@coll@titleSwitch{\filright}

```

```

1090 \or
1091   \def\SUF@lr@coll@titleSwitch{\filcenter}
1092 \or
1093   \def\SUF@lr@coll@titleSwitch{\filleft}
1094 \fi}
1095 \define@choicekey{}{revauthortitle}[\val\nr]
1096   {true,false}[false]{%
1097 \ifcase\nr\relax
1098 \suftesi@reverseauthortitletrue
1099 \or\relax
1100 \fi}
1101 \define@choicekey{}{titlefont}[\val\nr]{roman,italic,smallcaps}[roman]{%
1102 \ifcase\nr\relax
1103 \def\SUF@titlefont@Switch{\relax}
1104 \or
1105 \def\SUF@titlefont@Switch{\itshape}
1106 \or
1107 \def\SUF@titlefont@Switch{\expandafter\SUF@titlesmallcaps}
1108 \fi}
1109
1110 \define@choicekey{}{authorfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
1111 \ifcase\nr\relax
1112 \def\SUF@authorfont@Switch{\relax}
1113 \or
1114 \def\SUF@authorfont@Switch{\itshape}
1115 \or
1116 \def\SUF@authorfont@Switch{\expandafter\SUF@titlesmallcaps}
1117 \fi}

```

Execute and process options

```

1118 \ExecuteOptionsX<>{
1119   structure=book,
1120   captionstyle=standard,
1121   marginpar=true,
1122   parindent=compact,
1123   tocstyle=standard,
1124   defaultfont=cochineal,
1125   mathfont=minimal,
1126   greekfont=none,
1127   pagelayout=standard,
1128   headerstyle=inner,
1129   liststyle=bulged,
1130   footnotestyle=bulged,
1131   quotesize=footnotesize,
1132   quotestyle=center,
1133   partstyle=left,
1134   chapstyle=left,
1135   secstyle=left,
1136   subsecstyle=left,
1137   subsubsecstyle=left,

```

```

1138 partfont=roman,
1139 chapfont=roman,
1140 secfont=italic,
1141 subsecfont=roman,
1142 subsubsecfont=roman,
1143 headerfont=roman,
1144 partnumstyle=Roman,
1145 chapnumstyle=arabic,
1146 secnumstyle=arabic,
1147 subseccnumstyle=arabic,
1148 subsubseccnumstyle=arabic,
1149 smallcapsstyle=low,
1150 titlefont=italic,
1151 authorfont=roman,
1152 toctitlefont=italic,
1153 tocauthorfont=roman,
1154 revauthortitle=false,
1155 papertitlestyle=left,
1156 authorfont=roman,
1157 titlefont=italic,
1158 tocchapfont=roman,
1159 tocsecfont=roman,
1160 tocsubsecfont=roman,
1161 tocsubsubsecfont=roman}
1162 \ProcessOptionsX<>\relax

```

The use of the `\XKV@useoption` command, provided by the `xkeyval`, is a trick to delete the option given as its argument from the list stored in `\@unusedoptionlist` so that the option will not produce the “Unused global options” message:

```

1163 \XKV@useoption{a4paper} \XKV@useoption{10pt}
1164 \XKV@useoption{11pt} \XKV@useoption{12pt}
1165 \XKV@useoption{oneside} \XKV@useoption{twoside}
1166 \XKV@useoption{onecolumn} \XKV@useoption{twocolumn}
1167 \XKV@useoption{titlepage} \XKV@useoption{notitlepage}
1168 \XKV@useoption{openright} \XKV@useoption{openany}
1169 \XKV@useoption{leqno} \XKV@useoption{fleqn}
1170 \XKV@useoption{a5paper} \XKV@useoption{b5paper}
1171 \XKV@useoption{legalpaper}\XKV@useoption{executivepaper}
1172 \XKV@useoption{landscape}

```

A trick to delete the class options from `\XKV@classoptionslist`, in order to avoid incompatibility with packages using options defined by `suftesi` too. Thanks to Enrico Gregorio!

```
1173 \def\XKV@classoptionslist{}
```

Basic packages

```

1174 \RequirePackage{color}
1175     \definecolor{sufred}{rgb}{0.5,0,0}
1176     \definecolor{sufgray}{rgb}{0.5,0.5,0.5}
1177 \RequirePackage{multicol}
1178 \RequirePackage{emptypage}
1179 \RequirePackage{microtype}
1180 \RequirePackage{iftex}

```

```

1181  \ifLuaTeX
1182    \RequirePackage{luatex85}
1183  \else
1184  \fi

The FSPL style requires a verbose colophon which uses specific icons:
1185 \ifsuftesi@FSPL
1186  \RequirePackage{cclicenses}
1187  \else
1188 \fi

```

Page layout

The `\geometry` command must be declare before the `fontenc` package. If declared after it, the `heightrounded` option becomes ineffective and many underfull vertical boxes may occur.

```

1189 \ifsuftesi@screen
1190  \newcommand*\crop[1][]{}
1191    \ifsuftesi@screencentered
1192      \geometry{hmarginratio=1:1}
1193    \else
1194    \fi
1195 \else
1196  \RequirePackage[a4,cam,center]{crop}
1197 \fi

```

Fonts

With X_ET_EX we do not load any fonts. Anyway the `fontspec` package is required because some commands of the class are base on it.

```

1198 \unless\ifPDFTeX%if xelatex or lualatex
1199 \AtBeginDocument{%
1200 \@ifpackageloaded{fontspec}%
1201   {\relax}%
1202   {\ClassError{suftesi}%
1203    {*****\MessageBreak
1204     * For using sufftesi with XeLaTeX\MessageBreak
1205     * load either 'fontspec' or 'mathspec'\MessageBreak
1206     * For using sufftesi with LuaLaTeX\MessageBreak
1207     * load 'fontspec' \MessageBreak
1208    *****}%
1209    {*****\MessageBreak
1210     * For using sufftesi with XeLaTeX\MessageBreak
1211     * load either 'fontspec' or 'mathspec'\MessageBreak
1212     * For using sufftesi with LuaLaTeX\MessageBreak
1213     * load 'fontspec' \MessageBreak
1214    *****}}%
1215 }
1216 \else% if pdftex
1217 \RequirePackage[LGR,T1]{fontenc}
1218 \RequirePackage{substitutefont}
1219 \AtBeginDocument{\fontencoding{T1}\selectfont}

```

Now we load the macros for the `defaultfont` option. The greek fonts by the Greek Font Society are available only with `palatino`, `libertine` and `cochineal` options. A warning appears if the `cbgreek` option is unused.

```

1220 \ifsuftesi@nofont
1221     \ifsuftesi@greekfont
1222         \ClassWarningNoLine{suftesi}{%
1223             Unused 'greekfont' option}%
1224         \suftesi@greekfontfalse
1225         \else\suftesi@greekfontfalse\fi
1226 \else
1227 \ifsuftesi@standard
1228     \RequirePackage{lmodern}
1229     \ifsuftesi@greekfont
1230         \ClassWarningNoLine{suftesi}{%
1231             Unused 'greekfont' option}%
1232         \suftesi@greekfontfalse
1233         \else\suftesi@greekfontfalse\fi
1234 \else

```

Previous versions of the class were based on Palatino (`mathpazo`), Iwona and Bera Mono. Now this combination is provided only for backward compatibility.

```

1235 \ifsuftesi@compatibility
1236     \RequirePackage[osf,sc]{mathpazo}
1237     \RequirePackage[scaled=0.8]{beramono}
1238         \renewcommand{\sfdefault}{iwona}
1239     \ifsuftesi@greekfont
1240     \ifsuftesi@bodoni
1241         \gdef\SUFFntscale{0.96}
1242     \else
1243     \ifsuftesi@artemisia
1244         \gdef\SUFFntscale{0.97}
1245     \else
1246     \ifsuftesi@porson
1247         \gdef\SUFFntscale{1.18}
1248     \else
1249     \ifsuftesi@cbgreek
1250         \def\lmfntscale{1.06}
1251     \else
1252     \fi
1253     \fi
1254     \fi
1255     \fi
1256     \else
1257         \ClassWarningNoLine{suftesi}{\MessageBreak
1258             If you need the Greek font remember\MessageBreak
1259             to set one of the following options:\MessageBreak
1260             greekfont=artemisia,\MessageBreak
1261             greekfont=porson,\MessageBreak
1262             greekfont=cbgreek}
1263     \fi
1264 \else

```

```

1265 \ifsuftesi@palatino
1266   \RequirePackage[full]{textcomp}
1267     \RequirePackage{newpxtext}
1268     \RequirePackage[scaled=1.06]{biolinum}
1269     \RequirePackage[varqu,varl]{inconsolata}
1270   \ifsuftesi@mathextended
1271     \RequirePackage{amsthm}
1272     \RequirePackage[bigdelims,vvarbb]{newpxmath}
1273     \RequirePackage[cal=boondoxo]{mathalfa}
1274   \else
1275     \ifsuftesi@mathminimal
1276       \RequirePackage[bigdelims,vvarbb]{newpxmath}
1277     \else
1278       \fi
1279       \fi
1280       \useosf
1281       \useproportional
1282     \ifsuftesi@greekfont
1283       \ifsuftesi@bodoni
1284         \gdef\SUFFntscale{0.96}
1285       \else
1286         \ifsuftesi@artemisia
1287           \gdef\SUFFntscale{0.97}
1288         \else
1289           \ifsuftesi@porson
1290             \gdef\SUFFntscale{1.18}
1291           \else
1292             \ifsuftesi@cbgreek
1293               \def\lmfnts{1.06}
1294             \else
1295               \fi
1296             \fi
1297             \fi
1298             \fi
1299             \else
1300               \ClassWarningNoLine{suftesi}{\MessageBreak
1301                 If you need the Greek font remember\MessageBreak
1302                 to set one of the following options:\MessageBreak
1303                 greekfont=artemisia,\MessageBreak
1304                 greekfont=porson,\MessageBreak
1305                 greekfont=cbgreek}
1306               \fi
1307 \else
1308   \ifsuftesi@libertine
1309     \RequirePackage{textcomp}
1310     \RequirePackage[sb]{libertine}
1311     \RequirePackage[varqu,varl,scaled=0.94]{inconsolata}
1312   \ifsuftesi@mathextended
1313     \RequirePackage{amsthm}
1314     \RequirePackage{libertinust1math}

```

```

1315 \RequirePackage[cal=stix,scr=boondoxo,bb=boondox]{mathalfa}
1316 \else
1317 \ifsuftesi@mathminimal
1318 \RequirePackage{libertinust1math}
1319 \else
1320 \fi
1321 \fi
1322     \useosf
1323     \ifsuftesi@bodoni
1324         \gdef\SUFFntscale{0.9}
1325     \else
1326         \ifsuftesi@artemisia
1327             \gdef\SUFFntscale{0.91}
1328         \else
1329             \ifsuftesi@porson
1330                 \gdef\SUFFntscale{1.1}
1331             \else
1332                 \fi
1333             \fi
1334         \fi
1335 \else
1336     \ifsuftesi@cochineal
1337         \RequirePackage{textcomp}
1338             \RequirePackage{cochineal}
1339             \RequirePackage[varqu,varl,var0]{inconsolata}
1340             \RequirePackage{biolinum}
1341             \ifsuftesi@mathextended
1342                 \RequirePackage{amsthm}
1343                 \RequirePackage[cochineal,bigdelims,cmintegrals,vvarbb]{newtxmath}
1344                 \RequirePackage[cal=boondoxo]{mathalfa}
1345             \else
1346                 \ifsuftesi@mathminimal
1347                     \RequirePackage[cochineal,bigdelims,cmintegrals,vvarbb]{newtxmath}
1348                 \else
1349                     \fi
1350                 \fi
1351             \useosf
1352             \useproportional
1353             \ifsuftesi@bodoni
1354                 \gdef\SUFFntscale{0.9}
1355             \else
1356                 \ifsuftesi@artemisia
1357                     \gdef\SUFFntscale{0.905}
1358                 \else
1359                     \ifsuftesi@porson
1360                         \gdef\SUFFntscale{1.1}
1361                     \else
1362                         \fi
1363                     \fi
1364                 \fi

```

```

1365      \else
1366      \fi
1367      \fi
1368      \fi
1369      \fi
1370      \fi
1371      \fi
1372 \fi
1373 \unless\ifPDFTeX\else
1374 \ifsuftesi@greekfont
1375   \ifsuftesi@artemisia
1376     \def\SUF@greekfamily{artemisia}
1377   \else
1378     \ifsuftesi@porson
1379       \def\SUF@greekfamily{porson}
1380     \else
1381       \ifsuftesi@bodoni
1382         \def\SUF@greekfamily{bodoni}
1383     \else
1384       \ifsuftesi@cbgreek
1385         \def\SUF@greekfamily{lmr}
1386       \else
1387       \fi
1388     \fi
1389   \fi
1390 \fi

```

Thanks to Claudio Beccari for the following macro.

```

1391 \AtBeginDocument{
1392   \substitutefont{LGR}{\rmdefault}{\SUF@greekfamily}
1393   \DeclareRobustCommand{\greektext}{%
1394     \usefont{LGR}{\SUF@greekfamily}{\f@series}{\f@shape}
1395     \def\encodingdefault{LGR}}
1396   \DeclareTextFontCommand{\textgreek}{\greektext}
1397 \ifsuftesi@cbgreek
1398 \else

```

We redefine the font definitions of the GFS fonts in order to scale the fonts according to the roman default.

```

1399 \DeclareFontFamily{LGR}{bodoni}{}
1400 \DeclareFontShape{LGR}{bodoni}{m}{n}{<-> s * [\SUFntscale] gbonirg6a}{}
1401 \DeclareFontShape{LGR}{bodoni}{m}{it}{<-> s * [\SUFntscale] gbonii6a}{}
1402 \DeclareFontShape{LGR}{bodoni}{b}{n}{<-> s * [\SUFntscale] gbonib6a}{}
1403 \DeclareFontShape{LGR}{bodoni}{b}{it}{<-> s * [\SUFntscale] gbonibi6a}{}
1404 \DeclareFontShape{LGR}{bodoni}{m}{sl}{<-> s * [\SUFntscale] gbonio6a}{}
1405 \DeclareFontShape{LGR}{bodoni}{b}{sl}{<-> s * [\SUFntscale] gbonibo6a}{}
1406 \DeclareFontShape{LGR}{bodoni}{m}{sc}{<-> s * [\SUFntscale] gbonisc6a}{}
1407 \DeclareFontShape{LGR}{bodoni}{m}{sco}{<-> s * [\SUFntscale] gbonisco6a}{}
1408
1409 \DeclareFontShape{LGR}{bodoni}{bx}{n}{<-> s * [\SUFntscale] gbonib6a}{}
1410 \DeclareFontShape{LGR}{bodoni}{bx}{it}{<-> s * [\SUFntscale] gbonibi6a}{}

```

```

1411 \DeclareFontShape{LGR}{bodoni}{bx}{s1}{<-> s * [\SUFfntscale] gbonib6a}{}
1412
1413 \DeclareFontFamily{LGR}{artemisia}{}
1414 \DeclareFontShape{LGR}{artemisia}{m}{n}{<-> s * [\SUFfntscale] gartemisiarg6a}{}
1415 \DeclareFontShape{LGR}{artemisia}{m}{it}{<-> s * [\SUFfntscale] gartemisiai6a}{}
1416 \DeclareFontShape{LGR}{artemisia}{b}{n}{<-> s * [\SUFfntscale] gartemisiab6a}{}
1417 \DeclareFontShape{LGR}{artemisia}{b}{it}{<-> s * [\SUFfntscale] gartemisiabi6a}{}
1418 \DeclareFontShape{LGR}{artemisia}{m}{sl}{<-> s * [\SUFfntscale] gartemisiao6a}{}
1419 \DeclareFontShape{LGR}{artemisia}{b}{sl}{<-> s * [\SUFfntscale] gartemisiabo6a}{}
1420 \DeclareFontShape{LGR}{artemisia}{m}{sc}{<-> s * [\SUFfntscale] gartemisiasc6a}{}
1421 \DeclareFontShape{LGR}{artemisia}{m}{sco}{<-> s * [\SUFfntscale] gartemisisasco6a}{}
1422
1423 \DeclareFontShape{LGR}{artemisia}{bx}{n}{<-> s * [\SUFfntscale] gartemisiaab6a}{}
1424 \DeclareFontShape{LGR}{artemisia}{bx}{it}{<-> s * [\SUFfntscale] gartemisiabi6a}{}
1425 \DeclareFontShape{LGR}{artemisia}{bx}{sl}{<-> s * [\SUFfntscale] gartemisiabo6a}{}
1426
1427 \DeclareFontFamily{LGR}{porson}{}
1428 \DeclareFontShape{LGR}{porson}{m}{n}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1429 \DeclareFontShape{LGR}{porson}{m}{it}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1430 \DeclareFontShape{LGR}{porson}{b}{n}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1431 \DeclareFontShape{LGR}{porson}{b}{it}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1432 \DeclareFontShape{LGR}{porson}{m}{sl}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1433 \DeclareFontShape{LGR}{porson}{b}{sl}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1434 \DeclareFontShape{LGR}{porson}{m}{sc}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1435
1436 \DeclareFontShape{LGR}{porson}{bx}{n}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1437 \DeclareFontShape{LGR}{porson}{bx}{it}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1438 \DeclareFontShape{LGR}{porson}{bx}{sl}{<-> s * [\SUFfntscale] gporsonrg6a}{}
1439 \fi
1440 \else
1441 \fi
1442 \fi

```

Section titles

```

1443 \RequirePackage{titlesec}
1444     \newlength{\sectionsep}
1445     \setlength{\sectionsep}{\dimexpr(\baselineskip) plus 1pt minus 1pt}
1446 \unless\ifPDFTeX% if xetex or luatex
1447     \ DeclareRobustCommand{\SUF@TOCtitlesmallcaps}[1]{%
1448         \addfontfeature{LetterSpace=10}\scshape\suftesi@MakeTextTOCLowercase{#1}}
1449     \ DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1450         \addfontfeature{LetterSpace=10}\scshape\suftesi@MakeTextLowercase{#1}}
1451     \ DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1452         \addfontfeature{LetterSpace=10}\scshape\suftesi@MakeTextLowercase{#1}}
1453 \else% if pdfTeX
1454     \ DeclareRobustCommand{\SUF@TOCtitlesmallcaps}[1]{%
1455         \scshape\suftesi@MakeTextTOCLowercase{\textls*{#1}}}{%
1456     \ DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1457         \scshape\suftesi@MakeTextLowercase{\textls*{#1}}}{%

```

```

1458 \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1459   \scshape\suftesi@MakeTextLowercase{\textls*[#1]}}%
1460 \fi

  Default styles:
1461 \newlength\SUF@ADJnumparchap
1462 \def\SUF@default@CHAPTER{%
1463 \ifsuftesi@numparchap
1464   \titleformat{\chapter}[display]
1465     {\SUF@chaptersize\SUF@lr@CHAPSwitch}
1466     {\SUF@thechapter\SUF@dotchap}
1467     {2ex}
1468     {\SUF@CHAP@StyleSwitch}
1469   \else
1470   \titleformat{\chapter}[hang]
1471     {\SUF@chaptersize\SUF@lr@CHAPSwitch}
1472     {\SUF@thechapter\SUF@dotchap}
1473     {3em}
1474     {\SUF@CHAP@StyleSwitch}
1475   \fi
1476 \ifsuftesi@numparchap
1477   \setlength{\SUF@ADJnumparchap}{-2.5\baselineskip}
1478   \else
1479   \setlength{\SUF@ADJnumparchap}{0pt}
1480 \fi}

1481 \def\SUF@default@SECTIONS{%
1482 \ifsuftesi@numparsec
1483 %\titleformat{\section}[display]
1484 %  {\SUF@sectionsiz\SUF@lr@SECSwitch}
1485 %  {\ifsuftesi@article\SUF@thesection
1486 %    \else\thesection\fi\SUF@dotsec}
1487 %  {0ex}
1488 %  {\SUF@SEC@StyleSwitch}
1489 \titleformat{\section}[display]
1490 {\SUF@sectionsiz\SUF@lr@SECSwitch}
1491 {\SUF@thesection\SUF@dotsec}
1492 {0ex}
1493 {\SUF@SEC@StyleSwitch}
1494 \titlespacing*{\section}{0em}{\sectionsep}{\sectionsep}[0em]
1495 \else
1496 %\titleformat{\section}[hang]
1497 %  {\SUF@sectionsiz\SUF@lr@SECSwitch}
1498 %  {\ifsuftesi@article\SUF@thesection
1499 %    \else\thesection\fi\SUF@dotsec}
1500 %  {1em}
1501 %  {\SUF@SEC@StyleSwitch}
1502 \titleformat{\section}[hang]
1503 {\SUF@sectionsiz\SUF@lr@SECSwitch}
1504 {\SUF@thesection\SUF@dotsec}
1505 {1em}}

```

```

1506 {\SUF@SEC@StyleSwitch}
1507 \titlespacing*{\section}{0ex}{\sectionsep}{\sectionsep}[0ex]
1508 \fi
1509 \ifsoftesi@numparsubsec
1510 %\titleformat{\subsection}[display]
1511 % {\SUF@subsectionsiz\SUF@lr@SUBSECSwitch}
1512 % {\textnormal\thesubsection}
1513 % {0ex}
1514 % {\SUF@SUBSEC@StyleSwitch}
1515 \titleformat{\subsection}[display]
1516 {\SUF@subsectionsiz\SUF@lr@SUBSECSwitch}
1517 {\textnormal\SUF@thesubsection\SUF@dotsubsec}
1518 {0ex}
1519 {\SUF@SUBSEC@StyleSwitch}
1520 \titlespacing*{\subsection}{0em}{\sectionsep}{\sectionsep}[0em]
1521 \else
1522 %\titleformat{\subsection}[hang]
1523 % {\SUF@subsectionsiz\SUF@lr@SUBSECSwitch}
1524 % {\textnormal\thesubsection}
1525 % {1em}
1526 % {\SUF@SUBSEC@StyleSwitch}
1527 \titleformat{\subsection}[hang]
1528 {\SUF@subsectionsiz\SUF@lr@SUBSECSwitch}
1529 {\textnormal\SUF@thesubsection\SUF@dotsubsec}
1530 {1em}
1531 {\SUF@SUBSEC@StyleSwitch}
1532 \titlespacing*{\subsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1533 \fi
1534 \ifsoftesi@numparsubsubsec
1535 %\titleformat{\subsubsection}[display]
1536 % {\SUF@subsectionsiz\SUF@lr@SUBSUBSECSwitch}
1537 % {\textnormal\thesubsubsection}
1538 % {0ex}
1539 % {\SUF@SUBSUBSEC@StyleSwitch}
1540 \titleformat{\subsubsection}[display]
1541 {\SUF@subsectionsiz\SUF@lr@SUBSUBSECSwitch}
1542 {\textnormal\SUF@thesubsubsection\SUF@dotsubsubsec}
1543 {0ex}
1544 {\SUF@SUBSUBSEC@StyleSwitch}
1545 \titlespacing*{\subsubsection}{0em}{\sectionsep}{\sectionsep}[0em]
1546 \else
1547 %\titleformat{\subsubsection}[hang]
1548 % {\SUF@subsectionsiz\SUF@lr@SUBSUBSECSwitch}
1549 % {\textnormal\thesubsubsection}
1550 % {1em}
1551 % {\SUF@SUBSUBSEC@StyleSwitch}
1552 \titleformat{\subsubsection}[hang]
1553 {\SUF@subsectionsiz\SUF@lr@SUBSUBSECSwitch}
1554 {\textnormal\SUF@thesubsubsection\SUF@dotsubsubsec}

```

```

1555 {1em}
1556 {\SUF@SUBSUBSEC@StyleSwitch}
1557 \titlespacing*{\subsubsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1558 \fi
1559 }
1560 \SUF@default@CHAPTER
1561 \SUF@default@SECTIONS
1562 \ifsuftesi@periodical
1563 \titlespacing*{\chapter}{0em}{0\SUF@ADJnumparchap}{18ex}
1564 \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1565 \else
1566 \ifsuftesi@periodicalaureo
1567 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1568 \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1569 \else
1570 \ifsuftesi@compact
1571 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1572 \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1573 \else
1574 \ifsuftesi@compactaureo
1575 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1576 \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1577 \else
1578 \ifsuftesi@supercompact
1579 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1580 \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1581 \else
1582 \ifsuftesi@supercompactaureo
1583 \titlespacing*{\chapter}{0em}{\SUF@ADJnumparchap}{18ex}
1584 \titlespacing*{name=\chapter, numberless}{0em}{0pt}{18ex}
1585 \else%standard/standardaureo
1586 \titlespacing*{\chapter}{0em}{%
1587 \dimexpr 6ex+\SUF@ADJnumparchap}{18ex}
1588 \titlespacing*{name=\chapter, numberless}{0em}{6ex}{18ex}
1589 \fi
1590 \fi
1591 \fi
1592 \fi
1593 \fi
1594 \fi

```

Redefinitions for ‘article’ mode

```

1595 \ifsuftesi@article
1596 \def\chapter{\ClassError{suftesi}}
1597 {\noexpand\chapter level is undefined
1598 using 'structure=article'}
1599 {\noexpand\chapter level is undefined
1600 using 'structure=article'}}
1601 \setcounter{tocdepth}{3}
1602 \setcounter{secnumdepth}{3}

```

```

1603     \renewcommand\thesection{%
1604         \@arabic\c@section}
1605     \renewcommand\thesubsection{%
1606         \thesection.\@arabic\c@subsection}
1607     \renewcommand\thesubsubsection{%
1608         \thesubsection.\@arabic\c@subsubsection}
1609     \renewcommand\theparagraph{%
1610         \thesubsubsection.\@arabic\c@paragraph}
1611     \renewcommand\thesubparagraph{%
1612         \theparagraph.\@arabic\c@subparagraph}

The partpage options allows you to print a standard part page in article mode.

1613 \ifsuftesi@partpage
1614     \relax
1615     \else

```

In article mode the \part command is similar to a \section but with more vertical space before and after.

```

1616     \titleclass{\part}{straight}
1617     \titlespacing*\{\part\}{0ex}{2\sectionsep}{2\sectionsep}[0ex]
1618 \fi
1619 \ifsuftesi@numparpart
1620 \titleformat{\part}[display]
1621     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1622     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@the\part\SUF@dotpart}
1623     {2ex}
1624     {\SUF@PART@StyleSwitch}
1625 \else
1626 \titleformat{\part}[hang]
1627     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1628     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@the\part\SUF@dotpart}
1629     {1em}
1630     {\SUF@PART@StyleSwitch}
1631 \fi
1632 \else

```

The default ‘book’ mode

```

1633 \ifsuftesi@numparpart
1634 \titleformat{\part}[display]
1635     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1636     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@the\part\SUF@dotpart}
1637     {2ex}
1638     {\SUF@PART@StyleSwitch}
1639 \else
1640 \titleformat{\part}[hang]
1641     {\SUF@chaptersize\SUF@lr@PARTSwitch}
1642     {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@the\part\SUF@dotpart}
1643     {1em}
1644     {\SUF@PART@StyleSwitch}
1645 \fi
1646 \fi

```

```

1647
1648 \titleformat{\paragraph}[runin]
1649   {}
1650   {\theparagraph}
1651   {.5em}
1652   {\itshape}
1653   [{}]\hspace*{1em}]
1654 \titlespacing*{\paragraph}{\parindent}{.5\sectionsep}{.5\sectionsep}
1655 \titleformat{\subparagraph}[runin]
1656   {}
1657   {\thesubparagraph}
1658   {.5em}
1659   {}
1660   [{}]\hspace*{1em}]
1661 \titlespacing*{\subparagraph}{\parindent}{.5\sectionsep}{.5\sectionsep}

The biblatex package uses the book class definitions of bibliography and list of shorthands, so
we must redefine them according to the styles of suftesi, which does not use uppercase letters
in the headings.

1662 \ifsuftesi@article
1663 \AtBeginDocument{%
1664 \@ifpackageloaded{biblatex}{%
1665   \defbibheading{bibliography}[\refname]{%
1666     \section*{#1}%
1667     \markboth{#1}{#1}%
1668   }%
1669   \defbibheading{shorthands}[\losname]{%
1670     \section*{#1}%
1671     \markboth{#1}{#1}%
1672   }%
1673   \defbibheading{bibintoc}[\refname]{%
1674     \section*{#1}%
1675     \addcontentsline{toc}{section}{#1}%
1676     \markboth{#1}{#1}%
1677   }%
1678   \defbibheading{losintoc}[\losname]{%
1679     \section*{#1}%
1680     \addcontentsline{toc}{section}{#1}%
1681     \markboth{#1}{#1}%
1682   }%
1683   \defbibheading{losnumbered}[\losname]{%
1684     \section*{#1}%
1685     \if@twoside\markright{#1}\fi%
1686   }%
1687   \defbibheading{subbibliography}[\refname]{%
1688     \subsection*{#1}%
1689   }%
1690   \defbibheading{subbibintoc}[\refname]{%
1691     \subsection*{#1}%
1692     \addcontentsline{toc}{subsection}{#1}%
1693   }%
1694   \defbibheading{subbibnumbered}[\refname]{%
1695     \subsection*{#1}%
1696     \addcontentsline{toc}{subsection}{#1}%
1697   }%
1698   \relax}%
1699 }

```

```

1693 }%
1694 \else
1695 \AtBeginDocument{%
1696 \@ifpackagelloaded{biblatex}{%
1697   \defbibheading{bibliography}[\bibname]{%
1698     \chapter*{\#1}%
1699     \markboth{\#1}{\#1}%
1700   \defbibheading{shorthands}[\losname]{%
1701     \chapter*{\#1}%
1702     \markboth{\#1}{\#1}%
1703   \defbibheading{bibintoc}[\bibname]{%
1704     \chapter*{\#1}%
1705     \addcontentsline{toc}{chapter}{\#1}%
1706     \markboth{\#1}{\#1}%
1707   \defbibheading{losintoc}[\losname]{%
1708     \chapter*{\#1}%
1709     \addcontentsline{toc}{chapter}{\#1}%
1710     \markboth{\#1}{\#1}%
1711   \defbibheading{bibnumbered}[\bibname]{%
1712     \chapter{\#1}%
1713     \if@twoside\markright{\#1}\fi%
1714   \defbibheading{losnumbered}[\losname]{%
1715     \chapter{\#1}%
1716     \if@twoside\markright{\#1}\fi%
1717   \defbibheading{subbibliography}[\refname]{%
1718     \section*{\#1}%
1719     \if@twoside\markright{\#1}\fi%
1720   \defbibheading{subbibintoc}[\refname]{%
1721     \section*{\#1}%
1722     \addcontentsline{toc}{section}{\#1}%
1723     \if@twoside\markright{\#1}\fi%
1724   \defbibheading{subbibnumbered}[\refname]{%
1725     \section{\#1}}%
1726     {\relax}%
1727 }%
1728 \fi

```

Cover page

```

1729 \newcommand{\Ctitle}[1]{\def\@Ctitle{\#1}}
1730 \newcommand{\Csubtitle}[1]{\def\@Csubtitle{\#1}}
1731 \newcommand{\Cauthor}[1]{\def\@Cauthor{\#1}}
1732 \newcommand{\Ceditor}[1]{\def\@Ceditor{\#1}}
1733 \newcommand{\Cfoot}[1]{\def\@Cfoot{\#1}}
1734 \newcommand{\Cpagecolor}[1]{\def\@Cpagecolor{\#1}}
1735 \newcommand{\Cciclecolor}[1]{\def\@Cciclecolor{\#1}}
1736 \newcommand{\Ctextcolor}[1]{\def\@Ctextcolor{\#1}}
1737 \newcommand{\Cfootcolor}[1]{\def\@Cfootcolor{\#1}}
1738 \Cauthor{}
1739 \Ctitle{}

```

```

1740 \Csubtitle{}
1741 \Ceditor{}
1742 \Cfoot{}
1743 \Cpagecolor{gray!30}
1744 \Ctextcolor{white}
1745 \Cfootcolor{black}
1746 \AtBeginDocument{
1747 \@ifpackageloaded{tikz}{%
1748 \newcommand\makecover[1][]{%
1749 \begin{titlepage}
1750 \begin{tikzpicture}[overlay,remember picture]
1751   \draw[draw=none,fill=\@Cpagecolor]
1752     (current page.north west) rectangle (current page.south east);
1753   \node[anchor=center,yshift=.22\paperwidth] at (current page.center) (c) {};
1754   \draw[draw=none,fill=gray,#1]
1755     (c) circle (.38\paperwidth) ;
1756   \node[anchor=center] at (c) (author) {};
1757 \parbox{.7\paperwidth}{%
1758   \centering
1759   \ifx\@Cauthor\empty
1760     \else
1761       {\scshape\color{\@Ctextcolor}\@Cauthor\}
1762       \vspace*{\baselineskip}
1763     \fi
1764
1765   \ifx\@Ctitle\empty
1766     \else
1767       {\Huge\bfseries\color{\@Ctextcolor}\@Ctitle\`{i}ex}
1768     \fi
1769
1770   \ifx\@Csubtitle\empty
1771     \else
1772       {\smallskip\Large\color{\@Ctextcolor}\@Csubtitle\`{i}ex}
1773     \fi
1774
1775   \ifx\@Ceditor\empty
1776     \else
1777       {\vspace*{2\baselineskip}\color{\@Ctextcolor}\@Ceditor\`{i}ex}
1778     \fi
1779 };
1780 \ifx\@Cfoot\empty\else
1781   \node[xshift=.5\paperwidth,yshift=1cm,
1782     align=center,text=\@Cfootcolor,anchor=south]
1783   at (current page.south west) {\@Cfoot};
1784 \fi
1785 \end{tikzpicture}
1786 \end{titlepage}
1787 }
1788 }
1789 {\def\makecover{\ClassError{suftesi}{\MessageBreak%
```

```

1790 ****\MessageBreak
1791 * To use the \noexpand\makecover command\MessageBreak
1792 * load the 'tikz' package.\MessageBreak
1793 ****{\MessageBreak%
1794 ****\MessageBreak
1795 * To use the \noexpand\makecover command\MessageBreak
1796 * load the 'tikz' package.\MessageBreak
1797 ****}}}
1798 }

```

Title page

The new `\title` command has an optional argument which can be used in the headers.

```

1799 \def\isbn#1{\gdef@isbn{#1}}
1800   \def@issn{\@latex@warning@no@line{%
1801     No \noexpand\isbn given}}
1802 \def\doi#1{\gdef@doi{#1}}
1803   \def@doi{\@latex@warning@no@line{%
1804     No \noexpand\doi given}}
1805 \def\isbn#1{\gdef@issn{#1}}
1806   \def@issn{\@latex@warning@no@line{%
1807     No \noexpand\isbn given}}
1808
1809 \renewcommand*{\title}[2][]{{\gdef\@headtitle{#1}\gdef\@title{#2}}
1810   \edef\title{\noexpand\@dblarg
1811   \expandafter\noexpand\csname\string\title\endcsname}
1812   \def\@headtitle{--missing title--%
1813     \protect\ClassWarningNoLine{suftesi}{%
1814       No \string\title\space given \MessageBreak%
1815       See the class documentation for explanation}}
1816   \def\@title{--missing title--%
1817     \protect\ClassWarningNoLine{suftesi}{%
1818       No \string\title\space given\MessageBreak%
1819       See the class documentation for explanation}}
1820   \def\@author{--missing author--%
1821     \protect\ClassWarningNoLine{suftesi}{%
1822       No \string\author\space given\MessageBreak%
1823       See the class documentation for explanation}}
1824   For \titlepage (default) option:
1825 \if@titlepage% \titlepage
1826   \renewcommand\maketitle{\begin{titlepage}%
1827   \let\footnotesize\small
1828   \let\footnoterule\relax
1829   \let \footnote \thanks
1830   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1831   \null\vfil
1832   \vskip 60\p@
1833   \begin{center}%
1834     {\SUF@chaptersize\color{sufred}\sffamily%
1835      \if@smallcapschap%
```

```

1835      \SUF@titlesmallcaps{\@title}
1836      \else
1837      \ifsuftesi@article
1838      \ifsuftesi@smallcapssec
1839      \SUF@titlesmallcaps{\@title}
1840      \else
1841      \@title
1842      \fi
1843      \else
1844      \@title
1845      \fi
1846      \fi\par}%
1847      \vskip 3em%
1848      {\small\lineskip .75em%
1849      \begin{tabular}[t]{c}%
1850      \author
1851      \end{tabular}\par}%
1852      \vskip 1.5em%
1853      {\small\@date\par}%
1854      \end{center}\par
1855      \thanks
1856      \vfil\null
1857      \end{titlepage}%
1858      \setcounter{footnote}{0}%
1859      \global\let\thanks\relax
1860      \global\let\maketitle\relax
1861      \global\let\@thanks\empty
1862      \global\let\@date\empty
1863      \global\let\date\relax
1864      \global\let\and\relax}

```

Reproduces the standard \maketitle style:

```

1865 \newcommand\standardtitle{\begin{titlepage}%
1866   \let\footnotesize\small
1867   \let\footnoterule\relax
1868   \let \footnote \thanks
1869   \null\vfil
1870   \vskip 60\p@
1871   \begin{center}%
1872     {\LARGE \@title \par}%
1873     \vskip 3em%
1874     {\large
1875       \lineskip .75em%
1876       \begin{tabular}[t]{c}%
1877       \author
1878       \end{tabular}\par}%
1879       \vskip 1.5em%
1880     {\large \@date \par}%
1881   \end{center}\par
1882   \thanks

```

```

1883 \vfil\null
1884 \end{titlepage}%
1885 \setcounter{footnote}{0}%
1886 \global\let\thanks\relax
1887 \global\let\maketitle\relax
1888 \global\let\@thanks\@empty
1889     \global\let\@date\@empty
1890 \global\let\date\relax
1891 \global\let\and\relax}
1892 \else
    For notitlepage option:
1893 \renewcommand\maketitle{\par
1894     \begingroup
1895         \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1896         \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1897         \long\def\@makefntext##1{\parindent 1em\noindent
1898             \hb@xt@1.8em{%
1899                 \hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
1900         \if@twocolumn
1901             \ifnum \col@number=\@ne
1902                 \@maketitle
1903             \else
1904                 \twocolumn[\@maketitle]%
1905             \fi
1906         \else
1907             \newpage
1908             \global\@topnum\z@% Prevents figures from going at top of page.
1909             \@maketitle
1910             \fi
1911             \thispagestyle{plain}\@thanks
1912         \endgroup
1913         \setcounter{footnote}{0}%
1914         \global\let\thanks\relax
1915         \global\let\maketitle\relax
1916         \global\let\@maketitle\relax
1917         \global\let\@thanks\@empty
1918         \global\let\@date\@empty
1919         \global\let\date\relax
1920         \global\let\and\relax}
1921         \def\@maketitle{%
1922             \newpage
1923             \null
1924             \vskip 2em%
1925             \begin{center}%
1926                 \let \footnote \thanks
1927                 {\SUF@\chapter@size\color{sufred}\sffamily%
1928                 \if@suftesi@smallcapschap%
1929                     \SUF@titlesmallcaps{\@title}%
1930                 \else

```

```

1931      \ifsuftesi@article
1932          \ifsuftesi@smallcapssec
1933              \SUF@titlesmallcaps{\@title}
1934          \else
1935              \@title
1936          \fi
1937      \else
1938          \@title
1939      \fi
1940  \fi\par}%
1941      \vskip 1.5em%
1942  {\small\lineskip .5em%
1943      \begin{tabular}[t]{c}%
1944          \author\par
1945      \end{tabular}\par}%
1946      \vskip 1em%
1947  {\small\@date\par}%
1948  \end{center}%
1949  \par
1950  \vskip 1.5em}

```

Reproduces the standard `\maketitle` style:

```

1951 \newcommand\standardtitle{\par
1952  \begingroup
1953      \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1954      \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1955      \long\def\@makefntext##1{\par\indent 1em\noindent
1956          \hb@xt@1.8em{%
1957              \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
1958          \if@twocolumn
1959              \ifnum \col@number=\@ne
1960                  \@standardmaketitle
1961              \else
1962                  \twocolumn[\@standardmaketitle]%
1963              \fi
1964          \else
1965              \newpage
1966              \global\@topnum\z@
1967              \@standardmaketitle
1968          \fi
1969          \thispagestyle{plain}\@thanks
1970      \endgroup
1971      \setcounter{footnote}{0}%
1972      \global\let\thanks\relax
1973      \global\let\maketitle\relax
1974      \global\let\@standardmaketitle\relax
1975      \global\let\@thanks\empty
1976      \global\let\@date\empty
1977      \global\let\date\relax
1978      \global\let\and\relax}

```

```

1979 \def\@standardmaketitle{%
1980   \newpage
1981   \null
1982   \vskip 2em%
1983   \begin{center}%
1984     \let \footnote \thanks
1985     {\LARGE \@title \par}%
1986     \vskip 1.5em%
1987     {\large
1988       \lineskip .5em%
1989       \begin{tabular}[t]{c}%
1990         \author
1991       \end{tabular}\par}%
1992     \vskip 1em%
1993     {\large \@date}%
1994   \end{center}%
1995   \par
1996   \vskip 1.5em}
1997 \fi

```

The collection document structure

```

1998 \ifsuftesi@collection
1999 \newcounter{journalnumber}
2000 \newcounter{journalvolume}
2001 \newcounter{issue}
2002 \newcounter{title}
2003 \setcounter{title}{1}
2004 \newcounter{article}
2005 \setcounter{article}{0}
2006 \setcounter{journalnumber}{0}
2007 \setcounter{tocdepth}{0}
2008 \def\journalname#1{\gdef\@journalname{#1}}
2009   \def\@journalname{\@latex@warning@no@line{%
2010     No \noexpand\journalname given}}
2011 \def\journalvolume#1{\gdef\@journalvolume{#1}}
2012   \def\@journalvolume{\@latex@warning@no@line{%
2013     No \noexpand\journalvolume given}}
2014 \def\journalnumber#1{\gdef\@journalnumber{#1}}
2015   \def\@journalnumber{\@latex@warning@no@line{%
2016     No \noexpand\journalnumber given}}
2017 \def\issue#1{\gdef\@issue{#1}}
2018   \def\@issue{\@latex@warning@no@line{%
2019     No \noexpand\issue given}}
2020 \def\journalyear#1{\gdef\@journalyear{#1}}
2021   \def\@journalyear{\@latex@warning@no@line{%
2022     No \noexpand\journalyear given}}
2023 \def\journalwebsite#1{\gdef\@journalwebsite{\url{#1}}}
2024   \def\@journalwebsite{\@latex@warning@no@line{%
2025     No \noexpand\journalwebsite given}}

```

```

2026 \def\thanks#1{\footnotemark\ \protected@xdef@\thanks{%
2027   \@thanks\protect\footnotetext[\the\c@footnote]{#1}}}
2028 \def\fulljournal{\emph{\@journalname} \@journalnumber, %
2029   \@issue{} \@journalyear}
2030 \def\issuename#1{\gdef\@issuename{#1}}
2031 \def\collectiontitle#1{\gdef\@collectiontitle{#1}}
2032   \def\@collectiontitle{\@latex@warning@no@line{%
2033     No \noexpand\collectiontitle given}}
2034 \def\collectioneditor#1{\gdef\@collectioneditor{#1}}
2035   \def\@collectioneditor{\@latex@warning@no@line{%
2036     No \noexpand\collectioneditor given}}
2037 \renewcommand*{\title}[2][]{%
2038   \gdef\@headtitle{\#1}\gdef\@title{\#2}\markright{\#1}}
2039   \edef\title{\noexpand\@dblarg
2040 \expandafter\noexpand\csname\string\title\endcsname}
2041   \def\@headtitle{--missing title--%
2042     \protect\ClassWarningNoLine{suftesi}{%
2043       No \string\title\space given \MessageBreak%
2044       See the class documentation for explanation}}
2045 \def\@title{--missing title--%
2046     \protect\ClassWarningNoLine{suftesi}{%
2047       No \string\title\space given\MessageBreak%
2048       See the class documentation for explanation}}
2049 \def\@author{--missing author--%
2050     \protect\ClassWarningNoLine{suftesi}{%
2051       No \string\author\space given\MessageBreak%
2052       See the class documentation for explanation}}
2053
2054 \newcommand*{\l@title}[2]{%
2055   \ifnum \c@tocdepth >\m@ne
2056     \addpenalty{-\@highpenalty}%
2057     \vskip 1.0ex \oplus\p@
2058     \begingroup
2059       \parindent \z@ \rightskip \pnumwidth
2060       \parfillskip -\pnumwidth
2061       \advance\leftskip\pnumwidth
2062       \hskip -\leftskip
2063       #1\nobreak%
2064     \ifsuftesi@dottedtoc\dotfill%
2065       \nobreak\hb@xt@\pnumwidth{\hss #2}\par
2066     \else
2067       \ifsuftesi@raggedtoc%
2068         \nobreak\hskip\pnumwidth #2 \hfill\null\par
2069       \else
2070         \ifsuftesi@pagelefttoc
2071           \ClassError{suftesi}{%
2072             {\MessageBreak
2073               You can not use tocstyle=leftpage\MessageBreak
2074               with structure=collection}}

```

```

2075          {You can not use tocstyle=leftpage\MessageBreak
2076          with structure=collection}
2077          \else
2078          \nobreak\hfill #2\par
2079          \fi
2080          \fi
2081          \fi
2082          \penalty\@highpenalty
2083          \endgroup
2084          \fi}

2085 \renewcommand\maketitle{\par
2086 \begingroup
2087   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
2088   \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
2089   \long\def\@makefntext##1{\parindent 1em\noindent
2090     \hb@xt@1.8em{%
2091       \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
2092   \if@twocolumn
2093     \ifnum \col@number=\@ne
2094       \maketitle
2095     \else
2096       \twocolumn[\maketitle]%
2097     \fi
2098   \else
2099     \newpage
2100     \global\@topnum\z@    % Prevents figures from going at top of page.
2101     \maketitle
2102   \fi
2103   \thispagestyle{plain}\@thanks%
2104 \endgroup
2105 \% \setcounter{footnote}{0}%
2106 \setcounter{section}{0}%
2107 \% \global\let\thanks\relax
2108 \% \global\let\maketitle\relax
2109 \% \global\let\maketitle\relax
2110 \% \global\let\@thanks\@empty
2111 \% \global\let\@author\@empty
2112 \% \global\let\@date\@empty
2113 \% \global\let\@title\@empty
2114 \% \global\let\@title\relax
2115 \% \global\let\@author\relax
2116 \% \global\let\@date\relax
2117 \global\let\and\relax
2118 \let\thanks\@gobble}
2119 \AtBeginDocument{\def\@maketitle{%
2120   \refstepcounter{article}
2121   \SUF@chaptersize
2122   \SUF@lr@coll@titleSwitch
2123   \let\footnote\thanks

```

```

2124     \parindent=0pt
2125     {\ifsufthesi@reverseauthortitle
2126         \SUF@titlefont@Switch{\@title}%
2127         \else\SUF@authorfont@Switch{\@author}\fi}%
2128     \label{begin:\thearticle}
2129     \xdef\@currentHref{title.\thearticle}%
2130 \Hy@raisedlink{%
2131 \hyper@anchorstart{\@currentHref}\hyper@anchorend}%
2132 \csname toc@entry@\endcsname
2133     \begingroup%
2134     \let\thanks\gobble
2135     \addcontentsline{toc}{title}{%
2136     {\SUF@tocAUT@font{\@author}}\texorpdfstring{\newline}{, }%
2137     {\SUF@tocTIT@font{\@headtitle}}}%
2138     \endgroup%
2139     \par\nobreak\vspace[2ex]
2140     {\ifsufthesi@reverseauthortitle
2141         \SUF@authorfont@Switch{\@author}%
2142         \else
2143             \SUF@titlefont@Switch{\@title}%
2144         \fi\vskip1.5cm}%
2145     }
2146 \%newenvironment{article}
2147 \% {\begingroup
2148 \% \global\let\@thanks\empty
2149 \% \setcounter{footnote}{0}
2150 \% \refstepcounter{article}
2151 \% \label{begin:\thearticle}
2152 \%}
2153 \% {\label{end:\thearticle}\endgroup
2154 \%}
2155 \%newenvironment{article}
2156     {\begingroup
2157     \setcounter{section}{0}
2158     \setcounter{footnote}{0}
2159     \setcounter{figure}{0}
2160     \setcounter{table}{0}%
2161     \label{end:\thearticle}
2162     \cleardoublepage
2163     \global\let\@thanks\empty
2164     \endgroup}

```

A command to typeset the frontispiece of the collection.

```

2165 \%newcommand{\frontispiece}{%
2166     \thispagestyle{empty}%
2167     \begingroup
2168     \centering
2169     \vspace*{\stretch{1}}%
2170     {\SUF@chaptersize\collectiontitle\par}

```

```

2172      \vskip5ex
2173
2174      \@collectioneditor
2175      \vspace*\{\stretch{3}\}
2176
2177  \endgroup
2178  \clearpage

```

In the collection document structure the articles are treated as chapters but you would not need to print in the table of contents all the sections of every article. So first of all we include in the table of contents only the author and the title of each paper:

```
2179 \setcounter{tocdepth}{0}
```

Anyway the sections inside each paper are numbered as in standard articles:

```

2180 \renewcommand\thesection{%
2181     \@arabic\c@section}
2182 \renewcommand\thesubsection{%
2183     \thesection.\@arabic\c@subsection}
2184 \renewcommand\thesubsubsection{%
2185     \thesubsection.\@arabic\c@subsubsection}
2186 \renewcommand\theparagraph{%
2187     \thesubsubsection.\@arabic\c@paragraph}
2188 \renewcommand\thesubparagraph{%
2189     \theparagraph.\@arabic\c@subparagraph}
2190 \else
2191 \fi

```

Frontispiece

```

2192 \AtBeginDocument{%
2193 \@ifpackagewith{frontespizio}{suftesi}{%
2194 \ifsuftesi@periodical
2195     \Margini {5.5cm}{7cm}{4.5cm}{0cm}
2196     \else
2197 \ifsuftesi@compact
2198     \Margini {4.5cm}{7cm}{4.5cm}{0cm}
2199     \else
2200 \ifsuftesi@supercompact
2201     \Margini {4.5cm}{10cm}{6cm}{1cm}
2202     \else
2203 \ifsuftesi@compactaureo
2204     \Margini {4.5cm}{7cm}{4.5cm}{0cm}
2205     \else
2206 \ifsuftesi@supercompactaureo
2207     \Margini {4.5cm}{10cm}{6cm}{1cm}
2208     \else
2209 \ifsuftesi@periodicalaureo
2210     \Margini {5.5cm}{7cm}{4.5cm}{0cm}
2211     \else
2212 \fi\fi\fi\fi\fi\fi
2213 {\@ifpackageloaded{frontespizio}{%
2214 \ifsuftesi@periodical
2215     \Margini {1cm}{7cm}{5cm}{1cm}

```

```

2216   \Rientro{1cm}
2217   \else
2218 \ifsuftesi@compact
2219   \Margini {1cm}{7cm}{6cm}{1cm}
2220   \Rientro{1cm}
2221   \else
2222 \ifsuftesi@supercompact
2223   \Margini {1cm}{10cm}{8cm}{1cm}
2224   \Rientro{1cm}
2225   \else
2226 \ifsuftesi@compactaureo
2227   \Margini {1cm}{7cm}{6cm}{1cm}
2228   \Rientro{1cm}
2229   \else
2230 \ifsuftesi@supercompactaureo
2231   \Margini {1cm}{10cm}{8cm}{1cm}
2232   \Rientro{1cm}
2233   \else
2234 \ifsuftesi@periodicalaureo
2235   \Margini {1cm}{7cm}{5cm}{1cm}
2236   \Rientro{1cm}
2237   \else
2238 \fi\fi\fi\fi\fi
2239 {\relax}}}

2240 \renewenvironment{theindex}
2241           {\if@twocolumn
2242             \restonecolfalse
2243           \else
2244             \restonecoltrue
2245           \fi
2246           \ifsuftesi@article
2247             \twocolumn[\section*{\indexname}]%
2248           \else
2249             \twocolumn[\makeschapterhead{\indexname}]%
2250           \fi
2251           \mkboth{\indexname}{\indexname}%
2252           \thispagestyle{plain}%
2253           \raggedright%
2254           \parindent\z@
2255           \parskip\z@\@plus .3\p@\relax
2256           \columnseprule \z@
2257           \columnsep 35\p@
2258           \let\item\idxitem
2259           \if@restonecol\onecolumn\else\clearpage\fi}

```

Appendix

```

2260 % \changes{v2.9.5}{2020/02/04}{New mechanism for the appendices through the \sty{appendix} packa
2261 \RequirePackage{appendix}
2262 \renewcommand{\appendixpagename}{Appendici}

```

```

2263 \renewcommand{\appendixtocname}{Appendici}
2264 \renewcommand{\appendixname}{Appendice}
2265 \noappendicestocpagenum
2266 \AtBeginEnvironment{appendices}{\appendix\mainmatter}
2267 %^A\newcommand{\appendicesname}[1]{\def\SUF@appendices{#1}}
2268 %^A \appendicesname{Appendici}
2269 %^A \newcommand{\appendixpage}{\SUF@appendixpage}
2270 %^A\def\SUF@appendixpage{%
2271 %^A @mainmattertrue
2272 %^A \titlecontents{part}
2273 %^A [0em]
2274 %^A {\addvspace{3ex}}
2275 %^A {}
2276 %^A {}
2277 %^A {}
2278 %^A [\addvspace{1ex}]
2279 %^A\let\contentspage\relax
2280 %^A \cleardoublepage
2281 %^A \thispagestyle{empty}
2282 %^A \addcontentsline{toc}{part}{\SUF@appendices}
2283 %^A \begingroup
2284 %^A \centering
2285 %^A \null\vfil
2286 %^A {\LARGE\SUF@appendices\par}
2287 %^A \vfil
2288 %^A \endgroup
2289 %^A \cleardoublepage
2290 %^A\titlecontents{part}
2291 %^A [0em]
2292 %^A {\addvspace{3ex}\partname~}
2293 %^A {\makebox[\SUF@label@part][1]{%
2294 %^A \thecontentslabel}\hspace*{1em}}
2295 %^A {}
2296 %^A {}
2297 %^A [\addvspace{1ex}]
2298 %^A}
2299 \renewcommand{\@chap@pppage}{%
2300 \clear@ppage
2301 \thispagestyle{plain}%
2302 \if@twocolumn\onecolumn\@tempswatrue\else\@tempswafalse\fi
2303 \null\vfil
2304 \markboth{}{}%
2305 \centering
2306 \interlinepenalty \OM
2307 \normalfont
2308 \SUF@chaptersize\appendixpagename\par}%
2309 \if@dotoc@pp
2310 \addapptagetoc
2311 \fi
2312 \vfil\newpage

```

```

2313 \if@twoside
2314 \if@openright
2315 \null
2316 \thispagestyle{empty}%
2317 \newpage
2318 \fi
2319 \fi
2320 \if@tempswa
2321 \twocolumn
2322 \fi
2323 }
2324 \renewcommand{\@sec@pppage}{%
2325 \par
2326 \addvspace{4ex}%
2327 \c@afterindentfalse
2328 {\parindent \z@ \raggedright
2329 \interlinepenalty \zM
2330 \normalfont
2331 \SUF@chaptersize\appendixpagename}%
2332 \markboth{}{}\par}%
2333 \if@dotoc@pp
2334 \addapptocentry{toc}
2335 \fi
2336 \nobreak
2337 \vskip 3ex
2338 \c@afterheading
2339 }
2340 \ifsufthesi@article
2341   \renewcommand\appendix{\par
2342     \setcounter{section}{0}%
2343     \setcounter{subsection}{0}%
2344     \gdef\SUF@thesection{\c@Alph\c@section}%
2345     \gdef\SUF@HEAD@thesection{\c@Alph\c@section}%
2346 \else
2347   \renewcommand\appendix{\par
2348     \setcounter{chapter}{0}%
2349     \setcounter{section}{0}%
2350     \gdef\@chapapp{\appendixname}%
2351     \gdef\SUF@thechapter{\c@Alph\c@chapter}%
2352     \gdef\SUF@HEAD@thechapter{\c@Alph\c@chapter}%
2353 \fi

```

Headings

```

2354 \RequirePackage{fancyhdr}
2355 \newcommand{\versionstring}[1]{\def\version@string{#1}}
2356   \versionstring{Version of}
2357 \AtBeginDocument{%
2358   \pagestyle{fancy}
2359   \renewcommand{\headrulewidth}{0pt}
2360   \renewcommand{\footnoterule}{}

```

```

2361 \def\SUF@versionstring{\texttt{\version@string{} \today}}
The default headers
2362 \renewcommand{\chaptermark}[1]{%
2363   \markboth{\chaptertitlename\ \protect\SUF@HEAD@thechapter}{#1}}
2364 \ifsuftesi@article
2365   \renewcommand{\sectionmark}[1]{\markright{\protect\SUF@HEAD@thesection.\ #1}}
2366   \else
2367   \renewcommand{\sectionmark}[1]{}
2368 \fi

The plain style
2369 \fancypagestyle{plain}{\fancyhf{}}

The sufplain style
2370 \fancypagestyle{sufplain}{%
2371   \fancyhf{}%
2372   \fancyfoot[RE,LO]{%
2373     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi
2374     \fancyfoot[C]{\footnotesize\SUF@thepage}}}

The centerheader style
2375 \fancypagestyle{centerheader}{%
2376   \fancyhf{}%
2377   \fancyfoot[RE,LO]{%
2378     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi
2379     \fancyhead[CO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
2380     \fancyhead[CE]{\footnotesize\xheadbreakfalse%
2381       \SUF@LR@MarkSwitch}
2382     \fancyfoot[C]{\footnotesize\SUF@thepage}}%
2383 }%

The sufdefault style
2384 \fancypagestyle{sufdefault}{%
2385   \fancyhf{}%
2386   \fancyfoot[RE,LO]{%
2387     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi
2388     \fancyhead[LE,RO]{\footnotesize\SUF@thepage}
2389     \fancyhead[LO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
2390     \fancyhead[RE]{\footnotesize\xheadbreakfalse%
2391       \SUF@LR@MarkSwitch}
2392   }%
2393 }%
2394 \ifsuftesi@article
2395 \ifsuftesi@authortitle
2396 \def\SUF@LR@MarkSwitch{\SUF@leftmark}
2397 \else
2398 \def\SUF@LR@MarkSwitch{\SUF@rightmark}
2399 \fi
2400 \else

```

```

2401     \def\SUF@LR@MarkSwitch{\SUF@leftmark}
2402 \fi
2403 \def\SUF@leftrightmark{%
2404   \if@mainmatter\leftmark\else\rightmark\fi}
    Setting the default page style:
2405 \pagestyle{sufdefault}
2406   \ifsuftesi@centerheader\pagestyle{centerheader}\else\fi
2407   \ifsuftesi@sufplain\pagestyle{sufplain}\else\fi

```

Text elements

Block Quotations New environments for block quotations according to a popular Italian style. The font size is the same of the footnotes and the margins are set to `\parindent`.

```

2408 \renewenvironment{quotation}
2409   {\list{}{\listparindent\parindent%
2410     \itemindent \listparindent
2411     \leftmargin \parindent
2412     \SUF@quote@style
2413     \parsep \z@ \p@}%
2414     \item\relax%
2415     \SUF@quotation@size%
2416     \noindent\ignorespaces}
2417   {\endlist}
2418 \renewenvironment{quote}
2419   {\list{}{\leftmargin \parindent
2420     \SUF@quote@style}%
2421     \item\relax%
2422     \SUF@quotation@size%\ignorespaces?
2423   {\endlist}
2424 \renewenvironment{verse}
2425   {\let\\@\centercr
2426     \list{}{\itemsep \z@
2427       \itemindent -1.5em%
2428       \listparindent\itemindent
2429       \rightmargin \leftmargin
2430       \advance\leftmargin 1.5em}%
2431     \item\relax
2432     \SUF@quotation@size}
2433   {\endlist}

```

The fewfootnotes option Enable only with three footnotes per page maximum.

```

2434 \ifsuftesi@fewfootnotes
2435 \AtBeginDocument{%
2436 \def\@fnssymbol#1{\ensuremath{\ifcase#1\or*\or{*}{*}\or{*}{*}\or{*}{*}\or{*}{*}}%
2437   \ClassError{suftesi}%
2438   {Too many footnotes\MessageBreak
2439 Remove the class option 'fewfootnote'}
2440   {Too many footnotes\MessageBreak
2441 Remove the class option 'fewfootnote'}

```

```

2442 \else\@ctrerr\fi}}}
2443 \def\thefootnote{\fnsymbol{c@footnote}%
2444 \else\fi
    Prints a footnote with discretionary symbol give in the first argument.
2445 \newcommand*\xfootnote[1][*]{%
2446     \xdef\@thefnmark{#1}%
2447     \footnotemark\footnotetext}

```

Marginal notes The `\marginpar` command is redefined according to the look of *Classic Thesis* by André Miede (2011).

```

2448 \def\SUF@mpsetup{%
2449     \itshape
2450     \footnotesize%
2451     \parindent=0pt \lineskip=0pt \lineskiplimit=0pt %
2452     \tolerance=2000 \hyphenpenalty=300 \exhyphenpenalty=300%
2453     \doublehyphendemerits=100000%
2454     \finalhyphendemerits=\doublehyphendemerits}
2455     \let\oldmarginpar\marginpar
2456     \renewcommand{\marginpar}[1]{\oldmarginpar%
2457         [\SUF@mpsetup\raggedleft\hspace{0pt}{#1}]%
2458         [\SUF@mpsetup\raggedright\hspace{0pt}{#1}]}}

```

Redefine an internal command of the `todonotes` package in order to use the class-specific marginal notes when this package is loaded. This redefinition simply substitute `\oldmarginpar` to `\marginpar`:

```

2459 \AtBeginDocument{%
2460 \@ifpackage{todonotes}{%
2461 \renewcommand{\@todonotes@drawMarginNoteWithLine}{%
2462 \begin{tikzpicture}[remember picture, overlay, baseline=-0.75ex]%
2463     \node [coordinate] (inText) {};%
2464 \end{tikzpicture}%
2465 \oldmarginpar[{\% Draw note in left margin
2466     \@todonotes@drawMarginNote}%
2467     \@todonotes@drawLineToLeftMargin%
2468 }]{% Draw note in right margin
2469     \@todonotes@drawMarginNote}%
2470     \@todonotes@drawLineToRightMargin%
2471 }%
2472 }%
2473 }
2474 {\relax}}

```

Abstract

```

2475 \ifsuftesi@collection
2476 \newenvironment{abstract}{%
2477     \if@twocolumn
2478         \section*{\abstractname}%
2479     \else
2480         \small
2481         \begin{center}%

```

```

2482      {\abstractname\vspace{-.5em}\vspace{\z@}}%
2483      \end{center}%
2484      \quotation
2485      \fi}
2486      {\if@twocolumn\else\endquotation\fi\vspace{6ex}}
2487 \else
2488 \if@titlepage
2489   \newenvironment{abstract}{%
2490     \titlepage
2491     \null\vfil
2492     \begin{parpenalty}\lowpenalty
2493     \begin{center}%
2494       \abstractname
2495       \endparpenalty\@M
2496     \end{center}%
2497     {\par\vfil\null\endtitlepage}
2498 \else
2499   \newenvironment{abstract}{%
2500     \if@twocolumn
2501       \section*{\abstractname}%
2502     \else
2503       \small
2504       \begin{center}%
2505         {\abstractname\vspace{-.5em}\vspace{\z@}}%
2506       \end{center}%
2507       \quotation
2508       \fi}
2509     {\if@twocolumn\else\endquotation\fi}
2510 \fi
2511 \fi
2512 \newcommand{\abstractname}{Abstract}

```

Colophon or copyright notice

```

2513 \newcommand{\colophon}[3][]{%
2514   \thispagestyle{empty}
2515   \null
2516   \vfill
2517   \def\next{\#2}
2518   \ifx\next\empty\else
2519     \noindent Copyright \copyright{} \the\year^{#2}\,[1ex]
2520     Tutti i diritti riservati
2521   \fi
2522   \vfill
2523   {\small\noindent Questo lavoro \`e stato composto con \LaTeX{}%
2524     \def\next{\#1}
2525     \ifx\next\empty\else su #1
2526     \fi usando la classe \textsf{suftesi} di
2527     Ivan Valbusa\index{Valbusa, Ivan}. #3\par}
2528   \cleardoublepage

```

```

2529 \newcommand{\bookcolophon}[2]{%
2530   \thispagestyle{empty}%
2531   \null
2532   \vfill
2533   \noindent #1
2534   \vfill
2535   {\small\noindent #2\par}
2536   \cleardoublepage}

2537 \newcommand{\artcolophon}[1]{%
2538 \thispagestyle{empty}%
2539 \null
2540 \vfill
2541 {\small\noindent #1\par} }

2542 \newcommand{\finalcolophon}[1]{%
2543 \thispagestyle{empty}%
2544 \null\vspace*{\stretch{1}}
2545 \begin{center}
2546 \begin{minipage}{.5\textwidth}
2547 \centering\small #1
2548 \end{minipage}
2549 \end{center}
2550 \vspace*{\stretch{6}}}

```

The \FSPL colophon This command is defined only for the `style=FSPL*` options.

```

2551 \ifsuftesi@FSPL
2552 \newcommand{\FSPLcolophon}[1][\the\year]{%
2553 \begingroup
2554 \thispagestyle{empty}
2555 \null\vspace{\stretch{1}}
2556 \noindent \hskip-.5em\cc #1 \@author%
2557 \vskip1ex
2558
2559 \small\noindent This work is licensed under the Creative Commons
2560 Attribution-NonCommercial-NoDerivs 3.0 Unported License.
2561 To view a copy of this license,
2562 visit http://creativecommons.org/licenses/by-nc-nd/3.0/.
2563
2564 \endgroup
2565
2566 \begingroup
2567 \footnotesize
2568
2569 \null\vspace{\stretch{1}}
2570
2571 \noindent Typeset with \LaTeX{} in collaboration with the Joint Project
2572 \emph{Formal Style for PhD Theses with \LaTeX{}} (University of Verona,
2573 Italy) using the \textsf{suftesi} class by Ivan Valbusa. The text face
2574 is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by
2575 Janusz M. Nowacki.

```

```

2576
2577 \endgroup
2578
2579 \clearpage}
2580 \else
2581 \def\FSPLcolophon{%
2582   \ClassError{suftesi}{%
2583     {\noexpand\FSPLcolophon is defined\MessageBreak
2584      only for the FSPL styles}%
2585     {\noexpand\FSPLcolophon is defined\MessageBreak
2586      only for the FSPL styles}}}
2587 \fi

```

Toc, lof, lot

```

2588 \RequirePackage{titletoc}
All the lengths depend on \SUF@label@chap so we define this first.
2589 \newlength\SUF@label@chap
2590 \setlength\SUF@label@chap{.5em}
\toclabelwidth is provided to adjust the label width in the table of contents:
2591 \newcommand*{\toclabelwidth}[2]{%
2592   \AtBeginDocument{%
2593     \addtolength{\csname SUF@label@\#1\endcsname}{#2}%
2594     \addtolength{\csname SUF@tocindent@\#1\endcsname}{#2}%
2595   }
2596 }
2597 \newcommand{\toclabelspace}{%
2598   \ClassError{suftesi}{%
2599     {\MessageBreak
2600       \noexpand\toclabelspace is not more defined\MessageBreak
2601       Use \noexpand\toclabelwidth instead.\MessageBreak
2602       See package documentation for details}%
2603     {\MessageBreak
2604       \noexpand\toclabelspace is not more defined\MessageBreak
2605       Use \noexpand\toclabelwidth instead.\MessageBreak
2606       See package documentation for details}}}
This macro controls the space between page number and chapter label using the tocpageleft
option:
2607 \newlength{\SUF@tochang}
2608 \setlength{\SUF@tochang}{3em}
2609 \AtBeginDocument{
2610 \newlength\SUF@label@part
2611 \newlength\SUF@label@sec
2612 \newlength\SUF@label@subsec
2613 \newlength\SUF@label@subsubsec
2614 \newlength\SUF@label@par
2615 \newlength\SUF@label@subpar
2616 \newlength\SUF@label@fig
2617 \newlength\SUF@label@tab
2618 \setlength\SUF@label@part

```

```

2619      {\SUF@label@chap}
2620 \setlength{\SUF@label@sec
2621     {\dimexpr(\SUF@label@chap+.5em)}
2622 \setlength{\SUF@label@subsec
2623     {\dimexpr(\SUF@label@sec+.5em)}
2624 \setlength{\SUF@label@subsubsec
2625     {\dimexpr(\SUF@label@subsec+.5em)}
2626 \setlength{\SUF@label@par
2627     {\dimexpr(\SUF@label@subsubsec+.5em)}
2628 \setlength{\SUF@label@subpar
2629     {\dimexpr(\SUF@label@par+.5em)}
2630 \setlength{\SUF@label@fig
2631     {\SUF@label@sec}
2632 \setlength{\SUF@label@tab
2633     {\SUF@label@sec}
2634 }

      Part in article mode
2635 \titlecontents{part}
2636   [0em]
2637   {\addvspace{3ex}\partname\hspace*{.5em}}
2638   {\makebox[\SUF@label@part][1]{%
2639     \thecontentslabel}\hspace*{1em}}
2640   {}
2641   {}
2642   [\addvspace{1ex}]
      ‘tocpageleft’ toc
2643 \if sulf@pagelefttoc
      First we reset the right margin to zero:
2644 \contentsmargin{0pt}
2645 \AtBeginDocument{
2646 \newlength{\SUF@tochang@chap}
2647 \newlength{\SUF@tochang@sec}
2648 \newlength{\SUF@tochang@subsec}
2649 \newlength{\SUF@tochang@subsubsec}
2650 \newlength{\SUF@tochang@par}
2651 \newlength{\SUF@tochang@subpar}
2652 \newlength{\SUF@tochang@fig}
2653 \newlength{\SUF@tochang@tab}
2654 \newlength{\SUF@addto@tochang@chap}
2655 \newlength{\SUF@addto@tochang@sec}
2656 \newlength{\SUF@addto@tochang@subsec}
2657 \newlength{\SUF@addto@tochang@subsubsec}
2658 \newlength{\SUF@addto@tochang@par}
2659 \newlength{\SUF@addto@tochang@subpar}
2660 \newlength{\SUF@addto@tochang@fig}
2661 \newlength{\SUF@addto@tochang@tab}
2662 \setlength{\SUF@tochang@chap
2663   {\dimexpr(1em+\SUF@tochang+\SUF@label@chap+1em)}
2664 \setlength{\SUF@tochang@sec

```

```

2665      {\dimexpr(\SUF@tochang@chap+\SUF@label@sec+1em)}
2666 \setlength{\SUF@tochang@subsec}
2667      {\dimexpr(\SUF@tochang@sec+\SUF@label@subsec+1em)}
2668 \setlength{\SUF@tochang@subsubsec}
2669      {\dimexpr(\SUF@tochang@subsec+\SUF@label@subsubsec+1em)}
2670 \setlength{\SUF@tochang@par}
2671      {\dimexpr(\SUF@tochang@subsubsec+\SUF@label@par+1em)}
2672 \setlength{\SUF@tochang@subpar}
2673      {\dimexpr(\SUF@tochang@par+\SUF@label@subpar+1em)}
2674 \setlength{\SUF@tochang@fig}
2675      {\SUF@tochang@chap}
2676 \setlength{\SUF@tochang@tab}
2677      {\SUF@tochang@chap}
2678 \setlength{\SUF@addto@tochang@chap}
2679      {\SUF@tochang}
2680 \setlength{\SUF@addto@tochang@sec}
2681      {\dimexpr(\SUF@addto@tochang@chap+\SUF@label@sec+.5em)}
2682 \setlength{\SUF@addto@tochang@subsec}
2683      {\dimexpr(\SUF@addto@tochang@sec+\SUF@label@subsec+.5em)}
2684 \setlength{\SUF@addto@tochang@subsubsec}
2685      {\dimexpr(\SUF@addto@tochang@subsec+\SUF@label@subsubsec+.5em)}
2686 \setlength{\SUF@addto@tochang@par}
2687      {\dimexpr(\SUF@addto@tochang@subsubsec+\SUF@label@par+.5em)}
2688 \setlength{\SUF@addto@tochang@subpar}
2689      {\dimexpr(\SUF@addto@tochang@par+\SUF@label@subpar+.5em)}
2690 \setlength{\SUF@addto@tochang@fig}
2691      {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2692 \setlength{\SUF@addto@tochang@tab}
2693      {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2694 }

```

TOC entries

```

2695 \titlecontents{chapter}
2696   [\SUF@tochang@chap]
2697   {\addvspace{2ex}}
2698   {\hspace{-\SUF@tochang@chap}%
2699     \makebox[1em][l]{\thecontentspage}%
2700     \hspace{\SUF@addto@tochang@chap}%
2701     \makebox[\SUF@label@chap][l]{%
2702       \SUF@CHAP@thecontentslabel}\hspace*{1em}%
2703       \SUF@tocCHAP@font}%
2704   {\hspace{-\SUF@tochang@chap}%
2705     \makebox[1em][l]{\thecontentspage}%
2706     \hspace{\SUF@addto@tochang@chap}\SUF@tocCHAP@font}%
2707   {}%
2708   [\addvspace{1ex}]
2709 \titlecontents{section}
2710   [\SUF@tochang@sec]
2711   {}%
2712   {\hspace{-\SUF@tochang@sec}%

```

```

2713   \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@sec%
2714 %^^A   \makebox[\SUF@label@sec] [1]{%
2715 %^^A   \ifsuftesi@article\SUF@toclabelnum%
2716 %^^A   \else\fi\thecontentslabel}\hspace*{1em}%
2717   \makebox[\SUF@label@sec] [1]{\SUF@SEC@thecontentslabel}\hspace*{1em}%
2718   \SUF@tocSEC@font}
2719 {\hskip-\SUF@tochang@sec%
2720 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@sec%
2721   \SUF@tocSEC@font}
2722 {}
2723 \titlecontents{subsection}
2724 [\SUF@tochang@subsec]
2725 {}
2726 {\hskip-\SUF@tochang@subsec%
2727 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@subsec%
2728 \makebox[\SUF@label@subsec] [1]{\SUF@SUBSEC@thecontentslabel}\hspace*{1em}%
2729 \SUF@tocSUBSEC@font}
2730 {\hskip-\SUF@tochang@subsec%
2731 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@subsec%
2732 \SUF@tocSUBSEC@font}
2733 {}
2734 \titlecontents{subsubsection}
2735 [\SUF@tochang@subsubsec]
2736 {}
2737 {\hskip-\SUF@tochang@subsubsec%
2738 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@subsubsec%
2739 \makebox[\SUF@label@subsubsec] [1]{\SUF@SUBSUBSEC@thecontentslabel}\hspace*{1em}%
2740 \SUF@tocSUBSUBSEC@font}
2741 {\hskip-\SUF@tochang@subsubsec%
2742 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@subsubsec%
2743 \SUF@tocSUBSUBSEC@font}
2744 {}
2745 \titlecontents{paragraph}
2746 [\SUF@tochang@par]
2747 {}
2748 {\hskip-\SUF@tochang@par%
2749 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@par%
2750 \makebox[\SUF@label@par] [1]{\thecontentslabel}\hspace*{1em}%
2751 {\hskip-\SUF@tochang@par%
2752 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@par}
2753 {}
2754 \titlecontents{ subparagraph}
2755 [\SUF@tochang@subpar]
2756 {}
2757 {\hskip-\SUF@tochang@subpar%
2758 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@subpar%
2759 \makebox[\SUF@label@subpar] [1]{\thecontentslabel}\hspace*{1em}%
2760 {\hskip-\SUF@tochang@subpar%
2761 \makebox[1em] [1]{\thecontentspage}\hskip\SUF@addto@tochang@subpar}
2762 {}

```

```

2763 \titlecontents{figure}
2764   [ \SUF@tochang@fig]
2765   {}
2766   {\hspace{-\SUF@tochang@fig}%
2767     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@fig}%
2768     \makebox[\SUF@label@tab][l]{\thecontentslabel}\hspace*{1em}%
2769   {}%
2770   {}%
2771 \titlecontents{table}
2772   [ \SUF@tochang@tab]
2773   {}
2774   {\hspace{-\SUF@tochang@tab}%
2775     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@tab}%
2776     \makebox[\SUF@label@tab][l]{\thecontentslabel}\hspace*{1em}%
2777   {}%
2778   {}%
2779 \else

```

Default toc

```

2780 \AtBeginDocument{
2781 \newlength\SUF@tocindent@chap
2782 \newlength\SUF@tocindent@sec
2783 \newlength\SUF@tocindent@subsec
2784 \newlength\SUF@tocindent@subsubsec
2785 \newlength\SUF@tocindent@par
2786 \newlength\SUF@tocindent@subpar
2787 \newlength\SUF@tocindent@fig
2788 \newlength\SUF@tocindent@tab
2789 \ifsufthesi@article
2790 \setlength\SUF@tocindent@sec
2791   {\dimexpr(\SUF@label@chap+1.5em)}
2792 \setlength\SUF@tocindent@subsec
2793   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2794 \setlength\SUF@tocindent@subsubsec
2795   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2796 \setlength\SUF@tocindent@par
2797   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2798 \setlength\SUF@tocindent@subpar
2799   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2800 \setlength\SUF@tocindent@fig
2801   {\dimexpr(\SUF@label@chap+1.5em)}
2802 \setlength\SUF@tocindent@tab
2803   {\dimexpr(\SUF@label@chap+1.5em)}
2804 \else
2805 \setlength\SUF@tocindent@chap
2806   {\dimexpr(\SUF@label@chap+1em)}
2807 \setlength\SUF@tocindent@sec
2808   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec+1em)}
2809 \setlength\SUF@tocindent@subsec
2810   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}

```

```

2811 \setlength{\SUF@tocindent@subsubsec}
2812   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2813 \setlength{\SUF@tocindent@par}
2814   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2815 \setlength{\SUF@tocindent@subpar}
2816   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2817 \setlength{\SUF@tocindent@fig}
2818   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2819 \setlength{\SUF@tocindent@tab}
2820   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2821 \fi
2822 }

```

TOC entries

```

2823 \titlecontents{chapter}
2824   [\SUF@tocindent@chap]
2825   {\addvspace{2ex}}
2826   {\hspace{-\SUF@tocindent@chap}%
2827     \makebox[\SUF@label@chap][1]{\SUF@CHAP@thecontentslabel}%
2828     \hspace*{1em}%
2829     \SUF@tocCHAP@font}
2830   {\hspace{-\SUF@tocindent@chap}%
2831     \SUF@tocCHAP@font}
2832   {\SUF@chaptitlerule\contentspage}
2833   [\addvspace{1ex}]
2834 \titlecontents{section}
2835   [\SUF@tocindent@sec]
2836   {}
2837   {\hspace{-\dimexpr(\SUF@label@sec+1em)}%
2838 %^A     \makebox[\SUF@label@sec][1]{%
2839 %^A     \ifsuftesi@article\SUF@toclabelnum%
2840 %^A     \else\fi\thecontentslabel}\hspace*{1em}%
2841     \makebox[\SUF@label@sec][1]{\SUF@SEC@thecontentslabel}\hspace*{1em}%
2842     \SUF@tocSEC@font}
2843   {\hspace{-\dimexpr(\SUF@label@sec+1em)}%
2844     \SUF@tocSEC@font}
2845   {\ifsuftesi@article\SUF@chaptitlerule%
2846     \else\SUF@titlerule\fi\contentspage}
2847 \titlecontents{subsection}
2848   [\SUF@tocindent@subsec]
2849   {}
2850   {\hspace{-\dimexpr(\SUF@label@subsec+1em)}%
2851     \makebox[\SUF@label@subsec][1]{\SUF@SUBSEC@thecontentslabel}\hspace*{1em}%
2852     \SUF@tocSUBSEC@font}
2853   {\hspace{-\dimexpr(\SUF@label@subsec+1em)}%
2854     \SUF@tocSUBSEC@font}
2855   {\SUF@titlerule\contentspage}
2856 \titlecontents{subsubsection}
2857   [\SUF@tocindent@subsubsec]
2858   {}

```

```

2859  {\hskip-\dimexpr(\SUF@label@subsubsec+1em)%
2860   \makebox[\SUF@label@subsubsec][1]{\SUF@SUBSUBSEC@thecontentslabel}\hspace*{1em}%
2861   \SUF@tocSUBSUBSEC@font}
2862  {\hskip-\dimexpr(\SUF@label@subsubsec+1em)%
2863   \SUF@tocSUBSUBSEC@font}
2864  {\SUF@titlerule\contentspage}
2865 \titlecontents{paragraph}
2866  [\SUF@tocindent@par]
2867  {}
2868  {\hskip-\dimexpr(\SUF@label@par+1em)%
2869   \makebox[\SUF@label@par][1]{\thecontentslabel}\hspace*{1em}%
2870  {\hskip-\dimexpr(\SUF@label@par+1em)%
2871  {\SUF@titlerule\contentspage}
2872 \titlecontents{subparagraph}
2873  [\SUF@tocindent@subpar]
2874  {}
2875  {\hskip-\dimexpr(\SUF@label@subpar+1em)%
2876   \makebox[\SUF@label@subpar][1]{\thecontentslabel}\hspace*{1em}%
2877  {\hskip-\dimexpr(\SUF@label@subpar+1em)%
2878  {\SUF@titlerule\contentspage}
2879 \titlecontents{figure}
2880  [\SUF@tocindent@fig]
2881  {}
2882  {\hskip-\SUF@tocindent@fig%
2883   \makebox[\SUF@label@fig][1]{\thecontentslabel}\hspace*{1em}%
2884  {}
2885  {\SUF@titlerule\contentspage}
2886 \titlecontents{table}
2887  [\SUF@tocindent@tab]
2888  {}
2889  {\hskip-\SUF@tocindent@tab%
2890   \makebox[\SUF@label@tab][1]{\thecontentslabel}\hspace*{1em}%
2891  {}
2892  {\SUF@titlerule\contentspage}
2893 \fi
With article option the toc, lof and lot are printed as sections.
2894 \ifsuftesi@article
2895 \renewcommand\tableofcontents{%
2896   \vspace{2ex}%
2897   \section*{\contentsname}%
2898   \mkboth{\contentsname}{\contentsname}%
2899   \thispagestyle{empty}%
2900   \ifsuftesi@twocolumn@toc
2901     \begin{multicols}{2}%
2902       \starttoc{toc}%
2903     \end{multicols}%
2904   \else
2905     \starttoc{toc}%
2906   \fi

```

```

2907      \vspace{2ex}%
2908  }
2909 \renewcommand{\listoffigures}{%
2910     \vspace{2ex}%
2911     \section*{\listfigurename}%
2912     \mkboth{\listfigurename}{\listfigurename}%
2913     \thispagestyle{empty}%
2914     \ifnum\value{multicols}>1
2915         \begin{multicols}{2}%
2916             \starttoc{lof}%
2917         \end{multicols}%
2918     \else
2919         \starttoc{lof}%
2920     \fi
2921     \vspace{2ex}%
2922 }
2923 \renewcommand{\listoftables}{%
2924     \vspace{2ex}%
2925     \section*{\listtablename}%
2926     \mkboth{\listtablename}{\listtablename}%
2927     \thispagestyle{empty}%
2928     \ifnum\value{multicols}>1
2929         \begin{multicols}{2}%
2930             \starttoc{lot}%
2931         \end{multicols}%
2932     \else
2933         \starttoc{lot}%
2934     \fi
2935     \vspace{2ex}%
2936 }
2937 \else
    The default toc, lof and lot are treated as chapters.
2938 \renewcommand{\tableofcontents}{%
2939     \if@twocolumn
2940         \restonecoltrue\onecolumn
2941     \else
2942         \restonecolfalse
2943     \fi
2944     \chapter*{\contentsname}%
2945     \mkboth{%
2946         \contentsname
2947         {\contentsname}}%
2948     \thispagestyle{empty}%
2949     \ifnum\value{multicols}>1
2950         \begin{multicols}{2}%
2951             \starttoc{toc}%
2952         \end{multicols}%
2953     \else
2954         \starttoc{toc}%

```

```

2955      \fi
2956      \if@restonecol\twocolumn\fi
2957  }
2958 \renewcommand{\listoffigures}{%
2959     \if@twocolumn
2960         \restonecoltrue\onecolumn
2961     \else
2962         \restonecolfalse
2963     \fi
2964     \chapter*{\listfigurename}%
2965     \mkboth{\listfigurename}{%
2966         \listfigurename}%
2967     \thispagestyle{empty}
2968     \ifsuftesi@twocolumnlof
2969         \begin{multicols}{2}
2970             \starttoc{lof}%
2971         \end{multicols}
2972     \else
2973         \starttoc{lof}%
2974     \fi
2975     \if@restonecol\twocolumn\fi
2976 }
2977 \renewcommand{\listoftables}{%
2978     \if@twocolumn
2979         \restonecoltrue\onecolumn
2980     \else
2981         \restonecolfalse
2982     \fi
2983     \chapter*{\listtablename}%
2984     \mkboth{%
2985         \listtablename}%
2986     {\listtablename}%
2987     \thispagestyle{empty}
2988     \ifsuftesi@twocolumnlot
2989         \begin{multicols}{2}
2990             \starttoc{lot}%
2991         \end{multicols}
2992     \else
2993         \starttoc{lot}%
2994     \fi
2995     \if@restonecol\twocolumn\fi
2996 }
2997 \fi

```

New commands

```

2998 \ifsuftesi@article
2999 \def\chapterintro{%
3000 \ClassError{suftesi}{%
3001 {Command \noexpand\chapterintro is undefined\MessageBreak

```

```

3002     using 'structure=article'}
3003 {Command \noexpand\chapterintro is undefined\MessageBreak
3004     using 'structure=article'}
3005 \else
3006 \def\chapterintro{\@ifstar{%
3007   \tempswafalse\@chapterintro}{\tempswatrue\@chapterintro}}
3008 \def\@chapterintro{\phantomsection
3009   \if@tempswa\section*\{\SUF@fchapterintroname\}\fi
3010   \addcontentsline{toc}{section}{\SUF@fchapterintroname}}
3011 \newcommand{\chapterintroname}[1]{\def\SUF@fchapterintroname{#1}}
3012 \chapterintroname{Introduzione}
3013 \fi

```

Manual breaks Active in the table of contents but not in the text.

```

3014 \newif\ifheadbreak\headbreakfalse
3015 \DeclareRobustCommand{\headbreak}
3016 {\ifheadbreak\else\fi}

```

Active in the text but not in the table of contents.

```

3017 \newif\ifxheadbreak\xheadbreaktrue
3018 \def\xheadbreakNL{\ifxheadbreak\newline\else\fi}
3019 \def\xheadbreakBB{\ifxheadbreak\\else\fi}

3020 \let\origtableofcontents\tableofcontents
3021 \renewcommand{\tableofcontents}{%
3022   \begin{group}\headbreaktrue\xheadbreakfalse%
3023   \origtableofcontents\endgroup}

```

Backward compatibility An environment to manually typeset the bibliography. (Use `biblatax` instead!)

```

3024 \newenvironment{bibliografia}{%
3025   \ifsuftesi@article
3026   \section*\{\refname\}
3027   \addcontentsline{toc}{section}{\refname}
3028 \else
3029 \chapter{\bibname}%
3030 \fi
3031   \normalfont \list{}{%
3032     \setlength{\itemindent}{-\parindent}
3033     \setlength{\leftmargin}{\parindent}
3034     \setlength{\labelwidth}{0pt}
3035     \setlength{\parsep}{\parskip}
3036     \let\makelabel}
3037   \endlist}

```

An environment to manually typeset the list of shorthands. (Use `biblatax` instead!)

```

3038 \newcommand{\losname}{\Sige}
3039 \newcommand{\itlabel}[1]{\itshape\hbox to 6em{#1}}
3040 \newenvironment{sigle}{%
3041   \chapter{\losname}
3042   \normalfont \list{}{%
3043     \setlength{\labelsep}{0.5em}

```

```

3044     \settlength{\itemindent}{0pt}
3045     \settlength{\leftmargin}{6em}
3046     \settlength{\labelwidth}{\leftmargin}
3047     \settlength{\listparindent}{\parindent}
3048     \settlength{\parsep}{\parskip}
3049     \let\makelabel\itlabel}
3050 {\endlist}

```

Final settings

Renew `\frontmatter` to have arabic page numbering:

```

3051 \ifsuftesi@article
3052 \renewcommand\frontmatter{\ClassError{suftesi}
3053 {Command \noexpand\frontmatter is undefined\MessageBreak
3054     using 'structure=article'}
3055 {Command \noexpand\frontmatter is undefined\MessageBreak
3056     using 'structure=article'}`}
3057 \renewcommand\mainmatter{\ClassError{suftesi}
3058 {Command \noexpand\mainmatter is undefined\MessageBreak
3059     using 'structure=article'}
3060 {Command \noexpand\mainmatter is undefined\MessageBreak
3061     using 'structure=article'`}
3062 \renewcommand\backmatter{\ClassError{suftesi}
3063 {Command \noexpand\backmatter is undefined\MessageBreak
3064     using 'structure=article'}
3065 {Command \noexpand\backmatter is undefined\MessageBreak
3066     using 'structure=article'`}
3067 \else
3068 \renewcommand\frontmatter{\cleardoublepage{@mainmatterfalse}
3069 \renewcommand\mainmatter{\cleardoublepage{@mainmattertrue}
3070 \fi

```

In a previous version the `\hemph` command was provided to fix a bug in the hyphenation of some italian expressions like “dell’*encyclopaedia*”. Now the bug has been fixed by the `fixltxhyph` package by Claudio Beccari. The package must be loaded after `babel` or `polyglossia`:

```

3071 \@ifpackageloaded{babel}
3072 {\AtBeginDocument{\RequirePackage{fixltxhyph}}}{}
3073 \@ifpackageloaded{polyglossia}
3074 {\AtBeginDocument{\RequirePackage{fixltxhyph}}}{}

```

The `\hemph` command is provided only for backward compatibility:

```
3075 \let\hemph\emph
```

The first line of all sections is indented by default using X_E^A_T^EX with Italian as the main language. Anyway this is incongruous with the L^AT_EX default.

```

3076 \unless\ifPDFTeX% if xetex or luatex
3077 \let@afterindenttrue\@afterindentfalse
3078 \else
3079 \relax
3080 \fi

```

Just one touch of french typography:

```
3081 \frenchspacing
```

Change History

v0.5	New option <code>dottedtoc</code>	25
	New option <code>raggedtoc</code>	25
v0.6	General: First public release. The frontispiece of <code>suftesi</code> is now included in the package <code>frontespizio</code> . New option <code>fullplain</code> Changed option <code>sctitles</code>	1
	New command <code>chapnumfont</code>	20
	New option <code>compact</code>	25
	New option <code>elements</code>	25
	New option <code>nocrop</code>	25
	New option <code>nomarginpar</code>	25
	New option <code>sufelements</code>	25
	New option <code>supercompact</code>	25
v0.6a	General: English documentation. Renamed options <code>plain</code> and <code>fullplain</code> to <code>centerheadings</code> and <code>sufplain</code>	1
	New command <code>\artcolophon</code>	19
	New command <code>\bookcolophon</code>	19
	New option <code>authortitle</code>	25
v0.6b	General: Maintenance release, no changes	1
v0.6c	General: Improved full compatibility with X _Ǝ T _Ǝ X. <code>varioref</code> and <code>footmisc</code> packages are no longer loaded	1
v0.7	General: Maintenance release, no changes. Provided a thesis template	1
v0.8	General: Added macro for using <code>frontespizio</code> package with <code>compact</code> and <code>supercompact</code> options.	1
	New option <code>periodical</code>	25
	Renewed <code>\title</code> command	21
v0.9	General: Improved compatibility with <code>mathspec</code>	1
v0.9a	General: Added inline option to <code>enumitem</code> package. Deleted <code>centertitle</code> option. Deleted <code>sctitles</code> option. Changed code for toc, lot and lof elements.	1
	New command <code>\toclabelspace</code>	21
	New option <code>alignlist</code>	25
	New option <code>centerchap</code>	25
	New option <code>centerpart</code>	25
	New option <code>centersec</code>	25
	New option <code>defaultparindent</code>	25
	New option <code>dottedchap</code>	25
	New option <code>dottedfootnote</code>	25
	New option <code>dottedpart</code>	25
	New option <code>indentlist</code>	25
	New option <code>italicchap</code>	25
	New option <code>italicheader</code>	25
	New option <code>italicpart</code>	25
	New option <code>italicsec</code>	25
	New option <code>italicsubsec</code>	25
	New option <code>itstyle(1-12)</code>	25
	New option <code>numparchap</code>	25
	New option <code>numparpart</code>	25
	New option <code>numparsec</code>	25
	New option <code>ralignquotation</code>	25
	New option <code>rightchap</code>	25
	New option <code>rightpart</code>	25
	New option <code>rightsec</code>	25
	New option <code>rmstyle(1-6)</code>	25
	New option <code>romanchap</code>	25
	New option <code>scstyle(1-12)</code>	25
	New option <code>smallcapschap</code>	25
	New option <code>smallcapsheader</code>	25
	New option <code>smallcapspart</code>	25
	New option <code>smallcapssec</code>	25
	New option <code>smallquotation</code>	25
	New option <code>standardfootnote</code>	25
	New option <code>tocpageleft</code>	25
v0.9b	General: Changed <code>standardfootnote</code> option and renamed to <code>footnotestyle</code>	15
	New command <code>\xfootnote</code>	21

New option <code>fewfootnotes</code>	15	v1.6
New option <code>greekfont</code>	12	General: New option <code>viewmode</code> . Corrected bugs in the definition of <code>\listoffigures</code> , <code>\listoftables</code> and <code>\tableofcontents</code> commands.
New option <code>pagestyle</code>	10	Updated documentation. 1
New option <code>parindent</code>	16	
New option <code>partpage</code>	16	
New option <code>quotationfont</code>	15	
New option <code>quotestyle</code>	15	
New option <code>structure</code>	10	v1.7
New option <code>tocstyle</code>	13	General: Renamed <code>viewmode</code> option to <code>version</code> : renamed <code>print</code> value to <code>draft</code> and added <code>final</code> value. New <code>smallcapsstyle</code> option. 1
Restored 11pt and 12pt option to default	1	
The <code>epigraph</code> package is no longer loaded	2	
The <code>mparhack</code> package is no longer loaded. It is not compatible with <code>crop</code>	3	
v0.9c		v1.8
General: Maintenance release, no changes	1	General: Maintenance release. Corrected a bug in the definition of <code>\appendix</code> 1
v1.0		v1.9
General: First stable release. Renamed option <code>bozza</code> to <code>draftdate</code>	16	General: Added <code>italic</code> , <code>smallcaps</code> and <code>sanserif</code> values for <code>captionstyle</code> option. New <code>twocolcontents</code> option. New <code>supercompactaureo</code> page layout. Changed <code>\toclabelspace</code> command and renamed to <code>\toclabelwidth</code> . New <code>collection</code> document structure 1
v1.1		v1.9a
General: Added the <code>fixltxhyph</code> package. Documentation updated	1	General: Maintenance release. Updated greek support. Updated documentation. 1
v1.2		v1.9b
General: Maintenance release. Added the <code>\toclabelspace</code> command	1	General: Corrected a bug in “toc”, “lof” and “lot” commands. 1
v1.3		v1.9c
General: New command <code>\FSPLcolophon</code>	25	General: The <code>cbgreek</code> value for the <code>greekfont</code> option allows now to use the full set of the CB Greek font together with the default font (Palatino). 1
Updated documentation. Added <code>FSPLa</code> , <code>FSPLb</code> and <code>FSPLc</code> styles.	1	
v1.4		v2.0
General: New value <code>periodicalaureo</code> for option <code>pagelayout</code> . Changed code for <code>\xfootnote</code> command	1	General: New page layout <code>standardaureo</code> . Enhanced support for Lua ^A T _E X. Headers settings are now executed <code>\AtBeginDocument</code> . Loaded <code>ifluatex</code> and <code>ifthen</code> packages. Added <code>listparindent</code> to
v1.5		
General: The <code>microtype</code> package is loaded for all engines. Improved compatibility with <code>todonotes</code> package and with <code>mdframed</code> and <code>bookmark</code> packages when using <code>style</code> class option. New option <code>viewmode</code>	1	

	\setlist options. Updated documentation.	1	
v2.0.1	General: Corrected a bug in version option.	1	headerstyle, captionstyle, chapstyle, style; sufelements for option: style. The \chapnumfont command is no longer available.
v2.1	General: New option toc<level>font . Updated documentation. Removed \includeart command	1	1
v2.2	General: Maintenance release.	1	General: Corrected a bug in v.2.7 (missing some \fi commands).
v2.3	General: Maintenance release.	1	v2.8 General: textcase no longer loaded. Changed definitions of \suftesi@MakeTextLowercase, \SUF@titlesmallcaps, \headbreak, \xheadbreak.
v2.4	General: Changed the default font to Cochineal with Linux Biolinum O sans serif and Inconsolata monospaced. The Palatino is now loaded with newpxtext and newpxmath . Bera Mono and Iwona have been substituted by Linux Biolinum O and Inconsolata. New values for font options: cochineal , libertine , bodoni (greek only). Value compatibility for defaultfont option to get the fonts of sufjesi v2.3 or previous. Updated documentation.	1	v2.9 General: New options tocauthorfont and toctitlefont . Added macros \suftesi@MakeTextTOCLowercase and \SUF@TOCTitlesmallcaps. Improved \xheadbreak command. New templates book , theses-template-article , theses-template-book
v2.5	General: Corrected a bug when loading CB Greek fonts. Renamed option documentstructure to structure . Updated documentation.	1	v2.9.1 General: Added libertinust1math package for Libertine font. Added luatex85 for LuaTeX engine
v2.6	General: New mathfont option for non-standard fonts. New command \makecover for printing the cover page. Updated documentation.	1	v2.9.2 General: Added \protect to \SUF@thechapter and \SUF@thesection in the definitions of \chaptermark and \sectionmark to correct a bug when loading greek option with babel
v2.7	General: New value cscreen for version option. Updated documentation. Removed value elements for options: pagelayout ,		v2.9.3 General: New commands to change the font of the section titles and numbers.
			20
			Updated documentation.
			1
			v2.9.4 General: New commands to change the font of the title of the articles and of the author's name in the collections
			24
			Updated documentation.
			1

v2.9.5		folder. New template
General: Restored templates		book-customize 1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	\@collectiontitle	\@journalyear
\@Alph	2344,	2031, 2032, 2171
2345, 2351, 2352	\@ctrerr	2442 \@latex@warning@no@line
\@Cauthor 1731, 1759, 1761	\@currentHref 2129, 2131	1800, 1803,
\@Ccirclegcolor	\@date	1806, 2009,
\@Ceditor 1732, 1775, 1777	1853, 1862,	2012, 2015,
\@Cfoot 1733, 1780, 1783	1880, 1889,	2018, 2021,
\@Cfootcolor 1737, 1782	1918, 1947,	2024, 2032, 2035
\@Cpagecolor 1734, 1751	1976, 1993, 2112	\@lowpenalty 2492
\@Csubtitle	\@dblarg 1810, 2039	\@mainmatterfalse 3068
. 1730, 1770, 1772	\@doi 1802, 1803	\@mainmattertrue 2271, 3069
\@Ctextcolor	\@endparpenalty 2495	\@makefnmark 1896, 1954, 2088
. 1736, 1761, 1767, 1772, 1777	\@fnsymbol 1829, 1895, 1953, 2087, 2436, 2443	\@makefntext 683, 686, 690, 693, 1897, 1955, 2089
\@Ctitle 1729, 1765, 1767	\@footnotemark 2447	\@makeschapterhead 2249
\@M 2306, 2329, 2495	\@footnotetext 2447	\@maketitle 1902, 1904, 1909, 1916, 1921, 2094, 2096, 2101, 2109, 2119
\@Roman 432, 444, 462, 477, 495, 510, 525, 537, 552, 564	\@headtitle 615, 619, 1809, 1812, 2038, 2041, 2137	\@mkboth 2251, 2898, 2912, 2926, 2945, 2965, 2984
\@afterheading 2338	\@highpenalty 2056, 2082	\@plus 2057, 2255, 2413
\@afterindentfalse 2327, 3077	\@idxitem 2258	\@pnumwidth 2059, 2060, 2065
\@afterindenttrue 3077	\@ifpackageloaded 1200, 1664, 1696, 1747, 2213, 2460, 3071, 3073	\@restonecolfalse 2242, 2942, 2962, 2981
\@arabic 1604, 1606, 1608, 1610, 1612, 2181, 2183, 2185, 2187, 2189	\@ifpackagewith 2193	\@restonecoltrue 2244, 2940, 2960, 2979
\@author 616, 620, 1820, 1850, 1877, 1944, 1990, 2049, 2111, 2127, 2136, 2141, 2556	\@ifstar 3006	\@roman 428, 440, 457, 472, 490, 505, 521, 533, 548, 560
\@beginparpenalty 2492	\@isbn 1799	\@sec@pppage 2324
\@centercr 2425	\@issn 1800, 1805, 1806	\@standardmaketitle 1960, 1962,
\@chap@pppage 2299	\@issue 2017, 2018, 2029	
\@chapapp 2350	\@issuename 2030	
\@chapterintro 3007, 3008	\@journalname	
\@collectioneditor 2034, 2035, 2174 2008, 2009, 2028	
	\@journalnumber	
 2014, 2015, 2028	
	\@journalvolume	
 2011, 2012	
	\@journalwebsite	
 2023, 2024	

1967, 1974, 1979	2482, 2494,	C
\@starttoc 2902, 2905, 2916, 2919, 2930, 2933, 2951, 2954, 2970, 2973, 2990, 2993	2501, 2505, 2512 \addappheadtotoc 2310, 2334 \addfontfeature 1448, 1450, 1452 \addpenalty 2056	\c@chapter 2351, 2352 \c@footnote 1829, 1895, 1953, 2027, 2087, 2443 \c@paragraph 1610, 2187 \c@section 1604, 2181, 2344, 2345 \c@subparagraph 1612, 2189
\@tempswafalse 2302, 3007	\addtolength 2593, 2594	\c@subsection 1606, 2183
\@tempswatrue 2302, 3007	\alph 646, 653, 660	\c@subsubsection 1608, 2185
\@textsuperscript 1896, 1899, 1954, 1957, 2088, 2091	\and 1864, 1891, 1920, 1978, 2117 \appendicesname 2267, 2268	\c@tocdepth 2055 \captionsetup 707, 709, 710, 712, 713, 715
\@thanks 1855, 1861, 1882, 1888, 1911, 1917, 1969, 1975, 2026, 2027, 2103, 2110, 2148, 2163	\appendix 2266, 2341, 2347 \appendixname 2264, 2350 \appendixpage 2269 \appendixpagename 2262, 2308, 2331 \appendixtocname 2263	\Cauthor 1731, 1738 \cc 2556 \Cciclecolor 1735
\@thefnmark 684, 688, 691, 694, 1896, 1899, 1954, 1957, 2088, 2091, 2446	\arabic 422, 434, 449, 450, 464, 465, 482, 483, 497, 498, 515, 527, 542, 554, 645, 652, 659	\Ceditor 1732, 1741 \Cfoot 1733, 1742 \Cfootcolor 1737, 1745 \changes 2260 \chapfont 576 \chapnumfont 580
\@title . 1809, 1816, 1835, 1839, 1841, 1844, 1872, 1929, 1933, 1935, 1938, 1985, 2038, 2045, 2113, 2126, 2143	\artcolophon 2537 \AtBeginDocument 836, 1199, 1219, 1391, 1663, 1695, 1746, 2119, 2192, 2357, 2435, 2459, 2592, 2609, 2645,	\chapter 1464, 1470, 1563, 1564, 1567, 1568, 1571, 1572, 1575, 1576, 1579, 1580, 1583, 1584, 1586, 1588, 1596, 1597, 1599, 1698, 1701, 1704, 1708, 1712, 1715, 2944, 2964, 2983, 3029, 3041
\@titlepagefalse 79, 853	2780, 3072, 3074 2467 \AtBeginEnvironment	\chapterintro . 2999, 3001, 3003, 3006
\@titlepagetrue . . . 851	2266	\chapterintroname 3011, 3012
\@todonotes@drawLineToLeftMargin	2470 \author 1822, 2051, 2115	\chaptermark 2362
. 2466, 2469	\authorfont 586	\chaptertitlename . 2363
\@todonotes@drawMarginNoteWithLine	B	\ClassError
. 2461	\backmatter 3062, 3063, 3065 1202, 1596, 1789, 2071,
\@topnum 1908, 1966, 2100	\baselineskip . 1445, 1477, 1762, 1777	
_ . 731, 2026, 2363, 2365	\bibname 1697, 1703, 1711, 3029	
A	\bookcolophon 2529	
\abstractname . 2478,		

2437, 2582, \DeclareFontShape . .	795, 808, 815,
2598, 3000, 1400–	821, 827, 838,
3052, 3057, 3062 1407, 1409–	848, 855, 1086,
\ClassWarningNoLine 1411, 1414–	1095, 1101, 1110
.... 1, 57, 59, 1421, 1423–	\definecolor 1175, 1176
61, 63, 65, 67, 1425, 1428–	\disable@keys
88, 840, 1222, 1434, 1436–1438	75, 1042, 1060, 1079
1230, 1257, \DeclareRobustCommand	\doi 1802, 1804
1300, 1813, 103–106,	\dotfill 2064
1817, 1821, 117–120, 132–	\doublehyphendemerits
2042, 2046, 2050 135, 148–151, 2453, 2454
\clear@ppage 2300 164–167, 180–	\draw 1751, 1754
\cleardoublepage ... 183, 196–199,	
... 2162, 2280, 212–215, 232,	E
2289, 2528, 235, 238, 242,	\emph ... 2028, 2572, 3075
2536, 3068, 3069 246, 250, 256,	\encodingdefault . 1395
\clearpage 259, 262, 266,	\endcsname 1811, 2040,
... 2178, 2259, 2579 270, 274, 280,	2132, 2593, 2594
\col@number 283, 286, 290,	\endlist 2417, 2423,
... 1901, 1959, 2093 294, 298, 303,	2433, 3037, 3050
\collectioneditor ... 306, 309, 314,	\endquotation 2486, 2509
..... 2034, 2036 317, 320, 1393,	\ensuremath 2436
\collectiontitle ... 1447, 1449,	\ExecuteOptionsX . 1118
..... 2031, 2033 1451, 1454,	\exhyphenpenalty . 2452
\colophon 2513 1456, 1458, 3015	
\columnsep 2257 \DeclareTextFontCommand	F
\columnseprule ... 2256 1396	\f@series 1394
\contentsmargin ... 2644 \defbibheading 1665,	\f@shape 1394
\contentsname 1668, 1671,	\fancyfoot 2372, 2374,
... 2897, 2898, 1675, 1679,	2377, 2382, 2386
2944, 2946, 2947 1682, 1685,	\fancyhead 2379,
\contentspage 1687, 1690,	2380, 2388–2390
... 2279, 2832, 1697, 1700,	\fancyhf 2369,
2846, 2855, 1703, 1707,	2371, 2376, 2385
2864, 2871, 1711, 1714,	\fancypagestyle 2369,
2878, 2885, 2892 1717, 1720, 1724	2370, 2375, 2384
\copyright 2519 \define@choicekey ..	\finalcolophon ... 2542
\Cpagecolor . 1734, 1743 ... 72, 86, 99,	\finalhyphendemerits
\crop 836, 1190 228, 252, 276, 2454
\csname . 1811, 2040, 300, 311, 322,	\fontencoding 1219
2132, 2593, 2594 330, 338, 346,	\footnote 1828, 1868,
\Csubtitle ... 1730, 1740 354, 363, 371,	1926, 1984, 2123
\Ctextcolor . 1736, 1744 379, 387, 395,	\footnotemark 2026
\Title 1729, 1739 403, 411, 419,	\footnoterule
	.. 1827, 1867, 2360
D	\footnotesize . 676,
\date ... 1863, 1890, 623, 642, 666,	731, 1826, 1866,
1919, 1977, 2116 673, 680, 696,	2373, 2374,
\DeclareFontFamily 1399, 1413, 1427 704, 718, 724,	2378–2380,

	I	
2382, 2387–		\ifsuftesi@compatibility
2390, 2450, 2567	\if@dotoc@pp 2309, 2333	11, 1235
\footnotetext 2027	\if@mainmatter . . . 2404	\ifsuftesi@dottedtoc
\frenchspacing 3081	\if@openright 2314	36, 2064
\frontispiece 2165	\if@restonecol 2259,	\ifsuftesi@draftdate
\frontmatter 3052, 3053, 3055, 3068	2956, 2975, 2995	46, 2373, 2378, 2387
\FSPLcolophon 2552, 2581, 2583, 2585	\if@tempswa . 2320, 3009	\ifsuftesi@fewfootnotes
\fulljournal 2028	\if@titlepage 1824, 2488	47, 2434
G	\if@twocolumn . 1900,	\ifsuftesi@FSPL 49, 1185, 2551
\gdef 1241, 1244, 1247, 1284, 1287,	1958, 2092,	\ifsuftesi@greekfont
1290, 1324,	2241, 2302,	13, 1221, 1229,
1327, 1330,	2477, 2486,	1239, 1282, 1374
1354, 1357,	2500, 2509,	\ifsuftesi@libertine
1360, 1799,	2939, 2959, 2978	16, 1308
1802, 1805,	\ifheadbreak 3014, 3016	\ifsuftesi@mathextended
1809, 2008,	\ifLuaTeX 1181	23, 1270, 1312, 1341
2011, 2014,	\ifPDFTeX 1198,	\ifsuftesi@mathminimal
2017, 2020,	1373, 1446, 3076	22, 1275, 1317, 1346
2023, 2030,	\ifsuftesi@artemisia	\ifsuftesi@nofont
2031, 2034,	19, 1243, 1286, 12, 1220
2038, 2344,	1326, 1356, 1375	\ifsuftesi@numparchap
2345, 2350–2352	\ifsuftesi@article 39, 1463, 1476
\global . 1859–1864, 1886–1891, 26, 1485,	\ifsuftesi@numparpart
1908, 1914–	1498, 1595, 38, 1619, 1633
1920, 1966,	1662, 1837,	\ifsuftesi@numparsec
1972–1978,	1931, 2246, 40, 1482
2100, 2107–	2340, 2364,	\ifsuftesi@numparsubsec
2117, 2148, 2163	2394, 2715, 41, 1509
\greektext 1393, 1396	2789, 2839,	\ifsuftesi@numparsubsubsec
H	2845, 2894, 42, 1534
\hb@xt@ 1898, 1956, 2065, 2090	2998, 3025, 3051	\ifsuftesi@pagelefttoc
\headbreak 3015	\ifsuftesi@authortitle 50, 2070, 2643
\headbreakfalse 3014 27, 2395	\ifsuftesi@palatino
\headbreaktrue 3022	\ifsuftesi@bodoni 17, 1265
\headrulewidth 2359	20, 1240, 1283,	\ifsuftesi@partpage
\hemph 3075	1323, 1353, 1381 48, 1613
\hfill 2068, 2078	\ifsuftesi@cbgreek .	\ifsuftesi@periodical
\hss 1899, 1957, 2065, 2091 21, 1249,	28, 1562, 2194, 2214
\Huge 1767	1292, 1384, 1397	\ifsuftesi@periodicalaureo
\Hy@raisedlink 2130	\ifsuftesi@centerheader	29, 1566, 2209, 2234
\hyper@anchored 2131 24, 2406	\ifsuftesi@porson
\hyper@anchorstart 2131	\ifsuftesi@cochineal 18, 1246, 1289,
\hyphenpenalty 2452 15, 1336	1329, 1359, 1378
	\ifsuftesi@collection	\ifsuftesi@raggedtoc
 55, 1998, 2475 37, 2067
	\ifsuftesi@compact .	\ifsuftesi@reverseauthortitle
	30, 1570, 2197, 2218 54, 2125, 2140
	\ifsuftesi@compactaureo	\ifsuftesi@screen
	31, 1574, 2203, 2226 34, 1189

\ifsuftesi@screencentered	\journalnumber	2014, 2016	\makelabel ..	3036, 3049	
.....	35, 1191	\journalvolume	2011, 2013	\MakeLowercase	569
\ifsuftesi@smallcapschap	\journalwebsite	...	\maketitle	1825,	
...	44, 1834, 1928	1860,	1887,	
\ifsuftesi@smallcapspart	\journalyear	2020, 2022	1893,	1915,	
.....	43		1973,	2085, 2108	
\ifsuftesi@smallcapssec	L				
...	45, 1838, 1932	\l@title	2054	
\ifsuftesi@standard	\label	2128,	2198, 2201,	
.....	14, 1227	2151, 2153,	2161	2204, 2207,	
\ifsuftesi@sufplain	\labelitemi	639	2210, 2215,	
.....	25, 2407	\labelsep	2219, 2223,	
\ifsuftesi@supercompact	\labelwidth	..	3043	2227, 2231, 2235	
32, 1578, 2200, 2222	\LARGE	.	3034, 3046	\marginpar	722, 2455, 2456
\ifsuftesi@supercompactaur	\barge	...	1872, 1985, 2286	\markboth	1667, 1670,
33, 1582, 2206, 2230	\LaTeX	.	103, 117, 1772	1674,	1678,
\ifsuftesi@twocolumnlof	\leftmargin	2523, 2571, 2572	1699,	1702,
...	52, 2914, 2968	...	2411, 2419,	1706,	1710,
\ifsuftesi@twocolumnlot		2429,	2430,	2304, 2332,	2363
...	53, 2928, 2988	3033,	3045, 3046	\markright 1681,
\ifsuftesi@twocolumnmtoc	\leftmark	2404	1684,	1713,
...	51, 2900, 2949	\leftskip	687, 2061, 2062	1716,	1719,
\ifxheadbreak	\lineskip	1848, 1875,		1723,	2038, 2365
\ignorespaces		1942, 1988,	2451	Miede, André 78
\index	\lineskiplimit	...	2451	N	
\indexname	\list	...	2409, 2419,	\newcounter
...	2247, 2249, 2251	2426,	3031, 3042	..	1999–2002, 2004
\interlinepenalty	\listfigurename	2911,		\newlength 1444,
...	2306, 2329	2912,	2964–2966	1461,	2589,
\isbn	\listoffigures	2909, 2958		2607,	2610–
...	1799, 1801, 1805,	\listoftables	2923, 2977	2617,	2646–
\issue	\listparindent	2409,		2661,	2781–2788
...	2017, 2019	2410, 2428,	3047	\newline	... 2136, 3018
\issuename	\listtablename		\noappendicestocpagenum 2265
...	2030	2925, 2926,		\nobreak 2063,
\item		2983,	2985, 2986	2065,	2068,
...	2258, 2414, 2421,	\lmfntsclae	. 1250, 1293	2078,	2139, 2336
\itemindent		2421,	2431	\node 1753,
...	2410, 2427,	\LoadClass 71	1756,	1781, 2463
	2428,	3032,	3044	\noindent 1897,
\itemsep	\losname	1668,	1955,	2089,
...	2426	1675,	1682,	2416,	2519,
\itlabel		1700,	1707,	2523,	2533,
...	326, 334,	1714,	3038, 3041	2535,	2541,
	342, 350, 358,	1714,	3038, 3041	2556,	2559, 2571
	367, 375, 383,	\lowercase 570	\nr	72, 74, 86, 91, 99,
	391, 399, 407,	...	2266, 3057,	102,	228, 230,
	415, 630, 631,	3058,	3060, 3069	252,	254, 276,
	641, 1105, 1114,	\makecover 1748,	278,	300, 301,
	1652, 2449,	1789,	1791, 1795		
J					
\journalname					
...	2008, 2010				

311, 312, 322,	\partfont	575	519, 531, 546,
323, 330, 331,	\partname	1622,	558, 647, 654, 661
338, 339, 346,	1628,	1636,	
347, 354, 355,	1642,	2292, 2637	S
363, 364, 371,	\PassOptionsToClass	68	\secfont
372, 379, 380,	\penalty	2082	\secnumfont
387, 388, 395,	\phantomsection . .	3008	\section 1483, 1489,
396, 403, 404,	Poll, Philipp H.	4	1494, 1496,
411, 412, 419,	\ProcessOptionsX . . .	1162	1502, 1507,
421, 446, 448,	\protect 1813, 1817,		1666, 1669,
479, 481, 512,	1821, 2027,		1672, 1676,
514, 539, 541,	2042, 2046,		1680, 1683,
566, 568, 601,	2050, 2363, 2365		1718, 1721,
604, 623, 625,	\protected@xdef . . .	2026	1725, 2247,
642, 644, 666,			2478, 2501,
668, 673, 675,			2897, 2911,
680, 682, 696,	\quotation	2484, 2507	2925, 3009, 3026
698, 704, 706,			\sectionmark 2365, 2367
718, 720, 724,			\sectionsep
726, 740, 742,	\raggedleft	2457	1444, 1445,
770, 772, 785,	\raggedright		1494, 1507,
787, 795, 797, 2253, 2328, 2458		1520, 1532,
808, 810, 815,	\refname 1665, 1671,		1545, 1557,
816, 821, 823,	1679, 1685,		1617, 1654, 1661
827, 829, 838,	1687, 1690,		\setlength
843, 848, 850,	1717, 1720,		811, 813, 1445,
855, 863, 1086,	1724, 3026, 3027		1477, 1479,
1088, 1095,	\refstepcounter		2590, 2608,
1097, 1101, 2120, 2150		2618, 2620,
1102, 1110, 1111	\renewenvironment		2622, 2624,
 2240,		2626, 2628,
	2408, 2418, 2424		2630, 2632,
O			2662, 2664,
\oldmarginpar	\Rientro	2216,	2666, 2668,
. 2455, 2456, 2465	2220, 2224,		2670, 2672,
\onecolumn 2259, 2302,	2228, 2232, 2236		2674, 2676,
2940, 2960, 2979	\rightmargin	669, 2429	2678, 2680,
\origtableofcontents	\rightmark 605, 609, 2404		2682, 2684,
3020, 3023	\rightskip	2059	2686, 2688,
	\rlap	1896, 1954, 2088	2690, 2692,
P	\rmdefault	1392	2790, 2792,
\p@ 1831, 1870, 2057,	\Roman	430,	2794, 2796,
2255, 2257, 2413	442, 459, 460,		2798, 2800,
\pagestyle	474, 475, 492,		2802, 2805,
. 2358, 2405–2407	493, 507, 508,		2807, 2809,
\paragraph	523, 535, 550, 562		2811, 2813,
\parfillskip	\roman	426,	2815, 2817,
2060	438, 454, 455,		2819, 3032–
\parskip 2255, 3035, 3048	469, 470, 487,		3035, 3043–3048
\part 1616, 1617, 1620,	488, 502, 503,		\setlist
1626, 1634, 1640			640,

641, 645–650,	\SUF@ADJnumparchap .	\SUF@dotsubsec 516,
652–657, 659–664 1461,	520, 524, 528,
\sfdefault	1477, 1479,	532, 536, 1517, 1529
\small 678, 1826, 1848,	1563, 1567,	\SUF@dotsubsubsec ..
1853, 1866,	1571, 1575, 543,
1942, 1947,	1579, 1583, 1587	547, 551, 555,
2480, 2503,	\SUF@appendices ...	559, 563, 1542, 1554
2523, 2535,	.. 2267, 2282, 2286	\SUF@chapterintroname
2541, 2547, 2559	\SUF@appendixpage 3009–3011
\smallskip 2269, 2270	\SUF@greekfamily ..
\standardtitle 1865, 1951	\SUF@authorfont@Switch 1376,
\sty	586, 1112, 1114,	1379, 1382,
\subparagraph 1655, 1661	1116, 2127, 2141	1385, 1392, 1394
\subsecfont	\SUF@CHAP@StyleSwitch	\SUF@HEAD@thechapter
\subsecnumfont 582 332, 334, 450,
\subsection	336, 576, 1468, 1474	455, 460, 465,
... 1510, 1515,	\SUF@CHAP@thecontentslabel	470, 475, 2352, 2363
1520, 1522, 452, 457,	\SUF@HEAD@thesection
1527, 1532,	462, 467, 472, 483,
1686, 1688, 1691	477, 595, 2702, 2827	488, 493, 498,
\substitutefont .. 1392	\SUF@chapswitch 76,	503, 508, 2345, 2365
\subsubsecfont 579	80, 84, 482, 487,	\SUF@headingsmallcaps
\subsubsecnumfont .. 583	492, 497, 502, 507	634–636, 1451, 1458
\subsubsection 1535,	\SUF@chaptersize ..	\SUF@label@chap ..
1540, 1545,	. 103, 117, 132,	... 2589, 2590,
1547, 1552, 1557	148, 164, 180,	2619, 2621,
\SUF@addto@tochang@chap	196, 212, 1465,	2663, 2691,
... 2654, 2678,	1471, 1621,	2693, 2701,
2681, 2691,	1627, 1635,	2791, 2801,
2693, 2700, 2706	1641, 1833,	2803, 2806,
\SUF@addto@tochang@fig	1927, 2121,	2818, 2820, 2827
... 2660, 2690, 2767	2171, 2308, 2331	\SUF@label@fig ..
\SUF@addto@tochang@par 728,	... 2616, 2630, 2883
... 2658, 2686,	732, 736, 2832, 2845	\SUF@label@par 2614,
2689, 2749, 2752	\SUF@default@CHAPTER	2626, 2629,
\SUF@addto@tochang@sec 1462, 1560	2671, 2687,
... 2655, 2680,	\SUF@default@SECTIONS	2750, 2797,
2683, 2713, 2720 1481, 1561	2814, 2868–2870
\SUF@addto@tochang@subpar	\SUF@dotchap .. 451,	\SUF@label@part 2293,
..... 2659,	456, 461, 466,	2610, 2618, 2638
2688, 2758, 2761	471, 476, 1466, 1472	\SUF@label@sec 2611,
\SUF@addto@tochang@subsec	\SUF@dotpart .. 423,	2620, 2623,
... 2656, 2682,	427, 431, 435,	2631, 2633,
2685, 2727, 2731	439, 443, 1622,	2665, 2681,
\SUF@addto@tochang@subsubsec	1628, 1636, 1642	2691, 2693,
... 2657, 2684,	\SUF@dotsec .. 484,	2714, 2717,
2687, 2738, 2742	489, 494, 499,	2808, 2818,
\SUF@addto@tochang@tab	504, 509, 1486,	2820, 2837,
... 2661, 2692, 2775	1491, 1499, 1504	2838, 2841, 2843

\SUF@label@subpar . .	305, 308, 1511,	\SUF@subsectionszie
... 2615, 2628,	1516, 1523, 1528	. 105, 119, 134,
2673, 2689,	\SUF@lr@SUBSUBSECSwitch	150, 166, 182,
2759, 2799, 313,	198, 214, 1511,
2816, 2875–2877	316, 319, 1536,	1516, 1523,
\SUF@label@subsec . .	1541, 1548, 1553	1528, 1536,
... 2612, 2622,	\SUF@mpsetup	1541, 1548, 1553
2625, 2667,	... 2448, 2457, 2458	\SUF@SUBSUBSEC@StyleSwitch
2683, 2728,	\SUF@PART@StyleSwitch 356, 358,
2793, 2810, 324, 326,	360, 579, 1539,
2850, 2851, 2853	328, 575, 1622,	1544, 1551, 1556
\SUF@label@subsubsec	1624, 1628,	\SUF@SUBSUBSEC@thecontentslabel
... 2613, 2624,	1630, 1636, 544, 548,
2627, 2669,	1638, 1642, 1644	552, 556, 560,
2685, 2739,	\SUF@PART@thecontentslabel	564, 598, 2739, 2860
2795, 2812,	. 424, 428, 432,	\SUF@subsubsectionszie
2859, 2860, 2862	436, 440, 444, 594 106,
\SUF@label@tab 676, 678,	120, 135, 151,
... 2617, 2632,	2415, 2422, 2432	167, 183, 199, 215
2768, 2776, 2890	\SUF@thechapter	449,
\SUF@leftmark . . .	454, 459, 464,	
.... 606, 610,	469, 474, 580,	
616, 620, 2396, 2401	1466, 1472, 2351	
\SUF@leftrightmark .	\SUF@Rheadstyle . .	\SUF@thepage . . .
... 606, 610, 2403	. 605, 609, 615,	. 628, 632, 636,
\SUF@Lheadstyle . .	619, 626, 630, 634	2374, 2382, 2388
. 606, 610, 616,	\SUF@rightmark 605,	\SUF@theprt . . 422,
620, 627, 631, 635	609, 615, 619,	426, 430, 434,
\SUF@lr@CHAPSwitch .	2379, 2389, 2398	438, 442, 1622,
..... 255,	\SUF@SEC@StyleSwitch	1628, 1636, 1642
258, 261, 264, 340, 342,	\SUF@thesection . .
268, 272, 1465, 1471	344, 577, 1488,	. 482, 487, 492,
\SUF@lr@coll@titleSwitch	1493, 1501, 1506	497, 502, 507,
..... 1089,	\SUF@SEC@thecontentslabel	515, 519, 523,
1091, 1093, 2122 485, 490,	527, 531, 535,
\SUF@LR@MarkSwitch .	495, 500, 505,	581, 1485, 1491,
... 2381, 2391,	510, 596, 2717, 2841	1498, 1504, 2344
2396, 2398, 2401	\SUF@sectionszie . .	\SUF@thesubsection .
\SUF@lr@PARTSwitch .	. 104, 118, 133, 515, 519,
..... 231,	149, 165, 181,	523, 527, 531,
234, 237, 240,	197, 213, 1484,	535, 542, 546,
244, 248, 1621,	1490, 1497, 1503	550, 554, 558,
1627, 1635, 1641	\SUF@SUBSEC@StyleSwitch	562, 582, 1517, 1529
\SUF@lr@SECSwitch 348, 350,	\SUF@thesubsubsection
..... 279,	352, 578, 1514, 542, 546,
282, 285, 288,	1519, 1526, 1531	550, 554, 558,
292, 296, 1484,	\SUF@SUBSEC@thecontentslabel	562, 583, 1542, 1554
1490, 1497, 1503 517, 521,	\SUF@titlefont@Switch
..... 302,	525, 529, 533,	585, 1103, 1105,
	537, 597, 2728, 2851	1107, 2126, 2143

\SUF@titlerule . . .	\SUF@tocindent@chap	385, 393, 401, 409, 417, 1447, 1454
.... 727, 731, 735, 2846, 2855, 2864, 2871, 2878, 2885, 2892 2781, 2805, 2808, 2818, 2820, 2824, 2826, 2830	\SUF@versionstring 2361, 2373, 2378, 2387
\SUF@titlesmallcaps	\SUF@tocindent@fig .	\SUF@fntscale . . 1241, 1244, 1247, 1284, 1287, 1290, 1324, 1327, 1330, 1354, 1357, 1360, 1400– 1407, 1409– 1411, 1414– 1421, 1423– 1425, 1428– 1434, 1436–1438
. 328, 336, 344, 352, 360, 1107, 1116, 1449, 1456, 1835, 1839, 1929, 1933	... 2787, 2800, 2817, 2880, 2882 \SUF@tocindent@par 2785, 2796, 2799, 2813, 2816, 2866 2782, 2790, 2793, 2807, 2810, 2835
\SUF@tocAUT@font .. 405, 407, 409, 2136	\SUF@tocindent@sec 2783, 2798, 2815, 2873
\SUF@tocCHAP@font .. 373, 375, 377, 589, 2703, 2706, 2829, 2831	\SUF@tocindent@subpar	\SUF@tocindent@subsec
\SUF@tochang .. 2607, 2608, 2663, 2679 2786, 2798, 2815, 2873	\suftesi@artemisiatriue 800
\SUF@tochang@chap ..	\SUF@tocindent@subsec	\suftesi@articletrue 78
.... 2646, 2662, 2665, 2675, 2677, 2696, 2698, 2704 2783, 2792, 2795, 2809, 2812, 2848	\suftesi@authortitletrue 614, 618
\SUF@tochang@fig .. 2652, 2674, 2764, 2766	\SUF@tocindent@subsubsec	\suftesi@bodonittrue 804
\SUF@tochang@par .. 2650, 2670, 2673, 2746, 2748, 2751 2784, 2794, 2797, 2811, 2814, 2857	\suftesi@cbgreektrue 806
\SUF@tochang@sec .. 2647, 2664, 2667, 2710, 2712, 2719	\SUF@tocindent@tab .	\suftesi@centerheadertrue 608, 621
\SUF@tochang@subpar ... 2651, 2672, 2755, 2757, 2760 2788, 2802, 2819, 2887, 2889	\suftesi@cochinealtrue 775
\SUF@tochang@subsec .. 2648, 2666, 2669, 2724, 2726, 2730	\SUF@toclabelnum ..	\suftesi@collectiontrue 82
\SUF@tochang@subsubsec .. 2649, 2668, 2671, 2735, 2737, 2741 2715, 2839	\suftesi@compactaureottrue 163
\SUF@tochang@tab .. 2653, 2676, 2772, 2774	\SUF@tocPART@font ..	\suftesi@compactcttrue 147
 365, 367, 369, 588	\suftesi@compatibilitytrue 783
	\SUF@tocSEC@font ..	\suftesi@dotteddototrue 730
 381, 383, 385, 590, 2718,	\suftesi@draftdatettrue 824
	2721, 2842, 2844	\suftesi@fewfootnotesttrue 699
	\SUF@tocSUBSEC@font	\suftesi@FSPLtrue 1033, 1050, 1068
 389, 391, 393, 591, 2729,	\suftesi@greekfontfalse 798, 1224,
	2732, 2852, 2854	1225, 1232, 1233
	\SUF@tocSUBSUBSEC@font	\suftesi@greekfonttrue . 800, 802, 804, 806
 397, 399, 401, 592, 2740, 2743, 2861, 2863	
	\SUF@tocTIT@font .. 413, 415, 417, 2137	
	\SUF@TOCtitlesmallcaps	
 369, 377,	

\suftesi@libertinetrue	\suftesi@twocolumnloftrue	556, 560, 564, 594–598, 2294,
.....	777	746, 753, 760, 765
\suftesi@MakeTextLowercase	\suftesi@twocolumnlottrue	2639, 2716,
.....	569, 572, 1450,	2750, 2759,
.....	. 749, 757, 761, 766	2768, 2776,
\suftesi@MakeTextTOCLowercase	. 743, 752, 756, 764	2840, 2869,
.....	570, 573, 1448, 1455	2876, 2883, 2890
\suftesi@mathextendedfalse	T	\thecontentspage ..
.....	789 \tableofcontents 2699,
\suftesi@mathextendedtrue 2895,	2705, 2713,
.....	793 2938, 3020, 3021	2720, 2727,
\suftesi@mathminimalse	\texorpdfstring .. 2136	2731, 2738,
.....	788 \textbullet .. 639	2742, 2749,
\suftesi@mathminimaltrue	\textgreek .. 1396	2752, 2758,
.....	791 \textls 1455, 1457, 1459	2761, 2767, 2775
\suftesi@nofonttrue	773 \textnormal .. 1512,	\thefootnote ..
\suftesi@numparchaptrue	1517, 1524,	... 1829, 1895,
....	265, 269, 273	1953, 2087, 2443
\suftesi@numparparttrue	1542, 1549, 1554	\thepage .. 628, 632, 636
....	241, 245, 249 \textsc 426, 438, 454,	\theparagraph ..
\suftesi@numparsectrue	455, 457, 469,	... 1609, 1612,
....	289, 293, 297	1650, 2186, 2189
\suftesi@pagelefttoctrue	470, 472, 487,	\thesection .. 1486,
.....	738 488, 490, 502,	1499, 1603,
\suftesi@palatinottrue	503, 505, 519,	1606, 2180, 2183
.....	521, 531, 533,	\thesubparagraph ..
.....	779 546, 548, 558, 560	... 1611, 1657, 2188
\suftesi@partpagetrue	\textsf .. 2526, 2573	\thesubsection 1512,
.....	817 \textsuperscript .. 694	1524, 1605,
\suftesi@periodicalaureotrue	\texttt .. 2361	1608, 2182, 2185
.....	211, \thanks 615, 616, 619,	\thesubsubsection ..
.....	1032, 1049, 1067 1537,
\suftesi@periodicaltrue	620, 1828, 1859, 1868, 1886,	1549, 1607,
.....	1886, 1914, 1926,	1610, 2184, 2187
\suftesi@porsontrue	1972, 1984,	\title .. 1809–
\suftesi@raggedtoctrue	2026, 2107,	1811, 1814,
.....	2118, 2123, 2134	1818, 2037,
\suftesi@reverseauthortitle	\textarticle ..	2039, 2040,
.....	1098 ... 2128, 2129,	2043, 2047, 2114
\suftesi@screencenteredtrue	2151, 2153, 2161	\titleclass .. 1616
.....	833 \thechapter .. 76	\titlecontents ..
\suftesi@screentrue	\thecontentslabel 2272, 2290,
.....	830, 832 . 424, 428, 432,	2635, 2695,
\suftesi@standardtrue	436, 440, 444,	2709, 2723,
.....	781 452, 457, 462,	2734, 2745,
\suftesi@sufplaintrue	467, 472, 477,	2754, 2763,
.....	612 485, 490, 495,	2771, 2823,
\suftesi@supercompactaureotrue	500, 505, 510,	2834, 2847,
.....	195 517, 521, 525,	2856, 2865,
\suftesi@supercompacttrue	529, 533, 537,	2872, 2879, 2886
.....	179 544, 548, 552,	

\titlefont	585	\tocsubsecfont	591	848, 855, 1086,
\titleformat . . .	1464,	\tocsubsecnumfont . .	597	1095, 1101, 1110
1470,	1483,	\tocsubsubsecfont . .	592	\version@string
1489,	1496,	\tocsubsubsecnumfont		2355, 2361
1502,	1510,	598	\versionstring 2355, 2356
1515,	1522,	\today	2361	
1527,	1535,	\tolerance	2452	
1540,	1547,	\twocolumn 1904, 1962,		X
1552,	1620,	2096, 2247,		\xfootnote 2445
1626,	1634,	2249, 2321,		\xheadbreak 232, 235,
1640,	1648, 1655	2956, 2975, 2995		238, 242, 246,
\titlerule				250, 256, 259,
. 727, 728, 731, 732				262, 266, 270,
		U		274, 280, 283,
\titlespacing		\url	2023	286, 290, 294,
. . . 1494, 1507,		\usefont	1394	298, 303, 306,
1520,	1532,	\useosf 1280, 1322, 1351		309, 314, 317, 320
1545,	1557,	\useproportional . . .		\xheadbreakBB . 235,
1563,	1564, 1281, 1352		238, 246, 250,
1567,	1568,			259, 262, 270,
1571,	1572,			274, 283, 286,
1575,	1576,	V		294, 298, 306,
1579,	1580,	\val	72, 86, 99,	309, 317, 320, 3019
1583,	1584,	228, 252, 276,		\xheadbreakfalse . . .
1586,	1588,	300, 311, 322,		2379, 2380,
1617,	1654, 1661	330, 338, 346,		2389, 2390, 3022
		354, 363, 371,		\xheadbreakNL
\tocchapfont	589	379, 387, 395,		232, 242,
\tocchapnumfont . . .	595	403, 411, 419,		256, 266, 280,
\toclabelspace		446, 479, 512,		290, 303, 314, 3018
. . . 2597, 2600, 2604		539, 566, 601,		\xheadbreaktrue . . . 3017
\toclabelwidth		623, 642, 666,		\XKV@classoptionslist
. . . 2591, 2601, 2605		673, 680, 696,	 1173
\tocpartfont	588	704, 718, 724,		\XKV@useoption 1163–1172
\tocpartnumfont . . .	594	740, 770, 785,		
\tocsecfont	590	795, 808, 815,		Y
\tocsecnumfont . . .	596	821, 827, 838,		\year 2519, 2552