

User's Guide to *suftesi*

A document class for typesetting
theses, books and articles

Ivan Valbusa*

v2.5 – 2016/03/02

Abstract

The standard document classes allow you to typeset beautiful documents but their layout is quite far from the stylistic requests of some humanists (mainly Italian). The *suftesi* class provides a set of “humanistic” page layouts, title styles and heading styles to typeset books, articles and theses. The styles are very simple and sober and also have the aim of finding an aesthetic harmony in its formal simplicity (see Valbusa 2012). They are largely inspired by some interesting readings, particularly *The Elements of Typographic Style* by Robert Bringhurst (1992), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie* by Jan Tschichold (1975) and *First Principles of Typography* by Stanley Morison (1936).

Contents				
1 Use	3	3.6 Notes, lists, quotations	13	
		3.7 Other options	14	
		3.8 Pre-defined styles	15	
2 Class features	3	4 New commands	15	
2.1 Document structure	3	4.1 Printing the colophon	15	
2.2 Page layouts	4	4.2 Breaking titles	17	
2.3 Font	4	4.3 Other commands	17	
2.3.1 Mathematics	5			
2.3.2 Greek	5			
2.4 The frontispiece	7	5 Collections	18	
		5.1 Options	19	
		5.2 Commands	20	
3 Options	9	6 Backward compatibility	20	
3.1 Layout	9	7 References	20	
3.2 Fonts	10			
3.3 Titles	11	8 The Code	21	
3.4 Table of contents	12			
3.5 Headings	12			

*Dipartimento di Scienze Umane, Università degli Studi di Verona — ivan dot valbusa at univr dot it

Legalese

Copyright © 2009-2016 Ivan Valbusa

This package is author-maintained. Permission is granted to copy, distribute and/or modify this software under the terms of the LaTeX Project Public License, version 1.3c or later (<http://latex-project.org/lppl>). This software is provided “as is”, without warranty of any kind, either expressed or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose.

In addition to the terms of this license the author requires an attribution notice (see section 4) like the following one: *This work has been typeset with L^AT_EX, using the **suftesi** class by Ivan Valbusa.*

The main feature of this class is the set of styles it provides. For this reason DO NOT MODIFY THE STYLES OF THIS CLASS WITH PACKAGES AND/OR COMMANDS WHICH CHANGE THE LAYOUT OF THE DOCUMENT. IF YOU DO NOT LIKE THESE STYLES, USE ANOTHER CLASS. If you use **suftesi** in a document typeset with another class (for example **book**), remember to clean up the preamble from all the layout redefinitions.

A brief history

The **suftesi** class was born as a result of the course *Introduzione a L^AT_EX per le scienze umane* (*Introduction to L^AT_EX for the human sciences*) which I held at the Graduate School of Human Sciences and Philosophy (**Scienze Umane e Filosofia**) of Verona University (Italy) in June 2010. Originally thought as a class to typeset theses, during these years it has developed many new features and styles. Finally it has become the referential class of the Joint Project *Formal Style for PhD Theses with LaTe_X* of the University of Verona.

Acknowledgments

I would like to thank Professors Paola Di Nicola, Director of the Graduate School, and Ugo Savardi who suggested to propose the course precisely to that School; Gilberto D'Arduini, Matteo Lanza and Antonio Rinaldi, who installed L^AT_EX on the computers used during the course; Catia Cordioli, for her help in the organization of the lessons; Corrado Ferreri, responsible of the E-Learning Center, who provided the T_EX Live 2009 DVDs. Special thanks to Professors Enrico Gregorio, the Italian guru of T_EX, for the T_EXpert support and his priceless “magic formulas”, and Tommaso Gordini for his valuable advice in choosing and improving the class features during these years. I would finally thank all the participants to the course who patiently resisted the four intensive lessons. This work is dedicated to them.

Feedback

If you have any questions, feedback or requests please email me at `ivan dot valbusa at univr dot it`. If you need specific features not already implemented, remember to attach the example files.

1 Use

The `suftesi` class is called as usual by

```
\documentclass[options]{suftesi}
```

You do not need to set the `a4paper` option as it is automatically loaded. All the options defined by the class are in the `<key>=<value>` format. In addition to these you can also use the options defined by the standard `book` class (on which `suftesi` is based) except those modifying the page dimensions (`a5paper`, `b5paper`, `legalpaper`, `executivepaper` and `landscape`), which are automatically disabled.

For using the class with the X_ET_EX and LuaT_EX engines you need to load the `fontspec` package (`mathspec` is an alternative only for X_ET_EX). With these engines the font options are turned off and the L_AT_EX default font (Computer Modern) is loaded.

The class loads some packages that may cause incompatibility if loaded in your main document: `caption`, `color`, `crop`, `enumitem`, `emptypage`, `extramarks`, `fancyhdr`, `fixltxhyph`, `fontenc`, `geometry`, `ifxetex`, `ifluatex`, `ifthen`, `microtype`, `multicol`, `textcase`, `titlesec`, `titletoc`, `xkeyval`; `substitutefont` and `fontenc` (pdfL_AT_EXonly); `lmodern` (`defaultfont=standard`); `textcomp`, `newpxtext`, `biolinum`, `inconsolata`, `newpxmath`, `mathalpha` (`defaultfont=palatino`); `textcomp`, `libertine`, `biolinum`, `inconsolata`, `newtxmath`, `mathalpha` (`defaultfont=libertine`); `textcomp`, `cochineal`, `biolinum`, `inconsolata`, `newtxmath`, `mathalpha` (`defaultfont=cochineal`); `mathpazo`, `beramono` (`defaultfont=compatibility`).

2 Class features

The `suftesi` class provides a large set of options to customize the style of page, titles, headings and other text elements (see section 3). The simplest way to get to know the class features is therefore to typeset one of the templates which you can find in the `/doc/latex/suftesi` folder in your L_AT_EX distribution (see also Valbusa 2012). The class files as well as the templates are also available online on the CTAN's website at:

<https://www.ctan.org/tex-archive/macros/latex/contrib/suftesi>

2.1 Document structure

With `suftesi` you can typeset book-style documents (with chapters), article-style documents (without chapters) and collections of papers (see section 5). The kind of document is set by the `structure` option which defaults to `book` (see section 3).

```
\documentclass[structure=value,options]{suftesi}
```

2.2 Page layouts

The class provides nine page layouts which can be selected by the `pagelayout` option (table 1). The `standard` layout (default) or `standardaureo` layout are aimed to typeset A4 documents, while the other seven layouts are particularly suitable to typeset compact books, articles or theses. For these compact layouts it is particularly useful the `version=screen` option which shows the output in its real size. See section 3.1 for details.

Layout	Dimensions (mm)				Proportions			
	Typeblock		Page		Margins		Stock	
	w	h	w	h	t / b	i / o	Typeblock	Page
<code>standard</code>	110	220	210	297	1 : 2	1 : 2	1 : 2	1 : $\sqrt{2}$
<code>standardaureo</code>	136	220	210	297	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$
<code>compact</code>	110	165	160	240	2 : 3	2 : 3	2 : 3	2 : 3
<code>compactaureo</code>	118	191	160	240	2 : 3	2 : 3	5 : 8*	2 : 3
<code>supercompact</code>	100	150	140	210	2 : 3	2 : 3	2 : 3	2 : 3
<code>supercompactaureo</code>	108	175	140	210	1 : 1	1 : 1	5 : 8*	2 : 3
<code>periodical</code>	110	165	170	240	2 : 3	2 : 3	2 : 3	1 : $\sqrt{2}$
<code>periodicalaureo</code>	120	194	170	240	2 : 3	2 : 3	5 : 8*	1 : $\sqrt{2}$
<code>elements (pt)</code>	251	502	374	648	1 : 2	2 : 5	1 : 2	1 : $\sqrt{3}$

Table 1: The layouts of `suftesi`

* $5 : 8 \approx 1 : 1,618$

2.3 Font

The default roman font is Cochineal by Michael Sharpe, the sans serif font is Linux Biolinum O, designed by Philipp H. Poll, and the typewriter face is Inconsolata by Michael Sharpe. Cochineal is a fork of Crimson, by Sebastina Kosch, a font inspired by masterpieces like Sabon and Minion. It is a very complete typeface and it offers full support for Greek and Cyrillic, real small caps (even in italic shape) and four figure styles. Moreover it provides support for mathematics through the `newtxmath` package.

The `defaultfont` option allows you to change the default roman font to New PX (Palatino), Linux Libertine O, or Latin modern. You can use other fonts as well, but in this case remember to load the `defaultfont=none` class option which turns off the default font settings (see section 3 for details).

Another beautiful Garamond-like font, complete of real small caps, bold weight and mathematical support, is made available by the `garamondx` package by Michael Sharpe, which provides an extension of the `ugm` fonts, (URW)++ GaramondNo8. They are not distributed as part of TeXLive, but they may be downloaded using the `getnonfreefonts` script. See the instructions for installation at <http://tug.org/fonts/getnonfreefonts/>.

2.3.1 Typesetting mathematics

All the non-standard fonts selectable with the `defaultfont` option, i.e. Cochineal (default), Linux Libertine O and New PX, have a very good mathematical support, but if you aim at typesetting high mathematics the Latin Modern font family remains, of course, the better choice: `defaultfont=standard` (see section 3.2).

2.3.2 Typesetting Greek

The Cochineal default font is complete of Greek and Cyrillic. Anyway the class provides the `greekfont` option (see section 3.2) to select four different Greek fonts for use with the roman typeface set by the `defaultfont` option (except for the `defaultfont=standard` option, i.e. with Latin Modern font family which uses the CB Greek by default). These fonts are: GFS Bodoni, GFS Artemisia, GFS Porson, by the Greek Font Society and CB Greek by Claudio Beccari. You may, of course, choose a different font but, as previously cleared, remember to load the `defaultfont=none` option.

Cochineal/Cochineal Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Cochineal/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Cochineal/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Cochineal/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Cochineal/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Libertine/Libertine Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἐστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Libertine/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἐστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Libertine/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἐστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Libertine/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἐστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Libertine/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἐστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Palatino/Bodoni Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἐστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Palatino/Artemisia Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἴτα διορίσαι τί ἐστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Palatino/Porson Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἐστὶν

ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Palatino/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

Latin Modern/CB Greek Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit. Πρῶτον εἰπεῖν περὶ τί καὶ τίνος ἔστιν ἡ σκέψις, ὅτι περὶ ἀπόδειξιν καὶ ἐπιστήμης ἀποδεικτικῆς· εἶτα διορίσαι τί ἔστι πρότασις καὶ τί ὄρος καὶ τί συλλογισμός Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio.

2.4 The frontispiece

The class has an original frontispiece (see figure 1) now directly available loading the `frontespizio` package with the `suftesi` option. It is meant only for Italian users (see Gregorio 2009, version 1.4 or later):

```
\usepackage[suftesi]{frontespizio}
```

Note that this frontispiece requires the use of a logo which could be restricted by some institutions. So before using it you have to be sure that you have the required permissions.

The `frontespizio` package produces a frontispiece in the standard Computer Modern typeface. If you prefer a consistent font remember to load the needed packages or commands in the `\Preambolo` command:

```
\begin{frontespizio}
\Preambolo{\usepackage[osf]{cochineal}}% <===
\Universita{Paperopoli}
\Dipartimento{Filosofia, Pedagogia e Psicologia}
\Corso{Laurea}{Filosofia}
\Annoaccademico{2030--2031}
\Titolo{La mia tesi:\ una lunga serie di risultati\%
difficilissimi e complicatissimi}
\Sottotitolo{Alcune considerazioni mitevoli}
\Candidato[vr12301231]{Paolo Rossi}
\Relatore{Guido Bianchi}
\end{frontespizio}
```



University of St. Anford
Department of Typography

Ph.D. degree in `TeX` and `LATEX`

How to prepare a formal frontispiece

Theory and practice

Candidate:
Enrico Gregorio

Thesis advisor:
Prof. R. J. Drofnats

Research supervisors:
J. H. Quick
B. L. User

Thesis submitted in 2010

Figure 1: The frontispiece of `suftesi`

3 Options

3.1 Layout

structure=book, article, collection default: book

- book** For typesetting texts with chapters.
- article** For typesetting articles or short theses (that is without chapter division).
- collection** For typesetting journals or collections of articles (see section 5).

pagelayout=standard, standardaureo, periodical, default: standard
periodicalaureo, compact, compactaureo,
supercompact, supercompact, elements

- standard** Prints an A4 typeblock with a text area of 110 mm × 220 mm.

With the following values the option prints the typeblock on a an A4 paper showing the crop marks which can be controlled by the **version** option.

- periodical** Prints a typeblock of 17 cm × 24 cm with a text area of 11 cm × 16.5 cm.
- periodicalaureo** The same of **periodical** but with a *golden ratio* text area of 120 cm × 194 mm.
- compact** Prints a typeblock of 16 cm × 24 cm with a text area of 11 cm × 16.5 cm.
- compactaureo** The same as **compact** but with a *golden ratio* text area of 11.8 cm × 19.1 cm.
- supercompact** Prints a typeblock of 14 cm × 21 cm with a text area of 10 cm × 15.5 cm.
- supercompactaureo** The same as **supercompact** but with a *golden ratio* text area of 10.8 cm × 17.5 cm.
- elements** Prints a typeblock with the dimensions of Bringhurst (1992). To reproduce the whole style of this book use **style=elements** option instead.

The details of this option are shown in table 1.

version=screen, draft, final default: final

- screen** Prints the PDF with its real dimensions (according to the **pagelayout** option) and execute the **oneside** option. It is provided to have a better view when you are typesetting and reading the PDF on the screen.
- draft** Prints the output on a A4 paper, showing the crop marks.
- final** Prints the output on a A4 paper, hiding the crop marks.

3.2 Fonts

The first two options are available only with L^AT_EX. Using X_EL^AT_EX or LuaL^AT_EX the default font is the Computer Modern but you can change it through the `fontspec` or `mathspec` (X_EL^AT_EX only) packages. If you do not need to typeset mathematics, with these engines I do suggest the EB Garamond font family.

`defaultfont=none, cochineal, libertine, palatino, standard` default: `cochineal`

- | | |
|------------------|---|
| none | Does not load any font. Use this option if you want full control over the font selection. |
| cochineal | Loads the Cochineal serif, the Linux Biolinum O sans serif and the Inconsolata typewriter. |
| libertine | Loads the Linux Libertine O serif, the Linux Biolinum O sans serif and the Inconsolata typewriter. |
| palatino | Loads the New PX serif, the Linux Biolinum O sans serif and the Inconsolata typewriter. Note that the New PX font does not provide support for Greek. The <code>greekfont=artemisa</code> option offers a very good solution. |
| standard | Loads the Latin Modern font family and the standard CB Greek font. |

`greekfont=none, artemisia, porson, bodoni, cbgreek` default: `none`

- | | |
|------------------|---|
| none | Does not load any Greek font. |
| artemisia | Loads the Artemisia font by the Greek Font Society. |
| porson | Loads the Porson font by the Greek Font Society. ¹ |
| bodoni | Loads the Bodoni font by the Greek Font Society. |
| cbgreek | Loads the standard CB Greek font by Claudio Beccari. |

`smallcapsstyle=low, upper` default: `low`

- | | |
|--------------|--|
| low | Prints lowercase SMALL CAPITALS. |
| upper | Prints SMALL CAPITALS without changing the case. |

Active only with `<level>font=smallcaps` and `toc<level>font=smallcaps` options (see sections 3.3 and 3.4).

¹The first code for the Porson font has been written by Enrico Gregorio. Claudio Beccari successively added the code to improve the scale factor when using this greek font in combination with Palatino.

3.3 Titles

`<level>font=roman, italic, smallcaps` default: `roman`

- roman** Prints the `<level>` title in roman.
- italic** Prints the `<level>` title in *italic*.
- smallcaps** Prints the `<level>` title in SMALL CAPS

Where `<level>` can be `part, chap, sec, subsec, subsubsec`.

`<level>style=left, center, right, parleft, parcenter, parright` default: `left`

- left** Aligns the `<level>` title on the left.
- center** Centers the `<level>` title.
- right** Aligns the `<level>` title on the right.

Where `<level>` can be `part, chap, sec subsec, subsubsec`.

- parleft** As `left` but with the title below the number.
- parcenter** As `center` but with the title below the number.
- parright** As `right` but with the title below the number.

Where `<level>` can be `part, chap, sec`.

elements Print a chapter number in the style of Bringhurst (1992).

Where `<level>` can be `chap`.

`<level>numstyle=arabic, roman, Roman, dotarabic, dotroman, dotRoman` default: `Roman/arabic/arabic`

- arabic** Arabic `<level>` number.
- roman** Small caps lowercase roman `<level>` number.
- Roman** Uppercase roman `<level>` number.
- dotarabic** As `arabic` but followed by a dot.
- dotroman** As `roman` but followed by a dot.
- dotRoman** As `Roman` but followed by a dot.

Where `<level>` can be `part, chap, sec`.

3.4 Table of contents

tocstyle=standard, dotted, ragged, leftpage default: standard

- standard** Prints a standard table of contents with page numbers on the right margin.
- dotted** As the previous one but with dotted lines.
- ragged** Aligns the table of contents on the left as suggested by Bringhurst (1992).
- leftpage** Prints a table of contents with page numbers on the left margin.

toc<level>**font=**roman, italic, smallcaps default: roman

- roman** Prints the <level> TOC entry in roman.
- italic** Prints the <level> TOC entry in italic.
- smallcaps** Prints the <level> TOC entry in SMALL CAPS

Where <level> can be chap, sec, subsec, subsubsec.

twocolcontents=toc, lof, lot, toclof, toclot, loflot, all default: all

This option activates the **tocstyle=ragged** option and disables the other values of **tocstyle**.

- toc** Prints the table of contents in two columns.
- lof** Prints the list of figures in two columns.
- lot** Prints the list of tables in two columns.
- toclof** Prints the table of contents and the list of figures in two columns.
- toclot** Prints the table of contents and the list of tables in two columns.
- loflot** Prints the list of figures and the list of tables in two columns.
- all** Prints the table of contents, the list of figures and the list of tables in two columns.

3.5 Headings

headerstyle=inner, center, plain, authortitleinner, authortitlecenter, elements default: inner

- inner** Prints the chapter title and the string “Chapter <n>” in the inner side respectively of even and odd headers, and the page number in the outer side.
- center** Centers the header and footer and puts the page number in the center of the footer.
- plain** Prints no headers and puts the page number in the center of the footer.

authortitleinner Prints the author's name on the even pages and the title on the odd ones. In order to use this option the `\title` and `\author` commands are required.

authortitlecenter As the previous one but with centered headers and footers.

elements Prints the chapter title and the section title in the margin respectively of even pages and odd pages. The page number is put in the outer side of the footer. This is the style loaded by the option `style=elements`.

headerfont=roman, italic, smallcaps default: `roman`

roman Prints the headers in roman.

italic Prints the headers in *italic*.

smallcaps Prints the headers in SMALL CAPS.

3.6 Notes, lists, quotations

quotestyle=center, right default: `center`

center Indents the block quotations on both the left and right margins.

right Indents the block quotations only on the left margin.

quotesize=footnotesize, small default: `footnotesize`

footnotesize Prints the block quotations in `\footnotesize` size.

small Prints the block quotations in `\small` size.

footnotestyle=bulged, hung, dotted, superscript default: `bulged`

bulged The footnote number protrudes beyond the left margin.

hung Indents the footnote text, so it will hang under the first line of the text.

dotted The footnote number is aligned to the left margin and followed by a dot.

superscript Prints a superscript footnote number aligned to the left margin.

fewfootnotes=true, false default: `false`

Uses symbols instead of numbers to mark footnotes. It is active only in documents with three footnotes per page maximum. The symbol sequence is: *, **, ***. With more footnotes you should not need this option.

liststyle=bulged, aligned, indented default: `bulged`

bulged The item number or symbol protrudes beyond the left margin.

aligned Aligns the lists to the left margin.

indented Prints standard indented lists.

captionstyle=standard, sanserif, italic, smallcaps, elements default: standard

All these values print the caption in small size, changing the shape:

standard Prints the caption text and label in normal font.

sanserif Prints the caption text and label in `sanserif`.

italic Prints the caption text and label in *italic*.

smallcaps Prints only the caption label in SMALL CAPS.

elements An alias of `sanserif`.

3.7 Other options

parindent=compact, wide default: compact

Sets the indentation of the first line of each paragraph except those following a section title.

compact Sets indentation to 1 em.

wide Sets indentation to 1.5 em.

marginpar=true, false default: true

true Prints the marginal notes.

false Hide the marginal notes.

partpage=true, false default: false

Active only with `structure=article`.

true Prints the part title in a separate page as in `structure=book`

false Prints a part title similar to the one used in the standard `article` class.

draftdate=true, false default: false

If `true` it prints the string “Version of `\date{<date>}`” in the footer. It requires the `\date{<date>}` command.

crop=true, false default: true

Actually useless. Use the `version` option instead.

true Prints the output on a A4 paper, showing the crop marks. It is the same of `version=draft`.

false Prints a PDF with page dimensions according to the `pagelayout` option. It is similar to `version=screen` but it does not execute `oneside` option and it does not redefine `\crop`.

3.8 Pre-defined styles

These pre-defined styles are intended as shotrcuts to some groups of class options. Combining them with `dottedchap` and `romanchapnum` options you can get up to 120 variants.

```
style=roman(1-6), italic(1-12), smallcaps(1-6), elements,           default: roman1
      sufelements
```

roman(1-6) The titles of chapters and headers are printed in `roman`. The number of the chapter is on the same line in styles 1-3 and above the title in styles 4-6. The title can be printed on the left (styles 1 and 4), in the center (styles 2 and 5) or on the right (styles 3 and 6).

italic(1-12) The titles of chapters and headers are in `italic`. The section title is in `italic` in styles 1-6 and in `SMALL CAPS` in styles 7-12. There are three position for the title and two positions for the number as above.

smallcaps(1-12) The titles of chapters and headers are in `SMALL CAPS`. The title of the section is in `italic` in styles 1-6 and in `SMALL CAPS` in styles 7-12. There are three position for the title and two positions for the chapter as above.

elements Reproduces the style of the Italian edition of Bringhurst (1992).

sufelements Combines the `elements`-style sections with standard small caps headers. It can be used with all the page layouts.

4 New commands

4.1 Printing the colophon

As explained at the beginning of this documentation, in addition to the terms of the L^AT_EX Project Public License, `suftesi` requires a specific attribution notice. You can typeset the attribution notice manually or using one of these commands.

```
\colophon[<OS>]{<name and surname>}{{<additional info>}}
```

This command is provided only for Italian documents. It prints a page with a copyright notice and the colophon in the bottom of the page. For different languages use the `\bookcolophon` instead (see below).

If you don't need the copyright notice, leave the second argument of the command empty:

```
\colophon[<OS>]{}{{<additional info>}}
```

With the `article` option, you can use the `\artcolophon` command (see below) or the `\thanks` command:

```
\author{Name Surname}
\thanks{This work has been typeset with \LaTeX,
using the \textsf{suftesi} class
by Ivan Valbusa.}
```

\bookcolophon{\textit{copyright notice}}{\textit{attribution notice and other informations}}

Similar to \colophon but completely customizable. The first argument prints its content (usually the copyright notice) in the center of the page. The second one prints its content at the bottom. For example:

```
\bookcolophon{%
Copyright © 2007 by Ivan Valbusa}%
This work has been typeset with \LaTeX,
using the \textsf{suftesi} class
by Ivan Valbusa\index{Valbusa, Ivan}.
The serif font is Cochineal and the sans serif font
is Linux Biolinum O by Michael Sharpe.
}
```

\artcolophon{\textit{copyright notice, attribution and other informations}}

This command only has one argument. It simply prints its content at the bottom of the page. Here is an example:

```
\artcolophon{%
This work is licensed under the Creative Commons
Attribution-NonCommercial-NoDerivs 3.0 Unported
License. To view a copy of this license, visit
\begin{center}
http://creativecommons.org/licenses/by-nc-nd/3.0
\end{center}
or send a letter to Creative Commons, 444
Castro Street, Suite 900, Mountain View,
California, 94041, USA.\[1ex]

Typeset with \LaTeX, using the \textsf{suftesi}
class by Ivan Valbusa.}
```

\finalcolophon{\textit{colophon content}}

The same as \artcolophon, but centering its content at the top of the page. It is aimed at typesetting a classical *colophon* at the end of the work.

4.2 Breaking titles

\headbreak

A manual break which is active for the table of contents but not in the text or in the headers.

```
\section{This title will be break here \headbreak{}  
inside the table of contents}
```

\xheadbreak

A manual break which is active in the text but not in the headers and in the table of contents.

```
\section{This title will be break here \xheadbreak{}  
inside the text}
```

4.3 Other commands

\toclabelwidth{\langle level\rangle}{\langle dim\rangle}

Adds the *dim* to the *level* label in the table of contents, where *level* can be **part**, **chap**, **sec**, **subsec**, **subsubsec**, **par**, **subpar**, **fig**, **tab**. For example, when using **chapnumstyle=Roman** you would probably need to adjust the width of the chapter label with:

```
\toclabelwidth{chap}{1em}
```

\xfootnote[\langle symbol\rangle]{\langle footnote text\rangle}

A command to print a footnote with a discretionary symbols given in the optional argument (default=*)). It does not increment the footnote counter.

```
\xfootnote[$\dagger$]{\langle Footnote text\rangle}  
\xfootnote[\textdagger]{\langle Footnote text\rangle}
```

\title[\langle short title for headers\rangle]{\langle complete title for titlepage\rangle}

Useful with **authortitle** option if the title is too long or has some breaks.

\chapterintro

Prints an unnumbered introduction at the beginning of the chapter, with the correct hyperlink. In order to use this command the **hyperref** package must be loaded.

`\chapterintroname{\langle name\rangle}` (default=Introduzione)

Changes in `\langle name\rangle` the title printed by the `\chapterintro` command.

`\appendixpage`

Prints a page with the argument of `\appendicesname` (default=Appendici) at the center. Particularly useful if you have two or more appendices.

`\appendicesname{\langle name\rangle}` (default=Appendici)

Changes in `\langle name\rangle` the title printed by the `\appendixpage` command.

`\chapnumfont{\langle name\rangle}`

Sets the font of the chapter number of `style=elements` and `style=sufelements` styles. The default is Libertine (L^AT_EX) or Computer Modern (X_EL^AT_EX and LuaL^AT_EX). Using (pdf)L^AT_EX you can change it simply giving the name of the font family.

For example, to select the Helvetica family you will need:

`\chapnumfont{phv}`

With X_EL^AT_EX and LuaL^AT_EX the `\fontspec` command is required:

`\chapnumfont{\fontspec[Numbers=OldStyle]{Helvetica}}`

5 Collections

The `collection` document structure is thought to compose a collection of papers. Each paper has to be typeset in a separate `.tex` inside the `article` environment:

```
\begin{article}
\author{Author}
\title{Title of the paper}
% The abstract is optional.
% \begin{abstract}
% The abstract
% \end{abstract}

\maketitle

Text of the paper
\end{article}
```

If the names of the papers are `article1.tex`, `article2.tex`, `article3.tex`, etc., then a minimal main file should be similar to this:

```
\documentclass[structure=collection]{suftesi}

\begin{document}
\input{article1}
\input{article2}
\input{article3}
\end{document}
```

5.1 Options

In addition to the following options you can use the other options of the class too. In particular, with the `chapstyle` and `chapfont` options you can customize all the section titles which are treated as a normal unnumbered chapters in the `book` document structure, such as “Table of Contents”, “Index”, “Bibliography”, etc.

papertitlestyle=left, center, right default: left

- left** Aligns the author-title block on the left.
- center** Centers the author-title block.
- right** Aligns the author-title block on the right.

revauthortitle=true, false default: false

- true** Prints the author’s name below the title.
- false** Prints the author’s name above the title.

titlefont=roman, italic, smallcaps default: italic

- roman** Prints the title of the articles in roman.
- italic** Prints the title of the articles in *italic*.
- smallcaps** Prints the title of the articles in SMALL CAPS.

authorfont=roman, italic, smallcaps default: roman

- roman** Prints the author’s name in roman.
- italic** Prints the author’s name in *italic*.
- smallcaps** Prints the author’s name in SMALL CAPS.

Note that if you use this last option you need to protect the `\thanks` command:

```
\author{The Author\protect\thanks{...}}
```

5.2 Commands

\frontispiece

Typeset the frontispiece of the collection.

It requires the \collectiontitle and \collectioneditor commands in the preamble of your document.

\collectiontitle{\langle The Title of the Collection\rangle}

Sets the title of the collection.

\collectioneditor{\langle The Editor(s)\rangle}

Sets the editor(s) of the collection.

6 Backward compatibility

defaultfont=compatibility

Loads the fonts of *suftesi* v2.3 (or previous): Palatino (*mathpazo*), Iwona, Bera Mono. To get the default Greek font (*Artemisia*) of those versions add the *greekfont=artemisia* option.

documentstructure=book, article, collection

default: book

An alias for **structure**

style=FSPLa, FSPLb, FSPLc

These styles are only meant to typeset a doctoral thesis respecting the features required by the Joint Project *Formal Style for PhD Theses with LaTeX* of the Verona University (Italy).

The \FSPLcolophon{\langle Name Surname\rangle} command is provided to typeset the colophon according to these styles:

© 2016 \langle Name Surname\rangle

This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/3.0/>.

Typeset with *LATeX* in collaboration with the Joint Project *Formal Style for PhD Theses with LATeX* (University of Verona, Italy) using the *suftesi* class by Ivan Valbusa. The text face is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by Janus M. Nowacki.

References

This bibliography has been typeset with the `biblatex-philosophy` package, created by the same author of this class.

- Bringhurst, Robert (1992), *The Elements of Typographic Style*, 4th ed. (version 4.0), Hurtley & Marks Publisher, Vancouver; trans. *Gli elementi dello stile tipografico*, 5th ed., Sylvestre Bonnard, Milano 2009.
- Gregorio, Enrico (2009), *Il pacchetto frontespizio*, version 1.1, <http://www.guit.sssup.it/phpbb/index.php>.
- Miede, André (2011), *A Classic Thesis style*, <http://mirrors.ctan.org/macros/latex/contrib/classicthesis/ClassicThesis.pdf>.
- Morison, Stanley (1936), *First Principles of Typography*, Cambridge University Press, Cambridge; trans. *I principi fondamentali della tipografia*, Fabrizio Serra editore, Pisa-Roma 2008.
- Tschichold, Jan (1975), *Ausgewählte Aufsätze über Fragen der Gestalt des Buches und der Typographie*, Birkhäuser Verlag, Basel; trans. *La forma del libro*, Sylvestre Bonnard, Milano 2003.
- Valbusa, Ivan (2012), “La forma del testo umanistico. La classe `suftesi`”, *ArsTEXnica*, 14 (Oct. 2012), pp. 15-30.

The Code

```
1 \ClassWarningNoLine{suftesi}{%
2   ****\MessageBreak
3   * DO NOT MODIFY THE STYLES OF THIS CLASS\MessageBreak
4   * WITH PACKAGES AND/OR COMMANDS WHICH\MessageBreak
5   * MAY CHANGE THE LAYOUT OF THE DOCUMENT.\MessageBreak
6   * SEE DOCUMENTATION FOR DETAILS.\MessageBreak
7   * ANYWAY, DON'T WORRY!\MessageBreak
8   * THIS IS A HARMLESS MESSAGE :-)\MessageBreak
9   ****}\%
10 \RequirePackage{xkeyval}
11 \newif\ifsuftesi@compatibility
12 \newif\ifsuftesi@nofont
13 \newif\ifsuftesi@greekfont
14 \newif\ifsuftesi@standard
15 \newif\ifsuftesi@cochineal
16 \newif\ifsuftesi@libertine
17 \newif\ifsuftesi@palatino
18 \newif\ifsuftesi@porson
19 \newif\ifsuftesi@artemisia
20 \newif\ifsuftesi@bodoni
21 \newif\ifsuftesi@cbgreek
22 \newif\ifsuftesi@centerheader
23 \newif\ifsuftesi@sufplain
24 \newif\ifsuftesi@article
25 \newif\ifsuftesi@authortitle
26 \newif\ifsuftesi@periodical
```

```

27 \newif\ifsuftesi@periodicalaureo
28 \newif\ifsuftesi@compact
29 \newif\ifsuftesi@compactaureo
30 \newif\ifsuftesi@supercompact
31 \newif\ifsuftesi@supercompactaureo
32 \newif\ifsuftesi@sufelements
33 \newif\ifsuftesi@nocrop
34 \newif\ifsuftesi@dottedtoc
35 \newif\ifsuftesi@raggedtoc
36 \newif\ifsuftesi@numparpart
37 \newif\ifsuftesi@numparchap
38 \newif\ifsuftesi@numparsec
39 \newif\ifsuftesi@numparsubsec
40 \newif\ifsuftesi@numparsubsubsec
41 \newif\ifsuftesi@smallcapspart
42 \newif\ifsuftesi@smallcapschap
43 \newif\ifsuftesi@smallcapssec
44 \newif\ifsuftesi@elementschap
45 \newif\ifsuftesi@elementsheader
46 \newif\ifsuftesi@elementsstructure
47 \newif\ifsuftesi@elementspagelayout
48 \newif\ifsuftesi@draftdate
49 \newif\ifsuftesi@fewfootnotes
50 \newif\ifsuftesi@partpage
51 \newif\ifsuftesi@FSPL
52 \newif\ifsuftesi@screen
53 \newif\ifsuftesi@pagelefttoc
54 \newif\ifsuftesi@twocolumntoc
55 \newif\ifsuftesi@twocolumnlof
56 \newif\ifsuftesi@twocolumnlot
57 \newif\ifsuftesi@reverseauthortitle
58 \newif\ifsuftesi@collection
59 \DeclareOption{a5paper}{%
60   \ClassError{suftesi}{Option 'a5paper' not available}%
61 \DeclareOption{b5paper}{%
62   \ClassError{suftesi}{Option 'b5paper' not available}%
63 \DeclareOption{legalpaper}{%
64   \ClassError{suftesi}{Option 'legalpaper' not available}%
65 \DeclareOption{executivepaper}{%
66   \ClassError{suftesi}{Option 'executivepaper' not available}%
67 \DeclareOption{landscape}{%
68   \ClassError{suftesi}{Option 'landscape' not available}%
The suftesi class is based on the standard book class but the previous options are disabled as
they contrast with the layouts provided by the class.
69 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{book}}
70 \ProcessOptions
71 \relax
72 \LoadClass{book}

```

Document structure

```

73 \define@choicekey{}{structure}{\val\nr}
74     {book,article,collection}[book]{%
75 \ifcase\nr\relax
76 \disable@keys{}{secnumstyle}
77 \or
78 \suftesi@articletrue
79 \atitlepagefalse
80 \or
81 \suftesi@collectiontrue
82 \setkeys{}{headerstyle=authortitleinner}
83 \fi}
84 \define@choicekey{}{documentstructure}{\val\nr}
85     {book,article,collection}[book]{%
86 \ifcase\nr\relax
87 \disable@keys{}{secnumstyle}
88 \or
89 \suftesi@articletrue
90 \atitlepagefalse
91 \or
92 \suftesi@collectiontrue
93 \setkeys{}{headerstyle=authortitleinner}
94 \fi}

```

Page layout

```

95 \RequirePackage{geometry}
96 \define@choicekey{}{pagelayout}{\val\nr}
97     {standard,standardaureo,periodical,compact,compactaureo,supercompact,
98      supercompactaureo,elements,periodicalaureo}[standard]{%
99 \ifcase\nr\relax
100 \DeclareRobustCommand{\SUF@chaptersize}{\Large}
101 \geometry{%
102     heightrounded,
103     a4paper,
104     includeheadfoot=true,
105     textwidth=    110mm,
106     textheight=   220mm,
107     marginratio=  1:2,
108     marginparwidth= 30mm,
109     marginparsep= 12pt}
110 \or
111 \DeclareRobustCommand{\SUF@chaptersize}{\Large}
112 \geometry{%
113     heightrounded,
114     a4paper,
115     includeheadfoot=true,
116     textwidth=    136mm,
117     textheight=   220mm,
118     marginratio=  2:3,
119     marginparwidth= 30mm,
120     marginparsep= 12pt}

```

```

121 \or
122 \suftesi@periodicaltrue
123 \DeclareRobustCommand{\SUF@chaptersize}{\large}
124 \geometry{
125   heightrounded,
126   includeheadfoot=false,
127   textheight=    165mm,
128   textwidth=    110mm,
129   paperwidth=    170mm,
130   paperheight=   240mm,
131   marginratio=  2:3,
132   marginparwidth= 26mm,
133   marginparsep= 10pt}
134 \or
135 \suftesi@compacttrue
136 \DeclareRobustCommand{\SUF@chaptersize}{\large}
137 \geometry{
138   heightrounded,
139   includeheadfoot=false,
140   textheight=    165mm,
141   textwidth=    110mm,
142   paperwidth=    160mm,
143   paperheight=   240mm,
144   marginratio=  2:3,
145   marginparwidth= 22mm,
146   marginparsep=  9pt}
147 \or
148 \suftesi@compactaureottrue
149 \DeclareRobustCommand{\SUF@chaptersize}{\large}
150 \geometry{
151   heightrounded,
152   includeheadfoot=false,
153   textheight=    191mm,
154   textwidth=    118mm,
155   paperwidth=    160mm,
156   paperheight=   240mm,
157   marginratio=  2:3,
158   marginparwidth= 19mm,
159   marginparsep=  9pt}
160 \or
161 \suftesi@supercompacttrue
162 \DeclareRobustCommand{\SUF@chaptersize}{\large}
163 \geometry{
164   heightrounded,
165   includeheadfoot=false,
166   textheight=    150mm,
167   textwidth=    100mm,
168   paperwidth=    140mm,
169   paperheight=   210mm,
170   marginratio=  2:3,

```

```

171     marginparwidth= 18mm,
172     marginparsep= 8pt}
173 \or
174 \suftesi@supercompactaureottrue
175 \DeclareRobustCommand{\SUF@chaptersize}{\large}
176 \geometry{
177     heightrounded,
178     includeheadfoot=false,
179     textheight= 175mm,
180     textwidth= 108mm,
181     paperwidth= 140mm,
182     paperheight= 210mm,
183     marginratio= 1:1,
184     marginparwidth= 11mm,
185     marginparsep= 7pt}\or
186 \suftesi@elementspagelayouttrue
187 \geometry{%
188     heightrounded,
189     includeheadfoot=false,
190     textwidth= 251pt,
191     textheight= 502pt,
192     paperwidth= 374pt,
193     paperheight= 648pt,
194     vmarginratio= 1:2,
195     marginparwidth= 60pt,
196     marginparsep= 18pt,
197     outer= 90pt}
198 \or
199 \suftesi@periodicalaureottrue
200 \DeclareRobustCommand{\SUF@chaptersize}{\large}
201 \geometry{%
202     heightrounded,
203     includeheadfoot=true,
204     textwidth= 120mm,
205     textheight= 194mm,
206     paperwidth= 17cm,
207     paperheight= 24cm,
208     marginratio= 2:3,
209     marginparwidth= 62pt,
210     marginparsep= 10pt}
211 \or
212 \fi}

```

Sections style

```

213 \define@choicekey{}{partstyle}[\val\nr]{%
214     left,center,right,parleft,parcenter,parright}[left]{%
215 \ifcase\nr\relax
216     \def\SUF@lr@PARTSwitch{\filright}
217 \or
218     \def\SUF@lr@PARTSwitch{\filcenter}

```

```

219 \or
220   \def\SUF@lr@PARTSwitch{\filleft}
221 \or\numpar
222   \def\SUF@lr@PARTSwitch{\filright}
223   \suftesi@numparparttrue
224 \or
225   \def\SUF@lr@PARTSwitch{\filcenter}
226   \suftesi@numparparttrue
227 \or
228   \def\SUF@lr@PARTSwitch{\filleft}
229   \suftesi@numparparttrue
230 \fi}
231 \define@choicekey{}{chapstyle}[\val\nr]{%
232   left,center,right,parleft,parcenter,parright,elements}[left]{%
233 \ifcase\nr\relax
234   \def\SUF@lr@CHAPSwitch{\filright}
235 \or
236   \def\SUF@lr@CHAPSwitch{\filcenter}
237 \or
238   \def\SUF@lr@CHAPSwitch{\filleft}
239 \or\numparchap
240   \def\SUF@lr@CHAPSwitch{\filright}
241   \suftesi@numparchaptrue
242 \or
243   \def\SUF@lr@CHAPSwitch{\filcenter}
244   \suftesi@numparchaptrue
245 \or
246   \def\SUF@lr@CHAPSwitch{\filleft}
247   \suftesi@numparchaptrue
248 \or
249   \suftesi@elementschaptrue
250 \fi}
251 \define@choicekey{}{secstyle}[\val\nr]{%
252   left,center,right,parleft,parcenter,parright}[left]{%
253 \ifcase\nr\relax
254   \def\SUF@lr@SECSwitch{\filright}
255 \or
256   \def\SUF@lr@SECSwitch{\filcenter}
257 \or
258   \def\SUF@lr@SECSwitch{\filleft}
259 \or\numparsec
260   \def\SUF@lr@SECSwitch{\filright}
261   \suftesi@numparsecttrue
262 \or
263   \def\SUF@lr@SECSwitch{\filcenter}
264   \suftesi@numparsecttrue
265 \or
266   \def\SUF@lr@SECSwitch{\filleft}
267   \suftesi@numparsecttrue
268 \fi}

```

```

269 \define@choicekey{}{subsecstyle}[\val\nr]{left,center,right}[left]{%
270 \ifcase\nr\relax
271   \def\SUF@lr@SUBSECSwitch{\filright}
272 \or
273   \def\SUF@lr@SUBSECSwitch{\filcenter}
274 \or
275   \def\SUF@lr@SUBSECSwitch{\filleft}
276 \fi}
277 \define@choicekey{}{subsubsecstyle}[\val\nr]{left,center,right}[left]{%
278 \ifcase\nr\relax
279   \def\SUF@lr@SUBSUBSECSwitch{\filright}
280 \or
281   \def\SUF@lr@SUBSUBSECSwitch{\filcenter}
282 \or
283   \def\SUF@lr@SUBSUBSECSwitch{\filleft}
284 \fi}

```

Sections font

```

285 \define@choicekey{}{partfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
286 \ifcase\nr\relax
287   \def\SUF@PART@StyleSwitch{\relax}
288 \or
289   \def\SUF@PART@StyleSwitch{\itshape}
290 \or
291   \def\SUF@PART@StyleSwitch{\expandafter\SUF@titlesmallcaps}
292 \fi}
293 \define@choicekey{}{chapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
294 \ifcase\nr\relax
295   \def\SUF@CHAP@StyleSwitch{\relax}
296 \or
297   \def\SUF@CHAP@StyleSwitch{\itshape}
298 \or
299   \def\SUF@CHAP@StyleSwitch{\expandafter\SUF@titlesmallcaps}
300 \fi}
301 \define@choicekey{}{secfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
302 \ifcase\nr\relax
303   \def\SUF@SEC@StyleSwitch{\relax}
304 \or
305   \def\SUF@SEC@StyleSwitch{\itshape}
306 \or
307   \def\SUF@SEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
308 \fi}
309 \define@choicekey{}{subsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
310 \ifcase\nr\relax
311   \def\SUF@SUBSEC@StyleSwitch{\relax}
312 \or
313   \def\SUF@SUBSEC@StyleSwitch{\itshape}
314 \or
315   \def\SUF@SUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
316 \fi}

```

```

317 \define@choicekey{}{subsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
318 \ifcase\nr\relax
319 \def\SUF@SUBSUBSEC@StyleSwitch{\relax}
320 \or
321 \def\SUF@SUBSUBSEC@StyleSwitch{\itshape}
322 \or
323 \def\SUF@SUBSUBSEC@StyleSwitch{\expandafter\SUF@titlesmallcaps}
324 \fi}

```

TOC font

```

325 \define@choicekey{}{tocchapfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
326 \ifcase\nr\relax
327 \def\SUF@tocCHAP@font{\relax}
328 \or
329 \def\SUF@tocCHAP@font{\itshape}
330 \or
331 \def\SUF@tocCHAP@font{\expandafter\SUF@titlesmallcaps}
332 \fi}
333 \define@choicekey{}{tocsecfont}[\val\nr]{roman,italic,smallcaps}[italic]{%
334 \ifcase\nr\relax
335 \def\SUF@tocSEC@font{\relax}
336 \or
337 \def\SUF@tocSEC@font{\itshape}
338 \or
339 \def\SUF@tocSEC@font{\expandafter\SUF@titlesmallcaps}
340 \fi}
341 \define@choicekey{}{tocsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
342 \ifcase\nr\relax
343 \def\SUF@tocSUBSEC@font{\relax}
344 \or
345 \def\SUF@tocSUBSEC@font{\itshape}
346 \or
347 \def\SUF@tocSUBSEC@font{\expandafter\SUF@titlesmallcaps}
348 \fi}
349 \define@choicekey{}{tocsubsubsecfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
350 \ifcase\nr\relax
351 \def\SUF@tocSUBSUBSEC@font{\relax}
352 \or
353 \def\SUF@tocSUBSUBSEC@font{\itshape}
354 \or
355 \def\SUF@tocSUBSUBSEC@font{\expandafter\SUF@titlesmallcaps}
356 \fi}

```

Sections number style

Part number style

```

357 \define@choicekey{}{partnumstyle}[\val\nr]
358     {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
359 \ifcase\nr\relax
360 \def\SUF@thepart{\arabic{part}}

```

```

361   \def\SUF@dotpart{}
362   \def\SUF@toclabelnum{}
363 \or
364   \def\SUF@thepart{\textsc{\romannumeral{part}}}
365   \def\SUF@dotpart{}
366   \def\SUF@toclabelnum{\scshape\@roman}
367 \or
368   \def\SUF@thepart{\Roman{part}}
369   \def\SUF@dotpart{}
370   \def\SUF@toclabelnum{\@Roman}
371 \or
372   \def\SUF@thepart{\arabic{part}}
373   \def\SUF@dotpart{.}
374   \def\SUF@toclabelnum{}
375 \or
376   \def\SUF@thepart{\textsc{\romannumeral{part}}}
377   \def\SUF@dotpart{.}
378   \def\SUF@toclabelnum{\scshape\@roman}
379 \or
380   \def\SUF@thepart{\Roman{part}}
381   \def\SUF@dotpart{.}
382   \def\SUF@toclabelnum{\@Roman}
383 \fi}

```

Chapter number style

```

384 \define@choicekey{}{chapnumstyle}[\val\nr]{arabic,roman,Roman,
385 dotarabic,dotroman,dotRoman}[arabic]{%
386 \ifcase\nr\relax
387   \def\SUF@thechapter{\arabic{chapter}}
388   \def\SUF@dotchap{}
389   \def\SUF@toclabelnum{}
390 \or
391   \def\SUF@thechapter{\textsc{\romannumeral{chapter}}}
392   \def\SUF@dotchap{}
393   \def\SUF@toclabelnum{\scshape\@roman}
394 \or
395   \def\SUF@thechapter{\Roman{chapter}}
396   \def\SUF@dotchap{}
397   \def\SUF@toclabelnum{\@Roman}
398 \or
399   \def\SUF@thechapter{\arabic{chapter}}
400   \def\SUF@dotchap{.}
401   \def\SUF@toclabelnum{}
402 \or
403   \def\SUF@thechapter{\textsc{\romannumeral{chapter}}}
404   \def\SUF@dotchap{.}
405   \def\SUF@toclabelnum{\scshape\@roman}
406 \or
407   \def\SUF@thechapter{\Roman{chapter}}
408   \def\SUF@dotchap{.}

```

```

409   \def\SUF@toclabelnum{\@Roman}
410 \fi}

Section number style

411 \define@choicekey{}{secnumstyle}[\val\nr]
412   {arabic,roman,Roman,dotarabic,dotroman,dotRoman}[arabic]{%
413 \ifcase\nr\relax
414   \def\SUF@thesection{\arabic{section}}
415   \def\SUF@dotsec{}
416   \def\SUF@toclabelnum{}
417 \or
418   \def\SUF@thesection{\textsc{\roman{section}}}
419   \def\SUF@dotsec{}
420   \def\SUF@toclabelnum{\scshape\@roman}
421 \or
422   \def\SUF@thesection{\Roman{section}}
423   \def\SUF@dotsec{}
424   \def\SUF@toclabelnum{\@Roman}
425 \or
426   \def\SUF@thesection{\arabic{section}}
427   \def\SUF@dotsec{.}
428   \def\SUF@toclabelnum{}
429 \or
430   \def\SUF@thesection{\textsc{\roman{section}}}
431   \def\SUF@dotsec{.}
432   \def\SUF@toclabelnum{\scshape\@roman}
433 \or
434   \def\SUF@thesection{\Roman{section}}
435   \def\SUF@dotsec{.}
436   \def\SUF@toclabelnum{\@Roman}
437 \fi}

```

This option controls the style of small capitals used in the title of chapters and sections using *<level>font=smallcaps* option:

```

438 \define@choicekey{}{smallcapsstyle}[\val\nr]
439   {low,upper}[low]{%
440 \ifcase\nr\relax
441   \def\suftesi@MakeTextLowercase{\MakeTextLowercase}
442 \or
443   \def\suftesi@MakeTextLowercase{\relax}
444 \fi}

```

Headers

Header style

```

445 \define@choicekey{}{headerstyle}[\val\nr]
446   {inner,center,plain,authortitleinner,
447    authortitlecenter,elements}[inner]{%
448 \ifcase\nr\relax
449   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
450   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}

```

```

451 \or
452   \suftesi@centerheadertrue
453   \def\SUF@rightmark{\SUF@Rheadstyle{\rightmark}}
454   \def\SUF@leftmark{\SUF@Lheadstyle{\SUF@leftrightmark}}
455 \or
456   \suftesi@sufplaintrue
457 \or
458   \suftesi@authortitletrue
459   \def\SUF@rightmark{\let\thanks@gobble\SUF@Rheadstyle{\@headtitle}}
460   \def\SUF@leftmark{\let\thanks@gobble\SUF@Lheadstyle{\@author}}
461 \or
462   \suftesi@authortitletrue
463   \def\SUF@rightmark{\let\thanks@gobble\SUF@Rheadstyle{\@headtitle}}
464   \def\SUF@leftmark{\let\thanks@gobble\SUF@Lheadstyle{\@author}}
465   \suftesi@centerheadertrue
466 \or
467   \suftesi@elementsheadertrue
468 \fi}

```

Header font

```

469 \define@choicekey{}{headerfont}[\val\nr]
470   {roman,italic,smallcaps}[roman]{%
471 \ifcase\nr\relax
472   \def\SUF@Rheadstyle{}
473   \def\SUF@Lheadstyle{}
474   \def\SUF@thepage{\thepage}
475 \or
476   \def\SUF@Rheadstyle{\itshape}
477   \def\SUF@Lheadstyle{\itshape}
478   \def\SUF@thepage{\thepage}
479 \or
480   \def\SUF@Rheadstyle{\SUF@headingsmallcaps}
481   \def\SUF@Lheadstyle{\SUF@headingsmallcaps}
482   \def\SUF@thepage{\SUF@headingsmallcaps{\thepage}}
483 \fi}

```

Text elements

Lists

```

484 \RequirePackage[inline]{enumitem}
485 \renewcommand\labelitemi{\color{sufgray}\textbullet}
486 \setlist[itemsep=.5ex,parsep=0pt,listparindent=\parindent}
487 \setlist[description]{font=\normalfont\itshape}
488 \define@choicekey{}{liststyle}[\val\nr]
489   {bulged,aligned,indented}[bulged]{%
490 \ifcase\nr\relax
491   \setlist[enumerate,1]{leftmargin=0pt,label=\arabic*.}
492   \setlist[enumerate,2]{leftmargin= 1.3\parindent,label=\alph*.}
493   \setlist[enumerate,3]{leftmargin= 1.3\parindent,label=\roman*.}
494   \setlist[itemize,1]{leftmargin=0pt}

```

```

495      \setlist[itemize,2]{leftmargin=1.3\parindent}
496      \setlist[itemize,3]{leftmargin=1.3\parindent}
497 \or
498      \setlist[enumerate,1]{leftmargin=1\parindent,label=\arabic*.}
499      \setlist[enumerate,2]{leftmargin= 1.5\parindent,label=\alph*.}
500      \setlist[enumerate,3]{leftmargin= 1.5\parindent,label=\roman*.}
501      \setlist[itemize,1]{leftmargin=1\parindent}
502      \setlist[itemize,2]{leftmargin=1.5\parindent}
503      \setlist[itemize,3]{leftmargin=1.5\parindent}
504 \or
505      \setlist[enumerate,1]{leftmargin=2\parindent,label=\arabic*.}
506      \setlist[enumerate,2]{leftmargin= 2.5\parindent,label=\alph*.}
507      \setlist[enumerate,3]{leftmargin= 2.5\parindent,label=\roman*.}
508      \setlist[itemize,1]{leftmargin=2\parindent}
509      \setlist[itemize,2]{leftmargin=2.5\parindent}
510      \setlist[itemize,3]{leftmargin=2.5\parindent}
511 \fi}

```

Quotations

```

512 \define@choicekey{}{quotestyle}[\val\nr]
513     {center,right}[center]{%
514 \ifcase\nr\relax
515 \def\SUF@quote@style{\rightmargin=\parindent}
516 \or
517 \def\SUF@quote@style{}%
518 \fi}
519 \define@choicekey{}{quotesize}[\val\nr]
520     {footnotesize,small}[footnotesize]{%
521 \ifcase\nr\relax
522 \def\SUF@quotation@size{\footnotesize}
523 \or
524 \def\SUF@quotation@size{\small}
525 \fi}

```

Footnotes

```

526 \define@choicekey{}{footnotestyle}[\val\nr]
527     {bulged,hung,dotted,superscript}[bulged]{%
528 \ifcase\nr\relax
529     \renewcommand\@makefntext{%
530         \hskip-2.5em\makebox[2em][r]{\@thefnmark}\hskip.5em}
531 \or
532     \renewcommand\@makefntext{%
533         \leftskip=1em\hskip-1.5em%
534         \makebox[1em][r]{\@thefnmark}\hskip.5em}
535 \or
536     \renewcommand\@makefntext{%
537         \textsuperscript{\@thefnmark}\hskip.5em}
538 \or
539     \renewcommand\@makefntext{%
540         \textsuperscript{\@thefnmark}\hskip.3em}

```

```

541 \fi}
542 \define@choicekey{}{fewfootnotes}[\val\nr]
543   {true,false}[true]{%
544 \ifcase\nr\relax
545   \suftesi@fewfootnotestrue
546 \or
547   \relax
548 \fi}

```

Captions

```

549 \RequirePackage[caption]
550 \define@choicekey{}{captionstyle}[\val\nr]
551   {standard,sanserif,italic,smallcaps,elements}[standard]{%
552 \ifcase\nr\relax
553   \captionsetup[labelsep=period,font=small]
554 \or
555   \captionsetup[labelsep=period,font=small]
556   \captionsetup{font+=sf}
557 \or
558   \captionsetup[labelsep=period,font=small]
559   \captionsetup{font+=it}
560 \or
561   \captionsetup[labelsep=period,font=small,labelfont=sc]
562 \or
563   \captionsetup[labelsep=period,font=small]
564   \captionsetup{font+=sf}
565 \fi
566 }

```

Marginal notes

```

567 \define@choicekey{}{marginpar}[\val\nr]
568   {true,false}[true]{%
569 \ifcase\nr\relax
570 \or
571   \renewcommand\marginpar[2][]{}
572 \fi}

```

Table of contents

```

573 \define@choicekey{}{tocstyle}[\val\nr]{%
574   {standard,dotted,ragged,leftpage}[standard]{%
575 \ifcase\nr\relax
576   \def\SUF@titlerule{\titlerule*{}}
577   \def\SUF@chaptitlerule{\titlerule*{}}
578 \or
579   \suftesi@dottedtoctrue
580   \def\SUF@titlerule{\titlerule*{\footnotesize .\ }}
581   \def\SUF@chaptitlerule{\titlerule*{}}
582 \or
583   \suftesi@raggedtoctrue
584   \def\SUF@titlerule{\hspace{1em}}}

```

```

585 \def\SUF@chaptitlerule{\hspace{1em}}
586 \or
587 \suftesi@pagelefttotrue
588 \fi}
589 \define@choicekey{}{twocolcontents}[\val\nr]{%
590   toc,lof,lot,toclof,toclot,loflot,all}[all]{%
591 \ifcase\nr\relax
592   \suftesi@twocolumnmtotrue
593   \setkeys{}{tocstyle=ragged}
594 \or
595   \suftesi@twocolumnloftrue
596   \setkeys{}{tocstyle=ragged}
597 \or
598   \suftesi@twocolumnlottrue
599   \setkeys{}{tocstyle=ragged}
600 \or
601   \suftesi@twocolumnmtotrue
602   \suftesi@twocolumnloftrue
603   \setkeys{}{tocstyle=ragged}
604 \or
605   \suftesi@twocolumnmtotrue
606   \suftesi@twocolumnlottrue
607   \setkeys{}{tocstyle=ragged}
608 \or
609   \suftesi@twocolumnloftrue
610   \suftesi@twocolumnlottrue
611   \setkeys{}{tocstyle=ragged}
612 \or
613   \suftesi@twocolumnmtotrue
614   \suftesi@twocolumnloftrue
615   \suftesi@twocolumnlottrue
616   \setkeys{}{tocstyle=ragged}
617 \fi
618 }

```

Fonts

Roman fonts

```

619 \define@choicekey{}{defaultfont}[\val\nr]{%
620   none,cochineal,libertine,palatino,standard,compatibility}[cochineal]{%
621 \ifcase\nr\relax
622   \suftesi@nofonttrue\suftesi@greekfontfalse
623 \or
624   \suftesi@cochinealtrue
625 \or
626   \suftesi@libertinetrue
627 \or
628   \suftesi@palatinotrue
629 \or
630   \suftesi@standardtrue

```

```
631 \or
632   \suftesi@compatibilitytrue
633 \fi}
```

Greek fonts

```
634 \define@choicekey{}{greekfont}[\val\nr]{%
635   none,artemisia,porson,bodoni,cbgreek}[none]{%
636 \ifcase\nr\relax
637 \suftesi@greekfontfalse
638 \or
639 \suftesi@greekfonttrue\suftesi@artemisiatrue
640 \or
641 \suftesi@greekfonttrue\suftesi@porsontrue
642 \or
643 \suftesi@greekfonttrue\suftesi@bodonittrue
644 \or
645 \suftesi@greekfonttrue\suftesi@cbgreektrue
646 \fi}
```

Other options

Indentation

```
647 \define@choicekey{}{parindent}[\val\nr]
648   {compact,wide}[compact]{%
649 \ifcase\nr\relax
650 \setlength\parindent{1em}
651 \or
652 \setlength\parindent{1.5em}
653 \fi}
```

Part page

```
654 \define@choicekey{}{partpage}[\val\nr]{true,false}[true]{%
655 \ifcase\nr\relax
656   \suftesi@partpagetrue
657 \or
658   \relax
659 \fi}
```

Crop marks

```
660 \define@choicekey{}{crop}[\val\nr]
661   {true,false}[true]{%
662 \ifcase\nr\relax
663 \or
664   \suftesi@nocroptrue
665   \newcommand*\crop[1][]{}
666 \fi}
```

Draftdate

```
667 \define@choicekey{}{draftdate}[\val\nr]
668   {true,false}[true]{%
```

```

669 \ifcase\nr\relax
670   \suftesi@draftdatetrue
671 \or
672 \fi}

View mode

673 \define@choicekey{}{version}[\val\nr]
674   {screen,draft,final}[draft]{%
675 \ifcase\nr\relax
676   \suftesi@nocroptrue
677   \newcommand*\crop[1][]{}
678 \or
679 \or
680   \AtBeginDocument{\crop[off]}}
681 \fi}

```

Titlepage

```

682 \define@choicekey{}{titlepage}[\val\nr]
683   {true,false}[true]{%
684 \ifcase\nr\relax
685   \titlepagetrue
686 \or
687   \titlepagefalse
688 \fi}

```

Pre-defined styles

```

689 \define@choicekey{}{style}[\val\nr]
690   {roman1,roman2,roman3,roman4,roman5,roman6,
691   italic1,italic2,italic3,italic4,italic5,italic6,
692   italic7,italic8,italic9,italic10,italic11,italic12,
693   smallcaps1,smallcaps2,smallcaps3,smallcaps4,smallcaps5,smallcaps6,
694   smallcaps7,smallcaps8,smallcaps9,smallcaps10,smallcaps11,smallcaps12,
695   elements,sufelements,FSPLa,FSPLb,FSPLc}
696   [roman1]{%
697 \ifcase\nr\relax

```

The ‘roman’ styles

```

698   \setkeys{}{chapstyle=left}
699 \or
700   \setkeys{}{chapstyle=center}
701 \or
702   \setkeys{}{chapstyle=right}
703 \or
704   \setkeys{}{chapstyle=parleft}
705 \or
706   \setkeys{}{chapstyle=parcenter}
707 \or
708   \setkeys{}{chapstyle=parright}
709 \or

```

The ‘italic’ styles

```
710  \setkeys{}{  
711  chapstyle=left,  
712  chapfont=italic,  
713  tocchapfont=italic,  
714  headerfont=italic}  
715 \or  
716  \setkeys{}{  
717  chapstyle=center,  
718  chapfont=italic,  
719  tocchapfont=italic,  
720  headerfont=italic}  
721 \or  
722  \setkeys{}{  
723  chapstyle=right,  
724  chapfont=italic,  
725  tocchapfont=italic,  
726  headerfont=italic}  
727 \or  
728  \setkeys{}{  
729  chapstyle=parleft,  
730  chapfont=italic,  
731  tocchapfont=italic,  
732  headerfont=italic}  
733 \or  
734  \setkeys{}{  
735  chapstyle=parcenter,  
736  chapfont=italic,  
737  headerfont=italic}  
738 \or  
739  \setkeys{}{  
740  chapstyle=parright,  
741  chapfont=italic,  
742  tocchapfont=italic,  
743  headerfont=italic}  
744 \or  
745  \setkeys{}{  
746  chapstyle=left,  
747  chapfont=italic,  
748  tocchapfont=italic,  
749  secfont=smallcaps,  
750  headerfont=italic}  
751 \or  
752  \setkeys{}{  
753  chapstyle=center,  
754  chapfont=italic,  
755  tocchapfont=italic,  
756  secfont=smallcaps,  
757  headerfont=italic}
```

```

758 \or
759   \setkeys{}{
760     chapstyle=right,
761     chapfont=italic,
762     tocchapfont=italic,
763     secfont=smallcaps,
764     headerfont=italic}
765 \or
766   \setkeys{}{
767     chapstyle=parleft,
768     chapfont=italic,
769     tocchapfont=italic,
770     secfont=smallcaps,
771     headerfont=italic}
772 \or
773   \setkeys{}{
774     chapstyle=parcenter,
775     chapfont=italic,
776     tocchapfont=italic,
777     secfont=smallcaps,
778     headerfont=italic}
779 \or
780   \setkeys{}{
781     chapstyle=parright,
782     chapfont=italic,
783     tocchapfont=italic,
784     secfont=smallcaps,
785     headerfont=italic}
786 \or

```

The smallcaps' styles

```

787   \setkeys{}{
788     chapstyle=left,
789     chapfont=smallcaps,
790     tocchapfont=smallcaps,
791     headerfont=smallcaps}
792 \or
793   \setkeys{}{
794     chapstyle=center,
795     chapfont=smallcaps,
796     tocchapfont=smallcaps,
797     headerfont=smallcaps}
798 \or
799   \setkeys{}{
800     chapstyle=right,
801     chapfont=smallcaps,
802     tocchapfont=smallcaps,
803     headerfont=smallcaps}
804 \or
805   \setkeys{}{

```

```

806   chapstyle=parleft,
807   chapfont=smallcaps,
808   tocchapfont=smallcaps,
809   headerfont=smallcaps}
810 \or
811   \setkeys{}{
812   chapstyle=parcenter,
813   chapfont=smallcaps,
814   tocchapfont=smallcaps,
815   headerfont=smallcaps}
816 \or
817   \setkeys{}{
818   chapstyle=parright,
819   chapfont=smallcaps,
820   tocchapfont=smallcaps,
821   headerfont=smallcaps}
822 \or
823   \setkeys{}{
824   chapstyle=left,
825   chapfont=smallcaps,
826   tocchapfont=smallcaps,
827   secfont=smallcaps,
828   headerfont=smallcaps}
829 \or
830   \setkeys{}{
831   chapstyle=center,
832   chapfont=smallcaps,
833   tocchapfont=smallcaps,
834   secfont=smallcaps,
835   headerfont=smallcaps}
836 \or
837   \setkeys{}{
838   chapstyle=right,
839   chapfont=smallcaps,
840   tocchapfont=smallcaps,
841   secfont=smallcaps,
842   headerfont=smallcaps}
843 \or
844   \setkeys{}{
845   chapstyle=parleft,
846   chapfont=smallcaps,
847   tocchapfont=smallcaps,
848   secfont=smallcaps,
849   headerfont=smallcaps}
850 \or
851   \setkeys{}{
852   chapstyle=parcenter,
853   chapfont=smallcaps,
854   tocchapfont=smallcaps,
855   secfont=smallcaps,

```

```

856   headerfont=smallcaps}
857 \or
858   \setkeys{}{
859   chapstyle=parright,
860   chapfont=smallcaps,
861   tocchapfont=smallcaps,
862   secfont=smallcaps,
863   headerfont=smallcaps}
864 \or

```

The ‘elements’ style

```

865   \setkeys{}{
866     pagelayout=elements,
867     headerstyle=elements,
868     chapstyle=elements,
869     secfont=smallcaps,
870     subsecfont=italic,
871     captionstyle=elements}
872 \disable@keys{}
873   {pagelayout,headerstyle,chapstyle,secfont,subsecfont,captionstyle}
874 \or

```

The sufelements’ style

```

875   \setkeys{}{
876     chapstyle=elements,
877     headerfont=smallcaps,
878     secfont=smallcaps,
879     subsecfont=italic}
880 \disable@keys{}
881   {headerstyle,chapstyle,secfont,subsecfont}
882 \or

```

The FSPL styles

```

883 \suftesi@periodicalaureottrue
884 \suftesi@FSPLtrue
885   \setkeys{}{%
886     pagelayout=periodicalaureo,
887     style=roman5,
888     chapnumstyle=roman,
889     headerstyle=inner,
890     footnotestyle=hung,
891     liststyle=indented,
892     tocstyle=leftpage}
893 \disable@keys{}
894 {structure,pagelayout,partfont,chapfont,secfont,%
895 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
896 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
897 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
898 quotesize,footnotestyle,liststyle,captionstyle,parindent}

```

```

899 \or
900 \suftesi@periodicalaureottrue
901 \suftesi@FSPLtrue
902 \setkeys{}{%
903   pagelayout=periodicalaureo,
904   style=italic5,
905   chapnumstyle=roman,
906   headerstyle=inner,
907   headerfont=italic,
908   footnotestyle=hung,
909   liststyle=indented,
910   tocstyle=leftpage}
911 \disable@keys{}
912 {structure,pagelayout,partfont,chapfont,secfont,%
913 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
914 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
915 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
916 quotesize,footnotestyle,liststyle,captionstyle,parindent}
917 \or
918 \suftesi@periodicalaureottrue
919 \suftesi@FSPLtrue
920 \setkeys{}{%
921   pagelayout=periodicalaureo,
922   style=smallcaps5,
923   chapnumstyle=roman,
924   headerstyle=inner,
925   headerfont=smallcaps,
926   secfont=smallcaps,
927   footnotestyle=hung,
928   liststyle=indented,
929   tocstyle=leftpage}
930 \disable@keys{}
931 {structure,pagelayout,partfont,chapfont,secfont,%
932 subsecfont,subsubsecfont,partstyle,chapstyle,secstyle,%
933 subsecstyle,subsubsecstyle,partnumstyle,chapnumstyle,%
934 secnumstyle,tocstyle,headerstyle,headerfont,quotestyle,%
935 quotesize,footnotestyle,liststyle,captionstyle,parindent}
936 \fi}

```

Options for collection document structure

```

937 \define@choicekey{}{papertitlestyle}[\val\nr]{%
938   left,center,right}[left]{%
939 \ifcase\nr\relax
940   \def\SUF@lr@coll@titleSwitch{\filright}
941 \or
942   \def\SUF@lr@coll@titleSwitch{\filcenter}
943 \or
944   \def\SUF@lr@coll@titleSwitch{\filleft}
945 \fi}

```

```

946 \define@choicekey{}{revauthortitle}[\val\nr]
947   {true,false}[false]{%
948 \ifcase\nr\relax
949 \suftesi@reverseauthortitletrue
950 \or\relax
951 \fi}
952 \define@choicekey{}{titlefont}[\val\nr]{roman,italic,smallcaps}[roman]{%
953 \ifcase\nr\relax
954 \def\SUF@titlefont@Switch{\relax}
955 \or
956 \def\SUF@titlefont@Switch{\itshape}
957 \or
958 \def\SUF@titlefont@Switch{\expandafter\SUF@titlesmallcaps}
959 \fi}
960
961 \define@choicekey{}{authorfont}[\val\nr]{roman,italic,smallcaps}[roman]{%
962 \ifcase\nr\relax
963 \def\SUF@authorfont@Switch{\relax}
964 \or
965 \def\SUF@authorfont@Switch{\itshape}
966 \or
967 \def\SUF@authorfont@Switch{\expandafter\SUF@titlesmallcaps}
968 \fi}

```

Execute and process options

```

969 \ExecuteOptionsX<>{
970   captionstyle=standard,
971   marginpar=true,
972   parindent=compact,
973   tocstyle=standard,
974   defaultfont=cochineal,
975   greekfont=none,
976   pagelayout=standard,
977   headerstyle=inner,
978   liststyle=bulged,
979   footnotestyle=bulged,
980   quotesize=footnotesize,
981   quotestyle=center,
982   partstyle=left,
983   chapstyle=left,
984   secstyle=left,
985   subsecstyle=left,
986   subsubsecstyle=left,
987   partfont=roman,
988   chapfont=roman,
989   secfont=italic,
990   subsecfont=roman,
991   subsubsecfont=roman,
992   headerfont=roman,
993   secnumstyle=arabic,

```

```

994 partnumstyle=Roman,
995 chapnumstyle=arabic,
996 smallcapsstyle=low,
997 titlefont=italic,
998 authorfont=roman,
999 revauthortitle=false,
1000 papertitlestyle=left,
1001 authorfont=roman,
1002 titlefont=italic,
1003 tocchapfont=roman,
1004 tocsecfont=roman,
1005 tocsubsecfont=roman,
1006 tocsubsubsecfont=roman}
1007 \ProcessOptionsX<>\relax

```

The use of the `\XKV@useoption` command, provided by the `xkeyval`, is a trick to delete the option given as its argument from the list stored in `\@unusedoptionlist` so that the option will not produce the “Unused global options” message:

```

1008 \XKV@useoption{a4paper} \XKV@useoption{10pt}
1009 \XKV@useoption{11pt} \XKV@useoption{12pt}
1010 \XKV@useoption{oneside} \XKV@useoption{twoside}
1011 \XKV@useoption{onecolumn} \XKV@useoption{twocolumn}
1012 \XKV@useoption{titlepage} \XKV@useoption{notitlepage}
1013 \XKV@useoption{openright} \XKV@useoption{openany}
1014 \XKV@useoption{leqno} \XKV@useoption{fleqn}
1015 \XKV@useoption{a5paper} \XKV@useoption{b5paper}
1016 \XKV@useoption{legalpaper}\XKV@useoption{executivepaper}
1017 \XKV@useoption{landscape}

```

A trick to delete the class options from `\XKV@classoptionslist`, in order to avoid incompatibility with packages using options defined by `suftesi` too. Thanks to Enrico Gregorio!

```
1018 \def\XKV@classoptionslist{}
```

Basic packages

```

1019 \RequirePackage{color}
1020   \definecolor{sufred}{rgb}{0.5,0,0}
1021   \definecolor{sufgray}{rgb}{0.5,0.5,0.5}
1022 \RequirePackage{multicol}
1023 \RequirePackage{emptypage}
1024 \RequirePackage{ifxetex}
1025 \RequirePackage{ifluatex}
1026 \RequirePackage{ifthen}
1027 \RequirePackage{microtype}
1028 \RequirePackage{textcase}

```

The `\MakeTextLowercase` command provided by `textcase` conflicts with `hyperref` when the command is used to format the TOC entries (for example when unsing the `tocchapfont=smallcaps` option). Thanks to the user `skevin93` of the GuIT forum (www.guitex.org/home/it/forum) for this macro:

```

1029   \AtBeginDocument{
1030     \@ifpackageloaded{hyperref}{%
1031       \def\@uclcnmath#1#2#3#4{\begingroup #1%
1032         \def\({\$}\let\)\(\def\NoCaseChange##1{%

```

```

1033 \noexpand \NoCaseChange {\noexpand ##1}%
1034 \def\hyper@linkstart##1##2##3{%
1035 $ \valign$ \noexpand\hyper@linkstart{##1}{##2}{%
1036 \noexpand\@skipmath #3
1037 ##3$\valign $}\noexpand\@skipmath}\def\hyper@linkend{%
1038 \noexpand\hyper@linkend}%
1039 \cnonchange case \label
1040 \cnonchange case \ref
1041 \cnonchange case \ensuremath
1042 \def \cite ##1##2{\toks@ {\noexpand \cite ##1}\@citex }%
1043 \def \@citex ##1{\NoCaseChange {\the \toks@ {##1}}}%
1044 \def \reserved@a ##1##2{\let #2\reserved@a }%
1045 \expandafter \reserved@a \c@uclclist \reserved@c %
1046 {\reserved@c \c@gobble }%
1047 \protected@edef \reserved@a {\endgroup\noexpand %
1048 \c@skipmath #3##4$\valign $}%
1049 \reserved@a}{}}

```

The FSPL style requires a verbose colophon which uses specific icons:

```

1050 \ifsuftesi@FSPL
1051   \RequirePackage{cclicenses}
1052 \else
1053 \fi

```

Greek fonts

```

1054 \ifthenelse{\boolean{xetex}\or\boolean{luatex}}
1055 {%
1056   \AtBeginDocument{%
1057     \c@ifpackageloaded{fontspec}%
1058       {\relax}%
1059       {\ClassError{suftesi}%
1060         {*****\MessageBreak
1061         * For using suftesi with XeLaTeX\MessageBreak
1062         * load either 'fontspec' or 'mathspec'\MessageBreak
1063         * For using suftesi with LuaLaTeX\MessageBreak
1064         * load 'fontspec' \MessageBreak
1065         *****}%
1066         {*****\MessageBreak
1067         * For using suftesi with XeLaTeX\MessageBreak
1068         * load either 'fontspec' or 'mathspec'\MessageBreak
1069         * For using suftesi with LuaLaTeX\MessageBreak
1070         * load 'fontspec' \MessageBreak
1071         *****}%
1072       }
1073     }%
1074   }%
1075 \RequirePackage[LGR,T1]{fontenc}
1076 \RequirePackage{substitutefont}
1077 \AtBeginDocument{\fontencoding{T1}\selectfont}
1078 \ifsuftesi@nofont\relax
1079 \else

```

```

1080 \ifsuftesi@standard
1081     \RequirePackage{lmodern}
1082     \else
1083     \ifsuftesi@compatibility
1084         \RequirePackage[osf,sc]{mathpazo}
1085         \RequirePackage[scaled=0.8]{beramono}
1086             \renewcommand{\sfdefault}{iwona}
1087     \ifsuftesi@bodoni
1088         \def\SUFFntscale{0.955}
1089     \else
1090         \ifsuftesi@artemisia
1091             \def\SUFFntscale{0.97}
1092         \else
1093             \ifsuftesi@porson
1094                 \def\SUFFntscale{1.18}
1095             \else
1096                 \fi
1097             \fi
1098             \fi
1099     \else
1100         \ifsuftesi@palatino
1101             \RequirePackage[full]{textcomp}
1102                 \RequirePackage[osf]{newpxtext}
1103                 \RequirePackage[scaled=1.06]{biolinum}
1104                 \RequirePackage[varqu,varl]{inconsolata}
1105                 \RequirePackage[bigdelims,vvarbb]{newpxmath}
1106                 \RequirePackage[cal=boondoxo]{mathalfa}
1107         \ifsuftesi@bodoni
1108             \def\SUFFntscale{0.955}
1109         \else
1110             \ifsuftesi@artemisia
1111                 \def\SUFFntscale{0.97}
1112             \else
1113                 \ifsuftesi@porson
1114                     \def\SUFFntscale{1.18}
1115                 \else
1116                     \fi
1117                 \fi
1118                 \fi
1119 \else
1120     \ifsuftesi@libertine
1121         \RequirePackage{textcomp}
1122             \RequirePackage[sb]{libertine}
1123             \RequirePackage[varqu,varl,scaled=0.94]{inconsolata}
1124             \RequirePackage[libertine,bigdelims,vvarbb]{newtxmath}
1125             \RequirePackage[cal=boondoxo]{mathalfa}
1126             \useosf
1127     \ifsuftesi@bodoni
1128         \def\SUFFntscale{0.89}
1129     \else

```

```

1130      \ifsuftesi@artemisia
1131      \def\SUFfntscale{0.91}
1132      \else
1133      \ifsuftesi@porson
1134      \def\SUFfntscale{1.08}
1135      \else
1136      \fi
1137      \fi
1138      \fi
1139 \else
1140 \ifsuftesi@cochineal
1141 \RequirePackage{textcomp}
1142     \RequirePackage{cochineal}
1143     \RequirePackage[varqu,varl,varo]{inconsolata}
1144     \RequirePackage{biolinum}
1145     \RequirePackage[cochineal,bigdelims,cmintegrals,vvarbb]{newtxmath}
1146     \RequirePackage[cal=boondoxo]{mathalfa}
1147     \useosf
1148     \useproportional
1149 \ifsuftesi@bodoni
1150 \def\SUFfntscale{0.88}
1151 \else
1152 \ifsuftesi@artemisia
1153 \def\SUFfntscale{0.89}
1154 \else
1155 \ifsuftesi@porson
1156 \def\SUFfntscale{1.04}
1157 \else
1158 \fi
1159 \fi
1160 \fi
1161 \else
1162 \fi
1163 \fi
1164 \fi
1165 \fi
1166 \fi
1167 \fi

```

The greek fonts are available only with palatino, libertine and cochineal options.

```

1168 \ifsuftesi@greekfont
1169 \ifsuftesi@artemisia
1170 \def\SUF@greekfamily{artemisia}
1171 \else
1172 \ifsuftesi@porson
1173 \def\SUF@greekfamily{porson}
1174 \else
1175 \ifsuftesi@bodoni
1176 \def\SUF@greekfamily{bodoni}
1177 \else

```

```

1178           \ifsuftesi@cbgreek
1179           \def\SUF@greekfamily{lmr}
1180       \else
1181       \fi
1182   \fi
1183 \fi
1184 \fi

Thanks to Claudio Beccari for this macro.

1185 \AtBeginDocument{
1186   \substitutefont{LGR}{\rmdefault}{\SUF@greekfamily}
1187   \DeclareRobustCommand{\greektext}{%
1188     \usefont{LGR}{\SUF@greekfamily}{\f@series}{\f@shape}%
1189     \def\encodingdefault{LGR}%
1190     \DeclareTextFontCommand{\textgreek}{\greektext}%
1191   \else
1192   \fi
1193 % \DeclareFontFamily{LGR}{pplj}{}%
1194 % \DeclareFontShape{LGR}{pplj}{m}{n}{<->ssub * lmr/m/n}{}%
1195 % \DeclareFontShape{LGR}{pplj}{m}{it}{<->ssub * lmr/m/it}{}%
1196 % \DeclareFontShape{LGR}{pplj}{m}{sl}{<->ssub * lmr/m/sl}{}%
1197 % \DeclareFontShape{LGR}{pplj}{m}{sc}{<->ssub * lmr/m/sc}{}%
1198 % \DeclareFontShape{LGR}{pplj}{b}{n}{<->ssub * lmr/bx/n}{}%
1199 % \DeclareFontShape{LGR}{pplj}{b}{it}{<->ssub * lmr/bx/it}{}%
1200 % \DeclareFontShape{LGR}{pplj}{b}{sl}{<->ssub * lmr/bx/sl}{}%
1201 % \DeclareFontShape{LGR}{pplj}{b}{sc}{<->ssub * lmr/bx/sc}{}%
1202 % \DeclareFontShape{LGR}{pplj}{bx}{n}{<->ssub * lmr/bx/n}{}%
1203 % \DeclareFontShape{LGR}{pplj}{bx}{it}{<->ssub * lmr/bx/it}{}%
1204 % \DeclareFontShape{LGR}{pplj}{bx}{sl}{<->ssub * lmr/bx/sl}{}%
1205 % \DeclareFontShape{LGR}{pplj}{bx}{sc}{<->ssub * lmr/bx/sc}{}%
1206 % \DeclareFontShape{LGR}{pplj}{m}{li}{<->ssub * lmr/m/li}{}%
1207 % \DeclareFontShape{LGR}{pplj}{b}{li}{<->ssub * lmr/b/li}{}%
1208 % \DeclareFontShape{LGR}{pplj}{bx}{li}{<->ssub * lmr/bx/li}{}%
1209 % \DeclareFontShape{LGR}{pplj}{m}{ui}{<->ssub * lmr/m/ui}{}%
1210 % \DeclareFontShape{LGR}{pplj}{b}{ui}{<->ssub * lmr/m/ui}{}%
1211 % \DeclareFontShape{LGR}{pplj}{bx}{ui}{<->ssub * lmr/bx/ui}{}%
1212 % \DeclareFontShape{LGR}{pplj}{m}{rs}{<->ssub * lmr/m/rs}{}%
1213 % \DeclareFontShape{LGR}{pplj}{b}{rs}{<->ssub * lmr/m/rs}{}%
1214 % \DeclareFontShape{LGR}{pplj}{bx}{rs}{<->ssub * lmr/bx/rs}{}%
1215 %\ifsuftesi@porson
1216 %\sbox{z}{\fontsize{10}{10}\normalfont A}
1217 %\sbox{tw}{\font\temp=gporsonrg6a at 10pt \temp A}
1218 %\dimen@=\dimexpr \p@*\ht{z}/\ht{tw}@relax
1219 %\sbox{z}{\normalfont\fontsize{10}{10}\selectfont a}
1220 %\sbox{tw}{\font\temp=gporsonrg6a at 10pt \temp a}
1221 %\dimen2=\dimexpr \p@*\ht{z}/\ht{tw}@relax
1222 %\dimen4= 0.6\p@
1223 %\dimen@=\dimexpr \dimen@ - \dimen4*\dimen@/\p@+\dimen4*\dimen2/\p@\relax
1224 %\edef\art@scale{\strip@pt\dimen@}
1225 %\DeclareFontFamily{LGR}{porson}{}%
1226 %\DeclareFontShape{LGR}{porson}{m}{n}{ <-> s * [\art@scale] gporsonrg6a}{}%

```

```

1227 \%\\DeclareFontShape{LGR}{porson}{m}{it} {<-> ssub * porson/m/n}{}
1228 \%\\DeclareFontShape{LGR}{porson}{b}{n} {<-> ssub * porson/m/n}{}
1229 \%\\DeclareFontShape{LGR}{porson}{b}{it} {<-> ssub * porson/m/n}{}
1230 \%\\DeclareFontShape{LGR}{porson}{m}{sl} {<-> ssub * porson/m/n}{}
1231 \%\\DeclareFontShape{LGR}{porson}{b}{sl} {<-> ssub * porson/m/n}{}
1232 \%\\DeclareFontShape{LGR}{porson}{m}{sc} {<-> ssub * porson/m/n}{}
1233 \%\\DeclareFontShape{LGR}{porson}{bx}{n} {<-> ssub * porson/m/n}{}
1234 \%\\DeclareFontShape{LGR}{porson}{bx}{it}{<-> ssub * porson/m/n}{}
1235 \%\\DeclareFontShape{LGR}{porson}{bx}{sl}{<-> ssub * porson/m/n}{}
1236 % \fi
1237 }
1238 \\ifsuftesi@nofont
1239   \\ifsuftesi@greekfont
1240     \\ClassError{suftesi}
1241       {'greekfont' option\MessageBreak
1242         You can not use 'greekfont' option\MessageBreak
1243         with 'defaultfont=none' option\MessageBreak
1244         Set 'greekfont=none' or do not load\MessageBreak
1245         the 'greekfont' option}
1246       {'greekfont' option\MessageBreak
1247         You can not use 'greekfont' option\MessageBreak
1248         with 'defaultfont=none' option\MessageBreak
1249         Set 'greekfont=none' or do not load\MessageBreak
1250         the 'greekfont' option}
1251     \\else
1252   \\fi
1253 \\else
1254 \\fi
1255
1256 \\ifxetex\\else
1257   \\ifsuftesi@greekfont
1258     \\ifsuftesi@cbgreek
1259   \\else
1260   \\DeclareFontFamily{LGR}{bodoni}{}
1261   \\DeclareFontShape{LGR}{bodoni}{m}{n}{<-> s * [\SUFfntscale] gbodonirg6a}{}
1262   \\DeclareFontShape{LGR}{bodoni}{m}{it}{<-> s * [\SUFfntscale] gbodonii6a}{}
1263   \\DeclareFontShape{LGR}{bodoni}{b}{n}{<-> s * [\SUFfntscale] gbodonib6a}{}
1264   \\DeclareFontShape{LGR}{bodoni}{b}{it}{<-> s * [\SUFfntscale] gbodonibi6a}{}
1265   \\DeclareFontShape{LGR}{bodoni}{m}{sl}{<-> s * [\SUFfntscale] gbodonio6a}{}
1266   \\DeclareFontShape{LGR}{bodoni}{b}{sl}{<-> s * [\SUFfntscale] gbodonibo6a}{}
1267   \\DeclareFontShape{LGR}{bodoni}{m}{sc}{<-> s * [\SUFfntscale] gbodonisc6a}{}
1268   \\DeclareFontShape{LGR}{bodoni}{m}{sco}{<-> s * [\SUFfntscale] gbodonisco6a}{}
1269
1270   \\DeclareFontShape{LGR}{bodoni}{bx}{n}{<-> s * [\SUFfntscale] gbodonib6a}{}
1271   \\DeclareFontShape{LGR}{bodoni}{bx}{it}{<-> s * [\SUFfntscale] gbodonibi6a}{}
1272   \\DeclareFontShape{LGR}{bodoni}{bx}{sl}{<-> s * [\SUFfntscale] gbodonibo6a}{}
1273
1274 \\DeclareFontFamily{LGR}{artemisia}{}
1275 \\DeclareFontShape{LGR}{artemisia}{m}{n}{<-> s * [\SUFfntscale] gartemisiarg6a}{}

```

```

1276 \DeclareFontShape{LGR}{artemisia}{m}{it}{<-> s * [\SUFfnts] gartemisiai6a}{}
1277 \DeclareFontShape{LGR}{artemisia}{b}{n}{<-> s * [\SUFfnts] gartemisiab6a}{}
1278 \DeclareFontShape{LGR}{artemisia}{b}{it}{<-> s * [\SUFfnts] gartemisiabi6a}{}
1279 \DeclareFontShape{LGR}{artemisia}{m}{sl}{<-> s * [\SUFfnts] gartemisiao6a}{}
1280 \DeclareFontShape{LGR}{artemisia}{b}{sl}{<-> s * [\SUFfnts] gartemisiabo6a}{}
1281 \DeclareFontShape{LGR}{artemisia}{m}{sc}{<-> s * [\SUFfnts] gartemisisc6a}{}
1282 \DeclareFontShape{LGR}{artemisia}{m}{sco}{<-> s * [\SUFfnts] gartemisisasco6a}{}
1283
1284 \DeclareFontShape{LGR}{artemisia}{bx}{n}{<-> s * [\SUFfnts] gartemisiab6a}{}
1285 \DeclareFontShape{LGR}{artemisia}{bx}{it}{<-> s * [\SUFfnts] gartemisiabi6a}{}
1286 \DeclareFontShape{LGR}{artemisia}{bx}{sl}{<-> s * [\SUFfnts] gartemisiabo6a}{}
1287
1288 \DeclareFontFamily{LGR}{porson}{}}
1289 \DeclareFontShape{LGR}{porson}{m}{n}{<-> s * [\SUFfnts] gporsonrg6a}{}
1290 \DeclareFontShape{LGR}{porson}{m}{it}{<-> s * [\SUFfnts] gporsonrg6a}{}
1291 \DeclareFontShape{LGR}{porson}{b}{n}{<-> s * [\SUFfnts] gporsonrg6a}{}
1292 \DeclareFontShape{LGR}{porson}{b}{it}{<-> s * [\SUFfnts] gporsonrg6a}{}
1293 \DeclareFontShape{LGR}{porson}{m}{sl}{<-> s * [\SUFfnts] gporsonrg6a}{}
1294 \DeclareFontShape{LGR}{porson}{b}{sl}{<-> s * [\SUFfnts] gporsonrg6a}{}
1295 \DeclareFontShape{LGR}{porson}{m}{sc}{<-> s * [\SUFfnts] gporsonrg6a}{}
1296
1297 \DeclareFontShape{LGR}{porson}{bx}{n}{<-> s * [\SUFfnts] gporsonrg6a}{}
1298 \DeclareFontShape{LGR}{porson}{bx}{it}{<-> s * [\SUFfnts] gporsonrg6a}{}
1299 \DeclareFontShape{LGR}{porson}{bx}{sl}{<-> s * [\SUFfnts] gporsonrg6a}{}
1300 \fi
1301 \else
1302   \fi
1303 \fi

```

Page layout

```

1304 \ifsuftesi@nocrop
1305   \relax
1306   \else
1307     \RequirePackage[a4,cam,center]{crop}
1308 \fi

```

A trick to produce one-side documents:

```

1309 \ifsuftesi@screen
1310   \geometry{hmarginratio=1:1}
1311 \else
1312 \fi

```

Section titles

```

1313 \RequirePackage{titlesec}
1314   \newlength{\sectionsep}
1315   \setlength{\sectionsep}{\dimexpr(\baselineskip) plus 1pt minus 1pt}
1316 \ifthenelse{\boolean{xetex}\or\boolean{luatex}}
1317   {%
1318     \ DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1319       \addfontfeature{LetterSpace=6}\scshape\suftesi@MakeTextLowercase{#1}}%

```

```

1320 \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1321   \addfontfeature{LetterSpace=6}\scshape\suftesi@MakeTextLowercase{#1}%
1322   \newcommand{\chapnumfont}[1]{%
1323     \def\SUF@chapnumfont{#1}%
1324     \chapnumfont{\relax}%
1325   }%
1326   {%
1327     \if pdftex
1328       \DeclareRobustCommand{\SUF@titlesmallcaps}[1]{%
1329         \scshape\suftesi@MakeTextLowercase{\lsstyle #1}}%
1330       \DeclareRobustCommand{\SUF@headingsmallcaps}[1]{%
1331         \scshape\suftesi@MakeTextLowercase{\lsstyle #1}}%
1332       \newcommand{\chapnumfont}[1]{%
1333         \def\SUF@chapnumfont{\fontfamily{#1}}%
1334         \chapnumfont{pplj}%
1335       }%
1336       The chapter for elements style:
1337       \define@key[SUF]{elements}{chapsize}[90]{%
1338         \def\cmdSUF@elements@chapsize{\fontsize{#1}{#1}\selectfont}%
1339       }%
1340       \define@key[SUF]{elements}{chapposition}[-83]{%
1341         \def\cmdSUF@elements@chapposition{#1}%
1342       }%
1343       \def\SUF@elements@CHAPTER{%
1344         \titleformat{\chapter}[block]
1345           {\Large}%
1346           {\begin{picture}(0,0)
1347             \setlength{\unitlength}{1pt}
1348             \SUF@chapnumfont%
1349             \cmdSUF@elements@chapsize
1350             \put(0,\cmdSUF@elements@chapposition){%
1351               \hspace*{\dimexpr(\textwidth+0.9\marginparsep)}%
1352               \textcolor{sufgray}{\SUF@thechapter}}%
1353             \end{picture}}%
1354           {0pt}
1355           {\SUF@titlesmallcaps}
1356           [\vspace*{-6pt}\rule{\textwidth}{.1pt}]
1357       }%
1358       The sections for elements style:
1359       \def\SUF@elements@SECTIONS{%
1360         \titleformat{\section}[block]
1361           {\extramarks{}{}\filright}
1362           {\textnormal\thesection}
1363           {1em}
1364           {\SUF@titlesmallcaps}
1365           \titlespacing*{\section}{0em}{1em}{1em}[0em]
1366         \titleformat{\subsection}[block]
1367           {\filright\normalsize\itshape}
1368           {\textnormal\thesubsection}
1369           {1em}
1370           {}%
1371           \titlespacing*{\subsection}{0em}{\baselineskip}{\baselineskip}[0em]

```

```

1367 \titleformat{\subsubsection}[block]
1368   {\filright\normalsize}
1369   {\textnormal\thesubsubsection}
1370   {1em}
1371   {}
1372 \titlespacing*{\subsubsection}{0em}{\baselineskip}{\baselineskip}[0em]
1373 }

  Default styles:
1374 \newlength\SUF@ADJnumparchap
1375 \def\SUF@default@CHAPTER{
1376 \ifsuftesi@numparchap
1377   \titleformat{\chapter}[display]
1378   {\SUF@chaptersize\SUF@lr@CHAPSwitch}
1379   {\SUF@thechapter\SUF@dotchap}
1380   {2ex}
1381   {\SUF@CHAP@StyleSwitch}
1382 \else
1383   \titleformat{\chapter}[hang]
1384   {\SUF@chaptersize\SUF@lr@CHAPSwitch}
1385   {\SUF@thechapter\SUF@dotchap}
1386   {3em}
1387   {\SUF@CHAP@StyleSwitch}
1388 \fi
1389 \ifsuftesi@numparchap
1390   \setlength{\SUF@ADJnumparchap}{-2.5\baselineskip}
1391   \else
1392   \setlength{\SUF@ADJnumparchap}{0pt}
1393 \fi}

1394 \def\SUF@default@SECTIONS{
1395 \ifsuftesi@numparsec
1396 \titleformat{\section}[display]
1397   {\SUF@lr@SECSwitch}
1398   {\ifsuftesi@article\SUF@thesection
1399     \else\thesection\fi\SUF@dotsec}
1400   {0ex}
1401   {\SUF@SEC@StyleSwitch}
1402 \titlespacing*{\section}{0em}{\sectionsep}{\sectionsep}[0em]
1403 \else
1404 \titleformat{\section}[hang]
1405   {\SUF@lr@SECSwitch}
1406   {\ifsuftesi@article\SUF@thesection
1407     \else\thesection\fi\SUF@dotsec}
1408   {1em}
1409   {\SUF@SEC@StyleSwitch}
1410 \titlespacing*{\section}{0ex}{\sectionsep}{\sectionsep}[0ex]
1411 \fi

1412 \ifsuftesi@numparsubsec
1413 \titleformat{\subsection}[display]
1414   {\SUF@lr@SUBSECSwitch}

```

```

1415  {\textnormal\thesubsection}
1416  {0ex}
1417  {\SUF@SUBSEC@StyleSwitch}
1418 \titlespacing*{\subsection}{0em}{\sectionsep}{\sectionsep}[0em]
1419 \else
1420 \titleformat{\subsection}[hang]
1421  {\SUF@lr@SUBSECSwitch}
1422  {\textnormal\thesubsection}
1423  {1em}
1424  {\SUF@SUBSEC@StyleSwitch}
1425 \titlespacing*{\subsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1426 \fi
1427 \ifsuftesi@numparsubsubsec
1428 \titleformat{\subsubsection}[display]
1429  {\SUF@lr@SUBSUBSECSwitch}
1430  {\textnormal\thesubsubsection}
1431  {0ex}
1432  {\SUF@SUBSUBSEC@StyleSwitch}
1433 \titlespacing*{\subsubsection}{0em}{\sectionsep}{\sectionsep}[0em]
1434 \else
1435 \titleformat{\subsubsection}[hang]
1436  {\SUF@lr@SUBSUBSECSwitch}
1437  {\textnormal\thesubsubsection}
1438  {1em}
1439  {\SUF@SUBSUBSEC@StyleSwitch}
1440 \titlespacing*{\subsubsection}{\parindent}{\sectionsep}{\sectionsep}[0ex]
1441 \fi
1442 }
1443 \ifsuftesi@elementschap
1444 \RequirePackage{extramarks}
1445  \SUF@elements@CHAPTER
1446  \SUF@elements@SECTIONS
1447 \ifsuftesi@periodical
1448  \titlespacing*{\chapter}{0em}{-\baselineskip}{10pt}[0pt]
1449    \setkeys[SUF]{elements}{chapsize=80,chapposition=-83}
1450 \else
1451 \ifsuftesi@periodicalaureo
1452  \titlespacing*{\chapter}{0em}{-\baselineskip}{10pt}[0pt]
1453    \setkeys[SUF]{elements}{chapsize=80,chapposition=-83}
1454 \else
1455 \ifsuftesi@compact
1456  \titlespacing*{\chapter}{0em}{-1\baselineskip}{10pt}[0pt]
1457    \setkeys[SUF]{elements}{chapsize=75,chapposition=-83}
1458 \else
1459 \ifsuftesi@compactaureo
1460  \titlespacing*{\chapter}{0em}{-1\baselineskip}{10pt}[0pt]
1461    \setkeys[SUF]{elements}{chapsize=75,chapposition=-83}
1462 \else
1463 \ifsuftesi@supercompact

```

```

1464 \titlespacing*\{chapter\}{0em}{-1\baselineskip}{10pt}[0pt]
1465   \setkeys[SUF]{elements}{chapsize=70,chapposition=-73}
1466 \else
1467 \ifsuftesi@supercompactaureo
1468 \titlespacing*\{chapter\}{0em}{-1\baselineskip}{10pt}[0pt]
1469   \setkeys[SUF]{elements}{chapsize=70,chapposition=-73}
1470 \else
1471 \ifsuftesi@elementspagelayout
1472 \titlespacing*\{chapter\}{0em}{-\baselineskip}{10pt}[0pt]
1473   \setkeys[SUF]{elements}{chapsize=60,chapposition=-73}
1474 \else
1475 \titlespacing*\{chapter\}{0em}{-\baselineskip}{10pt}[0pt]
1476   \setkeys[SUF]{elements}{chapsize=90,chapposition=-83}
1477     \fi
1478   \fi
1479     \fi
1480   \fi
1481   \fi
1482 \fi
1483 \fi
1484 \else
1485 \SUF@default@CHAPTER
1486 \SUF@default@SECTIONS
1487 \ifsuftesi@periodicalaureo
1488 \titlespacing*\{chapter\}{0em}{0\SUF@ADJnumparchap}{18ex}
1489 \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1490 \else
1491 \ifsuftesi@periodical
1492 \titlespacing*\{chapter\}{0em}{\SUF@ADJnumparchap}{18ex}
1493 \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1494 \else
1495 \ifsuftesi@compact
1496   \titlespacing*\{chapter\}{0em}{\SUF@ADJnumparchap}{18ex}
1497   \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1498 \else
1499   \ifsuftesi@supercompact
1500     \titlespacing*\{chapter\}{0em}{\SUF@ADJnumparchap}{18ex}
1501     \titlespacing*\{name=\chapter, numberless\}{0em}{0pt}{18ex}
1502 \else
1503   \titlespacing*\{chapter\}{0em}{%
1504     \dimexpr(6ex+\SUF@ADJnumparchap)}{18ex}
1505     \titlespacing*\{name=\chapter, numberless\}{0em}{6ex}{18ex}
1506   \fi
1507   \fi
1508 \fi
1509 \fi
1510 \fi

```

Redefinitions for ‘article’ mode

```
1511 \ifsuftesi@article
```

```

1512 \def\chapter{\ClassError{suftesi}
1513   {\noexpand\chapter level is undefined
1514     using 'structure=article'}
1515   {\noexpand\chapter level is undefined
1516     using 'structure=article'}}
1517 \setcounter{tocdepth}{3}
1518   \setcounter{secnumdepth}{3}
1519   \renewcommand\thesection{%
1520     \@arabic\c@section}
1521 \renewcommand\thesubsection{%
1522   \thesection.\@arabic\c@subsection}
1523 \renewcommand\thesubsubsection{%
1524   \thesubsection.\@arabic\c@subsubsection}
1525 \renewcommand\theparagraph{%
1526   \thesubsubsection.\@arabic\c@paragraph}
1527 \renewcommand\thesubparagraph{%
1528   \theparagraph.\@arabic\c@subparagraph}

The partpage options allows you to print a standard part page in article mode.

1529 \ifsuftesi@partpage
1530   \relax
1531   \else

```

In article mode the \part command is similar to a \section but with more vertical space before and after.

```

1532 \titleclass{\part}{straight}
1533 \titlespacing*{\part}{0ex}{2\sectionsep}{2\sectionsep}[0ex]
1534 \fi
1535 \ifsuftesi@numparpart
1536 \titleformat{\part}[display]
1537   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1538   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1539   {2ex}
1540   {\SUF@PART@StyleSwitch}
1541 \else
1542 \titleformat{\part}[hang]
1543   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1544   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1545   {1em}
1546   {\SUF@PART@StyleSwitch}
1547 \fi
1548 \else

```

The default ‘book’ mode

```

1549 \ifsuftesi@numparpart
1550 \titleformat{\part}[display]
1551   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1552   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1553   {2ex}
1554   {\SUF@PART@StyleSwitch}
1555 \else

```

```

1556 \titleformat{\part}[hang]
1557   {\SUF@chaptersize\SUF@lr@PARTSwitch}
1558   {\SUF@PART@StyleSwitch\partname\hskip.5em\SUF@thepart\SUF@dotpart}
1559   {1em}
1560   {\SUF@PART@StyleSwitch}
1561 \fi
1562 \fi
1563
1564 \titleformat{\paragraph}[runin]
1565   {}
1566   {\theparagraph}
1567   {.5em}
1568   {\itshape}
1569   [{.}\hspace*{1em}]
1570 \titlespacing*{\paragraph}{\parindent}{.5\sectionsep}{.5\sectionsep}
1571 \titleformat{\subparagraph}[runin]
1572   {}
1573   {\thesubparagraph}
1574   {.5em}
1575   {}
1576   [{.}\hspace*{1em}]
1577 \titlespacing*{\subparagraph}{\parindent}{.5\sectionsep}{.5\sectionsep}

The biblatex package uses the book class definitions of bibliography and list of shorthands, so we must redefine them according to the styles of suftesi, which does not use uppercase letters in the headings.

1578 \ifsuftesi@article
1579 \AtBeginDocument{%
1580 \@ifpackageloaded{biblatex}{%
1581   \defbibheading{bibliography}[\refname]{%
1582     \section*{\#1}%
1583     \markboth{\#1}{\#1}%
1584   }%
1585   \defbibheading{shorthands}[\losname]{%
1586     \section*{\#1}%
1587     \markboth{\#1}{\#1}%
1588   }%
1589   \defbibheading{bibintoc}[\refname]{%
1590     \addcontentsline{toc}{section}{\#1}%
1591     \markboth{\#1}{\#1}%
1592   }%
1593   \defbibheading{losintoc}[\losname]{%
1594     \addcontentsline{toc}{section}{\#1}%
1595     \markboth{\#1}{\#1}%
1596   }%
1597   \defbibheading{bibnumbered}[\refname]{%
1598     \if@twoside\markright{\#1}\fi%
1599   }%
1600   \defbibheading{losnumbered}[\losname]{%
1601     \section*{\#1}%
1602     \if@twoside\markright{\#1}\fi%
1603   }%
1604   \defbibheading{subbibliography}[\refname]{%
1605     \if@twoside\markright{\#1}\fi%
1606   }%
1607 }
```

```

1602     \subsection*{\#1}}
1603     \defbibheading{subbibintoc}[\refname]{%
1604         \subsection*{\#1}%
1605         \addcontentsline{toc}{subsection}{\#1}%
1606     \defbibheading{subbibnumbered}[\refname]{%
1607         \subsection{\#1}}%
1608         {\relax}%
1609     }%
1610 \else
1611 \AtBeginDocument{%
1612 \@ifpackageloaded{biblatex}{%
1613     \defbibheading{bibliography}[\bibname]{%
1614         \chapter*{\#1}%
1615         \markboth{\#1}{\#1}%
1616     \defbibheading{shorthands}[\losname]{%
1617         \chapter*{\#1}%
1618         \markboth{\#1}{\#1}%
1619     \defbibheading{bibintoc}[\bibname]{%
1620         \chapter*{\#1}%
1621         \addcontentsline{toc}{chapter}{\#1}%
1622         \markboth{\#1}{\#1}%
1623     \defbibheading{losintoc}[\losname]{%
1624         \chapter*{\#1}%
1625         \addcontentsline{toc}{chapter}{\#1}%
1626         \markboth{\#1}{\#1}%
1627     \defbibheading{bibnumbered}[\bibname]{%
1628         \chapter{\#1}%
1629         \if@twoside\markright{\#1}\fi}%
1630     \defbibheading{losnumbered}[\losname]{%
1631         \chapter{\#1}%
1632         \if@twoside\markright{\#1}\fi}%
1633     \defbibheading{subbibliography}[\refname]{%
1634         \section*{\#1}%
1635         \if@twoside\markright{\#1}\fi}%
1636     \defbibheading{subbibintoc}[\refname]{%
1637         \section*{\#1}%
1638         \addcontentsline{toc}{section}{\#1}%
1639         \if@twoside\markright{\#1}\fi}%
1640     \defbibheading{subbibnumbered}[\refname]{%
1641         \section{\#1}}%
1642         {\relax}%
1643     }%
1644 \fi

```

Title page

The new `\title` command has an optional argument which can be used in the headers.

```

1645 \def\isbn#1{\gdef\@isbn{\#1}}
1646   \def\@issn{\@latex@warning@no@line{%
1647     No \noexpand\isbn given}}

```

```

1648 \def\doi#1{\gdef\@doi{#1}}
1649   \def\@doi{\@latex@warning@no@line{%
1650     No \noexpand\doi given}}
1651 \def\isbn#1{\gdef\@issn{#1}}
1652   \def\@issn{\@latex@warning@no@line{%
1653     No \noexpand\isbn given}}
1654
1655 \renewcommand*{\title}[2][]{\gdef\@headtitle{\#1}\gdef\@title{\#2}}
1656   \edef\title{\noexpand\@dblarg
1657   \expandafter\noexpand\csname\string\title\endcsname}
1658   \def\@headtitle{--missing title--%
1659     \protect\ClassWarningNoLine{suftesi}{%
1660       No \string\title\space given \MessageBreak%
1661       See the class documentation for explanation}}
1662   \def\@title{--missing title--%
1663     \protect\ClassWarningNoLine{suftesi}{%
1664       No \string\title\space given\MessageBreak%
1665       See the class documentation for explanation}}
1666   \def\@author{--missing author--%
1667     \protect\ClassWarningNoLine{suftesi}{%
1668       No \string\author\space given\MessageBreak%
1669       See the class documentation for explanation}}
1670   For titlepage (default) option:
1671 \if@titlepage% titlepage
1672   \renewcommand\maketitle{\begin{titlepage}%
1673   \let\footnotesize\small
1674   \let\footnoterule\relax
1675   \let \footnote \thanks
1676   \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1677   \null\vfil
1678   \vskip 60\p@
1679   \begin{center}%
1680     {\SUF@chaptersize\color{sufred}\sffamily%
1681     \ifsuftesi@smallcapschap%
1682       \SUF@titlesmallcaps{\@title}%
1683     \else
1684       \ifsuftesi@article
1685         \SUF@titlesmallcapssec%
1686       \else
1687         \@title
1688       \fi
1689     \else
1690       \@title
1691     \fi
1692   \fi\par}%
1693   \vskip 3em%
1694   {\small\lineskip .75em%
1695   \begin{tabular}[t]{c}}
```

```

1696      \@author
1697      \end{tabular}\par}%
1698      \vskip 1.5em%
1699      {\small \@date\par}%
1700  \end{center}\par
1701  \@thanks
1702  \vfil\null
1703  \end{titlepage}%
1704  \setcounter{footnote}{0}%
1705  \global\let\thanks\relax
1706  \global\let\maketitle\relax
1707  \global\let\@thanks\empty
1708    \global\let\@date\empty
1709  \global\let\date\relax
1710  \global\let\and\relax}

Reproduces the standard \maketitle style:
1711 \newcommand\standardtitle{\begin{titlepage}%
1712   \let\footnotesize\small
1713   \let\footnoterule\relax
1714   \let \footnote \thanks
1715   \null\vfil
1716   \vskip 60\p@
1717   \begin{center}%
1718     {\LARGE \@title \par}%
1719     \vskip 3em%
1720     {\large
1721       \lineskip .75em%
1722       \begin{tabular}[t]{c}%
1723         \@author
1724       \end{tabular}\par}%
1725     \vskip 1.5em%
1726     {\large \@date \par}%
1727   \end{center}\par
1728   \@thanks
1729   \vfil\null
1730   \end{titlepage}%
1731   \setcounter{footnote}{0}%
1732   \global\let\thanks\relax
1733   \global\let\maketitle\relax
1734   \global\let\@thanks\empty
1735   \global\let\@date\empty
1736   \global\let\date\relax
1737   \global\let\and\relax}
1738 \else

For notitlepage option:
1739 \renewcommand\maketitle{\par
1740   \begingroup
1741     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1742     \def\@makefnmark{\rlap{\textsuperscript{\normalfont\@thefnmark}}}%

```

```

1743 \long\def\@makefntext##1{\parindent 1em\noindent
1744     \hb@xt@1.8em{%
1745         \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
1746 \if@twocolumn
1747     \ifnum \col@number=\@ne
1748         \@maketitle
1749     \else
1750         \twocolumn[\@maketitle]%
1751     \fi
1752 \else
1753     \newpage
1754     \global\@topnum\z@% Prevents figures from going at top of page.
1755     \@maketitle
1756     \fi
1757     \thispagestyle{plain}\@thanks
1758 \endgroup
1759 \setcounter{footnote}{0}%
1760 \global\let\thanks\relax
1761 \global\let\maketitle\relax
1762 \global\let\@maketitle\relax
1763 \global\let\@thanks\@empty
1764 \global\let\@date\@empty
1765 \global\let\date\relax
1766 \global\let\and\relax
1767     \def\@maketitle{%
1768     \newpage
1769     \null
1770     \vskip 2em%
1771     \begin{center}%
1772     \let \footnote \thanks
1773         {\SUF@chaptersize\color{sufred}\sffamily%
1774 \ifsuftesi@smallcapschap%
1775         \SUF@titlesmallcaps{\@title}%
1776     \else
1777         \ifsuftesi@article
1778             \ifsuftesi@smallcapssec
1779                 \SUF@titlesmallcaps{\@title}%
1780             \else
1781                 \@title
1782             \fi
1783         \else
1784             \@title
1785         \fi
1786     \fi\par}%
1787     \vskip 1.5em%
1788     {\small\lineskip .5em%
1789         \begin{tabular}[t]{c}%
1790             \author\par
1791         \end{tabular}\par}%
1792     \vskip 1em%

```

```

1793      {\small\@date\par}%
1794      \end{center}%
1795      \par
1796      \vskip 1.5em}
      Reproduces the standard \maketitle style:
1797 \newcommand\standardtitle{\par
1798   \begingroup
1799     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1800     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
1801     \long\def\@makefntext##1{\parindent 1em\noindent
1802       \hb@xt@1.8em{%
1803         \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
1804       \if@twocolumn
1805         \ifnum \col@number=\@ne
1806           \@standardmaketitle
1807         \else
1808           \twocolumn[\@standardmaketitle]%
1809         \fi
1810       \else
1811         \newpage
1812         \global\@topnum\z@
1813         \@standardmaketitle
1814       \fi
1815       \thispagestyle{plain}\@thanks
1816     \endgroup
1817     \setcounter{footnote}{0}%
1818     \global\let\thanks\relax
1819     \global\let\maketitle\relax
1820     \global\let\@standardmaketitle\relax
1821     \global\let\@thanks\empty
1822     \global\let\@date\empty
1823     \global\let\date\relax
1824     \global\let\and\relax
1825 \def\@standardmaketitle{%
1826   \newpage
1827   \null
1828   \vskip 2em%
1829   \begin{center}%
1830     \let \footnote \thanks
1831     {\LARGE \@title \par}%
1832     \vskip 1.5em%
1833     {\large
1834       \lineskip .5em%
1835       \begin{tabular}[t]{c}%
1836         \author
1837       \end{tabular}\par}%
1838     \vskip 1em%
1839     {\large \@date}%
1840   \end{center}%

```

```

1841   \par
1842   \vskip 1.5em}
1843 \fi

```

The collection document structure

```

1844 \ifsuftesi@collection
1845 \newcounter{journalnumber}
1846 \newcounter{journalvolume}
1847 \newcounter{issue}
1848 \newcounter{title}
1849 \setcounter{title}{1}
1850 \newcounter{article}
1851 \setcounter{article}{0}
1852 \setcounter{journalnumber}{0}
1853 \setcounter{tocdepth}{0}
1854 \def\journalname#1{\gdef\@journalname{#1}}
1855 \def\@journalname{\@latex@warning@no@line{%
1856     No \noexpand\journalname given}}
1857 \def\journalvolume#1{\gdef\@journalvolume{#1}}
1858 \def\@journalvolume{\@latex@warning@no@line{%
1859     No \noexpand\journalvolume given}}
1860 \def\journalnumber#1{\gdef\@journalnumber{#1}}
1861 \def\@journalnumber{\@latex@warning@no@line{%
1862     No \noexpand\journalnumber given}}
1863 \def\issue#1{\gdef\@issue{#1}}
1864 \def\@issue{\@latex@warning@no@line{%
1865     No \noexpand\issue given}}
1866 \def\journalyear#1{\gdef\@journalyear{#1}}
1867 \def\@journalyear{\@latex@warning@no@line{%
1868     No \noexpand\journalyear given}}
1869 \def\journalwebsite#1{\gdef\@journalwebsite{\url{#1}}}
1870 \def\@journalwebsite{\@latex@warning@no@line{%
1871     No \noexpand\journalwebsite given}}
1872 \def\thanks#1{\footnotemark\ \protected@xdef\@thanks{%
1873 \@thanks\protect\footnotetext[\the\c@footnote]{#1}}}
1874 \def\fulljournal{\emph{\@journalname} \@journalnumber, %
1875 \@issue{} \@journalyear}
1876 \def\issuename#1{\gdef\@issuename{#1}}
1877 \def\collectiontitle#1{\gdef\@collectiontitle{#1}}
1878 \def\@collectiontitle{\@latex@warning@no@line{%
1879     No \noexpand\collectiontitle given}}
1880 \def\collectioneditor#1{\gdef\@collectioneditor{#1}}
1881 \def\@collectioneditor{\@latex@warning@no@line{%
1882     No \noexpand\collectioneditor given}}
1883 \renewcommand*\title}[2][]{%
1884 \gdef\@headtitle{\gdef\@title{\#2}\markright{\#1}}
1885 \edef\@title{\noexpand\@dblarg
1886 \expandafter\noexpand\csname\string\title\endcsname}
1887 \def\@headtitle{--missing title--%

```

```

1888 \protect\ClassWarningNoLine{suftesi}{%
1889   No \string\title\space given \MessageBreak%
1890   See the class documentation for explanation}}
1891 \def\@title{--missing title--%
1892   \protect\ClassWarningNoLine{suftesi}{%
1893     No \string\title\space given\MessageBreak%
1894     See the class documentation for explanation}}
1895 \def\@author{--missing author--%
1896   \protect\ClassWarningNoLine{suftesi}{%
1897     No \string\author\space given\MessageBreak%
1898     See the class documentation for explanation}}
1899
1900 \newcommand*\l@title[2]{%
1901   \ifnum \c@tocdepth >\m@ne
1902     \addpenalty{-\@highpenalty}%
1903     \vskip 1.0ex \oplus \p@
1904     \begingroup
1905       \parindent \z@ \rightskip \pnumwidth
1906       \parfillskip -\pnumwidth
1907       \advance\leftskip\pem
1908       \hskip -\leftskip
1909       #1\nobreak%
1910     \ifsuftesi@dottedtoc\dotfill%
1911       \nobreak\hb@xt@\pnumwidth{\hss #2}\par
1912     \else
1913       \ifsuftesi@raggedtoc%
1914         \nobreak\hskip\pem #2 \hfill\null\par
1915       \else
1916         \ifsuftesi@pagelefttoc
1917           \ClassError{suftesi}{%
1918             {\MessageBreak
1919               You can not use tocstyle=leftpage\MessageBreak
1920               with structure=collection}
1921             {You can not use tocstyle=leftpage\MessageBreak
1922               with structure=collection}}
1923           \else
1924             \nobreak\hfill #2\par
1925           \fi
1926         \fi
1927       \fi
1928       \penalty\@highpenalty
1929     \endgroup
1930   \fi}
1931 \renewcommand\maketitle{\par
1932   \begingroup
1933     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
1934     \def\@makefnmark{\rlap{\textsuperscript{\normalfont\@thefnmark}}}%
1935     \long\def\@makefntext##1{\parindent 1em\noindent
1936       \hb@xt@1.8em{%

```

```

1937   \hss\@textsuperscript{\normalfont\@thefnmark}##1}%
1938   \if@twocolumn
1939     \ifnum \col@number=\@ne
1940       \maketitle
1941     \else
1942       \twocolumn[\maketitle]%
1943     \fi
1944   \else
1945     \newpage
1946     \global\@topnum\z@    % Prevents figures from going at top of page.
1947     \maketitle
1948   \fi
1949   \thispagestyle{plain}\@thanks%
1950 \endgroup
1951 % \setcounter{footnote}{0}%
1952 \setcounter{section}{0}%
1953 % \global\let\thanks\relax
1954 % \global\let\maketitle\relax
1955 % \global\let\@maketitle\relax
1956 % \global\let\@thanks\@empty
1957 % \global\let\@author\@empty
1958 % \global\let\@date\@empty
1959 % \global\let\@title\@empty
1960 % \global\let\title\relax
1961 % \global\let\author\relax
1962 % \global\let\date\relax
1963 \global\let\and\relax
1964 \let\thanks\@gobble}
1965 \AtBeginDocument{\def\@maketitle{%
1966   \refstepcounter{article}
1967   \SUF@chaptersize
1968   \SUF@lr@coll@titleSwitch
1969   \let\footnote\thanks
1970   \parindent=0pt
1971   {\ifsuftesi@reverseauthortitle
1972     \SUF@titlefont@Switch{\@title}%
1973     \else\SUF@authorfont@Switch{\@author}\fi}%
1974   \label{begin:\thearticle}
1975   \xdef\@currentHref{title.\thearticle}%
1976   \Hy@raisedlink{%
1977     \hyper@anchorstart{\@currentHref}\hyper@anchorend}%
1978   \csname toc@entry@\endcsname
1979   \begingroup%
1980   \let\thanks\@gobble
1981   \addcontentsline{toc}{title}{%
1982     \normalfont{\@author}\texorpdfstring{\newline}{, }%
1983     \itshape\@headtitle}%
1984   \endgroup%
1985   \par\nobreak\vspace{2ex}%
1986   {\ifsuftesi@reverseauthortitle

```

```

1987      \SUF@authorfont@Switch{@author}%
1988      \else
1989      \SUF@titlefont@Switch{@title}%
1990      \fi\vskip1.5cm}%
1991  }
1992 \%newenvironment{article}
1993 \% {\begingroup
1994 \% \global\let\@thanks\empty
1995 \% \setcounter{footnote}{0}
1996 \% \refstepcounter{article}
1997 \% \label{begin:\thearticle}
1998 \%}
1999 \% {\label{end:\thearticle}\endgroup
2000 \% }
2001 \newenvironment{article}
2002     {\begingroup
2003         \setcounter{section}{0}
2004         \setcounter{footnote}{0}
2005         \setcounter{figure}{0}
2006         \setcounter{table}{0}}
2007         {\label{end:\thearticle}
2008             \cleardoublepage
2009             \global\let\@thanks\empty
2010         }\endgroup}

```

A command to typeset the frontispiece of the collection.

```

2011 \newcommand{\frontispiece}{%
2012   \thispagestyle{empty}%
2013   \begingroup
2014   \centering
2015   \vspace*{\stretch{1}}
2016
2017   {\SUF@chaptersize@\collectiontitle\par}
2018   \vskip5ex
2019
2020   \collectioneditor
2021   \vspace*{\stretch{3}}
2022
2023 \endgroup
2024 \clearpage}

```

In the collection document structure the articles are treated as chapters but you would not need to print in the table of contents all the sections of every article. So first of all we include in the table of contents only the author and the title of each paper:

```

2025 \setcounter{tocdepth}{0}
2026 \renewcommand\thesection{%
2027   \@arabic\c@section}
2028 \renewcommand\thesubsection{%
2029   \thesection.\@arabic\c@subsection}
2030 \renewcommand\thesubsubsection{%
2031   \thesubsection.\@arabic\c@subsubsection}

```

```

2032 \renewcommand\theparagraph{%
2033     \thesubsubsection.\@arabic\c@paragraph}
2034 \renewcommand\thesubparagraph{%
2035     \theparagraph.\@arabic\c@subparagraph}
2036 \else
2037 \fi

```

Frontispiece

```

2038 \AtBeginDocument{%
2039 \ifpackagewith{frontespizio}{suftesi}
2040     {\ifsuftesi@periodical
2041         \Margini {5.5cm}{7cm}{4.5cm}{0cm}
2042     \else
2043     \ifsuftesi@compact
2044         \Margini {4.5cm}{7cm}{4.5cm}{0cm}
2045     \else
2046         \ifsuftesi@supercompact
2047             \Margini {4.5cm}{10cm}{6cm}{1cm}
2048         \else
2049             \ifsuftesi@periodicalaureo
2050                 \Margini {5.5cm}{7cm}{4.5cm}{0cm}
2051             \fi
2052         \fi
2053     \fi
2054 \fi}
2055 {\@ifpackageloaded{frontespizio}
2056     {\ifsuftesi@periodical
2057         \Margini {1cm}{7cm}{5cm}{1cm}
2058         \Rientro{1cm}
2059     \else
2060     \ifsuftesi@compact
2061         \Margini {1cm}{7cm}{6cm}{1cm}
2062         \Rientro{1cm}
2063     \else
2064         \ifsuftesi@supercompact
2065             \Margini {1cm}{10cm}{8cm}{1cm}
2066             \Rientro{1cm}
2067     \else
2068         \ifsuftesi@periodicalaureo
2069             \Margini {1cm}{7cm}{5cm}{1cm}
2070             \Rientro{1cm}
2071     \fi
2072     \fi
2073   \fi
2074 \fi}
2075 {\relax}}
2076 \renewenvironment{theindex}
2077     {\if@twocolumn
2078         \restonecolfalse

```

```

2079         \else
2080             \@restonecoltrue
2081         \fi
2082     \ifsoftesi@article
2083         \twocolumn[\section*{\indexname}]%
2084     \else
2085         \twocolumn[\@makeschapterhead{\indexname}]%
2086     \fi
2087     \mkboth{\indexname}{\indexname}%
2088     \thispagestyle{plain}%
2089     \raggedright%
2090     \parindent\z@
2091     \parskip\z@ \z@plus .3\p@\relax
2092     \columnseprule \z@
2093     \columnsep 35\p@
2094     \let\item@idxitem
2095     {\if@restonecol\onecolumn\else\clearpage\fi}

```

Appendix

```

2096 \newcommand{\appendicesname}[1]{\def\SUF@appendices{#1}}
2097     \appendicesname{Appendici}
2098     \newcommand{\appendixpage}{\SUF@appendixpage}
2099 \def\SUF@appendixpage{%
2100     \@mainmattertrue
2101     \titlecontents{part}
2102         [0em]
2103         {\addvspace{3ex}}
2104         {}
2105         {}
2106         {}
2107         [\addvspace{1ex}]
2108 \let\contentspage\relax
2109     \cleardoublepage
2110     \thispagestyle{empty}
2111     \addcontentsline{toc}{part}{\SUF@appendices}
2112     \begingroup
2113         \centering
2114         \null\vfil
2115         {\LARGE\SUF@appendices\par}
2116         \vfил
2117     \endgroup
2118     \cleardoublepage
2119 \titlecontents{part}
2120     [0em]
2121     {\addvspace{3ex}\partname~}
2122     {\makebox[\SUF@label@part][1]{%
2123         \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}
2124     {}
2125     {}
2126     [\addvspace{1ex}]

```

```

2127 }

2128 \ifsuftesi@sufelements
2129 \renewcommand\appendix{\par
2130   \setcounter{chapter}{0}%
2131   \setcounter{section}{0}%
2132   \gdef\@chapapp{\appendixname}%
2133   \gdef\thechapter{\@Alph\c@chapter}
2134   \titleformat{\chapter}[block]
2135     {\vskip-22pt}%
2136     {\small%
2137       \SUF@titlesmallcaps{\appendixname}\~\Alph{chapter}:\hskip.5em}%
2138     {0pt}%
2139     {\small\SUF@titlesmallcaps}%
2140     [\rule{\textwidth}{.4pt}]%
2141     \titlespacing*{\chapter}{0em}{-16pt}{10pt}[0em]%
2142 \else
2143   \ifsuftesi@article
2144     \renewcommand\appendix{\par
2145       \setcounter{section}{0}%
2146       \setcounter{subsection}{0}%
2147       \gdef\SUF@thesection{\@Alph\c@section}}%
2148 \else
2149   \renewcommand\appendix{\par
2150     \setcounter{chapter}{0}%
2151     \setcounter{section}{0}%
2152     \gdef\@chapapp{\appendixname}%
2153     \gdef\SUF@thechapter{\@Alph\c@chapter}}
2154 \fi
2155 \fi

```

Headings

```

2156 \RequirePackage{fancyhdr}
2157 \newcommand{\versionstring}[1]{\def\version@string{#1}}
2158   \versionstring{Version of}
2159 \AtBeginDocument{%
2160   \pagestyle{fancy}
2161   \renewcommand{\headrulewidth}{0pt}
2162   \renewcommand{\footnoterule}{}
2163 \def\SUF@versionstring{\texttt{\version@string} \today}}

```

The elements headers

```

2164 \ifsuftesi@elementsheader%
2165   \renewcommand{\chaptermark}[1]{\markboth{#1}{#1}}
2166   \renewcommand{\sectionmark}[1]{\markright{#1}}
2167 \fancypagestyle{elements}{%
2168   \setlength{\unitlength}{1pt}
2169   \fancyhf{}%
2170   \fancyfoot[LE,RO]{\thepage}
2171   \fancyhead[RO]{%
2172     \begin{picture}(0,0)

```

```

2173      \put(0,-104){%
2174      \hskip\marginparsep
2175      \parbox[t]{\marginparwidth}{\itshape\raggedright\leftmark}}%
2176      \end{picture}}
2177 \fancyhead[LE]{%
2178   \begin{picture}(0,0)
2179     \put(0,-104){%
2180       \hskip-\dimexpr(\marginparwidth+\marginparsep)
2181       \parbox[t]{\marginparwidth}{\itshape\raggedleft\rightmark}}%
2182   \end{picture}}%
2183 }%
2184 \else

```

The default headers

```

2185 \renewcommand{\chaptermark}[1]{%
2186   \markboth{\chaptertitlename\ \SUF@thechapter}{#1}}
2187 \ifsuftesi@article
2188   \renewcommand{\sectionmark}[1]{\markright{\SUF@thesection.\ #1}}
2189   \else
2190   \renewcommand{\sectionmark}[1]{}
2191 \fi
2192 \fi

```

The plain style

```
2193 \fancypagestyle{plain}{\fancyhf{}}
```

The sufplain style

```

2194 \fancypagestyle{sufplain}{%
2195   \fancyhf{}%
2196   \fancyfoot[RE,LO]{%
2197     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
2198   \fancyfoot[C]{\footnotesize\SUF@thepage}}

```

The centerheader style

```

2199 \fancypagestyle{centerheader}{%
2200   \fancyhf{}%
2201   \fancyfoot[RE,LO]{%
2202     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}
2203   \fancyhead[CO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
2204   \fancyhead[CE]{\footnotesize\xheadbreakfalse%
2205     \SUF@LR@MarkSwitch}
2206   \fancyfoot[C]{\footnotesize\SUF@thepage}%
2207 }%

```

The sufdefault style

```

2208 \fancypagestyle{sufdefault}{%
2209   \fancyhf{}%
2210   \fancyfoot[RE,LO]{%
2211     \ifsuftesi@draftdate\footnotesize\SUF@versionstring\else\fi}

```

```

2212 \fancyhead[LE,RO]{\footnotesize\SUF@thepage}
2213 \fancyhead[LO]{\footnotesize\xheadbreakfalse\SUF@rightmark}
2214 \fancyhead[RE]{\footnotesize\xheadbreakfalse%
2215 \SUF@LR@MarkSwitch}
2216 }%
2217 %
2218 \ifsuftesi@article
2219 \ifsuftesi@authortitle
2220 \def\SUF@LR@MarkSwitch{\SUF@leftmark}
2221 \else
2222 \def\SUF@LR@MarkSwitch{\SUF@rightmark}
2223 \fi
2224 \else
2225 \def\SUF@LR@MarkSwitch{\SUF@leftmark}
2226 \fi
2227 \def\SUF@leftrightmark{%
2228 \if@mainmatter\leftmark\else\rightmark\fi}

Setting the default page style:
2229 \pagestyle{sufdefault}
2230 \ifsuftesi@centerheader\pagestyle{centerheader}\else\fi
2231 \ifsuftesi@sufplain\pagestyle{sufplain}\else\fi
2232 \ifsuftesi@elementsheader\pagestyle{elements}\else\fi
2233 }

```

Text elements

Block Quotations New environments for block quotations according to a popular Italian style. The font size is the same of the footnotes and the margins are set to `\parindent`.

```

2234 \renewenvironment{quotation}
2235     {\list{}{\listparindent\parindent%
2236         \itemindent \listparindent
2237         \leftmargin \parindent
2238         \SUF@quote@style
2239         \parsep \z@ \oplus\p@}%
2240         \item\relax%
2241         \SUF@quotation@size%
2242         \noindent\ignorespaces}
2243     {\endlist}
2244 \renewenvironment{quote}
2245     {\list{}{\leftmargin \parindent
2246         \SUF@quote@style}%
2247         \item\relax%
2248         \SUF@quotation@size}\ignorespaces?
2249     {\endlist}
2250 \renewenvironment{verse}
2251     {\let\\@\centercr
2252         \list{}{\itemsep \z@
2253             \itemindent -1.5em%
2254             \listparindent\itemindent
2255             \rightmargin \leftmargin

```

```

2256           \advance\leftmargin 1.5em}%
2257           \item\relax
2258           \SUF@quotation@size}
2259           {\endlist}

```

The fewfootnotes option Enable only with three footnotes per page maximum.

```

2260 \ifsuftesi@fewfootnotes
2261 \AtBeginDocument{%
2262 \def\@fnsymbol{\ensuremath{\ifcase#1\or*\or{*\!\!}{*}\or{*\!\!}{*}\or{*\!\!}{*}\or%}
2263   \ClassError{suftesi}{%
2264     {Too many footnotes}\MessageBreak
2265     Remove the class option 'fewfootnote'}%
2266   {Too many footnotes}\MessageBreak
2267   Remove the class option 'fewfootnote'}%
2268   \else\@ctrerr{fi}}}}
2269 \def\thefootnote{\@fnsymbol\c@footnote}%
2270 \else\fi

```

Prints a footnote with discretionary symbol give in the first argument.

```

2271 \newcommand*\xfootnote[1][*]{%
2272   \xdef\@thefnmark{#1}%
2273   \footnotemark\footnotetext}

```

Marginal notes The `\marginpar` command is redefined according to the look of *Classic Thesis* by André Miede (2011).

```
2274 \def\SUF@mpsetup{%
```

In the *The Elements of Typographic Style* (with `elements` option) the marginal notes are printed in roman, but I prefer italic shape for the other options:

```

2275   \ifsuftesi@elementsheader\relax
2276     \else\itshape\fi
2277   \footnotesize%
2278   \parindent=0pt \lineskip=0pt \lineskiplimit=0pt %
2279   \tolerance=2000 \hyphenpenalty=300 \exhyphenpenalty=300%
2280   \doublehyphendemerits=100000%
2281   \finalhyphendemerits=\doublehyphendemerits}
2282   \let\oldmarginpar\marginpar
2283   \renewcommand{\marginpar}[1]{\oldmarginpar%
2284     [\SUF@mpsetup\raggedleft\hspace{0pt}{#1}]%
2285     [\SUF@mpsetup\raggedright\hspace{0pt}{#1}]}

```

Redefine an internal command of the `todonotes` package in order to use the class-specific marginal notes when this package is loaded. This redefinition simply substitute `\oldmarginpar` to `\marginpar`:

```

2286 \AtBeginDocument{%
2287 \@ifpackageloaded{todonotes}{%
2288 \renewcommand{\todonotes@drawMarginNoteWithLine}{%
2289 \begin{tikzpicture}[remember picture, overlay, baseline=-0.75ex]%
2290   \node [coordinate] (inText) {};%
2291 \end{tikzpicture}%
2292 \oldmarginpar[% Draw note in left margin
2293   \todonotes@drawMarginNote%}

```

```

2294      \@todonotes@drawLineToLeftMargin%
2295  }]{% Draw note in right margin
2296      \@todonotes@drawMarginNote%
2297      \@todonotes@drawLineToRightMargin%
2298 }%
2299 }%
2300 }
2301 {\relax}

```

Abstract

```

2302 \ifsuftesi@collection
2303   \newenvironment{abstract}{%
2304     \if@twocolumn
2305       \section*{\abstractname}%
2306     \else
2307       \small
2308       \begin{center}%
2309         {\abstractname\vspace{-.5em}\vspace{\z@}}%
2310       \end{center}%
2311       \quotation
2312     \fi
2313     {\if@twocolumn\else\endquotation\fi\vspace{6ex}}}
2314 \else
2315 \if@titlepage
2316   \newenvironment{abstract}{%
2317     \titlepage
2318     \null\vfil
2319     \begin{parpenalty}{\lowpenalty}
2320       \begin{center}%
2321         \abstractname
2322         \endparpenalty{0M}
2323       \end{center}%
2324     \par\vfil\null\endtitlepage}
2325 \else
2326   \newenvironment{abstract}{%
2327     \if@twocolumn
2328       \section*{\abstractname}%
2329     \else
2330       \small
2331       \begin{center}%
2332         {\abstractname\vspace{-.5em}\vspace{\z@}}%
2333       \end{center}%
2334       \quotation
2335     \fi
2336     {\if@twocolumn\else\endquotation\fi}
2337 \fi
2338 \fi
2339 \newcommand{\abstractname}{Abstract}

```

Colophon or copyright notice

```
2340 \newcommand{\colophon}[3] [] {%
2341   \thispagestyle{empty}
2342   \null
2343   \vfill
2344   \def\next{\#2}
2345   \ifx\next\@empty\else
2346     \noindent Copyright \copyright[] \the\year~#2\lex
2347     Tutti i diritti riservati
2348   \fi
2349   \vfill
2350   {\small\noindent Questo lavoro \`e stato composto con \LaTeX{}%
2351   \def\next{\#1}
2352   \ifx\next\@empty\else su #1
2353   \fi usando la classe \textsf{suftesi} di
2354   Ivan Valbusa\index{Valbusa, Ivan}. #3\par}
2355   \cleardoublepage}

2356 \newcommand{\bookcolophon}[2] {%
2357   \thispagestyle{empty}
2358   \null
2359   \vfill
2360   \noindent #1
2361   \vfill
2362   {\small\noindent #2\par}
2363   \cleardoublepage}

2364 \newcommand{\artcolophon}[1] {%
2365 \thispagestyle{empty}
2366 \null
2367 \vfill
2368 {\small\noindent #1\par}}

2369 \newcommand{\finalcolophon}[1] {%
2370 \thispagestyle{empty}
2371 \null\vspace*{\stretch{1}}
2372 \begin{center}
2373 \begin{minipage}{.5\textwidth}
2374 \centering\small #1
2375 \end{minipage}
2376 \end{center}
2377 \vspace*{\stretch{6}}}
```

The \FSPL colophon This command is defined only for the `style=FSPL*` options.

```
2378 \ifsuftesi@FSPL
2379 \newcommand{\FSPLcolophon}[1] [\the\year]{%
2380 \begingroup
2381 \thispagestyle{empty}
2382 \null\vspace{\stretch{1}}
2383 \noindent \hspace{-0.5em}\cc #1 \author%
2384 \vskip1ex
```

```

2385
2386 \small\noindent This work is licensed under the Creative Commons
2387 Attribution-NonCommercial-NoDerivs 3.0 Unported License.
2388 To view a copy of this license,
2389 visit http://creativecommons.org/licenses/by-nc-nd/3.0/.
2390
2391 \endgroup
2392
2393 \begingroup
2394 \footnotesize
2395
2396 \null\vspace{\stretch{1}}
2397
2398 \noindent Typeset with \LaTeX{} in collaboration with the Joint Project
2399 \emph{Formal Style for PhD Theses with \LaTeX{}} (University of Verona,
2400 Italy) using the \textsf{suftesi} class by Ivan Valbusa. The text face
2401 is Palatino, designed by Hermann Zapf. The sans serif font is Iwona by
2402 Janusz M. Nowacki.
2403
2404 \endgroup
2405
2406 \clearpage
2407 \else
2408 \def\FSPLcolophon{%
2409   \ClassError{suftesi}{%
2410     \noexpand\FSPLcolophon is defined\MessageBreak
2411     only for the FSPL styles}%
2412   \noexpand\FSPLcolophon is defined\MessageBreak
2413   only for the FSPL styles}%
2414 \fi

```

Toc, lof, lot

```

2415 \RequirePackage{titletoc}
All the lengths depend on \SUF@label@chap so we define this first.
2416 \newlength\SUF@label@chap
2417 \setlength\SUF@label@chap{.5em}
\toclabelwidth is provided to adjust the label width in the table of contents:
2418 \newcommand*\toclabelwidth[2]{%
2419   \AtBeginDocument{%
2420     \addtolength{\csname SUF@label@#1\endcsname}{#2}%
2421     \addtolength{\csname SUF@tocindent@#1\endcsname}{#2}%
2422   }%
2423 }
2424 \newcommand{\toclabelspace}{%
2425   \ClassError{suftesi}{%
2426     \MessageBreak
2427     \noexpand\toclabelspace is not more defined\MessageBreak
2428     Use \noexpand\toclabelwidth instead.\MessageBreak
2429     See package documentation for details}%

```

```

2430      {\MessageBreak
2431      \noexpand\toclabelspace is not more defined\MessageBreak
2432      Use \noexpand\toclabelwidth instead.\MessageBreak
2433      See package documentation for details}}
This macro controls the space between page number and chapter label using the tocpageleft option:
2434 \newlength{\SUF@tochang}
2435 \setlength{\SUF@tochang}{3em}
2436 \AtBeginDocument{
2437 \newlength\SUF@label@part
2438 \newlength\SUF@label@sec
2439 \newlength\SUF@label@subsec
2440 \newlength\SUF@label@subsubsec
2441 \newlength\SUF@label@par
2442 \newlength\SUF@label@subpar
2443 \newlength\SUF@label@fig
2444 \newlength\SUF@label@tab
2445 \setlength\SUF@label@part
2446     {\SUF@label@chap}
2447 \setlength\SUF@label@sec
2448     {\dimexpr(\SUF@label@chap+.5em)}
2449 \setlength\SUF@label@subsec
2450     {\dimexpr(\SUF@label@sec+.5em)}
2451 \setlength\SUF@label@subsubsec
2452     {\dimexpr(\SUF@label@subsec+.5em)}
2453 \setlength\SUF@label@par
2454     {\dimexpr(\SUF@label@subsubsec+.5em)}
2455 \setlength\SUF@label@subpar
2456     {\dimexpr(\SUF@label@par+.5em)}
2457 \setlength\SUF@label@fig
2458     {\SUF@label@sec}
2459 \setlength\SUF@label@tab
2460     {\SUF@label@sec}
2461 }

Part in article mode
2462 \titlecontents{part}
2463 [0em]
2464     {\addvspace{3ex}\partname\hspace*{.5em}}
2465     {\makebox[\SUF@label@part][l]{%
2466         \SUF@toclabelnum\thecontentslabel}\hspace*{1em}}
2467     {}
2468     {}
2469     [\addvspace{1ex}]
‘tocpageleft’ toc
2470 \ifsuftesi@pagelefttoc
First we reset the right margin to zero:
2471 \contentsmargin{0pt}
2472 \AtBeginDocument{
2473 \newlength\SUF@tochang@chap

```

```

2474 \newlength{\SUF@tochang@sec}
2475 \newlength{\SUF@tochang@subsec}
2476 \newlength{\SUF@tochang@subsubsec}
2477 \newlength{\SUF@tochang@par}
2478 \newlength{\SUF@tochang@subpar}
2479 \newlength{\SUF@tochang@fig}
2480 \newlength{\SUF@tochang@tab}
2481 \newlength{\SUF@addto@tochang@chap}
2482 \newlength{\SUF@addto@tochang@sec}
2483 \newlength{\SUF@addto@tochang@subsec}
2484 \newlength{\SUF@addto@tochang@subsubsec}
2485 \newlength{\SUF@addto@tochang@par}
2486 \newlength{\SUF@addto@tochang@subpar}
2487 \newlength{\SUF@addto@tochang@fig}
2488 \newlength{\SUF@addto@tochang@tab}
2489 \setlength{\SUF@tochang@chap}
2490   {\dimexpr(1em+\SUF@tochang+\SUF@label@chap+1em)}
2491 \setlength{\SUF@tochang@sec}
2492   {\dimexpr(\SUF@tochang@chap+\SUF@label@sec+1em)}
2493 \setlength{\SUF@tochang@subsec}
2494   {\dimexpr(\SUF@tochang@sec+\SUF@label@subsec+1em)}
2495 \setlength{\SUF@tochang@subsubsec}
2496   {\dimexpr(\SUF@tochang@subsec+\SUF@label@subsubsec+1em)}
2497 \setlength{\SUF@tochang@par}
2498   {\dimexpr(\SUF@tochang@subsubsec+\SUF@label@par+1em)}
2499 \setlength{\SUF@tochang@subpar}
2500   {\dimexpr(\SUF@tochang@par+\SUF@label@subpar+1em)}
2501 \setlength{\SUF@tochang@fig}
2502   {\SUF@tochang@chap}
2503 \setlength{\SUF@tochang@tab}
2504   {\SUF@tochang@chap}
2505 \setlength{\SUF@addto@tochang@chap}
2506   {\SUF@tochang}
2507 \setlength{\SUF@addto@tochang@sec}
2508   {\dimexpr(\SUF@addto@tochang@chap+\SUF@label@sec+.5em)}
2509 \setlength{\SUF@addto@tochang@subsec}
2510   {\dimexpr(\SUF@addto@tochang@sec+\SUF@label@subsec+.5em)}
2511 \setlength{\SUF@addto@tochang@subsubsec}
2512   {\dimexpr(\SUF@addto@tochang@subsec+\SUF@label@subsubsec+.5em)}
2513 \setlength{\SUF@addto@tochang@par}
2514   {\dimexpr(\SUF@addto@tochang@subsubsec+\SUF@label@par+.5em)}
2515 \setlength{\SUF@addto@tochang@subpar}
2516   {\dimexpr(\SUF@addto@tochang@par+\SUF@label@subpar+.5em)}
2517 \setlength{\SUF@addto@tochang@fig}
2518   {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2519 \setlength{\SUF@addto@tochang@tab}
2520   {\dimexpr(\SUF@addto@tochang@chap-\SUF@label@sec+\SUF@label@chap)}
2521 }

```

TOC entries

```

2522 \titlecontents{chapter}
2523   [ \SUF@tochang@chap]
2524   {\addvspace{2ex}}
2525   {\hspace{-\SUF@tochang@chap\%}
2526     \makebox[1em][l]{\thecontentspage}\%
2527     \hspace{\SUF@addto@tochang@chap\%}
2528     \makebox[\SUF@label@chap][l]{\%
2529       \SUF@toclabelnum\thecontentslabel}\hspace*{1em}\%
2530       \SUF@tocCHAP@font}
2531   {\hspace{-\SUF@tochang@chap\%}
2532     \makebox[1em][l]{\thecontentspage}\%
2533     \hspace{\SUF@addto@tochang@chap\hspace{\SUF@tocCHAP@font}}}
2534   {}
2535   {\addvspace{1ex}}
2536 \titlecontents{section}
2537   [ \SUF@tochang@sec]
2538   {}
2539   {\hspace{-\SUF@tochang@sec\%}
2540     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@sec\%}
2541     \makebox[\SUF@label@sec][l]{\%
2542       \if suftesi@article\SUF@toclabelnum\%
2543       \else\fi\thecontentslabel}\hspace*{1em}\%
2544       \SUF@tocSEC@font}
2545   {\hspace{-\SUF@tochang@sec\%}
2546     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@sec\%}
2547       \SUF@tocSEC@font}
2548   {}
2549 \titlecontents{subsection}
2550   [ \SUF@tochang@subsec]
2551   {}
2552   {\hspace{-\SUF@tochang@subsec\%}
2553     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsec\%}
2554     \makebox[\SUF@label@subsec][l]{\thecontentslabel}\hspace*{1em}\%
2555       \SUF@tocSUBSEC@font}
2556   {\hspace{-\SUF@tochang@subsec\%}
2557     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsec\%}
2558       \SUF@tocSUBSEC@font}
2559   {}
2560 \titlecontents{subsubsection}
2561   [ \SUF@tochang@subsubsec]
2562   {}
2563   {\hspace{-\SUF@tochang@subsubsec\%}
2564     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsubsec\%}
2565     \makebox[\SUF@label@subsubsec][l]{\thecontentslabel}\hspace*{1em}\%
2566       \SUF@tocSUBSUBSEC@font}
2567   {\hspace{-\SUF@tochang@subsubsec\%}
2568     \makebox[1em][l]{\thecontentspage}\hspace{\SUF@addto@tochang@subsubsec\%}
2569       \SUF@tocSUBSUBSEC@font}
2570   {}
2571 \titlecontents{paragraph}

```

```

2572  [\SUF@tochang@par]
2573  {}
2574  {\hskip-\SUF@tochang@par%
2575   \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@par%
2576   \makebox[\SUF@label@par][l]{\thecontentslabel}\hspace*{1em}}
2577  {\hskip-\SUF@tochang@par%
2578   \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@par}
2579  {}
2580 \titlecontents{subparagraph}
2581  [\SUF@tochang@subpar]
2582  {}
2583  {\hskip-\SUF@tochang@subpar%
2584   \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subpar%
2585   \makebox[\SUF@label@subpar][l]{\thecontentslabel}\hspace*{1em}}
2586  {\hskip-\SUF@tochang@subpar%
2587   \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@subpar}
2588  {}
2589 \titlecontents{figure}
2590  [\SUF@tochang@fig]
2591  {}
2592  {\hskip-\SUF@tochang@fig%
2593   \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@fig%
2594   \makebox[\SUF@label@tab][l]{\thecontentslabel}\hspace*{1em}}
2595  {}
2596  {}
2597 \titlecontents{table}
2598  [\SUF@tochang@tab]
2599  {}
2600  {\hskip-\SUF@tochang@tab%
2601   \makebox[1em][l]{\thecontentspage}\hskip\SUF@addto@tochang@tab%
2602   \makebox[\SUF@label@tab][l]{\thecontentslabel}\hspace*{1em}}
2603  {}
2604  {}
2605 \else

```

Default toc

```

2606 \AtBeginDocument{
2607 \newlength\SUF@tocindent@chap
2608 \newlength\SUF@tocindent@sec
2609 \newlength\SUF@tocindent@subsec
2610 \newlength\SUF@tocindent@subsubsec
2611 \newlength\SUF@tocindent@par
2612 \newlength\SUF@tocindent@subpar
2613 \newlength\SUF@tocindent@fig
2614 \newlength\SUF@tocindent@tab
2615 \ifsuftesi@article
2616 \setlength\SUF@tocindent@sec
2617   {\dimexpr(\SUF@label@chap+1.5em)}
2618 \setlength\SUF@tocindent@subsec
2619   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}

```

```

2620 \setlength{\SUF@tocindent@subsubsec}
2621   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2622 \setlength{\SUF@tocindent@par}
2623   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2624 \setlength{\SUF@tocindent@subpar}
2625   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2626 \setlength{\SUF@tocindent@fig}
2627   {\dimexpr(\SUF@label@chap+1.5em)}
2628 \setlength{\SUF@tocindent@tab}
2629   {\dimexpr(\SUF@label@chap+1.5em)}
2630 \else
2631 \setlength{\SUF@tocindent@chap}
2632   {\dimexpr(\SUF@label@chap+1em)}
2633 \setlength{\SUF@tocindent@sec}
2634   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec+1em)}
2635 \setlength{\SUF@tocindent@subsec}
2636   {\dimexpr(\SUF@tocindent@sec+\SUF@label@subsec+1em)}
2637 \setlength{\SUF@tocindent@subsubsec}
2638   {\dimexpr(\SUF@tocindent@subsec+\SUF@label@subsubsec+1em)}
2639 \setlength{\SUF@tocindent@par}
2640   {\dimexpr(\SUF@tocindent@subsubsec+\SUF@label@par+1em)}
2641 \setlength{\SUF@tocindent@subpar}
2642   {\dimexpr(\SUF@tocindent@par+\SUF@label@subpar+1em)}
2643 \setlength{\SUF@tocindent@fig}
2644   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2645 \setlength{\SUF@tocindent@tab}
2646   {\dimexpr(\SUF@tocindent@chap+\SUF@label@sec-\SUF@label@chap)}
2647 \fi
2648 }

```

TOC entries

```

2649 \titlecontents{chapter}
2650   [\SUF@tocindent@chap]
2651   {\addvspace{2ex}}
2652   {\hspace{-\SUF@tocindent@chap}%
2653     \makebox[\SUF@label@chap][1]{\SUF@toclabelnum\thecontentslabel}%
2654     \hspace*{1em}%
2655     \SUF@tocCHAP@font}
2656   {\hspace{-\SUF@tocindent@chap}%
2657     \SUF@tocCHAP@font}
2658   {\SUF@chaptitlerule\contentspage}
2659   [\addvspace{1ex}]
2660 \titlecontents{section}
2661   [\SUF@tocindent@sec]
2662   {}
2663   {\hspace{-\dimexpr(\SUF@label@sec+1em)}%
2664     \makebox[\SUF@label@sec][1]{%
2665       \ifsuftesi@article\SUF@toclabelnum%
2666       \else\fi\thecontentslabel}\hspace*{1em}%
2667     \SUF@tocSEC@font}

```

```

2668 {\hskip-\dimexpr(\SUF@label@sec+1em)%
2669   \SUF@tocSEC@font}%
2670 {\ifsuftesi@article\SUF@chaptitlerule%
2671   \else\SUF@titlerule\fi\contentspage}%
2672 \titlecontents{subsection}
2673 [\SUF@tocindent@subsec]
2674 {}
2675 {\hskip-\dimexpr(\SUF@label@subsec+1em)%
2676   \makebox[\SUF@label@subsec][1]{\thecontentslabel}\hspace*{1em}%
2677   \SUF@tocSUBSEC@font}%
2678 {\hskip-\dimexpr(\SUF@label@subsec+1em)%
2679   \SUF@tocSUBSEC@font}%
2680 {\SUF@titlerule\contentspage}%
2681 \titlecontents{subsubsection}
2682 [\SUF@tocindent@subsubsec]
2683 {}
2684 {\hskip-\dimexpr(\SUF@label@subsubsec+1em)%
2685   \makebox[\SUF@label@subsubsec][1]{\thecontentslabel}\hspace*{1em}%
2686   \SUF@tocSUBSUBSEC@font}%
2687 {\hskip-\dimexpr(\SUF@label@subsubsec+1em)%
2688   \SUF@tocSUBSUBSEC@font}%
2689 {\SUF@titlerule\contentspage}%
2690 \titlecontents{paragraph}
2691 [\SUF@tocindent@par]
2692 {}
2693 {\hskip-\dimexpr(\SUF@label@par+1em)%
2694   \makebox[\SUF@label@par][1]{\thecontentslabel}\hspace*{1em}}%
2695 {\hskip-\dimexpr(\SUF@label@par+1em)}%
2696 {\SUF@titlerule\contentspage}%
2697 \titlecontents{subparagraph}
2698 [\SUF@tocindent@subpar]
2699 {}
2700 {\hskip-\dimexpr(\SUF@label@subpar+1em)%
2701   \makebox[\SUF@label@subpar][1]{\thecontentslabel}\hspace*{1em}}%
2702 {\hskip-\dimexpr(\SUF@label@subpar+1em)}%
2703 {\SUF@titlerule\contentspage}%
2704 \titlecontents{figure}
2705 [\SUF@tocindent@fig]
2706 {}
2707 {\hskip-\SUF@tocindent@fig%
2708   \makebox[\SUF@label@fig][1]{\thecontentslabel}\hspace*{1em}}%
2709 {}
2710 {\SUF@titlerule\contentspage}%
2711 \titlecontents{table}
2712 [\SUF@tocindent@tab]
2713 {}
2714 {\hskip-\SUF@tocindent@tab%
2715   \makebox[\SUF@label@tab][1]{\thecontentslabel}\hspace*{1em}}%
2716 {}
2717 {\SUF@titlerule\contentspage}

```

```

2718 \fi
With article option the toc, lof and lot are printed as sections.
2719 \ifsuftesi@article
2720 \renewcommand\tableofcontents{%
2721   \vspace{2ex}%
2722   \section*{\contentsname}%
2723   \mkboth{\contentsname}{\contentsname}%
2724   \thispagestyle{empty}%
2725   \ifsuftesi@twocolumntoc
2726     \begin{multicols}{2}
2727     \starttoc{toc}%
2728     \end{multicols}%
2729   \else
2730     \starttoc{toc}%
2731   \fi
2732   \vspace{2ex}%
2733 }
2734 \renewcommand\listoffigures{%
2735   \vspace{2ex}%
2736   \section*{\listfigurename}%
2737   \mkboth{\listfigurename}{\listfigurename}%
2738   \thispagestyle{empty}%
2739   \ifsuftesi@twocolumnlof
2740     \begin{multicols}{2}
2741     \starttoc{lof}%
2742     \end{multicols}%
2743   \else
2744     \starttoc{lof}%
2745   \fi
2746   \vspace{2ex}%
2747 }
2748 \renewcommand\listoftables{%
2749   \vspace{2ex}%
2750   \section*{\listtablename}%
2751   \mkboth{\listtablename}{\listtablename}%
2752   \thispagestyle{empty}%
2753   \ifsuftesi@twocolumnlot
2754     \begin{multicols}{2}
2755     \starttoc{lot}%
2756     \end{multicols}%
2757   \else
2758     \starttoc{lot}%
2759   \fi
2760   \vspace{2ex}%
2761 }
2762 \else
The default toc, lof and lot are treated as chapters.
2763 \renewcommand\tableofcontents{%
2764   \if@twocolumn

```

```

2765      \@restonecoltrue\onecolumn
2766  \else
2767      \@restonecolfalse
2768  \fi
2769  \chapter*{\contentsname}%
2770      \mkboth{%
2771          \contentsname}{%
2772          \contentsname}%
2773  \thispagestyle{empty}
2774  \ifsuf{twocolumn}{toc}
2775      \begin{multicols}{2}
2776      \starttoc{toc}%
2777      \end{multicols}
2778  \else
2779      \starttoc{toc}%
2780  \fi
2781  \if@restonecol\twocolumn\fi
2782 }
2783 \renewcommand\listoffigures{%
2784     \if@twocolumn
2785         \@restonecoltrue\onecolumn
2786     \else
2787         \@restonecolfalse
2788     \fi
2789     \chapter*{\listfigurename}%
2790     \mkboth{\listfigurename}{%
2791         \listfigurename}%
2792     \thispagestyle{empty}
2793     \ifsuf{twocolumn}{lof}
2794         \begin{multicols}{2}
2795         \starttoc{lof}%
2796         \end{multicols}
2797     \else
2798         \starttoc{lof}%
2799     \fi
2800     \if@restonecol\twocolumn\fi
2801 }
2802 \renewcommand\listoftables{%
2803     \if@twocolumn
2804         \@restonecoltrue\onecolumn
2805     \else
2806         \@restonecolfalse
2807     \fi
2808     \chapter*{\listtablename}%
2809     \mkboth{%
2810         \listtablename}{%
2811         \listtablename}%
2812     \thispagestyle{empty}
2813     \ifsuf{twocolumn}{lot}
2814         \begin{multicols}{2}

```

```

2815      \@starttoc{lot}%
2816      \end{multicols}
2817      \else
2818      \@starttoc{lot}%
2819      \fi
2820      \if@restonecol\twocolumn\fi
2821  }
2822 \fi

```

New commands

```

2823 \ifsuftesi@article
2824 \def\chapterintro{%
2825 \ClassError{suftesi}{%
2826 {Command \noexpand\chapterintro is undefined\MessageBreak
2827     using 'structure=article'}%
2828 {Command \noexpand\chapterintro is undefined\MessageBreak
2829     using 'structure=article'}}}
2830 \else
2831 \def\chapterintro{%
2832 \@ifstar{\@tempswafalse\@chapterintro}{\@tempswatrue\@chapterintro}%
2833 \def\@chapterintro{\phantomsection
2834 \if@tempswa\section*{\SUF\fchapterintroname}\fi
2835 \addcontentsline{toc}{section}{\SUF\fchapterintroname}}
2836 \newcommand{\chapterintroname}[1]{\def\SUF\fchapterintroname{#1}}
2837 \chapterintroname{Introduzione}
2838 \fi

```

Manual breaks Active in the table of contents but not in the text.

```

2839 \newif\ifheadbreak\headbreakfalse
2840 \DeclareRobustCommand{\headbreak}{%
2841 {\ifheadbreak\else\fi}

```

Active in the text but not in the table of contents.

```

2842 \newif\ifxheadbreak\xheadbreaktrue
2843 \DeclareRobustCommand{\xheadbreak}{%
2844 {\ifxheadbreak\else\fi}
2845 \let\origtableofcontents\tableofcontents
2846 \renewcommand{\tableofcontents}{%
2847 \begin{group}\headbreaktrue\xheadbreakfalse%
2848 \origtableofcontents\endgroup}

```

Backward compatibility An environment to manually typeset the bibliography. (Use `biblatax` instead!)

```

2849 \newenvironment{bibliografia}{%
2850 \ifsuftesi@article
2851 \section*{\refname}
2852 \addcontentsline{toc}{section}{\refname}
2853 \else
2854 \chapter{\bibname}%
2855 \fi

```

```

2856     \normalfont \list{}{%
2857     \setlength{\itemindent}{-\parindent}
2858     \setlength{\leftmargin}{\parindent}
2859     \setlength{\labelwidth}{0pt}
2860     \setlength{\parsep}{\parskip}
2861     \let\makelabel\relax}
2862   {\endlist}

An environment to manually typeset the list of shorthands. (Use biblatax instead!)

2863 \newcommand{\losname}{Sigle}
2864 \newcommand{\itlabel}[1]{\itshape\hbox to 6em{#1}}
2865 \newenvironment{sigle}{%
2866   \chapter{\losname}
2867   \normalfont \list{}{%
2868     \setlength{\labelsep}{0.5em}
2869     \setlength{\itemindent}{0pt}
2870     \setlength{\leftmargin}{6em}
2871     \setlength{\labelwidth}{\leftmargin}
2872     \setlength{\listparindent}{\parindent}
2873     \setlength{\parsep}{\parskip}
2874     \let\makelabel\itlabel}
2875   {\endlist}

```

Final settings

Renew `\frontmatter` to have arabic page numbering:

```

2876 \ifsuftesi@article
2877 \renewcommand\frontmatter{\ClassError{suftesi}
2878   {Command \noexpand\frontmatter is undefined\MessageBreak
2879     using 'structure=article'}
2880   {Command \noexpand\frontmatter is undefined\MessageBreak
2881     using 'structure=article'}}
2882 \renewcommand\mainmatter{\ClassError{suftesi}
2883   {Command \noexpand\mainmatter is undefined\MessageBreak
2884     using 'structure=article'}
2885   {Command \noexpand\mainmatter is undefined\MessageBreak
2886     using 'structure=article'}}
2887 \renewcommand\backmatter{\ClassError{suftesi}
2888   {Command \noexpand\backmatter is undefined\MessageBreak
2889     using 'structure=article'}
2890   {Command \noexpand\backmatter is undefined\MessageBreak
2891     using 'structure=article'}}
2892 \else
2893 \renewcommand\frontmatter{\cleardoublepage\@mainmatterfalse}
2894 \renewcommand\mainmatter{\cleardoublepage\@mainmattertrue}
2895 \fi

```

In a previous version the `\hemph` command was provided to fix a bug in the hyphenation of some italian expressions like "dell'*encyclopaedia*". Now the bug has been fixed by the `fixltxhyph` package by Claudio Beccari. The package must be loaded after `babel` or `polyglossia`:

```
2896 \@ifpackageloaded{babel}
```

```

2897  {\AtBeginDocument{\RequirePackage{fixltxhyph}}}{}
2898 \@ifpackage{polyglossia}
2899  {\AtBeginDocument{\RequirePackage{fixltxhyph}}}{}
The \hemph command is provided only for backward compatibility:
2900 \let\hemph\emph
The first line of all sections is indented by default using XELATEX with Italian as the main language.
Anyway this is incongruous with the LATEX default.
2901 \ifthenelse{\boolean{xetex} \or \boolean{luatex}}
2902  {\let\@afterindenttrue\@afterindentfalse}
2903  {\relax}
Just one touch of french typography:
2904 \frenchspacing

```

Change History

v0.5	changes	1
	General: First public release. The frontispiece of <code>suftesi</code> is now included in the package <code>frontespizio</code> . New option <code>fullplain</code> Changed option <code>sctitles</code>	1
	New command <code>chapnumfont</code> ...	17
	New option <code>compact</code>	20
	New option <code>elements</code>	20
	New option <code>nocrop</code>	20
	New option <code>nomarginpar</code>	20
	New option <code>sufelements</code>	20
	New option <code>supercompact</code> ...	20
v0.6	General: English documentation. Renamed options <code>plain</code> and <code>fullplain</code> to <code>centerheadings</code> and <code>sufplain</code>	1
	New command <code>\artcolophon</code> .	15
	New command <code>\bookcolophon</code> .	15
	New option <code>authortitle</code>	20
v0.6a	General: Maintenance release, no changes	1
v0.6b	General: Improved full compatibility with X _E L ^A T _E X. <code>variorref</code> and <code>footmisc</code> packages are no longer loaded	1
v0.6c	General: Maintenance release, no	
v0.7	changes	1
	General: Maintenance release, no changes. Provided a thesis template	1
v0.8	General: Added macro for using <code>frontespizio</code> package with <code>compact</code> and <code>supercompact</code> options.	1
	New option <code>periodical</code>	20
	Renewed <code>\title</code> command ...	17
v0.9	General: Improved compatibility with <code>mathspec</code>	1
	New option <code>dottedtoc</code>	20
	New option <code>raggedtoc</code>	20
v0.9a	General: Added inline option to <code>enumitem</code> package. Deleted <code>centertitle</code> option. Deleted <code>sctitles</code> option. Changed code for toc, lot and lof elements.	1
	New command <code>\toclabelspace</code>	16
	New option <code>alignlist</code>	20
	New option <code>centerchap</code>	20
	New option <code>centerpart</code>	20
	New option <code>centersec</code>	20
	New option <code>defaultparindent</code>	20
	New option <code>dottedchap</code>	20
	New option <code>dottedfootnote</code> ..	20
	New option <code>dottedpart</code>	20

New option <code>indentlist</code>	20	v1.0	
New option <code>italicchap</code>	20	General: First stable release.	
New option <code>italicheader</code>	20	Renamed option <code>bozza</code> to	
New option <code>italicpart</code>	20	<code>draftdate</code>	14
New option <code>italicsec</code>	20	v1.1	
New option <code>italicsubsec</code>	20	General: Added the <code>fixltxhyph</code>	
New option <code>itstyle(1-12)</code>	20	package. Documentation up-	
New option <code>numparchap</code>	20	dated.	1
New option <code>numparpart</code>	20	v1.2	
New option <code>numparsec</code>	20	General: Maintenance release.	
New option <code>ralignquotation</code>	20	Added the <code>\toclabelspace</code>	
New option <code>rightchap</code>	20	command.	1
New option <code>rightpart</code>	20	v1.3	
New option <code>rightsec</code>	20	General: New command	
New option <code>rmstyle(1-6)</code>	20	<code>\FSPLcolophon</code>	20
New option <code>romanchap</code>	20	Updated documentation. Added	
New option <code>scstyle(1-12)</code>	20	<code>FSPLa</code> , <code>FSPLb</code> and <code>FSPLc</code> styles.	1
New option <code>smallcapschap</code>	20	v1.4	
New option <code>smallcapsheader</code>	20	General: New value <code>periodicalaureo</code>	
New option <code>smallcapspart</code>	20	for option <code>pagelayout</code> .	
New option <code>smallcapssec</code>	20	Changed code for <code>\xfootnote</code>	
New option <code>smallquotation</code>	20	command.	1
New option <code>standardfootnote</code>	20	v1.5	
New option <code>tocpageleft</code>	20	General: The <code>microtype</code> package is	
v0.9b		loaded for all engines. Improved	
General: Changed <code>standardfootnote</code>		compatibility with <code>todonotes</code>	
option and renamed to		package and with <code>mdframed</code> and	
<code>footnotestyle</code>	13	<code>bookmark</code> packages when using	
New command <code>\xfootnote</code>	17	<code>style</code> class option. New option	
New option <code>fewfootnotes</code>	13	<code>viewmode</code>	1
New option <code>greekfont</code>	10	v1.6	
New option <code>pagestyle</code>	7	General: New option <code>viewmode</code> .	
New option <code>parindent</code>	13	Corrected bugs in the def-	
New option <code>partpage</code>	14	inition of <code>\listoffigures</code> ,	
New option <code>quotationfont</code>	12	<code>\listoftables</code> and <code>\tableofcontents</code>	
New option <code>quotestyle</code>	12	commands. Updated documen-	
New option <code>structure</code>	7	tation.	1
New option <code>tocstyle</code>	11	v1.7	
Restored 11pt and 12pt option to		General: Renamed <code>viewmode</code> option	
default	1	to <code>version</code> : renamed <code>print</code>	
The <code>epigraph</code> package is no		value to <code>draft</code> and added <code>final</code>	
longer loaded	3	value. New <code>smallcapsstyle</code> op-	
The <code>mparhack</code> package is no		tion.	1
longer loaded. It is not compati-		v1.8	
ble with <code>crop</code>	3	General: Maintenance release. Cor-	
v0.9c		rected a bug in the definition of	
General: Maintenance release, no		<code>\appendix</code>	1
changes	1	v1.9	
		General: Added <code>italic</code> , <code>smallcaps</code>	
		and <code>sanserif</code> values for	

<code>captionstyle</code> option.	New	v2.0.1
<code>twocolcontents</code> option.	New	General: Corrected a bug in <code>version</code>
<code>supercompactaureo</code> page layout.	Changed <code>\toclabelspace</code>	option.
command and renamed	<code>\toclabelwidth</code> .	1
<code>collection</code> document structure	v2.1
		General: New option <code>toc<level>font</code> .
		Updated documentation. Removed <code>\includeart</code> command .
v1.9a		1 v2.2
General: Maintenance release.	Up-	General: Maintenance release.
dated greek support. Updated	dated	1
documentation.	documentation.	v2.3
v1.9b		General: Maintenance release.
General: Corrected a bug in “toc”,	“lof” and “lot” commands.	1 v2.4
v1.9c		General: Changed the default font
General: The <code>cbgreek</code> value for the	to Cochineal with Linux Bi-	
<code>greekfont</code> option allows now to	olinum O sans serif and Inconsolata monospaced. The Palatino	
use the full set of the CB Greek	is now loaded with <code>newpxtext</code>	
font together with the default	and <code>newpxmath</code> . Bera Mono	
font (Palatino).	and Iwona have been substituted by Linux Biolinum O	
v2.0		and Inconsolata. New values for font options: <code>cochineal</code> ,
General: New page layout	<code>libertine</code> , <code>bodoni</code> (greek	
<code>standardaureo</code> .	only). Value <code>compatibility</code> for	
Enhanced support for Lua ^L ATE _X .	<code>defaultfont</code> option to get the	
Headers settings are now executed	fons of softesi v2.3 or previous.	
<code>\AtBeginDocument</code> .	Updated documentation.	
Loaded <code>ifluatex</code> and <code>ifthen</code> pack-	1	
ages. Added <code>listparindent</code>	v2.5	
to <code>\setlist</code> options. Updated	General: Corrected a bug when load-	
documentation.	ing CB Greek fonts. Updated	
	documentation.	
	1	

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols			
<code>\(`</code>	1032	<code>\@author</code>	460,
<code>\)`</code>	1032		464, 1666, 1696,
<code>\@Alph</code> .	2133, 2147, 2153		1723, 1790, 1836,
<code>\@M</code>	2322		1895, 1957, 1973,
<code>\@Roman</code> .	370, 382,		1982, 1987, 2383
	397, 409, 424, 436	<code>\begin{parpenalty}</code> .	2319
			1708, 1726, 1735,
<code>\@afterindentfalse</code> .	2902	<code>\centercr</code>	2251
<code>\@afterindenttrue</code> .	2902	<code>\chapapp</code>	2132, 2152
<code>\@arabic</code>	1520, 1522, 1524, 1526,	<code>\chapterintro</code>	2832, 2833
	1528, 2027, 2029,	<code>\citex</code>	1042, 1043
		<code>\collectioneditor</code> .	1656, 1885
			<code>\doi</code>
			1648, 1649
			<code>\endparpenalty</code>
			2322

\@fnsymbol	1675,	\@mkboth	2087,	\@todonotes@drawLineToLeftMargin
1741,	1799,	2723, 2737, 2751,	2294
1933,	2262, 2269	2770, 2790, 2809	\@todonotes@drawLineToRightMargin	
\@footnotemark . . .	2273	\@nonchange-case	2297
\@footnotetext . . .	2273	1039–1041	\@todonotes@drawMarginNote
\@headtitle	459,	\@plus	1903, 2091, 2239 2293, 2296
463, 1655, 1658,		\@pnumwidth 1905, 1906, 1911	\@todonotes@drawMarginNoteWithLine
1884, 1887, 1983		2078, 2288
\@highpenalty	1902, 1928	\@restonecolfalse	\@topnum 1754, 1812, 1946
\@idxitem	2094	2767, 2787, 2806	\@uclclist 1045
\@ifpackage{loaded} . . .		\@restonecoltrue	\@uclcnnotmath 1031
... 1030, 1057,		2080,	
1580, 1612, 2055,		2765, 2785, 2804	\u 580, 1872, 2186, 2188	
2287, 2896, 2898		\@roman	366, 378,	A
\@ifpackage{with} . . .	2039	393, 405, 420, 432	\@abstractname	2305,
\@ifstar	2832	\@skipmath	2309, 2321,	
\@isbn	1645	.. 1036, 1037, 1048	2328, 2332, 2339	
\@issn	1646, 1651, 1652	\@standardmaketitle		\addfontfeature
\@issue	1863, 1864, 1875	... 1806, 1808, 1319, 1321	
\@issuename	1876	1813, 1820, 1825	\@addpenalty 1902	
\@journalname		\@starttoc 2727,	\@addtolen... 2420, 2421	
... 1854, 1855, 1874		2730, 2741, 2744,	\@Alph 2137	
\@journalnumber		2755, 2758, 2776,	\@alph 492, 499, 506	
... 1860, 1861, 1874		2779, 2795,	\@and 1710, 1737,	
\@journalvolume		2798, 2815, 2818	1766, 1824, 1963	
... 1857, 1858		\@tempswafalse 2832	\appendicesname	
\@journalwebsite		\@tempswatrue 2832 2096, 2097	
\@journalyear		\@textsuperscript	\appendix 2129, 2144, 2149	
... 1866, 1867, 1875	 1742,	\appendixname	
\@latex@warning{no@line}		1745, 1800,	... 2132, 2137, 2152	
... 1646, 1649,		1803, 1934, 1937	\@appendixpage 2098	
1652, 1855, 1858,		\@thanks 1701, 1707,	\arabic 360, 372,	
1861, 1864, 1867,		1728, 1734, 1757,	387, 399, 414,	
1870, 1878, 1881		1763, 1815, 1821,	426, 491, 498, 505	
\@lowpenalty	2319	1872, 1873, 1949,	\@art@scale .. . 1224, 1226	
\@mainmatterfalse . . .	2893	1956, 1994, 2009	\@artcolophon 2364	
\@mainmattertrue . . .		\@thefnmark 530, 534,	\AtBeginDocument	
... 2100, 2894		537, 540, 1742,	680, 1029, 1056,	
\@makefnmark		1745, 1800, 1803,	1077, 1185, 1579,	
... 1742, 1800, 1934		1934, 1937, 2272	1611, 1965, 2038,	
\@makefntext	529,	\@title 1655, 1662,	2159, 2261, 2286,	
532, 536, 539,		1681, 1685, 1687,	2419, 2436, 2472,	
1743, 1801, 1935		1690, 1718, 1775,	2606, 2897, 2899	
\@makeschapterhead . . .	2085	1779, 1781, 1784,		
\@maketitle	1748,	1831, 1884, 1891,	\author 1668, 1897, 1961	
1750, 1755, 1762,		1959, 1972, 1989		B
1767, 1940, 1942,		\@titlepagefalse		
1947, 1955, 1965	 79, 90, 687	\backmatter	
		\@titlepagetrue 685	... 2887, 2888, 2890	

\baselineskip .	1315,	\ClassError	1214, 1226–1235,
1366, 1372, 1390,		. 60, 62, 64, 66,	1261–1268, 1270–
1448, 1452, 1456,		68, 1059, 1240,	1272, 1275–1282,
1460, 1464,		1512, 1917, 2263,	1284–1286, 1289–
1468, 1472, 1475		2409, 2425, 2825,	1295, 1297–1299
\bibname	1613,	2877, 2882, 2887 \DeclareRobustCommand	
1619, 1627, 2854		. 100, 111, 123,	
\bookcolophon	2356 1,	136, 149, 162,
\boolean 1054, 1316, 2901		1659, 1663, 1667,	175, 200, 1187,
C		1888, 1892, 1896	1318, 1320, 1327,
\c@chapter	2133, 2153	\cleardoublepage	1329, 2840, 2843
\c@footnote	1675, 2008,	\DeclareTextFontCommand
1741, 1799,		2109, 2118, 2355, 1190
1873, 1933, 2269		2363, 2893, 2894	\defbibheading 1581,
\c@paragraph 1526, 2033		\clearpage	1584, 1587, 1591,
\c@section 2024, 2095, 2406	1595, 1598, 1601,
. 1520, 2027, 2147		\cmdSUF@elements@chapposition	1603, 1606, 1613,
\c@subparagraph 1338, 1346	1616, 1619, 1623,
. 1528, 2035		\cmdSUF@elements@chapsize	1627, 1630,
\c@subsection 1522, 2029	 1336, 1345	1633, 1636, 1640
\c@subsubsection		\col@number	\define@choicekey 73,
. 1524, 2031	 1747, 1805, 1939	84, 96, 213, 231,
\c@tocdepth	1901	\collectioneditor	251, 269, 277,
\captionsetup	553,	\collectiontitle	285, 293, 301,
555, 556, 558,	 1877, 1879	309, 317, 325,
559, 561, 563, 564		\colophon	333, 341, 349,
\cc	2383	\columnsep	357, 384, 411,
\chapnumfont	1322,	\columnseprule	438, 445, 469,
1324, 1331, 1333		\contentsmargin	488, 512, 519,
\chapter	1340,	\contentsname	526, 542, 550,
1377, 1383, 1448,	 2722, 2723,	567, 573, 589,
1452, 1456, 1460,		2769, 2771, 2772	619, 634, 647,
1464, 1468, 1472,		\contentspage	654, 660, 667,
1475, 1488, 1489,		2108, 2658, 2671, 2680,	673, 682, 689,
1492, 1493, 1496,		2689, 2696,	937, 946, 952, 961
1497, 1500, 1501,		2703, 2710, 2717	\definecolor . 1020, 1021
1503, 1505, 1512,		\copyright	\dimen 1221–1223
1513, 1515, 1614,		\crop 665, 677, 680	\dimen@ 1218, 1223, 1224
1617, 1620, 1624,		\csname	\disable@keys
1628, 1631, 2134,		1657, 1886, 1978, 2420, 2421 76, 87, 872,
2141, 2769, 2789,		D	880, 893, 911, 930
2808, 2854, 2866		\date 1709, 1736,	\doi 1648, 1650
\chapterintro	2824,	1765, 1823, 1962	\dotfill 1910
2826, 2828, 2831		\DeclareFontFamily	\doublehyphendemerits
\chapterintroname 1193, 1225, 2280, 2281
. 2836, 2837		1260, 1274, 1288	E
\chaptermark 2165, 2185		\DeclareFontShape	\emph 1874, 2399, 2900
\chaptertitlename	2186 1194–	\encodingdefault 1189
\cite	1042		

\endcsname	1657, 1886,	G	\ifsuftesi@article .
1978,	2420, 2421	\gdef 24,
\endlist	2243, 2249,	1645, 1648, 1651, 1655,	1398, 1406, 1511,
2259,	2862, 2875	1854, 1857, 1860,	1578, 1683, 1777,
\endquotation	2313, 2336	1863, 1866, 1869,	2082, 2143, 2187,
\ensuremath	. 1041, 2262	1876, 1877, 1880,	2218, 2542, 2615,
\ExecuteOptionsX	. . 969	1884, 2132, 2133,	2665, 2670, 2719,
\exhyphenpenalty	. 2279	2147, 2152, 2153	2823, 2850, 2876
\extramarks	. . . 1356	\global	\ifsuftesi@authortitle .
F		1705– 1710, 1732–1737, 25, 2219
\f@series	. . . 1188	1754, 1760–1766,	\ifsuftesi@bodoni ..
\f@shape	. . . 1188	1812, 1818–1824,	20, 1087, 1107,
\fancyfoot	. . 2170, 2196, 2198, 2201, 2206, 2210	1946, 1953– 1963, 1994, 2009	1127, 1149, 1175
\fancyhead	. . 2171, 2177, 2203, 2204, 2212–2214	\greektext .. . 1187, 1190	\ifsuftesi@cbgreek .
\fancyhf	. . 2169, 2193, 2195, 2200, 2209	H	... 21, 1178, 1258
\fancypagestyle	. . . 2167, 2193, 2194, 2199, 2208	\hb@xt@ .. . 1744, 1802, 1911, 1936	\ifsuftesi@cochineal 15, 1140
\finalcolophon	. . . 2369	\headbreak .. . 2840	\ifsuftesi@collection
\finalhyphendemerits 2281	\headbreakfalse .. . 2839	... 58, 1844, 2302
\font	. . . 1217, 1220	\headbreaktrue .. . 2847	\ifsuftesi@compact .
\fontencoding	. . . 1077	\headrulewidth .. . 2161 28, 1455,
\fontfamily	. . . 1332	\hemp 2900	1495, 2043, 2060
\footnote	. . 1674, 1714, 1772, 1830, 1969	\hfill 1914, 1924	\ifsuftesi@compactaureo 29, 1459
\footnotemark	. . . 1872	\hss 1745, 1803, 1911, 1937	\ifsuftesi@compatibility
\footnoterule 1673, 1713, 2162	\ht 1218, 1221 11, 1083
\footnotesize	. . . 522, 580, 1672, 1712, 2197, 2198, 2202– 2204, 2206, 2211– 2214, 2277, 2394	\Hy@raisedlink .. . 1976	\ifsuftesi@dottedtoc 34, 1910
\footnotetext	. . . 1873	\hyper@anchorend . 1977	\ifsuftesi@draftdate 48, 2197, 2202, 2211
\fracingspacing	. . . 2904	\hyper@anchorstart 1977	\ifsuftesi@elementschap 44, 1443
\frontispiece	. . . 2011	\hyper@linkend 1037, 1038	\ifsuftesi@elementsheader 45, 2164, 2232, 2275
\frontmatter	. . 2877, 2878, 2880, 2893	\hyper@linkstart 1034, 1035	\ifsuftesi@elementspagelayout 47, 1471
\FSPLcolophon	. . . 2379, 2408, 2410, 2412	\hyphenpenalty .. . 2279	\ifsuftesi@elementsstructure 46
\fulljournal	. . . 1874	I	\ifsuftesi@fewfootnotes 49, 2260
		\if@mainmatter .. . 2228	\ifsuftesi@FSPL 51, 1050, 2378
		\if@restonecol 2095, 2781, 2800, 2820	\ifsuftesi@greekfont 13, 1168, 1239, 1257
		\if@tempswa 2834	\ifsuftesi@libertine 16, 1120
		\if@titlepage 1670, 2315	\ifsuftesi@nocrop 33, 1304
		\if@twocolumn 1746, 1804, 1938, 2077, 2304, 2313, 2327, 2336, 2764, 2784, 2803	
		\ifheadbreak . 2839, 2841	
		\ifsuftesi@artemisia .. . 19, 1090, 1110, 1130, 1152, 1169	

\ifsuftesi@nofont 12, 1078, 1238
\ifsuftesi@numparchap 37, 1376, 1389
\ifsuftesi@numparpart 36, 1535, 1549
\ifsuftesi@numparsec 38, 1395
\ifsuftesi@numparsubsec 39, 1412
\ifsuftesi@numparsubsubsec\ignorespaces 40, 1427
\ifsuftesi@pagelefttoc 53, 1916, 2470
\ifsuftesi@palatino 17, 1100
\ifsuftesi@partpage 50, 1529
\ifsuftesi@periodical 26, 1447,
1491, 2040, 2056
\ifsuftesi@periodicalaureo 27, 1451,
1487, 2049, 2068
\ifsuftesi@porson 18, 1093, 1113, 1133,
1155, 1172, 1215
\ifsuftesi@raggedtoc 35, 1913
\ifsuftesi@reverseauthortitle 57, 1971, 1986
\ifsuftesi@screen 52, 1309
\ifsuftesi@smallcapschap 42, 1680, 1774
\ifsuftesi@smallcapspart 41
\ifsuftesi@smallcapssec 43, 1684, 1778
\ifsuftesi@standard 14, 1080
\ifsuftesi@sufelements 32, 2128
\ifsuftesi@sufplain 23, 2231
\ifsuftesi@supercompact 30, 1463,
1499, 2046, 2064
\ifsuftesi@supercompactaurebARGE 31, 1467
\ifsuftesi@twocolumnlof 55, 2739, 2793
\ifsuftesi@twocolumnlot 56, 2753, 2813
\ifsuftesi@twocolumntoc 54, 2725, 2774
\ifthenelse 1054, 1316, 2901
\ifxetex 1256
\ifxheadbreak 2842, 2844
\index 2354
\indexname 2083, 2085, 2087
\isbn 1645,
1647, 1651, 1653
\issue 1863, 1865
\issuename 1876
\item 2094,
2240, 2247, 2257
\itemindent 2236, 2253,
2254, 2857, 2869
\itemsep 2252
\itlabel 2864, 2874
\itshape 289, 297, 305,
313, 321, 329,
337, 345, 353,
476, 477, 487,
956, 965, 1362,
1568, 1983, 2175,
2181, 2276, 2864

J

\journalname 1854, 1856
\journalnumber 1860, 1862
\journalvolume 1857, 1859
\journalwebsite 1869, 1871
\journalyear 1866, 1868

L

\l@title 1900
\label 1039, 1974,
1997, 1999, 2007
\labelitemi 485
\labelsep 2868
\labelwidth 2859, 2871
\Large 100, 111, 1341

\LaTeX 2350, 2398, 2399
\leftmargin 2237,
2245, 2255, 2256,
2858, 2870, 2871
\leftmark 2175, 2228
\leftskip 533, 1907, 1908
\lineskip 1694, 1721,
1788, 1834, 2278
\lineskiplimit 2278
\list 2235, 2245,
2252, 2856, 2867
\listfigurename 2736,
2737, 2789–2791
\listoffigures 2734, 2783
\listoftables 2748, 2802
\listparindent 2235,
2236, 2254, 2872
\listtablename
. 2750, 2751,
2808, 2810, 2811
\LoadClass 72
\losname 1584, 1591,
1598, 1616, 1623,
1630, 2863, 2866
\lsstyle 1328, 1330

M

\mainmatter 2882,
2883, 2885, 2894
\makelabel 2861, 2874
\MakeTextLowercase 441
\maketitle 1671, 1706,
1733, 1739, 1761,
1819, 1931, 1954

N

\Margini 2041, 2044,
2047, 2050, 2057,
2061, 2065, 2069
\marginpar 571, 2282, 2283
\marginparsep 1347, 2174, 2180
\marginparwidth 2175, 2180, 2181
\markboth 1583,
1586, 1590, 1594,
1615, 1618, 1622,
1626, 2165, 2186
\markright 1597,
1600, 1629, 1632,
1635, 1639,
1884, 2166, 2188

Miede, André	69	O	\renewenvironment
		\oldmarginpar 2076,
		.. 2282, 2283, 2292	2234, 2244, 2250
N		\onecolumn	2095,
\newcounter	1845–1848, 1850	2765, 2785, 2804	1045, 1047, 1049
\newlength	1314,	\origtableofcontents	1045, 1046
	1374, 2416, 2434, 2845, 2848	\Rientro
	2437–2444, 2473–		2058,
	2488, 2607–2614		2062, 2066, 2070
\newline	1982	P	\rightmargin . 515, 2255
\nobreak	1909, 1911,	\p@ 1218, 1221–1223,	\rightmark
	1914, 1924, 1985	1677, 1716, 1903,	449, 453, 2181, 2228
\NoCaseChange	1032, 1033, 1043	2091, 2093, 2239	\rightskip 1905
\node	2290	\pagestyle	\rlap .. 1742, 1800, 1934
\noindent	1743,	.. 2160, 2229–2232	\rmdefault 1186
	1801, 1935, 2242,	\paragraph .. 1564, 1570	\Roman 368, 380,
	2346, 2350, 2360,	\parfillskip 1906	395, 407, 422, 434
	2362, 2368,	\parsep 2239, 2860, 2873	\roman 364, 376,
	2383, 2386, 2398	\parskip 2091, 2860, 2873	391, 403, 418,
\nr	73, 75, 84, 86,	\part 1532, 1533, 1536,	430, 493, 500, 507
	96, 99, 213, 215,	1542, 1550, 1556	\rule 1352, 2140
	231, 233, 251,	\partname 1538,	S
	253, 269, 270,	1544, 1552,	\sbox 1216,
	277, 278, 285,	1558, 2121, 2464	1217, 1219, 1220
	286, 293, 294,	\PassOptionsToClass 69	\section 1355, 1360,
	301, 302, 309,	\penalty 1928	1396, 1402, 1404,
	310, 317, 318,	\phantomsection 2833	1410, 1582, 1585,
	325, 326, 333,	Poll, Philipp H. 3	1588, 1592, 1596,
	334, 341, 342,	\ProcessOptionsX 1007	1599, 1634, 1637,
	349, 350, 357,	\protect 1659,	1641, 2083, 2305,
	359, 384, 386,	1663, 1667, 1873,	2328, 2722, 2736,
	411, 413, 438,	1888, 1892, 1896	2750, 2834, 2851
	440, 445, 448,	\protected@edef 1047	\sectionmark
	469, 471, 488,	\protected@xdef 1872	.. 2166, 2188, 2190
	490, 512, 514,	\put 1346, 2173, 2179	\sectionsep
	519, 521, 526,		... 1314, 1315,
	528, 542, 544,		1402, 1410, 1418,
	550, 552, 567,		1425, 1433, 1440,
	569, 573, 575,	Q	1533, 1570, 1577
	589, 591, 619,	\quotation 2311, 2334	R
	621, 634, 636,	\raggedleft 2181, 2284	\setlength 650,
	647, 649, 654,	\raggedright	652, 1315, 1343,
	655, 660, 662,	.. 2089, 2175, 2285	1390, 1392, 2168,
	667, 669, 673,	\ref 1040	2417, 2435, 2445,
	675, 682, 684,	\refname 1581, 1587,	2447, 2449, 2451,
	689, 697, 937,	1595, 1601, 1603,	2453, 2455, 2457,
	939, 946, 948,	1606, 1633, 1636,	2459, 2489, 2491,
	952, 953, 961, 962	1640, 2851, 2852	2493, 2495, 2497,
		\refstepcounter	2499, 2501, 2503,
	 1966, 1996	2505, 2507, 2509,
			2511, 2513, 2515,

2517, 2519, 2616,	\SUF@addto@tochang@tab	1173, 1176,
2618, 2620, 2622,	.. 2488, 2519, 2601	1179, 1186, 1188
2624, 2626, 2628,	\SUF@ADJnumparchap .	\SUF@headingsmallcaps
2631, 2633, 2635,	.. 1374, 1390,	480–482, 1320, 1329
2637, 2639, 2641,	1392, 1488, 1492,	\SUF@label@chap 2416,
2643, 2645, 2857–	1496, 1500, 1504	2417, 2446, 2448,
2860, 2868–2873	\SUF@appendices .. .	2490, 2518, 2520,
\setlist 2096, 2111, 2115	2528, 2617, 2627,
486,	\SUF@appendixpage ..	2629, 2632,
487, 491–496, 2098, 2099	2644, 2646, 2653
498–503, 505–510		\SUF@label@fig
\sfdefault	\SUF@authorfont@Switch	.. 2443, 2457, 2708
\small 963,	\SUF@label@par 2441,
524,	965, 967, 1973, 1987	2453, 2456, 2498,
1672, 1694, 1699,	\SUF@CHAP@StyleSwitch	2514, 2576, 2623,
1712, 1788, 1793, 295,	2640, 2693–2695
2136, 2139, 2307,	297, 299, 1381, 1387	\SUF@label@part 2122,
2330, 2350, 2362,	\SUF@chapnumfont .. .	2437, 2445, 2465
2368, 2374, 2386	.. 1323, 1332, 1344	\SUF@label@sec 2438,
\standardtitle 1711, 1797	\SUF@chaptersize .. .	2447, 2450, 2458,
\strip@pt 100, 111, 123,	2460, 2492, 2508,
1224	136, 149, 162,	2518, 2520, 2541,
\subparagraph 1571, 1577	175, 200, 1378,	2634, 2644, 2646,
\subsection .. . 1361,	1384, 1537, 1543,	2663, 2664, 2668
1366, 1413, 1418,	1551, 1557, 1679,	\SUF@label@subpar ..
1420, 1425,	1773, 1967, 2017 2442,
1602, 1604, 1607	\SUF@chaptitlerule ..	2455, 2500, 2516,
\substitutefont .. 1186 577,	2585, 2625,
\subsubsection 1367,	581, 585, 2658, 2670	2642, 2700–2702
1372, 1428,	\SUF@default@CHAPTER	\SUF@label@subsec ..
1433, 1435, 1440 1375, 1485	... 2439, 2449,
\SUF@addto@tochang@chap	\SUF@default@SECTIONS	2452, 2494, 2510,
..... 2481, 1394, 1486	2554, 2619, 2636,
2505, 2508, 2518,	\SUF@dotchap .. . 388,	2675, 2676, 2678
2520, 2527, 2533	392, 396, 400,	\SUF@label@subsubsec
\SUF@addto@tochang@fig	404, 408, 1379, 1385	... 2440, 2451,
.. 2487, 2517, 2593	\SUF@dotpart .. . 361,	2454, 2496, 2512,
\SUF@addto@tochang@par	365, 369, 373,	2565, 2621, 2638,
... 2485, 2513,	377, 381, 1538,	2684, 2685, 2687
2516, 2575, 2578	1544, 1552, 1558	\SUF@label@tab .. .
\SUF@addto@tochang@sec	\SUF@dotsec .. . 415,	... 2444, 2459,
... 2482, 2507,	419, 423, 427,	2594, 2602, 2715
2510, 2540, 2546	431, 435, 1399, 1407	\SUF@leftmark .. .
\SUF@addto@tochang@subpar	\SUF@elements@CHAPTER 450, 454,
..... 2486, 1339, 1445	460, 464, 2220, 2225
2515, 2584, 2587 1354, 1446	\SUF@leftrightmark .
\SUF@addto@tochang@subsec	\SUF@elements@SECTIONS	... 450, 454, 2227
... 2483, 2509, 1354, 1446	\SUF@Lheadstyle ..
2512, 2553, 2557	\SUF@fchapterintroname	. 450, 454, 460,
\SUF@addto@tochang@subsubsec 2834–2836	464, 473, 477, 481
... 2484, 2511,	\SUF@greekfamily ..	
2514, 2564, 2568 1170,	

\SUF@lr@CHAPSwitch .	321, 323, 1432, 1439	\SUF@tochang@sec .
..... 234,	\SUF@thechapter 2474,
236, 238, 240, 387, 391,	2491, 2494,
243, 246, 1378, 1384	395, 399, 403,	2537, 2539, 2545
\SUF@lr@coll@titleSwitch	407, 1348, 1379,	\SUF@tochang@subpar
940, 942, 944, 1968	1385, 2153, 2186	... 2478, 2499,
\SUF@LR@MarkSwitch .	\SUF@thepage	2581, 2583, 2586
... 2205, 2215,	. 474, 478, 482,	\SUF@tochang@subsec
2220, 2222, 2225	2198, 2206, 2212 2475,
\SUF@lr@PARTSwitch .	\SUF@thechapter . 360,	2493, 2496,
..... 216,	364, 368, 372,	2550, 2552, 2556
218, 220, 222,	376, 380, 1538,	\SUF@tochang@subsubsec
225, 228, 1537,	1544, 1552, 1558 2476,
1543, 1551, 1557	\SUF@thesection 414,	2495, 2498,
\SUF@lr@SECSwitch .	418, 422, 426,	2561, 2563, 2567
..... 254,	430, 434, 1398,	\SUF@tochang@tab ..
256, 258, 260,	1406, 2147, 2188 2480,
263, 266, 1397, 1405	\SUF@titlefont@Switch	2503, 2598, 2600
\SUF@lr@SUBSECSwitch 954,	\SUF@tocindent@chap
..... 271,	956, 958, 1972, 1989	... 2607, 2631,
273, 275, 1414, 1421	\SUF@titlerule . 576,	2634, 2644, 2646,
\SUF@lr@SUBSUBSECSwitch	580, 584, 2671,	2650, 2652, 2656
..... 279,	2680, 2689, 2696,	\SUF@tocindent@fig .
281, 283, 1429, 1436	2703, 2710, 2717	... 2613, 2626,
\SUF@mpsetup	\SUF@titlesmallcaps	2643, 2705, 2707
... 2274, 2284, 2285	. 291, 299, 307,	\SUF@tocindent@par .
\SUF@PART@StyleSwitch	315, 323, 331, 2611,
..... 287, 289,	339, 347, 355,	2622, 2625,
291, 1538, 1540,	958, 967, 1318,	2639, 2642, 2691
1544, 1546, 1552,	1327, 1351, 1359,	\SUF@tocindent@sec .
1554, 1558, 1560	1681, 1685, 1775, 2608,
\SUF@quotation@size	1779, 2137, 2139	2616, 2619,
..... 522, 524,	\SUF@tocCHAP@font ..	2633, 2636, 2661
2241, 2248, 2258 327,	\SUF@tocindent@subpar
\SUF@quote@style ..	329, 331, 2530, 2612,
515, 517, 2238, 2246	2533, 2655, 2657	2624, 2641, 2698
\SUF@Rheadstyle ...	\SUF@tochang .. 2434,	\SUF@tocindent@subsec
. 449, 453, 459,	2435, 2490, 2506 2609,
463, 472, 476, 480	\SUF@tochang@chap ..	2618, 2621,
\SUF@rightmark . 449,	... 2473, 2489,	2635, 2638, 2673
453, 459, 463,	2492, 2502, 2504,	\SUF@tocindent@subsubsec
2203, 2213, 2222	2523, 2525, 2531 2610,
\SUF@SEC@StyleSwitch	\SUF@tochang@fig ..	2620, 2623,
..... 303, 2479,	2637, 2640, 2682
305, 307, 1401, 1409	2501, 2590, 2592	\SUF@tocindent@tab .
\SUF@SUBSEC@StyleSwitch	\SUF@tochang@par 2614, 2628,
..... 311, 2477,	2645, 2712, 2714
313, 315, 1417, 1424	2497, 2500,	\SUF@toclabelnum ..
..... 319,	2572, 2574, 2577	. 362, 366, 370,
		374, 378, 382,

389, 393, 397,	\suftesi@dotteddoctrue	\suftesi@sufplaintrue
401, 405, 409,	579
416, 420, 424,	\suftesi@draftdatetrue	\suftesi@supercompactaureottrue
428, 432, 436,	670
2123, 2466, 2529,	\suftesi@elementschaptrue	\suftesi@supercompacttrue
2542, 2653, 2665	249
\SUF@tocSEC@font	\suftesi@elementsheadertrue	\suftesi@twocolumnloftrue
335, 337, 339, 2544,	467
2547, 2667, 2669	\suftesi@elementspagelayout	\suftesi@twocolumnlotttrue
\SUF@tocSUBSEC@font	186
..... 343,	\suftesi@fewfootnotesttrue	\suftesi@twocolumnoctrue
345, 347, 2555,	545
2558, 2677, 2679	\suftesi@FSPLtrue ..	. 592, 601, 605, 613
\SUF@tocSUBSUBSEC@font	T
..... 351,	\suftesi@greekfontfalse	\tableofcontents ..
353, 355, 2566,	2720,
2569, 2686, 2688	\suftesi@greekfonttrue	2763, 2845, 2846
\SUF@versionstring .	..	\temp 1217, 1220
..... 2163,	\suftesi@libertinetrue	\texorpdfstring .. 1982
2197, 2202, 2211	\textbullet 485
\SUFFntscale .. 1088,	\suftesi@MakeTextLowercase	\textcolor 1348
1091, 1094, 1108,	441, 443, 1319,	\textgreek 1190
1111, 1114, 1128,	1321, 1328, 1330	\textnormal ... 1357,
1131, 1134, 1150,	\suftesi@nocropttrue	1363, 1369, 1415,
1153, 1156, 1261– 664, 676	1422, 1430, 1437
1268, 1270–1272,	\suftesi@nofonttrue	\textsc ... 364, 376,
1275–1282, 1284–	622	391, 403, 418, 430
1286, 1289–	\suftesi@numparchaptrue	\textsf ... 2353, 2400
1295, 1297–1299 241, 244, 247	\textsuperscript ... 540
\suftesi@artemisiatrue	\suftesi@numparparttrue	\texttt 2163
..... 639 223, 226, 229	\thanks ... 459, 460,
\suftesi@articletrue	\suftesi@numparsectrue	463, 464, 1674,
..... 78, 89 261, 264, 267	1705, 1714, 1732,
\suftesi@authortitletrue	\suftesi@pagelefttocttrue	1760, 1772, 1818,
..... 458, 462	1830, 1872, 1953,
\suftesi@bodonitrue 643	\suftesi@palatinotrue	1964, 1969, 1980
\suftesi@cbgreektrue	\thearticle
..... 645	\suftesi@partpagetrue	... 1974, 1975,
\suftesi@centerheadertrue	1997, 1999, 2007
..... 452, 465	\suftesi@periodicalaureottrue	\thechapter 2133
\suftesi@cochinealtrue	.. 199, 883, 900, 918	\thecontentslabel ..
..... 624	\suftesi@periodicaltrue 2123,
\suftesi@collectiontrue	2466, 2529, 2543,
..... 81, 92	\suftesi@porsontrue	2554, 2565, 2576,
\suftesi@compactaureottrue	\suftesi@raggeddocttrue	2585, 2594, 2602,
..... 148	2653, 2666, 2676,
\suftesi@compacttrue	\suftesi@reverseauthortitletrue	2685, 2694,
..... 135	2701, 2708, 2715
\suftesi@compatibilitytrue	\suftesi@standardtrue	\thecontentspage ..
..... 632 2526, 2532,

2540, 2546, 2553,	\titleformat . . . 1340,	\useosf 1126, 1147
2557, 2564, 2568,	1355, 1361, 1367,	\useproportional . . 1148
2575, 2578, 2584,	1377, 1383, 1396,	
2587, 2593, 2601	1404, 1413, 1420,	
\thefootnote	1428, 1435, 1536,	\val 73,
. . . 1675, 1741,	1542, 1550, 1556,	84, 96, 213, 231,
1799, 1933, 2269	1564, 1571, 2134	251, 269, 277,
\thepage	\titlerule	285, 293, 301,
474, 478, 482, 2170	. . . 576, 577, 580, 581	309, 317, 325,
\theparagraph	\titlespacing . . 1360,	333, 341, 349,
. . . 1525, 1528,	1366, 1372, 1402,	357, 384, 411,
1566, 2032, 2035	1410, 1418, 1425,	438, 445, 469,
\thesection 1357,	1433, 1440, 1448,	488, 512, 519,
1399, 1407, 1519,	1452, 1456, 1460,	526, 542, 550,
1522, 2026, 2029	1464, 1468, 1472,	567, 573, 589,
\thesubparagraph . . .	1475, 1488, 1489,	619, 634, 647,
. . . 1527, 1573, 2034	1492, 1493, 1496,	654, 660, 667,
\thesubsection . . . 1363,	1497, 1500, 1501,	673, 682, 689,
1415, 1422, 1521,	1503, 1505, 1533,	937, 946, 952, 961
1524, 2028, 2031	1570, 1577, 2141	\valign 1035, 1037, 1048
\thesubsubsection	\toclabelspace	\version@string
. 1369,	. . . 2424, 2427, 2431 2157, 2163
1430, 1437, 1523,	\toclabelwidth	\versionstring 2157, 2158
1526, 2030, 2033	. . . 2418, 2428, 2432	
\title 1655–	\today 2163	X
1657, 1660, 1664,	\toks@ 1042, 1043	\xfootnote 2271
1883, 1885, 1886,	\tolerance 2279	\xheadbreak 2843
1889, 1893, 1960	\tw@ 1217, 1218, 1220, 1221	\xheadbreakfalse
\titleclass 1532	\twocolumn 1750, 1808,	. . . 2203, 2204,
\titlecontents 2101,	1942, 2083, 2085,	2213, 2214, 2847
2119, 2462, 2522,	2781, 2800, 2820	\xheadbreaktrue . . . 2842
2536, 2549, 2560,		\XKV@classoptionslist 1018
2571, 2580, 2589,	\unitlength . . . 1343, 2168	\XKV@useoption 1008–1017
2597, 2649, 2660,	\url 1869	
2672, 2681, 2690,		Y
2697, 2704, 2711	\usefont 1188	\year 2346, 2379