

tcolorbox 3.36

**tcolorbox**

tcolorbox 3.36

**Manual for  
version  
3.36  
(2015/01/09)**

tcolorbox 3.36

tcolorbox 3.36

**Thomas F. Sturm**

### Cover code

```
% \usepackage{incgraph}
\begin{inctext}
\begin{tikzpicture}
\definecolorseries{boxcol}{rgb}{last}{blue}{red}
\resetcolorseries[28]{boxcol}
\coordinate (A) at (0,0); \coordinate (B) at (21,29.7);
\path[use as bounding box] (A) rectangle coordinate (C) (B);
\node[transform shape,xslant=0.7,rotate=-10,xshift=0cm] at (C) {%
  \begin{tcbaster}[raster columns=4,title=tcolorbox \version,
    fonttitle=\small\bfseries,raster width=50cm]
  \foreach \b in {1,...,28} {\begin{tcolorbox}[enhanced,
    watermark text=\thetcbasternum,
    colframe=boxcol!30!white,
    colback=boxcol!25!white!30!white,
    colbacktitle=boxcol!!+!50!black!30!white,
    colupper=black!30!white]\lipsum[2]\end{tcolorbox}}
  \end{tcbaster}%
};
\node at (C) {%
  \begin{tcbitemize}[title=tcolorbox \version,fonttitle=\small\bfseries,
    enhanced jigsaw,opacityback=0.5,opacitybacktitle=0.75,
    center upper,valign=center,arc=5mm,
    raster width=16cm,raster column skip=8mm,raster halign=center,
    raster force size=false,
    raster row 1/.style={height=6cm},
    raster row 2/.style={width=6cm,height=4cm},
    raster column 1/.style={flushright title,
      frame style={left color=yellow!50!black,right color=green!50!black},
      title style={left color=yellow!50!blue,right color=blue!50!green!50!black},
      interior style={left color=yellow!70,right color=green!70},
      underlay={\draw[line width=6mm,line cap=round,black!60]
        ([shift={(0.4,-0.15)}]frame.north east)
        --([shift={(0.4,0.15)}]frame.south east);}},
    raster column 2/.style={
      frame style={left color=green!50!black,right color=yellow!50!black},
      title style={left color=blue!50!green!50!black,right color=yellow!50!blue},
      interior style={left color=green!70,right color=yellow!70}}]
  \tcbitem[fontupper=\Huge\bfseries,sharp corners=east,
    underlay={\draw[line width=6mm,line cap=round,black!60]
      ([shift={(0.4,0.30)}]frame.north east)-- coordinate(A) +(0,0.2);
      \draw[line width=1mm,line cap=round,black!60](A) -- +(30:1.5cm);
      \draw[line width=1mm,line cap=round,black!60](A) -- +(150:1.5cm);}]
    tcolorbox
  \tcbitem[fontupper=\large\bfseries,sharp corners=west]
    Manual for\ version\ \version\(\datum)
  \tcbitem[sharp corners=northeast]
  \tcbitem[sharp corners=northwest] Thomas F.~Sturm
  \end{tcbitemize}%
};
\end{tikzpicture}
\end{inctext}
```

# The tcolorbox package

Manual for version 3.36 (2015/01/09)

Thomas F. Sturm<sup>1</sup>


## Abstract

`tcolorbox` provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part. The package `tcolorbox` can be used for the setting of L<sup>A</sup>T<sub>E</sub>X examples where one part of the box displays the source code and the other part shows the output. Another common use case is the setting of theorems. The package supports saving and reuse of source code and text parts.

## Contents

<b>1</b>	<b>Introduction</b>	<b>7</b>
1.1	Installation . . . . .	7
1.2	Loading the Package . . . . .	7
1.3	Libraries . . . . .	8
<b>2</b>	<b>Quick Reference</b>	<b>10</b>
<b>3</b>	<b>Macros for Box Creation</b>	<b>11</b>
<b>4</b>	<b>Option Keys</b>	<b>17</b>
4.1	Title . . . . .	17
4.2	Subtitle . . . . .	20
4.3	Upper Part . . . . .	21
4.4	Lower Part . . . . .	22
4.5	Colors and Fonts . . . . .	25
4.6	Geometry . . . . .	28
4.7	Corners . . . . .	40
4.8	Transparency . . . . .	43
4.9	Height Control . . . . .	45
4.10	Box Content Additions . . . . .	52
4.11	Overlays . . . . .	61
4.12	Floating Objects . . . . .	66
4.13	Side by Side . . . . .	68
4.14	Embedding into the Surroundings . . . . .	72
4.15	Bounding Box . . . . .	76
4.16	Layered Boxes and Every Box Settings . . . . .	82
4.17	Capture Mode . . . . .	85
4.18	Text Characteristics . . . . .	86
4.19	Files . . . . .	87
4.20	<code>\tcbox</code> Specials . . . . .	87
4.21	Counters, Labels, and References . . . . .	88
4.22	Externalization . . . . .	90

<sup>1</sup>Prof. Dr. Dr. Thomas F. Sturm, Institut für Mathematik und Informatik, Universität der Bundeswehr München, D-85577 Neubiberg, Germany; email: [thomas.sturm@unibw.de](mailto:thomas.sturm@unibw.de)

4.23	Miscellaneous . . . . .	90
<b>5</b>	<b>Initialization Option Keys</b>	<b>92</b>
5.1	Numbered Boxes . . . . .	92
5.2	Lists of <code>tcolorboxes</code> . . . . .	97
<b>6</b>	<b>Saving and Loading of Verbatim Texts</b>	<b>98</b>
<b>7</b>	<b>Recording</b>	<b>99</b>
7.1	Makros . . . . .	99
7.2	Options . . . . .	99
7.3	Example: Exercises . . . . .	100
7.4	Example: Solutions . . . . .	103
<b>8</b>	<b>Technical Overview and Customization</b>	<b>105</b>
8.1	Skins and Drawing Engines . . . . .	105
8.2	Code Option Keys . . . . .	109
8.3	Subskins . . . . .	112
8.4	Drawing Scheme . . . . .	113
<b>9</b>	<b>Library  skins</b>	<b>117</b>
9.1	Style Option Keys . . . . .	117
9.2	Boxed Title Option Keys . . . . .	123
9.3	Watermark Option Keys . . . . .	130
9.4	Clip Environments . . . . .	137
9.5	Border Line Option Keys . . . . .	142
9.6	Shadow Option Keys . . . . .	147
9.7	TikZ Picture Option Keys . . . . .	156
9.8	Underlay Option Keys . . . . .	159
9.9	Finish Option Keys . . . . .	161
9.10	Jigsaw Skin Variants . . . . .	163
9.11	Draft Mode . . . . .	165
9.12	Skin Family 'standard' . . . . .	166
9.13	Skin Family 'enhanced' . . . . .	168
9.14	Skin Family 'bicolor' . . . . .	181
9.15	Skin Family 'beamer' . . . . .	186
9.16	Skin Family 'widget' . . . . .	191
9.17	Skin Family 'empty' . . . . .	195
9.18	Skin 'spartan' . . . . .	204
9.19	Skin 'draft' . . . . .	205
9.20	Skin Family 'freelance' . . . . .	207
<b>10</b>	<b>Inclusion of Boxed Image Files</b>	<b>208</b>
10.1	Macros . . . . .	208
10.2	Option Keys . . . . .	211
<b>11</b>	<b>TikZ Image and Picture Fill Extensions; Auxiliary Macros</b>	<b>212</b>
11.1	Fill Plain . . . . .	212
11.2	Fill Stretch . . . . .	213
11.3	Fill Overzoom . . . . .	214
11.4	Fill Zoom . . . . .	215
11.5	Fill Shrink . . . . .	216

11.6	Fill Tile	217
11.7	Filling Options	218
11.8	Extracting Node Dimensions	220
<b>12</b>	<b>Library <small>LIB</small> raster</b>	<b>221</b>
12.1	Concept of Rasters	221
12.2	Macros of the Library	223
12.3	Option Keys of the Library	225
12.4	Adding Styles for Specific Boxes	230
<b>13</b>	<b>Libraries <small>LIB</small> listings, <small>LIB</small> listingsutf8, and <small>LIB</small> minted</b>	<b>232</b>
13.1	Loading the Libraries	232
13.1.1	Loading <small>LIB</small> listings	232
13.1.2	Loading <small>LIB</small> listingsutf8	232
13.1.3	Loading <small>LIB</small> minted	233
13.2	Common Macros of the Libraries	233
13.3	Option Keys of the <small>LIB</small> listings Library	239
13.4	Option Keys of the <small>LIB</small> listingsutf8 Library	241
13.5	Option Keys of the <small>LIB</small> minted Library	242
13.6	Common Option Keys of all Libraries	244
13.7	Option Keys for Processing and Full Document Examples	252
13.8	Creation of L <sup>A</sup> T <sub>E</sub> X Tutorials	258
13.9	Creation of L <sup>A</sup> T <sub>E</sub> X Exercises	265
13.10	List of Exercises	268
13.11	Solutions for the given L <sup>A</sup> T <sub>E</sub> X Exercises	269
<b>14</b>	<b>Library <small>LIB</small> theorems</b>	<b>271</b>
14.1	Macros of the Library	271
14.2	Option Keys of the Library	275
14.3	Examples for Definitions and Theorems	288
14.4	Using other theorem environments with tcolorbox	293
<b>15</b>	<b>Library <small>LIB</small> breakable</b>	<b>294</b>
15.1	Technical Overview	294
15.2	Limitations and Known Bugs	295
15.3	Main Option Keys	296
15.4	Option Keys for the Break Appearance	300
15.5	Breakable boxes and the multicol package	302
15.6	Break Sequence for the Skins	305
15.7	Break by Hand (Faked Break)	313
<b>16</b>	<b>Library <small>LIB</small> fitting</b>	<b>314</b>
16.1	Macros of the Library	314
16.2	Option Keys of the Library	316
<b>17</b>	<b>Library <small>LIB</small> hooks</b>	<b>325</b>
17.1	Concept of Hooks	325
17.2	Box Content Additions	326
17.3	Embedding into the Surroundings	327
17.4	Overlays	328
17.5	Watermarks	330
17.6	Underlays	332




17.7	Finishes . . . . .	333
17.8	Skin Code . . . . .	333
<b>18</b>	<b>Library</b> <small>LIB</small> <b>xparse</b>	<b>335</b>
18.1	Option Keys . . . . .	335
18.2	Producing <code>tcolorbox</code> Environments and Commands . . . . .	337
18.3	Producing <code>tcbox</code> Commands . . . . .	340
18.4	Producing <code>tcblisting</code> Environments . . . . .	343
18.5	Producing <code>tcbinputlisting</code> Commands . . . . .	345
18.6	Producing <code>tboxfit</code> Commands . . . . .	346
<b>19</b>	<b>Library</b> <small>LIB</small> <b>documentation</b>	<b>348</b>
19.1	Macros of the Library . . . . .	348
19.2	Option Keys of the Library . . . . .	358
19.3	Predefined Colors of the Library . . . . .	364
<b>A</b>	<b>Picture Credits</b>	<b>365</b>
	<b>References</b>	<b>366</b>
	<b>Index</b>	<b>368</b>

# 1 Introduction

The package originates from the first edition of my book «*L<sup>A</sup>T<sub>E</sub>X – Einführung in das Textsatzsystem*» [19] in about 2006. For the L<sup>A</sup>T<sub>E</sub>X examples and tutorials given there, I wanted to have accentuated and colored boxes to display source code and compiled text in combination. Since, in my opinion, this type of boxes is also quite useful to highlight definitions and theorems, I applied them for my lecture notes in mathematics [16–18] as well. With this package, you are invited to apply these boxes for similar projects.

Starting with version 2.00, for all internal calculations  $\epsilon$ -T<sub>E</sub>X [2] expressions are used in replacement of the package `calc` [21]. The breaking news for version 2.00 is the support for breakable boxes. This new feature allows new applications of the package without affecting the core package too much if you do not need boxes to break automatically. With version 2.20, the often requested 'side by side' mode for listings has been added. With version 3.00, boxed titles are introduced together with improved customization options for overlays, underlays, finishes, and own code extensions.

Since the first public release in 2011, I received a lot of feedback from all over the world. I want to thank all who wrote me for supporting this package by sending bug reports and ideas for new or better features.



## 1.1 Installation

Typically, `tcolorbox` will be installed as part of a major L<sup>A</sup>T<sub>E</sub>X distribution and there is nothing special to do for a user.

If you intend to make a local installation *by hand*, see the `README` file of the `tcolorbox` package for some hints. The short story is: you have to install not only `tcolorbox.sty`, but also all `*.code.tex` files in the local `texmf` tree.

## 1.2 Loading the Package

The base package `tcolorbox` loads the packages `pgf` [20], `verbatim` [15], `etoolbox` [7], and `environ` [13]. `tcolorbox` itself is loaded in the usual manner in the preamble:

```
\usepackage{tcolorbox}
```

The package takes option keys in the key-value syntax. Alternatively, you may use these keys later in the preamble with `\tcboxuselibrary`<sup>→P.8</sup> (see there). For example, the key to typeset listings is:

```
\usepackage[listings]{tcolorbox}
```

### 1.3 Libraries

The base package `tcolorbox` is extendable by program libraries. This is done by using option keys while loading the package or inside the preamble by applying the following macro with the same set of keys.

```
\tcbuselibrary{<key list>}
```

Loads the libraries given by the `<key list>`.

```
\tcbuselibrary{listings,theorems}
```

The following keys are used inside `\tcbuselibrary` respectively `\usepackage` without the key tree path `/tcb/library/`.

`/tcb/library/skins`

(LIB skins)

Loads the package `tikz` [20] and provides additional styles (skins) for the appearance of the colored boxes; see Section 9 from page 117.

`/tcb/library/raster`

(LIB raster)

Provides additional macros and options for typesetting multiple boxes arranged in a kind of raster; see Section 12 from page 221.

`/tcb/library/listings`

(LIB listings)

Loads the package `listings` [6] and provides additional macros for typesetting listings which are described in Section 13 from page 232.

`/tcb/library/listingsutf8`

(LIB listingsutf8)

Loads the packages `listings` [6] and `listingsutf8` [10] for UTF-8 support. This is a variant of the library (LIB listings) and is described in Section 13 from page 232.

`/tcb/library/minted`

(LIB minted)

Loads the package `minted` [14] to typeset listings with the `Pygments` [12] tool, also see Section 13 on page 232.

`/tcb/library/theorems`

(LIB theorems)

Provides additional macros for typesetting theorems which are described in Section 14 from page 271.

`/tcb/library/breakable`

(LIB breakable)

Provides support for automatic box breaking from one page to another; see Section 15 from page 294.

`/tcb/library/fitting`

(LIB fitting)

Provides support for font size adaption of the box content to the box dimensions; see Section 16 from page 314.

`/tcb/library/hooks`

(LIB hooks)

Extends several option keys to 'hookable' keys; see Section 17 from page 325.

`/tcb/library/xparse`

(LIB xparse)

Provides document command production with `xparse` for `tcolorbox`; see Section 18 from page 335.

`/tcb/library/documentation`

(LIB documentation)

Provides additional macros for typesetting L<sup>A</sup>T<sub>E</sub>X documentations which are described in Section 19 from page 348.



**/tcb/library/many** (style, no value)


Loads the libraries `\lib skins`, `\lib breakable`, `\lib raster`, `\lib hooks`, `\lib theorems`, `\lib fitting`, and `\lib xparse`. Use this shortcut, if you want to use all features of `tcolorbox` with exception of typesetting listings and using the specialized `\lib documentation` library.

**/tcb/library/most** (style, no value)



Loads all libraries except `\lib minted` and `\lib documentation`. Use this shortcut, if you want to use all features of `tcolorbox` with exception of using the `minted` package and using the specialized `\lib documentation` library.

**/tcb/library/all** (style, no value)

Loads all libraries. Use this shortcut only, if you intend to use the `\lib documentation` library.



## 2 Quick Reference



### 3 Macros for Box Creation

```
\begin{tcolorbox}[\langle options \rangle]  
  \langle environment content \rangle  
\end{tcolorbox}
```

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts. The appearance of this box is controlled by numerous options. In the most simple case the source code

```
\begin{tcolorbox}  
  This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

creates the following compiled text box:

This is a **tcolorbox**.

The text content of the box can be divided in an upper and a lower part by the command `\tcblower`. Visually, both parts are separated by a line. For example:

```
\begin{tcolorbox}  
  This is another \textbf{tcolorbox}.  
  \tcblower  
  Here, you see the lower part of the box.  
\end{tcolorbox}
```

This code gives the following box:

This is another **tcolorbox**.

---

Here, you see the lower part of the box.

The `\langle options \rangle` control the appearance and several functions of the boxes, see Section 4 on page 17 for the complete list. A quick example is given here:

```
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,title=My nice heading]  
  This is another \textbf{tcolorbox}.  
  \tcblower  
  Here, you see the lower part of the box.  
\end{tcolorbox}
```

My nice heading

This is another **tcolorbox**.

---

Here, you see the lower part of the box.

#### `\tcblower`

Used inside `tcolorbox` to separate the upper box part from the optional lower box part. The upper and the lower part are treated as separate functional units. If you only want to draw a line, see `\tcblines`<sup>→ P. 171</sup>.

**`\tcbset{⟨options⟩}`**

Sets options for every following `tcolorbox`<sup>→P.11</sup> inside the current TeX group. By default, this does not apply to nested boxes, see Section 4.16 on page 82.

For example, the colors of the boxes may be defined for the whole document by this:

```
\tcbset{colback=red!5!white,colframe=red!75!black}
```

**`\tcbsetforeverylayer{⟨options⟩}`**

Sets options for every following `tcolorbox`<sup>→P.11</sup> inside the current TeX group. In contrast to `\tcbset`, this does also apply to nested boxes, see Section 4.16 on page 82. Technically, the `⟨options⟩` are appended to the default values for every `tcolorbox` which are applied by `/tcb/reset`<sup>→P.90</sup>.

You should not use this macro, if you are not completely sure that you want to have the `⟨options⟩` also for boxes in boxes (in boxes in boxes ...).

```
\tcbset{colback=green!10!white}
\tcbsetforeverylayer{colframe=red!75!black}

\begin{tcolorbox}[title=All options for this box]
  This is a tcolorbox.\par\medskip
  \begin{tcolorbox}[title=Nested box]
    Note that this nested box has a red frame but no green background.
  \end{tcolorbox}
\end{tcolorbox}
\bigskip

\begin{tcolorbox}[reset]
  Options given with |\tcbsetforeverylayer| survive a |reset|.
\end{tcolorbox}
```

All options for this box

This is a tcolorbox.

Nested box

Note that this nested box has a red frame but no green background.

Options given with `\tcbsetforeverylayer` survive a `reset`.

`\tcbox[<options>]{<box content>}`

Creates a colored box which is fitted to the width of the given *<box content>*. In principal, most *<options>* for a `\tcolorbox`<sup>P.11</sup> can be used for `\tcbox` with some restrictions. A `\tcbox` cannot have a lower part and cannot be broken.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
fonttitle=\bfseries,nobeforeafter,center title}

Text \tcbox[tcbbox raise base]{Hello World}\hfill
%
\tcbbox[left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=0mm,
toptitle=0.5mm,bottomtitle=0.5mm,title=My table]{%
\arrayrulecolor{blue!50!black}\renewcommand{\arraystretch}{1.2}%
\begin{tabular}{r|c|l}
One & Two & Three \\ \hline
Men & Mice & Lions \\ \hline
Upper & Middle & Lower
\end{tabular}}\hfill
%
\tcbbox[colback=blue!85!black,
left=0mm,right=0mm,top=0mm,bottom=0mm,boxsep=1mm,arc=0mm,boxrule=0.5pt,
title=My picture]{%
\includegraphics[width=5cm]{Basilica_5.png}}
```


Text

Hello World

My table

One	Two	Three
Men	Mice	Lions
Upper	Middle	Lower

My picture



```
% \usepackage{tikz}
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
fonttitle=\bfseries,center title}

% Fixed width box
\begin{tcolorbox}Hello\World!\end{tcolorbox}

% Fitted width box (like hbox or makebox)
\tcbbox{Hello\World!}

% Fitted width box (using a \tikzname\ node)
\tcbbox[tikznode]{Hello\World!}
```

Hello  
World!

HelloWorld!

Hello  
World!

See Section 18.2 on page 337 and Section 18.3 on page 340 for more elaborate methods to create new environments and commands.

**`\newtcolorbox`** $\langle\textit{init options}\rangle\{\langle\textit{name}\rangle\}[\langle\textit{number}\rangle][\langle\textit{default}\rangle]\{\langle\textit{options}\rangle\}$

Creates a new environment  $\langle\textit{name}\rangle$  based on `tcolorbox`<sup>P.11</sup>. Basically, `\newtcolorbox` operates like `\newenvironment`. This means, the new environment  $\langle\textit{name}\rangle$  optionally takes  $\langle\textit{number}\rangle$  arguments, where  $\langle\textit{default}\rangle$  is the default value for the optional first argument. The  $\langle\textit{options}\rangle$  are given to the underlying `tcolorbox`. Note that `/tcb/savedelimiter`<sup>P.24</sup> is set to the given  $\langle\textit{name}\rangle$  automatically. The  $\langle\textit{init options}\rangle$  allow setting up automatic numbering, see Section 5 from page 92.

```
\newtcolorbox{mybox}{colback=red!5!white,
colframe=red!75!black}
```

```
\begin{mybox}
This is my own box.
\end{mybox}
```

This is my own box.

```
\newtcolorbox{mybox}[1]{colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries,
title=#1}
```

```
\begin{mybox}{Hello there}
This is my own box with a mandatory title.
\end{mybox}
```

**Hello there**

This is my own box with a mandatory title.

```
\newtcolorbox{mybox}[2][\colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries,
colbacktitle=red!85!black,enhanced,
attach boxed title to top center={yshift=-2mm},
title=#2,#1}
```

```
\begin{mybox}[colback=yellow]{Hello there}
This is my own box with a mandatory title
and options.
\end{mybox}
```

**Hello there**

This is my own box with a mandatory title and options.

*Definition in the preamble:*

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][\colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[colback=yellow]{Hello there}
This is my own box with a mandatory
numbered title and options.
\end{pabox}
```

**Examp. 3.1: Hello there**

This is my own box with a mandatory numbered title and options.

**`\renewtcolorbox`** $\langle\textit{init options}\rangle\{\langle\textit{name}\rangle\}[\langle\textit{number}\rangle][\langle\textit{default}\rangle]\{\langle\textit{options}\rangle\}$

Operates like `\newtcolorbox`, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.



**\newtcbox**[*<init options>*]{*<name>*}[*<number>*][*<default>*]{*<options>*}

Creates a new macro *<name>* based on *\tcbox*<sup>P.13</sup>. Basically, *\newtcbox* operates like *\newcommand*. The new macro *<name>* optionally takes *<number>*+1 arguments, where *<default>* is the default value for the optional first argument. The *<options>* are given to the underlying *tcbox*. The *<init options>* allow setting up automatic numbering, see Section 5 from page 92.

```
\newtcbox{\mybox}{colback=red!5!white,
colframe=red!75!black}
```

```
\mybox{This is my own box.}
```

This is my own box.

```
\newtcbox{\mybox}[1]{colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries,
title=#1}
```

```
\mybox{Hello there}{This is my own box.}
```

Hello there

This is my own box.

```
\newtcbox{\mybox}[2][ ]{colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries,
title=#2,#1}
```

```
\mybox[colback=yellow]{Hello there}%
{This is my own box.}
```

Hello there

This is my own box.

*Definition in the preamble:*

*% counter from previous example*

```
\newtcbox[use counter from=pabox]{\pbbbox}[2][ ]{%
colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
title=(\thetcbcounter) #2,#1}
```

```
\pbbbox[colback=yellow]{Hello there}%
{This is my own box.}
```

(3.2) Hello there

This is my own box.

```
\newtcbox{\mybox}[1][red]{on line,
arc=0pt,outer arc=0pt,colback=#1!10!white,colframe=#1!50!black,
boxsep=0pt,left=1pt,right=1pt,top=2pt,bottom=2pt,
boxrule=0pt,bottomrule=1pt,toprule=1pt}
```

```
\newtcbox{\xmybox}[1][red]{on line,
arc=7pt,colback=#1!10!white,colframe=#1!50!black,
before upper={\rule[-3pt]{0pt}{10pt}},boxrule=1pt,
boxsep=0pt,left=6pt,right=6pt,top=2pt,bottom=2pt}
```

The *\mybox*[green]{quick} brown *\mybox*{fox} *\mybox*[blue]{jumps} over the  
*\mybox*[green]{lazy} *\mybox*{dog}. *\par*  
The *\xmybox*[green]{quick} brown *\xmybox*{fox} *\xmybox*[blue]{jumps} over the  
*\xmybox*[green]{lazy} *\xmybox*{dog}.

The quick brown fox jumps over the lazy dog.

The quick brown fox jumps over the lazy dog.

**\renewtcbox**[*<init options>*]{*<name>*}[*<number>*][*<default>*]{*<options>*}

Operates like *\newtcbox*, but based on *\renewcommand* instead of *\newcommand*. An existing macro is redefined.

**\tcolorboxenvironment**{ $\langle name \rangle$ }{ $\langle options \rangle$ }

An existing environment  $\langle name \rangle$  is redefined to be boxed inside a `tcolorbox` with the given  $\langle options \rangle$ .

```
% tcbuselibrary{skins}
\newenvironment{myitemize}{%
  \begin{itemize}}{\end{itemize}}

\tcolorboxenvironment{myitemize}{blanker,
  before skip=6pt,after skip=6pt,
  borderline west={3mm}{0pt}{red}}

Some text.
\begin{myitemize}
\item Alpha
\item Beta
\item Gamma
\end{myitemize}
More text.
```

Some text.

- Alpha
- Beta
- Gamma

More text.

See further examples in Section 14.4 on page 293.

## 4 Option Keys

For the  $\langle options \rangle$  in `tcolorbox`<sup>P.11</sup> respectively `\tcbset`<sup>P.12</sup> the following pgf keys can be applied. The key tree path `/tcb/` is not to be used inside these macros. It is easy to add your own style keys using the syntax for pgf keys, see [19, 20] or the examples starting from page 258.

### 4.1 Title

`/tcb/title= $\langle text \rangle$`  (no default, initially empty)  
Creates a heading line with  $\langle text \rangle$  as content.

```
\begin{tcolorbox}[title=My heading line]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My heading line

This is a **tcolorbox**.

`/tcb/notitle` (no value, initially set)  
Removes the title line if set before.

`/tcb/adjusted title= $\langle text \rangle$`  (style, no default, initially unset)  
Creates a heading line with  $\langle text \rangle$  as content. The minimal height of this line is adjusted to fit the text given by `/tcb/adjust text`. This option makes sense for single line headings if boxes are set side by side with equal height. Note that it is very easy to trick this adjustment.

```
\tcbset{colback=White,arc=0mm,width=(\linewidth-4pt)/4,
equal height group=AT,before=,after=\hfill,fonttitle=\bfseries}
```

```
The following titles are not adjusted:\\
\foreach \n in {xxx,ggg,AAA,\"Ägypten}
{\begin{tcolorbox}[title=\n,colframe=red!75!black]
Some content.\end{tcolorbox}}
Now, we try again with adjusted titles:\\
\foreach \n in {xxx,ggg,AAA,\"Ägypten}
{\begin{tcolorbox}[adjusted title=\n,colframe=blue!75!black]
Some content.\end{tcolorbox}}
```

The following titles are not adjusted:

xxx	ggg	AAA	Ägypten
Some content.	Some content.	Some content.	Some content.

Now, we try again with adjusted titles:

xxx	ggg	AAA	Ägypten
Some content.	Some content.	Some content.	Some content.

`/tcb/adjust text= $\langle text \rangle$`  (no default, initially `\pgjy`)

This sets the reference text for `/tcb/adjusted title`. If your texts never exceed '`\pgjy`' in depth and height you don't need to care about this option.

**/tcb/squeezed title**= $\langle text \rangle$  (style, no default, initially unset)

Creates a single heading line with  $\langle text \rangle$  as content. If the  $\langle text \rangle$  is longer than the available space, the text is squeezed to fit into the available space.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title={Short title}]
  First box
\tcbitem[squeezed title={This is a very very long title}]
  Second box
\tcbitem[squeezed title={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```

Short title	This is a very very long title	This title is clearly to long for this application
First box	Second box	Third box

**/tcb/squeezed title\***= $\langle text \rangle$  (style, no default, initially unset)

This is a combination of `/tcb/adjusted title`<sup>→P. 17</sup> and `/tcb/squeezed title`.

```
% \tcbuselibrary{raster}
\begin{tcbitemize}[raster columns=3,raster equal height,
  colframe=red!75!black,colback=red!5!white,fonttitle=\bfseries]
\tcbitem[squeezed title*={Short title}]
  First box
\tcbitem[squeezed title*={This is a very very long title}]
  Second box
\tcbitem[squeezed title*={This title is clearly to long for this application}]
  Third box
\end{tcbitemize}
```


Short title	This is a very very long title	This title is clearly to long for this application
First box	Second box	Third box

`/tcb/detach title` (no value)

Detaches the title from its normal position. The text of the title is stored into `\tcbtitletext` and the formatted title is available by `\tcbtitle`. The main application is to move the title from its usual place to another one.

```
\newtcolorbox{mybox}[2][\colbacktitle=red!10!white,
colback=blue!10!white,coltitle=red!70!black,
title={#2},fonttitle=\bfseries,#1]

\begin{mybox}{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[detach title,before upper={\tcbtitle\quad}]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[detach title,after upper={\par\hfill\tcbtitle}]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



`/tcb/attach title` (no value)


Attaches the title to its normal position. This option is used to reverse `/tcb/detach title`.

`/tcb/attach title to upper=<text>` (style, default empty, initially unset)

Attaches the title to the begin of the upper part of the box content. The optional `<text>` is set between the formatted title and the box content.

```
\newtcolorbox{mybox}[2][\colbacktitle=red!10!white,
colback=blue!10!white,coltitle=red!70!black,
title={#2},fonttitle=\bfseries,#1]

\begin{mybox}[attach title to upper={\ ---\ }]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
\begin{mybox}[attach title to upper,after title={:\ }]{My title}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



More title options are documented in Section 4.10 on page 52 and Section 9.2 on page 123.

## 4.2 Subtitle

Inside the box content, one or more subtitles can be added. In general, a subtitle is a further `tcolorbox`<sup>→P.11</sup> which inherits some color and geometry options from the enclosing box. It may be customized just like any other `tcolorbox`<sup>→P.11</sup>.

N 2014-10-10

`\tcbsubtitle[⟨options⟩]{⟨text⟩}`

Used inside a `tcolorbox`<sup>→P.11</sup> to add a subtitle box with the given *⟨text⟩*. This is an independent `tcolorbox`<sup>→P.11</sup> which is formatted by several inherited properties of the enclosing box, by further settings from `/tcb/subtitle` style, and by the given *⟨options⟩*.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
  \tcbsubtitle[before skip=\baselineskip]%
    {My subtitle}
    Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  colbacktitle=yellow!50!red,
  coltitle=red!25!black,
  fonttitle=\bfseries]
  This is a \textbf{tcolorbox}.
  \tcbsubtitle[before skip=\baselineskip]%
    {My subtitle}
    Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

N 2014-10-10

`/tcb/subtitle style=⟨options⟩`

(no default, initially empty)

Adds `tcolorbox` *⟨options⟩* to the settings for `\tcbsubtitle`.

```
\begin{tcolorbox}[title=My title,
  colback=red!5!white,
  colframe=red!75!black,
  colbacktitle=yellow!50!red,
  coltitle=red!25!black,
  fonttitle=\bfseries,
  subtitle style={boxrule=0.4pt,
    colback=yellow!50!red!25!white} ]
  This is a \textbf{tcolorbox}.
  \tcbsubtitle{My subtitle}
    Further text.
  \tcbsubtitle{Second subtitle}
    Further text.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My subtitle

Further text.

Second subtitle

Further text.



### 4.3 Upper Part

The text content of a `tcolorbox`<sup>→P.11</sup> may be parted into a mandatory *upper part* and an optional *lower part*. These parts are separated by `\tcblower`<sup>→P.11</sup>. If there is no `\tcblower`<sup>→P.11</sup> present, there is no *lower part* and the *upper part* forms the complete text content.

N 2015-01-06

`/tcb/upperbox=<mode>` (no default, initially **visible**)

Controls the treatment of the upper part of the box. If there is no lower part, this is the complete text content. Feasible values for `<mode>` are:

- **visible**: usual type setting of the upper part,
- **invisible**: empty space instead of the uooyer part contents.

```
\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}
```

`\bigskip`

```
\begin{tcolorbox}[upperbox=invisible,colback=white]
This is a \textbf{tcolorbox} (but invisible).
\tcblower
This is the lower part.
\end{tcolorbox}
```



N 2015-01-06

`/tcb/visible` (style, no value)

Shortcut for setting `/tcb/upperbox` and `/tcb/lowerbox`<sup>→P.22</sup> to be **visible**.

N 2015-01-06

`/tcb/invisible` (style, no value)

Shortcut for setting `/tcb/upperbox` and `/tcb/lowerbox`<sup>→P.22</sup> to be **invisible**.

```
\begin{tcolorbox}[invisible]
This is a \textbf{tcolorbox} (but invisible).
\end{tcolorbox}
```



## 4.4 Lower Part

`/tcb/lowerbox=<mode>` (no default, initially **visible**)

Controls the treatment of the lower part of the box. Feasible values for  $\langle mode \rangle$  are:

- **visible**: usual type setting of the lower part,
- **invisible**: empty space instead of the lower part contents,
- **ignored**: the lower part is not used (here).

The last two values are usually applied in connection with `savelowerto`.

```
\begin{tcolorbox}[lowerbox=invisible,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but invisible).
\end{tcolorbox}

\begin{tcolorbox}[lowerbox=ignored,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part (but ignored).
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

U 2014-11-28

`/tcb/savelowerto=<file name>` (no default, initially empty)

Saves the content of the lower part in a file for an optional later usage.

```
\begin{tcolorbox}[lowerbox=invisible,savelowerto=\jobname_bsp save.tex,colback=white]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part which may be quite complex:

$$f(x)=\frac{1+x^2}{1-x^2}$$

\end{tcolorbox}

Now, we load the saved text:\\
\input{\jobname_bsp save.tex}
```

This is a **tcolorbox**.

Now, we load the saved text:

This is the lower part which may be quite complex:  $f(x) = \frac{1+x^2}{1-x^2}$ .

`/tcb/lower separated=true|false` (default `true`, initially `true`)

If set to `true`, the lower part is visually separated from the upper part. It depends on the chosen skin how the visualization of the separation is done.

```
% \tcbuselibrary{skins,raster}
\begin{tcbrafter}[colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,fontlower=\itshape]
%
\begin{tcolorbox}[title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[sidebyside,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower separated]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
%
\begin{tcolorbox}[beamer,title=Lower not separated,lower separated=false]
This is the upper part.
\tcblower
This is the lower part.
\end{tcolorbox}
\end{tcbrafter}
```

#### Lower separated

This is the upper part.

*This is the lower part.*

#### Lower not separated

This is the upper part.

*This is the lower part.*

#### Lower separated

This is the upper  
part.

*This is the lower  
part.*

#### Lower not separated

This is the upper  
part.

*This is the lower  
part.*

#### Lower separated

This is the upper part.

*This is the lower part.*

#### Lower not separated

This is the upper part.

*This is the lower part.*

`/tcb/savedelimiter=<name>` (no default, initially `tcolorbox`)

Used in connection with new environment definitions which extend `tcolorbox` and use or allow the option `savelowerto`. To catch the end of the new box environment `<name>` has to be the name of this environment. Additionally, the environment definition has to use `\tcolorbox` instead of `\begin{tcolorbox}` and `\end{tcolorbox}` instead of `\end{tcolorbox}`.

```
\newenvironment{mybox}[1]{%
  \tcolorbox[savedelimiter=mybox,
    savelowerto=\jobname_bspsave2.tex,lowerbox=ignored,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=#1]{}%
  {\end{tcolorbox}}

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bspsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

The `savedelimiter` is used implicitly with `\newtcolorbox`<sup>P.14</sup> which allows a more convenient usage:

```
\newtcolorbox{mybox}[1]{%
  savelowerto=\jobname_bspsave2.tex,lowerbox=ignored,
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=#1}%

\begin{mybox}{My Example}
Upper part.
\tcblower
Saved lower part!
\end{mybox}

Now, the saved part is used:
\begin{tcolorbox}[colback=green!5]
\input{\jobname_bspsave2.tex}
\end{tcolorbox}
```

My Example

Upper part.

Now, the saved part is used:

Saved lower part!

## 4.5 Colors and Fonts

**/tcb/colframe**= $\langle color \rangle$  (no default, initially black!75!white)

Sets the frame  $\langle color \rangle$  of the box.

```
\begin{tcolorbox}[colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**/tcb/colback**= $\langle color \rangle$  (no default, initially black!5!white)

Sets the background  $\langle color \rangle$  of the box.

```
\begin{tcolorbox}[colback=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**/tcb/title filled**=true|false (default true, initially false)

Switches the drawing of the title background according to the given value. This option is set to true automatically by **/tcb/colbacktitle**, **/tcb/opacitybacktitle**<sup>→ P. 43</sup>, and **/tcb/title style**<sup>→ P. 120</sup>, and **/tcb/title code**<sup>→ P. 111</sup>.

```
\begin{tcolorbox}[title=My title,title filled]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[title=My title,
title filled=false]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

My title

This is a **tcolorbox**.

**/tcb/colbacktitle**= $\langle color \rangle$  (no default, initially black!50!white)

Sets the background  $\langle color \rangle$  of the title area of the box.

```
\begin{tcolorbox}[colbacktitle=red!50!white,
title=My title,coltitle=black,
fonttitle=\bfseries]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

**My title**

This is a **tcolorbox**.

**/tcb/colupper**= $\langle color \rangle$  (no default, initially black)

Sets the text  $\langle color \rangle$  of the upper part.

```
\begin{tcolorbox}[colupper=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

-----  
This is the lower part.

**/tcb/collower**= $\langle color \rangle$  (no default, initially black)

Sets the text  $\langle color \rangle$  of the lower part.

```
\begin{tcolorbox}[collower=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

-----  
This is the lower part.

**/tcb/coltext**= $\langle color \rangle$  (style, no default, initially black)

Sets the text  $\langle color \rangle$  of the box. This is an abbreviation for setting **colupper** and **collower** to the same value.

```
\begin{tcolorbox}[coltext=red!75!black]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

-----  
This is the lower part.

**/tcb/coltitle**= $\langle color \rangle$  (no default, initially white)

Sets the title text  $\langle color \rangle$  of the box.

```
\begin{tcolorbox}[coltitle=red!75!black,
colbacktitle=black!10!white,title=Test]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Test

-----  
This is a **tcolorbox**.



`/tcb/fontupper=<text>` (no default, initially empty)

Sets `<text>` before the content of the upper part (e.g. font settings).

```
\begin{tcolorbox}[fontupper=Hello!\sffamily]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Hello! This is a **tcolorbox**.

`/tcb/fontlower=<text>` (no default, initially empty)

Sets `<text>` before the content of the lower part (e.g. font settings).

```
\begin{tcolorbox}[fontlower=\sffamily\bfseries]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

-----  
**This is the lower part.**

`/tcb/fonttitle=<text>` (no default, initially empty)

Sets `<text>` before the content of the title text (e.g. font settings).

```
\begin{tcolorbox}[fonttitle=\sffamily\bfseries\large,title=Hello]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

**Hello**

This is a **tcolorbox**.

More color options are provided by using skins documented in Section 9 from page 117.

## 4.6 Geometry

**/tcb/width=** $\langle length \rangle$  (no default, initially `\linewidth`)

Sets the total width of the colored box to  $\langle length \rangle$ . See also `/tcb/height`<sup>→ P. 45</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=\linewidth/2]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

N 2014-10-31

**/tcb/text width=** $\langle length \rangle$  (style, no default)

Sets the text width of the upper part to  $\langle length \rangle$ . See also `/tcb/text height`<sup>→ P. 46</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text width=4cm]
This is a \textbf{tcolorbox} where the text has a width of 4cm.
\end{tcolorbox}
```

This is a **tcolorbox** where  
the text has a width of 4cm.

N 2014-11-07

**/tcb/add to width=** $\langle length \rangle$  (style, no default)

Adds  $\langle length \rangle$  to the current total width of the colored box.

```
\tcbset{width=4cm,colback=red!5!white,
colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[add to width=1cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

`/tcb/toprule=<length>` (no default, initially 0.5mm)

Sets the line width of the top rule to  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toprule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/bottomrule=<length>` (no default, initially 0.5mm)

Sets the line width of the bottom rule to  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/leftrule=<length>` (no default, initially 0.5mm)

Sets the line width of the left rule to  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/rightrule=<length>` (no default, initially 0.5mm)

Sets the line width of the right rule to  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[rightrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/titlerule=<length>` (no default, initially 0.5mm)

Sets the line width of the rule below the title to  $\langle length \rangle$ .

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,
colbacktitle=red!90!black}

\begin{tcolorbox}[titlerule=3mm,title=This is the title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/boxrule=<length>` (style, no default, initially 0.5mm)

Sets all rules of the frame to  $\langle length \rangle$ , i.e. `/tcb/toprule`<sup>→ P. 29</sup>, `/tcb/bottomrule`<sup>→ P. 29</sup>, `/tcb/leftrule`<sup>→ P. 29</sup>, `/tcb/rightrule`<sup>→ P. 29</sup>, and `/tcb/titlerule`.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[boxrule=3mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



More options for drawing a `/tcb/borderline`<sup>→ P. 142</sup> are provided by using skins documented in Section 9 from page 117.

`/tcb/arc=<length>` (no default, initially 1mm)

Sets the inner radius of the four frame arcs to  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[arc=0mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[arc=4mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

`/tcb/outer arc=<length>` (no default, initially unset)

Sets the outer radius of the four frame arcs to  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[arc=4mm,outer arc=1mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/auto outer arc` (no value, initially set)

Sets the outer radius of the four frame arcs automatically in dependency of the inner radius given by `/tcb/arc`.

`/tcb/boxsep=<length>` (no default, initially 1mm)

Sets a common padding of  $\langle length \rangle$  between the text content and the frame of the box. This value is added to the key values of `left`, `right`, `top`, `bottom`, and `middle` at the appropriate places.

```
\tcbset{colback=red!5!white,colframe=red!75!black,width=(\linewidth-4mm)/2,
before=,after=\hfill}

\begin{tcolorbox}[boxsep=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[boxsep=5mm,draft]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

frame: w=195.33255pt, h=48.97505pt

upper: w=115.2724pt, h=6.296pt

interior: w=192.4873pt, h=46.1298pt

`/tcb/left=<length>` (style, no default, initially 4mm)

Sets the left space between all text parts and frame (additional to `boxsep`). This is an abbreviation for setting `lefttitle`, `leftupper`, and `leftlower` to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[left=0mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/lefttitle=<length>` (no default, initially 4mm)

Sets the left space between title text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[lefttitle=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

`/tcb/leftupper=<length>` (no default, initially 4mm)

Sets the left space between upper text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftupper=3cm,title=My Title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My Title

This is a **tcolorbox**.

`/tcb/leftlower=<length>` (no default, initially 4mm)

Sets the left space between lower text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[leftlower=3cm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.



**/tcb/right**= $\langle length \rangle$  (style, no default, initially 4mm)

Sets the right space between all text parts and frame (additional to **boxsep**). This is an abbreviation for setting **righttitle**, **rightupper**, and **rightlower** to the same value.

```
\tcbset{colback=red!5!white,colframe=red!75!black}
```

```
\begin{tcolorbox}[width=5cm,right=2cm]
```

```
This is a \textbf{tcolorbox}.
```

```
\end{tcolorbox}
```

This is a **tcolorbox**.

**/tcb/righttitle**= $\langle length \rangle$  (no default, initially 4mm)

Sets the right space between title text and frame (additional to **boxsep**).

```
\tcbset{colback=red!5!white,colframe=red!75!black}
```

```
\begin{tcolorbox}[width=5cm,righttitle=2cm,title=My very long title text]
```

```
This is a \textbf{tcolorbox} with standard upper box dimensions.
```

```
\end{tcolorbox}
```

My very long title text

This is a **tcolorbox** with standard upper box dimensions.

**/tcb/rightupper**= $\langle length \rangle$  (no default, initially 4mm)

Sets the right space between upper text and frame (additional to **boxsep**).

```
\tcbset{colback=red!5!white,colframe=red!75!black}
```

```
\begin{tcolorbox}[width=5cm,rightupper=2cm,title=My very long title text]
```

```
This is a \textbf{tcolorbox} with compressed upper box dimensions.
```

```
\end{tcolorbox}
```

My very long title text

This is a **tcolorbox** with compressed upper box dimensions.

`/tcb/rightlower=<length>` (no default, initially 4mm)

Sets the right space between lower text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[width=5cm,rightlower=2cm]
This is a \textbf{tcolorbox} with standard upper box dimensions.
\tcblower
This is the lower part with large space at right.
\end{tcolorbox}
```

This is a **tcolorbox** with standard upper box dimensions.

This is the lower part with large space at right.

`/tcb/top=<length>` (no default, initially 2mm)

Sets the top space between text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[top=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

`/tcb/toptitle=<length>` (no default, initially 0mm)

Sets the top space between title and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[toptitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/bottom=<length>` (no default, initially 2mm)

Sets the bottom space between text and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottom=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

-----  
This is the lower part.

`/tcb/bottomtitle=<length>` (no default, initially 0mm)

Sets the bottom space between title and frame (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[bottomtitle=3mm,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/middle=<length>` (no default, initially 2mm)

Sets the space between upper and lower text to the separation line (additional to `boxsep`).

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[middle=0mm,boxsep=0mm]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

-----  
This is a **tcolorbox**.  
-----  
This is the lower part.

`/tcb/size=<name>` (no default, initially `normal`)

Sets all geometry keys with exception of `/tcb/width` <sup>P.28</sup> to predefined length values. For `<name>`, the following values are feasible:


- **normal**: normal sized boxes e.g. of width `\linewidth`.
- **title**: title line sized boxes.
- **small**: small boxes e.g. for keyword highlighting.
- **fbox**: identical to the standard `\fbox`.
- **tight**: no padding space at all.
- **minimal**: no padding space, no box rules.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\foreach \s in {minimal,tight,fbox,small,title,normal} {
  \tcbbox[size=\s,on line]{\s} }

\foreach \s in {minimal,tight,fbox,small,title,normal} {
  \tcbbox[size=\s,on line,title=Test]{\s} }

\foreach \s in {minimal,tight,fbox,small,title,normal} {
  \begin{tcolorbox}[size=\s,on line,title=Test,width=2.2cm]
    \s \tcblower lower\end{tcolorbox} }
```



Predefined values						
	normal	title	small	fbox	tight	minimal
boxrule	0.5mm	0.4mm	0.3mm	0.4pt	0.4pt	0.0pt
boxsep	1.0mm	1.0mm	1.0mm	3.0pt	0.0pt	0.0pt
left	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
right	4.0mm	2.0mm	1.0mm	0.0pt	0.0pt	0.0pt
top	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
bottom	2.0mm	0.25mm	0.0mm	0.0pt	0.0pt	0.0pt
toptitle	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
bottomtitle	0.0mm	0.0mm	0.0mm	0.0pt	0.0pt	0.0pt
middle	2.0mm	0.75mm	0.5mm	1.0pt	0.2pt	0.0pt
arc	1.0mm	0.75mm	0.5mm	1.0pt	0.0pt	0.0pt
outer arc	auto	auto	auto	auto	0.0pt	0.0pt

`/tcb/oversize=<length>` (style, default 0pt)

Sets the text width of the upper part to the current line width plus an optional `<length>`. This is achieved by changing the keys `/tcb/width`<sup>P.28</sup> `/tcb/enlarge left by`<sup>P.77</sup>, and `/tcb/enlarge right by`<sup>P.77</sup> appropriately. The resulting box is overlapping into the left and right margin of the page. Note that this style option has to be given *after* all other geometry keys!

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\textit{Normal text for comparison:}\
\lipsum[2]

\begin{tcolorbox}[oversize,title=Oversized box]
\lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[title=Normal box]
\lipsum[2]
\end{tcolorbox}
```

*Normal text for comparison:*

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

### Oversized box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

### Normal box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/toggle left and right=<toggle preset>` (default `evenpage`, initially `none`)

According to the `<toggle preset>`, the left and the right settings of the `tcolorbox` are switched or not. Feasible values are:

- **none**: no switching.
- **forced**: the values of the left and right rules and spaces are switched.
- **evenpage**: if the page is an even page, the values of the left and right rules and spaces are switched. It is recommended that one use this setting in conjunction with `/tcb/check odd page` <sup>→ P. 89</sup>.

```
% \usepackage{changepage} for 'check odd page'
% \usepackage{lipsum}
% \usetikzlibrary{patterns}
% \tcbuselibrary{skins,breakable}
\begin{tcolorbox}[skin=enhancedmiddle,breakable,
  check odd page,toggle left and right,
  boxrule=0mm,top=0mm,bottom=0mm,left=1mm,right=1mm,
  rightrule=1cm,colupper=blue!25!black,
  interior style={fill overzoom image=lichtspiel.jpg,fill image opacity=0.25},
  frame style={pattern=crosshatch dots light steel blue},
  overlay={%
    \ifoddpage\coordinate (X) at ([xshift=-5mm]frame.east);
    \else\coordinate (X) at ([xshift=5mm]frame.west);\fi
    \fill[shading=ball,ball color=blue!50!white,opacity=0.5] (X) circle (4mm);}
\lipsum[1-6]
\end{tcolorbox}
```

This example switches a 1cm thick rule from the left to the right side depending on the page number. Thereby, the rule is always on the outer side of the double-sided paper. Additionally, a ball is drawn on the outer side with help of an overlay.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc



eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.



## 4.7 Corners

The four corners of any `tcolorbox` can be set individually as `/tcb/sharp corners` or as `/tcb/rounded corners`<sup>→P.41</sup>. These settings are also reflected in the behavior of `/tcb/borderline`<sup>→P.142</sup> and `/tcb/shadow`<sup>→P.147</sup> as one would expect.

By default, all four corners are *rounded*. So, only the `/tcb/sharp corners` option will be necessary for most use cases. The `/tcb/rounded corners`<sup>→P.41</sup> option can be used to revert a `/tcb/sharp corners` setting.

`/tcb/sharp corners=<position>` (default `all`, initially unset)

The `<position>` denotes one or more of the four box corners to be set as *sharp* corners. The not assigned corners will retain their mode. Feasible values for `<position>` are:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,  
colframe=red!75!black,  
sharp corners=northwest ]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a `tcolorbox`.

```
\begin{tcolorbox}[colback=red!5!white,  
colframe=red!75!black,  
sharp corners ]  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

This is a `tcolorbox`.

`/tcb/rounded corners=<position>` (default `all`, initially `all`)

The `/tcb/rounded corners` can be used to revert a `/tcb/sharp corners`<sup>→P.40</sup> setting. The `<position>` denotes one or more of the four box corners to be set as *rounded* corners. The not assigned corners will retain their mode. Feasible values for `<position>` are<sup>2</sup>:

- `northwest`
- `northeast`
- `southwest`
- `southeast`
- `north`
- `south`
- `east`
- `west`
- `downhill`
- `uphill`
- `all`

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,sharp corners,
  rounded corners=northwest ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

`/tcb/sharpish corners` (style, no value)

Shortcut for setting `/tcb/arc`<sup>→P.31</sup> and `/tcb/outer arc`<sup>→P.31</sup> to `0pt`. With this setting, rounded corners will appear als quasi-sharp, but e. g. the shadow will be somewhat rounder than the shadow of really sharp corners.


Corners are still of type *rounded* with this option, but appear *sharp*. To switch back to rounded corners, one has to adapt `/tcb/arc`<sup>→P.31</sup> and `/tcb/outer arc`<sup>→P.31</sup>.

```
\begin{tcolorbox}[colback=red!5!white,
  colframe=red!75!black,
  sharpish corners ]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

<sup>2</sup>The graphical examples assume that the boxes were set to have sharp corners before.

The following examples will show the differences between `/tcb/rounded corners`<sup>→P.41</sup>, `/tcb/sharpish corners`<sup>→P.41</sup>, and `/tcb/sharp corners`<sup>→P.40</sup>. The later two give the same core box, but `/tcb/borderline`<sup>→P.142</sup> and `/tcb/shadow`<sup>→P.147</sup> settings are slightly different. The following examples use `/tcb/drop fuzzy shadow`<sup>→P.149</sup>.



## 4.8 Transparency

Transparency effects are likely to be used in conjunction with *jigsaw* skin variants, see Section 9.10 on page 163.

**/tcb/opacityframe**= $\langle fraction \rangle$  (no default, initially 1.0)

Sets the frame opacity of the box to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[opacityframe=0.25]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**/tcb/opacityback**= $\langle fraction \rangle$  (no default, initially 1.0)

Sets the background opacity of the box to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[standard jigsaw,
opacityframe=0.5, opacityback=0.5]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**/tcb/opacitybacktitle**= $\langle fraction \rangle$  (no default, initially 1.0)

Sets the title background opacity of the box to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[standard jigsaw,
opacityframe=0.5, opacitybacktitle=0.5,
title filled, title=This is a title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

**/tcb/opacityfill**= $\langle fraction \rangle$  (style, no default, initially 1.0)

Sets the fill opacity for frame, interior and optionally the title background to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[standard jigsaw,
opacityfill=0.7, title=This is a title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title

This is a **tcolorbox**.

**/tcb/opacityupper**= $\langle fraction \rangle$  (no default, initially 1.0)

Sets the text opacity of the upper box part to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[enhanced,opacityupper=0.5,
  interior style={pattern=crosshatch dots }
    {light steel blue}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**/tcb/opacitylower**= $\langle fraction \rangle$  (no default, initially 1.0)

Sets the text opacity of the lower box part to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[enhanced,opacitylower=0.5,
  interior style={pattern=crosshatch dots }
    {light steel blue}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

**/tcb/opacitytext**= $\langle fraction \rangle$  (no default, initially 1.0)

Sets the text opacity of the upper and the lower box part to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[enhanced,opacitytext=0.5,
  interior style={pattern=crosshatch dots }
    {light steel blue}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is the lower part.

**/tcb/opacitytitle**= $\langle fraction \rangle$  (no default, initially 1.0)

Sets the text opacity of the box title to the given  $\langle fraction \rangle$ .

```
\begin{tcolorbox}[enhanced,opacitytitle=0.7,
  fonttitle=\bfseries,title=This is a title,
  title style={pattern=crosshatch dots light }
    {steel blue}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title.

This is a **tcolorbox**.

```
\begin{tcolorbox}[enhanced jigsaw,fonttitle=\bfseries,title=This is a title,
  opacityframe=0.5,opacityback=0.25,opacitybacktitle=0.25,opacitytext=0.8,
  colback=red!5!white,colframe=red!75!black,colbacktitle=yellow!20!red]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a title.

This is a **tcolorbox**.

## 4.9 Height Control

In a typical usage scenario, the height of a `tcolorbox` is computed automatically to fit the content. Nevertheless, the height can be set to a fixed value or to fit commonly for several boxes, e.g. if boxes are set side by side.

The height control keys are only applicable to unbreakable boxes. If a box is set to be `/tcb/breakable`<sup>→ P. 296</sup>, the height is always computed according to the *natural height*.

**`/tcb/natural height`** (no value, initially set)


Sets the total height of the colored box to its natural height depending on the box content.

**`/tcb/height=<length>`** (no default)

Sets the total height of the colored box to `<length>` independent of the box content. `<length>` is the minimum height of the box, if `/tcb/height plus` is larger than zero.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white}

\begin{tcolorbox}[height=1cm,valign=center]
  This box has a height of 1cm.
\end{tcolorbox}
\begin{tcolorbox}[height=2cm,valign=center]
  This box has a height of 2cm.
\end{tcolorbox}
\begin{tcolorbox}[height=3cm,split=0.5,valign=center,valign lower=center]
  This box has a height of 3cm.
  \tcblower
  Lower part.
\end{tcolorbox}
```




**`/tcb/height plus=<length>`** (no default, initially 0pt)

The box may extend a given fixed `/tcb/height` up to the given `<length>`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,width=3cm,nobeforeafter}

\begin{tcolorbox}[height=1cm]
  This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
  This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[height=1cm,height plus=1cm]
  This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{tcolorbox}
```



**/tcb/height from**= $\langle min \rangle$  to  $\langle max \rangle$  (style, no default)

Sets the box height to a dimension between  $\langle min \rangle$  and  $\langle max \rangle$ .

```
% \usepackage{lipsum}
\newtcolorbox{mybox}{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=4.5cm,nobeforeafter,
  height from=2cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

N 2014-10-31

**/tcb/text height**= $\langle length \rangle$  (style, no default)

Sets the text height to  $\langle length \rangle$ . This is the length from the top of the upper part to the bottom of the optional lower part. See also **/tcb/text width**<sup>→ P. 28</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[text height=2cm]
This is a \textbf{tcolorbox} where the text area has a height of 2cm.
\end{tcolorbox}
```


This is a **tcolorbox** where the text area has a height of 2cm.

`/tcb/add to height=<length>` (style, no default)

Adds  $\langle length \rangle$  to the current height of the colored box. `/tcb/height`<sup>→P.45</sup> has to be set before this key is used!

```
\tcbset{height=1cm,
  valign=center,width=(\linewidth-2mm)/2,
  before=,after=\hfill,colframe=blue!75!black,colback=white}

\begin{tcolorbox}
  This box has a height of 1cm.
\end{tcolorbox}
\begin{tcolorbox}[add to height=1cm]
  This box has a height of 2cm.
\end{tcolorbox}
```



`/tcb/height fill=true|false|maximum` (default `true`, initially `false`)

If set to `true`, the height of the `tcolorbox` is set to the rest of the available vertical space of the current page. If set to `maximum`, the page is compressed as much as possible. Note that the `tcolorbox` is always set as its own paragraph using this option.

Note that the library `\usepackage{breakable}` has to be loaded to use this key!

This height control key is only applicable to unbreakable boxes but it uses code from the library `\usepackage{breakable}`. The counterpart for breakable boxes is `/tcb/height fixed for`<sup>→P.301</sup>.

```
% \usepackage{lipsum}
% \tcbuselibrary{breakable}
\begin{tcolorbox}[height fill,
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Box which fills the rest of the page]
\lipsum[1]
\end{tcolorbox}
```

### Box which fills the rest of the page

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.




`/tcb/space= $\langle fraction \rangle$`  (no default, initially 0)

If the height of a `tcolorbox` is not the natural height, the space difference between the forced and the natural size is distributed between the upper and the lower part of the box. This space could also be negative.  $\langle fraction \rangle$  with a value between 0 and 1 is the amount of space which is added to the upper part, the rest is added to the lower part. If there is no lower part, then all of the space is added to the upper part always.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=3cm}

\foreach \f in {0.2,0.4,0.7}
{\begin{tcolorbox}[space=\f]
  This is the upper part.
  \tcblower
  This is the lower part.
\end{tcolorbox}}
```



`/tcb/space to upper` (style)

This is an abbreviation for `space=1`, i. e. all extra space is added to the upper part.

`/tcb/space to lower` (style, initially set)


This is an abbreviation for `space=0`, i. e. all extra space is added to the lower part (if there is any).

`/tcb/space to both` (style)

This is an abbreviation for `space=0.5`, i. e. the extra space equally distributed between the upper and the lower part.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=3cm}

\foreach \myspace in {space to upper,space to both,space to lower}
{\begin{tcolorbox}[\myspace]
  This is the upper part.
  \tcblower
  This is the lower part.
\end{tcolorbox}}
```




**/tcb/split**= $\langle fraction \rangle$  (no default)

If the height of a `tcolorbox` is not the natural height, the  $\langle fraction \rangle$  with a value between 0 and 1 determines the positioning of the segmentation between the upper and the lower part. Here, 0 stands for top and 1 for bottom. Note that the box is split regardless of the actual dimensions of the text parts!

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,height=3cm,
colback=white,colframe=blue!75!black,valign=center,valign lower=center}

\foreach \f in {0.1,0.5,0.8}
{\begin{tcolorbox}[split=\f]
This is the upper part.
\tcblower
This is the lower part with a lot of text in several lines.
\end{tcolorbox}}
```




**/tcb/valign**= $\langle alignment \rangle$  (no default, initially top)

If the height of a `tcolorbox` is not the natural height, `valign` determines the vertical  $\langle alignment \rangle$  of the upper part. Feasible values are `top`, `center`, and `bottom`. For a box with natural height, these values are meaningless.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,
colframe=blue!75!black,colback=white,height=2cm}

\foreach \myalign in {top,center,bottom}
{\begin{tcolorbox}[valign=\myalign]
This is a \textbf{tcolorbox}.
\end{tcolorbox}}
```



**/tcb/valign lower**= $\langle alignment \rangle$  (no default, initially top)

This key has the same meaning for the lower part as `valign` for the upper part, i.e. it determines the vertical  $\langle alignment \rangle$  of the lower part with feasible values `top`, `center`, and `bottom`.

Boxes which are members of an `equal height group` will all get the same height, i.e. the maximum of all their natural heights. The `<id>` serves to distinguish between different height groups. Note that you have to compile twice to see changes and that height groups are global definitions.

```
\tcbset{width=(\linewidth-2mm)/3,before=,after=\hfill,arc=0mm,
colframe=blue!75!black,colback=white,fonttitle=\bfseries}

\begin{tcolorbox}[equal height group=A,adjusted title={One}]
  My smallest box.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Two}]
  This box is also small.
  \tcblower
  But with a lower part.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=A,adjusted title={Three}]
  This box contains a lot of text just to fill the space
  with word flowing and flowing and flowing until the box
  is filled with all of it.
\end{tcolorbox}\linebreak
%
\tcbset{width=(\linewidth-1mm)/2,before=,after=\hfill,arc=0mm,
colframe=red!75!black,colback=white}
%
\begin{tcolorbox}[equal height group=B]
  Now, we use another equal height group.
\end{tcolorbox}%
\begin{tcolorbox}[equal height group=B]
  \begin{equation*}
    \int\limits_0^1 x^2 = \frac{1}{3}.
  \end{equation*}
\end{tcolorbox}
```

One	Two	Three
My smallest box.	This box is also small. ----- But with a lower part.	This box contains a lot of text just to fill the space with word flowing and flowing and flowing until the box is filled with all of it.
Now, we use another equal height group.	$\int_0^1 x^2 = \frac{1}{3}.$	

See Section 12 on page 221 for more equal height options.

`/tcb/minimum for equal height group=<id>:<length>` (no default, initially unset)

Plants a  $\langle length \rangle$  into the equal height group with the given  $\langle id \rangle$ . This ensures that the height will not drop below  $\langle length \rangle$ . Note that you cannot reduce a computed height value by using this key with a small value. The difference to applying `/tcb/height`<sup>→ P. 45</sup> directly is that the boxes are never too small for their content.

```
\tcbset{colframe=blue!75!black,colback=white,arc=0mm,
  before=,after=\hfill,fonttitle=\bfseries,left=2mm,right=2mm,
  width=3.5cm,
  equal height group=C,
  minimum for equal height group=C:3.5cm}

\begin{tcolorbox}
  My first box. All boxes will get 3.5cm times 3.5cm
  if the content height is not too large.
\end{tcolorbox}%
\begin{tcolorbox}
  My second box.
  \tcblower
  This is the lower part.
\end{tcolorbox}%
\begin{tcblisting}{\textbf{Mixed}}
  with a listing.
\end{tcblisting}
\begin{tcolorbox}[title={Fourth box}]
  My final box.
\end{tcolorbox}%
```

My first box. All boxes will get 3.5cm times 3.5cm if the content height is not too large.

My second box.

This is the lower part.

**Mixed** with a listing.

**Mixed** with a listing.

**Fourth box**

My final box.

## 4.10 Box Content Additions

The following options introduce some arbitrary *<code>* to the content of a `tcolorbox`. These additions can be given at the beginning or at the ending of the title, the upper part, or the lower part.

`/tcb/before title=<code>` (no default, initially unset)

The given *<code>* is placed *after* the color and font settings and *before* the content of the title.

```
\tcbset{before title={\textcolor{yellow}{\large Important:}~},
colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

**Important:** My title

This is a **tcolorbox**.

`/tcb/after title=<code>` (no default, initially unset)

The given *<code>* is placed *after* the content of the title.

```
\tcbset{after title={\hfill\colorbox{Navy}{approved}}},
colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

approved

This is a **tcolorbox**.

`/tcb/before upper=<code>` (no default, initially unset)

The given *<code>* is placed *after* the color and font settings and *before* the content of the upper part.

```
\tcbset{before upper={\textit{The story:}\par},
colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

*The story:*

This is a **tcolorbox**.

`/tcb/after upper=<code>` (no default, initially unset)

The given `<code>` is placed *after* the content of the upper part.

```
\tcbset{after upper={\par\hfill\textit{Read more next week}}},
colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

*Read more next week*

`/tcb/before lower=<code>` (no default, initially unset)

The given `<code>` is placed *after* the color and font settings and *before* the content of the lower part.

```
\tcbset{before lower=\textit{Behold:~},colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.

*Behold:* This is the lower part.

`/tcb/after lower=<code>` (no default, initially unset)

The given `<code>` is placed *after* the content of the lower part.

```
\tcbset{after lower=\ \textit{This is the end.},
colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

This is a **tcolorbox**.


This is the lower part. *This is the end.*

`/tcb/center title` (style, no value, initially unset)

This style sets `/tcb/before title` <sup>→ P.52</sup> to `\centering`.

```
\tcbset{center title,colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```




`/tcb/center upper` (style, no value, initially unset)

This style sets `/tcb/before upper` <sup>→ P.52</sup> to `\centering`.

```
\tcbset{center upper,colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```




`/tcb/center lower` (style, no value, initially unset)

This style sets `/tcb/before lower` <sup>→ P.53</sup> to `\centering`.

```
\tcbset{center lower,colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/flushleft title` (style, no value, initially unset)

This style sets `/tcb/before title`<sup>→P.52</sup> to `\raggedright`.

```
\tcbset{flushleft title,colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title which is
quite long but always flushed left]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title which is quite  
long but always flushed  
left

This is a **tcolorbox**.

`/tcb/flushleft upper` (style, no value, initially unset)

This style sets `/tcb/before upper`<sup>→P.52</sup> to `\raggedright`.

```
\tcbset{flushleft upper,colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}. Here, the
content is flushed left.
You see the effect on the right hand side.
\end{tcolorbox}
```

My title

This is a **tcolorbox**. Here,  
the content is flushed left.  
You see the effect on the  
right hand side.

`/tcb/flushleft lower` (style, no value, initially unset)

This style sets `/tcb/before lower`<sup>→P.53</sup> to `\raggedright`.

```
\tcbset{flushleft lower,colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}. The upper part
is not flushed left or right. This could be
unpleasant for small boxes.
\tcblower
This is the lower part. Here, the
content is flushed left.
You see the effect on the right hand side.
\end{tcolorbox}
```

My title

This is a **tcolorbox**. The up-  
per part is not flushed left or  
right. This could be unpleas-  
ant for small boxes.

This is the lower part. Here,  
the content is flushed left.  
You see the effect on the  
right hand side.



`/tcb/flushright title` (style, no value, initially unset)

This style sets `/tcb/before title` <sup>→ P.52</sup> to `\raggedleft`.

```
\tcbset{flushright title,colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/flushright upper` (style, no value, initially unset)

This style sets `/tcb/before upper` <sup>→ P.52</sup> to `\raggedleft`.

```
\tcbset{flushright upper,colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/flushright lower` (style, no value, initially unset)

This style sets `/tcb/before lower` <sup>→ P.53</sup> to `\raggedleft`.

```
\tcbset{flushright lower,colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

---

This is the lower part.

If `/tcb/tabularx` or `/tcb/tabularx*` are used, one cannot have a lower part.

`/tcb/tabularx=<preamble>` (style)

This style sets `/tcb/before upper`<sup>→P.52</sup> and `/tcb/after upper`<sup>→P.53</sup> and several geometry keys to support a `tabularx` with the given `<preamble>`. The packages `tabularx` [4], `array`, and `colortbl` have to be loaded separately.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\newcolumntype{Y}{>{\raggedleft\arraybackslash}X}% see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabularx={X|Y|Y|Y|Y|Y},title=My table]
Group & One & Two & Three & Four & Sum\\ \hline
Red & 1000.00 & 2000.00 & 3000.00 & 4000.00 & 10000.00\\ \hline
Green & 2000.00 & 3000.00 & 4000.00 & 5000.00 & 14000.00\\ \hline
Blue & 3000.00 & 4000.00 & 5000.00 & 6000.00 & 18000.00\\ \hline
Sum & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table					
Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

`/tcb/tabularx*={<code>}{<preamble>}` (style)

This is a variant of `/tcb/tabularx` which adds some `<code>` before the table starts.

```
% \usepackage{array,tabularx}
% \usepackage{colortbl} - or - \usepackage[table]{xcolor}
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sffamily,
  colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
  coltitle=black,center title}

\begin{tcolorbox}[tabularx*={\arrayrulewidth0.5mm}{X|X|X},title=My table]
One & Two & Three \\ \hline
1000.00 & 2000.00 & 3000.00 \\ \hline
2000.00 & 3000.00 & 4000.00
\end{tcolorbox}
```

My table		
One	Two	Three
1000.00	2000.00	3000.00
2000.00	3000.00	4000.00

`/tcb/tikz upper=<options>` (style)

This style adds a centered `tikzpicture` environment to the start and end of the upper part. The `<options>` may be given as TikZ picture options.

```
% \usepackage{tikz}
```

```
\begin{tcolorbox}[tikz upper,fonttitle=\bfseries,colback=white,colframe=black,
title=\tikzname\ drawing]
\path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
\fill[red] (45:5mm) circle (1mm);
\fill[red] (135:5mm) circle (1mm);
\draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);
\end{tcolorbox}
```

**TikZ drawing**



`/tcb/tikz lower=<options>` (style)

This style adds a centered `tikzpicture` environment to the start and end of the lower part. The `<options>` may be given as TikZ picture options.

```
% \usepackage{tikz}
```

```
% \tcbuselibrary{skins,listings}
```

```
\tcbset{tikz lower,listing side text,fonttitle=\bfseries,
bicolor,colback=LightBlue!50!white,colbacklower=white,colframe=black,
righthand width=3cm}
```

```
\begin{tcblisting}{title=\tikzname\ drawing}
```

```
\path[fill=yellow,draw=yellow!75!red]
```

```
(0,0) circle (1cm);
```

```
\fill[red] (45:5mm) circle (1mm);
```

```
\fill[red] (135:5mm) circle (1mm);
```

```
\draw[line width=1mm,red]
```

```
(215:5mm) arc (215:325:5mm);
```

```
\end{tcblisting}
```

**TikZ drawing**

```
\path[fill=yellow,draw=yellow!75!red]
```

```
(0,0) circle (1cm);
```

```
\fill[red] (45:5mm) circle (1mm);
```

```
\fill[red] (135:5mm) circle (1mm);
```

```
\draw[line width=1mm,red]
```

```
(215:5mm) arc (215:325:5mm);
```



`/tcb/tikznode upper=<options>` (style)

This style places the upper part content into a centered TikZ node. The `<options>` may be given as TikZ node options. This style is especially useful for boxes with multiline texts which are fitted to the text width.

```
% \usepackage{tikz}
\newtcbbox{\headline}[1][]{enhanced,before=\begin{center},after=\end{center},
fontupper=\Large\bfseries,colframe=red!50!black,colback=red!10!white,
drop fuzzy shadow=yellow,tikznode upper,#1}

\headline{Important\Headline}
```

Important  
Headline

`/tcb/tikznode lower=<options>` (style)

This style places the lower part content into a centered TikZ node. The `<options>` may be given as TikZ node options.

```
% \usepackage{tikz}
\begin{tcolorbox}[bicolor,colback=LightBlue!50!white,colbacklower=white,
colframe=black,tikznode lower={inner sep=2pt,draw=red,fill=yellow}]
Upper part.
\tcblower
Lower part.
\end{tcolorbox}
```

Upper part.

Lower part.

`/tcb/tikznode=<options>` (style)

Shortcut for setting `/tcb/tikznode upper` and `/tcb/tikznode lower` the same time.

`/tcb/varwidth upper=<length>` (style, default `/tcb/width`<sup>P. 28</sup>)

This style places the upper part content into a `varwidth` environment. This style needs the `varwidth` package [1] to be loaded manually. The resulting box has a maximal width of `<length>`. This option is only senseful for a `\tcbbox`<sup>P. 13</sup>.

```
% \usepackage{varwidth}
\newtcbbox{\varbox}{colframe=red!50!black,
colback=red!10!white,varwidth upper}

\varbox{Short text.}
\varbox{This box contains is a longer text
which is broken.}
```

Short text.

This box contains is a longer  
text which is broken.

`/tcb/code=<code>` (no default, initially unset)

The given `<code>` is executed immediately. This option is useful to place some arbitrary code into an option list.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  code={Useless at this spot but functional.},
  fonttitle=\bfseries}

\begin{tcolorbox}[code={\newcommand{\mycommand}{\textit{working}}},
  title=My \mycommand\ title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

Useless at this spot but functional.

***My working title***

This is a **tcolorbox**.

## 4.11 Overlays

With an overlay, arbitrary *graphical code* can be added to a `tcolorbox`. This code is executed *after* the frame and interior are drawn and *before* the text content is drawn. Therefore, you can decorate the `tcolorbox` with your own extensions. Common special cases are *watermarks* which are implemented using overlays. See Subsection 9.3 from page 130 if you want to add *watermarks*.

If you use the core package only, the *graphical code* has to be `pgf` code and there is not much assistance for positioning. Therefore, the usage of the `/tcb/enhanced`<sup>P. 168</sup> mode from the library skins is recommended which allows `tikz` code and gives access to `/tcb/geometry nodes`<sup>P. 108</sup> for positioning.

`/tcb/overlay=<graphical code>` (no default, initially unset)

Adds *graphical code* to the box drawing process. This *graphical code* is drawn *after* the frame and interior and *before* the text content.

```
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
  enlarge top by=5.5mm,
  overlay={\foreach \x in {2cm,3.5cm} {
    \begin{scope}[shift={([xshift=\x]frame.north west)}]
      \path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
      \path[fill=black] (-0.2,0) arc (0:180:1mm);
    \end{scope}}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins} % preamble
\tcbset{ribbonbox/.style={enhanced,colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,
  overlay={\path[fill=blue!75!white,draw=blue,double=white!85!blue,
    preaction={opacity=0.6,fill=blue!75!white},
    line width=0.1mm,double distance=0.2mm,
    pattern=fivepointed stars,pattern color=white!75!blue]
    ([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
    -- ++(-1,1) -- ++(-0.5,0) -- ++(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[ribbonbox,title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



- /tcb/no overlay** (style, no default, initially set)  
Removes the overlay if set before.
- /tcb/overlay broken**= $\langle graphical\ code \rangle$  (no default, initially unset)  
If the box is set to be **/tcb/breakable**<sup>→P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay unbroken**= $\langle graphical\ code \rangle$  (no default, initially unset)  
If the box is set to be **/tcb/breakable**<sup>→P. 296</sup> but *is not* broken actually or if the box is set to be **/tcb/unbreakable**<sup>→P. 297</sup>, then the  $\langle graphical\ code \rangle$  is added to the box drawing process. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay first**= $\langle graphical\ code \rangle$  (no default, initially unset)  
If the box is set to be **/tcb/breakable**<sup>→P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process for the *first* part of the break sequence. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay middle**= $\langle graphical\ code \rangle$  (no default, initially unset)  
If the box is set to be **/tcb/breakable**<sup>→P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process for the *middle* parts (if any) of the break sequence. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay last**= $\langle graphical\ code \rangle$  (no default, initially unset)  
If the box is set to be **/tcb/breakable**<sup>→P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process for the *last* part of the break sequence. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay unbroken and first**= $\langle graphical\ code \rangle$  (no default, initially unset)  
This is an optimized abbreviation for setting **/tcb/overlay unbroken** and **/tcb/overlay first** together. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay middle and last**= $\langle graphical\ code \rangle$  (no default, initially unset)  
This is an optimized abbreviation for setting **/tcb/overlay middle** and **/tcb/overlay last** together. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay unbroken and last**= $\langle graphical\ code \rangle$  (no default, initially unset)  
This is an optimized abbreviation for setting **/tcb/overlay unbroken** and **/tcb/overlay last** together. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.
- /tcb/overlay first and middle**= $\langle graphical\ code \rangle$  (no default, initially unset)  
This is an optimized abbreviation for setting **/tcb/overlay first** and **/tcb/overlay middle** together. **/tcb/overlay**<sup>→P. 61</sup> overwrites this key.

N 2014-09-19

This example demonstrates the application of break sequence specific overlay options. Here, we define an environment **myexample** based on **tcolorbox** where the visible drawing is done totally by overlay keys.

Here, the first application of **myexample** produces an unbroken **tcolorbox**. The frame is drawn by the code given with **/tcb/overlay unbroken**.

The second application of **myexample** is broken into several parts which are drawn by the codes given with **/tcb/overlay first**, **/tcb/overlay middle**, and **/tcb/overlay last**.

```
% Preamble:
%\usepackage{tikz,lipsum}
%\tcbuselibrary{skins,breakable}
%\newcounter{example}
\colorlet{colexam}{red!75!black}
```



```

\newcolorbox[use counter=example]{myexample}{%
  empty,title={Example \thetcbcounter},attach boxed title to top left,
  boxed title style={empty,size=minimal,toprule=2pt,top=4pt,
    overlay={\draw[colexam,line width=2pt]
      ([yshift=-1pt]frame.north west)--([yshift=-1pt]frame.north east);}},
  coltitle=colexam,fonttitle=\Large\bfseries,
  before=\par\medskip\noindent,parbox=false,boxsep=0pt,left=0pt,right=3mm,top=4pt,
  breakable,pad at break*=0mm,vfill before first,
  overlay unbroken={\draw[colexam,line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west); },
  overlay first={\draw[colexam,line width=1pt]
    ([yshift=-1pt]title.north east)--([xshift=-0.5pt,yshift=-1pt]title.north-|frame.east)
    --([xshift=-0.5pt]frame.south east); },
  overlay middle={\draw[colexam,line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east); },
  overlay last={\draw[colexam,line width=1pt] ([xshift=-0.5pt]frame.north east)
    --([xshift=-0.5pt]frame.south east)--(frame.south west);},%
}

\begin{myexample}
\lipsum[1]
\end{myexample}

\begin{myexample}
\lipsum[2-11]
\end{myexample}

\lipsum[12]% following text

```

## Example 1

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

## Example 2

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent



euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetur. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in,

sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

## Floating box from `floatplacement`

This floating box is placed at the top of a page.

### 4.12 Floating Objects

`/tcb/floatplacement=<values>` (no default, initially `htb`)

Sets `<values>` as default values for the usage of `/tcb/float` and `/tcb/float*`. Feasible are the usual parameters for floating objects.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,
  watermark color=red!15!white}

\begin{tcolorbox}[floatplacement=t,float,
  title=Floating box from |floatplacement|,
  watermark text={I am floating}]
  This floating box is placed at the top of a page.
\end{tcolorbox}
```

`/tcb/float=<values>` (default from `floatplacement`)

Turns the box to a floating object where `<values>` are the usual parameters for such floating objects. If they are not used, the placement uses the default values given by `floatplacement`.

```
\begin{tcolorbox}[float, title=Floating box from |float|,
  enhanced,watermark text={I'm also floating}]
  This box floats to a feasible place automatically. You do not have to
  use a numbering for this floating object.
\end{tcolorbox}
```

## Floating box from `float`

This box floats to a feasible place automatically. You do not have to use a numbering for this floating object.

`/tcb/float*=<values>` (default from `floatplacement`)

Identical to `/tcb/float`, but for wide boxes spanning the whole page width of two column documents or in conjunction with the packages `multicol` or `paracol`. Note that you have to set `width=\textwidth` additionally, if the box should span the whole page width in these cases!

```
\begin{tcolorbox}[float*=b, title=Floating box from |float*|,width=\textwidth,
  enhanced,watermark text={I'm also floating}]
  In this single column document, you will see no difference to |float|.
\end{tcolorbox}
```

`/tcb/nofloat` (style, initially set)

Turns the floating behavior off.

## Floating box from `float*`


In this single column document, you will see no difference to `float`.

`/tcb/every float=<code>` (no default, initially empty)

For floating objects, the `/tcb/before`<sup>→ P. 72</sup> and `/tcb/after`<sup>→ P. 72</sup> settings are ignored. Instead, the given `<code>` is inserted before a floating box. If the box is `/tcb/breakable`<sup>→ P. 296</sup>, the given `<code>` is inserted before every part of the break sequence. The most common use case is `every float=\centering`.

```
\tcbbox[float=htb,title={Floating box},every float=\centering,
colback=blue!50!black,colframe=blue!50!white,colbacktitle=blue!10!white,
coltitle=black,center title]
{\includegraphics[height=6cm]{lichtspiel.jpg}}
```

Floating box



## 4.13 Side by Side

Further side by side options for code examples are `/tcb/listing side text`<sup>→P.248</sup>, `/tcb/text side listing`<sup>→P.248</sup>, `/tcb/listing outside text`<sup>→P.248</sup>, and `/tcb/text outside listing`<sup>→P.248</sup>.

`/tcb/sidebyside=true|false` (default `true`, initially `false`)

Normally, the upper part and the lower part of the box have their positions as their names suggest. If `sidebyside` is set to `true`, the upper part is drawn *left-handed* and the lower part is drawn *right-handed*. Both parts are drawn together with the geometry settings of the upper part but the space is divided horizontally according to the following options. Colors, fonts, and box content additions are used individually. The resulting box is unbreakable.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```

My title

This is the upper (*left-handed*) part.

This is the lower (*right-handed*) part.

`/tcb/sidebyside align=<alignment value>` (no default, initially `center`)

Sets the vertical alignment for the left-handed and right-handed part. Feasible values are `center`, `top`, and `bottom`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,nobeforeafter,
left=2mm,right=2mm,sidebyside,sidebyside gap=6mm,width=(\linewidth-2mm)/3}

\begin{tcolorbox}[adjusted title=center,sidebyside align=center]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=top,sidebyside align=top]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=bottom,sidebyside align=bottom]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}
```

center

This is a text which is too long for one line.

This is a short text.

top

This is a text which is too long for one line.

This is a short text.

bottom

This is a text which is too long for one line.


This is a short text.

`/tcb/sidebyside gap=<length>` (no default, initially 10mm)

Sets the horizontal distance between the left-handed and right-handed part to  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries,nobeforeafter,
sidebyside,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[adjusted title=Wide gap,sidebyside gap=30mm]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}\hfill
\begin{tcolorbox}[adjusted title=Narrow gap,sidebyside gap=1mm]
This is a text which is too long for one line.
\tcblower
This is a short text.
\end{tcolorbox}
```




`/tcb/lefthand width=<length>` (no default, initially unset)

Sets the width of the left-handed part to the given  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,lefthand width=3cm]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```



`/tcb/righthand width=<length>` (no default, initially unset)

Sets the width of the right-handed part to the given  $\langle length \rangle$ .

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,righthand width=3cm]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```




`/tcb/lefthand ratio=<fraction>` (no default, initially 0.5)

Sets the width of the left-handed part to the given  $\langle fraction \rangle$  of the available space.  $\langle fraction \rangle$  is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,lefthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```



`/tcb/righthand ratio=<fraction>` (no default, initially 0.5)

Sets the width of the right-handed part to the given  $\langle fraction \rangle$  of the available space.  $\langle fraction \rangle$  is a value between 0 and 1.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My title,sidebyside,righthand ratio=0.25]
This is the upper (\textit{left-handed}) part.
\tcblower
This is the lower (\textit{right-handed}) part.
\end{tcolorbox}
```






If one side of a side-by-side box should be adapted to the width of its content, this width has to be computed beforehand. The following example uses a savebox `\mysavebox` to store the picture to determine its width.

```
% \tcboxlibrary{skins,xparse}
% \usepackage{lipsum}
% \newsavebox\mysavebox % preamble
\DeclareTotalTColorBox{\mysidebox}{ 0 } +m +m ){
  bicolor,colback=white,colbacklower=yellow!10,
  fonttitle=\bfseries,center title,
  sidebyside,
  code={\sbox{\mysavebox}{#2}},
  lefthand width=\wd\mysavebox,
  drop lifted shadow,
  #1
}
{\usebox{\mysavebox}\tcblower#3}

\mysidebox[title=The Triangle]{%
  \begin{tikzpicture}
    \path[fill=red!20,draw=red!50!black]
      (0,0) node[below]{A} -- (3,1) node[right]{B}
      -- (1,4) node[above]{C} -- cycle;
  \end{tikzpicture}%
}{%
  \lipsum[1]
}
```

The Triangle	
	<p>Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.</p>

## 4.14 Embedding into the Surroundings

Typically, but not necessarily, a `tcolorbox` is put inside a separate paragraph and has some vertical space before and after it. This behavior is controlled by the keys `before` and `after`.

**/tcb/before**=*<code>* (no default, initially see `/tcb/autoparskip`)  
Sets the *<code>* which is executed before the colored box. It is not used for floating boxes. Also, it is not used, if the box follows a heading immediately and `/tcb/ignore nobreak`<sup>→ P. 75</sup> is set to `false`.

**/tcb/after**=*<code>* (no default, initially see `/tcb/autoparskip`)  
Sets the *<code>* which is executed after the colored box. It is not used for floating boxes.

**/tcb/parskip** (style, no value)  
Sets the keys `before` and `after` to values which are recommended, if the package `parskip` is used and there is no better idea for `before` and `after`.

```
\tcbset{parskip/.style={before={\par\pagebreak[0]\parindent=0pt},
                        after={\par}}}
```

**/tcb/noparskip** (style, no value)  
Sets the keys `before` and `after` to values which are recommended, if the package `parskip` is *not* used and there is no better idea for `before` and `after`.

```
\tcbset{noparskip/.style={before={\par\smallskip\pagebreak[0]\parindent=0pt},
                        after={\par\smallskip}}}
```

**/tcb/autoparskip** (style, no value, initially set)  
Tries to detect the usage of the package `parskip` and sets the keys `before` and `after` accordingly. Actually, the following is done:

- If the length of `\parskip` is greater than `0pt` at the beginning of the document, `/tcb/parskip` is executed. Here, the usage of package `parskip` is *assumed*.
- Otherwise, if the length of `\parskip` is not greater than `0pt` at the beginning of the document, `/tcb/noparskip` is executed. Here, the absence of package `parskip` is *assumed*.

`autoparskip` is the default for the package `tcolorbox`, if `before` or `after` are not changed otherwise.

**/tcb/nobeforeafter** (style, no value)  
Abbreviation for clearing the keys `before` and `after`. The colored box is not put into a paragraph and there is no space before or after the box.

```
\tcbset{myone/.style={colback=LightGreen,colframe=DarkGreen,
    equal height group=nobefaf,width=\linewidth/4,nobeforeafter}}
\begin{tcolorbox}[myone,title=Box 1]Box 1\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 2]Box 2\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 3]Box 3\end{tcolorbox}%
\begin{tcolorbox}[myone,title=Box 4]Box 4\end{tcolorbox}
```

Box 1	Box 2	Box 3	Box 4
Box 1	Box 2	Box 3	Box 4

`/tcb/baseline=<length>` (no default, initially 0pt)

Used to set the `\pgfsetbaseline` value of the resulting `tcolorbox`.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[baseline=3mm]
One line.
\end{tcolorbox}
\begin{tcolorbox}[baseline=3mm]
First line.\Second line.
\end{tcolorbox}
```

Some text .....

One line.

First line.  
Second line.

N 2014-10-10

`/tcb/box align=<alignment>` (style, no default, initially bottom)

Used to set the `/tcb/baseline` value of the resulting `tcolorbox`. Feasible values for `<alignment>` are:

- **bottom**: alignment with the box bottom,
- **top**: alignment with the box top,
- **center**: alignment with the box center,
- **base**: alignment with the box content base. This option is not applicable for a `tcolorbox`<sup>→P.11</sup> but for a `\tcbbox`<sup>→P.13</sup> only. It is an alias for `/tcb/tcbbox raise base`<sup>→P.87</sup>.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=bottom]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=bottom]
First line.\Second line.
\end{tcolorbox}
```

Some text .....

One line.

First line.  
Second line.

```
\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=top]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=top]
First line.\Second line.
\end{tcolorbox}
```

Some text .....

One line.

First line.  
Second line.

```

\tcbset{colframe=red!50!white,width=4cm,nobeforeafter}
Some text\dotfill
\begin{tcolorbox}[box align=center]
One line.
\end{tcolorbox}
\begin{tcolorbox}[box align=center]
First line.\Second line.
\end{tcolorbox}

```

Some text .....

One line.

First line.  
Second line.

```

\tcbset{colframe=red!50!white,nobeforeafter}
Some text\dotfill
\tcbbox[nobeforeafter,box align=base]{One line}
\tcbbox[nobeforeafter,box align=base,size=fbox]{Another line}

```

Some text .....

One line

Another line

N 2014-10-10  
U 2014-12-16

**/tcb/before skip**= $\langle glue \rangle$  (style, no default)

Inserts some vertical space of the given  $\langle glue \rangle$  before the colored box. This style sets `/tcb/before`<sup>→ P. 72</sup>.

```

Some text.
\begin{tcolorbox}[before skip=1cm,
colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

```

Some text.

This is a **tcolorbox**.

N 2014-10-10  
U 2014-12-16

**/tcb/after skip**= $\langle glue \rangle$  (style, no default)

Inserts some vertical space of the given  $\langle glue \rangle$  after the colored box. This style sets `/tcb/after`<sup>→ P. 72</sup>.

```

\begin{tcolorbox}[after skip=1cm,
colframe=red!50!white]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
Some text.

```

This is a **tcolorbox**.

Some text.

N 2014-10-10

**/tcb/beforeafter skip**= $\langle glue \rangle$  (style, no default)

Inserts some vertical space of the given  $\langle glue \rangle$  before *and* after the colored box. This style sets `/tcb/before`<sup>→ P. 72</sup> and `/tcb/after`<sup>→ P. 72</sup>.

```

\tcbset{beforeafter skip=0pt,
colframe=red!50!white}
\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}
Second box.
\end{tcolorbox}

```

This is a **tcolorbox**.

Second box.

**N 2014-11-07** `/tcb/left skip=<length>` (style, no default, initially 0mm)

Inserts some horizontal space of the given  $\langle length \rangle$  before the colored box. This style sets `/tcb/grow to left by`<sup>P.78</sup> with the negated  $\langle length \rangle$ , i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[left skip=1cm,
  colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**N 2014-11-07** `/tcb/right skip=<length>` (style, no default, initially 0mm)

Inserts some horizontal space of the given  $\langle length \rangle$  after the colored box. This style sets `/tcb/grow to right by`<sup>P.78</sup> with the negated  $\langle length \rangle$ , i.e. the bounding box and box width are changed.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[right skip=1cm,
  colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**N 2014-10-10** `/tcb/leftright skip=<length>` (style, no default)

Inserts some horizontal space of the given  $\langle length \rangle$  before *and* after the colored box. This style changes the bounding box and the box width.

```
\noindent\rule{\linewidth}{2pt}

\begin{tcolorbox}[leftright skip=1cm,
  colframe=red!50!white]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcol-  
orbox**.

**N 2014-12-11** `/tcb/ignore nobreak=true|false` (default true, initially false)

After a heading, L<sup>A</sup>T<sub>E</sub>X tries to avoid a break by setting a `nobreak` boolean value. Starting from version 3.33, the `/tcb/before`<sup>P.72</sup> respectively `/tcb/before skip`<sup>P.74</sup> settings are not used after a heading if `/tcb/ignore nobreak` is set to **false**. For an unbreakable box, `/tcb/before nobreak` is used instead. Further, a `/tcb/breakable`<sup>P.296</sup> box will also try to avoid a break between a heading and a directly following first part of a break sequence. Set `/tcb/ignore nobreak` to **true**, if `nobreak` should be ignored as prior to version 3.33. Also, such a setting may be used locally to enforce the `/tcb/before`<sup>P.72</sup> setting.

**N 2014-12-16** `/tcb/before nobreak=<code>` (no default, initially `\noindent`)

Sets the  $\langle code \rangle$  which is executed before the colored box if it is unbreakable, if `/tcb/ignore nobreak` is not set, and if the box follows a heading.

## 4.15 Bounding Box

Normally, every `tcolorbox` has a bounding box which fits exactly to the dimensions of the outer frame. Therefore,  $\text{\LaTeX}$  reserves exactly the space needed for the box. This behavior can be changed by enlarging (or shrinking) the bounding box. If the bounding box is enlarged, the `tcolorbox` will get some clearance around it. If the bounding box is shrunk, i. e. enlarged with negative values, the `tcolorbox` will overlap to other parts of the page. For example, the `tcolorbox` could be stretched into the page margin.

The following examples use `/tcb/show bounding box`<sup>→P.144</sup> to display the actual bounding box. For this, the library `\usepackage{skins}` has to be included and `/tcb/enhanced`<sup>→P.168</sup> has to be set.

`/tcb/enlarge top initially by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by `<length>`. If the box is *breakable*, only the first box of the break sequence gets enlarged. `/tcb/enlarge top by`<sup>→P.77</sup> overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge top initially by=-5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge top initially by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

`/tcb/enlarge bottom finally by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the bottom of the box by `<length>`. If the box is *breakable*, only the last box of the break sequence gets enlarged. `/tcb/enlarge bottom by`<sup>→P.77</sup> overwrites this key.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge bottom finally by=5mm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge bottom finally by=-5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

`/tcb/enlarge top at break by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by  $\langle length \rangle$ , if the box is `/tcb/breakable`<sup>→P. 296</sup>. In this case, it is applied to *middle* and *last* parts in a break sequence. `/tcb/enlarge top by` overwrites this key.

`/tcb/enlarge bottom at break by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the bottom of the box by  $\langle length \rangle$ , if the box is `/tcb/breakable`<sup>→P. 296</sup>. In this case, it is applied to *first* and *middle* parts in a break sequence. `/tcb/enlarge bottom by` overwrites this key.

`/tcb/enlarge top by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the top of the box by  $\langle length \rangle$ . `/tcb/enlarge top initially by`<sup>→P. 76</sup> and `/tcb/enlarge top at break by` are set to  $\langle length \rangle$ .

`/tcb/enlarge bottom by=<length>` (no default, initially 0mm)



Enlarges the bounding box distance to the bottom of the box by  $\langle length \rangle$ . `/tcb/enlarge bottom finally by`<sup>→P. 76</sup> and `/tcb/enlarge bottom at break by` are set to  $\langle length \rangle$ .

`/tcb/enlarge left by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the left side of the box by  $\langle length \rangle$ .

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge left by=2cm,width=5cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge left by=-2cm,width=\linewidth+2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



`/tcb/enlarge right by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to the right side of the box by  $\langle length \rangle$ .

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[enlarge right by=-2cm,width=\linewidth+2cm,
enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[enlarge right by=2cm,width=\linewidth-2cm]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```






`/tcb/enlarge by=<length>` (no default, initially 0mm)

Enlarges the bounding box distance to all sides of the box by  $\langle length \rangle$ .

```
\tcbset{colframe=blue!75!black,colback=white,width=5cm,nobeforeafter}

\begin{tcolorbox}
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[enlarge by=5mm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```




`/tcb/grow to left by=<length>` (no default, initially 0mm)

Enlarges the current box width by  $\langle length \rangle$  and enlarges (shrinks) the bounding box distance to the left side of the box by  $-\langle length \rangle$ . Also see `/tcb/left skip`<sup>→ P. 75</sup>.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[width=5cm,grow to left by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox} with a width of 7cm.
\end{tcolorbox}
```



This is a **tcolorbox** with a width of 7cm.

`/tcb/grow to right by=<length>` (no default, initially 0mm)


Enlarges the current box width by  $\langle length \rangle$  and enlarges (shrinks) the bounding box distance to the right side of the box by  $-\langle length \rangle$ . Also see `/tcb/right skip`<sup>→ P. 75</sup>.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[grow to right by=2cm,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\bigskip

\begin{tcolorbox}[grow to right by=2cm,grow to left by=1cm,
enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```





## Floating box from toggle enlargement

This page is an odd page. Therefore, the left and right enlargements are not toggled (with some luck; otherwise use `forced`). This box stretches to the right margin on odd pages and to the left margin on even pages. The current document is one-sided – this feature makes sense for two-sided documents only.

`/tcb/toggle enlargement=<toggle preset>` (default `evenpage`, initially `none`)

According to the `<toggle preset>`, the left and the right enlargements of the bounding box are switched or not. Feasible values are:

- **none**: no switching.
- **forced**: the values of the left and right enlargement are switched.
- **evenpage**: if the page is an even page, the values of the left and right enlargement are switched. It is recommended that one use this setting in conjunction with `/tcb/check odd page`<sup>→ P. 89</sup>.

```
% \usepackage{changepage} for 'check odd page'
\tcbset{colframe=blue!75!black,colback=white,
grow to left by=20mm,grow to right by=-5mm}

\begin{tcolorbox}[toggle enlargement=none,enhanced,show bounding box]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[toggle enlargement=forced]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
\begin{tcolorbox}[toggle enlargement=evenpage,check odd page]
This page is an \ifthenelse{\isodd{\thepage}}{odd}{even} page.
Therefore, the left and right enlargements
\ifthenelse{\isodd{\thepage}}{are not}{are} toggled.
\end{tcolorbox}
```

This is a **tcolorbox**.

This is a **tcolorbox**.

This page is an odd page. Therefore, the left and right enlargements are not toggled.

```
% \usepackage{changepage} for 'check odd page'
\begin{tcolorbox}[colframe=red!60!black,colback=red!15!white,check odd page,
fonttitle=\bfseries,title=Floating box from \texttt{toggle enlargement},
width=\textwidth,grow to right by=2cm,toggle enlargement=evenpage,float=t]
This page is an \ifthenelse{\isodd{\thepage}}{odd}{even} page.
Therefore, the left and right enlargements
\ifthenelse{\isodd{\thepage}}{are not}{are} toggled (with some luck; otherwise
use |forced|). This box stretches to the right margin on odd pages and to the left
margin on even pages. The current document is one-sided -- this feature makes
sense for two-sided documents only.
\end{tcolorbox}
```

The following keys should not be used with breakable boxes or boxes with a lower part.

**/tcb/shrink tight** (style, no value, initially unset)

The total colored box is shrunk to the dimensions of the upper part. There should be no lower part and no title. This style sets the `/tcb/boxsep`<sup>→ P. 31</sup> to 0pt and other geometry keys to fitting values. This option is likely to be used with the following extrusion keys.

```
\tcbset{colframe=blue!75!black,colback=white,arc=0mm,boxrule=0.4pt,  
nobeeforeafter,tcbbox raise base,shrink tight}
```

```
\begin{tcolorbox}  
This is a \textbf{tcolorbox}.  
\end{tcolorbox}
```

Lorem \tcbbox{ipsum} dolor sit amet, consectetur adipiscing elit.

This is a **tcolorbox**.

Lorem ipsum dolor sit amet, consectetur adipiscing elit.

U 2014-09-19

**/tcb/extrude left by=<length>** (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to the left side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,  
frame style={opacity=0.25},interior style={opacity=0.5},  
nobeeforeafter,tcbbox raise base,shrink tight,extrude by=2mm}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis.

\tcbbox[extrude left by=1cm]{Curabitur} dictum gravida mauris.

Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

U 2014-09-19

**/tcb/extrude right by=<length>** (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to the right side. The inner width and the bounding box is kept unchanged and the operation is additive!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,  
frame style={opacity=0.25},interior style={opacity=0.5},  
nobeeforeafter,tcbbox raise base,shrink tight,extrude by=2mm}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis.

\tcbbox[extrude right by=1cm]{Curabitur} dictum gravida mauris.

Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

`/tcb/extrude top by=<length>` (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to the top side. The inner width and the bounding box is kept unchanged and the operation is additiv!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbbox raise base,shrink tight,extrude by=2mm}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis.

`\tcbbox[extrude top by=1cm]{Curabitur}` dictum gravida mauris.

Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

`/tcb/extrude bottom by=<length>` (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to the bottom side. The inner width and the bounding box is kept unchanged and the operation is additiv!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbbox raise base,shrink tight,extrude by=2mm}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis.

`\tcbbox[extrude bottom by=1cm]{Curabitur}` dictum gravida mauris.

Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna.

`/tcb/extrude by=<length>` (style, no default, initially unset)

The (upper part of the) colored box is extruded by the given *<length>* to all sides. The inner width and the bounding box is kept unchanged and the operation is additiv!

```
\tcbset{enhanced,colframe=red,colback=yellow!25!white,
  frame style={opacity=0.25},interior style={opacity=0.5},
  nobeforeafter,tcbbox raise base,shrink tight,extrude by=2mm}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. `\tcbbox{Curabitur}` dictum gravida mauris. `\tcbbox[colframe=Green,interior style={opacity=0.0}]{Nam}` arcu libero, nonummy eget, consectetur id, `\tcbbox{vulputate}` a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. `\tcbbox{Mauris ut leo.}`

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo.

## 4.16 Layered Boxes and Every Box Settings

A `tcolorbox` may contain another `tcolorbox` and so on. The package takes track of the nesting level using a counter `tcblayer`. Counter values may be used for doing some fancy things, but you should never change the counter value yourself.

The package takes special care for the first four layers or nesting levels, called managed layers. Here, footnote texts are administrated to find their intended place and specific layer dependent options may be set by changing `/tcb/every box on layer n`<sup>→P.83</sup>. If needed, the number of managed layers can be increased by setting `\tcbsetmanagedlayer`<sup>→P.83</sup> to a higher value than 4.

The following styles have a considerable influence on how layered boxes are processed. Note especially that nested boxes are getting a `/tcb/reset`<sup>→P.90</sup> by default. You can change this, but be prepared for surprises if you do.

If the defaults are *not changed*, a `tcolorbox` gets its options in the following order. Following options overwrite preceding options.

1. On package load, all options are set to default values.
2. Every `\tcbset`<sup>→P.12</sup> command adds or changes options for the following boxes inside the current  $\text{\TeX}$  group.
3. While entering a `tcolorbox`, a `/tcb/every box on layer n`<sup>→P.83</sup> or `/tcb/every box on higher layers`<sup>→P.83</sup> option list is applied. With default settings this means:
  - For layer 1 (lowest layer), the `/tcb/every box` option list is applied. Not overwritten options given by a preceding `\tcbset`<sup>→P.12</sup> survive.
  - For layer 2 and above (nested boxes), a `/tcb/reset`<sup>→P.90</sup> followed by `/tcb/every box` option list is applied. Every resettable options given by a preceding `\tcbset`<sup>→P.12</sup> and by the surrounding box(es) are reset.
4. The `\options` given to the `tcolorbox` are applied. Or, if the box was generated by `\newtcolorbox`<sup>→P.14</sup> or friends, the `\options` given there are applied.
5. If the box was generated by `\newtcolorbox`<sup>→P.14</sup> or friends, some automated options are applied.

`/tcb/every box` (style)

By default, this style is empty.

```
% default setting:
\tcbset{every box/.style={}}
```

It may be changed by redefining this style.

```
% setting all boxes to be enhanced:
\tcbset{every box/.style={enhanced}}
```

The alternative for setting something for every box (on every layer) is `\tcbsetforeverylayer`<sup>→P.12</sup>:

```
% setting all boxes to be enhanced:
\tcbsetforeverylayer{enhanced}
```

### `/tcb/every box on layer n` (style)

Here, `n` has to be replaced by a number ranging from 1 to the highest managed layer number (4 by default).

```
% default settings:
\tcbset{
  every box on layer 1/.style={every box},
  every box on layer 2/.style={reset,every box},
  every box on layer 3/.style={reset,every box},
  every box on layer 4/.style={reset,every box},
}
```

### `/tcb/every box on higher layers` (style)

Higher layers are layers above the highest managed layer number (4 by default).

```
\tcbset{every box on higher layers/.style={reset,every box}}
```

### `\tcbsetmanagedlayer{<number>}`

Replaces the highest managed layer number by `<number>` where 4 is the default. This macro can only be used inside the preamble. Using a `<number>` lower than 4 typically makes no sense, but is not forbidden.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins,breakable}
\tcbset{colframe=red!75!black,fonttitle=\bfseries,
  colback=red!5!white,
  every box/.style={enhanced,watermark text=\thetcblayer,
    before=\par\smallskip,after=\par\smallskip},
  every box on layer 2/.style={reset,every box,colback=yellow!10!white,
    drop fuzzy shadow}}
\begin{tcolorbox}[enhanced jigsaw,breakable,title=Layer 1 Box]
Here comes a footnote\footnote{Footnote from layer 1 box}.
\lipsum[2]
\begin{tcolorbox}[title=Layer 2 Box]
abc\footnote{The footnote of abc}
\end{tcolorbox}
\begin{tcolorbox}[title=Another Box,ams equation]
\tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} = \infty.
\end{tcolorbox}
Some text\footnote{Footnote from some text}.
\begin{tcolorbox}[title=Yet Another Box]
\tcbboxfit[height=2cm]{\lipsum[1]}
My text.
\begin{tcolorbox}
Another lipsum text\footnote{A lipsum text}. \lipsum[3]
\begin{tcolorbox}[title=Layer 4,colframe=blue,colback=white]
Layer 4\footnote{Layer 4 footnote}
\end{tcolorbox}
The End\footnote{Last footnote}.
\end{tcolorbox}
\end{tcolorbox}
\end{tcolorbox}
```

### Layer 1 Box

Here comes a footnote<sup>a</sup>. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae

ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

#### Layer 2 Box

abc<sup>a</sup>

<sup>a</sup>The footnote of abc

2

#### Another Box

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (1)$$

Some text<sup>b</sup>.

#### Yet Another Box

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

My text.

Another lipsum text<sup>a</sup>. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

#### Layer 4

Layer 4<sup>a</sup>

<sup>a</sup>Layer 4 footnote

4

The End<sup>b</sup>.

<sup>a</sup>A lipsum text

<sup>b</sup>Last footnote

<sup>a</sup>Footnote from layer 1 box

<sup>b</sup>Footnote from some text



## 4.17 Capture Mode

`/tcb/capture=<mode>` (no default, initially `minipage`)

The capture `<mode>` defines how the box content is processed.

Feasible values for `<mode>` are:

- **minipage:**  
This is the default `<mode>` for `tcolorbox`<sup>→P.11</sup>. The content may have an upper and a lower part. Optionally, the box can be `/tcb/breakable`<sup>→P.296</sup>. The box content is put into a minipage or into something similar to a minipage.
- **hbox:**  
This is the default `<mode>` for `\tcbox`<sup>→P.13</sup>. The content cannot have a lower part and cannot be broken. The colored box is sized according to the dimensions of the content. A shortcut to set this mode is `/tcb/hbox`.
- **fitbox:** (needs the `fitting` library)  
This is the default `<mode>` for `\tcboxfit`<sup>→P.314</sup>. The content cannot have a lower part and cannot be broken. The content is sized according to the dimensions of the colored box. A shortcut to set this mode is `/tcb/fit`<sup>→P.316</sup>.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[capture=minipage]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=hbox]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[capture=fitbox,height=9mm]% needs the 'fitting' library
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

This is a tcolorbox.

`/tcb/hbox` (style, no default)

Shortcut for `capture=hbox`.

```
\tcbset{colframe=blue!75!black,colback=white}

\begin{tcolorbox}[hbox]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/minipage` (style, no default)

Shortcut for `capture=minipage`.

## 4.18 Text Characteristics

`/tcb/parbox=true|false` (default `true`, initially `true`)

The text inside a `tcolorbox` is formatted using a L<sup>A</sup>T<sub>E</sub>X `minipage` if the box is unbreakable. If breakable, the box tries a mimicry of a `minipage`. In a `minipage` or `parbox`, paragraphs are formatted slightly different as the main text. If the key value is set to `false`, the normal main text behavior is restored. In some situations, this has some unwanted side effects. It is recommended that one use this experimental setting only where you really want to have this feature.

```
% \usepackage{lipsum} % preamble
\tcbset{width=(\linewidth-2mm)/2,nobeforeafter,arc=1mm,
  colframe=blue!75!black,colback=white,fonttitle=\bfseries,fontupper=\small,
  left=2mm,right=2mm,top=1mm,bottom=1mm,equal height group=parbox}

\begin{tcolorbox}[parbox,adjusted title={parbox=true (normal)}]
  \lipsum[1-2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[parbox=false,adjusted title={parbox=false}]
  \lipsum[1-2]
\end{tcolorbox}%
```

### parbox=true (normal)

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

### parbox=false

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



**/tcb/hyphenationfix**=*true|false* (default **true**, initially **false**)

Long words at the beginning of paragraphs in very narrow boxes will not be hyphenated using pdf<sub>l</sub>at<sub>ex</sub>. This problem is circumvented by applying the **hyphenationfix** option.

```
\tcbset{colframe=blue!75!black,
fontupper=\normalsize,
colback=blue!5!white,width=4cm}

\begin{tcolorbox}
Rechnungsadjunktentochter.\par
Statthaltereikonzipist.
\end{tcolorbox}

\begin{tcolorbox}[hyphenationfix]
Rechnungsadjunktentochter.\par
Statthaltereikonzipist.
\end{tcolorbox}
```

Rechnungsadjunktentochter.  
Statthaltereikonzipist.

Rechnungsad-  
junktentochter.  
Statthal-  
tereikonzipist.

**parbox=false** and **hyphenationfix** should not be used together. They are targeting different box types and they do not blend very well.

## 4.19 Files

**/tcb/tempfile**=*<file name>* (no default, initially `\jobname.tcbtemp`)

Sets *<file name>* as name for the temporary file which is used inside `tcbwritetemp`<sup>→ P. 98</sup> and `\tcbusetemp`<sup>→ P. 98</sup> implicitly.

## 4.20 \tcbox Specials

The following options are applicable for `\tcbox`<sup>→ P. 13</sup> and `\tcboxmath`<sup>→ P. 273</sup> only.

**/tcb/tcbox raise**=*<length>* (no default, initially **0pt**)

Raises the `\tcbox`<sup>→ P. 13</sup> by the given *<length>*.

```
\tcbset{colframe=blue!50!black,colback=white,colupper=red!50!black,
fonttitle=\bfseries,nobeforeafter,center title}

Test\dotfill
\tcbox[tcbox raise base]{Hello World 1}\dotfill
\tcbox{Hello World 2}\dotfill
\tcbox[tcbox raise=5mm]{Hello World 3}
```

Test ..... Hello World 1 ..... Hello World 2 ..... Hello World 3

**/tcb/tcbox raise base** (style, no value, initially **unset**)

Raises the `\tcbox`<sup>→ P. 13</sup> such that the base of its content matches the base of the environmental line; see example above.

**/tcb/on line** (style, no value, initially **unset**)

Combines `/tcb/tcbox raise base` with `/tcb/nobeforeafter`<sup>→ P. 72</sup>. The resulting box behaves analogue to `\fbox`.

## 4.21 Counters, Labels, and References

**/tcb/phantom**= $\langle code \rangle$  (no default, initially unset)

The  $\langle code \rangle$  is put in a box at the upper left corner of the `tcolorbox`. If the `tcolorbox` is breakable, the  $\langle code \rangle$  is executed for the first box of the break sequence only. If there already was some phantom code given, the new  $\langle code \rangle$  is appended.

The  $\langle code \rangle$  is intended to be used for counter stepping, labelling, and related operations which do not produce visible text.

- The  $\langle code \rangle$  is executed before the title and box content, i. e. counter values are ensured to be increased before usage.
- Labels are ensured to reference the correct page number.
- The  $\langle code \rangle$  is executed only once even during fitting operations for title and box content.
- In combination with the `hyperref` package, the hyper anchor is set to the upper left corner of the `tcolorbox`, i. e. links inside the pdf document will jump to the box pleasantly.
- Since the  $\langle code \rangle$  is executed inside a  $\text{\TeX}$  group, only global operations can survive this group.

Examples for the `phantom` usage are given in Section 13.9 from page 265, e. g. Example 13.1 on page 266.

**/tcb/nophantom** (no value, initially set)

Removes the phantom code if set before.

**/tcb/label**= $\langle marker \rangle$  (no default, initially unset)

The  $\langle marker \rangle$  is set as label text for a reference with the `\ref` macro. Typically, this option is used for numbered boxes, see Subsection 5.1 from page 92, e. g. `/tcb/new/autocounter`<sup>→ P. 92</sup>.

N 2014-11-28

**/tcb/phantomlabel**= $\langle marker \rangle$  (no default, initially unset)

Equivalent to `/tcb/label` for an *unnumbered* box. A `\phantomsection` from the package `hyperref` is used to set a correct hyperlink target. This is not needed for a numbered box.

**/tcb/label type**= $\langle type \rangle$  (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately.  $\langle type \rangle$  has to be a cross-reference type *known* to `cleveref` like `theorem`, `algorithm`, `result`, etc. References made with `cleveref` will use this type. Note that using `label type` will result in compilation errors, if `cleveref` is not loaded. For an example, see Theorem 14.3.5 on page 290.

**/tcb/no label type** (no value, initially set)

Removes a `/tcb/label type`, if set before.

**/tcb/step**= $\langle counter \rangle$  (no default, initially unset)

Shortcut for `phantom={\refstepcounter{#1}}`. The given  $\langle counter \rangle$  is increased and ready for labelling. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 92.

**/tcb/step and label**= $\{\langle counter \rangle\}\{\langle marker \rangle\}$  (no default, initially unset)

Shortcut for using `/tcb/step` and `/tcb/label`. This option is not needed when using the convenient automated numbering introduced with version 2.40, see Subsection 5.1 from page 92.

`/tcb/list entry=<text>` (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 97 is used, this key describes the `<text>` for an entry into the generated list, e.g.

```
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 13.9 from page 265 for a complete example.

N 2014-09-19

`/tcb/list text=<text>` (style, no default)

This is a shortcut for setting `/tcb/list entry` to `\protect\numberline{\thetcbcounter}<text>`. So, the following settings are identical:

```
list text={My beautiful Example},  
list entry={\protect\numberline{\thetcbcounter}My beautiful Example}
```

See Section 13.9 from page 265 for a complete example.

`/tcb/add to list={<list>}{<type>}` (no default, initially unset)

If the «list of tcolorbox(es)» feature described in Subsection 5.2 from page 97 is used, list entries are generated automatically. With this key, you can enforce an entry to the given `<list>` with the given `<type>`. This issues:

```
\addcontentsline{<list>}{<type>}{<entry text>}
```

`/tcb/check odd page=true|false` (default `true`, initially `false`)

If set to `true`, the even/odd page testing from the package `changepage` is applied. The `/tcb/toggle enlargement`<sup>P.79</sup> check and the `/tcb/toggle left and right`<sup>P.38</sup> check will use the `\ifoddpages` macro from this package or another package like `ifoddpages`. This options is independent from `/tcb/phantom`<sup>P.88</sup>. Note that you have to include the package `changepage` by hand<sup>3</sup>:

```
\usepackage{changepage}  
\strictpagecheck
```

The macro `\ifoddpages` can be used inside overlay or watermark code to test if the box is on an odd page. This will work also for boxes in a break sequence. Note that you cannot use the test inside the normal box content.

```
% \usepackage{changepage}  
\tcbset{colframe=blue!75!black,colback=white}  
  
\begin{tcolorbox}[enhanced,check odd page,  
  watermark text={\ifoddpages Odd\else Even\fi\ page!}]  
\lipsum[1]  
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

<sup>3</sup>If `changepage` is not included, a compilation error will arise.

## 4.22 Externalization

If the *externalization* library of the *tikz* package is used and */tcb/graphical environment*<sup>→ P.105</sup> is set to *tikzpicture*, a *tcolorbox* could trigger the externalization process which will arise a compilation error.

To avoid this, there are two possible strategies:

- Ensure, that `\tikzexternaldisable` is set before a *tcolorbox* is used. If you typically use the pattern `\tikzexternalenable some picture \tikzexternaldisable`, there is nothing to care about.
- If *externalization* is enabled globally, use */tcb/shield externalize* to shield any *tcolorbox*. The preamble code could look like this:

```
\usetikzlibrary{external}  
\tikzexternalize  
\tcbset{shield externalize}
```

*/tcb/shield externalize=true|false* (default *true*, initially *false*)

If set to *true*, the drawing part of the *tcolorbox* is not being externalized which is a good thing at the current state of art. Nevertheless, if the *tcolorbox* contains a *tikzpicture*, this picture is still externalized. Pictures drawn with help of */tcb/tikz upper*<sup>→ P.58</sup> or alike are *not* externalized.

If a *tcolorbox* is used inside a node of an encircling *tikzpicture* which is externalized, do *not* use `\tikzexternaldisable` in front of the *tcolorbox*. */tcb/shield externalize* is deactivated automatically inside a *tikzpicture*.

*/tcb/external=<file name>* (no default, initially unset)

Convenience option which calls `\tikzsetnextfilename{<file name>}`. Typically, it may be used inside the option list of a *tcolorbox* to set the externalization *<file name>* for the first *tikzpicture* which is discovered *inside* the box content. The package *tikz* [20] or the library *skins* has to be loaded to use this option. Additionally, `\usetikzlibrary{external}` has to be used.

*/tcb/remake=true|false* (default *true*, initially *false*)

Convenience option which calls */tikz/external/remake next*. Typically, it may be used inside the option list of a *tcolorbox* to force the remake of the first *tikzpicture* which is discovered *inside* the box content. The package *tikz* [20] or the library *skins* has to be loaded to use this option. Additionally, `\usetikzlibrary{external}` has to be used.

## 4.23 Miscellaneous

*/tcb/reset* (no value, initially set)

Sets (nearly) all *tcolorbox* settings (including loaded libraries) back to their default values *plus* any settings given by `\tcbsetforeverylayer`<sup>→ P.12</sup>. */tcb/savedelimiter*<sup>→ P.24</sup> and */tcb/capture*<sup>→ P.85</sup> keep their values. Also, all raster values (see Section 12 on page 221) are not resetted.

This option is useful for boxes in boxes where the inner box should not inherit the settings of the outer box. Note that for boxes inside boxes the *reset* is done automatically, if the standard settings of the package are used (v2.40 and above), see Section 4.16 from page 82.

**/tcb/only**=<⟨*overlay specification*⟩>{⟨*options*⟩} (style, no default, initially unset)

Sets the given `tcolorbox` ⟨*options*⟩ in dependency of a `beamer` ⟨*overlay specification*⟩. Note that this needs the `beamer` class. The ⟨*options*⟩ will only be used on the specified `beamer` frames.

```
\documentclass{beamer}
\usepackage[many]{tcolorbox}
\begin{document}

\begin{frame}
  \begin{tcolorbox}[title=My title,fonttitle=\bfseries,
    enhanced,colframe=red!50!black,colback=red!10,colbacktitle=red,
    sidebyside,righthand width=3cm,
    lowerbox=invisible,lower separated=false,
    drop lifted shadow,
    only=<1>{colbacktitle=yellow,coltitle=red!50!black,colframe=red},
    only=<3>{colback=yellow!50,watermark text={Attention!}},
    only=<3->{lowerbox=visible} ]
    This is a test.
  \begin{itemize}[<+>->]
    \item One
    \item Two
    \item \alert<3>{Three}
    \item Four
  \end{itemize}
  \tcblower
  \begin{equation*}
    \int\limits_{1}^{x} \frac{1}{t} \sim dt = \ln(x).
  \end{equation*}
  \end{tcolorbox}
\end{frame}

\end{document}
```

## 5 Initialization Option Keys

The *initialization* options are only applicable for the generation of new environments and commands based on `tcolorbox` and friends. Particularly, they can be used for

- `\newtcolorbox`<sup>→P.14</sup>,
- `\newtcbox`<sup>→P.15</sup>,
- `\newtcblisting`<sup>→P.236</sup>,
- `\newtcbinputlisting`<sup>→P.238</sup>,
- `\newtcbtheorem`<sup>→P.271</sup>, and
- `\newtcbboxfit`<sup>→P.315</sup>.

Typically, these options may generate counters and alike. It is **strongly** recommended that one use initialization options inside the preamble only. Otherwise, you may get trouble when using L<sup>A</sup>T<sub>E</sub>X's `\include` features.

### 5.1 Numbered Boxes

Counters assigned using the initialization options are administrated automatically. Especially, they are increased for each new box. Independent from the real counter name, the counter value can be referenced by `\thetcbcounter`, e.g. inside the title of the box. The real counter name is stored inside `\tcbcounter`.

`/tcb/new/auto counter` (no value, initially unset)

Creates a new counter automatically. With `/tcb/new/number format`<sup>→P.94</sup> and `/tcb/new/number within`<sup>→P.94</sup>, the appearance and behavior of the counter can be changed. The counter value is referenced by `\thetcbcounter`.

*Definition in the preamble:*

```
\newtcolorbox[auto counter,number within=section]{pabox}[2][]{%
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
  title=Examp.~\thetcbcounter: #2,#1}
```

```
\begin{pabox}[label={myautocounter}]{Title with number}
This box is automatically numbered with \ref{myautocounter} on page
\pageref{myautocounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{pabox}
```

#### Examp. 5.1: Title with number

This box is automatically numbered with 5.1 on page 92. Inside the box, the 5.1 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pabox`.

`/tcb/new/use counter from=<tclobox>` (no default, initially unset)

Here, a counter from another `<tclobox>` is reused. Note that the settings for `/tcb/new/number format`<sup>→ P.94</sup> and `/tcb/new/number within`<sup>→ P.94</sup> are inherited and cannot be changed. The counter value is referenced by `\thetcbcounter`.

```
\newtcolorbox[use counter from=pabox]{mybox}[2][]{%
colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounterfrom}]{Title with continued number}
This box is automatically numbered with \ref{myusecounterfrom} on page
\pageref{myusecounterfrom}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

#### Some Box 5.2: Title with continued number

This box is automatically numbered with 5.2 on page 93. Inside the box, the 5.2 can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@pabox`.

`/tcb/new/use counter=<counter>` (no default, initially unset)

Here, an ordinary existing L<sup>A</sup>T<sub>E</sub>X `<counter>` is used for numbering. With `/tcb/new/number format`<sup>→ P.94</sup> and `/tcb/new/number within`<sup>→ P.94</sup>, the appearance and behavior of the counter can be changed. The counter value is referenced by `\thetcbcounter`.

```
% \newcounter{myexample}% preamble
\newtcolorbox[use counter=myexample,number format=\Alph]{mybox}[2][]{%
colback=green!5!white,colframe=green!55!black,fonttitle=\bfseries,
title=Some Box \thetcbcounter: #2,#1}

\begin{mybox}[label={myusecounter}]{Title with \LaTeX\ number}
This box is automatically numbered with \ref{myusecounter} on page
\pageref{myusecounter}. Inside the box, the \thetcbcounter\ can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{mybox}
```

#### Some Box A: Title with L<sup>A</sup>T<sub>E</sub>X number

This box is automatically numbered with A on page 93. Inside the box, the A can also be referenced by `\thetcbcounter`. The real counter name is `myexample`.

N 2014-09-19

`/tcb/new/use counter*=<counter>` (no default, initially unset)

An existing L<sup>A</sup>T<sub>E</sub>X `<counter>` is used for numbering. In contrast to `/tcb/new/use counter`, the options `/tcb/new/number format`<sup>→ P.94</sup> and `/tcb/new/number within`<sup>→ P.94</sup> are ignored. Use this for counters which are already configured outside the `tcolorbox` package, e.g. the standard `figure` counter.

`/tcb/new/no counter` (no value, initially set)

The created boxes are not numbered. This is the default. The option may be used to overrule a previous option.



`/tcb/new/number within=<counter>` (no default, initially unset)

The automatic counter is set to zero, if `<counter>` is increased. Additionally, during output, the value of `<counter>` is prepended to the value of the automatic counter.

To prepend the automatic counter with the chapter number and to reset it with every new chapter, use:

```
number within=chapter
```

See `/tcb/new/use counter`<sup>→ P.93</sup> for a complete example.

`/tcb/new/number format=<format macro>` (no default, initially `\arabic`)

Declares the format of the automatic counter. The `<format macro>` can be any valid L<sup>A</sup>T<sub>E</sub>X number formatting macro like `\arabic`, `\roman`, etc.

To display the counter value in large roman numbers, use:

```
number format=\Roman
```

See `/tcb/new/auto counter`<sup>→ P.92</sup> for a complete example.

`/tcb/new/number freestyle=<code>` (no default, initially unset)

Allows advanced control over the complete number format. This option overrules the format given by `/tcb/new/number within` and `/tcb/new/number format`. Nevertheless, you can combine it with `/tcb/new/number within` to get the desired reset property.

The `<code>` is some formatting code which should contain `\tcbcounter` to reference the automated counter. Since this `<code>` is expanded, you have to secure each macro with `\noexpand` with exception of `\tcbcounter`.

*Definition in the preamble:*

```
\newtcolorbox[auto counter,number within=section,
  number freestyle={(Q/\noexpand\thesection/\noexpand\Alph{\tcbcounter})},
  ]{phbox}[2][]{%
  colback=yellow!15!white,colframe=blue!75!black,fonttitle=\bfseries,
  title=Question~\thetcbcounter: #2,#1}
```

```
\begin{phbox}[label={myfreestyle}]{Title with freestyle number}
This box is automatically numbered with \ref{myfreestyle} on page
\pageref{myfreestyle}. Inside the box, the \thetcbcounter can
also be referenced by |\thetcbcounter|.
The real counter name is \texttt{\tcbcounter}.
\end{phbox}
```

**Question (Q/5/A): Title with freestyle number**

This box is automatically numbered with (Q/5/A) on page 94. Inside the box, the (Q/5/A) can also be referenced by `\thetcbcounter`. The real counter name is `tcb@cnt@phbox`.



The following options `/tcb/new/crefname` and `/tcb/new/Crefname` need to be set inside the preamble.

U 2014-12-01

`/tcb/new/crefname={⟨singular⟩}{⟨plural⟩}` (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the lowercase `⟨singular⟩` and `⟨plural⟩` forms of the cross-reference are given. This type is the environment or macro name and `/tcb/label type→P.88` is set automatically. See `/tcb/label type→P.88` and [5] for more information.

U 2014-12-01

`/tcb/new/Crefname={⟨singular⟩}{⟨plural⟩}` (no default, initially unset)

This option key can be used only in conjunction with the `cleveref` package [5] which has to be loaded separately. It creates a cross-reference type for the new `tcolorbox`'es, where the uppercase `⟨singular⟩` and `⟨plural⟩` forms of the cross-reference are given. This type is the environment or macro name and `/tcb/label type→P.88` is set automatically. See `/tcb/label type→P.88` and [5] for more information.

*Definition in the preamble:*

```
% \usepackage{cleveref}
\newtcolorbox[auto counter,number within=section,
crefname={bluebox}{blueboxes}]%
{mybluebox}[2][{}]{colback=blue!5!white,colframe=blue!75!black,fonttitle=\bfseries,
title=Bluebox \thetcbcounter: #2,#1}
```

```
% \usepackage{varioref}
% \usepackage{cleveref}
\begin{mybluebox}[label={myreference}]{My title}
This is an example.
\end{mybluebox}

\Cref{myreference}, \cref{myreference}.\
\Cpageref{myreference}, \cpageref{myreference}.\
\nameCref{myreference}, \namecref{myreference}.\
\labelcref{myreference}, \labelcpageref{myreference}.\
With \texttt{varioref}:\
\Vref{myreference}, \vref{myreference}.\
\Vref*{myreference}, \vref*{myreference}.
```

**Bluebox 5.1: My title**

This is an example.

Bluebox 5.1, bluebox 5.1.

Page 95, page 95.

Bluebox, bluebox.

5.1, 95.

With `varioref`:

Bluebox 5.1, bluebox 5.1.

Bluebox 5.1, bluebox 5.1.

`/tcb/new/blend into=<name>` (style, no default, initially unset)

Used to comfortably blend into an existing schema of naming and numbering for some selected cases. For example, a `tcolorbox` can be used to display and entitle an image pretending to be a standard `figure` environment. Here, `/tcb/title`<sup>P.17</sup> is used instead of the standard `\caption` and `/tcb/list text`<sup>P.89</sup> can be used instead of the optional parameter of the standard `\caption`.

Feasible values for `<name>` are:

- **figures**: blend into the standard `figure` environment.
- **tables**: blend into the standard `table` environment.
- **listings**: blend into the standard `lstlistings` environment of the package `listings` [6].

Note that `blend into=listings` can only be used in the document content or, preferably, inside a `\AtBeginDocument` clause! Using it without `\AtBeginDocument` inside the preamble does not work since the `listings` packages initializes its counter also inside `\AtBeginDocument`.

```
\begin{figure}[htb]
  \centering\includegraphics[height=4cm]{lichtspiel.jpg}
  \caption{A standard figure}
\end{figure}

\newtcolorbox[blend into=figures]{myfigure}[2][\float=htb,capture=hbox,
  title={#2},every float=\centering,#1]

\begin{myfigure}{A tcolorbox figure}
  \includegraphics[height=4cm]{lichtspiel.jpg}
\end{myfigure}
```





Figure 1: A standard figure

Figure 2: A tcolorbox figure



## 5.2 Lists of tcolorboxes

For figures and tables, L<sup>A</sup>T<sub>E</sub>X provides the `\listoffigures` and `\listoftables` commands to create lists of these numbered entities. Also, a `tcolorbox` can be part of such a kind of list.

1. Assign a list  $\langle name \rangle$  by the *initialization* option `/tcb/new/list inside`.
2. Optionally, a new  $\langle type \rangle$  for list entries may be assigned by the *initialization* option `/tcb/new/list type`.
3. List entries are generated automatically within each new `tcolorbox` using the above initialization.
  - If `/tcb/list entry`<sup>→ P.89</sup> is set, the entry is generated with it.
  - Otherwise, if `/tcb/title`<sup>→ P.17</sup> is set, the entry is generated with it.
  - Otherwise, the entry is generated with the current number and the environment name.
4. The generated list is displayed by `\tcblistof`.

`/tcb/new/list inside= $\langle name \rangle$`  (no default, initially unset)

Assigns a list or contents file to the generated `tcolorboxes`. Entries to this list are saved to a file which gets the  $\langle name \rangle$  as file name extension. The list is referenced by this name in `\tcblistof`. For example:

```
list inside=exam
```

See Section 13.9 from page 265 for a complete example.

`/tcb/new/list type= $\langle type \rangle$`  (no default, initially `tcolorbox`)

Optionally, some  $\langle type \rangle$  can be assigned to the list entries. For a new  $\langle type \rangle$ , a macro `\l@ $\langle type \rangle$`  has to exist which controls the format of the list entry. The default type is defined by

```
\newcommand*\l@tcolorbox{\@dottedtocline{1}{1.5em}{2.3em}}
```

This is identical to the `\l@section` setting of L<sup>A</sup>T<sub>E</sub>X. `\l@tcolorbox` can be redefined or a new  $\langle type \rangle$  can be assigned.

`\tcblistof[ $\langle macro \rangle$ ]{ $\langle name \rangle$ }{ $\langle title text \rangle$ }`

Displays the generated list of `tcolorboxes` with the given  $\langle name \rangle$ . The heading is generated by  $\langle macro \rangle$ { $\langle title text \rangle$ } where `\section` is the default setting for  $\langle macro \rangle$ .

To display the list inside a subsection, use for example:

```
\tcblistof[\subsection]{exam}{List of Exercises}
```

The result of the example is found as Subsection 13.10 on page 268.

The core of the list is generated by `\starttoc{ $\langle name \rangle$ }` which can be wrapped into an own macro.

## 6 Saving and Loading of Verbatim Texts

The following macros are slightly modified versions of the original macros from the known packages `moreverb` and `verbatim`. They are used implicitly inside of a `tcolorbox` environment, but they can be used outside also.

```
\begin{tcbverbatimwrite}{\file name}  
  \environment content  
\end{tcbverbatimwrite}
```

Saves the `\environment content` to a file named by `\file name`. T<sub>E</sub>X macros inside the environment are not expanded.

```
\begin{tcbverbatimwrite}{\jobname_verbexp.tex}  
  This text is saved \textit{as is}.  
\end{tcbverbatimwrite}  
  
Now, we are using the file:\par  
\input{\jobname_verbexp.tex}
```

Now, we are using the file:  
This text is saved *as is*.

This environment may be used inside an own environment. Note, that inside the environment definition `\tcbverbatimwrite` has to be used instead of `\begin{tcbverbatimwrite}` and `\end{tcbverbatimwrite}` instead of `\end{tcbverbatimwrite}`.

```
\newenvironment{myverbatim}{%  
  \begin{group}\tcbverbatimwrite{\jobname_myverb.tex}}%  
  {\end{tcbverbatimwrite}\endgroup}  
  
\begin{myverbatim}  
  This is the text which is saved by my own environment.  
\end{myverbatim}  
  
Now, we are using the file:\par  
\input{\jobname_myverb.tex}
```

Now, we are using the file:  
This is the text which is saved by my own environment.

```
\begin{tcbwritetemp}  
  \environment content  
\end{tcbwritetemp}
```

Has the same function as `tcbverbatimwrite`, but uses the key value of `tempfile` for the file name.

```
\begin{tcbwritetemp}  
  This text is saved \textit{as is}.  
\end{tcbwritetemp}  
  
Now, we are using the file:\par  
\tcbusetemp
```

Now, we are using the file:  
This text is saved *as is*.

```
\tcbusetemp
```

Loads the current temporary file which was saved by `tcbwritetemp`.

## 7 Recording

The package provides some macros and options to take *records* during compilation. This is done by L<sup>A</sup>T<sub>E</sub>X file operations to save some data to a file for later usage. The main application scenario is depicted in Section 7.3 on the next page where informations about example solutions are recorded and read again in Section 7.4 on page 103.

### 7.1 Makros

N 2014-11-28

**\tcbstartrecording**[*<file name>*]

Opens a file denoted by *<file name>* for writing the records. The default file name is `\jobname.records`. See Section 7.3 on the next page for an example application.

N 2014-11-28

**\tcbrecord**{*<content>*}

Records any *<content>* to the record file. `\tcbrecord` is implemented as `\immediate\write`. `\tcbstartrecording` has to be called before; otherwise, `\tcbrecord` is silently ignored.

```
\tcbrecord{\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28

**\tcbstoprecording**

Closes the current record file which was opened by `\tcbstartrecording` before.

N 2014-11-28

**\tcbinputrecords**[*<file name>*]

Opens a file denoted by *<file name>* for reading the records via `\input`. The default file name is the name of the last used record file for saving. `\tcbstoprecording` has to be called before.

### 7.2 Options

N 2014-11-28

**/tcb/record**=*<content>* (style, no default)

Records any *<content>* to the record file, see `\tcbrecord`. This key can be used several times to write several lines.

```
record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}}
```

N 2014-11-28

**/tcb/no recording**

Disables `\tcbrecord` and `/tcb/record` inside the current group.

### 7.3 Example: Exercises

The following application example creates exercises and their corresponding solutions. Each pair is generated inside a single `tcolorbox` where the solution is given below `\tcbblower`<sup>→P.11</sup>. For every example, the solution part is saved by `/tcb/savelowerto`<sup>→P.22</sup> to a file. The saving is recorded using `/tcb/record`<sup>→P.99</sup>. To enlighten the possibilities, the second exercise has no solution. Finally, the solutions are input in Section 7.4 on page 103.

*Definition in the preamble:*

```
% \tcbuselibrary{skins,xparse}

\NewTColorBox[auto counter,number within=section]{exercise}{+0{}}{%
  enhanced,colframe=green!20!black,colback=yellow!10!white,coltitle=green!40!black,
  fonttitle=\bfseries,
  underlay={\begin{tcbclipinterior}
    \shade[inner color=green!80!yellow,outer color=yellow!10!white]
      (interior.north west) circle (2cm);
    \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
      (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
  title={Exercise~\thetcbcounter:},
  label={exercise@\thetcbcounter},
  attach title to upper=\quad,
  after upper={\par\hfill\textcolor{green!40!black}{%
    {\itshape Solution on page~\pageref{solution@\thetcbcounter}}}},
  lowerbox=ignored,
  savelowerto=solutions/exercise-\thetcbcounter.tex,
  record={\string\solution{\thetcbcounter}{solutions/exercise-\thetcbcounter.tex}},
  #1
}

\NewTotalTColorBox{\solution}{mm}{%
  enhanced,colframe=red!20!black,colback=yellow!10!white,coltitle=red!40!black,
  fonttitle=\bfseries,
  underlay={\begin{tcbclipinterior}
    \shade[inner color=red!50!yellow,outer color=yellow!10!white]
      (interior.north west) circle (2cm);
    \draw[help lines,step=5mm,yellow!80!black,shift={(interior.north west)}]
      (interior.south west) grid (interior.north east);
    \end{tcbclipinterior}},
  title={Solution of Exercise~\ref{exercise@#1} on page~\pageref{exercise@#1}:},
  phantomlabel={solution@#1},
  attach title to upper=\par,
}{\input{#2}}

\tcbset{no solution/.style={no recording,after upper=}}
```

```
\tcbstartrecording

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\sin((\sin x)^2)
  \end{equation*}
\tcbblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \sin((\sin x)^2) \right)' \\
    &= \cos((\sin x)^2) 2\sin x \cos x.
  \end{align*}
\end{exercise}
```

```

\end{exercise}

\begin{exercise}[no solution]
  It holds:
  \begin{equation*}
    \frac{d}{dx}\left(\ln|x|\right) = \frac{1}{x}.
  \end{equation*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=(\sin(\sin x))^2
  \end{equation*}
  \tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( (\sin(\sin x))^2 \right)' \\
    &= 2\sin(\sin x)\cos(\sin x)\cos x.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\sqrt{x^3-6x^2+2x}
  \end{equation*}
  \tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \sqrt{x^3-6x^2+2x} \right)' \\
    &= \frac{3x^2-12x+2}{2\sqrt{x^3-6x^2+2x}}.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\left(\frac{2+3x}{1-2x}\right)^3
  \end{equation*}
  \tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \left(\frac{2+3x}{1-2x}\right)^3 \right)' \\
    &= 3 \left(\frac{2+3x}{1-2x}\right)^2 \frac{(1-2x)^3-(2+3x)(-2)}{(1-2x)^2} \\
    &= \frac{21(2+3x)^2}{(1-2x)^4}.
  \end{align*}
\end{exercise}

\begin{exercise}
  Compute the derivative of the following function:
  \begin{equation*}
    f(x)=\frac{\cos x}{(\tan 2x)^2}
  \end{equation*}
  \tcblower
  The derivative is:
  \begin{align*}
    f'(x) &= \left( \frac{\cos x}{(\tan 2x)^2} \right)' \\
    &= \left( \frac{\cos x}{(\cos 2x)^2} \cdot (\sin 2x)^2 \right)' \\
    &= \frac{(\sin 2x)^2}{(\cos 2x)^4} [(-\sin x)(\cos 2x)^2 + (\cos x)4\cos 2x (-\sin 2x)] \\
    &\quad - \cos x (\cos 2x)^2 4\sin 2x \cos 2x (\sin 2x)^4 \\
    &= -\frac{\cos(2x)}{(\sin x \sin 2x \cos 2x + 4\cos x(\sin 2x)^2} \\
    &\quad + 4 \cos x (\cos 2x)^2 (\sin 2x)^3
  \end{align*}

```



```

&= -\frac{\cos(2x)}{(\sin x \sin 2x \cos 2x + 4 \cos x)}{(\sin 2x)^3}.
\end{align*}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x)=\cos((2x^2+3)^3)
\end{equation*}
\end{exercise}
\tcblower
The derivative is:
\begin{align*}
f'(x) &= \left( \cos((2x^2+3)^3) \right)' \\
&= -\sin((2x^2+3)^3) \cdot 3(2x^2+3)^2 \cdot 2x \\
&= -12x(2x^2+3)^2 \sin((2x^2+3)^3).
\end{align*}
\end{exercise}

\begin{exercise}
Compute the derivative of the following function:
\begin{equation*}
f(x)=(x^2+1)\sqrt{x^4+1}
\end{equation*}
\end{exercise}
\tcblower
The derivative is:
\begin{align*}
f'(x) &= \left( (x^2+1)\sqrt{x^4+1} \right)' \\
&= 2x\sqrt{x^4+1} + \frac{2x^3(x^2+1)}{\sqrt{x^4+1}}.
\end{align*}
\end{exercise}
\tcbstoprecording

```

**Exercise 7.1:** Compute the derivative of the following function:

$$f(x) = \sin((\sin x)^2)$$

*Solution on page 103*

**Exercise 7.2:** It holds:

$$\frac{d}{dx} (\ln x) = \frac{1}{x}.$$

**Exercise 7.3:** Compute the derivative of the following function:

$$f(x) = (\sin(\sin x))^2$$

*Solution on page 103*

**Exercise 7.4:** Compute the derivative of the following function:

$$f(x) = \sqrt{x^3 - 6x^2 + 2x}$$

*Solution on page 104*



**Exercise 7.5:** Compute the derivative of the following function:

$$f(x) = \left( \frac{2+3x}{1-2x} \right)^3$$

*Solution on page 104*

**Exercise 7.6:** Compute the derivative of the following function:

$$f(x) = \frac{\cos x}{(\tan 2x)^2}$$

*Solution on page 104*

**Exercise 7.7:** Compute the derivative of the following function:

$$f(x) = \cos((2x^2 + 3)^3)$$

*Solution on page 104*

**Exercise 7.8:** Compute the derivative of the following function:

$$f(x) = (x^2 + 1)\sqrt{x^4 + 1}$$

*Solution on page 104*

## 7.4 Example: Solutions

This concludes the example given in Section 7.3 on page 100. Now, the saved and recorded solutions are included.

`\tcbinputrecords`

**Solution of Exercise 7.1 on page 102:**

The derivative is:

$$f'(x) = \left( \sin((\sin x)^2) \right)' = \cos((\sin x)^2) 2 \sin x \cos x.$$

**Solution of Exercise 7.3 on page 102:**

The derivative is:

$$f'(x) = \left( (\sin(\sin x))^2 \right)' = 2 \sin(\sin x) \cos(\sin x) \cos x.$$

**Solution of Exercise 7.4 on page 102:**

The derivative is:

$$f'(x) = \left( \sqrt{x^3 - 6x^2 + 2x} \right)' = \frac{3x^2 - 12x + 2}{2\sqrt{x^3 - 6x^2 + 2x}}.$$

**Solution of Exercise 7.5 on page 103:**

The derivative is:

$$f'(x) = \left( \left( \frac{2+3x}{1-2x} \right)^3 \right)' = 3 \left( \frac{2+3x}{1-2x} \right)^2 \frac{(1-2x)3 - (2+3x)(-2)}{(1-2x)^2} = \frac{21(2+3x)^2}{(1-2x)^4}.$$

**Solution of Exercise 7.6 on page 103:**

The derivative is:

$$\begin{aligned} f'(x) &= \left( \frac{\cos x}{(\tan 2x)^2} \right)' = \left( \frac{\cos x (\cos 2x)^2}{(\sin 2x)^2} \right)' \\ &= \frac{(\sin 2x)^2 [(-\sin x)(\cos 2x)^2 + (\cos x)4 \cos 2x(-\sin 2x)] - \cos x (\cos 2x)^2 4 \sin 2x \cos 2x}{(\sin 2x)^4} \\ &= -\frac{\cos(2x) [\sin x \sin 2x \cos 2x + 4 \cos x (\sin 2x)^2 + 4 \cos x (\cos 2x)^2]}{(\sin 2x)^3} \\ &= -\frac{\cos(2x) [\sin x \sin 2x \cos 2x + 4 \cos x]}{(\sin 2x)^3}. \end{aligned}$$

**Solution of Exercise 7.7 on page 103:**

The derivative is:

$$\begin{aligned} f'(x) &= \left( \cos((2x^2 + 3)^3) \right)' = -\sin((2x^2 + 3)^3) 3(2x^2 + 3)^2 \cdot 2x \\ &= -12x(2x^2 + 3)^2 \sin((2x^2 + 3)^3). \end{aligned}$$

**Solution of Exercise 7.8 on page 103:**

The derivative is:

$$f'(x) = \left( (x^2 + 1)\sqrt{x^4 + 1} \right)' = 2x\sqrt{x^4 + 1} + \frac{2x^3(x^2 + 1)}{\sqrt{x^4 + 1}}.$$

## 8 Technical Overview and Customization

This section provides a technical overview of the skin concept of `tcolorbox`. For most applications of `tcolorbox`, one will not need to know the bells and whistles described herein. You may proceed to Section 9 on page 117 where the customization options for most users are documented.

The following explanations also cover options and settings from the `skins` library, see Section 9 on page 117.

### 8.1 Skins and Drawing Engines


From a technical point of view, a *skin* is a style definition for the appearance of a `tcolorbox`. The core package provides some additional option keys for skins but only two skins called `standard`<sup>P. 166</sup> and `standard jigsaw`<sup>P. 167</sup>. The `skins` library adds several more skins. To change to a skin, only one option from the core package has to be set.

**`/tcb/skin=<name>`** (style, no default, initially `standard`)

Sets the current skin to `<name>`. This is a style definition which sets all the following keys, i.e. for many use cases there is nothing more to do.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,
width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=ske}

\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[skin=beamer,beamer,adjusted title=My title]
  This is my content.
\end{tcolorbox}
```



**`/tcb/skin first=<name>`** (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`<sup>P. 296</sup> and *is* broken actually, then the skin for the *first* part of the break sequence is set to `<name>`, see Subsection 15.6 on page 305. Typically, this key is set by a `/tcb/skin`.

**`/tcb/skin middle=<name>`** (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`<sup>P. 296</sup> and *is* broken actually, then the skin for the *middle* parts (if any) of the break sequence is set to `<name>`, see Subsection 15.6 on page 305. Typically, this key is set by a `/tcb/skin`.

**`/tcb/skin last=<name>`** (style, no default, initially `standard`)

If the box is set to be `/tcb/breakable`<sup>P. 296</sup> and *is* broken actually, then the skin for the *last* part of the break sequence is set to `<name>`, see Subsection 15.6 on page 305. Typically, this key is set by a `/tcb/skin`.

**`/tcb/graphical environment=<name>`** (no default, initially `pgfpicture`)

Sets the graphical environment for the `tcolorbox` to `<name>`. Feasible values are `pgfpicture` and `tikzpicture` or environments which inherit from one of these two. This key is set by a `/tcb/skin` and may seldom be used directly.

The skin of a `tcolorbox` is drawn by up to four *engines*. Afterwards, the text content is drawn which is not part of a skin. The four steps are:

1. The *frame* of the box, drawn by `/tcb/frame engine`.
2. The *interior* of the box. The interior of a box with title is drawn differently from a box without title. `/tcb/interior titled engine` or `/tcb/interior engine`<sup>→ P. 107</sup> is used to draw the interior.
3. The *segmentation* (line) of the box, if there is a lower part; drawn by `/tcb/segmentation engine`<sup>→ P. 107</sup>.
4. The *title area* of the box, if there is a title and `/tcb/title filled`<sup>→ P. 25</sup> is set to `true`; drawn by `/tcb/title engine`<sup>→ P. 107</sup>.

`/tcb/frame engine=⟨name⟩` (no default, initially `standard`)

Sets the *frame* drawing engine for a box to `⟨name⟩`. Typically, this key is set by a `/tcb/skin`<sup>→ P. 105</sup>. Feasible values for `⟨name⟩` are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `pathjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `pathfirstjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `pathmiddlejigsaw`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `pathlast`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `pathlastjigsaw`: a `tikz` path which is controlled by `/tcb/frame style`<sup>→ P. 117</sup>,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/interior titled engine=⟨name⟩` (no default, initially `standard`)

Sets the *interior* drawing engine for a titled box to `⟨name⟩`. Typically, this key is set by a `/tcb/skin`<sup>→ P. 105</sup>. Feasible values for `⟨name⟩` are:

- `standard`: the original code from the core package,
- `path`: a `tikz` path which is controlled by `/tcb/interior style`<sup>→ P. 118</sup>,
- `pathfirst`: a `tikz` path which is controlled by `/tcb/interior style`<sup>→ P. 118</sup>,
- `pathmiddle`: a `tikz` path which is controlled by `/tcb/interior style`<sup>→ P. 118</sup>,
- `pathlast`: a `tikz` path which is controlled by `/tcb/interior style`<sup>→ P. 118</sup>,
- `freelance`: deprecated.
- `spartan`: a quite spartan code.
- `empty`: draw nothing.

`/tcb/interior engine=<name>` (no default, initially **standard**)

Sets the *interior* drawing engine for an untitled box to `<name>`. Typically, this key is set by a `/tcb/skin`<sup>→P.105</sup>. Feasible values for `<name>` are:

- **standard**: the original code from the core package,
- **path**: a tikz path which is controlled by `/tcb/interior style`<sup>→P.118</sup>,
- **pathfirst**: a tikz path which is controlled by `/tcb/interior style`<sup>→P.118</sup>,
- **pathmiddle**: a tikz path which is controlled by `/tcb/interior style`<sup>→P.118</sup>,
- **pathlast**: a tikz path which is controlled by `/tcb/interior style`<sup>→P.118</sup>,
- **freelance**: deprecated.
- **spartan**: a quite spartan code.
- **empty**: draw nothing.

`/tcb/segmentation engine=<name>` (no default, initially **standard**)

Sets the *segmentation* (line) drawing engine for a box to `<name>`. Typically, this key is set by a `/tcb/skin`<sup>→P.105</sup>. Feasible values for `<name>` are:

- **standard**: the original code from the core package,
- **path**: a tikz path which is controlled by `/tcb/segmentation style`<sup>→P.120</sup>,
- **freelance**: deprecated.
- **spartan**: a quite spartan code.
- **empty**: draw nothing.

`/tcb/title engine=<name>` (no default, initially **standard**)

Sets the *title area* drawing engine for a titled box to `<name>`. Typically, this key is set by a `/tcb/skin`<sup>→P.105</sup>. Feasible values for `<name>` are:

- **standard**: the original code from the core package,
- **path**: a tikz path which is controlled by `/tcb/title style`<sup>→P.120</sup>,
- **pathfirst**: a tikz path which is controlled by `/tcb/title style`<sup>→P.120</sup>,
- **pathmiddle**: a tikz path which is controlled by `/tcb/title style`<sup>→P.120</sup>,
- **pathlast**: a tikz path which is controlled by `/tcb/title style`<sup>→P.120</sup>,
- **freelance**: deprecated.
- **spartan**: a quite spartan code.
- **empty**: draw nothing.

After an engine is set to an initializing value, the resulting graphical code can be changed using code option keys, see Section 8.2 on page 109.



`/tcb/geometry nodes=true|false` (default `true`, initially `false`)

If set to `true`, up to four `tikz` nodes are defined for a `tcolorbox` which are named `frame`, `interior`, `segmentation`, and `title`. These nodes describe the boundaries of the equally named parts of a `tcolorbox`. They are used by most engines based on `TikZ`. Typically, this key is set automatically by a `/tcb/skin` <sup>→ P. 105</sup>.

```
\tcbset{colback=Salmon!50!white,colframe=FireBrick!75!black,
width=(\linewidth-8mm)/2,before=,after=\hfill,equal height group=geon}

\begin{tcolorbox}[adjusted title=The title]
  The upper part.\tcblower The lower part.
\end{tcolorbox}

\begin{tcolorbox}[enhanced,adjusted title=The title,
frame code={\path[draw=red,fill=red!25]
  (frame.south west) rectangle (frame.north east);},
interior titled code={\path[draw=blue,fill=blue!25]
  (interior.south west) rectangle (interior.north east);},
segmentation code={\path[draw=green,fill=green!25]
  (segmentation.south west) rectangle (segmentation.north east);},
title code={\path[draw=black,fill=brown!75!black]
  (title.south west) rectangle (title.north east);}]
  The upper part.\tcblower The lower part.
\end{tcolorbox}
```




## 8.2 Code Option Keys

The following code options are applicable for all skins. The used  $\langle graphical\ code \rangle$  can be any pgf code. For all skins with exception of `standard`<sup>P.166</sup> and `standard jigsaw`<sup>P.167</sup>, the  $\langle graphical\ code \rangle$  can also be any TikZ code.

`/tcb/frame code= $\langle graphical\ code \rangle$`  (code, default from `standard`)

The given  $\langle graphical\ code \rangle$  is used for drawing the *frame* of the box.




`/tcb/frame empty` (style, no value)

This is a shortcut for setting `/tcb/frame code` to empty. This option removes the drawing of the frame. Alternatively, use `/tcb/frame hidden`<sup>P.118</sup>.

`/tcb/interior titled code= $\langle graphical\ code \rangle$`  (code, default from `standard`)

The given  $\langle graphical\ code \rangle$  is used for drawing the *interior* of the box, if the box comes with a title.



`/tcb/interior titled empty` (style, no value)

This is a shortcut for setting `/tcb/interior titled code` to empty. This option removes the drawing of the untitled interior. Alternatively, use `/tcb/interior hidden`<sup>P.119</sup>.




`/tcb/interior code=<graphical code>` (code, default from `standard`)

The given `<graphical code>` is used for drawing the *interior* of the box, if the box is without a title.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[enhanced,interior code={
  \path[draw=red!5!white,line width=5mm,line cap=round]
    ([xshift=3mm,yshift=-3mm]interior.north west)
    --([xshift=-3mm,yshift=3mm]interior.south east)
    ([xshift=3mm,yshift=3mm]interior.south west)
    --([xshift=-3mm,yshift=-3mm]interior.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/interior empty` (style, no value)

This is a shortcut for setting `/tcb/interior code` to empty. This option removes the drawing of the interior. Alternatively, use `/tcb/interior hidden` <sup>→ P. 119</sup>.

`/tcb/segmentation code=<graphical code>` (code, default from `standard`)

The given `<graphical code>` is used for drawing the *segmentation* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,segmentation code={
  \path[top color=red!5!white,bottom color=red!5!white,middle color=blue]
    (segmentation.south west) rectangle (segmentation.north east);}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/segmentation empty` (style, no value)


This is a shortcut for setting `/tcb/segmentation code` to empty. This option removes the drawing of the segmentation line. Alternatively, use `/tcb/segmentation hidden` <sup>→ P. 120</sup>.

`/tcb/title code=<graphical code>` (code, default from `standard`)

The given `<graphical code>` is used for drawing the *title* area of the box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,title code={
  \path[draw=yellow,solid,decorate,line width=2mm,
    decoration={coil,aspect=0,segment length=10.1mm}]
    ([xshift=1mm]title.west) -- ([xshift=-1mm]title.east);}]
  This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



`/tcb/title empty` (style, no value)

This is a shortcut for setting `/tcb/title code` to empty. This option removes the drawing of the title area. Alternatively, use `/tcb/title hidden`<sup>→P.121</sup>.

### 8.3 Subskins

A subskin is a new `/tcb/skin`<sup>P.105</sup> based on an existing skin which is extended or changed.

Never use geometry settings or bounding box options inside a subskin definition! If one skin is replaced by another skin, the overall bounding box should stay constant. Especially, if a skin is used for a breakable box, unpredictable and unpleasant results could arise otherwise. If you want to change the geometry also, use an additional style. See the skin `beamer`<sup>→ P. 186</sup> and the style `/tcb/beamer`<sup>→ P. 186</sup> as pattern.

$$\texttt{\textbackslash tcbsubskin}\{\langle name \rangle\}\{\langle base skin \rangle\}\{\langle options \rangle\}$$

Creates a new skin `<name>` which inherits all properties of an existing `<base skin>` plus the given `<options>`. The new skin `<name>` can be used as value for the keys `/tcb/skin`<sup>P. 105</sup>, `/tcb/skin first`<sup>P. 105</sup>, `/tcb/skin middle`<sup>P. 105</sup>, and `/tcb/skin last`<sup>P. 105</sup>. As `<base skin>`, one can take `standard`<sup>P. 166</sup>, `empty`<sup>P. 195</sup>, `enhanced`<sup>P. 168</sup>, or any skin from the `lib skins` library, see Section 9 on page 117.

```
% \tcbuselibrary{skins}
\tcbsubskin{mycross}{empty}{frame code={%
  \draw[red,line width=5pt] (frame.south west)--(frame.north east);
  \draw[red,line width=5pt] (frame.north west)--(frame.south east);},
  skin first=mycross,skin middle=mycross,skin last=mycross }

\begin{tcolorbox}[skin=mycross]
  This is my content.
\end{tcolorbox}
```

This is my content.

`/tcb/skin first is subskin of`= $\{\langle base\ skin \rangle\}\{\langle options \rangle\}$  (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing  $\langle base\ skin \rangle$  plus the given  $\langle options \rangle$ . This skin is set as `/tcb/skin first`<sup>P.105</sup>.

See a detailed example on page 200.

`/tcb/skin middle is subskin of={⟨base skin⟩}{⟨options⟩}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing  $\langle base\ skin \rangle$  plus the given  $\langle options \rangle$ . This skin is set as `/tcb/skin middle`<sup>P. 105</sup>.

See a detailed example on page 200.

`/tcb/skin last is subskin of={⟨base skin⟩}{⟨options⟩}` (no default, initially unset)

Creates a new unnamed skin which inherits all properties of an existing  $\langle base\ skin \rangle$  plus the given  $\langle options \rangle$ . This skin is set as `/tcb/skin last`<sup>P.105</sup>.

See a detailed example on page 200.

## 8.4 Drawing Scheme

Depending on the complexity of a `tcolorbox` definition, the resulting box is drawn in a more or less complex series of steps.

To document and demonstrate these drawing steps, we consider the following box definition:

```
\newtcolorbox{testbox}[1][\{enhanced,title=Test Box,
  boxrule=1mm,titlerule=0.5mm,colframe=blue!50!black,
  interior style={top color=blue!20!green!50!white,bottom color=blue!20!yellow!50!white},
  colbacktitle=blue!50!green!90!white,segmentation style={solid},
  fonttitle=\bfseries,drop fuzzy shadow,borderline={0.3mm}{0.35mm}{yellow!50!white},
  underlay={\path[fill image opacity=0.15,fill image scale=0.9,
    fill stretch picture={\draw[blue,line width=2mm] circle (1);}}
    (interior.south west) rectangle (interior.north east);},
  watermark text={Watermark},watermark color={green!20!white},
  finish={\begin{tcbclipframe}
    \path[bottom color=black,top color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;
    \path[top color=white,bottom color=black!50!white,opacity=0.1]
      (frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;
  \end{tcbclipframe}}{#1}
```


For this definition, we get the maximal number of drawing steps:

1. shadow

- Section 9.6 on page 147.

2. frame

- `/tcb/colframe`  $\rightarrow$  P. 25, `/tcb/opacityframe`  $\rightarrow$  P. 43
- `/tcb/frame code`  $\rightarrow$  P. 109
- `/tcb/frame style`  $\rightarrow$  P. 117



### 3. interior

- `/tcb/colback`  $\rightarrow$  P. 25, `/tcb/opacityback`  $\rightarrow$  P. 43
- `/tcb/interior code`  $\rightarrow$  P. 110, `/tcb/interior titled code`  $\rightarrow$  P. 109
- `/tcb/interior style`  $\rightarrow$  P. 118




### 4. title area

- `/tcb/colbacktitle`  $\rightarrow$  P. 25, `/tcb/opacitybacktitle`  $\rightarrow$  P. 43
- `/tcb/title code`  $\rightarrow$  P. 111
- `/tcb/title style`  $\rightarrow$  P. 120




### 5. segmentation


- `/tcb/lower separated`  $\rightarrow$  P. 23
- `/tcb/segmentation code`  $\rightarrow$  P. 110
- `/tcb/segmentation style`  $\rightarrow$  P. 120



- Section 9.5 on page 142



- Section 9.2 on page 123
- Section 9.8 on page 159



- Section 4.11 on page 61
- Section 9.3 on page 130

### Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

9. text content

Lower part

- `/tcb/colupper`<sup>→ P. 26</sup>, `/tcb/collower`<sup>→ P. 26</sup>, `/tcb/coltitle`<sup>→ P. 26</sup>
- `/tcb/fontupper`<sup>→ P. 27</sup>, `/tcb/fontlower`<sup>→ P. 27</sup>, `/tcb/fonttitle`<sup>→ P. 27</sup>
- `/tcb/opacityupper`<sup>→ P. 44</sup>, `/tcb/opacitylower`<sup>→ P. 44</sup>, `/tcb/opacitytitle`<sup>→ P. 44</sup>

### Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

10. finish

Lower part

- Section 9.9 on page 161

All together, the box is drawn:

```
% \usepackage{lipsum}
\begin{testbox}
\lipsum[2]
\tcblower
Lower part
\end{testbox}
```

### Test Box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Lower part



## 9 Library

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

This also loads the package `tikz` [20]. Typically but not necessarily, the following skins use `tikz` instead of `pgf`.

### 9.1 Style Option Keys


The following style options are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced`<sup>→ P.168</sup> supports *all* of them and `standard`<sup>→ P.166</sup> *none*.

`/tcb/frame style=<tikz keys>` (style, no default)

The `<tikz keys>` are used inside the `tikz` path command for drawing the *frame* of the box. This option is available if the `/tcb/frame engine`<sup>→ P.106</sup> is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style={left color=red!75!black,
               right color=blue!75!black}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/frame style image=<file name>` (no default, initially unset)

Fills the frame with an external image referenced by `<file name>`. For advanced features like blending of a picture with the background, use `/tcb/frame style` together with `/tikz/fill stretch image`<sup>→ P.213</sup>.

```
\tcbset{colback=red!5!white,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style image=blueshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




**/tcb/frame style tile**={<graphics options>}{<file name>} (no default, initially unset)

Fills the frame with a tile pattern based on an external image referenced by <file name>. The <graphics options> are given to the underlying **\includegraphics** command. For advanced features like blending of a picture with the background, use **/tcb/frame style** <sup>→ P. 117</sup> together with **/tikz/fill tile image** <sup>→ P. 217</sup>.

```
\tcbset{colback=red!5!white,coltitle=red!30!black,
  opacityback=0.75,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  frame style tile={width=1cm}{pink_marble.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```



**/tcb/frame hidden** (style, no value)

This is a shortcut for **frame style={draw=none,fill=none}**. Depending on the skin, this option switches off the drawing of the frame. Alternatively, use **/tcb/frame empty** <sup>→ P. 109</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
  fonttitle=\bfseries,coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,
  frame hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

---

This is the lower part.


**/tcb/interior style**=<tikz keys> (style, no default)

The <tikz keys> are used inside the **tikz** path command for drawing the *interior* of the box. They are used for the titled and for the untitled version as well.

This option is available if the **/tcb/interior titled engine** <sup>→ P. 106</sup> or **/tcb/interior engine** <sup>→ P. 107</sup> is set to **path**, **pathfirst**, **pathmiddle**, or **pathlast**. It is *not* available for **standard**.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style={left color=red!20!white,
    right color=yellow!50!white}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/interior style image=<file name>` (no default, initially unset)

Fills the interior with an external image referenced by `<file name>`. For advanced features like blending of a picture with the background, use `/tcb/interior style`<sup>→ P. 118</sup> together with `/tikz/fill stretch image`<sup>→ P. 213</sup>.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style image=goldshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/interior style tile={<graphics options>}{<file name>}` (no default, initially unset)

Fills the interior with a tile pattern based on an external image referenced by `<file name>`. The `<graphics options>` are given to the underlying `\includegraphics` command. For advanced features like blending of a picture with the background, use `/tcb/interior style`<sup>→ P. 118</sup> together with `/tikz/fill tile image`<sup>→ P. 217</sup>.

```
\tcbset{colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  interior style tile={width=2cm}{crinklepaper.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/interior hidden` (style, no value)

This is a shortcut for `interior style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the interior. Alternatively, use `/tcb/interior empty`<sup>→ P. 110</sup> and/or `/tcb/interior titled empty`<sup>→ P. 109</sup>.

```
\tcbset{frame style={top color=red!20!white,
  bottom color=red!20!white!75!black},
  fonttitle=\bfseries,coltitle=black}

\begin{tcolorbox}[enhanced,title=My title,
  interior hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/segmentation style=<tikz keys>` (style, no default)

The `<tikz keys>` are used inside the `tikz` path command for drawing the *segmentation* line of the box.

This option is available if the `/tcb/segmentation engine`<sup>→ P. 107</sup> is set to `path`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
segmentation style={double=white,draw=blue,
double distance=1pt,solid}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/segmentation hidden` (style, no value)

This is a shortcut for `segmentation style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the segmentation line. See also `/tcb/lower separated`<sup>→ P. 23</sup> which has the same effect for most skins. Alternatively, use `/tcb/segmentation empty`<sup>→ P. 110</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,
enhanced,segmentation hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/title style=<tikz keys>` (style, no default)

The `<tikz keys>` are used inside the `tikz` path command for drawing the *title area* of the box.

This option is available if the `/tcb/title engine`<sup>→ P. 107</sup> is set to `path`, `pathfirst`, `pathmiddle`, or `pathlast`. It is *not* available for `standard`.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
coltitle=blue!50!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
title style={left color=blue!15!yellow,
right color=red!85!black}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/title style image=<file name>` (no default, initially unset)

Fills the title area with an external image referenced by `<file name>`. For advanced features like blending of a picture with the background, use `/tcb/title style`<sup>→ P. 120</sup> together with `/tikz/fill stretch image`<sup>→ P. 213</sup>.

```
\tcbset{colback=blue!5!white,colframe=blue!75!black,
fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
title style image=blueshade.png]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/title style tile={<graphics options>}{<file name>}` (no default, initially unset)

Fills the title area with a tile pattern based on an external image referenced by `<file name>`. The `<graphics options>` are given to the underlying `\includegraphics` command. For advanced features like blending of a picture with the background, use `/tcb/title style`<sup>→ P. 120</sup> together with `/tikz/fill tile image`<sup>→ P. 217</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
coltitle=blue!50!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
title style tile={width=1cm}{pink_marble.png}]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tcb/title hidden` (style, no value)

This is a shortcut for `title style={draw=none,fill=none}`. Depending on the skin, this option switches off the drawing of the title background. See also `/tcb/title filled`<sup>→ P. 25</sup> for a similar effect. Alternatively, use `/tcb/title empty`<sup>→ P. 111</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black,
fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,
enhanced,title hidden]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




The combined TikZ style applied to frame, interior, and title background can be used by authors in customizing code.

`/tikz/tcb fill frame` (style, no value)

This is a TikZ style which is finally applied to the *frame* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  frame code app={\path[tcb fill frame]
    ([yshift=-2mm]frame.north)
      circle (8mm); } }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tikz/tcb fill interior` (style, no value)

This is a TikZ style which is finally applied to the *interior* of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  interior titled code app={\path[tcb fill interior]
    ([yshift=-0.1pt]interior.north east)
    --([yshift=3pt]interior.north)
    --([yshift=-0.1pt]interior.north west)
    --cycle;} }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```




`/tikz/tcb fill title` (style, no value)

This is a TikZ style which is finally applied to the *title* area of the box.

```
% \tcbuselibrary{hooks}
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries,
  colbacktitle=blue!75!black,
  title code app={\path[tcb fill title]
    (title) circle (5mm); } }

\begin{tcolorbox}[title=My title]
This is a \textbf{tcolorbox}.
\tcblower
This is the lower part.
\end{tcolorbox}
```





## 9.2 Boxed Title Option Keys

The following options place the title text into an own `\tcbox`<sup>→P.13</sup>. This boxed title can be customized independently from the main box using `/tcb/boxed title style`<sup>→P.125</sup>. The placement can be influenced by `\boxedtitle options`.

`/tcb/attach boxed title to top left=``\boxedtitle options` (style, default empty)

The title is boxed with a `\tcbox`<sup>→P.13</sup> and attached to the top left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/attach boxed title to top center=``\boxedtitle options` (style, default empty)

The title is boxed with a `\tcbox`<sup>→P.13</sup> and attached to the top of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/attach boxed title to top right=``\boxedtitle options` (style, default empty)

The title is boxed with a `\tcbox`<sup>→P.13</sup> and attached to the top right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top right]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/attach boxed title to bottom left=``\boxedtitle options` (style, default empty)

The title is boxed with a `\tcbox`<sup>→P.13</sup> and attached to the bottom left corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom left]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

`/tcb/attach boxed title to bottom center=``\boxedtitle options` (style, default empty)

The title is boxed with a `\tcbox`<sup>→P.13</sup> and attached to the bottom of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom center]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title

`/tcb/attach boxed title to bottom right=``\boxedtitle options` (style, default empty)

The title is boxed with a `\tcbox`<sup>→P.13</sup> and attached to the bottom right corner of the main box.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to bottom right]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

My title



The  $\langle\text{boxtitle options}\rangle$  of the keys described above are shift values. The dimensions of the boxed title are stored into two macros `\tcboxedtitleheight` and `\tcboxedtitlewidth`. These macros can be used inside the following  $\langle\text{boxtitle options}\rangle$ :

`/tcb/boxtitle/xshift= $\langle\text{length}\rangle$`  (no default, initially 0pt)

The boxed title is shifted by  $\langle\text{length}\rangle$  in the horizontal direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left={xshift=-2mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/boxtitle/yshift= $\langle\text{length}\rangle$`  (no default, initially 0pt)

The boxed title is shifted by  $\langle\text{length}\rangle$  in the vertical direction.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-\tcboxedtitleheight/2},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/boxtitle/yshifttext= $\langle\text{length}\rangle$`  (no default, initially 0pt)

The text inside the main box by  $\langle\text{length}\rangle$  to give room for e. g. a sunken title.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

`/tcb/boxtitle/yshift*= $\langle\text{length}\rangle$`  (no default, initially 0pt)

Sets `/tcb/boxtitle/yshift` and `/tcb/boxtitle/yshifttext` the same time.

`/tcb/boxtitle/yshifttext` is only set if necessary.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top center={yshift*=-3mm},
  boxed title style={size=small,colback=blue}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

The bounding box of the resulting total `tcolorbox` is adapted automatically to the *vertical* dimensions of the boxed title. Possible horizontal enlargements are *not* automatically computed.

```
\begin{tcolorbox}[enhanced,title=My title,
  attach boxed title to top left=
    {xshift=-2mm,yshift=-2mm},
  boxed title style={size=small,colback=blue},
  show bounding box]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

My title

This is a **tcolorbox**.

The boxed title options are implemented as an underlay, see Section 9.8 on page 159. Therefore, a boxed title is not drawn, if a skin does not support underlays like `standard`<sup>→P.166</sup>. Still, the room for the boxed titles gets reserved in these cases.


A TikZ node `title` is produced by a boxed title which can be used inside `/tcb/frame code`<sup>→P.109</sup>, `/tcb/interior code`<sup>→P.110</sup>, underlays, overlays, and finishes.

A boxed title is almost always the first underlay. The only exceptions are underlays defined by `/tcb/underlay boxed title`<sup>→P.160</sup> which are drawn before. Additionally, underlays defined by `/tcb/underlay boxed title`<sup>→P.160</sup> are only drawn, if a boxed title is actually set. They are ignored, if there is no boxed title.


`/tcb/boxed title style=<options>` (style, initially empty)

By default, a boxed title is dimensioned with `/tcb/size`<sup>→P.36</sup>=`title` and inherits `/tcb/colframe`<sup>→P.25</sup> of the main box. Also, the `/tcb/colback`<sup>→P.25</sup> is inherited from the main `/tcb/colbacktitle`<sup>→P.25</sup>. Font and color of the title text are set as usual. All other `<options>` are set by the `boxed title style` key. Since a boxed title is set by `\tcbbox`<sup>→P.13</sup>, all `tcolorbox` options are applicable here.

```
\begin{tcolorbox}[enhanced,title=My title,
fonttitle=\bfseries,coltitle=green!25!black,
attach boxed title to top center=
{yshift=-2mm,yshifttext=-1mm},
boxed title style={colframe=green!75!black,
colback=yellow!50!green}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



```
\begin{tcolorbox}[enhanced,title=My title,
colframe=red!50!black,colback=red!10!white,
arc=1mm,colbacktitle=red!10!white,
fonttitle=\bfseries,coltitle=red!50!black,
attach boxed title to top left=
{xshift=3.2mm,yshift=-0.50mm},
boxed title style={enhanced,
skin=enhancedfirst jigsaw,
size=small,arc=1mm,bottom=-1mm,
interior style={top color=red!30!white,
bottom color=red!20!white}}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```



```

\begin{tcolorbox}[enhanced,title=My title,
colframe=blue!50!black,colback=blue!10!white,colbacktitle=blue!5!yellow!10!white,
fonttitle=\bfseries,coltitle=black,attach boxed title to top center=
{yshift=-0.25mm-\tcboxedtitleheight/2,yshifttext=2mm-\tcboxedtitleheight/2},
boxed title style={enhanced,boxrule=0.5mm,
frame code={ \path[tcb fill frame] ([xshift=-4mm]frame.west)
-- (frame.north west) -- (frame.north east) -- ([xshift=4mm]frame.east)
-- (frame.south east) -- (frame.south west) -- cycle; },
interior code={ \path[tcb fill interior] ([xshift=-2mm]interior.west)
-- (interior.north west) -- (interior.north east)
-- ([xshift=2mm]interior.east) -- (interior.south east) -- (interior.south west)
-- cycle;} }]
\lipsum[2]
\end{tcolorbox}

```

### My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```

% \usepackage{varwidth}
\newtcolorbox{mybox}[2][{}]{enhanced,skin=enhancedlast jigsaw,
attach boxed title to top left={xshift=-4mm,yshift=-0.5mm},
fonttitle=\bfseries\sffamily,varwidth boxed title=0.7\linewidth,
colbacktitle=blue!45!white,colframe=red!50!black,
interior style={top color=blue!10!white,bottom color=red!10!white},
boxed title style={empty,arc=0pt,outer arc=0pt,boxrule=0pt},
underlay boxed title={
\fill[blue!45!white] (title.north west) -- (title.north east)
-- +(\tcboxedtitleheight-1mm,-\tcboxedtitleheight+1mm)
-- ([xshift=4mm,yshift=0.5mm]frame.north east) -- +(0mm,-1mm)
-- (title.south west) -- cycle;
\fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north west)
-- +(-0.4,0) -- +(0,-0.3) -- cycle;
\fill[blue!45!white!50!black] ([yshift=-0.5mm]frame.north east)
-- +(0,-0.3) -- +(0.4,0) -- cycle; },
title={#2},#1}

\begin{mybox}{My title}
\lipsum[2]
\end{mybox}

```

### My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][{}]{enhanced,
  attach boxed title to top left={xshift=1cm,yshift=-2mm},
  fonttitle=\bfseries,varwidth boxed title=0.7\linewidth,
  colbacktitle=green!45!white,coltitle=green!10!black,colframe=green!50!black,
  interior style={top color=yellow!10!white,bottom color=green!10!white},
  boxed title style={enhanced,boxrule=0.75mm,colframe=white,
    borderline={0.1mm}{0mm}{green!50!black},
    borderline={0.1mm}{0.75mm}{green!50!black},
    interior style={top color=green!10!white,bottom color=green!10!white,
      middle color=green!50!white},
    drop fuzzy shadow},
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

### My title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[2][{}]{skin=enhancedlast jigsaw,interior hidden,
  boxsep=0pt,top=0pt,colframe=red,coltitle=red!50!black,
  fonttitle=\bfseries\sffamily,
  attach boxed title to bottom center,
  boxed title style={empty,boxrule=0.5mm},
  varwidth boxed title=0.5\linewidth,
  underlay boxed title={
    \draw[white,line width=0.5mm]
      ([xshift=0.3mm-\tcboxedtitleheight*2,yshift=0.3mm]title.north west)
      --([xshift=-0.3mm+\tcboxedtitleheight*2,yshift=0.3mm]title.north east);
    \path[draw=red,top color=white,bottom color=red!50!white,line width=0.5mm]
      ([xshift=0.25mm-\tcboxedtitleheight*2,yshift=0.25mm]title.north west)
      cos +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
      sin +(\tcboxedtitleheight,-\tcboxedtitleheight/2)
      -- ([xshift=0.25mm,yshift=0.25mm]title.south west)
      -- ([yshift=0.25mm]title.south east)
      cos +(\tcboxedtitleheight,\tcboxedtitleheight/2)
      sin +(\tcboxedtitleheight,\tcboxedtitleheight/2); },
  title={#2},#1}

\begin{mybox}{My title}
  \lipsum[2]
\end{mybox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

### My title

### /tcb/hbox boxed title


(no value, initially set)

The title text content is captured with a horizontal box. Especially, there are no linebreak possible.

```
\newtcolorbox{mybox}[1]{hbox boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



### /tcb/minipage boxed title=<length>


(initially unset)

The title text content is captured with a minipage with a width of  $\langle length \rangle$ . By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```



### /tcb/minipage boxed title\*=<length>


(initially unset)

The title text content is captured with a minipage with a width of main box width plus  $\langle length \rangle$ . By default, the resulting boxed title is somewhat smaller than the main box.

```
\newtcolorbox{mybox}[1]{minipage boxed title*=-2cm,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```




`/tcb/tikznode boxed title=<options>` (initially unset)

The title text content is captured with a TikZ node with given TikZ *<options>*. The text is centered by default

```
\newtcolorbox{mybox}[1]{tikznode boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title\\is not really\\very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```




`/tcb/varwidth boxed title=<length>` (initially unset)

The title text content is captured with a `varwidth` environment with a width of *<length>*. This style needs the `varwidth` package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```




`/tcb/varwidth boxed title*=<length>` (initially unset)

The title text content is captured with a `varwidth` environment with a width of main box width plus *<length>*. This style needs the `varwidth` package [1] to be loaded manually. By default, the resulting boxed title is somewhat smaller than the main box.

```
% \usepackage{varwidth}
\newtcolorbox{mybox}[1]{varwidth boxed title*=-2cm,
  enhanced,attach boxed title to top center=
    {yshift=-3mm,yshifttext=-1mm},
  boxed title style={size=small,colback=red},
  center title,title={#1}}

\begin{mybox}{Short title}
  This is a \textbf{tcolorbox}.
\end{mybox}\bigskip

\begin{mybox}{This title is not really very short}
  This is a \textbf{tcolorbox}.
\end{mybox}
```





### 9.3 Watermark Option Keys

The following watermark options are applicable for all skins which use `tikzpicture` as `/tcb/graphical environment`<sup>→ P. 105</sup>. Therefore, the skin `standard`<sup>→ P. 166</sup> does not support these watermarks, but all other skins, e. g. `enhanced`<sup>→ P. 168</sup>.

The watermark options rely on the more general overlay options described in Section 4.11 from page 61. Therefore, *watermarks* and *overlays* cannot be used mixed. But a mixture is possible with the `lib hooks` library, see Section 17.

`/tcb/watermark text=<text>` (no default, initially unset)

Writes some *<text>* in the center of the interior region of a `tcolorbox`. This *<text>* is written *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of `/tcb/watermark zoom`<sup>→ P. 133</sup> or `/tcb/watermark stretch`<sup>→ P. 135</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```

#### My title

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark text on=<part> is <text>` (no default, initially unset)

This option writes some *<text>* in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark text`. But this is done only for boxes named *<part>* of a break sequence, see `/tcb/breakable`<sup>→ P. 296</sup>.

Feasible values for *<part>* are:

- **broken**: all broken box parts,
- **unbroken**: unbroken boxes only,
- **first**: first parts of a break sequence,
- **middle**: middle parts of a break sequence,
- **last**: last parts of a break sequence,
- **unbroken and first**: unbroken boxes and first parts of a break sequence,
- **middle and last**: middle and last parts of a break sequence.
- **first and middle**: first and middle parts of a break sequence.



**/tcb/watermark graphics**=*<file name>* (no default, initially unset)

Draws an external picture referenced by *<file name>* in the center of the interior region of a `tcolorbox`. The picture is drawn *after* the frame and interior are drawn and *before* the text content is drawn. It is zoomed or stretched according the values of `/tcb/watermark zoom`<sup>→ P. 133</sup> or `/tcb/watermark stretch`<sup>→ P. 135</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.15]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

#### My title

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

---

This example uses a public domain picture from  
[http://commons.wikimedia.org/wiki/File:Basilica\\_5.png](http://commons.wikimedia.org/wiki/File:Basilica_5.png)

**/tcb/watermark graphics on**=*<part>* is *<file name>* (no default, initially unset)

This option draws a picture referenced by *<file name>* in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark graphics`. But this is done only for boxes named *<part>* of a break sequence, see `/tcb/breakable`<sup>→ P. 296</sup>.

Feasible values for *<part>* are:

- **broken**: all broken box parts,
- **unbroken**: unbroken boxes only,
- **first**: first parts of a break sequence,
- **middle**: middle parts of a break sequence,
- **last**: last parts of a break sequence,
- **unbroken and first**: unbroken boxes and first parts of a break sequence,
- **middle and last**: middle and last parts of a break sequence.

`/tcb/watermark tikz=<graphical code>` (no default, initially unset)

Draws the given `tikz` *<graphical code>* in the center of the interior region of a `tcolorbox`. The code is executed *after* the frame and interior are drawn and *before* the text content is drawn. The result is zoomed or stretched according the values of `/tcb/watermark zoom`<sup>→ P. 133</sup> or `/tcb/watermark stretch`<sup>→ P. 135</sup>.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,
  watermark tikz={\draw[line width=2mm] circle (1cm)
    node{\fontfamily{ptm}\fontseries{b}\fontsize{20mm}{20mm}\selectfont ?};}]
\lipsum[1]
\tcblower
\lipsum[2]
\end{tcolorbox}
```

#### My title

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark tikz on=<part> is <graphical code>` (no default, initially unset)

This option draws the given `tikz` *<graphical code>* in the center of the interior region of a `tcolorbox` as described for `/tcb/watermark tikz`. But this is done only for boxes named *<part>* of a break sequence, see `/tcb/breakable`<sup>→ P. 296</sup>.

Feasible values for *<part>* are:

- **broken**: all broken box parts,
- **unbroken**: unbroken boxes only,
- **first**: first parts of a break sequence,
- **middle**: middle parts of a break sequence,
- **last**: last parts of a break sequence,
- **unbroken and first**: unbroken boxes and first parts of a break sequence,
- **middle and last**: middle and last parts of a break sequence.

`/tcb/no watermark` (style, no default, initially set)

Removes the watermark if set before. This is an alias for `/tcb/no overlay`<sup>→ P. 62</sup>.

`/tcb/watermark opacity=<fraction>` (no default, initially 1.00)

Sets the opacity value  $\in [0, 1]$  for a watermark.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Opacity 1.00,watermark opacity=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Opacity 0.50,watermark opacity=0.50]
\lipsum[2]
\end{tcolorbox}%
```

#### Opacity 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

#### Opacity 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark zoom=<fraction>` (no default, initially 0.75)

Sets the zoom value for a watermark. The zoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches the frame.

```
\tcbset{enhanced,colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
watermark text=Watermark,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Zoom 0.5,watermark zoom=0.5]
\lipsum[2]
\end{tcolorbox}%
```

#### Zoom 1.0

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

#### Zoom 0.5

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark shrink=<fraction>` (no default, initially unset)

Identically to `/tcb/watermark zoom`<sup>P. 133</sup>, but the watermark never gets enlarged. Thus, the watermark keeps its original size or is shrunk.

`/tcb/watermark overzoom=<fraction>` (no default, initially unset)

Sets the overzoom value for a watermark. The overzoom respects the aspect ratio. The value 1.0 means to fill the whole box until the watermark touches all four sides of the frame.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
watermark opacity=0.5,
watermark graphics=lichtspiel.jpg,nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Zoom 1.0,watermark zoom=1.0]
\lipsum[1]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Overzoom 1.0,watermark overzoom=1.0]
\lipsum[1]
\end{tcolorbox}%
```

#### Zoom 1.0

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

#### Overzoom 1.0

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

If a `/tcb/watermark overzoom` value of 1.0 is used in connection with invisible top and bottom rules which still have a thickness greater than 0pt, the space of these invisible rules may not be covered by the watermark. For example, this situation may occur during the breaking of `/tcb/enhanced`<sup>P. 168</sup> boxes. To avoid this optical glitch, just set `/tcb/pad at break`<sup>P. 300</sup> to any desired value.

`/tcb/watermark stretch=<fraction>` (no default, initially unset)

Sets the stretch value for a watermark. The stretch value is applied to width and height in relation to the box dimensions. It does not respect the aspect ratio. The value 1.0 means to fill the whole box.

```
\tcbset{enhanced,colback=white,colframe=blue!50!black,fonttitle=\bfseries,
  watermark graphics=lichtspiel.jpg,watermark opacity=0.5,
  nobeforeafter,width=(\linewidth-2mm)/2}

\begin{tcolorbox}[title=Stretch 1.00,watermark stretch=1.00]
\lipsum[2]
\end{tcolorbox}\hfill%
\begin{tcolorbox}[title=Stretch 0.50,watermark stretch=0.50]
\lipsum[2]
\end{tcolorbox}%
```

#### Stretch 1.00

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

#### Stretch 0.50

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/watermark color=<color>` (no default, initially mixed background and frame color)

Sets the color for the watermark.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark text=My Watermark,
  watermark color=yellow!50!red]
\lipsum[1]
\end{tcolorbox}
```

#### My title

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



`/tcb/clip watermark=true|false`

(default true, initially true)

Sets the watermark to be clipped to the interior area.

```
\tcbset{enhanced,colback=white,colframe=blue!50!white,fonttitle=\bfseries,
watermark opacity=0.5,watermark stretch=1.00,arc=3mm,
watermark graphics=lichtspiel.jpg}

\begin{tcolorbox}[title=Clip (default),clip watermark]
\lipsum[1]
\end{tcolorbox}

\begin{tcolorbox}[title=No clip,clip watermark=false]
\lipsum[1]
\end{tcolorbox}%
```

#### Clip (default)

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

#### No clip

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

## 9.4 Clip Environments

The following clip environments are applicable for all skins which use engines of type `path`, `pathfirst`, `pathmiddle`, or `pathlast`. Especially, the skin `enhanced`<sup>→ P.168</sup> supports *all* of them and `standard`<sup>→ P.166</sup> *none*. The typical area of application is inside overlay code, see Section 4.11 from page 61.

```
\begin{tcbclipframe}  
  <environment content>  
\end{tcbclipframe}
```

Defines a Tikz scope which clips to the frame area path.

```
\makeatletter  
\newtcolorbox{picturebox}[2][]{%  
  enhanced,frame hidden,interior hidden,fonttitle=\bfseries,  
  overlay={\begin{tcbclipframe}\node at (frame)  
    {\includegraphics[width=\tcb@width,height=\tcb@height]{#2}};\end{tcbclipframe}}%  
  \begin{tcbclipinterior}\fill[white,opacity=0.75]  
    (frame.south west) rectangle (frame.north east);\end{tcbclipinterior}},#1}  
\makeatother  
  
\begin{picturebox}[title=My Picture Box]{lichtspiel.jpg}  
\lipsum[1]  
\end{picturebox}
```

### My Picture Box

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



```
\begin{tcbinvclipframe}
  <environment content>
\end{tcbinvclipframe}
```

Defines a Tikz scope which clips to the *outside* of the frame area path.

```
\tcbset{enhanced jigsaw,fonttitle=\bfseries,opacityback=0.35,colback=blue!5!white,
  frame style={left color=red!75!black,right color=red!10!yellow}}

\begin{tikzpicture}% draw two balls
  \path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
  \shadedraw [shading=ball] (0,0) circle (1cm);
  \shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}

\begin{tcolorbox}[title=A translucent box,
  overlay={\begin{tcbinvclipframe}
    \draw[red,line width=1cm] ([xshift=-2mm,yshift=2mm]frame.north west)
      --([xshift=2mm,yshift=-2mm]frame.south east);
    \draw[red,line width=1cm] ([xshift=-2mm,yshift=-2mm]frame.south west)
      --([xshift=2mm,yshift=2mm]frame.north east);
  \end{tcbinvclipframe}}]
  \lipsum[2]
\end{tcolorbox}
```


#### A translucent box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\begin{tcbclipinterior}
  <environment content>
\end{tcbclipinterior}
```

Defines a Tikz scope which clips to the interior area path.


```
\begin{tcolorbox}[enhanced,title=My Title,
  overlay={\begin{tcbclipinterior}
    \draw[red,line width=1cm] (interior.north west)--(interior.south east);
    \draw[red,line width=1cm] (interior.south west)--(interior.north east);
  \end{tcbclipinterior}}]
\lipsum[1]
\end{tcolorbox}
```



```
\begin{tcbcliptitle}
  <environment content>
\end{tcbcliptitle}
```

Defines a Tikz scope which clips to the title area path.

```
\begin{tcolorbox}[enhanced,title=My Title,colframe=blue,colback=yellow!10!white,
  overlay={\begin{tcbcliptitle}\node at (title)
    {\includegraphics[width=\linewidth]{lichtspiel.jpg}};\end{tcbcliptitle}}]
\lipsum[1]
\end{tcolorbox}
```



`/tcb/clip title=true|false` (default true, initially false)

Sets the title to be clipped to the title area.

```
\tcbset{enhanced,width=5cm,colframe=red!50!white,coltitle=black,
colbacktitle=yellow!50!white}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long}]
This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[title=\mbox{This is a title which is unbreakable and far too long},
clip title]
This is a tcolorbox.
\end{tcolorbox}
```

This is a title which is unbreakable and far too long

This is a tcolorbox.

This is a title which is unbreak



This is a tcolorbox.

`/tcb/clip upper=true|false` (default true, initially false)

Sets the upper part to be clipped to the interior area.

```
\newcommand{\mygraphics}[2][{}]{%
\tcbbox[enhanced,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
right=0pt,boxrule=0.4pt,drop fuzzy shadow,clip upper,
colback=black!75!white,toptitle=2pt,bottomtitle=2pt,nobeforeafter,
center title,fonttitle=\small\sffamily,title=\detokenize{#2}]
{\includegraphics[width=\the\dimexpr(\linewidth-4mm)/2\relax]{#2}}


\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```



The example for `/tcb/clip upper`<sup>→ P. 140</sup> sizes the box according to the dimensions of the picture. To do it the other way around, the watermark options provide an easy solution.

```
\newcommand{\mygraphics}[2][\%
\tcbbox[enhanced,capture=minipage,boxsep=0pt,top=0pt,bottom=0pt,left=0pt,
right=0pt,boxrule=0.4pt,drop fuzzy shadow,nobeforeafter,
colback=black!75!white,toptitle=2pt,bottomtitle=2pt,
center title,fonttitle=\small\sffamily,title=\detokenize{#2},
width=(\linewidth-4mm)/2,height=6cm,colbacktitle={black},
watermark zoom=1.0,watermark graphics={#2}]{}}

\mygraphics{lichtspiel.jpg}\hfill
\mygraphics{Basilica_5.png}
```



`/tcb/clip lower=true|false` (default true, initially false)  
Sets the lower part to be clipped to the interior area.

```
\tcbset{enhanced,width=5cm,colframe=red!50!black,text and listing}

\begin{tcblisting}{}
Donau\dampf\schiff\fahrts\ka\pi\t"ans\m"ut\zen\fran\sen
\end{tcblisting}

\begin{tcblisting}{clip lower}
Donau\dampf\schiff\fahrts\ka\pi\t"ans\m"ut\zen\fran\sen
\end{tcblisting}
```

Donaudampfschiffahrtska-  
pitänsmützenfransen

Donau\dampf\schiff\fahrts\ka\pi\t"ans\m"ut\zen\fran\sen

Donaudampfschiffahrtska-  
pitänsmützenfransen

Donau\dampf\schiff\fa

## 9.5 Border Line Option Keys

The following borderline options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment`<sup>→ P. 105</sup>. Therefore, the skin `standard`<sup>→ P. 166</sup> does not support these border lines, but most other skins, e.g. `enhanced`<sup>→ P. 168</sup>.

The borderlines are independent from the normal `tcolorbox` rules. They may be used with or without the `/tcb/segmentation engine`<sup>→ P. 107</sup>.

The borderlines are stackable, i.e. several different border lines can be used on the same `tcolorbox`. They are drawn *after* the box frame and box interior and *before* overlays or watermarks.

Technically, the normal `tcolorbox` rules result from a TikZ *filling* process. The border lines are created by a TikZ *drawing* process. This can be used to apply different effects.

`/tcb/borderline={⟨width⟩}{⟨offset⟩}{⟨options⟩}` (no default, initially unset)

Adds a new borderline to the stack of border lines. This border line is drawn with the given `⟨width⟩` and gets an `⟨offset⟩` computed from the frame outline. A positive `⟨offset⟩` value moves the borderline inside the `tcolorbox` and a negative `⟨offset⟩` value moves it outside without changing the bounding box.

The border line is drawn along a TikZ path with the given TikZ `⟨options⟩`. Note that the TikZ `line width` option should not be used here.

The border lines adapt to the rounded corners of the `tcolorbox`. An inside borderline will switch to sharp corners if necessary, an outside borderline will always be rounded except for `/tcb/sharp corners`<sup>→ P. 40</sup>.

```
\begin{tcolorbox}[enhanced,title=Rounded corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
\bigskip
\begin{tcolorbox}[enhanced,title=Sharp corners,fonttitle=\bfseries,boxsep=5pt,
  arc=8pt,sharp corners=downhill,
  borderline={0.5pt}{0pt}{red},
  borderline={0.5pt}{5pt}{blue,dotted},
  borderline={0.5pt}{-5pt}{green} ]
This is a tcolorbox.
\end{tcolorbox}
```

Rounded corners

This is a tcolorbox.

Sharp corners

This is a tcolorbox.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,boxsep=1.5mm,
colback=yellow!20!white,
colframe=blue,
borderline={1mm}{1mm}{white},
borderline={1mm}{2mm}{red} ]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,arc=3mm,boxrule=1.5mm,
frame hidden,colback=blue!10!white,
borderline={1mm}{0mm}{blue,dotted} ]
\lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
% \usepackage{lipsum}
\begin{tcolorbox}[enhanced,skin=enhancedmiddle,
frame hidden,interior hidden,top=0mm,bottom=0mm,boxsep=0mm,
borderline={0.75mm}{0mm}{red},
borderline={0.75mm}{0.75mm}{red!50!yellow},
borderline={0.75mm}{1.5mm}{yellow}, ]
\lipsum[3]
\end{tcolorbox}
```

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.



```
% \usepackage{lipsum}
\newtcolorbox{mygreenbox}[2][]{%
  enhanced,width=\linewidth-6pt,
  enlarge top by=3pt,enlarge bottom by=3pt,
  enlarge left by=3pt,enlarge right by=3pt,
  title={#2},frame hidden,boxrule=0pt,top=1mm,bottom=1mm,
  colframe=green!30!black, colbacktitle=green!50!yellow,
  coltitle=black, colback=green!25!white,
  borderline={0.5pt}{-0.5pt}{green!75!blue},
  borderline={1pt}{-3pt}{green!50!blue},#1}

\begin{mygreenbox}{My title}
  \lipsum[4]
\end{mygreenbox}
```

My title

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

**/tcb/no borderline**

(no default, initially set)

Removes all borderlines if set before.


**/tcb/show bounding box=***<color>*

(default **red**, initially unset)

Displays the bounding box borderline of a `tcolorbox`. Its intended use is debugging and fine tuning. It should not be part of a final document. The optional *<color>* is the base color for the bounding box borderline.

```
\tcbset{enhanced,nobeforeafter,width=4cm,fonttitle=\bfseries}

\begin{tcolorbox}[show bounding box,title=Normal]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=blue,title=Shadow,drop fuzzy shadow]
This is a tcolorbox.
\end{tcolorbox}%
\begin{tcolorbox}[show bounding box=green,title=Enlarged,drop fuzzy shadow,
  enlarge by=2mm]
This is a tcolorbox.
\end{tcolorbox}
```





The following *partial* borderlines act slightly different from the complete borderlines described before. They ignore rounded corner settings, their length is not modified by their  $\langle offset \rangle$ , they ignore skin settings but adapt to breakable boxes.

**N 2014-10-20** `/tcb/borderline north={\langle width \rangle}{\langle offset \rangle}{\langle options \rangle}` (no default, initially unset)

Adds a new borderline with the given  $\langle width \rangle$  to the north of the `tcolorbox`. A positive  $\langle offset \rangle$  value moves the borderline inside the `tcolorbox` and a negative  $\langle offset \rangle$  value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline north={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**N 2014-10-20** `/tcb/borderline south={\langle width \rangle}{\langle offset \rangle}{\langle options \rangle}` (no default, initially unset)

Adds a new borderline with the given  $\langle width \rangle$  to the south of the `tcolorbox`. A positive  $\langle offset \rangle$  value moves the borderline inside the `tcolorbox` and a negative  $\langle offset \rangle$  value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline south={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**N 2014-10-20** `/tcb/borderline east={\langle width \rangle}{\langle offset \rangle}{\langle options \rangle}` (no default, initially unset)

Adds a new borderline with the given  $\langle width \rangle$  to the east of the `tcolorbox`. A positive  $\langle offset \rangle$  value moves the borderline inside the `tcolorbox` and a negative  $\langle offset \rangle$  value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline east={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**N 2014-10-20** `/tcb/borderline west={\langle width \rangle}{\langle offset \rangle}{\langle options \rangle}` (no default, initially unset)

Adds a new borderline with the given  $\langle width \rangle$  to the west of the `tcolorbox`. A positive  $\langle offset \rangle$  value moves the borderline inside the `tcolorbox` and a negative  $\langle offset \rangle$  value moves it outside without changing the bounding box.

```
\begin{tcolorbox}[enhanced,
  borderline west={2pt}{-2pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

This is a **tcolorbox**.

**/tcb/borderline horizontal**= $\{\langle width \rangle\}\{\langle offset \rangle\}\{\langle options \rangle\}$  (no default, initially unset)

Adds a new borderline with the given  $\langle width \rangle$  to the north and south of the `tcolorbox`. A positive  $\langle offset \rangle$  value moves the borderlines inside the `tcolorbox` and a negative  $\langle offset \rangle$  value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,top=3mm,bottom=3mm,
  borderline horizontal={2pt}{0pt}{red}]
  This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

— This is a **tcolorbox**. —

**/tcb/borderline vertical**= $\{\langle width \rangle\}\{\langle offset \rangle\}\{\langle options \rangle\}$  (no default, initially unset)

Adds a new borderline with the given  $\langle width \rangle$  to the east and west of the `tcolorbox`. A positive  $\langle offset \rangle$  value moves the borderlines inside the `tcolorbox` and a negative  $\langle offset \rangle$  value moves them outside without changing the bounding box.

```
\begin{tcolorbox}[blanker,left=3mm,right=3mm,
  borderline vertical={2pt}{0pt}{red}]
  This is a \textbf{tcolorbox}.\n
  My second line.
\end{tcolorbox}
```

| This is a **tcolorbox**.  
| My second line. |

```
\begin{tcolorbox}[enhanced,colback=yellow!10!white,boxrule=0pt,frame hidden,
  borderline north={1mm}{-2mm}{red},
  borderline south={1mm}{-2mm}{blue},
  borderline west={1mm}{-2mm}{green},
  borderline east={1mm}{-2mm}{yellow}]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

## 9.6 Shadow Option Keys

The following shadow options are applicable for most skins which use `tikzpicture` as `/tcb/graphical environment`<sup>→ P. 105</sup>. Therefore, the skin `standard`<sup>→ P. 166</sup> does not support these shadows, but most other skins, e.g. `enhanced`<sup>→ P. 168</sup>.

The shadows are stackable, i.e. several different shadows can be used on the same `tcolorbox`. They are drawn *before* the box frame is drawn.

`/tcb/no shadow` (no default)

Removes all shadows if set before.

`/tcb/shadow={⟨xshift⟩}{⟨yshift⟩}{⟨offset⟩}{⟨options⟩}` (no default)

Adds a new shadow to the stack of shadows. This shadow follows the outline of the `tcolorbox` but is shifted by `⟨xshift⟩` and `⟨yshift⟩`. The `⟨offset⟩` value is a distance value from the frame outline. A positive `⟨offset⟩` value shrinks the shadow and a negative `⟨offset⟩` value enlarges the shadow. The shadow is filled along a TikZ path with the given TikZ `⟨options⟩`.

The shadows adapt to the rounded corners of the `tcolorbox`. An shrunk shadow will switch to sharp corners if necessary, an enlarged shadow may become more rounded depending on several factors. But `/tcb/sharp corners`<sup>→ P. 40</sup> have sharp shadows.

Shadows are not considered for the bounding box computation by default. Large shadows may be overlapped by the following content. But, the bounding box can be adapted if necessary.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  shadow={2mm}{-1mm}{0mm}{black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  shadow={-1mm}{-2mm}{0mm}{fill=blue,
  opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
  shadow={-1.5mm}{-1.5mm}{0mm}{fill=blue,
  opacity=0.25},
  shadow={1.5mm}{-1.5mm}{0mm}{fill=red,
  opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
  shadow={5.5mm}{-3.5mm}{2mm}{fill=black,
  opacity=0.25}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Halo shadow,
  shadow={0mm}{0mm}{-1.5mm}%
  {fill=yellow!75!red,opacity=0.5}]
This is a tcolorbox.
\end{tcolorbox}
```

**My own shadow**

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

**Double shadow**

This is a tcolorbox.

**Far shadow**

This is a tcolorbox.

**Halo shadow**

This is a tcolorbox.

**/tcb/fuzzy shadow**={ $\langle xshift \rangle$ }{ $\langle yshift \rangle$ }{ $\langle offset \rangle$ }{ $\langle step \rangle$ }{ $\langle options \rangle$ } (no default)

Adds a new fuzzy shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This fuzzy shadow follows the outline of the `tcolorbox` but is shifted by  $\langle xshift \rangle$  and  $\langle yshift \rangle$ . The  $\langle offset \rangle$  value is a distance value from the frame outline. A positive  $\langle offset \rangle$  value shrinks the shadow and a negative  $\langle offset \rangle$  value enlarges the shadow. The  $\langle step \rangle$  value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a TikZ path with the given TikZ  $\langle options \rangle$  but any opacity value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  fuzzy shadow={2mm}{-1mm}{0mm}{0.1mm}%
    {black!50!white}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  fuzzy shadow={-1mm}{-2mm}{0mm}{0.2mm}%
    {fill=blue}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Double shadow,
  fuzzy shadow={-1.5mm}{-1.5mm}{0mm}{0.1mm}%
    {blue},
  fuzzy shadow={1.5mm}{-1.5mm}{0mm}{0.1mm}%
    {red}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip
\begin{tcolorbox}[title=Far shadow,
  fuzzy shadow={5.5mm}{-3.5mm}{0mm}{0.3mm}%
    {black}]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Glow shadow,
  fuzzy shadow={0mm}{0mm}{-1.5mm}{0.15mm}%
    {yellow!75!red}]
This is a tcolorbox.
\end{tcolorbox}
```

**My own shadow**

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

**Double shadow**

This is a tcolorbox.

**Far shadow**

This is a tcolorbox.

**Glow shadow**

This is a tcolorbox.

```
\newtcolorbox{mybox}[1][\tcbset{enhanced,
  fuzzy shadow={1.0mm}{-1.0mm}{0.12mm}{0mm}{blue!50!white},
  fuzzy shadow={-1.0mm}{-1.0mm}{0.12mm}{0mm}{red!50!white},
  fuzzy shadow={-1.0mm}{1.0mm}{0.12mm}{0mm}{green!50!white},
  fuzzy shadow={1.0mm}{1.0mm}{0.12mm}{0mm}{yellow!50!white},#1
}]

\begin{mybox}[title=A multi shadow box]
This is a tcolorbox.
\end{mybox}
```

**A multi shadow box**

This is a tcolorbox.

`/tcb/drop shadow=<color>` (style, default black!50!white)

Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[drop shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

`/tcb/drop fuzzy shadow=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[drop fuzzy shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop fuzzy shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

`/tcb/drop midday shadow=<color>` (style, default black!50!white)

Adds a new shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[drop midday shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop midday shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

`/tcb/drop fuzzy midday shadow=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[drop fuzzy midday shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop fuzzy midday shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

`/tcb/halo=<size> with <color>` (style, default 0.9mm with yellow)

Adds a new halo shadow with the given `<color>` which overlaps the colorbox on all sides by `<size>`.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,halo]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
  halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```

My own halo

This is a tcolorbox.

Another halo

This is a tcolorbox.

`/tcb/fuzzy halo=<size> with <color>` (style, default 0.9mm with yellow)

Adds a new fuzzy halo shadow with the given `<color>` which overlaps the colorbox on all sides by `<size>` plus 0.48mm.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=My own halo,fuzzy halo]
This is a tcolorbox.
\end{tcolorbox}
\par\bigskip\bigskip
\begin{tcolorbox}[title=Another halo,
  fuzzy halo=2mm with green]
This is a tcolorbox.
\end{tcolorbox}
```

My own halo

This is a tcolorbox.

Another halo

This is a tcolorbox.

```
\begin{tcolorbox}[blank,enhanced jigsaw,boxsep=2pt,arc=2pt,
  fuzzy halo=2mm with red!50!white,
  fuzzy halo=1mm with white]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



For all following shadows, the optionally given  $\langle color \rangle$  for the shadow can be changed equivalent to the preceding examples.

`/tcb/drop shadow southeast= $\langle color \rangle$`  (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop shadow`<sup>→ P. 149</sup>.

```
\begin{tcolorbox}[drop shadow southeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow south= $\langle color \rangle$`  (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop midday shadow`<sup>→ P. 149</sup>.

```
\begin{tcolorbox}[drop shadow south,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow southwest= $\langle color \rangle$`  (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow southwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow west= $\langle color \rangle$`  (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow west,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow northwest= $\langle color \rangle$`  (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow north= $\langle color \rangle$`  (style, default `black!50!white`)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow north,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.



`/tcb/drop shadow northeast=<color>` (style, default black!50!white)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow northeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop shadow east=<color>` (style, default black!50!white)

Adds a new shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop shadow east,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow southeast=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop fuzzy shadow`<sup>→ P. 149</sup>.

```
\begin{tcolorbox}[drop fuzzy shadow southeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow south=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows. This shadow is identical to `/tcb/drop fuzzy midday shadow`<sup>→ P. 149</sup>.

```
\begin{tcolorbox}[drop fuzzy shadow south,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow southwest=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow southwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow west=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow west,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow northwest=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northwest,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow north=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow north,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow northeast=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow northeast,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

`/tcb/drop fuzzy shadow east=<color>` (style, default black!50!white)

Adds a new fuzzy shadow with standard dimensions to the stack of shadows.

```
\begin{tcolorbox}[drop fuzzy shadow east,
  enhanced,colback=red!5!white,colframe=red!75!black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**/tcb/lifted shadow**={ $\langle xshift \rangle$ }{ $\langle yshift \rangle$ }{ $\langle bend \rangle$ }{ $\langle step \rangle$ }{ $\langle options \rangle$ } (no default)

Adds a new lifted shadow to the stack of shadows. Actually, this option adds several shadows which appear like a shadow with a fuzzy border. This lifted shadow follows the outline of the `tcolorbox` but is shifted by  $\langle xshift \rangle$  and  $\langle yshift \rangle$  on the lower left corner and by  $-\langle xshift \rangle$  and  $\langle yshift \rangle$  on the lower right corner. Additionally, there is a  $\langle bend \rangle$  in the middle. The  $\langle step \rangle$  value describes a shrink offset used for the combination of the partial shadows. The shadow is filled along a TikZ path with the given TikZ  $\langle options \rangle$  but any opacity value will be ignored.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.1pt,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My own shadow,
  lifted shadow={1mm}{-2mm}{3mm}{0.1mm}%
    {black!50!white}]
  This is a tcolorbox.
\end{tcolorbox}
```

**My own shadow**

This is a tcolorbox.

**/tcb/drop lifted shadow**= $\langle color \rangle$  (style, default black!50!white)

Adds a new lifted shadow with standard dimensions to the stack of shadows. Optionally, the  $\langle color \rangle$  for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.4pt,sharp corners,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop lifted shadow]
  This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop lifted shadow=blue]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

**/tcb/drop small lifted shadow**= $\langle color \rangle$  (style, default black!50!white)

Adds a new small lifted shadow with standard dimensions to the stack of shadows. Optionally, the  $\langle color \rangle$  for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  boxrule=0.4pt,sharp corners,
  colframe=red!75!black,fonttitle=\bfseries}

\tcbbox[drop small lifted shadow,size=fbox]
  {This is a tcolorbox.}
\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop small lifted shadow=black]
  This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**Another shadow**

This is a tcolorbox.

`/tcb/drop large lifted shadow=<color>` (style, default black!50!white)

Adds a new large lifted shadow with standard dimensions to the stack of shadows. Optionally, the `<color>` for the shadow can be changed.

```
\tcbset{enhanced,colback=red!5!white,
  colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[drop large lifted shadow]
This is a tcolorbox.
\end{tcolorbox}\par\bigskip
\begin{tcolorbox}[title=Another shadow,
  drop large lifted shadow=blue]
This is a tcolorbox.
\end{tcolorbox}
```

This is a tcolorbox.

**Another shadow**


This is a tcolorbox.

## 9.7 TikZ Picture Option Keys

The following general options are applicable for skins which use `tikzpicture` as `/tcb/graphical environment`<sup>→ P.105</sup>. Therefore, the skin `standard`<sup>→ P.166</sup> does not support these options, but most other skins, e.g. `enhanced`<sup>→ P.168</sup>.

**`/tcb/tikz=<tikz option list>`** (no default, initially empty)

Adds the given *<tikz option list>* to the main `tikzpicture` environment used to draw the color box, see [20]. If this option is applied a second time, the new *<tikz option list>* is appended to the current option list.



**`/tcb/tikz reset`** (initially set)

Removes all options given by `/tcb/tikz`.

**`/tcb/at begin tikz=<tikz code>`** (no default, initially empty)

The given *<tikz code>* is executed at the beginning of the `tikzpicture` environment after the TikZ option `execute at begin picture` was applied. If this option is applied a second time, the new *<tikz code>* is appended to the current code.

**`/tcb/at begin tikz reset`** (initially set)

Removes all code given by `/tcb/at begin tikz`.

**`/tcb/at end tikz=<tikz code>`** (no default, initially empty)

The given *<tikz code>* is executed at the ending of the `tikzpicture` environment before the TikZ option `execute at end picture` was applied. If this option is applied a second time, the new *<tikz code>* is appended to the current code.

**`/tcb/at end tikz reset`** (initially set)


Removes all code given by `/tcb/at end tikz`.

**/tcb/rotate**= $\langle angle \rangle$  (no default, initially unset)

Rotates the `tcolorbox` by the given  $\langle angle \rangle$ . Note that this is a TikZ coordinate transformation i.e. not all graphical elements like shadings will really be rotated.

```
\tcbset{enhanced,colback=red!5!white,
colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=Rotated box,rotate=30]
This is a tcolorbox.
\end{tcolorbox}
```





**/tcb/scale**= $\langle fraction \rangle$  (no default, initially unset)

Scales the `tcolorbox` by the given  $\langle fraction \rangle$ . Note that this is a TikZ coordinate transformation i.e. not all graphical elements like line widths will really be scaled.

```
\tcbset{enhanced,colback=red!5!white,
colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[title=Scaled box,scale=0.5]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[title=Scaled box,scale=1.25]
This is a tcolorbox.
\end{tcolorbox}
```



**/tcb/remember** (style, initially unset)

Shortcut for `tikz={remember picture}`. This allows one to reference nodes in other TikZ pictures.

```
\begin{tcolorbox}[enhanced,remember,colback=red!5!white,colframe=red!75!black,
fonttttitle=\bfseries,title=The four corners of a paper,
overlay={\draw[red!50!white,line width=1mm,opacity=0.5,shorten >=3mm]
(frame.north west) edge[->] (current page.north west)
(frame.north east) edge[->] (current page.north east)
(frame.south west) edge[->] (current page.south west)
(frame.south east) edge[->] (current page.south east);}]
This is a tcolorbox.
\end{tcolorbox}
```



`/tcb/remember as=<name>` (style, no default, initially unset)

The `frame` node will be remembered by the given `<name>` to be referenced in other TikZ pictures.


```
% \usepackage{lipsum}
\newtcolorbox{mybox}[1][]{enhanced,colframe=blue!75!black,colback=blue!10!white,
fonttitle=\bfseries,#1}

\begin{mybox}[title=First Box,nobeforeafter,width=\linewidth/4,remember as=one]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Second Box,nobeforeafter,width=\linewidth/4,remember as=two]
This is a test.
\end{mybox}
\hfill
\begin{mybox}[title=Third Box,nobeforeafter,width=\linewidth/4,remember as=three]
This is a test.
\end{mybox}

\lipsum[2]

\begin{mybox}[title=Fourth Box,remember as=four]
This is a test.
\end{mybox}

\begin{tikzpicture}[overlay,remember picture,line width=1mm,draw=red!75!black]
\draw[->] (one.east) to[bend right] node[above] {A} (two.west);
\draw[->] (two.east) to[bend left] node[above] {B} (three.west);
\draw[->] (three.east) to[bend left=90] node[right] {C} (four.east);
\draw[->] (four.west) to[bend left=90] node[left] {D} (one.west);
\end{tikzpicture}
```





## 9.8 Underlay Option Keys

Underlays are quite similar to overlays described in Section 4.11 on page 61. Underlays are drawn *after* the frame and interior are drawn and *before* overlays and the text content is drawn; see Section 8.4 on page 113 for the general drawing scheme.

The differences between underlays and overlays are:

- Underlays are not applicable for the skins `standard`<sup>→ P.166</sup> and `standard jigsaw`<sup>→ P.167</sup>, whereas overlays are applicable also for these skins. The skin `spartan`<sup>→ P.204</sup> supports underlays but no overlays.

If an underlay is used with the `standard`<sup>→ P.166</sup> skin, it is silently ignored.

- Underlays are stackable, i.e. several different underlays can be used on the same `tcolorbox`. Overlays are not stackable by default (but with some help of the library `hooks`).
- Boxed titles are implemented with underlays (Section 9.2 on page 123), watermarks are implemented with overlays (Section 9.3 on page 130).

`/tcb/underlay=<graphical code>` (no default, initially unset)

Adds `<graphical code>` to the box drawing process. This `<graphical code>` is drawn *after* the frame and interior and *before* the text content.

```
\newtcolorbox{mybox}[1][\{enhanced,colback=red!5!white,
colbacktitle=red!85!black!50!white,
colframe=red!75!black,fonttitle=\bfseries,watermark color=yellow!50!white,
underlay={\begin{tcbclipinterior}
\draw[red!40!white,line width=1cm] (interior.south west)--(interior.north east);
\end{tcbclipinterior}}},
attach boxed title to top center={yshift=-2mm},#1}

\begin{mybox}[title=My box,watermark text=My Watermark]
\lipsum[2]
\end{mybox}
```

My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/no underlay` (style, no default, initially set)

Removes the underlay if set before.

**/tcb/underlay broken**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 If the box is set to be **/tcb/breakable**<sup>→ P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/underlay unbroken**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 If the box is set to be **/tcb/breakable**<sup>→ P. 296</sup> but *is not* broken actually or if the box is set to be **/tcb/unbreakable**<sup>→ P. 297</sup>, then the  $\langle graphical\ code \rangle$  is added to the box drawing process. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/no underlay unbroken** (style, no default, initially set)  
 Removes the unbroken underlay if set before.

**/tcb/underlay first**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 If the box is set to be **/tcb/breakable**<sup>→ P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process for the *first* part of the break sequence. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/no underlay first** (style, no default, initially set)  
 Removes the first underlay if set before.

**/tcb/underlay middle**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 If the box is set to be **/tcb/breakable**<sup>→ P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process for the *middle* parts (if any) of the break sequence. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/no underlay middle** (style, no default, initially set)  
 Removes the middle underlay if set before.

**/tcb/underlay last**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 If the box is set to be **/tcb/breakable**<sup>→ P. 296</sup> and *is* broken actually, then the  $\langle graphical\ code \rangle$  is added to the box drawing process for the *last* part of the break sequence. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/no underlay last** (style, no default, initially set)  
 Removes the last underlay if set before.

**/tcb/underlay boxed title**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 If the box has a *boxed title*, see Section 9.2 on page 123, then the  $\langle graphical\ code \rangle$  is added to the box drawing process *before* the boxed title is drawn.

**/tcb/no underlay boxed title** (style, no default, initially set)  
 Removes the boxed title underlay if set before.

**/tcb/underlay unbroken and first**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 This is an abbreviation for setting **/tcb/underlay unbroken** and **/tcb/underlay first** together. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/underlay middle and last**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 This is an abbreviation for setting **/tcb/underlay middle** and **/tcb/underlay last** together. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/underlay unbroken and last**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 This is an abbreviation for setting **/tcb/underlay unbroken** and **/tcb/underlay last** together. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

**/tcb/underlay first and middle**= $\langle graphical\ code \rangle$  (no default, initially unset)  
 This is an abbreviation for setting **/tcb/underlay first** and **/tcb/underlay middle** together. **/tcb/underlay**<sup>→ P. 159</sup> overwrites this key.

## 9.9 Finish Option Keys

Finishes are quite similar to underlays described in Section 9.8 on page 159 and overlays described in Section 4.11 on page 61. Finishes are drawn *after* the text content is drawn; see Section 8.4 on page 113 for the general drawing scheme. Therefore, a finish will reduce the readability of the text content.

Finishes are intended for special effects like highlights or glosses or text over text.

- Finishes are only applicable for the skins `enhanced`<sup>→ P. 168</sup>, `empty`<sup>→ P. 195</sup>, `freelance`<sup>→ P. 207</sup>, `bicolor`<sup>→ P. 181</sup>, `beamer`<sup>→ P. 186</sup>, and `widget`<sup>→ P. 191</sup>.

If a finish is used with the `standard`<sup>→ P. 166</sup> skin, it is silently ignored.

- Finishes are stackable, i. e. several different finishes can be used on the same `tcolorbox`.

`/tcb/finish=<graphical code>` (no default, initially unset)

Adds `<graphical code>` to the box drawing process. This `<graphical code>` is drawn *after* the text content.

```
\newtcolorbox{mybox}[1][\{enhanced,colback=red!5!white,
colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
finish={\begin{tcbclipframe}
\path[bottom color=black,top color=black!50!white,opacity=0.1]
(frame.south west) -- (frame.south east) -- (frame.north east) -- cycle;
\path[top color=white,bottom color=black!50!white,opacity=0.1]
(frame.south west) -- (frame.north east) -- (frame.north west) -- cycle;
\end{tcbclipframe}}\},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

### My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\newtcolorbox{mybox}[1][\{enhanced,colback=red!5!white,
colbacktitle=red!85!black!50!white,colframe=red!75!black,fonttitle=\bfseries,
finish={\node[draw,fill=white,fill opacity=0.85,inner sep=5mm,
rounded corners] at (frame.center) {\Huge\bfseries Finish!}}\},#1}

\begin{mybox}[title=My box]
\lipsum[2]
\end{mybox}
```

### My box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

**Finish!**

<b>/tcb/no finish</b>	(style, no default, initially set)
Removes the finish if set before.	
<b>/tcb/finish broken</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
If the box is set to be <b>/tcb/breakable</b> <sup>→ P. 296</sup> and <i>is</i> broken actually, then the $\langle graphical\ code \rangle$ is added to the box drawing process. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/finish unbroken</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
If the box is set to be <b>/tcb/breakable</b> <sup>→ P. 296</sup> but <i>is not</i> broken actually or if the box is set to be <b>/tcb/unbreakable</b> <sup>→ P. 297</sup> , then the $\langle graphical\ code \rangle$ is added to the box drawing process. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/no finish unbroken</b>	(style, no default, initially set)
Removes the unbroken finish if set before.	
<b>/tcb/finish first</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
If the box is set to be <b>/tcb/breakable</b> <sup>→ P. 296</sup> and <i>is</i> broken actually, then the $\langle graphical\ code \rangle$ is added to the box drawing process for the <i>first</i> part of the break sequence. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/no finish first</b>	(style, no default, initially set)
Removes the first finish if set before.	
<b>/tcb/finish middle</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
If the box is set to be <b>/tcb/breakable</b> <sup>→ P. 296</sup> and <i>is</i> broken actually, then the $\langle graphical\ code \rangle$ is added to the box drawing process for the <i>middle</i> parts (if any) of the break sequence. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/no finish middle</b>	(style, no default, initially set)
Removes the middle finish if set before.	
<b>/tcb/finish last</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
If the box is set to be <b>/tcb/breakable</b> <sup>→ P. 296</sup> and <i>is</i> broken actually, then the $\langle graphical\ code \rangle$ is added to the box drawing process for the <i>last</i> part of the break sequence. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/no finish last</b>	(style, no default, initially set)
Removes the last finish if set before.	
<b>/tcb/finish unbroken and first</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
This is an abbreviation for setting <b>/tcb/finish unbroken</b> and <b>/tcb/finish first</b> together. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/finish middle and last</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
This is an abbreviation for setting <b>/tcb/finish middle</b> and <b>/tcb/finish last</b> together. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/finish unbroken and last</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
This is an abbreviation for setting <b>/tcb/finish unbroken</b> and <b>/tcb/finish last</b> together. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	
<b>/tcb/finish first and middle</b> = $\langle graphical\ code \rangle$	(no default, initially unset)
This is an abbreviation for setting <b>/tcb/finish first</b> and <b>/tcb/finish middle</b> together. <b>/tcb/finish</b> <sup>→ P. 161</sup> overwrites this key.	

## 9.10 Jigsaw Skin Variants

As described in Section 8.1 on page 105, a `tcolorbox` is drawn by up to four *engines*. Typically, the *frame* engine fills the complete box area with color and the other engines fill certain areas with other colors. Finally, only the area which you see as *frame* of the box will display the frame color. For most applications, this is a good approach.

For certain boxes, a more delicate procedure is needed. E.g., if the box should be translucent, an already painted area cannot be made unpainted. Therefore, more elaborate frame engines saw holes into the frame where the interior area and optionally the title area will be painted. The resulting skins are called *jigsaw* skins. For `standard`<sup>→ P.166</sup> and `enhanced`<sup>→ P.168</sup>, there are variants called `standard jigsaw`<sup>→ P.167</sup> and `enhanced jigsaw`<sup>→ P.175</sup>.

```
\newcommand{\ballexample}{\begin{tikzpicture}
  \path[use as bounding box] (0,0.8) rectangle +(0.1,0.1);
  \shadedraw [shading=ball] (0,0) circle (1cm);
  \shadedraw [ball color=red] (3,-2.2) circle (1cm);
\end{tikzpicture}}

\tcbset{enhanced,colback=blue!5!white,
  frame style={left color=red!75!black,right color=red!10!yellow},
  fonttitle=\bfseries }

\ballexample

\begin{tcolorbox}[title=A normal box]
  \lipsum[2]
\end{tcolorbox}

\ballexample

\begin{tcolorbox}[title=A translucent jigsaw box,
  enhanced jigsaw,opacityback=0.35]
  \lipsum[2]
\end{tcolorbox}
```

### A normal box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

### A translucent jigsaw box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```

\tcbset{enhanced,colback=red!10!white,coltitle=black,
  frame style={left color=red!75!black,right color=red!10!yellow},
  fonttitle=\bfseries,interior hidden,title hidden}

\begin{tcolorbox}[title=A normal box with hidden interior and title]
  This is a tcolorbox.
\end{tcolorbox}

\begin{tcolorbox}[enhanced jigsaw,
  title=A jigsaw box with hidden interior and title]
  This is a tcolorbox.
\end{tcolorbox}

```

A normal box with hidden interior and title

This is a tcolorbox.

A jigsaw box with hidden interior and title

This is a tcolorbox.

```

\newtcolorbox{mybox}{skin=enhancedmiddle jigsaw,leftrule=5mm,rightrule=5mm,
  boxsep=0mm,top=0mm,bottom=0mm,
  frame style={top color=blue,bottom color=red},interior hidden}

\begin{mybox}
  \lipsum[2]
\end{mybox}

```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



## 9.11 Draft Mode

To reduce the compilation time while drafting a document, the *draft mode* can be applied. Basically, it changes all skins to `spartan`<sup>→P.204</sup> and sets the `/tcb/fit algorithm`<sup>→P.322</sup> to `squeeze`. Especially, when fuzzy shadows are used, the speedup will be considerable high.

It is strongly recommended that the draft mode is *not* used for the final document. Use `spartan`<sup>→P.204</sup> directly, if you want to stay with it. The draft mode implementation may change in future.

Normally, switching to the draft mode should not alter the geometry of your document. Since overlays are deactivated, any code placed there (e.g. counter changes) is not executed anymore! Also, `/tcb/remember as`<sup>→P.158</sup> will not have any effect. You may exclude critical code with `\tcbinterruptdraftmode` / `\tcbcontinuedraftmode` from converting to draft mode.

### `\tcbstartdraftmode`

Any following `tcolorbox` code is put into *draft mode*. All skin settings are overruled with `spartan`<sup>→P.204</sup>. Overlays, watermarks, shadows, borderlines, and rounded corners are deactivated for all `tcolorbox` layers.

### `\tcbstopdraftmode`

The *draft mode* is deactivated for the following code.

### `\tcbinterruptdraftmode`

If the compilation is in *draft mode*, the *draft mode* is deactivated until a following `\tcbcontinuedraftmode` is detected.

If the compilation is not in *draft mode*, nothing happens and a following `\tcbcontinuedraftmode` will not start the *draft mode*.

The pair `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` cannot be used nested.

### `\tcbcontinuedraftmode`

Continues the *draft mode* which was suspended by a preceding `\tcbinterruptdraftmode`. Nothing happens, if there was no draft mode before `\tcbinterruptdraftmode`.

Code, which is place between `\tcbinterruptdraftmode` and `\tcbcontinuedraftmode` is shielded from *draft mode*.

`/tcb/draftmode=true|false` (default `true`, initially `false`)

If set to `true`, the *draft mode* is started. If set to `false`, the *draft mode* is stopped.

```
\newtcolorbox{mybeamer}[2][\beamer,colback=Salmon!50!white,
colframe=FireBrick!75!black,adjusted title={#2},#1}

\begin{mybeamer}{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}\par\medskip
\begin{mybeamer}[draftmode]{Beamer box}
This box looks like a box provided by the \texttt{beamer} class.
\end{mybeamer}
```

Beamer box

This box looks like a box provided by the `beamer` class.

Beamer box

This box looks like a box provided by the `beamer` class.



## 9.12 Skin Family 'standard'

Note that the option keys `/tcb/frame style`<sup>→P.117</sup>, `/tcb/interior style`<sup>→P.118</sup>, `/tcb/segmentation style`<sup>→P.120</sup>, and `/tcb/title style`<sup>→P.120</sup> are not applicable to the standard skin. Also, watermarks (see Subsection 9.3) are not usable with the standard skin.

`/tcb/skin=standard` (skin)

This is the standard skin from the core package. All drawing engines are set to type standard. The drawing is based on pgf commands and does not need the tikz package.

### Environment and engines for the skin 'standard'

<code>/tcb/graphical environment</code> <sup>→P.105</sup> :	<code>pgfpicture</code>
<code>/tcb/frame engine</code> <sup>→P.106</sup> :	<code>standard</code>
<code>/tcb/interior titled engine</code> <sup>→P.106</sup> :	<code>standard</code>
<code>/tcb/interior engine</code> <sup>→P.107</sup> :	<code>standard</code>
<code>/tcb/segmentation engine</code> <sup>→P.107</sup> :	<code>standard</code>
<code>/tcb/title engine</code> <sup>→P.107</sup> :	<code>standard</code>

`/tcb/standard` (style, no value)

This is an abbreviation for setting `skin=standard`.

```
\begin{tcbrafter}[standard,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=standard jigsaw` (skin)

This is the standard jigsaw skin from the core package. It differs from the skin `standard`<sup>→P.166</sup> by its frame engine, see Section 9.10 on page 163.

Environment and engines for the skin 'standard jigsaw'

```
/tcb/graphical environment→P.105: pgfpicture
/tcb/frame engine→P.106: standardjigsaw
/tcb/interior titled engine→P.106: standard
/tcb/interior engine→P.107: standard
/tcb/segmentation engine→P.107: standard
/tcb/title engine→P.107: standard
```

`/tcb/standard jigsaw` (style, no value)

This is an abbreviation for setting `skin=standard jigsaw`.

```
\begin{tcbrafter}[standard jigsaw,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

## 9.13 Skin Family 'enhanced'

If you like the standard appearance of a `tcolorbox` but you want to have some 'enhanced' features, the `enhanced` skin is what you are looking for.

`/tcb/skin=enhanced` (skin)

This skin translates the drawing commands of the core package into `tikz` path commands. Therefore, it allows all `tikz` high level options for these paths and has more flexibility compared to the `standard`<sup>→P.166</sup> skin. You pay for this with some prolonged compilation time. The `tikz` path options can be given with the option keys `/tcb/frame style`<sup>→P.117</sup>, `/tcb/interior style`<sup>→P.118</sup>, `/tcb/segmentation style`<sup>→P.120</sup>, and `/tcb/title style`<sup>→P.120</sup>.

### Environment and engines for the skin 'enhanced'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: path
/tcb/interior titled engine→P.106: path
/tcb/interior engine→P.107: path
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: path
```

`/tcb/enhanced` (style, no value)

This is an abbreviation for setting `skin=enhanced`.

```
\begin{tcbraster}[enhanced,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

```
% \usetikzlibrary{shadings} % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,
  frame style={upper left=blue,upper right=red,lower left=yellow,lower right=green},
  interior style={white,opacity=0.5},
  segmentation style={black,solid,opacity=0.2,line width=1pt}}

\begin{tcolorbox}[title=Nice box in rainbow colors]
  With the 'enhanced' skin, it is quite easy to produce fancy looking effects.
  \tcblower
  Note that this is still a \texttt{tcolorbox}.
\end{tcolorbox}
```

#### Nice box in rainbow colors

With the 'enhanced' skin, it is quite easy to produce fancy looking effects.

Note that this is still a `tcolorbox`.

```
% \usetikzlibrary{decorations.pathmorphing} % preamble
\tcbset{skin=enhanced,fonttitle=\bfseries,boxrule=1mm,
  frame style={draw=FireBrick,fill=Salmon},drop fuzzy shadow,
  interior style={draw=FireBrick,top color=Salmon!10,bottom color=Salmon!20},
  segmentation style={draw=FireBrick,solid,decorate,
    decoration={coil,aspect=0,segment length=10.1mm}}}}

\begin{tcblisting}{title=A listing box with shadow and some specials}
Of course, skins can be used for listings also.
\begin{equation}
\int\limits_1^2 \frac{1}{x} dx = \ln(2).
\end{equation}
\end{tcblisting}
```

#### A listing box with shadow and some specials

Of course, skins can be used for listings also.

```
\begin{equation}
\int\limits_1^2 \frac{1}{x} dx = \ln(2).
\end{equation}
```

Of course, skins can be used for listings also.

$$\int_1^2 \frac{1}{x} dx = \ln(2). \quad (2)$$

**/tcb/enhanced standard** (style, no value)

For unbreakable boxes, this is identical to using **/tcb/enhanced**<sup>→P. 168</sup>. But, for breakable boxes, the *break sequence* is identical to the **standard**<sup>→P. 166</sup> skin, see Section 15.6 from page 305.

**/tcb/blank** (style, initially unset)

This style relies on the skin **enhanced**<sup>→P. 168</sup>. All drawing operations are hidden and all margins are set to 0pt. See **/tcb/blanker**<sup>→P. 196</sup> for switching off the drawing engines.

```
\begin{tcolorbox}[blank,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

## `\tcbline`

Sometimes, a line is only a line. With `\tcblower`<sup>→P.11</sup> you separate the box content into two functional units. `\tcbline` draws only a line which looks like the segmentation line between upper and lower part. Furthermore, you can use `\tcbline` more than just once. `\tcbline` always uses the `path` drawing engine. Therefore, the `/tcb/segmentation` style<sup>→P.120</sup> can be applied.

```
\tcbset{enhanced,colframe=blue!50!black,colback=white}  
  
\begin{tcolorbox}[colupper=red!50!black,collower=green!50!black]  
  \lipsum[1]  
  \tcbline  
  \lipsum[2]  
  \tcblower  
  \lipsum[3]  
  \tcbline  
  \lipsum[4]  
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

## `\tcbline*`

Equivalent to `\tcbline`, but in a breakable box, `\tcbline*` is removed if at a page/box break. Also, it is removed at the end of a box.

`/tcb/skin=enhancedfirst` (skin)

This is a flavor of `enhanced`<sup>→P.168</sup> which is used as a *first* part in a break sequence for `enhanced`<sup>→P.168</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'enhancedfirst'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathfirst
/tcb/interior titled engine→P.106: pathfirst
/tcb/interior engine→P.107: pathfirst
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: pathfirst
```

```
\begin{tcbrafter}[skin=enhancedfirst,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.



`/tcb/skin=enhancedmiddle` (skin)

This is a flavor of `enhanced`<sup>→P.168</sup> which is used as a *middle* part in a break sequence for `enhanced`<sup>→P.168</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'enhancedmiddle'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathmiddle
/tcb/interior titled engine→P.106: pathmiddle
/tcb/interior engine→P.107: pathmiddle
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: pathmiddle
```

```
\begin{tcbrafter}[skin=enhancedmiddle,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcbblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcbblower
More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

-----  
More content.

This is my content.

This is my content.

-----  
More content.

`/tcb/skin=enhancedlast` (skin)

This is a flavor of `enhanced`<sup>→P.168</sup> which is used as a *last* part in a break sequence for `enhanced`<sup>→P.168</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'enhancedlast'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathlast
/tcb/interior titled engine→P.106: pathlast
/tcb/interior engine→P.107: pathlast
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: pathlast
```

```
\begin{tcbrafter}[skin=enhancedlast,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

-----  
More content.

This is my content.

This is my content.

-----  
More content.

`/tcb/skin=enhanced jigsaw` (skin)

This is the jigsaw variant of skin `enhanced`<sup>→P.168</sup>. It differs by its frame engine, see Section 9.10 on page 163.

#### Environment and engines for the skin 'enhanced jigsaw'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathjigsaw
/tcb/interior titled engine→P.106: path
/tcb/interior engine→P.107: path
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: path
```

`/tcb/enhanced jigsaw` (style, no value)

This is an abbreviation for setting `skin=enhanced jigsaw`.

```
\begin{tcbraster}[enhanced jigsaw,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=enhancedfirst jigsaw` (skin)

This is the jigsaw variant of skin `enhancedfirst`<sup>→P. 172</sup>. It differs by its frame engine, see Section 9.10 on page 163.

#### Environment and engines for the skin 'enhancedfirst jigsaw'

```
/tcb/graphical environment→P. 105: tikzpicture
/tcb/frame engine→P. 106: pathfirstjigsaw
/tcb/interior titled engine→P. 106: pathfirst
/tcb/interior engine→P. 107: pathfirst
/tcb/segmentation engine→P. 107: path
/tcb/title engine→P. 107: pathfirst
```

```
\begin{tcbraster}[skin=enhancedfirst jigsaw,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=enhancedmiddle jigsaw` (skin)

This is the jigsaw variant of skin `enhancedmiddle`<sup>→P.173</sup>. It differs by its frame engine, see Section 9.10 on page 163.

#### Environment and engines for the skin 'enhancedmiddle jigsaw'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathmiddlejigsaw
/tcb/interior titled engine→P.106: pathmiddle
/tcb/interior engine→P.107: pathmiddle
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: pathmiddle
```

```
\begin{tcbraster}[skin=enhancedmiddle jigsaw,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcbblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcbblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/marker` (style, no value)

This styles relies on the skin `enhancedmiddle jigsaw`. It is intended to be used as an optical marker like a highlighter pen.

```
\begin{tcolorbox}[marker]
\lipsum[2]
\end{tcolorbox}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This examples demonstrates the creation of several *text marker* environments based on `enhancedmiddle` → P. 173.

```
\tcbset{textmarker/.style={%
  skin=enhancedmiddle jigsaw,breakable,parbox=false,
  boxrule=0mm,leftrule=5mm,boxsep=0mm,arc=0mm,outer arc=0mm,
  left=3mm,right=3mm,top=1mm,bottom=1mm,toptitle=1mm,bottomtitle=1mm,oversize}}

\newtcolorbox{yellow}{textmarker,colback=yellow!5!white,colframe=yellow}
\newtcolorbox{orange}{textmarker,colback=DarkOrange!5!white,
  colframe=DarkOrange!75!yellow}
\newtcolorbox{red}{textmarker,colback=red!5!white,colframe=red}
\newtcolorbox{blue}{textmarker,colback=DeepSkyBlue!5!white,colframe=DeepSkyBlue}
\newtcolorbox{green}{textmarker,colback=Chartreuse!5!white,colframe=Chartreuse}
\newtcolorbox{rainbow}{textmarker,interior hidden,
  frame style={top color=blue,bottom color=red,middle color=green}}

\begin{yellow}
  \lipsum[1-3]
\end{yellow}

\begin{orange}
  \lipsum[4]
\end{orange}

\begin{red}
  \lipsum[5]
\end{red}

\begin{green}
  \lipsum[6]
\end{green}

\begin{blue}
  \lipsum[7]
\end{blue}

\begin{rainbow}
  \lipsum[8]
\end{rainbow}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.



`/tcb/skin=enhancedlast jigsaw` (skin)

This is the jigsaw variant of skin `enhancedlast`<sup>→P.174</sup>. It differs by its frame engine, see Section 9.10 on page 163.

#### Environment and engines for the skin 'enhancedlast'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathlastjigsaw
/tcb/interior titled engine→P.106: pathlast
/tcb/interior engine→P.107: pathlast
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: pathlast
```

```
\begin{tcbraster}[skin=enhancedlast jigsaw,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
opacityframe=0.5,opacityback=0.5,opacitybacktitle=0.5,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

-----  
More content.

This is my content.

This is my content.

-----  
More content.

## 9.14 Skin Family 'bicolor'

`/tcb/skin=bicolor` (skin)


This skin is quite similar to the `standard`<sup>→P. 166</sup> and `enhanced`<sup>→P. 168</sup> skin. But instead of a segmentation line, the optional lower part of the box is filled with a different color or drawn with a different style.

### Environment and engines for the skin 'bicolor'

```
/tcb/graphical environment→P. 105: tikzpicture
/tcb/frame engine→P. 106: path
/tcb/interior titled engine→P. 106: special
/tcb/interior engine→P. 107: special
/tcb/segmentation engine→P. 107: special
/tcb/title engine→P. 107: path
```

- The most basic usage of this skin is to set the background color of the lower part by `/tcb/colbacklower`<sup>→P. 182</sup> and all other options like for the `standard`<sup>→P. 166</sup> skin.

```
\begin{tcolorbox}[skin=bicolor,title=The title,
  colframe=FireBrick!75!black,colback=Salmon!50!white,colbacklower=Salmon]
  The upper part.
  \tcblower
  The lower part.
\end{tcolorbox}
```




The title

The upper part.

The lower part.

- The more advanced usage of this skin is to apply the `/tcb/frame style`<sup>→P. 117</sup> and the `/tcb/interior style`<sup>→P. 118</sup> like for the `enhanced`<sup>→P. 168</sup> skin. Also, the `/tcb/segmentation style`<sup>→P. 120</sup> can be used, but it is applied to the whole lower part.

```
\begin{tcolorbox}[skin=bicolor,title=The title,
  frame style={top color=FireBrick,
    bottom color=FireBrick!15!white,draw=black},
  interior style={left color=Salmon,right color=Salmon!50!white},
  segmentation style={right color=Salmon,left color=Salmon!50!white}]
  The upper part.
  \tcblower
  The lower part.
\end{tcolorbox}
```



The title

The upper part.

The lower part.

`/tcb/bicolor` (style, no value)

This is an abbreviation for setting `skin=bicolor`.

```

\begin{tcbraster}[bicolor,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
  colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}

```

This is my content.

This is my content.

More content.

My title

This is my content.

My title

This is my content.

More content.

`/tcb/colbacklower=<color>` (no default, initially black!15!white)  
Sets the background `<color>` of the lower part. It depends on the skin, if this value is used.

```

\tcbset{gitexample/.style={listing and comment,comment={#1},
  skin=bicolor,boxrule=1mm,fonttitle=\bfseries,coltitle=black,
  frame style={draw=black,left color=Gold,right color=Goldenrod!50!Gold},
  colback=black,colbacklower=Goldenrod!75!Gold,
  colupper=white,collower=black,
  listing options={language={bash},aboveskip=0pt,belowskip=0pt,nolol,
  basicstyle=\ttfamily\bfseries,extendedchars=true}}}

\begin{tcblisting}{title={Snapshot of the staging area},
  gitexample={The option '-a' automatically stages all tracked and modified
    files before the commit.\par
    This can be combined with the message option '-m'
    as seen in the third line.}}

git commit
git commit -a
git commit -am 'changes to my example'
\end{tcblisting}

```

#### Snapshot of the staging area

```

git commit
git commit -a
git commit -am 'changes to my example'

```

The option '-a' automatically stages all tracked and modified files before the commit.  
This can be combined with the message option '-m' as seen in the third line.

`/tcb/skin=bicolorfirst` (skin)

This is a flavor of `bicolor`<sup>→P.181</sup> which is used as a *first* part in a break sequence for `bicolor`<sup>→P.181</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'bicolorfirst'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathfirst
/tcb/interior titled engine→P.106: special
/tcb/interior engine→P.107: special
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: pathfirst
```

```
\begin{tcbraster}[skin=bicolorfirst,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
colbacktitle=LimeGreen!75!DarkGreen,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=bicolormiddle` (skin)

This is a flavor of `bicolor`<sup>→P.181</sup> which is used as a *middle* part in a break sequence for `bicolor`<sup>→P.181</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'bicolormiddle'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathmiddle
/tcb/interior titled engine→P.106: special
/tcb/interior engine→P.107: special
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: pathmiddle
```

```
\begin{tcbraster}[skin=bicolormiddle,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
  colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=bicolorlast` (skin)

This is a flavor of `bicolor`<sup>→P.181</sup> which is used as a *last* part in a break sequence for `bicolor`<sup>→P.181</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'bicolorlast'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathlast
/tcb/interior titled engine→P.106: special
/tcb/interior engine→P.107: special
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: pathlast
```

```
\begin{tcbraster}[skin=bicolorlast,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacklower=LimeGreen!75!LightGreen,
  colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

## 9.15 Skin Family 'beamer'

`/tcb/skin=beamer` (skin)

This skin resembles boxes known from the `beamer` class and therefore is called 'beamer'. It uses the normal colors from the core package but shades them a little bit. To use this skin, the `tikz` library `shadings` has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

The appearance of the skin can be controlled by `/tcb/frame style`<sup>→P.117</sup> and `/tcb/interior style`<sup>→P.118</sup>, if needed. Here, the *segmentation* cannot be controlled by a style.

### Environment and engines for the skin 'beamer'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: path
/tcb/interior titled engine→P.106: special
/tcb/interior engine→P.107: special
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: path
```

`/tcb/beamer` (style, no value)

This is an abbreviation for setting `skin=beamer`.

It also changes the geometry and some style options.

```
\begin{tcbraster}[beamer,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.



```
\begin{tcolorbox}[beamer,colback=Salmon!50!white,colframe=FireBrick!75!black,
adjusted title=A colored box with the 'beamer' skin]
This box looks like a box provided by the \texttt{beamer} class.
\end{tcolorbox}
```

#### A colored box with the 'beamer' skin

This box looks like a box provided by the `beamer` class.

```
\begin{tcolorbox}[beamer,colframe=blue,colback=black,
watermark graphics=lichtspiel.jpg,
coltext=white,watermark opacity=0.75,watermark stretch=1.0,
title=Beamer Box with background picture]
\lipsum[1]
\end{tcolorbox}
```

#### Beamer Box with background picture

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
\newtcolorbox{myblock}[2][\%
beamer,breakable,colback=LightBlue,colframe=DarkBlue,#1,title=#2]\%

\begin{myblock}{Beamerish \texttt{block}: \texttt{myblock}}
\lipsum[1]
\end{myblock}
```

#### Beamerish block: myblock

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

`/tcb/skin=beamerfirst` (skin)

This is a flavor of `beamer`<sup>→P.186</sup> which is used as a *first* part in a break sequence for `beamer`<sup>→P.186</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'beamerfirst'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathfirst
/tcb/interior titled engine→P.106: special
/tcb/interior engine→P.107: special
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: pathfirst
```

```
\begin{tcbrafter}[beamer,skin=beamerfirst,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=beamermiddle` (skin)

This is a flavor of `beamer`<sup>→ P.186</sup> which is used as a *middle* part in a break sequence for `beamer`<sup>→ P.186</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'beamermiddle'

```
/tcb/graphical environment→ P.105: tikzpicture
/tcb/frame engine→ P.106: pathmiddle
/tcb/interior titled engine→ P.106: special
/tcb/interior engine→ P.107: special
/tcb/segmentation engine→ P.107: special
/tcb/title engine→ P.107: pathmiddle
```

```
\begin{tcbrafter}[beamer,skin=beamermiddle,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=beamerlast` (skin)

This is a flavor of `beamer`<sup>→P. 186</sup> which is used as a *last* part in a break sequence for `beamer`<sup>→P. 186</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'beamerlast'

```
/tcb/graphical environment→P. 105: tikzpicture
/tcb/frame engine→P. 106: pathlast
/tcb/interior titled engine→P. 106: special
/tcb/interior engine→P. 107: special
/tcb/segmentation engine→P. 107: special
/tcb/title engine→P. 107: pathlast
```

```
\begin{tcbrafter}[beamer,skin=beamerlast,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

## 9.16 Skin Family 'widget'

`/tcb/skin=widget` (skin)

This skin uses the normal colors from the core package but shades them a little bit. To use this skin, the `tikz` library `shadings` has to be included in the preamble by:

```
\usetikzlibrary{shadings}
```

The appearance of the skin can be controlled by `/tcb/frame style`<sup>P. 117</sup>, `/tcb/interior style`<sup>P. 118</sup>, and `/tcb/segmentation style`<sup>P. 120</sup>, if needed.

### Environment and engines for the skin 'widget'

```
/tcb/graphical environmentP. 105: tikzpicture
/tcb/frame engineP. 106: path
/tcb/interior titled engineP. 106: path
/tcb/interior engineP. 107: path
/tcb/segmentation engineP. 107: special
/tcb/title engineP. 107: special
```

`/tcb/widget` (style, no value)

This is an abbreviation for setting `skin=widget`.

It also changes the geometry and some style options.

```
\begin{tcbrafter}[widget,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

```
\begin{tcolorbox}[widget,colback=Salmon!50!white,colframe=FireBrick!75!black,
adjusted title=A colored box with the 'widget' skin]
This is my content.
\end{tcolorbox}
```

A colored box with the 'widget' skin

This is my content.

`/tcb/skin=widgetfirst`

(skin)

This is a flavor of `widget`<sup>→P.191</sup> which is used as a *first* part in a break sequence for `widget`<sup>→P.191</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'widgetfirst'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathfirst
/tcb/interior titled engine→P.106: pathfirst
/tcb/interior engine→P.107: pathfirst
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: special
```

```
\begin{tcbraster}[widget,skin=widgetfirst,raster equal height,raster columns=4,
colback=LightGreen,colframe=DarkGreen,
left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
This is my content.
\end{tcolorbox}
\begin{tcolorbox}
This is my content.
\tcbblower
More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
This is my content.
\tcbblower
More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=widgetmiddle` (skin)

This is a flavor of `widget`<sup>→P.191</sup> which is used as a *middle* part in a break sequence for `widget`<sup>→P.191</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'widgetmiddle'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathmiddle
/tcb/interior titled engine→P.106: pathmiddle
/tcb/interior engine→P.107: pathmiddle
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: special
```

```
\begin{tcbrafter}[widget,skin=widgetmiddle,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.



`/tcb/skin=widgetlast` (skin)

This is a flavor of `widget`<sup>→P.191</sup> which is used as a *last* part in a break sequence for `widget`<sup>→P.191</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'widgetlast'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: pathlast
/tcb/interior titled engine→P.106: pathlast
/tcb/interior engine→P.107: pathlast
/tcb/segmentation engine→P.107: special
/tcb/title engine→P.107: special
```

```
\begin{tcbrafter}[widget,skin=widgetlast,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

## 9.17 Skin Family 'empty'

`/tcb/skin=empty` (skin)

This skin sets all engines to **empty**, i.e. nothing is drawn at all. Therefore, this skin is a good starting point to create a complete new style by yourself.

### Environment and engines for the skin 'empty'

```
/tcb/graphical environment→ P. 105: tikzpicture
/tcb/frame engine→ P. 106: empty
/tcb/interior titled engine→ P. 106: empty
/tcb/interior engine→ P. 107: empty
/tcb/segmentation engine→ P. 107: empty
/tcb/title engine→ P. 107: empty
```

`/tcb/empty` (style, no value)

This is an abbreviation for setting `skin=empty`.

```
\begin{tcbraster}[empty,raster equal height,raster columns=4,
  coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.  
More content.

My title  
This is my content.

My title  
This is my content.  
More content.

This style relies on the skin `empty`<sup>→ P. 195</sup>. All engines are set to empty and all margins are set to 0pt. In contrast to `/tcb/blank`<sup>→ P. 170</sup>, the graphical paths are not constructed with exception of the geometry nodes.

```
\begin{tcolorbox}[blanker,watermark text=A blank box]
\lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \tcbuselibrary{fitting}
\newtcbboxfit{\mybox}[1]{blanker,width=4cm,height=7cm,top=4pt,
  watermark text=#1}

\begin{tabular}{|c|c|c|}\hline
A & B & C\\\hline
\mybox{A}{\lipsum[1]} & \mybox{B}{\lipsum[2]} & \mybox{C}{\lipsum[3]}\\\hline
\end{tabular}
```

A	B	C
<p>Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.</p>	<p>Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.</p>	<p>Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.</p>

`/tcb/skin=emptyfirst` (skin)

This is a flavor of `empty`<sup>→P.195</sup> which is used as a *first* part in a break sequence for `empty`<sup>→P.195</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'emptyfirst'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: empty
/tcb/interior titled engine→P.106: empty
/tcb/interior engine→P.107: empty
/tcb/segmentation engine→P.107: empty
/tcb/title engine→P.107: empty
```

```
\begin{tcbrafter}[empty,skin=emptyfirst,raster equal height,raster columns=4,
  coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=emptymiddle` (skin)

This is a flavor of `empty`<sup>→P.195</sup> which is used as a *middle* part in a break sequence for `empty`<sup>→P.195</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'emptymiddle'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: empty
/tcb/interior titled engine→P.106: empty
/tcb/interior engine→P.107: empty
/tcb/segmentation engine→P.107: empty
/tcb/title engine→P.107: empty
```

```
\begin{tcbrafter}[empty,skin=emptymiddle,raster equal height,raster columns=4,
  coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

`/tcb/skin=emptylast` (skin)

This is a flavor of `empty`<sup>→P.195</sup> which is used as a *last* part in a break sequence for `empty`<sup>→P.195</sup>. Nevertheless, this skin can be applied independently.

#### Environment and engines for the skin 'emptylast'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: empty
/tcb/interior titled engine→P.106: empty
/tcb/interior engine→P.107: empty
/tcb/segmentation engine→P.107: empty
/tcb/title engine→P.107: empty
```

```
\begin{tcbraster}[empty,skin=emptylast,raster equal height,raster columns=4,
  coltitle=Navy,borderline={2pt}{0pt}{black!10!white},
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.  
More content.

My title  
This is my content.

My title  
This is my content.  
More content.

This example demonstrates a breakable customized box. Here, we define an environment `freebox`. The first application of `freebox` produces an unbroken `tcolorbox`. The box is drawn by the code given by `/tcb/frame code`<sup>P.109</sup> and `/tcb/interior code`<sup>P.110</sup>. The second application of `freebox` is broken into several parts which are drawn by the codes given by `/tcb/skin first is subskin of`<sup>P.112</sup>, `/tcb/skin middle is subskin of`<sup>P.112</sup>, and `/tcb/skin last is subskin of`<sup>P.112</sup>.

```
% Preamble:
%\usepackage{tikz, lipsum}
%\tcbuselibrary{skins, breakable}
\tikzset{coltria/.style={fill=red!15!white}}

\newtcolorbox{freebox}[1][{}]{empty,breakable,leftrule=5mm,left=2mm,
  frame style={fill,top color=red!75!black,bottom color=red!75!black,middle color=red},
  colback=yellow!50!white,
  watermark color=red!50!yellow!75!white,
  watermark text on=unbroken is unbroken box,
  watermark text on=first is first part,
  watermark text on=middle is middle part,
  watermark text on=last is last part,
  % code for unbroken boxes:
  frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
    --([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
    --([yshift=5mm]frame.south east)--([xshift=-5mm]frame.south east)--cycle; },
  interior code={\path[tcb fill interior] (interior.south west)--(interior.north west)
    --([xshift=-4.8mm]interior.north east)--([yshift=-4.8mm]interior.north east)
    --([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
    --cycle; },
  % code for the first part of a break sequence:
  skin first is subskin of={emptyfirst}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --([xshift=-5mm]frame.north east)--([yshift=-5mm]frame.north east)
      --(frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
      -- +(60:2mm)-- cycle; },
    interior code={\path[tcb fill interior] (interior.south west|-frame.south)
      --(interior.north west)--([xshift=-4.8mm]interior.north east)
      --([yshift=-4.8mm]interior.north east)--(interior.south east|-frame.south)
      --cycle; },
  },%
  % code for the middle part of a break sequence:
  skin middle is subskin of={emptymiddle}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --(frame.north east)--(frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
      -- +(300:2mm) -- cycle;
      \path[coltria] ([xshift=2.5mm,yshift=1mm]frame.south west) -- +(120:2mm)
      -- +(60:2mm) -- cycle;
    },
    interior code={\path[tcb fill interior] (interior.south west|-frame.south)
      --(interior.north west|-frame.north)--(interior.north east|-frame.north)
      --(interior.south east|-frame.south)--cycle; },
  },
  % code for the last part of a break sequence:
  skin last is subskin of={emptylast}{%
    frame code={\path[tcb fill frame] (frame.south west)--(frame.north west)
      --(frame.north east)--([yshift=5mm]frame.south east)
      --([xshift=-5mm]frame.south east)--cycle;
      \path[coltria] ([xshift=2.5mm,yshift=-1mm]frame.north west) -- +(240:2mm)
      -- +(300:2mm) -- cycle;
    },
    interior code={\path[tcb fill interior] (interior.south west)
```



```

--(interior.north west|-frame.north)--(interior.north east|-frame.north)
--([yshift=4.8mm]interior.south east)--([xshift=-4.8mm]interior.south east)
--cycle; },
},
#1}

\begin{freebox}
\lipsum[1]
\end{freebox}

\begin{freebox}
\lipsum[1-12]
\end{freebox}

```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim.

Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetur. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus. Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et,

lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

## 9.18 Skin 'spartan'

`/tcb/skin=spartan` (skin)

This skin is quite ... spartan. It supports no rounded corners, no overlays, no shadows, no borderlines, and no finishes. The only exception are underlays. One cannot do very fancy things with this skin, but it compiles very fast. Therefore, the `spartan` skin is used for the draft mode, see Section 9.11 on page 165. Nevertheless, it can be used as a normal skin.

### Environment and engines for the skin 'spartan'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106:          spartan
/tcb/interior titled engine→P.106: spartan
/tcb/interior engine→P.107:       spartan
/tcb/segmentation engine→P.107:   spartan
/tcb/title engine→P.107:          spartan
```

`/tcb/spartan` (style, no value)

This is an abbreviation for setting `skin=spartan`.

```
\begin{tcbraster}[spartan,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbraster}
```

This is my content.

This is my content.

My title

My title

More content.

This is my content.

This is my content.

More content.

## 9.19 Skin 'draft'

`/tcb/skin=draft` (skin)

This skin is intended to be used while drafting new geometric settings for a `tcolorbox`.

### Environment and engines for the skin 'draft'

```
/tcb/graphical environment→P.105: tikzpicture
/tcb/frame engine→P.106: special
/tcb/interior titled engine→P.106: special
/tcb/interior engine→P.107: special
/tcb/segmentation engine→P.107: path
/tcb/title engine→P.107: path
```

`/tcb/draft` (style, no value)

This is an abbreviation for setting `skin=draft`.

```
\begin{tcbrafter}[draft,raster equal height,raster columns=4,
  colback=LightGreen,colframe=DarkGreen,colbacktitle=LimeGreen!75!DarkGreen,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm]
\begin{tcolorbox}
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
\end{tcolorbox}
\begin{tcolorbox}[adjusted title=My title]
  This is my content.
  \tcblower
  More content.
\end{tcolorbox}
\end{tcbrafter}
```

frame: w=101.71864pt, h=56.11296pt, h=56.11296pt, h=56.11296pt, h=56.11296pt, h=56.11296pt, h=56.11296pt, h=56.11296pt  
 upper: w=87.49236pt, h=7.9310pt, h=7.9310pt, h=7.9310pt, h=7.9310pt, h=7.9310pt, h=7.9310pt, h=7.9310pt  
 upper: w=87.49236pt, h=41.8866pt, h=41.8866pt, h=41.8866pt, h=41.8866pt, h=41.8866pt, h=41.8866pt, h=41.8866pt  
 lower: w=87.49236pt, h=22.5530pt, h=22.5530pt, h=22.5530pt, h=22.5530pt, h=22.5530pt, h=22.5530pt, h=22.5530pt  
 interior: w=98.8734pt, h=53.2667pt, h=53.2667pt, h=53.2667pt, h=53.2667pt, h=53.2667pt, h=53.2667pt, h=53.2667pt

```

\vspace*{3mm}
\begin{tcolorbox}[draft,title=A colored box with the 'draft' skin]
\lipsum[1-3]
\tcblower
\lipsum[4-6]
\end{tcolorbox}

```

frame: w=423.94617pt, h=506.20157pt

A colored box with the 'draft' skin title: w=392.64822pt, h=6.2pt

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultrices et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquam.

hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultrices tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dui.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultrices auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultrices non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

interior: w=421.10092pt, h=490.04318pt

## 9.20 Skin Family 'freelance'

This skin family 'freelance' is deprecated with `tcolorbox` 3.00. It is not longer needed, because `/tcb/frame` <sup>→P.109</sup>, `/tcb/interior` <sup>→P.110</sup>, `/tcb/interior titled` <sup>→P.109</sup>, and `/tcb/title` <sup>→P.111</sup> can be applied to every skin now. In this sense, everything has become *freelance* now.

For users of `/tcb/freelance`: Old code should continue to work. There may be exceptions for breakable freelance boxes under certain circumstances. For new code, use `/tcb/empty` <sup>→P.195</sup> or `/tcb/enhanced` <sup>→P.168</sup> where you would have used `/tcb/freelance` before.

`/tcb/skin=freelance` (skin)

This skin gives full freedom for the appearance of the `tcolorbox`. All drawing engines are set to type `freelance`; they use the `tikz` package and compute the `/tcb/geometry nodes` <sup>→P.108</sup>.

### Environment and engines for the skin 'freelance'

<code>/tcb/graphical environment</code> <sup>→P.105</sup> :	<code>tikzpicture</code>
<code>/tcb/frame engine</code> <sup>→P.106</sup> :	<code>freelance</code>
<code>/tcb/interior titled engine</code> <sup>→P.106</sup> :	<code>freelance</code>
<code>/tcb/interior engine</code> <sup>→P.107</sup> :	<code>freelance</code>
<code>/tcb/segmentation engine</code> <sup>→P.107</sup> :	<code>freelance</code>
<code>/tcb/title engine</code> <sup>→P.107</sup> :	<code>freelance</code>

`/tcb/freelance` (style, no value)

This is an abbreviation for setting `skin=freelance`.

`/tcb/skin=freelancefirst` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 15.6 on page 305.

`/tcb/skin=freelancemiddle` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 15.6 on page 305.

`/tcb/skin=freelancelast` (skin)

This skin equals `freelance` with exception of the break sequence, see Section 15.6 on page 305.

`/tcb/extend freelance=<options>` (no default, initially empty)

The `<options>` are added to the skin definition of `freelance`.

`/tcb/extend freelancefirst=<options>` (no default, initially empty)

The `<options>` are added to the skin definition of `freelancefirst` which is used as first part of the break sequence of `freelance`. See `/tcb/skin first is subskin of` <sup>→P.112</sup> for a substitute of this key.

`/tcb/extend freelancemiddle=<options>` (no default, initially empty)

The `<options>` are added to the skin definition of `freelancemiddle` which is used as middle part of the break sequence of `freelance`. See `/tcb/skin middle is subskin of` <sup>→P.112</sup> for a substitute of this key.

`/tcb/extend freelancelast=<options>` (no default, initially empty)

The `<options>` are added to the skin definition of `freelancelast` which is used as last part of the break sequence of `freelance`. See `/tcb/skin last is subskin of` <sup>→P.112</sup> for a substitute of this key.



## 10 Inclusion of Boxed Image Files

The `\skins` library adds some commands to conveniently include boxed image files. For the following macros and options, the `\skins` library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```

See Section 9 on page 117 for the documentation of all other options of the `\skins` library.

### 10.1 Macros


`\tcbincludegraphics`[*<options>*]{*<file name>*}

In principle, this macro includes an image file denoted by *<file name>* using the standard `\includegraphics` and puts it into a `tcolorbox`<sup>P.11</sup>. The *<options>* are `tcolorbox` keys to set up the colored box. Use `/tcb/graphics options`<sup>P.211</sup> to specify options for the underlying `\includegraphics`. Some `tcolorbox` option keys are automatically set, namely `/tcb/enhanced`<sup>P.168</sup> and options to center the image inside the box.

The sizing of the included image is done depending on the following:

- If a `/tcb/width`<sup>P.28</sup> is specified, but no fixed `/tcb/height`<sup>P.45</sup>, the image is sized to fill the inner width of the box. The height of the box adapts to the image.
- If a fixed `/tcb/height`<sup>P.45</sup> is specified, the image is sized to fill the fixed inner area of the box.
- If the `/tcb/capture`<sup>P.85</sup> mode `/tcb/hbox`<sup>P.85</sup> is specified, the image is sized according to given `\includegraphics` options only. The box adapts to the image.


```
% \tcbuselibrary{raster}
\begin{tcbrafter}[raster columns=3,raster force size=false,size=fbox,
  colframe=red!50!black,colback=red!20!black,
  fonttitle=\bfseries,center title,drop fuzzy shadow]
\tcbincludegraphics[title=Normal]{goldshade.png}
\tcbincludegraphics[title=Fixed height,height=3cm]{goldshade.png}
\tcbincludegraphics[title=hbox mode,hbox,graphics options={width=3cm}]
{goldshade.png}
\end{tcbrafter}
```



N 2014-11-14  
U 2014-11-24

The auxiliary macro `\imagenname` may be used inside `\tcbincluegraphics`<sup>→ P. 208</sup> to display the name of the file. `\imagenname` is already partially detokenized and is allowed to contain special characters like the underscore. Note that an appropriate font is required to display such characters.

```
% \tcbuselibrary{raster}
\begin{tcbraster}[size=fbox,
  colframe=red!50!black,colback=red!20!black,
  fonttitle=\bfseries\ttfamily,center title,drop fuzzy shadow]
\tcbincluegraphics[title=\imagenname]{goldshade.png}
\tcbincluegraphics[finish={
  \node[fill=white,fill opacity=0.5,text opacity=1]
  at (frame.center) {\bfseries\ttfamily\imagenname};}]{blueshade.png}
\end{tcbraster}
```



This is a generalized version of `\tcbincludegraphics`<sup>→P.208</sup> which allows to include a complete PDF file denoted by *<file name>*. Every page is boxed into an own `tcolorbox`<sup>→P.11</sup> customized by the given *<options>*. It is reasonable to put such a series of boxes inside a `tcbraaster`<sup>→P.223</sup> for alignment.

Use `/tcb/graphics pages`<sup>→P.211</sup> to use a selection of pages instead of using the whole file. The auxiliary macro `\imagepage` may be used inside `\tcbincludepdf` to display the current page number.

```
% \tcbuselibrary{raster}
\begin{tcbraaster}[raster columns=3,colframe=blue,colback=white,
colbacktitle=blue!50!white,fonttitle=\small\bfseries\ttfamily,
left=0pt,right=0pt,top=0pt,bottom=0pt,boxsep=0pt,boxrule=0.6pt,
toptitle=1mm,bottomtitle=1mm,drop lifted shadow,center title,
graphics pages={1,...,6},title={\imagename\ [\imagepage]}]
\tcbincludepdf[tcolorbox-example.pdf]
\end{tcbraaster}
```

tcolorbox-example.pdf [1]

1 Colored boxes

My box.

My title.

My box with my title.

Upper part of my box.

Lower part of my box.

My title.

I can do this also with a title.

Lower part of my box.

Now, we play hide and seek. Where is the lower part?

Here I am.

I'm invisible until you find me.

Image settings.

My title.

This box is filled with an external image.

This can be used to show the image.

My title.

This box uses a boxed title. The box of the title can be formatted independently from the main box.

tcolorbox-example.pdf [2]

2 BfX-Examples

This is a LaTeX example.

This is a BfX example.

This is a LaTeX example.

This is a BfX example.

Theorem 3.1. Summation of Numbers

For all natural number  $n$  it holds:

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}$$

We have given Theorem 3.1 on page 2.

3.2 Theorem (Summation of Numbers): For all natural number  $n$  it holds:

$$\sum_{i=1}^n i = \frac{n(n+1)}{2}$$

tcolorbox-example.pdf [3]

4 Watermarks

Box with a watermark picture

5 Boxes in boxes

6 Breakable Boxes

tcolorbox-example.pdf [4]

4

tcolorbox-example.pdf [5]

5

tcolorbox-example.pdf [6]

6


## 10.2 Option Keys

N 2014-11-14

**/tcb/graphics options**= $\langle options \rangle$  (no default, initially empty)

Used for `\tcbincludegraphics`<sup>→ P. 208</sup> and `\tcbincludepdf`<sup>→ P. 210</sup> to specify `\includegraphics  $\langle options \rangle$` .

```
% \tcbuselibrary{raster}
\begin{tcbrafter}[raster columns=3,size=fbox,raster equal height,
  colframe=red!50!black,colback=red!20!black,drop fuzzy shadow]
  \tcbincludegraphics{goldshade.png}
  \tcbincludegraphics[graphics options={angle=20}]{goldshade.png}
  \tcbincludegraphics[graphics options={viewport=0cm 0cm 8cm 4cm,clip}]
    {goldshade.png}
\end{tcbrafter}
```



N 2014-11-14

**/tcb/graphics directory**= $\langle directory \rangle$  (no default, initially empty)

Used for `\tcbincludegraphics`<sup>→ P. 208</sup> and `\tcbincludepdf`<sup>→ P. 210</sup> to specify a file system  $\langle directory \rangle$  where the image files are located.

```
\tcbset{
  graphics directory={.},
  graphics directory={examples},
  graphics directory={../../pictures},
}
```

The `\graphicspath` macro from the `graphics` package is superior to this option. `/tcb/graphics directory` may be used especially for `\tcbincludepdf`<sup>→ P. 210</sup>.

N 2014-11-14

**/tcb/graphics pages**= $\langle selection \rangle$  (no default, initially 1,...,\pdfpages)

Used for `\tcbincludepdf`<sup>→ P. 210</sup> to specify a  $\langle selection \rangle$  of pages to be included. The largest page number is accessible by `\pdfpages`. The  $\langle selection \rangle$  has to be given using the `\foreach` syntax of `TikZ`.

```
\tcbset{
  graphics pages={1,3,7},
  graphics pages={1,...,10},
  graphics pages={1,3,...,18},
  graphics pages={100,...,\pdfpages},
}
```

## 11 TikZ Image and Picture Fill Extensions; Auxiliary Macros

The `\skins` library adds some image and picture fill options to the vast option set of TikZ [20]. These options can be used in any `tikzpicture`. For the following options, the `\skins` library has to be loaded by a package option or inside the preamble by:

```
\tcbuselibrary{skins}
```


See Section 9 on page 117 for the documentation of all other options of the `\skins` library.

### 11.1 Fill Plain

`/tikz/fill plain image=<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is put in the center of the path, but it is not resized to fit into the path area.


```
\begin{tikzpicture}
\path[draw,fill plain image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill plain image*=<file name>` (no default, initially unset)

Fills the current path with an external image referenced by `<file name>`. The image is put in the center of the path, but it is not resized to fit into the path area. The `<graphics options>` are given to the underlying `\includegraphics` command.


```
\begin{tikzpicture}
\path[draw,fill plain *
{image*={width=2.5cm}{goldshade.png}}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



`/tikz/fill plain picture=<graphical code>` (no default, initially unset)

Fills the current path with the given `<graphical code>`. The result is put in the center of the path, but it is not resized to fit into the path area. Note that this is almost identical to the standard `path picture` option.

```
\begin{tikzpicture}
\path[draw,fill plain picture={%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




## 11.2 Fill Stretch

**/tikz/fill stretch image=***<file name>* (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The image is stretched to fill the path area.


```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill stretch image\*=***<graphics options>*{*<file name>*} (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The *<graphics options>* are given to the underlying `\includegraphics` command. The image is stretched to fill the path area.


```
\begin{tikzpicture}
\path[fill stretch image*=
  {angle=90,origin=c}{goldshade.png}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill stretch picture=***<graphical code>* (no default, initially unset)

Fills the current path with the given *<graphical code>*. The result is stretched to fill the path area.

```
\begin{tikzpicture}
\path[draw,fill stretch picture={%
  \draw[red!50!yellow,line width=2mm]
    (0,0) circle (1cm);
  \draw[red,line width=5mm] (-1,-1) -- (1,1);
  \draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
  (2.75,-0.75) -- (3,0) -- (2.75,0.75)
  \foreach \w in {45,90,...,315}
    { -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```






### 11.3 Fill Overzoom

**/tikz/fill overzoom image=***<file name>* (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The image is zoomed such that the path area fills the image.


```
\begin{tikzpicture}
\path[fill overzoom image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill overzoom image\*=***<graphics options>*{*<file name>*} (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The *<graphics options>* are given to the underlying **\includegraphics** command. The image is zoomed such that the path area fills the image.


```
\begin{tikzpicture}
\path[fill overzoom image*=
{angle=90,origin=c}{goldshade.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill overzoom picture=***<graphical code>* (no default, initially unset)

Fills the current path with the given *<graphical code>*. The result is zoomed such that the path area fills the image.

```
\begin{tikzpicture}
\path[draw,fill overzoom picture={%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```






## 11.4 Fill Zoom

**/tikz/fill zoom image**=*<file name>* (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.


```
\begin{tikzpicture}
\path[draw,fill zoom image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill zoom image\***=*<graphics options>*{*<file name>*} (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The *<graphics options>* are given to the underlying **\includegraphics** command. The image is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.


```
\begin{tikzpicture}
\path[draw,fill zoom image*=
{angle=90,origin=c}{goldshade.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill zoom picture**=*<graphical code>* (no default, initially unset)

Fills the current path with the given *<graphical code>*. The result is zoomed such that it fits inside the path area. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill zoom picture={%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




## 11.5 Fill Shrink

**/tikz/fill shrink image**=*<file name>* (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.


```
\begin{tikzpicture}
\path[draw,fill shrink image=goldshade.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill shrink image\***=*<file name>* (no default, initially unset)

Fills the current path with an external image referenced by *<file name>*. The *<graphics options>* are given to the underlying **\includegraphics** command. The image is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.


```
\begin{tikzpicture}
\path[draw,fill shrink *
{image*={width=1.5cm}{goldshade.png}}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill shrink picture**=*<graphical code>* (no default, initially unset)

Fills the current path with the given *<graphical code>*. The result is zoomed such that it fits inside the path area, but it never gets enlarged. Typically, some parts of the path area will stay unfilled.

```
\begin{tikzpicture}
\path[draw,fill shrink picture={%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



## 11.6 Fill Tile

**/tikz/fill tile image**= $\langle file name \rangle$  (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by  $\langle file name \rangle$ .


```
\begin{tikzpicture}
\path[fill tile image=pink_marble.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill tile image\***= $\{\langle graphics options \rangle\}\{\langle file name \rangle\}$  (no default, initially unset)

Fills the current path with a tile pattern using an external image referenced by  $\langle file name \rangle$ . The  $\langle graphics options \rangle$  are given to the underlying **\includegraphics** command.


```
\begin{tikzpicture}
\path[fill tile image*={width=1cm}{pink_marble.png}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill tile picture**= $\langle graphical code \rangle$  (no default, initially unset)

Fills the current path with a tile pattern using the given  $\langle graphical code \rangle$ .


```
\begin{tikzpicture}
\path[draw,fill tile picture={%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



**/tikz/fill tile picture\***= $\{\langle fraction \rangle\}\{\langle graphical code \rangle\}$  (no default, initially unset)

Fills the current path with a tile pattern using the given  $\langle graphical code \rangle$ . The graphic is resized by  $\langle fraction \rangle$ .

```
\begin{tikzpicture}
\path[draw,fill tile picture*={0.25}{%
\draw[red!50!yellow,line width=2mm]
(0,0) circle (1cm);
\draw[red,line width=5mm] (-1,-1) -- (1,1);
\draw[red,line width=5mm] (-1,1) -- (1,-1);
}]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```




## 11.7 Filling Options

**/tikz/fill image opacity= $\langle fraction \rangle$**  (no default, initially 1.0)

Sets the fill opacity for the image or picture fill options to the given  $\langle fraction \rangle$ .

```
\begin{tikzpicture}
\path[fill stretch image=goldshade.png] (0,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.75]
(2,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.5]
(4,0) circle (1cm);
\path[fill=red,fill stretch image=goldshade.png,fill image opacity=0.25]
(6,0) circle (1cm);
\path[fill=red] (8,0) circle (1cm);
\end{tikzpicture}
```



**/tikz/fill image scale= $\langle fraction \rangle$**  (no default, initially 1.0)

Stretches, zooms, overzooms or shrinks the image or picture to the given  $\langle fraction \rangle$  of the width and height of the current path.

```
\begin{tikzpicture}
\path[draw,fill zoom image=goldshade.png]
(0,0) rectangle +(2,2);

\path[draw,fill zoom image=goldshade.png,fill image scale=0.75]
(3,0) rectangle +(2,2);


\path[draw,fill zoom image=goldshade.png,fill image scale=1.5]
(6,0) rectangle +(2,2);
\end{tikzpicture}
```



**/tikz/fill image options= $\langle graphics options \rangle$**  (no default, initially empty)


The  $\langle graphics options \rangle$  are given to the underlying `\includegraphics` command for the image fill options. This can be just together with `/tikz/fill stretch image`<sup>P.213</sup>, `/tikz/fill overzoom image`<sup>P.214</sup>, `/tikz/fill zoom image`<sup>P.215</sup>, and `/tikz/fill tile image`<sup>P.217</sup>.

```
\begin{tikzpicture}
\path[fill image options={width=1cm},
fill tile image=pink_marble.png]
(2.75,-0.75) -- (3,0) -- (2.75,0.75)
\foreach \w in {45,90,...,315}
{ -- (\w:1.5cm) } -- cycle;
\end{tikzpicture}
```



## Image blending example

```
\begin{tikzpicture}[every node/.style=
  {circle,minimum width=2cm}]
\node[fill stretch image=blueshade.png]
  (A) at (120:3cm) {A};
\node[fill stretch image=goldshade.png]
  (B) at (60:3cm) {B};
\node[
  preaction={fill stretch image=blueshade.png},
  fill stretch image=goldshade.png,
  fill image opacity=0.5] (C) {C};
\path (A) -- node{+} (B);
\draw[->,very thick] (A)--(C);
\draw[->,very thick] (B)--(C);
\end{tikzpicture}
```



## 11.8 Extracting Node Dimensions

The following auxiliary macros are defined by the `skins` library. They allow to determine the width and height of an arbitrary TikZ node. To be more specific, they determine the east-to-west and the north-to-south dimensions which may be not the maximal dimensions for a non-rectangular node.

N 2014-09-19

```
\tcbsettowidthofnode{\register}{\node}
```

Sets the east-to-west dimension of the given  $\langle node \rangle$  to the T<sub>E</sub>X  $\langle register \rangle$ .

N 2014-09-19

```
\tcbsetmacrotowidthofnode{\macro}{\node}
```

Defines  $\langle macro \rangle$  as the east-to-west dimension of the given  $\langle node \rangle$ .

N 2014-09-19

```
\tcbsettoheightofnode{\register}{\node}
```

Sets the north-to-south dimension of the given  $\langle node \rangle$  to the T<sub>E</sub>X  $\langle register \rangle$ .

N 2014-09-19

```
\tcbsetmacrototoheightofnode{\macro}{\node}
```

Defines  $\langle macro \rangle$  as the north-to-south dimension of the given  $\langle node \rangle$ .

```
\begin{tikzpicture}
  \node[align=center,draw=red,fill=yellow] (A) {This is my\example node};
  \tcbsetmacrotowidthofnode\mywidth{A}
  \tcbsetmacrototoheightofnode\myheight{A}
  \path[draw=blue,fill=blue!25!white] ([xshift=2mm]A.south east)
    rectangle node{Copy} +(\mywidth,\myheight);
\end{tikzpicture}
```

This is my  
example node

Copy

## 12 Library


The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{raster}
```

### 12.1 Concept of Rasters

A *raster* is used to align several colored boxes in a regular way. It can be seen as a far related counterpart to the `matrix` construct of TikZ, but it differs in many aspects.

In principle, `tcolorboxes` are arranged in rows and columns when put inside a `tcbraster`<sup>→ P. 223</sup> environment. The boxes are fluently added to the raster like adding text to a paragraph. Especially, line/row breaks are done automatically and one cannot end a line/row ahead of schedule. Further, a *raster* is not restricted to a single page but may break into an arbitrary series of pages.






```

\begin{tcbraster}[raster columns=3,raster rows=3,raster height=\linewidth,
enhanced,size=small,sharp corners,arc=8mm,colframe=red!50!black,
colback=yellow!10!white,watermark overzoom=1.0,fit algorithm=hybrid* ]
\begin{tcolorbox}[rounded corners=northwest,boxrule=0pt,
watermark graphics=lichtspiel.jpg]\end{tcolorbox}
\tcboxfit{\lipsum[1]}
\begin{tcolorbox}[rounded corners=northeast,boxrule=0pt,
watermark graphics=goldshade.png]\end{tcolorbox}
\tcboxfit{\lipsum[2]}
\begin{tcolorbox}[valign=center,center upper]Nine Boxes.\end{tcolorbox}
\tcboxfit{\lipsum[3]}
\begin{tcolorbox}[rounded corners=southwest,boxrule=0pt,
watermark graphics=goldshade.png]\end{tcolorbox}
\tcboxfit{\lipsum[4]}
\begin{tcolorbox}[rounded corners=southeast,boxrule=0pt,
watermark graphics=lichtspiel.jpg]\end{tcolorbox}
\end{tcbraster}

```



Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.



Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

### Nine Boxes.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.



Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.



## 12.2 Macros of the Library

N 2014-11-10

```
\begin{tcbrafter}[\langle options \rangle]
\langle environment content \rangle
\end{tcbrafter}
```

A raster arranges enclosed boxes in a regular way, mainly into rows and columns. The  $\langle options \rangle$  are used to control the raster parameters and to set the properties for the enclosed boxes.

- The *raster* is only allowed to contain a series of `tcolorbox`<sup>P.11</sup> environments or derived constructs. With some small restrictions, boxes created with `\tcboxfit`<sup>P.314</sup> can also be added. Boxes created with `\tcbox`<sup>P.13</sup> are not reasonable here, but may be used to a certain degree.
- Do not add anything else between the boxes inside the raster with exception of white-space. Especially, do not use `\` or `\par` to end a row; row breaks are done automatically.
- The boxes inside a raster are numbered automatically. `\thetcbrafternum` may be used inside a box to access this number.

```
\begin{tcbrafter}[raster columns=3, raster equal height,
size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
title={Box \# \thetcbrafternum}]
\begin{tcolorbox}First box\end{tcolorbox}
\begin{tcolorbox}Second box\end{tcolorbox}
\begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
\begin{tcolorbox}Another box\end{tcolorbox}
\begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbrafter}
```

Box # 1 First box	Box # 2 Second box	Box # 3 This is a box with a second line
Box # 4 Another box	Box # 5 A box again	

```
\begin{tcbrafter}[raster columns=2, raster equal height=rows,
size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
title={Box \# \thetcbrafternum}]
\begin{tcolorbox}First box\end{tcolorbox}
\begin{tcolorbox}Second box\end{tcolorbox}
\begin{tcolorbox}This is a box\\with a second line\end{tcolorbox}
\begin{tcolorbox}Another box\end{tcolorbox}
\begin{tcolorbox}A box again\end{tcolorbox}
\end{tcbrafter}
```

Box # 1 First box	Box # 2 Second box
Box # 3 This is a box with a second line	Box # 4 Another box
Box # 5 A box again	


```
\begin{tcbitemize}[\langle options \rangle]
  \langle environment content \rangle
\end{tcbitemize}
```

This is a special case of a `tcbraaster`<sup>→P.223</sup> with the given  $\langle options \rangle$ .

- Here, the enclosed boxes are created using `\tcbitem`.
- There has to be at least one `\tcbitem`.
- One cannot use anything else than `\tcbitem` to add something to the *raster*.

This leads to a very compact syntax.

```
\begin{tcbitemize}[raster columns=2, raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white,colbacktitle=red!50!white,
  title={Box \# \thetcbraaternum}]
  \tcbitem First box
  \tcbitem Second box
  \tcbitem This is a box\\with a second line
  \tcbitem[colback=yellow,colbacktitle=yellow!50!black] Another box
  \tcbitem A box again
\end{tcbitemize}
```



`tcbitemize` has more restrictions than `tcbraaster`<sup>→P.223</sup>. Especially, the `/tcb/capture`<sup>→P.85</sup> mode has to be `minipage`. For example, `/tcb/fit`<sup>→P.316</sup> cannot be used safely. If `/tcb/fit`<sup>→P.316</sup> should be used, turn over to `tcbraaster`<sup>→P.223</sup>.

```
\tcbitem[\langle options \rangle]
```

Used inside `tcbitemize` to create a new `tcolorbox`<sup>→P.11</sup> with the given  $\langle options \rangle$ .

## 12.3 Option Keys of the Library

N 2014-11-10

**/tcb/raster columns**= $\langle number \rangle$  (no default, initially 2)

Sets the  $\langle number \rangle$  of columns for a *raster*.

```
\begin{tcbitemize}[raster columns=3,
  size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
\begin{tcbitemize}[raster columns=4,
  size=small,colframe=blue!50!black,colback=blue!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

One

Two

Three

Four

N 2014-11-10

**/tcb/raster rows**= $\langle number \rangle$  (no default, initially 2)

Sets the  $\langle number \rangle$  of rows for a *raster*. Note that this is only relevant in connection with setting `/tcb/raster height`<sup>→ P. 226</sup> to a value greater than 0pt. Then, it defines the number of rows *per* given height.

N 2014-11-10

**/tcb/raster width**= $\langle length \rangle$  (no default, initially `\linewidth`)

Sets the total raster width to the given  $\langle length \rangle$ . `/tcb/raster left skip`<sup>→ P. 227</sup> and `/tcb/raster right skip`<sup>→ P. 227</sup> are part of the total width.

```
\begin{tcbitemize}[raster width=\linewidth/2,
  size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One

Two

Three


Four

N 2014-11-10

**/tcb/raster height**= $\langle length \rangle$  (no default, initially 0pt)

Sets the raster height *per* /tcb/raster rows<sup>→P.225</sup> to the given  $\langle length \rangle$ . This forces an appropriate height for the enclosed boxes. /tcb/raster before skip and /tcb/raster after skip are not part of this calculation. If the  $\langle length \rangle$  is set to 0pt, this feature is deactivated.

```
\begin{tcbitemize}[raster height=4cm, raster rows=2,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem[enhanced,
finish={\draw[blue,very thick,<->] (frame.south)
-- node[right,pos=.75]{4cm} +(0,4); }]
Three
\tcbitem Four
\tcbitem Five
\end{tcbitemize}
```



N 2014-11-10

**/tcb/raster before skip**= $\langle glue \rangle$  (no default, initially 2mm)

U 2014-12-16

Space of the given  $\langle glue \rangle$  is inserted vertically before the *raster*. This space is discardable.

N 2014-11-10

**/tcb/raster after skip**= $\langle glue \rangle$  (no default, initially 2mm)

U 2014-12-16


Space of the given  $\langle glue \rangle$  is inserted vertically after the *raster*. This space is discardable.

N 2015-01-08

**/tcb/raster equal skip**= $\langle length \rangle$  (style, no default)

Shortcut to set /tcb/raster before skip, /tcb/raster after skip, /tcb/raster column skip<sup>→P.227</sup>, and /tcb/raster row skip<sup>→P.227</sup> to the same  $\langle length \rangle$  value.

```
\begin{tcbitemize}[raster equal skip=4mm,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```



**N 2014-11-10** `/tcb/raster left skip=<length>` (no default, initially 0pt)

Space of the given  $\langle length \rangle$  is inserted horizontally left of the *raster*.

```
\begin{tcbitemize}[raster left skip=2cm,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One	Two
Three	Four

**N 2014-11-10** `/tcb/raster right skip=<length>` (no default, initially 0pt)

Space of the given  $\langle length \rangle$  is inserted horizontally right of the *raster*.

```
\begin{tcbitemize}[raster right skip=2cm,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One	Two
Three	Four

**N 2014-11-10** `/tcb/raster column skip=<length>` (no default, initially 2mm)

Space of the given  $\langle length \rangle$  is inserted horizontally between the columns.

```
\begin{tcbitemize}[raster column skip=2cm,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One	Two
Three	Four

**N 2014-11-10** `/tcb/raster row skip=<length>` (no default, initially 2mm)

Space of the given  $\langle length \rangle$  is inserted vertically between the rows.

```
\begin{tcbitemize}[raster row skip=0pt,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One	Two
Three	Four

`/tcb/raster halign=<alignment>` (no default, initially **left**)

Defines the horizontal alignment for the boxes of the rows of a *raster*, if these rows are not completely filled (mainly: the last one).

Feasible values for *<alignment>* are:

- **left**: align to the left side,
- **center**: align to the center,
- **right**: align to the right side.

```
\begin{tcbitemize}[raster halign=center,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem Three
\end{tcbitemize}
```

One

Two

Three

`/tcb/raster valign=<alignment>` (no default, initially **center**)

Defines the vertical alignment for the boxes of a row, if the boxes do not have equal height. This sets the `/tcb/box align` <sup>P. 73</sup> option.

Feasible values for *<alignment>* are:

- **top**: align to the top side,
- **center**: align to the center,
- **bottom**: align to the bottom side.

```
\begin{tcbitemize}[raster valign=top, raster columns=3,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem \Huge One
\tcbitem \Large Two
\tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=center, raster columns=3,
size=small,colframe=blue!50!black,colback=blue!10!white]
\tcbitem \Huge One
\tcbitem \Large Two
\tcbitem Three
\end{tcbitemize}
\begin{tcbitemize}[raster valign=bottom, raster columns=3,
size=small,colframe=green!50!black,colback=green!10!white]
\tcbitem \Huge One
\tcbitem \Large Two
\tcbitem Three
\end{tcbitemize}
```

One

Two

Three

One

Two

Three

One

Two

Three



`/tcb/raster equal height=<type>` (default `all`, initially `none`)

Puts the enclosed boxes into a common `/tcb/equal height group`<sup>→ P.50</sup>. The `<id>` of the equal height group is chosen automatically, but it may be set manually by `/tcb/raster equal height group`.

Feasible values for `<type>` are:

- `none`: no equal height setting,
- `rows`: all boxes in a row are set to equal height,
- `all`: all boxes in the raster are set to equal height.

Note that you have to compile twice to see changes.

```
\begin{tcbitemize}[raster equal height=rows,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem \Huge Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

```
\begin{tcbitemize}[raster equal height,
  size=small,colframe=red!50!black,colback=red!10!white]
  \tcbitem One
  \tcbitem \Huge Two
  \tcbitem Three
  \tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

`/tcb/raster equal height group=<id>` (no default)

Overwrites the automatically chosen id with the given `<id>`. If this is used to share a common height between the *raster* and another raster or box, the `/tcb/raster equal height` option should be set to `all`.

```
\tcbset{size=small,colframe=red!50!black,colback=red!10!white}
\begin{tcolorbox}[equal height group=raster-manual-id]
  A single box
\end{tcolorbox}
\begin{tcbitemize}[raster equal height,raster equal height group=raster-manual-id]
  \tcbitem One
  \tcbitem \Huge Two
\end{tcbitemize}
```

A single box


One

Two

**N 2014-11-10** `/tcb/raster force size=true|false` (default `true`, initially `true`)

Enforces the raster size computations onto the enclosed boxes. If set to `false`, individual settings can be used (for the better or worse).

```
\begin{tcbitemize}[raster force size=false, raster halign=center,
size=small,colframe=red!50!black,colback=red!10!white]
\tcbitem One
\tcbitem Two
\tcbitem[add to width=-3cm] Three
\tcbitem[add to width=-3cm] Four
\tcbitem[add to width=-3cm] Five
\tcbitem[add to width=3cm] Six
\end{tcbitemize}
```



**N 2014-11-10** `/tcb/raster reset` (no value)

Sets all raster settings back to their default values. Note that `/tcb/reset`<sup>→P.90</sup> does not execute this option. Style settings like `/tcb/raster odd column` etc. are not touched by `/tcb/raster reset`.

## 12.4 Adding Styles for Specific Boxes

The following styles can be defined to address certain boxes inside a *raster*. Note that such style definitions are not removed by `/tcb/reset`<sup>→P.90</sup> or `/tcb/raster reset`. The style definitions are used in the order given below.

**N 2014-11-24** `/tcb/raster every box` (style)

This style is used for every box.

**N 2014-11-10** `/tcb/raster odd column` (style)

This style is used for every box in an odd column.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster odd column/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```



**N 2014-11-10** `/tcb/raster even column` (style)

This style is used for every box in an even column.

**N 2014-11-10** `/tcb/raster column n` (style)

This style is used for every box in the *n*-th column. *n* has to be replaced by a number.

**N 2014-11-10** `/tcb/raster odd row` (style)

This style is used for every box in an odd row.

**N 2014-11-10** `/tcb/raster even row` (style)

This style is used for every box in an even row.

**N 2014-11-10** `/tcb/raster row m` (style)

This style is used for every box in the  $m$ -th row.  $m$  has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster row 2/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One

Two

Three

Four

**N 2014-11-10** `/tcb/raster odd number` (style)

This style is used for every box with an odd number.

**N 2014-11-10** `/tcb/raster even number` (style)

This style is used for every box with an even number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster columns=3,
raster even number/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\tcbitem Five
\tcbitem Six
\end{tcbitemize}
```

One

Two

Three

Four

Five

Six

**N 2014-11-10** `/tcb/raster row m column n` (style)

This style is used for the box in the  $m$ -th row and  $n$ -th column.  $m$  and  $n$  have to be replaced by numbers.

**N 2014-11-10** `/tcb/raster number n` (style)

This style is used for the box with number  $n$ .  $n$  has to be replaced by a number.

```
\begin{tcbitemize}[size=small,colframe=red!50!black,colback=red!10!white,
raster number 4/.style={colframe=blue!50!black,colback=blue!10!white}]
\tcbitem One
\tcbitem Two
\tcbitem Three
\tcbitem Four
\end{tcbitemize}
```

One





Two

Three

Four

## 13 Libraries , , and

### 13.1 Loading the Libraries

In contrast to other `tcolorbox` libraries, the libraries , , and  are concurrent in the sense that they all do the same thing, i. e. displaying listings with or without typesetting the listing in  $\text{\LaTeX}$  parallel. The difference is the underlying  $\text{\LaTeX}$  package which does the core job for displaying a listing. So, typically, you need just *one* of these libraries. If you do not have a clue, which one of them you should use, you should take .

The order in which the libraries are included influences the default settings and the `/tcb/reset`<sup>→ P. 90</sup> behavior. The settings of a later loaded library overwrite the settings of a previous loaded library. A library is never loaded twice.

#### 13.1.1 Loading

This library uses the package `listings` [6] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{listings}
```

This also loads the package `listings` [6].


The `/tcb/listing engine`<sup>→ P. 244</sup> is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=listings}
```

#### 13.1.2 Loading

To extend `listings` for UTF-8 encoded sources, you can use the support from the package `listingsutf8` [10] by loading the library variant .

```
\tcbuselibrary{listingsutf8}  
\tcbset{listing utf8=latin1}% optional; 'latin1' is the default.
```

This also loads the library  and the packages `listings` [6] and `listingsutf8` [10].

The `/tcb/listing engine`<sup>→ P. 244</sup> is set to `listings` by the library. To reactivate this setting, if overwritten by other libraries, use


```
\tcbset{listing engine=listings}
```

### 13.1.3 Loading

This library uses the package `minted` [14] to typeset listings. It is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{minted}
```

This also loads the package `minted` [14].

The `minted` package uses the external tool `Pygments` [12] to apply syntax highlighting. It has to be installed and set up, before the library can be used, see [14] and [12]. The `tcolorbox` library  does not work, if the package `minted` [14] does not work.

The `/tcb/listing engine` <sup>P.244</sup> is set to `minted` by the library. To reactivate this setting, if overwritten by other libraries, use

```
\tcbset{listing engine=minted}
```

## 13.2 Common Macros of the Libraries

```
\begin{tcblisting}{\langle options \rangle}
\langle environment content \rangle
\end{tcblisting}
```

Creates a colored box based on a `tcolorbox` <sup>P.11</sup>. Controlled by the given `\langle options \rangle`, the environment content is typeset normally and/or as a listing. Furthermore, the `\langle options \rangle` control appearance and functions of the `tcolorbox`. By default, the listing is interpreted as a `LATEX` listing.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

This is a `\LaTeX\` example which displays the text as source code  
and in compiled form.

This is a `LATEX` example which displays the text as source code and in compiled form.

```
% \tcbuselibrary{listings} /or/ \tcbuselibrary{listingsutf8}
\begin{tcblisting}{colback=yellow!5,colframe=yellow!50!black,listing only,
  title=This is source code in another language (XML), fonttitle=\bfseries,
  listing options={language=XML,columns=fullflexible,keywordstyle=\color{red}}}
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package_tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
```

```
% \tcbuselibrary{minted}
\begin{tcblisting}{colback=yellow!5,colframe=yellow!50!black,listing only,
  title=This is source code in another language (XML), fonttitle=\bfseries,
  listing engine=minted,minted language=xml}
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
\end{tcblisting}
```

This is source code in another language (XML)

```
<?xml version="1.0"?>
<project name="Package tcolorbox" default="documentation" basedir=".">
  <description>
    Apache Ant build file (http://ant.apache.org/)
  </description>
</project>
```

```
% This box is as wide as needed (listing only !!)
% \tcbuselibrary{skins}
\begin{tcblisting}{colback=green!5!white,colframe=green!50!black,listing only,
  hbox,enhanced,drop fuzzy shadow,before=\begin{center},after=\end{center}}
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
\end{tcblisting}
```

```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

```
\begin{tcboutputlisting}
  <environment content>
\end{tcboutputlisting}
```

Saves the environment content to a file which is named by the key value of listing file. Later, this file can be loaded by `\tcbinputlisting` or `\tcbuselistingtext` or `\tcbuselistinglisting`.

```
\begin{tcboutputlisting}
This \textbf{text} is written to a standardized file for later usage.
\end{tcboutputlisting}
```

```
\tcbinputlisting{<options>}
```

Creates a colored boxed based on a `tcolorbox`. The text content is read from a file named by the key value of listing file. Apart from that, the function is equal to that of `tcblisting` <sup>→ P. 233</sup>.

```
\tcbinputlisting{colback=red!5!white,colframe=red!75!black,text only}
\tcbinputlisting{colback=green!5,colframe=green!75!black,listing only}
```



```
\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

```
\tcbuselistingtext
```

Loads text from a file named by the key value of listing file.

```
\tcbuselistingtext
```



```
\tcbuselistinglisting
```

Typesets text as listing from a file named by the key value of listing file.

```
\tcbuselistinglisting

\begin{tikzpicture}
\fill[red] (0,0) rectangle (1,1);
\end{tikzpicture}
```

```
\tcbusetemplisting
```

Typesets text as listing from a temporary file which was written by `tcbwritetemp` <sup>→ P. 98</sup>.



See Section 18.4 on page 343 and Section 18.5 on page 345 for more elaborate methods to create new environments and commands.

If a new sort of `tcblisting` environments should be created with one optional argument only, one is highly recommended to use `\DeclareTCBListing`<sup>→ P. 343</sup> or `\NewTCBListing`<sup>→ P. 343</sup> instead of `\newtcblisting` to avoid content scanning problems.

**`\newtcblisting`***[`<init options>`]{`<name>`}[`<number>`][`<default>`]{`<options>`}*

Creates a new environment `<name>` based on `tcblisting`<sup>→ P. 233</sup>. Basically, `\newtcblisting` operates like `\newenvironment`. This means, the new environment `<name>` optionally takes `<number>` arguments, where `<default>` is the default value for the optional first argument. The `<options>` are given to the underlying `tcblisting`. Note that `/tcb/savedelimiter`<sup>→ P. 24</sup> is set to the given `<name>` automatically. The `<init options>` allow setting up automatic numbering, see Section 5 from page 92.

```
\newtcblisting{mybox}{%
  colback=red!5!white,
  colframe=red!75!black}
```

```
\begin{mybox}
This is my \LaTeX\ box.
\end{mybox}
```

This is my \LaTeX\ box.

This is my L<sup>A</sup>T<sub>E</sub>X box.

```
\newtcblisting{mybox}[1]{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=#1}
```

```
\begin{mybox}{Listing Box}
This is my \LaTeX\ box.
\end{mybox}
```

Listing Box

This is my \LaTeX\ box.

This is my L<sup>A</sup>T<sub>E</sub>X box.

```
\newtcblisting{mybox}[2][{}]{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=#2,#1}
```

```
\begin{mybox}[listing only]
{Listing Box}
This is my \LaTeX\ box.
\end{mybox}
\bigskip
```

```
\begin{mybox}[listing side text]
{Listing Box}
This is my
\LaTeX\ box.
\end{mybox}
```

Listing Box

This is my \LaTeX\ box.

Listing Box

This is my  
\LaTeX\ box.

This is my  
L<sup>A</sup>T<sub>E</sub>X box.

*Definition in the preamble:*

```
\newtcblisting[auto counter]{mycbox}[1]{%  
  colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,  
  title=Listing \thetcbcounter: #1}
```

```
\begin{mycbox}{Listing Box}  
This is my \LaTeX\ box.  
\end{mycbox}
```

#### Listing 1: Listing Box

This is my \LaTeX\ box.

This is my L<sup>A</sup>T<sub>E</sub>X box.

**\renewtcblisting***[[<init options>]]{<name>[[<number>]] [[<default>]]{<options>}}*

Operates like `\newtcblisting`<sup>→ P. 236</sup>, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

`\newtcbinputlisting` [*<init options>*] {<name>} [*<number>*] [*<default>*] {<options>}

Creates a new macro `\<name>` based on `\tcbinputlisting`<sup>P. 235</sup>. Basically, `\newtcbinputlisting` operates like `\newcommand`. The new macro `\<name>` optionally takes *<number>* arguments, where *<default>* is the default value for the optional first argument. The *<options>* are given to the underlying `tcbinputlisting`. The *<init options>* allow setting up automatic numbering, see Section 5 from page 92.

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  {\jobname.tcbtemp}
```

Listing (2) of `tcolorbox.tcbtemp`

*This is the included file content:*

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  {\jobname.tcbtemp}
```

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing engine=minted,minted language=latex,minted style=colorful,
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  {\jobname.tcbtemp}
```

Listing (3) of `tcolorbox.tcbtemp`

*This is the included file content:*

```
\newtcbinputlisting[use counter from=mycbox]{\mylisting}[2][]{%
  listing engine=minted,minted language=latex,minted style=colorful,
  listing file={#2},
  title=Listing (\thetcbcounter) of \texttt{#2},
  colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries,
  listing only,breakable,#1}

\mylisting[before upper=\textit{This is the included file content:}]
  {\jobname.tcbtemp}
```

`\renewtcbinputlisting` [*<init options>*] {<name>} [*<number>*] [*<default>*] {<options>}

Operates like `\newtcbinputlisting`, but based on `\renewcommand` instead of `\newcommand`. An existing macro is redefined.

### 13.3 Option Keys of the `listings` Library

`/tcb/listing options=<key list>` (no default, initially `style=tcblatex`)

Sets the options from the package `listings` [6] which are used during typesetting of the listing. For  $\text{\LaTeX}$  listings, there is a predefined `listings` style named `tcblatex` which can be used.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!25,left=6mm,
listing options={style=tcblatex,numbers=left,numberstyle=\tiny\color{red!75!black}}}
This is a \LaTeX\ example which displays the text as source code
and in compiled form. Additionally, we use line numbers here.
\end{tcblisting}
```

```
1 This is a \LaTeX\ example which displays the text as source code
2 and in compiled form. Additionally, we use line numbers here.
```

This is a  $\text{\LaTeX}$  example which displays the text as source code and in compiled form. Additionally, we use line numbers here.

`/tcb/no listing options` (no value, initially unset)

Abbreviation for `listing options={}`. This removes all options for the `listings` package. This includes the `tcblisting` standard style `tcblatex` and the encoding presets. Use this option, if you want to set the `listings` options outside of `tcblisting`, e.g. globally in the preamble.

```
\begin{tcblisting}{no listing options}
All \textit{listings} options removed.
\end{tcblisting}
```

```
All \textit{listings} options removed.
```

All *listings* options removed.

`/tcb/listing style=<style>` (no default, initially `tcblatex`)

Abbreviation for `listing options={style=...}`. This key sets a `<style>` for the `listings` package, see [6]. For  $\text{\LaTeX}$ , there is a predefined style named `tcblatex`.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,
listing style=tcblatex}
Here, we use the predefined style.
\end{tcblisting}
```

```
Here, we use the predefined style.
```

Here, we use the predefined style.

`/tcb/listing inputencoding=<encoding>` (no default, initially `\inputencodingname`)

Sets the input encoding value for the predefined listing style `tcblatex` and `tcbdocumentation` from the library `lib documentation`. The initial value is derived from the package `inputenc` if used.

`/tcb/listing remove caption=true|false` (default `true`, initially `true`)

If set to `true`, some part of the caption building code of the `listings` package is silenced to prevent some unwanted interaction with the `hyperref` package resulting in additional vertical space. If set to `false`, the `listings` package code is kept unchanged. Note that listings outside `tcblisting`<sup>→ P. 233</sup> and `\tcbinputlisting`<sup>→ P. 235</sup> are always processed normally. Typically, a user is not expected to use this key at all.

`/tcb/every listing line=<text>` (no default, initially unset/empty)

Inserts some `<text>` to the begin of every line of a listing. Note that this is a hack of the `listings` package code. This may become unusable or superfluous in the future.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
  listing only,listing options={style=tcblatex,language=sh},
  every listing line={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}

\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

`/tcb/every listing line*=<text>` (no default, initially unset/empty)

Identical to `/tcb/every listing line` plus additional enlargement of `/tcb/rightupper`<sup>→ P. 33</sup> by the width of `<text>`. Therefore, this option has to be used after the geometry settings are done. This option is intended to be used in conjunction with `/tcb/hbox`<sup>→ P. 85</sup>.

```
\newtcblisting{commandshell}{colback=black,colupper=white,colframe=yellow!75!black,
  listing only,listing options={style=tcblatex,language=sh},hbox,
  every listing line*={\textcolor{red}{\small\ttfamily\bfseries root \$> }}}

\begin{commandshell}
ls -al
cd /usr/lib
\end{commandshell}
```

```
root $> ls -al
root $> cd /usr/lib
```

See further options in Section 13.6 on page 244.

For an combined example of using `\lstinline` inside a `tcolorbox`, see `\DeclareTotalTCBox`<sup>→ P. 341</sup>.

## 13.4 Option Keys of the `listingsutf8` Library

The `listingsutf8` library is an extension of the `listings` library, so all options from Section 13.3 on page 239 are applicable.

`/tcb/listing utf8=<one-byte-encoding>` (style, no default, initially `latin1`)  
Abbreviation for using `/tcb/listing inputencoding`<sup>→ P. 240</sup> together with UTF-8 support from the package `listingsutf8` [10]. This option is available only for the library variant `listingsutf8`. The `<one-byte-encoding>` is one of the applicable encodings from [10], e. g. `latin1`.

See further options in Section 13.6 on page 244.

### 13.5 Option Keys of the Library

`/tcb/minted language=<programming language>` (no default, initially latex)

Sets a `<programming language>` known to Pygments [12].

```
\begin{tcblisting}{listing engine=minted,minted style=trac,
  minted language=java,
  colback=red!5!white,colframe=red!75!black,listing only}
public class HelloWorld {
  // A 'Hello World' in Java
  public static void main(String[] args) {
    System.out.println("Hello World!");
  }
}
\end{tcblisting}
```

```
public class HelloWorld {
  // A 'Hello World' in Java
  public static void main(String[] args) {
    System.out.println("Hello World!");
  }
}
```

`/tcb/minted options=<key list>` (no default, initially `tabsize=2,fontsize=\small`)

Sets the options from the package `minted` [14] which are used during typesetting of the listing.

```
% \tcbuselibrary{skins}
\newtcblisting{myjava}{listing engine=minted,minted style=colorful,
  minted language=java,minted options={fontsize=\small,linenos,numbersep=3mm},
  colback=blue!5!white,colframe=blue!75!black,listing only,
  left=5mm,enhanced,
  overlay={\begin{tcbclipinterior}\fill[red!20!blue!20!white] (frame.south west)
    rectangle ([xshift=5mm]frame.north west);\end{tcbclipinterior}}}}

\begin{myjava}
public class HelloWorld {
  // A 'Hello World' in Java
  public static void main(String[] args) {
    System.out.println("Hello World!");
  }
}
\end{myjava}
```

```
1 public class HelloWorld {
2   // A 'Hello World' in Java
3   public static void main(String[] args) {
4     System.out.println("Hello World!");
5   }
6 }
```



`/tcb/minted style=<style>` (no default, initially unset)

Sets a `<style>` known to `Pygments` [12]. This is independent from `/tcb/minted options`<sup>→ P. 242</sup>. Note that styles are always applied globally; all following examples will be set in the given `<style>` until a new style is set. Also note that setting `\usemintedstyle{<style>}` only once per document is more economic, if all styles in a document are the same. For examples of different styles, see `/tcb/minted language`<sup>→ P. 242</sup> and `/tcb/minted options`<sup>→ P. 242</sup>.

See further options in Section 13.6 on the following page.

## 13.6 Common Option Keys of all Libraries

For the  $\langle options \rangle$  in `tcblisting`<sup>→ P. 233</sup> respectively `\tcbinputlisting`<sup>→ P. 235</sup> the following `pgf` keys can be applied. The key tree path `/tcb/` is not to be used inside these macros.

`/tcb/listing engine= $\langle engine \rangle$`  (no default)

Sets the  $\langle engine \rangle$  which typesets the listings. Feasible values are

- `listings`, if library `\lib listings` or `\lib listingsutf8` is loaded.
- `minted`, if library `\lib minted` is loaded.

`/tcb/listing file= $\langle file name \rangle$`  (no default, initially `\jobname.listing`)

Sets the  $\langle file name \rangle$  of the file which is used to save listings.

`/tcb/listing and text` (no value, initially set)

Typesets the environment content as listing in the upper part and as compiled text in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

-----  
This is a L<sup>A</sup>T<sub>E</sub>X example.

`/tcb/text and listing` (no value)

Typesets the environment content as compiled text in the upper part and as listing in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text and listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L<sup>A</sup>T<sub>E</sub>X example.

-----  
This is a \LaTeX\ example.

`/tcb/listing only` (no value)

Typesets the environment content as listing.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing only}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

`/tcb/text only` (no value)

Typesets the environment content as compiled text.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text only}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a  $\text{\LaTeX}$  example.

`/tcb/comment=<text>` (no default, initially empty)

Records a comment with  $\langle text \rangle$  as content. The comment is displayed e.g. in conjunction with `/tcb/listing and comment`<sup>P.247</sup> and `/tcb/comment and listing`<sup>P.247</sup>.

```
\begin{tcblisting}{comment={This comment is really only a comment},
colback=red!5!white,colframe=red!75!black}
This is a \textbf{tcolorbox}.
\end{tcblisting}
```

This is a `\textbf{tcolorbox}`.

This is a `tcolorbox`.

N 2014-11-17

`/tcb/comment only` (no value)

Typesets the environment content with the comment text.

```
\begin{tcblisting}{comment only,
comment={This is a comment.},
colback=red!5!white,colframe=red!75!black}
This is a \textbf{tcolorbox}.
\end{tcblisting}
```


This is a comment.

`/tcb/image comment={<options>}{<filename>}` (style, no default, initially unset)

Uses an image denoted by  $\langle filename \rangle$  as *comment* for the listing. The image is included by the standard `\includegraphics` macro with given  $\langle options \rangle$ .

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
image comment={width=2.5cm}{example-image-a.pdf},center lower}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a `\LaTeX` example.




`/tcb/tcbimage comment=<filename>` (style, no default, initially unset)

Uses an image denoted by  $\langle filename \rangle$  as *comment* for the listing. The image is included by the `\tcbincludegraphics`<sup>→ P. 208</sup> macro. The inclusion can be customized by `/tcb/comment style`<sup>→ P. 247</sup>.

The library `\skins` is needed to apply this option.

```
% \tcbuselibrary{skins}
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  righthand width=3cm,lower separated=false,
  tcbimage comment={example-image-a.pdf},
  comment style={size=fbox,colframe=blue,colback=blue!50,sharp corners,
    drop fuzzy shadow}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.




`/tcb/pdf comment=<filename>` (style, default listing file, initially unset)

Uses a PDF file denoted by  $\langle filename \rangle$  as *comment* for the listing. The image is included by `\tcbincludepdf`<sup>→ P. 210</sup> inside a `tcbraaster`<sup>→ P. 223</sup>. The inclusion can be customized by `/tcb/comment style`<sup>→ P. 247</sup>.

The libraries `\skins` and `\raster` are needed to apply this option.

```
% \tcbuselibrary{skins,raster}
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
  righthand width=3cm,lower separated=false,middle=1mm,
  pdf comment={tcolorbox-example.pdf},
  comment style={raster columns=3,graphics pages={1,2,3},
    colframe=blue,drop fuzzy shadow}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



**N 2014-11-14** `/tcb/pdf extension=<extension>` (no default, initially pdf)

Sets the PDF file name extension for `/tcb/pdf comment`<sup>→ P. 246</sup> to `<extension>`. Note that `<extension>` always overwrites any actual extension given inside `/tcb/pdf comment`<sup>→ P. 246</sup>.

**N 2014-11-14** `/tcb/comment style=<options>` (no default, initially empty)

Sets the `<options>` for `/tcb/tcbimage comment`<sup>→ P. 246</sup> and `/tcb/pdf comment`<sup>→ P. 246</sup>. These are `tcolorbox` options to customize the colored box drawn around the image(s), also image options encapsulated by `/tcb/graphics options`<sup>→ P. 211</sup>, and `tcbaster`<sup>→ P. 223</sup> options for `/tcb/pdf comment`<sup>→ P. 246</sup>.

`/tcb/listing and comment` (no value)

Typesets the environment content as listing in the upper part and a given comment in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing and comment,
comment={This is my comment. It may contain line breaks.\par
It can even use the environment content
\flqq\ignorespaces\tcbuselistingtext\unskip\frqq}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is my comment. It may contain line breaks.  
It can even use the environment content «This is a L<sup>A</sup>T<sub>E</sub>X example.»

`/tcb/comment and listing` (no value)

Typesets a given comment in the upper part and the environment content as listing in the lower part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment and listing,
comment={This is my comment.}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is my comment.

This is a \LaTeX\ example.

### `/tcb/listing side text` (no value)

Typesets the environment content side by side as listing in the left (upper) part and as compiled text in the right (lower) part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a L<sup>A</sup>T<sub>E</sub>X example.

### `/tcb/text side listing` (no value)

Typesets the environment content side by side as compiled text in the left (upper) part and as listing in the right (lower) part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text side listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L<sup>A</sup>T<sub>E</sub>X example.

This is a \LaTeX\ example.

### `/tcb/listing outside text` (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and as compiled text outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 4.13, see page 68.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing outside text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a L<sup>A</sup>T<sub>E</sub>X example.

### `/tcb/text outside listing` (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and as compiled text outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 4.13, see page 68.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text outside listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L<sup>A</sup>T<sub>E</sub>X example.


This is a \LaTeX\ example.

### `/tcb/listing side comment` (no value)

Typesets the environment content side by side as listing in the left (upper) part and a given comment in the right (lower) part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing side comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```


This is a \LaTeX\ example.



### `/tcb/comment side listing` (no value)

Typesets the environment content side by side with a given comment in the left (upper) part and as listing in the right (lower) part.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment side listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```



This is a \LaTeX\ example.

### `/tcb/listing outside comment` (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and a given comment outside the box in the right part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 4.13, see page 68.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing outside comment,
  righthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```


This is a \LaTeX\ example.



### `/tcb/comment outside listing` (no value)

Typesets the environment content side by side as listing in a `tcolorbox` and a given comment outside the box in the left part of the page. Nevertheless, the outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The space partitioning is done with the side by side options from Section 4.13, see page 68.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment outside listing,
  lefthand width=1.5cm,image comment={width=1.5cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```



This is a \LaTeX\ example.



`/tcb/listing above text` (no value)

Typesets the environment content as listing in a `tcolorbox` and as compiled text outside and below the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and text is controlled by `/tcb/middle`<sup>→ P. 35</sup>.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing above text}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.

This is a L<sup>A</sup>T<sub>E</sub>X example.

N 2014-11-07

`/tcb/listing above* text` (no value)

Widely equal to `/tcb/listing above text`, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by `/tcb/after`<sup>→ P. 72</sup>.

`/tcb/text above listing` (no value)

Typesets the environment content as listing in a `tcolorbox` and as compiled text outside and above the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and text is controlled by `/tcb/middle`<sup>→ P. 35</sup>.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,text above listing}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a L<sup>A</sup>T<sub>E</sub>X example.

This is a \LaTeX\ example.

N 2014-11-07

`/tcb/text above* listing` (no value)


Widely equal to `/tcb/text above listing`, but the outside text is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and text is controlled by `/tcb/before`<sup>→ P. 72</sup>.

`/tcb/listing above comment` (no value)

Typesets the environment content as listing in a `tcolorbox` and a given comment outside and below the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and comment is controlled by `/tcb/middle` <sup>→ P. 35</sup>.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,listing above comment,
  center lower,image comment={width=3cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```

This is a \LaTeX\ example.



N 2014-11-07


`/tcb/listing above* comment` (no value)

Widely equal to `/tcb/listing above comment`, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by `/tcb/after` <sup>→ P. 72</sup>.

`/tcb/comment above listing` (no value)

Typesets the environment content as listing in a `tcolorbox` and a given comment outside and above the box. The outside text is treated as *lower* part of the `tcolorbox` and can be formatted with all lower part options. The distance between box and comment is controlled by `/tcb/middle` <sup>→ P. 35</sup>.

```
\begin{tcblisting}{colback=red!5!white,colframe=red!75!black,comment above listing,
  center lower,image comment={width=3cm}{example-image-a.pdf}}
This is a \LaTeX\ example.
\end{tcblisting}
```



This is a \LaTeX\ example.

N 2014-11-07

`/tcb/comment above* listing` (no value)

Widely equal to `/tcb/comment above listing`, but the outside comment is not formatted with the lower part options. Also, it is not put into a minipage and it may span several pages. The distance between box and comment is controlled by `/tcb/before` <sup>→ P. 72</sup>.

## 13.7 Option Keys for Processing and Full Document Examples

A complete L<sup>A</sup>T<sub>E</sub>X document including `\documentclass`, `\begin{document}` and `\end{document}` cannot be processed directly by `tcolorbox`. It always has to be compiled separately. There are two methods supported by the package to process and display such a full document example:

- Prepare and compile the example document independent from your main document. The source file and the resulting PDF file can be included into the main document afterwards. This is the most economic way since the example document can be left untouched after the example is complete.
- The other possibility is to compile the example on the fly while the main document is compiled. This way has some charm, because the example can be edited inside the main document. But be aware that the compilation of the example is issued on every run of the main document. Also, there are fewer degrees of freedom how the example is compiled.

For both methods, the resulting example PDF file can be included as a `/tcb/pdf comment`<sup>→ P. 246</sup>.

The following example shows how to apply the first method. There already is a file `tcolorbox-example.tex` and a PDF file `tcolorbox-example.pdf`. Both of them are input partly by the following:

```
% \tcbuselibrary{breakable,skins,raster}
\tcbinputlisting{
  enhanced jigsaw,breakable,pad at break*=2mm,height fixed for=first and middle,
  lower separated=false,
  leftlower=0pt,rightlower=0pt,middle=0pt,
  colframe=red!50!black,colback=yellow!10!white,
  listing and comment,
  listing file={tcolorbox-example},
  listing options=
    {style=tcblatex,texcsstyle=*\color{red!70!black},firstline=20,lastline=85},
  after upper={\par\bigskip\texttt{\ldots}\par},
  pdf comment,
  comment style={drop lifted shadow,graphics pages={1,...,4}},
}
```

```
\documentclass{article}
\usepackage{tikz,lipsum,lmodern}
\usepackage[most]{tcolorbox}

\begin{document}

%-----
\section{Colored boxes}

\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black]
  My box.
\end{tcolorbox}

\begin{tcolorbox}[colback=blue!5!white,colframe=blue!75!black,title=My title]
  My box with my title.
\end{tcolorbox}

\begin{tcolorbox}[colback=green!5!white,colframe=green!75!black]
  Upper part of my box.
```

```

\tcblower
Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!5!white,colframe=yellow!50!black,
colbacktitle=yellow!75!black,title=My title]
I can do this also with a title.
\tcblower
Lower part of my box.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,lowerbox=invisible,
savelowerto=\jobname_ex.tex]
Now, we play hide and seek. Where is the lower part?
\tcblower
I'm invisible until you find me.
\end{tcolorbox}

\begin{tcolorbox}[colback=yellow!10!white,colframe=red!75!black,title=Here I am]
\input{\jobname_ex.tex}
\end{tcolorbox}

\begin{tcolorbox}[enhanced,sharp corners=uphill,
colback=blue!50!white,colframe=blue!25!black,coltext=yellow,
fontupper=\Large\bfseries,arc=6mm,boxrule=2mm,boxsep=5mm,
borderline={0.3mm}{0.3mm}{white}]
Funny settings.
\end{tcolorbox}

\begin{tcolorbox}[enhanced,frame style image=blushade.png,
opacityback=0.75,opacitybacktitle=0.25,
colback=blue!5!white,colframe=blue!75!black,
title=My title]
This box is filled with an external image.\par
Title and interior are made partly transparent to show the image.
\end{tcolorbox}

\begin{tcolorbox}[enhanced,attach boxed title to top
center={yshift=-3mm,yshifttext=-1mm},
colback=blue!5!white,colframe=blue!75!black,colbacktitle=red!80!black,
title=My title,fonttitle=\bfseries,
boxed title style={size=small,colframe=red!50!black} ]
This box uses a \textit{boxed title}. The box of the title can
be formatted independently from the main box.
\end{tcolorbox}

...

```

## 1 Colored boxes

My box.

My title  
My box with my title.

Upper part of my box.  
Lower part of my box.

My title  
I can do this also with a title.  
Lower part of my box.

Now, we play hide and seek. Where is the lower part?

Here I am.  
I'm invisible until you find me.

Punny settings.

My title  
This box is filled with an external image.  
Title and interior are made partly transparent to show the image.

My title  
This box uses a *font* title. The box of the title can be formatted independently from the main box.

1

## 2 B<sup>2</sup>T<sub>E</sub>X-Examples

This is a  $\LaTeX$  example:  
$$\sum_{i=1}^n i = \frac{n(n+1)}{2}.$$
$$\lim_{n \rightarrow \infty} \frac{1}{n} = 0.$$

This is a B<sup>2</sup>T<sub>E</sub>X example:  
$$\sum_{i=1}^n i = \frac{n(n+1)}{2}.$$

Side by side  
This is a  $\LaTeX$  example:  
$$\sum_{i=1}^n i = \frac{n(n+1)}{2}.$$
  
This is a B<sup>2</sup>T<sub>E</sub>X example:  
$$\sum_{i=1}^n i = \frac{n(n+1)}{2}.$$

3 Theorems  
Theorem 3.1: Summation of Numbers  
For all natural number  $n$  it holds:  
$$\sum_{i=1}^n i = \frac{n(n+1)}{2}.$$
  
We have given Theorem 3.1 on page 2.  
3.2 Theorem (Summation of Numbers): For all natural number  $n$  it holds:  
$$\sum_{i=1}^n i = \frac{n(n+1)}{2}.$$

2

## 4 Watermarks

Box with a watermark picture  
Here, you see my nice box with a picture as a watermark. This picture is automatically resized to fit the dimensions of my box. Instead of a picture, some text could be used or arbitrary graphical code. See the documentation for more options.

## 5 Boxes in boxes

Box  
Box inside box  
Box inside box inside box  
And now for something completely different: Boxes!  
This is another box.

## 6 Breakable Boxes

Breakable box  
Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur ut, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.  
Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae,

3

ultrices et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula fegiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultrices tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultrices auctor, pede lorem egestas dui, et conallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultrices non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit.

4

N 2014-11-14 `/tcb/no process` (no default)

Removes all processing commands if set before.

N 2014-11-14 `/tcb/process code=<code>` (no default, initially empty)

Adds `<code>` which is executed during `\tcbinputlisting`<sup>→ P. 235</sup> and `tcblisting`<sup>→ P. 233</sup>. At the time of executing the given `<code>`, the listing is already written to `/tcb/listing file`<sup>→ P. 244</sup>, but the colored box is not constructed yet. Its intended use is to process the listing somehow before displaying. The processing result can be used inside a `/tcb/comment`<sup>→ P. 245</sup>. Several `/tcb/process code` options can be given which are processed in the given order.

To use the further options, the compiler has to be called with the `-shell-escape` permission to authorize potentially dangerous system calls. Be warned that this is a security risk. Anyway, it's more economic to compile examples independent from the main document and to include them as shown in the previous pages.

N 2014-11-14 `/tcb/run system command=<system command>` (style, no default, initially unset)

Runs a `<system command>`, if the document is compiled with the `-shell-escape` permission. The current listing file can be accessed as `\filename@area\filename@base\filename@ext`.

N 2014-11-14 `/tcb/compilable listing` (style, no default)

Sets `/tcb/listing file`<sup>→ P. 244</sup> to `\jobname-listing-<counter>`.

The default `/tcb/listing file`<sup>→ P. 244</sup> setting cannot be used to compile a listing, since the base name equals the `\jobname` and the included PDF files should be unique. Therefore, to use `/tcb/run pdflatex` etc., the `/tcb/listing file`<sup>→ P. 244</sup> has to be set to a unique value. One may use `/tcb/compilable listing` for this purpose.

N 2014-11-14 `/tcb/run pdflatex=<arguments>` (style, no default, initially unset)

Issues a `pdflatex` compilation of the listing with the given `<arguments>`.

- The main document has to be compiled with the `-shell-escape` permission.
- The `/tcb/listing file`<sup>→ P. 244</sup> has to be unique for the listing.
- If the listing has to be compiled twice, add `run pdflatex` two times to the option list.

```
\begin{tcblisting}{enhanced jigsaw,lower separated=false,
  leftlower=Opt,rightlower=Opt,
  colframe=red!50!black,colback=yellow!10!white,
  listing options={style=tcblatex,texcsstyle={\color{red!70!black}}},
  listing and comment,
  pdf comment,
  compilable listing,
  run pdflatex
}
\documentclass{beamer}
\usetheme{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
\begin{block}{Hello World}
\begin{itemize}[<+>-]
\item One
\item Two
\end{itemize}
\end{block}

\begin{alertblock}{Integral}
\begin{equation}
\visible<3->{\int\limits_1^x \frac{1}{t}\,dt}
\visible<4->{= \ln(x).}
\end{equation}
\end{alertblock}
\end{document}
```

```

\end{alertblock}
\end{frame}
\end{document}
\end{tcblisting}

```

```

\documentclass{beamer}
\usetheme{Warsaw}
\begin{document}
\begin{frame}{Beamer example}
\begin{block}{Hello World}
\begin{itemize}[<+>]
\item One
\item Two
\end{itemize}
\end{block}

\begin{alertblock}{Integral}
\begin{equation}
\visible<3->\{\int\limits_1^x \frac{1}{t} dt\}
\visible<4->\{ = \ln(x) \}
\end{equation}
\end{alertblock}
\end{frame}
\end{document}

```

#### Beamer example

Hello World

- One

Integral

(1)

#### Beamer example

Hello World

- One
- Two

Integral

(1)

#### Beamer example

Hello World

- One
- Two

Integral

$$\int_1^x \frac{1}{t} dt$$

(1)

#### Beamer example

Hello World

- One
- Two

Integral

$$\int_1^x \frac{1}{t} dt = \ln(x).$$

(1)



<b>N</b> 2014-11-14	<code>/tcb/run xelatex=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a xelatex compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run lualatex=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a lualatex compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run makeindex=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a makeindex compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run bibtex=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a bibtex compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run biber=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a biber compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run arara=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues an arara compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run latex=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a latex compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run dvips=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a dvips compilation of the listing with the given <arguments>.	
<b>N</b> 2014-11-14	<code>/tcb/run ps2pdf=&lt;arguments&gt;</code>	(style, no default, initially unset)
	Issues a ps2pdf compilation of the listing with the given <arguments>.	

```

\begin{tcblisting}{enhanced jigsaw,
  title={PSTricks with pdflatex},fonttitle=\bfseries,
  colframe=red!50!black,colback=yellow!10!white,
  listing options={style=tcblatex,texcsstyle=*\color{red!70!black}},
  lower separated=false,middle=0pt,
  listing side comment,righthand width=4.5cm,
  compilable listing,
  run latex,run dvips,run ps2pdf,
  pdf comment,
  comment style={raster columns=1,graphics options={viewport=0in 8in 4in 11.5in,clip}},
}
\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01,linecolor=MyColor]{\nHue}}
\end{document}
\end{tcblisting}


```

### PSTricks with pdflatex

```

\documentclass{article}
\usepackage{pstricks,multido}
\begin{document}
\psset{unit=3}%
\multido{\nHue=0.01+0.01}{100}{%
\definecolor{MyColor}{hsb}{\nHue,1,1}%
\pscircle[linewidth=0.01,linecolor=MyColor]{\nHue}}
\end{document}

```



## 13.8 Creation of L<sup>A</sup>T<sub>E</sub>X Tutorials

The following source code gives a guideline for the creation of L<sup>A</sup>T<sub>E</sub>X tutorials. In the next section, a framework for L<sup>A</sup>T<sub>E</sub>X exercises is described. All examples shall be numbered optionally.

Firstly, some additional `tcb` keys are defined for the appearance. For the examples, three environments `texexp`, `texexptitled`, and `texexptitledspec` are defined with automatic numbering.

- `texexp` is used for untitled examles,
- `texexptitled` is used for titled examles,
- `texexptitledspec` is used for titled examles with special treatment.

*Definition in the preamble:*

```
\tcbset{
  texexp/.style={colframe=red!50!yellow!50!black, colback=red!50!yellow!5!white,
    coltitle=red!50!yellow!3!white,
    fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small},
  example/.style 2 args={texexp,
    title={Example \thetcbcounter: #1},label={#2}},
}

\newtcblisting{texexp}[1]{texexp,#1}
\newtcblisting[auto counter,number within=section]{texexptitled}[3][]{%
  example={#2}{#3},#1}
\newcolorbox[use counter from=texexptitled]{texexptitledspec}[3][]{%
  example={#2}{#3},#1}
```

```
\begin{tcblisting}{texexp}
This is a \LaTeX\ example which displays the text as source code
and in compiled form.
\end{tcblisting}
```

This is a \LaTeX\ example which displays the text as source code  
and in compiled form.

This is a L<sup>A</sup>T<sub>E</sub>X example which displays the text as source code and in compiled form.

```
\begin{texexptitled}{First example with a title line}{firstExample}
Here, we use Example \ref{firstExample} with a title line.
\end{texexptitled}
```

**Example 13.1: First example with a title line**

Here, we use Example \ref{firstExample} with a title line.

Here, we use Example 13.1 with a title line.

```
\begin{texexp}{}
```

This is a `\LaTeX` example which displays the text as source code  
and in compiled form.

```
\end{texexp}
```

This is a `\LaTeX` example which displays the text as source code  
and in compiled form.

This is a  $\text{\LaTeX}$  example which displays the text as source code and in compiled form.

```
\begin{texexp}{text and listing}
```

This is a `\LaTeX` example which displays the text as source code  
and in compiled form.

```
\end{texexp}
```

This is a  $\text{\LaTeX}$  example which displays the text as source code and in compiled form.

This is a `\LaTeX` example which displays the text as source code  
and in compiled form.

```
\begin{texexp}{listing only}
```

This is a `\LaTeX` example which displays the text as source code only.

```
\end{texexp}
```

This is a `\LaTeX` example which displays the text as source code only.

```
\begin{texexp}{text only}
```

This is a `\LaTeX` example which displays the text in compiled form only.

```
\end{texexp}
```

This is a  $\text{\LaTeX}$  example which displays the text in compiled form only.

```
\begin{texexptitled}{An Example with a Heading}{heading1}
This is a \LaTeX\ example with a numbered heading line
which can be referred to.
\end{texexptitled}
Here, we see Example \ref{heading1}.
```

#### Example 13.2: An Example with a Heading

This is a \LaTeX\ example with a numbered heading line  
which can be referred to.

---

This is a L<sup>A</sup>T<sub>E</sub>X example with a numbered heading line which can be referred to.

Here, we see Example 13.2.

```
\begin{texexptitled}[listing only]{Another Example with a Heading}{heading2}
The keys can be used in combination. Here, an example with a heading line
and source code only is given.
\end{texexptitled}
Here, we see Example \ref{heading2}.
```

#### Example 13.3: Another Example with a Heading

The keys can be used in combination. Here, an example with a heading line  
and source code only is given.

Here, we see Example 13.3.

```
\begin{texexptitled}[float]{A floating Example with a Heading}{heading3}
This is another \LaTeX\ example with numbered heading line.
But now, the box is a floating object.
\end{texexptitled}
```

#### Example 13.4: A floating Example with a Heading

This is another \LaTeX\ example with numbered heading line.  
But now, the box is a floating object.

---

This is another L<sup>A</sup>T<sub>E</sub>X example with numbered heading line. But now, the box is a floating object.

The floating box of the last example is seen as Example \ref{heading3}  
on page \pageref{heading3}.

The floating box of the last example is seen as Example 13.4 on page 260.

```

\begin{texeptitledspec}{Special application}{texexpbox1}
\begin{lstlisting}[style=tcblatex]
Some \LaTeX\ source code.
\end{lstlisting}
\tcblower

```

For special cases, the environment `texeptitledspec` with style `example` can be used directly. As one can see, the upper and the lower part of the box can be used uncoupled also.

```

\end{texeptitledspec}

```

#### Example 13.5: Special application

Some `\LaTeX` source code.

For special cases, the environment `texeptitledspec` with style `example` can be used directly. As one can see, the upper and the lower part of the box can be used uncoupled also.

The following series of examples demonstrate the application of `tcolorbox`<sup>→P.11</sup> options for diversification.

```

\begin{texeptitled}{How to use options (1):\par The basic example}{options1}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texeptitled}


```

#### Example 13.6: How to use options (1): The basic example

```

\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}

```



```

\begin{texexptitled}[center lower,enhanced,segmentation hidden,middle=0mm]
  {How to use options (2):\par The text output is centered and the
    segmentation line has vanished.}{options2}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}

```


#### Example 13.7: How to use options (2):

The text output is centered and the segmentation line has vanished.

```

\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{tikzpicture}

```



```

\begin{texexptitled}[tikz lower,bicolor,colbacklower=white]
  {How to use options (3):\par Here, the |tikzpicture| is totally hidden.
    The |bicolor| skin highlights the output.}{options3}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}
\end{texexptitled}

```


#### Example 13.8: How to use options (3):

Here, the tikzpicture is totally hidden. The bicolor skin highlights the output.

```

\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c] (\w:1cm) circle (7mm);}

```



```

\begin{texexptitled}[center lower,listing side text,righthand width=3.5cm,
  bicolor,colbacklower=white]
{How to use options (4):\par The |bicolor| skin also works with side
  by side mode}{options4}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
  (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}


```

**Example 13.9: How to use options (4):**  
**The bicolor skin also works with side by side mode**

```

\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
  (\w:1cm) circle (7mm);}
\end{tikzpicture}

```



```

\begin{texexptitled}[center lower,listing outside text,righthand width=3.5cm]
{How to use options (5):\par Putting our picture outside is just
  a matter of one word.}{options5}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
  (\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}


```

**Example 13.10: How to use options (5):**  
**Putting our picture outside is just a matter of one word.**

```

\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
  (\w:1cm) circle (7mm);}
\end{tikzpicture}

```






```

\begin{texexptitled}[center lower,text above listing]
{How to use options (6):\par The picture may also be put above
the listing box.}{options6}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}

```



**Example 13.11: How to use options (6):**  
The picture may also be put above the listing box.

```


\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}

```

```

\begin{texexptitled}[beamer,center lower,text outside listing,lefthand width=3.5cm]
{How to use options (7):\par Our style is easily transformed into
a beamerish one.}{options7}
\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}
\end{texexptitled}

```



**Example 13.12: How to use options (7):**  
Our style is easily transformed into a beamerish one.

```

\begin{tikzpicture}
\path[fill=yellow!50!white] (0,0) circle (11mm);
\path[fill=white] (0,0) circle (9mm);
\foreach \w/\c in {90/red,210/green,330/blue}
{\path[shading=ball,ball color=\c]
(\w:1cm) circle (7mm);}
\end{tikzpicture}

```

### 13.9 Creation of L<sup>A</sup>T<sub>E</sub>X Exercises

In the following, a guideline is given for the creation of L<sup>A</sup>T<sub>E</sub>X exercises with solutions. These solutions are saved to disk for application at a place of choice. Therefore, all used exercises are logged to a file `\jobname.records` for automatic processing. The solution contents themselves are saved to a subdirectory named `solutions`. Also see Section 7 on page 99.

- Before the first exercise is given, `\tcbstartrecording`<sup>→ P. 99</sup> has to be called to start recording.
- The solution is given as content of a `tcboutputlisting`<sup>→ P. 235</sup> environment. Note, that you can use this content also inside the exercise with `\tcbuselistingtext`<sup>→ P. 235</sup> in compiled form.
- After the last exercise is given (and before using the solutions), `\tcbstoprecording`<sup>→ P. 99</sup> has to be called to stop recording.
- The solutions are loaded by `\tcbinputrecords`<sup>→ P. 99</sup>.

Inside the exercise text, there may be text parts which are needed as L<sup>A</sup>T<sub>E</sub>X source code and as compiled text as well. These parts can be saved by `tcbwritetemp`<sup>→ P. 98</sup> and used in compiled form by `\tcbusetemp`<sup>→ P. 98</sup> or as source code by `\tcbusetemplisting`<sup>→ P. 235</sup>.

At first, we generate some a common style for the exercises and the solutions. Further, since exercises and solutions should be numbered, we force to use a label `<marker>`. Automatically, the label `exe:<marker>` is used to mark the exercise and the label `sol:<marker>` is used to mark the solution.

```
\tcbset{texercisestyle/.style={arc=0.5mm, colframe=blue!25!yellow!90!white,
colback=blue!25!yellow!5!white, coltitle=blue!25!yellow!40!black,
fonttitle=\small\sffamily\bfseries, fontupper=\small, fontlower=\small,
listing options={style=tcblatex, texcsstyle=\color{red!40!black}}},
}}
```

With these preparations, the kernel environment `texercise` for our exercises is created quickly:

*Definition in the preamble:*

```
\newcolorbox[auto counter,number within=section,list inside=exam]{texercise}[2][]{%
texercisestyle,
listing file={solutions/texercise\thetcbcounter.tex},
label={exe:#2},
record={\string\processsol{solutions/texercise\thetcbcounter.tex}{#2}},
title={Exercise \thetcbcounter\hfill\mdseries Solution on page \pageref{sol:#2}},
list text={Exercise with solution on page \pageref{sol:#2}},#1}
```

The following examples demonstrate the application.

`\tcbstartrecording`

```
\begin{texercise}{tabular_example}
\textit{Create the following table:}\par\smallskip%
\begin{tcboutputlisting}
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries\itshape Das alte Italien}\hline
\multicolumn{2}{|c|}{\bfseries Antike} & 
\multicolumn{2}{c|}{\bfseries Mittelalter}\hline
\multicolumn{1}{|c|}{\itshape Republik}& 
\multicolumn{1}{c|}{\itshape Kaiserreich}& 
\multicolumn{1}{c|}{\itshape Franken}& 
\multicolumn{1}{c|}{\itshape Teilstaaten}\hline
In den Zeiten der r"\{o}mischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. & 
Das r"\{o}mische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser,
regiert.
& In der V"\{o}lkerwanderungszeit "\{u}bernahmen die Goten und sp"\{a}ter die
Franken die Vorherrschaft.
& Im sp"\{a}teren Mittelalter regierten F"\{u}rsten einen Fleckenteppich
von Einzelstaaten.\hline
\end{tabular}
\end{tcboutputlisting}
\tcbuselistingtext%
\end{texercise}
```

### Exercise 13.1

Solution on page 269

Create the following table:

<i>Das alte Italien</i>			
<b>Antike</b>		<b>Mittelalter</b>	
<i>Republik</i>	<i>Kaiserreich</i>	<i>Franken</i>	<i>Teilstaaten</i>
In den Zeiten der römischen Republik standen dem Staat jeweils zwei Konsuln vor, deren Machtbefugnisse identisch waren.	Das römische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser, regiert.	In der Völkerwanderungszeit übernahmen die Goten und später die Franken die Vorherrschaft.	Im späteren Mittelalter regierten Fürsten einen Fleckenteppich von Einzelstaaten.

```

\begin{texercise}{macro_oneparam}
\begin{tcboutputlisting}
\newcommand{\headingline}[1]{%
  \begin{center}\Large\bfseries #1\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%

```

Create a new macro `\verb+\headingline+` which produces the following output: `\par\smallskip`

```

\begin{tcbwritetemp}
\headingline{Very important heading}
\end{tcbwritetemp}
\tcbusetemplisting\tcbusetemp%
\end{texercise}

```

### Exercise 13.2

Solution on page 269

Create a new macro `\headingline` which produces the following output:

```
\headingline{Very important heading}
```

**Very important heading**

```

\begin{texercise}{macro_twoparam}
\begin{tcboutputlisting}
\newcommand{\minitable}[2]{%
  \begin{center}\begin{tabular}{p{10cm}}\hline%
    \multicolumn{1}{c}{\bfseries#1}\hline%
    #2\hline%
  \end{tabular}\end{center}}
\end{tcboutputlisting}
\tcbuselistingtext%

```

Create a new macro `\verb+\minitable+` which produces the following output: `\par\smallskip`

```

\begin{tcbwritetemp}
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
\end{tcbwritetemp}
\tcbusetemplisting\par\smallskip\tcbusetemp%
\end{texercise}

```

### Exercise 13.3

Solution on page 269

Create a new macro `\minitable` which produces the following output:

```
\minitable{My heading}{In this tiny tabular, there is only a heading
  and some text below which has a width of ten centimeters.}
```

**My heading**

In this tiny tabular, there is only a heading and some text below  
which has a width of ten centimeters.

```

\begin{texercise}{macro_threeparam}
\begin{tcboutputlisting}
\newcommand{\synop}[3]{%
  \begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
    p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
    \multicolumn{2}{c}{\bfseries #1}\\ \hline
    \multicolumn{1}{c|}{\itshape English}&
    \multicolumn{1}{c}{\itshape German}\\ \hline
    #2 & #3
  \end{tabular}}
\end{tcboutputlisting}
\tcbuselistingtext%
Create a new macro \verb+\synop+ which typesets a synoptic text according
to the following example. Base your macro on a tabular which takes the
total line width. \par\smallskip
\begin{tcbwritetemp}
\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"{u}r einen Mann,
  ein riesiger Sprung f\"{u}r die Menschheit.}
\end{tcbwritetemp}
\tcbusetemplisting\par\smallskip\tcbusetemp%
\end{texercise}

```

#### Exercise 13.4

Solution on page 270

Create a new macro `\synop` which typesets a synoptic text according to the following example. Base your macro on a tabular which takes the total line width.

```

\synop{Neil Armstrong}%
{That's one small step for a man, one giant leap for mankind.}%
{Das ist ein kleiner Schritt f\"{u}r einen Mann,
  ein riesiger Sprung f\"{u}r die Menschheit.}

```

Neil Armstrong	
<i>English</i>	<i>German</i>
That's one small step for a man, one giant leap for mankind.	Das ist ein kleiner Schritt für einen Mann, ein riesiger Sprung für die Menschheit.

```
\tcbstoprecording
```

Now, we give a list of all exercises with:

```

\tcblistof[\subsection]{exam}{List of Exercises%
  \label{listofexercises}}

```

## 13.10 List of Exercises

13.1 Exercise with solution on page 269	266
13.2 Exercise with solution on page 269	267
13.3 Exercise with solution on page 269	267
13.4 Exercise with solution on page 270	268

## 13.11 Solutions for the given L<sup>A</sup>T<sub>E</sub>X Exercises

For all solutions, a macro `\processsol` was written to the file `\jobname.records`. Now, we need a definition for this macro to use the solutions.

```
% \usepackage{hyperref} % for phantomlabel
\newtcbinputlisting{\processsol}[2]{%
  exercisestyle,
  listing only,
  listing file={#1},
  phantomlabel={sol:#2},%
  title={Solution for Exercise \ref{exe:#2} on page \pageref{exe:#2}},
}
```

The loading of all solutions is done by:

```
\tcbinputrecords
```

With this, we get:

### Solution for Exercise 13.1 on page 266

```
\begin{tabular}{|p{3cm}|p{3cm}|p{3cm}|p{3cm}|}\hline
\multicolumn{4}{|c|}{\bfseries\itshape Das alte Italien}\hline
\multicolumn{2}{|c|}{\bfseries Antike} &
\multicolumn{2}{|c|}{\bfseries Mittelalter}\hline
\multicolumn{1}{|c|}{\itshape Republik}&
\multicolumn{1}{|c|}{\itshape Kaiserreich}&
\multicolumn{1}{|c|}{\itshape Franken}&
\multicolumn{1}{|c|}{\itshape Teilstaaten}\hline
In den Zeiten der r\{"o}mischen Republik standen dem Staat jeweils zwei
Konsuln vor, deren Machtbefugnisse identisch waren. &
Das r\{"o}mische Kaiserreich wurde von einem Alleinherrscher, dem Kaiser,
regiert.
& In der V\{"o}lkerwanderungszeit \{"u}bernahmen die Goten und sp\{a}ter die
Franken die Vorherrschaft.
& Im sp\{a}teren Mittelalter regierten F\{"u}rsten einen Fleckenteppich
von Einzelstaaten.\hline
\end{tabular}
```

### Solution for Exercise 13.2 on page 267

```
\newcommand{\headingline}[1]{%
  \begin{center}\Large\bfseries #1\end{center}}
```

### Solution for Exercise 13.3 on page 267

```
\newcommand{\minitable}[2]{%
  \begin{center}\begin{tabular}{p{10cm}}\hline%
  \multicolumn{1}{c}{\bfseries#1}\hline%
  #2\hline%
  \end{tabular}\end{center}}
```

```

\newcommand{\synop}[3]{%
  \begin{tabular}{@{}p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}|%
    p{(\linewidth-\tabcolsep*2-\arrayrulewidth)/2}@{}}\hline
    \multicolumn{2}{c}{\bfseries #1}\\ \hline
    \multicolumn{1}{c|}{\itshape English}&
    \multicolumn{1}{c}{\itshape German}\\ \hline
    #2 & #3
  \end{tabular}}

```



## 14 Library lib **theorems**

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{theorems}
```

This also loads the package `amsmath`.

### 14.1 Macros of the Library

**\newtcbtheorem**[*<init options>*]{*<name>*}{*<display name>*}{*<options>*}{*<prefix>*}

Creates new environments *<name>* and *<name>\** based on `tcolorbox` to frame a (mathematical) theorem. The *<display name>* is used in the title line with a number, e.g. «Theorem 5.1». The *<options>* are given to the underlying `tcolorbox` to control the appearance. The *<init options>* allow setting up automatic numbering, see Section 5 on page 92. The new environment *<name>* takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and the second mandatory parameter is a *<marker>*. The theorem is automatically labeled with *<prefix>*:*<marker>*. The new environment *<name>\** takes one optional and one mandatory parameter and represents an unnumbered variant of the environment *<name>*. This variant is not labeled and not listed in lists of theorems.

*Definition in the preamble:*

```
\newtcbtheorem[number within=section]{mytheo}{My Theorem}%  
{colback=green!5,colframe=green!35!black,fonttitle=\bfseries}{th}
```

```
\begin{mytheo}{This is my title}{theoexample}  
This is the text of the theorem. The counter is automatically assigned and,  
in this example, prefixed with the section number. This theorem is numbered with  
\ref{th:theoexample} and is given on page \pageref{th:theoexample}.  
\end{mytheo}
```

**My Theorem 14.1: This is my title**

This is the text of the theorem. The counter is automatically assigned and, in this example, prefixed with the section number. This theorem is numbered with 14.1 and is given on page 271.

```
\begin{mytheo}[label=myownlabel]{This is my title}{}  
The label parameter can be left empty without \LaTeX error.  
Or you may use an own label to reference Theorem \ref{myownlabel}.  
\end{mytheo}
```

**My Theorem 14.2: This is my title**

The label parameter can be left empty without  $\LaTeX$  error. Or you may use an own label to reference Theorem 14.2.

```
\begin{mytheo}{}{}
  The title can also be left empty without problem. Note that the ':'
  vanished magically.
\end{mytheo}
```

### My Theorem 14.3

The title can also be left empty without problem. Note that the ':' vanished magically.

```
\begin{mytheo*}{Unnumbered Theorem}
  This theorem is not numbered.
\end{mytheo*}
```

### My Theorem: Unnumbered Theorem

This theorem is not numbered.

```
\begin{mytheo*}{}{}
  This theorem has no number and no title.
\end{mytheo*}
```

### My Theorem

This theorem has no number and no title.

**`\renewtcbtheorem`**[*`<init options>`*]{*`<name>`*}{*`<display name>`*}{*`<options>`*}{*`<prefix>`*}

Operates like `\newtcbtheorem`<sup>P. 271</sup>, but based on `\renewenvironment` instead of `\newenvironment`. An existing environment is redefined.

**`\tcbmaketheorem`**{*`<name>`*}{*`<display name>`*}{*`<options>`*}{*`<counter>`*}{*`<prefix>`*}

`\newtcbtheorem`<sup>P. 271</sup> supersedes this macro.

Creates a new environment *`<name>`* based on `tcolorbox` to frame a (mathematical) theorem. The *`<display name>`* is used in the title line with a number, e.g. «Theorem 5.1». The *`<options>`* are given to the underlying `tcolorbox` to control the appearance. The *`<counter>`* is used for automatic numbering. The new environment *`<name>`* takes one optional and two mandatory parameters. The optional parameter supplements the options and should be used only in rare cases. The first mandatory parameter is the title text for the theorem and the second mandatory parameter is a *`<marker>`*. The theorem is automatically labeled with *`<prefix>`*:*`<marker>`*.

`\tcboxmath[⟨options⟩]{⟨mathematical box content⟩}`

Creates a `\tcboxmath`<sup>P.11</sup> which is fitted to the width of the given *⟨mathematical box content⟩*. This box is intended to be applied as part of a larger formula and may be used as replacement for the `\boxed` macro of `amsmath`.

```
\begin{equation}
\tcbset{fonttitle=\scriptsize}
\tcbboxmath[colback=LightBlue!25!white,colframe=blue]{ a^2 = 16 }
\quad \Rightarrow \quad
\tcbboxmath[colback=Salmon!25!white,colframe=red,title=Implication]{
  { a = 4 ~\vee~ a=-4. }
}
\end{equation}
```

$$\boxed{a^2 = 16} \Rightarrow \boxed{\text{Implication} \quad a = 4 \vee a = -4.} \quad (3)$$

`\tcbhighmath[⟨options⟩]{⟨mathematical box content⟩}`

This is a special case of the `\tcboxmath` macro which uses the style `/tcb/highlight math`<sup>P.280</sup>. It is intended to provide context sensitive highlighting of formula parts. The color settings via `/tcb/highlight math style`<sup>P.280</sup> may be different inside theorems or other colored areas and outside.

```
\tcbset{myformula/.style={colback=yellow!10!white,colframe=red!50!black,
every box/.style={highlight math style={colback=LightBlue!50!white,colframe=Navy}}}

\begin{align}
\tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} &= \infty. \\
\int x^2 \, dx &= \frac{1}{3} x^3 + c.
\end{align}

\begin{tcolorbox}[ams align,myformula]
\tcbhighmath{\sum\limits_{n=1}^{\infty} \frac{1}{n}} &= \infty. \\
\int x^2 \, dx &= \frac{1}{3} x^3 + c.
\end{tcolorbox}
```

$$\boxed{\sum_{n=1}^{\infty} \frac{1}{n}} = \infty. \quad (4)$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c. \quad (5)$$

$$\boxed{\sum_{n=1}^{\infty} \frac{1}{n}} = \infty. \quad (6)$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c. \quad (7)$$

`\tcbhighmath`<sup>→ P. 273</sup> can be used in symbiosis with the `empheq` package which allows to specify own boxing commands to mark multiline formulas.

```
% \usepackage{empheq}
\begin{empheq}[box=\tcbhighmath]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}

\tcbset{highlight math style={enhanced,
colframe=red!60!black,colback=yellow!50!white,arc=4pt,boxrule=1pt,
drop fuzzy shadow}}

\begin{empheq}[box=\tcbhighmath]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}
```

$$a = \sin(z) \tag{8}$$

$$E = mc^2 + \int_a^b x \, dx \tag{9}$$

$$a = \sin(z) \tag{10}$$

$$E = mc^2 + \int_a^b x \, dx \tag{11}$$

Besides `\tcbhighmath`<sup>→ P. 273</sup>, one can easily define an independent new box based on `\tcbox`<sup>→ P. 13</sup> which acts like `\tcbhighmath`<sup>→ P. 273</sup>:

```
% \usepackage{empheq}
\newtcbox{\otherbox}[1][\nobeforeafter,math upper,tcbbox raise base,
enhanced,frame hidden,boxrule=0pt,interior style={top color=green!10!white,
bottom color=green!10!white,middle color=green!50!yellow},
fuzzy halo=1pt with green,#1]

\begin{empheq}[box=\otherbox]{align}
a&=\sin(z)\\
E&=mc^2 + \int_a^b x\, dx
\end{empheq}

\begin{equation}
\tcbhighmath{E} = \otherbox{mc^2}
\end{equation}
```

$$a = \sin(z) \tag{12}$$

$$E = mc^2 + \int_a^b x \, dx \tag{13}$$

$$E = mc^2 \tag{14}$$

## 14.2 Option Keys of the Library

`/tcb/separator sign= $\langle sign \rangle$`  (no default, initially :)

The given  $\langle sign \rangle$  is used inside the title text of a theorem as separator between display name combined with number and the specific title text. It is omitted, if there is no specific title text.

```
% \usepackage{amssymb}
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 separator sign={\ $\blacktriangleright$}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.4  $\blacktriangleright$  My example**

My theorem text.

`/tcb/separator sign colon` (style, no value, initially set)

Sets `/tcb/separator sign` to the default colon : sign.

`/tcb/separator sign dash` (style, no value)

Sets `/tcb/separator sign` to an en-dash sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 separator sign dash}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.5 – My example**

My theorem text.

`/tcb/separator sign none` (style, no value)

Sets `/tcb/separator sign` to empty.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
 separator sign none}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.6 My example**

My theorem text.

`/tcb/description delimiters={\langle left\rangle}{\langle right\rangle}` (no default, initially empty)

The given  $\langle left \rangle$  and  $\langle right \rangle$  delimiter signs are used to frame the descriptive title text of a theorem.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
description delimiters={\flqq}{\frqq}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.7: «My example»**

My theorem text.

`/tcb/description delimiters parenthesis` (style, no value)

Sets `/tcb/description delimiters` to ( and ).

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
description delimiters parenthesis}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.8: (My example)**

My theorem text.

`/tcb/description delimiters none` (style, no value, initially set)

Sets `/tcb/description delimiters` to the default empty texts.

`/tcb/description color=\langle color\rangle` (default empty, initially empty)

Sets the  $\langle color \rangle$  of the descriptive title text deviating from `/tcb/coltitle`<sup>→ P. 26</sup>. The color is reset to `/tcb/coltitle`<sup>→ P. 26</sup>, if `description color` is used without value.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
description color=red!25!yellow}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.9: My example**

My theorem text.

`/tcb/description font=<text>` (default empty, initially empty)

Sets  $\langle text \rangle$  (e.g. font settings) before the descriptive title text deviating from `/tcb/fonttitle`<sup>P.27</sup>. The  $\langle text \rangle$  is removed, if `description font` is used without value.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
description delimiters={\glqq}{\grqq},
description font=\mdseries\itshape}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.10:** „My example“

My theorem text.

`/tcb/description formatter=<macro>` (default empty, initially empty)

Sets  $\langle macro \rangle$  as formatter for the descriptive title text. The  $\langle macro \rangle$  has to take one mandatory argument (the description text).

Note that `/tcb/description delimiters`<sup>P.276</sup>, `/tcb/description color`<sup>P.276</sup>, and `/tcb/description font` are ignored, if this option is used.

If `description formatter` is used without value, the formatter is reset to its standard behavior.

```
\newtcbbox{\formbox}{enhanced,frame empty,size=minimal,boxsep=2pt,arc=1pt,
on line,interior style image=goldshade.png}

\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
description formatter=\formbox}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.11:** My example

My theorem text.

`/tcb/terminator sign=<sign>` (no default, initially empty)

The given  $\langle sign \rangle$  is used as terminator at the end of the title text of a theorem.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
terminator sign={.}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem 14.12:** My example.

My theorem text.



`/tcb/terminator sign colon` (style, no value, initially set)

Sets `/tcb/terminator sign` <sup>→ P. 277</sup> to the colon : sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%  
  {colback=white,colframe=red!50!black,fonttttitle=\bfseries,  
    separator sign dash,terminator sign colon}{theo}  
\begin{sometheorem}{My example}{}  
My theorem text.  
\end{sometheorem}
```

**Theorem 14.13 – My example:**

My theorem text.

`/tcb/terminator sign dash` (style, no value)

Sets `/tcb/terminator sign` <sup>→ P. 277</sup> to an en-dash sign.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%  
  {colback=white,colframe=red!50!black,fonttttitle=\bfseries,  
    terminator sign dash}{theo}  
\begin{sometheorem}{My example}{}  
My theorem text.  
\end{sometheorem}
```

**Theorem 14.14: My example –**

My theorem text.

`/tcb/terminator sign none` (style, no value)

Sets `/tcb/terminator sign` <sup>→ P. 277</sup> to the default empty text.

`/tcb/theorem name and number` (style, no value, initially set)

Prints theorem name followed by theorem number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%  
  {colback=white,colframe=red!50!black,fonttttitle=\bfseries,  
    theorem name and number}{theo}  
\begin{sometheorem}{My example}{}  
My theorem text.  
\end{sometheorem}
```

**Theorem 14.15: My example**

My theorem text.

`/tcb/theorem number and name` (style, no value)

Prints theorem number followed by theorem name inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
theorem number and name}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**14.16 Theorem: My example**

My theorem text.

`/tcb/theorem name` (style, no value)

Prints theorem name without number inside the title.

```
\newtcbtheorem[use counter from=mytheo]{sometheorem}{Theorem}%
{colback=white,colframe=red!50!black,fonttitle=\bfseries,
theorem name,enhanced,watermark text={\thetcbcounter}}{theo}
\begin{sometheorem}{My example}{}
My theorem text.
\end{sometheorem}
```

**Theorem: My example**

My theorem text.

14.17

`/tcb/theorem={\langle display name \rangle}{\langle counter \rangle}{\langle title \rangle}{\langle marker \rangle}` (no default)

This key is internally used by `\tcbmaketheorem`<sup>→ P. 272</sup>, but can be used directly in a `tcolorbox` for a more flexible approach. The `\langle display name \rangle` is used together with the increased `\langle counter \rangle` value and the `\langle title \rangle` for the title line of the box. Additionally, a `\label` with the given `\langle marker \rangle` is created.

```
% \newcounter{texercise}% preamble
\begin{tcolorbox}[colback=green!10,colframe=green!50!black,arc=4mm,
theorem={Test}{texercise}{Direct usage}{myMarker}]
Here, we see the test \ref{myMarker}.
\end{tcolorbox}
```

**Test 1: Direct usage**

Here, we see the test 1.

For a common appearance inside the document, the key `theorem` should not be used directly as in the example above, but as part of a new environment created by hand or using `\tcbmaketheorem`<sup>→ P. 272</sup> or using its successor `\newtcbtheorem`<sup>→ P. 271</sup>.

`/tcb/highlight math` (style, no value)

Predefined style which is used for `\tcbhighmath`<sup>P.273</sup>. It can be changed comfortably with `/tcb/highlight math style`.

`/tcb/highlight math style=<style definition>` (style, no default)

Changes the definition for `/tcb/highlight math` to the given `<style definition>`. See `\tcbhighmath`<sup>P.273</sup> for another example.

```
% \tcbuselibrary{skins}
\tcbset{highlight math style={enhanced,%<-- needed for the 'remember' options
colframe=red,colback=red!10!white,boxsep=0pt}}
\begin{align*}
\tcbhighmath[remember as=fx]{f(x)}
&= \int\limits_{-1}^x \frac{1}{t^2} dt \\
&= \left[ -\frac{1}{t} \right]_{-1}^x \\
&= -\frac{1}{x} + \frac{1}{1} \\
&= 1 - \frac{1}{x}
\tcbhighmath[remember,overlay={%
\draw[blue,very thick,->] (fx.south) to[bend right] ([yshift=2mm]frame.west);}]
{1-\frac{1}{x}.}
\end{align*}
```

$$\begin{aligned}
 f(x) &= \int_{-1}^x \frac{1}{t^2} dt = \left[ -\frac{1}{t} \right]_{-1}^x \\
 &= -\frac{1}{x} + \frac{1}{1} \\
 &= 1 - \frac{1}{x}
 \end{aligned}$$

`/tcb/math upper` (style, no value)

Sets the upper part to mathematical mode with font `\displaystyle`.

`/tcb/math lower` (style, no value)

Sets the lower part to mathematical mode with font `\displaystyle`.

`/tcb/math` (style, no value)

Sets the upper part *and* lower part to mathematical mode with font `\displaystyle`.

```
\begin{tcolorbox}[math,colback=yellow!10!white,colframe=red!50!black]
\sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

The following styles are only tested to work with the original `amsmath` environments. If e.g. the `equation` environment is redefined as `gather`, then `/tcb/ams equation` should / could not be used. Obviously, you are encouraged to use `/tcb/ams gather`<sup>→ P. 283</sup> in this case.

**U** 2014-10-30 `/tcb/ams equation upper` (style, no value)

Adds an `amsmath equation` environment to the start and end of the upper part.

**U** 2014-10-30 `/tcb/ams equation lower` (style, no value)

Adds an `amsmath equation` environment to the start and end of the lower part.

**U** 2014-10-30 `/tcb/ams equation` (style, no value)

Adds an `amsmath equation` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation,colback=yellow!10!white,colframe=red!50!black]
\sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (15)$$

**U** 2014-10-30 `/tcb/ams equation* upper` (style, no value)

Adds an `amsmath equation*` environment to the start and end of the upper part.

**U** 2014-10-30 `/tcb/ams equation* lower` (style, no value)

Adds an `amsmath equation*` environment to the start and end of the lower part.

**U** 2014-10-30 `/tcb/ams equation*` (style, no value)

Adds an `amsmath equation*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams equation*,colback=yellow!10!white,colframe=red!50!black]
\sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

`/tcb/ams align upper` (style, no value)

Adds an `amsmath align` environment to the start and end of the upper part.

`/tcb/ams align lower` (style, no value)

Adds an `amsmath align` environment to the start and end of the lower part.

`/tcb/ams align` (style, no value)

Adds an `amsmath align` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 \, dx = \frac{1}{3} x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (16)$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c. \quad (17)$$

`/tcb/ams align* upper` (style, no value)

Adds an `amsmath align*` environment to the start and end of the upper part.

`/tcb/ams align* lower` (style, no value)

Adds an `amsmath align*` environment to the start and end of the lower part.

`/tcb/ams align*` (style, no value)

Adds an `amsmath align*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams align*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 \, dx = \frac{1}{3} x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c.$$

`/tcb/ams gather upper` (style, no value)

Adds an `amsmath gather` environment to the start and end of the upper part.

`/tcb/ams gather lower` (style, no value)

Adds an `amsmath gather` environment to the start and end of the lower part.

`/tcb/ams gather` (style, no value)

Adds an `amsmath gather` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams gather,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 \, dx = \frac{1}{3} x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (18)$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c. \quad (19)$$

`/tcb/ams gather* upper` (style, no value)

Adds an `amsmath gather*` environment to the start and end of the upper part.

`/tcb/ams gather* lower` (style, no value)

Adds an `amsmath gather*` environment to the start and end of the lower part.

`/tcb/ams gather*` (style, no value)

Adds an `amsmath gather*` environment to the start and end of the upper *and* lower part.

```
\begin{tcolorbox}[ams gather*,colback=yellow!10!white,colframe=red!50!black]
  \sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
  \int x^2 \, dx = \frac{1}{3} x^3 + c.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c.$$

`/tcb/ams nodisplayskip upper` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part. Note that the text content has to start with such a formula.

`/tcb/ams nodisplayskip lower` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the lower part. Note that the text content has to start with such a formula.

`/tcb/ams nodisplayskip` (style, no value)

Neutralizes the `\abovedisplayskip` of a following `align` or `gather` environment for the upper part *and* lower part. Note that the text content has to start with such a formula.

```
\begin{tcolorbox}[ams nodisplayskip,colback=yellow!10!white,colframe=red!50!black]
\begin{gather}
\sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
\int x^2 \sim \text{d}x = \frac{1}{3} x^3 + c.
\end{gather}
And now for something completely different.
\end{tcolorbox}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (20)$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c. \quad (21)$$

And now for something completely different.

New colored mathematical environments are easily created using `\newtcolorbox`<sup>→ P. 14</sup>:

```
\newtcolorbox{mymath}{ams gather*,colback=yellow!10!white,colframe=red!50!black}

\begin{mymath}
\sum\limits_{n=1}^{\infty} \frac{1}{n} = \infty.\\
\int x^2 \sim \text{d}x = \frac{1}{3} x^3 + c.
\end{mymath}
```

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty.$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c.$$

All described options like `/tcb/ams gather upper`<sup>→ P. 283</sup>, `/tcb/ams gather lower`<sup>→ P. 283</sup>, `/tcb/ams gather`<sup>→ P. 283</sup> are (partially) setting (overwriting) the keys `/tcb/before upper`<sup>→ P. 52</sup>, `/tcb/after upper`<sup>→ P. 53</sup>, `/tcb/before lower`<sup>→ P. 53</sup>, `/tcb/after lower`<sup>→ P. 53</sup>.

Therefore, e.g. `\tcbset{ams gather,before upper={\text{Pythagoras:}}}` produces an invalid result. For this case, you are invited to use

`\tcbset{ams gather,before upper app={\text{Pythagoras:}}}`,  
see `/tcb/before upper app`<sup>→ P. 326</sup>.



`/tcb/theorem style=<name>` (no default, initially `standard`)

Applies a predefined style `<name>` to the theorem environment. Some of the feasible `<name>` values resemble style names from the packages `theorem` and `ntheorem` to give convenient access to known patterns.

The styles alter `/tcb/separator sign`<sup>→P.275</sup>, `/tcb/description delimiters`<sup>→P.276</sup>, `/tcb/terminator sign`<sup>→P.277</sup>, and more. Therefore, one should apply such keys *after* a theorem style.

For the following examples, we use:

*Definition in the preamble:*

```
\newtcbtheorem[use counter from=mytheo]{theorem}{Theorem}{%
  fonttitle=\bfseries\upshape,fontupper=\itshape,
  colframe=green!50!black,colback=green!10!white,
  colbacktitle=green!20!white,coltitle=blue!75!black}{theo}
```

The predefined styles are:

- `standard`: This is the initial value.

```
\begin{theorem}[theorem style=standard]{standard}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**Theorem 14.18: standard**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

- `change standard`

```
\begin{theorem}[theorem style=change standard]{change standard}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**14.19 Theorem: change standard**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

- `plain`

```
\begin{theorem}[theorem style=plain]{plain}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**Theorem 14.20 (plain):** *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **break**

```
\begin{theorem}[theorem style=break]{break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**Theorem 14.21 (break):**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **plain apart**

```
\begin{theorem}[theorem style=plain apart]{plain apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**Theorem 14.22 (plain apart)**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **change**

```
\begin{theorem}[theorem style=change]{change}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**14.23 Theorem (change):** *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **change break**

```
\begin{theorem}[theorem style=change break]{change break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**14.24 Theorem (change break):**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **change apart**

```
\begin{theorem}[theorem style=change apart]{change apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**14.25 Theorem (change apart)**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **margin**

```
\begin{theorem}[theorem style=margin,left=10mm]{margin}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin,left=10mm,oversize]{margin}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**14.26 Theorem (margin):** *This is my theorem.*

$$a^2 + b^2 = c^2.$$

**14.27 Theorem (margin):** *This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **margin break**

```
\begin{theorem}[theorem style=margin break,left=10mm]{margin break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin break,left=10mm,oversize]{margin break}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**14.28 Theorem (margin break):**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

**14.29 Theorem (margin break):**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

- **margin apart**

```
\begin{theorem}[theorem style=margin apart,left=10mm]{margin apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
\begin{theorem}[theorem style=margin apart,left=10mm,oversize]{margin apart}{}
This is my theorem. \begin{equation*} a^2 + b^2 = c^2. \end{equation*}
\end{theorem}
```

**14.30 Theorem (margin apart)**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

**14.31 Theorem (margin apart)**

*This is my theorem.*

$$a^2 + b^2 = c^2.$$

### 14.3 Examples for Definitions and Theorems

In the following, the application of `\tcbmaketheorem`<sup>P.272</sup> to highlight mathematical definitions, theorems, or the like is demonstrated.

At first, additional `tcb` keys are created for the appearance of the colored boxes. It is assumed that theorems and corollaries should be identically colored. All following environments are numbered with a common counter, but this can be changed easily. Here, the counter output is supplemented by the subsection number. Further, the `cleveref` package [5] is used for clever references.

*Definition in the preamble:*

```
% \usepackage{cleveref}
\tcbset{
  defstyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
    arc=0mm, colback=blue!5!white,colframe=blue!75!black},
  theostyle/.style={fonttitle=\bfseries\upshape, fontupper=\slshape,
    colback=red!10!white,colframe=red!75!black},
}
\newtcbtheorem[number within=subsection,crefname={definition}{definitions}]%
{Definition}{Definition}{defstyle}{def}
\newtcbtheorem[use counter from=Definition,crefname={theorem}{theorems}]%
{Theorem}{Theorem}{theostyle}{theo}
\newtcbtheorem[use counter from=Definition,crefname={corollary}{corollaries}]%
{Corollary}{Corollary}{theostyle}{cor}
```

By `\newtcbtheorem`<sup>P.271</sup>, commonly numbered theorem environments are created now. `defstyle` and `theostyle` are used for the appearance.

Now, everything is prepared for the following examples.

The following theorem is numbered as `\Cref{theo:diffbarstetig}` and referenced with the marker `\texttt{theo:diffbarstetig}.\bigskip`

```
\begin{Theorem}{Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung
zu Testzwecken ungew\u{h}nlich lang ist}{diffbarstetig}%
Eine Funktion  $f:I\rightarrow\mathbb{R}$  ist in  $x_0\in I$  stetig, wenn  $f$  in
 $x_0$  differenzierbar ist.
\end{Theorem}
```

The following theorem is numbered as Theorem 14.3.1 and referenced with the marker `theo:diffbarstetig`.

**Theorem 14.3.1: Differenzierbarkeit bedingt Stetigkeit, wobei diese Benennung zu Testzwecken ungewöhnlich lang ist**

Eine Funktion  $f : I \rightarrow \mathbb{R}$  ist in  $x_0 \in I$  stetig, wenn  $f$  in  $x_0$  differenzierbar ist.

The following definition is numbered as `\Cref{def:diffbarkeit}` and referenced with the marker `\texttt{def:diffbarkeit}`.  
`\bigskip`

```
\begin{Definition}{Differenzierbarkeit}{diffbarkeit}
  Eine Funktion  $f: I \rightarrow \mathbb{R}$  auf einem Intervall  $I$  heit in  $x_0 \in I$  differenzierbar oder linear approximierbar, wenn der Grenzwert
  \begin{equation*}
    \lim_{x \rightarrow x_0} \frac{f(x) - f(x_0)}{x - x_0} = \lim_{h \rightarrow 0} \frac{f(x_0 + h) - f(x_0)}{h}
  \end{equation*}
  existiert. Bei Existenz heit dieser Grenzwert Ableitung oder Differentialquotient von  $f$  in  $x_0$  und man schreibt  $f'(x_0)$  fr ihn
  \begin{equation*}
    f'(x_0) \quad \text{oder} \quad \frac{df}{dx}(x_0).
  \end{equation*}
\end{Definition}
```

The following definition is numbered as Definition 14.3.2 and referenced with the marker `def:diffbarkeit`.

#### Definition 14.3.2: Differenzierbarkeit

Eine Funktion  $f : I \rightarrow \mathbb{R}$  auf einem Intervall  $I$  heit in  $x_0 \in I$  differenzierbar oder linear approximierbar, wenn der Grenzwert

$$\lim_{x \rightarrow x_0} \frac{f(x) - f(x_0)}{x - x_0} = \lim_{h \rightarrow 0} \frac{f(x_0 + h) - f(x_0)}{h}$$

existiert. Bei Existenz heit dieser Grenzwert Ableitung oder Differentialquotient von  $f$  in  $x_0$  und man schreibt fr ihn

$$f'(x_0) \quad \text{oder} \quad \frac{df}{dx}(x_0).$$

The following corollary is numbered as `\Cref{cor:nullstellen}` and referenced with the marker `\texttt{cor:nullstellen}`.  
`\bigskip`

```
\begin{Corollary}{Nullstellenexistenz}{nullstellen}
  Ist  $f: [a, b] \rightarrow \mathbb{R}$  stetig und haben  $f(a)$  und  $f(b)$  entgegengesetzte Vorzeichen, also  $f(a)f(b) < 0$ , so besitzt  $f$  eine Nullstelle  $x_0 \in ]a, b[$ , also  $f(x_0) = 0$ .
\end{Corollary}
```

The following corollary is numbered as Corollary 14.3.3 and referenced with the marker `cor:nullstellen`.

#### Corollary 14.3.3: Nullstellenexistenz

Ist  $f : [a, b] \rightarrow \mathbb{R}$  stetig und haben  $f(a)$  und  $f(b)$  entgegengesetzte Vorzeichen, also  $f(a)f(b) < 0$ , so besitzt  $f$  eine Nullstelle  $x_0 \in ]a, b[$ , also  $f(x_0) = 0$ .

```
\begin{Theorem}[boxrule=2mm,toptitle=-1.5mm,bottomtitle=-1.5mm]{%
  Hinreichende Bedingung f\u{r} Wendepunkte}{wendehinreichend}%
  $$$ sei eine auf einem Intervall $]a,b[$ dreimal stetig differenzierbare Funktion.
  Ist $$$'(x_0)=0$ in $x_0\in]a,b[$ und $$$''(x_0)\neq 0$, so ist
  $(x_0,f(x_0))$ ein Wendepunkt von $f$.
\end{Theorem}
```

#### Theorem 14.3.4: Hinreichende Bedingung für Wendepunkte

*$f$  sei eine auf einem Intervall  $]a,b[$  dreimal stetig differenzierbare Funktion. Ist  $f''(x_0) = 0$  in  $x_0 \in ]a,b[$  und  $f'''(x_0) \neq 0$ , so ist  $(x_0, f(x_0))$  ein Wendepunkt von  $f$ .*

```
% \usepackage{varioref}
% \usepackage{cleveref}
% \tcbuselibrary{skins}
\newtctheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{theorem style=plain apart,label type=theorem,enhanced,frame hidden,
 boxrule=2mm,titlerule=0mm,toptitle=1mm,bottomtitle=1mm,
 fonttitle=\bfseries\large,fontupper=\normalsize,
 coltitle=green!35!black,colbacktitle=green!15!white,
 colback=green!50!yellow!15!white,borderline={1pt}{0pt}{green!25!blue},
 }{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\u{r} $n$ Variable}{meanvalueththeorem}%
  Es sei $n\in\mathbb{N}$, $D\subseteq\mathbb{R}^n$ eine offene Menge und
  $f\in C^1(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
  $[x_0,x]\subseteq D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
  \begin{equation*}
    f(x)-f(x_0) = \operatorname{grad} f(\xi)^\top(x-x_0)
  \end{equation*}
\end{YetAnotherTheorem}

\medskip
Here, |cleveref| support is used to reference \Cref{theo:meanvalueththeorem}
on \Cpageref{theo:meanvalueththeorem}. This \namecref{theo:meanvalueththeorem}
can also be referenced by |\Vref| resulting in \Vref{theo:meanvalueththeorem}.
```

#### Theorem 14.3.5 (Mittelwertsatz für $n$ Variable)

Es sei  $n \in \mathbb{N}$ ,  $D \subseteq \mathbb{R}^n$  eine offene Menge und  $f \in C^1(D, \mathbb{R})$ . Dann gibt es auf jeder Strecke  $[x_0, x] \subset D$  einen Punkt  $\xi \in [x_0, x]$ , so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^\top (x - x_0)$$

Here, `cleveref` support is used to reference Theorem 14.3.5 on Page 290. This theorem can also be referenced by `\Vref` resulting in Theorem 14.3.5.

Note that `/tcb/label type→ P. 88` was used in the example above to feed `cleveref` [5] with the needed name information.

Here, using `\Vref` resulting in `\Vref{theo:meanvaluetheorem}` is more interesting`\ldots`

Here, using `\Vref` resulting in Theorem 14.3.5 on page 290 is more interesting...

```
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{theorem style=change apart,enhanced,arc=0mm,outer arc=0mm,
boxrule=0mm,toprule=1mm,bottomrule=1mm,left=1mm,right=1mm,
titlerule=0mm,toptitle=0mm,bottomtitle=1mm,top=0mm,
colframe=red!50!black,colback=red!5!white,coltitle=red!50!black,
title style={top color=yellow!50!white,bottom color=red!5!white,
middle color=yellow!50!white},
fonttitle=\bfseries\sffamily\normalsize,fontupper=\normalsize\itshape,
}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\{"{u}r $n$ Variable}{mittelwertsatz_n2}%
Es sei $n\in\mathbb{N}$, $D\subset\mathbb{R}^n$ eine offene Menge und
$f\in C^1(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
$[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
\begin{equation*}
f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
\end{equation*}
\end{YetAnotherTheorem}
```

### 14.3.6 Theorem (Mittelwertsatz für $n$ Variable)

Es sei  $n \in \mathbb{N}$ ,  $D \subseteq \mathbb{R}^n$  eine offene Menge und  $f \in C^1(D, \mathbb{R})$ . Dann gibt es auf jeder Strecke  $[x_0, x] \subset D$  einen Punkt  $\xi \in [x_0, x]$ , so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^{\top}(x - x_0)$$

```
% \usepackage{varwidth} \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{enhanced,frame empty,interior empty,colframe=ForestGreen!50!white,
coltitle=ForestGreen!50!black,fonttitle=\bfseries,colbacktitle=ForestGreen!15!white,
borderline={0.5mm}{0mm}{ForestGreen!15!white},
borderline={0.5mm}{0mm}{ForestGreen!50!white,dashed},
attach boxed title to top center={yshift=-2mm},
boxed title style={boxrule=0.4pt,varwidth boxed title}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\{"{u}r $n$ Variable}{mittelwertsatz_n3}%
Es sei $n\in\mathbb{N}$, $D\subset\mathbb{R}^n$ eine offene Menge und
$f\in C^1(D,\mathbb{R})$. Dann gibt es auf jeder Strecke
$[x_0,x]\subset D$ einen Punkt $\xi\in[x_0,x]$, so dass gilt
\begin{equation*}
f(x)-f(x_0) = \operatorname{grad} f(\xi)^{\top}(x-x_0)
\end{equation*}
\end{YetAnotherTheorem}
```

#### Theorem 14.3.7: Mittelwertsatz für $n$ Variable

Es sei  $n \in \mathbb{N}$ ,  $D \subseteq \mathbb{R}^n$  eine offene Menge und  $f \in C^1(D, \mathbb{R})$ . Dann gibt es auf jeder Strecke  $[x_0, x] \subset D$  einen Punkt  $\xi \in [x_0, x]$ , so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^{\top}(x - x_0)$$



You need more attention for your theorems? Here, you are ...

```
% tcbuselibrary{skins} % preamble
\begin{Theorem}[enhanced,
  fuzzy halo=3mm with yellow,
  fuzzy halo=2mm with red,
  fuzzy halo=1mm with yellow,
  watermark color=red!35!white,
  watermark text={Overacting\\Fundamental Theorem}]%
{Fundamental Theorem of Theorems}{fundamental}%
\lipsum[1-2]
\end{Theorem}
```

#### Theorem 14.3.8: Fundamental Theorem of Theorems

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Let's try a more conservative approach:

```
% \tcbuselibrary{skins}
\newtcbtheorem[use counter from=Definition]{YetAnotherTheorem}{Theorem}%
{theorem style=plain,enhanced,colframe=blue!50!black,colback=yellow!20!white,
 coltitle=red!50!black,fonttitle=\upshape\bfseries,fontupper=\itshape,
 drop fuzzy shadow=blue!50!black!50!white,boxrule=0.4pt}{theo}

\begin{YetAnotherTheorem}{Mittelwertsatz f\"{u}r $n$ Variable}{mittelwertsatz_n4}%
Es sei $n \in \mathbb{N}$, $D \subseteq \mathbb{R}^n$ eine offene Menge und
$f \in C^1(D, \mathbb{R})$. Dann gibt es auf jeder Strecke
$[x_0, x] \subseteq D$ einen Punkt $\xi \in [x_0, x]$, so dass gilt
\begin{equation*}
f(x) - f(x_0) = \operatorname{grad} f(\xi)^{\top} (x - x_0)
\end{equation*}
\end{YetAnotherTheorem}
```

**Theorem 14.3.9 (Mittelwertsatz für  $n$  Variable):** Es sei  $n \in \mathbb{N}$ ,  $D \subseteq \mathbb{R}^n$  eine offene Menge und  $f \in C^1(D, \mathbb{R})$ . Dann gibt es auf jeder Strecke  $[x_0, x] \subset D$  einen Punkt  $\xi \in [x_0, x]$ , so dass gilt

$$f(x) - f(x_0) = \operatorname{grad} f(\xi)^{\top} (x - x_0)$$



## 14.4 Using other theorem environments with tcolorbox

Instead of creating theorem environments with the methods described before, environments from other packages can be boxed with a `tcolorbox`.

Environments may be created e.g. by methods from the `theorem` package or the `amsthm` package. `\tcolorboxenvironment`<sup>→P.16</sup> can be used to put a box around these environments.

*Definition in the preamble:*

```
\usepackage{amsthm}

\theoremstyle{plain}%    from 'amsthm'
\newtheorem{lem}{Lemma}% from 'amsthm'

\tcolorboxenvironment{lem}{
  enhanced jigsaw,colframe=cyan,interior hidden,
  breakable,before skip=10pt,after skip=10pt }

\tcolorboxenvironment{proof}{% 'proof' from 'amsthm'
  blanker,breakable,left=5mm,
  before skip=10pt,after skip=10pt,
  borderline west={1mm}{0pt}{red}}
```

```
\begin{lem}
  \lipsum[2]
\end{lem}

\lipsum[3]

\begin{proof}
  \lipsum*[4]
\end{proof}
```

**Lemma 1.** *Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.*

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

*Proof.* Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. □

## 15 Library lib breakable

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{breakable}
```

### 15.1 Technical Overview

The library lib breakable supports the automatic breaking of a `tcolorbox`. This feature is enabled by `/tcb/breakable`<sup>→P. 296</sup> and disabled by `/tcb/unbreakable`<sup>→P. 297</sup>.

If a `tcolorbox` is set to be `/tcb/breakable`<sup>→P. 296</sup>, then the following algorithm is executed:

1. The box content is read to a box register similar but not identical to the unbreakable case.
2. If the total box fits into the current page, it is shipped out visibly unbroken and the algorithm stops.

#### Unbroken Box

The box.

unbroken

3. Otherwise, it is checked if at least `/tcb/lines before break`<sup>→P. 297</sup> of the upper box can be placed on the current page. If not, a page break is inserted and the algorithm goes back to Step 2.
4. Now, the *break sequence* starts. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *first part* of the *break sequence* and shipped out.

#### Broken Box

The box.

first

5. If the remaining content of the total box fits into the current page, the algorithm continues with Step 7, else with Step 6.
6. The upper box part or the lower box part is split such that it fits into the current page. The fitting part is named *middle part* of the *break sequence* and shipped out. Then, the algorithm goes back to Step 5.

The box.

middle

7. The remaining part is named *last part* of the *break sequence* and shipped out. The algorithm stops.

The box.

last

The algorithm takes care that the optional segmentation line never appears at the end of a box. The optional lower box part is also checked to have at least `/tcb/lines before break`<sup>→P. 297</sup>.

In principal, all boxes of the *break sequence* share the same geometric parameters. The differences are:

- The given `/tcb/before→P.72` and `/tcb/after→P.72` values are used only before the *first* and after the *last* part of the *break sequence*.
- A special behavior between the parts of the *break sequence* can be given by `/tcb/toprule at break→P.300`, `/tcb/bottomrule at break→P.300`, `/tcb/enlarge top at break by→P.77`, and `/tcb/enlarge bottom at break by→P.77`.
- The `/tcb/skin→P.105` decides *how* the *first*, *middle*, and *last* part look like. Actually, every part type has its own skin given by the options `/tcb/skin first→P.105`, `/tcb/skin middle→P.105`, and `/tcb/skin last→P.105`. Typically, these options are set automatically by the main skin, see Subsection 15.6 from page 305.

## 15.2 Limitations and Known Bugs

- The maximal total height of the upper and of the lower part of normal breakable `tcolorboxes` is about 65536pt (ca. 2300cm) apiece. If such a part gets longer, the output will get buggy without warning. For very oversized boxes which are longer than 65536pt, use the `unlimited` value for `/tcb/breakable→P.296`. With the `unlimited` setting, the applied algorithm has (virtually) no height limit for boxes, but very likely the compiler memory will have to be increased for boxes longer than 300 pages (depending on compiler settings and box content). But it is recommended to use `unlimited` for critical large boxes only.
- You can nest an unbreakable `tcolorbox` inside another `tcolorbox`, even inside a breakable one. But you cannot not nest a breakable box inside a breakable box. The `/tcb/breakable→P.296` key for a nested box is ignored automatically<sup>4</sup>, i. e. inner boxes are always unbreakable.

After all, in the unlikely case you really want to have the nested box to be breakable, use `/tcb/enforce breakable→P.297` for the nested box<sup>5</sup>. **But, a breakable box inside a breakable box will usually give a mess.**

- If your text content contains some text color changing commands, your color will not survive the break to the next box. But, with the `fontspec` package and `xelatex` or `lualatex`, you can use `\addfontfeatures{Color=mycolor}` to add a font color which survives the break.
- The `perpage` option of the `footmisc` package is deliberately deactivated inside a breakable box since all footnotes are placed at the end of the box (possibly far away from the reference point).

N 2014-10-30

<sup>4</sup>Until `tcolorbox` 3.04, the `/tcb/breakable→P.296` key was not ignored for nested boxes.

<sup>5</sup> `/tcb/enforce breakable→P.297` acts like `/tcb/breakable→P.296` until `tcolorbox` 3.04.

## 15.3 Main Option Keys

`/tcb/breakable=true|false|unlimited` (default `true`, initially `false`)

Allows the `tcolorbox` to be breakable. If the box is larger than the available space at the current page, the box is automatically broken and continued to the next next page. All sorts of `tcolorbox` can be made breakable. It depends on the skin how the breaking looks like. If you do not know better, use `/tcb/enhanced`<sup>P.168</sup> for breaking a box. The parts of the *break sequence* are numbered by the counter `tcbbreakpart`.

- **false**: Sets the `tcolorbox` to be unbreakable.
- **true**: Breaks the `tcolorbox` from one page to another. The maximal total height of the upper and of the lower part is about 65536pt (ca. 2300cm or ca. 90 pages) apiece.
- **unlimited**: Experimental code for unlimited total height of breakable boxes. For boxes longer than 300 pages (or even shorter ones) the compiler memory will have to be increased.

```
% \usepackage{lipsum} % preamble
\tcbset{enhanced jigsaw,colback=red!5!white,colframe=red!75!black,
  watermark color=yellow!25!white,watermark text=\arabic{tcbbreakpart},
  fonttitle=\bfseries}

\begin{tcolorbox}[breakable,title=My breakable box]
\lipsum[1-6]
\end{tcolorbox}
```

### My breakable box

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea

dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

**/tcb/unbreakable** (no value, initially set)

Sets the `tcolorbox` to be unbreakable.

**/tcb/enforce breakable** (no value)

A `tcolorbox` inside a `tcolorbox` is automatically set to be unbreakable. Using `/tcb/breakable`<sup>P. 296</sup> on such an inner box has no effect. If one *really* wants the inner box to be breakable, use `/tcb/enforce breakable`. **This will usually give a mess of shattered boxes. You are advised to not use this option.**

Note that `/tcb/enforce breakable` has the functionality that `/tcb/breakable`<sup>P. 296</sup> had until package version 3.04 and exists for backward compatibility.

**/tcb/title after break**=*<text>* (no default, initially empty)

The `/tcb/title`<sup>P. 17</sup> is used only for the *first* part of a *break sequence*. Use `title after break` to create a heading line with *<text>* as content for all following parts.

**/tcb/notitle after break** (no value, initially set)

Removes the title line or following parts in a *break sequence* if set before.

**/tcb/adjusted title after break**=*<text>* (style, no default, initially unset)

Works like `/tcb/adjusted title`<sup>P. 17</sup> but applied to `/tcb/title after break`.

**/tcb/lines before break**=*<number>* (no default, initially 2)

Assures that the given *<number>* of lines of the upper box part or the lower box part are placed before a break happens.

`/tcb/break at=<length>/<length>/.../<length>` (no default, initially 0pt)

Defines break points at the given  $\langle length \rangle$  values. The first  $\langle length \rangle$  defines the (maximal) height of the first partial box, the second  $\langle length \rangle$  defines the (maximal) height of the second partial box, and so on. The last  $\langle length \rangle$  value is applied to all following partial boxes if any. Setting a length to 0pt means that the naturally available space is used for breaking.

```
% \usepackage{multicol, lipsum}
\begin{multicols}{3}\footnotesize
Breakable boxes inside a |multicols| environment need special attendance.
They are broken by default at |\textheight|.
The |break at| option can be used to insert better break points by hand.
\begin{tcolorbox}[enhanced jigsaw,size=small,vfill before first,
  colframe=red,colback=yellow!10!white,before title=\raggedright,
  title={Broken box inside a |multicols| environment},fonttitle=\bfseries,
  enforce breakable,% use only breakable in the real world!
  pad at break=1mm,break at=3cm/6.3cm ]
\lipsum[1]
\end{tcolorbox}
\refKey{/tcb/height fixed for} may also be considered for |multicols| environments.
\end{multicols}
```

Breakable boxes inside a `multicols` environment need special attendance. They are broken by default at `\textheight`. The `break at` option can be used to insert better break points by hand.

#### Broken box inside a multicols environment

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dic-

tum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis,

viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

`/tcb/height fixed for`<sup>→ P. 301</sup> may also be considered for `multicols` environments.

`/tcb/enlargepage=<length>/<length>/.../<length>` (no default, initially 0pt)

Inserts a `\enlargethispage{<length>}` to the pages of the break sequence, i.e. allows one to enlarge (or shrink) partial boxes. The first  $\langle length \rangle$  is applied to the first partial box, the second  $\langle length \rangle$  is applied to the second partial box, and so on. The last  $\langle length \rangle$  value is applied to all following partial boxes if any. Note that floating boxes will not be enlarged.

```
\begin{tcolorbox}[breakable,enlargepage=0mm/\baselineskip/2\baselineskip/0mm,...
```

The example code enlarged the second partial box by one line, the third partial box by two lines, and all following parts are not enlarged.

If an automated page break occurs before the first partial box, the page enlargement is applied to the page before the first partial box *and* again to the page of the first partial box. Insert a manual break to prevent this.

In general, `enlargepage` should be used at the final stage of a document for fine-tuning only.

`/tcb/enlargepage flexible=<length>` (no default, initially 0pt)

This allows an automated page enlargement for up to  $\langle length \rangle$ . The algorithm can use this to avoid breaking a box, if there is enough room after enlargement. Also, the *last* partial box of a break sequence may be enlarged to avoid further breaking.

Note that this potential enlargement is *additive* to settings of `/tcb/enlargepage`<sup>→ P. 298</sup>. But `/tcb/enlargepage flexible` overwrites settings of `/tcb/pad before break*`<sup>→ P. 300</sup> or `/tcb/pad at break*`<sup>→ P. 300</sup>.

```
% The following setting hinders orphan lines for the last partial box
\tcbset{enlargepage flexible=\baselineskip}
```

N 2014-12-15

`/tcb/compress page=<option>` (default all, initially baselineskip)

This option controls the space management on the page which contains the unbroken box or the first part of a *break sequence*. Feasible  $\langle option \rangle$  values are:

- **all** (default value): All shrinkable glue on the page is potentially used for the unbroken box or the first part of a *break sequence*. Thus, all vertical spaces on the page will potentially be reduced to their minimal values.
- **baselineskip** (initial value): Shrinkable glue up to one `\baselineskip` on the page is potentially used for the unbroken box or the first part of a *break sequence*.
- **none**: The break algorithm respects the target size of the given glue values on the page. This was the initial value before version 3.34.

Note that the box *content* is not influenced by this option.

`/tcb/shrink break goal=<length>` (no default, initially 0pt)

This is an emergency parameter if the break algorithm produces unpleasant breaks. It shrinks the goal height of the current box part by  $\langle length \rangle$  which may result in smaller boxes. Never use negative values. *Usually, this option will never be needed at all.*



## 15.4 Option Keys for the Break Appearance

**/tcb/toprule at break=** $\langle length \rangle$  (no default, initially 0.5mm)

Sets the line width of the top rule to  $\langle length \rangle$  if the box is **/tcb/breakable**<sup>→ P. 296</sup>. In this case, it is applied to *middle* and *last* parts in a break sequence. Note that **/tcb/toprule**<sup>→ P. 29</sup> overwrites this value if used afterwards.

**/tcb/bottomrule at break=** $\langle length \rangle$  (no default, initially 0.5mm)

Sets the line width of the bottom rule to  $\langle length \rangle$  if the box is **/tcb/breakable**<sup>→ P. 296</sup>. In this case, it is applied to *first* and *middle* parts in a break sequence. Note that **/tcb/bottomrule**<sup>→ P. 29</sup> overwrites this value if used afterwards.

**/tcb/topsep at break=** $\langle length \rangle$  (no default, initially 0mm)

Additional vertical space of  $\langle length \rangle$  which is added at the top of *middle* and *last* parts in a break sequence. In general, it is not advisable to change this value if these parts start with a rule or a title.

**/tcb/bottomsep at break=** $\langle length \rangle$  (no default, initially 0mm)

Additional vertical space of  $\langle length \rangle$  which is added at the bottom of *first* and *middle* parts in a break sequence. In general, it is not advisable to change this value if these parts end with a rule.

**/tcb/pad before break=** $\langle length \rangle$  (style, no default, initially 3.5mm)

Sets the total amount of vertical space after the text content and before the break point to  $\langle length \rangle$ . This style sets **/tcb/toprule at break** to 0pt and changes **/tcb/topsep at break** as required. In general, it is not advisable to change this value if the *middle* and *last* parts in a break sequence start with a rule or a title.

**/tcb/pad before break\*=** $\langle length \rangle$  (style, no default)

Sets **/tcb/pad before break** to  $\langle length \rangle$  and **/tcb/enlargepage flexible**<sup>→ P. 299</sup> to an appropriate value such that empty closing frames are avoided.

**/tcb/pad after break=** $\langle length \rangle$  (style, no default, initially 3.5mm)

Sets the total amount of vertical space after the break point and before the text content to  $\langle length \rangle$ . This style sets **/tcb/bottomrule at break** to 0pt and changes **/tcb/bottomsep at break** as required. In general, it is not advisable to change this value if the *first* and *middle* parts in a break sequence end with a rule.

**/tcb/pad at break=** $\langle length \rangle$  (style, no default, initially 3.5mm)

Abbreviation for setting  $\langle length \rangle$  to **/tcb/pad before break** and **/tcb/pad after break**.

**/tcb/pad at break\*=** $\langle length \rangle$  (style, no default)

Sets **/tcb/pad at break** to  $\langle length \rangle$  and **/tcb/enlargepage flexible**<sup>→ P. 299</sup> to an appropriate value such that empty closing frames are avoided.

```
% \usepackage{lipsum} % preamble
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[enhanced jigsaw,breakable,pad at break*=0mm,
  title={For this box, the pad space at the break point is set to 0mm}]
  \lipsum[1-2]
\end{tcolorbox}
```

**For this box, the pad space at the break point is set to 0mm**

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/pad at break`<sup>→ P. 300</sup> or `/tcb/pad at break*`<sup>→ P. 300</sup> should be used as very last option in an option list, because they adapt other settings.

Also see `/tcb/enlarge top at break by`<sup>→ P. 77</sup> and `/tcb/enlarge bottom at break by`<sup>→ P. 77</sup>.

`/tcb/height fixed for=<part>` (no default, initially `none`)

When certain amount of space is available for a partial box of a break sequence, the partial box typically is smaller than this space (depending on the box content). For given `<part>(s)`, the height can be set to all available space.

- `none`: Every partial `tcolorbox` is set with its natural height.
- `first`: The *first* partial box is set to a height which matches the available space.
- `middle`: All *middle* partial boxes are set to a height which matches the available space.
- `last`: The *last* partial box is set to a height which matches the available space.
- `first and middle`: The *first* and all *middle* partial boxes are set to a height which matches the available space.
- `middle and last`: All *middle* partial boxes and the *last* partial box are set to a height which matches the available space.
- `all`: All partial boxes are set to a height which matches the available space.

If the box keeps unbroken, this option is not applied. See `/tcb/height`<sup>→ P. 45</sup> for setting a fixed height for unbroken boxes. See `/tcb/height fill`<sup>→ P. 47</sup> for giving unbroken boxes maximum height.

`/tcb/vfill before first=true|false` (default `true`, initially `false`)

Inserts a `\vfill` at the begin of the *first* partial box to move this partial box to the end of the current page. This may be used as an alternative to `/tcb/height fixed for=first` to get justified columns or pages. The `\vfill` is not inserted, if the box gets not actually broken.

## 15.5 Breakable boxes and the multicol package

Unbreakable `tcolorboxes` can be used without special care inside a `multicols` environment from the `multicol` package [9].

Since version 3.10, a breakable `tcolorbox` detects, if it is used inside a `multicols` environment. But choosing break points for a

breakable box cannot be done by the balancing routine of `multicols`. By default, boxes will break at `\textheight`. To get pleasant results, use the `/tcb/break at`<sup>→P.298</sup> and `/tcb/height fixed for`<sup>→P.301</sup> options.

```
% \usepackage{lipsum,multicol} % preamble
\small
\begin{multicols}{2}
  \lipsum[1]
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=title,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=1mm, break at=7.5cm/0pt ]
  \lipsum[2-4]
  \end{tcolorbox}
  \lipsum[4]
\end{multicols}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

### My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis.

Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

This example is already set inside a `multicols` environment. This time, a *middle* part has full `\textheight`. `/tcb/height fixed for`<sup>P.301</sup> is used to spread this box part over the full height to align with neighboring columns.

```
% \usepackage{lipsum,multicol}
\lipsum[1]
\begin{tcolorbox}[enhanced 2
  {jigsaw,breakable,
  size=title,
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  title=My breakable box,
  pad at break=2mm,
  break at=8.2cm/0pt,
  height fixed for=middle ]
\lipsum[2-7]
\end{tcolorbox}
\lipsum[8]
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

#### My breakable box

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris. Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus

adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula. Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.

Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi

quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec

odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

The following example has a `\tcolorbox` which fills the `\multicols` environment completely. Here, `/tcb/height fixed for`<sup>→ P.301</sup> is used to give all three columns the full height. Note that the appropriate `/tcb/break at`<sup>→ P.298</sup> value is not computed automatically but set manually.

```
% \usepackage{lipsum,multicol} % preamble
\small
\begin{multicols}{3}
  \begin{tcolorbox}[enhanced jigsaw,breakable,size=small,
    colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries,
    title=My breakable box,pad at break=2mm,drop fuzzy shadow,
    height fixed for=all, break at=11.4cm ]
    \lipsum[1-3]
  \end{tcolorbox}
\end{multicols}
```

#### My breakable box


Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur

auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum. Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.


Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

## 15.6 Break Sequence for the Skins


The following diagrams document the *break sequence* for different skins. Depending on the main skin of a `tcolorbox`, the actual skins of the *break sequence* parts are displayed.
























## 15.7 Break by Hand (Faked Break)

See Section 15.5 on page 302 for *real* column breaks.

Since the appearance of broken boxes is done by skins, it is quite easy to 'fake a break'. For this, you actually don't need the `lib breakable` library at all.

```
\tcbsset{enhanced,equal height group=fakedbreak,
  colback=LightGreen,colframe=DarkGreen,
  width=(\linewidth-6mm)/3,nobeforeafter,
  left=1mm,right=1mm,top=1mm,bottom=1mm,middle=1mm}
%
\begin{tcolorbox}[title=My broken box,skin=enhancedfirst]
This is a box which breaks from one column to another
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedmiddle]
column. I am sorry to say that this is a trick.
Nevertheless, you may use this trick for your
\end{tcolorbox}\hfill
\begin{tcolorbox}[skin=enhancedlast]
own purposes.
\end{tcolorbox}
```

My broken box

This is a box which breaks  
from one column to another

column. I am sorry to say that  
this is a trick. Nevertheless,  
you may use this trick for your

own purposes.



## 16 Library

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{fitting}
```

### 16.1 Macros of the Library

**`\tcbboxfit`**[*options*]{*box content*}

Creates a colored box where the given *box content* is fitted to the width and height of the box. A `tcbboxfit` has to have a fixed height. If no fixed height is given, a square box is constructed. In principal, most *options* for a `tcolorbox`<sup>P.11</sup> can be used for `\tcbboxfit` with some restrictions. A `\tcbboxfit` cannot have a lower part and cannot be broken.

```
% \usepackage{lipsum} \tcbuselibrary{raster}
\tcbset{colframe=blue!50!black,colback=red!10!white,
  boxsep=0pt,top=1mm,bottom=1mm,left=1mm,right=1mm,
  fit algorithm=hybrid*,raster equal skip=1mm}
\begin{tcbrafter}[raster columns=3,raster valign=bottom]
  \tcbboxfit[height=8cm]{\lipsum[1]}
  \tcbboxfit[height=4cm]{\lipsum[1]}
  \tcbboxfit[height=2cm]{\lipsum[1]}
\end{tcbrafter}
\begin{tcbrafter}[colback=green!10!white,boxsep=1mm]
  \tcbboxfit[height=4cm]{\lipsum[2]}
  \tcbboxfit[height=4cm,title=With a title]{\lipsum[2]}
\end{tcbrafter}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

#### With a title

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

**\newtcboxfit** [*\init options*] {\<name>} [<number>] [<default>] {\<options>}

Creates a new macro \<name> based on \tcboxfit<sup>P.314</sup>. Basically, \newtcboxfit operates like \newcommand. The new macro \<name> optionally takes <number>+1 arguments, where <default> is the default value for the optional first argument. The <options> are given to the underlying tcboxfit. The <init options> allow setting up automatic numbering, see Section 5 from page 92.

```
\newtcboxfit{\mybox}{colback=red!5!white,
colframe=red!75!black,width=4cm,
height=1.5cm,center upper}
```

```
\mybox{This is my own box.}\par
\mybox{This is my own box with more text
to be written.}
```

This is my own  
box.

This is my own box  
with more text to be  
written.

```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2]{colback=red!5!white,
colframe=red!75!black,fonttitle=\bfseries,
boxsep=1mm,left=0mm,right=0mm,top=0mm,
bottom=0mm,center upper,valign=center,
nobeeforeafter,width=#1,height=#2}
```

```
\mybox{2.5cm}{1cm}{First box}%
\mybox{2.5cm}{1cm}{Second box with more text}\\
\mybox{5cm}{2cm}{Third box with text}\\
\mybox{5cm}{3cm}{\lipsum[1]}
```

First box

Second box  
with more text

Third box with text

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

```
% \usepackage{lipsum}
\newtcboxfit{\mybox}[2][\colback=red!5!white,
colframe=red!75!black,
width=#2,height=#2/3*2,#1]
```

```
\mybox[colback=yellow]{5cm}%
{\lipsum[2]}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

**\renewtcboxfit** [*\init options*] {\<name>} [<number>] [<default>] {\<options>}

Operates like \newtcboxfit, but based on \renewcommand instead of \newcommand. An existing macro is redefined.

**\tcbfontsize** {\<factor>}

Selects a font size inside a tcolorbox which is scaled with the given <factor> relative to \tcbfitdim.

```
\tcbset{colback=red!5!white,colframe=red!75!black}
\begin{tcolorbox}[fit basedim=10pt]
{\tcbfontsize{0.25} Very tiny,}\\
{\tcbfontsize{0.5} Small,}\\
{\tcbfontsize{1} Normal,}\\
{\tcbfontsize{2} Large,}\\
{\tcbfontsize{4} Huge.}
\end{tcolorbox}
```

Very tiny,

Small,

Normal,

Large,

Huge.

## 16.2 Option Keys of the Library

The font size for the content of a box with fixed width and fixed height can be adjusted automatically. This is called the *fitbox capture mode*. Note that the fit control algorithm constructs a series of versions for the box and selects the 'best'. Therefore, the compilation time is quite longer than for a normal box. The algorithm will fail, if a different selected font size does not change the overall size of the box content. The `\tcboxfit`<sup>→P.314</sup> macro uses this algorithm by default.

The fit control keys are only applicable to unbreakable boxes without a lower part. The box content should not change counters.

**/tcb/fit** (style, initially unset)

Sets the `/tcb/capture`<sup>→P.85</sup> mode to `fitbox`, i.e. enables the font size adjustment algorithm. Thereby, a `tcolorbox`<sup>→P.11</sup> acts like `\tcboxfit`<sup>→P.314</sup> where the given  $\langle box\ content \rangle$  is fitted to the width and height of the box. Therefore, the box has to have a fixed height. If no fixed height is given, a square box is constructed. The font dimension `\tcbfitdim` can also be used to adjust the margins of the box since a box with a tiny font may not need large margins. The number of constructed boxes is saved to the macro `\tcbfitsteps` for analysis.

```
% \usepackage{lipsum}
% \tcbuselibrary{skins}
\newtcolorbox{fitting}[2][]{fit,height=#2,boxsep=1pt,valign=center,opacityupper=0.5,
top=0.4\tcbfitdim,bottom=0.4\tcbfitdim,left=0.75\tcbfitdim,right=0.75\tcbfitdim,
enhanced,watermark text={\tcbfitsteps},colframe=blue!75!black,colback=white,#1}

\begin{fitting}{4cm}
\lipsum[1]
\end{fitting}

\begin{fitting}{2cm}
\lipsum[2]
\end{fitting}

\begin{fitting}{1cm}
\lipsum[3]
\end{fitting}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

`/tcb/fit to=<width> and <height>` (style, initially unset)  
 Shortcut for using `/tcb/fit`<sup>P.316</sup> and setting the `<width>` and `<height>` values separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=3cm and 2cm]
  This box content is fitted to the given
  dimensions.
\end{tcolorbox}
```

This box content is fitted to the given dimensions.

`/tcb/fit to height=<height>` (style, initially unset)  
 Shortcut for using `/tcb/fit`<sup>P.316</sup> and setting the `<height>` value separately.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to height=2cm]
  This box content is fitted to the given
  height.
\end{tcolorbox}
```

This box content is fitted to the given height.

`/tcb/fit basedim=<length>` (no default, initially 10pt)  
 Sets the starting font dimension for the font size adjustment algorithm to `<length>`. The algorithm never enlarges this dimension.

```
\tcbset{colback=red!5!white,colframe=red!75!black}

\begin{tcolorbox}[fit to=4cm and 2cm]
  Too few words for the box.
\end{tcolorbox}

\begin{tcolorbox}[fit to=4cm and 2cm,
  fit basedim=50pt]
  Enough words for the box.
\end{tcolorbox}
```

Too few words for the box.

Enough words for the box.

`/tcb/fit skip=<real value>` (no default, initially 1.2)  
 Sets the skip value of the selected font to `<real value>` times `\tcbfitdim`.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\begin{tcolorbox}[fit to=5cm and 4cm,
  fit skip=1.0 ]
  \lipsum[1]
\end{tcolorbox}
```

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Redefines the standard L<sup>A</sup>T<sub>E</sub>X font size macros `\tiny`, `\scriptsize`, `\footnotesize`, `\small`, `\normalsize`, `\large`, `\Large`, `\LARGE`, `\huge`, and `\Huge`, to set font sizes relative to the current `\tcbfitdim`. Note that the display skip values for mathematical formulas are respected by the redefined macros.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\begin{tcolorbox}[fit to height=4cm]
  {\Large\bfseries This text is
    not adapted:\par}

  \lipsum[2]
\end{tcolorbox}

\begin{tcolorbox}[fit to height=4cm,
  fit fontsize macros ]
  {\Large\bfseries This text is adapted:\par}
  \lipsum[2]
\end{tcolorbox}
```

**This text is not adapted:**

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

**This text is adapted:**

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

```
\tcbset{colback=red!5!white,
  colframe=red!75!black,left=1mm,
  right=1mm,boxsep=0mm}

\let\realHuge=\Huge

\begin{tcolorbox}[fit basedim=7pt,
  fontupper=\normalsize,
  fit fontsize macros]
The relative relative font size macros
are also usable without the
\textit{fit} algorithm.\par
{\Huge Adapted Huge} ---
{\realHuge Original Huge}
\end{tcolorbox}
```

The relative relative font size macros are also usable without the *fit* algorithm.

Adapted Huge –  
Original Huge

```
\tcbset{size=fbox,colback=red!5!white,
  colframe=red!75!black}

\tcbboxfit[height=5cm,
  fit fontsize macros,
  fonttitle=\normalsize\bfseries,
  title=Adapted title]
{\lipsum[2]}
```

**Adapted title**

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit height plus=<dimension>` (no default, initially 0pt)

The box is allowed to enlarge the fixed height up to the given *<dimension>*, before a font size fit is applied. An optional `/tcb/fit width plus` is tried after the height adaption.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit height plus=1cm]
\lipsum[2]
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit width plus=<dimension>` (no default, initially 0pt)

The box is allowed to enlarge the fixed width up to the given *<dimension>*, before a font size fit is applied. An optional `/tcb/fit height plus` is tried before the width adaption.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,width=3cm,height=3cm,nobeforeafter}

\begin{tcolorbox}[fit]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
This is a tcolorbox.
\end{tcolorbox}
\begin{tcolorbox}[fit]
\lipsum[2]
\end{tcolorbox}
\begin{tcolorbox}[fit,fit width plus=1cm]
\lipsum[2]
\end{tcolorbox}
```

This is a tcolorbox.

This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



Typically but not necessarily, the optional title of a `tcolorbox` is not part of the fit operation. If a `/tcb/fit width plus` is applied, the title is also adapted to the new width. If counters are increased inside the title text, they may be increased more than one time. To avoid this, you are encouraged to use `/tcb/phantom`<sup>P.88</sup> or `/tcb/step and label`<sup>P.88</sup> to set counters or use automatic numbering, see Subsection 5.1 from page 92.

`/tcb/fit width from=<min> to <max>` (style, no default)

Sets the box width to `<min>` and allows the width to grow up to `<max>`.

```
% \usepackage{lipsum}
\tcbset{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,bottom=1mm,
right=1mm,boxsep=0mm,height=4cm}

\begin{tcolorbox}[fit,width=\linewidth/2]
\lipsum[2]
\end{tcolorbox}\par
\begin{tcolorbox}[fit width from=\linewidth/2 to \linewidth]
\lipsum[2]
\end{tcolorbox}\par
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

`/tcb/fit height from= $\langle min \rangle$  to  $\langle max \rangle$`  (style, no default)

Sets the box height to  $\langle min \rangle$  and allows the height to grow up to  $\langle max \rangle$ .

```
% \usepackage{lipsum}
\newtcolorbox{mybox}{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
  bottom=1mm,right=1mm,boxsep=0mm,width=4cm,nobeforeafter,
  fit height from=1cm to 8cm}

\begin{mybox}
This is a tcolorbox.
\end{mybox}
\begin{mybox}
This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.
\end{mybox}
\begin{mybox}
\lipsum[2]
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox. This is a tcolorbox. This is a tcolorbox.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.



`/tcb/fit algorithm=<name>` (no default, initially `fontsize`)

Sets the algorithm for the fitting process *after* optionally width and height are adapted.

Feasible values for `<name>` are:

- **fontsize** (initial): The algorithm is a bisection method that adapts the font size until certain stop conditions are fulfilled. This is the most time-consuming method but it is robust and gives pleasant results.

The used font has to be freely scalable for this method! Other content than text is not scaled down. The aspect ratio is fully guaranteed.

- **fontsize\***: First, the **fontsize** algorithm is applied. If the font was scaled down and the resulting height is too small, the box is squeezed to fit the area.

The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully guaranteed.

- **areaseize**: The algorithm calculates the area size for the text without scaling the font. The text box is shaped for the needed aspect ratio in one or two steps. Finally, it is scaled down with a standard `\resizebox` macro.

The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully guaranteed.

- **areaseize\***: The **areaseize** algorithm is applied, but if the content was scaled down and the resulting height is too small, the box is squeezed to fit the area.

The used font has not to be scalable. Every box content is scaled down. The aspect ratio cannot be fully guaranteed.

- **hybrid**: First, this algorithm estimates the needed font size in one or two steps. Then an **areaseize** fitting as above is applied.

The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully guaranteed.

- **hybrid\***: First, this algorithm estimates the needed font size in one or two steps. Then an **areaseize\*** fitting as above is applied.

The used font has to be freely scalable for this method! Other content than text may be slightly rescaled. The aspect ratio cannot be fully guaranteed.

- **squeeze**: The text box is brutally scaled down to fit.

The aspect ratio is very likely to be horrible. You should not use this method for final documents.

N 2014-10-29





N 2014-10-29

N 2014-10-29

```
% \usepackage{lipsum}
\newtcboxfit{mybox}[1]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
bottom=1mm,right=1mm,boxsep=0mm,width=3.5cm,height=7cm,nobeforeafter,
before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
enhanced,watermark text={\tcboxfitsteps},
fonttitle=\bfseries,adjusted title=#1,fit algorithm=#1}
```

```
\mybox{fontsize}{\lipsum[2]}\hfill
\mybox{hybrid}{\lipsum[2]}\hfill
\mybox{areaseize}{\lipsum[2]}\hfill
\mybox{squeeze}{\lipsum[2]}
```



Quality `\dotfill` versus `\dotfill` Speed

fontsize	hybrid	areaseize	squeeze
			

Quality ..... versus ..... Speed

```
% \usepackage{lipsum}
\newtcboxfit{mybox}[2]{colback=red!5!white,colframe=red!75!black,left=1mm,top=1mm,
size=tight,width=7.2cm,height=5cm,nobeforeafter,
before upper=\textcolor{blue}{\rule{5mm}{5mm}}\ ,
enhanced,fonttitle=\bfseries,adjusted title=#2,fit algorithm=#1}
```

```
\mybox{hybrid}{hybrid (possible gap at end)}{\lipsum[1]}\hfill
\mybox{hybrid*}{hybrid* (no gap but possibly squeezed)}{\lipsum[1]}
```

hybrid (possible gap at end)	hybrid* (no gap but possibly squeezed)
	

The following options set control parameters for the fit algorithm. Mainly, they apply to the `fontsize` variant, see `/tcb/fit algorithm` <sup>P. 322</sup>. The options should be seen as experimental and are likely to change in future versions, if necessary.

`/tcb/fit maxstep=<number>` (no default, initially 20)

Sets the maximal step size for the font size adjustment algorithm. In normal situations, the algorithm stops before reaching the initial value of 20 steps. If the box content does not shrink, this value prevents an endless loop.

`/tcb/fit maxfontdiff=<dimension>` (no default, initially 0.1pt)

The algorithm stops, if the font size is determined within a deviation of `<dimension>`.

`/tcb/fit maxfontdiffgap=<dimension>` (no default, initially 1pt)

The algorithm stops, if the number of lines is determined and the font size is determined within a deviation of `<dimension>`.

`/tcb/fit maxwidthdiff=<dimension>` (no default, initially 1pt)

The algorithm stops, if the (optionally) flexible box width is determined within a deviation of `<dimension>`.

`/tcb/fit maxwidthdiffgap=<dimension>` (no default, initially 10pt)

The algorithm stops, if the number of lines is determined and the (optionally) flexible box width is determined within a deviation of `<dimension>`.

`/tcb/fit warning=<value>` (no default, initially `off`)

Typically, the fit control algorithm constructs several auxiliary boxes to determine the optimal one. If not switched off, the construction of the auxiliary boxes may produce many `hbox` warnings. This option key changes the `\hbadness` value.

- `off`: Most of `'Underfull \hbox'` and `'Overfull \hbox'` warnings are switched off (including the ones for the finally used box).
- `on`: All warnings for all auxiliary boxes are displayed.
- `final`: Only warnings for the finally used box are displayed. Note that an additional box has to be constructed for these messages.

## 17 Library LIB hooks

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{hooks}
```

For the skin related options, the library LIB skins has to be loaded separately.

### 17.1 Concept of Hooks

A hook is a placeholder in some L<sup>A</sup>T<sub>E</sub>X code where additional code can be added. For example, the L<sup>A</sup>T<sub>E</sub>X macro `\AtBeginDocument` adds code to a hook which is placed at the beginning of every document.

Several option keys of `tcolorbox` allow providing some code which is added to specific places of a colored box. For example, `/tcb/before upper`<sup>→ P. 52</sup> places code before the content of the upper part. A following usage of this key overwrites any prior settings.

The library LIB hooks extends `/tcb/before upper`<sup>→ P. 52</sup> and several more existing keys to 'hookable' versions, e.g. `/tcb/before upper app`<sup>→ P. 326</sup> and `/tcb/before upper pre`<sup>→ P. 326</sup>. The 'hookable' keys don't overwrite prior settings but either *append* or *prepend* the newly given code to the existing code.

The general naming convention (with some small exceptions) is:

- `<option key> app`: works like `<option key>` but *appends* its code to the existing code.
- `<option key> pre`: works like `<option key>` but *prepends* its code to the existing code.

If the original `<option key>` is used (again), all code will be overwritten. Therefore, the order of the option key usage is crucial.

```
% \usepackage{array, tabularx}
\newcolumnstype{Y}{>{\raggedleft\arraybackslash}X}% see tabularx
\tcbset{enhanced,fonttitle=\bfseries\large,fontupper=\normalsize\sfamily,
colback=yellow!10!white,colframe=red!50!black,colbacktitle=Salmon!30!white,
coltitle=black,center title,
tabularx={X||Y|Y|Y|Y|Y},% this sets 'before upper' and 'after upper'
before upper app={Group & One & Two & Three & Four & Sum\\hline\hline} }

\begin{tcolorbox}[title=My table]
Red   & 1000.00 & 2000.00 & 3000.00 & 4000.00 & 10000.00\\hline
Green & 2000.00 & 3000.00 & 4000.00 & 5000.00 & 14000.00\\hline
Blue  & 3000.00 & 4000.00 & 5000.00 & 6000.00 & 18000.00\\hline\hline
Sum   & 6000.00 & 9000.00 & 12000.00 & 15000.00 & 42000.00
\end{tcolorbox}
```

My table					
Group	One	Two	Three	Four	Sum
Red	1000.00	2000.00	3000.00	4000.00	10000.00
Green	2000.00	3000.00	4000.00	5000.00	14000.00
Blue	3000.00	4000.00	5000.00	6000.00	18000.00
Sum	6000.00	9000.00	12000.00	15000.00	42000.00

## 17.2 Box Content Additions

The following option keys extend the options given in Subsection 4.10 from page 52.

**/tcb/before title app**= $\langle code \rangle$  (no default)

Appends the given  $\langle code \rangle$  to `/tcb/before title`<sup>P. 52</sup> *after* the color and font settings and *before* the content of the title.

**/tcb/before title pre**= $\langle code \rangle$  (no default)

Prepends the given  $\langle code \rangle$  to `/tcb/before title`<sup>P. 52</sup> *after* the color and font settings and *before* the content of the title.

**/tcb/after title app**= $\langle code \rangle$  (no default)

Appends the given  $\langle code \rangle$  to `/tcb/after title`<sup>P. 52</sup> *after* the content of the title.

**/tcb/after title pre**= $\langle code \rangle$  (no default)

Prepends the given  $\langle code \rangle$  to `/tcb/after title`<sup>P. 52</sup> *after* the content of the title.

**/tcb/before upper app**= $\langle code \rangle$  (no default)

Appends the given  $\langle code \rangle$  to `/tcb/before upper`<sup>P. 52</sup> *after* the color and font settings and *before* the content of the upper part.

**/tcb/before upper pre**= $\langle code \rangle$  (no default)

Prepends the given  $\langle code \rangle$  to `/tcb/before upper`<sup>P. 52</sup> *after* the color and font settings and *before* the content of the upper part.

**/tcb/after upper app**= $\langle code \rangle$  (no default)

Appends the given  $\langle code \rangle$  to `/tcb/after upper`<sup>P. 53</sup> *after* the content of the upper part.

**/tcb/after upper pre**= $\langle code \rangle$  (no default)

Prepends the given  $\langle code \rangle$  to `/tcb/after upper`<sup>P. 53</sup> *after* the content of the upper part.

```
% \tcbuselibrary{theorems}
\tcbset{ams align,% this sets 'before upper' and 'after upper'
  colback=yellow!10!white,colframe=red!50!black,
  before upper app={\frac{2}{\sqrt{2}}&=\sqrt{2}.\\},
  after upper pre={\\\sin\left(\frac{\pi}{2}\right)&=1.},
}

\begin{tcolorbox}
  \sum\limits_{n=1}^{\infty} \frac{1}{n} &= \infty.\\
  \int x^2 \, dx &= \frac{1}{3} x^3 + c.
\end{tcolorbox}
```

$$\frac{2}{\sqrt{2}} = \sqrt{2}. \quad (22)$$

$$\sum_{n=1}^{\infty} \frac{1}{n} = \infty. \quad (23)$$

$$\int x^2 \, dx = \frac{1}{3} x^3 + c. \quad (24)$$

$$\sin\left(\frac{\pi}{2}\right) = 1. \quad (25)$$

- `/tcb/before lower app=<code>` (no default)  
 Appends the given `<code>` to `/tcb/before lower`<sup>→ P. 53</sup> *after* the color and font settings and *before* the content of the lower part.
- `/tcb/before lower pre=<code>` (no default)  
 Prepends the given `<code>` to `/tcb/before lower`<sup>→ P. 53</sup> *after* the color and font settings and *before* the content of the lower part.
- `/tcb/after lower app=<code>` (no default)  
 Appends the given `<code>` to `/tcb/after lower`<sup>→ P. 53</sup> *after* the content of the lower part.
- `/tcb/after lower pre=<code>` (no default)  
 Prepends the given `<code>` to `/tcb/after lower`<sup>→ P. 53</sup> *after* the content of the lower part.

### 17.3 Embedding into the Surroundings

The following option keys extend the options given in Subsection 4.14 from page 72.

The 'hookable' versions are usable inside the document. In the preamble, they can only be used after explicit setting of `/tcb/before`<sup>→ P. 72</sup> and `/tcb/after`<sup>→ P. 72</sup> or by e. g. `/tcb/parskip`<sup>→ P. 72</sup>.

- `/tcb/before app=<code>` (no default)  
 Appends the given `<code>` to `/tcb/before`<sup>→ P. 72</sup> before the colored box.
- `/tcb/before pre=<code>` (no default)  
 Prepends the given `<code>` to `/tcb/before`<sup>→ P. 72</sup> before the colored box.
- `/tcb/after app=<code>` (no default)  
 Appends the given `<code>` to `/tcb/after`<sup>→ P. 72</sup> after the colored box.
- `/tcb/after pre=<code>` (no default)  
 Prepends the given `<code>` to `/tcb/after`<sup>→ P. 72</sup> after the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttitle=\bfseries}

\begin{tcolorbox}[title=My title,before app={The box follows:\\[4pt]},
  after app={This is the end.}]
This is a \textbf{tcolorbox}.
\end{tcolorbox}
```

The box follows:

**My title**

This is a **tcolorbox**.

This is the end.

## 17.4 Overlays

The following option keys extend the options given in Subsection 4.11 from page 61.


**/tcb/overlay app=***<graphical code>* (no default)

Appends the given *<graphical code>* to `/tcb/overlay`<sup>→ P. 61</sup>.

```
% \usetikzlibrary{patterns} % preamble
% \tcbuselibrary{skins} % preamble
\tcbset{frogbox/.style={enhanced,colback=green!10,colframe=green!65!black,
  enlarge top by=5.5mm,
  overlay={\foreach \x in {2cm,3.5cm} {
    \begin{scope}[shift={([xshift=\x]frame.north west)}]
      \path[draw=green!65!black,fill=green!10,line width=1mm] (0,0) arc (0:180:5mm);
      \path[fill=black] (-0.2,0) arc (0:180:1mm);
    \end{scope}}}}
\tcbset{ribbon/.style={overlay app={%
  \path[fill=blue!75!white,draw=blue,double=white!85!blue,
    preaction={opacity=0.6,fill=blue!75!white},
    line width=0.1mm,double distance=0.2mm,
    pattern=fivepointed stars,pattern color=white!75!blue]
    ([xshift=-0.2mm,yshift=-1.02cm]frame.north east)
    -- ++(-1,1) -- ++(-0.5,0) -- ++(1.5,-1.5) -- cycle;}}}

\begin{tcolorbox}[frogbox,title=My title]
This is a \textbf{tcolorbox}.
\end{tcolorbox}

\begin{tcolorbox}[frogbox,ribbon,title=My title]
This is a \textbf{tcolorbox}.\par
Here, we apply a second overlay.
\end{tcolorbox}
```



**/tcb/overlay pre=***<graphical code>* (no default)

Prepends the given *<graphical code>* to `/tcb/overlay`<sup>→ P. 61</sup>.

**/tcb/overlay unbroken app=***<graphical code>* (no default)

Appends the given *<graphical code>* to `/tcb/overlay unbroken`<sup>→ P. 62</sup>.

**/tcb/overlay unbroken pre=***<graphical code>* (no default)

Prepends the given *<graphical code>* to `/tcb/overlay unbroken`<sup>→ P. 62</sup>.

**/tcb/overlay first app=***<graphical code>* (no default)

Appends the given *<graphical code>* to `/tcb/overlay first`<sup>→ P. 62</sup>.

**/tcb/overlay first pre=***<graphical code>* (no default)

Prepends the given *<graphical code>* to `/tcb/overlay first`<sup>→ P. 62</sup>.



	<code>/tcb/overlay middle app=&lt;graphical code&gt;</code>	(no default)
	Appends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay middle</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay middle pre=&lt;graphical code&gt;</code>	(no default)
	Prepends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay middle</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay last app=&lt;graphical code&gt;</code>	(no default)
	Appends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay last</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay last pre=&lt;graphical code&gt;</code>	(no default)
	Prepends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay last</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay broken app=&lt;graphical code&gt;</code>	(no default)
	Appends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay broken</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay broken pre=&lt;graphical code&gt;</code>	(no default)
	Prepends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay broken</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay unbroken and first app=&lt;graphical code&gt;</code>	(no default)
	Appends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay unbroken and first</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay unbroken and first pre=&lt;graphical code&gt;</code>	(no default)
	Prepends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay unbroken and first</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay middle and last app=&lt;graphical code&gt;</code>	(no default)
	Appends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay middle and last</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay middle and last pre=&lt;graphical code&gt;</code>	(no default)
	Prepends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay middle and last</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay unbroken and last app=&lt;graphical code&gt;</code>	(no default)
	Appends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay unbroken and last</code> <sup>→ P. 62</sup> .	
	<code>/tcb/overlay unbroken and last pre=&lt;graphical code&gt;</code>	(no default)
	Prepends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay unbroken and last</code> <sup>→ P. 62</sup> .	
<div>N 2014-09-19</div>	<code>/tcb/overlay first and middle app=&lt;graphical code&gt;</code>	(no default)
	Appends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay first and middle</code> <sup>→ P. 62</sup> .	
<div>N 2014-09-19</div>	<code>/tcb/overlay first and middle pre=&lt;graphical code&gt;</code>	(no default)
	Prepends the given <code>&lt;graphical code&gt;</code> to <code>/tcb/overlay first and middle</code> <sup>→ P. 62</sup> .	

## 17.5 Watermarks

The following option keys extend the options given in Subsection 9.3 from page 130.

Watermarks are special overlays. The `hooks` library allows the combination of several watermarks and overlays.

`/tcb/watermark text app=<text>` (no default)

Appends a `/tcb/watermark text` <sup>→ P. 130</sup> to the colored box.

```
\tcbset{colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries}

\begin{tcolorbox}[enhanced,title=My title,watermark graphics=Basilica_5.png,
  watermark opacity=0.25,
  watermark text app=Basilica,watermark color=Navy
]
\lipsum[1-2]
\tcblower
This example uses a public domain picture from\
\url{http://commons.wikimedia.org/wiki/File:Basilica_5.png}
\end{tcolorbox}
```

### My title

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

This example uses a public domain picture from  
[http://commons.wikimedia.org/wiki/File:Basilica\\_5.png](http://commons.wikimedia.org/wiki/File:Basilica_5.png)

`/tcb/watermark text pre=<text>` (no default)

Prepends a `/tcb/watermark text` <sup>→ P. 130</sup> to the colored box.

`/tcb/watermark text app on=<part> is <text>` (no default)

Appends a `/tcb/watermark text on` <sup>→ P. 130</sup> the named `<part>` of a break sequence.

`/tcb/watermark text pre on=<part> is <text>` (no default)

Prepends a `/tcb/watermark text on` <sup>→ P. 130</sup> the named `<part>` of a break sequence.

- `/tcb/watermark graphics app=<file name>` (no default)  
 Appends a `/tcb/watermark graphics` <sup>→ P.131</sup> referenced by `<file name>` to the colored box.
- `/tcb/watermark graphics pre=<file name>` (no default)  
 Prepends a `/tcb/watermark graphics` <sup>→ P.131</sup> referenced by `<file name>` to the colored box.
- `/tcb/watermark graphics app on=<part> is <file name>` (no default)  
 Appends a `/tcb/watermark graphics on` <sup>→ P.131</sup> the named `<part>` of a break sequence.  
 The picture is referenced by `<file name>`.
- `/tcb/watermark graphics pre on=<part> is <file name>` (no default)  
 Prepends a `/tcb/watermark graphics on` <sup>→ P.131</sup> the named `<part>` of a break sequence.  
 The picture is referenced by `<file name>`.
- `/tcb/watermark tikz app=<graphical code>` (no default)  
 Appends a `/tcb/watermark tikz` <sup>→ P.132</sup> with the given `tikz <graphical code>` to the colored box.
- `/tcb/watermark tikz pre=<graphical code>` (no default)  
 Prepends a `/tcb/watermark tikz` <sup>→ P.132</sup> with the given `tikz <graphical code>` to the colored box.

```
% \usepackage{tikz}
\tcbset{colback=red!5!white,colframe=red!75!black,fonttttitle=\bfseries,
  watermark color=Navy,watermark opacity=0.25,
  smiley/.style={watermark tikz pre={%
    \path[fill=yellow,draw=yellow!75!red] (0,0) circle (1cm);
    \fill[red] (45:5mm) circle (1mm);
    \fill[red] (135:5mm) circle (1mm);
    \draw[line width=1mm,red] (215:5mm) arc (215:325:5mm);}}}

\begin{tcolorbox}[enhanced,title=My title, watermark text=Watermark,
  smiley]
\lipsum[1-2]
\end{tcolorbox}
```

#### My title

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

- `/tcb/watermark tikz app on=<part> is <graphical code>` (no default)  
 Appends a `/tcb/watermark tikz on` <sup>→ P.132</sup> the named `<part>` of a break sequence.
- `/tcb/watermark tikz pre on=<part> is <graphical code>` (no default)  
 Prepends a `/tcb/watermark tikz on` <sup>→ P.132</sup> the named `<part>` of a break sequence.

## 17.6 Underlays

The following option keys extend the options given in Section 9.8 on page 159. There are no app type keys since underlays are stackable by default.

`/tcb/underlay pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay`<sup>→ P. 159</sup>.

`/tcb/underlay unbroken pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay unbroken`<sup>→ P. 160</sup>.

`/tcb/underlay first pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay first`<sup>→ P. 160</sup>.

`/tcb/underlay middle pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay middle`<sup>→ P. 160</sup>.

`/tcb/underlay last pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay last`<sup>→ P. 160</sup>.

`/tcb/underlay boxed title pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay boxed title`<sup>→ P. 160</sup>.

`/tcb/underlay broken pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay broken`<sup>→ P. 160</sup>.

`/tcb/underlay unbroken and first pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay unbroken and first`<sup>→ P. 160</sup>.

`/tcb/underlay middle and last pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay middle and last`<sup>→ P. 160</sup>.

`/tcb/underlay unbroken and last pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay unbroken and last`<sup>→ P. 160</sup>.

`/tcb/underlay first and middle pre=<graphical code>` (no default)  
Prepends the given *<graphical code>* to `/tcb/underlay first and middle`<sup>→ P. 160</sup>.

N 2014-09-19

## 17.7 Finishes

The following option keys extend the options given in Section 9.9 on page 161. There are no app type keys since finishes are stackable by default.

**/tcb/finish pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish*<sup>→ P. 161</sup>.

**/tcb/finish unbroken pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish unbroken*<sup>→ P. 162</sup>.

**/tcb/finish first pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish first*<sup>→ P. 162</sup>.

**/tcb/finish middle pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish middle*<sup>→ P. 162</sup>.

**/tcb/finish last pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish last*<sup>→ P. 162</sup>.

**/tcb/finish broken pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish broken*<sup>→ P. 162</sup>.

**/tcb/finish unbroken and first pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish unbroken and first*<sup>→ P. 162</sup>.

**/tcb/finish middle and last pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish middle and last*<sup>→ P. 162</sup>.

**/tcb/finish unbroken and last pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish unbroken and last*<sup>→ P. 162</sup>.

**/tcb/finish first and middle pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/finish first and middle*<sup>→ P. 162</sup>.

N 2014-09-19

## 17.8 Skin Code

The following option keys extend the options given in Subsection 8.2 from page 109.

**/tcb/frame code app**=*<graphical code>* (no default)  
Appends the given *<graphical code>* to */tcb/frame code*<sup>→ P. 109</sup>.

**/tcb/frame code pre**=*<graphical code>* (no default)  
Prepends the given *<graphical code>* to */tcb/frame code*<sup>→ P. 109</sup>.

**/tcb/interior titled code app**=*<graphical code>* (no default)  
Appends the given *<graphical code>* to */tcb/interior titled code*<sup>→ P. 109</sup>.

```

\begin{tcolorbox}[title=My title,enhanced,colframe=Navy,
  frame code app={\draw[yellow,line width=1cm] (
    frame.south west)--(frame.north east);},
  interior titled code app={\draw[red,line width=1cm]
    (frame.north west)--(frame.south east);},
]
\lipsum[1]
\end{tcolorbox}

```

My title

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

**/tcb/interior titled code pre**=*<graphical code>* (no default)

Prepends the given *<graphical code>* to `/tcb/interior titled code`<sup>→P. 109</sup>.

**/tcb/interior code app**=*<graphical code>* (no default)

Appends the given *<graphical code>* to `/tcb/interior code`<sup>→P. 110</sup>.

**/tcb/interior code pre**=*<graphical code>* (no default)

Prepends the given *<graphical code>* to `/tcb/interior code`<sup>→P. 110</sup>.

**/tcb/segmentation code app**=*<graphical code>* (no default)

Appends the given *<graphical code>* to `/tcb/segmentation code`<sup>→P. 110</sup>.

**/tcb/segmentation code pre**=*<graphical code>* (no default)

Prepends the given *<graphical code>* to `/tcb/segmentation code`<sup>→P. 110</sup>.

**/tcb/title code app**=*<graphical code>* (no default)

Appends the given *<graphical code>* to `/tcb/title code`<sup>→P. 111</sup>.

**/tcb/title code pre**=*<graphical code>* (no default)

Prepends the given *<graphical code>* to `/tcb/title code`<sup>→P. 111</sup>.

## 18 Library **xparse**

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{xparse}
```

This also loads the package `xparse` [11].

The purpose of this library is to give comfortable access to the powerful document command production with `xparse` for `tcolorbox`. See the `xparse` package documentation [11] for details about the argument  $\langle specification \rangle$  used in this section.

### 18.1 Option Keys

**/tcb/verbatim** (style, no value)

Sets options for a *verbatim* style `\tcbox`<sup>P.13</sup>. Since the indented boxes may contain only very few words, the dimensions are made smaller and `/tcb/nobeforeafter`<sup>P.72</sup> and `/tcb/tcbox raise base`<sup>P.87</sup> are set.

```
\DeclareTotalTCBox{\myverb}{ v }{verbatim,
  colframe=red!75!black,colupper=blue}{#1}

\myverb{\textbf} is a \myverb{\LaTeX} command.
```

`\textbf` is a `\LaTeX` command.

**/tcb/IfNoValueTF**= $\{\langle argument \rangle\}\{\langle true options \rangle\}\{\langle false options \rangle\}$  (no default)

Wraps the `\IfNoValueTF` command of `xparse` for option setting. If the  $\langle argument \rangle$  has no value, the  $\langle true options \rangle$  are set. Otherwise, the  $\langle false options \rangle$  are set.

```
\DeclareTColorBox{mybox}{ o }{colframe=red!75!black,
  IfNoValueTF={#1}{colback=red!5!white}{enhanced,interior style image=#1}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[goldshade.png]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.



**/tcb/IfValueTF**={*<argument>*}{*<true options>*}{*<false options>*} (no default)

Wraps the `\IfValueTF` command of `xparse` for option setting. If the *<argument>* has a value, the *<true options>* are set. Otherwise, the *<false options>* are set.

```
\DeclareTColorBox{mybox}{o}{colframe=red!75!black,colback=red!5!white,
  IfValueTF={#1}{title={\flqq #1\frqq},fonttitle=\bfseries}{}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[My title]
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

«My title»

This is a tcolorbox.

**/tcb/IfBooleanTF**={*<argument>*}{*<true options>*}{*<false options>*} (no default)

Wraps the `\IfBooleanTF` command of `xparse` for option setting. If the *<argument>* is `\BooleanTrue`, the *<true options>* are set. If the *<argument>* is `\BooleanFalse`, the *<false options>* are set.

```
\DeclareTColorBox{mybox}{s}{colframe=red!75!black,
  IfBooleanTF={#1}{colback=yellow!50!red}{colback=red!5!white}}

\begin{mybox}
This is a tcolorbox.
\end{mybox}

\begin{mybox}*
This is a tcolorbox.
\end{mybox}
```

This is a tcolorbox.

This is a tcolorbox.

## 18.2 Producing tcolorbox Environments and Commands

**\DeclareTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Creates a new environment *<name>* based on `tcolorbox` <sup>P. 11</sup>.

Basically, `\DeclareTColorBox` operates like `\DeclareDocumentEnvironment`. This means, the new environment *<name>* is constructed with the given argument *<specification>*. The *<options>* are given to the underlying `tcolorbox` <sup>P. 11</sup>.

Note that `/tcb/savedelimiter` <sup>P. 24</sup> is set to the given *<name>* automatically.

The *<init options>* allow setting up automatic numbering, see Section 5 from page 92.

The new environment is always created, irrespective of an already existing environment with the same name.

```
% counter from previous example
\DeclareTColorBox[use counter from=pabox]{mybox}{ 0{red} m d"" 0{ } }
{enhanced,colframe=#1!75!black,colback=#1!5!white,
 fonttitle=\bfseries,title={\thetcbcounter~#2},
 IfValueTF={#3}{watermark text={#3}}{},{#4}}

\begin{mybox}{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[blue]{My title}
This is a tcolorbox.
\end{mybox}

\begin{mybox}[green]{My title}"My Watermark"
This is a tcolorbox.
\end{mybox}

\begin{mybox}[yellow]{My title}[colbacktitle=yellow!50!white,coltitle=black]
This is a tcolorbox.
\end{mybox}

\begin{mybox}[purple]{My title}"All together"[coltitle=yellow]
This is a tcolorbox.
\end{mybox}
```

### 18.1 My title

This is a tcolorbox.

### 18.2 My title

This is a tcolorbox.

### 18.3 My title

This is a tcolorbox.

My Watermark

### 18.4 My title

This is a tcolorbox.

### 18.5 My title

This is a tcolorbox.

All together

**\NewTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like **\DeclareTColorBox**<sup>→ P. 337</sup>, but based on **\NewDocumentEnvironment** instead of **\DeclareDocumentEnvironment**. An error is issued if *<name>* has already been defined.

**\RenewTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like **\DeclareTColorBox**<sup>→ P. 337</sup>, but based on **\RenewDocumentEnvironment** instead of **\DeclareDocumentEnvironment**. An existing environment is redefined.

**\ProvideTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like **\DeclareTColorBox**<sup>→ P. 337</sup>, but based on **\ProvideDocumentEnvironment** instead of **\DeclareDocumentEnvironment**. The environment *<name>* is only created if it is not already defined.

**\DeclareTotalTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}{*<content>*}

Creates a new command `\<name>` based on `tcolorbox`<sup>→P.11</sup>. In contrast to `\DeclareTColorBox`<sup>→P.337</sup>, also the *<content>* of the `tcolorbox` is specified.

Basically, `\DeclareTotalTColorBox` operates like `\DeclareDocumentCommand`. This means, the new command `\<name>` is constructed with the given argument *<specification>*. The *<options>* are given to the underlying `tcolorbox`<sup>→P.11</sup> which is filled with the specified *<content>*.

Note that `/tcb/savedelimiter`<sup>→P.24</sup> is set to the given *<name>* automatically.

The *<init options>* allow setting up automatic numbering, see Section 5 from page 92.

The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTColorBox{\diabox}{0}{v m }
{ bicolor,nobeforeafter,equal height group=diabox,width=5.7cm,
  fonttitle=\bfseries\ttfamily,adjusted title={#2},center title,
  colframe=blue!20!black,leftupper=0mm,rightupper=0mm,colback=black!75!white,#1}
{ \tikz\path[fill zoom image={#2}] (0,0) rectangle (\linewidth,4cm);%
  \tcblower#3}

\diabox{blueshade.png}{Created with |GIMP|.\\url{http://www.gimp.org}}
\diabox{goldshade.png}{Created with |GIMP|.\\url{http://www.gimp.org}}
```



**\NewTotalTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}{*<content>*}

Operates like `\DeclareTotalTColorBox`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if *<name>* has already been defined.

**\RenewTotalTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}{*<content>*}

Operates like `\DeclareTotalTColorBox`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

**\ProvideTotalTColorBox**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}{*<content>*}

Operates like `\DeclareTotalTColorBox`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command *<name>* is only created if it is not already defined.

## 18.3 Producing tcbbox Commands

**\DeclareTCBox**[*<init options>*]{\<name>}{<specification>}{<options>}

Creates a new command \<name> based on \tcbbox<sup>→ P. 13</sup>. Basically, \DeclareTCBox operates like \DeclareDocumentCommand. This means, the new command \<name> is constructed with the given argument <specification>. The <options> are given to the underlying \tcbbox<sup>→ P. 13</sup>.

Note that /tcb/savedelimiter<sup>→ P. 24</sup> is set to the given <name> automatically.

The <init options> allow setting up automatic numbering, see Section 5 from page 92.

The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBox[use counter from=pabox]{\mybox}{ s m s }
{ nobeforeafter,colback=red!5!white,colframe=red!75!black,
  title={#2 (Box \thetcbcounter)},fonttitle=\bfseries,
  IfBooleanTF={#1}{enhanced,drop shadow}{},
  IfBooleanTF={#3}{colbacktitle=red!50!white}{}}

\mybox{Bird}{This is my first box.}
\hfill
\mybox*{Tree}{This is my second box.}
\par\bigskip
\mybox{Bike}*{This is my third box.}
\hfill
\mybox*{City}*{This is my fourth box.}
```

**Bird (Box 18.6)**

This is my first box.

**Tree (Box 18.7)**

This is my second box.

**Bike (Box 18.8)**

This is my third box.

**City (Box 18.9)**

This is my fourth box.

**\NewTCBox**[*<init options>*]{\<name>}{<specification>}{<options>}

Operates like \DeclareTCBox, but based on \NewDocumentCommand instead of \DeclareDocumentCommand. An error is issued if \<name> has already been defined.

**\RenewTCBox**[*<init options>*]{\<name>}{<specification>}{<options>}

Operates like \DeclareTCBox, but based on \RenewDocumentCommand instead of \DeclareDocumentCommand. An existing command is redefined.

**\ProvideTCBox**[*<init options>*]{\<name>}{<specification>}{<options>}

Operates like \DeclareTCBox, but based on \ProvideDocumentCommand instead of \DeclareDocumentCommand. The command \<name> is only created if it is not already defined.

**\DeclareTotalTCBox**[*\init options*]{\<name>}{\<specification>}{\<options>}{\<content>}

Creates a new command \<name> based on \tcbox<sup>→P.13</sup>. In contrast to \DeclareTCBox<sup>→P.340</sup>, also the <content> of the tcbox is specified.

Basically, \DeclareTotalTCBox operates like \DeclareDocumentCommand. This means, the new command \<name> is constructed with the given argument <specification>. The <options> are given to the underlying \tcbox<sup>→P.13</sup> which is filled with the specified <content>.

Note that /tcb/savedelimiter<sup>→P.24</sup> is set to the given <name> automatically.

The <init options> allow setting up automatic numbering, see Section 5 from page 92.

The new command is always created, irrespective of an already existing command with the same name.

```
\DeclareTotalTCBox{\myverb}{ 0{red} v 0{ } }
{ fontupper=\ttfamily,nobeforeafter,tcbbox raise base,arc=0pt,outer arc=0pt,
  top=0pt,bottom=0pt,left=0mm,right=0mm,
  leftrule=0pt,rightrule=0pt,toprule=0.3mm,bottomrule=0.3mm,boxsep=0.5mm,
  colback=#1!10!white,colframe=#1!50!black,#3}{#2}
```

To set a word \textbf{bold} in \myverb{\LaTeX}, one uses  
\myverb[green]{\textbf{bold}}. Alternatively, write  
\myverb[yellow]{\bfseries bold}.  
In \myverb[blue]{\LaTeX}[enhanced,fuzzy halo], other font settings are  
done in the same way, e.\,g. \myverb{\textit}, \myverb{\itshape}\  
or \myverb[brown]{\texttt}, \myverb[brown]{\ttfamily}.

To set a word **bold** in \LaTeX, one uses \textbf{bold}. Alternatively, write {\bfseries bold}.  
In \LaTeX, other font settings are done in the same way, e.g. \textit, \itshape  
or \texttt, \ttfamily.

The next example uses \lstinline from the listings package to typeset the verbatim content.

```
% \usepackage{listings} or \tcbuselibrary{listings}
\DeclareTotalTCBox{\commandbox}{ s v }
{verbatim,colupper=white,colback=black!75!white,colframe=black}
{\IfBooleanTF{#1}{\textcolor{red}{\ttfamily\bfseries > }}{}}%
  \lstinline[language=command.com,keywordstyle=\color{blue!35!white}\bfseries]^#2~}

\commandbox*{cd "My Documents"} changes to directory \commandbox{My Documents}.

\commandbox*{dir /A} lists the directory content.

\commandbox*{copy example.txt d:\target} copies \commandbox{example.txt} to
\commandbox{d:\target}.
```

> cd "My\_Documents" changes to directory My Documents .

> dir /A lists the directory content.

> copy example.txt d:\target copies example.txt to d:\target .

- \NewTotalTCBox**[*<init options>*]{\<name>}{<specification>}{<options>}{<content>}
- Operates like `\DeclareTotalTCBox`<sup>P. 341</sup>, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\<name>` has already been defined.
- \RenewTotalTCBox**[*<init options>*]{\<name>}{<specification>}{<options>}{<content>}
- Operates like `\DeclareTotalTCBox`<sup>P. 341</sup>, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.
- \ProvideTotalTCBox**[*<init options>*]{\<name>}{<specification>}{<options>}{<content>}
- Operates like `\DeclareTotalTCBox`<sup>P. 341</sup>, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\<name>` is only created if it is not already defined.
- \tcboxverb**[*<options>*]{<verbatim box content>}
- Creates a colored box based on `\tcbox`<sup>P. 13</sup> which is fitted to the width of the given `<verbatim box content>`. The underlying `\tcbox`<sup>P. 13</sup> is styled with `/tcb/verbatim`<sup>P. 335</sup> plus the given `<options>`. The difference to `\tcbox`<sup>P. 13</sup> is that the `<verbatim box content>` is interpreted *verbatim*. Therefore, `\tcboxverb` acts similar to `\verb`.

```
\tcboxverb{\LaTeX}, \tcboxverb[colback=blue!10!white,colupper=blue]{\LaTeX},
\tcbboxverb[blank,fuzzy halo]{\LaTeX}, \tcboxverb[beamer]{\LaTeX},
\tcbboxverb[enhanced,skin=enhancedmiddle jigsaw,colframe=red]{\LaTeX}.
```

`\LaTeX`, `\LaTeX`, `\LaTeX`, `\LaTeX`, `\LaTeX`.



## 18.4 Producing tcblisting Environments

The following commands need the `\usepackage{listings}` library to be included.

**\DeclareTCBListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Creates a new environment *<name>* based on `tcblisting` <sup>→ P. 233</sup>.

Basically, `\DeclareTCBListing` operates like `\DeclareDocumentEnvironment`. This means, the new environment *<name>* is constructed with the given argument *<specification>*.

The *<options>* are given to the underlying `tcblisting` <sup>→ P. 233</sup>.

Note that `/tcb/savedelimiter` <sup>→ P. 24</sup> is set to the given *<name>* automatically.

The *<init options>* allow setting up automatic numbering, see Section 5 from page 92.

The new environment is always created, irrespective of an already existing environment with the same name.

```
\DeclareTCBListing{mybox}{ s 0{ } m }{%
  colback=red!5!white,
  colframe=red!75!black,
  fonttitle=\bfseries,
  IfBooleanTF={#1}
    {listing side text}
    {text side listing},
  title=#3,#2}
```

```
\begin{mybox}{Listing Box}
```

```
This is my
```

```
\LaTeX\ box.
```

```
\end{mybox}
```

```
\bigskip
```

```
\begin{mybox}*{Listing Box}
```

```
This is my
```

```
\LaTeX\ box.
```

```
\end{mybox}
```

```
\bigskip
```

```
\begin{mybox}[colback=yellow]
```

```
{Listing Box}
```

```
This is my
```

```
\LaTeX\ box.
```

```
\end{mybox}
```

### Listing Box

```
This is my
\LaTeX box.
```

```
This is my
\LaTeX\ box.
```

### Listing Box

```
This is my
\LaTeX\ box.
```

```
This is my
\LaTeX\ box.
```

### Listing Box

```
This is my
\LaTeX box.
```

```
This is my
\LaTeX\ box.
```

**\NewTCBListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like `\DeclareTCBListing`, but based on `\NewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An error is issued if *<name>* has already been defined.

**\RenewTCBListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like `\DeclareTCBListing`, but based on `\RenewDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. An existing environment is redefined.

**\ProvideTCBListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like `\DeclareTCBListing`, but based on `\ProvideDocumentEnvironment` instead of `\DeclareDocumentEnvironment`. The environment *<name>* is only created if it is not already defined.

## Caveats of using an environment ending with an optional argument

```
\DeclareTCBListing{mybox}{0}{ }{listing only,#1}
```

```
\begin{mybox}[colframe=red]  
\good  
\end{mybox}
```

```
\begin{mybox}[colframe=red]\good\end{mybox}
```

```
\begin{mybox}  
\good  
\end{mybox}
```

```
\begin{mybox} \good\end{mybox}
```

```
\begin{mybox}\bad!\end{mybox}
```

```
\begin{mybox}  
[\good]  
\end{mybox}
```

```
\begin{mybox} [\good]\end{mybox}
```

```
\begin{mybox} [\bad!]\end{mybox}
```

## 18.5 Producing tcbinputlisting Commands

The following commands need the `\lib listings` library to be included.

**\DeclareTCBInputListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Creates a new command `\<name>` based on `\tcbinputlisting`<sup>→ P. 235</sup>. Basically, `\DeclareTCBInputListing` operates like `\DeclareDocumentCommand`. This means, the new command `\<name>` is constructed with the given argument *<specification>*. The *<options>* are given to the underlying `\tcbinputlisting`<sup>→ P. 235</sup>.

The *<init options>* allow setting up automatic numbering, see Section 5 from page 92.

The new command is always created, irrespective of an already existing command with the same name.

```
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ 0{ } 0{red} m }{%
  listing file={#3},title=Listing~\thetcbcounter,
  colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
  fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
[blue]{\jobname.tcbtemp}
```

### Listing 18.10

```
This is the included file content:
% counter from previous example
\DeclareTCBInputListing[use counter from=pabox]{\mylisting}{ 0{ }
  0{red} m }{%
  listing file={#3},title=Listing~\thetcbcounter,
  colback=#2!5!white,colframe=#2!50!black,colbacktitle=#2!75!black,
  fonttitle=\bfseries,listing only,#1}

\mylisting[before upper=\textit{This is the included file content:}]
[blue]{\jobname.tcbtemp}
```

**\NewTCBInputListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like `\DeclareTCBInputListing`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\<name>` has already been defined.

**\RenewTCBInputListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like `\DeclareTCBInputListing`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

**\ProvideTCBInputListing**[*<init options>*]{*<name>*}{*<specification>*}{*<options>*}

Operates like `\DeclareTCBInputListing`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\<name>` is only created if it is not already defined.

## 18.6 Producing `tbxfit` Commands

The following commands need the `lib fitting` library to be included.

**`\DeclareTCBoxFit`** [*init options*] {\<name>}{\<specification>}{\<options>}

Creates a new command `\<name>` based on `\tcboxfit`<sup>P.314</sup>. Basically, `\DeclareTCBoxFit` operates like `\DeclareDocumentCommand`. This means, the new command `\<name>` is constructed with the given argument `\<specification>`. The `\<options>` are given to the underlying `\tcboxfit`<sup>P.314</sup>.

Note that `/tcb/savedelimiter`<sup>P.24</sup> is set to the given `\<name>` automatically.

The `\<init options>` allow setting up automatic numbering, see Section 5 from page 92.

The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}

\DeclareTCBoxFit{\mybox}{0}{m o }
{colback=red!5!white,
 colframe=red!75!black,
 width=#2,height=#2/3*2,
 IfValueTF={#3}{height=#3}{},
 #1}

\mybox[colback=yellow]{5cm}%
{\lipsum[2]}

\mybox[colback=yellow]{5cm}[4cm]{\lipsum[2]}
```

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

**`\NewTCBoxFit`** [*init options*] {\<name>}{\<specification>}{\<options>}

Operates like `\DeclareTCBoxFit`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\<name>` has already been defined.

**`\RenewTCBoxFit`** [*init options*] {\<name>}{\<specification>}{\<options>}

Operates like `\DeclareTCBoxFit`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

**`\ProvideTCBoxFit`** [*init options*] {\<name>}{\<specification>}{\<options>}

Operates like `\DeclareTCBoxFit`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\<name>` is only created if it is not already defined.

```
\DeclareTotalTCBoxFit[<init options>]{\<name>}{<specification>}{<options>}{<content>}
```

Creates a new command `\langle name \rangle` based on `\tcboxfit`<sup>P.314</sup>. In contrast to `\DeclareTCBoxFit`<sup>P.346</sup>, also the `\langle content \rangle` of the `tcboxfit` is specified.

Basically, `\DeclareTotalTCBoxFit` operates like `\DeclareDocumentCommand`. This means, the new command `\langle name \rangle` is constructed with the given argument `\langle specification \rangle`. The `\langle options \rangle` are given to the underlying `\tcbboxfit`<sup>P.314</sup> which is filled with the specified `\langle content \rangle`.

Note that `/tcb/savedelimiter`<sup>P.24</sup> is set to the given  $\langle name \rangle$  automatically.

The `init options` allow setting up automatic numbering, see Section 5 from page 92.

The new command is always created, irrespective of an already existing command with the same name.

```
% \usepackage{lipsum}
```

```
\DeclareTotalTCBoxFit{\multibox}{ 0{ } m 0{10} m }
{ nobeforeafter, colback=red!5!white, colframe=red!75!black, width=#2, height=#2/3*2,
  valign=center, #1 }
{ \foreach \n in {1,...,#3} { #4 } }

\multibox{5cm}{I shall not repeat.}
\multibox[colframe=blue!75!white]{5cm}[20]{I shall not repeat.}\\
\multibox[colback=yellow,height=5cm]{14cm}[100]{I shall not repeat.}
```

I shall not repeat. I shall  
not repeat. I shall not re-  
peat. I shall not repeat. I  
shall not repeat. I shall not  
repeat. I shall not repeat. I  
shall not repeat. I shall not  
repeat. I shall not repeat.

[illegible][illegible]
$$\backslash\text{NewTotalTCBoxFit}[\langle\textit{init options}\rangle]\{\backslash\langle\textit{name}\rangle\}\{\langle\textit{specification}\rangle\}\{\langle\textit{options}\rangle\}\{\langle\textit{content}\rangle\}$$

Operates like `\DeclareTotalTCBoxFit`, but based on `\NewDocumentCommand` instead of `\DeclareDocumentCommand`. An error is issued if `\langle name \rangle` has already been defined.

```
\RenewTotalTCBoxFit[\langle init options \rangle]{\langle name \rangle}{\langle specification \rangle}{\langle options \rangle}{\langle content \rangle}
```

Operates like `\DeclareTotalTCBoxFit`, but based on `\RenewDocumentCommand` instead of `\DeclareDocumentCommand`. An existing command is redefined.

$$\backslash\text{ProvideTotalTCBoxFit}[\langle\textit{init options}\rangle][\backslash\langle\textit{name}\rangle][\langle\textit{specification}\rangle][\langle\textit{options}\rangle][\langle\textit{content}\rangle]$$




Operates like `\DeclareTotalTCBoxFit`, but based on `\ProvideDocumentCommand` instead of `\DeclareDocumentCommand`. The command `\langle name \rangle` is only created if it is not already defined.

## 19 Library documentation

This library has the single purpose to support L<sup>A</sup>T<sub>E</sub>X package documentations like this one. Actually, the visual nature follows the approach from Till Tantau's `pgf` [20] documentation. Typically, this library is assumed to be used in conjunction with the class `ltxdoc` or alike.

The library is loaded by a package option or inside the preamble by:

```
\tcbuselibrary{documentation}
```

This also loads the library  `listings`, see Section 13 on page 232, the library  `skins`, see Section 9 on page 117, the library  `xparse`, see Section 18 on page 335, and a bunch of packages, namely `doc`, `pifont`, `marvosym`, `makeidx`, `marginnote`, `refcount`, and `hyperref`.

The package `makeidx` is loaded only, if `\printindex` is *not* already defined. Therefore, one can include an alternative to `makeidx` like `imakeidx` *before* the library documentation is used.

For UTF-8 support, load:

```
\tcbuselibrary{listingsutf8,documentation}
```

For minted [14] support, load:

```
\tcbuselibrary{documentation,minted}  
\tcbset{listing engine=minted}
```

### 19.1 Macros of the Library

```
\begin{docCommand}[<options>]{<name>}{<parameters>}  
  <command description>  
\end{docCommand}
```

Documents a L<sup>A</sup>T<sub>E</sub>X macro with given `<name>` where `<name>` is written without backslash. The given `<options>` are set with `\tcbset`<sup>→ P. 12</sup>. This macro takes mandatory or optional `<parameters>`. It is automatically indexed and can be referenced with `\refCom`<sup>→ P. 355</sup>{`<name>`}.

```
\begin{docCommand}{foomakedocSubKey}{\marg{name}\marg{key path}}  
  Creates a new environment \meta{name} based on \refEnv{docKey} for the  
  documentation of keys with the given \meta{key path}.  
\end{docCommand}
```

```
\foomakedocSubKey{<name>}{<key path>}  
  Creates a new environment <name> based on docKey→ P. 349 for the documentation of keys with  
  the given <key path>.
```

```
\begin{docCommand}[color definition=blue]{foomakedocSubKey*}%  
  {\marg{name}\marg{key path}}  
  Creates a new environment \meta{name} based on \refEnv{docKey} for the  
  documentation of keys with the given \meta{key path}.  
\end{docCommand}
```

```
\foomakedocSubKey*{<name>}{<key path>}  
  Creates a new environment <name> based on docKey→ P. 349 for the documentation of keys with  
  the given <key path>.
```

```
\begin{docCommand*}[\langle options \rangle]{\langle name \rangle}{\langle parameters \rangle}
  \langle command description \rangle
\end{docCommand*}
```

Identical to `docCommand`<sup>→ P. 348</sup>, but without index entry.

```
\begin{docEnvironment}[\langle options \rangle]{\langle name \rangle}{\langle parameters \rangle}
  \langle environment description \rangle
\end{docEnvironment}
```

Documents a L<sup>A</sup>T<sub>E</sub>X environment with given  $\langle name \rangle$ . The given  $\langle options \rangle$  are set with `\tcbsset`<sup>→ P. 12</sup>. This environment takes mandatory or optional  $\langle parameters \rangle$ . It is automatically indexed and can be referenced with `\refEnv`<sup>→ P. 355</sup> $\{\langle name \rangle\}$ .

```
\begin{docEnvironment}{foocolorbox}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

```
\begin{foocolorbox}[\langle options \rangle]
  \langle environment content \rangle
\end{foocolorbox}
```

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

```
\begin{docEnvironment}%
  [doclang/environment content=My content text]%
  {foocolorbox*}{\oarg{options}}
  This is the main environment to create an accentuated colored text box with
  rounded corners and, optionally, two parts.
\end{docEnvironment}
```

```
\begin{foocolorbox*}[\langle options \rangle]
  \langle My content text \rangle
\end{foocolorbox*}
```

This is the main environment to create an accentuated colored text box with rounded corners and, optionally, two parts.

```
\begin{docEnvironment*}[\langle options \rangle]{\langle name \rangle}{\langle parameters \rangle}
  \langle environment description \rangle
\end{docEnvironment*}
```

Identical to `docEnvironment`, but without index entry.

U 2014-09-29

```
\begin{docKey}[\langle key path \rangle][\langle options \rangle]{\langle name \rangle}{\langle parameters \rangle}{\langle description \rangle}
  \langle key description \rangle
\end{docKey}
```

Documents a key with given  $\langle name \rangle$  and an optional  $\langle key path \rangle$ . The given  $\langle options \rangle$  are set with `\tcbsset`<sup>→ P. 12</sup>. This key takes mandatory or optional  $\langle parameters \rangle$  as value with a short  $\langle description \rangle$ . It is automatically indexed and can be referenced with `\refKey`<sup>→ P. 356</sup> $\{\langle name \rangle\}$ .

```
\begin{docKey}[foo]{footitle}{=\meta{text}}{no default, initially empty}
  Creates a heading line with \meta{text} as content.
\end{docKey}
```

```
/foo/footitle=\langle text \rangle (no default, initially empty)
  Creates a heading line with  $\langle text \rangle$  as content.
```



```
\begin{docKey*}[\langle key path \rangle][\langle options \rangle]{\langle name \rangle}{\langle parameters \rangle}{\langle description \rangle}
  \langle key description \rangle
\end{docKey*}
```

Identical to `\docKey`<sup>P. 349</sup>, but without index entry.

```
\docValue{\langle name \rangle}
```

Documents a value with given  $\langle name \rangle$ . Typically, this is a value for a key. This value is automatically indexed.

A feasible value for `\refKey{/foo/footitle}` is `\docValue{foovalue}`.

A feasible value for `/foo/footitle`<sup>P. 349</sup> is `foovalue`.

```
\docValue*{\langle name \rangle}
```

Identical to `\docValue`, but without index entry.

```
\docAuxCommand{\langle name \rangle}
```

Documents an auxiliary or minor L<sup>A</sup>T<sub>E</sub>X macro with given  $\langle name \rangle$  where  $\langle name \rangle$  is written without backslash. This macro is automatically indexed.

The macro `\docAuxCommand{fooaux}` holds some interesting data.

The macro `\fooaux` holds some interesting data.

```
\docAuxCommand*{\langle name \rangle}
```

Identical to `\docAuxCommand`, but without index entry.

```
\docAuxEnvironment{\langle name \rangle}
```

Documents an auxiliary or minor L<sup>A</sup>T<sub>E</sub>X environment with given  $\langle name \rangle$ . This macro is automatically indexed.

The environment `\docAuxEnvironment{fooauxenv}` holds some interesting data.

The environment `fooauxenv` holds some interesting data.

```
\docAuxEnvironment*[\langle key path \rangle]{\langle name \rangle}
```

Identical to `\docAuxEnvironment`, but without index entry.

```
\docAuxKey[\langle key path \rangle]{\langle name \rangle}
```

Documents an auxiliary key with given  $\langle name \rangle$  and an optional  $\langle key path \rangle$ . It is automatically indexed.

The key `\docAuxKey[foo]{fooaux}` holds some interesting data.

The key `/foo/fooaux` holds some interesting data.

```
\docAuxKey*[\langle key path \rangle]{\langle name \rangle}
```

Identical to `\docAuxKey`, but without index entry.

N 2015-01-08

**\docCounter**{*<name>*}

Documents a counter with given *<name>*. The counter is automatically indexed.

The counter **\docCounter**{foocounter} can be used for computation.

The counter **foocounter** can be used for computation.

N 2015-01-08

**\docCounter\***{*<name>*}

Identical to **\docCounter**, but without index entry.

N 2015-01-08

**\docLength**{*<name>*}

Documents a counter with given *<name>*. The counter is automatically indexed.

The length **\docLength**{foolength} can be used for computation.

The length **\foolength** can be used for computation.

N 2015-01-08

**\docLength\***{*<name>*}

Identical to **\docLength**, but without index entry.

**\docColor**{*<name>*}

Documents a color with given *<name>*. The color is automatically indexed.

The color **\docColor**{foocolor} is available.

The color **foocolor** is available.

**\docColor\***{*<name>*}

Identical to **\docColor**, but without index entry.

### `\cs{<name>}`

Macro from `ltxdoc` [3] to typeset a command word `<name>` where the backslash is prefixed. The library overwrites the original macro.

```
This is a \cs{foocommand}.
```

```
This is a \foocommand.
```

### `\meta{<text>}`

Macro from `doc` [8] to typeset a meta `<text>`. The library overwrites the original macro.

```
This is a \meta{text}.
```

```
This is a <text>.
```

### `\marg{<text>}`

Macro from `ltxdoc` [3] to typeset a `<text>` with curly brackets as a mandatory argument. The library overwrites the original macro.

```
This is a mandatory \marg{argument}.
```

```
This is a mandatory {<argument>}.
```

### `\oarg{<text>}`

Macro from `ltxdoc` [3] to typeset a `<text>` with square brackets as an optional argument. The library overwrites the original macro.

```
This is an optional \oarg{argument}.
```

```
This is an optional [<argument>].
```

### `\brackets{<text>}`

Sets the given `<text>` with curly brackets.

```
Here we use \brackets{some text}.
```

```
Here we use {some text}.
```

```
\begin{dispExample}
  <environment content>
\end{dispExample}
```

Creates a colored box based on a `tcolorbox`<sup>→P.11</sup>. It displays the environment content as source code in the upper part and as compiled text in the lower part of the box. The appearance is controlled by `/tcb/documentation listing style`<sup>→P.358</sup> and the style `/tcb/docexample`<sup>→P.358</sup>. It may be changed by redefining this style.

```
\begin{dispExample}
This is a \LaTeX\ example.
\end{dispExample}
```

This is a \LaTeX\ example.

This is a L<sup>A</sup>T<sub>E</sub>X example.

```
\begin{dispExample*}{<options>}
  <environment content>
\end{dispExample*}
```

The starred version of `dispExample` takes `tcolorbox`<sup>→P.11</sup> `<options>` as parameter. These `<options>` are executed after `/tcb/docexample`<sup>→P.358</sup>.

```
\begin{dispExample*}{sidebyside}
This is a \LaTeX\ example.
\end{dispExample*}
```

This is a \LaTeX\ example.

This is a L<sup>A</sup>T<sub>E</sub>X example.

```
\begin{displisting}
  <environment content>
\end{displisting}
```

Creates a colored box based on a `tcolorbox`<sup>→ P. 11</sup>. It displays the environment content as source code. The appearance is controlled by `/tcb/documentation listing style`<sup>→ P. 358</sup> and the style `/tcb/docexample`<sup>→ P. 358</sup>. It may be changed by redefining this style.

```
\begin{displisting}
This is a \LaTeX\ example.
\end{displisting}
```

This is a `\LaTeX` example.

```
\begin{displisting*}[<options>]
  <environment content>
\end{displisting*}
```

The starred version of `displisting` takes `tcolorbox`<sup>→ P. 11</sup> `<options>` as parameter. These `<options>` are executed after `/tcb/docexample`<sup>→ P. 358</sup>.

```
\begin{displisting*}[title=My listing]
This is a \LaTeX\ example.
\end{displisting*}
```

My listing

This is a `\LaTeX` example.

```
\begin{absquote}
  <environment content>
\end{absquote}
```

Used to typeset an abstract as quoted and small text.

```
\begin{absquote}
|tcolorbox| provides an environment for colored and framed text boxes with a
heading line. Optionally, such a box can be split in an upper and a lower part.
\end{absquote}
```

`tcolorbox` provides an environment for colored and framed text boxes with a heading line. Optionally, such a box can be split in an upper and a lower part.

### `\tcbmakedocSubKey{⟨name⟩}{⟨key path⟩}`

Creates a new environment  $\langle name \rangle$  based on `\docKey`<sup>→ P. 349</sup> for the documentation of keys with the given  $\langle key path \rangle$  as default. The new environment  $\langle name \rangle$  takes the same parameters as `\docKey`<sup>→ P. 349</sup> itself. A second starred environment  $\langle name \rangle$  is also created, which is identical to  $\langle name \rangle$  but without index entry.

```
\tcbmakedocSubKey{docFooKey}{foo}

\begin{docFooKey}{foodummy}{=\meta{nothing}}{no default, initially empty}
Some key.
\end{docFooKey}

\begin{docFooKey*}{foo another dummy}{=\meta{nothing}}{no default, initially empty}
Some key (not indexed).
\end{docFooKey*}
```

`/foo/foodummy=⟨nothing⟩` (no default, initially empty)  
Some key.

`/foo/foo another dummy=⟨nothing⟩` (no default, initially empty)  
Some key (not indexed).

### `\refCom{⟨name⟩}`

References a documented L<sup>A</sup>T<sub>E</sub>X macro with given  $\langle name \rangle$  where  $\langle name \rangle$  is written without backslash. The page reference is suppressed if it links to the same page.

We have created `\refCom{foomakedocSubKey}` as an example.

We have created `\foomakedocSubKey`<sup>→ P. 348</sup> as an example.

### `\refCom*{⟨name⟩}`

References a documented L<sup>A</sup>T<sub>E</sub>X macro with given  $\langle name \rangle$  where  $\langle name \rangle$  is written without backslash. There is no page reference.

We have created `\refCom*{foomakedocSubKey}` as an example.

We have created `\foomakedocSubKey` as an example.

### `\refEnv{⟨name⟩}`

References a documented L<sup>A</sup>T<sub>E</sub>X environment with given  $\langle name \rangle$ . The page reference is suppressed if it links to the same page.

We have created `\refEnv{foocolorbox}` as an example.

We have created `foocolorbox`<sup>→ P. 349</sup> as an example.

### `\refEnv*{⟨name⟩}`

References a documented L<sup>A</sup>T<sub>E</sub>X environment with given  $\langle name \rangle$ . There is no page reference.

We have created `\refEnv*{foocolorbox}` as an example.

We have created `foocolorbox` as an example.

### `\refKey{⟨name⟩}`

References a documented key with given  $\langle name \rangle$  where  $\langle name \rangle$  is the full path name of the key. The page reference is suppressed if it links to the same page.

We have created `\refKey{/foo/footitle}` as an example.

We have created `/foo/footitle`<sup>→ P. 349</sup> as an example.

### `\refKey*{⟨name⟩}`

References a documented key with given  $\langle name \rangle$  where  $\langle name \rangle$  is the full path name of the key. There is no page reference.

We have created `\refKey*{/foo/footitle}` as an example.

We have created `/foo/footitle` as an example.

### `\refAux{⟨name⟩}`

References some auxiliary environment, key, value, or color. The hyperlink color is used, but there is no real link.

Some pages back, one can see `\refAux{/foo/footitle}` as an example.

Some pages back, one can see `/foo/footitle` as an example.

### `\refAuxcs{⟨name⟩}`

References some auxiliary macro  $\langle name \rangle$  where  $\langle name \rangle$  is written without backslash. The hyperlink color is used, but there is no real link.

Some pages back, one can see `\refAuxcs{fooaux}` as an example.

Some pages back, one can see `\fooaux` as an example.

### `\colDef{⟨text⟩}`

Sets  $\langle text \rangle$  with the command color, see `/tcb/color command`<sup>→ P. 360</sup>.

This is my `\colDef{text}`.

This is my `text`.

### `\colOpt{⟨text⟩}`

Sets  $\langle text \rangle$  with the option color, see `/tcb/color option`<sup>→ P. 360</sup>.

This is my `\colOpt{text}`.

This is my `text`.



**N** 2014-09-19 `\tcbdocmarginnote`[*<options>*]{*<text>*}

Creates a `tcolorbox` note with the given *<text>* inside the margin using the `marginnote` package. The style of the `tcolorbox` is predefined and can be altered by `/tcb/docmarginnote`<sup>→ P. 364</sup> and the given *<options>*.

Some text\tcbdocmarginnote{Note A}  
which is commented by a note inside the margin.  
Alternatively to |\tcbdocmarginnote|, you can always use  
|\marginnote| with a |tcolorbox| directly.\par  
This is further text%  
\tcbdocmarginnote[colframe=blue!50!white,colback=blue!5!white]{Note B}  
with another note.

Note A  
Some text which is commented by a note inside the margin. Alternatively to \tcbdocmarginnote,  
you can always use \marginnote with a tcolorbox directly.  
Note B  
This is further text with another note.

**N** 2014-09-19 `\tcbdocnew`{*<date>*}

Auxiliary macro which typesets the `/tcb/doclang/new`<sup>→ P. 361</sup> text with the given *<date>*. It may be redefined for customization.

New:  
1978-02-09

\tcbdocnew{1981-10-29}.  
% Next one is displayed in the margin:  
\tcbdocmarginnote{\tcbdocnew{1978-02-09}}

New: 1981-10-29.

**N** 2014-09-19 `\tcbdocupdated`{*<date>*}

Auxiliary macro which typesets the `/tcb/doclang/updated`<sup>→ P. 361</sup> text with the given *<date>*. It may be redefined for customization.

\tcbdocupdated{2014-09-19}.

Updated: 2014-09-19.

## 19.2 Option Keys of the Library

**/tcb/docexample** (style, no value)

Sets the style for `dispExample`<sup>→ P. 353</sup> and `dispListing`<sup>→ P. 354</sup> with the colors `ExampleBack` and `ExampleFrame`. To change the appearance of the examples, this style can be redefined.

**/tcb/documentation listing options**=*<key list>* (no default, initially `style=tcbdocumentation`)

Sets the options from the package `listings` [6]. They are used inside `dispExample`<sup>→ P. 353</sup> and `dispListing`<sup>→ P. 354</sup> to typeset the listings. Note that this is not identical to the key `/tcb/listing options`<sup>→ P. 239</sup> which is used for 'normal' listings.

Used for `/tcb/listing engine`<sup>→ P. 244</sup>=`listings` only.

**/tcb/documentation listing style**=*<listing style>* (no default, initially `tcbdocumentation`)

Abbreviation for `documentation listing options={style=...}`. This key sets a *<style>* for the `listings` package, see [6]. Note that this is not identical to the key `/tcb/listing style`<sup>→ P. 239</sup> which is used for 'normal' listings.

Used for `/tcb/listing engine`<sup>→ P. 244</sup>=`listings` only.

**/tcb/documentation minted style**=*<key list>* (no default, initially unset)

Sets a *<style>* known to `Pygments` [12] for the package `minted` [14], if used. Note that this is not identical to the key `/tcb/minted style`<sup>→ P. 243</sup> which is used for 'normal' listings.

Used for `/tcb/listing engine`<sup>→ P. 244</sup>=`minted` only.

**/tcb/documentation minted options**=*<minted style>* (no default, initially `tabsize=2, fontsize=\small`)

Sets the options from the package `minted` [14] which are used during typesetting of the listing, if used. Note that this is not identical to the key `/tcb/minted options`<sup>→ P. 242</sup> which is used for 'normal' listings.

Used for `/tcb/listing engine`<sup>→ P. 244</sup>=`minted` only.

**/tcb/before example**=*<macros>* (no default, initially `\par\smallskip`)

Sets the *<macros>* which are executed before `dispExample`<sup>→ P. 353</sup> and `dispListing`<sup>→ P. 354</sup> additional to `/tcb/before`<sup>→ P. 72</sup>.

**/tcb/after example**=*<macros>* (no default, initially empty)

Sets the *<macros>* which are executed after `dispExample`<sup>→ P. 353</sup> and `dispListing`<sup>→ P. 354</sup> additional to `/tcb/after`<sup>→ P. 72</sup>.

**/tcb/index command**= $\langle macro \rangle$  (no default, initially `\index`)

Replaces the internally used `\index` macro by the given  $\langle macro \rangle$ . The  $\langle macro \rangle$  has to take one mandatory argument like `\index`. This option is mutually exclusive with `/tcb/index command name`.

```
\tcbset{index command=\myindexcommand}
```

**/tcb/index command name**= $\langle name \rangle$  (no default, initially unset)

Replaces the internally used `\index` macro by `\index[\langle name \rangle]`, i.e. `\index{...}` is replaced by `\index[\langle name \rangle]{...}`. This option is intended to be used with `imakeidx` and is mutually exclusive with `/tcb/index command`.

```
\tcbset{index command name=mydoc}
```

**/tcb/index format**= $\langle format \rangle$  (no default, initially `pgf`)

Determines the basic  $\langle format \rangle$  of the generated index. Feasible values are:

- **pgfsection**: The index is formatted like in the `pgf` documentation (as a section).
- **pgfchapter**: The index is formatted like in the `pgf` documentation (as a chapter).
- **pgf**: Alias for `pgfsection`.
- **doc**: The index is assumed to be formatted by `doc` or `ltxdoc`. The usage of `makeindex` with `-s gind.ist` is assumed. The package `hypdoc` has to be loaded *before* `tcolorbox`.
- **off**: The index is not formatted by `tcolorbox`. Use this, if the index is formatted by other package like `imakeidx`.

**/tcb/index actual**= $\langle character \rangle$  (no default, initially `@`)

Sets the character for 'actual' in automatic indexing.

**/tcb/index quote**= $\langle character \rangle$  (no default, initially `"`)

Sets the character for 'quote' in automatic indexing.

**/tcb/index level**= $\langle character \rangle$  (no default, initially `!`)

Sets the character for 'level' in automatic indexing.

**/tcb/index default settings** (style, no value)

Sets the `makeindex` default values for `/tcb/index actual`, `/tcb/index quote`, and `/tcb/index level`.

**/tcb/index german settings** (style, no value)

Sets the `makeindex` values recommended for German language texts. This is identical to setting the following:

```
\tcbset{index actual={=},index quote={!},index level={>}}
```

`/tcb/index annotate=true|false` (default `true`, initially `true`)

If set to `true`, the index entries are annotated with short descriptions given by `/tcb/doclang/environment`<sup>→ P. 361</sup>, `/tcb/doclang/key`<sup>→ P. 361</sup>, and others.

`/tcb/index colorize=true|false` (default `true`, initially `false`)

If set to `true`, the index entries colorized according to the color settings given by `/tcb/color environment`, `/tcb/color key`, and others.

`/tcb/color command=<color>` (no default, initially `Definition`)

Sets the highlight color used by macro definitions.

`/tcb/color environment=<color>` (no default, initially `Definition`)

Sets the highlight color used by environment definitions.

`/tcb/color key=<color>` (no default, initially `Definition`)

Sets the highlight color used by key definitions.

`/tcb/color value=<color>` (no default, initially `Definition`)

Sets the highlight color used by value definitions.

N 2015-01-08

`/tcb/color counter=<color>` (no default, initially `Definition`)

Sets the highlight color used by counter definitions.

N 2015-01-08

`/tcb/color length=<color>` (no default, initially `Definition`)

Sets the highlight color used by length definitions.

`/tcb/color color=<color>` (no default, initially `Definition`)

Sets the highlight color used by color definitions.

`/tcb/color definition=<color>` (no default, initially `Definition`)

Sets the highlight color for `/tcb/color command`, `/tcb/color environment`, `/tcb/color key`, `/tcb/color value`, `/tcb/color counter`, `/tcb/color length`, and `/tcb/color color`.

`/tcb/color option=<color>` (no default, initially `Option`)

Sets the color used for optional arguments.

`/tcb/color hyperlink=<color>` (no default, initially `Hyperlink`)

Sets the color for all hyper-links, i. e. all internal and external links.

The following keys are provided for language specific settings. The English language is predefined.

**/tcb/english language** (style, no value)

Sets all language specific settings to English.

**/tcb/doclang/color**= $\langle text \rangle$  (no default, initially color)

Text used in the index for colors.

**/tcb/doclang/colors**= $\langle text \rangle$  (no default, initially Colors)

Heading text in the index for colors.

N 2015-01-08

**/tcb/doclang/counter**= $\langle text \rangle$  (no default, initially counter)

Text used in the index for counters.

N 2015-01-08

**/tcb/doclang/counters**= $\langle text \rangle$  (no default, initially Counters)

Heading text in the index for counters.

**/tcb/doclang/environment**= $\langle text \rangle$  (no default, initially environment)

Text used in the index for environments.

**/tcb/doclang/environments**= $\langle text \rangle$  (no default, initially Environments)

Heading text in the index for environments.

**/tcb/doclang/environment content**= $\langle text \rangle$  (no default, initially environment content)

Text used in docEnvironment<sup>→ P. 349</sup>.

**/tcb/doclang/index**= $\langle text \rangle$  (no default, initially Index)

Heading text for the index.

**/tcb/doclang/key**= $\langle text \rangle$  (no default, initially key)

Text used in the index for keys.

**/tcb/doclang/keys**= $\langle text \rangle$  (no default, initially Keys)

Heading text used in the index for keys.

N 2015-01-08

**/tcb/doclang/length**= $\langle text \rangle$  (no default, initially length)

Text used in the index for lengths.

N 2015-01-08

**/tcb/doclang/lengths**= $\langle text \rangle$  (no default, initially Lengths)

Heading text in the index for lengths.

N 2014-09-19

**/tcb/doclang/new**= $\langle text \rangle$  (no default, initially New)

Announcement text for new content.

**/tcb/doclang/pageshort**= $\langle text \rangle$  (no default, initially P.)

Short text for page references.

N 2014-09-19

**/tcb/doclang/updated**= $\langle text \rangle$  (no default, initially Updated)

Announcement text for updated content.

**/tcb/doclang/value**= $\langle text \rangle$  (no default, initially value)

Text used in the index for values.

**/tcb/doclang/values**= $\langle text \rangle$  (no default, initially Values)

Heading text in the index for values.

`/tcb/doc left=<length>` (no default, initially 2em)

Sets the left hand offset of the documentation texts from `docCommand`<sup>→ P. 348</sup>, `docEnvironment`<sup>→ P. 349</sup>, `docKey`<sup>→ P. 349</sup>, etc, to `<length>`.

```
\begin{docCommand*}[doc left=2cm,doc left indent=-2cm]{myCommandA}{\marg{argument}}
  This is the documentation of \refCom{myCommandA} which takes one \meta{argument}.
  \refCom{myCommandA} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandA{<argument>}
  This is the documentation of \myCommandA which takes one <argument>. \myCommandA
  does some funny things with its <argument>.
```

`/tcb/doc right=<length>` (no default, initially 0em)

Sets the right hand offset of the documentation texts from `docCommand`<sup>→ P. 348</sup>, `docEnvironment`<sup>→ P. 349</sup>, `docKey`<sup>→ P. 349</sup>, etc, to `<length>`.

```
\begin{docCommand*}[doc right=2cm]{myCommandB}{\marg{argument}}
  This is the documentation of \refCom{myCommandB} which takes one \meta{argument}.
  \refCom{myCommandB} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandB{<argument>}
  This is the documentation of \myCommandB which takes one <argument>.
  \myCommandB does some funny things with its <argument>.
```

`/tcb/doc left indent=<length>` (no default, initially -2em)

Sets the left hand indent of documentation heads from `docCommand`<sup>→ P. 348</sup>, `docEnvironment`<sup>→ P. 349</sup>, `docKey`<sup>→ P. 349</sup>, etc, to `<length>`.

```
\begin{docCommand*}[doc left indent=2cm]{myCommandC}{\marg{argument}}
  This is the documentation of \refCom{myCommandC} which takes one \meta{argument}.
  \refCom{myCommandC} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandC{<argument>}
  This is the documentation of \myCommandC which takes one <argument>. \myCommandC does some
  funny things with its <argument>.
```

`/tcb/doc right indent=<length>` (no default, initially 0pt)

Sets the right hand indent of documentation heads from `docCommand`<sup>→ P. 348</sup>, `docEnvironment`<sup>→ P. 349</sup>, `docKey`<sup>→ P. 349</sup>, etc, to `<length>`.

```
\begin{docCommand*}[doc right indent=-10mm,doc right=10mm,
  doc description=test value]{myCommandD}{\marg{argument}}
  This is the documentation of \refCom{myCommandD} which takes one \meta{argument}.
  \refCom{myCommandD} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandD{<argument>} (test value)
  This is the documentation of \myCommandD which takes one <argument>. \myCommandD
  does some funny things with its <argument>.
```

The head lines of the main documentation environments `docCommand`<sup>→ P. 348</sup>, `docEnvironment`<sup>→ P. 349</sup>, `docKey`<sup>→ P. 349</sup>, etc, are set inside `tcolorboxes`. Options to these `tcolorboxes` can be given using the following keys.

**/tcb/doc head command**=*<options>* (no default, initially empty)

Sets *<options>* for the head line of `docCommand`<sup>→ P. 348</sup> and `docCommand*`<sup>→ P. 349</sup>.

```
\tcbset{doc head command={interior style={fill,left color=red!20!white,
right color=blue!20!white}}}

\begin{docCommand*}{myCommandE}{\marg{argument}}
  This is the documentation of \refCom{myCommandE} which takes one \meta{argument}.
  \refCom{myCommandE} does some funny things with its \meta{argument}.
\end{docCommand*}
```

---

```
\myCommandE{<argument>}
  This is the documentation of \myCommandE which takes one <argument>. \myCommandE does some
  funny things with its <argument>.
```

**/tcb/doc head environment**=*<options>* (no default, initially empty)

Sets *<options>* for the head line of `docEnvironment`<sup>→ P. 349</sup> and `docEnvironment*`<sup>→ P. 349</sup>.

```
\tcbset{doc head environment={beamer,boxsep=2pt,arc=2pt,colback=green!20!white,
after=\par\smallskip}}

\begin{docEnvironment*}{myEnvironment}{\marg{argument}}
  This is the documentation of \refEnv{myEnvironment} which
  takes one \meta{argument}.
\end{docEnvironment*}
```

---

```
\begin{myEnvironment}{<argument>}
  <environment content>
\end{myEnvironment}
```

This is the documentation of `myEnvironment` which takes one *<argument>*.

**/tcb/doc head key**=*<options>* (no default, initially empty)

Sets *<options>* for the head line of `docKey`<sup>→ P. 349</sup> and `docKey*`<sup>→ P. 350</sup>.

```
\tcbset{doc head key={boxsep=4pt,arc=4pt,boxrule=0.6pt,
frame style=fill,interior style=fill,colframe=green!50!black}}

\begin{docKey*}{/foo/myKey}{\no value}
  This is the documentation of \refKey{/foo/myKey}.
\end{docKey*}
```

---

```
/foo/myKey (no value)
```

This is the documentation of `/foo/myKey`.

**/tcb/doc head**=*<options>* (no default, initially empty)

Shortcut for setting the same *<options>* for `/tcb/doc head command`, `/tcb/doc head environment`, and `/tcb/doc head key`.



**/tcb/doc description=** $\langle text \rangle$  (no default, initially empty)  
 Sets a (short!) additional description  $\langle text \rangle$  for `docCommand`<sup>→ P. 348</sup> or `docEnvironment`<sup>→ P. 349</sup>.  
 Such a description is mandatory for `docKey`<sup>→ P. 349</sup>.

```
\begin{docCommand*}[doc description=my description]{myCommandF}{\marg{argument}}
  This is the documentation of \refCom{myCommandF} which takes one \meta{argument}.
  \refCom{myCommandF} does some funny things with its \meta{argument}.
\end{docCommand*}
```

```
\myCommandF{<argument>} (my description)
  This is the documentation of \myCommandF which takes one <argument>. \myCommandF does some
  funny things with its <argument>.
```

Note that the description  $\langle text \rangle$  may overlap with the text on the left hand side if too long. Linebreaks can be used inside the  $\langle text \rangle$ .

**/tcb/doc into index=true|false** (default `true`, initially `true`)  
 If set to `false`, no index entries are written for the main documentation environments. The same effect is achieved by using e.g. `docCommand*`<sup>→ P. 349</sup> instead of `docCommand`<sup>→ P. 348</sup>.

N 2014-09-19

**/tcb/doc marginnote=** $\langle options \rangle$  (no default, initially empty)  
 Sets style  $\langle options \rangle$  for the displayed box of the `\tcbdocmarginnote`<sup>→ P. 357</sup> command.

```
\tcbset{doc marginnote={colframe=blue!50!white,colback=blue!5!white}}%
This is some text\tcbdocmarginnote{Note A}
which is commented by a note inside the margin.
```

Note A

This is some text which is commented by a note inside the margin.

N 2014-09-19

**/tcb/doc new=** $\langle date \rangle$  (style, no default)  
 Adds a a marginnote with a 'New:  $\langle data \rangle$ ' message at the beginning of the upper box part. The intended use is inside the option list of `docCommand`<sup>→ P. 348</sup>, `docEnvironment`<sup>→ P. 349</sup>, etc.

```
\begin{docCommand}[doc new=2000-01-01]{foosomething}{\marg{text}}
Some command for something.
\end{docCommand}
```

New:  
2000-01-01

```
\foosomething{<text>}
  Some command for something.
```

N 2014-09-19

**/tcb/doc updated=** $\langle date \rangle$  (style, no default)  
 Adds a marginnote with a 'Updated:  $\langle data \rangle$ ' message at the beginning of the upper box part. See `/tcb/doc new`.

N 2014-09-19

**/tcb/doc new and updated=** $\{ \langle new date \rangle \} \{ \langle update date \rangle \}$  (style, no default)  
 Adds a marginnote with 'New:  $\langle new date \rangle$ ' and 'Updated:  $\langle update data \rangle$ ' messages at the beginning of the upper box part. See `/tcb/doc new`.

## 19.3 Predefined Colors of the Library


The following colors are predefined. They are used as default colors in some library commands.

Option , Definition , ExampleFrame , ExampleBack , Hyperlink .

## A Picture Credits

The following pictures were used inside this documentation.

Basilica\_5.png



[http://commons.wikimedia.org/wiki/File:Basilica\\_5.png](http://commons.wikimedia.org/wiki/File:Basilica_5.png)

lichtspiel.jpg




Photograph taken by Thomas F. Sturm.

crinklepaper.png




Created with GIMP.  
<http://www.gimp.org>

pink\_marble.png




Created with GIMP.  
<http://www.gimp.org>

blueshade.png



Created with GIMP.  
<http://www.gimp.org>

goldshade.png



Created with GIMP.  
<http://www.gimp.org>

## References

- [1] Donald Arseneau. *The varwidth package*. Sept. 26, 2011.  
[mirrors.ctan.org/macros/latex/contrib/varwidth/varwidth-doc.pdf](http://mirrors.ctan.org/macros/latex/contrib/varwidth/varwidth-doc.pdf).
- [2] Peter Breitenlohner. *The  $\varepsilon$ -T<sub>E</sub>X manual*. Version 2. Feb. 1998.  
[http://ftp.gwdg.de/pub/ctan/systems/e-tex/v2/doc/etex\\_man.pdf](http://ftp.gwdg.de/pub/ctan/systems/e-tex/v2/doc/etex_man.pdf).
- [3] David Carlisle. *The file ltxdoc.dtx for use with L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>*. Nov. 11, 2007.  
<http://mirror.ctan.org/macros/latex/base/ltxdoc.dtx>.
- [4] David Carlisle. *The tabularx package*. May 13, 2014.  
<http://mirror.ctan.org/macros/latex/required/tools/tabularx.pdf>.
- [5] Toby Cubitt. *The cleveref Package*. Mar. 22, 2013.  
<http://mirror.ctan.org/macros/latex/contrib/cleveref/cleveref.pdf>.
- [6] Carsten Heinz, Brooks Moses, and Jobst Hoffmann. *The Listings Package*. Version 1.5b. Aug. 26, 2013.  
<http://mirror.ctan.org/macros/latex/contrib/listings/listings.pdf>.
- [7] Philipp Lehman. *The etoolbox Package*. Jan. 3, 2011.  
<http://mirror.ctan.org/macros/latex/contrib/etoolbox/etoolbox.pdf>.
- [8] Frank Mittelbach. *The doc and shortvrb Packages*. June 30, 2011.  
<http://mirror.ctan.org/macros/latex/base/doc.dtx>.
- [9] Frank Mittelbach. *An environment for multicolumn output*. June 21, 2014.  
<http://mirror.ctan.org/macros/latex/required/tools/multicol.pdf>.
- [10] Heiko Oberdiek. *The listingsutf8 package*. Nov. 10, 2011.  
<http://mirror.ctan.org/macros/latex/contrib/oberdiek/listingsutf8.pdf>.
- [11] The L<sup>A</sup>T<sub>E</sub>X3 Project. *The xparse Package*. Dec. 31, 2013.  
<http://mirror.ctan.org/macros/latex/contrib/l3packages/xparse.pdf>.
- [12] *Pygments. Python syntax highlighter*. 2013.  
<http://pygments.org/>.
- [13] Will Robertson. *A couple of things involving environments*. Apr. 1, 2013.  
<http://mirror.ctan.org/macros/latex/contrib/envron/envron.pdf>.
- [14] Konrad Rudolph. *The minted package. Highlighted source code in L<sup>A</sup>T<sub>E</sub>X*. Sept. 17, 2011.  
<http://mirror.ctan.org/macros/latex/contrib/minted/minted.pdf>.
- [15] Rainer Schöpf, Bernd Raichle, and Chris Rowley. *A New Implementation of L<sup>A</sup>T<sub>E</sub>X's verbatim and verbatim\* Environments*. Mar. 12, 2001.  
<http://mirror.ctan.org/macros/latex/required/tools/verbatim.pdf>.
- [16] Thomas F. Sturm. *Mathematik 1 (B.Eng.) Vorlesungs-Skriptum*. Neubiberg: Universität der Bundeswehr München, 2007.  
<http://www.unibw.de/bw/sturm>.
- [17] Thomas F. Sturm. *Mathematik 2 (B.Eng.) Vorlesungs-Skriptum*. Neubiberg: Universität der Bundeswehr München, 2008.  
<http://www.unibw.de/bw/sturm>.
- [18] Thomas F. Sturm. *Höhere Mathematik: Fortgeschrittene mathematische Methoden (M.Eng.) Vorlesungs-Skriptum*. Neubiberg: Universität der Bundeswehr München, 2010.  
<http://www.unibw.de/bw/sturm>.
- [19] Thomas F. Sturm. *L<sup>A</sup>T<sub>E</sub>X – Einführung in das Textsatzsystem*. 10th edition. RRZN-Handbücher. Hannover: Regionales Rechenzentrum für Niedersachsen (RRZN), Mar. 2014.  
<http://www.rrzn.uni-hannover.de/buch.html?&titel=latex>.
- [20] Till Tantau. *The TikZ and PGF Packages. Manual for version 3.0.0*. Dec. 20, 2013.  
<http://sourceforge.net/projects/pgf/>.

- [21] Kresten Krab Thorub, Frank Jensen, and Chris Rowley. *The calc package – Infix notation arithmetic in L<sup>A</sup>T<sub>E</sub>X*. Aug. 22, 2007.  
<http://mirror.ctan.org/macros/latex/required/tools/>.

# Index

- `absquote` environment, 354
- `add to height` key, 47
- `add to list` key, 89
- `add to width` key, 28
- `adjust text` key, 17
- `adjusted title` key, 17
- `adjusted title after break` key, 297
- `after` key, 72
- `after app` key, 327
- `after example` key, 358
- `after lower` key, 53
- `after lower app` key, 327
- `after lower pre` key, 327
- `after pre` key, 327
- `after skip` key, 74
- `after title` key, 52
- `after title app` key, 326
- `after title pre` key, 326
- `after upper` key, 53
- `after upper app` key, 326
- `after upper pre` key, 326
- `all` key, 9
- `all` value, 40, 41, 229, 299, 301
- `ams align` key, 282
- `ams align lower` key, 282
- `ams align upper` key, 282
- `ams align*` key, 282
- `ams align* lower` key, 282
- `ams align* upper` key, 282
- `ams equation` key, 281
- `ams equation lower` key, 281
- `ams equation upper` key, 281
- `ams equation*` key, 281
- `ams equation* lower` key, 281
- `ams equation* upper` key, 281
- `ams gather` key, 283
- `ams gather lower` key, 283
- `ams gather upper` key, 283
- `ams gather*` key, 283
- `ams gather* lower` key, 283
- `ams gather* upper` key, 283
- `ams nodisplayskip` key, 284
- `ams nodisplayskip lower` key, 284
- `ams nodisplayskip upper` key, 284
- `arc` key, 31
- `areaseize` value, 322
- `areaseize*` value, 322
- `at begin tikz` key, 156
- `at begin tikz reset` key, 156
- `at end tikz` key, 156
- `at end tikz reset` key, 156
- `attach boxed title to bottom center` key, 123
- `attach boxed title to bottom left` key, 123
- `attach boxed title to bottom right` key, 123
- `attach boxed title to top center` key, 123
- `attach boxed title to top left` key, 123
- `attach boxed title to top right` key, 123
- `attach title` key, 19
- `attach title to upper` key, 19
- `auto counter` key, 92
- `auto outer arc` key, 31
- `autoparskip` key, 72
- `base` value, 73
- `baseline` key, 73
- `baselineskip` value, 299
- `beamer` key, 186
- `beamer` Skin, 186
- `beamerfirst` Skin, 188
- `beamerlast` Skin, 190
- `beamermiddle` Skin, 189
- `before` key, 72
- `before app` key, 327
- `before example` key, 358
- `before lower` key, 53
- `before lower app` key, 327
- `before lower pre` key, 327
- `before nobreak` key, 75
- `before pre` key, 327
- `before skip` key, 74
- `before title` key, 52
- `before title app` key, 326
- `before title pre` key, 326
- `before upper` key, 52
- `before upper app` key, 326
- `before upper pre` key, 326
- `beforeafter skip` key, 74
- `bicolor` key, 181
- `bicolor` Skin, 181
- `bicolorfirst` Skin, 183
- `bicolorlast` Skin, 185
- `bicolormiddle` Skin, 184
- `blank` key, 170
- `blanker` key, 196
- `blend into` key, 96
- `borderline` key, 142
- `borderline east` key, 145
- `borderline horizontal` key, 146
- `borderline north` key, 145
- `borderline south` key, 145
- `borderline vertical` key, 146
- `borderline west` key, 145
- `bottom` key, 35
- `bottom` value, 49, 68, 73, 228
- `bottomrule` key, 29
- `bottomrule at break` key, 300
- `bottomsep at break` key, 300
- `bottomtitle` key, 35
- `box align` key, 73
- `boxed title style` key, 125

- boxrule key, 30
- boxsep key, 31
- \brackets, 352
- break value, 286
- break at key, 298
- breakable key, 8, 296
- broken value, 130–132
- capture key, 85
- center value, 49, 68, 73, 228
- center lower key, 54
- center title key, 54
- center upper key, 54
- change value, 286
- change apart value, 286
- change break value, 286
- change standard value, 285
- check odd page key, 89
- clip lower key, 141
- clip title key, 140
- clip upper key, 140
- clip watermark key, 136
- code key, 60
- colback key, 25
- colbacklower key, 182
- colbacktitle key, 25
- \colDef, 356
- colframe key, 25
- collower key, 26
- \colOpt, 356
- color key, 361
- color color key, 360
- color command key, 360
- color counter key, 360
- color definition key, 360
- color environment key, 360
- color hyperlink key, 360
- color key key, 360
- color length key, 360
- color option key, 360
- color value key, 360
- Colors
  - Definition, 364
  - ExampleBack, 364
  - ExampleFrame, 364
  - foocolor, 351
  - Hyperlink, 364
  - Option, 364
- colors key, 361
- coltext key, 26
- coltitle key, 26
- colupper key, 26
- comment key, 245
- comment above listing key, 251
- comment above\* listing key, 251
- comment and listing key, 247
- comment only key, 245
- comment outside listing key, 249
- comment side listing key, 249
- comment style key, 247
- compilable listing key, 255
- compress page key, 299
- counter key, 361
- Counters
  - foocounter, 351
- counters key, 361
- Crefname key, 95
- crefname key, 95
- \cs, 352
- \DeclareTCBInputListing, 345
- \DeclareTCBListing, 343
- \DeclareTCBox, 340
- \DeclareTCBoxFit, 346
- \DeclareTColorBox, 337
- \DeclareTotalTCBox, 341
- \DeclareTotalTCBoxFit, 347
- \DeclareTotalTColorBox, 339
- Definition color, 364
- description color key, 276
- description delimiters key, 276
- description delimiters none key, 276
- description delimiters parenthesis key, 276
- description font key, 277
- description formatter key, 277
- detach title key, 19
- dispExample environment, 353
- dispExample\* environment, 353
- displisting environment, 354
- displisting\* environment, 354
- doc value, 359
- doc description key, 364
- doc head key, 363
- doc head command key, 363
- doc head environment key, 363
- doc head key key, 363
- doc into index key, 364
- doc left key, 362
- doc left indent key, 362
- doc marginnote key, 364
- doc new key, 364
- doc new and updated key, 364
- doc right key, 362
- doc right indent key, 362
- doc updated key, 364
- \docAuxCommand, 350
- \docAuxCommand\*, 350
- \docAuxEnvironment, 350
- \docAuxEnvironment\*, 350
- \docAuxKey, 350
- \docAuxKey\*, 350
- \docColor, 351
- \docColor\*, 351
- docCommand environment, 348
- docCommand\* environment, 349
- \docCounter, 351
- \docCounter\*, 351
- docEnvironment environment, 349
- docEnvironment\* environment, 349



`docexample` key, 358  
`docKey` environment, 349  
`docKey*` environment, 350  
`\docLength`, 351  
`\docLength*`, 351  
`documentation` key, 8  
`documentation listing options` key, 358  
`documentation listing style` key, 358  
`documentation minted options` key, 358  
`documentation minted style` key, 358  
`\docValue`, 350  
`\docValue*`, 350  
`downhill` value, 40, 41  
`draft` key, 205  
`draft Skin`, 205  
`draftmode` key, 165  
`drop fuzzy midday shadow` key, 149  
`drop fuzzy shadow` key, 149  
`drop fuzzy shadow east` key, 153  
`drop fuzzy shadow north` key, 153  
`drop fuzzy shadow northeast` key, 153  
`drop fuzzy shadow northwest` key, 153  
`drop fuzzy shadow south` key, 152  
`drop fuzzy shadow southeast` key, 152  
`drop fuzzy shadow southwest` key, 152  
`drop fuzzy shadow west` key, 152  
`drop large lifted shadow` key, 155  
`drop lifted shadow` key, 154  
`drop midday shadow` key, 149  
`drop shadow` key, 149  
`drop shadow east` key, 152  
`drop shadow north` key, 151  
`drop shadow northeast` key, 152  
`drop shadow northwest` key, 151  
`drop shadow south` key, 151  
`drop shadow southeast` key, 151  
`drop shadow southwest` key, 151  
`drop shadow west` key, 151  
`drop small lifted shadow` key, 154  
  
`east` value, 40, 41  
`empty` key, 195  
`empty Skin`, 195  
`empty` value, 106, 107  
`emptyfirst Skin`, 197  
`emptylast Skin`, 199  
`emptymiddle Skin`, 198  
`enforce breakable` key, 297  
`english language` key, 361  
`enhanced` key, 168  
`enhanced Skin`, 168  
`enhanced jigsaw` key, 175  
`enhanced jigsaw Skin`, 175  
`enhanced standard` key, 170  
`enhancedfirst Skin`, 172  
`enhancedfirst jigsaw Skin`, 176  
`enhancedlast Skin`, 174  
`enhancedlast jigsaw Skin`, 180  
`enhancedmiddle Skin`, 173  
`enhancedmiddle jigsaw Skin`, 177  
  
`enlarge bottom at break by` key, 77  
`enlarge bottom by` key, 77  
`enlarge bottom finally by` key, 76  
`enlarge by` key, 78  
`enlarge left by` key, 77  
`enlarge right by` key, 77  
`enlarge top at break by` key, 77  
`enlarge top by` key, 77  
`enlarge top initially by` key, 76  
`enlargepage` key, 298  
`enlargepage flexible` key, 299  
`environment` key, 361  
`environment content` key, 361  
Environments  
    `absquote`, 354  
    `dispExample`, 353  
    `dispExample*`, 353  
    `dispListing`, 354  
    `dispListing*`, 354  
    `docCommand`, 348  
    `docCommand*`, 349  
    `docEnvironment`, 349  
    `docEnvironment*`, 349  
    `docKey`, 349  
    `docKey*`, 350  
    `fooauxenv`, 350  
    `foocolorbox`, 349  
    `foocolorbox*`, 349  
    `tcbclipframe`, 137  
    `tcbclipinterior`, 139  
    `tcbcliptitle`, 139  
    `tcbinvcclipframe`, 138  
    `tcbitemize`, 224  
    `tcblisting`, 233  
    `tcboutputlisting`, 235  
    `tcbrafter`, 223  
    `tcbverbatimwrite`, 98  
    `tcbwritetemp`, 98  
    `tcolorbox`, 11  
`environments` key, 361  
`equal height group` key, 50  
`evenpage` value, 38, 79  
`every box` key, 82  
`every box on higher layers` key, 83  
`every box on layer n` key, 83  
`every float` key, 67  
`every listing line` key, 240  
`every listing line*` key, 240  
`ExampleBack` color, 364  
`ExampleFrame` color, 364  
`extend freelance` key, 207  
`extend freelancefirst` key, 207  
`extend freelancelast` key, 207  
`extend freelancemiddle` key, 207  
`external` key, 90  
`extrude bottom by` key, 81  
`extrude by` key, 81  
`extrude left by` key, 80  
`extrude right by` key, 80



extrude top by key, 81  
 false value, 72, 75, 230, 296  
 fbox value, 36  
 figures value, 96  
 fill image opacity key, 218  
 fill image options key, 218  
 fill image scale key, 218  
 fill overzoom image key, 214  
 fill overzoom image\* key, 214  
 fill overzoom picture key, 214  
 fill plain image key, 212  
 fill plain image\* key, 212  
 fill plain picture key, 212  
 fill shrink image key, 216  
 fill shrink image\* key, 216  
 fill shrink picture key, 216  
 fill stretch image key, 213  
 fill stretch image\* key, 213  
 fill stretch picture key, 213  
 fill tile image key, 217  
 fill tile image\* key, 217  
 fill tile picture key, 217  
 fill tile picture\* key, 217  
 fill zoom image key, 215  
 fill zoom image\* key, 215  
 fill zoom picture key, 215  
 final value, 324  
 finish key, 161  
 finish broken key, 162  
 finish broken pre key, 333  
 finish first key, 162  
 finish first and middle key, 162  
 finish first and middle pre key, 333  
 finish first pre key, 333  
 finish last key, 162  
 finish last pre key, 333  
 finish middle key, 162  
 finish middle and last key, 162  
 finish middle and last pre key, 333  
 finish middle pre key, 333  
 finish pre key, 333  
 finish unbroken key, 162  
 finish unbroken and first key, 162  
 finish unbroken and first pre key, 333  
 finish unbroken and last key, 162  
 finish unbroken and last pre key, 333  
 finish unbroken pre key, 333  
 first value, 130–132, 301  
 first and middle value, 130, 301  
 fit key, 316  
 fit algorithm key, 322  
 fit basedim key, 317  
 fit fontsize macros key, 318  
 fit height from key, 321  
 fit height plus key, 319  
 fit maxfontdiff key, 324  
 fit maxfontdiffgap key, 324  
 fit maxstep key, 324  
 fit maxwidthdiff key, 324  
 fit maxwidthdiffgap key, 324  
 fit skip key, 317  
 fit to key, 317  
 fit to height key, 317  
 fit warning key, 324  
 fit width from key, 320  
 fit width plus key, 319  
 fitbox value, 85  
 fitting key, 8  
 float key, 66  
 float\* key, 66  
 floatplacement key, 66  
 flushleft lower key, 55  
 flushleft title key, 55  
 flushleft upper key, 55  
 flushright lower key, 56  
 flushright title key, 56  
 flushright upper key, 56  
 fontlower key, 27  
 fontsize value, 322  
 fontsize\* value, 322  
 fonttitle key, 27  
 fontupper key, 27  
 \fooaux, 350  
 fooaux key, 350  
 fooauxenv environment, 350  
 foocolor color, 351  
 foocolorbox environment, 349  
 foocolorbox\* environment, 349  
 foocounter counter, 351  
 foodummy key, 355  
 \foolength length, 351  
 \foomakedocSubKey, 348  
 \foomakedocSubKey\*, 348  
 \foosomething, 364  
 footitle key, 349  
 foovalue value, 350  
 forced value, 38, 79  
 frame code key, 109  
 frame code app key, 333  
 frame code pre key, 333  
 frame empty key, 109  
 frame engine key, 106  
 frame hidden key, 118  
 frame style key, 117  
 frame style image key, 117  
 frame style tile key, 118  
 freelance key, 207  
 freelance Skin, 207  
 freelance value, 106, 107  
 freelancefirst Skin, 207  
 freelancelast Skin, 207  
 freelancemiddle Skin, 207  
 fuzzy halo key, 150  
 fuzzy shadow key, 148  
 geometry nodes key, 108  
 graphical environment key, 105  
 graphics directory key, 211  
 graphics options key, 211

graphics pages key, 211  
grow to left by key, 78  
grow to right by key, 78

halo key, 150  
hbox key, 85  
hbox value, 85  
hbox boxed title key, 128  
height key, 45  
height fill key, 47  
height fixed for key, 301  
height from key, 46  
height plus key, 45  
highlight math key, 280  
highlight math style key, 280  
hooks key, 8  
hybrid value, 322  
hybrid\* value, 322  
Hyperlink color, 364  
hyphenationfix key, 87

IfBooleanTF key, 336  
IfNoValueTF key, 335  
IfValueTF key, 336  
ignore nobreak key, 75  
ignored value, 22  
image comment key, 245  
`\imagenname`, 209  
`\imagepage`, 210  
index key, 361  
index actual key, 359  
index annotate key, 360  
index colorize key, 360  
index command key, 359  
index command name key, 359  
index default settings key, 359  
index format key, 359  
index german settings key, 359  
index level key, 359  
index quote key, 359  
interior code key, 110  
interior code app key, 334  
interior code pre key, 334  
interior empty key, 110  
interior engine key, 107  
interior hidden key, 119  
interior style key, 118  
interior style image key, 119  
interior style tile key, 119  
interior titled code key, 109  
interior titled code app key, 333  
interior titled code pre key, 334  
interior titled empty key, 109  
interior titled engine key, 106  
invisible key, 21  
invisible value, 21, 22

key key, 361  
Keys  
/foo/

fooaux, 350  
foodummy, 355  
footitle, 349  
/tcb/  
add to height, 47  
add to list, 89  
add to width, 28  
adjust text, 17  
adjusted title, 17  
adjusted title after break, 297  
after, 72  
after app, 327  
after example, 358  
after lower, 53  
after lower app, 327  
after lower pre, 327  
after pre, 327  
after skip, 74  
after title, 52  
after title app, 326  
after title pre, 326  
after upper, 53  
after upper app, 326  
after upper pre, 326  
ams align, 282  
ams align lower, 282  
ams align upper, 282  
ams align\*, 282  
ams align\* lower, 282  
ams align\* upper, 282  
ams equation, 281  
ams equation lower, 281  
ams equation upper, 281  
ams equation\*, 281  
ams equation\* lower, 281  
ams equation\* upper, 281  
ams gather, 283  
ams gather lower, 283  
ams gather upper, 283  
ams gather\*, 283  
ams gather\* lower, 283  
ams gather\* upper, 283  
ams nodelayskip, 284  
ams nodelayskip lower, 284  
ams nodelayskip upper, 284  
arc, 31  
at begin tikz, 156  
at begin tikz reset, 156  
at end tikz, 156  
at end tikz reset, 156  
attach boxed title to bottom  
center, 123  
attach boxed title to bottom left,  
123  
attach boxed title to bottom right,  
123  
attach boxed title to top center,  
123  
attach boxed title to top left, 123

- attach boxed title to top right, 123
- attach title, 19
- attach title to upper, 19
- auto outer arc, 31
- autoparskip, 72
- baseline, 73
- beamer, 186
- before, 72
- before app, 327
- before example, 358
- before lower, 53
- before lower app, 327
- before lower pre, 327
- before nobreak, 75
- before pre, 327
- before skip, 74
- before title, 52
- before title app, 326
- before title pre, 326
- before upper, 52
- before upper app, 326
- before upper pre, 326
- beforeafter skip, 74
- bicolor, 181
- blank, 170
- blanker, 196
- borderline, 142
- borderline east, 145
- borderline horizontal, 146
- borderline north, 145
- borderline south, 145
- borderline vertical, 146
- borderline west, 145
- bottom, 35
- bottomrule, 29
- bottomrule at break, 300
- bottomsep at break, 300
- bottomtitle, 35
- box align, 73
- boxed title style, 125
- boxrule, 30
- boxsep, 31
- break at, 298
- breakable, 296
- capture, 85
- center lower, 54
- center title, 54
- center upper, 54
- check odd page, 89
- clip lower, 141
- clip title, 140
- clip upper, 140
- clip watermark, 136
- code, 60
- colback, 25
- colbacklower, 182
- colbacktitle, 25
- colframe, 25
- collower, 26
- color color, 360
- color command, 360
- color counter, 360
- color definition, 360
- color environment, 360
- color hyperlink, 360
- color key, 360
- color length, 360
- color option, 360
- color value, 360
- coltext, 26
- coltitle, 26
- colupper, 26
- comment, 245
- comment above listing, 251
- comment above\* listing, 251
- comment and listing, 247
- comment only, 245
- comment outside listing, 249
- comment side listing, 249
- comment style, 247
- compilable listing, 255
- compress page, 299
- description color, 276
- description delimiters, 276
- description delimiters none, 276
- description delimiters parenthesis, 276
- description font, 277
- description formatter, 277
- detach title, 19
- doc description, 364
- doc head, 363
- doc head command, 363
- doc head environment, 363
- doc head key, 363
- doc into index, 364
- doc left, 362
- doc left indent, 362
- doc marginnote, 364
- doc new, 364
- doc new and updated, 364
- doc right, 362
- doc right indent, 362
- doc updated, 364
- docexample, 358
- documentation listing options, 358
- documentation listing style, 358
- documentation minted options, 358
- documentation minted style, 358
- draft, 205
- draftmode, 165
- drop fuzzy midday shadow, 149
- drop fuzzy shadow, 149
- drop fuzzy shadow east, 153
- drop fuzzy shadow north, 153
- drop fuzzy shadow northeast, 153
- drop fuzzy shadow northwest, 153

- drop fuzzy shadow south, 152
- drop fuzzy shadow southeast, 152
- drop fuzzy shadow southwest, 152
- drop fuzzy shadow west, 152
- drop large lifted shadow, 155
- drop lifted shadow, 154
- drop midday shadow, 149
- drop shadow, 149
- drop shadow east, 152
- drop shadow north, 151
- drop shadow northeast, 152
- drop shadow northwest, 151
- drop shadow south, 151
- drop shadow southeast, 151
- drop shadow southwest, 151
- drop shadow west, 151
- drop small lifted shadow, 154
- empty, 195
- enforce breakable, 297
- english language, 361
- enhanced, 168
- enhanced jigsaw, 175
- enhanced standard, 170
- enlarge bottom at break by, 77
- enlarge bottom by, 77
- enlarge bottom finally by, 76
- enlarge by, 78
- enlarge left by, 77
- enlarge right by, 77
- enlarge top at break by, 77
- enlarge top by, 77
- enlarge top initially by, 76
- enlargepage, 298
- enlargepage flexible, 299
- equal height group, 50
- every box, 82
- every box on higher layers, 83
- every box on layer n, 83
- every float, 67
- every listing line, 240
- every listing line\*, 240
- extend freelance, 207
- extend freelancefirst, 207
- extend freelancelast, 207
- extend freelancemiddle, 207
- external, 90
- extrude bottom by, 81
- extrude by, 81
- extrude left by, 80
- extrude right by, 80
- extrude top by, 81
- finish, 161
- finish broken, 162
- finish broken pre, 333
- finish first, 162
- finish first and middle, 162
- finish first and middle pre, 333
- finish first pre, 333
- finish last, 162
- finish last pre, 333
- finish middle, 162
- finish middle and last, 162
- finish middle and last pre, 333
- finish middle pre, 333
- finish pre, 333
- finish unbroken, 162
- finish unbroken and first, 162
- finish unbroken and first pre, 333
- finish unbroken and last, 162
- finish unbroken and last pre, 333
- finish unbroken pre, 333
- fit, 316
- fit algorithm, 322
- fit basedim, 317
- fit fontsize macros, 318
- fit height from, 321
- fit height plus, 319
- fit maxfontdiff, 324
- fit maxfontdiffgap, 324
- fit maxstep, 324
- fit maxwidthdiff, 324
- fit maxwidthdiffgap, 324
- fit skip, 317
- fit to, 317
- fit to height, 317
- fit warning, 324
- fit width from, 320
- fit width plus, 319
- float, 66
- float\*, 66
- floatplacement, 66
- flushleft lower, 55
- flushleft title, 55
- flushleft upper, 55
- flushright lower, 56
- flushright title, 56
- flushright upper, 56
- fontlower, 27
- fonttitle, 27
- fontupper, 27
- frame code, 109
- frame code app, 333
- frame code pre, 333
- frame empty, 109
- frame engine, 106
- frame hidden, 118
- frame style, 117
- frame style image, 117
- frame style tile, 118
- freelance, 207
- fuzzy halo, 150
- fuzzy shadow, 148
- geometry nodes, 108
- graphical environment, 105
- graphics directory, 211
- graphics options, 211
- graphics pages, 211
- grow to left by, 78

grow to right by, 78  
 halo, 150  
 hbox, 85  
 hbox boxed title, 128  
 height, 45  
 height fill, 47  
 height fixed for, 301  
 height from, 46  
 height plus, 45  
 highlight math, 280  
 highlight math style, 280  
 hyphenationfix, 87  
 IfBooleanTF, 336  
 IfNoValueTF, 335  
 IfValueTF, 336  
 ignore nobreak, 75  
 image comment, 245  
 index actual, 359  
 index annotate, 360  
 index colorize, 360  
 index command, 359  
 index command name, 359  
 index default settings, 359  
 index format, 359  
 index german settings, 359  
 index level, 359  
 index quote, 359  
 interior code, 110  
 interior code app, 334  
 interior code pre, 334  
 interior empty, 110  
 interior engine, 107  
 interior hidden, 119  
 interior style, 118  
 interior style image, 119  
 interior style tile, 119  
 interior titled code, 109  
 interior titled code app, 333  
 interior titled code pre, 334  
 interior titled empty, 109  
 interior titled engine, 106  
 invisible, 21  
 label, 88  
 label type, 88  
 left, 32  
 left skip, 75  
 lefthand ratio, 70  
 lefthand width, 69  
 leftlower, 32  
 leftright skip, 75  
 leftrule, 29  
 lefttitle, 32  
 leftupper, 32  
 lifted shadow, 154  
 lines before break, 297  
 list entry, 89  
 list text, 89  
 listing above comment, 251  
 listing above text, 250  
 listing above\* comment, 251  
 listing above\* text, 250  
 listing and comment, 247  
 listing and text, 244  
 listing engine, 244  
 listing file, 244  
 listing inputencoding, 240  
 listing only, 244  
 listing options, 239  
 listing outside comment, 249  
 listing outside text, 248  
 listing remove caption, 240  
 listing side comment, 249  
 listing side text, 248  
 listing style, 239  
 listing utf8, 241  
 lower separated, 23  
 lowerbox, 22  
 marker, 177  
 math, 280  
 math lower, 280  
 math upper, 280  
 middle, 35  
 minimum for equal height group, 51  
 minipage, 85  
 minipage boxed title, 128  
 minipage boxed title\*, 128  
 minted language, 242  
 minted options, 242  
 minted style, 243  
 natural height, 45  
 no borderline, 144  
 no finish, 162  
 no finish first, 162  
 no finish last, 162  
 no finish middle, 162  
 no finish unbroken, 162  
 no label type, 88  
 no listing options, 239  
 no overlay, 62  
 no process, 255  
 no recording, 99  
 no shadow, 147  
 no underlay, 159  
 no underlay boxed title, 160  
 no underlay first, 160  
 no underlay last, 160  
 no underlay middle, 160  
 no underlay unbroken, 160  
 no watermark, 132  
 nobeforeafter, 72  
 nofloat, 66  
 noparskip, 72  
 nophantom, 88  
 notitle, 17  
 notitle after break, 297  
 on line, 87  
 only, 91  
 opacityback, 43

- opacitybacktitle, 43
- opacityfill, 43
- opacityframe, 43
- opacitylower, 44
- opacitytext, 44
- opacitytitle, 44
- opacityupper, 44
- outer arc, 31
- overlay, 61
- overlay app, 328
- overlay broken, 62
- overlay broken app, 329
- overlay broken pre, 329
- overlay first, 62
- overlay first and middle, 62
- overlay first and middle app, 329
- overlay first and middle pre, 329
- overlay first app, 328
- overlay first pre, 328
- overlay last, 62
- overlay last app, 329
- overlay last pre, 329
- overlay middle, 62
- overlay middle and last, 62
- overlay middle and last app, 329
- overlay middle and last pre, 329
- overlay middle app, 329
- overlay middle pre, 329
- overlay pre, 328
- overlay unbroken, 62
- overlay unbroken and first, 62
- overlay unbroken and first app, 329
- overlay unbroken and first pre, 329
- overlay unbroken and last, 62
- overlay unbroken and last app, 329
- overlay unbroken and last pre, 329
- overlay unbroken app, 328
- overlay unbroken pre, 328
- oversize, 37
- pad after break, 300
- pad at break, 300
- pad at break\*, 300
- pad before break, 300
- pad before break\*, 300
- parbox, 86
- parskip, 72
- pdf comment, 246
- pdf extension, 247
- phantom, 88
- phantomlabel, 88
- process code, 255
- raster after skip, 226
- raster before skip, 226
- raster column n, 230
- raster column skip, 227
- raster columns, 225
- raster equal height, 229
- raster equal height group, 229
- raster equal skip, 226
- raster even column, 230
- raster even number, 231
- raster even row, 231
- raster every box, 230
- raster force size, 230
- raster halign, 228
- raster height, 226
- raster left skip, 227
- raster number n, 231
- raster odd column, 230
- raster odd number, 231
- raster odd row, 230
- raster reset, 230
- raster right skip, 227
- raster row m, 231
- raster row m column n, 231
- raster row skip, 227
- raster rows, 225
- raster valign, 228
- raster width, 225
- record, 99
- remake, 90
- remember, 157
- remember as, 158
- reset, 90
- right, 33
- right skip, 75
- righthand ratio, 70
- righthand width, 69
- rightlower, 34
- rightrule, 29
- righttitle, 33
- rightupper, 33
- rotate, 157
- rounded corners, 41
- run arara, 257
- run biber, 257
- run bibtex, 257
- run dvips, 257
- run latex, 257
- run lualatex, 257
- run makeindex, 257
- run pdflatex, 255
- run ps2pdf, 257
- run system command, 255
- run xelatex, 257
- savedelimiter, 24
- savelowerto, 22
- scale, 157
- segmentation code, 110
- segmentation code app, 334
- segmentation code pre, 334
- segmentation empty, 110
- segmentation engine, 107
- segmentation hidden, 120
- segmentation style, 120
- separator sign, 275
- separator sign colon, 275
- separator sign dash, 275



- separator sign none, 275
- shadow, 147
- sharp corners, 40
- sharpish corners, 41
- shield externalize, 90
- show bounding box, 144
- shrink break goal, 299
- shrink tight, 80
- sidebyside, 68
- sidebyside align, 68
- sidebyside gap, 69
- size, 36
- skin, 105
- skin first, 105
- skin first is subskin of, 112
- skin last, 105
- skin last is subskin of, 112
- skin middle, 105
- skin middle is subskin of, 112
- space, 48
- space to both, 48
- space to lower, 48
- space to upper, 48
- spartan, 204
- split, 49
- squeezed title, 18
- squeezed title\*, 18
- standard, 166
- standard jigsaw, 167
- step, 88
- step and label, 88
- subtitle style, 20
- tabularx, 57
- tabularx\*, 57
- tcbimage comment, 246
- tcbox raise, 87
- tcbox raise base, 87
- tempfile, 87
- terminator sign, 277
- terminator sign colon, 278
- terminator sign dash, 278
- terminator sign none, 278
- text above listing, 250
- text above\* listing, 250
- text and listing, 244
- text height, 46
- text only, 245
- text outside listing, 248
- text side listing, 248
- text width, 28
- theorem, 279
- theorem name, 279
- theorem name and number, 278
- theorem number and name, 279
- theorem style, 285
- tikz, 156
- tikz lower, 58
- tikz reset, 156
- tikz upper, 58
- tikznode, 59
- tikznode boxed title, 129
- tikznode lower, 59
- tikznode upper, 59
- title, 17
- title after break, 297
- title code, 111
- title code app, 334
- title code pre, 334
- title empty, 111
- title engine, 107
- title filled, 25
- title hidden, 121
- title style, 120
- title style image, 121
- title style tile, 121
- titlerule, 30
- toggle enlargement, 79
- toggle left and right, 38
- top, 34
- toprule, 29
- toprule at break, 300
- topsep at break, 300
- toptitle, 34
- unbreakable, 297
- underlay, 159
- underlay boxed title, 160
- underlay boxed title pre, 332
- underlay broken, 160
- underlay broken pre, 332
- underlay first, 160
- underlay first and middle, 160
- underlay first and middle pre, 332
- underlay first pre, 332
- underlay last, 160
- underlay last pre, 332
- underlay middle, 160
- underlay middle and last, 160
- underlay middle and last pre, 332
- underlay middle pre, 332
- underlay pre, 332
- underlay unbroken, 160
- underlay unbroken and first, 160
- underlay unbroken and first pre, 332
- underlay unbroken and last, 160
- underlay unbroken and last pre, 332
- underlay unbroken pre, 332
- upperbox, 21
- valign, 49
- valign lower, 49
- varwidth boxed title, 129
- varwidth boxed title\*, 129
- varwidth upper, 59
- verbatim, 335
- vfill before first, 301
- visible, 21
- watermark color, 135
- watermark graphics, 131



- watermark graphics app, 331
- watermark graphics app on, 331
- watermark graphics on, 131
- watermark graphics pre, 331
- watermark graphics pre on, 331
- watermark opacity, 133
- watermark overzoom, 134
- watermark shrink, 134
- watermark stretch, 135
- watermark text, 130
- watermark text app, 330
- watermark text app on, 330
- watermark text on, 130
- watermark text pre, 330
- watermark text pre on, 330
- watermark tikz, 132
- watermark tikz app, 331
- watermark tikz app on, 331
- watermark tikz on, 132
- watermark tikz pre, 331
- watermark tikz pre on, 331
- watermark zoom, 133
- widget, 191
- width, 28
- /tcb/boxtitle/
  - xshift, 124
  - yshift, 124
  - yshift\*, 124
  - yshiftttext, 124
- /tcb/doclang/
  - color, 361
  - colors, 361
  - counter, 361
  - counters, 361
  - environment, 361
  - environment content, 361
  - environments, 361
  - index, 361
  - key, 361
  - keys, 361
  - length, 361
  - lengths, 361
  - new, 361
  - pageshort, 361
  - updated, 361
  - value, 361
  - values, 361
- /tcb/library/
  - all, 9
  - breakable, 8
  - documentation, 8
  - fitting, 8
  - hooks, 8
  - listings, 8
  - listingsutf8, 8
  - many, 9
  - minted, 8
  - most, 9
  - raster, 8
  - skins, 8
  - theorems, 8
  - xparse, 8
- /tcb/new/
  - auto counter, 92
  - blend into, 96
  - Crefname, 95
  - crefname, 95
  - list inside, 97
  - list type, 97
  - no counter, 93
  - number format, 94
  - number freestyle, 94
  - number within, 94
  - use counter, 93
  - use counter from, 93
  - use counter\*, 93
- /tikz/
  - fill image opacity, 218
  - fill image options, 218
  - fill image scale, 218
  - fill overzoom image, 214
  - fill overzoom image\*, 214
  - fill overzoom picture, 214
  - fill plain image, 212
  - fill plain image\*, 212
  - fill plain picture, 212
  - fill shrink image, 216
  - fill shrink image\*, 216
  - fill shrink picture, 216
  - fill stretch image, 213
  - fill stretch image\*, 213
  - fill stretch picture, 213
  - fill tile image, 217
  - fill tile image\*, 217
  - fill tile picture, 217
  - fill tile picture\*, 217
  - fill zoom image, 215
  - fill zoom image\*, 215
  - fill zoom picture, 215
  - tcb fill frame, 122
  - tcb fill interior, 122
  - tcb fill title, 122
- keys key, 361
- label key, 88
- label type key, 88
- last value, 130–132, 301
- left key, 32
- left value, 228
- left skip key, 75
- lefthand ratio key, 70
- lefthand width key, 69
- leftlower key, 32
- leftright skip key, 75
- leftrule key, 29
- lefttitle key, 32
- leftupper key, 32
- length key, 361
- Lengths

- `\foolength`, 351
- `lengths` key, 361
- `lifted shadow` key, 154
- `lines before break` key, 297
- `list entry` key, 89
- `list inside` key, 97
- `list text` key, 89
- `list type` key, 97
- `listing above comment` key, 251
- `listing above text` key, 250
- `listing above* comment` key, 251
- `listing above* text` key, 250
- `listing and comment` key, 247
- `listing and text` key, 244
- `listing engine` key, 244
- `listing file` key, 244
- `listing inputencoding` key, 240
- `listing only` key, 244
- `listing options` key, 239
- `listing outside comment` key, 249
- `listing outside text` key, 248
- `listing remove caption` key, 240
- `listing side comment` key, 249
- `listing side text` key, 248
- `listing style` key, 239
- `listing utf8` key, 241
- `listings` key, 8
- `listings` value, 96, 244
- `listingsutf8` key, 8
- `lower separated` key, 23
- `lowerbox` key, 22
- 
- `many` key, 9
- `\marg`, 352
- `margin` value, 287
- `margin apart` value, 287
- `margin break` value, 287
- `marker` key, 177
- `math` key, 280
- `math lower` key, 280
- `math upper` key, 280
- `maximum` value, 47
- `\meta`, 352
- `middle` key, 35
- `middle` value, 130–132, 301
- `middle and last` value, 130–132, 301
- `minimal` value, 36
- `minimum for equal height group` key, 51
- `minipage` key, 85
- `minipage` value, 85, 224
- `minipage boxed title` key, 128
- `minipage boxed title*` key, 128
- `minted` key, 8
- `minted` value, 244
- `minted language` key, 242
- `minted options` key, 242
- `minted style` key, 243
- `most` key, 9
- 
- `natural height` key, 45

- `new` key, 361
- `\NewTCBInputListing`, 345
- `\newtcbinputlisting`, 238
- `\NewTCBListing`, 343
- `\newtcblisting`, 236
- `\NewTCBox`, 340
- `\newtcbox`, 15
- `\NewTCBoxFit`, 346
- `\newtcboxfit`, 315
- `\newtcbtheorem`, 271
- `\NewTColorBox`, 338
- `\newtcolorbox`, 14
- `\NewTotalTCBox`, 342
- `\NewTotalTCBoxFit`, 347
- `\NewTotalTColorBox`, 339
- `no borderline` key, 144
- `no counter` key, 93
- `no finish` key, 162
- `no finish first` key, 162
- `no finish last` key, 162
- `no finish middle` key, 162
- `no finish unbroken` key, 162
- `no label type` key, 88
- `no listing options` key, 239
- `no overlay` key, 62
- `no process` key, 255
- `no recording` key, 99
- `no shadow` key, 147
- `no underlay` key, 159
- `no underlay boxed title` key, 160
- `no underlay first` key, 160
- `no underlay last` key, 160
- `no underlay middle` key, 160
- `no underlay unbroken` key, 160
- `no watermark` key, 132
- `nobeforeafter` key, 72
- `nofloat` key, 66
- `none` value, 38, 79, 229, 299, 301
- `noparskip` key, 72
- `nophantom` key, 88
- `normal` value, 36
- `north` value, 40, 41
- `northeast` value, 40, 41
- `northwest` value, 40, 41
- `notitle` key, 17
- `notitle after break` key, 297
- `number format` key, 94
- `number freestyle` key, 94
- `number within` key, 94
- 
- `\oarg`, 352
- `off` value, 324, 359
- `on` value, 324
- `on line` key, 87
- `only` key, 91
- `opacityback` key, 43
- `opacitybacktitle` key, 43
- `opacityfill` key, 43
- `opacityframe` key, 43
- `opacitylower` key, 44

`opacitytext` key, 44  
`opacitytitle` key, 44  
`opacityupper` key, 44  
`Option` color, 364  
`outer arc` key, 31  
`overlay` key, 61  
`overlay app` key, 328  
`overlay broken` key, 62  
`overlay broken app` key, 329  
`overlay broken pre` key, 329  
`overlay first` key, 62  
`overlay first and middle` key, 62  
`overlay first and middle app` key, 329  
`overlay first and middle pre` key, 329  
`overlay first app` key, 328  
`overlay first pre` key, 328  
`overlay last` key, 62  
`overlay last app` key, 329  
`overlay last pre` key, 329  
`overlay middle` key, 62  
`overlay middle and last` key, 62  
`overlay middle and last app` key, 329  
`overlay middle and last pre` key, 329  
`overlay middle app` key, 329  
`overlay middle pre` key, 329  
`overlay pre` key, 328  
`overlay unbroken` key, 62  
`overlay unbroken and first` key, 62  
`overlay unbroken and first app` key, 329  
`overlay unbroken and first pre` key, 329  
`overlay unbroken and last` key, 62  
`overlay unbroken and last app` key, 329  
`overlay unbroken and last pre` key, 329  
`overlay unbroken app` key, 328  
`overlay unbroken pre` key, 328  
`oversize` key, 37  
  
`pad after break` key, 300  
`pad at break` key, 300  
`pad at break*` key, 300  
`pad before break` key, 300  
`pad before break*` key, 300  
`pageshort` key, 361  
`parbox` key, 86  
`parskip` key, 72  
`path` value, 106, 107  
`pathfirst` value, 106, 107  
`pathfirstjigsaw` value, 106  
`pathjigsaw` value, 106  
`pathlast` value, 106, 107  
`pathlastjigsaw` value, 106  
`pathmiddle` value, 106, 107  
`pathmiddlejigsaw` value, 106  
`pdf comment` key, 246  
`pdf extension` key, 247  
`\pdfpages`, 211  
`pgf` value, 359  
`pgfchapter` value, 359  
`pgfsection` value, 359  
`phantom` key, 88  
  
`phantomlabel` key, 88  
`plain` value, 285  
`plain apart` value, 286  
`process code` key, 255  
`\ProvideTCBInputListing`, 345  
`\ProvideTCBListing`, 343  
`\ProvideTCBox`, 340  
`\ProvideTCBoxFit`, 346  
`\ProvideTColorBox`, 338  
`\ProvideTotalTCBox`, 342  
`\ProvideTotalTCBoxFit`, 347  
`\ProvideTotalTColorBox`, 339  
  
`raster` key, 8  
`raster after skip` key, 226  
`raster before skip` key, 226  
`raster column n` key, 230  
`raster column skip` key, 227  
`raster columns` key, 225  
`raster equal height` key, 229  
`raster equal height group` key, 229  
`raster equal skip` key, 226  
`raster even column` key, 230  
`raster even number` key, 231  
`raster even row` key, 231  
`raster every box` key, 230  
`raster force size` key, 230  
`raster halign` key, 228  
`raster height` key, 226  
`raster left skip` key, 227  
`raster number n` key, 231  
`raster odd column` key, 230  
`raster odd number` key, 231  
`raster odd row` key, 230  
`raster reset` key, 230  
`raster right skip` key, 227  
`raster row m` key, 231  
`raster row m column n` key, 231  
`raster row skip` key, 227  
`raster rows` key, 225  
`raster valign` key, 228  
`raster width` key, 225  
`record` key, 99  
`\refAux`, 356  
`\refAuxcs`, 356  
`\refCom`, 355  
`\refCom*`, 355  
`\refEnv`, 355  
`\refEnv*`, 355  
`\refKey`, 356  
`\refKey*`, 356  
`remake` key, 90  
`remember` key, 157  
`remember as` key, 158  
`\RenewTCBInputListing`, 345  
`\renewtcbinputlisting`, 238  
`\RenewTCBListing`, 343  
`\renewtcblisting`, 237  
`\RenewTCBox`, 340  
`\renewtcbox`, 15

- `\RenewTCBoxFit`, 346
- `\renewtcboxfit`, 315
- `\renewtcbtheorem`, 272
- `\RenewTColorBox`, 338
- `\renewtcolorbox`, 14
- `\RenewTotalTCBox`, 342
- `\RenewTotalTCBoxFit`, 347
- `\RenewTotalTColorBox`, 339
- `reset` key, 90
- `right` key, 33
- `right` value, 228
- `right skip` key, 75
- `righthand ratio` key, 70
- `righthand width` key, 69
- `rightlower` key, 34
- `rightrule` key, 29
- `righttitle` key, 33
- `rightupper` key, 33
- `rotate` key, 157
- `rounded corners` key, 41
- `rows` value, 229
- `run arara` key, 257
- `run biber` key, 257
- `run bibtex` key, 257
- `run dvips` key, 257
- `run latex` key, 257
- `run lualatex` key, 257
- `run makeindex` key, 257
- `run pdflatex` key, 255
- `run ps2pdf` key, 257
- `run system command` key, 255
- `run xelatex` key, 257
- 
- `savedelimiter` key, 24
- `savelowerto` key, 22
- `scale` key, 157
- `segmentation code` key, 110
- `segmentation code app` key, 334
- `segmentation code pre` key, 334
- `segmentation empty` key, 110
- `segmentation engine` key, 107
- `segmentation hidden` key, 120
- `segmentation style` key, 120
- `separator sign` key, 275
- `separator sign colon` key, 275
- `separator sign dash` key, 275
- `separator sign none` key, 275
- `shadow` key, 147
- `sharp corners` key, 40
- `sharpish corners` key, 41
- `shield externalize` key, 90
- `show bounding box` key, 144
- `shrink break goal` key, 299
- `shrink tight` key, 80
- `sidebyside` key, 68
- `sidebyside align` key, 68
- `sidebyside gap` key, 69
- `size` key, 36
- `skin` key, 105
- `skin first` key, 105

- `skin first is subskin of` key, 112
- `skin last` key, 105
- `skin last is subskin of` key, 112
- `skin middle` key, 105
- `skin middle is subskin of` key, 112

#### Skins

- `beamer`, 186
- `beamerfirst`, 188
- `beamerlast`, 190
- `beamermiddle`, 189
- `bicolor`, 181
- `bicolorfirst`, 183
- `bicolorlast`, 185
- `bicolormiddle`, 184
- `draft`, 205
- `empty`, 195
- `emptyfirst`, 197
- `emptylast`, 199
- `emptymiddle`, 198
- `enhanced`, 168
- `enhanced jigsaw`, 175
- `enhancedfirst`, 172
- `enhancedfirst jigsaw`, 176
- `enhancedlast`, 174
- `enhancedlast jigsaw`, 180
- `enhancedmiddle`, 173
- `enhancedmiddle jigsaw`, 177
- `freelance`, 207
- `freelancefirst`, 207
- `freelancelast`, 207
- `freelancemiddle`, 207
- `spartan`, 204
- `standard`, 166
- `standard jigsaw`, 167
- `widget`, 191
- `widgetfirst`, 192
- `widgetlast`, 194
- `widgetmiddle`, 193
- 
- `skins` key, 8
- `small` value, 36
- `south` value, 40, 41
- `southeast` value, 40, 41
- `southwest` value, 40, 41
- `space` key, 48
- `space to both` key, 48
- `space to lower` key, 48
- `space to upper` key, 48
- `spartan` key, 204
- `spartan Skin`, 204
- `spartan` value, 106, 107
- `split` key, 49
- `squeeze` value, 322
- `squeezed title` key, 18
- `squeezed title*` key, 18
- `standard` key, 166
- `standard Skin`, 166
- `standard` value, 106, 107, 285
- `standard jigsaw` key, 167
- `standard jigsaw Skin`, 167

`step` key, 88  
`step and label` key, 88  
`subtitle style` key, 20  
  
`tables` value, 96  
`tabularx` key, 57  
`tabularx*` key, 57  
`tcb fill frame` key, 122  
`tcb fill interior` key, 122  
`tcb fill title` key, 122  
`tcbclipframe` environment, 137  
`tcbclipinterior` environment, 139  
`tcbcliptitle` environment, 139  
`\tcbcontinuedraftmode`, 165  
`\tcbcounter`, 92  
`\tcbdocmarginnote`, 357  
`\tcbdocnew`, 357  
`\tcbdocupdated`, 357  
`\tcbfitdim`, 315–318  
`\tcbfitsteps`, 316  
`\tcbfontsize`, 315  
`\tcbhighmath`, 273  
`tcbimage comment` key, 246  
`\tcbincludegraphics`, 208  
`\tcbincludepdf`, 210  
`\tcbinputlisting`, 235  
`\tcbinputrecords`, 99  
`\tcbinterruptdraftmode`, 165  
`tcbinvclipframe` environment, 138  
`\tcbitem`, 224  
`tcbitemize` environment, 224  
`\tcbline`, 171  
`\tcbline*`, 171  
`tcblisting` environment, 233  
`\tcblistof`, 97  
`\tcblower`, 11  
`\tcbmakedocSubKey`, 355  
`\tcbmaketheorem`, 272  
`tcboutputlisting` environment, 235  
`\tcbox`, 13  
`tcbox raise` key, 87  
`tcbox raise base` key, 87  
`\tcboxedtitleheight`, 124  
`\tcboxedtitlewidth`, 124  
`\tcboxfit`, 314  
`\tcboxmath`, 273  
`\tcboxverb`, 342  
`tcbrafter` environment, 223  
`\tcbrecord`, 99  
`\tcbset`, 12  
`\tcbsetforeverylayer`, 12  
`\tcbsetmacrotoheightofnode`, 220  
`\tcbsetmacrotowidthofnode`, 220  
`\tcbsetmanagedlayer`, 83  
`\tcbsettoheightofnode`, 220  
`\tcbsettowidthofnode`, 220  
`\tcbstartdraftmode`, 165  
`\tcbstartrecording`, 99  
`\tcbstopdraftmode`, 165  
`\tcbstoprecording`, 99  
  
`\tcbsubskin`, 112  
`\tcbsubtitle`, 20  
`\tcbtitle`, 19  
`\tcbtitletext`, 19  
`\tcbuselibrary`, 8  
`\tcbuselistinglisting`, 235  
`\tcbuselistingtext`, 235  
`\tcbusetemp`, 98  
`\tcbusetemplisting`, 235  
`tcbverbatimwrite` environment, 98  
`tcbwritetemp` environment, 98  
`tcolorbox` environment, 11  
`\tcolorboxenvironment`, 16  
`tempfile` key, 87  
`terminator sign` key, 277  
`terminator sign colon` key, 278  
`terminator sign dash` key, 278  
`terminator sign none` key, 278  
`text above listing` key, 250  
`text above* listing` key, 250  
`text and listing` key, 244  
`text height` key, 46  
`text only` key, 245  
`text outside listing` key, 248  
`text side listing` key, 248  
`text width` key, 28  
`theorem` key, 279  
`theorem name` key, 279  
`theorem name and number` key, 278  
`theorem number and name` key, 279  
`theorem style` key, 285  
`theorems` key, 8  
`\thetcbcounter`, 92, 93  
`\thetcbrastrernum`, 223  
`tight` value, 36  
`tikz` key, 156  
`tikz lower` key, 58  
`tikz reset` key, 156  
`tikz upper` key, 58  
`tikznode` key, 59  
`tikznode boxed title` key, 129  
`tikznode lower` key, 59  
`tikznode upper` key, 59  
`title` key, 17  
`title` value, 36  
`title after break` key, 297  
`title code` key, 111  
`title code app` key, 334  
`title code pre` key, 334  
`title empty` key, 111  
`title engine` key, 107  
`title filled` key, 25  
`title hidden` key, 121  
`title style` key, 120  
`title style image` key, 121  
`title style tile` key, 121  
`titlerule` key, 30  
`toggle enlargement` key, 79  
`toggle left and right` key, 38

`top` key, 34  
`top` value, 49, 68, 73, 228  
`toprule` key, 29  
`toprule at break` key, 300  
`topsep at break` key, 300  
`toptitle` key, 34  
`true` value, 75, 296

`unbreakable` key, 297  
`unbroken` value, 130–132  
`unbroken and first` value, 130–132  
`underlay` key, 159  
`underlay boxed title` key, 160  
`underlay boxed title pre` key, 332  
`underlay broken` key, 160  
`underlay broken pre` key, 332  
`underlay first` key, 160  
`underlay first and middle` key, 160  
`underlay first and middle pre` key, 332  
`underlay first pre` key, 332  
`underlay last` key, 160  
`underlay last pre` key, 332  
`underlay middle` key, 160  
`underlay middle and last` key, 160  
`underlay middle and last pre` key, 332  
`underlay middle pre` key, 332  
`underlay pre` key, 332  
`underlay unbroken` key, 160  
`underlay unbroken and first` key, 160  
`underlay unbroken and first pre` key, 332  
`underlay unbroken and last` key, 160  
`underlay unbroken and last pre` key, 332  
`underlay unbroken pre` key, 332  
`unlimited` value, 295, 296  
`updated` key, 361  
`uphill` value, 40, 41  
`upperbox` key, 21  
`use counter` key, 93  
`use counter from` key, 93  
`use counter*` key, 93

`valign` key, 49  
`valign lower` key, 49  
`value` key, 361

Values
 

- `all`, 40, 41, 229, 299, 301
- `areaseize`, 322
- `areaseize*`, 322
- `base`, 73
- `baselineskip`, 299
- `bottom`, 49, 68, 73, 228
- `break`, 286
- `broken`, 130–132
- `center`, 49, 68, 73, 228
- `change`, 286
- `change apart`, 286
- `change break`, 286
- `change standard`, 285
- `doc`, 359
- `downhill`, 40, 41
- `east`, 40, 41
- `empty`, 106, 107
- `evenpage`, 38, 79
- `false`, 72, 75, 230, 296
- `fbox`, 36
- `figures`, 96
- `final`, 324
- `first`, 130–132, 301
- `first and middle`, 130, 301
- `fitbox`, 85
- `fontsize`, 322
- `fontsize*`, 322
- `foovalue`, 350
- `forced`, 38, 79
- `freelance`, 106, 107
- `hbox`, 85
- `hybrid`, 322
- `hybrid*`, 322
- `ignored`, 22
- `invisible`, 21, 22
- `last`, 130–132, 301
- `left`, 228
- `listings`, 96, 244
- `margin`, 287
- `margin apart`, 287
- `margin break`, 287
- `maximum`, 47
- `middle`, 130–132, 301
- `middle and last`, 130–132, 301
- `minimal`, 36
- `minipage`, 85, 224
- `minted`, 244
- `none`, 38, 79, 229, 299, 301
- `normal`, 36
- `north`, 40, 41
- `northeast`, 40, 41
- `northwest`, 40, 41
- `off`, 324, 359
- `on`, 324
- `path`, 106, 107
- `pathfirst`, 106, 107
- `pathfirstjigsaw`, 106
- `pathjigsaw`, 106
- `pathlast`, 106, 107
- `pathlastjigsaw`, 106
- `pathmiddle`, 106, 107
- `pathmiddlejigsaw`, 106
- `pgf`, 359
- `pgfchapter`, 359
- `pgfsection`, 359
- `plain`, 285
- `plain apart`, 286
- `right`, 228
- `rows`, 229
- `small`, 36
- `south`, 40, 41
- `southeast`, 40, 41
- `southwest`, 40, 41
- `spartan`, 106, 107



- `squeeze`, 322
- `standard`, 106, 107, 285
- `tables`, 96
- `tight`, 36
- `title`, 36
- `top`, 49, 68, 73, 228
- `true`, 75, 296
- `unbroken`, 130–132
- `unbroken and first`, 130–132
- `unlimited`, 295, 296
- `uphill`, 40, 41
- `visible`, 21, 22
- `west`, 40, 41
- `values` key, 361
- `varwidth boxed title` key, 129
- `varwidth boxed title*` key, 129
- `varwidth upper` key, 59
- `verbatim` key, 335
- `vfill before first` key, 301
- `visible` key, 21
- `visible` value, 21, 22
- 
- `watermark color` key, 135
- `watermark graphics` key, 131
- `watermark graphics app` key, 331
- `watermark graphics app on` key, 331
- `watermark graphics on` key, 131
- `watermark graphics pre` key, 331
- `watermark graphics pre on` key, 331
- `watermark opacity` key, 133
- `watermark overzoom` key, 134
- `watermark shrink` key, 134
- `watermark stretch` key, 135
- `watermark text` key, 130
- `watermark text app` key, 330
- `watermark text app on` key, 330
- `watermark text on` key, 130
- `watermark text pre` key, 330
- `watermark text pre on` key, 330
- `watermark tikz` key, 132
- `watermark tikz app` key, 331
- `watermark tikz app on` key, 331
- `watermark tikz on` key, 132
- `watermark tikz pre` key, 331
- `watermark tikz pre on` key, 331
- `watermark zoom` key, 133
- `west` value, 40, 41
- `widget` key, 191
- `widget Skin`, 191
- `widgetfirst Skin`, 192
- `widgetlast Skin`, 194
- `widgetmiddle Skin`, 193
- `width` key, 28
- 
- `xparse` key, 8
- `xshift` key, 124
- 
- `yshift` key, 124
- `yshift*` key, 124
- `yshifttext` key, 124