

The `todonotes` package*

Henrik Skov Midtiby
`henrikmidtiby@gmail.com`

January 9, 2009

Abstract

The `todonotes` package allows you to insert to-do items in your document. At any point in the document a list of all the inserted to-do items can be listed with the `\listoftodos` command.

Contents

1	Introduction	2
1.1	Usage	2
1.2	Package options	3
1.3	Options for the <code>todo</code> command	4
1.4	Options for the <code>missingfigure</code> command	5
1.5	Options for the <code>listoftodos</code> command	6
1.6	Known issues	6
1.6.1	Package loading order	6
1.6.2	Wrapping of long lines in list of todos	7
1.7	Things to improve	7
1.7.1	Owner information	7
1.7.2	Due date	7
1.7.3	Mark accomplished todos	7
1.7.4	Enumeration of the todo notes	8
1.8	Usage methods	8
1.8.1	Define new commands with fixed options	8
1.8.2	Combination with the <code>fixme</code> package	8
1.8.3	Altering the linespacing of <code>todonotes</code>	8
1.8.4	Comments "a la Word"	9
2	Implementation	9
2.1	Declaration of options for the package	10
2.2	Options for the <code>todo</code> command	12
2.3	The main code part	13

*This document corresponds to `todonotes.dtx`, dated 2009/01/09.

1 Introduction

The `todonotes` package makes three commands available to the user: `\todo[]{}{}`, `\missingfigure{}` and `\listoftodos`. `\todo[]{}{}` and `\missingfigure{}` makes it possible to insert notes in your document about things that has to be done later (`todonotes ...`). I developed the basic functionality of the package while I worked on my bachelor project.

1.1 Usage


`\todo` My most common usage of the `todonotes` package, is to insert an uncustomized `todonotes` somewhere in a latex document. An example of this usage is the command

`\todo{Make a cake \ldots},`

which renders like. The `\todo` command has this structure: `\todo[options]{<todo text>}`. The `todo text` is the text that will be shown in the todonote and in the list of todos. The optional argument `options`, allows the user to customize the appearance of the inserted `todonotes`. For a description of all the options see section 1.3.

`\missingfigure` The `\missingfigure` command inserts an image containing an attention sign and the given text. The command takes only one argument `\missingfigure{<text>}`, a text string that could describe what the figure should consist of. An example of its usage could be












`\missingfigure{Make a sketch of the structure of a trebuchet.}`
which renders like.



`\listoftodos` The `\listoftodos` command inserts a list of all the todos in the current document. `\listoftodos` takes no arguments. For this document the list of to-do's looks like.

Todo list

■ Make a cake ...	2
Figure: Make a sketch of the structure of a trebuchet.	2
■ And a green note	4
■ Anything but default colors	4

	A note with no line connecting it to the placement in the original text. . .	4
	A todonote placed in the text	4
	Fill those circles	4
	A note with a large fontsize.	5
	Note with very small fontsize.	5
	Short note	5
	Short note with prepend	5
	Short note with noprepnd	5
	Figure: Testing a long text string	5
	Figure: Testing a long text string	6
	Figure: Add a test image	6
	Some lines with a decreased line spacing. This is accomplished using the setspace package that is included in standard latex distributions. . . .	9
	Comment [HSM1]: Testing first time.	9
	Comment [HSM2]: Testing second time.	9

1.2 Package options

disable	If the option disable is passed to the package, the macros usually defined by the package (\todo , \listoftodos and \missingfigure) are defined as macros with no effect, and thus all inserted notes are removed.
danish, german, french spanish, catalan	Use the danish or german translations of the text strings "List of todos" and "Missing figure". The default is to use none of these options, which results in english text strings.
colorinlistoftodos	Adds a small colored square in front of all items in the Todo list. The color of the square is the same as the fill color of the inserted todonote. This can be usefull if there are different types of todos (insert reference, explain in detail, ...) where the color of the inserted todonote marks the type of todo.
color	These options sets the default colors for the todo command. There is three colors that can be specified. The border color (default bordercolor=black) around
backgroundcolor	the inserted text, the color behind the inserted text (default backgroundcolor=orange)
linecolor	and the color of the line connecting the inserted textbox with the current location
bordercolor	in the text (default linecolor=orange). Setting the color option to val passes this value on to the background and line color options. The specified colors must be valid according to the xcolor package.
textwidth	textwidth=length sets the width of a todo item in the margin to length . The width of inline todonotes will allways be the same as the current line width.
textsize	textsize=value sets the default text size of the inserted todonotes to the given value. Value is the "name" of the used fontsize, eg. if the desired fontsize is \tiny use textsize=tiny . The default value is textsize=normalsize .
prependcaption	The prependcaption option triggers a special behaviour of the caption=val option for the todo command, where the given value val is inserted in the inserted todonote.
shadow	If the shadow option is given, the inserted todonotes will be displayed with a gray shadow. I expect that the option will trigger problems with tikz versions prior to 2.0.

`dvistyle` When a document with `todonotes` is compiled with plain latex (to a dvi-file), there is an issue with the visual appearance¹. The option `dvistyle` changes the appearance of the inserted `todonotes` to avoid this problem.

1.3 Options for the `todo` command

There are several options that can be given to the `\todo` command. All the options are described here and often I have included examples of the change in visual appearance.

`color` These options set the color that is used in the current `todo` command. The color classes is the same as used in the `color` package options, see section 1.2.
`backgroundcolor` Default values can be set by the color options when the `todonotes` package is loaded.
`linecolor` The `todo` notes inserted in this paragraph is created with the command
`bordercolor` `\todo[color=green!40]{And a green note}`. The color of the inserted note

And a green note

could be used to mark different types of tasks (insert references, explain something in detail, ...), this could be streamlined by defining new commands like below.

```
\newcommand{\insertref}[1]{\todo[color=green!40]{#1}}
\newcommand{\explainindetail}[1]{\todo[color=red!40]{#1}}
```

Anything but default colors

An example that uses all of the color options is given below .

```
\todo[linecolor=green!70!white, backgroundcolor=blue!20!white,
bordercolor=red]{Anything but default colors}.
```

`line / noline`

A note with no line connecting it to the placement in the original text.

If you want to get rid of the line connecting the inserted note with the place in the text where the note occurs in the latex code, the option `noline` can be used.
`\todo[noline]{A note with no line ...}`

`inline / noinline`

It is possible to place a `todonote` inside the text instead of placing it in the margin, this could be desirable if the text in the note has a considerable length.
`\todo[inline]{A todonote placed in the text}`

A todonote placed in the text

Another usage for the `inline` option is when you want to add a `todonote` to a figure caption.

```
\begin{wrapfigure}{r}[20mm]{40mm}
\begin{tikzpicture}
\draw[red] (0, 0) circle(0.45);
\draw[green] (1, 0) circle(0.45);
\draw[blue] (2, 0) circle(0.45);
\end{tikzpicture}
\caption{A text explaining the image.}
```



Figure 1: A text explaining the image.

Fill those circles ...

¹The problem is placement of text inside the colored boxes.

```
\todo[inline]{Fill those circles \ldots}}
\end{wrapfigure}
```

size `size=val` changes the size of the text inside the todonote. The commands used to create the notes below are

```
\todo[size=\Large]{A note with a large fontsize.} and
\todo[inline, size=\tiny]{Note with very small fontsize.}
```

Note with very small fontsize.

list / nolist

When the option `nolist` is given, the todo item will not appear in the list of todos.

caption

The `caption` option enables the user to specify a short description of the todonote that are inserted in the list of todos instead of the full todonote text.

```
\todo[caption={Short note}]{A very long and tedious note that
cannot be on one line in the list of todos.}
```

The effect of this option is altered with the package option `prependcaption` or the `prepend / nopprepend` option for the `todo` command.

prepend / nopprepend

The options `prepend` and `nopprepend` can be used for setting whether a given caption should be prepended to the todonote or not. Globally this can be set using the `prependcaption` option for the package. Below is the effect of the option shown using the code:

```
\todo[prepend, caption={Short note with prepend}]{A very long and tedious
note that cannot be on one line in the list of todos.}.
\todo[nopprepend, caption={Short note with nopprepend}]{A very long and
tedious note that cannot be on one line in the list of todos.}.
```

figwidth


The `figwidth=length` option sets the default width of the figure inserted by the `\missingfigure` command. The default value is `\textwidth`.

1.4 Options for the missingfigure command


figwidth

The `figwidth=length` option sets the width of the figure inserted by the `\missingfigure` command. Length values below *6cm* might trigger some problems with the visual appearance. Try to compare the default of the missing figure command, when the option is given or not.

```
\missingfigure[figwidth=6cm]{Testing a long text string}
```




```
\missingfigure{Testing a long text string}
```



Another usage of the option is when `\missingfigure` is used in the `wrapfigure` environment.

```
\begin{wrapfigure}{r}[2cm]{6cm}
\missingfigure[figwidth=6cm]{Add a test image \ldots}
\end{wrapfigure}
```



1.5 Options for the `listoftodos` command

Currently the `listoftodos` command takes no optional arguments.

1.6 Known issues

1.6.1 Package loading order

The `todonotes` package requires the following packages.

- `ifthen`
- `hyperref`
- `xkeyval`
- `xcolor`

- tikz
- calc
- graphicx (is loaded via the tikz package)

When todonotes are loaded in the preamble, the package checks if these packages all are loaded. If that is not the case it loads the missing packages with no options given. If you want to give some specific options to some of these packages, you have to load them *before* the todonotes package, otherwise you will get an "Option clash" error when latex works on the document.

1.6.2 Wrapping of long lines in list of todos

When a document is compiled with latex (and not pdflatex) long items in the list of todos are not wrapped into several lines, and do instead continue to the right out of the page.

1.7 Things to improve

This is a list of things I consider to improve sometime in the future. I havent been done yet as I lack the time or skills to implement them. Patches with implementations of these tasks will be appreciated and might be included in the package if it will improve the package quality.

1.7.1 Owner information

Option for the todo command.

```
\todo[owner={Fabrice}]{Stuff}
```

Add info on who "owns" the current todo. Idea: Fabrice Niessen

1.7.2 Due date

Option for the todo command.

```
\todo[due=2008-12-07]{Stuff}
```

Add info on when the current todo is due. Might be enhanced by a time line of the todos that have a due date assigned. Idea: Fabrice Niessen

1.7.3 Mark accomplished todos

```
\todo[done]{Stuff}
```

Idea: Fabrice Niessen

1.7.4 Enumeration of the todo notes

Add counters to the inserted notes. Idea: Henrik

1.8 Usage methods

In this section I have collected some different methods to use the `todonotes` package.

1.8.1 Define new commands with fixed options

Often there is a need for marking different classes of things to do (add reference, rewrite, ...). One way to do this, is to define some new commands as shown below (idea from Florent B.).

```
\newcommand{\addref}{\todo[color=red!40]{Add reference.}}
\newcommand{\rewrite}[1]{\todo[color=green!40]{#1}}
```

To distinguish between the different types of todos, the `todonotes` package can be loaded with the `colorinlistoftodos` option, which adds small colored squares to the list of todos.

```
\usepackage[colorinlistoftodos]{todonotes}
```

1.8.2 Combination with the `fixme` package

Thomas Arildsen has mailed me this use case. Check the documentation for the `fixme` package, as the code below relies directly on it (the `\FDUser` command is augmented when `\begin{document}` is reached).

```
\usepackage[user,nomargin]{fixme}
\usepackage{todonotes}
\newcommand{\FXUser}[2]{\todo[inline,size=\small]{\bfseries #1:} #2}}
```

1.8.3 Altering the linespacing of `todonotes`

The `setspace` package lets you alter the line spacing of smaller sections of your document. The primary construct is the `spacing` environment, which is demonstrated below.

```
\begin{spacing}{0.5}
Some lines with a decreased line spacing. This is accomplished
using the setspace package that is included in standard latex
distributions.
\end{spacing}
```


Some lines with a decreased line spacing. This is accomplished using the `setspace` package that is included in standard latex distributions.

Using the `spacing` environment we can define a new `todonote` command using the code below:

```
\newcommand{\smalltodo}[2] []
{\todo[caption={#2}, #1]
{\begin{spacing}{0.5}#2\end{spacing}}}
```

Some lines with a decreased line spacing. This is accomplished using the `setspace` package that is included in standard latex distributions.

Todonotes with decreased line spacing can now be inserted as follows

```
\smalltodo[size=\footnotesize]{
Some lines with a decreased line spacing. This is accomplished
using the setspace package that is included in standard latex
distributions.}
```

1.8.4 Comments "a la Word"

Fabrice Niessen sent me the following usecase. The idea is to define a new command `\mycomment` which adds a counter and optionally the initials of the author to the inserted `todonote`.

```
\newcounter{mycomment}
\newcommand{\mycomment}[2] []{%
  % initials of the author (optional) + note in the margin
  \refstepcounter{mycomment}%
  {%
    \setstretch{0.7}% spacing
    \todo[color={red!100!green!33},size=\small]{%
      \textbf{Comment [\uppercase{#1}\themycment]}~#2}%
    }
}
```

Comment [HSM1]: Testing first time.

Comment [HSM2]: Testing second time.

The command `\mycomment[HSM]{Testing first time.}` is displayed like shown in the left margin, and another call of the command is added below `\mycomment[HSM]{Testing second time.}`.

2 Implementation

Identifies the package and loads the packages dependences.

```
1 \ProvidesPackage{todonotes}[2009/01/09]
2 \RequirePackage{ifthen}
3 \RequirePackage{xkeyval}
4 \RequirePackage{hyperref}
5 \RequirePackage{xcolor}
6 \RequirePackage{tikz}
7 \RequirePackage{calc}
```

Some default values are set

```

8 \newcommand{\@todonotes@text}{}%
9 \newcommand{\@todonotes@backgroundcolor}{orange}
10 \newcommand{\@todonotes@linecolor}{orange}
11 \newcommand{\@todonotes@bordercolor}{black}
12 \newcommand{\@todonotes@textwidth}{\marginparwidth}
13 \newcommand{\@todonotes@textsize}{\normalsize}
14 \newcommand{\@todonotes@figwidth}{\textwidth}

```

2.1 Declaration of options for the package

In this part the various options for the package are defined.

Define the default text strings and set localization options for the danish and german languages.

```

15 \newcommand{\@todonotes@todolistname}{Todo list}
16 \newcommand{\@todonotes@MissingFigureText}{Figure}
17 \newcommand{\@todonotes@MissingFigureUp}{Missing}
18 \newcommand{\@todonotes@MissingFigureDown}{figure}
19 \newcommand{\@todonotes@SetTodoListName}[1]{\renewcommand{\@todonotes@todolistname}{#1}}
20 \newcommand{\@todonotes@SetMissingFigureText}[1]{\renewcommand{\@todonotes@MissingFigureText}{#1}}
21 \newcommand{\@todonotes@SetMissingFigureUp}[1]{\renewcommand{\@todonotes@MissingFigureUp}{#1}}
22 \newcommand{\@todonotes@SetMissingFigureDown}[1]{\renewcommand{\@todonotes@MissingFigureDown}{#1}}
23 \newif{\if@todonotes@reverseMissingFigureTriangle}
24 \DeclareOptionX{danish}{%
25     \@todonotes@SetTodoListName{G\o{}rem\aa{}lsliste}%
26     \@todonotes@SetMissingFigureText{Figur}%
27     \@todonotes@SetMissingFigureUp{Manglende}%
28     \@todonotes@SetMissingFigureDown{figur}%
29 }
30 \DeclareOptionX{german}{%
31     \@todonotes@SetTodoListName{Liste der noch zu erledigenden Punkte}%
32     \@todonotes@SetMissingFigureText{Abbildung}%
33     \@todonotes@SetMissingFigureUp{Fehlende}%
34     \@todonotes@SetMissingFigureDown{Abbildung}%
35 }
36 \DeclareOptionX{french}{%
37     \@todonotes@SetTodoListName{Liste des points \textit{à} traiter}%
38     \@todonotes@SetMissingFigureText{Figure}%
39     \@todonotes@SetMissingFigureUp{Figure}%
40     \@todonotes@SetMissingFigureDown{manquante}%
41     \@todonotes@reverseMissingFigureTrianglefalse
42 }
43 \DeclareOptionX{catalan}{%
44     \@todonotes@SetTodoListName{Llista de feines pendents}%
45     \@todonotes@SetMissingFigureText{Figura}%
46     \@todonotes@SetMissingFigureUp{Figura}%
47     \@todonotes@SetMissingFigureDown{pendent}%
48 }
49 \DeclareOptionX{spanish}{%

```

```

50 \@todonotes@SetTodoListName{Lista de tareas pendientes}%
51 \@todonotes@SetMissingFigureText{Figura}%
52 \@todonotes@SetMissingFigureUp{Figura}%
53 \@todonotes@SetMissingFigureDown{pendient}%
54 }

```

Create a counter, for storing the number of inserted todos.

```

55 \newcounter{@todonotes@numberoftodonotes}

```

Make it possible to disable the functionality of the package. If this option is given, the commands `\todo{}` and `\listoftodos` are defined as commands with no effect. (But you can still compile you document with these commands).

```

56 \newif{\if@todonotes@disabled}
57 \DeclareOptionX{disable}{\@todonotes@disabledtrue}

```

Show small boxes in the list of todos with the color of the inserted todonotes.

```

58 \newif{\if@todonotes@colorinlistoftodos}
59 \DeclareOptionX{colorinlistoftodos}{\@todonotes@colorinlistoftodostrue}

```

The default style behaves bad when compiled with latex (some text placement problems). The `dvistyle` option, changes the visual behavior to avoid this text placement problem.

```

60 \newif{\if@todonotes@dviStyle}
61 \DeclareOptionX{dvistyle}{\@todonotes@dviStyletrue}

```

Create a color option.

```

62 \define@key{todonotes.sty}%
63   {color}{
64     \renewcommand{\@todonotes@backgroundcolor}{#1}
65     \renewcommand{\@todonotes@linecolor}{#1}}

```

Make the background color of the notes as an option.

```

66 \define@key{todonotes.sty}%
67   {backgroundcolor}{\renewcommand{\@todonotes@backgroundcolor}{#1}}

```

Make the line color of the notes as an option.

```

68 \define@key{todonotes.sty}%
69   {linecolor}{\renewcommand{\@todonotes@linecolor}{#1}}

```

Make the color of the notes box color as an option.

```

70 \define@key{todonotes.sty}%
71   {bordercolor}{\renewcommand{\@todonotes@bordercolor}{#1}}

```

Set whether short captions given as arguments to the `todo` command should be included in the inserted todonote.

```

72 \newif{\if@todonotes@prependcaptionglobal}
73 \@todonotes@prependcaptionglobalfalse
74 \DeclareOptionX{prependcaption}{\@todonotes@prependcaptionglobaltrue}

```

Make the text width as an option.

```

75 \define@key{todonotes.sty}%
76   {textwidth}{\renewcommand{\@todonotes@textwidth}{#1}}

```

Make the text size as an option. It requires some magic with the `\csname` and `\endcsname` macros, as commands cannot be taken as options for a package.

```
77 \define@key{todonotes.sty}%
78   {textsize}{\renewcommand{\@todonotes@textsize}{\csname #1\endcsname}}
```

Add option for shadows behind the inserted notes

```
79 \newif{\if@todonotes@shadowenabled}
80 \@todonotes@shadowenabledfalse
81 \DeclareOptionX{shadow}{\@todonotes@shadowenabledtrue
82 \usetikzlibrary{shadows}}
```

Add option for the default width of the figure inserted with `\missingfigure`.

```
83 \define@key{todonotes.sty}%
84   {figwidth}{\renewcommand{\@todonotes@figwidth}{#1}}
```

Make the text width as an option.

```
85 % Finally process the given options.
86 %   \begin{macrocode}
87 \ProcessOptionsX
```

2.2 Options for the todo command

In this part the various options for commands in the package are defined. Set an arbitrarily fill color

```
88 \newcommand{\@todonotes@currentlinecolor}{}%
89 \newcommand{\@todonotes@currentbackgroundcolor}{}%
90 \newcommand{\@todonotes@currentbordercolor}{}%
91 \define@key{todonotes}{color}{%
92   \renewcommand{\@todonotes@currentlinecolor}{#1}%
93   \renewcommand{\@todonotes@currentbackgroundcolor}{#1}}%
94 \define@key{todonotes}{linecolor}{%
95   \renewcommand{\@todonotes@currentlinecolor}{#1}}%
96 \define@key{todonotes}{backgroundcolor}{%
97   \renewcommand{\@todonotes@currentbackgroundcolor}{#1}}%
98 \define@key{todonotes}{bordercolor}{%
99   \renewcommand{\@todonotes@currentbordercolor}{#1}}%
```

Set a relative font size

```
100 \newcommand{\@todonotes@sizecommand}{}%
101 \define@key{todonotes}{size}{\renewcommand{\@todonotes@sizecommand}{#1}}%
```

Should the todo item be included in the list of todos?

```
102 \newif\if@todonotes@appendtolistoftodos%
103 \define@key{todonotes}{list}[]{\@todonotes@appendtolistoftodostrue}%
104 \define@key{todonotes}{nolist}[]{\@todonotes@appendtolistoftodosfalse}%
```

Should the todo item be displayed inline?

```
105 \newif\if@todonotes@inlinenote%
106 \define@key{todonotes}{inline}[]{\@todonotes@inlinenotetrue}%
107 \define@key{todonotes}{noinline}[]{\@todonotes@inlinenotefalse}%
```

```

108 \newif\if@todonotes@prependcaption%
109 \define@key{todonotes}{prepend}[]{\@todonotes@prependcaptiontrue}%
110 \define@key{todonotes}{nopprepend}[]{\@todonotes@prependcaptionfalse}%

Should the note in the margin be connected to the insertion point in the text?
111 \newif\if@todonotes@line%
112 \define@key{todonotes}{line}[]{\@todonotes@linetrue}%
113 \define@key{todonotes}{noline}[]{\@todonotes@linefalse}%

Should the text in the list of todos be different from the text in the todonote?
114 \newcommand{\@todonotes@caption}{}%
115 \newif\if@todonotes@captiongiven%
116 \define@key{todonotes}{caption}%
117     {\renewcommand{\@todonotes@caption}{#1}}%
118     \@todonotes@captiongiventrue}%
119 \define@key{todonotes}{nocaption}[]{\@todonotes@captiongivenfalse}%

Change the current figure width.
120 \newcommand{\@todonotes@currentfigwidth}{\@todonotes@figwidth}
121 \define@key{todonotes}%
122     {figwidth}{\renewcommand{\@todonotes@currentfigwidth}{#1}}

Preset values of the options
123 \presetkeys%
124     {todonotes}%
125     {linecolor=\@todonotes@linecolor,%
126     backgroundcolor=\@todonotes@backgroundcolor,%
127     bordercolor=\@todonotes@bordercolor,%
128     noline,%
129     nocaption,%
130     figwidth=\@todonotes@figwidth,%
131     line, list, size=\@todonotes@textsize}{}%

```

2.3 The main code part

Here is the actual macros defined. If the option "disable" was passed to the package define empty commands.

```

132 \if@todonotes@disabled%
133     \newcommand{\listoftodos}{}
134     \newcommand{\todo}[2][]{\ignorespaces}
135     \newcommand{\missingfigure}[2]{}
136 \else % \if@todonotes@disabled

Define the \listoftodos command and define the appearance of the list of todos.
137 \newcommand{\listoftodos}
138     {\section*{\@todonotes@todolistname} \@starttoc{tdo}}
139 \newcommand{\l@todo}
140     {\@dottedtocline{1}{0em}{2.3em}}

Define styles used by the todo command
141 \tikzstyle{notestylera} = [

```

```

142     draw=\@todonotes@currentbordercolor,
143     fill=\@todonotes@currentbackgroundcolor,
144     line width=0.5pt,
145     text width = \@todonotes@textwidth - 1.6 ex - 1pt,
146     inner sep = 0.8 ex,
147     rounded corners=4pt]

```

Add shadows and rounded corners to the inserted todonotes.

```

148 \if@todonotes@shadowenabled
149 \tikzstyle{notestyle} = [notestylraw,
150     general shadow={shadow xshift=.5ex, shadow yshift=-.5ex,
151         opacity=1,fill=black!50}]
152 \else
153 \tikzstyle{notestyle} = [notestylraw]
154 \fi
155 \tikzstyle{notestyleleft} = [
156     notestyle,
157     left]
158 \tikzstyle{connectstyle} = [
159     thick,
160     draw=\@todonotes@currentlinecolor]
161 \tikzstyle{inlinenotestyle} = [
162     notestyle,
163     text width=\linewidth - 1.6 ex - 1 pt]

```

`\todo` Define the todo command

```

164 \newcommand{\todo}[2] [] {%

```

Use the global value for determining the default prepend behavior.

```

165 \if@todonotes@prependcaptionglobal%
166 \@todonotes@prependcaptiontrue%
167 \else%
168 \@todonotes@prependcaptionfalse%
169 \fi%

```

Store the original text for later usage.

```

170 \renewcommand{\@todonotes@text}{#2}%
171 \renewcommand{\@todonotes@caption}{#2}%
172 \setkeys{todonotes}{#1}%

```

Add the item to the list of todos. When the option `colorinlistoftodos` is given to the package a small colored square is added in front of the text.

```

173 \addtocounter{\@todonotes@numberoftodonotes}{1}%
174 \if@todonotes@appendtolistoftodos%
175     \phantomsection%
176     \if@todonotes@captiongiven%
177     \else%
178         \renewcommand{\@todonotes@caption}{#2}%
179     \fi%
180     \if@todonotes@colorinlistoftodos%
181         \addcontentsline{tdo}{todo}{\protect{%

```

```

182         \colorbox{\@todonotes@currentbackgroundcolor}%
183         {\textcolor{\@todonotes@currentbackgroundcolor}{o}}%
184         \@todonotes@caption}}%
185     \else%
186         \addcontentsline{tdo}{todo}{\protect{\@todonotes@caption}}%
187     \fi%
188 \fi%

```

Prepend the short caption given if it is requested

```

189 \if@todonotes@captiongiven%
190     \if@todonotes@prependcaption%
191         \renewcommand{\@todonotes@text}{\@todonotes@caption: #2}%
192     \fi%
193 \fi%

```

Place the todonote as indicated by the options (inline or in a marginpar), below is the code for the inline placement.

```

194 \if@todonotes@inlinenote%
195     \if@todonotes@dviStyle%
196         {\par\noindent\begin{tikzpicture}[remember picture]%
197             \draw node[inlinenotestyle] {};\end{tikzpicture}\par}%
198         {\noindent \@todonotes@sizecommand \@todonotes@text}%
199         {\par\noindent\begin{tikzpicture}[remember picture]%
200             \draw node[inlinenotestyle] {};\end{tikzpicture}\par}%
201     \else%
202         {\par\noindent\begin{tikzpicture}[remember picture]%
203             \draw node[inlinenotestyle] {\@todonotes@sizecommand \@todonotes@text};%
204             \end{tikzpicture}\par}%
205     \fi%
206 \else%

```

When the todonote should be placed inside a marginpar, the code below is applied. First is the current location in the document stored, this enables us later to connect this point with the inserted todonote.

```

207 \begin{tikzpicture}[remember picture, baseline=-0.75ex]%
208     \node [coordinate] (inText) {};%
209 \end{tikzpicture}%
210 \marginpar[{} Draw note in left margin
211 \if@todonotes@dviStyle%
212     \begin{tikzpicture}[remember picture]%
213         \draw node[notestyle] {};%
214     \end{tikzpicture}\\
215     \begin{minipage}{\@todonotes@textwidth}%
216         \@todonotes@sizecommand \@todonotes@text%
217     \end{minipage}\\
218     \begin{tikzpicture}[remember picture]%
219         \draw node[notestyle] (inNote) {};%
220     \end{tikzpicture}%
221 \else%
222     \begin{tikzpicture}[remember picture]%
223         \draw node[notestyle] (inNote)%

```

```

224         {\@todonotes@sizecommand \@todonotes@text};%
225     \end{tikzpicture}%
226 \fi%
227 \if@todonotes@line%
228     \begin{tikzpicture}[remember picture, overlay]%
229         \draw[connectstyle]%
230             ([yshift=-0.2cm] inText)%
231             -| ([xshift=0.2cm] inNote.east)%
232             -| (inNote.east);%
233     \end{tikzpicture}%
234 \fi%

```

In the book documentclass (which is a twoside layout), the `\marginpar` macro takes two arguments `\marginpar[left]{right}`. If both arguments are given, latex will decide in which side the margin note has to be inserted, and then use the corresponding commands.

```

235 }]{% Draw note in right margin
236 \if@todonotes@dviStyle%
237     \begin{tikzpicture}[remember picture]%
238         \draw node[notestyle] {};%
239     \end{tikzpicture}\\%
240     \begin{minipage}{\@todonotes@textwidth}%
241         \@todonotes@sizecommand \@todonotes@text%
242     \end{minipage}\\%
243     \begin{tikzpicture}[remember picture]%
244         \draw node[notestyle] (inNote) {};%
245     \end{tikzpicture}%
246 \else%
247     \begin{tikzpicture}[remember picture]%
248         \draw node[notestyle] (inNote)%
249             {\@todonotes@sizecommand \@todonotes@text};%
250     \end{tikzpicture}%
251 \fi%
252 \if@todonotes@line%
253     \begin{tikzpicture}[remember picture, overlay]%
254         \draw[connectstyle]%
255             ([yshift=-0.2cm] inText)%
256             -| ([xshift=-0.2cm] inNote.west)%
257             -| (inNote.west);%
258     \end{tikzpicture}%
259 \fi%
260 }%
261 \fi%
262 \ignorespaces%
263 }%

```

`\missingfigure` Defines the `\missingfigure` macro.

```

264 \newcommand{\missingfigure}[2][]{
265     \setkeys{todonotes}{#1}%
266     \addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: \protect{#2}}%

```



```

267 \par
268 \noindent
269 \begin{tikzpicture}
270 \draw[fill=black!40, draw = white, line width=0pt]
271     (-2, -2.5) rectangle +(\@todonotes@currentfigwidth, 4cm);
272 \draw (2, -0.3) node[right, text
273     width=\@todonotes@currentfigwidth-4.5cm] {#2};
274 \draw[red, fill=white, rounded corners = 5pt, line width=10pt]
275     (30:2cm) -- (150:2cm) -- (270:2cm) -- cycle;
276 \draw (0, 0.3) node {\@todonotes@MissingFigureUp};
277 \draw (0, -0.3) node {\@todonotes@MissingFigureDown};
278 \end{tikzpicture}
279 }% Ending \missingfigure command
280 \fi % Ending \@todonotes@ifdisabled

```

Change History

0.1	General: The first version of the package 1	/ previous section, subsection or figure using the phantomsection macro. 1
0.2	General: Updated the option handling of the package 1	0.4 General: Modified the behaviour of the inline todonotes, to avoid empty lines around the inline todonotes. 1
0.2.1	General: Slightly modified by Kjell Magne Fauske to support notes in the left margin (for documentstyle book). 1	0.4.1 General: Added the option colorinlistoftodos which inserts a small box with the used fillcolor of the todonotes in the list of todos. . . 1
0.2.2	General: Added a missingfigure command 1	0.4.2 General: Fixed a bug with the disable option to the package. . . . 1
0.2.3	General: Made a dependency on the calc package 1	0.5 General: Created a dtx file containing both source code and documentation of the package 1
0.3	General: Delayed the requirements for the hyperref package until begin document and added an optional argument to the todo command for adding inline todonotes (Idea from Patrick Toche) 1	0.5.1 General: Updated the documentation 1
0.3.1	General: Added some options to the todo macro (Idea: Patrick Toche) and made the listoftodos point at the inserted todos and not only the current	0.5.2 General: Fixed a bug that prevented the usage of the option french for babel. Bug report by Thomas Braun. 1
		0.6 General: Added the caption option to the todo command. 1

0.6.1	General: Added a new usecase with decreased line spacing.	1			
0.6.2	General: Added a usecase by Fabrice Niessen.	1			
0.7	General: Added language options on request from Peter Zimmermann.	1			
0.7.1	General: Reworked the color options for both the whole package and the todo command. General code clean up. Added the prependcaption package option.	1			
0.7.2	General: Avoid to change the font-size inside the list of todos, fixing a bug revealed by Vladimir Zhuravlev.	1			
0.7.3	General: The localization options (danish and german) and the disable options, were all flawed by naming inconsistencies that made then break the package.				
					This have been fixed. 1
			0.7.4	General: Fixed a bug related to the caption option for the todo command. Introduced a counter of the number of inserted todos. . .	1
			0.7.5	General: Fixed a typo in a macroname.	1
			0.7.6	General: Added a textsize option for the package and the prepend / noprepnd option for the todo command.	1
			0.8	General: Added three new translations french, spanish and catalan thanks to Richard Dominique and Joan Queralt. Improved the visual appearance of the inserted notes (rounded corners and optional shadows) with code from Joan Queralt. Found an untranslated textstring "Figure" in the source. Added a figwidth option to the missing-figure command, patch by Paul Ivanov.	1