

The `enumerate` package*

David Carlisle

1999/03/05

Abstract

This package gives the `enumerate` environment an optional argument which determines the style in which the counter is printed.

An occurrence of one of the tokens `A a I i` or `1` produces the value of the counter printed with (respectively) `\Alph \alph \Roman \roman` or `\arabic`.

These letters may be surrounded by any strings involving any other TeX expressions, however the tokens `A a I i 1` must be inside a `{ }` group if they are not to be taken as special.

1 Examples

EX i.	one one one one one one one one one one one one one	<pre>\begin{enumerate}[EX i.] \item one one one one one one one one one one one\label{LA} \item two \begin{enumerate}[{example} a)] \item one of two one of two one of two\label{LB} \item two of two \end{enumerate} \item two of two \end{enumerate}</pre>
EX ii.	two	
	example a) one of two one of two one of two	
	example b) two of two	
A-1	one	<pre>\begin{enumerate}[{A}-1] \item one\label{LC} \item two \end{enumerate}</pre>
A-2	two	

`\label` and `\ref` may be used as with the standard `enumerate` environment. `\ref` only produces the counter value, not the whole label. `\ref` prints the value in the same style as `\item`, as determined by the presence of one of the tokens `A a I i 1` in the optional argument. In the above example `\ref{LA}`, `\ref{LB}` and `\ref{LC}` produce ‘i’, ‘ia’ and ‘1’ respectively.

2 Macros

```
1 (*package)
\@enlab Internal token register used to build up the label command from the optional
argument.
2 \newtoks\@enLab
```

*This file has version number v3.00, last revised 1999/03/05.

`\@enqmark` This just expands to a ‘?’. `\ref` will produce this, if no counter is printed.

The next four macros build up the command that will print the item label. They each gobble one token or group from the optional argument, and add corresponding tokens to the register `\@enLab`. They each end with a call to `\@enloop`, which starts the processing of the next token.

```

4 \def\@enLabel#1#2{%
5   \edef\@enThe{\noexpand#1{\@enumctr}}%
6   \@enLab\expandafter{the\@enLab\csname the\@enumctr\endcsname}%
7   \@enloop}

```

```

8 \def\@enSpace{\afterassignment\@enSp@ce\let\@tempa= }
9 \def\@enSp@ce{\@enLab\expandafter{\the\@enLab\space}\@enloop}

```

```
10 \def\@enGroup#1{\@enLab\expandafter{\the\@enLab{#1}}\@enloop}
```

```
11 \def\@enOther#1{\@enLab\expandafter{\the\@enLab#1}\@enloop}
```

```
12 \def\@enloop{\futurelet\@entemp\@enloop@}
```

Hook for possible extensions

24 \fi\fi\fi\fi\fi\fi\fi\fi

25 \@tempa}

To enable a new counter type based on a letter, you just need to add a new `\ifx` clause by analogy with the code above. So for example to make `*` trigger footnote symbol counting, a package should do the following.

```
\providecommand\@enhook{}
```

Add to the hook a new `\ifx` clause that associates `*` with the `\fnsymbol` counter command.

```
\g@addto@macro\@enhook{%
  \ifx *\@entemp
    \def\@tempa{\@enLabel\fnsymbol}%
  \fi}
```

This code sequence should work whether it is loaded before or after this enumerate package. Any number of new counter types may be added in this way.

At this point we just need initialise the hook, taking care not to over write any definitions another package may already have added.

```
26 \providecommand\@enhook{}
```

`\enumerate` The new `enumerate` environment. This is the first half of the original `enumerate` environment. If there is an optional argument, call `\@enum@` to define the label commands, otherwise call `\@enum@` which is the second half of the original definition.

```
27 \def\enumerate{%
28   \ifnum \@enumdepth >3 \toodeep\else
29     \advance\@enumdepth \@ne
30     \edef\@enumctr{enum\romannumeral\the\@enumdepth}\fi
31   \ifnextchar [{\@enum@}{\@enum@}}
```

`\@enum@` Handle the optional argument..

```
32 \def\@enum@[#1]{%
```

Initialise the loop which will break apart the optional argument. The command to print the label is built up in `\@enlab`. `\@enthe` will be used to define `\theenum`.

```
33   \@enlab{}\let\@enthe\@enqmark
```

The `\@enum@` below is never expanded, it is used to detect the end of the token list.

```
34   \@enloop#1\@enum@
```

Issue a warning if we did not find one of the ‘special’ tokens.

```
35   \ifx\@enthe\@enqmark\@warning{The counter will not be printed.%
36   ^^J\space\@spaces\@spaces\@spaces The label is: \the\@enlab}\fi
```

Define `\labelenum` n and `\theenum` n .

```
37   \expandafter\edef\csname label\@enumctr\endcsname{\the\@enlab}%
38   \expandafter\let\csname the\@enumctr\endcsname\@enthe
```

Set the counter to 7 so that we get the width of ‘vii’ if roman numbering is in force then set `\leftmargin` n . to the width of the label plus `\labelsep`.

```
39   \csname c@\@enumctr\endcsname7
40   \expandafter\settowidth
41     \csname leftmargin\romannumeral\@enumdepth\endcsname
42     {\the\@enlab\hspace{\labelsep}}%
```

Finally call `\@enum@` which is the second half of the original definition.

```
43   \@enum@}
```

`\@enum@` All the list parameters have now been defined, so call `\list`. This is taken straight from the original definition of `\enumerate`.

```
44 \def\@enum@{\list{\csname label\@enumctr\endcsname}%
45               {\usecounter{\@enumctr}\def\makelabel##1{\hss\llap{##1}}}}
```

```
46 \endpackage
```