

The univie-ling-wlg class

Jürgen Spitzmüller*

Version 1.5, 2018/09/03

Abstract

The univie-ling-wlg class provides a \LaTeX 2_{ϵ} class suitable for articles in the journal *Wiener Linguistische Gazette* (WLG), the house journal of the Department of Linguistics at the University of Vienna.¹

Contents

1	Aims and scope	2
2	Fonts	2
3	Class Options	2
3.1	Font selection	2
3.2	Package loading	2
3.3	Titlepage settings	3
4	General settings	3
4.1	Editorial data	3
4.2	Titling	3
4.3	Abstract and keywords	3
4.4	Structuring	3
5	Semantic markup	4
6	Linguistic examples and glosses	4
7	Bibliography	5
8	LyX layouts and templates	5
9	Release History	5

*Please report issues via <https://github.com/jspitz/univie-ling>.

¹See <https://wlg.univie.ac.at>.

1 Aims and scope

The `univie-ling-wlg` class provides a \LaTeX 2_{ϵ} class suitable for articles in the journal *Wiener Linguistische Gazette* (WLG) and should be used for contributions to this journal. It comes with suitable `biblatex` style files that follow the style sheet of the journal.

2 Fonts

The class uses PostScript (a. k. a. Type 1) fonts and thus requires classic (PDF)LaTeX.

By default, the class uses by default *Crimson* as a serif font (via the `cochineal` package). Alternatively, the quite similar shaped *MinionPro* can also be used. It covers more glyphs and is probably a bit more polished than *Cochineal*, but due to license reasons it is not included in the common \LaTeX distributions. *MinionPro* is provided by the excellent `FontPro` package.² However, some effort is needed to install the package and fonts. Please refer to the package's documentation in case you are interested.

If you want to use *MinionPro*, use the class option `expertfonts=true` (see sec. 3).

3 Class Options

The `univie-ling-wlg` class provides a range of key=value type options to control the font handling, package loading and some specific behavior. These are documented in this section.

3.1 Font selection

As elaborated above, the package supports only PostScript fonts (via LaTeX and PDFLaTeX). PostScript is the traditional LaTeX font format. Specific LaTeX packages and metrics files are needed to use the fonts (but the default font needed to use this class should be included in your LaTeX distribution and thus ready to use).

The class provides the following option to set the font handling:

`expertfonts=true|false`: if this option is set to `true`, *MinionPro* is used instead of *Crimson*. See sec. 2 for details.

3.2 Package loading

Some extra features provided by the class can be toggled. This might be useful if you do not need the respective feature anyway, and crucial if you need an alternative package that conflicts with one of the preloaded package.

`biblatex=true|false`: If `true`, `biblatex` is loaded with a suitable style. This is actually encouraged. See sec. 7 for details.

`covington=true|false`: If `false`, `covington` is not loaded. `Covington` is used for numbered examples.

²<https://github.com/sebschub/FontPro> <25.01.2017>.

3.3 Titlepage settings

The class can generate a titlepage in two different forms.

titlepage=none|specialprint|issue: If **none** (default), no titlepage is generated. With **issue**, a title page for a whole journal issue is output. With **specialprint**, a special print (“Sonderdruck”) title page suitable for single articles is generated.

4 General settings

4.1 Editorial data

\startpage{<page>} Set start pagination (default: 1).

\issue{<number>}{<year>} Set journal issue (number and year)

\issuetitle{<title>} Set title of special issue

\issuesubtitle{<subtitle>} Set subtitle of special issue

\issueeditors{<names>} Set editors of special issue.

4.2 Titling

\author{<name>}: Article author(s); multiple authors separated by \and. Author affiliations should be specified via the macro **\aff{Affilitation}** immediately behind the author name, using **\aff*[m|f]{Affilitation}** for the corresponding author (the optional argument, **f** or **m**, specifies the gender)

\title{<title>}: Title of the paper.

\subtitle{<subtitle>}: Subtitle.

Use **\maketitle** to set the title after the above settings have been made.

4.3 Abstract and keywords

The abstract is set with the **abstract** environment. Keywords (following the abstract) are set with the **\keywords{<comma-separated keywords>}** macro.

4.4 Structuring

The usual sectioning commands are used. For quotations, it is advised to use the display quote environments provided by the csquotes package (which is automatically loaded). If you want to start your paper with a smart quote, use

\motto[<source>]{Motto}

5 Semantic markup

The class defines some basic semantic markup common in linguistics:

`\Expression{<text>}`: To mark expressions (object language). Typeset in *italics*.

`\Concept{<text>}`: To mark concepts. Typeset in SMALL CAPITALS.

`\Meaning{<text>}`: To mark meaning. Typeset in ‘single quotation marks’.

You can redefine each of these commands, if needed, like this:

```
\renewcommand*\Expression[1]{\textit{#1}}
\renewcommand*\Concept[1]{\textsc{#1}}
\renewcommand*\Meaning[1]{\enquote*{#1}}
```

Furthermore, the class features a `\versal{<text>}` macro to typeset capital text and acronyms (slightly scaled and tracked).

6 Linguistic examples and glosses

The class automatically loads the covington package which provides macros for examples and glosses. Please refer to the covington manual for details.

In addition to covington’s own macros, univie-ling-wlg defines a `subexamples` environment for sub-examples. The code

```
\begin{subexamples}
\item First subexample.
\item Second subexample.
\end{subexamples}
```

will print something like this:

- (1) (a) First subexample.
- (b) Second subexample.

as opposed to covington’s

```
\begin{examples}
\item First example.
\item Second example.
\end{examples}
```

which will print:

- (1) First example.
- (2) Second example.

An `\item` can also hold glosses.

7 Bibliography

If the class option `biblatex=true` is set, the `univie-ling-wlg` class loads a bibliography style which matches journal style sheet. These conventions draw on the *Unified Style Sheet for Linguistics* of the LSA (*Linguistic Society of America*). In order to conform to this style, the `univie-ling-wlg` class uses the `biblatex` package with the `univie-ling` style that is included in the `univie-ling` bundle.

8 LyX layouts and templates

A layout for LyX³ can be retrieved from <https://github.com/jspitz/univie-ling/raw/master/lyx/layouts/univie-ling-wlg.layout>.

A template is provided as well: <https://github.com/jspitz/univie-ling/raw/master/lyx/templates/template-wlg-article.lyx>.

9 Release History

- 2018/09/03 (v. 1.5)
 - Introduce `subexamples` environment.
 - Fix `expertfonts` option.
- 2018/04/26 (v. 1.4) Fix full date issue in `biblatex` bibliography style.
- 2018/03/02 (v. 1.3) Add (CC BY-NC-ND-4.0) license statement to copyright page (via `doclicense` package).
- 2018/02/13 (v. 1.2) Rename `wlg.cls` to `univie-ling-wlg.cls` as per TeXLive request.
- 2018/02/11 (v. 1.1) Initial release to CTAN.

³See <https://www.lyx.org>.