

The package `witharrows`*

F. Pantigny
fpantigny@wanadoo.fr

January 20, 2018

Abstract

The LaTeX package `witharrows` gives an environment `{WithArrows}` which is similar to environment `{aligned}` of `amsmath` (and `mathtools`) but gives the possibility to draw arrows on the right side of the alignment. These arrows are usually used to give explanations concerning the mathematical calculus presented.

This package can be used with `xelatex`, `lualatex`, `pdflatex` but also by the classical workflow `latex-dvips-ps2pdf` (or Adobe Distiller). Two compilations may be necessary. This package requires the packages `expl3`, `xparse` and `tikz`. The following Tikz libraries are also required: `calc`, `arrows.meta` and `bending`.

This package gives an environment `{WithArrows}` to construct alignments of equations with arrows for the explanations on the right side:

```
$\begin{WithArrows}
A & = (a+1)^2 \Arrow{we expand} \\
& = a^2 + 2a + 1 \\
\end{WithArrows}$
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned} \quad \begin{array}{l} \searrow \\ \text{we expand} \end{array}$$

The arrow has been drawn with the command `\Arrow` on the line from which it starts. The command `\Arrow` must be used in the second column (the best way is to put it at the end of the second cell of the line as in the previous exemple).

1 Options for the shape of the arrows

The commande `\Arrow` has several options. These options can be put between square brackets, before, or after the mandatory argument.

The option `jump` gives the number¹ of lines the arrow must jump (the default value is, of course, 1).

```
$\begin{WithArrows}
A & = \bigl((a+b)+1\bigr)^2 \Arrow[jump=2]{we expand} \\
& = (a+b)^2 + 2(a+b) + 1 \\
& = a^2 + 2ab + b^2 + 2a + 2b + 1 \\
\end{WithArrows}$
```

*This document corresponds to the version 1.4 of `witharrows`, at the date of 2018/01/20.

¹It's not possible to give a non-positive value to `jump`. See below (p. 2) the way to draw an arrow which goes backwards.

$$\begin{aligned} A &= ((a+b)+1)^2 \\ &= (a+b)^2 + 2(a+b) + 1 \\ &= a^2 + 2ab + b^2 + 2a + 2b + 1 \end{aligned} \quad \left. \vphantom{\begin{aligned} A &= ((a+b)+1)^2 \\ &= (a+b)^2 + 2(a+b) + 1 \\ &= a^2 + 2ab + b^2 + 2a + 2b + 1 \end{aligned}} \right) \text{we expand}$$

It's possible to put several arrows which start from the same line.

```

\begin{WithArrows}
A &= \bigl((a+b)+1\bigr)^2 \quad \text{\Arrow{\}\Arrow{}}[jump=2] \quad \text{\}
&= (a+b)^2 + 2(a+b) + 1 \quad \text{\}
&= a^2 + 2ab + b^2 + 2a + 2b + 1
\end{WithArrows}$

```

$$\begin{aligned} A &= ((a+b)+1)^2 \\ &= (a+b)^2 + 2(a+b) + 1 \\ &= a^2 + 2ab + b^2 + 2a + 2b + 1 \end{aligned}$$

The option `xoffset` shift the arrows to the right (we usually don't want the arrows to be stucked on the text). The default value of `xoffset` is 3 mm.

```

\begin{WithArrows}
A &= \bigl((a+b)+1\bigr)^2
\Arrow[xoffset=1cm]{with \texttt{xoffset=1cm}} \\\
&= (a+b)^2 + 2(a+b) + 1
\end{WithArrows}$

```

$$\begin{aligned} A &= ((a+b)+1)^2 \\ &= (a+b)^2 + 2(a+b) + 1 \end{aligned} \quad \downarrow \text{with } xoffset=1cm$$

The arrows are drawn with Tikz. That's why the command `\Arrow` has an option `tikz` which can be used to give to the arrow (in fact, the command `\path` of Tikz) the options proposed by Tikz for such an arrow. The following example gives an blue thick arrow.

```
\begin{WithArrows}
A &= (a+1)^2 \xrightarrow[tikz={blue,thick}]{we expand} \backslash
&= a^2 + 2a + 1
\end{WithArrows}
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned} \quad \downarrow \text{we expand}$$

It's also possible to change the arrowheads. For example, we can draw an arrow which goes backwards with the Tikz option `<-`.

```
\begin{WithArrows}
A &= (a+1)^2 \Arrow[tikz=<-]{we factorize} \\\
&= a^2 + 2a + 1
\end{WithArrows}
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned} \quad \uparrow \text{we factorize}$$

It's also possible to suppress both tips of the arrow with the Tikz option `->`.

```
\begin{WithArrows}
A &= (a+1)^2 \xrightarrow[tikz=--]{very classical} \backslash
&= a^2 + 2a + 1
\end{WithArrows}
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned} \quad \Bigg) \textit{ very classical}$$

In order to have straight arrows instead of curved ones, we must use the Tikz option “`bend left = 0`”.

```
$\begin{WithArrows}
A &= (a+1)^2 \Arrow[tikz={bend left=0}]{we expand} \\
&= a^2 + 2a + 1 \\
\end{WithArrows}$
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned} \quad \downarrow \textit{we expand}$$

One of the most useful options is “`text width`” to control the width of the text associated to the arrow.

```
$\begin{WithArrows}
A &= \bigl((a+b)+1\bigr)^2 \\
\Arrow[jump=2,tikz={text width=5.3cm}]{We have done...} \\
&= (a+b)^2 + 2(a+b) + 1 \\
&= a^2 + 2ab + b^2 + 2a + 2b + 1 \\
\end{WithArrows}$
```

$$\begin{aligned} A &= ((a+b)+1)^2 \\ &= (a+b)^2 + 2(a+b) + 1 \\ &= a^2 + 2ab + b^2 + 2a + 2b + 1 \end{aligned} \quad \Bigg) \begin{array}{l} \textit{We have done a two-stages expansion} \\ \textit{but it would have been clever to ex-} \\ \textit{pand with the multinomial theorem.} \end{array}$$

If we want to change the font of the text associated to the arrow, we can, of course, put a command like `\bfseries`, `\large` or `\sffamily` at the beginning of the text. But, by default, the texts are composed with a combination of `\small` and `\itshape`. When adding `\bfseries` at the beginning of the text, we won’t suppress the `\small` and the `\itshape` and we will consequently have a text in a bold, italic and small font.

```
$\begin{WithArrows}
A &= (a+1)^2 \Arrow{\bfseries we expand} \\
&= a^2 + 2a + 1 \\
\end{WithArrows}$
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned} \quad \Bigg) \textit{we expand}$$

If we put commands `\` in the text to force newlines, a command of font placed in the beginning of the text will have effect only until the first command `\` (like in an environment `{tabular}`). That’s why Tikz gives a option `font` to modify the font of the whole text. Nevertheless, if we use the option `tikz={font={\bfseries}}`, the default specification of `\small` and `\itshape` will be overwritten.

```
$\begin{WithArrows}
A &= (a+1)^2 \Arrow[tikz={font={\bfseries}}]{we expand} \\
&= a^2 + 2a + 1 \\
\end{WithArrows}$
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned} \quad \Bigg) \textbf{we expand}$$

If we want exactly the same result as previously, we have to give to the option `font` the value `{\itshape\small\bfseries}`.

Almost all the options can be given directly to the environment `{WithArrows}` (between square brackets). In this case, they apply to all the arrows of the environment.²

²They also apply to the nested environments `{WithArrows}` with the notable exception of `interline`.

```

 $\begin{WithArrows}[tikz=blue]$ 
 $\& = \bigl((a+b)+1\bigr)^2 \quad \text{\Arrow{First expansion.}} \quad \backslash\backslash$ 
 $\& = (a+b)^2 + 2(a+b) + 1 \quad \text{\Arrow{Second expansion.}} \quad \backslash\backslash$ 
 $\& = a^2 + 2ab + b^2 + 2a + 2b + 1$ 
 $\end{WithArrows}$ 

```

$$\begin{aligned}
A &= ((a+b)+1)^2 \\
&= (a+b)^2 + 2(a+b) + 1 && \text{\textit{First expansion.}} \\
&= a^2 + 2ab + b^2 + 2a + 2b + 1 && \text{\textit{Second expansion.}}
\end{aligned}$$

The environment `{WithArrows}` has an option `displaystyle`. With this option, all the elements are composed in `\displaystyle` (like in an environment `{aligned}` of `amsmath`).

Without the option `displaystyle`:

```

 $\begin{WithArrows}$ 
 $\int_0^1 (x+1)^2 dx$ 
 $\& = \int_0^1 (x^2+2x+1) dx$ 
 $\text{\Arrow{linearity of integration}} \quad \backslash\backslash$ 
 $\& = \int_0^1 x^2 dx + 2 \int_0^1 x dx + \int_0^1 dx \quad \backslash\backslash$ 
 $\& = \frac{1}{3} + 2\frac{1}{2} + 1 \quad \backslash\backslash$ 
 $\& = \frac{7}{3}$ 
 $\end{WithArrows}$ 

```

$$\begin{aligned}
\int_0^1 (x+1)^2 dx &= \int_0^1 (x^2 + 2x + 1) dx \\
&= \int_0^1 x^2 dx + 2 \int_0^1 x dx + \int_0^1 dx && \text{\textit{linearity of integration}} \\
&= \frac{1}{3} + 2\frac{1}{2} + 1 \\
&= \frac{7}{3}
\end{aligned}$$

The same example with the option `displaystyle`:

$$\begin{aligned}
\int_0^1 (x+1)^2 dx &= \int_0^1 (x^2 + 2x + 1) dx \\
&= \int_0^1 x^2 dx + 2 \int_0^1 x dx + \int_0^1 dx && \text{\textit{linearity of integration}} \\
&= \frac{1}{3} + 2\frac{1}{2} + 1 \\
&= \frac{7}{3}
\end{aligned}$$

Almost all the options can also be set at the document level with the command `\WithArrowsOptions`. In this case, the scope of the declarations is the current TeX group (these declarations are “semi-global”). For example, if we want all the environments `{WithArrows}` composed in `\displaystyle` with blue arrows, we can write `\WithArrowsOptions{displaystyle,tikz=blue}`.³

```

 $\WithArrowsOptions{displaystyle,tikz=blue}$ 
 $\begin{WithArrows}$ 
 $\sum_{i=1}^n (x_i+1)^2$ 
 $\& = \sum_{i=1}^n (x_i^2+2x_i+1) \quad \text{\Arrow{by linearity}} \quad \backslash\backslash$ 
 $\& = \sum_{i=1}^n x_i^2 + 2\sum_{i=1}^n x_i + n$ 
 $\end{WithArrows}$ 

```

$$\begin{aligned}
\sum_{i=1}^n (x_i+1)^2 &= \sum_{i=1}^n (x_i^2 + 2x_i + 1) \\
&= \sum_{i=1}^n x_i^2 + 2 \sum_{i=1}^n x_i + n && \text{\textit{by linearity}}
\end{aligned}$$

³Since version 1.4 of `witharrows`, it's no longer possible to give these options directly when loading the package, *i.e.* with the command `\usepackage` in the preamble.

The command `\Arrow` is recognized only in the environments `{WithArrows}`. If we have a command `\Arrow` previously defined, it's possible to go on using it outside the environments `{WithArrows}`. However, a previously defined command `\Arrow` may still be useful in an environment `{WithArrows}`. If we want to use it in such an environment, it's possible to change the name of the command `\Arrow` of the package `witharrows`: there is an option `CommandName` for this purpose. The new name of the command must be given to the option *without* the leading backslash.

```
\newcommand{\Arrow}{\longmapsto}
$\begin{WithArrows}[CommandName=Explanation]
f &= \bigl(x \ \Arrow (x+1)^2\bigr)
\Explanation{we work directly on fonctions}\\
&= \bigl(x \ \Arrow x^2+2x+1\bigr)
\end{WithArrows}$
```

$$\begin{aligned} f &= (x \mapsto (x+1)^2) \\ &= (x \mapsto x^2 + 2x + 1) \end{aligned} \quad \Downarrow \text{we work directly on fonctions}$$

It's possible to use directly the nodes created by `{WithArrows}` with explicit Tikz instructions (in order, for example, to draw something that can't be drawn with the command `\Arrow`). That's why a style for the tips of the arrows has been created: `TipsOfWithArrows`. By using this style, we will have homogeneous tips for the arrows of the document.

Therefore, if we want to modify the tips of the arrows of `{WithArrows}`, we have to modify the style `TipsOfWithArrows`.

```
\tikzset{TipsOfWithArrows/.style= { > = {Latex[scale=1.2,bend]}}} }
```

The names of the Tikz nodes created by `witharrows` in the whole document are explained p. 12.

2 Precise positioning of the arrows

The environment `{WithArrows}` defines, during the composition of the array, two series of nodes materialized in red in the following example.⁴

$$\begin{aligned} I &= \int_{\frac{\pi}{4}}^0 \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right)(-du) && \text{left node} \\ &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right)du && \text{right node} \\ &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \frac{1 - \tan u}{1 + \tan u}\right) du && \text{left node} \\ &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{1 + \tan u + 1 - \tan u}{1 + \tan u}\right) du && \text{right node} \\ &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{2}{1 + \tan u}\right) du && \text{left node} \\ &= \int_0^{\frac{\pi}{4}} (\ln 2 - \ln(1 + \tan u)) du && \text{right node} \\ &= \frac{\pi}{4} \ln 2 - \int_0^{\frac{\pi}{4}} \ln(1 + \tan u) du && \text{left node} \\ &= \frac{\pi}{4} \ln 2 - I && \text{right node} \end{aligned}$$

The nodes of the left are at the end of each line of text. These nodes will be called *left nodes*. The nodes of the right side are aligned vertically on the right side of the array. These nodes will be called *right nodes*.

⁴The option `shownodes` can be used to materialize the nodes. The nodes are in fact Tikz nodes of shape “rectangle”, but with zero width. An arrow between two nodes starts at the *south* anchor of the first node and arrives at the *north* anchor of the second node.

By default, the arrows use the right nodes. We will say that they are in **rr** mode (*r* for *right*). These arrows are **vertical** (we will say that an arrow is *vertical* when its two ends have the same abscissa). However, it's possible to use the left nodes, or a combination of left and right nodes, with one of the options **lr**, **rl** and **ll** (*l* for *left*). Those arrows are, usually, not vertical.

$$\begin{aligned}
 \text{Therefore } I &= \int_{\frac{\pi}{4}}^0 \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right)(-du) && \text{This arrow uses the } \texttt{lr} \text{ option.} \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \frac{1 - \tan u}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{1 + \tan u + 1 - \tan u}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{2}{1 + \tan u}\right) du && \text{This arrow uses a } \texttt{ll} \text{ option and a} \\
 &= \int_0^{\frac{\pi}{4}} (\ln 2 - \ln(1 + \tan u)) du && \text{jump equal to 2} \\
 &= \frac{\pi}{4} \ln 2 - \int_0^{\frac{\pi}{4}} \ln(1 + \tan u) du \\
 &= \frac{\pi}{4} \ln 2 - I
 \end{aligned}$$

There is also an option called **i** (*i* for *intermediate*). With this option, the arrow is vertical and at the leftmost position.

```

\begin{WithArrows}
(a+b)(a+ib)(a-b)(a-ib)
& = (a+b)(a-b)\cdot(a+ib)(a-ib) \\\
& = (a^2-b^2)(a^2+b^2) \ \text{\textcolor{blue}{Arrow[i]}because $(x-y)(x+y)=x^2-y^2$}\\
& = a^4-b^4
\end{WithArrows}

```

$$\begin{aligned}
 (a+b)(a+ib)(a-b)(a-ib) &= (a+b)(a-b) \cdot (a+ib)(a-ib) \\
 &= (a^2-b^2)(a^2+b^2) \\
 &= a^4-b^4 \quad \downarrow \text{because } (x-y)(x+y) = x^2-y^2
 \end{aligned}$$

The environment **{WithArrows}** gives also a **group** option. With this option, *all* the arrows of the environment are grouped on a same vertical line and at a leftmost position.

```

\begin{WithArrows}[displaystyle,group]
2xy'-3y=\sqrt{x}
& \Leftrightarrow 2x(K'y_0+Ky'_0)-3Ky_0 = \sqrt{x} \\\
& \Leftrightarrow 2xK'y_0 + K(2xy'_0-3y_0) = \sqrt{x} \\\
& \Leftrightarrow 2xK'y_0 = \sqrt{x} \ \text{\textcolor{blue}{Arrow{...}}}\\\
...
\end{WithArrows}

```

$$\begin{aligned}
 2xy' - 3y &= \sqrt{x} \iff 2x(K'y_0 + Ky'_0) - 3Ky_0 = \sqrt{x} \\
 &\iff 2xK'y_0 + K(2xy'_0 - 3y_0) = \sqrt{x} \\
 &\iff 2xK'y_0 = \sqrt{x} \\
 &\iff 2xK'x^{\frac{3}{2}} = x^{\frac{1}{2}} && \text{We replace } y_0 \text{ by its value.} \\
 &\iff K' = \frac{1}{2x^2} && \text{simplification of the } x \\
 &\iff K = -\frac{1}{2x} && \text{antiderivation}
 \end{aligned}$$

The environment `{WithArrows}` gives also a `groups` option (with a *s* in the name). With this option, the arrows are divided into several “groups”. Each group is a set of connected⁵ arrows. All the arrows of a given group are grouped on a same vertical line and at a leftmost position.

$$\begin{aligned}
 A &= B \\
 &= C + D \quad \left. \begin{array}{l} \nearrow \\ \searrow \end{array} \right\} \begin{array}{l} one \\ two \end{array} \\
 &= D' \\
 &= E + F + G + H + I \\
 &= K + L + M \quad \left. \begin{array}{l} \nearrow \\ \searrow \end{array} \right\} \begin{array}{l} three \\ four \end{array} \\
 &= N \\
 &= O
 \end{aligned}$$

If desired, the option `group` or the option `groups` can be given to the command `\WithArrowsOptions` so that it will become the default value. In this case, it's still possible to come back to the default behaviour for a given environment `{WithArrows}` with the option `rr`: `\begin{WithArrows}{rr}`

3 Comparison with the environment `{aligned}`

`{WithArrows}` bears similarities with the environment `{aligned}` of the extension `amsmath`. These are only similarities because `{WithArrows}` has not been written upon the environment `{aligned}`.⁶

As in the environments of `amsmath`, it's possible to change the spacing between two given lines with the option of the command `\` of end of line (it's also possible to use `*` but it has exactly the same effect as `\` since an environment `{WithArrows}` is always unbreakable).

```

\begin{WithArrows}
A &= (a+1)^2 \Arrow{we expand} \\\[2ex]
&= a^2 + 2a + 1
\end{WithArrows}

```

$$\begin{aligned}
 A &= (a+1)^2 \\
 &= a^2 + 2a + 1 \quad \left. \begin{array}{l} \nearrow \\ \searrow \end{array} \right\} we \ expand
 \end{aligned}$$

In the environments of `amsmath` (or `mathtools`), the spacing between lines is fixed by a parameter called `\jot` (it's a dimension and not a skip). That's also the case for the environment `{WithArrows}`. An option `jot` has been given to the environment `{WithArrows}` in order to change the value of this parameter `\jot` for an given environment.⁷

```

\begin{WithArrows}[displaystyle,jot=2ex]
F &= \frac{1}{2}G \Arrow{we expand} \\\
&= H + \frac{1}{2}K \Arrow{we go on} \\\
&= K
\end{WithArrows}

```

$$\begin{aligned}
 F &= \frac{1}{2}G \\
 &= H + \frac{1}{2}K \quad \left. \begin{array}{l} \nearrow \\ \searrow \end{array} \right\} we \ expand \\
 &= K \quad \left. \begin{array}{l} \nearrow \\ \searrow \end{array} \right\} we \ go \ on
 \end{aligned}$$

However, this new value of `\jot` will also be used in other alignments included in the environment `{WithArrows}`:

⁵More precisely: for each arrow *a*, we note *i(a)* the number of its initial line and *f(a)* the number of its final line ; for two arrows *a* and *b*, we say that *a* ~ *b* when $\llbracket i(a), f(a) \rrbracket \cap \llbracket i(b), f(b) \rrbracket \neq \emptyset$; the groups are the equivalence classes of the transitive closure of ~.

⁶In fact, it's possible to use the package `witharrows` without the package `amsmath`.

⁷It's also possible to change `\jot` with the environment `{spreadlines}` of `mathtools`.

```

 $\begin{WithArrows}[jot=2ex]
\varphi(x,y) = 0 \quad \& \quad \Leftrightarrow (x+y)^2 + (x+2y)^2 = 0
\Arrow{$x$ and $y$ are real}\\
& \Leftrightarrow \left\{ \begin{array}{l} x+y = 0 \\ x+2y = 0 \end{array} \right. \\
\begin{aligned}
x+y &= 0 \\
x+2y &= 0
\end{aligned}
\end{aligned}
\right.
\end{WithArrows}$ 

```

$$\varphi(x,y) = 0 \Leftrightarrow (x+y)^2 + (x+2y)^2 = 0 \quad \left. \vphantom{\varphi(x,y) = 0} \right\} x \text{ and } y \text{ are real}$$

$$\Leftrightarrow \begin{cases} x+y = 0 \\ x+2y = 0 \end{cases}$$

Maybe this doesn't correspond to the desired outcome. That's why an option `interline` is proposed. It's possible to use a skip (`=glue`) for this option.

```

 $\begin{WithArrows}[interline=2ex]
\varphi(x,y) = 0 \quad \& \quad \Leftrightarrow (x+y)^2 + (x+2y)^2 = 0
\Arrow{$x$ and $y$ are real}\\
& \Leftrightarrow \left\{ \begin{array}{l} x+y = 0 \\ x+2y = 0 \end{array} \right. \\
\begin{aligned}
x+y &= 0 \\
x+2y &= 0
\end{aligned}
\end{aligned}
\right.
\end{WithArrows}$ 

```

$$\varphi(x,y) = 0 \Leftrightarrow (x+y)^2 + (x+2y)^2 = 0 \quad \left. \vphantom{\varphi(x,y) = 0} \right\} x \text{ and } y \text{ are real}$$

$$\Leftrightarrow \begin{cases} x+y = 0 \\ x+2y = 0 \end{cases}$$

Like the environment `{aligned}`, `{WithArrows}` has an option of placement which can assume the values `t`, `c` or `b`. However, the default value is not `c` but `t`. If desired, it's possible to have the `c` value as the default with the command `\WithArrowsOptions{c}` at the beginning of the document.

```

 $\begin{WithArrows}
A = (a+1)^2 \quad \& \quad \text{we expand} \\
& = a^2 + 2a + 1
\end{WithArrows}$ 

```

$$\text{So } A = (a+1)^2 \quad \left. \vphantom{A = (a+1)^2} \right\} \text{we expand}$$

$$= a^2 + 2a + 1$$

The value `c` may be useful, for example, if we want to add curly braces:

```

 $\begin{WithArrows}[c]
f(x) = 3x^3 + 2x^2 - x + 4 \\
\text{both are polynoms} \\
g(x) = 5x^2 - 5x + 6
\end{WithArrows}$ 

```


On pose $\left\{ \begin{array}{l} f(x) = 3x^3 + 2x^2 - x + 4 \\ g(x) = 5x^2 - 5x + 6 \end{array} \right\}$ both are *polynoms*

Unlike `{aligned}`, the environment `{WithArrows}` uses `\textstyle` by default.

Once again, it's possible to change this behaviour with `\WithArrowsOptions`:

`\WithArrowsOptions{displaystyle}`.

The following example is composed with `{aligned}`:

$$\left\{ \begin{array}{l} \sum_{i=1}^n (x_i + 1)^2 = \sum_{i=1}^n (x_i^2 + 2x_i + 1) \\ \\ = \sum_{i=1}^n x_i^2 + 2 \sum_{i=1}^n x_i + n \end{array} \right.$$

The following is composed with `{WithArrows}[c,displaystyle]`. The results are stricly identical.⁸

$$\left\{ \begin{array}{l} \sum_{i=1}^n (x_i + 1)^2 = \sum_{i=1}^n (x_i^2 + 2x_i + 1) \\ \\ = \sum_{i=1}^n x_i^2 + 2 \sum_{i=1}^n x_i + n \end{array} \right.$$

4 Examples

4.1 With only one column

It's possible to use the environment `{WithArrows}` with making use of the left column only, or the right column only.

```
\begin{WithArrows}
&f(x) \ge g(x) \ \Arrow{by squaring both sides} \\\
&f(x)^2 \ge g(x)^2 \ \Arrow{by moving to left side} \\\
&f(x)^2 - g(x)^2 \ge 0 \\
\end{WithArrows}
```

$$\begin{array}{l} f(x) \ge g(x) \\ f(x)^2 \ge g(x)^2 \\ f(x)^2 - g(x)^2 \ge 0 \end{array} \quad \begin{array}{l} \\ \downarrow \textit{by squaring both sides} \\ \downarrow \textit{by moving to left side} \end{array}$$

4.2 MoveEqLeft

It's possible to use `\MoveEqLeft` of `mathtools` (if we don't want ampersand on the first line):

```
\begin{WithArrows}[interline=0.5ex]
\MoveEqLeft \arccos(x) = \arcsin \frac{4}{5} + \arcsin \frac{5}{13}
\Arrow{because both are in $[-\frac{\pi}{2}, \frac{\pi}{2}]$} \\\
&\Leftrightarrow x = \sin(\arcsin \frac{4}{5} + \arcsin \frac{5}{13}) \\\
&\Leftrightarrow x = \frac{4}{5} \cos \arcsin \frac{5}{13} + \frac{5}{13} \cos \arcsin \frac{4}{5} \\
\Arrow{\$forall x \in [-1,1], \cos(\arcsin x) = \sqrt{1-x^2}} \\\
&\Leftrightarrow x = \frac{4}{5} \sqrt{1 - (\frac{5}{13})^2} + \frac{5}{13} \sqrt{1 - (\frac{4}{5})^2} \\
+ \frac{5}{13} \sqrt{1 - (\frac{4}{5})^2} \\\
\end{WithArrows}
```

$$\begin{array}{l} \arccos(x) = \arcsin \frac{4}{5} + \arcsin \frac{5}{13} \\ \Leftrightarrow x = \sin \left(\arcsin \frac{4}{5} + \arcsin \frac{5}{13} \right) \\ \Leftrightarrow x = \frac{4}{5} \cos \arcsin \frac{5}{13} + \frac{5}{13} \cos \arcsin \frac{4}{5} \\ \Leftrightarrow x = \frac{4}{5} \sqrt{1 - \left(\frac{5}{13} \right)^2} + \frac{5}{13} \sqrt{1 - \left(\frac{4}{5} \right)^2} \end{array} \quad \begin{array}{l} \\ \\ \downarrow \textit{because both are in } [-\frac{\pi}{2}, \frac{\pi}{2}] \\ \downarrow \forall x \in [-1, 1], \cos(\arcsin x) = \sqrt{1 - x^2} \end{array}$$

⁸In versions of `amsmath` older than the 5 nov. 2016, an thin space was added on the left of an environment `{aligned}`. The new versions do not add this space and neither do `{WithArrows}`.

4.3 Nested environments

The environments `{WithArrows}` can be nested. In this case, the options given to the encompassing environment applies also to the inner ones (with the notable exception of `interline`).

```

 $\begin{WithArrows}[tikz=blue]
\varphi(x,y)=0
& \Leftrightarrow (x+2y)^2+(2x+4y)^2 = 0 \text{ \Arrow{the numbers are real}}
& \Leftrightarrow
\left\{ \begin{array}{l}
x+2y = 0 \\
2x+4y = 0
\end{array} \right.
& \Leftrightarrow
\left\{ \begin{array}{l}
x+2y = 0 \\
x+2y = 0
\end{array} \right.
& \Leftrightarrow x+2y=0
\end{WithArrows}$ 

```

$$\begin{aligned}
\varphi(x,y) = 0 &\Leftrightarrow (x+2y)^2 + (2x+4y)^2 = 0 && \text{the numbers are real} \\
&\Leftrightarrow \begin{cases} x+2y = 0 \\ 2x+4y = 0 \end{cases} \\
&\Leftrightarrow \begin{cases} x+2y = 0 \\ x+2y = 0 \end{cases} && \text{the same equation} \\
&\Leftrightarrow x+2y = 0
\end{aligned}$$

4.4 A loop flow


Here is an example with a loop flow.

```

 $\begin{WithArrows}[tikz={font={\tiny}}]
a.\text{ } f \text{ est continuous on } E
\Arrow{(1)}
b.\text{ } f \text{ est continuous in } 0
\Arrow{(2)}
c.\text{ } f \text{ is bounded on the unit sphere}
\Arrow{(3)}
d.\exists K > 0 \quad \forall x \in E \quad \|f(x)\| \leq K \|x\|
\Arrow{(4)}
e.\text{ } f \text{ is lipschitzian}
\end{WithArrows}$ 

```

- a. f est continuous on E
- b. f est continuous in 0
- c. f is bounded on the unit sphere
- d. $\exists K > 0 \quad \forall x \in E \quad \|f(x)\| \leq K \|x\|$
- e. f is lipschitzian



4.5 Automatic numerotation

The option `font` of Tikz contains in fact a list of tokens which will be placed at the beginning of the text. These tokens can be true commands for a change of font (like `\bfseries` or `\sffamily`) but can also be, in fact, any TeX command.

In the following example, the argument of `font` is the token list `\tiny\counter` where `\counter` is a command which increments a counter previously defined and displays its new value. Thus, the arrows are automatically numbered.

```

\newcounter{MyCounter}
\newcommand{\counter}{\stepcounter{MyCounter}\theMyCounter.}
$\begin{WithArrows}[tikz={font={\tiny\counter}}]
A(x)
&= B(x) \Arrow{} \backslash
&= C(x) \Arrow{} \backslash
&= C(x) \Arrow{} \backslash
&= E(x) \Arrow{} \backslash
&= F(x) \Arrow{} \backslash
&= G(x)
\end{WithArrows}$

```

$$\begin{aligned}
 A(x) &= B(x) \\
 &= C(x) \downarrow^{1.} \\
 &= C(x) \downarrow^{2.} \\
 &= E(x) \downarrow^{3.} \\
 &= F(x) \downarrow^{4.} \\
 &= G(x) \downarrow^{5.}
 \end{aligned}$$

5 Footnotes in the environment WithArrows

If you want to put footnotes in an environment `{WithArrows}`, you can use a pair `\footnotemark–\footnotetext`.

It's also possible to extract the footnotes with the help of the package `footnote` or the package `footnotehyper`.

If `witharrows` is loaded with the option `footnote` (with `\usepackage[footnote]{witharrows}` or with `\PassOptionsToPackage`), the package `footnote` is loaded (if it is not yet loaded) and it is used to extract the footnotes.

If `witharrows` is loaded with the option `footnotehyper`, the package `footnotehyper` is loaded (if it is not yet loaded) and it is used to extract footnotes.

Caution: The packages `footnote` and `footnotehyper` are incompatible. The package `footnotehyper` is the successor of the package `footnote` and should be used preferently. The package `footnote` has some drawbacks, in particular: it must be loaded after the package `xcolor` and it is not perfectly compatible with `hyperref`.

In this document, the package `witharrows` has been loaded with the option `footnotehyper` and we give an example with a footnote in the label of an arrow:

$$\begin{aligned}
 A &= (a + b)^2 \\
 &= a^2 + b^2 + 2ab \quad \downarrow \textit{We expand}^9
 \end{aligned}$$

6 Fine tuning

The version 1.3 of `witharrows` give two new options for a fine tuning of the arrows:

- the option `ystart` set the vertical distance between the base line of the text and the start of the arrow (default value: 0.4 ex).
- the option `ygap` set the vertical distance between two consecutive arrows (default value: 0.4 ex).

These options can be set at the document level or at the environment level.

$$\begin{aligned}
 (\cos x + \sin x)^2 &= \cos^2 x + 2 \cos x \sin x + \sin^2 x \xrightarrow{\text{ystart}} \\
 &= \cos^2 x + \sin^2 x + 2 \sin x \cos x \xrightarrow{\text{ygap}} \\
 &= 1 + \sin(2x)
 \end{aligned}$$

Remark: It's also possible to use the options “`shorten <`” and “`shorten >`” of Tikz (via the option `tikz` of `witharrows`).

⁹A footnote.

7 An technical remark about the names of the nodes

Environments `{WithArrows}` can be nested, and, therefore, we have a “nesting tree” for the environments `{WithArrows}` of the whole document. This nesting tree is used to give a unique name to each node in the document.

The Tikz name of a node created by `witharrows` is prefixed by `wa-`. Then, we have a list of numbers which give the position in the nesting tree and the number of the line in the environment. At the end, we have the suffixe `l` for a “left node” and `r` for a “right node”.

For illustrative purposes, we give an example of nested environments `{WithArrows}`, and, for each “right node”, the name of that node.¹⁰

$$\begin{aligned}
 & A \triangleleft B + B + B + B + B + B + B + B + B + B + B + B + B_{\text{wa-36-1}} \\
 & \triangleleft \begin{cases} C \triangleleft D_{\text{wa-36-1-1}} \\ E \triangleleft F_{\text{wa-36-1-2}} \end{cases} \quad \text{wa-36-2} \\
 & \triangleleft \begin{cases} G \triangleleft H + H + H + H + H + H + H_{\text{wa-36-2-1}} \\ I \triangleleft \begin{cases} J \triangleleft K_{\text{wa-36-2-1-1}} \\ L \triangleleft M_{\text{wa-36-2-1-2}} \end{cases} \end{cases} \quad \begin{matrix} \text{wa-36-3} \\ \text{wa-36-2-2} \end{matrix} \\
 & \triangleleft \begin{cases} N \triangleleft O_{\text{wa-36-3-1}} \\ P \triangleleft Q_{\text{wa-36-3-2}} \end{cases} \quad \text{wa-36-4}
 \end{aligned}$$

The command `\WithArrowsLastEnv` gives the number of the last environment of level 0. For example, we can draw an arrow from the node `wa-36-1` to the node `wa-36-2-1` with the following Tikz command.¹¹

```

\begin{tikzpicture}[remember picture,overlay,->,TipsOfWithArrows]
\draw (wa-\WithArrowsLastEnv-1-r) to (wa-\WithArrowsLastEnv-2-1-r) ;
\end{tikzpicture}

```

8 Implementation

8.1 Declaration of the package and extensions loaded

First, `tikz` and some Tikz libraries are loaded before the `\ProvidesExplPackage`. They are loaded this way because `\usetikzlibrary` in `expl3` code fails.¹²

```

1 \RequirePackage{tikz}
2 \usetikzlibrary{calc,arrows.meta,bending}

```

Then, we can give the traditionnal declaration of a package written with `expl3`:

```

3 \RequirePackage{l3keys2e}
4 \ProvidesExplPackage
5   {witharrows}
6   {\myfiledate}
7   {\myfileversion}
8   {Draws arrows for explanations on the right}

```

The package `xparse` will be used to define the environment `{WithArrows}` and the document-level commands (`\Arrow`, `\WithArrowsOptions` and `\WithArrowsLastEnv`).

```

9 \RequirePackage{xparse}

```

¹⁰There is an option `shownodenames` to show the names of these nodes.

¹¹The command `\WithArrowsLastEnv` is *fully expandable* and thus, can be used directly in the name of a Tikz node.

¹²cf. tex.stackexchange.com/questions/57424/using-of-usetikzlibrary-in-an-expl3-package-fails

8.2 The packages footnote and footnotehyper

A few options can be given to the package `witharrows` when it is loaded (with `\usepackage`, `\RequirePackage` or `\PassOptionsToPackage`). Currently (version 1.4), there are two such options: `footnote` and `footnotehyper`. With the option `footnote`, `witharrows` loads `footnote` and uses it to extract the footnotes from the environments `{WithArrows}`. Idem for the option `footnotehyper`.

The boolean `\g_@@_footnotehyper_bool` will indicate if the option `footnotehyper` is used.

```
10 \bool_new:N \g_@@_footnotehyper_bool
```

The boolean `\g_@@_footnote_bool` will indicate if the option `footnote` is used, but quickly, it will also be set to true if the option `footnotehyper` is used.

```
11 \bool_new:N \g_@@_footnote_bool
```

We define a set of keys `WithArrows/package` for these options. However, first, we define a “level of options” `\l_@@_level_int` even if, in the version 1.4 of `witharrows`, this integer is not used by the options of the set `WithArrows/package`.

```
12 \int_new:N \l_@@_level_int
```

```
13 \keys_define:nn {WithArrows/package}
14   {footnote      .bool_gset:N = \g_@@_footnote_bool,
15   footnotehyper .bool_gset:N = \g_@@_footnotehyper_bool}
```

We process the options when the package is loaded (with `\usepackage`).

```
16 \ProcessKeysOptions {WithArrows/package}
```

```
17 \msg_new:nnn {witharrows}
18   {Option-incompatible-with-Beamer}
19   {The-option-"\tl_use:N \l_keys_key_tl"\ is-incompatible-
20     with-Beamer-because-Beamer-has-its-own-system-to-extract-footnotes.}

21 \msg_new:nnn {witharrows}
22   {footnote-with-footnotehyper-package}
23   {You-can't-use-the-option-footnote-because-the-package-
24     footnotehyper-has-already-been-loaded.~
25     If-you-want,~you-can-use-the-option-"footnotehyper"~and-the-footnotes~
26     within-the-environments~{WithArrows}~will-be-extracted-with-the-tools~
27     of-the-package-footnotehyper.}

28 \msg_new:nnn {witharrows}
29   {footnotehyper-with-footnote-package}
30   {You-can't-use-the-option-"footnotehyper"~because-the-package-
31     footnote-has-already-been-loaded.~
32     If-you-want,~you-can-use-the-option-"footnote"~and-the-footnotes~
33     within-the-environments~{WithArrows}~will-be-extracted-with-the-tools~
34     of-the-package-footnote.}

35 \cs_new_protected:Nn \@@_test_beamer:n
36   {\@ifclassloaded {beamer}
37     {\msg_fatal:nn {witharrows}
38       {Option-incompatible-with-Beamer}}}
39   {} }

40 \bool_if:NT \g_@@_footnote_bool
41   {\@@_test_beamer:n {footnote}
42     \@ifpackageloaded{footnotehyper}
43       {\msg_fatal:nn {witharrows}
44         {footnote-with-footnotehyper-package}}
45     {}
46     \usepackage{footnote}}
```

```

47 \bool_if:NT \g_@@_footnotehyper_bool
48     {\@@_test_beamer:n {footnotehyper}
49      \ifpackageloaded{footnote}
50          {\msg_fatal:nn {witharrows}
51              {footnotehyper~with~footnote~package}}
52      {}
53      \usepackage{footnotehyper}
54      \bool_gset_true:N \g_@@_footnote_bool}

```

The flag `\g_@@_footnote_bool` has been set to `true` and so, we will only have to test `\g_@@_footnote_bool` in order to know if we have to insert an environment `{savenotes}` (see the definition of environment `{WithArrows}`).

8.3 Some technical definitions

We define a Tikz style `@@_node_style` for the nodes that will be created in the `\halign`. The nodes are Tikz nodes of shape “rectangle” but with zero width. An arrow between two nodes starts from the *south* anchor of the first node and arrives at the *north* anchor of the second node.

```

55 \tikzset{@@_node_style/.style={
56     above = \l_@@_ystart_dim,
57     inner~sep = 0 pt,
58     minimum~width = 0pt,
59     minimum~height = \l_@@_ygap_dim,
60     red,
61     \bool_if:NT \l_@@_shownodes_bool {draw}}}

```

The color of the nodes is red, but in fact, the nodes will be drawn only when the option `shownodes` is used (this option is useful for debugging).

We also define a style for the tips of arrow. The final user of the extension `witharrows` will use this style if he wants to draw an arrow directly with a Tikz command in his document (probably using the Tikz nodes created by `{WithArrows}` in the `\halign`).

```

62 \tikzset{TipsOfWithArrows/.style= { > = {Straight~Barb[scale=1.2,bend]}} }

```

In order to increase the interline in the environments `{WithArrows}`, we will use the command `\spread@equation` of `amsmath`. When used, this command becomes no-op (in the current TeX group). Therefore, it will be possible to use the environments of `amsmath` (e.g. `{aligned}`) in an environment `{WithArrows}`.

Nevertheless, we want the extension `witharrows` available without `amsmath`. That’s why we give a definition of `\spread@equation` (this definition will be loaded only if `amsmath` — or `mathtools` — has not been loaded yet).

```

63 \cs_if_free:NT \spread@equation
64     {\cs_set:Npn \spread@equation{\openup\jot
65         \cs_set:Npn \spread@equation {}}}

```

Don’t put `\cs_set_eq:NN \spread@equation \prog_do_nothing:` in the last line because this would raise errors with nested environments.

8.4 Variables

The following sequence is the position of the last environment `{WithArrows}` in the tree of the nested environments `{WithArrows}`.

```

66 \seq_new:N \g_@@_position_in_the_tree_seq
67 \seq_gput_right:Nn \g_@@_position_in_the_tree_seq 1

```

The following counter will give the number of the last environment `{WithArrows}` of level 0. This counter will be used only in the definition of `\WithArrowsLastEnv`.

```

68 \int_new:N \g_@@_last_env_int

```

The following skip (`=glue`) is the vertical space inserted between two lines of the `\halign`.

```

69 \skip_new:N \l_@@_interline_skip

```

If the following flag is raised, then the user can use more than two columns.

```
70 \bool_new:N \l_@@_MoreColumns_bool
```

The following integer indicates the position of the box that will be created: 0 ($=t=\texttt{\backslash vtop}$), 1 ($=c=\texttt{\backslash vcenter}$) or 2 ($=b=\texttt{\backslash vbox}$).

```
71 \int_new:N \l_@@_pos_env_int
```

The integer $\texttt{\backslash l_@@_pos_arrows_int}$ indicates the position of the arrows with the following code:

option	rr	ll	rl	lr	i	group	groups
$\texttt{\backslash l_@@_pos_arrows_int}$	0	1	2	3	4	5	6

```
72 \int_new:N \l_@@_pos_arrows_int
```

When we scan a list of options, we want to be able to raise an error if two options of position of the arrows are present. That's why we keep the code of the first option of position in a variable called $\texttt{\backslash l_@@_previous_pos_arrows_int}$. This variable will be set to -1 each time we start the scanning of a list of options.

```
73 \int_new:N \l_@@_previous_pos_arrows_int
```

The gap between two consecutive arrows.

```
74 \dim_new:N \l_@@_ygap_dim
75 \dim_set:Nn \l_@@_ygap_dim {0.4 ex}
```

The vertical position of the starting point of an arrow.

```
76 \dim_new:N \l_@@_ystart_dim
77 \dim_set:Nn \l_@@_ystart_dim {0.4 ex}
```

The following dimension is the value of the translation of the whole arrow to the right (of course, it's a dimension and not a skip).

```
78 \dim_new:N \l_@@_xoffset_dim
79 \dim_set:Nn \l_@@_xoffset_dim {3mm}
```

If the following flag is raised, the nodes will be drawn in red (useful for debugging).

```
80 \bool_new:N \l_@@_shownodes_bool
```

If the following flag is raised, the name of the “right nodes” will be shown in the document (useful for debugging).

```
81 \bool_new:N \l_@@_shownodenames_bool
```

If the following flag is raised, the elements of the $\texttt{\backslash halign}$ will be composed with $\texttt{\backslash displaystyle}$:

```
82 \bool_new:N \l_@@_displaystyle_bool
```

The following token list variable will contains the Tikz options used to draw the arrows.

```
83 \tl_clear_new:N \l_@@_options_tikz_tl
```

At each possible level for the options (*global*, *environment* or *local*: see below), the new values will be appended on the right of this token list.

The dimension $\texttt{\backslash g_@@_x_dim}$ will be used to compute the x -value for some vertical arrows when one of the options *i*, *group* and *groups* (values 4, 5 and 6 of $\texttt{\backslash l_@@_pos_arrows_int}$) is used.

```
84 \dim_new:N \g_@@_x_dim
```

In the $\texttt{\backslash halign}$ of an environment $\texttt{\{WithArrows\}}$, we will have to use three counters:

- $\texttt{\backslash g_@@_arrow_int}$ to count the arrows created in the environment ;

- `\g_@@_line_int` to count the lines of the `\halign` ;
- `\g_@@_line_bis_int` to count the lines of the `\halign` which have a second column.¹³

These three counters will be incremented in a cell of the `\halign` and, therefore, the incrementation must be global. However, we want to be able to include a `{WithArrows}` in another `{WithArrows}`. To do so, we must restore the previous value of these counters at the end of an environment `{WithArrows}` and we decide to manage a stack for each of these counters.

```

85 \seq_new:N \g_@@_arrow_int_seq
86 \int_new:N \g_@@_arrow_int
87 \seq_new:N \g_@@_line_int_seq
88 \int_new:N \g_@@_line_int
89 \seq_new:N \g_@@_line_bis_int_seq
90 \int_new:N \g_@@_line_bis_int

```

8.5 The definition of the options

There are four levels where options can be set:

- in the options of the `\usepackage`: this level will be called *package* level (number 0);
- with `\WithArrowsOptions{...}`: this level will be called *global* level (number 1);
- with `\begin{WithArrows}[...]`: this level will be called *environment* level (number 2);
- with `\Arrow[...]`: this level will be called *local* level (number 3).

The level is specified in the variable `\l_@@_level_int` and the code attached to the options can use this information to alter their actions.

```

91 \int_set:Nn \l_@@_level_int 1

```

We go on with a submodule which will be loaded only at the global or the environment level.

The options `t`, `c` and `b` indicate if we will create a `\vtop`, a `\vcenter` of a `\vbox`. This information is stored in the variable `\l_@@_pos_env_int`.

```

92 \keys_define:nn {WithArrows/GlobalOrEnv}
93 { t .code:n = {\int_set:Nn \l_@@_pos_env_int 0},
94   t .value_forbidden:n = true,
95   c .code:n = {\int_set:Nn \l_@@_pos_env_int 1},
96   c .value_forbidden:n = true,
97   b .code:n = {\int_set:Nn \l_@@_pos_env_int 2},
98   b .value_forbidden:n = true,

```

The gap between two consecutive arrows.

```

99   ygap .dim_set:N = \l_@@_ygap_dim,
100   ygap .value_required:n = true,

```

The vertical position of the starting point of an arrow.

```

101   ystart .dim_set:N = \l_@@_ystart_dim,
102   ystart .value_required:n = true,

```

Usually, the number of columns in a `{WithArrows}` environment is limited to 2. Nevertheless, it's possible to have more columns with the option `MoreColumns`.

```

103   MoreColumns .bool_set:N = \l_@@_MoreColumns_bool,
104   MoreColumns .value_forbidden:n = true,

```

¹³This counter is used in order to raise an error if there is a line without the second column (such an situation could raise a PGF error for an undefined node).

If the user wants to give a new name to the `\Arrow` command (and the name `\Arrow` remains free).

```

105     CommandName .tl_set:N          = \l_@@_CommandName_tl,
106     CommandName .initial:n         = {\Arrow},
107     CommandName .value_required:n = true,

```

With the option `displaystyle`, the environments will be composed in `\displaystyle`.

```

108     displaystyle .bool_set:N      = \l_@@_displaystyle_bool,

```

With the option `shownodes`, the nodes will be drawn in red (useful only for debugging).

```

109     shownodes .bool_set:N        = \l_@@_shownodes_bool,

```

With the option `shownodenames`, the name of the “right nodes” will be written in the document (useful only for debugging).

```

110     shownodenames .bool_set:N    = \l_@@_shownodenames_bool,

```

With the option `group`, *all* the arrows of the environment are vertical with the same abscissa and at a leftmost position.

```

111     group .code:n      = {\int_compare:nNnT \l_@@_previous_pos_arrows_int > {-1}
112                          {\msg_error:nn {witharrows}
113                           {Two~options~are~incompatible}}}
114                          \int_set:Nn \l_@@_previous_pos_arrows_int 5
115                          \int_set:Nn \l_@@_pos_arrows_int 5},
116     group .value_forbidden:n = true,

```

With the option `groups` (with a *s*), the arrows of the environment are divided in groups by an argument of connexity, and, in each group, the arrows are vertical with the same abscissa and at a leftmost position. When the option `group` or `groups` is used, it’s not possible to an other option of position like `ll`, `lr`, etc. for a individual key.

```

117     groups .code:n      = {\int_compare:nNnT \l_@@_previous_pos_arrows_int > {-1}
118                          {\msg_error:nn {witharrows}
119                           {Two~options~are~incompatible}}}
120                          \int_set:Nn \l_@@_previous_pos_arrows_int 6
121                          \int_set:Nn \l_@@_pos_arrows_int 6},
122     groups .value_forbidden:n = true}

```

Then we define the main module called `WithArrows` which will be loaded at all the levels.

The option `tikz` gives Tikz parameters that will be given to the arrow when it is drawn (more precisely, the parameters will be given to the command `\path` of Tikz).

```

123 \keys_define:nn {WithArrows}
124     {tikz .code:n      = {\tl_put_right:Nn \l_@@_options_tikz_tl {,#1}},
125     tikz .value_required:n = true,

```

The other options are for the position of the arrows. The treatment is the same for the options `ll`, `rr`, `lr`, `rl` and `i` and that’s why a dedicated fonction `\@@_analyze_option_position:n` has been written (see below).

```

126     rr .value_forbidden:n = true,
127     rr .code:n            = {\@@_analyze_option_position:n 0},
128     ll .value_forbidden:n = true,
129     ll .code:n            = {\@@_analyze_option_position:n 1},
130     rl .value_forbidden:n = true,
131     rl .code:n            = {\@@_analyze_option_position:n 2},
132     lr .value_forbidden:n = true,
133     lr .code:n            = {\@@_analyze_option_position:n 3},
134     i .value_forbidden:n = true,
135     i .code:n             = {\@@_analyze_option_position:n 4},

```

The option `xoffset` change the x -offset of the arrows (towards the right). It's a dimension and not a skip. It's not possible to change the value of this parameter for a individual arrow if the option `group` or the option `groups` is used.

```

136     xoffset .code:n = {\bool_if:nTF {\int_compare:nNn \l_@@_level_int = 3 &&
137                               \int_compare:nNn \l_@@_pos_arrows_int > 4}
138                               {\msg_error:nn {witharrows}
139                               {Option~incompatible~with~"group(s)"}}
140                               {\dim_set:Nn \l_@@_xoffset_dim {#1}}},
141     xoffset .value_required:n = true,

```

The option `jot` exists for compatibility. It changes directly the value of the parameter `\jot`, which is a LaTeX parameter and not a parameter specific to `witharrows`. It's allowed only at the level of the environment (maybe we should suppress completely this option in the future).

```

142     jot .code:n = {\int_compare:nNnTF \l_@@_level_int = 2
143                   {\dim_set:Nn \jot {#1}}
144                   {\msg_error:nn {witharrows} {Option~will~be~ignored} }},
145     jot .value_required:n = true,

```

The option `interline` gives the vertical skip (=glue) inserted between two lines (independently of `\jot`). It's accepted only at the level of the environment (this last point is a kind of security). Furthermore, this option has a particular behaviour: it applies only to the current environment and doesn't apply to the nested environments.

```

146     interline .code:n = {\int_compare:nNnTF \l_@@_level_int = 2
147                           {\skip_set:Nn \l_@@_interline_skip {#1}}
148                           {\msg_error:nn {witharrows} {Option~will~be~ignored}}},
149     interline .value_required:n = true,

```

Eventually, a key `jump` (see below) and a key for unknown keys.

```

150     jump .code:n = {\msg_error:nn {witharrows} {Option~will~be~ignored}},
151     unknown .code:n = {\msg_error:nn {witharrows} {Option~unknown}},
152 }

```

The key `jump` indicates the number of lines jumped by the arrow (1 by default). This key will be extracted when the command `\Arrow` will be executed. That's why there is a special module for this key. The key `jump` is extracted in the command `\Arrow` because we want to compute right away the final line of the arrow (this will be useful for the options `group` and `groups`).

```

153 \keys_define:nn {WithArrows/jump}
154     {jump .code:n = {\int_set:Nn \l_@@_jump_int {#1}
155                     \int_compare:nNnF \l_@@_jump_int > 0
156                     {\msg_error:nn {witharrows}
157                     {The~option~"jump"~must~be~non~negative}}},
158     jump .value_required:n = true}

```

The following command is for technical reasons. It's used for the following options of position: `ll`, `lr`, `rl`, `rr` and `i`. The argument is the corresponding code for the position of the arrows.

```

159 \cs_new_protected:Nn \@@_analyze_option_position:n
160     {\int_compare:nNnT \l_@@_previous_pos_arrows_int > {-1}
161       {\msg_error:nn {witharrows}
162         {Two~options~are~incompatible}}
163       \int_set:Nn \l_@@_previous_pos_arrows_int {#1}}

```

It's not possible to use one of the considered options at the level of an arrow (level 2) when the option `group` or the option `groups` is used. However, if we are at the level of an environment, it's possible to override a previous option `group` or `groups` (this previous option `group` or `groups` would necessarily have been set at a global level by `\WithArrowsOptions`).

```

164     \bool_if:nTF { \int_compare:nNn \l_@@_level_int = 3 &&
165                 \int_compare:nNn \l_@@_pos_arrows_int > 4}
166     {\msg_error:nn {witharrows}
167     {Option~incompatible~with~"group(s)"}}
168     {\int_set:Nn \l_@@_pos_arrows_int {#1}}

```

`\WithArrowsOptions` is the command of the `witharrows` package to fix options at the document level.

```

169 \NewDocumentCommand \WithArrowsOptions {m}
170   {\int_set:Nn \l_@@_previous_pos_arrows_int {-1}
171     \keys_set:known:nnN {WithArrows} {#1} \l_tmpa_tl
172     \keys_set:nV {WithArrows/GlobalOrEnv} \l_tmpa_tl}

```

8.6 The command `Arrow`

In fact, the internal command is not named `\Arrow` but `\@@_Arrow`. Usually, at the beginning of an environment `{WithArrows}`, `\Arrow` is set to be equivalent to `\@@_Arrow`. However, the user can change the name with the option `CommandName` and the user command for `\@@_Arrow` will be different. This mechanism can be useful when the user has already a command named `\Arrow` he wants to still be able to use in the environment `{WithArrows}`.

```

173 \NewDocumentCommand \@@_Arrow {0{} m 0{}}
174   {

```

The counter `\g_@@_arrow_int` counts the arrows in the environment. The incrementation must be global (`gincr`) because the command `\Arrow` will be used in the cell of a `\halign`. It's recalled that we manage a stack for this counter.

```

175     \int_gincr:N \g_@@_arrow_int

```

We decide to extract immediatly the key `jump` in order to compute the end line. That's the reason why there is a module `WithArrows/jump` with this sole key. The remained key-value pairs are stored in `\l_tmpa_tl` and will be stored further in the properly list of the arrow.

```

176     \int_zero_new:N \l_@@_jump_int
177     \int_set:Nn \l_@@_jump_int 1
178     \keys_set:known:nnN {WithArrows/jump} {#1,#3} \l_tmpa_tl

```

We will construct a global property list to store the informations of the considered arrow. The four fields of this property list are “initial”, “final”, “options” and “label”.

1. First, the line from which the arrow starts:

```

179     \prop_put:NnV \l_tmpa_prop {initial} \g_@@_line_int

```

2. The line where the arrow ends (that's why it was necessary to extract the key `jump`):

```

180     \int_set:Nn \l_tmpa_int {\g_@@_line_int + \l_@@_jump_int}
181     \prop_put:NnV \l_tmpa_prop {final} \l_tmpa_int

```

3. All the options of the arrow (it's a token list):

```

182     \prop_put:NnV \l_tmpa_prop {options} \l_tmpa_tl

```

4. The label of the arrow (it's also a token list):

```

183     \prop_put:Nnn \l_tmpa_prop {label} {#2}

```

The property list has been created in a local variable for convenience. Now, it will be stored in a global variable indicating both the position-in-the-tree and the number of the arrow.

```

184     \prop_gclear_new:c
185     {g_@@_arrow_\l_@@_prefix_tl _\int_use:N\g_@@_arrow_int _prop}
186     \prop_gset_eq:cN
187     {g_@@_arrow_\l_@@_prefix_tl _\int_use:N\g_@@_arrow_int _prop}
188     \l_tmpa_prop
189   }

```

```

190 \cs_new_protected:Nn \@@_Arrow_first_column:

```

All messages of LaTeX3 must be *fully expandable* and that's why we do the affectation (necessary for a comparison) before the `\msg_error:nn`.

```

191     {\tl_set:Nn \l_tmpa_tl {Arrow}
192      \msg_error:nn {witharrows} {Arrow-in-first-column}
193      \@@_Arrow}

```

8.7 The environnement `{WithArrows}`

The environment `{WithArrows}` starts with the initialisation of the three counters `\g_@@_arrow_int`, `\g_@@_line_int` and `\g_@@_line_bis_int`. However, we have to save their previous values with the three stacks created for this end.

```

194 \NewDocumentEnvironment {WithArrows} {0{}}
195     { \seq_gput_right:NV \g_@@_arrow_int_seq \g_@@_arrow_int
196       \int_gzero:N \g_@@_arrow_int
197       \seq_gput_right:NV \g_@@_line_int_seq \g_@@_line_int
198       \int_gzero:N \g_@@_line_int
199       \seq_gput_right:NV \g_@@_line_bis_int_seq \g_@@_line_bis_int
200       \int_gzero:N \g_@@_line_bis_int

```

We also have to update the position on the nesting tree.

```

201     \seq_gput_right:Nn \g_@@_position_in_the_tree_seq 1

```

The nesting tree is used to create a prefix which will be used in the names of the Tikz nodes and in the names of the arrows (each arrow is a property list of four fields). If we are in the second environment `{WithArrows}` nested in the third environment `{WithArrows}` of the document, the prefix will be 3-2 (although the position in the tree is [3,2,1] since such a position always ends with a 1). First, we do a copy of the position-in-the-tree and then we pop the last element of this copy (in order to drop the last 1).

```

202     \seq_set_eq:NN \l_tmpa_seq \g_@@_position_in_the_tree_seq
203     \seq_pop_right:NN \l_tmpa_seq \l_tmpa_tl
204     \tl_clear_new:N \l_@@_prefix_tl
205     \tl_set:Nx \l_@@_prefix_tl {\seq_use:Nnnn \l_tmpa_seq {-} {-} {-}}

```

The environment `{WithArrows}` must be used in math mode.

```

206     \reverse_if:N \if_mode_math:
207         \msg_error:nn {witharrows} {{WithArrows}-used-outside-math-mode}
208     \fi

```

If the option `footnote` or the option `footnotehyper` is used, then we extract the footnotes with an environment `{savenotes}` (of the package `footnote` or the package `footnotehyper`).

```

209     \bool_if:NT \g_@@_footnote_bool {\begin{savenotes}}

```

We define the command `\` to be the command `\@@_cr`: (defined below).

```

210     \cs_set_eq:NN \ \ \@@_cr:
211     \mathsurround = \c_zero_dim

```

These counters will be used later as variables.

```

212     \int_zero_new:N \l_@@_initial_int
213     \int_zero_new:N \l_@@_final_int
214     \int_zero_new:N \l_@@_arrow_int

```

The value corresponding to the key `interline` is put to zero before the treatment of the options of the environment.¹⁴

```

215     \skip_zero:N \l_@@_interline_skip

```

We process the options given to the `{WithArrows}` environment. The level of options is set to 1.

```

216     \int_set:Nn \l_@@_previous_pos_arrows_int {-1}
217     \int_set:Nn \l_@@_level_int 2
218     \keys_set:known:nnN {WithArrows} {#1} \l_tmpa_tl
219     \keys_set:nV {WithArrows/GlobalOrEnv} \l_tmpa_tl

```

¹⁴It's recalled that, by design, the option `interline` of a environment doesn't apply in the nested environments.

If the user has given a value for the option `CommandName` (at the global or at the *environment* level), a command with this name is defined locally in the environment with meaning `\@@_Arrow`. The default value of the option `CommandName` is “`Arrow`” and thus, by default, the name of the command will be `\Arrow`.

```
220 \cs_set_eq:cn \l_@@_CommandName_tl \@@_Arrow
```

The environment begins with a `\vtop`, a `\vcenter` or a `\vbox`¹⁵ depending of the value of `\l_@@_pos_env_int` (fixed by the options `t`, `c` or `b`). The environment `{WithArrows}` must be used in math mode¹⁶ and therefore, we can use `\vcenter`.

```
221 \int_case:nn \l_@@_pos_env_int
222 {0 {\vtop}
223 1 {\vcenter}
224 2 {\vbox}}
225 \bgroup
```

The command `\spread@equation` is the command used by `amsmath` in the beginning of an alignment to fix the interline. When used, it becomes no-op. However, it’s possible to use `witharrows` without `amsmath` since we have redefined `\spread@equation` (if it is not defined yet).

```
226 \spread@equation
```

We begin the `\halign` and the preamble.

```
227 \ialign\bgroup
```

We increment the counter `\g_@@_line_int` which will be used in the names of the Tikz nodes created in the array. This incrementation must be global (`gincr`) because we are in the cell of a `\halign`. It’s recalled that we manage a stack for this counter.

```
228 \int_gincr:N \g_@@_line_int
229 \cs_set_eq:cn \l_@@_CommandName_tl \@@_Arrow_first_column:
230 \strut\hfil
231 $\bool_if:NT \l_@@_displaystyle_bool \displaystyle {##}$
232 &
```

In the second column, we increment the counter `\g_@@_line_bis_int` because we want to count the lines with a second column and raise an error if there is lines without a second column. Once again, the incrementation must be global and it’s recalled that we manage a stack for this counter too.

```
233 \int_gincr:N \g_@@_line_bis_int
234 $\bool_if:NT \l_@@_displaystyle_bool \displaystyle {{}}{##}$
```

We create the “left node” of the line (when using macros in Tikz node names, the macros have to be fully expandable: here, `\tl_use:N` and `\int_use:N` are fully expandable).

```
235 \tikz[remember~picture,overlay]
236 \node[@@_node_style]
237 (wa-\tl_use:N\l_@@_prefix_tl-\int_use:N\g_@@_line_int-1) {} ;
238 \hfil
```

Now, after the `\hfil`, we create the “right node” and, if the option `shownodenames` is raised, the name of the node is written in the document (useful for debugging).

```
239 \tikz[remember~picture,overlay]
240 \node[@@_node_style]
241 (wa-\tl_use:N\l_@@_prefix_tl-\int_use:N\g_@@_line_int-r) {} ;
242 \bool_if:NT \l_@@_shownodenames_bool
243 {\hbox_overlap_right:n {\small wa-\tl_use:N\l_@@_prefix_tl
244 -\int_use:N\g_@@_line_int}}
```

¹⁵Notice that the use of `\vtop` seems color-safe here...

¹⁶An error is raised if the environment is used outside math mode.

Usually, the `\halign` of an environment `{WithArrows}` will have exactly two columns. Nevertheless, if the user wants to use more columns (without arrows) it's possible with the option `MoreColumns`.

```

245      && \bool_if:NF \l_@@_MoreColumns_bool
246      {\msg_error:nn {witharrows} {Third-column-in-a-{WithArrows}-environment}}
247      $\bool_if:NT \l_@@_displaystyle_bool \displaystyle {##}$
248      \cr
249      }

```

We begin the second part of the environment `{WithArrows}`. We have two `\egroup`: one for the `\halign` and one for the `\vtop` (or `\vcenter` or `\vbox`).

```

250      {\crrcr
251      \egroup
252      \egroup

```

If there is a line without the second column, we raise an error (a line without the second column could generate an PGF error for an unknown node since the nodes are created in the second column).

```

253      \int_compare:nNnT \g_@@_line_bis_int < \g_@@_line_int
254      {\msg_error:nn {witharrows} {All-lines-must-have-an-ampersand}}

```

If there is really arrows in the environment, we draw the arrows:

- if neither option `group` or `groups` is used, we can draw directly ;
- if option `group` or option `groups` is used (`\l_@@_pos_arrows_int > 4`), we have to draw the arrows group by group ; the macro `\@@_draw_arrows:` does the work.

```

255      \int_compare:nNnT \g_@@_arrow_int > 0
256      {\int_compare:nNnTF \l_@@_pos_arrows_int > 4
257      \@@_draw_arrows:
258      {\@@_draw_arrows:nn 1 \g_@@_arrow_int}}

```

If the option `footnote` or the option `footnotehyper` is used, then we extract the footnotes with an environment `{footnote}` (of the package `footnote` or the package `footnotehyper`).

```

259      \bool_if:NT \g_@@_footnote_bool {\end{savenotes}}

```

We update the position-in-the-tree. First, we drop the last component and then we increment the last element.

```

260      \seq_gpop_right:NN \g_@@_position_in_the_tree_seq \l_tmpa_tl
261      \seq_gpop_right:NN \g_@@_position_in_the_tree_seq \l_tmpa_tl
262      \seq_gput_right:Nx \g_@@_position_in_the_tree_seq {\int_eval:n {\l_tmpa_tl + 1}}

```

We update the value of the counter `\g_@@_last_env_int`. This counter is used only by the user function `\WithArrowsLastEnv`.

```

263      \int_compare:nNnT {\seq_count:N \g_@@_position_in_the_tree_seq} = 1
264      {\int_gincr:N \g_@@_last_env_int}

```

Finally, we restore the previous values of the three counters `\g_@@_arrow_int`, `\g_@@_line_int` and `\g_@@_line_bis_int`. It is recalled that we manage three stacks in order to be able to do such a restoration.

```

265      \seq_gpop_right:NN \g_@@_arrow_int_seq {\l_tmpa_tl}
266      \int_gset:Nn \g_@@_arrow_int {\l_tmpa_tl}
267      \seq_gpop_right:NN \g_@@_line_int_seq \l_tmpa_tl
268      \int_gset:Nn \g_@@_line_int {\l_tmpa_tl}
269      \seq_gpop_right:NN \g_@@_line_bis_int_seq \l_tmpa_tl
270      \int_gset:Nn \g_@@_line_bis_int {\l_tmpa_tl}
271      }

```

That’s the end of the environment `{WithArrows}`.

We give now the definition of `\@@_cr`: which is the definition of `\` in an environment `{WithArrows}`. The two `expl3` commands `\group_align_safe_begin:` and `\group_align_safe_end:` are specifically designed for this purpose: test the token that follows in a `\halign` structure.

First, we remove an eventual token `*` since the commands `\` and `*` are equivalent in an environment `{WithArrows}` (an environment `{WithArrows}`, like an environment `{aligned}` of `amsmath` is always unbreakable).

```

272 \cs_set_protected:Nn \@@_cr:
273     {\scan_stop:
274     \group_align_safe_begin:
275     \peek_meaning_remove:NTF * \@@_cr_i: \@@_cr_i:}

```

Then, we peek the next token to see if it’s a `[`. In this case, the command `\` has an optional argument which is the vertical skip (`=glue`) to put.

```

276 \cs_set_protected:Nn \@@_cr_i:
277     {\peek_meaning:NTF [ {\@@_cr_ii:} {\@@_cr_ii: [\c_zero_dim]} }
278 \cs_new_protected:Npn \@@_cr_ii: [#1]
279     {\group_align_safe_end:
280     \cr\noalign{\skip_vertical:n {#1 + \l_@@_interline_skip}
281     \scan_stop:}}

```

According of the documentation of `expl3`, the previous addition in “`#1 + \l_@@_interline_skip`” is really an addition of skips (`=glues`).

8.8 We draw the arrows

`\@@_draw_arrows:` draws the arrows when the option `group` or the option `groups` is used. In both cases, we have to compute the x -value of a group of arrows before actually drawing the arrows of that group. The arrows will actually be drawn by the macro `\@@_draw_arrows:nn`.

```

282 \cs_new_protected:Nn \@@_draw_arrows:
283     { \group_begin:

```

`\l_@@_first_arrow_of_group_int` will be the first arrow of the current group.

`\l_@@_first_line_of_group_int` will be the first line involved in the group of arrows (equal to the initial line of the first arrow of the group because the option `jump` is always positive).

`\l_@@_last_line_of_group_int` will be the last line involved in the group (impossible to guess in advance).

```

284     \int_zero_new:N \l_@@_first_arrow_of_group_int
285     \int_zero_new:N \l_@@_first_line_of_group_int
286     \int_zero_new:N \l_@@_last_line_of_group_int
287     \bool_set_true:N \l_@@_new_group_bool

```

We begin a loop over all the arrows of the environment. Inside this loop, if a group is finished, we will draw the lines of that group.

```

288     \int_set:Nn \l_@@_arrow_int 1
289     \int_until_do:nNnn \l_@@_arrow_int > \g_@@_arrow_int
290     {

```

We extract from the property list of the current arrow the fields “initial” and “final” and we store these values in `\l_@@_initial_int` and `\l_@@_final_int`. However, we have to do a conversion because the components of a property list are token lists.

```

291     \prop_get:cnN {g_@@_arrow_\l_@@_prefix_tl _\int_use:N\l_@@_arrow_int _prop}
292         {initial} \l_tmpa_tl
293     \int_set:Nn \l_@@_initial_int {\l_tmpa_tl}
294     \prop_get:cnN {g_@@_arrow_\l_@@_prefix_tl _\int_use:N\l_@@_arrow_int _prop}
295         {final} \l_tmpa_tl
296     \int_set:Nn \l_@@_final_int {\l_tmpa_tl}

```

We test if the previous arrow was in fact the last arrow of a group. In this case, we have to draw all the arrows of that group (with the x -value computed in `\g_@@_x_dim`).

```

297     \bool_if:nTF { \int_compare_p:nNn \l_@@_pos_arrows_int = 6
298                   && \int_compare_p:nNn \l_@@_arrow_int > 1
299                   && \int_compare_p:nNn \l_@@_initial_int > \l_@@_last_line_of_group_int}
300     {\@@_draw_arrows:nn \l_@@_first_arrow_of_group_int {\l_@@_arrow_int - 1}
301     \bool_set_true:N \l_@@_new_group_bool}

```

The flag `\l_@@_new_group_bool` indicates if we have to begin a new group of arrows. In fact, We have to begin a new group in two circumstances: if we are at the first arrow of the environment (that's why the flag is raised before the beginning of the loop) and if we have just finished a group (that's why the flag is raised in the previous conditionnal). At the beginning of a group, we have to initialize four variables: `\l_@@_first_arrow_int`, `\l_@@_first_line_of_group_int`, `\l_@@_last_line_of_group` and `\g_@@_x_dim` (global for technical reasons). The last two will evolve during the construction of the group.

```

302     \bool_if:nTF \l_@@_new_group_bool
303     {\bool_set_false:N \l_@@_new_group_bool
304     \int_set:Nn \l_@@_first_arrow_of_group_int \l_@@_arrow_int
305     \int_set:Nn \l_@@_first_line_of_group_int \l_@@_initial_int
306     \int_set:Nn \l_@@_last_line_of_group_int \l_@@_final_int
307     \tikz[remember-picture]
308     \path let \p1 = (wa-|tl_use:N\l_@@_prefix_tl-\int_use:N\l_@@_initial_int-1)
309     in \pgfextra {\dim_gset:Nn \g_@@_x_dim {\x1}} ;
310 }

```

If we are not at the beginning of a new group, we actualize `\l_@@_last_line_of_group_int`.

```

311     {\int_set:Nn \l_@@_last_line_of_group_int
312     {\int_max:nn \l_@@_last_line_of_group_int \l_@@_final_int}}

```

We actualise the current x -value (in `\g_@@_x_dim`) even if we are at the beginning of a group. Indeed, the previous initialisation of `\g_@@_x_dim` only considers the initial line of the arrows and now we consider all the lines between the initial and the final line. This is done with `\@@_actualise_x_value:nn`. We have written a command for this because it is also used with the option `i` (`\l_@@_pos_arrows_int = 4`).

```

313     \@@_actualise_x_value:nn \l_@@_initial_int \l_@@_final_int

```

Incrementation of the index of the loop (and end of the loop).

```

314     \int_incr:N \l_@@_arrow_int
315 }

```

After the last arrow of the environment, you have to draw the last group of arrows.

```

316     \@@_draw_arrows:nn \l_@@_first_arrow_of_group_int \g_@@_arrow_int
317     \group_end:
318 }

```

The following code is necessary because we will have to expand an argument exactly 3 times.

```

319 \cs_generate_variant:Nn \keys_set:nn {no}
320 \cs_new_protected:Nn \keys_set_WithArrows: {\keys_set:no {WithArrows}}

```

The macro `\@@_draw_arrows:nn` draws all the arrows whose numbers are between `#1` and `#2`. `#1` and `#2` must be expressions that expands to an integer (they are expanded in the beginning of the macro).

```

321 \cs_new_protected:Nn \@@_draw_arrows:nn
322 {\group_begin:
323  \int_zero_new:N \l_@@_first_arrow_int
324  \int_set:Nn \l_@@_first_arrow_int {#1}
325  \int_zero_new:N \l_@@_last_arrow_int
326  \int_set:Nn \l_@@_last_arrow_int {#2}

```


We begin a loop over the arrows of the environment. The variable `\l_@@_arrow_int` (local in the environment `{WithArrows}`) will be used as index for the loop.

```

327   \int_set:Nn \l_@@_arrow_int \l_@@_first_arrow_int
328   \int_until_do:nNnn \l_@@_arrow_int > \l_@@_last_arrow_int
329   {

```

We extract from the property list of the current arrow the fields “initial” and “final” and we store these values in `\l_@@_initial_int` and `\l_@@_final_int`. However, we have to do a conversion because the components of a property list are token lists.

```

330       \prop_get:cnN {g_@@_arrow_\l_@@_prefix_tl _\int_use:N\l_@@_arrow_int _prop}
331           {initial} \l_tmpa_tl
332   \int_set:Nn \l_@@_initial_int {\l_tmpa_tl}
333   \prop_get:cnN {g_@@_arrow_\l_@@_prefix_tl _\int_use:N\l_@@_arrow_int _prop}
334       {final} \l_tmpa_tl
335   \int_set:Nn \l_@@_final_int {\l_tmpa_tl}

```

If the arrow ends after the last line of the environment, we raise an error.

```

336       \int_compare:nNnT \l_@@_final_int > \g_@@_line_int
337       {\msg_fatal:nn {witharrows} {Too-few-lines-for-an-arrow}}

```

We prepare the process of the options of the current arrow.

```

338       \group_begin:
339       \int_set:Nn \l_@@_previous_pos_arrows_int {-1}
340       \int_set:Nn \l_@@_level_int 3

```

We process the options of the current arrow. The second argument of `\keys_set:nn` must be expanded exactly three times. An x-expansion is not possible because there can be tokens like `\bfseries` in the option `font` of the option `tikz`. This expansion is a bit tricky.

```

341       \prop_get:cnN {g_@@_arrow_\l_@@_prefix_tl
342           _\int_use:N\l_@@_arrow_int _prop} {options} \l_tmpa_tl
343       \exp_args:NNo \exp_args:No \keys_set:WithArrows: {\l_tmpa_tl}

```

We create two booleans to indicate the position of the initial node and final node of the arrow in cases of options `rr`, `rl`, `lr` or `ll`:

```

344       \bool_set_false:N \l_@@_initial_r_bool
345       \bool_set_false:N \l_@@_final_r_bool
346       \int_case:nn \l_@@_pos_arrows_int
347           {0 {\bool_set_true:N \l_@@_initial_r_bool
348               \bool_set_true:N \l_@@_final_r_bool}
349             2 {\bool_set_true:N \l_@@_initial_r_bool}
350             3 {\bool_set_true:N \l_@@_final_r_bool}}

```

In case of option `i` (`\l_@@_pos_arrows_int = 4`), we have to compute the x -value of the arrow (which is vertical). The computed x -value is stored in `\g_@@_x_dim` (the same variable used when the option `group` or the option `groups` is used). This variable is global for technical reasons: we have to do assignments in a Tikz node.

```

351       \int_compare:nNnT \l_@@_pos_arrows_int = 4
352       {

```

First, we calculate the initial value for `\g_@@_x_dim`. We use a Tikz command, but, in fact, nothing is drawn. We use this Tikz command only to read the abscissa of a Tikz node.

```

353           \tikz[remember~picture]
354           \path let \p1 = (wa-\tl_use:N\l_@@_prefix_tl-\int_use:N\l_@@_initial_int-1)
355           in \pgfextra {\dim_gset:Nn \g_@@_x_dim {\x1}} ;

```

A global assignment is necessary because of Tikz.

Then, we will loop to determine the maximal length of all the lines between the lines `\l_@@_initial_int` and `\l_@@_final_int`... but we have written a command dedicated to this work because it will also be used in `\@@_draw_arrows:`.

```

356           \@@_actualise_x_value:nn \l_@@_initial_int \l_@@_final_int
357       }

```

`\l_@@_initial_tl` contains the name of the Tikz node from which the arrow starts (in normal cases... because with the option `i`, `group` and `groups`, the point will perhaps have an other x -value — but always the same y -value). Idem for `\l_@@_final_tl`.

```

358     \tl_set:Nx \l_@@_initial_tl
359         {wa-\tl_use:N\l_@@_prefix_tl-\int_use:N\l_@@_initial_int-
360          \bool_if:NTF\l_@@_initial_r_bool rl .south}
361     \tl_set:Nx \l_@@_final_tl
362         {wa-\tl_use:N\l_@@_prefix_tl-\int_use:N\l_@@_final_int-
363          \bool_if:NTF\l_@@_final_r_bool rl .north}

```

We use “`. north`” because we want a small gap between two consecutive arrows (and the Tikz nodes created have the shape of small vertical segments: use option `shownodes` to visualize the nodes).

We can now draw the arrow in a `{tikzpicture}`:

```

364     \begin{tikzpicture}[remember-picture,
365                         overlay,
366                         align=left,
367                         auto=left,
368                         font = {\small\itshape},
369                         TipsOfWithArrows,
370                         ->,
371                         looseness=1,
372                         bend-left=45]

```

Of course, the arrow is drawn with the command `\draw` of Tikz. The syntax for this command is:

`\draw (x1,y1) to node (name) {contents} (x2,y2)`

The surprising aspect of this syntax is the position of *contents* which is the label of the arrow.

`\p1` and `\p2` are the two ends of the arrow (in fact, if the option `i` or the option `group` is used, it's not exactly the two ends of the arrow because, in this case, the abscissa used is the value previously calculated in `g_@@_x_dim`).

The ability to define `\p1` and `\p2` is given by the library `calc` of Tikz. When `\p1` and `\p2` are defined, the x -value and y -value of these two points can be read in `\x1`, `\x2`, `\y1` and `\y2`. This is the way to have the coordinates of a node defined in Tikz.

```

373     \prop_get:cnN {g_@@_arrow_\l_@@_prefix_tl _\int_use:N\l_@@_arrow_int _prop}
374         {label} \l_tmpa_tl
375     \draw \exp_after:wN [\l_@@_options_tikz_tl]
376         let \p1 = (\tl_use:N \l_@@_initial_tl),
377             \p2 = (\tl_use:N \l_@@_final_tl) in
378         (\int_compare:nNnTF \l_@@_pos_arrows_int > 3
379          {\dim_use:N \g_@@_x_dim + \dim_use:N \l_@@_xoffset_dim, \y1}
380          {\x1 + \dim_use:N \l_@@_xoffset_dim, \y1} )

```

There are two ways to give the content of the node: the classical way, with curly braces, and the option “node contents”. However, both are not strictly equivalent: when `\usetikzlibrary{babel}` is used, the tokens of the contents are rescanned in the first way but not in the second. We don't want the tokens to be rescanned (because this would lead to an error due of the characters `_` and `:` of the `expl3` syntax) and that's why we use the second method. ¹⁷

```

381         to node [node~contents = {\tl_use:N \l_tmpa_tl}] {}
382         (\int_compare:nNnTF \l_@@_pos_arrows_int > 3
383          {\dim_use:N \g_@@_x_dim + \dim_use:N \l_@@_xoffset_dim, \y2}
384          {\x2 + \dim_use:N \l_@@_xoffset_dim, \y2} ) ;
385     \end{tikzpicture}

```

We close the TeX group opened for the options given to `\Arrow[...]` (local level of the options).

```

386     \group_end:
387     \int_incr:N \l_@@_arrow_int
388 }
389 \group_end:
390 }

```

¹⁷cf.: tex.stackexchange.com/questions/298177/how-to-get-around-a-problem-with-usetikzlibrarybabel

The command `\@@actualise_x_value:nn` will analyze the lines between #1 and #2 in order to modify `\g_@@_x_dim` in consequence. More precisely, `\g_@@_x_dim` is increased if a line longer than the current value of `\g_@@_x_dim` is found. `\@@actualise_x_value:nn` is used in `\@@draw_arrows:` (for options `group` and `groups`) and in `\@@draw_arrows:nn` (for option `i`).

```

391 \cs_new_protected:Nn \@@actualise_x_value:nn
392   {\group_begin:
393     \int_set:Nn \l_@@_initial_int {#1}
394     \int_set:Nn \l_@@_final_int {#2}
395     \int_compare:nNnT \l_@@_final_int > \g_@@_line_int
396       {\msg_error:nn {witharrows} {Too-few-lines-for-an-arrow}}

```

We begin a loop with `\l_tmpa_int` as index. In this loop, we use a Tikz command, but, in fact, nothing is drawn. We use this Tikz command only to read the abscissa of a Tikz node.

```

397     \int_set:Nn \l_tmpa_int \l_@@_initial_int
398     \int_until_do:nNnn \l_tmpa_int > \l_@@_final_int
399       {\tikz[remember-picture]
400         \path let \p1 = (wa-\tl_use:N\l_@@_prefix_tl-\int_use:N\l_tmpa_int-1)
401           in \pgfextra {\dim_gset:Nn \g_@@_x_dim {\dim_max:nn \g_@@_x_dim {\x1}}};
402         \int_incr:N \l_tmpa_int
403       }
404   \group_end:
405 }

```

The command `\WithArrowsLastEnv` is not used by the package `witharrows`. It's only a facility given to the final user. It gives the number of the last environment `{WithArrows}` at level 0 (to the sens of the nested environments). This macro is fully expandable and, thus, can be used directly in the name of a Tikz node.

```

406 \NewDocumentCommand \WithArrowsLastEnv {}
407   {\int_use:N \g_@@_last_env_int}

```

8.9 The error messages of the package

```

408 \msg_new:nnn {witharrows}
409   {Third-column-in-a-{WithArrows}-environment}
410   {By-default,~a~\{WithArrows\}-environment-can-only-have-two-columns.~
411     Maybe-you-have-forgotten-a~\str_use:N \c_backslash_str
412     \str_use:N \c_backslash_str.~If-you-really-want-more-than-two-columns,~
413     you-should-use-the-option-"MoreColumns"-at-a-global-level-or-for~
414     an-environment.~However,~you-can-go-one-for-this-time.}

415 \msg_new:nnn {witharrows}
416   {The-option-"jump"-must-be-non-negative}
417   {You-can't-use-a-strictly-negative-value-for-the-option-"jump"-of-command~
418     \token_to_str:N\Arrow.~ You-can-create-an-arrow-going-backwards-with~
419     the-option-"<"-of-Tikz.}

420 \msg_new:nnn {witharrows}
421   {Too-few-lines-for-an-arrow}
422   {An-arrow-specified-in-line-\int_use:N \l_@@_initial_int\ can't-be-drawn~
423     because-it-arrives-after-the-last-line-of-the-environment.}

424 \msg_new:nnn {witharrows}
425   {{WithArrows}-used-outside-math-mode}
426   {The-environment-\{WithArrows\}-should-be-used-only-in-math-mode.~
427     Nevertheless,~you-can-go-on.}

428 \msg_new:nnn {witharrows}
429   {Two-options-are-incompatible}
430   {You-try-to-use-the-option-"\tl_use:N\l_keys_key_tl"-but~
431     this-option-is-incompatible-or-redundant-with-the-option~
432     \int_case:nn\l_@@_previous_pos_arrows_int
433       {0 {rr}
434         1 {ll}
435         2 {rl}
436         3 {lr}

```

```

437         4 {i}
438         5 {group}
439         6 {groups}}"}~
440     previously-set-in-the-same~
441     \int_case:nn\l_@@_level_int
442     {1 {command-\token_to_str:N\WithArrowsOptions}
443      2 {declaration-of-options-of-the-environment-\{WithArrows\}}
444      3 {command-\token_to_str:N\Arrow}}.~
445     If~you-go-on,~I~will~overwrite~the~first~option.}
446 \msg_new:nnnn {witharrows}
447 {All~lines~must~have~an~ampersand}
448 {All~lines~of~an~environment~\{WithArrows\}~must~have~an~second~column~
449  (because~the~nodes~are~created~in~the~second~column).~You~can~go~on~but~maybe~
450  you~will~have~an~pgf~error~for~an~undefined~shape.}
451 {The~ampersand~can~be~implicit~
452  (e.g.~if~you~use~\token_to_str:N\MoveEqLeft\ of~mathtools).}
453 \msg_new:nnn {witharrows}
454 {Option~incompatible~with~"group(s)"}
455 {You~try~to~use~the~option~"\tl_use:N\l_keys_key_tl"~while~
456  you~are~using~the~option~"
457  \int_compare:nNnTF \l_@@_pos_arrows_int = 5
458    {group}
459    {groups}}".~
460  It's~incompatible.~You~can~go~on~ignoring~this~option~
461  "\tl_use:N\l_keys_key_tl"~but~you~should~correct~your~code.}
462 \msg_new:nnn {witharrows}
463 {Option~will~be~ignored}
464 {The~option~"\tl_use:N\l_keys_key_tl"~can't~be~used~here.~
465  If~you~go~on,~it~will~be~ignored.}
466 \msg_new:nnn {witharrows}
467 {Option~unknown}
468 {The~option~"\tl_use:N\l_keys_key_tl"~is~unknown~or~meaningless~in~the~context.~
469  If~you~go~on,~it~will~be~ignored.}
470 \msg_new:nnn {witharrows}
471 {Arrow~in~first~column}
472 {You~should~not~use~the~command~\token_to_str:N\Arrow\
473  \tl_if_eq:NnF \l_@@_CommandName_tl \l_tmpa_tl
474    {(renamed~in~\str_use:N \c_backslash_str
475     \tl_use:N \l_@@_CommandName_tl)~}
476  ~in~the~first~column~but~only~in~the~second~column.~
477  This~is~a~restriction~of~the~version~1.3~of~the~
478  package~witharrows~(in~the~aim~of~developping~further~
479  ~a~new~functionality~with~\token_to_str:N\Arrow\ in~the~
480  first~column).\\
481  However~you~can~go~on~for~this~time.}

```

9 History

9.1 Changes between versions 1.0 and 1.1

Option for the command `\` and option `interline`
 Compatibility with `\usetikzlibrary{babel}`
 Possibility of nested environments `{WithArrows}`
 Better error messages
 Creation of a DTX file

9.2 Changes between versions 1.1 and 1.2

The package `witharrows` can now be loaded without having loaded previously `tikz` and the Tikz libraries `calc`, `arrow.meta` and `bending`.
 New option groups (with a `s`)
 Better error messages

9.3 Changes between versions 1.2 and 1.3

New options `ygap` and `ystart` for fine tuning.
Minor bugs.

9.4 Changes between versions 1.3 and 1.4

The package `footnote` is no longer loaded by default. Instead, two options `footnote` and `footnotehyper` have been added. In particular, `witharrows` becomes compatible with `beamer`.