

The package `witharrows`^{*}

F. Pantigny
`fpantigny@wanadoo.fr`

August 17, 2018

Abstract

The LaTeX package `witharrows` provides an environment `{WithArrows}` which is similar to environment `{aligned}` of `amsmath` (and `mathtools`) but gives the possibility to draw arrows on the right side of the alignment. These arrows are usually used to give explanations concerning the mathematical calculus presented.

This package can be used with `xelatex`, `lualatex`, `pdflatex` but also by the classical workflow `latex-dvips-ps2pdf` (or Adobe Distiller). Two compilations may be necessary. This package requires the packages `expl3`, `xparse` and `tikz`. The following Tikz libraries `arrows.meta` and `bending` are also required.

This package provides an environment `{WithArrows}` to construct alignments of equations with arrows for the explanations on the right side:

```
$\begin{WithArrows} A & = (a+1)^2 \Arrow[we expand] \\ & = a^2 + 2a + 1 \end{WithArrows}$
```

$$A = (a + 1)^2 \\ = a^2 + 2a + 1 \quad \downarrow \text{we expand}$$

The arrow has been drawn with the command `\Arrow` on the row from which it starts. The command `\Arrow` must be used in the second column (the best way is to put it at the end of the second cell of the row as in the previous example).

The environment `{WithArrows}` bears similarities with the environment `{aligned}` of `amsmath` (and `mathtools`). The extension `witharrows` also provides an environment `{DispWithArrows}` which is similar to the environment `{align}` of `amsmath`: cf. p. 13.

1 Options for the shape of the arrows

The command `\Arrow` has several options. These options can be put between square brackets, before, or after the mandatory argument.

The option `jump` gives the number¹ of rows the arrow must jump (the default value is, of course, 1).

```
$\begin{WithArrows} A & = \bigl((a+b)+1\bigr)^2 \Arrow[jump=2]{we expand} \\ & = (a+b)^2 + 2(a+b) +1 \\ & = a^2 + 2ab + b^2 + 2a + 2b +1 \end{WithArrows}$
```

^{*}This document corresponds to the version 1.9 of `witharrows`, at the date of 2018/08/17.

¹It's not possible to give a non-positive value to `jump`. See below (p. 2) the way to draw an arrow which goes backwards.

$$\begin{aligned}
 A &= ((a+b)+1)^2 \\
 &= (a+b)^2 + 2(a+b) + 1 \\
 &= a^2 + 2ab + b^2 + 2a + 2b + 1
 \end{aligned}
 \quad \text{we expand}$$

It's possible to put several arrows which start from the same row.

```
$\begin{WithArrows} \\ A &= \bigl((a+b)+1\bigr)^2 \> \text{\Arrow{} \Arrow{} [jump=2]} \\ &= (a+b)^2 + 2(a+b) + 1 \\ &= a^2 + 2ab + b^2 + 2a + 2b + 1 \end{WithArrows}$
```

$$\begin{aligned}
 A &= ((a+b)+1)^2 \\
 &= (a+b)^2 + 2(a+b) + 1 \\
 &= a^2 + 2ab + b^2 + 2a + 2b + 1
 \end{aligned}
 \quad \downarrow$$

The option `xoffset` shifts the arrows to the right (we usually don't want the arrows to be stucked on the text). The default value of `xoffset` is 3 mm.

```
$\begin{WithArrows} \\ A &= \bigl((a+b)+1\bigr)^2 \\ &\text{\Arrow[xoffset=1cm]{with \texttt{xoffset=1cm}}} \\ &= (a+b)^2 + 2(a+b) + 1 \\ \end{WithArrows}$
```

$$\begin{aligned}
 A &= ((a+b)+1)^2 \\
 &= (a+b)^2 + 2(a+b) + 1
 \end{aligned}
 \quad \downarrow \text{with } xoffset=1cm$$

The arrows are drawn with Tikz. That's why the command `\Arrow` has an option `tikz` which can be used to give to the arrow (in fact, the command `\path` of Tikz) the options proposed by Tikz for such an arrow. The following example gives an thick arrow.

```
$\begin{WithArrows} \\ A &= (a+1)^2 \> \text{\Arrow[tikz=thick]{we expand}} \\ &= a^2 + 2a + 1 \\ \end{WithArrows}$
```

$$\begin{aligned}
 A &= (a+1)^2 \\
 &= a^2 + 2a + 1
 \end{aligned}
 \quad \downarrow \text{we expand}$$

It's also possible to change the arrowheads. For example, we can draw an arrow which goes backwards with the Tikz option `<-`.

```
$\begin{WithArrows} \\ A &= (a+1)^2 \> \text{\Arrow[tikz=<-]{we factorize}} \\ &= a^2 + 2a + 1 \\ \end{WithArrows}$
```

$$\begin{aligned}
 A &= (a+1)^2 \\
 &= a^2 + 2a + 1
 \end{aligned}
 \quad \nearrow \text{we factorize}$$

It's also possible to suppress both tips of the arrow with the Tikz option `-`.

```
$\begin{WithArrows} \\ A &= (a+1)^2 \> \text{\Arrow[tikz=-]{very classical}} \\ &= a^2 + 2a + 1 \\ \end{WithArrows}$
```

$$A = (a + 1)^2 \\ = a^2 + 2a + 1 \quad) \text{ very classical}$$

In order to have straight arrows instead of curved ones, we must use the Tikz option “`bend left = 0`”.

```
$\begin{WithArrows} \\ A &= (a+1)^2 \Arrow[tikz={bend left=0}]{we expand} \\ &= a^2 + 2a + 1 \\ \end{WithArrows}$
```

$$A = (a + 1)^2 \\ = a^2 + 2a + 1 \quad \downarrow \text{we expand}$$

In fact, it's possible to change more drastically the shape or the arrows with the option `TikzCode` presented p. 16.

One of the most useful options is “`text width`” to control the width of the text associated to the arrow.

```
$\begin{WithArrows} \\ A &= \bigl((a+b)+1\bigr)^2 \\ &\Arrow[jump=2,tikz={text width=5.3cm}]{We have done...} \\ &= (a+b)^2 + 2(a+b) + 1 \\ &= a^2 + 2ab + b^2 + 2a + 2b + 1 \\ \end{WithArrows}$
```

$$A = ((a + b) + 1)^2 \\ = (a + b)^2 + 2(a + b) + 1 \\ = a^2 + 2ab + b^2 + 2a + 2b + 1 \quad) \begin{array}{l} \text{We have done a two-stages expansion} \\ \text{but it would have been clever to ex-} \\ \text{pand with the multinomial theorem.} \end{array}$$

In the environments `{DispWithArrows}` and `{DispWithArrows*}`, there is an option `wrap-line`. With this option, the lines of the labels are automatically wrapped on the right: see p. 15.

If we want to change the font of the text associated to the arrow, we can, of course, put a command like `\bfseries`, `\large` or `\sffamily` at the beginning of the text. But, by default, the texts are composed with a combination of `\small` and `\itshape`. When adding `\bfseries` at the beginning of the text, we won't suppress the `\small` and the `\itshape` and we will consequently have a text in a bold, italic and small font.

```
$\begin{WithArrows} \\ A &= (a+1)^2 \Arrow{\bfseries we expand} \\ &= a^2 + 2a + 1 \\ \end{WithArrows}$
```

$$A = (a + 1)^2 \\ = a^2 + 2a + 1 \quad \downarrow \text{we expand}$$

If we put commands `\\\` in the text to force newlines, a command of font placed in the beginning of the text will have effect only until the first command `\\\` (like in an environment `{tabular}`). That's why Tikz gives a option `font` to modify the font of the whole text. Nevertheless, if we use the option `tikz={font=\bfseries}`, the default specification of `\small` and `\itshape` will be overwritten.

```
$\begin{WithArrows} \\ A &= (a+1)^2 \Arrow[tikz={font=\bfseries}]{we expand} \\ &= a^2 + 2a + 1 \\ \end{WithArrows}$
```

$$A = (a + 1)^2 \\ = a^2 + 2a + 1$$

we expand

If we want exactly the same result as previously, we have to give to the option `font` the value `{\itshape\small\bfseries}`.

Almost all the options can be given directly to the environment `{WithArrows}` (between square brackets). In this case, they apply to all the arrows of the environment.²

```
$\begin{WithArrows}[\tikz=blue]
A &= \bigl((a+b)+1\bigr)^2 \Arrow{First expansion.} \\
&= (a+b)^2 + 2(a+b) + 1 \Arrow{Second expansion.} \\
&= a^2 + 2ab + b^2 + 2a + 2b + 1
\end{WithArrows}$
```

$$A = ((a + b) + 1)^2 \\ = (a + b)^2 + 2(a + b) + 1 \\ = a^2 + 2ab + b^2 + 2a + 2b + 1$$

First expansion.
Second expansion.

The environment `{WithArrows}` has an option `displaystyle`. With this option, all the elements are composed in `\displaystyle` (like in an environment `{aligned}` of `amsmath`).

Without the option `displaystyle`:

```
$\begin{WithArrows}
\int_0^1 (x+1)^2 dx
&= \int_0^1 (x^2+2x+1) dx
\Arrow{linearity of integration} \\
&= \int_0^1 x^2 dx + 2 \int_0^1 x dx + \int_0^1 1 dx \\
&= \frac{1}{3} + 2\frac{1}{2} + 1 \\
&= \frac{7}{3}
\end{WithArrows}$
```

$$\int_0^1 (x + 1)^2 dx = \int_0^1 (x^2 + 2x + 1) dx \\ = \int_0^1 x^2 dx + 2 \int_0^1 x dx + \int_0^1 1 dx \quad \text{linearity of integration} \\ = \frac{1}{3} + 2\frac{1}{2} + 1 \\ = \frac{7}{3}$$

The same example with the option `displaystyle`:

$$\int_0^1 (x + 1)^2 dx = \int_0^1 (x^2 + 2x + 1) dx \\ = \int_0^1 x^2 dx + 2 \int_0^1 x dx + \int_0^1 1 dx \quad \text{linearity of integration} \\ = \frac{1}{3} + 2\frac{1}{2} + 1 \\ = \frac{7}{3}$$

The version 1.3 of `witharrows` give two options for a fine tuning of the arrows:

- the option `ystart` set the vertical distance between the base line of the text and the start of the arrow (default value: 0.4 ex);
- the option `ygap` set the vertical distance between two consecutive arrows (default value: 0.4 ex).

²They also apply to the nested environments `{WithArrows}` (with the logical exceptions of `interline`, `CodeBefore` and `CodeAfter`).

$$\begin{aligned}
 (\cos x + \sin x)^2 &= \cos^2 x + 2 \cos x \sin x + \sin^2 x \\
 &= \cos^2 x + \sin^2 x + 2 \sin x \cos x \\
 &= 1 + \sin(2x)
 \end{aligned}$$

Remark: It's also possible to use the options “`shorten <`” and “`shorten >`” of Tikz (via the option `tikz` of `witharrows`).

Almost all the options can also be set at the document level with the command `\WithArrowsOptions`. In this case, the scope of the declarations is the current TeX group (these declarations are “semi-global”). For example, if we want all the environments `{WithArrows}` composed in `\displaystyle` with blue arrows, we can write `\WithArrowsOptions{displaystyle,tikz=blue}`.³

```
\WithArrowsOptions{displaystyle,tikz=blue}
$\begin{WithArrows}
\sum_{i=1}^n (x_{i+1})^2
& = \sum_{i=1}^n (x_i^2 + 2x_i + 1) \Arrow{by linearity}\\
& = \sum_{i=1}^n x_i^2 + 2 \sum_{i=1}^n x_i + n
\end{WithArrows}$
```

$$\begin{aligned}
 \sum_{i=1}^n (x_i + 1)^2 &= \sum_{i=1}^n (x_i^2 + 2x_i + 1) \\
 &= \sum_{i=1}^n x_i^2 + 2 \sum_{i=1}^n x_i + n
 \end{aligned}$$

The command `\Arrow` is recognized only in the environments `{WithArrows}`. If we have a command `\Arrow` previously defined, it's possible to go on using it outside the environments `{WithArrows}`. However, a previously defined command `\Arrow` may still be useful in an environment `{WithArrows}`. If we want to use it in such an environment, it's possible to change the name of the command `\Arrow` of the package `witharrows`: there is an option `CommandName` for this purpose. The new name of the command must be given to the option *without* the leading backslash.

```
\NewDocumentCommand {\Arrow} {} {\longmapsto}
$\begin{WithArrows}[\CommandName=Explanation]
f & = \bigl(x \Arrow (x+1)^2\bigr) \\
& \Explanation{we work directly on fonctions}\\
& = \bigl(x \Arrow x^2+2x+1\bigr)
\end{WithArrows}$
```

$$\begin{aligned}
 f &= (x \longrightarrow (x+1)^2) \\
 &= (x \longrightarrow x^2 + 2x + 1)
 \end{aligned}$$

The environment `{WithArrows}` gives also two options `CodeBefore` and `CodeAfter` for LaTeX code that will be executed at the beginning and at the end of the environment. These options are not designed to be hooks (they are available only at the environment level and they are not applied to the nested environments).

```
$\begin{WithArrows}[\CodeBefore = \color{blue}]
A & = (a+b)^2 \Arrow{we expand} \\
& = a^2 + 2ab + b^2
\end{WithArrows}$
```

$$\begin{aligned}
 A &= (a + b)^2 \\
 &= a^2 + 2ab + b^2
 \end{aligned}$$

Special commands are available in `CodeAfter`: a command `\NbLines` which gives the number of lines (=rows) of the current environment (this is a command and not a counter), a special form of the command `\Arrow` and the command `\MultiArrow`: these commands are described in the section concerning the nested environments, p. 10.

³Since version 1.4 of `witharrows`, it's no longer possible to give these options directly when loading the package, i.e. with the command `\usepackage` in the preamble.

2 Precise positioning of the arrows

The environment `{WithArrows}` defines, during the composition of the array, two series of nodes materialized in red in the following example.⁴

$$\begin{aligned}
 I &= \int_{\frac{\pi}{4}}^0 \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right)(-du) \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \frac{1 - \tan u}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{1 + \tan u + 1 - \tan u}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{2}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} (\ln 2 - \ln(1 + \tan u)) du \\
 &= \frac{\pi}{4} \ln 2 - \int_0^{\frac{\pi}{4}} \ln(1 + \tan u) du \\
 &= \frac{\pi}{4} \ln 2 - I
 \end{aligned}$$

The nodes of the left are at the end of each line of text. These nodes will be called *left nodes*. The nodes of the right side are aligned vertically on the right side of the array. These nodes will be called *right nodes*.

By default, the arrows use the right nodes. We will say that they are in `rr` mode (`r` for *right*). These arrows are `vertical` (we will say that an arrow is *vertical* when its two ends have the same abscissa).

However, it's possible to use the left nodes, or a combination of left and right nodes, with one of the options `lr`, `rl` and `ll` (`l` for *left*). Those arrows are, usually, not vertical.

$$\begin{aligned}
 \text{Therefore } I &= \int_{\frac{\pi}{4}}^0 \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right)(-du) \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \tan\left(\frac{\pi}{4} - u\right)\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(1 + \frac{1 - \tan u}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{1 + \tan u + 1 - \tan u}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} \ln\left(\frac{2}{1 + \tan u}\right) du \\
 &= \int_0^{\frac{\pi}{4}} (\ln 2 - \ln(1 + \tan u)) du \\
 &= \frac{\pi}{4} \ln 2 - \int_0^{\frac{\pi}{4}} \ln(1 + \tan u) du \\
 &= \frac{\pi}{4} \ln 2 - I
 \end{aligned}$$

This arrow uses the `lr` option.

This arrow uses a `ll` option and a jump equal to 2

There is also an option called `i` (`i` for *intermediate*). With this option, the arrow is vertical and at the leftmost position.

⁴The option `shownodes` can be used to materialize the nodes. The nodes are in fact Tikz nodes of shape “rectangle”, but with zero width. An arrow between two nodes starts at the `south` anchor of the first node and arrives at the `north` anchor of the second node.

```

$\\begin{WithArrows}
(a+b)(a+ib)(a-b)(a-ib)
& = (a+b)(a-b)\\cdot(a+ib)(a-ib) \\
& = (a^2-b^2)(a^2+b^2) \\Arrow[i]{because $(x-y)(x+y)=x^2-y^2} \\
& = a^4-b^4
\\end{WithArrows}$

(a + b)(a + ib)(a - b)(a - ib) = (a + b)(a - b) · (a + ib)(a - ib)
= (a2 - b2)(a2 + b2)  $\downarrow$  because  $(x - y)(x + y) = x^2 - y^2$ 
= a4 - b4

```

The environment `{WithArrows}` gives also a `group` option. With this option, *all* the arrows of the environment are grouped on a same vertical line and at a leftmost position.

```

$\\begin{WithArrows}[displaystyle,group]
2xy'-3y=\\sqrt{x}
& \\Longleftarrow 2x(K'y_0+Ky_0')-3Ky_0 = \\sqrt{x} \\
& \\Longleftarrow 2xK'y_0 + K(2xy_0'-3y_0) = \\sqrt{x} \\
& \\Longleftarrow 2xK'y_0 = \\sqrt{x} \\
& \\Longleftarrow 2xK'x^{\\frac{3}{2}} = x^{\\frac{1}{2}} \quad \\downarrow We\ replace\ y_0\ by\ its\ value. \\
& \\Longleftarrow K' = \\frac{1}{2x^2} \quad \\downarrow simplification\ of\ the\ x \\
& \\Longleftarrow K = -\\frac{1}{2x} \quad \\downarrow antiderivation
\\end{WithArrows}$

2xy' - 3y =  $\sqrt{x} \iff 2x(K'y_0 + Ky'_0) - 3Ky_0 = \sqrt{x}$ 
 $\iff 2xK'y_0 + K(2xy'_0 - 3y_0) = \sqrt{x}$ 
 $\iff 2xK'y_0 = \sqrt{x}$ 
 $\iff 2xK'x^{\frac{3}{2}} = x^{\frac{1}{2}}$   $\downarrow$  We replace  $y_0$  by its value.
 $\iff K' = \frac{1}{2x^2}$   $\downarrow$  simplification of the  $x$ 
 $\iff K = -\frac{1}{2x}$   $\downarrow$  antiderivation

```

The environment `{WithArrows}` gives also a `groups` option (with a *s* in the name). With this option, the arrows are divided into several “groups”. Each group is a set of connected⁵ arrows. All the arrows of a given group are grouped on a same vertical line and at a leftmost position.

$$\begin{aligned}
A &= B \\
&= C + D \quad \downarrow one \\
&= D' \quad \downarrow two \\
&= E + F + G + H + I \\
&= K + L + M \quad \downarrow three \\
&= N \quad \downarrow four \\
&= O
\end{aligned}$$

If desired, the option `group` or the option `groups` can be given to the command `\WithArrowsOptions` so that it will become the default value. In this case, it's still possible to come back to the default behaviour for a given environment `{WithArrows}` with the option `rr`: `\begin{WithArrows}[rr]`

3 Comparison with the environment `{aligned}`

`{WithArrows}` bears similarities with the environment `{aligned}` of the extension `amsmath`. These are only similarities because `{WithArrows}` has not been written upon the environment `{aligned}`.⁶

As in the environments of `amsmath`, it's possible to change the spacing between two given rows with the option of the command `\\` of end of line (it's also possible to use `*` but it has exactly the same effect as `\\` since an environment `{WithArrows}` is always unbreakable).

⁵More precisely: for each arrow a , we note $i(a)$ the number of its initial row and $f(a)$ the number of its final line; for two arrows a and b , we say that $a \sim b$ when $[i(a), f(a)] \cap [i(b), f(b)] \neq \emptyset$; the groups are the equivalence classes of the transitive closure of \sim .

⁶In fact, it's possible to use the package `witharrows` without the package `amsmath`.


```
$\begin{WithArrows}
```

$$A &= (a+1)^2 \Arrow{we expand} \\[2ex]$$

$$&= a^2 + 2a + 1$$

```
\end{WithArrows}$
```

$$\begin{aligned} A &= (a+1)^2 \\ &= a^2 + 2a + 1 \end{aligned}$$



In the environments of `amsmath` (or `mathtools`), the spacing between rows is fixed by a parameter called `\jot` (it's a dimension and not a skip). That's also the case for the environment `{WithArrows}`. An option `jot` has been given to the environment `{WithArrows}` in order to change the value of this parameter `\jot` for an given environment.⁷

```
$\begin{WithArrows}[displaystyle,jot=2ex]
```


$$F &= \frac{1}{2}G \Arrow{we expand}\\$$

$$&= H + \frac{1}{2}K \Arrow{we go on}\\$$

$$&= K$$

```
\end{WithArrows}$
```

$$\begin{aligned} F &= \frac{1}{2}G \\ &= H + \frac{1}{2}K \\ &= K \end{aligned}$$



However, this new value of `\jot` will also be used in other alignments included in the environment `{WithArrows}`:

```
$\begin{WithArrows}[jot=2ex]
```


$$\varphi(x,y) = 0 \& \Leftrightarrow (x+y)^2 + (x+2y)^2 = 0$$

$$\& \Arrow{\$x\$ and \$y\$ are real}\&$$

$$\& \Leftrightarrow \left. \begin{aligned} x+y &= 0 \\ x+2y &= 0 \end{aligned} \right\}$$

```
\end{WithArrows}$
```

$$\begin{aligned} \varphi(x,y) = 0 &\Leftrightarrow (x+y)^2 + (x+2y)^2 = 0 \\ &\Leftrightarrow \left. \begin{aligned} x+y &= 0 \\ x+2y &= 0 \end{aligned} \right\} \end{aligned}$$



Maybe this doesn't correspond to the desired outcome. That's why an option `interline` is proposed. It's possible to use a skip (=glue) for this option.

```
$\begin{WithArrows}[interline=2ex]
```

$$\varphi(x,y) = 0 \& \Leftrightarrow (x+y)^2 + (x+2y)^2 = 0$$

$$\& \Arrow{\$x\$ and \$y\$ are real}\&$$

$$\& \Leftrightarrow \left. \begin{aligned} x+y &= 0 \\ x+2y &= 0 \end{aligned} \right\}$$

```
\end{WithArrows}$
```

⁷It's also possible to change `\jot` with the environment `{spreadlines}` of `mathtools`.

$$\varphi(x, y) = 0 \Leftrightarrow (x + y)^2 + (x + 2y)^2 = 0$$

$$\Leftrightarrow \begin{cases} x + y = 0 \\ x + 2y = 0 \end{cases} \quad \left. \begin{array}{l} \\ \end{array} \right\} x \text{ and } y \text{ are real}$$

Like the environment `{aligned}`, `{WithArrows}` has an option of placement which can assume the values `t`, `c` or `b`. However, the default value is not `c` but `t`. If desired, it's possible to have the `c` value as the default with the command `\WithArrowsOptions{c}` at the beginning of the document.

```
So\enskip
$ \begin{WithArrows}
A &= (a+1)^2 \Arrow{we expand} \\
&= a^2 + 2a + 1
\end{WithArrows}$
```

$$\text{So } A = (a + 1)^2 \quad \left. \begin{array}{l} \\ \end{array} \right\} \text{we expand}$$

$$= a^2 + 2a + 1$$

The value `c` may be useful, for example, if we want to add curly braces:

```
On pose\enskip \$\left\{\begin{array}{l}
\begin{WithArrows}[\mathbf{c}]
f(x) &= 3x^3+2x^2-x+4 \\
\Arrow[tikz=-]{both are polynoms} \\
g(x) &= 5x^2-5x+6
\end{WithArrows}
\right.\$
```

$$\text{On pose } \left\{ \begin{array}{l} f(x) = 3x^3 + 2x^2 - x + 4 \\ g(x) = 5x^2 - 5x + 6 \end{array} \right. \text{ both are polynomials}$$

Unlike `{aligned}`, the environment `{WithArrows}` uses `\textstyle` by default.
Once again, it's possible to change this behaviour with `\WithArrowsOptions`:

`\WithArrowsOptions{displaystyle}.`

The following example is composed with `{aligned}`:

$$\left\{ \begin{array}{l} \sum_{i=1}^n (x_i + 1)^2 = \sum_{i=1}^n (x_i^2 + 2x_i + 1) \\ \quad = \sum_{i=1}^n x_i^2 + 2 \sum_{i=1}^n x_i + n \end{array} \right.$$

The following is composed with `{WithArrows}[c,displaystyle]`. The results are strictly identical.⁸

$$\left\{ \begin{array}{l} \sum_{i=1}^n (x_i + 1)^2 = \sum_{i=1}^n (x_i^2 + 2x_i + 1) \\ \quad = \sum_{i=1}^n x_i^2 + 2 \sum_{i=1}^n x_i + n \end{array} \right.$$

⁸In versions of `amsmath` older than the 5 nov. 2016, a thin space was added on the left of an environment `{aligned}`. The new versions do not add this space and neither do `{WithArrows}`.

4 Arrows in nested environments

The environments `{WithArrows}` can be nested. In this case, the options given to the encompassing environment applies also to the inner ones (with logical exceptions for `interline`, `CodeBefore` and `CodeAfter`). The command `Arrow` can be used as usual in each environment `{WithArrows}`.

```

$ \begin{WithArrows}
\varphi(x,y)=0
& \Leftrightarrow (x+2y)^2 + (2x+4y)^2 = 0 \Arrow{the numbers are real} \\
& \Leftrightarrow
\left\{ \begin{aligned}
x+2y &= 0 \\ 
2x+4y &= 0
\end{aligned} \right. \Arrow{tikz=-}{the same equation} \\
& \Leftrightarrow x+2y=0
\end{WithArrows} $

```

$$\begin{aligned}\varphi(x, y) = 0 &\Leftrightarrow (x + 2y)^2 + (2x + 4y)^2 = 0 \\ &\Leftrightarrow \begin{cases} x + 2y = 0 \\ 2x + 4y = 0 \end{cases} \quad \text{the numbers are real} \\ &\Leftrightarrow \begin{cases} x + 2y = 0 \\ x + 2y = 0 \end{cases} \quad \text{the same equation} \\ &\Leftrightarrow x + 2y = 0\end{aligned}$$

However, one may want to draw an arrow between rows that are not in the same environment. For example, one may want to draw the following arrow :

$$\begin{aligned}\varphi(x, y) = 0 &\Leftrightarrow (x + 2y)^2 + (2x + 4y)^2 = 0 \\ &\Leftrightarrow \begin{cases} x + 2y = 0 \\ 2x + 4y = 0 \end{cases} \\ &\Leftrightarrow \begin{cases} x + 2y = 0 \\ x + 2y = 0 \end{cases} \quad \text{Division by 2} \\ &\Leftrightarrow x + 2y = 0\end{aligned}$$

Such a construction is possible by using \Arrow in the CodeAfter option. Indeed, in CodeAfter, a special version of \Arrow is available (we will call it “\Arrow in CodeAfter”).

A command \Arrow in CodeAfter takes three arguments :

- a specification of the start row of the arrow ;
 - a specification of the end row of the arrow ;
 - the label of the arrow.

As usual, it's also possible to give options within square brackets before or after the three arguments. However, these options are limited (see below).

The specification of the row is constructed with the position of the concerned environment in the nesting tree, followed (after an hyphen) by the number of the row.

In the previous example, there are two environments `{WithArrows}` nested in the main environment `{WithArrows}`.

$$\begin{aligned}
\varphi(x, y) = 0 &\Leftrightarrow (x + 2y)^2 + (2x + 4y)^2 = 0 \\
&\Leftrightarrow \begin{cases} x + 2y = 0 \\ 2x + 4y = 0 \end{cases} \quad \text{environment number 1} \\
&\Leftrightarrow \begin{cases} x + 2y = 0 \\ x + 2y = 0 \end{cases} \quad \text{environment number 2} \\
&\Leftrightarrow x + 2y = 0
\end{aligned}$$

The arrow we want to draw starts in the row 2 of the sub-environment number 1 (and therefore, the specification is 1-2) and ends in the row 2 of the sub-environment number 2 (and therefore, the specification is 2-2). We can draw the arrow with the following command `\Arrow` in `CodeAfter` :

```
$\begin{WithArrows}[CodeAfter = {\Arrow{1-2}{2-2}{Division by \$2$}}]
\varphi(x,y)=0
& \Leftrightarrow (x+2y)^2+(2x+4y)^2 = 0 \\
.....
\end{WithArrows}$
```

$$\begin{aligned}
\varphi(x, y) = 0 &\Leftrightarrow (x + 2y)^2 + (2x + 4y)^2 = 0 \\
&\Leftrightarrow \begin{cases} x + 2y = 0 \\ 2x + 4y = 0 \end{cases} \\
&\Leftrightarrow \begin{cases} x + 2y = 0 \\ x + 2y = 0 \end{cases} \quad \text{Division by 2} \\
&\Leftrightarrow x + 2y = 0
\end{aligned}$$

The options allowed for a command `\Arrow` in `CodeAfter` are : `ll`, `lr`, `rl`, `rr`, `v`, `xoffset`, `tikz` and `TikzCode`. Except `v`, which is specific to `\Arrow` in `CodeAfter`, all these options have their usual meaning.

With the option `v`, the arrow drawn is vertical to an abscissa computed with the start row and the end row only : the intermediate lines are not taken into account unlike with the option `i`. Currently, the option `i` is not available for the command `\Arrow` in `CodeAfter`. However, it's always possible to translate an arrow with `xoffset` (or `xshift` of Tikz).

```
$\begin{WithArrows}[CodeAfter = {\Arrow[v]{1-2}{2-2}{Division by \$2$}}]
\varphi(x,y)=0
& \Leftrightarrow (x+2y)^2+(2x+4y)^2 = 0 \\
.....
\end{WithArrows}$
```

$$\begin{aligned}
\varphi(x, y) = 0 &\Leftrightarrow (x + 2y)^2 + (2x + 4y)^2 = 0 \\
&\Leftrightarrow \begin{cases} x + 2y = 0 \\ 2x + 4y = 0 \end{cases} \\
&\Leftrightarrow \begin{cases} x + 2y = 0 \\ x + 2y = 0 \end{cases} \quad \text{Division by 2} \\
&\Leftrightarrow x + 2y = 0
\end{aligned}$$

The package `witharrows` gives also another command available only in `CodeAfter`: the command `\MultiArrow`. This command draws a “rak”. The list of the rows of the environment concerned by this rak are given in the first argument of the command `\MultiArrow`. This list is given with the syntax of the list in a `\foreach` command of `pgfkeys`.


```
$\begin{WithArrows}[tikz = rounded corners,
CodeAfter = {\MultiArrow[1,...,4]{text}}]
A & = B \\
& = C \\

```

```

& = D \\
& = E \\
& = F
\end{WithArrows}$

```



As of now, there is no option available for the command \MultiArrow (maybe in a future release).

5 Arrows from outside environments {WithArrows}

If someone wants to draw arrows from outside the environments `\{WithArrows\}`, he can use the Tikz nodes created in the environments.

The Tikz name of a node created by `witharrows` is prefixed by `wa-`. Then, we have a list of numbers which give the position in the nesting tree and the row number in the environment. At the end, we have the suffix `l` for a “left node” and `r` for a “right node”.

For illustrative purposes, we give an example of nested environments `{WithArrows}`, and, for each “right node”, the name of that node.⁹

The package `witharrows` provides some tools facilitating the use of these nodes:

- the command `\WithArrowsLastEnv` gives the number of the last environment of level 0;
 - a name can be given to a given environment with the option `name` and, in this case, the nodes created in the environment will have aliases constructed with this name;
 - the Tikz style `WithArrows/arrow` is the style used by `witharrows` when drawing an arrow¹⁰;
 - the Tikz style `WithArrows/arrow/tips` is the style for the tip of the arrow (loaded by `WithArrows/arrow`).

For example, we can draw an arrow from `wa-37-2-1-2-r.south` to `wa-37-3-2-r.north` with the following Tikz command.

```
\begin{tikzpicture}[remember picture,overlay]
\draw [WithArrows/arrow]
    ([xshift=3mm]wa-\WithArrowsLastEnv-2-1-2-r.south)
    to ([xshift=3mm]wa-\WithArrowsLastEnv-3-2-r.north) ;
\end{tikzpicture}
```

⁹There is an option `shownodenames` to show the names of these nodes.

¹⁰More precisely, this style is given to the Tikz option “**every path**” before drawing the arrow with the code of the option **TikzCode**. This style is modified (in TeX scopes) by the option **tikz** of **witharrows**.

$$\begin{aligned}
A &\lhd B + B + B + B + B + B + B + B + B + B + B + B \\
&\lhd \left\{ \begin{array}{l} C \lhd D \\ E \lhd F \end{array} \right. \\
&\lhd \left\{ \begin{array}{l} G \lhd H + H + H + H + H + H + H \\ I \lhd \left\{ \begin{array}{l} J \lhd K \\ L \lhd M \end{array} \right. \end{array} \right. \\
&\lhd \left\{ \begin{array}{l} N \lhd O \\ P \lhd Q \end{array} \right. \quad \curvearrowleft
\end{aligned}$$

In this case, it would be easier to use a command `\Arrow` in `CodeAfter` but this is an example to explain how the Tikz nodes created by `witharrows` can be used.

In the following example, we create two environments `{WithArrows}` named “first” and “second” and we draw a line between a node of the first and a node of the second.

```

$\begin{WithArrows} [name=first]
A & = B \\
& = C
\end{WithArrows}$

\bigskip
$\begin{WithArrows} [name=second]
A' & = B' \\
& = C'
\end{WithArrows}$

\begin{tikzpicture} [remember picture,overlay]
\draw [WithArrows/arrow]
($(\text{first}-1-r.south)+(3mm,0)$)
to ($(\text{second}-1-r.north)+(3mm,0)$) ;
\end{tikzpicture}

```

$$\begin{array}{c}
A = B \\
= C \\
A' = B' \\
= C'
\end{array}
\quad
\begin{array}{c}
\curvearrowleft \\
\curvearrowright
\end{array}$$

6 The environment `{DispWithArrows}`

As previously said, the environment `{WithArrows}` bears similarities with the environment `{aligned}` of `amsmath` (and `mathtools`). This extension also provides an environment `{DispWithArrows}` which is similar to the environments `{align}` and `{flalign}` of `amsmath`.

The environment `{DispWithArrows}` must be used *outside* math mode.

```

\begin{DispWithArrows}
A & = (a+1)^2 \Arrow{we expand} \\
& = a^2 + 2a + 1
\end{DispWithArrows}

```

$$A = (a + 1)^2 \quad (1)$$

$$= a^2 + 2a + 1 \quad \downarrow \text{we expand} \quad (2)$$

It's possible to use the command `\notag` (or `\nonumber`) to suppress a tag.

It's possible to use the command `\tag` to put a special tag (e.g. \star).¹¹

It's also possible to put a label to the line of an equation with the command `\label`.¹²

These commands must be in the second column of the environment.

```
\begin{DispWithArrows}
A & = (a+1)^2 \Arrow{we expand} \notag \\
& = a^2 + 2a + 1 \tag{$\star$} \label{my-equation}
\end{DispWithArrows}
```

$$A = (a + 1)^2 \quad (1)$$

$$= a^2 + 2a + 1 \quad \downarrow \text{we expand} \quad (\star) \quad (2)$$

A link to the equation (\star) . This link has been composed with `\eqref{my-equation}` (the command `\eqref` is a command of `amsmath`).

It's also possible to suppress all the autogenerated numbers with the option `notag` (or `nonumber`), at the global or environment level. There is also an environment `{DispWithArrows*}` which suppresses all these numbers.¹³

```
\begin{DispWithArrows*}
A & = (a+1)^2 \Arrow{we expand} \\
& = a^2 + 2a + 1
\end{DispWithArrows*}
```

$$A = (a + 1)^2 \quad (1)$$

$$= a^2 + 2a + 1 \quad \downarrow \text{we expand} \quad (2)$$

With the option `fleqn`, the environment is composed flush left (in a way similar to the option `fleqn` of the standard classes of LaTeX). In this case, the left margin can be controlled with the option `mathindent` (with a name inspired by the parameter `\mathindent` of standard LaTeX). The default value of this parameter is 25 pt.

```
\begin{DispWithArrows} [fleqn,mathindent = 1cm]
A & = (a+1)^2 \Arrow{we expand} \\
& = a^2 + 2a + 1
\end{DispWithArrows}
```

$$A = (a + 1)^2 \quad (3)$$

$$= a^2 + 2a + 1 \quad \downarrow \text{we expand} \quad (4)$$

Remark : By design, the option `fleqn` of `witharrows` is independant of the option `fleqn` of LaTeX. Indeed, since the environments of `witharrows` are meant to be used with arrows on the right side, the user may want to use `witharrows` with the option `fleqn` (in order to have more space on the right of the equations for the arrows) while still centering the classical equations.

¹¹If `amsmath` (or `mathtools`) is loaded, it's also possible to use `\tag*` which, as in `amsmath`, typesets the tag without the parenthesis.

¹²As in the environment `{align}` of `amsmath`, it's not possible to put two commands `\label` in the same line.

¹³Even in this case, it's possible to put a "manual tag" with the command `\tag`.

If the package `amsmath` is loaded, it's possible to use the environment `{subequations}` and the command `\intertext` in the environments `{DispWithArrows}` and `{DispWithArrows*}` (and even the `\intertext` of `nccmath` if this package is loaded).

If the option `leqno` is used (for the document or when the package `amsmath` is loaded), the labels will be composed on the left also for the environments `{DispWithArrows}` et `{DispWithArrows*}`.

The environment `{DispWithArrows}` is similar to the environment `{align}` of `amsmath`. However, `{DispWithArrows}` is not constructed upon `{align}` (in fact, it's possible to use `witharrows` without `amsmath`).

There are differences between `{DispWithArrows}` and `{align}`.

- The environment `{DispWithArrows}` allows only two columns.
- With `{DispWithArrows}`, there is no control of a collision between an equation and its tag.
- An environment `{DispWithArrows}` is always unbreakable (even with `\allowdisplaybreaks` of `amsmath`).
- The commands `\label`, `\tag`, `\notag`, `\nonumber` are allowed only in the second column.
- **Last but not least, by default, the elements of a `{DispWithArrows}` are composed in `textstyle` and not in `displaystyle` (it's possible to change this point with the option `displaystyle`).**

Concerning the references, the package `witharrows` is compatible with the extensions `autonum`, `cleveref`, `fancyref`, `hyperref`, `prettyref`, `refstyle`, `typedref` and `varioref`, and with the options `showonlyrefs` and `showmanualtags` of `mathtools`.¹⁴

It is not compatible with `showkeys` (not all the labels are shown).

The environments `{DispWithArrows}` and `{DispWithArrows*}` provide an option `wrap-lines`. With this option, the lines of the label are automatically wrapped on the right.

```
\begin{DispWithArrows*}[displaystyle,wrap-lines]
S_n
& = \frac{1}{n} \Re \left( \sum_{k=0}^{n-1} (e^{i\frac{\pi}{2n}})^k \right) \\
& \quad \backslash Arrow{sum of terms of a geometric progression of ratio $e^{i\frac{2\pi}{n}}$} \\
& = \frac{1}{n} \Re \left( \frac{1 - (e^{i\frac{\pi}{2n}})^n}{1 - e^{i\frac{\pi}{2n}}} \right) \\
& \quad \backslash Arrow{This line has been wrapped automatically.} \\
& = \frac{1}{n} \Re \left( \frac{1 - e^{i\frac{n\pi}{2}}}{1 - e^{i\frac{\pi}{2n}}} \right)
\end{DispWithArrows*}
```

$$\begin{aligned}
S_n &= \frac{1}{n} \Re \left(\sum_{k=0}^{n-1} \left(e^{i\frac{\pi}{2n}} \right)^k \right) && \text{sum of terms of a geometric progression of ratio } e^{i\frac{2\pi}{n}} \\
&= \frac{1}{n} \Re \left(\frac{1 - \left(e^{i\frac{\pi}{2n}} \right)^n}{1 - e^{i\frac{\pi}{2n}}} \right) && \text{This line has been wrapped automatically.} \\
&= \frac{1}{n} \Re \left(\frac{1 - e^{i\frac{n\pi}{2}}}{1 - e^{i\frac{\pi}{2n}}} \right)
\end{aligned}$$

The option `wrap-lines` doesn't apply to the environments `{WithArrows}` nested in an environment `{DispWithArrows}` or `{DispWithArrows*}`. However, it applies to the instructions `\Arrow` and `\MultiArrow` of the `CodeAfter` of the environment `{DispWithArrows}` or `{DispWithArrows*}`.

¹⁴We recall that `varioref`, `hyperref`, `cleveref` and `autonum` must be loaded in this order. The package `witharrows` can be loaded anywhere.

7 Advanced features

7.1 The option `TikzCode` : how to change the shape of the arrows

The option `TikzCode` allows the user to change the shape of the arrows.¹⁵

The value of this option must be a valid Tikz drawing instruction (with the final semi-colon) with three markers `#1`, `#2` and `#3` for the start point, the end point and the label of the arrow.

By default, the value is the following:

```
\draw (#1) to node {#3} (#2) ;
```

In the following example, we replace this default path by a path with three segments (and the node overwriting the second segment).

```
\begin{WithArrows}[ygap=5pt,interline=4mm,
TikzCode = {\draw[rounded corners]
(#1) -- ($(#1) + (5mm,0)$)
-- node[circle,
draw,
auto = false,
fill = gray!50,
inner sep = 1pt] {\tiny #3}
($(#2) + (5mm,0)$)
-- (#2) ; }]

E & \Longleftarrow 3(2x+4) = 6 & \Arrow{\div 3} \\
& \Longleftarrow 2x+4 = 2 & \Arrow{-4} \\
& \Longleftarrow 2x = -2 & \Arrow{\div 2} \\
& \Longleftarrow x = -1 &
```

$$\begin{aligned} E &\iff 3(2x+4) = 6 \\ &\iff 2x+4 = 2 \\ &\iff 2x = -2 \\ &\iff x = -1 \end{aligned}$$

7.2 Footnotes in the environments of `witharrows`

If you want to put footnotes in an environment `{WithArrows}` or `{DispWithArrows}`, you can use a pair `\footnotemark–\footnotetext`.

It's also possible to extract the footnotes with the help of the package `footnote` or the package `footnotehyper`.

If `witharrows` is loaded with the option `footnote` (with `\usepackage[footnote]{witharrows}` or with `\PassOptionsToPackage`), the package `footnote` is loaded (if it is not yet loaded) and it is used to extract the footnotes.

If `witharrows` is loaded with the option `footnotehyper`, the package `footnotehyper` is loaded (if it is not yet loaded) and it is used to extract footnotes.

Caution: The packages `footnote` and `footnotehyper` are incompatible. The package `footnotehyper` is the successor of the package `footnote` and should be used preferably. The package `footnote` has some drawbacks, in particular: it must be loaded after the package `xcolor` and it is not perfectly compatible with `hyperref`.

¹⁵If the option `wrap-lines` is used in an environment `{DispWithArrows}` or `{DispWithArrows*}`, the option `TikzCode` will have no effect for the arrows of this environment but only for the arrows in the nested environments `{WithArrows}`.

In this document, the package `witharrows` has been loaded with the option `footnotehyper` and we give an example with a footnote in the label of an arrow:

$$\begin{aligned} A &= (a+b)^2 \\ &= a^2 + b^2 + 2ab \end{aligned} \quad \text{\textcolor{red}{\footnote{We expand}}}\text{16}$$

8 Examples

8.1 With only one column

It's possible to use the environment `{WithArrows}` with making use of the left column only, or the right column only.

```
$\begin{WithArrows}
```

$$\begin{aligned} &f(x) \geq g(x) \\ &f(x)^2 \geq g(x)^2 \\ &f(x)^2 - g(x)^2 \geq 0 \end{aligned}$$

\begin{WithArrows}

by squaring both sides
by moving to left side

```
\end{WithArrows}$
```

$$\begin{aligned} f(x) &\geq g(x) && \text{by squaring both sides} \\ f(x)^2 &\geq g(x)^2 && \text{by moving to left side} \\ f(x)^2 - g(x)^2 &\geq 0 \end{aligned}$$

8.2 MoveEqLeft

It's possible to use `\MoveEqLeft` of `mathtools` (if we don't want ampersand on the first line):

```
$\begin{WithArrows}[interline=0.5ex]
```

$$\begin{aligned} \arccos(x) &= \arcsin \frac{4}{5} + \arcsin \frac{5}{13} \\ \Leftrightarrow x &= \sin \left(\arcsin \frac{4}{5} + \arcsin \frac{5}{13} \right) \end{aligned}$$

\begin{WithArrows}

because both are in $[-\frac{\pi}{2}, \frac{\pi}{2}]$

$$\begin{aligned} \Leftrightarrow x &= \frac{4}{5} \cos \arcsin \frac{5}{13} + \frac{5}{13} \cos \arcsin \frac{4}{5} \\ \Leftrightarrow x &= \frac{4}{5} \sqrt{1 - \left(\frac{5}{13}\right)^2} + \frac{5}{13} \sqrt{1 - \left(\frac{4}{5}\right)^2} \end{aligned}$$

\end{WithArrows}\$

$$\begin{aligned} \arccos(x) &= \arcsin \frac{4}{5} + \arcsin \frac{5}{13} && \text{because both are in } [-\frac{\pi}{2}, \frac{\pi}{2}] \\ \Leftrightarrow x &= \sin \left(\arcsin \frac{4}{5} + \arcsin \frac{5}{13} \right) \\ \Leftrightarrow x &= \frac{4}{5} \cos \arcsin \frac{5}{13} + \frac{5}{13} \cos \arcsin \frac{4}{5} \\ \Leftrightarrow x &= \frac{4}{5} \sqrt{1 - \left(\frac{5}{13}\right)^2} + \frac{5}{13} \sqrt{1 - \left(\frac{4}{5}\right)^2} \end{aligned}$$

$\forall x \in [-1, 1], \cos(\arcsin x) = \sqrt{1 - x^2}$

8.3 Modifying the shape of the nodes

It's possible to change the shape of the labels, which are Tikz nodes, by modifying the key “`every node`” of Tikz.

```
\begin{WithArrows}[%
    interline = 4mm,
    tikz = {every node/.style = {circle,
        draw,
        auto = false,
        fill = gray!50,
        inner sep = 1pt,
        font = \tiny}}]
```

¹⁶A footnote.

```

E & \Longleftarrow 3 (2x+4) = 6
\Arrow{$\div 3$} \\
& \Longleftarrow 2x+4 = 2
\Arrow{$-4$} \\
& \Longleftarrow 2x = -2
\Arrow{$\div 2$} \\
& \Longleftarrow 2x = -1
\end{WithArrows}

```

$$\begin{aligned}
E &\iff 3(2x + 4) = 6 \\
&\iff 2x + 4 = 2 \\
&\iff 2x = -2 \\
&\iff 2x = -1
\end{aligned}$$

8.4 Examples with the option TikzCode

We recall that the option `TikzCode` is the Tikz code used by `witharrows` to draw the arrows. The value by default of `TikzCode` is `\draw (#1) to node [#3] (#2) ;` where the three markers `#1`, `#2` and `#3` represent the start row, the end row and the label of the arrow.

8.4.1 Example 1

In the following example, we define the value of `TikzCode` with two instructions `\path`: the first instruction draws the arrow itself and the second puts the label in a Tikz node in the rectangle delimited by the arrow.

```

\$begin{WithArrows}[
    displaystyle,
    ygap = 2mm,
    ystart = 0mm,
    TikzCode = {\draw (#1) -- ++(4.5cm,0) |- (#2) ;
                \path (#1) -- (#2)
                node[text width = 4.2cm, right, midway] {#3} ;}
]
S_n
& = \frac{1}{n} \sum_{k=0}^{n-1} \cos \bigl( \frac{\pi}{2} \cdot \frac{k}{n} \bigr)
.....

```

$$\begin{aligned}
S_n &= \frac{1}{n} \sum_{k=0}^{n-1} \cos \left(\frac{\pi}{2} \cdot \frac{k}{n} \right) \\
&= \frac{1}{n} \sum_{k=0}^{n-1} \Re \left(e^{i \frac{k\pi}{2n}} \right) \\
&= \frac{1}{n} \Re \left(\sum_{k=0}^{n-1} e^{i \frac{k\pi}{2n}} \right) \\
&= \frac{1}{n} \Re \left(\sum_{k=0}^{n-1} \left(e^{i \frac{\pi}{2n}} \right)^k \right) \\
&= \frac{1}{n} \Re \left(\frac{1 - \left(e^{i \frac{\pi}{2n}} \right)^n}{1 - e^{i \frac{\pi}{2n}}} \right) \\
&= \frac{1}{n} \Re \left(\frac{1 - i}{1 - e^{i \frac{\pi}{2n}}} \right)
\end{aligned}$$

$\cos x = \Re(e^{ix})$

$\Re(z + z') = \Re(z) + \Re(z')$

\exp is a morphism for \times et +

sum of terms of a geometric progression of ratio $e^{i \frac{\pi}{2n}}$

8.4.2 Example 2

In the following example, we change the shape of the arrow depending on whether the start row is longer than the end row or not. This example requires the Tikz library `calc`.

```
\begin{WithArrows}[ll, interline=5mm, xoffset=5mm,
TikzCode = {\draw[rounded corners,
every node/.style = {circle,
draw,
auto = false,
inner sep = 1pt,
fill = gray!50,
font = \tiny }]
let \p1 = (#1),
\p2 = (#2)
in \ifdim \x1 > \x2
(\p1) -- node {#3} (\x1,\y2) -- (\p2)
\else
(\p1) -- (\x2,\y1) -- node {#3} (\p2)
\fi ;]
E & \Longleftarrow \frac{(x+4)}{3} + \frac{5x+3}{5} = 7
\Arrow{$\times 15$} \\
& \Longleftarrow 5(x+4) + 3(5x+3) = 105 \\
& \Longleftarrow 5x+20 + 15x+9 = 105 \\
& \Longleftarrow 20x+29 = 105
\Arrow{$-29$} \\
& \Longleftarrow 20x = 76
\Arrow{$\div 20$} \\
& \Longleftarrow x = \frac{38}{10}
```

$$\begin{aligned}
E &\iff \frac{(x+4)}{3} + \frac{5x+3}{5} = 7 \\
&\iff 5(x+4) + 3(5x+3) = 105 \\
&\iff 5x + 20 + 15x + 9 = 105 \\
&\iff 20x + 29 = 105 \\
&\iff 20x = 76 \\
&\iff x = \frac{38}{10}
\end{aligned}$$

8.5 Automatic numbered loop

Assume we want to draw a loop of numbered arrows. In this purpose, it's possible to write a dedicated command `\NumberedLoop` which will do the job when used in `CodeAfter`. In the following example, we write this command with `\NewDocumentCommand` of `xparse` and `\foreach` of `pgffor` (both packages are loaded when `witharrows` is loaded).

```
\NewDocumentCommand \NumberedLoop {}
{\foreach \j in {2, ..., \NbLines}
{ \pgfmathtruncatemacro{\i}{\j-1}
\Arrow[rr]{\i}{\j}{\i}
\Arrow[rr, xoffset=1cm, tikz=<-]{\j}{\NbLines}{\NbLines}}
```

The command `\NbLines` is a command available in `CodeAfter` which gives the total number of lines (=rows) of the current environment (it's a command and not a counter).

```
$\begin{WithArrows}[\CodeAfter = {\NumberedLoop}]
a.\;& f \text{ est continuous on } E \\
b.\;& f \text{ est continuous in } 0 \\
c.\;& f \text{ is bounded on the unit sphere} \\
d.\;& \exists K > 0 \quad \forall x \in E \quad \|f(x)\| \leq K \|x\| \\
e.\;& f \text{ is lipschitzian}
\end{WithArrows}$
```


a. f est continuous on E

b. f est continuous in 0

c. f is bounded on the unit sphere

d. $\exists K > 0 \quad \forall x \in E \quad \|f(x)\| \leq K \|x\|$

e. f is lipschitzian



As usual, it's possible to change the characteristic of both arrows and nodes with the option `tikz`. However, if we want to change the style to have, for example, numbers in parenthesis, the best way is to change the value of `TikzCode`:

```
TikzCode = {\draw (#1) to node {\footnotesize (#3)} (#2) ;}
```


a. f est continuous on E

b. f est continuous in 0

c. f is bounded on the unit sphere

d. $\exists K > 0 \quad \forall x \in E \quad \|f(x)\| \leq K \|x\|$

e. f is lipschitzian



9 Implementation

9.1 Declaration of the package and extensions loaded

First, `tikz` and some `Tikz` libraries are loaded before the `\ProvidesExplPackage`. They are loaded this way because `\usetikzlibrary` in `expl3` code fails.¹⁷

```
1 \RequirePackage{tikz}
2 \usetikzlibrary{arrows.meta,bending}
```

Then, we can give the traditional declaration of a package written with `expl3`:

```
3 \RequirePackage{l3keys2e}
4 \ProvidesExplPackage
5   {witharrows}
6   {\myfiledate}
7   {\myfileversion}
8   {Draws arrows for explanations on the right}
```

The package `xparse` will be used to define the environments `{WithArrows}`, `{DispWithArrows}`, `{DispWithArrows*}` and the document-level commands `\Arrow` and `\WithArrowsOptions`.

```
9 \RequirePackage{xparse}
```

¹⁷cf. tex.stackexchange.com/questions/57424/using-of-usetikzlibrary-in-an-exp13-package-fails

9.2 The packages `footnote` and `footnotehyper`

A few options can be given to the package `witharrows` when it is loaded (with `\usepackage`, `\RequirePackage` or `\PassOptionsToPackage`). Currently (version 1.9), there are two such options: `footnote` and `footnotehyper`. With the option `footnote`, `witharrows` loads `footnote` and uses it to extract the footnotes from the environments `{WithArrows}`. Idem for the option `footnotehyper`.

The boolean `\g_@@_footnotehyper_bool` will indicate if the option `footnotehyper` is used.

```
10 \bool_new:N \g_@@_footnotehyper_bool
```

The boolean `\g_@@_footnote_bool` will indicate if the option `footnote` is used, but quickly, it will also be set to true if the option `footnotehyper` is used.

```
11 \bool_new:N \g_@@_footnote_bool
```

We define a set of keys `WithArrows/package` for these options. However, first, we define a “level of options” `\l_@@_level_int` even if, in the version 1.9 of `witharrows`, this integer is not used by the options of the set `WithArrows/package`.

```
12 \int_new:N \l_@@_level_int
13 \keys_define:nn {WithArrows/package}
14   {footnote      .bool_gset:N = \g_@@_footnote_bool,
15    footnotehyper .bool_gset:N = \g_@@_footnotehyper_bool}
```

We process the options when the package is loaded (with `\usepackage`).

```
16 \ProcessKeysOptions {WithArrows/package}

17 \msg_new:nnn {witharrows}
18   {Option-incompatible-with-Beamer}
19   {The-option-\tl_use:N \l_keys_key_tl"\ is-incompatible-
20    with-Beamer-because-Beamer-has-its-own-system-to-extract-footnotes.}

21 \msg_new:nnn {witharrows}
22   {footnote-with-footnotehyper-package}
23   {You-can't-use-the-option-footnote-because-the-package-
24    footnotehyper-has-already-been-loaded.-
25    If-you-want,-you-can-use-the-option-"footnotehyper"-and-the-footnotes-
26    within-the-environments-{WithArrows}-will-be-extracted-with-the-tools-
27    of-the-package-footnotehyper.}

28 \msg_new:nnn {witharrows}
29   {footnotehyper-with-footnote-package}
30   {You-can't-use-the-option-"footnotehyper"-because-the-package-
31    footnote-has-already-been-loaded.-
32    If-you-want,-you-can-use-the-option-"footnote"-and-the-footnotes-
33    within-the-environments-{WithArrows}-will-be-extracted-with-the-tools-
34    of-the-package-footnote.}

35 \bool_if:NT \g_@@_footnote_bool
36   {\@ifclassloaded{beamer}
37     {\msg_fatal:nn {witharrows}
38       {Option-incompatible-with-Beamer}}
39     {}}
40   \@ifpackageloaded{footnotehyper}
41     {\msg_fatal:nn {witharrows}
42       {footnote-with-footnotehyper-package}}
43     {}}
44   \usepackage{footnote}

45 \bool_if:NT \g_@@_footnotehyper_bool
46   {\@ifclassloaded{beamer}
47     {\msg_fatal:nn {witharrows}
48       {Option-incompatible-with-Beamer}}
49     {}}
50   \@ifpackageloaded{footnote}
```

```

51     {\msg_fatal:nn {witharrows}
52         {footnotehyper~with~footnote~package}}
53     {}
54 \usepackage{footnotehyper}
55 \bool_gset_true:N \g_@@_footnote_bool

```

The flag `\g_@@_footnote_bool` is raised and so, we will only have to test `\g_@@_footnote_bool` in order to known if we have to insert an environnement `{savenotes}` (the `\begin{savenotes}` is in `\@@_pre_environment:n` and `\end{savenotes}` in `\@@_post_environment:` which are executed at the beginning and at the end of the environments `{WithArrows}` and `{DispWithArrows}`).

9.3 Some technical definitions

We create booleans in order to known if some packages are loaded. For example, for the package `amsmath`, the boolean is called `\c_@@_amsmath_loaded_bool`.¹⁸

```

56 \AtBeginDocument{\clist_map_inline:nn
57     {amsmath,mathtools,autonum,cleveref,hyperref,typedref}
58     {\bool_new:c {c_@@_#1_loaded_bool}
59      \c_ifpackageloaded {#1}
60      {\bool_set_true:c {c_@@_#1_loaded_bool}}
61      {}}}

```

We define a Tikz style `@@_node_style` for the nodes that will be created in the `\halign`. The nodes are Tikz nodes of shape “rectangle” but with zero width. An arrow between two nodes starts from the *south* anchor of the first node and arrives at the *north* anchor of the second node.

```

62 \tikzset{@@_node_style/.style= {
63     above = \l_@@_ystart_dim,
64     inner sep = 0 pt,
65     minimum width = 0pt,
66     minimum height = \l_@@_ygap_dim,
67     red,
68     \bool_if:NT \l_@@_shownodes_bool {draw} }}

```

The color of the nodes is red, but in fact, the nodes will be drawn only when the option `shownodes` is used (this option is useful for debugging).

The style `@@_standard` is load in standard in the `{tikzpicture}` we need. The names of the nodes are prefixed by `wa` (by security) but also by a prefix which is the position-in-the-tree of the nested environments.

```

69 \tikzset{@@_standard/.style= { remember picture,
70     overlay,
71     name prefix = wa-\l_@@_prefix_str- }}

```

We also define a style for the tips of arrow. The final user of the extension `witharrows` will use this style if he wants to draw an arrow directly with a Tikz command in his document (probably using the Tikz nodes created by `{WithArrows}` in the `\halign`).

```

72 \tikzset{WithArrows/arrow/tips/.style = { > = {Straight-Barb[scale=1.2,bend]} }}

73 \tikzset{WithArrows/arrow/.style  = { align = left,
74     auto = left,
75     font = {\small\itshape},
76     WithArrows/arrow/tips,
77     bend-left = 45,
78     -> }}

```

¹⁸It's not possible to use `\c_ifpackageloaded` in the core of the functions because `\c_ifpackageloaded` is available only in the preamble.

In order to increase the interline in the environments `{WithArrows}`, we will use the command `\spread@equation` of `amsmath`. When used, this command becomes no-op (in the current TeX group). Therefore, it will be possible to use the environments of `amsmath` (e.g. `{aligned}`) in an environment `{WithArrows}`.

Nevertheless, we want the extension `witharrows` available without `amsmath`. That's why we give a definition of `\spread@equation` if `amsmath` is not loaded (you put the code in a `\AtBeginDocument` because the flag `\c_@@_amsmath_loaded_bool` is itself set in a `\AtBeginDocument`).

```

79 \AtBeginDocument
80   {\bool_if:NF \c_@@_amsmath_loaded_bool
81     {\cs_set_protected:Npn \spread@equation
82       {\openup\jot
83         \cs_set_protected:Npn \spread@equation {}}}}

```

Don't put `\cs_set_eq:NN \spread@equation \prog_do_nothing`: in the last line because this would raise errors with nested environments.

9.4 Variables

The boolean `\l_@@_in_witharrows_bool` will be raised if (and only if) we are in an environment `{WithArrows}` (and not in an environment `{DispWithArrows}` or `{DispWithArrows*}`).

```
84 \bool_new:N \l_@@_in_witharrows_bool
```

The following sequence is the position of the last environment `{WithArrows}` in the tree of the nested environments `{WithArrows}`.

```

85 \seq_new:N \g_@@_position_in_the_tree_seq
86 \seq_gput_right:Nn \g_@@_position_in_the_tree_seq 1

```

The following counter will give the number of the last environment `{WithArrows}` of level 0. This counter will be used only in the definition of `\WithArrowsLastEnv`.

```
87 \int_new:N \g_@@_last_env_int
```

The following skip (=glue) is the vertical space inserted between two lines (=rows) of the `\halign`.

```
88 \skip_new:N \l_@@_interline_skip
```

The following integer indicates the position of the box that will be created: 0 (`=t=\vtop`), 1 (`=c=\vcenter`) or 2 (`=b=\vbox`).

```
89 \int_new:N \l_@@_pos_env_int
```

```

90 \dim_new:N \l_@@_xoffset_dim
91 \dim_set:Nn \l_@@_xoffset_dim {3mm}

```

The integer `\l_@@_pos_arrows_int` indicates the position of the arrows with the following code (the option `v` is accessible only for the arrows in `CodeAfter` where the options `i`, `group` et `groups` are not available).

option	rr	ll	rl	lr	v	i	group	groups
<code>\l_@@_pos_arrows_int</code>	0	1	2	3	4	5	6	7

The option `v` can be used only in `\Arrow` in `CodeAfter` (see below).

```
92 \int_new:N \l_@@_pos_arrows_int
```

When we scan a list of options, we want to be able to raise an error if two options of position of the arrows are present. That's why we keep the code of the first option of position in a variable called `\l_@@_previous_pos_arrows_int`. This variable will be set to `-1` each time we start the scanning of a list of options.

```
93 \int_new:N \l_@@_previous_pos_arrows_int
```

At each possible level for the options (*global*, *environment* or *local*: see below), the new values will be appended on the right of this token list.

The dimension `\g_@@_x_dim` will be used to compute the *x*-value for some vertical arrows when one of the options `i`, `group` and `groups` (values 5, 6 and 7 of `\l_@@_pos_arrows_int`) is used.

```
94 \dim_new:N \g_@@_x_dim
```

In the `\halign` of an environment `{WithArrows}`, we will have to use three counters:

- `\g_@@_arrow_int` to count the arrows created in the environment ;
- `\g_@@_line_int` to count the lines of the `\halign` ;
- `\g_@@_line_bis_int` to count the lines of the `\halign` which have a second column.¹⁹

These three counters will be incremented in a cell of the `\halign` and, therefore, the incrementation must be global. However, we want to be able to include a `{WithArrows}` in another `{WithArrows}`. To do so, we must restore the previous value of these counters at the end of an environment `{WithArrows}` and we decide to manage a stack for each of these counters.

```
95 \seq_new:N \g_@@_arrow_int_seq
96 \int_new:N \g_@@_arrow_int
97 \seq_new:N \g_@@_line_int_seq
98 \int_new:N \g_@@_line_int
99 \seq_new:N \g_@@_line_bis_int_seq
100 \int_new:N \g_@@_line_bis_int
```

The token list `\l_@@_name_tl` will contain the name of the environment (given with the option `name`). This name will be used to create aliases for the names of the nodes.

```
101 \tl_new:N \l_@@_name_tl
```

The boolean `\l_@@_notag_bool` will be used in `{DispWithArrows}`. In particular, it will be raised when the command `\notag` is used.

```
102 \bool_new:N \l_@@_notag_bool
```

The token list `\l_@@_tag_tl` will contain the argument of the command `\tag`.

```
103 \tl_new:N \l_@@_tag_tl
```

The boolean `\l_@@_tag_star_bool` will be raised if the user uses the command `\tag` with a star.

```
104 \bool_new:N \l_@@_tag_star_bool
```

The command `\@@_label:n` will be linked to `\label` in the second column of the `\halign` of the environment `{DispWithArrows}`. It's possible to put several labels for the same line (it's not possible in the environments of `amsmath`). That's why we store the different labels of a same line in a sequence `\l_@@_labels_seq`.

```
105 \seq_new:N \l_@@_labels_seq
106 \cs_set:Nn \@@_label:n {\seq_if_empty:NF \l_@@_labels_seq
107   {\msg_error:nn {witharrows} {Multiple-labels}}
108   \seq_put_right:Nn \l_@@_labels_seq {\#1}
109   \bool_if:nT \c_@@_mathtools_loaded_bool
110     {\MH_if_boolean:nT {show_only_refs}
111       {\cs_if_exist:cTF {\MT_r_\#1}
112         {\bool_set_false:N \l_@@_notag_bool}
113         {\bool_set_true:N \l_@@_notag_bool}}}
114   \bool_if:nT \c_@@_autonum_loaded_bool
115     {\cs_if_exist:cTF {\autonum@#1Referenced}
116       {\bool_set_false:N \l_@@_notag_bool}
117       {\bool_set_true:N \l_@@_notag_bool}}}
```

¹⁹This counter is used in order to raise an error if there is a line without the second column (such an situation could raise a PGF error for an undefined node).

The boolean `\l_@@_fleqn_bool` indicates whether the environments `{DispWithArrows}` must be composed flush left or centered. It corresponds to the option `fleqn`.

```
118 \bool_new:N \l_@@_fleqn_bool
```

The dimension `\l_@@_mathindent_dim` is used only by the environments `{DispWithArrows}`: it's the left margin of the environments `{DispWithArrows}` if the environment `{DispWithArrows}` is composed flush left (option `fleqn`).

```
119 \dim_new:N \l_@@_mathindent_dim
120 \dim_set:Nn \l_@@_mathindent_dim {25pt}
```

The boolean `\l_@@_wrap_lines_bool` corresponds to the option `wrap-lines`.

```
121 \bool_new:N \l_@@_wrap_lines_bool
```

9.5 The definition of the options

There are four levels where options can be set:

- with `\usepackage[...]{witharrows}`: this level will be called *package* level (number 0);
- with `\WithArrowsOptions{...}`: this level will be called *global* level (number 1);
- with `\begin{WithArrows}{...}`: this level will be called *environment* level (number 2);
- with `\Arrow{...}` (included in `CodeAfter`): this level will be called *local* level (number 3).

The level is specified in the variable `\l_@@_level_int` and the code attached to the options can use this information to alter its actions.

```
122 \int_set:Nn \l_@@_level_int 1
```

We start with a submodule which will be loaded only at the global or the environment level.

The options `t`, `c` and `b` indicate if we will create a `\vtop`, a `\vcenter` or a `\vbox`. This information is stored in the variable `\l_@@_pos_env_int`. Of course, they are available only in `{WithArrows}` and not in `{DispWithArrows}` or `{DispWithArrows*}`

```
123 \keys_define:nn {WithArrows/GlobalOrEnv}
124   { t .code:n      = {\bool_if:NTF \l_@@_in_witharrows_bool
125     {\int_set:Nn \l_@@_pos_env_int 0}
126     {\msg_error:nn {witharrows} {Option-will-be-ignored}}},
127   t .value_forbidden:n = true,
128   c .code:n      = {\bool_if:NTF \l_@@_in_witharrows_bool
129     {\int_set:Nn \l_@@_pos_env_int 1}
130     {\msg_error:nn {witharrows} {Option-will-be-ignored}}},
131   c .value_forbidden:n = true,
132   b .code:n      = {\bool_if:NTF \l_@@_in_witharrows_bool
133     {\int_set:Nn \l_@@_pos_env_int 2}
134     {\msg_error:nn {witharrows} {Option-will-be-ignored}}},
135   b .value_forbidden:n = true,
```

The gap between two consecutive arrows.

```
136   ygap .dim_set:N      = \l_@@_ygap_dim,
137   ygap .value_required:n = true,
138   ygap .initial:n       = 0.4 ex,
```

The vertical position of the start point of an arrow.

```
139   ystart .dim_set:N      = \l_@@_ystart_dim,
140   ystart .value_required:n = true,
141   ystart .initial:n       = 0.4 ex,
```

Usually, the number of columns in a `{WithArrows}` environment is limited to 2. Nevertheless, it's possible to have more columns with the option `MoreColumns`.

```
142     MoreColumns .code:n      = { \msg_redirect_name:nnn
143                               {witharrows}
144                               {Third~column~in~an~environment~{WithArrows}}
145                               {none} },
146     MoreColumns .value_forbidden:n = true,
```

By default, an error message is raised if there is a line without ampersand (`&`). However, it's possible to suppress this error with the option `AllowLineWithoutAmpersand`.

```
147     AllowLineWithoutAmpersand .code:n = { \msg_redirect_name:nnn
148                               {witharrows}
149                               {All~lines~must~have~an~ampersand}
150                               {none} },
151     AllowLineWithoutAmpersand .value_forbidden:n = true,
```

If the user wants to give a new name to the `\Arrow` command (and the name `\Arrow` remains free).

```
152     CommandName .tl_set:N      = \l_@@_CommandName_tl,
153     CommandName .initial:n     = Arrow ,
154     CommandName .value_required:n = true,

155     TikzCode .tl_set:N        = \l_@@_tikz_code_tl,
156     TikzCode .initial:n       = \draw~(#1)~to~node{#3}~(#2); ,
157     TikzCode .value_required:n = true,
```

With the option `displaystyle`, the environments will be composed in `\displaystyle`.

```
158     displaystyle .bool_set:N    = \l_@@_displaystyle_bool,
159     displaystyle .initial:n     = false,
```

With the option `shownodes`, the nodes will be drawn in red (useful only for debugging).

```
160     shownodes .bool_set:N      = \l_@@_shownodes_bool,
161     shownodes .initial:n       = false,
```

With the option `shownodenames`, the name of the “right nodes” will be written in the document (useful only for debugging).

```
162     shownodenames .bool_set:N   = \l_@@_shownodenames_bool,
163     shownodenames .initial:n    = false,
```

With the option `group`, *all* the arrows of the environment are vertical with the same abscissa and at a leftmost position.

```
164     group     .code:n      = {\int_compare:nNnT \l_@@_previous_pos_arrows_int > {-1}
165                               {\msg_error:nn {witharrows}
166                               {Two~options~are~incompatible}}
167                               \int_set:Nn \l_@@_previous_pos_arrows_int 6
168                               \int_set:Nn \l_@@_pos_arrows_int 6} ,
169     group     .value_forbidden:n = true,
```

With the option `groups` (with a *s*), the arrows of the environment are divided in groups by an argument of connexity, and, in each group, the arrows are vertical with the same abscissa and at a leftmost position. When the option `group` or `groups` is used, it's not possible to another option of position like `ll`, `lr`, etc. for a individual key.

```
170     groups    .code:n      = {\int_compare:nNnT \l_@@_previous_pos_arrows_int > {-1}
171                               {\msg_error:nn {witharrows}
172                               {Two~options~are~incompatible}}
173                               \int_set:Nn \l_@@_previous_pos_arrows_int 7
174                               \int_set:Nn \l_@@_pos_arrows_int 7} ,
175     groups    .value_forbidden:n = true,
```

The option `CodeBefore` gives a code that is executed at the beginning of the environment `{WithArrows}` (after the eventual `\begin{savenotes}`).

```
176     CodeBefore .code:n = {\int_compare:nNnTF \l_@@_level_int = 1
177             {\msg_error:nn {witharrows} {Option-will-be-ignored}}
178             {\tl_put_right:Nn \l_@@_code_before_tl {#1}}} ,
179     CodeBefore .value_required:n = true,
```

The option `CodeAfter` gives a code that is executed at the end of the environment `{WithArrows}` (after the eventual `\end{savenotes}`).

```
180     CodeAfter .code:n = {\int_compare:nNnTF \l_@@_level_int = 1
181             {\msg_error:nn {witharrows} {Option-will-be-ignored}}
182             {\tl_put_right:Nn \l_@@_code_after_tl {#1}}} ,
183     CodeAfter .value_required:n = true,
```

The option `name` is a name given to the environment. If this option is used, the nodes created in the environment will have aliases constructed with this name (and it will be easier to use these nodes from outside the environment).

```
184     name .code:n = {\int_compare:nNnTF \l_@@_level_int = 1
185             {\msg_error:nn {witharrows} {Option-will-be-ignored}}
186             {\tl_set:Nn \l_@@_name_tl {#1}}} ,
187     name .value_required:n = true,
```

The option `fleqn` indicates whether the environments `{DispWithArrows}` are composed centered or flush left.

```
188     fleqn .code:n = {\bool_if:NTF \l_@@_in_witharrows_bool
189             {\msg_error:nn {witharrows} {Option-will-be-ignored}}
190             {\tl_if_eq:nnTF {#1} {true}
191                 {\bool_set_true:N \l_@@_fleqn_bool}
192                 {\bool_set_false:N \l_@@_fleqn_bool}}},
193     fleqn .default:n = true,
```

The option `mathindent` is the left margin of the environments `{DispWithArrows}` when the option `fleqn` is used.

```
194     mathindent .code:n = {\bool_if:NTF \l_@@_in_witharrows_bool
195             {\msg_error:nn {witharrows} {Option-will-be-ignored}}
196             {\dim_set:Nn \l_@@_mathindent_dim {#1}}},
197     mathindent .value_required:n = true,
```

The option `notag` indicates whether the environments `{DispWithArrows}` will be without tags (like `{DispWithArrows*}`).

```
198     notag .code:n = {\bool_if:NTF \l_@@_in_witharrows_bool
199             {\msg_error:nn {witharrows} {Option-will-be-ignored}}
200             {\tl_if_eq:nnTF {#1} {true}
201                 {\bool_set_true:N \l_@@_notag_bool}
202                 {\bool_set_false:N \l_@@_notag_bool}}},
203     notag .default:n = true,
204     nonumber .meta:n = notag,
```

The option `AllowMultipleLabels` indicates whether multiple labels are allowed for the same line of an environment `{DispWithArrows}` or `{DispWithArrows*}`.

```
205     AllowMultipleLabels .code:n = {\bool_if:NTF \l_@@_in_witharrows_bool
206             {\msg_error:nn {witharrows} {Option-will-be-ignored}}
207             {\msg_redirect_name:nnn {witharrows}
208                 {Multiple-labels}
209                 {none}}},
210     AllowMultipleLabels .value_forbidden:n = true,
211 %   \begin{macrocode}
212 %
213 % \bigskip
```

```

214 % With the option |wrap-lines|, a special |TikzCode| is used in the environments |{DispWithArrows}| and
215 % |{DispWithArrows*}| and, with this |TikzCode|, the lines of the labels are automatically wrapped on the right
216 % \begin{macrocode}
217   wrap-lines .code:n = {\bool_if:NTF \l_@@_in_witharrows_bool
218     {\msg_error:nn {witharrows} {Option-will-be-ignored}}
219     {\tl_if_eq:nnTF {#1} {true}
220       {\bool_set_true:N \l_@@_wrap_lines_bool}
221       {\bool_set_false:N \l_@@_wrap_lines_bool}}},
222   wrap-lines .default:n = true,
223   unknown .code:n = \msg_error:nn {witharrows} {Option-unknown}
224 }

```

Then we define the main module called `WithArrows/General` which will be loaded at all the levels.

The option `tikz` gives Tikz parameters that will be given to the arrow when it is drawn (more precisely, the parameters will be given to the command `\path` of Tikz).

```

225 \keys_define:nn {WithArrows/General}
226   {tikz .code:n = \tikzset {WithArrows/arrow/.append-style = {#1}},
227    tikz .initial:n = {},
228    tikz .value_required:n = true,

```

The other options are for the position of the arrows. The treatment is the same for the options `ll`, `rr`, `lr`, `rl` and `i` and that's why a dedicated fonction `\@@_analyze_option_position:n` has been written (see below).

```

229   rr .value_forbidden:n = true,
230   rr .code:n = \@@_analyze_option_position:n 0 ,
231   ll .value_forbidden:n = true,
232   ll .code:n = \@@_analyze_option_position:n 1 ,
233   rl .value_forbidden:n = true,
234   rl .code:n = \@@_analyze_option_position:n 2 ,
235   lr .value_forbidden:n = true,
236   lr .code:n = \@@_analyze_option_position:n 3 ,
237   i .value_forbidden:n = true,
238   i .code:n = \@@_analyze_option_position:n 5 ,

```

The option `xoffset` change the *x*-offset of the arrows (towards the right). It's a dimension and not a skip. It's not possible to change the value of this parameter for a individual arrow if the option `group` or the option `groups` is used. When we will treat an individual arrow, we will give it the option `tikz={xshift=\l_@@_xoffset_dim}` (we can't to it at the global or the environment level because the Tikz options `xshift` are cumulative).

```

239   xoffset .code:n = {\bool_if:nTF {\int_compare_p:nNn \l_@@_level_int = 3 &&
240                           \int_compare_p:nNn \l_@@_pos_arrows_int > 5}
241                           {\msg_error:nn {witharrows}
242                            {Option-incompatible-with-"group(s)"}}
243                           {\dim_set:Nn \l_@@_xoffset_dim {#1}}},
244   xoffset .value_required:n = true,

```

The option `jot` exists for compatibility. It changes directly the value of the parameter `\jot`, which is a LaTeX parameter and not a parameter specific to `witharrows`. It's allowed only at the level of the environment (maybe we should suppress completely this option in the future).

```

245   jot .code:n = {\int_compare:nNnTF \l_@@_level_int = 2
246                           {\dim_set:Nn \jot {#1}}
247                           {\msg_error:nn {witharrows}
248                            {Option-will-be-ignored}}},
249   jot .value_required:n = true,

```

The option `interline` gives the vertical skip (=glue) inserted between two lines (independently of `\jot`). It's accepted only at the level of the environment (this last point is a kind of security).

Futhermore, this option has a particular behaviour: it applies only to the current environment and doesn't apply to the nested environments.

```

250     interline .code:n      = {\int_compare:nNnTF \l_@@_level_int = 2
251                                         {\skip_set:Nn \l_@@_interline_skip {#1}}
252                                         {\msg_error:nn {witharrows}
253                                         {Option~will~be~ignored}}}
254     interline .value_required:n = true,

```

Eventually, a key `jump` (see below) and a key for unknown keys.

```

255     jump .code:n = \msg_error:nn {witharrows} {Option~will~be~ignored},
256     unknown .code:n = \msg_error:nn {witharrows} {Option~unknown}
257 }

```

The key `jump` indicates the number of lines jumped by the arrow (1 by default). This key will be extracted when the command `\Arrow` will be executed. That's why there is a special module for this key. The key `jump` is extracted in the command `\Arrow` because we want to compute right away the final line of the arrow (this will be useful for the options `group` and `groups`).

```

258 \keys_define:nn {WithArrows/jump}
259   {jump .code:n = {\int_set:Nn \l_@@_jump_int {#1}
260                     \int_compare:nNnF \l_@@_jump_int > 0
261                     {\msg_error:nn {witharrows}
262                     {The~option~"jump"~must~be~non~negative}}}
263   jump .value_required:n = true}

```

The following command is for technical reasons. It's used for the following options of position: `ll`, `lr`, `rl`, `rr` and `i`. The argument is the corresponding code for the position of the arrows.

```

264 \cs_new_protected:Nn \@@_analyze_option_position:n
265   {\int_compare:nNnT \l_@@_previous_pos_arrows_int > {-1}
266     {\msg_error:nn {witharrows}
267     {Two~options~are~incompatible}}
268   \int_set:Nn \l_@@_previous_pos_arrows_int {#1}

```

It's not possible to use one of the considered options at the level of an arrow (level 2) when the option `group` or the option `groups` is used. However, if we are at the level of an environment, it's possible to override a previous option `group` or `groups` (this previous option `group` or `groups` would necessarily have been set at a global level by `\WithArrowsOptions`).

```

269   \bool_if:nTF { \int_compare_p:nNn \l_@@_level_int = 3 &&
270             \int_compare_p:nNn \l_@@_pos_arrows_int > 5}
271     {\msg_error:nn {witharrows}
272     {Option~incompatible~with~"group(s)"}}
273   \int_set:Nn \l_@@_pos_arrows_int {#1}}

```

`\WithArrowsOptions` is the command of the `witharrows` package to fix options at the document level.

```

274 \NewDocumentCommand \WithArrowsOptions {m}
275   {\int_set:Nn \l_@@_previous_pos_arrows_int {-1}
276   \keys_set_known:nnN {WithArrows/General} {#1} \l_tmpa_t1
277   \keys_set:nV {WithArrows/GlobalOrEnv} \l_tmpa_t1}

```

9.6 The command Arrow

In fact, the internal command is not named `\Arrow` but `\@@_Arrow`. Usually, at the beginning of an environment `{WithArrows}`, `\Arrow` is set to be equivalent to `\@@_Arrow`. However, the user can change the name with the option `CommandName` and the user command for `\@@_Arrow` will be different. This mechanism can be useful when the user has already a command named `\Arrow` he wants to still be able to use in the environment `{WithArrows}`.

```

278 \NewDocumentCommand \@@_Arrow {O{} m O{}}
279   {

```

The counter `\g_@@_arrow_int` counts the arrows in the environment. The incrementation must be global (`gincr`) because the command `\Arrow` will be used in the cell of a `\halign`. It's recalled that we manage a stack for this counter.

```
280 \int_gincr:N \g_@@_arrow_int
```

We decide to extract immediately the key `jump` in order to compute the end line. That's the reason why there is a module `WithArrows/jump` with this sole key. The remained key-value pairs are stored in `\l_tmpa_t1` and will be stored further in the properly list of the arrow.

```
281 \int_zero_new:N \l_@@_jump_int
282 \int_set:Nn \l_@@_jump_int 1
283 \keys_set_known:nnN {WithArrows/jump} {#1,#3} \l_tmpa_t1
```

We will construct a global property list to store the informations of the considered arrow. The four fields of this property list are “initial”, “final”, “options” and “label”.

1. First, the line from which the arrow starts:

```
284 \prop_put:NnV \l_tmpa_prop {initial} \g_@@_line_int
```

2. The line where the arrow ends (that's why it was necessary to extract the key `jump`):

```
285 \int_set:Nn \l_tmpa_int {\g_@@_line_int + \l_@@_jump_int}
286 \prop_put:NnV \l_tmpa_prop {final} \l_tmpa_int
```

3. All the options of the arrow (it's a token list):

```
287 \prop_put:NnV \l_tmpa_prop {options} \l_tmpa_t1
```

4. The label of the arrow (it's also a token list):

```
288 \prop_put:Nnn \l_tmpa_prop {label} {#2}
```

The property list has been created in a local variable for convenience. Now, it will be stored in a global variable indicating both the position-in-the-tree and the number of the arrow.

```
289 \prop_gclear_new:c
290   {g_@@_arrow_\l_@@_prefix_str _\int_use:N\g_@@_arrow_int _prop}
291 \prop_gset_eq:cN
292   {g_@@_arrow_\l_@@_prefix_str _\int_use:N\g_@@_arrow_int _prop}
293   \l_tmpa_prop
294 }
```

```
295 \cs_new_protected:Nn \@@_Arrow_first_column:
```

All messages of LaTeX3 must be *fully expandable* and that's why we do the affectation (necessary for a comparison) before the `\msg_error:nn`.

```
296   {\tl_set:Nn \l_tmpa_t1 {Arrow}}
297   \msg_error:nn {witharrows} {Arrow-in-first-column}
298   \@@_Arrow}
```

9.7 The environment `{WithArrows}`

The command `\@@_pre_environement`: is a code common to the environments `{WithArrows}` and `{DispWithArrows}`. The argument is the options given to the environment.

```
299 \cs_new_protected:Nn \@@_pre_environment:n
```

First the initialisation of the three counters `\g_@@_arrow_int`, `\g_@@_line_int` and `\g_@@_line_bis_int`. However, we have to save their previous values with the three stacks created for this end.

```
300 { \seq_gput_right:NV \g_@@_arrow_int_seq \g_@@_arrow_int
301   \int_gzero:N \g_@@_arrow_int
302   \seq_gput_right:NV \g_@@_line_int_seq \g_@@_line_int
303   \int_gzero:N \g_@@_line_int
304   \seq_gput_right:NV \g_@@_line_bis_int_seq \g_@@_line_bis_int
305   \int_gzero:N \g_@@_line_bis_int
```

We also have to update the position on the nesting tree.

```
306      \seq_gput_right:Nn \g_@@_position_in_the_tree_seq 1
```

The nesting tree is used to create a prefix which will be used in the names of the Tikz nodes and in the names of the arrows (each arrow is a property list of four fields). If we are in the second environment `{WithArrows}` nested in the third environment `{WithArrows}` of the document, the prefix will be `3-2` (although the position in the tree is `[3, 2, 1]` since such a position always ends with a `1`). First, we do a copy of the position-in-the-tree and then we pop the last element of this copy (in order to drop the last `1`).

```
307      \seq_set_eq:NN \l_tmpa_seq \g_@@_position_in_the_tree_seq
308      \seq_pop_right:NN \l_tmpa_seq \l_tmpa_t1
309      \str_clear_new:N \l_@@_prefix_str
310      \str_set:Nx \l_@@_prefix_str {\seq_use:Nnnn \l_tmpa_seq {-} {-} {-}}
```

We define the command `\\"\\` to be the command `\@@_cr`: (defined below).

```
311      \cs_set_eq:NN \\ \@@_cr:
312      \dim_zero:N \mathsurround
```

These counters will be used later as variables.

```
313      \int_zero_new:N \l_@@_initial_int
314      \int_zero_new:N \l_@@_final_int
315      \int_zero_new:N \l_@@_arrow_int
```

The value corresponding to the key `interline` is put to zero before the treatment of the options of the environment.²⁰

```
316      \skip_zero:N \l_@@_interline_skip
```

The value corresponding to the key `CodeBefore` is put to nil before the treatment of the options of the environment, because, of course, we don't want the code executed at the beginning of all the nested environments `{WithArrows}`. Idem for `CodeAfter`.

```
317      \tl_clear_new:N \l_@@_code_before_t1
318      \tl_clear_new:N \l_@@_code_after_t1
```

We process the options given to the `{WithArrows}` environment. The level of options is set to 1.

```
319      \int_set:Nn \l_@@_previous_pos_arrows_int {-1}
320      \int_set:Nn \l_@@_level_int 2
321      \keys_set_known:nnN {WithArrows/General} {#1} \l_tmpa_t1
322      \keys_set:nV {WithArrows/GlobalOrEnv} \l_tmpa_t1
```

If the option `footnote` or the option `footnotehyper` is used, then we extract the footnotes with an environment `{savenotes}` (of the package `footnote` or the package `footnotehyper`).

```
323      \bool_if:NT \g_@@_footnote_bool {\begin{savenotes}}
```

We execute the code `\l_@@_code_before_t1` of the option `CodeBefore` of the environment after the eventual `\begin{savenotes}` and, symetrically, we will execute the `\l_@@_code_after_t1` before the eventual `\end{savenotes}` (we have a good reason for the last point : we want to extract the footnotes of the arrows executed in the `CodeAfter`).

```
324      \l_@@_code_before_t1
```

If the user has given a value for the option `CommandName` (at the global or at the *environment* level), a command with this name is defined locally in the environment with meaning `\@@_Arrow`. The default value of the option `CommandName` is “`Arrow`” and thus, by default, the name of the command will be `\Arrow`.

```
325      \cs_set_eq:cN \l_@@_CommandName_t1 \@@_Arrow}
```

²⁰It's recalled that, by design, the option `interline` of an environment doesn't apply in the nested environments.

This is the end of \@@_pre_environment:n.

Now, we begin the environment {WithArrows}.

```

326 \NewDocumentEnvironment {WithArrows} {O{}}
327   { \bool_set_true:N \l_@@_in_witharrows_bool
328     \reverse_if:N \if_mode_math:
329       \msg_error:nn {witharrows}
330         {{WithArrows}~used~outside~math~mode}
331       \fi:
332     \cs_set:Npn \notag {\msg_error:nnn {witharrows}
333       {Command-not-allowed-in-{WithArrows}}
334       {\notag}}
335     \cs_set:Npn \nonumber {\msg_error:nnn {witharrows}
336       {Command-not-allowed-in-{WithArrows}}
337       {\nonumber}}
338     \cs_set:Npn \tag ##1 {\msg_error:nnn {witharrows}
339       {Command-not-allowed-in-{WithArrows}}
340       {\tag}}
341     \cs_set:Npn \label ##1 {\msg_error:nnn {witharrows}
342       {Command-not-allowed-in-{WithArrows}}
343       {\label}}
344   \@@_pre_environment:n {#1}

```

The environment begins with a `\vtop`, a `\vcenter` or a `\vbox`²¹ depending of the value of `\l_@@_pos_env_int` (fixed by the options t, c or b). The environment {WithArrows} must be used in math mode²² and therefore, we can use `\vcenter`.

```

345 \int_case:nn \l_@@_pos_env_int
346   {0 {\vtop}
347    1 {\vcenter}
348    2 {\vbox}}
349 \bgroup

```

The command `\spread@equation` is the command used by `amsmath` in the beginning of an alignment to fix the interline. When used, it becomes no-op. However, it's possible to use `witharrows` without `amsmath` since we have redefined `\spread@equation` (if it is not defined yet).

```
350 \spread@equation
```

We begin the `\halign` and the preamble.

```
351 \ialign\bgroup
```

We increment the counter `\g_@@_line_int` which will be used in the names of the Tikz nodes created in the array. This incrementation must be global (`gincr`) because we are in the cell of a `\halign`. It's recalled that we manage a stack for this counter.

```

352 \int_gincr:N \g_@@_line_int
353 \cs_set_eq:cN \l_@@_CommandName_tl \@@_Arrow_first_column:
354 \strut\hfil
355 \$\bool_if:NT \l_@@_displaystyle_bool \displaystyle {##}$
356 &

```

In the second column, we increment the counter `\g_@@_line_bis_int` because we want to count the lines with a second column and raise an error if there is lines without a second column. Once again, the incrementation must be global and it's recalled that we manage a stack for this counter too.

```

357 \int_gincr:N \g_@@_line_bis_int
358 \$\bool_if:NT \l_@@_displaystyle_bool \displaystyle {{}##}$

```

²¹Notice that the use of `\vtop` seems color-safe here...

²²An error is raised if the environment is used outside math mode.

We create the “left node” of the line (when using macros in Tikz node names, the macros have to be fully expandable: here, `\tl_use:N` and `\int_use:N` are fully expandable).

```

359      \tikz [remember~picture,overlay]
360          \node [@@_node_style,
361              name = wa-\l_@@_prefix_str-\int_use:N\g_@@_line_int-l,
362              alias = {\tl_if_empty:NF \l_@@_name_tl
363                      {\l_@@_name_tl-\int_use:N\g_@@_line_int-l}} ] {} ;
364
365 \hfil

```

Now, after the `\hfil`, we create the “right node” and, if the option `shownodenames` is raised, the name of the node is written in the document (useful for debugging).

```

365      \tikz [remember~picture,overlay]
366          \node [@@_node_style,
367              name = wa-\l_@@_prefix_str-\int_use:N\g_@@_line_int-r,
368              alias = {\tl_if_empty:NF \l_@@_name_tl
369                      {\l_@@_name_tl-\int_use:N\g_@@_line_int-r}} ] {} ;
370
371 \bool_if:NT \l_@@_shownodenames_bool
372     {\hbox_overlap_right:n {\small wa-\l_@@_prefix_str
373                             -\int_use:N\g_@@_line_int}}
374
375 \cr
376 }

```

Usually, the `\halign` of an environment `{WithArrows}` will have exactly two columns. Nevertheless, if the user wants to use more columns (without arrows) it’s possible with the option `MoreColumns`.

```

373 && \msg_error:nn {witharrows} {Third-column-in-an-environment-{WithArrows}}
374 $ \bool_if:NT \l_@@_displaystyle_bool \displaystyle {##}$
375 \cr
376 }

```

We begin the second part of the environment `{WithArrows}`. We have two `\egroup`: one for the `\halign` and one for the `\vtop` (or `\vcenter` or `\vbox`).

```

377 {\crcr
378 \egroup
379 \egroup
380 \@@_post_environment:}

```

This is the end of the environment `{WithArrows}`.

The command `\@@_post_environment:` is a code common to the second part of the environment `{WithArrows}` and the environment `{DispWithArrows}`.

```
381 \cs_new_protected:Nn \@@_post_environment:
```

If there is a line without the second column, we raise an error (a line without the second column could generate an PGF error for an unknown node since the nodes are created in the second column).

```

382 {\int_compare:nNnT \g_@@_line_bis_int < \g_@@_line_int
383   \msg_error:nn {witharrows} {All-lines-must-have-an-ampersand}}

```

If there is really arrows in the environment, we draw the arrows:

- if neither option `group` or `groups` is used, we can draw directly ;
- if option `group` or option `groups` is used (`\l_@@_pos_arrows_int > 5`), we have to draw the arrows group by group ; the macro `\@@_draw_arrows:` does the work.

```

384 \int_compare:nNnT \g_@@_arrow_int > 0
385   {\int_compare:nNnTF \l_@@_pos_arrows_int > 5
386     \@@_draw_arrows:
387     {\@@_draw_arrows:nn 1 \g_@@_arrow_int}}

```

We will execute the code specified in the option `CodeAfter`, after some settings.

```

388 \group_begin:
389 \tikzset{every~picture/.style = @@_standard}

```

The command `\NbLines` is not used by `witharrows`. It's only a convenience given to the user.

```
390     \cs_set:Npn \NbLines {\int_use:N \g_@@_line_int}
```

The command `\MultiArrow` is available in `CodeAfter`, and we have a special version of `\Arrow`, called “`\Arrow` in `CodeAfter`” in the documentation.²³

```
391     \cs_set_eq:NN \MultiArrow \c@_MultiArrow:nn
392     \cs_set_eq:cN \l_@@_CommandName_tl \c@_Arrow_code_after
393     \l_@@_code_after_tl
394     \group_end:
```

If the option `footnote` or the option `footnotehyper` is used, then we extract the footnotes with an environment `{footnote}` (of the package `footnote` or the package `footnotehyper`).

```
395     \bool_if:NT \g_@@_footnote_bool {\end{footnote}}
```

We update the position-in-the-tree. First, we drop the last component and then we increment the last element.

```
396     \seq_gpop_right:NN \g_@@_position_in_the_tree_seq \l_tmpa_tl
397     \seq_gpop_right:NN \g_@@_position_in_the_tree_seq \l_tmpa_tl
398     \seq_gput_right:Nx \g_@@_position_in_the_tree_seq {\int_eval:n {\l_tmpa_tl+1}}
```

We update the value of the counter `\g_@@_last_env_int`. This counter is used only by the user function `\WithArrowsLastEnv`.

```
399     \int_compare:nNnT {\seq_count:N \g_@@_position_in_the_tree_seq} = 1
400             {\int_gincr:N \g_@@_last_env_int}
```

Finally, we restore the previous values of the three counters `\g_@@_arrow_int`, `\g_@@_line_int` and `\g_@@_line_bis_int`. It is recalled that we manage three stacks in order to be able to do such a restoration.

```
401     \seq_gpop_right:NN \g_@@_arrow_int_seq {\l_tmpa_tl}
402     \int_gset:Nn \g_@@_arrow_int {\l_tmpa_tl}
403     \seq_gpop_right:NN \g_@@_line_int_seq \l_tmpa_tl
404     \int_gset:Nn \g_@@_line_int {\l_tmpa_tl}
405     \seq_gpop_right:NN \g_@@_line_bis_int_seq \l_tmpa_tl
406     \int_gset:Nn \g_@@_line_bis_int {\l_tmpa_tl}
407 }
```

That's the end of the command `\@@_post_environment`:

We give now the definition of `\@@_cr`: which is the definition of `\backslash` in an environment `{WithArrows}`. The two `expl3` commands `\group_align_safe_begin`: and `\group_align_safe_end`: are specifically designed for this purpose: test the token that follows in a `\halign` structure.

First, we remove an eventual token `*` since the commands `\backslash` and `\backslash*` are equivalent in an environment `{WithArrows}` (an environment `{WithArrows}`, like an environment `{aligned}` of `amsmath`, is always unbreakable).

```
408 \cs_new_protected:Nn \@@_cr:
409     {\scan_stop:
410     \group_align_safe_begin:
411     \peek_meaning_remove:NTF * \@@_cr_i: \@@_cr_i:}
```

Then, we peek the next token to see if it's a `[`. In this case, the command `\backslash` has an optional argument which is the vertical skip (=glue) to put.

```
412 \cs_new_protected:Nn \@@_cr_i:
413     {\peek_meaning:NTF [ {\@@_cr_ii:} {\@@_cr_ii:[\c_zero_dim]} ]}
414 \cs_new_protected:Npn \@@_cr_ii:[#1]
415     {\group_align_safe_end:
```

²³As for now, `\MultiArrow` has no option, and that's why its internal name is a name of `expl3` with the signature `:nn` whereas `\Arrow` in `CodeAfter` provides options and has the name of a function defined with `\NewDocumentCommand`.

For the environment `{DispWithArrows}`, the behaviour of `\\"` is different because we add the third column which is the column for the tag (number of the equation).

```
416     \bool_if:NF \l_@@_in_witharrows_bool
417         {\bool_if:NTF \l_@@_notag_bool}
```

If there is no tag to put, we use as well the third column because you want to raise an error if the user uses more than two columns.

```
418     {& \tikz [remember-picture,overlay]
419         \coordinate [name = wa-\l_@@_prefix_str-\int_use:N\g_@@_line_int-v ] ; }
420 }
```

Here, we can't use `\refstepcounter{equation}` because if the user has issued a `\tag` command, we have to use `\l_@@_tag_t1` and not `\theequation`. That's why we have to do the job done by `\refstepcounter` manually.

First, the incrementation of the counter (potentially).

```
421     \tl_if_empty:NT \l_@@_tag_t1
422         {\int_gincr:N \c@equation}
```

We store in `\g_tmpa_t1` the tag we will have to compose at the end of the line. We use a global variable because we will use it in the *next* cell (after the `&`).

```
423     \cs_gset:Npx \g_tmpa_t1
424         {\tl_if_empty:NTF \l_@@_tag_t1
425             \theequation
426             \l_@@_tag_t1}
```

It's possible to put several labels for the same line (it's not possible in the environments of `amsmath`). That's why the different labels of a same line are stored in a sequence `\l_@@_labels_seq`.

```
427     \seq_if_empty:NF \l_@@_labels_seq
428         {
```

Now, we do the job done by `\refstepcounter` and by the redefinitions of `\refstepcounter` done by some packages (the incrementation of the counter has been done yet).

First an action which is in the definition of `\refstepcounter` in `source2e`.

```
429     \cs_set:Npx \currentlabel {\p@equation \g_tmpa_t1}
```

Then, an action done by `hyperref` in its redefinition of `\refstepcounter`.

```
430     \bool_if:NT \c_@@_hyperref_loaded_bool
431         {\cs_set:Npn \This@name {equation}
432             \hyper@refstepcounter{equation}}
```

Then, an action done by `cleveref` in its redefinition of `\refstepcounter`. The package `cleveref` creates in the `aux` file a command `\cref@currentlabel` similar to `\@current` but with more informations.

```
433     \bool_if:NT \c_@@_cleveref_loaded_bool
434         {\cref@constructprefix{equation}{\cref@result}
435             @ifundefined{\cref@equation@alias}
436                 {\def\@tempa{equation}}
437                 {\def\@tempa{\csname cref@equation@alias\endcsname}}
438             \protected@edef\cref@currentlabel{[\@tempa] [\arabic{equation}] [\cref@result]
439                 \p@equation \g_tmpa_t1}}
```

Then, an action done by `typedref` in its redefinition of `\refstepcounter`. The command `\sr@name` is a prefix added to the name of the label by the redefinition of `\label` done by `typedref`.

```
440     \bool_if:NT \c_@@_typedref_loaded_bool
441         {\cs_set:Npn \sr@name {equation}}
```

Now, we can issue the command `\label` (some package may have redefined `\label`, for example `typedref`) for each item in the sequence of the labels (it's possible to put several labels to the same line and that's why the labels are in the sequence `\l_@@_labels_seq`).

```
442     \seq_map_function:NN \l_@@_labels_seq \c@old_label}
```

We store the boolean `\l_@@_tag_star_bool` in the global variable `\g_tmpa_bool` because we will use it in the *next* cell (after the `&`).

```
443     \bool_gset_eq:NN \g_tmpa_bool \l_@@_tag_star_bool
444     & \cs_set_eq:NN \theequation \g_tmpa_t1
445         \bool_if:NT \g_tmpa_bool {\cs_set:Npn \tagform@ {}}
```

We use `\@eqnnum` (we recall that there are two definitions of `\@eqnnum`, a standard definition and another, loaded if the option `\leqno` is used).

```

446          \hbox_overlap_left:n
447          { \tikz [@@_standard]
448              \coordinate [name = \int_use:N \g_@@_line_int-v ] ;
449              \quad
450              \@eqnnum}
451      }
452      \cr\noalign{\skip_vertical:n {\#1 + \l_@@_interline_skip}
453      \scan_stop:}}

```

According to the documentation of `expl3`, the previous addition in “`#1 + \l_@@_interline_skip`” is really an addition of skips (=glues).

9.8 The environment {DispWithArrows}

For the environment `{DispWithArrows}`, the construction is a construction of the type:

```
\[ \vcenter{ \halign to \displaywidth { ... } } ]
```

The purpose of the `\vcenter` is to have an environment unbreakable.

```

454 \NewDocumentEnvironment {DispWithArrows} {O{}}
455 {

```

If `mathtools` has been loaded with the option `showonlyrefs`, we deactivate the code of `mathtools` for the option `showonlyrefs` with the command `\MT_showonlyrefs_false`: (it will be reactivated at the end of the environment).

```

456 \bool_if:nT \c_@@_mathtools_loaded_bool
457   {\MH_if_boolean:nT {show_only_refs}
458    {\MT_showonlyrefs_false:

```

However, we have to re-raise the flag `{show_only_refs}` of `mhsetup` because it has been switched off by `\MT_showonlyrefs_false`: and we will use it in the code of the new version of `\label`.

```

459 \MH_set_boolean_T:n {show_only_refs}
460 \bool_set_true:N \l_@@_notag_bool}

```

The command `\intertext@` is a command of `amsmath` which loads the definition of `\intertext`.

```

461 \bool_if:NT \c_@@_amsmath_loaded_bool \intertext@
462 \if_mode_math:
463   \msg_error:nn {witharrows}
464     {{DispWithArrows}~used~in~math~mode}
465 \fi:
466 \bool_set_false:N \l_@@_in_witharrows_bool
467 \c_@@_pre_environment:n {\#1}

```

We don't use `\[` of `LaTeX` because some extensions, like `autonum`, do a redefinition of `\[`. However, we put the two following lines which are in the definition of `\[`.

```

468 \nointerlineskip
469 \makebox[.6\linewidth]{}
470 $$

```

We use a `\vcenter` in order to prevent page breaks in the environment.

```

471 \vcenter \bgroup
472 \spread@equation
473 \bool_if:NTF \l_@@_fleqn_bool
474   {\tabskip = \c_zero_skip}
475   {\tabskip = 0 pt plus 1000 pt minus 1000 pt}

```

If `amsmath` is loaded, the `LaTeX` version of `\label` is stored in `\ltx@label`. If not, it's, of course, stored in `\label`. We store this definition of `\label` because we will redefine `\label` in the environment.

```

476 \bool_if:NTF \c_@@_amsmath_loaded_bool
477   {\cs_set_eq:NN \l_@@_old_label \ltx@label}
478   {\cs_set_eq:NN \l_@@_old_label \label}

```

```

479 \cs_set:Npn \notag {\msg_error:n{witharrows}
480                                     {Command-not-allowed-in-{DispWithArrows}}
481                                     {\notag}}
482 \cs_set:Npn \nonumber {\msg_error:n{witharrows}
483                                     {Command-not-allowed-in-{DispWithArrows}}
484                                     {\nonumber}}
485 \cs_set:Npn \tag ##1 {\msg_error:n{witharrows}
486                                     {Command-not-allowed-in-{DispWithArrows}}
487                                     {\tag}}
488 \cs_set:Npn \label ##1 {\msg_error:n{witharrows}
489                                     {Command-not-allowed-in-{DispWithArrows}}
490                                     {\label}}
491 \halign to \displaywidth \bgroup
492     \int_gincr:N \g_@@_line_int
493     \cs_set_eq:cN \l_@@_CommandName_tl \@@_Arrow_first_column:
494     \strut
495     \bool_if:NT \l_@@_fleqn_bool
496         {\skip_horizontal:n \l_@@_mathindent_dim}
497     \hfil
498     $ \bool_if:NT \l_@@_displaystyle_bool \displaystyle {##}$
499     \tabskip = \c_zero_skip
500     &
501     \cs_set:Npn \notag {\bool_set_true:N \l_@@_notag_bool}
502     \cs_set_eq:NN \nonumber \notag
503     \cs_set_eq:NN \tag \@@_tag
504     \cs_set_eq:NN \label \@@_label:n
505     $ \bool_if:NT \l_@@_displaystyle_bool \displaystyle {}##}$
506     \tabskip = 0 pt plus 1000 pt minus 1000 pt
507     \int_gincr:N \g_@@_line_bis_int
508     \tikz [remember picture, overlay]
509         \node [_@@_node_style,
510                 name = wa-\l_@@_prefix_str-\int_use:N\g_@@_line_int-1,
511                 alias = {\tl_if_empty:NF \l_@@_name_tl
512                           {\l_@@_name_tl-\int_use:N\g_@@_line_int-1}} ] {} ;
513     \hfil
514     \tikz [remember picture, overlay]
515         \node [_@@_node_style,
516                 name = wa-\l_@@_prefix_str-\int_use:N\g_@@_line_int-r,
517                 alias = {\tl_if_empty:NF \l_@@_name_tl
518                           {\l_@@_name_tl-\int_use:N\g_@@_line_int-r}} ] {} ;
519     \bool_if:NT \l_@@_shownodenames_bool
520         {\hbox_overlap_right:n {\small wa-\l_@@_prefix_str
521                               -\int_use:N\g_@@_line_int}}
522     & ##
523     \tabskip = \c_zero_skip
524     && \msg_error:nn {witharrows} {Third-column-in-an-environment-{DispWithArrows}}
525         \iffalse ## \fi
526         \cr
527     {\\}

```

The following \egroup is for the \halign.

```
528     \egroup
```

The following \egroup is for the \vcenter (aimed to prevent page breaks).

```
529     \egroup
530     $$
```

If the option `wrap-lines` is used (only in `{DispWithArrows}` and `{DispWithArrows*}`), we compute `\g_@@_x_right_dim`. As a first approximation, `\g_@@_x_right_dim` is the *x*-value of the right side of the current composition box. In fact, we must take into account the potential labels of the equations. That's why we compute `\g_@@_x_right_dim` with the v-nodes of each row specifically built in this goal. `\g_@@_x_right_dim` is the minimal value of the *x*-value of these nodes.

```
531     \bool_if:NT \l_@@_wrap_lines_bool
532         {\dim_gzero_new:N \g_@@_x_right_dim}
```

```

533     \dim_gset:Nn \g_@@_x_right_dim \c_max_dim
534     \begin{tikzpicture} [@@_standard]
535     \int_step_variable:nnnNn 1 1 \g_@@_line_int \l_tmpa_int
536         {\tikz@parse@node\pgfutil@firstofone (\l_tmpa_int-v)
537             \dim_set:Nn \l_tmpa_dim \pgf@x
538             \dim_compare:nNnT \l_tmpa_dim < \g_@@_x_right_dim
539                 {\dim_gset:Nn \g_@@_x_right_dim \l_tmpa_dim} }
540     \end{tikzpicture}}

```

The code in `\@@_post_environment:` is common to `{WithArrows}` and `{DispWithArrows}`.

```

541     \@@_post_environment:

```

If `mathtools` has been loaded with the option `showonlyrefs`, we reactivate the code of `mathtools` for the option `showonlyrefs` with the command `\MT_showonlyrefs_true:` (it has been desactivated in the beginning of the environment).

```

542     \bool_if:nT \c_@@_mathtools_loaded_bool
543         {\MH_if_boolean:nT {show_only_refs}
544             \MT_showonlyrefs_true:
545         \ignorespacesafterend
546     }

```

The command `\@@_tag` will be linked to `\tag` in the environment `{DispWithArrows}`.

```

547 \NewDocumentCommand \@@_tag {sm}
548     {\tl_if_empty:NF \l_@@_tag_tl
549         {\msg_error:nnn {witharrows} {Multiple~tags} {#2}}
550     \bool_set_false:N \l_@@_notag_bool
551     \bool_if:nT \c_@@_mathtools_loaded_bool
552         {\MH_if_boolean:nT {show_only_refs}
553             {\MH_if_boolean:nF {show_manual_tags}
554                 {\bool_set_true:N \l_@@_notag_bool}}}
555     \tl_set:Nn \l_@@_tag_tl {#2}
556     \bool_set:Nn \l_@@_tag_star_bool {#1}

```

The starred version `\tag*` can't be used if `amsmath` has not been loaded because this version does the job by desactivating the command `\tagform@` inserted by `amsmath` in the (two versions of the) command `\@eqnnum`.²⁴

```

557     \bool_if:nT {#1 && ! \bool_if_p:N \c_@@_amsmath_loaded_bool}
558         { \msg_error:nn {witharrows} {tag*~without~amsmath} }
559     }

```

With the environment `{DispWithArrows*}`, the equations are not numbered. We don't put `\begin{DispWithArrows}` and `\end{DispWithArrows}` because there is a `\@currenvir` in an error message.

```

560 \NewDocumentEnvironment {DispWithArrows*} {}
561     {\WithArrowsOptions{notag}
562     \DispWithArrows
563     \endDispWithArrows}

```

9.9 We draw the arrows

`\@@_draw_arrows:` draws the arrows when the option `group` or the option `groups` is used. In both cases, we have to compute the x -value of a group of arrows before actually drawing the arrows of that group. The arrows will actually be drawn by the macro `\@@_draw_arrows:nn`.

```

564 \cs_new_protected:Nn \@@_draw_arrows:
565     { \group_begin:

```

²⁴There are two versions of `\@eqnnum`, a standard version and a version for the option `leqno`.

\l_@@_first_arrow_of_group_int will be the first arrow of the current group.
\l_@@_first_line_of_group_int will be the first line involved in the group of arrows (equal to the initial line of the first arrow of the group because the option jump is always positive).
\l_@@_last_line_of_group_int will be the last line involved in the group (impossible to guess in advance).

```
566   \int_zero_new:N \l_@@_first_arrow_of_group_int
567   \int_zero_new:N \l_@@_first_line_of_group_int
568   \int_zero_new:N \l_@@_last_line_of_group_int
569   \bool_set_true:N \l_@@_new_group_bool
```

We begin a loop over all the arrows of the environment. Inside this loop, if a group is finished, we will draw the lines of that group.

```
570   \int_set:Nn \l_@@_arrow_int 1
571   \int_until_do:nNnn \l_@@_arrow_int > \g_@@_arrow_int
572   {
```

We extract from the property list of the current arrow the fields “initial” and “final” and we store these values in \l_@@_initial_int and \l_@@_final_int. However, we have to do a conversion because the components of a property list are token lists.

```
573   \prop_get:cN {g_@@_arrow_\l_@@_prefix_str _\int_use:N\l_@@_arrow_int _prop}
574     {initial} \l_tmpa_tl
575   \int_set:Nn \l_@@_initial_int {\l_tmpa_tl}
576   \prop_get:cN {g_@@_arrow_\l_@@_prefix_str _\int_use:N\l_@@_arrow_int _prop}
577     {final} \l_tmpa_tl
578   \int_set:Nn \l_@@_final_int {\l_tmpa_tl}
```

We test if the previous arrow was in fact the last arrow of a group. In this case, we have to draw all the arrows of that group (with the x -value computed in \g_@@_x_dim).

```
579   \bool_if:nT {      \int_compare_p:nNn \l_@@_pos_arrows_int = 7
580             && \int_compare_p:nNn \l_@@_arrow_int > 1
581             && \int_compare_p:nNn
582               \l_@@_initial_int > \l_@@_last_line_of_group_int}
583   { \@@_draw_arrows:nn \l_@@_first_arrow_of_group_int {\l_@@_arrow_int - 1}
584     \bool_set_true:N \l_@@_new_group_bool}
```

The flag \l_@@_new_group_bool indicates if we have to begin a new group of arrows. In fact, we have to begin a new group in two circonstancies: if we are at the first arrow of the environment (that's why the flag is raised before the beginning of the loop) an if we have just finished a group (that's why the flag is raised in the previous conditionnal). At the beginning of a group, we have to initialize four variables: \l_@@_first_arrow_int, \l_@@_first_line_of_group_int, \l_@@_last_line_of_group and \g_@@_x_dim (global for technical reasons). The last two will evolve during the construction of the group.

```
585   \bool_if:nTF \l_@@_new_group_bool
586     {\bool_set_false:N \l_@@_new_group_bool
587      \int_set:Nn \l_@@_first_arrow_of_group_int \l_@@_arrow_int
588      \int_set:Nn \l_@@_first_line_of_group_int \l_@@_initial_int
589      \int_set:Nn \l_@@_last_line_of_group_int \l_@@_final_int
590      \begin{tikzpicture} [\@_standard]
591        \tikz@parse@node\pgfutil@firstofone (\int_use:N\l_@@_initial_int-1)
592        \dim_gset:Nn \g_@@_x_dim \pgf@x
593        \end{tikzpicture}
594    }
```

If we are not at the beginning of a new group, we actualize \l_@@_last_line_of_group_int.

```
595   {\int_set:Nn \l_@@_last_line_of_group_int
596     {\int_max:nn \l_@@_last_line_of_group_int \l_@@_final_int}}
```

We update the current x -value (in $\backslash g_{@@}x_dim$) even if we are at the beginning of a group. Indeed, the previous initialisation of $\backslash g_{@@}x_dim$ only considers the initial line of the arrows and now we consider all the lines between the initial and the final line. This is done with $\backslash @@_update_x_value:nn$. We have written a command for this because it is also used with the option i ($\backslash l_{@@}pos_arrows_int = 5$).

```
597     \@@_update_x_value:nn \l_{@@}initial_int \l_{@@}final_int
```

Incrementation of the index of the loop (and end of the loop).

```
598     \int_incr:N \l_{@@}arrow_int
599 }
```

After the last arrow of the environment, we have to draw the last group of arrows.

```
600     \@@_draw_arrows:nn \l_{@@}first_arrow_of_group_int \g_{@@}arrow_int
601     \group_end:
602 }
```

The following code is necessary because we will have to expand an argument exactly 3 times.

```
603 \cs_generate_variant:Nn \keys_set:nn {no}
604 \cs_new_protected:Nn \@@_keys_set: { \keys_set:no {WithArrows/General}}
```

The macro $\backslash @@_draw_arrows:nn$ draws all the arrows whose numbers are between #1 and #2. #1 and #2 must be expressions that expands to an integer (they are expanded in the beginning of the macro).

```
605 \cs_new_protected:Nn \@@_draw_arrows:nn
606 { \group_begin:
607   \int_zero_new:N \l_{@@}first_arrow_int
608   \int_set:Nn \l_{@@}first_arrow_int {#1}
609   \int_zero_new:N \l_{@@}last_arrow_int
610   \int_set:Nn \l_{@@}last_arrow_int {#2}
```

We begin a loop over the arrows we have to draw. The variable $\backslash l_{@@}arrow_int$ (local in the environment $\{WithArrows\}$) will be used as index for the loop.

```
611 \int_set:Nn \l_{@@}arrow_int \l_{@@}first_arrow_int
612 \int_until_do:nNnn \l_{@@}arrow_int > \l_{@@}last_arrow_int
613 {
```

We extract from the property list of the current arrow the fields “initial” and “final” and we store these values in $\backslash l_{@@}initial_int$ and $\backslash l_{@@}final_int$. However, we have to do a conversion because the components of a property list are token lists.

```
614 \prop_get:cnN {g_{@@}arrow_\l_{@@}prefix_str _\int_use:N\l_{@@}arrow_int _prop}
615   {initial} \l_tma_t1
616 \int_set:Nn \l_{@@}initial_int {\l_tma_t1}
617 \prop_get:cnN {g_{@@}arrow_\l_{@@}prefix_str _\int_use:N\l_{@@}arrow_int _prop}
618   {final} \l_tma_t1
619 \int_set:Nn \l_{@@}final_int {\l_tma_t1}
```

If the arrow ends after the last line of the environment, we raise an error (we recall that, after the construction of the $\backslash halign$, $\backslash g_{@@}line_int$ is the total number of lines of the environment). If the initial node or the final node doesn’t exist, we also raise an error.²⁵

```
620 \int_compare:nNnTF \l_{@@}final_int > \g_{@@}line_int
621   {\msg_error:nn {witharrows} {Too-few-lines-for-an-arrow}}
622   {\cs_if_free:cTF {pgf@sh@ns@wa-\l_{@@}prefix_str-\int_use:N\l_{@@}initial_int-1}
623     { \msg_error:nn {witharrows} {A-PGF-node-doesn't-exist} }
624     {\cs_if_free:cTF {pgf@sh@ns@wa-\l_{@@}prefix_str-\int_use:N\l_{@@}final_int-1}
625       { \msg_error:nn {witharrows} {A-PGF-node-doesn't-exist} }}
```

²⁵This case occurs if the considered line has no ampersand. In fact, we raise an error if there is such a line in the $\backslash halign$, but, nonetheless, we consider the case where the user goes on and we try to avoid other errors.

```

626          {\@_draw_arrows_i:}}}
627      \int_incr:N \l_@@_arrow_int
628  }
629 \group_end:
630 }
```

The macro `\@_draw_arrows_i:` is only for the lisibility of the code. This macro will draw the current arrow if the arrow is not impossible (that is to say if the Tikz nodes exist). The first `\group_begin:` is for the options of the arrow.

```

631 \cs_new:Nn \@_draw_arrows_i:
632   {\group_begin:
633     \int_set:Nn \l_@@_previous_pos_arrows_int {-1}
634     \int_set:Nn \l_@@_level_int 3}
```

We process the options of the current arrow. The second argument of `\keys_set:nn` must be expanded exactly three times. An x-expansion is not possible because there can be tokens like `\bfseries` in the option `font` of the option `tikz`. This expansion is a bit tricky.

```

635   \prop_get:cnN {g_@@_arrow_\l_@@_prefix_str}
636     _int_use:N\l_@@_arrow_int _prop} {options} \l_tmpa_tl
637   \exp_args:NNo \exp_args:No
638     \@@_keys_set: {\l_tmpa_tl,tikz={xshift = \l_@@_xoffset_dim}}
```

We create two booleans to indicate the position of the initial node and final node of the arrow in cases of options `rr`, `rl`, `lr` or `ll`:

```

639   \bool_set_false:N \l_@@_initial_r_bool
640   \bool_set_false:N \l_@@_final_r_bool
641   \int_case:nn \l_@@_pos_arrows_int
642     {0 {\bool_set_true:N \l_@@_initial_r_bool
643       \bool_set_true:N \l_@@_final_r_bool}
644     2 {\bool_set_true:N \l_@@_initial_r_bool}
645     3 {\bool_set_true:N \l_@@_final_r_bool}}
```

option	rr	ll	rl	lr	v	i	group	groups
<code>\l_@@_pos_arrows_int</code>	0	1	2	3	4	5	6	7

The option `v` can be used only in `\Arrow in CodeAfter` (see below).

In case of option `i` (`\l_@@_pos_arrows_int = 5`), we have to compute the *x*-value of the arrow (which is vertical). The computed *x*-value is stored in `\g_@@_x_dim` (the same variable used when the option `group` or the option `groups` is used). This variable is global for technical reasons: we have to do assignments in a Tikz node.

```

646   \int_compare:nNnT \l_@@_pos_arrows_int = 5
647   {
```

First, we calculate the initial value for `\g_@@_x_dim`. We use a Tikz command, but, in fact, nothing is drawn. We use this Tikz command only to read the abscissa of a Tikz node.

```

648   \begin{tikzpicture} [@@_standard]
649   \tikz@parse@node\pgfutil@firstofone (\int_use:N\l_@@_initial_int-1)
650   \dim_gset:Nn \g_@@_x_dim \pgf@x
651   \end{tikzpicture}
```

A global assignment is necessary because of Tikz.

Then, we will loop to determine the maximal length of the lines between the lines `\l_@@_initial_int` and `\l_@@_final_int...` but we have written a command dedicated to this work because it will also be used in `\@_draw_arrows:`.

```

652   \@@_update_x_value:nn \l_@@_initial_int \l_@@_final_int
653 }
```

`\l_@@_initial_tl` contains the name of the Tikz node from which the arrow starts (in normal cases... because with the option `i`, `group` and `groups`, the point will perhaps have another *x*-value — but always the same *y*-value). Idem for `\l_@@_final_tl`.

```
654     \tl_set:Nx \l_@@_initial_tl
655         {\int_use:N\l_@@_initial_int-\bool_if:NTF\l_@@_initial_r_bool rl .south}
656     \tl_set:Nx \l_@@_final_tl
657         {\int_use:N\l_@@_final_int-\bool_if:NTF\l_@@_final_r_bool rl .north}
```

We use “`.south`” and “`.north`” because we want a small gap between two consecutive arrows (and the Tikz nodes created have the shape of small vertical segments: use option `shownodes` to visualize the nodes).

The label of the arrow will is stored in `\l_tmpa_tl`.

```
658     \prop_get:cN {g_@@_arrow}\l_@@_prefix_str _\int_use:N\l_@@_arrow_int _prop}
659         {label}
660     \l_tmpa_tl
```

We have to compute the coordinates of the extremities of the arrow. We retrieve the coordinates in `\g_tmpa_tl` and `\g_tmpb_tl`. This extraction of the coordinates is necessary because we must give coordinates and not nodes (even anchored) to `\@_draw_arrow:nnn` to have the `xshift` correct.

```
661     \int_compare:nNnTF \l_@@_pos_arrows_int < 5
662         {\begin{tikzpicture} [\@_standard]
663             \tikz@scan@one@point\pgfutil@firstofone(\l_@@_initial_tl)
664             \tl_gset:Nx \g_tmpa_tl {\dim_use:N\pgf@x,\dim_use:N\pgf@y}
665             \tikz@scan@one@point\pgfutil@firstofone(\l_@@_final_tl)
666             \tl_gset:Nx \g_tmpb_tl {\dim_use:N\pgf@x,\dim_use:N\pgf@y}
667         \end{tikzpicture}}
668 }
```

If we use option `i` or `group` or `groups`, we use the abscissa specially computed in `\g_@@_x_dim`.

```
669     {\begin{tikzpicture} [\@_standard]
670         \tikz@scan@one@point\pgfutil@firstofone (\l_@@_initial_tl)
671         \tl_gset:Nx \g_tmpa_tl {\dim_use:N \g_@@_x_dim , \dim_use:N \pgf@y}
672         \tikz@scan@one@point\pgfutil@firstofone (\l_@@_final_tl)
673         \tl_gset:Nx \g_tmpb_tl {\dim_use:N \g_@@_x_dim , \dim_use:N \pgf@y}
674     \end{tikzpicture}}
```

Eventually, we can draw the arrow with the code in `\l_@@_tikz_code_tl`. We recall that the value by default for this token list is : “`\draw (#1) to node {#3} (#2) ;`”. This value can be modified with the option `TikzCode`. We use the variant `\@_draw_arrow:nno` of the macro `\@_draw_arrow:nnn` because of the characters *underscore* in the name `\l_tmpa_tl` : if the user uses the Tikz library `babel`, the third argument of the command `\@_draw_arrow:nno` will be rescanned because this third argument will be in the argument of a command `node` of an instruction `\draw` of Tikz... and we will have an error because of the characters *underscore*.²⁶

```
675     \@_draw_arrow:nno {\g_tmpa_tl} {\g_tmpb_tl} {\l_tmpa_tl}
```

We close the TeX group opened for the options given to `\Arrow[...]` (local level of the options).

```
676     \group_end: }
```

The function `\@_tmpa:nnn` will draw the arrow. It’s merely an environment `{tikzpicture}`. However, the Tikz instruction in this environment must be inserted from `\l_@@_tikz_code_tl` with the markers `#1`, `#2` and `#3`. That’s why we create a function `\@_def_function_tmpa:n` which will create the function `\@_tmpa:nnn`.

```
677     \cs_new_protected:Nn \@_def_function_tmpa:n
678         {\cs_set:Nn \@_tmpa:nnn
679             {\begin{tikzpicture}[\@_standard,every~path/.style = {WithArrows/arrow}]
680                 #1
681             \end{tikzpicture}}}
```

²⁶There were other solutions : use another name without *underscore* (like `\ltmpat1`) or use the package `underscore` (with this package, the characters *underscore* will be rescanned without errors, even in text mode).

When we draw the arrow (with `\@@_draw_arrow:nnn`), we first create the function `\@@_tmpa:nnn` and, then, we use the function `\@@_tmpa:nnn`:

```
682 \cs_new_protected:Nn \@@_draw_arrow:nnn
683     {
```

If the option `wrap-lines` is used, we have to use a special version of `TikzCode`. Here is the use of `\g_@@_x_right_dim` which has been computed previously with the v-nodes.

```
684     \bool_if:nT {\l_@@_wrap_lines_bool && ! \l_@@_in_witharrows_bool}
685         {\tl_set:Nn \l_@@_tikz_code_tl
686             {\draw (#1) to node (@_label) {} (#2) ;
687                 \tikz@parse@node \pgfutil@firstofone (@_label.west)
688                 \path (@_label.west)
689                 node [anchor = west,
690                     text-width = \dim_eval:n {\g_@@_x_right_dim - \pgf@x - 0.3333 em}]
691                     {##3} ; }}
```

`0.3333 em` is the default value of `inner sep` in the nodes of `Tikz`. Maybe we should put the exact `Tikz` parameter. Now, the main lines of this function `\@@_draw_arrow:nnn`.

```
692     \exp_args:No \@@_def_function_tmpa:n \l_@@_tikz_code_tl
693         \@@_tmpa:nnn {#1} {#2} {#3} }
694 \cs_generate_variant:Nn \@@_draw_arrow:nnn {nno}
```

The command `\@@_update_x_value:nn` will analyze the lines²⁷ between #1 and #2 in order to modify `\g_@@_x_dim` in consequence. More precisely, `\g_@@_x_dim` is increased if a line longer than the current value of `\g_@@_x_dim` is found. `\@@_update_x_value:nn` is used in `\@@_draw_arrows:` (for options `group` and `groups`) and in `\@@_draw_arrows:nn` (for option `i`).

```
695 \cs_new_protected:Nn \@@_update_x_value:nn
696     {\int_step_inline:nnnn {#1} {\c_one} {#2}
697         {\cs_if_exist:cT {\pgf@sh@ns@wa-\l_@@_prefix_str-##1-1}
698             {\begin{tikzpicture} [\@_standard]
699                 \tikz@scan@one@point\pgfutil@firstofone (#1-1)
700                 \dim_gset:Nn \g_@@_x_dim {\dim_max:nn \g_@@_x_dim \pgf@x}
701             \end{tikzpicture} } } }
```

The command `\WithArrowsLastEnv` is not used by the package `witharrows`. It's only a facility given to the final user. It gives the number of the last environment `{WithArrows}` at level 0 (to the sens of the nested environments). This macro is fully expandable and, thus, can be used directly in the name of a `Tikz` node.

```
702 \cs_new:Npn \WithArrowsLastEnv {\int_use:N \g_@@_last_env_int}
```

9.10 The command Arrow in CodeAfter

The option `CodeAfter` is an option of the environment `{WithArrows}` (this option is only available at the environment level). In the option `CodeAfter`, one can use the command `Arrow` but it's a special version of the command `Arrow`. For this special version (internally called `\@@_Arrow_code_after`), we define a special set of keys called `WithArrows/CodeAfter`.

```
703 \keys_define:nn {WithArrows/CodeAfter}
704     {tikz .code:n           = \tikzset {WithArrows/arrow/.append~style = {#1}} ,
705      tikz .value_required:n = true,
706      rr   .value_forbidden:n = true,
707      rr   .code:n           = \@@_analyze_option_position:n 0 ,
708      ll   .value_forbidden:n = true,
709      ll   .code:n           = \@@_analyze_option_position:n 1 ,
710      rl   .value_forbidden:n = true,
711      rl   .code:n           = \@@_analyze_option_position:n 2 ,
712      lr   .value_forbidden:n = true,
```

²⁷If a line has no ampersand, this line is ignored. In fact, we raise an error if there is a line without ampersand but, nonetheless, we consider the case where the user goes on and we try to avoid other errors.

```

713     lr      .code:n      = \@@_analyze_option_position:n 3 ,
714     v       .value_forbidden:n = true,
715     v       .code:n      = \@@_analyze_option_position:n 4 ,
716     TikzCode .tl_set:N      = \l_@@_tikz_code_t1,
717     TikzCode .value_required:n = true,
718     xoffset .dim_set:N      = \l_@@_xoffset_dim,
719     xoffset .value_required:n = true}

720 \NewDocumentCommand \@@_Arrow_code_after {O{} mmm O{}}
721   {\int_set:Nn \l_@@_pos_arrows_int 1
722    \int_set:Nn \l_@@_previous_pos_arrows_int {-1}
723    \group_begin:

```

Even if `\Arrow` in `CodeAfter` has its own set of options (`WithArrows/CodeAfter`), we set the level of the options to 3 (as with the classical command `\Arrow`) because of the error messages.

```

724   \int_set:Nn \l_@@_level_int 3
725   \keys_set:nn {WithArrows/CodeAfter}
726     {#1,#5,tikz={xshift = \l_@@_xoffset_dim}}
727   \bool_set_false:N \l_@@_initial_r_bool
728   \bool_set_false:N \l_@@_final_r_bool
729   \int_case:nn \l_@@_pos_arrows_int
730     {0 {\bool_set_true:N \l_@@_initial_r_bool
731         \bool_set_true:N \l_@@_final_r_bool}
732     2 {\bool_set_true:N \l_@@_initial_r_bool}
733     3 {\bool_set_true:N \l_@@_final_r_bool}}

```

We test whether the two Tikz nodes (#2-1) and (#3-1) really exist. If not, the arrow won't be drawn.

```

734   \cs_if_free:cTF {pgf@sh@ns@wa-\l_@@_prefix_str-#2-1}
735     {\msg_error:nnx {witharrows} {Wrong-line-specification-in-Arrow} {#2}}
736     {\cs_if_free:cTF {pgf@sh@ns@wa-\l_@@_prefix_str-#3-1}
737       {\msg_error:nnx {witharrows} {Wrong-line-specification-in-Arrow} {#3}}
738       {\int_compare:nNnTF \l_@@_pos_arrows_int = 4
739         {\begin{tikzpicture} [@@_standard]
740           \tikz@scan@one@point\pgfutil@firstofone(#2-1.south)
741           \dim_set_eq:NN \l_tmpa_dim \pgf@x
742           \dim_set_eq:NN \l_tmpb_dim \pgf@y
743           \tikz@scan@one@point\pgfutil@firstofone(#3-1.north)
744           \dim_set:Nn \l_tmpa_dim {\dim_max:nn \l_tmpa_dim \pgf@x}
745           \tl_gset:Nx \g_tmpa_tl {\dim_use:N \l_tmpa_dim , \dim_use:N \l_tmpb_dim}
746           \tl_gset:Nx \g_tmpb_tl {\dim_use:N \l_tmpa_dim , \dim_use:N \pgf@y}
747         \end{tikzpicture} }
748         {\begin{tikzpicture} [@@_standard]
749           \tikz@scan@one@point\pgfutil@firstofone
750             (#2-\bool_if:NTF\l_@@_initial_r_bool rl .south)
751             \tl_gset:Nx \g_tmpa_tl {\dim_use:N \pgf@x , \dim_use:N \pgf@y}
752             \tikz@scan@one@point\pgfutil@firstofone
753               (#3-\bool_if:NTF\l_@@_final_r_bool rl .north)
754               \tl_gset:Nx \g_tmpb_tl {\dim_use:N \pgf@x , \dim_use:N \pgf@y}
755             \end{tikzpicture}}
756           \@@_draw_arrow:nnn {\g_tmpa_tl} {\g_tmpb_tl} {#4} }
757         \group_end:
758       }

```

9.11 MultiArrow

The command `\@@_MultiArrow:nn` will be linked to `\MultiArrow` when the `CodeAfter` is executed.

```

759 \cs_new_protected:Nn \@@_MultiArrow:nn
760   {

```

The user of the command `\MultiArrow` (in `CodeAfter`) will be able to specify the list of lines with the same syntax as the loop `\foreach` of `pgffor`. That's why we construct a “clist” of `expl3` from the specification of list given by the user. The construction of the “clist” must be global in order to exit the `\foreach` and that's why we construct the list in `\g_tmpa_clist`.

```
761 \foreach \x in {#1} {\cs_if_free:cTF {pgf@sh@ns@wa-\l_@@_prefix_str-\x-1}
762             {\msg_error:nnx {witharrows}
763                 {Wrong-line-specification-in-MultiArrow}
764                 {\x}}
765             {\clist_gput_right:Nx \g_tmpa_clist {\x}}}
```

We sort the list `\g_tmpa_clist` because we want to extract the minimum and the maximum.

```
766 \int_compare:nNnTF {\clist_count:N \g_tmpa_clist} < 2
767     {\msg_error:nn {witharrows} {Too-small-specification-for-MultiArrow}}
768     {\clist_sort:Nn \g_tmpa_clist
769         {\int_compare:nNnTF {##1} > {##2}
770             {\sort_return_swapped:}
771             {\sort_return_same:}}}
```

We extract the minimum in `\l_tmpa_tl` (it must be an integer but we store it in a token list of `expl3`).

```
772 \clist_pop:NN \g_tmpa_clist \l_tmpa_tl
```

We extract the maximum in `\l_tmpb_tl`. The remaining list (in `\g_tmpa_clist` will be sorted in decreasing order but never mind...).

```
773 \clist_reverse:N \g_tmpa_clist
774 \clist_pop:NN \g_tmpa_clist \l_tmpb_tl
```

We draw the teeth of the rak (except the first one and the last one) with the auxiliary function `\@@_MultiArrow_i:n`. This auxiliary fonction is necessary to expand the specification of the list in the `\foreach` loop. The first and the last teeth of the rak can't be drawn the same way as the others (think, for example, to the case of the option “rounded corners” is used).

```
775 \exp_args:Nx \@@_MultiArrow_i:n {\g_tmpa_clist}
```

Now, we draw the rest of the structure.

```
776 \begin{tikzpicture}[@@_standard,every-path/.style={WithArrows/arrow}]
777     \draw [->] ([xshift = \l_@@_xoffset_dim]\l_tmpa_tl-r.south)
778             -- +(5mm,0)
779             -- node (@@_label) {}
780             ([xshift = \l_@@_xoffset_dim+5mm]\l_tmpb_tl-r.south)
781             -- ([xshift = \l_@@_xoffset_dim]\l_tmpb_tl-r.south) ;
782     \tikz@parse@node \pgfutil@firstofone (@@_label.west)
783     \path (@@_label.west)
784     node [anchor = west,
785             text-width =
786             {\bool_if:nTF {\l_@@_wrap_lines_bool && ! \l_@@_in_witharrows_bool}
787                 {\dim_eval:n {\g_@@_x_right_dim - \pgf@x - 0.3333 em}}
788                 {20 cm}}
789             ] {#2} ;
790 \end{tikzpicture} } }
```

```
791
792 \cs_new_protected:Nn \@@_MultiArrow_i:n
793     {\begin{tikzpicture}[@@_standard,every-path/.style={WithArrows/arrow}]
794         \foreach \k in {#1}
795             {\draw[<-] ([xshift = \l_@@_xoffset_dim]\k-r.south) -- +(5mm,0) ;}
796     \end{tikzpicture}}
```

9.12 The error messages of the package

```
797 \msg_new:nnn {witharrows}
798     {Third-column-in-an-environment-{WithArrows}}
799     {By-default,-an-environment-\{WithArrows\}-can-only-have-two-columns.-}
800     {Maybe-you-have-forgotten-a-\str_use:N \c_underscored_str
801     \str_use:N \c_underscored_str.-If-you-really-want-more-than-two-columns,-}
```

```

802     you~should~use~the~option~"MoreColumns"~at~a~global~level~or~for~
803     an~environment.~However,~you~can~go~one~for~this~time.}

804 \msg_new:nnn {witharrows}
805   {Third~column~in~an~environment~\{DispWithArrows\}}
806   {An~environment~\{DispWithArrows\}~or~\{DispWithArrows*\}~can~only~
807    have~two~columns.~If~you~go~on,~you~may~have~an~incorrect~output.}

808 \msg_new:nnn {witharrows}
809   {The~option~"jump"~must~be~non~negative}
810   {You~can't~use~a~strictly~negative~value~for~the~option~"jump"~of~command~
811    \token_to_str:N\Arrow.~ You~can~create~an~arrow~going~backwards~with~
812    the~option~"<-"~of~Tikz.}

813 \msg_new:nnn {witharrows}
814   {Too~few~lines~for~an~arrow}
815   {An~arrow~specified~in~line~\int_use:N \l_@@_initial_int~can't~be~drawn~
816    because~it~arrives~after~the~last~line~of~the~environment~(remind~that~
817    the~command~\token_to_str:N\Arrow~must~be~in~the~*start*~line~
818    of~the~arrow).~If~you~go~on,~this~arrow~will~be~ignored.}

819 \msg_new:nnn {witharrows}
820   {{WithArrows}~used~outside~math~mode}
821   {The~environment~\{WithArrows\}~should~be~used~only~in~math~mode.~
822    Nevertheless,~you~can~go~on.}

823 \msg_new:nnn {witharrows}
824   {{DispWithArrows}~used~in~math~mode}
825   {The~environment~\{DispWithArrows\}~should~be~used~only~outside~math~mode.~
826    If~you~go~on,~you~will~have~other~errors.}

827 \msg_new:nnn {witharrows}
828   {Two~options~are~incompatible}
829   {You~try~to~use~the~option~"\tl_use:N\l_keys_key_tl"~but~
830    this~option~is~incompatible~or~redundant~with~the~option~"
831    \int_case:nn\l_@@_previous_pos_arrows_int
832      {0 {rr}
833        1 {ll}
834        2 {rl}
835        3 {lr}
836        4 {v}
837        5 {i}
838        6 {group}
839        7 {groups}}"~
840    set~in~the~same~
841    \int_case:nn\l_@@_level_int
842      {1 {command~\token_to_str:N\WithArrowsOptions}
843        2 {declaration-of-options-of-the-environment-
844          \{\currenvir\}}
845        3 {command~\token_to_str:N\Arrow}}.~
846    If~you~go~on,~I~will~use~the~option~"\tl_use:N\l_keys_key_tl".}

847 \msg_new:nnnn {witharrows}
848   {All~lines~must~have~an~ampersand}
849   {All~lines~of~an~environment~\{WithArrows\}~should~
850    have~an~second~column~(because~the~nodes~are~created~
851    in~the~second~column).~However,~you~can~go~but~you~will~
852    have~an~error~if~one~of~your~arrows~needs~an~PGF~
853    node~absent~by~lack~of~ampersand.~If~you~don't~want~to~
854    see~this~message~again,~you~can~use~the~option~
855    AllowLineWithoutAmpersand.}
856   {Moreover,~the~ampersand~can~be~implicit~
857    (e.g.~if~you~use~\token_to_str:N\MoveEqLeft~of~mathtools).}

858 \msg_new:nnn {witharrows}
859   {Option~incompatible~with~"group(s)"}
860   {You~try~to~use~the~option~"\tl_use:N\l_keys_key_tl"~while~
861    you~are~using~the~option~"

```

```

862     \int_compare:nNnTF \l_@@_pos_arrows_int = 5
863         {group}
864         {groups}".~"
865         It's~incompatible.~You~can~go~on~ignoring~this~option~
866         "\tl_use:N\l_keys_key_tl"~but~you~should~correct~your~code.}

867 \msg_new:nnn {witharrows}
868     {Option~will~be~ignored}
869     {The~option~"\tl_use:N\l_keys_key_tl"~can't~be~used~here.~
870      If~you~go~on,~it~will~be~ignored.}

871 \msg_new:nnn {witharrows}
872     {Option~unknown}
873     {The~option~"\tl_use:N\l_keys_key_tl"~is~unknown~or~
874      meaningless~in~the~context.~If~you~go~on,~it~will~be~ignored.}

875 \msg_new:nnn {witharrows}
876     {Arrow~in~first~column}
877     {You~should~not~use~the~command~"\token_to_str:N\Arrow\
878      \tl_if_eq:NNF \l_@@_CommandName_tl \l_tmpa_tl
879          {(renamed~in~\str_use:N \c_underscore)
880            \tl_use:N \l_@@_CommandName_tl)~}
881          ~in~the~first~column~but~only~in~the~second~column.~
882          This~is~a~restriction~of~the~version~1.3~of~the~
883          package~witharrows~(in~the~aim~of~developing~further~
884          ~a~new~functionality~with~"\token_to_str:N\Arrow\ in~the~
885          first~column).\\
886          However~you~can~go~on~for~this~time.}

887 \msg_new:nnn {witharrows}
888     {Wrong~line~specification~in~Arrow}
889     {The~specification~of~line~"#1"~you~use~in~"\token_to_str:N\Arrow\
890      ~doesn't~exist.\\
891      If~you~go~on,~the~arrow~will~be~ignored.}

892 \msg_new:nnn {witharrows}
893     {Wrong~line~specification~in~MultiArrow}
894     {The~specification~of~line~"#1"~doesn't~exist.\\
895      If~you~go~on,~it~will~be~ignored~for~"\token_to_str:N \MultiArrow."}

896 \msg_new:nnn {witharrows}
897     {Too~small~specification~for~MultiArrow}
898     {The~specification~of~lines~you~gave~to~"\token_to_str:N \MultiArrow\
899      is~too~small:~we~need~at~least~two~lines.~If~you~go~on,~the~
900      command~"\token_to_str:N\MultiArrow\ ~will~be~ignored.}

901 \msg_new:nnn {witharrows}
902     {A~PGF~node~doesn't~exist}
903     {A~PGF~node~necessary~to~draw~an~arrow~doesn't~exist~
904       because~you~didn't~put~an~ampersand~in~the~corresponding~line.~
905       If~you~go~on,~the~arrow~will~be~ignored.}

906 \msg_new:nnn {witharrows}
907     {tag*~without~amsmath}
908     {We~can't~use~"\token_to_str:N\tag*~because~you~haven't~load~amsmath~
909       (or~mathtools).~If~you~go~on,~the~command~"\token_to_str:N\tag\
910       will~be~used~instead.}

911 \msg_new:nnn {witharrows}
912     {Command~not~allowed~in~{DispWithArrows}}
913     {The~command~"\token_to_str:N #1
914       is~not~allowed~in~the~first~column~of~"\{DispWithArrows\}~but~
915       only~in~the~second~column~(and,~of~course,~in~the~
916       environments~of~amsmath).~If~you~go~on,~this~command~will~be~ignored.}

917 \msg_new:nnn {witharrows}
918     {Command~not~allowed~in~{WithArrows}}
919     {The~command~"\token_to_str:N #1
920       is~not~allowed~in~"\{WithArrows\}~but~is~allowed~in~the~second~
```

```

921         column~of~\{DispWithArrows\}~(and,~of~course,~in~the~
922         environments~of~amsmath).~If~you~go~on,~this~command~will~be~ignored.)}
923 \msg_new:nnn {witharrows}
924     {Multiple-tags}
925     {You~can't~use~twice~the~command~\token_to_str:N\tag\
926     in~a~line~of~the~environment~\{@currenvir\}.~If~you~go~on,~the~tag~
927     '#1'~will~be~used.}
928 \msg_new:nnn {witharrows}
929     {Multiple-labels}
930     {Normally,~we~can't~use~the~command~\token_to_str:N\label\
931     twice~in~a~line~of~the~environment~\{@currenvir\}.~
932     However,~you~can~go~on.~
933     If~you~don't~want~to~see~this~message~again,~you~can~use~the~option~
934     "AllowMultipleLabels"~at~the~global~or~
935     environment~level~(this~doesn't~work~if~you~use~cleveref).}

```

9.13 Environment {CasesWithArrows}

```

936 \coffin_new:N \l_@@_halign_coffin
937 \NewDocumentEnvironment {CasesWithArrows} {m O{}}
938     {\hbox_set:Nn \l_tmpa_box {$\left\{\vcenter to 1cm {} \right.\right.$}
939     \dim_zero_new:N \l_@@_delim_wd_dim
940     \dim_set:Nn \l_@@_delim_wd_dim {\box_wd:N \l_tmpa_box}
941     \box_clear_new:N \l_@@_left_part_box
942     \hbox_set:Nn \l_@@_left_part_box
943     {${\bool_if:NT \l_@@_displaystyle_bool \displaystyle #1 {}$}}
944     \bool_if:nT \c_@@_mathtools_loaded_bool
945         {\MH_if_boolean:nT {show_only_refs}
946             {\MT_showonlyrefs_false:
947                 \MH_set_boolean_T:n {show_only_refs}
948                 \bool_set_true:N \l_@@_notag_bool}
949             \bool_if:NT \c_@@_amsmath_loaded_bool \intertext@}
950             \if_mode_math:
951                 \msg_error:nn {witharrows}
952                     {{DispWithArrows}~used~in~math~mode}
953             \fi:
954             \bool_set_false:N \l_@@_in_witharrows_bool
955             %
956             \l_@@_pre_environment:n {#2}
957             \nointerlineskip
958             \hbox_to_wd:nn {0.6\linewidth} {}
959             $$
960             \spread@equation
961             \vc coffin_set:Nnw \l_@@_halign_coffin \displaywidth
962                 \bool_if:NTF \l_@@_fleqn_bool
963                     {\tabskip = \c_zero_skip}
964                     {\tabskip = 0 pt plus 1000 pt minus 1000 pt}
965                 \bool_if:NTF \c_@@_amsmath_loaded_bool
966                     {\cs_set_eq:NN \l_@@_old_label \ltx@label}
967                     {\cs_set_eq:NN \l_@@_old_label \label}
968                 \cs_set:Npn \notag {\msg_error:nnn {witharrows}
969                     {Command~not~allowed~in~{DispWithArrows}}
970                     {\notag}}
971                 \cs_set:Npn \nonumber {\msg_error:nnn {witharrows}
972                     {Command~not~allowed~in~{DispWithArrows}}
973                     {\nonumber}}
974                 \cs_set:Npn \tag ##1 {\msg_error:nnn {witharrows}
975                     {Command~not~allowed~in~{DispWithArrows}}
976                     {\tag}}
977                 \cs_set:Npn \label ##1 {\msg_error:nnn {witharrows}
978                     {Command~not~allowed~in~{DispWithArrows}}
979                     {\label}}
980                 \halign to \displaywidth \bgroup
981                     \int_gincr:N \g_@@_line_int

```

```

982     \cs_set_eq:cN \l_@@_CommandName_tl \@@_Arrow_first_column:
983     \strut
984     \bool_if:NT \l_@@_fleqn_bool
985         {\skip_horizontal:n \l_@@_mathindent_dim}
986     \hfil
987     \skip_horizontal:n {\box_wd:N \l_@@_left_part_box + \l_@@_delim_wd_dim}
988     $ \bool_if:NT \l_@@_displaystyle_bool \displaystyle {##}$
989     \tabskip = \c_zero_skip
990     &
991     \cs_set:Npn \notag {\bool_set_true:N \l_@@_notag_bool}
992     \cs_set_eq:NN \nonumber \notag
993     \cs_set_eq:NN \tag \@@_tag
994     \cs_set_eq:NN \label \@@_label:n
995     $ \bool_if:NT \l_@@_displaystyle_bool \displaystyle {{}##}$
996     \tabskip = 0 pt plus 1000 pt minus 1000 pt
997     \int_gincr:N \g_@@_line_bis_int
998     \tikz [remember picture, overlay]
999         \node [@@_node_style,
1000             name = wa-\l_@@_prefix_str-\int_use:N\g_@@_line_int-l,
1001             alias = {\tl_if_empty:NF \l_@@_name_tl
1002                     {\l_@@_name_tl-\int_use:N\g_@@_line_int-l}} ] {} ;
1003     \hfil
1004     \tikz [remember picture, overlay]
1005         \node [@@_node_style,
1006             name = wa-\l_@@_prefix_str-\int_use:N\g_@@_line_int-r,
1007             alias = {\tl_if_empty:NF \l_@@_name_tl
1008                     {\l_@@_name_tl-\int_use:N\g_@@_line_int-r}} ] {} ;
1009     \bool_if:NT \l_@@_shownodenames_bool
1010         {\hbox_overlap_right:n {\small wa-\l_@@_prefix_str
1011                         -\int_use:N\g_@@_line_int}}
1012     & ##
1013     \tabskip = \c_zero_skip
1014     && \msg_error:nn {witharrows} {Third-column-in-an-environment-{DispWithArrows}}
1015         \if_false: ## \fi:
1016         \cr
1017     {
1018         \egroup
1019         \unskip\unpenalty\unskip\unpenalty
1020         \box_set_to_last:N \l_tmpa_box
1021         \nointerlineskip
1022         \box_use:N \l_tmpa_box
1023         \dim_gzero_new:N \g_@@_alignment_dim
1024         \dim_gset:Nn \g_@@_alignment_dim {\box_wd:N \l_tmpa_box}
1025         \box_clear_new:N \l_@@_new_box
1026         \hbox_set:Nn \l_@@_new_box {\hbox_unpack_clear:N \l_tmpa_box}
1027         \dim_compare:nNnT {\box_wd:N \l_@@_new_box} < \g_@@_alignment_dim
1028             \dim_gset:Nn \g_@@_alignment_dim {\box_wd:N \l_@@_new_box}
1029         \vcoffin_set_end:
1030         \hbox_to_wd:nn \displaywidth
1031         {
1032             \bool_if:NTF \l_@@_fleqn_bool
1033                 {\skip_horizontal:n \l_@@_mathindent_dim}
1034                 {\hfil}
1035             \hbox_to_wd:nn \g_@@_alignment_dim
1036                 { \box_use_drop:N \l_@@_left_part_box
1037                     \dim_set:Nn \l_tmpa_dim { \box_ht:N \l_@@_halign_coffin
1038                         + \box_dp:N \l_@@_halign_coffin}
1039                     $ \left \{ \vcenter to \l_tmpa_dim {\vfil} \right . \$ }
1040                 \hfil}
1041             \coffin_typeset:Nnnnn \l_@@_halign_coffin {l} {vc} {-\displaywidth} \c_zero_dim
1042             $$
1043             \_@@_post_environment:
1044             \bool_if:nT \c_@@_mathtools_loaded_bool

```

```

1045      {\MH_if_boolean:nT {show_only_refs}
1046          \MT_showonlyrefs_true:}
1047      \ignorespacesafterend
1048  }

```

10 History

10.1 Changes between versions 1.0 and 1.1

Option for the command `\` and option `interline`

Compatibility with `\usetikzlibrary{babel}`

Possibility of nested environments `{WithArrows}`

Better error messages

Creation of a DTX file

10.2 Changes between versions 1.1 and 1.2

The package `witharrows` can now be loaded without having loaded previously `tikz` and the libraries `arrow.meta` and `bending` (this extension and these libraries are loaded silently by `witharrows`).

New option `groups` (with a *s*)

Better error messages

10.3 Changes between versions 1.2 and 1.3

New options `ygap` and `ystart` for fine tuning.

Minor bugs.

10.4 Changes between versions 1.3 and 1.4

The package `footnote` is no longer loaded by default. Instead, two options `footnote` and `footnotehyper` have been added. In particular, `witharrows` becomes compatible with `beamer`.

10.5 Changes between versions 1.4 and 1.5

The Tikz code used to draw the arrows can be changed with the option `TikzCode`.

Two new options `CodeBefore` and `CodeAfter` have been added at the environment level.

A special version of `\Arrow` is available in `CodeAfter` in order to draw arrows in nested environments.

A command `\MultiArrow` is available in `CodeAfter` to draw arrows of other shapes.

10.6 Changes between versions 1.5 and 1.6

The code has been improved to be faster and the Tikz library `calc` is no longer required.

A new option `name` is available for the environments `{WithArrows}`.

10.6.1 Changes between 1.6 and 1.6.1

Correction of a bug that leads to incompatibility with `\usetikzlibrary{babel}`.

10.7 Changes between 1.6.1 and 1.7

New environments `{DispWithArrows}` and `{DispWithArrows*}`.

10.8 Changes between 1.7 and 1.8

The numbers and tags of the environment `{DispWithArrows}` are now compatible with all the major LaTeX packages concerning references (`autonum`, `cleveref`, `fancyref`, `hyperref`, `prettyref`, `refstyle`, `typedref` and `variorref`) and with the options `showonlyrefs` and `showmanualtags` of `mathtools`.

10.9 Changes between 1.8 and 1.9

New options `wrap-lines` for the environments `{DispWithArrows}` and `{DispWithArrows*}`.