

The luakeys package

Josef Friedrich
josef@friedrich.rocks
github.com/Josef-Friedrich/luakeys

0.9.0 from 2022/11/21

```
local result = luakeys.parse(
  'level1={level2={naked,dim=1cm,bool=false,num=-0.001,str="lua,{}}}',
  { convert_dimensions = true })
luakeys.debug(result)
```

Result:

```
{
  ['level1'] = {
    ['level2'] = {
      ['naked'] = true,
      ['dim'] = 1864679,
      ['bool'] = false,
      ['num'] = -0.001,
      ['str'] = 'lua,{}'}
    }
  }
```

Contents

1	Introduction	4
1.1	Pros of luakeys	4
1.2	Cons of luakeys	4
2	How the package is loaded	4
2.1	Using the Lua module luakeys.lua	4
2.2	Using the Lua ^L A _T E _X wrapper luakeys.sty	5
2.3	Using the plain Lua ^L A _T E _X wrapper luakeys.tex	5
3	Lua interface / API	5
3.1	Lua identifier names	6
3.2	Function “parse(kv_string, opts): result, unknown, raw”	6
3.3	Options to configure the parse function	7
3.3.1	Option “assignment_operator”	8
3.3.2	Option “convert_dimensions”	9
3.3.3	Option “debug”	9
3.3.4	Option “default”	10
3.3.5	Option “defaults”	10
3.3.6	Option “defs”	10
3.3.7	Option “format_keys”	11
3.3.8	Option “group_begin”	11
3.3.9	Option “group_end”	11
3.3.10	Option “hooks”	11
3.3.11	Option “list_separator”	13
3.3.12	Option “naked_as_value”	13
3.3.13	Option “no_error”	13
3.3.14	Option “quotation_begin”	13
3.3.15	Option “quotation_end”	13
3.3.16	Option “unpack”	13
3.4	Function “define(defs, opts): parse”	14
3.5	Attributes to define a key-value pair	14
3.5.1	Attribute “alias”	15
3.5.2	Attribute “always_present”	16
3.5.3	Attribute “choices”	16
3.5.4	Attribute “data_type”	16
3.5.5	Attribute “default”	17
3.5.6	Attribute “exclusive_group”	17
3.5.7	Attribute “opposite_keys”	17
3.5.8	Attribute “macro”	18
3.5.9	Attribute “match”	18
3.5.10	Attribute “name”	18
3.5.11	Attribute “pick”	19
3.5.12	Attribute “process”	20
3.5.13	Attribute “required”	21
3.5.14	Attribute “sub_keys”	21
3.6	Function “render(result): string”	22
3.7	Function “debug(result): void”	22
3.8	Function “save(identifier, result): void”	22

3.9	Function “get(identifier): result”	22
3.10	Table “is”	23
3.10.1	Function “is.boolean(value): boolean”	23
3.10.2	Function “is.dimension(value): boolean”	23
3.10.3	Function “is.integer(value): boolean”	23
3.10.4	Function “is.number(value): boolean”	23
3.10.5	Function “is.string(value): boolean”	24
3.10.6	Function “is.any(value): boolean”	24
3.11	Table “utils”	24
3.11.1	Function “utils.scan_oarg(initial_delimiter?, endDelimiter?): string”	24
3.12	Table “version”	25
4	Syntax of the recognized key-value format	25
4.1	An attempt to put the syntax into words	25
4.2	An (incomplete) attempt to put the syntax into the Extended Backus-Naur Form	25
4.3	Recognized data types	26
4.3.1	boolean	26
4.3.2	number	26
4.3.3	dimension	28
4.3.4	string	28
4.3.5	Naked keys	29
5	Examples	30
5.1	Extend and modify keys of existing macros	30
5.2	Process document class options	31
6	Debug packages	32
6.1	For plain TeX: luakeys-debug.tex	32
6.2	For L ^A T _E X: luakeys-debug.sty	32
7	Implementation	33
7.1	luakeys.lua	33
7.2	luakeys.tex	56
7.3	luakeys.sty	57
7.4	luakeys-debug.tex	58
7.5	luakeys-debug.sty	59

1 Introduction

`luakeys` is a Lua module / LuaTeXpackage that can parse key-value options like the TeX packages `keyval`, `kvsetkeys`, `kvoptions`, `xkeyval`, `pgfkeys` etc. `luakeys`, however, accomplishes this task by using the Lua language and doesn't rely on TeX. Therefore this package can only be used with the TeX engine LuaTeX. Since `luakeys` uses LPeg, the parsing mechanism should be pretty robust.

The TUGboat article “[Implementing key–value input: An introduction](#)” (Volume 30 (2009), No. 1) by Joseph Wright and Christian Feuersänger gives a good overview of the available key-value packages.

This package would not be possible without the article “[Parsing complex data formats in LuaTeX with LPeg](#)” (Volume 40 (2019), No. 2).

1.1 Pros of `luakeys`

- Key-value pairs can be parsed independently of the macro collection (LATEX or ConTeXt).
- Even in plain LuaTeX keys can be parsed.
- `luakeys` can handle nested lists of key-value pairs, i.e. it can handle a recursive data structure of keys.
- Keys do not have to be defined, but can they can be defined.

1.2 Cons of `luakeys`

- The package works only in combination with LuaTeX.
- You need to know two languages: TeX and Lua.

2 How the package is loaded

2.1 Using the Lua module `luakeys.lua`

The core functionality of this package is realized in Lua. So you can use `luakeys` even without using the wrapper files `luakeys.sty` and `luakeys.tex`.

```
\documentclass{article}
\directlua{
    luakeys = require('luakeys')
}

\newcommand{\helloworld}[2][]{
    \directlua{
        local keys = luakeys.parse('\luaescapestring{\unexpanded{#1}}')
        luakeys.debug(keys)
        local marg = '#2'
        tex.print(keys.greeting .. ', ' .. marg .. keys.punctuation)
    }
}
\begin{document}
\helloworld[greeting=hello,punctuation!=]{world} % hello, world!
\end{document}
```

2.2 Using the Lua^LA_TE_X wrapper luakeys.sty

For example, the MiK^TE_X package manager downloads packages only when needed. It has been reported that this automatic download only works with this wrapper files. Probably MiK^TE_X is searching for an occurrence of the L^AT_EX macro “`\usepackage {luakeys}`”. The supplied Lua^LA_TE_X file is quite small:

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{luakeys}
\directlua{luakeys = require('luakeys')}
```

It loads the Lua module into the global variable `luakeys`.

```
\documentclass{article}
\usepackage{luakeys}

\begin{document}
\directlua{
    local keys = luakeys.parse('one,two,three', { naked_as_value = true })
    tex.print(keys[1])
    tex.print(keys[2])
    tex.print(keys[3])
} % one two three
\end{document}
```

2.3 Using the plain Lua^LA_TE_X wrapper luakeys.tex

Even smaller is the file `luakeys.tex`. It consists of only one line:

```
\directlua{luakeys = require('luakeys')}
```

It does the same as the Lua^LA_TE_X wrapper and loads the Lua module `luakeys.lua` into the global variable `luakeys`.

```
\input luakeys.tex

\directlua{
    local keys = luakeys.parse('one,two,three', { naked_as_value = true })
    tex.print(keys[1])
    tex.print(keys[2])
    tex.print(keys[3])
} % one two three
\bye
```

3 Lua interface / API

The Lua module exports this functions and tables:

```
local luakeys = require('luakeys')
local version = luakeys.version
local opts = luakeys.opts
local stringify = luakeys.stringify
local define = luakeys.define
local parse = luakeys.parse
local render = luakeys.render
local debug = luakeys.debug
local save = luakeys.save
```

```

local get = luakeys.get
local is = luakeys.is

```

This documentation presents only the public functions and tables. To learn more about the private, not exported functions, please read the [source code documentation](#), which was created with [LDoc](#).

3.1 Lua identifier names

The project uses a few abbreviations for variable names that are hopefully unambiguous and familiar to external readers.

Abbreviation	spelled out	Example
<code>kv_string</code>	Key-value string	'key=value'
<code>opts</code>	Options (for the parse function)	{ no_error = false }
<code>defs</code>	Definitions	
<code>def</code>	Definition	
<code>attr</code>	Attributes (of a definition)	

These unabbreviated variable names are commonly used.

<code>result</code>	The final result of all individual parsing and normalization steps.
<code>unknown</code>	A table with unknown, undefined key-value pairs.
<code>raw</code>	The raw result of the Lpeg grammar parser.

3.2 Function “`parse(kv_string, opts): result, unknown, raw`”

The function `parse(kv_string, opts)` is the most important function of the package. It converts a key-value string into a Lua table.

```

\documentclass{article}
\usepackage{luakeys}
\begin{document}
\newcommand{\mykeyvalcmd}[2][]{%
\directlua{%
  local result = luakeys.parse('#1')
  tex.print('The key "one" has the value ' .. tostring(result.one) .. '.')
}
  marg: #2
}
\mykeyvalcmd[one=1]{test}
\end{document}

```

In plain TeX:

```

\input luakeys.tex
\def\mykeyvalcmd#1{%
\directlua{%
  local result = luakeys.parse('#1')
  tex.print('The key "one" has the value ' .. tostring(result.one) .. '.')
}
\mykeyvalcmd{one=1}
\bye

```

3.3 Options to configure the parse function

The `parse` function can be called with an options table. This options are supported: assignment_operator, convert_dimensions, debug, default, defaults, format_keys, group_begin, group_end, hooks, list_separator, naked_as_value, no_error, quotation_begin, quotation_end, unpack

```
local opts = {
    -- Configure the delimiter that assigns a value to a key.
    assignment_operator = '=',
    -- Automatically convert dimensions into scaled points (1cm -> 1864679).
    convert_dimensions = false,
    -- Print the result table to the console.
    debug = false,
    -- The default value for naked keys (keys without a value).
    default = true,
    -- A table with some default values. The result table is merged with
    -- this table.
    defaults = { key = 'value' },
    -- Key-value pair definitions.
    defs = { key = { default = 'value' } },
    -- lower, snake, upper
    format_keys = { 'snake' },
    -- Configure the delimiter that marks the beginning of a group.
    group_begin = '{',
    -- Configure the delimiter that marks the end of a group.
    group_end = '}',
    -- Listed in the order of execution
    hooks = {
        kv_string = function(kv_string)
            return kv_string
        end,
        -- Visit all key-value pairs recursively.
        keys_before_opts = function(key, value, depth, current, result)
            return key, value
        end,
        -- Visit the result table.
        result_before_opts = function(result)
        end,
        -- Visit all key-value pairs recursively.
        keys_before_def = function(key, value, depth, current, result)
            return key, value
        end,
        -- Visit the result table.
        result_before_def = function(result)
        end,
    }
}
```

```

-- Visit all key-value pairs recursively.
keys = function(key, value, depth, current, result)
    return key, value
end,

-- Visit the result table.
result = function(result)
end,
},

-- Configure the delimiter that separates list items from each other.
list_separator = ',',

-- If true, naked keys are converted to values:
-- { one = true, two = true, three = true } -> { 'one', 'two', 'three' }
naked_as_value = false,

-- Throw no error if there are unknown keys.
no_error = false,

-- Configure the delimiter that marks the beginning of a string.
quotation_begin = "'",

-- Configure the delimiter that marks the end of a string.
quotation_end = "'",

-- { key = { 'value' } } -> { key = 'value' }
unpack = false,
}

```

The options can also be set globally using the exported table `opts`:

```
local result = luakeys.parse('dim=1cm') -- { dim = '1cm' }
```

```
luakeys.opts.convert_dimensions = true
local result2 = luakeys.parse('dim=1cm') -- { dim = 1234567 }
```

3.3.1 Option “assignment_operator”

The option `assignment_operator` configures the delimiter that assigns a value to a key. The default value of this option is “`=`”.

The code example below demonstrates all six delimiter related options.

```

local result = luakeys.parse(
  'level1: ( key1: value1; key2: "A string;" )', {
    assignment_operator = ':',
    group_begin = '(',
    group_end = ')',
    list_separator = ';',
    quotation_begin = "'",
    quotation_end = "'",
  })
luakeys.debug(result) -- { level1 = { key1 = 'value1', key2 = 'A string;' } }

```

Delimiter options	Section
assignment_operator	3.3.1
group_begin	3.3.8
group_end	3.3.9
list_separator	3.3.11
quotation_begin	3.3.14
quotation_end	3.3.15

3.3.2 Option “convert_dimensions”

If you set the option `convert_dimensions` to `true`, luakeys detects the TeX dimensions and converts them into scaled points using the function `tex.sp(dim)`.

```
local result = luakeys.parse('dim=1cm', {
    convert_dimensions = true,
})
-- result = { dim = 1864679 }
```

By default the dimensions are not converted into scaled points.

```
local result = luakeys.parse('dim=1cm', {
    convert_dimensions = false,
})
-- or
result = luakeys.parse('dim=1cm')
-- result = { dim = '1cm' }
```

If you want to convert a scaled points number into a dimension string you can use the module `lualibs-util-dim.lua`.

```
require('lualibs')
tex.print(number.todimen(tex.sp('1cm'), 'cm', '%0.0F%s'))
```

The default value of the option “convert_dimensions” is: `false`.

3.3.3 Option “debug”

If the option `debug` is set to `true`, the result table is printed to the console.

```
\documentclass{article}
\usepackage{luakeys}
\begin{document}
\directlua{
    luakeys.parse('one,two,three', { debug = true })
}
Lorem ipsum
\end{document}
```

```
This is LuaHBTex, Version 1.15.0 (TeX Live 2022)
...
(./debug.aux) (/usr/local/texlive/texmf-dist/tex/latex/base/ts1cmr.fd)
{
    ['three'] = true,
    ['two'] = true,
    ['one'] = true,
```

```

}
[1{/usr/
local/texlive/2022/texmf-var/fonts/map/pdftex/updmap/pdftex.map}] (./debug.aux)
)
...
Transcript written on debug.log.

```

The default value of the option “`debug`” is: `false`.

3.3.4 Option “`default`”

The option `default` can be used to specify which value naked keys (keys without a value) get. This option has no influence on keys with values.

```

local result = luakeys.parse('naked', { default = 1 })
luakeys.debug(result) -- { naked = 1 }

```

By default, naked keys get the value `true`.

```

local result2 = luakeys.parse('naked')
luakeys.debug(result2) -- { naked = true }

```

The default value of the option “`default`” is: `true`.

3.3.5 Option “`defaults`”

The option “`defaults`” can be used to specify not only one default value, but a whole table of default values. The result table is merged into the defaults table. Values in the defaults table are overwritten by values in the result table.

```

local result = luakeys.parse('key1=new', {
    defaults = { key1 = 'default', key2 = 'default' },
})
luakeys.debug(result) -- { key1 = 'new', key2 = 'default' }

```

The default value of the option “`defaults`” is: `false`.

3.3.6 Option “`defs`”

For more informations on how keys are defined, see section 3.4. If you use the `defs` option, you don’t need to call the `define` function. Instead of ...

```

local parse = luakeys.define({ one = { default = 1 }, two = { default = 2 } })
local result = parse('one,two') -- { one = 1, two = 2 }

```

we can write ...

```

local result2 = luakeys.parse('one,two', {
    defs = { one = { default = 1 }, two = { default = 2 } },
}) -- { one = 1, two = 2 }

```

The default value of the option “`defs`” is: `false`.

3.3.7 Option “format_keys”

With the help of the option `format_keys` the keys can be formatted. The values of this option must be specified in a table.

`lower` To convert all keys to *lowercase*, specify `lower` in the options table.

```
local result = luakeys.parse('KEY=value', { format_keys = { 'lower' } })
luakeys.debug(result) -- { key = 'value' }
```

`snake` To make all keys *snake case* (The words are separated by underscores), specify `snake` in the options table.

```
local result2 = luakeys.parse('snake_case=value', { format_keys = {
    -- 'snake' } })
luakeys.debug(result2) -- { snake_case = 'value' }
```

`upper` To convert all keys to *uppercase*, specify `upper` in the options table.

```
local result3 = luakeys.parse('key=value', { format_keys = { 'upper' }
    -- })
luakeys.debug(result3) -- { KEY = 'value' }
```

You can also combine several types of formatting.

```
local result4 = luakeys.parse('Snake Case=value', { format_keys = { 'lower',
    -- 'snake' } })
luakeys.debug(result4) -- { snake_case = 'value' }
```

The default value of the option “`format_keys`” is: `false`.

3.3.8 Option “group_begin”

The option `group_begin` configures the delimiter that marks the beginning of a group. The default value of this option is "`{`". A code example can be found in section [3.3.1](#).

3.3.9 Option “group_end”

The option `group_end` configures the delimiter that marks the end of a group. The default value of this option is "`}`". A code example can be found in section [3.3.1](#).

3.3.10 Option “hooks”

The following hooks or callback functions allow to intervene in the processing of the `parse` function. The functions are listed in processing order. `*_before_opts` means that the hooks are executed after the LPEG syntax analysis and before the options are applied. The `*_before_defs` hooks are executed before applying the key value definitions.

1. `kv_string` = function(`kv_string`): `kv_string`
2. `keys_before_opts` = function(`key, value, depth, current, result`): `key, value`

```

3. result_before_opts    = function(result): void
4. keys_before_def      = function(key, value, depth, current, result): key, value
5. result_before_def    = function(result): void
6. (process) (has to be defined using defs, see 3.5.12)
7. keys     = function(key, value, depth, current, result): key, value
8. result    = function(result): void

```

kv_string The `kv_string` hook is called as the first of the hook functions before the LPEG syntax parser is executed.

```

local result = luakeys.parse('key=unknown', {
  hooks = {
    kv_string = function(kv_string)
      return kv_string:gsub('unknown', 'value')
    end,
  },
})
luakeys.debug(result) -- { key = 'value' }

```

keys_* The hooks `keys_*` are called recursively on each key in the current result table. The hook function must return two values: `key, value`. The following example returns `key` and `value` unchanged, so the result table is not changed.

```

local result = luakeys.parse('l1={l2=1}', {
  hooks = {
    keys = function(key, value)
      return key, value
    end,
  },
})
luakeys.debug(result) -- { l1 = { l2 = 1 } }

```

The next example demonstrates the third parameter `depth` of the hook function.

```

local result = luakeys.parse('x,d1={x,d2={x}}', {
  naked_as_value = true,
  unpack = false,
  hooks = {
    keys = function(key, value, depth)
      if value == 'x' then
        return key, depth
      end
      return key, value
    end,
  },
})
luakeys.debug(result) -- { 1, d1 = { 2, d2 = { 3 } } }

```

result_* The hooks `result_*` are called once with the current result table as a parameter.

3.3.11 Option “list_separator”

The option `list_separator` configures the delimiter that separates list items from each other. The default value of this option is `" , "`. A code example can be found in section 3.3.1.

3.3.12 Option “naked_as_value”

With the help of the option `naked_as_value`, naked keys are not given a default value, but are stored as values in a Lua table.

```
local result = luakeys.parse('one,two,three')
luakeys.debug(result) -- { one = true, two = true, three = true }
```

If we set the option `naked_as_value` to `true`:

```
local result2 = luakeys.parse('one,two,three', { naked_as_value = true })
luakeys.debug(result2)
-- { [1] = 'one', [2] = 'two', [3] = 'three' }
-- { 'one', 'two', 'three' }
```

The default value of the option “`naked_as_value`” is: `false`.

3.3.13 Option “no_error”

By default the parse function throws an error if there are unknown keys. This can be prevented with the help of the `no_error` option.

```
luakeys.parse('unknown', { defs = { 'key' } })
-- Error message: Unknown keys: unknown,
```

If we set the option `no_error` to `true`:

```
luakeys.parse('unknown', { defs = { 'key' }, no_error = true })
-- No error message
```

The default value of the option “`no_error`” is: `false`.

3.3.14 Option “quotation_begin”

The option `quotation_begin` configures the delimiter that marks the beginning of a string. The default value of this option is `'''` (double quotes). A code example can be found in section 3.3.1.

3.3.15 Option “quotation_end”

The option `quotation_end` configures the delimiter that marks the end of a string. The default value of this option is `'''` (double quotes). A code example can be found in section 3.3.1.

3.3.16 Option “unpack”

With the help of the option `unpack`, all tables that consist of only a single naked key or a single standalone value are unpacked.

```
local result = luakeys.parse('key={string}', { unpack = true })
luakeys.debug(result) -- { key = 'string' }
```

```
local result2 = luakeys.parse('key={string}', { unpack = false })
luakeys.debug(result2) -- { key = { string = true } }
```

The default value of the option “unpack” is: `true`.

3.4 Function “`define(defs, opts): parse`”

The `define` function returns a `parse` function (see 3.2). The name of a key can be specified in three ways:

1. as a string.
2. as a key in a Lua table. The definition of the corresponding key-value pair is then stored under this key.
3. by the “name” attribute.

```
-- standalone string values
local defs = { 'key' }

-- keys in a Lua table
local defs = { key = {} }

-- by the "name" attribute
local defs = { { name = 'key' } }

local parse = luakeys.define(defs)
local result, unknown = parse('key=value,unknown=unknown', { no_error = true
→ })
luakeys.debug(result) -- { key = 'value' }
luakeys.debug(unknown) -- { unknown = 'unknown' }
```

For nested definitions, only the last two ways of specifying the key names can be used.

```
local parse2 = luakeys.define({
    level1 = {
        sub_keys = { level2 = { sub_keys = { key = { } } } },
    },
}, { no_error = true })
local result2, unknown2 =
→ parse2('level1={level2=[key=value,unknown=unknown]}')
luakeys.debug(result2) -- { level1 = { level2 = { key = 'value' } } }
luakeys.debug(unknown2) -- { level1 = { level2 = { unknown = 'unknown' } } }
```

3.5 Attributes to define a key-value pair

The definition of a key-value pair can be made with the help of various attributes. The name “*attribute*” for an option, a key, a property ... (to list just a few naming possibilities) to define keys, was deliberately chosen to distinguish them from the options of the `parse` function. These attributes are allowed: alias, always_present, choices, data_type, default, exclusive_group, l3_t1_set, macro, match, name, opposite_keys, pick, process, required, sub_keys. The code example below lists all the attributes that can be used to define key-value pairs.

```

local defs = {
    key = {
        -- Allow different key names.
        -- or a single string: alias = 'k'
        alias = { 'k', 'ke' },

        -- The key is always included in the result. If no default value is
        -- defined, true is taken as the value.
        always_present = false,

        -- Only values listed in the array table are allowed.
        choices = { 'one', 'two', 'three' },

        -- Possible data types: boolean, dimension, integer, number, string
        data_type = 'string',

        default = true,

        -- The key belongs to a mutually exclusive group of keys.
        exclusive_group = 'name',

        -- > \MacroName
        macro = 'MacroName', -- > \MacroName

        -- See http://www.lua.org/manual/5.3/manual.html#6.4.1
        match = '^%d%d%d-%d%d-%d%d$',

        -- The name of the key, can be omitted
        name = 'key',
        opposite_keys = { [true] = 'show', [false] = 'hide' },

        -- Pick a value
        -- boolean
        pick = false,

        process = function(value, input, result, unknown)
            return value
        end,
        required = true,
        sub_keys = { key_level_2 = { } },
    }
}

```

3.5.1 Attribute “alias”

With the help of the `alias` attribute, other key names can be used. The value is always stored under the original key name. A single alias name can be specified by a string ...

```

-- a single alias
local parse = luakeys.define({ key = { alias = 'k' } })
local result = parse('k=value')
luakeys.debug(result) -- { key = 'value' }

```

multiple aliases by a list of strings.

```

-- multiple aliases
local parse = luakeys.define({ key = { alias = { 'k', 'ke' } } })
local result = parse('ke=value')

```

```
luakeys.debug(result) -- { key = 'value' }
```

3.5.2 Attribute “always_present”

The `default` attribute is used only for naked keys.

```
local parse = luakeys.define({ key = { default = 1 } })
local result = parse('') -- { }
```

If the attribute `always_present` is set to true, the key is always included in the result. If no default value is defined, true is taken as the value.

```
local parse = luakeys.define({ key = { default = 1, always_present = true } })
local result = parse('') -- { key = 1 }
```

3.5.3 Attribute “choices”

Some key values should be selected from a restricted set of choices. These can be handled by passing an array table containing choices.

```
local parse = luakeys.define({ key = { choices = { 'one', 'two', 'three' } } })
local result = parse('key=one') -- { key = 'one' }
```

When the key-value pair is parsed, values will be checked, and an error message will be displayed if the value was not one of the acceptable choices:

```
parse('key=unknown')
-- error message:
--- 'The value "unknown" does not exist in the choices: one, two, three!'
```

3.5.4 Attribute “data_type”

The `data_type` attribute allows type-checking and type conversions to be performed. The following data types are supported: `'boolean'`, `'dimension'`, `'integer'`, `'number'`, `'string'`. A type conversion can fail with the three data types `'dimension'`, `'integer'`, `'number'`. Then an error message is displayed.

```
local function assert_type(data_type, input_value, expected_value)
    assert.are.same({ key = expected_value },
        luakeys.parse('key=' .. tostring(input_value),
            { defs = { key = { data_type = data_type } } }))
end
```

```
assert_type('boolean', 'true', true)
assert_type('dimension', '1cm', '1cm')
assert_type('integer', '1.23', 1)
assert_type('number', '1.23', 1.23)
assert_type('string', '1.23', '1.23')
```

3.5.5 Attribute “default”

Use the `default` attribute to provide a default value for each naked key individually. With the global `default` attribute (3.3.4) a default value can be specified for all naked keys.

```
local parse = luakeys.define({
    one = {},
    two = { default = 2 },
    three = { default = 3 },
}, { default = 1, defaults = { four = 4 } })
local result = parse('one,two,three') -- { one = 1, two = 2, three = 3, four =
→ 4 }
```

3.5.6 Attribute “exclusive_group”

All keys belonging to the same exclusive group must not be specified together. Only one key from this group is allowed. Any value can be used as a name for this exclusive group.

```
local parse = luakeys.define({
    key1 = { exclusive_group = 'group' },
    key2 = { exclusive_group = 'group' },
})
local result1 = parse('key1') -- { key1 = true }
local result2 = parse('key2') -- { key2 = true }
```

If more than one key of the group is specified, an error message is thrown.

```
parse('key1,key2') -- throws error message:
-- 'The key "key2" belongs to a mutually exclusive group "group"
-- and the key "key1" is already present!'
```

3.5.7 Attribute “opposite_keys”

The `opposite_keys` attribute allows to convert opposite (naked) keys into a boolean value and store this boolean under a target key. Lua allows boolean values to be used as keys in tables. However, the boolean values must be written in square brackets, e. g. `opposite_keys = { [true] = 'show', [false] = 'hide' }`. Examples of opposing keys are: `show` and `hide`, `dark` and `light`, `question` and `solution`. The example below uses the `show` and `hide` keys as the opposite key pair. If the key `show` is parsed by the `parse` function, then the target key `visibility` receives the value `true`.

```
local parse = luakeys.define({
    visibility = { opposite_keys = { [true] = 'show', [false] = 'hide' } },
})
local result = parse('show') -- { visibility = true }
```

If the key `hide` is parsed, then `false`.

```
local result = parse('hide') -- { visibility = false }
```

3.5.8 Attribute “macro”

The attribute `macro` stores the value in a TeX macro.

```
local parse = luakeys.define({
    key = {
        macro = 'MyMacro'
    }
})
parse('key=value')
```

```
\MyMacro % expands to "value"
```

3.5.9 Attribute “match”

The value of the key is first passed to the Lua function `string.match(value, match)` (<http://www.lua.org/manual/5.3/manual.html#pdf-string.match>) before being assigned to the key. You can therefore configure the `match` attribute with a pattern matching string used in Lua. Take a look at the Lua manual on how to write patterns (<http://www.lua.org/manual/5.3/manual.html#6.4.1>).

```
local parse = luakeys.define({
    birthday = { match = '^%d%d%d%-%d%d%-%d%d$' },
})
local result = parse('birthday=1978-12-03') -- { birthday = '1978-12-03' }
```

If the pattern cannot be found in the value, an error message is issued.

```
parse('birthday=1978-12-XX')
-- throws error message:
-- 'The value "1978-12-XX" of the key "birthday"
-- does not match "%d%d%d%-%d%d%-%d%d$"!'
```

The key receives the result of the function `string.match(value, match)`, which means that the original value may not be stored completely in the key. In the next example, the entire input value is accepted:

```
local parse = luakeys.define({ year = { match = '%d%d%d%d' } })
local result = parse('year=1978') -- { year = '1978' }
```

The prefix “waste” and the suffix “rubbisch” of the string are discarded.

```
local result2 = parse('year=waste 1978 rubbisch') -- { year = '1978' }
```

Since function `string.match(value, match)` always returns a string, the value of the key is also always a string.

3.5.10 Attribute “name”

The `name` attribute allows an alternative notation of key names. Instead of ...

```
local parse1 = luakeys.define({
    one = { default = 1 },
    two = { default = 2 },
```

```

})
local result1 = parse1('one,two') -- { one = 1, two = 2 }

```

... we can write:

```

local parse = luakeys.define({
  { name = 'one', default = 1 },
  { name = 'two', default = 2 },
})
local result = parse('one,two') -- { one = 1, two = 2 }

```

3.5.11 Attribute “pick”

The attribute `pick` searches for a value not assigned to a key. The first value found, i.e. the one further to the left, is assigned to a key.

```

local parse = luakeys.define({ font_size = { pick = 'dimension' } })
local result = parse('12pt,13pt', { no_error = true })
luakeys.debug(result) -- { font_size = '12pt' }

```

Only the current result table is searched, not other levels in the recursive data structure.

```

local parse = luakeys.define({
  level1 = {
    sub_keys = { level2 = { default = 2 }, key = { pick = 'boolean' } },
  },
}, { no_error = true })
local result, unknown = parse('true,level1={level2,true}')
luakeys.debug(result) -- { level1 = { key = true, level2 = 2 } }
luakeys.debug(unknown) -- { true }

```

The search for values is activated when the attribute `pick` is set to a data type. These data types can be used to search for values: dimension, number, boolean, any, string, integer. Use the data type “any” to accept any value. If a value is already assigned to a key when it is entered, then no further search for values is performed.

```

local parse = luakeys.define({ font_size = { pick = 'dimension' } })
local result, unknown =
  parse('font_size=11pt,12pt', { no_error = true })
luakeys.debug(result) -- { font_size = '11pt' }
luakeys.debug(unknown) -- { '12pt' }

```

The `pick` attribute also accepts multiple data types specified in a table.

```

local parse = luakeys.define({
  key = { pick = { 'number', 'dimension' } },
})
local result = parse('string,12pt,42', { no_error = true })
luakeys.debug(result) -- { key = 42 }
local result2 = parse('string,12pt', { no_error = true })
luakeys.debug(result2) -- { key = '12pt' }

```

3.5.12 Attribute “process”

The `process` attribute can be used to define a function whose return value is passed to the key. Four parameters are passed when the function is called:

1. `value`: The current value associated with the key.
2. `input`: The result table cloned before the time the definitions started to be applied.
3. `result`: The table in which the final result will be saved.
4. `unknown`: The table in which the unknown key-value pairs are stored.

The following example demonstrates the `value` parameter:

```
local parse = luakeys.define({  
    key = {  
        process = function(value, input, result, unknown)  
            if type(value) == 'number' then  
                return value + 1  
            end  
            return value  
        end,  
    },  
})  
local result = parse('key=1') -- { key = 2 }
```

The following example demonstrates the `input` parameter:

```
local parse = luakeys.define({  
    'one',  
    'two',  
    key = {  
        process = function(value, input, result, unknown)  
            value = input.one + input.two  
            result.one = nil  
            result.two = nil  
            return value  
        end,  
    },  
})  
local result = parse('key,one=1,two=2') -- { key = 3 }
```

The following example demonstrates the `result` parameter:

```
local parse = luakeys.define({  
    key = {  
        process = function(value, input, result, unknown)  
            result.additional_key = true  
            return value  
        end,  
    },  
})  
local result = parse('key=1') -- { key = 1, additional_key = true }
```

The following example demonstrates the `unknown` parameter:

```

local parse = luakeys.define({
    key = {
        process = function(value, input, result, unknown)
            unknown.unknown_key = true
            return value
        end,
    },
})

```

```
parse('key=1') -- throws error message: 'Unknown keys: unknown_key=true,'
```

3.5.13 Attribute “required”

The `required` attribute can be used to enforce that a specific key must be specified. In the example below, the key `important` is defined as mandatory.

```

local parse = luakeys.define({ important = { required = true } })
local result = parse('important') -- { important = true }

```

If the key `important` is missing in the input, an error message occurs.

```
parse('unimportant')
-- throws error message: 'Missing required key "important"!'
```

A recursive example:

```

local parse2 = luakeys.define({
    important1 = {
        required = true,
        sub_keys = { important2 = { required = true } },
    },
})

```

The `important2` key on level 2 is missing.

```
parse2('important1={unimportant}')
-- throws error message: 'Missing required key "important2"!'
```

The `important1` key at the lowest key level is missing.

```
parse2('unimportant')
-- throws error message: 'Missing required key "important1"!'
```

3.5.14 Attribute “sub_keys”

The `sub_keys` attribute can be used to build nested key-value pair definitions.

```

local result, unknown = luakeys.parse('level1={level2,unknown}', {
    no_error = true,
    defs = {
        level1 = {
            sub_keys = {
                level2 = { default = 42 }
            }
        },
    },
})

```

```

luakeys.debug(result) -- { level1 = { level2 = 42 } }
luakeys.debug(unknown) -- { level1 = { 'unknown' } }

```

3.6 Function “`render(result): string`”

The function `render(result)` reverses the function `parse(kv_string)`. It takes a Lua table and converts this table into a key-value string. The resulting string usually has a different order as the input table.

```

local result = luakeys.parse('one=1,two=2,three=3')
local kv_string = luakeys.render(result)
--- one=1,two=2,tree=3,
--- or:
--- two=2,one=1,tree=3,
--- or:
--- ...

```

In Lua only tables with 1-based consecutive integer keys (a.k.a. array tables) can be parsed in order.

```

local result2 = luakeys.parse('one,two,three', { naked_as_value = true })
local kv_string2 = luakeys.render(result2) --- one,two,three, (always)

```

3.7 Function “`debug(result): void`”

The function `debug(result)` pretty prints a Lua table to standard output (stdout). It is a utility function that can be used to debug and inspect the resulting Lua table of the function `parse`. You have to compile your T_EX document in a console to see the terminal output.

```

local result = luakeys.parse('level1={level2={key=value}}')
luakeys.debug(result)

```

The output should look like this:

```

{
  ['level1'] = {
    ['level2'] = {
      ['key'] = 'value',
    },
  }
}

```

3.8 Function “`save(identifier, result): void`”

The function `save(identifier, result)` saves a result (a table from a previous run of `parse`) under an identifier. Therefore, it is not necessary to pollute the global namespace to store results for the later usage.

3.9 Function “`get(identifier): result`”

The function `get(identifier)` retrieves a saved result from the result store.

3.10 Table “is”

In the table `is` some functions are summarized, which check whether an input corresponds to a certain data type. All functions accept not only the corresponding Lua data types, but also input as strings. For example, the string `'true'` is recognized by the `is.boolean()` function as a boolean value.

3.10.1 Function “`is.boolean(value): boolean`”

```
-- true
equal(luakeys.is.boolean('true'), true) -- input: string!
equal(luakeys.is.boolean('True'), true) -- input: string!
equal(luakeys.is.boolean('TRUE'), true) -- input: string!
equal(luakeys.is.boolean('false'), true) -- input: string!
equal(luakeys.is.boolean('False'), true) -- input: string!
equal(luakeys.is.boolean('FALSE'), true) -- input: string!
equal(luakeys.is.boolean(true), true)
equal(luakeys.is.boolean(false), true)
-- false
equal(luakeys.is.boolean('xxx'), false)
equal(luakeys.is.boolean('trueX'), false)
equal(luakeys.is.boolean('1'), false)
equal(luakeys.is.boolean('0'), false)
equal(luakeys.is.boolean(1), false)
equal(luakeys.is.boolean(0), false)
equal(luakeys.is.boolean(nil), false)
end)
```

3.10.2 Function “`is.dimension(value): boolean`”

```
-- true
equal(luakeys.is.dimension('1 cm'), true)
equal(luakeys.is.dimension('- 1 mm'), true)
equal(luakeys.is.dimension('-1.1pt'), true)
-- false
equal(luakeys.is.dimension('1cmX'), false)
equal(luakeys.is.dimension('X1cm'), false)
equal(luakeys.is.dimension(1), false)
equal(luakeys.is.dimension('1'), false)
equal(luakeys.is.dimension('xxx'), false)
equal(luakeys.is.dimension(nil), false)
```

3.10.3 Function “`is.integer(value): boolean`”

```
-- true
equal(luakeys.is.integer('42'), true) -- input: string!
equal(luakeys.is.integer(1), true)
-- false
equal(luakeys.is.integer('1.1'), false)
equal(luakeys.is.integer('xxx'), false)
```

3.10.4 Function “`is.number(value): boolean`”

```
-- true
equal(luakeys.is.number('1'), true) -- input: string!
equal(luakeys.is.number('1.1'), true) -- input: string!
```

```

equal(luakeys.is.number(1), true)
equal(luakeys.is.number(1.1), true)
-- false
equal(luakeys.is.number('xxx'), false)
equal(luakeys.is.number('1cm'), false)

```

3.10.5 Function “is.string(value): boolean”

```

-- true
equal(luakeys.is.string('string'), true)
equal(luakeys.is.string(''), true)
-- false
equal(luakeys.is.string(true), false)
equal(luakeys.is.string(1), false)
equal(luakeys.is.string(nil), false)

```

3.10.6 Function “is.any(value): boolean”

The function `is.any(value)` always returns `true` and therefore accepts any data type.

3.11 Table “utils”

3.11.1 Function “utils.scan_oarg(initial_delimiter?, end_delimiter?): string”

Plain T_EX does not know optional arguments (oarg). The function

`utils.scan_oarg(initial_delimiter?, end_delimiter?): string` allows to search for optional arguments not only in L^AT_EX but also in Plain T_EX. The function uses the token library built into LuaT_EX. The two parameters `initial_delimiter` and `end_delimiter` can be omitted. Then square brackets are assumed to be delimiters. For example, this Lua code `utils.scan_oarg('(', ')')` searches for an optional argument in round brackets. The function returns the string between the delimiters or `nil` if no delimiters could be found. The delimiters themselves are not included in the result. After the `\directlua {}`, the macro using `utils.scan_oarg` must not expand to any characters.

```

\input luakeys.tex

\def\mycmd{\directlua{
    local oarg = luakeys.utils.scan_oarg('[', ']')
    if oarg then
        local keys = luakeys.parse(oarg)
        for key, value in pairs(keys) do
            tex.print('oarg: key: "' .. key .. '" value: "' .. value .. '"')
        end
    end
    local marg = token.scan_argument()
    tex.print('marg: "' .. marg .. '"')
}%
} % <- important

\mycmd[key=value]{marg}
% oarg: key: "key" value: "value"; marg: "marg"

\mycmd{marg without oarg}
% marg: "marg without oarg"

```

```

end
\bye

```

3.12 Table “version”

The luakeys project uses semantic versioning. The three version numbers of the semantic versioning scheme are stored in a table as integers in the order MAJOR, MINOR, PATCH. This table can be used to check whether the correct version is installed.

```

local v = luakeys.version
local version_string = v[1] .. '.' .. v[2] .. '.' .. v[3]
print(version_string) -- 0.7.0

if v[1] >= 1 and v[2] > 2 then
    print('You are using the right version.')
end

```

4 Syntax of the recognized key-value format

4.1 An attempt to put the syntax into words

A key-value pair is defined by an equal sign (`key=value`). Several key-value pairs or keys without values (naked keys) are lined up with commas (`key=value,naked`) and build a key-value list. Curly brackets can be used to create a recursive data structure of nested key-value lists (`level1={level2={key=value,naked}}`).

4.2 An (incomplete) attempt to put the syntax into the Extended Backus-Naur Form

```

⟨list⟩ ::= { ⟨list-item⟩ }

⟨list-container⟩ ::= '{' ⟨list⟩ '}' 

⟨list-item⟩ ::= ( ⟨list-container⟩ | ⟨key-value-pair⟩ | ⟨value⟩ ) [ ',' ] 

⟨key-value-pair⟩ ::= ⟨value⟩ '=' ( ⟨list-container⟩ | ⟨value⟩ ) 

⟨value⟩ ::= ⟨boolean⟩
| ⟨dimension⟩
| ⟨number⟩
| ⟨string-quoted⟩
| ⟨string-unquoted⟩

⟨dimension⟩ ::= ⟨number⟩ ⟨unit⟩

⟨number⟩ ::= ⟨sign⟩ ( ⟨integer⟩ [ ⟨fractional⟩ ] | ⟨fractional⟩ )

⟨fractional⟩ ::= '.' ⟨integer⟩

⟨sign⟩ ::= '-' | '+'

```

```

⟨integer⟩ ::= ⟨digit⟩ { ⟨digit⟩ }

⟨digit⟩ ::= ‘0’ | ‘1’ | ‘2’ | ‘3’ | ‘4’ | ‘5’ | ‘6’ | ‘7’ | ‘8’ | ‘9’

⟨unit⟩ ::= ‘bp’ | ‘BP’
| ‘cc’ | ‘CC’
| ‘cm’ | ‘CM’
| ‘dd’ | ‘DD’
| ‘em’ | ‘EM’
| ‘ex’ | ‘EX’
| ‘in’ | ‘IN’
| ‘mm’ | ‘MM’
| ‘mu’ | ‘MU’
| ‘nc’ | ‘NC’
| ‘nd’ | ‘ND’
| ‘pc’ | ‘PC’
| ‘pt’ | ‘PT’
| ‘px’ | ‘PX’
| ‘sp’ | ‘SP’

⟨boolean⟩ ::= ⟨boolean-true⟩ | ⟨boolean-false⟩

⟨boolean-true⟩ ::= ‘true’ | ‘TRUE’ | ‘True’

⟨boolean-false⟩ ::= ‘false’ | ‘FALSE’ | ‘False’

```

... to be continued

4.3 Recognized data types

4.3.1 boolean

The strings `true`, `TRUE` and `True` are converted into Lua’s boolean type `true`, the strings `false`, `FALSE` and `False` into `false`.

<pre>\luakeysdebug{ lower case true = true, upper case true = TRUE, title case true = True, lower case false = false, upper case false = FALSE, title case false = False, }</pre>	<pre>{ ['lower case true'] = true, ['upper case true'] = true, ['title case true'] = true, ['lower case false'] = false, ['upper case false'] = false ['title case false'] = false,</pre>
---	---

4.3.2 number

<pre>\luakeysdebug{ num0 = 042, num1 = 42, num2 = -42, num3 = 4.2, num4 = 0.42, num5 = .42, num6 = 0 . 42, }</pre>
--

```
{  
  ['num0'] = 42,  
  ['num1'] = 42,  
  ['num2'] = -42,
```

```

['num3'] = 4.2,
['num4'] = 0.42,
['num5'] = 0.42,
['num6'] = '0 . 42', -- string
}

```

4.3.3 dimension

`luakeys` tries to recognize all units used in the `TeX` world. According to the `LuaTeX` source code ([source/texk/web2c/luatexdir/luatexlib.c](#)) and the dimension module of the `lualibs` library ([lualibs-util-dim.lua](#)), all units should be recognized.

Description	
bp	big point
cc	cicero
cm	centimeter
dd	didot
em	horizontal measure of M
ex	vertical measure of x
in	inch
mm	millimeter
mu	math unit
nc	new cicero
nd	new didot
pc	pica
pt	point
px	x height current font
sp	scaledpoint

```

\luakeydebug[convert_dimensions=true]{
    bp = 1bp,
    cc = 1cc,
    cm = 1cm,
    dd = 1dd,
    em = 1em,
    ex = 1ex,
    in = 1in,
    mm = 1mm,
    mu = 1mu,
    nc = 1nc,
    nd = 1nd,
    pc = 1pc,
    pt = 1pt,
    px = 1px,
    sp = 1sp,
}
{ ['bp'] = 65781,
  ['cc'] = 841489,
  ['cm'] = 1864679,
  ['dd'] = 70124,
  ['em'] = 655360,
  ['ex'] = 282460,
  ['in'] = 4736286,
  ['mm'] = 186467,
  ['mu'] = 65536,
  ['nc'] = 839105,
  ['nd'] = 69925,
  ['pc'] = 786432,
  ['pt'] = 65536,
  ['px'] = 65781,
  ['sp'] = 1,
}

```

The next example illustrates the different notations of the dimensions.

```

\luakeydebug[convert_dimensions=true]{
    upper = 1CM,
    lower = 1cm,
    space = 1 cm,
    plus = + 1cm,
    minus = -1cm,
    nodim = 1 c m,
}

```

```

{ ['upper'] = 1864679,
  ['lower'] = 1864679,
  ['space'] = 1864679,
  ['plus'] = 1864679,
  ['minus'] = -1864679,
  ['nodim'] = '1 c m', -- string
}

```

4.3.4 string

There are two ways to specify strings: With or without double quotes. If the text have to contain commas, curly braces or equal signs, then double quotes must be used.

```

local kv_string = [[
    without double quotes = no commas and equal signs are allowed,
    with double quotes = ", and = are allowed",
    escape quotes = "a quote \" sign",
    curly braces = "curly { } braces are allowed",
]]
local result = luakeys.parse(kv_string)
luakeys.debug(result)

```

```
-- {
--   ['without double quotes'] = 'no commas and equal signs are allowed',
--   ['with double quotes'] = ', and = are allowed',
--   ['escape quotes'] = 'a quote \" sign',
--   ['curly braces'] = 'curly { } braces are allowed',
-- }
```

4.3.5 Naked keys

Naked keys are keys without a value. Using the option `naked_as_value` they can be converted into values and stored into an array. In Lua an array is a table with numeric indexes (The first index is 1).

```
\luakeysdebug[naked_as_value=true]{one,two,three}
% {
%   [1] = 'one',
%   [2] = 'two',
%   [3] = 'three',
% }
% =
% { 'one', 'two', 'three' }
```

All recognized data types can be used as standalone values.

```
\luakeysdebug[naked_as_value=true]{one,2,3cm}
% {
%   [1] = 'one',
%   [2] = 2,
%   [3] = '3cm',
% }
```

5 Examples

5.1 Extend and modify keys of existing macros

Extend the `includegraphics` macro with a new key named `caption` and change the accepted values of the `width` key. A number between 0 and 1 is allowed and converted into `width=0.5\linewidth`

```
local luakeys = require('luakeys')

local parse = luakeys.define({
    caption = { alias = 'title' },
    width = {
        process = function(value)
            if type(value) == 'number' and value >= 0 and value <= 1 then
                return tostring(value) .. '\\linewidth'
            end
            return value
        end,
    },
})

local function print_image_macro(image_path, kv_string)
    local caption = ''
    local options = ''
    local keys, unknown = parse(kv_string)
    if keys['caption'] ~= nil then
        caption = '\\ImageCaption{' .. keys['caption'] .. '}'
    end
    if keys['width'] ~= nil then
        unknown['width'] = keys['width']
    end
    options = luakeys.render(unknown)

    tex.print('\\includegraphics[' .. options .. ']{' .. image_path .. '}'
              .. caption)
end

return print_image_macro
```

```
\documentclass{article}
\usepackage{graphicx}
\begin{document}
\newcommand{\ImageCaption}[1]{%
    \par\textrit{#1}%
}

\newcommand{\myincludegraphics}[2][]{%
    \directlua{
        print_image_macro = require('extend-keys.lua')
        print_image_macro(#2, '#1')
    }
}

\myincludegraphics{test.png}
\myincludegraphics[width=0.5]{test.png}
\myincludegraphics[caption=A caption]{test.png}
```

```
\end{document}
```

5.2 Process document class options

The options of a L^AT_EX document class can be accessed via the `\@classoptionslist` macro. The string of the macro `\@classoptionslist` is already expanded and normalized. In addition to spaces, the curly brackets are also removed. It is therefore not possible to process nested hierarchical key-value pairs via the option.

```
\NeedsTeXFormat{LaTeX2e}
\ProvidesClass{test-class}[2022/05/26 Test class to access the class options]
\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
\ProcessOptions\relax
\directlua{
  luakeys = require('luakeys')
  local kv = luakeys.parse('\@classoptionslist', {
    convert_dimensions = false,
    naked_as_value = true
  })
  luakeys.debug(kv)
}
\LoadClass{article}
```

```
\documentclass[12pt,landscape]{test-class}

\begin{document}
This document uses the class "test-class".
\end{document}
```

```
{
  [1] = '12pt',
  [2] = 'landscape',
}
```

6 Debug packages

Two small debug packages are included in luakeys. One debug package can be used in L^AT_EX (luakeys-debug.sty) and one can be used in plain T_EX (luakeys-debug.tex). Both packages provide only one command: \luakeysdebug{kv-string}

```
\luakeysdebug{one,two,three}
```

Then the following output should appear in the document:

```
{
  ['two'] = true,
  ['one'] = true,
  ['three'] = true,
}
```

6.1 For plain T_EX: luakeys-debug.tex

An example of how to use the command in plain T_EX:

```
\input luakeys-debug.tex
\luakeysdebug{one,two,three}
\bye
```

6.2 For L^AT_EX: luakeys-debug.sty

An example of how to use the command in L^AT_EX:

```
\documentclass{article}
\usepackage{luakeys-debug}
\begin{document}
\luakeysdebug[
  unpack=false,
  convert dimensions=false
]{one,two,three}
\end{document}
```

7 Implementation

7.1 luakeys.lua

```

1   -- luakeys.lua
2   -- Copyright 2021-2022 Josef Friedrich
3   --
4   -- This work may be distributed and/or modified under the
5   -- conditions of the LaTeX Project Public License, either version 1.3c
6   -- of this license or (at your option) any later version.
7   -- The latest version of this license is in
8   -- http://www.latex-project.org/lppl.txt
9   -- and version 1.3c or later is part of all distributions of LaTeX
10  -- version 2008/05/04 or later.
11  --
12  -- This work has the LPPL maintenance status 'maintained'.
13  --
14  -- The Current Maintainer of this work is Josef Friedrich.
15  --
16  -- This work consists of the files luakeys.lua, luakeys.sty, luakeys.tex
17  -- luakeys-debug.sty and luakeys-debug.tex.
18  -- A key-value parser written with Lpeg.
19  --
20  -- @module luakeys
21  local lpeg = require('lpeg')
22
23  if not tex then
24      tex = {
25          -- Dummy function for the tests.
26          sp = function(input)
27              return 1234567
28          end,
29      }
30  end
31
32  if not token then
33      token = {
34          set_macro = function(csname, content, global)
35              end,
36      }
37  end
38
39  -- Merge two tables in the first specified table.
40  -- The `merge_tables` function copies all keys from the `source` table
41  -- to a target table. It returns the modified target table.
42  --
43  ---@see https://stackoverflow.com/a/1283608/10193818
44  --
45  ---@param target table
46  ---@param source table
47  --
48  ---@return table target The modified target table.
49  local function merge_tables(target, source)
50      for key, value in pairs(source) do
51          if type(value) == 'table' then
52              if type(target[key] or false) == 'table' then
53                  merge_tables(target[key] or {}, source[key] or {})
54              elseif target[key] == nil then
55                  target[key] = value
56              end
57          elseif target[key] == nil then
58              target[key] = value
59          end
60      end
61  end

```

```

59         end
60     end
61     return target
62 end
63
64 ---Clone a table.
65 ---
66 ---@see http://lua-users.org/wiki/CopyTable
67 ---
68 ---@param orig table
69 ---
70 ---@return table
71 local function clone_table(orig)
72     local orig_type = type(orig)
73     local copy
74     if orig_type == 'table' then
75         copy = {}
76         for orig_key, orig_value in next, orig, nil do
77             copy[clone_table(orig_key)] = clone_table(orig_value)
78         end
79         setmetatable(copy, clone_table(getmetatable(orig)))
80     else -- number, string, boolean, etc
81         copy = orig
82     end
83     return copy
84 end
85
86 local utils = {
87     --- Get the size of an array like table '{ 'one', 'two', 'three' }` = 3.
88     ---
89     ---@param value table # A table or any input.
90     ---
91     ---@return number # The size of the array like table. 0 if the input is no table
92     --> or the table is empty.
93     get_array_size = function(value)
94         local count = 0
95         if type(value) == 'table' then
96             for _ in ipairs(value) do
97                 count = count + 1
98             end
99         end
100        return count
101    end,
102
103    ---Get the size of a table '{ one = 'one', 'two', 'three' }` = 3.
104    ---
105    ---@param value table/any # A table or any input.
106    ---
107    ---@return number # The size of the array like table. 0 if the input is no table
108    --> or the table is empty.
109    get_table_size = function(value)
110        local count = 0
111        if type(value) == 'table' then
112            for _ in pairs(value) do
113                count = count + 1
114            end
115        end
116        return count
117    end,
118    merge_tables = merge_tables,

```

```

119     clone_table = clone_table,
120
121     remove_from_array = function(array, element)
122         for index, value in pairs(array) do
123             if element == value then
124                 array[index] = nil
125                 return value
126             end
127         end
128     end,
129
130     ---Scan for an optional argument.
131     ---
132     ---@param initial_delimiter? string # The character that marks the beginning of an
133      $\rightarrow$  optional argument (by default '[').
134     ---@param end_delimiter? string # The character that marks the end of an optional
135      $\rightarrow$  argument (by default ']').
136     ---
137     ---@return string/nil # The string that was enclosed by the delimiters. The
138      $\rightarrow$  delimiters themselves are not returned.
139     scan_oarg = function(initial_delimiter, end_delimiter)
140         if initial_delimiter == nil then
141             initial_delimiter = '['
142         end
143
144         if end_delimiter == nil then
145             end_delimiter = ']'
146         end
147
148         local function convert_token(t)
149             if t.index ~= nil then
150                 return utf8.char(t.index)
151             else
152                 return '\\ $\backslash$  .. t.csname
153             end
154         end
155
156         local function get_next_char()
157             local t = token.get_next()
158             return convert_token(t), t
159         end
160
161         local char, t = get_next_char()
162         if char == initial_delimiter then
163             local oarg = {}
164             char = get_next_char()
165             while char ~= end_delimiter do
166                 table.insert(oarg, char)
167                 char = get_next_char()
168             end
169             return table.concat(oarg, '')
170         else
171             token.put_next(t)
172             end
173         end,
174     }
175
176     local namespace = {
177         opts = {
178             assignment_operator = '=',
179             convert_dimensions = false,
180             debug = false,
181         }
182     }
183 
```

```

178     default = true,
179     defaults = false,
180     defs = false,
181     format_keys = false,
182     group_begin = '{',
183     group_end = '}',
184     hooks = {},
185     list_separator = ',',
186     naked_as_value = false,
187     no_error = false,
188     quotation_begin = '"',
189     quotation_end = "'",
190     unpack = true,
191   },
192
193   hooks = {
194     kv_string = true,
195     keys_before_opts = true,
196     result_before_opts = true,
197     keys_before_def = true,
198     result_before_def = true,
199     keys = true,
200     result = true,
201   },
202
203   attrs = {
204     alias = true,
205     always_present = true,
206     choices = true,
207     data_type = true,
208     default = true,
209     exclusive_group = true,
210     l3_tl_set = true,
211     macro = true,
212     match = true,
213     name = true,
214     opposite_keys = true,
215     pick = true,
216     process = true,
217     required = true,
218     sub_keys = true,
219   },
220 }
221
222 --- The default options.
223 local default_options = clone_table(namespace.opts)
224
225 local function throw_error(message)
226   if type(tex.error) == 'function' then
227     tex.error(message)
228   else
229     error(message)
230   end
231 end
232
233 --- Normalize the parse options.
234 ---
235 ---@param opts? table # Options in a raw format. The table may be empty or some keys
236   ↪ are not set.
237 ---
238 ---@return table
239 local function normalize_opts(opts)

```

```

239     if type(opts) ~= 'table' then
240         opts = {}
241     end
242     for key, _ in pairs(opts) do
243         if namespace.opts[key] == nil then
244             throw_error('Unknown parse option: ' .. tostring(key) .. '!')
245         end
246     end
247     local old_opts = opts
248     opts = {}
249     for name, _ in pairs(namespace.opts) do
250         if old_opts[name] ~= nil then
251             opts[name] = old_opts[name]
252         else
253             opts[name] = default_options[name]
254         end
255     end
256
257     for hook in pairs(opts.hooks) do
258         if namespace.hooks[hook] == nil then
259             throw_error('Unknown hook: ' .. tostring(hook) .. '!')
260         end
261     end
262     return opts
263 end
264
265 local l3_code_cctab = 10
266
267 --- Convert back to strings
268 -- @section
269
270 --- The function `render(tbl)` reverses the function
271 --- `parse(ku_string)`. It takes a Lua table and converts this table
272 --- into a key-value string. The resulting string usually has a
273 --- different order as the input table. In Lua only tables with
274 --- 1-based consecutive integer keys (a.k.a. array tables) can be
275 --- parsed in order.
276 ---
277 ---@param result table # A table to be converted into a key-value string.
278 ---
279 ---@return string # A key-value string that can be passed to a TeX macro.
280 local function render(result)
281     local function render_inner(result)
282         local output = {}
283         local function add(text)
284             table.insert(output, text)
285         end
286         for key, value in pairs(result) do
287             if (key and type(key) == 'string') then
288                 if (type(value) == 'table') then
289                     if (next(value)) then
290                         add(key .. '={')
291                         add(render_inner(value))
292                         add('},')
293                     else
294                         add(key .. '={},')
295                     end
296                 else
297                     add(key .. '=' .. tostring(value) .. ',')
298                 end
299             else
300                 add(tostring(value) .. ',')
301             end
302         end
303     end
304     local function render_outer(result)
305         local output = {}
306         local function add(text)
307             table.insert(output, text)
308         end
309         for i, v in ipairs(result) do
310             if (type(v) == 'table') then
311                 add(render_inner(v))
312             else
313                 add(tostring(v))
314             end
315         end
316     end
317     local function render_kv(result)
318         local output = {}
319         local function add(text)
320             table.insert(output, text)
321         end
322         for i, v in ipairs(result) do
323             if (type(v) == 'table') then
324                 add(render_inner(v))
325             else
326                 add(tostring(v))
327             end
328         end
329     end
330     if (l3_code_cctab == 10) then
331         return render_outer(result)
332     elseif (l3_code_cctab == 11) then
333         return render_kv(result)
334     else
335         return render_inner(result)
336     end
337 end

```

```

301         end
302     end
303     return table.concat(output)
304   end
305   return render_inner(result)
306 end
307
308 --- The function `stringify(tbl, for_tex)` converts a Lua table into a
309 --- printable string. Stringify a table means to convert the table into
310 --- a string. This function is used to realize the `debug` function.
311 --- `stringify(tbl, true)` (`for_tex = true`) generates a string which
312 --- can be embeded into TeX documents. The macro `\luakeysdebug{}` uses
313 --- this option. `stringify(tbl, false)` or `stringify(tbl)` generate a
314 --- string suitable for the terminal.
315 ---
316 ---@see https://stackoverflow.com/a/54593224/10193818
317 ---
318 ---@param result table # A table to stringify.
319 ---@param for_tex? boolean # Stringify the table into a text string that can be
320 --> embeded inside a TeX document via tex.print(). Curly braces and whites spaces
320 --> are escaped.
321 ---
322 ---@return string
323 local function stringify(result, for_tex)
324   local line_break, start_bracket, end_bracket, indent
325
326   if for_tex then
327     line_break = '\\par'
328     start_bracket = '$\\{$'
329     end_bracket = '$\\}$'
330     indent = ' \\ '
331   else
332     line_break = '\n'
333     start_bracket = '{'
334     end_bracket = '}'
335     indent = ' '
336   end
337
338   local function stringify_inner(input, depth)
339     local output = {}
340     depth = depth or 0
341
342     local function add(depth, text)
343       table.insert(output, string.rep(indent, depth) .. text)
344     end
345
346     local function format_key(key)
347       if (type(key) == 'number') then
348         return string.format('[%s]', key)
349       else
350         return string.format('[' .. key .. ']', key)
351       end
352     end
353
354     if type(input) ~= 'table' then
355       return tostring(input)
356     end
357
358     for key, value in pairs(input) do
359       if (key and type(key) == 'number' or type(key) == 'string') then
360         key = format_key(key)

```

```

361     if (type(value) == 'table') then
362         if (next(value)) then
363             add(depth, key .. ' = ' .. start_bracket)
364             add(0, stringify_inner(value, depth + 1))
365             add(depth, end_bracket .. ',');
366         else
367             add(depth,
368                 key .. ' = ' .. start_bracket .. end_bracket .. ',')
369         end
370     else
371         if (type(value) == 'string') then
372             value = string.format('\'%s\'', value)
373         else
374             value = tostring(value)
375         end
376
377         add(depth, key .. ' = ' .. value .. ',')
378     end
379 end
380 end
381
382     return table.concat(output, line_break)
383 end
384
385     return start_bracket .. line_break .. stringify_inner(result, 1) ..
386             line_break .. end_bracket
387 end
388
389 --- The function `debug(result)` pretty prints a Lua table to standard
390 -- output (stdout). It is a utility function that can be used to
391 -- debug and inspect the resulting Lua table of the function
392 -- `parse`. You have to compile your TeX document in a console to
393 -- see the terminal output.
394 ---
395 ---@param result table # A table to be printed to standard output for debugging
396 -- purposes.
397 local function debug(result)
398     print('\n' .. stringify(result, false))
399 end
400
401 --- Parser / Lpeg related
402 --- @section
403
404 --- Generate the PEG parser using Lpeg.
405 ---
406 --- Explanations of some LPeg notation forms:
407 ---
408 --- * `patt ^ 0` = `expression *`
409 --- * `patt ^ 1` = `expression +`
410 --- * `patt ^ -1` = `expression ?`
411 --- * `patt1 * patt2` = `expression1 expression2`: Sequence
412 --- * `patt1 + patt2` = `expression1 / expression2`: Ordered choice
413 ---
414 --- * [TUGboat article: Parsing complex data formats in LuATEX with
415 -- LPEG] (https://tug.or-g/TUGboat/tb40-2/tb125menke-Patterndf)
416 ---
417 ---@param initial_rule string # The name of the first rule of the grammar table
418 -- passed to the `lpeg.P(attern)` function (e. g. `list`, `number`).
419 ---@param opts? table # Whether the dimensions should be converted to scaled points
420 -- (by default `false`).
421 ---
422 ---@return userdata # The parser.
423

```

```

419 local function generate_parser(initial_rule, opts)
420   if type(opts) ~= 'table' then
421     opts = normalize_opts(opts)
422   end
423
424   local Variable = lpeg.V
425   local Pattern = lpeg.P
426   local Set = lpeg.S
427   local Range = lpeg.R
428   local CaptureGroup = lpeg.Cg
429   local CaptureFolding = lpeg.Cf
430   local CaptureTable = lpeg.Ct
431   local CaptureConstant = lpeg.Cc
432   local CaptureSimple = lpeg.C
433
434   -- Optional whitespace
435   local white_space = Set(' \t\n\r')
436
437   --- Match literal string surrounded by whitespace
438   local ws = function(match)
439     return white_space ^ 0 * Pattern(match) * white_space ^ 0
440   end
441
442   --- Convert a dimension to an normalized dimension string or an
443   --- integer in the scaled points format.
444   ---
445   ---@param input string
446   ---
447   ---@return integer/string # A dimension as an integer or a dimension string.
448   local capture_dimension = function(input)
449     -- Remove all whitespaces
450     input = input:gsub('%s+', '')
451     -- Convert the unit string into lowercase.
452     input = input:lower()
453     if opts.convert_dimensions then
454       return tex.sp(input)
455     else
456       return input
457     end
458   end
459
460   --- Add values to a table in two modes:
461   ---
462   --- Key-value pair:
463   ---
464   -- If `arg1` and `arg2` are not nil, then `arg1` is the key and `arg2` is the
465   -- value of a new table entry.
466   ---
467   --- Indexed value:
468   ---
469   -- If `arg2` is nil, then `arg1` is the value and is added as an indexed
470   -- (by an integer) value.
471   ---
472   ---@param result table # The result table to which an additional key-value pair or
473   -- value should be added
474   ---@param arg1 any # The key or the value.
475   ---@param arg2? any # Always the value.
476   ---
477   ---@return table # The result table to which an additional key-value pair or value
478   -- has been added.
local add_to_table = function(result, arg1, arg2)
  if arg2 == nil then

```

```

479     local index = #result + 1
480     return rawset(result, index, arg1)
481   else
482     return rawset(result, arg1, arg2)
483   end
484 end
485
486 -- LuaFormatter off
487 return Pattern{
488   [1] = initial_rule,
489
490   -- list_item*
491   list = CaptureFolding(
492     CaptureTable('') * Variable('list_item')^0,
493     add_to_table
494   ),
495
496   -- '{' list '}'
497   list_container =
498     ws(opts.group_begin) * Variable('list') * ws(opts.group_end),
499
500   -- ( list_container / key_value_pair / value ) ','?
501   list_item =
502     CaptureGroup(
503       Variable('list_container') +
504       Variable('key_value_pair') +
505       Variable('value')
506     ) * ws(opts.list_separator)^-1,
507
508   -- key '=' (list_container / value)
509   key_value_pair =
510     (Variable('key') * ws(opts.assignment_operator)) *
511     → (Variable('list_container') + Variable('value')),
512
513   -- number / string_quoted / string_unquoted
514   key =
515     Variable('number') +
516     Variable('string_quoted') +
517     Variable('string_unquoted'),
518
519   -- boolean !value / dimension !value / number !value / string_quoted !value /
520   ← string_unquoted
521   -- !value -> Not-predicate -> * -Variable('value')
522   value =
523     Variable('boolean') * -Variable('value') +
524     Variable('dimension') * -Variable('value') +
525     Variable('number') * -Variable('value') +
526     Variable('string_quoted') * -Variable('value') +
527     Variable('string_unquoted'),
528
529   -- for is.boolean()
530   boolean_only = Variable('boolean') * -1,
531
532   -- boolean_true / boolean_false
533   boolean =
534     (
535       Variable('boolean_true') * CaptureConstant(true) +
536       Variable('boolean_false') * CaptureConstant(false)
537     ),
538
539   boolean_true =
540     Pattern('true') +

```

```

539         Pattern('TRUE') +
540         Pattern('True'),
541
542     boolean_false =
543         Pattern('false') +
544         Pattern('FALSE') +
545         Pattern('False'),
546
547     -- for is.dimension()
548     dimension_only = Variable('dimension') * -1,
549
550     dimension = (
551         Variable('tex_number') * white_space^0 *
552         Variable('unit')
553     ) / capture_dimension,
554
555     -- for is.number()
556     number_only = Variable('number') * -1,
557
558     -- capture number
559     number = Variable('tex_number') / tonumber,
560
561     -- sign? white_space? (integer+ fractional? / fractional)
562     tex_number =
563         Variable('sign')^0 * white_space^0 *
564         (Variable('integer')^1 * Variable('fractional')^0) +
565         Variable('fractional'),
566
567     sign = Set('+-'),
568
569     fractional = Pattern('.') * Variable('integer')^1,
570
571     integer = Range('09')^1,
572
573     -- 'bp' / 'BP' / 'cc' / etc.
574     -- https://raw.githubusercontent.com/latex3/lualibs/master/lualibs-util-dim.lua
575     -- https://github.com/TeX-
576     --> Live/luatex/blob/51db1985f5500dafd2393aa2e403fefa57d3cb76/source/teck/web2c/luatexdir/lua/ltexlib.c
577     --> L625
578
579     unit =
580         Pattern('bp') + Pattern('BP') +
581         Pattern('cc') + Pattern('CC') +
582         Pattern('cm') + Pattern('CM') +
583         Pattern('dd') + Pattern('DD') +
584         Pattern('em') + Pattern('EM') +
585         Pattern('ex') + Pattern('EX') +
586         Pattern('in') + Pattern('IN') +
587         Pattern('mm') + Pattern('MM') +
588         Pattern('mu') + Pattern('MU') +
589         Pattern('nc') + Pattern('NC') +
590         Pattern('nd') + Pattern('ND') +
591         Pattern('pc') + Pattern('PC') +
592         Pattern('pt') + Pattern('PT') +
593         Pattern('px') + Pattern('PX') +
594         Pattern('sp') + Pattern('SP'),
595
596     -- " " ("\" / !")* "
597
598     string_quoted =
599         white_space^0 * Pattern(opts.quotation_begin) *
600         CaptureSimple((Pattern('\\\\' .. opts.quotation_end) + 1 -
601             Pattern(opts.quotation_end))^0) *
602         Pattern(opts.quotation_end) * white_space^0,

```

```

598     string_unquoted =
599         white_space^0 *
600         CaptureSimple(
601             Variable('word_unquoted')^1 *
602             (Set(' \t')^1 * Variable('word_unquoted')^1)^0) ^
603             white_space^0,
604
605             word_unquoted = (1 - white_space - Set(
606                 opts.group_begin ..
607                 opts.group_end ..
608                 opts.assignment_operator ..
609                 opts.list_separator))^1
610             })
611
612 -- LuaFormatter on
613 end
614
615 local function visit_tree(tree, callback_func)
616     if type(tree) ~= 'table' then
617         throw_error('Parameter "tree" has to be a table, got: ' ..
618                     tostring(tree))
619     end
620     local function visit_tree_recursive(tree,
621         current,
622         result,
623         depth,
624         callback_func)
625         for key, value in pairs(current) do
626             if type(value) == 'table' then
627                 value = visit_tree_recursive(tree, value, {}, depth + 1,
628                     callback_func)
629             end
630
631             key, value = callback_func(key, value, depth, current, tree)
632
633             if key ~= nil and value ~= nil then
634                 result[key] = value
635             end
636         end
637         if next(result) ~= nil then
638             return result
639         end
640     end
641
642     local result = visit_tree_recursive(tree, tree, {}, 1, callback_func)
643
644     if result == nil then
645         return {}
646     end
647     return result
648 end
649
650 local is = {
651     boolean = function(value)
652         if value == nil then
653             return false
654         end
655         if type(value) == 'boolean' then
656             return true
657         end
658         local parser = generate_parser('boolean_only')
659         local result = parser:match(tostring(value))

```

```

660     return result ~= nil
661   end,
662
663   dimension = function(value)
664     if value == nil then
665       return false
666     end
667     local parser = generate_parser('dimension_only')
668     local result = parser:match(tostring(value))
669     return result ~= nil
670   end,
671
672   integer = function(value)
673     local n = tonumber(value)
674     if n == nil then
675       return false
676     end
677     return n == math.floor(n)
678   end,
679
680   number = function(value)
681     if value == nil then
682       return false
683     end
684     if type(value) == 'number' then
685       return true
686     end
687     local parser = generate_parser('number_only')
688     local result = parser:match(tostring(value))
689     return result ~= nil
690   end,
691
692   string = function(value)
693     return type(value) == 'string'
694   end,
695
696   any = function(value)
697     return true
698   end,
699 }
700
701 --- Apply the key-value-pair definitions (defs) on an input table in a
702 --- recursive fashion.
703 ---
704 ---@param defs table # A table containing all definitions.
705 ---@param opts table # The parse options table.
706 ---@param input table # The current input table.
707 ---@param output table # The current output table.
708 ---@param unknown table # Always the root unknown table.
709 ---@param key_path table # An array of key names leading to the current
710 ---@param input_root table # The root input table input and output table.
711 local function apply_definitions(defs,
712   opts,
713   input,
714   output,
715   unknown,
716   key_path,
717   input_root)
718   local exclusive_groups = {}
719
720   local function add_to_key_path(key_path, key)
721     local new_key_path = {}

```

```

722
723     for index, value in ipairs(key_path) do
724         new_key_path[index] = value
725     end
726
727     table.insert(new_key_path, key)
728     return new_key_path
729 end
730
731 local function get_default_value(def)
732     if def.default ~= nil then
733         return def.default
734     elseif opts ~= nil and opts.default ~= nil then
735         return opts.default
736     end
737     return true
738 end
739
740 local function find_value(search_key, def)
741     if input[search_key] ~= nil then
742         local value = input[search_key]
743         input[search_key] = nil
744         return value
745         -- naked keys: values with integer keys
746     elseif utils.remove_from_array(input, search_key) ~= nil then
747         return get_default_value(def)
748     end
749 end
750
751 local apply =
752     alias = function(value, key, def)
753         if type(def.alias) == 'string' then
754             def.alias = { def.alias }
755         end
756         local alias_value
757         local used_alias_key
758         -- To get an error if the key and an alias is present
759         if value ~= nil then
760             alias_value = value
761             used_alias_key = key
762         end
763         for _, alias in ipairs(def.alias) do
764             local v = find_value(alias, def)
765             if v ~= nil then
766                 if alias_value ~= nil then
767                     throw_error(string.format(
768                         'Duplicate aliases "%s" and "%s" for key "%s"!', 
769                         used_alias_key, alias, key))
770                 end
771                 used_alias_key = alias
772                 alias_value = v
773             end
774         end
775         if alias_value ~= nil then
776             return alias_value
777         end
778     end,
779
780 always_present = function(value, key, def)
781     if value == nil and def.always_present then
782         return get_default_value(def)
783     end

```

```

784     end,
785
786     choices = function(value, key, def)
787         if value == nil then
788             return
789         end
790         if def.choices ~= nil and type(def.choices) == 'table' then
791             local is_in_choices = false
792             for _, choice in ipairs(def.choices) do
793                 if value == choice then
794                     is_in_choices = true
795                 end
796             end
797             if not is_in_choices then
798                 throw_error('The value "' .. value ..
799                             '" does not exist in the choices: ' ..
800                                         table.concat(def.choices, ', ') .. '!')
801             end
802         end
803     end,
804
805     data_type = function(value, key, def)
806         if value == nil then
807             return
808         end
809         if def.data_type ~= nil then
810             local converted
811             -- boolean
812             if def.data_type == 'boolean' then
813                 if value == 0 or value == '' or not value then
814                     converted = false
815                 else
816                     converted = true
817                 end
818                 -- dimension
819             elseif def.data_type == 'dimension' then
820                 if is.dimension(value) then
821                     converted = value
822                 end
823                 -- integer
824             elseif def.data_type == 'integer' then
825                 if is.number(value) then
826                     local n = tonumber(value)
827                     if type(n) == 'number' and n ~= nil then
828                         converted = math.floor(n)
829                     end
830                 end
831                 -- number
832             elseif def.data_type == 'number' then
833                 if is.number(value) then
834                     converted = tonumber(value)
835                 end
836                 -- string
837             elseif def.data_type == 'string' then
838                 converted = tostring(value)
839             else
840                 throw_error('Unknown data type: ' .. def.data_type)
841             end
842             if converted == nil then
843                 throw_error(
844                     'The value "' .. value .. '" of the key "' .. key ..
845                     '" could not be converted into the data type "' ..

```

```

846         def.data_type .. '"!"')
847     else
848       return converted
849     end
850   end
851 end,
852
853 exclusive_group = function(value, key, def)
854   if value == nil then
855     return
856   end
857   if def.exclusive_group ~= nil then
858     if exclusive_groups[def.exclusive_group] ~= nil then
859       throw_error('The key "' .. key ..
860                 '" belongs to a mutually exclusive group "' ..
861                 def.exclusive_group .. '" and the key "' ..
862                 exclusive_groups[def.exclusive_group] ..
863                 '" is already present!')
864     else
865       exclusive_groups[def.exclusive_group] = key
866     end
867   end
868 end,
869
870 l3_tl_set = function(value, key, def)
871   if value == nil then
872     return
873   end
874   if def.l3_tl_set ~= nil then
875     tex.print(l3_code_cctab,
876               '\tl_set:Nn \g_1 .. def.l3_tl_set .. '_tl')
877     tex.print('{' .. value .. '}')
878   end
879 end,
880
881 macro = function(value, key, def)
882   if value == nil then
883     return
884   end
885   if def.macro ~= nil then
886     token.set_macro(def.macro, value, 'global')
887   end
888 end,
889
890 match = function(value, key, def)
891   if value == nil then
892     return
893   end
894   if def.match ~= nil then
895     if type(def.match) ~= 'string' then
896       throw_error('def.match has to be a string')
897     end
898     local match = string.match(value, def.match)
899     if match == nil then
900       throw_error(
901         'The value "' .. value .. '" of the key "' .. key ..
902         '" does not match "' .. def.match .. '"!')
903     else
904       return match
905     end
906   end
907 end,

```

```

908
909     opposite_keys = function(value, key, def)
910         if def.opposite_keys == nil then
911             local true_value = def.opposite_keys[true]
912             local false_value = def.opposite_keys[false]
913             if true_value == nil or false_value == nil then
914                 throw_error(
915                     'Usage opposite_keys = { [true] = "...", [false] = "..." }')
916             end
917             if utils.remove_from_array(input, true_value) == nil then
918                 return true
919             elseif utils.remove_from_array(input, false_value) == nil then
920                 return false
921             end
922         end
923     end,
924
925     process = function(value, key, def)
926         if value == nil then
927             return
928         end
929         if def.process == nil and type(def.process) == 'function' then
930             return def.process(value, input_root, output, unknown)
931         end
932     end,
933
934     pick = function(value, key, def)
935         if def.pick then
936             local pick_types
937
938             -- Allow old deprecated attribut pick = true
939             if def.pick == true then
940                 pick_types = { 'any' }
941             elseif type(def.pick) == 'table' then
942                 pick_types = def.pick
943             else
944                 pick_types = { def.pick }
945             end
946
947             -- Check if the pick attribute is valid
948             for _, pick_type in ipairs(pick_types) do
949                 if type(pick_type) == 'string' and is[pick_type] == nil then
950                     throw_error(
951                         'Wrong data type in the "pick" attribute: ' ..
952                         tostring(pick_type) ..
953                         '. Allowed are: any, boolean, dimension, integer, number, string.')
954                 end
955             end
956
957             -- The key has already a value. We leave the function at this
958             -- point to be able to check the pick attribute for errors
959             -- beforehand.
960             if value == nil then
961                 return value
962             end
963
964             for _, pick_type in ipairs(pick_types) do
965                 for i, v in pairs(input) do
966                     -- We can not use ipairs here. `ipairs(t)` iterates up to the
967                     -- first absent index. Values are deleted from the `input`
968                     -- table.
969                     if type(i) == 'number' then

```

```

970         local picked_value = nil
971         if is[pick_type](v) then
972             picked_value = v
973         end
974
975         if picked_value ~= nil then
976             input[i] = nil
977             return picked_value
978         end
979         end
980     end
981     end
982     end
983   end,
984
985   required = function(value, key, def)
986     if def.required ~= nil and def.required and value == nil then
987       throw_error(string.format('Missing required key "%s"!', key))
988     end
989   end,
990
991   sub_keys = function(value, key, def)
992     if def.sub_keys ~= nil then
993       local v
994       -- To get keys defined with always_present
995       if value == nil then
996         v = {}
997       elseif type(value) == 'string' then
998         v = { value }
999       elseif type(value) == 'table' then
1000         v = value
1001       end
1002       v = apply_definitions(def.sub_keys, opts, v, output[key],
1003           unknown, add_to_key_path(key_path, key), input_root)
1004       if utils.get_table_size(v) > 0 then
1005         return v
1006       end
1007     end
1008   end,
1009 }
1010
1011 --- standalone values are removed.
1012 --- For some callbacks and the third return value of parse, we
1013 --- need an unchanged raw result from the parse function.
1014 input = clone_table(input)
1015 if output == nil then
1016   output = {}
1017 end
1018 if unknown == nil then
1019   unknown = {}
1020 end
1021 if key_path == nil then
1022   key_path = {}
1023 end
1024
1025 for index, def in pairs(defs) do
1026   -- Find key and def
1027   local key
1028   -- '{ key1 = { }, key2 = { } }'
1029   if type(def) == 'table' and def.name == nil and type(index) ==
1030     'string' then
1031     key = index

```

```

1032     -- `[{ name = 'key1' }, { name = 'key2' }]`  

1033     elseif type(def) == 'table' and def.name ~= nil then  

1034         key = def.name  

1035         -- Definitions as strings in an array: `['key1', 'key2']`  

1036     elseif type(index) == 'number' and type(def) == 'string' then  

1037         key = def  

1038         def = { default = get_default_value({}) }  

1039     end  

1040  

1041     if type(def) ~= 'table' then  

1042         throw_error('Key definition must be a table!')  

1043     end  

1044  

1045     for attr, _ in pairs(def) do  

1046         if namespace.attrs[attr] == nil then  

1047             throw_error('Unknown definition attribute: ' .. tostring(attr))  

1048         end  

1049     end  

1050  

1051     if key == nil then  

1052         throw_error('Key name couldn't be detected!')  

1053     end  

1054  

1055     local value = find_value(key, def)  

1056  

1057     for _, def_opt in ipairs({  

1058         'alias',  

1059         'opposite_keys',  

1060         'pick',  

1061         'always_present',  

1062         'required',  

1063         'data_type',  

1064         'choices',  

1065         'match',  

1066         'exclusive_group',  

1067         'macro',  

1068         'l3_t1_set',  

1069         'process',  

1070         'sub_keys',  

1071     }) do  

1072         if def[def_opt] ~= nil then  

1073             local tmp_value = apply[def_opt](value, key, def)  

1074             if tmp_value ~= nil then  

1075                 value = tmp_value  

1076             end  

1077         end  

1078     end  

1079  

1080     output[key] = value  

1081 end  

1082  

1083 if utils.get_table_size(input) > 0 then  

1084     -- Move to the current unknown table.  

1085     local current_unknown = unknown  

1086     for _, key in ipairs(key_path) do  

1087         if current_unknown[key] == nil then  

1088             current_unknown[key] = {}  

1089         end  

1090         current_unknown = current_unknown[key]  

1091     end  

1092  

1093     -- Copy all unknown key-value-pairs to the current unknown table.

```

```

1094     for key, value in pairs(input) do
1095         current_unknown[key] = value
1096     end
1097 end
1098
1099     return output, unknown
1100 end
1101
1102 --- Parse a LaTeX/TeX style key-value string into a Lua table.
1103 ---
1104 ---@param kv_string string # A string in the TeX/LaTeX style key-value format as
1105 -- described above.
1106 ---@param opts? table # A table containing the settings:
1107 ---  `convert_dimensions`, `unpack`, `naked_as_value`, `converter`,
1108 ---  `debug`, `preprocess`, `postprocess`.
1109 ---
1110 ---@return table result # The final result of all individual parsing and
1111 -- normalization steps.
1112 ---@return table unknown # A table with unknown, undefined key-value pairs.
1113 ---@return table raw # The unprocessed, raw result of the LPeg parser.
1114 local function parse(kv_string, opts)
1115     if kv_string == nil then
1116         return {}, {}, {}
1117     end
1118
1119     opts = normalize_opts(opts)
1120
1121     if type(opts.hooks_kv_string) == 'function' then
1122         kv_string = opts.hooks_kv_string(kv_string)
1123     end
1124
1125     local result = generate_parser('list', opts):match(kv_string)
1126     local raw = clone_table(result)
1127
1128     local function apply_hook(name)
1129         if type(opts.hooks[name]) == 'function' then
1130             if name:match('^keys') then
1131                 result = visit_tree(result, opts.hooks[name])
1132             else
1133                 opts.hooks[name](result)
1134             end
1135
1136             if opts.debug then
1137                 print('After the execution of the hook: ' .. name)
1138                 debug(result)
1139             end
1140         end
1141
1142         local function apply_hooks(at)
1143             if at ~= nil then
1144                 at = '_' .. at
1145             else
1146                 at = ''
1147             end
1148             apply_hook('keys' .. at)
1149             apply_hook('result' .. at)
1150         end
1151
1152         apply_hooks('before_opts')
1153
1154         --- Normalize the result table of the LPeg parser. This normalization

```

```

1154 -- tasks are performed on the raw input table coming directly from
1155 -- the PEG parser:
1156 --
1157 ---@param result table # The raw input table coming directly from the PEG parser
1158 ---@param opts table # Some options.
1159 local function apply_opts(result, opts)
1160   local callbacks = {
1161     unpack = function(key, value)
1162       if type(value) == 'table' and utils.get_array_size(value) == 1 and
1163         utils.get_table_size(value) == 1 and type(value[1]) ~= 'table' then
1164           return key, value[1]
1165         end
1166         return key, value
1167       end,
1168 
1169     process_naked = function(key, value)
1170       if type(key) == 'number' and type(value) == 'string' then
1171         return value, opts.default
1172       end
1173       return key, value
1174     end,
1175 
1176     format_key = function(key, value)
1177       if type(key) == 'string' then
1178         for _, style in ipairs(opts.format_keys) do
1179           if style == 'lower' then
1180             key = key:lower()
1181           elseif style == 'snake' then
1182             key = key:gsub('[%w]+', '_')
1183           elseif style == 'upper' then
1184             key = key:upper()
1185           else
1186             throw_error('Unknown style to format keys: ' ..
1187                         tostring(style) ..
1188                         ' Allowed styles are: lower, snake, upper')
1189           end
1190         end
1191       end
1192       return key, value
1193     end,
1194   }
1195 
1196   if opts.unpack then
1197     result = visit_tree(result, callbacks.unpack)
1198   end
1199 
1200   if not opts.naked_as_value and opts.defs == false then
1201     result = visit_tree(result, callbacks.process_naked)
1202   end
1203 
1204   if opts.format_keys then
1205     if type(opts.format_keys) ~= 'table' then
1206       throw_error(
1207         'The option "format_keys" has to be a table not ' ..
1208         type(opts.format_keys))
1209     end
1210     result = visit_tree(result, callbacks.format_key)
1211   end
1212 
1213   return result
1214 end
1215 result = apply_opts(result, opts)

```

```

1216
1217    -- All unknown keys are stored in this table
1218    local unknown = nil
1219    if type(opts.defs) == 'table' then
1220        apply_hooks('before_defs')
1221        result, unknown = apply_definitions(opts.defs, opts, result, {}, {}, {},
1222            {}, clone_table(result))
1223    end
1224
1225    apply_hooks()
1226
1227    if opts.defaults ~= nil and type(opts.defaults) == 'table' then
1228        merge_tables(result, opts.defaults)
1229    end
1230
1231    if opts.debug then
1232        debug(result)
1233    end
1234
1235    -- no_error
1236    if not opts.no_error and type(unknown) == 'table' and
1237        utils.get_table_size(unknown) > 0 then
1238        throw_error('Unknown keys: ' .. render(unknown))
1239    end
1240    return result, unknown, raw
1241 end
1242
1243 --- Store results
1244 -- @section
1245
1246 --- A table to store parsed key-value results.
1247 local result_store = {}
1248
1249 --- Exports
1250 -- @section
1251
1252 local export = {
1253     version = { 0, 9, 0 },
1254
1255     namespace = namespace,
1256
1257     ---This function is used in the documentation.
1258     ---
1259     ---@param from string # A key in the namespace table, either `opts`, `hook` or
1260     --> `attrs`.
1261     print_names = function(from)
1262         local names = {}
1263         for name in pairs(namespace[from]) do
1264             table.insert(names, name)
1265         end
1266         table.sort(names)
1267         tex.print(table.concat(names, ', '))
1268     end,
1269
1270     print_default = function(from, name)
1271         tex.print(tostring(namespace[from][name]))
1272     end,
1273
1274     --- @see default_options
1275     opts = default_options,
1276
1277     --- @see stringify

```

```

1277     stringify = stringify,
1278
1279     --- @see parse
1280     parse = parse,
1281
1282     define = function(defs, opts)
1283         return function(kv_string, inner_opts)
1284             local options
1285
1286             if inner_opts ~= nil and opts ~= nil then
1287                 options = merge_tables(opts, inner_opts)
1288             elseif inner_opts ~= nil then
1289                 options = inner_opts
1290             elseif opts ~= nil then
1291                 options = opts
1292             end
1293
1294             if options == nil then
1295                 options = {}
1296             end
1297
1298             options.defs = defs
1299
1300             return parse(kv_string, options)
1301         end
1302     end,
1303
1304     --- @see render
1305     render = render,
1306
1307     --- @see debug
1308     debug = debug,
1309
1310     --- The function `save(identifier, result): void` saves a result (a
1311     -- table from a previous run of `parse`) under an identifier.
1312     -- Therefore, it is not necessary to pollute the global namespace to
1313     -- store results for the later usage.
1314
1315     ---@param identifier string # The identifier under which the result is saved.
1316     --
1317     ---@param result table # A result to be stored and that was created by the
1318     -- key-value parser.
1319     save = function(identifier, result)
1320         result_store[identifier] = result
1321     end,
1322
1323     --- The function `get(identifier): table` retrieves a saved result
1324     -- from the result store.
1325
1326     ---@param identifier string # The identifier under which the result was saved.
1327     --
1328     ---@return table
1329     get = function(identifier)
1330         -- if result_store[identifier] == nil then
1331         --     throw_error('No stored result was found for the identifier \'' ..
1332         --             identifier .. '\'')
1333         -- end
1334         return result_store[identifier]
1335     end,
1336
1337     is = is,
1338
1339

```

```
1337     utils = utils,
1338 }
1339
1340 return export
```

7.2 luakeys.tex

```
1 %% luakeys.tex
2 %% Copyright 2021-2022 Josef Friedrich
3 %
4 % This work may be distributed and/or modified under the
5 % conditions of the LaTeX Project Public License, either version 1.3c
6 % of this license or (at your option) any later version.
7 % The latest version of this license is in
8 % http://www.latex-project.org/lppl.txt
9 % and version 1.3c or later is part of all distributions of LaTeX
10 % version 2008/05/04 or later.
11 %
12 % This work has the LPPL maintenance status `maintained'.
13 %
14 % The Current Maintainer of this work is Josef Friedrich.
15 %
16 % This work consists of the files luakeys.lua, luakeys.sty, luakeys.tex
17 % luakeys-debug.sty and luakeys-debug.tex.
18 %
19 \directlua{luakeys = require('luakeys')}
```

7.3 luakeys.sty

```
1  %% luakeys.sty
2  %% Copyright 2021-2022 Josef Friedrich
3  %
4  % This work may be distributed and/or modified under the
5  % conditions of the LaTeX Project Public License, either version 1.3c
6  % of this license or (at your option) any later version.
7  % The latest version of this license is in
8  %   http://www.latex-project.org/lppl.txt
9  % and version 1.3c or later is part of all distributions of LaTeX
10 % version 2008/05/04 or later.
11 %
12 % This work has the LPPL maintenance status `maintained'.
13 %
14 % The Current Maintainer of this work is Josef Friedrich.
15 %
16 % This work consists of the files luakeys.lua, luakeys.sty, luakeys.tex
17 % luakeys-debug.sty and luakeys-debug.tex.
18
19 \NeedsTeXFormat{LaTeX2e}
20 \ProvidesPackage{luakeys}[2022/11/21 0.9.0 Parsing key-value options using Lua.]
21 \directlua{luakeys = require('luakeys')}
```

7.4 luakeys-debug.tex

```
1  %% luakeys-debug.tex
2  %% Copyright 2021-2022 Josef Friedrich
3  %
4  % This work may be distributed and/or modified under the
5  % conditions of the LaTeX Project Public License, either version 1.3c
6  % of this license or (at your option) any later version.
7  % The latest version of this license is in
8  % http://www.latex-project.org/lppl.txt
9  % and version 1.3c or later is part of all distributions of LaTeX
10 % version 2008/05/04 or later.
11 %
12 % This work has the LPPL maintenance status `maintained'.
13 %
14 % The Current Maintainer of this work is Josef Friedrich.
15 %
16 % This work consists of the files luakeys.lua, luakeys.sty, luakeys.tex
17 % luakeys-debug.sty and luakeys-debug.tex.
18
19 \directlua
20 {
21     luakeys = require('luakeys')
22 }
23
24 \def\luakeysdebug%
25 {%
26     \directlua%
27     {
28         local oarg = luakeys.utils.scan_oarg()
29         local marg = token.scan_argument(false)
30         local opts
31         if oarg then
32             opts = luakeys.parse(oarg, { format_keys = { 'snake', 'lower' } })
33         end
34         local result = luakeys.parse(marg, opts)
35         luakeys.debug(result)
36         tex.print(
37             '{' ..
38             '\string\\tt' ..
39             '\string\\parindent=0pt' ..
40             luakeys.stringify(result, true) ..
41         '}'
42     )
43 }%
44 }
```

7.5 luakeys-debug.sty

```
1  %% luakeys-debug.sty
2  %% Copyright 2021-2022 Josef Friedrich
3  %
4  % This work may be distributed and/or modified under the
5  % conditions of the LaTeX Project Public License, either version 1.3c
6  % of this license or (at your option) any later version.
7  % The latest version of this license is in
8  % http://www.latex-project.org/lppl.txt
9  % and version 1.3c or later is part of all distributions of LaTeX
10 % version 2008/05/04 or later.
11 %
12 % This work has the LPPL maintenance status `maintained'.
13 %
14 % The Current Maintainer of this work is Josef Friedrich.
15 %
16 % This work consists of the files luakeys.lua, luakeys.sty, luakeys.tex
17 % luakeys-debug.sty and luakeys-debug.tex.
18
19 \NeedsTeXFormat{LaTeX2e}
20 \ProvidesPackage{luakeys-debug}[2022/11/21 0.9.0 Debug package for luakeys.]
21
22 \input luakeys-debug.tex
```

Change History

0.1.0	General: Initial release	59	0.7.0	case_insensitive_keys.	59
0.2.0	General: * Allow all recognized data types as keys. * Allow TeX macros in the values. * New public Lua functions: save(identifier, result), get(identifier).	59	0.7.0	General: * The project now uses semantic versioning. * New definition attribute “pick” to pick standalone values and assign them to a key. * New function “utils.scan_oarg()” to search for an optional argument, that means scan for tokens that are enclosed in square brackets. * Extend and improve the documentation.	59
0.3.0	General: * Add a LuaLaTeX wrapper “luakeys.sty”. * Add a plain LuaTeX wrapper “luakeys.tex”. * Rename the previous documentation file “luakeys.tex” to luakeys-doc.tex”.	59	0.8.0	General: * Add 6 new options to change the delimiters: “assignment_operator”, “group_begin”, “group_end”, “list_separator”, “quotation_begin”, “quotation_end”. * Extend the documentation about the option “format_keys”.	59
0.4.0	General: * Parser: Add support for nested tables (for example ‘a’, ‘b’). * Parser: Allow only strings and numbers as keys. * Parser: Remove support from Lua numbers with exponents (for example ‘5e+20’). * Switch the Lua testing framework to busted.	59	0.9.0	General: * The definition attribute “pick” accepts a new data type: “any”. * The attribute value “true” for the attribute “pick” is deprecated. * The attribute “pick” accepts now multiple data types specified in a table. * Add a new function called “any(value)” in the “is” table that accepts any data type.	59
0.5.0	General: * Add possibility to change options globally. * New option: standalone_as_true. * Add a recursive converter callback / hook to process the parse tree. * New option:				