

LuaT_EX

Reference

beta 0.40.2



LuaT_EX

Reference

Manual

copyright: LuaT_EX development team
more info: www.luatex.org
version: June 3, 2009

Contents

1	Introduction	9
2	Basic T _E X enhancements	11
2.1	Introduction	11
2.2	Version information	11
2.3	Unicode text support	12
2.4	Extended tables	12
2.5	Attribute registers	13
2.5.1	Box attributes	13
2.6	Lua related primitives	14
2.6.1	<code>\directlua</code>	14
2.6.2	<code>\latelua</code>	15
2.6.3	<code>\luaescapestring</code>	16
2.7	New ε -T _E X primitives	16
2.7.1	<code>\clearmarks</code>	16
2.7.2	<code>\noligs</code> and <code>\nokerns</code>	16
2.7.3	<code>\formatname</code>	17
2.7.4	<code>\scantextokens</code>	17
2.7.5	Catcode tables	17
2.7.5.1	<code>\catcodetable</code>	17
2.7.5.2	<code>\initcatcodetable</code>	17
2.7.5.3	<code>\savecatcodetable</code>	18
2.7.6	<code>\suppressfontnotfounderror</code> (0.11)	18
2.7.7	<code>\suppresslongerror</code> (0.36)	18
2.7.8	<code>\suppressifcsnameerror</code> (0.36)	18
2.7.9	<code>\suppressoutererror</code> (0.36)	19
2.7.10	<code>\outputbox</code> (0.37)	19
2.7.11	Font syntax	19
2.8	Debugging	19
3	Lua general	21
3.1	Initialization	21
3.1.1	LuaT _E X as a Lua interpreter	21
3.1.2	LuaT _E X as a Lua byte compiler	21
3.1.3	Other commandline processing	21
3.2	Lua changes	23
3.3	Lua modules	25
4	LuaT _E X Lua Libraries	27
4.1	The <code>tex</code> library	27
4.1.1	Internal parameter values	27
4.1.1.1	Integer parameters	27



4.1.1.2	Dimension parameters	29
4.1.1.3	Direction parameters	29
4.1.1.4	Glue parameters	29
4.1.1.5	Muglue parameters	30
4.1.1.6	Tokenlist parameters	30
4.1.2	Convert commands	30
4.1.3	Last item commands	31
4.1.4	Attribute, count, dimension, skip and token registers	31
4.1.5	Box registers	32
4.1.6	Math parameters	33
4.1.7	Special list heads	34
4.1.8	Print functions	34
4.1.8.1	<code>tex.print</code>	34
4.1.8.2	<code>tex.sprint</code>	35
4.1.8.3	<code>tex.write</code>	35
4.1.9	Helper functions	36
4.1.9.1	<code>tex.round</code>	36
4.1.9.2	<code>tex.scale</code>	36
4.1.9.3	<code>tex.definefont</code>	36
4.1.10	Functions for dealing with primitives	36
4.1.10.1	<code>tex.enableprimitives</code>	36
4.1.10.2	<code>tex.extraprimitives</code>	37
4.1.10.3	<code>tex.primitives</code>	40
4.2	The <code>token</code> library	40
4.2.1	<code>token.get_next</code>	41
4.2.2	<code>token.is_expandable</code>	41
4.2.3	<code>token.expand</code>	41
4.2.4	<code>token.is_activechar</code>	41
4.2.5	<code>token.create</code>	41
4.2.6	<code>token.command_name</code>	42
4.2.7	<code>token.command_id</code>	42
4.2.8	<code>token.csname_name</code>	42
4.2.9	<code>token.csname_id</code>	42
4.3	The <code>node</code> library	43
4.3.1	Node handling functions	43
4.3.1.1	<code>node.types</code>	43
4.3.1.2	<code>node.whatsits</code>	44
4.3.1.3	<code>node.id</code>	44
4.3.1.4	<code>node.subtype</code>	44
4.3.1.5	<code>node.type</code>	44
4.3.1.6	<code>node.fields</code>	44
4.3.1.7	<code>node.has_field</code>	44
4.3.1.8	<code>node.new</code>	45
4.3.1.9	<code>node.free</code>	45



4.3.1.10	<code>node.flush_list</code>	45
4.3.1.11	<code>node.copy</code>	45
4.3.1.12	<code>node.copy_list</code>	45
4.3.1.13	<code>node.hpack</code>	46
4.3.1.14	<code>node.mlist_to_hlist</code>	46
4.3.1.15	<code>node.slide</code>	46
4.3.1.16	<code>node.length</code>	46
4.3.1.17	<code>node.count</code>	46
4.3.1.18	<code>node.traverse</code>	47
4.3.1.19	<code>node.traverse_id</code>	47
4.3.1.20	<code>node.remove</code>	47
4.3.1.21	<code>node.insert_before</code>	47
4.3.1.22	<code>node.insert_after</code>	47
4.3.1.23	<code>node.first_character</code>	48
4.3.1.24	<code>node.ligaturing</code>	48
4.3.1.25	<code>node.kerning</code>	48
4.3.1.26	<code>node.unprotect_glyphs</code>	48
4.3.1.27	<code>node.protect_glyphs</code>	48
4.3.1.28	<code>node.last_node</code>	49
4.3.1.29	<code>node.write</code>	49
4.3.2	Attribute handling	49
4.3.2.1	<code>node.has_attribute</code>	49
4.3.2.2	<code>node.set_attribute</code>	49
4.3.2.3	<code>node.unset_attribute</code>	49
4.4	The <code>texio</code> library	50
4.4.1	Printing functions	50
4.4.1.1	<code>texio.write</code>	50
4.4.1.2	<code>texio.write_nl</code>	50
4.5	The <code>pdf</code> library	50
4.6	The <code>img</code> library	51
4.7	The <code>mplib</code> library	55
4.7.1	<code>mp:statistics</code>	55
4.7.2	<code>mp:execute</code>	56
4.7.3	<code>mp:finish</code>	57
4.7.4	Result table	57
4.7.5.1	fill	58
4.7.5.2	outline	59
4.7.5.3	text	59
4.7.5.4	special	59
4.7.5.5	start_bounds, start_clip	59
4.7.5.6	stop_bounds, stop_clip	59
4.7.6	Subsidiary table formats	60
4.7.6.1	Paths and pens	60



4.7.6.2	Colors	60
4.7.6.3	Transforms	60
4.7.6.4	Dashes	61
4.7.7	Character size information	61
4.7.7.1	<code>mp.char_width</code>	61
4.7.7.2	<code>mp.char_height</code>	61
4.7.7.3	<code>mp.char_depth</code>	61
4.8	The <code>callback</code> library	61
4.8.1	File discovery callbacks	62
4.8.1.1	<code>find_read_file</code> and <code>find_write_file</code>	62
4.8.1.2	<code>find_font_file</code>	62
4.8.1.3	<code>find_output_file</code>	63
4.8.1.4	<code>find_format_file</code>	63
4.8.1.5	<code>find_vf_file</code>	63
4.8.1.6	<code>find_ocp_file</code>	63
4.8.1.7	<code>find_map_file</code>	63
4.8.1.8	<code>find_enc_file</code>	63
4.8.1.9	<code>find_sfd_file</code>	63
4.8.1.10	<code>find_pk_file</code>	64
4.8.1.11	<code>find_data_file</code>	64
4.8.1.12	<code>find_opentype_file</code>	64
4.8.1.13	<code>find_truetype_file</code> and <code>find_type1_file</code>	64
4.8.1.14	<code>find_image_file</code>	64
4.8.2	File reading callbacks	65
4.8.2.1	<code>open_read_file</code>	65
4.8.2.1.1	<code>reader</code>	65
4.8.2.1.2	<code>close</code>	65
4.8.2.2	General file readers	66
4.8.3	Data processing callbacks	66
4.8.3.1	<code>process_input_buffer</code>	66
4.8.3.2	<code>token_filter</code>	67
4.8.4	Node list processing callbacks	67
4.8.4.1	<code>buildpage_filter</code>	67
4.8.4.2	<code>pre_linebreak_filter</code>	68
4.8.4.3	<code>linebreak_filter</code>	69
4.8.4.4	<code>post_linebreak_filter</code>	69
4.8.4.5	<code>hpack_filter</code>	69
4.8.4.6	<code>vpack_filter</code>	69
4.8.4.7	<code>pre_output_filter</code>	70
4.8.4.8	<code>hyphenate</code>	70
4.8.4.9	<code>ligaturing</code>	70
4.8.4.10	<code>kerning</code>	71
4.8.4.11	<code>mlist_to_hlist</code>	71
4.8.5	Information reporting callbacks	71



4.8.5.1	<code>start_run</code>	71
4.8.5.2	<code>stop_run</code>	71
4.8.5.3	<code>start_page_number</code>	71
4.8.5.4	<code>stop_page_number</code>	72
4.8.5.5	<code>show_error_hook</code>	72
4.8.6	Font-related callbacks	72
4.8.6.1	<code>define_font</code>	72
4.9	The <code>lua</code> library	73
4.9.1	Lua bytecode registers	73
4.9.2	Lua chunk name registers	74
4.10	The <code>kpse</code> library	74
4.10.1	<code>kpse.set_program_name</code> and <code>kpse.new</code>	74
4.10.2	<code>find_file</code>	75
4.10.3	<code>init_prog</code>	76
4.10.4	<code>readable_file</code>	77
4.10.5	<code>expand_path</code>	77
4.10.6	<code>expand_var</code>	77
4.10.7	<code>expand_braces</code>	77
4.10.8	<code>show_path</code>	77
4.10.9	<code>var_value</code>	77
4.11	The <code>status</code> library	78
4.12	The <code>texconfig</code> table	79
4.13	The <code>font</code> library	80
4.13.1	Loading a tfm file	80
4.13.2	Loading a vf file	81
4.13.3	The fonts array	81
4.13.4	Checking a font's status	81
4.13.5	Defining a font directly	81
4.13.6	Projected next font id	82
4.13.7	Currently active font	82
4.13.8	Maximum font id	82
4.13.9	Iterating over all fonts	82
4.14	The <code>fontloader</code> library (0.36)	82
4.14.1	Getting quick information on a font	83
4.14.2	Loading an OpenType or TrueType file	83
4.14.3	Applying a 'feature file'	84
4.14.4	Applying an 'afm file'	84
4.15	Fontloader font tables	85
4.15.1	Table types	85
4.15.1.1	Top-level	85
4.15.1.2	Glyph items	87
4.15.1.3	map table	89
4.15.1.4	private table	90
4.15.1.5	cidinfo table	90



4.15.1.6	pfminfo table	90
4.15.1.7	names table	92
4.15.1.8	anchor_classes table	93
4.15.1.9	gpos table	93
4.15.1.10	gsub table	94
4.15.1.11	ttf_tables and ttf_tab_saved tables	94
4.15.1.12	sm table	94
4.15.1.13	features table	95
4.15.1.14	mm table	95
4.15.1.15	math table	96
4.15.1.16	validation_state table	97
4.15.1.17	horiz_base and vert_base table	98
4.15.1.18	altuni table	98
4.15.1.19	vert_variants and horiz_variants table	98
4.15.1.20	mathkern table	99
4.15.1.21	kerns table	99
4.15.1.22	vkerns table	99
4.15.1.23	texdata table	99
4.15.1.24	lookups table	99
4.16	The lang library	100
5	Math	103
5.1	The current math style	103
5.1.1	\mathstyle	103
5.1.2	\Ustack	103
5.2	Unicode math characters	104
5.3	Cramped math styles	105
5.4	Math parameter settings	106
5.5	Font-based Math Parameters	107
5.6	Math spacing setting	109
5.7	Math accent handling	110
5.8	Math root extension	111
5.9	Math kerning in super- and subscripts	111
5.10	Scripts on horizontally extensible items like arrows	112
5.11	Extensible delimiters	112
5.12	Other Math changes	112
5.12.1	Verbose versions of single-character math commands	112
5.12.2	Allowed math commands in non-math modes	113
5.13	Math todo	113
6	Languages and characters, fonts and glyphs	115
6.1	Characters and glyphs	115
6.2	The main control loop	116
6.3	Loading patterns and exceptions	117
6.4	Applying hyphenation	118



6.5	Applying ligatures and kerning	119
6.6	Breaking paragraphs into lines	121
7	Font structure	123
7.1	Real fonts	128
7.2	Virtual fonts	130
7.2.1	Artificial fonts	132
7.2.2	Example virtual font	132
8	Nodes	135
8.1	Lua node representation	135
8.1.1	Auxiliary items	135
8.1.1.1	glue_spec items	135
8.1.1.2	attribute_list and attribute items	136
8.1.1.3	action item	136
8.1.2	Main text nodes	136
8.1.2.1	hlist nodes	137
8.1.2.2	vlist nodes	137
8.1.2.3	rule nodes	137
8.1.2.4	ins nodes	138
8.1.2.5	mark nodes	138
8.1.2.6	adjust nodes	138
8.1.2.7	disc nodes	138
8.1.2.8	math nodes	139
8.1.2.9	glue nodes	139
8.1.2.10	kern nodes	139
8.1.2.11	penalty nodes	139
8.1.2.12	glyph nodes	140
8.1.2.13	margin_kern nodes	140
8.1.3	Math nodes	141
8.1.3.1	Math kernel subnodes	141
8.1.3.1.1	math_char and math_text_char subnodes	141
8.1.3.1.2	sub_box and sub_mlist subnodes	141
8.1.3.2	Math delimiter subnode	141
8.1.3.2.1	delim subnodes	142
8.1.3.3	Math core nodes	142
8.1.3.3.1	simple nodes	142
8.1.3.3.2	accent nodes	143
8.1.3.3.3	style nodes	143
8.1.3.3.4	choice nodes	143
8.1.3.3.5	radical nodes	144
8.1.3.3.6	fraction nodes	144
8.1.3.3.7	fence nodes	144
8.1.4	whatsit nodes	145
8.1.4.1	open nodes	145



8.1.4.2	write nodes	145
8.1.4.3	close nodes	145
8.1.4.4	special nodes	145
8.1.4.5	language nodes	146
8.1.4.6	local_par nodes	146
8.1.4.7	dir nodes	146
8.1.4.8	pdf_literal nodes	147
8.1.4.9	pdf_refobj nodes	147
8.1.4.10	pdf_refxform nodes	147
8.1.4.11	pdf_refximage nodes	147
8.1.4.12	pdf_annot nodes	148
8.1.4.13	pdf_start_link nodes	148
8.1.4.14	pdf_end_link nodes	148
8.1.4.15	pdf_dest nodes	148
8.1.4.16	pdf_thread nodes	149
8.1.4.17	pdf_start_thread nodes	149
8.1.4.18	pdf_end_thread nodes	149
8.1.4.19	pdf_save_pos nodes	150
8.1.4.20	late_lua nodes	150
8.1.4.21	pdf_colorstack nodes	150
8.1.4.22	pdf_setmatrix nodes	150
8.1.4.23	pdf_save nodes	150
8.1.4.24	pdf_restore nodes	150
8.1.4.25	user_defined nodes	151
9	Modifications	153
9.1	Changes from T _E X 3.1415926	153
9.2	Changes from ϵ -T _E X 2.2	153
9.3	Changes from pdfT _E X 1.40	153
9.4	Changes from Aleph RC4	154
9.5	Changes from standard web2c	155
10	Implementation notes	157
10.1	Primitives overlap	157
10.2	Memory allocation	157
10.3	Sparse arrays	157
10.4	Simple single-character csnames	158
10.5	Compressed format	158
10.6	Binary file reading	158
11	Known bugs and limitations	159
12	TODO	161



1 Introduction

This book will eventually become the reference manual of LuaT_EX. At the moment, it simply reports the behaviour of the executable matching the snapshot or beta release date in the title page.

Features may come and go. The current version of LuaT_EX is not meant for production and users cannot depend on stability, nor on functionality staying the same.

Nothing is considered stable just yet. This manual therefore simply reflects the current state of the executable. ***Absolutely nothing*** on the following pages is set in stone. When the need arises, anything can (and will) be changed without prior notice.

If you are not willing to deal with this situation, you should wait for the stable version. Currently we expect the first release with (some) fixed interfaces to be available sometime in the autumn of 2008. Full stabilization will not happen soon, the TODO list is still very large.

LuaT_EX consists of a number of interrelated but (still) distinguishable parts:

- pdfT_EX version 1.40.9
- Aleph RC4 (from the T_EXLive repository)
- Lua 5.1.4 (+ coco 1.1.5 + portable bytecode)
- dedicated Lua libraries
- various T_EX extensions
- parts of FontForge 2008.11.17
- the MetaPost library
- newly written compiled source code to glue it all together

Neither Aleph's I/O translation processes, nor tcx files, nor encT_EX can be used, these encoding-related functions are superseded by a Lua-based solution (reader callbacks). Also, some experimental pdfT_EX features are removed. These can be implemented in Lua instead.





2 Basic T_EX enhancements

2.1 Introduction

From day one, LuaT_EX has offered extra functionality when compared to the superset of pdf_TE_X and Aleph. That has not been limited to the possibility to execute lua code via `\directlua`, but LuaT_EX also adds functionality via new T_EX-side primitives.

However, starting with beta 0.39.0, most of that functionality will be hidden by default. When LuaT_EX 0.40.0 starts up in ‘`iniluatex`’ mode (`luatex -ini`), it defines only the primitive commands known by T_EX82 and the one extra command `\directlua`.

As is fitting, a lua function has to be called to add the extra primitives to the user environment. The simplest method to get access to all of the new primitive commands is by adding this line to the format generation file:

```
\directlua { tex.enableprimitives('',tex.extraprimitives()) }
```

But be aware, that the curly braces may not have the proper `\catcode` assigned to them at this early time (giving a ‘Missing number’ error), so it may be needed to put these assignments

```
\catcode `\{=1
\catcode `\}=2
```

before the above line. More fine-grained primitives control is possible, you can look the details in [section 4.1.104.1.10](#). For simplicity’s sake, this manual assumes that you have executed the lua command given above.

2.2 Version information

There are three new primitives to test the version of LuaT_EX:

primitive	explanation
<code>\luatexversion</code>	a combination of major and minor number, as in pdf _T E _X ; the current current value is 41
<code>\luatexrevision</code>	the revision number, as in pdf _T E _X ; the current value is 0
<code>\luatexdatestamp</code>	a combination of the local date and hour when the current executable was compiled, the syntax is identical to <code>\luatexrevision</code> ; the value for the executable that generated this document is 2009060314.

The official LuaT_EX version is defined follows:

- The major version is the integer result of `\luatexversion` divided by 100. The primitive is and ‘internal variable’, so you may need to prefix it use with `\the` depending on the context.
- The minor version is the two-digit result of `\luatexversion` modulo 100.



- The revision is the given by `\luatexrevision`. This primitive expands to a positive integer.
- The full version number consists of the major version, minor version and revision, separated by dots.

Note that the `\luatexdatestamp` depends on both the compilation time and compilation place of the current executable, it is defined in terms of the local time. The purpose of this primitive is solely to be an aid in the development process, do not use it for anything besides debugging.

2.3 Unicode text support

Text input and output is now considered to be Unicode text, so input characters can use the full range of Unicode ($2^{20} + 2^{16} - 1 = 0x10FFFF$).

Later chapters will talk of characters and glyphs. Although these are not the interchangeable, they are closely related. During typesetting, a character is always converted to a suitable graphic representation of that character in a specific font. However, while processing a list of to-be-typeset nodes, its contents may still be seen as a character. Inside LuaT_EX there is not yet a clear separation between the two concepts. Until this is implemented, please do not be too harsh on us if we make errors in the usage of the terms.

A few primitives are affected by this, all in a similar fashion: each of them has to accommodate for a larger range of acceptable numbers. For instance, `\char` now accepts values between 0 and 1,114,111. This should not be a problem for well-behaved input files, but it could create incompatibilities for input that would have generated an error when processed by older T_EX-based engines. The affected commands with an altered initial (left of the equals sign) or secondary (right of the equals sign) value are: `\char`, `\lccode`, `\uccode`, `\catcode`, `\sfcode`, `\efcode`, `\lpcode`, `\rpcode`, `\chardef`

As far as the core engine is concerned, all input and output to text files is utf-8 encoded. Input files can be pre-processed using the `reader` callback. This will be explained in a later chapter.

Output in byte-sized chunks can be achieved by using characters just outside of the valid Unicode range, starting at the value 1,114,112 (0x110000). When the times comes to print a character $c \geq 1,114,112$, LuaT_EX will actually print the single byte corresponding to c minus 1,114,112.

Output to the terminal uses `^^` notation for the lower control range ($c < 32$), with the exception of `^^I`, `^^J` and `^^M`. These are considered ‘safe’ and therefore printed as-is.

Normalization of the Unicode input can be handled by a macro package during callback processing (this will be explained in [section 4.8.24.8.2](#)).

2.4 Extended tables

All traditional T_EX and ϵ -T_EX registers can be 16 bit numbers as in Aleph. The affected commands are:

<code>\count</code>	<code>\marks</code>	<code>\skipdef</code>	<code>\unhbox</code>
<code>\dimen</code>	<code>\toks</code>	<code>\muskipdef</code>	<code>\unvbox</code>
<code>\skip</code>	<code>\countdef</code>	<code>\toksdef</code>	<code>\copy</code>
<code>\muskip</code>	<code>\dimendef</code>	<code>\box</code>	<code>\unhcopy</code>



<code>\unvcopy</code>	<code>\dp</code>
<code>\wd</code>	<code>\setbox</code>
<code>\ht</code>	<code>\vsplit</code>

The glyph properties (like `\efcode`) introduced in pdf \TeX that deal with font expansion (hz) and character protruding are also 16 bit. Because font memory management has been rewritten, these character properties are no longer shared among fonts instances that originate from the same metric file

2.5 Attribute registers

Attributes are a completely new concept in Lua \TeX . Syntactically, they behave a lot like counters: attributes obey \TeX 's nesting stack and can be used after `\the` etc. just like the normal `\count` registers.

```
\attribute <16-bit number> <optional equals> <31-bit number>
\attributedef <csname> <optional equals> <16-bit number>
```

Conceptually, an attribute is either 'set' or 'unset'. Unset attributes have a special negative value to indicate that they are unset, that value is the lowest legal value: `-"7FFFFFFF` in hexadecimal, a.k.a. `-2147483647` in decimal. It follows that the value `-"7FFFFFFF` cannot be used as a legal attribute value, but you *can* assign `-"7FFFFFFF` to 'unset' an attribute. All attributes start out in this 'unset' state in ini \TeX (prior to 0.37, there could not be valid negative attribute values, and the 'unset' value was `-1`).

Attributes can be used as extra counter values, but their usefulness comes mostly from the fact that the numbers and values of all 'set' attributes are attached to all nodes created in their scope. These can then be queried from any Lua code that deals with node processing. Future versions of Lua \TeX will probably be using specific negative attribute ids for internal use. Further information about how to use attributes for node list processing from Lua is given in **chapter 88**.

2.5.1 Box attributes

Nodes typically receive the list of attributes that is in effect when they are created. This moment can be quite asynchronous. For example: in paragraph building, the individual line boxes are created after the `\par` command has been processed, so they will receive the list of attributes that is in effect then, not the attributes that were in effect in, say, the first or third line of the paragraph.

Similar situations happen in Lua \TeX regularly. A few of the more obvious problematic cases are dealt with: the attributes for nodes that are created during hyphenation and ligaturing borrow their attributes from their surrounding glyphs, and it is possible to influence box attributes directly.

When you assemble a box in a register, the attributes of the nodes contained in the box are unchanged when such a box is placed, unboxed, or copied. In this respect attributes act the same as characters that have been converted to references to glyphs in fonts. For instance, when you use attributes to implement color support, each node carries information about its color. In that case, unless you implement mechanisms that deal with it, applying a color to already boxed material will have no effect. Keep in



mind that this incompatibility is mostly due to the fact that specials and literals are a more unnatural approach to colors than attributes.

Many other inserted nodes, like the nodes resulting from math mode and alignments, are processed ‘out of order’, and will have the attributes that are in effect at the precise moment of creation (which is often later than expected). This area needs studying, and is in fact one of the reasons for a beta at this moment.

It is possible to fine-tune the list of attributes that are applied to a `hbox`, `vbox` or `vtop` by the use of the keyword `attr`. An example:

```
\attribute2=5
\setbox0=\hbox {Hello}
\setbox2=\hbox attr1=12 attr2=-1{Hello}
```

This will set the attribute list of box 2 to 1 = 12, and the attributes of box 0 will be 2 = 5. As you can see, assigning a negative value causes an attribute to be ignored.

The `attr` keyword(s) should come before a `to` or `spread`, if that is also specified.

2.6 Lua related primitives

In order to merge Lua code with T_EX input, a few new primitives are needed.

2.6.1 `\directlua`

The primitive `\directlua` is used to execute Lua code immediately. The syntax is

```
\directlua <general text>
\directlua name <general text> <general text>
\directlua <16-bit number> <general text>
```

Up until beta 0.36, there was support for multiple lua states, and to make that possible, the `\directlua` and `\latelua` command required an integer argument to be given always. Such integer values are still accepted for the moment, although they generate a (rather pesky) warning. This backward compatibility support will be removed starting with beta 0.41.0.

The last `<general text>` is expanded fully, and then fed into the Lua interpreter. After reading and expansion has been applied to the `<general text>`, the resulting token list is converted to a string as if it was displayed using `\the\toks`. On the Lua side, each `\directlua` block is treated as a separate chunk. In such a chunk you can use the `local` directive to keep your variables from interfering with those used by the macro package.

The conversion from and to a token list means that you normally can not use Lua line comments (starting with `--`) within the argument, as there typically will be only one ‘line’, so that comment will then run on until the end of the input. You will either need to use T_EX-style line comments (starting with `%`), or change the T_EX category codes locally. Another possibility is to say:



```
\begingroup
\endlinechar=10
\directlua ...
\endgroup
```

Then Lua line comments can be used, since T_EX does not replace line endings with spaces.

The `name` `<general text>` specifies the name of the Lua chunk, mainly shown in the stack backtrace of error messages created by Lua code. The `<general text>` is expanded fully, thus macros can be used to generate the chunk name, i.e.

```
\directlua name{\jobname:\the\inputlineno} ...
```

to include the name of the input file as well as the input line into the chunk name.

Likewise, the `<16-bit number>` designates a name of a Lua chunk, but in this case the name will be taken from the `lua.name` array (see the documentation of the `lua` table further in this manual). This syntax is new in version 0.36.0.

Backward compatibility note: when there is a valid name in `lua.name[<16-bit number>]`, the potential warning about a superfluous integer will be suppressed.

The chunk name should not start with a `@`, or it will be displayed as a file name (this is a quirk in the current Lua implementation).

The `\directlua` command is expandable: the results of the Lua code become effective immediately. As an example, the following input:

```
$\pi = \directlua{tex.print(math.pi)}$
```

will result in

```
 $\pi = 3.1415926535898$ 
```

Because the `<general text>` is a chunk, the normal Lua error handling is triggered if there is a problem in the included code. The Lua error messages should be clear enough, but the contextual information is still pretty bad. Typically, you will only see the line number of the right brace at the end of the code.

While on the subject of errors: some of the things you can do inside Lua code can break up LuaT_EX pretty bad. If you are not careful while working with the node list interface, you may even end up with assertion errors from within the T_EX portion of the executable.

2.6.2 `\latelua`

`\latelua` stores Lua code in a whatsit that will be processed inside the output routine. Its intended use is a cross between `\pdfliteral` and `\write`. Within the Lua code, you can print pdf statements directly to the pdf file via `tex.print`, or you can write to other output streams via `texio.write` or simply using lua's I/O routines.



```

\latelua <general text>
\latelua name <general text> <general text>
\latelua <16-bit number> <general text>

```

Up until beta 0.36, there was support for multiple lua states, and to make that possible, the `\directlua` and `\latelua` command required an integer argument to be given always. Such integer values are still accepted for the moment, although they generate a (rather pesky) warning. This backward compatibility support will be removed starting with beta 0.41.0.

Expansion of macros etcetera in the final `<general text>` is delayed until just before the whatsit is executed (like in `\write`). With regard to PDF output stream `\latelua` behaves as `\pdfliteral` page.

The `name <general text>` and `<16-bit number>` behave in the same way as they do for `\directlua`

2.6.3 `\luaescapestring`

This primitive converts a T_EX token sequence so that it can be safely used as the contents of a Lua string: embedded backslashes, double and single quotes, and newlines and carriage returns are escaped. This is done by prepending an extra token consisting of a backslash with category code 12, and for the line endings, converting them to `n` and `r` respectively. The token sequence is fully expanded.

```

\luaescapestring <general text>

```

Most often, this command is not actually the best way to deal with the differences between the T_EX and Lua. In very short bits of Lua code it is often not needed, and for longer stretches of Lua code it is easier to keep the code in a separate file and load it using Lua's `dofile`:

```

\directlua { dofile('mysetups.lua')}

```

2.7 New ϵ -T_EX primitives

2.7.1 `\clearmarks`

This primitive clears a marks class completely, resetting all three connected mark texts to empty.

```

\clearmarks <16-bit number>

```

2.7.2 `\noligs` and `\nokerns`

These primitives prohibit ligature and kerning insertion at the time when the initial node list is built by LuaT_EX's main control loop. They are part of a temporary trick and will be removed in the near future. For now, you need to enable these primitives when you want to do node list processing of 'characters', where T_EX's normal processing would get in the way.



```
\noligs <integer>
\nokerns <integer>
```

These primitives can now be implemented by overloading the ligature building and kerning functions, i.e. by assigning dummy functions to their associated callbacks.

2.7.3 `\formatname`

`\formatname`'s syntax is identical to `\jobname`.

In `iniTEX`, the expansion is empty. Otherwise, the expansion is the value that `\jobname` had during the `iniTEX` run that dumped the currently loaded format.

2.7.4 `\scantextokens`

The syntax of `\scantextokens` is identical to `\scantokens`. This primitive is a slightly adapted version of ϵ -T_EX's `\scantokens`. The differences are:

- The last (and usually only) line does not have a `\endlinechar` appended
- `\scantextokens` never raises an EOF error, and it does not execute `\everyeof` tokens.
- The '... while end of file ...' error tests are not executed, allowing the expansion to end on a different grouping level or while a conditional is still incomplete.

2.7.5 Catcode tables

Catcode tables are a new feature that allows you to switch to a predefined catcode regime in a single statement. You can have a practically unlimited number of different tables.

The subsystem is backward compatible: if you never use the following commands, your document will not notice any difference in behavior compared to traditional T_EX.

The contents of each catcode table is independent from any other catcode tables, and their contents is stored and retrieved from the format file.

2.7.5.1 `\catcodetable`

```
\catcodetable <16-bit number>
```

The `\catcodetable` switches to a different catcode table. Such a table has to be previously created using one of the two primitives below, or it has to be zero. Table zero is initialized by `iniTEX`.

2.7.5.2 `\initcatcodetable`

```
\initcatcodetable <16-bit number>
```

The `\initcatcodetable` creates a new table with catcodes identical to those defined by `iniTEX`:



0	-		escape	
5	^^M	return	car_ret	(this name may change)
9	^^@	null	ignore	
10	<space>	space	spacer	
11	a – z		letter	
11	A – Z		letter	
12	everything else		other	
14	%		comment	
15	^^?	delete	invalid_char	

The new catcode table is allocated globally: it will not go away after the current group has ended. If the supplied number is identical to the currently active table, an error is raised.

2.7.5.3 `\savecatcodetable`

`\savecatcodetable <16-bit number>`

`\savecatcodetable` copies the current set of catcodes to a new table with the requested number. The definitions in this new table are all treated as if they were made in the outermost level.

The new table is allocated globally: it will not go away after the current group has ended. If the supplied number is the currently active table, an error is raised.

2.7.6 `\suppressfontnotfounderror` (0.11)

`\suppressfontnotfounderror = 1`

If this new integer parameter is non-zero, then LuaT_EX will not complain about font metrics that are not found. Instead it will silently skip the font assignment, making the requested csname for the font `\ifx` equal to `\nullfont`, so that it can be tested against that without bothering the user.

2.7.7 `\suppresslongerror` (0.36)

`\suppresslongerror = 1`

If this new integer parameter is non-zero, then LuaT_EX will not complain about `\par` commands encountered in contexts where that is normally prohibited (most prominently in the arguments of non-long macros).

2.7.8 `\suppressifcsnameerror` (0.36)

`\suppressifcsnameerror = 1`

If this new integer parameter is non-zero, then LuaT_EX will not complain about non-expandable commands appearing in the middle of a `\ifcsname` expansion. Instead, it will keep getting expanded tokens from the input until it encounters an `\endcsname` command. Use with care! This command is experimental:



if the input expansion is unbalanced wrt. `\csname ... \endcsname` pairs, the LuaTeX process may hang indefinitely.

2.7.9 `\suppressoutererror` (0.36)

```
\suppressoutererror = 1
```

If this new integer parameter is non-zero, then LuaTeX will not complain about `\outer` commands encountered in contexts where that is normally prohibited.

The addition of this command coincides with a change in the LuaTeX engine: ever since the snapshot of 20060915, `\outer` was simply ignored. That behaviour has now reverted back to be T_EX82-compatible by default.

2.7.10 `\outputbox` (0.37)

```
\outputbox = 65535
```

This new integer parameter allows you to alter the number of the box that will be used to store the page to be shipped out in. It's default value is 255, and the acceptable range is from 0 to 65535.

2.7.11 Font syntax

LuaTeX will accept a braced argument as a font name:

```
\font\myfont = {cmr10}
```

This allows for embedded spaces, without the need for double quotes. Macro expansion takes place inside the argument.

2.8 Debugging

If `\tracingonline` is larger than 2, the node list display will also print the node number of the nodes.





3 Lua general

3.1 Initialization

3.1.1 LuaTeX as a Lua interpreter

There are some situations that make LuaTeX behave like a standalone Lua interpreter:

- if a `--luaonly` option is given on the commandline, or
- if the executable is named `texlua` (or `luatexlua`), or
- if the only non-option argument (file) on the commandline has the extension `lua` or `luc`.

In this mode, it will set Lua's `arg[0]` to the found script name, pushing preceding options in negative values and the rest of the commandline in the positive values, just like the Lua interpreter.

LuaTeX will exit immediately after executing the specified Lua script and is, in effect, a somewhat bulky standalone Lua interpreter with a bunch of extra preloaded libraries.

3.1.2 LuaTeX as a Lua byte compiler

There are two situations that make LuaTeX behave like the Lua byte compiler:

- if a `--luaonly` option is given on the commandline, or
- if the executable is named `texluac`

In this mode, LuaTeX is exactly like `luac` from the standalone Lua distribution, except that it does not have the `-l` switch, and that it accepts (but ignores) the `--luaonly` switch.

3.1.3 Other commandline processing

When the LuaTeX executable starts, it looks for the `--lua` commandline option. If there is no `--lua` option, the commandline is interpreted in a similar fashion as in traditional pdfTeX and Aleph. But if the option is present, LuaTeX will enter an alternative mode of commandline parsing in comparison to the standard web2c programs.

In this mode, a small series of actions is taken in order. At first, it will only interpret a small subset of the commandline directly:

<code>--lua=s</code>	load and execute a Lua initialization script
<code>--safer</code>	disable easily exploitable Lua commands
<code>--nosocket</code>	disable the Lua socket library
<code>--help</code>	display help and exit
<code>--version</code>	display version and exit



Now it searches for the requested Lua initialization script. If it can not be found using the actual name given on the commandline, a second attempt is made by prepending the value of the environment variable `LUATEXDIR`, if that variable is defined.

Then it checks the `--safer` switch. You can use that to disable some Lua commands that can easily be abused by a malicious document. At the moment, this switch `nils` the following functions:

library functions

```
os      execute exec setenv rename remove tmpdir
io      popen output tmpfile
lfs      rmdir mkdir chdir lock touch
```

And it makes `io.open()` fail on files that are opened for anything besides reading.

Next the initialization script is loaded and executed. From within the script, the entire commandline is available in the Lua table `arg`, beginning with `arg[0]`, containing the name of the executable.

Commandline processing happens very early on. So early, in fact, that none of T_EX's initializations have taken place yet. For that reason, the tables that deal with typesetting, like `tex`, `token`, `node` and `pdf`, are off-limits during the execution of the startup file (they are nilled). Special care is taken that `texio.write` and `texio.write_nl` function properly, so that you can at least report your actions to the log file when (and if) it eventually becomes opened (note that T_EX does not even know its `\jobname` yet at this point). See [chapter 44](#) for more information about the LuaT_EX-specific Lua extension tables.

Everything you do in the Lua initialization script will remain visible during the rest of the run, with the exception of the aforementioned `tex`, `token`, `node` and `pdf` tables: those will be initialized to their documented state after the execution of the script. You should not store anything in variables or within tables with these four global names, as they will be overwritten completely.

We recommend you use the startup file only for your own T_EX-independent initializations (if you need any), to parse the commandline, set values in the `texconfig` table, and register the callbacks you need. LuaT_EX will fetch some of the other commandline options from the `texconfig` table at the end of script execution (see the description of the `texconfig` table later on in this document for more details on which ones exactly).

Unless the `texconfig` table tells LuaT_EX not to initialize kpathsea at all (set `texconfig.kpse_init` to `false` for that), LuaT_EX acts on three more commandline options after the initialization script is finished:

flag	meaning
<code>--fmt=s</code>	set the format name
<code>--progname=s</code>	set the progname (only for kpathsea)
<code>--ini</code>	enable iniT _E X mode

In order to initialize the built-in kpathsea library properly, LuaT_EX needs to know the correct `progname` to use, and for that it needs to check `--progname` (and `--ini` and `--fmt`, if `--progname` is missing).



3.2 Lua changes

The C coroutine (coco) patches from luajit are applied to the Lua core, the used version is 1.1.3. See <http://luajit.org/coco.html> for details.

In keeping with the other T_EX-like programs in T_EXLive, the two Lua functions `os.execute` and `io.popen` (as well as the two new functions `os.exec` and `os.spawn` that are explained below) take the value of `shell_escape` and/or `shell_escape_commands` in account. Whenever LuaT_EX is run with the assumed intention to typeset a document (and by that I mean that it is called as `luatex`, as opposed to `texlua`, and that the commandline option `--luaonly` was not given), it will only run the four functions above if the matching texmf.cnf variable(s) or their `texconfig` (see [section 4.124.12](#)) counterparts allow execution of the requested system command. In ‘script interpreter’ runs of LuaT_EX, these settings have no effect, and all four functions function as normal. This change is new in 0.37.0.

The `read(*line)` function from the `io` library has been adjusted so that it is line-ending neutral: any of `LF`, `CR` or `CR+LF` are acceptable line endings.

The `tostring()` printer for numbers has been changed so that it returns `0` instead of something like `2e-5` (which confused T_EX enormously) when the value is so small that T_EX cannot distinguish it from zero.

Dynamic loading of `.so` and `.dll` files is disabled on all platforms.

`luafilesystem` has been extended with two extra boolean functions (`isdir(filename)` and `isfile(filename)`) and one extra string field in its attributes table (`permissions`).

The `string` library has an extra function: `string.explode(s[,m])`. This function returns an array containing the string argument `s` split into sub-strings based on the value of the string argument `m`. The second argument is a string that is either empty (this splits the string into characters), a single character (this splits on each occurrence of that character, possibly introducing empty strings), or a single character followed by the plus sign `+` (this special version does not create empty sub-strings). The default value for `m` is `+` (multiple spaces).

Note: `m` is not hidden by surrounding braces (as it would be if this function was written in T_EX macros).

The `string` library also has six extra iterators that return strings piecemeal:

- `string.utfvalues(s)` (returns an integer value in the Unicode range)
- `string.utfcharacters(s)` (returns a string with a single utf-8 token in it)
- `string.characters(s)` (a string containing one byte)
- `string.characterpairs(s)` (two strings each containing one byte) will produce an empty second string in the string length was odd.
- `string.bytes(s)` (a single byte value)
- `string.bytepairs(s)` (two byte values) Will produce nil instead of a number as its second return value if the string length was odd.

The `string.characterpairs()` and `string.bytepairs()` are useful especially in the conversion of UTF-16 encoded data into UTF-8.



Note: The `string` library functions `find` etc. are not Unicode-aware. In cases where this is required (i. e. because the pattern used for searching contains characters above code point 127), the corresponding functions from `unicode.utf8` should be used.

The `os` library has a few extra functions and variables:

- `os.exec(commandline)` is a variation on `os.execute`.
The `commandline` can be either a single string or a single table.
If the argument is a table: LuaTeX first checks if there is a value at integer index zero. If there is, this is the command to be executed. Otherwise, it will use the value at integer index one. (if neither are present, nothing at all happens).
The set of consecutive values starting at integer 1 in the table are the arguments that are passed on to the command (the value at index 1 becomes `argv[0]`). The command is searched for in the execution path, so there is normally no need to pass on a fully qualified pathname.
If the argument is a string, then it is automatically converted into a table by splitting on whitespace. In this case, it is impossible for the command and first argument to differ from each other.
In the string argument format, whitespace can be protected by putting (part of) an argument inside single or double quotes. One layer of quotes is interpreted by LuaTeX, and all occurrences of `\`, `'` or `\\` within the quoted text are un-escaped. In the table format, there is no string handling taking place.
This function normally does not return control back to the Lua script: the command will replace the current process. However, it will return the two values `nil` and `'error'` if there was a problem while attempting to execute the command.
On windows, the current process is actually kept in memory until after the execution of the command has finished. This prevents crashes in situations where TeX Lua scripts are run inside integrated TeX environments.
The original reason for this command is that it cleans out the current process before starting the new one, making it especially useful for use in TeX Lua.
- `os.spawn(commandline)` is a returning version of `os.exec`, with otherwise identical calling conventions.
If the command ran ok, then the return value is the exit status of the command. Otherwise, it will return the two values `nil` and `'error'`.
- `os.setenv('key', 'value')` This sets a variable in the environment. Passing `nil` instead of a value string will remove the variable.
- `os.env` This is a hash table containing a dump of the variables and values in the process environment at the start of the run. It is writeable, but the actual environment is *not* updated automatically.
- `os.gettimeofday()` Returns the current 'Unix time', but as a float. This function is not available on the SunOS platforms, so do not use this function for portable documents.
- `os.times()` Returns the current process times cf. the Unix C library 'times' call in seconds. This function is not available on the MS Windows and SunOS platforms, so do not use this function for portable documents.
- `os.tmpdir()` This will create a directory in the 'current directory' with the name `luatex.XXXXXX` where the X-es are replaced by a unique string. The function also returns this string, so you can `lfs.chdir()` into it, or `nil` if it failed to create the directory. The user is responsible for cleaning up at the end of the run, it does not happen automatically.



- `os.type` This is a string that gives a global indication of the class of operating system. The possible values are currently `windows`, `unix`, and `msdos` (you are unlikely to find this value ‘in the wild’).
- `os.name` This is a string that gives a more precise indication of the operating system. These possible values are not yet fixed, and for `os.type` values `windows` and `msdos`, the `os.name` values are simply `windows` and `msdos`.
The list for the type `unix` is more precise: `linux`, `freebsd`, `openbsd`, `solaris`, `sunos` (pre-solaris), `hpux`, `irix`, `macosx`, `bsd` (unknown, but bsd-like), `sysv` (unknown, but sysv-like), `generic` (unknown).
(`os.version` is planned as a future extension)

In stock Lua, many things depend on the current locale. In LuaTeX, we can’t do that, because it makes documents unportable. While LuaTeX is running it forces the following locale settings:

```
LC_CTYPE=C
LC_COLLATE=C
LC_NUMERIC=C
```

3.3 Lua modules

Some modules that are normally external to Lua are statically linked in with LuaTeX, because they offer useful functionality:

- `slnunicode`, from the `Selene` libraries, <http://luaforge.net/projects/sln>. (version 1.1)
This library has been slightly extended so that the `unicode.utf8.*` functions also accept the first 256 values of plane 18. This is the range LuaTeX uses for raw binary output, as explained above,
- `luazip`, from the kepler project, <http://www.keplerproject.org/luazip/>. (version 1.2.1, but patched for compilation with Lua 5.1)
- `luafilesystem`, also from the kepler project, <http://www.keplerproject.org/luafilesystem/>. (version 1.4.1)
- `lpeg`, by Roberto Ierusalimsky, <http://www.inf.puc-rio.br/~roberto/lpeg.html>. (version 0.9.0)
Note: `lpeg` is not Unicode-aware, but interprets strings on a byte-per-byte basis. This mainly means that `lpeg.S` cannot be used with characters above code point 127, since those characters are encoded using two bytes, and thus `lpeg.S` will look for one of those two bytes when matching, not the combination of the two.
The same is true for `lpeg.R`, although the latter will display an error message if used with characters above code point 127: i.e. `lpeg.R('ä')` results in the message `bad argument #1 to 'R' (range must have two characters)`, since to `lpeg`, `ä` is two ‘characters’ (bytes), so `ä` totals three.
- `lzlib`, by Tiago Dionizio, <http://mega.ist.utl.pt/~tngd/lua/>. (version 0.2)
- `md5`, by Roberto Ierusalimsky <http://www.inf.puc-rio.br/~roberto/md5/md5-5/md5.html>.
- `luasocket`, by Diego Nehab <http://www.tecgraf.puc-rio.br/~diego/professional/luasocket/> (version 2.0.2).
Note: the `.lua` support modules from `luasocket` are also preloaded inside the executable, there are no external file dependencies.





4 LuaTeX Lua Libraries

The interfacing between T_EX and Lua is facilitated by a set of library modules. The Lua libraries in this chapter are all defined and initialized by the LuaT_EX executable. Together, they allow Lua scripts to query and change a number of T_EX's internal variables, run various internal functions T_EX, and set up LuaT_EX's hooks to execute Lua code.

4.1 The tex library

The `tex` table contains a large list of virtual internal T_EX parameters that are partially writable.

The designation 'virtual' means that these items are not properly defined in Lua, but are only frontends that are handled by a metatable that operates on the actual T_EX values. As a result, most of the Lua table operators (like `pairs` and `#`) do not work on such items.

At the moment, it is possible to access almost every parameter that has these characteristics:

- You can use it after `\the`
- It is a single token.
- Some special others, see the list below

This excludes parameters that need extra arguments, like `\the\scriptfont`.

The subset comprising simple integer and dimension registers are writable as well as readable (stuff like `\tracingcommands` and `\parindent`).

4.1.1 Internal parameter values

For all the parameters in this section, it is possible to access them directly using their names as index in the `tex` table, or by using one of the functions `tex.get()` and `tex.set()`.

The exact parameters and return values differ depending on the actual parameter, and so does whether `tex.set` has any effect. For the parameters that *can* be set, it is possible to use `'global'` as the first argument to `tex.set`; this makes the assignment global instead of local.

```
tex.set (<string> n, ...)
tex.set ('global', <string> n, ...)
... = tex.get (<string> n)
```

4.1.1.1 Integer parameters

The integer parameters accept and return Lua numbers.

Read-write:



tex.adjdemerits
 tex.binoppenalty
 tex.brokenpenalty
 tex.catcodetable
 tex.clubpenalty
 tex.day
 tex.defaultthyphenchar
 tex.defaultskewchar
 tex.delimiterfactor
 tex.displaywidowpenalty
 tex.doublehyphendemerits
 tex.endlinechar
 tex.errorcontextlines
 tex.escapechar
 tex.exhyphenpenalty
 tex.fam
 tex.finalhyphendemerits
 tex.floatingpenalty
 tex.globaldefs
 tex.hangafter
 tex.hbadness
 tex.holdinginserts
 tex.hyphenpenalty
 tex.interlinepenalty
 tex.language
 tex.lastlinefit
 tex.lefthyphenmin
 tex.linepenalty
 tex.localbrokenpenalty
 tex.localinterlinepenalty
 tex.looseness
 tex.mag
 tex.maxdeadcycles
 tex.month
 tex.newlinechar
 tex.outputpenalty
 tex.pausing
 tex.pdfadjustinterwordglue
 tex.pdfadjustspacing
 tex.pdfappendkern
 tex.pdfcompresslevel
 tex.pdfdecimaldigits
 tex.pdfgamma
 tex.pdfgentounicode
 tex.pdfimageapplygamma

tex.pdfimagegamma
 tex.pdfimagehicolor
 tex.pdfimageresolution
 tex.pdfinclusionerrorlevel
 tex.pdfminorversion
 tex.pdfobjcompresslevel
 tex.pdfoutput
 tex.pdfpagebox
 tex.pdfpkresolution
 tex.pdfprependkern
 tex.pdfprotrudechars
 tex.pdftracingfonts
 tex.pdfuniqueresname
 tex.postdisplaypenalty
 tex.predisplaydirection
 tex.predisplaypenalty
 tex.pretolerance
 tex.relpentalty
 tex.righthyphenmin
 tex.savinghyphcodes
 tex.savingvdiscards
 tex.showboxbreadth
 tex.showboxdepth
 tex.time
 tex.tolerance
 tex.tracingassigns
 tex.tracingcommands
 tex.tracinggroups
 tex.tracingifs
 tex.tracinglostchars
 tex.tracingmacros
 tex.tracingnesting
 tex.tracingonline
 tex.tracingoutput
 tex.tracingpages
 tex.tracingparagraphs
 tex.tracingrestores
 tex.tracingscantokens
 tex.tracingstats
 tex.uchyph
 tex.vbadness
 tex.widowpenalty
 tex.year



Read-only:

<code>tex.deadcycles</code>	<code>tex.parshape</code>	<code>tex.spacefactor</code>
<code>tex.insertpenalties</code>	<code>tex.prevgraf</code>	

4.1.1.2 Dimension parameters

The dimension parameters accept Lua numbers (signifying scaled points) or strings (with included dimension). The result is always a number in scaled points.

Read-write:

<code>tex.boxmaxdepth</code>	<code>tex.pagebottomoffset</code>	<code>tex.pdfpageheight</code>
<code>tex.delimitershortfall</code>	<code>tex.pageheight</code>	<code>tex.pdfpagewidth</code>
<code>tex.displayindent</code>	<code>tex.pageleftoffset</code>	<code>tex.pdfpxdimen</code>
<code>tex.displaywidth</code>	<code>tex.pagerightoffset</code>	<code>tex.pdfthreadmargin</code>
<code>tex.emergencystretch</code>	<code>tex.pagetopoffset</code>	<code>tex.pdfvorigin</code>
<code>tex.hangindent</code>	<code>tex.pagewidth</code>	<code>tex.predisplaysize</code>
<code>tex.hfuzz</code>	<code>tex.parindent</code>	<code>tex.scriptspace</code>
<code>tex.hoffset</code>	<code>tex.pdfdestmargin</code>	<code>tex.splitmaxdepth</code>
<code>tex.hsize</code>	<code>tex.pdfeachlinedepth</code>	<code>tex.vfuzz</code>
<code>tex.lineskiplimit</code>	<code>tex.pdfeachlineheight</code>	<code>tex.voffset</code>
<code>tex.mathsurround</code>	<code>tex.pdffirstlineheight</code>	<code>tex.vsize</code>
<code>tex.maxdepth</code>	<code>tex.pdfhorigin</code>	
<code>tex.nulldelimiterspace</code>	<code>tex.pdflastlinedepth</code>	
<code>tex.overfullrule</code>	<code>tex.pdflinkmargin</code>	

Read-only:

<code>tex.pagedepth</code>	<code>tex.pagegoal</code>	<code>tex.prevdepth</code>
<code>tex.pagefillllstretch</code>	<code>tex.pageshrink</code>	
<code>tex.pagefillstretch</code>	<code>tex.pagestretch</code>	
<code>tex.pagefilstretch</code>	<code>tex.pagetotal</code>	

4.1.1.3 Direction parameters

The direction parameters are read-only and return a Lua string.

<code>tex.bodydir</code>	<code>tex.pagedir</code>	<code>tex.textdir</code>
<code>tex.mathdir</code>	<code>tex.pardir</code>	

4.1.1.4 Glue parameters

All glue parameters are read-only and return a userdata object that represents a `glue_spec` node.

<code>tex.abovedisplayshort-skip</code>	<code>tex.baselineskip</code>	<code>tex.belowdisplayskip</code>
<code>tex.abovedisplayskip</code>	<code>tex.belowdisplayshort-skip</code>	<code>tex.leftskip</code>
		<code>tex.lineskip</code>



<code>tex.parfillskip</code>	<code>tex.spaceskip</code>	<code>tex.topskip</code>
<code>tex.parskip</code>	<code>tex.splittopskip</code>	<code>tex.xspaceskip</code>
<code>tex.rightskip</code>	<code>tex.tabskip</code>	

4.1.1.5 Muglue parameters

All muglue parameters are read-only and return a Lua string.

<code>tex.medmuskip</code>	<code>tex.thinmuskip</code>
<code>tex.thickmuskip</code>	

4.1.1.6 Tokenlist parameters

All tokenlist parameters are read-only and return a Lua string.

<code>tex.errhelp</code>	<code>tex.everyjob</code>	<code>tex.pdfpageattr</code>
<code>tex.everycr</code>	<code>tex.everymath</code>	<code>tex.pdfpageresources</code>
<code>tex.everydisplay</code>	<code>tex.everypar</code>	<code>tex.pdfpagesattr</code>
<code>tex.everyeof</code>	<code>tex.everyvbox</code>	<code>tex.pdfpkmode</code>
<code>tex.everyhbox</code>	<code>tex.output</code>	

4.1.2 Convert commands

All ‘convert’ commands are read-only and return a Lua string. The supported commands at this moment are:

<code>tex.AlephVersion</code>	<code>tex.pdfTeXrevision</code>
<code>tex.Alephrevision</code>	<code>tex.fontname(number)</code>
<code>tex.OmegaVersion</code>	<code>tex.pdfFontname(number)</code>
<code>tex.Omegarevision</code>	<code>tex.pdfFontobjnum(number)</code>
<code>tex.eTeXVersion</code>	<code>tex.pdfFontSize(number)</code>
<code>tex.eTeXrevision</code>	<code>tex.uniformdeviate(number)</code>
<code>tex.formatname</code>	<code>tex.number(number)</code>
<code>tex.jobname</code>	<code>tex.roman numeral(number)</code>
<code>tex.luatexrevision</code>	<code>tex.pdfPageRef(number)</code>
<code>tex.luatexdatestamp</code>	<code>tex.pdfXformname(number)</code>
<code>tex.pdfNormaldeviate</code>	<code>tex.fontIdentifier(number)</code>
<code>tex.pdfTeXBanner</code>	

If you are wondering why this list looks haphazard; these are all the cases of the ‘convert’ internal command that do not require an argument, as well as the ones that require only a simple numeric value.

The special (lua-only) case of `tex.fontIdentifier` returns the `csname` string that matches a font id number (if there is one).



4.1.3 Last item commands

All ‘last item’ commands are read-only and return a number.

The supported commands at this moment are:

<code>tex.lastpenalty</code>	<code>tex.pdflastannot</code>	<code>tex.eTeXversion</code>
<code>tex.lastkern</code>	<code>tex.pdflastxpos</code>	<code>tex.currentgrouplevel</code>
<code>tex.lastskip</code>	<code>tex.pdflastypos</code>	<code>tex.currentgrouptype</code>
<code>tex.lastnodetype</code>	<code>tex.pdfrandomseed</code>	<code>tex.currentiflevel</code>
<code>tex.inputlineno</code>	<code>tex.pdflastlink</code>	<code>tex.currentiftype</code>
<code>tex.badness</code>	<code>tex.luatexversion</code>	<code>tex.currentifbranch</code>
<code>tex.pdfTeXversion</code>	<code>tex.Alephversion</code>	<code>tex.pdflastximagecol-</code>
<code>tex.pdflastobj</code>	<code>tex.Omegaversion</code>	<code>ordepth</code>
<code>tex.pdflastxform</code>	<code>tex.Alephminorversion</code>	
<code>tex.pdflastximage</code>	<code>tex.Omegaminorversion</code>	
<code>tex.pdflastximagepages</code>	<code>tex.eTeXminorversion</code>	

4.1.4 Attribute, count, dimension, skip and token registers

TeX’s attributes (`\attribute`), counters (`\count`), dimensions (`\dimen`), skips (`\skip`) and token (`\toks`) registers can be accessed and written to using two times five virtual sub-tables of the `tex` table:

<code>tex.attribute</code>	<code>tex.dimen</code>	<code>tex.toks</code>
<code>tex.count</code>	<code>tex.skip</code>	

It is possible to use the names of relevant `\attributedef`, `\countdef`, `\dimendef`, `\skipdef`, or `\toksdef` control sequences as indices to these tables:

```
tex.count.scratchcounter = 0
enormous = tex.dimen['maxdimen']
```

In this case, LuaTeX looks up the value for you on the fly. You have to use a valid `\countdef` (or `\attributedef`, or `\dimendef`, or `\skipdef`, or `\toksdef`), anything else will generate an error (the intent is to eventually also allow `<chardef tokens>` and even macros that expand into a number).

The attribute and count registers accept and return Lua numbers.

The dimension registers accept Lua numbers (in scaled points) or strings (with an included absolute dimension; `em` and `ex` and `px` are forbidden). The result is always a number in scaled points.

The token registers accept and return Lua strings. Lua strings are converted to and from token lists using `\the\toks` style expansion: all category codes are either space (10) or other (12).

The skip registers accept and return `glue_spec` userdata node objects (see the description of the node interface elsewhere in this manual).

As an alternative to array addressing, there are also accessor functions defined for all cases, for example, here is the set of possibilities for `\skip` registers:



```

tex.setskip (<number> n, <node> s)
tex.setskip (<string> s, <node> s)
tex.setskip ('global', <number> n, <node> s)
tex.setskip ('global', <string> s, <node> s)
<node> s = tex.getskip (<number> n)
<node> s = tex.getskip (<string> s)

```

In the function-based interface, it is possible to define values globally by using the string `'global'` as the first function argument.

4.1.5 Box registers

The current dimensions of `\box` registers can be read and altered using three other virtual sub-tables :

```

tex.wd
tex.ht
tex.dp

```

Boxes are indexed by number or by name. In macro packages `chardef` is normally used to refer to allocated box registers and LuaTeX is able to deal with these symbolic names.

The box size registers accept Lua numbers (in scaled points) or strings (with included dimension). The result is always a number in scaled points.

As an alternative to array addressing, there are also three sets of accessor functions defined (like above):

```

tex.setboxwd(<number> n, <number> n)
tex.setboxwd('global', <number> n, <number> n)
<number> n = tex.getboxwd(<number> n)

```

In the function-based interface, it is possible to define values globally by using the string `'global'` as the first function argument.

It is also possible to set and query actual boxes, using the node interface as defined in the `node` library:

```

tex.box

```

for array access, or

```

tex.setbox(<number> n, <node> s)
tex.setbox('global', <number> n, <node> s)
<node> n = tex.getbox(<number> n)

```

for function-based access. In the function-based interface, it is possible to define values globally by using the string `'global'` as the first function argument.

Be warned that an assignment like

```

tex.box[0] = tex.box[2]

```



does not copy the node list, it just duplicates a node pointer. If `\box2` will be cleared by T_EX commands later on, the contents of `\box0` becomes invalid as well. To prevent this from happening, always use `node.copy_list()` unless you are assigning to a temporary variable:

```
tex.box[0] = node.copy_list(tex.box[2])
```

4.1.6 Math parameters

It is possible to set and query the internal math parameters using:

```
tex.setmath(<string> n, <string> t, <number> n)
tex.setmath('global', <string> n, <string> t, <number> n)
<number> n = tex.getmath(<string> n, <string> t)
```

As before an optional first parameter of 'global' indicates a global assignment.

The first string is the parameter name minus the leading 'Umath', and the second string is the style name minus the trailing 'style'.

Just to be complete, the values for the math parameter name are:

quad	axis	operatorsize	
overbarkern	overbarrule	overbarvgap	
underbarkern	underbarrule	underbarvgap	
radicalkern	radicalrule	radicalvgap	
radicaldegreebefore	radicaldegreeafter	radicaldegreeraise	
stackvgap	stacknumup	stackdenomdown	
fractionrule	fractionnumvgap	fractionnumup	
fractiondenomvgap	fractiondenomdown	fractiondelsize	
limitabovevgap	limitabovebgap	limitabovekern	
limitdownvgap	limitdownbgap	limitdownkern	
underdelimitervgap	underdelimiterbgap		
overdelimitervgap	overdelimiterbgap		
subshiftdrop	supshiftdrop	subshiftdown	
subsupshiftdown	subtopmax	supshiftup	
subbottommin	supsubbottommax	subsupvgap	
spaceafterscript	connectoroverlapmin		
ordordspacing	ordopspacing	ordbinspacing	ordrelspacing
ordopenspacing	ordclosespacing	ordpunctspacing	ordinnerspacing
opordspacing	opopspacing	opbinspacing	oprelspacing
opopenspacing	opclosespacing	oppunctspacing	opinnerspacing
binordspacing	binopspacing	binbinspacing	binrelspacing
binopenspacing	binclosespacing	binpunctspacing	bininnerspacing
relordspacing	relopspacing	relbinspacing	relrelspacing
relopenspacing	relclosespacing	relpunctspacing	relinnerspacing
openordspacing	openopspacing	openbinspacing	openrelspacing



<code>openopenspacing</code>	<code>openclonespacing</code>	<code>openpunctspacing</code>	<code>openinnerspacing</code>
<code>closeordspacing</code>	<code>closeopspacing</code>	<code>closebinspacing</code>	<code>closerelspacing</code>
<code>closeopenspacing</code>	<code>closeclonespacing</code>	<code>closepunctspacing</code>	<code>closeinnerspacing</code>
<code>punctordspacing</code>	<code>punctopspacing</code>	<code>punctbinspacing</code>	<code>punctrelspacing</code>
<code>punctopenspacing</code>	<code>punctclonespacing</code>	<code>punctpunctspacing</code>	<code>punctinnerspacing</code>
<code>innerordspacing</code>	<code>inneropspacing</code>	<code>innerbinspacing</code>	<code>innerrelspacing</code>
<code>inneropenspacing</code>	<code>innerclonespacing</code>	<code>innerpunctspacing</code>	<code>innerinnerspacing</code>

The values for the style parameter name are:

<code>display</code>	<code>crampeddisplay</code>
<code>text</code>	<code>crampedtext</code>
<code>script</code>	<code>crampedscript</code>
<code>scriptscript</code>	<code>crampedscriptscript</code>

4.1.7 Special list heads

The virtual table `tex.lists` contains the set of internal registers that keep track of building page lists.

field	description
<code>page_ins_head</code>	circular list of pending insertions
<code>contrib_head</code>	the recent contributions
<code>page_head</code>	the page-so-far
<code>hold_head</code>	used for held-over items for next page
<code>adjust_head</code>	head of the current <code>\adjust</code> list
<code>pre_adjust_head</code>	head of the current <code>\adjust pre</code> list

4.1.8 Print functions

The `tex` table also contains the three print functions that are the major interface from Lua scripting to T_EX.

The arguments to these three functions are all stored in an in-memory virtual file that is fed to the T_EX scanner as the result of the expansion of `\directlua`.

The total amount of returnable text from a `\directlua` command is only limited by available system ram. However, each separate printed string has to fit completely in T_EX's input buffer.

The result of using these functions from inside callbacks is undefined at the moment.

4.1.8.1 `tex.print`

```
tex.print(<string> s, ...)
tex.print(<number> n, <string> s, ...)
```



```
tex.print(<table> t)
tex.print(<number> n, <table> t)
```

Each string argument is treated by T_EX as a separate input line. If there is a table argument instead of a list of strings, this has to be a consecutive array of strings to print (the first non-string value will stop the printing process). This syntax was added in 0.36.

The optional parameter can be used to print the strings using the catcode regime defined by `\catcodetable n`. If `n` is not a valid catcode table, then it is ignored, and the currently active catcode regime is used instead.

The very last string of the very last `tex.print()` command in a `\directlua` will not have the `\endlinechar` appended, all others do.

4.1.8.2 tex.sprint

```
tex.sprint(<string> s, ...)
tex.sprint(<number> n, <string> s, ...)
tex.sprint(<table> t)
tex.sprint(<number> n, <table> t)
```

Each string argument is treated by T_EX as a special kind of input line that makes it suitable for use as a partial line input mechanism:

- T_EX does not switch to the ‘new line’ state, so that leading spaces are not ignored.
- No `\endlinechar` is inserted.
- Trailing spaces are not removed.
Note that this does not prevent T_EX itself from eating spaces as result of interpreting the line. For example, in

```
before\directlua{tex.sprint("\relax")tex.sprint(" inbetween")}after
```

the space before `inbetween` will be gobbled as a result of the ‘normal’ scanning of `\relax`.

If there is a table argument instead of a list of strings, this has to be a consecutive array of strings to print (the first non-string value will stop the printing process). This syntax was added in 0.36.

4.1.8.3 tex.write

```
tex.write(<string> s, ...)
tex.write(<table> t)
```

Each string argument is treated by T_EX as a special kind of input line that makes is suitable for use as a quick way to dump information:

- All catcodes on that line are either ‘space’ (for ‘ ’) or ‘character’ (for all others).
- There is no `\endlinechar` appended.



If there is a table argument instead of a list of strings, this has to be a consecutive array of strings to print (the first non-string value will stop the printing process). This syntax was added in 0.36.

4.1.9 Helper functions

4.1.9.1 `tex.round`

```
<number> n = tex.round(<number> o)
```

Rounds Lua number `o`, and returns a number that is in the range of a valid T_EX register value. If the number starts out of range, it generates a ‘number to big’ error as well.

4.1.9.2 `tex.scale`

```
<number> n = tex.scale(<number> o, <number> delta)
<table> n = tex.scale(table o, <number> delta)
```

Multiplies the Lua numbers `o` and `delta`, and returns a rounded number that is in the range of a valid T_EX register value. In the table version, it creates a copy of the table with all numeric top-level values scaled in that manner. If the multiplied number(s) are of range, it generates ‘number to big’ error(s) as well.

4.1.9.3 `tex.definefont`

```
tex.definefont(<string> csname, <number> fontid)
tex.definefont(<boolean> global, <string> csname, <number> fontid)
```

Associates `csname` with the internal font number `fontid`. The definition is global if (and only if) `global` is specified and true (the setting of `globaldefs` is not taken into account).

4.1.10 Functions for dealing with primitives

4.1.10.1 `tex.enableprimitives`

```
tex.enableprimitives(<string> prefix, <table> primitive names)
```

This function accepts a prefix string and an array of primitive names.

For each combination of ‘prefix’ and ‘name’, the `tex.enableprimitives` first verifies that ‘name’ is an actual primitive (it must be returned by one of the `tex.extraprimitives()` calls explained above, or part of T_EX82, or `\directlua`). If it is not, `tex.enableprimitives` does nothing and skips to the next pair.



But if it is, then it will construct a `csname` variable by concatenating the ‘prefix’ and ‘name’, unless the ‘prefix’ is already the actual prefix of ‘name’. In the latter case, it will discard the ‘prefix’, and just use ‘name’.

Then it will check for the existence of the constructed `csname`. If the `csname` is currently undefined (note: that is not the same as `\relax`), it will globally define the `csname` to have the meaning: run code belonging to the primitive ‘name’. If for some reason the `csname` is already defined, it does nothing and tries the next pair.

An example:

```
tex.enableprimitives('LuaTeX', {'formatname'})
```

will define `\LuaTeXformatname` with the same intrinsic meaning as the documented primitive `\formatname`, provided that the control sequences `\LuaTeXformatname` is currently undefined.

Second example:

```
tex.enableprimitives('Omega',tex.extraprimitives ('omega'))
```

will define a whole series of `csnames` like `\Omegatextdir`, `\Omegapardir`, etc., but it will stick with `\OmegaVersion` instead of creating the doubly-prefixed `\OmegaOmegaVersion`.

Starting with version 0.39.0 (and this is why the above two functions are needed), LuaTeX in `--ini` mode contains only the T_EX82 primitives and `\directlua`, no extra primitives **at all**.

So, if you want to have all the new functionality available using their default names, as it is now, you will have to add

```
\expandafter\ifx\csname directlua\endcsname \relax \else
  \directlua {tex.enableprimitives('',tex.extraprimitives ())}
\fi
```

near the beginning of your format generation file. Or you can choose different prefixes for different subsets, as you see fit.

Calling some form of `tex.enableprimitives()` is highly important though, because if you do not, you will end up with a T_EX82-lookalike that can run lua code but not do much else. The defined `csnames` are (of course) saved in the format and will be available runtime.

4.1.10.2 tex.extraprimitives

```
<table> t = tex.extraprimitives(<string> s, ...)
```

This function returns a list of the primitives that originate from the engine(s) given by the requested string value(s). The possible values and their (current) return values are:

name values

tex	vskip	write	vsize	unhcopy	output	-	/	unskip	unvbox	boxmaxdepth	muskipdef
	string	toksdef	floatingpenalty	rightthyphenmin	voffset	escapechar	topmark	splitfirstmark			



vsplit everydisplay badness xleaders textfont showlists language mathchoice topskip
 abovedisplayshortskip underline tracinglostchars pagefillstretch unvcopy splitbotmark
 finallyhyphenemerits atopwithdelims pretolerance fi dp setlanguage ht nulldelimiterspace or
 wd pagegoal advance chardef catcode mathchar scriptscriptfont leftskip pagefilstretch delcode
 fontname lastkern belowdisplayshortskip tolerance mathopen exhyphenpenalty maxdepth
 futurelet abovewithdelims hangindent lastskip linepenalty everyjob xspaceskip globaldefs
 everypar scriptfont delimiter afterassignment firstmark lineskiplimit lineskip def fam day
 iffalse textstyle end mag box belowdisplayskip ifx errmessage exhyphenchar hss expandafter
 hfilneg the displaywidth mathsurround pagedepth looseness leaders vss ifhmode botmark
 ifinner displaystyle accent immediate ifmmode parshape meaning abovedisplayskip
 medmuskip emergencystretch rightskip mathclose hangafter hoffset aftergroup cleaders
 romannumeral hbadness mathbin showboxbreadth jobname vbadness patterns nonstopmode
 errhelp predisplaypenalty endlinechar mathinner lastbox showboxdepth postdisplaypenalty
 mathrel holdinginserts radical mathord pagetotal everycr adjdemerits halign defaultskewchar
 errorcontextlines splitmaxdepth ifcase tracingmacros moveright predisplaysize tracingrestores
 message ifhbox deadcycles interlinepenalty mathpunct lcode noboundary displayingindent
 nonscript everyhbox global penalty tracingcommands everymath nolimits noalign inputlineno
 pagestretch parskip indent dimendef widowpenalty ifvbox above spaceskip middle
 displaylimits pausing everyvbox iftrue moveleft mathop endcsname dimen ifcat clubpenalty
 splittopskip doublehyphenemerits ifdim limits ifeof insert delimitershortfall ifodd
 insertpenalties tracingpages vadjust tracingonline count ifnum edef char begingroup
 tracingparagraphs hyphenation ucode hfuzz openout leqno hyphenpenalty vcenter hfil
 thickmuskip maxdeadcycles mkern hbox overfullrule else hsize raise thinmuskip spacefactor
 input hrule left eqno parfillskip font valign dump relax prevdepth read shipout batchmode
 right skipdef setbox baselineskip special mskip endgroup uchyph binoppenalty endinput omit
 pagefillstretch overwithdelims newlinechar vfilneg time vfill span prevgraf over vbox
 tracingstats year defaultthyphenchar nullfont muskip closeout toks outer multiply
 tracingoutput parindent displaywidowpenalty unhbox lefthyphenmin vtop mathaccent
 discretionary vfuzz overline unkern showthe showbox show uppercase lowercase closein
 openin errorstopmode scrollmode skewchar hyphenchar sfcodes mathcode countdef
 mathchardef let xdef gdef long atop scriptscriptstyle scriptstyle unpenalty noindent copy
 lower kern vfil hfill hskip pageshrink crcr cr ifvoid ifvmode if number lastpenalty skip par
 vrule noexpand mark ignorespaces fontdimen divide csname scriptspace outputpenalty month
 delimiterfactor relpenalty brokenpenalty tabskip

core directlua

etex unless botmarks currentifttype pagediscards mutoglu displaywidowpenalties fontcharic
 fontchardp fontcharwd iffontchar eTeXVersion protected topmarks showgroups glueexpr
 splitfirstmarks predisplaydirection gluetomu everyeof eTeXversion scantokens clubpenalties
 savingvdiscards splitbotmarks showtokens tracingassigns dimexpr parshapedimen readline
 eTeXminorversion glueshrinkorder ifdefined currentifbranch firstmarks lastnodetype marks
 currentgrouplevel interlinepenalties muexpr unexpanded ifcsname parshapeindent
 showifs parshapelength currentgrouptype widowpenalties splitdiscards glueshrink
 gluestretch gluestretchorder numexpr interactionmode detokenize fontcharht currentiflevel



savinghyphcodes lastlinefit tracingnesting tracingscantokens tracingifs tracinggroups
 eTeXrevision
 pdftex pdfximage pdfpxdimen pdftrailer pdfuniqueresname pdfoutput pdfgentounicode pdfoutline
 pdfsetrandomseed pdfprimitive pdfoptionpdfminorversion pdfendthread pdfimagehicolor
 pdflastximagecolordepth pdfpkresolution pdfthreadmargin pdfimageapplygamma
 pdfobjcompresslevel pdfpageheight pdfreplacefont pdffirstlineheight pdfcopyfont pdfvorigin
 ifincsname pdfnormaldeviate letterspacefont pdflastximagepages pdfforcepagebox
 pdfoptionalwaysusepdfpagebox ifpdfprimitive pdfcatalog pdfignoreddimen pdfpageattr
 pdfgamma pdffontname pdfannot pdfnoligatures rightmarginkern pdflastlink pdfuniformdeviate
 pdfstartthread pdffontsize expanded pdflastxpos pdflastypos pdfrandomseed pdfimagegamma
 ifpdfabsdim pdfglyphtounicode pdffontobjnum pdftexrevision pdfcolorstack pdfxform
 pdfprotrudechars ifpdfabsnum pdfcompresslevel pdfinsertht pdfstartlink quitvmode pdfmapfile
 pdftracingfonts pdfpagebox pdfcreationdate pdfcolorstackinit pdfdest pdfmovechars
 pdflastlinedepth pdfinclusionerrorlevel pdfinfo pdfxformname pdfpagesattr pdflastannot
 pdfsave pdfhorigin pdfpagewidth pdfrefxform tagcode pdfeachlineheight pdfliteral
 pdflastximage pdfimageresolution pdfdestmargin pdfobj pdfminorversion pdfeachlinedepth
 pdftexversion pdflastxform pdfximagebbox pdfincludechars pdfsavepos pdfpkmode rcode
 pdfretval pdfdecimaldigits pdfoptionpdfinclusionerrorlevel pdfadjustspacing pdftexbanner
 pdflinkmargin pdfdraftmode pdffontexpand pdfmapline pdffontattr pdfnames pdfthread
 pdfendlink pdfrefximage pdfrefobj pdfrestore pdfsetmatrix ecode lcode leftmarginkern
 pdfpageref pdflastobj pdfinclusioncopyfonts pdfpageresources
 omega textdir popocplist rightghost omathchardef nullocplist localrightbox addbeforeocplist
 omathchar omathcode localleftbox addafterocplist bodydir localinterlinepenalty pagedir
 chardp mathdir charht charit charwd pagewidth oradical externalocp OmegaVersion ocplist
 clearocplists pardir localbrokenpenalty nullocp pageheight ocptracelevel removeafterocplist
 removebeforeocplist pushocplist ocp odelcode omathaccent leftghost odelimiter
 aleph pagebottomoffset Omegaminorversion Omegarevision Alephrevision boxdir AlephVersion
 Alephminorversion Omegaversion Alephversion pagerightoffset
 luatex Umathcloseopspacing Umathordpunctspacing Udelimiterunder luastartup
 Umathopenpunctspacing Umathordinnerspacing Umathbinclasespacing Umath-
 openinnerspacing Uoverdelimiter Umathpunctpunctspacing Umathclosepunctspacing
 Umathlimitdownbgap Umathrelordspacing Umathsupbottommin Umathstackdenomdown
 Umathfractionrule Umathpunctinnerspacing Umathcloseinnerspacing Umathopenrelspacing
 Umathsupsubbottommax Umathcloserelspacing Umathlimitdownkern Umathcharnum
 Umathinnerordspacing synctex formatname Umathrelinnerspacing Umathsubtopmax
 suppressoutererror Umathsubsupshiftdown Umathopbinspacing Umathordbinspacing
 Umathreloppacing Umathopenbinspacing Umathoverdelimiterbgap Uunderdelimiter
 Umathclosebinspacing Umathcodenum Umathpunctopenspacing Umathconnectoroverlapmin
 crampedscriptsriptstyle Umathradicaldegreeafter luatexversion Umathfractionnumup
 Umathopclasespacing Umathordclasespacing Umathoverdelimitervgap Udelcode
 Umathopenclasespacing attribute Umathsubshiftdrop Umathsubshiftdown
 Umathpunctrelspacing Umathradicaldegreeraise Umathsupshiftdrop Umathpunctclasespacing
 Umathcloseclasespacing luatexrevision Umathchar Udelimiterover Ustack Umathcode
 Udelcodenum suppresslongerror Umathbotaccent Umathaxis Umathfractionnumvgap



Umathrelclosespacing Umathpunctbinspacing luatexdatestamp Ustopdisplaymath
 crampedscriptstyle latelua crampedtextstyle Umathbinrelspacing Umathopordspacing
 attributedef Umathordordspacing Umathopenordspacing outputbox Ustopmath
 Umathpunctopspacing Umathsubsupvgap luaescapestring Umathfractiondenomvgap
 Umathradicalrule Umathunderbarrule postexhyphenchar Umathradicaldegreebefore
 Umathstacknumup Umathbinopspacing Ustartdisplaymath savecatcodetable
 Umathbinpunctspacing Uroot Umathoverbarkern Umathoperatorsizesize Uradical mathstyle
 Umathopopenspacing Umathordopenspacing Umathbininnerspacing Umathinnerrelspacing
 clearmarks Umathoverbarvgap Umathopenopenspacing Umathunderdelimiterbgap
 Umathoverbarrule crampeddisplaystyle ifabsdim Umathlimitabovebgap Umathstackvgap
 Umathinneropspacing Umathrelbinspacing Umathcloseopenspacing initcatcodetable
 nokerns Umathlimitabovekern Udelimiter Umathfractiondelsize Umathunderdelimitervgap
 Umathinnerbinspacing noligs Ustartmath Usubscript Umathaccent pagetopoffset
 catcodetable Umathspaceafterscript primitive Umathinneropenspacing Umathaccents
 Umathordopspacing Umathopenopspacing ifabsnum scantextokens suppressifcsnameerror
 suppressfontnotfounderror pageleftoffset preexhyphenchar posthyphenchar
 prehyphenchar Umathinnerinnerspacing Umathinnerpunctspacing Umathinnerclosespacing
 Umathpunctordspacing Umathcloseordspacing Umathrelpunctspacing Umathreloppspacing
 Umathrelrelspacing Umathbinopspacing Umathbinbinspacing Umathbinordspacing
 Umathopinnerspacing Umathoppunctspacing Umathoprelspacing Umathopopspacing
 Umathordrelspacing Umathsupshiftup Umathlimitdownvgap Umathlimitabovevgap
 Umathfractiondenomdown Umathradicalvgap Umathradicalkern Umathunderbarvgap
 Umathunderbarkern Umathquad Umathchardef Usuperscript ifprimitive

Note that `'luatex'` does not contain `directlua`, as that is considered to be a core primitive, along with all the T_EX82 primitives, so it is part of the list that is returned from `'core'`.

Running `tex.extraprimitives()` will give you the complete list of primitives that are not defined at LuaT_EX 0.39.0 `-ini` startup. It is exactly equivalent to `tex.extraprimitives('etex', 'pdf-tex', 'omega', 'aleph', 'luatex')`

4.1.10.3 tex.primitives

```
<table> t = tex.primitives()
```

This function returns a hash table listing all primitives that LuaT_EX knows about. The keys in the hash are primitives names, the values are tables representing tokens (see [section 4.24.2](#)). The third value is always zero.

4.2 The token library

The `token` table contains interface functions to T_EX's handling of tokens. These functions are most useful when combined with the `token_filter` callback, but they could be used standalone as well.



A token is represented in Lua as a small table. For the moment, this table consists of three numeric entries:

index	meaning	description
1	command code	this is a value between 0 and 130 (approximately)
2	command modifier	this is a value between 0 and 2^{21}
3	control sequence id	for commands that are not the result of control sequences, like letters and characters, it is zero, otherwise, it is a number pointing into the 'equivalence table'

4.2.1 `token.get_next`

```
token t = token.get_next()
```

This fetches the next input token from the current input source, without expansion.

4.2.2 `token.is_expandable`

```
<boolean> b = token.is_expandable(token t)
```

This tests if the token `t` could be expanded.

4.2.3 `token.expand`

```
token.expand()
```

If a token is expandable, this will expand one level of it, so that the first token of the expansion will now be the next token to be read by `token.get_next()`.

4.2.4 `token.is_activechar`

```
<boolean> b = token.is_activechar(token t)
```

This is a special test that is sometimes handy. Discovering whether some control sequence is the result of an active character turned out to be very hard otherwise.

4.2.5 `token.create`

```
token t = token.create(<string> csname)
token t = token.create(<number> charcode)
token t = token.create(<number> charcode, <number> catcode)
```



This is the token factory. If you feed it a string, then it is the name of a control sequence (without leading backslash), and it will be looked up in the equivalence table.

If you feed it number, then this is assumed to be an input character, and an optional second number gives its category code. This means it is possible to overrule a character's category code, with a few exceptions: the category codes 0 (escape), 9 (ignored), 13 (active), 14 (comment), and 15 (invalid) cannot occur inside a token. The values 0, 9, 14 and 15 are therefore illegal as input to `token.create()`, and active characters will be resolved immediately.

Note: unknown string sequences and never defined active characters will result in a token representing an 'undefined control sequence' with a near-random name. It is *not* possible to define brand new control sequences using `token.create`!

4.2.6 `token.command_name`

```
<string> commandname = token.command_name(<token> t)
```

This returns the name associated with the 'command' value of the token in Lua_T_EX. There is not always a direct connection between these names and primitives. For instance, all `\ifxxx` tests are grouped under `if_fest`, and the 'command modifier' defines which test is to be run.

4.2.7 `token.command_id`

```
<number> i = token.command_id(<string> commandname)
```

This returns a number that is the inverse operation of the previous command, to be used as the first item in a token table.

4.2.8 `token.csname_name`

```
<string> csname = token.csname_name(<token> t)
```

This returns the name associated with the 'equivalence table' value of the token in Lua_T_EX. It returns the string value of the command used to create the current token, or an empty string if there is no associated control sequence.

Keep in mind that there are potentially two control sequences that return the same csname string: single character control sequences and active characters have the same 'name'.

4.2.9 `token.csname_id`

```
<number> i = token.csname_id(<string> csname)
```



This returns a number that is the inverse operation of the previous command, to be used as the third item in a token table.

4.3 The node library

The `node` library contains functions that facilitate dealing with (lists of) nodes and their values. They allow you to create, alter, copy, delete, and insert LuaTeX node objects, the core objects within the typesetter.

LuaTeX nodes are represented in Lua as userdata with the metadata type `luatex.node`. The various parts within a node can be accessed using named fields.

Each node has at least the three fields `next`, `id`, and `subtype`:

- The `next` field returns the userdata object for the next node in a linked list of nodes, or nil, if there is no next node.
- The `id` indicates TeX's 'node type'. The field `id` has a numeric value for efficiency reasons, but some of the library functions also accept a string value instead of `id`.
- The `subtype` is another number. It often gives further information about a node of a particular `id`, but it is most important when dealing with 'whatsits', because they are differentiated solely based on their `subtype`.

The other available fields depend on the `id` (and for 'whatsits', the `subtype`) of the node. Further details on the various fields and their meanings are given in **chapter 88**.

Support for `unset` (alignment) nodes is partial: they can be queried and modified from Lua code, but not created.

Nodes can be compared to each other, but: you are actually comparing indices into the node memory. This means that equality tests can only be trusted under very limited conditions. It will not work correctly in any situation where one of the two nodes has been freed and/or reallocated: in that case, there will be false positives.

At the moment, memory management of nodes should still be done explicitly by the user. Nodes are not 'seen' by the Lua garbage collector, so you have to call the node freeing functions yourself when you are no longer in need of a node (list). Nodes form linked lists without reference counting, so you have to be careful that when control returns back to LuaTeX itself, you have not deleted nodes that are still referenced from a `next` pointer elsewhere, and that you did not create nodes that are referenced more than once.

There are statistics available with regards to the allocated node memory, which can be handy for tracing.

4.3.1 Node handling functions

4.3.1.1 `node.types`

```
table t = node.types()
```



This function returns an array that maps node id numbers to node type strings, providing an overview of the possible top-level `id` types.

4.3.1.2 `node.whatsits`

```
table t = node.whatsits()
```

TeX's 'whatsits' all have the same `id`. The various subtypes are defined by their `subtype`. The function is much like `node.types`, except that it provides an array of `subtype` mappings.

4.3.1.3 `node.id`

```
<number> id = node.id(<string> type)
```

This converts a single type name to its internal numeric representation.

4.3.1.4 `node.subtype`

```
<number> subtype = node.subtype(<string> type)
```

This converts a single whatsit name to its internal numeric representation (`subtype`).

4.3.1.5 `node.type`

```
<string> type = node.type(<number> id)
```

This converts a internal numeric representation to an external string representation.

4.3.1.6 `node.fields`

```
table t = node.fields(<number> id)
table t = node.fields(<number> id, <number> subtype)
```

This function returns an array of valid field names for a particular type of node. If you want to get the valid fields for a 'whatsit', you have to supply the second argument also. In other cases, any given second argument will be silently ignored.

This function accepts string `id` and `subtype` values as well.

4.3.1.7 `node.has_field`

```
<boolean> t = node.has_field(<node> n, <string> field)
```



This function returns a boolean that is only true if `n` is actually a node, and it has the field.

4.3.1.8 `node.new`

```
<node> n = node.new(<number> id)
<node> n = node.new(<number> id, <number> subtype)
```

Creates a new node. All of the new node's fields are initialized to either zero or nil except for `id` and `subtype` (if supplied). If you want to create a new `whatsit`, then the second argument is required, otherwise it need not be present. As with all node functions, this function creates a node on the $\text{T}_{\text{E}}\text{X}$ level.

This function accepts string `id` and `subtype` values as well.

4.3.1.9 `node.free`

```
node.free(<node> n)
```

Removes the node `n` from $\text{T}_{\text{E}}\text{X}$'s memory. Be careful: no checks are done on whether this node is still pointed to from a register or some `next` field: it is up to you to make sure that the internal data structures remain correct.

4.3.1.10 `node.flush_list`

```
node.flush_list(<node> n)
```

Removes the node list `n` and the complete node list following `n` from $\text{T}_{\text{E}}\text{X}$'s memory. Be careful: no checks are done on whether any of these nodes is still pointed to from a register or some `next` field: it is up to you to make sure that the internal data structures remain correct.

4.3.1.11 `node.copy`

```
<node> m = node.copy(<node> n)
```

Creates a deep copy of node `n`, including all nested lists as in the case of a `hlist` or `vlist` node. Only the `next` field is not copied.

4.3.1.12 `node.copy_list`

```
<node> m = node.copy_list(<node> n)
```

Creates a deep copy of the node list that starts at `n`.



4.3.1.13 node.hpack

```
<node> h = node.hpack(<node> n)
<node> h = node.hpack(<node> n, <number> w, <string> info)
```

This function creates a new hlist by packaging the list that begins at node **n** into a horizontal box. With only a single argument, this box is created using the natural width of its components. In the three argument form, **info** must be either **additional** or **exactly**, and **w** is the additional (**\hbox spread**) or exact (**\hbox to**) width to be used.

Caveat: at this moment, there can be unexpected side-effects to this function, like updating some of the **\marks** and **\inserts**. Also note that the content of **h** is the original node list **n**: if you call **node.free(h)** you will also free the node list itself, unless you explicitly set the **list** field to **nil** beforehand. And in a similar way, calling **node.free(n)** will invalidate **h** as well!

4.3.1.14 node.mlist_to_hlist

```
<node> h = node.mlist_to_hlist(<node> n,
                              <string> displaytype, <boolean> penalties)
```

This runs the internal mlist to hlist conversion, converting the math list in **n** into the horizontal list **h**. The interface is exactly the same as for the callback **mlist_to_hlist**.)

4.3.1.15 node.slide

```
<node> m = node.slide(<node> n)
```

Returns the last node of the node list that starts at **n**. As a side-effect, it also creates a reverse chain of **prev** pointers between nodes.

4.3.1.16 node.length

```
<number> i = node.length(<node> n)
<number> i = node.length(<node> n, <node> m)
```

Returns the number of nodes contained in the node list that starts at **n**. If **m** is also supplied it stops at **m** instead of at the end of the list. The node **m** is not counted.

4.3.1.17 node.count

```
<number> i = node.count(<number> id, <node> n)
<number> i = node.count(<number> id, <node> n, <node> m)
```



Returns the number of nodes contained in the node list that starts at `n` that have an matching `id` field. If `m` is also supplied, counting stops at `m` instead of at the end of the list. The node `m` is not counted.

This function also accept string `id`'s.

4.3.1.18 `node.traverse`

```
<node> t = node.traverse(<node> n)
```

This is an iterator that loops over the node list that starts at `n`.

4.3.1.19 `node.traverse_id`

```
<node> t = node.traverse_id(<number> id, <node> n)
```

This is an iterator that loops over all the nodes in the list that starts at `n` that have a matching `id` field.

4.3.1.20 `node.remove`

```
<node> head, current = node.remove(<node> head, <node> current)
```

This function removes the node `current` from the list following `head`. It is your responsibility to make sure it is really part of that list. The return values are the new `head` and `current` nodes. The returned `current` is the node in the calling argument, and is only passed back as a convenience (its `next` field will be cleared). The returned `head` is more important, because if the function is called with `current` equal to `head`, it will be changed.

4.3.1.21 `node.insert_before`

```
<node> head, new = node.insert_before(<node> head, <node> current, <node> new)
```

This function inserts the node `new` before `current` into the list following `head`. It is your responsibility to make sure that `current` is really part of that list. The return values are the (potentially mutated) `head` and the `new`, set up to be part of the list (with correct `next` field). If `head` is initially `nil`, it will become `new`.

4.3.1.22 `node.insert_after`

```
<node> head, new = node.insert_after(<node> head, <node> current, <node> new)
```



This function inserts the node `new` after `current` into the list following `head`. It is your responsibility to make sure that `current` is really part of that list. The return values are the `head` and the `new`, set up to be part of the list (with correct `next` field). If `head` is initially `nil`, it will become `new`.

4.3.1.23 `node.first_character`

```
<node> n = node.first_character(<node> n)
<node> n = node.first_character(<node> n, <node> m)
```

Returns the first node that is a glyph node with a subtype indicating it is a character, or `nil`.

4.3.1.24 `node.ligaturing`

```
<node> h, <node> t, <boolean> success = node.ligaturing(<node> n)
<node> h, <node> t, <boolean> success = node.ligaturing(<node> n, <node> m)
```

Apply T_EX-style ligaturing to the specified nodelist. The tail node `m` is optional. The two returned nodes `h` and `t` are the new head and tail (both `n` and `m` can change into a new ligature).

4.3.1.25 `node.kerning`

```
<node> h, <node> t, <boolean> success = node.kerning(<node> n)
<node> h, <node> t, <boolean> success = node.kerning(<node> n, <node> m)
```

Apply T_EX-style kerning to the specified nodelist. The tail node `m` is optional. The two returned nodes `h` and `t` are the head and tail (either one of these can be an inserted kern node, because special kernings with word boundaries are possible).

4.3.1.26 `node.unprotect_glyphs`

```
node.unprotect_glyphs(<node> n)
```

Subtracts 256 from all glyph node subtypes. This and the next function are helpers to convert from `characters` to `glyphs` during node processing.

4.3.1.27 `node.protect_glyphs`

```
node.protect_glyphs(<node> n)
```

Adds 256 to all glyph node subtypes in the node list starting at `n`, except that if the value is 1, it adds only 255. The special handling of 1 means that `characters` will become `glyphs` after subtraction of 256.



4.3.1.28 `node.last_node`

```
<node> n = node.last_node()
```

This function pops the last node from T_EX's 'current list'. It returns that node, or `nil` if the current list is empty.

4.3.1.29 `node.write`

```
node.write(<node> n)
```

This is an experimental function that will append a node list to T_EX's 'current list' (the node list is not deep-copied any more since version 0.38). There is no error checking yet!

4.3.2 Attribute handling

Attributes appear as linked list of userdata objects in the `attr` field of individual nodes. They can be handled individually, but it is much safer and more efficient to use the dedicated functions associated with them.

4.3.2.1 `node.has_attribute`

```
<number> v = node.has_attribute(<node> n, <number> id)
<number> v = node.has_attribute(<node> n, <number> id, <number> val)
```

Tests if a node has the attribute with number `id` set. If `val` is also supplied, also tests if the value matches `val`. It returns the value, or, if no match is found, `nil`.

4.3.2.2 `node.set_attribute`

```
node.set_attribute(<node> n, <number> id, <number> val)
```

Sets the attribute with number `id` to the value `val`. Duplicate assignments are ignored. *[needs explanation]*

4.3.2.3 `node.unset_attribute`

```
<number> v = node.unset_attribute(<node> n, <number> id, <number> val)
<number> v = node.unset_attribute(<node> n, <number> id)
```

Unsets the attribute with number `id`. If `val` is also supplied, it will only perform this operation if the value matches `val`. Missing attributes or attribute-value pairs are ignored.



If the attribute was actually deleted, returns its old value. Otherwise, returns nil.

4.4 The texio library

This library takes care of the low-level I/O interface.

4.4.1 Printing functions

4.4.1.1 `texio.write`

```
texio.write(<string> target, <string> s, ...)  
texio.write(<string> s, ...)
```

Without the `target` argument, writes all given strings to the same location(s) `TeX` writes messages to at this moment. If `\batchmode` is in effect, it writes only to the log, otherwise it writes to the log and the terminal.

The optional `target` can be one of three possibilities: `term`, `log` or `term and log`.

Note: If several strings are given, and if the first of these strings is or might be one of the targets above, the `target` must be specified explicitly to prevent Lua from interpreting the first string as the target.

4.4.1.2 `texio.write_nl`

```
texio.write_nl(<string> target, <string> s, ...)  
texio.write_nl(<string> s, ...)
```

This function behaves like `texio.write`, but make sure that the given strings will appear at the beginning of a new line. You can pass a single empty string if you only want to move to the next line.

4.5 The pdf library

This table contains the current `h` and `v` values that define the location on the output page. The values can be queried and set using scaled points as units.

```
pdf.v  
pdf.h
```

The associated function calls are

```
pdf.setv(<number> n)  
<number> n = pdf.getv()
```



```
pdf.seth(<number> n)
<number> n = pdf.geth()
```

It also holds a print function to write stuff to the pdf document that can be used from within a `\latelua` argument. This function is not to be used inside `\directlua` unless you know *exactly* what you are doing.

pdf.print

```
pdf.print(<string> s)
pdf.print(<string> type, <string> s)
```

The optional parameter can be used to mimic the behavior of `\pdfliteral`: the `type` is `direct` or `page`.

4.6 The img library

The `img` library can be used as an alternative to `\pdfximage` and `\pdfrefximage`, and the associated ‘satellite’ commands like `\pdfximagebbox`. Image objects can also be used within virtual fonts via the `image` command listed in [section 7.27.2](#).

img.new

```
<image> var = img.new()
<image> var = img.new(image_spec)
```

This function creates a userdata object of type ‘image’. The `image_spec` argument is optional. If it is given, it must be a table, and that table must contain a `filename` key. A number of other keys can also be useful, these are explained below.

You can either say

```
a=img.new()
```

followed by

```
a.filename="foo.png"
```

or you can put the file name (and some or all of the other keys) into a table directly, like so:

```
a=img.new{filename='foo.pdf',page=1}
```

The generated `<image>` userdata object allows access to a set of user-specified values as well as a set of values that are normally filled in and updated automatically by LuaTeX itself. Some of those are derived from the actual image file, others are updated to reflect the pdf output status of the object.



There is one required user-specified field: the file name ([filename](#)). It can optionally be augmented by the requested image dimensions ([width](#), [depth](#), [height](#)), user-specified image attributes ([attr](#)), the requested pdf page identifier ([page](#)), the requested boundingbox ([pagebox](#)) for pdf inclusion, the requested color space object ([colorspace](#)).

The function [img.new](#) does not access the actual image file, it just creates the `<image>` userdata object and initializes some memory structures. The `<image>` object and its internal structures are automatically garbage collected.

Once the image is scanned, all the values in the `<image>` become frozen, and you cannot change them any more.

[img.keys](#)

```
<table> keys = img.keys()
```

This function returns a list of all the possible [image_spec](#) keys, both user-supplied and automatic ones.

field name	type	description
depth	number	the image depth for LuaTeX (in scaled points)
height	number	the image height for LuaTeX (in scaled points)
width	number	the image width for LuaTeX (in scaled points)
transform	number	the image transform, integer number 0..7
attr	string	the image attributes for LuaTeX
filename	string	the image file name
stream	string	the raw stream data for an <code>/XObject /Form</code> object
page	??	the identifier for the requested image page (type is number or string, default is the number 1)
pagebox	string	the requested bounding box, one of none , media , crop , bleed , trim , art
bbox	table	table with 4 boundingbox dimensions llx , lly , urx , and ury overruling the pagebox entry
filepath	string	the full (expanded) file name of the image
colordepth	number	the number of bits used by the color space
colorspace	number	the color space object number
imagetype	string	one of pdf , png , jpg , jbig2 , or nil
objnum	number	the pdf image object number
index	number	the pdf image name suffix
pages	number	the total number of available pages
xsize	number	the natural image width
ysize	number	the natural image height
xres	number	the horizontal natural image resolution (in dpi)
yres	number	the vertical natural image resolution (in dpi)

A running (undefined) dimension in [width](#), [height](#), or [depth](#) is represented as [nil](#) in Lua, so if you want to load an image at its ‘natural’ size, you do not have to specify any of those three fields.



The `stream` parameter allows to fabricate an `/XObject /Form` object from a string giving the stream contents, e. g., for a filled rectangle:

```
a.stream = "0 0 20 10 re f"
```

When writing the image, an `/XObject /Form` object is created, like with embedded pdf file writing. The object is written out only once. The `stream` key requires that also the `bbox` table is given. The `stream` key conflicts with the `filename` key. The `transform` key works as usual also with `stream`.

The `bbox` key needs a table with four boundingbox values, e. g.:

```
a.bbox = {"30bp", 0, "225bp", "200bp"}
```

This replaces and overrules any given `pagebox` value; with given `bbox` the box dimensions coming with an embedded pdf file are ignored. The `xsize` and `ysize` dimensions are set accordingly, when the image is scaled. The `bbox` parameter is ignored for non-pdf images.

The `transform` allows to mirror and rotate the image in steps of 90 deg. The default value 0 gives an unmirrored, unrotated image. Values 1–3 give counterclockwise rotation by 90, 180, or 270 degrees, whereas with values 4–7 the image is first mirrored and then rotated counterclockwise by 90, 180, or 270 degrees. The `transform` operation gives the same visual result as if you would externally preprocess the image by a graphics tool and then use it by LuaTeX. If a pdf file to be embedded already contains a `/Rotate` specification, the rotation result is the combination of the `/Rotate` rotation followed by the `transform` operation.

`img.scan`

```
<image> var = img.scan(<image> var)
<image> var = img.scan(image_spec)
```

When you say `img.scan(a)` for a new image, the file is scanned, and variables such as `xsize`, `ysize`, image `type`, number of `pages`, and the resolution are extracted. Each of the `width`, `height`, `depth` fields are set up according to the image dimensions, if they were not given an explicit value already. An image file will never be scanned more than once for a given image variable. With all subsequent `img.scan(a)` calls only the dimensions are again set up (if they have been changed by the user in the meantime).

For ease of use, you can do right-away a

```
<image> a = img.scan { filename = "foo.png" }
```

without a prior `img.new`.

Nothing is written yet at this point, so you can do `a=img.scan`, retrieve the available info like image width and height, and then throw away `a` again by saying `a=nil`. In that case no image object will be reserved in the PDF, and the used memory will be cleaned up automatically.



`img.copy`

```
<image> var = img.copy(<image> var)
<image> var = img.copy(image_spec)
```

If you say `a = b`, then both variables point to the same `<image>` object. if you want to write out an image with different sizes, you can do `b=img.copy(a)`.

Afterwards, `a` and `b` still reference the same actual image dictionary, but the dimensions for `b` can now be changed from their initial values that were just copies from `a`.

`img.write`

```
<image> var = img.write(<image> var)
<image> var = img.write(image_spec)
```

By `img.write(a)` a pdf object number is allocated, and a whatsit node of subtype `pdf_refximage` is generated and put into the output list. By this the image `a` is placed into the page stream, and the image file is written out into an image stream object after the shipping of the current page is finished.

Again you can do a terse call like

```
img.write { filename = "foo.png" }
```

The `<image>` variable is returned in case you want it for later processing.

`img.immediatewrite`

```
<image> var = img.immediatewrite(<image> var)
<image> var = img.immediatewrite(image_spec)
```

By `img.immediatewrite(a)` a pdf object number is allocated, and the image file for image `a` is written out immediately into the pdf file as an image stream object (like with `\immediate\pdfximage`). The object number of the image stream dictionary is then available by the `objnum` key. No `pdf_refximage` whatsit node is generated. You will need a `img.write(a)` or `img.node(a)` call to let the image appear on the page, or reference it by another trick; else you will have a dangling image object in the pdf file.

Also here you can do a terse call like

```
a = img.immediatewrite { filename = "foo.png" }
```

The `<image>` variable is returned and you will most likely need it.

`img.node`



```
<node> n = img.node(<image> var)
<node> n = img.node(image_spec)
```

This function allocates a pdf object number and returns a whatsit node of subtype `pdf_refximage`, filled with the image parameters `width`, `height`, `depth`, and `objnum`. Also here you can do a terse call like:

```
n = img.node { filename = "foo.png" }
```

This example outputs an image:

```
node.write(img.node{filename="foo.png"})
```

`img.types`

```
<table> types = img.types()
```

This function returns a list with the supported image file type names, currently these are `pdf`, `png`, `jpg`, and `jbig2`.

`img.bboxes`

```
<table> bboxes = img.bboxes()
```

This function returns a list with the supported pdf page box names, currently these are `media`, `crop`, `bleed`, `trim`, and `art` (all in lowercase letters).

4.7 The `mplib` library

The MetaPost library interface registers itself in the table `mplib`. It is based on MPlib version 1.202.

4.7.1 `mplib.new`

To create a new MetaPost instance, call

```
<mpinstance> mp = mplib.new({...})
```

This creates the `mp` instance object. The argument hash can have a number of different fields, as follows:

name	type	description	default
<code>error_line</code>	number	error line width	79
<code>print_line</code>	number	line length in ps output	100
<code>main_memory</code>	number	total memory size	5000
<code>hash_size</code>	number	hash size	16384



<code>param_size</code>	number	max. active macro parameters	150
<code>max_in_open</code>	number	max. input file nestings	10
<code>random_seed</code>	number	the initial random seed	variable
<code>interaction</code>	string	the interaction mode, one of <code>batch</code> , <code>errorstop</code> , <code>nonstop</code> , <code>scroll</code> , <code>errorstop</code>	
<code>ini_version</code>	boolean	the <code>-ini</code> switch	true
<code>mem_name</code>	string	<code>--mem</code>	<code>plain</code>
<code>job_name</code>	string	<code>--jobname</code>	<code>mpout</code>
<code>find_file</code>	function	a function to find files	only local files

The `find_file` function should be of this form:

```
<string> found = finder (<string> name, <string> mode, <string> type)
```

with:

name the requested file

mode the file mode: `r` or `w`

type the kind of file, one of: `mp`, `mem`, `tfm`, `map`, `pfb`, `enc`

Return either the full pathname of the found file, or `nil` if the file cannot be found.

4.7.2 mp:statistics

You can request statistics with:

```
<table> stats = mp:statistics()
```

This function returns the vital statistics for an MPlib instance. There are four fields, giving the maximum number of used items in each of the four statically allocated object classes:

<code>main_memory</code>	number	memory size
<code>hash_size</code>	number	hash size
<code>param_size</code>	number	simultaneous macro parameters
<code>max_in_open</code>	number	input file nesting levels

4.7.3 mp:execute

You can ask the MetaPost interpreter to run a chunk of code by calling

```
local rettable = mp:execute('metapost language chunk')
```



for various bits of MetaPost language input. Be sure to check the `rettable.status` (see below) because when a fatal MetaPost error occurs the MPLib instance will become unusable thereafter.

Generally speaking, it is best to keep your chunks small, but beware that all chunks have to obey proper syntax, like each of them is a small file. For instance, you cannot split a single statement over multiple chunks.

In contrast with the normal standalone `mpost` command, there is *no* implied ‘input’ at the start of the first chunk.

4.7.4 `mp:finish`

```
local rettable = mp:finish()
```

If for some reason you want to stop using an MPLib instance while processing is not yet actually done, you can call `mp:finish`. Eventually, used memory will be freed and open files will be closed by the Lua garbage collector, but an explicit `mp:finish` is the only way to capture the final part of the output streams.

4.7.5 Result table

The return value of `mp:execute` and `mp:finish` is a table with a few possible keys (only `status` is always guaranteed to be present).

<code>log</code>	string	output to the ‘log’ stream
<code>term</code>	string	output to the ‘term’ stream
<code>error</code>	string	output to the ‘error’ stream (only used for ‘out of memory’)
<code>status</code>	number	the return value: 0=good, 1=warning, 2=errors, 3=fatal error
<code>fig</code>	table	an array of generated figures (if any)

When `status` equals 3, you should stop using this MPLib instance immediately, it is no longer capable of processing input.

If it is present, each of the entries in the `fig` array is a userdata representing a figure object, and each of those has a number of object methods you can call:

<code>boundingbox</code>	function	returns the bounding box, as an array of 4 values
<code>postscript</code>	function	return a string that is the ps output of the <code>fig</code> . this function accepts two optional integer arguments for specifying the values of <code>prologues</code> (first argument) and <code>procset</code> (second argument)
<code>svg</code>	function	return a string that is the svg output of the <code>fig</code> . this function accepts an optional integer arguments for specifying the value of <code>prologues</code>
<code>objects</code>	function	returns the actual array of graphic objects in this <code>fig</code>
<code>copy_objects</code>	function	returns a deep copy of the array of graphic objects in this <code>fig</code>
<code>filename</code>	function	the filename this <code>fig</code> ’s PostScript output would have written to in standalone mode



width	function	the <code>charwd</code> value
height	function	the <code>charht</code> value
depth	function	the <code>chardp</code> value
italcorr	function	the <code>charit</code> value
charcode	function	the (rounded) <code>charcode</code> value

NOTE: you can call `fig:objects()` only once for any one `fig` object!

When the boundingbox represents a ‘negated rectangle’, i.e. when the first set of coordinates is larger than the second set, the picture is empty.

Graphical objects come in various types that each have a different list of accessible values. The types are: `fill`, `outline`, `text`, `start_clip`, `stop_clip`, `start_bounds`, `stop_bounds`, `special`.

There is helper function (`mplib.fields(obj)`) to get the list of accessible values for a particular object, but you can just as easily use the tables given below).

All graphical objects have a field `type` that gives the object type as a string value, that not explicit mentioned in the tables. In the following, `numbers` are PostScript points represented as a floating point number, unless stated otherwise. Field values that are of `table` are explained in the next section.

4.7.5.1 fill

path	table	the list of knots
htap	table	the list of knots for the reversed trajectory
pen	table	knots of the pen
color	table	the object’s color
linejoin	number	line join style (bare number)
miterlimit	number	miterlimit
prescript	string	the prescript text
postscript	string	the postscript text

The entries `htap` and `pen` are optional.

There is helper function (`mplib.pen_info(obj)`) that returns a table containing a bunch of vital characteristics of the used pen (all values are floats):

width	number	width of the pen
rx	number	x scale
sx	number	xy multiplier
sy	number	yx multiplier
ry	number	y scale
tx	number	x offset
ty	number	y offset



4.7.5.2 outline

path	table	the list of knots
pen	table	knots of the pen
color	table	the object's color
linejoin	number	line join style (bare number)
miterlimit	number	miterlimit
linecap	number	line cap style (bare number)
dash	table	representation of a dash list
prescript	string	the prescript text
postscript	string	the postscript text

The entry `dash` is optional.

4.7.5.3 text

text	string	the text
font	string	font tfm name
dsize	number	font size
color	table	the object's color
width	number	
height	number	
depth	number	
transform	table	a text transformation
prescript	string	the prescript text
postscript	string	the postscript text

4.7.5.4 special

prescript	string	special text
-----------	--------	--------------

4.7.5.5 start_bounds, start_clip

path	table	the list of knots
------	-------	-------------------

4.7.5.6 stop_bounds, stop_clip

Here are no fields available.



4.7.6 Subsidiary table formats

4.7.6.1 Paths and pens

Paths and pens (that are really just a special type of paths as far as MPLib is concerned) are represented by an array where each entry is a table that represents a knot.

<code>left_type</code>	string	when present: 'endpoint', but usually absent
<code>right_type</code>	string	like <code>left_type</code>
<code>x_coord</code>	number	X coordinate of this knot
<code>y_coord</code>	number	Y coordinate of this knot
<code>left_x</code>	number	X coordinate of the precontrol point of this knot
<code>left_y</code>	number	Y coordinate of the precontrol point of this knot
<code>right_x</code>	number	X coordinate of the postcontrol point of this knot
<code>right_y</code>	number	Y coordinate of the postcontrol point of this knot

There is one special case: pens that are (possibly transformed) ellipses have an extra string-valued key `type` with value `elliptical` besides the array part containing the knot list.

4.7.6.2 Colors

A color is an integer array with 0, 1, 3 or 4 values:

0	marking only	no values
1	greyscale	one value in the range (0,1), 'black' is 0
3	rgb	three values in the range (0,1), 'black' is 0,0,0
4	cmyk	four values in the range (0,1), 'black' is 0,0,0,1

If the color model of the internal object was `uninitialized`, then it was initialized to the values representing 'black' in the colorspace `defaultcolormodel` that was in effect at the time of the `shipout`.

4.7.6.3 Transforms

Each transform is a six-item array.

1	number	represents x
2	number	represents y
3	number	represents xx
4	number	represents yx
5	number	represents xy
6	number	represents yy

Note that the translation (index 1 and 2) comes first. This differs from the ordering in PostScript, where the translation comes last.



4.7.6.4 Dashes

Each `dash` is two-item hash, using the same model as PostScript for the representation of the dashlist. `dashes` is an array of ‘on’ and ‘off’, values, and `offset` is the phase of the pattern.

`dashes` hash an array of on-off numbers
`offset` number the starting offset value

4.7.7 Character size information

These functions find the size of a glyph in a defined font. The `fontname` is the same name as the argument to `infont`; the `char` is a glyph id in the range 0 to 255; the returned `w` is in AFM units.

4.7.7.1 `mp.char_width`

```
<number> w = mp.char_width(<string> fontname, <number> char)
```

4.7.7.2 `mp.char_height`

```
<number> w = mp.char_height(<string> fontname, <number> char)
```

4.7.7.3 `mp.char_depth`

```
<number> w = mp.char_depth(<string> fontname, <number> char)
```

4.8 The callback library

This library has functions that register, find and list callbacks.

```
id, error = callback.register(<string> callback_name,function callback_func)
id, error = callback.register(<string> callback_name,nil)
id, error = callback.register(<string> callback_name,false)
```

where the `callback_name` is a predefined callback name, see below. The function returns the internal `id` of the callback or `nil`, if the callback could not be registered. In the latter case, `error` contains an error message, otherwise it is `nil`.

LuaTeX internalizes the callback function in such a way that it does not matter if you redefine a function accidentally.

Callback assignments are always global. You can use the special value `nil` instead of a function for clearing the callback.



For some minor speed gain, you can assign the boolean `false` to the non-file related callbacks, doing so will prevent LuaTeX from executing whatever it would execute by default (when no callback function is registered at all). Be warned: this may cause all sorts of grief unless you know *exactly* what you are doing! This functionality is present since version 0.38.

Currently, callbacks are not dumped into the format file.

```
table info = callback.list()
```

The keys in the table are the known callback names, the value is a boolean where `true` means that the callback is currently set (active).

```
function f = callback.find(callback_name)
```

If the callback is not set, `callback.find` returns `nil`.

4.8.1 File discovery callbacks

4.8.1.1 find_read_file and find_write_file

Your callback function should have the following conventions:

```
<string> actual_name = function (number id_number, <string> asked_name)
```

Arguments:

`id_number`

This number is zero for the log or `\input` files. For TeX's `\read` or `\write` the number is incremented by one, so `\read0` becomes 1.

`asked_name`

This is the user-supplied filename, as found by `\input`, `\openin` or `\openout`.

Return value:

`actual_name`

This is the filename used. For the very first file that is read in by TeX, you have to make sure you return an `actual_name` that has an extension and that is suitable for use as `jobname`. If you don't, you will have to manually fix the name of the log file and output file after LuaTeX is finished, and an eventual format filename will become mangled. That is because these file names depend on the `jobname`.

You have to return `nil` if the file cannot be found.

4.8.1.2 find_font_file

Your callback function should have the following conventions:



```
<string> actual_name = function (<string> asked_name)
```

The `asked_name` is an otf or tfm font metrics file.

Return `nil` if the file cannot be found.

4.8.1.3 find_output_file

Your callback function should have the following conventions:

```
<string> actual_name = function (<string> asked_name)
```

The `asked_name` is the pdf or dvi file for writing.

4.8.1.4 find_format_file

Your callback function should have the following conventions:

```
<string> actual_name = function (<string> asked_name)
```

The `asked_name` is a format file for reading (the format file for writing is always opened in the current directory).

4.8.1.5 find_vf_file

Like `find_font_file`, but for virtual fonts. This applies to both Aleph's ovf files and traditional Knuthian vf files.

4.8.1.6 find_ocp_file

Like `find_font_file`, but for ocp files.

4.8.1.7 find_map_file

Like `find_font_file`, but for map files.

4.8.1.8 find_enc_file

Like `find_font_file`, but for enc files.

4.8.1.9 find_sfd_file

Like `find_font_file`, but for subfont definition files.



4.8.1.10 find_pk_file

Like `find_font_file`, but for pk bitmap files. The argument `name` is a bit special in this case. Its form is

```
<base res>dpi/<fontname>.<actual res>pk
```

So you may be asked for `600dpi/manfnt.720pk`. It is up to you to find a ‘reasonable’ bitmap file to go with that specification.

4.8.1.11 find_data_file

Like `find_font_file`, but for embedded files (`\pdfobj file '...'`).

4.8.1.12 find_opentype_file

Like `find_font_file`, but for OpenType font files.

4.8.1.13 find_truetype_file and find_type1_file

Your callback function should have the following conventions:

```
<string> actual_name = function (<string> asked_name)
```

The `asked_name` is a font file. This callback is called while LuaT_EX is building its internal list of needed font files, so the actual timing may surprise you. Your return value is later fed back into the matching `read_file` callback.

Strangely enough, `find_type1_file` is also used for OpenType (otf) fonts.

4.8.1.14 find_image_file

Your callback function should have the following conventions:

```
<string> actual_name = function (<string> asked_name)
```

The `asked_name` is an image file. Your return value is used to open a file from the harddisk, so make sure you return something that is considered the name of a valid file by your operating system.



4.8.2 File reading callbacks

4.8.2.1 open_read_file

Your callback function should have the following conventions:

```
<table> env = function (<string> file_name)
```

Argument:

file_name

The filename returned by a previous `find_read_file` or the return value of `kpse.find_file()` if there was no such callback defined.

Return value:

env

This is a table containing at least one required and one optional callback function for this file. The required field is `reader` and the associated function will be called once for each new line to be read, the optional one is `close` that will be called once when LuaTeX is done with the file.

LuaTeX never looks at the rest of the table, so you can use it to store your private per-file data. Both the callback functions will receive the table as their only argument.

4.8.2.1.1 reader

LuaTeX will run this function whenever it needs a new input line from the file.

```
function(<table> env)
    return <string> line
end
```

Your function should return either a string or `nil`. The value `nil` signals that the end of file has occurred, and will make TeX call the optional `close` function next.

4.8.2.1.2 close

LuaTeX will run this optional function when it decides to close the file.

```
function(<table> env)
    return
end
```

Your function should not return any value.



4.8.2.2 General file readers

There is a set of callbacks for the loading of binary data files. These all use the same interface:

```
function(<string> name)
    return <boolean> success, <string> data, <number> data_size
end
```

The `name` will normally be a full path name as it is returned by either one of the file discovery callbacks or the internal version of `kpse.find_file()`.

`success`

Return false when a fatal error occurred (e.g. when the file cannot be found, after all).

`data`

The bytes comprising the file.

`data_size`

The length of the `data`, in bytes.

Return an empty string and zero if the file was found but there was a reading problem.

The list of functions is as follows:

<code>read_font_file</code>	ofm or tfm files
<code>read_vf_file</code>	virtual fonts
<code>read_ocp_file</code>	ocp files
<code>read_map_file</code>	map files
<code>read_enc_file</code>	encoding files
<code>read_sfd_file</code>	subfont definition files
<code>read_pk_file</code>	pk bitmap files
<code>read_data_file</code>	embedded files (<code>\pdfobj file ...</code>)
<code>read_truetype_file</code>	TrueType font files
<code>read_type1_file</code>	Type1 font files
<code>read_opentype_file</code>	OpenType font files

4.8.3 Data processing callbacks

4.8.3.1 process_input_buffer

This callback allows you to change the contents of the line input buffer just before LuaTeX actually starts looking at it.

```
function(<string> buffer)
    return <string> adjusted_buffer
end
```



If you return `nil`, LuaTeX will pretend like your callback never happened. You can gain a small amount of processing time from that.

This callback does not replace any internal code.

4.8.3.2 `token_filter`

This callback allows you to replace the way LuaTeX fetches lexical tokens.

```
function()  
    return <table> token  
end
```

The calling convention for this callback is a bit more complicated than for most other callbacks. The function should either return a Lua table representing a valid to-be-processed token or tokenlist, or something else like `nil` or an empty table.

If your Lua function does not return a table representing a valid token, it will be immediately called again, until it eventually does return a useful token or tokenlist (or until you reset the callback value to `nil`). See the description of `token` for some handy functions to be used in conjunction with this callback.

If your function returns a single usable token, then that token will be processed by LuaTeX immediately. If the function returns a token list (a table consisting of a list of consecutive token tables), then that list will be pushed to the input stack at a completely new token list level, with its token type set to ‘inserted’. In either case, the returned token(s) will not be fed back into the callback function.

Setting this callback to `false` has no effect (because otherwise nothing would happen, forever).

4.8.4 Node list processing callbacks

The description of nodes and node lists is in **chapter 88**.

4.8.4.1 `buildpage_filter`

This callback is called whenever LuaTeX is ready to move stuff to the main vertical list. You can use this callback to do specialized manipulation of the page building stage like imposition or column balancing.

```
function(<string> extrainfo)  
end
```

The string `extrainfo` gives some additional information about what TeX’s state is with respect to the ‘current page’. The possible values are:

value	explanation
<code>alignment</code>	a (partial) alignment is being added
<code>after_output</code>	an output routine has just finished
<code>box</code>	a typeset box is being added



<code>new_graf</code>	the beginning of a new paragraph
<code>vmode_par</code>	<code>\par</code> was found in vertical mode
<code>hmode_par</code>	<code>\par</code> was found in horizontal mode
<code>insert</code>	an insert is added
<code>penalty</code>	a penalty (in vertical mode)
<code>before_display</code>	immediately before a display starts
<code>after_display</code>	a display is finished
<code>end</code>	LuaTeX is terminating (it's all over)

This callback does not replace any internal code.

4.8.4.2 `pre_linebreak_filter`

This callback is called just before LuaTeX starts converting a list of nodes into a stack of `\hboxes`. The removal of a possible final skip and the subsequent insertion of `\parfillskip` has not happened yet at that moment.

```
function(<node> head, <string> groupcode)
    return true | false | <node> newhead
end
```

The string called `groupcode` identifies the nodelist's context within TeX's processing. The range of possibilities is given in the table below, but not all of those can actually appear in `pre_linebreak_filter`, some are for the `hpack_filter` and `vpack_filter` callbacks that will be explained in the next two paragraphs.

value	explanation
<code><empty></code>	main vertical list
<code>hbox</code>	<code>\hbox</code> in horizontal mode
<code>adjusted_hbox</code>	<code>\hbox</code> in vertical mode
<code>vbox</code>	<code>\vbox</code>
<code>vtop</code>	<code>\vtop</code>
<code>align</code>	<code>\halign</code> or <code>\valign</code>
<code>disc</code>	discretionaries
<code>insert</code>	packaging an insert
<code>vcenter</code>	<code>\vcenter</code>
<code>local_box</code>	<code>\localleftbox</code> or <code>\localrightbox</code>
<code>split_off</code>	top of a <code>\vsplit</code>
<code>split_keep</code>	remainder of a <code>\vsplit</code>
<code>align_set</code>	alignment cell
<code>fin_row</code>	alignment row

This callback does not replace any internal code.



4.8.4.3 linebreak_filter

This callback replaces LuaTeX's line breaking algorithm.

```
function(<node> head, <boolean> is_display)
    return <node> newhead
end
```

The returned node is the head of the list that will be added to the main vertical list, the boolean argument is true if this paragraph is interrupted by a following math display.

If you return something that is not a `<node>`, LuaTeX will apply the internal linebreak algorithm on the list that starts at `<head>`.

Setting this callback to `false` is possible, but dangerous, because it is possible you will end up in an unfixable 'deadcycles loop'.

4.8.4.4 post_linebreak_filter

This callback is called just after LuaTeX has converted a list of nodes into a stack of `\hboxes`.

```
function(<node> head, <string> groupcode)
    return true | false | <node> newhead
end
```

This callback does not replace any internal code.

4.8.4.5 hpack_filter

This callback is called when TeX is ready to start boxing some horizontal mode material. Math items and line boxes are ignored at the moment.

```
function(<node> head, <string> groupcode, <number> size, <string> packtype)
    return true | false | <node> newhead
end
```

The `packtype` is either `additional` or `exactly`. If `additional`, then the `size` is a `\hbox spread ...` argument. If `exactly`, then the `size` is a `\hbox to ...`. In both cases, the number is in scaled points.

This callback does not replace any internal code.

4.8.4.6 vpack_filter

This callback is called when TeX is ready to start boxing some vertical mode material. Math displays are ignored at the moment.



This function is very similar to the `hpack_filter`. Besides the fact that it is called at different moments, there is an extra variable that matches T_EX's `\maxdepth` setting.

```
function(<node> head, <string> groupcode, <number> size, <string> packtype,
<number> maxdepth)
    return true | false | <node> newhead
end
```

This callback does not replace any internal code.

4.8.4.7 `pre_output_filter`

This callback is called when T_EX is ready to start boxing the box 255 for `\output`.

```
function(<node> head, <string> groupcode, <number> size, <string> packtype,
<number> maxdepth)
    return true | false | <node> newhead
end
```

This callback does not replace any internal code.

4.8.4.8 `hyphenate`

```
function(<node> head, <node> tail)
end
```

No return values. This callback has to insert discretionary nodes in the node list it receives. Setting this callback to `false` will prevent the internal discretionary insertion pass.

4.8.4.9 `ligaturing`

```
function(<node> head, <node> tail)
end
```

No return values. This callback has to apply ligaturing to the node list it receives.

You don't have to worry about return values because the `head` node that is passed on to the callback is guaranteed not to be a `glyph_node` (if need be, a temporary node will be prepended), and therefore it cannot be affected by the mutations that take place. After the callback, the internal value of the 'tail of the list' will be recalculated.

The `next` of `head` is guaranteed to be non-nil.

The `next` of `tail` is guaranteed be nil, and therefore the second callback argument can often be ignored. It is provided for orthogonality, and because it can sometimes be handy when special processing has to take place.



Setting this callback to `false` will prevent the internal ligature creation pass.

4.8.4.10 kerning

```
function(<node> head, <node> tail) end
```

No return values. This callback has to apply kerning between the nodes in the node list it receives. See [ligaturing](#) for calling conventions.

Setting this callback to `false` will prevent the internal kern insertion pass.

4.8.4.11 mlist_to_hlist

This callback replaces LuaT_EX's math list to node list conversion algorithm.

```
function(<node> head, <string> displaytype, <boolean> need_penalties)
    return <node> newhead
end
```

The returned node is the head of the list that will be added to the vertical or horizontal list, the string argument is either 'text' or 'display' depending on the current math mode, the boolean argument is `true` if penalties have to be inserted in this list, `false` otherwise.

Setting this callback to `false` is bad, it will almost certainly result in an endless loop.

4.8.5 Information reporting callbacks

4.8.5.1 start_run

```
function()
```

This callback replaces the code that prints LuaT_EX's banner. Note that for successful use, this callback has to be set in the lua initialization file, otherwise it will be seen only after the run has already started.

4.8.5.2 stop_run

```
function()
```

This callback replaces the code that prints LuaT_EX's statistics and 'output written to' messages.

4.8.5.3 start_page_number

```
function()
```



Replaces the code that prints the [and the page number at the begin of `\shipout`. This callback will also override the printing of box information that normally takes place when `\tracingoutput` is positive.

4.8.5.4 stop_page_number

```
function()
```

Replaces the code that prints the] at the end of `\shipout`.

4.8.5.5 show_error_hook

```
function()  
    return  
end
```

This callback is run from inside the T_EX error function, and the idea is to allow you to do some extra reporting on top of what T_EX already does (none of the normal actions are removed). You may find some of the values in the `status` table useful.

This callback does not replace any internal code.

message

is the formal error message T_EX has given to the user. (the line after the '!').

indicator

is either a filename (when it is a string) or a location indicator (a number) that can mean lots of different things like a token list id or a `\read` number.

lineno

is the current line number.

This is an investigative item for 'testing the water' only. The final goal is the total replacement of T_EX's error handling routines, but that needs lots of adjustments in the web source because T_EX deals with errors in a somewhat haphazard fashion. This is why the exact definition of `indicator` is not given here.

4.8.6 Font-related callbacks

4.8.6.1 define_font

```
function(<string> name, <number> size, <number> id) return <table> font end
```

The string `name` is the filename part of the font specification, as given by the user.

The number `size` is a bit special:



- if it is positive, it specifies an ‘at size’ in scaled points.
- if it is negative, its absolute value represents a ‘scaled’ setting relative to the designsize of the font.

The internal structure of the `font` table that is to be returned is explained in **chapter 77**. That table is saved internally, so you can put extra fields in the table for your later Lua code to use.

Setting this callback to `false` is pointless as it will prevent font loading completely but will nevertheless generate errors.

4.9 The lua library

This library contains one read-only item:

```
<string> s = lua.version
```

This returns a LuaTeX version identifier string. The value is currently `lua.version`, but it is soon to be replaced by something more elaborate.

4.9.1 Lua bytecode registers

Lua registers can be used to communicate Lua functions across Lua chunks. The accepted values for assignments are functions and `nil`. Likewise, the retrieved value is either a function or `nil`.

```
lua.bytecode[n] = function () .. end
lua.bytecode[n]()
```

The contents of the `lua.bytecode` array is stored inside the format file as actual Lua bytecode, so it can also be used to preload Lua code.

Note: The function must not contain any upvalues. Currently, functions containing upvalues can be stored (and their upvalues are set to `nil`), but this is an artifact of the current Lua implementation and thus subject to change.

The associated function calls are

```
function f = lua.getbytecode(<number> n)
lua.setbytecode(<number> n, <function> f)
```

Note: Since a Lua file loaded using `loadfile(filename)` is essentially an anonymous function, a complete file can be stored in a bytecode register like this:

```
lua.bytecode[n] = loadfile(filename)
```

Now all definitions (functions, variables) contained in the file can be created by executing this bytecode register:

```
lua.bytecode[n]()
```



Note that the path of the file is stored in the Lua bytecode to be used in stack backtraces and therefore dumped into the format file if above code is used in `iniTEX`. If it contains private information, i.e. the user name, this information is then contained in the format file as well. This should be kept in mind when preloading files into a bytecode register in `iniTEX`.

4.9.2 Lua chunk name registers

There is an array of 65536 (0–65535) potential chunk names for use with the `\directlua` and `\latelua` primitives.

```
lua.name[<number> n] = <string> s
<string> s = lua.name[<number n>]
```

If you want to unset a lua name, you can assign `nil` to it.

4.10 The kpse library

This library provides two separate, but nearly identical interfaces to the kpathsea file search functionality: there is a ‘normal’ procedural interface that shares its kpathsea instance with LuaT_EX itself, and an object oriented interface that is completely on its own. The object oriented interface and `kpse.new` have been added in LuaT_EX 0.37.

4.10.1 `kpse.set_program_name` and `kpse.new`

Before the search library can be used at all, its database has to be initialized. There are three possibilities, two of which belong to the procedural interface.

First, when LuaT_EX is used to typeset documents, this initialization happens automatically and the kpathsea executable and program names are set to `luatex` (that is, unless explicitly prohibited by the user’s startup script. See [section 3.13.1](#) for more details).

Second, in T_EX Lua mode, the initialization has to be done explicitly via the `kpse.set_program_name` function, which sets the kpathsea executable (and optionally program) name.

```
kpse.set_program_name(<string> name)
kpse.set_program_name(<string> name, <string> progname)
```

The second argument controls the use of the ‘dotted’ values in the `texmf.cnf` configuration file, and defaults to the first argument.

Third, if you prefer the object oriented interface, you have to call a different function. It has the same arguments, but it returns a userdata variable.

```
local kpathsea = kpse.new(<string> name)
local kpathsea = kpse.new(<string> name, <string> progname)
```



Apart from these two functions, the calling conventions of the interfaces are identical. Depending on the chosen interface, you either call `kpse.find_file()` or `kpathsea:find_file()`, with identical arguments and return vales.

4.10.2 find_file

The most often used function in the library is `find_file`:

```
<string> f = kpse.find_file(<string> filename)
<string> f = kpse.find_file(<string> filename, <string> ftype)
<string> f = kpse.find_file(<string> filename, <boolean> mustexist)
<string> f = kpse.find_file(<string> filename, <string> ftype, <boolean>
mustexist)
<string> f = kpse.find_file(<string> filename, <string> ftype, <number> dpi)
```

Arguments:

`filename`

the name of the file you want to find, with or without extension.

`ftype`

maps to the `-format` argument of `kpsewhich`. The supported `ftype` values are the same as the ones supported by the standalone `kpsewhich` program:



'gf'	'texpool'
'pk'	'TeX system sources'
'bitmap font'	'PostScript header'
'tfm'	'Troff fonts'
'afm'	'type1 fonts'
'base'	'vf'
'bib'	'dvips config'
'bst'	'ist'
'cnf'	'truetype fonts'
'ls-R'	'type42 fonts'
'fmt'	'web2c files'
'map'	'other text files'
'mem'	'other binary files'
'mf'	'misc fonts'
'mfpool'	'web'
'mft'	'cweb'
'mp'	'enc files'
'mppool'	'cmap files'
'MetaPost support'	'subfont definition files'
'ocp'	'opentype fonts'
'ofm'	'pdftex config'
'opl'	'lig files'
'otp'	'texmfscripts'
'ovf'	'lua',
'ovp'	'font feature files',
'graphic/figure'	'cid maps',
'tex'	'mlbib',
'TeX system documentation'	'mlbst',

The default type is `tex`. Note: this is different from `kpsewhich`, which tries to deduce the file type itself from looking at the supplied extension. The last four types: 'font feature files', 'cid maps', 'mlbib', 'mlbst' were new additions in LuaTeX 0.40.2.

`mustexist`

is similar to `kpsewhich`'s `-must-exist`, and the default is `false`. If you specify `true` (or a non-zero integer), then the `kpse` library will search the disk as well as the `ls-R` databases.

`dpi`

This is used for the size argument of the formats `pk`, `gf`, and `bitmap font`.

4.10.3 `init_prog`

Extra initialization for programs that need to generate bitmap fonts.

```
kpse.init_prog(<string> prefix, <number> base_dpi, <string> mfmode)
kpse.init_prog(<string> prefix, <number> base_dpi, <string> mfmode, <string>
fallback)
```



4.10.4 readable_file

Test if an (absolute) file name is a readable file

```
<string> f = kpse.readable_file(<string> name)
```

The return value is the actual absolute filename you should use, because the disk name is not always the same as the requested name, due to aliases and system-specific handling under e.g. msdos.

Returns `nil` if the file does not exist or is not readable.

4.10.5 expand_path

Like `kpsewhich`'s `-expand-path`:

```
<string> r = kpse.expand_path(<string> s)
```

4.10.6 expand_var

Like `kpsewhich`'s `-expand-var`:

```
<string> r = kpse.expand_var(<string> s)
```

4.10.7 expand_braces

Like `kpsewhich`'s `-expand-braces`:

```
<string> r = kpse.expand_braces(<string> s)
```

4.10.8 show_path

Like `kpsewhich`'s `-show-path`:

```
<string> r = kpse.show_path(<string> ftype)
```

4.10.9 var_value

Like `kpsewhich`'s `-var-value`:

```
<string> r = kpse.var_value(<string> s)
```



4.11 The status library

This contains a number of run-time configuration items that you may find useful in message reporting, as well as an iterator function that gets all of the names and values as a table.

```
<table> info = status.list()
```

The keys in the table are the known items, the value is the current value. Almost all of the values in `status` are fetched through a metatable at run-time whenever they are accessed, so you cannot use `pairs` on `status`, but you *can* use `pairs` on `info`, of course. If you do not need the full list, you can also ask for a single item by using its name as an index into `status`.

The current list is:

key	explanation
pdf_gone	written pdf bytes
pdf_ptr	not yet written pdf bytes
dvi_gone	written dvi bytes
dvi_ptr	not yet written dvi bytes
total_pages	number of written pages
output_file_name	name of the pdf or dvi file
log_name	name of the log file
banner	terminal display banner
var_used	variable (one-word) memory in use
dyn_used	token (multi-word) memory in use
str_ptr	number of strings
init_str_ptr	number of iniT _E X strings
max_strings	maximum allowed strings
pool_ptr	string pool index
init_pool_ptr	iniT _E X string pool index
pool_size	current size allocated for string characters
node_mem_usage	a string giving insight into currently used nodes
var_mem_max	number of allocated words for nodes
fix_mem_max	number of allocated words for tokens
fix_mem_end	maximum number of used tokens
cs_count	number of control sequences
hash_size	size of hash
hash_extra	extra allowed hash
font_ptr	number of active fonts
max_in_stack	max used input stack entries
max_nest_stack	max used nesting stack entries
max_param_stack	max used parameter stack entries
max_buf_stack	max used buffer position
max_save_stack	max used save stack entries
stack_size	input stack size



<code>nest_size</code>	nesting stack size
<code>param_size</code>	parameter stack size
<code>buf_size</code>	current allocated size of the line buffer
<code>save_size</code>	save stack size
<code>obj_ptr</code>	max pdf object pointer
<code>obj_tab_size</code>	pdf object table size
<code>pdf_os_cnr</code>	max pdf object stream pointer
<code>pdf_os_objidx</code>	pdf object stream index
<code>pdf_dest_names_ptr</code>	max pdf destination pointer
<code>dest_names_size</code>	pdf destination table size
<code>pdf_mem_ptr</code>	max pdf memory used
<code>pdf_mem_size</code>	pdf memory size
<code>largest_used_mark</code>	max referenced marks class
<code>filename</code>	name of the current input file
<code>inputid</code>	numeric id of the current input
<code>linenumber</code>	location in the current input file
<code>lasterrorstring</code>	last error string
<code>luabytecodes</code>	number of active Lua bytecode registers
<code>luabytecode_bytes</code>	number of bytes in Lua bytecode registers
<code>luastate_bytes</code>	number of bytes in use by Lua interpreters
<code>output_active</code>	<code>true</code> if the <code>\output</code> routine is active
<code>callbacks</code>	total number of executed callbacks so far
<code>indirect_callbacks</code>	number of those that were themselves a result of other callbacks (e.g. file readers)
<code>luatex_version</code>	the luatex version number (added in 0.38)
<code>luatex_revision</code>	the luatex revision string (added in 0.38)
<code>ini_version</code>	<code>true</code> if this is an iniT _E X run (added in 0.38)

4.12 The texconfig table

This is a table that is created empty. A startup Lua script could fill this table with a number of settings that are read out by the executable after loading and executing the startup file.

key	type	default	explanation
<code>kpse_init</code>	boolean	<code>true</code>	<code>false</code> totally disables kpathsea initialisation, and enables interpretation of the following numeric key–value pairs. (only ever unset this if you implement <i>all</i> file find callbacks!)
<code>shell_escape</code>	string	<code>'f'</code>	Use <code>'y'</code> or <code>'t'</code> or <code>'1'</code> to enable <code>\write 18</code> unconditionally, <code>'p'</code> to enable the commands that are listed in <code>shell_escape_commands</code> (new in 0.37)
<code>shell_escape_commands</code>	string		Comma-separated list of command names that may be executed by <code>\write 18</code> even if <code>shell_escape</code> is set to <code>'p'</code> . Do <i>not</i> use spaces around commas,



separate any required command arguments by using a space, and use the ASCII double quote (") for any needed argument or path quoting (new in 0.37)

string_vacancies	number	75000	cf. web2c docs
pool_free	number	5000	cf. web2c docs
max_strings	number	15000	cf. web2c docs
strings_free	number	100	cf. web2c docs
nest_size	number	50	cf. web2c docs
max_in_open	number	15	cf. web2c docs
param_size	number	60	cf. web2c docs
save_size	number	4000	cf. web2c docs
stack_size	number	300	cf. web2c docs
dvi_buf_size	number	16384	cf. web2c docs
error_line	number	79	cf. web2c docs
half_error_line	number	50	cf. web2c docs
max_print_line	number	79	cf. web2c docs
ocp_list_size	number	1000	cf. web2c docs
ocp_buf_size	number	1000	cf. web2c docs
ocp_stack_size	number	1000	cf. web2c docs
hash_extra	number	0	cf. web2c docs
pk_dpi	number	72	cf. web2c docs
trace_file_names	boolean	true	<code>false</code> disables T _E X's normal file open-close feedback (the assumption is that callbacks will take care of that)
file_line_error	boolean	false	do <code>file:line</code> style error messages
halt_on_error	boolean	false	abort run on the first encountered error
formatname	string		if no format name was given on the commandline, this key will be tested first instead of simply quitting
jobname	string		if no input file name was given on the commandline, this key will be tested first instead of simply giving up

Note: the numeric values that match web2c parameters are only used if `kpse_init` is explicitly set to `false`. In all other cases, the normal values from `texmf.cnf` are used.

4.13 The font library

The font library provides the interface into the internals of the font system, and also it contains helper functions to load traditional T_EX font metrics formats. Other font loading functionality is provided by the `fontloader` library that will be discussed in the next section.

4.13.1 Loading a tfm file

```
<table> fnt = font.read_tfm(<string> name, <number> s)
```



The number is a bit special:

- if it is positive, it specifies an ‘at size’ in scaled points.
- if it is negative, its absolute value represents a ‘scaled’ setting relative to the designsize of the font.

The internal structure of the metrics font table that is returned is explained in **chapter 77**.

4.13.2 Loading a vf file

```
<table> vf_fnt = font.read_vf(<string> name, <number> s)
```

The meaning of the number `s`, and the format of the returned table is similar to the one returned by the `read_tfm()` function.

4.13.3 The fonts array

The whole table of T_EX fonts is accessible from Lua using a virtual array.

```
font.fonts[n] = { ... }  
<table> f = font.fonts[n]
```

See **chapter 77** for the structure of the tables. Because this is a virtual array, you cannot call `pairs` on it, but see below for the `font.each` iterator.

The two metatable functions implementing the virtual array are:

```
<table> f = font.getfont(<number> n)  
font.setfont(<number> n, <table> f)
```

Also note the following: assignments can only be made to fonts that have already been defined in T_EX, but have not been accessed *at all* since that definition. This limits the usability of the write access to `font.fonts` quite a lot, a less stringent ruleset will likely be implemented later.

4.13.4 Checking a font’s status

You can test for the status of a font by calling this function:

```
<boolean> f = font.frozen(<number> n)
```

The return value is one of true (unassignable), false (can be changed) or nil (not a valid font at all).

4.13.5 Defining a font directly

You can define your own font into `font.fonts` by calling this function:



```
<number> i = font.define(<table> f)
```

The return value is the internal id number of the defined font (the index into `font.fonts`). If the font creation fails, an error is raised. The table is a font structure, as explained in [chapter 77](#).

4.13.6 Projected next font id

```
number i = font.nextid();
```

This returns the font id number that would be returned by a `font.define` call if it was executed at this spot in the code flow. This is useful for virtual fonts that need to reference themselves.

4.13.7 Currently active font

```
<number> i = font.current();  
font.current(<number> i);
```

This gets or sets the currently used font number.

4.13.8 Maximum font id

```
<number> i = font.max();
```

This is the largest used index in `font.fonts`.

4.13.9 Iterating over all fonts

```
for i,v in font.each() do  
    ...  
end
```

This is an iterator over each of the defined T_EX fonts. The first returned value is the index in `font.fonts`, the second the font itself, as a Lua table. The indices are listed incrementally, but they do not always form an array of consecutive numbers: in some cases there can be holes in the sequence.

4.14 The fontloader library (0.36)

This library used to be called ‘fontforge’. The library is still available under that name for now, but that alias will be removed starting with beta [0.41.0](#)



4.14.1 Getting quick information on a font

```
local info = fontloader.info('filename')
```

This function returns either `nil`, or a `table`, or an array of small tables (in the case of a TrueType collection). The returned table(s) will contain six fairly interesting information items from the font(s) defined by the file:

key	type	explanation
fontname	string	the PostScript name of the font
fullname	string	the formal name of the font
famillyname	string	the family name this font belongs to
weight	string	a string indicating the color value of the font
version	string	the internal font version
italicangle	float	the slant angle

Getting information through this function is (sometimes much) more efficient than loading the font properly, and is therefore handy when you want to create a dictionary of available fonts based on a directory contents.

4.14.2 Loading an OpenType or TrueType file

If you want to use an OpenType font, you have to get the metric information from somewhere. Using the `fontloader` library, the basic way to get that information is thus:

```
function load_font (filename)
  local metrics = nil
  local font = fontloader.open(filename)
  if font then
    metrics = fontloader.to_table(font)
    fontloader.close(font)
  end
  return metrics
end

myfont = load_font('/opt/tex/texmf/fonts/data/arial.ttf')
```

The main function call is

```
f, w = fontloader.open('filename')
```

The first return value is a table representation of the font. The second return value is a table containing any warnings and errors reported by fontloader while opening the font. In normal typesetting, you would probably ignore the second argument, but it can be useful for debugging purposes.



For TrueType collections (when filename ends in 'ttc'), you have to use a second string argument to specify which font you want from the collection. Use one of the `fullname` strings that are returned by `fontloader.info` for that.

```
f, w = fontloader.open('filename', 'fullname')
```

The font file is parsed and partially interpreted by the font loading routines from FontForge. The file format can be OpenType, TrueType, TrueType Collection, cff, or Type1.

There are a few advantages to this approach compared to reading the actual font file ourselves:

- The font is automatically re-encoded, so that the `metrics` table for TrueType and OpenType fonts is using Unicode for the character indices.
- Many features are pre-processed into a format that is easier to handle than just the bare tables would be.
- PostScript-based OpenType fonts do not store the character height and depth in the font file, so the character boundingbox has to be calculated in some way.
- In the future, it may be interesting to allow Lua scripts access to the font program itself, perhaps even creating or changing the font.

4.14.3 Applying a ‘feature file’

You can apply a ‘feature file’ to a loaded font:

```
fontloader.apply_featurefile(f, 'filename')
```

A ‘feature file’ is a textual representation of the features in an OpenType font. See http://www.adobe.com/devnet/opentype/afdko/topic_feature_file_syntax.html and <http://fontforge.sourceforge.net/featurefile.html> for a more detailed description of feature files.

4.14.4 Applying an ‘afm file’

You can apply an ‘afm file’ to a loaded font:

```
fontloader.apply_afmfile(f, 'filename')
```

An afm file is a textual representation of (some of) the meta information in a Type1 font. See http://www.adobe.com/devnet/font/pdfs/5004.AFM_Spec.pdf for more information about afm files.

Note: If you `fontloader.open()` a Type1 file named `font.pfb`, the library will automatically search for and apply `font.afm` if it exists in the same directory as the file `font.pfb`. In that case, there is no need for an explicit call to `apply_afmfile()`.



4.15 Fontloader font tables

4.15.1 Table types

4.15.1.1 Top-level

The top-level keys in the returned table are (the explanations in this part of the documentation are not yet finished):

key	type	explanation
table_version	number	indicates the metrics version (currently 0.3)
fontname	string	PostScript font name
fullname	string	official font name
familyname	string	family name
weight	string	weight indicator
copyright	string	copyright information
filename	string	the file name
version	string	font version
italicangle	float	slant angle
units_per_em	number	1000 for PostScript-based fonts, usually 2048 for TrueType
ascent	number	height of ascender in units_per_em
descent	number	depth of descender in units_per_em
upos	float	
uwidth	float	
uniqueid	number	
glyphcnt	number	number of included glyphs
glyphs	array	
glyphmax	number	maximum used index the glyphs array
hasvmetrics	number	
onlybitmaps	number	
serifcheck	number	
isserif	number	
issans	number	
encodingchanged	number	
strokedfont	number	
use_typo_metrics	number	
weight_width_slope_only	number	
head_optimized_for_cleartype	number	
uni_interp	enum	unset , none , adobe , greek , japanese , trad_chinese , simp_chinese , korean , ams
origname	string	the file name, as supplied by the user



map	table
private	table
xuid	string
pfminfo	table
names	table
cidinfo	table
subfonts	array
comments	string
fontlog	string
cvt_names	string
anchor_classes	table
ttf_tables	table
ttf_tab_saved	table
kerns	table
vkerns	table
texdata	table
lookups	table
gpos	table
gsub	table
sm	table
features	table
mm	table
chosenname	string
macstyle	number
fondname	string
design_size	number
fontstyle_id	number
fontstyle_name	table
design_range_bottom	number
design_range_top	number
strokewidth	float
mark_classes	array
mark_class_names	array
creationtime	number
modificationtime	number
os2_version	number
sfd_version	number
math	table
validation_state	table
horiz_base	table
vert_base	table
extrema_bound	number



4.15.1.2 Glyph items

The `glyphs` is an array containing the per-character information (quite a few of these are only present if nonzero).

key	type	explanation
name	string	the glyph name
unicode	number	unicode code point, or -1
boundingbox	array	array of four numbers
width	number	only for horizontal fonts
vwidth	number	only for vertical fonts
lsidebearing	number	only if nonzero and not equal to boundingbox[1]
class	string	one of "automatic", "none", "base", "ligature", "mark", "component"
kerns	array	only for horizontal fonts, if set
vkerns	array	only for vertical fonts, if set
dependents	array	linear array of glyph name strings, only if nonempty
lookups	table	only if nonempty
ligatures	table	only if nonempty
anchors	table	only if set
comment	string	only if set
tex_height	number	only if set
tex_depth	number	only if set
italic_correction	number	only if set
top_accent	number	only if set
is_extended_shape	number	only if this character is part of a math extension list
altuni	table	alternate Unicode items
vert_variants	table	
horiz_variants	table	
mathkern	table	

The `kerns` and `vkerns` are linear arrays of small hashes:

key	type	explanation
char	string	
off	number	
lookup	string	

The `lookups` is a hash, based on lookup subtable names, with the value of each key inside that a linear array of small hashes:

key	type	explanation
type	enum	<code>position</code> , <code>pair</code> , <code>substitution</code> , <code>alternate</code> , <code>multiple</code> , <code>ligature</code> , <code>lcaret</code> , <code>kerning</code> , <code>vkerning</code> , <code>anchors</code> , <code>contextpos</code> , <code>contextsub</code> , <code>chainpos</code> , <code>chainsub</code> , <code>reversesub</code> , <code>max</code> , <code>kernback</code> , <code>vkernback</code>
specification	table	extra data



For the first seven values of `type`, there can be additional sub-information, stored in the sub-table `specification`:

value	type	explanation
position	table	a table of the <code>offset_specs</code> type
pair	table	one string: <code>paired</code> , and an array of one or two <code>offset_specs</code> tables: <code>offsets</code>
substitution	table	one string: <code>variant</code>
alternate	table	one string: <code>components</code>
multiple	table	one string: <code>components</code>
ligature	table	two strings: <code>components</code> , <code>char</code>
lcaret	array	linear array of numbers

Tables for `offset_specs` contain up to four number-valued fields: `x` (a horizontal offset), `y` (a vertical offset), `h` (an advance width correction) and `v` (an advance height correction).

The `ligatures` is a linear array of small hashes:

key	type	explanation
lig	table	uses the same substructure as a single <code>possub</code> item
char	string	
components	array	linear array of named components
ccnt	number	

The `anchor` table is indexed by a string signifying the anchor type, which is one of

key	type	explanation
mark	table	placement mark
basechar	table	mark for attaching combining items to a base char
baselig	table	mark for attaching combining items to a ligature
basemark	table	generic mark for attaching combining items to connect to
centry	table	cursive entry point
cexit	table	cursive exit point

The content of these is an short array of defined anchors, with the entry keys being the anchor names. For all except `baselig`, the value is a single table with this definition:

key	type	explanation
x	number	x location
y	number	y location
ttf_pt_index	number	truetype point index, only if given

For `baselig`, the value is a small array of such anchor sets sets, one for each constituent item of the ligature.

For clarification, an anchor table could for example look like this :



```

['anchor'] = {
  ['basemark'] = {
    ['Anchor-7'] = { ['x']=170, ['y']=1080 }
  },
  ['mark'] = {
    ['Anchor-1'] = { ['x']=160, ['y']=810 },
    ['Anchor-4'] = { ['x']=160, ['y']=800 }
  },
  ['baselig'] = {
    [1] = { ['Anchor-2'] = { ['x']=160, ['y']=650 } },
    [2] = { ['Anchor-2'] = { ['x']=460, ['y']=640 } }
  }
}

```

4.15.1.3 map table

The top-level map is a list of encoding mappings. Each of those is a table itself.

key	type	explanation
enccount	number	
encmax	number	
backmax	number	
remap	table	
map	array	non-linear array of mappings
backmap	array	non-linear array of backward mappings
enc	table	

The [remap](#) table is very small:

key	type	explanation
firstenc	number	
lastenc	number	
infont	number	

The [enc](#) table is a bit more verbose:

key	type	explanation
enc_name	string	
char_cnt	number	
char_max	number	
unicode	array	of Unicode position numbers
psnames	array	of PostScript glyph names
builtin	number	
hidden	number	
only_1byte	number	



has_1byte	number	
has_2byte	number	
is_unicodebmp	number	only if nonzero
is_unicodedefull	number	only if nonzero
is_custom	number	only if nonzero
is_original	number	only if nonzero
is_compact	number	only if nonzero
is_japanese	number	only if nonzero
is_korean	number	only if nonzero
is_tradchinese	number	only if nonzero [name?]
is_simplechinese	number	only if nonzero
low_page	number	
high_page	number	
iconv_name	string	
iso_2022_escape	string	

4.15.1.4 private table

This is the font's private PostScript dictionary, if any. Keys and values are both strings.

4.15.1.5 cidinfo table

key	type	explanation
registry	string	
ordering	string	
supplement	number	
version	number	

4.15.1.6 pfminfo table

The `pfminfo` table contains most of the OS/2 information:

key	type	explanation
pfmset	number	
winascent_add	number	
windescent_add	number	
hheadascent_add	number	
hheaddescent_add	number	
typoascent_add	number	
typodescent_add	number	
subsuper_set	number	
panose_set	number	
hheadset	number	



vheadset	number	
pfmfamily	number	
weight	number	
width	number	
avgwidth	number	
firstchar	number	
lastchar	number	
fstype	number	
linegap	number	
vlinegap	number	
hhead_ascent	number	
hhead_descent	number	
hhead_descent	number	
os2_typoascent	number	
os2_typodescent	number	
os2_typolinegap	number	
os2_winascent	number	
os2_windescent	number	
os2_subxsize	number	
os2_subysize	number	
os2_subxoff	number	
os2_subyoff	number	
os2_supxsize	number	
os2_supysize	number	
os2_supxoff	number	
os2_supyoff	number	
os2_strikeysize	number	
os2_strikeypos	number	
os2_family_class	number	
os2_xheight	number	
os2_capheight	number	
os2_defaultchar	number	
os2_breakchar	number	
os2_vendor	string	
codepages	table	A two-number array of encoded code pages
unicoderanges	table	A four-number array of encoded unicode ranges
panose	table	

The [panose](#) subtable has exactly 10 string keys:

key	type	explanation
familytype	string	Values as in the OpenType font specification: Any , No Fit , Text and Display , Script , Decorative , Pictorial
serifstyle	string	See the OpenType font specification for values
weight	string	id.



proportion	string	id.
contrast	string	id.
strokevariation	string	id.
armstyle	string	id.
letterform	string	id.
midline	string	id.
xheight	string	id.

4.15.1.7 names table

Each item has two top-level keys:

key	type	explanation
lang	string	language for this entry
names	table	

The [names](#) keys are the actual TrueType name strings. The possible keys are:

key	explanation
copyright	
family	
subfamily	
uniqueid	
fullname	
version	
postscriptname	
trademark	
manufacturer	
designer	
descriptor	
venderurl	
designerurl	
license	
licenseurl	
idontknow	
preffamilyname	
prefmodifiers	
compatfull	
sampletext	
cidfindfontname	
wwsfamily	
wwssubfamily	



4.15.1.8 anchor_classes table

The anchor_classes classes:

key	type	explanation
name	string	a descriptive id of this anchor class
lookup	string	
type	string	one of mark , mkmk , curs , mklg

4.15.1.9 gpos table

Th gpos table has one array entry for each lookup. (The [gpos_](#) prefix is somewhat redundant.)

key	type	explanation
type	string	one of gpos_single , gpos_pair , gpos_cursive , gpos_mark2base , gpos_mark2ligature , gpos_mark2mark , gpos_context , gpos_contextchain
flags	table	
name	string	
features	array	
subtables	array	

The flags table has a true value for each of the lookup flags that is actually set:

key	type	explanation
r2l	boolean	
ignorebaseglyphs	boolean	
ignoreligatures	boolean	
ignorecombiningmarks	boolean	

The features subtable of gpos has:

key	type	explanation
tag	string	
scripts	table	
ismac	number	(only if true)

The scripts table within features has:

key	type	explanation
script	string	
langs	array of strings	

The subtables table has:

key	type	explanation
name	string	



suffix	string	(only if used)
anchor_classes	number	(only if used)
vertical_kerning	number	(only if used)
kernclass	table	(only if used)

The kernclass with subtables table has:

key	type	explanation
firsts	array of strings	
seconds	array of strings	
lookup	string	associated lookup
offsets	array of numbers	

4.15.1.10 gsub table

This has identical layout to the [gpos](#) table, except for the type:

key	type	explanation
type	string	one of gsub_single , gsub_multiple , gsub_alternate , gsub_ligature , gsub_context , gsub_contextchain , gsub_reversecontextchain

4.15.1.11 ttf_tables and ttf_tab_saved tables

key	type	explanation
tag	string	
len	number	
maxlen	number	
data	number	

4.15.1.12 sm table

key	type	explanation
type	string	one of "indic", "context", "lig", "simple", "insert", "kern"
lookup	string	
flags	table	a set of boolean values with the keys : "vert", "descending", "always"
classes	table	an array of named classes
state	table	

The [state](#) table has:

key	type	explanation
next	number	
flags	number	



context	table	A small table that has 'mark' and 'cur' as possible keys, with the values being lookup names. Only applies if the <code>sm.type = context</code> .
insert	table	A small table that has 'mark' and 'cur' as possible keys, with the values strings. Only applies if the <code>sm.type = insert</code> .
kern	table	A small array with kern data. Only applies if the <code>sm.type = kern</code> .

4.15.1.13 features table

key	type	explanation
feature	number	
ismutex	number	
default_setting	number	
strid	number	
featname	table	A set of mac names. macnames are like oftnames except that they also have an 'enc' field
settings	table	

The `settings` are:

key	type	explanation
setting	number	
strid	number	
initially_enabled	number	
setname	table	A set of mac names. macnames are like oftnames except that they also have an 'enc' field

4.15.1.14 mm table

key	type	explanation
axes	table	array of axis names
instance_count	number	
positions	table	array of instance positions (#axes * instances)
defweights	table	array of default weights for instances
cdv	string	
ndv	string	
axismaps	table	
named_instance_count	number	
named_instances	table	
apple	number	

The `axismaps`:



key	type	explanation
blends	table	an array of blend points
designs	table	an array of design values
min	number	
def	number	
max	number	
axisnames	table	a set of mac names

The `named_instances` is an array of instances:

key	type	explanation
names	table	a set of mac names
coords	table	an array of coordinates

4.15.1.15 math table

ScriptPercentScaleDown
 ScriptScriptPercentScaleDown
 DelimitedSubFormulaMinHeight
 DisplayOperatorMinHeight
 MathLeading
 AxisHeight
 AccentBaseHeight
 FlattenedAccentBaseHeight
 SubscriptShiftDown
 SubscriptTopMax
 SubscriptBaselineDropMin
 SuperscriptShiftUp
 SuperscriptShiftUpCramped
 SuperscriptBottomMin
 SuperscriptBaselineDropMax
 SubSuperscriptGapMin
 SuperscriptBottomMaxWithSubscript
 SpaceAfterScript
 UpperLimitGapMin
 UpperLimitBaselineRiseMin
 LowerLimitGapMin
 LowerLimitBaselineDropMin
 StackTopShiftUp
 StackTopDisplayStyleShiftUp
 StackBottomShiftDown
 StackBottomDisplayStyleShiftDown
 StackGapMin
 StackDisplayStyleGapMin



StretchStackTopShiftUp
 StretchStackBottomShiftDown
 StretchStackGapAboveMin
 StretchStackGapBelowMin
 FractionNumeratorShiftUp
 FractionNumeratorDisplayStyleShiftUp
 FractionDenominatorShiftDown
 FractionDenominatorDisplayStyleShiftDown
 FractionNumeratorGapMin
 FractionNumeratorDisplayStyleGapMin
 FractionRuleThickness
 FractionDenominatorGapMin
 FractionDenominatorDisplayStyleGapMin
 SkewedFractionHorizontalGap
 SkewedFractionVerticalGap
 OverbarVerticalGap
 OverbarRuleThickness
 OverbarExtraAscender
 UnderbarVerticalGap
 UnderbarRuleThickness
 UnderbarExtraDescender
 RadicalVerticalGap
 RadicalDisplayStyleVerticalGap
 RadicalRuleThickness
 RadicalExtraAscender
 RadicalKernBeforeDegree
 RadicalKernAfterDegree
 RadicalDegreeBottomRaisePercent
 MinConnectorOverlap

4.15.1.16 validation_state table

key	explanation
bad_ps_fontname	
bad_glyph_table	
bad_cff_table	
bad_metrics_table	
bad_cmap_table	
bad_bitmaps_table	
bad_gx_table	
bad_ot_table	
bad_os2_version	
bad_sfnt_header	



4.15.1.17 `horiz_base` and `vert_base` table

key	type	explanation
<code>tags</code>	table	an array of script list tags
<code>scripts</code>	table	

The `scripts` subtable:

key	type	explanation
<code>baseline</code>	table	
<code>default_baseline</code>	number	
<code>lang</code>	table	

The `lang` subtable:

key	type	explanation
<code>tag</code>	string	a script tag
<code>ascent</code>	number	
<code>descent</code>	number	
<code>features</code>	table	

The `features` points to an array of tables with the same layout except that in those nested tables, the tag represents a language.

4.15.1.18 `altuni` table

An array of alternate Unicode values. Inside that array are hashes with:

key	type	explanation
<code>unicode</code>	number	
<code>variant</code>	number	

4.15.1.19 `vert_variants` and `horiz_variants` table

key	type	explanation
<code>variants</code>	string	
<code>italic_correction</code>	number	
<code>parts</code>	table	

The `parts` table is an array of smaller tables:

key	type	explanation
<code>component</code>	string	
<code>extender</code>	number	
<code>start</code>	number	



end	number
advance	number

4.15.1.20 mathkern table

key	type	explanation
top_right	table	
bottom_right	table	
top_left	table	
bottom_left	table	

Each of the subtables is an array of small hashes with two keys:

key	type	explanation
height	number	
kern	number	

4.15.1.21 kerns table

Substructure is identical to the per-glyph subtable.

4.15.1.22 vkerns table

Substructure is identical to the per-glyph subtable.

4.15.1.23 texdata table

key	type	explanation
type	string	unset , text , math , mathext
params	array	22 font numeric parameters

4.15.1.24 lookups table

Top-level [lookups](#) is quite different from the ones at character level. The keys in this hash are strings, the values the actual lookups, represented as dictionary tables.

key	type	explanation
type	number	
format	enum	one of glyphs , class , coverage , reversecoverage
tag	string	
current_class	array	
before_class	array	



<code>after_class</code>	array	
<code>rules</code>	array	an array of rule items

Rule items have one common item and one specialized item:

key	type	explanation
<code>lookups</code>	array	a linear array of lookup names
<code>glyph</code>	array	only if the parent's format is <code>glyph</code>
<code>class</code>	array	only if the parent's format is <code>glyph</code>
<code>coverage</code>	array	only if the parent's format is <code>glyph</code>
<code>reversecoverage</code>	array	only if the parent's format is <code>glyph</code>

A glyph table is:

key	type	explanation
<code>names</code>	string	
<code>back</code>	string	
<code>fore</code>	string	

A class table is:

key	type	explanation
<code>current</code>	array	of numbers
<code>before</code>	array	of numbers
<code>after</code>	array	of numbers

coverage:

key	type	explanation
<code>current</code>	array	of strings
<code>before</code>	array	of strings
<code>after</code>	array	of strings

reversecoverage:

key	type	explanation
<code>current</code>	array	of strings
<code>before</code>	array	of strings
<code>after</code>	array	of strings
<code>replacements</code>	string	

4.16 The lang library

This library provides the interface to Lua_T_EX's structure representing a language, and the associated functions.




```
<language> l = lang.new()
<language> l = lang.new(<number> id)
```

This function creates a new userdata object. An object of type `<language>` is the first argument to most of the other functions in the `lang` library. These functions can also be used as if they were object methods, using the colon syntax.

Without an argument, the next available internal id number will be assigned to this object. With argument, an object will be created that links to the internal language with that id number.

```
<number> n = lang.id(<language> l)
```

returns the internal `\language` id number this object refers to.

```
<string> n = lang.hyphenation(<language> l)
lang.hyphenation(<language> l, <string> n)
```

Either returns the current hyphenation exceptions for this language, or adds new ones. The syntax of the string is explained in the next chapter, **section 6.36.3**.

```
lang.clear_hyphenation(<language> l)
```

Clears the exception dictionary for this language.

```
<string> n = lang.clean(<string> o)
```

Creates a hyphenation key from the supplied hyphenation value. The syntax of the argument string is explained in the next chapter, **section 6.36.3**. This function is useful if you want to do something else based on the words in a dictionary file, like spell-checking.

```
<string> n = lang.patterns(<language> l)
lang.patterns(<language> l, <string> n)
```

Adds additional patterns for this language object, or returns the current set. The syntax of this string is explained in the next chapter, **section 6.36.3**.

```
lang.clear_patterns(<language> l)
```

Clears the pattern dictionary for this language.

```
<number> n = lang.prehyphenchar(<language> l)
lang.prehyphenchar(<language> l, <number> n)
```

Gets or sets the ‘pre-break’ hyphen character for implicit hyphenation in this language (initially the hyphen, decimal 45).

```
<number> n = lang.posthyphenchar(<language> l)
lang.posthyphenchar(<language> l, <number> n)
```



Gets or sets the ‘post-break’ hyphen character for implicit hyphenation in this language (initially null, decimal 0, indicating emptiness).

```
<number> n = lang.preexhyphenchar(<language> l)  
lang.preexhyphenchar(<language> l, <number> n)
```

Gets or sets the ‘pre-break’ hyphen character for explicit hyphenation in this language (initially null, decimal 0, indicating emptiness).

```
<number> n = lang.postexhyphenchar(<language> l)  
lang.postexhyphenchar(<language> l, <number> n)
```

Gets or sets the ‘post-break’ hyphen character for explicit hyphenation in this language (initially null, decimal 0, indicating emptiness).

```
<boolean> success = lang.hyphenate(<node> head)  
<boolean> success = lang.hyphenate(<node> head, <node> tail)
```

Inserts hyphenation points (discretionary nodes) in a node list. If `tail` is given as argument, processing stops on that node. Currently, `success` is always true if `head` (and `tail`, if specified) are proper nodes, regardless of possible other errors.

Hyphenation works only on ‘characters’, a special subtype of all the glyph nodes with the node subtype having the value 1. Glyph modes with different subtypes are not processed. See **section 6.16.1** for more details.



5 Math

The handling of mathematics in LuaTeX differs quite a bit from how TeX82 (and therefore pdfTeX) handles math. First, LuaTeX adds primitives and extends some others so that Unicode input can be used easily. Second, all of TeX82's internal special values (for example for operator spacing) have been made accessible and changeable via control sequences. Third, there are extensions that make it easier to use OpenType math fonts. And finally, there are some extensions that have been proposed in the past that are now added to the engine.

5.1 The current math style

Starting with LuaTeX 0.39.0, it is possible to discover the math style that will be used for a formula in an expandable fashion (while the math list is still being read). To make this possible, LuaTeX adds the new primitive: `\mathstyle`. This is a 'convert command' like e.g. `\romannumeral`: its value can only be read, not set.

5.1.1 `\mathstyle`

The returned value is between 0 and 7 (in math mode), or -1 (all other modes). For easy testing, the eight math style commands have been altered so that they can be used as numeric values, so you can write code like this:

```
\ifnum\mathstyle=\textstyle
  \message{normal text style}
\else \ifnum\mathstyle=\crampedtextstyle
  \message{cramped text style}
\fi \fi
```

5.1.2 `\Ustack`

There are a few math commands in TeX where the style that will be used is not known straight from the start. These commands (`\over`, `\atop`, `\overwithdelims`, `\atopwithdelims`) would therefore normally return wrong values for `\mathstyle`. To fix this, LuaTeX introduces a special prefix command: `\Ustack`:

```
 $\Ustack {a \over b}$ 
```

The `\Ustack` command will scan the next brace and start a new math group with the correct (numerator) math style.



5.2 Unicode math characters

Character handling is now extended up to the full Unicode range. The extension from 8-bit to 16-bit was already present in Aleph by means of a set of extra primitives starting with the `\o` prefix, the extension to full Unicode (the `\U` prefix) is compatible with $\X\TeX$.

The math primitives from \TeX and Aleph are kept as they are, except for the ones that convert from input to math commands: `\mathcode`, `\omathcode`, `\delcode`, and `\odelcode`. These four now allow for a 21-bit character argument on the left hand side of the equals sign.

Some of the Aleph math primitives and the new Lua \TeX primitives read more than one separate value. This is shown in the tables below by a plus sign in the second column.

The input for such primitives would look like this:

```
\def\overbrace {\Umathaccent 0 1 "23DE }
```

Altered \TeX 82 primitives:

primitive	value range (in hex)
<code>\mathcode</code>	0–10FFFF = 0–8000
<code>\delcode</code>	0–10FFFF = 0–FFFFFF

Unaltered:

primitive	value range (in hex)
<code>\mathchardef</code>	0–8000
<code>\mathchar</code>	0–7FFF
<code>\mathaccent</code>	0–7FFF
<code>\delimiter</code>	0–7FFFFFFF
<code>\radical</code>	0–7FFFFFFF

Altered Aleph primitives:

primitive	value range (in hex)
<code>\omathcode</code>	0–10FFFF = 0–8000000
<code>\odelcode</code>	0–10FFFF = 0+0–FFFFFF+FFFFFF

Unaltered:

primitive	value range (in hex)
<code>\omathchardef</code>	0–8000000
<code>\omathchar</code>	0–7FFFFFFF
<code>\omathaccent</code>	0–7FFFFFFF
<code>\odelimiter</code>	0+0–7FFFFFFF + FFFFFFFF
<code>\oradical</code>	0+0–7FFFFFFF + FFFFFFFF

New primitives that are compatible with $\X\TeX$:



primitive	value range (in hex)
<code>\Umathchardef</code>	$0+0+0-7+FF+10FFFF^1$
<code>\Umathcode</code>	$0-10FFFF = 0+0+0-7+FF+10FFFF^1$
<code>\Udelcode</code>	$0-10FFFF = 0+0-FF+10FFFF^2$
<code>\Umathchar</code>	$0+0+0-7+FF+10FFFF$
<code>\Umathaccent</code>	$0+0+0-7+FF+10FFFF^2$
<code>\Udelimiter</code>	$0+0+0-7+FF+10FFFF^2$
<code>\Uradical</code>	$0+0-FF+10FFFF^2$
<code>\Umathcharnum</code>	$-80000000-7FFFFFFF^3$
<code>\Umathcodenum</code>	$0-10FFFF = -80000000-7FFFFFFF^3$
<code>\Udelcodenum</code>	$0-10FFFF = -80000000-7FFFFFFF^3$

Note 1: `\Umathchardef<csname>="8"0"0` and `\Umathchardef<number>="8"0"0` are also accepted.

Note 2: The new primitives that deal with delimiter-style objects do not set up a ‘large family’. Selecting a suitable size for display purposes is expected to be dealt with by the font via the `\Umathoperator-size` parameter (more information a following section).

Note 3: For these three primitives, all information is packed into a single signed integer. For the first two (`\Umathcharnum` and `\Umathcodenum`), the lowest 21 bits are the character code, the 3 bits above that represent the math class, and the family data is kept in the topmost bits (This means that the values for math families 128–255 are actually negative). For `\Udelcodenum` there is no math class; the math family information is stored in the bits directly on top of the character code. Using these three commands is not as natural as using the two- and three-value commands, so unless you know exactly what you are doing and absolutely require the speedup resulting from the faster input scanning, it is better to use the verbose commands instead.

New primitives that exist in LuaTeX only (all of these will be explained in following sections):

primitive	value range (in hex)
<code>\Umathbotaccent</code>	$0+0+0-7+FF+10FFFF$
<code>\Umathaccents</code>	$0+0+0+0+0+0-7+FF+10FFFF+7+FF+10FFFF$
<code>\Uroot</code>	$0+0-FF+10FFFF^2$
<code>\Uoverdelimiter</code>	$0+0-FF+10FFFF^2$
<code>\Uunderdelimiter</code>	$0+0-FF+10FFFF^2$
<code>\Udelimiterover</code>	$0+0-FF+10FFFF^2$
<code>\Udelimiterrunder</code>	$0+0-FF+10FFFF^2$

5.3 Cramped math styles

LuaTeX has four new primitives to set the cramped math styles directly:

```
\crampeddisplaystyle
\crampedtextstyle
```



`\crampedscriptstyle`
`\crampedscriptscriptstyle`

These additional commands are not all that valuable on their own, but they come in handy as arguments to the math parameter settings that will be added shortly.

5.4 Math parameter settings

In LuaTeX, the font dimension parameters that T_EX used in math typesetting are now accessible via primitive commands. In fact, refactoring of the math engine has resulted in many more parameters than were accessible before.

primitive name	description
<code>\Umathquad</code>	the width of 18mu's
<code>\Umathaxis</code>	height of the vertical center axis of the math formula above the baseline
<code>\Umathoperatorsize</code>	minimum size of large operators in display mode
<code>\Umathoverbarkern</code>	vertical clearance above the rule
<code>\Umathoverbarrule</code>	the width of the rule
<code>\Umathoverbarvgap</code>	vertical clearance below the rule
<code>\Umathunderbarkern</code>	vertical clearance below the rule
<code>\Umathunderbarrule</code>	the width of the rule
<code>\Umathunderbarvgap</code>	vertical clearance above the rule
<code>\Umathradicalkern</code>	vertical clearance above the rule
<code>\Umathradicalrule</code>	the width of the rule
<code>\Umathradicalvgap</code>	vertical clearance below the rule
<code>\Umathradicaldegreebefore</code>	the forward kern that takes place before placement of the radical degree
<code>\Umathradicaldegreeafter</code>	the backward kern that takes place after placement of the radical degree
<code>\Umathradicaldegreeraise</code>	this is the percentage of the total height and depth of the radical sign that the degree is raised by. It is expressed in percents , so 60% is expressed as the integer 60.
<code>\Umathstackvgap</code>	vertical clearance between the two elements in a <code>\atop</code> stack
<code>\Umathstacknumup</code>	numerator shift upward in <code>\atop</code> stack
<code>\Umathstackdenomdown</code>	denominator shift downward in <code>\atop</code> stack
<code>\Umathfractionrule</code>	the width of the rule in a <code>\over</code>
<code>\Umathfractionnumvgap</code>	vertical clearance between the numerator and the rule
<code>\Umathfractionnumup</code>	numerator shift upward in <code>\over</code>
<code>\Umathfractiondenomvgap</code>	vertical clearance between the denominator and the rule
<code>\Umathfractiondenomdown</code>	denominator shift downward in <code>\over</code>
<code>\Umathfractiondelsize</code>	minimum delimiter size for <code>\dotswithdelims</code>
<code>\Umathlimitabovevgap</code>	vertical clearance for limits above operators
<code>\Umathlimitabovebgap</code>	vertical baseline clearance for limits above operators



<code>\Umathlimitabovekern</code>	space reserved at the top of the limit
<code>\Umathlimitbelowvgap</code>	vertical clearance for limits below operators
<code>\Umathlimitbelowbgap</code>	vertical baseline clearance for limits below operators
<code>\Umathlimitbelowkern</code>	space reserved at the bottom of the limit
<code>\Umathoverdelimitervgap</code>	vertical clearance for limits above delimiters
<code>\Umathoverdelimiterbgap</code>	vertical baseline clearance for limits above delimiters
<code>\Umathunderdelimitervgap</code>	vertical clearance for limits below delimiters
<code>\Umathunderdelimeterbgap</code>	vertical baseline clearance for limits below delimiters
<code>\Umathsubshiftdrop</code>	subscript drop for boxes and subformulas
<code>\Umathsubshiftdown</code>	subscript drop for characters
<code>\Umathsupshiftdrop</code>	superscript drop (raise, actually) for boxes and subformulas
<code>\Umathsupshiftdown</code>	superscript raise for characters
<code>\Umathsubsupshiftdrop</code>	subscript drop in the presence of a superscript
<code>\Umathsubtopmax</code>	the top of standalone subscripts cannot be higher than this above the baseline
<code>\Umathsupbottommin</code>	the bottom of standalone superscripts cannot be less than this above the baseline
<code>\Umathsupsubbottommax</code>	the bottom of the superscript of a combined super- and subscript be at least as high as this above the baseline
<code>\Umathsubsupvgap</code>	vertical clearance between super- and subscript
<code>\Umathspaceafterscript</code>	additional space added after a super- or subscript
<code>\Umathconnectoroverlapmin</code>	minimum overlap between parts in an extensible recipe

Each of the parameters in this section can be set by a command like this:

```
\Umathquad\displaystyle=1em
```

they obey grouping, and you can use `\the\Umathquad\displaystyle` if needed.

5.5 Font-based Math Parameters

While it is nice to have these math parameters available for tweaking, it would be tedious to have to set each of them by hand. For this reason, Lua \TeX initializes a bunch of these parameters whenever you assign a font identifier to a math family based on either the traditional math font dimensions in the font (for assignments to math family 2 and 3 using tfm-based fonts like `cmsy` and `cmex`), or based on the named values in a potential `MathConstants` table when the font is loaded via Lua. If there is a `MathConstants` table, this takes precedence over font dimensions, and in that case no attention is paid to which family is being assigned to: the `MathConstants` tables in the last assigned family sets all parameters.

In the table below, the one-letter style abbreviations and symbolic tfm font dimension names match those using in the \TeX book. Assignments to `\textfont` set the values for the cramped and uncramped display and text styles. Use `\scriptfont` for the script styles, and `\scriptscriptfont` for the scriptscript styles (totalling eight parameters for three font sizes). In the tfm case, assignments only happen in family 2 and family 3 (and of course only for the parameters for which there are font dimensions).



Besides the parameters below, Lua \TeX also looks at the ‘space’ font dimension parameter. For math fonts, this should be set to zero.

variable	style	default value	opentype	default value	tfm
$\backslash\mathrm{Umathaxis}$	–	AxisHeight		axis_height	
$\backslash\mathrm{Umathoperatorsize}$	D, D’	MinimumDisplayOperatorHeight		⁶	
$\backslash\mathrm{Umathfractiondelsize}$	D, D’	0 ¹		delim1	
"	T, T’, S, S’, SS, SS’	0 ¹		delim2	
$\backslash\mathrm{Umathfractiondenomdown}$	D, D’	FractionDenominatorDisplayStyleShiftDown		denom1	
"	T, T’, S, S’, SS, SS’	FractionDenominatorShiftDown		denom2	
$\backslash\mathrm{Umathfractiondenomvgap}$	D, D’	FractionDenominatorDisplayStyleGapMin		3*default_rule_thickness	
"	T, T’, S, S’, SS, SS’	FractionDenominatorGapMin		default_rule_thickness	
$\backslash\mathrm{Umathfractionnumup}$	D, D’	FractionNumeratorDisplayStyleShiftUp		num1	
"	T, T’, S, S’, SS, SS’	FractionNumeratorShiftUp		num2	
$\backslash\mathrm{Umathfractionnumvgap}$	D, D’	FractionNumeratorDisplayStyleGapMin		3*default_rule_thickness	
"	T, T’, S, S’, SS, SS’	FractionNumeratorGapMin		default_rule_thickness	
$\backslash\mathrm{Umathfractionrule}$	–	FractionRuleThickness		default_rule_thickness	
$\backslash\mathrm{Umathlimitabovebgap}$	–	UpperLimitBaselineRiseMin		big_op_spacing3	
$\backslash\mathrm{Umathlimitabovekern}$	–	0 ¹		big_op_spacing5	
$\backslash\mathrm{Umathlimitabovevgap}$	–	UpperLimitGapMin		big_op_spacing1	
$\backslash\mathrm{Umathlimitbelowbgap}$	–	LowerLimitBaselineDropMin		big_op_spacing4	
$\backslash\mathrm{Umathlimitbelowkern}$	–	0 ¹		big_op_spacing5	
$\backslash\mathrm{Umathlimitbelowvgap}$	–	LowerLimitGapMin		big_op_spacing2	
$\backslash\mathrm{Umathoverdelimitervgap}$	–	StretchStackGapBelowMin		big_op_spacing1	
$\backslash\mathrm{Umathoverdelimiterbgap}$	–	StretchStackTopShiftUp		big_op_spacing3	
$\backslash\mathrm{Umathunderdelimitervgap}$	–	StretchStackGapAboveMin		big_op_spacing2	
$\backslash\mathrm{Umathunderdelimiterbgap}$	–	StretchStackBottomShiftDown		big_op_spacing4	
$\backslash\mathrm{Umathoverbarkern}$	–	OverbarExtraAscender		default_rule_thickness	
$\backslash\mathrm{Umathoverbarrule}$	–	OverbarRuleThickness		default_rule_thickness	
$\backslash\mathrm{Umathoverbarvgap}$	–	OverbarVerticalGap		3*default_rule_thickness	
$\backslash\mathrm{Umathquad}$	–	<font_size(f)> ¹		math_quad	
$\backslash\mathrm{Umathradicalkern}$	–	RadicalExtraAscender		default_rule_thickness	
$\backslash\mathrm{Umathradicalrule}$	–	RadicalRuleThickness		<not set> ²	
$\backslash\mathrm{Umathradicalvgap}$	D, D’	RadicalDisplayStyleVerticalGap		(default_rule_thickness+ (abs(math_x_height)/4)) ³	
"	T, T’, S, S’, SS, SS’	RadicalVerticalGap		(default_rule_thickness+ (abs(default_rule_thickness)/4)) ³	
$\backslash\mathrm{Umathradicaldegreebefore}$	–	RadicalKernBeforeDegree		<not set> ²	
$\backslash\mathrm{Umathradicaldegreeafter}$	–	RadicalKernAfterDegree		<not set> ²	
$\backslash\mathrm{Umathradicaldegreeraise}$	–	RadicalDegreeBottomRaisePercent		<not set> ^{2,7}	
$\backslash\mathrm{Umathspaceafterscript}$	–	SpaceAfterScript		script_space ⁴	
$\backslash\mathrm{Umathstackdenomdown}$	D, D’	StackBottomDisplayStyleShiftDown		denom1	
"	T, T’, S, S’, SS, SS’	StackBottomShiftDown		denom2	
$\backslash\mathrm{Umathstacknumup}$	D, D’	StackTopDisplayStyleShiftUp		num1	
"	T, T’, S, S’, SS, SS’	StackTopShiftUp		num3	
$\backslash\mathrm{Umathstackvgap}$	D, D’	StackDisplayStyleGapMin		7*default_rule_thickness	
"	T, T’, S, S’, SS, SS’	StackGapMin		3*default_rule_thickness	
$\backslash\mathrm{Umathsubshiftdown}$	–	SubscriptShiftDown		sub1	
$\backslash\mathrm{Umathsubshiftdrop}$	–	SubscriptBaselineDropMin		sub_drop	
$\backslash\mathrm{Umathsubsupshiftdown}$	–	SubscriptShiftDownWithSuperscript ⁸			
		or SubscriptShiftDown		sub2	
$\backslash\mathrm{Umathsubtopmax}$	–	SubscriptTopMax		(abs(math_x_height * 4) / 5)	
$\backslash\mathrm{Umathsubsupvgap}$	–	SubSuperscriptGapMin		4*default_rule_thickness	
$\backslash\mathrm{Umathsupbottommin}$	–	SuperscriptBottomMin		(abs(math_x_height) / 4)	
$\backslash\mathrm{Umathsupshiftdrop}$	–	SuperscriptBaselineDropMax		sup_drop	
$\backslash\mathrm{Umathsupshiftup}$	D	SuperscriptShiftUp		sup1	
"	T, S, SS,	SuperscriptShiftUp		sup2	
"	D’, T’, S’, SS’	SuperscriptShiftUpCramped		sup3	
$\backslash\mathrm{Umathsupsubbottommax}$	–	SuperscriptBottomMaxWithSubscript		(abs(math_x_height * 4) / 5)	
$\backslash\mathrm{Umathunderbarkern}$	–	UnderbarExtraDescender		default_rule_thickness	
$\backslash\mathrm{Umathunderbarrule}$	–	UnderbarRuleThickness		default_rule_thickness	



<code>\Umathunderbarvgap</code>	–	UnderbarVerticalGap	$3 * \text{default_rule_thickness}$
<code>\Umathconnectoroverlapmin</code>	–	MinConnectorOverlap	0^5

Note 1: OpenType fonts set `\Umathfractiondelsize`, `\Umathlimitabovekern`, `\Umathlimitbelowkern` to zero and set `\Umathquad` to the font size of the used font, because these are not supported in the MATH table,

Note 2: tfm fonts do not set `\Umathradicalrule` because T_EX82 uses the height of the radical instead. When this parameter is indeed not set when LuaT_EX has to typeset a radical, a backward compatibility mode will kick in that assumes that an oldstyle T_EX font is used. Also, they do not set `\Umathradicaldegreebefore`, `\Umathradicaldegreeafter`, and `\Umathradicaldegreeraise`. These are then automatically initialized to 5/18quad, –10/18quad, and 60.

Note 3: If tfm fonts are used, then the `\Umathradicalvgap` is not set until the first time LuaT_EX has to typeset a formula because this needs parameters from both family2 and family3. This provides a partial backward compatibility with T_EX82, but that compatibility is only partial: once the `\Umathradicalvgap` is set, it will not be recalculated any more.

Note 4: (also if tfm fonts are used) A similar situation arises wrt. `\Umathspaceafterscript`: it is not set until the first time LuaT_EX has to typeset a formula. This provides some backward compatibility with T_EX82. But once the `\Umathspaceafterscript` is set, `\scriptspace` will never be looked at again.

Note 5: Tfm fonts set `\Umathconnectoroverlapmin` to zero because T_EX82 always stacks extensibles without any overlap.

Note 6: The `\Umathoperatorsiz` is only used in `\displaystyle`, and is only set in OpenType fonts. In tfm font mode, it is artificially set to one scaled point more than the initial attempt’s size, so that always the ‘first next’ will be tried, just like in T_EX82.

Note 7: The `\Umathradicaldegreeraise` is a special case because it is the only parameter that is expressed in a percentage instead of as a number of scaled points.

Note 8: `SubscriptShiftDownWithSuperscript` does not actually exist in the ‘standard’ Opentype Math font Cambria, but it is useful enough to be added. New in version 0.38.

5.6 Math spacing setting

Besides the parameters mentioned in the previous sections, there are also 64 new primitives to control the math spacing table (as explained in Chapter 18 of the T_EXbook). The primitive names are a simple matter of combining two math atom types, but for completeness’ sake, here is the whole list:

<code>\Umathbinordspacing</code>	<code>\Umathbininnerspacing</code>
<code>\Umathbinopspacing</code>	<code>\Umathrelordspacing</code>
<code>\Umathbinbinspacing</code>	<code>\Umathreloppspacing</code>
<code>\Umathbinrelspacing</code>	<code>\Umathrelbinspacing</code>
<code>\Umathbinopenspacing</code>	<code>\Umathrelrelspacing</code>
<code>\Umathbinclonespacing</code>	<code>\Umathreloppspacing</code>
<code>\Umathbinpunctspacing</code>	<code>\Umathrelclonespacing</code>



<code>\Umathrelpunctspacing</code>	<code>\Umathpunctordspacing</code>
<code>\Umathrelinnerspacing</code>	<code>\Umathpuncttopspacing</code>
<code>\Umathopenordspacing</code>	<code>\Umathpunctbinspacing</code>
<code>\Umathopenopspacing</code>	<code>\Umathpunctrelspacing</code>
<code>\Umathopenbinspacing</code>	<code>\Umathpunctopenspacing</code>
<code>\Umathopenrelspacing</code>	<code>\Umathpunctclosespacing</code>
<code>\Umathopenopenspacing</code>	<code>\Umathpunctpunctspacing</code>
<code>\Umathopenclosespacing</code>	<code>\Umathpunctinnerspacing</code>
<code>\Umathopenpunctspacing</code>	<code>\Umathinnerordspacing</code>
<code>\Umathopeninnerspacing</code>	<code>\Umathinneropspacing</code>
<code>\Umathcloseordspacing</code>	<code>\Umathinnerbinspacing</code>
<code>\Umathcloseopspacing</code>	<code>\Umathinnerrelspacing</code>
<code>\Umathclosebinspacing</code>	<code>\Umathinneropenspacing</code>
<code>\Umathcloserelspacing</code>	<code>\Umathinnerclosespacing</code>
<code>\Umathcloseopspacing</code>	<code>\Umathinnerpunctspacing</code>
<code>\Umathcloseclosespacing</code>	<code>\Umathinnerinnerspacing</code>
<code>\Umathclosepunctspacing</code>	
<code>\Umathcloseinnerspacing</code>	

These parameters are of type `\muskip`, so setting a parameter can be done like this:

```
\Umathopordspacing\displaystyle=4mu plus 2mu
```

They are all initialized by `initex` to the values mentioned in the table in Chapter 18 of the `TEXbook`.

Note 1: for ease of use as well as for backward compatibility, `\thinmuskip`, `\medmuskip` and `\thickmuskip` are treated especially. In their case a pointer to the corresponding internal parameter is saved, not the actual `\muskip` value. This means that any later changes to one of these three parameters will be taken into account.

Note 2: Careful readers will realise that there are also primitives for the items marked `*` in the `TEXbook`. These will not actually be used as those combinations of atoms cannot actually happen, but it seemed better not to break orthogonality. They are initialized to zero.

5.7 Math accent handling

Lua`TEX` supports both top accents and bottom accents in math mode. For bottom accents, there is the new primitive `\Umathbotaccent`. If you want to set both top and bottom accents on a single item, there is `\Umathaccents`.

If a math top accent has to be placed and the accentee is a character and has a non-zero `top_accent` value, then this value will be used to place the accent instead of the `\skewchar` kern used by `TEX82`.

The `top_accent` value represents a vertical line somewhere in the accentee. The accent will be shifted horizontally such that its own `top_accent` line coincides with the one from the accentee. If the `top_accent` value of the accent is zero, then half the width of the accent followed by its italic correction is used instead.



The vertical placement of a top accent depends on the `x_height` of the font of the accentee (as explained in the `TEXbook`), but if value that turns out to be zero and the font had a `MathConstants` table, then `AccentBaseHeight` is used instead.

If a math bottom accent has to be placed, the `bot_accent` value is checked instead of `top_accent`. Because bottom accents do not exist in `TEX82`, the `\skewchar` kern is ignored.

The vertical placement of a bottom accent is straight below the accentee, no correction takes place.

Lua`TEX` has horizontal extensibles, and when present, these will be used by the accent commands.

5.8 Math root extension

The new primitive `\Uroot` allows the construction of a radical noad including a degree field. Its syntax is an extension of `\Uradical`:

```
\Uradical <fam integer> <char integer> <radicand>
\Uroot    <fam integer> <char integer> <degree> <radicand>
```

The placement of the degree is controlled by the math parameters `\Umathradicaldegreebefore`, `\Umathradicaldegreeafter`, and `\Umathradicaldegreeraise`. The degree will be typeset in `\scriptscriptstyle`.

5.9 Math kerning in super- and subscripts

The character fields in a lua-loaded OpenType math font can have a ‘mathkern’ table. The format of this table is the same as the ‘mathkern’ table that is returned by the `fontloader` library, except that all height and kern values have to be specified in actual scaled points.

When a super- or subscript has to be placed next to a math item, Lua`TEX` checks whether the super- or subscript and the nucleus are both simple character items. If they are, and if the fonts of both character imtes are OpenType fonts (as opposed to legacy `TEX` fonts), then Lua`TEX` will use the OpenType MATH algorithm for deciding on the horizontal placement of the super- or subscript.

This works as follows:

- The vertical position of the script is calculated.
- The default horizontal position is flat next to the base character.
- For superscripts, the italic correction of the base character is added.
- For a superscript, two vertical values are calculated: the bottom of the script (after shifting up), and the top of the base. For a subscript, the two values are the top of the (shifted down) script, and the bottom of the base.
- For each of these two locations:



- find the mathkern value at this height for the base (for a subscript placement, this is the bottom_right corner, for a superscript placement the top_right corner)
- find the mathkern value at this height for the script (for a subscript placement, this is the top_left corner, for a superscript placement the bottom_left corner)
- add the found values together to get a preliminary result.
- The horizontal kern to be applied is the smallest of the two results from previous step.

The mathkern value at a specific height is the kern value that is specified by the next higher height and kern pair, or the highest one in the character (if there is no value high enough in the character), or simply zero (if the character has no mathkern pairs at all).

5.10 Scripts on horizontally extensible items like arrows

The new primitives `\Uunderdelimit` and `\Uoverdelimit` (both from 0.35) allow the placement of a subscript or superscript on an automatically extensible item and `\Udelimitunder` and `\Udelimitover` (both from 0.37) allow the placement of an automatically extensible item as a subscript or superscript on a nucleus.

The vertical placements are controlled by `\Umathunderdelimitervgap`, `\Umathunderdelimitervgap`, `\Umathoverdelimitervgap`, and `\Umathoverdelimitervgap` in a similar way as limit placements on large operators. The superscript in `\Uoverdelimit` is typeset in a suitable scripted style, the subscript in `\Uunderdelimit` is cramped as well.

5.11 Extensible delimiters

LuaTeX internally uses a structure that supports OpenType ‘MathVariants’ as well as tfm ‘extensible recipes’.

5.12 Other Math changes

5.12.1 Verbose versions of single-character math commands

LuaTeX defines six new primitives that have the same function as `^`, `_`, `$`, and `$$`.

primitive	explanation
<code>\Usuperscript</code>	Duplicates the functionality of <code>^</code>
<code>\Usubscript</code>	Duplicates the functionality of <code>_</code>
<code>\Ustartmath</code>	Duplicates the functionality of <code>\$</code> , when used in non-math mode.
<code>\Ustopmath</code>	Duplicates the functionality of <code>\$</code> , when used in inline math mode.
<code>\Ustartdisplaymath</code>	Duplicates the functionality of <code>\$\$</code> , when used in non-math mode.
<code>\Ustopdisplaymath</code>	Duplicates the functionality of <code>\$\$</code> , when used in display math mode.



All are new in version 0.38. The `\Ustopmath` and `\Ustopdisplaymath` primitives check if the current math mode is the correct one (inline vs. displayed), but you can freely intermix the four `mathon/mathoff` commands with explicit dollar sign(s).

5.12.2 Allowed math commands in non-math modes

The commands `\mathchar`, `\omathchar`, and `\Umathchar` and control sequences that are the result of `\mathchardef`, `\omathchardef`, or `\Umathchardef` are also acceptable in the horizontal and vertical modes. In those cases, the `\textfont` from the requested math family is used.

5.13 Math todo

The following items are still todo.

- Pre-scripts.
- Multi-story stacks.
- Flattened accents for high characters (?).
- Better control over the spacing around displays and handling of equation numbers.
- Support for multi-line displays using MathML style alignment points.





6 Languages and characters, fonts and glyphs

LuaTeX's internal handling of the characters and glyphs that eventually become typeset is quite different from the way T_EX82 handles those same objects. The easiest way to explain the difference is to focus on unrestricted horizontal mode (i. e. paragraphs) and hyphenation first. Later on, it will be easy to deal with the differences that occur in horizontal and math modes.

In T_EX82, the characters you type are converted into `char_node` records when they are encountered by the main control loop. T_EX attaches and processes the font information while creating those records, so that the resulting 'horizontal list' contains the final forms of ligatures and implicit kerning. This packaging is needed because we may want to get the effective width of for instance a horizontal box.

When it becomes necessary to hyphenate words in a paragraph, T_EX converts (one word at time) the `char_node` records into a string array by replacing ligatures with their components and ignoring the kerning. Then it runs the hyphenation algorithm on this string, and converts the hyphenated result back into a 'horizontal list' that is consecutively spliced back into the paragraph stream. Keep in mind that the paragraph may contain unboxed horizontal material, which then already contains ligatures and kerns and the words therein are part of the hyphenation process.

The `char_node` records are somewhat misnamed, as they are glyph positions in specific fonts, and therefore not really 'characters' in the linguistic sense. There is no language information inside the `char_node` records. Instead, language information is passed along using `language whatsit` records inside the horizontal list.

In LuaTeX, the situation is quite different. The characters you type are always converted into `glyph_node` records with a special subtype to identify them as being intended as linguistic characters. LuaTeX stores the needed language information in those records, but does not do any font-related processing at the time of node creation. It only stores the index of the font.

When it becomes necessary to typeset a paragraph, LuaTeX first inserts all hyphenation points right into the whole node list. Next, it processes all the font information in the whole list (creating ligatures and adjusting kerning), and finally it adjusts all the subtype identifiers so that the records are 'glyph nodes' from now on.

That was the broad overview. The rest of this chapter will deal with the minutiae of the new process.

6.1 Characters and glyphs

T_EX82 (including pdfT_EX) differentiated between `char_nodes` and `lig_nodes`. The former are simple items that contained nothing but a 'character' and a 'font' field, and they lived in the same memory as tokens did. The latter also contained a list of components, and a subtype indicating whether this ligature was the result of a word boundary, and it was stored in the same place as other nodes like boxes and kerns and glues.

In LuaTeX, these two types are merged into one, somewhat larger structure called a `glyph_node`. Besides having the old character, font, and component fields, and the new special fields like 'attr' (see [section 8.1.2.128.1.2.12](#)), these nodes also contain:



- A subtype, split into four main types:
 - `character`, for characters to be hyphenated: the lowest bit (bit 0) is set to 1.
 - `glyph`, for specific font glyphs: the lowest bit (bit 0) is not set.
 - `ligature`, for ligatures (bit 1 is set)
 - `ghost`, for ‘ghost objects’ (bit 2 is set)
 The latter two make further use of two extra fields (bits 3 and 4):
 - `left`, for ligatures created from a left word boundary and for ghosts created from `\leftghost`
 - `right`, for ligatures created from a right word boundary and for ghosts created from `\rightghost`
 For ligatures, both bits can be set at the same time (in case of a single-glyph word).
- `glyph_nodes` of type ‘character’ also contain language data, split into four items that were current when the node was created: the `\setlanguage` (15 bits), `\lefthyphenmin` (8 bits), `\righthyphenmin` (8 bits), and `\uchyph` (1 bit).

Incidentally, LuaTeX allows 32768 separate languages, and words can be 256 characters long.

Because the `\uchyph` value is saved in the actual nodes, its handling is subtly different from TeX82: changes to `\uchyph` become effective immediately, not at the end of the current partial paragraph.

Typeset boxes now always have their language information embedded in the nodes themselves, so there is no longer a possible dependency on the surrounding language settings. In TeX82, a mid-paragraph statement like `\unhbox0` would process the box using the current paragraph language unless there was a `\setlanguage` issued inside the box. In LuaTeX, all language variables are already frozen.

6.2 The main control loop

In LuaTeX’s main loop, almost all input characters that are to be typeset are converted into `glyph_node` records with subtype ‘character’, but there are a few small exceptions.

First, the `\accent` primitives create nodes with subtype ‘glyph’ instead of ‘character’: one for the actual accent and one for the accentee. The primary reason for this is that `\accent` in TeX82 is explicitly dependent on the current font encoding, so it would not make much sense to attach a new meaning to the primitive’s name, as that would invalidate many old documents and macro packages. A secondary reason is that in TeX82, `\accent` prohibits hyphenation of the current word. Since in LuaTeX hyphenation only takes place on ‘character’ nodes, it is possible to achieve the same effect.

This change of meaning did happen with `\char`, that now generates ‘character’ nodes, consistent with its changed meaning in XeTeX. The changed status of `\char` is not yet finalized, but if it stays as it is now, a new primitive `\glyph` should be added to directly insert a font glyph id.

Second, all the results of processing in math mode eventually become nodes with ‘glyph’ subtypes.

Third, the Aleph-derived commands `\leftghost` and `\rightghost` create nodes of a third subtype: ‘ghost’. These nodes are ignored completely by all further processing until the stage where inter-glyph kerning is added.

Fourth, automatic discretionaries are handled differently. TeX82 inserts an empty discretionary after sensing an input character that matches the `\hyphenchar` in the current font. This test is wrong, in our



opinion: whether or not hyphenation takes place should not depend on the current font, it is a language property.

In LuaT_EX, it works like this: if LuaT_EX senses a string of input characters that matches the value of the new integer parameter `\exhyphenchar`, it will insert an explicit discretionary after that series of nodes. Initex sets the `\exhyphenchar=`. Incidentally, this is a global parameter instead of a language-specific one because it may be useful to change the value depending on the document structure instead of the text language.

The only use LuaT_EX has for `\hyphenchar` is at the check whether a word should be considered for hyphenation at all. If the `\hyphenchar` of the font attached to the first character node in a word is negative, then hyphenation of that word is abandoned immediately. **This behaviour is added for backward compatibility only, and the use of `\hyphenchar=-1` as a means of preventing hyphenation should not be used in new LuaT_EX documents.**

Fifth, `\setlanguage` no longer creates whatsits. The meaning of `\setlanguage` is changed so that it is now an integer parameter like all others. That integer parameter is used in `\glyph_node` creation to add language information to the glyph nodes. In conjunction, the `\language` primitive is extended so that it always also updates the value of `\setlanguage`.

Sixth, the `\noboundary` command (this command prohibits word boundary processing where that would normally take place) now does create whatsits. These whatsits are needed because the exact place of the `\noboundary` command in the input stream has to be retained until after the ligature and font processing stages.

Finally, there is no longer a `main_loop` label in the code. Remember that T_EX82 did quite a lot of processing while adding `char_nodes` to the horizontal list? For speed reasons, it handled that processing code outside of the ‘main control’ loop, and only the first character of any ‘word’ was handled by that ‘main control’ loop. In LuaT_EX, there is no longer a need for that (all hard work is done later), and the (now very small) bits of character-handling code have been moved back inline. When `\tracingcommands` is on, this is visible because the full word is reported, instead of just the initial character.

6.3 Loading patterns and exceptions

The hyphenation algorithm in LuaT_EX is quite different from the one in T_EX82, although it uses essentially the same user input.

After expansion, the argument for `\patterns` has to be proper UTF-8, no `\char` or `\chardef-ed` commands are allowed. (The current implementation is even more strict, and will reject all non-Unicode characters, but that will be changed in the future. For now, the generated errors are a valuable tool in discovering font-encoding specific pattern files)

Likewise, the expanded argument for `\hyphenation` also has to be proper UTF-8, but here a tiny little bit of extra syntax is provided:

1. three sets of arguments in curly braces (`{ } { } { }`) indicates a desired complex discretionary, with arguments as in `\discretionary`’s command in normal document input.
2. `-` indicates a desired simple discretionary, cf. `\-` and `\discretionary-` in normal document input.



3. Internal command names are ignored. This rule is provided especially for `\discretionary`, but it also helps to deal with `\relax` commands that may sneak in.
4. `=` indicates a hyphen in the document input (but that is only useful in documents where `\exhyphenchar` is not equal to the hyphen).

The expanded argument is first converted back to a space-separated string while dropping the internal command names. This string is then converted into a dictionary by a routine that creates key–value pairs by converting the other listed items. It is important to note that the keys in an exception dictionary can always be generated from the values. Here are a few examples:

value	implied key (input)	effect
<code>ta-ble</code>	table	<code>ta\ble (= ta\discretionary {-}{ }ble)</code>
<code>ba{k-}{c}ken</code>	backen	<code>ba\discretionary {k-}{ }c}ken</code>

The resultant patterns and exception dictionary will be stored under the language code that is the present value of `\language`.

In the last line of the table, you see there is no `\discretionary` command in the value: the command is optional in the T_EX-based input syntax. The underlying reason for that is that it is conceivable that a whole dictionary of words is stored as a plain text file and loaded into LuaT_EX using one of the functions in the Lua `lang` library. This loading method is quite a bit faster than going through the T_EX language primitives, but some (most?) of that speed gain would be lost if it had to interpret command sequences while doing so.

The motivation behind the ϵ -T_EX extension `\savingshyphcodes` was that hyphenation heavily depended on font encodings. This is no longer true in LuaT_EX, and the corresponding primitive is ignored pending complete removal. The future semantics of `\uppercase` and `\lowercase` are still under consideration, no changes have taken place yet.

6.4 Applying hyphenation

The internal structures LuaT_EX uses for the insertion of discretionaries in words is very different from the ones in T_EX82, and that means there are some noticeable differences in handling as well.

First and foremost, there is no ‘compressed trie’ involved in hyphenation. The algorithm still reads patgen-generated pattern files, but LuaT_EX uses a finite state hash to match the patterns against the word to be hyphenated. This algorithm is based on the ‘libhnj’ library used by OpenOffice, which in turn is inspired by T_EX. The memory allocation for this new implementation is completely dynamic, so the `web2c` setting for `trie_size` is ignored.

Differences between LuaT_EX and T_EX82 that are a direct result of that:

- LuaT_EX happily hyphenates the full Unicode character range.
- Pattern and exception dictionary size is limited by the available memory only, all allocations are done dynamically. The trie-related settings in `texmf.cnf` are ignored.



- Because there is no ‘trie preparation’ stage, language patterns never become frozen. This means that the primitive `\patterns` (and its Lua counterpart `lang.patterns`) can be used at any time, not only in `initex`.
- Only the string representation of `\patterns` and `\hyphenation` is stored in the format file. At format load time, they are simply re-evaluated. It follows that there is no real reason to preload languages in the format file. In fact, it is usually not a good idea to do so. It is much smarter to load patterns no sooner than the first time they are actually needed.
- LuaTeX uses the language-specific variables `\prehyphenchar` and `\posthyphenchar` in the creation of implicit discretionary, instead of TeX82’s `\hyphenchar`, and the values of the language-specific variables `\preexhyphenchar` and `\postexhyphenchar` for explicit discretionary (instead of TeX82’s empty discretionary).

Inserted characters and ligatures inherit their attributes from the nearest glyph node item (usually the preceding one, but the following one for the items inserted at the left-hand side of a word).

Word boundaries are no longer implied by font switches, but by language switches. One word can have two separate fonts and still be hyphenated correctly (but it can not have two different languages, the `\setlanguage` command forces a word boundary).

All languages start out with `\prehyphenchar=`, `\posthyphenchar=0`, `\preexhyphenchar=0` and `\postexhyphenchar=0`. When you assign the values of one of these four parameters, you are actually changing the settings for the current `\language`, this behavior is compatible with `\patterns` and `\hyphenation`.

LuaTeX also hyphenates the first word in a paragraph.

Words can be up to 256 characters long (up from 64 in TeX82). Longer words generate an error right now, but eventually either the limitation will be removed or perhaps it will become possible to silently ignore the excess characters (this is what happens in TeX82, but there the behaviour cannot be controlled).

If you are using the Lua function `lang.hyphenate`, you should be aware that this function expects to receive a list of ‘character’ nodes. It will not operate properly in the presence of ‘glyph’, ‘ligature’, or ‘ghost’ nodes, nor does it know how to deal with kerning. In the near future, it will be able to skip over ‘ghost’ nodes, and we may add a less fuzzy function you can call as well.

The hyphenation exception dictionary is maintained as key-value hash, and that is also dynamic, so the `hyph_size` setting is not used either.

A technical paper detailing the new algorithm will be released as a separate document.

6.5 Applying ligatures and kerning

After all possible hyphenation points have been inserted in the list, LuaTeX will process the list to convert the ‘character’ nodes into ‘glyph’ and ‘ligature’ nodes. This is actually done in two stages: first all ligatures are processed, then all kerning information is applied to the result list. But those two stages are somewhat dependent on each other: If the used font makes it possible to do so, the ligaturing stage adds virtual ‘character’ nodes to the word boundaries in the list. While doing so, it removes and interprets `noboundary` nodes. The kerning stage deletes those word boundary items after it is done



with them, and it does the same for ‘ghost’ nodes. Finally, at the end of the kerning stage, all remaining ‘character’ nodes are converted to ‘glyph’ nodes.

This work separation is worth mentioning because, if you overrule from Lua only one of the two callbacks related to font handling, then you have to make sure you perform the tasks normally done by LuaTeX itself in order to make sure that the other, non-overruled, routine continues to function properly.

Work in this area is not yet complete, but most of the possible cases are handled by our rewritten ligaturing engine. We are working hard to make sure all of the possible inputs will become supported soon.

For example, take the word `office`, hyphenated `of-fice`, using a ‘normal’ font with all the `f-i` ligatures:

```
Initial:           {o}{f}{f}{i}{c}{e}
After hyphenation: {o}{f}{f}{-},{f}{f}{i}{c}{e}
First ligature stage: {o}{f}{f}{-},{f}{f}{f}{i}{c}{e}
Final result:       {o}{f}{f}{-},{f}{f}{f}{i}{c}{e}
```

That’s bad enough, but if there was a hyphenation point between the `f` and the `i`: `of-f-ice`, the final result should be:

```
{o}{f}{f}{-},
  {f}{f}{-},
  {i},
  {fi}},
  {ff}{f}{-},
  {i},
  {ffi}}}{c}{e}
```

with discretionaries in the post-break text as well as in the replacement text of the top-level discretionary that resulted from the first hyphenation point. And this is only a simple case.

As of 0.39.0, the solution in LuaTeX is not as smart as all this. It essentially creates the following set of items for `of-f-ice`:

```
{o}{f}{f}{-},
  {fi},
  {ffi}},
  {f}{f}{-},
  {i},
  {fi}}}{c}{e}
```

This is not perfect (because the `off-ice` hyphenation will never be chosen), but luckily three-item ligatures with multiple embedded hyphenation points are extremely rare indeed: even this example was artificially created. A full, perfect solution is possible, but is low on the agenda now that at least `office` can be hyphenated properly again.



6.6 Breaking paragraphs into lines

This code is still almost unchanged, but because of the above-mentioned changes with respect to discretionary nodes and ligatures, line breaking will potentially be different from traditional \TeX . The actual line breaking code is still based on the \TeX 82 algorithms, and it does not expect there to be discretionary nodes inside of discretionary nodes.

But that situation is now fairly common in \LuaTeX , due to the changes to the ligaturing mechanism. And also, the \LuaTeX discretionary nodes are implemented slightly different from the \TeX 82 nodes: the `no_break` text is now embedded inside the disc node, where previously these nodes kept their place in the horizontal list (the discretionary node contained a counter indicating how many nodes to skip).

The combined effect of these two differences is that \LuaTeX does not always use all of the potential breakpoints in a paragraph, especially when fonts with many ligatures are used.





7 Font structure

All T_EX fonts are represented to Lua code as tables, and internally as C structures. All keys in the table below are saved in the internal font structure if they are present in the table returned by the `define_font` callback, or if they result from the normal tfm/vf reading routines if there is no `define_font` callback defined.

The column ‘from vf’ means that this key will be created by the `font.read_vf()` routine, ‘from tfm’ means that the key will be created by the `font.read_tfm()` routine, and ‘used’ means whether or not the LuaT_EX engine itself will do something with the key.

The top-level keys in the table are as follows:

key	from vf	from tfm	used	value type	description
name	yes	yes	yes	string	metric (file) name
area	no	yes	yes	string	(directory) location, typically empty
used	no	yes	yes	boolean	used already? (initial: false)
characters	yes	yes	yes	table	the defined glyphs of this font
checksum	yes	yes	no	number	default: 0
designsize	no	yes	yes	number	expected size (default: 655360 == 10pt)
direction	no	yes	yes	number	default: 0 (LTR)
encodingbytes	no	no	yes	number	default: depends on <code>format</code>
encodingname	no	no	yes	string	encoding name
fonts	yes	no	yes	table	locally used fonts
fullname	no	no	yes	string	actual (PostScript) name
header	yes	no	no	string	header comments, if any
hyphenchar	no	no	yes	number	default: TeX’s <code>\hyphenchar</code>
parameters	no	yes	yes	hash	default: 7 parameters, all zero
size	no	yes	yes	number	loaded (at) size. (default: same as designsize)
skewchar	no	no	yes	number	default: TeX’s <code>\skewchar</code>
type	yes	no	yes	string	basic type of this font
format	no	no	yes	string	disk format type
embedding	no	no	yes	string	pdf inclusion
filename	no	no	yes	string	disk file name
tounicode	no	yes	yes	number	if 1, LuaT _E X assumes per-glyph touni- code entries are present in the font
stretch	no	no	yes	number	the ‘stretch’ value from <code>\pdffontex- pand</code>
shrink	no	no	yes	number	the ‘shrink’ value from <code>\pdffontex- pand</code>
step	no	no	yes	number	the ‘step’ value from <code>\pdffontexpand</code>



<code>auto_expand</code>	no	no	yes	boolean	the ‘autoexpand’ keyword from <code>\pdf-fontexpand</code>
<code>expansion_factor</code>	no	no	no	number	the actual expansion factor of an expanded font
<code>attributes</code>	no	no	yes	string	the <code>\pdffontattr</code>
<code>cache</code>	no	no	yes	string	this key controls caching of the lua table on the <code>tex</code> end. yes : use a reference to the table that is passed to LuaTeX (this is the default). no : don’t store the table reference, don’t cache any lua data for this font. renew : don’t store the table reference, but save a reference to the table that is created at the first access to one of its fields in <code>font.fonts</code> . (new in 0.40.0, before that caching was always yes)

The key `name` is always required. The keys `stretch`, `shrink`, `step` and optionally `auto_expand` only have meaning when used together: they can be used to replace a post-loading `\pdffontexpand` command. The `expansion_factor` is value that can be present inside a font in `font.fonts`. It is the actual expansion factor (a value between `-shrink` and `stretch`, with step `step`) of a font that was automatically generated by the font expansion algorithm. The key `attributes` can be used to replace `\pdffontattr`. The key `used` is set by the engine when a font is actively in use, this makes sure that the font’s definition is written to the output file (dvi or pdf). The tfm reader sets it to false. The `direction` is a number signalling the ‘normal’ direction for this font. There are sixteen possibilities:

number	meaning	number	meaning
0	LT	8	TT
1	LL	9	TL
2	LB	10	TB
3	LR	11	TR
4	RT	12	BT
5	RL	13	BL
6	RB	14	BB
7	RR	15	BR

These are Omega-style direction abbreviations: the first character indicates the ‘first’ edge of the character glyphs (the edge that is seen first in the writing direction), the second the ‘top’ side.

The `parameters` is a hash with mixed key types. There are seven possible string keys, as well as a number of integer indices (these start from 8 up). The seven strings are actually used instead of the bottom seven indices, because that gives a nicer user interface.

The names and their internal remapping are:

name	internal remapped number
<code>slant</code>	1



space	2
space_stretch	3
space_shrink	4
x_height	5
quad	6
extra_space	7

The keys `type`, `format`, `embedding`, `fullname` and `filename` are used to embed OpenType fonts in the result pdf.

The `characters` table is a list of character hashes indexed by an integer number. The number is the ‘internal code’ T_EX knows this character by.

Two very special string indexes can be used also: `left_boundary` is a virtual character whose ligatures and kerns are used to handle word boundary processing. `right_boundary` is similar but not actually used for anything (yet!).

Other index keys are ignored.

Each character hash itself is a hash. For example, here is the character ‘f’ (decimal 102) in the font cmr10 at 10 points:

```
[102] = {
  ['width'] = 200250,
  ['height'] = 455111,
  ['depth'] = 0,
  ['italic'] = 50973,
  ['kerns'] = {
    [63] = 50973,
    [93] = 50973,
    [39] = 50973,
    [33] = 50973,
    [41] = 50973
  },
  ['ligatures'] = {
    [102] = {
      ['char'] = 11,
      ['type'] = 0
    },
    [108] = {
      ['char'] = 13,
      ['type'] = 0
    },
    [105] = {
      ['char'] = 12,
      ['type'] = 0
    }
  }
}
```



```
}
}
```

Of course a more compact is also possible, but keep in mind that reserved words cannot be used compact and in Lua_T_EX we often have a `type` key.

```
[102] = {
  ...
  ligatures = {
    [102] = {
      char = 11,
      ['type'] = 0
    },
    ...
  }
}
```

The following top-level keys can be present inside a character hash:

key	from vf	from tfm	used	value type	description
width	yes	yes	yes	number	character's width, in sp (default 0)
height	no	yes	yes	number	character's height, in sp (default 0)
depth	no	yes	yes	number	character's depth, in sp (default 0)
italic	no	yes	yes	number	character's italic correction, in sp (default zero)
top_accent	no	no	maybe	number	character's top accent alignment place, in sp (default zero)
bot_accent	no	no	maybe	number	character's bottom accent alignment place, in sp (default zero)
left_protruding	no	no	maybe	number	character's <code>\lrcode</code>
right_protruding	no	no	maybe	number	character's <code>\rrcode</code>
expansion_factor	no	no	maybe	number	character's <code>\efcode</code>
tounicode	no	no	maybe	string	character's Unicode equivalent(s), in UTF-16BE hexadecimal format
next	no	yes	yes	number	the 'next larger' character index
extensible	no	yes	yes	table	the constituent parts of an extensible recipe
vert_variants	no	no	yes	table	constituent parts of a vertical variant set
horiz_variants	no	no	yes	table	constituent parts of a horizontal variant set
kerns	no	yes	yes	table	kerning information
ligatures	no	yes	yes	table	ligaturing information
commands	yes	no	yes	array	virtual font commands
name	no	no	no	string	the character (PostScript) name



<code>index</code>	no	no	yes	number	the (OpenType or TrueType) font glyph index
<code>used</code>	no	yes	yes	boolean	typeset already (default: false)?
<code>mathkern</code>	no	no	yes	table	math cut-in specifications

The values of `top_accent`, `bot_accent` and `mathkern` are used only for math accent and superscript placement, see the 103math chapter in this manual for details.

The values of `left_protruding` and `right_protruding` are used only when `\pdfprotrudechars` is non-zero.

Whether or not `expansion_factor` is used depends on the font's global expansion settings, as well as on the value of `\pdfadjustspacing`.

The usage of `tounicode` is this: if this font specifies a `tounicode=1` at the top level, then LuaT_EX will construct a `/ToUnicode` entry for the pdf font (or font subset) based on the character-level `tounicode` strings, where they are available. If a character does not have a sensible Unicode equivalent, do not provide a string either (no empty strings).

If the font-level `tounicode` is not set, then LuaT_EX will build up `/ToUnicode` based on the T_EX code points you used, and any character-level `tounicodes` will be ignored. *At the moment, the string format is exactly the format that is expected by Adobe CMap files (utf-16BE in hexadecimal encoding), minus the enclosing angle brackets. This may change in the future.* Small example: the `tounicode` for a `fi` ligature would be `00660069`.

The presence of `extensible` will overrule `next`, if that is also present. It in turn can be overruled by `vert_variants`.

The `extensible` table is very simple:

key	type	description
<code>top</code>	number	'top' character index
<code>mid</code>	number	'middle' character index
<code>bot</code>	number	'bottom' character index
<code>rep</code>	number	'repeatable' character index

The `horiz_variants` and `vert_variants` are arrays of components. Each of those components is itself a hash of up to five keys:

key	type	explanation
<code>component</code>	number	The character index (note that this is an encoding number, not a name).
<code>extender</code>	number	One (1) if this part is repeatable, zero (0) otherwise.
<code>start</code>	number	Maximum overlap at the starting side (in scaled points).
<code>end</code>	number	Maximum overlap at the ending side (in scaled points).
<code>advance</code>	number	Total advance width of this item (can be zero or missing, then the natural size of the glyph for character <code>component</code> is used).

The `kerns` table is a hash indexed by character index (and 'character index' is defined as either a non-negative integer or the string value `right_boundary`), with the values the kerning to be applied, in scaled points.



The `ligatures` table is a hash indexed by character index (and ‘character index’ is defined as either a non-negative integer or the string value `right_boundary`), with the values being yet another small hash, with two fields:

key	type	description
<code>type</code>	number	the type of this ligature command, default 0
<code>char</code>	number	the character index of the resultant ligature

The `char` field in a ligature is required.

The `type` field inside a ligature is the numerical or string value of one of the eight possible ligature types supported by T_EX. When T_EX inserts a new ligature, it puts the new glyph in the middle of the left and right glyphs. The original left and right glyphs can optionally be retained, and when at least one of them is kept, it is also possible to move the new ‘insertion point’ forward one or two places. The glyph that ends up to the right of the insertion point will become the next ‘left’.

textual (Knuth)	number	string	result
<code>l + r =: n</code>	0	<code>=:</code>	<code> n</code>
<code>l + r =: n</code>	1	<code>=: </code>	<code> nr</code>
<code>l + r =: n</code>	2	<code> =:</code>	<code> ln</code>
<code>l + r =: n</code>	3	<code> =: </code>	<code> lnr</code>
<code>l + r =: > n</code>	5	<code>=: ></code>	<code>n r</code>
<code>l + r =:> n</code>	6	<code> =:></code>	<code>l n</code>
<code>l + r =: > n</code>	7	<code> =: ></code>	<code>l nr</code>
<code>l + r =: >> n</code>	11	<code> =: >></code>	<code>ln r</code>

The default value is 0, and can be left out. That signifies a ‘normal’ ligature where the ligature replaces both original glyphs. In this table the `|` indicates the final insertion point.

The `commands` array is explained below.

7.1 Real fonts

Whether or not a T_EX font is a ‘real’ font that should be written to the pdf document is decided by the `type` value in the top-level font structure. If the value is `real`, then this is a proper font, and the inclusion mechanism will attempt to add the needed font object definitions to the pdf.

Values for `type`:

value	description
<code>real</code>	this is a base font
<code>virtual</code>	this is a virtual font

The actions to be taken depend on a number of different variables:



- Whether the used font fits in an 8-bit encoding scheme or not
- The type of the disk font file
- The level of embedding requested

A font that uses anything other than an 8-bit encoding vector has to be written to the pdf in a different way.

The rule is: if the font table has `encodingbytes` set to 2, then this is a wide font, in all other cases it isn't. The value 2 is the default for OpenType and TrueType fonts loaded via Lua. For Type1 fonts, you have to set `encodingbytes` to 2 explicitly. For pk bitmap fonts, wide font encoding is not supported at all.

If no special care is needed, LuaTeX currently falls back to the mapfile-based solution used by pdfTeX and dvips. This behaviour will be removed in the future, when the existing code becomes integrated in the new subsystem.

But if this is a 'wide' font, then the new subsystem kicks in, and some extra fields have to be present in the font structure. In this case, LuaTeX does not use a map file at all.

The extra fields are: `format`, `embedding`, `fullname`, `cidinfo` (as explained above), `filename`, and the `index` key in the separate characters.

Values for `format` are:

value	description
<code>type1</code>	this is a PostScript Type1 font
<code>type3</code>	this is a bitmapped (pk) font
<code>truetype</code>	this is a TrueType or TrueType-based OpenType font
<code>opentype</code>	this is a PostScript-based OpenType font

(`type3` fonts are provided for backward compatibility only, and do not support the new wide encoding options.)

Values for `embedding` are:

value	description
<code>no</code>	don't embed the font at all
<code>subset</code>	include and attempt to subset the font
<code>full</code>	include this font in its entirety

It is not possible to artificially modify the transformation matrix for the font at the moment.

The other fields are used as follows: The `fullname` will be the PostScript/pdf font name. The `cidinfo` will be used as the character set (the CID `/Ordering` and `/Registry` keys). The `filename` points to the actual font file. If you include the full path in the `filename` or if the file is in the local directory, LuaTeX will run a little bit more efficient because it will not have to re-run the `find_xxx_file` callback in that case.

Be careful: when mixing old and new fonts in one document, it is possible to create PostScript name clashes that can result in printing errors. When this happens, you have to change the `fullname` of the font.



Typeset strings are written out in a wide format using 2 bytes per glyph, using the `index` key in the character information as value. The overall effect is like having an encoding based on numbers instead of traditional (PostScript) name-based reencoding. The way to get the correct `index` numbers for Type1 fonts is by loading the font via `fontloader.open`; use the table indices as `index` fields.

This type of reencoding means that there is no longer a clear connection between the text in your input file and the strings in the output pdf file. Dealing with this is high on the agenda.

7.2 Virtual fonts

You have to take the following steps if you want LuaTeX to treat the returned table from `define_font` as a virtual font:

- Set the top-level key `type` to `virtual`.
- Make sure there is at least one valid entry in `fonts` (see below).
- Give a `commands` array to every character (see below).

The presence of the toplevel `type` key with the specific value `virtual` will trigger handling of the rest of the special virtual font fields in the table, but the mere existence of 'type' is enough to prevent LuaTeX from looking for a virtual font on its own.

Therefore, this also works 'in reverse': if you are absolutely certain that a font is not a virtual font, assigning the value `base` or `real` to `type` will inhibit LuaTeX from looking for a virtual font file, thereby saving you a disk search.

The `fonts` is another Lua array. The values are one- or two-key hashes themselves, each entry indicating one of the base fonts in a virtual font. In case your font is referring to itself, you can use the `font.nextid()` function which returns the index of the next to be defined font which is probably the currently defined one.

An example makes this easy to understand

```
fonts = {
  { name = 'ptmr8a', size = 655360 },
  { name = 'psyr', size = 600000 },
  { id = 38 }
}
```

says that the first referenced font (index 1) in this virtual font is `ptrmr8a` loaded at 10pt, and the second is `psyr` loaded at a little over 9pt. The third one is previously defined font that is known to LuaTeX as fontid '38'.

The array index numbers are used by the character command definitions that are part of each character.

The `commands` array is a hash where each item is another small array, with the first entry representing a command and the extra items being the parameters to that command. The allowed commands and their arguments are:



command name	arguments	arg type	description
font	1	number	select a new font from the local <code>fonts</code> table
char	1	number	typeset this character number from the current font, and move right by the character's width
node	1	node	output this node (list), and move right by the width of this list
slot	2	number	a shortcut for the combination of a font and char command
push	0		save current position
nop	0		do nothing
pop	0		pop position
rule	2	2 numbers	output a rule <i>ht * wd</i> , and move right.
down	1	number	move down on the page
right	1	number	move right on the page
special	1	string	output a <code>\special</code> command
image	1	image	output an image (the argument can be either an <code><image></code> variable or an <code>image_spec</code> table)
comment	any	any	the arguments of this command are ignored

Here is a rather elaborate glyph commands example:

```
...
commands = {
  {'push'},           -- remember where we are
  {'right', 5000},    -- move right about 0.08pt
  {'font', 3},        -- select the fonts[3] entry
  {'char', 97},       -- place character 97 (ASCII 'a')
  {'pop'},            -- go all the way back
  {'down', -200000},  -- move upwards by about 3pt
  {'special', 'pdf: 1 0 0 rg'} -- switch to red color
  {'rule', 500000, 20000} -- draw a bar
  {'special', 'pdf: 0 g'} -- back to black
}
...
```

The default value for `font` is always 1 at the start of the `commands` array. Therefore, if the virtual font is essentially only a re-encoding, then you do usually not have create an explicit 'font' command in the array.

Rules inside of `commands` arrays are built up using only two dimensions: they do not have depth. For correct vertical placement, an extra `down` command may be needed.

Regardless of the amount of movement you create within the `commands`, the output pointer will always move by exactly the width that was given in the `width` key of the character hash. Any movements that take place inside the `commands` array are ignored on the upper level.



7.2.1 Artificial fonts

Even in a ‘real’ font, there can be virtual characters. When LuaT_EX encounters a `commands` field inside a character when it becomes time to typeset the character, it will interpret the commands, just like for a true virtual character. In this case, if you have created no ‘fonts’ array, then the default (and only) ‘base’ font is taken to be the current font itself. In practice, this means that you can create virtual duplicates of existing characters which is useful if you want to create composite characters.

Note: this feature does *not* work the other way around. There can not be ‘real’ characters in a virtual font! You cannot use this technique for font re-encoding either; you need a truly virtual font for that (because characters that are already present cannot be altered).

7.2.2 Example virtual font

Finally, here is a plain T_EX input file with a virtual font demonstration:

```
\directlua {
  callback.register('define_font',
    function (name,size)
      if name == 'cmr10-red' then
        f = font.read_tfm('cmr10',size)
        f.name = 'cmr10-red'
        f.type = 'virtual'
        f.fonts = {{ name = 'cmr10', size = size }}
        for i,v in pairs(f.characters) do
          if (string.char(i)):find('[taco hanshartmut]') then
            v.commands = {
              {'special','pdf: 1 0 0 rg'},
              {'char',i},
              {'special','pdf: 0 g'},
            }
          else
            v.commands = {{ 'char',i }}
          end
        end
      else
        f = font.read_tfm(name,size)
      end
      return f
    end
  )
}
```




```
\font\myfont = cmr10-red at 10pt \myfont This is a line of text \par  
\font\myfontx= cmr10 at 10pt \myfontx Here is another line of text \par
```





8 Nodes

8.1 Lua node representation

TEX's nodes are represented in Lua as userdata object with a variable set of fields. In the following syntax tables, such the type of such a userdata object is represented as `<node>`.

The current return value of `node.types()` is: `hlist` (0), `vlist` (1), `rule` (2), `ins` (3), `mark` (4), `adjust` (5), `disc` (7), `whatsit` (8), `math` (9), `glue` (10), `kern` (11), `penalty` (12), `unset` (13), `style` (14), `choice` (15), `noad` (16), `op` (17), `bin` (18), `rel` (19), `open` (20), `close` (21), `punct` (22), `inner` (23), `radical` (24), `fraction` (25), `under` (26), `over` (27), `accent` (28), `vcenter` (29), `fence` (30), `math_char` (31), `sub_box` (32), `sub_mlist` (33), `math_text_char` (34), `delim` (35), `margin_kern` (36), `glyph` (37), `align_record` (38), `pseudo_file` (39), `pseudo_line` (40), `page_insert` (41), `split_insert` (42), `expr_stack` (43), `nested_list` (44), `span` (45), `attribute` (46), `glue_spec` (47), `attribute_list` (48), `action` (49), `temp` (50), `align_stack` (51), `movement_stack` (52), `if_stack` (53), `unhyphenated` (54), `hyphenated` (55), `delta` (56), `passive` (57), `shape` (58), `fake` (100), but as already mentioned, the math and alignment nodes in this list are not supported at the moment. The useful list is described in the next sections.

8.1.1 Auxiliary items

A few node-typed userdata objects do not occur in the 'normal' list of nodes, but can be pointed to from within that list. They are not quite the same as regular nodes, but it is easier for the library routines to treat them as if they were.

8.1.1.1 glue_spec items

Skips are about the only type of data objects in traditional TEX that are not a simple value. The structure that represents the glue components of a skip is called a `glue_spec`, and it has the following accessible fields:

key	type	explanation
<code>width</code>	number	
<code>stretch</code>	number	
<code>stretch_order</code>	number	
<code>shrink</code>	number	
<code>shrink_order</code>	number	

These objects are reference counted, so there is actually an extra field named `ref_count` as well. This item type will likely disappear in the future, and the glue fields themselves will become part of the nodes referencing glue items.



8.1.1.2 attribute_list and attribute items

The newly introduced attribute registers are non-trivial, because the value that is attached to a node is essentially a sparse array of key-value pairs.

It is generally easiest to deal with attribute lists and attributes by using the dedicated functions in the `node` library, but for completeness, here is the low-level interface.

An `attribute_list` item is used as a head pointer for a list of attribute items. It has only one user-visible field:

field	type	explanation
<code>next</code>	<code><node></code>	pointer to the first attribute

A normal node's attribute field will point to an item of type `attribute_list`, and the `next` field in that item will point to the first defined 'attribute' item, whose `next` will point to the second 'attribute' item, etc.

Valid fields in `attribute` items:

field	type	explanation
<code>next</code>	<code><node></code>	pointer to the next attribute
<code>number</code>	number	the attribute type id
<code>value</code>	number	the attribute value

8.1.1.3 action item

Valid fields: `action_type`, `named_id`, `action_id`, `file`, `new_window`, `data`, `ref_count`

These are a special kind of item that only appears inside pdf start link objects.

field	type	explanation
<code>action_type</code>	number	
<code>action_id</code>	number or string	
<code>named_id</code>	number	
<code>file</code>	string	
<code>new_window</code>	number	
<code>data</code>	string	
<code>ref_count</code>	number	

8.1.2 Main text nodes

These are the nodes that comprise actual typesetting commands.

A few fields are present in all nodes regardless of their type, these are:

field	type	explanation
<code>next</code>	<code><node></code>	The next node in a list, or nil



id	number	The node's type (id) number
subtype	number	The node subtype identifier

The **subtype** is sometimes just a stub entry. Not all nodes actually use the **subtype**, but this way you can be sure that all nodes accept it as a valid field name, and that is often handy in node list traversal. In the following tables **next** and **id** are not explicitly mentioned.

Besides these three fields, almost all nodes also have an **attr** field, and there is also a field called **prev**. That last field is always present, but only initialized on explicit request: when the function **node.slide()** is called, it will set up the **prev** fields to be a backwards pointer in the argument node list.

8.1.2.1 hlist nodes

Valid fields: **attr**, **width**, **depth**, **height**, **dir**, **shift**, **glue_order**, **glue_sign**, **glue_set**, **list**

field	type	explanation
subtype	number	unused
attr	<node>	The head of the associated attribute list
width	number	
height	number	
depth	number	
shift	number	a displacement perpendicular to the character progression direction
glue_order	number	a number in the range 0–4, indicating the glue order
glue_set	number	the calculated glue ratio
glue_sign	number	
list	<node>	the body of this list
dir	string	the direction of this box. see 8.1.4.78.1.4.7

8.1.2.2 vlist nodes

Valid fields: As for hlist, except that 'shift' is a displacement perpendicular to the line progression direction.

8.1.2.3 rule nodes

Valid fields: **attr**, **width**, **depth**, **height**, **dir**

field	type	explanation
subtype	number	unused
attr	<node>	
width	number	the width of the rule; the special value –1073741824 is used for 'running' glue dimensions
height	number	the height of the rule (can be negative)



depth	number	the depth of the rule (can be negative)
dir	string	the direction of this rule. see 8.1.4.78.1.4.7

8.1.2.4 ins nodes

Valid fields: [attr](#), [cost](#), [depth](#), [height](#), [spec](#), [list](#)

field	type	explanation
subtype	number	the insertion class
attr	<node>	
cost	number	the penalty associated with this insert
height	number	
depth	number	
list	<node>	the body of this insert
spec	<node>	a pointer to the \splittopskip glue spec

8.1.2.5 mark nodes

Valid fields: [attr](#), [class](#), [mark](#)

field	type	explanation
subtype	number	unused
attr	<node>	
class	number	the mark class
mark	table	a table representing a token list

8.1.2.6 adjust nodes

Valid fields: [attr](#), [list](#)

field	type	explanation
subtype	number	0 = normal, 1 = 'pre'
attr	<node>	
list	<node>	adjusted material

8.1.2.7 disc nodes

Valid fields: [attr](#), [pre](#), [post](#), [replace](#)

field	type	explanation
subtype	number	indicates the source of a discretionary. 0 = the \discretionary command, 1 = the \- command, 2 = added automatically following a - , 3 = added by the



hyphenation algorithm (simple), 4 = added by the hyphenation algorithm (hard, first item), 5 = added by the hyphenation algorithm (hard, second item)

attr	<node>	
pre	<node>	pointer to the pre-break text
post	<node>	pointer to the post-break text
replace	<node>	pointer to the no-break text

The subtype numbers 4 and 5 belong to the ‘of-f-ice’ explanation given elsewhere.

8.1.2.8 math nodes

Valid fields: attr, surround

field	type	explanation
subtype	number	0 = ‘on’, 1 = ‘off’
attr	<node>	
surround	number	width of the <code>\mathsurround</code> kern

8.1.2.9 glue nodes

Valid fields: attr, spec, leader

field	type	explanation
subtype	number	0 = <code>\skip</code> , 1–18 = internal glue parameters, 100 = <code>\leaders</code> , 101 = <code>\cleaders</code> , 102 = <code>\xleaders</code>
attr	<node>	
spec	<node>	pointer to a glue_spec item
leader	<node>	pointer to a box or rule for leaders

8.1.2.10 kern nodes

Valid fields: attr, kern

field	type	explanation
subtype	number	0 = from font, 1 = from <code>\kern</code> or <code>\/</code> , 2 = from <code>\accent</code>
attr	<node>	
kern	number	

8.1.2.11 penalty nodes

Valid fields: attr, penalty



field	type	explanation
subtype	number	not used
attr	<node>	
penalty	number	

8.1.2.12 glyph nodes

Valid fields: [attr](#), [char](#), [font](#), [lang](#), [left](#), [right](#), [uchyph](#), [components](#), [xoffset](#), [yoffset](#)

field	type	explanation
subtype	number	bitfield
attr	<node>	
char	number	
font	number	
lang	number	
left	number	
right	number	
uchyph	boolean	
components	<node>	pointer to ligature components
xoffset	number	
yoffset	number	

Valid bits for the [subtype](#) field are:

bit	meaning
0	character
1	glyph
2	ligature
3	ghost
4	left
5	right

See [section 6.16.1](#) for a detailed description of the [subtype](#) field.

8.1.2.13 margin_kern nodes

Valid fields: [attr](#), [width](#), [glyph](#)

field	type	explanation
subtype	number	0 = left side, 1 = right side
attr	<node>	
width	number	
glyph	<node>	



8.1.3 Math nodes

These are the so-called ‘noad’s and the nodes that are specifically associated with math processing. Most of these nodes contain sub-nodes so that the list of possible fields is actually quite small. First, the subnodes:

8.1.3.1 Math kernel subnodes

Many object fields in math mode are either simple characters in a specific family or math lists or node lists. There are four associated subnodes that represent these cases (in the following node descriptions these are indicated by the word `<kernel>`).

The `next` and `prev` fields for these subnodes are unused.

8.1.3.1.1 `math_char` and `math_text_char` subnodes

Valid fields: `attr`, `fam`, `char`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>char</code>	number	
<code>fam</code>	number	

The `math_char` is the simplest subnode field, it contains the character and family for a single glyph object. The `math_text_char` is a special case that you will not normally encounter, it arises temporarily during math list conversion (its sole function is to suppress a following italic correction).

8.1.3.1.2 `sub_box` and `sub_mlist` subnodes

Valid fields: `attr`, `list`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>list</code>	<code><node></code>	

These two subnode types are used for subsidiary list items. For `sub_box`, the `list` points to a ‘normal’ vbox or hbox. For `sub_mlist`, the `list` points to a math list that is yet to be converted.

8.1.3.2 Math delimiter subnode

There is a fifth subnode type that is used exclusively for delimiter fields. As before, the `next` and `prev` fields are unused.



8.1.3.2.1 delim subnodes

Valid fields: `attr`, `small_fam`, `small_char`, `large_fam`, `large_char`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>small_char</code>	number	
<code>small_fam</code>	number	
<code>large_char</code>	number	
<code>large_fam</code>	number	

The fields `large_char` and `large_fam` can be zero, in that case the font that is sed for the `small_fam` is expected to provide the large version as an extension to the `small_char`.

8.1.3.3 Math core nodes

First, there are the objects (the T_EXbook calls then ‘atoms’) that are associated with the simple math objects: Ord, Op, Bin, Rel, Open, Close, Punct, Inner, Over, Under, Vcent. These all have the same fields, and they are combined into a single node type with separate subtypes for differentiation.

8.1.3.3.1 simple nodes

Valid fields: `attr`, `nucleus`, `sub`, `sup`

field	type	explanation
<code>subtype</code>	number	see below
<code>attr</code>	<code><node></code>	
<code>nucleus</code>	<code><kernel></code>	
<code>sub</code>	<code><kernel></code>	
<code>sup</code>	<code><kernel></code>	

Operators are a bit special because they occupy three subtypes. `subtype`.

number	node sub type
0	Ord
1	Op, <code>\displaylimits</code>
2	Op, <code>\limits</code>
3	Op, <code>\nolimits</code>
4	Bin



5	Rel
6	Open
7	Close
8	Punct
9	Inner
10	Under
11	Over
12	Vcent

8.1.3.3.2 accent nodes

Valid fields: `attr`, `nucleus`, `sub`, `sup`, `accent`, `bot_accent`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>nucleus</code>	<code><kernel></code>	
<code>sub</code>	<code><kernel></code>	
<code>sup</code>	<code><kernel></code>	
<code>accent</code>	<code><kernel></code>	
<code>bot_accent</code>	<code><kernel></code>	

8.1.3.3.3 style nodes

Valid fields: `attr`, `style`

field	type	explanation
<code>style</code>	string	contains the style

There are eight possibilities for the string value: one of 'display', 'text', 'script', or 'scriptscript'. Each of these can have a trailing ' to signify 'cramped' styles.

8.1.3.3.4 choice nodes

Valid fields: `attr`, `display`, `text`, `script`, `scriptscript`



field	type	explanation
attr	<node>	
display	<node>	
text	<node>	
script	<node>	
scriptscript	<node>	

8.1.3.3.5 radical nodes

Valid fields: attr, nucleus, sub, sup, left, degree

field	type	explanation
attr	<node>	
nucleus	<kernel>	
sub	<kernel>	
sup	<kernel>	
left	<delim>	
degree	<kernel>	Only set by \Uroot

8.1.3.3.6 fraction nodes

Valid fields: attr, width, num, denom, left, right

field	type	explanation
attr	<node>	
width	number	
num	<kernel>	
denom	<kernel>	
left	<delim>	
right	<delim>	

8.1.3.3.7 fence nodes

Valid fields: attr, delim

field	type	explanation
subtype	number	1 = \left , 2 = \middle , 3 = \right
attr	<node>	
delim	<delim>	



8.1.4 whatsit nodes

Whatsit nodes come in many subtypes that you can ask for by running `node.whatsits()`: `write` (1), `close` (2), `special` (3), `local_par` (6), `dir` (7), `pdf_literal` (8), `pdf_refobj` (10), `pdf_refxform` (12), `pdf_refximage` (14), `pdf_annot` (15), `pdf_start_link` (16), `pdf_end_link` (17), `pdf_dest` (19), `pdf_thread` (20), `pdf_start_thread` (21), `pdf_end_thread` (22), `pdf_save_pos` (23), `pdf_thread_data` (24), `pdf_link_data` (25), `open` (0), `late_lua` (35), `fake` (100), `pdf_colorstack` (39), `pdf_save` (41), `cancel_boundary` (43), `close_lua` (36), `pdf_setmatrix` (40), `pdf_restore` (42), `user_defined` (44),

8.1.4.1 open nodes

Valid fields: `attr`, `stream`, `name`, `area`, `ext`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>stream</code>	number	T _E X's stream id number
<code>name</code>	string	file name
<code>ext</code>	string	file extension
<code>area</code>	string	file area (this may become obsolete)

8.1.4.2 write nodes

Valid fields: `attr`, `stream`, `data`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>stream</code>	number	T _E X's stream id number
<code>data</code>	table	a table representing the token list to be written

8.1.4.3 close nodes

Valid fields: `attr`, `stream`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>stream</code>	number	T _E X's stream id number

8.1.4.4 special nodes

Valid fields: `attr`, `data`



field	type	explanation
attr	<node>	
data	string	the \special information

8.1.4.5 language nodes

LuaTeX does not have language whatsits any more. All language information is already present inside the glyph nodes themselves. This whatsit subtype will be removed in the next release.

8.1.4.6 local_par nodes

Valid fields: [attr](#), [pen_inter](#), [pen_broken](#), [dir](#), [box_left](#), [box_left_width](#), [box_right](#), [box_right_width](#)

field	type	explanation
attr	<node>	
pen_inter	number	interline penalty
pen_broken	number	broken penalty
dir	string	the direction of this par. see 8.1.4.78.1.4.7
box_left	<node>	the \localleftbox
box_left_width	number	width of the \localleftbox
box_right	<node>	the \localrightbox
box_right_width	number	width of the \localrightbox

8.1.4.7 dir nodes

Valid fields: [attr](#), [dir](#), [level](#), [dvi_ptr](#), [dvi_h](#)

field	type	explanation
attr	<node>	
dir	string	the direction (but see below)
level	number	nesting level of this direction whatsit
dvi_ptr	number	a saved dvi buffer byte offset
dir_h	number	a saved dvi position

A note on [dir](#) strings. Direction specifiers are three-letter combinations of [T](#), [B](#), [R](#), and [L](#).

These are built up out of three separate items:

- the first is the direction of the ‘top’ of paragraphs.
- the second is the direction of the ‘start’ of lines.
- the third is the direction of the ‘top’ of glyphs.

Each of the three items can have 4 separate values, but the directions of the first and second items always have to be perpendicular to each other, which limits the total to 16.



Inside actual `dir` whatsit nodes, the representation of `dir` is not a three-letter but a four-letter combination. The first character in this case is always either `+` or `-`, indicating whether the value is pushed or popped from the direction stack.

8.1.4.8 pdf_literal nodes

Valid fields: `attr`, `mode`, `data`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>mode</code>	number	the 'mode' setting of this literal
<code>data</code>	string	the <code>\pdfliteral</code> information

8.1.4.9 pdf_refobj nodes

Valid fields: `attr`, `objnum`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>objnum</code>	number	the referenced pdf object number

8.1.4.10 pdf_refxform nodes

Valid fields: `attr`, `width`, `height`, `depth`, `objnum`.

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>width</code>	number	
<code>height</code>	number	
<code>depth</code>	number	
<code>objnum</code>	number	the referenced pdf object number

Be aware that `pdf_refxform` nodes have dimensions that are used by LuaTeX.

8.1.4.11 pdf_refximage nodes

Valid fields: `attr`, `width`, `height`, `depth`, `objnum`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>width</code>	number	
<code>height</code>	number	



depth number
objnum number the referenced pdf object number

Be aware that `pdf_refximage` nodes have dimensions that are used by LuaTeX.

8.1.4.12 pdf_annot nodes

Valid fields: `attr`, `width`, `height`, `depth`, `objnum`, `data`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>width</code>	number	
<code>height</code>	number	
<code>depth</code>	number	
<code>objnum</code>	number	the referenced pdf object number
<code>data</code>	string	the annotation data

8.1.4.13 pdf_start_link nodes

Valid fields: `attr`, `width`, `height`, `depth`, `objnum`, `link_attr`, `action`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>width</code>	number	
<code>height</code>	number	
<code>depth</code>	number	
<code>objnum</code>	number	the referenced pdf object number
<code>link_attr</code>	table	the link attribute token list
<code>action</code>	<code><node></code>	the action to perform

8.1.4.14 pdf_end_link nodes

Valid fields: `attr`

field	type	explanation
<code>attr</code>	<code><node></code>	

8.1.4.15 pdf_dest nodes

Valid fields: `attr`, `width`, `height`, `depth`, `named_id`, `dest_id`, `dest_type`, `xyz_zoom`, `objnum`

field	type	explanation
<code>attr</code>	<code><node></code>	



width	number	
height	number	
depth	number	
named_id	number	is the dest_id a string value?
dest_id	number or string	the destination id
dest_type	number	type of destination
xyz_zoom	number	
objnum	number	the pdf object number

8.1.4.16 pdf_thread nodes

Valid fields: `attr`, `width`, `height`, `depth`, `named_id`, `thread_id`, `thread_attr`

field	type	explanation
attr	<node>	
width	number	
height	number	
depth	number	
named_id	number	is the tread_id a string value?
tread_id	number or string	the thread id
thread_attr	number	extra thread information

8.1.4.17 pdf_start_thread nodes

Valid fields: `attr`, `width`, `height`, `depth`, `named_id`, `thread_id`, `thread_attr`

field	type	explanation
attr	<node>	
width	number	
height	number	
depth	number	
named_id	number	is the tread_id a string value?
tread_id	number or string	the thread id
thread_attr	number	extra thread information

8.1.4.18 pdf_end_thread nodes

Valid fields: `attr`

field	type	explanation
attr	<node>	



8.1.4.19 pdf_save_pos nodes

Valid fields: `attr`

field	type	explanation
<code>attr</code>	<code><node></code>	

8.1.4.20 late_lua nodes

Valid fields: `attr`, `reg`, `data`, `name`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>data</code>	string	data to execute

8.1.4.21 pdf_colorstack nodes

Valid fields: `attr`, `stack`, `cmd`, `data`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>stack</code>	number	colorstack id number
<code>cmd</code>	number	command to execute
<code>data</code>	string	data

8.1.4.22 pdf_setmatrix nodes

Valid fields: `attr`, `data`

field	type	explanation
<code>attr</code>	<code><node></code>	
<code>data</code>	string	data

8.1.4.23 pdf_save nodes

Valid fields: `attr`

field	type	explanation
<code>attr</code>	<code><node></code>	

8.1.4.24 pdf_restore nodes

Valid fields: `attr`



field	type	explanation
attr	<node>	

8.1.4.25 user_defined nodes

User-defined whatsit nodes can only be created and handled from Lua code. In effect, they are an extension to the extension mechanism. The LuaTeX engine will simply step over such whatsits without ever looking at the contents.

Valid fields: attr, user_id, type, value

field	type	explanation
attr	<node>	
user_id	number	id number
type	number	type of the value
value	number	
	string	
	<node>	
	table	

The type can have one of five distinct values:

value	explanation
-------	-------------

97	the value is an attribute node list
100	the value is a number
110	the value is a node list
115	the value is a string
116	the value is a token list in Lua table form





9 Modifications

Besides the expected changes caused by new functionality, there are a number of not-so-expected changes. These are sometimes a side-effect of a new (conflicting) feature, or, more often than not, a change necessary to clean up the internal interfaces.

9.1 Changes from T_EX 3.1415926

- See **chapter 66** for many small changes related to paragraph building, language handling, and hyphenation. Most important change: adding a brace group in the middle of a word (like in `of{}fice`) does not prevent ligature creation.
- There is no pool file, all strings are embedded during compilation.
- `plus 1 filllll` does not generate an error. The extra 'l' is simply typeset.
- The `\endlinechar` can be either added (values 0 or more), or not (negative values). If it is added, the character is always decimal 13 a/k/a `^^M` a/k/a carriage return (This change may be temporary).

9.2 Changes from ϵ -T_EX 2.2

- The ϵ -T_EX functionality is always present and enabled (but see below about T_EX_{Xe}T), so the prepended asterisk or `-etex` switch for `initex` is not needed.
- T_EX_{Xe}T is not present, so the primitives

```
\TeXXeTstate
\beginR
\beginL
\endR
\endL
```

are missing.

- Some of the tracing information that is output by ϵ -T_EX's `\tracingassigns` and `\tracingrestores` is not there.
- Register management in LuaT_EX uses the Aleph model, so the maximum value is 65535 and the implementation uses a flat array instead of the mixed flat&sparse model from ϵ -T_EX.
- `savinghyphcodes` is a no-op. See **chapter 66** for details.
- When `kpathsea` is used to find files, LuaT_EX uses the `ofm` file format to search for font metrics. In turn, this means that LuaT_EX looks at the `OFM FONTS` configuration variable (like Omega and Aleph) instead of `TFM FONTS` (like T_EX and pdfT_EX). Likewise for virtual fonts (LuaT_EX uses the variable `OVF FONTS` instead of `VF FONTS`).

9.3 Changes from pdfT_EX 1.40



- The (experimental) support for snap nodes has been removed, because it is much more natural to build this functionality on top of node processing and attributes. The associated primitives that are now gone are: `\pdfsnaprefpoint`, `\pdfsnapy`, and `\pdfsnapycomp`.
- The (experimental) support for specialized spacing around nodes has also been removed. The associated primitives that are now gone are: `\pdfadjustinterwordglue`, `\pdfprependkern`, and `\pdfappendkern`, as well as the five supporting primitives `\knbscode`, `\stbscode`, `\shbscode`, `\knbcode`, and `\knacode`.
- A number of ‘utility functions’ is removed:

<code>\pdfelapsedtime</code>	<code>\pdffilesize</code>	<code>\pdfstrcmp</code>
<code>\pdfescapehex</code>	<code>\pdflastmatch</code>	<code>\pdfunescapehex</code>
<code>\pdfescapename</code>	<code>\pdfmatch</code>	
<code>\pdfescapestring</code>	<code>\pdfmdfivesum</code>	
<code>\pdffiledump</code>	<code>\pdfresettimer</code>	
<code>\pdffilemoddate</code>	<code>\pdfshellescape</code>	
- A few other experimental primitives are also provided without the extra `pdf` prefix, so they can also be called like this:

<code>\primitive</code>	<code>\ifabsnum</code>
<code>\ifprimitive</code>	<code>\ifabsdim</code>
- The `\pdftexversion` is set to 200.
- The PNG transparency fix from 1.40.6 is not applied (high-level support is pending)
- LFS (pdf Files larger than 2GiB) support is not working yet.

9.4 Changes from Aleph RC4

- The input translations from Aleph are not implemented, the related primitives are not available:

<code>\DefaultInputMode</code>	<code>\noDefaultInputTranslation</code>
<code>\noDefaultInputMode</code>	<code>\noInputTranslation</code>
<code>\noInputMode</code>	<code>\InputTranslation</code>
<code>\InputMode</code>	<code>\DefaultOutputTranslation</code>
<code>\DefaultOutputMode</code>	<code>\noDefaultOutputTranslation</code>
<code>\noDefaultOutputMode</code>	<code>\noOutputTranslation</code>
<code>\noOutputMode</code>	<code>\OutputTranslation</code>
<code>\OutputMode</code>	
<code>\DefaultInputTranslation</code>	
- A small series of bounds checking fixes to `\ocp` and `\ocplist` has been added to prevent the system from crashing due to array indexes running out of bounds.
- The `\hoffset` bug when `\pagedir TRT` is fixed, removing the need for an explicit fix to `\hoffset`
- A bug causing `\fam` to fail for family numbers above 15 is fixed.
- Some bits of Aleph assumed `0` and `null` were identical. This resulted for instance in a bug that sometimes caused an eternal loop when trying to `\show` a box.
- A fair amount of other minor bugs are fixed as well, most of these related to `\tracingcommands` output.



- The number of possible fonts, ocps and ocplists is smaller than their maximum Aleph value (around 5000 fonts and 30000 ocps / ocplists).
- The internal function `scan_dir()` has been renamed to `scan_direction()` to prevent a naming clash.
- The `^^` notation can come in five and six item repetitions also, to insert characters that do not fit in the BMP.
- Glues *immediately after* direction change commands are not legal breakpoints.
- The `\ocp` and `\ocplist` statistics at the end of a run are only printed if OCP's are actually used.

9.5 Changes from standard web2c

- There is no `mltex`
- There is no `enctex`
- The following commandline switches are silently ignored, even in non-Lua mode:

```
-8bit
-translate-file=TCXNAME
-mltex
-enc
-etex
```

- `\openout` whatsits are not written to the log file.
- Some of the so-called web2c extensions are hard to set up in non-kpse mode because `texmf.cnf` is not read: `shell-escape` is off (but that is not a problem because of Lua's `os.execute`), and the paranoia checks on `openin` and `openout` do not happen (however, it is easy for a Lua script to do this itself by overloading `io.open`).
- The 'E' option does not do anything useful.





10 Implementation notes

10.1 Primitives overlap

The primitives

<code>\pdfpagewidth</code>	<code>\pagewidth</code>
<code>\pdfpageheight</code>	<code>\pageheight</code>
<code>\fontcharwd</code>	<code>\charwd</code>
<code>\fontcharht</code>	<code>\charht</code>
<code>\fontchardp</code>	<code>\chardp</code>
<code>\fontcharic</code>	<code>\charit</code>

are all aliases of each other.

10.2 Memory allocation

The single internal memory heap that traditional T_EX used for tokens and nodes is split into two separate arrays. Each of these will grow dynamically when needed.

The `texmf.cnf` settings related to main memory are no longer used (these are: `main_memory`, `mem_bot`, `extra_mem_top` and `extra_mem_bot`). ‘Out of main memory’ errors can still occur, but the limiting factor is now the amount of RAM in your system, not a predefined limit.

Also, the memory (de)allocation routines for nodes are completely rewritten. The relevant code now lives in the C file `luanode.c`, and basically uses a dozen or so avail lists instead of a doubly-linked model. An extra function layer is added so that the code can ask for nodes by type instead of directly requisitioning a certain amount of memory words.

Because of the split into two arrays and the resulting differences in the data structures, some of the Pascal web macros have been duplicated. For instance, there are now `vlink` and `vinfo` as well as `link` and `info`. All access to the variable memory array is now hidden behind a macro called `vmem`.

The implementation of the growth of two arrays (via reallocation) introduces a potential pitfall: the memory arrays should never be used as the left hand side of a statement that can modify the array in question.

The input line buffer and pool size are now also reallocated when needed, and the `texmf.cnf` settings `buf_size` and `pool_size` are silently ignored.

10.3 Sparse arrays

The `\mathcode`, `\delcode`, `\catcode`, `\sfcode`, `\lccode` and `\uccode` tables are now sparse arrays that are implemented in C. They are no longer part of the T_EX ‘equivalence table’ and because



each had 1.1 million entries with a few memory words each, this makes a major difference in memory usage.

These assignments do not yet show up when using the etex tracing routines `\tracingassigns` and `\tracingrestores` (code simply not written yet).

A side-effect of the current implementation is that `\global` is now more expensive in terms of processing than non-global assignments.

See `mathcodes.c` and `textcodes.c` if you are interested in the details.

Also, the glyph ids within a font are now managed by means of a sparse array and glyph ids can go up to index $2^{21} - 1$.

10.4 Simple single-character csnames

Single-character commands are no longer treated specially in the internals, they are stored in the hash just like the multiletter csnames.

The code that displays control sequences explicitly checks if the length is one when it has to decide whether or not to add a trailing space.

10.5 Compressed format

The format is passed through zlib, allowing it to shrink to roughly half of the size it would have had in uncompressed form. This takes a bit more CPU cycles but much less disk I/O, so it should still be faster.

10.6 Binary file reading

All of the internal code is changed in such a way that if one of the `read_xxx_file` callbacks is not set, then the file is read by a C function using basically the same convention as the callback: a single read into a buffer big enough to hold the entire file contents. While this uses more memory than the previous code (that mostly used `getc` calls), it can be quite a bit faster (depending on your I/O subsystem).



11 Known bugs and limitations

The bugs below are going to be fixed eventually.

The top ones will be fixed soon, but in the later items either the actual problem is hard to find, or the code that causes the bug is going to be replaced by a new subsystem soon anyway, or it may not be worth the hassle and the limitations will eventually be documented.

- The current linebreaking implementation still does not yet take all possible breakpoints into account where ligatures are involved in the process. This means that line breaks may change in future versions of LuaTeX, in situations where exotic fonts (with ligatures with 3 parts or more) are combined with languages with exotic hyphenation patterns (where multiple hyphenation points can happen within one such ligature).
- `tex.print()` and `tex.sprint()` do not work if `\directlua` is used in an otp file (in the output of an `expression` rule).
- When used inside `\directlua`, `pdf.print()` should create a literal node instead of flushing immediately.
- Not all of Aleph's direction commands are handled properly in pdf mode, and especially the vertical scripts support is missing almost completely (only `TRT` and `TLT` are routinely tested).
- Node pointers are not always checked for validity, so if you make a mistake in the node list processing, LuaTeX may terminate itself with an assertion error or 'Emergency stop'.
- In dvi generation mode, using a `\textdir` switch inside the preamble of a `\halign` results in overprinted text in the dvi file, because the column width is not taken into account during the final placement phase (this is a bug inherited from Aleph). Also, Aleph apparently dislikes having more than one non-grouped `\textdir` command in a single lined paragraph.





12 TODO

On top of the ‘normal’ extensions that are planned, there are some more specific small feature requests. Whether these will all be included is not certain yet. New requests are welcome but should fit into our ideas, i.e. no new hard coded solutions. Beware, this is not the roadmap, which is somewhat more ambitious.

- Implement the T_EX primitive `\dimension`, cf. `\number`.
- Do something about `\withoutpt` and/or a new register type `\real`?
- Create callback for the automatic creation of missing characters in fonts.
- Do boxes with dual baselines.
- Make the number of the output box configurable.
- Switch all the node lists to a double-linked list.
- Finish the interface from Lua to T_EX’s internals, specially the hash and equivalence table (a small subpart is implementing `\csname` lookups for `tex.box` access).
- Use of Type1C for embedded PostScript font subsets in traditional 8-bit encodings.
- Support font reencoding of 8-bit fonts via char index instead of via map files.
- Attempt to parse ofm level 0 fonts that are masquerading as level 1.



