

NAME

asy – Asymptote: a script-based vector graphics language

SYNOPSIS

asy [*options*] [*file* ...]

DESCRIPTION

Asymptote is a powerful descriptive vector graphics language for technical drawings, inspired by MetaPost but with an improved C++-like syntax. Asymptote provides for figures the same high-quality level of typesetting that LaTeX does for scientific text.

OPTIONS

If no arguments are given, Asymptote runs in interactive mode.

If "-" is given as the file argument, Asymptote reads from standard input.

A summary of options is included below. The effect of most options can be negated by prepending **no** to the option name. Default values for most options may also be entered in the file **.asy/config.asy** in the user's home directory using the long form:

```
import settings;
batchView=true;
```

For a complete description, see the Info files.

-GPUindexing

Compute indexing partial sums on GPU [true].

-GPUinterlock

Use fragment shader interlock [true].

-V,-View

View output; command-line only.

-absolute

Use absolute WebGL dimensions [false].

-a,-align C|B|T|Z

Center, Bottom, Top, or Zero page alignment [C].

-aligndir pair

Directional page alignment (overrides align) [(0,0)].

-antialias n

Antialiasing width for rasterized output [2].

-auto3D

Automatically activate 3D scene [true].

-autobillboard

3D labels always face viewer by default [true].

-autoimport string

Module to automatically import.

-autoplain

Enable automatic importing of plain [true].

- autoplay**
Autoplay 3D animations [false].
- autorotate**
Enable automatic PDF page rotation [false].
- axes3** Show 3D axes in PDF output [true].
- batchMask**
Mask fpu exceptions in batch mode [false].
- batchView**
View output in batch mode [false].
- bw** Convert all colors to black and white [false].
- cd directory**
Set current directory; command-line only.
- cmyk** Convert rgb colors to cmyk [false].
- c,-command string**
Command to autoexecute.
- compact**
Conserve memory at the expense of speed [false].
- compress**
Compress images in PDF output [true].
- d,-debug**
Enable debugging messages [false].
- devicepixelratio n**
Ratio of physical to logical pixels [1].
- digits n**
Default output file precision [7].
- divisor n**
Garbage collect using purge(divisor=n) [2].
- dvisvgmMultipleFiles**
dvisvgm supports multiple files [false].
- embed**
Embed rendered preview image [true].
- exitonEOF**
Exit interactive mode on EOF [true].
- fitscreen**
Fit rendered image to screen [true].
- framedelay ms**
Additional frame delay [0].
- framerate frames/s**
Animation speed [30].

- globalread**
Allow read from other directory [true].
- globalwrite**
Allow write to other directory [false].
- gray** Convert all colors to grayscale [false].
- h,-help**
Show summary of options; command-line only.
- historylines n**
Retain n lines of history [1000].
- ibl** Enable environment map image-based lighting [false].
- iconify**
Iconify rendering window [false].
- image string**
Environment image name [snowyField].
- imageDir string**
Environment image library directory [ibl].
- inlineimage**
Generate inline embedded image [false].
- inlinetex**
Generate inline TeX code [false].
- interactiveMask**
Mask fpu exceptions in interactive mode [true].
- interactiveView**
View output in interactive mode [true].
- interactiveWrite**
Write expressions entered at the prompt to stdout [true].
- k,-keep**
Keep intermediate files [false].
- keepaux**
Keep intermediate LaTeX .aux files [false].
- level n**
Postscript level [3].
- l,-listvariables**
List available global functions and variables [false].
- localhistory**
Use a local interactive history file [false].
- loop** Loop 3D animations [false].
- lossy** Use single precision for V3D reals [false].
- lsp** Interactive mode for the Language Server Protocol [false].

- m, -mask**
Mask fpu exceptions; command-line only.
- maxtile pair**
Maximum rendering tile size [(1024,768)].
- maxviewport pair**
Maximum viewport size [(0,0)].
- multiline**
Input code over multiple lines at the prompt [false].
- multipleView**
View output from multiple batch-mode files [false].
- multisample n**
Multisampling width for screen images [4].
- offline**
Produce offline html files [false].
- O, -offset pair**
PostScript offset [(0,0)].
- f, -outformat format**
Convert each output file to specified format.
- o, -outname name**
Alternative output directory/filename.
- p, -parseonly**
Parse file [false].
- pdfreload**
Automatically reload document in pdfviewer [false].
- pdfreloaddelay usec**
Delay before attempting initial pdf reload [750000].
- position pair**
Initial 3D rendering screen position [(0,0)].
- prc** Embed 3D PRC graphics in PDF output [false].
- prerender resolution**
Prerender V3D objects (0 implies vector output) [0].
- prompt string**
Prompt [>].
- prompt2 string**
Continuation prompt for multiline input [..].
- q, -quiet**
Suppress welcome text and noninteractive stdout [false].
- render n**
Render 3D graphics using n pixels per bp (-1=auto) [-1].

- resizestep step**
Resize step [1.2].
- reverse**
reverse 3D animations [false].
- rgb** Convert cmyk colors to rgb [false].
- safe** Disable system call [true].
- scroll n**
Scroll standard output n lines at a time [0].
- shiftHoldDistance n**
WebGL touch screen distance limit for shift mode [20].
- shiftWaitTime ms**
WebGL touch screen shift mode delay [200].
- spinstep deg/s**
Spin speed [60].
- svgemulation**
Emulate unimplemented SVG shading [true].
- tabcompletion**
Interactive prompt auto-completion [true].
- tex engine**
latex|pdflatex|xelatex|lualatex|tex|pdfTeX|luatex|context|none [latex].
- thick** Render thick 3D lines [true].
- thin** Render thin 3D lines [true].
- threads**
Use POSIX threads for 3D rendering [true].
- toolbar**
Show 3D toolbar in PDF output [true].
- s,-translate**
Show translated virtual machine code [false].
- twice** Run LaTeX twice (to resolve references) [false].
- twosided**
Use two-sided 3D lighting model for rendering [true].
- u,-user string**
General purpose user string.
- v,-verbose**
Increase verbosity level (can specify multiple times) [0].
- version**
Show version; command-line only.
- vibrateTime ms**
WebGL shift mode vibrate duration [25].

-viewportmargin pair

Horizontal and vertical 3D viewport margin [(0.5,0.5)].

-wait Wait for child processes to finish before exiting [false].

-warn string

Enable warning; command-line only.

-webgl2

Use webgl2 if available [false].

-where

Show where listed variables are declared [false].

-wsl Run asy under the Windows Subsystem for Linux. [false].

-xasy Interactive mode for xasy [false].

-zoomPinchCap limit

WebGL maximum zoom pinch [100].

-zoomPinchFactor n

WebGL zoom pinch sensitivity [10].

-zoomfactor factor

Zoom step factor [1.05].

-zoomstep step

Mouse motion zoom step [0.1].

SEE ALSO

Asymptote is documented fully in the asymptote Info page. The manual can also be accessed in interactive mode with the "help" command.

AUTHOR

Asymptote was written by Andy Hammerlindl, John Bowman, and Tom Prince.

This manual page was written by Hubert Chan for the Debian project (but may be used by others).