### **NAME**

dvitype, odvitype – translate a dvi file for humans

### **SYNOPSIS**

**dvitype** *dvi* name[.**dvi**]

### DESCRIPTION

This manual page is not meant to be exhaustive. The complete documentation for this version of T<sub>E</sub>X can be found in the info file or manual *Web2C*: A TeX implementation.

The **dvitype** program translates a DVI (DeVice Independent) file output by (for example) **tex**(1) or **gftodvi**(1), to a file that humans can read. It also serves as a DVI file-validating program (i.e., if **dvitype** can read it, it's correct) and as an example of a DVI-reading program for future device drivers.

The output file can include all commands, just the important ones, or none at all (in which case only errors are reported). A subinterval of pages may be selected for transliteration; the magnification and resolution of the "output device" may be changed; and so on. All options are specified with an on-line dialog.

The .dvi extension is supplied if omitted from dvi\_name. The output goes to stdout.

### **OPTIONS**

# -dpi=REAL

Set resolution to *REAL* pixels per inch; default 300.0.

# -magnification=*NUMBER*

Override existing magnification with NUMBER.

### -max-pages=*NUMBER*

Process *NUMBER* pages; default one million.

## -output-level=*NUMBER*

Verbosity level, from 0 to 4; default 4.

### -page-start=PAGE-SPEC

Start at *PAGE-SPEC*, for example '2' or '5.\*.-2'.

## -show-opcodes

Show numeric opcodes (in decimal).

### **ENVIRONMENT**

The environment variable TEXFONTS is used to search for the TFM files used in the DVI file. See tex(1) for the details of the searching. If TEXFONTS is not set, it uses the system default.

# **SEE ALSO**

```
gftype(1), pktype(1). Donald E. Knuth, T_FXware.
```

## **AUTHORS**

Donald E. Knuth wrote the program. It was published as part of the  $T_EX$  ware technical report, available from the  $T_EX$  Users Group. Howard Trickey and Pavel Curtis originally ported it to Unix.