

**NAME**

**ovf2ovp** – convert virtual font file and associated font metrics to property-list format

**SYNOPSIS**

**ovf2ovp** [*options*] *ovfname*[.ovf] [*ofmname*[.ofm] [*ovpfile*[.ovp]]]

**DESCRIPTION**

**ovf2ovp** translates a virtual font (OVF) file, *ovfname*, and its companion font metric (OFM) file, *ofmname*, into a human-readable property-list format. The program writes to standard output (by default) or to a file specified as *ovpname*.

The program also works with TeX VF and TFM files, producing TeX VPL files.

**OPTIONS**

(Same as **ofm2opl**).

**-charcode-format=type**

output character codes according to *type*, either ‘hex’, ‘octal’ or ‘ascii’. Default is ‘hex’; ‘ascii’ says to use ASCII for letters and digits, hex for all else.

**-char-format=stype**

output character codes according to *stype*, either ‘num’ or ‘ascii’. Default is ‘num’; ‘ascii’ as in -charcode-format. (These two redundant options both exist only for historical compatibility.)

**-num-format=ntype**

output numbers according to *ntype*, either ‘hex’ or ‘octal’; default is hex.

**-text-format=ttype**

output coding scheme and family according to *ttype*, either ‘mixed’ or ‘upper’ case; default is mixed.

**-help** display a brief summary of syntax and options

**-verbose**

display progress reports

**-version**

output version information and exit

**FILES**

*ovpfile* Omega Virtual Property List file

*ofmname*

Omega Font Metric file

*ovfname*

Omega Virtual Font file

**BUGS**

Send bug reports to <<http://lists.tug.org/tex-k>> (mailing list); may also check if the same bug is present in **vftovp**(1). General discussion of Omega (and Aleph) can take place on the <<http://lists.tug.org/omega>> mailing list.

**SEE ALSO**

**omega**(1), **aleph**(1), **ofm2opl**(1), **ovp2ovf**(1), **pltotf**(1), **tftopl**(1), **vftovp**(1), **vptovf**(1)

## AUTHOR

According to the WEB documentation:

**VFtoVP** is an extended version of the program **TFtoPL**, which is part of the standard TeXware library. The idea of a virtual font was inspired by the work of David R. Fuchs who designed a similar set of conventions in 1984 while developing a device driver for ArborText, Inc. He wrote a somewhat similar program called **AMFtoXPL**.

Thus, **ovf2ovp** is based on the WEB source code for **vftovp**(1), although nowadays it is a link to **omfonts**, implemented entirely in C.

The primary authors of Omega are John Plaice and Yannis Haralambous. Omega (and Aleph) are now maintained as part of TeX Live.

This manual page was written by C.M. Connelly <cmc@debian.org>, for the Debian GNU/Linux system. It may be used by other distributions without contacting the author. Any mistakes or omissions in the manual page are my fault; inquiries about or corrections to this manual page should be directed to me (and not to the primary author).