

NAME

texlinks – maintain symbolic links from format to engine

SYNOPSIS

texlinks [*OPTIONS...*] *DIRECTORIES...*

DESCRIPTION

texlinks is used to create or recreate symbolic links from formats to engines according to the information in *fmtutil.cnf* or a file specified with **--cnffile**.

DIRECTORIES is an optional list of directories in which to operate. If no directories are specified the list of directories depends on the **--multiplatform** option.

OPTIONS

--cnffile *FILE* or **-f** *FILE*

use file as configuration file (default: *fmtutil.cnf*)

--help or **-h**

show some help text

--multiplatform or **-m**

operate in all platform-specific directories (default: operate only in the directory for this platform)

--silent or **-s**

silently skip over existing scripts/binaries instead of printing a warning

--unlink or **-u**

Unlink previously created symlinks

--verbose or **-v**

+set verbose mode on (default: off)

FILES

fmtutil.cnf

default configuration file

SEE ALSO

fmtutil(1), **fmtutil.cnf(5)**

Web page: <<https://tug.org/texlive/>>

BUGS

Email bug reports to <<https://lists.tug.org/tex-k>> (public mailing list).

AUTHOR

texlinks was written by Thomas Esser in 1999. **texlinks** has been released into the public domain.

This manual page was written by C.M. Connelly for the Debian GNU/Linux system. It is now maintained as part of TeX Live.