


Molecular Coding Format manual

Akira Yamaji

January 29, 2017

Located at <http://www.ctan.org/pkg/mcf2graph>



Contents

1	Introduction	1
2	MCF syntax	1
2.1	Make bond	1
2.1.1	Chain	1
2.1.2	Jump and branch bond	1
2.1.3	Branch bond	1
2.1.4	Connect atom	1
2.1.5	Ring	1
2.1.6	Rotate current angle	1
2.2	Change bond type	2
2.2.1	Double,triple	2
2.2.2	Wedge	2
2.2.3	Vector	2
2.2.4	Dotted,wave	2
2.2.5	Broad	2
2.2.6	Change multi bond type	2
2.2.7	Over line	2
2.3	Change bond length	2
2.3.1	Chain length	2
2.3.2	Ring length	2
2.4	Change atom	3
2.4.1	Insert atom	3
2.4.2	Addressed atom	3
2.4.3	Brock address	3
2.4.4	Absolute address	3
2.4.5	Relative address	3
2.5	Fuse ring	3
2.5.1	Attached 1 bond	3
2.5.2	Attached 2 bond	3
2.5.3	Attached 3 bond	4
2.5.4	Attached 4 bond	4
2.5.5	Spiro ring	4
2.6	Substituent	4
2.6.1	Insert substituent	4
2.6.2	Insert modified substituent	4
2.6.3	Add substituent	4
2.6.4	Add modified substituent	4
2.7	Chain environment	5
2.7.1	Horizontal,vertical	5
2.7.2	Left-right,right-left	5
2.7.3	Fixed angle,multi angle	5
2.8	Miscellaneous	5
2.8.1	Change atom and Substituent	5
2.8.2	Change color	5
2.8.3	Make block	5
2.8.4	Chain start multiple characters	5
2.8.5	User definition	5
2.8.6	Inline definition	5
3	Option parameter	6
3.1	Size parameter	6
3.1.1	Font size	6
3.1.2	Margin left and right	6
3.1.3	Margin top and bottom	6
3.1.4	Offset thickness of bond	6
3.1.5	Offset of doublebond gap	6
3.1.6	Offset of atom width	6
3.1.7	Offset of wedge width	6
3.1.8	Max bond length	6
3.2	Ratio parameter	6
3.2.1	Thickness/bond length	6
3.2.2	Char/bond thickness	6
3.2.3	Bondgap/bond length	6
3.2.4	Atom/bond length	6
3.2.5	Wedge/bond length	7
3.2.6	Font atom gap/atom length	7
3.2.7	Chain/ring length	7
3.2.8	Zebra gap/bond length	7
3.3	Drawing mode	7
3.3.1	Numbering atom	7
3.3.2	Numbering bond	7
3.3.3	Clipping mode	7
3.3.4	Solid mode	7
3.3.5	Expand mode	8
3.3.6	Substituent off mode	8
3.3.7	Single bond mode	8
3.4	Frame	8
3.4.1	Font frame	8
3.4.2	Molecular frame	8
3.4.3	Atom frame	8
4	Function	8
4.1	Function MCd()	8
4.2	Function MCf()	8
4.3	Function EXT()	9
4.4	Function ext()	9
4.5	Local parameter setting	9
4.6	Global parameter setting	9
5	Output information	10
5.1	Output molecular information	10
5.2	Output additional information	10
5.3	Change aux information delimiter	10
5.4	Fixed aux information	10
6	MCF example	11
7	Example to use mcf2graph	13
7.1	Molecular definition file	13
7.2	Information auxfile output	14
7.3	Report output	15
7.4	Molfile output	16
7.5	LuaTeX file example	17
7.6	LaTeX file example	18

1 Introduction

Molecular Coding Format(MCF) is new linear notation represent chemical structure diagrams. This 'Coding' is named from coding(programing) technique like addressing,grouping,macro,etc. There are no Meta language commands in MCF. mcf2graph.m convert MCF file to graphics file pk font,PNG,SVG,EPS or MDL MOL file(V2000).


2 MCF syntax

2.1 Make bond

2.1.1 Chain


real number plus (+): anticlockwise
real number minus(-): clockwise

<30,-60,60,-90,120,-90,60



! : take value 60 or -60 depend on
current angle and enviroment
!6 : !,!,!,!,!,!,!


<30,! ,! ,! ,! ,! ,!
<30,!6



2.1.2 Jump and branch bond


n* : Jump to An
** An: atom number(-999<=n<=4095)

<30,!6,3*,0,! ,5*,-30



3\ : 3*,0


<30,!6,3\,! ,



2.1.3 Branch bond


2\ : 2*,0
4*\ : 4*,0~wf
6* : 6*,0~zf
8\\ : 8*,0~dm

<30,!8,2\,! ,4*\,! ,6*,! ,8\\,! ,



2\~dr : 2*,0~dr
4\'1.5 : 4*,0\'1.5
6\^15 : 6*,0^15


<-30,!6,
2\~dr,! ,
4\'1.5,-90,
6\^15,-60



2.1.4 Connect atom


&n : Connect to An

<30,!6,3\,! ,&5



2.1.5 Ring


?n : n membered ring(3<=n<=20)
?6 : <-120,60,60,60,60,60,&1
?6



2.1.6 Rotate current angle

<angle : rotate current angle

0,0,<90,0,<-90,0,0,\$(1,2,3,4,5)vf




2.2 Change bond type

2.2.1 Double, triple

a~type : ~type,a
dm : double middle
dl : double left side
dr : double right side
db : double left or right side
tm : triple
!! : !~db / !!! : !~tm


<30,!~dm,!~dl,!~dr,!~db,!~db,!~tm
<30,!~dm,!~dl,!~dr,!! ,!! ,!!



2.2.2 Wedge

wf : wedge forward / wb : wedge backward
zf : wedge dotted
zb : wedge dotted backward


<30,!~wf,!~wb,!~zf,!~zb



2.2.3 Vector

vf:vector forward / vb:vector backward


<30,!~vf,!~vb



2.2.4 Dotted, wave

Bn=bond type : change bond type at Bn
dt : dotted / ww : wave


<30,!3,1=dt,3=ww



2.2.5 Broad

bd : broad / bz : broad dotted


<30,!3,1=bd,3=bz



2.2.6 Change multi bond type

\$(2,4,6)dr : 2=dr,4=dr,6=dr


<30,!7,\$(2,4,6)dr



2.2.7 Over line

si_ : single over line
wf_ : wedge forward over line
wb_ : wedge backward over line
bd_ : broad over line

<-30,!8,!60,90'8,
@(2~si_,4~wf_,6~wb_,8~bd_)/_ '2




2.3 Change bond length

2.3.1 Chain length

(!,!n)'length : change length of !,!n


<30,!2,!2'1.2,!2

** !2'1.2 : ''1.2,!2



''length : change all bond length after


<30,!2, ''1.2,!4



2.3.2 Ring length

?n'length : change ring length

?6,4\,?6'1.2




2.4 Change atom

2.4.1 Insert atom

Insert hetero atom

<30,!2,0,!2,N,!2




2.4.2 Addressed atom

2:0 : change A2 C to O

@(3,5)N : change A3,A5 C to N


<30,!6,2:0,@(3,5)N



2.4.3 Brock address


| : divide brock

?6,4\,|,?6,2:0



|| : reset brock address

?6,4\,|,?6,||,2:N




2.4.4 Absolute address

#2:N : change A#2 C to N

** #n : (1<=n<=3095)

?6,4\,|,?6,#2:N




2.4.5 Relative address

-2:N : change A(-2) C to N

** -n : (1<=n<=999)

?6,4\,?6,-2:N




2.5 Fuse ring

2.5.1 Attached 1 bond

?6,3=?6 : fuse ?6 at B3


** Bn(n:-999<=n<=4095): bond number

?6,3=?6



** fused ring size depend on attached bond length

?6,4\,?6'1.2,5=?6,11=?6




?6,3=?6[13] : fuse ?6[13] at B3

?6[13]: 6 membered ring scaled 13/10


** ?m[n] (5<=m<=8,11<=n<=15)

?6,3=?6[13]



?6,\$(-3,-4,-4,-2,-2,-4,-4)?6

?6,\$(4,8,13,20,25,28,33)?6



2.5.2 Attached 2 bond

(4,11)=?6[4] : fuse 4/6 ring to B11..B4

(4,11)=?5[3] : fuse 3/5 ring to B11..B4


(4,11)=?4[2] : fuse 2/4 ring to B11..B4

** ?m[n] (4<=m<=6,n=m-2)

1:MCd(1,.7)(0,0)(<30,?6,3=?6,(11,4)=?6[4])

2:MCd(1,.6)(.54,1)(<30,?6,3=?6,(11,4)=?5[3])


3:MCd(1,.6)(1,0)(<30,?6,3=?6,(11,4)=?4[2])



2.5.3 Attached 3 bond

(16,4)=?6[3] : fuse 3/6 ring to B16..B4
 (16,4)=?5[2] : fuse 2/5 ring to B16..B4
 ** ?m[n] (5<=m<=6,n=m-3)

1:MCd(1,.55)(0,0)(?6,\$(3,10)?6,(16,4)=?6[3])
 2:MCd(1,.55)(1,0)(?6,\$(3,10)?6,(16,4)=?5[2])




2.5.4 Attached 4 bond

(21,4)=?6[2] : fuse 2/6 ring to B21..B4

MCf(<-30,?6,\$(3,10,15)?6,(21,4)=?6[2])

** ?m[n] (m=6,n=2)




2.5.5 Spiro ring

4*,?5 : add ?5(5 membered ring) at A4

<30,!6,4*,?5

An* : jump to An




2.6 Substituent

2.6.1 Insert substituent

/ : single

<30,!/,Me,!,/Et,!3,/Pr,!,/iPr,
 !3,/tBu,!,/Ph^-30,!)


** Me:methyl(/_) Et:ethyl(!)
 Pr:propyl(!2) iPr:isopropyl
 tBu:tertial buthyl Ph:phenyl



2.6.2 Insert modified substituent


// : double (double middle)
 */ : wedge forward
 /* : wedge dotted forward
 ** : direct

<30,!/,/0,!,/*H,!,*/H,!,/?3,!,**?3,!




~ : change type
 ^ : change angle
 ' : change length
 > : change enviroment

<30,'^1,!,/_~zf'^2^30,
 !2,*/!2>lr,!2,*/!2>r1,!)



2.6.3 Add substituent


<-30,!17,2:/_,4:/!,6:/!2,
 10:/iPr,14:/tBu,16:/Ph^-60



2.6.4 Add modified substituent


~,^,' : change type,angle,length

<-30,!6,
 @(2~wf,4~zf,6^-30)/_



~,^,'> : change angle,length,environment

<30,!7'^1,
 3:/*'^2^30,5:*/!2>lr,7:*/!2>r1




2.7 Chain environment

2.7.1 Horizontal,vertical

>hz : horizontal enviroment (default)
>vt : vertical enviroment


```
?4,@(3^-90,3^-30,3^90)/'(!3,"{hz}")>hz,  
  @(1^-60,1^2,1^60)/'(!2,"{vt}")>vt
```



2.7.2 Left-right,right-left

>lr : left-right enviroment
>rl : right-left enviroment


```
<30,!6,  
  @(3^-30,3,3^30)/'(!3,"{lr}")>lr,  
  @(5^-30,5,5^30)/'(!3,"{rl}")>rl
```



2.7.3 Fixed angle,multi angle

>45 : fixed angle enviroment
>'(-90,90,-90) : multi angle enviroment

```
<-30,!6,@(2>45)/'(!3,"{45}")  
  @(6>'(-90,90,-90))/'(!3,"{(-90,90,-90)}")
```




2.8 Miscellaneous

2.8.1 Change atom and Substituent

NH,S0,S00 :
 inset hetero atom and substituent
 simultaneously


```
<30,!2,NH,! ,S0,! ,S00,!3
```



2.8.2 Change color

@(5)green : change color of A5 green
\$(3)red : change color of B3 red
** METAFONT ignore color command


```
<30,Ph,@(2,5)N,2:red,5:blue,3:green
```



2.8.3 Make block

{ : start brock
} : end brock


```
<30,!2,{,'1.2,!2},!2
```




2.8.4 Chain start multiple characters

if chain start multi charactor string,
use !0 instead of !

```
MCf(<30,COOH,!0,!3,COOH)
```




```
MCf(<30,COOH,!4,COOH)
```



2.8.5 User definition

iBuOH : user defined substructure


```
iBuOH:= '(!,/_,!,OH)  
MCf(<30,?6,@(4,6)/iBuOH)
```



2.8.6 Inline definition

Insert user defined substructure

```
<30,!3,/ '(!,/_,!,OH),!3
```




3 Option parameter

3.1 Size parameter


3.1.1 Font size

```
beginfont("EN:Caffeine")
font_wd#:=30mm#; %<=font width
font_ht#:=20mm#; %<=font height
MCf(<30,?6,-4=?5,$(3,8)d1,@(2,6,7,9)N,
    @(2,6,9)/_,@(1,5)//0) endfont
```




3.1.2 Margin left and right

default: margin_left_right=0.4mm




3.1.3 Margin top and bottom

default: margin_top_bottom=0.4mm




3.1.4 Offset thickness of bond

default: offset_thickness#=0.2pt#




3.1.5 Offset of doublebond gap

default: offset_bond_gap#=0.3pt#




3.1.6 Offset of atom width

default: offset_atom#=0.8pt#




3.1.7 Offset of wedge width

default: offset_wedge#=0.4pt#



3.1.8 Max bond length


default: max_bond_length#=10mm#



3.2 Ratio parameter


3.2.1 Thickness/bond length

default: ratio_thickness_bond=0.015




3.2.2 Char/bond thickness

default: ratio_char_bond=1.5




3.2.3 Bondgap/bond length

default: ratio_bondgap_bond= 0.15




3.2.4 Atom/bond length

default: ratio_atom_bond= 0.36




3.2.5 Wedge/bond length

default: ratio_wedge_bond=0.12




3.2.6 Font atom gap/atom length

default: ratio_atomgap_atom= 0.050




3.2.7 Chain/ring length

default: ratio_chain_ring= 0.66



3.2.8 Zebra gap/bond length


default: ratio_zebragap_bond=0.12



3.3 Drawing mode


3.3.1 Numbering atom

```
numberA_start:=3; numberA_end:=8;
default: sw_numberA=0 :
      numberA_start=1 numberA_end=4095
```




3.3.2 Numbering bond

```
numberB_start:=3; numberB_end:=8;
default: sw_numberB=0 :
      numberB_start=1 numberB_end=4095
```



3.3.3 Clipping mode

```
sw_clip:=0;
MCd(1,0.7)(0.2,0.3)(Ph)
MCd(1,0.7)(0.8,0.7)(Ph)
** default: sw_clip=0
```




```
sw_clip:=1;
MCd(1,0.7)(0.2,0.3)(Ph)
MCd(1,0.7)(0.8,0.7)(Ph)
```




3.3.4 Solid mode


```
(fit to font size)
sw_solid=0    ** default
```




```
(solid ratio bond/font width)
sw_solid:=1;
ratio_bond_width=0.1
font_width=60mm
(bond_len#=60mm#*0.1=6mm#)
** ignore bond_len#
```



```
(solid bond length)
sw_solid:=2;
bond_len#=10mm#
** ignore ratio_bond_width
```




```
(solid bond length and clip)
sw_solid:=2;
sw_clip:=1;
bond_len#=10mm#
```



3.3.5 Expand mode

default: sw_expand=0




0 :default

1

3.3.6 Substituent off mode

default: sw_subst_off=0




0 :default

1

3.3.7 Single bond mode

default: sw_bond_single=0



0 :default

1

3.4 Frame

3.4.1 Font frame


(Draw font frame)

margin_left_right:=5mm;

margin_top_bottom:=2mm;


sw_font_frame:=1;

MCf(<30,Ph,4:/Cl,3:/F)




(Draw frame inside margin)

sw_font_frame=2



(Draw both frame)

sw_font_frame=3




3.4.2 Molecular frame

sw_mol_frame:=1;

MCd(1,.5)(1,0.5)(<30,Ph,4:/Cl,3:/F)

** default: sw_mol_frame=0




3.4.3 Atom frame

sw_atom_frame:=1;

MCf(<30,COOH,!0,COOH)

** default: sw_atom_frame=0



4 Function

4.1 Function MCd()

(Draw molecular structure)

MCd(a,b)(c,d)(...)

a: ratio molecular width/font width

b: ratio molecular height/font height

c: x axis position


d: y axis position

beginfont()

MCd(1,0.8)(0.2,0.9)(<30,Ph,3:/F,4:/Cl)

MCd(1,0.8)(0.8,0.1)(<30,Ph,3:/F,4:/Cl)

endfont



4.2 Function MCf()

(Draw molecular fit to font size)

MCf(...) : MCd(1,1)(0.5,0.5)(...)

beginfont()

font_wd#:=25mm#;

font_ht#:=15mm#;

MCf(<30,Ph)

endfont



beginfont()

font_wd#:=13mm#;

font_ht#:=25mm#;

MCf(<30,Ph)

endfont



4.3 Function EXT()


(Extra graphic to font)

```
w: font width
h: font height
wd: font width-margin_left_right*2
ht: font height-margin_top_bottom*2
p0: x=margin_left_right
      y=margin_top_bottom
n: molecular number
p[m]: molecular origin position
      (1<=m<=molecular count)
```

(Function)

```
puts(pos)(string):
  put string at pos
use_font(wd#):
  make string font for puts()
  (font width = wd#)
draw_vector(pos,angle,length):
  draw vector at pos

%-----
beginfont()
sw_font_frame:=3;
%-----
MCd(1,0.8)(0.1,0.5)
  (<30,Ph,2:/OH,5:/OH)
MCd(1,0.8)(0.9,0.5)
  (<30,?6,$(3,6)d1,@(2,5)//O)
%-----
EXT(
  draw ((0,0)--(25mm,0)--(21mm,2mm))
    shifted (0.3w,0.52h);
  draw ((4mm,-2mm)--(0,0)--(25mm,0))
    shifted (0.3w,0.48h)
  draw fullcircle scaled 3mm
    shifted p0;
  drawdot p1
    withpen pencircle scaled 2mm;
  drawdot p2
    withpen pensquare scaled 2mm;
%-----
  use_font(5pt#);
  puts((0.4w,0.6h))("Oxidation");
  puts((0.4w,0.35h))("Reduction");
)
%-----
endfont
```




4.4 Function ext()

(Extra graphic to molecule)

```
wd: molecular width
ht: molecular height
p0: origin of molecular structure
n: atom number
l: bond length
p[m]: atom position of A[m]
a[m]: branch angle of A[m]
      (1<=m<=atom count)
```


beginfont()

```
%-----
MCd(1,0.9)(0.1,0.5)(<30,Ph,3:/F,4:/Cl)
ext(
  drawdot p0 withpen pencircle scaled 2mm;
  draw p0--(p0+(wd,0))--(p0+(wd,ht));
)
%-----
MCd(1,0.9)(0.9,0.5)(<30,Ph,3:/F,4:/Cl)
ext(
  draw_vector(p6,a6-180,l);
  drawdot p0 withpen pensquare scaled 2mm;
  draw p0--(p0+(wd,0))--(p0+(wd,ht));
)
%-----
endfont
```




4.5 Local parameter setting

```
beginfont() MCf(Ph) endfont
beginfont()
  ratio_thickness_bond:=0.05;
  MCf(Ph)
endfont
beginfont() MCf(Ph) endfont
```



4.6 Global parameter setting

```
beginfont() MCf(Ph) endfont
ratio_thickness_bond:=0.05;
beginfont() MCf(Ph) endfont
beginfont() MCf(Ph) endfont
```



5 Output information


5.1 Output molecular information

```
tag3:="cMW"; var3:="calc_weight";
tag4:="cFM"; var4:="calc_formula";
%-----
beginfont()
  MCf(<30,?6,3=d,
      @ (2,6)N,@ (2,6)/_,@ (1,5)//O,
      |,-4=?5,2=d1,@ (1,3)N,3:/_)
endfont
%-----
```

```
% Output to mcf_man_soc-info.aux %%
..... ;C:85;cMW:194.19174;cFM:C8H10N4O2
```

```
** default value
tag1:="F"; var1:="jobname";
tag2:="C"; var2:="char_num";
```

```
cMW:calculated molecular weight
cFM:calculated molecular formula
```




5.2 Output additional information

```
beginfont("EN:Tocopherol","CAS:59-02-9")
  MCf(<30,Ph,3=?6,
      7:O,@ (1,2,5)/_,8:/*_~60,6:/OH,
      8\,|,!12,@ (4,8)/*_,12:/_)
endfont

% Output to mcf_man_soc-info.aux %%
F:mcf_man_soc;C:86;EN:Tocopherol;CAS:59-02-9
.....
```

```
*F:filename *C:char number EN:molecular name
CAS:CAS number *:default output
```




5.3 Change aux information delimiter

```
aux_delimiter:="/";
beginfont("EN:Ampicillin","CAS:69-53-4")
  MCf(<45,?4,2:N,2=?5,-1:S,
      @ (3^45,4^-45)/*H,1://O^15,
      5:/*COOH^-18,@ (6^35,6^-35)/_,
      4*\^75,NH,!,//O,!/*NH2,! ,Ph)
endfont
beginfont(.....)
.....
endfont
.....
```

```
% Output to mcf_man_soc-info.aux %%
F:mcf_man_soc/C:90/EN:Ampicillin/CAS:69-53-4
.....
```

```
**default aux_delimiter=","
```




5.4 Fixed aux information

```
tag3:="N0"; var3:="inf_N0";
tag4:="EN"; var4:="inf_EN";
sw_auxfix:=1;
auxtag_out; % output tag list
%-----
beginfont("EN:Cholesterol","N0:1")
  MCf(
    <30,?6,$(-4,-2)?6,-4=?5,7=d1,
    1:*/OH,@ (4,12)/*/_^60,9:/*H^60,
    10:/*H^180,11:/*H^-60,17:/*H^-54,
    -1\^18,/*_,-60,!3,/_,!
  )
endfont
%-----
beginfont(.....)
.....
endfont
%-----
.....
```

```
% Output to mcf_man_soc-info.aux %%
F;C;N0;EN
mcf_man_soc;91;1;Ampicillin
.....
.....
```


```
** default sw_auxfix=0
```



6 MCF example


Acetamiprid

<30,Ph,2:N,1:/Cl,
4\,!,N,/_,!,/_,!!,N,!,CN




Fenitrothion

<30,!,0,!,P,//S,/O!^160,!,0,!,
|,Ph,3:/_,4:/NO2




Permethrin

<-30,?3,2^-35:*/_-,2^35:/*_,
1\,!!,/Cl,!,Cl,
3\,//0,!,0,!,2,|,Ph,
3\,0,-60,Ph




Endosulfan

<26,?7,7=?6[13],11*,208~wf'1.45,&8~wb,
10=d,@(3,5)0,4:S,4:/0,
@(8,9,10,11,12^-210,12^-150)/Cl




Luciferin

<30,Ph,3=?5,8\,?5,\$(9,16)d,
@(9,14)N,@(7,11)S,
1:/OH,-2:*/COOH




Warfarin

<30,Ph,3=?6,8=d1,
10:0,7:/OH,9:/0,
8\,/Ph'1,60,!,//0,!




Limonin

<30,?6,\$(-3,-4)?6,-5=?3,
-2=wf,-1=wb,6=?5,-4=?6,-5=wf,
@(13,15,17,20)0,@(3,12,21)//0,
@(4~wf^60,8~zf^60,18^35,18^-35)/_,
@(1^60,5^180,16^60)/*H,
14*,|,?5,\$(1,4)d1,3:0




Sesamine

<54,?5,1=?5,
@(4,7)0,@(1^-54,2^54)*H,
#5*\^-12,Ph,|,-3=?5,@(-1,-3)0,
#8*\^-12,Ph,|,-3=?5,@(-1,-3)0




Colchicine

<30,Ph,@(1,2,6)/O!,
-4=?7,-5=?7,
\$(-1,-4,-6)d1,-2:/0,-3:/O!,
9\,NH,!,//0,!




Lycorine

<30,Ph,
-4=?6,-2=?6,6=?5,(9,12)=?5[3],
13=d1,
8:N,@(15,17)O,
9:/*H^180,10:/*H^60,
13:*/OH,14:/*OMe




Gibberellin

<18,?5,3=?7,5=?6[12],
8*,160'1.3,&3,
13=d1,6=wf,8=wb,
5*,40~zf'1,0,60,//0^180,&14~zb,
2:/COOH,7://_,13:*/OH,8:*/OH,
14:*/_,@(1^60,4^60)*/H




Quinine

<30,Ph,3=Ph,7:N,6:/O!,
10\,*/OH,/H~zf^-60,!,
|,?6,2:N,1:*/H^60,
4*\,!!,
2*,165~zf,60,&5~zb




Atoropin

<-30,0,!,//0,!,!,Ph,
#1\~zb^-120,
|,?7,6*\^190'1.02,N,/_,&3~wb,
#3\~wv,!,OH




Rotenone

<-60,?5,\$(-3,-2,-3,-4)?6,
\$(7,9,-2,-4)d1,\$(3,17)dr,
@(2,13,16)O,10:/O, @(11^-60,12^60)*/H,
@(-2,-3)/O!,1*\,/_,!!




Pyrethrin I

<30,?3,@(3^35~wf,3^-35~zf)/_,
1*\,!!iPr,2*,//0,!,0,-36~zb,|,
?5,-2=d,-1:/_, -3:/O,-2\,!4,\$(-1,-3)d1




Validamycin

<30,?6,@(5,6)/OH,3:/!OH>r1,
#4\,0,-60,|,?6,2:O, @(3,4,5)/OH,6:/!OH,
#1\,NH,!,|,?6,2=d1, @(4,5,6)/OH,3:/!OH



Paclitaxel

?6,5=d,3*{,' '1,36,45,45,45,45,},
-4=?6,-4=?4,-1=wb,-3=wf,-1:O,||,
@(4^35,4^-35,6)/_,@(3^-60,15)*/OH,
8:/*H^-60,9:*/_ ^60,10:/O,
1\,0,!,//0,!,*/OH,!,/Ph,
60~wf,NH,-60,//0,60,Ph,
7*,0,-45,//0,60,Ph,11*\,0,-60,//0,60,
12*^-15,0,60,//0,-60



7 Example to use mcf2graph

7.1 Molecular definition file

```
%-----
input mcf2graph.mf;                                     % input macro
%-----
sw_auxout:=1;      % aux(information) file output on > Gloval setting
font_wd#:=60mm#;   % font width                      >
font_ht#:=40mm#;   % font height                     >
var3:="cal_MW"; tag3:="cMW";                          > AUX file table
var4:="cal_FM"; tag4:="cFM";                          >
%%% sw_report:=1;  > Report output
%%% sw_MOLout:=1;  > MOL file output
outputformat:="png"; hppp:=vppp:=0.1;                  > PNG output
outputtemplate:="%j-%3c.png";                         >
%-----
beginfont("NO:1","EN:Ampicillin")                      > begin font(information)
  MCF(<45,?4,2:N,2=?5,-1:S,                             > begin MCF (1)
    @(3^45,4^~45)*H,1://0^15,5:/*COOH^~18,              >
    @(6^35,6^~35)/_,                                    >
    4\^75,NH,!,//0,!/*NH,! ,Ph)                        > end MCF
endfont                                                  > end font
%-----
beginfont("NO:2","EN:Cholesterol")                     > begin font(information)
  MCF(<30,?6,$(-4,-2)?6,-4=?5,7=d1,                    > begin MCF (2)
    1:*/OH,@(4,12)*/_^60,9:*/H^60,                     >
    10:/*H^180,@(11,-1)*H^~60,                         >
    -1\^17,/*_,!4,/_,!)                                > end MCF
endfont                                                  > end font
%-----
beginfont("NO:3","EN:Limonin")                         > begin font(information)
  MCF(<30,?6,$(-3,-4)?6,                                > begin MCF (3)
    -5=?3,-2=wf,-1=wb,6=?5,-4=?6,-5=wf,               >
    @(13,15,17,20)0,@(3,12,21)//0,                     >
    @(4~wf^60,8~zf^60,18^35,18^~35)/_,                 >
    @(1^60,5^180,16^60)*H,                             >
    14\*,|,?5,$(1,4)d1,3:0)                            > end MCF
endfont                                                  > end font
%-----
beginfont("NO:4","EN:beta-carotene")                   > begin font(information)
  MCF(<30,?6,3=d1,@(3,5^35,5^~35)/_,                  > begin MCF (4)
    4\,|,!18,$(1,3,5,7,9,11,13,15,17)dr,               >
    @(3,7,12,16)/_,                                    >
    |,?6,6=d1,@(6,2^35,2^~35)/_)                       > end MCF
endfont                                                  > end font
%-----
beginfont("NO:5","EN:Gibberellin A3");                 > begin font(information)
  MCF(<18,?5,3=?7,5=?6[12],                             > begin MCF (5)
    8*,160'1.3,&3,13=d1,6=wf,8=wb,                     >
    5*,40~zf'1,0,60,//0^180,&14~zb,                   >
    2:/COOH,7://_,13:*/OH,8:/*OH,                     >
    14:*/_,@(1^60,4^60)*H)                             > end MCF
endfont;                                                 > end font
%-----
bye
```

7.2 Information auxfile output

(Insert option parameter setting)

```
sw_auxout:=1;  
** default : sw_auxout=0
```

(Command line)

```
>mpost -s ahandle=0 FILENAME (molecular definition file)
```

(Output)

```
(sw_auxfix=0)  
F:mcf_man_soc;C:1;cMW:349.40462;cFM:C16H19N3O4S;EN:Ampicillin  
F:mcf_man_soc;C:2;cMW:386.6532;cFM:C27H46O;EN:Cholesterol  
F:mcf_exa_soc;C:3;cMW:470.5113;cFM:C26H30O8;EN:Limonin  
F:mcf_exa_soc;C:4;cMW:536.8722;cFM:C40H56;EN:beta-Carotene  
F:mcf_exa_soc;C:5;cMW:346.3742;cFM:C19H22O6;EN:Gibberellin A3  
.....  
.....
```

```
(sw_auxfix=1)  
F;C;cMW;cFM;EN  
mcf_man_soc;1;349.40462;C16H19N3O4S;Ampicillin  
mcf_man_soc;2;386.6532;C27H46O;Cholesterol  
mcf_exa_soc;3;470.5113;C26H30O8;Limonin  
mcf_exa_soc;4;536.8722;C40H56;beta-Carotene  
mcf_exa_soc;5;346.3742;C19H22O6;Gibberellin A3  
.....  
.....
```

(Tag)

```
F : filename  
C : char number  
NO : serial number  
EN : english name  
JN : japanese name  
FM : formula from literature data  
MW : molecular weight from literature data  
USE : the use  
cMW : molecular weight calculated  
cMI : monoisotopic mass calculated  
cFM : molecular formula calculated
```


7.3 Report output

(Insert option parameter setting)

```
sw_report:=1;  
** default : sw_report=0
```

(Command line)

```
>mpost -s ahandle=0 -s ahandle=2 FILENAME (molecular definition file)
```

(Output)

```
%-----  
% Molecular name = Caffeine  
% Warnings = 0 / Expanded command = 80  
% Width * Height = 54.31772 * 50.43338  
% Shift width * height = -12.59462 * -17.49146  
% Bond length = 12.75589 Atom size = 5.38914  
% Atom count= 14 Bond count= 15 Ring count= 2 Hide H count= 10  
%-----  
%< NO. >( x axis , y axis )< atom >< bond >< hide_H >  
% A1 ( 0 , 0 ) C 4  
% A2 ( 0.866 , -0.5 ) N 3  
% A3 ( 1.732 , 0 ) C 4  
% A4 ( 1.732 , 1 ) C 4  
% A5 ( 0.866 , 1.5 ) C 4  
% A6 ( 0 , 1 ) N 3  
% A7 ( 2.683 , -0.309 ) N 3  
% A8 ( 3.271 , 0.5 ) C 3 1  
% A9 ( 2.683 , 1.309 ) N 3  
% A10 ( 0.866 , -1.371 ) C 1 3  
% A11 ( -0.776 , 1.448 ) C 1 3  
% A12 ( -0.776 , -0.448 ) O 2  
% A13 ( 0.866 , 2.371 ) O 2  
% A14 ( 2.955 , 2.147 ) C 1 3  
%-----  
%< NO. >< bond (sdt)><angle + ( +- )><length ( pt )>  
% B1 1 -> 2 ( 1 ) 330 ( -30 ) 1 ( 12.76 )  
% B2 2 -> 3 ( 1 ) 30 ( 30 ) 1 ( 12.76 )  
% B3 3 -> 4 ( 2 ) 90 ( 90 ) 1 ( 12.76 )  
% B4 4 -> 5 ( 1 ) 150 ( 150 ) 1 ( 12.76 )  
% B5 5 -> 6 ( 1 ) 210 ( -150 ) 1 ( 12.76 )  
% B6 6 -> 1 ( 1 ) 270 ( -90 ) 1 ( 12.76 )  
% B7 3 -> 7 ( 1 ) 342 ( -18 ) 1 ( 12.76 )  
% B8 7 -> 8 ( 2 ) 54 ( 54 ) 1 ( 12.76 )  
% B9 8 -> 9 ( 1 ) 126 ( 126 ) 1 ( 12.76 )  
% B10 9 -> 4 ( 1 ) 198 ( -162 ) 0.66 ( 8.42 )  
% B11 2 -> 10 ( 1 ) 270 ( -90 ) 0.66 ( 8.42 )  
% B12 6 -> 11 ( 1 ) 150 ( 150 ) 0.66 ( 8.42 )  
% B13 1 -> 12 ( 2 ) 210 ( -150 ) 0.66 ( 8.42 )  
% B14 5 -> 13 ( 2 ) 90 ( 90 ) 0.66 ( 8.42 )  
% B15 9 -> 14 ( 1 ) 72 ( 72 ) 0.66 ( 8.42 )  
%-----  
% C ( 12.0107 ) * 8 = 96.08557  
% H ( 1.00793 ) * 10 = 10.07935  
% N ( 14.0067 ) * 4 = 56.0268  
% O ( 15.9994 ) * 2 = 31.99881  
% Monoisotopic mass: 194.08038  
% Weight Calc: 194.1905 / Input: 194.194 / weight gap= -0.00348  
% Formula Calc: C8H10N4O2 / Input:  
%=====
```

7.4 Molfile output

(Insert option parameter setting)

```
sw_MOLout:=1;  
** default : sw_MOLout=0
```

(Command line)

```
>mpost -s ahandle=3  FILENAME (molecular definition file)
```

(Output)

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%  
-MCFtoMOL- EN:Caffeine
```

```
14 15  0  0  0  0  0  0  0  0  0999 V2000  
      0      0      0 C  0  0  0  0  
  0.86603    -0.5      0 N  0  0  0  0  
  1.73206      0      0 C  0  0  0  0  
  1.73206      1      0 C  0  0  0  0  
  0.86603     1.5      0 C  0  0  0  0  
      0      1      0 N  0  0  0  0  
  2.6831   -0.30902      0 N  0  0  0  0  
  3.27089      0.5      0 C  0  0  0  0  
  2.6831    1.30902      0 N  0  0  0  0  
  0.86603   -1.36383      0 C  0  0  0  0  
 -0.76894    1.44394      0 C  0  0  0  0  
 -0.76894   -0.44394      0 O  0  0  0  0  
  0.86603    2.36383      0 O  0  0  0  0  
  2.95299    2.1396      0 C  0  0  0  0  
  1  2  1  0      0  0  
  2  3  1  0      0  0  
  3  4  2  0      0  0  
  4  5  1  0      0  0  
  5  6  1  0      0  0  
  6  1  1  0      0  0  
  3  7  1  0      0  0  
  7  8  2  0      0  0  
  8  9  1  0      0  0  
  9  4  1  0      0  0  
  2 10  1  0      0  0  
  6 11  1  0      0  0  
  1 12  2  0      0  0  
  5 13  2  0      0  0  
  9 14  1  0      0  0
```

```
M  END
```

```
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
```

7.5 LuaTeX file example


```
%-----
\documentclass{article}
\usepackage{luamplib}%
\mplibcodeinherit{enable}%
\mplibverbatim{enable}%
\everymplib{if unknown Ph1:
    input mcf2graph.mf;
    mp_log_name:="temp-info.aux";
    sw_auxout:=1;
fi}%
%-----
\begin{document}
\noindent%
%-----
\begin{mplibcode}
font_wd:=50mm; font_ht:=50mm;
beginfont("N0:2","EN:Limonin","MW:470.51")
Mcf(<30,
    ?6,$(-3,-4)?6,
    -5=?3,-2=wf,-1=wb,6=?5,-4=?6,-5=wf,
    @(13,15,17,20)0,@(3,12,21)//0,
    @(4~wf^60,8~zf^60,18^35,18^-35)/_,
    @(1^60,5^180,16^60)*H,
    14\*,|,?5,$(1,4)d1,3:0
)
endfont
\end{mplibcode}\\
%-----
\begin{mplibcode}
font_wd:=80mm; font_ht:=50mm;
beginfont("N0:3","EN:beta-carotene","MW:536.87")
Mcf(<30,
    ?6,3=d1,@(3,5^35,5^-35)/_,
    4\,|,!18,$(1,3,5,7,9,11,13,15,17)dr,
    @(3,7,12,16)/_,
    |,?6,6=d1,@(6,2^35,2^-35)/_
)
endfont
\end{mplibcode}\\
%-----
\begin{mplibcode}
font_wd:=50mm; font_ht:=50mm;
beginfont("N0:4","EN:Gibberellin A3","MW:346.37");
Mcf(<18,?5,3=?7,5=?6[12],
    8*,160'1.3,&3,13=d1,6=wf,8=wb,
    5*,40~zf'1,0,60,//0^180,&14~zb,
    2:/COOH,7://_,13:*/OH,8:/*OH,
    14:*/_,@(1^60,4^60)*H
)
endfont;
\end{mplibcode}\\
%-----
\end{document}
%-----
```

7.6 LaTeX file example

```
%-----
\documentclass[a4paper]{article}
\usepackage{graphicx}
\pagestyle{empty}
\makeatletter%
%-----
\def\@F{F}\def\@C{C}\def\@EN{EN}\def\@NO{NO}\def\@MW{MW}\def\@FMc{FMc}%
\def\@fst@param#1:#2;{#1}\def\@sec@param#1:#2;{#2}%
\def\mol@sel#1{%
\if#1\empty\relax\else%
\edef\@tag{\expandafter\@fst@param#1;}%
\edef\@var{\expandafter\@sec@param#1;}%
\ifx\@tag\@F\edef\MOLfile{\@var}\fi%
\ifx\@tag\@C\edef\MOLchar{\@var}\fi%
\ifx\@tag\@EN\edef\MOLnameE{\@var}\fi%
\ifx\@tag\@NO\edef\MOLnum{\@var}\fi%
\ifx\@tag\@MW\edef\CALmw{\@var}\fi%
\ifx\@tag\@FMc\edef\CALfm{\@var}\fi%
\fi}%
\def\put@char{%
\begin{picture}(84,42)%
\put(0,38){\bf [MOLnum]\MOLnameE{ }\small\tt/FM:\CALfm/MW:\CALmw}%
\put(10,0){\font\@strufont=\MOLfile\relax%
\hbox{\@strufont\char\MOLchar}}%
\end{picture}%
\def\INFO#1{\@for\@temp:=#1\do{\mol@sel\@temp}\put@char}%
\makeatother
%-----
\begin{document}
\unitlength=1mm%
\INFO{F:mcf_man_soc,C:115,NO:1,cMW:349.40462,cFM:C16H19N3O4S,EN:Ampicillin}%
\INFO{F:mcf_man_soc,C:116,NO:2,cMW:386.6532,cFM:C27H46O,EN:Cholesterol}%
\end{document}
%-----
```

[1]Ampicillin

FM:C16H19N3O4S MW:349.40462



[2]Cholesterol

FM:C27H46O MW:386.6532

