

Building T_EX Live (2018)

2018 release
February 2018

Peter Breitenlohner
Karl Berry
<http://tug.org/texlive>

This file documents the T_EX Live build system and more.

Copyright © 2016–2018 Karl Berry.

Copyright © 2013–2015 Karl Berry & Peter Breitenlohner.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions, except that this permission notice may be stated in a translation approved by the T_EX Users Group.

Short Contents

1	Introduction	1
2	Overview of build system	2
3	Prerequisites	3
4	Building	4
5	Installing	7
6	Layout and infrastructure	10
7	Configure options	20
8	Cross compilation	27
9	Coding conventions	29
10	Continuous integration	31
A	install-tl	33
B	tlmgr	38
	Index	64

Table of Contents

1	Introduction	1
2	Overview of build system	2
3	Prerequisites	3
4	Building	4
4.1	Build iteration	4
4.2	Build problems	4
4.3	Build in parallel	4
4.4	Build distribution	4
4.5	Build one package	5
5	Installing	7
5.1	Installation directories	7
5.2	Linked scripts	7
5.3	Distro builds	8
6	Layout and infrastructure	10
6.1	Build system tools	10
6.2	Top-level directories	10
6.3	Autoconf macros	11
6.3.1	General setup macros	11
6.3.2	Macros for programs	12
6.3.3	Macros for compilers	12
6.3.4	Macros for libraries	12
6.3.5	Macros for library and header flags	13
6.3.6	Macros for Windows	13
6.4	Library modules	14
6.4.1	The <code>png</code> library in <code>libs/libpng</code>	14
6.4.2	The <code>zlib</code> library in <code>libs/zlib</code>	15
6.4.3	The <code>freetype</code> library in <code>libs/freetype2</code>	15
6.4.4	The <code>kpathsea</code> library in <code>texk/kpathsea</code>	15
6.5	Program modules	16
6.5.1	The <code>t1utils</code> package in <code>utils/t1utils</code>	16
6.5.2	The <code>xindy</code> package in <code>utils/xindy</code>	16
6.5.3	The <code>xdvik</code> package in <code>texk/xdvik</code>	16
6.5.4	The subdirectory <code>utils/asymptote</code>	16
6.6	Extending <code>T_EX Live</code>	17
6.6.1	Adding a new program module	17
6.6.2	Adding a new generic library module	18
6.6.3	Adding a new <code>T_EX</code> -specific library module	19

7	Configure options	20
7.1	Global configure options	20
7.1.1	--disable-native-texlive-build	20
7.1.2	--prefix, --bindir	20
7.1.3	--disable-largefile	20
7.1.4	--disable-missing	21
7.1.5	--enable-compiler-warnings= <i>level</i>	21
7.1.6	--enable-cxx-runtime-hack	21
7.1.7	--enable-maintainer-mode	21
7.1.8	--enable-multiplatform	21
7.1.9	--enable-shared	21
7.1.10	--enable-silent-rules	21
7.1.11	--without-ln-s	21
7.1.12	--without-x	22
7.2	Program-specific configure options	22
7.2.1	--enable-prog, --disable-prog	22
7.2.2	--disable-all-pkgs	22
7.2.3	Configure options for <code>texk/web2c</code>	22
7.2.4	Configure options for <code>texk/bibtex-x</code>	23
7.2.5	Configure options for <code>texk/dvipdfm-x</code>	23
7.2.6	Configure options for <code>texk/dvisvgm</code>	23
7.2.7	Configure options for <code>texk/texlive</code>	24
7.2.8	Configure options for <code>texk/xdvik</code>	24
7.2.9	Configure options for <code>utils/xindy</code>	24
7.3	Library-specific configure options	24
7.3.1	Configure options for <code>kpathsea</code>	25
7.3.2	Configure options for system <code>poppler</code>	25
7.4	Variables for configure	25
8	Cross compilation	27
8.1	Cross configuring	27
8.2	Cross problems	28
9	Coding conventions	29
9.1	Declarations and definitions	29
9.2	Const	30
10	Continuous integration	31
Appendix A	install-tl	33
A.1	NAME	33
A.2	SYNOPSIS	33
A.3	DESCRIPTION	33
A.4	REFERENCES	33
A.5	OPTIONS	33
A.6	ENVIRONMENT VARIABLES	37
A.7	AUTHORS AND COPYRIGHT	37

Appendix B	tlmgr	38
B.1	NAME	38
B.2	SYNOPSIS	38
B.3	DESCRIPTION	38
B.4	EXAMPLES	38
B.5	OPTIONS	39
B.6	ACTIONS	40
B.6.1	help	40
B.6.2	version	40
B.6.3	backup [-clean[= <i>N</i>]] [-backupdir <i>dir</i>] [-all <i>pkg</i>]	41
B.6.4	candidates <i>pkg</i>	41
B.6.5	check [<i>option</i>]... [files depends executes runfiles all]	41
B.6.6	conf [texmf tlmgr updmap [-conffile <i>file</i>] [-delete] [<i>key</i> [<i>value</i>]]]	42
B.6.7	dump-tlpdb [-local remote]	42
B.6.8	generate [<i>option</i>]... <i>what</i>	43
B.6.9	gui	44
B.6.10	info [<i>option</i>]... [collections schemes <i>pkg</i>]	44
B.6.11	init-usertree	45
B.6.12	install [<i>option</i>]... <i>pkg</i>	45
B.6.13	option	46
B.6.14	paper	47
B.6.15	path [-w32mode=user admin] [add remove]	48
B.6.16	pinning	48
B.6.17	platform list add remove <i>platform</i>	48
B.6.18	platform set <i>platform</i>	48
B.6.19	platform set auto	49
B.6.20	postaction [-w32mode=user admin] [-fileassocmode=1 2] [-all] [install remove] [shortcut fileassoc script] [<i>pkg</i>]	49
B.6.21	print-platform	49
B.6.22	restore [-backupdir <i>dir</i>] [-all <i>pkg</i> [<i>rev</i>]]	49
B.6.23	remove [<i>option</i>]... <i>pkg</i>	50
B.6.24	repository	50
B.6.25	search [<i>option</i>]... <i>what</i>	51
B.6.25.1	search [<i>option</i>]... -file <i>what</i>	51
B.6.25.2	search [<i>option</i>]... -taxonomy <i>what</i>	51
B.6.25.3	search [<i>option</i>]... -keyword <i>what</i>	51
B.6.25.4	search [<i>option</i>]... -functionality <i>what</i>	51
B.6.25.5	search [<i>option</i>]... -characterization <i>what</i>	51
B.6.25.6	search [<i>option</i>]... -all <i>what</i>	51
B.6.26	uninstall	52
B.6.27	update [<i>option</i>]... [<i>pkg</i>]	52
B.7	USER MODE	55
B.7.1	user mode install	55
B.7.2	user mode backup; restore; remove; update	56
B.7.3	user mode generate; option; paper	56
B.8	CONFIGURATION FILE FOR TLMGR	56
B.9	TAXONOMIES	56

B.10	MULTIPLE REPOSITORIES.....	57
B.10.1	Pinning.....	57
B.11	GUI FOR TLMGR	58
B.11.1	Main display.....	59
B.11.1.1	Display configuration area.....	59
B.11.1.2	Package list area.....	59
B.11.1.3	Main display action buttons.....	60
B.11.2	Menu bar.....	60
B.12	MACHINE-READABLE OUTPUT.....	61
B.12.1	Machine-readable <code>update</code> and <code>install</code> output.....	61
B.12.2	Machine-readable <code>option</code> output.....	63
B.13	AUTHORS AND COPYRIGHT	63
Index.....		64

1 Introduction

This manual (dated February 2018) corresponds to the T_EX Live 2018 release.

This manual is aimed at system installers and programmers, and focuses on how to configure, build, and develop the T_EX Live (TL) sources. It is also available as plain text files in the source tree: `source/README.*`.

The `source/README` file in the TL source tree provides the maximally-terse information for doing a build, and portability information for different systems, along with `source/doc/README.solaris`.

For information on acquiring the TL sources, see <http://tug.org/texlive/svn>.

This manual does not duplicate the information found in other TL documentation resources, such as:

- The T_EX Live web pages: <http://tug.org/texlive>.
- The web page describing how to build the binaries which are distributed with T_EX Live: <http://tug.org/texlive/build.html>.
- The T_EX Live user manual: <http://tug.org/texlive/doc.html>, or run `texdoc texlive`.
- Other T_EX-related Texinfo manuals (see *Web2c*, *Kpathsea*, etc.): <http://tug.org/texinfohtml/>, or check the ‘T_EX’ category in the GNU Info system.
- Package documentation: <http://tug.org/texlive/Contents/live/doc.html>, or the `doc.html` file at the top level of the installed TL.

As an exception, the full documentation for `install-tl` and `tlmgr` is included here, just because it is convenient to do so. The same text is available online (linked from <http://tug.org/texlive/doc.html>, or by invoking the program with ‘`--help`’ (or look at the end of the source).

2 Overview of build system

The T_EX Live build system was redesigned in 2009, consistently using Autoconf, Automake, and Libtool. Thus

`configure && make && make check && make install`

or the basically-equivalent top-level `Build` script suffice to build and install the TL programs. The `make check` clause performs various tests of the generated programs—not strictly required but strongly recommended. Running `configure --help` will display a comprehensive list of all `configure` options.

The main components of the TL build system are:

`libs/lib` Generic libraries.

`texk/lib` T_EX-specific libraries in subdirectories, notably `lib=kpathsea`. (The other one is `texk/ptexenc`.)

`texk/prog` T_EX-specific programs (that use Kpathsea).

`utils/prog` Other programs (that don't use Kpathsea).

The primary design goal of the build system is modularity. Each program and library module (or package) specifies its own requirements and properties, such as required libraries, whether an installed (system) version of a library can be used, `configure` options to be seen at the top level, and more. An explicit list of all available modules is kept in only one central place, namely `m4/kpse-pkgs.m4`.

A second, related goal is to configure and build each library before configuring any other (program or library) module which uses that library. This allows checking for properties and features of a library built as part of the TL tree in much the same way as for a system version of that library.

All generic libraries and several programs are maintained independently. The corresponding modules use (most of) the distributed source tree and document any modifications of that source.

All this is for the sake of simplifying both upgrading of modules and integrating new modules into the TL build system. (Not to say that either task is trivial.)

3 Prerequisites

Overall, building the T_EX Live programs, when using all libraries from the TL source tree, requires only C and C++ compilers and GNU `make`. (If `make` from your `PATH` is not GNU `make`, you can set `MAKE` in the environment to whatever is necessary.)

GNU `make` is required only because of some third-party libraries, notably FreeType; all the TL-maintained directories (and Automake/Autoconf output in general) should work with any reasonable `make`.

However, a few programs in the tree have additional requirements:

<code>dvisvgm</code>	requires a C++11 compiler, such as gcc 4.8.1 (or later) or clang 3.3 (or later).
<code>web2c</code>	requires <code>perl</code> for some tests run by <code>make check</code> .
<code>xdvik</code>	
<code>xpdfopen</code>	require X11 headers and libraries, often in “development” packages that are not installed by default.
<code>xetex</code>	requires <code>fontconfig</code> (again both headers and library), or, for MacOSX only, the <code>ApplicationServices</code> and <code>Cocoa</code> frameworks.
<code>xindy</code>	requires GNU <code>clisp</code> and in addition <code>perl</code> , <code>latex</code> , and <code>pdflatex</code> to build the rules and/or documentation.

Lacking the required tools, building these programs must avoided, e.g.,
`configure --without-x --disable-xetex --disable-xindy`

Modifying source files induces more requirements, as one might expect:

- Modification of any `.y` or `.l` source files requires `bison` or `flex` to update the corresponding C sources.
- Modification of the sources for `.info` files requires `makeinfo`.
- Modification of any part of the build system (M4 macros, `configure.ac`, `Makefile.am`, or their fragments) requires GNU M4, GNU Autoconf, GNU Automake, and GNU Libtool to update the generated files. See Section 6.1 [Build system tools], page 10.

If you haven’t modified any source files, and infrastructure tools such as `autoconf` or `makeinfo` are still being run, check your timestamps—notably, `use-commit-times` must be set to `yes` in your Subversion configuration (see Section 6.1 [Build system tools], page 10). Barring buggy commits, no infrastructure tools are needed to do a normal build.

As an example, on Debian systems the necessary build dependencies can be installed via:

```
apt-get install libfontconfig-dev libx11-dev libxmu-dev libxaw7-dev
```

4 Building

The top-level `Build` script is intended to simplify building the binaries distributed with T_EX Live itself—we call this the “native” TL build. It configures and makes everything in a subdirectory of the main build tree (default `Work/`), installs everything in another subdirectory (default `inst/`), and finally runs `make check`. The exact directory and command names can be specified via environment variables and a few leading options. All remaining arguments (assignments or options) are passed to the `configure` script. Please take a look at the `./Build` source file itself for more information; it is a straightforward shell script.

An alternative, and the one we will mainly discuss here, is to run `configure` and `make` oneself in a suitable empty subdirectory. Building in the source directory itself is not supported (sorry).

4.1 Build iteration

Running the top-level `configure` script configures the top level and the subdirectories `libs`, `utils`, and `texk`. Running `make` at the top-level first iterates over all T_EX-specific libraries, and then runs `make` in `libs`, `utils`, and `texk` to iterate over all generic libraries, utility programs, and T_EX-specific programs. These iterations consist of two steps:

1. For each library or program module not yet configured, run `configure`, adding the configure option `--disable-build` if the module need not be built, otherwise running `make all`.
2. For each library or program module that must be built, run `make` for the selected target(s): `default` or `all` to (re-)build, `check` to run tests, `install`, etc.

Running the top-level `make` a second time iterates again over all the library and program modules, but finds (should find) nothing to be done unless some source files have been modified.

4.2 Build problems

If configuring or building a module fails, you should first find and fix the problem, then perhaps remove the subdirectory for that module from the build tree, and finally rerun the top level `make` (or `Build` with `--no-clean` as its first argument).

4.3 Build in parallel

The TL build system carefully formulates dependencies as well as `make` rules when a tool (such as `tangle`, `ctangle`, or `convert`) creates several output files. This allows for parallel builds (`make -j n` with $n > 1$ or even `make -j`) that can considerably speed up the TL build.

Incidentally, a noticeable speed-up can also be (independently) gained by using a configure cache file, i.e., with the option `-C` (recommended).

4.4 Build distribution

Running `make dist` at the top level creates a tarball `tex-live-yyyy-mm-dd.tar.xz` from the TL source tree. Running `make distcheck` also verifies that this tarball suffices to build and install all of TL.

This is useful for checking consistency of the source tree and Makefiles, but the result is not a complete or even usable \TeX system, since all the support files are lacking; see Chapter 5 [Installing], page 7.

4.5 Build one package

To build one package, the basic idea is to use the `configure` option `--disable-all-pkgs` (see Section 7.2.2 [`--disable-all-pkgs`], page 22). Then all program and library modules are configured but none are made. However, the `Makefiles` still contain all build rules and dependencies and can be invoked to build an individual program or library and causes to first build any required libraries.

This “build-on-demand” procedure is used, e.g., in the upstream Lua \TeX repository to build Lua \TeX , essentially from a subset of the complete \TeX Live tree. Similarly, when, e.g., building the original e- \TeX has been disabled (as it is by default), one can run `make etex` (or `make etex.exe`) in `texk/web2c/` to build e- \TeX (although there is no comparably simple way to install e- \TeX).

If you want to work on a single program within the TL sources, this is the recommended way to do it. Here is an example from start to finish for working on `dvipdfm-x`.

```
mkdir mydir && cd mydir # new working directory

# Get sources (http://tug.org/texlive/svn)
rsync -a --delete --exclude=.svn --exclude=Work \
    tug.org::tldevsrc/Build/source/ .

# Create build directory:
mkdir Work && cd Work

# Do the configure:
../configure --disable-all-pkgs --enable-dvipdfm-x \
    -C CFLAGS=-g CXXFLAGS=-g >&outc

# Do the make:
make >&outm

# Test:
cd texk/dvipdfm-x
make check
```

Then you modify source files in `mydir/texk/dvipdfm-x` and rerun `make` in `mydir/Work/texk/dvipdfm-x` to rebuild.

The second line of the `configure` invocation shows examples of extra things you likely want to specify if you intend to hack the sources (and not just build binaries): the `-C` speeds up `configure`, and the `CFLAGS` and `CXXFLAGS` settings eliminate compiler optimization for debugging purposes.

Of course, one should actually look at the output and check that things are working. There are many `configure` options you can tweak as desired; check the output from `configure --help`.

Finally, the above retrieves the entire TL source tree (several hundred megabytes). It is natural to ask if this is really necessary. Strictly speaking, the answer is no, but it is vastly more convenient to do so. If you cut down the source tree, you must also give additional **configure** flags to individually disable using system versions of libraries, or the intricacies of the dependencies (such as **teckit** requiring **zlib**) will have undesired side effects. For an example, see the **build-pdftex.sh** script in the **pdftex** development source (<http://pdftex.org>), which is indeed a cut-down TL source tree.

Even with **--disable-all-pkgs**, dependencies will be checked. For instance, if a non-MacOSX system does not have **fontconfig**, XeTeX cannot be built (see Chapter 3 [Pre-requisites], page 3) and **configure** will terminate. To proceed without such dependencies, specify **--enable-missing** also. (Arguably this should happen automatically.)

By default, the **gcc** compilers will be used if present; otherwise, individual packages may use something different. You can explicitly specify the compilers to be used with the environment variables **CC**, **CXX**, and **OBJCXX**.

5 Installing

This section discusses the results of `make install` in the source tree.

The main consideration is that `make install` is not enough to make a usable \TeX installation. Beyond the compiled binaries, (thousands of) support files are needed; just as a first example `plain.tex` is not in the source tree.

These support files are maintained completely independently and are not present in the source tree. The best basis for dealing with them is the \TeX Live (plain text) database in `Master/tlpkg/texlive.tlpdb`, and/or the \TeX Live installer, `install-tl`. More information is under `Master/tlpkg` and at <http://tug.org/texlive/distro.html>.

5.1 Installation directories

Running `make install` (or `make install-strip`) installs executables in *bindir*, libraries in *libdir*, headers in *includedir*, general data (including “linked scripts”, see Section 5.2 [Linked scripts], page 7) in *datarootdir*/*texmf-dist*, man pages in *mandir*, and Info files in *infodir*.

The values of these directories are determined by `configure` and can be specified explicitly as options such as `--prefix=prefix` or `--bindir=bindir`; otherwise, they are given by their usual Autoconf defaults:

<i>prefix</i>	<code>/usr/local</code>
<i>exec_prefix</i>	<i>prefix</i>
<i>bindir</i>	<i>exec_prefix</i> /bin
<i>libdir</i>	<i>exec_prefix</i> /lib
<i>includedir</i>	<i>prefix</i> /include
<i>datarootdir</i>	<i>prefix</i> /share
<i>mandir</i>	<i>datarootdir</i> /man
<i>infodir</i>	<i>datarootdir</i> /info

except possibly modified as follows:

- If the option `--enable-multiplatform` is given, */platform* (i.e., the canonical platform name) is appended to *bindir* and *libdir*. This is implied for a native TL build.
- In a native TL build, *datarootdir* is set to *prefix*, *infodir* is set to *prefix*/*texmf-dist*/doc/info, and *mandir* to *prefix*/*texmf-dist*/doc/man, corresponding to the directories used in the TL distribution.

The top-level `configure` script displays all these installation paths.

For the native TL build, the `Build` script leaves the binaries in `./inst/bin/std-platform-name`. The new binaries are not directly usable from that location; they need to be copied to `Master/bin/tl-platform`. The other files and directories that end up in `./inst/` are ignored.

5.2 Linked scripts

Quite a few executables are architecture-independent shell, Perl, or other interpreted scripts, rather than compiled binaries. A few are maintained as part of the TL source tree, but most are maintained elsewhere with copies under `texk/texlive/linked_scripts`.

These so-called *linked scripts* are installed under `datarootdir/texmf-dist/scripts`; for Unix-like systems a symbolic link is made in `bindir`. For example, a symlink points from `bindir/ps2eps` to `datarootdir/texmf-dist/scripts/ps2eps/ps2eps.pl`. For Windows, a standard wrapper binary (e.g., `bindir/ps2eps.exe`) serves the same purpose. (The source for the wrapper is in `texk/texlive/w32_wrapper`.)

One reason for this is to avoid having many copies of the same script; a more important reason is that it guarantees the scripts will stay in sync across the different supported operating systems.

Most important of all, we want the `bindir` resulting from the build to be as close as possible to what is in the TL distribution. At present, there are a few exceptions—Asymptote, Biber, Xindy—and each one creates considerable extra work. We don’t want to add more. (See <http://tug.org/texlive/build.html> for information about building those exceptions, as well as the `xz` and `wget` programs that are used in the TL infrastructure.)

5.3 Distro builds

Although they use the same code base, building for the native TL distribution as shipped by the T_EX user groups is typically quite different from a “distro” build needed by, e.g., a full GNU/Linux or BSD operating system distribution.

The native TL distribution uses shared libraries only when absolutely necessary (`libc`, `libm`, X11 libraries, and `libfontconfig`). However, a distro typically wants to use as many shared libraries as possible from elsewhere on the system, including T_EX-specific libraries such as `libkpathsea` (even though Kpathsea has never officially been released as a shared library, but we digress). In addition, the installation paths will, in general, be completely different.

Here are the `configure` options that distro builds are likely to find most relevant:

`--disable-native-texlive-build`

This must be specified to avoid interference from the many tweaks we do for the native TL build.

`--with-banner-add=/SomeDistro`

This isn’t technically required, but is strongly recommended, so your build and your distro can be distinguished from others.

`--enable-shared`

Build shared versions of the T_EX-specific libraries (uses `libtool`).

`--disable-static`

Do not build the static versions of the T_EX-specific libraries.

`--with-system-lib`

Use system versions for as many libraries *lib* as possible. `configure --help` will give you the list of possibilities.

`--with-lib-includes=dir`

`--with-lib-libdir=dir`

If needed, allows you to specify where the headers/code are for the given library *lib*.

`--prefix=/usr`

`--prefix=/opt/TeXLive`

Or whatever your convention is. The default is `/usr/local` and you shouldn't install there for a distro.

`--libdir=\${exec_prefix}/lib64`

May be needed for 64-bit bi-architecture (GNU/Linux) systems.

You will need to take care of the support files mentioned above (see Chapter 5 [Installing], page 7), and many other issues, such as font maps, languages, and formats, independently of the build. Norbert Preining has written a detailed article on adapting TL for distros: <http://tug.org/TUGboat/tb34-3/tb108preining-distro.pdf>. (If the article needs updating in the future, perhaps we will merge it into this document.)

6 Layout and infrastructure

The T_EX Live source tree is the subtree rooted at `Build/source` of the complete TL distribution and contains the sources for all executables distributed by TL, as well as `configure` scripts and `make` rules to build and install them together with some of their support files.

6.1 Build system tools

As mentioned above (see Chapter 3 [Prerequisites], page 3), a normal build requires very little. On the other hand, if you want to modify the T_EX Live infrastructure sources, such as `configure.ac` or `Makefile.am` files, you will need to have several additional tools installed.

In general, the TL build system uses the latest released versions of the GNU build tools, installed directly from the original GNU releases (e.g., by building them with `configure --prefix=/usr/local/gnu` and having `PATH` start with `/usr/local/gnu/bin`). We have found that trying to use the versions of these tools packaged for distros causes many extra hassles, so don't do that, tempting as it may be.

Currently the versions we use are:

```
autoconf (GNU Autoconf) 2.69
automake (GNU automake) 1.15.1
bison (GNU Bison) 3.0.4
flex 2.6.0
ltmain.sh (GNU libtool) 2.4.6
m4 (GNU M4) 1.4.18
makeinfo (GNU texinfo) 6.5
```

These versions should be used to update the generated files (e.g., `configure` or `Makefile.in`) in all or parts of the TL tree after their dependencies have been changed. This can be done explicitly with the top-level `reautoconf` script or implicitly by using the `configure` option `--enable-maintainer-mode`.

The files in the Subversion repository (see <http://tug.org/texlive/svn>) are all up to date, but unfortunately this may not be reflected by their timestamps. (For starters, be sure to set `use-commit-times=yes` in `~/subversion/config` or the equivalent.)

To avoid unnecessary runs of `bison`, `flex`, or `makeinfo` it may be necessary to `touch` the generated (`.c`, `.h`, or `.info`) files. With `--enable-maintainer-mode` it may also be necessary to `touch` first `aclocal.m4`, then `configure` and `config.h.in` (or `c-auto.in`), and finally all `Makefile.in` files. Perhaps `make -t` will help.

6.2 Top-level directories

Here is a brief description of the top-level directories in the T_EX Live source tree.

As mentioned at the beginning of see Chapter 2 [Overview of build system], page 2, the main source directories are `texk/` (T_EX-specific programs and libraries), `utils/` (additional programs), and `libs/` (generic libraries).

In addition, the top-level directories `am/` and `m4/` contain `Makefile.am` fragments and Autoconf macros, respectively, used in many places. Specifically, the file `m4/kpse-pkgs.m4` contains lists of all program and library modules; missing modules are silently ignored. (This helps in creating cut-down source trees.)

Each module contributes fragments (in separate files) defining its capabilities and requirements to the `configure.ac` scripts at the top-level and in the subdirectories `libs`, `utils`, and `texk`. The fragments from program modules supply `configure` options to disable or enable building them; those from library modules specify if an installed (system) version of that library can be used. This ultimately determines which modules need to be built—although all modules must be configured for the benefit of `make` targets such as `dist` or `distcheck`.

The top-level `build-aux/` directory contains the common files `compile`, `config.guess`, `config.sub`, `depcomp`, etc. used by most packages. These are from the GNU Gnulib sources (<http://www.gnu.org/software/gnulib>), which in turn synchronizes with the appropriate ultimate upstream repository. There are, however, independent copies in, e.g., `libs/freetype2/freetype-*/builds/unix/`, and a few other places. The `reautoconf` script does not touch those, but a TL cron job keeps them in sync (nightly).

The directory `extra/` contains things which are not part of the TL build, but are present just for (someone's) convenience, e.g., is `epstopdf` development source is here.

When the top-level `./Build` script is used to build TL, two more two more top-level directories appear: `Work/` for the build tree, and `inst/` for the install tree (from `make install`). These names (and everything else about `Build`'s operation) can be changed by setting environment variables before running it; see the script file.

6.3 Autoconf macros

Here we describe some of the Autoconf macros used in several modules—not a complete list, by any means. These general macros are supplemented by module-specific macros in directories such as `texk/dvipng/m4/`; some of those are described in Section 6.4 [Library modules], page 14, and see Section 6.5 [Program modules], page 16.

6.3.1 General setup macros

The TL sources use two general setup macros:

KPSE_BASIC (*name*, [*more-options*]) [Macro]

Initialize the basic TL infrastructure for module *name*:

`AM_INIT_AUTOMAKE([foreign more-options])`

`AM_MAINTAINER_MODE`

`KPSE_COMPILER_WARNINGS`

and make sure the C compiler understands function prototypes. This is used for all generic library and program modules.

KPSE_COMMON (*name*, [*more-options*]) [Macro]

Like `KPSE_BASIC` but add:

`LT_PREREQ([2.2.6])`

`LT_INIT([win32-dll])`

`AC_SYS_LARGEFILE`

`AC_FUNC_FSEEKO`

and check for frequently used functions, headers, types, and structures. This is used for \TeX -specific modules.

6.3.2 Macros for programs

Macros for program checks:

- KPSE_CHECK_LATEX** [Macro]
 Set `LATEX` to the name of the first of `latex`, `elatex`, or `lambda` which exists in `PATH`, or to `no` if none of them exists. Call `AC_SUBST` for `LATEX`. The result of this test can be overridden by setting the `LATEX` environment variable or the cache variable `ac_cv_prog_LATEX`.
- KPSE_CHECK_PDFLATEX** [Macro]
 Check for `pdflatex` in `PATH` and set `PDFLATEX`.
- KPSE_CHECK_PERL** [Macro]
 Check for `perl` or `perl5` in `PATH` and set `PERL`.
- KPSE_PROG_LEX** [Macro]
 Call `AC_PROG_LEX` and add the flag `-l` for `flex`.

6.3.3 Macros for compilers

Macros for compiler-related checks:

- KPSE_COMPILER_WARNINGS** [Macro]
 When using the (Objective) C/C++ compiler, set `WARNING_[OBJ]C[XX]FLAGS` to suitable warning flags (depending on the value given to or implied for `--enable-compiler-warnings`). Call `AC_SUBST` for them. At the moment this only works for GNU compilers, but could be extended to others if necessary.
 This macro caches its results in the `kpse_cv_warning_cflags`, ... variables.
- KPSE_COMPILER_VISIBILITY** [Macro]
 When using the C or C++ compiler, try to set `VISIBILITY_C[XX]FLAGS` to flags to hide external symbols. Call `AC_SUBST` for this variable. At the moment this only tests for the compiler option `-fvisibility=hidden`, but that could be extended with more checks if necessary.
 This macro caches its results in the `kpse_cv_visibility_cflags` or `kpse_cv_visibility_cxxflags` variable.
- KPSE_CXX_HACK** [Macro]
 Provide the configure option `--enable-cxx-runtime-hack`. If enabled and when using `g++`, try to statically link with `libstdc++`, somewhat improving portability of the resulting binary.
 This macro caches its result in the `kpse_cv_cxx_hack` variable.

6.3.4 Macros for libraries

One macro for a library check:

- KPSE_LARGEFILE** (*variable*, [*extra-define*]) [Macro]
 Call `AC_SYS_LARGEFILE` and `AC_FUNC_FSEEKO` and append suitable `-D` flags (optionally including `-Dextra-define`) to *variable*.

6.3.5 Macros for library and header flags

Each library module `libs/lib` or `texk/lib` is supplemented by a macro `KPSE_LIB_FLAGS` (all uppercase) that provides make variables for that library. E.g., for `libs/libpng`:

`KPSE_LIBPNG_FLAGS` [Macro]

Provide the configure option `--with-system-libpng`. Set and `AC_SUBST` make variables for modules using this library (either an installed version or from the T_EX Live tree): `LIBPNG_INCLUDES` for use in `CPPFLAGS`, `LIBPNG_LIBS` for use in `LDADD`, `LIBPNG_DEPEND` for use as dependency, and `LIBPNG_RULE` defining make rules to rebuild the library.

`KPSE_ADD_FLAGS (name)` [Macro]

Temporarily extend `CPPFLAGS` and `LIBS` with the values required for the library module *name*.

`KPSE_RESTORE_FLAGS` [Macro]

Restore `CPPFLAGS` and `LIBS` to their original values.

As an example, the `configure.ac` file for a hypothetical program `utils/foo` using `libpng`, and hence `zlib`, would contain

```
KPSE_ZLIB_FLAGS
KPSE_LIBPNG_FLAGS
```

and its `Makefile.am` would be along these lines:

```
bin_PROGRAMS = foo
AM_CPPFLAGS = ${LIBPNG_INCLUDES} ${ZLIB_INCLUDES}
foo_LDADD = ${LIBPNG_LIBS} ${ZLIB_LIBS}
foo_DEPENDENCIES = ${ZLIB_DEPEND} ${LIBPNG_DEPEND}
## Rebuild libz
@ZLIB_RULE@
## Rebuild libpng
@LIBPNG_RULE@
```

If it was necessary to examine whether certain `zlib` or `libpng` features were available, `configure.ac` should be continued this way:

```
KPSE_ADD_FLAGS([zlib])
... # tests for zlib features, if any
KPSE_ADD_FLAGS([libpng])
... # tests for libpng features
KPSE_RESTORE_FLAGS # restore CPPFLAGS and LIBS
```

6.3.6 Macros for Windows

Windows differs in several aspects from Unix-like systems, many of them due to the lack of symbolic links.

`KPSE_CHECK_WIN32` [Macro]

Check if compiling for a Windows system. The result is `no` for Unix-like systems (including Cygwin), `mingw32` for Windows with GCC, or `native` for Windows with MSVC. The result is cached in the `kpse_cv_have_win32` variable.

KPSE_COND_WIN32 [Macro]
 Call `KPSE_CHECK_WIN32` and define the Automake conditional `WIN32` (`true` if the value of `kpse_cv_have_win32` is not `no`).

KPSE_COND_MINGW32 [Macro]
 Call `KPSE_COND_WIN32` and define the Automake conditional `MINGW32` (`true` if the value of `kpse_cv_have_win32` is `mingw32`).

KPSE_COND_WIN32_WRAP [Macro]
 Call `KPSE_COND_WIN32` and define the Automake conditional `WIN32_WRAP` (`true` if the standard Windows wrapper (`texk/texlive/w32_wrapper/runscript.exe`) exists. This wrapper is used on Windows instead of symlinks for the “linked scripts” (see Section 5.2 [Linked scripts], page 7).

KPSE_WIN32_CALL [Macro]
 Call `KPSE_COND_WIN32`, check if the file `texk/texlive/w32_wrapper/callexe.c` exists; if it does, create a symlink in the build tree. Compiling `callexe.c` with `-DEXEPROG='foo.exe'` and installing `callexe.exe` as `bar.exe` is used on Windows instead of a symlink `bar->foo` for Unix-like systems.

6.4 Library modules

Here we discuss some specifics for a few of the libraries in TL, both for the details themselves, and as a way of illuminating the general structure and variation.

6.4.1 The png library in `libs/libpng`

This generic library uses the source tree in, e.g., the subdirectory `libpng-src/` with all modifications for TL recorded in `TLpatches/*`. The `configure.ac` fragment `ac/withenable.ac` contains

```
KPSE_WITH_LIB([libpng], [zlib])
```

specifying the module name, and indicating the dependency on `zlib`. A third literal argument `tree` would specify that the library from the T_EX Live tree cannot be replaced by a system version. That not being the case here, a second fragment `ac/libpng.ac` contains

```
KPSE_TRY_LIB([libpng],
  [#include <png.h>],
  [png_structp png; png_voidp io; png_rw_ptr fn;
  png_set_read_fn(png, io, fn);])
```

thus providing the simple C code

```
#include <png.h>
int main ()
{ png_structp png; png_voidp io; png_rw_ptr fn;
  png_set_read_fn(png, io, fn);
  return 0; }
```

which Autoconf uses to verify the usability of a system version with C code. The analogous macro `KPSE_TRY_LIBXX` would check using C++ code. These fragments are included by `configure.ac` at the top level.

For this library, among many other modules, a proxy build system for TL is used (`configure.ac`, `Makefile.am`, and `include/Makefile.am`), ignoring the distributed one. Consequently, a few generated files and auxiliary scripts are removed from the distributed source tree. The public headers `png.h`, `pngconf.h`, and `pnglibconf.h` are “installed” (as symlinks) under `include/` in the build tree exactly as they are for a system version under, e.g., `/usr/include/`.

The module is supplemented by the file `m4/kpse-libpng-flags.m4` that defines the M4 macro `KPSE_LIBPNG_FLAGS` used by all modules depending on this library in their `configure.ac` to generate the `make` variables `LIBPNG_INCLUDES` for use in `CPPFLAGS`, `LIBPNG_LIBS` for use in `LDADD`, `LIBPNG_DEPEND` for use as dependencies, and `LIBPNG_RULE` defining `make` rules to rebuild the library.

`m4/kpse-libpng-flags.m4` also supplies the configure option `--with-system-libpng` and uses `pkg-config` to determine the flags required for the system library.

6.4.2 The zlib library in `libs/zlib`

This generic library is very much analogous to `libpng`, but without the dependency on any other library. The file `m4/kpse-zlib-flags.m4` supplies the configure option `--with-system-zlib`, as well as `--with-zlib-includes` and `--with-zlib-libdir` to specify non-standard locations of the `zlib` headers and/or library.

6.4.3 The freetype library in `libs/freetype2`

This module uses a wrapper build system with an almost trivial `configure.ac` and with a `Makefile.am` that invokes `configure` and `make` for the distributed source, followed by `make install` with the build tree as destination. The flags required for the system library are obtained through `freetype-config`.

6.4.4 The kpathsea library in `texk/kpathsea`

This is one of the \TeX -specific libraries that are maintained as part of \TeX Live (see *Kpathsea*). Despite being a core part of the \TeX system, it is not a terribly special case in the infrastructure. The \TeX libraries are Libtool libraries (static and/or shared) and are installed by `make install` together with the programs. They are, however, not part of the TL DVD as distributed by \TeX user groups, and have never been officially released for standalone use.

It is possible, and perhaps even useful for distro builds (see Section 5.3 [Distro builds], page 8), to specify the configure option `--with-system-kpathsea` in order to use a system version of the library. Programs outside the TL tree should use `pkg-config` for the required flags.

In addition to `ac/withenable.ac` and `ac/kpathsea.ac` there is a third fragment `ac/mktex.ac` included by both `ac/withenable.ac` and `configure.ac` that supplies configure options such as `--enable-mktex-tfm-default`, which determine the compile time default of whether or not to run `mktex-tfm` to generate a missing `.tfm` file. In any case, however, the command line options `-mktex=tmf` or `-no-mktex=tmf` for the \TeX -like engines override this default.

6.5 Program modules

As with libraries (see Section 6.4 [Library modules], page 14), here we discuss the details for a few of the programs in TL.

6.5.1 The `t1utils` package in `utils/t1utils`

Once again we use the distributed source tree `t1utils-src` with modifications documented in `TLpatches/*` and a proxy build system consisting of `configure.ac` and `Makefile.am`. The fragment `ac/withenable.ac` contains

```
KPSE_ENABLE_PROG([t1utils])
```

specifying the module name without any dependencies, and supplies the configure option `--disable-t1utils`.

6.5.2 The `xindy` package in `utils/xindy`

This module uses the distributed source tree `xindy-src/` with modifications documented in `TLpatches/*`, a proxy `configure.ac`, and a wrapper `Makefile.am` that descends into `xindy-src`. The `xindy` build requires a `make` that supports a `VPATH` build, can handle all targets, and do not refer to `${top_srcdir}` or `${top_builddir}`. The fragment `ac/withenable.ac` contains

```
KPSE_ENABLE_PROG([xindy], , [disable native])
m4_include(kpse_TL[utils/xindy/ac/xindy.ac])
m4_include(kpse_TL[utils/xindy/ac/clisp.ac])
```

where `disable` in the third argument indicates that `xindy` is only built if explicitly enabled by the user with `configure --enable-xindy` (the need for `clisp` is too painful to require by default), and `native` disallows cross compilation. The additional fragments `ac/xindy.ac` and `ac/clisp.ac` specify more `configure` options to be seen at the top level with `ac/xindy.ac` also included by `configure.ac`.

6.5.3 The `xdvik` package in `texk/xdvik`

This package is maintained as part of the T_EX Live tree with sources in its top level directory and the subdirectory `gui`. The fragment `ac/withenable.ac` contains

```
dn1 extra_dirs = texk/xdvik/squeeze
KPSE_ENABLE_PROG([xdvik], [kpathsea freetype2], [x])
m4_include(kpse_TL[texk/xdvik/ac/xdvik.ac])
```

thus specifying the dependency on the `kpathsea`, `freetype`, and `X11` libraries. The M4 comment (following `dn1`) signals the subsidiary `squeeze/configure.ac`. This is needed because the main executable `xdvi-bin` (to be installed as, e.g., `xdvi-xaw`) is for the `host` system whereas the auxiliary program `squeeze/squeeze` has to run on the `build` system and in a cross compilation they differ.

The additional fragment `ac/xdvik.ac` is also included by `configure.ac` and supplies the configure option `--with-xdvi-x-toolkit` also seen at the top-level.

6.5.4 The subdirectory `utils/asymptote`

This subdirectory contains the sources for `asy` and `xasy` but due to its complexity and prerequisites (e.g., `OpenGL`) it is not part of the TL build system. These programs must

be built and installed independently, but are included on the TL DVD together with their support files.

6.6 Extending T_EX Live

This section outlines the basic process for adding new packages to the TL build system.

In any case, a new package directory `foo` should contain the original sources, as modified for TL, in `foo/foo-src`, and the changes should be documented in `foo/TLpatches/*`; changes should also be submitted upstream whenever reasonable, of course. In addition, `foo/` will need the usual Automake build-related files (`configure.ac`, `Makefile.am`, etc. Please keep a `ChangeLog` for all TL changes.

6.6.1 Adding a new program module

A T_EX-specific program module in a subdirectory `texk/prog` may use the T_EX-specific libraries and is included by adding its name `prog` to the M4 list `kpse_texk_pkgs` defined in `m4/kpse-pkgs.m4`.

A generic program module in a subdirectory `utils/prog` must not use the T_EX-specific libraries and is included by adding its name `prog` to the M4 list `kpse_utils_pkgs` in `m4/kpse-pkgs.m4`.

In either case, the subdirectory `texk/prog` or `utils/prog` must provide a fragment `ac/withenable.ac` that contains the M4 macro `KPSE_ENABLE_PROG` defined in `m4/kpse-setup.m4` with `prog` as the mandatory first argument and three optional arguments:

1. a list of required libraries from the TL tree;
2. a list of options (`disable` if this module is not to be built without the configure option `--enable-prog`, `native` if cross compilation is not possible, `x` if the program requires X11 libraries);
3. a comment added to the help text for the `configure` option `--enable-prog` or `--disable-prog`.

If the module requires specific configure options to be seen at the top level, they should be defined in an additional fragment `ac/prog.ac` included from `ac/withenable.ac` and `configure.ac`.

Usually, the new program is maintained somewhere outside of T_EX Live. In that case, we put the upstream sources into a subdirectory `prog-src` (e.g., `utils/newprog/newprog-src`). We do not run `configure` in this original `...-src` directory, only in our own directory, but we do compile using the source files in `...-src`.

So, these are the files that we must generally create:

`ac/withenable.ac`

The `KPSE_ENABLE_PROG` call just explained.

`configure.ac`

`Makefile.am`

By merging the contents of the original `configure.ac` (if provided) and a comparable program already in TL. There is no magic recipe, it's necessary to think about needs to be done in the original vs. in T_EX Live.

TLpatches/TL-Changes

Actions taken after getting the original source tree; typically removal of derived or unused common files.

TLpatches/patch-...

If any changes are needed to the original sources, record the patches here so they can be applied next time. And send them upstream so that perhaps they won't have to be.

ChangeLog

Record all TL-specific changes, now and in the future.

Then, run GNU **autoreconf** in the new directory (see Section 6.1 [Build system tools], page 10). After that works, **svn add** the necessary files, notably **Makefile.in**, **aclocal.m4**, **configure**, and **svn:ignore** the Automake cache **autom4te.cache**. (This is so people checking out the TL source tree do not have to run any autotools, but can simply run **configure**.)

Then, run the TL tool **reautoconf** in the top-level TL **source/** directory, to incorporate the new program into the build tree.

Then, run (and rerun) a build until the program compiles and tests successfully, probably involving rerunning **autoreconf** in the source directory, **make** in the build directory, etc.

After final success, don't forget to commit.

6.6.2 Adding a new generic library module

A generic library module in a subdirectory **libs/lib** must not depend on **T_EX**-specific libraries, by definition. It is included by adding its name **lib** to the M4 list **kpse_libs_pkgs** in **m4/kpse-pkgs.m4**—before any other libraries from the **T_EX** Live tree on which it depends.

As with program modules, the subdirectory **libs/lib** must contain the sources and build system for the library (and any installable support programs) and a fragment **ac/withenable.ac** that contains the M4 macro **KPSE_WITH_LIB** defined in **m4/kpse-setup.m4** with **lib** as the mandatory first argument and two optional arguments: a list of required libraries from the TL tree, and a list of options (currently there is only one: specify **tree** if this library cannot be replaced by a system version).

If a system version can be used, a second fragment **ac/lib.ac** is needed, containing the M4 macro **KPSE_TRY_LIB** (or **KPSE_TRY_LIBXX**) with **lib** as the mandatory first argument and two additional arguments for the Autoconf macro **AC_LANG_PROGRAM** used to compile and link a small C (or C++) program as sanity check for using the system library.

In addition a file **m4/kpse-lib-flags** (at the top level) must define the M4 macro **KPSE_LIB_FLAGS** (all uppercase) setting up the **make** variables **LIB_INCLUDES**, **LIB_LIBS**, **LIB_DEPEND**, and **LIB_RULE** with the values required for **CPPFLAGS**, **LDADD**, dependencies, and a (multi-line) **make** rule to rebuild the library when necessary. All of that is needed for the library from the TL tree and, if supported, for a system version.

If a system library is allowed, **KPSE_LIB_FLAGS** also provides the configure option **--with-system-lib** and uses the additional M4 macro **KPSE_LIB_SYSTEM_FLAGS** to generate the **make** variables for a system library. Furthermore the definition of the M4 macro **KPSE_ALL_SYSTEM_FLAGS** in **m4/kpse-pkgs.m4** must be extended by the line:

```
AC_REQUIRE([KPSE_LIB_SYSTEM_FLAGS])
```

6.6.3 Adding a new T_EX-specific library module

A T_EX-specific library module in a subdirectory `texk/lib` may depend on other T_EX-specific libraries but must not depend on any generic library from the TL tree. It is included in the same general ways as a generic library (see the previous section), with these modifications:

- The library name `lib` is added to the M4 list `kpse_texlibs_pkgs` also in `m4/kpse-pkgs.m4`.
- The fragment `ac/withenable.ac` must use `KPSE_WITH_TEXLIB`.

7 Configure options

Corresponding to the large number of program and library modules there are a large number `configure` options, most of which are described here. The command

```
configure --help
```

at the top level gives an exhaustive list of all global options and a few important module-specific ones, whereas, e.g.,

```
texk/lcdf-typetools/configure --help
```

also displays the `lcdf-typetools` specific options, which are not shown at the top-level.

The help text also mentions several influential environment variables, but for T_EX Live it is better to specify them as assignments on the command line.

The `./Build` script used to make the binaries shipped with T_EX Live invokes the top-level `configure` with a few additional options (see Chapter 4 [Building], page 4). The defaults discussed below are those for the actual `configure` script; invoking `configure` via `./Build` may yield different results.

Defaults for most options are set at the top level and propagated explicitly to all sub-directories. Options specified on the command line are checked for consistency but never modified.

7.1 Global configure options

Here are the global configure options.

7.1.1 `--disable-native-texlive-build`

If enabled (the default), build for a TL binary distribution as shipped by the T_EX user groups. This requires GNU `make` and implies `--enable-multiplatform` and `--enable-cxx-runtime-hack` (unless they are explicitly disabled), and enforces `--disable-shared`.

If building TL for a GNU/Linux or other distribution, this should be disabled and system versions of most libraries would be used (see Section 5.3 [Distro builds], page 8). This may fail without GNU `make`, but will be tried regardless.

A related option, `--enable-texlive-build`, is automatically passed to all subdirectories (and cannot be disabled). Subdirectories that can also be built independently from the TL tree (such as `utils/xindy` and `texk/dvipng`) can use this option, e.g., to choose TL-specific installation paths.

7.1.2 `--prefix`, `--bindir`, ...

These standard Autoconf options specify various installation directories as usual. For the complete list, see Section 5.1 [Installation directories], page 7.

Also as usual, all values are prefixed by the value of `DESTDIR`, if set, on the `make` command line (see Section “Installation in a temporary location” in *GNU Automake*).

7.1.3 `--disable-largefile`

Omit large file support (LFS), needed on most 32-bit Unix systems for files with 2GB or more. Regardless of this, the size of DVI and GF files must always be < 2GB, due to the file format specifications.

With LFS, there is no fixed limit on the size of PDF files created by `pdftex` or PostScript files created by `dvips`. The size of PDF images included by `pdftex` or `luatex` must, however, be < 2GB when using `poppler` version 0.22 or before (even on 64-bit systems with LFS).

7.1.4 `--disable-missing`

Immediately terminate the build process if a requested program or feature must be disabled, e.g., due to missing libraries. This can help when figuring out a specific (sub)set of modules to enable.

7.1.5 `--enable-compiler-warnings=level`

Enable various levels of compiler warnings for (Objective) C and C++: the *level* value can be one of: `no` `min` `yes` `max` `all`. The default is `yes` in `maintainer-mode` (see below) and `min` otherwise. This option defines `WARNING_[OBJ]C[XX]FLAGS` but these flags are not used in all library and program modules. Using them should help to resolve portability problems.

At present, these warning flags are only defined for the GNU compilers but flags for other compilers could be added when needed.

7.1.6 `--enable-cxx-runtime-hack`

If enabled (as it is for the native TL build) and when using `g++`, try to statically link with `libstdc++`, somewhat improving portability of the resulting binary. See Section 6.3.3 [Macros for compilers], page 12.

7.1.7 `--enable-maintainer-mode`

Enable `make` rules and dependencies not useful (and sometimes confusing) to the casual user. This requires current versions of the GNU build tools (see Section 6.1 [Build system tools], page 10), as it automatically rebuilds infrastructure files as needed. See Section “missing and `AM_MAINTAINER_MODE`” in *GNU Automake*.

7.1.8 `--enable-multiplatform`

If enabled and `--bindir=dir` or `--libdir=dir` are not specified, install executables and libraries in per-platform subdirectories of `eprefix/bin` and `eprefix/lib` where *eprefix* is the value given or implied for `exec_prefix`. In any case, the values for `bindir` and `libdir` are automatically propagated to all subdirectories.

7.1.9 `--enable-shared`

Build shared versions of the TeX-specific libraries such as `libkpathsea`. This is not allowed for a native TL build (i.e., `--disable-native-texlive-build` must also be specified).

7.1.10 `--enable-silent-rules`

Enable the use of less verbose build rules. When using GNU `make` (or another `make` implementation supporting nested variable expansions), you can specify `V=1` on the `make` command line to get more verbosity, or `V=0` to get less, regardless of this option.

7.1.11 `--without-ln-s`

Required when using a system without a working `ln -s` to build binaries for a Unix-like system. However, `make install` will not create anything useful and might even fail.

7.1.12 `--without-x`

Disable all programs using the X Window System.

7.2 Program-specific configure options

Here are (some of) the program-specific `configure` options.

7.2.1 `--enable-prog`, `--disable-prog`

Do or do not build and install the program(s) of the module *prog*.

7.2.2 `--disable-all-pkgs`

Do not build any program modules by default—only those explicitly enabled. This is useful when one wants to work on only a single program, which is specified with an additional `--enable` option, e.g., `--enable-dvipdfm-x`. It's still simplest to check out and configure the whole source tree, but at least only the program you are interested in, and its dependencies, are built. The `configure` will generally take less than a minute with everything disabled. (It is a good idea to run `make check` after doing this, and after making any changes, to ensure that whatever tests have been written still pass.)

Without this option, all modules are built except those that are explicitly disabled or specify `disable` in their `ac/withenable.ac` fragment.

7.2.3 Configure options for `texk/web2c`

`--with-banner-add=str`

Add *str* to the default version string (TeX Live *year* or Web2C *year*) appended to banner lines. This is ignored for a native TL build, but distro builds should specify, e.g., */SomeDistro*.

`--with-editor=cmd`

Specify the command *cmd* to invoke from the `e` option of T_EX-like engines, replacing the default `vi +%d '%s'` for Unix or `texworks --position=%d "%s"` for Windows.

`--with-fontconfig-includes=dir`, `--with-fontconfig-libdir=dir`

Building XeT_EX on non-Mac systems requires the `fontconfig` library headers and code. If one or both of these options are given, the required flags are derived from them; otherwise, they are determined via `pkg-config` (if present).

`--with-mf-x-toolkit`

Use the X toolkit (`libXt`) for Metafont (the default is to use the lowest-level `Xlib` support; it seems this has the best chance of working across X installations nowadays).

`--disable-dump-share`

Make the `fmt/base` dump files architecture dependent (somewhat faster on LittleEndian architectures).

`--disable-ipc`

Disable T_EX's `--ipc` option.

`--disable-mf-nowin`

Do not build a separate non-graphically-capable Metafont (`mf-nowin`).

--disable-tex, --enable-etex, ...

Do not or do build the various T_EX, Metafont, and MetaPost engines (defaults are defined in the fragment `texk/web2c/ac/web2c.ac`).

--disable-web-progs

Do not build the core WEB programs `bibtex`, ..., `weave`. Useful if, e.g., you only want to (re)build some engines.

--enable-auto-core

This option causes T_EX and Metafont to produce a core dump when a particular hacky filename is encountered, for use in creating preloaded binaries. This is rarely done nowadays.

--enable-libtool-hack

If enabled (which is the default for all platforms), prevents `libtool` from linking explicitly with dependencies of `libfontconfig` such as `libexpat`.

--enable-*win

Include various types of other window support for Metafont (EPSF output, `mftalk`, old terminals, ...).

--enable-tex-synctex, --disable-etex-synctex, ...

Build the T_EX engines with or without SyncTeX support; ignored for a native T_EX Live build, defaults are again defined in `texk/web2c/ac/web2c.ac`.

--disable-synctex

Do not build the SyncTeX library and tool.

7.2.4 Configure options for `texk/bibtex-x`

The programs `bibtex8` and `bibtexu` have been merged into the module `bibtex-x` (extended BibT_EX).

--disable-bibtex8

Do not build the `bibtex8` program.

--disable-bibtexu

Do not build the `bibtexu` program (building `bibtexu` requires ICU libraries).

7.2.5 Configure options for `texk/dvipdfm-x`

The former modules `dvipdfmx` (extended DVI to PDF converter) and `xdvipdfmx` (the same, as used by XeT_EX) have been merged into `dvipdfm-x` at the source level. Two separate binaries are still created by default. In addition, `dvipdfm` is created as a symlink to `dvipdfmx`, with backward-compatible (very slightly different) behavior.

--disable-dvipdfmx

Do not build the `dvipdfmx` program with the `dvipdfm` symlink.

--disable-xdvipdfmx

Do not build the `xdvipdfmx` program.

7.2.6 Configure options for `texk/dvisvgm`

--with-system-libgs

Build `dvisvgm` using installed Ghostscript (`gs`) headers and library (not allowed for a native TL build). The default is to load the `gs` library at runtime if possible, or otherwise disable support for PostScript specials.

--without-libgs

Build `dvisvgm` without PostScript support at all. Because the dynamic loading just mentioned defeats all attempts at static linking, the result can crash due to library incompatibilities, e.g., on CentOS 5.

--with-libgs-includes=dir, --with-libgs-libdir=dir

Specify non-standard locations of the Ghostscript headers and library.

7.2.7 Configure options for `texk/texlive`**--disable-linked-scripts**

Do not install the “linked scripts” (see Section 5.2 [Linked scripts], page 7), except for the TL scripts required to run `texlinks`.

7.2.8 Configure options for `texk/xdvik`**--with-gs=filename**

Hardwire the location of Ghostscript (`gs`).

--with-xdvi-x-toolkit=kit

Use toolkit *kit* for `xdvik`, one of: `motif` `xaw` `xaw3d` `neXtaw`. The default is `motif` if available, else `xaw`.

--enable-xi2-scrolling

Use XInput 2.1 “smooth scrolling” if available. (default: yes, except for a native TL build).

7.2.9 Configure options for `utils/xindy`**--enable-xindy-rules**

Build and install `xindy` rules (default: yes, except for a native TL build).

--enable-xindy-docs

Build and install `xindy` documentation (default: yes, except for a native TL build).

--with-clisp-runtime=filename

Specifies the Full path for the CLISP runtime file (`lisp.run` or `lisp.exe`) to be installed. When specified as `default` (the default for a native TL build) the path is determined by the CLISP executable; the value `system` (not allowed for a native TL build, but the default for a non-native one) indicates that `xindy` will use the installed version of `clisp` (which must be identical to the one used to build `xindy`).

7.3 Library-specific configure options

Here are (some of) the library-specific configure options, starting with this generic one:

--with-system-lib

Use an installed (system) version of the library *lib*; this option exists for most libraries, but is not allowed for a native TL build. Using a system version implies also using the system versions of all libraries (if any) that *lib* depends on.

For many libraries `--with-lib-includes=dir` and `--with-lib-libdir=dir` can specify non-standard search locations; others use `pkg-config` or similar to determine the required flags.

The top-level `configure` script performs a consistency check for all required system libraries and bails out if tests fail.

7.3.1 Configure options for kpathsea

`--enable-cmd-default`, `--disable-cmd-default`

Determine the compile time default whether or not to run *cmd*, one of:

`mkocp` (Omega compiled translation process file)
`mkofm` (Omega font metrics file)
`mktxfmt` (format/base dump file)
`mktxmf` (Metafont source)
`mktxpk` (PK bitmap font)
`mktextex` (T_EX source)
`mktextfm` (TFM file)

to generate the specified type of file dynamically. The default can be overridden by the user in any case.

7.3.2 Configure options for system poppler

Building LuaT_EX (or LuaJIT_EX) and XeT_EX requires **poppler**, either from the TL tree or system headers and library. Building pdfT_EX requires either **xpdf** from the T_EX Live tree or system **poppler** headers and library.

`--with-system-poppler`

Use a system version (0.18 or newer) of **poppler** for LuaT_EX (or LuaJIT_EX) and XeT_EX, and use **pkg-config** to obtain the required flags.

`--with-system-xpdf`

Use a system version (0.12 or better) of **poppler** (and **pkg-config**) for pdfT_EX instead of **xpdf** from the TL tree. See Section 7.1.3 [`--disable-largefile`], page 20.

7.4 Variables for configure

The values for these variables can be specified as **configure** arguments of the form *VAR=value*. They can also be defined in the environment, but that might not work for cross compilations.

CC

CXX

CPPFLAGS And plenty more. As usual with Autoconf, these variables specify the name (or full path) of compilers, preprocessor flags, and similar. See Section “autoconf” in GNU Autoconf.

CLISP Name (or full path) of the **clisp** executable, used to build **xindy**.

FT2_CONFIG

ICU_CONFIG

PKG_CONFIG

These specify the name (or path) for the **freetype-config**, **icu-config**, and **pkg-config** commands used to determine the flags required for system versions of **libfreetype**, the ICU libraries, or many other libraries.

KPSEWHICH

Name (or path) of an installed `kpsewhich` binary, used by `make check` to determine the location of, e.g., `cmbx10.tfm`.

MAKE

SED And more. Name (or path) of the `make`, `sed`, and similar programs; used at the top level and propagated to all subdirectories.

PERL**LATEX**

PDFLATEX Name (or full path) for the `perl`, `latex`, and `pdflatex` commands used, e.g., to build the `xindy` documentation.

8 Cross compilation

In a cross compilation a *build* system is used to create binaries to be executed on a *host* system with different hardware and/or operating system.

In simple cases, the build system can execute binaries for the host system. This typically occurs for bi-arch systems where, e.g., `i386-linux` binaries can run on `x86_64-linux` systems and `win32` binaries can run on `win64` systems. Although sometimes called “native cross”, technically this is not cross compilation at all. In most such cases it suffices to specify suitable compiler flags. It might be useful to add the configure option `--build=host` to get the correct canonical host name, but note that this should *not* be `--host=host` (see Section “Hosts and Cross-Compilation” in *GNU Autoconf*).

In order to build, e.g., 32-bit binaries with `clang` on a 64-bit MacOSX system one could use:

```
TL_BUILD_ENV="CC='clang -arch i386' \  
CXX='clang++ -arch i386' \  
OBJCXX='clang++ -arch i386'" \  
./Build --build=i386-apple-darwin
```

8.1 Cross configuring

In a standard cross compilation, binaries for the host system cannot execute on the build system and it is necessary to specify the configure options `--host=host` and `--build=build` with two different values.

Building binaries requires suitable “cross” tools, e.g., compiler, linker, and archiver, and perhaps a “cross” version of `pkg-config` and similar to locate host system libraries. Autoconf expects that these cross tools are given by their usual variables or found under their usual name prefixed with *host-*. Here a list of such tools and corresponding variables:

<code>ar</code>	<code>AR</code>
<code>freetype-config</code>	<code>FT2_CONFIG</code>
<code>g++</code>	<code>CXX</code>
<code>gcc</code>	<code>CC</code>
<code>icu-config</code>	<code>ICU_CONFIG</code>
<code>objdump</code>	<code>OBJDUMP</code>
<code>pkg-config</code>	<code>PKG_CONFIG</code>
<code>ranlib</code>	<code>RANLIB</code>
<code>strip</code>	<code>STRIP</code>

In order to, e.g., build `mingw32` binaries on `x86_64-linux` with a cross compiler found as `i386-pc-mingw32-gcc` one would specify

```
--host=i386-pc-mingw32 --build=x86_64-linux-gnu
```

or perhaps

```
--host=mingw32 --build=x86_64-linux CC=i386-pc-mingw32-gcc
```

but this latter, especially, might require adding `CXX` and others.

Configure arguments such as `CFLAGS=...` refer to the cross compiler. If necessary, you can specify compilers and flags for the few auxiliary C and C++ programs required for the build process as configure arguments

```
BUILDCC=...  
BUILDCCPPFLAGS=...  
BUILDCCFLAGS=...  
BUILDCCXX=...  
BUILDCCXXFLAGS=...  
BUILDLDFLAGS=...
```

8.2 Cross problems

The fact that binaries for the host system cannot be executed on the build system causes some problems.

One problem is that configure tests using `AC_RUN_IFELSE` can compile and link the test program but cannot execute it. Such tests should be avoided if possible and otherwise must supply a pessimistic test result.

Another problem arises if the build process must execute some (auxiliary or installable) programs. Auxiliary programs can be placed into a subdirectory that is configured natively as is done for `texk/web2c/web2c`, `texk/dvipsk/squeeze`, and `texk/xdvik/squeeze`. The module `libs/freetype2` uses the value of `CC_BUILD`, `build-gcc`, `gcc`, or `cc` as the compiler for the auxiliary program.

The situation for installable programs needed by the build process is somewhat different. A rather expensive possibility, chosen for the ICU libraries in module `libs/icu`, is to first compile natively for the build system and in a second step to use these (uninstalled) programs during the cross compilation.

This approach would also be possible for the tools such as `tangle` used in the module `texk/web2c` to build the WEB programs, but that would require first building a native `kpathsea` library. To avoid this complication, cross compilation of the WEB or CWEB programs requires sufficiently recent installed versions of `tangle`, `ctangle`, `otangle`, and `tie`.

Building `xindy` requires running the host system `clisp` binary, thus cross compilation is not possible.

9 Coding conventions

Ideally, building all of T_EX Live with `--enable-compiler-warnings=max` should produce no (GCC) compiler warnings at all. In spite of considerable efforts into that direction we are still far from that goal and there are reasons that we may never fully reach it. Below are some rules about declarations of functions or variables and the use of `const`. These rules should be applied to most of the T_EX Live tree, the exception being code that is maintained independently and whose maintainers don't want to accept patches.

9.1 Declarations and definitions

C standards

The T_EX Live build system no longer supports pre-ANSI C compilers. Thus all function prototypes and definitions must conform to the ANSI C standard (including `void` in the declaration of C functions with no parameters). On the other hand, TL is built for a wide variety of systems, not all of which support the C99 standard. Therefore using C99 features should be avoided if that can easily be done. In particular C code must not contain declarations after statements or C++-style comments.

If some C99 (or later) constructs must be used, the module should verify that they are available and otherwise provide an alternative. For example, the module `texk/chktex` uses the C99 function `strcpy()` that may or may not be available on a particular system. It uses `AC_CHECK_DECLS([strcpy])` in `configure.ac` to test this, and provides the perhaps slightly less efficient alternative

```
#if !(defined HAVE_DECL_STPCPY && HAVE_DECL_STPCPY)
static inline char *strcpy(char *dest, const char *src)
{
    return strcpy(dest, src) + strlen(src);
}
#endif
```

in the file `Utility.h`.

Static functions

Functions used in only one file should be declared `static`; they require no prototype except as forward declaration.

Extern functions

Functions not declared `static`, usually because they are used in several files, require an (`extern`) prototype in exactly one header file, which is included in the file defining the function and in all files using that function—this is the only way to guarantee consistency between definition and use. There should be no `extern` declarations sprinkled throughout the C code (with or without comments as to where that function is defined).

Variable declarations

The declaration of global variables follows analogous rules: they are either declared `static` if used in only one file or declared `extern` in exactly one header and instantiated in exactly one file.

9.2 Const

The `const` feature of C is valuable, but easy to mis-use.

Function parameters

Ideally, a function parameter not modified by the function should be declared as `const`. This is important in particular for strings (`char*`) because the actual arguments are often string literals. It is perfectly legitimate and safe to use a type `char*` value for a type `const char*` variable (in an assignment, as initializer, as function argument, or as return value). It is equally safe to use a type `char**` value for a type `const char*const*` variable, but not for a type `const char**` variable since that might cause modification of a quantity supposed to be constant.

Getting all `const` qualifiers right can get quite involved but can almost always be done. There are only a couple notable exceptions: the X11 headers are full of declarations that ought to use `const` but do not, and the same is true to some extent for `libfreetype` (but, thankfully, not for `zlib` nowadays).

What must be avoided with const

The GCC compiler warnings “assignment discards qualifiers. . .” and analogous warnings for “initialization”, “passing arg”, or “return” must be strenuously avoided in our own code. The only exception is when they are caused by X11 headers or macros or other third party code.

What should be avoided with const

A type cast, e.g., from `const char*` to `char*` does not solve any problems; depending on warning options, it may only hide them. Therefore such casts should be avoided whenever possible and otherwise must be carefully analyzed to make sure that they cannot cause the modification of quantities supposed to be constant.

10 Continuous integration

Overview: the sources of T_EX Live are subjected to continuous integration testing on Travis-CI (<https://travis-ci.org/TeX-Live/texlive-source>) via a git-svn mirror of the sources that is pushed to Github (<https://github.com/TeX-Live/texlive-source>). The git-svn mirror is updated (currently) at 30 minute intervals, and only the last commit pushed is tested on Travis-CI.

Transfer from Subversion to Github

git-svn (<https://git-scm.com/docs/git-svn>) is used to check out the subtree `Build/source` of the Subversion repository. The author index file used is not maintained in either Git or Subversion but can be provided on request.

The initial checkout was done by invoking

```
git svn --authors-file usermap clone svn://USER@tug.org/texlive/trunk/Build/source
```

where the `usermap` file maps Subversion user names to name and emails of the authors. If no user account at `tug.org` is available, anonymous checkout is possible, too:

```
git svn --authors-file usermap clone svn://tug.org/texlive/trunk/Build/source
```

In the following, we will use *admin* to refer to a user who has read/write access to the T_EX Live subversion repository, and is also an administrator of the TeX-Live Team on Github. The above initial checkout has been carried out by *admin* on the server `texlive.info`.

On Github (<https://github.com>), a new git repository named `texlive-source` was created by *admin* within the TeX-Live “organization” (<https://github.com/TeX-Live>). The remote was added to the checkout with `git remote add origin git@github.com:TeX-Live/texlive-source.git`.

To automate the update on Github, a new ssh key was generated and added to the `texlive-source` repository on Github as deployment key. This way pushes using this key can only go to the `texlive-source` repository and not anywhere else.

The usage of `git-svn` requires a strict discipline to keep a linear history in the master branch. Since we are aiming at a pure mirror facility, we have decided to further restrict the `master` branch of the `texlive-source` repository on Github to changes by *admin*.

This setup allows other developers to branch off `master` and push their branches to the Github repository, but all updates need to come from the local `master` (not the one on Github) to Subversion, back to `master` on `texlive.info`, and from there to Github.

Automatic update of the Git mirror

admin has installed a cron job on `texlive.info` running every 30 minute which essentially runs `git svn rebase` and `git push` in the `master` branch of the checkout. The first command fetches the changes from the Subversion repository and updates the `master` branch with them, the second one pushes changes (if available) to Github.

CI testing on Travis-CI

The `source` tree of T_EX Live contains a top-level file `.travis.yml` which controls the automatic testing on Travis-CI. *admin* has registered to Travis-CI and allowed access to

the Github's **TeX-Live** organization's **texlive-source** repository. The default settings are to build the last commit of each push. No further action is necessary on Travis-CI.

If changes have been pushed via the cron job above, Travis-CI will automatically checkout the last pushed commit and try building it.

Appendix A install-tl

A.1 NAME

install-tl - TeX Live cross-platform installer

A.2 SYNOPSIS

```
install-tl [option]...
install-tl.bat [option]...
```

A.3 DESCRIPTION

This installer creates a runnable TeX Live installation from various media, including over the network. The installer works across all platforms supported by TeX Live. For information on initially downloading the TeX Live, see <http://tug.org/texlive/acquire.html>.

The basic idea of TeX Live installation is to choose one of the top-level *schemes*, each of which is defined as a different set of *collections* and *packages*, where a collection is a set of packages, and a package is what contains actual files.

Within the installer, you can choose a scheme, and further customize the set of collections to install, but not the set of the packages. To do that, use **tlmgr** (reference below) after the initial installation is completely.

The default is **scheme-full**, to install everything, and this is highly recommended.

A.4 REFERENCES

Post-installation configuration, package updates, and much more, are handled through **tlmgr**(1), the TeX Live Manager (<http://tug.org/texlive/tlmgr.html>).

The most up-to-date version of this documentation is on the Internet at <http://tug.org/texlive/doc/install-tl.html>.

For the full documentation of TeX Live, see <http://tug.org/texlive/doc>.

A.5 OPTIONS

As usual, all options can be specified in any order, and with either a leading **-** or **--**. An argument value can be separated from its option by either a space or **=**.

-gui **[[=]***module***]**

If no *module* is given starts the **perlTk** (see below) GUI installer.

If *module* is given loads the given installer module. Currently the following modules are supported:

text

The text mode user interface (default on Unix systems). Same as the **-no-gui** option.

wizard

The wizard mode user interface (default on Windows), asking only minimal questions before installing all of TeX Live.

perlTk

The expert GUI installer, providing access to more options. Can also be invoked on Windows by running `install-tl-advanced.bat`.

The `perlTk` and `wizard` modules, and thus also when calling with a bare `-gui` (without *module*), requires the Perl/Tk module (<http://tug.org/texlive/distro.html#perlTk>); if Perl/Tk is not available, installation continues in text mode.

-no-gui

Use the text mode installer (default except on Windows).

-lang *llcode*

By default, the GUI tries to deduce your language from the environment (on Windows via the registry, on Unix via `LC_MESSAGES`). If that fails you can select a different language by giving this option with a language code (based on ISO 639-1). Currently supported (but not necessarily completely translated) are: English (`en`, default), Czech (`cs`), German (`de`), French (`fr`), Italian (`it`), Japanese (`ja`), Dutch (`nl`), Polish (`pl`), Brazilian Portuguese (`pt_BR`), Russian (`ru`), Slovak (`sk`), Slovenian (`sl`), Serbian (`sr`), Ukrainian (`uk`), Vietnamese (`vi`), simplified Chinese (`zh_CN`), and traditional Chinese (`zh_TW`).

-repository *url|path*

Specify the package repository to be used as the source of the installation, either a local directory via `/path/to/directory` or a `file:/` url, or a network location via a `http://` or `ftp://` url. (No other protocols are supported.)

The default is to pick a mirror automatically, using <http://mirror.ctan.org/systems/texlive/tlnet>; the chosen mirror is used for the entire download. You can use the special argument `ctan` as an abbreviation for this. See <http://ctan.org> for more about CTAN and its mirrors.

If the repository is on the network, trailing `/` characters and/or trailing `/tlpkg` and `/archive` components are ignored. For example, you could choose a particular CTAN mirror with something like this:

```
-repository http://ctan.example.org/its/ctan/dir/systems/texlive/tlnet
```

Of course a real hostname and its particular top-level CTAN path have to be specified. The list of CTAN mirrors is available at <http://ctan.org/mirrors>.

If the repository is local, the installation type (compressed or live) is automatically determined, by checking for the presence of a `archive` directory relative to the root. Compressed is preferred if both are available, since it is faster. Here's an example of using a local directory:

```
-repository /local/TL/repository
```

After installation is complete, you can use that installation as the repository for another installation. If you chose to install less than the full scheme containing all packages, the list of available schemes will be adjusted accordingly.

For backward compatibility and convenience, `--location` and `--repo` are accepted as aliases for this option.

-select-repository

This option allows manual selection of a mirror from the current list of active CTAN mirrors. This option is supported in all installer modes (text, wizard, perlTk), and will also offer to install from local media if available, or from a repository specified on the command line (see above). It's useful when the (default) automatic redirection does not choose a good host for you.

-all-options

Normally options not relevant to the current platform are not shown (i.e., when running on Unix, Windows-specific options are omitted). Giving this command line option allows configuring settings in the final `texlive.tlpdb` that do not have any immediate effect.

-custom-bin *path*

If you have built your own set of TeX Live binaries (perhaps because your platform was not supported by TeX Live out of the box), this option allows you to specify the *path* to a directory where the binaries for the current system are present. The installation will continue as usual, but at the end all files from *path* are copied over to `bin/custom/` under your installation directory and this `bin/custom/` directory is what will be added to the path for the post-install actions. (By the way, for information on building TeX Live, see <http://tug.org/texlive/build.html>).

-debug-translation

In GUI mode, this switch makes `tlmgr` report any missing, or more likely untranslated, messages to standard error. Helpful for translators to see what remains to be done.

-force-platform *platform*

Instead of auto-detecting the current platform, use *platform*. Binaries for this platform must be present and they must actually be runnable, or installation will fail. `-force-arch` is a synonym.

-help, -help, -?

Display this help and exit (on the web via <http://tug.org/texlive/doc/install-tl.html>). Sometimes the `perlDoc` and/or `PAGER` programs on the system have problems, possibly resulting in control characters being literally output. This can't always be detected, but you can set the `NOPERLDOC` environment variable and `perlDoc` will not be used.

-in-place

This is a quick-and-dirty installation option in case you already have an `rsync` or `svn` checkout of TeX Live. It will use the checkout as-is and will just do the necessary post-install. Be warned that the file `tlpkg/texlive.tlpdb` may be rewritten, that removal has to be done manually, and that the only realistic way to maintain this installation is to redo it from time to time. This option is not available via the installer interfaces. **USE AT YOUR OWN RISK.**

-logfile *file*

Write both all messages (informational, debugging, warnings) to *file*, in addition to standard output or standard error.

If this option is not given, the installer will create a log file in the root of the writable installation tree, for example, `/usr/local/texlive/YYYY/install-tl.log` for the *YYYY* release.

-no-cls

(only for text mode installer) do not clear the screen when entering a new menu (for debugging purposes).

-non-admin

For Windows only: configure for the current user, not for all users.

-persistent-downloads

-no-persistent-downloads

For network installs, activating this option makes the installer try to set up a persistent connection using the `Net::LWP` Perl module. This opens only one connection between your computer and the server per session and reuses it, instead of initiating a new download for each package, which typically yields a significant speed-up.

This option is turned on by default, and the installation program will fall back to using `wget` if this is not possible. To disable usage of LWP and persistent connections, use `--no-persistent-downloads`.

-portable

Install for portable use, e.g., on a USB stick. Also selectable from within the `perltk` and text installers.

-print-platform

Print the TeX Live identifier for the detected platform (hardware/operating system) combination to standard output, and exit. `-print-arch` is a synonym.

-profile *profile*

Load the file *profile* and do the installation with no user interaction, that is, a batch (unattended) install.

A *profile* file contains all the values needed to perform an installation. After a normal installation has finished, a profile for that exact installation is written to the file `DEST/tlpkg/texlive.profile`. That file can be given as the argument to `-profile` to redo the exact same installation on a different system, for example. Alternatively, you can use a custom profile, most easily created by starting from a generated one and changing values, or an empty file, which will take all the defaults.

Normally a profile has to specify the value `1` for each collection to be installed, even if the scheme is specified. This follows from the logic of the installer in that you can first select a scheme and then change the collections being installed. But for convenience there is an exception to this within profiles: If the profile contains a variable for `selected_scheme` and *no* collection variables at all are defined in the profile, then the collections which the specified scheme requires are installed.

Thus, a line `selected_scheme scheme-medium` together with the definitions of the installation directories (`TEXDIR`, `TEXMFHOME`, `TEXMFLOCAL`, `TEXMFSYSCONFIG`, `TEXMFSYSVAR`) suffices to install the medium scheme with all default options.

-q

Omit normal informational messages.

-scheme *scheme*

Schemes are the highest level of package grouping in TeX Live; the default is to use the `full` scheme, which includes everything. This option overrides that default. You can change the scheme again before the actual installation with the usual menu. The *scheme* argument may optionally have a prefix `scheme-`. The list of supported scheme names depends on what your package repository provides; see the interactive menu list.

-v

Include verbose debugging messages; repeat for maximum debugging, as in `-v -v`. (Further repeats are accepted but ignored.)

-version, --version

Output version information and exit. If `-v` has also been given the revisions of the used modules are reported, too.

A.6 ENVIRONMENT VARIABLES

For ease in scripting and debugging, `install-tl` will look for the following environment variables. They are not of interest in normal user installations.

TEXLIVE_INSTALL_ENV_NOCHECK

Omit the check for environment variables containing the string `tex`. People developing TeX-related software are likely to have many such variables.

TEXLIVE_INSTALL_NO_CONTEXT_CACHE

Omit creating the ConTeXt cache. This is useful for redistributors.

TEXLIVE_INSTALL_PREFIX**TEXLIVE_INSTALL_TEXMFCONFIG****TEXLIVE_INSTALL_TEXMFHOME****TEXLIVE_INSTALL_TEXMFLOCAL****TEXLIVE_INSTALL_TEXMFSYSCONFIG****TEXLIVE_INSTALL_TEXMFSYSVAR****TEXLIVE_INSTALL_TEXMFVAR**

Specify the respective directories.

NOPERLDOC

Don't try to run the `--help` message through `perldoc`.

A.7 AUTHORS AND COPYRIGHT

This script and its documentation were written for the TeX Live distribution (<http://tug.org/texlive>) and both are licensed under the GNU General Public License Version 2 or later.

Appendix B `tlmgr`

B.1 NAME

`tlmgr` - the TeX Live Manager

B.2 SYNOPSIS

`tlmgr` [*option*]... *action* [*option*]... [*operand*]...

B.3 DESCRIPTION

tlmgr manages an existing TeX Live installation, both packages and configuration options. For information on initially downloading and installing TeX Live, see <http://tug.org/texlive/acquire.html>.

The most up-to-date version of this documentation (updated nightly from the development sources) is available at <http://tug.org/texlive/tlmgr.html>, along with procedures for updating **tlmgr** itself and information about test versions.

TeX Live is organized into a few top-level *schemes*, each of which is specified as a different set of *collections* and *packages*, where a collection is a set of packages, and a package is what contains actual files. Schemes typically contain a mix of collections and packages, but each package is included in exactly one collection, no more and no less. A TeX Live installation can be customized and managed at any level.

See <http://tug.org/texlive/doc> for all the TeX Live documentation available.

B.4 EXAMPLES

After successfully installing TeX Live, here are a few common operations with **tlmgr**:

`tlmgr option repository http://mirror.ctan.org/systems/texlive/tlnet`

Tell **tlmgr** to use a nearby CTAN mirror for future updates; useful if you installed TeX Live from the DVD image and want continuing updates.

`tlmgr update --list`

Report what would be updated without actually updating anything.

`tlmgr update --all`

Make your local TeX installation correspond to what is in the package repository (typically useful when updating from CTAN).

`tlmgr info pkg`

Display detailed information about *pkg*, such as the installation status and description.

For all the capabilities and details of **tlmgr**, please read the following voluminous information.

B.5 OPTIONS

The following options to `tlmgr` are global options, not specific to any action. All options, whether global or action-specific, can be given anywhere on the command line, and in any order. The first non-option argument will be the main action. In all cases, `--option` and `-option` are equivalent, and an `=` is optional between an option name and its value.

-repository *url|path*

Specifies the package repository from which packages should be installed or updated, overriding the default package repository found in the installation's TeX Live Package Database (a.k.a. the TLPDB, defined entirely in the file `tlpkg/texlive.tlpdb`). The documentation for `install-tl` has more details about this (<http://tug.org/texlive/doc/install-tl.html>).

`--repository` changes the repository location only for the current run; to make a permanent change, use `option repository` (see the Section B.6.13 [option], page 46, action).

For backward compatibility and convenience, `--location` and `--repo` are accepted as aliases for this option.

-gui [*action*]

`tlmgr` has a graphical interface as well as the command line interface. You can give this option, `--gui`, together with an action to be brought directly into the respective screen of the GUI. For example, running

```
tlmgr --gui update
```

starts you directly at the update screen. If no action is given, the GUI will be started at the main screen.

-gui-lang *llcode*

By default, the GUI tries to deduce your language from the environment (on Windows via the registry, on Unix via `LC_MESSAGES`). If that fails you can select a different language by giving this option with a language code (based on ISO 639-1). Currently supported (but not necessarily completely translated) are: English (en, default), Czech (cs), German (de), French (fr), Italian (it), Japanese (ja), Dutch (nl), Polish (pl), Brazilian Portuguese (pt_BR), Russian (ru), Slovak (sk), Slovenian (sl), Serbian (sr), Ukrainian (uk), Vietnamese (vi), simplified Chinese (zh_CN), and traditional Chinese (zh_TW).

-debug-translation

In GUI mode, this switch tells `tlmgr` to report any untranslated (or missing) messages to standard error. This can help translators to see what remains to be done.

-machine-readable

Instead of the normal output intended for human consumption, write (to standard output) a fixed format more suitable for machine parsing. See the Section B.12 [MACHINE-READABLE OUTPUT], page 61, section below.

-no-execute-actions

Suppress the execution of the execute actions as defined in the `tlpsrc` files. Documented only for completeness, as this is only useful in debugging.

-package-logfile *file*

tlmgr logs all package actions (install, remove, update, failed updates, failed restores) to a separate log file, by default `TEXMFSYSVAR/web2c/tlmgr.log`. This option allows you to specify a different file for the log.

-pause

This option makes **tlmgr** wait for user input before exiting. Useful on Windows to avoid disappearing command windows.

-persistent-downloads**-no-persistent-downloads**

For network-based installations, this option (on by default) makes **tlmgr** try to set up a persistent connection (using the LWP Perl module). The idea is to open and reuse only one connection per session between your computer and the server, instead of initiating a new download for each package.

If this is not possible, **tlmgr** will fall back to using **wget**. To disable these persistent connections, use **--no-persistent-downloads**.

-pin-file

Change the pinning file location from `TEXMFLOCAL/tlpkg/pinning.txt` (see Section B.10.1 [Pinning], page 57, below). Documented only for completeness, as this is only useful in debugging.

-usermode

Activates user mode for this run of **tlmgr**; see Section B.7 [USER MODE], page 55, below.

-usertree *dir*

Uses *dir* for the tree in user mode; see Section B.7 [USER MODE], page 55, below.

The standard options for TeX Live programs are also accepted: **--help/-h/-?**, **--version**, **-q** (no informational messages), **-v** (debugging messages, can be repeated). For the details about these, see the **TeXLive::TLUtils** documentation.

The **--version** option shows version information about the TeX Live release and about the **tlmgr** script itself. If **-v** is also given, revision number for the loaded TeX Live Perl modules are shown, too.

B.6 ACTIONS

B.6.1 help

Display this help information and exit (same as **--help**, and on the web at <http://tug.org/texlive/doc/tlmgr.html>). Sometimes the **perldoc** and/or **PAGER** programs on the system have problems, resulting in control characters being literally output. This can't always be detected, but you can set the **NOPERLDOC** environment variable and **perldoc** will not be used.

B.6.2 version

Gives version information (same as **--version**).

If **-v** has been given the revisions of the used modules are reported, too.

B.6.3 backup [`--clean[=N]`] [`--backupdir dir`] [`--all` | *pkg*]...

If the `--clean` option is not specified, this action makes a backup of the given packages, or all packages given `--all`. These backups are saved to the value of the `--backupdir` option, if that is an existing and writable directory. If `--backupdir` is not given, the `backupdir` option setting in the TLPDB is used, if present. If both are missing, no backups are made.

If the `--clean` option is specified, backups are pruned (removed) instead of saved. The optional integer value *N* may be specified to set the number of backups that will be retained when cleaning. If *N* is not given, the value of the `autobackup` option is used. If both are missing, an error is issued. For more details of backup pruning, see the `option` action.

Options:

`--backupdir directory`

Overrides the `backupdir` option setting in the TLPDB. The *directory* argument is required and must specify an existing, writable directory where backups are to be placed.

`--all`

If `--clean` is not specified, make a backup of all packages in the TeX Live installation; this will take quite a lot of space and time. If `--clean` is specified, all packages are pruned.

`--clean[=N]`

Instead of making backups, prune the backup directory of old backups, as explained above. The optional integer argument *N* overrides the `autobackup` option set in the TLPDB. You must use `--all` or a list of packages together with this option, as desired.

`--dry-run`

Nothing is actually backed up or removed; instead, the actions to be performed are written to the terminal.

B.6.4 candidates *pkg*

`candidates pkg`

Shows the available candidate repositories for package *pkg*. See Section B.10 [MULTIPLE REPOSITORIES], page 57, below.

B.6.5 check [*option*]... [`files`|`depends`|`executes`|`runfiles`|`all`]

Executes one (or all) check(s) on the consistency of the installation.

`files`

Checks that all files listed in the local TLPDB (`texlive.tlpdb`) are actually present, and lists those missing.

`depends`

Lists those packages which occur as dependencies in an installed collections, but are themselves not installed, and those packages that are not contained in any collection.

If you call `tlmgr check collections` this test will be carried out instead since former versions for `tlmgr` called it that way.

executes

Check that the files referred to by **execute** directives in the TeX Live Database are present.

runfiles

List those filenames that are occurring more than one time in the runfiles.

Options:

-use-svn

Use the output of **svn status** instead of listing the files; for checking the TL development repository.

B.6.6 **conf** [**texmf**|**tlmgr**|**updmap** [**-conffile** *file*] [**-delete**] [*key* [*value*]]]

With only **conf**, show general configuration information for TeX Live, including active configuration files, path settings, and more. This is like the **texconfig conf** call, but works on all supported platforms.

With either **conf texmf**, **conf tlmgr**, or **conf updmap** given in addition, shows all key/value pairs (i.e., all settings) as saved in `ROOT/texmf.cnf`, the tlmgr configuration file (see below), or the first found (via `kpsewhich`) `updmap.cfg` file, respectively.

If *key* is given in addition, shows the value of only that *key* in the respective file. If option **-delete** is also given, the configuration file – it is removed, not just commented out!

If *value* is given in addition, *key* is set to *value* in the respective file. *No error checking is done!*

In all cases the file used can be explicitly specified via the option **--conffile file**, in case one wants to operate on a different file.

Practical application: if the execution of (some or all) system commands via `\write18` was left enabled during installation, you can disable it afterwards:

```
tlmgr conf texmf shell_escape 0
```

A more complicated example: the `TEXMFHOME` tree (see the main TeX Live guide, <http://tug.org/texlive/doc.html>) can be set to multiple directories, but they must be enclosed in braces and separated by commas, so quoting the value to the shell is a good idea. Thus:

```
tlmgr conf texmf TEXMFHOME "{~/texmf,~/texmfbis}"
```

Warning: The general facility is here, but tinkering with settings in this way is very strongly discouraged. Again, no error checking on either keys or values is done, so any sort of breakage is possible.

B.6.7 **dump-tlpdb** [**-local**|**-remote**]

Dump complete local or remote TLPDB to standard output, as-is. The output is analogous to the **--machine-readable** output; see Section B.12 [MACHINE-READABLE OUTPUT], page 61, section.

Options:

-local

Dump the local tlpdb.

-remote

Dump the remote tlpdb.

Exactly one of `--local` and `--remote` must be given.

In either case, the first line of the output specifies the repository location, in this format:

```
"location-url" "\t" location
```

where `location-url` is the literal field name, followed by a tab, and *location* is the file or url to the repository.

Line endings may be either LF or CRLF depending on the current platform.

B.6.8 generate [option]... what

generate language

generate language.dat

generate language.def

generate language.dat.lua

generate fmtutil

The **generate** action overwrites any manual changes made in the respective files: it recreates them from scratch based on the information of the installed packages, plus local adaptations. The TeX Live installer and **tlmgr** routinely call **generate** for all of these files.

For managing your own fonts, please read the **updmap --help** information and/or <http://tug.org/fonts/fontinstall.html>.

In more detail: **generate** remakes any of the configuration files `language.dat`, `language.def`, `language.dat.lua`, and `fmtutil.cnf`, from the information present in the local TLPDB, plus locally-maintained files.

The locally-maintained files are `language-local.dat`, `language-local.def`, `language-local.dat.lua`, or `fmtutil-local.cnf`, searched for in `TEXMFLOCAL` in the respective directories. If local additions are present, the final file is made by starting with the main file, omitting any entries that the local file specifies to be disabled, and finally appending the local file.

(Historical note: The formerly supported `updmap-local.cfg` is no longer read, since **updmap** now supports multiple `updmap.cfg` files. Thus, local additions can and should be put into an `updmap.cfg` file in `TEXMFLOCAL`. The **generate updmap** action no longer exists.)

Local files specify entries to be disabled with a comment line, namely one of these:

```
#!NAME
```

```
%!NAME
```

```
--!NAME
```

where `fmtutil.cnf` uses `#`, `language.dat` and `language.def` use `%`, and `language.dat.lua` use `--`. In all cases, the *name* is the respective format name or hyphenation pattern identifier. Examples:

```
#!pdflatex
```

```
%!german
```

```
--!usenglishmax
```

(Of course, you're not likely to actually want to disable those particular items. They're just examples.)

After such a disabling line, the local file can include another entry for the same item, if a different definition is desired. In general, except for the special disabling lines, the local files follow the same syntax as the master files.

The form `generate language` recreates all three files `language.dat`, `language.def`, and `language.dat.lua`, while the forms with an extension recreates only that given language file.

Options:

-dest *output_file*

specifies the output file (defaults to the respective location in `TEXMFSYSVAR`). If **--dest** is given to `generate language`, it serves as a basename onto which `.dat` will be appended for the name of the `language.dat` output file, `.def` will be appended to the value for the name of the `language.def` output file, and `.dat.lua` to the name of the `language.dat.lua` file. (This is just to avoid overwriting; if you want a specific name for each output file, we recommend invoking `tlmgr` twice.)

-localcfg *local_conf_file*

specifies the (optional) local additions (defaults to the respective location in `TEXMFLOCAL`).

-rebuild-sys

tells `tlmgr` to run necessary programs after config files have been regenerated. These are: `fmtutil-sys --all` after `generate fmtutil`, `fmtutil-sys --byhyphen .../language.dat` after `generate language.dat`, and `fmtutil-sys --byhyphen .../language.def` after `generate language.def`. These subsequent calls cause the newly-generated files to actually take effect. This is not done by default since those calls are lengthy processes and one might want to make several related changes in succession before invoking these programs.

The respective locations are as follows:

```
tex/generic/config/language.dat (and language-local.dat);
tex/generic/config/language.def (and language-local.def);
tex/generic/config/language.dat.lua (and language-local.dat.lua);
web2c/fmtutil.cnf (and fmtutil-local.cnf);
```

B.6.9 gui

Start the graphical user interface. See **GUI** below.

B.6.10 info [*option...*] [*collections|schemes|pkg...*]

With no argument, lists all packages available at the package repository, prefixing those already installed with `i`.

With the single word `collections` or `schemes` as the argument, lists the request type instead of all packages.

With any other arguments, display information about *pkg*: the name, category, short and long description, installation status, and TeX Live revision number. If *pkg* is not locally installed, searches in the remote installation source.

It also displays information taken from the TeX Catalogue, namely the package version, date, and license. Consider these, especially the package version, as approximations only, due to timing skew of the updates of the different pieces. By contrast, the `revision` value comes directly from TL and is reliable.

The former actions `show` and `list` are merged into this action, but are still supported for backward compatibility.

Options:

-list

If the option `--list` is given with a package, the list of contained files is also shown, including those for platform-specific dependencies. When given with schemes and collections, `--list` outputs their dependencies in a similar way.

-only-installed

If this options is given, the installation source will not be used; only locally installed packages, collections, or schemes are listed. (Does not work for listing of packages for now)

-taxonomy

-keyword

-functionality

-characterization

In addition to the normal data displayed, also display information for given packages from the corresponding taxonomy (or all of them). See Section B.9 [TAXONOMIES], page 56, below for details.

B.6.11 `init-usertree`

Sets up a texmf tree for so-called user mode management, either the default user tree (`TEXMFHOME`), or one specified on the command line with `--usertree`. See Section B.7 [USER MODE], page 55, below.

B.6.12 `install [option]... pkg...`

Install each *pkg* given on the command line. By default this installs all packages on which the given *pkgs* are dependent, also. Options:

-file

Instead of fetching a package from the installation repository, use the package files given on the command line. These files must be standard TeX Live package files (with contained `tlpobj` file).

-reinstall

Reinstall a package (including dependencies for collections) even if it already seems to be installed (i.e, is present in the TLPDB). This is useful to recover from accidental removal of files in the hierarchy.

When re-installing, only dependencies on normal packages are followed (i.e., not those of category Scheme or Collection).

-no-depends

Do not install dependencies. (By default, installing a package ensures that all dependencies of this package are fulfilled.)

-no-depends-at-all

Normally, when you install a package which ships binary files the respective binary package will also be installed. That is, for a package `foo`, the package `foo.i386-linux` will also be installed on an `i386-linux` system. This option suppresses this behavior, and also implies `--no-depends`. Don't use it unless you are sure of what you are doing.

-dry-run

Nothing is actually installed; instead, the actions to be performed are written to the terminal.

-force

If updates to `tlmgr` itself (or other parts of the basic infrastructure) are present, `tlmgr` will bail out and not perform the installation unless this option is given. Not recommended.

B.6.13 option

option [show]

option showall

option *key* [*value*]

The first form shows the global TeX Live settings currently saved in the TLPDB with a short description and the *key* used for changing it in parentheses.

The second form is similar, but also shows options which can be defined but are not currently set to any value.

In the third form, if *value* is not given, the setting for *key* is displayed. If *value* is present, *key* is set to *value*.

Possible values for *key* are (run `tlmgr option showall` for the definitive list):

```
repository (default package repository),
formats    (create formats at installation time),
postcode   (run postinst code blobs)
docfiles   (install documentation files),
srcfiles    (install source files),
backupdir  (default directory for backups),
autobackup (number of backups to keep).
sys_bin    (directory to which executables are linked by the path action)
sys_man    (directory to which man pages are linked by the path action)
sys_info   (directory to which Info files are linked by the path action)
desktop_integration (Windows-only: create Start menu shortcuts)
fileassocs (Windows-only: change file associations)
multiuser  (Windows-only: install for all users)
```

One common use of `option` is to permanently change the installation to get further updates from the Internet, after originally installing from DVD. To do this, you can run

```
tlmgr option repository http://mirror.ctan.org/systems/texlive/tlnet
```

The `install-tl` documentation has more information about the possible values for `repository`. (For backward compatibility, `location` can be used as alternative name for `repository`.)

If `formats` is set (this is the default), then formats are regenerated when either the engine or the format files have changed. Disable this only when you know what you are doing.

The `postcode` option controls execution of per-package postinstallation action code. It is set by default, and again disabling is not likely to be of interest except perhaps to developers.

The `docfiles` and `srcfiles` options control the installation of their respective files of a package. By default both are enabled (1). This can be disabled (set to 0) if disk space is (very) limited.

The options `autobackup` and `backupdir` determine the defaults for the actions `update`, `backup` and `restore`. These three actions need a directory in which to read or write the backups. If `--backupdir` is not specified on the command line, the `backupdir` option value is used (if set).

The `autobackup` option (de)activates automatic generation of backups. Its value is an integer. If the `autobackup` value is `-1`, no backups are removed. If `autobackup` is 0 or more, it specifies the number of backups to keep. Thus, backups are disabled if the value is 0. In the `--clean` mode of the `backup` action this option also specifies the number to be kept.

To setup `autobackup` to `-1` on the command line, use:

```
tlmgr option -- autobackup -1
```

The `--` avoids having the `-1` treated as an option. (`--` stops parsing for options at the point where it appears; this is a general feature across most Unix programs.)

The `sys_bin`, `sys_man`, and `sys_info` options are used on Unix-like systems to control the generation of links for executables, info files and man pages. See the `path` action for details.

The last three options control behaviour on Windows installations. If `desktop_integration` is set, then some packages will install items in a sub-folder of the Start menu for `tlmgr` gui, documentation, etc. If `fileassocs` is set, Windows file associations are made (see also the `postaction` action). Finally, if `multiuser` is set, then adaptations to the registry and the menus are done for all users on the system instead of only the current user. All three options are on by default.

B.6.14 paper

paper [`a4|letter`]

[`xdvi|pdftex|dvips|dvipdfmx|context|psutils`] **paper** [`papersize|--list`]

With no arguments (`tlmgr paper`), shows the default paper size setting for all known programs.

With one argument (e.g., `tlmgr paper a4`), sets the default for all known programs to that paper size.

With a program given as the first argument and no paper size specified (e.g., `tlmgr dvips paper`), shows the default paper size for that program.

With a program given as the first argument and a paper size as the last argument (e.g., `tlmgr dvips paper a4`), set the default for that program to that paper size.

With a program given as the first argument and `--list` given as the last argument (e.g., `tlmgr dvips paper --list`), shows all valid paper sizes for that program. The first size shown is the default.

Incidentally, this syntax of having a specific program name before the `paper` keyword is unusual. It is inherited from the longstanding `texconfig` script, which supports other configuration settings for some programs, notably `dvips`. `tlmgr` does not support those extra settings.

B.6.15 `path` [`-w32mode=user|admin`] [`add|remove`]

On Unix, merely adds or removes symlinks for binaries, man pages, and info pages in the system directories specified by the respective options (see the Section B.6.13 [option], page 46, description above). Does not change any initialization files, either system or personal.

On Windows, the registry part where the binary directory is added or removed is determined in the following way:

If the user has admin rights, and the option `--w32mode` is not given, the setting `w32_multi_user` determines the location (i.e., if it is on then the system path, otherwise the user path is changed).

If the user has admin rights, and the option `--w32mode` is given, this option determines the path to be adjusted.

If the user does not have admin rights, and the option `--w32mode` is not given, and the setting `w32_multi_user` is off, the user path is changed, while if the setting `w32_multi_user` is on, a warning is issued that the caller does not have enough privileges.

If the user does not have admin rights, and the option `--w32mode` is given, it must be `user` and the user path will be adjusted. If a user without admin rights uses the option `--w32mode admin` a warning is issued that the caller does not have enough privileges.

B.6.16 `pinning`

The `pinning` action manages the pinning file, see Section B.10.1 [Pinning], page 57, below.

`pinning show`

Shows the current pinning data.

`pinning add repo pkgglob...`

Pins the packages matching the *pkgglob*(s) to the repository *repo*.

`pinning remove repo pkgglob...`

Any packages recorded in the pinning file matching the <pkgglob>s for the given repository *repo* are removed.

`pinning remove repo --all`

Remove all pinning data for repository *repo*.

B.6.17 `platform list|add|remove platform...`

B.6.18 `platform set platform`

B.6.19 platform set auto

platform list lists the TeX Live names of all the platforms (a.k.a. architectures), (i386-linux, ...) available at the package repository.

platform add platform... adds the executables for each given platform *platform* to the installation from the repository.

platform remove platform... removes the executables for each given platform *platform* from the installation, but keeps the currently running platform in any case.

platform set platform switches TeX Live to always use the given platform instead of auto detection.

platform set auto switches TeX Live to auto detection mode for platform.

Platform detection is needed to select the proper **xz**, **xzdec** and **wget** binaries that are shipped with TeX Live.

arch is a synonym for **platform**.

Options:

-dry-run

Nothing is actually installed; instead, the actions to be performed are written to the terminal.

B.6.20 postaction [-w32mode=user|admin] [-fileassocmode=1|2] [-all] [install|remove] [shortcut|fileassoc|script] [pkg]...

Carry out the postaction **shortcut**, **fileassoc**, or **script** given as the second required argument in install or remove mode (which is the first required argument), for either the packages given on the command line, or for all if **--all** is given.

If the option **--w32mode** is given the value **user**, all actions will only be carried out in the user-accessible parts of the registry/filesystem, while the value **admin** selects the system-wide parts of the registry for the file associations. If you do not have enough permissions, using **--w32mode=admin** will not succeed.

--fileassocmode specifies the action for file associations. If it is set to 1 (the default), only new associations are added; if it is set to 2, all associations are set to the TeX Live programs. (See also option **fileassocs**.)

B.6.21 print-platform

Print the TeX Live identifier for the detected platform (hardware/operating system) combination to standard output, and exit. **--print-arch** is a synonym.

B.6.22 restore [-backupdir dir] [-all | pkg [rev]]

Restore a package from a previously-made backup.

If **--all** is given, try to restore the latest revision of all package backups found in the backup directory.

Otherwise, if neither *pkg* nor *rev* are given, list the available backup revisions for all packages.

With *pkg* given but no *rev*, list all available backup revisions of *pkg*.

When listing available packages tlmgr shows the revision and in parenthesis the creation time if available (in format yyyy-mm-dd hh:mm).

With both *pkg* and *rev*, tries to restore the package from the specified backup.

Options:

-all

Try to restore the latest revision of all package backups found in the backup directory. Additional non-option arguments (like *pkg*) are not allowed.

-backupdir *directory*

Specify the directory where the backups are to be found. If not given it will be taken from the configuration setting in the TLPDB.

-dry-run

Nothing is actually restored; instead, the actions to be performed are written to the terminal.

-force

Don't ask questions.

B.6.23 remove [*option*]... *pkg*...

Remove each *pkg* specified. Removing a collection removes all package dependencies (unless **--no-depends** is specified), but not any collection dependencies of that collection. However, when removing a package, dependencies are never removed. Options:

-no-depends

Do not remove dependent packages.

-no-depends-at-all

See above under **install** (and beware).

-force

By default, removal of a package or collection that is a dependency of another collection or scheme is not allowed. With this option, the package will be removed unconditionally. Use with care.

A package that has been removed using the **--force** option because it is still listed in an installed collection or scheme will not be updated, and will be mentioned as **forcibly removed** in the output of **tlmgr update -list**.

-dry-run

Nothing is actually removed; instead, the actions to be performed are written to the terminal.

B.6.24 repository

repository list

repository list *path*|*tag*

repository add *path* [*tag*]

repository remove *path*|*tag*

repository set *path*[*#tag*] [*path*[*#tag*] ...]

This action manages the list of repositories. See Section B.10 [MULTIPLE REPOSITORIES], page 57, below for detailed explanations.

The first form (**list**) lists all configured repositories and the respective tags if set. If a path, url, or tag is given after the **list** keyword, it is interpreted as source from where to initialize a TeX Live Database and lists the contained packages. This can also be an up-to-now not used repository, both locally and remote. If one pass in addition **--with-platforms**, for each package the available platforms (if any) are listed, too.

The third form (**add**) adds a repository (optionally attaching a tag) to the list of repositories. The forth form (**remove**) removes a repository, either by full path/url, or by tag. The last form (**set**) sets the list of repositories to the items given on the command line, not keeping previous settings

In all cases, one of the repositories must be tagged as **main**; otherwise, all operations will fail!

B.6.25 search [*option...*] *what*

B.6.25.1 search [*option...*] **--file** *what*

B.6.25.2 search [*option...*] **--taxonomy** *what*

B.6.25.3 search [*option...*] **--keyword** *what*

B.6.25.4 search [*option...*] **--functionality** *what*

B.6.25.5 search [*option...*] **--characterization** *what*

B.6.25.6 search [*option...*] **--all** *what*

By default, search the names, short descriptions, and long descriptions of all locally installed packages for the argument *what*, interpreted as a regular expression.

Options:

--global

Search the TeX Live Database of the installation medium, instead of the local installation.

--word

Restrict the search to match only full words. For example, searching for **table** with this option will not output packages containing the word **tables** (unless they also contain the word **table** on its own).

--list

If a search for any (or all) taxonomies is done, by specifying one of the taxonomy options below, then instead of searching for packages, list the entire corresponding taxonomy (or all of them). See Section B.9 [TAXONOMIES], page 56, below.

Other search options are selected by specifying one of the following:

--file

List all filenames containing *what*.

-taxonomy

-keyword

-functionality

-characterization

Search in the corresponding taxonomy (or all) instead of the package descriptions. See Section B.9 [TAXONOMIES], page 56, below.

-all

Search for package names, descriptions, and taxonomies, but not files.

B.6.26 uninstall

Uninstalls the entire TeX Live installation. Options:

-force

Do not ask for confirmation, remove immediately.

B.6.27 update [*option*]... [*pkg*]...

Updates the packages given as arguments to the latest version available at the installation source. Either **--all** or at least one *pkg* name must be specified. Options:

-all

Update all installed packages except for **tlmgr** itself. Thus, if updates to **tlmgr** itself are present, this will simply give an error, unless also the option **--force** or **--self** is given. (See below.)

In addition to updating the installed packages, during the update of a collection the local installation is (by default) synchronized to the status of the collection on the server, for both additions and removals.

This means that if a package has been removed on the server (and thus has also been removed from the respective collection), **tlmgr** will remove the package in the local installation. This is called “auto-remove” and is announced as such when using the option **--list**. This auto-removal can be suppressed using the option **--no-auto-remove** (not recommended, see option description).

Analogously, if a package has been added to a collection on the server that is also installed locally, it will be added to the local installation. This is called “auto-install” and is announced as such when using the option **--list**. This auto-installation can be suppressed using the option **--no-auto-install**.

An exception to the collection dependency checks (including the auto-installation of packages just mentioned) are those that have been “forcibly removed” by you, that is, you called **tlmgr remove --force** on them. (See the **remove** action documentation.) To reinstall any such forcibly removed packages use **--reinstall-forcibly-removed**.

If you want to exclude some packages from the current update run (e.g., due to a slow link), see the **--exclude** option below.

-self

Update **tlmgr** itself (that is, the infrastructure packages) if updates to it are present. On Windows this includes updates to the private Perl interpreter shipped inside TeX Live.

If this option is given together with either **--all** or a list of packages, then **tlmgr** will be updated first and, if this update succeeds, the new version will be restarted to complete the rest of the updates.

In short:

```
tlmgr update --self          # update infrastructure only
tlmgr update --self --all    # update infrastructure and all packages
tlmgr update --force --all   # update all packages but *not* infrastructure
                             # ... this last at your own risk, not recommended!
```

-dry-run

Nothing is actually installed; instead, the actions to be performed are written to the terminal. This is a more detailed report than **--list**.

-list [*pkg*]

Concisely list the packages which would be updated, newly installed, or removed, without actually changing anything. If **--all** is also given, all available updates are listed. If **--self** is given, but not **--all**, only updates to the critical packages (**tlmgr**, texlive infrastructure, perl on Windows, etc.) are listed. If neither **--all** nor **--self** is given, and in addition no *pkg* is given, then **--all** is assumed (thus, **tlmgr update --list** is the same as **tlmgr update --list --all**). If neither **--all** nor **--self** is given, but specific package names are given, those packages are checked for updates.

-exclude *pkg*

Exclude *pkg* from the update process. If this option is given more than once, its arguments accumulate.

An argument *pkg* excludes both the package *pkg* itself and all its related platform-specific packages *pkg.ARCH*. For example,

```
tlmgr update --all --exclude a2ping
```

will not update **a2ping**, **a2ping.i386-linux**, or any other **a2ping.ARCH** package.

If this option specifies a package that would otherwise be a candidate for auto-installation, auto-removal, or reinstallation of a forcibly removed package, **tlmgr** quits with an error message. Excludes are not supported in these circumstances.

-no-auto-remove [*pkg*]...

By default, **tlmgr** tries to remove packages which have disappeared on the server, as described above under **--all**. This option prevents such removals, either for all packages (with **--all**), or for just the given *pkg* names. This can lead to an inconsistent TeX installation, since packages are not infrequently renamed or replaced by their authors. Therefore this is not recommended.

-no-auto-install [*pkg*]...

Under normal circumstances **tlmgr** will install packages which are new on the server, as described above under **--all**. This option prevents any such automatic installation, either for all packages (with **--all**), or the given *pkg* names. Furthermore, after the **tlmgr** run using this has finished, the packages that would have been auto-installed *will be considered as forcibly removed*. So, if **foobar** is the only new package on the server, then

```
tlmgr update --all --no-auto-install
```

is equivalent to

```
tlmgr update --all
tlmgr remove --force foobar
```

-reinstall-forcibly-removed

Under normal circumstances **tlmgr** will not install packages that have been forcibly removed by the user; that is, removed with **remove --force**, or whose installation was prohibited by **--no-auto-install** during an earlier update.

This option makes **tlmgr** ignore the forcible removals and re-install all such packages. This can be used to completely synchronize an installation with the server's idea of what is available:

```
tlmgr update --reinstall-forcibly-removed --all
```

-backup and **-backupdir** *directory*

These two options control the creation of backups of packages *before* updating; that is, backup of packages as currently installed. If neither of these options are given, no backup package will be saved. If **--backupdir** is given and specifies a writable directory then a backup will be made in that location. If only **--backup** is given, then a backup will be made to the directory previously set via the **option** action (see below). If both are given then a backup will be made to the specified *directory*.

You can set options via the **option** action to automatically create backups for all packages, and/or keep only a certain number of backups. Please see the **option** action for details.

tlmgr always makes a temporary backup when updating packages, in case of download or other failure during an update. In contrast, the purpose of this **--backup** option is to allow you to save a persistent backup in case the actual *content* of the update causes problems, e.g., introduces an incompatibility.

The **restore** action explains how to restore from a backup.

-no-depends

If you call for updating a package normally all depending packages will also be checked for updates and updated if necessary. This switch suppresses this behavior.

-no-depends-at-all

See above under **install** (and beware).

-force

Force update of normal packages, without updating `tlmgr` itself (unless the `--self` option is also given). Not recommended.

Also, `update --list` is still performed regardless of this option.

If the package on the server is older than the package already installed (e.g., if the selected mirror is out of date), `tlmgr` does not downgrade. Also, packages for uninstalled platforms are not installed.

B.7 USER MODE

`tlmgr` provides a restricted way, called “user mode”, to manage arbitrary texmf trees in the same way as the main installation. For example, this allows people without write permissions on the installation location to update/install packages into a tree of their own.

`tlmgr` is switched into user mode with the command line option `--usermode`. It does not switch automatically, nor is there any configuration file setting for it. Thus, this option has to be explicitly given every time user mode is to be activated.

This mode of `tlmgr` works on a user tree, by default the value of the `TEXMFHOME` variable. This can be overridden with the command line option `--usertree`. In the following when we speak of the user tree we mean either `TEXMFHOME` or the one given on the command line.

Not all actions are allowed in user mode; `tlmgr` will warn you and not carry out any problematic actions. Currently not supported (and probably will never be) is the `platform` action. The `gui` action is currently not supported, but may be in a future release.

Some `tlmgr` actions don’t need any write permissions and thus work the same in user mode and normal mode. Currently these are: `check`, `help`, `list`, `print-platform`, `search`, `show`, `version`.

On the other hand, most of the actions dealing with package management do need write permissions, and thus behave differently in user mode, as described below: `install`, `update`, `remove`, `option`, `paper`, `generate`, `backup`, `restore`, `uninstall`, `symlinks`.

Before using `tlmgr` in user mode, you have to set up the user tree with the `init-usertree` action. This creates `usertree/web2c` and `usertree/tlpkg/tlpobj`, and a minimal `usertree/tlpkg/texlive.tlpdb`. At that point, you can tell `tlmgr` to do the (supported) actions by adding the `--usermode` command line option.

In user mode the file `usertree/tlpkg/texlive.tlpdb` contains only the packages that have been installed into the user tree using `tlmgr`, plus additional options from the “virtual” package `00texlive.installation` (similar to the main installation’s `texlive.tlpdb`).

All actions on packages in user mode can only be carried out on packages that are known as `relocatable`. This excludes all packages containing executables and a few other core packages. Of the 2500 or so packages currently in TeX Live the vast majority are relocatable and can be installed into a user tree.

Description of changes of actions in user mode:

B.7.1 user mode install

In user mode, the `install` action checks that the package and all dependencies are all either relocated or already installed in the system installation. If this is the case, it unpacks all containers to be installed into the user tree (to repeat, that’s either `TEXMFHOME` or the value

of `--usertree`) and add the respective packages to the user tree's `texlive.tlpdb` (creating it if need be).

Currently installing a collection in user mode installs all dependent packages, but in contrast to normal mode, does *not* install dependent collections. For example, in normal mode `tlmgr install collection-context` would install `collection-basic` and other collections, while in user mode, *only* the packages mentioned in `collection-context` are installed.

B.7.2 user mode backup; restore; remove; update

In user mode, these actions check that all packages to be acted on are installed in the user tree before proceeding; otherwise, they behave just as in normal mode.

B.7.3 user mode generate; option; paper

In user mode, these actions operate only on the user tree's configuration files and/or `texlive.tlpdb`. `generate` creates configuration files in user tree

B.8 CONFIGURATION FILE FOR TLMGR

A small subset of the command line options can be set in a config file for `tlmgr` which resides in `TEXMFCONFIG/tlmgr/config`. By default, the config file is in `~/.texliveYYYY/texmf-config/tlmgr/config` (replacing `YYYY` with the year of your TeX Live installation). This is *not* `TEXMFSYSVAR`, so that the file is specific to a single user.

In this file, empty lines and lines starting with `#` are ignored. All other lines must look like

```
key = value
```

where the allowed keys are `gui-expertmode` (value 0 or 1), `persistent-downloads` (value 0 or 1), `auto-remove` (value 0 or 1), and `gui-lang` (value like in the command line option).

`persistent-downloads`, `gui-lang`, and `auto-remove` correspond to the respective command line options of the same name. `gui-expertmode` switches between the full GUI and a simplified GUI with only the important and mostly used settings.

B.9 TAXONOMIES

`tlmgr` allows searching and listing of various categorizations, which we call *taxonomies*, as provided by an enhanced TeX Catalogue (available for testing at <http://az.ctan.org>). This is useful when, for example, you don't know a specific package name but have an idea of the functionality you need; or when you want to see all packages relating to a given area.

There are three different taxonomies, specified by the following options:

`--keyword`

The keywords, as specified at <http://az.ctan.org/keyword>.

`--functionality`

The “by-topic” categorization created by Jürgen Fenn, as specified at <http://az.ctan.org/characterization/by-function>.

--characterization

Both the primary and secondary functionalities, as specified at http://az.ctan.org/characterization/choose_dimen.

--taxonomy

Operate on all the taxonomies.

The taxonomies are updated nightly and stored within TeX Live, so Internet access is not required to search them.

Examples:

```
tlmgr search --taxonomy exercise      # check all taxonomies for "exercise"
tlmgr search --taxonomy --word table  # check for "table" on its own
tlmgr search --list --keyword         # dump entire keyword taxonomy
tlmgr show --taxonomy pdftex          # show pdftex package information,
                                     # including all taxonomy entries
```

B.10 MULTIPLE REPOSITORIES

The main TeX Live repository contains a vast array of packages. Nevertheless, additional local repositories can be useful to provide locally-installed resources, such as proprietary fonts and house styles. Also, alternative package repositories distribute packages that cannot or should not be included in TeX Live, for whatever reason.

The simplest and most reliable method is to temporarily set the installation source to any repository (with the `-repository` or `option repository` command line options), and perform your operations.

When you are using multiple repositories over a sustained time, however, explicitly switching between them becomes inconvenient. Thus, it's possible to tell `tlmgr` about additional repositories you want to use. The basic command is `tlmgr repository add`. The rest of this section explains further.

When using multiple repositories, one of them has to be set as the main repository, which distributes most of the installed packages. When you switch from a single repository installation to a multiple repository installation, the previous sole repository will be set as the main repository.

By default, even if multiple repositories are configured, packages are *still only* installed from the main repository. Thus, simply adding a second repository does not actually enable installation of anything from there. You also have to specify which packages should be taken from the new repository, by specifying so-called “pinning” rules, described next.

B.10.1 Pinning

When a package `foo` is pinned to a repository, a package `foo` in any other repository, even if it has a higher revision number, will not be considered an installable candidate.

As mentioned above, by default everything is pinned to the main repository. Let's now go through an example of setting up a second repository and enabling updates of a package from it.

First, check that we have support for multiple repositories, and have only one enabled (as is the case by default):

```
$ tlmgr repository list
```


List of repositories (with tags if set):
 /var/www/norbert/tlnet

Ok. Let's add the tlcontrib repository (this is a real repository, hosted at <http://tlcontrib.metatex.org>, maintained by Taco Hoekwater et al.), with the tag tlcontrib:

```
$ tlmgr repository add http://tlcontrib.metatex.org/2012 tlcontrib
```

Check the repository list again:

```
$ tlmgr repository list
```

List of repositories (with tags if set):

```
http://tlcontrib.metatex.org/2012 (tlcontrib)
/var/www/norbert/tlnet (main)
```

Now we specify a pinning entry to get the package context from tlcontrib:

```
$ tlmgr pinning add tlcontrib context
```

Check that we can find context:

```
$ tlmgr show context
```

```
tlmgr: package repositories:
```

```
...
```

```
package:      context
```

```
repository:   tlcontrib/26867
```

```
...
```

```
- install context:
```

```
$ tlmgr install context
```

```
tlmgr: package repositories:
```

```
...
```

```
[1/1,  ??:??/?:??] install: context @tlcontrib [
```

In the output here you can see that the context package has been installed from the tlcontrib repository (@tlcontrib).

Finally, tlmgr pinning also supports removing certain or all packages from a given repository:

```
$ tlmgr pinning remove tlcontrib context # remove just context
```

```
$ tlmgr pinning remove tlcontrib --all   # take nothing from tlcontrib
```

A summary of the tlmgr pinning actions is given above.

B.11 GUI FOR TLMGR

The graphical user interface for tlmgr needs Perl/Tk to be installed. For Windows the necessary modules are shipped within TeX Live, for all other (i.e., Unix-based) systems Perl/Tk (as well as Perl of course) has to be installed. <http://tug.org/texlive/distro.html#perlTk> has a list of invocations for some distros.

When started with `tlmgr gui` the graphical user interface will be shown. The main window contains a menu bar, the main display, and a status area where messages normally shown on the console are displayed.

Within the main display there are three main parts: the Display configuration area, the list of packages, and the action buttons.

Also, at the top right the currently loaded repository is shown; this also acts as a button and when clicked will try to load the default repository. To load a different repository, see the `tlmgr` menu item.

Finally, the status area at the bottom of the window gives additional information about what is going on.

B.11.1 Main display

B.11.1.1 Display configuration area

The first part of the main display allows you to specify (filter) which packages are shown. By default, all are shown. Changes here are reflected right away.

Status

Select whether to show all packages (the default), only those installed, only those *not* installed, or only those with update available.

Category

Select which categories are shown: packages, collections, and/or schemes. These are briefly explained in the Section B.3 [DESCRIPTION], page 38, section above.

Match

Select packages matching for a specific pattern. By default, this uses the same algorithm as `tlmgr search`, i.e., searches everything: descriptions, taxonomies, and/or filenames. You can also select any subset for searching.

Selection

Select packages to those selected, those not selected, or all. Here, “selected” means that the checkbox in the beginning of the line of a package is ticked.

Display configuration buttons

To the right there are three buttons: select all packages, select none (a.k.a. deselect all), and reset all these filters to the defaults, i.e., show all available.

B.11.1.2 Package list area

The second area of the main display lists all installed packages. If a repository is loaded, those that are available but not installed are also listed.

Double clicking on a package line pops up an informational window with further details: the long description, included files, etc.

Each line of the package list consists of the following items:

a checkbox

Used to select particular packages; some of the action buttons (see below) work only on the selected packages.

package name

The name (identifier) of the package as given in the database.

local revision (and version)

If the package is installed the TeX Live revision number for the installed package will be shown. If there is a catalogue version given in the database for this package, it will be shown in parentheses. However, the catalogue version, unlike the TL revision, is not guaranteed to reflect what is actually installed.

remote revision (and version)

If a repository has been loaded the revision of the package in the repository (if present) is shown. As with the local column, if a catalogue version is provided it will be displayed. And also as with the local column, the catalogue version may be stale.

short description

The short description of the package.

B.11.1.3 Main display action buttons

Below the list of packages are several buttons:

Update all installed

This calls `tlmgr update --all`, i.e., tries to update all available packages. Below this button is a toggle to allow reinstallation of previously removed packages as part of this action.

The other four buttons only work on the selected packages, i.e., those where the checkbox at the beginning of the package line is ticked.

Update

Update only the selected packages.

Install

Install the selected packages; acts like `tlmgr install`, i.e., also installs dependencies. Thus, installing a collection installs all its constituent packages.

Remove

Removes the selected packages; acts like `tlmgr remove`, i.e., it will also remove dependencies of collections (but not dependencies of normal packages).

Backup

Makes a backup of the selected packages; acts like `tlmgr backup`. This action needs the option `backupdir` set (see `Options - General`).

B.11.2 Menu bar

The following entries can be found in the menu bar:

tlmgr menu

The items here load various repositories: the default as specified in the TeX Live database, the default network repository, the repository specified on the command line (if any), and an arbitrarily manually-entered one. Also has the so-necessary `quit` operation.

Options menu

Provides access to several groups of options: **Paper** (configuration of default paper sizes), **Platforms** (only on Unix, configuration of the supported/installed platforms), **GUI Language** (select language used in the GUI interface), and **General** (everything else).

Several toggles are also here. The first is **Expert options**, which is set by default. If you turn this off, the next time you start the GUI a simplified screen will be shown that display only the most important functionality. This setting is saved in the configuration file of **tlmgr**; see Section B.8 [CONFIGURATION FILE FOR TLMGR], page 56, for details.

The other toggles are all off by default: for debugging output, to disable the automatic installation of new packages, and to disable the automatic removal of packages deleted from the server. Playing with the choices of what is or isn't installed may lead to an inconsistent TeX Live installation; e.g., when a package is renamed.

Actions menu

Provides access to several actions: update the filename database (aka **ls-R**, **mktextlsr**, **texhash**), rebuild all formats (**fmtutil-sys --all**), update the font map database (**updmap-sys**), restore from a backup of a package, and use of symbolic links in system directories (not on Windows).

The final action is to remove the entire TeX Live installation (also not on Windows).

Help menu

Provides access to the TeX Live manual (also on the web at <http://tug.org/texlive/doc.html>) and the usual “About” box.

B.12 MACHINE-READABLE OUTPUT

With the **--machine-readable** option, **tlmgr** writes to stdout in the fixed line-oriented format described here, and the usual informational messages for human consumption are written to stderr (normally they are written to stdout). The idea is that a program can get all the information it needs by reading stdout.

Currently this option only applies to the Section B.6.27 [update], page 52, Section B.6.12 [install], page 45, and Section B.6.13 [option], page 46, actions.

B.12.1 Machine-readable update and install output

The output format is as follows:

```
fieldname "\t" value
...
"end-of-header"
pkgname status localrev serverrev size runtime esttot
...
"end-of-updates"
other output from post actions, not in machine readable form
```

The header section currently has two fields: **location-url** (the repository source from which updates are being drawn), and **total-bytes** (the total number of bytes to be downloaded).

The *localrev* and *serverrev* fields for each package are the revision numbers in the local installation and server repository, respectively. The *size* field is the number of bytes to be downloaded, i.e., the size of the compressed tar file for a network installation, not the unpacked size. The *runtime* and *esttot* fields are only present for updated and auto-install packages, and contain the currently passed time since start of installation/updates and the estimated total time.

Line endings may be either LF or CRLF depending on the current platform.

location-url *location*

The *location* may be a url (including **file:///foo/bar/...**), or a directory name (**/foo/bar**). It is the package repository from which the new package information was drawn.

total-bytes *count*

The *count* is simply a decimal number, the sum of the sizes of all the packages that need updating or installing (which are listed subsequently).

Then comes a line with only the literal string **end-of-header**.

Each following line until a line with literal string **end-of-updates** reports on one package. The fields on each line are separated by a tab. Here are the fields.

pkgname

The TeX Live package identifier, with a possible platform suffix for executables. For instance, **pdftex** and **pdftex.i386-linux** are given as two separate packages, one on each line.

status

The status of the package update. One character, as follows:

d

The package was removed on the server.

f

The package was removed in the local installation, even though a collection depended on it. (E.g., the user ran **tlmgr remove --force**.)

u

Normal update is needed.

r

Reversed non-update: the locally-installed version is newer than the version on the server.

a

Automatically-determined need for installation, the package is new on the server and is (most probably) part of an installed collection.

i Package will be installed and isn't present in the local installation (action install).

I Package is already present but will be reinstalled (action install).

localrev The revision number of the installed package, or - if it is not present locally.

serverrev The revision number of the package on the server, or - if it is not present on the server.

size The size in bytes of the package on the server. The sum of all the package sizes is given in the **total-bytes** header field mentioned above.

runtime The run time since start of installations or updates.

esttot The estimated total time.

B.12.2 Machine-readable option output

The output format is as follows:

key "\t" value

If a value is not saved in the database the string (**not set**) is shown.

If you are developing a program that uses this output, and find that changes would be helpful, do not hesitate to write the mailing list.

B.13 AUTHORS AND COPYRIGHT

This script and its documentation were written for the TeX Live distribution (<http://tug.org/texlive>) and both are licensed under the GNU General Public License Version 2 or later.

Index

—	
--bindir configure option	20, 21
--build=host	27
--disable-all-packages	5
--disable-all-pkgs	22
--disable-bibtex8	23
--disable-bibtexu	23
--disable-dump-share	22
--disable-dvipdfmx	23
--disable-etex-synctex	23
--disable-ipc	22
--disable-largefile	20
--disable-linked-scripts	24
--disable-mf-nowin	22
--disable-missing	21
--disable-native-texlive-build	20
--disable-prog	22
--disable-synctex	23
--disable-tex	22
--disable-web-progs	23
--disable-xdvipdfmx	23
--enable-*win for Metafont window support	23
--enable-auto-core	23
--enable-compiler-warnings=level	21
--enable-cxx-runtime-hack	12
--enable-etex	22
--enable-libtool-hack	23
--enable-maintainer-mode	10, 21
--enable-missing to ignore dependencies	6
--enable-mktextfm-default	15
--enable-multiplatform	21
--enable-prog	22
--enable-shared	21
--enable-silent-rules	21
--enable-tex-synctex	23
--enable-texlive-build	20
--enable-xi2-scrolling	24
--enable-xindy-docs	24
--enable-xindy-rules	24
--host=host	27
--libdir configure option	21
--no-clean Build option	4
--prefix configure option	20
--with-banner-add=str	22
--with-clisp-runtime=filename	24
--with-editor=cmd	22
--with-fontconfig-includes=dir	22
--with-fontconfig-libdir=dir	22
--with-gs=filename	24
--with-lib-includes=dir, -libdir	24
--with-libgs-includes, -libdir	24
--with-system-kpathsea	15
--with-system-lib	18, 24
--with-system-libgs	23
--with-system-poppler	25
--with-system-xpdf	25
--with-xdvi-x-toolkit	16
--with-xdvi-x-toolkit=kit	24
--without-libgs	23
--without-ln-s	21
--without-x	22
-C configure option	4
-j make option	4
•	
.travis.yml	31
A	
adapting T _E X Live for distros	9
adding a new generic library	18
adding a new program	17
adding a new T _E X-specific library	19
adding to T _E X Live	17
am/ top-level directory	10
ANSI C	29
ApplicationServices Mac framework, required by xetex	3
asymptote	8, 16
Autoconf	2
autoconf macros	11
Automake	2
B	
biber	8
bibtex-x	23
bibtex8	23
bibtexu	23
BSD distro	8
build directory, required	4
build iteration	4
build on demand	5
build one package	5
build problems	4
Build script	4
build system, design of	2
build-aux/ top-level directory	11
BUILDCC, BUILDCLFLAGS	27
building	4
building a distribution	4
building in parallel	4

C

C++11, required by <code>dvisvgm</code>	3
C, ANSI, required	29
C99, avoided	29
cache file, for <code>configure</code>	4
cache for <code>configure</code>	4
<code>callexe.c</code>	14
<code>CC</code>	25
<code>CC=c-compiler</code>	6
<code>CC_BUILD</code>	28
<code>chktex</code>	29
<code>ci</code>	31
<code>clisp</code>	25
<code>clisp</code> , required by <code>xindy</code>	3
<code>CLISP</code>	24, 25
Cocoa Mac framework, required by <code>xetex</code>	3
coding conventions	29
compilers, C and C++	3
<code>config.guess</code> , <code>config.sub</code> ,	11
<code>configure</code> options	20
<code>configure</code> options, for <code>bibtex-x</code>	23
<code>configure</code> options, for <code>dvipdfm-x</code>	23
<code>configure</code> options, for <code>dvisvgm</code>	23
<code>configure</code> options, for <code>kpathsea</code>	25
<code>configure</code> options, for system <code>poppler</code>	25
<code>configure</code> options, for <code>texk/texlive</code>	24
<code>configure</code> options, for <code>web2c</code>	22
<code>configure</code> options, for <code>xdvik</code>	24
<code>configure</code> options, for <code>xindy</code>	24
<code>configure</code> options, global	20
<code>configure</code> options, library-specific	24
<code>configure</code> options, program-specific	22
<code>configure</code> variables	25
configuring, for cross compilation	27
<code>const</code>	30
continuous integration	31
conventions, coding	29
<code>CPPFLAGS</code>	25
cross compilation	27
cross compilation configuring	27
cross compilation problems	28
cross compilation, with host binary	16
<code>ctangle</code>	28
<code>CXX</code>	25
<code>CXX=c++-compiler</code>	6

D

Debian installation of build prerequisites	3
declarations and definitions, in source code	29
dependencies, with several output files	4
<code>DESTDIR</code>	20
directories, for installation	7
directories, top-level	10
discards qualifiers warning	30
<code>dist</code> and <code>distcheck</code> targets for <code>make</code>	4
distribution tarball, making	4
distro, building for	8

<code>dvipdfmx</code>	23
<code>dvisvgm</code>	23
<code>dvisvgm</code> requirement for C++11	3

E

environment variables, for <code>configure</code>	20
<code>exec_prefix</code>	21
extending T _E X Live	17
<code>extern</code> functions	29
<code>extra/</code> top-level directory	11

F

failure to build	4
<code>ffcall</code> , required by <code>xindy</code>	3
flags, macros for library and header	13
<code>fontconfig</code> library, required by <code>xetex</code>	3
FreeType	3
<code>freetype</code> cross compiling	28
<code>freetype</code> library	15
<code>freetype-config</code>	15, 25
<code>FT2_CONFIG</code>	25

G

general setup macros	11
generic library module, adding	18
global <code>configure</code> options	20
<code>gmake</code> , required	3
GNU <code>make</code> , required	3
GNU tools, needed for building	10
GNU/Linux distro	8
Gnulib, used for common files	11

I

<code>icu-config</code>	25
ICU cross compiling	28
ICU libraries	25
<code>ICU_CONFIG</code>	25
infrastructure, tools needed for	10
<code>inst/</code> top-level directory	11
<code>install-tl</code> , T _E X Live installer	7
installation directories	7
installing	7
interprocess communication	22
introduction	1
iteration through sources, by <code>configure</code> and <code>make</code>	4

K

kpathsea library	15
kpathsea.ac	15
kpse-libpng-flags.m4	15
kpse-pkgs.m4	2
kpse-zlib-flags.m4	15
kpse_cv_cxx_hack	12
kpse_cv_have_win32	13
kpse_cv_visibility_c[xx]flags	12
kpse_cv_warning_cflags	12
kpse_libs_pkgs	18
kpse_textk_pkgs	17
kpse_texlibs_pkgs	19
kpse_utils_pkgs	17
KPSE_ADD_FLAGS	13
KPSE_ALL_SYSTEM_FLAGS	18
KPSE_BASIC	11
KPSE_CHECK_LATEX	12
KPSE_CHECK_PDFLATEX	12
KPSE_CHECK_PERL	12
KPSE_CHECK_WIN32	13
KPSE_COMMON	11
KPSE_COMPILER_VISIBILITY	12
KPSE_COMPILER_WARNINGS	12
KPSE_COND_MINGW32	14
KPSE_COND_WIN32	14
KPSE_COND_WIN32_WRAP	14
KPSE_CXX_HACK	12
KPSE_ENABLE_PROG	17
KPSE_LARGEFILE	12
KPSE_LIB_FLAGS	13, 18
KPSE_LIB_SYSTEM_FLAGS	18
KPSE_LIBPNG_FLAGS	13, 15
KPSE_PROG_LEX	12
KPSE_RESTORE_FLAGS	13
KPSE_TRY_LIB	14, 18
KPSE_TRY_LIBXX	14, 18
KPSE_WIN32_CALL	14
KPSE_WITH_LIB	18
KPSE_WITH_TEXLIB	19
kpsewhich	26
KPSEWHICH	26

L

large file support	20
LATEX	26
layout of sources	10
LFS (large file support)	20
libfreetype	25
libfreetype, and const	30
libpng library	14
library module, generic, adding	18
library module, T _E X-specific, adding	19
library modules	14
library-specific configure options	24
libstc++, statically linking	12
Libtool	2

libtool, hack for avoiding excessive linking	23
libXt	22
linked scripts	7
linking C++ libraries statically	12
lisp.run, lisp.exe	24
LittleEndian architectures	22

M

m4/ top-level directory	10
macros, for compilers	12
macros, for libraries	12
macros, for library and header flags	13
macros, for programs	12
macros, for Windows	13
macros, general setup	11
make -t	10
MAKE	26
mf-nowin	22
mingw32	27
MINGW32, Automake conditional	14
mktx.ac	15
mktextfm	15
modules, for libraries	14
modules, for programs	16
motif	24

N

native cross compilation	27
--------------------------	----

O

OBJCXX=objc-compiler	6
one package, building	5
OpenGL, required for Asymptote	16
operating system distribution, building for	8
otangle	28
overall build process	4

P

parallel build	4
paths, for installation	7
PDF files, size of	20
PDFLATEX	26
perl, required by web2c, etc.	3
PERL	26
PKG_CONFIG	25
plain.tex, not in source tree	7
png library	14
poppler	25
PostScript files, size of	20
Preining, Norbert	9
preloaded binaries	23
prerequisites for building	3
problems with build	4
program module, adding	17

program modules 16
 program-specific **configure** options 22

R

reautoconf 10
 requirements for building 3
runscript.exe 14

S

scripts, linked and not maintained 7
scrolling 24
SED 26
 setup macros, general 11
 shared libraries, using vs. avoiding 8
 size of PDF and PS files 20
 size of source tree 5
 source code declarations 29
 source directory building, not supported 4
 source tree 10
squeeze 28
squeeze/configure.ac 16
 static functions 29
 static linking for C++ 12
stpcpy 29
 Subversion repository 10
 support files, separate from build 7
 symlinks, used for scripts 7
 syntex 23
 system distribution, building for 8

T

tlutils package 16
tangle 28
 tests, running 2
 T_EX-specific library module, adding 19
texlive.tlpdb, T_EX Live database 7
tie 28
 timestamps, in repository 10
 tools, for building 10
 top-level directories 10
 touching files to avoid rerunning 10
 Travis-CI 31
 type cast, avoiding 30

U

use-commit-times, Subversion 10

V

variable declarations, in source code 29
 variables for **configure** 25

W

warning, discards qualifiers 30
WARNING_C[XX]FLAGS 12
web2c program 28
web2c.ac 22
wget 8
WIN32, Automake conditional 14
WIN32_WRAP, Automake conditional 14
 Windows, invoking scripts on 7
 Windows, macros for 13
withenable.ac, for new modules 17
 Work/ top-level directory 11
 wrapper binary for scripts on Windows 7

X

X toolkit 22
 X11 headers, and **const** 30
 X11, required by X clients 3
xasy 16
xaw 24
xdvik 16, 24
xdvipdfmx 23
xindy 8, 16, 24
 xindy cross compiling impossible 28
XInput 24
Xlib 22
 xpdf as library 25
xz 8

Z

zlib library 15