

The `mathspec` package

version 0.16

Andrew Gilbert Moschou
`andmos@gmail.com`

SATURDAY, 29 AUGUST 2009

TABLE OF CONTENTS

1	PREAMBLE	1	6	ADDITIONAL INFORMATION	6
2	INTRODUCTION	1	6.1	Glyph bounds	6
3	IMPLEMENTATION	2	6.2	Compatibility	8
3.1	Letters and Digits	2	7	<code>mathspec.sty</code>	9
3.2	Symbols	3	7.1	Initialising and options processing	9
4	ALPHABETS	3	7.2	Greek characters and digits .	9
4.1	Shorthands	4	7.3	Internal commands	11
4.2	Limitations	4	7.4	End user commands	12
5	GREEK CHARACTERS	5	7.5	More internal commands . .	14
			7.6	xkeyval things	16
			7.7	Extending L ^A T _E X commands .	17
			7.8	Declarations	18

1 PREAMBLE

This document describes the `mathspec` package, a package that provides an interface to typeset mathematics in X_EL^AT_EX using arbitrary text fonts. It relies on `fontspec` to work and familiarity with `fontspec` is advised. Thanks to Will Robertson for his useful advice and suggestions!

The package is in its developmental stage and later versions are likely to be incompatible with this version.

2 INTRODUCTION

Since Jonathan Kew released X_EL^AT_EX, an extension to T_EX that permits the inclusion of system wide Unicode fonts and modern font technologies in T_EX documents, users have been able to easily typeset documents using readily available fonts such as Hoefler Text and Times New Roman (This document is typeset using Sabon LT Std). Will Robertson's X_EL^AT_EX package `fontspec` provides an automatic font selection process for such arbitrary fonts. Still, mathematics typesetting has not benefited from this development to the same extent as text typesetting, which is not surprising given the font requirements that are demanded.

Will Robertson has in development a package `unicode-math` that is used to typeset mathematics using some font that has an OpenType mathematics table. Currently, the only two that are available are Cambria Math, a new design, by Microsoft and Asana Math, based on Hermann Zapf's Palatino, by Apostolos Syropoulos. It is expected that the STIX fonts, based on Times, may also be used.

Thus, it is evident that a book designer is confronted with such narrow variety in mathematics typefaces, even considering already established L^AT_EX packages such as `euler` (and Computer Modern, of course!) that are dedicated to providing mathematics typefaces; and the book designer is challenged to find a suitable pair of typefaces for mathematics and body text.

This package provides mathematics alphabets in any of the same typefaces that are available to X^ET_EX, using `fontspec` as a back end. Other mathematics symbols such as arrows and operators, whose designs are largely independent of an alphabetic typeface, can be taken from collections like `MnSymbol` or Computer Modern and are not covered by the scope of this package.

3 IMPLEMENTATION

```
\usepackage[mathspec and fontspec options]{mathspec}
```

To use the package, put `\usepackage{mathspec}` in the preamble of the document. It is not necessary to put `\usepackage[requirepackage=fontspec]` because `mathspec` will ensure that `fontspec` is loaded anyway. To load `fontspec` with some options, parse them through `mathspec`, for example, `\usepackage[quiet]{mathspec}` is equivalent to `\usepackage[quiet]{fontspec}\usepackage{mathspec}`.

Actually, `mathspec` ordinarily loads `fontspec` with the `no-math` option. To cancel this, explicitly use the `math` option: e.g. `\usepackage[math]{mathspec}`.

3.1 Letters and Digits

```
\setmathsfont[Set-set,shapes,font features]{font name}
```

`\setmathsfont` This single command is used to entirely describe the desired font for some use.
`\setmathfont` Usually, the command would appear up to two times in a document, to specify each the Latin and the Greek fonts. The command can be used only in the preamble, that is before `\begin{document}` because L^AT_EX will not allow it to be used elsewhere. Then, there can be only one Latin mathematics typeface and one Greek mathematics typeface in the document (The different fonts in section 6.1 of this document was only achieved through trickery).

(set) Compulsory value for key `Set`.

Latin, Greek.

(shapes) Optional comma separated list of keys.

A comma separated list of keys and their values, e.g. (`Uppercase=Regular`, `Lowercase=Italic`, `Digits=Regular`). Keys are `Uppercase`, `Lowercase` and `Digits` which can each have value `Regular`, `Italic` or `Plain`; `Regular` and `Italic` respectively indicate the regular and italic fonts of the typeface, `Plain`

indicates that no font assignment is performed by `\mathspec`, and that the symbols will be typeset in the default font, which is usually Computer Modern. If a key is absent, its default value, as indicated in table 1, is used.

The default values are very good and you would be wise not to change the Latin and the digit shapes. The Greek shapes can be changed to adhere to some particular style, for example all italic, or because the specified Greek font has only one shape regular.

TABLE 1: The default shapes for the symbol sets

		Latin		Greek	
Digits		Uppercase	Lowercase	Uppercase	Lowercase
Regular		Italic	Italic	Regular	Italic

`\plaindigits`

It is clear that the digits can be typeset by only one font at any one time. By default, if only one set is specified (Latin or Greek), then the digits are typeset using the font that is used for the set or if both sets are specified, then the digits are typeset using the Latin font, unless this choice is overridden. The choice can be overridden by explicitly writing `Digits=Regular` or `Digits=Plain` in the optional argument to `\setmathsf`, or with the command `\plaindigits`, which might be an easier way to cancel the assignment of a new font for the digits.

(font features), *(font name)* *(font features)* optional comma separated list, *(font name)* compulsory argument.

These are the same arguments as those used by `\fontspec` and are interpreted by `\fontspec`. See `\fontspec`'s documentation for details.

3.2 Symbols

Support for setting the symbols font was removed in this version. I am focussing on the other areas of the package and feel that an incomplete feature should not be present at all.

You can try `MnSymbol`, which has greater (and more uniform) coverage, with the package option `MnSymbol`, e.g. `\usepackage[MnSymbol]{mathspec}`. Note that `MnSymbol` is a third party package by Achim Blumensath, which can only be used if additionally installed.

4 ALPHABETS

`\setmathrm`
`\setmathcal`
`\setmathsf`
`\setmathit`
`\setmathfrak`
`\setmathbb`

The mathematics alphabets like `\mathrm` and `\mathcal` can be set using the commands:

- `\setmathrm[]{}` (defines `\mathrm`, `\mathit`, `\mathbf` and the font for operators)
- `\setmathcal[]{}` (defines `\mathcal`)

- `\setmathsf[font features]{font name}` (defines `\mathsf`)
- `\setmathtt[font features]{font name}` (defines `\mathtt`)
- `\setmathfrak[font features]{font name}` (defines `\mathfrak`)
- `\setmathbb[font features]{font name}` (defines `\mathbb`)

All are straight forward, but `\setmathrm` does a little more than the others. `mathspec` redefines `fontspec`'s definitions.

4.1 Shorthands

`\setprimaryfont[font features]{font name}`

`\setprimaryfont` `\setprimaryfont` is equivalent to:

`\setmainfont[font features]{font name}`
`\setmathsf[Set=Latin,font features]{font name}`
`\setmathrm[font features]{font name}`

and is useful to save typing the same information multiple times.

`\setsansfonts[font features]{font name}`
`\setmonofonts[font features]{font name}`

`\setsansfonts` `\setsansfonts` and `\setmonofonts` (note the plurals) are equivalent to:

`\setsansfont[font features]{font name}`
`\setmathsf[font features]{font name}`

and

`\setmonofont[font features]{font name}`
`\setmathtt[font features]{font name}`

respectively.

See `fontspec`'s documentation for details of `\setmainfont`, `\setsansfont` and `\setmonofont`.

4.2 Limitations

Apparently, there is a limit on the number of math groups (symbol fonts and alphabets) that a document may contain. It seems that 16 is the limit, which is enforced by `LATEX 2E` kernel macros. I am under the impression that `XETEX` actually permits 256 math groups, but I have not found that redefined `LATEX` macros alleviates the problem.

Maybe I am going about this the wrong way, but until I truly understand what's going on and improve this area, beware '`! LaTeX Error: Too many math alphabets used in version normal.`'.

5 GREEK CHARACTERS

For reference, the Greek alphabet and variant letter forms is given in table 2. Despite the name, `\varsigma` ζ is not a variant form of `\sigma`, it is the final form. Digamma F is an obsolete letter of the alphabet, originally placed between epsilon ϵ and zeta ζ .

TABLE 2: The Greek alphabet and variant letter forms with control sequences

	Uppercase	Lowercase	Uppercase	Lowercase
A	<code>\Alpha</code>	α	<code>\Xi</code>	ξ
B	<code>\Beta</code>	β	<code>\Omicron</code>	\omicron
Γ	<code>\Gammaamma</code>	γ	<code>\Pi</code>	π
Δ	<code>\Deltaleta</code>	δ	<code>\Rho</code>	ρ
E	<code>\Epsilon</code>	ϵ	<code>\Sigma</code>	ς
Z	<code>\Zeta</code>	ζ		σ
H	<code>\Eta</code>	η	<code>\Tau</code>	τ
Θ	<code>\Thetatha</code>	θ	<code>\Upsilonilon</code>	υ
I	<code>\Iota</code>	ι	<code>\Phi</code>	ϕ
K	<code>\Kappa</code>	κ	<code>\Chi</code>	χ
Λ	<code>\Lambda</code>	λ	<code>\Psi</code>	ψ
M	<code>\Mu</code>	μ	<code>\Omegaega</code>	ω
N	<code>\Nu</code>	ν	<code>\Digamma</code>	\digamma
	Normal form	Variant form	Normal form	Variant form
	β	$\mathbf{\beta}$	π	ϖ
	ϵ	$\mathbf{\epsilon}$	ρ	ϱ
	θ	$\mathbf{\theta}$	ϕ	φ
	κ	$\mathbf{\kappa}$	Θ	\varTheta

Initially, `mathspec` defines control sequences for the Greek characters that are absent in Computer Modern, because they are similar in form to Latin characters, from ASCII, thus control sequences like `\Alpha` and `\omicron` are defined. Any variant forms that are absent are equivalent to the normal forms. The meanings of these control sequences are preserved by a control sequence of the same name with the prefix `cm` (e.g. `\cmAlpha`), which may be recalled after the Greek mathematics font is changed.

`\normalvarforms`

Since not all fonts contain all variant forms, there might be the odd variant letter that remains in Computer Modern while other Greek letters have changed font. For these characters, the command `\normalvarforms` will make them equivalent to their corresponding normal forms. Note that this command only adjusts those that are absent in the font. Of course, this might mean that, for example, `\vartheta` and `\theta` would print the same glyph, which would be dubious if they are used in the same document, with different meanings.

`\varforms`

If an author does not agree with the font designer's choice of normal and variant forms, for example, I prefer `\phi` to print ' ϕ ' and `\varphi` to print ' φ ', which is not the default behaviour for many fonts, the forms can be exchanged by putting the list of letters to the command `\varforms`, e.g. `\varforms{theta,kappa,phi}` might be used if the Greek mathematics font is Garamond Premier Pro Italic.

It should be noted that `\epsilon` prints the lunate epsilon ‘ ϵ ’ and `\varepsilon` prints the usual (double loop) epsilon ‘ ε ’ in Plain T_EX and L^AT_EX. This is in contrast to other fonts, which contain the lunate style epsilon separately from the Greek alphabet among variant letter forms and symbols (where Unicode assigns ‘Greek Lunate Epsilon Symbol’). The definition of `\LaTeXe`, which prints ‘L^AT_EX ε ’ uses `\varepsilon` and care should be taken to ensure that `\LaTeXe` uses the usual epsilon either by using one of the methods that were presented in this section or by redefining `\LaTeXe` (possibly using my `metalogo` package), because ‘L^AT_EX ε ’ is not as good as ‘L^AT_EX ε ’.

6 ADDITIONAL INFORMATION

This section describes the shortcomings of this package. I wonder whether the benefits of being able to use an arbitrary font for mathematics outweigh the detriments; in a production environment, it might be best to seek an alternative approach and use some L^AT_EX set, like MathTime, MinionPro, Math Design or the TX or PX fonts, that is dedicated to producing good mathematics with one font.

6.1 Glyph bounds

In using this package to provide arbitrary fonts for mathematics, there are issues with glyph bounds (similar to italic correction), as illustrated in the equations:

$$f(x) = \sum_{n=-\infty}^{\infty} c_n e^{inx} \quad (1)$$

$$c_n = \frac{1}{2\pi} \int_{-\pi}^{\pi} f(x) e^{-inx} dx \quad (2)$$

where the function f is too close the parenthesis (and the exponent inx is so close to its base e that there is actually a collision! The reason is that the font has metrics that are suitable for use in text, but not for mathematics.

6.1.1 Discussion

Comparing the alphabets typeset in Computer Modern Italic, in table 3, it is shown that many characters have greater space around them in the mathematics version, which does not exist in the text version. The tracked alphabet shows the alphabet typeset as text, but also with a constant 1 mu intercharacter space (poor man’s tracking). Since the adjusted alphabet is approximately as long as the mathematics alphabet, on average, this is a fair method to increase the space between alphabetic characters in mathematics.

TABLE 3: Computer Modern Italic in text and mathematics

Text	<i>abcdefghijklmnpqrstuvwxyz</i>
Mathematics	<i>abcdefghijklmnpqrstuvwxyz</i>
Tracked	<i>abcdefghijklmnpqrstuvwxyz</i>

Now, the problem lies with implementing this behaviour. The best way would be to adjust T_EX’s mathematics spacing rules to add this 1 mu extra space after each

\mathalpha, but not after the \mathords. I do not know whether it is possible to separate the two types as such, since they are almost equivalent. Otherwise, would it look worse if \mathords also have this extra space?

As it turns out, TEX's mathematics spacing rules are hardwired into TEX and can not be adjusted by the user. The table that is used to determine the spacing between pairs of adjacent atoms, from *The TEXbook*, is reproduced below:

Left atom	Right atom							
	Ord.	Op.	Bin.	Rel.	Open	Close	Punct.	Inner
Ordinary, et al. (Ord.)	o	i	2	3	o	o	o	i
Large operator (Op.)	i	i		3	o	o	o	i
Binary operation (Bin.)	2	2			2			2
Relation (Rel.)	3	3		o	3	o	o	3
Opening (Open)	o	o		o	o	o	o	o
Closing (Close)	o	i	2	3	o	o	o	i
Punctuation (Punct.)	i	i		i	i	i	i	i
Delimited subformula (Inner)	i	i	2	3	i	o	i	i

where o, i, 2 and 3 represent zero, thin, medium and thick skips respectively and coloured entries indicate that space is to be inserted only in display and text styles and not in script and scriptscript styles. Both Plain TEX and LATEX define the three skips as:

```
\thinmuskip 3mu
\medmuskip 4mu plus 3mu minus 4mu
\thickmuskip 5mu plus 5mu
```

and unless the option `normalskips` to the package is used (e.g. `\usepackage [normalskips]{mathspec}`), `mathspec` increases each skip by 1 mu:

```
\thinmuskip 4mu
\medmuskip 5mu plus 3mu minus 4mu
\thickmuskip 6mu plus 5mu
```

As far as I can tell, nothing can be done about the zero skip.

If XETEX is able to get information about the ‘ink box’ of a character, this elaborate, awkward and ugly hack, which is not even good anyway, might be replaced with something that is more elegant (or at least yields better results); better yet, if XETEX allows customisation of the mathematics spacing rules. It is impossible at the moment, for now, this described method is the best that is possible.

6.1.2 Solution

$\text{\textbackslash +}[\langle size \rangle]$

- + The command \+ is used to produce fine control over the spacing in mathematics. Without its optional argument, it inserts a 1 mu ($\frac{1}{18}$ em) skip. \+[\langle size \rangle] inserts a

`\langle size \rangle` mu skip. The spacing of equations (1, 2) are improved by the replacements that are described in table 4:

$$f(x) = \sum_{n=-\infty}^{\infty} c_n e^{jnx} \quad f(x) = \sum_{n=-\infty}^{\infty} c_n e^{jnx} \quad (3)$$

$$c_n = \frac{1}{2\pi} \int_{-\pi}^{\pi} f(x) e^{-jnx} dx \quad c_n = \frac{1}{2\pi} \int_{-\pi}^{\pi} f(x) e^{-jnx} dx \quad (4)$$

TABLE 4: Example replacements that improve spacing

Original	Replacement
<code>f(x)</code>	<code>\+f\left(x\right)</code>
<code>e^{jnx}</code>	<code>e^{\+\left[5\right]jn\+x}</code>
<code>e^{-jnx}</code>	<code>e^{\+\-jn\+x}</code>

This procedure is indeed awkward for the user, but still necessary to produce decent results. Note that `(x)` is replaced with `\left(x\right)`, which should always be done anyway (or with a more convenient macro, perhaps `\grp{}{x}` defined by `\newcommand\grp[3]{\left#1#3\right#2}`).

6.2 Compatibility

If the package `amsmath` is used, it must be loaded before `mathspec`.

7 `mathspec.sty`

7.1 Initialising and options processing

```
1 \let\eu@ifnot@normalskips@\firstofone
2 \let\eu@if@MnSymbol@\gobble
3 \def\eu@zf@math{no-math}
4 \DeclareOption{normalskips}{\let\eu@ifnot@normalskips@\gobble}
5 \DeclareOption{no-math}{\relax}
6 \DeclareOption{MnSymbol}{\let\eu@if@MnSymbol@\firstofone}
7 \DeclareOption{math}{\def\eu@zf@math{math}}
8 \DeclareOption*[{\PassOptionsToPackage{\CurrentOption}{fontspec}}]
9 \ProcessOptions\relax
10 \RequirePackage[\eu@zf@math]{fontspec}[2008/08/09]
11 \eu@if@MnSymbol{\RequirePackage{MnSymbol}}
12 \RequirePackage{xkeyval}
13 \RequirePackage{xifthen}
14 \newif\if@eu@LatinUppercase@
15 \newif\if@eu@LatinLowercase@
16 \newif\if@eu@LatinDigits@
17 \newif\if@eu@GreekUppercase@
18 \newif\if@eu@GreekLowercase@
19 \newif\if@eu@GreekDigits@
20 \newif\if@eu@Symbols@
21 \newif\if@eu@Digits@
22 \let\eu@if@varforms@\gobble
23 \let\eu@ifset@mathrm@\gobble
24 \let\eu@ifset@mathcal@\gobble
25 \let\eu@ifset@mathsf@\gobble
26 \let\eu@ifset@mathtt@\gobble
27 \let\eu@ifset@mathfrak@\gobble
28 \let\eu@ifset@mathbb@\gobble
```

Redefine the skips.

```
29 \eu@ifnot@normalskips{
30   \thinmuskip=4mu
31   \medmuskip=5mu plus 2mu minus 4mu
32   \thickmuskip=6mu plus 5mu}
```

`\eu@isloaded` A command to test whether a package is loaded and puts the result in a Boolean. Used to test for `amsmath` here and `\AtBeginDocument` because `amsmath`, if used, must be loaded before `mathspec`.

```
33 \newcommand\eu@isloaded[2][]{%
34   \expandafter\ifx\csname if@eu@#2loaded@\endcsname\relax
35     \expandafter\newif\csname if@eu@#2loaded@\endcsname
36   \fi
37   \@ifpackageloaded{#2}
38   { \csname @eu@#2loaded@\true\endcsname #1}
39   { \csname @eu@#2loaded@\false\endcsname}}
40 \eu@isloaded{amsmath}
```

7.2 Greek characters and digits

Complete the missing Greek characters from ASCII. Easier done now than later.

```

41 \DeclareMathSymbol{\Alpha}{\mathalpha}{operators}{41}
42 \DeclareMathSymbol{\Beta}{\mathalpha}{operators}{42}
43 \DeclareMathSymbol{\Epsilon}{\mathalpha}{operators}{45}
44 \DeclareMathSymbol{\Zeta}{\mathalpha}{operators}{5A}
45 \DeclareMathSymbol{\Eta}{\mathalpha}{operators}{48}
46 \DeclareMathSymbol{\Iota}{\mathalpha}{operators}{49}
47 \DeclareMathSymbol{\Kappa}{\mathalpha}{operators}{4B}
48 \DeclareMathSymbol{\Mu}{\mathalpha}{operators}{4D}
49 \DeclareMathSymbol{\Nu}{\mathalpha}{operators}{4E}
50 \DeclareMathSymbol{\Omicron}{\mathalpha}{operators}{4F}
51 \DeclareMathSymbol{\Rho}{\mathalpha}{operators}{50}
52 \DeclareMathSymbol{\Tau}{\mathalpha}{operators}{54}
53 \DeclareMathSymbol{\Chi}{\mathalpha}{operators}{58}
54 \DeclareMathSymbol{\omicron}{\mathord}{letters}{6F}

```

Unavailable variant forms are equivalent to normal forms. Using Latin ‘F’ for digamma \digamma is better than nothing.

```

55 \let\varbeta\beta
56 @ifundefined{varkappa}
57   {\let\varkappa\kappa}
58   {\relax}
59 \let\varTheta\Theta
60 @ifundefined{digamma}
61   {\DeclareMathSymbol{\Digamma}{\mathalpha}{operators}{46}}
62   {\DeclareMathSymbol{\digamma}{\mathord}{operators}{46}}
63   {\let\Digamma\digamma}

```

Preserve the original definitions of the Greek control sequences with `cm` prefix.

```

64 \let\cmAlpha\Alpha
65 \let\cmBeta\Beta
66 \let\cmGamma\Gamma
67 \let\cmDelta\Delta
68 \let\cmEpsilon\Epsilon
69 \let\cmZeta\Zeta
70 \let\cmEta\Eta
71 \let\cmTheta\Theta
72 \let\cmIota\Iota
73 \let\cmKappa\Kappa
74 \let\cmLambda\Lambda
75 \let\cmMu\Mu
76 \let\cmNu\nu
77 \let\cmXi\xi
78 \let\cmOmicron\Omicron
79 \let\cmPi\Pi
80 \let\cmRho\Rho
81 \let\cmSigma\Sigma
82 \let\cmTau\Tau
83 \let\cmUpsilon\Upsilon
84 \let\cmPhi\Phi
85 \let\cmChi\Chi
86 \let\cmPsi\Psi
87 \let\cmOmega\Omega
88 \let\cmDigamma\Digamma
89 \let\cmAlpha\alpha
90 \let\cmbeta\beta

```

```

91 \let\cmgamma\gamma
92 \let\cmdelta\delta
93 \let\cmepsilon\epsilon
94 \let\cmzeta\zeta
95 \let\cmeta\eta
96 \let\cmtheta\theta
97 \let\cmiota\iota
98 \let\cmkappa\kappa
99 \let\cmlambda\lambda
100 \let\cmmu\mu
101 \let\cmnu\nu
102 \let\cmxi\xi
103 \let\cmomicron\omicron
104 \let\cmpi\pi
105 \let\cmrho\rho
106 \let\cmvarsigma\varsigma
107 \let\cmsigma\sigma
108 \let\cmtau\tau
109 \let\cmupsilon\upsilon
110 \let\cmphi\phi
111 \let\cmchi\chi
112 \let\cmpsi\psi
113 \let\cmomega\omega
114 \let\cmdigamma\digamma
115 \let\cmvarbeta\varbeta
116 \let\cmvarepsilon\varepsilon
117 \let\cmvartheta\vartheta
118 \let\cmvarkappa\varkappa
119 \let\cmvarpi\varpi
120 \let\cmvarrho\varrho
121 \let\cmvarphi\varphi
122 \let\cmvarTheta\varTheta

```

7.3 Internal commands

`\ernewcommand` Useful macros and internal commands.

```

123 \RequirePackage{etoolbox}
124 \gobble{\providecommand\expandonce[1]{\unexpanded\expandafter{\#1}}}
125 \providecommand\expanded[1]{\edef@tempa{\#1}@tempa}
126 \providecommand\ernewcommand[1]{
127   \ifundefined{\expandafter\gobble\string#1}%
128     {\let\er@newcommand\newcommand}%
129     {\let\er@newcommand\renewcommand
130      \PackageWarning{mathspec}{Redefining command `\\string#1'}}%
131   \er@newcommand#1}
132 \newcommand\eu@setkeys[3][]{%
133   \ifthenelse{\isempty{\#1}}%
134     {\relax}%
135     {\presetkeys{\eu}{\#2}{\#1}{}}%
136   \expanded{\noexpand\setkeys*\eu{\#2}{\expandonce{\#3}}}%
137 \newcommand\eu@fontspec[2]{\expanded{\noexpand\zf@fontspec{\expandonce{\#1}}{\expandonce{\#2}}}}

```

`\eu@DeclareRobustCommand` breqn's `\@ifnext` replaces `\@ifnextchar` in the definition of L^AT_EX's `\DeclareRobustCommand`. This is needed for the definition of `\+`.

```

138 \def\@ifnext#1#2#3{%
139   \let\@tempd=#1%
140   \def\@tempa{#2}%
141   \def\@tempb{#3}%
142   \futurelet\@tempc\@ifnextra}
143 \def\@ifnextra{%
144   \ifx\@tempc\@tempd%
145   \let\@tempb\@tempa%
146   \fi\@tempb}
147 \def\eu@DeclareRobustCommand{\star@or@long\eu@declare@robustcommand}
148 \def\eu@declare@robustcommand#1{%
149   \ifx#1\undefined\else\ifx#1\relax\else
150     \@latex@info{Redefining \string#1}%
151   \fi\fi
152   \edef\reserved@a{\string#1}%
153   \def\reserved@b{#1}%
154   \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
155   \edef#1{%
156     \ifx\reserved@a\reserved@b
157       \noexpand\x@protect
158       \noexpand#1%
159     \fi
160     \noexpand\protect
161     \expandafter\noexpand\csname\expandafter@gobble\string#1\endcsname}%
162   \let\ifdefinable\@rc@ifdefinable
163   \expandafter\eu@new@command\csname\expandafter@gobble\string#1\endcsname}%
164 \def\eu@new@command#1{\eu@testopt{\eu@newcommand#1}0}
165 \def\eu@newcommand#1[#2]{\@ifnext[{\@xargdef#1[#2]}{\@argdef#1[#2]}}%
166 \long\def\eu@testopt#1#2{\@ifnext[{\#1}{\#1[\#2]}}}

```

7.4 End user commands

- \normalvarforms If, after the Greek font is assigned, variant forms retain their original definitions, this command will cause them to be equivalent to the normal forms.

```

167 \newcommand\normalvarforms[1][]{\AtBeginDocument{%
168   \ifx\varbeta\cmvarbeta
169     \let\varbeta\beta
170   \fi
171   \ifx\varepsilon\cmvarepsilon
172     \let\varepsilon\epsilon
173   \fi
174   \ifx\vartheta\cmvartheta
175     \let\vartheta\theta
176   \fi
177   \ifx\varkappa\cmvarkappa
178     \let\varkappa\kappa
179   \fi
180   \ifx\varpi\cmvarpi
181     \let\varpi\pi
182   \fi
183   \ifx\varrho\cmvarrho
184     \let\varrho\rho
185   \fi

```

```

186 \ifx\varphi\cmvarphi
187   \let\varphi\phi
188 \fi
189 \ifx\varTheta\cmvarTheta
190   \let\varTheta\Theta
191 \fi}}

```

\plaindigits This command is used to easily disable digits redefinitions.

```

192 \let\eu@ifnot@plaindigits@\firstofone
193 \newcommand\plaindigits{\let\eu@ifnot@plaindigits@\gobble}

```

The quintessential command. From here, the code branches to four locations.

\setmathsf

```

194 \providecommand\setmathsf{\eu@setmathsf}
195 \let\setmathfont\setmathsf

```

- + This command inserts a horizontal skip in mathematics. It must be robust and any white space between the control sequence and a next [must not be ignored, so that legitimate (square) brackets in mathematics is not interpreted as an optional argument.

```
196 \eu@DeclareRobustCommand\+[1][1]{\ensuremath{\mskip#1mu}}
```

\varforms This command exchanges variant and normal forms for the specified letters.

```
197 \newcommand\varforms[1]{\def\eu@if@varforms##1{##1}}
```

\setmathrm Mathematics alphabet commands.

```

198 \ernewcommand\setmathrm[2][]{
199   \zf@fontspec{#1}{#2}
200   \let\eu@mathrm\zf@family
201 \setmathfrak \let\eu@ifset@mathrm@\firstofone
202   \providecommand\eu@mathbf@shape{n}
203 \ernewcommand\setmathcal[2][]{
204   \zf@fontspec{#1}{#2}
205   \let\eu@mathcal\zf@family
206   \let\eu@ifset@mathcal@\firstofone
207   \providecommand\eu@mathcal@series{m}
208   \providecommand\eu@mathcal@shape{n}
209 \ernewcommand\setmathsf[2][]{
210   \zf@fontspec{#1}{#2}
211   \let\eu@mathsf\zf@family
212   \let\eu@ifset@mathsf@\firstofone}
213 \ernewcommand\setmathtt[2][]{
214   \zf@fontspec{#1}{#2}
215   \let\eu@mathtt\zf@family
216   \let\eu@ifset@mathtt@\firstofone}
217 \ernewcommand\setmathfrak[2][]{
218   \zf@fontspec{#1}{#2}
219   \let\eu@mathfrak\zf@family
220   \let\eu@ifset@mathfrak@\firstofone
221   \providecommand\eu@mathfrak@series{m}}
222 \ernewcommand\setmathbb[2][]{
223   \zf@fontspec{#1}{#2}

```

```

224 \let\eu@mathbb\zf@family
225 \let\eu@ifset@mathbb@\firstofone
226 \providecommand\eu@mathbb@series{m}}

```

\setprimaryfont Shorthands

```

\setsansfonts 227 \newcommand\setprimaryfont[2][]{%
\setmonofonts 228 \setmainfont[#1]{#2}
229 \setmathsf[Set=Latin,#1]{#2}
230 \setmathrm[#1]{#2}}
231 \newcommand\setsansfonts[2][]{%
232 \setsansfont[#1]{#2}
233 \setmathsf[#1]{#2}}
234 \newcommand\setmonofonts[2][]{%
235 \setmonofont[#1]{#2}
236 \setmathtt[#1]{#2}}

```

7.5 More internal commands

7.5.1 \setmathsf branches

```

237 \newcommand\eu@setmathsf[1][Set=Special]{%
238 \eu@setkeys{Scope}{#1}
239 \ifcase\eu@ScopeSet@@value
240 \let\eu@ScopeSet@Value\eu@ScopeSet@Special
241 \or
242 \let\eu@ScopeSet@Value\eu@ScopeSet@Latin
243 \or
244 \let\eu@ScopeSet@Value\eu@ScopeSet@Greek
245 \or
246 \let\eu@ScopeSet@Value\eu@ScopeSet@Symbols
247 \fi
248 \eu@ScopeSet@Value}

```

Special set. This command can be used as a hook to some external code.

```
249 \providecommand\eu@ScopeSet@Special[1]{\relax}
```

Latin set.

```

250 \newcommand\eu@ScopeSet@Latin[1]{%
251 \eu@setkeys[Uppercase=Italic,Lowercase=Italic,Digits=Regular]{Latin}{\XKV@rm}
252 \eu@fontspec{\XKV@rm}{#1}
253 \ifcase\eu@LatinUppercase@@value
254 \ernewcommand\eu@LatinUppercase@symfont{Lmn}
255 \let\eu@Latinmathsf\zf@family
256 @_eu@LatinUppercase@true
257 \def\operator@font{\mathgroup\symLmn}
258 \or
259 \ernewcommand\eu@LatinUppercase@symfont{Lmit}
260 \let\eu@Latinmathsf\zf@family
261 @_eu@LatinUppercase@true
262 \or\fi
263 \ifcase\eu@LatinLowercase@@value
264 \ernewcommand\eu@LatinLowercase@symfont{Lmn}
265 \let\eu@Latinmathsf\zf@family
266 @_eu@LatinLowercase@true
267 \or

```

```

268     \ernewcommand\eu@LatinLowercase@symfont{Lmit}
269     \let\eu@Latinmathsfont\zf@family
270     \@eu@LatinLowercase@true
271     \or\fi
272     \ifcase\eu@LatinDigits@@value
273     \ernewcommand\eu@LatinDigits@symfont{Lmn}
274     \let\eu@Latinmathsfont\zf@family
275     \@eu@LatinDigits@true
276     \or
277     \ernewcommand\eu@LatinDigits@symfont{Lmit}
278     \let\eu@Latinmathsfont\zf@family
279     \@eu@LatinDigits@true
280     \or\fi}

Greek set
281 \newcommand\eu@ScopeSet@Greek[1]{
282   \eu@setkeys[Uppercase=Regular,Lowercase=Italic,Digits=Plain]{Greek}{\XKV@rm}
283   \eu@fontspec{\XKV@rm}{#1}
284   \ifcase\eu@GreekUppercase@@value
285     \ernewcommand\eu@GreekUppercase@symfont{Gmn}
286     \let\eu@Greekmathsfont\zf@family
287     \@eu@GreekUppercase@true
288   \or
289     \ernewcommand\eu@GreekUppercase@symfont{Gmit}
290     \let\eu@Greekmathsfont\zf@family
291     \@eu@GreekUppercase@true
292   \or\fi
293   \ifcase\eu@GreekLowercase@@value
294     \ernewcommand\eu@GreekLowercase@symfont{Gmn}
295     \let\eu@Greekmathsfont\zf@family
296     \@eu@GreekLowercase@true
297   \or
298     \ernewcommand\eu@GreekLowercase@symfont{Gmit}
299     \let\eu@Greekmathsfont\zf@family
300     \@eu@GreekLowercase@true
301   \or\fi
302   \ifcase\eu@GreekDigits@@value
303     \ernewcommand\eu@GreekDigits@symfont{Gmn}
304     \let\eu@Greekmathsfont\zf@family
305     \@eu@GreekDigits@true
306   \or
307     \ernewcommand\eu@GreekDigits@symfont{Gmit}
308     \let\eu@Greekmathsfont\zf@family
309     \@eu@GreekDigits@true
310   \or\fi}

```

Symbols set. This command actually does not do a lot.

```

311 \newcommand\eu@ScopeSet@Symbols[1]{
312   \@eu@Symbols@true
313   \zf@fontspec{}{#1}
314   \let\eu@Symbolsmathsfont\zf@family
315   \def\eu@Symbol@symfont{Smn}}
316 \renewcommand\eu@ScopeSet@Symbols[1]{
317   \@eu@Symbols@false}

```

7.5.2 Exchanging variant and normal forms

```

318 \newcommand\eu@VarForms[1]{
319   \fontfamily\eu@Greekmathsfont\selectfont
320   \eu@setkeys{VarForms}{#1}
321   \ifeu@VarForms@beta
322     \eu@DeclareMathSymbol{\beta}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D0}}[\beta]
323     \eu@DeclareMathSymbol{\beta}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D0}}[\varbeta]
324   \fi
325   \ifeu@VarForms@epsilon
326     \eu@DeclareMathSymbol{\epsilon}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F5}}[\epsilon]
327     \eu@DeclareMathSymbol{\epsilon}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F5}}[\varepsilon]
328   \fi
329   \ifeu@VarForms@theta
330     \eu@DeclareMathSymbol{\theta}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D1}}[\theta]
331     \eu@DeclareMathSymbol{\theta}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D1}}[\vartheta]
332   \fi
333   \ifeu@VarForms@kappa
334     \eu@DeclareMathSymbol{\kappa}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F0}}[\kappa]
335     \eu@DeclareMathSymbol{\kappa}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F0}}[\varkappa]
336   \fi
337   \ifeu@VarForms@pi
338     \eu@DeclareMathSymbol{\pi}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D6}}[\pi]
339     \eu@DeclareMathSymbol{\pi}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D6}}[\varpi]
340   \fi
341   \ifeu@VarForms@rho
342     \eu@DeclareMathSymbol{\rho}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F1}}[\rho]
343     \eu@DeclareMathSymbol{\rho}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F1}}[\varrho]
344   \fi
345   \ifeu@VarForms@phi
346     \eu@DeclareMathSymbol{\phi}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D5}}[\phi]
347     \eu@DeclareMathSymbol{\phi}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3D5}}[\varphi]
348   \fi
349   \ifeu@VarForms@Theta
350     \eu@DeclareMathSymbol{\Theta}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F4}}[\Theta]
351     \eu@DeclareMathSymbol{\Theta}{\mathalpha}{\eu@GreekLowercase@symfont}{\text{3F4}}[\varTheta]
352   \fi

```

7.6 xkeyval things

```

353 \define@choicekey[eu]{Scope}{Set}
354   [\eu@ScopeSet@value\eu@ScopeSet@@value]
355   {Special,Latin,Greek,Symbols}[Special]{\relax}
356 \define@choicekey[eu]{Latin}{Uppercase}
357   [\eu@LatinUppercase@value\eu@LatinUppercase@@value]
358   {Regular,Italic,Plain}[Italic]{\relax}
359 \define@choicekey[eu]{Latin}{Lowercase}
360   [\eu@LatinLowercase@value\eu@LatinLowercase@@value]
361   {Regular,Italic,Plain}[Italic]{\relax}
362 \define@choicekey[eu]{Latin}{Digits}
363   [\eu@LatinDigits@value\eu@LatinDigits@@value]
364   {Regular,Italic,Plain}[Regular]{\relax}
365 \define@choicekey[eu]{Greek}{Uppercase}
366   [\eu@GreekUppercase@value\eu@GreekUppercase@@value]
367   {Regular,Italic,Plain}[Regular]{\relax}

```

```

368 \define@choicekey[eu]{Greek}{Lowercase}
369   [\eu@GreekLowercase@value\eu@GreekLowercase@@value]
370   {Regular,Italic,Plain}[Italic]{\relax}
371 \define@choicekey[eu]{Greek}{Digits}
372   [\eu@GreekDigits@value\eu@GreekDigits@@value]
373   {Regular,Italic,Plain}[Regular]{\relax}
374 \define@boolkey[eu]{VarForms}{beta}[True]{\relax}
375 \define@boolkey[eu]{VarForms}{epsilon}[True]{\relax}
376 \define@boolkey[eu]{VarForms}{theta}[True]{\relax}
377 \define@boolkey[eu]{VarForms}{kappa}[True]{\relax}
378 \define@boolkey[eu]{VarForms}{pi}[True]{\relax}
379 \define@boolkey[eu]{VarForms}{rho}[True]{\relax}
380 \define@boolkey[eu]{VarForms}{phi}[True]{\relax}
381 \define@boolkey[eu]{VarForms}{Theta}[True]{\relax}

```

7.7 Extending L^AT_EX commands

- \eu@XeTeXDeclareMathSymbol A crude extension of L^AT_EX's \DeclareMathSymbol to allow the greater set of Unicode characters.

```

382 \newcommand\eu@XeTeXDeclareMathSymbol[4]{
383   \expandafter\XeTeXmathcode`#1\mathchar@type#2\csname sym#3\endcsname#4}

```

- \eu@DeclareMathSymbol This command declares a symbol only if it appears in the font and optionally defines an equivalent control sequence.

```

384 \newcommand\eu@DeclareMathSymbol[4]{
385   \ifnum\XeTeXcharglyph#4>0
386     \eu@XeTeXDeclareMathSymbol#1#2#3#4
387   \fi
388   \let\eu@character#1
389   \def\eu@character{#4}
390   \futurelet\@tempa\eu@DeclareMathSymbol
391   \def\eu@@@DeclareMathSymbol{
392     \ifx\@tempa[
393       \let\eu@@@DeclareMathSymbol\eu@DeclareMathSymbol@option
394     \else
395       \let\eu@@@DeclareMathSymbol\relax
396     \fi
397     \eu@@@DeclareMathSymbol}
398   \def\eu@DeclareMathSymbol@option[#1]{%
399     \ifnum\XeTeXcharglyph\eu@character>0
400       \let#1\eu@character
401     \fi}

```

A modification of L^AT_EX's \DeclareMathSymbol to perform only if the glyph appears in the font.

```

402 \let\LaTeXe@DeclareMathSymbol\DeclareMathSymbol
403 \newcommand\eu@LaTeXe@DeclareMathSymbol[4]{
404   \ifnum\XeTeXcharglyph#4>0
405     \LaTeXe@DeclareMathSymbol{-#1}{#2}{#3}{#4}
406   \fi}
407 \let\DeclareMathSymbol\eu@LaTeXe@DeclareMathSymbol

```

7.8 Declarations

Fonts.

```
408 \newcommand\eu@DeclareFonts{  
409   \let\eu@if@Latin@gobble  
410   \if@eu@LatinUppercase@\let\eu@if@Latin@\firstofone\fi  
411   \if@eu@LatinLowercase@\let\eu@if@Latin@\firstofone\fi  
412   \if@eu@LatinDigits@\let\eu@if@Latin@\firstofone\fi  
413   \let\eu@if@Greek@gobble  
414   \if@eu@GreekUppercase@\let\eu@if@Greek@\firstofone\fi  
415   \if@eu@GreekLowercase@\let\eu@if@Greek@\firstofone\fi  
416   \if@eu@GreekDigits@\let\eu@if@Greek@\firstofone\fi  
417   \eu@if@Latin{  
418     \DeclareSymbolFont{Lmn}{EU1}{\eu@Latinmathsfont}{m}{n}  
419     \DeclareSymbolFont{Lmit}{EU1}{\eu@Latinmathsfont}{m}{it}  
420   }  
421   \eu@if@Greek{  
422     \DeclareSymbolFont{Gmn}{EU1}{\eu@Greekmathsfont}{m}{n}  
423     \DeclareSymbolFont{Gmit}{EU1}{\eu@Greekmathsfont}{m}{it}}  
424   \if@eu@Symbols@  
425     \DeclareSymbolFont{Smn}{EU1}{\eu@Symbolsmathsfont}{m}{n}  
426   \fi}
```

Digits.

```
427 \newcommand\eu@DeclareDigits{  
428   \let\eu@if@Digits@gobble  
429   \if@eu@GreekDigits@  
430     \let\eu@if@Digits@\firstofone  
431     \let\eu@Digits@symfont\eu@GreekDigits@symfont  
432     \let\eu@Digitsmathsfont\eu@Greekmathsfont  
433   \else  
434     \if@eu@LatinDigits@  
435       \let\eu@if@Digits@\firstofone  
436       \let\eu@Digits@symfont\eu@LatinDigits@symfont  
437       \let\eu@Digitsmathsfont\eu@Latinmathsfont  
438     \fi  
439   \fi  
440   \eu@if@Digits{  
441     \fontfamily\eu@Digitsmathsfont\selectfont  
442     \DeclareMathSymbol{0}{\mathord}{\eu@Digits@symfont}{`0}  
443     \DeclareMathSymbol{1}{\mathord}{\eu@Digits@symfont}{`1}  
444     \DeclareMathSymbol{2}{\mathord}{\eu@Digits@symfont}{`2}  
445     \DeclareMathSymbol{3}{\mathord}{\eu@Digits@symfont}{`3}  
446     \DeclareMathSymbol{4}{\mathord}{\eu@Digits@symfont}{`4}  
447     \DeclareMathSymbol{5}{\mathord}{\eu@Digits@symfont}{`5}  
448     \DeclareMathSymbol{6}{\mathord}{\eu@Digits@symfont}{`6}  
449     \DeclareMathSymbol{7}{\mathord}{\eu@Digits@symfont}{`7}  
450     \DeclareMathSymbol{8}{\mathord}{\eu@Digits@symfont}{`8}  
451     \DeclareMathSymbol{9}{\mathord}{\eu@Digits@symfont}{`9}}}
```

Uppercase Latin.

```
452 \newcommand\eu@DeclareLatinUppercase{  
453   \if@eu@LatinUppercase@  
454     \fontfamily\eu@Latinmathsfont\selectfont  
455     \DeclareMathSymbol{A}{\mathalpha}{\eu@LatinUppercase@symfont}{`A}}
```

```

456 \DeclareMathSymbol{B}{\mathalpha}{\eu@LatinUppercase@symfont}{`B}
457 \DeclareMathSymbol{C}{\mathalpha}{\eu@LatinUppercase@symfont}{`C}
458 \DeclareMathSymbol{D}{\mathalpha}{\eu@LatinUppercase@symfont}{`D}
459 \DeclareMathSymbol{E}{\mathalpha}{\eu@LatinUppercase@symfont}{`E}
460 \DeclareMathSymbol{F}{\mathalpha}{\eu@LatinUppercase@symfont}{`F}
461 \DeclareMathSymbol{G}{\mathalpha}{\eu@LatinUppercase@symfont}{`G}
462 \DeclareMathSymbol{H}{\mathalpha}{\eu@LatinUppercase@symfont}{`H}
463 \DeclareMathSymbol{I}{\mathalpha}{\eu@LatinUppercase@symfont}{`I}
464 \DeclareMathSymbol{J}{\mathalpha}{\eu@LatinUppercase@symfont}{`J}
465 \DeclareMathSymbol{K}{\mathalpha}{\eu@LatinUppercase@symfont}{`K}
466 \DeclareMathSymbol{L}{\mathalpha}{\eu@LatinUppercase@symfont}{`L}
467 \DeclareMathSymbol{M}{\mathalpha}{\eu@LatinUppercase@symfont}{`M}
468 \DeclareMathSymbol{N}{\mathalpha}{\eu@LatinUppercase@symfont}{`N}
469 \DeclareMathSymbol{O}{\mathalpha}{\eu@LatinUppercase@symfont}{`O}
470 \DeclareMathSymbol{P}{\mathalpha}{\eu@LatinUppercase@symfont}{`P}
471 \DeclareMathSymbol{Q}{\mathalpha}{\eu@LatinUppercase@symfont}{`Q}
472 \DeclareMathSymbol{R}{\mathalpha}{\eu@LatinUppercase@symfont}{`R}
473 \DeclareMathSymbol{S}{\mathalpha}{\eu@LatinUppercase@symfont}{`S}
474 \DeclareMathSymbol{T}{\mathalpha}{\eu@LatinUppercase@symfont}{`T}
475 \DeclareMathSymbol{U}{\mathalpha}{\eu@LatinUppercase@symfont}{`U}
476 \DeclareMathSymbol{V}{\mathalpha}{\eu@LatinUppercase@symfont}{`V}
477 \DeclareMathSymbol{W}{\mathalpha}{\eu@LatinUppercase@symfont}{`W}
478 \DeclareMathSymbol{X}{\mathalpha}{\eu@LatinUppercase@symfont}{`X}
479 \DeclareMathSymbol{Y}{\mathalpha}{\eu@LatinUppercase@symfont}{`Y}
480 \DeclareMathSymbol{Z}{\mathalpha}{\eu@LatinUppercase@symfont}{`Z}
481 \fi}

```

Lowercase Latin.

```

482 \newcommand{\eu@DeclareLatinLowercase{
483   \if@eu@LatinLowercase@
484     \fontfamily{\eu@Latinmathsfont}\selectfont
485     \DeclareMathSymbol{a}{\mathalpha}{\eu@LatinLowercase@symfont}{`a}
486     \DeclareMathSymbol{b}{\mathalpha}{\eu@LatinLowercase@symfont}{`b}
487     \DeclareMathSymbol{c}{\mathalpha}{\eu@LatinLowercase@symfont}{`c}
488     \DeclareMathSymbol{d}{\mathalpha}{\eu@LatinLowercase@symfont}{`d}
489     \DeclareMathSymbol{e}{\mathalpha}{\eu@LatinLowercase@symfont}{`e}
490     \DeclareMathSymbol{f}{\mathalpha}{\eu@LatinLowercase@symfont}{`f}
491     \DeclareMathSymbol{g}{\mathalpha}{\eu@LatinLowercase@symfont}{`g}
492     \DeclareMathSymbol{h}{\mathalpha}{\eu@LatinLowercase@symfont}{`h}
493     \DeclareMathSymbol{i}{\mathalpha}{\eu@LatinLowercase@symfont}{`i}
494     \DeclareMathSymbol{j}{\mathalpha}{\eu@LatinLowercase@symfont}{`j}
495     \DeclareMathSymbol{k}{\mathalpha}{\eu@LatinLowercase@symfont}{`k}
496     \DeclareMathSymbol{l}{\mathalpha}{\eu@LatinLowercase@symfont}{`l}
497     \DeclareMathSymbol{m}{\mathalpha}{\eu@LatinLowercase@symfont}{`m}
498     \DeclareMathSymbol{n}{\mathalpha}{\eu@LatinLowercase@symfont}{`n}
499     \DeclareMathSymbol{o}{\mathalpha}{\eu@LatinLowercase@symfont}{`o}
500     \DeclareMathSymbol{p}{\mathalpha}{\eu@LatinLowercase@symfont}{`p}
501     \DeclareMathSymbol{q}{\mathalpha}{\eu@LatinLowercase@symfont}{`q}
502     \DeclareMathSymbol{r}{\mathalpha}{\eu@LatinLowercase@symfont}{`r}
503     \DeclareMathSymbol{s}{\mathalpha}{\eu@LatinLowercase@symfont}{`s}
504     \DeclareMathSymbol{t}{\mathalpha}{\eu@LatinLowercase@symfont}{`t}
505     \DeclareMathSymbol{u}{\mathalpha}{\eu@LatinLowercase@symfont}{`u}
506     \DeclareMathSymbol{v}{\mathalpha}{\eu@LatinLowercase@symfont}{`v}
507     \DeclareMathSymbol{w}{\mathalpha}{\eu@LatinLowercase@symfont}{`w}
508     \DeclareMathSymbol{x}{\mathalpha}{\eu@LatinLowercase@symfont}{`x}

```

```

509      \DeclareMathSymbol{y}{\mathalpha}{\eu@LatinLowercase@symfont}{`y}
510      \DeclareMathSymbol{z}{\mathalpha}{\eu@LatinLowercase@symfont}{`z}
511      \fi}

```

Uppercase Greek.

```

512 \newcommand{\eu@DeclareGreekUppercase{
513   \if@eu@GreekUppercase@
514     \fontfamily{\eu@Greekmathsfont}\selectfont
515     \eu@DeclareMathSymbol{A}{\mathalpha}{\eu@GreekUppercase@symfont}{`A}[\Alpha]
516     \eu@DeclareMathSymbol{B}{\mathalpha}{\eu@GreekUppercase@symfont}{`B}[\Beta]
517     \eu@DeclareMathSymbol{Gamma}{\mathalpha}{\eu@GreekUppercase@symfont}{`Gamma}[\Gamma]
518     \eu@DeclareMathSymbol{Delta}{\mathalpha}{\eu@GreekUppercase@symfont}{`Delta}[\Delta]
519     \eu@DeclareMathSymbol{Epsilon}{\mathalpha}{\eu@GreekUppercase@symfont}{`E}[\Epsilon]
520     \eu@DeclareMathSymbol{Zeta}{\mathalpha}{\eu@GreekUppercase@symfont}{`Z}[\Zeta]
521     \eu@DeclareMathSymbol{Eta}{\mathalpha}{\eu@GreekUppercase@symfont}{`H}[\Eta]
522     \eu@DeclareMathSymbol{Theta}{\mathalpha}{\eu@GreekUppercase@symfont}{`Theta}[\Theta]
523     \eu@DeclareMathSymbol{Iota}{\mathalpha}{\eu@GreekUppercase@symfont}{`I}[\Iota]
524     \eu@DeclareMathSymbol{Kappa}{\mathalpha}{\eu@GreekUppercase@symfont}{`K}[\Kappa]
525     \eu@DeclareMathSymbol{Lambda}{\mathalpha}{\eu@GreekUppercase@symfont}{`Lambda}[\Lambda]
526     \eu@DeclareMathSymbol{Mu}{\mathalpha}{\eu@GreekUppercase@symfont}{`M}[\Mu]
527     \eu@DeclareMathSymbol{Nu}{\mathalpha}{\eu@GreekUppercase@symfont}{`N}[\Nu]
528     \eu@DeclareMathSymbol{Xi}{\mathalpha}{\eu@GreekUppercase@symfont}{`Xi}[\Xi]
529     \eu@DeclareMathSymbol{Omicron}{\mathalpha}{\eu@GreekUppercase@symfont}{`O}[\Omicron]
530     \eu@DeclareMathSymbol{Pi}{\mathalpha}{\eu@GreekUppercase@symfont}{`Pi}[\Pi]
531     \eu@DeclareMathSymbol{Rho}{\mathalpha}{\eu@GreekUppercase@symfont}{`Rho}[\Rho]
532     \eu@DeclareMathSymbol{Sigma}{\mathalpha}{\eu@GreekUppercase@symfont}{`Sigma}[\Sigma]
533     \eu@DeclareMathSymbol{Tau}{\mathalpha}{\eu@GreekUppercase@symfont}{`Tau}[\Tau]
534     \eu@DeclareMathSymbol{Upsilon}{\mathalpha}{\eu@GreekUppercase@symfont}{`Y}[\Upsilon]
535     \eu@DeclareMathSymbol{Phi}{\mathalpha}{\eu@GreekUppercase@symfont}{`Phi}[\Phi]
536     \eu@DeclareMathSymbol{Chi}{\mathalpha}{\eu@GreekUppercase@symfont}{`X}[\Chi]
537     \eu@DeclareMathSymbol{Psi}{\mathalpha}{\eu@GreekUppercase@symfont}{`Psi}[\Psi]
538     \eu@DeclareMathSymbol{Omega}{\mathalpha}{\eu@GreekUppercase@symfont}{`Omega}[\Omega]
539     \eu@DeclareMathSymbol{varTheta}{\mathalpha}{\eu@GreekUppercase@symfont}{`3F4}[\varTheta]
540     \eu@DeclareMathSymbol{Digamma}{\mathalpha}{\eu@GreekUppercase@symfont}{`3DC}[\Digamma]
541   \fi}

```

Lowercase Greek.

```

542 \newcommand{\eu@DeclareGreekLowercase{
543   \if@eu@GreekLowercase@
544     \fontfamily{\eu@Greekmathsfont}\selectfont
545     \eu@DeclareMathSymbol{alpha}{\mathalpha}{\eu@GreekLowercase@symfont}{`alpha}[\alpha]
546     \eu@DeclareMathSymbol{beta}{\mathalpha}{\eu@GreekLowercase@symfont}{`beta}[\beta]
547     \eu@DeclareMathSymbol{gamma}{\mathalpha}{\eu@GreekLowercase@symfont}{`gamma}[\gamma]
548     \eu@DeclareMathSymbol{delta}{\mathalpha}{\eu@GreekLowercase@symfont}{`delta}[\delta]
549     \eu@DeclareMathSymbol{epsilon}{\mathalpha}{\eu@GreekLowercase@symfont}{`epsilon}[\epsilon]
550     \eu@DeclareMathSymbol{zeta}{\mathalpha}{\eu@GreekLowercase@symfont}{`zeta}[\zeta]
551     \eu@DeclareMathSymbol{eta}{\mathalpha}{\eu@GreekLowercase@symfont}{`eta}[\eta]
552     \eu@DeclareMathSymbol{theta}{\mathalpha}{\eu@GreekLowercase@symfont}{`theta}[\theta]
553     \eu@DeclareMathSymbol{iota}{\mathalpha}{\eu@GreekLowercase@symfont}{`iota}[\iota]
554     \eu@DeclareMathSymbol{kappa}{\mathalpha}{\eu@GreekLowercase@symfont}{`kappa}[\kappa]
555     \eu@DeclareMathSymbol{lambda}{\mathalpha}{\eu@GreekLowercase@symfont}{`lambda}[\lambda]
556     \eu@DeclareMathSymbol{mu}{\mathalpha}{\eu@GreekLowercase@symfont}{`mu}[\mu]
557     \eu@DeclareMathSymbol{nu}{\mathalpha}{\eu@GreekLowercase@symfont}{`nu}[\nu]
558     \eu@DeclareMathSymbol{xi}{\mathalpha}{\eu@GreekLowercase@symfont}{`xi}[\xi]
559     \eu@DeclareMathSymbol{omicron}{\mathalpha}{\eu@GreekLowercase@symfont}{`omicron}[\omicron]

```

```

560      \eu@DeclareMathSymbol{\pi}{\mathalpha}{\eu@GreekLowercase@symfont}{` \pi }[\pi]
561      \eu@DeclareMathSymbol{\rho}{\mathalpha}{\eu@GreekLowercase@symfont}{` \rho }[\rho]
562      \eu@DeclareMathSymbol{\sigma}{\mathalpha}{\eu@GreekLowercase@symfont}{` \sigma }[\sigma]
563      \eu@DeclareMathSymbol{\tau}{\mathalpha}{\eu@GreekLowercase@symfont}{` \tau }[\tau]
564      \eu@DeclareMathSymbol{\upsilon}{\mathalpha}{\eu@GreekLowercase@symfont}{` \upsilon }[\upsilon]
565      \eu@DeclareMathSymbol{\phi}{\mathalpha}{\eu@GreekLowercase@symfont}{` \phi }[\phi]
566      \eu@DeclareMathSymbol{\chi}{\mathalpha}{\eu@GreekLowercase@symfont}{` \chi }[\chi]
567      \eu@DeclareMathSymbol{\psi}{\mathalpha}{\eu@GreekLowercase@symfont}{` \psi }[\psi]
568      \eu@DeclareMathSymbol{\omega}{\mathalpha}{\eu@GreekLowercase@symfont}{` \omega }[\omega]
569      \eu@DeclareMathSymbol{\varsigma}{\mathalpha}{\eu@GreekLowercase@symfont}{` \varsigma }[\varsigma]
570      \eu@DeclareMathSymbol{\vartheta}{\mathalpha}{\eu@GreekLowercase@symfont}{` \vartheta }["3D0"][\vartheta]
571      \eu@DeclareMathSymbol{\varepsilon}{\mathalpha}{\eu@GreekLowercase@symfont}{` "3F5"}[\varepsilon]
572      \eu@DeclareMathSymbol{\vartheta}{\mathalpha}{\eu@GreekLowercase@symfont}{` "3D1"}[\vartheta]
573      \eu@DeclareMathSymbol{\varkappa}{\mathalpha}{\eu@GreekLowercase@symfont}{` "3F0"}[\varkappa]
574      \eu@DeclareMathSymbol{\varpi}{\mathalpha}{\eu@GreekLowercase@symfont}{` "3D6"}[\varpi]
575      \eu@DeclareMathSymbol{\varrho}{\mathalpha}{\eu@GreekLowercase@symfont}{` "3F1"}[\varrho]
576      \eu@DeclareMathSymbol{\varphi}{\mathalpha}{\eu@GreekLowercase@symfont}{` "3D5"}[\varphi]
577      \eu@DeclareMathSymbol{\digamma}{\mathalpha}{\eu@GreekLowercase@symfont}{` "3DD"}[\digamma]
578      \vfi}

    Symbols.

579 \newcommand\eu@DeclareSymbols{
580   \if@eu@Symbols@
581     \fontfamily\eu@Symbolsmathsfont\selectfont
582     \eu@DeclareMathSymbol{!}{\mathclose}{\eu@Symbols@symfont}{` ! }[\exclam]
583     \eu@DeclareMathSymbol{+}{\mathbin}{\eu@Symbols@symfont}{` + }[\plus]
584     \eu@DeclareMathSymbol{,}{\mathpunct}{\eu@Symbols@symfont}{` , }
585     \eu@DeclareMathSymbol{.}{\mathord}{\eu@Symbols@symfont}{` . }
586     \XeTeXmathchardef\ldotp=6\symSnn`.
587     \eu@DeclareMathSymbol{::}{\mathrel}{\eu@Symbols@symfont}{` ::}
588     \XeTeXmathchardef\colon=6\symSnn`:
589     \eu@DeclareMathSymbol{;}{\mathpunct}{\eu@Symbols@symfont}{` ; }[\semicolon]
590     \eu@DeclareMathSymbol{<}{\mathrel}{\eu@Symbols@symfont}{` < }[\less]
591     \DeclareMathSymbol{=}{\mathrel}{\eu@Symbols@symfont}{` =}
592       \let\eq==
593     \eu@DeclareMathSymbol{>}{\mathrel}{\eu@Symbols@symfont}{` > }[\greater]
594     \eu@DeclareMathSymbol{?}{\mathclose}{\eu@Symbols@symfont}{` ? }
595     \eu@DeclareMathSymbol{\neg}{\mathord}{\eu@Symbols@symfont}{` \neg }
596       \let\not\neg
597     \eu@DeclareMathSymbol{\circ}{\mathord}{\eu@Symbols@symfont}{` \circ }[\degree]
598     \eu@DeclareMathSymbol{\pm}{\mathbin}{\eu@Symbols@symfont}{` \pm }[\pm]
599     \eu@DeclareMathSymbol{\mu}{\mathord}{\eu@Symbols@symfont}{` \mu }[\micro]
600     \eu@DeclareMathSymbol{\times}{\mathbin}{\eu@Symbols@symfont}{` \times }[\times]
601     \eu@DeclareMathSymbol{\div}{\mathbin}{\eu@Symbols@symfont}{` \div }[\div]
602     \eu@DeclareMathSymbol{\forall}{\mathord}{\eu@Symbols@symfont}{` \forall }[\forall]
603     \eu@DeclareMathSymbol{\partial}{\mathord}{\eu@Symbols@symfont}{` \partial }[\partial]
604     \eu@DeclareMathSymbol{\exists}{\mathord}{\eu@Symbols@symfont}{` \exists }[\exists]
605     \eu@DeclareMathSymbol{\varnothing}{\mathord}{\eu@Symbols@symfont}{` \varnothing }[\varnothing]
606     \eu@DeclareMathSymbol{\Delta}{\mathord}{\eu@Symbols@symfont}{` \Delta }[\increment]
607     \eu@DeclareMathSymbol{\nabla}{\mathord}{\eu@Symbols@symfont}{` \nabla }[\nabla]
608     \eu@DeclareMathSymbol{\in}{\mathrel}{\eu@Symbols@symfont}{` \in }[\in]
609     \eu@DeclareMathSymbol{\notin}{\mathrel}{\eu@Symbols@symfont}{` \notin }[\notin]
610     \eu@DeclareMathSymbol{\ni}{\mathrel}{\eu@Symbols@symfont}{` \ni }[\ni]
611       \let\owns\ni
612     \eu@DeclareMathSymbol{-}{\mathbin}{\eu@Symbols@symfont}{` - }

```

```

613 \eu@DeclareMathSymbol{-}{\mathbin}{\eu@Symbols@symfont}{`-}[\minus]
614 \eu@DeclareMathSymbol{/}{\mathbin}{\eu@Symbols@symfont}{`/}[\slash]
615 \eu@DeclareMathSymbol{*}{\mathbin}{\eu@Symbols@symfont}{`*}[\ast]
616 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\ast]
617 \eu@DeclareMathSymbol{.}{\mathbin}{\eu@Symbols@symfont}{`·}[\vysmblkcircle]
618   \let\bullet\vysmblkcircle
619 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\propto]
620 \eu@DeclareMathSymbol{∞}{\mathord}{\eu@Symbols@symfont}{`∞}[\infty]
621 \eu@DeclareMathSymbol{L}{\mathord}{\eu@Symbols@symfont}{`L}[\rightangle]
622 \eu@DeclareMathSymbol{[]}{\mathord}{\eu@Symbols@symfont}{`[]}[\angle]
623 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\wedge]
624   \let\and\wedge
625 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\vee]
626   \let\or\vee
627 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\cap]
628 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\cup]
629 \eu@DeclareMathSymbol{[]}{\mathord}{\eu@Symbols@symfont}{`[]}[\therefore]
630 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\sim]
631 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\cong]
632 \eu@DeclareMathSymbol{≈}{\mathrel}{\eu@Symbols@symfont}{`≈}[\approx]
633 \eu@DeclareMathSymbol{≠}{\mathrel}{\eu@Symbols@symfont}{`≠}[\neq]
634   \let\neg\neq
635 \eu@DeclareMathSymbol{≡}{\mathrel}{\eu@Symbols@symfont}{`≡}[\equiv]
636 \eu@DeclareMathSymbol{≤}{\mathrel}{\eu@Symbols@symfont}{`≤}[\leq]
637   \let\leq\leq
638 \eu@DeclareMathSymbol{≥}{\mathrel}{\eu@Symbols@symfont}{`≥}[\geq]
639   \let\geq\geq
640 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\subset]
641 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\supset]
642 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\nsupset]
643   \let\notsubset\nsupset
644 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\subseteq]
645 \eu@DeclareMathSymbol{[]}{\mathrel}{\eu@Symbols@symfont}{`[]}[\supseteq]
646 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\oplus]
647 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\otimes]
648 \eu@DeclareMathSymbol{[]}{\mathord}{\eu@Symbols@symfont}{`[]}[\bot]
649   \let\perp\bot
650 \eu@DeclareMathSymbol{[]}{\mathbin}{\eu@Symbols@symfont}{`[]}[\cdotp]
651   \XeTeXmathchardef\cdotp=6\symSmn`·
652 \fi}

```

The main work.

```

653 \AtBeginDocument{
654   \if@eu@amsmathloaded@\else
655     \eu@isloaded[\PackageError{mathspec}{Package amsmath must be loaded before mathspec}{}]{amsmath}
656   \fi
657   \eu@DeclareFonts
658   \eu@ifnot@plaindigits{\eu@DeclareDigits}
659   \eu@DeclareLatinUppercase
660   \eu@DeclareLatinLowercase
661   \eu@DeclareGreekUppercase
662   \eu@DeclareGreekLowercase
663   \eu@DeclareSymbols
664   \eu@if@varforms{\eu@VarForms}

```

```

665 \eu@ifset@mathrm{
666   \DeclareMathAlphabet{\mathrm}{EU1}{\eu@mathrm}{m}{n}
667   \SetMathAlphabet{\mathrm}{bold}{EU1}{\eu@mathrm}{bx}{n}
668   \DeclareMathAlphabet{\mathit}{EU1}{\eu@mathrm}{m}{it}
669   \DeclareMathAlphabet{\mathbf}{EU1}{\eu@mathrm}{bx}{\eu@mathbf@shape}
670   \SetMathAlphabet{\mathit}{bold}{EU1}{\eu@mathrm}{bx}{it}
671   \@ifundefined{symLmn}{\relax}{\def\operator@font{\mathgroup\symLmn}}
672 \eu@ifset@mathcal{
673   \DeclareMathAlphabet{\mathcal}{EU1}{\eu@mathcal}{\eu@mathcal@series}{\eu@mathcal@shape}
674 \eu@ifset@mathsf{
675   \DeclareMathAlphabet{\mathsf}{EU1}{\eu@mathsf}{m}{n}
676   \SetMathAlphabet{\mathsf}{bold}{EU1}{\eu@mathsf}{bx}{n}
677 \eu@ifset@mathtt{
678   \DeclareMathAlphabet{\mathtt}{EU1}{\eu@mathtt}{m}{n}
679 \eu@ifset@mathfrak{
680   \DeclareMathAlphabet{\mathfrak}{EU1}{\eu@mathfrak}{\eu@mathfrak@series}{n}
681 \eu@ifset@mathbb{
682   \DeclareMathAlphabet{\mathbb}{EU1}{\eu@mathbb}{\eu@mathbb@series}{n}
683 \fontfamily\rmdefault\selectfont
684 \let\DeclareMathSymbol\LaTeXe@DeclareMathSymbol

```

INDEX

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\+	7, <u>196</u>	\cmChi 85 \cmchi 111 \cmDelta 67 \cmdelta 92
\Alpha	41, 64, <u>515</u>	\cmDigamma 88 \cmdigamma 114
\alpha	89, <u>545</u>	\cmEpsilon 68 \cmepsilon 93
\angle	622	\cmEta 70 \cmEta 95
\approx	632	\cmGamma 66 \cmgamma 91
\ast	616	\cmIota 72 \cmiota 97
		\cmKappa 73 \cmkappa 98
B		\cmLambda 74 \cmLambda 99
\Beta	42, 65, <u>516</u>	\cmMu 75 \cmmu 100
\beta	55, 90, <u>169</u> , 322, 546	\cmNu 76 \cmnu 101
\bot	648, 649	\cmOmega 87 \cmomega 113
\bullet	618	\cmOmicron 78 \cmomicron 103
		\cmPhi 84 \cmphi 110
C		\cmPi 79 \cmpi 104
\cap	627	\cmPsi 86 \cmpsi 112
\cdot	650	\cmRho 80 \cmrho 105
\cdotp	651	\cmSigma 81 \cmsigma 107
\Chi	53, 85, 536	\cmTau 82 \cmtau 108
\chi	111, 566	\cmUpsilon 83 \cmupsilon 109
\cmAlpha	64	\cmVarbeta 115, 168 \cmvarepsilon 116, 171
\cmalpha	89	\cmVarkappa 118, 177 \cmvarphi 121, 186
\cmBeta	65	\cmVarpi 119, 180 \cmvarrho 120, 183
\cmbeta	90	\cmVarsigma 106 \cmvartheta 122, 189
		\cmvartheta 117, 174 \cmXi 77

\cmxi	102	323, 326, 327,	\eu@GreekUppercase@symfont
\cmZeta	69	330, 331, 334,	285, 289, 515–540
\cmzeta	94	335, 338, 339,	\eu@GreekUppercase@value
\colon	588	342, 343, 346, 366
\cong	631	347, 350, 351,	\eu@if@Digits
\cup	628	384, 515–540,	428, 430, 435, 440
D			
\degree	597	545–577,	\eu@if@Greek 413–416, 421
\Delta	67, 518	582–585,	\eu@if@Latin 409–412, 417
\delta	92, 548	587, 589,	\eu@if@MnSymbol . 2, 6, 11
\Digamma .	61, 63, 88, 540	590, 593–595,	\eu@if@varforms
\digamma .	62, 63, 114, 577	597–610, 22, 197, 664
\div	601	612–617,	\eu@ifnot@normalskips
E			
\Epsilon ...	43, 68, 519	619–623, 1, 4, 29
\epsilon	93, 172, 327, 549	625, 627–633,	\eu@ifnot@plaindigits
\eq	592	635, 636, 192, 193, 658
\equiv	635	638, 640–642,	\eu@ifset@mathbb
\er@newcommand	128, 129, 131	644–648, 650 28, 225, 681
\ernewcommand	123, 198, 203,	\eu@DeclareMathSymbol@option	\eu@ifset@mathcal ..
	209, 213, 217, 393, 398 24, 206, 672
	222, 254, 259,	\eu@DeclareRobustCommand	\eu@ifset@mathfrak .
	264, 268, 273, 138, 196 27, 220, 679
	277, 285, 289,	\eu@DeclareSymbols .	\eu@ifset@mathrm ..
	294, 298, 303, 307 579, 663 23, 201, 665
\Eta	45, 70, 521	\eu@Digits@symfont .	\eu@ifset@mathsf ..
\eta	95, 551	431, 436, 442–451 25, 212, 674
\eu@@@DeclareMathSymbol	393, 395, 397	\eu@Digits@mathsf	\eu@ifset@mathhtt ..
	389, 399 432, 437, 441 26, 216, 677
\eu@@@character	390, 391	\eu@fontspec 137, 252, 283	\eu@isloaded ... 33, 655
\eu@@@DeclareMathSymbol	164, 165	\eu@GreekDigits@@value	\eu@LaTeXe@DeclareMathSymbol
	164, 166 302, 372 403, 407
\eu@@@newcommand	388, 400	\eu@GreekDigits@symfont	\eu@LatinDigits@@value
\eu@@@testopt ..	147, 148 303, 307, 431 272, 363
\eu@character .	147, 148	\eu@GreekDigits@value	\eu@LatinDigits@symfont
\eu@declare@robustcommand	427, 658 372 273, 277, 436
	408, 657	\eu@GreekLowercase@@value	\eu@LatinDigits@value
\eu@DeclareFonts	542, 662 293, 369 363
\eu@DeclareGreekLowercase	512, 661	\eu@GreekLowercase@symfont	\eu@LatinLowercase@@value
	482, 660 294, 263, 360
\eu@DeclareLatinLowercase	452, 659	298, 322, 323,	\eu@LatinLowercase@symfont
	452, 659	326, 327, 330,	264, 268, 485–510
\eu@DeclareMathSymbol	322,	331, 334, 335,	\eu@LatinLowercase@value
		338, 339, 342, 360
		343, 346, 347,	\eu@Latinmathsfont .
		350, 351, 545–577 255,
		\eu@GreekLowercase@value	260, 265, 269,
	 369	274, 278, 418,
		\eu@Greekmathsfont .	419, 437, 454, 484
	 286, 290,	\eu@LatinUppercase@@value
		295, 299, 304, 253, 357
		308, 319, 422,	\eu@LatinUppercase@symfont
		423, 432, 514, 544	254, 259, 455–480
		\eu@GreekUppercase@@value	\eu@LatinUppercase@value
	 284, 366 357
			\eu@mathbb 224, 682

\eu@mathbb@series ..	F	\le	637	
..... 226, 682	\forall	602	\leq	636, 637
\eu@mathbf@shape 202, 669	G	\less	590	
\eu@mathcal ... 205, 673	\Gamma	66, 517	\lnot	596
\eu@mathcal@series ..	\gamma	91, 547	\lor	626
..... 207, 673	\ge	639	M	
\eu@mathcal@shape ..	\geq	638, 639	\mathbb	682
..... 208, 673	\greater	593	\mathbf	669
\eu@mathfrak .. 219, 680	I	\mathcal	673	
\eu@mathfrak@series ..	\if@eu@amsmathloaded@	\mathfrak	680	
..... 221, 680 654	\mathit	668, 670	
\eu@mathrm . 200, 666–670	\if@eu@Digits@	\mathrel	587, 590, 591,	
\eu@mathsf . 211, 675, 676	\if@eu@GreekDigits@	593, 608–610,		
\eu@mathtt 215, 678 19, 416, 429	619, 630–633,		
\eu@new@command 163, 164	\if@eu@GreekLowercase@	635, 636, 638,		
\eu@ScopeSet@value 18, 415, 543	640–642, 644, 645		
..... 239, 354	\if@eu@GreekUppercase@	\mathrm	666, 667	
\eu@ScopeSet@Greek 17, 414, 513	\mathsf	675, 676	
..... 244, 281	\if@eu@LatinDigits@	\mathtt	678	
\eu@ScopeSet@Latin 16, 412, 434	\medmuskip	31	
..... 242, 250	\if@eu@LatinLowercase@	\micro	599	
\eu@ScopeSet@Special 15, 411, 483	\minus	613	
..... 240, 249	\if@eu@LatinUppercase@	\Mu	48, 75, 526	
\eu@ScopeSet@Symbols 14, 410, 453	\mu	100, 556	
..... 246, 311, 316	\if@eu@Symbols@	N		
\eu@ScopeSet@Value 20, 424, 580	\nabla	607	
..... 240,	\ifeu@VarForms@beta 321	\ne	634	
242, 244, 246, 248	\ifeu@VarForms@epsilon	\neg	595, 596	
\eu@ScopeSet@value .. 354 325	\neq	633, 634	
\eu@setkeys 132,	\ifeu@VarForms@kappa 333	\ni	610, 611	
238, 251, 282, 320	\ifeu@VarForms@phi 345	\normalvarforms .. 5, 167		
\eu@setmathsfont 194, 237	\ifeu@VarForms@pi 337	\notin	609	
\eu@Symbolssympfont .. 315	\ifeu@VarForms@rho 341	\notsubset	643	
\eu@Symbolssympfont ..	\ifeu@VarForms@Theta 349	\nsupset	642, 643	
582–585, 587, 589–591,	\ifeu@VarForms@theta 329	\Nu	49, 76, 527	
593–595, 597–610,	\in	\nu	101, 557	
612–617, 619–623,	608	O		
625, 627–633, 635,	\increment	\Omega	87, 538	
636, 638, 640–642,	606	\omega	113, 568	
644–648, 650	\infty	\Omicron .. 50, 78, 529		
\eu@Symbolssympfont ..	\Iota	\omicron .. 54, 103, 559		
314, 425, 581	46, 72, 523	\operator@font .. 257, 671		
\eu@VarForms .. 318, 664	\iota	\oplus	646	
\eu@XeTeXDeclareMathSymbol ..	97, 553	\otimes	647	
..... 382, 386	K	\owns	611	
\eu@zf@math 3, 7, 10	\Kappa	P		
\exclam	47, 73, 524	\partial	603	
\exists	\kappa	\perp	649	
\expanded .. 125, 136, 137	57,	\Phi	84, 535	
\expandonce 124, 136, 137	98, 178, 335, 554	\phi .. 110, 187, 347, 565		
	L			
	\Lambda			
	\lambda			
	\land			
	\LaTeXe@DeclareMathSymbol ..			
 402, 405, 684			
	\ldotp			

\Pi	79, 530	\slash	614	\varrho	120,
\pi ...	104, 181, 339, 560	\subset	640	\varsigma	106, 569
\plaindigits ...	3, 192	\subseteqq	644	\varTheta ...	59, 122,
\plus	583	\supset	641	\vartheta ...	189, 190, 350, 539
\pm	598	\supseteqq	645	\varthetaeta	117,
\proto	619	\symLmn	257, 671	\varthetaeta	174, 175, 330, 572
\Psi	86, 537	\symSmn ...	586, 588, 651	\vee	625, 626
\psi	112, 567	T		\vysmblkcircle	617, 618
R		\Tau	52, 82, 533		
\Rho	51, 80, 531	\tau	108, 563	W	
\rho ..	105, 184, 343, 561	\therefore	629	\wedge	623, 624
\rightangle	621	\Theta	59,		
\rmdefault	683	\theta	71, 190, 351, 522	X	
S		\theta .	96, 175, 331, 552	\XeTeXcharglyph	
\semicolon	589	\thickmuskip	32	385, 399, 404
\setmainfont	228	\thinmuskip	30	\XeTeXmathchardef	
\setmathbb	3, 198	\times	600	586, 588, 651
\setmathcal	3, 198	U		\XeTeXmathcode	383
\setmathfont	2, 195	\Upsilon	83, 534	\Xi	77, 528
\setmathfrak	3, 198	\upsilon	109, 564	\xi	102, 558
\setmathrm ..	3, 198, 230	V		Z	
\setmathsf ..	3, 198, 233	\varbeta ...	55, 115,	\Zeta	44, 69, 520
\setmathsf ..	2, 194, 229		168, 169, 323, 570	\zeta	94, 550
\setmathtt ..	3, 198, 236	\varepsilon	116,	\zf@family	
\setmonofont	235		171, 172, 326, 571	200, 205, 211,
\setmonofonts ...	4, 227	\varforms	5, 197	215, 219, 224,	
\setprimaryfont ..	4, 227	\varkappa ...	57, 118,	255, 260, 265,	
\setsansfont	232		177, 178, 334, 573	269, 274, 278,	
\setsansfonts ...	4, 227	\varnothing	605	286, 290, 295,	
\Sigma	81, 532	\varphi	121,	299, 304, 308, 314	
\sigma	107, 562		186, 187, 346, 576	\zf@fontspec ...	137,
\sim	630	\varpi	119,	199, 204, 210,	
			180, 181, 338, 574	214, 218, 223, 313	