



The XePersian *Package*

Documentation for version 18.9

to my Master, Ferdowsi The Great

If you want to report any bugs or typos and corrections in the documentation, or ask for any new features, or suggest any improvements, or ask any questions about the package, then please do not send any direct email to me; I will not answer any direct email. Instead please use the issue tracker:

<https://github.com/tex-xet/xepersian/issues>

In doing so, please always explain your issue well enough, always include a minimal working example showing the issue, and always choose the appropriate label for your query (i.e. if you are reporting any bugs, choose 'Bug' label).

Copyright (c) 2008–2017 Vafa Khalighi

Permission is granted to distribute and/or modify *both the documentation and the code* under the conditions of the L^AT_EX Project Public License, either version 1.3c of this license or (at your option) any later version.

The XePersian *Package*

Persian for \LaTeX _{2 ϵ} , using Xe \TeX engine

Documentation for [version 18.9](#)

Vafa Khalighi
persian-tex@tug.org

August 9, 2017

Contents

1	Introduction	4			
1.1	Important Notes	4			
1.2	XePersian Info On The Terminal and In The Log File	4			
2	Basics	5			
2.1	Loading The Package	5			
2.2	XePersian's Symbol	6			
2.3	Commands for Version number, and Date of The Package	6			
2.4	Options of The Package	6			
2.4.1	<code>defaultlatinfontfeatures</code> Option	6	2.6.1	Basic Font Commands	39
2.4.2	<code>extrafootnotefeatures</code> Option	7	2.6.2	Defining Extra Persian and Latin Fonts	39
2.4.3	Kashida Option	7	2.6.3	Choosing Persian Sans Font	40
2.4.4	<code>quickindex</code> Option	7	2.6.4	Choosing Persian Mono Font	40
2.4.5	<code>quickindex-variant1</code> Option	7	2.6.5	Choosing Persian Iranic Font	40
2.4.6	<code>quickindex-variant2</code> Option	7	2.6.6	Choosing Persian Navar Font	40
2.4.7	<code>localise</code> Option	8	2.6.7	Choosing Persian Pook Font	40
2.4.8	Localizations of the keys and key values of <code>graphicx</code> package	35	2.6.8	Choosing Persian Sayeh Font	40
2.4.9	Localizations of font features and font feature options	36	2.6.9	Choosing Latin Sans Font	40
2.5	A Sample Input \TeX File	38	2.6.10	Choosing Latin Mono Font	40
2.6	Font Commands	38	3	Latin and Persian Environment	41
			3.1	<code>latinitems</code> and <code>parsiitems</code> environments	41
			3.2	Short Latin and Persian Texts	41
			3.3	Miscellaneous Commands	41
			3.4	New Commands	42
			3.5	Additional Counters	42
			3.6	Things To Know About <code>\setdigitfont</code> , <code>\setmathsfdigitfont</code> , and <code>\setmathttdigitfont</code>	43

4	New Conditionals	43	7	xepersian implementation	55
4.1	Shell escape (or write18) conditional	43	7.1	algorithmic-xepersian.def	55
5	Bilingual Captions	43	7.2	algorithm-xepersian.def	56
5.1	Support For Various Packages	44	7.3	amsart-xepersian.def	56
5.1.1	Things You Should Know about Support For enumerate Package	44	7.4	amsbook-xepersian.def	56
5.2	Index Generation	44	7.5	appendix-xepersian.def	56
5.3	Converting Your FarsiT _E X Files To XePersian or Unicode	44	7.6	article-xepersian.def	56
6	Extra Packages And Classes	45	7.7	artikel1-xepersian.def	57
6.1	Magazine Typesetting	45	7.8	artikel2-xepersian.def	57
6.1.1	Introduction	45	7.9	artikel3-xepersian.def	57
6.1.2	Usage	45	7.10	backref-xepersian.def	57
6.1.3	Front Page	45	7.11	bidituftesidenote-xepersian.def	58
6.1.4	Inside	47	7.12	bidimoderncv-xepersian.def . . .	58
6.1.5	The article environment	47	7.13	boek3-xepersian.def	58
6.1.6	The editorial environment	48	7.14	boek-xepersian.def	58
6.1.7	The shortarticle environment	49	7.15	bookest-xepersian.def	58
6.1.8	Commands between articles	49	7.16	book-xepersian.def	59
6.1.9	Customization	49	7.17	breqn-xepersian.def	59
6.1.10	Front Page	50	7.18	latex-localise-commands-xepersian.def	60
6.1.11	Inside The Magazine	51	7.19	color-localise-xepersian.def . . .	79
6.1.12	Class Options	52	7.20	xepersian-localise-commands-xepersian.def	79
6.2	Typesetting Multiple-choice Questions	52	7.21	enumerate-xepersian.def	80
6.2.1	Introduction	52	7.22	latex-localise-environments-xepersian.def	81
6.2.2	Usage	53	7.23	xepersian-localise-environments-xepersian.def	82
6.2.3	Loading The Package	53	7.24	extarticle-xepersian.def	82
6.2.4	Creating Questions	53	7.25	extbook-xepersian.def	82
6.2.5	The question Environment	53	7.26	extrafootnotefeatures-xepersian.def	82
6.2.6	Question Numbers	53	7.27	extreport-xepersian.def	82
6.2.7	The Form and the Mask	54	7.28	flowfram-xepersian.def	83
6.2.8	Typesetting corrections	54	7.29	footnote-xepersian.def	83
6.2.9	Important Note	54	7.30	framed-xepersian.def	83
6.3	Customising The Package	54	7.31	glossaries-xepersian.def	84
6.3.1	The question environment	55	7.32	hyperref-xepersian.def	84
6.3.2	The Form and the Mask	55	7.33	imsproc-xepersian.def	85
6.3.3	The correction	55	7.34	kashida-xepersian.def	85
			7.35	listings-xepersian.def	86
			7.36	loadingorder-xepersian.def . . .	86
			7.37	localise-xepersian.def	87
			7.38	memoir-xepersian.def	88
			7.39	latex-localise-messages-xepersian.def	89
			7.40	minitoc-xepersian.def	89
			7.41	latex-localise-misc-xepersian.def	89
			7.42	natbib-xepersian.def	96
			7.43	packages-localise-xepersian.def	101



7.44	parsidigits.map	104	7.53	tkz-linknodes-xepersian.def . . .	107
7.45	rapport1-xepersian.def	105	7.54	tocloft-xepersian.def	108
7.46	rapport3-xepersian.def	105	7.55	xepersian.sty	108
7.47	refrep-xepersian.def	105	7.56	xepersian-magazine.cls	127
7.48	report-xepersian.def	105	7.57	xepersian-mathsdigitspec.sty . .	144
7.49	scrartcl-xepersian.def	105	7.58	xepersian-multiplechoice.sty . .	149
7.50	scrbook-xepersian.def	106	7.59	xepersian-persiancal.sty	151
7.51	scrreprt-xepersian.def	107			
7.52	soul-xepersian.def	107	8	Change History	188



1 Introduction

XePersian is a package for typesetting Persian/English documents with Xe \LaTeX . The package includes adaptations for use with many other commonly-used packages.

1.1 Important Notes

- ☞ The XePersian package only works with Xe \TeX engine.
- ☞ Before reading this documentation, you should have read the documentation of the bidi package. The XePersian package automatically loads bidi package with `RTLdocument` option enabled and hence any commands that bidi package offers, is also available in XePersian package. Here, in this documentation, we will not repeat any of bidi package's commands.
- ☞ In previous versions ($\leq 1.0.3$) of XePersian, a thesis class provided for typesetting thesis. As of version 1.0.4, we no longer provide this class because we are not familiar with specification of a thesis in Iran and even if we were, the specifications are different from University to University. XePersian is a general package like \LaTeX and should not provide any class for typesetting thesis. So if you really want to have a class file for typesetting thesis, then you should ask your University/department to write one for you.

1.2 XePersian Info On The Terminal and In The Log File

If you use XePersian package to write any input \TeX document, and then run `xelatex` on your document, in addition to what bidi package writes to the terminal and to the log file, the XePersian package also writes some information about itself to the terminal and to the log file, too. The information is something like:

```
*****
*
* xepersian package (Persian for LaTeX, using XeTeX engine)
*
* Description: The package supports Persian
* typesetting, using fonts provided in the
* distribution.
*
* Copyright (c) 2008--2017 Vafa Khalighi
*
* v18.9, 2017/08/09
*
* License: LaTeX Project Public License, version
* 1.3c or higher (your choice)
*
* Location on CTAN: /macros/xetex/latex/xepersian
*
* Issue tracker: https://github.com/tex-xet/xepersian/issues
```



```
*
* Support: persian-tex@tug.org
*
*****
```

2 Basics

2.1 Loading The Package

You can load the package in the ordinary way;

```
\usepackage [Options] {xepersian}
```

Where options of the package are explained later in [subsection 2.4](#).
When loading the package, it is important to know that:

- ❶ xepersian should be the last package that you load, because otherwise you are certainly going to overwrite bidi and XePersian package's definitions and consequently, you will not get the expected output.
- ❷ In fact, in addition to bidi, XePersian also makes sure that some specific packages are loaded before bidi and XePersian; these are those packages that bidi and XePersian modifies them for bidirectional and Persian/English typesetting. If you load XePersian before any of these packages, then you will get an error saying that you should load XePersian or bidi as your last package. When it says that you should load bidi package as your last package, it really means that you should load XePersian as your last package as bidi package is loaded automatically by XePersian package.

For instance, consider the following minimal example:

```
1 \documentclass{minimal}
2 \usepackage{xepersian}
3 \usepackage{enumerate}
4 \settextfont{XB Niloofar}
5 \begin{document}
6 این فقط یک آزمایش است
7 \end{document}
```

Where enumerate is loaded after XePersian. If you run xelatex on this document, you will get an error which looks like this:

```
! Package xepersian Error: Oops! you have loaded package enumerate
after xepersian package. Please load package enumerate before
xepersian package, and then try to run xelatex on your document
again.
```

See the xepersian package documentation for explanation.



```
Type H <return> for immediate help.
...

1.5 \begin{document}

?
```

2.2 XePersian's Symbol

As you may know lion symbolizes T_EX but lion does not symbolizes XePersian. **Simorgh**¹ (shown on the first page of this documentation) symbolizes XePersian.

2.3 Commands for Version number, and Date of The Package

```
\xepersianversion \xepersiandate
```

☞ \xepersianversion gives the current version of the package.

☞ \xepersiandate gives the current date of the package.

```
1 \documentclass{article}
2 \usepackage{xepersian}
3 \settextfont{XB Niloofar}
4 \begin{document}
5 \begin{latin}
6 This is typeset by \textsf{\XePersian} package, \xepersianversion,
7 \xepersiandate.
8 \end{latin}
9 \end{document}
```

2.4 Options of The Package

There are few options:

2.4.1 defaultlatinfontfeatures Option

```
defaultlatinfontfeatures=<value>
```

The defaultlatinfontfeatures option allows you to pass font features to the main Latin font. <value> is a set of font features.

¹Simorgh is an Iranian benevolent, mythical flying creature which has been shown on the titlepage of this documentation. For more details see <http://en.wikipedia.org/wiki/Simurgh>



2.4.2 extrafootnotefeatures Option

This is just the `extrafootnotefeatures` Option of `bidi` package. If you enable this option, you can typeset footnotes in paragraph form or in multi-columns (from two-columns to ten-columns). For more details, please read the manual of `bidi` package.

2.4.3 Kashida Option

If you pass `Kashida` option to the package, you will use `Kashida` for stretching words for better output quality and getting rid of underfull or overfull `\hbox` messages. Note that you can not use `Kashida` option when you are using `Nastaliq`-like font (well, you still can use `Kashida` option when you use any `Nastaliq`-like font, but I can not guarantee high quality output!).

The following two commands are provided when you activate the `Kashida` option:

`\KashidaOn` `\KashidaOff`

☞ `\KashidaOn` enables `Kashida` and is active by default when `Kashida` option is activated.

☞ `\KashidaOff` disables `Kashida`.

2.4.4 quickindex Option

When you generally want to prepare index for your Persian documents, you need to first run `xelatex`, then `xindy`, and again `xelatex` on your document respectively, which is very time consuming. The `quickindex` option gives you the index with only and only one run of `xelatex`. To use this feature, you will need to run `xelatex --shell-escape` on your `TEX` document; otherwise you get an error which indicates that `shell scape` (or `write18`) is not enabled.

This option is now obsolete and equivalent to `quickindex-variant2` option.

2.4.5 quickindex-variant1 Option

Same as `quickindex` Option but uses variant one (in which `ĩ` is grouped under `l`) for sorting Persian alphabets.

2.4.6 quickindex-variant2 Option

Same as `quickindex` Option but uses variant two (in which `ĩ` is a separate letter) for sorting Persian alphabets.



2.4.7 localise Option

This option allows you to use most frequently-used \LaTeX commands and environments in Persian, almost like what \TeX -e-Parsi offers. This is still work in progress and we wish to add lots more Persian equivalents of \LaTeX and \TeX commands and environments. The Persian equivalents of \LaTeX and \TeX commands are shown in [Table 1](#), The Persian equivalents of XePersian commands are shown in [Table 2](#), Persian equivalents of \LaTeX environments are shown in [Table 3](#) and Persian equivalents of XePersian environments are shown in [Table 4](#).

Please note that the Persian equivalents of \LaTeX and \TeX commands and environments are only available after loading xepersian package. This means that you have to write all commands or environments that come before `\usepackage{xepersian}`, in its original form, i.e. `\documentclass`.

Not only you can use Persian equivalents of \LaTeX and \TeX commands and environments, but still original \LaTeX and \TeX commands and environments work too.

The \TeX , \LaTeX and XePersian commands and environments and their Persian equivalents listed in [Table 1](#), [Table 2](#), [Table 3](#) and [Table 4](#) is not the whole story; If any command and environment in [Table 1](#), [Table 2](#), [Table 3](#) and [Table 4](#) have a starred version, their starred version also work. For example in [Table 1](#), the Persian equivalent of `\chapter` is `فصل`. I know that `\chapter` has a starred version, so this means `*فصل` is also the Persian equivalent of `\chapter*`. Is that clear?

However there is more; you can localise any other commands/environments you want. You can use the following commands to localise your own commands/environments:

```
\eqcommand{<command-name in Persian>}{<original LaTeX command-name>}
\eqenvironment{<environment-name in Persian>}{<original LaTeX environment-name>}
```

Table 1: The Equivalent \LaTeX and \TeX Commands

Command in \TeX or \LaTeX	Equivalent Persian Command
<code>\@arstrut</code>	شمع جدول
<code>\above</code>	فوق
<code>\abovedisplayshortskip</code>	فاصله کوتاه بالای نمایش
<code>\abovedisplayskip</code>	فاصله بالای نمایش
<code>\abstractname</code>	عنوان چکیده
<code>\accent</code>	اکسنت
<code>\active</code>	فعال
<code>\addcontentsline</code>	بیفزاسطر فهرست
<code>\addpenalty</code>	اضافه بر جریمه
<code>\address</code>	نشانی
<code>\addtocontents</code>	بیفزابه فهرست
<code>\addtocounter</code>	اضافه بر شمارنده
<code>\addtolength</code>	اضافه بر بعد

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\addvspace</code>	<code>\بیفزافضای و</code>
<code>\adjdemerits</code>	<code>\تنظیم بدنمایی</code>
<code>\advance</code>	<code>\بیفزابر</code>
<code>\afterassignment</code>	<code>\بعد از انتساب</code>
<code>\aftergroup</code>	<code>\بعد از گروه</code>
<code>\aleph</code>	<code>\الف</code>
<code>\aliasfontfeature</code>	<code>\خصیصه مستعار قلم</code>
<code>\aliasfontfeatureoption</code>	<code>\انتخاب خصیصه مستعار قلم</code>
<code>\allowbreak</code>	<code>\شکستی</code>
<code>\alloc@</code>	<code>\تخصی @</code>
<code>\allocationnumber</code>	<code>\تخصیص یافته</code>
<code>\allowdisplaybreaks</code>	<code>\شکست نمایش مجاز</code>
<code>\Alph</code>	<code>\حروف بزرگ</code>
<code>\alph</code>	<code>\حروف کوچک</code>
<code>\alsiname</code>	<code>\نام همچنین</code>
<code>\and</code>	<code>\و</code>
<code>\angle</code>	<code>\زاویه</code>
<code>\appendixname</code>	<code>\عنوان پیوست</code>
<code>\approx</code>	<code>\تقریب</code>
<code>\arabic</code>	<code>\عربی</code>
<code>\arg</code>	<code>\آرگ</code>
<code>\arrayrulecolor</code>	<code>\رنگ خط جدول</code>
<code>\arraycolsep</code>	<code>\فاصله ستونهای آرایه</code>
<code>\arrayrulewidth</code>	<code>\ضخامت خط جدول</code>
<code>\arraystretch</code>	<code>\کشیدگی آرایه</code>
<code>\AtBeginDocument</code>	<code>\در آغاز نوشتار</code>
<code>\AtEndDocument</code>	<code>\در پایان نوشتار</code>
<code>\AtEndOfClass</code>	<code>\در انتهای طبقه</code>
<code>\AtEndOfPackage</code>	<code>\در انتهای سبک</code>
<code>\author</code>	<code>\نویسنده</code>
<code>\backmatter</code>	<code>\مطلب پشت</code>
<code>\backslash</code>	<code>\شکاف پشت</code>
<code>\badness</code>	<code>\بدنمایی</code>
<code>\bar</code>	<code>\میله</code>
<code>\baselineskip</code>	<code>\فاصله کرسی</code>
<code>\baselinestretch</code>	<code>\کشش فاصله کرسی</code>
<code>\batchmode</code>	<code>\پردازش دسته ای</code>
<code>\begin</code>	<code>\شروع</code>
<code>\beginL</code>	<code>\شروع چپ</code>
<code>\beginR</code>	<code>\شروع راست</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
\begingroup	\شروع گروه
\belowdisplayshortskip	\فاصله کوتاه پایین نمایش
\belowdisplayskip	\فاصله پایین نمایش
\bf	\سیاه
\bfdefault	\پیش فرض سیاه
\bfseries	\شمايل سیاه
\bgroup	\شرگروه
\bibitem	\مرجع
\bibliography	\کتاب نامه
\bibliographystyle	\سبک کتاب نامه
\bibname	\عنوان کتاب نامه
\bigskip	\پرش بلند
\bigskipamount	\مقدار پرش بلند
\botfigrule	\خط پایین شناور
\botmark	\علامت پایین
\bottompageskip	\کادر تا پایین
\bottomfraction	\نسبت پایین
\box	\کادر
\boxmaxdepth	\حد اکثر عمق کادر
\break	\بشکن
\bullet	\گلوله
\@cclv	\دوپن @ پنج
\@cclvi	\دوپن @ شش
\caption	\شرح
\catcode	\کدرده
\cc	\رونوشت
\ccname	\نام رونوشت
\cdot	\نقطه وسط
\cdots	\نقاط وسط
\centering	\تنظیم از وسط
\centerline	\خط وسط
\ch@ck	\چک @ ن
\chapter	\فصل
\chaptername	\عنوان فصل
\char	\نویسه
\chardef	\تعریف نویسه
\CheckCommand	\برسی فرمان
\cite	\مرجع
\ClassError	\خطای طبقه
\ClassInfo	\اطلاع طبقه

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
\ClassWarning	\هشدارطبقه
\ClassWarningNoLine	\هشدارطبقه بی سطر
\cleaders	\نشانگرمرکزی
\cleardoublepage	\دو صفحه پاک
\clearpage	\صفحه پاک
\cline	\خط ناپر
\closein	\ببندورودی
\closeout	\ببندخروجی
\closing	\بستن
\clubpenalty	\جریمه سربند
\clubsuit	\خاج
\colbotmark	\علامت پایین ستون اول
\colfirstmark	\علامت اول ستون اول
\color	\رنگ
\colorbox	\کادررنگ
\coltopmark	\علامت بالای ستون اول
\columncolor	\رنگ ستون
\columnsep	\بین ستون
\columnwidth	\پهنای ستون
\columnseprule	\خط بین ستون
\contentsline	\سطرفهرست
\contentsname	\عنوان فهرست مطالب
\copy	\کپی
\copyright	\حق تالیف
\count	\شمار
\count@	\شمار@
\countdef	\تعریف شمار
\cr	\سخ
\crrc	\سخ سخ
\csname	\نام فرمان
\CurrentOption	\گزینه جاری
\dashbox	\کادر بینابین
\dashv	\بینابین ع
\@date	\@تاریخ
\date	\تاریخ
\day	\روز
\dblbotfigrule	\خط پایین شناورپهن
\dblbottomfraction	\نسبت پهن پایین
\dblfigrule	\خط بالای شناورپهن
\dblfloatpagefraction	\نسبت صفحه شناورپهن

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\dblfloatsep</code>	\فاصله بین شناور پهن
<code>\dblftntlocatecode</code>	\کدامکان غیرهمانطور
<code>\dbltextfloatsep</code>	\فاصله متن و شناور پهن
<code>\dbltopfraction</code>	\نسبت پهن بالا
<code>\DeclareFixedFont</code>	\اعلان قلم ثابت
<code>\DeclareGraphicsExtensions</code>	\اعلان پسوند گرافیک
<code>\DeclareGraphicsRule</code>	\اعلان دستور گرافیک
<code>\DeclareOldFontCommand</code>	\اعلان فرمان قلم قدیمی
<code>\DeclareOption</code>	\اعلان گزینه
<code>\DeclareRobustCommand</code>	\اعلان فرمان قوی
<code>\DeclareSymbolFont</code>	\اعلان قلم علائم
<code>\deadcycles</code>	\دور بسته
<code>\def</code>	\تر
<code>\define@key</code>	\تعریف @کلید
<code>\definecolor</code>	\تعریف رنگ
<code>\deg</code>	\درجه
<code>\delcode</code>	\کد جداساز
<code>\delimiter</code>	\جداساز
<code>\delimiterfactor</code>	\ضریب جداساز
<code>\depth</code>	\گودی
<code>\diamondsuit</code>	\خشت
<code>\dim</code>	\ابعاد
<code>\dimen</code>	\بعد
<code>\dimen@</code>	\بعد @
<code>\dimen@i</code>	\بعد @یک
<code>\dimen@ii</code>	\بعد @دو
<code>\dimendef</code>	\تعریف بعد
<code>\discretionary</code>	\تیره گذاری
<code>\displaybreak</code>	\شکست نمایش
<code>\displayindent</code>	\تورفتگی نمایش
<code>\displaystyle</code>	\سبک نمایش
<code>\displaywidth</code>	\عرض نمایش
<code>\divide</code>	\تقسیم
<code>\documentclass</code>	\طبقه نوشتار
<code>\do</code>	\کن
<code>\dospecials</code>	\تعویض کدها
<code>\dot</code>	\نقطه
<code>\doteq</code>	\نقطه مساوی
<code>\dotfill</code>	\پر نقطه
<code>\dots</code>	\نقاط

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\doublebox</code>	<code>\کادر دولا</code>
<code>\doublerulesepcolor</code>	<code>\رنگ فاصله دو خط جدول</code>
<code>\doublerulesep</code>	<code>\فاصله بین دو خط</code>
<code>\downarrow</code>	<code>\فلش پایین</code>
<code>\dp</code>	<code>\عمق</code>
<code>\dump</code>	<code>\تخلیه</code>
<code>\edef</code>	<code>\ترگ</code>
<code>\egroup</code>	<code>\پا گروه</code>
<code>\eject</code>	<code>\انتهای فاصله</code>
<code>\else</code>	<code>\گرنه</code>
<code>\em</code>	<code>\تاکید</code>
<code>\emergencystretch</code>	<code>\کشش لاجرم</code>
<code>\emph</code>	<code>\موکد</code>
<code>\@empty</code>	<code>\@پوچ</code>
<code>\empty</code>	<code>\پوچ</code>
<code>\emptyset</code>	<code>\مجموعه پوچ</code>
<code>\end</code>	<code>\پایان</code>
<code>\endL</code>	<code>\پایان چپ</code>
<code>\endR</code>	<code>\پایان راست</code>
<code>\endcsname</code>	<code>\پایان نام فرمان</code>
<code>\endfirsthead</code>	<code>\پایان اولین سر</code>
<code>\endfoot</code>	<code>\پایان پا</code>
<code>\endgraf</code>	<code>\ته بند</code>
<code>\endgroup</code>	<code>\پایان گروه</code>
<code>\endhead</code>	<code>\پایان سر</code>
<code>\endinput</code>	<code>\پایان ورودی</code>
<code>\endlastfoot</code>	<code>\پایان آخرین پا</code>
<code>\enlargethispage</code>	<code>\گسترش این صفحه</code>
<code>\endline</code>	<code>\ته سطر</code>
<code>\endlinechar</code>	<code>\نویسه ته سطر</code>
<code>\enspace</code>	<code>\ان دوری</code>
<code>\enskip</code>	<code>\ان فاصله</code>
<code>\eqcommand</code>	<code>\فرمان جانشین</code>
<code>\eqenvironment</code>	<code>\محیط جانشین</code>
<code>\eqref</code>	<code>\ارجاع فر</code>
<code>\errhelp</code>	<code>\کمک خطا</code>
<code>\errmessage</code>	<code>\پیام خطا</code>
<code>\errorcontextlines</code>	<code>\سطر متن خطا</code>
<code>\errorstopmode</code>	<code>\پردازش توقف خطا</code>
<code>\escapechar</code>	<code>\نویسه ویژه</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\euro</code>	<code>\یورو</code>
<code>\evensidemargin</code>	<code>\حاشیه زوج</code>
<code>\everycr</code>	<code>\هرسخ</code>
<code>\everydisplay</code>	<code>\هرنمایش</code>
<code>\everyhbox</code>	<code>\هرکادرا</code>
<code>\everyjob</code>	<code>\هرکار</code>
<code>\everymath</code>	<code>\هرریاضی</code>
<code>\everypar</code>	<code>\هربند</code>
<code>\everyvbox</code>	<code>\هرکادرو</code>
<code>\ExecuteOptions</code>	<code>\اجرای گزینه ها</code>
<code>\exhyphenpenalty</code>	<code>\جریمه اضافی تیره بندی</code>
<code>\expandafter</code>	<code>\بگستر پس از</code>
<code>\extracolsep</code>	<code>\فاصله اضافی بین ستونها</code>
<code>\@firstofone</code>	<code>\@اولی از یک</code>
<code>\@firstoftwo</code>	<code>\@اولی از دو</code>
<code>\f@ur</code>	<code>\چ@ار</code>
<code>\fam</code>	<code>\خانواده</code>
<code>\fancy page</code>	<code>\صفحه تجملی</code>
<code>\fbox</code>	<code>\کادر با</code>
<code>\fboxrule</code>	<code>\ضخامت کادر با</code>
<code>\fboxsep</code>	<code>\حاشیه کادر با</code>
<code>\fcolorbox</code>	<code>\کادر با رنگ</code>
<code>\fi</code>	<code>\رگ</code>
<code>\figurename</code>	<code>\عنوان شکل</code>
<code>\filbreak</code>	<code>\پرشکن</code>
<code>\fill</code>	<code>\پر</code>
<code>\firstmark</code>	<code>\علامت اول</code>
<code>\flat</code>	<code>\پهن</code>
<code>\floatpagefraction</code>	<code>\نسبت صفحه شناور</code>
<code>\floatingpenalty</code>	<code>\جریمه شناور</code>
<code>\floatsep</code>	<code>\فاصله بین شناور</code>
<code>\flushbottom</code>	<code>\تنظیم از پایین</code>
<code>\fmtname</code>	<code>\شکل بندی</code>
<code>\fmtversion</code>	<code>\رده شکل بندی</code>
<code>\fnsymbol</code>	<code>\نشانه</code>
<code>\font</code>	<code>\قلم</code>
<code>\fontdimen</code>	<code>\بعد قلم</code>
<code>\fontencoding</code>	<code>\رمزینه قلم</code>
<code>\fontfamily</code>	<code>\فامیل قلم</code>
<code>\fontname</code>	<code>\نام قلم</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\fontseries</code>	<code>\شمايل قلم</code>
<code>\fontshape</code>	<code>\شكل قلم</code>
<code>\fontsize</code>	<code>\اندازه قلم</code>
<code>\footheight</code>	<code>\بلنداي پايين صفحه</code>
<code>\footins</code>	<code>\درج زيرويس</code>
<code>\footnote</code>	<code>\زيرويس</code>
<code>\footnotemark</code>	<code>\علامت زيرويس</code>
<code>\footnoterule</code>	<code>\خط زيرويس</code>
<code>\footnotesep</code>	<code>\فاصله تازيرويس</code>
<code>\footnotesize</code>	<code>\اندازه زيرويس</code>
<code>\footnotetext</code>	<code>\متن زيرويس</code>
<code>\footskip</code>	<code>\فاصله تا پايين صفحه</code>
<code>\frame</code>	<code>\فريم</code>
<code>\framebox</code>	<code>\كادر با خط</code>
<code>\frenchspacing</code>	<code>\فواصل يكنواخت لاتين</code>
<code>\frontmatter</code>	<code>\مطلب پيش</code>
<code>\futurelet</code>	<code>\بعد بگذار</code>
<code>\@gobble</code>	<code>\@خورخري صانه</code>
<code>\@gobbletwo</code>	<code>\@خورخري صانه دو</code>
<code>\@gobblefour</code>	<code>\@خورخري صانه چهار</code>
<code>\@gtempa</code>	<code>\@عاقبت آ</code>
<code>\@gtempb</code>	<code>\@عاقبت ب</code>
<code>\gdef</code>	<code>\ترع</code>
<code>\GenericInfo</code>	<code>\الگوی اطلاع</code>
<code>\GenericWarning</code>	<code>\الگوی هشدار</code>
<code>\GenericError</code>	<code>\الگوی خطا</code>
<code>\global</code>	<code>\عام</code>
<code>\globaldefs</code>	<code>\تعريف عام</code>
<code>\glossary</code>	<code>\لغت نامه</code>
<code>\glossaryentry</code>	<code>\فقره فرهنگ</code>
<code>\goodbreak</code>	<code>\خوش شكن</code>
<code>\graphpaper</code>	<code>\كاغذگراف</code>
<code>\guillemotleft</code>	<code>\گيومه چپ</code>
<code>\guillemotright</code>	<code>\گيومه راست</code>
<code>\guilsinglleft</code>	<code>\گيومه تكي چپ</code>
<code>\guilsinglright</code>	<code>\گيومه تكي راست</code>
<code>\halign</code>	<code>\رديف ا</code>
<code>\hang</code>	<code>\بروتو</code>
<code>\hangafter</code>	<code>\بعد از سطر</code>
<code>\hangindent</code>	<code>\تورفتگی ثابت</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\hbadness</code>	<code>\بدنمایی</code>
<code>\hbox</code>	<code>\کادرا</code>
<code>\headheight</code>	<code>\بلندای سرصفحه</code>
<code>\headsep</code>	<code>\فاصله از سرصفحه</code>
<code>\headtoname</code>	<code>\سربه نام</code>
<code>\heartsuit</code>	<code>\دل</code>
<code>\height</code>	<code>\بلندا</code>
<code>\hfil</code>	<code>\پرا</code>
<code>\hfill</code>	<code>\پرا</code>
<code>\hfilneg</code>	<code>\رفع پرا</code>
<code>\hfuzz</code>	<code>\پرزاقفی</code>
<code>\hideskip</code>	<code>\فاصله مخفی</code>
<code>\hidewidth</code>	<code>\عرض پنهان</code>
<code>\hline</code>	<code>\خط پر</code>
<code>\hoffset</code>	<code>\حاشیه</code>
<code>\holdinginserts</code>	<code>\حفظ درج</code>
<code>\hrboxsep</code>	<code>\فاصله اگر</code>
<code>\hrule</code>	<code>\خط</code>
<code>\hrulefill</code>	<code>\پرخط</code>
<code>\hsize</code>	<code>\طول سطر</code>
<code>\hskip</code>	<code>\فاصله</code>
<code>\hspace</code>	<code>\فضای</code>
<code>\hss</code>	<code>\هردوا</code>
<code>\ht</code>	<code>\ارتفاع</code>
<code>\huge</code>	<code>\بزرگ</code>
<code>\Huge</code>	<code>\بزرگ تر</code>
<code>\hyperlink</code>	<code>\ابر پیوند</code>
<code>\hypersetup</code>	<code>\بارگذاری ابر</code>
<code>\hypertarget</code>	<code>\هدف ابر</code>
<code>\hyphenation</code>	<code>\تیره بندی</code>
<code>\hyphenchar</code>	<code>\نویسه تیره</code>
<code>\hyphenpenalty</code>	<code>\جریمه تیره بندی</code>
<code>\@ifclassloaded</code>	<code>\@گرکلاس فراخوانی شده</code>
<code>\@ifdefinable</code>	<code>\@گرترشدنی</code>
<code>\@ifnextchar</code>	<code>\@گرنویسه بعدی</code>
<code>\@ifpackageloaded</code>	<code>\@گرسبک فراخوانی شده</code>
<code>\@ifstar</code>	<code>\@گرستاره</code>
<code>\@ifundefined</code>	<code>\@گرتعریف نشده</code>
<code>\if</code>	<code>\گر</code>
<code>\if@tempswa</code>	<code>\گر@سواقت آ</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\ifcase</code>	\گرا نواع
<code>\ifcat</code>	\گر رده
<code>\ifdefined</code>	\گر تعریف شده
<code>\ifdim</code>	\گر بعد
<code>\ifeof</code>	\گر ته پرونده
<code>\iff</code>	\گر ر
<code>\iffalse</code>	\گر نادرست
<code>\IfFileExists</code>	\گر پرونده موجود
<code>\ifhbox</code>	\گر کا در ا
<code>\ifhmode</code>	\گر حالت ا
<code>\ifinner</code>	\گر درونی
<code>\ifmmode</code>	\گر حالت ریاضی
<code>\ifnum</code>	\گر عدد
<code>\ifodd</code>	\گر فرد
<code>\ifthenelse</code>	\گر آنگاه دیگر
<code>\iftrue</code>	\گر درست
<code>\ifvbox</code>	\گر کا در و
<code>\ifvmode</code>	\گر حالت و
<code>\ifvoid</code>	\گر تهی
<code>\ifx</code>	\گر نام
<code>\ignorespaces</code>	\فاصله خالی را ندیده بگیر
<code>\immediate</code>	\فوری
<code>\include</code>	\شامل
<code>\includegraphics</code>	\درج تصویر
<code>\includeonly</code>	\مشمولین
<code>\indent</code>	\تورفتگی
<code>\index</code>	\درنمایه
<code>\indexentry</code>	\استعلام
<code>\indexname</code>	\عنوان نمایه
<code>\indexspace</code>	\فاصله رهنما
<code>\input</code>	\ورودی
<code>\InputIfFileExists</code>	\ورود پرونده گر موجود
<code>\inputlineno</code>	\شماره سطر ورودی
<code>\insert</code>	\درج
<code>\insertpenalties</code>	\جریمه درج
<code>\interfootnotelinepenalty</code>	\جریمه بین سطرهای زیرنویس
<code>\interdisplaylinepenalty</code>	\جریمه بین سطرهای نمایش
<code>\interlinepenalty</code>	\جریمه بین سطرها
<code>\intertext</code>	\متن داخلی
<code>\intertextsep</code>	\فاصله شناورد متن

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\invisible</code>	<code>\مخفی</code>
<code>\itdefault</code>	<code>\پیش فرض ای</code>
<code>\itshape</code>	<code>\شکل ایتالیک</code>
<code>\item</code>	<code>\فقره</code>
<code>\itemindent</code>	<code>\تورفتگی فقره</code>
<code>\itemsep</code>	<code>\فاصله فقره</code>
<code>\iterate</code>	<code>\تکرارکن</code>
<code>\itshape</code>	<code>\شکل ای</code>
<code>\jobname</code>	<code>\نام کار</code>
<code>\jot</code>	<code>\قلب</code>
<code>\kern</code>	<code>\دوری</code>
<code>\kill</code>	<code>\الگو</code>
<code>\label</code>	<code>\برچسب</code>
<code>\labelenumi</code>	<code>\برچسب شمارش یک</code>
<code>\labelenumii</code>	<code>\برچسب شمارش دو</code>
<code>\labelenumiii</code>	<code>\برچسب شمارش سه</code>
<code>\labelenumiv</code>	<code>\برچسب شمارش چهار</code>
<code>\labelitemi</code>	<code>\برچسب فقره یک</code>
<code>\labelitemii</code>	<code>\برچسب فقره دو</code>
<code>\labelitemiii</code>	<code>\برچسب فقره سه</code>
<code>\labelitemiv</code>	<code>\برچسب فقره چهار</code>
<code>\labelsep</code>	<code>\فاصله از برچسب</code>
<code>\labelwidth</code>	<code>\پهنای برچسب</code>
<code>\language</code>	<code>\زبان</code>
<code>\large</code>	<code>\درشت</code>
<code>\Large</code>	<code>\درشت تر</code>
<code>\LARGE</code>	<code>\درشت درشت</code>
<code>\lastbox</code>	<code>\آخرین کادر</code>
<code>\lastkern</code>	<code>\آخرین دوری</code>
<code>\lastpenalty</code>	<code>\آخرین جریمه</code>
<code>\lastskip</code>	<code>\آخرین فاصله</code>
<code>\LaTeX</code>	<code>\لاتک</code>
<code>\LaTeXe</code>	<code>\لاتک ای</code>
<code>\lccode</code>	<code>\کدکوچک</code>
<code>\ldots</code>	<code>\نقاط خ</code>
<code>\leaders</code>	<code>\نشانگر</code>
<code>\leavevmode</code>	<code>\ترک و</code>
<code>\left</code>	<code>\چپ</code>
<code>\leftmargin</code>	<code>\حاشیه چپ</code>
<code>\leftmargini</code>	<code>\حاشیه چپ یک</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\leftmarginii</code>	<code>\حاشیه چپ دو</code>
<code>\leftmarginiii</code>	<code>\حاشیه چپ سه</code>
<code>\leftmarginiv</code>	<code>\حاشیه چپ چهار</code>
<code>\leftmarginv</code>	<code>\حاشیه چپ پنج</code>
<code>\leftmarginvi</code>	<code>\حاشیه چپ شش</code>
<code>\leftmark</code>	<code>\علامت چپ</code>
<code>\leftpageskip</code>	<code>\کادر تا چپ</code>
<code>\leftskip</code>	<code>\فاصله ابتدای سطر</code>
<code>\let</code>	<code>\بگذار</code>
<code>\line</code>	<code>\سطر</code>
<code>\linebreak</code>	<code>\سطرشکن</code>
<code>\linepenalty</code>	<code>\جریمه سطر</code>
<code>\lineskip</code>	<code>\فاصله سطرها</code>
<code>\lineskiplimit</code>	<code>\حد فاصله سطر</code>
<code>\linespread</code>	<code>\کشش فاصله سطر</code>
<code>\linethickness</code>	<code>\ضخامت خط</code>
<code>\linewidth</code>	<code>\پهنای سطر</code>
<code>\listfigurename</code>	<code>\عنوان فهرست اشکال</code>
<code>\listfiles</code>	<code>\لیست پرونده ها</code>
<code>\listoffigures</code>	<code>\فهرست اشکال</code>
<code>\listoftables</code>	<code>\فهرست جداول</code>
<code>\listparindent</code>	<code>\تورفتگی بند لیست</code>
<code>\listtablename</code>	<code>\عنوان فهرست جداول</code>
<code>\LoadClass</code>	<code>\بارکن طبقه</code>
<code>\LoadClassWithOptions</code>	<code>\بارکن طبقه با گزینه</code>
<code>\location</code>	<code>\مکان</code>
<code>\long</code>	<code>\بلند</code>
<code>\loop</code>	<code>\حلقه</code>
<code>\looseness</code>	<code>\گسیختگی</code>
<code>\lower</code>	<code>\انتقال بپایین</code>
<code>\@makeother</code>	<code>\@دیگر</code>
<code>\@m</code>	<code>\@زار</code>
<code>\@M</code>	<code>\ده@زار</code>
<code>\@Mi</code>	<code>\ده@زاریک</code>
<code>\@Mii</code>	<code>\ده@زاردو</code>
<code>\@Miii</code>	<code>\ده@زارسه</code>
<code>\@Miv</code>	<code>\ده@زارچهار</code>
<code>\@MM</code>	<code>\بیس@زار</code>
<code>\m@ne</code>	<code>\من@</code>
<code>\mag</code>	<code>\بزرگ نمایی</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\magstep</code>	\گام
<code>\magstephalf</code>	\نیم گام
<code>\mainmatter</code>	\مطلب اصلی
<code>\makeatletter</code>	\ات حرف
<code>\makeatother</code>	\ات دیگر
<code>\makebox</code>	\کادر بی خط
<code>\makeglossary</code>	\ساخت فرهنگ
<code>\makeindex</code>	\تهیه نمایه
<code>\makelabel</code>	\ساخت برچسب
<code>\makelabels</code>	\ساخت برچسب ها
<code>\MakeLowercase</code>	\ساخت حروف کوچک
<code>\maketitle</code>	\عنوان ساز
<code>\MakeUppercase</code>	\ساخت حروف بزرگ
<code>\marginpar</code>	\در حاشیه
<code>\marginparpush</code>	\فاصله دو حاشیه
<code>\marginparsep</code>	\فاصله تا حاشیه
<code>\marginparwidth</code>	\پهنای حاشیه
<code>\mark</code>	\علامت
<code>\markboth</code>	\علامت در دو طرف
<code>\markright</code>	\علامت در راست
<code>\mathaccent</code>	\اعراب ریاضی
<code>\mathchar</code>	\نویسه ریاضی
<code>\mathchardef</code>	\تعریف نویسه ریاضی
<code>\mathcode</code>	\کد ریاضی
<code>\mathrm</code>	\ریاضی رومن
<code>\maxdeadcycles</code>	\حد اکثر تکرار
<code>\maxdepth</code>	\حد اکثر عمق صفحه
<code>\maxdimen</code>	\بعد بیشین
<code>\mbox</code>	\کادر بی
<code>\mdseries</code>	\شمایل نازک
<code>\meaning</code>	\معنا
<code>\mediumseries</code>	\نازک
<code>\medmuskip</code>	\فاصله متوسط ریاضی
<code>\medskip</code>	\پرش متوسط
<code>\medskipamount</code>	\مقدار پرش متوسط
<code>\medspace</code>	\فضای متوسط
<code>\message</code>	\پیام
<code>\MessageBreak</code>	\پیام شکن
<code>\minrowclearance</code>	\حد اقل فاصله ردیف
<code>\mkern</code>	\دوری ریاضی

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

\month	\ماه
\moveleft	\انتقال بچپ
\moveright	\انتقال برآست
\mskip	\فاصله ریاضی
\m@th	\ری@ضی
\multicolumn	\چندستونی
\multiply	\ضرب
\multispan	\چندادغام
\muskip	\میوفاصله
\muskipdef	\تعریف میوفاصله
\@namedef	\@ترنام
\@nameuse	\@کاربردنام
\@ne	\یک@
\name	\نام
\natural	\طبیعی
\nearrow	\باریک
\nearrower	\باریکتر
\NeedsTeXFormat	\شکلبندی مورد نیاز
\neg	\منفی
\negmedspace	\فضای متوسط منفی
\negthickspace	\فضای ضخیم منفی
\negthinspace	\دوری کوچک منفی
\newboolean	\بولی نو
\newbox	\کادر جدید
\newcommand	\فرمان نو
\newcount	\شمار جدید
\newcounter	\شمارنده جدید
\newdimen	\بعد جدید
\newenvironment	\محیط نو
\newfam	\خانواده جدید
\newfont	\قلم نو
\newhelp	\کمک جدید
\newif	\اگر جدید
\newinsert	\درج جدید
\newlabel	\برچسب جدید
\newlength	\تعریف بعد جدید
\newline	\سطر جدید
\newlinechar	\نویسه سطر جدید
\newmuskip	\میوفاصله جدید
\newpage	\صفحه جدید

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\newread</code>	<code>\بخوان جدید</code>
<code>\newsavebox</code>	<code>\تعریف کادر جدید</code>
<code>\newskip</code>	<code>\فاصله جدید</code>
<code>\newtheorem</code>	<code>\قضیه جدید</code>
<code>\newtoks</code>	<code>\جزء جدید</code>
<code>\newwrite</code>	<code>\بنویس جدید</code>
<code>\noalign</code>	<code>\بی ردیف</code>
<code>\nobreak</code>	<code>\نشکن</code>
<code>\nobreakspace</code>	<code>\فاصله نشکستی</code>
<code>\nocite</code>	<code>\بدون سند</code>
<code>\noexpand</code>	<code>\نگستر</code>
<code>\nofiles</code>	<code>\بدون پرونده</code>
<code>\noindent</code>	<code>\بدون تورفتگی</code>
<code>\nointerlineskip</code>	<code>\بی فاصله سطر</code>
<code>\nolimits</code>	<code>\بدون حد</code>
<code>\nolinebreak</code>	<code>\سطرنشکن</code>
<code>\nonstopmode</code>	<code>\پردازش بدون توقف</code>
<code>\nonfrenchspacing</code>	<code>\فواصل متعارف لاتین</code>
<code>\nonumber</code>	<code>\بدون شماره</code>
<code>\nopagebreak</code>	<code>\صفحه نشکن</code>
<code>\normalbaselines</code>	<code>\کرسیهای متعارف</code>
<code>\normalbaselineskip</code>	<code>\فاصله کرسی متعارف</code>
<code>\normalcolor</code>	<code>\رنگ عادی</code>
<code>\normalfont</code>	<code>\قلم عادی</code>
<code>\normallineskip</code>	<code>\فاصله سطر متعارف</code>
<code>\normallineskiplimit</code>	<code>\حد فاصله سطر متعارف</code>
<code>\normalmarginpar</code>	<code>\در حاشیه عادی</code>
<code>\normalsize</code>	<code>\اندازه عادی</code>
<code>\notag</code>	<code>\بدون اتیکت</code>
<code>\null</code>	<code>\نول</code>
<code>\nullfont</code>	<code>\قلم تهی</code>
<code>\number</code>	<code>\عدد</code>
<code>\numberline</code>	<code>\سطر عددی</code>
<code>\numberwithin</code>	<code>\شماره مطابق</code>
<code>\@evenfoot</code>	<code>\پایین صفحه زوج</code>
<code>\@evenhead</code>	<code>\بالای صفحه زوج</code>
<code>\@oddfoot</code>	<code>\پایین صفحه فرد</code>
<code>\@oddhead</code>	<code>\بالای صفحه فرد</code>
<code>\@outeqntrue</code>	<code>\شماره بیرون درست</code>
<code>\@outeqnfalse</code>	<code>\شماره بیرون نادرست</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\obeylines</code>	<code>\سطربه سطر</code>
<code>\obeyspaces</code>	<code>\فضا فعال</code>
<code>\oddsidemargin</code>	<code>\حاشیه فرد</code>
<code>\offinterlineskip</code>	<code>\سطور بی فاصله</code>
<code>\omit</code>	<code>\حذف</code>
<code>\@onlypreamble</code>	<code>\@تنها در پیش در آمد</code>
<code>\onecolumn</code>	<code>\یک ستون</code>
<code>\onlynotes</code>	<code>\تنها یادداشت ها</code>
<code>\onlyslides</code>	<code>\تنها اسلایدها</code>
<code>\openin</code>	<code>\بازکن ورودی</code>
<code>\openout</code>	<code>\بازکن خروجی</code>
<code>\OptionNotUsed</code>	<code>\گزینه مصرف نشده</code>
<code>\or</code>	<code>\یا</code>
<code>\outer</code>	<code>\برونی</code>
<code>\output</code>	<code>\صفحه بندی</code>
<code>\outputpenalty</code>	<code>\جریمه صفحه بندی</code>
<code>\overfullrule</code>	<code>\علامت سرریز</code>
<code>\@preamblecmds</code>	<code>\@فرمان های پیش در آمد</code>
<code>\p@</code>	<code>\@پو</code>
<code>\PackageError</code>	<code>\خطای سبک</code>
<code>\PackageInfo</code>	<code>\اطلاع سبک</code>
<code>\PackageWarning</code>	<code>\هشدار سبک</code>
<code>\PackageWarningNoLine</code>	<code>\هشدار سبک بی سطر</code>
<code>\pagebreak</code>	<code>\صفحه شکن</code>
<code>\pagecolor</code>	<code>\رنگ صفحه</code>
<code>\pagedepth</code>	<code>\عمق صفحه</code>
<code>\pagefilllstretch</code>	<code>\کشش پرر صفحه</code>
<code>\pagefillstretch</code>	<code>\کشش پرر صفحه</code>
<code>\pagefilstretch</code>	<code>\کشش پرر صفحه</code>
<code>\pagegoal</code>	<code>\غایت صفحه</code>
<code>\pagename</code>	<code>\نام صفحه</code>
<code>\pagenumbering</code>	<code>\شماره گذاری صفحه</code>
<code>\pageref</code>	<code>\رجوع صفحه</code>
<code>\pagerulewidth</code>	<code>\ضخامت خط صفحه</code>
<code>\pageshrink</code>	<code>\فشرده گی صفحه</code>
<code>\pagestretch</code>	<code>\کشش صفحه</code>
<code>\pagestyle</code>	<code>\سبک صفحه</code>
<code>\pagetotal</code>	<code>\جمع صفحه</code>
<code>\paperheight</code>	<code>\بلندای کاغذ</code>
<code>\paperwidth</code>	<code>\پهنای کاغذ</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\par</code>	<code>\بند</code>
<code>\paragraph</code>	<code>\پاراگراف</code>
<code>\parallel</code>	<code>\موازی</code>
<code>\parbox</code>	<code>\کادرپار</code>
<code>\parfillskip</code>	<code>\فاصله ته بند</code>
<code>\parindent</code>	<code>\تورفتگی سر بند</code>
<code>\parsep</code>	<code>\فاصله بند لیست</code>
<code>\parshape</code>	<code>\شکل بند</code>
<code>\parskip</code>	<code>\فاصله بند</code>
<code>\part</code>	<code>\بخش</code>
<code>\partname</code>	<code>\عنوان بخش</code>
<code>\partopsep</code>	<code>\فاصله بالای لیست بند</code>
<code>\PassOptionToClass</code>	<code>\ارسال گزینه به کلاس</code>
<code>\PassOptionToPackage</code>	<code>\ارسال گزینه به پکیج</code>
<code>\path</code>	<code>\مسیر</code>
<code>\patterns</code>	<code>\الگوها</code>
<code>\pausing</code>	<code>\مکث</code>
<code>\penalty</code>	<code>\جریمه</code>
<code>\phantom</code>	<code>\غیب</code>
<code>\poptabs</code>	<code>\الگوی قبلی</code>
<code>\postdisplaypenalty</code>	<code>\جریمه پس نمایش</code>
<code>\predisplaydirection</code>	<code>\جهت پیش نمایش</code>
<code>\predisplaypenalty</code>	<code>\جریمه پیش نمایش</code>
<code>\predisplaysize</code>	<code>\اندازه پیش نمایش</code>
<code>\pretolerance</code>	<code>\پیش حد بدنمایی</code>
<code>\prevdepth</code>	<code>\عمق قبلی</code>
<code>\prevgraf</code>	<code>\بند قبلی</code>
<code>\printindex</code>	<code>\نمایه در اینجا</code>
<code>\ProcessOptions</code>	<code>\پردازش گزینه ها</code>
<code>\protect</code>	<code>\تأمین</code>
<code>\providecommand</code>	<code>\تهیه فرمان</code>
<code>\ProvidesClass</code>	<code>\آماده سازی طبقه</code>
<code>\ProvidesFile</code>	<code>\آماده سازی پرونده</code>
<code>\ProvidesPackage</code>	<code>\آماده سازی سبک</code>
<code>\pushtabs</code>	<code>\ثبت الگو</code>
<code>\quad</code>	<code>\کواد</code>
<code>\qqquad</code>	<code>\کو کواد</code>
<code>\@outputpagerestore</code>	<code>\@بازآیی خروج صفحه</code>
<code>\radical</code>	<code>\رادیكال</code>
<code>\raggedbottom</code>	<code>\پایین بی تنظیم</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\raggedleft</code>	<code>\تنظیم از راست</code>
<code>\raggedright</code>	<code>\تنظیم از چپ</code>
<code>\raise</code>	<code>\انتقال ببالا</code>
<code>\raisebox</code>	<code>\بالا بر</code>
<code>\raisetag</code>	<code>\ترفع اتيکت</code>
<code>\rangle</code>	<code>\زاويه ر</code>
<code>\rceil</code>	<code>\سقف ر</code>
<code>\read</code>	<code>\بخوان</code>
<code>\ref</code>	<code>\رجوع</code>
<code>\reflectbox</code>	<code>\کادر قرينه</code>
<code>\refname</code>	<code>\عنوان مراجع</code>
<code>\refstepcounter</code>	<code>\گام شماره شده مرجع</code>
<code>\relax</code>	<code>\راحت</code>
<code>\removelastskip</code>	<code>\رفع آخرين فاصله</code>
<code>\renewcommand</code>	<code>\فرمان از نو</code>
<code>\renewenvironment</code>	<code>\محيط از نو</code>
<code>\repeat</code>	<code>\از نو</code>
<code>\RequirePackage</code>	<code>\سبک مورد نیاز</code>
<code>\RequirePackageWithOptions</code>	<code>\سبک مورد نیاز با گزینه</code>
<code>\resizebox</code>	<code>\کادر کشیده</code>
<code>\reversemarginpar</code>	<code>\در حاشیه معکوس</code>
<code>\rfloor</code>	<code>\کف ر</code>
<code>\right</code>	<code>\راست</code>
<code>\rightmargin</code>	<code>\حاشیه راست</code>
<code>\rightmark</code>	<code>\علامت راست</code>
<code>\rightpageskip</code>	<code>\کادر تا راست</code>
<code>\rightskip</code>	<code>\فاصله انتهای سطر</code>
<code>\rmdefault</code>	<code>\رومن عادی</code>
<code>\rmfamily</code>	<code>\فامیل رومن</code>
<code>\Roman</code>	<code>\رومن بزرگ</code>
<code>\roman</code>	<code>\رومن کوچک</code>
<code>\romannumeral</code>	<code>\عدد رومی</code>
<code>\rotatebox</code>	<code>\کادر چرخان</code>
<code>\rowcolor</code>	<code>\رنگ ردیف</code>
<code>\rule</code>	<code>\خط</code>
<code>\@secondoftwo</code>	<code>\@دومی از دو</code>
<code>\@spaces</code>	<code>\@فضاها</code>
<code>\samepage</code>	<code>\همین صفحه</code>
<code>\savebox</code>	<code>\مقدار کادر</code>
<code>\sbox</code>	<code>\مقدار</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\scalebox</code>	<code>\کادراندازه</code>
<code>\sdefault</code>	<code>\پیش فرض تمام بزرگ</code>
<code>\scshape</code>	<code>\شکل تمام بزرگ</code>
<code>\scriptfont</code>	<code>\قلم توان</code>
<code>\scriptscriptfont</code>	<code>\قلم توان توان</code>
<code>\scriptscriptstyle</code>	<code>\سبک ته نوشت ته نوشت</code>
<code>\scriptsize</code>	<code>\اندازه پانویس</code>
<code>\scripstyle</code>	<code>\سبک ته نوشت</code>
<code>\scrollmode</code>	<code>\پردازش گذری</code>
<code>\section</code>	<code>\قسمت</code>
<code>\secdef</code>	<code>\تعریف قسمت</code>
<code>\see</code>	<code>\ببینید</code>
<code>\seealso</code>	<code>\نیز ببینید</code>
<code>\seename</code>	<code>\نام ببینید</code>
<code>\selectfont</code>	<code>\قلم بردار</code>
<code>\setboolean</code>	<code>\تنظیم بولی</code>
<code>\setbox</code>	<code>\درکادر</code>
<code>\setcounter</code>	<code>\مقدار شمارنده</code>
<code>\setkeys</code>	<code>\مقدار کلیدها</code>
<code>\setlength</code>	<code>\مقدار بعد</code>
<code>\setminus</code>	<code>\تنظیم منها</code>
<code>\SetSymbolFont</code>	<code>\تعریف قلم علائم</code>
<code>\settodepth</code>	<code>\تنظیم به عمق</code>
<code>\settoheight</code>	<code>\تنظیم به ارتفاع</code>
<code>\settowidth</code>	<code>\مقدار بعد به اندازه</code>
<code>\sfcode</code>	<code>\کد ضریب فاصله</code>
<code>\sfdefault</code>	<code>\پیش فرض س ف</code>
<code>\sffamily</code>	<code>\فامیل سن سریف</code>
<code>\shadowbox</code>	<code>\کادر سایه دار</code>
<code>\sharp</code>	<code>\تیز</code>
<code>\shipout</code>	<code>\بفرست</code>
<code>\shortstack</code>	<code>\پشته کوتاه</code>
<code>\show</code>	<code>\نمایش بده</code>
<code>\showbox</code>	<code>\نمایش بده کادر</code>
<code>\showboxbreadth</code>	<code>\میزان نمایش کادر</code>
<code>\showboxdepth</code>	<code>\عمق نمایش کادر</code>
<code>\showlists</code>	<code>\نمایش بده لیستها</code>
<code>\showthe</code>	<code>\نمایش بده محتوای</code>
<code>\simplefontmode</code>	<code>\حالت ساده قلم</code>
<code>\sixt@@n</code>	<code>\شانزد @</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\skewchar</code>	<code>\نویسه اریب</code>
<code>\skip</code>	<code>\فاصله</code>
<code>\skip@</code>	<code>@فاصل</code>
<code>\skipdef</code>	<code>\تعریف فاصله</code>
<code>\sl</code>	<code>\خوابیده</code>
<code>\sldefault</code>	<code>\پیش فرض خو</code>
<code>\slshape</code>	<code>\شکل خوابیده</code>
<code>\sloppy</code>	<code>\راحت چین</code>
<code>\slshape</code>	<code>\شمایل خو</code>
<code>\small</code>	<code>\کوچک</code>
<code>\smallskip</code>	<code>\پرش کوتاه</code>
<code>\smallskipamount</code>	<code>\مقدار پرش کوتاه</code>
<code>\smash</code>	<code>\کوب</code>
<code>\smile</code>	<code>\لبخند</code>
<code>\snglftlocatcode</code>	<code>\کدمکان همانطور</code>
<code>\space</code>	<code>\فضا</code>
<code>\spacefactor</code>	<code>\ضریب فاصله</code>
<code>\spaceskip</code>	<code>\فاصله کلمات</code>
<code>\spadesuit</code>	<code>\پیک</code>
<code>\span</code>	<code>\ادغام</code>
<code>\special</code>	<code>\ویژه</code>
<code>\splitmaxdepth</code>	<code>\حد اکثر عمق ستون</code>
<code>\splittopskip</code>	<code>\فاصله بالای ستون</code>
<code>\star</code>	<code>\ستاره</code>
<code>\stepcounter</code>	<code>\گام شمارنده</code>
<code>\stretch</code>	<code>\کشی</code>
<code>\string</code>	<code>\رشته</code>
<code>\strut</code>	<code>\شمع</code>
<code>\strutbox</code>	<code>\کادر شمع</code>
<code>\subitem</code>	<code>\زیر بند</code>
<code>\subparagraph</code>	<code>\زیر پاراگراف</code>
<code>\subsection</code>	<code>\زیر قسمت</code>
<code>\substack</code>	<code>\زیر پشته</code>
<code>\subsubitem</code>	<code>\زیر زیر بند</code>
<code>\subsubsection</code>	<code>\زیر زیر قسمت</code>
<code>\subset</code>	<code>\زیر مجموعه</code>
<code>\subseteq</code>	<code>\زیر مجموعه مسا</code>
<code>\supereject</code>	<code>\منتهای صفحه</code>
<code>\suppressfloats</code>	<code>\حذف مکان شناور</code>
<code>\@tempa</code>	<code>@موقت آ</code>

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

\@tempb	\@موقت ب
\@tempc	\@موقت پ
\@tempd	\@موقت ت
\@tempe	\@موقت ث
\@tempboxa	\@کادرقت آ
\@tempcnta	\@شماقت آ
\@tempcntb	\@شماقت ب
\@tempdima	\@بعدقت آ
\@tempdimb	\@بعدقت ب
\@tempdimc	\@بعدقت پ
\@tempskipa	\@فاقت آ
\@tempskipb	\@فاقت ب
\@tempswafalse	\@سواقت آنادرست
\@tempswatru	\@سواقت آدرست
\@temptokena	\@جزقت آ
\@thefnmark	\انگ زیرنویس
\@thirdofthree	\@سومی ازسه
\tabbingsep	\فاصله جاگذاری
\tabcolsep	\فاصله بین ستونها
\tableofcontents	\فهرست مطالب
\tablename	\عنوان جدول
\tabskip	\فاصله ستونها
\tabularnewline	\ته سطرجدول
\tag	\اتیکت
\telephone	\تلفن
\TeX	\تک
\text	\متن
\textbullet	\گلوله متنی
\textfont	\قلم متن
\textemdash	\ام دش متنی
\textendash	\ان دش متنی
\textexclamdown	\تعجب وارونه متنی
\textperiodcentered	\نقطه وسط متنی
\textquestiondown	\سوال وارونه متنی
\textquotedblleft	\نقل چپ متنی دولا
\textquotedblright	\نقل راست متنی دولا
\textquoteleft	\نقل متنی چپ
\textquoteright	\نقل متنی راست
\textvisiblespace	\فضای نمایان متنی
\textbackslash	\شکافت پشت متنی

Continued on next page



Command in T_EX or L^AT_EX Equivalent Persian Command

<code>\textbar</code>	\میلۀ متنی
<code>\textgreater</code>	\بزرگ ترممتی
<code>\textless</code>	\کمترمتی
<code>\textbf</code>	\متن سیاه
<code>\textcircled</code>	\مدورمتی
<code>\textcolor</code>	\رنگ متن
<code>\textcompwordmark</code>	\نشان کلمه مرکب متن
<code>\textfloatsep</code>	\فاصله متن و شناور
<code>\textfraction</code>	\نسبت متن
<code>\textheight</code>	\بلندای متن
<code>\textindent</code>	\متن تورفته
<code>\textit</code>	\متن ایتالیک
<code>\textmd</code>	\متن نازک
<code>\textnormal</code>	\متن نرمال
<code>\textregistered</code>	\ثبّتی متنی
<code>\textrm</code>	\متن رومن
<code>\textsc</code>	\متن تمام بزرگ
<code>\textsf</code>	\متن سن سریف
<code>\textsl</code>	\متن خوابیده
<code>\textstyle</code>	\سبک متنی
<code>\textsuperscript</code>	\بالا نویس متنی
<code>\texttrademark</code>	\علامت تجاری متنی
<code>\texttt</code>	\متن تایپ
<code>\textup</code>	\متن ایستاده
<code>\textwidth</code>	\پهنای متن
<code>\thanks</code>	\زیرنویس عنوان
<code>\the</code>	\محتوای
<code>\thempfn</code>	\این زیرنویس
<code>\thicklines</code>	\خط ها ضخیم
<code>\thickmuskip</code>	\فاصله زیاد ریاضی
<code>\thinmuskip</code>	\فاصله کم ریاضی
<code>\thickspace</code>	\فضا ضخیم
<code>\thinlines</code>	\خط ها نازک
<code>\thinspace</code>	\دوری کوچک
<code>\thisfancypage</code>	\این صفحه تجملی
<code>\thispagestyle</code>	\سبک این صفحه
<code>\thr@@</code>	\سه @
<code>\tilde</code>	\مد
<code>\tiny</code>	\ظریف
<code>\time</code>	\زمان

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\times</code>	\ضرب در
<code>\title</code>	\عنوان
<code>\to</code>	\به
<code>\today</code>	\امروز
<code>\toks</code>	\جزء
<code>\toksdef</code>	\تعریف جزء
<code>\tolerance</code>	\حدبدنمایی
<code>\top</code>	\بالا
<code>\topfigrule</code>	\خط بالای شناور
<code>\topfraction</code>	\نسبت بالا
<code>\topmargin</code>	\حاشیه بالا
<code>\topmark</code>	\علامت بالا
<code>\toppageskip</code>	\کادر تا بالا
<code>\topsep</code>	\فاصله بالای لیست
<code>\topskip</code>	\فاصله بالا
<code>\totalheight</code>	\بلندای کل
<code>\tracingall</code>	\ردگیری کل
<code>\tracingcommands</code>	\ردگیری فرامین
<code>\tracinglostchars</code>	\ردگیری حروف
<code>\tracingmacros</code>	\ردگیری ماکروها
<code>\tracingonline</code>	\ردگیری نمایشی
<code>\tracingoutput</code>	\ردگیری صفحه بندی
<code>\tracingpages</code>	\ردگیری صفحات
<code>\tracingparagraphs</code>	\ردگیری بندها
<code>\tracingrestores</code>	\ردگیری بازگردانی
<code>\tracingstats</code>	\ردگیری آمارها
<code>\triangle</code>	\مثلث
<code>\ttdefault</code>	\پیش فرض تایپ
<code>\ttfamily</code>	\فامیل تایپ
<code>\tw@</code>	\دو@
<code>\twocolumn</code>	\دو ستون
<code>\typein</code>	\درنویس
<code>\typeout</code>	\برنویس
<code>\uccode</code>	\کد بزرگ
<code>\uchyph</code>	\تیره بندی بزرگ
<code>\undefined</code>	\تعریف نشده
<code>\underline</code>	\زیرخط
<code>\unhbox</code>	\بی کادر
<code>\unhcopy</code>	\بی کپی
<code>\unitlength</code>	\واحد طول

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\unkern</code>	<code>\برگشت دوری</code>
<code>\unpenalty</code>	<code>\برگشت جریمه</code>
<code>\unskip</code>	<code>\برگشت فاصله</code>
<code>\unvbox</code>	<code>\بی کادرو</code>
<code>\unvcopy</code>	<code>\بی کپی و</code>
<code>\updefault</code>	<code>\پیش فرض ایستاده</code>
<code>\upshape</code>	<code>\شکل ایستاده</code>
<code>\usebox</code>	<code>\از کادر</code>
<code>\usecounter</code>	<code>\باشمارشگر</code>
<code>\usefont</code>	<code>\گزینش قلم</code>
<code>\usepackage</code>	<code>\سبک لازم</code>
<code>\@vobeyspaces</code>	<code>\@فضاهای فعال</code>
<code>\@void</code>	<code>\@تهی</code>
<code>\vadjust</code>	<code>\تنظیم و</code>
<code>\valign</code>	<code>\ردیف و</code>
<code>\value</code>	<code>\محتوای شمارنده</code>
<code>\vbadness</code>	<code>\بدنمایی و</code>
<code>\vbox</code>	<code>\کادرو</code>
<code>\vcenter</code>	<code>\کادرو وسط</code>
<code>\verb</code>	<code>\همانطور</code>
<code>\vfil</code>	<code>\پرو</code>
<code>\vfill</code>	<code>\پررو</code>
<code>\vfilneg</code>	<code>\رفع پرو</code>
<code>\vfuzz</code>	<code>\پرزعمودی</code>
<code>\visible</code>	<code>\نمایان</code>
<code>\vline</code>	<code>\خط عمود</code>
<code>\voffset</code>	<code>\حاشیه و</code>
<code>\voidb@x</code>	<code>\ک@درتهی</code>
<code>\vpageref</code>	<code>\ارجاع صفحه ع</code>
<code>\vrbboxsep</code>	<code>\فاصله وگرد</code>
<code>\vref</code>	<code>\ارجاع ع</code>
<code>\vrule</code>	<code>\خط و</code>
<code>\vsize</code>	<code>\طول صفحه</code>
<code>\vskip</code>	<code>\فاصله و</code>
<code>\vspace</code>	<code>\فضای و</code>
<code>\vsplit</code>	<code>\شکست و</code>
<code>\vss</code>	<code>\هر دو و</code>
<code>\vtop</code>	<code>\کادرگود</code>
<code>\wd</code>	<code>\عرض</code>
<code>\whiledo</code>	<code>\مادام بکن</code>

Continued on next page



Command in T _E X or L ^A T _E X	Equivalent Persian Command
<code>\widehat</code>	<code>\کلاه‌پهن</code>
<code>\widetilde</code>	<code>\مد‌پهن</code>
<code>\widowpenalty</code>	<code>\جریمه‌ته‌بند</code>
<code>\width</code>	<code>\پهنا</code>
<code>\wlog</code>	<code>\درکارنامه</code>
<code>\write</code>	<code>\بنویس</code>
<code>\@xobeysp</code>	<code>\@فضای‌لاتین</code>
<code>\@xxxii</code>	<code>\سی‌@‌دو</code>
<code>\xdef</code>	<code>\ترگج</code>
<code>\xleaders</code>	<code>\نش‌انگر‌گسترشی</code>
<code>\xspaceskip</code>	<code>\فاصله‌اضافی‌کلمات</code>
<code>\year</code>	<code>\سال</code>
<code>\z@</code>	<code>\@فر</code>
<code>\z@skip</code>	<code>\@فر‌فاصله</code>

Table 2: The Equivalent XePersian Commands

Command in XePersian	Equivalent Persian Command
<code>\autofootnoterule</code>	<code>\خط‌زیرنویس‌خودکار</code>
<code>\AutoMathsDigits</code>	<code>\اعداد‌فرمول‌ها‌خودکار</code>
<code>\DefaultMathsDigits</code>	<code>\اعداد‌فرمول‌ها‌لاتین</code>
<code>\deflatinfont</code>	<code>\تعریف‌قلم‌لاتین</code>
<code>\defpersianfont</code>	<code>\تعریف‌قلم‌پارسی</code>
<code>\hboxL</code>	<code>\کادر‌را‌چپ</code>
<code>\hboxR</code>	<code>\کادر‌را‌ست</code>
<code>\keyval@eq@alias@key</code>	<code>\معادل‌@‌کلید</code>
<code>\Latincite</code>	<code>\مرجع‌لاتین</code>
<code>\latinfont</code>	<code>\قلم‌لاتین</code>
<code>\latintoday</code>	<code>\امروز‌لاتین</code>
<code>\leftfootnoterule</code>	<code>\خط‌زیرنویس‌چپ</code>
<code>\lr</code>	<code>\متن‌لاتین</code>
<code>\LRE</code>	<code>\چپ‌بر‌است</code>
<code>\LTRdblcol</code>	<code>\دو‌ستونی‌چپ</code>
<code>\LTRfootnote</code>	<code>\پانویس</code>
<code>\LTRfootnotetext</code>	<code>\متن‌پانویس</code>
<code>\LTRthanks</code>	<code>\پانویس‌عنوان</code>
<code>\persianday</code>	<code>\روز‌پارسی</code>
<code>\persianfont</code>	<code>\قلم‌پارسی</code>
<code>\PersianMathsDigits</code>	<code>\اعداد‌فرمول‌ها‌پارسی</code>
<code>\persianmonth</code>	<code>\ماه‌پارسی</code>
<code>\persianyear</code>	<code>\سال‌پارسی</code>

Continued on next page



Command in XePersian	Equivalent Persian Command
\plq	\علامت چپ نقل قول پارسی
\prq	\علامت راست نقل قول پارسی
\rightfootnoterule	\خط زیرنویس راست
\rl	\متن پارسی
\RLE	\راست بچپ
\RTLdblcol	\دوستونی راست
\RTLfootnote	\پانوش
\RTLfootnotetext	\متن پانوش
\RTLthanks	\پانوش عنوان
\@SepMark	\@علامت بین
\SepMark	\علامت بین
\setdefaultbibitems	\بگذارمرجوعات عادی
\setdefaultmarginpar	\بگذاردرحاشیه عادی
\setdigitfont	\گزینش قلم اعداد فرمولها
\setfootnoteLR	\بگذارزیرنویس چپ
\setfootnoteRL	\بگذارزیرنویس راست
\setlatintextfont	\گزینش قلم لاتین متن
\setLTR	\بگذارمتن چپ
\setLTRbibitems	\بگذارمرجوعات چپ
\setLTRmarginpar	\بگذاردرحاشیه چپ
\setRTL	\بگذارمتن راست
\setRTLbibitems	\بگذارمرجوعات راست
\setRTLmarginpar	\بگذاردرحاشیه راست
\settextfont	\گزینش قلم متن
\textwidthfootnoterule	\خط زیرنویس پهنای متن
\twocolumnstableofcontents	\فهرست مطالب دوستونی
\unsetfootnoteRL	\نگذارزیرنویس راست
\unsetLTR	\نگذارمتن چپ
\unsetRTL	\نگذارمتن راست
\vboxL	\کادر وازچپ
\vboxR	\کادر وازراست
\XeLaTeX	\زی لاتک
\XePersian	\زی پرشین
\xepersianversion	\گونه زی پرشین
\xepersiandate	\تاریخ گونه زی پرشین
\XeTeX	\زی تک

Table 3: The Equivalent \LaTeX Environments

Environment in \LaTeX	Equivalent Persian Environment
abstract	چکیده
appendix	پیوست

Continued on next page



Environment in \LaTeX	Equivalent Persian Environment
array	آرایه
center	وسط چین
description	توضیح
displaymath	ریاضی نمایشی
document	نوشتار
enumerate	شمارش
figure	شکل
figure*	شکل*
filecontents	محتوای پرونده
filecontents*	محتوای پرونده*
flushleft	چپ چین
flushright	راست چین
itemize	فقرات
letter	نامه
list	لیست
longtable	جدول دراز
lrbox	کادر چپ
math	ریاضی
matrix	ماتریس
minipage	صفحه کوچک
multicols	چند ستونی ها
multline	چند خطی
note	یادداشت
overlay	انباشتن
picture	تصویر
quotation	اقتباس
quote	نقل
slide	اسلاید
sloppypar	پارنا مرتب
split	شکافتن
subarray	زیر آرایه
tabbing	جاگذاری
table	لوح
table*	لوح*
tabular	جدول
tabular*	جدول*
thebibliography	مراجع
theindex	محتوای نمایه
titlepage	صفحه عنوان
trivlist	لیست بدوی

Continued on next page



Environment in \LaTeX	Equivalent Persian Environment
verbatim	همانطورکه هست
verbatim*	همانطورکه هست*
verse	شعر

Table 4: The Equivalent XePersian Environments

Environment in XePersian	Equivalent Persian Environment
latin	لاتین
LTR	متن چپ
LTRitems	دسته بندی چپ
persian	پارسی
RTL	متن راست
RTLitems	دسته بندی راست

Localisation of position arguments. Some environments like `tabular` and some commands like `\parbox` have an argument which specifies the position. Table [Table 5](#) shows their localisations.

Table 5: The Equivalent \LaTeX position arguments

Position argument in \LaTeX	Equivalent Persian position argument
b	ز
c	و
C	س
h	ا
H	آ
J	ت
l	چ
L	ف
m	م
p	پ
p	ص
r	ر
R	ا
s	ک
t	ب

☞ There are two `ps` in [Table 5](#), first `p` and its Persian equivalent `پ` stand for paragraph (used in `tabular` and similar environments) and the second `p` and its Persian equivalent `ص` stand for page (used in `float`-like environments).

2.4.8 Localizations of the keys and key values of `graphicx` package

The equivalent Persian keys and key values of `graphicx` package is shown in [Table 6](#) and [Table 7](#) respectively.



Table 6: Persian Equivalent keys of graphicx package

Original Key	Equivalent Persian Key
draft	پیش نویس
origin	مبدا
clip	بی اضافه
keepaspectratio	حفظ تناسب
natwidth	پهنای طبیعی
natheight	بلندای طبیعی
bb	مختصات
viewport	محدوده نمایش
trim	حذف اطراف
angle	زاویه
width	پهنا
height	بلندا
totalheight	بلندای کل
scale	ضریب
type	نوع
ext	پسوند
read	خواندنی
command	فرمان
x	طول
y	عرض
units	واحد

Table 7: Persian Equivalent key values of graphicx package

Original Key value	Equivalent Persian Key value
b	ز
B	ک
false	نادرست
l	چ
r	ر
t	ب
true	درست

2.4.9 Localizations of font features and font feature options

The equivalent Persian font features and font feature options is shown in [Table 8](#) and [Table 9](#) respectively.

Table 8: Persian Equivalent font features

Original font feature	Equivalent Persian font feature
ExternalLocation	مکان خارجی
ExternalLocation	مسیر

Continued on next page



Original font feature	Equivalent Persian font feature
Renderer	تحويل دهنده
BoldFont	قلم سیاه
Language	زبان
Script	خط
UprightFont	قلم عمودی
ItalicFont	قلم ایتالیک
BoldItalicFont	قلم ایتالیک سیاه
SlantedFont	قلم خوابیده
BoldSlantedFont	قلم خوابیده سیاه
SmallCapsFont	قلم کلاه کوچک
UprightFeatures	ویژگی های قلم عمودی
BoldFeatures	ویژگی های قلم سیاه
ItalicFeatures	ویژگی های قلم ایتالیک
BoldItalicFeatures	ویژگی های قلم ایتالیک سیاه
SlantedFeatures	ویژگی های قلم خوابیده
BoldSlantedFeatures	ویژگی های قلم خوابیده سیاه
SmallCapsFeatures	ویژگی های قلم کلاه کوچک
SizeFeatures	ویژگی های اندازه
Scale	ضریب
WordSpace	فضای کلمه
PunctuationSpace	فضای نقطه گذاری
FontAdjustment	تنظیم قلم
LetterSpace	فضای حرف
HyphenChar	نویسه تیره
Color	رنگ
Opacity	کدری
Mapping	نگاشت
Weight	سنگینی
Width	پهنا
OpticalSize	اندازه چشمی
FakeSlant	خوابیده تقلبی
FakeStretch	کشش تقلبی
FakeBold	سیاه تقلبی
AutoFakeSlant	خوابیده تقلبی خودکار
AutoFakeBold	سیاه تقلبی خودکار
Ligatures	دو یا چند حرف متصل به هم
Alternate	متناوب
Variant	گوناگون
Variant	مجموعه سبکی
CharacterVariant	گوناگونی نویسه

Continued on next page



Original font feature	Equivalent Persian font feature
Style	سبک
Annotation	یادداشت
RawFeature	ویژگی های کال
CharacterWidth	پهنای نویسه
Numbers	ارقام
Contextuals	متنی
Diacritics	تفکیک کننده ها
Letters	حروف
Kerning	دوری
VerticalPosition	موقعیت عمودی
Fractions	کسر

Table 9: Persian Equivalent font feature options

font feature	font feature option	Persian font feature option
Language	Default	پیش فرض
Language	Parsi	پارسی
Script	Parsi	پارسی
Script	Latin	لاتین
Style	MathScript	اسکرپیت ریاضی
Style	MathScriptScript	اسکرپیت اسکرپیت ریاضی

2.5 A Sample Input T_EX File

```

1 \documentclass{article}
2 \usepackage{xepersian}
3 \settextfont{XB Niloofar}
4 \title{یک سند نمونه}
5 \author{نام نویسنده}
6 \begin{document}
7 \maketitle
8 \tableofcontents
9 \part{عنوان بخش}
10 ...
11 \section{عنوان قسمت}
12 ...
13 \subsection{عنوان زیرقسمت}
14 ...
15 \subsubsection{عنوان زیر زیر قسمت}
16 ...
17 \end{document}

```

2.6 Font Commands



2.6.1 Basic Font Commands

```
\settextfont [Options] {\font name}  
\setlatintextfont [Options] {\font name}  
\setdigitfont [Options] {\font name}  
\setmathsfdigitfont [Options] {\font name}  
\setmathttdigitfont [Options] {\font name}
```

- ☞ Options in any font command in this documentation are anything that fontspec package provides as the option of loading fonts, except Script and Mapping.
- ☞ `\settextfont` will choose the default font for Persian texts of your document.
- ☞ `\setlatintextfont` will choose the font for Latin texts of your document. If you do not use this command at all, the default T_EX font (fonts used in this documentation) will be used for Latin texts of your document.
- ☞ `\setdigitfont` will choose the Persian font for digits in math mode. By default, digits in math mode will appear in Persian form.
- ☞ `\setmathsfdigitfont` will choose the Persian font for digits in math mode inside `\mathsf`. By using this command, digits in math mode inside `\mathsf` will appear in Persian form and if you do not use this command at all, you will get default T_EX font for digits in math mode inside `\mathsf` and digits appear in their original form (Western).
- ☞ `\setmathttdigitfont` will choose the Persian font for digits in math mode inside `\mathtt`. By using this command, digits in math mode inside `\mathtt` will appear in Persian form and if you do not use this command at all, you will get default T_EX font for digits in math mode inside `\mathtt` and digits appear in their original form (Western).

2.6.2 Defining Extra Persian and Latin Fonts

```
\defpersianfont\CS [Options] {\font name}  
\deflatinfont\CS [Options] {\font name}
```

- ☞ With `\defpersianfont`, you can define extra Persian fonts.

```
\defpersianfont\Nastaliq[Scale=1]{IranNastaliq}
```

In this example, we define `\Nastaliq` to stand for IranNastaliq font.

- ☞ With `\deflatinfont`, you can define extra Latin fonts.

```
\deflatinfont\junicode[Scale=1]{Junicode}
```

In this example, we define `\junicode` to stand for Junicode font.



2.6.3 Choosing Persian Sans Font

```
\setpersiansansfont [Options] {\font name}  
\persiansffamily \textpersiansf{\text}
```

2.6.4 Choosing Persian Mono Font

```
\setpersianmonofont [Options] {\font name}  
\persianttfamily \textpersiantt{\text}
```

2.6.5 Choosing Persian Iranic Font

```
\setiraniconfont [Options] {\font name}  
\iranicfamily \textiranicon{\text}
```

2.6.6 Choosing Persian Navar Font

```
\setnavarfont [Options] {\font name}  
\navarfamily \textnavar{\text}
```

2.6.7 Choosing Persian Pook Font

```
\setpookfont [Options] {\font name}  
\pookfamily \textpook{\text}
```

2.6.8 Choosing Persian Sayeh Font

```
\setsayehfont [Options] {\font name}  
\sayehfamily \textsayeh{\text}
```

2.6.9 Choosing Latin Sans Font

```
\setlatinsansfont [Options] {\font name}  
\sffamily \textsf{\text}
```

2.6.10 Choosing Latin Mono Font

```
\setlatinmonofont [Options] {\font name}  
\ttfamily \texttt{\text}
```



3 Latin and Persian Environment

```
\begin{latin} <text> \end{latin}  
\begin{persian} <text> \end{persian}
```

☞ `latin` environment both changes direction of the paragraphs to LTR and font to Latin font.

☞ `persian` environment both changes direction of the Paragraphs to RTL and font to Persian font.

3.1 `latinitems` and `parsiitems` environments

```
\begin{latinitems}  
  \item <text>  
  ...  
\end{latinitems}
```

☞ `latinitems` environment is similar to `LTItems` environment but changes the font to Latin font.

```
\begin{parsiitems}  
  \item <text>  
  ...  
\end{parsiitems}
```

☞ `parsiitems` environment is similar to `RTLItems` environment but changes the font to Persian font.

3.2 Short Latin and Persian Texts

```
\lr{<text>} \rl{<text>}
```

☞ With `\lr` command, you can typeset short LTR texts.

☞ With `\rl` command, you can typeset short RTL texts.

3.3 Miscellaneous Commands

```
\persianyear \persianmonth \persianday  
\today \latintoday \twocolumnstableofcontents \XePersian  
\plq \prq
```

☞ `\persianyear` is Persian equivalent of `\year`.



- ☞ `\persianmonth` is Persian equivalent of `\month`.
- ☞ `\persianday` is Persian equivalent of `\day`.
- ☞ `\today` typesets current Persian date and `\latintoday` typesets current Latin date.
- ☞ `\twocolumnstableofcontents` typesets table of contents in two columns. This requires that you have loaded `multicol` package before `XePersian` package, otherwise an error will be issued.
- ☞ `\XePersian` typesets XePersian's logo.
- ☞ `\plq` and `\prq` typeset Persian left quote and Persian right quote respectively.

3.4 New Commands

`\Latincite`

- ☞ `\Latincite` functions exactly like `\cite` command with only one difference; the reference to biblabel item is printed in Latin font in the text.

3.5 Additional Counters

XePersian defines several additional counters to what already \LaTeX offers. These counters are `harfi`, `adadi`, and `tartibi`. In addition, the following commands are also provided:

`\harfinumeral{⟨integer⟩}` `\adadinumeral{⟨integer⟩}` `\tartibinumeral{⟨integer⟩}`

- ☞ The range of `harfi` counter is integers between 1 and 32 (number of the Persian alphabets) and `adadi` and `tartibi` counters, are integers between 0 and 999,999,999.
- ☞ For `harfi` counter, if you give an integer bigger than 32 or a negative integer (if you give integer 0, it returns nothing), then you get error and for `adadi` and `tartibi` counters, if you give an integer bigger than 999,999,999, then you get an error message.
- ☞ For `adadi` and `tartibi` counters, if you give an integer less than 0 (a negative integer), then `adadi` and `tartibi` counters return **adadi** and **tartibi** form of the integer 0, respectively.
- ☞ `\harfinumeral` returns the **harfi** form of $\langle integer \rangle$, where $1 \leq integer \leq 32$ and `\adadinumeral`, and `\tartibinumeral` return **adadi**, and **tartibi** form of $\langle integer \rangle$ respectively, where $0 \leq integer \leq 999,999,999$.



3.6 Things To Know About `\setdigitfont`, `\setmathsfdigitfont`, and `\setmathttdigitfont`

`\DefaultMathsDigits` `\PersianMathsDigits` `\AutoMathsDigits`

- ☞ As we discussed before, `\setdigitfont` will choose the Persian font for digits in math mode. By default, digits in math mode will appear in Persian form.
- ☞ As we discussed before, `\setmathsfdigitfont`, and `\setmathttdigitfont` will choose the Persian sans serif and typewriter fonts for digits in math mode. By using this command, digits in math mode will appear in Persian form and if you do not use this command at all, you will get default T_EX font for digits in math mode and digits appear in their original form (Western).
If you use `\setdigitfont`, `\setmathsfdigitfont`, and `\setmathttdigitfont`, then you should know that:
 - ☞ By default, `\AutoMathsDigits` is active, which means that in Persian mode, you get Persian digits in math mode and in Latin mode, you get T_EX's default font and digits in math mode.
 - ☞ If you use `\PersianMathsDigits` anywhere, you will overwrite XePersian's default behaviour and you will always get Persian digits in math mode.
 - ☞ If you use `\DefaultMathsDigits` anywhere, again you will overwrite XePersian's default behaviour and you will always get T_EX's default font and digits in math mode.

4 New Conditionals

4.1 Shell escape (or `write18`) conditional

```
\ifwritexviii
  <material when Shell escape (or write18) is enabled>
\else
  <material when Shell escape (or write18) is not enabled>
\fi
```

5 Bilingual Captions

XePersian sets caption bilingually. This means if you are in RTL mode, you get Persian caption and if you are in LTR mode, you get English caption.



5.1 Support For Various Packages

In addition to what bidi package supports, XePersian also support a few packages. This support is more about language aspect rather than directionality. These packages are algorithmic, algorithm, enumerate, and backref packages.

5.1.1 Things You Should Know about Support For enumerate Package

The enumerate package gives the enumerate environment an optional argument which determines the style in which the counter is printed.

An occurrence of one of the tokens A, a, I, i, or 1 produces the value of the counter printed with (respectively) \Alph, \alph, \Roman, \roman or \arabic.

In addition with the extra support that XePersian provides, an occurrence of one of the tokens l, ی, or ت produces the value of the counter printed with (respectively) \harfi, \adadi, or \tartibi.

These letters may be surrounded by any strings involving any other T_EX expressions, however the tokens A, a, I, i, 1, l, ی, ت must be inside a {} group if they are not to be taken as special.

To see an Example, please look at enumerate package documentation.

5.2 Index Generation

For generating index, you are advised to use xindy program, any other program such as makeindex is not recommended.

5.3 Converting Your FarsiT_EX Files To XePersian or Unicode

There is a python program written by Mostafa Vahedi that enables you to convert FarsiT_EX files to XePersian or unicode. This program can be found in doc folder with the name ftxe-0.12.py. To convert your FarsiT_EX files to XePersian, put ftxe-0.12.py in the same directory that your FarsiT_EX file is, and then open a terminal/command prompt and do the following:

```
python ftxe-0.12.py file.ftx file.tex
```

This will convert your file.ftx (FarsiT_EX file) to file.tex (XePersian file).

The general syntax of using the python script is as follow:

```
python ftxe-0.12.py [-r] [-s] [-x] [-u] input-filename1 input-filename2
```

Where

-r (DEFAULT) recursively consider files included in the given files

-s do not recursively consider files

-x (DEFAULT) insert XePersian related commands



-u only convert to unicode (and not to XePersian)

Please note that the python script will not work with versions of python later than 2.6. So you are encouraged to use version 2.6 of python to benefit from this python script.

6 Extra Packages And Classes

6.1 Magazine Typesetting

6.1.1 Introduction

xepersian-magazine class allows you to create magazines, newspapers and any other types of papers. The output document has a front page and as many inner pages as desired. Articles appear one after another, telling the type, number of columns, heading, subheading, images, author and so forth. It is possible to change the aspect of (almost) everything therefore it is highly customisable. Commands to add different titles, headings and footers are also provided.

6.1.2 Usage

To create² a magazine just load the class as usual³, with

```
\documentclass [Options] {xepersian-magazine}
```

at the beginning of your source file. The class options are described in [subsubsection 6.1.12](#).

From this point it is possible to include packages and renew class commands described in [subsubsection 6.1.9](#).

6.1.3 Front Page

As every magazine, xepersian-magazine has its own front page. It includes main headings, an index, the magazine logo and other useful information. This environment should be the first you use within xepersian-magazine class but it is not mandatory.

```
\firstimage \firstarticle
```

The first two commands you can use inside the `frontpage` environment are `\firstimage` and `\firstarticle` which include, respectively, the main image and the main heading in the front page. The first one takes two arguments *<image>* and *<description>*. Notice that second argument is optional and it declares the image

²For a sample file, please look at `magazine-sample.tex` in the doc folder

³You also need to load `graphicx`, `xunicode` and `xepersian` packages respectively, after loading the document class and choose fonts for the main text, Latin text and digits in maths formulas. For more detail see [section 2](#) of the documentation.



caption; *<image>* defines the relative path to the image. In order to include the first piece of article use

```
\firstarticle{<title>}{<opening>}{<time>}
```

first two arguments are mandatory and represent heading and the opening paragraph. Last argument is optional (you can leave it blank) and indicates the time when article happened.

```
\secondarticle
```

The second piece of article is included using the command `\secondarticle` just as the first article. The main difference are that this second piece has two more arguments and it does not include an image.

```
\secondarticle{<title>}{<subtitle>}{<opening>}{<pagesof>}{<time>}
```

The new arguments *<subtitle>* and *<pagesof>* define a subtitle and the name of the section for this piece of article.

```
\thirdarticle
```

The third piece of article is the last one in the xepersian-magazine front page. It works like the `\secondarticle`.

```
\thirdarticle{<title>}{<subtitle>}{<opening>}{<pagesof>}{<time>}
```

The arguments meaning is the same as `\secondarticle` command.

The front page includes three information blocks besides the news: `indexblock` which contains the index, `authorblock` which includes information about the author and a `weatherblock` containing a weather forecast. All these three environments are mostly a frame in the front page therefore they can be redefined to fit your personal wishes but I kept them to give an example and to respect the original xepersian-magazine format.

```
\indexitem
```

The `indexblock` environment contains a manually edited index of xepersian-magazine. It takes one optional argument *<title>* and places a title over the index block. To add entries inside the index just type

```
\indexitem{<title>}{<reference>}
```

inside the environment. The *<title>* is the index entry text and the *<reference>* points to a article inside xepersian-magazine. It will be more clear when you read [subsub-](#)



[section 6.1.4](#). In order to get a correct output, it is necessary to leave a blank line between index items.

The `authorblock` environment can include whatever you would like. I called it `authorblock` because I think it is nice to include some author reference in the front page: who you are, why are you doing this... This environment creates a frame box in the bottom right corner of the front page with your own logo at the top.

```
\weatheritem
```

Finally, the `weatherblock` lets you include a weather forecast. It takes one optional argument $\langle title \rangle$ that places a title over the weather block. It can fit up to three weather icons with maximum and minimum temperatures, description and name. To add each of the weather entries type the following

```
\weatheritem{\langle image \rangle}{\langle day-name \rangle}{\langle max \rangle}{\langle min \rangle}{\langle short-des \rangle}
```

The first argument includes the path to the weather icon (i.e. sunny or rainy), $\langle day-name \rangle$ like Monday, $\langle max \rangle$ and $\langle min \rangle$ are the highest and lowest day temperatures and $\langle short-des \rangle$ is a brief description of the weather condition: partly cloudy, sunny and windy ...

6.1.4 Inside

Once we have created the front page we should include all articles inside our magazine. `xepersian-magazine` arranges all articles one after each other, expanding headings all over the page and splitting the article text in the number of columns we wish. There are three different environments to define a piece of article: the `article` environment described in [subsubsection 6.1.5](#), the `editorial` environment [subsubsection 6.1.6](#) for opinion articles and the `shortarticle` environment explained in [subsubsection 6.1.7](#).

6.1.5 The article environment

The main environment to include a piece of article is called `article`. It takes four arguments that set up the headings and structure of the article.

```
\begin{article}{\langle num-of-columns \rangle}{\langle title \rangle}{\langle subtitle \rangle}{\langle pagesof \rangle}{\langle label \rangle}  
... \langle text \rangle ...  
\end{article}
```

The first argument $\langle num-of-columns \rangle$ sets the number of columns the article will be divided whereas $\langle label \rangle$ is used when pointing an article from the index in the front page. The rest of the arguments are easy to understand.

Inside the `article` environment, besides the main text of the article, it is possible to include additional information using several class commands.




```
\authorandplace \timestamp
```

The `\authorandplace{author}{place}` inserts the name of the editor and the place where the article happened in the way many magazines do. Another useful command is `\timestamp{time}` which includes the time and a separator just before the text. These two commands should be used before the text because they type the text as the same place they are executed.

```
\image
```

To include images within the text of an article, xepersian-magazine provides an `\image` command. Since multicols package does not provide any float support for its multicols environment, I created a macro that includes an image only if that is possible, calculating if there is enough space for the image. It is not the best solution but it works quite well and I could not find a better one. To include an image use the command and its two arguments: the relative path to the image and a short description.

```
\image{image}{description}
```

```
\columnntitle \expandedtitle
```

Within the text of the article, it is possible to add column and expanded titles. The main difference between them is that the first one keeps inside the width of an article column whereas the second expands all over the width of the page, breaking all the columns. Their use is analogous, as follows

```
\columnntitle{type}{text}  
\expandedtitle{type}{text}
```

These two commands use fancybox package features. That is why there are five different types of titles which correspond mainly with fancybox ones: shadowbox, doublebox, ovalbox, Ovalbox and lines.

6.1.6 The editorial environment

In addition to the editorial article environment, one can use the editorial environment to create editorial or opinion texts. The main feature is that it transforms the style of the heading. Although this environment accepts all the commands article takes, it does not make any sense to use the `\authorandplace` command within it since it includes an author argument. To create an editorial text use



```
\begin{editorial}{\langle num-of-columns \rangle}{\langle title \rangle}{\langle author \rangle}{\langle label \rangle}
...{\langle text \rangle}...
\end{editorial}
```

All arguments have the same meaning as article environment (see [subsubsection 6.1.5](#)).

6.1.7 The shortarticle environment

The shortarticle environment creates a block of short article. Although it has its own title and subtitle, each piece of article within it may have a title. To use it just type:

```
\begin{shortarticle}{\langle num-of-columns \rangle}{\langle title \rangle}{\langle subtitle \rangle}{\langle label \rangle}
...{\langle text \rangle}...
\shortarticleitem{\langle title \rangle}{\langle text \rangle}
...
\end{shortarticle}
```

You can also specify the number of columns of the block like editorial and article environments. To add a piece of article inside the shortarticle use the `\shortarticleitem`, indicating a title and the text of the issue.

6.1.8 Commands between articles

```
\articlesep \newsection
```

There are two commands you can use among the articles inside xepersian-magazine: `\articlesep` and `\newsection`. The first one does not take any parameter and just draws a line between two articles. The second changes the content of `\xepersian@section` to the new *`\section name`*. From the point it is used, all articles which follow will be grouped within the new section.

```
\newsection{\langle section name \rangle}
```

6.1.9 Customization

xepersian-magazine includes many commands which can be used to customize its aspect, from the front page to the last page. I will list them grouped so it is easy to find them. Treat them as standard \LaTeX commands, using `\renewcommand` to change their behaviour.



6.1.10 Front Page

```
\customlogo \customminilogo \custommagazinenam
```

When creating a magazine, everyone wants to show its own logo instead of xepersian-magazine default heading. To achieve this, you need to put the following command at the preamble of your document:

```
\customlogo{<text>}  
\customminilogo{<text>}  
\custommagazinenam{<text>}
```

```
\edition \editionformat
```

The edition text has to be declared in the preamble of the document. One important thing to know is that `\author`, `\date` and `\title` have no effect inside xepersian-magazine since the magazine date is taken from `\today` command and the other two are only for the title page (if using `\maketitle`).

```
\indexFormat \indexEntryFormat \indexEntryPageTxt  
\indexEntryPageFormat \indexEntrySeparator
```

When defining the index in the front page, there are several commands to customize the final index style. `\indexFormat` sets the format of the title; `\indexEntryFormat`, the format of each index entry; `\indexEntryPageTxt` and `\indexEntryPageFormat` lets you define which is the text that goes with the page number and its format. Finally, xepersian-magazine creates a thin line between index entries, you can redefine it using `\indexEntrySeparator`. To get the index with `\xepersian@indexwidth` is provided.

```
\weatherFormat \weatherTempFormat \weatherUnits
```

Relating to the weather block, the title format can be changed redefining `\weatherFormat`. In order to customize the format of the temperature numbers and their units it is necessary to redefine `\weatherTempFormat` and `\weatherUnits` respectively.

```
\*TitleFormat \*SubtitleFormat \*TextFormat
```

The main article that appear in the front page can change their formats. To obtain that there are three standard commands to modify the title, subtitle and text style. You just have to replace the star (*) with first, second or third depending on which article you are editing. Note that first piece of article has no subtitle therefore it does not make any sense to use the non-existent command `\firstSubtitleFormat`.



```
\pictureCaptionFormat \pagesFormat
```

Two other elements to configure are the picture captions and the pages or section format in the entire document. To proceed just redefine the macros `\pictureCaptionFormat` and `\pagesFormat`.

6.1.11 Inside The Magazine

```
\innerTitleFormat \innerSubtitleFormat \innerAuthorFormat  
\innerPlaceFormat
```

The articles inside `xepersian-magazine` may have a different format from the ones in the front page. To change their title or subtitle format redefine `\innerTitleFormat` and `\innerSubtitleFormat`. The article text format matches the document general definition. When using the `\authorandplace` command, you might want to change the default style. Just renew `\innerAuthorFormat` and `\innerPlaceFormat` to get the results.

```
\timestampTxt \timestampSeparator \timestampFormat
```

The `\timestamp` command described in [subsubsection 6.1.5](#) lets you introduce the time of the event before the article text. You can configure its appearance by altering several commands: `\timestampTxt` which means the text after the timestamp; `\timestampSeparator` which defines the element between the actual timestamp and the beginning of the text and, finally, `\timestampFormat` to change the entire timestamp format.

```
\innerTextFinalMark
```

`xepersian-magazine` puts a small black square at the end of the article. As I wanted to create a highly customizable \LaTeX class I added the macro `\innerTextFinalMark` to change this black square. This item will appear always following the last character of the text with the `~` character.

```
\minraggedcols \raggedFormat
```

The `\minraggedcols` counter is used to tell `xepersian-magazine` when article text should be ragged instead of justified. The counter represents the minimum number of columns that are needed in order to use ragged texts. For example, if `\minraggedcols` is set to 3, all articles with 3 columns or more will be ragged. Articles with 1, 2 columns will have justified text. By default, `\minraggedcols` is set to 4.

The `\raggedFormat` macro can be redefined to fit user ragged style. Default value is `\RaggedLeft`.



```
\heading \foot
```

xepersian-magazine includes package fancyhdr for changing headings and footers. Although it is possible to use its own commands to modify xepersian-magazine style, there are two commands to change headings and foot appearance. Place them in the preamble of your xepersian-magazine document.

```
\heading{\left}\{center\}\{right\}  
\foot{\left}\{center\}\{right\}
```

If you still prefer to use fancyhdr macros, use them after the `frontpage` environment. xepersian-magazine by default places no headers and footers. If you want headers and footers, then after loading xepersian package, you should write `\pagestyle{fancy}` at the preamble of your document.

6.1.12 Class Options

The xepersian-magazine class is in itself an alteration of the standard article class, thus it inherits most of its class options but twoside, twocolumn, notitlepage and a4paper. If you find problems when loading other article features, please let me know to fix it. There are also five own options that xepersian-magazine implements.

a3paper (false) This option makes xepersian-magazine 297 mm width by 420 mm height. This option is implemented because the standard article class does not allow this document size.

9pt (false) Allows the 9pt font size that article class does not include (default is 10pt).

columnlines columnlines (false) Adds lines between columns in the entire xepersian-magazine. The default line width is 0.1pt but it is possible to change this by setting length `\columnlines` in the preamble.

showgrid (false) This option is only for developing purposes. Because the front page has a personal design using the textpos package, I created this grid to make easier the lay out.

6.2 Typesetting Multiple-choice Questions

6.2.1 Introduction

xepersian-multiplechoice is a package for making multiple choices questionnaires under \LaTeX . A special environment allows you to define questions and possible answers. You can specify which answers are correct and which are not. xepersian-multiplechoice not only formats the questions for you, but also generates a “form” (a grid that your students will have to fill in), and a “mask” (the same grid, only with correct answers properly checked in). You can then print the mask on a slide and correct the questionnaires more easily by superimposing the mask on top of students’ forms.



6.2.2 Usage

Here we now explain the usage of this package, however there are four example files, namely `test-question-only.tex`, `test-solution-form.tex`, `test-empty-form.tex` and `test-correction.tex`, available in doc folder that you may want to look at.

6.2.3 Loading The Package

You can load the package as usual by:

```
\usepackage [Options] {xepersian-multiplechoice}
```

The available options are described along the text, where appropriate.

6.2.4 Creating Questions

Here's a simple example demonstrating how to produce a new question:

```
1 \begin{question}{سؤال}
2 \false \ جواب
3 \true ۲ جواب
4 \false ۳ جواب
5 \false ۴ جواب
6 \end{question}
7 \begin{correction}
8 جواب واقعی و علت اینکه این جواب، جواب واقعی هست
9 \end{correction}
```

6.2.5 The question Environment

The `question` environment allows you to insert questions into your document. It takes one mandatory argument which specifies the actual question's text. The question will be displayed in a frame box, the size of the line.

```
\true \false
```

The proposed answers are displayed below the question in a list fashion (the question environment is a list-based one). Instead of using `\item` however, use either `\true` or `\false` to insert a possible answer.

6.2.6 Question Numbers

The `question` environment is associated with a \TeX counter named `question`. This counter stores the number of the next (or current) question. It is initialized to 1, and automatically incremented at the end of `question` environments. You might want to use it to format question titles. For instance, you could decide that each question belongs to a subsection in the `article` class, and use something like this before each question: `\subsection*{Question \thethequestion}`



6.2.7 The Form and the Mask

`\makeform \makemask`

Based on the questions appearing in your document, xepersian-multiplechoice has the ability to generate a “form” (a grid that your students will have to fill in), and a “mask” (the same grid, only with correct answers properly checked in). This can make the correction process easier.

To generate a form and a mask, use the macros `\makeform` and `\makemask`. xepersian-multiplechoice uses two auxiliary files to build them. These files have respectively an extension of `frm` and `msk`. If you use these macros, you will need two passes of L^AT_EX in order to get a correctly formatted document.

6.2.8 Typesetting corrections

The “correction” mode allows you to automatically typeset and distribute corrections to your students. These corrections are slightly modified versions of your questionnaire: each possible answer is prefixed with a small symbol (a visual clue) indicating whether the answer was correct or wrong. In addition, you can typeset explanations below each question.

To activate the correction mode, use the `correction` option. It is off by default.

To typeset explanations below the questions, use the `correction` environment (no argument). The contents of this environment is displayed only in correction mode. In normal mode, it is simply discarded.

In addition, note that xepersian-multiplechoice cancels the actions performed by `\makeform` and `\makemask` in `correction` mode. This is to avoid further edition of the source when typesetting a correction.

6.2.9 Important Note

Currently, xepersian-multiplechoice requires that you provide a constant number of proposed answers across all questions in your xepersian-multiplechoice. This is something natural when you want to build forms, but this might be too restrictive otherwise, I’m not sure, so it is possible that this restriction will be removed in future versions.

Currently, there is a built-in mechanism for checking that the number of proposed answers remains constant: when xepersian-multiplechoice encounters the first occurrence of the `question` environment, it remembers the number of proposed answers from there. Afterwards, any noticed difference in subsequent occurrences will generate an error. As a consequence, you never have to tell xepersian-multiplechoice explicitly what that number is.

6.3 Customising The Package



6.3.1 The question environment

`\questionspace \answerstitlefont \answernumberfont`

`\questionspace` is the amount of extra vertical space to put under the question, before the list of proposed answers. This is a \LaTeX length that defaults to 0pt. Before the list of possible answers, a short title is displayed (for English, it reads “Possible answers:”). The `\answerstitlefont` macro takes one mandatory argument which redefines the font to use for the answers title. By default, `\bfseries` is used. Each proposed answer in the list is numbered automatically (and alphabetically). The `\answernumberfont` macro takes one mandatory argument which redefines the font to use for displaying the answer number. By default, `\bfseries` is used.

6.3.2 The Form and the Mask

`\headerfont \X`

The `\headerfont` macro takes one mandatory argument which redefines the font to use for the headers (first line and first column) of the form and mask arrays. By default, `\bfseries` is used.

In the mask, correct answers are checked in by filling the corresponding cell with an “X” character. If you want to change this, call the `\X` macro with one (mandatory) argument.

6.3.3 The correction

`\truesymbol \falsesymbol`

In correction mode, labels in front of answers are modified to give a visual clue about whether the answer was correct or wrong. By default, a cross and a small arrow are used. You can change these symbols by using the `\truesymbol` and `\falsesymbol` macros. For instance, you could give a fancier look to your correction by using the `pifont` package and issuing:

```
\truesymbol{\ding{'063}~}
\falsesymbol{\ding{'067}~}
```

`\correctionstyle`

The appearance of the contents of the correction environment can be adjusted by using the `\correctionstyle` macro. By default, `\itshape` is used.

7 xepersian implementation

7.1 algorithmic-xepersian.def




```

1 \ProvidesFile{algorithmic-xepersian.def}[2010/07/25 v0.2 adaptations for algorithmic package]
2 \def\algorithmicrequire{\if@RTL\textbf{ :}\else\textbf{Require:}\fi}
3 \def\algorithmicensure{\if@RTL\textbf{ :}\else\textbf{Ensure:}\fi}

```

7.2 algorithm-xepersian.def

```

4 \ProvidesFile{algorithm-xepersian.def}[2010/07/25 v0.2 adaptations for algorithm package]
5 \def\ALG@name{\if@RTL else\ Algorithm\fi}
6 \def\ALGS@name{ }
7 \def\listalgorithmname{\if@RTL \ALGS@name\else List of \ALG@name s\fi}

```

7.3 amsart-xepersian.def

```

8 \ProvidesFile{amsart-xepersian.def}[2017/02/04 v0.4 adaptations for amsart class]
9 \renewcommand \thepart {\@tartibi\c@part}
10 \def\appendix{\par\c@section\z@ \c@subsection\z@
11 \let\sectionname\appendixname
12 \def\thesection{\@harfi\c@section}}
13

```

7.4 amsbook-xepersian.def

```

14 \ProvidesFile{amsbook-xepersian.def}[2017/02/04 v0.5 adaptations for amsbook class]
15 \def\frontmatter{\cleardoublepage\pagenumbering{harfi}}
16 \renewcommand \thepart {\@tartibi\c@part}
17 \def\appendix{\par
18 \c@chapter\z@ \c@section\z@
19 \let\chaptername\appendixname
20 \def\thechapter{\@harfi\c@chapter}}
21
22

```

7.5 appendix-xepersian.def

```

23 \ProvidesFile{appendix-xepersian.def}[2015/02/01 v0.1 adaptations for appendix package]
24 \renewcommand{\@resets@pp}{\par
25 \@ppsavesec
26 \stepcounter{@pps}
27 \setcounter{section}{0}%
28 \if@chapter@pp
29 \setcounter{chapter}{0}%
30 \renewcommand\@chapapp{\appendixname}%
31 \renewcommand\thechapter{\@harfi\c@chapter}%
32 \else
33 \setcounter{subsection}{0}%
34 \renewcommand\thesection{\@harfi\c@section}%
35 \fi
36 \restoreapp
37 }

```

7.6 article-xepersian.def

```

38 \ProvidesFile{article-xepersian.def}[2010/07/25 v0.2 adaptations for standard article class]

```



```

39 \renewcommand \thepart {\@tartibi\c@part}
40 \renewcommand\appendix{\par
41 \setcounter{section}{0}%
42 \setcounter{subsection}{0}%
43 \gdef\thesection{\@harfi\c@section}}

```

7.7 artikel1-xepersian.def

```

44 \ProvidesFile{artikel1-xepersian.def}[2010/07/25 v0.1 adaptations for artikel1 class]
45 \renewcommand*\thepart{\@tartibi\c@part}
46 \renewcommand*\appendix{\par
47 \setcounter{section}{0}%
48 \setcounter{subsection}{0}%
49 \gdef\thesection{\@harfi\c@section}}

```

7.8 artikel2-xepersian.def

```

50 \ProvidesFile{artikel2-xepersian.def}[2010/07/25 v0.1 adaptations for artikel2 class]
51 \renewcommand*\thepart{\@tartibi\c@part}
52 \renewcommand*\appendix{\par
53 \setcounter{section}{0}%
54 \setcounter{subsection}{0}%
55 \gdef\thesection{\@harfi\c@section}}

```

7.9 artikel3-xepersian.def

```

56 \ProvidesFile{artikel3-xepersian.def}[2010/07/25 v0.1 adaptations for artikel3 class]
57 \renewcommand*\thepart{\@tartibi\c@part}
58 \renewcommand*\appendix{\par
59 \setcounter{section}{0}%
60 \setcounter{subsection}{0}%
61 \gdef\thesection{\@harfi\c@section}}

```

7.10 backref-xepersian.def

```

62 \ProvidesFile{backref-xepersian.def}[2010/07/25 v0.1 adaptations for backref package]
63 \def\backrefpagesname{\if@RTL else\    pages\fi}
64 \def\BR@Latincitex[#1]#2{%
65 \BRorg@Latincitex[{#1}]{#2}%
66 \ifBR@verbose
67 \PackageInfo{backref}{back Latin cite \string`#2\string'}%
68 \fi
69 \Hy@backout{#2}%
70 }
71 \AtBeginDocument{%
72 \@ifundefined{NAT@parse}{%
73 \global\let\BRorg@Latincitex\@Latincitex
74 \global\let\@Latincitex\BR@Latincitex
75 }{%
76 \@ifpackageloaded{hyperref}{%
77 \def\hyper@natlinkstart#1{\Hy@backout{#1}}%
78 }%
79 \PackageInfo{backref}{** backref set up for natbib **}%

```



```

80 }%
81 }%

```

7.11 bidentuftsidenote-xepersian.def

```

82 \ProvidesFile{bidentuftsidenote-xepersian.def}[2017/02/04 v0.3 xepersian changes to bidentufts
83
84 \setLTRcitationfont{\resetlatinfont\footnotesize}
85
86 \renewcommand*{\@bidentuftsidenote@LTRmarginfont}{\resetlatinfont\footnotesize}
87
88 \renewcommand*{\@bidentuftsidenote@RTLmarginfont}{\setpersianfont\footnotesize}
89
90

```

7.12 bidimoderncv-xepersian.def

```

91 \ProvidesFile{bidimoderncv-xepersian.def}[2010/07/25 v0.1 adaptations for bidimoderncv class]
92 \def\refname{\if@RTL else\      Publications\fi}

```

7.13 boek3-xepersian.def

```

93 \ProvidesFile{boek3-xepersian.def}[2010/07/25 v0.1 adaptations for boek3 class]
94 \renewcommand*\thepart{\@tartibi\c@part}
95 \renewcommand*\frontmatter{%
96   \cleardoublepage
97   \@mainmatterfalse
98   \pagenumbering{harfi}}
99 \renewcommand*\appendix{\par
100   \setcounter{chapter}{0}%
101   \setcounter{section}{0}%
102   \gdef\@chapapp{\appendixname}%
103   \gdef\thechapter{\@harfi\c@chapter}}

```

7.14 boek-xepersian.def

```

104 \ProvidesFile{boek-xepersian.def}[2010/07/25 v0.1 adaptations for boek class]
105 \renewcommand*\thepart{\@tartibi\c@part}
106 \renewcommand*\frontmatter{%
107   \cleardoublepage
108   \@mainmatterfalse
109   \pagenumbering{harfi}}
110 \renewcommand*\appendix{\par
111   \setcounter{chapter}{0}%
112   \setcounter{section}{0}%
113   \gdef\@chapapp{\appendixname}%
114   \gdef\thechapter{\@harfi\c@chapter}}

```

7.15 bookest-xepersian.def

```

115 \ProvidesFile{bookest-xepersian.def}[2010/07/25 v0.1 adaptations for bookest class]
116 \renewcommand \thepart {\@tartibi\c@part}
117 \renewcommand\appendix{\par

```



```

118 \setcounter{chapter}{0}%
119 \setcounter{section}{0}%
120 \gdef\@chapapp{\appendixname}%
121 \gdef\thechapter{\@harfi\c@chapter}
122 }%end appendix

```

7.16 book-xepersian.def

```

123 \ProvidesFile{book-xepersian.def}[2010/07/25 v0.2 adaptations for standard book class]
124 \renewcommand\frontmatter{%
125     \cleardoublepage
126     \@mainmatterfalse
127     \pagenumbering{harfi}}
128 \renewcommand \thepart {\@tartibi\c@part}
129 \renewcommand\appendix{\par
130     \setcounter{chapter}{0}%
131     \setcounter{section}{0}%
132     \gdef\@chapapp{\appendixname}%
133     \gdef\thechapter{\@harfi\c@chapter}
134 }%end appendix

```

7.17 breqn-xepersian.def

```

135 \ProvidesFile{breqn-xepersian.def}[2010/07/25 v0.1 adaptations for breqn package]
136 \def\@dmath[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
137     \everydisplay\expandafter{\the\everydisplay \display@setup}%
138     \if@noskipsec \leavevmode \fi
139     \if@inlabel \leavevmode \global\@inlabelfalse \fi
140     \if@eq@group\else\eq@prelim\fi
141     \setkeys{breqn}{#1}%
142     \the\eqstyle
143     \eq@setnumber
144     \begingroup
145     \eq@setup@a
146     \eq@startup
147 }
148 \def\@dgroup[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
149     \let\eq@group\@True \global\let\eq@GRP@first@dmath\@True
150     \global\GRP@queue\@emptytoks \global\setbox\GRP@box\box\voidb@x
151     \global\let\GRP@label\@empty
152     \global\grp@wdL\z@\global\grp@wdR\z@\global\grp@wdT\z@
153     \global\grp@linewidth\z@\global\grp@wdNum\z@
154     \global\let\grp@eqs@numbered\@False
155     \global\let\grp@aligned\@True
156     \global\let\grp@shiftnumber\@False
157     \eq@prelim
158     \setkeys{breqn}{#1}%
159     \if\grp@hasNumber \grp@setnumber \fi
160 }
161 \def\@dseries[#1]{\if@RTL\@RTLfalse\addfontfeatures{Mapping=farsidigits}\fi%
162     \let\display@setup\dseries@display@setup

```



```

163 % Question: should this be the default for dseries???
164 \global\eq@wdCond\z@
165 \@dmath[layout={M},#1]%
166 \mathsurround\z@\@math \penalty\@Mi
167 \let\endmath\ends@math
168 \def\premath{%
169     \ifdim\lastskip<.3em \unskip
170     \else\ifnum\lastpenalty<\@M \dquad\fi\fi
171 }%
172 \def\postmath{\unpenalty\eq@addpunct \penalty\intermath@penalty \dquad \@ignoretrue}%
173 \ignorespaces
174 }

```

7.18 latex-localise-commands-xepersian.def

```

175 \ProvidesFile{latex-localise-commands-xepersian.def}[2014/02/05 v0.3 Persian localisation of L
176 \eqcommand{ }{@arstrut}
177 \eqcommand{ }{above}
178 \eqcommand{ }{abovedisplayshortskip}
179 \eqcommand{ }{abovedisplayskip}
180 \eqcommand{ }{abstractname}
181 \eqcommand{ }{accent}
182 \eqcommand{ }{active}
183 \eqcommand{ }{addcontentsline}
184 \eqcommand{ }{addpenalty}
185 \eqcommand{ }{address}
186 \eqcommand{ }{addtocontents}
187 \eqcommand{ }{addtocounter}
188 \eqcommand{ }{addtolength}
189 \eqcommand{ }{addvspace}
190 \eqcommand{ }{adjdemerits}
191 \eqcommand{ }{advance}
192 \eqcommand{ }{afterassignment}
193 \eqcommand{ }{aftergroup}
194 \eqcommand{ }{aleph}
195 \eqcommand{ }{aliasfontfeature}
196 \eqcommand{ }{aliasfontfeatureoption}
197 \eqcommand{ }{allowbreak}
198 \eqcommand{ @}{alloc@}
199 \eqcommand{ }{allocationnumber}
200 \eqcommand{ }{allowdisplaybreaks}
201 \eqcommand{ }{Alph}
202 \eqcommand{ }{alph}
203 \eqcommand{ }{alsoname}
204 \eqcommand{ }{and}
205 \eqcommand{ }{angle}
206 \eqcommand{ }{appendixname}
207 \eqcommand{ }{approx}
208 \eqcommand{ }{arabic}
209 \eqcommand{ }{arg}

```



```

210 \eqcommand{      }{arrayrulecolor}
211 \eqcommand{      }{arraycolsep}
212 \eqcommand{      }{arrayrulewidth}
213 \eqcommand{      }{arraystretch}
214 \eqcommand{      }{AtBeginDocument}
215 \eqcommand{      }{AtEndDocument}
216 \eqcommand{      }{AtEndOfClass}
217 \eqcommand{      }{AtEndOfPackage}
218 \eqcommand{      }{author}
219 \eqcommand{      }{backmatter}
220 \eqcommand{      }{backslash}
221 \eqcommand{      }{badness}
222 \eqcommand{      }{bar}
223 \eqcommand{      }{baselineskip}
224 \eqcommand{      }{baselinestretch}
225 \eqcommand{      }{batchmode}
226 \eqcommand{      }{begin}
227 \eqcommand{      }{beginL}
228 \eqcommand{      }{beginR}
229 \eqcommand{      }{begingroup}
230 \eqcommand{      }{belowdisplayshortskip}
231 \eqcommand{      }{belowdisplayskip}
232 \eqcommand{      }{bf}
233 \eqcommand{      }{bfdefault}
234 \eqcommand{      }{bfseries}
235 \eqcommand{      }{bgroup}
236 \eqcommand{      }{bibitem}
237 \eqcommand{      }{bibliography}
238 \eqcommand{      }{bibliographystyle}
239 \eqcommand{      }{bibname}
240 \eqcommand{      }{bigskip}
241 \eqcommand{      }{bigskipamount}
242 \eqcommand{      }{botfigrule}
243 \eqcommand{      }{botmark}
244 \eqcommand{      }{bottompageskip}
245 \eqcommand{      }{bottomfraction}
246 \eqcommand{      }{box}
247 \eqcommand{      }{boxmaxdepth}
248 \eqcommand{      }{break}
249 \eqcommand{      }{bullet}
250 \eqcommand{ @ }{@cclv}
251 \eqcommand{ @ }{@ccclvi}
252 \eqcommand{      }{caption}
253 \eqcommand{      }{catcode}
254 \eqcommand{      }{cc}
255 \eqcommand{      }{ccname}
256 \eqcommand{      }{cdot}
257 \eqcommand{      }{cdots}
258 \eqcommand{      }{centering}
259 \eqcommand{      }{centerline}

```



```

260 \eqcommand{ @ }{ch@ck}
261 \eqcommand{ }{chapter}
262 \eqcommand{ }{chaptername}
263 \eqcommand{ }{char}
264 \eqcommand{ }{chardef}
265 \eqcommand{ }{CheckCommand}
266 \eqcommand{ }{cite}
267 \eqcommand{ }{ClassError}
268 \eqcommand{ }{ClassInfo}
269 \eqcommand{ }{ClassWarning}
270 \eqcommand{ }{ClassWarningNoLine}
271 \eqcommand{ }{cleaders}
272 \eqcommand{ }{cleardoublepage}
273 \eqcommand{ }{clearpage}
274 \eqcommand{ }{cline}
275 \eqcommand{ }{closein}
276 \eqcommand{ }{closeout}
277 \eqcommand{ }{closing}
278 \eqcommand{ }{clubpenalty}
279 \eqcommand{ }{clubsuit}
280 \eqcommand{ }{colbotmark}
281 \eqcommand{ }{colfirstmark}
282 \eqcommand{ }{color}
283 \eqcommand{ }{colorbox}
284 \eqcommand{ }{coltopmark}
285 \eqcommand{ }{columncolor}
286 \eqcommand{ }{columnsep}
287 \eqcommand{ }{columnwidth}
288 \eqcommand{ }{columnseprule}
289 \eqcommand{ }{contentsline}
290 \eqcommand{ }{contentsname}
291 \eqcommand{ }{copy}
292 \eqcommand{ }{copyright}
293 \eqcommand{ }{count}
294 \eqcommand{ @ }{count@}
295 \eqcommand{ }{countdef}
296 \eqcommand{ }{cr}
297 \eqcommand{ }{crr}
298 \eqcommand{ }{csname}
299 \eqcommand{ }{CurrentOption}
300 \eqcommand{ }{dashbox}
301 \eqcommand{ }{dashv}
302 \eqcommand{ @ }{@date}
303 \eqcommand{ }{date}
304 \eqcommand{ }{day}
305 \eqcommand{ }{dblbotfigrule}
306 \eqcommand{ }{dblbottomfraction}
307 \eqcommand{ }{dblfigrule}
308 \eqcommand{ }{dblfloatpagefraction}
309 \eqcommand{ }{dblfloatsep}

```



```

310 \eqcommand{      }{dblfontlocatcode}
311 \eqcommand{      }{dbltextfloatsep}
312 \eqcommand{      }{dbltopfraction}
313 \eqcommand{      }{DeclareFixedFont}
314 \eqcommand{      }{DeclareGraphicsExtensions}
315 \eqcommand{      }{DeclareGraphicsRule}
316 \eqcommand{      }{DeclareOldFontCommand}
317 \eqcommand{      }{DeclareOption}
318 \eqcommand{      }{DeclareRobustCommand}
319 \eqcommand{      }{DeclareSymbolFont}
320 \eqcommand{      }{deadcycles}
321 \eqcommand{ }{def}
322 \eqcommand{ @ }{define@key}
323 \eqcommand{   }{definecolor}
324 \eqcommand{ }{deg}
325 \eqcommand{   }{delcode}
326 \eqcommand{   }{delimiter}
327 \eqcommand{   }{delimiterfactor}
328 \eqcommand{ }{depth}
329 \eqcommand{ }{diamondsuit}
330 \eqcommand{ }{dim}
331 \eqcommand{ }{dimen}
332 \eqcommand{ @ }{dimen@}
333 \eqcommand{ @ }{dimen@i}
334 \eqcommand{ @ }{dimen@ii}
335 \eqcommand{   }{dimendef}
336 \eqcommand{   }{discretionary}
337 \eqcommand{   }{displaybreak}
338 \eqcommand{   }{displayindent}
339 \eqcommand{   }{displaystyle}
340 \eqcommand{   }{displaywidth}
341 \eqcommand{ }{divide}
342 \eqcommand{   }{documentclass}
343 \eqcommand{ }{do}
344 \eqcommand{   }{dospecials}
345 \eqcommand{ }{dot}
346 \eqcommand{   }{doteq}
347 \eqcommand{   }{dotfill}
348 \eqcommand{ }{dots}
349 \eqcommand{   }{doublebox}
350 \eqcommand{   }{doublerulesepcolor}
351 \eqcommand{   }{doublerulesep}
352 \eqcommand{   }{downarrow}
353 \eqcommand{ }{dp}
354 \eqcommand{ }{dump}
355 \eqcommand{ }{edef}
356 \eqcommand{   }{egroup}
357 \eqcommand{   }{eject}
358 \eqcommand{ }{else}
359 \eqcommand{ }{em}

```




```

360 \eqcommand{    }{emergencystretch}
361 \eqcommand{    }{emph}
362 \eqcommand{@    }{@empty}
363 \eqcommand{    }{empty}
364 \eqcommand{    }{emptyset}
365 \eqcommand{    }{end}
366 \eqcommand{    }{endL}
367 \eqcommand{    }{endR}
368 \eqcommand{    }{endcsname}
369 \eqcommand{    }{endfirsthead}
370 \eqcommand{    }{endfoot}
371 \eqcommand{    }{endgraf}
372 \eqcommand{    }{endgroup}
373 \eqcommand{    }{endhead}
374 \eqcommand{    }{endinput}
375 \eqcommand{    }{endlastfoot}
376 \eqcommand{    }{enlargethispage}
377 \eqcommand{    }{endline}
378 \eqcommand{    }{endlinechar}
379 \eqcommand{    }{enspace}
380 \eqcommand{    }{enskip}
381 \eqcommand{    }{eqcommand}
382 \eqcommand{    }{eqenvironment}
383 \eqcommand{    }{eqref}
384 \eqcommand{    }{errhelp}
385 \eqcommand{    }{errmessage}
386 \eqcommand{    }{errorcontextlines}
387 \eqcommand{    }{errorstopmode}
388 \eqcommand{    }{escapechar}
389 \eqcommand{    }{euro}
390 \eqcommand{    }{evensidemargin}
391 \eqcommand{    }{everycr}
392 \eqcommand{    }{everydisplay}
393 \eqcommand{    }{everyhbox}
394 \eqcommand{    }{everyjob}
395 \eqcommand{    }{everymath}
396 \eqcommand{    }{everypar}
397 \eqcommand{    }{everyvbox}
398 \eqcommand{    }{ExecuteOptions}
399 \eqcommand{    }{exhyphenpenalty}
400 \eqcommand{    }{expandafter}
401 \eqcommand{    }{extracolsep}
402 \eqcommand{@    }{@firstofone}
403 \eqcommand{@    }{@firstoftwo}
404 \eqcommand{ @ }{f@ur}
405 \eqcommand{    }{fam}
406 \eqcommand{    }{fancypage}
407 \eqcommand{    }{fbox}
408 \eqcommand{    }{fboxrule}
409 \eqcommand{    }{fboxsep}

```



```

410 \eqcommand{      }{fcolorbox}
411 \eqcommand{ }{fi}
412 \eqcommand{      }{figurename}
413 \eqcommand{      }{filbreak}
414 \eqcommand{ }{fill}
415 \eqcommand{      }{firstmark}
416 \eqcommand{ }{flat}
417 \eqcommand{      }{floatpagefraction}
418 \eqcommand{      }{floatingpenalty}
419 \eqcommand{      }{floatsep}
420 \eqcommand{      }{flushbottom}
421 \eqcommand{      }{fmtname}
422 \eqcommand{      }{fmtversion}
423 \eqcommand{      }{fnsymbol}
424 \eqcommand{ }{font}
425 \eqcommand{      }{fontdimen}
426 \eqcommand{      }{fontencoding}
427 \eqcommand{      }{fontfamily}
428 \eqcommand{      }{fontname}
429 \eqcommand{      }{fontseries}
430 \eqcommand{      }{fontshape}
431 \eqcommand{      }{fontsize}
432 \eqcommand{      }{footheight}
433 \eqcommand{      }{footins}
434 \eqcommand{ }{footnote}
435 \eqcommand{      }{footnotemark}
436 \eqcommand{      }{footnoterule}
437 \eqcommand{      }{footnotesep}
438 \eqcommand{      }{footnotesize}
439 \eqcommand{      }{footnotetext}
440 \eqcommand{      }{footskip}
441 \eqcommand{ }{frame}
442 \eqcommand{      }{framebox}
443 \eqcommand{      }{frenchspacing}
444 \eqcommand{      }{frontmatter}
445 \eqcommand{      }{futurelet}
446 \eqcommand{@      }{@gobble}
447 \eqcommand{@      }{@gobbletwo}
448 \eqcommand{@      }{@gobblefour}
449 \eqcommand{@      }{@gtempa}
450 \eqcommand{@      }{@gtempb}
451 \eqcommand{ }{gdef}
452 \eqcommand{      }{GenericInfo}
453 \eqcommand{      }{GenericWarning}
454 \eqcommand{      }{GenericError}
455 \eqcommand{ }{global}
456 \eqcommand{      }{globaldefs}
457 \eqcommand{      }{glossary}
458 \eqcommand{      }{glossaryentry}
459 \eqcommand{      }{goodbreak}

```



```

460 \eqcommand{ }{graphpaper}
461 \eqcommand{ }{guillemotleft}
462 \eqcommand{ }{guillemotright}
463 \eqcommand{ }{guilsinglleft}
464 \eqcommand{ }{guilsinglright}
465 \eqcommand{ }{halign}
466 \eqcommand{ }{hang}
467 \eqcommand{ }{hangafter}
468 \eqcommand{ }{hangindent}
469 \eqcommand{ }{hbadness}
470 \eqcommand{ }{hbox}
471 \eqcommand{ }{headheight}
472 \eqcommand{ }{headsep}
473 \eqcommand{ }{headtoname}
474 \eqcommand{ }{heartsuit}
475 \eqcommand{ }{height}
476 \eqcommand{ }{hfil}
477 \eqcommand{ }{hfill}
478 \eqcommand{ }{hfilneg}
479 \eqcommand{ }{hfuzz}
480 \eqcommand{ }{hideskip}
481 \eqcommand{ }{hidewidth}
482 \bidi@csletcs{ }{hline}% this is an exception
483 \eqcommand{ }{hoffset}
484 \eqcommand{ }{holdinginserts}
485 \eqcommand{ }{hrboxsep}
486 \eqcommand{ }{hrule}
487 \eqcommand{ }{hrulefill}
488 \eqcommand{ }{hsize}
489 \eqcommand{ }{hskip}
490 \eqcommand{ }{hspace}
491 \eqcommand{ }{hss}
492 \eqcommand{ }{ht}
493 \eqcommand{ }{huge}
494 \eqcommand{ }{Huge}
495 \eqcommand{ }{hyperlink}
496 \eqcommand{ }{hypersetup}
497 \eqcommand{ }{hypertarget}
498 \eqcommand{ }{hyphenation}
499 \eqcommand{ }{hyphenchar}
500 \eqcommand{ }{hyphenpenalty}
501 \eqcommand{@ }{@ifclassloaded}
502 \eqcommand{@ }{@ifdefinable}
503 \eqcommand{@ }{@ifnextchar}
504 \eqcommand{@ }{@ifpackageloaded}
505 \eqcommand{@ }{@ifstar}
506 \eqcommand{@ }{@ifundefined}
507 \eqcommand{ }{if}
508 \eqcommand{ @ }{@if@tempswa}
509 \eqcommand{ }{ifcase}

```



```

510 \eqcommand{ }{ifcat}
511 \eqcommand{ }{ifdefined}
512 \eqcommand{ }{ifdim}
513 \eqcommand{ }{ifeof}
514 \eqcommand{ }{iff}
515 \eqcommand{ }{iffalse}
516 \eqcommand{ }{IfFileExists}
517 \eqcommand{ }{ifhbox}
518 \eqcommand{ }{ifhmode}
519 \eqcommand{ }{ifinner}
520 \eqcommand{ }{ifmmode}
521 \eqcommand{ }{ifnum}
522 \eqcommand{ }{ifodd}
523 \eqcommand{ }{ifthenelse}
524 \eqcommand{ }{iftrue}
525 \eqcommand{ }{ifvbox}
526 \eqcommand{ }{ifvmode}
527 \eqcommand{ }{ifvoid}
528 \eqcommand{ }{ifx}
529 \eqcommand{ }{ignorespaces}
530 \eqcommand{ }{immediate}
531 \eqcommand{ }{include}
532 \eqcommand{ }{includegraphics}
533 \eqcommand{ }{includeonly}
534 \eqcommand{ }{indent}
535 \eqcommand{ }{index}
536 \eqcommand{ }{indexentry}
537 \eqcommand{ }{indexname}
538 \eqcommand{ }{indexspace}
539 \eqcommand{ }{input}
540 \eqcommand{ }{InputIfFileExists}
541 \eqcommand{ }{inputlineno}
542 \eqcommand{ }{insert}
543 \eqcommand{ }{insertpenalties}
544 \eqcommand{ }{interfootnotelinepenalty}
545 \eqcommand{ }{interdisplaylinepenalty}
546 \eqcommand{ }{interlinepenalty}
547 \eqcommand{ }{intertext}
548 \eqcommand{ }{intertextsep}
549 \eqcommand{ }{invisible}
550 \eqcommand{ }{itdefault}
551 \eqcommand{ }{itshape}
552 \eqcommand{ }{item}
553 \eqcommand{ }{itemindent}
554 \eqcommand{ }{itemsep}
555 \eqcommand{ }{iterate}
556 \eqcommand{ }{itshape}
557 \eqcommand{ }{jobname}
558 \eqcommand{ }{jot}
559 \eqcommand{ }{kern}

```



```

560 \eqcommand{ }{kill}
561 \eqcommand{ }{label}
562 \eqcommand{ }{labelenumi}
563 \eqcommand{ }{labelenumii}
564 \eqcommand{ }{labelenumiii}
565 \eqcommand{ }{labelenumiv}
566 \eqcommand{ }{labelitemi}
567 \eqcommand{ }{labelitemii}
568 \eqcommand{ }{labelitemiii}
569 \eqcommand{ }{labelitemiv}
570 \eqcommand{ }{labelsep}
571 \eqcommand{ }{labelwidth}
572 \eqcommand{ }{language}
573 \eqcommand{ }{large}
574 \eqcommand{ }{Large}
575 \eqcommand{ }{LARGE}
576 \eqcommand{ }{lastbox}
577 \eqcommand{ }{lastkern}
578 \eqcommand{ }{lastpenalty}
579 \eqcommand{ }{lastskip}
580 \eqcommand{ }{LaTeX}
581 \eqcommand{ }{LaTeXe}
582 \eqcommand{ }{lccode}
583 \eqcommand{ }{ldots}
584 \eqcommand{ }{leaders}
585 \eqcommand{ }{leavevmode}
586 \eqcommand{ }{left}
587 \eqcommand{ }{leftmargin}
588 \eqcommand{ }{leftmargini}
589 \eqcommand{ }{leftmarginii}
590 \eqcommand{ }{leftmarginiii}
591 \eqcommand{ }{leftmarginiv}
592 \eqcommand{ }{leftmarginv}
593 \eqcommand{ }{leftmarginvi}
594 \eqcommand{ }{leftmark}
595 \eqcommand{ }{leftpageskip}
596 \eqcommand{ }{leftskip}
597 \eqcommand{ }{let}
598 \eqcommand{ }{line}
599 \eqcommand{ }{linebreak}
600 \eqcommand{ }{linepenalty}
601 \eqcommand{ }{lineskip}
602 \eqcommand{ }{lineskiplimit}
603 \eqcommand{ }{linespread}
604 \eqcommand{ }{linethickness}
605 \eqcommand{ }{linewidth}
606 \eqcommand{ }{listfigurename}
607 \eqcommand{ }{listfiles}
608 \eqcommand{ }{listoffigures}
609 \eqcommand{ }{listoftables}

```



```

610 \eqcommand{      }{listparindent}
611 \eqcommand{      }{listtablename}
612 \eqcommand{      }{LoadClass}
613 \eqcommand{      }{LoadClassWithOptions}
614 \eqcommand{ }{location}
615 \eqcommand{ }{long}
616 \eqcommand{ }{looseness}
617 \eqcommand{ }{lower}
618 \eqcommand{@ }{@makeother}
619 \eqcommand{@ }{@m}
620 \eqcommand{ @ }{@M}
621 \eqcommand{ @ }{@Mi}
622 \eqcommand{ @ }{@Mii}
623 \eqcommand{ @ }{@Miii}
624 \eqcommand{ @ }{@Miv}
625 \eqcommand{ @ }{@MM}
626 \eqcommand{ @ }{@m@ne}
627 \eqcommand{ }{mag}
628 \eqcommand{ }{magstep}
629 \eqcommand{ }{magstephalf}
630 \eqcommand{ }{mainmatter}
631 \eqcommand{ }{makeatletter}
632 \eqcommand{ }{makeatother}
633 \eqcommand{ }{makebox}
634 \eqcommand{ }{makeglossary}
635 \eqcommand{ }{makeindex}
636 \eqcommand{ }{makelabel}
637 \eqcommand{ }{makelabels}
638 \eqcommand{ }{MakeLowercase}
639 \eqcommand{ }{maketitle}
640 \eqcommand{ }{MakeUppercase}
641 \eqcommand{ }{marginpar}
642 \eqcommand{ }{marginparpush}
643 \eqcommand{ }{marginparsep}
644 \eqcommand{ }{marginparwidth}
645 \eqcommand{ }{mark}
646 \eqcommand{ }{markboth}
647 \eqcommand{ }{markright}
648 \eqcommand{ }{mathaccent}
649 \eqcommand{ }{mathchar}
650 \eqcommand{ }{mathchardef}
651 \eqcommand{ }{mathcode}
652 \eqcommand{ }{mathrm}
653 \eqcommand{ }{maxdeadcycles}
654 \eqcommand{ }{maxdepth}
655 \eqcommand{ }{maxdimen}
656 \eqcommand{ }{mbox}
657 \eqcommand{ }{mdseries}
658 \eqcommand{ }{meaning}
659 \eqcommand{ }{mediumseries}

```



```

660 \eqcommand{      }\{medmuskip}
661 \eqcommand{      }\{medskip}
662 \eqcommand{      }\{medskipamount}
663 \eqcommand{      }\{medspace}
664 \eqcommand{ }{message}
665 \eqcommand{      }\{MessageBreak}
666 \eqcommand{      }\{minrowclearance}
667 \eqcommand{      }\{mkern}
668 \eqcommand{ }{month}
669 \eqcommand{      }\{moveleft}
670 \eqcommand{      }\{moveright}
671 \eqcommand{      }\{mskip}
672 \eqcommand{ @ }{m@th}
673 \eqcommand{      }\{multicolumn}
674 \eqcommand{ }{multiply}
675 \eqcommand{      }\{multispan}
676 \eqcommand{      }\{muskip}
677 \eqcommand{      }\{muskipdef}
678 \eqcommand{@ }{@namedef}
679 \eqcommand{@ }{@nameuse}
680 \eqcommand{ @}{@one}
681 \eqcommand{ }{name}
682 \eqcommand{      }\{natural}
683 \eqcommand{      }\{nearrow}
684 \eqcommand{      }\{nearrower}
685 \eqcommand{      }\{NeedsTeXFormat}
686 \eqcommand{ }{neg}
687 \eqcommand{      }\{negmedspace}
688 \eqcommand{      }\{negthickspace}
689 \eqcommand{      }\{negthinspace}
690 \eqcommand{ }{newboolean}
691 \eqcommand{      }\{newbox}
692 \eqcommand{      }\{newcommand}
693 \eqcommand{      }\{newcount}
694 \eqcommand{      }\{newcounter}
695 \eqcommand{      }\{newdimen}
696 \eqcommand{ }{newenvironment}
697 \eqcommand{      }\{newfam}
698 \eqcommand{ }{newfont}
699 \eqcommand{      }\{newhelp}
700 \eqcommand{      }\{newinsert}
701 \eqcommand{      }\{newlabel}
702 \eqcommand{      }\{newlength}
703 \eqcommand{ }{newline}
704 \eqcommand{      }\{newlinechar}
705 \eqcommand{      }\{newmuskip}
706 \eqcommand{      }\{newpage}
707 \eqcommand{      }\{newread}
708 \eqcommand{      }\{newsavebox}
709 \eqcommand{      }\{newskip}

```



```

710 \eqcommand{    }\{newtheorem}
711 \eqcommand{    }\{newtoks}
712 \eqcommand{    }\{newwrite}
713 \eqcommand{    }\{noalign}
714 \eqcommand{    }\{nobreak}
715 \eqcommand{    }\{nobreakspace}
716 \eqcommand{    }\{nocite}
717 \eqcommand{    }\{noexpand}
718 \eqcommand{    }\{nofiles}
719 \eqcommand{    }\{noindent}
720 \eqcommand{    }\{nointerlineskip}
721 \eqcommand{    }\{nolimits}
722 \eqcommand{    }\{nolinebreak}
723 \eqcommand{    }\{nonstopmode}
724 \eqcommand{    }\{nonfrenchspacing}
725 \eqcommand{    }\{nonumber}
726 \eqcommand{    }\{nopagebreak}
727 \eqcommand{    }\{normalbaselines}
728 \eqcommand{    }\{normalbaselineskip}
729 \eqcommand{    }\{normalcolor}
730 \eqcommand{    }\{normalfont}
731 \eqcommand{    }\{normallineskip}
732 \eqcommand{    }\{normallineskiplimit}
733 \eqcommand{    }\{normalmarginpar}
734 \eqcommand{    }\{normalsize}
735 \eqcommand{    }\{notag}
736 \eqcommand{    }\{null}
737 \eqcommand{    }\{nullfont}
738 \eqcommand{    }\{number}
739 \eqcommand{    }\{numberline}
740 \eqcommand{    }\{numberwithin}
741 \eqcommand{    }\{@evenfoot}
742 \eqcommand{    }\{@evenhead}
743 \eqcommand{    }\{@oddfoot}
744 \eqcommand{    }\{@oddhead}
745 \eqcommand{    }\{@outeqntrue}
746 \eqcommand{    }\{@outeqnfalse}
747 \eqcommand{    }\{obeylines}
748 \eqcommand{    }\{obeyspaces}
749 \eqcommand{    }\{oddsidemargin}
750 \eqcommand{    }\{offinterlineskip}
751 \eqcommand{    }\{omit}
752 \eqcommand{@    }\{@onlypreamble}
753 \eqcommand{    }\{onecolumn}
754 \eqcommand{    }\{onlynotes}
755 \eqcommand{    }\{onlyslides}
756 \eqcommand{    }\{openin}
757 \eqcommand{    }\{openout}
758 \eqcommand{    }\{OptionNotUsed}
759 \eqcommand{    }\{or}

```




```

760 \eqcommand{ }{outer}
761 \eqcommand{ }{output}
762 \eqcommand{ }{outputpenalty}
763 \eqcommand{ }{overfullrule}
764 \eqcommand{@ }{@preamblecmds}
765 \eqcommand{@ }{p@}
766 \eqcommand{ }{PackageError}
767 \eqcommand{ }{PackageInfo}
768 \eqcommand{ }{PackageWarning}
769 \eqcommand{ }{PackageWarningNoLine}
770 \eqcommand{ }{pagebreak}
771 \eqcommand{ }{pagecolor}
772 \eqcommand{ }{pagedepth}
773 \eqcommand{ }{pagefillstretch}
774 \eqcommand{ }{pagefillstretch}
775 \eqcommand{ }{pagefilstretch}
776 \eqcommand{ }{pagegoal}
777 \eqcommand{ }{pagename}
778 \eqcommand{ }{pagenumbering}
779 \eqcommand{ }{pageref}
780 \eqcommand{ }{pagerulewidth}
781 \eqcommand{ }{pageshrink}
782 \eqcommand{ }{pagestretch}
783 \eqcommand{ }{pagestyle}
784 \eqcommand{ }{pagetotal}
785 \eqcommand{ }{paperheight}
786 \eqcommand{ }{paperwidth}
787 \bidi@csdefcs{ }{par}% this is an exception since \par is redefined only in some circumstances
788 \eqcommand{ }{paragraph}
789 \eqcommand{ }{parallel}
790 \eqcommand{ }{parbox}
791 \eqcommand{ }{parfillskip}
792 \eqcommand{ }{parindent}
793 \eqcommand{ }{parsep}
794 \eqcommand{ }{parshape}
795 \eqcommand{ }{parskip}
796 \eqcommand{ }{part}
797 \eqcommand{ }{partname}
798 \eqcommand{ }{partopsep}
799 \eqcommand{ }{PassOptionToClass}
800 \eqcommand{ }{PassOptionToPackage}
801 \eqcommand{ }{path}
802 \eqcommand{ }{patterns}
803 \eqcommand{ }{pausing}
804 \eqcommand{ }{penalty}
805 \eqcommand{ }{phantom}
806 \eqcommand{ }{poptabs}
807 \eqcommand{ }{postdisplaypenalty}
808 \eqcommand{ }{predisplaydirection}
809 \eqcommand{ }{predisdisplaypenalty}

```



```

810 \eqcommand{      }{predisplaysize}
811 \eqcommand{      }{pretolerance}
812 \eqcommand{      }{prevdepth}
813 \eqcommand{      }{prevgraf}
814 \eqcommand{      }{printindex}
815 \eqcommand{      }{ProcessOptions}
816 \eqcommand{ }{protect}
817 \eqcommand{      }{providecommand}
818 \eqcommand{      }{ProvidesClass}
819 \eqcommand{      }{ProvidesFile}
820 \eqcommand{      }{ProvidesPackage}
821 \eqcommand{      }{pushtabs}
822 \eqcommand{ }{quad}
823 \eqcommand{      }{qqquad}
824 \eqcommand{@      }{@outputpagerestore}
825 \eqcommand{      }{radical}
826 \eqcommand{      }{raggedbottom}
827 \eqcommand{      }{raggedleft}
828 \eqcommand{      }{raggedright}
829 \eqcommand{      }{raise}
830 \eqcommand{      }{raisebox}
831 \eqcommand{      }{raisetag}
832 \eqcommand{      }{rangle}
833 \eqcommand{ }{rceil}
834 \eqcommand{      }{read}
835 \eqcommand{      }{ref}
836 \eqcommand{      }{reflectbox}
837 \eqcommand{      }{refname}
838 \eqcommand{      }{refstepcounter}
839 \eqcommand{ }{relax}
840 \eqcommand{      }{removelastskip}
841 \eqcommand{      }{renewcommand}
842 \eqcommand{      }{renewenvironment}
843 \eqcommand{      }{RequirePackage}
844 \eqcommand{      }{RequirePackageWithOptions}
845 \eqcommand{      }{resizebox}
846 \eqcommand{      }{reversemarginpar}
847 \eqcommand{ }{rfloor}
848 \eqcommand{ }{right}
849 \eqcommand{      }{rightmargin}
850 \eqcommand{      }{rightmark}
851 \eqcommand{      }{rightpageskip}
852 \eqcommand{      }{rightskip}
853 \eqcommand{      }{rmdefault}
854 \eqcommand{      }{rmfamily}
855 \eqcommand{      }{Roman}
856 \eqcommand{      }{roman}
857 \eqcommand{      }{romannumeral}
858 \eqcommand{      }{rotatebox}
859 \eqcommand{      }{rowcolor}

```



```

860 \eqcommand{ }{rule}
861 \eqcommand{@ }{@secondoftwo}
862 \eqcommand{@ }{@spaces}
863 \eqcommand{ }{samepage}
864 \eqcommand{ }{savebox}
865 \eqcommand{ }{sbox}
866 \eqcommand{ }{scalebox}
867 \eqcommand{ }{scdefault}
868 \eqcommand{ }{scshape}
869 \eqcommand{ }{setkeys}
870 \eqcommand{ }{scriptfont}
871 \eqcommand{ }{scriptscriptfont}
872 \eqcommand{ }{scriptscriptstyle}
873 \eqcommand{ }{scriptsize}
874 \eqcommand{ }{scripstyle}
875 \eqcommand{ }{scrollmode}
876 \eqcommand{ }{section}
877 \eqcommand{ }{secdef}
878 \eqcommand{ }{see}
879 \eqcommand{ }{seealso}
880 \eqcommand{ }{seename}
881 \eqcommand{ }{selectfont}
882 \eqcommand{ }{setboolean}
883 \eqcommand{ }{setbox}
884 \eqcommand{ }{setcounter}
885 \eqcommand{ }{setlength}
886 \eqcommand{ }{setminus}
887 \eqcommand{ }{SetSymbolFont}
888 \eqcommand{ }{settodepth}
889 \eqcommand{ }{settoheight}
890 \eqcommand{ }{settowidth}
891 \eqcommand{ }{sfcode}
892 \eqcommand{ }{sfdefault}
893 \eqcommand{ }{sffamily}
894 \eqcommand{ }{shadowbox}
895 \eqcommand{ }{sharp}
896 \eqcommand{ }{shipout}
897 \eqcommand{ }{shortstack}
898 \eqcommand{ }{show}
899 \eqcommand{ }{showbox}
900 \eqcommand{ }{showboxbreadth}
901 \eqcommand{ }{showboxdepth}
902 \eqcommand{ }{showlists}
903 \eqcommand{ }{showthe}
904 \eqcommand{ }{simplefontmode}
905 \eqcommand{@}{sxt@@n}
906 \eqcommand{ }{skewchar}
907 \eqcommand{ }{skip}
908 \eqcommand{@}{skip@}
909 \eqcommand{ }{skipdef}

```



```

910 \eqcommand{ }{sl}
911 \eqcommand{ }{sldefault}
912 \eqcommand{ }{slshape}
913 \eqcommand{ }{sloppy}
914 \eqcommand{ }{slshape}
915 \eqcommand{ }{small}
916 \eqcommand{ }{smallskip}
917 \eqcommand{ }{smallskipamount}
918 \eqcommand{ }{smash}
919 \eqcommand{ }{smile}
920 \eqcommand{ }{snglfntlocatcode}
921 \eqcommand{ }{space}
922 \eqcommand{ }{spacefactor}
923 \eqcommand{ }{spaceskip}
924 \eqcommand{ }{spadesuit}
925 \eqcommand{ }{span}
926 \eqcommand{ }{special}
927 \eqcommand{ }{splitmaxdepth}
928 \eqcommand{ }{splittopskip}
929 \eqcommand{ }{star}
930 \eqcommand{ }{stepcounter}
931 \eqcommand{ }{stretch}
932 \eqcommand{ }{string}
933 \eqcommand{ }{strut}
934 \eqcommand{ }{strutbox}
935 \eqcommand{ }{subitem}
936 \eqcommand{ }{subparagraph}
937 \eqcommand{ }{subsection}
938 \eqcommand{ }{substack}
939 \eqcommand{ }{subsubitem}
940 \eqcommand{ }{subsubsection}
941 \eqcommand{ }{subset}
942 \eqcommand{ }{subseteq}
943 \eqcommand{ }{supereject}
944 \eqcommand{ }{suppressfloats}
945 \eqcommand{@ }{@tempa}
946 \eqcommand{@ }{@tempb}
947 \eqcommand{@ }{@tempc}
948 \eqcommand{@ }{@tempd}
949 \eqcommand{@ }{@tempe}
950 \eqcommand{@ }{@tempboxa}
951 \eqcommand{@ }{@tempcnta}
952 \eqcommand{@ }{@tempcntb}
953 \eqcommand{@ }{@tempdima}
954 \eqcommand{@ }{@tempdimb}
955 \eqcommand{@ }{@tempdimc}
956 \eqcommand{@ }{@tempskipa}
957 \eqcommand{@ }{@tempskipb}
958 \eqcommand{@ }{@tempswafalse}
959 \eqcommand{@ }{@tempswatrue}

```



```

960 \eqcommand{@ }{@temptokena}
961 \eqcommand{ }{@thefnmark}
962 \eqcommand{@ }{@thirdofthree}
963 \eqcommand{ }{tabbingsep}
964 \eqcommand{ }{tabcolsep}
965 \eqcommand{ }{tableofcontents}
966 \eqcommand{ }{tablename}
967 \eqcommand{ }{tabskip}
968 \eqcommand{ }{tabularnewline}
969 \eqcommand{ }{tag}
970 \eqcommand{ }{telephone}
971 \eqcommand{ }{TeX}
972 \eqcommand{ }{text}
973 \eqcommand{ }{textbullet}
974 \eqcommand{ }{textfont}
975 \eqcommand{ }{textemdash}
976 \eqcommand{ }{textendash}
977 \eqcommand{ }{textexclamdown}
978 \eqcommand{ }{textperiodcentered}
979 \eqcommand{ }{textquestiondown}
980 \eqcommand{ }{textquotedblleft}
981 \eqcommand{ }{textquotedblright}
982 \eqcommand{ }{textquoteleft}
983 \eqcommand{ }{textquoteright}
984 \eqcommand{ }{textvisiblespace}
985 \eqcommand{ }{textbackslash}
986 \eqcommand{ }{textbar}
987 \eqcommand{ }{textgreater}
988 \eqcommand{ }{textless}
989 \eqcommand{ }{textbf}
990 \eqcommand{ }{textcircled}
991 \eqcommand{ }{textcolor}
992 \eqcommand{ }{textcompwordmark}
993 \eqcommand{ }{textfloatsep}
994 \eqcommand{ }{textfraction}
995 \eqcommand{ }{textheight}
996 \eqcommand{ }{textindent}
997 \eqcommand{ }{textit}
998 \eqcommand{ }{textmd}
999 \eqcommand{ }{textnormal}
1000 \eqcommand{ }{textregistered}
1001 \eqcommand{ }{textrm}
1002 \eqcommand{ }{textsc}
1003 \eqcommand{ }{textsf}
1004 \eqcommand{ }{textsl}
1005 \eqcommand{ }{textstyle}
1006 \eqcommand{ }{textsuperscript}
1007 \eqcommand{ }{texttrademark}
1008 \eqcommand{ }{texttt}
1009 \eqcommand{ }{textup}

```



```

1010 \eqcommand{      }{textwidth}
1011 \eqcommand{      }{thanks}
1012 \eqcommand{      }{the}
1013 \eqcommand{      }{thempfn}
1014 \eqcommand{      }{thicklines}
1015 \eqcommand{      }{thickmuskip}
1016 \eqcommand{      }{thinmuskip}
1017 \eqcommand{      }{thickspace}
1018 \eqcommand{      }{thinlines}
1019 \eqcommand{      }{thinspace}
1020 \eqcommand{      }{thisfancypage}
1021 \eqcommand{      }{thispagestyle}
1022 \eqcommand{ @}{thr@@}
1023 \eqcommand{ }{tilde}
1024 \eqcommand{ }{tiny}
1025 \eqcommand{ }{time}
1026 \eqcommand{ }{times}
1027 \eqcommand{ }{title}
1028 \eqcommand{ }{to}
1029 \eqcommand{ }{today}
1030 \eqcommand{ }{toks}
1031 \eqcommand{      }{toksdef}
1032 \eqcommand{      }{tolerance}
1033 \eqcommand{ }{top}
1034 \eqcommand{      }{topfigrule}
1035 \eqcommand{      }{topfraction}
1036 \eqcommand{      }{topmargin}
1037 \eqcommand{      }{topmark}
1038 \eqcommand{      }{toppageskip}
1039 \eqcommand{      }{topsep}
1040 \eqcommand{      }{topskip}
1041 \eqcommand{      }{totalheight}
1042 \eqcommand{      }{tracingall}
1043 \eqcommand{      }{tracingcommands}
1044 \eqcommand{      }{tracinglostchars}
1045 \eqcommand{      }{tracingmacros}
1046 \eqcommand{      }{tracingonline}
1047 \eqcommand{      }{tracingoutput}
1048 \eqcommand{      }{tracingpages}
1049 \eqcommand{      }{tracingparagraphs}
1050 \eqcommand{      }{tracingrestores}
1051 \eqcommand{      }{tracingstats}
1052 \eqcommand{ }{triangle}
1053 \eqcommand{      }{ttdefault}
1054 \eqcommand{      }{ttfamily}
1055 \eqcommand{ @}{tw@}
1056 \eqcommand{      }{twocolumn}
1057 \eqcommand{      }{typein}
1058 \eqcommand{      }{typeout}
1059 \eqcommand{      }{uccode}

```



```

1060 \eqcommand{      }\{uchyph\}
1061 \eqcommand{      }\{underline\}
1062 \eqcommand{      }\{unhbox\}
1063 \eqcommand{      }\{unhcopy\}
1064 \eqcommand{      }\{unitlength\}
1065 \eqcommand{      }\{unkern\}
1066 \eqcommand{      }\{unpenalty\}
1067 \eqcommand{      }\{unskip\}
1068 \eqcommand{      }\{unvbox\}
1069 \eqcommand{      }\{unvcopy\}
1070 \eqcommand{      }\{updefault\}
1071 \eqcommand{      }\{upshape\}
1072 \eqcommand{      }\{usebox\}
1073 \eqcommand{      }\{usecounter\}
1074 \eqcommand{      }\{usefont\}
1075 \eqcommand{      }\{usepackage\}
1076 \eqcommand{@      }\{@vobeyspaces\}
1077 \eqcommand{@      }\{@void\}
1078 \eqcommand{      }\{vadjust\}
1079 \eqcommand{      }\{valign\}
1080 \eqcommand{      }\{value\}
1081 \eqcommand{      }\{vbadness\}
1082 \eqcommand{      }\{vbox\}
1083 \eqcommand{      }\{vcenter\}
1084 \eqcommand{      }\{verb\}
1085 \eqcommand{      }\{vfil\}
1086 \eqcommand{      }\{vfill\}
1087 \eqcommand{      }\{vfilneg\}
1088 \eqcommand{      }\{vfuzz\}
1089 \eqcommand{      }\{visible\}
1090 \eqcommand{      }\{vline\}
1091 \eqcommand{      }\{voffset\}
1092 \eqcommand{      }\@}\{voidb@x\}
1093 \eqcommand{      }\{vpageref\}
1094 \eqcommand{      }\{vrboxsep\}
1095 \eqcommand{      }\{vref\}
1096 \eqcommand{      }\{vrule\}
1097 \eqcommand{      }\{vsize\}
1098 \eqcommand{      }\{vskip\}
1099 \eqcommand{      }\{vspace\}
1100 \eqcommand{      }\{vsplit\}
1101 \eqcommand{      }\{vss\}
1102 \eqcommand{      }\{vtop\}
1103 \eqcommand{      }\{wd\}
1104 \eqcommand{      }\{whiledo\}
1105 \eqcommand{      }\{widehat\}
1106 \eqcommand{      }\{widetilde\}
1107 \eqcommand{      }\{widowpenalty\}
1108 \eqcommand{      }\{width\}
1109 \eqcommand{      }\{wlog\}

```



```

1110 \eqcommand{ }{write}
1111 \eqcommand{@ }{@xobeysp}
1112 \eqcommand{ @ }{@xxxii}
1113 \eqcommand{ }{xdef}
1114 \eqcommand{ }{xleaders}
1115 \eqcommand{ }{xspaceskip}
1116 \eqcommand{ }{year}
1117 \eqcommand{@ }{z@}
1118 \eqcommand{@ }{z@skip}

```

7.19 color-localise-xepersian.def

```

1119 color} \-localise-xepersian.def}[2011/03/01 v0.1 localising color package]
1120 0}{rgb}{ } \0,,0}
1121 1}{rgb}{ } \1,,1}
1122 1}{rgb}{ } \0,,0}
1123 0}{rgb}{ } \1,,0}
1124 0}{rgb}{ } \0,,1}
1125 1}{cmyk}{ } \0,,0,0}
1126 0}{cmyk}{ } \1,,0,0}
1127 0}{cmyk}{ } \0,,1,0}

```

7.20 xepersian-localise-commands-xepersian.def

```

1128 \ProvidesFile{xepersian-localise-commands-xepersian.def}[2012/07/25 v0.2 Persian localisation]
1129 \eqcommand{ }{autofootnoterule}
1130 \eqcommand{ }{AutoMathsDigits}
1131 \eqcommand{ }{DefaultMathsDigits}
1132 \eqcommand{ @ }{keyval@eq@alias@key}
1133 \eqcommand{ }{deflatinfont}
1134 \eqcommand{ }{defpersianfont}
1135 \eqcommand{ }{hboxL}
1136 \eqcommand{ }{hboxR}
1137 \eqcommand{ }{Latincite}
1138 \eqcommand{ }{latinfont}
1139 \eqcommand{ }{latintoday}
1140 \eqcommand{ }{leftfootnoterule}
1141 \eqcommand{ }{lr}
1142 \eqcommand{ }{LRE}
1143 \eqcommand{ }{LTRdblcol}
1144 \eqcommand{ }{LTRfootnote}
1145 \eqcommand{ }{LTRfootnotetext}
1146 \eqcommand{ }{LTRthanks}
1147 \eqcommand{ }{persianday}
1148 \eqcommand{ }{persianfont}
1149 \eqcommand{ }{PersianMathsDigits}
1150 \eqcommand{ }{persianmonth}
1151 \eqcommand{ }{persianyear}
1152 \eqcommand{ }{plq}
1153 \eqcommand{ }{prq}
1154 \eqcommand{ }{rightfootnoterule}

```




```

1155 \eqcommand{      }\{rl\}
1156 \eqcommand{      }\{RLE\}
1157 \eqcommand{      }\{RTLdblcol\}
1158 \eqcommand{      }\{RTLfootnote\}
1159 \eqcommand{      }\{RTLfootnotetext\}
1160 \eqcommand{      }\{RTLthanks\}
1161 \eqcommand{@      }\{@SepMark\}
1162 \eqcommand{      }\{SepMark\}
1163 \eqcommand{      }\{setdefaultbibitems\}
1164 \eqcommand{      }\{setdefaultmarginpar\}
1165 \eqcommand{      }\{setdigitfont\}
1166 \eqcommand{      }\{setfootnoteLR\}
1167 \eqcommand{      }\{setfootnoteRL\}
1168 \eqcommand{      }\{setlatintextfont\}
1169 \eqcommand{      }\{setLTR\}
1170 \eqcommand{      }\{setLTRbibitems\}
1171 \eqcommand{      }\{setLTRmarginpar\}
1172 \eqcommand{      }\{setRTL\}
1173 \eqcommand{      }\{setRTLbibitems\}
1174 \eqcommand{      }\{setRTLmarginpar\}
1175 \eqcommand{      }\{settextfont\}
1176 \eqcommand{      }\{textwidthfootnoterule\}
1177 \eqcommand{      }\{twocolumnstableofcontents\}
1178 \eqcommand{      }\{unsetfootnoteRL\}
1179 \eqcommand{      }\{unsetLTR\}
1180 \eqcommand{      }\{unsetRTL\}
1181 \eqcommand{      }\{vboxL\}
1182 \eqcommand{      }\{vboxR\}
1183 \eqcommand{      }\{XeLaTeX\}
1184 \eqcommand{      }\{XePersian\}
1185 \eqcommand{      }\{xepersianversion\}
1186 \eqcommand{      }\{xepersiandate\}
1187 \eqcommand{      }\{XeTeX\}

```

7.21 enumerate-xepersian.def

```

1188 \ProvidesFile{enumerate-xepersian.def}[2010/07/25 v0.1 adaptations for enumerate package]
1189 \def\@enloop@{%
1190   \ifx \entemp@ \def\@tempa{\@enLabel\harfi } \else
1191   \ifx \entemp@ \def\@tempa{\@enLabel\adadi } \else
1192   \ifx \entemp@ \def\@tempa{\@enLabel\tartibi } \else
1193   \ifx A\entemp \def\@tempa{\@enLabel\Alph } \else
1194   \ifx a\entemp \def\@tempa{\@enLabel\alph } \else
1195   \ifx i\entemp \def\@tempa{\@enLabel\roman } \else
1196   \ifx I\entemp \def\@tempa{\@enLabel\Roman } \else
1197   \ifx 1\entemp \def\@tempa{\@enLabel\arabic} \else
1198   \ifx \@sptoken\entemp \let\@tempa\@enSpace \else
1199   \ifx \bgroupp\entemp \let\@tempa\@enGroup \else
1200   \ifx \@enum@\entemp \let\@tempa\@gobble \else
1201   \let\@tempa\@enOther

```



```

1202 \enhook
1203 \fi\fi\fi\fi\fi\fi\fi\fi\fi\fi
1204 \@tempa}

```

7.22 latex-localise-environments-xepersian.def

```

1205 \ProvidesFile{latex-localise-environments-xepersian.def}[2010/07/25 v0.2 Persian localisation]
1206 \eqenvironment{ }{abstract}
1207 \eqenvironment{ }{appendix}
1208 \eqenvironment{ }{array}
1209 \eqenvironment{ }{center}
1210 \eqenvironment{ }{description}
1211 \eqenvironment{ }{displaymath}
1212 \eqenvironment{ }{document}
1213 \eqenvironment{ }{enumerate}
1214 \eqenvironment{ }{figure}
1215 \eqenvironment{ *}{figure*}
1216 \eqenvironment{ }{filecontents}
1217 \eqenvironment{ *}{filecontents*}
1218 \eqenvironment{ }{flushleft}
1219 \eqenvironment{ }{flushright}
1220 \eqenvironment{ }{itemize}
1221 \eqenvironment{ }{letter}
1222 \eqenvironment{ }{list}
1223 \eqenvironment{ }{longtable}
1224 \eqenvironment{ }{lrbox}
1225 \eqenvironment{ }{math}
1226 \eqenvironment{ }{matrix}
1227 \eqenvironment{ }{minipage}
1228 \eqenvironment{ }{multline}
1229 \eqenvironment{ }{note}
1230 \eqenvironment{ }{overlay}
1231 \eqenvironment{ }{picture}
1232 \eqenvironment{ }{quotation}
1233 \eqenvironment{ }{quote}
1234 \eqenvironment{ }{slide}
1235 \eqenvironment{ }{sloppypar}
1236 \eqenvironment{ }{split}
1237 \eqenvironment{ }{subarray}
1238 \eqenvironment{ }{tabbing}
1239 \eqenvironment{ }{table}
1240 \eqenvironment{ *}{table*}
1241 \eqenvironment{ }{tabular}
1242 \eqenvironment{ *}{tabular*}
1243 \eqenvironment{ }{thebibliography}
1244 \eqenvironment{ }{theindex}
1245 \eqenvironment{ }{titlepage}
1246 \eqenvironment{ }{trivlist}
1247 \eqenvironment{ }{verse}

```



7.23 xepersian-localise-environments-xepersian.def

```
1248 \ProvidesFile{xepersian-localise-environments-xepersian.def}[2010/07/25 v0.1 Persian localisat
1249 \eqenvironment{ }{latin}
1250 \eqenvironment{ }{LTR}
1251 \eqenvironment{ }{LTRitems}
1252 \eqenvironment{ }{modernpoem}
1253 \eqenvironment{ *}{modernpoem*}
1254 \eqenvironment{ }{persian}
1255 \eqenvironment{ }{RTL}
1256 \eqenvironment{ }{RTLitems}
1257 \eqenvironment{ }{traditionalpoem}
1258 \eqenvironment{ *}{traditionalpoem*}
```

7.24 extarticle-xepersian.def

```
1259 \ProvidesFile{extarticle-xepersian.def}[2010/07/25 v0.1 adaptations for extarticle class]
1260 \renewcommand\thepart { \@tartibi\c@part}
1261 \renewcommand\appendix{\par
1262 \setcounter{section}{0}%
1263 \setcounter{subsection}{0}%
1264 \gdef\thesection{\@harfi\c@section}}
```

7.25 extbook-xepersian.def

```
1265 \ProvidesFile{extbook-xepersian.def}[2010/07/25 v0.1 adaptations for extbook class]
1266 \renewcommand\frontmatter{%
1267 \cleardoublepage
1268 \@mainmatterfalse
1269 \pagenumbering{harfi}}
1270 \renewcommand\thepart { \@tartibi\c@part}
1271 \renewcommand\appendix{\par
1272 \setcounter{chapter}{0}%
1273 \setcounter{section}{0}%
1274 \gdef\@chapapp{\appendixname}%
1275 \gdef\thechapter{\@harfi\c@chapter}
1276 }%end appendix
```

7.26 extrafootnotefeatures-xepersian.def

```
1277 \ProvidesFile{extrafootnotefeatures-xepersian.def}[2012/01/01 v0.2 footnote macros for extrafo
1278 \renewcommand{\foottextfont}{\footnotesize\if@RTL@footnote\else\resetlatinfont\fi}
1279 \renewcommand{\LTRfoottextfont}{\footnotesize\resetlatinfont}
1280 \renewcommand{\RTLfoottextfont}{\footnotesize\setpersianfont}
```

7.27 extreport-xepersian.def

```
1281 \ProvidesFile{extreport-xepersian.def}[2010/07/25 v0.1 adaptations for extreport class]
1282 \renewcommand\thepart { \@tartibi\c@part}
1283 \renewcommand\appendix{\par
1284 \setcounter{chapter}{0}%
1285 \setcounter{section}{0}%
1286 \gdef\@chapapp{\appendixname}%
```



```
1287 \gdef\thechapter{\@harfi\c@chapter}}
```

7.28 flowfram-xepersian.def

```
1288 \ProvidesFile{flowfram-xepersian.def}[2010/07/25 v0.1 adaptations for flowfram package]
1289 \def\@outputpage{%
1290 \begingroup
1291   \let\protect\noexpand
1292   \@resetactivechars
1293   \global\let\@if@newlist@if@newlist
1294   \global\@newlistfalse\@parboxrestore
1295   \shipout\vbox{\set@typeset@protect
1296     \aftergroup
1297     \endgroup
1298     \aftergroup
1299     \set@typeset@protect
1300     \reset@font\normalsize\normalsfcodes
1301     \let\label\@gobble
1302     \let\index\@gobble
1303     \let\glossary\@gobble
1304     \baselineskip\z@skip
1305     \lineskip\z@skip
1306     \lineskiplimit\z@
1307     \vskip\topmargin\moveright\@themargin
1308     \vbox{%
1309       \vskip\headheight
1310       \vskip\headsep
1311       \box\@outputbox
1312     }}%
1313 \global\let@if@newlist\@if@newlist
1314 \stepcounter{page}%
1315 \setcounter{displayedframe}{0}%
1316 \let\firstmark\botmark}
```

7.29 footnote-xepersian.def

```
1317 \ProvidesFile{footnote-xepersian.def}[2017/08/09 v0.6 footnote macros for xepersian package]
1318
1319 \renewcommand*{\bidi@footnotetext@font}{\footnotesize@if@RTL@footnote\else\resetlatinfont\fi}
1320
1321 \renewcommand*{\bidi@LTRfootnotetext@font}{\footnotesize\resetlatinfont}
1322
1323 \renewcommand*{\bidi@RTLfootnotetext@font}{\footnotesize\setpersianfont}
1324
```

7.30 framed-xepersian.def

```
1325 \ProvidesFile{framed-xepersian.def}[2012/06/05 v0.1 xepersian adaptations for framed package f
1326 \renewenvironment{titled-frame}[1]{%
1327   \def\FrameCommand{\fboxsep8pt\fboxrule2pt
1328     \TitleBarFrame{\textbf{#1}}}%
1329   \def\FirstFrameCommand{\fboxsep8pt\fboxrule2pt
```



```

1330 \TitleBarFrame[ $\if@RTL\blacktriangleleft\else\blacktriangleright\fi$ ]{\textbf{#1}}}%
1331 \def\MidFrameCommand{\fboxsep8pt\fboxrule2pt
1332 \TitleBarFrame[ $\if@RTL\blacktriangleleft\else\blacktriangleright\fi$ ]{\textbf{#1} (\if@RTL
1333 \def\LastFrameCommand{\fboxsep8pt\fboxrule2pt
1334 \TitleBarFrame{\textbf{#1} (\if@RTL else\ cont\fi)}}}%
1335 \MakeFramed{\advance\hsize-20pt \FrameRestore}}%
1336 % note: 8 + 2 + 8 + 2 = 20. Don't use \width because the frame title
1337 % could interfere with the width measurement.
1338 {\endMakeFramed}

```

7.31 glossaries-xepersian.def

```

1339 \ProvidesFile{glossaries-xepersian.def}[2014/09/04 v0.4 xepersian adaptations for glossaries p
1340 \glsaddprotectedpagefmt{@harfi}
1341 \glsaddprotectedpagefmt{@tartibi}
1342 \glsaddprotectedpagefmt{@adadi}

```

7.32 hyperref-xepersian.def

```

1343 \ProvidesFile{hyperref-xepersian.def}[2015/02/02 v0.6 bilingual captions for hyperref package]
1344 \def\equationautorefname{\if@RTL else\ Equation\fi}%
1345 \def\footnoteautorefname{\if@RTL else\ footnote\fi}%
1346 \def\itemautorefname{\if@RTL else\ item\fi}%
1347 \def\figureautorefname{\if@RTL else\ Figure\fi}%
1348 \def\tableautorefname{\if@RTL else\ Table\fi}%
1349 \def\partautorefname{\if@RTL else\ Part\fi}%
1350 \def\appendixautorefname{\if@RTL else\ Appendix\fi}%
1351 \def\chapterautorefname{\if@RTL else\ chapter\fi}%
1352 \def\sectionautorefname{\if@RTL else\ section\fi}%
1353 \def\subsectionautorefname{\if@RTL else\ subsection\fi}%
1354 \def\subsubsectionautorefname{\if@RTL else\ subsubsection\fi}%
1355 \def\paragraphautorefname{\if@RTL else\ paragraph\fi}%
1356 \def\subparagraphautorefname{\if@RTL else\ subparagraph\fi}%
1357 \def\FancyVerbLineautorefname{\if@RTL else\ line\fi}%
1358 \def\theoremautorefname{\if@RTL else\ Theorem\fi}%
1359 \def\pageautorefname{\if@RTL else\ page\fi}%
1360 \AtBeginDocument{%
1361 \let\HyOrg@appendix\appendix
1362 \def\appendix{%
1363 \ltx@ifundefined{chapter}%
1364 {\gdef\theHsection{\Alph{section}}}%
1365 {\gdef\theHchapter{\Alph{chapter}}}%
1366 \xdef\Hy@chapapp{\Hy@appendixstring}%
1367 \HyOrg@appendix
1368 }
1369 }
1370 \pdfstringdefDisableCommands{%
1371 \let\lr\@firstofone
1372 \let\rl\@firstofone
1373 \def\XePersian{XePersian}
1374 }

```



```

1375 \ltx@ifundefined{@resets@pp}{%
1376 }{%
1377   \let\HyOrg@resets@pp\@resets@pp
1378   \def\@resets@pp{%
1379     \ltx@ifundefined{chapter}{%
1380       \gdef\theHsection{\Hy@AlphNoErr{section}}}%
1381     }{%
1382       \gdef\theHchapter{\Hy@AlphNoErr{chapter}}}%
1383     }%
1384     \xdef\Hy@chapapp{\Hy@appendixstring}%
1385     \HyOrg@resets@pp
1386   }%
1387 }

```

7.33 imspc-xepersian.def

```

1388 \ProvidesFile{imspc-xepersian.def}[2017/06/09 v0.5 xepersian adaptations for imspc class f
1389
1390 \renewcommand \thepart {\@tartibi\c@part}
1391 \def\appendix{\par\c@section\z@ \c@subsection\z@
1392   \let\sectionname\appendixname
1393   \def\thesection{\@harfi\c@section}}
1394

```

7.34 kashida-xepersian.def

```

1395 \ProvidesFile{kashida-xepersian.def}[2016/09/09 v0.5 implementation of Kashida for xepersian p
1396 \chardef\xepersian@zwj="200D % zero-width joiner
1397
1398 \chardef\xepersian@D=10 % dual-joiner class
1399 \chardef\xepersian@L=11 % lam
1400 \chardef\xepersian@R=12 % right-joiner
1401 \chardef\xepersian@A=13 % alef
1402 \chardef\xepersian@V=4096 % vowel or other combining mark (to be ignored)
1403
1404 \newif\if@Kashida@on
1405 \def\xepersian@kashida{\if@Kashida@on\xepersian@zwj\nobreak%
1406   \leaders\hrule height \XeTeXglyphheight\tw@ \the\XeTeXcharglyph"0640 depth \XeTeXglyphb
1407 \def\setclass#1#2{\def\theclass{#1}\def\charlist{#2}%
1408   \expandafter\dosetclass\charlist,\end}
1409 \def\dosetclass#1,#2\end{%
1410   \def\test{#1}\def\charlist{#2}%
1411   \ifx\test\empty\let\next\finishsetclass
1412   \else \XeTeXcharclass "\test = \theclass
1413     \let\next\dosetclass \fi
1414   \expandafter\next\charlist,,\end}
1415 \def\finishsetclass#1,,\end{}
1416
1417 \setclass \xepersian@A {0622,0623,0625,0627}
1418 \setclass \xepersian@R {0624,0629,062F,0630,0631,0632,0648,0698}
1419 \setclass \xepersian@D {0626,0628,062A,062B,062C,062D,062E}

```



```

1420 \setclass \xepersian@D {0633,0634,0635,0636,0637,0638,0639,063A}
1421 \setclass \xepersian@D {0640,0641,0642,0643,0645,0646,0647,0649,064A}
1422 \setclass \xepersian@D {067E,0686,06A9,06AF,06CC}
1423 \setclass \xepersian@L {0644}
1424 \setclass \xepersian@V {064B,064C,064D,064E,064F,0650,0651,0652}
1425
1426 \XeTeXinterchartoks \xepersian@D \xepersian@D = {\xepersian@kashida}
1427 \XeTeXinterchartoks \xepersian@L \xepersian@D = {\xepersian@kashida}
1428 \XeTeXinterchartoks \xepersian@D \xepersian@L = {\xepersian@kashida}
1429 \XeTeXinterchartoks \xepersian@L \xepersian@L = {\xepersian@kashida}
1430 \XeTeXinterchartoks \xepersian@D \xepersian@R = {\xepersian@kashida}
1431 \XeTeXinterchartoks \xepersian@D \xepersian@A = {\xepersian@kashida}
1432 \XeTeXinterchartoks \xepersian@L \xepersian@R = {\xepersian@kashida}
1433 \XeTeXinterchartoks \xepersian@L \xepersian@A = {}
1434
1435 \newcommand{\KashidaOn}{\@Kashida@ontrue}
1436 \newcommand{\KashidaOff}{\@Kashida@onfalse}
1437 \KashidaOn

```

7.35 listings-xepersian.def

```

1438 \ProvidesFile{listings-xepersian.def}[2014/07/17 v0.3 bilingual captions for listings package]
1439 \def\lstlistingname{\if@RTL else\ Listing\fi}
1440 \def\lstlistlistingname{\if@RTL else\ Listings\fi}

```

7.36 loadingorder-xepersian.def

```

1441 \ProvidesFile{loadingorder-xepersian.def}[2012/01/01 v0.3 making sure that xepersian is the la
1442 \bidi@isloaded{algorithmic}
1443 \bidi@isloaded{algorithm}
1444 \bidi@isloaded{backref}
1445 \bidi@isloaded{enumerate}
1446 \bidi@isloaded{tocloft}
1447 \bidi@isloaded{url}
1448 \AtBeginDocument{
1449   \if@bidi@algorithmicloaded@else
1450     \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package algorithmic after xe
1451     \fi%
1452     \if@bidi@algorithmloaded@else
1453       \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package algorithm after xepe
1454       \fi%
1455       \if@bidi@backrefloaded@else
1456         \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package backref after xepers
1457         \fi%
1458         \if@bidi@enumerateloaded@else
1459           \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package enumerate after xepe
1460           \fi%
1461           \if@bidi@tocloftloaded@else
1462             \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package tocloft after xepers
1463             \fi%
1464             \if@bidi@urlloaded@else

```



```

1465 \bidi@isloaded[\PackageError{xepersian}{Oops! you have loaded package url after xepersian
1466 \fi%
1467 }

```

7.37 localise-xepersian.def

```

1468 \ProvidesFile{localise-xepersian.def}[2014/07/10 v0.2b Persian localisation of LaTeX2e]
1469 \newcommand{\makezwnjletter}{\catcode`\=11\relax}
1470 \makezwnjletter
1471 \newcommand*\eqcommand[2]{\if@bidi@csprimitive{#2}{\bidi@csletcs{#1}{#2}}{\bidi@csdefcs{#1}{%
1472 \newcommand*\eqenvironment[2]{\newenvironment{#1}{\csname#2\endcsname}{\csname end#2\endcsna
1473 \@ifpackageloaded{keyval}{%
1474 \newcommand*\keyval@eq@alias@key[4][KV]{%
1475 \bidi@csletcs{#1@#2@#3}{#1@#2@#4}%
1476 \bidi@csletcs{#1@#2@#3@default}{#1@#2@#4@default}}%
1477 }{\@ifpackageloaded{xkeyval}{%
1478 \newcommand*\keyval@eq@alias@key[4][KV]{%
1479 \bidi@csletcs{#1@#2@#3}{#1@#2@#4}%
1480 \bidi@csletcs{#1@#2@#3@default}{#1@#2@#4@default}}%
1481 }{}}
1482 \input{latex-localise-commands-xepersian.def}
1483 \input{xepersian-localise-commands-xepersian.def}
1484 \input{latex-localise-environments-xepersian.def}
1485 \input{xepersian-localise-environments-xepersian.def}
1486 \input{latex-localise-messages-xepersian.def}
1487 \input{latex-localise-misc-xepersian.def}
1488 \input{packages-localise-xepersian.def}
1489 \aliasfontfeature{ExternalLocation}{ }
1490 \aliasfontfeature{ExternalLocation}{ }
1491 \aliasfontfeature{Renderer}{ }
1492 \aliasfontfeature{BoldFont}{ }
1493 \aliasfontfeature{Language}{ }
1494 \aliasfontfeature{Script}{ }
1495 \aliasfontfeature{UprightFont}{ }
1496 \aliasfontfeature{ItalicFont}{ }
1497 \aliasfontfeature{BoldItalicFont}{ }
1498 \aliasfontfeature{SlantedFont}{ }
1499 \aliasfontfeature{BoldSlantedFont}{ }
1500 \aliasfontfeature{SmallCapsFont}{ }
1501 \aliasfontfeature{UprightFeatures}{ }
1502 \aliasfontfeature{BoldFeatures}{ }
1503 \aliasfontfeature{ItalicFeatures}{ }
1504 \aliasfontfeature{BoldItalicFeatures}{ }
1505 \aliasfontfeature{SlantedFeatures}{ }
1506 \aliasfontfeature{BoldSlantedFeatures}{ }
1507 \aliasfontfeature{SmallCapsFeatures}{ }
1508 \aliasfontfeature{SizeFeatures}{ }
1509 \aliasfontfeature{Scale}{ }
1510 \aliasfontfeature{WordSpace}{ }
1511 \aliasfontfeature{PunctuationSpace}{ }

```




```

1512 \aliasfontfeature{FontAdjustment}{    }
1513 \aliasfontfeature{LetterSpace}{    }
1514 \aliasfontfeature{HyphenChar}{    }
1515 \aliasfontfeature{Color}{    }
1516 \aliasfontfeature{Opacity}{    }
1517 \aliasfontfeature{Mapping}{    }
1518 \aliasfontfeature{Weight}{    }
1519 \aliasfontfeature{Width}{    }
1520 \aliasfontfeature{OpticalSize}{    }
1521 \aliasfontfeature{FakeSlant}{    }
1522 \aliasfontfeature{FakeStretch}{    }
1523 \aliasfontfeature{FakeBold}{    }
1524 \aliasfontfeature{AutoFakeSlant}{    }
1525 \aliasfontfeature{AutoFakeBold}{    }
1526 \aliasfontfeature{Ligatures}{    }
1527 \aliasfontfeature{Alternate}{    }
1528 \aliasfontfeature{Variant}{    }
1529 \aliasfontfeature{Variant}{    }
1530 \aliasfontfeature{CharacterVariant}{    }
1531 \aliasfontfeature{Style}{    }
1532 \aliasfontfeature{Annotation}{    }
1533 \aliasfontfeature{RawFeature}{    }
1534 \aliasfontfeature{CharacterWidth}{    }
1535 \aliasfontfeature{Numbers}{    }
1536 \aliasfontfeature{Contextuals}{    }
1537 \aliasfontfeature{Diacritics}{    }
1538 \aliasfontfeature{Letters}{    }
1539 \aliasfontfeature{Kerning}{    }
1540 \aliasfontfeature{VerticalPosition}{    }
1541 \aliasfontfeature{Fractions}{    }
1542 \aliasfontfeatureoption{Language}{Default}{    }
1543 \aliasfontfeatureoption{Language}{Parsi}{    }
1544 \aliasfontfeatureoption{Script}{Parsi}{    }
1545 \aliasfontfeatureoption{Script}{Latin}{    }
1546 \aliasfontfeatureoption{Style}{MathScript}{    }
1547 \aliasfontfeatureoption{Style}{MathScriptScript}{    }

```

7.38 memoir-xepersian.def

```

1548 \ProvidesFile{memoir-xepersian.def}[2010/07/25 v0.1 adaptations for memoir class]
1549 \renewcommand{\@memfront}{%
1550   \@smemfront\pagenumbering{harfi}}
1551 \renewcommand{\setthesection}{\thechapter\@SepMark\harfi{section}}
1552 \renewcommand*{\thebook}{\@tartibi\c@book}
1553 \renewcommand*{\thepart}{\@tartibi\c@part}
1554 \renewcommand{\appendix}{\par
1555   \setcounter{chapter}{0}%
1556   \setcounter{section}{0}%
1557   \gdef\@chapapp{\appendixname}%
1558   \gdef\thechapter{\@harfi\c@chapter}%

```



```
1559 \anappendixtrue}
```

7.39 latex-localise-messages-xepersian.def

```
1560 latex} \-localise-messages-xepersian.def}[2011/03/01 v0.1 localising LaTeX2e messages]
```

7.40 minitoc-xepersian.def

```
1561 \ProvidesFile{minitoc-xepersian.def}[2010/07/25 v0.1 bilingual captions for minitoc package]
1562 \def\ptctitle{\if@RTL else\ Table of Contents\fi}%
1563 \def\plftitle{\if@RTL else\ List of Figures\fi}%
1564 \def\plttitle{\if@RTL else\ List of Tables\fi}%
1565 \def\mtctitle{\if@RTL else\ Contents\fi}%
1566 \def\mlftitle{\if@RTL else\ Figures\fi}%
1567 \def\mlttitle{\if@RTL else\ Tables\fi}%
1568 \def\stctitle{\if@RTL else\ Contents\fi}%
1569 \def\slftitle{\if@RTL else\ Figures\fi}%
1570 \def\slttitle{\if@RTL else\ Tables\fi}%

```

7.41 latex-localise-misc-xepersian.def

```
1571 \ProvidesFile{latex-localise-misc-xepersian.def}[2012/01/01 v0.2 miscellaneous Persian localis
1572 %}1# \ \
1573 \ @ \ @ \ \
1574 \1# \
1575 \1# @\
1576 \1# @\
1577 {\ @ \ \
1578 %}2#1# @\ \
1579 %1# \ @\ \ \ \
1580 \2# \ @\ \
1581 {{2#1# \}}
1582 undefined\ \ \
1583
1584 %{\ \ \ \ \1#} \ \} \1# \ \
1585 \ { \ \ \
1586 \ \ \
1587
1588
1589 \ \ \ \%} \#1
1590 \1#} \ \ \% \
1591 \ \ \
1592 }%
1593 \
1594 \ \ \
1595 }
1596 \ = \ \
1597
1598
1599 \@ifdefinitionfileloaded{latex-xetex-bidi}{%
1600 \def\@xfloat #1[#2]{%
1601 \@nodocument

```



```

1602 \def \@capttype {#1}%
1603 \def \@fps {#2}%
1604 \@onelevel@sanitize \@fps
1605 \def \reserved@a {!}%
1606 \ifx \reserved@a \@fps
1607   \@fpsadddefault
1608 \else
1609   \ifx \@fps \@empty
1610     \@fpsadddefault
1611   \fi
1612 \fi
1613 \ifhmode
1614   \@bsphack
1615   \@floatpenalty -\@Mii
1616 \else
1617   \@floatpenalty-\@Miii
1618 \fi
1619 \ifinner
1620   \@parmoderr\@floatpenalty\z@
1621 \else
1622   \@next\@currbox\@freelist
1623   {%
1624     \@tempcnta \sixt@@n
1625     \expandafter \@tfor \expandafter \reserved@a
1626     \expandafter :\expandafter =\@fps
1627     \do
1628     {%
1629       \if \reserved@a h%
1630         \ifodd \@tempcnta
1631         \else
1632           \advance \@tempcnta \@ne
1633         \fi
1634       \fi
1635       \if \reserved@a %
1636         \ifodd \@tempcnta
1637         \else
1638           \advance \@tempcnta \@ne
1639         \fi
1640       \fi
1641       \if \reserved@a t%
1642         \@setfpsbit \tw@
1643       \fi
1644       \if \reserved@a %
1645         \@setfpsbit \tw@
1646       \fi
1647       \if \reserved@a b%
1648         \@setfpsbit 4%
1649       \fi
1650       \if \reserved@a %
1651         \@setfpsbit 4%

```



```

1652         \fi
1653         \if \reserved@a p%
1654             \setfpsbit 8%
1655         \fi
1656         \if \reserved@a %
1657             \setfpsbit 8%
1658         \fi
1659         \if \reserved@a !%
1660             \ifnum \@tempcnta>15
1661                 \advance\@tempcnta -\sixt@@n\relax
1662             \fi
1663         \fi
1664     }%
1665     \@tempcntb \csname ftype@\@capytype \endcsname
1666     \multiply \@tempcntb \@xxxii
1667     \advance \@tempcnta \@tempcntb
1668     \global \count\@currbox \@tempcnta
1669 }%
1670 \@fltovf
1671 \fi
1672 \global \setbox\@currbox
1673 \color@vbox
1674 \normalcolor
1675 \vbox \bgroup
1676 \hsize\columnwidth
1677 \@parboxrestore
1678 \@floatboxreset
1679 }
1680 \let\bm@ \bm@c
1681 \let\bm@ \bm@l
1682 \let\bm@ \bm@r
1683 \let\bm@ \bm@b
1684 \let\bm@ \bm@t
1685 \let\bm@ \bm@s
1686 \long\def\@iiparbox#1#2[#3]#4#5{%
1687     \leavevmode
1688     \@pboxswfalse
1689     \if@hboxRconstruct\@bidi@list@minipage@parbox@not@nobtrue\fi
1690     \if@RTL\if#1t\@bidi@list@minipage@parboxtrue\else\if#1b\@bidi@list@minipage@parboxtrue\else\
1691     \setlength\@tempdima{#4}%
1692     \@begin@tempboxa\vbox{\hsize\@tempdima\@parboxrestore#5\@@par}%
1693     \ifx\relax#2\else
1694         \setlength\@tempdimb{#2}%
1695         \edef\@parboxto{to\the\@tempdimb}%
1696     \fi
1697     \if#1b\vbox
1698     \else\if#1\vbox
1699     \else\if #1t\top
1700     \else\if vtop\ #1
1701     \else\ifmmode\center

```



```

1702 \else\@pboxswtrue $\vcenter
1703 \fi\fi\fi\fi\fi
1704 \@parboxto{\let\hss\vss\let\unhbox\unvbox
1705 \csname bm@#3\endcsname}%
1706 \if@pboxsw \m@th$\fi
1707 \@end@tempboxa}
1708 \def\@iiiminipage#1#2[#3]#4{%
1709 \leavevmode
1710 \@pboxswfalse
1711 \if@hboxRconstruct\@bidi@list@minipage@parbox@not@nobtrue\fi
1712 \ifRTL\if#1t\@bidi@list@minipage@parboxtrue\else\if#1b\@bidi@list@minipage@parboxtrue\els
1713 \setlength\@tempdima{#4}%
1714 \def\@mpargs{{#1}{#2}[#3]{#4}}%
1715 \setbox\@tempboxa\vbox\bgroup
1716 \color@begingroup
1717 \hsize\@tempdima
1718 \textwidth\hsize \columnwidth\hsize
1719 \@parboxrestore
1720 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
1721 \let\@footnotetext\@mpfootnotetext
1722 \let\@LTRfootnotetext\@mpLTRfootnotetext
1723 \let\@RTLfootnotetext\@mpRTLfootnotetext
1724 \let\@listdepth\@mplistdepth \@mplistdepth\z@
1725 \@minipagerestore
1726 \@setminipage}
1727 \def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4 \else
1728 \ifnum \@lastchclass=3 5 \else
1729 \z@ \if #1c\@chnum \z@ \else
1730 \if chnum@ #1 \z@ \else
1731 \if \if@RTLtab#1r\else#1l\fi\@chnum \@one \else
1732 \if \if@RTLtab#1 \else#1\fi\@chnum \@one \else
1733 \if \if@RTLtab#1l\else#1r\fi\@chnum \tw@ \else
1734 \if \if@RTLtab#1 \else#1\fi\@chnum \tw@ \else
1735 \@chclass \if #1|\@one \else
1736 \if #1@\tw@ \else
1737 \if #1p3 \else
1738 \if 3 #1 \else \z@ \@preamerr 0\fi
1739 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
1740 \fi}%
1741 \}{}
1742 \@ifdefinitionfileloaded{array-xetex-bidi}{%
1743 \def\@testpach{\@chclass
1744 \ifnum \@lastchclass=6 \@one \@chnum \@one \else
1745 \ifnum \@lastchclass=7 5 \else
1746 \ifnum \@lastchclass=8 \tw@ \else
1747 \ifnum \@lastchclass=9 \thr@@
1748 \else \z@
1749 \ifnum \@lastchclass = 10 \else
1750 \edef\@nextchar{\expandafter\string\@nextchar}%
1751 \@chnum

```



```

1752 \if \@nextchar c\z@ \else
1753 \if \@nextchar @z\ \else
1754 \if \@nextchar \if@RTLtab r\else l\fi\@ne \else
1755 \if \@nextchar \if@RTLtab else\ fi\@ne\ \else
1756 \if \@nextchar \if@RTLtab l\else r\fi\@tw@ \else
1757 \if \@nextchar \if@RTLtab else\ @fi\@tw\ \else
1758 \z@ \@chclass
1759 \if \@nextchar |\@ne \else
1760 \if \@nextchar !6 \else
1761 \if \@nextchar @7 \else
1762 \if \@nextchar <8 \else
1763 \if \@nextchar >9 \else
1764 10
1765 \@chnum
1766 \if \@nextchar m\thr@@\else
1767 \if \@nextchar thr@@\else\
1768 \if \@nextchar p4 \else
1769 \if \@nextchar 4 \else
1770 \if \@nextchar b5 \else
1771 \if \@nextchar 5 \else
1772 \z@ \@chclass \z@ \@preamerr \z@ \fi \fi \fi \fi \fi \fi \fi
1773 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi}%
1774 }{}
1775 \ifdefinitionfileloaded{arydshln-xetex-bidi}{
1776 \ifadl@usingarypkg
1777 \def\@testpach{\@chclass
1778 \ifnum \@lastchclass=6 \@ne \@chnum \@ne \else
1779 \ifnum \@lastchclass=7 5 \else
1780 \ifnum \@lastchclass=8 \tw@ \else
1781 \ifnum \@lastchclass=9 \thr@@
1782 \else \z@
1783 \ifnum \@lastchclass = 10 \else
1784 \edef\@nextchar{\expandafter\string\@nextchar}%
1785 \@chnum
1786 \if \@nextchar c\z@ \else
1787 \if \@nextchar @z\ \else
1788 \if \@nextchar \if@RTLtab r\else l\fi\@ne \else
1789 \if \@nextchar \if@RTLtab else\ fi\@ne\ \else
1790 \if \@nextchar \if@RTLtab l\else r\fi\@tw@ \else
1791 \if \@nextchar \if@RTLtab else\ @fi\@tw\ \else
1792 \z@ \@chclass
1793 \if \@nextchar |\@ne \let\@arrayrule\adl@arrayrule \else
1794 \if \@nextchar : \@ne \let\@arrayrule\adl@arraydashrule \else
1795 \if \@nextchar ; \@ne \let\@arrayrule\adl@argarraydashrule \else
1796 \if \@nextchar !6 \else
1797 \if \@nextchar @7 \else
1798 \if \@nextchar <8 \else
1799 \if \@nextchar >9 \else
1800 10
1801 \@chnum

```



```

1802 \if \@nextchar m\thr@@\else
1803 \if \@nextchar thr@@\else\
1804 \if \@nextchar p4 \else
1805 \if \@nextchar 4 \else
1806 \if \@nextchar b5 \else
1807 \if \@nextchar 5 \else
1808 \z@ \@chclass \z@ \@preamerr \z@ \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
1809 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
1810
1811 \def\@classz{\@classx
1812 \@tempcnta \count@
1813 \prepnext@tok
1814 \@addtopreamble{\ifcase \@chnum
1815 \hfil
1816 \adl@putlrc{\dollarbegin \insert@column \dollarend}\hfil \or
1817 \hskip1sp\adl@putlrc{\dollarbegin \insert@column \dollarend}\hfil \or
1818 \hfil\hskip1sp\adl@putlrc{\dollarbegin \insert@column \dollarend}\or
1819 \setbox\adl@box\hbox \adl@startmbox{\@nextchar}\insert@column
1820 \adl@endmbox\or
1821 \setbox\adl@box\vtop \@startpbox{\@nextchar}\insert@column \@endpbox \or
1822 \setbox\adl@box\vbox \@startpbox{\@nextchar}\insert@column \@endpbox
1823 \fi}\prepnext@tok}
1824 \def\adl@class@start{4}
1825 \def\adl@class@iiiorvii{7}
1826
1827 \else
1828 \def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4\relax \else
1829 \ifnum \@lastchclass=\thr@@ 5\relax \else
1830 \z@ \if #1c\@chnum \z@ \else
1831 \if @chnum\z@\ #1 \else
1832 \if \if@RTLtab#1r\else#1l\fi\@chnum \@one \else
1833 \if \if@RTLtab#1 \else#1 \fi\@chnum \@one \else
1834 \if \if@RTLtab#1l\else#1r\fi\@chnum \tw@ \else
1835 \if \if@RTLtab#1 \else#1 \fi\@chnum \tw@ \else
1836 \@chclass
1837 \if #1|\@one \let\@arrayrule\adl@arrayrule \else
1838 \if #1:\@one \let\@arrayrule\adl@arraydashrule \else
1839 \if #1;\@one \let\@arrayrule\adl@argarraydashrule \else
1840 \if #1@\tw@ \else
1841 \if #1p\thr@@ \else
1842 \if @@thr\ #1 \else\z@ \@preamerr 0\fi
1843 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
1844
1845 \def\@arrayclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
1846 \or \or \@addamp \or
1847 \@acolampacol \or \@firstampfalse \@acol \fi
1848 \edef\@preamble{\@preamble
1849 \ifcase \@chnum
1850 \hfil\adl@putlrc{\$}\relax\@sharp$}\hfil
1851 \or \adl@putlrc{\$}\relax\@sharp$}\hfil

```



```

1852          \or \hfil\adl@putlrc{\$ \relax \@sharp$}\fi}}
1853 \def\@tabclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
1854          \or \or \@addamp \or
1855          \@acolampacol \or \@firstampfalse \@acol \fi
1856 \edef\@preamble{\@preamble
1857 \ifcase \@chnum
1858          \hfil\adl@putlrc{\@sharp\unskip}\hfil
1859          \or \adl@putlrc{\@sharp\unskip}\hfil
1860          \or \hfil\hskip\z@ \adl@putlrc{\@sharp\unskip}\fi}}
1861 \def\adl@class@start{6}
1862 \def\adl@class@iiiorvii{3}
1863 \fi
1864 }{}
1865 \ifdefinitionfileloaded{tabulary-xetex-bidi}{%
1866 \def\@testpach{\@chclass
1867 \ifnum \@lastchclass=6 \@ne \@chnum \@ne \else
1868 \ifnum \@lastchclass=7 5 \else
1869 \ifnum \@lastchclass=8 \tw@ \else
1870 \ifnum \@lastchclass=9 \thr@@
1871 \else \z@
1872 \ifnum \@lastchclass = 10 \else
1873 \edef\@nextchar{\expandafter\string\@nextchar}%
1874 \@chnum
1875 \if \@nextchar c\z@ \else
1876 \if \@nextchar @z\ \else
1877 \if \@nextchar \if@RTLtab r\else l\fi\@ne \else
1878 \if \@nextchar \if@RTLtab else\ fi\@ne\ \else
1879 \if \@nextchar \if@RTLtab l\else r\fi\@tw@ \else
1880 \if \@nextchar \if@RTLtab else\ @fi\@tw\ \else
1881 \if \@nextchar C7 \else
1882 \if \@nextchar 7 \else
1883 \if \@nextchar L8 \else
1884 \if \@nextchar 8 \else
1885 \if \@nextchar R9 \else
1886 \if \@nextchar 9 \else
1887 \if \@nextchar J10 \else
1888 \if \@nextchar 10 \else
1889 \z@ \@chclass
1890 \if \@nextchar |\@ne \else
1891 \if \@nextchar !6 \else
1892 \if \@nextchar @7 \else
1893 \if \@nextchar <8 \else
1894 \if \@nextchar >9 \else
1895 10
1896 \@chnum
1897 \if \@nextchar m\thr@@\else
1898 \if \@nextchar thr@@\else\
1899 \if \@nextchar p4 \else
1900 \if \@nextchar4 \else
1901 \if \@nextchar b5 \else

```




```

1902 \if \nextchar 5 \else
1903 \z@ \@chclass \z@ \@preamerr \z@ \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi
1904 \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi \fi}%
1905 }{}
1906 \@ifdefinitionfileloaded{float-xetex-bidi}{%
1907 \let\@float@Hx\@xfloat
1908 \def\@xfloat#1[{\@ifnextchar{H}{\@float@HH#1}]{\@ifnextchar{ }{\@float@{#1} }{\@float@Hx{#1}
1909 \def\@float@HH#1[H]{%
1910 \expandafter\let\csname end#1\endcsname\float@endH
1911 \let\@currbox\float@box
1912 \def\@captive{#1}\setbox\@floatcapt=\vbox{}}%
1913 \expandafter\ifx\csname fst@#1\endcsname\relax
1914 \@firststylefalse\else\@firststyletrue\fi
1915 \setbox\@currbox\color@vbox\normalcolor
1916 \vbox\bgroup \hsize\columnwidth \@parboxrestore
1917 \@floatboxreset \@setnobreak
1918 \ignorespaces}
1919 \def\@float@[ ]1# {%
1920 \expandafter\let\csname end#1\endcsname\float@endH
1921 \let\@currbox\float@box
1922 \def\@captive{#1}\setbox\@floatcapt=\vbox{}}%
1923 \expandafter\ifx\csname fst@#1\endcsname\relax
1924 \@firststylefalse\else\@firststyletrue\fi
1925 \setbox\@currbox\color@vbox\normalcolor
1926 \vbox\bgroup \hsize\columnwidth \@parboxrestore
1927 \@floatboxreset \@setnobreak
1928 \ignorespaces}
1929 }{}
1930 \begingroup \catcode `|=0 \catcode `|= 1
1931 \catcode`=2 \catcode `={12 \catcode `}=12
1932 \catcode`\|=12 \gdef|\@x@xepersian@localize@verbatim#1\[[ ] |1#]{ }
1933 \gdef|\@sx@xepersian@localize@verbatim#1\[[* ] |1#]{* }
1934 \endgroup
1935 \def\@{\@verbatim \frenchspacing\@vobeyspaces \@x@xepersian@localize@verbatim}
1936 \def\end{\if\newlist \leavevmode\fi\endtrivlist}
1937 \ExplSyntaxOn
1938 \AtBeginDocument{\@namedef{ *}{\@verbatim \fontspec_print_visible_spaces: \@sx@xepersian@
1939 \ExplSyntaxOff
1940 \expandafter\let\csname end * \endcsname =\end

```

```

1941 \ProvidesFile{natbib-xepersian.def}[2011/08/01 v0.1 adaptations for natbib package]
1942 \renewcommand\NAT@set@cites{%
1943   \ifNAT@numbers
1944     \ifNAT@super \let\@cite\NAT@citesuper
1945     \def\NAT@mbox##1{\unskip\nobreak\textsuperscript{##1}}%
1946     \let\citeyearpar=\citeyear
1947     \let\NAT@space\relax
1948     \def\NAT@super@kern{\kern\p@}%

```



```

1949 \else
1950 \let\NAT@mbox=\mbox
1951 \let\@cite\NAT@citenum
1952 \let\NAT@space\NAT@spacechar
1953 \let\NAT@super@kern\relax
1954 \fi
1955 \let\@citex\NAT@citexnum
1956 \let\@Latincitex\NAT@Latin@citexnum
1957 \let\@biblabel\NAT@biblabelnum
1958 \let\@bibsetup\NAT@bibsetnum
1959 \renewcommand\NAT@idxtxt{\NAT@name\NAT@spacechar\NAT@open\NAT@num\NAT@close}%
1960 \def\natexlab##1{%
1961 \def\NAT@penalty{\penalty\@m}%
1962 \else
1963 \let\@cite\NAT@cite
1964 \let\@citex\NAT@citex
1965 \let\@Latincitex\NAT@Latin@citex
1966 \let\@biblabel\NAT@biblabel
1967 \let\@bibsetup\NAT@bibsetup
1968 \let\NAT@space\NAT@spacechar
1969 \let\NAT@penalty\@empty
1970 \renewcommand\NAT@idxtxt{\NAT@name\NAT@spacechar\NAT@open\NAT@date\NAT@close}%
1971 \def\natexlab##1{##1}%
1972 \fi}
1973 \newcommand\NAT@Latin@citex{}
1974 \def\NAT@Latin@citex%
1975 [#1][#2]#3{%
1976 \NAT@reset@parser
1977 \NAT@sort@cites{#3}%
1978 \NAT@reset@citea
1979 \@cite{\lr{\let\NAT@nm\@empty\let\NAT@year\@empty
1980 \@for\@citeb:=\NAT@cite@list\do
1981 {\@safe@activestru
1982 \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
1983 \@safe@activesfalse
1984 \@ifundefined{b@\@citeb\@extra@b@citeb}{\@citea%
1985 {\reset@font\bfseries ?}\NAT@citeundefined
1986 \PackageWarning{natbib}%
1987 {Citation `'\@citeb' on page \thepage \space undefined}\def\NAT@date{}}}%
1988 {\let\NAT@last@nm=\NAT@nm\let\NAT@last@yr=\NAT@year
1989 \NAT@parse{\@citeb}%
1990 \ifNAT@longnames\@ifundefined{bv@\@citeb\@extra@b@citeb}{%
1991 \let\NAT@name=\NAT@all@names
1992 \global\@namedef{bv@\@citeb\@extra@b@citeb}{}}{}}%
1993 \fi
1994 \ifNAT@full\let\NAT@nm\NAT@all@names\else
1995 \let\NAT@nm\NAT@name\fi
1996 \ifNAT@swa\ifcase\NAT@ctype
1997 \if\relax\NAT@date\relax
1998 \@citea\NAT@hyper@{\NAT@nmfmt{\NAT@nm}\NAT@date}%

```



```

1999 \else
2000 \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
2001 \ifx\NAT@last@yr\NAT@year
2002 \def\NAT@temp{?}%
2003 \ifx\NAT@temp\NAT@exlab\PackageWarningNoLine{natbib}%
2004 {Multiple citation on page \thepage: same authors and
2005 year\MessageBreak without distinguishing extra
2006 letter,\MessageBreak appears as question mark}\fi
2007 \NAT@hyper@{\NAT@exlab}%
2008 \else\unskip\NAT@spacechar
2009 \NAT@hyper@{\NAT@date}%
2010 \fi
2011 \else
2012 \@citea\NAT@hyper@{%
2013 \NAT@nmfmt{\NAT@nm}%
2014 \hyper@natlinkbreak{%
2015 \NAT@aysep\NAT@spacechar}{\@citeb\@extra@b@citeb
2016 }%
2017 \NAT@date
2018 }%
2019 \fi
2020 \fi
2021 \or\@citea\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2022 \or\@citea\NAT@hyper@{\NAT@date}%
2023 \or\@citea\NAT@hyper@{\NAT@alias}%
2024 \fi \NAT@def@citea
2025 \else
2026 \ifcase\NAT@ctype
2027 \if\relax\NAT@date\relax
2028 \@citea\NAT@hyper@{\NAT@nmfmt{\NAT@nm}}%
2029 \else
2030 \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
2031 \ifx\NAT@last@yr\NAT@year
2032 \def\NAT@temp{?}%
2033 \ifx\NAT@temp\NAT@exlab\PackageWarningNoLine{natbib}%
2034 {Multiple citation on page \thepage: same authors and
2035 year\MessageBreak without distinguishing extra
2036 letter,\MessageBreak appears as question mark}\fi
2037 \NAT@hyper@{\NAT@exlab}%
2038 \else
2039 \unskip\NAT@spacechar
2040 \NAT@hyper@{\NAT@date}%
2041 \fi
2042 \else
2043 \@citea\NAT@hyper@{%
2044 \NAT@nmfmt{\NAT@nm}%
2045 \hyper@natlinkbreak{\NAT@spacechar\NAT@@open\if*#1*\else#1\NAT@spacechar\fi}%
2046 {\@citeb\@extra@b@citeb}%
2047 \NAT@date
2048 }%

```



```

2049     \fi
2050     \fi
2051     \or\@citea\NAT@hyper@\NAT@nmfmt{\NAT@nm}}%
2052     \or\@citea\NAT@hyper@\NAT@date}%
2053     \or\@citea\NAT@hyper@\NAT@alias}%
2054     \fi
2055     \if\relax\NAT@date\relax
2056         \NAT@def@citea
2057     \else
2058         \NAT@def@citea@close
2059     \fi
2060 \fi
2061 }}\ifNAT@swa\else\if*#2*\else\NAT@cmt#2\fi
2062 \if\relax\NAT@date\relax\else\NAT@close\fi\fi}}{#1}{#2}}
2063 \newcommand\NAT@Latin@citexnum{
2064 \def\NAT@Latin@citexnum[#1][#2]#3{%
2065     \NAT@reset@parser
2066     \NAT@sort@cites{#3}%
2067     \NAT@reset@citea
2068     \@cite{\lr{\def\NAT@num{-1}\let\NAT@last@yr\relax\let\NAT@nm\@empty
2069     \@for\@citeb:=\NAT@cite@list\do
2070     {\@safe@activestrue
2071     \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}}%
2072     \@safe@activesfalse
2073     \ifundefined{b@\@citeb\@extra@b@citeb}{%
2074         {\reset@font\bfseries?}
2075         \NAT@citeundefined\PackageWarning{natbib}%
2076         {Citation ``\@citeb' on page \thepage \space undefined}}%
2077     {\let\NAT@last@num\NAT@num\let\NAT@last@nm\NAT@nm
2078     \NAT@parse{\@citeb}%
2079     \ifNAT@longnames\ifundefined{bv@\@citeb\@extra@b@citeb}{%
2080         \let\NAT@name=\NAT@all@names
2081         \global\@namedef{bv@\@citeb\@extra@b@citeb}{}}}%
2082     \fi
2083     \ifNAT@full\let\NAT@nm\NAT@all@names\else
2084         \let\NAT@nm\NAT@name\fi
2085     \ifNAT@swa
2086         \@ifnum{\NAT@ctype>\@ne}{%
2087             \@citea
2088             \NAT@hyper@\@ifnum{\NAT@ctype=\tw@}{\NAT@test{\NAT@ctype}}{\NAT@alias}}%
2089         }{%
2090             \@ifnum{\NAT@cmprs>\z@}{%
2091                 \NAT@ifcat@num\NAT@num
2092                 {\let\NAT@nm=\NAT@num}%
2093                 {\def\NAT@nm{-2}}%
2094                 \NAT@ifcat@num\NAT@last@num
2095                 {\@tempcnta=\NAT@last@num\relax}%
2096                 {\@tempcnta\m@ne}%
2097                 \@ifnum{\NAT@nm=\@tempcnta}{%
2098                     \@ifnum{\NAT@merge>\@ne}{\NAT@last@yr@mbbox}%

```



```

2099      }{%
2100      \advance\@tempcnta by\@ne
2101      \@ifnum{\NAT@nm=\@tempcnta}{%
2102      \ifx\NAT@last@yr\relax
2103      \def\NAT@last@yr{\@citea}%
2104      \else
2105      \def\NAT@last@yr{--\NAT@penalty}%
2106      \fi
2107      }{%
2108      \NAT@last@yr@mbox
2109      }%
2110      }%
2111      }{%
2112      \@tempswatrue
2113      \@ifnum{\NAT@merge>\@ne}{\@ifnum{\NAT@last@num=\NAT@num\relax}{\@tempswafalse}{}}{%
2114      \if@tempswa\NAT@citea@mbox\fi
2115      }%
2116      }%
2117      \NAT@def@citea
2118      \else
2119      \ifcase\NAT@ctype
2120      \ifx\NAT@last@nm\NAT@nm \NAT@yrsep\NAT@penalty\NAT@space\else
2121      \@citea \NAT@test{\@ne}\NAT@spacechar\NAT@mbox{\NAT@super@kern\NAT@@open}%
2122      \fi
2123      \if*#1*\else#1\NAT@spacechar\fi
2124      \NAT@mbox{\NAT@hyper@{\citenumfont{\NAT@num}}}%
2125      \NAT@def@citea@box
2126      \or
2127      \NAT@hyper@citea@space{\NAT@test{\NAT@ctype}}%
2128      \or
2129      \NAT@hyper@citea@space{\NAT@test{\NAT@ctype}}%
2130      \or
2131      \NAT@hyper@citea@space\NAT@alias
2132      \fi
2133      \fi
2134      }%
2135      }%
2136      \@ifnum{\NAT@cmprs>\z@}{\NAT@last@yr}{}%
2137      \ifNAT@swa\else
2138      \@ifnum{\NAT@ctype=\z@}{%
2139      \if*#2*\else\NAT@cmt#2\fi
2140      }{}%
2141      \NAT@mbox{\NAT@@close}%
2142      \fi
2143      }{#1}{#2}%
2144      }%
2145      \AtBeginDocument{\NAT@set@cites}
2146      \DeclareRobustCommand\Latincite
2147      {\begingroup\let\NAT@ctype\z@\NAT@partrue\NAT@swatrue
2148      \@ifstar{\NAT@fulltrue\NAT@Latin@cites}{\NAT@fullfalse\NAT@Latin@cites}}

```



```

2149 \newcommand\NAT@Latin@cites{\@ifnextchar [{\NAT@Latin@@citetp}{%
2150     \ifNAT@numbers\else
2151     \NAT@swafalse
2152     \fi
2153     \NAT@Latin@@citetp[]}}
2154 \newcommand\NAT@Latin@@citetp{
2155 \def\NAT@Latin@@citetp[#1]{\@ifnextchar[{\@Latincitex[#1]}{\@Latincitex[] [#1]}}

```

7.43 packages-localise-xepersian.def

```

2156 packages} \-localise-xepersian.def}[2013/04/24 v0.2 localising LaTeX2e Packages]
2157 color} \}{color} @-localise-xepersian.def}}{}
2158 \@ifpackageloaded{multicol}{%
2159 \newenvironment{ }{\begin{multicols}}{\end{multicols}}}%
2160 \newenvironment{ *}{\begin{multicols*}}{\end{multicols*}}}%
2161 }{}
2162 \@ifpackageloaded{verbatim}{%
2163 \begingroup
2164 \vrb@catcodes
2165 \lccode`!=`\\ \lccode`\[=``{\ \lccode`\]=``}
2166 \catcode`\~=\active \lccode`\~=\`^M
2167 \lccode`\C=``C
2168 \lowercase{\endgroup
2169 \def\xepersian@localize@verbatim@start#1{%
2170     \verbatim@startline
2171     \if\noexpand#1\noexpand~%
2172     \let\next\xepersian@localize@verbatim@
2173     \else \def\next{\xepersian@localize@verbatim@#1}\fi
2174     \next}%
2175 \def\xepersian@localize@verbatim@#1~{\xepersian@localize@verbatim@@#1! \@nil}%
2176 \def\xepersian@localize@verbatim@@#1! {%
2177     \verbatim@addtoline{#1}%
2178     \futurelet\next\xepersian@localize@verbatim@@@}%
2179 \def\xepersian@localize@verbatim@@@#1\@nil{%
2180     \ifx\next\@nil
2181     \verbatim@processline
2182     \verbatim@startline
2183     \let\next\xepersian@localize@verbatim@
2184     \else
2185     \def\@tempa##1! \@nil{##1}%
2186     \@temptokena{! }%
2187     \def\next{\expandafter\xepersian@localize@verbatim@test\@tempa#1\@nil~}%
2188     \fi \next}%
2189 \def\xepersian@localize@verbatim@test#1{%
2190     \let\next\xepersian@localize@verbatim@test
2191     \if\noexpand#1\noexpand~%
2192     \expandafter\verbatim@addtoline
2193     \expandafter{\the\@temptokena}%
2194     \verbatim@processline
2195     \verbatim@startline

```



```

2196         \let\next\xepersian@localize@verbatim@
2197     \else \if\noexpand#1
2198         \@temptokena\expandafter{\the\@temptokena#1}%
2199     \else \if\noexpand#1\noexpand[%
2200         \let\@tempc\@empty
2201         \let\next\xepersian@localize@verbatim@testend
2202     \else
2203         \expandafter\verbatim@addtoline
2204         \expandafter{\the\@temptokena}%
2205         \def\next{\xepersian@localize@verbatim@#1}%
2206     \fi\fi\fi
2207     \next}%
2208 \def\xepersian@localize@verbatim@testend#1{%
2209     \if\noexpand#1\noexpand~%
2210         \expandafter\verbatim@addtoline
2211         \expandafter{\the\@temptokena[]}%
2212         \expandafter\verbatim@addtoline
2213         \expandafter{\@tempc}%
2214         \verbatim@processline
2215         \verbatim@startline
2216         \let\next\xepersian@localize@verbatim@
2217     \else\if\noexpand#1\noexpand]%
2218         \let\next\xepersian@localize@verbatim@@testend
2219     \else\if\noexpand#1\noexpand!%
2220         \expandafter\verbatim@addtoline
2221         \expandafter{\the\@temptokena[]}%
2222         \expandafter\verbatim@addtoline
2223         \expandafter{\@tempc}%
2224         \def\next{\xepersian@localize@verbatim@!}%
2225     \else \expandafter\def\expandafter\@tempc\expandafter
2226         {\@tempc#1}\fi\fi\fi
2227     \next}%
2228 \def\xepersian@localize@verbatim@@testend{%
2229     \ifx\@tempc\@currenvir
2230         \verbatim@finish
2231         \edef\next{\noexpand\end{\@currenvir}}%
2232         \noexpand\xepersian@localize@verbatim@rescan{\@currenvir}}}%
2233     \else
2234         \expandafter\verbatim@addtoline
2235         \expandafter{\the\@temptokena[]}%
2236         \expandafter\verbatim@addtoline
2237         \expandafter{\@tempc}}}%
2238     \let\next\xepersian@localize@verbatim@
2239     \fi
2240     \next}%
2241 \def\xepersian@localize@verbatim@rescan#1#2~{\if\noexpand~\noexpand#2~\else
2242     \@warning{Characters dropped after ~\string\end{#1}'}\fi}}%
2243 \def\
2244     {\begingroup\@verbatim \frenchspacing\@vobeyspaces
2245     \xepersian@localize@verbatim@start}
2245 \@namedef{
    *}{\begingroup\@verbatim\xepersian@localize@verbatim@start}

```



```

2246 \def\end      {\endtrivlist\endgroup\@doendpe}
2247 \expandafter\let\csname end      * \endcsname =\end
2248 }{}
2249 \ExplSyntaxOn
2250 \AtBeginDocument{
2251   \xepersian_localize_patch_verbatim:
2252 }
2253 \cs_set:Npn \xepersian_localize_patch_verbatim: {
2254   \@ifpackageloaded{verbatim}{
2255     \cs_set:cpn {*      } }
2256     \group_begin: \@verbatim \fontspec_print_visible_spaces: \xepersian@localize@verbatim@st
2257   }
2258 }{
2259 }
2260 }
2261 \ExplSyntaxOff
2262 \@ifpackageloaded{graphicx}{%
2263 \def\Gin@boolkey#1#2{%
2264 \expandafter\@ifdefinable \csname Gin@#2 \endcsname{%
2265 \expandafter\let\csname Gin@#2 \expandafter\endcsname\csname Gin@#2true\endcsname}%
2266 \expandafter\@ifdefinable \csname Gin@#2 \endcsname{%
2267 \expandafter\let\csname Gin@#2 \expandafter\endcsname\csname Gin@#2false\endcsname}%
2268 \csname Gin@#2\ifx\relax#1\relax true\else#1\fi\endcsname}
2269 \define@key{Grot}{origin}[c]{%
2270   \@tfor\@tempa:=#1\do{%
2271     \if l\@tempa \Grot@x\z@ \else
2272     \if tempa@ \Grot@x\z@ \else
2273     \if r\@tempa \Grot@x\width \else
2274     \if tempa@ \Grot@x\width \else
2275     \if t\@tempa \Grot@y\height \else
2276     \if tempa@ \Grot@y\height \else
2277     \if b\@tempa \Grot@y-\depth \else
2278     \if tempa@ \Grot@y-\depth \else
2279     \if B\@tempa \Grot@y\z@ \else
2280     \if tempa@ \Grot@y\z@\fi\fi\fi\fi\fi\fi\fi\fi\fi\fi}
2281 {draft}{ \Gin } @ \
2282 {origin}{ \Gin } @ \
2283 {origin}{ \Grot } @ \
2284 {clip}{ \Gin } @ \
2285 {keepaspectratio}{ \Gin } @ \
2286 {natwidth}{ \Gin } @ \
2287 {natheight}{ \Gin } @ \
2288 {bb}{ \Gin } @ \
2289 {viewport}{ \Gin } @ \
2290 {trim}{ \Gin } @ \
2291 {angle}{ \Gin } @ \
2292 {width}{ \Gin } @ \
2293 {height}{ \Gin } @ \
2294 {totalheight}{ \Gin } @ \
2295 {scale}{ \Gin } @ \

```




```

2296 {type}{ }{Gin} @ \
2297 {ext}{ }{Gin} @ \
2298 {read}{ }{Gin} @ \
2299 {command}{ }{Gin} @ \
2300 {x}{ }{Grot} @ \
2301 {y}{ }{Grot} @ \
2302 {units}{ }{Grot} @ \
2303 }{}

```

7.44 parsidigits.map

```

2304 LHSName "Digits"
2305 RHSName "ParsiDigits"
2306
2307 pass(Unicode)
2308 U+0030 <> U+06F0 ;
2309 U+0031 <> U+06F1 ;
2310 U+0032 <> U+06F2 ;
2311 U+0033 <> U+06F3 ;
2312 U+0034 <> U+06F4 ;
2313 U+0035 <> U+06F5 ;
2314 U+0036 <> U+06F6 ;
2315 U+0037 <> U+06F7 ;
2316 U+0038 <> U+06F8 ;
2317 U+0039 <> U+06F9 ;
2318
2319
2320 U+002C <> U+060C ; comma > arabic comma
2321 U+003F <> U+061F ; question mark -> arabic qm
2322 U+003B <> U+061B ; semicolon -> arabic semicolon
2323
2324 ; ligatures from Knuth's original CMR fonts
2325 U+002D U+002D <> U+2013 ; -- -> en dash
2326 U+002D U+002D U+002D <> U+2014 ; --- -> em dash
2327
2328 U+0027 <> U+2019 ; ' -> right single quote
2329 U+0027 U+0027 <> U+201D ; '' -> right double quote
2330 U+0022 > U+201D ; " -> right double quote
2331
2332 U+0060 <> U+2018 ; ` -> left single quote
2333 U+0060 U+0060 <> U+201C ; `` -> left double quote
2334
2335 U+0021 U+0060 <> U+00A1 ; !` -> inverted exclam
2336 U+003F U+0060 <> U+00BF ; ?` -> inverted question
2337
2338 ; additions supported in T1 encoding
2339 U+002C U+002C <> U+201E ; ,, -> DOUBLE LOW-9 QUOTATION MARK
2340 U+003C U+003C <> U+00AB ; << -> LEFT POINTING GUILLEMET
2341 U+003E U+003E <> U+00BB ; >> -> RIGHT POINTING GUILLEMET

```



7.45 rapport1-xepersian.def

```
2342 \ProvidesFile{rapport1-xepersian.def}[2010/07/25 v0.1 adaptations for rapport1 class]
2343 \renewcommand*\thepart{\@tartibi\c@part}
2344 \renewcommand*\appendix{\par
2345   \setcounter{chapter}{0}%
2346   \setcounter{section}{0}%
2347   \gdef\@chapapp{\appendixname}%
2348   \gdef\thechapter{\@harfi\c@chapter}}
```

7.46 rapport3-xepersian.def

```
2349 \ProvidesFile{rapport3-xepersian.def}[2010/07/25 v0.2 adaptations for rapport3 class]
2350 \renewcommand*\thepart{\@tartibi\c@part}
2351 \renewcommand*\appendix{\par
2352   \setcounter{chapter}{0}%
2353   \setcounter{section}{0}%
2354   \gdef\@chapapp{\appendixname}%
2355   \gdef\thechapter{\@harfi\c@chapter}}
```

7.47 refrep-xepersian.def

```
2356 \ProvidesFile{refrep-xepersian.def}[2010/07/25 v0.2 adaptations for refrep class]
2357 \renewcommand \thepart {\@tartibi\c@part}
2358 \renewcommand\appendix{\par
2359   \setcounter{chapter}{0}%
2360   \setcounter{section}{0}%
2361   \gdef\@chapapp{\appendixname}%
2362   \gdef\thechapter{\@harfi\c@chapter}
2363 }%end appendix
```

7.48 report-xepersian.def

```
2364 \ProvidesFile{report-xepersian.def}[2010/07/25 v0.2 adaptations for standard report class]
2365 \renewcommand \thepart {\@tartibi\c@part}
2366 \renewcommand\appendix{\par
2367   \setcounter{chapter}{0}%
2368   \setcounter{section}{0}%
2369   \gdef\@chapapp{\appendixname}%
2370   \gdef\thechapter{\@harfi\c@chapter}
2371 }%end appendix
```

7.49 scrartcl-xepersian.def

```
2372 \ProvidesFile{scrartcl-xepersian.def}[2010/07/25 v0.2 adaptations for scrartcl class]
2373 \renewcommand*\thepart{\@tartibi\c@part}
2374 \renewcommand*\appendix{\par%
2375   \setcounter{section}{0}%
2376   \setcounter{subsection}{0}%
2377   \gdef\thesection{\@harfi\c@section}%
2378   \csname appendixmore\endcsname
2379 }
2380 \renewcommand*\@maybeautodot[1]{%
```



```

2381 \ifx #1\@stop\let\@@maybeautodot\relax
2382 \else
2383 \ifx #1\harfi \@autodottrue\fi
2384 \ifx #1\adadi \@autodottrue\fi
2385 \ifx #1\tartibi \@autodottrue\fi
2386 \ifx #1\Alph \@autodottrue\fi
2387 \ifx #1\alph \@autodottrue\fi
2388 \ifx #1\Roman \@autodottrue\fi
2389 \ifx #1\roman \@autodottrue\fi
2390 \ifx #1\@harfi \@autodottrue\fi
2391 \ifx #1\@adadi \@autodottrue\fi
2392 \ifx #1\@tartibi \@autodottrue\fi
2393 \ifx #1\@Alph \@autodottrue\fi
2394 \ifx #1\@alph \@autodottrue\fi
2395 \ifx #1\@Roman \@autodottrue\fi
2396 \ifx #1\@roman \@autodottrue\fi
2397 \ifx #1\romannumeral \@autodottrue\fi
2398 \fi
2399 \@@maybeautodot
2400 }

```

7.50 scrbook-xepersian.def

```

2401 \ProvidesFile{scrbook-xepersian.def}[2010/07/25 v0.2 adaptations for scrbook class]
2402 \renewcommand*\frontmatter{%
2403 \if@twoside\cleardoubleoddpagel\else\clearpage\fi
2404 \@mainmatterfalse\pagenumbering{harfi}%
2405 }
2406 \renewcommand*\thepart{\@tartibi\c@part}
2407 \renewcommand*\appendix{\par%
2408 \setcounter{chapter}{0}%
2409 \setcounter{section}{0}%
2410 \gdef\@chapapp{\appendixname}%
2411 \gdef\thechapter{\@harfi\c@chapter}%
2412 \csname appendixmore\endcsname
2413 }
2414 \renewcommand*\@@maybeautodot}[1]{%
2415 \ifx #1\@stop\let\@@maybeautodot\relax
2416 \else
2417 \ifx #1\harfi \@autodottrue\fi
2418 \ifx #1\adadi \@autodottrue\fi
2419 \ifx #1\tartibi \@autodottrue\fi
2420 \ifx #1\Alph \@autodottrue\fi
2421 \ifx #1\alph \@autodottrue\fi
2422 \ifx #1\Roman \@autodottrue\fi
2423 \ifx #1\roman \@autodottrue\fi
2424 \ifx #1\@harfi \@autodottrue\fi
2425 \ifx #1\@adadi \@autodottrue\fi
2426 \ifx #1\@tartibi \@autodottrue\fi
2427 \ifx #1\@Alph \@autodottrue\fi

```



```

2428 \ifx #1\@alph \@autodottrue\fi
2429 \ifx #1\@Roman \@autodottrue\fi
2430 \ifx #1\@roman \@autodottrue\fi
2431 \ifx #1\romannumeral \@autodottrue\fi
2432 \fi
2433 \@maybeautodot
2434 }

```

7.51 scrreprt-xepersian.def

```

2435 \ProvidesFile{scrreprt-xepersian.def}[2010/07/25 v0.2 adaptations for scrreprt class]
2436 \renewcommand*{\thepart}{\@tartibi\c@part}
2437 \renewcommand*{\appendix}{\par%
2438 \setcounter{chapter}{0}%
2439 \setcounter{section}{0}%
2440 \gdef\@chapapp{\appendixname}%
2441 \gdef\thechapter{\@harfi\c@chapter}%
2442 \csname appendixmore\endcsname
2443 }
2444 \renewcommand*{\@maybeautodot}[1]{%
2445 \ifx #1\@stop\let\@maybeautodot\relax
2446 \else
2447 \ifx #1\harfi \@autodottrue\fi
2448 \ifx #1\adadi \@autodottrue\fi
2449 \ifx #1\tartibi \@autodottrue\fi
2450 \ifx #1\Alph \@autodottrue\fi
2451 \ifx #1\alph \@autodottrue\fi
2452 \ifx #1\Roman \@autodottrue\fi
2453 \ifx #1\roman \@autodottrue\fi
2454 \ifx #1\@harfi \@autodottrue\fi
2455 \ifx #1\@adadi \@autodottrue\fi
2456 \ifx #1\@tartibi \@autodottrue\fi
2457 \ifx #1\@Alph \@autodottrue\fi
2458 \ifx #1\@alph \@autodottrue\fi
2459 \ifx #1\@Roman \@autodottrue\fi
2460 \ifx #1\@roman \@autodottrue\fi
2461 \ifx #1\romannumeral \@autodottrue\fi
2462 \fi
2463 \@maybeautodot
2464 }

```

7.52 soul-xepersian.def

```

2465 \ProvidesFile{soul-xepersian.def}[2015/10/16 v0.1 adaptations for soul package]
2466 \let\SOUL@tt\relax
2467 \newfontface{\SOUL@tt}{Times New Roman}

```

7.53 tkz-linknodes-xepersian.def

```

2468 \ProvidesFile{tkz-linknodes-xepersian.def}[2012/06/13 v0.1 adaptations for tkz-linknodes packa
2469 \renewcommand*{\@SetTab}{%
2470 \let\@alph\@latinalph%

```



```

2471 \ifnum \value{C@NumTab}>25\relax%
2472 \setcounter{C@NumTab}{1}%
2473 \else%
2474 \stepcounter{C@NumTab}%
2475 \fi%
2476 \setcounter{C@NumGroup}{0}%
2477 \newcommand*{\PrefixCurrentTab}{\alph{C@NumTab}}
2478 \setboolean{B@FirstLink}{true}
2479 \setboolean{B@NewGroup}{false}
2480 \setcounter{C@NumGroup}{0}
2481 \setcounter{C@CurrentGroup}{0}
2482 \setcounter{NumC@Node}{0}
2483 \setcounter{NumC@Stop}{0}
2484 \setcounter{C@NextNode}{0}
2485 \setcounter{C@CurrentStop}{0}
2486 \setcounter{C@CurrentNode}{0}
2487 }%

```

7.54 tocloft-xepersian.def

```

2488 \ProvidesFile{tocloft-xepersian.def}[2010/07/25 v0.1 bilingual captions for tocloft package]
2489 \renewcommand*{\cftchapname}{\if@RTL else\ chapter\fi}
2490 \renewcommand*{\cftsecname}{\if@RTL else\ section\fi}
2491 \renewcommand*{\cftsubsecname}{\if@RTL else\ subsection\fi}
2492 \renewcommand*{\cftsubsubsecname}{\if@RTL else\ subsubsection\fi}
2493 \renewcommand*{\cftparaname}{\if@RTL else\ paragraph\fi}
2494 \renewcommand*{\cftsubparaname}{\if@RTL else\ subparagraph\fi}
2495 \renewcommand*{\cftfigname}{\if@RTL else\ figure\fi}
2496 \renewcommand*{\cftsubfigname}{\if@RTL else\ subfigure\fi}
2497 \renewcommand*{\cfttabname}{\if@RTL else\ table\fi}
2498 \renewcommand*{\cftsubtabname}{\if@RTL else\ subtable\fi}

```

7.55 xepersian.sty

```

2499 \NeedsTeXFormat{LaTeX2e}
2500 \def\xepersianversion{v18.9}
2501 \def\xepersiandate{2017/08/09}
2502 \ProvidesPackage{xepersian}[\xepersiandate\space \xepersianversion\space
2503 Persian typesetting in XeLaTeX]
2504 \RequirePackage{fontspec}
2505 \RequirePackage{xepersian-persiancal}
2506 \RequirePackage{xepersian-mathsdigitspec}
2507 \RequirePackage{bidi}
2508 \edef\xepersian@info{*****~J%
2509 * ~J%
2510 * xepersian package (Persian for LaTeX, using XeTeX engine)~J%
2511 * ~J%
2512 * Description: The package supports Persian~J%
2513 * typesetting, using fonts provided in the~J%
2514 * distribution.~J%
2515 * ~J%

```



```

2516 * Copyright (c) 2008--2017 Vafa Khalighi^^J%
2517 * ^^J%
2518 * \xepersianversion, \xepersiandate^^J%
2519 * ^^J%
2520 * License: LaTeX Project Public License, version^^J%
2521 * 1.3c or higher (your choice)^^J%
2522 * ^^J%
2523 * Location on CTAN: /macros/xetex/latex/xepersian^^J%
2524 * ^^J%
2525 * Issue tracker: https://github.com/tex-xet/xepersian/issues^^J%
2526 * ^^J%
2527 * Support: persian-tex@tug.org^^J%
2528 * ^^J%
2529 *****}
2530 \typeout{\@xepersian@info}
2531 \edef\xepersian@everyjob{\the\everyjob}
2532 \everyjob{\xepersian@everyjob\typeout{\@xepersian@info}}
2533 \edef\@bidi@strip@v\xepersianversion{\expandafter\@gobble\xepersianversion}
2534 \newcommand*{\IfxepersianPackageVersionLater}[1]{%
2535   \ifdim\@bidi@strip@v\xepersianversion pt > #1 pt %
2536     \expandafter\@firstoftwo
2537   \else
2538     \expandafter\@secondoftwo
2539   \fi}
2540 \newcommand*{\IfxepersianPackageVersionBefore}[1]{%
2541   \ifdim\@bidi@strip@v\xepersianversion pt < #1 pt %
2542     \expandafter\@firstoftwo
2543   \else
2544     \expandafter\@secondoftwo
2545   \fi}
2546 \newcommand*{\IfxepersianPackageVersion}[1]{%
2547   \ifdim\@bidi@strip@v\xepersianversion pt = #1 pt %
2548     \expandafter\@firstoftwo
2549   \else
2550     \expandafter\@secondoftwo
2551   \fi}
2552 \def\prq{«}
2553 \def\plq{»}
2554 \def\xepersian@cmds@temp#1{%
2555   \begingroup\expandafter\expandafter\expandafter\endgroup
2556   \expandafter\ifx\csname xepersian@#1\endcsname\relax
2557     \begingroup
2558       \escapechar=-1 %
2559       \edef\x{\expandafter\meaning\csname#1\endcsname}%
2560       \def\y{#1}%
2561       \def\z##1->{%}%
2562       \edef\y{\expandafter\z\meaning\y}%
2563     \expandafter\endgroup
2564     \ifx\x\y
2565       \expandafter\def\csname xepersian@#1\endcsname

```



```

2566     \expandafter{%
2567     \csname#1\endcsname
2568     }%
2569     \fi
2570     \fi
2571 }%
2572 \xepersian@cmds@temp{shellescape}
2573 \newif\ifwritexviii
2574 \ifnum\xepersian@shellescape=1\relax
2575     \writexviiitrue
2576 \else
2577 \writexviiiifalse
2578 \fi
2579 \newfontscript{Parsi}{arab}
2580 \newfontlanguage{Parsi}{FAR}
2581 \ExplSyntaxOn
2582
2583 \DeclareDocumentCommand \settextfont { 0{} m 0{} }
2584 {
2585     \fontspec_set_family:Nnn \g__xepersian_persianfont_family {Script=Parsi,Language=Parsi,Mapping=
2586     \tl_set_eq:NN \rmdefault \g__xepersian_persianfont_family
2587     \use:x { \exp_not:n { \DeclareRobustCommand \persianfont }
2588     {
2589         \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2590         \exp_not:N \fontfamily { \g__xepersian_persianfont_family }
2591         \exp_not:N \selectfont
2592     }
2593     }
2594     \str_if_eq_x:nnT {\familydefault} {\rmdefault}
2595     { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2596     \normalfont
2597     \ignorespaces
2598 }
2599
2600 \DeclareDocumentCommand \setlatintextfont { 0{} m 0{} }
2601 {
2602     \fontspec_set_family:Nnn \g__xepersian_latinfont_family {Mapping=tex-text,#1,#3} {#2}
2603     \use:x { \exp_not:n { \DeclareRobustCommand \latinfont }
2604     {
2605         \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2606         \exp_not:N \fontfamily { \g__xepersian_latinfont_family }
2607         \exp_not:N \selectfont
2608     }
2609     }
2610     \str_if_eq_x:nnT {\familydefault} {\rmdefault}
2611     { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2612     \normalfont
2613     \ignorespaces
2614 }
2615

```



```

2616 \tl_set_eq:NN \setlatinsansfont \setsansfont
2617 \tl_set_eq:NN \setlatinmonofont \setmonofont
2618
2619 \DeclareDocumentCommand \defpersianfont { m O{} m O{} }
2620 {
2621   \fontspec_set_family:cnn { g__xepersian_ \cs_to_str:N #1 _family } {Script=Parsi,Language=Pa
2622   \use:x
2623   {
2624     \exp_not:N \DeclareRobustCommand \exp_not:N #1
2625     {
2626       \exp_not:N \fontfamily { \use:c {g__xepersian_ \cs_to_str:N #1 _family} }
2627       \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2628       \exp_not:N \selectfont
2629     }
2630   }
2631 }
2632
2633 \DeclareDocumentCommand \deflatinfont { m O{} m O{} }
2634 {
2635   \fontspec_set_family:cnn { g__xepersian_ \cs_to_str:N #1 _family } {Mapping=tex-text,#2,#4}
2636   \use:x
2637   {
2638     \exp_not:N \DeclareRobustCommand \exp_not:N #1
2639     {
2640       \exp_not:N \fontfamily { \use:c {g__xepersian_ \cs_to_str:N #1 _family} }
2641       \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2642       \exp_not:N \selectfont
2643     }
2644   }
2645 }
2646
2647 \newcommand\persiansfdefault{}
2648 \newcommand\persianttdefault{}
2649 \newcommand\iranicsfdefault{}
2650 \newcommand\navarsfdefault{}
2651 \newcommand\pookdefault{}
2652 \newcommand\sayehdefault{}
2653 \DeclareRobustCommand\persiansffamily
2654   {\not@math@alphabet\persiansffamily\mathpersiansf
2655   \fontfamily\persiansfdefault\selectfont}
2656 \DeclareRobustCommand\persianttfamily
2657   {\not@math@alphabet\persianttfamily\mathpersiantt
2658   \fontfamily\persianttdefault\selectfont}
2659 \DeclareRobustCommand\iranicsfamily
2660   {\not@math@alphabet\iranicsfamily\mathiranics
2661   \fontfamily\iranicsdefault\selectfont}
2662 \DeclareRobustCommand\navarsfamily
2663   {\not@math@alphabet\navarsfamily\mathnavar
2664   \fontfamily\navarsdefault\selectfont}
2665 \DeclareRobustCommand\pookfamily

```




```

2666         {\not@math@alphabet\pookfamily\mathpook
2667         \fontfamily\pookdefault\selectfont}
2668 \DeclareRobustCommand\sayehfamily
2669         {\not@math@alphabet\sayehfamily\mathsayeh
2670         \fontfamily\sayehdefault\selectfont}
2671 \DeclareTextFontCommand{\textpersiansf}{\persiansffamily}
2672 \DeclareTextFontCommand{\textpersiantt}{\persianttfamily}
2673 \DeclareTextFontCommand{\textiranica}{\iranicafamily}
2674 \DeclareTextFontCommand{\textnavar}{\navarfamily}
2675 \DeclareTextFontCommand{\textpook}{\pookfamily}
2676 \DeclareTextFontCommand{\textsayeh}{\sayehfamily}
2677
2678 \DeclareDocumentCommand \setpersiansansfont { 0{} m 0{} }
2679 {
2680   \fontspec_set_family:Nnn \g__xepersian_persiansffamily_family {Script=Parsi,Language=Parsi,M
2681   \tl_set_eq:NN \persiansfdefault \g__xepersian_persiansffamily_family
2682   \use:x { \exp_not:n { \DeclareRobustCommand \persiansffamily }
2683   {
2684     \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2685     \exp_not:N \fontfamily { \g__xepersian_persiansffamily_family }
2686     \exp_not:N \selectfont
2687   }
2688   }
2689   \str_if_eq:x:nnT {\familydefault} {\persiansfdefault}
2690   { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2691   \normalfont
2692   \ignorespaces
2693 }
2694
2695 \DeclareDocumentCommand \setpersianmonofont { 0{} m 0{} }
2696 {
2697   \fontspec_set_family:Nnn \g__xepersian_persianttfamily_family {Script=Parsi,Language=Parsi,M
2698   \tl_set_eq:NN \persianttdefault \g__xepersian_persianttfamily_family
2699   \use:x { \exp_not:n { \DeclareRobustCommand \persianttfamily }
2700   {
2701     \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2702     \exp_not:N \fontfamily { \g__xepersian_persianttfamily_family }
2703     \exp_not:N \selectfont
2704   }
2705   }
2706   \str_if_eq:x:nnT {\familydefault} {\persianttdefault}
2707   { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2708   \normalfont
2709   \ignorespaces
2710 }
2711
2712 \DeclareDocumentCommand \setnavarfont { 0{} m 0{} }
2713 {
2714   \fontspec_set_family:Nnn \g__xepersian_navarfamil_family {Script=Parsi,Language=Parsi,Mappi
2715   \tl_set_eq:NN \navardefault \g__xepersian_navarfamil_family

```



```

2716 \use:x { \exp_not:n { \DeclareRobustCommand \navarfamily }
2717 {
2718 \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2719 \exp_not:N \fontfamily { \g__xepersian_navarfamilly_family }
2720 \exp_not:N \selectfont
2721 }
2722 }
2723 \str_if_eq_x:nnT {\familydefault} {\navardefault}
2724 { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2725 \normalfont
2726 \ignorespaces
2727 }
2728
2729 \DeclareDocumentCommand \setpookfont { 0{} m 0{} }
2730 {
2731 \fontspec_set_family:Nnn \g__xepersian_pookfamily_family {Script=Parsi,Language=Parsi,Mappi
2732 \tl_set_eq:NN \pookdefault \g__xepersian_pookfamily_family
2733 \use:x { \exp_not:n { \DeclareRobustCommand \pookfamily }
2734 {
2735 \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2736 \exp_not:N \fontfamily { \g__xepersian_pookfamily_family }
2737 \exp_not:N \selectfont
2738 }
2739 }
2740 \str_if_eq_x:nnT {\familydefault} {\pookdefault}
2741 { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2742 \normalfont
2743 \ignorespaces
2744 }
2745
2746 \DeclareDocumentCommand \setsayehfont { 0{} m 0{} }
2747 {
2748 \fontspec_set_family:Nnn \g__xepersian_sayehfamily_family {Script=Parsi,Language=Parsi,Mappi
2749 \tl_set_eq:NN \sayehdefault \g__xepersian_sayehfamily_family
2750 \use:x { \exp_not:n { \DeclareRobustCommand \sayehfamily }
2751 {
2752 \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2753 \exp_not:N \fontfamily { \g__xepersian_sayehfamily_family }
2754 \exp_not:N \selectfont
2755 }
2756 }
2757 \str_if_eq_x:nnT {\familydefault} {\sayehdefault}
2758 { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2759 \normalfont
2760 \ignorespaces
2761 }
2762
2763 \DeclareDocumentCommand \setiranifont { 0{} m 0{} }
2764 {
2765 \fontspec_set_family:Nnn \g__xepersian_iranicfamily_family {Script=Parsi,Language=Parsi,Mapp

```



```

2766 \tl_set_eq:NN \iranicondefault \g__xepersian_iranicfamily_family
2767 \use:x { \exp_not:n { \DeclareRobustCommand \iraniconfamily }
2768 {
2769 \exp_not:N \fontencoding { \l__fontspec_nfss_enc_tl }
2770 \exp_not:N \fontfamily { \g__xepersian_iranicfamily_family }
2771 \exp_not:N \selectfont
2772 }
2773 }
2774 \str_if_eq:x:nnT {\familydefault} {\iranicondefault}
2775 { \tl_set_eq:NN \encodingdefault \l__fontspec_nfss_enc_tl }
2776 \normalfont
2777 \ignorespaces
2778 }
2779
2780
2781 \ExplSyntaxOff
2782 \def\resetlatinfont{%
2783 \@nonlatinfalse%
2784 \let\normalfont\latinfont%
2785 \let\reset@font\normalfont%
2786 \latinfont%
2787 \fontsize\fontsize\fontsize\fontbaseline\fontbaseline%
2788 \selectfont}
2789 \def\setpersianfont{%
2790 \@nonlatintrue%
2791 \let\normalfont\persianfont%
2792 \let\reset@font\normalfont%
2793 \persianfont%
2794 \fontsize\fontsize\fontsize\fontbaseline\fontbaseline%
2795 \selectfont}
2796 \bidi@newrobustcmd*{\lr}[1]{\LRE{\resetlatinfont#1}}
2797 \bidi@newrobustcmd*{\rl}[1]{\RLE{\setpersianfont#1}}
2798 \def\latin{\LTR\LatinAlphs\@RTL@footnotefalse\resetlatinfont}
2799 \def\endlatin{\endLTR}
2800 \def\persian{\RTL\PersianAlphs\@RTL@footnotetrue\setpersianfont}
2801 \def\endpersian{\endRTL}
2802 \newenvironment{latinitems}{\begin{LTRitems}\LatinAlphs\@RTL@footnotefalse\resetlatinfont}{\end{LATINITEMS}}
2803 \newenvironment{persiitems}{\begin{RTLitems}\PersianAlphs\@RTL@footnotetrue\setpersianfont}{\end{PERSIITEMS}}
2804 \let\originaltoday=\today
2805 \def\latintoday{\lr{\originaltoday}}
2806 \def\today{\rl{\persiantoday}}
2807 \def \@LTRmarginparreset {%
2808 \reset@font
2809 \resetlatinfont
2810 \normalsize
2811 \@minipagetrue
2812 \everypar{\@minipagefalse\everypar{}\beginL}%
2813 }
2814 \DeclareRobustCommand\Latincite{%
2815 \ifnextchar [{\@tempswatrue\@Latincitex}{\@tempswafalse\@Latincitex[]}]

```



```

2816 \def\@Latincitex[#1]#2{\leavevmode
2817   \let\@citea\@empty
2818   \@cite{\lr{\@for\@citeb:=#2\do
2819     {\@citea\def\@citea{\penalty\@m\ }%
2820     \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}}%
2821     \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi
2822     \@ifundefined{b@\@citeb}{\hbox{\reset@font\bfseries ?}%
2823     \G@refundefinedtrue
2824     \@latex@warning
2825       {Citation `'\@citeb' on page \thepage \space undefined}}%
2826     {\@cite@ofmt{\csname b@\@citeb\endcsname}}}\}}{#1}}
2827
2828 \renewcommand*{\@bidi@font@@@outputpage}{\if@RTLmain\setpersianfont\else\resetlatinfont\fi}
2829
2830 \newif\if@xepersian@@computeautoilg
2831 \newcount\xepersian@tcl
2832 \newdimen\xepersian@ilg
2833 \newdimen\xepersian@strutilg
2834 \chardef\f@ur=4
2835 \newcommand*\@xepersian@computeautoilg{\% compute the interline glue
2836   \xepersian@tcl=1536\xepersian@ilg\z@\xepersian@strutilg\z@
2837   \loop
2838     \iffontchar\font\xepersian@tcl
2839     \ifdim\XeTeXglyphbounds\tw@ \the\XeTeXcharglyph\xepersian@tcl>\z@
2840     \ifdim\XeTeXglyphbounds\tw@ \the\XeTeXcharglyph\xepersian@tcl>\xepersian@ilg
2841     \xepersian@ilg=\XeTeXglyphbounds\tw@ \the\XeTeXcharglyph\xepersian@tcl
2842     \fi
2843     \else
2844     \ifdim\XeTeXglyphbounds\tw@ \the\XeTeXcharglyph\xepersian@tcl<\z@
2845     \ifdim-\XeTeXglyphbounds\tw@ \the\XeTeXcharglyph\xepersian@tcl>\xepersian@ilg
2846     \xepersian@ilg=-\XeTeXglyphbounds\tw@ \the\XeTeXcharglyph\xepersian@tcl
2847     \fi
2848     \fi
2849     \fi
2850     \ifdim\XeTeXglyphbounds\f@ur \the\XeTeXcharglyph\xepersian@tcl>\z@
2851     \ifdim\XeTeXglyphbounds\f@ur \the\XeTeXcharglyph\xepersian@tcl>\xepersian@strutilg
2852     \xepersian@strutilg=\XeTeXglyphbounds\f@ur \the\XeTeXcharglyph\xepersian@tcl
2853     \fi
2854     \else
2855     \ifdim\XeTeXglyphbounds\f@ur \the\XeTeXcharglyph\xepersian@tcl<\z@
2856     \ifdim-\XeTeXglyphbounds\f@ur \the\XeTeXcharglyph\xepersian@tcl>\xepersian@strutilg
2857     \xepersian@strutilg=-\XeTeXglyphbounds\f@ur \the\XeTeXcharglyph\xepersian@tcl
2858     \fi
2859     \fi
2860     \fi
2861     \fi
2862     \advance\xepersian@tcl\@ne
2863     \ifnum\xepersian@tcl<1792\repeat
2864     \advance\xepersian@strutilg\xepersian@ilg
2865 \% \ifdim\xepersian@strutilg>\baselineskip

```



```

2866 % \PackageInfo{xepersian}{character with height+depth greater than current baselineskip found
2867 % \PackageInfo{xepersian}{baselineskip changed to that height+depth!}
2868 % \linespread{\strip@pt\dimexpr 1pt * \xepersian@strutilg / \baselineskip\relax}
2869 % \selectfont
2870 % \fi
2871 }
2872
2873 \newcommand\twocolumnstableofcontents{%
2874 \if@bidi@csundef{multi@column@out}{%
2875 \PackageError{xepersian}{Oops! you should load multicols package before xepersian package for b
2876 \begin{multicols}{2}[\section*{\contentsname}]]%
2877 \small
2878 \@starttoc{toc}%
2879 \end{multicols}}}}
2880 \bidi@newrobustcmd*{\XePersian}{\leavevmode$\smash{\hbox{X\lower.5ex
2881 \hbox{\kern-.125em\bidi@reflect@box{E}}Persian}}}$}
2882 \def\figurename{\if@RTL else\ Figure\fi}
2883 \def\tablename{\if@RTL else\ Table\fi}
2884 \def\contentsname{\if@RTL else\ Contents\fi}
2885 \def\listfigurename{\if@RTL else\ List of Figures\fi}
2886 \def\listtablename{\if@RTL else\ List of Tables\fi}
2887 \def\appendixname{\if@RTL else\ Appendix\fi}
2888 \def\indexname{\if@RTL else\ Index\fi}
2889 \def\refname{\if@RTL else\ References\fi}
2890 \def\abstractname{\if@RTL else\ Abstract\fi}
2891 \def\partname{\if@RTL else\ Part\fi}
2892 \def\datename{\if@RTL else\ Date:\fi}
2893 \def\@and{\if@RTL else\ and\fi}
2894 \def\bibname{\if@RTL else\ Bibliography\fi}
2895 \def\chaptername{\if@RTL else\ Chapter\fi}
2896 \def\ccname{\if@RTL else\ cc\fi}
2897 \def\enclname{\if@RTL else\ encl\fi}
2898 \def\pagename{\if@RTL else\ Page\fi}
2899 \def\headtoname{\if@RTL else\ To\fi}
2900 \def\proofname{\if@RTL else\ Proof\fi}
2901 \def\@Abjad#1{%
2902 \ifcase#1\or or\ or\ or\ %
2903 \or or\ or\ or\ or\ %
2904 \or or\ or\ or\ or\ %
2905 \or or\ or\ or\ %
2906 \or or\ or\ or\ or\ %
2907 \or or\ or\ or\ or\ %
2908 \else\@ctrerr\fi}
2909 \def\Abjad#1{\expandafter\@Abjad\csname c@#1\endcsname}
2910 \let\Abjadnumeral\@Abjad
2911 \def\@harfi#1{\ifcase#1\or or\ or\ or\ or\ or\
2912 or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\ or\
2913 or\ or\ or\ or\ or\ or\ or\ or\ or\ {else\@ctrerr\fi}
2914 \def\harfi#1{\expandafter\@harfi\csname c@#1\endcsname}

```



```

2915 \let\harfinumeral\@harfi
2916 \newcommand{\adadi}[1]{%
2917 \expandafter\@adadi\csname c@#1\endcsname%
2918 }
2919 \newcommand{\@adadi}[1]{%
2920 \xepersian@numberstring{#1}\xepersian@yekanii{ }{}%
2921 }
2922 \let\adadinumeral\@adadi%
2923 \def\xepersian@numberoutofrange#1#2{%
2924 \PackageError{xepersian}{The number `#1' is too large %
2925 to be formatted using xepersian}{The largest possible %
2926 number is 999,999,999.}%
2927 }
2928 \def\xepersian@numberstring#1#2#3#4{%
2929 \ifnum\number#1<\@ne%
2930 #3%
2931 \else\ifnum\number#1<1000000000 %
2932 \expandafter\xepersian@adadi\expandafter{\number#1}#2%
2933 \else%
2934 \xepersian@numberoutofrange{#1}{#4}%
2935 \fi\fi%
2936 }
2937 \def\xepersian@adadi#1#2{%
2938 \expandafter\xepersian@@adadi%
2939 \ifcase%
2940 \ifnum#1<10 1%
2941 \else\ifnum#1<100 2%
2942 \else\ifnum#1<\@m 3%
2943 \else\ifnum#1<\@M 4%
2944 \else\ifnum#1<100000 5%
2945 \else\ifnum#1<1000000 6%
2946 \else\ifnum#1<10000000 7%
2947 \else\ifnum#1<100000000 8%
2948 \else9%
2949 \fi\fi\fi\fi\fi\fi\fi\fi %
2950 \or00000000#1% case 1: Add 8 leading zeros
2951 \or0000000#1% case 2: Add 7 leading zeros
2952 \or000000#1% case 3: Add 6 leading zeros
2953 \or00000#1% case 4: Add 5 leading zeros
2954 \or0000#1% case 5: Add 4 leading zeros
2955 \or000#1% case 6: Add 3 leading zeros
2956 \or00#1% case 7: Add 2 leading zeros
2957 \or0#1% case 8: Add 1 leading zero
2958 \or#1% case 9: Add no leading zeros
2959 \or%
2960 \@nil#2%
2961 \fi%
2962 }
2963 \def\xepersian@@adadi#1#2#3#4#5#6#7\or#8\@nil#9{%
2964 \ifnum#1#2#3>\z@

```



```

2965 \xepersian@milyoongan#1#2#3%
2966 \ifnum#7>\z@\ifnum#4#5#6>\z@ \else \fi\else\ifnum#4#5#6>\z@ \fi\fi%
2967 \fi%
2968 \ifnum#4#5#6>\z@%
2969 \xepersian@sadgan#4#5#6{#1#2#3}{#4#5}\xepersian@yekani%
2970 \ifnum#4#5#6>\@ne\fi%
2971 %
2972 \ifnum#7>\z@ \fi%
2973 \fi%
2974 \xepersian@sadgan#7{#4#5#6}1#9%
2975 }
2976 \def\xepersian@milyoongan#1#2#3{%
2977 \ifnum#1#2#3=\@ne%
2978 \xepersian@sadgan#1#2#301\xepersian@yekanii%
2979 %
2980 %
2981 \else%
2982 \xepersian@sadgan#1#2#301\xepersian@yekanii%
2983 %
2984 %
2985 \fi%
2986 }
2987 \def\xepersian@sadgan#1#2#3#4#5#6{%
2988 \ifnum#1>\z@%
2989 \ifnum#4#1>\@ne\xepersian@yekaniv#1\fi%
2990 %
2991 \ifnum#2#3>\z@ \fi%
2992 \fi%
2993 \ifnum#2#3<20%
2994 \ifnum#5#2#3>\@ne#6{#2#3}\fi%
2995 \else%
2996 \xepersian@dahgan#2%
2997 \ifnum#3>\z@ \xepersian@yekani#3\fi%
2998 #60%
2999 \fi%
3000 }
3001 \def\xepersian@yekani#1{%
3002 \ifcase#1\@empty\or or\ or\ or\ or\ or\ %
3003 \or or\ or\ or\ or\ or\ or\ %
3004 \or or\ or\ or\ %
3005 \or or\ %fi\
3006 }
3007 \def\xepersian@yekanii#1{%
3008 \ifcase#1\@empty\or %else\xepersian@yekani{#1}\fi\
3009 }
3010 \def\xepersian@yekanii#1{%
3011 \ifcase#1\@empty\or %else\xepersian@yekani{#1}\fi\
3012 }
3013 \def\xepersian@yekaniv#1{%
3014 \ifcase#1\@empty\or or\ or\ or\ or\ %

```



```

3015 \or or\ or\ %fi\
3016 }
3017 \def\xepersian@dahgan#1{%
3018 \ifcase#1\or\or or\ or\ %
3019 \or or\ or\ or\ %
3020 \or %fi\
3021 }
3022 \newcommand{\tartibi}[1]{%
3023 \expandafter\@tartibi\csname c@#1\endcsname%
3024 }
3025 \newcommand{\@tartibi}[1]{%
3026 \xepersian@numberstring@tartibi{#1}\xepersian@tartibi{ }{ }%
3027 }
3028 \let\tartibinumeral\@tartibi%
3029 \def\xepersian@numberstring@tartibi#1#2#3#4{%
3030 \ifnum\number#1<\@ne%
3031 #3%
3032 \else\ifnum\number#1<1000000000 %
3033 \expandafter\xepersian@adadi@tartibi\expandafter{\number#1}#2%
3034 \else%
3035 \xepersian@numberoutofrange{#1}{#4}%
3036 \fi\fi%
3037 }
3038 \def\xepersian@adadi@tartibi#1#2{%
3039 \expandafter\xepersian@@adadi@tartibi%
3040 \ifcase%
3041 \ifnum#1<10 1%
3042 \else\ifnum#1<100 2%
3043 \else\ifnum#1<\@m 3%
3044 \else\ifnum#1<\@M 4%
3045 \else\ifnum#1<100000 5%
3046 \else\ifnum#1<1000000 6%
3047 \else\ifnum#1<10000000 7%
3048 \else\ifnum#1<100000000 8%
3049 \else9%
3050 \fi\fi\fi\fi\fi\fi\fi\fi %
3051 \or00000000#1% case 1: Add 8 leading zeros
3052 \or0000000#1% case 2: Add 7 leading zeros
3053 \or000000#1% case 3: Add 6 leading zeros
3054 \or00000#1% case 4: Add 5 leading zeros
3055 \or0000#1% case 5: Add 4 leading zeros
3056 \or000#1% case 6: Add 3 leading zeros
3057 \or00#1% case 7: Add 2 leading zeros
3058 \or0#1% case 8: Add 1 leading zero
3059 \or#1% case 9: Add no leading zeros
3060 \or%
3061 \@nil#2%
3062 \fi%
3063 }
3064 \def\xepersian@@adadi@tartibi#1#2#3#4#5#6#7\or#8\@nil#9{%

```




```

3065 \ifnum#1#2#3>\z@
3066 \xepersian@milyoongan@tartibi#1#2#3%
3067 \ifnum#7>\z@\ifnum#4#5#6>\z@\ \else\ \fi\else\ifnum#4#5#6>\z@\ \fi\fi%
3068 \fi%
3069 \ifnum#4#5#6>\z@%
3070 \xepersian@sadgan#4#5#6{#1#2#3}{#4#5}\xepersian@yekani%
3071 \ifnum#4#5#6>\@ne \fi%
3072 %
3073 \ifnum#7>\z@\ \fi%
3074 \fi%
3075 \xepersian@sadgan@tartibi#7{#4#5#6}1#9%
3076 }
3077 \def\xepersian@milyoongan@tartibi#1#2#3{%
3078 \ifnum#1#2#3=\@ne%
3079 \xepersian@sadgan@tartibi#1#2#301\xepersian@yekanii%
3080 %
3081 %
3082 \else%
3083 \xepersian@sadgan#1#2#301\xepersian@yekanii%
3084 %
3085 %
3086 \fi%
3087 }
3088 \def\xepersian@sadgan@tartibi#1#2#3#4#5#6{%
3089 \ifnum#1>\z@%
3090 \ifnum#4#1>\@ne\xepersian@yekaniv#1\fi%
3091 %
3092 \ifnum#2#3>\z@\ \fi%
3093 \fi%
3094 \ifnum#2#3<20%
3095 \ifnum#5#2#3>\@ne\ifnum#1#2#3#4#5=10001 %else#6{#2#3}\fi\fi\
3096 \else%
3097 \ifnum#2#3=30%
3098 \xepersian@dahgan@tartibi#2%
3099 \else%
3100 \xepersian@dahgan#2%
3101 \fi%
3102 \ifnum#3>\z@\ \xepersian@yekanv#3\fi%
3103 #60%
3104 \fi%
3105 }
3106 \def\xepersian@dahgan@tartibi#1{%
3107 \ifcase#1\or\or or\ or\ %
3108 \or or\ or\ or\ %
3109 \or %fi\
3110 }
3111 \def\xepersian@tartibi#1{%
3112 \ifcase#1\or or\ or\ or\ %
3113 \or or\ or\ or\ or\ %
3114 \or or\ or\ or\ %

```



```

3115 \or or\ or\ %
3116 \or or\ or\ %fi\
3117 }
3118 \def\xepersian@yekanv#1{%
3119 \ifcase#1\@empty\or or\ or\ or\ or\ or\ %
3120 \or or\ or\ or\ or\ or\ or\ %
3121 \or or\ or\ or\ %
3122 \or or\ %fi\
3123 }
3124 \providecommand*\xpg@warning}[1]{%
3125 \PackageWarning{XePersian}%
3126 {#1}}
3127 \if@bidi@csundef{@abjad}{%
3128 \def\@abjad#1{%
3129 \ifnum#1>1999 \xpg@warning{Illegal value (#1) for abjad numeral} {#1}
3130 \else
3131 \ifnum#1<z@\space\xpg@warning{Illegal value (#1) for abjad numeral}%
3132 \else
3133 \ifnum#1<10\expandafter\abj@num@i\number#1%
3134 \else
3135 \ifnum#1<100\expandafter\abj@num@ii\number#1%
3136 \else
3137 \ifnum#1<M\expandafter\abj@num@iii\number#1%
3138 \else
3139 \ifnum#1<@M\expandafter\abj@num@iv\number#1%since #1<2000, we must have 1000
3140 \fi
3141 \fi
3142 \fi
3143 \fi
3144 \fi
3145 \fi
3146 }
3147 \def\abjad#1{\expandafter\@abjad\csname c@#1\endcsname}
3148 \let\abjadnumeral\@abjad
3149 \def\abjad@zero{}
3150 \def\abj@num@i#1{%
3151 \ifcase#1\or or\ or\ or\ %
3152 \or or\ or\ or\ or\ fi\
3153 \ifnum#1=z@\abjad@zero\fi}
3154 \def\abj@num@ii#1{%
3155 \ifcase#1\or or\ or\ or\ or\ %
3156 \or or\ or\ or\ fi\
3157 \ifnum#1=z@\fi\abj@num@i}
3158 \def\abj@num@iii#1{%
3159 \ifcase#1\or or\ or\ or\ or\ %
3160 \or or\ or\ or\ fi\
3161 \ifnum#1=z@\fi\abj@num@ii}
3162 \def\abj@num@iv#1{%
3163 \ifcase#1\or fi\
3164 \ifnum#1=z@\fi\abj@num@iii}

```



```

3165 }{}
3166 \let\@latinalph\@alph%
3167 \let\@latinAlph\@Alph%
3168 \def\LatinAlphs{%
3169     \let\@alph\@latinalph%
3170     \let\@Alph\@latinAlph%
3171 }
3172 \renewcommand*{\bidi@thebibliography@font@hook}{%
3173 \if@LTRbibitems
3174     \resetlatinfont
3175 \fi}
3176 \bidi@AfterEndPreamble{%
3177 \if@bidi@csundef{persianfont}{%
3178 \PackageError{xepersian}{You have not specified any font\MessageBreak
3179 for the main Persian text}{Use \settextfont' to load a font.}%
3180 }{}
3181 \@ifdefinitionfileloaded{loadingorder-xetex-bidi}{\input{loadingorder-xepersian.def}}{}
3182 \@ifdefinitionfileloaded{footnote-xetex-bidi}{\input{footnote-xepersian.def}}{}
3183 \@ifpackageloaded{appendix}{\input{appendix-xepersian.def}}{}
3184 \@ifpackageloaded{listings}{\input{listings-xepersian.def}}{}
3185 \@ifpackageloaded{algorithmic}{\input{algorithmic-xepersian.def}}{}
3186 \@ifpackageloaded{algorithm}{\input{algorithm-xepersian.def}}{}
3187 \@ifpackageloaded{backref}{\input{backref-xepersian.def}}{}
3188 \@ifpackageloaded{flowfram}{\input{flowfram-xepersian.def}}{}
3189 \@ifpackageloaded{bidiuftesidenote}{\input{bidiuftesidenote-xepersian.def}}{}
3190 \@ifpackageloaded{breqn}{\input{breqn-xepersian.def}}{}
3191 \@ifpackageloaded{enumerate}{\input{enumerate-xepersian.def}}{}
3192 \@ifpackageloaded{framed}{\input{framed-xepersian.def}}{}
3193 \@ifpackageloaded{glossaries}{\input{glossaries-xepersian.def}}{}
3194 \@ifpackageloaded{hyperref}{\input{hyperref-xepersian.def}}{}
3195 \@ifpackageloaded{minitoc}{\input{minitoc-xepersian.def}}{}
3196 \@ifpackageloaded{natbib}{\input{natbib-xepersian.def}}{}
3197 \@ifpackageloaded{soul}{\input{soul-xepersian.def}}{}
3198 \@ifpackageloaded{tkz-linknodes}{\input{tkz-linknodes-xepersian.def}}{}
3199 \@ifpackageloaded{tocloft}{\@ifclassloaded{memoir}{}{\input{tocloft-xepersian.def}}{}
3200 \@ifclassloaded{article}{\input{article-xepersian.def}}{}
3201 \@ifclassloaded{extarticle}{\input{extarticle-xepersian.def}}{}
3202 \@ifclassloaded{artikel1}{\input{artikel1-xepersian.def}}{}
3203 \@ifclassloaded{artikel2}{\input{artikel2-xepersian.def}}{}
3204 \@ifclassloaded{artikel3}{\input{artikel3-xepersian.def}}{}
3205 \@ifclassloaded{amsart}{\input{amsart-xepersian.def}}{}
3206 \@ifclassloaded{bidimoderncv}{\input{bidimoderncv-xepersian.def}}{}
3207 \@ifclassloaded{report}{\input{report-xepersian.def}}{}
3208 \@ifclassloaded{extreport}{\input{extreport-xepersian.def}}{}
3209 \@ifclassloaded{rapport1}{\input{rapport1-xepersian.def}}{}
3210 \@ifclassloaded{rapport3}{\input{rapport3-xepersian.def}}{}
3211 \@ifclassloaded{scrartcl}{\input{scrartcl-xepersian.def}}{}
3212 \@ifclassloaded{scrbook}{\input{scrbook-xepersian.def}}{}
3213 \@ifclassloaded{scrreprt}{\input{scrreprt-xepersian.def}}{}
3214 \@ifclassloaded{amsbook}{\input{amsbook-xepersian.def}}{}

```



```

3215 \@ifclassloaded{boek3}{\input{boek3-xepersian.def}}{}
3216 \@ifclassloaded{boek}{\input{boek-xepersian.def}}{}
3217 \@ifclassloaded{bookest}{\input{bookest-xepersian.def}}{}
3218 \@ifclassloaded{extbook}{\input{extbook-xepersian.def}}{}
3219 \@ifclassloaded{book}{\input{book-xepersian.def}}{}
3220 \@ifclassloaded{refrep}{\input{refrep-xepersian.def}}{}
3221 \@ifclassloaded{memoir}{\input{memoir-xepersian.def}}{}
3222 \@ifclassloaded{imsproc}{\input{imsproc-xepersian.def}}{}
3223 \define@choicekey{xepersian.sty}{mathdigits}[\xepersian@tempa\xepersian@tempb]{automatic,default}
3224 \ifcase\xepersian@tempb\relax
3225 \AutoMathsDigits
3226 \or
3227 \DefaultMathsDigits
3228 \or
3229 \PersianMathsDigits
3230 \fi}
3231 \define@choicekey{xepersian.sty}{RTLdocument}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3232 \ifcase\xepersian@tempb\relax
3233 \RTLtrue
3234 \or
3235 \RTLfalse
3236 \fi}
3237
3238 \define@choicekey{xepersian.sty}{documentdirection}[\xepersian@tempa\xepersian@tempb]{righttoleft}
3239 \ifcase\xepersian@tempb\relax
3240 \RTLtrue
3241 \or
3242 \RTLfalse
3243 \fi}
3244
3245
3246 \define@choicekey{xepersian.sty}{tabledirection}[\xepersian@tempa\xepersian@tempb]{righttoleft}
3247 \ifcase\xepersian@tempb\relax
3248 \RTLtabtrue
3249 \or
3250 \RTLtabfalse
3251 \fi}
3252
3253 \define@choicekey{xepersian.sty}{script}[\xepersian@tempa\xepersian@tempb]{latin,nonlatin}[latin]
3254 \ifcase\xepersian@tempb\relax
3255 \@nonlatinfalse
3256 \or
3257 \@nonlatintrue
3258 \fi}
3259
3260 \define@choicekey{xepersian.sty}{rldocument}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3261 \RTLtrue
3262 \or
3263 \RTLfalse
3264 \fi}

```



```

3265 \fi}
3266 \define@choicekey{xepersian.sty}{footnoterule}[\xepersian@tempa\xepersian@tempb]{automatic,lef
3267 \ifcase\xepersian@tempb\relax
3268 \autofootnoterule
3269 \or
3270 \leftfootnoterule
3271 \or
3272 \rightfootnoterule
3273 \or
3274 \SplitFootnoteRule
3275 \or
3276 \textwidthfootnoterule
3277 \fi}
3278 \define@choicekey{xepersian.sty}{footnotedirection}[\xepersian@tempa\xepersian@tempb]{righttol
3279 \ifcase\xepersian@tempb\relax
3280 \@RTL@footnotetrue
3281 \or
3282 \@RTL@footnotefalse
3283 \fi}
3284 \define@choicekey{xepersian.sty}{debugfootnotedirection}[\xepersian@tempa\xepersian@tempb]{on,
3285 \ifcase\xepersian@tempb\relax
3286 \footdir@debugtrue
3287 \or
3288 \footdir@debugfalse
3289 \fi}
3290 \define@choicekey{xepersian.sty}{Kashida}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3291 \ifcase\xepersian@tempb\relax
3292 \input{kashida-xepersian.def}
3293 \fi}
3294 \define@choicekey{xepersian.sty}{localise}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3295 \ifcase\xepersian@tempb\relax
3296 \input{localise-xepersian.def}
3297 \fi}
3298 \define@choicekey{xepersian.sty}{extrafootnotefeatures}[\xepersian@tempa\xepersian@tempb]{on,o
3299 \ifcase\xepersian@tempb\relax
3300 \@extrafootnotefeaturestrue
3301 \or
3302 \@extrafootnotefeaturesfalse
3303 \fi}
3304 \define@choicekey{xepersian.sty}{quickindex}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3305 \ifcase\xepersian@tempb\relax
3306 \PackageWarning{xepersian}{Obsolete option}%
3307 \ifwritexviii%
3308 \ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with th
3309 \renewcommand\printindex{\newpage%
3310 \immediate\closeout\@indexfile
3311 \immediate\write18{xindy -L persian-variant2 -C utf8 -M texindy -M page-ranges \jobname.
3312 \@input@{\jobname.ind}}}%
3313 \else
3314 \PackageError{xepersian}{"shell escape" (or "write18") is not enabled. You need to run "

```



```

3315     \fi
3316 \fi}
3317 \define@choicekey{xepersian.sty}{quickindex-variant1}[\xepersian@tempa\xepersian@tempb]{on,off}
3318 \ifcase\xepersian@tempb\relax
3319     \ifwritexviii%
3320     \ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with th
3321     \renewcommand\printindex{\newpage%
3322     \immediate\closeout\@indexfile
3323     \immediate\write18{xindy -L persian-variant1 -C utf8 -M texindy -M page-ranges \jobnam
3324     \@input@{\jobname.ind}}}%
3325     \else
3326     \PackageError{xepersian}{"shell escape" (or "write18") is not enabled. You need to run
3327     \fi
3328 \fi}
3329 \define@choicekey{xepersian.sty}{quickindex-variant2}[\xepersian@tempa\xepersian@tempb]{on,off}
3330 \ifcase\xepersian@tempb\relax
3331     \ifwritexviii%
3332     \ifclassloaded{memoir}{\PackageError{xepersian}{This feature does not yet work with th
3333     \renewcommand\printindex{\newpage%
3334     \immediate\closeout\@indexfile
3335     \immediate\write18{xindy -L persian-variant2 -C utf8 -M texindy -M page-ranges \jobname
3336     \@input@{\jobname.ind}}}%
3337     \else
3338     \PackageError{xepersian}{"shell escape" (or "write18") is not enabled. You need to run
3339     \fi
3340 \fi}
3341 \define@choicekey{xepersian.sty}{abjadvariant}[\xepersian@tempa\xepersian@tempb]{one,two}{%
3342 \ifcase\xepersian@tempb\relax
3343     \def\PersianAlphs{%
3344     \let\@alph\@abjad%
3345     \let\@Alph\@abjad%
3346     }
3347 \or
3348     \def\PersianAlphs{%
3349     \let\@alph\@Abjad%
3350     \let\@Alph\@Abjad%
3351     }
3352 \fi}
3353 \DeclareOptionX{defaultlatinfontfeatures}{%
3354 \defaultfontfeatures
3355 [\latinfont]
3356 {#1}
3357 }
3358
3359
3360 \define@choicekey{xepersian.sty}{computeautoilg}[\xepersian@tempa\xepersian@tempb]{on,off}[on]
3361 \ifcase\xepersian@tempb\relax
3362     \xepersian@@computeautoilgtrue
3363 \or
3364     \xepersian@@computeautoilgfalse

```



```

3365 \fi}
3366
3367 \define@choicekey{xepersian.sty}{DetectColumn}[\xepersian@tempa\xepersian@tempb]{on,off}[on]{%
3368 \ifcase\xepersian@tempb\relax
3369 \def\bidi@firstcolumn@status@write{%
3370 \protected@write\@auxout{}%
3371 {\string\bidi@column@status
3372 {1}}}%
3373 \def\bidi@lastcolumn@status@write{%
3374 \protected@write\@auxout{}%
3375 {\string\bidi@column@status{2}}}%
3376 \or
3377 \let\bidi@firstcolumn@status@write\relax
3378 \let\bidi@lastcolumn@status@write\relax
3379 \fi}
3380
3381
3382 \ExecuteOptionsX{%
3383 documentdirection=righttoleft,
3384 tabledirection=righttoleft,
3385 script=nonlatin,
3386 footnotedirection=righttoleft,
3387 footnoterule=automatic,
3388 abjadvariant=two,
3389 DetectColumn=off
3390 }
3391
3392 \ProcessOptionsX
3393
3394 \if@extrafootnotefeatures
3395 \input{extrafootnotefeatures-xetex-bidi.def}
3396 \input{extrafootnotefeatures-xepersian.def}
3397 \fi
3398
3399 \ifxepersian@computeautoilg
3400 \bidi@patchcmd{\set@fontsize}{%
3401 \baselineskip\f@baselineskip\relax
3402 }{%
3403 \baselineskip\f@baselineskip\relax
3404 \xepersian@computeautoilg
3405 \ifdim\xepersian@strutilg>\baselineskip
3406 \PackageInfo{xepersian}{character with height+depth greater than current baselineskip found}
3407 \PackageInfo{xepersian}{baselineskip changed to that height+depth!}%
3408 \baselineskip\xepersian@strutilg
3409 \ifdim\footnotesep=.7\baselineskip
3410 \else
3411 \footnotesep.7\baselineskip
3412 \fi
3413 \fi
3414 }{}{}

```



```

3415 \fi
3416
3417 \setlatintextfont[ExternalLocation,BoldFont={lmroman10-bold},BoldItalicFont={lmroman10-boldita
3418 \PersianAlphs

```

7.56 xepersian-magazine.cls

```

3419 \NeedsTeXFormat{LaTeX2e}
3420 \ProvidesClass{xepersian-magazine}[2010/07/25 v0.2 Typesetting Persian magazines in XeLaTeX]
3421 \RequirePackage{ifthen}
3422 \newlength{\xepersian@imgsize}
3423 \newlength{\xepersian@coltitsize}
3424 \newlength{\xepersian@pageneed}
3425 \newlength{\xepersian@pageleft}
3426 \newlength{\xepersian@indexwidth}
3427 \newcommand{\xepersian@ncolumns}{0}
3428 \newlength{\columnlines}
3429 \setlength{\columnlines}{0 pt} % no lines by default
3430 \newboolean{xepersian@hyphenatedtitles}
3431 \setboolean{xepersian@hyphenatedtitles}{true}
3432 \newboolean{xepersian@ninepoints}
3433 \setboolean{xepersian@ninepoints}{false}
3434 \newboolean{xepersian@showgrid}
3435 \setboolean{xepersian@showgrid}{false}
3436 \newboolean{xepersian@a3paper}
3437 \setboolean{xepersian@a3paper}{false}
3438 \newboolean{xepersian@insidefrontpage}
3439 \setboolean{xepersian@insidefrontpage}{false}
3440 \newboolean{xepersian@insideweather}
3441 \setboolean{xepersian@insideweather}{false}
3442 \newboolean{xepersian@insideindex}
3443 \setboolean{xepersian@insideindex}{false}
3444 \newcount\xepersian@gridrows
3445 \newcount\xepersian@gridcolumns
3446 \xepersian@gridrows=40
3447 \xepersian@gridcolumns=50
3448 \newcount\minraggedcols
3449 \minraggedcols=5
3450 \DeclareOption{10pt}{\PassOptionsToClass{10pt}{article}}
3451 \DeclareOption{11pt}{\PassOptionsToClass{11pt}{article}}
3452 \DeclareOption{12pt}{\PassOptionsToClass{12pt}{article}}
3453 \DeclareOption{twocolumn}%
3454 {\ClassWarning{xepersian-magazine}{Option 'twocolumn' not available for xepersian-magazine.}}
3455 \DeclareOption{notitlepage}%
3456 {\ClassWarning{xepersian-magazine}{Option 'notitlepage' not available for xepersian-magazine.}}
3457 \DeclareOption{twoside}%
3458 {\ClassWarning{xepersian-magazine}{Option 'twoside' not available for xepersian-magazine.}}
3459 \DeclareOption{9pt}{\setboolean{xepersian@ninepoints}{true}}
3460 \DeclareOption{hyphenatedtitles}{\setboolean{xepersian@hyphenatedtitles}{false}}
3461 \DeclareOption{columnlines}{\setlength{\columnlines}{0.1 pt}}

```




```

3462 \DeclareOption{showgrid}{\setboolean{xepersian@showgrid}{true}}
3463 \DeclareOption{a3paper}{\setboolean{xepersian@a3paper}{true}}
3464 \ProcessOptions\relax
3465 \LoadClass[10pt, onecolumn, titlepage, a4paper]{article}
3466 \RequirePackage{ifxetex}
3467 \RequirePackage{multido}
3468 \RequirePackage{datetime}
3469 \RequirePackage{multicol}
3470 \RequirePackage{fancyhdr}
3471 \RequirePackage{fancybox}
3472 \ifthenelse{\boolean{xepersian@a3paper}}{%
3473 \RequirePackage[a3paper,headsep=0.5cm,vmargin={2cm,2cm},hmargin={1.5cm,1.5cm}]{geometry}
3474 }{
3475 \RequirePackage[headsep=0.5cm,vmargin={2cm,2cm},hmargin={1.5cm,1.5cm}]{geometry}
3476 }
3477 \RequirePackage[absolute]{textpos} % absolute positioning
3478 \RequirePackage{hyphenat} % when hyphenate
3479 \RequirePackage{lastpage} % to know the last page number
3480 \RequirePackage{setspace} % set space between lines
3481 \RequirePackage{ragged2e}
3482 \newcommand{\raggedFormat}{\RaggedLeft}
3483 \AtEndOfClass{\xepersianInit}
3484 \ifthenelse{\boolean{xepersian@showgrid}}{%
3485 \AtBeginDocument{
3486 \grid[show]{\xepersian@gridrows}{\xepersian@gridcolumns}}
3487 \advance\minraggedcols by -1
3488 }{%
3489 \AtBeginDocument{
3490 \grid[]{\xepersian@gridrows}{\xepersian@gridcolumns}}
3491 \advance\minraggedcols by -1
3492 }
3493 \ifthenelse{\boolean{xepersian@ninepoints}}{
3494 \renewcommand{\normalsize}{%
3495 \setfontsize{\normalsize}{9pt}{10pt}%
3496 \setlength{\abovedisplayskip}{5pt plus 1pt minus .5pt}%
3497 \setlength{\belowdisplayskip}{\abovedisplayskip}%
3498 \setlength{\abovedisplayshortskip}{3pt plus 1pt minus 2pt}%
3499 \setlength{\belowdisplayshortskip}{\abovedisplayshortskip}}
3500
3501 \renewcommand{\tiny}{\setfontsize{\tiny}{5pt}{6pt}}
3502
3503 \renewcommand{\scriptsize}{\setfontsize{\scriptsize}{7pt}{8pt}}
3504
3505 \renewcommand{\small}{%
3506 \setfontsize{\small}{8pt}{9pt}%
3507 \setlength{\abovedisplayskip}{4pt plus 1pt minus 1pt}%
3508 \setlength{\belowdisplayskip}{\abovedisplayskip}%
3509 \setlength{\abovedisplayshortskip}{2pt plus 1pt}%
3510 \setlength{\belowdisplayshortskip}{\abovedisplayshortskip}}
3511

```



```

3512 \renewcommand{\footnotesize}{%
3513   \@setfontsize{\footnotesize}{8pt}{9pt}%
3514   \setlength{\abovedisplayskip}{4pt plus 1pt minus .5pt}%
3515   \setlength{\belowdisplayskip}{\abovedisplayskip}%
3516   \setlength{\abovedisplayskip}{2pt plus 1pt}%
3517   \setlength{\belowdisplayskip}{\abovedisplayskip}}
3518
3519 \renewcommand{\large}{\@setfontsize{\large}{11pt}{13pt}}
3520 \renewcommand{\Large}{\@setfontsize{\Large}{14pt}{18pt}}
3521 \renewcommand{\LARGE}{\@setfontsize{\LARGE}{18pt}{20pt}}
3522 \renewcommand{\huge}{\@setfontsize{\huge}{20pt}{25pt}}
3523 \renewcommand{\Huge}{\@setfontsize{\Huge}{25pt}{30pt}}
3524 }{}
3525 \def\customwwwTxt#1{\gdef\@customwwwTxt{\lr{#1}}}
3526 \newcommand{\xepersian@wwwFormat}{\sffamily}
3527 \newcommand{\xepersian@www}{%
3528 \raisebox{-3pt}{\xepersian@wwwFormat\@customwwwTxt}}
3529 }
3530 \newcommand{\xepersian@edition}{ {
3531 \newcommand{\editionFormat}{\large\bfseries\texttt}
3532 \newcommand{\xepersian@editionLogo}{%
3533 \raisebox{-3pt}{%
3534 {\editionFormat\xepersian@edition}%
3535 }%
3536 }
3537 \newcommand{\indexFormat}{\large\bfseries}
3538 \newcommand{\xepersian@indexFrameTitle}[1]
3539 {\begin{flushright}{\indexFormat #1}\end{flushright}}
3540
3541 \newcommand{\indexEntryFormat}{\normalsize}
3542 \newcommand{\xepersian@indexEntry}[1]{\begin{minipage}{13\TPHorizModule}%
3543 {\indexEntryFormat\noindent\ignorespaces{#1}}%
3544 \end{minipage}}
3545 \newcommand{\indexEntrySeparator}{\rule{\xepersian@indexwidth}{.1pt}}
3546 \newcommand{\indexEntryPageTxt}{ {
3547 \newcommand{\indexEntryPageFormat}{\footnotesize}
3548 \newcommand{\xepersian@indexEntryPage}[1]{%
3549 {\indexEntryPageFormat{\indexEntryPageTxt{~#1}}%
3550 }
3551 \newcommand{\headDateTimeFormat}{%
3552 \newcommand{\xepersian@headDateTime}{%
3553 \headDateTimeFormat\date\hspace{5pt}\$ \parallel \$\hspace{5pt}%
3554 \currenttime %
3555 }
3556 \newcommand{\weatherFormat}{\bfseries}
3557 \newcommand{\xepersian@weather}[1]{%
3558 \noindent{\weatherFormat #1}%
3559 }
3560 \newcommand{\weatherTempFormat}{\small}
3561 \newcommand{\weatherUnits}{\textdegree{C}}

```



```

3562 \newcommand{\xepersian@section}[0]{ {
3563 \newcommand{\xepersian@headleft}{%
3564 {\small\bfseries \@custommagazinename} \date
3565 }
3566 \newcommand{\xepersian@headcenter}{%
3567 \xepersian@section{}
3568 }
3569 \newcommand{\xepersian@headright}{%
3570 \small\xepersian@edition%
3571 \hspace*{5pt}\beginL\thepage\ / \pageref{LastPage}\endL
3572 }
3573
3574 \newcommand{\heading}[3]{%
3575 \renewcommand{\xepersian@headleft}{\beginR#1\endR}%
3576 \renewcommand{\xepersian@headcenter}{\beginR#2\endR}%
3577 \renewcommand{\xepersian@headright}{\beginR#3\endR}%
3578 }
3579 \newcommand{\xepersian@footright}{%
3580 {\footnotesize\lr{\copyright\ \@customwwwTxt{}}-- - \lr{\XePersian}}%
3581 }
3582 \newcommand{\xepersian@footcenter}{%
3583 }
3584 \newcommand{\xepersian@footleft}{%
3585 }
3586
3587 \newcommand{\foot}[3]{%
3588 \renewcommand{\xepersian@footleft}{\beginR#1\endR}%
3589 \renewcommand{\xepersian@footcenter}{\beginR#2\endR}%
3590 \renewcommand{\xepersian@footright}{\beginR#3\endR}%
3591 }
3592 \newcommand{\firstTitleFormat}{\Huge\bfseries\flushright}
3593 \newcommand{\xepersian@firstTitle}[1]{%
3594 {%
3595 \begin{spacing}{2.0}{%
3596 \noindent\ignorespaces
3597 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3598 {\nohyphens{\firstTitleFormat #1}}%
3599 {\firstTitleFormat #1}}%
3600 }%
3601 \end{spacing}%
3602 }%
3603 }
3604 \newcommand{\firstTextFormat}{%
3605 \newcommand{\xepersian@firstText}[1]{%
3606 {\noindent\ignorespaces\firstTextFormat #1}%
3607 }
3608 \newcommand{\secondTitleFormat}{\LARGE\bfseries}
3609 \newcommand{\xepersian@secondTitle}[1]{%
3610 \begin{spacing}{1.5}{%
3611 \noindent\ignorespaces\flushright

```



```

3612 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3613 {\nohyphens{\secondTitleFormat #1}}%
3614 {\secondTitleFormat #1}}%
3615 }\end{spacing}%
3616 }
3617 \newcommand{\secondSubtitleFormat}{\large}
3618 \newcommand{\xepersian@secondSubtitle}[1]{%
3619 {\noindent\ignorespaces{\secondSubtitleFormat #1}}%
3620 }
3621 \newcommand{\secondTextFormat}{%
3622 \newcommand{\xepersian@secondText}[1]{%
3623 \begin{multicols}{2}
3624 {\noindent\ignorespaces\secondTextFormat #1}
3625 \end{multicols}
3626 }
3627 \newcommand{\thirdTitleFormat}{\Large\bfseries}
3628 \newcommand{\xepersian@thirdTitle}[1]{%
3629 \begin{spacing}{1.5}{%
3630 \noindent\ignorespaces\flushright
3631 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3632 {\nohyphens{\thirdTitleFormat #1}}%
3633 {\thirdTitleFormat #1}}%
3634 }\end{spacing}%
3635 }
3636 \newcommand{\thirdSubtitleFormat}{\large}
3637 \newcommand{\xepersian@thirdSubtitle}[1]{%
3638 {\noindent\ignorespaces\thirdSubtitleFormat #1}}
3639 \newcommand{\thirdTextFormat}{%
3640 \newcommand{\xepersian@thirdText}[1]{\thirdTextFormat #1}}
3641 \newcommand{\pictureCaptionFormat}{\small\bfseries}
3642 \newcommand{\xepersian@pictureCaption}[1]{%
3643 {\noindent\pictureCaptionFormat #1}}%
3644 }
3645 \newcommand{\pagesFormat}{\bfseries\footnotesize}
3646 \newcommand{\xepersian@pages}[1]{%
3647 {\noindent{\pagesFormat\MakeUppercase{#1}}}
3648 \newcommand{\innerTitleFormat}{\Huge}
3649 \newcommand{\xepersian@innerTitle}[1]{%
3650 \begin{flushright}{%
3651 \noindent
3652 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3653 {\nohyphens{\innerTitleFormat #1}}%
3654 {\innerTitleFormat #1}}%
3655 }%
3656 \\%
3657 \end{flushright}}%
3658 }
3659 \newcommand{\innerSubtitleFormat}{\large}
3660 \newcommand{\xepersian@innerSubtitle}[1]{\innerSubtitleFormat #1}}
3661 \newcommand{\timestampText}{%

```



```

3662 \newcommand{\timestampSeparator}{|}
3663 \newcommand{\timestampFormat}{\small}
3664 \newcommand{\timestamp}[1]{%
3665 {\timestampFormat%
3666 #1~\timestampTxt}{}%
3667 }~\timestampSeparator}{}%
3668 }
3669 \newcommand{\innerAuthorFormat}{\footnotesize}
3670 \newcommand{\innerPlaceFormat}{\footnotesize\bfseries}
3671 \newcommand{\innerTextFinalMark}{\rule{0.65em}{0.65em}}
3672 \newcommand{\editorialTitleFormat}{\LARGE\textit}
3673 \newcommand{\xepersian@editorialTitle}[1]{\editorialTitleFormat{#1}}
3674 \newcommand{\editorialAuthorFormat}{\textsc}
3675 \newcommand{\shortarticleTitleFormat}{\LARGE\bfseries}
3676 \newcommand{\xepersian@shortarticleTitle}[1]{\shortarticleTitleFormat #1}}
3677 \newcommand{\shortarticleSubtitleFormat}{\Large}
3678 \newcommand{\xepersian@shortarticleSubtitle}[1]{\shortarticleSubtitleFormat #1}}
3679 \newcommand{\shortarticleItemTitleFormat}{\large\bfseries}
3680 \newcommand{\xepersian@shortarticleItemTitle}[1]{\shortarticleItemTitleFormat #1}}
3681 \renewcommand{\maketitle}{\begin{titlepage}%
3682 \let\footnotesize\small
3683 \let\footnoterule\relax
3684 \let \footnote \thanks
3685 \null\vfil
3686 \vskip 60\p@
3687 \begin{center}%
3688 {\LARGE \@title \par}%
3689 \vskip 1em%
3690 {\LARGE «\xepersian@edition» \par}%
3691 \vskip 3em%
3692 {\large
3693 \lineskip .75em%
3694 \begin{tabular}[t]{c}%
3695 \@author
3696 \end{tabular}\par}%
3697 \vskip 1.5em%
3698 {\large \@date \par}%
3699 \end{center}\par
3700 \@thanks
3701 \vfil\null
3702 \end{titlepage}%
3703 \setcounter{footnote}{0}%
3704 \global\let\thanks\relax
3705 \global\let\maketitle\relax
3706 \global\let\@thanks\@empty
3707 \global\let\@author\@empty
3708 \global\let\@date\@empty
3709 \global\let\@title\@empty
3710 \global\let\title\relax
3711 \global\let\author\relax

```



```

3712 \global\let\date\relax
3713 \global\let\and\relax
3714 }
3715 \newcommand{\xepersian@say}[1]{\typeout{#1}}
3716 \newsavebox{\xepersian@fmbox}
3717 \newenvironment{xepersian@fmpage}[1]
3718 {\begin{lrbox}{\xepersian@fmbox}\begin{minipage}{#1}}
3719 {\end{minipage}\end{lrbox}\fbox{\usebox{\xepersian@fmbox}}}
3720 \newcommand{\image}[2]{
3721 \vspace{5pt}
3722 \setlength{\fboxsep}{1pt}
3723 \addtolength{\xepersian@imgsize}{\columnwidth}
3724 \addtolength{\xepersian@imgsize}{-1\columnsep}
3725 \ifxetex
3726 \setlength{\xepersian@pageneed}{1.5\xepersian@imgsize}
3727 \addtolength{\xepersian@pageneed}{50pt}
3728 \ClassWarning{xepersian-magazine}{%
3729 Image #1 needs: \the\xepersian@pageneed \space %
3730 and there is left: \the\page@free\space%
3731 }
3732 \ifdim \xepersian@pageneed < \page@free
3733
3734 {\centering\fbox{%
3735 \includegraphics[width = \xepersian@imgsize,
3736 height = \xepersian@imgsize,
3737 keepaspectratio ]{#1}}}
3738 \xepersian@pictureCaption{#2}
3739
3740 \vspace{5pt}
3741 \else
3742 \ClassWarning{Image #1 needs more space!%
3743 It was not inserted!}
3744 \fi
3745 \fi
3746 }
3747 \textblockorigin{1cm}{1cm}
3748 \newdimen\xepersian@dx
3749 \newdimen\xepersian@dy
3750 \newcount\xepersian@cx
3751 \newcount\xepersian@cy
3752 \newcommand{\grid}[3][ ]{
3753 \xepersian@dx=\textwidth%
3754 \xepersian@dy=\textheight%
3755 \xepersian@cx=#3% %columns
3756 \xepersian@cy=#2% %rows
3757
3758 \count1=#3%
3759 \advance\count1 by 1
3760
3761 \count2=#2%

```



```

3762 \advance\count2 by 1
3763
3764 \divide\xepersian@dx by #3
3765 \divide\xepersian@dy by #2
3766
3767 \setlength{\TPHorizModule}{\xepersian@dx}
3768 \setlength{\TPVertModule}{\xepersian@dy}
3769
3770 \ifthenelse{\equal{#1}{show}}{
3771 \multido{\xepersian@nrow=0+1}{\count2}{
3772 \begin{textblock}{\xepersian@cx}(0,\xepersian@nrow)
3773 \rule[0pt]{\textwidth}{.1pt}
3774 \end{textblock}
3775 }
3776
3777 \multido{\xepersian@ncol=0+1}{\count1}{
3778 \begin{textblock}{\xepersian@cy}(\xepersian@ncol,0)
3779 \rule[0pt]{.1pt}{\textheight}
3780 \end{textblock}
3781 }
3782 }{}
3783 }
3784 \newcommand{\xepersianInit}{
3785 \setlength{\headheight}{14pt}
3786 \renewcommand{\headrulewidth}{0.4pt}
3787
3788 \pagestyle{fancy}
3789
3790 \setlength{\columnseprule}{\columnlines}
3791 \setlength{\fboxrule}{0.1 pt}
3792
3793 }
3794
3795 \def\customlogo#1{\gdef\@customlogo{\beginR#1\endR}}
3796 \def\customminilogo#1{\gdef\@customminilogo{\beginR#1\endR}}
3797 \def\custommagazinenamename#1{\gdef\@custommagazinenamename{\beginR#1\endR}}
3798 \newcommand{\logo}[0]{
3799 %% Heading %%
3800 \noindent\hrulefill\hspace{10pt}\xepersian@editionLogo\hspace{5pt}\xepersian@www
3801
3802 \vspace*{-3pt}
3803
3804 {\Large\bfseries \@customlogo}
3805 \hrulefill
3806 \hspace{10pt}\xepersian@headDateTime
3807
3808 }
3809 \newcommand{\minilogo}[0]{
3810 {\large\bfseries \@customminilogo}
3811

```



```

3812 \vspace*{5pt}
3813 }
3814 \newcommand{\mylogo}[1]{
3815 {\beginR#1\endR}
3816
3817 \noindent
3818 \xepersian@editionLogo\hspace{5pt}
3819 \hrulefill
3820 \hspace{5pt}\xepersian@headDateTime
3821 }
3822 \newcommand{\edition}[1]{\renewcommand{\xepersian@edition}{#1}}
3823 \newenvironment{frontpage}[0]
3824 {
3825 \setboolean{xepersian@insidefrontpage}{true}
3826 \thispagestyle{empty}
3827 \logo
3828
3829 }%
3830 {
3831 \thispagestyle{empty}
3832 \clearpage
3833 \newpage
3834 \fancyhead{}
3835 \fancyfoot{}
3836 \fancyhead[RO,LE]{\beginR\xepersian@headright\endR}
3837 \fancyhead[LO,RE]{\beginR\xepersian@headleft\endR}
3838 \fancyhead[C]{\beginR\xepersian@headcenter\endR}
3839 \fancyfoot[RO,LE]{\beginR\xepersian@footright\endR}
3840 \fancyfoot[LO,RE]{\beginR\xepersian@footleft\endR}
3841 \fancyfoot[C]{\beginR\xepersian@footcenter\endR}
3842 \renewcommand{\headrulewidth}{0.4pt}
3843 \setboolean{xepersian@insidefrontpage}{false}
3844
3845 }
3846 \newcommand{\firstarticle}[3]
3847 {
3848 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
3849 \ifthenelse{\boolean{xepersian@hyphenatedtitles}}{%
3850 \begin{textblock}{24}(22,5)
3851 }
3852 {
3853 \begin{textblock}{28}(22,5)
3854 }
3855 \vspace{-7pt}
3856 \xepersian@firstTitle{#1}
3857 \end{textblock}
3858 \begin{textblock}{29}(22,10)
3859 \vspace{5pt plus 2pt minus 2pt}
3860
3861 \xepersian@firstText{\timestamp{#3}~#2}

```




```

3862
3863 \end{textblock}
3864
3865 \begin{textblock}{50}(0,15)
3866 \rule{50\TPHorizModule}{.3pt}
3867 \end{textblock}
3868 }{%else
3869 \ClassError{xepersian-magazine}{%
3870 \protect\firstarticle\space in a wrong place.\MessageBreak
3871 \protect\firstarticle\space may only appear inside frontpage environment.
3872 }{%
3873 \protect\firstarticle\space may only appear inside frontpage environment.
3874 }%
3875 }
3876 }
3877 \newcommand{\secondarticle}[5]
3878 {
3879 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
3880 \begin{textblock}{33}(2,16)
3881 \xepersian@pages{#4}
3882 \vspace{-5pt}
3883 \xepersian@secondTitle{#1}
3884
3885 \vspace*{5pt}
3886
3887 \xepersian@secondSubtitle{#2}
3888
3889 \vspace*{-7pt}
3890
3891 \xepersian@secondText{\timestamp{#5}~#3}
3892
3893 \end{textblock}
3894
3895 \begin{textblock}{33}(2,25)
3896 \vspace{5pt plus 2pt minus 2pt}
3897
3898 \noindent\ignorespaces\rule{33\TPHorizModule}{.3pt}
3899 \end{textblock}
3900 }{%else
3901 \ClassError{xepersian-magazine}{%
3902 \protect\secondarticle\space in a wrong place.\MessageBreak
3903 \protect\secondarticle\space may only appear inside frontpage environment.
3904 }{%
3905 \protect\secondarticle\space may only appear inside frontpage environment.
3906 }%
3907 }
3908 }
3909 \newcommand{\thirdarticle}[6]
3910 {
3911 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%

```



```

3912 \begin{textblock}{32}(2,26)
3913 \xepersian@pages{#5}
3914 \vspace{-5pt}
3915 \setlength{\fboxsep}{1pt}
3916 \xepersian@thirdTitle{#1}
3917
3918 \vspace*{5pt}
3919
3920 \xepersian@thirdSubtitle{#2}
3921
3922 \vspace*{5pt}
3923
3924 {\noindent\ignorespaces %
3925 \ifthenelse{\equal{#4}{}}{}{}}
3926
3927 \xepersian@thirdText{\timestamp{#6}~#3}
3928
3929 }
3930
3931 \vspace*{5pt}
3932
3933 \end{textblock}
3934 }{%else
3935 \ClassError{xepersian-magazine}{%
3936 \protect\thirdarticle\space in a wrong place.\MessageBreak
3937 \protect\thirdarticle\space may only appear inside frontpage environment.
3938 }{%
3939 \protect\thirdarticle\space may only appear inside frontpage environment.
3940 }%
3941 }
3942 }
3943 \newcommand{\firstimage}[2]
3944 {
3945 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
3946 \begin{textblock}{18}(2,5)
3947 \setlength{\fboxsep}{1pt}
3948 \ifxetex % only in PDF
3949 \noindent\fbbox{\includegraphics[width = 18\TPHorizModule ]{#1}}
3950 \fi
3951
3952 \xepersian@pictureCaption{#2}
3953 \end{textblock}%
3954 }
3955 {\ClassError{xepersian-magazine}{%
3956 \protect\firstimage\space in a wrong place.\MessageBreak
3957 \protect\firstimage\space may only appear inside frontpage environment.
3958 }{%
3959 \protect\firstimage\space may only appear inside frontpage environment.
3960 }}
3961 }%

```



```

3962 \newcommand{\weatheritem}[5]{%
3963 \ifthenelse{\boolean{xepersian@insideweather}}{%
3964 \begin{minipage}{45pt}
3965 \ifxetex
3966 \includegraphics[width=40pt]{#1}
3967 \fi
3968 \end{minipage}
3969 \begin{minipage}{50pt}
3970 \weatherTempFormat
3971 #2\\
3972 \beginL#3 $\!$ #4 \lr{\weatherUnits{}}\endL\\
3973 #5
3974 \end{minipage}
3975 }{%else
3976 \ClassError{xepersian-magazine}{%
3977 \protect\weatheritem\space in a wrong place.\MessageBreak
3978 \protect\weatheritem\space may only appear inside weatherblock environment.
3979 }{%
3980 \protect\weatheritem\space may only appear inside weatherblock environment.\MessageBreak
3981 weatherblock environment may only appear inside frontpage environment.
3982 }%
3983 }
3984 }
3985 \newenvironment{weatherblock}[1]
3986 {
3987 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
3988 \setboolean{xepersian@insideweather}{true}
3989 \begin{textblock}{32}(2,38)
3990 \vspace*{-15pt}
3991
3992 \xepersian@weather{\beginR#1\endR}
3993
3994 \vspace*{5pt}
3995
3996 \noindent\begin{xepersian@fmpage}{32\TPHorizModule}
3997 \begin{minipage}{32\TPHorizModule}
3998 \hspace{5pt}
3999
4000 }{%
4001 \ClassError{xepersian-magazine}{%
4002 weatherblock in a wrong place.\MessageBreak
4003 weatherblock may only appear inside frontpage environment.
4004 }{%
4005 weatherblock may only appear inside frontpage environment.
4006 }
4007 }
4008 }%
4009 {
4010 \end{minipage}
4011 \end{xepersian@fmpage}

```



```

4012 \end{textblock}
4013 \setboolean{xepersian@insideweather}{false}
4014 }
4015 \newenvironment{authorblock}[0]
4016 {
4017 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4018 \begin{textblock}{15}(36,35)
4019 \setlength{\fboxsep}{5pt}
4020 \begin{xepersian@fmpage}{13\TPHorizModule}
4021 \begin{minipage}{13\TPHorizModule}
4022 \centering
4023 \minilogo
4024
4025 }{%else
4026 \ClassError{xepersian-magazine}{%
4027 authorblock in a wrong place.\MessageBreak
4028 authorblock may only appear inside frontpage environment.
4029 }{%
4030 authorblock may only appear inside frontpage environment.
4031 }
4032 }
4033 }
4034 {
4035 \end{minipage}
4036 \end{xepersian@fmpage}
4037 \end{textblock}
4038 }
4039 \newenvironment{indexblock}[1]
4040 {
4041 \ifthenelse{\boolean{xepersian@insidefrontpage}}{%
4042 \setboolean{xepersian@insideindex}{true}%let's in
4043 \begin{textblock}{15}(36,16)
4044 \setlength{xepersian@indexwidth}{13\TPHorizModule}
4045 \xepersian@indexFrameTitle{#1}
4046
4047 \setlength{\fboxsep}{5pt} %espacio entre el frame y la imagen
4048 \begin{xepersian@fmpage}{\xepersian@indexwidth}
4049 \begin{minipage}{\xepersian@indexwidth}
4050 \vspace*{10pt}
4051 }{%else
4052 \ClassError{xepersian-magazine}{%
4053 indexblock in a wrong place.\MessageBreak
4054 indexblock may only appear inside frontpage environment.
4055 }{%
4056 indexblock may only appear inside frontpage environment.
4057 }
4058 }
4059 }%
4060 {
4061 \end{minipage}

```



```

4062 \end{xepersian@fmpage}
4063 \end{textblock}
4064 \setboolean{xepersian@insideindex}{false}%let's out
4065 }
4066 \newcommand{\indexitem}[2]
4067 {
4068 \ifthenelse{\boolean{xepersian@insideindex}}{
4069 \xepersian@indexEntry{#1 \xepersian@indexEntryPage{\pageref{#2}}}
4070
4071 \vspace{0.5cm}
4072
4073 \noindent\ignorespaces\indexEntrySeparator{}
4074 }{%else
4075 \ClassError{xepersian-magazine}{%
4076 \protect\indexitem\space in a wrong place.\MessageBreak
4077 \protect\indexitem\space may only appear inside indexblock environment.
4078 }{%
4079 \protect\indexitem\space may only appear inside indexblock environment.\MessageBreak
4080 indexblock environment may only appear inside frontpage environment.
4081 }%
4082 }
4083 }
4084 \newcommand{\xepersian@inexpandedtitle}[1]{
4085 \begin{minipage}{.95\textwidth}
4086 \begin{center}
4087 \noindent\Large\textbf{\beginR#1\endR}
4088 \end{center}
4089 \end{minipage}
4090 }
4091 \newcommand{\expandedtitle}[2]{
4092 \end{multicols}
4093
4094 \begin{center}
4095 \setlength{\fboxsep}{5pt}
4096 \setlength{\shadowsize}{2pt}
4097 \ifthenelse{\equal{#1}{shadowbox}}{%
4098 \shadowbox{%
4099 \xepersian@inexpandedtitle{#2}%
4100 }%
4101 }{}
4102 \ifthenelse{\equal{#1}{doublebox}}{%
4103 \doublebox{%
4104 \xepersian@inexpandedtitle{#2}%
4105 }%
4106 }{}
4107 \ifthenelse{\equal{#1}{ovalbox}}{%
4108 \ovalbox{%
4109 \xepersian@inexpandedtitle{#2}%
4110 }%
4111 }{}

```



```

4112 \ifthenelse{\equal{#1}{0valbox}}{%
4113 \0valbox{%
4114 \xepersian@inexpandedtitle{#2}%
4115 }%
4116 }{}
4117 \ifthenelse{\equal{#1}{lines}}{
4118 \hrule
4119 \vspace*{8pt}
4120 \begin{center}
4121 \noindent\Large\textbf{#2}
4122 \end{center}
4123 \vspace*{8pt}
4124 \hrule
4125 }{}
4126 \end{center}
4127
4128 \begin{multicols}{\xepersian@ncolumns{}}
4129 \ifnum \xepersian@ncolumns > \minraggedcols
4130 \raggedFormat
4131 \fi
4132 }
4133 \newcommand{\xepersian@incolumntitle}[2]{
4134 \begin{minipage}{#1}
4135 \begin{center}
4136 \noindent\normalsize\textbf{#2}
4137 \end{center}
4138 \end{minipage}
4139 }
4140
4141 \newcommand{\columnntitle}[2]{
4142 \vspace*{5pt}
4143 \begin{center}
4144 \setlength{\fboxsep}{5pt}
4145 \setlength{\shadowsize}{2pt}
4146 \addtolength{\xepersian@coltitsize}{\columnwidth}
4147 \addtolength{\xepersian@coltitsize}{-1\columnsep}
4148 \addtolength{\xepersian@coltitsize}{-5pt}
4149 \addtolength{\xepersian@coltitsize}{-1\shadowsize}
4150 \ifthenelse{\equal{#1}{shadowbox}}{%
4151 \shadowbox{%
4152 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4153 }%
4154 }{}
4155 \ifthenelse{\equal{#1}{doublebox}}{%
4156 \doublebox{%
4157 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4158 }%
4159 }{}
4160 \ifthenelse{\equal{#1}{ovalbox}}{%
4161 \ovalbox{%

```



```

4162 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4163 }%
4164 }{}
4165 \ifthenelse{\equal{#1}{0valbox}}{%
4166 \0valbox{%
4167 \xepersian@incolumntitle{\xepersian@coltitsize}{#2}%
4168 }%
4169 }{}
4170 \ifthenelse{\equal{#1}{lines}}{
4171 \hrule
4172 \vspace*{5pt}
4173 \begin{center}
4174 \noindent\normalsize\textbf{#2}
4175 \end{center}
4176 \vspace*{5pt}
4177 \hrule
4178 }{}
4179 \end{center}
4180 }
4181 \renewcommand{\date}{%
4182 \longdate{\today}%
4183 }
4184 \newcommand{\authorandplace}[2]{%
4185 \rightline{%
4186 {\innerAuthorFormat #1},\space{\innerPlaceFormat #2}%
4187 }%
4188 \par %
4189 }
4190 \newcommand{\newsection}[1]{
4191 \renewcommand{\xepersian@section}{#1}
4192 }
4193 \newenvironment{article}[5]
4194 {
4195 \xepersian@say{Adding a new piece of article}
4196 \renewcommand{\xepersian@ncolumns}{#1}
4197 \begin{multicols}{#1}[
4198 \xepersian@pages{#4}
4199 \xepersian@innerTitle{#2}%
4200 \xepersian@innerSubtitle{#3}%
4201 ] [4cm]%
4202 \label{#5}
4203 \ifnum #1 > \minraggedcols
4204 \raggedFormat
4205 \fi
4206 }
4207 {\sim\innerTextFinalMark{
4208 \end{multicols}
4209 }
4210 \newcommand{\articlesep}{%
4211 \setlength{\xepersian@pageneed}{16000pt}

```



```

4212 \setlength\xepersian@pageleft{\pagegoal}
4213 \addtolength\xepersian@pageleft{-\pagetotal}
4214
4215 \xepersian@say{How much left \the\xepersian@pageleft}
4216
4217 \ifdim \xepersian@pageneed < \xepersian@pageleft
4218 \xepersian@say{Not enough space}
4219 \else
4220 \xepersian@say{Adding sep line between articles}
4221 \vspace*{10pt plus 10pt minus 5pt}
4222 \hrule
4223 \vspace*{10pt plus 5pt minus 5pt}
4224 \fi
4225
4226 }
4227 \newcommand{\xepersian@editorialTit}[2]{
4228 \setlength{\arrayrulewidth}{.1pt}
4229 \begin{center}
4230 \begin{tabular}{c}
4231 \noindent
4232 \xepersian@editorialTitle{#1}
4233 \vspace{2pt plus 1pt minus 1pt}
4234 \\
4235 \hline
4236 \vspace{2pt plus 1pt minus 1pt}
4237 \\
4238 \editorialAuthorFormat{#2}
4239 \end{tabular}
4240 \end{center}
4241 }
4242 \newenvironment{editorial}[4]
4243 {
4244 \xepersian@say{Adding a new editorial}
4245 \begin{multicols}{#1}[%
4246 \xepersian@editorialTit{#2}{#3}%
4247 ] [4cm]
4248 \label{#4}
4249 \ifnum #1 > \minraggedcols
4250 \raggedFormat
4251 \fi
4252 }
4253 {
4254 \end{multicols}
4255 }
4256 \newcommand{\xepersian@shortarticleTit}[2]{
4257 \begin{center}
4258 \vbox{%
4259 \noindent
4260 \xepersian@shortarticleTitle{#1}
4261 \vspace{4pt plus 2pt minus 2pt}

```




```

4262 \hrule
4263 \vspace{4pt plus 2pt minus 2pt}
4264 \xepersian@shortarticleSubtitle{#2}
4265 }
4266 \end{center}
4267 }
4268 \newenvironment{shortarticle}[4]
4269 {
4270 \xepersian@say{Adding a short article block}
4271 \begin{multicols}{#1}[\xepersian@shortarticleTit{#2}{#3}][4cm] %
4272 \label{#4}
4273 \par %
4274 \ifnum #1 > \minraggedcols
4275 \raggedFormat
4276 \fi
4277 }
4278 {
4279 \end{multicols}
4280 }
4281 \newcommand{\shortarticleitem}[2]{
4282 \goodbreak
4283 \vspace{5pt plus 3pt minus 3pt}
4284 {\vbox{\noindent\xepersian@shortarticleItemTitle{#1}}}
4285 \vspace{5pt plus 3pt minus 3pt}
4286 {\noindent #2}\\
4287 }

```

7.57 xepersian-mathsdigitspec.sty

```

4288 \NeedsTeXFormat{LaTeX2e}
4289 \ProvidesPackage{xepersian-mathsdigitspec}
4290 [2016/05/03 v1.1.2 Unicode Persian maths digits in XeLaTeX]
4291 \def\new@mathgroup{\alloc@8\mathgroup\chardef\@cclvi}
4292 \let\newfam\new@mathgroup
4293 \def\select@group#1#2#3#4{%
4294 \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
4295 {%
4296 \ifmmode
4297 \ifnum\csname c@mv@\math@version\endcsname<\@cclvi
4298 \begingroup
4299 \escapechar\m@ne
4300 \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
4301 \globaldefs\@ne \math@fonts
4302 \endgroup
4303 \init@restore@version
4304 \xdef#1{\noexpand\use@mathgroup\noexpand#2%
4305 {\number\csname c@mv@\math@version\endcsname}}%
4306 \global\advance\csname c@mv@\math@version\endcsname\@ne
4307 \else
4308 \let#1\relax

```



```

4309 \latex@error{Too many math alphabets used in
4310 version \math@version}%
4311 \@eha
4312 \fi
4313 \else \expandafter\non@alpherr\fi
4314 #1{#4}%
4315 }%
4316 }
4317 \def\document@select@group#1#2#3#4{%
4318 \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
4319 {%
4320 \ifmmode
4321 \ifnum\csname c@mv@\math@version\endcsname<\@cclvi
4322 \begingroup
4323 \escapechar\m@ne
4324 \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
4325 \globaldefs\@ne \math@fonts
4326 \endgroup
4327 \expandafter\extract@alph@from@version
4328 \csname mv@\math@version\expandafter\endcsname
4329 \expandafter{\number\csname
4330 c@mv@\math@version\endcsname}%
4331 #1%
4332 \global\advance\csname c@mv@\math@version\endcsname\@ne
4333 \else
4334 \let#1\relax
4335 \latex@error{Too many math alphabets used
4336 in version \math@version}%
4337 \@eha
4338 \fi
4339 \else \expandafter\non@alpherr\fi
4340 #1{#4}%
4341 }%
4342 }
4343 \ExplSyntaxOn
4344 \bool_set_false:N \g__fontspec_math_bool
4345 \tl_map_inline:nn
4346 {
4347 \new@mathgroup\cdp@list\cdp@elt\DeclareMathSizes
4348 \@DeclareMathSizes\newmathalphabet\newmathalphabet@@\newmathalphabet@@@
4349 \DeclareMathVersion\define@mathalphabet\define@mathgroup\addtoversion
4350 \version@list\version@elt\alpha@list\alpha@elt
4351 \restore@mathversion\init@restore@version\dorestore@version\process@table
4352 \new@mathversion\DeclareSymbolFont\group@list\group@elt
4353 \new@symbolfont\SetSymbolFont\SetSymbolFont@\get@cdp
4354 \DeclareMathAlphabet\new@mathalphabet\SetMathAlphabet\SetMathAlphabet@
4355 \DeclareMathAccent\set@mathaccent\DeclareMathSymbol\set@mathchar
4356 \set@mathsymbol\DeclareMathDelimiter\@xxDeclareMathDelimiter
4357 \@DeclareMathDelimiter\@xDeclareMathDelimiter\set@mathdelimiter
4358 \set@mathdelimiter\DeclareMathRadical\mathchar@type

```



```

4359 \DeclareSymbolFontAlphabet\DeclareSymbolFontAlphabet@
4360 }
4361 {
4362 \tl_remove_once:Nn \@preamblecmds {\do#1}
4363 }
4364 \ExplSyntaxOff
4365 \newcommand\xepersian@PackageInfo[1]{\PackageInfo{xepersian-mathsdigitspec}{#1}}
4366 \newcommand\SetMathCode[4]{%
4367 \Umathcode#1="\mathchar@type#2 \csname sym#3\endcsname #4\relax}
4368 \newcommand\SetMathCharDef[4]{%
4369 \Umathchardef#1="\mathchar@type#2 \csname sym#3\endcsname #4\relax}
4370 \ExplSyntaxOn
4371 \cs_new_eq:NN \orig_mathbf:n \mathbf
4372 \cs_new_eq:NN \orig_mathit:n \mathit
4373 \cs_new_eq:NN \orig_mathrm:n \mathrm
4374 \cs_new_eq:NN \orig_mathsf:n \mathsf
4375 \cs_new_eq:NN \orig_mathtt:n \mathtt
4376 \NewDocumentCommand \new@mathbf { m } {
4377 \orig_mathbf:n {
4378 \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4379 \mathcode ##1 = \numexpr "100 * \symnew@mathbf@font@digits + ##1 \relax
4380 }
4381 #1
4382 }
4383 }
4384 \NewDocumentCommand \new@mathit { m } {
4385 \orig_mathit:n {
4386 \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4387 \mathcode ##1 = \numexpr "100 * \symnew@mathit@font@digits + ##1 \relax
4388 }
4389 #1
4390 }
4391 }
4392 \NewDocumentCommand \new@mathrm { m } {
4393 \orig_mathrm:n {
4394 \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4395 \mathcode ##1 = \numexpr "100 * \symnew@mathrm@font@digits + ##1 \relax
4396 }
4397 #1
4398 }
4399 }
4400 \NewDocumentCommand \new@mathsf { m } {
4401 \orig_mathsf:n {
4402 \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4403 \mathcode ##1 = \numexpr "100 * \symnew@mathsf@font@digits + ##1 \relax
4404 }
4405 #1
4406 }
4407 }
4408 \NewDocumentCommand \new@mathtt { m } {

```



```

4409 \orig_mathtt:n {
4410   \int_step_inline:nnnn { `0 } { \c_one } { `9 } {
4411     \mathcode ##1 = \numexpr "100 * \symnew@mathtt@font@digits + ##1 \relax
4412   }
4413   #1
4414 }
4415 }
4416 \DeclareDocumentCommand \setdigitfont { 0{} m 0{} }
4417 {
4418   \let\glb@currsize\relax
4419   \fontspec_set_family:Nnn \g__xepersian_digitsfamily_family {Mapping=parsidigits,#1,#3} {#2}
4420   \xepersian@PackageInfo{Defining the default Persian maths digits font as '#2'}
4421   \DeclareSymbolFont{OPERATORS} {\g_fontspec_encoding_tl}{\g__xepersian_digitsfamily_family}
4422   \DeclareSymbolFont{new@mathbf@font@digits}{\g_fontspec_encoding_tl}{\g__xepersian_digitsfamily_family}
4423   \DeclareSymbolFont{new@mathit@font@digits}{\g_fontspec_encoding_tl}{\g__xepersian_digitsfamily_family}
4424   \DeclareSymbolFont{new@mathrm@font@digits}{\g_fontspec_encoding_tl}{\g__xepersian_digitsfamily_family}
4425   \def\persianmathsdigits{%
4426     \SetMathCode{`0}{\mathalpha}{OPERATORS}{`0}
4427     \SetMathCode{`1}{\mathalpha}{OPERATORS}{`1}
4428     \SetMathCode{`2}{\mathalpha}{OPERATORS}{`2}
4429     \SetMathCode{`3}{\mathalpha}{OPERATORS}{`3}
4430     \SetMathCode{`4}{\mathalpha}{OPERATORS}{`4}
4431     \SetMathCode{`5}{\mathalpha}{OPERATORS}{`5}
4432     \SetMathCode{`6}{\mathalpha}{OPERATORS}{`6}
4433     \SetMathCode{`7}{\mathalpha}{OPERATORS}{`7}
4434     \SetMathCode{`8}{\mathalpha}{OPERATORS}{`8}
4435     \SetMathCode{`9}{\mathalpha}{OPERATORS}{`9}
4436     \SetMathCode{`%}{\mathbin}{OPERATORS}{` }
4437     \SetMathCharDef{\decimalseparator}{\mathord}{OPERATORS}{"066B}
4438     \tl_set_eq:NN \mathbf \new@mathbf
4439     \tl_set_eq:NN \mathit \new@mathit
4440     \tl_set_eq:NN \mathrm \new@mathrm
4441   }
4442
4443
4444 \DeclareDocumentCommand \setmathsfdigitfont { 0{} m 0{} }
4445 {
4446   \fontspec_set_family:Nnn \g__fontspec_mathsf_tl {Mapping=parsidigits,#1,#3} {#2}
4447   \DeclareSymbolFont{new@mathsf@font@digits}{\g_fontspec_encoding_tl}{\g__fontspec_mathsf_tl}
4448   \def\persianmathsfdigits{\tl_set_eq:NN \mathsf \new@mathsf}
4449 }
4450
4451
4452
4453 \DeclareDocumentCommand \setmathttdigitfont { 0{} m 0{} }
4454 {
4455   \fontspec_set_family:Nnn \g__fontspec_mathtt_tl {Mapping=parsidigits,#1,#3} {#2}
4456   \DeclareSymbolFont{new@mathtt@font@digits}{\g_fontspec_encoding_tl}{\g__fontspec_mathtt_tl}
4457   \def\persianmathttdigits{\tl_set_eq:NN \mathtt \new@mathtt}

```



```

4458 }
4459
4460 \ExplSyntaxOff
4461 \ifx\newcommand\undefined\else
4462   \newcommand{\ZifferAn}{}
4463 \fi
4464 \mathchardef\ziffer@DotOri="013A
4465 {\ZifferAn
4466   \catcode\.\=\active\gdef.{\begingroup\obeyspaces\futurelet\n\ziffer@dcheck}}
4467 \def\ziffer@dcheck{\ziffer@check\ZifferLeer\ziffer@DotOri}
4468 \def\ziffer@check#1#2{%
4469   \ifx\n1\endgroup#1\else
4470     \ifx\n2\endgroup#1\else
4471       \ifx\n3\endgroup#1\else
4472         \ifx\n4\endgroup#1\else
4473           \ifx\n5\endgroup#1\else
4474             \ifx\n6\endgroup#1\else
4475               \ifx\n7\endgroup#1\else
4476                 \ifx\n8\endgroup#1\else
4477                   \ifx\n9\endgroup#1\else
4478                     \ifx\n0\endgroup#1\else
4479                       \ifx\n\overline\endgroup#1\else
4480                         \endgroup#2%
4481                       \fi
4482                     \fi
4483                   \fi
4484                 \fi
4485               \fi
4486             \fi
4487           \fi
4488         \fi
4489       \fi
4490     \fi
4491   \fi}
4492 \mathcode\.`="8000\relax
4493 \def\ZifferLeer{\ifx\decimalseparator\undefined.\else\decimalseparator\fi}
4494 \def\DefaultMathsDigits{\def\SetMathsDigits{}}
4495 \def\PersianMathsDigits{\def\SetMathsDigits{%
4496   \ifx\persianmathsdigits\undefined\else\persianmathsdigits\fi%
4497   \ifx\persianmathsfdigits\undefined\else\persianmathsfdigits\fi%
4498   \ifx\persianmaththtdigits\undefined\else\persianmaththtdigits\fi}}
4499 \def\AutoMathsDigits{\def\SetMathsDigits{%
4500   \ifx\persianmathsdigits\undefined\else\if@nonlatin\persianmathsdigits\fi\fi%
4501   \ifx\persianmathsfdigits\undefined\else\if@nonlatin\persianmathsfdigits\fi\fi%
4502   \ifx\persianmaththtdigits\undefined\else\if@nonlatin\persianmaththtdigits\fi\fi}}
4503 \AutoMathsDigits
4504 \everymath\expandafter{\the\everymath\SetMathsDigits}
4505 \g@addto@macro\document{\everydisplay\expandafter{\the\everydisplay\SetMathsDigits}}

```



7.58 xepersian-multiplechoice.sty

```

4506 \NeedsTeXFormat{LaTeX2e}
4507 \ProvidesPackage{xepersian-multiplechoice}[2010/07/25 v0.2
4508           Multiple Choice Questionnaire class for Persian in XeLaTeX]
4509 \RequirePackage{pifont}
4510 \RequirePackage{fullpage}
4511 \RequirePackage{ifthen}
4512 \RequirePackage{calc}
4513 \RequirePackage{verbatim}
4514 \RequirePackage{tabularx}
4515 \def\@headerfont{\bfseries}
4516 \newcommand\headerfont[1]{\gdef\@headerfont{#1}}
4517 \def\@X{X}
4518 \newcommand\X[1]{\gdef\@X{#1}}
4519 \def\pbs#1{\let\tmp=\#1\let\=\tmp}
4520 \newcolumnntype{D}{>\pbs\centering}X}
4521 \newcolumnntype{Q}{>\@headerfont}X}
4522
4523 \renewcommand\tabularxcolumn[1]{m{#1}}
4524 \newcommand\makeform@nocorrection{%
4525   \addtocontents{frm}{\protect\end{tabularx}}
4526   \@starttoc{frm}}
4527 \newcommand\makeform@correction{%
4528   \addtocontents{frm}{\protect\end{tabularx}}}
4529 \newcommand\makemask@nocorrection{%
4530   \addtocontents{msk}{\protect\end{tabularx}}
4531   \@starttoc{msk}}
4532 \newcommand\makemask@correction{%
4533   \addtocontents{msk}{\protect\end{tabularx}}}
4534 \newlength\questionspace
4535 \setlength\questionspace{0pt}
4536 \newcommand\answerstyle[1]{\gdef\@answerstyle{#1}}
4537 \def\@answerstylefont{\bfseries}
4538 \newcommand\answerstylefont[1]{\gdef\@answerstylefont{#1}}
4539 \def\@answernumberfont{\bfseries}
4540 \newcommand\answernumberfont[1]{\gdef\@answernumberfont{#1}}
4541 \newcounter{question}\stepcounter{question}
4542 \newcounter{@choice}
4543 \def\@initorcheck{%
4544   \xdef\@choices{\the@choice}%
4545   \setcounter{@choice}{1}%
4546   \gdef\@arraydesc{|Q||}%
4547   \gdef\@headerline{}}
4548 \whiledo{\not{\value{@choice}>\@choices}}{
4549   \xdef\@arraydesc{\@arraydesc D|}
4550   \def\@appendheader{\g@addto@macro\@headerline}
4551   \@appendheader{&\protect\@headerfont}
4552   \edef\@the@choice{\alph{@choice}}
4553   \expandafter\@appendheader\@the@choice

```



```

4554 \stepcounter{@choice}}%
4555 \addtocontents{frm}{%
4556 \protect\begin{tabularx}{\protect\linewidth}{\@arraydesc}
4557 \protect\hline
4558 \@headerline\protect\\protect\hline\protect\hline}%
4559 \addtocontents{msk}{%
4560 \protect\begin{tabularx}{\protect\linewidth}{\@arraydesc}
4561 \protect\hline
4562 \@headerline\protect\\protect\hline\protect\hline}%
4563 \gdef\@initorcheck{%
4564 \ifthenelse{value{@choice} = \@choices}{}%
4565 \ClassError{xepersian-multiplechoice}{Question \thequestion: wrong number of choices
4566 (\the@choice\space instead of \@choices)}{%
4567 Questions must all have the same number of proposed answers.%
4568 \MessageBreak
4569 Type X <return> to quit, fix your MCQ (multiple choice question) and rerun XeLaTeX.}}}%
4570 \newenvironment{question}[1]{%
4571 %% \begin{question}
4572 \begin{minipage}{\textwidth}
4573 \xdef\@formanswerline{\@questionheader}%
4574 \xdef\@maskanswerline{\@questionheader}%
4575 \fbox{\parbox[c]{\linewidth}{#1}}
4576 \vspace\questionspace\par
4577 {\@answerstitlefont\@answerstitle}
4578 \begin{list}{\@answernumberfont\alph{@choice}}~{\usecounter{@choice}}{%
4579 %% \end{question}
4580 \end{list}
4581 \@initorcheck%
4582 \addtocontents{frm}{\@formanswerline\protect\\protect\hline}%
4583 \addtocontents{msk}{\@maskanswerline\protect\\protect\hline}%
4584 \end{minipage}
4585 \stepcounter{question}}
4586 \def\@truesymbol{\ding{52}~}
4587 \def\@falsesymbol{\ding{56}~}
4588 \newcommand\truesymbol[1]{\gdef\@truesymbol{#1}}
4589 \newcommand\falsesymbol[1]{\gdef\@falsesymbol{#1}}
4590 \def\@true@nocorrection{\item}
4591 \def\@false@nocorrection{\item}
4592 \def\@true@correction{\item[\@truesymbol\refstepcounter{@choice}]}
4593 \def\@false@correction{\item[\@falsesymbol\refstepcounter{@choice}]}
4594 \newcommand\true{%
4595 \xdef\@formanswerline{\@formanswerline&}%
4596 \xdef\@maskanswerline{\@maskanswerline&\@X}%
4597 \@true}%
4598 \newcommand>false{%
4599 \xdef\@formanswerline{\@formanswerline&}%
4600 \xdef\@maskanswerline{\@maskanswerline&}%
4601 \@false}%
4602 \def\@correctionstyle{\itshape}
4603 \newcommand\correctionstyle[1]{\gdef\@correctionstyle{#1}}

```



```

4604 \newenvironment{@correction}{\@correctionstyle}{}
4605 \def\@questionheader{ \thequestion}
4606 \answerstyle{ }
4607 \DeclareOption{nocorrection}{%
4608 \let\@true\@true@nocorrection
4609 \let\@false\@false@nocorrection
4610 \let\correction\comment
4611 \let\endcorrection\endcomment
4612 \def\makeform{\makeform@nocorrection}
4613 \def\makemask{\makemask@nocorrection}}
4614 \DeclareOption{correction}{%
4615 \let\@true\@true@correction
4616 \let\@false\@false@correction
4617 \let\correction\@correction
4618 \let\endcorrection\end@correction
4619 \def\makeform{\makeform@correction}
4620 \def\makemask{\makemask@correction}}
4621 \ExecuteOptions{nocorrection}
4622 \newcommand\questiontitle[1]{\gdef\@questiontitle{#1}}
4623 \def\@questiontitlefont{\bfseries}
4624 \newcommand\questiontitlefont[1]{\gdef\@questiontitlefont{#1}}
4625 \newlength\questiontitlespace
4626 \setlength\questiontitlespace{5pt}
4627 \newlength\questionsepspace
4628 \setlength\questionsepspace{20pt}
4629 \gdef\@questionsepspace{0pt}
4630 \let\old@question\question
4631 \let\old@endquestion\endquestion
4632 \renewenvironment{question}[1]{%
4633 %% \begin{question}
4634 \vspace\@questionsepspace
4635 \fbox{\parbox[c]{0.25\linewidth}{\@questiontitlefont\@questiontitle}}
4636 \nopagebreak\vspace\questiontitlespace\par
4637 \old@question{#1}}{%
4638 %% \end{question}
4639 \old@endquestion
4640 \gdef\@questionsepspace{\questionsepspace}}
4641 \questiontitle{ \thequestion:}
4642 \ProcessOptions

```

7.59 xepersian-persiancal.sty

```

4643 \NeedsTeXFormat{LaTeX2e}
4644 \ProvidesPackage{xepersian-persiancal}[2012/07/25 v0.2 provides Persian calendar]
4645
4646 \newif\ifXePersian@leap \newif\ifXePersian@kabiseh
4647 \newcount\XePersian@i \newcount\XePersian@y \newcount\XePersian@m \newcount\XePersian@d
4648 \newcount\XePersian@latini \newcount\XePersian@persiani
4649 \newcount\XePersian@latinii \newcount\XePersian@persianii
4650 \newcount\XePersian@latiniii \newcount\XePersian@persianiii

```




```

4651 \newcount\XePersian@latiniv \newcount\XePersian@persianiv
4652 \newcount\XePersian@latinvi \newcount\XePersian@persianv
4653 \newcount\XePersian@latinvi \newcount\XePersian@persianvi
4654 \newcount\XePersian@latinvii \newcount\XePersian@persianvii
4655 \newcount\XePersian@latinviii \newcount\XePersian@persianviii
4656 \newcount\XePersian@latinix \newcount\XePersian@persianix
4657 \newcount\XePersian@latinx \newcount\XePersian@persianx
4658 \newcount\XePersian@latinxi \newcount\XePersian@persianxi
4659 \newcount\XePersian@latinxii \newcount\XePersian@persianxii
4660 \newcount\XePersian@persianxiii
4661
4662 \newcount\XePersian@temp
4663 \newcount\XePersian@temptwo
4664 \newcount\XePersian@tempthree
4665 \newcount\XePersian@yModHundred
4666 \newcount\XePersian@thirtytwo
4667 \newcount\XePersian@dn
4668 \newcount\XePersian@sn
4669 \newcount\XePersian@mminusone
4670
4671
4672 \XePersian@y=\year \XePersian@m=\month \XePersian@d=\day
4673 \XePersian@temp=\XePersian@y
4674 \divide\XePersian@temp by 100\relax
4675 \multiply\XePersian@temp by 100\relax
4676 \XePersian@yModHundred=\XePersian@y
4677 \advance\XePersian@yModHundred by -\XePersian@temp\relax
4678 \ifodd\XePersian@yModHundred
4679 \XePersian@leapfalse
4680 \else
4681 \XePersian@temp=\XePersian@yModHundred
4682 \divide\XePersian@temp by 2\relax
4683 \ifodd\XePersian@temp\XePersian@leapfalse
4684 \else
4685 \ifnum\XePersian@yModHundred=0%
4686 \XePersian@temp=\XePersian@y
4687 \divide\XePersian@temp by 400\relax
4688 \multiply\XePersian@temp by 400\relax
4689 \ifnum\XePersian@y=\XePersian@temp\XePersian@leaptrue\else\XePersian@leapfalse\fi
4690 \else\XePersian@leaptrue
4691 \fi
4692 \fi
4693 \fi
4694 \XePersian@latini=31\relax
4695 \ifXePersian@leap
4696 \XePersian@latinii = 29\relax
4697 \else
4698 \XePersian@latinii = 28\relax
4699 \fi
4700 \XePersian@latiniii = 31\relax

```



```

4701 \XePersian@latiniv = 30\relax
4702 \XePersian@latinvi = 31\relax
4703 \XePersian@latinvi = 30\relax
4704 \XePersian@latinvii = 31\relax
4705 \XePersian@latinviii = 31\relax
4706 \XePersian@latinix = 30\relax
4707 \XePersian@latinx = 31\relax
4708 \XePersian@latinxi = 30\relax
4709 \XePersian@latinxii = 31\relax
4710 \XePersian@thirtytwo=32\relax
4711 \XePersian@temp=\XePersian@y
4712 \advance\XePersian@temp by -17\relax
4713 \XePersian@temptwo=\XePersian@temp
4714 \divide\XePersian@temptwo by 33\relax
4715 \multiply\XePersian@temptwo by 33\relax
4716 \advance\XePersian@temp by -\XePersian@temptwo
4717 \ifnum\XePersian@temp=\XePersian@thirtytwo\XePersian@kabisehfalsethen
4718 \else
4719   \XePersian@temptwo=\XePersian@temp
4720   \divide\XePersian@temptwo by 4\relax
4721   \multiply\XePersian@temptwo by 4\relax
4722   \advance\XePersian@temp by -\XePersian@temptwo
4723   \ifnum\XePersian@temp=z@\XePersian@kabisehtrue\else\XePersian@kabisehfalsethen\fi
4724 \fi
4725 \XePersian@tempthree=\XePersian@y % Number of Leap years
4726 \advance\XePersian@tempthree by -1
4727 \XePersian@temp=\XePersian@tempthree % T := (MY-1) div 4
4728 \divide\XePersian@temp by 4\relax
4729 \XePersian@temptwo=\XePersian@tempthree % T := T - ((MY-1) div 100)
4730 \divide\XePersian@temptwo by 100\relax
4731 \advance\XePersian@temp by -\XePersian@temptwo
4732 \XePersian@temptwo=\XePersian@tempthree % T := T + ((MY-1) div 400)
4733 \divide\XePersian@temptwo by 400\relax
4734 \advance\XePersian@temp by \XePersian@temptwo
4735 \advance\XePersian@tempthree by -611 % Number of Kabise years
4736 \XePersian@temptwo=\XePersian@tempthree % T := T - ((SY+10) div 33) * 8
4737 \divide\XePersian@temptwo by 33\relax
4738 \multiply\XePersian@temptwo by 8\relax
4739 \advance\XePersian@temp by -\XePersian@temptwo
4740 \XePersian@temptwo=\XePersian@tempthree %
4741 \divide\XePersian@temptwo by 33\relax
4742 \multiply\XePersian@temptwo by 33\relax
4743 \advance\XePersian@tempthree by -\XePersian@temptwo
4744 \ifnum\XePersian@tempthree=32\advance\XePersian@temp by 1\fi % if (SY+10) mod 33=32 then Inc(T)
4745 \divide\XePersian@tempthree by 4\relax % T := T - ((SY+10) mod 33) div 4
4746 \advance\XePersian@temp by -\XePersian@tempthree
4747 \advance\XePersian@temp by -137 % T := T - 137 Adjust the value
4748 \XePersian@persiani=31
4749 \advance\XePersian@persiani by -\XePersian@temp % now 31 - T is the persiani
4750 \XePersian@persianii = 30\relax

```



```

4751 \ifXePersian@kabiseh
4752   \XePersian@persianiii = 30\relax
4753 \else
4754   \XePersian@persianiii = 29\relax
4755 \fi
4756 \XePersian@persianiv = 31\relax
4757 \XePersian@persianv = 31\relax
4758 \XePersian@persianvi = 31\relax
4759 \XePersian@persianvii = 31\relax
4760 \XePersian@persianviii= 31\relax
4761 \XePersian@persianix = 31\relax
4762 \XePersian@persianx = 30\relax
4763 \XePersian@persianxi = 30\relax
4764 \XePersian@persianxii = 30\relax
4765 \XePersian@persianxiii= 30\relax
4766 \XePersian@dn= 0\relax
4767 \XePersian@sn= 0\relax
4768 \XePersian@mminusone=\XePersian@m
4769 \advance\XePersian@mminusone by -1\relax
4770 \XePersian@i=0\relax
4771 \ifnum\XePersian@i < \XePersian@mminusone
4772 \loop
4773 \advance \XePersian@i by 1\relax
4774 \advance\XePersian@dn by \csname XePersian@latin\romannumeral\the\XePersian@i\endcsname
4775 \ifnum\XePersian@i<\XePersian@mminusone \repeat
4776 \fi
4777 \advance \XePersian@dn by \XePersian@d
4778 \XePersian@i=1\relax
4779 \XePersian@sn = \XePersian@persiani
4780 \ifnum \XePersian@sn<\XePersian@dn
4781 \loop
4782 \advance \XePersian@i by 1\relax
4783 \advance\XePersian@sn by \csname XePersian@persian\romannumeral\the\XePersian@i\endcsname
4784 \ifnum \XePersian@sn<\XePersian@dn \repeat
4785 \fi
4786 \ifnum \XePersian@i < 4
4787   \XePersian@m = 9 \advance\XePersian@m by \XePersian@i
4788   \advance \XePersian@y by -622\relax
4789 \else
4790   \XePersian@m = \XePersian@i \advance \XePersian@m by -3\relax
4791   \advance \XePersian@y by -621\relax
4792 \fi
4793 \advance\XePersian@sn by -\csname XePersian@persian\romannumeral\the\XePersian@i%
4794 \endcsname
4795 \ifnum\XePersian@i = 1
4796   \XePersian@d = \XePersian@dn \advance \XePersian@d by 30 \advance\XePersian@d by -\XePersian
4797 \else
4798   \XePersian@d = \XePersian@dn \advance \XePersian@d by -\XePersian@sn
4799 \fi
4800 \newcommand*{\persiantoday}{\%

```



```

4801 \number\XePersian@d\space%
4802 \XePersian@persian@month{\XePersian@m}\space\number\XePersian@y%
4803 }
4804 \let\persianyear\XePersian@y
4805 \let\persianmonth\XePersian@m
4806 \let\persianday\XePersian@d
4807 \def\XePersian@persian@month#1{\ifcase#1\or or\
4808 or\
4809 or\    or\
4810 or\
4811 or\    or\
4812 or\    or\
4813 or\    or\
4814 {fi\

```



Index

Symbols	
<code>\!</code>	2165
<code>\%</code>	4436
<code>\.</code>	4466
<code>\@and</code>	2893
<code>\@if@newlist</code>	1293, 1313
<code>\@math</code>	166
<code>\@maybeautodot</code>	2380, 2381, 2399, 2414, 2415, 2433, 2444, 2445, 2463
<code>\@par</code>	1692
<code>\Abjad</code> ..	2901, 2909, 2910, 3349, 3350
<code>\Alph</code> ...	2393, 2427, 2457, 3167, 3170, 3345, 3350
<code>\DeclareMathDelimiter</code> ..	4357
<code>\DeclareMathSizes</code>	4348
<code>\@False</code>	154, 156
<code>\Kashida@onfalse</code>	1436
<code>\Kashida@ontrue</code>	1435
<code>\LTRfootnotetext</code>	1722
<code>\LTRmarginparreset</code>	2807
<code>\Latincitex</code> ..	73, 74, 1956, 1965, 2155, 2815, 2816
<code>\@M</code>	170, 2943, 3044, 3139
<code>\@Mi</code>	166
<code>\@Mii</code>	1615
<code>\@Miii</code>	1617
<code>\@RTL@footnotefalse</code> ..	2798, 2802, 3282
<code>\@RTL@footnotetrue</code> ..	2800, 2803, 3280
<code>\@RTLfalse</code> ..	136, 148, 161, 3235, 3242, 3264
<code>\@RTLfootnotetext</code>	1723
<code>\@RTLtabfalse</code>	3250
<code>\@RTLtabtrue</code>	3248
<code>\@RTLtrue</code>	3233, 3240, 3262
<code>\@Roman</code>	2395, 2429, 2459
<code>\@SepMark</code>	1551
<code>\@SetTab</code>	2469
<code>\@True</code>	149, 155
<code>\@X</code>	4517, 4518, 4596
<code>\@abjad</code> ...	3128, 3147, 3148, 3344, 3345
<code>\@acol</code>	1847, 1855
<code>\@acolampacol</code> ..	1845, 1847, 1853, 1855
<code>\@adadi</code> ..	2391, 2425, 2455, 2917, 2919, 2922
<code>\@addamp</code>	1846, 1854
<code>\@addtopreamble</code>	1814
<code>\@alph</code> ...	2394, 2428, 2458, 2470, 3166, 3169, 3344, 3349
<code>\@ampacol</code>	1845, 1853
<code>\@answernumberfont</code> ..	4539, 4540, 4578
<code>\@answerstitle</code>	4536, 4577
<code>\@answerstitlefont</code> ..	4537, 4538, 4577
<code>\@appendheader</code> ..	4550, 4551, 4553
<code>\@arrayclassz</code>	1845
<code>\@arraydesc</code> ..	4546, 4549, 4556, 4560
<code>\@arrayrule</code> ..	1793, 1794, 1795, 1837, 1838, 1839
<code>\@author</code>	3695, 3707
<code>\@autodottrue</code> 2383, 2384, 2385, 2386, 2387, 2388, 2389, 2390, 2391, 2392, 2393, 2394, 2395, 2396, 2397, 2417, 2418, 2419, 2420, 2421, 2422, 2423, 2424, 2425, 2426, 2427, 2428, 2429, 2430, 2431, 2447, 2448, 2449, 2450, 2451, 2452, 2453, 2454, 2455, 2456, 2457, 2458, 2459, 2460, 2461
<code>\@auxout</code>	2821, 3370, 3374
<code>\@begin@tempboxa</code>	1692
<code>\@biblabel</code>	1957, 1966
<code>\@bibsetup</code>	1958, 1967
<code>\@bidi@list@minipage@parbox@not@nobtrue</code>	1689, 1711

<code>\@bidi@list@minipage@parboxtrue</code>	<code>\@custommagazinenam</code>	3564, 3797
..... 1690, 1712	<code>\@customminilogo</code>	... 3796, 3810
<code>\@bidi@strip@v@xepersianversion</code>	<code>\@customwwwTxt</code>	3525, 3528, 3580
.. 2533, 2535, 2541, 2547	<code>\@date</code>	... 3698, 3708
<code>\@bidityftesidenote@LTRmarginfont</code>	<code>\@dgroup</code>	... 148
..... 86	<code>\@dmath</code>	... 136, 165
<code>\@bidityftesidenote@RTLmarginfont</code>	<code>\@doendpe</code>	... 2246
..... 88	<code>\@dseries</code>	... 161
<code>\@bsphack</code>	<code>\@eha</code>	... 4311, 4337
..... 1614	<code>\@empty</code>	... 151, 1609,
<code>\@capttype</code>	1969, 1979, 1982, 2068, 2071,	
.. 1602, 1665, 1912, 1922	2200, 2817, 2820, 3002, 3008,	
<code>\@ccclvi</code>	3011, 3014, 3119, 3706, 3707,	
..... 4291, 4297, 4321	3708, 3709	
<code>\@chapapp</code>	<code>\@emptytoks</code>	... 150
.. 30, 102, 113, 120, 132,	<code>\@enGroup</code>	... 1199
1274, 1286, 1557, 2347, 2354,	<code>\@enLabel</code>	.. 1190, 1191, 1192, 1193,
2361, 2369, 2410, 2440	1194, 1195, 1196, 1197	
<code>\@chclass</code>	<code>\@enOther</code>	... 1201
.. 1727, 1735, 1743, 1758,	<code>\@enSpace</code>	... 1198
1772, 1777, 1792, 1808, 1828,	<code>\@end@tempboxa</code>	... 1707
1836, 1866, 1889, 1903	<code>\@endpbox</code>	... 1821, 1822
<code>\@chnum</code>	<code>\@enhook</code>	... 1202
... 1729, 1730, 1731, 1732,	<code>\@enloop@</code>	... 1189
1733, 1734, 1744, 1751, 1765,	<code>\@entemp</code>	1190, 1191, 1192, 1193, 1194,
1778, 1785, 1801, 1814, 1830,	1195, 1196, 1197, 1198, 1199,	
1831, 1832, 1833, 1834, 1835,	1200	
1849, 1857, 1867, 1874, 1896	<code>\@enum@</code>	... 1200
<code>\@choices</code>	<code>\@extra@b@citeb</code>	... 1984, 1990, 1992, 2015,
4544, 4548, 4564, 4566	2046, 2073, 2079, 2081	
<code>\@cite</code>	<code>\@extrafootnotefeaturesfalse</code>	...
1944, 1951, 1963, 1979, 2068,	... 3302	
2818	<code>\@extrafootnotefeaturestrue</code>	...
<code>\@cite@ofmt</code>	... 3300	
..... 2826	<code>\@false</code>	... 4601, 4609, 4616
<code>\@citea</code>	<code>\@false@correction</code>	.. 4593, 4616
1984, 1998, 2012, 2021, 2022,	<code>\@false@nocorrection</code>	4591, 4609
2023, 2028, 2043, 2051, 2052,	<code>\@falsesymbol</code>	.. 4587, 4589, 4593
2053, 2087, 2103, 2121, 2817,	<code>\@firstampfalse</code>	... 1847, 1855
2819	<code>\@firstofone</code>	... 1371, 1372, 1982,
<code>\@citeb</code>	2071, 2820, 4294, 4318	
... 1980, 1982, 1984, 1987,	<code>\@firstoftwo</code>	.. 2536, 2542, 2548
1989, 1990, 1992, 2015, 2046,	<code>\@float@HH</code>	... 1908, 1909
2069, 2071, 2073, 2076, 2078,	<code>\@float@Hx</code>	... 1907, 1908
2079, 2081, 2818, 2820, 2821,	<code>\@float@</code>	... 1908, 1919
2822, 2825, 2826		
<code>\@citex</code>		
..... 1955, 1964		
<code>\@classx</code>		
..... 1811		
<code>\@classz</code>		
..... 1811		
<code>\@correction</code>		
..... 4617		
<code>\@correctionstyle</code>		
.. 4602, 4603,		
4604		
<code>\@ctrerr</code>		
..... 2908, 2913		
<code>\@currbox</code>		
.. 1622, 1668, 1672, 1911,		
1915, 1921, 1925		
<code>\@currenvir</code>		
.. 2229, 2231, 2232		
<code>\@customlogo</code>		
..... 3795, 3804		



<code>\@floatboxreset</code>	1678, 1917, 1927	<code>\@ifstar</code>	2148
<code>\@floatcapt</code>	1912, 1922	<code>\@ifundefined</code>	72, 1984, 1990, 2073, 2079, 2822
<code>\@floatpenalty</code>	1615, 1617, 1620	<code>\@ignoretrue</code>	172
<code>\@flstylefalse</code>	1914, 1924	<code>\@iiiminipage</code>	1708
<code>\@flstyletrue</code>	1914, 1924	<code>\@iiiparbox</code>	1686
<code>\@fltovf</code>	1670	<code>\@indexfile</code>	3310, 3322, 3334
<code>\@footnotetext</code>	1721	<code>\@initorcheck</code>	4543, 4563, 4581
<code>\@for</code>	1980, 2069, 2818	<code>\@inlabelfalse</code>	139
<code>\@formanswerline</code>	4573, 4582, 4595, 4599	<code>\@input@</code>	3312, 3324, 3336
<code>\@fps</code>	1603, 1604, 1606, 1609, 1626	<code>\@lastchclass</code>	1727, 1728, 1744, 1745, 1746, 1747, 1749, 1778, 1779, 1780, 1781, 1783, 1828, 1829, 1845, 1853, 1867, 1868, 1869, 1870, 1872
<code>\@fpsadddefault</code>	1607, 1610	<code>\@latex@error</code>	4309, 4335
<code>\@freelist</code>	1622	<code>\@latex@warning</code>	2824
<code>\@gobble</code>	1200, 1301, 1302, 1303, 2533	<code>\@latinAlpha</code>	3167, 3170
<code>\@harfi</code>	12, 20, 31, 34, 43, 49, 55, 61, 103, 114, 121, 133, 1264, 1275, 1287, 1393, 1558, 2348, 2355, 2362, 2370, 2377, 2390, 2411, 2424, 2441, 2454, 2911, 2914, 2915	<code>\@latinalph</code>	2470, 3166, 3169
<code>\@headerfont</code>	4515, 4516, 4521, 4551	<code>\@listdepth</code>	1724
<code>\@headerline</code>	4547, 4550, 4558, 4562	<code>\@m</code>	1961, 2819, 2942, 3043, 3137
<code>\@ifclassloaded</code>	3199, 3200, 3201, 3202, 3203, 3204, 3205, 3206, 3207, 3208, 3209, 3210, 3211, 3212, 3213, 3214, 3215, 3216, 3217, 3218, 3219, 3220, 3221, 3222, 3308, 3320, 3332	<code>\@mainmatterfalse</code>	97, 108, 126, 1268, 2404
<code>\@ifdefinable</code>	2264, 2266	<code>\@maskanswerline</code>	4574, 4583, 4596, 4600
<code>\@ifdefinitionfileloaded</code>	1599, 1742, 1775, 1865, 1906, 3181, 3182	<code>\@memfront</code>	1549
<code>\@ifnextchar</code>	1908, 2149, 2155, 2815	<code>\@minipagefalse</code>	2812
<code>\@ifnum</code>	2086, 2088, 2090, 2097, 2098, 2101, 2113, 2136, 2138	<code>\@minipagerestore</code>	1725
<code>\@ifpackageloaded</code>	76, 1473, 1477, 2158, 2162, 2254, 2262, 3183, 3184, 3185, 3186, 3187, 3188, 3189, 3190, 3191, 3192, 3193, 3194, 3195, 3196, 3197, 3198, 3199	<code>\@minipagetrue</code>	2811
		<code>\@mpLTrfootnotetext</code>	1722
		<code>\@mpRTLfootnotetext</code>	1723
		<code>\@mpargs</code>	1714
		<code>\@mpfn</code>	1720
		<code>\@mpfootnotetext</code>	1721
		<code>\@mplistdepth</code>	1724
		<code>\@namedef</code>	1938, 1992, 2081, 2245
		<code>\@one</code>	1632, 1638, 1731, 1732, 1735, 1744, 1754, 1755, 1759, 1778, 1788, 1789, 1793, 1794, 1795, 1832, 1833, 1837, 1838, 1839, 1867, 1877, 1878, 1890, 2086, 2098, 2100, 2113, 2121, 2862, 2929, 2970, 2977, 2989, 2994, 3030, 3071, 3078, 3090, 3095, 4301, 4306, 4325, 4332



<code>\@newlistfalse</code>	1294	<code>\@safe@activesfalse</code>	1983, 2072
<code>\@next</code>	1622	<code>\@safe@activetrue</code> .	1981, 2070
<code>\@nextchar</code> 1750, 1752, 1753, 1754,		<code>\@secondoftwo</code> .	2538, 2544, 2550
1755, 1756, 1757, 1759, 1760,		<code>\@setfontsize</code>	
1761, 1762, 1763, 1766, 1767,		.. 3495, 3501, 3503, 3506,	
1768, 1769, 1770, 1771, 1784,		3513, 3519, 3520, 3521, 3522,	
1786, 1787, 1788, 1789, 1790,		3523	
1791, 1793, 1794, 1795, 1796,		<code>\@setfpsbit</code> 1642, 1645, 1648, 1651,	
1797, 1798, 1799, 1802, 1803,		1654, 1657	
1804, 1805, 1806, 1807, 1819,		<code>\@setminipage</code>	1726
1821, 1822, 1873, 1875, 1876,		<code>\@setnobreak</code>	1917, 1927
1877, 1878, 1879, 1880, 1881,		<code>\@sharp</code> . . . 1850, 1851, 1852, 1858,	
1882, 1883, 1884, 1885, 1886,		1859, 1860	
1887, 1888, 1890, 1891, 1892,		<code>\@smemfront</code>	1550
1893, 1894, 1897, 1898, 1899,		<code>\@sptoken</code>	1198
1901, 1902		<code>\@startpbox</code>	1821, 1822
<code>\@nextchar</code>	1900	<code>\@starttoc</code> 2878, 4526, 4531	
<code>\@nil</code> . 2175, 2179, 2180, 2185, 2187,		<code>\@stop</code> 2381, 2415, 2445	
2960, 2963, 3061, 3064		<code>\@sx@xepersian@localize@verbatim</code>	
<code>\@nodocument</code>	1601 1938	
<code>\@nonlatinfalse</code> 2783, 3255		<code>\@tabclassz</code>	1853
<code>\@nonlatintrue</code> 2790, 3257		<code>\@tartibi</code> . . . 9, 16, 39, 45, 51, 57,	
<code>\@onelevel@sanitize</code> 1604		94, 105, 116, 128, 1260, 1270,	
<code>\@outputbox</code>	1311	1282, 1390, 1552, 1553, 2343,	
<code>\@outputpage</code>	1289	2350, 2357, 2365, 2373, 2392,	
<code>\@parboxrestore</code> 1294, 1677, 1692,		2406, 2426, 2436, 2456, 3023,	
1719, 1916, 1926		3025, 3028	
<code>\@parboxto</code>	1695, 1704	<code>\@tempa</code> 1190, 1191, 1192,	
<code>\@parmoderr</code>	1620	1193, 1194, 1195, 1196, 1197,	
<code>\@pboxswfalse</code>	1688, 1710	1198, 1199, 1200, 1201, 1204,	
<code>\@pboxswtrue</code>	1702	2185, 2187, 2270, 2271, 2272,	
<code>\@ppsavesec</code>	25	2273, 2274, 2275, 2276, 2277,	
<code>\@preamble</code>	1848, 1856	2278, 2279, 2280	
<code>\@preamblecmds</code>	4362	<code>\@tempboxa</code>	1715
<code>\@preamerr</code> 1738, 1772, 1808, 1842,		<code>\@tempc</code> . . 2200, 2213, 2223, 2225,	
1903		2226, 2229, 2237	
<code>\@questionheader</code> . . . 4573, 4574,		<code>\@tempcnta</code>	1624,
4605		1630, 1632, 1636, 1638, 1660,	
<code>\@questionsepspace</code> . 4629, 4634,		1661, 1667, 1668, 1812, 2095,	
4640		2096, 2097, 2100, 2101	
<code>\@questiontitle</code> 4622, 4635		<code>\@tempcntb</code> 1665, 1666, 1667	
<code>\@questiontitlefont</code> 4623, 4624,		<code>\@tempdima</code> . 1691, 1692, 1713, 1717	
4635		<code>\@tempdimb</code>	1694, 1695
<code>\@resetactivechars</code>	1292	<code>\@tempswafalse</code>	2113, 2815
<code>\@resetspp</code> 24, 1377, 1378		<code>\@tempswatru</code>	2112, 2815
<code>\@roman</code>	2396, 2430, 2460	<code>\@temptokena</code> . . . 2186, 2193, 2198,	



2204, 2211, 2221, 2235
 \@testpach 1727, 1743, 1777, 1828,
 1866
 \@tfor 1625, 2270
 \@thanks 3700, 3706
 \@the@choice 4552, 4553
 \@themargin 1307
 \@title 3688, 3709
 \@true 4597, 4608, 4615
 \@true@correction .. 4592, 4615
 \@true@nocorrection 4590, 4608
 \@truesymbol .. 4586, 4588, 4592
 \@verbatim 1935, 1938, 2243, 2245,
 2256
 \@vobeyspaces 1935, 2243
 \@warning 2242
 \@x@xepersian@localize@verbatim
 1935
 \@xDeclareMathDelimiter . 4357
 \@xepersian@@computeautoilgfalse
 3364
 \@xepersian@@computeautoilgtrue
 3362
 \@xepersian@info .. 2508, 2530,
 2532
 \@xfloat 1600, 1907, 1908
 \@xxDeclareMathDelimiter 4356
 \@xxxii 1666
 @\ 1579, 1580
 @\ 1575, 1576, 1578
 @\ 2157
]\ 2165
 \ 1932, 2165, 3656, 3971, 3972, 4234,
 4237, 4286, 4519, 4558, 4562,
 4582, 4583
 \{ 1931, 2165
 \} 1931, 2165
 \] 2165
 \^ 2166
 \| 3972
 \~ 2166
 _ 1332, 1334, 2819, 2966, 2972, 2991,
 2997, 3067, 3073, 3092, 3102,
 3571, 3580

A

\abj@num@i 3133, 3150, 3157
 \abj@num@ii ... 3135, 3154, 3161
 \abj@num@iii ... 3137, 3158, 3164
 \abj@num@iv 3139, 3162
 \Abjad 2909
 \abjad 3147
 \abjad@zero 3149, 3153
 \Abjadnumeral 2910
 \abjadnumeral 3148
 \abovedisplayshortskip .. 3498,
 3499, 3509, 3510, 3516, 3517
 \abovedisplayskip .. 3496, 3497,
 3507, 3508, 3514, 3515
 \abstractname 2890
 \active 2166, 4466
 \adadi 1191, 2384, 2418, 2448, 2916
 \adadinumeral 2922
 \addfontfeatures .. 136, 148, 161
 \addtocontents
 .. 4525, 4528, 4530, 4533,
 4555, 4559, 4582, 4583
 \addtolength .. 3723, 3724, 3727,
 4146, 4147, 4148, 4149, 4213
 \addtoversion 4349
 \adl@argarraydashrule 1795, 1839
 \adl@arraydashrule . 1794, 1838
 \adl@arrayrule 1793, 1837
 \adl@box 1819, 1821, 1822
 \adl@class@iiiorvii 1825, 1862
 \adl@class@start ... 1824, 1861
 \adl@endmbox 1820
 \adl@putlrc 1816, 1817, 1818, 1850,
 1851, 1852, 1858, 1859, 1860
 \adl@startmbox 1819
 \advance 1335, 1632, 1638,
 1661, 1667, 2100, 2862, 2864,
 3487, 3491, 3759, 3762, 4306,
 4332, 4677, 4712, 4716, 4722,
 4726, 4731, 4734, 4735, 4739,
 4743, 4744, 4746, 4747, 4749,
 4769, 4773, 4774, 4777, 4782,
 4783, 4787, 4788, 4790, 4791,
 4793, 4796, 4798
 \aftergroup 1296, 1298
 \ALG@name 5, 7



<code>\algorithmicensure</code>	3	<code>\author</code>	3711
<code>\algorithmicrequire</code>	2	<code>\authorandplace</code>	4184
<code>\ALGS@name</code>	6, 7	<code>\autofootnoterule</code>	3268
<code>\aliasfontfeature</code>	1489, 1490, 1491, 1492, 1493, 1494, 1495, 1496, 1497, 1498, 1499, 1500, 1501, 1502, 1503, 1504, 1505, 1506, 1507, 1508, 1509, 1510, 1511, 1512, 1513, 1514, 1515, 1516, 1517, 1518, 1519, 1520, 1521, 1522, 1523, 1524, 1525, 1526, 1527, 1528, 1529, 1530, 1531, 1532, 1533, 1534, 1535, 1536, 1537, 1538, 1539, 1540, 1541	<code>\AutoMathsDigits</code>	3225, 4499, 4503
<code>\aliasfontfeatureoption</code>	1542, 1543, 1544, 1545, 1546, 1547	B	
<code>\alloc@</code>	4291	<code>\backrefpagesname</code>	63
<code>\Alph</code>	1193, 1364, 1365, 2386, 2420, 2450	<code>\baselineskip</code>	1304, 2865, 2868, 3401, 3403, 3405, 3408, 3409, 3411
<code>\alph</code>	1194, 2387, 2421, 2451, 2477, 4552, 4578	<code>\begin</code>	2159, 2160, 2802, 2803, 2876, 3539, 3542, 3595, 3610, 3623, 3629, 3650, 3681, 3687, 3694, 3718, 3772, 3778, 3850, 3853, 3858, 3865, 3880, 3895, 3912, 3946, 3964, 3969, 3989, 3996, 3997, 4018, 4020, 4021, 4043, 4048, 4049, 4085, 4086, 4094, 4120, 4128, 4134, 4135, 4143, 4173, 4197, 4229, 4230, 4245, 4257, 4271, 4556, 4560, 4571, 4572, 4578, 4633
<code>\alpha@elt</code>	4350	<code>\begingroup</code>	144, 1290, 1930, 2147, 2163, 2243, 2245, 2555, 2557, 4298, 4322, 4466
<code>\alpha@list</code>	4350	<code>\beginL</code>	2812, 3571, 3972
<code>\anappendixtrue</code>	1559	<code>\beginR</code>	3575, 3576, 3577, 3588, 3589, 3590, 3795, 3796, 3797, 3815, 3836, 3837, 3838, 3839, 3840, 3841, 3992, 4087
<code>\and</code>	3713	<code>\belowdisplayshortskip</code>	3499, 3510, 3517
<code>\answernumberfont</code>	4540	<code>\belowdisplayskip</code>	3497, 3508, 3515
<code>\answerstitle</code>	4536, 4606	<code>\bfseries</code>	1985, 2074, 2822, 3531, 3537, 3556, 3564, 3592, 3608, 3627, 3641, 3645, 3670, 3675, 3679, 3804, 3810, 4515, 4537, 4539, 4623
<code>\answerstitlefont</code>	4538	<code>\bgroup</code>	1199, 1675, 1715, 1916, 1926, 4294, 4318
<code>\appendix</code>	10, 17, 40, 46, 52, 58, 99, 110, 117, 129, 1261, 1271, 1283, 1361, 1362, 1391, 1554, 2344, 2351, 2358, 2366, 2374, 2407, 2437	<code>\bibname</code>	2894
<code>\appendixautorefname</code>	1350	<code>\bidi@footnotetext@font</code>	1319
<code>\appendixname</code>	11, 19, 30, 102, 113, 120, 132, 1274, 1286, 1392, 1557, 2347, 2354, 2361, 2369, 2410, 2440, 2887	<code>\bidi@LTRfootnotetext@font</code>	1321
<code>\arabic</code>	1197		
<code>\arrayrulewidth</code>	4228		
<code>\articlesep</code>	4210		
<code>\AtBeginDocument</code>	71, 1360, 1448, 1938, 2145, 2250, 3485, 3489		
<code>\AtEndOfClass</code>	3483		



<code>\cleardoubleoddpaper</code>	2403	<code>\decimalseparator</code> . .	4437, 4493
<code>\cleardoublepage</code> 15, 96, 107, 125,		<code>\DeclareDocumentCommand</code>	
1267		2583, 2600, 2619, 2633,
<code>\clearpage</code>	2403, 3832		2678, 2695, 2712, 2729, 2746,
<code>\closeout</code>	3310, 3322, 3334		2763, 4416, 4444, 4453
<code>\color@begingroup</code>	1716	<code>\DeclareMathAccent</code>	4355
<code>\color@vbox</code>	1673, 1915, 1925	<code>\DeclareMathAlphabet</code>	4354
<code>\columnlines</code>	3428, 3429, 3461,	<code>\DeclareMathDelimiter</code>	4356
3790		<code>\DeclareMathRadical</code>	4358
<code>\columnsep</code>	3724, 4147	<code>\DeclareMathSizes</code>	4347
<code>\columnseprule</code>	3790	<code>\DeclareMathSymbol</code>	4355
<code>\columnstitle</code>	4141	<code>\DeclareMathVersion</code>	4349
<code>\columnwidth</code>	1676, 1718, 1916,	<code>\DeclareOption</code>	
1926, 3723, 4146		3450, 3451, 3452, 3453,
<code>\comment</code>	4610		3455, 3457, 3459, 3460, 3461,
<code>\contentsname</code>	2876, 2884		3462, 3463, 4607, 4614
<code>\copyright</code>	3580	<code>\DeclareOptionX</code>	3353
<code>\correction</code>	4610, 4617	<code>\DeclareRobustCommand</code>	
<code>\correctionstyle</code>	4603	2146, 2587, 2603, 2624,
<code>\count</code>	1668, 3758, 3759, 3761,		2638, 2653, 2656, 2659, 2662,
3762, 3771, 3777			2665, 2668, 2682, 2699, 2716,
<code>\count@</code>	1812		2733, 2750, 2767, 2814
<code>\cs</code> 2253, 2255, 2621, 2626, 2635,		<code>\DeclareSymbolFont</code>	4352,
2640, 4371, 4372, 4373, 4374,			4421, 4422, 4423, 4424, 4447,
4375			4456
<code>\csname</code> 1472, 1665, 1705, 1910, 1913,		<code>\DeclareSymbolFontAlphabet</code> . .	
1920, 1923, 1940, 2247, 2264,		4359
2265, 2266, 2267, 2268, 2378,		<code>\DeclareSymbolFontAlphabet@</code> .	
2412, 2442, 2556, 2559, 2565,		4359
2567, 2826, 2909, 2914, 2917,		<code>\DeclareTextFontCommand</code>	
3023, 3147, 4297, 4300, 4305,		2671, 2672, 2673, 2674,
4306, 4321, 4324, 4328, 4329,			2675, 2676
4332, 4367, 4369, 4774, 4783,		<code>\def</code>	2, 3, 5, 6, 7, 10, 12,
4793			15, 17, 20, 63, 64, 77, 92, 136,
<code>\currenttime</code>	3554		148, 161, 168, 172, 1189, 1190,
<code>\customlogo</code>	3795		1191, 1192, 1193, 1194, 1195,
<code>\custommagazinenam</code>	3797		1196, 1197, 1289, 1327, 1329,
<code>\customminilogo</code>	3796		1331, 1333, 1344, 1345, 1346,
<code>\customwwwTxt</code>	3525		1347, 1348, 1349, 1350, 1351,
			1352, 1353, 1354, 1355, 1356,
			1357, 1358, 1359, 1362, 1373,
			1378, 1391, 1393, 1404, 1407,
			1409, 1410, 1415, 1439, 1440,
			1562, 1563, 1564, 1565, 1566,
			1567, 1568, 1569, 1570, 1600,
			1602, 1603, 1605, 1686, 1708,

D

<code>\dollarbegin</code>	1816, 1817, 1818
<code>\dollarend</code>	1816, 1817, 1818
<code>\date</code>	3553, 3564, 3712, 4181
<code>\datename</code>	2892
<code>\day</code>	4672



1714, 1720, 1727, 1743, 1777,
 1811, 1824, 1825, 1828, 1845,
 1853, 1861, 1862, 1866, 1908,
 1909, 1912, 1919, 1922, 1935,
 1936, 1945, 1948, 1960, 1961,
 1971, 1974, 1987, 2002, 2032,
 2064, 2068, 2093, 2155, 2169,
 2173, 2175, 2176, 2179, 2185,
 2187, 2189, 2205, 2208, 2224,
 2225, 2228, 2241, 2243, 2246,
 2263, 2500, 2501, 2552, 2553,
 2554, 2560, 2561, 2565, 2782,
 2789, 2798, 2799, 2800, 2801,
 2805, 2806, 2807, 2816, 2819,
 2882, 2883, 2884, 2885, 2886,
 2887, 2888, 2889, 2890, 2891,
 2892, 2893, 2894, 2895, 2896,
 2897, 2898, 2899, 2900, 2901,
 2909, 2911, 2914, 2923, 2928,
 2937, 2963, 2976, 2987, 3001,
 3007, 3010, 3013, 3017, 3029,
 3038, 3064, 3077, 3088, 3106,
 3111, 3118, 3128, 3147, 3149,
 3150, 3154, 3158, 3162, 3168,
 3343, 3348, 3369, 3373, 3525,
 3795, 3796, 3797, 4291, 4293,
 4317, 4425, 4448, 4457, 4467,
 4468, 4493, 4494, 4495, 4499,
 4515, 4517, 4519, 4537, 4539,
 4543, 4550, 4586, 4587, 4590,
 4591, 4592, 4593, 4602, 4605,
 4612, 4613, 4619, 4620, 4623,
 4807
 \def@NAT@last@yr ... 2103, 2105
 \defaultfontfeatures 3354
 \DefaultMathsDigits 3227, 4494
 \define@choicekey
 .. 3223, 3231, 3238, 3246,
 3253, 3260, 3266, 3278, 3284,
 3290, 3294, 3298, 3304, 3317,
 3329, 3341, 3360, 3367
 \define@key 2269
 \define@mathalphabet 4349
 \define@mathgroup 4349
 \deflatinfont 2633
 \defpersianfont 2619
 \depth 2277, 2278
 \dimexpr 2868
 \ding 4586, 4587
 \display@setup 137, 162
 \divide .. 3764, 3765, 4674, 4682,
 4687, 4714, 4720, 4728, 4730,
 4733, 4737, 4741, 4745
 \do . 1627, 1980, 2069, 2270, 2818,
 4362
 \document 4505
 \document@select@group .. 4317
 \dorestore@version 4351
 \dosetclass ... 1408, 1409, 1413
 \doublebox 4103, 4156
 \dquad 170, 172
 \dseries@display@setup ... 162

 E
 \edef 1695,
 1750, 1784, 1848, 1856, 1873,
 1982, 2071, 2231, 2508, 2531,
 2533, 2559, 2562, 2820, 4552
 \edition 3822
 \editionFormat 3531, 3534
 \editorialAuthorFormat .. 3674,
 4238
 \editorialTitleFormat ... 3672,
 3673
 \else 2, 3, 5, 7, 32, 63, 92, 140, 170,
 1190, 1191, 1192, 1193, 1194,
 1195, 1196, 1197, 1198, 1199,
 1200, 1278, 1319, 1330, 1332,
 1334, 1344, 1345, 1346, 1347,
 1348, 1349, 1350, 1351, 1352,
 1353, 1354, 1355, 1356, 1357,
 1358, 1359, 1412, 1439, 1440,
 1449, 1452, 1455, 1458, 1461,
 1464, 1562, 1563, 1564, 1565,
 1566, 1567, 1568, 1569, 1570,
 1608, 1616, 1621, 1631, 1637,
 1690, 1693, 1698, 1699, 1700,
 1701, 1702, 1712, 1727, 1728,
 1729, 1730, 1731, 1732, 1733,
 1734, 1735, 1736, 1737, 1738,
 1744, 1745, 1746, 1748, 1749,
 1752, 1753, 1754, 1755, 1756,



1757, 1759, 1760, 1761, 1762,	4498, 4500, 4501, 4502, 4680,
1763, 1766, 1767, 1768, 1769,	4684, 4689, 4690, 4697, 4718,
1770, 1771, 1778, 1779, 1780,	4723, 4753, 4789, 4797
1782, 1783, 1786, 1787, 1788,	\empty 1411
1789, 1790, 1791, 1793, 1794,	\enclname 2897
1795, 1796, 1797, 1798, 1799,	\encodingdefault 2595,
1802, 1803, 1804, 1805, 1806,	2611, 2690, 2707, 2724, 2741,
1807, 1827, 1828, 1829, 1830,	2758, 2775
1831, 1832, 1833, 1834, 1835,	\end 1408, 1409, 1414,
1837, 1838, 1839, 1840, 1841,	1415, 2159, 2160, 2231, 2242,
1842, 1867, 1868, 1869, 1871,	2802, 2803, 2879, 3539, 3544,
1872, 1875, 1876, 1877, 1878,	3601, 3615, 3625, 3634, 3657,
1879, 1880, 1881, 1882, 1883,	3696, 3699, 3702, 3719, 3774,
1884, 1885, 1886, 1887, 1888,	3780, 3857, 3863, 3867, 3893,
1890, 1891, 1892, 1893, 1894,	3899, 3933, 3953, 3968, 3974,
1897, 1898, 1899, 1900, 1901,	4010, 4011, 4012, 4035, 4036,
1902, 1914, 1924, 1949, 1962,	4037, 4061, 4062, 4063, 4088,
1994, 1999, 2008, 2011, 2025,	4089, 4092, 4122, 4126, 4137,
2029, 2038, 2042, 2045, 2057,	4138, 4175, 4179, 4208, 4239,
2061, 2062, 2083, 2104, 2118,	4240, 4254, 4266, 4279, 4525,
2120, 2123, 2137, 2139, 2150,	4528, 4530, 4533, 4579, 4580,
2173, 2184, 2197, 2199, 2202,	4584, 4638
2217, 2219, 2225, 2233, 2241,	\end@correction 4618
2268, 2271, 2272, 2273, 2274,	\endcomment 4611
2275, 2276, 2277, 2278, 2279,	\endcorrection 4611, 4618
2382, 2403, 2416, 2446, 2473,	\endcsname 1472, 1665,
2489, 2490, 2491, 2492, 2493,	1705, 1910, 1913,
2494, 2495, 2496, 2497, 2498,	1920, 1923, 1940, 2247, 2264,
2537, 2543, 2549, 2576, 2828,	2265, 2266, 2267, 2268, 2378,
2843, 2854, 2882, 2883, 2884,	2412, 2442, 2556, 2559, 2565,
2885, 2886, 2887, 2888, 2889,	2567, 2826, 2909, 2914, 2917,
2890, 2891, 2892, 2893, 2894,	3023, 3147, 4297, 4300, 4305,
2895, 2896, 2897, 2898, 2899,	4306, 4321, 4324, 4328, 4330,
2900, 2908, 2913, 2931, 2933,	4332, 4367, 4369, 4774, 4783,
2941, 2942, 2943, 2944, 2945,	4794
2946, 2947, 2948, 2966, 2981,	\endgroup 1297, 2168, 2246, 2555,
2995, 3008, 3011, 3032, 3034,	2563, 4302, 4326, 4469, 4470,
3042, 3043, 3044, 3045, 3046,	4471, 4472, 4473, 4474, 4475,
3047, 3048, 3049, 3067, 3082,	4476, 4477, 4478, 4479, 4480
3095, 3096, 3099, 3130, 3132,	\endL 3571, 3972
3134, 3136, 3138, 3313, 3325,	\endlatin 2799
3337, 3410, 3741, 4219, 4294,	\endLTR 2799
4307, 4313, 4318, 4333, 4339,	\endMakeFramed 1338
4461, 4469, 4470, 4471, 4472,	\endmath 167
4473, 4474, 4475, 4476, 4477,	\endpersian 2801
4478, 4479, 4493, 4496, 4497,	\endquestion 4631



<code>\endR</code>	3575, 3576, 3577, 3588, 3589, 3590, 3795, 3796, 3797, 3815, 3836, 3837, 3838, 3839, 3840, 3841, 3992, 4087	354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630,
<code>\endRTL</code>	2801	
<code>\ends@math</code>	167	
<code>\endtrivlist</code>	1936, 2246	
<code>\end</code>	1936, 1940, 2246, 2247	
<code>\eq@addpunct</code>	172	
<code>\eq@group</code>	140, 149	
<code>\eq@GRP@first@dmath</code>	149	
<code>\eq@prelim</code>	140, 157	
<code>\eq@setnumber</code>	143	
<code>\eq@setup@a</code>	145	
<code>\eq@startup</code>	146	
<code>\eq@wdCond</code>	164	
<code>\eqcommand</code>	176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 255, 256, 257, 258, 259, 260, 261, 262, 263, 264, 265, 266, 267, 268, 269, 270, 271, 272, 273, 274, 275, 276, 277, 278, 279, 280, 281, 282, 283, 284, 285, 286, 287, 288, 289, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353,	



631, 632, 633, 634, 635, 636,
637, 638, 639, 640, 641, 642,
643, 644, 645, 646, 647, 648,
649, 650, 651, 652, 653, 654,
655, 656, 657, 658, 659, 660,
661, 662, 663, 664, 665, 666,
667, 668, 669, 670, 671, 672,
673, 674, 675, 676, 677, 678,
679, 680, 681, 682, 683, 684,
685, 686, 687, 688, 689, 690,
691, 692, 693, 694, 695, 696,
697, 698, 699, 700, 701, 702,
703, 704, 705, 706, 707, 708,
709, 710, 711, 712, 713, 714,
715, 716, 717, 718, 719, 720,
721, 722, 723, 724, 725, 726,
727, 728, 729, 730, 731, 732,
733, 734, 735, 736, 737, 738,
739, 740, 741, 742, 743, 744,
745, 746, 747, 748, 749, 750,
751, 752, 753, 754, 755, 756,
757, 758, 759, 760, 761, 762,
763, 764, 765, 766, 767, 768,
769, 770, 771, 772, 773, 774,
775, 776, 777, 778, 779, 780,
781, 782, 783, 784, 785, 786,
788, 789, 790, 791, 792, 793,
794, 795, 796, 797, 798, 799,
800, 801, 802, 803, 804, 805,
806, 807, 808, 809, 810, 811,
812, 813, 814, 815, 816, 817,
818, 819, 820, 821, 822, 823,
824, 825, 826, 827, 828, 829,
830, 831, 832, 833, 834, 835,
836, 837, 838, 839, 840, 841,
842, 843, 844, 845, 846, 847,
848, 849, 850, 851, 852, 853,
854, 855, 856, 857, 858, 859,
860, 861, 862, 863, 864, 865,
866, 867, 868, 869, 870, 871,
872, 873, 874, 875, 876, 877,
878, 879, 880, 881, 882, 883,
884, 885, 886, 887, 888, 889,
890, 891, 892, 893, 894, 895,
896, 897, 898, 899, 900, 901,
902, 903, 904, 905, 906, 907,

908, 909, 910, 911, 912, 913,
914, 915, 916, 917, 918, 919,
920, 921, 922, 923, 924, 925,
926, 927, 928, 929, 930, 931,
932, 933, 934, 935, 936, 937,
938, 939, 940, 941, 942, 943,
944, 945, 946, 947, 948, 949,
950, 951, 952, 953, 954, 955,
956, 957, 958, 959, 960, 961,
962, 963, 964, 965, 966, 967,
968, 969, 970, 971, 972, 973,
974, 975, 976, 977, 978, 979,
980, 981, 982, 983, 984, 985,
986, 987, 988, 989, 990, 991,
992, 993, 994, 995, 996, 997,
998, 999, 1000, 1001, 1002,
1003, 1004, 1005, 1006, 1007,
1008, 1009, 1010, 1011, 1012,
1013, 1014, 1015, 1016, 1017,
1018, 1019, 1020, 1021, 1022,
1023, 1024, 1025, 1026, 1027,
1028, 1029, 1030, 1031, 1032,
1033, 1034, 1035, 1036, 1037,
1038, 1039, 1040, 1041, 1042,
1043, 1044, 1045, 1046, 1047,
1048, 1049, 1050, 1051, 1052,
1053, 1054, 1055, 1056, 1057,
1058, 1059, 1060, 1061, 1062,
1063, 1064, 1065, 1066, 1067,
1068, 1069, 1070, 1071, 1072,
1073, 1074, 1075, 1076, 1077,
1078, 1079, 1080, 1081, 1082,
1083, 1084, 1085, 1086, 1087,
1088, 1089, 1090, 1091, 1092,
1093, 1094, 1095, 1096, 1097,
1098, 1099, 1100, 1101, 1102,
1103, 1104, 1105, 1106, 1107,
1108, 1109, 1110, 1111, 1112,
1113, 1114, 1115, 1116, 1117,
1118, 1129, 1130, 1131, 1132,
1133, 1134, 1135, 1136, 1137,
1138, 1139, 1140, 1141, 1142,
1143, 1144, 1145, 1146, 1147,
1148, 1149, 1150, 1151, 1152,
1153, 1154, 1155, 1156, 1157,
1158, 1159, 1160, 1161, 1162,



1163, 1164, 1165, 1166, 1167,
 1168, 1169, 1170, 1171, 1172,
 1173, 1174, 1175, 1176, 1177,
 1178, 1179, 1180, 1181, 1182,
 1183, 1184, 1185, 1186, 1187,
 1471
 \backslash eqenvironment 1206,
 1207, 1208, 1209, 1210, 1211,
 1212, 1213, 1214, 1215, 1216,
 1217, 1218, 1219, 1220, 1221,
 1222, 1223, 1224, 1225, 1226,
 1227, 1228, 1229, 1230, 1231,
 1232, 1233, 1234, 1235, 1236,
 1237, 1238, 1239, 1240, 1241,
 1242, 1243, 1244, 1245, 1246,
 1247, 1249, 1250, 1251, 1252,
 1253, 1254, 1255, 1256, 1257,
 1258, 1472
 \backslash eqstyle 142
 \backslash equal 3770, 3925,
 4097, 4102, 4107, 4112, 4117,
 4150, 4155, 4160, 4165, 4170
 \backslash equationautorefname 1344
 \backslash escapechar 2558, 4299, 4323
 \backslash everydisplay 137, 4505
 \backslash everyjob 2531, 2532
 \backslash everymath 4504
 \backslash everypar 2812
 \backslash ExecuteOptions 4621
 \backslash ExecuteOptionsX 3382
 \backslash exp 2587, 2589, 2590, 2591, 2603,
 2605, 2606, 2607, 2624, 2626,
 2627, 2628, 2638, 2640, 2641,
 2642, 2682, 2684, 2685, 2686,
 2699, 2701, 2702, 2703, 2716,
 2718, 2719, 2720, 2733, 2735,
 2736, 2737, 2750, 2752, 2753,
 2754, 2767, 2769, 2770, 2771
 \backslash expandafter
 137, 1408, 1414, 1625, 1626,
 1750, 1784, 1873, 1910, 1913,
 1920, 1923, 1940, 1982, 2071,
 2187, 2192, 2193, 2198, 2203,
 2204, 2210, 2211, 2212, 2213,
 2220, 2221, 2222, 2223, 2225,
 2234, 2235, 2236, 2237, 2247,
 2264, 2265, 2266, 2267, 2533,
 2536, 2538, 2542, 2544, 2548,
 2550, 2555, 2556, 2559, 2562,
 2563, 2565, 2566, 2820, 2909,
 2914, 2917, 2932, 2938, 3023,
 3033, 3039, 3133, 3135, 3137,
 3139, 3147, 4294, 4313, 4318,
 4327, 4328, 4329, 4339, 4504,
 4505, 4553
 \backslash expandedtitle 4091
 \backslash ExplSyntaxOff 1939, 2261, 2781,
 4364, 4460
 \backslash ExplSyntaxOn 1937, 2249, 2581,
 4343, 4370
 \backslash extract@alph@from@version . .
 4327
 F
 \backslash f@baselineskip 2787, 2794, 3401,
 3403
 \backslash f@size 2787, 2794
 \backslash f@ur 1405, 2834, 2850, 2851, 2852,
 2855, 2856, 2857
 \backslash false 4598
 \backslash falsesymbol 4589
 \backslash familydefault
 2594, 2610, 2689, 2706,
 2723, 2740, 2757, 2774
 \backslash fancyfoot 3835, 3839, 3840, 3841
 \backslash fancyhead 3834, 3836, 3837, 3838
 \backslash FancyVerbLineautorefname 1357
 \backslash fbox 3719, 3734, 3949, 4575, 4635
 \backslash fboxrule 1327, 1329, 1331, 1333,
 3791
 \backslash fboxsep 1327, 1329,
 1331, 1333, 3722, 3915, 3947,
 4019, 4047, 4095, 4144
 \backslash fi 2, 3, 5, 7,
 35, 63, 68, 92, 136, 138, 139,
 140, 148, 159, 161, 170, 1203,
 1278, 1319, 1330, 1332, 1334,
 1344, 1345, 1346, 1347, 1348,
 1349, 1350, 1351, 1352, 1353,
 1354, 1355, 1356, 1357, 1358,
 1359, 1405, 1413, 1439, 1440,
 1451, 1454, 1457, 1460, 1463,



1466, 1562, 1563, 1564, 1565,
1566, 1567, 1568, 1569, 1570,
1611, 1612, 1618, 1633, 1634,
1639, 1640, 1643, 1646, 1649,
1652, 1655, 1658, 1662, 1663,
1671, 1689, 1690, 1696, 1703,
1706, 1711, 1712, 1731, 1732,
1733, 1734, 1738, 1739, 1740,
1754, 1755, 1756, 1757, 1772,
1773, 1788, 1789, 1790, 1791,
1808, 1809, 1823, 1832, 1833,
1834, 1835, 1842, 1843, 1847,
1852, 1855, 1860, 1863, 1877,
1878, 1879, 1880, 1903, 1904,
1914, 1924, 1936, 1954, 1972,
1993, 1995, 2006, 2010, 2019,
2020, 2024, 2036, 2041, 2045,
2049, 2050, 2054, 2059, 2060,
2061, 2062, 2082, 2084, 2106,
2114, 2122, 2123, 2132, 2133,
2139, 2142, 2152, 2173, 2188,
2206, 2226, 2239, 2242, 2268,
2280, 2383, 2384, 2385, 2386,
2387, 2388, 2389, 2390, 2391,
2392, 2393, 2394, 2395, 2396,
2397, 2398, 2403, 2417, 2418,
2419, 2420, 2421, 2422, 2423,
2424, 2425, 2426, 2427, 2428,
2429, 2430, 2431, 2432, 2447,
2448, 2449, 2450, 2451, 2452,
2453, 2454, 2455, 2456, 2457,
2458, 2459, 2460, 2461, 2462,
2475, 2489, 2490, 2491, 2492,
2493, 2494, 2495, 2496, 2497,
2498, 2539, 2545, 2551, 2569,
2570, 2578, 2821, 2828, 2842,
2847, 2848, 2849, 2853, 2858,
2859, 2860, 2861, 2870, 2882,
2883, 2884, 2885, 2886, 2887,
2888, 2889, 2890, 2891, 2892,
2893, 2894, 2895, 2896, 2897,
2898, 2899, 2900, 2908, 2913,
2935, 2949, 2961, 2966, 2967,
2970, 2972, 2973, 2985, 2989,
2991, 2992, 2994, 2997, 2999,
3005, 3008, 3011, 3015, 3020,
3036, 3050, 3062, 3067, 3068,
3071, 3073, 3074, 3086, 3090,
3092, 3093, 3095, 3101, 3102,
3104, 3109, 3116, 3122, 3140,
3141, 3142, 3143, 3144, 3145,
3152, 3153, 3156, 3157, 3160,
3161, 3163, 3164, 3175, 3230,
3236, 3243, 3251, 3258, 3265,
3277, 3283, 3289, 3293, 3297,
3303, 3315, 3316, 3327, 3328,
3339, 3340, 3352, 3365, 3379,
3397, 3412, 3413, 3415, 3744,
3745, 3950, 3967, 4131, 4205,
4224, 4251, 4276, 4294, 4312,
4313, 4318, 4338, 4339, 4463,
4481, 4482, 4483, 4484, 4485,
4486, 4487, 4488, 4489, 4490,
4491, 4493, 4496, 4497, 4498,
4500, 4501, 4502, 4689, 4691,
4692, 4693, 4699, 4723, 4724,
4744, 4755, 4776, 4785, 4792,
4799, 4814
\figureautorefname 1347
\figurename 2882
\finishsetclass 1411, 1415
\firstarticle 3846, 3870, 3871,
3873
\FirstFrameCommand 1329
\firstimage 3943, 3956, 3957,
3959
\firstmark 1316
\firstTextFormat 3604, 3606
\firstTitleFormat 3592, 3598,
3599
\float@box 1911, 1921
\float@endH 1910, 1920
\flushright 3592, 3611, 3630
\font 2838
\fontencoding 2589, 2605, 2627,
2641, 2684, 2701, 2718, 2735,
2752, 2769
\fontfamily
. 2590, 2606, 2626, 2640,
2655, 2658, 2661, 2664, 2667,
2670, 2685, 2702, 2719, 2736,
2753, 2770



`\fontsize` 2787, 2794
`\fontspec` 1938, 2256, 2585, 2602,
 2621, 2635, 2680, 2697, 2714,
 2731, 2748, 2765, 4419, 4446,
 4455
`\foot` 3587
`\footdir@debugfalse` 3288
`\footdir@debugtrue` 3286
`\footnote` 3684
`\footnoteautorefname` 1345
`\footnoterule` 3683
`\footnotesep` 3409, 3411
`\footnotesize` 84, 86, 88,
 1278, 1279, 1280, 1319, 1321,
 1323, 3512, 3513, 3547, 3580,
 3645, 3669, 3670, 3682
`\foottextfont` 1278
`\FrameCommand` 1327
`\FrameRestore` 1335
`\frenchspacing` 1935, 2243
`\frontmatter` 15, 95, 106, 124, 1266,
 2402
`\futurelet` 2178, 4466

G

`\g` . 2585, 2586, 2590, 2602, 2606,
 2680, 2681, 2685, 2697, 2698,
 2702, 2714, 2715, 2719, 2731,
 2732, 2736, 2748, 2749, 2753,
 2765, 2766, 2770, 4344, 4419,
 4421, 4422, 4423, 4424, 4446,
 4447, 4455, 4456
`\g@addto@macro` 4505, 4550
`\G@refundefinedtrue` 2823
`\gdef` 43, 49, 55, 61,
 102, 103, 113, 114, 120, 121,
 132, 133, 1264, 1274, 1275,
 1286, 1287, 1364, 1365, 1380,
 1382, 1557, 1558, 2347, 2348,
 2354, 2355, 2361, 2362, 2369,
 2370, 2377, 2410, 2411, 2440,
 2441, 3525, 3795, 3796, 3797,
 4466, 4516, 4518, 4536, 4538,
 4540, 4546, 4547, 4563, 4588,
 4589, 4603, 4622, 4624, 4629,
 4640

`\get@cdp` 4353
`\getanddefine@fonts` 4300, 4324
`\Gin@boolkey` 2263
`\glb@currsiz` 4418
`\global` 73, 74, 139, 149, 150,
 151, 152, 153, 154, 155, 156,
 164, 1293, 1294, 1313, 1668,
 1672, 1992, 2081, 3704, 3705,
 3706, 3707, 3708, 3709, 3710,
 3711, 3712, 3713, 4306, 4332
`\globaldefs` 4301, 4325
`\glossary` 1303
`\glsaddprotectedpagefmt` . 1340,
 1341, 1342
`\goodbreak` 4282
`\grid` 3486, 3490, 3752
`\Grot@x` .. 2271, 2272, 2273, 2274
`\Grot@y` .. 2275, 2276, 2277, 2278,
 2279, 2280
`\group` 2256
`\group@elt` 4352
`\group@list` 4352
`\grp@aligned` 155
`\GRP@box` 150
`\grp@eqs@numbered` 154
`\grp@hasNumber` 159
`\GRP@label` 151
`\grp@linewidth` 153
`\GRP@queue` 150
`\grp@setnumber` 159
`\grp@shiftnumber` 156
`\grp@wdL` 152
`\grp@wdNum` 153
`\grp@wdR` 152
`\grp@wdT` 152

H

`\harfi` 1190, 1551, 2383, 2417, 2447,
 2914
`\harfinumeral` 2915
`\hbox` 1819, 2822, 2880, 2881
`\headDateTimeFormat` 3551, 3553
`\headerfont` 4516
`\headheight` 1309, 3785
`\heading` 3574
`\headrulewidth` 3786, 3842



<code>\headsep</code>	1310		1888, 1890, 1891, 1892, 1893,
<code>\headtoname</code>	2899		1894, 1897, 1898, 1899, 1900,
<code>\height</code>	2275, 2276		1901, 1902, 1997, 2027, 2045,
<code>\hfil</code> .	1815, 1816, 1817, 1818, 1850,		2055, 2061, 2062, 2123, 2139,
	1851, 1852, 1858, 1859, 1860		2171, 2191, 2197, 2199, 2209,
<code>\hline</code> ...	4235, 4557, 4558, 4561,		2217, 2219, 2241, 2271, 2272,
	4562, 4582, 4583		2273, 2274, 2275, 2276, 2277,
<code>\hrule</code>	1405, 4118, 4124, 4171, 4177,		2278, 2279, 2280
	4222, 4262	<code>\if@bidi@algorithmicloaded@</code> .	
<code>\hrulefill</code> ...	3800, 3805, 3819		1449
<code>\hsize</code>	1335, 1676, 1692, 1717, 1718,	<code>\if@bidi@algorithmloaded@</code>	1452
	1916, 1926	<code>\if@bidi@backrefloaded@</code> .	1455
<code>\hskip</code>	1405, 1817, 1818, 1860	<code>\if@bidi@csprimitive</code>	1471
<code>\hspace</code> ..	3553, 3571, 3800, 3806,	<code>\if@bidi@csundef</code>	2874, 3127, 3177
	3818, 3820, 3998	<code>\if@bidi@enumerateloaded@</code>	1458
<code>\hss</code>	1704	<code>\if@bidi@tocloftloaded@</code> ..	1461
<code>\Huge</code>	3523, 3592, 3648	<code>\if@bidi@urlloaded@</code>	1464
<code>\huge</code>	3522	<code>\if@chapter@pp</code>	28
<code>\Hy@AlphNoErr</code>	1380, 1382	<code>\if@extrafootnotefeatures</code>	3394
<code>\Hy@appendixstring</code> .	1366, 1384	<code>\if@files</code>	2821
<code>\Hy@backout</code>	69, 77	<code>\if@hboxRconstruct</code> ..	1689, 1711
<code>\Hy@chapapp</code>	1366, 1384	<code>\if@inlabel</code>	139
<code>\HyOrg@appendix</code>	1361, 1367	<code>\if@Kashida@on</code>	1403, 1404
<code>\HyOrg@resets@pp</code> ...	1377, 1385	<code>\if@LTRbibitems</code>	3173
<code>\hyper@natlinkbreak</code>	2014, 2045	<code>\if@newlist</code> ...	1293, 1313, 1936
<code>\hyper@natlinkstart</code>	77	<code>\if@nonlatin</code> ...	4500, 4501, 4502
		<code>\if@noskipsec</code>	138
		<code>\if@pboxsw</code>	1706
		<code>\if@RTL</code>	2, 3, 5,
<code>\if</code>	140, 159, 1629,		7, 63, 92, 136, 148, 161, 1330,
	1635, 1641, 1644, 1647, 1650,		1332, 1334, 1344, 1345, 1346,
	1653, 1656, 1659, 1690, 1697,		1347, 1348, 1349, 1350, 1351,
	1698, 1699, 1700, 1712, 1729,		1352, 1353, 1354, 1355, 1356,
	1730, 1731, 1732, 1733, 1734,		1357, 1358, 1359, 1439, 1440,
	1735, 1736, 1737, 1738, 1752,		1562, 1563, 1564, 1565, 1566,
	1753, 1754, 1755, 1756, 1757,		1567, 1568, 1569, 1570, 1690,
	1759, 1760, 1761, 1762, 1763,		1712, 2489, 2490, 2491, 2492,
	1766, 1767, 1768, 1769, 1770,		2493, 2494, 2495, 2496, 2497,
	1771, 1786, 1787, 1788, 1789,		2498, 2882, 2883, 2884, 2885,
	1790, 1791, 1793, 1794, 1795,		2886, 2887, 2888, 2889, 2890,
	1796, 1797, 1798, 1799, 1802,		2891, 2892, 2893, 2894, 2895,
	1803, 1804, 1805, 1806, 1807,		2896, 2897, 2898, 2899, 2900
	1830, 1831, 1832, 1833, 1834,	<code>\if@RTL@footnote</code> ...	1278, 1319
	1835, 1837, 1838, 1839, 1840,	<code>\if@RTLmain</code>	2828
	1841, 1842, 1875, 1876, 1877,	<code>\if@RTLtab</code>	1731, 1732, 1733, 1734,
	1878, 1879, 1880, 1881, 1882,		1754, 1755, 1756, 1757, 1788,
	1883, 1884, 1885, 1886, 1887,		



1789, 1790, 1791, 1832, 1833, 1834, 1835, 1877, 1878, 1879, 1880	3139, 3153, 3157, 3161, 3164, 4129, 4203, 4249, 4274, 4297, 4321, 4685, 4689, 4717, 4723, 4744, 4771, 4775, 4780, 4784, 4786, 4795
\if@tempswa 2114	\ifodd . . . 1630, 1636, 4678, 4683
\if@twoside 2403	\ifthenelse 3472, 3484, 3493, 3597, 3612, 3631, 3652, 3770, 3848, 3849, 3879, 3911, 3925, 3945, 3963, 3987, 4017, 4041, 4068, 4097, 4102, 4107, 4112, 4117, 4150, 4155, 4160, 4165, 4170, 4564
\if@xepersian@@computeautoilg 2830, 3399	\ifwritexviii . 2573, 3307, 3319, 3331
\ifadl@usingarypkg 1776	\ifx . . . 1190, 1191, 1192, 1193, 1194, 1195, 1196, 1197, 1198, 1199, 1200, 1411, 1606, 1609, 1693, 1913, 1923, 2000, 2001, 2003, 2030, 2031, 2033, 2102, 2120, 2180, 2229, 2268, 2381, 2383, 2384, 2385, 2386, 2387, 2388, 2389, 2390, 2391, 2392, 2393, 2394, 2395, 2396, 2397, 2415, 2417, 2418, 2419, 2420, 2421, 2422, 2423, 2424, 2425, 2426, 2427, 2428, 2429, 2430, 2431, 2445, 2447, 2448, 2449, 2450, 2451, 2452, 2453, 2454, 2455, 2456, 2457, 2458, 2459, 2460, 2461, 2556, 2564, 4294, 4318, 4461, 4469, 4470, 4471, 4472, 4473, 4474, 4475, 4476, 4477, 4478, 4479, 4493, 4496, 4497, 4498, 4500, 4501, 4502
\ifBR@verbose 66	\ifXePersian@kabiseh 4646, 4751
\ifcase . . . 1814, 1845, 1849, 1853, 1857, 1996, 2026, 2119, 2902, 2911, 2939, 3002, 3008, 3011, 3014, 3018, 3040, 3107, 3112, 3119, 3151, 3155, 3159, 3163, 3224, 3232, 3239, 3247, 3254, 3261, 3267, 3279, 3285, 3291, 3295, 3299, 3305, 3318, 3330, 3342, 3361, 3368, 4807	\ifXePersian@leap . . 4646, 4695
\ifdim 169, 2535, 2541, 2547, 2839, 2840, 2844, 2845, 2850, 2851, 2855, 2856, 2865, 3405, 3409, 3732, 4217	\IfxepersianPackageVersion 2546
\iffontchar 2838	\IfxepersianPackageVersionBefore 2540
\ifhmode 1613	\IfxepersianPackageVersionLater 2534
\ifinner 1619	\ifxetex 3725, 3948, 3965
\ifmmode 1701, 4296, 4320	\ignorespaces 173, 1918, 1928, 2597, 2613, 2692,
\ifNAT@full 1994, 2083	
\ifNAT@longnames . . . 1990, 2079	
\ifNAT@numbers 1943, 2150	
\ifNAT@super 1944	
\ifNAT@swa 1996, 2061, 2085, 2137	
\ifnum 170, 1660, 1727, 1728, 1744, 1745, 1746, 1747, 1749, 1778, 1779, 1780, 1781, 1783, 1828, 1829, 1867, 1868, 1869, 1870, 1872, 2471, 2574, 2863, 2929, 2931, 2940, 2941, 2942, 2943, 2944, 2945, 2946, 2947, 2964, 2966, 2968, 2970, 2972, 2977, 2988, 2989, 2991, 2993, 2994, 2997, 3030, 3032, 3041, 3042, 3043, 3044, 3045, 3046, 3047, 3048, 3065, 3067, 3069, 3071, 3073, 3078, 3089, 3090, 3092, 3094, 3095, 3097, 3102, 3129, 3131, 3133, 3135, 3137,	



2709, 2726, 2743, 2760, 2777, 3543, 3596, 3606, 3611, 3619, 3624, 3630, 3638, 3898, 3924, 4073	\itemautorefname 1346
\image 3720	\itshape 4602
\immediate 2821, 3310, 3311, 3322, 3323, 3334, 3335	J
\includegraphics . . . 3735, 3949, 3966	\jobname . . 3311, 3312, 3323, 3324, 3335, 3336
\index 1302	K
\indexEntryFormat . . 3541, 3543	\KashidaOff 1436
\indexEntryPageFormat . . . 3547, 3549	\KashidaOn 1435, 1437
\indexEntryPageTxt . . 3546, 3549	\kern 1948, 2881
\indexEntrySeparator 3545, 4073	\keyval@eq@alias@key 1474, 1478
\indexFormat 3537, 3539	L
\indexitem 4066, 4076, 4077, 4079	\l 2589, 2595, 2605, 2611, 2627, 2641, 2684, 2690, 2701, 2707, 2718, 2724, 2735, 2741, 2752, 2758, 2769, 2775
\indexname 2888	\label . . . 1301, 4202, 4248, 4272
\init@restore@version . . . 4303, 4351	\LARGE . . . 3521, 3608, 3672, 3675, 3688, 3690
\innerAuthorFormat . . 3669, 4186	\Large . . . 3520, 3627, 3677, 3804, 4087, 4121
\innerPlaceFormat . . 3670, 4186	\large 3519, 3531, 3537, 3617, 3636, 3659, 3679, 3692, 3698, 3810
\innerSubtitleFormat 3659, 3660	\LastFrameCommand 1333
\innerTextFinalMark 3671, 4207	\lastpenalty 170
\innerTitleFormat . . 3648, 3653, 3654	\lastskip 169
\input 1482, 1483, 1484, 1485, 1486, 1487, 1488, 3181, 3182, 3183, 3184, 3185, 3186, 3187, 3188, 3189, 3190, 3191, 3192, 3193, 3194, 3195, 3196, 3197, 3198, 3199, 3200, 3201, 3202, 3203, 3204, 3205, 3206, 3207, 3208, 3209, 3210, 3211, 3212, 3213, 3214, 3215, 3216, 3217, 3218, 3219, 3220, 3221, 3222, 3292, 3296, 3395, 3396	\latin 2798
\insert@column . . 1816, 1817, 1818, 1819, 1821, 1822	\LatinAlphs . . . 2798, 2802, 3168
\int . 4378, 4386, 4394, 4402, 4410	\Latincite 2146, 2814
\intermath@penalty 172	\latinfont 2603, 2784, 2786, 3355
\iranicdefault 2649, 2661, 2766, 2774	\latintoday 2805
\iranicfamily . . 2659, 2660, 2673, 2767	\lccode 2165, 2166, 2167
\item 4590, 4591, 4592, 4593	\leaders 1405
	\leavevmode 138, 139, 1687, 1709, 1936, 2816, 2880
	\leftfootnoterule 3270
	\let 11, 19, 73, 74, 149, 151, 154, 155, 156, 162, 167, 1198, 1199, 1200, 1201, 1291, 1293, 1301, 1302, 1303, 1313, 1316, 1361, 1371, 1372, 1377, 1392, 1411, 1413, 1680, 1681, 1682, 1683, 1684, 1685, 1704, 1721, 1722, 1723, 1724, 1793, 1794,



\MessageBreak
... 2005, 2006, 2035, 2036,
3178, 3870, 3902, 3936, 3956,
3977, 3980, 4002, 4027, 4053,
4076, 4079, 4568
\MidFrameCommand 1331
\minilogo 3809, 4023
\minraggedcols 3448, 3449, 3487,
3491, 4129, 4203, 4249, 4274
\mlfttitle 1566
\mltttitle 1567
\month 4672
\moveright 1307
\mtctitle 1565
\multido 3771, 3777
\multiply 1666, 4675, 4688, 4715,
4721, 4738, 4742
\mylogo 3814

N
\n 4466, 4469, 4470,
4471, 4472, 4473, 4474, 4475,
4476, 4477, 4478, 4479
\NAT@close 2062, 2141
\NAT@Latin@citetp 2149, 2153,
2154, 2155
\NAT@open 2045, 2121
\NAT@alias 2023, 2053, 2088, 2131
\NAT@all@names . 1991, 1994, 2080,
2083
\NAT@aysep 2015
\NAT@biblabel 1966
\NAT@biblabelnum 1957
\NAT@bibsetnum 1958
\NAT@bibsetup 1967
\NAT@cite 1963
\NAT@cite@list 1980, 2069
\NAT@citea@mbox 2114
\NAT@citenum 1951
\NAT@citesuper 1944
\NAT@citeundefined . 1985, 2075
\NAT@citex 1964
\NAT@citexnum 1955
\NAT@close 1959, 1970
\NAT@cmprs 2090, 2136
\NAT@cmt 2061, 2139

\NAT@ctype 1996, 2026, 2086, 2088,
2119, 2127, 2129, 2138, 2147
\NAT@date 1970,
1987, 1997, 1998, 2009, 2017,
2022, 2027, 2040, 2047, 2052,
2055, 2062
\NAT@def@citea . 2024, 2056, 2117
\NAT@def@citea@box 2125
\NAT@def@citea@close 2058
\NAT@exlab 2003, 2007, 2033, 2037
\NAT@fullfalse 2148
\NAT@fulltrue 2148
\NAT@hyper@ 1998, 2007, 2009, 2012,
2021, 2022, 2023, 2028, 2037,
2040, 2043, 2051, 2052, 2053,
2088, 2124
\NAT@hyper@citea@space .. 2127,
2129, 2131
\NAT@idtxt 1959, 1970
\NAT@ifcat@num 2091, 2094
\NAT@last@nm .. 1988, 2000, 2030,
2077, 2120
\NAT@last@num . 2077, 2094, 2095,
2113
\NAT@last@yr ... 1988, 2001, 2031,
2068, 2102, 2136
\NAT@last@yr@mbox .. 2098, 2108
\NAT@Latin@cites ... 2148, 2149
\NAT@Latin@citex 1965, 1973, 1974
\NAT@Latin@citexnum 1956, 2063,
2064
\NAT@mbox . 1945, 1950, 2121, 2124,
2141
\NAT@merge 2098, 2113
\NAT@name . 1959, 1970, 1991, 1995,
2080, 2084
\NAT@nm 1979, 1988, 1994,
1995, 1998, 2000, 2013, 2021,
2028, 2030, 2044, 2051, 2068,
2077, 2083, 2084, 2092, 2093,
2097, 2101, 2120
\NAT@nmfmt 1998, 2013, 2021, 2028,
2044, 2051
\NAT@num . 1959, 2068, 2077, 2091,
2092, 2113, 2124
\NAT@open 1959, 1970



<code>\NAT@parse</code>	1989, 2078		3542, 3545, 3546, 3547, 3548,
<code>\NAT@partrue</code>	2147		3551, 3552, 3556, 3557, 3560,
<code>\NAT@penalty</code> . . .	1961, 1969, 2105,		3561, 3562, 3563, 3566, 3569,
	2120		3574, 3579, 3582, 3584, 3587,
<code>\NAT@reset@citea</code> . . .	1978, 2067		3592, 3593, 3604, 3605, 3608,
<code>\NAT@reset@parser</code> . .	1976, 2065		3609, 3617, 3618, 3621, 3622,
<code>\NAT@set@cites</code>	1942, 2145		3627, 3628, 3636, 3637, 3639,
<code>\NAT@sort@cites</code>	1977, 2066		3640, 3641, 3642, 3645, 3646,
<code>\NAT@space</code> 1947, 1952, 1968, 2120			3648, 3649, 3659, 3660, 3661,
<code>\NAT@spacechar</code>	1952,		3662, 3663, 3664, 3669, 3670,
	1959, 1968, 1970, 2008, 2015,		3671, 3672, 3673, 3674, 3675,
	2039, 2045, 2121, 2123		3676, 3677, 3678, 3679, 3680,
<code>\NAT@super@kern</code> 1948, 1953, 2121			3715, 3720, 3752, 3784, 3798,
<code>\NAT@swafalse</code>	2151		3809, 3814, 3822, 3846, 3877,
<code>\NAT@swatrue</code>	2147		3909, 3943, 3962, 4066, 4084,
<code>\NAT@temp</code> 2002, 2003, 2032, 2033			4091, 4133, 4141, 4184, 4190,
<code>\NAT@test</code> . 2088, 2121, 2127, 2129			4210, 4227, 4256, 4281, 4365,
<code>\NAT@year</code> . 1979, 1988, 2001, 2031			4366, 4368, 4461, 4462, 4516,
<code>\NAT@yrsep</code> . . . 2000, 2030, 2120			4518, 4524, 4527, 4529, 4532,
<code>\natexlab</code>	1960, 1971		4536, 4538, 4540, 4588, 4589,
<code>\navardefault</code> . 2650, 2664, 2715,			4594, 4598, 4603, 4622, 4624,
	2723		4800
<code>\navarfamily</code> . . 2662, 2663, 2674,		<code>\newcount</code> 2831, 3444, 3445, 3448,	
	2716		3750, 3751, 4647, 4648, 4649,
<code>\NeedsTeXFormat</code> 2499, 3419, 4288,			4650, 4651, 4652, 4653, 4654,
	4506, 4643		4655, 4656, 4657, 4658, 4659,
<code>\new@mathalphabet</code>	4354		4660, 4662, 4663, 4664, 4665,
<code>\new@mathbf</code>	4376, 4438		4666, 4667, 4668, 4669
<code>\new@mathgroup</code> . 4291, 4292, 4347		<code>\newcounter</code>	4541, 4542
<code>\new@mathit</code>	4384, 4439	<code>\newdimen</code> 2832, 2833, 3748, 3749	
<code>\new@mathrm</code>	4392, 4440	<code>\NewDocumentCommand</code> 4376, 4384,	
<code>\new@mathsf</code>	4400, 4448		4392, 4400, 4408
<code>\new@mathtt</code>	4408, 4457	<code>\newenvironment</code>	
<code>\new@mathversion</code>	4352		. . . 1472, 2159, 2160, 2802,
<code>\new@symbolfont</code>	4353		2803, 3717, 3823, 3985, 4015,
<code>\newboolean</code> . . 3430, 3432, 3434,			4039, 4193, 4242, 4268, 4570,
	3436, 3438, 3440, 3442		4604
<code>\newcolumntype</code>	4520, 4521	<code>\newfam</code>	4292
<code>\newcommand</code>	1435, 1436,	<code>\newfontface</code>	2467
	1469, 1471, 1472, 1474, 1478,	<code>\newfontlanguage</code>	2580
	1973, 2063, 2149, 2154, 2477,	<code>\newfontscript</code>	2579
	2534, 2540, 2546, 2647, 2648,	<code>\newif</code> . . . 1403, 2573, 2830, 4646	
	2649, 2650, 2651, 2652, 2835,	<code>\newlength</code> 3422, 3423, 3424, 3425,	
	2873, 2916, 2919, 3022, 3025,		3426, 3428, 4534, 4625, 4627
	3427, 3482, 3526, 3527, 3530,	<code>\newmathalphabet</code>	4348
	3531, 3532, 3537, 3538, 3541,	<code>\newmathalphabet@</code>	4348



1269, 1550, 2404
 \pageref 3571, 4069
 \pagesFormat 3645, 3647
 \pagestyle 3788
 \pagetotal 4213
 \par 10, 17, 24,
 40, 46, 52, 58, 99, 110, 117,
 129, 787, 1261, 1271, 1283,
 1391, 1554, 2344, 2351, 2358,
 2366, 2374, 2407, 2437, 3688,
 3690, 3696, 3698, 3699, 4188,
 4273, 4576, 4636
 \paragraphautorefname ... 1355
 \parallel 3553
 \parbox 4575, 4635
 \partautorefname 1349
 \partname 2891
 \PassOptionsToClass 3450, 3451,
 3452
 \pbs 4519, 4520
 \pdfstringdefDisableCommands .
 1370
 \penalty 166, 172, 1961, 2819
 \persian 2800
 \PersianAlphs . 2800, 2803, 3343,
 3348, 3418
 \persianday 4806
 \persianfont ... 2587, 2791, 2793
 \PersianMathsDigits 3229, 4495
 \persianmathsdigits 4425, 4496,
 4500
 \persianmathsfdigits 4448, 4497,
 4501
 \persianmathttdigits 4457, 4498,
 4502
 \persianmonth 4805
 \persiansfdefault .. 2647, 2655,
 2681, 2689
 \persiansffamily ... 2653, 2654,
 2671, 2682
 \persiantoday 2806, 4800
 \persianttdefault .. 2648, 2658,
 2698, 2706
 \persianttfamily ... 2656, 2657,
 2672, 2699
 \persianyear 4804
 \pictureCaptionFormat ... 3641,
 3643
 \plftitle 1563
 \plq 2553
 \plttitle 1564
 \pookdefault .. 2651, 2667, 2732,
 2740
 \pookfamily .. 2665, 2666, 2675,
 2733
 \postmath 172
 \PrefixCurrentTab 2477
 \premath 168
 \prepnext@tok 1813, 1823
 \printindex .. 3309, 3321, 3333
 \process@table 4351
 \ProcessOptions 3464, 4642
 \ProcessOptionsX 3392
 \proofname 2900
 \protect . 1291, 3870, 3871, 3873,
 3902, 3903, 3905, 3936, 3937,
 3939, 3956, 3957, 3959, 3977,
 3978, 3980, 4076, 4077, 4079,
 4525, 4528, 4530, 4533, 4551,
 4556, 4557, 4558, 4560, 4561,
 4562, 4582, 4583
 \protected@write ... 3370, 3374
 \providecommand 3124
 \ProvidesClass 3420
 \ProvidesFile 1, 4, 8,
 14, 23, 38, 44, 50, 56, 62, 82,
 91, 93, 104, 115, 123, 135, 175,
 1128, 1188, 1205, 1248, 1259,
 1265, 1277, 1281, 1288, 1317,
 1325, 1339, 1343, 1388, 1395,
 1438, 1441, 1468, 1548, 1561,
 1571, 1941, 2342, 2349, 2356,
 2364, 2372, 2401, 2435, 2465,
 2468, 2488
 \ProvidesPackage ... 2502, 4289,
 4507, 4644
 \prq 2552
 \ptctitle 1562
 Q
 \question 4630



`\questionsepspace` . . 4627, 4628, 4640
`\questionspace` 4534, 4535, 4576
`\questiontitle` 4622, 4641
`\questiontitlefont` 4624
`\questiontitlespace` 4625, 4626, 4636

R

`\raggedFormat` . 3482, 4130, 4204, 4250, 4275
`\RaggedLeft` 3482
`\raisebox` 3528, 3533
`\refname` 92, 2889
`\refstepcounter` 4592, 4593
`\relax` 1469, 1661, 1693, 1828, 1829, 1850, 1851, 1852, 1913, 1923, 1947, 1953, 1997, 2027, 2055, 2062, 2068, 2095, 2102, 2113, 2268, 2381, 2415, 2445, 2466, 2471, 2556, 2574, 2868, 3224, 3232, 3239, 3247, 3254, 3261, 3267, 3279, 3285, 3291, 3295, 3299, 3305, 3318, 3330, 3342, 3361, 3368, 3377, 3378, 3401, 3403, 3464, 3683, 3704, 3705, 3710, 3711, 3712, 3713, 4294, 4308, 4318, 4334, 4367, 4369, 4379, 4387, 4395, 4403, 4411, 4418, 4492, 4674, 4675, 4677, 4682, 4687, 4688, 4694, 4696, 4698, 4700, 4701, 4702, 4703, 4704, 4705, 4706, 4707, 4708, 4709, 4710, 4712, 4714, 4715, 4720, 4721, 4728, 4730, 4733, 4737, 4738, 4741, 4742, 4745, 4750, 4752, 4754, 4756, 4757, 4758, 4759, 4760, 4761, 4762, 4763, 4764, 4765, 4766, 4767, 4769, 4770, 4773, 4778, 4782, 4788, 4790, 4791
`\renewcommand` . . 9, 16, 24, 30, 31, 34, 39, 40, 45, 46, 51, 52, 57, 58, 86, 88, 94, 95, 99, 105, 106, 110, 116, 117, 124, 128, 129, 1260, 1261, 1266, 1270, 1271, 1278, 1279, 1280, 1282, 1283, 1319, 1321, 1323, 1390, 1549, 1551, 1552, 1553, 1554, 1942, 1959, 1970, 2343, 2344, 2350, 2351, 2357, 2358, 2365, 2366, 2373, 2374, 2380, 2402, 2406, 2407, 2414, 2436, 2437, 2444, 2469, 2489, 2490, 2491, 2492, 2493, 2494, 2495, 2496, 2497, 2498, 2828, 3172, 3309, 3321, 3333, 3494, 3501, 3503, 3505, 3512, 3519, 3520, 3521, 3522, 3523, 3575, 3576, 3577, 3588, 3589, 3590, 3681, 3786, 3822, 3842, 4181, 4191, 4196, 4523
`\renewenvironment` . . 1326, 4632
`\repeat` 2863, 4775, 4784
`\RequirePackage`
. 2504, 2505, 2506, 2507, 3421, 3466, 3467, 3468, 3469, 3470, 3471, 3473, 3475, 3477, 3478, 3479, 3480, 3481, 4509, 4510, 4511, 4512, 4513, 4514
`\reserved@a` 1625, 1629, 1635, 1641, 1644, 1647, 1650, 1653, 1656, 1659
`\reserved@b` 1605, 1606
`\reset@font` . . . 1300, 1985, 2074, 2785, 2792, 2808, 2822
`\resetlatinfont` 84, 86, 1278, 1279, 1319, 1321, 2782, 2796, 2798, 2802, 2809, 2828, 3174
`\restore@mathversion` 4351
`\restoreapp` 36
`\rightfootnoterule` 3272
`\rightline` 4185
`\rl` 1372, 2797, 2806
`\RLE` 2797
`\rmdefault` 2586, 2594, 2610
`\Roman` . . . 1196, 2388, 2422, 2452
`\roman` . . . 1195, 2389, 2423, 2453
`\romannumeral` . . 2397, 2431, 2461, 4774, 4783, 4793
`\RTL` 2800
`\RTLfoottextfont` 1280



`\rule` 3545, 3671, 3773, 3779, 3866, 3898
S
`\sayehdefault` . 2652, 2670, 2749, 2757
`\sayehfamily` . . 2668, 2669, 2676, 2750
`\scriptsize` 3503
`\secondarticle` 3877, 3902, 3903, 3905
`\secondSubtitleFormat` 3617, 3619
`\secondTextFormat` . . 3621, 3624
`\secondTitleFormat` . 3608, 3613, 3614
`\section` 2876
`\sectionautorefname` 1352
`\sectionname` 11, 1392
`\select@group` 4293
`\selectfont` 2591, 2607, 2628, 2642, 2655, 2658, 2661, 2664, 2667, 2670, 2686, 2703, 2720, 2737, 2754, 2771, 2788, 2795, 2869
`\set@@mathdelimiter` 4358
`\set@fontsize` 3400
`\set@mathaccent` 4355
`\set@mathchar` 4355
`\set@mathdelimiter` 4357
`\set@mathsymbol` 4356
`\set@typeset@protect` 1295, 1299
`\setboolean` 2478, 2479, 3431, 3433, 3435, 3437, 3439, 3441, 3443, 3459, 3460, 3462, 3463, 3825, 3843, 3988, 4013, 4042, 4064
`\setbox` 150, 1672, 1715, 1819, 1821, 1822, 1912, 1915, 1922, 1925
`\setclass` . . 1407, 1417, 1418, 1419, 1420, 1421, 1422, 1423, 1424
`\setcounter`
. . 27, 29, 33, 41, 42, 47, 48, 53, 54, 59, 60, 100, 101, 111, 112, 118, 119, 130, 131, 1262, 1263, 1272, 1273, 1284, 1285, 1315, 1555, 1556, 2345, 2346, 2352, 2353, 2359, 2360, 2367, 2368, 2375, 2376, 2408, 2409, 2438, 2439, 2472, 2476, 2480, 2481, 2482, 2483, 2484, 2485, 2486, 3703, 4545
`\setdigitfont` 4416
`\setiranicfont` 2763
`\setkeys` 141, 158
`\setlatinmonofont` 2617
`\setlatinsansfont` 2616
`\setlatintextfont` . . 2600, 3417
`\setlength` 1691, 1694, 1713, 3429, 3461, 3496, 3497, 3498, 3499, 3507, 3508, 3509, 3510, 3514, 3515, 3516, 3517, 3722, 3726, 3767, 3768, 3785, 3790, 3791, 3915, 3947, 4019, 4044, 4047, 4095, 4096, 4144, 4145, 4211, 4212, 4228, 4535, 4626, 4628
`\setLTRcitationfont` 84
`\SetMathAlphabet` 4354
`\SetMathAlphabet@` 4354
`\SetMathCharDef` 4368, 4437
`\SetMathCode`
. . 4366, 4426, 4427, 4428, 4429, 4430, 4431, 4432, 4433, 4434, 4435, 4436
`\SetMathsDigits` 4494, 4495, 4499, 4504, 4505
`\setmathsfdigitfont` 4444
`\setmathttdigitfont` 4453
`\setmonofont` 2617
`\setnavarfont` 2712
`\setpersianfont`
88, 1280, 1323, 2789, 2797, 2800, 2803, 2828
`\setpersianmonofont` 2695
`\setpersiansansfont` 2678
`\setpookfont` 2729
`\setsansfont` 2616
`\setsayehfont` 2746
`\SetSymbolFont` 4353
`\SetSymbolFont@` 4353
`\setttextfont` 2583, 3179
`\setthesection` 1551
`\sffamily` 3526
`\shadowbox` 4098, 4151



<code>\shadowsize</code> . . .	4096, 4145, 4149	<code>\tablename</code>	2883
<code>\shipout</code>	1295	<code>\tabularxcolumn</code>	4523
<code>\shortarticleitem</code>	4281	<code>\tartibi</code>	1192, 2385, 2419, 2449, 3022
<code>\shortarticleItemTitleFormat</code>	3679, 3680	<code>\tartibinumeral</code>	3028
<code>\shortarticleSubtitleFormat</code>	3677, 3678	<code>\test</code>	1410, 1411, 1412
<code>\shortarticleTitleFormat</code>	3675, 3676	<code>\textbf</code> 2, 3, 1328, 1330, 1332, 1334, 4087, 4121, 4136, 4174	
<code>\sixin@n</code>	1624, 1661	<code>\textblockorigin</code>	3747
<code>\slftitle</code>	1569	<code>\textdegree</code>	3561
<code>\sltttitle</code>	1570	<code>\textheight</code>	3754, 3779
<code>\small</code> 2877, 3505, 3506, 3560, 3564, 3570, 3641, 3663, 3682		<code>\textiranic</code>	2673
<code>\smash</code>	2880	<code>\textit</code>	3672
<code>\SOUL@tt</code>	2466, 2467	<code>\textnavar</code>	2674
<code>\space</code>	1987, 2076, 2502, 2825, 3131, 3729, 3730, 3870, 3871, 3873, 3902, 3903, 3905, 3936, 3937, 3939, 3956, 3957, 3959, 3977, 3978, 3980, 4076, 4077, 4079, 4186, 4566, 4801, 4802	<code>\textpersiansf</code>	2671
<code>\SplitFootnoteRule</code>	3274	<code>\textpersiantt</code>	2672
<code>\stctitle</code>	1568	<code>\textpook</code>	2675
<code>\stepcounter</code> 26, 1314, 2474, 4541, 4554, 4585		<code>\textsayeh</code>	2676
<code>\str</code>	2594, 2610, 2689, 2706, 2723, 2740, 2757, 2774	<code>\textsc</code>	3674
<code>\string</code> 67, 1750, 1784, 1873, 2242, 2821, 3371, 3375		<code>\textsuperscript</code>	1945
<code>\strip@pt</code>	2868	<code>\texttt</code>	3531
<code>\subparagraphautorefname</code>	1356	<code>\textwidth</code> 1718, 3753, 3773, 4085, 4572	
<code>\subsectionautorefname</code>	1353	<code>\textwidthfootnoterule</code>	3276
<code>\subsubsectionautorefname</code>	1354	<code>\thanks</code>	3684, 3704
<code>\symnew@mathbf@font@digits</code>	4379	<code>\the</code>	137, 142, 1405, 1695, 2193, 2198, 2204, 2211, 2221, 2235, 2531, 2839, 2840, 2841, 2844, 2845, 2846, 2850, 2851, 2852, 2855, 2856, 2857, 3729, 3730, 4215, 4504, 4505, 4774, 4783, 4793
<code>\symnew@mathit@font@digits</code>	4387	<code>\the@choice</code>	4544, 4566
<code>\symnew@mathrm@font@digits</code>	4395	<code>\thebook</code>	1552
<code>\symnew@mathsf@font@digits</code>	4403	<code>\thechapter</code> 20, 31, 103, 114, 121, 133, 1275, 1287, 1551, 1558, 2348, 2355, 2362, 2370, 2411, 2441	
<code>\symnew@mathtt@font@digits</code>	4411	<code>\theHchapter</code>	1305, 1382
		<code>\theHsection</code>	1364, 1380
		<code>\thempfn</code>	1720
		<code>\thempfootnote</code>	1720
		<code>\theoremautorefname</code>	1358
		<code>\thepage</code>	1987, 2004, 2034, 2076, 2825, 3571
		<code>\thepart</code>	9, 16, 39, 45,

T



51, 57, 94, 105, 116, 128, 1260,
 1270, 1282, 1390, 1553, 2343,
 2350, 2357, 2365, 2373, 2406,
 2436
 \thequestion . . . 4565, 4605, 4641
 \thesection 12, 34, 43, 49, 55, 61,
 1264, 1393, 2377
 \thirdarticle . 3909, 3936, 3937,
 3939
 \thirdSubtitleFormat 3636, 3638
 \thirdTextFormat . . . 3639, 3640
 \thirdTitleFormat . . 3627, 3632,
 3633
 \thispagestyle 3826, 3831
 \thr@@ 1747, 1766, 1767, 1781, 1802,
 1803, 1829, 1841, 1842, 1870,
 1897, 1898
 \timestamp 3664, 3861, 3891, 3927
 \timestampFormat . . . 3663, 3665
 \timestampSeparator 3662, 3667
 \timestampTxt 3661, 3666
 \tiny 3501
 \title 3710
 \TitleBarFrame . 1328, 1330, 1332,
 1334
 \tl 2586, 2595,
 2611, 2616, 2617, 2681, 2690,
 2698, 2707, 2715, 2724, 2732,
 2741, 2749, 2758, 2766, 2775,
 4345, 4362, 4438, 4439, 4440,
 4448, 4457
 \tmp 4519
 \today 2804, 2806, 4182
 \topmargin 1307
 \TPHorizModule
 . . 3542, 3767, 3866, 3898,
 3949, 3996, 3997, 4020, 4021,
 4044
 \TPVertModule 3768
 \true 4594
 \truesymbol 4588
 \tw@ 1405,
 1642, 1645, 1727, 1733, 1734,
 1736, 1746, 1756, 1757, 1780,
 1790, 1791, 1828, 1834, 1835,
 1840, 1869, 1879, 1880, 2088,
 2839, 2840, 2841, 2844, 2845,
 2846
 \twocolumnstableofcontents . .
 2873
 \typeout 2530, 2532, 3715

 U
 \Umathchardef 4369
 \Umathcode 4367
 \undefined 1582, 4461, 4493, 4496,
 4497, 4498, 4500, 4501, 4502
 \unhbox 1704
 \unpenalty 172
 \unskip 169, 1858, 1859, 1860, 1945,
 2008, 2039
 \unvbox 1704
 \use 2587, 2603, 2622, 2626, 2636,
 2640, 2682, 2699, 2716, 2733,
 2750, 2767
 \use@mathgroup 4304
 \usebox 3719
 \usecounter 4578

 V
 \value 2471, 4548, 4564
 \vbox 1295, 1308, 1675, 1692,
 1697, 1698, 1715, 1822, 1912,
 1916, 1922, 1926, 4258, 4284
 \vcenter 1701, 1702
 \verbatim@addtoline
 . . . 2177, 2192, 2203, 2210,
 2212, 2220, 2222, 2234, 2236
 \verbatim@finish 2230
 \verbatim@processline 2181, 2194,
 2214
 \verbatim@startline 2170, 2182,
 2195, 2215
 \version@elt 4350
 \version@list 4350
 \vfil 3685, 3701
 \voidb@x 150
 \vrb@catcodes 2164
 \vskip 1307, 1309, 1310, 3686, 3689,
 3691, 3697
 \vspace . . 3721, 3740, 3802, 3812,
 3855, 3859, 3882, 3885, 3889,



3896, 3914, 3918, 3922, 3931,
3990, 3994, 4050, 4071, 4119,
4123, 4142, 4172, 4176, 4221,
4223, 4233, 4236, 4261, 4263,
4283, 4285, 4576, 4634, 4636
\vss 1704
\vtop 1699, 1700, 1821

W

\weatherFormat 3556, 3558
\weatheritem .. 3962, 3977, 3978,
3980
\weatherTempFormat . 3560, 3970
\weatherUnits 3561, 3972
\whiledo 4548
\width 1336, 2273, 2274
\write 2821, 3311, 3323, 3335
\writexviiifalse 2577
\writexviiiittrue 2575

X

\X 4518
\x 2559, 2564
\xdef 1366, 1384, 4304, 4544, 4549,
4573, 4574, 4595, 4596, 4599,
4600
\XePersian ... 1373, 2880, 3580
\xepersian 2251, 2253
\xepersian@adadi .. 2938, 2963
\xepersian@adadi@tartibi 3039,
3064
\xepersian@A 1401, 1417, 1431, 1433
\xepersian@adadi ... 2932, 2937
\xepersian@adadi@tartibi 3033,
3038
\xepersian@cmds@temp 2554, 2572
\xepersian@coltitsize ... 3423,
4146, 4147, 4148, 4149, 4152,
4157, 4162, 4167
\xepersian@computeautoilg 2835,
3404
\xepersian@cx . 3750, 3755, 3772
\xepersian@cy .. 3751, 3756, 3778
\XePersian@d .. 4647, 4672, 4777,
4796, 4798, 4801, 4806

\xepersian@D 1398, 1419,
1420, 1421, 1422, 1426, 1427,
1428, 1430, 1431
\xepersian@dahgan .. 2996, 3017,
3100
\xepersian@dahgan@tartibi 3098,
3106
\XePersian@dn
.. 4667, 4766, 4774, 4777,
4780, 4784, 4796, 4798
\xepersian@dx . 3748, 3753, 3764,
3767
\xepersian@dy . 3749, 3754, 3765,
3768
\xepersian@edition . 3530, 3534,
3570, 3690, 3822
\xepersian@editionLogo .. 3532,
3800, 3818
\xepersian@editorialTit . 4227,
4246
\xepersian@editorialTitle 3673,
4232
\xepersian@everyjob 2531, 2532
\xepersian@firstText 3605, 3861
\xepersian@firstTitle ... 3593,
3856
\xepersian@fmbox 3716, 3718, 3719
\xepersian@footcenter ... 3582,
3589, 3841
\xepersian@footleft 3584, 3588,
3840
\xepersian@footright 3579, 3590,
3839
\xepersian@gridcolumns .. 3445,
3447, 3486, 3490
\xepersian@gridrows 3444, 3446,
3486, 3490
\xepersian@headcenter ... 3566,
3576, 3838
\xepersian@headDateTime . 3552,
3806, 3820
\xepersian@headleft 3563, 3575,
3837
\xepersian@headright 3569, 3577,
3836
\XePersian@i 4647, 4770,



4771, 4773, 4774, 4775, 4778,
 4782, 4783, 4786, 4787, 4790,
 4793, 4795
 \xepersian@ilg 2832, 2836, 2840,
 2841, 2845, 2846, 2864
 \xepersian@imgsize . 3422, 3723,
 3724, 3726, 3735, 3736
 \xepersian@incolumntitle 4133,
 4152, 4157, 4162, 4167
 \xepersian@indexEntry ... 3542,
 4069
 \xepersian@indexEntryPage 3548,
 4069
 \xepersian@indexFrameTitle ..
 3538, 4045
 \xepersian@indexwidth ... 3426,
 3545, 4044, 4048, 4049
 \xepersian@inexpandedtitle ..
 ... 4084, 4099, 4104, 4109,
 4114
 \xepersian@innerSubtitle 3660,
 4200
 \xepersian@innerTitle ... 3649,
 4199
 \XePersian@kabisehfalse . 4717,
 4723
 \XePersian@kabisehtrue .. 4723
 \xepersian@kashida 1404,
 1426, 1427, 1428, 1429, 1430,
 1431, 1432
 \xepersian@L ... 1399, 1423, 1427,
 1428, 1429, 1432, 1433
 \XePersian@latini .. 4648, 4694
 \XePersian@latinii . 4649, 4696,
 4698
 \XePersian@latiniii 4650, 4700
 \XePersian@latiniv . 4651, 4701
 \XePersian@latinix . 4656, 4706
 \XePersian@latinvi .. 4652, 4702
 \XePersian@latinvi . 4653, 4703
 \XePersian@latinvii 4654, 4704
 \XePersian@latinviii 4655, 4705
 \XePersian@latinix .. 4657, 4707
 \XePersian@latinxi . 4658, 4708
 \XePersian@latinxii 4659, 4709
 \XePersian@leapfalse 4679, 4683,
 4689
 \XePersian@leaptrue 4689, 4690
 \xepersian@localize@verbatim@
 2172,
 2173, 2175, 2183, 2196, 2205,
 2216, 2224, 2238
 \xepersian@localize@verbatim@@
 2175, 2176
 \xepersian@localize@verbatim@@@
 2178, 2179
 \xepersian@localize@verbatim@@testend
 2218, 2228
 \xepersian@localize@verbatim@rescan
 2232, 2241
 \xepersian@localize@verbatim@start
 . 2169, 2244, 2245, 2256
 \xepersian@localize@verbatim@test
 ... 2187, 2189, 2190
 \xepersian@localize@verbatim@testend
 2201, 2208
 \XePersian@m .. 4647, 4672, 4768,
 4787, 4790, 4802, 4805
 \xepersian@milyoongan ... 2965,
 2976
 \xepersian@milyoongan@tartibi
 3066, 3077
 \XePersian@mminusone 4669, 4768,
 4769, 4771, 4775
 \xepersian@ncol 3777, 3778
 \xepersian@ncolumns 3427, 4128,
 4129, 4196
 \xepersian@nrow 3771, 3772
 \xepersian@numberoutofrange .
 ... 2923, 2934, 3035
 \xepersian@numberstring . 2920,
 2928
 \xepersian@numberstring@tartibi
 3026, 3029
 \xepersian@PackageInfo .. 4365,
 4420
 \xepersian@pageleft 3425, 4212,
 4213, 4215, 4217
 \xepersian@pageneed 3424, 3726,
 3727, 3729, 3732, 4211, 4217
 \xepersian@pages ... 3646, 3881,
 3913, 4198



\XePersian@persian@month 4802,
4807
\XePersian@persiani 4648, 4748,
4749, 4779, 4796
\XePersian@persianii 4649, 4750
\XePersian@persianiii ... 4650,
4752, 4754
\XePersian@persianiv 4651, 4756
\XePersian@persianix 4656, 4761
\XePersian@persianv 4652, 4757
\XePersian@persianvi 4653, 4758
\XePersian@persianvii ... 4654,
4759
\XePersian@persianviii .. 4655,
4760
\XePersian@persianx 4657, 4762
\XePersian@persianxi 4658, 4763
\XePersian@persianxii ... 4659,
4764
\XePersian@persianxiii .. 4660,
4765
\XePersian@pictureCaption 3642,
3738, 3952
\XePersian@R ... 1400, 1418, 1430,
1432
\XePersian@sadgan
.. 2969, 2974, 2978, 2982,
2987, 3070, 3083
\XePersian@sadgan@tartibi 3075,
3079, 3088
\XePersian@say . 3715, 4195, 4215,
4218, 4220, 4244, 4270
\XePersian@secondSubtitle 3618,
3887
\XePersian@secondText ... 3622,
3891
\XePersian@secondTitle .. 3609,
3883
\XePersian@section . 3562, 3567,
4191
\XePersian@shellescape .. 2574
\XePersian@shortarticleItemTitle
..... 3680, 4284
\XePersian@shortarticleSubtitle
..... 3678, 4264
\XePersian@shortarticleTit ..
..... 4256, 4271
\XePersian@shortarticleTitle .
..... 3676, 4260
\XePersian@sn
.. 4668, 4767, 4779, 4780,
4783, 4784, 4793, 4798
\XePersian@strutilg
.. 2833, 2836, 2851, 2852,
2856, 2857, 2864, 2865, 2868,
3405, 3408
\XePersian@tartibi . 3026, 3111
\XePersian@tcl
.. 2831, 2836, 2838, 2839,
2840, 2841, 2844, 2845, 2846,
2850, 2851, 2852, 2855, 2856,
2857, 2862, 2863
\XePersian@temp
.. 4662, 4673, 4674, 4675,
4677, 4681, 4682, 4683, 4686,
4687, 4688, 4689, 4711, 4712,
4713, 4716, 4717, 4719, 4722,
4723, 4727, 4728, 4731, 4734,
4739, 4744, 4746, 4747, 4749
\XePersian@tempa
.. 3223, 3231, 3238, 3246,
3253, 3260, 3266, 3278, 3284,
3290, 3294, 3298, 3304, 3317,
3329, 3341, 3360, 3367
\XePersian@tempb
.. 3223, 3224, 3231, 3232,
3238, 3239, 3246, 3247, 3253,
3254, 3260, 3261, 3266, 3267,
3278, 3279, 3284, 3285, 3290,
3291, 3294, 3295, 3298, 3299,
3304, 3305, 3317, 3318, 3329,
3330, 3341, 3342, 3360, 3361,
3367, 3368
\XePersian@tempthree
.. 4664, 4725, 4726, 4727,
4729, 4732, 4735, 4736, 4740,
4743, 4744, 4745, 4746
\XePersian@temptwo . 4663, 4713,
4714, 4715, 4716, 4719, 4720,
4721, 4722, 4729, 4730, 4731,
4732, 4733, 4734, 4736, 4737,
4738, 4739, 4740, 4741, 4742,



4743
\XePersian@thirdSubtitle 3637,
3920
\XePersian@thirdText 3640, 3927
\XePersian@thirdTitle ... 3628,
3916
\XePersian@thirtytwo 4666, 4710,
4717
\XePersian@V 1402, 1424
\XePersian@weather . 3557, 3992
\XePersian@www 3527, 3800
\XePersian@wwwFormat 3526, 3528
\XePersian@y .. 4647, 4672, 4673,
4676, 4686, 4689, 4711, 4725,
4788, 4791, 4802, 4804
\XePersian@yekani .. 2969, 2997,
3001, 3008, 3011, 3070
\XePersian@yekanii 2920, 2982,
3007, 3083
\XePersian@yekaniiiii 2978, 3010,
3079
\XePersian@yekaniv . 2989, 3013,
3090
\XePersian@yekanv .. 3102, 3118
\XePersian@yModHundred .. 4665,
4676, 4677, 4678, 4681, 4685
\XePersian@zwj . 1396, 1404, 1405
\XePersian@date . 2501, 2502, 2518
\XePersian@Init 3483, 3784
\XePersian@version . 2500, 2502,
2518, 2533
\XeTeXcharclass 1412
\XeTeXcharglyph
... 1405, 2839, 2840, 2841,
2844, 2845, 2846, 2850, 2851,
2852, 2855, 2856, 2857
\XeTeXglyphbounds
... 1405, 2839, 2840, 2841,
2844, 2845, 2846, 2850, 2851,
2852, 2855, 2856, 2857
\XeTeXinterchartoks 1426, 1427,
1428, 1429, 1430, 1431, 1432,
1433
\XeTeXwarning 3124, 3129, 3131

Y

\y 2560, 2562, 2564
\year 4672

Z

\z 2561, 2562
\z@ 10, 18, 152, 153, 164,
166, 1306, 1391, 1620, 1720,
1724, 1729, 1730, 1738, 1748,
1752, 1753, 1758, 1772, 1782,
1786, 1787, 1792, 1808, 1830,
1831, 1842, 1860, 1871, 1875,
1876, 1889, 1903, 2090, 2136,
2138, 2147, 2271, 2272, 2279,
2280, 2836, 2839, 2844, 2850,
2855, 2964, 2966, 2968, 2972,
2988, 2991, 2997, 3065, 3067,
3069, 3073, 3080, 3092, 3102,
3131, 3153, 3157, 3161, 3164,
4723
\z@skip 1304, 1305
\ziffer@check 4467, 4468
\ziffer@dcheck 4466, 4467
\ziffer@DotOri 4464, 4467
\ZifferAn 4462, 4465
\ZifferLeer 4467, 4493

\ 1119, 1560, 2156
\ 1584, 1586, 1589, 1596
\ 1589
\ .. 1574, 1581, 1582, 1585, 1586,
1594, 1596
\ 1579, 1580, 1584, 1591
\ 1572, 1578, 1579, 1584, 1589, 1590
\ ... 1120, 1121, 1122, 1123, 1124,
1125, 1126, 1127, 1582
\ . 1584, 1585, 1590, 1591, 1593,
1594
\ 1584, 1589
\ 1584, 1585, 1590, 1594
\ 1579, 1580
\ 1584, 1586, 1591, 1596
@ \ 1573, 1577

@ \ .. 2281, 2282, 2283, 2284,



2285, 2286, 2287, 2288, 2289,
 2290, 2291, 2292, 2293, 2294,
 2295, 2296, 2297, 2298, 2299,
 2300, 2301, 2302
 @ \ 1573
 \ 1579
 \ 1573, 1577
 \ 1935, 2243
 \ 2157
 \ 1580, 1932, 1933

 \ 1572
 \ 1575
 \ 1574, 1576



8 Change History

v13.1	General: Added implementation of the package.	0	v13.5	General: Fixed the extra space after Persian decimal separator. . . .	147
v13.2	General: Replaced <code>\reflect</code> with <code>\bidi@reflect@box</code>	116	v13.6	General: Used <code>\XeTeXglyphbounds</code> to find the true height and depth of the Kashida character.	85

